axiom™



The 30 Year Horizon

Manuel Bronstein *William Burge* *Timothy Daly*
James Davenport *Michael Dewar* *Martin Dunstan*
Albrecht Fortenbacher *Patrizia Gianni* *Johannes Grabmeier*
Jocelyn Guidry *Richard Jenks* *Larry Lambe*
Michael Monagan *Scott Morrison* *William Sit*
Jonathan Steinbach *Robert Sutor* *Barry Trager*
Stephen Watt *Jim Wen* *Clifton Williamson*

Volume 10: Axiom Algebra: Domains

Portions Copyright (c) 2005 Timothy Daly

The Blue Bayou image Copyright (c) 2004 Jocelyn Guidry

Portions Copyright (c) 2004 Martin Dunstan

Portions Copyright (c) 1991-2002,
The Numerical ALgorithms Group Ltd.
All rights reserved.

This book and the Axiom software is licensed as follows:

Redistribution and use in source and binary forms, with or
without modification, are permitted provided that the following
conditions are
met:

- Redistributions of source code must retain the above
  copyright notice, this list of conditions and the
  following disclaimer.

- Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the
  following disclaimer in the documentation and/or other
  materials provided with the distribution.

- Neither the name of The Numerical ALgorithms Group Ltd.
  nor the names of its contributors may be used to endorse
  or promote products derived from this software without
  specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

Inclusion of names in the list of credits is based on historical information and is as accurate as possible. Inclusion of names does not in any way imply an endorsement but represents historical influence on Axiom development.

Cyril Alberga
George Andrews
Yurij Baransky
Gilbert Baumslag
Mark Botch
Martin Brock
William Burge
Bruce Char
Gregory V. Chudnovsky
Don Coppersmith
Gary Cornell
Timothy Daly Sr.
Jean Della Dora
Claire DiCrescendo
Martin Dunstan
Robert Edwards
Richard Fateman
Brian Ford
Constantine Frangos
Marc Gaetano
Patricia Gianni
Laureano Gonzalez-Vega
Matt Grayson
Oswald Gschnitzer
Vilya Harvey
Ralf Hemmecke
Pietro Iglio
Grant Keady
Klaus Kusche
Frederic Lehobey
Rudiger Loos
Camm Maguire
Ian Meikle
Gerard Milmeister
Michael Monagan
Mark Murray
John Nelder
Jinzhong Niu
Julian A. Padget
Susan Pelzel
Claude Quitte
Renaud Rioboo
Simon Robinson
Philip Santas
Gerhard Schneider
Fritz Schwarz
Elena Smirnova
Robert Sutor
James Thatcher
Dylan Thurston
Gregory Vanuxem
Juergen Weiss
James Wen
John M. Wiley
Stephen Wilson
Sandra Wityak

Roy Adler
Henry Baker
David R. Barton
Fred Blair
Alexandre Bouyer
Manuel Bronstein
Quentin Carpent
Cheekai Chin
Josh Cohen
George Corliss
Meino Cramer
Timothy Daly Jr.
Gabriel Dos Reis
Sam Dooley
Brian Dupee
Heow Eide-Goodman
Bertfried Fauser
Albrecht Fortenbacher
Timothy Freeman
Rudiger Gebauer
Holger Gollan
Stephen Gortler
James Griesmer
Jocelyn Guidry
Satoshi Hamaguchi
Henderson
Richard Jenks
Tony Kennedy
Bernhard Kutzler
Michel Levaud
Michael Lucks
Bob McElrath
David Mentre
Mohammed Mobarak
Marc Moreno-Maza
William Naylor
Godfrey Nolan
Michael O'Connor
Bill Page
Michel Petitot
Norman Ramsey
Jean Rivlin
Michael Rothstein
Alfred Scheerhorn
Martin Schoenert
Nick Simicich
Jonathan Steinbach
Moss E. Sweedler
Baldir Thomas
Barry Trager
Bernhard Wall
M. Weller
Thorsten Werther
Berhard Will
Shmuel Winograd
Waldemar Wiwianka

Richard Anderson
Stephen Balzac
Gerald Baumgartner
Vladimir Bondarenko
Peter A. Broadbery
Florian Bundschuh
Bob Caviness
David V. Chudnovsky
Christophe Conil
Robert Corless
Claire Di Crescenzo
James H. Davenport
Michael Dewar
Lionel Ducos
Dominique Duval
Lars Erickson
Stuart Feldman
George Frances
Korrinn Fu
Kathy Gerber
Teresa Gomez-Diaz
Johannes Grabmeier
Vladimir Grinberg
Steve Hague
Martin Hassner
Antoine Hersen
Kai Kaminski
Paul Kosinski
Larry Lambe
Howard Levy
Richard Luczak
Michael McGettrick
Victor S. Miller
H. Michael Moeller
Scott Morrison
C. Andrew Neff
Arthur Norman
Kostas Oikonomou
Jaap Weel
Didier Pinchon
Michael Richardson
Nicolas Robidoux
Martin Rubey
William Schelter
Marshall Schor
William Sit
Christine Sundaresan
Eugene Surowitz
Mike Thomas
Themos T. Tsikas
Stephen Watt
Mark Wegman
Michael Wester
Clifton J. Williamson
Robert Wisbauer
Knut Wolf

Contents

1 Chapter Overview **1**

2 Chapter A **3**
2.1 domain AFFPL AffinePlane . . . 3
2.1.1 AffinePlane (AFFPL) . . . 4
2.2 domain AFFPLPS AffinePlaneOverPseudoAlgebraicClosureOfFiniteField . . 5
2.2.1 AffinePlaneOverPseudoAlgebraicClosureOfFiniteField (AFFPLPS) . . 7
2.3 domain AFFSP AffineSpace . . . 8
2.3.1 AffineSpace (AFFSP) . . . 9
2.4 domain ALGSC AlgebraGivenByStructuralConstants . . . 12
2.4.1 AlgebraGivenByStructuralConstants (ALGSC) . . . 14
2.5 domain ALGFF AlgebraicFunctionField . . . 23
2.5.1 AlgebraicFunctionField (ALGFF) . . . 27
2.6 domain AN AlgebraicNumber . . . 32
2.6.1 AlgebraicNumber (AN) . . . 35
2.7 domain ANON AnonymousFunction . . . 37
2.7.1 AnonymousFunction (ANON) . . . 38
2.8 domain ANTISYM AntiSymm . . . 38
2.8.1 AntiSymm (ANTISYM) . . . 40
2.9 domain ANY Any . . . 45
2.9.1 Any (ANY) . . . 50
2.10 domain ASTACK ArrayStack . . . 52
2.10.1 ArrayStack (ASTACK) . . . 65
2.11 domain ASP1 Asp1 . . . 70
2.11.1 Asp1 (ASP1) . . . 71
2.12 domain ASP10 Asp10 . . . 73
2.12.1 Asp10 (ASP10) . . . 75
2.13 domain ASP12 Asp12 . . . 78
2.13.1 Asp12 (ASP12) . . . 79
2.14 domain ASP19 Asp19 . . . 81
2.14.1 Asp19 (ASP19) . . . 82
2.15 domain ASP20 Asp20 . . . 88
2.15.1 Asp20 (ASP20) . . . 89
2.16 domain ASP24 Asp24 . . . 93

2.16.1 Asp24 (ASP24) 95
2.17 domain ASP27 Asp27 97
2.17.1 Asp27 (ASP27) 99
2.18 domain ASP28 Asp28 101
2.18.1 Asp28 (ASP28) 102
2.19 domain ASP29 Asp29 107
2.19.1 Asp29 (ASP29) 108
2.20 domain ASP30 Asp30 110
2.20.1 Asp30 (ASP30) 111
2.21 domain ASP31 Asp31 114
2.21.1 Asp31 (ASP31) 115
2.22 domain ASP33 Asp33 119
2.22.1 Asp33 (ASP33) 120
2.23 domain ASP34 Asp34 121
2.23.1 Asp34 (ASP34) 123
2.24 domain ASP35 Asp35 125
2.24.1 Asp35 (ASP35) 127
2.25 domain ASP4 Asp4 131
2.25.1 Asp4 (ASP4) 132
2.26 domain ASP41 Asp41 135
2.26.1 Asp41 (ASP41) 136
2.27 domain ASP42 Asp42 141
2.27.1 Asp42 (ASP42) 142
2.28 domain ASP49 Asp49 147
2.28.1 Asp49 (ASP49) 149
2.29 domain ASP50 Asp50 152
2.29.1 Asp50 (ASP50) 153
2.30 domain ASP55 Asp55 157
2.30.1 Asp55 (ASP55) 158
2.31 domain ASP6 Asp6 163
2.31.1 Asp6 (ASP6) 164
2.32 domain ASP7 Asp7 168
2.32.1 Asp7 (ASP7) 169
2.33 domain ASP73 Asp73 172
2.33.1 Asp73 (ASP73) 174
2.34 domain ASP74 Asp74 177
2.34.1 Asp74 (ASP74) 178
2.35 domain ASP77 Asp77 183
2.35.1 Asp77 (ASP77) 184
2.36 domain ASP78 Asp78 187
2.36.1 Asp78 (ASP78) 189
2.37 domain ASP8 Asp8 192
2.37.1 Asp8 (ASP8) 193
2.38 domain ASP80 Asp80 196
2.38.1 Asp80 (ASP80) 197
2.39 domain ASP9 Asp9 201

2.39.1 Asp9 (ASP9) . . . 202
2.40 domain JORDAN AssociatedJordanAlgebra . . . 205
2.40.1 AssociatedJordanAlgebra (JORDAN) . . . 208
2.41 domain LIE AssociatedLieAlgebra . . . 211
2.41.1 AssociatedLieAlgebra (LIE) . . . 213
2.42 domain ALIST AssociationList . . . 216
2.42.1 AssociationList (ALIST) . . . 220
2.43 domain ATTRBUT AttributeButtons . . . 223
2.43.1 AttributeButtons (ATTRBUT) . . . 224
2.44 domain AUTOMOR Automorphism . . . 229
2.44.1 Automorphism (AUTOMOR) . . . 230

3 Chapter B 233
3.1 domain BBTREE BalancedBinaryTree . . . 233
3.1.1 BalancedBinaryTree (BBTREE) . . . 236
3.2 domain BPADIC BalancedPAdicInteger . . . 240
3.2.1 BalancedPAdicInteger (BPADIC) . . . 242
3.3 domain BPADICRT BalancedPAdicRational . . . 243
3.3.1 BalancedPAdicRational (BPADICRT) . . . 246
3.4 domain BFUNCT BasicFunctions . . . 248
3.4.1 BasicFunctions (BFUNCT) . . . 249
3.5 domain BOP BasicOperator . . . 251
3.5.1 BasicOperator (BOP) . . . 258
3.6 domain BSD BasicStochasticDifferential . . . 262
3.6.1 BasicStochasticDifferential (BSD) . . . 270
3.7 domain BINARY BinaryExpansion . . . 272
3.7.1 BinaryExpansion (BINARY) . . . 276
3.8 domain BINFILE BinaryFile . . . 278
3.8.1 BinaryFile (BINFILE) . . . 279
3.9 domain BSTREE BinarySearchTree . . . 282
3.9.1 BinarySearchTree (BSTREE) . . . 287
3.10 domain BTOURN BinaryTournament . . . 289
3.10.1 BinaryTournament (BTOURN) . . . 291
3.11 domain BTREE BinaryTree . . . 292
3.11.1 BinaryTree (BTREE) . . . 294
3.12 domain BITS Bits . . . 296
3.12.1 Bits (BITS) . . . 299
3.13 domain BLHN BlowUpWithHamburgerNoether . . . 300
3.13.1 BlowUpWithHamburgerNoether (BLHN) . . . 301
3.14 domain BLQT BlowUpWithQuadTrans . . . 302
3.14.1 BlowUpWithQuadTrans (BLQT) . . . 304
3.15 domain BOOLEAN Boolean . . . 305
3.15.1 Boolean (BOOLEAN) . . . 306

4 Chapter C **311**
4.1 domain CARD CardinalNumber . . . 311
4.1.1 CardinalNumber (CARD) . . . 318
4.2 domain CARTEN CartesianTensor . . . 322
4.2.1 CartesianTensor (CARTEN) . . . 342
4.3 domain CHAR Character . . . 354
4.3.1 Character (CHAR) . . . 359
4.4 domain CCLASS CharacterClass . . . 362
4.4.1 CharacterClass (CCLASS) . . . 367
4.5 domain CLIF CliffordAlgebra[**?**, **?**] . . . 371
4.5.1 Vector (linear) spaces . . . 371
4.5.2 Quadratic Forms[**?**] . . . 372
4.5.3 Quadratic spaces, Clifford Maps[**?**, **?**] . . . 372
4.5.4 Universal Clifford algebras[**?**] . . . 372
4.5.5 Real Clifford algebras $\mathbb{R}_{p,q}$[**?**] . . . 373
4.5.6 Notation for integer sets . . . 373
4.5.7 Frames for Clifford algebras[**?**, **?**, **?**] . . . 373
4.5.8 Real frame groups[**?**, **?**] . . . 373
4.5.9 Canonical products[**?**, **?**, **?**] . . . 374
4.5.10 Clifford algebra of frame group[**?**, **?**, **?**, **?**] . . . 374
4.5.11 Neutral matrix representations[**?**, **?**, **?**] . . . 375
4.5.12 CliffordAlgebra (CLIF) . . . 388
4.6 domain COLOR Color . . . 392
4.6.1 Color (COLOR) . . . 394
4.7 domain COMM Commutator . . . 396
4.7.1 Commutator (COMM) . . . 397
4.8 domain COMPLEX Complex . . . 399
4.8.1 Complex (COMPLEX) . . . 405
4.9 domain CDFMAT ComplexDoubleFloatMatrix . . . 409
4.9.1 ComplexDoubleFloatMatrix (CDFMAT) . . . 413
4.10 domain CDFVEC ComplexDoubleFloatVector . . . 415
4.10.1 ComplexDoubleFloatVector (CDFVEC) . . . 419
4.11 domain CONTFRAC ContinuedFraction . . . 420
4.11.1 ContinuedFraction (CONTFRAC) . . . 432

5 Chapter D **441**
5.1 domain DBASE Database . . . 441
5.1.1 Database (DBASE) . . . 442
5.2 domain DLIST DataList . . . 444
5.2.1 DataList (DLIST) . . . 447
5.3 domain DECIMAL DecimalExpansion . . . 449
5.3.1 DecimalExpansion (DECIMAL) . . . 453
5.4 Denavit-Hartenberg Matrices . . . 455
5.4.1 Homogeneous Transformations . . . 455
5.4.2 Notation . . . 455
5.4.3 Vectors . . . 456

5.4.4 Planes . . . 457
5.4.5 Transformations . . . 459
5.4.6 Translation Transformation . . . 459
5.4.7 Rotation Transformations . . . 461
5.4.8 Coordinate Frames . . . 465
5.4.9 Relative Transformations . . . 465
5.4.10 Objects . . . 466
5.4.11 Inverse Transformations . . . 467
5.4.12 General Rotation Transformation . . . 467
5.4.13 Equivalent Angle and Axis of Rotation . . . 470
5.4.14 Example 1.1 . . . 473
5.4.15 Stretching and Scaling . . . 474
5.4.16 Perspective Transformations . . . 475
5.4.17 Transform Equations . . . 477
5.4.18 Summary . . . 478
5.4.19 DenavitHartenbergMatrix (DHMATRIX) . . . 478
5.5 domain DEQUEUE Dequeue . . . 481
5.5.1 Dequeue (DEQUEUE) . . . 499
5.6 domain DERHAM DeRhamComplex . . . 505
5.6.1 DeRhamComplex (DERHAM) . . . 517
5.7 domain DSTREE DesingTree . . . 520
5.7.1 DesingTree (DSTREE) . . . 522
5.8 domain DSMP DifferentialSparseMultivariatePolynomial . . . 524
5.8.1 DifferentialSparseMultivariatePolynomial (DSMP) . . . 528
5.9 domain DIRPROD DirectProduct . . . 530
5.9.1 DirectProduct (DIRPROD) . . . 534
5.10 domain DPMM DirectProductMatrixModule . . . 537
5.10.1 DirectProductMatrixModule (DPMM) . . . 540
5.11 domain DPMO DirectProductModule . . . 541
5.11.1 DirectProductModule (DPMO) . . . 544
5.12 domain DIRRING DirichletRing . . . 546
5.12.1 DirichletRing (DIRRING) . . . 551
5.13 domain DMP DistributedMultivariatePolynomial . . . 554
5.13.1 DistributedMultivariatePolynomial (DMP) . . . 559
5.14 domain DIV Divisor . . . 561
5.14.1 Divisor (DIV) . . . 563
5.15 domain DFLOAT DoubleFloat . . . 566
5.15.1 DoubleFloat (DFLOAT) . . . 574
5.16 domain DFMAT DoubleFloatMatrix . . . 582
5.16.1 DoubleFloatMatrix (DFMAT) . . . 586
5.17 domain DFVEC DoubleFloatVector . . . 588
5.17.1 DoubleFloatVector (DFVEC) . . . 592
5.18 domain DROPT DrawOption . . . 594
5.18.1 DrawOption (DROPT) . . . 595
5.19 domain D01AJFA d01ajfAnnaType . . . 600
5.19.1 d01ajfAnnaType (D01AJFA) . . . 602

5.20 domain D01AKFA d01akfAnnaType . . . 603
5.20.1 d01akfAnnaType (D01AKFA) . . . 605
5.21 domain D01ALFA d01alfAnnaType . . . 606
5.21.1 d01alfAnnaType (D01ALFA) . . . 608
5.22 domain D01AMFA d01amfAnnaType . . . 610
5.22.1 d01amfAnnaType (D01AMFA) . . . 611
5.23 domain D01ANFA d01anfAnnaType . . . 613
5.23.1 d01anfAnnaType (D01ANFA) . . . 614
5.24 domain D01APFA d01apfAnnaType . . . 616
5.24.1 d01apfAnnaType (D01APFA) . . . 617
5.25 domain D01AQFA d01aqfAnnaType . . . 619
5.25.1 d01aqfAnnaType (D01AQFA) . . . 620
5.26 domain D01ASFA d01asfAnnaType . . . 622
5.26.1 d01asfAnnaType (D01ASFA) . . . 624
5.27 domain D01FCFA d01fcfAnnaType . . . 626
5.27.1 d01fcfAnnaType (D01FCFA) . . . 627
5.28 domain D01GBFA d01gbfAnnaType . . . 629
5.28.1 d01gbfAnnaType (D01GBFA) . . . 630
5.29 domain D01TRNS d01TransformFunctionType . . . 632
5.29.1 d01TransformFunctionType (D01TRNS) . . . 633
5.30 domain D02BBFA d02bbfAnnaType . . . 637
5.30.1 d02bbfAnnaType (D02BBFA) . . . 638
5.31 domain D02BHFA d02bhfAnnaType . . . 640
5.31.1 d02bhfAnnaType (D02BHFA) . . . 641
5.32 domain D02CJFA d02cjfAnnaType . . . 644
5.32.1 d02cjfAnnaType (D02CJFA) . . . 645
5.33 domain D02EJFA d02ejfAnnaType . . . 647
5.33.1 d02ejfAnnaType (D02EJFA) . . . 648
5.34 domain D03EEFA d03eefAnnaType . . . 651
5.34.1 d03eefAnnaType (D03EEFA) . . . 652
5.35 domain D03FAFA d03fafAnnaType . . . 654
5.35.1 d03fafAnnaType (D03FAFA) . . . 655

6 Chapter E 657
6.1 domain EQ Equation . . . 657
6.1.1 Equation (EQ) . . . 661
6.2 domain EQTBL EqTable . . . 666
6.2.1 EqTable (EQTBL) . . . 669
6.3 domain EMR EuclideanModularRing . . . 670
6.3.1 EuclideanModularRing (EMR) . . . 672
6.4 domain EXIT Exit . . . 675
6.4.1 Exit (EXIT) . . . 677
6.5 domain EXPEXPAN ExponentialExpansion . . . 678
6.5.1 ExponentialExpansion (EXPEXPAN) . . . 681
6.6 domain EXPR Expression . . . 685
6.6.1 Expression (EXPR) . . . 693

6.7 domain EXPUPXS ExponentialOfUnivariatePuiseuxSeries . . . 705
6.7.1 ExponentialOfUnivariatePuiseuxSeries (EXPUPXS) . . . 709
6.8 domain EAB ExtAlgBasis . . . 712
6.8.1 ExtAlgBasis (EAB) . . . 713
6.9 domain E04DGFA e04dgfAnnaType . . . 715
6.9.1 e04dgfAnnaType (E04DGFA) . . . 717
6.10 domain E04FDFA e04fdfAnnaType . . . 719
6.10.1 e04fdfAnnaType (E04FDFA) . . . 720
6.11 domain E04GCFA e04gcfAnnaType . . . 723
6.11.1 e04gcfAnnaType (E04GCFA) . . . 724
6.12 domain E04JAFA e04jafAnnaType . . . 727
6.12.1 e04jafAnnaType (E04JAFA) . . . 728
6.13 domain E04MBFA e04mbfAnnaType . . . 730
6.13.1 e04mbfAnnaType (E04MBFA) . . . 731
6.14 domain E04NAFA e04nafAnnaType . . . 733
6.14.1 e04nafAnnaType (E04NAFA) . . . 735
6.15 domain E04UCFA e04ucfAnnaType . . . 737
6.15.1 e04ucfAnnaType (E04UCFA) . . . 738

7 Chapter F 743
7.1 domain FR Factored . . . 743
7.1.1 Factored (FR) . . . 756
7.2 domain FILE File . . . 767
7.2.1 File (FILE) . . . 772
7.3 domain FNAME FileName . . . 774
7.3.1 FileName (FNAME) . . . 780
7.4 domain FDIV FiniteDivisor . . . 781
7.4.1 FiniteDivisor (FDIV) . . . 783
7.5 domain FF FiniteField . . . 786
7.5.1 FiniteField (FF) . . . 789
7.6 domain FFCG FiniteFieldCyclicGroup . . . 791
7.6.1 FiniteFieldCyclicGroup (FFCG) . . . 794
7.7 domain FFCGX FiniteFieldCyclicGroupExtension . . . 796
7.7.1 FiniteFieldCyclicGroupExtension (FFCGX) . . . 799
7.8 domain FFCGP FiniteFieldCyclicGroupExtensionByPolynomial . . . 801
7.8.1 FiniteFieldCyclicGroupExtensionByPolynomial (FFCGP) . . . 804
7.9 domain FFX FiniteFieldExtension . . . 812
7.9.1 FiniteFieldExtension (FFX) . . . 815
7.10 domain FFP FiniteFieldExtensionByPolynomial . . . 817
7.10.1 FiniteFieldExtensionByPolynomial (FFP) . . . 820
7.11 domain FFNB FiniteFieldNormalBasis . . . 826
7.11.1 FiniteFieldNormalBasis (FFNB) . . . 829
7.12 domain FFNBX FiniteFieldNormalBasisExtension . . . 832
7.12.1 FiniteFieldNormalBasisExtension (FFNBX) . . . 835
7.13 domain FFNBP FiniteFieldNormalBasisExtensionByPolynomial . . . 838
7.13.1 FiniteFieldNormalBasisExtensionByPolynomial (FFNBP) . . . 841

7.14 domain FARRAY FlexibleArray . . . 850
7.14.1 FlexibleArray (FARRAY) . . . 856
7.15 domain FLOAT Float . . . 857
7.15.1 Float (FLOAT) . . . 878
7.16 domain FC FortranCode . . . 899
7.16.1 FortranCode (FC) . . . 901
7.17 domain FEXPR FortranExpression . . . 914
7.17.1 FortranExpression (FEXPR) . . . 917
7.18 domain FORTRAN FortranProgram . . . 925
7.18.1 FortranProgram (FORTRAN) . . . 926
7.19 domain FST FortranScalarType . . . 931
7.19.1 FortranScalarType (FST) . . . 932
7.20 domain FTEM FortranTemplate . . . 936
7.20.1 FortranTemplate (FTEM) . . . 937
7.21 domain FT FortranType . . . 940
7.21.1 FortranType (FT) . . . 941
7.22 domain FCOMP FourierComponent . . . 944
7.22.1 FourierComponent (FCOMP) . . . 945
7.23 domain FSERIES FourierSeries . . . 946
7.23.1 FourierSeries (FSERIES) . . . 948
7.24 domain FRAC Fraction . . . 950
7.24.1 Fraction (FRAC) . . . 956
7.25 domain FRIDEAL FractionalIdeal . . . 963
7.25.1 FractionalIdeal (FRIDEAL) . . . 965
7.26 domain FRMOD FramedModule . . . 969
7.26.1 FramedModule (FRMOD) . . . 970
7.27 domain FAGROUP FreeAbelianGroup . . . 973
7.27.1 FreeAbelianGroup (FAGROUP) . . . 974
7.28 domain FAMONOID FreeAbelianMonoid . . . 976
7.28.1 FreeAbelianMonoid (FAMONOID) . . . 977
7.29 domain FGROUP FreeGroup . . . 978
7.29.1 FreeGroup (FGROUP) . . . 980
7.30 domain FM FreeModule . . . 982
7.30.1 FreeModule (FM) . . . 983
7.31 domain FM1 FreeModule1 . . . 985
7.31.1 FreeModule1 (FM1) . . . 987
7.32 domain FMONOID FreeMonoid . . . 989
7.32.1 FreeMonoid (FMONOID) . . . 991
7.33 domain FNLA FreeNilpotentLie . . . 995
7.33.1 FreeNilpotentLie (FNLA) . . . 997
7.34 domain FPARFRAC FullPartialFractionExpansion . . . 1000
7.34.1 FullPartialFractionExpansion (FPARFRAC) . . . 1010
7.35 domain FUNCTION FunctionCalled . . . 1014
7.35.1 FunctionCalled (FUNCTION) . . . 1015

8 Chapter G **1017**
8.1 domain GDMP GeneralDistributedMultivariatePolynomial 1017
8.1.1 GeneralDistributedMultivariatePolynomial (GDMP) 1022
8.2 domain GMODPOL GeneralModulePolynomial 1028
8.2.1 GeneralModulePolynomial (GMODPOL) 1029
8.3 domain GCNAALG GenericNonAssociativeAlgebra 1031
8.3.1 GenericNonAssociativeAlgebra (GCNAALG) 1034
8.4 domain GPOLSET GeneralPolynomialSet 1042
8.4.1 GeneralPolynomialSet (GPOLSET) 1044
8.5 domain GSTBL GeneralSparseTable 1046
8.5.1 GeneralSparseTable (GSTBL) 1048
8.6 domain GTSET GeneralTriangularSet 1050
8.6.1 GeneralTriangularSet (GTSET) 1053
8.7 domain GSERIES GeneralUnivariatePowerSeries 1057
8.7.1 GeneralUnivariatePowerSeries (GSERIES) 1060
8.8 domain GRIMAGE GraphImage 1064
8.8.1 GraphImage (GRIMAGE) 1065
8.9 domain GOPT GuessOption 1074
8.9.1 GuessOption (GOPT) 1075
8.10 domain GOPT0 GuessOptionFunctions0 1079
8.10.1 GuessOptionFunctions0 (GOPT0) 1081

9 Chapter H **1087**
9.1 domain HASHTBL HashTable 1087
9.1.1 HashTable (HASHTBL) 1089
9.2 domain HEAP Heap 1091
9.2.1 Heap (HEAP) 1104
9.3 domain HEXADEC HexadecimalExpansion 1109
9.3.1 HexadecimalExpansion (HEXADEC) 1112
9.4 package HTMLFORM HTMLFormat 1114
9.4.1 Overview 1115
9.4.2 Why output to HTML? 1115
9.5 Using the formatter 1115
9.6 Form of the output 1116
9.7 Matrix Formatting 1116
9.8 Programmers Guide 1117
9.8.1 Future Developments 1117
9.8.2 HTMLFormat (HTMLFORM) 1122
9.9 domain HDP HomogeneousDirectProduct 1139
9.9.1 HomogeneousDirectProduct (HDP) 1142
9.10 domain HDMP HomogeneousDistributedMultivariatePolynomial 1144
9.10.1 HomogeneousDistributedMultivariatePolynomial (HDMP) 1149
9.11 domain HELLFDIV HyperellipticFiniteDivisor 1151
9.11.1 HyperellipticFiniteDivisor (HELLFDIV) 1153

10 Chapter I **1159**
10.1 domain ICP InfClsPt 1159
10.1.1 InfClsPt (ICP) 1160
10.2 domain ICARD IndexCard 1162
10.2.1 IndexCard (ICARD) 1163
10.3 domain IBITS IndexedBits 1165
10.3.1 IndexedBits (IBITS) 1169
10.4 domain IDPAG IndexedDirectProductAbelianGroup 1171
10.4.1 IndexedDirectProductAbelianGroup (IDPAG) 1172
10.5 domain IDPAM IndexedDirectProductAbelianMonoid 1174
10.5.1 IndexedDirectProductAbelianMonoid (IDPAM) 1175
10.6 domain IDPO IndexedDirectProductObject 1178
10.6.1 IndexedDirectProductObject (IDPO) 1179
10.7 domain IDPOAM IndexedDirectProductOrderedAbelianMonoid 1180
10.7.1 IndexedDirectProductOrderedAbelianMonoid (IDPOAM) 1182
10.8 domain IDPOAMS IndexedDirectProductOrderedAbelianMonoidSup 1183
10.8.1 IndexedDirectProductOrderedAbelianMonoidSup (IDPOAMS) 1184
10.9 domain INDE IndexedExponents 1186
10.9.1 IndexedExponents (INDE) 1187
10.10domain IFARRAY IndexedFlexibleArray 1189
10.10.1 IndexedFlexibleArray (IFARRAY) 1191
10.11domain ILIST IndexedList 1197
10.11.1 IndexedList (ILIST) 1200
10.12domain IMATRIX IndexedMatrix 1205
10.12.1 IndexedMatrix (IMATRIX) 1208
10.13domain IARRAY1 IndexedOneDimensionalArray 1210
10.13.1 IndexedOneDimensionalArray (IARRAY1) 1212
10.14domain ISTRING IndexedString 1215
10.14.1 IndexedString (ISTRING) 1218
10.15domain IARRAY2 IndexedTwoDimensionalArray 1223
10.15.1 IndexedTwoDimensionalArray (IARRAY2) 1225
10.16domain IVECTOR IndexedVector 1226
10.16.1 IndexedVector (IVECTOR) 1229
10.17domain ITUPLE InfiniteTuple 1230
10.17.1 InfiniteTuple (ITUPLE) 1231
10.18domain INFCLSPT InfinitlyClosePoint 1232
10.18.1 InfinitlyClosePoint (INFCLSPT) 1234
10.19domain INFCLSPS InfinitlyClosePointOverPseudoAlgebraicClosureOfFinite-Field 1238
10.19.1 InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField (INFCLSPS)1239
10.20domain IAN InnerAlgebraicNumber 1241
10.20.1 InnerAlgebraicNumber (IAN) 1244
10.21domain IFF InnerFiniteField 1248
10.21.1 InnerFiniteField (IFF) 1251
10.22domain IFAMON InnerFreeAbelianMonoid 1253
10.22.1 InnerFreeAbelianMonoid (IFAMON) 1254

10.23domain IIARRAY2 InnerIndexedTwoDimensionalArray 1256
10.23.1 InnerIndexedTwoDimensionalArray (IIARRAY2) 1258
10.24domain IPADIC InnerPAdicInteger 1260
10.24.1 InnerPAdicInteger (IPADIC) 1262
10.25domain IPF InnerPrimeField 1268
10.25.1 InnerPrimeField (IPF) 1271
10.26domain ISUPS InnerSparseUnivariatePowerSeries 1275
10.26.1 InnerSparseUnivariatePowerSeries (ISUPS) 1278
10.27domain INTABL InnerTable 1301
10.27.1 InnerTable (INTABL) 1303
10.28domain ITAYLOR InnerTaylorSeries 1305
10.28.1 InnerTaylorSeries (ITAYLOR) 1306
10.29domain INFORM InputForm 1309
10.29.1 InputForm (INFORM) 1311
10.30domain INT Integer 1315
10.30.1 Integer (INT) 1329
10.31domain ZMOD IntegerMod 1334
10.31.1 IntegerMod (ZMOD) 1335
10.32domain INTFTBL IntegrationFunctionsTable 1338
10.32.1 IntegrationFunctionsTable (INTFTBL) 1339
10.33domain IR IntegrationResult 1341
10.33.1 IntegrationResult (IR) 1343
10.34domain INTRVL Interval 1347
10.34.1 Interval (INTRVL) 1352

11 Chapter J **1363**

12 Chapter K **1365**
12.1 domain KERNEL Kernel 1365
12.1.1 Kernel (KERNEL) 1372
12.2 domain KAFILE KeyedAccessFile 1375
12.2.1 KeyedAccessFile (KAFILE) 1381

13 Chapter L **1387**
13.1 domain LAUPOL LaurentPolynomial 1387
13.1.1 LaurentPolynomial (LAUPOL) 1389
13.2 domain LIB Library 1393
13.2.1 Library (LIB) 1396
13.3 domain LEXP LieExponentials 1398
13.3.1 LieExponentials (LEXP) 1403
13.4 domain LPOLY LiePolynomial 1406
13.4.1 LiePolynomial (LPOLY) 1414
13.5 domain LSQM LieSquareMatrix 1419
13.5.1 LieSquareMatrix (LSQM) 1423
13.6 domain LODO LinearOrdinaryDifferentialOperator 1427
13.6.1 LinearOrdinaryDifferentialOperator (LODO) 1437

13.7 domain LODO1 LinearOrdinaryDifferentialOperator1 . . . 1438
13.7.1 LinearOrdinaryDifferentialOperator1 (LODO1) . . . 1447
13.8 domain LODO2 LinearOrdinaryDifferentialOperator2 . . . 1448
13.8.1 LinearOrdinaryDifferentialOperator2 (LODO2) . . . 1459
13.9 domain LIST List . . . 1460
13.9.1 List (LIST) . . . 1472
13.10 domain LMOPS ListMonoidOps . . . 1475
13.10.1 ListMonoidOps (LMOPS) . . . 1477
13.11 domain LMDICT ListMultiDictionary . . . 1481
13.11.1 ListMultiDictionary (LMDICT) . . . 1483
13.12 domain LA LocalAlgebra . . . 1486
13.12.1 LocalAlgebra (LA) . . . 1488
13.13 domain LO Localize . . . 1489
13.13.1 Localize (LO) . . . 1491
13.14 domain LWORD LyndonWord . . . 1493
13.14.1 LyndonWord (LWORD) . . . 1500

14 Chapter M 1505
14.1 domain MCMPLX MachineComplex . . . 1505
14.1.1 MachineComplex (MCMPLX) . . . 1510
14.2 domain MFLOAT MachineFloat . . . 1513
14.2.1 MachineFloat (MFLOAT) . . . 1515
14.3 domain MINT MachineInteger . . . 1522
14.3.1 MachineInteger (MINT) . . . 1525
14.4 domain MAGMA Magma . . . 1527
14.4.1 Magma (MAGMA) . . . 1533
14.5 domain MKCHSET MakeCachableSet . . . 1537
14.5.1 MakeCachableSet (MKCHSET) . . . 1538
14.6 domain MMLFORM MathMLFormat . . . 1539
14.6.1 Introduction to Mathematical Markup Language . . . 1540
14.6.2 Displaying MathML . . . 1540
14.6.3 Test Cases . . . 1541
14.6.4)set output mathml on . . . 1542
14.6.5 File src/interp/setvars.boot.pamphlet . . . 1542
14.6.6 File setvart.boot.pamphlet . . . 1542
14.6.7 File src/algebra/Makefile.pamphlet . . . 1543
14.6.8 File src/algebra/exposed.lsp.pamphlet . . . 1543
14.6.9 File src/algebra/Lattice.pamphlet . . . 1543
14.6.10 File src/doc/axiom.bib.pamphlet . . . 1544
14.6.11 File interp/i-output.boot.pamphlet . . . 1544
14.6.12 Public Declarations . . . 1544
14.6.13 Private Constant Declarations . . . 1546
14.6.14 Private Function Declarations . . . 1547
14.6.15 Public Function Definitions . . . 1549
14.6.16 Private Function Definitions . . . 1551
14.6.17 Mathematical Markup Language Form . . . 1567

14.6.18 MathMLForm (MMLFORM) . . . 1571
14.7 domain MATRIX Matrix . . . 1572
14.7.1 Matrix (MATRIX) . . . 1590
14.8 domain MODMON ModMonic . . . 1595
14.8.1 ModMonic (MODMON) . . . 1599
14.9 domain MODFIELD ModularField . . . 1604
14.9.1 ModularField (MODFIELD) . . . 1606
14.10 domain MODRING ModularRing . . . 1607
14.10.1 ModularRing (MODRING) . . . 1608
14.11 domain MODMONOM ModuleMonomial . . . 1611
14.11.1 ModuleMonomial (MODMONOM) . . . 1612
14.12 domain MODOP ModuleOperator . . . 1613
14.12.1 ModuleOperator (MODOP) . . . 1615
14.13 domain MOEBIUS MoebiusTransform . . . 1620
14.13.1 MoebiusTransform (MOEBIUS) . . . 1622
14.14 domain MRING MonoidRing . . . 1624
14.14.1 MonoidRing (MRING) . . . 1626
14.15 domain MSET Multiset . . . 1633
14.15.1 Multiset (MSET) . . . 1638
14.16 domain MPOLY MultivariatePolynomial . . . 1644
14.16.1 MultivariatePolynomial (MPOLY) . . . 1649
14.17 domain MYEXPR MyExpression . . . 1651
14.17.1 MyExpression (MYEXPR) . . . 1655
14.18 domain MYUP MyUnivariatePolynomial . . . 1657
14.18.1 MyUnivariatePolynomial (MYUP) . . . 1662

15 Chapter N **1665**
15.1 domain NSDPS NeitherSparseOrDensePowerSeries . . . 1665
15.1.1 NeitherSparseOrDensePowerSeries (NSDPS) . . . 1669
15.2 domain NSMP NewSparseMultivariatePolynomial . . . 1676
15.2.1 NewSparseMultivariatePolynomial (NSMP) . . . 1680
15.3 domain NSUP NewSparseUnivariatePolynomial . . . 1690
15.3.1 NewSparseUnivariatePolynomial (NSUP) . . . 1695
15.4 domain NONE None . . . 1702
15.4.1 None (NONE) . . . 1704
15.5 domain NNI NonNegativeInteger . . . 1705
15.5.1 NonNegativeInteger (NNI) . . . 1706
15.6 domain NOTTING NottinghamGroup . . . 1708
15.6.1 NottinghamGroup (NOTTING) . . . 1711
15.7 domain NIPROB NumericalIntegrationProblem . . . 1712
15.7.1 NumericalIntegrationProblem (NIPROB) . . . 1713
15.8 domain ODEPROB NumericalODEProblem . . . 1715
15.8.1 NumericalODEProblem (ODEPROB) . . . 1716
15.9 domain OPTPROB NumericalOptimizationProblem . . . 1718
15.9.1 NumericalOptimizationProblem (OPTPROB) . . . 1719
15.10 domain PDEPROB NumericalPDEProblem . . . 1721

15.10.1 NumericalPDEProblem (PDEPROB) 1722

16 Chapter O **1725**
16.1 domain OCT Octonion 1725
16.1.1 Octonion (OCT) 1731
16.2 domain ODEIFTBL ODEIntensityFunctionsTable 1733
16.2.1 ODEIntensityFunctionsTable (ODEIFTBL) 1734
16.3 domain ARRAY1 OneDimensionalArray 1736
16.3.1 OneDimensionalArray (ARRAY1) 1740
16.4 domain ONECOMP OnePointCompletion 1741
16.4.1 OnePointCompletion (ONECOMP) 1743
16.5 domain OMCONN OpenMathConnection 1746
16.5.1 OpenMathConnection (OMCONN) 1747
16.6 domain OMDEV OpenMathDevice 1749
16.6.1 OpenMathDevice (OMDEV) 1750
16.7 domain OMENC OpenMathEncoding 1754
16.7.1 OpenMathEncoding (OMENC) 1755
16.8 domain OMERR OpenMathError 1757
16.8.1 OpenMathError (OMERR) 1758
16.9 domain OMERRK OpenMathErrorKind 1759
16.9.1 OpenMathErrorKind (OMERRK) 1761
16.10domain OP Operator 1762
16.10.1 Operator (OP) 1770
16.11domain OMLO OppositeMonogenicLinearOperator 1771
16.11.1 OppositeMonogenicLinearOperator (OMLO) 1773
16.12domain ORDCOMP OrderedCompletion 1774
16.12.1 OrderedCompletion (ORDCOMP) 1776
16.13domain ODP OrderedDirectProduct 1780
16.13.1 OrderedDirectProduct (ODP) 1783
16.14domain OFMONOID OrderedFreeMonoid 1784
16.14.1 OrderedFreeMonoid (OFMONOID) 1795
16.15domain OVAR OrderedVariableList 1800
16.15.1 OrderedVariableList (OVAR) 1803
16.16domain ODPOL OrderlyDifferentialPolynomial 1804
16.16.1 OrderlyDifferentialPolynomial (ODPOL) 1817
16.17domain ODVAR OrderlyDifferentialVariable 1819
16.17.1 OrderlyDifferentialVariable (ODVAR) 1821
16.18domain ODR OrdinaryDifferentialRing 1822
16.18.1 OrdinaryDifferentialRing (ODR) 1824
16.19domain OWP OrdinaryWeightedPolynomials 1826
16.19.1 OrdinaryWeightedPolynomials (OWP) 1827
16.20domain OSI OrdSetInts 1829
16.20.1 OrdSetInts (OSI) 1830
16.21domain OUTFORM OutputForm 1831
16.21.1 OutputForm (OUTFORM) 1833

17 Chapter P **1845**
17.1 domain PADIC PAdicInteger . . . 1845
17.1.1 PAdicInteger (PADIC) . . . 1847
17.2 domain PADICRAT PAdicRational . . . 1848
17.2.1 PAdicRational (PADICRAT) . . . 1851
17.3 domain PADICRC PAdicRationalConstructor . . . 1853
17.3.1 PAdicRationalConstructor (PADICRC) . . . 1856
17.4 domain PALETTE Palette . . . 1861
17.4.1 Palette (PALETTE) . . . 1862
17.5 domain PARPCURV ParametricPlaneCurve . . . 1864
17.5.1 ParametricPlaneCurve (PARPCURV) . . . 1865
17.6 domain PARSCURV ParametricSpaceCurve . . . 1866
17.6.1 ParametricSpaceCurve (PARSCURV) . . . 1867
17.7 domain PARSURF ParametricSurface . . . 1869
17.7.1 ParametricSurface (PARSURF) . . . 1870
17.8 domain PFR PartialFraction . . . 1871
17.8.1 PartialFraction (PFR) . . . 1880
17.9 domain PRTITION Partition . . . 1888
17.9.1 Partition (PRTITION) . . . 1889
17.10domain PATTERN Pattern . . . 1892
17.10.1 Pattern (PATTERN) . . . 1894
17.11domain PATLRES PatternMatchListResult . . . 1902
17.11.1 PatternMatchListResult (PATLRES) . . . 1903
17.12domain PATRES PatternMatchResult . . . 1905
17.12.1 PatternMatchResult (PATRES) . . . 1906
17.13domain PENDTREE PendantTree . . . 1909
17.13.1 PendantTree (PENDTREE) . . . 1911
17.14domain PERM Permutation . . . 1912
17.14.1 Permutation (PERM) . . . 1915
17.15domain PERMGRP PermutationGroup . . . 1924
17.15.1 PermutationGroup (PERMGRP) . . . 1926
17.16domain HACKPI Pi . . . 1941
17.16.1 Pi (HACKPI) . . . 1943
17.17domain ACPLOT PlaneAlgebraicCurvePlot . . . 1945
17.17.1 PlaneAlgebraicCurvePlot (ACPLOT) . . . 1958
17.18domain PLACES Places . . . 1983
17.18.1 Places (PLACES) . . . 1984
17.19domain PLACESPS PlacesOverPseudoAlgebraicClosureOfFiniteField . . . 1985
17.19.1 PlacesOverPseudoAlgebraicClosureOfFiniteField (PLACESPS) . . . 1987
17.20domain PLCS Plcs . . . 1988
17.20.1 Plcs (PLCS) . . . 1989
17.21domain PLOT Plot . . . 1992
17.21.1 Plot (PLOT) . . . 1995
17.22domain PLOT3D Plot3D . . . 2007
17.22.1 Plot3D (PLOT3D) . . . 2008
17.23domain PBWLB PoincareBirkhoffWittLyndonBasis . . . 2018

17.23.1 PoincareBirkhoffWittLyndonBasis (PBWLB) . . . 2020
17.24 domain POINT Point . . . 2022
17.24.1 Point (POINT) . . . 2025
17.25 domain POLY Polynomial . . . 2027
17.25.1 Polynomial (POLY) . . . 2043
17.26 domain IDEAL PolynomialIdeals . . . 2045
17.26.1 PolynomialIdeals (IDEAL) . . . 2047
17.27 domain PR PolynomialRing . . . 2056
17.27.1 PolynomialRing (PR) . . . 2058
17.28 domain PI PositiveInteger . . . 2065
17.28.1 PositiveInteger (PI) . . . 2066
17.29 domain PF PrimeField . . . 2067
17.29.1 PrimeField (PF) . . . 2070
17.30 domain PRIMARR PrimitiveArray . . . 2072
17.30.1 PrimitiveArray (PRIMARR) . . . 2075
17.31 domain PRODUCT Product . . . 2076
17.31.1 Product (PRODUCT) . . . 2078
17.32 domain PROJPL ProjectivePlane . . . 2081
17.32.1 ProjectivePlane (PROJPL) . . . 2083
17.33 domain PROJPLPS ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField 2084
17.33.1 ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField (PROJPLPS) 2085
17.34 domain PROJSP ProjectiveSpace . . . 2086
17.34.1 ProjectiveSpace (PROJSP) . . . 2087
17.35 domain PACEXT PseudoAlgebraicClosureOfAlgExtOfRationalNumber . . . 2091
17.35.1 PseudoAlgebraicClosureOfAlgExtOfRationalNumber (PACEXT) . . . 2092
17.36 domain PACOFF PseudoAlgebraicClosureOfFiniteField . . . 2098
17.36.1 PseudoAlgebraicClosureOfFiniteField (PACOFF) . . . 2101
17.37 domain PACRAT PseudoAlgebraicClosureOfRationalNumber . . . 2109
17.37.1 PseudoAlgebraicClosureOfRationalNumber (PACRAT) . . . 2112

18 Chapter Q **2119**
18.1 domain QFORM QuadraticForm . . . 2119
18.1.1 QuadraticForm (QFORM) . . . 2120
18.2 domain QALGSET QuasiAlgebraicSet . . . 2122
18.2.1 QuasiAlgebraicSet (QALGSET) . . . 2123
18.3 domain QUAT Quaternion . . . 2127
18.3.1 Quaternion (QUAT) . . . 2132
18.4 domain QEQUAT QueryEquation . . . 2134
18.4.1 QueryEquation (QEQUAT) . . . 2135
18.5 domain QUEUE Queue . . . 2136
18.5.1 Queue (QUEUE) . . . 2150

19 Chapter R **2155**
19.1 domain RADFF RadicalFunctionField . . . 2155
19.1.1 RadicalFunctionField (RADFF) . . . 2159
19.2 domain RADIX RadixExpansion . . . 2165
19.2.1 RadixExpansion (RADIX) . . . 2171
19.3 domain RECLOS RealClosure . . . 2177
19.3.1 RealClosure (RECLOS) . . . 2202
19.4 domain RMATRIX RectangularMatrix . . . 2209
19.4.1 RectangularMatrix (RMATRIX) . . . 2211
19.5 domain REF Reference . . . 2214
19.5.1 Reference (REF) . . . 2215
19.6 domain RGCHAIN RegularChain . . . 2217
19.6.1 RegularChain (RGCHAIN) . . . 2220
19.7 domain REGSET RegularTriangularSet . . . 2223
19.7.1 RegularTriangularSet (REGSET) . . . 2251
19.8 domain RESRING ResidueRing . . . 2261
19.8.1 ResidueRing (RESRING) . . . 2262
19.9 domain RESULT Result . . . 2264
19.9.1 Result (RESULT) . . . 2266
19.10domain RULE RewriteRule . . . 2269
19.10.1 RewriteRule (RULE) . . . 2271
19.11domain ROIRC RightOpenIntervalRootCharacterization . . . 2274
19.11.1 RightOpenIntervalRootCharacterization (ROIRC) . . . 2276
19.12domain ROMAN RomanNumeral . . . 2286
19.12.1 RomanNumeral (ROMAN) . . . 2292
19.13domain ROUTINE RoutinesTable . . . 2294
19.13.1 RoutinesTable (ROUTINE) . . . 2297
19.14domain RULECOLD RuleCalled . . . 2306
19.14.1 RuleCalled (RULECOLD) . . . 2307
19.15domain RULESET Ruleset . . . 2308
19.15.1 Ruleset (RULESET) . . . 2309

20 Chapter S **2311**
20.1 domain FORMULA ScriptFormulaFormat . . . 2311
20.1.1 ScriptFormulaFormat (FORMULA) . . . 2312
20.2 domain SEG Segment . . . 2321
20.2.1 Segment (SEG) . . . 2325
20.3 domain SEGBIND SegmentBinding . . . 2327
20.3.1 SegmentBinding (SEGBIND) . . . 2330
20.4 domain SET Set . . . 2331
20.4.1 Set (SET) . . . 2338
20.5 domain SETMN SetOfMIntegersInOneToN . . . 2342
20.5.1 SetOfMIntegersInOneToN (SETMN) . . . 2344
20.6 domain SDPOL SequentialDifferentialPolynomial . . . 2347
20.6.1 SequentialDifferentialPolynomial (SDPOL) . . . 2351
20.7 domain SDVAR SequentialDifferentialVariable . . . 2353

20.7.1 SequentialDifferentialVariable (SDVAR) . . . 2357
20.8 domain SEX SExpression . . . 2359
20.8.1 SExpression (SEX) . . . 2360
20.9 domain SEXOF SExpressionOf . . . 2361
20.9.1 SExpressionOf (SEXOF) . . . 2362
20.10 domain SAE SimpleAlgebraicExtension . . . 2364
20.10.1 SimpleAlgebraicExtension (SAE) . . . 2368
20.11 domain SFORT SimpleFortranProgram . . . 2372
20.11.1 SimpleFortranProgram (SFORT) . . . 2373
20.12 domain SINT SingleInteger . . . 2375
20.12.1 SingleInteger (SINT) . . . 2380
20.13 domain SAOS SingletonAsOrderedSet . . . 2385
20.13.1 SingletonAsOrderedSet (SAOS) . . . 2386
20.14 domain SMP SparseMultivariatePolynomial . . . 2387
20.14.1 SparseMultivariatePolynomial (SMP) . . . 2390
20.15 domain SMTS SparseMultivariateTaylorSeries . . . 2403
20.15.1 SparseMultivariateTaylorSeries (SMTS) . . . 2408
20.16 domain STBL SparseTable . . . 2415
20.16.1 SparseTable (STBL) . . . 2418
20.17 domain SULS SparseUnivariateLaurentSeries . . . 2419
20.17.1 SparseUnivariateLaurentSeries (SULS) . . . 2424
20.18 domain SUP SparseUnivariatePolynomial . . . 2430
20.18.1 SparseUnivariatePolynomial (SUP) . . . 2434
20.19 domain SUPEXPR SparseUnivariatePolynomialExpressions . . . 2443
20.19.1 SparseUnivariatePolynomialExpressions (SUPEXPR) . . . 2448
20.20 domain SUPXS SparseUnivariatePuiseuxSeries . . . 2451
20.20.1 SparseUnivariatePuiseuxSeries (SUPXS) . . . 2454
20.21 domain ORESUP SparseUnivariateSkewPolynomial . . . 2457
20.21.1 SparseUnivariateSkewPolynomial (ORESUP) . . . 2459
20.22 domain SUTS SparseUnivariateTaylorSeries . . . 2461
20.22.1 SparseUnivariateTaylorSeries (SUTS) . . . 2464
20.23 domain SHDP SplitHomogeneousDirectProduct . . . 2472
20.23.1 SplitHomogeneousDirectProduct (SHDP) . . . 2476
20.24 domain SPLNODE SplittingNode . . . 2478
20.24.1 SplittingNode (SPLNODE) . . . 2479
20.25 domain SPLTREE SplittingTree . . . 2483
20.25.1 SplittingTree (SPLTREE) . . . 2485
20.26 domain SREGSET SquareFreeRegularTriangularSet . . . 2492
20.26.1 SquareFreeRegularTriangularSet (SREGSET) . . . 2501
20.27 domain SQMATRIX SquareMatrix . . . 2511
20.27.1 SquareMatrix (SQMATRIX) . . . 2514
20.28 domain STACK Stack . . . 2518
20.28.1 Stack (STACK) . . . 2530
20.29 domain SD StochasticDifferential . . . 2535
20.29.1 StochasticDifferential (SD) . . . 2539
20.30 domain STREAM Stream . . . 2545

20.30.1 Stream (STREAM) . . . 2549
20.31 domain STRING String . . . 2564
20.31.1 String (STRING) . . . 2574
20.32 domain STRTBL StringTable . . . 2576
20.32.1 StringTable (STRTBL) . . . 2578
20.33 domain SUBSPACE SubSpace . . . 2579
20.33.1 SubSpace (SUBSPACE) . . . 2582
20.34 domain COMPPROP SubSpaceComponentProperty . . . 2591
20.34.1 SubSpaceComponentProperty (COMPPROP) . . . 2592
20.35 domain SUCH SuchThat . . . 2593
20.35.1 SuchThat (SUCH) . . . 2595
20.36 domain SWITCH Switch . . . 2596
20.36.1 Switch (SWITCH) . . . 2597
20.37 domain SYMBOL Symbol . . . 2599
20.37.1 Symbol (SYMBOL) . . . 2608
20.38 domain SYMTAB SymbolTable . . . 2615
20.38.1 SymbolTable (SYMTAB) . . . 2616
20.39 domain SYMPOLY SymmetricPolynomial . . . 2620
20.39.1 SymmetricPolynomial (SYMPOLY) . . . 2622

21 Chapter T 2625
21.1 domain TABLE Table . . . 2625
21.1.1 Table (TABLE) . . . 2631
21.2 domain TABLEAU Tableau . . . 2633
21.2.1 Tableau (TABLEAU) . . . 2634
21.3 domain TS TaylorSeries . . . 2635
21.3.1 TaylorSeries (TS) . . . 2638
21.4 domain TEX TexFormat . . . 2640
21.4.1 product(product(i*j,i=a..b),j=c..d) fix . . . 2640
21.4.2 TexFormat (TEX) . . . 2645
21.5 domain TEXTFILE TextFile . . . 2657
21.5.1 TextFile (TEXTFILE) . . . 2661
21.6 domain SYMS TheSymbolTable . . . 2663
21.6.1 TheSymbolTable (SYMS) . . . 2665
21.7 domain M3D ThreeDimensionalMatrix . . . 2669
21.7.1 ThreeDimensionalMatrix (M3D) . . . 2671
21.8 domain VIEW3D ThreeDimensionalViewport . . . 2677
21.8.1 ThreeDimensionalViewport (VIEW3D) . . . 2679
21.9 domain SPACE3 ThreeSpace . . . 2699
21.9.1 ThreeSpace (SPACE3) . . . 2700
21.10 domain TREE Tree . . . 2708
21.10.1 Tree (TREE) . . . 2710
21.11 domain TUBE TubePlot . . . 2717
21.11.1 TubePlot (TUBE) . . . 2718
21.12 domain TUPLE Tuple . . . 2720
21.12.1 Tuple (TUPLE) . . . 2721

21.13domain ARRAY2 TwoDimensionalArray . . . 2723
21.13.1 TwoDimensionalArray (ARRAY2) . . . 2732
21.14domain VIEW2D TwoDimensionalViewport . . . 2733
21.14.1 TwoDimensionalViewport (VIEW2D) . . . 2738

22 Chapter U **2753**
22.1 domain UFPS UnivariateFormalPowerSeries . . . 2753
22.1.1 UnivariateFormalPowerSeries (UFPS) . . . 2756
22.2 domain ULS UnivariateLaurentSeries . . . 2758
22.2.1 UnivariateLaurentSeries (ULS) . . . 2762
22.3 domain ULSCONS UnivariateLaurentSeriesConstructor . . . 2765
22.3.1 UnivariateLaurentSeriesConstructor (ULSCONS) . . . 2770
22.4 domain UP UnivariatePolynomial . . . 2781
22.4.1 UnivariatePolynomial (UP) . . . 2794
22.5 domain UPXS UnivariatePuiseuxSeries . . . 2797
22.5.1 UnivariatePuiseuxSeries (UPXS) . . . 2800
22.6 domain UPXSCONS UnivariatePuiseuxSeriesConstructor . . . 2805
22.6.1 UnivariatePuiseuxSeriesConstructor (UPXSCONS) . . . 2808
22.7 domain UPXSSING UnivariatePuiseuxSeriesWithExponentialSingularity . . . 2816
22.7.1 UnivariatePuiseuxSeriesWithExponentialSingularity (UPXSSING) . . . 2819
22.8 domain OREUP UnivariateSkewPolynomial . . . 2825
22.8.1 UnivariateSkewPolynomial (OREUP) . . . 2839
22.9 domain UTS UnivariateTaylorSeries . . . 2841
22.9.1 UnivariateTaylorSeries (UTS) . . . 2844
22.10domain UTSZ UnivariateTaylorSeriesCZero . . . 2850
22.10.1 UnivariateTaylorSeriesCZero (UTSZ) . . . 2853
22.11domain UNISEG UniversalSegment . . . 2859
22.11.1 UniversalSegment (UNISEG) . . . 2863
22.12domain U32VEC U32Vector . . . 2866
22.12.1 U32Vector (U32VEC) . . . 2868

23 Chapter V **2871**
23.1 domain VARIABLE Variable . . . 2871
23.1.1 Variable (VARIABLE) . . . 2872
23.2 domain VECTOR Vector . . . 2873
23.2.1 Vector (VECTOR) . . . 2877
23.3 domain VOID Void . . . 2879
23.3.1 Void (VOID) . . . 2881

24 Chapter W **2883**
24.1 domain WP WeightedPolynomials . . . 2883
24.1.1 WeightedPolynomials (WP) . . . 2884
24.2 domain WUTSET WuWenTsunTriangularSet . . . 2887
24.2.1 WuWenTsunTriangularSet (WUTSET) . . . 2894

25 Chapter X **2903**
25.1 domain XDPOLY XDistributedPolynomial 2903
25.1.1 XDistributedPolynomial (XDPOLY) 2905
25.2 domain XPBWPOLY XPBWPolynomial 2908
25.2.1 XPBWPolynomial (XPBWPOLY) 2925
25.3 domain XPOLY XPolynomial 2930
25.3.1 XPolynomial (XPOLY) 2936
25.4 domain XPR XPolynomialRing 2937
25.4.1 XPolynomialRing (XPR) 2945
25.5 domain XRPOLY XRecursivePolynomial 2949
25.5.1 XRecursivePolynomial (XRPOLY) 2951

26 Chapter Y **2959**

27 Chapter Z **2961**

28 The bootstrap code **2963**
28.1 BOOLEAN.lsp 2963
28.2 CHAR.lsp BOOTSTRAP 2968
28.3 DFLOAT.lsp BOOTSTRAP 2972
28.4 ILIST.lsp BOOTSTRAP 2988
28.5 INT.lsp BOOTSTRAP 3000
28.6 ISTRING.lsp BOOTSTRAP 3011
28.7 LIST.lsp BOOTSTRAP 3029
28.8 NNI.lsp BOOTSTRAP 3035
28.9 OUTFORM.lsp BOOTSTRAP 3038
28.10PI.lsp BOOTSTRAP 3052
28.11PRIMARR.lsp BOOTSTRAP 3054
28.12REF.lsp BOOTSTRAP 3057
28.13SINT.lsp BOOTSTRAP 3060
28.14SYMBOL.lsp BOOTSTRAP 3073
28.15VECTOR.lsp BOOTSTRAP 3089

29 Chunk collections **3093**

30 Index **3103**

New Foreword

On October 1, 2001 Axiom was withdrawn from the market and ended life as a commercial product. On September 3, 2002 Axiom was released under the Modified BSD license, including this document. On August 27, 2003 Axiom was released as free and open source software available for download from the Free Software Foundation's website, Savannah.

Work on Axiom has had the generous support of the Center for Algorithms and Interactive Scientific Computation (CAISS) at City College of New York. Special thanks go to Dr. Gilbert Baumslag for his support of the long term goal.

The online version of this documentation is roughly 1000 pages. In order to make printed versions we've broken it up into three volumes. The first volume is tutorial in nature. The second volume is for programmers. The third volume is reference material. We've also added a fourth volume for developers. All of these changes represent an experiment in print-on-demand delivery of documentation. Time will tell whether the experiment succeeded.

Axiom has been in existence for over thirty years. It is estimated to contain about three hundred man-years of research and has, as of September 3, 2003, 143 people listed in the credits. All of these people have contributed directly or indirectly to making Axiom available. Axiom is being passed to the next generation. I'm looking forward to future milestones.

With that in mind I've introduced the theme of the "30 year horizon". We must invent the tools that support the Computational Mathematician working 30 years from now. How will research be done when every bit of mathematical knowledge is online and instantly available? What happens when we scale Axiom by a factor of 100, giving us 1.1 million domains? How can we integrate theory with code? How will we integrate theorems and proofs of the mathematics with space-time complexity proofs and running code? What visualization tools are needed? How do we support the conceptual structures and semantics of mathematics in effective ways? How do we support results from the sciences? How do we teach the next generation to be effective Computational Mathematicians?

The "30 year horizon" is much nearer than it appears.

Tim Daly
CAISS, City College of New York
November 10, 2003 ((iHy))

Chapter 1

Chapter Overview

This book contains the domains in Axiom, in alphabetical order.

Each domain has an associated 'dotpic' chunk which only lists the domains, categories, and packages that are in the layer immediately below in the build order. For the full list see the algebra Makefile where this information is maintained.

Each domain is preceded by a picture. The picture indicates several things. The colors indicate whether the name refers to a category, domain, or package. An ellipse means that the name refers to something in the bootstrap set. Thus,



Chapter 2

Chapter A

2.1 domain AFFPL AffinePlane

— AffinePlane.input —

```
)set break resume
)sys rm -f AffinePlane.output
)spool AffinePlane.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AffinePlane
--R
--R AffinePlane(K: Field)  is a domain constructor
--R Abbreviation for AffinePlane is AFFPL
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for AFFPL
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               affinePoint : List(K) -> %
--R coerce : List(K) -> %                coerce : % -> List(K)
--R coerce : % -> OutputForm             conjugate : % -> %
--R definingField : % -> K               degree : % -> PositiveInteger
--R ?.? : (%,Integer) -> K               hash : % -> SingleInteger
--R latex : % -> String                  list : % -> List(K)
--R orbit : % -> List(%)                 origin : () -> %
--R pointValue : % -> List(K)            rational? : % -> Boolean
--R setelt : (%,Integer,K) -> K          ?~=? : (%,%) -> Boolean
--R conjugate : (%,NonNegativeInteger) -> %
--R orbit : (%,NonNegativeInteger) -> List(%)
```

```
--R rational? : (%,NonNegativeInteger) -> Boolean
--R removeConjugate : List(%) -> List(%)
--R removeConjugate : (List(%),NonNegativeInteger) -> List(%)
--R
--E 1

)spool
)lisp (bye)
```

———-


— AffinePlane.help —

```
=====================================================================
AffinePlane examples
=====================================================================

See Also:
o )show AffinePlane
```

———-

2.1.1 AffinePlane (AFFPL)



Exports:

— domain AFFPL AffinePlane —

```
)abbrev domain AFFPL AffinePlane
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
```

```
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is all the categories and domains related to projective
++ space and part of the PAFF package
AffinePlane(K):Exports == Implementation where
  K:Field

  Exports ==> AffineSpaceCategory(K)

  Implementation ==> AffineSpace(2,K)
```

———-

— **AFFPL.dotabb** —

```
"AFFPL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AFFPL"];
"AFFSP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AFFSP"];
"AFFPL" -> "AFFSP"
```

———-

2.2 domain AFFPLPS AffinePlaneOverPseudoAlgebraicClosureOfFiniteField

— **AffinePlaneOverPseudoAlgebraicClosureOfFiniteField.input** —

```
)set break resume
)sys rm -f AffinePlaneOverPseudoAlgebraicClosureOfFiniteField.output
)spool AffinePlaneOverPseudoAlgebraicClosureOfFiniteField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AffinePlaneOverPseudoAlgebraicClosureOfFiniteField
--R
--R AffinePlaneOverPseudoAlgebraicClosureOfFiniteField(K: FiniteFieldCategory)  is a domain constructor
--R Abbreviation for AffinePlaneOverPseudoAlgebraicClosureOfFiniteField is AFFPLPS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for AFFPLPS
--R
--R------------------------------ Operations --------------------------------
```

```
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R conjugate : % -> %                    degree : % -> PositiveInteger
--R hash : % -> SingleInteger             latex : % -> String
--R orbit : % -> List(%)                  origin : () -> %
--R rational? : % -> Boolean              ?~=? : (%,%) -> Boolean
--R affinePoint : List(PseudoAlgebraicClosureOfFiniteField(K)) -> %
--R coerce : List(PseudoAlgebraicClosureOfFiniteField(K)) -> %
--R coerce : % -> List(PseudoAlgebraicClosureOfFiniteField(K))
--R conjugate : (%,NonNegativeInteger) -> %
--R definingField : % -> PseudoAlgebraicClosureOfFiniteField(K)
--R ?.? : (%,Integer) -> PseudoAlgebraicClosureOfFiniteField(K)
--R list : % -> List(PseudoAlgebraicClosureOfFiniteField(K))
--R orbit : (%,NonNegativeInteger) -> List(%)
--R pointValue : % -> List(PseudoAlgebraicClosureOfFiniteField(K))
--R rational? : (%,NonNegativeInteger) -> Boolean
--R removeConjugate : List(%) -> List(%)
--R removeConjugate : (List(%),NonNegativeInteger) -> List(%)
--R setelt : (%,Integer,PseudoAlgebraicClosureOfFiniteField(K)) -> PseudoAlgebraicClosureOfFinit
--R
--E 1

)spool
)lisp (bye)
```

———-


— AffinePlaneOverPseudoAlgebraicClosureOfFiniteField.help —

```
oooo
====================================================================
AffinePlaneOverPseudoAlgebraicClosureOfFiniteField examples
====================================================================

See Also:
o )show AffinePlaneOverPseudoAlgebraicClosureOfFiniteField
```

———-

2.2.1 AffinePlaneOverPseudoAlgebraicClosureOfFiniteField (AFFPLPS)



Exports:

?.?	?=?	?~=?	affinePoint	coerce
conjugate	definingField	degree	hash	latex
list	orbit	origin	pointValue	rational?
removeConjugate	setelt			

— **domain AFFPLPS AffinePlaneOverPseudoAlgebraicClosureOfFiniteField** —

```
)abbrev domain AFFPLPS AffinePlaneOverPseudoAlgebraicClosureOfFiniteField
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is all the categories and domains related to projective
++ space and part of the PAFF package
AffinePlaneOverPseudoAlgebraicClosureOfFiniteField(K):Exports == Impl where
  K:FiniteFieldCategory

  KK ==> PseudoAlgebraicClosureOfFiniteField(K)

  Exports ==> AffineSpaceCategory(KK)

  Impl ==> AffinePlane(KK)
```

———-

— **AFFPLPS.dotabb** —

```
"AFFPLPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AFFPLPS"];
"AFFPL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AFFPL"];
"AFFPLPS" -> "AFFPL"
```

———-

2.3 domain AFFSP AffineSpace

— **AffineSpace.input** —

```
)set break resume
)sys rm -f AffineSpace.output
)spool AffineSpace.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AffineSpace
--R
--R AffineSpace(dim: NonNegativeInteger,K: Field)  is a domain constructor
--R Abbreviation for AffineSpace is AFFSP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for AFFSP
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               affinePoint : List(K) -> %
--R coerce : List(K) -> %                coerce : % -> List(K)
--R coerce : % -> OutputForm             conjugate : % -> %
--R definingField : % -> K               degree : % -> PositiveInteger
--R ?.? : (%,Integer) -> K               hash : % -> SingleInteger
--R latex : % -> String                  list : % -> List(K)
--R orbit : % -> List(%)                 origin : () -> %
--R pointValue : % -> List(K)            rational? : % -> Boolean
--R setelt : (%,Integer,K) -> K          ?~=? : (%,%) -> Boolean
--R conjugate : (%,NonNegativeInteger) -> %
--R orbit : (%,NonNegativeInteger) -> List(%)
--R rational? : (%,NonNegativeInteger) -> Boolean
--R removeConjugate : List(%) -> List(%)
--R removeConjugate : (List(%),NonNegativeInteger) -> List(%)
--R
--E 1

)spool
)lisp (bye)
```

———-

— **AffineSpace.help** —


```
=======================================================================
```

```
AffineSpace examples
====================================================================

See Also:
o )show AffineSpace
```

———-

2.3.1 AffineSpace (AFFSP)



Exports:

?.?	?=?	?~=?	affinePoint	coerce
conjugate	definingField	degree	hash	latex
list	orbit	origin	pointValue	rational?
removeConjugate	setelt			

— domain AFFSP AffineSpace —

```
)abbrev domain AFFSP AffineSpace
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is all the categories and domains related to projective
++ space and part of the PAFF package
AffineSpace(dim,K):Exports == Implementation where
  dim:NonNegativeInteger
  K:Field

  LIST ==> List
  NNI  ==> NonNegativeInteger

  Exports ==> AffineSpaceCategory(K)
```

```
Implementation ==> List(K)  add

  Rep:= List(K)

  origin== new(dim,0$K)$List(K)

  coerce(pt:%):OutputForm ==
    dd:OutputForm:= ":" :: OutputForm
    llout:List(OutputForm):=[ hconcat(dd, a::OutputForm) for a in rest pt]
    lout:= cons( (first pt)::OutputForm , llout)
    out:= hconcat lout
    oo:=paren(out)
    ee:OutputForm:= degree(pt) :: OutputForm
    oo**ee

  definingField(pt)==
    K has PseudoAlgebraicClosureOfPerfectFieldCategory => _
      maxTower(pt pretend Rep)
    1$K

  degree(pt)==
    K has PseudoAlgebraicClosureOfPerfectFieldCategory => _
      extDegree definingField pt
    1

  coerce(pt:%):List(K) == pt pretend Rep

  affinePoint(pt:LIST(K))==
      pt :: %

  list(ptt)==
    ptt pretend Rep

  pointValue(ptt)==
    ptt pretend Rep

  conjugate(p,e)==
    lp:Rep:=p
    pc:List(K):=[c**e for c in lp]
    affinePoint(pc)

  rational?(p,n)== p=conjugate(p,n)

  rational?(p)==rational?(p,characteristic()$K)

  removeConjugate(l)==removeConjugate(l,characteristic()$K)

  removeConjugate(l:LIST(%),n:NNI):LIST(%)==
    if K has FiniteFieldCategory then
      allconj:LIST(%):=empty()
```

```
        conjrem:LIST(%):=empty()
        for p in l repeat
          if ^member?(p,allconj) then
            conjrem:=cons(p,conjrem)
            allconj:=concat(allconj,orbit(p,n))
        conjrem
      else
        error "The field is not finite"

    conjugate(p)==conjugate(p,characteristic()$K)

    orbit(p)==orbit(p,characteristic()$K)

    orbit(p,e)==
      if K has FiniteFieldCategory then
        l:LIST(%):=[p]
        np:%:=conjugate(p,e)
        flag:=^(np=p)::Boolean
        while flag repeat
          l:=concat(np,l)
          np:=conjugate(np,e)
          flag:=not (np=p)::Boolean
        l
      else
        error "Cannot compute the conjugate"

    aa:% = bb:% ==
      aa =$Rep bb

    coerce(pt:LIST(K))==
        ^(dim=#pt) => error "Le point n'a pas la bonne dimension"
        ptt:%:= pt
        ptt
```

———-

— **AFFSP.dotabb** —

```
"AFFSP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AFFSP"];
"PACPERC" [color=lightblue,href="bookvol10.2.pdf#nameddest=PACPERC"];
"FPC" [color=lightblue,href="bookvol10.2.pdf#nameddest=FPC"];
"AFFSP" -> "FPC"
"AFFSP" -> "PACPERC"
```

———-

2.4 domain ALGSC AlgebraGivenByStructuralConstants

— AlgebraGivenByStructuralConstants.input —

```
)set break resume
)sys rm -f AlgebraGivenByStructuralConstants.output
)spool AlgebraGivenByStructuralConstants.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AlgebraGivenByStructuralConstants
--R
--R AlgebraGivenByStructuralConstants(R: Field,n: PositiveInteger,ls: List(Symbol),gamma: Vector
--R Abbreviation for AlgebraGivenByStructuralConstants is ALGSC
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ALGSC
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (SquareMatrix(n,R),%) -> %      ?*? : (R,%) -> %
--R ?*? : (%,R) -> %                      ?*? : (%,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                0 : () -> %
--R alternative? : () -> Boolean          antiAssociative? : () -> Boolean
--R antiCommutative? : () -> Boolean      antiCommutator : (%,%) -> %
--R apply : (Matrix(R),%) -> %            associative? : () -> Boolean
--R associator : (%,%,%) -> %             basis : () -> Vector(%)
--R coerce : Vector(R) -> %               coerce : % -> OutputForm
--R commutative? : () -> Boolean          commutator : (%,%) -> %
--R convert : Vector(R) -> %              convert : % -> Vector(R)
--R coordinates : % -> Vector(R)          ?.? : (%,Integer) -> R
--R flexible? : () -> Boolean             hash : % -> SingleInteger
--R jacobiIdentity? : () -> Boolean       jordanAdmissible? : () -> Boolean
--R jordanAlgebra? : () -> Boolean        latex : % -> String
--R leftAlternative? : () -> Boolean      leftDiscriminant : () -> R
--R leftDiscriminant : Vector(%) -> R     leftNorm : % -> R
--R leftTrace : % -> R                    leftTraceMatrix : () -> Matrix(R)
--R lieAdmissible? : () -> Boolean        lieAlgebra? : () -> Boolean
--R powerAssociative? : () -> Boolean     rank : () -> PositiveInteger
--R represents : Vector(R) -> %           rightAlternative? : () -> Boolean
--R rightDiscriminant : () -> R           rightNorm : % -> R
--R rightTrace : % -> R                   rightTraceMatrix : () -> Matrix(R)
--R sample : () -> %                      someBasis : () -> Vector(%)
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
```

```
--R associatorDependence : () -> List(Vector(R)) if R has INTDOM
--R conditionsForIdempotents : () -> List(Polynomial(R))
--R conditionsForIdempotents : Vector(%) -> List(Polynomial(R))
--R coordinates : Vector(%) -> Matrix(R)
--R coordinates : (Vector(%),Vector(%)) -> Matrix(R)
--R coordinates : (%,Vector(%)) -> Vector(R)
--R leftCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R)
--R leftMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if R has INTDOM
--R leftPower : (%,PositiveInteger) -> %
--R leftRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if R has FIELD
--R leftRecip : % -> Union(%,"failed") if R has INTDOM
--R leftRegularRepresentation : % -> Matrix(R)
--R leftRegularRepresentation : (%,Vector(%)) -> Matrix(R)
--R leftTraceMatrix : Vector(%) -> Matrix(R)
--R leftUnit : () -> Union(%,"failed") if R has INTDOM
--R leftUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if R has INTDOM
--R noncommutativeJordanAlgebra? : () -> Boolean
--R plenaryPower : (%,PositiveInteger) -> %
--R recip : % -> Union(%,"failed") if R has INTDOM
--R represents : (Vector(R),Vector(%)) -> %
--R rightCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R)
--R rightDiscriminant : Vector(%) -> R
--R rightMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if R has INTDOM
--R rightPower : (%,PositiveInteger) -> %
--R rightRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if R has FIELD
--R rightRecip : % -> Union(%,"failed") if R has INTDOM
--R rightRegularRepresentation : % -> Matrix(R)
--R rightRegularRepresentation : (%,Vector(%)) -> Matrix(R)
--R rightTraceMatrix : Vector(%) -> Matrix(R)
--R rightUnit : () -> Union(%,"failed") if R has INTDOM
--R rightUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if R has INTDOM
--R structuralConstants : () -> Vector(Matrix(R))
--R structuralConstants : Vector(%) -> Vector(Matrix(R))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit : () -> Union(%,"failed") if R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```


———-

— AlgebraGivenByStructuralConstants.help —

```
=====================================================================
AlgebraGivenByStructuralConstants examples
=====================================================================
```

```
See Also:
o )show AlgebraGivenByStructuralConstants
```

2.4.1 AlgebraGivenByStructuralConstants (ALGSC)



Exports:

0	alternative?
antiAssociative?	antiCommutative?
antiCommutator	apply
associative?	associator
associatorDependence	basis
coerce	commutative?
commutator	conditionsForIdempotents
convert	coordinates
flexible?	hash
jacobiIdentity?	jordanAdmissible?
jordanAlgebra?	latex
leftAlternative?	leftCharacteristicPolynomial
leftDiscriminant	leftMinimalPolynomial
leftNorm	leftPower
leftRankPolynomial	leftRecip
leftRegularRepresentation	leftTrace
leftTraceMatrix	leftUnit
leftUnits	lieAdmissible?
lieAlgebra?	noncommutativeJordanAlgebra?
plenaryPower	powerAssociative?
rank	recip
represents	rightAlternative?
rightCharacteristicPolynomial	rightDiscriminant
rightMinimalPolynomial	rightNorm
rightPower	rightRankPolynomial
rightRecip	rightRegularRepresentation
rightTrace	rightTraceMatrix
rightUnit	rightUnits
sample	someBasis
structuralConstants	subtractIfCan
unit	zero?
?*?	?**?
?+?	?-?
-?	?=?
?.?	?~=?
?*?	

— domain ALGSC AlgebraGivenByStructuralConstants —

```
)abbrev domain ALGSC AlgebraGivenByStructuralConstants
++ Authors: J. Grabmeier, R. Wisbauer
++ Date Created: 01 March 1991
++ Date Last Updated: 22 January 1992
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
```

```
++ Keywords: algebra, structural constants
++ Reference:
++  R.D. Schafer: An Introduction to Nonassociative Algebras
++  Academic Press, New York, 1966
++ Description:
++ AlgebraGivenByStructuralConstants implements finite rank algebras
++ over a commutative ring, given by the structural constants \spad{gamma}
++ with respect to a fixed  basis \spad{[a1,..,an]}, where
++ \spad{gamma} is an \spad{n}-vector of n by n matrices
++ \spad{[(gammaijk) for k in 1..rank()]} defined by
++ \spad{ai * aj = gammaij1 * a1 + ... + gammaijn * an}.
++ The symbols for the fixed basis
++ have to be given as a list of symbols.

AlgebraGivenByStructuralConstants(R:Field, n : PositiveInteger,_
  ls : List Symbol, gamma: Vector Matrix R ): public == private where

  V  ==> Vector
  M  ==> Matrix
  I  ==> Integer
  NNI  ==> NonNegativeInteger
  REC  ==> Record(particular: Union(V R,"failed"),basis: List V R)
  LSMP ==> LinearSystemMatrixPackage(R,V R,V R, M R)

  --public ==> FramedNonAssociativeAlgebra(R) with
  public ==> Join(FramedNonAssociativeAlgebra(R), _
    LeftModule(SquareMatrix(n,R)) ) with

    coerce : Vector R -> %
      ++ coerce(v) converts a vector to a member of the algebra
      ++ by forming a linear combination with the basis element.
      ++ Note: the vector is assumed to have length equal to the
      ++ dimension of the algebra.

  private ==> DirectProduct(n,R) add

    Rep := DirectProduct(n,R)

    x,y : %
    dp : DirectProduct(n,R)
    v : V R


    recip(x) == recip(x)$FiniteRankNonAssociativeAlgebra_&(%,R)

    (m:SquareMatrix(n,R))*(x:%) == apply((m :: Matrix R),x)
    coerce v == directProduct(v) :: %

    structuralConstants() == gamma
```

```
    coordinates(x) == vector(entries(x :: Rep)$Rep)$Vector(R)

    coordinates(x,b) ==
      --not (maxIndex b = n) =>
      --  error("coordinates: your 'basis' has not the right length")
      m : NonNegativeInteger := (maxIndex b) :: NonNegativeInteger
      transitionMatrix   : Matrix R := new(n,m,0$R)$Matrix(R)
      for i in 1..m repeat
        setColumn_!(transitionMatrix,i,coordinates(b.i))
      res : REC := solve(transitionMatrix,coordinates(x))$LSMP
      if (not every?(zero?$R,first res.basis)) then
        error("coordinates: warning your 'basis' is linearly dependent")
      (res.particular  case "failed") =>
        error("coordinates: first argument is not in linear span of second argument")
      (res.particular) :: (Vector R)

    basis() == [unitVector(i::PositiveInteger)::% for i in 1..n]

    someBasis() == basis()$%

    rank() == n

    elt(x,i) == elt(x:Rep,i)$Rep

    coerce(x:%):OutputForm ==
      zero?(x::Rep)$Rep => (0$R) :: OutputForm
      le : List OutputForm := nil
      for i in 1..n repeat
        coef : R := elt(x::Rep,i)
        not zero?(coef)$R =>
--          one?(coef)$R =>
          ((coef) = 1)$R =>
            -- sy : OutputForm := elt(ls,i)$(List Symbol) :: OutputForm
            le := cons(elt(ls,i)$(List Symbol) :: OutputForm, le)
          le := cons(coef :: OutputForm *  elt(ls,i)$(List Symbol)_
              :: OutputForm, le)
      reduce("+",le)

    x * y ==
      v : Vector R :=  new(n,0)
      for k in 1..n repeat
        h : R := 0
        for i in 1..n repeat
          for j in 1..n repeat
            h := h  +$R elt(x,i) *$R elt(y,j) *$R elt(gamma.k,i,j )
        v.k := h
      directProduct v
```

```
alternative?() ==
  for i in 1..n repeat
    -- expression for check of left alternative is symmetric in i and j:
    -- expression for check of right alternative is symmetric in j and k:
    for j in 1..i-1 repeat
      for k in j..n repeat
        -- right check
        for r in 1..n repeat
          res := 0$R
          for l in 1..n repeat
            res := res - _
              (elt(gamma.l,j,k)+elt(gamma.l,k,j))*elt(gamma.r,i,l)+_
              (elt(gamma.l,i,j)*elt(gamma.r,l,k) + elt(gamma.l,i,k)*_
              elt(gamma.r,l,j) )
          not zero? res =>
            messagePrint("algebra is not right alternative")$OutputForm
            return false
    for j in i..n repeat
      for k in 1..j-1 repeat
        -- left check
        for r in 1..n repeat
          res := 0$R
          for l in 1..n repeat
            res := res + _
              (elt(gamma.l,i,j)+elt(gamma.l,j,i))*elt(gamma.r,l,k)-_
              (elt(gamma.l,j,k)*elt(gamma.r,i,l) + elt(gamma.l,i,k)*_
               elt(gamma.r,j,l) )
          not (zero? res) =>
            messagePrint("algebra is not left alternative")$OutputForm
            return false

      for k in j..n repeat
        -- left check
        for r in 1..n repeat
          res := 0$R
          for l in 1..n repeat
            res := res + _
              (elt(gamma.l,i,j)+elt(gamma.l,j,i))*elt(gamma.r,l,k)-_
              (elt(gamma.l,j,k)*elt(gamma.r,i,l) + elt(gamma.l,i,k)*_
               elt(gamma.r,j,l) )
          not (zero? res) =>
            messagePrint("algebra is not left alternative")$OutputForm
            return false
        -- right check
        for r in 1..n repeat
          res := 0$R
          for l in 1..n repeat
            res := res - _
              (elt(gamma.l,j,k)+elt(gamma.l,k,j))*elt(gamma.r,i,l)+_
              (elt(gamma.l,i,j)*elt(gamma.r,l,k) + elt(gamma.l,i,k)*_
```

```
                elt(gamma.r,l,j) )
              not (zero? res) =>
                messagePrint("algebra is not right alternative")$OutputForm
                return false

      messagePrint("algebra satisfies 2*associator(a,b,b) = 0 = 2*associator(a,a,b) = 0")$OutputForm
      true

    -- should be in the category, but is not exported
--    conditionsForIdempotents b  ==
--      n := rank()
--      --gamma : Vector Matrix R := structuralConstants b
--      listOfNumbers : List String :=  [STRINGIMAGE(q)$Lisp for q in 1..n]
--      symbolsForCoef : Vector Symbol :=
--        [concat("%", concat("x", i))::Symbol  for i in listOfNumbers]
--      conditions : List Polynomial R := []
 --     for k in 1..n repeat
 --       xk := symbolsForCoef.k
 --       p : Polynomial R :=  monomial( - 1$Polynomial(R), [xk], [1] )
 --       for i in 1..n repeat
 --         for j in 1..n repeat
 --           xi := symbolsForCoef.i
 --           xj := symbolsForCoef.j
 --           p := p + monomial(_
 --             elt((gamma.k),i,j) :: Polynomial(R), [xi,xj], [1,1])
 --       conditions := cons(p,conditions)
 --     conditions

    associative?() ==
      for i in 1..n repeat
       for j in 1..n repeat
        for k in 1..n repeat
         for r in 1..n repeat
           res := 0$R
           for l in 1..n repeat
             res := res + elt(gamma.l,i,j)*elt(gamma.r,l,k)-_
                          elt(gamma.l,j,k)*elt(gamma.r,i,l)
           not (zero? res) =>
            messagePrint("algebra is not associative")$OutputForm
            return false
      messagePrint("algebra is associative")$OutputForm
      true


    antiAssociative?() ==
      for i in 1..n repeat
       for j in 1..n repeat
        for k in 1..n repeat
         for r in 1..n repeat
           res := 0$R
```

```
        for l in 1..n repeat
          res := res + elt(gamma.l,i,j)*elt(gamma.r,l,k)+_
                       elt(gamma.l,j,k)*elt(gamma.r,i,l)
        not (zero? res) =>
         messagePrint("algebra is not anti-associative")$OutputForm
         return false
  messagePrint("algebra is anti-associative")$OutputForm
  true

commutative?() ==
  for i in 1..n repeat
   for j in (i+1)..n repeat
    for k in 1..n repeat
       not ( elt(gamma.k,i,j)=elt(gamma.k,j,i) ) =>
        messagePrint("algebra is not commutative")$OutputForm
        return false
  messagePrint("algebra is commutative")$OutputForm
  true

antiCommutative?() ==
  for i in 1..n repeat
   for j in i..n repeat
    for k in 1..n repeat
      not zero? (i=j => elt(gamma.k,i,i); elt(gamma.k,i,j)+elt(gamma.k,j,i) ) =>
        messagePrint("algebra is not anti-commutative")$OutputForm
        return false
  messagePrint("algebra is anti-commutative")$OutputForm
  true

leftAlternative?() ==
  for i in 1..n repeat
   -- expression is symmetric in i and j:
   for j in i..n repeat
    for k in 1..n repeat
     for r in 1..n repeat
       res := 0$R
       for l in 1..n repeat
         res := res + (elt(gamma.l,i,j)+elt(gamma.l,j,i))*elt(gamma.r,l,k)-_
           (elt(gamma.l,j,k)*elt(gamma.r,i,l) + elt(gamma.l,i,k)*elt(gamma.r,j,l) )
       not (zero? res) =>
        messagePrint("algebra is not left alternative")$OutputForm
        return false
  messagePrint("algebra is left alternative")$OutputForm
  true


rightAlternative?() ==
  for i in 1..n repeat
   for j in 1..n repeat
   -- expression is symmetric in j and k:
```

```
      for k in j..n repeat
       for r in 1..n repeat
         res := 0$R
         for l in 1..n repeat
           res := res - (elt(gamma.l,j,k)+elt(gamma.l,k,j))*elt(gamma.r,i,l)+_
             (elt(gamma.l,i,j)*elt(gamma.r,l,k) + elt(gamma.l,i,k)*elt(gamma.r,l,j) )
         not (zero? res) =>
          messagePrint("algebra is not right alternative")$OutputForm
          return false
    messagePrint("algebra is right alternative")$OutputForm
    true


  flexible?() ==
    for i in 1..n repeat
     for j in 1..n repeat
     -- expression is symmetric in i and k:
      for k in i..n repeat
       for r in 1..n repeat
         res := 0$R
         for l in 1..n repeat
           res := res + elt(gamma.l,i,j)*elt(gamma.r,l,k)-_
                        elt(gamma.l,j,k)*elt(gamma.r,i,l)+_
                        elt(gamma.l,k,j)*elt(gamma.r,l,i)-_
                        elt(gamma.l,j,i)*elt(gamma.r,k,l)
         not (zero? res) =>
          messagePrint("algebra is not flexible")$OutputForm
          return false
    messagePrint("algebra is flexible")$OutputForm
    true

  lieAdmissible?() ==
    for i in 1..n repeat
     for j in 1..n repeat
      for k in 1..n repeat
       for r in 1..n repeat
         res := 0$R
         for l in 1..n repeat
           res := res_
            + (elt(gamma.l,i,j)-elt(gamma.l,j,i))*(elt(gamma.r,l,k)-elt(gamma.r,k,l)) _
            + (elt(gamma.l,j,k)-elt(gamma.l,k,j))*(elt(gamma.r,l,i)-elt(gamma.r,i,l)) _
            + (elt(gamma.l,k,i)-elt(gamma.l,i,k))*(elt(gamma.r,l,j)-elt(gamma.r,j,l))
         not (zero? res) =>
          messagePrint("algebra is not Lie admissible")$OutputForm
          return false
    messagePrint("algebra is Lie admissible")$OutputForm
    true

  jordanAdmissible?()  ==
    recip(2 * 1$R) case "failed" =>
```

```
      messagePrint("this algebra is not Jordan admissible, as 2 is not invertible in the groun
      false
    for i in 1..n repeat
     for j in 1..n repeat
      for k in 1..n repeat
       for w in 1..n repeat
        for t in 1..n repeat
         res := 0$R
         for l in 1..n repeat
          for r in 1..n repeat
           res := res_
            + (elt(gamma.l,i,j)+elt(gamma.l,j,i))_
              * (elt(gamma.r,w,k)+elt(gamma.r,k,w))_
              * (elt(gamma.t,l,r)+elt(gamma.t,r,l))_
            - (elt(gamma.r,w,k)+elt(gamma.r,k,w))_
              * (elt(gamma.l,j,r)+elt(gamma.l,r,j))_
              * (elt(gamma.t,i,l)+elt(gamma.t,l,i))_
            + (elt(gamma.l,w,j)+elt(gamma.l,j,w))_
              * (elt(gamma.r,k,i)+elt(gamma.r,i,k))_
              * (elt(gamma.t,l,r)+elt(gamma.t,r,l))_
            - (elt(gamma.r,k,i)+elt(gamma.r,k,i))_
              * (elt(gamma.l,j,r)+elt(gamma.l,r,j))_
              * (elt(gamma.t,w,l)+elt(gamma.t,l,w))_
            + (elt(gamma.l,k,j)+elt(gamma.l,j,k))_
              * (elt(gamma.r,i,w)+elt(gamma.r,w,i))_
              * (elt(gamma.t,l,r)+elt(gamma.t,r,l))_
            - (elt(gamma.r,i,w)+elt(gamma.r,w,i))_
              * (elt(gamma.l,j,r)+elt(gamma.l,r,j))_
              * (elt(gamma.t,k,l)+elt(gamma.t,l,k))
         not (zero? res) =>
           messagePrint("algebra is not Jordan admissible")$OutputForm
           return false
    messagePrint("algebra is Jordan admissible")$OutputForm
    true

  jordanAlgebra?()  ==
    recip(2 * 1$R) case "failed" =>
      messagePrint("this is not a Jordan algebra, as 2 is not invertible in the ground ring")$
      false
    not commutative?() =>
      messagePrint("this is not a Jordan algebra")$OutputForm
      false
    for i in 1..n repeat
     for j in 1..n repeat
      for k in 1..n repeat
       for l in 1..n repeat
         for t in 1..n repeat
           res := 0$R
           for r in 1..n repeat
             for s in 1..n repeat
```

```
                res := res +  _
                  elt(gamma.r,i,j)*elt(gamma.s,l,k)*elt(gamma.t,r,s) - _
                  elt(gamma.r,l,k)*elt(gamma.s,j,r)*elt(gamma.t,i,s) + _
                  elt(gamma.r,l,j)*elt(gamma.s,k,k)*elt(gamma.t,r,s) - _
                  elt(gamma.r,k,i)*elt(gamma.s,j,r)*elt(gamma.t,l,s) + _
                  elt(gamma.r,k,j)*elt(gamma.s,i,k)*elt(gamma.t,r,s) - _
                  elt(gamma.r,i,l)*elt(gamma.s,j,r)*elt(gamma.t,k,s)
                not zero? res =>
                  messagePrint("this is not a Jordan algebra")$OutputForm
                  return false
      messagePrint("this is a Jordan algebra")$OutputForm
      true


    jacobiIdentity?()  ==
      for i in 1..n repeat
       for j in 1..n repeat
        for k in 1..n repeat
         for r in 1..n repeat
           res := 0$R
           for s in 1..n repeat
                 res := res +  elt(gamma.r,i,j)*elt(gamma.s,j,k) +_
                               elt(gamma.r,j,k)*elt(gamma.s,k,i) +_
                               elt(gamma.r,k,i)*elt(gamma.s,i,j)
           not zero? res =>
                 messagePrint("Jacobi identity does not hold")$OutputForm
                 return false
      messagePrint("Jacobi identity holds")$OutputForm
      true
```

———-

— ALGSC.dotabb —

```
"ALGSC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALGSC"]
"FRNAALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRNAALG"]
"ALGSC" -> "FRNAALG"
```

———-

2.5 domain ALGFF AlgebraicFunctionField

— AlgebraicFunctionField.input —

```
)set break resume
```

```
)sys rm -f AlgebraicFunctionField.output
)spool AlgebraicFunctionField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AlgebraicFunctionField
--R
--R AlgebraicFunctionField(F: Field,UP: UnivariatePolynomialCategory(F),UPUP: UnivariatePolynomi
--R Abbreviation for AlgebraicFunctionField is ALGFF
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ALGFF
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(UP),%) -> %           ?*? : (%,Fraction(UP)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        basis : () -> Vector(%)
--R branchPoint? : UP -> Boolean          branchPoint? : F -> Boolean
--R coerce : Fraction(UP) -> %            coerce : Integer -> %
--R coerce : % -> OutputForm              convert : UPUP -> %
--R convert : % -> UPUP                   definingPolynomial : () -> UPUP
--R discriminant : () -> Fraction(UP)     elt : (%,F,F) -> F
--R generator : () -> %                   genus : () -> NonNegativeInteger
--R hash : % -> SingleInteger             integral? : (%,UP) -> Boolean
--R integral? : (%,F) -> Boolean          integral? : % -> Boolean
--R integralBasis : () -> Vector(%)       latex : % -> String
--R lift : % -> UPUP                      norm : % -> Fraction(UP)
--R one? : % -> Boolean                   primitivePart : % -> %
--R ramified? : UP -> Boolean             ramified? : F -> Boolean
--R rank : () -> PositiveInteger          rationalPoint? : (F,F) -> Boolean
--R recip : % -> Union(%,"failed")        reduce : UPUP -> %
--R represents : (Vector(UP),UP) -> %     retract : % -> Fraction(UP)
--R sample : () -> %                      singular? : UP -> Boolean
--R singular? : F -> Boolean              trace : % -> Fraction(UP)
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Fraction(UP) has FIELD
--R ?*? : (Fraction(Integer),%) -> % if Fraction(UP) has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Integer) -> % if Fraction(UP) has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if Fraction(UP) has FIELD
--R D : % -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fraction(UP) has FFIELD
--R D : (%,NonNegativeInteger) -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fr
--R D : (%,Symbol) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
```

```
--R D : (%,Symbol,NonNegativeInteger) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRIN
--R D : (%,(Fraction(UP) -> Fraction(UP))) -> % if Fraction(UP) has FIELD
--R D : (%,(Fraction(UP) -> Fraction(UP)),NonNegativeInteger) -> % if Fraction(UP) has FIELD
--R ?^? : (%,Integer) -> % if Fraction(UP) has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R absolutelyIrreducible? : () -> Boolean
--R algSplitSimple : (%,(UP -> UP)) -> Record(num: %,den: UP,derivden: UP,gd: UP)
--R associates? : (%,%) -> Boolean if Fraction(UP) has FIELD
--R branchPointAtInfinity? : () -> Boolean
--R characteristic : () -> NonNegativeInteger
--R characteristicPolynomial : % -> UPUP
--R charthRoot : % -> Union(%,"failed") if Fraction(UP) has CHARNZ
--R charthRoot : % -> % if Fraction(UP) has FFIELDC
--R coerce : % -> % if Fraction(UP) has FIELD
--R coerce : Fraction(Integer) -> % if Fraction(UP) has FIELD or Fraction(UP) has RETRACT(FRAC(INT))
--R complementaryBasis : Vector(%) -> Vector(%)
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if Fraction(UP) has FFIELDC
--R convert : Vector(Fraction(UP)) -> %
--R convert : % -> Vector(Fraction(UP))
--R coordinates : Vector(%) -> Matrix(Fraction(UP))
--R coordinates : % -> Vector(Fraction(UP))
--R coordinates : (Vector(%),Vector(%)) -> Matrix(Fraction(UP))
--R coordinates : (%,Vector(%)) -> Vector(Fraction(UP))
--R createPrimitiveElement : () -> % if Fraction(UP) has FFIELDC
--R derivationCoordinates : (Vector(%),(Fraction(UP) -> Fraction(UP))) -> Matrix(Fraction(UP)) if Fraction(U
--R differentiate : % -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fraction(UP) has FFIELD
--R differentiate : (%,NonNegativeInteger) -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fr
--R differentiate : (%,Symbol) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRIN
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Fraction(UP) has FIELD and Fraction(UP
--R differentiate : (%,(UP -> UP)) -> %
--R differentiate : (%,(Fraction(UP) -> Fraction(UP))) -> % if Fraction(UP) has FIELD
--R differentiate : (%,(Fraction(UP) -> Fraction(UP)),NonNegativeInteger) -> % if Fraction(UP) has FIELD
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if Fraction(UP) has FFIELDC
--R discreteLog : % -> NonNegativeInteger if Fraction(UP) has FFIELDC
--R discriminant : Vector(%) -> Fraction(UP)
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Fraction(UP) has FIELD
--R elliptic : () -> Union(UP,"failed")
--R euclideanSize : % -> NonNegativeInteger if Fraction(UP) has FIELD
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Fraction(UP) has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Fraction(UP) has FIELD
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Fraction(UP) has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Fraction(UP) has FIELD
--R factor : % -> Factored(%) if Fraction(UP) has FIELD
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if Fraction(UP) has FF
--R gcd : (%,%) -> % if Fraction(UP) has FIELD
--R gcd : List(%) -> % if Fraction(UP) has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
```

```
--R hyperelliptic : () -> Union(UP,"failed")
--R index : PositiveInteger -> % if Fraction(UP) has FINITE
--R init : () -> % if Fraction(UP) has FFIELDC
--R integralAtInfinity? : % -> Boolean
--R integralBasisAtInfinity : () -> Vector(%)
--R integralCoordinates : % -> Record(num: Vector(UP),den: UP)
--R integralDerivationMatrix : (UP -> UP) -> Record(num: Matrix(UP),den: UP)
--R integralMatrix : () -> Matrix(Fraction(UP))
--R integralMatrixAtInfinity : () -> Matrix(Fraction(UP))
--R integralRepresents : (Vector(UP),UP) -> %
--R inv : % -> % if Fraction(UP) has FIELD
--R inverseIntegralMatrix : () -> Matrix(Fraction(UP))
--R inverseIntegralMatrixAtInfinity : () -> Matrix(Fraction(UP))
--R knownInfBasis : NonNegativeInteger -> Void
--R lcm : (%,%) -> % if Fraction(UP) has FIELD
--R lcm : List(%) -> % if Fraction(UP) has FIELD
--R lookup : % -> PositiveInteger if Fraction(UP) has FINITE
--R minimalPolynomial : % -> UPUP if Fraction(UP) has FIELD
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Fraction(UP) has FIELD
--R nextItem : % -> Union(%,"failed") if Fraction(UP) has FFIELDC
--R nonSingularModel : Symbol -> List(Polynomial(F)) if F has FIELD
--R normalizeAtInfinity : Vector(%) -> Vector(%)
--R numberOfComponents : () -> NonNegativeInteger
--R order : % -> OnePointCompletion(PositiveInteger) if Fraction(UP) has FFIELDC
--R order : % -> PositiveInteger if Fraction(UP) has FFIELDC
--R prime? : % -> Boolean if Fraction(UP) has FIELD
--R primeFrobenius : % -> % if Fraction(UP) has FFIELDC
--R primeFrobenius : (%,NonNegativeInteger) -> % if Fraction(UP) has FFIELDC
--R primitive? : % -> Boolean if Fraction(UP) has FFIELDC
--R primitiveElement : () -> % if Fraction(UP) has FFIELDC
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Fraction(UP) has FIELD
--R ?quo? : (%,%) -> % if Fraction(UP) has FIELD
--R ramifiedAtInfinity? : () -> Boolean
--R random : () -> % if Fraction(UP) has FINITE
--R rationalPoints : () -> List(List(F)) if F has FINITE
--R reduce : Fraction(UPUP) -> Union(%,"failed") if Fraction(UP) has FIELD
--R reduceBasisAtInfinity : Vector(%) -> Vector(%)
--R reducedSystem : Matrix(%) -> Matrix(Fraction(UP))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Fraction(UP)),vec: Vector(Fracti
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if Fraction(UP) has LINEXP(INT)
--R regularRepresentation : % -> Matrix(Fraction(UP))
--R regularRepresentation : (%,Vector(%)) -> Matrix(Fraction(UP))
--R ?rem? : (%,%) -> % if Fraction(UP) has FIELD
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if Fraction(UP) has FFIEL
--R represents : Vector(Fraction(UP)) -> %
--R represents : (Vector(Fraction(UP)),Vector(%)) -> %
--R retract : % -> Fraction(Integer) if Fraction(UP) has RETRACT(FRAC(INT))
--R retract : % -> Integer if Fraction(UP) has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(UP),"failed")
```

```
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if Fraction(UP) has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if Fraction(UP) has RETRACT(INT)
--R singularAtInfinity? : () -> Boolean
--R size : () -> NonNegativeInteger if Fraction(UP) has FINITE
--R sizeLess? : (%,%) -> Boolean if Fraction(UP) has FIELD
--R squareFree : % -> Factored(%) if Fraction(UP) has FIELD
--R squareFreePart : % -> % if Fraction(UP) has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if Fraction(UP) has FF
--R traceMatrix : () -> Matrix(Fraction(UP))
--R traceMatrix : Vector(%) -> Matrix(Fraction(UP))
--R unit? : % -> Boolean if Fraction(UP) has FIELD
--R unitCanonical : % -> % if Fraction(UP) has FIELD
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Fraction(UP) has FIELD
--R yCoordinates : % -> Record(num: Vector(UP),den: UP)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **AlgebraicFunctionField.help** —

```
=====================================================================
AlgebraicFunctionField examples
=====================================================================

See Also:
o )show AlgebraicFunctionField
```

———-

2.5.1 AlgebraicFunctionField (ALGFF)



See

⇒ "RadicalFunctionField" (RADFF) 19.1.1 on page 2159

Exports:

1	0	absolutelyIrreducible?
algSplitSimple	associates?	basis
branchPoint?	branchPointAtInfinity?	characteristic
characteristicPolynomial	charthRoot	coerce
complementaryBasis	conditionP	convert
coordinates	createPrimitiveElement	D
definingPolynomial	derivationCoordinates	differentiate
discreteLog	discriminant	divide
elliptic	elt	euclideanSize
expressIdealMember	exquo	extendedEuclidean
factor	factorsOfCyclicGroupSize	gcd
gcdPolynomial	generator	genus
hash	hyperelliptic	index
init	integral?	integralAtInfinity?
integralBasis	integralBasisAtInfinity	integralCoordinates
integralDerivationMatrix	integralMatrix	integralMatrixAtInfinity
integralRepresents	inv	inverseIntegralMatrix
inverseIntegralMatrixAtInfinity	knownInfBasis	latex
lcm	lift	lookup
minimalPolynomial	multiEuclidean	nextItem
nonSingularModel	norm	normalizeAtInfinity
numberOfComponents	one?	order
prime?	primeFrobenius	primitive?
primitiveElement	primitivePart	principalIdeal
ramified?	ramifiedAtInfinity?	random
rank	rationalPoint?	rationalPoints
recip	reduce	reduceBasisAtInfinity
reducedSystem	regularRepresentation	representationType
represents	retract	retractIfCan
sample	singular?	singularAtInfinity?
size	sizeLess?	squareFree
squareFreePart	subtractIfCan	tableForDiscreteLogarithm
trace	traceMatrix	unit?
unitCanonical	unitNormal	yCoordinates
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?
?/?	?quo?	?rem?

— domain ALGFF AlgebraicFunctionField —

```
)abbrev domain ALGFF AlgebraicFunctionField
```

```
++ Author: Manuel Bronstein
++ Date Created: 3 May 1988
++ Date Last Updated: 24 Jul 1990
++ Keywords: algebraic, curve, function, field.
++ Description:
++ Function field defined by f(x, y) = 0.

AlgebraicFunctionField(F, UP, UPUP, modulus): Exports == Impl where
  F      : Field
  UP     : UnivariatePolynomialCategory F
  UPUP   : UnivariatePolynomialCategory Fraction UP
  modulus: UPUP

  N   ==> NonNegativeInteger
  Z   ==> Integer
  RF  ==> Fraction UP
  QF  ==> Fraction UPUP
  UP2 ==> SparseUnivariatePolynomial UP
  SAE ==> SimpleAlgebraicExtension(RF, UPUP, modulus)
  INIT ==> if (deref brandNew?) then startUp false

  Exports ==> FunctionFieldCategory(F, UP, UPUP) with
    knownInfBasis: N -> Void
        ++ knownInfBasis(n) is not documented

  Impl ==> SAE add
    import ChangeOfVariable(F, UP, UPUP)
    import InnerCommonDenominator(UP, RF, Vector UP, Vector RF)
    import MatrixCommonDenominator(UP, RF)
    import UnivariatePolynomialCategoryFunctions2(RF, UPUP, UP, UP2)

    startUp    : Boolean -> Void
    vect       : Matrix RF -> Vector $
    getInfBasis: () -> Void

    brandNew?:Reference(Boolean) := ref true
    infBr?:Reference(Boolean) := ref true
    discPoly:Reference(RF) := ref 0
    n  := degree modulus
    n1 := (n - 1)::N
    ibasis:Matrix(RF)     := zero(n, n)
    invibasis:Matrix(RF)  := copy ibasis
    infbasis:Matrix(RF)   := copy ibasis
    invinfbasis:Matrix(RF):= copy ibasis

    branchPointAtInfinity?()   == (INIT; infBr?())
    discriminant()             == (INIT; discPoly())
    integralBasis()            == (INIT; vect ibasis)
    integralBasisAtInfinity()  == (INIT; vect infbasis)
    integralMatrix()           == (INIT; ibasis)
```

```
inverseIntegralMatrix()    == (INIT; invibasis)
integralMatrixAtInfinity() == (INIT; infbasis)
branchPoint?(a:F)          == zero?((retract(discriminant())@UP) a)
definingPolynomial()       == modulus
inverseIntegralMatrixAtInfinity() == (INIT; invinfbasis)

vect m ==
  [represents row(m, i) for i in minRowIndex m .. maxRowIndex m]

integralCoordinates f ==
  splitDenominator(coordinates(f) * inverseIntegralMatrix())

knownInfBasis d ==
  if deref brandNew? then
    alpha := [monomial(1, d * i)$UP :: RF for i in 0..n1]$Vector(RF)
    ib := diagonalMatrix
      [inv qelt(alpha, i) for i in minIndex alpha .. maxIndex alpha]
    invib := diagonalMatrix alpha
    for i in minRowIndex ib .. maxRowIndex ib repeat
      for j in minColIndex ib .. maxColIndex ib repeat
        infbasis(i, j)    := qelt(ib, i, j)
        invinfbasis(i, j) := invib(i, j)
  void

getInfBasis() ==
  x           := inv(monomial(1, 1)$UP :: RF)
  invmod      := map(s +-> s(x), modulus)
  r           := mkIntegral invmod
  degree(r.poly) ^= n => error "Should not happen"
  ninvmod:UP2 := map(s +-> retract(s)@UP, r.poly)
  alpha       := [(r.coef ** i) x for i in 0..n1]$Vector(RF)
  invalpha := [inv qelt(alpha, i)
               for i in minIndex alpha .. maxIndex alpha]$Vector(RF)
  invib       := integralBasis()$FunctionFieldIntegralBasis(UP, UP2,
                        SimpleAlgebraicExtension(UP, UP2, ninvmod))
  for i in minRowIndex ibasis .. maxRowIndex ibasis repeat
    for j in minColIndex ibasis .. maxColIndex ibasis repeat
      infbasis(i, j)    := ((invib.basis)(i,j) / invib.basisDen) x
      invinfbasis(i, j) := ((invib.basisInv) (i, j)) x
  ib2    := infbasis * diagonalMatrix alpha
  invib2 := diagonalMatrix(invalpha) * invinfbasis
  for i in minRowIndex ib2 .. maxRowIndex ib2 repeat
    for j in minColIndex ibasis .. maxColIndex ibasis repeat
      infbasis(i, j)    := qelt(ib2, i, j)
      invinfbasis(i, j) := invib2(i, j)
  void

startUp b ==
  brandNew?() := b
  nmod:UP2    := map(retract, modulus)
```

```
      ib          := integralBasis()$FunctionFieldIntegralBasis(UP, UP2,
                                SimpleAlgebraicExtension(UP, UP2, nmod))
      for i in minRowIndex ibasis .. maxRowIndex ibasis repeat
        for j in minColIndex ibasis .. maxColIndex ibasis repeat
          qsetelt_!(ibasis, i, j, (ib.basis)(i, j) / ib.basisDen)
          invibasis(i, j) := ((ib.basisInv) (i, j))::RF
      if zero?(infbasis(minRowIndex infbasis, minColIndex infbasis))
        then getInfBasis()
      ib2    := coordinates normalizeAtInfinity vect ibasis
      invib2 := inverse(ib2)::Matrix(RF)
      for i in minRowIndex ib2 .. maxRowIndex ib2 repeat
        for j in minColIndex ib2 .. maxColIndex ib2 repeat
          ibasis(i, j)    := qelt(ib2, i, j)
          invibasis(i, j) := invib2(i, j)
      dsc  := resultant(modulus, differentiate modulus)
      dsc0 := dsc * determinant(infbasis) ** 2
      degree(numer dsc0) > degree(denom dsc0) =>error "Shouldn't happen"
      infBr?() := degree(numer dsc0) < degree(denom dsc0)
      dsc := dsc * determinant(ibasis) ** 2
      discPoly() := primitivePart(numer dsc) / denom(dsc)
      void

    integralDerivationMatrix d ==
      w := integralBasis()
      splitDenominator(coordinates([differentiate(w.i, d)
          for i in minIndex w .. maxIndex w]$Vector($))
               * inverseIntegralMatrix())

    integralRepresents(v, d) ==
      represents(coordinates(represents(v, d)) * integralMatrix())

    branchPoint?(p:UP) ==
      INIT
      (r:=retractIfCan(p)@Union(F,"failed")) case F =>branchPoint?(r::F)
      not ground? gcd(retract(discriminant())@UP, p)
```

———-

— ALGFF.dotabb —

```
"ALGFF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALGFF"]
"FFCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FFCAT"]
"ALGFF" -> "FFCAT"
```

———-

2.6 domain AN AlgebraicNumber

— AlgebraicNumber.input —

```
)set break resume
)sys rm -f AlgebraicNumber.output
)spool AlgebraicNumber.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AlgebraicNumber
--R
--R AlgebraicNumber  is a domain constructor
--R Abbreviation for AlgebraicNumber is AN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for AN
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?*? : (Integer,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?**? : (%,PositiveInteger) -> %
--R ?**? : (%,Integer) -> %               ?+? : (%,%) -> %
--R -? : % -> %                           ?-? : (%,%) -> %
--R ?/? : (%,%) -> %                      ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R D : % -> %                            D : (%,NonNegativeInteger) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        ?^? : (%,Integer) -> %
--R associates? : (%,%) -> Boolean        belong? : BasicOperator -> Boolean
--R box : List(%) -> %                    box : % -> %
--R coerce : Integer -> %                 coerce : % -> %
--R coerce : Fraction(Integer) -> %       coerce : Kernel(%) -> %
--R coerce : % -> OutputForm              convert : % -> Complex(Float)
--R convert : % -> DoubleFloat            convert : % -> Float
--R differentiate : % -> %                distribute : (%,%) -> %
--R distribute : % -> %                   elt : (BasicOperator,%,%) -> %
--R elt : (BasicOperator,%) -> %          eval : (%,%,%) -> %
--R eval : (%,Equation(%)) -> %           eval : (%,Kernel(%),%) -> %
--R factor : % -> Factored(%)             freeOf? : (%,Symbol) -> Boolean
--R freeOf? : (%,%) -> Boolean            gcd : (%,%) -> %
--R gcd : List(%) -> %                    hash : % -> SingleInteger
--R height : % -> NonNegativeInteger      inv : % -> %
--R is? : (%,Symbol) -> Boolean           kernel : (BasicOperator,%) -> %
--R kernels : % -> List(Kernel(%))        latex : % -> String
--R lcm : (%,%) -> %                      lcm : List(%) -> %
```

```
--R max : (%,%) -> %                        min : (%,%) -> %
--R norm : (%,List(Kernel(%))) -> %         norm : (%,Kernel(%)) -> %
--R nthRoot : (%,Integer) -> %              one? : % -> Boolean
--R paren : List(%) -> %                    paren : % -> %
--R prime? : % -> Boolean                   ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")          reduce : % -> %
--R ?rem? : (%,%) -> %                      retract : % -> Fraction(Integer)
--R retract : % -> Integer                  retract : % -> Kernel(%)
--R rootOf : Polynomial(%) -> %             sample : () -> %
--R sizeLess? : (%,%) -> Boolean            sqrt : % -> %
--R squareFree : % -> Factored(%)           squareFreePart : % -> %
--R subst : (%,Equation(%)) -> %            tower : % -> List(Kernel(%))
--R unit? : % -> Boolean                    unitCanonical : % -> %
--R zero? : % -> Boolean                    zeroOf : Polynomial(%) -> %
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?**? : (%,Fraction(Integer)) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coerce : SparseMultivariatePolynomial(Integer,Kernel(%)) -> %
--R definingPolynomial : % -> % if $ has RING
--R denom : % -> SparseMultivariatePolynomial(Integer,Kernel(%))
--R differentiate : (%,NonNegativeInteger) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R elt : (BasicOperator,List(%)) -> %
--R elt : (BasicOperator,%,%,%,%) -> %
--R elt : (BasicOperator,%,%,%) -> %
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,BasicOperator,(% -> %)) -> %
--R eval : (%,BasicOperator,(List(%) -> %)) -> %
--R eval : (%,List(BasicOperator),List((List(%) -> %))) -> %
--R eval : (%,List(BasicOperator),List((% -> %))) -> %
--R eval : (%,Symbol,(% -> %)) -> %
--R eval : (%,Symbol,(List(%) -> %)) -> %
--R eval : (%,List(Symbol),List((List(%) -> %))) -> %
--R eval : (%,List(Symbol),List((% -> %))) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R eval : (%,List(Kernel(%)),List(%)) -> %
--R even? : % -> Boolean if $ has RETRACT(INT)
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R is? : (%,BasicOperator) -> Boolean
--R kernel : (BasicOperator,List(%)) -> %
--R mainKernel : % -> Union(Kernel(%),"failed")
--R map : ((% -> %),Kernel(%)) -> %
```

```
--R minPoly : Kernel(%) -> SparseUnivariatePolynomial(%) if $ has RING
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R norm : (SparseUnivariatePolynomial(%),List(Kernel(%))) -> SparseUnivariatePolynomial(%)
--R norm : (SparseUnivariatePolynomial(%),Kernel(%)) -> SparseUnivariatePolynomial(%)
--R numer : % -> SparseMultivariatePolynomial(Integer,Kernel(%))
--R odd? : % -> Boolean if $ has RETRACT(INT)
--R operator : BasicOperator -> BasicOperator
--R operators : % -> List(BasicOperator)
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R reducedSystem : Matrix(%) -> Matrix(Fraction(Integer))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Fraction(Integer)),vec: Vector(F
--R reducedSystem : Matrix(%) -> Matrix(Integer)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer))
--R retractIfCan : % -> Union(Fraction(Integer),"failed")
--R retractIfCan : % -> Union(Integer,"failed")
--R retractIfCan : % -> Union(Kernel(%),"failed")
--R rootOf : SparseUnivariatePolynomial(%) -> %
--R rootOf : (SparseUnivariatePolynomial(%),Symbol) -> %
--R rootsOf : Polynomial(%) -> List(%)
--R rootsOf : SparseUnivariatePolynomial(%) -> List(%)
--R rootsOf : (SparseUnivariatePolynomial(%),Symbol) -> List(%)
--R subst : (%,List(Kernel(%)),List(%)) -> %
--R subst : (%,List(Equation(%))) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R zeroOf : SparseUnivariatePolynomial(%) -> %
--R zeroOf : (SparseUnivariatePolynomial(%),Symbol) -> %
--R zerosOf : Polynomial(%) -> List(%)
--R zerosOf : SparseUnivariatePolynomial(%) -> List(%)
--R zerosOf : (SparseUnivariatePolynomial(%),Symbol) -> List(%)
--R
--E 1

)spool
)lisp (bye)
```

———-


— AlgebraicNumber.help —

```
=====================================================================
AlgebraicNumber examples
=====================================================================

See Also:
o )show AlgebraicNumber
```

———-

2.6.1 AlgebraicNumber (AN)



See

⇒ "InnerAlgebraicNumber" (IAN) 10.20.1 on page 1244

Exports:

1	0	associates?	belong?
box	characteristic	coerce	convert
D	definingPolynomial	denom	differentiate
distribute	divide	elt	euclideanSize
eval	even?	expressIdealMember	exquo
extendedEuclidean	factor	freeOf?	gcd
gcdPolynomial	hash	height	inv
is?	kernel	kernels	latex
lcm	mainKernel	map	max
min	minPoly	multiEuclidean	norm
nthRoot	numer	odd?	one?
operator	operators	paren	prime?
principalIdeal	recip	reduce	reducedSystem
retract	retractIfCan	rootOf	rootsOf
sample	sizeLess?	sqrt	squareFree
squareFreePart	subst	subtractIfCan	tower
unit?	unitCanonical	unitNormal	zero?
zeroOf	zerosOf	?*?	?**?
?+?	-?	?-?	?/?
?<?	?<=?	?=?	?>?
?>=?	?^?	?quo?	?rem?
?~=?			

— domain AN AlgebraicNumber —

```
)abbrev domain AN AlgebraicNumber
++ Author: James Davenport
++ Date Created: 9 October 1995
++ Date Last Updated: 10 October 1995 (JHD)
++ Keywords: algebraic, number.
```

```
++ Description:
++ Algebraic closure of the rational numbers, with mathematical =

AlgebraicNumber(): Exports == Implementation where
  Z   ==> Integer
  P   ==> SparseMultivariatePolynomial(Z, Kernel %)
  SUP ==>  SparseUnivariatePolynomial

  Exports ==> Join(ExpressionSpace, AlgebraicallyClosedField,
                   RetractableTo Z, RetractableTo Fraction Z,
                   LinearlyExplicitRingOver Z, RealConstant,
                   LinearlyExplicitRingOver Fraction Z,
                   CharacteristicZero,
                   ConvertibleTo Complex Float, DifferentialRing) with
    coerce : P -> %
      ++ coerce(p) returns p viewed as an algebraic number.
    numer  : % -> P
      ++ numer(f) returns the numerator of f viewed as a
      ++ polynomial in the kernels over Z.
    denom  : % -> P
      ++ denom(f) returns the denominator of f viewed as a
      ++ polynomial in the kernels over Z.
    reduce : % -> %
      ++ reduce(f) simplifies all the unreduced algebraic numbers
      ++ present in f by applying their defining relations.
    norm : (SUP(%),Kernel %) -> SUP(%)
      ++ norm(p,k) computes the norm of the polynomial p
      ++ with respect to the extension generated by kernel k
    norm : (SUP(%),List Kernel %) -> SUP(%)
      ++ norm(p,l) computes the norm of the polynomial p
      ++ with respect to the extension generated by kernels l
    norm : (%,Kernel %) -> %
      ++ norm(f,k) computes the norm of the algebraic number f
      ++ with respect to the extension generated by kernel k
    norm : (%,List Kernel %) -> %
      ++ norm(f,l) computes the norm of the algebraic number f
      ++ with respect to the extension generated by kernels l
  Implementation ==> InnerAlgebraicNumber add
    Rep:=InnerAlgebraicNumber
    a,b:%
    zero? a == trueEqual(a::Rep,0::Rep)
    one? a == trueEqual(a::Rep,1::Rep)
    a=b == trueEqual((a-b)::Rep,0::Rep)
```

———-

— AN.dotabb —

```
"AN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AN"]
"ACF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACF"]
"AN" -> "ACF"
```

———-

2.7 domain ANON AnonymousFunction

— **AnonymousFunction.input** —

```
)set break resume
)sys rm -f AnonymousFunction.output
)spool AnonymousFunction.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AnonymousFunction
--R AnonymousFunction  is a domain constructor
--R Abbreviation for AnonymousFunction is ANON
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ANON
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R hash : % -> SingleInteger            latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **AnonymousFunction.help** —

```
=======================================================================
AnonymousFunction examples
=======================================================================

See Also:
o )show AnonymousFunction
```

———-

2.7.1 AnonymousFunction (ANON)



Exports:
coerce hash latex ?=? ?~=?

— **domain ANON AnonymousFunction** —

```
)abbrev domain ANON AnonymousFunction
++ Author: Mark Botch
++ Description:
++ This domain implements anonymous functions

AnonymousFunction():SetCategory == add
  coerce(x:%):OutputForm == x pretend OutputForm
```

———-

— **ANON.dotabb** —

```
"ANON" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ANON"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"ANON" -> "BASTYPE"
"ANON" -> "KOERCE"
```

———-

2.8 domain ANTISYM AntiSymm

— AntiSymm.input —

```
)set break resume
)sys rm -f AntiSymm.output
)spool AntiSymm.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AntiSymm
--R
--R AntiSymm(R: Ring,lVar: List(Symbol))  is a domain constructor
--R Abbreviation for AntiSymm is ANTISYM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ANTISYM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coefficient : (%,%) -> R              coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      exp : List(Integer) -> %
--R hash : % -> SingleInteger             homogeneous? : % -> Boolean
--R latex : % -> String                   leadingBasisTerm : % -> %
--R leadingCoefficient : % -> R           map : ((R -> R),%) -> %
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R reductum : % -> %                     retract : % -> R
--R retractable? : % -> Boolean           sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R generator : NonNegativeInteger -> %
--R retractIfCan : % -> Union(R,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **AntiSymm.help** —

```
====================================================================
AntiSymm examples
====================================================================

See Also:
o )show AntiSymm
```

———-

2.8.1 AntiSymm (ANTISYM)



See

⇒ “ExtAlgBasis” (EAB) 6.8.1 on page 713
⇒ “DeRhamComplex” (DERHAM) 5.6.1 on page 517

Exports:

1	0	coefficient	coerce	coerce
coerce	degree	exp	hash	homogeneous?
latex	leadingBasisTerm	leadingCoefficient	map	one?
recip	reductum	retract	retractable?	sample
zero?	characteristic	generator	retractIfCan	subtractIfCan
?*?	?**?	?+?	?-?	-?
?=?	?^?	?~=?		

— **domain ANTISYM AntiSymm** —

```
)abbrev domain ANTISYM AntiSymm
++ Author: Larry A. Lambe
++ Date     : 01/26/91.
++ Revised  : 30 Nov 94
++ Description:
++ The domain of antisymmetric polynomials.
```

```
AntiSymm(R:Ring, lVar:List Symbol): Export == Implement where
  LALG ==> LeftAlgebra
  FMR  ==> FM(R,EAB)
  FM   ==> FreeModule
  I    ==> Integer
  L    ==> List
  EAB  ==> ExtAlgBasis     -- these are exponents of basis elements in order
  NNI  ==> NonNegativeInteger
  O    ==> OutputForm
  base ==> k
  coef ==> c
  Term ==> Record(k:EAB,c:R)

  Export == Join(LALG(R), RetractableTo(R)) with
      leadingCoefficient : %           -> R
        ++ leadingCoefficient(p) returns the leading
        ++ coefficient of antisymmetric polynomial p.
--    leadingSupport       : %           -> EAB
      leadingBasisTerm     : %           -> %
        ++ leadingBasisTerm(p) returns the leading
        ++ basis term of antisymmetric polynomial p.
      reductum             : %           -> %
        ++ reductum(p), where p is an antisymmetric polynomial,
        ++ returns p minus the leading
        ++ term of p if p has at least two terms, and 0 otherwise.
      coefficient          : (%,%)     -> R
        ++ coefficient(p,u) returns the coefficient of
        ++ the term in p containing the basis term u if such
        ++ a term exists, and 0 otherwise.
        ++ Error: if the second argument u is not a basis element.
      generator            : NNI         -> %
        ++ generator(n) returns the nth multiplicative generator,
        ++ a basis term.
      exp                  : L I         -> %
        ++  exp([i1,...in]) returns \spad{u_1\^{i_1} ... u_n\^{i_n}}
      homogeneous?         : %           -> Boolean
        ++  homogeneous?(p) tests if all of the terms of
        ++  p have the same degree.
      retractable?         : %           -> Boolean
        ++  retractable?(p) tests if p is a 0-form,
        ++  i.e., if degree(p) = 0.
      degree               : %           -> NNI
        ++  degree(p) returns the homogeneous degree of p.
      map                  : (R -> R, %) -> %
        ++  map(f,p) changes each coefficient of p by the
        ++  application of f.


--    1 corresponds to the empty monomial Nul = [0,...,0]
--    from EAB.  In terms of the exterior algebra on X,
```

```
--    it corresponds to the identity element which lives
--    in homogeneous degree 0.

  Implement == FMR add
      Rep := L Term
      x,y :  EAB
      a,b :  %
      r   :  R
      m   :  I

      dim := #lVar

      1 == [[ Nul(dim)$EAB, 1$R ]]

      coefficient(a,u) ==
        not null u.rest => error "2nd argument must be a basis element"
        x := u.first.base
        for t in a repeat
          if t.base = x then return t.coef
          if t.base < x then return 0
        0

      retractable?(a) ==
        null a or (a.first.k  =  Nul(dim))

      retractIfCan(a):Union(R,"failed") ==
        null a               => 0$R
        a.first.k = Nul(dim) => leadingCoefficient a
        "failed"

      retract(a):R ==
        null a => 0$R
        leadingCoefficient a

      homogeneous? a ==
        null a => true
        siz := _+/exponents(a.first.base)
        for ta in reductum a repeat
          _+/exponents(ta.base) ^= siz => return false
        true

      degree a ==
        null a => 0$NNI
        homogeneous? a => (_+/exponents(a.first.base)) :: NNI
        error "not a homogeneous element"

      zo : (I,I) -> L I
      zo(p,q) ==
        p = 0 => [1,q]
        q = 0 => [1,1]
```

```
    [0,0]

  getsgn : (EAB,EAB) -> I
  getsgn(x,y) ==
    sgn:I  := 0
    xx:L I := exponents x
    yy:L I := exponents y
    for i in 1 .. (dim-1) repeat
      xx  := rest xx
      sgn := sgn + (_+/xx)*yy.i
    sgn rem 2 = 0 => 1
    -1

  Nalpha: (EAB,EAB) -> L I
  Nalpha(x,y) ==
    i:I := 1
    dum2:L I := [0 for i in 1..dim]
    for j in 1..dim repeat
      dum:=zo((exponents x).j,(exponents y).j)
      (i:= i*dum.1) = 0 => leave
      dum2.j := dum.2
    i = 0 => cons(i, dum2)
    cons(getsgn(x,y), dum2)

  a * b ==
    null a => 0
    null b => 0
    ((null a.rest) and (a.first.k = Nul(dim))) => a.first.c * b
    ((null b.rest) and (b.first.k = Nul(dim))) => b.first.c * a
    z:% := 0
    for tb in b repeat
      for ta in a repeat
        stuff:=Nalpha(ta.base,tb.base)
        r:=first(stuff)*ta.coef*tb.coef
        if r ^= 0 then z := z + [[rest(stuff)::EAB, r]]
    z

  coerce(r):% ==
    r = 0 => 0
    [ [Nul(dim), r] ]

  coerce(m):% ==
    m = 0 => 0
    [ [Nul(dim), m::R] ]

  characteristic() == characteristic()$R

  generator(j) ==
    -- j < 1 or j > dim => error "your subscript is out of range"
    -- error will be generated by dum.j if out of range
```

```
        dum:L I := [0 for i in 1..dim]
        dum.j:=1
        [[dum::EAB, 1::R]]

      exp(li:(L I)) ==  [[li::EAB, 1]]

      leadingBasisTerm a ==
        [[a.first.k, 1]]

      displayList:EAB -> O
      displayList(x):O ==
        le: L I := exponents(x)$EAB
--      reduce(_*,[(lVar.i)::O for i in 1..dim | le.i = 1])$L(O)
--        reduce(_*,[(lVar.i)::O for i in 1..dim | one?(le.i)])$L(O)
        reduce(_*,[(lVar.i)::O for i in 1..dim | ((le.i) = 1)])$L(O)

      makeTerm:(R,EAB) -> O
      makeTerm(r,x) ==
      -- we know that r ^= 0
        x = Nul(dim)$EAB  => r::O
--        one? r => displayList(x)
        (r = 1) => displayList(x)
--      r = 1 => displayList(x)
--      r = 0 => 0$I::O
--      x = Nul(dim)$EAB  => r::O
        r::O * displayList(x)

      coerce(a):O ==
        zero? a     => 0$I::O
        null rest(a @ Rep) =>
                 t := first(a @ Rep)
                 makeTerm(t.coef,t.base)
        reduce(_+,[makeTerm(t.coef,t.base) for t in (a @ Rep)])$L(O)
```

———-

— ANTISYM.dotabb —

```
"ANTISYM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ANTISYM"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ANTISYM" -> "ALIST"
```

———-

2.9 domain ANY Any

— Any.input —

```
)set break resume
)sys rm -f Any.output
)spool Any.output
)set message test on
)set message auto off
)clear all

--S 1 of 18
a:Any := [1,2]
--R
--R
--R   (1)  [1,2]
--R                                                Type: List(PositiveInteger)
--E 1

--S 2 of 18
b:Any := [1,2]
--R
--R
--R   (2)  [1,2]
--R                                                Type: List(PositiveInteger)
--E 2

--S 3 of 18
(a = b)@Boolean
--R
--R
--R   (3)  true
--R                                                            Type: Boolean
--E 3

--S 4 of 18
c := [1,2]
--R
--R
--R   (4)  [1,2]
--R                                                Type: List(PositiveInteger)
--E 4

--S 5 of 18
typeOf a
--R
--R
--R   (5)  Any
```

```
--R                                                          Type: Domain
--E 5

--S 6 of 18
typeOf c
--R
--R
--R   (6)  List(PositiveInteger)
--R                                                          Type: Domain
--E 6

--S 7 of 18
(a = c)@Boolean
--R
--R
--R   (7)  true
--R                                                          Type: Boolean
--E 7

--S 8 of 18
b := [1,3]
--R
--R
--R   (8)  [1,3]
--R                                            Type: List(PositiveInteger)
--E 8

--S 9 of 18
(a = b)@Boolean
--R
--R
--R   (9)  false
--R                                                          Type: Boolean
--E 9

--S 10 of 18
a := "A"
--R
--R
--R   (10)  "A"
--R                                                           Type: String
--E 10

--S 11 of 18
(a = b)@Boolean
--R
--R
--R   (11)  false
--R                                                          Type: Boolean
--E 11
```

```
--S 12 of 18
b := "A"
--R
--R
--R   (12)  "A"
--R                                                                Type: String
--E 12

--S 13 of 18
(a = b)@Boolean
--R
--R
--R   (13)  true
--R                                                               Type: Boolean
--E 13

--S 14 of 18
Sae := SAE(FRAC INT, UP(x, FRAC INT), x^2-3)
--R
--R
--R   (14)
--R  SimpleAlgebraicExtension(Fraction(Integer),UnivariatePolynomial(x,Fraction(In
--R  teger)),x^2+-3)
--R                                                                Type: Domain
--E 14

--S 15 of 18
a := generator()$Sae
--R
--R
--R   (15)  x
--RType: SimpleAlgebraicExtension(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)),x^2+-3)
--E 15

--S 16 of 18
b := generator()$Sae
--R
--R
--R   (16)  x
--RType: SimpleAlgebraicExtension(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)),x^2+-3)
--E 16

--S 17 of 18
(a = b)@Boolean
--R
--R
--R   (17)  true
--R                                                               Type: Boolean
--E 17
```

```
--S 18 of 18
)show Any
--R
--R Any  is a domain constructor
--R Abbreviation for Any is ANY
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ANY
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                any : (SExpression,None) -> %
--R coerce : % -> OutputForm              dom : % -> SExpression
--R domainOf : % -> OutputForm            hash : % -> SingleInteger
--R latex : % -> String                   obj : % -> None
--R objectOf : % -> OutputForm            ?~=? : (%,%) -> Boolean
--R showTypeInOutput : Boolean -> String
--R
--E 18

)spool
)lisp (bye)
```

———-

— Any.help —

```
=====================================================================
Any examples
=====================================================================

Any implements a type that packages up objects and their types in
objects of Any. Roughly speaking that means that if s : S then when
converted to Any, the new object will include both the original object
and its type. This is a way of converting arbitrary objects into a
single type without losing any of the original information. Any object
can be converted to one of Any.

So we can convert a list to type Any

a:Any := [1,2]
   [1,2]

and another list to type Any

b:Any := [1,2]
   [1,2]

Equality works
```

```
(a = b)@Boolean
   true

We can compare the Any type with other types:

c := [1,2]

typeOf a

typeOf c

(a = c)@Boolean


If the values are differennt than we see the difference:

b := [1,3]
   [1,3]

(a = b)@Boolean
    false

The Any type works with many types:

a := "A"
    "A"

(a = b)@Boolean
    false

b := "A"
    "A"

(a = b)@Boolean
   true

This is true for more complex types:

Sae := SAE(FRAC INT, UP(x, FRAC INT), x^2-3)

a := generator()$Sae
   x


b := generator()$Sae
   x

(a = b)@Boolean
   true

See Also:
```

```
o )show Any
```

2.9.1 Any (ANY)



See

⇒ “None” (NONE) 15.4.1 on page 1704

Exports:

any	coerce	dom	domainOf	hash
latex	obj	objectOf	showTypeInOutput	?=?
?~=?				

— domain ANY Any —

```
)abbrev domain ANY Any
++ Author: Robert S. Sutor
++ Date Created:
++ Change History:
++ Basic Functions: any, domainOf, objectOf, dom, obj, showTypeInOutput
++ Related Constructors: AnyFunctions1
++ Also See: None
++ AMS Classification:
++ Keywords:
++ Description:
++ \spadtype{Any} implements a type that packages up objects and their
++ types in objects of \spadtype{Any}. Roughly speaking that means
++ that if \spad{s : S} then when converted to \spadtype{Any}, the new
++ object will include both the original object and its type. This is
++ a way of converting arbitrary objects into a single type without
++ losing any of the original information. Any object can be converted
++ to one of \spadtype{Any}.

Any(): SetCategory with
```

```
    any             : (SExpression, None) -> %
      ++ any(type,object) is a technical function for creating
      ++ an object of \spadtype{Any}. Arugment \spad{type} is a
      ++ \spadgloss{LISP} form for the type of \spad{object}.
    domainOf        : % -> OutputForm
      ++ domainOf(a) returns a printable form of the type of the
      ++ original object that was converted to \spadtype{Any}.
    objectOf        : % -> OutputForm
      ++ objectOf(a) returns a printable form of the
      ++ original object that was converted to \spadtype{Any}.
    dom             : % -> SExpression
      ++ dom(a) returns a \spadgloss{LISP} form of the type of the
      ++ original object that was converted to \spadtype{Any}.
    obj             : % -> None
      ++ obj(a) essentially returns the original object that was
      ++ converted to \spadtype{Any} except that the type is forced
      ++ to be \spadtype{None}.
    showTypeInOutput: Boolean -> String
      ++ showTypeInOutput(bool) affects the way objects of
      ++ \spadtype{Any} are displayed. If \spad{bool} is true
      ++ then the type of the original object that was converted
      ++ to \spadtype{Any} will be printed. If \spad{bool} is
      ++ false, it will not be printed.

== add
    Rep := Record(dm: SExpression, ob: None)

    printTypeInOutputP:Reference(Boolean) := ref false

    obj x      == x.ob
    dom x      == x.dm
    domainOf x == x.dm pretend OutputForm
    x = y      == (x.dm = y.dm) and EQ(x.ob, y.ob)$Lisp
    x = y      ==
     (x.dm = y.dm) and EQUAL(x.ob, y.ob)$Lisp

    objectOf(x : %) : OutputForm ==
      spad2BootCoerce(x.ob, x.dm,
         list("OutputForm"::Symbol)$List(Symbol))$Lisp

    showTypeInOutput(b : Boolean) : String ==
     printTypeInOutputP := ref b
     b=> "Type of object will be displayed in output of a member of Any"
     "Type of object will not be displayed in output of a member of Any"

    coerce(x):OutputForm ==
      obj1 : OutputForm := objectOf x
      not deref printTypeInOutputP => obj1
      dom1 :=
        p:Symbol := prefix2String(devaluate(x.dm)$Lisp)$Lisp
```

```
        atom?(p pretend SExpression) => list(p)$List(Symbol)
        list(p)$Symbol
      hconcat cons(obj1,
        cons(":"::OutputForm, [a::OutputForm for a in dom1]))

    any(domain, object) ==
      (isValidType(domain)$Lisp)@Boolean => [domain, object]
      domain := devaluate(domain)$Lisp
      (isValidType(domain)$Lisp)@Boolean => [domain, object]
      error "function any must have a domain as first argument"
```

———-

— ANY.dotabb —

```
"ANY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ANY"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ANY" -> "ALIST"
```

———-

2.10 domain ASTACK ArrayStack

— ArrayStack.input —

```
)set break resume
)sys rm -f ArrayStack.output
)spool ArrayStack.output
)set message test on
)set message auto off
)clear all

--S 1 of 44
a:ArrayStack INT:= arrayStack [1,2,3,4,5]
--R
--R
--R   (1)  [1,2,3,4,5]
--R                                                Type: ArrayStack(Integer)
--E 1

--S 2 of 44
pop! a
--R
--R
```

```
--R   (2)  1
--R                                                    Type: PositiveInteger
--E 2

--S 3 of 44
a
--R
--R
--R   (3)  [2,3,4,5]
--R                                                 Type: ArrayStack(Integer)
--E 3

--S 4 of 44
extract! a
--R
--R
--R   (4)  2
--R                                                    Type: PositiveInteger
--E 4

--S 5 of 44
a
--R
--R
--R   (5)  [3,4,5]
--R                                                 Type: ArrayStack(Integer)
--E 5

--S 6 of 44
push!(9,a)
--R
--R
--R   (6)  9
--R                                                    Type: PositiveInteger
--E 6

--S 7 of 44
a
--R
--R
--R   (7)  [9,3,4,5]
--R                                                 Type: ArrayStack(Integer)
--E 7

--S 8 of 44
insert!(8,a)
--R
--R
--R   (8)  [8,9,3,4,5]
--R                                                 Type: ArrayStack(Integer)
```

```
--E 8

--S 9 of 44
a
--R
--R
--R   (9)  [8,9,3,4,5]
--R                                          Type: ArrayStack(Integer)
--E 9

--S 10 of 44
inspect a
--R
--R
--R   (10)  8
--R                                             Type: PositiveInteger
--E 10

--S 11 of 44
empty? a
--R
--R
--R   (11)  false
--R                                                     Type: Boolean
--E 11

--S 12 of 44
top a
--R
--R
--R   (12)  8
--R                                             Type: PositiveInteger
--E 12

--S 13 of 44
depth a
--R
--R
--R   (13)  5
--R                                             Type: PositiveInteger
--E 13

--S 14 of 44
#a
--R
--R
--R   (14)  5
--R                                             Type: PositiveInteger
--E 14
```

```
--S 15 of 44
less?(a,9)
--R
--R
--R   (15)  true
--R                                                        Type: Boolean
--E 15

--S 16 of 44
more?(a,9)
--R
--R
--R   (16)  false
--R                                                        Type: Boolean
--E 16

--S 17 of 44
size?(a,#a)
--R
--R
--R   (17)  true
--R                                                        Type: Boolean
--E 17

--S 18 of 44
size?(a,9)
--R
--R
--R   (18)  false
--R                                                        Type: Boolean
--E 18

--S 19 of 44
parts a
--R
--R
--R   (19)  [8,9,3,4,5]
--R                                              Type: List(Integer)
--E 19

--S 20 of 44
bag([1,2,3,4,5])$ArrayStack(INT)
--R
--R
--R   (20)  [5,4,3,2,1]
--R                                         Type: ArrayStack(Integer)
--E 20

--S 21 of 44
b:=empty()$(ArrayStack INT)
```

```
--R
--R
--R   (21)  []
--R                                                Type: ArrayStack(Integer)
--E 21

--S 22 of 44
empty? b
--R
--R
--R   (22)  true
--R                                                           Type: Boolean
--E 22

--S 23 of 44
sample()$ArrayStack(INT)
--R
--R
--R   (23)  []
--R                                                Type: ArrayStack(Integer)
--E 23

--S 24 of 44
c:=copy a
--R
--R
--R   (24)  [8,9,3,4,5]
--R                                                Type: ArrayStack(Integer)
--E 24

--S 25 of 44
eq?(a,c)
--R
--R
--R   (25)  false
--R                                                           Type: Boolean
--E 25

--S 26 of 44
eq?(a,a)
--R
--R
--R   (26)  true
--R                                                           Type: Boolean
--E 26

--S 27 of 44
(a=c)@Boolean
--R
--R
```

```
--R   (27)  true
--R                                                    Type: Boolean
--E 27

--S 28 of 44
(a=a)@Boolean
--R
--R
--R   (28)  true
--R                                                    Type: Boolean
--E 28

--S 29 of 44
a~=c
--R
--R
--R   (29)  false
--R                                                    Type: Boolean
--E 29

--S 30 of 44
any?(x+->(x=4),a)
--R
--R
--R   (30)  true
--R                                                    Type: Boolean
--E 30

--S 31 of 44
any?(x+->(x=11),a)
--R
--R
--R   (31)  false
--R                                                    Type: Boolean
--E 31

--S 32 of 44
every?(x+->(x=11),a)
--R
--R
--R   (32)  false
--R                                                    Type: Boolean
--E 32

--S 33 of 44
count(4,a)
--R
--R
--R   (33)  1
--R                                            Type: PositiveInteger
```

```
--E 33

--S 34 of 44
count(x+->(x>2),a)
--R
--R
--R   (34)  5
--R                                                    Type: PositiveInteger
--E 34

--S 35 of 44
map(x+->x+10,a)
--R
--R
--R   (35)  [18,19,13,14,15]
--R                                                 Type: ArrayStack(Integer)
--E 35

--S 36 of 44
a
--R
--R
--R   (36)  [8,9,3,4,5]
--R                                                 Type: ArrayStack(Integer)
--E 36

--S 37 of 44
map!(x+->x+10,a)
--R
--R
--R   (37)  [18,19,13,14,15]
--R                                                 Type: ArrayStack(Integer)
--E 37

--S 38 of 44
a
--R
--R
--R   (38)  [18,19,13,14,15]
--R                                                 Type: ArrayStack(Integer)
--E 38

--S 39 of 44
members a
--R
--R
--R   (39)  [18,19,13,14,15]
--R                                                       Type: List(Integer)
--E 39
```

```
--S 40 of 44
member?(14,a)
--R
--R
--R   (40)  true
--R                                                              Type: Boolean
--E 40

--S 41 of 44
coerce a
--R
--R
--R   (41)  [18,19,13,14,15]
--R                                                           Type: OutputForm
--E 41

--S 42 of 44
hash a
--R
--R
--I   (42)  36310821
--R                                                         Type: SingleInteger
--E 42

--S 43 of 44
latex a
--R
--R
--R   (43)  "\mbox{\bf Unimplemented}"
--R                                                              Type: String
--E 43

--S 44 of 44
)show ArrayStack
--R
--R ArrayStack(S: SetCategory)  is a domain constructor
--R Abbreviation for ArrayStack is ASTACK
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASTACK
--R
--R------------------------------ Operations --------------------------------
--R arrayStack : List(S) -> %            bag : List(S) -> %
--R copy : % -> %                        depth : % -> NonNegativeInteger
--R empty : () -> %                      empty? : % -> Boolean
--R eq? : (%,%) -> Boolean               extract! : % -> S
--R insert! : (S,%) -> %                 inspect : % -> S
--R map : ((S -> S),%) -> %              pop! : % -> S
--R push! : (S,%) -> S                  sample : () -> %
--R top : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
```

```
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 44

)spool
)lisp (bye)
```

———-

— ArrayStack.help —

```
=====================================================================
ArrayStack examples
=====================================================================

An ArrayStack object is represented as a list ordered by last-in, first-out.
It operates like a pile of books, where the "next" book is the one
on the top of the pile.

Here we create an array stack of integers from a list. Notice that the
order in the list is the order in the stack.

   a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      [1,2,3,4,5]

We can remove the top of the stack using pop!:

   pop! a
      1
```

```
Notice that the use of pop! is destructive (destructive operations
in Axiom usually end with ! to indicate that the underylying data
structure is changed).

   a
      [2,3,4,5]

The extract! operation is another name for the pop! operation and
has the same effect. This operation treats the stack as a BagAggregate:

   extract! a
      2

and you can see that it also has destructively modified the stack:

   a
      [3,4,5]

Next we push a new element on top of the stack:

   push!(9,a)
      9

Again, the push! operation is destructive so the stack is changed:

   a
      [9,3,4,5]

Another name for push! is insert!, which treats the stack as a BagAggregate:

   insert!(8,a)
      [8,9,3,4,5]

and it modifies the stack:

   a
      [8,9,3,4,5]

The inspect function returns the top of the stack without modification,
viewed as a BagAggregate:

   inspect a
      8

The empty? operation returns true only if there are no element on the
stack, otherwise it returns false:

   empty? a
      false
```

```
The top operation returns the top of stack without modification, viewed
as a Stack:

   top a
      8

The depth operation returns the number of elements on the stack:

   depth a
      5

which is the same as the # (length) operation:

   #a
       5

The less? predicate will compare the stack length to an integer:

   less?(a,9)
        true

The more? predicate will compare the stack length to an integer:

   more?(a,9)
        false

The size? operation will compare the stack length to an integer:

   size?(a,#a)
        true

and since the last computation must alwasy be true we try:

   size?(a,9)
        false

The parts function will return  the stack as a list of its elements:

   parts a
        [8,9,3,4,5]

If we have a BagAggregate of elements we can use it to construct a stack.
Notice that the elements are pushed in reverse order:

   bag([1,2,3,4,5])$ArrayStack(INT)
        [5,4,3,2,1]

The empty function will construct an empty stack of a given type:
```

```
   b:=empty()$(ArrayStack INT)
        []
```

and the empty? predicate allows us to find out if a stack is empty:

```
   empty? b
        true
```

The sample function returns a sample, empty stack:

```
   sample()$ArrayStack(INT)
        []
```

We can copy a stack and it does not share storage so subsequent
modifications of the original stack will not affect the copy:

```
   c:=copy a
        [8,9,3,4,5]
```

The eq? function is only true if the lists are the same reference,
so even though c is a copy of a, they are not the same:

```
   eq?(a,c)
        false
```

However, a clearly shares a reference with itself:

```
   eq?(a,a)
        true
```

But we can compare a and c for equality:

```
   (a=c)@Boolean
        true
```

and clearly a is equal to itself:

```
   (a=a)@Boolean
        true
```

and since a and c are equal, they are clearly NOT not-equal:

```
   a~=c
        false
```

We can use the any? function to see if a predicate is true for any element:

```
   any?(x+->(x=4),a)
        true
```

```
or false for every element:

   any?(x+->(x=11),a)
        false

We can use the every? function to check every element satisfies a predicate:

   every?(x+->(x=11),a)
        false

We can count the elements that are equal to an argument of this type:

   count(4,a)
        1

or we can count against a boolean function:

   count(x+->(x>2),a)
        5

You can also map a function over every element, returning a new stack:

   map(x+->x+10,a)
        [18,19,13,14,15]

Notice that the orignal stack is unchanged:

   a
        [8,9,3,4,5]

You can use map! to map a function over every element and change
the original stack since map! is destructive:

   map!(x+->x+10,a)
       [18,19,13,14,15]

Notice that the orignal stack has been changed:

   a
       [18,19,13,14,15]

The member function can also get the element of the stack as a list:

   members a
       [18,19,13,14,15]


and using member? we can test if the stack holds a given element:

   member?(14,a)
       true
```

```
See Also:
o )show Stack
o )show ArrayStack
o )show Queue
o )show Dequeue
o )show Heap
o )show BagAggregate
```

———-

2.10.1 ArrayStack (ASTACK)



See

⇒ “Stack” (STACK) 20.28.1 on page 2530
⇒ “Queue” (QUEUE) 18.5.1 on page 2150
⇒ “Dequeue” (DEQUEUE) 5.5.1 on page 499
⇒ “Heap” (HEAP) 9.2.1 on page 1104

Exports:

any?	arrayStack	bag	coerce	copy
count	depth	empty	empty?	eq?
eval	every?	extract!	hash	insert!
inspect	latex	less?	map	map!
member?	members	more?	parts	pop!
push!	sample	size?	top	#?
?~=?	?=?			

— domain ASTACK ArrayStack —

```
)abbrev domain ASTACK ArrayStack
++ Author: Michael Monagan, Stephen Watt, Timothy Daly
++ Date Created:June 86 and July 87
++ Date Last Updated:Feb 92
```

```
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A stack represented as a flexible array.
--% Dequeue and Heap data types

ArrayStack(S:SetCategory): StackAggregate(S) with
    arrayStack: List S -> %
      ++ arrayStack([x,y,...,z]) creates an array stack with first (top)
      ++ element x, second element y,...,and last element z.
      ++
      ++E c:ArrayStack INT:= arrayStack [1,2,3,4,5]

 -- Inherited Signatures repeated for examples documentation

    pop_! : % -> S
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X pop! a
      ++X a
    extract_! : % -> S
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X extract! a
      ++X a
    push_! : (S,%) -> S
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X push!(9,a)
      ++X a
    insert_! : (S,%) -> %
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X insert!(8,a)
      ++X a
    inspect : % -> S
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X inspect a
    top : % -> S
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X top a
    depth : % -> NonNegativeInteger
      ++
```

```
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X depth a
  less? : (%,NonNegativeInteger) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X less?(a,9)
  more? : (%,NonNegativeInteger) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X more?(a,9)
  size? : (%,NonNegativeInteger) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X size?(a,5)
  bag : List S -> %
    ++
    ++X bag([1,2,3,4,5])$ArrayStack(INT)
  empty? : % -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X empty? a
  empty : () -> %
    ++
    ++X b:=empty()$(ArrayStack INT)
  sample : () -> %
    ++
    ++X sample()$ArrayStack(INT)
  copy : % -> %
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X copy a
  eq? : (%,%) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X b:=copy a
    ++X eq?(a,b)
  map :  ((S -> S),%) -> %
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X map(x+->x+10,a)
    ++X a
  if $ has shallowlyMutable then
    map! :  ((S -> S),%) -> %
      ++
      ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
      ++X map!(x+->x+10,a)
      ++X a
  if S has SetCategory then
    latex : % -> String
      ++
```

```
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X latex a
  hash : % -> SingleInteger
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X hash a
  coerce : % -> OutputForm
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X coerce a
  "=": (%,%) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X b:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X (a=b)@Boolean
  "~=" : (%,%) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X b:=copy a
    ++X (a~=b)
if % has finiteAggregate then
  every? : ((S -> Boolean),%) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X every?(x+->(x=4),a)
  any? : ((S -> Boolean),%) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X any?(x+->(x=4),a)
  count :  ((S -> Boolean),%) -> NonNegativeInteger
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X count(x+->(x>2),a)
  _# : % -> NonNegativeInteger
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X #a
  parts : % -> List S
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X parts a
  members : % -> List S
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X members a
if % has finiteAggregate and S has SetCategory then
  member? : (S,%) -> Boolean
    ++
    ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
    ++X member?(3,a)
```

```
      count : (S,%) -> NonNegativeInteger
        ++
        ++X a:ArrayStack INT:= arrayStack [1,2,3,4,5]
        ++X count(4,a)

  == add
    Rep := IndexedFlexibleArray(S,0)

    -- system operations
    # s == _#(s)$Rep
    s = t == s =$Rep t
    copy s == copy(s)$Rep
    coerce(d):OutputForm ==
        empty? d => empty()$(List S) ::OutputForm
        [(d.i::OutputForm) for i in 0..#d-1] ::OutputForm

    -- stack operations
    depth s == # s
    empty? s == empty?(s)$Rep
    extract_! s == pop_! s
    insert_!(e,s) == (push_!(e,s);s)
    push_!(e,s) == (concat(e,s); e)
    pop_! s ==
        if empty? s then error "empty stack"
        r := s.0
        delete_!(s,0)
        r
    top s == if empty? s then error "empty stack" else s.0
    arrayStack l == construct(l)$Rep
    empty() == new(0,0 pretend S)
    parts s == [s.i for i in 0..#s-1]::List(S)
    map(f,s) == construct [f(s.i) for i in 0..#s-1]
    map!(f,s) == ( for i in 0..#s-1 repeat qsetelt!(s,i,f(s.i)) ; s )
    inspect(s) ==
        if empty? s then error "empty stack"
        qelt(s,0)
```

———-

— ASTACK.dotabb —

```
"ASTACK" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASTACK"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"ASTACK" -> "A1AGG"
```

———-

2.11 domain ASP1 Asp1

— Asp1.input —

```
)set break resume
)sys rm -f Asp1.output
)spool Asp1.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp1
--R
--R Asp1(name: Symbol)  is a domain constructor
--R Abbreviation for Asp1 is ASP1
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP1
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R retract : Polynomial(Float) -> %      retract : Expression(Float) -> %
--R coerce : FortranExpression([construct,QUOTEX],[construct],MachineFloat) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Fraction(Polynomial(Integer)) -> %
--R retract : Fraction(Polynomial(Float)) -> %
--R retract : Polynomial(Integer) -> %
--R retract : Expression(Integer) -> %
--R retractIfCan : Fraction(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Fraction(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed")
--R retractIfCan : Polynomial(Float) -> Union(%,"failed")
--R retractIfCan : Expression(Integer) -> Union(%,"failed")
--R retractIfCan : Expression(Float) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```


———-

— Asp1.help —

```
=====================================================================
Asp1 examples
=====================================================================
```

```
See Also:
o )show Asp1
```

2.11.1 Asp1 (ASP1)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP1 Asp1 —

```
)abbrev domain ASP1 Asp1
++ Author: Mike Dewar, Grant Keady, Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994, 6 October 1994
++ Related Constructors: FortranFunctionCategory, FortranProgramCategory.
++ Description:
++ \spadtype{Asp1} produces Fortran for Type 1 ASPs, needed for various
++ NAG routines. Type 1 ASPs take a univariate expression (in the symbol x)
++ and turn it into a Fortran Function like the following:
++
++ \tab{5}DOUBLE PRECISION FUNCTION F(X)\br
++ \tab{5}DOUBLE PRECISION X\br
++ \tab{5}F=DSIN(X)\br
++ \tab{5}RETURN\br
++ \tab{5}END

Asp1(name): Exports == Implementation where
  name : Symbol

  FEXPR  ==> FortranExpression
  FST    ==> FortranScalarType
```

```
FT     ==> FortranType
SYMTAB ==> SymbolTable
RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float

Exports ==> FortranFunctionCategory with
  coerce : FEXPR(['X],[],MachineFloat) -> $
    ++coerce(f) takes an object from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns it into an ASP.

Implementation ==> add

  -- Build Symbol Table for Rep
  syms : SYMTAB := empty()$SYMTAB
  declare!(X,fortranReal()$FT,syms)$SYMTAB
  real : FST := "real"::FST

  Rep := FortranProgram(name,[real]$Union(fst:FST,void:"void"),[X],syms)

  retract(u:FRAC POLY INT):$ == (retract(u)@FEXPR(['X],[],MachineFloat))::$
  retractIfCan(u:FRAC POLY INT):Union($,"failed") ==
    foo : Union(FEXPR(['X],[],MachineFloat),"failed")
    foo := retractIfCan(u)$FEXPR(['X],[],MachineFloat)
    foo case "failed" => "failed"
    foo::FEXPR(['X],[],MachineFloat)::$

  retract(u:FRAC POLY FLOAT):$ == (retract(u)@FEXPR(['X],[],MachineFloat))::$
  retractIfCan(u:FRAC POLY FLOAT):Union($,"failed") ==
    foo : Union(FEXPR(['X],[],MachineFloat),"failed")
    foo := retractIfCan(u)$FEXPR(['X],[],MachineFloat)
    foo case "failed" => "failed"
    foo::FEXPR(['X],[],MachineFloat)::$

  retract(u:EXPR FLOAT):$ == (retract(u)@FEXPR(['X],[],MachineFloat))::$
  retractIfCan(u:EXPR FLOAT):Union($,"failed") ==
    foo : Union(FEXPR(['X],[],MachineFloat),"failed")
    foo := retractIfCan(u)$FEXPR(['X],[],MachineFloat)
    foo case "failed" => "failed"
    foo::FEXPR(['X],[],MachineFloat)::$

  retract(u:EXPR INT):$ == (retract(u)@FEXPR(['X],[],MachineFloat))::$
  retractIfCan(u:EXPR INT):Union($,"failed") ==
    foo : Union(FEXPR(['X],[],MachineFloat),"failed")
    foo := retractIfCan(u)$FEXPR(['X],[],MachineFloat)
    foo case "failed" => "failed"
    foo::FEXPR(['X],[],MachineFloat)::$
```

```
    retract(u:POLY FLOAT):$ == (retract(u)@FEXPR(['X],[],MachineFloat))::$
    retractIfCan(u:POLY FLOAT):Union($,"failed") ==
      foo : Union(FEXPR(['X],[],MachineFloat),"failed")
      foo := retractIfCan(u)$FEXPR(['X],[],MachineFloat)
      foo case "failed" => "failed"
      foo::FEXPR(['X],[],MachineFloat)::$

    retract(u:POLY INT):$ == (retract(u)@FEXPR(['X],[],MachineFloat))::$
    retractIfCan(u:POLY INT):Union($,"failed") ==
      foo : Union(FEXPR(['X],[],MachineFloat),"failed")
      foo := retractIfCan(u)$FEXPR(['X],[],MachineFloat)
      foo case "failed" => "failed"
      foo::FEXPR(['X],[],MachineFloat)::$

    coerce(u:FEXPR(['X],[],MachineFloat)):$ ==
      coerce((u::Expression(MachineFloat))$FEXPR(['X],[],MachineFloat))$Rep

    coerce(c:List FortranCode):$ == coerce(c)$Rep

    coerce(r:RSFC):$ == coerce(r)$Rep

    coerce(c:FortranCode):$ == coerce(c)$Rep

    coerce(u:$):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP1.dotabb —

```
"ASP1" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP1"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP1" -> "PFECAT"
```

———-

2.12 domain ASP10 Asp10

— Asp10.input —

```
)set break resume
)sys rm -f Asp10.output
)spool Asp10.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp10
--R
--R Asp10(name: Symbol)  is a domain constructor
--R Abbreviation for Asp10 is ASP10
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP10
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEJINT,QUOTEX,QUOTEELAM],[construct],Machine
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp10.help —

```
=====================================================================
Asp10 examples
=====================================================================

See Also:
o )show Asp10
```

———-

2.12.1 Asp10 (ASP10)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP10 Asp10 —

```
)abbrev domain ASP10 Asp10
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{ASP10} produces Fortran for Type 10 ASPs, needed for NAG routine
++ d02kef. This ASP computes the values of a set of functions, for example:
++
++ \tab{5}SUBROUTINE COEFFN(P,Q,DQDL,X,ELAM,JINT)\br
++ \tab{5}DOUBLE PRECISION ELAM,P,Q,X,DQDL\br
++ \tab{5}INTEGER JINT\br
++ \tab{5}P=1.0D0\br
++ \tab{5}Q=((-1.0D0*X**3)+ELAM*X*X-2.0D0)/(X*X)\br
++ \tab{5}DQDL=1.0D0\br
++ \tab{5}RETURN\br
++ \tab{5}END

Asp10(name): Exports == Implementation where
  name : Symbol

  FST  ==> FortranScalarType
  FT   ==> FortranType
  SYMTAB ==> SymbolTable
  EXF ==> Expression Float
```

```
RSFC ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
FEXPR ==> FortranExpression(['JINT,'X,'ELAM],[],MFLOAT)
MFLOAT ==> MachineFloat
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float
VEC    ==> Vector
VF2    ==> VectorFunctions2

Exports ==> FortranVectorFunctionCategory with
  coerce : Vector FEXPR -> %
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add

  real : FST := "real"::FST
  syms : SYMTAB := empty()$SYMTAB
  declare!(P,fortranReal()$FT,syms)$SYMTAB
  declare!(Q,fortranReal()$FT,syms)$SYMTAB
  declare!(DQDL,fortranReal()$FT,syms)$SYMTAB
  declare!(X,fortranReal()$FT,syms)$SYMTAB
  declare!(ELAM,fortranReal()$FT,syms)$SYMTAB
  declare!(JINT,fortranInteger()$FT,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$Union(fst:FST,void:"void"),
                        [P,Q,DQDL,X,ELAM,JINT],syms)

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
    v::$
```

```
retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

coerce(c:FortranCode):% == coerce(c)$Rep

coerce(r:RSFC):% == coerce(r)$Rep

coerce(c:List FortranCode):% == coerce(c)$Rep

-- To help the poor old compiler!
localAssign(s:Symbol,u:Expression MFLOAT):FortranCode ==
  assign(s,u)$FortranCode

coerce(u:Vector FEXPR):% ==
  import Vector FEXPR
  not (#u = 3) => error "Incorrect Dimension For Vector"
  ([localAssign(P,elt(u,1)::Expression MFLOAT),_
    localAssign(Q,elt(u,2)::Expression MFLOAT),_
    localAssign(DQDL,elt(u,3)::Expression MFLOAT),_
    returns()$FortranCode ]$List(FortranCode))::Rep
```

```
    coerce(u:%):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP10.dotabb** —

```
"ASP10" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP10"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP10" -> "PFECAT"
```

———-

2.13 domain ASP12 Asp12

— **Asp12.input** —

```
)set break resume
)sys rm -f Asp12.output
)spool Asp12.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp12
--R
--R Asp12(name: Symbol)  is a domain constructor
--R Abbreviation for Asp12 is ASP12
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP12
--R
--R------------------------------ Operations ------------------------------
--R coerce : % -> OutputForm              outputAsFortran : () -> Void
--R outputAsFortran : % -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp12.help** —

```
====================================================================
Asp12 examples
====================================================================

See Also:
o )show Asp12
```

———-

2.13.1 Asp12 (ASP12)



Exports:
coerce outputAsFortran

— **domain ASP12 Asp12** —

```
)abbrev domain ASP12 Asp12
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Oct 1993
++ Date Last Updated: 18 March 1994
++                    21 June 1994 Changed print to printStatement
++ Related Constructors:
++ Description:
++ \spadtype{Asp12} produces Fortran for Type 12 ASPs, needed for NAG routine
++ d02kef etc., for example:
++
++ \tab{5}SUBROUTINE MONIT (MAXIT,IFLAG,ELAM,FINFO)\br
++ \tab{5}DOUBLE PRECISION ELAM,FINFO(15)\br
++ \tab{5}INTEGER MAXIT,IFLAG\br
++ \tab{5}IF(MAXIT.EQ.-1)THEN\br
```

```
++ \tab{7}PRINT*,"Output from Monit"\br
++ \tab{5}ENDIF\br
++ \tab{5}PRINT*,MAXIT,IFLAG,ELAM,(FINFO(I),I=1,4)\br
++ \tab{5}RETURN\br
++ \tab{5}END\

Asp12(name): Exports == Implementation where
  name : Symbol

  O      ==> OutputForm
  S      ==> Symbol
  FST    ==> FortranScalarType
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  EXI    ==> Expression Integer
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  U      ==> Union(I: Expression Integer,F: Expression Float,_
                   CF: Expression Complex Float,switch:Switch)
  UFST   ==> Union(fst:FST,void:"void")

  Exports ==> FortranProgramCategory with
     outputAsFortran:() -> Void
      ++outputAsFortran() generates the default code for \spadtype{ASP12}.

  Implementation ==> add

    import FC
    import Switch

    real : FST := "real"::FST
    syms : SYMTAB := empty()$SYMTAB
    declare!(MAXIT,fortranInteger()$FT,syms)$SYMTAB
    declare!(IFLAG,fortranInteger()$FT,syms)$SYMTAB
    declare!(ELAM,fortranReal()$FT,syms)$SYMTAB
    fType : FT := construct([real]$UFST,["15"::Symbol],false)$FT
    declare!(FINFO,fType,syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$UFST,[MAXIT,IFLAG,ELAM,FINFO],syms)

    -- eqn : O := (I::O)=(1@Integer::EXI::O)
    code:=([cond(EQ([MAXIT@S::EXI]$U,[-1::EXI]$U),
                 printStatement(["_"Output from Monit_""::O])),
            printStatement([MAXIT::O,IFLAG::O,ELAM::O,subscript("(FINFO"::S,[I::O])::O,"I=1"::S:
            returns()]$List(FortranCode))::Rep

    coerce(u:%):OutputForm == coerce(u)$Rep

    outputAsFortran(u:%):Void == outputAsFortran(u)$Rep
    outputAsFortran():Void == outputAsFortran(code)$Rep
```

———-

— **ASP12.dotabb** —

```
"ASP12" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP12"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP12" -> "ALIST"
```

———-

2.14 domain ASP19 Asp19

— **Asp19.input** —

```
)set break resume
)sys rm -f Asp19.output
)spool Asp19.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp19
--R
--R Asp19(name: Symbol)  is a domain constructor
--R Abbreviation for Asp19 is ASP19
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP19
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct],[construct,QUOTEXC],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
```

```
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp19.help —

```
=======================================================================
Asp19 examples
=======================================================================

See Also:
o )show Asp19
```

———-

2.14.1 Asp19 (ASP19)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP19 Asp19 —

```
)abbrev domain ASP19 Asp19
++ Author: Mike Dewar, Godfrey Nolan, Grant Keady
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
```

```
++ Description:
++\spadtype{Asp19} produces Fortran for Type 19 ASPs, evaluating a set of
++functions and their jacobian at a given point, for example:
++
++\tab{5}SUBROUTINE LSFUN2(M,N,XC,FVECC,FJACC,LJC)\br
++\tab{5}DOUBLE PRECISION FVECC(M),FJACC(LJC,N),XC(N)\br
++\tab{5}INTEGER M,N,LJC\br
++\tab{5}INTEGER I,J\br
++\tab{5}DO 25003 I=1,LJC\br
++\tab{7}DO 25004 J=1,N\br
++\tab{9}FJACC(I,J)=0.0D0\br
++25004   CONTINUE\br
++25003 CONTINUE\br
++\tab{5}FVECC(1)=((XC(1)-0.14D0)*XC(3)+(15.0D0*XC(1)-2.1D0)*XC(2)+1.0D0)/(\br
++\tab{4}&XC(3)+15.0D0*XC(2))\br
++\tab{5}FVECC(2)=((XC(1)-0.18D0)*XC(3)+(7.0D0*XC(1)-1.26D0)*XC(2)+1.0D0)/(\br
++\tab{4}&XC(3)+7.0D0*XC(2))\br
++\tab{5}FVECC(3)=((XC(1)-0.22D0)*XC(3)+(4.333333333333333D0*XC(1)-0.953333\br
++\tab{4}&3333333333D0)*XC(2)+1.0D0)/(XC(3)+4.333333333333333D0*XC(2))\br
++\tab{5}FVECC(4)=((XC(1)-0.25D0)*XC(3)+(3.0D0*XC(1)-0.75D0)*XC(2)+1.0D0)/(\br
++\tab{4}&XC(3)+3.0D0*XC(2))\br
++\tab{5}FVECC(5)=((XC(1)-0.29D0)*XC(3)+(2.2D0*XC(1)-0.6379999999999999D0)*\br
++\tab{4}&XC(2)+1.0D0)/(XC(3)+2.2D0*XC(2))\br
++\tab{5}FVECC(6)=((XC(1)-0.32D0)*XC(3)+(1.666666666666667D0*XC(1)-0.533333\br
++\tab{4}&3333333333D0)*XC(2)+1.0D0)/(XC(3)+1.666666666666667D0*XC(2))\br
++\tab{5}FVECC(7)=((XC(1)-0.35D0)*XC(3)+(1.285714285714286D0*XC(1)-0.45D0)*\br
++\tab{4}&XC(2)+1.0D0)/(XC(3)+1.285714285714286D0*XC(2))\br
++\tab{5}FVECC(8)=((XC(1)-0.39D0)*XC(3)+(XC(1)-0.39D0)*XC(2)+1.0D0)/(XC(3)+\br
++\tab{4}&XC(2))\br
++\tab{5}FVECC(9)=((XC(1)-0.37D0)*XC(3)+(XC(1)-0.37D0)*XC(2)+1.285714285714\br
++\tab{4}&286D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(10)=((XC(1)-0.58D0)*XC(3)+(XC(1)-0.58D0)*XC(2)+1.66666666666\br
++\tab{4}&6667D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(11)=((XC(1)-0.73D0)*XC(3)+(XC(1)-0.73D0)*XC(2)+2.2D0)/(XC(3)\br
++\tab{4}&+XC(2))\br
++\tab{5}FVECC(12)=((XC(1)-0.96D0)*XC(3)+(XC(1)-0.96D0)*XC(2)+3.0D0)/(XC(3)\br
++\tab{4}&+XC(2))\br
++\tab{5}FVECC(13)=((XC(1)-1.34D0)*XC(3)+(XC(1)-1.34D0)*XC(2)+4.33333333333\br
++\tab{4}&3333D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(14)=((XC(1)-2.1D0)*XC(3)+(XC(1)-2.1D0)*XC(2)+7.0D0)/(XC(3)+X\br
++\tab{4}&C(2))\br
++\tab{5}FVECC(15)=((XC(1)-4.39D0)*XC(3)+(XC(1)-4.39D0)*XC(2)+15.0D0)/(XC(3\br
++\tab{4}&)+XC(2))\br
++\tab{5}FJACC(1,1)=1.0D0\br
++\tab{5}FJACC(1,2)=-15.0D0/(XC(3)**2+30.0D0*XC(2)*XC(3)+225.0D0*XC(2)**2)\br
++\tab{5}FJACC(1,3)=-1.0D0/(XC(3)**2+30.0D0*XC(2)*XC(3)+225.0D0*XC(2)**2)\br
++\tab{5}FJACC(2,1)=1.0D0\br
++\tab{5}FJACC(2,2)=-7.0D0/(XC(3)**2+14.0D0*XC(2)*XC(3)+49.0D0*XC(2)**2)\br
++\tab{5}FJACC(2,3)=-1.0D0/(XC(3)**2+14.0D0*XC(2)*XC(3)+49.0D0*XC(2)**2)\br
++\tab{5}FJACC(3,1)=1.0D0\br
```

```
++\tab{5}FJACC(3,2)=((-0.1110223024625157D-15*XC(3))-4.333333333333333D0)/(\br
++\tab{4}&XC(3)**2+8.666666666666666D0*XC(2)*XC(3)+18.77777777777778D0*XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(3,3)=(0.1110223024625157D-15*XC(2)-1.0D0)/(XC(3)**2+8.666666\br
++\tab{4}&666666666D0*XC(2)*XC(3)+18.77777777777778D0*XC(2)**2)\br
++\tab{5}FJACC(4,1)=1.0D0\br
++\tab{5}FJACC(4,2)=-3.0D0/(XC(3)**2+6.0D0*XC(2)*XC(3)+9.0D0*XC(2)**2)\br
++\tab{5}FJACC(4,3)=-1.0D0/(XC(3)**2+6.0D0*XC(2)*XC(3)+9.0D0*XC(2)**2)\br
++\tab{5}FJACC(5,1)=1.0D0\br
++\tab{5}FJACC(5,2)=((-0.1110223024625157D-15*XC(3))-2.2D0)/(XC(3)**2+4.399\br
++\tab{4}&999999999999D0*XC(2)*XC(3)+4.839999999999998D0*XC(2)**2)\br
++\tab{5}FJACC(5,3)=(0.1110223024625157D-15*XC(2)-1.0D0)/(XC(3)**2+4.399999\br
++\tab{4}&999999999D0*XC(2)*XC(3)+4.839999999999998D0*XC(2)**2)\br
++\tab{5}FJACC(6,1)=1.0D0\br
++\tab{5}FJACC(6,2)=((-0.2220446049250313D-15*XC(3))-1.666666666666667D0)/(\br
++\tab{4}&XC(3)**2+3.333333333333333D0*XC(2)*XC(3)+2.777777777777777D0*XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(6,3)=(0.2220446049250313D-15*XC(2)-1.0D0)/(XC(3)**2+3.333333\br
++\tab{4}&333333333D0*XC(2)*XC(3)+2.777777777777777D0*XC(2)**2)\br
++\tab{5}FJACC(7,1)=1.0D0\br
++\tab{5}FJACC(7,2)=((-0.5551115123125783D-16*XC(3))-1.285714285714286D0)/(\br
++\tab{4}&XC(3)**2+2.571428571428571D0*XC(2)*XC(3)+1.653061224489796D0*XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(7,3)=(0.5551115123125783D-16*XC(2)-1.0D0)/(XC(3)**2+2.571428\br
++\tab{4}&571428571D0*XC(2)*XC(3)+1.653061224489796D0*XC(2)**2)\br
++\tab{5}FJACC(8,1)=1.0D0\br
++\tab{5}FJACC(8,2)=-1.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(8,3)=-1.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(9,1)=1.0D0\br
++\tab{5}FJACC(9,2)=-1.285714285714286D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)*\br
++\tab{4}&*2)\br
++\tab{5}FJACC(9,3)=-1.285714285714286D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)*\br
++\tab{4}&*2)\br
++\tab{5}FJACC(10,1)=1.0D0\br
++\tab{5}FJACC(10,2)=-1.666666666666667D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(10,3)=-1.666666666666667D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(11,1)=1.0D0\br
++\tab{5}FJACC(11,2)=-2.2D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(11,3)=-2.2D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(12,1)=1.0D0\br
++\tab{5}FJACC(12,2)=-3.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(12,3)=-3.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(13,1)=1.0D0\br
++\tab{5}FJACC(13,2)=-4.333333333333333D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(13,3)=-4.333333333333333D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)\br
++\tab{4}&**2)\br
++\tab{5}FJACC(14,1)=1.0D0\br
```

```
++\tab{5}FJACC(14,2)=-7.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(14,3)=-7.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(15,1)=1.0D0\br
++\tab{5}FJACC(15,2)=-15.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}FJACC(15,3)=-15.0D0/(XC(3)**2+2.0D0*XC(2)*XC(3)+XC(2)**2)\br
++\tab{5}RETURN\br
++\tab{5}END

Asp19(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FC))
  FSTU   ==> Union(fst:FST,void:"void")
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  MFLOAT ==> MachineFloat
  VEC    ==> Vector
  VF2    ==> VectorFunctions2
  MF2    ==> MatrixCategoryFunctions2(FEXPR,VEC FEXPR,VEC FEXPR,Matrix FEXPR,EXPR MFLOAT,VEC EXPR MFLOAT,VE
  FEXPR  ==> FortranExpression([],['XC],MFLOAT)
  S      ==> Symbol

  Exports ==> FortranVectorFunctionCategory with
    coerce : VEC FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : FSTU := ["real"::FST]$FSTU
    syms : SYMTAB := empty()$SYMTAB
    declare!(M,fortranInteger()$FT,syms)$SYMTAB
    declare!(N,fortranInteger()$FT,syms)$SYMTAB
    declare!(LJC,fortranInteger()$FT,syms)$SYMTAB
    xcType : FT := construct(real,[N],false)$FT
    declare!(XC,xcType,syms)$SYMTAB
    fveccType : FT := construct(real,[M],false)$FT
    declare!(FVECC,fveccType,syms)$SYMTAB
    fjaccType : FT := construct(real,[LJC,N],false)$FT
    declare!(FJACC,fjaccType,syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$FSTU,[M,N,XC,FVECC,FJACC,LJC],syms)

    coerce(c:List FC):$ == coerce(c)$Rep
```

```
coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FC):$ == coerce(c)$Rep

-- Take a symbol, pull of the script and turn it into an integer!!
o2int(u:S):Integer ==
  o : OutputForm := first elt(scripts(u)$S,sub)
  o pretend Integer

-- To help the poor old compiler!
fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

localAssign1(s:S,j:Matrix FEXPR):FC ==
  j' : Matrix EXPR MFLOAT := map(fexpr2expr,j)$MF2
  assign(s,j')$FC

localAssign2(s:S,j:VEC FEXPR):FC ==
  j' : VEC EXPR MFLOAT := map(fexpr2expr,j)$VF2(FEXPR,EXPR MFLOAT)
  assign(s,j')$FC

coerce(u:VEC FEXPR):$ ==
  -- First zero the Jacobian matrix in case we miss some derivatives which
  -- are zero.
  import POLY INT
  seg1 : Segment (POLY INT) := segment(1::(POLY INT),LJC@S::(POLY INT))
  seg2 : Segment (POLY INT) := segment(1::(POLY INT),N@S::(POLY INT))
  s1 : SegmentBinding POLY INT := equation(I@S,seg1)
  s2 : SegmentBinding POLY INT := equation(J@S,seg2)
  as : FC := assign(FJACC,[I@S::(POLY INT),J@S::(POLY INT)],0.0::EXPR FLOAT)
  clear : FC := forLoop(s1,forLoop(s2,as))
  j:Integer
  x:S := XC::S
  pu:List(S) := []
  -- Work out which variables appear in the expressions
  for e in entries(u) repeat
    pu := setUnion(pu,variables(e)$FEXPR)
  scriptList : List Integer := map(o2int,pu)$ListFunctions2(S,Integer)
  -- This should be the maximum XC_n which occurs (there may be others
  -- which don't):
  n:Integer := reduce(max,scriptList)$List(Integer)
  p:List(S) := []
  for j in 1..n repeat p:= cons(subscript(x,[j::OutputForm])$S,p)
  p:= reverse(p)
  jac:Matrix(FEXPR) := _
  jacobian(u,p)$MultiVariableCalculusFunctions(S,FEXPR,VEC FEXPR,List(S))
  c1:FC := localAssign2(FVECC,u)
  c2:FC := localAssign1(FJACC,jac)
  [clear,c1,c2,returns()]$List(FC)::$
```

```
coerce(u:$):OutputForm == coerce(u)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
  p => restorePrecision()$NAGLinkSupportPackage


retract(u:VEC FRAC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC FRAC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
```

```
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$
```

———-

— ASP19.dotabb —

```
"ASP19" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP19"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP19" -> "FS"
```

———-

2.15 domain ASP20 Asp20

— Asp20.input —

```
)set break resume
)sys rm -f Asp20.output
)spool Asp20.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp20
--R
--R Asp20(name: Symbol)  is a domain constructor
--R Abbreviation for Asp20 is ASP20
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP20
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %            coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm             outputAsFortran : % -> Void
```

```
--R coerce : Matrix(FortranExpression([construct],[construct,QUOTEX,QUOTEHESS],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Matrix(Fraction(Polynomial(Integer))) -> %
--R retract : Matrix(Fraction(Polynomial(Float))) -> %
--R retract : Matrix(Polynomial(Integer)) -> %
--R retract : Matrix(Polynomial(Float)) -> %
--R retract : Matrix(Expression(Integer)) -> %
--R retract : Matrix(Expression(Float)) -> %
--R retractIfCan : Matrix(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Matrix(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp20.help** —

```
=====================================================================
Asp20 examples
=====================================================================

See Also:
o )show Asp20
```

———-

2.15.1 Asp20 (ASP20)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP20 Asp20 —

```
)abbrev domain ASP20 Asp20
++ Author: Mike Dewar and Godfrey Nolan and Grant Keady
++ Date Created: Dec 1993
++ Date Last Updated: 21 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp20} produces Fortran for Type 20 ASPs, for example:
++
++ \tab{5}SUBROUTINE QPHESS(N,NROWH,NCOLH,JTHCOL,HESS,X,HX)\br
++ \tab{5}DOUBLE PRECISION HX(N),X(N),HESS(NROWH,NCOLH)\br
++ \tab{5}INTEGER JTHCOL,N,NROWH,NCOLH\br
++ \tab{5}HX(1)=2.0D0*X(1)\br
++ \tab{5}HX(2)=2.0D0*X(2)\br
++ \tab{5}HX(3)=2.0D0*X(4)+2.0D0*X(3)\br
++ \tab{5}HX(4)=2.0D0*X(4)+2.0D0*X(3)\br
++ \tab{5}HX(5)=2.0D0*X(5)\br
++ \tab{5}HX(6)=(-2.0D0*X(7))+(-2.0D0*X(6))\br
++ \tab{5}HX(7)=(-2.0D0*X(7))+(-2.0D0*X(6))\br
++ \tab{5}RETURN\br
++ \tab{5}END

Asp20(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  PI     ==> PositiveInteger
  UFST   ==> Union(fst:FST,void:"void")
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  MAT    ==> Matrix
  VF2    ==> VectorFunctions2
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression([],['X,'HESS],MFLOAT)
  O      ==> OutputForm
  M2     ==> MatrixCategoryFunctions2
  MF2a   ==> M2(FRAC POLY INT,VEC FRAC POLY INT,VEC FRAC POLY INT,
```

```
              MAT FRAC POLY INT,FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2b   ==> M2(FRAC POLY FLOAT,VEC FRAC POLY FLOAT,VEC FRAC POLY FLOAT,
              MAT FRAC POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2c   ==> M2(POLY INT,VEC POLY INT,VEC POLY INT,MAT POLY INT,
              FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2d   ==> M2(POLY FLOAT,VEC POLY FLOAT,VEC POLY FLOAT,
              MAT POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2e   ==> M2(EXPR INT,VEC EXPR INT,VEC EXPR INT,MAT EXPR INT,
              FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2f   ==> M2(EXPR FLOAT,VEC EXPR FLOAT,VEC EXPR FLOAT,
              MAT EXPR FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)


  Exports ==> FortranMatrixFunctionCategory with
    coerce: MAT FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : UFST := ["real"::FST]$UFST
    syms : SYMTAB := empty()
    declare!(N,fortranInteger(),syms)$SYMTAB
    declare!(NROWH,fortranInteger(),syms)$SYMTAB
    declare!(NCOLH,fortranInteger(),syms)$SYMTAB
    declare!(JTHCOL,fortranInteger(),syms)$SYMTAB
    hessType : FT := construct(real,[NROWH,NCOLH],false)$FT
    declare!(HESS,hessType,syms)$SYMTAB
    xType : FT := construct(real,[N],false)$FT
    declare!(X,xType,syms)$SYMTAB
    declare!(HX,xType,syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$UFST,
                          [N,NROWH,NCOLH,JTHCOL,HESS,X,HX],syms)

    coerce(c:List FortranCode):$ == coerce(c)$Rep

    coerce(r:RSFC):$ == coerce(r)$Rep

    coerce(c:FortranCode):$ == coerce(c)$Rep

    -- To help the poor old compiler!
    fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

    localAssign(s:Symbol,j:VEC FEXPR):FortranCode ==
      j' : VEC EXPR MFLOAT := map(fexpr2expr,j)$VF2(FEXPR,EXPR MFLOAT)
      assign(s,j')$FortranCode

    coerce(u:MAT FEXPR):$ ==
      j:Integer
      x:Symbol := X::Symbol
```

```
  n := nrows(u)::PI
  p:VEC FEXPR := [retract(subscript(x,[j::O])$Symbol)@FEXPR for j in 1..n]
  prod:VEC FEXPR := u*p
  ([localAssign(HX,prod),returns()$FortranCode]$List(FortranCode))::$

retract(u:MAT FRAC POLY INT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2a
  v::$

retractIfCan(u:MAT FRAC POLY INT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2a
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT FRAC POLY FLOAT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2b
  v::$

retractIfCan(u:MAT FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2b
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT EXPR INT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2e
  v::$

retractIfCan(u:MAT EXPR INT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2e
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT EXPR FLOAT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2f
  v::$

retractIfCan(u:MAT EXPR FLOAT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2f
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT POLY INT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2c
  v::$

retractIfCan(u:MAT POLY INT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2c
  v case "failed" => "failed"
  (v::MAT FEXPR)::$
```

```
    retract(u:MAT POLY FLOAT):$ ==
      v : MAT FEXPR := map(retract,u)$MF2d
      v::$

    retractIfCan(u:MAT POLY FLOAT):Union($,"failed") ==
      v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2d
      v case "failed" => "failed"
      (v::MAT FEXPR)::$

    coerce(u:$):O == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP20.dotabb** —

```
"ASP20" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP20"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP20" -> "FS"
```

———-

2.16 domain ASP24 Asp24

— **Asp24.input** —

```
)set break resume
)sys rm -f Asp24.output
)spool Asp24.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp24
--R
--R Asp24(name: Symbol)  is a domain constructor
--R Abbreviation for Asp24 is ASP24
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP24
```

```
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R retract : Polynomial(Float) -> %      retract : Expression(Float) -> %
--R coerce : FortranExpression([construct],[construct,QUOTEXC],MachineFloat) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Fraction(Polynomial(Integer)) -> %
--R retract : Fraction(Polynomial(Float)) -> %
--R retract : Polynomial(Integer) -> %
--R retract : Expression(Integer) -> %
--R retractIfCan : Fraction(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Fraction(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed")
--R retractIfCan : Polynomial(Float) -> Union(%,"failed")
--R retractIfCan : Expression(Integer) -> Union(%,"failed")
--R retractIfCan : Expression(Float) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp24.help —

```
=====================================================================
Asp24 examples
=====================================================================

See Also:
o )show Asp24
```

———-

2.16.1 Asp24 (ASP24)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP24 Asp24 —

```
)abbrev domain ASP24 Asp24
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 21 March 1994
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp24} produces Fortran for Type 24 ASPs which evaluate a
++multivariate function at a point (needed for NAG routine e04jaf),
++for example:
++
++\tab{5}SUBROUTINE FUNCT1(N,XC,FC)\br
++\tab{5}DOUBLE PRECISION FC,XC(N)\br
++\tab{5}INTEGER N\br
++\tab{5}FC=10.0D0*XC(4)**4+(-40.0D0*XC(1)*XC(4)**3)+(60.0D0*XC(1)**2+5\br
++\tab{4}&.0D0)*XC(4)**2+((-10.0D0*XC(3))+(-40.0D0*XC(1)**3))*XC(4)+16.0D0*X\br
++\tab{4}&C(3)**4+(-32.0D0*XC(2)*XC(3)**3)+(24.0D0*XC(2)**2+5.0D0)*XC(3)**2+\br
++\tab{4}&(-8.0D0*XC(2)**3*XC(3))+XC(2)**4+100.0D0*XC(2)**2+20.0D0*XC(1)*XC(\br
++\tab{4}&2)+10.0D0*XC(1)**4+XC(1)**2\br
++\tab{5}RETURN\br
++\tab{5}END\br

Asp24(name): Exports == Implementation where
  name : Symbol

  FST  ==> FortranScalarType
  FT   ==> FortranType
  SYMTAB ==> SymbolTable
  RSFC ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FSTU ==> Union(fst:FST,void:"void")
```

```
FEXPR ==> FortranExpression([],['XC],MachineFloat)
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float

Exports ==> FortranFunctionCategory with
    coerce : FEXPR -> $
      ++ coerce(f) takes an object from the appropriate instantiation of
            ++ \spadtype{FortranExpression} and turns it into an ASP.


Implementation ==> add


  real : FSTU := ["real"::FST]$FSTU
  syms : SYMTAB := empty()
  declare!(N,fortranInteger(),syms)$SYMTAB
  xcType : FT := construct(real,[N::Symbol],false)$FT
  declare!(XC,xcType,syms)$SYMTAB
  declare!(FC,fortranReal(),syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$FSTU,[N,XC,FC],syms)

  coerce(c:List FortranCode):$ == coerce(c)$Rep

  coerce(r:RSFC):$ == coerce(r)$Rep

  coerce(c:FortranCode):$ == coerce(c)$Rep

  coerce(u:FEXPR):$ ==
    coerce(assign(FC,u::Expression(MachineFloat))$FortranCode)$Rep

  retract(u:FRAC POLY INT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:FRAC POLY INT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
    foo := retractIfCan(u)$FEXPR
    foo case "failed" => "failed"
    (foo::FEXPR)::$

  retract(u:FRAC POLY FLOAT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:FRAC POLY FLOAT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
    foo := retractIfCan(u)$FEXPR
    foo case "failed" => "failed"
    (foo::FEXPR)::$

  retract(u:EXPR FLOAT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:EXPR FLOAT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
```

```
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    retract(u:EXPR INT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:EXPR INT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    retract(u:POLY FLOAT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:POLY FLOAT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    retract(u:POLY INT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:POLY INT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    coerce(u:$):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP24.dotabb** —

```
"ASP24" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP24"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP24" -> "PFECAT"
```

———-

2.17 domain ASP27 Asp27

— **Asp27.input** —

```
)set break resume
)sys rm -f Asp27.output
)spool Asp27.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp27
--R
--R Asp27(name: Symbol)  is a domain constructor
--R Abbreviation for Asp27 is ASP27
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP27
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R coerce : Matrix(MachineFloat) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp27.help —

```
=====================================================================
Asp27 examples
=====================================================================

See Also:
o )show Asp27
```

———-

2.17.1 Asp27 (ASP27)



Exports:
coerce outputAsFortran

— domain ASP27 Asp27 —

```
)abbrev domain ASP27 Asp27
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Nov 1993
++ Date Last Updated: 27 April 1994
++                     6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp27} produces Fortran for Type 27 ASPs, needed for NAG routine
++f02fjf ,for example:
++
++\tab{5}FUNCTION DOT(IFLAG,N,Z,W,RWORK,LRWORK,IWORK,LIWORK)\br
++\tab{5}DOUBLE PRECISION W(N),Z(N),RWORK(LRWORK)\br
++\tab{5}INTEGER N,LIWORK,IFLAG,LRWORK,IWORK(LIWORK)\br
++\tab{5}DOT=(W(16)+(-0.5D0*W(15)))*Z(16)+((-0.5D0*W(16))+W(15)+(-0.5D0*W(1\br
++\tab{4}&4)))*Z(15)+((-0.5D0*W(15))+W(14)+(-0.5D0*W(13)))*Z(14)+((-0.5D0*W(\br
++\tab{4}&14))+W(13)+(-0.5D0*W(12)))*Z(13)+((-0.5D0*W(13))+W(12)+(-0.5D0*W(1\br
++\tab{4}&1)))*Z(12)+((-0.5D0*W(12))+W(11)+(-0.5D0*W(10)))*Z(11)+((-0.5D0*W(\br
++\tab{4}&11))+W(10)+(-0.5D0*W(9)))*Z(10)+((-0.5D0*W(10))+W(9)+(-0.5D0*W(8))\br
++\tab{4}&)*Z(9)+((-0.5D0*W(9))+W(8)+(-0.5D0*W(7)))*Z(8)+((-0.5D0*W(8))+W(7)\br
++\tab{4}&+(-0.5D0*W(6)))*Z(7)+((-0.5D0*W(7))+W(6)+(-0.5D0*W(5)))*Z(6)+((-0.\br
++\tab{4}&5D0*W(6))+W(5)+(-0.5D0*W(4)))*Z(5)+((-0.5D0*W(5))+W(4)+(-0.5D0*W(3\br
++\tab{4}&)))*Z(4)+((-0.5D0*W(4))+W(3)+(-0.5D0*W(2)))*Z(3)+((-0.5D0*W(3))+W(\br
++\tab{4}&2)+(-0.5D0*W(1)))*Z(2)+((-0.5D0*W(2))+W(1))*Z(1)\br
++\tab{5}RETURN\br
++\tab{5}END

Asp27(name): Exports == Implementation where
  name : Symbol

  O      ==> OutputForm
```

```
FST    ==> FortranScalarType
FT     ==> FortranType
SYMTAB ==> SymbolTable
UFST   ==> Union(fst:FST,void:"void")
FC     ==> FortranCode
PI     ==> PositiveInteger
RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
EXPR   ==> Expression
MAT    ==> Matrix
MFLOAT ==> MachineFloat



Exports == FortranMatrixCategory

Implementation == add


  real : UFST := ["real"::FST]$UFST
  integer : UFST := ["integer"::FST]$UFST
  syms : SYMTAB := empty()$SYMTAB
  declare!(IFLAG,fortranInteger(),syms)$SYMTAB
  declare!(N,fortranInteger(),syms)$SYMTAB
  declare!(LRWORK,fortranInteger(),syms)$SYMTAB
  declare!(LIWORK,fortranInteger(),syms)$SYMTAB
  zType : FT := construct(real,[N],false)$FT
  declare!(Z,zType,syms)$SYMTAB
  declare!(W,zType,syms)$SYMTAB
  rType : FT := construct(real,[LRWORK],false)$FT
  declare!(RWORK,rType,syms)$SYMTAB
  iType : FT := construct(integer,[LIWORK],false)$FT
  declare!(IWORK,iType,syms)$SYMTAB
  Rep := FortranProgram(name,real,
                        [IFLAG,N,Z,W,RWORK,LRWORK,IWORK,LIWORK],syms)

  -- To help the poor old compiler!
  localCoerce(u:Symbol):EXPR(MFLOAT) == coerce(u)$EXPR(MFLOAT)

  coerce (u:MAT MFLOAT):$ ==
    Ws: Symbol := W
    Zs: Symbol := Z
    code : List FC
    l:EXPR MFLOAT := "+"/ _
        [("+"/[localCoerce(elt(Ws,[j::O])$Symbol) * u(j,i)_
                                          for j in 1..nrows(u)::PI])_
         *localCoerce(elt(Zs,[i::O])$Symbol) for i in 1..ncols(u)::PI]
    c := assign(name,l)$FC
    code := [c,returns()]$List(FC)
    code::$
```

```
    coerce(c:List FortranCode):$ == coerce(c)$Rep

    coerce(r:RSFC):$ == coerce(r)$Rep

    coerce(c:FortranCode):$ == coerce(c)$Rep

    coerce(u:$):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP27.dotabb** —

```
"ASP27" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP27"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP27" -> "ALIST"
```

———-

2.18 domain ASP28 Asp28

— **Asp28.input** —

```
)set break resume
)sys rm -f Asp28.output
)spool Asp28.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp28
--R
--R Asp28(name: Symbol)  is a domain constructor
--R Abbreviation for Asp28 is ASP28
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP28
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %            coerce : List(FortranCode) -> %
```

```
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R coerce : Matrix(MachineFloat) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp28.help** —

```
=====================================================================
Asp28 examples
=====================================================================

See Also:
o )show Asp28
```

———-

2.18.1 Asp28 (ASP28)



Exports:
coerce outputAsFortran

— **domain ASP28 Asp28** —

```
)abbrev domain ASP28 Asp28
++ Author: Mike Dewar
++ Date Created: 21 March 1994
++ Date Last Updated: 28 April 1994
```

```
++                      6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp28} produces Fortran for Type 28 ASPs, used in NAG routine
++f02fjf, for example:
++
++\tab{5}SUBROUTINE IMAGE(IFLAG,N,Z,W,RWORK,LRWORK,IWORK,LIWORK)\br
++\tab{5}DOUBLE PRECISION Z(N),W(N),IWORK(LRWORK),RWORK(LRWORK)\br
++\tab{5}INTEGER N,LIWORK,IFLAG,LRWORK\br
++\tab{5}W(1)=0.01707454969713436D0*Z(16)+0.00174739587495405 1D0*Z(15)+0.00\br
++\tab{4}&2106973900813502D0*Z(14)+0.00295743499176908 7D0*Z(13)+(-0.00700554\br
++\tab{4}&0882865317D0*Z(12))+(-0.01219194009813166D0*Z(11))+0.0037230647365\br
++\tab{4}&3087D0*Z(10)+0.04932374658377151D0*Z(9)+(-0.03586220812223305D0*Z(\br
++\tab{4}&8))+(-0.04723268012114625D0*Z(7))+(-0.02434652144032987D0*Z(6))+0.\br
++\tab{4}&2264766947290192D0*Z(5)+(-0.1385343580686922D0*Z(4))+(-0.116530050\br
++\tab{4}&8238904D0*Z(3))+(-0.2803531651057233D0*Z(2))+1.019463911841327D0*Z\br
++\tab{4}&(1)\br
++\tab{5}W(2)=0.0227345011107737D0*Z(16)+0.00881232119739807 2D0*Z(15)+0.010\br
++\tab{4}&94012210519586D0*Z(14)+(-0.01764072463999744D0*Z(13))+(-0.01357136\br
++\tab{4}&72105995D0*Z(12))+0.00157466157362272D0*Z(11)+0.05258889186338282D\br
++\tab{4}&0*Z(10)+(-0.01981532388243379D0*Z(9))+(-0.06095390688679697D0*Z(8)\br
++\tab{4}&)+(-0.04153119955569051D0*Z(7))+0.2176561076571465D0*Z(6)+(-0.0532\br
++\tab{4}&5555586632358D0*Z(5))+(-0.1688977368984641D0*Z(4))+(-0.32440166056\br
++\tab{4}&67343D0*Z(3))+0.9128222941872173D0*Z(2)+(-0.2419652703415429D0*Z(1\br
++\tab{4}&))\br
++\tab{5}W(3)=0.03371198197190302D0*Z(16)+0.02021603150122265D0*Z(15)+(-0.0\br
++\tab{4}&06607305534689702D0*Z(14))+(-0.03023922389681 79D0*Z(13))+0.002033\br
++\tab{4}&305231024948D0*Z(12)+0.05375944956767728D0*Z(11)+(-0.0163213312502\br
++\tab{4}&9967D0*Z(10))+(-0.05483186562035512D0*Z(9))+(-0.04901428822579872D\br
++\tab{4}&0*Z(8))+0.2091097927887612D0*Z(7)+(-0.05760560341383113D0*Z(6))+(-\br
++\tab{4}&0.1236679206156403D0*Z(5))+(-0.3523683853026259D0*Z(4))+0.88929961\br
++\tab{4}&32269974D0*Z(3)+(-0.2995429545781457D0*Z(2))+(-0.02986582812574917\br
++\tab{4}&D0*Z(1))\br
++\tab{5}W(4)=0.05141563713660119D0*Z(16)+0.00523916596077929 9D0*Z(15)+(-0.\br
++\tab{4}&01623427735779699D0*Z(14))+(-0.01965809746040371D0*Z(13))+0.054688\br
++\tab{4}&97337339577D0*Z(12)+(-0.014224695935687D0*Z(11))+(-0.0505181779315\br
++\tab{4}&6355D0*Z(10))+(-0.04353074206076491D0*Z(9))+0.2012230497530726D0*Z\br
++\tab{4}&(8)+(-0.06630874514535952D0*Z(7))+(-0.1280829963720053D0*Z(6))+(-0\br
++\tab{4}&.305169742604165D0*Z(5))+0.8600427128450191D0*Z(4)+(-0.32415033802\br
++\tab{4}&68184D0*Z(3))+(-0.09033531980693314D0*Z(2))+0.09089205517109111D0*\br
++\tab{4}&Z(1)\br
++\tab{5}W(5)=0.04556369767776375D0*Z(16)+(-0.00182273697581869D0*Z(15))+(\br
++\tab{4}&-0.002512226501941856D0*Z(14))+0.02947046460707379D0*Z(13)+(-0.014\br
++\tab{4}&45079632086177D0*Z(12))+(-0.05034242196614937D0*Z(11))+(-0.0376966\br
++\tab{4}&3291725935D0*Z(10))+0.2171103102175198D0*Z(9)+(-0.0824949256021352\br
++\tab{4}&4D0*Z(8))+(-0.1473995209288945D0*Z(7))+(-0.315042193418466D0*Z(6))\br
++\tab{4}&+0.9591623347824002D0*Z(5)+(-0.3852396953763045D0*Z(4))+(-0.141718\br
++\tab{4}&5427288274D0*Z(3))+(-0.03423495461011043D0*Z(2))+0.319820917706851\br
++\tab{4}&6D0*Z(1)\br
++\tab{5}W(6)=0.04015147277405744D0*Z(16)+0.01328585741341559D0*Z(15)+0.048\br
```

```
++\tab{4}&26082005465965D0*Z(14)+(-0.04319641116207706D0*Z(13))+(-0.04931323\br
++\tab{4}&319055762D0*Z(12))+(-0.03526886317505474D0*Z(11))+0.22295383396730\br
++\tab{4}&01D0*Z(10)+(-0.07375317649315155D0*Z(9))+(-0.1589391311991561D0*Z(\br
++\tab{4}&8))+(-0.32800191089037 7D0*Z(7))+0.952576555482747D0*Z(6)+(-0.31583\br
++\tab{4}&09975786731D0*Z(5))+(-0.1846882042225383D0*Z(4))+(-0.0703762046700\br
++\tab{4}&4427D0*Z(3))+0.2311852964327382D0*Z(2)+0.04254083491825025D0*Z(1)\br
++\tab{5}W(7)=0.06069778964023718D0*Z(16)+0.06681263884671322D0*Z(15)+(-0.0\br
++\tab{4}&2113506688615768D0*Z(14))+(-0.083996867458326D0*Z(13))+(-0.0329843\br
++\tab{4}&8523869648D0*Z(12))+0.2276878326327734D0*Z(11)+(-0.067356038933017\br
++\tab{4}&95D0*Z(10))+(-0.1559813965382218D0*Z(9))+(-0.3363262957694705D0*Z(\br
++\tab{4}&8))+0.9442791158560948D0*Z(7)+(-0.3199955249404657D0*Z(6))+(-0.136\br
++\tab{4}&2463839920727D0*Z(5))+(-0.1006185171570586D0*Z(4))+0.2057504515015\br
++\tab{4}&423D0*Z(3)+(-0.02065879269286707D0*Z(2))+0.03160990266745513D0*Z(1\br
++\tab{4}&)\br
++\tab{5}W(8)=0.126386868896738D0*Z(16)+0.002563370039476418D0*Z(15)+(-0.05\br
++\tab{4}&581757739455641D0*Z(14))+(-0.07777893205900685D0*Z(13))+0.23117338\br
++\tab{4}&45834199D0*Z(12)+(-0.06031581134427592D0*Z(11))+(-0.14805474755869\br
++\tab{4}&52D0*Z(10))+(-0.3364014128402243D0*Z(9))+0.9364014128402244D0*Z(8)\br
++\tab{4}&+(-0.3269452524413048D0*Z(7))+(-0.1396841886557241D0*Z(6))+(-0.056\br
++\tab{4}&1733845834199D0*Z(5))+0.1777789320590069D0*Z(4)+(-0.04418242260544\br
++\tab{4}&359D0*Z(3))+(-0.02756337003947642D0*Z(2))+0.07361313110326199D0*Z(\br
++\tab{4}&1)\br
++\tab{5}W(9)=0.07361313110326199D0*Z(16)+(-0.02756337003947642D0*Z(15))+(-\br
++\tab{4}&0.04418242260544359D0*Z(14))+0.1777789320590069D0*Z(13)+(-0.056173\br
++\tab{4}&3845834199D0*Z(12))+(-0.1396841886557241D0*Z(11))+(-0.326945252441\br
++\tab{4}&3048D0*Z(10))+0.9364014128402244D0*Z(9)+(-0.3364014128402243D0*Z(8\br
++\tab{4}&))+(-0.1480547475586952D0*Z(7))+(-0.06031581134427592D0*Z(6))+0.23\br
++\tab{4}&11733845834199D0*Z(5)+(-0.07777893205900685D0*Z(4))+(-0.0558175773\br
++\tab{4}&9455641D0*Z(3))+0.002563370039476418D0*Z(2)+0.126386868896738D0*Z(\br
++\tab{4}&1)\br
++\tab{5}W(10)=0.03160990266745513D0*Z(16)+(-0.02065879269286707D0*Z(15))+0\br
++\tab{4}&.2057504515015423D0*Z(14)+(-0.1006185171570586D0*Z(13))+(-0.136246\br
++\tab{4}&3839920727D0*Z(12))+(-0.3199955249404657D0*Z(11))+0.94427911585609\br
++\tab{4}&48D0*Z(10)+(-0.3363262957694705D0*Z(9))+(-0.1559813965382218D0*Z(8\br
++\tab{4}&))+(-0.06735603893301795D0*Z(7))+0.2276878326327734D0*Z(6)+(-0.032\br
++\tab{4}&98438523869648D0*Z(5))+(-0.083996867458326D0*Z(4))+(-0.02113506688\br
++\tab{4}&615768D0*Z(3))+0.06681263884671322D0*Z(2)+0.06069778964023718D0*Z(\br
++\tab{4}&1)\br
++\tab{5}W(11)=0.04254083491825025D0*Z(16)+0.2311852964327382D0*Z(15)+(-0.0\br
++\tab{4}&7037620467004427D0*Z(14))+(-0.1846882042225383D0*Z(13))+(-0.315830\br
++\tab{4}&9975786731D0*Z(12))+0.952576555482747D0*Z(11)+(-0.328001910890377D\br
++\tab{4}&0*Z(10))+(-0.1589391311991561D0*Z(9))+(-0.07375317649315155D0*Z(8)\br
++\tab{4}&)+0.2229538339673001D0*Z(7)+(-0.03526886317505474D0*Z(6))+(-0.0493\br
++\tab{4}&1323319055762D0*Z(5))+(-0.04319641116207706D0*Z(4))+0.048260820054\br
++\tab{4}&65965D0*Z(3)+0.01328585741341559D0*Z(2)+0.04015147277405744D0*Z(1)\br
++\tab{5}W(12)=0.3198209177068516D0*Z(16)+(-0.03423495461011043D0*Z(15))+(-\br
++\tab{4}&0.1417185427288274D0*Z(14))+(-0.3852396953763045D0*Z(13))+0.959162\br
++\tab{4}&3347824002D0*Z(12)+(-0.315042193418466D0*Z(11))+(-0.14739952092889\br
++\tab{4}&45D0*Z(10))+(-0.08249492560213524D0*Z(9))+0.2171103102175198D0*Z(8\br
++\tab{4}&)+(-0.03769663291725935D0*Z(7))+(-0.05034242196614937D0*Z(6))+(-0.\br
```

```
++\tab{4}&01445079632086177D0*Z(5))+0.02947046460707379D0*Z(4)+(-0.002512226\br
++\tab{4}&501941856D0*Z(3))+(-0.018227373697581869D0*Z(2))+0.045563697677763\br
++\tab{4}&75D0*Z(1)\br
++\tab{5}W(13)=0.09089205517109111D0*Z(16)+(-0.09033531980693314D0*Z(15))+(\br
++\tab{4}&-0.3241503380268184D0*Z(14))+0.8600427128450191D0*Z(13)+(-0.305169\br
++\tab{4}&742604165D0*Z(12))+(-0.1280829963720053D0*Z(11))+(-0.0663087451453\br
++\tab{4}&5952D0*Z(10))+0.2012230497530726D0*Z(9)+(-0.04353074206076491D0*Z(\br
++\tab{4}&8))+(-0.05051817793156355D0*Z(7))+(-0.01422469593568 7D0*Z(6))+0.05\br
++\tab{4}&468897337339577D0*Z(5)+(-0.01965809746040371D0*Z(4))+(-0.016234277\br
++\tab{4}&35779699D0*Z(3))+0.005239165960779299D0*Z(2)+0.0514156371366011 9D0\br
++\tab{4}&*Z(1)\br
++\tab{5}W(14)=(-0.02986582812574917D0*Z(16))+(-0.2995429545781457D0*Z(15))\br
++\tab{4}&+0.8892996132269974D0*Z(14)+(-0.3523683853026259D0*Z(13))+(-0.1236\br
++\tab{4}&679206156403D0*Z(12))+(-0.05760560341383113D0*Z(11))+0.20910979278\br
++\tab{4}&87612D0*Z(10)+(-0.04901428822579872D0*Z(9))+(-0.05483186562035512D\br
++\tab{4}&0*Z(8))+(-0.01632133125029967D0*Z(7))+0.05375944956767728D0*Z(6)+0\br
++\tab{4}&.002033305231024948D0*Z(5)+(-0.03032392238968179D0*Z(4))+(-0.00660\br
++\tab{4}&7305534689702D0*Z(3))+0.02021603150122265D0*Z(2)+0.033711981971903\br
++\tab{4}&02D0*Z(1)\br
++\tab{5}W(15)=(-0.2419652703415429D0*Z(16))+0.9128222941872173D0*Z(15)+(-0\br
++\tab{4}&.3244016605667343D0*Z(14))+(-0.1688977368984641D0*Z(13))+(-0.05325\br
++\tab{4}&555586632358D0*Z(12))+0.2176561076571465D0*Z(11)+(-0.0415311995556\br
++\tab{4}&9051D0*Z(10))+(-0.06095390688679697D0*Z(9))+(-0.01981532388243379D\br
++\tab{4}&0*Z(8))+0.05258889186338282D0*Z(7)+0.00157466157362272D0*Z(6)+(-0.\br
++\tab{4}&0135713672105995D0*Z(5))+(-0.01764072463999744D0*Z(4))+0.010940122\br
++\tab{4}&10519586D0*Z(3)+0.008812321197398072D0*Z(2)+0.0227345011107737D0*Z\br
++\tab{4}&(1)\br
++\tab{5}W(16)=1.019463911841327D0*Z(16)+(-0.2803531651057233D0*Z(15))+(-0.\br
++\tab{4}&1165300508238904D0*Z(14))+(-0.1385343580686922D0*Z(13))+0.22647669\br
++\tab{4}&47290192D0*Z(12)+(-0.02434652144032987D0*Z(11))+(-0.04723268012114\br
++\tab{4}&625D0*Z(10))+(-0.03586220812223305D0*Z(9))+0.04932374658377151D0*Z\br
++\tab{4}&(8)+0.00372306473653087D0*Z(7)+(-0.01219194009813166D0*Z(6))+(-0.0\br
++\tab{4}&07005540882865317D0*Z(5))+0.002957434991769087D0*Z(4)+0.0021069739\br
++\tab{4}&00813502D0*Z(3)+0.001747395874954051D0*Z(2)+0.01707454969713436D0*\br
++\tab{4}&Z(1)\br
++\tab{5}RETURN\br
++\tab{5}END\br

Asp28(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  FC     ==> FortranCode
  PI     ==> PositiveInteger
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  EXPR   ==> Expression
  MFLOAT ==> MachineFloat
  VEC    ==> Vector
```

```
UFST   ==> Union(fst:FST,void:"void")
MAT    ==> Matrix

Exports == FortranMatrixCategory

Implementation == add


  real : UFST := ["real"::FST]$UFST
  syms : SYMTAB := empty()
  declare!(IFLAG,fortranInteger(),syms)$SYMTAB
  declare!(N,fortranInteger(),syms)$SYMTAB
  declare!(LRWORK,fortranInteger(),syms)$SYMTAB
  declare!(LIWORK,fortranInteger(),syms)$SYMTAB
  xType : FT := construct(real,[N],false)$FT
  declare!(Z,xType,syms)$SYMTAB
  declare!(W,xType,syms)$SYMTAB
  rType : FT := construct(real,[LRWORK],false)$FT
  declare!(RWORK,rType,syms)$SYMTAB
  iType : FT := construct(real,[LIWORK],false)$FT
  declare!(IWORK,rType,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$UFST,
                        [IFLAG,N,Z,W,RWORK,LRWORK,IWORK,LIWORK],syms)

  -- To help the poor old compiler!
  localCoerce(u:Symbol):EXPR(MFLOAT) == coerce(u)$EXPR(MFLOAT)

  coerce (u:MAT MFLOAT):$ ==
    Zs: Symbol := Z
    code : List FC
    r: List EXPR MFLOAT
    r := ["+"/[u(j,i)*localCoerce(elt(Zs,[i::OutputForm])$Symbol)_
                      for i in 1..ncols(u)$MAT(MFLOAT)::PI]_
                      for j in 1..nrows(u)$MAT(MFLOAT)::PI]
    code := [assign(W@Symbol,vector(r)$VEC(EXPR MFLOAT)),returns()]$List(FC)
    code::$

  coerce(c:FortranCode):$ == coerce(c)$Rep

  coerce(r:RSFC):$ == coerce(r)$Rep

  coerce(c:List FortranCode):$ == coerce(c)$Rep

  coerce(u:$):OutputForm == coerce(u)$Rep

  outputAsFortran(u):Void ==
    p := checkPrecision()$NAGLinkSupportPackage
    outputAsFortran(u)$Rep
    p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP28.dotabb** —

```
"ASP28" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP28"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP28" -> "ALIST"
```

———-

2.19 domain ASP29 Asp29

— **Asp29.input** —

```
)set break resume
)sys rm -f Asp29.output
)spool Asp29.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp29
--R
--R Asp29(name: Symbol)  is a domain constructor
--R Abbreviation for Asp29 is ASP29
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP29
--R
--R------------------------------ Operations --------------------------------
--R coerce : % -> OutputForm              outputAsFortran : () -> Void
--R outputAsFortran : % -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp29.help** —

```
=======================================================================
Asp29 examples
```

```
================================================================

See Also:
o )show Asp29
```

2.19.1 Asp29 (ASP29)



Exports:
coerce outputAsFortran

— domain ASP29 Asp29 —

```
)abbrev domain ASP29 Asp29
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Nov 1993
++ Date Last Updated: 18 March 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp29} produces Fortran for Type 29 ASPs, needed for NAG routine
++f02fjf, for example:
++
++\tab{5}SUBROUTINE MONIT(ISTATE,NEXTIT,NEVALS,NEVECS,K,F,D)\br
++\tab{5}DOUBLE PRECISION D(K),F(K)\br
++\tab{5}INTEGER K,NEXTIT,NEVALS,NVECS,ISTATE\br
++\tab{5}CALL F02FJZ(ISTATE,NEXTIT,NEVALS,NEVECS,K,F,D)\br
++\tab{5}RETURN\br
++\tab{5}END\br

Asp29(name): Exports == Implementation where
  name : Symbol

  FST  ==> FortranScalarType
```

```
FT   ==> FortranType
FSTU   ==> Union(fst:FST,void:"void")
SYMTAB ==> SymbolTable
FC   ==> FortranCode
PI   ==> PositiveInteger
EXF   ==> Expression Float
EXI   ==> Expression Integer
VEF  ==> Vector Expression Float
VEI  ==> Vector Expression Integer
MEI  ==> Matrix Expression Integer
MEF  ==> Matrix Expression Float
UEXPR ==> Union(I: Expression Integer,F: Expression Float,_
               CF: Expression Complex Float)
RSFC ==> Record(localSymbols:SymbolTable,code:List(FortranCode))

Exports == FortranProgramCategory  with
   outputAsFortran:() -> Void
     ++outputAsFortran() generates the default code for \spadtype{ASP29}.


Implementation == add

  import FST
  import FT
  import FC
  import SYMTAB

  real : FSTU := ["real"::FST]$FSTU
  integer : FSTU := ["integer"::FST]$FSTU
  syms : SYMTAB := empty()
  declare!(ISTATE,fortranInteger(),syms)
  declare!(NEXTIT,fortranInteger(),syms)
  declare!(NEVALS,fortranInteger(),syms)
  declare!(NVECS,fortranInteger(),syms)
  declare!(K,fortranInteger(),syms)
  kType : FT := construct(real,[K],false)$FT
  declare!(F,kType,syms)
  declare!(D,kType,syms)
  Rep := FortranProgram(name,["void"]$FSTU,
                        [ISTATE,NEXTIT,NEVALS,NEVECS,K,F,D],syms)


  outputAsFortran():Void ==
    callOne := call("F02FJZ(ISTATE,NEXTIT,NEVALS,NEVECS,K,F,D)")
    code : List FC := [callOne,returns()]$List(FC)
    outputAsFortran(coerce(code)@Rep)$Rep
```

— **ASP29.dotabb** —

```
"ASP29" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP29"]
"FORTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FORTCAT"]
"ASP29" -> "FORTCAT"
```

———-

2.20 domain ASP30 Asp30

— **Asp30.input** —

```
)set break resume
)sys rm -f Asp30.output
)spool Asp30.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp30
--R
--R Asp30(name: Symbol)  is a domain constructor
--R Abbreviation for Asp30 is ASP30
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP30
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R coerce : Matrix(MachineFloat) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp30.help** —

```
=====================================================================
Asp30 examples
```

```
================================================================

See Also:
o )show Asp30
```

2.20.1 Asp30 (ASP30)



Exports:
coerce outputAsFortran

— domain ASP30 Asp30 —

```
)abbrev domain ASP30 Asp30
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Nov 1993
++ Date Last Updated: 28 March 1994
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp30} produces Fortran for Type 30 ASPs, needed for NAG routine
++f04qaf, for example:
++
++\tab{5}SUBROUTINE APROD(MODE,M,N,X,Y,RWORK,LRWORK,IWORK,LIWORK)\br
++\tab{5}DOUBLE PRECISION X(N),Y(M),RWORK(LRWORK)\br
++\tab{5}INTEGER M,N,LIWORK,IFAIL,LRWORK,IWORK(LIWORK),MODE\br
++\tab{5}DOUBLE PRECISION A(5,5)\br
++\tab{5}EXTERNAL F06PAF\br
++\tab{5}A(1,1)=1.0D0\br
++\tab{5}A(1,2)=0.0D0\br
++\tab{5}A(1,3)=0.0D0\br
++\tab{5}A(1,4)=-1.0D0\br
++\tab{5}A(1,5)=0.0D0\br
```

```
++\tab{5}A(2,1)=0.0D0\br
++\tab{5}A(2,2)=1.0D0\br
++\tab{5}A(2,3)=0.0D0\br
++\tab{5}A(2,4)=0.0D0\br
++\tab{5}A(2,5)=-1.0D0\br
++\tab{5}A(3,1)=0.0D0\br
++\tab{5}A(3,2)=0.0D0\br
++\tab{5}A(3,3)=1.0D0\br
++\tab{5}A(3,4)=-1.0D0\br
++\tab{5}A(3,5)=0.0D0\br
++\tab{5}A(4,1)=-1.0D0\br
++\tab{5}A(4,2)=0.0D0\br
++\tab{5}A(4,3)=-1.0D0\br
++\tab{5}A(4,4)=4.0D0\br
++\tab{5}A(4,5)=-1.0D0\br
++\tab{5}A(5,1)=0.0D0\br
++\tab{5}A(5,2)=-1.0D0\br
++\tab{5}A(5,3)=0.0D0\br
++\tab{5}A(5,4)=-1.0D0\br
++\tab{5}A(5,5)=4.0D0\br
++\tab{5}IF(MODE.EQ.1)THEN\br
++\tab{7}CALL F06PAF('N',M,N,1.0D0,A,M,X,1,1.0D0,Y,1)\br
++\tab{5}ELSEIF(MODE.EQ.2)THEN\br
++\tab{7}CALL F06PAF('T',M,N,1.0D0,A,M,Y,1,1.0D0,X,1)\br
++\tab{5}ENDIF\br
++\tab{5}RETURN\br
++\tab{5}END

Asp30(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  FC     ==> FortranCode
  PI     ==> PositiveInteger
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  UFST   ==> Union(fst:FST,void:"void")
  MAT    ==> Matrix
  MFLOAT ==> MachineFloat
  EXI    ==> Expression Integer
  UEXPR  ==> Union(I:Expression Integer,F:Expression Float,_
                 CF:Expression Complex Float,switch:Switch)
  S      ==> Symbol

  Exports == FortranMatrixCategory

  Implementation == add

    import FC
```

```
import FT
import Switch

real : UFST := ["real"::FST]$UFST
integer : UFST := ["integer"::FST]$UFST
syms : SYMTAB := empty()$SYMTAB
declare!(MODE,fortranInteger()$FT,syms)$SYMTAB
declare!(M,fortranInteger()$FT,syms)$SYMTAB
declare!(N,fortranInteger()$FT,syms)$SYMTAB
declare!(LRWORK,fortranInteger()$FT,syms)$SYMTAB
declare!(LIWORK,fortranInteger()$FT,syms)$SYMTAB
xType : FT := construct(real,[N],false)$FT
declare!(X,xType,syms)$SYMTAB
yType : FT := construct(real,[M],false)$FT
declare!(Y,yType,syms)$SYMTAB
rType : FT := construct(real,[LRWORK],false)$FT
declare!(RWORK,rType,syms)$SYMTAB
iType : FT := construct(integer,[LIWORK],false)$FT
declare!(IWORK,iType,syms)$SYMTAB
declare!(IFAIL,fortranInteger()$FT,syms)$SYMTAB
Rep := FortranProgram(name,["void"]$UFST,
                      [MODE,M,N,X,Y,RWORK,LRWORK,IWORK,LIWORK],syms)

coerce(a:MAT MFLOAT):$ ==
  locals : SYMTAB := empty()
  numRows := nrows(a) :: Polynomial Integer
  numCols := ncols(a) :: Polynomial Integer
  declare!(A,[real,[numRows,numCols],false]$FT,locals)
  declare!(F06PAF@S,construct(["void"]$UFST,[]@List(S),true)$FT,locals)
  ptA:UEXPR := [("MODE"::S)::EXI]
  ptB:UEXPR := [1::EXI]
  ptC:UEXPR := [2::EXI]
  sw1 : Switch := EQ(ptA,ptB)$Switch
  sw2 : Switch := EQ(ptA,ptC)$Switch
  callOne := call("F06PAF('N',M,N,1.0D0,A,M,X,1,1.0D0,Y,1)")
  callTwo := call("F06PAF('T',M,N,1.0D0,A,M,Y,1,1.0D0,X,1)")
  c : FC := cond(sw1,callOne,cond(sw2,callTwo))
  code : List FC := [assign(A,a),c,returns()]
  ([locals,code]$RSFC)::$

coerce(c:List FortranCode):$ == coerce(c)$Rep

coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FortranCode):$ == coerce(c)$Rep

coerce(u:$):OutputForm == coerce(u)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
```

```
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP30.dotabb —

```
"ASP30" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP30"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP30" -> "ALIST"
```

———-

2.21 domain ASP31 Asp31

— Asp31.input —

```
)set break resume
)sys rm -f Asp31.output
)spool Asp31.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp31
--R
--R Asp31(name: Symbol)  is a domain constructor
--R Abbreviation for Asp31 is ASP31
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP31
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEX],[construct,QUOTEY],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
```

```
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp31.help —

```
========================================================================
Asp31 examples
========================================================================

See Also:
o )show Asp31
```

———-

2.21.1 Asp31 (ASP31)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP31 Asp31 —

```
)abbrev domain ASP31 Asp31
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
```

```
++ Date Created: Mar 1993
++ Date Last Updated: 22 March 1994
++                    6 October 1994
++ Related Constructors: FortranMatrixFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp31} produces Fortran for Type 31 ASPs, needed for NAG routine
++d02ejf, for example:
++
++\tab{5}SUBROUTINE PEDERV(X,Y,PW)\br
++\tab{5}DOUBLE PRECISION X,Y(*)\br
++\tab{5}DOUBLE PRECISION PW(3,3)\br
++\tab{5}PW(1,1)=-0.03999999999999999D0\br
++\tab{5}PW(1,2)=10000.0D0*Y(3)\br
++\tab{5}PW(1,3)=10000.0D0*Y(2)\br
++\tab{5}PW(2,1)=0.03999999999999999D0\br
++\tab{5}PW(2,2)=(-10000.0D0*Y(3))+(-60000000.0D0*Y(2))\br
++\tab{5}PW(2,3)=-10000.0D0*Y(2)\br
++\tab{5}PW(3,1)=0.0D0\br
++\tab{5}PW(3,2)=60000000.0D0*Y(2)\br
++\tab{5}PW(3,3)=0.0D0\br
++\tab{5}RETURN\br
++\tab{5}END

Asp31(name): Exports == Implementation where
  name : Symbol

  O      ==> OutputForm
  FST    ==> FortranScalarType
  UFST   ==> Union(fst:FST,void:"void")
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression(['X],['Y],MFLOAT)
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  MAT    ==> Matrix
  VF2    ==> VectorFunctions2
  MF2    ==> MatrixCategoryFunctions2(FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR,
                   EXPR MFLOAT,VEC EXPR MFLOAT,VEC EXPR MFLOAT,MAT EXPR MFLOAT)



  Exports ==> FortranVectorFunctionCategory with
    coerce : VEC FEXPR -> $
```

```
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add


  real : UFST := ["real"::FST]$UFST
  syms : SYMTAB := empty()
  declare!(X,fortranReal(),syms)$SYMTAB
  yType : FT := construct(real,["*"::Symbol],false)$FT
  declare!(Y,yType,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$UFST,[X,Y,PW],syms)

  -- To help the poor old compiler!
  fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

  localAssign(s:Symbol,j:MAT FEXPR):FC ==
    j' : MAT EXPR MFLOAT := map(fexpr2expr,j)$MF2
    assign(s,j')$FC

  makeXList(n:Integer):List(Symbol) ==
    j:Integer
    y:Symbol := Y::Symbol
    p:List(Symbol) := []
    for j in 1 .. n repeat p:= cons(subscript(y,[j::OutputForm])$Symbol,p)
    p:= reverse(p)

  coerce(u:VEC FEXPR):$ ==
    dimension := #u::Polynomial Integer
    locals : SYMTAB := empty()
    declare!(PW,[real,[dimension,dimension],false]$FT,locals)$SYMTAB
    n:Integer := maxIndex(u)$VEC(FEXPR)
    p:List(Symbol) := makeXList(n)
    jac: MAT FEXPR := jacobian(u,p)$MultiVariableCalculusFunctions(_
                                  Symbol,FEXPR ,VEC FEXPR,List(Symbol))
    code : List FC := [localAssign(PW,jac),returns()$FC]$List(FC)
    ([locals,code]$RSFC)::$

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v::$
```

```
retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

coerce(c:List FC):$ == coerce(c)$Rep

coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FC):$ == coerce(c)$Rep

coerce(u:$):O == coerce(u)$Rep
```

```
    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP31.dotabb** —

```
"ASP31" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP31"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP31" -> "FS"
```

———-

2.22 domain ASP33 Asp33

— **Asp33.input** —

```
)set break resume
)sys rm -f Asp33.output
)spool Asp33.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp33
--R
--R Asp33(name: Symbol)  is a domain constructor
--R Abbreviation for Asp33 is ASP33
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP33
--R
--R------------------------------ Operations --------------------------------
--R coerce : % -> OutputForm              outputAsFortran : () -> Void
--R outputAsFortran : % -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp33.help** —

```
==========================================================================
Asp33 examples
==========================================================================

See Also:
o )show Asp33
```

———-

2.22.1 Asp33 (ASP33)



Exports:
coerce outputAsFortran

— **domain ASP33 Asp33** —

```
)abbrev domain ASP33 Asp33
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Nov 1993
++ Date Last Updated: 30 March 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory.
++ Description:
++\spadtype{Asp33} produces Fortran for Type 33 ASPs, needed for NAG routine
++d02kef.  The code is a dummy ASP:
++
++\tab{5}SUBROUTINE REPORT(X,V,JINT)\br
++\tab{5}DOUBLE PRECISION V(3),X\br
++\tab{5}INTEGER JINT\br
++\tab{5}RETURN\br
++\tab{5}END
```

```
Asp33(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  UFST   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  FC     ==> FortranCode
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))

  Exports ==> FortranProgramCategory with
     outputAsFortran:() -> Void
      ++outputAsFortran() generates the default code for \spadtype{ASP33}.


  Implementation ==> add

    real : UFST := ["real"::FST]$UFST
    syms : SYMTAB := empty()
    declare!(JINT,fortranInteger(),syms)$SYMTAB
    declare!(X,fortranReal(),syms)$SYMTAB
    vType : FT := construct(real,["3"::Symbol],false)$FT
    declare!(V,vType,syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$UFST,[X,V,JINT],syms)

    outputAsFortran():Void ==
      outputAsFortran( (returns()$FortranCode)::Rep )$Rep

    outputAsFortran(u):Void == outputAsFortran(u)$Rep

    coerce(u:$):OutputForm == coerce(u)$Rep
```

———-

— ASP33.dotabb —

```
"ASP33" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP33"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP33" -> "ALIST"
```

———-

2.23 domain ASP34 Asp34

— Asp34.input —

```
)set break resume
)sys rm -f Asp34.output
)spool Asp34.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp34
--R
--R Asp34(name: Symbol)  is a domain constructor
--R Abbreviation for Asp34 is ASP34
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP34
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R coerce : Matrix(MachineFloat) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp34.help —

```
=====================================================================
Asp34 examples
=====================================================================

See Also:
o )show Asp34
```

———-

2.23.1 Asp34 (ASP34)



Exports:
coerce outputAsFortran

— domain ASP34 Asp34 —

```
)abbrev domain ASP34 Asp34
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Nov 1993
++ Date Last Updated: 14 June 1994 (Themos Tsikas)
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp34} produces Fortran for Type 34 ASPs, needed for NAG routine
++f04mbf, for example:
++
++\tab{5}SUBROUTINE MSOLVE(IFLAG,N,X,Y,RWORK,LRWORK,IWORK,LIWORK)\br
++\tab{5}DOUBLE PRECISION RWORK(LRWORK),X(N),Y(N)\br
++\tab{5}INTEGER I,J,N,LIWORK,IFLAG,LRWORK,IWORK(LIWORK)\br
++\tab{5}DOUBLE PRECISION W1(3),W2(3),MS(3,3)\br
++\tab{5}IFLAG=-1\br
++\tab{5}MS(1,1)=2.0D0\br
++\tab{5}MS(1,2)=1.0D0\br
++\tab{5}MS(1,3)=0.0D0\br
++\tab{5}MS(2,1)=1.0D0\br
++\tab{5}MS(2,2)=2.0D0\br
++\tab{5}MS(2,3)=1.0D0\br
++\tab{5}MS(3,1)=0.0D0\br
++\tab{5}MS(3,2)=1.0D0\br
++\tab{5}MS(3,3)=2.0D0\br
++\tab{5}CALL F04ASF(MS,N,X,N,Y,W1,W2,IFLAG)\br
++\tab{5}IFLAG=-IFLAG\br
++\tab{5}RETURN\br
++\tab{5}END

Asp34(name): Exports == Implementation where
```

```
name : Symbol

FST    ==> FortranScalarType
FT     ==> FortranType
UFST   ==> Union(fst:FST,void:"void")
SYMTAB ==> SymbolTable
FC     ==> FortranCode
PI     ==> PositiveInteger
EXI    ==> Expression Integer
RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))

Exports == FortranMatrixCategory

Implementation == add

  real : UFST := ["real"::FST]$UFST
  integer : UFST := ["integer"::FST]$UFST
  syms : SYMTAB := empty()$SYMTAB
  declare!(IFLAG,fortranInteger(),syms)$SYMTAB
  declare!(N,fortranInteger(),syms)$SYMTAB
  xType : FT := construct(real,[N],false)$FT
  declare!(X,xType,syms)$SYMTAB
  declare!(Y,xType,syms)$SYMTAB
  declare!(LRWORK,fortranInteger(),syms)$SYMTAB
  declare!(LIWORK,fortranInteger(),syms)$SYMTAB
  rType : FT := construct(real,[LRWORK],false)$FT
  declare!(RWORK,rType,syms)$SYMTAB
  iType : FT := construct(integer,[LIWORK],false)$FT
  declare!(IWORK,iType,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$UFST,
                        [IFLAG,N,X,Y,RWORK,LRWORK,IWORK,LIWORK],syms)

  -- To help the poor old compiler
  localAssign(s:Symbol,u:EXI):FC == assign(s,u)$FC

  coerce(u:Matrix MachineFloat):$ ==
    dimension := nrows(u) ::Polynomial Integer
    locals : SYMTAB := empty()$SYMTAB
    declare!(I,fortranInteger(),syms)$SYMTAB
    declare!(J,fortranInteger(),syms)$SYMTAB
    declare!(W1,[real,[dimension],false]$FT,locals)$SYMTAB
    declare!(W2,[real,[dimension],false]$FT,locals)$SYMTAB
    declare!(MS,[real,[dimension,dimension],false]$FT,locals)$SYMTAB
    assign1 : FC := localAssign(IFLAG@Symbol,(-1)@EXI)
    call : FC := call("F04ASF(MS,N,X,N,Y,W1,W2,IFLAG)")$FC
    assign2 : FC := localAssign(IFLAG::Symbol,-(IFLAG@Symbol::EXI))
    assign3 : FC := assign(MS,u)$FC
    code : List FC := [assign1,assign3,call,assign2,returns()]$List(FC)
    ([locals,code]$RSFC)::$
```

```
    coerce(c:List FortranCode):$ == coerce(c)$Rep

    coerce(r:RSFC):$ == coerce(r)$Rep

    coerce(c:FortranCode):$ == coerce(c)$Rep

    coerce(u:$):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP34.dotabb —

```
"ASP34" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP34"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"RADCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RADCAT"]
"ASP34" -> "FIELD"
"ASP34" -> "RADCAT"
```

———-

2.24 domain ASP35 Asp35

— Asp35.input —

```
)set break resume
)sys rm -f Asp35.output
)spool Asp35.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp35
--R
--R Asp35(name: Symbol)  is a domain constructor
--R Abbreviation for Asp35 is ASP35
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP35
--R
```

```
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct],[construct,QUOTEX],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp35.help —

```
=====================================================================
Asp35 examples
=====================================================================

See Also:
o )show Asp35
```

———-

2.24.1 Asp35 (ASP35)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP35 Asp35 —

```
)abbrev domain ASP35 Asp35
++ Author: Mike Dewar, Godfrey Nolan, Grant Keady
++ Date Created: Mar 1993
++ Date Last Updated: 22 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp35} produces Fortran for Type 35 ASPs, needed for NAG routines
++c05pbf, c05pcf, for example:
++
++\tab{5}SUBROUTINE FCN(N,X,FVEC,FJAC,LDFJAC,IFLAG)\br
++\tab{5}DOUBLE PRECISION X(N),FVEC(N),FJAC(LDFJAC,N)\br
++\tab{5}INTEGER LDFJAC,N,IFLAG\br
++\tab{5}IF(IFLAG.EQ.1)THEN\br
++\tab{7}FVEC(1)=(-1.0D0*X(2))+X(1)\br
++\tab{7}FVEC(2)=(-1.0D0*X(3))+2.0D0*X(2)\br
++\tab{7}FVEC(3)=3.0D0*X(3)\br
++\tab{5}ELSEIF(IFLAG.EQ.2)THEN\br
++\tab{7}FJAC(1,1)=1.0D0\br
++\tab{7}FJAC(1,2)=-1.0D0\br
++\tab{7}FJAC(1,3)=0.0D0\br
++\tab{7}FJAC(2,1)=0.0D0\br
++\tab{7}FJAC(2,2)=2.0D0\br
++\tab{7}FJAC(2,3)=-1.0D0\br
++\tab{7}FJAC(3,1)=0.0D0\br
++\tab{7}FJAC(3,2)=0.0D0\br
++\tab{7}FJAC(3,3)=3.0D0\br
++\tab{5}ENDIF\br
++\tab{5}END
```

```
Asp35(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  UFST   ==> Union(fst:FST,void:"void")
  SYMTAB ==> SymbolTable
  FC     ==> FortranCode
  PI     ==> PositiveInteger
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  MAT    ==> Matrix
  VF2    ==> VectorFunctions2
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression([],['X],MFLOAT)
  MF2    ==> MatrixCategoryFunctions2(FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR,
                  EXPR MFLOAT,VEC EXPR MFLOAT,VEC EXPR MFLOAT,MAT EXPR MFLOAT)
  SWU    ==> Union(I:Expression Integer,F:Expression Float,
                 CF:Expression Complex Float,switch:Switch)

  Exports ==> FortranVectorFunctionCategory with
    coerce : VEC FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : UFST := ["real"::FST]$UFST
    syms : SYMTAB := empty()$SYMTAB
    declare!(N,fortranInteger(),syms)$SYMTAB
    xType : FT := construct(real,[N],false)$FT
    declare!(X,xType,syms)$SYMTAB
    declare!(FVEC,xType,syms)$SYMTAB
    declare!(LDFJAC,fortranInteger(),syms)$SYMTAB
    jType : FT := construct(real,[LDFJAC,N],false)$FT
    declare!(FJAC,jType,syms)$SYMTAB
    declare!(IFLAG,fortranInteger(),syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$UFST,[N,X,FVEC,FJAC,LDFJAC,IFLAG],syms)

    coerce(u:$):OutputForm == coerce(u)$Rep

    makeXList(n:Integer):List(Symbol) ==
      x:Symbol := X::Symbol
      [subscript(x,[j::OutputForm])$Symbol for j in 1..n]
```

```
fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

localAssign1(s:Symbol,j:MAT FEXPR):FC ==
  j' : MAT EXPR MFLOAT := map(fexpr2expr,j)$MF2
  assign(s,j')$FC

localAssign2(s:Symbol,j:VEC FEXPR):FC ==
  j' : VEC EXPR MFLOAT := map(fexpr2expr,j)$VF2(FEXPR,EXPR MFLOAT)
  assign(s,j')$FC

coerce(u:VEC FEXPR):$ ==
  n:Integer := maxIndex(u)
  p:List(Symbol) := makeXList(n)
  jac: MAT FEXPR := jacobian(u,p)$MultiVariableCalculusFunctions(_
                                    Symbol,FEXPR,VEC FEXPR,List(Symbol))
  assf:FC := localAssign2(FVEC,u)
  assj:FC := localAssign1(FJAC,jac)
  iflag:SWU := [IFLAG@Symbol::EXPR(INT)]$SWU
  sw1:Switch := EQ(iflag,[1::EXPR(INT)]$SWU)
  sw2:Switch := EQ(iflag,[2::EXPR(INT)]$SWU)
  cond(sw1,assf,cond(sw2,assj)$FC)$FC::$

coerce(c:List FC):$ == coerce(c)$Rep

coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FC):$ == coerce(c)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
  p => restorePrecision()$NAGLinkSupportPackage

retract(u:VEC FRAC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC FRAC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$
```

```
    retract(u:VEC EXPR INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
      v::$

    retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC EXPR FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$
```

———-

— ASP35.dotabb —

```
"ASP35" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP35"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP35" -> "FS"
```

———-

2.25 domain ASP4 Asp4

— **Asp4.input** —

```
)set break resume
)sys rm -f Asp4.output
)spool Asp4.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp4
--R
--R Asp4(name: Symbol)  is a domain constructor
--R Abbreviation for Asp4 is ASP4
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP4
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R retract : Polynomial(Float) -> %      retract : Expression(Float) -> %
--R coerce : FortranExpression([construct],[construct,QUOTEX],MachineFloat) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Fraction(Polynomial(Integer)) -> %
--R retract : Fraction(Polynomial(Float)) -> %
--R retract : Polynomial(Integer) -> %
--R retract : Expression(Integer) -> %
--R retractIfCan : Fraction(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Fraction(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed")
--R retractIfCan : Polynomial(Float) -> Union(%,"failed")
--R retractIfCan : Expression(Integer) -> Union(%,"failed")
--R retractIfCan : Expression(Float) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```


———-

— **Asp4.help** —

```
=====================================================================
Asp4 examples
=====================================================================
```

```
See Also:
o )show Asp4
```

2.25.1 Asp4 (ASP4)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP4 Asp4 —

```
)abbrev domain ASP4 Asp4
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp4} produces Fortran for Type 4 ASPs, which take an expression
++in X(1) .. X(NDIM) and produce a real function of the form:
++
++\tab{5}DOUBLE PRECISION FUNCTION FUNCTN(NDIM,X)\br
++\tab{5}DOUBLE PRECISION X(NDIM)\br
++\tab{5}INTEGER NDIM\br
++\tab{5}FUNCTN=(4.0D0*X(1)*X(3)**2*DEXP(2.0D0*X(1)*X(3)))/(X(4)**2+(2.0D0*\br
++\tab{4}&X(2)+2.0D0)*X(4)+X(2)**2+2.0D0*X(2)+1.0D0)\br
++\tab{5}RETURN\br
++\tab{5}END

Asp4(name): Exports == Implementation where
  name : Symbol
```

```
FEXPR  ==> FortranExpression([],['X],MachineFloat)
FST    ==> FortranScalarType
FT     ==> FortranType
SYMTAB ==> SymbolTable
RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
FSTU   ==> Union(fst:FST,void:"void")
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float

Exports ==> FortranFunctionCategory with
  coerce : FEXPR -> $
    ++coerce(f) takes an object from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns it into an ASP.

Implementation ==> add

  real : FSTU := ["real"::FST]$FSTU
  syms : SYMTAB := empty()$SYMTAB
  declare!(NDIM,fortranInteger(),syms)$SYMTAB
  xType : FT := construct(real,[NDIM],false)$FT
  declare!(X,xType,syms)$SYMTAB
  Rep := FortranProgram(name,real,[NDIM,X],syms)

  retract(u:FRAC POLY INT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:FRAC POLY INT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
    foo := retractIfCan(u)$FEXPR
    foo case "failed" => "failed"
    foo::FEXPR::$

  retract(u:FRAC POLY FLOAT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:FRAC POLY FLOAT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
    foo := retractIfCan(u)$FEXPR
    foo case "failed" => "failed"
    foo::FEXPR::$

  retract(u:EXPR FLOAT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:EXPR FLOAT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
    foo := retractIfCan(u)$FEXPR
    foo case "failed" => "failed"
    foo::FEXPR::$

  retract(u:EXPR INT):$ == (retract(u)@FEXPR)::$
  retractIfCan(u:EXPR INT):Union($,"failed") ==
    foo : Union(FEXPR,"failed")
```

```
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      foo::FEXPR::$

    retract(u:POLY FLOAT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:POLY FLOAT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      foo::FEXPR::$

    retract(u:POLY INT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:POLY INT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      foo::FEXPR::$

    coerce(u:FEXPR):$ ==
      coerce((u::Expression(MachineFloat))$FEXPR)$Rep

    coerce(c:List FortranCode):$ == coerce(c)$Rep

    coerce(r:RSFC):$ == coerce(r)$Rep

    coerce(c:FortranCode):$ == coerce(c)$Rep

    coerce(u:$):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP4.dotabb —

```
"ASP4" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP4"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP4" -> "PFECAT"
```

———-

2.26 domain ASP41 Asp41

— Asp41.input —

```
)set break resume
)sys rm -f Asp41.output
)spool Asp41.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp41
--R
--R Asp41(nameOne: Symbol,nameTwo: Symbol,nameThree: Symbol)  is a domain constructor
--R Abbreviation for Asp41 is ASP41
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP41
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEX,QUOTEEPS],[construct,QUOTEY],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp41.help —

```
=====================================================================
Asp41 examples
```

```
================================================================

See Also:
o )show Asp41
```

2.26.1 Asp41 (ASP41)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP41 Asp41 —

```
)abbrev domain ASP41 Asp41
++ Author: Mike Dewar, Godfrey Nolan
++ Date Created:
++ Date Last Updated: 29 March 1994
++                    6 October 1994
++ Related Constructors: FortranFunctionCategory, FortranProgramCategory.
++ Description:
++\spadtype{Asp41} produces Fortran for Type 41 ASPs, needed for NAG
++routines d02raf and d02saf in particular.  These ASPs are in fact
++three Fortran routines which return a vector of functions, and their
++derivatives wrt Y(i) and also a continuation parameter EPS, for example:
++
++\tab{5}SUBROUTINE FCN(X,EPS,Y,F,N)\br
++\tab{5}DOUBLE PRECISION EPS,F(N),X,Y(N)\br
++\tab{5}INTEGER N\br
++\tab{5}F(1)=Y(2)\br
++\tab{5}F(2)=Y(3)\br
++\tab{5}F(3)=(-1.0D0*Y(1)*Y(3))+2.0D0*EPS*Y(2)**2+(-2.0D0*EPS)\br
++\tab{5}RETURN\br
++\tab{5}END\br
```

```
++\tab{5}SUBROUTINE JACOBF(X,EPS,Y,F,N)\br
++\tab{5}DOUBLE PRECISION EPS,F(N,N),X,Y(N)\br
++\tab{5}INTEGER N\br
++\tab{5}F(1,1)=0.0D0\br
++\tab{5}F(1,2)=1.0D0\br
++\tab{5}F(1,3)=0.0D0\br
++\tab{5}F(2,1)=0.0D0\br
++\tab{5}F(2,2)=0.0D0\br
++\tab{5}F(2,3)=1.0D0\br
++\tab{5}F(3,1)=-1.0D0*Y(3)\br
++\tab{5}F(3,2)=4.0D0*EPS*Y(2)\br
++\tab{5}F(3,3)=-1.0D0*Y(1)\br
++\tab{5}RETURN\br
++\tab{5}END\br
++\tab{5}SUBROUTINE JACEPS(X,EPS,Y,F,N)\br
++\tab{5}DOUBLE PRECISION EPS,F(N),X,Y(N)\br
++\tab{5}INTEGER N\br
++\tab{5}F(1)=0.0D0\br
++\tab{5}F(2)=0.0D0\br
++\tab{5}F(3)=2.0D0*Y(2)**2-2.0D0\br
++\tab{5}RETURN\br
++\tab{5}END

Asp41(nameOne,nameTwo,nameThree): Exports == Implementation where
  nameOne : Symbol
  nameTwo : Symbol
  nameThree : Symbol

  D      ==> differentiate
  FST    ==> FortranScalarType
  UFST   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  VF2    ==> VectorFunctions2
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression(['X,'EPS],['Y],MFLOAT)
  S      ==> Symbol
  MF2    ==> MatrixCategoryFunctions2(FEXPR,VEC FEXPR,VEC FEXPR,Matrix FEXPR,
                 EXPR MFLOAT,VEC EXPR MFLOAT,VEC EXPR MFLOAT,Matrix EXPR MFLOAT)

  Exports ==> FortranVectorFunctionCategory with
    coerce : VEC FEXPR -> $
```

```
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add
  real : UFST := ["real"::FST]$UFST

  symOne : SYMTAB := empty()$SYMTAB
  declare!(N,fortranInteger(),symOne)$SYMTAB
  declare!(X,fortranReal(),symOne)$SYMTAB
  declare!(EPS,fortranReal(),symOne)$SYMTAB
  yType : FT := construct(real,[N],false)$FT
  declare!(Y,yType,symOne)$SYMTAB
  declare!(F,yType,symOne)$SYMTAB

  symTwo : SYMTAB := empty()$SYMTAB
  declare!(N,fortranInteger(),symTwo)$SYMTAB
  declare!(X,fortranReal(),symTwo)$SYMTAB
  declare!(EPS,fortranReal(),symTwo)$SYMTAB
  declare!(Y,yType,symTwo)$SYMTAB
  fType : FT := construct(real,[N,N],false)$FT
  declare!(F,fType,symTwo)$SYMTAB

  symThree : SYMTAB := empty()$SYMTAB
  declare!(N,fortranInteger(),symThree)$SYMTAB
  declare!(X,fortranReal(),symThree)$SYMTAB
  declare!(EPS,fortranReal(),symThree)$SYMTAB
  declare!(Y,yType,symThree)$SYMTAB
  declare!(F,yType,symThree)$SYMTAB

  R1:=FortranProgram(nameOne,["void"]$UFST,[X,EPS,Y,F,N],symOne)
  R2:=FortranProgram(nameTwo,["void"]$UFST,[X,EPS,Y,F,N],symTwo)
  R3:=FortranProgram(nameThree,["void"]$UFST,[X,EPS,Y,F,N],symThree)
  Rep := Record(f:R1,fJacob:R2,eJacob:R3)
  Fsym:Symbol:=coerce "F"

  fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

  localAssign1(s:S,j:Matrix FEXPR):FC ==
    j' : Matrix EXPR MFLOAT := map(fexpr2expr,j)$MF2
    assign(s,j')$FC

  localAssign2(s:S,j:VEC FEXPR):FC ==
    j' : VEC EXPR MFLOAT := map(fexpr2expr,j)$VF2(FEXPR,EXPR MFLOAT)
    assign(s,j')$FC

  makeCodeOne(u:VEC FEXPR):FortranCode ==
    -- simple assign
    localAssign2(Fsym,u)

  makeCodeThree(u:VEC FEXPR):FortranCode ==
```

```
    -- compute jacobian wrt to eps
    jacEps:VEC FEXPR := [D(v,EPS) for v in entries(u)]$VEC(FEXPR)
    makeCodeOne(jacEps)

  makeYList(n:Integer):List(Symbol) ==
    j:Integer
    y:Symbol := Y::Symbol
    p:List(Symbol) := []
    [subscript(y,[j::OutputForm])$Symbol for j in 1..n]

  makeCodeTwo(u:VEC FEXPR):FortranCode ==
    -- compute jacobian wrt to f
    n:Integer := maxIndex(u)$VEC(FEXPR)
    p:List(Symbol) := makeYList(n)
    jac:Matrix(FEXPR) := _
    jacobian(u,p)$MultiVariableCalculusFunctions(S,FEXPR,VEC FEXPR,List(S))
    localAssign1(Fsym,jac)

  coerce(u:VEC FEXPR):$ ==
    aF:FortranCode := makeCodeOne(u)
    bF:FortranCode := makeCodeTwo(u)
    cF:FortranCode := makeCodeThree(u)
    -- add returns() to complete subroutines
    aLF:List(FortranCode) := [aF,returns()$FortranCode]$List(FortranCode)
    bLF:List(FortranCode) := [bF,returns()$FortranCode]$List(FortranCode)
    cLF:List(FortranCode) := [cF,returns()$FortranCode]$List(FortranCode)
    [coerce(aLF)$R1,coerce(bLF)$R2,coerce(cLF)$R3]

  coerce(u:$):OutputForm ==
    bracket commaSeparate
      [nameOne::OutputForm,nameTwo::OutputForm,nameThree::OutputForm]

  outputAsFortran(u:$):Void ==
    p := checkPrecision()$NAGLinkSupportPackage
    outputAsFortran elt(u,f)$Rep
    outputAsFortran elt(u,fJacob)$Rep
    outputAsFortran elt(u,eJacob)$Rep
    p => restorePrecision()$NAGLinkSupportPackage

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
```

```
    v::$

  retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$
```

———-

— ASP41.dotabb —

```
"ASP41" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP41"]
```

```
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP41" -> "FS"
```

———-

2.27 domain ASP42 Asp42

— **Asp42.input** —

```
)set break resume
)sys rm -f Asp42.output
)spool Asp42.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp42
--R
--R Asp42(nameOne: Symbol,nameTwo: Symbol,nameThree: Symbol)  is a domain constructor
--R Abbreviation for Asp42 is ASP42
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP42
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEEPS],[construct,QUOTEYA,QUOTEYB],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp42.help** —

```
=====================================================================
Asp42 examples
=====================================================================

See Also:
o )show Asp42
```

———-

2.27.1 Asp42 (ASP42)



Exports:
coerce outputAsFortran retract retractIfCan

— **domain ASP42 Asp42** —

```
)abbrev domain ASP42 Asp42
++ Author: Mike Dewar, Godfrey Nolan
++ Date Created:
++ Date Last Updated: 29 March 1994
++                    6 October 1994
++ Related Constructors: FortranFunctionCategory, FortranProgramCategory.
++ Description:
++\spadtype{Asp42} produces Fortran for Type 42 ASPs, needed for NAG
++routines d02raf and d02saf
++in particular.  These ASPs are in fact
++three Fortran routines which return a vector of functions, and their
++derivatives wrt Y(i) and also a continuation parameter EPS, for example:
++
++\tab{5}SUBROUTINE G(EPS,YA,YB,BC,N)\br
```

```
++\tab{5}DOUBLE PRECISION EPS,YA(N),YB(N),BC(N)\br
++\tab{5}INTEGER N\br
++\tab{5}BC(1)=YA(1)\br
++\tab{5}BC(2)=YA(2)\br
++\tab{5}BC(3)=YB(2)-1.0D0\br
++\tab{5}RETURN\br
++\tab{5}END\br
++\tab{5}SUBROUTINE JACOBG(EPS,YA,YB,AJ,BJ,N)\br
++\tab{5}DOUBLE PRECISION EPS,YA(N),AJ(N,N),BJ(N,N),YB(N)\br
++\tab{5}INTEGER N\br
++\tab{5}AJ(1,1)=1.0D0\br
++\tab{5}AJ(1,2)=0.0D0\br
++\tab{5}AJ(1,3)=0.0D0\br
++\tab{5}AJ(2,1)=0.0D0\br
++\tab{5}AJ(2,2)=1.0D0\br
++\tab{5}AJ(2,3)=0.0D0\br
++\tab{5}AJ(3,1)=0.0D0\br
++\tab{5}AJ(3,2)=0.0D0\br
++\tab{5}AJ(3,3)=0.0D0\br
++\tab{5}BJ(1,1)=0.0D0\br
++\tab{5}BJ(1,2)=0.0D0\br
++\tab{5}BJ(1,3)=0.0D0\br
++\tab{5}BJ(2,1)=0.0D0\br
++\tab{5}BJ(2,2)=0.0D0\br
++\tab{5}BJ(2,3)=0.0D0\br
++\tab{5}BJ(3,1)=0.0D0\br
++\tab{5}BJ(3,2)=1.0D0\br
++\tab{5}BJ(3,3)=0.0D0\br
++\tab{5}RETURN\br
++\tab{5}END\br
++\tab{5}SUBROUTINE JACGEP(EPS,YA,YB,BCEP,N)\br
++\tab{5}DOUBLE PRECISION EPS,YA(N),YB(N),BCEP(N)\br
++\tab{5}INTEGER N\br
++\tab{5}BCEP(1)=0.0D0\br
++\tab{5}BCEP(2)=0.0D0\br
++\tab{5}BCEP(3)=0.0D0\br
++\tab{5}RETURN\br
++\tab{5}END

Asp42(nameOne,nameTwo,nameThree): Exports == Implementation where
  nameOne : Symbol
  nameTwo : Symbol
  nameThree : Symbol

  D      ==> differentiate
  FST    ==> FortranScalarType
  FT     ==> FortranType
  FP     ==> FortranProgram
  FC     ==> FortranCode
  PI     ==> PositiveInteger
```

```
NNI    ==> NonNegativeInteger
SYMTAB ==> SymbolTable
RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
UFST   ==> Union(fst:FST,void:"void")
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float
VEC    ==> Vector
VF2    ==> VectorFunctions2
MFLOAT ==> MachineFloat
FEXPR  ==> FortranExpression(['EPS],['YA,'YB],MFLOAT)
S      ==> Symbol
MF2    ==> MatrixCategoryFunctions2(FEXPR,VEC FEXPR,VEC FEXPR,Matrix FEXPR,
               EXPR MFLOAT,VEC EXPR MFLOAT,VEC EXPR MFLOAT,Matrix EXPR MFLOAT)

Exports ==> FortranVectorFunctionCategory with
  coerce : VEC FEXPR -> $
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add
  real : UFST := ["real"::FST]$UFST

  symOne : SYMTAB := empty()$SYMTAB
  declare!(EPS,fortranReal(),symOne)$SYMTAB
  declare!(N,fortranInteger(),symOne)$SYMTAB
  yType : FT := construct(real,[N],false)$FT
  declare!(YA,yType,symOne)$SYMTAB
  declare!(YB,yType,symOne)$SYMTAB
  declare!(BC,yType,symOne)$SYMTAB

  symTwo : SYMTAB := empty()$SYMTAB
  declare!(EPS,fortranReal(),symTwo)$SYMTAB
  declare!(N,fortranInteger(),symTwo)$SYMTAB
  declare!(YA,yType,symTwo)$SYMTAB
  declare!(YB,yType,symTwo)$SYMTAB
  ajType : FT := construct(real,[N,N],false)$FT
  declare!(AJ,ajType,symTwo)$SYMTAB
  declare!(BJ,ajType,symTwo)$SYMTAB

  symThree : SYMTAB := empty()$SYMTAB
  declare!(EPS,fortranReal(),symThree)$SYMTAB
  declare!(N,fortranInteger(),symThree)$SYMTAB
  declare!(YA,yType,symThree)$SYMTAB
  declare!(YB,yType,symThree)$SYMTAB
  declare!(BCEP,yType,symThree)$SYMTAB

  rt := ["void"]$UFST
```

```
R1:=FortranProgram(nameOne,rt,[EPS,YA,YB,BC,N],symOne)
R2:=FortranProgram(nameTwo,rt,[EPS,YA,YB,AJ,BJ,N],symTwo)
R3:=FortranProgram(nameThree,rt,[EPS,YA,YB,BCEP,N],symThree)
Rep := Record(g:R1,gJacob:R2,geJacob:R3)
BCsym:Symbol:=coerce "BC"
AJsym:Symbol:=coerce "AJ"
BJsym:Symbol:=coerce "BJ"
BCEPsym:Symbol:=coerce "BCEP"

makeList(n:Integer,s:Symbol):List(Symbol) ==
  j:Integer
  p:List(Symbol) := []
  for j in 1 .. n repeat p:= cons(subscript(s,[j::OutputForm])$Symbol,p)
  reverse(p)

fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

localAssign1(s:S,j:Matrix FEXPR):FC ==
  j' : Matrix EXPR MFLOAT := map(fexpr2expr,j)$MF2
  assign(s,j')$FC

localAssign2(s:S,j:VEC FEXPR):FC ==
  j' : VEC EXPR MFLOAT := map(fexpr2expr,j)$VF2(FEXPR,EXPR MFLOAT)
  assign(s,j')$FC

makeCodeOne(u:VEC FEXPR):FortranCode ==
  -- simple assign
  localAssign2(BCsym,u)

makeCodeTwo(u:VEC FEXPR):List(FortranCode) ==
  -- compute jacobian wrt to ya
  n:Integer := maxIndex(u)
  p:List(Symbol) := makeList(n,YA::Symbol)
  jacYA:Matrix(FEXPR) := _
    jacobian(u,p)$MultiVariableCalculusFunctions(S,FEXPR,VEC FEXPR,List(S))
  -- compute jacobian wrt to yb
  p:List(Symbol) := makeList(n,YB::Symbol)
  jacYB: Matrix(FEXPR) := _
    jacobian(u,p)$MultiVariableCalculusFunctions(S,FEXPR,VEC FEXPR,List(S))
  -- assign jacobians to AJ & BJ
  [localAssign1(AJsym,jacYA),localAssign1(BJsym,jacYB),returns()$FC]$List(FC)

makeCodeThree(u:VEC FEXPR):FortranCode ==
  -- compute jacobian wrt to eps
  jacEps:VEC FEXPR := [D(v,EPS) for v in entries u]$VEC(FEXPR)
  localAssign2(BCEPsym,jacEps)

coerce(u:VEC FEXPR):$ ==
  aF:FortranCode := makeCodeOne(u)
  bF:List(FortranCode) := makeCodeTwo(u)
```

```
    cF:FortranCode := makeCodeThree(u)
    -- add returns() to complete subroutines
    aLF:List(FortranCode) := [aF,returns()$FC]$List(FortranCode)
    cLF:List(FortranCode) := [cF,returns()$FC]$List(FortranCode)
    [coerce(aLF)$R1,coerce(bF)$R2,coerce(cLF)$R3]

  coerce(u:$) : OutputForm ==
    bracket commaSeparate
      [nameOne::OutputForm,nameTwo::OutputForm,nameThree::OutputForm]

  outputAsFortran(u:$):Void ==
    p := checkPrecision()$NAGLinkSupportPackage
    outputAsFortran elt(u,g)$Rep
    outputAsFortran elt(u,gJacob)$Rep
    outputAsFortran elt(u,geJacob)$Rep
    p => restorePrecision()$NAGLinkSupportPackage

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
```

```
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$
```

———-

— **ASP42.dotabb** —

```
"ASP42" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP42"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP42" -> "FS"
```

———-

2.28 domain ASP49 Asp49

— **Asp49.input** —

```
)set break resume
)sys rm -f Asp49.output
)spool Asp49.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp49
```

```
--R
--R Asp49(name: Symbol)  is a domain constructor
--R Abbreviation for Asp49 is ASP49
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP49
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R retract : Polynomial(Float) -> %      retract : Expression(Float) -> %
--R coerce : FortranExpression([construct],[construct,QUOTEX],MachineFloat) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Fraction(Polynomial(Integer)) -> %
--R retract : Fraction(Polynomial(Float)) -> %
--R retract : Polynomial(Integer) -> %
--R retract : Expression(Integer) -> %
--R retractIfCan : Fraction(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Fraction(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed")
--R retractIfCan : Polynomial(Float) -> Union(%,"failed")
--R retractIfCan : Expression(Integer) -> Union(%,"failed")
--R retractIfCan : Expression(Float) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp49.help —

```
=====================================================================
Asp49 examples
=====================================================================

See Also:
o )show Asp49
```

———-

2.28.1 Asp49 (ASP49)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP49 Asp49 —

```
)abbrev domain ASP49 Asp49
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 23 March 1994
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp49} produces Fortran for Type 49 ASPs, needed for NAG routines
++e04dgf, e04ucf, for example:
++
++\tab{5}SUBROUTINE OBJFUN(MODE,N,X,OBJF,OBJGRD,NSTATE,IUSER,USER)\br
++\tab{5}DOUBLE PRECISION X(N),OBJF,OBJGRD(N),USER(*)\br
++\tab{5}INTEGER N,IUSER(*),MODE,NSTATE\br
++\tab{5}OBJF=X(4)*X(9)+((-1.0D0*X(5))+X(3))*X(8)+((-1.0D0*X(3))+X(1))*X(7)\br
++\tab{4}&+(-1.0D0*X(2)*X(6))\br
++\tab{5}OBJGRD(1)=X(7)\br
++\tab{5}OBJGRD(2)=-1.0D0*X(6)\br
++\tab{5}OBJGRD(3)=X(8)+(-1.0D0*X(7))\br
++\tab{5}OBJGRD(4)=X(9)\br
++\tab{5}OBJGRD(5)=-1.0D0*X(8)\br
++\tab{5}OBJGRD(6)=-1.0D0*X(2)\br
++\tab{5}OBJGRD(7)=(-1.0D0*X(3))+X(1)\br
++\tab{5}OBJGRD(8)=(-1.0D0*X(5))+X(3)\br
++\tab{5}OBJGRD(9)=X(4)\br
++\tab{5}RETURN\br
++\tab{5}END

Asp49(name): Exports == Implementation where
  name : Symbol
```

```
FST    ==> FortranScalarType
UFST   ==> Union(fst:FST,void:"void")
FT     ==> FortranType
FC     ==> FortranCode
SYMTAB ==> SymbolTable
RSFC   ==> Record(localSymbols:SymbolTable,code:List(FC))
MFLOAT ==> MachineFloat
FEXPR  ==> FortranExpression([],['X],MFLOAT)
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float
VEC    ==> Vector
VF2    ==> VectorFunctions2
S      ==> Symbol

Exports ==> FortranFunctionCategory with
  coerce : FEXPR -> $
    ++coerce(f) takes an object from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns it into an ASP.

Implementation ==> add

  real : UFST := ["real"::FST]$UFST
  integer : UFST := ["integer"::FST]$UFST
  syms : SYMTAB := empty()$SYMTAB
  declare!(MODE,fortranInteger(),syms)$SYMTAB
  declare!(N,fortranInteger(),syms)$SYMTAB
  xType : FT := construct(real,[N::S],false)$FT
  declare!(X,xType,syms)$SYMTAB
  declare!(OBJF,fortranReal(),syms)$SYMTAB
  declare!(OBJGRD,xType,syms)$SYMTAB
  declare!(NSTATE,fortranInteger(),syms)$SYMTAB
  iuType : FT := construct(integer,["*"::S],false)$FT
  declare!(IUSER,iuType,syms)$SYMTAB
  uType : FT := construct(real,["*"::S],false)$FT
  declare!(USER,uType,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$UFST,
                        [MODE,N,X,OBJF,OBJGRD,NSTATE,IUSER,USER],syms)

  fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

  localAssign(s:S,j:VEC FEXPR):FC ==
    j' : VEC EXPR MFLOAT := map(fexpr2expr,j)$VF2(FEXPR,EXPR MFLOAT)
    assign(s,j')$FC

  coerce(u:FEXPR):$ ==
    vars:List(S) := variables(u)
    grd:VEC FEXPR := gradient(u,vars)$MultiVariableCalculusFunctions(_
```

```
                                        S,FEXPR,VEC FEXPR,List(S))
  code : List(FC) := [assign(OBJF@S,fexpr2expr u)$FC,_
                      localAssign(OBJGRD@S,grd),_
                      returns()$FC]
  code::$

coerce(u:$):OutputForm == coerce(u)$Rep

coerce(c:List FC):$ == coerce(c)$Rep

coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FC):$ == coerce(c)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
  p => restorePrecision()$NAGLinkSupportPackage

retract(u:FRAC POLY INT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:FRAC POLY INT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:FRAC POLY FLOAT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:FRAC POLY FLOAT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:EXPR FLOAT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:EXPR FLOAT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:EXPR INT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:EXPR INT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:POLY FLOAT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:POLY FLOAT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
```

```
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    retract(u:POLY INT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:POLY INT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$
```

———-

— ASP49.dotabb —

```
"ASP49" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP49"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP49" -> "ALIST"
```

———-

2.29 domain ASP50 Asp50

— Asp50.input —

```
)set break resume
)sys rm -f Asp50.output
)spool Asp50.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp50
--R
--R Asp50(name: Symbol)  is a domain constructor
--R Abbreviation for Asp50 is ASP50
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP50
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct],[construct,QUOTEXC],MachineFloat)) -> %
```

```
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp50.help** —

```
=====================================================================
Asp50 examples
=====================================================================

See Also:
o )show Asp50
```

———-

2.29.1 Asp50 (ASP50)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP50 Asp50 —

```
)abbrev domain ASP50 Asp50
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 23 March 1994
++                     6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp50} produces Fortran for Type 50 ASPs, needed for NAG routine
++e04fdf, for example:
++
++\tab{5}SUBROUTINE LSFUN1(M,N,XC,FVECC)\br
++\tab{5}DOUBLE PRECISION FVECC(M),XC(N)\br
++\tab{5}INTEGER I,M,N\br
++\tab{5}FVECC(1)=((XC(1)-2.4D0)*XC(3)+(15.0D0*XC(1)-36.0D0)*XC(2)+1.0D0)/(\br
++\tab{4}&XC(3)+15.0D0*XC(2))\br
++\tab{5}FVECC(2)=((XC(1)-2.8D0)*XC(3)+(7.0D0*XC(1)-19.6D0)*XC(2)+1.0D0)/(X\br
++\tab{4}&C(3)+7.0D0*XC(2))\br
++\tab{5}FVECC(3)=((XC(1)-3.2D0)*XC(3)+(4.333333333333333D0*XC(1)-13.866666\br
++\tab{4}&66666667D0)*XC(2)+1.0D0)/(XC(3)+4.333333333333333D0*XC(2))\br
++\tab{5}FVECC(4)=((XC(1)-3.5D0)*XC(3)+(3.0D0*XC(1)-10.5D0)*XC(2)+1.0D0)/(X\br
++\tab{4}&C(3)+3.0D0*XC(2))\br
++\tab{5}FVECC(5)=((XC(1)-3.9D0)*XC(3)+(2.2D0*XC(1)-8.579999999999998D0)*XC\br
++\tab{4}&(2)+1.0D0)/(XC(3)+2.2D0*XC(2))\br
++\tab{5}FVECC(6)=((XC(1)-4.199999999999999D0)*XC(3)+(1.666666666666667D0*X\br
++\tab{4}&C(1)-7.0D0)*XC(2)+1.0D0)/(XC(3)+1.666666666666667D0*XC(2))\br
++\tab{5}FVECC(7)=((XC(1)-4.5D0)*XC(3)+(1.285714285714286D0*XC(1)-5.7857142\br
++\tab{4}&85714286D0)*XC(2)+1.0D0)/(XC(3)+1.285714285714286D0*XC(2))\br
++\tab{5}FVECC(8)=((XC(1)-4.899999999999999D0)*XC(3)+(XC(1)-4.8999999999999\br
++\tab{4}&99D0)*XC(2)+1.0D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(9)=((XC(1)-4.699999999999999D0)*XC(3)+(XC(1)-4.6999999999999\br
++\tab{4}&99D0)*XC(2)+1.285714285714286D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(10)=((XC(1)-6.8D0)*XC(3)+(XC(1)-6.8D0)*XC(2)+1.6666666666666\br
++\tab{4}&67D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(11)=((XC(1)-8.299999999999999D0)*XC(3)+(XC(1)-8.299999999999\br
++\tab{4}&999D0)*XC(2)+2.2D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(12)=((XC(1)-10.6D0)*XC(3)+(XC(1)-10.6D0)*XC(2)+3.0D0)/(XC(3)\br
++\tab{4}&+XC(2))\br
++\tab{5}FVECC(13)=((XC(1)-1.34D0)*XC(3)+(XC(1)-1.34D0)*XC(2)+4.33333333333\br
++\tab{4}&3333D0)/(XC(3)+XC(2))\br
++\tab{5}FVECC(14)=((XC(1)-2.1D0)*XC(3)+(XC(1)-2.1D0)*XC(2)+7.0D0)/(XC(3)+X\br
++\tab{4}&C(2))\br
++\tab{5}FVECC(15)=((XC(1)-4.39D0)*XC(3)+(XC(1)-4.39D0)*XC(2)+15.0D0)/(XC(3\br
++\tab{4}&)+XC(2))\br
++\tab{5}END
```

```
Asp50(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  UFST   ==> Union(fst:FST,void:"void")
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  VF2    ==> VectorFunctions2
  FEXPR  ==> FortranExpression([],['XC],MFLOAT)
  MFLOAT ==> MachineFloat

  Exports ==> FortranVectorFunctionCategory with
    coerce : VEC FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : UFST := ["real"::FST]$UFST
    syms : SYMTAB := empty()$SYMTAB
    declare!(M,fortranInteger(),syms)$SYMTAB
    declare!(N,fortranInteger(),syms)$SYMTAB
    xcType : FT := construct(real,[N],false)$FT
    declare!(XC,xcType,syms)$SYMTAB
    fveccType : FT := construct(real,[M],false)$FT
    declare!(FVECC,fveccType,syms)$SYMTAB
    declare!(I,fortranInteger(),syms)$SYMTAB
    tType : FT := construct(real,[M,N],false)$FT
--    declare!(TC,tType,syms)$SYMTAB
--    declare!(Y,fveccType,syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$UFST, [M,N,XC,FVECC],syms)

    fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

    coerce(u:VEC FEXPR):$ ==
      u' : VEC EXPR MFLOAT := map(fexpr2expr,u)$VF2(FEXPR,EXPR MFLOAT)
      assign(FVECC,u')$FortranCode::$

    retract(u:VEC FRAC POLY INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
      v::$
```

```
retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC FRAC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$
```

```
    coerce(c:List FortranCode):$ == coerce(c)$Rep

    coerce(r:RSFC):$ == coerce(r)$Rep

    coerce(c:FortranCode):$ == coerce(c)$Rep

    coerce(u:$):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP50.dotabb —

```
"ASP50" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP50"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP50" -> "PFECAT"
```

———-

2.30 domain ASP55 Asp55

— Asp55.input —

```
)set break resume
)sys rm -f Asp55.output
)spool Asp55.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp55
--R
--R Asp55(name: Symbol)  is a domain constructor
--R Abbreviation for Asp55 is ASP55
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP55
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %            coerce : List(FortranCode) -> %
```

```
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct],[construct,QUOTEX],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp55.help —

```
=====================================================================
Asp55 examples
=====================================================================

See Also:
o )show Asp55
```

———-

2.30.1 Asp55 (ASP55)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP55 Asp55 —

```
)abbrev domain ASP55 Asp55
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: June 1993
++ Date Last Updated: 23 March 1994
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory
++ Description:
++\spadtype{Asp55} produces Fortran for Type 55 ASPs, needed for NAG routines
++e04dgf and e04ucf, for example:
++
++\tab{5}SUBROUTINE CONFUN(MODE,NCNLN,N,NROWJ,NEEDC,X,C,CJAC,NSTATE,IUSER\br
++\tab{4}&,USER)\br
++\tab{5}DOUBLE PRECISION C(NCNLN),X(N),CJAC(NROWJ,N),USER(*)\br
++\tab{5}INTEGER N,IUSER(*),NEEDC(NCNLN),NROWJ,MODE,NCNLN,NSTATE\br
++\tab{5}IF(NEEDC(1).GT.0)THEN\br
++\tab{7}C(1)=X(6)**2+X(1)**2\br
++\tab{7}CJAC(1,1)=2.0D0*X(1)\br
++\tab{7}CJAC(1,2)=0.0D0\br
++\tab{7}CJAC(1,3)=0.0D0\br
++\tab{7}CJAC(1,4)=0.0D0\br
++\tab{7}CJAC(1,5)=0.0D0\br
++\tab{7}CJAC(1,6)=2.0D0*X(6)\br
++\tab{5}ENDIF\br
++\tab{5}IF(NEEDC(2).GT.0)THEN\br
++\tab{7}C(2)=X(2)**2+(-2.0D0*X(1)*X(2))+X(1)**2\br
++\tab{7}CJAC(2,1)=(-2.0D0*X(2))+2.0D0*X(1)\br
++\tab{7}CJAC(2,2)=2.0D0*X(2)+(-2.0D0*X(1))\br
++\tab{7}CJAC(2,3)=0.0D0\br
++\tab{7}CJAC(2,4)=0.0D0\br
++\tab{7}CJAC(2,5)=0.0D0\br
++\tab{7}CJAC(2,6)=0.0D0\br
++\tab{5}ENDIF\br
++\tab{5}IF(NEEDC(3).GT.0)THEN\br
++\tab{7}C(3)=X(3)**2+(-2.0D0*X(1)*X(3))+X(2)**2+X(1)**2\br
++\tab{7}CJAC(3,1)=(-2.0D0*X(3))+2.0D0*X(1)\br
++\tab{7}CJAC(3,2)=2.0D0*X(2)\br
++\tab{7}CJAC(3,3)=2.0D0*X(3)+(-2.0D0*X(1))\br
++\tab{7}CJAC(3,4)=0.0D0\br
++\tab{7}CJAC(3,5)=0.0D0\br
++\tab{7}CJAC(3,6)=0.0D0\br
++\tab{5}ENDIF\br
++\tab{5}RETURN\br
++\tab{5}END
```

```
Asp55(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  FSTU   ==> Union(fst:FST,void:"void")
  SYMTAB ==> SymbolTable
  FC     ==> FortranCode
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  S      ==> Symbol
  FLOAT  ==> Float
  VEC    ==> Vector
  VF2    ==> VectorFunctions2
  MAT    ==> Matrix
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression([],['X],MFLOAT)
  MF2    ==> MatrixCategoryFunctions2(FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR,
                  EXPR MFLOAT,VEC EXPR MFLOAT,VEC EXPR MFLOAT,MAT EXPR MFLOAT)
  SWU    ==> Union(I:Expression Integer,F:Expression Float,
                 CF:Expression Complex Float,switch:Switch)

  Exports ==> FortranVectorFunctionCategory with
    coerce : VEC FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : FSTU := ["real"::FST]$FSTU
    integer : FSTU := ["integer"::FST]$FSTU
    syms : SYMTAB := empty()$SYMTAB
    declare!(MODE,fortranInteger(),syms)$SYMTAB
    declare!(NCNLN,fortranInteger(),syms)$SYMTAB
    declare!(N,fortranInteger(),syms)$SYMTAB
    declare!(NROWJ,fortranInteger(),syms)$SYMTAB
    needcType : FT := construct(integer,[NCNLN::Symbol],false)$FT
    declare!(NEEDC,needcType,syms)$SYMTAB
    xType : FT := construct(real,[N::Symbol],false)$FT
    declare!(X,xType,syms)$SYMTAB
    cType : FT := construct(real,[NCNLN::Symbol],false)$FT
    declare!(C,cType,syms)$SYMTAB
    cjacType : FT := construct(real,[NROWJ::Symbol,N::Symbol],false)$FT
    declare!(CJAC,cjacType,syms)$SYMTAB
    declare!(NSTATE,fortranInteger(),syms)$SYMTAB
    iuType : FT := construct(integer,["*"::Symbol],false)$FT
```

```
declare!(IUSER,iuType,syms)$SYMTAB
uType : FT := construct(real,["*"::Symbol],false)$FT
declare!(USER,uType,syms)$SYMTAB
Rep := FortranProgram(name,["void"]$FSTU,
                [MODE,NCNLN,N,NROWJ,NEEDC,X,C,CJAC,NSTATE,IUSER,USER],syms)

-- Take a symbol, pull of the script and turn it into an integer!!
o2int(u:S):Integer ==
  o : OutputForm := first elt(scripts(u)$S,sub)
  o pretend Integer

localAssign(s:Symbol,dim:List POLY INT,u:FEXPR):FC ==
  assign(s,dim,(u::EXPR MFLOAT)$FEXPR)$FC

makeCond(index:INT,fun:FEXPR,jac:VEC FEXPR):FC ==
  needc : EXPR INT := (subscript(NEEDC,[index::OutputForm])$S)::EXPR(INT)
  sw : Switch := GT([needc]$SWU,[0::EXPR(INT)]$SWU)$Switch
  ass : List FC := [localAssign(CJAC,[index::POLY INT,i::POLY INT],jac.i)_
                                                  for i in 1..maxIndex(jac)]
  cond(sw,block([localAssign(C,[index::POLY INT],fun),:ass])$FC)$FC

coerce(u:VEC FEXPR):$ ==
  ncnln:Integer := maxIndex(u)
  x:S := X::S
  pu:List(S) := []
  -- Work out which variables appear in the expressions
  for e in entries(u) repeat
    pu := setUnion(pu,variables(e)$FEXPR)
  scriptList : List Integer := map(o2int,pu)$ListFunctions2(S,Integer)
  -- This should be the maximum X_n which occurs (there may be others
  -- which don't):
  n:Integer := reduce(max,scriptList)$List(Integer)
  p:List(S) := []
  for j in 1..n repeat p:= cons(subscript(x,[j::OutputForm])$S,p)
  p:= reverse(p)
  jac:MAT FEXPR := _
     jacobian(u,p)$MultiVariableCalculusFunctions(S,FEXPR,VEC FEXPR,List(S))
  code : List FC := [makeCond(j,u.j,row(jac,j)) for j in 1..ncnln]
  [:code,returns()$FC]::$

coerce(c:List FC):$ == coerce(c)$Rep

coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FC):$ == coerce(c)$Rep

coerce(u:$):OutputForm == coerce(u)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
```

```
    outputAsFortran(u)$Rep
    p => restorePrecision()$NAGLinkSupportPackage

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
```

```
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$
```

———-

— **ASP55.dotabb** —

```
"ASP55" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP55"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP55" -> "ALIST"
```

———-

2.31 domain ASP6 Asp6

— **Asp6.input** —

```
)set break resume
)sys rm -f Asp6.output
)spool Asp6.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp6
--R
--R Asp6(name: Symbol)  is a domain constructor
--R Abbreviation for Asp6 is ASP6
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP6
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct],[construct,QUOTEX],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
```

```
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp6.help** —

```
========================================================================
Asp6 examples
========================================================================

See Also:
o )show Asp6
```

———-

2.31.1 Asp6 (ASP6)



Exports:
coerce outputAsFortran retract retractIfCan

— **domain ASP6 Asp6** —

```
)abbrev domain ASP6 Asp6
++ Author: Mike Dewar and Godfrey Nolan and Grant Keady
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp6} produces Fortran for Type 6 ASPs, needed for NAG routines
++ c05nbf, c05ncf. These represent vectors of functions of X(i) and look like:
++
++ \tab{5}SUBROUTINE FCN(N,X,FVEC,IFLAG)
++ \tab{5}DOUBLE PRECISION X(N),FVEC(N)
++ \tab{5}INTEGER N,IFLAG
++ \tab{5}FVEC(1)=(-2.0D0*X(2))+(-2.0D0*X(1)**2)+3.0D0*X(1)+1.0D0
++ \tab{5}FVEC(2)=(-2.0D0*X(3))+(-2.0D0*X(2)**2)+3.0D0*X(2)+(-1.0D0*X(1))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(3)=(-2.0D0*X(4))+(-2.0D0*X(3)**2)+3.0D0*X(3)+(-1.0D0*X(2))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(4)=(-2.0D0*X(5))+(-2.0D0*X(4)**2)+3.0D0*X(4)+(-1.0D0*X(3))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(5)=(-2.0D0*X(6))+(-2.0D0*X(5)**2)+3.0D0*X(5)+(-1.0D0*X(4))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(6)=(-2.0D0*X(7))+(-2.0D0*X(6)**2)+3.0D0*X(6)+(-1.0D0*X(5))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(7)=(-2.0D0*X(8))+(-2.0D0*X(7)**2)+3.0D0*X(7)+(-1.0D0*X(6))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(8)=(-2.0D0*X(9))+(-2.0D0*X(8)**2)+3.0D0*X(8)+(-1.0D0*X(7))+1.
++ \tab{4}&0D0
++ \tab{5}FVEC(9)=(-2.0D0*X(9)**2)+3.0D0*X(9)+(-1.0D0*X(8))+1.0D0
++ \tab{5}RETURN
++ \tab{5}END

Asp6(name): Exports == Implementation where
  name : Symbol

  FEXPR  ==> FortranExpression([],['X],MFLOAT)
  MFLOAT ==> MachineFloat
  FST    ==> FortranScalarType
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  UFST   ==> Union(fst:FST,void:"void")
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  VF2    ==> VectorFunctions2
```

```
Exports == FortranVectorFunctionCategory with
  coerce: Vector FEXPR -> %
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation == add

  real : UFST := ["real"::FST]$UFST
  syms : SYMTAB := empty()$SYMTAB
  declare!(N,fortranInteger()$FT,syms)$SYMTAB
  xType : FT := construct(real,[N],false)$FT
  declare!(X,xType,syms)$SYMTAB
  declare!(FVEC,xType,syms)$SYMTAB
  declare!(IFLAG,fortranInteger()$FT,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$Union(fst:FST,void:"void"),
                        [N,X,FVEC,IFLAG],syms)

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VectorFunctions2(FRAC POLY FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=_
      map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR INT):$ ==
    v : VEC FEXPR := map(retract,u)$VectorFunctions2(EXPR INT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VectorFunctions2(EXPR FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
```

```
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY INT):$ ==
      v : VEC FEXPR := map(retract,u)$VectorFunctions2(POLY INT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VectorFunctions2(POLY FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    fexpr2expr(u:FEXPR):EXPR MFLOAT ==
      (u::EXPR MFLOAT)$FEXPR

    coerce(u:VEC FEXPR):% ==
      v : VEC EXPR MFLOAT
      v := map(fexpr2expr,u)$VF2(FEXPR,EXPR MFLOAT)
      ([assign(FVEC,v)$FortranCode,returns()$FortranCode]$List(FortranCode))::$

    coerce(c:List FortranCode):% == coerce(c)$Rep

    coerce(r:RSFC):% == coerce(r)$Rep

    coerce(c:FortranCode):% == coerce(c)$Rep

    coerce(u:%):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP6.dotabb —

```
"ASP6" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP6"]
```

```
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP6" -> "PFECAT"
```

———-

2.32 domain ASP7 Asp7

— **Asp7.input** —

```
)set break resume
)sys rm -f Asp7.output
)spool Asp7.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp7
--R
--R Asp7(name: Symbol)  is a domain constructor
--R Abbreviation for Asp7 is ASP7
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP7
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEX],[construct,QUOTEY],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp7.help** —

```
=====================================================================
Asp7 examples
=====================================================================

See Also:
o )show Asp7
```

———-

2.32.1 Asp7 (ASP7)



Exports:
coerce outputAsFortran retract retractIfCan

— **domain ASP7 Asp7** —

```
)abbrev domain ASP7 Asp7
++ Author: Mike Dewar and Godfrey Nolan and Grant Keady
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp7} produces Fortran for Type 7 ASPs, needed for NAG routines
++ d02bbf, d02gaf. These represent a vector of functions of the scalar X and
++ the array Z, and look like:
++
++ \tab{5}SUBROUTINE FCN(X,Z,F)\br
++ \tab{5}DOUBLE PRECISION F(*),X,Z(*)\br
++ \tab{5}F(1)=DTAN(Z(3))\br
```

```
++ \tab{5}F(2)=((-0.03199999999999999D0*DCOS(Z(3))*DTAN(Z(3)))+(-0.02D0*Z(2)\br
++ \tab{4}&**2))/(Z(2)*DCOS(Z(3)))\br
++ \tab{5}F(3)=-0.03199999999999999D0/(X*Z(2)**2)\br
++ \tab{5}RETURN\br
++ \tab{5}END

Asp7(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression(['X],['Y],MFLOAT)
  UFST   ==> Union(fst:FST,void:"void")
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  VEC    ==> Vector
  VF2    ==> VectorFunctions2

  Exports ==> FortranVectorFunctionCategory with
    coerce : Vector FEXPR -> %
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : UFST := ["real"::FST]$UFST
    syms : SYMTAB := empty()$SYMTAB
    declare!(X,fortranReal(),syms)$SYMTAB
    yType : FT := construct(real,["*"::Symbol],false)$FT
    declare!(Y,yType,syms)$SYMTAB
    declare!(F,yType,syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$UFST,[X,Y,F],syms)

    retract(u:VEC FRAC POLY INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
      v::$

    retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC FRAC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
```

```
    v::$

  retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC EXPR FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
    v::$

  retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  fexpr2expr(u:FEXPR):EXPR MFLOAT ==
    (u::EXPR MFLOAT)$FEXPR

  coerce(u:Vector FEXPR ):% ==
    v : Vector EXPR MFLOAT
    v:=map(fexpr2expr,u)$VF2(FEXPR,EXPR MFLOAT)
    ([assign(F,v)$FortranCode,returns()$FortranCode]$List(FortranCode))::%
```

```
    coerce(c:List FortranCode):% == coerce(c)$Rep

    coerce(r:RSFC):% == coerce(r)$Rep

    coerce(c:FortranCode):% == coerce(c)$Rep

    coerce(u:%):OutputForm == coerce(u)$Rep

    outputAsFortran(u):Void ==
      p := checkPrecision()$NAGLinkSupportPackage
      outputAsFortran(u)$Rep
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— ASP7.dotabb —

```
"ASP7" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP7"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP7" -> "ALIST"
```

———-

2.33 domain ASP73 Asp73

— Asp73.input —

```
)set break resume
)sys rm -f Asp73.output
)spool Asp73.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp73
--R
--R Asp73(name: Symbol)  is a domain constructor
--R Abbreviation for Asp73 is ASP73
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP73
--R
--R------------------------------ Operations ------------------------------
```

```
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEX,QUOTEY],[construct],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp73.help —

```
=====================================================================
Asp73 examples
=====================================================================

See Also:
o )show Asp73
```

———-

2.33.1 Asp73 (ASP73)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP73 Asp73 —

```
)abbrev domain ASP73 Asp73
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 30 March 1994, 6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp73} produces Fortran for Type 73 ASPs, needed for NAG routine
++ d03eef, for example:
++
++ \tab{5}SUBROUTINE PDEF(X,Y,ALPHA,BETA,GAMMA,DELTA,EPSOLN,PHI,PSI)\br
++ \tab{5}DOUBLE PRECISION ALPHA,EPSOLN,PHI,X,Y,BETA,DELTA,GAMMA,PSI\br
++ \tab{5}ALPHA=DSIN(X)\br
++ \tab{5}BETA=Y\br
++ \tab{5}GAMMA=X*Y\br
++ \tab{5}DELTA=DCOS(X)*DSIN(Y)\br
++ \tab{5}EPSOLN=Y+X\br
++ \tab{5}PHI=X\br
++ \tab{5}PSI=Y\br
++ \tab{5}RETURN\br
++ \tab{5}END

Asp73(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FSTU   ==> Union(fst:FST,void:"void")
  FEXPR  ==> FortranExpression(['X,'Y],[],MachineFloat)
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
```

```
FRAC   ==> Fraction
POLY   ==> Polynomial
EXPR   ==> Expression
INT    ==> Integer
FLOAT  ==> Float
VEC    ==> Vector
VF2    ==> VectorFunctions2

Exports ==> FortranVectorFunctionCategory with
  coerce : VEC FEXPR -> $
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add

  syms : SYMTAB := empty()$SYMTAB
  declare!(X,fortranReal(),syms) $SYMTAB
  declare!(Y,fortranReal(),syms) $SYMTAB
  declare!(ALPHA,fortranReal(),syms)$SYMTAB
  declare!(BETA,fortranReal(),syms) $SYMTAB
  declare!(GAMMA,fortranReal(),syms) $SYMTAB
  declare!(DELTA,fortranReal(),syms) $SYMTAB
  declare!(EPSOLN,fortranReal(),syms) $SYMTAB
  declare!(PHI,fortranReal(),syms) $SYMTAB
  declare!(PSI,fortranReal(),syms) $SYMTAB
  Rep := FortranProgram(name,["void"]$FSTU,
                        [X,Y,ALPHA,BETA,GAMMA,DELTA,EPSOLN,PHI,PSI],syms)

  -- To help the poor compiler!
  localAssign(u:Symbol,v:FEXPR):FortranCode ==
    assign(u,(v::EXPR MachineFloat)$FEXPR)$FortranCode

  coerce(u:VEC FEXPR):$ ==
    maxIndex(u) ^= 7 => error "Vector is not of dimension 7"
    [localAssign(ALPHA@Symbol,elt(u,1)),_
     localAssign(BETA@Symbol,elt(u,2)),_
     localAssign(GAMMA@Symbol,elt(u,3)),_
     localAssign(DELTA@Symbol,elt(u,4)),_
     localAssign(EPSOLN@Symbol,elt(u,5)),_
     localAssign(PHI@Symbol,elt(u,6)),_
     localAssign(PSI@Symbol,elt(u,7)),_
     returns()$FortranCode]$List(FortranCode)::$

  coerce(c:FortranCode):$ == coerce(c)$Rep

  coerce(r:RSFC):$ == coerce(r)$Rep

  coerce(c:List FortranCode):$ == coerce(c)$Rep

  coerce(u:$):OutputForm == coerce(u)$Rep
```

```
outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
  p => restorePrecision()$NAGLinkSupportPackage

retract(u:VEC FRAC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC FRAC POLY FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC EXPR FLOAT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
  v::$

retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$

retract(u:VEC POLY INT):$ ==
  v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
  v::$

retractIfCan(u:VEC POLY INT):Union($,"failed") ==
  v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
  v case "failed" => "failed"
  (v::VEC FEXPR)::$
```

```
    retract(u:VEC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$
```

———-

— **ASP73.dotabb** —

```
"ASP73" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP73"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"ASP73" -> "PFECAT"
```

———-

2.34 domain ASP74 Asp74

— **Asp74.input** —

```
)set break resume
)sys rm -f Asp74.output
)spool Asp74.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp74
--R
--R Asp74(name: Symbol)  is a domain constructor
--R Abbreviation for Asp74 is ASP74
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP74
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Matrix(FortranExpression([construct,QUOTEX,QUOTEY],[construct],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
```

```
--R retract : Matrix(Fraction(Polynomial(Integer))) -> %
--R retract : Matrix(Fraction(Polynomial(Float))) -> %
--R retract : Matrix(Polynomial(Integer)) -> %
--R retract : Matrix(Polynomial(Float)) -> %
--R retract : Matrix(Expression(Integer)) -> %
--R retract : Matrix(Expression(Float)) -> %
--R retractIfCan : Matrix(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Matrix(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp74.help** —

```
=====================================================================
Asp74 examples
=====================================================================

See Also:
o )show Asp74
```

———-

2.34.1 Asp74 (ASP74)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP74 Asp74 —

```
)abbrev domain ASP74 Asp74
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Oct 1993
++ Date Last Updated: 30 March 1994
++                    6 October 1994
++ Related Constructors: FortranScalarFunctionCategory, FortranProgramCategory.
++ Description:
++ \spadtype{Asp74} produces Fortran for Type 74 ASPs, needed for NAG routine
++ d03eef, for example:
++
++ \tab{5} SUBROUTINE BNDY(X,Y,A,B,C,IBND)\br
++ \tab{5} DOUBLE PRECISION A,B,C,X,Y\br
++ \tab{5} INTEGER IBND\br
++ \tab{5} IF(IBND.EQ.0)THEN\br
++ \tab{7} A=0.0D0\br
++ \tab{7} B=1.0D0\br
++ \tab{7} C=-1.0D0*DSIN(X)\br
++ \tab{5} ELSEIF(IBND.EQ.1)THEN\br
++ \tab{7} A=1.0D0\br
++ \tab{7} B=0.0D0\br
++ \tab{7} C=DSIN(X)*DSIN(Y)\br
++ \tab{5} ELSEIF(IBND.EQ.2)THEN\br
++ \tab{7} A=1.0D0\br
++ \tab{7} B=0.0D0\br
++ \tab{7} C=DSIN(X)*DSIN(Y)\br
++ \tab{5} ELSEIF(IBND.EQ.3)THEN\br
++ \tab{7} A=0.0D0\br
++ \tab{7} B=1.0D0\br
++ \tab{7} C=-1.0D0*DSIN(Y)\br
++ \tab{5} ENDIF\br
++ \tab{5} END

Asp74(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FSTU   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  SYMTAB ==> SymbolTable
  FC     ==> FortranCode
  PI     ==> PositiveInteger
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
```

```
MFLOAT ==> MachineFloat
FEXPR  ==> FortranExpression(['X,'Y],[],MFLOAT)
U      ==> Union(I: Expression Integer,F: Expression Float,_
                 CF: Expression Complex Float,switch:Switch)
VEC    ==> Vector
MAT    ==> Matrix
M2     ==> MatrixCategoryFunctions2
MF2a   ==> M2(FRAC POLY INT,VEC FRAC POLY INT,VEC FRAC POLY INT,
               MAT FRAC POLY INT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
MF2b   ==> M2(FRAC POLY FLOAT,VEC FRAC POLY FLOAT,VEC FRAC POLY FLOAT,
               MAT FRAC POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
MF2c   ==> M2(POLY INT,VEC POLY INT,VEC POLY INT,MAT POLY INT,
               FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
MF2d   ==> M2(POLY FLOAT,VEC POLY FLOAT,VEC POLY FLOAT,
               MAT POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
MF2e   ==> M2(EXPR INT,VEC EXPR INT,VEC EXPR INT,MAT EXPR INT,
               FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
MF2f   ==> M2(EXPR FLOAT,VEC EXPR FLOAT,VEC EXPR FLOAT,
               MAT EXPR FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)

Exports ==> FortranMatrixFunctionCategory with
  coerce : MAT FEXPR -> $
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add

  syms : SYMTAB := empty()$SYMTAB
  declare!(X,fortranReal(),syms)$SYMTAB
  declare!(Y,fortranReal(),syms)$SYMTAB
  declare!(A,fortranReal(),syms)$SYMTAB
  declare!(B,fortranReal(),syms)$SYMTAB
  declare!(C,fortranReal(),syms)$SYMTAB
  declare!(IBND,fortranInteger(),syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$FSTU,[X,Y,A,B,C,IBND],syms)

  -- To help the poor compiler!
  localAssign(u:Symbol,v:FEXPR):FC == assign(u,(v::EXPR MFLOAT)$FEXPR)$FC

  coerce(u:MAT FEXPR):$ ==
    (nrows(u) ^= 4 or ncols(u) ^= 3) => error "Not a 4X3 matrix"
    flag:U := [IBND@Symbol::EXPR INT]$U
    pt0:U  := [0::EXPR INT]$U
    pt1:U  := [1::EXPR INT]$U
    pt2:U  := [2::EXPR INT]$U
    pt3:U  := [3::EXPR INT]$U
    sw1: Switch := EQ(flag,pt0)$Switch
    sw2: Switch := EQ(flag,pt1)$Switch
    sw3: Switch := EQ(flag,pt2)$Switch
    sw4: Switch := EQ(flag,pt3)$Switch
```

```
    a11 : FC := localAssign(A,u(1,1))
    a12 : FC := localAssign(B,u(1,2))
    a13 : FC := localAssign(C,u(1,3))
    a21 : FC := localAssign(A,u(2,1))
    a22 : FC := localAssign(B,u(2,2))
    a23 : FC := localAssign(C,u(2,3))
    a31 : FC := localAssign(A,u(3,1))
    a32 : FC := localAssign(B,u(3,2))
    a33 : FC := localAssign(C,u(3,3))
    a41 : FC := localAssign(A,u(4,1))
    a42 : FC := localAssign(B,u(4,2))
    a43 : FC := localAssign(C,u(4,3))
    c : FC := cond(sw1,block([a11,a12,a13])$FC,
                   cond(sw2,block([a21,a22,a23])$FC,
                        cond(sw3,block([a31,a32,a33])$FC,
                             cond(sw4,block([a41,a42,a43])$FC)$FC)$FC)$FC)$FC
    c::$

  coerce(u:$):OutputForm == coerce(u)$Rep

  coerce(c:FortranCode):$ == coerce(c)$Rep

  coerce(r:RSFC):$ == coerce(r)$Rep

  coerce(c:List FortranCode):$ == coerce(c)$Rep

  outputAsFortran(u):Void ==
    p := checkPrecision()$NAGLinkSupportPackage
    outputAsFortran(u)$Rep
    p => restorePrecision()$NAGLinkSupportPackage

  retract(u:MAT FRAC POLY INT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2a
    v::$

  retractIfCan(u:MAT FRAC POLY INT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2a
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT FRAC POLY FLOAT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2b
    v::$

  retractIfCan(u:MAT FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2b
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT EXPR INT):$ ==
```

```
    v : MAT FEXPR := map(retract,u)$MF2e
    v::$

  retractIfCan(u:MAT EXPR INT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2e
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT EXPR FLOAT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2f
    v::$

  retractIfCan(u:MAT EXPR FLOAT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2f
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT POLY INT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2c
    v::$

  retractIfCan(u:MAT POLY INT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2c
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT POLY FLOAT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2d
    v::$

  retractIfCan(u:MAT POLY FLOAT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2d
    v case "failed" => "failed"
    (v::MAT FEXPR)::$
```

— ASP74.dotabb —

```
"ASP74" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP74"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP74" -> "FS"
```

2.35 domain ASP77 Asp77

— Asp77.input —

```
)set break resume
)sys rm -f Asp77.output
)spool Asp77.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp77
--R
--R Asp77(name: Symbol)  is a domain constructor
--R Abbreviation for Asp77 is ASP77
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP77
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Matrix(FortranExpression([construct,QUOTEX],[construct],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Matrix(Fraction(Polynomial(Integer))) -> %
--R retract : Matrix(Fraction(Polynomial(Float))) -> %
--R retract : Matrix(Polynomial(Integer)) -> %
--R retract : Matrix(Polynomial(Float)) -> %
--R retract : Matrix(Expression(Integer)) -> %
--R retract : Matrix(Expression(Float)) -> %
--R retractIfCan : Matrix(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Matrix(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp77.help —

```
=====================================================================
Asp77 examples
```

```
================================================================

See Also:
o )show Asp77
```

2.35.1 Asp77 (ASP77)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP77 Asp77 —

```
)abbrev domain ASP77 Asp77
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 30 March 1994
++                    6 October 1994
++ Related Constructors: FortranMatrixFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp77} produces Fortran for Type 77 ASPs, needed for NAG routine
++ d02gbf, for example:
++
++ \tab{5}SUBROUTINE FCNF(X,F)\br
++ \tab{5}DOUBLE PRECISION X\br
++ \tab{5}DOUBLE PRECISION F(2,2)\br
++ \tab{5}F(1,1)=0.0D0\br
++ \tab{5}F(1,2)=1.0D0\br
++ \tab{5}F(2,1)=0.0D0\br
++ \tab{5}F(2,2)=-10.0D0\br
++ \tab{5}RETURN\br
++ \tab{5}END
```

```
Asp77(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FSTU   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FC))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression(['X],[],MFLOAT)
  VEC    ==> Vector
  MAT    ==> Matrix
  M2     ==> MatrixCategoryFunctions2
  MF2    ==> M2(FEXPR,VEC FEXPR,VEC FEXPR,Matrix FEXPR,EXPR MFLOAT,
                 VEC EXPR MFLOAT,VEC EXPR MFLOAT,Matrix EXPR MFLOAT)
  MF2a   ==> M2(FRAC POLY INT,VEC FRAC POLY INT,VEC FRAC POLY INT,
                 MAT FRAC POLY INT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2b   ==> M2(FRAC POLY FLOAT,VEC FRAC POLY FLOAT,VEC FRAC POLY FLOAT,
                 MAT FRAC POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2c   ==> M2(POLY INT,VEC POLY INT,VEC POLY INT,MAT POLY INT,
                 FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2d   ==> M2(POLY FLOAT,VEC POLY FLOAT,VEC POLY FLOAT,
                 MAT POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2e   ==> M2(EXPR INT,VEC EXPR INT,VEC EXPR INT,MAT EXPR INT,
                 FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2f   ==> M2(EXPR FLOAT,VEC EXPR FLOAT,VEC EXPR FLOAT,
                 MAT EXPR FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)


  Exports ==> FortranMatrixFunctionCategory with
    coerce : MAT FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add

    real : FSTU := ["real"::FST]$FSTU
    syms : SYMTAB := empty()$SYMTAB
    declare!(X,fortranReal(),syms)$SYMTAB
    Rep := FortranProgram(name,["void"]$FSTU,[X,F],syms)

    fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

    localAssign(s:Symbol,j:MAT FEXPR):FortranCode ==
```

```
    j' : MAT EXPR MFLOAT := map(fexpr2expr,j)$MF2
    assign(s,j')$FortranCode

  coerce(u:MAT FEXPR):$ ==
    dimension := nrows(u)::POLY(INT)
    locals : SYMTAB := empty()
    declare!(F,[real,[dimension,dimension]$List(POLY(INT)),false]$FT,locals)
    code : List FC := [localAssign(F,u),returns()$FC]
    ([locals,code]$RSFC)::$

  coerce(c:List FC):$ == coerce(c)$Rep

  coerce(r:RSFC):$ == coerce(r)$Rep

  coerce(c:FC):$ == coerce(c)$Rep

  coerce(u:$):OutputForm == coerce(u)$Rep

  outputAsFortran(u):Void ==
    p := checkPrecision()$NAGLinkSupportPackage
    outputAsFortran(u)$Rep
    p => restorePrecision()$NAGLinkSupportPackage

  retract(u:MAT FRAC POLY INT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2a
    v::$

  retractIfCan(u:MAT FRAC POLY INT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2a
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT FRAC POLY FLOAT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2b
    v::$

  retractIfCan(u:MAT FRAC POLY FLOAT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2b
    v case "failed" => "failed"
    (v::MAT FEXPR)::$

  retract(u:MAT EXPR INT):$ ==
    v : MAT FEXPR := map(retract,u)$MF2e
    v::$

  retractIfCan(u:MAT EXPR INT):Union($,"failed") ==
    v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2e
    v case "failed" => "failed"
    (v::MAT FEXPR)::$
```

```
    retract(u:MAT EXPR FLOAT):$ ==
      v : MAT FEXPR := map(retract,u)$MF2f
      v::$

    retractIfCan(u:MAT EXPR FLOAT):Union($,"failed") ==
      v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2f
      v case "failed" => "failed"
      (v::MAT FEXPR)::$

    retract(u:MAT POLY INT):$ ==
      v : MAT FEXPR := map(retract,u)$MF2c
      v::$

    retractIfCan(u:MAT POLY INT):Union($,"failed") ==
      v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2c
      v case "failed" => "failed"
      (v::MAT FEXPR)::$

    retract(u:MAT POLY FLOAT):$ ==
      v : MAT FEXPR := map(retract,u)$MF2d
      v::$

    retractIfCan(u:MAT POLY FLOAT):Union($,"failed") ==
      v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2d
      v case "failed" => "failed"
      (v::MAT FEXPR)::$
```

———-

— ASP77.dotabb —

```
"ASP77" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP77"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP77" -> "FS"
```

———-

2.36 domain ASP78 Asp78

— Asp78.input —

```
)set break resume
)sys rm -f Asp78.output
)spool Asp78.output
```

```
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp78
--R
--R Asp78(name: Symbol)  is a domain constructor
--R Abbreviation for Asp78 is ASP78
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP78
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Vector(FortranExpression([construct,QUOTEX],[construct],MachineFloat)) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Vector(Fraction(Polynomial(Integer))) -> %
--R retract : Vector(Fraction(Polynomial(Float))) -> %
--R retract : Vector(Polynomial(Integer)) -> %
--R retract : Vector(Polynomial(Float)) -> %
--R retract : Vector(Expression(Integer)) -> %
--R retract : Vector(Expression(Float)) -> %
--R retractIfCan : Vector(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Vector(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Vector(Expression(Float)) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Asp78.help —

```
=====================================================================
Asp78 examples
=====================================================================

See Also:
o )show Asp78
```

———-

2.36.1 Asp78 (ASP78)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP78 Asp78 —

```
)abbrev domain ASP78 Asp78
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 30 March 1994
++                    6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp78} produces Fortran for Type 78 ASPs, needed for NAG routine
++ d02gbf, for example:
++
++ \tab{5}SUBROUTINE FCNG(X,G)\br
++ \tab{5}DOUBLE PRECISION G(*),X\br
++ \tab{5}G(1)=0.0D0\br
++ \tab{5}G(2)=0.0D0\br
++ \tab{5}END

Asp78(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FSTU   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FC))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
```

```
VEC    ==> Vector
VF2    ==> VectorFunctions2
MFLOAT ==> MachineFloat
FEXPR  ==> FortranExpression(['X],[],MFLOAT)

Exports ==> FortranVectorFunctionCategory with
  coerce : VEC FEXPR -> $
    ++coerce(f) takes objects from the appropriate instantiation of
    ++\spadtype{FortranExpression} and turns them into an ASP.

Implementation ==> add

  real : FSTU := ["real"::FST]$FSTU
  syms : SYMTAB := empty()$SYMTAB
  declare!(X,fortranReal(),syms)$SYMTAB
  gType : FT := construct(real,["*"::Symbol],false)$FT
  declare!(G,gType,syms)$SYMTAB
  Rep := FortranProgram(name,["void"]$FSTU,[X,G],syms)

  fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

  coerce(u:VEC FEXPR):$ ==
    u' : VEC EXPR MFLOAT := map(fexpr2expr,u)$VF2(FEXPR,EXPR MFLOAT)
    (assign(G,u')$FC)::$

  coerce(u:$):OutputForm == coerce(u)$Rep

  outputAsFortran(u):Void ==
    p := checkPrecision()$NAGLinkSupportPackage
    outputAsFortran(u)$Rep
    p => restorePrecision()$NAGLinkSupportPackage

  coerce(c:List FC):$ == coerce(c)$Rep

  coerce(r:RSFC):$ == coerce(r)$Rep

  coerce(c:FC):$ == coerce(c)$Rep

  retract(u:VEC FRAC POLY INT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY INT,FEXPR)
    v::$

  retractIfCan(u:VEC FRAC POLY INT):Union($,"failed") ==
    v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY INT,FEXPR)
    v case "failed" => "failed"
    (v::VEC FEXPR)::$

  retract(u:VEC FRAC POLY FLOAT):$ ==
    v : VEC FEXPR := map(retract,u)$VF2(FRAC POLY FLOAT,FEXPR)
    v::$
```

```
    retractIfCan(u:VEC FRAC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(FRAC POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC EXPR INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(EXPR INT,FEXPR)
      v::$

    retractIfCan(u:VEC EXPR INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC EXPR FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(EXPR FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC EXPR FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(EXPR FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY INT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY INT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY INT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY INT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$

    retract(u:VEC POLY FLOAT):$ ==
      v : VEC FEXPR := map(retract,u)$VF2(POLY FLOAT,FEXPR)
      v::$

    retractIfCan(u:VEC POLY FLOAT):Union($,"failed") ==
      v:Union(VEC FEXPR,"failed"):=map(retractIfCan,u)$VF2(POLY FLOAT,FEXPR)
      v case "failed" => "failed"
      (v::VEC FEXPR)::$
```

———-

— **ASP78.dotabb** —

```
"ASP78" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP78"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
```

```
"ASP78" -> "ALIST"
```

———-

2.37 domain ASP8 Asp8

— **Asp8.input** —

```
)set break resume
)sys rm -f Asp8.output
)spool Asp8.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp8
--R
--R Asp8(name: Symbol)  is a domain constructor
--R Abbreviation for Asp8 is ASP8
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP8
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R coerce : Vector(MachineFloat) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Asp8.help** —

```
=====================================================================
Asp8 examples
=====================================================================

See Also:
o )show Asp8
```

———-

2.37.1 Asp8 (ASP8)



Exports:
coerce outputAsFortran

— domain ASP8 Asp8 —

```
)abbrev domain ASP8 Asp8
++ Author: Godfrey Nolan and Mike Dewar
++ Date Created: 11 February 1994
++ Date Last Updated: 18 March 1994
++                    31 May 1994 to use alternative interface. MCD
++                    30 June 1994 to handle the end condition correctly. MCD
++                     6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp8} produces Fortran for Type 8 ASPs, needed for NAG routine
++ d02bbf.  This ASP prints intermediate values of the computed solution of
++ an ODE and might look like:
++
++ \tab{5}SUBROUTINE OUTPUT(XSOL,Y,COUNT,M,N,RESULT,FORWRD)\br
++ \tab{5}DOUBLE PRECISION Y(N),RESULT(M,N),XSOL\br
++ \tab{5}INTEGER M,N,COUNT\br
++ \tab{5}LOGICAL FORWRD\br
++ \tab{5}DOUBLE PRECISION X02ALF,POINTS(8)\br
++ \tab{5}EXTERNAL X02ALF\br
++ \tab{5}INTEGER I\br
++ \tab{5}POINTS(1)=1.0D0\br
++ \tab{5}POINTS(2)=2.0D0\br
++ \tab{5}POINTS(3)=3.0D0\br
++ \tab{5}POINTS(4)=4.0D0\br
++ \tab{5}POINTS(5)=5.0D0\br
++ \tab{5}POINTS(6)=6.0D0\br
```

```
++ \tab{5}POINTS(7)=7.0D0\br
++ \tab{5}POINTS(8)=8.0D0\br
++ \tab{5}COUNT=COUNT+1\br
++ \tab{5}DO 25001 I=1,N\br
++ \tab{7} RESULT(COUNT,I)=Y(I)\br
++ 25001 CONTINUE\br
++ \tab{5}IF(COUNT.EQ.M)THEN\br
++ \tab{7}IF(FORWRD)THEN\br
++ \tab{9}XSOL=X02ALF()\br
++ \tab{7}ELSE\br
++ \tab{9}XSOL=-X02ALF()\br
++ \tab{7}ENDIF\br
++ \tab{5}ELSE\br
++ \tab{7} XSOL=POINTS(COUNT)\br
++ \tab{5}ENDIF\br
++ \tab{5}END

Asp8(name): Exports == Implementation where
  name : Symbol

  O      ==> OutputForm
  S      ==> Symbol
  FST    ==> FortranScalarType
  UFST   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  EX     ==> Expression Integer
  MFLOAT ==> MachineFloat
  EXPR   ==> Expression
  PI     ==> Polynomial Integer
  EXU    ==> Union(I: EXPR Integer,F: EXPR Float,CF: EXPR Complex Float,
                   switch: Switch)

  Exports ==> FortranVectorCategory

  Implementation ==> add

    real : UFST := ["real"::FST]$UFST
    syms : SYMTAB := empty()$SYMTAB
    declare!([COUNT,M,N],fortranInteger(),syms)$SYMTAB
    declare!(XSOL,fortranReal(),syms)$SYMTAB
    yType : FT := construct(real,[N],false)$FT
    declare!(Y,yType,syms)$SYMTAB
    declare!(FORWRD,fortranLogical(),syms)$SYMTAB
    declare!(RESULT,construct(real,[M,N],false)$FT,syms)$SYMTAB
    Rep := _
     FortranProgram(name,["void"]$UFST,[XSOL,Y,COUNT,M,N,RESULT,FORWRD],syms)
```

```
coerce(c:List FC):% == coerce(c)$Rep

coerce(r:RSFC):% == coerce(r)$Rep

coerce(c:FC):% == coerce(c)$Rep

coerce(u:%):O == coerce(u)$Rep

outputAsFortran(u:%):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
  p => restorePrecision()$NAGLinkSupportPackage


f2ex(u:MFLOAT):EXPR MFLOAT == (u::EXPR MFLOAT)$EXPR(MFLOAT)

coerce(points:Vector MFLOAT):% ==
  import PI
  import EXPR Integer
  -- Create some extra declarations
  locals : SYMTAB := empty()$SYMTAB
  nPol : PI := "N"::S::PI
  iPol : PI := "I"::S::PI
  countPol : PI := "COUNT"::S::PI
  pointsDim : PI := max(#points,1)::PI
  declare!(POINTS,[real,[pointsDim],false]$FT,locals)$SYMTAB
  declare!(X02ALF,[real,[],true]$FT,locals)$SYMTAB
  -- Now build up the code fragments
  index : SegmentBinding PI := equation(I@S,1::PI..nPol)$SegmentBinding(PI)
  ySym : EX := (subscript("Y"::S,[I::O])$S)::EX
  loop := forLoop(index,assign(RESULT,[countPol,iPol],ySym)$FC)$FC
  v:Vector EXPR MFLOAT
  v := map(f2ex,points)$VectorFunctions2(MFLOAT,EXPR MFLOAT)
  assign1 : FC := assign(POINTS,v)$FC
  countExp: EX := COUNT@S::EX
  newValue: EX := 1 + countExp
  assign2 : FC := assign(COUNT,newValue)$FC
  newSymbol : S := subscript(POINTS,[COUNT]@List(O))$S
  assign3 : FC := assign(XSOL, newSymbol::EX )$FC
  fphuge : EX := kernel(operator X02ALF,empty()$List(EX))
  assign4 : FC := assign(XSOL, fphuge)$FC
  assign5 : FC := assign(XSOL, -fphuge)$FC
  innerCond : FC := cond("FORWRD"::Symbol::Switch,assign4,assign5)
  mExp : EX := M@S::EX
  endCase : FC := cond(EQ([countExp]$EXU,[mExp]$EXU)$Switch,innerCond,assign3)
  code := [assign1, assign2, loop, endCase]$List(FC)
  ([locals,code]$RSFC)::%
```

———-

— ASP8.dotabb —

```
"ASP8" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP8"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP8" -> "ALIST"
```

———-

2.38 domain ASP80 Asp80

— Asp80.input —

```
)set break resume
)sys rm -f Asp80.output
)spool Asp80.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp80
--R
--R Asp80(name: Symbol)  is a domain constructor
--R Abbreviation for Asp80 is ASP80
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP80
--R
--R------------------------------ Operations ------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Matrix(FortranExpression([construct,QUOTEXL,QUOTEXR,QUOTEELAM],[construct],MachineF
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Matrix(Fraction(Polynomial(Integer))) -> %
--R retract : Matrix(Fraction(Polynomial(Float))) -> %
--R retract : Matrix(Polynomial(Integer)) -> %
--R retract : Matrix(Polynomial(Float)) -> %
--R retract : Matrix(Expression(Integer)) -> %
--R retract : Matrix(Expression(Float)) -> %
--R retractIfCan : Matrix(Fraction(Polynomial(Integer))) -> Union(%,"failed")
--R retractIfCan : Matrix(Fraction(Polynomial(Float))) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Integer)) -> Union(%,"failed")
--R retractIfCan : Matrix(Expression(Float)) -> Union(%,"failed")
--R
```

```
--E 1

)spool
)lisp (bye)
```

———-


— **Asp80.help** —

```
=====================================================================
Asp80 examples
=====================================================================

See Also:
o )show Asp80
```

———-

2.38.1 Asp80 (ASP80)



Exports:
coerce outputAsFortran retract retractIfCan

— **domain ASP80 Asp80** —

```
)abbrev domain ASP80 Asp80
++ Author: Mike Dewar and Godfrey Nolan
++ Date Created: Oct 1993
++ Date Last Updated: 30 March 1994
++                    6 October 1994
++ Related Constructors: FortranMatrixFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp80} produces Fortran for Type 80 ASPs, needed for NAG routine
```

```
++ d02kef, for example:
++
++ \tab{5}SUBROUTINE BDYVAL(XL,XR,ELAM,YL,YR)\br
++ \tab{5}DOUBLE PRECISION ELAM,XL,YL(3),XR,YR(3)\br
++ \tab{5}YL(1)=XL\br
++ \tab{5}YL(2)=2.0D0\br
++ \tab{5}YR(1)=1.0D0\br
++ \tab{5}YR(2)=-1.0D0*DSQRT(XR+(-1.0D0*ELAM))\br
++ \tab{5}RETURN\br
++ \tab{5}END

Asp80(name): Exports == Implementation where
  name : Symbol

  FST    ==> FortranScalarType
  FSTU   ==> Union(fst:FST,void:"void")
  FT     ==> FortranType
  FC     ==> FortranCode
  SYMTAB ==> SymbolTable
  RSFC   ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  FRAC   ==> Fraction
  POLY   ==> Polynomial
  EXPR   ==> Expression
  INT    ==> Integer
  FLOAT  ==> Float
  MFLOAT ==> MachineFloat
  FEXPR  ==> FortranExpression(['XL,'XR,'ELAM],[],MFLOAT)
  VEC    ==> Vector
  MAT    ==> Matrix
  VF2    ==> VectorFunctions2
  M2     ==> MatrixCategoryFunctions2
  MF2a   ==> M2(FRAC POLY INT,VEC FRAC POLY INT,VEC FRAC POLY INT,
                MAT FRAC POLY INT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2b   ==> M2(FRAC POLY FLOAT,VEC FRAC POLY FLOAT,VEC FRAC POLY FLOAT,
                MAT FRAC POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2c   ==> M2(POLY INT,VEC POLY INT,VEC POLY INT,MAT POLY INT,
                FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2d   ==> M2(POLY FLOAT,VEC POLY FLOAT,VEC POLY FLOAT,
                MAT POLY FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2e   ==> M2(EXPR INT,VEC EXPR INT,VEC EXPR INT,MAT EXPR INT,
                FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)
  MF2f   ==> M2(EXPR FLOAT,VEC EXPR FLOAT,VEC EXPR FLOAT,
                MAT EXPR FLOAT, FEXPR,VEC FEXPR,VEC FEXPR,MAT FEXPR)

  Exports ==> FortranMatrixFunctionCategory with
    coerce : MAT FEXPR -> $
      ++coerce(f) takes objects from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns them into an ASP.

  Implementation ==> add
```

```
real : FSTU := ["real"::FST]$FSTU
syms : SYMTAB := empty()$SYMTAB
declare!(XL,fortranReal(),syms)$SYMTAB
declare!(XR,fortranReal(),syms)$SYMTAB
declare!(ELAM,fortranReal(),syms)$SYMTAB
yType : FT := construct(real,["3"::Symbol],false)$FT
declare!(YL,yType,syms)$SYMTAB
declare!(YR,yType,syms)$SYMTAB
Rep := FortranProgram(name,["void"]$FSTU, [XL,XR,ELAM,YL,YR],syms)

fexpr2expr(u:FEXPR):EXPR MFLOAT == coerce(u)$FEXPR

vecAssign(s:Symbol,u:VEC FEXPR):FC ==
  u' : VEC EXPR MFLOAT := map(fexpr2expr,u)$VF2(FEXPR,EXPR MFLOAT)
  assign(s,u')$FC

coerce(u:MAT FEXPR):$ ==
  [vecAssign(YL,row(u,1)),vecAssign(YR,row(u,2)),returns()$FC]$List(FC)::$

coerce(c:List FortranCode):$ == coerce(c)$Rep

coerce(r:RSFC):$ == coerce(r)$Rep

coerce(c:FortranCode):$ == coerce(c)$Rep

coerce(u:$):OutputForm == coerce(u)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
  p => restorePrecision()$NAGLinkSupportPackage

retract(u:MAT FRAC POLY INT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2a
  v::$

retractIfCan(u:MAT FRAC POLY INT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2a
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT FRAC POLY FLOAT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2b
  v::$

retractIfCan(u:MAT FRAC POLY FLOAT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2b
  v case "failed" => "failed"
  (v::MAT FEXPR)::$
```

```
retract(u:MAT EXPR INT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2e
  v::$

retractIfCan(u:MAT EXPR INT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2e
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT EXPR FLOAT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2f
  v::$

retractIfCan(u:MAT EXPR FLOAT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2f
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT POLY INT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2c
  v::$

retractIfCan(u:MAT POLY INT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2c
  v case "failed" => "failed"
  (v::MAT FEXPR)::$

retract(u:MAT POLY FLOAT):$ ==
  v : MAT FEXPR := map(retract,u)$MF2d
  v::$

retractIfCan(u:MAT POLY FLOAT):Union($,"failed") ==
  v:Union(MAT FEXPR,"failed"):=map(retractIfCan,u)$MF2d
  v case "failed" => "failed"
  (v::MAT FEXPR)::$
```

— ASP80.dotabb —

```
"ASP80" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP80"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ASP80" -> "FS"
```

2.39 domain ASP9 Asp9

— **Asp9.input** —

```
)set break resume
)sys rm -f Asp9.output
)spool Asp9.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Asp9
--R
--R Asp9(name: Symbol)  is a domain constructor
--R Abbreviation for Asp9 is ASP9
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ASP9
--R
--R------------------------------ Operations --------------------------------
--R coerce : FortranCode -> %             coerce : List(FortranCode) -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R retract : Polynomial(Float) -> %      retract : Expression(Float) -> %
--R coerce : FortranExpression([construct,QUOTEX],[construct,QUOTEY],MachineFloat) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R retract : Fraction(Polynomial(Integer)) -> %
--R retract : Fraction(Polynomial(Float)) -> %
--R retract : Polynomial(Integer) -> %
--R retract : Expression(Integer) -> %
--R retractIfCan : Fraction(Polynomial(Integer)) -> Union(%,"failed")
--R retractIfCan : Fraction(Polynomial(Float)) -> Union(%,"failed")
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed")
--R retractIfCan : Polynomial(Float) -> Union(%,"failed")
--R retractIfCan : Expression(Integer) -> Union(%,"failed")
--R retractIfCan : Expression(Float) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```


———-

— **Asp9.help** —

```
=====================================================================
Asp9 examples
=====================================================================
```

```
See Also:
o )show Asp9
```

2.39.1 Asp9 (ASP9)



Exports:
coerce outputAsFortran retract retractIfCan

— domain ASP9 Asp9 —

```
)abbrev domain ASP9 Asp9
++ Author: Mike Dewar, Grant Keady and Godfrey Nolan
++ Date Created: Mar 1993
++ Date Last Updated: 18 March 1994
++                    12 July 1994 added COMMON blocks for d02cjf, d02ejf
++                     6 October 1994
++ Related Constructors: FortranVectorFunctionCategory, FortranProgramCategory
++ Description:
++ \spadtype{Asp9} produces Fortran for Type 9 ASPs, needed for NAG routines
++ d02bhf, d02cjf, d02ejf.
++ These ASPs represent a function of a scalar X and a vector Y, for example:
++
++ \tab{5}DOUBLE PRECISION FUNCTION G(X,Y)\br
++ \tab{5}DOUBLE PRECISION X,Y(*)\br
++ \tab{5}G=X+Y(1)\br
++ \tab{5}RETURN\br
++ \tab{5}END
++
++ If the user provides a constant value for G, then extra information is added
++ via COMMON blocks used by certain routines.  This specifies that the value
++ returned by G in this case is to be ignored.
```

```
Asp9(name): Exports == Implementation where
  name : Symbol

  FEXPR   ==> FortranExpression(['X],['Y],MFLOAT)
  MFLOAT  ==> MachineFloat
  FC      ==> FortranCode
  FST     ==> FortranScalarType
  FT      ==> FortranType
  SYMTAB  ==> SymbolTable
  RSFC    ==> Record(localSymbols:SymbolTable,code:List(FortranCode))
  UFST    ==> Union(fst:FST,void:"void")
  FRAC    ==> Fraction
  POLY    ==> Polynomial
  EXPR    ==> Expression
  INT     ==> Integer
  FLOAT   ==> Float

  Exports ==> FortranFunctionCategory with
    coerce : FEXPR -> %
      ++coerce(f) takes an object from the appropriate instantiation of
      ++\spadtype{FortranExpression} and turns it into an ASP.

  Implementation ==> add

    real : FST := "real"::FST
    syms : SYMTAB := empty()$SYMTAB
    declare!(X,fortranReal()$FT,syms)$SYMTAB
    yType : FT := construct([real]$UFST,["*"::Symbol],false)$FT
    declare!(Y,yType,syms)$SYMTAB
    Rep := FortranProgram(name,[real]$UFST,[X,Y],syms)

    retract(u:FRAC POLY INT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:FRAC POLY INT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    retract(u:FRAC POLY FLOAT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:FRAC POLY FLOAT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
      foo case "failed" => "failed"
      (foo::FEXPR)::$

    retract(u:EXPR FLOAT):$ == (retract(u)@FEXPR)::$
    retractIfCan(u:EXPR FLOAT):Union($,"failed") ==
      foo : Union(FEXPR,"failed")
      foo := retractIfCan(u)$FEXPR
```

```
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:EXPR INT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:EXPR INT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:POLY FLOAT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:POLY FLOAT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

retract(u:POLY INT):$ == (retract(u)@FEXPR)::$
retractIfCan(u:POLY INT):Union($,"failed") ==
  foo : Union(FEXPR,"failed")
  foo := retractIfCan(u)$FEXPR
  foo case "failed" => "failed"
  (foo::FEXPR)::$

coerce(u:FEXPR):% ==
  expr : Expression MachineFloat := (u::Expression(MachineFloat))$FEXPR
  (retractIfCan(u)@Union(MFLOAT,"failed"))$FEXPR case "failed" =>
      coerce(expr)$Rep
  locals : SYMTAB := empty()
  charType : FT := construct(["character"::FST]$UFST,[6::POLY(INT)],false)$FT
  declare!([CHDUM1,CHDUM2,GOPT1,CHDUM,GOPT2],charType,locals)$SYMTAB
  common1 := common(CD02EJ,[CHDUM1,CHDUM2,GOPT1] )$FC
  common2 := common(AD02CJ,[CHDUM,GOPT2] )$FC
  assign1 := assign(GOPT1,"NOGOPT")$FC
  assign2 := assign(GOPT2,"NOGOPT")$FC
  result  := assign(name,expr)$FC
  code : List FC := [common1,common2,assign1,assign2,result]
  ([locals,code]$RSFC)::Rep

coerce(c:List FortranCode):% == coerce(c)$Rep

coerce(r:RSFC):% == coerce(r)$Rep

coerce(c:FortranCode):% == coerce(c)$Rep

coerce(u:%):OutputForm == coerce(u)$Rep

outputAsFortran(u):Void ==
  p := checkPrecision()$NAGLinkSupportPackage
  outputAsFortran(u)$Rep
```

```
      p => restorePrecision()$NAGLinkSupportPackage
```

———-

— **ASP9.dotabb** —

```
"ASP9" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ASP9"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ASP9" -> "ALIST"
```

———-

2.40 domain JORDAN AssociatedJordanAlgebra

— **AssociatedJordanAlgebra.input** —

```
)set break resume
)sys rm -f AssociatedJordanAlgebra.output
)spool AssociatedJordanAlgebra.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AssociatedJordanAlgebra
--R
--R AssociatedJordanAlgebra(R: CommutativeRing,A: NonAssociativeAlgebra(R))  is a domain constructor
--R Abbreviation for AssociatedJordanAlgebra is JORDAN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for JORDAN
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           antiCommutator : (%,%) -> %
--R associator : (%,%,%) -> %             coerce : A -> %
--R coerce : % -> A                       coerce : % -> OutputForm
--R commutator : (%,%) -> %               hash : % -> SingleInteger
--R latex : % -> String                   sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
```

```
--R alternative? : () -> Boolean if A has FINAALG(R)
--R antiAssociative? : () -> Boolean if A has FINAALG(R)
--R antiCommutative? : () -> Boolean if A has FINAALG(R)
--R apply : (Matrix(R),%) -> % if A has FRNAALG(R)
--R associative? : () -> Boolean if A has FINAALG(R)
--R associatorDependence : () -> List(Vector(R)) if A has FINAALG(R) and R has INTDOM or A has F
--R basis : () -> Vector(%) if A has FRNAALG(R)
--R commutative? : () -> Boolean if A has FINAALG(R)
--R conditionsForIdempotents : Vector(%) -> List(Polynomial(R)) if A has FINAALG(R)
--R conditionsForIdempotents : () -> List(Polynomial(R)) if A has FRNAALG(R)
--R convert : % -> Vector(R) if A has FRNAALG(R)
--R convert : Vector(R) -> % if A has FRNAALG(R)
--R coordinates : (%,Vector(%)) -> Vector(R) if A has FINAALG(R)
--R coordinates : (Vector(%),Vector(%)) -> Matrix(R) if A has FINAALG(R)
--R coordinates : % -> Vector(R) if A has FRNAALG(R)
--R coordinates : Vector(%) -> Matrix(R) if A has FRNAALG(R)
--R ?.? : (%,Integer) -> R if A has FRNAALG(R)
--R flexible? : () -> Boolean if A has FINAALG(R)
--R jacobiIdentity? : () -> Boolean if A has FINAALG(R)
--R jordanAdmissible? : () -> Boolean if A has FINAALG(R)
--R jordanAlgebra? : () -> Boolean if A has FINAALG(R)
--R leftAlternative? : () -> Boolean if A has FINAALG(R)
--R leftCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R)
--R leftDiscriminant : Vector(%) -> R if A has FINAALG(R)
--R leftDiscriminant : () -> R if A has FRNAALG(R)
--R leftMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R) and R has INT
--R leftNorm : % -> R if A has FINAALG(R)
--R leftPower : (%,PositiveInteger) -> %
--R leftRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if A has FRNAALG(R) and
--R leftRecip : % -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R)
--R leftRegularRepresentation : (%,Vector(%)) -> Matrix(R) if A has FINAALG(R)
--R leftRegularRepresentation : % -> Matrix(R) if A has FRNAALG(R)
--R leftTrace : % -> R if A has FINAALG(R)
--R leftTraceMatrix : Vector(%) -> Matrix(R) if A has FINAALG(R)
--R leftTraceMatrix : () -> Matrix(R) if A has FRNAALG(R)
--R leftUnit : () -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R)
--R leftUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if A has FINAALG(R) a
--R lieAdmissible? : () -> Boolean if A has FINAALG(R)
--R lieAlgebra? : () -> Boolean if A has FINAALG(R)
--R noncommutativeJordanAlgebra? : () -> Boolean if A has FINAALG(R)
--R plenaryPower : (%,PositiveInteger) -> %
--R powerAssociative? : () -> Boolean if A has FINAALG(R)
--R rank : () -> PositiveInteger if A has FINAALG(R)
--R recip : % -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and
--R represents : (Vector(R),Vector(%)) -> % if A has FINAALG(R)
--R represents : Vector(R) -> % if A has FRNAALG(R)
--R rightAlternative? : () -> Boolean if A has FINAALG(R)
--R rightCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R)
--R rightDiscriminant : Vector(%) -> R if A has FINAALG(R)
--R rightDiscriminant : () -> R if A has FRNAALG(R)
```

```
--R rightMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R) and R has INTDOM or A ha
--R rightNorm : % -> R if A has FINAALG(R)
--R rightPower : (%,PositiveInteger) -> %
--R rightRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if A has FRNAALG(R) and R has FIE
--R rightRecip : % -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and R has
--R rightRegularRepresentation : (%,Vector(%)) -> Matrix(R) if A has FINAALG(R)
--R rightRegularRepresentation : % -> Matrix(R) if A has FRNAALG(R)
--R rightTrace : % -> R if A has FINAALG(R)
--R rightTraceMatrix : Vector(%) -> Matrix(R) if A has FINAALG(R)
--R rightTraceMatrix : () -> Matrix(R) if A has FRNAALG(R)
--R rightUnit : () -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and R has
--R rightUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if A has FINAALG(R) and R has I
--R someBasis : () -> Vector(%) if A has FINAALG(R)
--R structuralConstants : Vector(%) -> Vector(Matrix(R)) if A has FINAALG(R)
--R structuralConstants : () -> Vector(Matrix(R)) if A has FRNAALG(R)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit : () -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and R has INTDO
--R
--E 1

)spool
)lisp (bye)
```

———-


— AssociatedJordanAlgebra.help —

```
=====================================================================
AssociatedJordanAlgebra examples
=====================================================================

See Also:
o )show AssociatedJordanAlgebra
```

———-

2.40.1 AssociatedJordanAlgebra (JORDAN)



See

⇒ "AssociatedLieAlgebra" (LIE) 2.41.1 on page 213
⇒ "LieSquareMatrix" (LSQM) 13.5.1 on page 1423

Exports:

0	alternative?
antiAssociative?	antiCommutative?
antiCommutator	apply
associative?	associator
associatorDependence	basis
coerce	commutative?
commutator	conditionsForIdempotents
convert	coordinates
flexible?	hash
jacobiIdentity?	jordanAdmissible?
jordanAlgebra?	latex
leftAlternative?	leftCharacteristicPolynomial
leftDiscriminant	leftMinimalPolynomial
leftNorm	leftPower
leftRankPolynomial	leftRecip
leftRegularRepresentation	leftTrace
leftTraceMatrix	leftUnit
leftUnits	lieAdmissible?
lieAlgebra?	noncommutativeJordanAlgebra?
plenaryPower	powerAssociative?
rank	recip
represents	rightAlternative?
rightCharacteristicPolynomial	rightDiscriminant
rightMinimalPolynomial	rightNorm
rightPower	rightRankPolynomial
rightRecip	rightRegularRepresentation
rightTrace	rightTraceMatrix
rightUnit	rightUnits
sample	someBasis
structuralConstants	subtractIfCan
unit	zero?
?*?	?**?
?+?	?-?
-?	?=?
?~=?	?.?

— domain JORDAN AssociatedJordanAlgebra —

```
)abbrev domain JORDAN AssociatedJordanAlgebra
++ Author: J. Grabmeier
++ Date Created: 14 June 1991
++ Date Last Updated: 14 June 1991
++ Basic Operations: *,**,+,-
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: associated Jordan algebra
```

```
++ References:
++ Description:
++ AssociatedJordanAlgebra takes an algebra \spad{A} and uses \spadfun{*$A}
++ to define the new multiplications \spad{a*b := (a *$A b + b *$A a)/2}
++ (anticommutator).
++ The usual notation \spad{{a,b}_+} cannot be used due to
++ restrictions in the current language.
++ This domain only gives a Jordan algebra if the
++ Jordan-identity \spad{(a*b)*c + (b*c)*a + (c*a)*b = 0} holds
++ for all \spad{a},\spad{b},\spad{c} in \spad{A}.
++ This relation can be checked by
++ \spadfun{jordanAdmissible?()$A}.
++
++ If the underlying algebra is of type
++ \spadtype{FramedNonAssociativeAlgebra(R)} (i.e. a non
++ associative algebra over R which is a free R-module of finite
++ rank, together with a fixed R-module basis), then the same
++ is true for the associated Jordan algebra.
++ Moreover, if the underlying algebra is of type
++ \spadtype{FiniteRankNonAssociativeAlgebra(R)} (i.e. a non
++ associative algebra over R which is a free R-module of finite
++ rank), then the same true for the associated Jordan algebra.

AssociatedJordanAlgebra(R:CommutativeRing,A:NonAssociativeAlgebra R):
    public == private where
  public ==> Join (NonAssociativeAlgebra R, CoercibleTo A)  with
    coerce : A -> %
      ++ coerce(a) coerces the element \spad{a} of the algebra \spad{A}
      ++ to an element of the Jordan algebra
      ++ \spadtype{AssociatedJordanAlgebra}(R,A).
    if A has FramedNonAssociativeAlgebra(R) then _
      FramedNonAssociativeAlgebra(R)
    if A has FiniteRankNonAssociativeAlgebra(R) then _
      FiniteRankNonAssociativeAlgebra(R)

  private ==> A add
    Rep := A
    two  : R := (1$R + 1$R)
    oneHalf : R := (recip two) :: R
    (a:%) * (b:%) ==
      zero? two => error
        "constructor must no be called with Ring of characteristic 2"
      ((a::Rep) * $Rep (b::Rep) +$Rep (b::Rep) * $Rep (a::Rep)) * oneHalf
      -- (a::Rep) * $Rep (b::Rep) +$Rep (b::Rep) * $Rep (a::Rep)
    coerce(a:%):A == a :: Rep
    coerce(a:A):% == a :: %
    (a:%) ** (n:PositiveInteger) == a
```

— **JORDAN.dotabb** —

```
"JORDAN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=JORDAN"]
"FRNAALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRNAALG"]
"JORDAN" -> "FRNAALG"
```

———-

2.41 domain LIE AssociatedLieAlgebra

— **AssociatedLieAlgebra.input** —

```
)set break resume
)sys rm -f AssociatedLieAlgebra.output
)spool AssociatedLieAlgebra.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AssociatedLieAlgebra
--R
--R AssociatedLieAlgebra(R: CommutativeRing,A: NonAssociativeAlgebra(R))  is a domain constructor
--R Abbreviation for AssociatedLieAlgebra is LIE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LIE
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           antiCommutator : (%,%) -> %
--R associator : (%,%,%) -> %             coerce : A -> %
--R coerce : % -> A                       coerce : % -> OutputForm
--R commutator : (%,%) -> %               hash : % -> SingleInteger
--R latex : % -> String                   sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R alternative? : () -> Boolean if A has FINAALG(R)
--R antiAssociative? : () -> Boolean if A has FINAALG(R)
--R antiCommutative? : () -> Boolean if A has FINAALG(R)
--R apply : (Matrix(R),%) -> % if A has FRNAALG(R)
--R associative? : () -> Boolean if A has FINAALG(R)
```

```
--R associatorDependence : () -> List(Vector(R)) if A has FINAALG(R) and R has INTDOM or A has F
--R basis : () -> Vector(%) if A has FRNAALG(R)
--R commutative? : () -> Boolean if A has FINAALG(R)
--R conditionsForIdempotents : Vector(%) -> List(Polynomial(R)) if A has FINAALG(R)
--R conditionsForIdempotents : () -> List(Polynomial(R)) if A has FRNAALG(R)
--R convert : % -> Vector(R) if A has FRNAALG(R)
--R convert : Vector(R) -> % if A has FRNAALG(R)
--R coordinates : (%,Vector(%)) -> Vector(R) if A has FINAALG(R)
--R coordinates : (Vector(%),Vector(%)) -> Matrix(R) if A has FINAALG(R)
--R coordinates : % -> Vector(R) if A has FRNAALG(R)
--R coordinates : Vector(%) -> Matrix(R) if A has FRNAALG(R)
--R ?.? : (%,Integer) -> R if A has FRNAALG(R)
--R flexible? : () -> Boolean if A has FINAALG(R)
--R jacobiIdentity? : () -> Boolean if A has FINAALG(R)
--R jordanAdmissible? : () -> Boolean if A has FINAALG(R)
--R jordanAlgebra? : () -> Boolean if A has FINAALG(R)
--R leftAlternative? : () -> Boolean if A has FINAALG(R)
--R leftCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R)
--R leftDiscriminant : Vector(%) -> R if A has FINAALG(R)
--R leftDiscriminant : () -> R if A has FRNAALG(R)
--R leftMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R) and R has INT
--R leftNorm : % -> R if A has FINAALG(R)
--R leftPower : (%,PositiveInteger) -> %
--R leftRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if A has FRNAALG(R) and
--R leftRecip : % -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R)
--R leftRegularRepresentation : (%,Vector(%)) -> Matrix(R) if A has FINAALG(R)
--R leftRegularRepresentation : % -> Matrix(R) if A has FRNAALG(R)
--R leftTrace : % -> R if A has FINAALG(R)
--R leftTraceMatrix : Vector(%) -> Matrix(R) if A has FINAALG(R)
--R leftTraceMatrix : () -> Matrix(R) if A has FRNAALG(R)
--R leftUnit : () -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R)
--R leftUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if A has FINAALG(R) a
--R lieAdmissible? : () -> Boolean if A has FINAALG(R)
--R lieAlgebra? : () -> Boolean if A has FINAALG(R)
--R noncommutativeJordanAlgebra? : () -> Boolean if A has FINAALG(R)
--R plenaryPower : (%,PositiveInteger) -> %
--R powerAssociative? : () -> Boolean if A has FINAALG(R)
--R rank : () -> PositiveInteger if A has FINAALG(R)
--R recip : % -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and
--R represents : (Vector(R),Vector(%)) -> % if A has FINAALG(R)
--R represents : Vector(R) -> % if A has FRNAALG(R)
--R rightAlternative? : () -> Boolean if A has FINAALG(R)
--R rightCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R)
--R rightDiscriminant : Vector(%) -> R if A has FINAALG(R)
--R rightDiscriminant : () -> R if A has FRNAALG(R)
--R rightMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if A has FINAALG(R) and R has IN
--R rightNorm : % -> R if A has FINAALG(R)
--R rightPower : (%,PositiveInteger) -> %
--R rightRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if A has FRNAALG(R) an
--R rightRecip : % -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R)
```

```
--R rightRegularRepresentation : (%,Vector(%)) -> Matrix(R) if A has FINAALG(R)
--R rightRegularRepresentation : % -> Matrix(R) if A has FRNAALG(R)
--R rightTrace : % -> R if A has FINAALG(R)
--R rightTraceMatrix : Vector(%) -> Matrix(R) if A has FINAALG(R)
--R rightTraceMatrix : () -> Matrix(R) if A has FRNAALG(R)
--R rightUnit : () -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and R has
--R rightUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if A has FINAALG(R) and R has IN
--R someBasis : () -> Vector(%) if A has FINAALG(R)
--R structuralConstants : Vector(%) -> Vector(Matrix(R)) if A has FINAALG(R)
--R structuralConstants : () -> Vector(Matrix(R)) if A has FRNAALG(R)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit : () -> Union(%,"failed") if A has FINAALG(R) and R has INTDOM or A has FRNAALG(R) and R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— **AssociatedLieAlgebra.help** —

```
=====================================================================
AssociatedLieAlgebra examples
=====================================================================

See Also:
o )show AssociatedLieAlgebra
```

———-

2.41.1 AssociatedLieAlgebra (LIE)



See

⇒ "AssociatedJordanAlgebra" (JORDAN) 2.40.1 on page 208
⇒ "LieSquareMatrix" (LSQM) 13.5.1 on page 1423

Exports:

0	alternative?
antiAssociative?	antiCommutative?
antiCommutator	apply
associative?	associator
associatorDependence	basis
coerce	commutative?
commutator	conditionsForIdempotents
convert	coordinates
flexible?	hash
jacobiIdentity?	jordanAdmissible?
jordanAlgebra?	latex
leftAlternative?	leftCharacteristicPolynomial
leftDiscriminant	leftMinimalPolynomial
leftNorm	leftPower
leftRankPolynomial	leftRecip
leftRegularRepresentation	leftTrace
leftTraceMatrix	leftUnit
leftUnits	lieAdmissible?
lieAlgebra?	noncommutativeJordanAlgebra?
plenaryPower	powerAssociative?
rank	recip
represents	represents
rightAlternative?	rightCharacteristicPolynomial
rightDiscriminant	rightMinimalPolynomial
rightNorm	rightPower
rightRankPolynomial	rightRecip
rightRegularRepresentation	rightTrace
rightTraceMatrix	rightUnit
rightUnits	sample
someBasis	structuralConstants
structuralConstants	subtractIfCan
unit	zero?
?*?	?**?
?+?	?-?
-?	?=?
?~=?	?.?

— domain LIE AssociatedLieAlgebra —

```
)abbrev domain LIE AssociatedLieAlgebra
++ Author: J. Grabmeier
++ Date Created: 07 March 1991
++ Date Last Updated: 14 June 1991
```

```
++ Basic Operations: *,**,+,-
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: associated Liealgebra
++ References:
++ Description:
++ AssociatedLieAlgebra takes an algebra \spad{A}
++ and uses \spadfun{*$A} to define the
++ Lie bracket \spad{a*b := (a *$A b - b *$A a)} (commutator). Note that
++ the notation \spad{[a,b]} cannot be used due to
++ restrictions of the current compiler.
++ This domain only gives a Lie algebra if the
++ Jacobi-identity \spad{(a*b)*c + (b*c)*a + (c*a)*b = 0} holds
++ for all \spad{a},\spad{b},\spad{c} in \spad{A}.
++ This relation can be checked by
++ \spad{lieAdmissible?()$A}.
++
++ If the underlying algebra is of type
++ \spadtype{FramedNonAssociativeAlgebra(R)} (i.e. a non
++ associative algebra over R which is a free \spad{R}-module of finite
++ rank, together with a fixed \spad{R}-module basis), then the same
++ is true for the associated Lie algebra.
++ Also, if the underlying algebra is of type
++ \spadtype{FiniteRankNonAssociativeAlgebra(R)} (i.e. a non
++ associative algebra over R which is a free R-module of finite
++ rank), then the same is true for the associated Lie algebra.

AssociatedLieAlgebra(R:CommutativeRing,A:NonAssociativeAlgebra R):
    public == private where
  public ==> Join (NonAssociativeAlgebra R, CoercibleTo A)  with
    coerce : A -> %
      ++ coerce(a) coerces the element \spad{a} of the algebra \spad{A}
      ++ to an element of the Lie
      ++ algebra \spadtype{AssociatedLieAlgebra}(R,A).
    if A has FramedNonAssociativeAlgebra(R) then
      FramedNonAssociativeAlgebra(R)
    if A has FiniteRankNonAssociativeAlgebra(R) then
      FiniteRankNonAssociativeAlgebra(R)

  private ==> A add
    Rep := A
    (a:%) * (b:%) == (a::Rep) * $Rep (b::Rep) -$Rep (b::Rep) * $Rep (a::Rep)
    coerce(a:%):A == a :: Rep
    coerce(a:A):% == a :: %
    (a:%) ** (n:PositiveInteger) ==
      n = 1 => a
      0
```

———-

— **LIE.dotabb** —

```
"LIE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LIE"]
"FRNAALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRNAALG"]
"LIE" -> "FRNAALG"
```

———-

2.42 domain ALIST AssociationList

— **AssociationList.input** —

```
)set break resume
)sys rm -f AssociationList.output
)spool AssociationList.output
)set message test on
)set message auto off
)clear all
--S 1 of 10
Data := Record(monthsOld : Integer, gender : String)
--R
--R
--R   (1)  Record(monthsOld: Integer,gender: String)
--R                                                                    Type: Domain
--E 1

--S 2 of 10
al : AssociationList(String,Data)
--R
--R                                                                      Type: Void
--E 2

--S 3 of 10
al := table()
--R
--R
--R   (3)  table()
--R      Type: AssociationList(String,Record(monthsOld: Integer,gender: String))
--E 3

--S 4 of 10
al."bob" := [407,"male"]$Data
--R
```

```
--R
--R   (4)  [monthsOld= 407,gender= "male"]
--R                              Type: Record(monthsOld: Integer,gender: String)
--E 4

--S 5 of 10
al."judith" := [366,"female"]$Data
--R
--R
--R   (5)  [monthsOld= 366,gender= "female"]
--R                              Type: Record(monthsOld: Integer,gender: String)
--E 5

--S 6 of 10
al."katie" := [24,"female"]$Data
--R
--R
--R   (6)  [monthsOld= 24,gender= "female"]
--R                              Type: Record(monthsOld: Integer,gender: String)
--E 6

--S 7 of 10
al."smokie" := [200,"female"]$Data
--R
--R
--R   (7)  [monthsOld= 200,gender= "female"]
--R                              Type: Record(monthsOld: Integer,gender: String)
--E 7

--S 8 of 10
al
--R
--R
--R   (8)
--R   table
--R      "smokie"= [monthsOld= 200,gender= "female"]
--R  ,
--R      "katie"= [monthsOld= 24,gender= "female"]
--R  ,
--R      "judith"= [monthsOld= 366,gender= "female"]
--R  ,
--R      "bob"= [monthsOld= 407,gender= "male"]
--R      Type: AssociationList(String,Record(monthsOld: Integer,gender: String))
--E 8

--S 9 of 10
al."katie" := [23,"female"]$Data
--R
--R
--R   (9)  [monthsOld= 23,gender= "female"]
```

```
--R                              Type: Record(monthsOld: Integer,gender: String)
--E 9

--S 10 of 10
delete!(al,1)
--R
--R
--R   (10)
--R   table
--R      "katie"= [monthsOld= 23,gender= "female"]
--R  ,
--R      "judith"= [monthsOld= 366,gender= "female"]
--R  ,
--R      "bob"= [monthsOld= 407,gender= "male"]
--R      Type: AssociationList(String,Record(monthsOld: Integer,gender: String))
--E 10
)spool
)lisp (bye)
```

———-

— AssociationList.help —

```
=====================================================================
AssociationList examples
=====================================================================

The AssociationList constructor provides a general structure for
associative storage.  This type provides association lists in which
data objects can be saved according to keys of any type.  For a given
association list, specific types must be chosen for the keys and
entries.  You can think of the representation of an association list
as a list of records with key and entry fields.

Association lists are a form of table and so most of the operations
available for Table are also available for AssociationList.  They can
also be viewed as lists and can be manipulated accordingly.

This is a Record type with age and gender fields.

  Data := Record(monthsOld : Integer, gender : String)
    Record(monthsOld: Integer,gender: String)
                     Type: Domain

In this expression, al is declared to be an association
list whose keys are strings and whose entries are the above records.

  al : AssociationList(String,Data)
                     Type: Void
```

```
The table operation is used to create an empty association list.

  al := table()
   table()
    Type: AssociationList(String,Record(monthsOld: Integer,gender: String))

You can use assignment syntax to add things to the association list.

  al."bob" := [407,"male"]$Data
   [monthsOld=407, gender= "male"]
                      Type: Record(monthsOld: Integer,gender: String)

  al."judith" := [366,"female"]$Data
   [monthsOld=366, gender= "female"]
                      Type: Record(monthsOld: Integer,gender: String)

  al."katie" := [24,"female"]$Data
   [monthsOld=24, gender= "female"]
                      Type: Record(monthsOld: Integer,gender: String)

Perhaps we should have included a species field.

  al."smokie" := [200,"female"]$Data
   [monthsOld=200, gender= "female"]
                      Type: Record(monthsOld: Integer,gender: String)

Now look at what is in the association list.  Note that the last-added
(key, entry) pair is at the beginning of the list.

  al
   table("smokie" = [monthsOld=200, gender= "female"],
         "katie" = [monthsOld=24, gender= "female"],
         "judith" = [monthsOld=366, gender= "female"],
         "bob" = [monthsOld=407, gender= "male"])
      Type: AssociationList(String,Record(monthsOld: Integer,gender: String))

You can reset the entry for an existing key.

  al."katie" := [23,"female"]$Data
   [monthsOld=23, gender= "female"]
                      Type: Record(monthsOld: Integer,gender: String)


Use delete! to destructively remove an element of the association
list.  Use delete to return a copy of the association list with the
element deleted.  The second argument is the index of the element to
delete.

  delete!(al,1)
   table("katie" = [monthsOld=23, gender= "female"],
```

```
        "judith" = [monthsOld=366, gender= "female"],
        "bob" = [monthsOld=407, gender= "male"])
    Type: AssociationList(String,Record(monthsOld: Integer,gender: String))

See Also:
o )help Table
o )help List
o )show AssociationList
```

2.42.1 AssociationList (ALIST)



See

⇒ “IndexedList” (ILIST) 10.11.1 on page 1200
⇒ “List” (LIST) 13.9.1 on page 1472

Exports:

any?	assoc	bag	child?	children
coerce	concat	concat!	construct	convert
copy	copyInto!	count	cycleEntry	cycleLength
cycleSplit!	cycleTail	cyclic?	delete	delete!
dictionary	distance	elt	empty	empty?
entries	entry?	eq?	eval	every?
explicitlyFinite?	extract!	fill!	find	first
hash	index?	indices	insert	insert!
inspect	key?	keys	last	latex
leaf?	leaves	less?	list	map
map!	max	maxIndex	member?	members
merge	merge!	min	minIndex	more?
new	node?	nodes	parts	position
possiblyInfinite?	qelt	qsetelt!	reduce	remove
remove!	removeDuplicates	removeDuplicates!	rest	reverse
reverse!	sample	search	second	select
select!	setchildren!	setelt	setfirst!	setlast!
setrest!	setvalue!	size?	sort	sort!
sorted?	split!	swap!	table	tail
third	value	#?	?<?	?<=?
?=?	?>?	?>=?	?~=?	?.rest
?.value	?.first	?.last	?.?	

— domain ALIST AssociationList —

```
)abbrev domain ALIST AssociationList
++ Author: Mark Botch
++ Date Created:
++ Change History:
++ Basic Operations: empty, empty?, keys, \#, concat, first, rest,
++   setrest!, search, setelt, remove!
++ Related Constructors:
++ Also See: List
++ AMS Classification:
++ Keywords: list, association list
++ Description:
++ \spadtype{AssociationList} implements association lists. These
++ may be viewed as lists of pairs where the first part is a key
++ and the second is the stored value. For example, the key might
++ be a string with a persons employee identification number and
++ the value might be a record with personnel data.

AssociationList(Key:SetCategory, Entry:SetCategory):
 AssociationListAggregate(Key, Entry) == add
        Pair ==> Record(key:Key, entry:Entry)
        Rep := Reference List Pair

        dictionary()            == ref empty()
```

```
        empty()                 == dictionary()
        empty? t                == empty? deref t
        entries(t:%):List(Pair) == deref t
        parts(t:%):List(Pair)   == deref t
        keys t                  == [k.key for k in deref t]
        # t                     == # deref t
        first(t:%):Pair         == first deref t
        rest t                  == ref rest deref t
        concat(p:Pair, t:%)     == ref concat(p, deref t)
        setrest_!(a:%, b:%)     == ref setrest_!(deref a, deref b)
        setfirst_!(a:%, p:Pair) == setfirst_!(deref a,p)
        minIndex(a:%):Integer   == minIndex(deref a)
        maxIndex(a:%):Integer   == maxIndex(deref a)

        search(k, t) ==
          for r in deref t repeat
            k = r.key => return(r.entry)
          "failed"

        latex(a : %) : String ==
          l : List Pair := entries a
          s : String := "\left["
          while not empty?(l) repeat
            r : Pair := first l
            l        := rest l
            s := concat(s, concat(latex r.key, concat(" = ", latex r.entry)$String)$String)$Stri
            if not empty?(l) then s := concat(s, ", ")$String
          concat(s, " \right]")$String

--      assoc(k, l) ==
--        (r := find(#1.key=k, l)) case "failed" => "failed"
--        r

        assoc(k, t) ==
          for r in deref t repeat
            k = r.key => return r
          "failed"

        setelt(t:%, k:Key, e:Entry) ==
          (r := assoc(k, t)) case Pair => (r::Pair).entry := e
          setref(t, concat([k, e], deref t))
          e

        remove_!(k:Key, t:%) ==
          empty?(l := deref t) => "failed"
          k = first(l).key =>
            setref(t, rest l)
            first(l).entry
          prev := l
          curr := rest l
```

```
          while not empty? curr and first(curr).key ^= k repeat
            prev := curr
            curr := rest curr
          empty? curr => "failed"
          setrest_!(prev, rest curr)
          first(curr).entry
```

———-

— **ALIST.dotabb** —

```
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"ALIST" -> "TBAGG"
```

———-

2.43 domain ATTRBUT AttributeButtons

— **AttributeButtons.input** —

```
)set break resume
)sys rm -f AttributeButtons.output
)spool AttributeButtons.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show AttributeButtons
--R AttributeButtons  is a domain constructor
--R Abbreviation for AttributeButtons is ATTRBUT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ATTRBUT
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R decrease : String -> Float            hash : % -> SingleInteger
--R increase : String -> Float            latex : % -> String
--R resetAttributeButtons : () -> Void    ?~=? : (%,%) -> Boolean
--R decrease : (String,String) -> Float
--R getButtonValue : (String,String) -> Float
--R increase : (String,String) -> Float
--R setAttributeButtonStep : Float -> Float
```

```
--R setButtonValue : (String,String,Float) -> Float
--R setButtonValue : (String,Float) -> Float
--R
--E 1

)spool
)lisp (bye)
```

———-


— AttributeButtons.help —

```
=====================================================================
AttributeButtons examples
=====================================================================

See Also:
o )show AttributeButtons
```

———-

2.43.1 AttributeButtons (ATTRBUT)



Exports:

coerce	decrease	getButtonValue	hash
increase	latex	resetAttributeButtons	setAttributeButtonStep
setButtonValue	?~=?	?=?	

— domain ATTRBUT AttributeButtons —

```
)abbrev domain ATTRBUT AttributeButtons
++ Author: Brian Dupee
++ Date Created: April 1996
++ Date Last Updated: December 1997
```

```
++ Basic Operations: increase, decrease, getButtonValue, setButtonValue
++ Related Constructors: Table(String,Float)
++ Description:
++ \axiomType{AttributeButtons} implements a database and associated
++ adjustment mechanisms for a set of attributes.
++
++ For ODEs these attributes are "stiffness", "stability" (i.e. how much
++ affect the cosine or sine component of the solution has on the stability of
++ the result), "accuracy" and "expense" (i.e. how expensive is the evaluation
++ of the ODE).  All these have bearing on the cost of calculating the
++ solution given that reducing the step-length to achieve greater accuracy
++ requires considerable number of evaluations and calculations.
++
++ The effect of each of these attributes can be altered by increasing or
++ decreasing the button value.
++
++ For Integration there is a button for increasing and decreasing the preset
++ number of function evaluations for each method.  This is automatically used
++ by ANNA when a method fails due to insufficient workspace or where the
++ limit of function evaluations has been reached before the required
++ accuracy is achieved.

AttributeButtons(): E == I where
  F     ==> Float
  ST    ==> String
  LST   ==> List String
  Rec   ==> Record(key:Symbol,entry:Any)
  RList ==> List(Record(key:Symbol,entry:Any))
  IFL   ==> List(Record(ifail:Integer,instruction:ST))
  Entry ==> Record(chapter:ST, type:ST, domainName: ST,
                   defaultMin:F, measure:F, failList:IFL, explList:LST)


  E ==> SetCategory with

    increase:(ST,ST) -> F
      ++ \axiom{increase(routineName,attributeName)} increases the value
      ++ for the effect of the attribute \axiom{attributeName} with routine
      ++ \axiom{routineName}.
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
    increase:(ST) -> F
      ++ \axiom{increase(attributeName)} increases the value for the
      ++ effect of the attribute \axiom{attributeName} with all routines.
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
```

```
    decrease:(ST,ST) -> F
      ++ \axiom{decrease(routineName,attributeName)} decreases the value
      ++ for the effect of the attribute \axiom{attributeName} with routine
      ++ \axiom{routineName}.
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
    decrease:(ST) -> F
      ++ \axiom{decrease(attributeName)} decreases the value for the
      ++ effect of the attribute \axiom{attributeName} with all routines.
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
    getButtonValue:(ST,ST) -> F
      ++ \axiom{getButtonValue(routineName,attributeName)} returns the
      ++ current value for the effect of the attribute \axiom{attributeName}
      ++ with routine \axiom{routineName}.
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
    resetAttributeButtons:() -> Void
      ++ \axiom{resetAttributeButtons()} resets the Attribute buttons to a
      ++ neutral level.
    setAttributeButtonStep:(F) -> F
      ++ \axiom{setAttributeButtonStep(n)} sets the value of the steps for
      ++ increasing and decreasing the button values. \axiom{n} must be
      ++ greater than 0 and less than 1.  The preset value is 0.5.
    setButtonValue:(ST,F) -> F
      ++ \axiom{setButtonValue(attributeName,n)} sets the
      ++ value of all buttons of attribute \spad{attributeName}
      ++ to \spad{n}. \spad{n} must be in the range [0..1].
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
    setButtonValue:(ST,ST,F) -> F
      ++ \axiom{setButtonValue(attributeName,routineName,n)} sets the
      ++ value of the button of attribute \spad{attributeName} to routine
      ++ \spad{routineName} to \spad{n}. \spad{n} must be in the range [0..1].
      ++
      ++ \axiom{attributeName} should be one of the values
      ++ "stiffness", "stability", "accuracy", "expense" or
      ++ "functionEvaluations".
    finiteAggregate

  I ==> add
```

```
Rep := StringTable(F)
import Rep

buttons:() -> $

buttons():$ ==
  eList := empty()$List(Record(key:ST,entry:F))
  l1:List String := ["stability","stiffness","accuracy","expense"]
  l2:List String := ["functionEvaluations"]
  ro1 := selectODEIVPRoutines(r := routines()$RoutinesTable)$RoutinesTable
  ro2 := selectIntegrationRoutines(r)$RoutinesTable
  k1:List String := [string(i)$Symbol for i in keys(ro1)$RoutinesTable]
  k2:List String := [string(i)$Symbol for i in keys(ro2)$RoutinesTable]
  for i in k1 repeat
    for j in l1 repeat
      e:Record(key:ST,entry:F) := [i j,0.5]
      eList := cons(e,eList)$List(Record(key:ST,entry:F))
  for i in k2 repeat
    for j in l2 repeat
      e:Record(key:ST,entry:F) := [i j,0.5]
      eList := cons(e,eList)$List(Record(key:ST,entry:F))
  construct(eList)$Rep

attributeButtons:$ := buttons()

attributeStep:F := 0.5

setAttributeButtonStep(n:F):F ==
  positive?(n)$F and (n<1$F) => attributeStep:F := n
  error("setAttributeButtonStep","New value must be in (0..1)")$ErrorFunctions

resetAttributeButtons():Void ==
  attributeButtons := buttons()
  void()$Void

setButtonValue(routineName:ST,attributeName:ST,n:F):F ==
  f := search(routineName attributeName,attributeButtons)$Rep
  f case Float =>
    n>=0$F and n<=1$F =>
      setelt(attributeButtons,routineName attributeName,n)$Rep
    error("setAttributeButtonStep","New value must be in [0..1]")$ErrorFunctions
  error("setButtonValue","attribute name " attributeName
        " not found for routine " routineName)$ErrorFunctions

setButtonValue(attributeName:ST,n:F):F ==
  ro1 := selectODEIVPRoutines(r := routines()$RoutinesTable)$RoutinesTable
  ro2 := selectIntegrationRoutines(r)$RoutinesTable
  l1:List String := ["stability","stiffness","accuracy","expense"]
  l2:List String := ["functionEvaluations"]
  if attributeName="functionEvaluations" then
```

```
    for i in keys(ro2)$RoutinesTable repeat
      setButtonValue(string(i)$Symbol,attributeName,n)
  else
    for i in keys(ro1)$RoutinesTable repeat
      setButtonValue(string(i)$Symbol,attributeName,n)
  n

increase(routineName:ST,attributeName:ST):F ==
  f := search(routineName attributeName,attributeButtons)$Rep
  f case Float =>
    newValue:F := (1$F-attributeStep)*f+attributeStep
    setButtonValue(routineName,attributeName,newValue)
  error("increase","attribute name " attributeName
         " not found for routine " routineName)$ErrorFunctions

increase(attributeName:ST):F ==
  ro1 := selectODEIVPRoutines(r := routines()$RoutinesTable)$RoutinesTable
  ro2 := selectIntegrationRoutines(r)$RoutinesTable
  l1:List String := ["stability","stiffness","accuracy","expense"]
  l2:List String := ["functionEvaluations"]
  if attributeName="functionEvaluations" then
    for i in keys(ro2)$RoutinesTable repeat
      increase(string(i)$Symbol,attributeName)
  else
    for i in keys(ro1)$RoutinesTable repeat
      increase(string(i)$Symbol,attributeName)
  getButtonValue(string(i)$Symbol,attributeName)

decrease(routineName:ST,attributeName:ST):F ==
  f := search(routineName attributeName,attributeButtons)$Rep
  f case Float =>
    newValue:F := (1$F-attributeStep)*f
    setButtonValue(routineName,attributeName,newValue)
  error("increase","attribute name " attributeName
         " not found for routine " routineName)$ErrorFunctions

decrease(attributeName:ST):F ==
  ro1 := selectODEIVPRoutines(r := routines()$RoutinesTable)$RoutinesTable
  ro2 := selectIntegrationRoutines(r)$RoutinesTable
  l1:List String := ["stability","stiffness","accuracy","expense"]
  l2:List String := ["functionEvaluations"]
  if attributeName="functionEvaluations" then
    for i in keys(ro2)$RoutinesTable repeat
      decrease(string(i)$Symbol,attributeName)
  else
    for i in keys(ro1)$RoutinesTable repeat
      decrease(string(i)$Symbol,attributeName)
  getButtonValue(string(i)$Symbol,attributeName)
```

```
    getButtonValue(routineName:ST,attributeName:ST):F ==
      f := search(routineName attributeName,attributeButtons)$Rep
      f case Float => f
      error("getButtonValue","attribute name " attributeName
              " not found for routine " routineName)$ErrorFunctions
```

———-

— **ATTRBUT.dotabb** —

```
"ATTRBUT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ATTRBUT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ATTRBUT" -> "ALIST"
```

———-

2.44 domain AUTOMOR Automorphism

— **Automorphism.input** —

```
)set break resume
)sys rm -f Automorphism.output
)spool Automorphism.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Automorphism
--R
--R Automorphism(R: Ring)  is a domain constructor
--R Abbreviation for Automorphism is AUTOMOR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for AUTOMOR
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                    ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %     ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean              1 : () -> %
--R ?^? : (%,Integer) -> %              ?^? : (%,PositiveInteger) -> %
--R coerce : % -> OutputForm            commutator : (%,%) -> %
--R conjugate : (%,%) -> %              ?.? : (%,R) -> R
--R hash : % -> SingleInteger           inv : % -> %
--R latex : % -> String                 morphism : (R -> R) -> %
```

```
--R one? : % -> Boolean                    recip : % -> Union(%,"failed")
--R sample : () -> %                       ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R morphism : ((R,Integer) -> R) -> %
--R morphism : ((R -> R),(R -> R)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Automorphism.help** —

```
=====================================================================
Automorphism examples
=====================================================================

See Also:
o )show Automorphism
```

———-

2.44.1 Automorphism (AUTOMOR)



See

⇒ “SparseUnivariateSkewPolynomial” (ORESUP) 20.21.1 on page 2459
⇒ “UnivariateSkewPolynomial” (OREUP) 22.8.1 on page 2839

Exports:

1	coerce	commutator	conjugate	hash
inv	latex	morphism	one?	recip
sample	?~=?	?**?	?^?	?.?
?*?	?/?	?=?		

— domain AUTOMOR Automorphism —

```
)abbrev domain AUTOMOR Automorphism
++ Author: Manuel Bronstein
++ Date Created: 31 January 1994
++ Date Last Updated: 31 January 1994
++ References:
++ Description:
++ Automorphism R is the multiplicative group of automorphisms of R.
-- In fact, non-invertible endomorphism are allowed as partial functions.
-- This domain is noncanonical in that f*f^{-1} will be the identity
-- function but won't be equal to 1.

Automorphism(R:Ring): Join(Group, Eltable(R, R)) with
      morphism: (R -> R) -> %
        ++ morphism(f) returns the non-invertible morphism given by f.
      morphism: (R -> R, R -> R) -> %
        ++ morphism(f, g) returns the invertible morphism given by f, where
        ++ g is the inverse of f..
      morphism: ((R, Integer) -> R) -> %
        ++ morphism(f) returns the morphism given by \spad{f^n(x) = f(x,n)}.
   == add
      err:   R -> R
      ident: (R, Integer) -> R
      iter:  (R -> R, NonNegativeInteger, R) -> R
      iterat: (R -> R, R -> R, Integer, R) -> R
      apply: (%, R, Integer) -> R

      Rep := ((R, Integer) -> R)

      1                               == ident
      err r                           == error "Morphism is not invertible"
      ident(r, n)                     == r
      f = g                           == EQ(f, g)$Lisp
      elt(f, r)                       == apply(f, r, 1)
      inv f  == (r1:R, i2:Integer):R +-> apply(f, r1, - i2)
      f ** n == (r1:R, i2:Integer):R +-> apply(f, r1, n * i2)
      coerce(f:%):OutputForm          == message("R -> R")
      morphism(f:(R, Integer) -> R):% == f
      morphism(f:R -> R):%            == morphism(f, err)
      morphism(f, g) == (r1:R, i2:Integer):R +-> iterat(f, g, i2, r1)
      apply(f, r, n) == (g := f pretend ((R, Integer) -> R); g(r, n))

      iterat(f, g, n, r) ==
          n < 0 => iter(g, (-n)::NonNegativeInteger, r)
```

```
          iter(f, n::NonNegativeInteger, r)

      iter(f, n, r) ==
          for i in 1..n repeat r := f r
          r

      f * g ==
        f = g => f**2
        (r1:R, i2:Integer):R +->
          iterat((u1:R):R +-> f g u1,
                 (v1:R):R +-> (inv g)(inv f) v1,
                 i2, r1)
```

———-

— AUTOMOR.dotabb —

```
"AUTOMOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=AUTOMOR"]
"GROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=GROUP"]
"AUTOMOR" -> "GROUP"
```

———-

Chapter 3

Chapter B

3.1 domain BBTREE BalancedBinaryTree

— BalancedBinaryTree.input —

```
)set break resume
)sys rm -f BalancedBinaryTree.output
)spool BalancedBinaryTree.output
)set message test on
)set message auto off
)clear all
--S 1 of 7
lm := [3,5,7,11]
--E 1

--S 2 of 7
t := balancedBinaryTree(#lm, 0)
--E 2

--S 3 of 7
setleaves!(t,lm)
--E 3

--S 4 of 7
mapUp!(t,_*)
--E 4

--S 5 of 7
t
--E 5

--S 6 of 7
```

```
mapDown!(t,12,_rem)
--E 6

--S 7 of 7
leaves %
--E 7

)spool
)lisp (bye)
```

———-

— BalancedBinaryTree.help —

```
====================================================================
BalancedBinaryTree examples
====================================================================

BalancedBinaryTrees(S) is the domain of balanced binary trees with
elements of type S at the nodes.  A binary tree is either empty or
else consists of a node having a value and two branches, each branch a
binary tree.  A balanced binary tree is one that is balanced with
respect its leaves.  One with 2^k leaves is perfectly "balanced": the
tree has minimum depth, and the left and right branch of every
interior node is identical in shape.

Balanced binary trees are useful in algebraic computation for
so-called "divide-and-conquer" algorithms.  Conceptually, the data
for a problem is initially placed at the root of the tree.  The
original data is then split into two subproblems, one for each
subtree.  And so on.  Eventually, the problem is solved at the leaves
of the tree.  A solution to the original problem is obtained by some
mechanism that can reassemble the pieces.  In fact, an implementation
of the Chinese Remainder Algorithm using balanced binary trees was
first proposed by David Y. Y.  Yun at the IBM T. J.  Watson Research
Center in Yorktown Heights, New York, in 1978.  It served as the
prototype for polymorphic algorithms in Axiom.

In what follows, rather than perform a series of computations with a
single expression, the expression is reduced modulo a number of
integer primes, a computation is done with modular arithmetic for each
prime, and the Chinese Remainder Algorithm is used to obtain the
answer to the original problem.  We illustrate this principle with the
computation of 12^2 = 144.

A list of moduli:

  lm := [3,5,7,11]
   [3,5,7,11]
```

```
                    Type: PositiveInteger
```

The expression modTree(n, lm) creates a balanced binary tree with leaf values n mod m for each modulus m in lm.

```
  modTree(12,lm)
   [0, 2, 5, 1]
                    Type: List Integer
```

Operation modTree does this using operations on balanced binary trees. We trace its steps. Create a balanced binary tree t of zeros with four leaves.

```
  t := balancedBinaryTree(#lm, 0)
   [[0, 0, 0], 0, [0, 0, 0]]
                    Type: BalancedBinaryTree NonNegativeInteger
```

The leaves of the tree are set to the individual moduli.

```
  setleaves!(t,lm)
   [[3, 0, 5], 0, [7, 0, 11]]
                    Type: BalancedBinaryTree NonNegativeInteger
```

mapUp! to do a bottom-up traversal of t, setting each interior node to the product of the values at the nodes of its children.

```
  mapUp!(t,_*)
   1155
                    Type: PositiveInteger
```

The value at the node of every subtree is the product of the moduli of the leaves of the subtree.

```
  t
   [[3, 15, 5], 1155, [7, 77, 11]]
                    Type: BalancedBinaryTree NonNegativeInteger
```

Operation mapDown!(t,a,fn) replaces the value v at each node of t by fn(a,v).

```
  mapDown!(t,12,_rem)
   [[0, 12, 2], 12, [5, 12, 1]]
                    Type: BalancedBinaryTree NonNegativeInteger
```

The operation leaves returns the leaves of the resulting tree. In this case, it returns the list of 12 mod m for each modulus m.

```
  leaves %
   [0, 2, 5, 1]
                    Type: List NonNegativeInteger
```

```
Compute the square of the images of 12 modulo each m.


  squares := [x**2 rem m for x in % for m in lm]
   [0, 4, 4, 1]
                        Type: List NonNegativeInteger

Call the Chinese Remainder Algorithm to get the answer for 12^2.

  chineseRemainder(%,lm)
   144
                        Type: PositiveInteger

See Also:
o )show BalancedBinaryTree
```

3.1.1 BalancedBinaryTree (BBTREE)



See

⇒ “Tree” (TREE) 21.10.1 on page 2710
⇒ “BinaryTree” (BTREE) 3.11.1 on page 294
⇒ “BinarySearchTree” (BSTREE) 3.9.1 on page 287
⇒ “BinaryTournament” (BTOURN) 3.10.1 on page 291
⇒ “PendantTree” (PENDTREE) 17.13.1 on page 1911

Exports:

any?	balancedBinaryTree	child?	children	coerce
copy	count	cyclic?	distance	empty
empty?	eq?	eval	every?	hash
latex	leaf?	leaves	left	less?
map	map!	mapDown!	mapUp!	member?
members	more?	node?	node	nodes
parts	right	sample	setchildren!	setelt
setleaves!	setleft!	setright!	setvalue!	size?
value	#?	?=?	?~=?	?.right
?.left	?.value			

— domain BBTREE BalancedBinaryTree —

```
)abbrev domain BBTREE BalancedBinaryTree
++ Description:
++ \spadtype{BalancedBinaryTree(S)} is the domain of balanced
++ binary trees (bbtree). A balanced binary tree of \spad{2**k} leaves,
++ for some \spad{k > 0}, is symmetric, that is, the left and right
++ subtree of each interior node have identical shape.
++ In general, the left and right subtree of a given node can differ
++ by at most leaf node.

BalancedBinaryTree(S: SetCategory): Exports == Implementation where
  Exports == BinaryTreeCategory(S) with
    finiteAggregate
    shallowlyMutable
--  BUG: applies wrong fnct for balancedBinaryTree(0,[1,2,3,4])
--    balancedBinaryTree: (S, List S) -> %
--      ++ balancedBinaryTree(s, ls) creates a balanced binary tree with
--      ++ s at the interior nodes and elements of ls at the
--      ++ leaves.
    balancedBinaryTree: (NonNegativeInteger, S) -> %
      ++ balancedBinaryTree(n, s) creates a balanced binary tree with
      ++ n nodes each with value s.
      ++
      ++X balancedBinaryTree(4, 0)

    setleaves_!: (%, List S) -> %
      ++ setleaves!(t, ls) sets the leaves of t in left-to-right order
      ++ to the elements of ls.
      ++
      ++X t1:=balancedBinaryTree(4, 0)
      ++X setleaves!(t1,[1,2,3,4])

    mapUp_!: (%, (S,S) -> S) -> S
      ++ mapUp!(t,f) traverses balanced binary tree t in an "endorder"
      ++ (left then right then node) fashion returning t with the value
      ++ at each successive interior node of t replaced by
      ++ f(l,r) where l and r are the values at the immediate
```

```
  ++ left and right nodes.
  ++
  ++X T1:=BalancedBinaryTree Integer
  ++X t2:=balancedBinaryTree(4, 0)$T1
  ++X setleaves!(t2,[1,2,3,4]::List(Integer))
  ++X adder(a:Integer,b:Integer):Integer == a+b
  ++X mapUp!(t2,adder)
  ++X t2

mapUp_!: (%, %, (S,S,S,S) -> S) -> %
  ++ mapUp!(t,t1,f) traverses balanced binary tree t in an "endorder"
  ++ (left then right then node) fashion returning t with the value
  ++ at each successive interior node of t replaced by
  ++ f(l,r,l1,r1) where l and r are the values at the immediate
  ++ left and right nodes. Values l1 and r1 are values at the
  ++ corresponding nodes of a balanced binary tree t1, of identical
  ++ shape at t.
  ++
  ++X T1:=BalancedBinaryTree Integer
  ++X t2:=balancedBinaryTree(4, 0)$T1
  ++X setleaves!(t2,[1,2,3,4]::List(Integer))
  ++X adder4(i:INT,j:INT,k:INT,l:INT):INT == i+j+k+l
  ++X mapUp!(t2,t2,adder4)
  ++X t2

mapDown_!: (%,S,(S,S) -> S) -> %
  ++ mapDown!(t,p,f) returns t after traversing t in "preorder"
  ++ (node then left then right) fashion replacing the successive
  ++ interior nodes as follows. The root value x is
  ++ replaced by q := f(p,x). The mapDown!(l,q,f) and
  ++ mapDown!(r,q,f) are evaluated for the left and right subtrees
  ++ l and r of t.
  ++
  ++X T1:=BalancedBinaryTree Integer
  ++X t2:=balancedBinaryTree(4, 0)$T1
  ++X setleaves!(t2,[1,2,3,4]::List(Integer))
  ++X adder(i:Integer,j:Integer):Integer == i+j
  ++X mapDown!(t2,4::INT,adder)
  ++X t2

mapDown_!: (%,S, (S,S,S) -> List S) -> %
  ++ mapDown!(t,p,f) returns t after traversing t in "preorder"
  ++ (node then left then right) fashion replacing the successive
  ++ interior nodes as follows. Let l and r denote the left and
  ++ right subtrees of t. The root value x of t is replaced by p.
  ++ Then f(value l, value r, p), where l and r denote the left
  ++ and right subtrees of t, is evaluated producing two values
  ++ pl and pr. Then \spad{mapDown!(l,pl,f)} and \spad{mapDown!(l,pr,f)}
  ++ are evaluated.
  ++
```

```
      ++X T1:=BalancedBinaryTree Integer
      ++X t2:=balancedBinaryTree(4, 0)$T1
      ++X setleaves!(t2,[1,2,3,4]::List(Integer))
      ++X adder3(i:Integer,j:Integer,k:Integer):List Integer == [i+j,j+k]
      ++X mapDown!(t2,4::INT,adder3)
      ++X t2

  Implementation == BinaryTree(S) add
    Rep := BinaryTree(S)
    leaf? x ==
      empty? x => false
      empty? left x and empty? right x
--    balancedBinaryTree(x: S, u: List S) ==
--      n := #u
--      n = 0 => empty()
--      setleaves_!(balancedBinaryTree(n, x), u)
    setleaves_!(t, u) ==
      n := #u
      n = 0 =>
        empty? t => t
        error "the tree and list must have the same number of elements"
      n = 1 =>
        setvalue_!(t,first u)
        t
      m := n quo 2
      acc := empty()$(List S)
      for i in 1..m repeat
        acc := [first u,:acc]
        u := rest u
      setleaves_!(left t, reverse_! acc)
      setleaves_!(right t, u)
      t
    balancedBinaryTree(n: NonNegativeInteger, val: S) ==
      n = 0 => empty()
      n = 1 => node(empty(),val,empty())
      m := n quo 2
      node(balancedBinaryTree(m, val), val,
           balancedBinaryTree((n - m) pretend NonNegativeInteger, val))
    mapUp_!(x,fn) ==
      empty? x => error "mapUp! called on a null tree"
      leaf? x  => x.value
      x.value := fn(mapUp_!(x.left,fn),mapUp_!(x.right,fn))
    mapUp_!(x,y,fn) ==
      empty? x  => error "mapUp! is called on a null tree"
      leaf? x  =>
        leaf? y => x
        error "balanced binary trees are incompatible"
      leaf? y  =>  error "balanced binary trees are incompatible"
      mapUp_!(x.left,y.left,fn)
      mapUp_!(x.right,y.right,fn)
```

```
      x.value := fn(x.left.value,x.right.value,y.left.value,y.right.value)
      x
    mapDown_!(x: %, p: S, fn: (S,S) -> S ) ==
      empty? x => x
      x.value := fn(p, x.value)
      mapDown_!(x.left, x.value, fn)
      mapDown_!(x.right, x.value, fn)
      x
    mapDown_!(x: %, p: S, fn: (S,S,S) -> List S) ==
      empty? x => x
      x.value := p
      leaf? x => x
      u := fn(x.left.value, x.right.value, p)
      mapDown_!(x.left, u.1, fn)
      mapDown_!(x.right, u.2, fn)
      x
```

———-

— BBTREE.dotabb —

```
"BBTREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BBTREE"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"BBTREE" -> "FLAGG"
```

———-

3.2 domain BPADIC BalancedPAdicInteger

— BalancedPAdicInteger.input —

```
)set break resume
)sys rm -f BalancedPAdicInteger.output
)spool BalancedPAdicInteger.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BalancedPAdicInteger
--R
--R BalancedPAdicInteger(p: Integer)  is a domain constructor
--R Abbreviation for BalancedPAdicInteger is BPADIC
--R This constructor is not exposed in this frame.
```

```
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BPADIC
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        associates? : (%,%) -> Boolean
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              complete : % -> %
--R digits : % -> Stream(Integer)         extend : (%,Integer) -> %
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R moduloP : % -> Integer                modulus : () -> Integer
--R one? : % -> Boolean                   order : % -> NonNegativeInteger
--R ?quo? : (%,%) -> %                    quotientByP : % -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R sqrt : (%,Integer) -> %               unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R approximate : (%,Integer) -> Integer
--R characteristic : () -> NonNegativeInteger
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R root : (SparseUnivariatePolynomial(Integer),Integer) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— BalancedPAdicInteger.help —

```
=============================================================================
BalancedPAdicInteger examples
=============================================================================

See Also:
o )show BalancedPAdicInteger
```

———-

3.2.1 BalancedPAdicInteger (BPADIC)



See

⇒ “InnerPAdicInteger” (IPADIC) 10.24.1 on page 1262
⇒ “PAdicInteger” (PADIC) 17.1.1 on page 1847
⇒ “PAdicRationalConstructor” (PADICRC) 17.3.1 on page 1856
⇒ “PAdicRational” (PADICRAT) 17.2.1 on page 1851
⇒ “BalancedPAdicRational” (BPADICRT) 3.3.1 on page 246

Exports:

0	1	approximate	associates?
characteristic	coerce	complete	digits
divide	euclideanSize	expressIdealMember	exquo
extend	extendedEuclidean	gcd	gcdPolynomial
hash	latex	lcm	moduloP
modulus	multiEuclidean	one?	order
principalIdeal	quotientByP	recip	root
sample	sizeLess?	sqrt	subtractIfCan
unit?	unitCanonical	unitNormal	zero?
?~=?	?*?	?**?	?^?
?+?	?-?	-?	?=?
?quo?	?rem?		

— domain BPADIC BalancedPAdicInteger —

```
)abbrev domain BPADIC BalancedPAdicInteger
```

```
++ Author: Clifton J. Williamson
++ Date Created: 15 May 1990
++ Date Last Updated: 15 May 1990
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: p-adic, complementation
++ Examples:
++ References:
++ Description:
++ Stream-based implementation of Zp: p-adic numbers are represented as
++ sum(i = 0.., a[i] * p^i), where the a[i] lie in -(p - 1)/2,...,(p - 1)/2.

BalancedPAdicInteger(p:Integer) == InnerPAdicInteger(p,false$Boolean)
```

———-

— **BPADIC.dotabb** —

```
"BPADIC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BPADIC"]
"PADICCT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PADICCT"]
"BPADIC" -> "PADICCT"
```

———-

3.3 domain BPADICRT BalancedPAdicRational

— **BalancedPAdicRational.input** —

```
)set break resume
)sys rm -f BalancedPAdicRational.output
)spool BalancedPAdicRational.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BalancedPAdicRational
--R
--R BalancedPAdicRational(p: Integer)  is a domain constructor
--R Abbreviation for BalancedPAdicRational is BPADICRT
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BPADICRT
```

```
--R
--R------------------------------- Operations --------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean        coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              denominator : % -> %
--R factor : % -> Factored(%)             gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R numerator : % -> %                    one? : % -> Boolean
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R removeZeroes : (Integer,%) -> %       removeZeroes : % -> %
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)         squareFreePart : % -> %
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,BalancedPAdicInteger(p)) -> %
--R ?*? : (BalancedPAdicInteger(p),%) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (BalancedPAdicInteger(p),BalancedPAdicInteger(p)) -> %
--R ?<? : (%,%) -> Boolean if BalancedPAdicInteger(p) has ORDSET
--R ?<=? : (%,%) -> Boolean if BalancedPAdicInteger(p) has ORDSET
--R ?>? : (%,%) -> Boolean if BalancedPAdicInteger(p) has ORDSET
--R ?>=? : (%,%) -> Boolean if BalancedPAdicInteger(p) has ORDSET
--R D : (%,(BalancedPAdicInteger(p) -> BalancedPAdicInteger(p))) -> %
--R D : (%,(BalancedPAdicInteger(p) -> BalancedPAdicInteger(p)),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if BalancedPAdicInteger(p) has PDRING(SYM
--R D : (%,Symbol,NonNegativeInteger) -> % if BalancedPAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if BalancedPAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if BalancedPAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if BalancedPAdicInteger(p) has DIFRING
--R D : % -> % if BalancedPAdicInteger(p) has DIFRING
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if BalancedPAdicInteger(p) has OINTDOM
--R approximate : (%,Integer) -> Fraction(Integer)
--R ceiling : % -> BalancedPAdicInteger(p) if BalancedPAdicInteger(p) has INS
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and BalancedPAdicInteger(p) has PFECAT o
--R coerce : Symbol -> % if BalancedPAdicInteger(p) has RETRACT(SYMBOL)
--R coerce : BalancedPAdicInteger(p) -> %
```

```
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and BalancedPAdicInteger(p) has PFE
--R continuedFraction : % -> ContinuedFraction(Fraction(Integer))
--R convert : % -> DoubleFloat if BalancedPAdicInteger(p) has REAL
--R convert : % -> Float if BalancedPAdicInteger(p) has REAL
--R convert : % -> InputForm if BalancedPAdicInteger(p) has KONVERT(INFORM)
--R convert : % -> Pattern(Float) if BalancedPAdicInteger(p) has KONVERT(PATTERN(FLOAT))
--R convert : % -> Pattern(Integer) if BalancedPAdicInteger(p) has KONVERT(PATTERN(INT))
--R denom : % -> BalancedPAdicInteger(p)
--R differentiate : (%,(BalancedPAdicInteger(p) -> BalancedPAdicInteger(p))) -> %
--R differentiate : (%,(BalancedPAdicInteger(p) -> BalancedPAdicInteger(p)),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if BalancedPAdicInteger(p) has PDRING(SY
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if BalancedPAdicInteger(p) has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if BalancedPAdicInteger(p) has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if BalancedPAdicInteger(p) has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if BalancedPAdicInteger(p) has DIFRING
--R differentiate : % -> % if BalancedPAdicInteger(p) has DIFRING
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R ?.? : (%,BalancedPAdicInteger(p)) -> % if BalancedPAdicInteger(p) has ELTAB(BPADIC(p),BPADIC(p))
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,Symbol,BalancedPAdicInteger(p)) -> % if BalancedPAdicInteger(p) has IEVALAB(SYMBOL,BPADIC(p))
--R eval : (%,List(Symbol),List(BalancedPAdicInteger(p))) -> % if BalancedPAdicInteger(p) has IEVALAB(SYMBO
--R eval : (%,List(Equation(BalancedPAdicInteger(p)))) -> % if BalancedPAdicInteger(p) has EVALAB(BPADIC(p)
--R eval : (%,Equation(BalancedPAdicInteger(p))) -> % if BalancedPAdicInteger(p) has EVALAB(BPADIC(p))
--R eval : (%,BalancedPAdicInteger(p),BalancedPAdicInteger(p)) -> % if BalancedPAdicInteger(p) has EVALAB(BP
--R eval : (%,List(BalancedPAdicInteger(p)),List(BalancedPAdicInteger(p))) -> % if BalancedPAdicInteger(p) h
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if BalancedP
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if
--R floor : % -> BalancedPAdicInteger(p) if BalancedPAdicInteger(p) has INS
--R fractionPart : % -> % if BalancedPAdicInteger(p) has EUCDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynom
--R init : () -> % if BalancedPAdicInteger(p) has STEP
--R map : ((BalancedPAdicInteger(p) -> BalancedPAdicInteger(p)),%) -> %
--R max : (%,%) -> % if BalancedPAdicInteger(p) has ORDSET
--R min : (%,%) -> % if BalancedPAdicInteger(p) has ORDSET
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R negative? : % -> Boolean if BalancedPAdicInteger(p) has OINTDOM
--R nextItem : % -> Union(%,"failed") if BalancedPAdicInteger(p) has STEP
--R numer : % -> BalancedPAdicInteger(p)
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if Balance
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if Ba
--R positive? : % -> Boolean if BalancedPAdicInteger(p) has OINTDOM
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if BalancedPAdicInteger(p) has INS
--R reducedSystem : Matrix(%) -> Matrix(BalancedPAdicInteger(p))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(BalancedPAdicInteger(p)),vec: Vector(Balance
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if BalancedP
```

```
--R reducedSystem : Matrix(%) -> Matrix(Integer) if BalancedPAdicInteger(p) has LINEXP(INT)
--R retract : % -> Integer if BalancedPAdicInteger(p) has RETRACT(INT)
--R retract : % -> Fraction(Integer) if BalancedPAdicInteger(p) has RETRACT(INT)
--R retract : % -> Symbol if BalancedPAdicInteger(p) has RETRACT(SYMBOL)
--R retract : % -> BalancedPAdicInteger(p)
--R retractIfCan : % -> Union(Integer,"failed") if BalancedPAdicInteger(p) has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if BalancedPAdicInteger(p) has RETRACT
--R retractIfCan : % -> Union(Symbol,"failed") if BalancedPAdicInteger(p) has RETRACT(SYMBOL)
--R retractIfCan : % -> Union(BalancedPAdicInteger(p),"failed")
--R sign : % -> Integer if BalancedPAdicInteger(p) has OINTDOM
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynom
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R wholePart : % -> BalancedPAdicInteger(p) if BalancedPAdicInteger(p) has EUCDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— **BalancedPAdicRational.help** —

```
=====================================================================
BalancedPAdicRational examples
=====================================================================

See Also:
o )show BalancedPAdicRational
```

———-

3.3.1 BalancedPAdicRational (BPADICRT)



See

⇒ "InnerPAdicInteger" (IPADIC) 10.24.1 on page 1262
⇒ "PAdicInteger" (PADIC) 17.1.1 on page 1847
⇒ "BalancedPAdicInteger" (BPADIC) 3.2.1 on page 242
⇒ "PAdicRationalConstructor" (PADICRC) 17.3.1 on page 1856
⇒ "PAdicRational" (PADICRAT) 17.2.1 on page 1851

Exports:

0	1	abs
approximate	associates?	ceiling
characteristic	charthRoot	coerce
conditionP	continuedFraction	convert
D	denom	denominator
differentiate	divide	?.?
euclideanSize	eval	expressIdealMember
exquo	extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial	floor
fractionPart	gcd	gcdPolynomial
hash	init	inv
latex	lcm	map
max	min	multiEuclidean
negative?	nextItem	numer
numerator	one?	patternMatch
positive?	prime?	principalIdeal
random	recip	reducedSystem
removeZeroes	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
zero?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?quo?
?rem?		

— domain BPADICRT BalancedPAdicRational —

```
)abbrev domain BPADICRT BalancedPAdicRational
++ Author: Clifton J. Williamson
++ Date Created: 15 May 1990
++ Date Last Updated: 15 May 1990
++ Keywords: p-adic, complementation
++ Basic Operations:
++ Related Domains:
```

```
++ Also See:
++ AMS Classifications:
++ Keywords: p-adic, completion
++ Examples:
++ References:
++ Description:
++ Stream-based implementation of Qp: numbers are represented as
++ sum(i = k.., a[i] * p^i), where the a[i] lie in -(p - 1)/2,...,(p - 1)/2.

BalancedPAdicRational(p:Integer) ==
  PAdicRationalConstructor(p,BalancedPAdicInteger p)
```

———-

— BPADICRT.dotabb —

```
"BPADICRT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BPADICRT"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"BPADICRT" -> "PFECAT"
```

———-

3.4 domain BFUNCT BasicFunctions

— BasicFunctions.input —

```
)set break resume
)sys rm -f BasicFunctions.output
)spool BasicFunctions.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BasicFunctions
--R
--R BasicFunctions  is a domain constructor
--R Abbreviation for BasicFunctions is BFUNCT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BFUNCT
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean               bfKeys : () -> List(Symbol)
--R coerce : % -> OutputForm             hash : % -> SingleInteger
```

```
--R latex : % -> String                    ?~=? : (%,%) -> Boolean
--R bfEntry : Symbol -> Record(zeros: Stream(DoubleFloat),ones: Stream(DoubleFloat),singularities: Stream(D
--R
--E 1

)spool
)lisp (bye)
```

———-


— **BasicFunctions.help** —

```
=====================================================================
BasicFunctions examples
=====================================================================

See Also:
o )show BasicFunctions
```

———-

3.4.1 BasicFunctions (BFUNCT)



Exports:

bfEntry	bfKeys	coerce	hash	latex
?~=?	?=?			

— **domain BFUNCT BasicFunctions** —

```
)abbrev domain BFUNCT BasicFunctions
++ Author: Brian Dupee
++ Date Created: August 1994
++ Date Last Updated: April 1996
++ Basic Operations: bfKeys, bfEntry
```

```
++ Description:
++ A Domain which implements a table containing details of
++ points at which particular functions have evaluation problems.

BasicFunctions():  E == I where
  DF  ==> DoubleFloat
  SDF ==> Stream DoubleFloat
  RS  ==> Record(zeros: SDF, ones: SDF, singularities: SDF)

  E ==> SetCategory with
    bfKeys:() -> List Symbol
      ++ bfKeys() returns the names of each function in the
      ++ \axiomType{BasicFunctions} table
    bfEntry:Symbol -> RS
      ++ bfEntry(k) returns the entry in the \axiomType{BasicFunctions} table
      ++ corresponding to \spad{k}
    finiteAggregate

  I ==> add

    Rep := Table(Symbol,RS)
    import Rep, SDF

    f(x:DF):DF ==
      positive?(x) => -x
      -x+1

    bf():$ ==
      import RS
      dpi := pi()$DF
      ndpi:SDF := map(x1+->x1*dpi,(z := generate(f,0))) -- [n pi for n in Z]
      n1dpi:SDF := map(x1+->-(2*(x1)-1)*dpi/2,z) -- [(n+1) pi /2]
      n2dpi:SDF := map(x1+->2*x1*dpi,z) -- [2 n pi for n in Z]
      n3dpi:SDF := map(x1+->-(4*(x1)-1)*dpi/4,z)
      n4dpi:SDF := map(x1+->-(4*(x1)-1)*dpi/2,z)
      sinEntry:RS := [ndpi, n4dpi, empty()$SDF]
      cosEntry:RS := [n1dpi, n2dpi, esdf := empty()$SDF]
      tanEntry:RS := [ndpi, n3dpi, n1dpi]
      asinEntry:RS := [construct([0$DF])$SDF,
                       construct([float(8414709848078965,-16,10)$DF]), esdf]
      acosEntry:RS := [construct([1$DF])$SDF,
                       construct([float(54030230586813977,-17,10)$DF]), esdf]
      atanEntry:RS := [construct([0$DF])$SDF,
                       construct([float(15574077246549023,-16,10)$DF]), esdf]
      secEntry:RS := [esdf, n2dpi, n1dpi]
      cscEntry:RS := [esdf, n4dpi, ndpi]
      cotEntry:RS := [n1dpi, n3dpi, ndpi]
      logEntry:RS := [construct([1$DF])$SDF,esdf, construct([0$DF])$SDF]
      entryList:List(Record(key:Symbol,entry:RS)) :=
         [[sin@Symbol, sinEntry], [cos@Symbol, cosEntry],
```

```
           [tan@Symbol, tanEntry], [sec@Symbol, secEntry],
            [csc@Symbol, cscEntry], [cot@Symbol, cotEntry],
             [asin@Symbol, asinEntry], [acos@Symbol, acosEntry],
              [atan@Symbol, atanEntry], [log@Symbol, logEntry]]
      construct(entryList)$Rep

    bfKeys():List Symbol == keys(bf())$Rep

    bfEntry(k:Symbol):RS == qelt(bf(),k)$Rep
```

———-

— **BFUNCT.dotabb** —

```
"BFUNCT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BFUNCT"]
"FIELD-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FIELD"]
"BFUNCT" -> "FIELD-"
```

———-

3.5 domain BOP BasicOperator

— **BasicOperator.input** —

```
)set break resume
)sys rm -f BasicOperator.output
)spool BasicOperator.output
)set message test on
)set message auto off
)clear all
--S 1 of 18
y := operator 'y
--R
--R
--R   (1)  y
--R                                                    Type: BasicOperator
--E 1

--S 2 of 18
deq := D(y x, x, 2) + D(y x, x) + y x = 0
--R
--R
--R         ,,       ,
--R   (2)  y  (x) + y (x) + y(x)= 0
```

```
--R
--R                                          Type: Equation(Expression(Integer))
--E 2

--S 3 of 18
solve(deq, y, x)
--R
--R
--R                                                x     x
--R                                          +-+   - -   - -      +-+
--R                                         x\|3      2     2    x\|3
--R   (3)  [particular= 0,basis= [cos(-----)%e   ,%e   sin(-----)]]
--R                                           2                   2
--IType: Union(Record(particular: Expression(Integer),basis: ...
--E 3

--S 4 of 18
nary? y
--R
--R
--R   (4)  true
--R                                                                  Type: Boolean
--E 4

--S 5 of 18
unary? y
--R
--R
--R   (5)  false
--R                                                                  Type: Boolean
--E 5

--S 6 of 18
opOne := operator('opOne, 1)
--R
--R
--R   (6)  opOne
--R                                                              Type: BasicOperator
--E 6

--S 7 of 18
nary? opOne
--R
--R
--R   (7)  false
--R                                                                  Type: Boolean
--E 7

--S 8 of 18
unary? opOne
```

```
--R
--R
--R   (8)  true
--R                                                              Type: Boolean
--E 8

--S 9 of 18
arity opOne
--R
--R
--R   (9)  1
--R                                          Type: Union(NonNegativeInteger,...)
--E 9

--S 10 of 18
name opOne
--R
--R
--R   (10)  opOne
--R                                                               Type: Symbol
--E 10

--S 11 of 18
is?(opOne, 'z2)
--R
--R
--R   (11)  false
--R                                                              Type: Boolean
--E 11

--S 12 of 18
is?(opOne, "opOne")
--R
--R
--R   (12)  true
--R                                                              Type: Boolean
--E 12

--S 13 of 18
properties y
--R
--R
--R   (13)  table()
--R                                           Type: AssociationList(String,None)
--E 13

--S 14 of 18
setProperty(y, "use", "unknown function" :: None )
--R
--R
```

```
--R   (14)  y
--R                                                    Type: BasicOperator
--E 14

--S 15 of 18
properties y
--R
--R
--R   (15)  table("use"= NONE)
--R                                          Type: AssociationList(String,None)
--E 15

--S 16 of 18
property(y, "use") :: None pretend String
--R
--R
--R   (16)  "unknown function"
--R                                                          Type: String
--E 16

--S 17 of 18
deleteProperty!(y, "use")
--R
--R
--R   (17)  y
--R                                                    Type: BasicOperator
--E 17

--S 18 of 18
properties y
--R
--R
--R   (18)  table()
--R                                          Type: AssociationList(String,None)
--E 18
)spool
)lisp (bye)
```

———-

— BasicOperator.help —

```
====================================================================
BasicOperator examples
====================================================================

A basic operator is an object that can be symbolically applied to a
list of arguments from a set, the result being a kernel over that set
or an expression.
```

```
You create an object of type BasicOperator by using the operator
operation.  This first form of this operation has one argument and it
must be a symbol.  The symbol should be quoted in case the name has
been used as an identifier to which a value has been assigned.

A frequent application of BasicOperator is the creation of an operator
to represent the unknown function when solving a differential equation.

Let y be the unknown function in terms of x.

  y := operator 'y
   y
                      Type: BasicOperator

This is how you enter the equation y'' + y' + y = 0.

  deq := D(y x, x, 2) + D(y x, x) + y x = 0
    ,,       ,
   y  (x) + y (x) + y(x) = 0
                      Type: Equation Expression Integer

To solve the above equation, enter this.

  solve(deq, y, x)
                                        x     x
                                +-+   - -   - -      +-+
                               x\|3     2     2    x\|3
   [particular= 0,basis= [cos(-----)%e   ,%e   sin(-----)]]
                                 2                    2
                      Type: Union(Record(particular: Expression Integer,
                                  basis: List Expression Integer),...)

Use the single argument form of BasicOperator (as above) when you
intend to use the operator to create functional expressions with an
arbitrary number of arguments

Nary means an arbitrary number of arguments can be used in the
functional expressions.

  nary? y
   true
                      Type: Boolean

  unary? y
   false
                      Type: Boolean

Use the two-argument form when you want to restrict the number of
arguments in the functional expressions created with the operator.
```

```
This operator can only be used to create functional expressions
with one argument.

  opOne := operator('opOne, 1)
   opOne
                      Type: BasicOperator

  nary? opOne
   false
                      Type: Boolean

  unary? opOne
   true
                      Type: Boolean

Use arity to learn the number of arguments that can be used.  It
returns "false" if the operator is nary.

  arity opOne
   1
                      Type: Union(NonNegativeInteger,...)

Use name to learn the name of an operator.

  name opOne
   opOne
                      Type: Symbol

Use is? to learn if an operator has a particular name.

  is?(opOne, 'z2)
   false
                      Type: Boolean

You can also use a string as the name to be tested against.

  is?(opOne, "opOne")
   true
                      Type: Boolean

You can attached named properties to an operator.  These are rarely
used at the top-level of the Axiom interactive environment but are
used with Axiom library source code.

By default, an operator has no properties.

  properties y
   table()
                      Type: AssociationList(String,None)
```

```
The interface for setting and getting properties is somewhat awkward
because the property values are stored as values of type None.

Attach a property by using setProperty.

  setProperty(y, "use", "unknown function" :: None )
   y
                      Type: BasicOperator

  properties y
   table("use"=NONE)
                      Type: AssociationList(String,None)

We know the property value has type String.

  property(y, "use") :: None pretend String
   "unknown function"
                      Type: String

Use deleteProperty! to destructively remove a property.


 deleteProperty!(y, "use")
  y
                      Type: BasicOperator

  properties y
   table()
                      Type: AssociationList(String,None)


See Also
o )help Expression
o )help Kernel
o )show BasicOperator
```

———-

3.5.1 BasicOperator (BOP)



Exports:

arity	assert	coerce	comparison	copy
deleteProperty!	display	display	display	equality
has?	hash	input	input	is?
latex	max	min	name	nary?
nullary?	operator	operator	properties	property
setProperties	setProperty	unary?	weight	weight
?~=?	?<?	?<=?	?=?	?>?
?>=?				

— domain BOP BasicOperator —

```
)abbrev domain BOP BasicOperator
++ Author: Manuel Bronstein
++ Date Created: 22 March 1988
++ Date Last Updated: 11 October 1993
++ Keywords: operator, kernel.
++ Description:
++ Basic system operators.
++ A basic operator is an object that can be applied to a list of
++ arguments from a set, the result being a kernel over that set.

BasicOperator(): Exports == Implementation where
  O   ==> OutputForm
  P   ==> AssociationList(String, None)
  L   ==> List Record(key:String, entry:None)
  SEX ==> InputForm
-- some internal properties
  LESS?   ==> "%less?"
  EQUAL?  ==> "%equal?"
  WEIGHT  ==> "%weight"
  DISPLAY ==> "%display"
  SEXPR   ==> "%input"

  Exports ==> OrderedSet with
```

```
name      : $ -> Symbol
  ++ name(op) returns the name of op.
properties: $ -> P
  ++ properties(op) returns the list of all the properties
  ++ currently attached to op.
copy      : $ -> $
  ++ copy(op) returns a copy of op.
operator  : Symbol -> $
  ++ operator(f) makes f into an operator with arbitrary arity.
operator  : (Symbol, NonNegativeInteger) -> $
  ++ operator(f, n) makes f into an n-ary operator.
arity     : $ -> Union(NonNegativeInteger, "failed")
  ++ arity(op) returns n if op is n-ary, and
  ++ "failed" if op has arbitrary arity.
nullary?  : $ -> Boolean
  ++ nullary?(op) tests if op is nullary.
unary?    : $ -> Boolean
  ++ unary?(op) tests if op is unary.
nary?     : $ -> Boolean
  ++ nary?(op) tests if op has arbitrary arity.
weight    : $ -> NonNegativeInteger
  ++ weight(op) returns the weight attached to op.
weight    : ($, NonNegativeInteger) -> $
  ++ weight(op, n) attaches the weight n to op.
equality  : ($, ($, $) -> Boolean) -> $
  ++ equality(op, foo?) attaches foo? as the "%equal?" property
  ++ to op. If op1 and op2 have the same name, and one of them
  ++ has an "%equal?" property f, then \spad{f(op1, op2)} is called to
  ++ decide whether op1 and op2 should be considered equal.
comparison : ($, ($, $) -> Boolean) -> $
  ++ comparison(op, foo?) attaches foo? as the "%less?" property
  ++ to op. If op1 and op2 have the same name, and one of them
  ++ has a "%less?" property f, then \spad{f(op1, op2)} is called to
  ++ decide whether \spad{op1 < op2}.
display   : $ -> Union(List O -> O, "failed")
  ++ display(op) returns the "%display" property of op if
  ++ it has one attached, and "failed" otherwise.
display   : ($, List O -> O)      -> $
  ++ display(op, foo) attaches foo as the "%display" property
  ++ of op. If op has a "%display" property f, then \spad{op(a1,...,an)}
  ++ gets converted to OutputForm as \spad{f(a1,...,an)}.
display   : ($, O -> O)           -> $
  ++ display(op, foo) attaches foo as the "%display" property
  ++ of op. If op has a "%display" property f, then \spad{op(a)}
  ++ gets converted to OutputForm as \spad{f(a)}.
  ++ Argument op must be unary.
input     : ($, List SEX -> SEX)  -> $
  ++ input(op, foo) attaches foo as the "%input" property
  ++ of op. If op has a "%input" property f, then \spad{op(a1,...,an)}
  ++ gets converted to InputForm as \spad{f(a1,...,an)}.
```

```
    input      : $ -> Union(List SEX -> SEX, "failed")
      ++ input(op) returns the "%input" property of op if
      ++ it has one attached, "failed" otherwise.
    is?        : ($, Symbol) -> Boolean
      ++ is?(op, s) tests if the name of op is s.
    has?       : ($, String) -> Boolean
      ++ has?(op, s) tests if property s is attached to op.
    assert     : ($, String) -> $
      ++ assert(op, s) attaches property s to op.
      ++ Argument op is modified "in place", i.e. no copy is made.
    deleteProperty_!: ($, String) -> $
      ++ deleteProperty!(op, s) unattaches property s from op.
      ++ Argument op is modified "in place", i.e. no copy is made.
    property      : ($, String) -> Union(None, "failed")
      ++ property(op, s) returns the value of property s if
      ++ it is attached to op, and "failed" otherwise.
    setProperty   : ($, String, None) -> $
      ++ setProperty(op, s, v) attaches property s to op,
      ++ and sets its value to v.
      ++ Argument op is modified "in place", i.e. no copy is made.
    setProperties : ($, P) -> $
      ++ setProperties(op, l) sets the property list of op to l.
      ++ Argument op is modified "in place", i.e. no copy is made.

  Implementation ==> add
    -- if narg < 0 then the operator has variable arity.
    Rep := Record(opname:Symbol, narg:SingleInteger, props:P)

    oper: (Symbol, SingleInteger, P) -> $

    is?(op, s)           == name(op) = s
    name op              == op.opname
    properties op        == op.props
    setProperties(op, l) == (op.props := l; op)
    operator s           == oper(s, -1::SingleInteger, table())
    operator(s, n)       == oper(s, n::Integer::SingleInteger, table())
    property(op, name)   == search(name, op.props)
    assert(op, s)        == setProperty(op, s, NIL$Lisp)
    has?(op, name)       == key?(name, op.props)
    oper(se, n, prop)    == [se, n, prop]
    weight(op, n)        == setProperty(op, WEIGHT, n pretend None)
    nullary? op          == zero?(op.narg)
--    unary? op            == one?(op.narg)
    unary? op            == ((op.narg) = 1)
    nary? op             == negative?(op.narg)
    equality(op, func)   == setProperty(op, EQUAL?, func pretend None)
    comparison(op, func) == setProperty(op, LESS?, func pretend None)
    display(op:$, f:O -> O)        == display(op,(x1:List(O)):O +-> f first x1)
    deleteProperty_!(op, name)     == (remove_!(name, properties op); op)
    setProperty(op, name, valu)    == (op.props.name := valu; op)
```

```
    coerce(op:$):OutputForm        == name(op)::OutputForm
    input(op:$, f:List SEX -> SEX) == setProperty(op, SEXPR, f pretend None)
    display(op:$, f:List O -> O)   == setProperty(op, DISPLAY, f pretend None)

    display op ==
      (u := property(op, DISPLAY)) case "failed" => "failed"
      (u::None) pretend (List O -> O)

    input op ==
      (u := property(op, SEXPR)) case "failed" => "failed"
      (u::None) pretend (List SEX -> SEX)

    arity op ==
      negative?(n := op.narg) => "failed"
      convert(n)@Integer :: NonNegativeInteger

    copy op ==
      oper(name op, op.narg,
          table([[r.key, r.entry] for r in entries(properties op)@L]$L))

-- property EQUAL? contains a function f: (BOP, BOP) -> Boolean
-- such that f(o1, o2) is true iff o1 = o2
    op1 = op2 ==
      (EQ$Lisp)(op1, op2) => true
      name(op1) ^= name(op2) => false
      op1.narg ^= op2.narg => false
      brace(keys properties op1)^=$Set(String) _
                     brace(keys properties op2) => false
      (func := property(op1, EQUAL?)) case None =>
                   ((func::None) pretend (($, $) -> Boolean)) (op1, op2)
      true

-- property WEIGHT allows one to change the ordering around
-- by default, every operator has weigth 1
    weight op ==
      (w := property(op, WEIGHT)) case "failed" => 1
      (w::None) pretend NonNegativeInteger

-- property LESS? contains a function f: (BOP, BOP) -> Boolean
-- such that f(o1, o2) is true iff o1 < o2
    op1 < op2 ==
      (w1 := weight op1) ^= (w2 := weight op2) => w1 < w2
      op1.narg ^= op2.narg => op1.narg < op2.narg
      name(op1) ^= name(op2) => name(op1) < name(op2)
      n1 := #(k1 := brace(keys(properties op1))$Set(String))
      n2 := #(k2 := brace(keys(properties op2))$Set(String))
      n1 ^= n2 => n1 < n2
      not zero?(n1 := #(d1 := difference(k1, k2))) =>
        n1 ^= (n2 := #(d2 := difference(k2, k1))) => n1 < n2
        inspect(d1) < inspect(d2)
```

```
      (func := property(op1, LESS?)) case None =>
                  ((func::None) pretend (($, $) -> Boolean)) (op1, op2)
      (func := property(op1, EQUAL?)) case None =>
             not(((func::None) pretend (($, $) -> Boolean)) (op1, op2))
      false
```

———-

— **BOP.dotabb** —

```
"BOP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BOP"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"BOP" -> "ALIST"
```

———-

3.6 domain BSD BasicStochasticDifferential

— **BasicStochasticDifferential.input** —

```
)set break resume
)sys rm -f BasicStochasticDifferential.output
)spool BasicStochasticDifferential.output
)set message test on
)set message auto off
)clear all

--S 1 of 30
print copyBSD()
--R
--R   []
--R                                                              Type: Void
--E 1

--S 2 of 30
print copyIto()
--R
--R   table()
--R                                                              Type: Void
--E 2

--S 3 of 30
dX:=introduce!(X,dX) -- dX is a new stochastic differential
--R
```

```
--R
--R   (3)  dX
--R                                Type: Union(BasicStochasticDifferential,...)
--E 3

--S 4 of 30
print copyBSD()
--R
--R   [dX]
--R                                                                Type: Void
--E 4

--S 5 of 30
print copyIto()
--R
--R   table(X= dX)
--R                                                                Type: Void
--E 5

--S 6 of 30
getSmgl(dX)
--R
--R
--R   (6)  X
--R                                                  Type: Union(Symbol,...)
--E 6

--S 7 of 30
print dX
--R
--R   dX
--R                                                                Type: Void
--E 7

--S 8 of 30
print domainOf(dX)
--R
--R   BasicStochasticDifferential()
--R                                                                Type: Void
--E 8

--S 9 of 30
print d X
--R
--R   dX
--R                                                                Type: Void
--E 9

--S 10 of 30
print ((d$BSD) X)
```

```
--R
--R   dX
--R                                                                    Type: Void
--E 10

--S 11 of 30
print domainOf((d$BSD) X)
--R
--R   BasicStochasticDifferential()
--R                                                                    Type: Void
--E 11

--S 12 of 30
introduce!(t,dt) -- dt is a new stochastic differential
--R
--R
--R   (12)  dt
--R                                 Type: Union(BasicStochasticDifferential,...)
--E 12

--S 13 of 30
print copyBSD()
--R
--R   [dX,dt]
--R                                                                    Type: Void
--E 13

--S 14 of 30
print copyIto()
--R
--R   table(t= dt,X= dX)
--R                                                                    Type: Void
--E 14

--S 15 of 30
introduce!(t,dt) -- fails (can't repeat an introduction!)
--R
--R
--R   (15)  "failed"
--R                                                  Type: Union("failed",...)
--E 15

--S 16 of 30
print copyBSD()
--R
--R   [dX,dt]
--R                                                                    Type: Void
--E 16

--S 17 of 30
```

```
print copyIto()
--R
--R   table(t= dt,X= dX)
--R                                                                    Type: Void
--E 17

--S 18 of 30
'dZ::BSD           -- can fail
--R
--R   dZ is not a stochastic differential
--R
--RDaly Bug
--R   >> Error detected within library code:
--R   above causes failure in convert$BSD
--R
--R   Continuing to read the file...
--R
--E 18

--S 19 of 30
dZ::BSD            -- fails
--R
--R   dZ is not a stochastic differential
--R
--RDaly Bug
--R   >> Error detected within library code:
--R   above causes failure in convert$BSD
--R
--R   Continuing to read the file...
--R
--E 19

--S 20 of 30
string(dY)::BSD    -- fails
--R
--R
--RDaly Bug
--R   Cannot convert from type String to BasicStochasticDifferential for
--R      value
--R   "dY"
--R
--E 20

--S 21 of 30
print domainOf(dt)
--R
--R   Variable(dt)
--R                                                                    Type: Void
--E 21
```

```
--S 22 of 30
dt::BSD            -- succeeds!
--R
--R
--R   (19)  dt
--R                                          Type: BasicStochasticDifferential
--E 22

--S 23 of 30
getSmgl(dt::BSD)
--R
--R
--R   (20)  t
--R                                                  Type: Union(Symbol,...)
--E 23

--S 24 of 30
dX::Symbol         -- succeeds
--R
--R
--R   (21)  dX
--R                                                             Type: Symbol
--E 24

--S 25 of 30
string(dX)         -- fails
--R
--R   There are 3 exposed and 1 unexposed library operations named string
--R      having 1 argument(s) but none was determined to be applicable.
--R      Use HyperDoc Browse, or issue
--R                              )display op string
--R      to learn more about the available operations. Perhaps
--R      package-calling the operation or using coercions on the arguments
--R      will allow you to apply the operation.
--R
--RDaly Bug
--R   Cannot find a definition or applicable library operation named
--R      string with argument type(s)
--R                          BasicStochasticDifferential
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--E 25

--S 26 of 30
string(dX::Symbol) -- succeeds
--R
--R
--R   (22)  "dX"
--R                                                             Type: String
```

```
--E 26

--S 27 of 30
[introduce!(A[i],dA[i]) for i in 1..2]
--R
--R
--R   (23)  [dA ,dA ]
--R            1   2
--R                      Type: List(Union(BasicStochasticDifferential,"failed"))
--E 27

--S 28 of 30
print copyBSD()
--R
--R   [dA ,dA ,dX,dt]
--R      1   2
--R                                                              Type: Void
--E 28

--S 29 of 30
print copyIto()
--R
--R   table(A = dA ,A = dA ,t= dt,X= dX)
--R          2    2  1    1
--R                                                              Type: Void
--E 29

--S 30 of 30
[d A[i] for i in 1..2]
--R
--R
--R   (26)  [dA ,dA ]
--R            1   2
--R                       Type: List(Union(BasicStochasticDifferential,Integer))
--E 30


)spool
)lisp (bye)
```

———-

— BasicStochasticDifferential.help —

```
=====================================================================
BasicStochasticDifferential examples
=====================================================================

Based on Symbol: a domain of symbols representing basic stochastic
```

```
differentials, used in StochasticDifferential(R) in the underlying
sparse multivariate polynomial representation.

We create new BSD only by coercion from Symbol using a special
function introduce! first of all to add to a private set SDset. We
allow a separate function convertIfCan which will check whether the
argument has previously been declared as a BSD.

The copyBSD() returns setBSD as a list of BSD.
Initially the BSD table of symbols is empty:
   print copyBSD()
      []

as is the Ito table. The copyIto() returns the table relating
semimartingales to basic stochastic differentials.
   print copyIto()
      table()

We introduce a new stochastic differential:
   dX:=introduce!(X,dX) -- dX is a new stochastic differential
      dX

and now it is in the BSD table of symbols:
   print copyBSD()
      [dX]

and the Ito table:
   print copyIto()
      table(X= dX)


The getSmgl(bsd) returns the semimartingale S related to the basic
stochastic differential bsd by introduce!:
   getSmgl(dX)
      X

Note that the dX symbol is of type BasicStochasticDifferential:
   print domainOf(dX)
     BasicStochasticDifferential()

The d function, d(X) returns dX if tableIto(X)=dX otherwise 0:
   print d X
      dX

and we can specify the domain:
   print ((d$BSD) X)
      dX

which clearly is of domain BasicStochasticDifferential
   print domainOf((d$BSD) X)
```

```
      BasicStochasticDifferential()

The introduce!(X,dX) returns dX as BSD if it isn't already in BSD
   introduce!(t,dt) -- dt is a new stochastic differential
       dt

Now we can see that dt is in the BSD table:
   print copyBSD()
       [dX,dt]

and the Ito table:
   print copyIto()
       table(t= dt,X= dX)

You cannot repeat an introduce! for an existing entry:
   introduce!(t,dt)
       "failed"

Regular symbols can be added, especially with subscripts:
   [introduce!(A[i],dA[i]) for i in 1..2]
            [dA ,dA ]
               1   2


And we can see them in the BSD table:
   print copyBSD()
      [dA ,dA ,dX,dt]
         1   2

and the Ito table:
   print copyIto()
      table(A = dA ,A = dA ,t= dt,X= dX)
             2    2  1    1

The d function can extract these symbols:
   [d A[i] for i in 1..2]
       [dA ,dA ]
          1   2

See Also:
o )show BasicStochasticDifferential
```

3.6.1 BasicStochasticDifferential (BSD)



See

⇒ "StochasticDifferential" (SD) 20.29.1 on page 2539

Exports:

coerce	convert	convertIfCan	copyBSD
copyIto	d	getSmgl	hash
introduce!	latex	max	min
?~=?	?<?	?<=?	?=?
?>?	?>=?		

— domain BSD BasicStochasticDifferential —

```
)abbrev domain BSD BasicStochasticDifferential
++ Author: Wilfrid S. Kendall
++ Date Last Updated: July 26, 1999
++ Related Domains: StochasticDifferential(R)
++ Keywords: stochastic differential, semimartingale.
++ References: Ito (1975), Kendall (1991a,b; 1993a,b; 1999a,b).
++ Description:
++ Based on Symbol: a domain of symbols representing basic stochastic
++ differentials, used in StochasticDifferential(R) in the underlying
++ sparse multivariate polynomial representation.
++
++ We create new BSD only by coercion from Symbol using a special
++ function introduce! first of all to add to a private set SDset.
++ We allow a separate function convertIfCan which will check whether the
++ argument has previously been declared as a BSD.

BasicStochasticDifferential(): category == implementation where
 INT ==> Integer
 OF  ==> OutputForm
 category ==> OrderedSet with
  ConvertibleTo(Symbol)

  convertIfCan: Symbol -> Union(%, "failed")
   ++ convertIfCan(ds) transforms \axiom{dX} into a \axiom{BSD}
```

```
   ++ if possible (if \axiom{introduce(X,dX)} has
   ++ been invoked previously).

  convert: Symbol -> %
   ++ convert(dX) transforms \axiom{dX} into a \axiom{BSD}
   ++ if possible and otherwise produces an error.

  introduce!: (Symbol,Symbol) -> Union(%, "failed")
   ++ introduce!(X,dX) returns \axiom{dX} as \axiom{BSD} if it
   ++ isn't already in \axiom{BSD}
   ++
   ++X introduce!(t,dt) -- dt is a new stochastic differential
   ++X copyBSD()

  d: Symbol -> Union(%,INT)
   ++ d(X) returns \axiom{dX} if \axiom{tableIto(X)=dX}
   ++ and otherwise returns \axiom{0}

  copyBSD:() -> List %
   ++ copyBSD() returns \axiom{setBSD} as a list of \axiom{BSD}.
   ++
   ++X introduce!(t,dt) -- dt is a new stochastic differential
   ++X copyBSD()

  copyIto:() -> Table(Symbol,%)
   ++ copyIto() returns the table relating semimartingales
   ++ to basic stochastic differentials.
   ++
   ++X introduce!(t,dt) -- dt is a new stochastic differential
   ++X copyIto()

  getSmgl: % -> Union(Symbol,"failed")
   ++ getSmgl(bsd) returns the semimartingale \axiom{S} related
   ++ to the basic stochastic differential \axiom{bsd} by
   ++ \axiom{introduce!}
   ++
   ++X introduce!(t,dt) -- dt is a new stochastic differential
   ++X getSmgl(dt::BSD)

 implementation ==> Symbol add

  Rep := Symbol

  setBSD := empty()$Set(Symbol)
  tableIto:Table(Symbol,%) := table()
  tableBSD:Table(%,Symbol) := table()

  convertIfCan(ds:Symbol):Union(%,"failed") ==
   not(member?(ds,setBSD)) => "failed"
   ds::%
```

```
  convert(ds:Symbol):% ==
   (du:=convertIfCan(ds))
    case "failed" =>
     print(hconcat(ds::Symbol::OF,
       message(" is not a stochastic differential")$OF))
     error "above causes failure in convert$BSD"
   du

  introduce!(X,dX) ==
   member?(dX,setBSD) => "failed"
   insert!(dX,setBSD)
   tableBSD(dX::%) := X
   tableIto(X) := dX::%

  d(X) ==
   search(X,tableIto) case "failed" => 0::INT
   tableIto(X)

  copyBSD() == [ds::% for ds in members(setBSD)]
  copyIto() == tableIto
  getSmgl(ds:%):Union(Symbol,"failed") == tableBSD(ds)
```

———-

— BSD.dotabb —

```
"BSD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BSD"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"BSD" -> "FSAGG"
```

———-

3.7 domain BINARY BinaryExpansion

— BinaryExpansion.input —

```
)set break resume
)sys rm -f BinaryExpansion.output
)spool BinaryExpansion.output
)set message test on
)set message auto off
)clear all
--S 1 of 7
```

```
r := binary(22/7)
--R
--R
--R           ___
--R   (1)  11.001
--R                                                    Type: BinaryExpansion
--E 1

--S 2 of 7
r + binary(6/7)
--R
--R
--R   (2)  100
--R                                                    Type: BinaryExpansion
--E 2

--S 3 of 7
[binary(1/i) for i in 102..106]
--R
--R
--R   (3)
--R       ________    ____________________________________________________
--R   [0.000000101, 0.000000100111110001000101100101111001110010010101001,
--R         ____________    ____________
--R    0.000000100111011, 0.000000100111,
--R       ____________________________________________________
--R    0.000000100110101001000011100111110110010101101111100011]
--R                                                  Type: List(BinaryExpansion)
--E 3

--S 4 of 7
binary(1/1007)
--R
--R
--R   (4)
--R   0.
--R     OVERBAR
--R        000000000100000100010100100101111000001111110000101111110010110001111110
--R          100010011100100110011000110010010101011110110100110000000011000011001
--R          111011100011010001011110100100011110110000101011101110011101010111001
--R          100101001011100000001110001111001000000100100100110111001010100111010
--R          001101110110101110001001000001100101101100000010110010111110001010000
--R          010101010110101100000110110111010010101111111010111010100110010000101
--R          001101100010011000100010000100001100011101001111000 1
--R                                                    Type: BinaryExpansion
--E 4

--S 5 of 7
p := binary(1/4)*x**2 + binary(2/3)*x + binary(4/9)
--R
```

```
--R
--R             2     --      ------
--R   (5)  0.01x  + 0.10x + 0.011100
--R                                                Type: Polynomial(BinaryExpansion)
--E 5

--S 6 of 7
q := D(p, x)
--R
--R
--R                   --
--R   (6)  0.1x + 0.10
--R                                                Type: Polynomial(BinaryExpansion)
--E 6

--S 7 of 7
g := gcd(p, q)
--R
--R
--R                --
--R   (7)  x + 1.01
--R                                                Type: Polynomial(BinaryExpansion)
--E 7
)spool
)lisp (bye)
```

— BinaryExpansion.help —

```
====================================================================
BinaryExpansion examples
====================================================================
All rational numbers have repeating binary expansions.  Operations to
access the individual bits of a binary expansion can be obtained by
converting the value to RadixExpansion(2).  More examples of
expansions are available with

The expansion (of type BinaryExpansion) of a rational number is
returned by the binary operation.

  r := binary(22/7)
      ---
   11.001
                      Type: BinaryExpansion

Arithmetic is exact.

  r + binary(6/7)
```

```
   100
                    Type: BinaryExpansion
```

The period of the expansion can be short or long.

```
  [binary(1/i) for i in 102..106]
     --------
   [0.00000101,
     ----------------------------------------------------
    0.000000100111110001000101100101111001110010010101001,
        ------------    ------------
    0.000000100111011, 0.000000100111,
       ----------------------------------------------------
    0.000000100110101001000011100111110110010101101111100011]
                    Type: List BinaryExpansion
```

or very long.

```
  binary(1/1007)
     ------------------------------------------------------------------------
   0.000000000100000100010100100101111000001111110000101111110010110001111101
     ------------------------------------------------------------------------
     000100111001001100110001100100101010111101101001100000000110000110011110
     ------------------------------------------------------------------------
     111000110100010111101001000111101100001010111011100111010101110011001010
     ------------------------------------------------------------------------
     010111000000011100011110010000001001001001101110010101001110100011011101
     ------------------------------------------------------------------------
     101011100010010000011001011011000000101100101111100010100000101010101101
     ------------------------------------------------------------------------
     011000001101101110100101011111110101110101001100100001010011011000100110
     -------------------------------------
     001000100001000011000111010011110001
                    Type: BinaryExpansion
```

These numbers are bona fide algebraic objects.

```
  p := binary(1/4)*x**2 + binary(2/3)*x + binary(4/9)
                --       ------
   0.01 x^2 +0.10 x + 0.011100
                    Type: Polynomial BinaryExpansion


  q := D(p, x)
              --
   0.1 x + 0.10
                    Type: Polynomial BinaryExpansion

  g := gcd(p, q)
       --
   x+1.01
```

```
                    Type: Polynomial BinaryExpansion

See Also:
o )help DecimalExpansion
o )help HexadecimalExpansion
o )show BinaryExpansion
```

3.7.1 BinaryExpansion (BINARY)



See

⇒ “RadixExpansion” (RADIX) 19.2.1 on page 2171
⇒ “DecimalExpansion” (DECIMAL) 5.3.1 on page 453
⇒ “HexadecimalExpansion” (HEXADEC) 9.3.1 on page 1112

Exports:

0	1	abs
associates?	binary	ceiling
characteristic	charthRoot	coerce
conditionP	convert	D
denom	denominator	differentiate
divide	euclideanSize	eval
expressIdealMember	exquo	extendedEuclidean
factor	factorPolynomial	factorSquareFreePolynomial
floor	fractionPart	gcd
gcdPolynomial	hash	init
inv	latex	lcm
map	max	min
multiEuclidean	negative?	nextItem
numer	numerator	one?
patternMatch	positive?	prime?
principalIdeal	random	recip
reducedSystem	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
zero?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?.?
?quo?	?rem?	

— domain BINARY BinaryExpansion —

```
)abbrev domain BINARY BinaryExpansion
++ Author: Clifton J. Williamson
++ Date Created: April 26, 1990
++ Date Last Updated: May 15, 1991
++ Basic Operations:
++ Related Domains: RadixExpansion
++ Also See:
++ AMS Classifications:
++ Keywords: radix, base, binary
++ Examples:
++ References:
++ Description:
++ This domain allows rational numbers to be presented as repeating
++ binary expansions.

BinaryExpansion(): Exports == Implementation where
  Exports ==> QuotientFieldCategory(Integer) with
    coerce: % -> Fraction Integer
```

```
      ++ coerce(b) converts a binary expansion to a rational number.
    coerce: % -> RadixExpansion(2)
      ++ coerce(b) converts a binary expansion to a radix expansion with base 2.
    fractionPart: % -> Fraction Integer
      ++ fractionPart(b) returns the fractional part of a binary expansion.
    binary: Fraction Integer -> %
      ++ binary(r) converts a rational number to a binary expansion.
      ++
      ++X binary(22/7)

  Implementation ==> RadixExpansion(2) add
    binary r == r :: %
    coerce(x:%): RadixExpansion(2) == x pretend RadixExpansion(2)
```

———-

— BINARY.dotabb —

```
"BINARY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BINARY"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"BINARY" -> "PFECAT"
```

———-

3.8 domain BINFILE BinaryFile

— BinaryFile.input —

```
)set break resume
)sys rm -f BinaryFile.output
)spool BinaryFile.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BinaryFile
--R BinaryFile  is a domain constructor
--R Abbreviation for BinaryFile is BINFILE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BINFILE
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean               close! : % -> %
```

```
--R coerce : % -> OutputForm              flush : % -> Void
--R hash : % -> SingleInteger             iomode : % -> String
--R latex : % -> String                   name : % -> FileName
--R open : (FileName,String) -> %         open : FileName -> %
--R position : % -> SingleInteger         read! : % -> SingleInteger
--R reopen! : (%,String) -> %             ?~=? : (%,%) -> Boolean
--R position! : (%,SingleInteger) -> SingleInteger
--R readIfCan! : % -> Union(SingleInteger,"failed")
--R write! : (%,SingleInteger) -> SingleInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— BinaryFile.help —

```
========================================================================
BinaryFile examples
========================================================================

See Also:
o )show BinaryFile
```

———-

3.8.1 BinaryFile (BINFILE)



See

⇒ “File” (FILE) 7.2.1 on page 772
⇒ “TextFile” (TEXTFILE) 21.5.1 on page 2661
⇒ “KeyedAccessFile” (KAFILE) 12.2.1 on page 1381
⇒ “Library” (LIB) 13.2.1 on page 1396

Exports:

close!	coerce	hash	iomode	latex
name	open	position	position!	read!
readIfCan!	reopen!	write!	?=?	?~=?

— domain BINFILE BinaryFile —

```
)abbrev domain BINFILE BinaryFile
++ Author: Barry M. Trager
++ Date Created: 1993
++ Date Last Updated:
++ Basic Operations: writeByte! readByte! readByteIfCan!
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain provides an implementation of binary files. Data is
++ accessed one byte at a time as a small integer.

BinaryFile: Cat == Def where

    Cat == FileCategory(FileName, SingleInteger) with
        readIfCan_!: % -> Union(SingleInteger, "failed")
            ++ readIfCan!(f) returns a value from the file f, if possible.
            ++ If f is not open for reading, or if f is at the end of file
            ++ then \spad{"failed"} is the result.

--      "#": % -> SingleInteger
--          ++ #(f) returns the length of the file f in bytes.

        position: % -> SingleInteger
            ++ position(f) returns the current byte-position in the file f.

        position_!: (%, SingleInteger) -> SingleInteger
            ++ position!(f, i) sets the current byte-position to i.

    Def == File(SingleInteger) add
        FileState ==> SExpression

        Rep := Record(fileName:   FileName,    _
                      fileState:  FileState,   _
                      fileIOmode: String)

--      direc : Symbol := INTERN("DIRECTION","KEYWORD")$Lisp
--      input : Symbol := INTERN("INPUT","KEYWORD")$Lisp
--      output : Symbol := INTERN("OUTPUT","KEYWORD")$Lisp
--      eltype : Symbol := INTERN("ELEMENT-TYPE","KEYWORD")$Lisp
--      bytesize : SExpression := LIST(QUOTE(UNSIGNED$Lisp)$Lisp,8)$Lisp
```

```
        defstream(fn: FileName, mode: String): FileState ==
            mode = "input"  =>
              not readable? fn => error ["File is not readable", fn]
              BINARY__OPEN__INPUT(fn::String)$Lisp
--            OPEN(fn::String, direc, input, eltype, bytesize)$Lisp
            mode = "output" =>
              not writable? fn => error ["File is not writable", fn]
              BINARY__OPEN__OUTPUT(fn::String)$Lisp
--            OPEN(fn::String, direc, output, eltype, bytesize)$Lisp
            error ["IO mode must be input or output", mode]

        open(fname, mode) ==
            fstream := defstream(fname, mode)
            [fname, fstream, mode]

        reopen_!(f, mode) ==
            fname := f.fileName
            f.fileState := defstream(fname, mode)
            f.fileIOmode:= mode
            f

        close_! f ==
            f.fileIOmode = "output" =>
                 BINARY__CLOSE__OUTPUT()$Lisp
                 f
            f.fileIOmode = "input" =>
                  BINARY__CLOSE__INPUT()$Lisp
                  f
            error "file must be in read or write state"

        read! f ==
            f.fileIOmode ^= "input"  => error "File not in read state"
            BINARY__SELECT__INPUT(f.fileState)$Lisp
            BINARY__READBYTE()$Lisp
--          READ_-BYTE(f.fileState)$Lisp
        readIfCan_! f ==
            f.fileIOmode ^= "input"  => error "File not in read state"
            BINARY__SELECT__INPUT(f.fileState)$Lisp
            n:SingleInteger:=BINARY__READBYTE()$Lisp
            n = -1 => "failed"
            n::Union(SingleInteger,"failed")
--          READ_-BYTE(f.fileState,NIL$Lisp,
--                   "failed"::Union(SingleInteger,"failed"))$Lisp
        write_!(f, x) ==
            f.fileIOmode ^= "output" => error "File not in write state"
            x < 0 or x>255 => error "integer cannot be represented as a byte"
            BINARY__PRINBYTE(x)$Lisp
--          WRITE_-BYTE(x, f.fileState)$Lisp
```

```
            x

--      # f == FILE_-LENGTH(f.fileState)$Lisp
        position f ==
           f.fileIOmode ^= "input"  => error "file must be in read state"
           FILE_-POSITION(f.fileState)$Lisp
        position_!(f,i) ==
           f.fileIOmode ^= "input"  => error "file must be in read state"
           (FILE_-POSITION(f.fileState,i)$Lisp ; i)
```

———-

— BINFILE.dotabb —

```
"BINFILE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BINFILE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"BINFILE" -> "STRING"
```

———-

3.9 domain BSTREE BinarySearchTree

— BinarySearchTree.input —

```
)set break resume
)sys rm -f BinarySearchTree.output
)spool BinarySearchTree.output
)set message test on
)set message auto off
)clear all
--S 1 of 12
lv := [8,3,5,4,6,2,1,5,7]
--R
--R
--R   (1)  [8,3,5,4,6,2,1,5,7]
--R                                                  Type: List(PositiveInteger)
--E 1

--S 2 of 12
t := binarySearchTree lv
--R
--R
--R   (2)  [[[1,2,.],3,[4,5,[5,6,7]]],8,.]
--R                                  Type: BinarySearchTree(PositiveInteger)
```

```
--E 2

--S 3 of 12
emptybst := empty()$BSTREE(INT)
--R
--R
--R   (3)  []
--R                                              Type: BinarySearchTree(Integer)
--E 3

--S 4 of 12
t1 := insert!(8,emptybst)
--R
--R
--R   (4)  8
--R                                              Type: BinarySearchTree(Integer)
--E 4

--S 5 of 12
insert!(3,t1)
--R
--R
--R   (5)  [3,8,.]
--R                                              Type: BinarySearchTree(Integer)
--E 5

--S 6 of 12
leaves t
--R
--R
--R   (6)  [1,4,5,7]
--R                                                 Type: List(PositiveInteger)
--E 6

--S 7 of 12
split(3,t)
--R
--R
--R   (7)  [less= [1,2,.],greater= [[.,3,[4,5,[5,6,7]]],8,.]]
--IType: Record(less: BinarySearchTree(PositiveInteger),greater: ...
--E 7

--S 8 of 12
insertRoot: (INT,BSTREE INT) -> BSTREE INT
--R
--R                                                                  Type: Void
--E 8

--S 9 of 12
insertRoot(x, t) ==
```

```
    a := split(x, t)
    node(a.less, x, a.greater)
--R
--R                                                                   Type: Void
--E 9

--S 10 of 12
buildFromRoot ls == reduce(insertRoot,ls,emptybst)
--R
--R                                                                   Type: Void
--E 10

--S 11 of 12
rt := buildFromRoot reverse lv
--R
--R   Compiling function buildFromRoot with type List(PositiveInteger) ->
--R      BinarySearchTree(Integer)
--R   Compiling function insertRoot with type (Integer,BinarySearchTree(
--R      Integer)) -> BinarySearchTree(Integer)
--R
--R   (11)  [[[1,2,.],3,[4,5,[5,6,7]]],8,.]
--R                                              Type: BinarySearchTree(Integer)
--E 11

--S 12 of 12
(t = rt)@Boolean
--R
--R
--R   (12)  true
--R                                                                 Type: Boolean
--E 12
)spool
)lisp (bye)
```

———-

— BinarySearchTree.help —

```
=====================================================================
BinarySearchTree examples
=====================================================================

BinarySearchTree(R) is the domain of binary trees with elements of
type R, ordered across the nodes of the tree.  A non-empty binary
search tree has a value of type R, and right and left binary search
subtrees.  If a subtree is empty, it is displayed as a period (".").

Define a list of values to be placed across the tree.  The resulting
tree has 8 at the root; all other elements are in the left subtree.
```

```
  lv := [8,3,5,4,6,2,1,5,7]
   [8, 3, 5, 4, 6, 2, 1, 5, 7]
                      Type: List PositiveInteger
```

A convenient way to create a binary search tree is to apply the operation binarySearchTree to a list of elements.

```
  t := binarySearchTree lv
   [[[1, 2, .], 3, [4, 5, [5, 6, 7]]], 8, .]
                      Type: BinarySearchTree PositiveInteger
```

Another approach is to first create an empty binary search tree of integers.

```
  emptybst := empty()$BSTREE(INT)
   []
                      Type: BinarySearchTree Integer
```

Insert the value 8. This establishes 8 as the root of the binary search tree. Values inserted later that are less than 8 get stored in the left subtree, others in the right subtree.

```
  t1 := insert!(8,emptybst)
   8
                      Type: BinarySearchTree Integer
```

Insert the value 3. This number becomes the root of the left subtree of t1. For optimal retrieval, it is thus important to insert the middle elements first.

```
  insert!(3,t1)
   [3, 8, .]
                      Type: BinarySearchTree Integer
```

We go back to the original tree t. The leaves of the binary search tree are those which have empty left and right subtrees.

```
  leaves t
   [1, 4, 5, 7]
                      Type: List PositiveInteger
```

The operation split(k,t) returns a record containing the two subtrees: one with all elements "less" than k, another with elements "greater" than k.

```
  split(3,t)
   [less=[1, 2, .], greater=[[., 3, [4, 5, [5, 6, 7]]], 8, .]]
              Type: Record(less: BinarySearchTree PositiveInteger,greater:
                            BinarySearchTree PositiveInteger)
```

```
Define insertRoot to insert new elements by creating a new node.

  insertRoot: (INT,BSTREE INT) -> BSTREE INT
                      Type: Void

The new node puts the inserted value between its "less" tree and
"greater" tree.


  insertRoot(x, t) ==
    a := split(x, t)
    node(a.less, x, a.greater)
                      Type: Void


Function buildFromRoot builds a binary search tree from a list
of elements ls and the empty tree emptybst.

  buildFromRoot ls == reduce(insertRoot,ls,emptybst)
                      Type: Void

Apply this to the reverse of the list lv.

  rt := buildFromRoot reverse lv
   [[[1, 2, . ], 3, [4, 5, [5, 6, 7]]], 8, .]
                      Type: BinarySearchTree Integer


Have Axiom check that these are equal.

  (t = rt)@Boolean
   true
                      Type: Boolean

See Also:
o )show BinarySearchTree
```

———-

3.9.1 BinarySearchTree (BSTREE)



See

⇒ "Tree" (TREE) 21.10.1 on page 2710
⇒ "BinaryTree" (BTREE) 3.11.1 on page 294
⇒ "BinaryTournament" (BTOURN) 3.10.1 on page 291
⇒ "BalancedBinaryTree" (BBTREE) 3.1.1 on page 236
⇒ "PendantTree" (PENDTREE) 17.13.1 on page 1911

Exports:

any?	binarySearchTree	child?	children	coerce
copy	count	count	cyclic?	distance
empty	empty?	eq?	eval	eval
eval	eval	every?	hash	insert!
insertRoot!	latex	leaf?	leaves	left
less?	map	map!	member?	members
more?	node	node?	nodes	parts
right	sample	setchildren!	setelt	setelt
setelt	setleft!	setright!	setvalue!	size?
split	value	#?	?=?	?~=?
?.right	?.left	?.value		

— **domain BSTREE BinarySearchTree** —

```
)abbrev domain BSTREE BinarySearchTree
++ Author: Mark Botch
++ Description:
++ BinarySearchTree(S) is the domain of
++ a binary trees where elements are ordered across the tree.
++ A binary search tree is either empty or has
++ a value which is an S, and a
++ right and left which are both BinaryTree(S)
++ Elements are ordered across the tree.

BinarySearchTree(S: OrderedSet): Exports == Implementation where
  Exports == BinaryTreeCategory(S) with
    shallowlyMutable
```

```
    finiteAggregate
    binarySearchTree: List S -> %
     ++ binarySearchTree(l) is not documented
     ++
     ++X binarySearchTree [1,2,3,4]

    insert_!: (S,%) -> %
     ++ insert!(x,b) inserts element x as leaves into binary search tree b.
     ++
     ++X t1:=binarySearchTree [1,2,3,4]
     ++X insert!(5,t1)

    insertRoot_!: (S,%) -> %
     ++ insertRoot!(x,b) inserts element x as a root of binary search tree b.
     ++
     ++X t1:=binarySearchTree [1,2,3,4]
     ++X insertRoot!(5,t1)

    split:      (S,%) -> Record(less: %, greater: %)
     ++ split(x,b) splits binary tree b into two trees, one with elements
     ++ greater than x, the other with elements less than x.
     ++
     ++X t1:=binarySearchTree [1,2,3,4]
     ++X split(3,t1)

  Implementation == BinaryTree(S) add
    Rep := BinaryTree(S)
    binarySearchTree(u:List S) ==
      null u => empty()
      tree := binaryTree(first u)
      for x in rest u repeat insert_!(x,tree)
      tree
    insert_!(x,t) ==
      empty? t => binaryTree(x)
      x >= value t =>
        setright_!(t,insert_!(x,right t))
        t
      setleft_!(t,insert_!(x,left t))
      t
    split(x,t) ==
      empty? t => [empty(),empty()]
      x > value t =>
        a := split(x,right t)
        [node(left t, value t, a.less), a.greater]
      a := split(x,left t)
      [a.less, node(a.greater, value t, right t)]
    insertRoot_!(x,t) ==
      a := split(x,t)
      node(a.less, x, a.greater)
```

———-

— **BSTREE.dotabb** —

```
"BSTREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BSTREE"]
"BTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BTCAT"]
"BSTREE" -> "BTCAT"
```

———-

3.10 domain BTOURN BinaryTournament

A BinaryTournament(S) is the domain of binary trees where elements are ordered down the tree. A binary search tree is either empty or is a node containing a value of type S, and a right and a left which are both BinaryTree(S)

— **BinaryTournament.input** —

```
)set break resume
)sys rm -f BinaryTournament.output
)spool BinaryTournament.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BinaryTournament
--R
--R BinaryTournament(S: OrderedSet)  is a domain constructor
--R Abbreviation for BinaryTournament is BTOURN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BTOURN
--R
--R------------------------------ Operations --------------------------------
--R binaryTournament : List(S) -> %       children : % -> List(%)
--R copy : % -> %                         cyclic? : % -> Boolean
--R distance : (%,%) -> Integer           ?.right : (%,right) -> %
--R ?.left : (%,left) -> %                ?.value : (%,value) -> S
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                insert! : (S,%) -> %
--R leaf? : % -> Boolean                  leaves : % -> List(S)
--R left : % -> %                         map : ((S -> S),%) -> %
--R node : (%,S,%) -> %                   nodes : % -> List(%)
--R right : % -> %                       sample : () -> %
--R value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
```

```
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,right,%) -> % if $ has shallowlyMutable
--R setelt : (%,left,%) -> % if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setleft! : (%,%) -> % if $ has shallowlyMutable
--R setright! : (%,%) -> % if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— BinaryTournament.help —

```
=====================================================================
BinaryTournament examples
=====================================================================

See Also:
o )show BinaryTournament
```

———-

3.10.1 BinaryTournament (BTOURN)



See

⇒ "Tree" (TREE) 21.10.1 on page 2710
⇒ "BinaryTree" (BTREE) 3.11.1 on page 294
⇒ "BinarySearchTree" (BSTREE) 3.9.1 on page 287
⇒ "BalancedBinaryTree" (BBTREE) 3.1.1 on page 236
⇒ "PendantTree" (PENDTREE) 17.13.1 on page 1911

Exports:

any?	binaryTournament	child?	children	coerce
copy	count	cyclic?	distance	empty
empty?	eq?	eval	every?	hash
insert!	latex	leaf?	leaves	left
less?	map	map!	member?	members
more?	node	node?	nodes	parts
right	sample	setchildren!	setelt	setleft!
setright!	setvalue!	size?	value	#?
?=?	?~=?	?.right	?.left	?.value

— domain BTOURN BinaryTournament —

```
)abbrev domain BTOURN BinaryTournament
++ Author: Mark Botch
++ Description:
++ BinaryTournament creates a binary tournament with the
++ elements of ls as values at the nodes.

BinaryTournament(S: OrderedSet): Exports == Implementation where
  Exports == BinaryTreeCategory(S) with
    shallowlyMutable
    binaryTournament: List S -> %
      ++ binaryTournament(ls) creates a binary tournament with the
      ++ elements of ls as values at the nodes.
      ++
      ++X binaryTournament [1,2,3,4]
```

```
    insert_!: (S,%) -> %
      ++ insert!(x,b) inserts element x as leaves into binary tournament b.
      ++
      ++X t1:=binaryTournament [1,2,3,4]
      ++X insert!(5,t1)
      ++X t1

  Implementation == BinaryTree(S) add
    Rep := BinaryTree(S)
    binaryTournament(u:List S) ==
      null u => empty()
      tree := binaryTree(first u)
      for x in rest u repeat insert_!(x,tree)
      tree
    insert_!(x,t) ==
      empty? t => binaryTree(x)
      x > value t =>
        setleft_!(t,copy t)
        setvalue_!(t,x)
        setright_!(t,empty())
      setright_!(t,insert_!(x,right t))
      t
```

———-

— BTOURN.dotabb —

```
"BTOURN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BTOURN"]
"BTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BTCAT"]
"BTOURN" -> "BTCAT"
```

———-

3.11 domain BTREE BinaryTree

— BinaryTree.input —

```
)set break resume
)sys rm -f BinaryTree.output
)spool BinaryTree.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show BinaryTree
--R
--R BinaryTree(S: SetCategory)  is a domain constructor
--R Abbreviation for BinaryTree is BTREE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BTREE
--R
--R------------------------------ Operations --------------------------------
--R binaryTree : (%,S,%) -> %            binaryTree : S -> %
--R children : % -> List(%)              copy : % -> %
--R cyclic? : % -> Boolean               distance : (%,%) -> Integer
--R ?.right : (%,right) -> %             ?.left : (%,left) -> %
--R ?.value : (%,value) -> S             empty : () -> %
--R empty? : % -> Boolean                eq? : (%,%) -> Boolean
--R leaf? : % -> Boolean                 leaves : % -> List(S)
--R left : % -> %                        map : ((S -> S),%) -> %
--R node : (%,S,%) -> %                  nodes : % -> List(%)
--R right : % -> %                       sample : () -> %
--R value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,right,%) -> % if $ has shallowlyMutable
--R setelt : (%,left,%) -> % if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setleft! : (%,%) -> % if $ has shallowlyMutable
--R setright! : (%,%) -> % if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
```

```
--R
--E 1

)spool
)lisp (bye)
```

———-


— **BinaryTree.help** —

```
====================================================================
BinaryTree examples
====================================================================

See Also:
o )show BinaryTree
```

———-

3.11.1 BinaryTree (BTREE)



See

⇒ “Tree” (TREE) 21.10.1 on page 2710
⇒ “BinarySearchTree” (BSTREE) 3.9.1 on page 287
⇒ “BinaryTournament” (BTOURN) 3.10.1 on page 291
⇒ “BalancedBinaryTree” (BBTREE) 3.1.1 on page 236
⇒ “PendantTree” (PENDTREE) 17.13.1 on page 1911

Exports:

any?	binaryTree	child?	children	coerce
copy	count	cyclic?	distance	empty
empty?	eq?	eval	every?	hash
latex	leaf?	leaves	left	less?
map	map!	member?	members	more?
node	node?	nodes	parts	right
sample	setchildren!	setelt	setleft!	setright!
setvalue!	size?	value	#?	?=?
?~=?	?.right	?.left	?.value	

— domain BTREE BinaryTree —

```
)abbrev domain BTREE BinaryTree
++ Author: Mark Botch
++ Description:
++ \spadtype{BinaryTree(S)} is the domain of all
++ binary trees. A binary tree over \spad{S} is either empty or has
++ a \spadfun{value} which is an S and a \spadfun{right}
++ and \spadfun{left} which are both binary trees.

BinaryTree(S: SetCategory): Exports == Implementation where
  Exports == BinaryTreeCategory(S) with
   binaryTree: S -> %
    ++ binaryTree(v) is an non-empty binary tree
    ++ with value v, and left and right empty.
    ++
    ++X t1:=binaryTree([1,2,3])

   binaryTree: (%,S,%) -> %
    ++ binaryTree(l,v,r) creates a binary tree with
    ++ value v with left subtree l and right subtree r.
    ++
    ++X t1:=binaryTree([1,2,3])
    ++X t2:=binaryTree([4,5,6])
    ++X binaryTree(t1,[7,8,9],t2)

  Implementation == add
     Rep := List Tree S
     t1 = t2 == (t1::Rep) =$Rep (t2::Rep)
     empty()== [] pretend %
     empty()== [] pretend %
     node(l,v,r) == cons(tree(v,l:Rep),r:Rep)
     binaryTree(l,v,r) == node(l,v,r)
     binaryTree(v:S) == node(empty(),v,empty())
     empty? t == empty?(t)$Rep
     leaf? t  == empty? t or empty? left t and empty? right t
     right t ==
       empty? t => error "binaryTree:no right"
```

```
      rest t
    left t ==
      empty? t => error "binaryTree:no left"
      children first t
    value t==
      empty? t => error "binaryTree:no value"
      value first t
    setvalue_! (t,nd)==
      empty? t => error "binaryTree:no value to set"
      setvalue_!(first(t:Rep),nd)
      nd
    setleft_!(t1,t2) ==
      empty? t1 => error "binaryTree:no left to set"
      setchildren_!(first(t1:Rep),t2:Rep)
      t1
    setright_!(t1,t2) ==
      empty? t1 => error "binaryTree:no right to set"
      setrest_!(t1:List Tree S,t2)
```

———-

— BTREE.dotabb —

```
"BTREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BTREE"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"BTREE" -> "FLAGG"
```

———-

3.12 domain BITS Bits

— Bits.input —

```
)set break resume
)sys rm -f Bits.output
)spool Bits.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Bits
--R
--R Bits  is a domain constructor
```

```
--R Abbreviation for Bits is BITS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BITS
--R
--R------------------------------ Operations --------------------------------
--R ?/\? : (%,%) -> %                    ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean              ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean               ?>=? : (%,%) -> Boolean
--R ?\/? : (%,%) -> %                    ^? : % -> %
--R ?and? : (%,%) -> %                   coerce : % -> OutputForm
--R concat : (%,Boolean) -> %            concat : (Boolean,%) -> %
--R concat : (%,%) -> %                  concat : List(%) -> %
--R construct : List(Boolean) -> %       copy : % -> %
--R delete : (%,Integer) -> %            ?.? : (%,Integer) -> Boolean
--R empty : () -> %                      empty? : % -> Boolean
--R entries : % -> List(Boolean)         eq? : (%,%) -> Boolean
--R hash : % -> SingleInteger            index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)         insert : (%,%,Integer) -> %
--R latex : % -> String                  max : (%,%) -> %
--R min : (%,%) -> %                     nand : (%,%) -> %
--R nor : (%,%) -> %                     not? : % -> %
--R ?or? : (%,%) -> %                    qelt : (%,Integer) -> Boolean
--R reverse : % -> %                     sample : () -> %
--R xor : (%,%) -> %                     ~? : % -> %
--R ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R any? : ((Boolean -> Boolean),%) -> Boolean if $ has finiteAggregate
--R bits : (NonNegativeInteger,Boolean) -> %
--R convert : % -> InputForm if Boolean has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : ((Boolean -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (Boolean,%) -> NonNegativeInteger if $ has finiteAggregate and Boolean has SETCAT
--R delete : (%,UniversalSegment(Integer)) -> %
--R elt : (%,Integer,Boolean) -> Boolean
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (Boolean,%) -> Boolean if $ has finiteAggregate and Boolean has SETCAT
--R eval : (%,List(Equation(Boolean))) -> % if Boolean has EVALAB(BOOLEAN) and Boolean has SETCAT
--R eval : (%,Equation(Boolean)) -> % if Boolean has EVALAB(BOOLEAN) and Boolean has SETCAT
--R eval : (%,Boolean,Boolean) -> % if Boolean has EVALAB(BOOLEAN) and Boolean has SETCAT
--R eval : (%,List(Boolean),List(Boolean)) -> % if Boolean has EVALAB(BOOLEAN) and Boolean has SETCAT
--R every? : ((Boolean -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,Boolean) -> % if $ has shallowlyMutable
--R find : ((Boolean -> Boolean),%) -> Union(Boolean,"failed")
--R first : % -> Boolean if Integer has ORDSET
--R insert : (Boolean,%,Integer) -> %
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : ((Boolean -> Boolean),%) -> %
--R map : (((Boolean,Boolean) -> Boolean),%,%) -> %
--R map! : ((Boolean -> Boolean),%) -> % if $ has shallowlyMutable
--R maxIndex : % -> Integer if Integer has ORDSET
```

```
--R member? : (Boolean,%) -> Boolean if $ has finiteAggregate and Boolean has SETCAT
--R members : % -> List(Boolean) if $ has finiteAggregate
--R merge : (((Boolean,Boolean) -> Boolean),%,%) -> %
--R merge : (%,%) -> % if Boolean has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,Boolean) -> %
--R parts : % -> List(Boolean) if $ has finiteAggregate
--R position : ((Boolean -> Boolean),%) -> Integer
--R position : (Boolean,%) -> Integer if Boolean has SETCAT
--R position : (Boolean,%,Integer) -> Integer if Boolean has SETCAT
--R qsetelt! : (%,Integer,Boolean) -> Boolean if $ has shallowlyMutable
--R reduce : (((Boolean,Boolean) -> Boolean),%,Boolean,Boolean) -> Boolean if $ has finiteAggreg
--R reduce : (((Boolean,Boolean) -> Boolean),%,Boolean) -> Boolean if $ has finiteAggregate
--R reduce : (((Boolean,Boolean) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R remove : (Boolean,%) -> % if $ has finiteAggregate and Boolean has SETCAT
--R remove : ((Boolean -> Boolean),%) -> % if $ has finiteAggregate
--R removeDuplicates : % -> % if $ has finiteAggregate and Boolean has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((Boolean -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,Integer,Boolean) -> Boolean if $ has shallowlyMutable
--R setelt : (%,UniversalSegment(Integer),Boolean) -> Boolean if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : (((Boolean,Boolean) -> Boolean),%) -> %
--R sort : % -> % if Boolean has ORDSET
--R sort! : (((Boolean,Boolean) -> Boolean),%) -> % if $ has shallowlyMutable
--R sort! : % -> % if $ has shallowlyMutable and Boolean has ORDSET
--R sorted? : (((Boolean,Boolean) -> Boolean),%) -> Boolean
--R sorted? : % -> Boolean if Boolean has ORDSET
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R
--E 1

)spool
)lisp (bye)
```

———-


— Bits.help —

```
=====================================================================
Bits examples
=====================================================================

See Also:
o )show Bits
```

———-

3.12.1 Bits (BITS)



See

⇒ "Reference" (REF) 19.5.1 on page 2215
⇒ "Boolean" (BOOLEAN) 3.15.1 on page 306
⇒ "IndexedBits" (IBITS) 10.3.1 on page 1169

Exports:

any?	bits	coerce	concat	construct
convert	copy	copyInto!	count	delete
elt	empty	empty?	entries	entry?
eq?	eval	every?	fill!	find
first	hash	index?	indices	insert
latex	less?	map	map!	max
maxIndex	member?	members	merge	min
minIndex	more?	nand	new	nor
not?	parts	position	qelt	qsetelt!
reduce	remove	removeDuplicates	reverse	reverse!
sample	setelt	size?	sort	sort!
sorted?	swap!	xor	#?	?.?
?/\?	?<?	?<=?	?=?	?>?
?>=?	?\/?	^?	?and?	?or?
?.?	~?	?~=?		

— domain BITS Bits —

```
)abbrev domain BITS Bits
++ Author: Stephen M. Watt
++ Date Created:
++ Change History:
++ Basic Operations: And, Not, Or
++ Related Constructors:
++ Keywords: bits
++ Description:
++ \spadtype{Bits} provides logical functions for Indexed Bits.

Bits(): Exports == Implementation where
```

```
  Exports == BitAggregate() with
    bits: (NonNegativeInteger, Boolean) -> %
      ++ bits(n,b) creates bits with n values of b
  Implementation == IndexedBits(1) add
    bits(n,b)    == new(n,b)
```

———-

— BITS.dotabb —

```
"BITS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BITS"]
"BTAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BTAGG"]
"BITS" -> "BTAGG"
```

———-

3.13 domain BLHN BlowUpWithHamburgerNoether

— BlowUpWithHamburgerNoether.input —

```
)set break resume
)sys rm -f BlowUpWithHamburgerNoether.output
)spool BlowUpWithHamburgerNoether.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BlowUpWithHamburgerNoether
--R
--R BlowUpWithHamburgerNoether  is a domain constructor
--R Abbreviation for BlowUpWithHamburgerNoether is BLHN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BLHN
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               chartCoord : % -> Integer
--R coerce : List(Integer) -> %          coerce : % -> OutputForm
--R excepCoord : % -> Integer            hash : % -> SingleInteger
--R infClsPt? : % -> Boolean             latex : % -> String
--R quotValuation : % -> Integer         ramifMult : % -> Integer
--R transCoord : % -> Integer            ?~=? : (%,%) -> Boolean
--R createHN : (Integer,Integer,Integer,Integer,Integer,Boolean,Union(left,center,right,vertical
--R type : % -> Union(left,center,right,vertical,horizontal)
```

```
--R
--E 1

)spool
)lisp (bye)
```

———-


— **BlowUpWithHamburgerNoether.help** —

```
=====================================================================
BlowUpWithHamburgerNoether examples
=====================================================================

See Also:
o )show BlowUpWithHamburgerNoether
```

———-

3.13.1 BlowUpWithHamburgerNoether (BLHN)



Exports:

?=?	?~=?	chartCoord	coerce	createHN
excepCoord	hash	infClsPt?	latex	quotValuation
ramifMult	transCoord	type		

— **domain BLHN BlowUpWithHamburgerNoether** —

```
)abbrev domain BLHN BlowUpWithHamburgerNoether
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
```

```
++ Description:
++ This domain is part of the PAFF package
BlowUpWithHamburgerNoether: Exports == Implementation where
  MetRec ==> Record(_
     ex:Integer, tr:Integer, ch:Integer , quotVal:Integer, _
     ramif:Integer, infClsPt:Boolean, _
     type:Union("left","center","right","vertical","horizontal") )

  Exports ==> BlowUpMethodCategory with HamburgerNoether

  Implementation ==  add
    Rep := MetRec

    infClsPt_? a == a.infClsPt

    createHN( a,b,c,d,e,f,g)==[a,b,c,d,e,f,g]$Rep

    excepCoord a == a.ex

    chartCoord a == a.ch

    transCoord a == a.tr

    ramifMult a == a.ramif

    quotValuation a == a.quotVal

    type a == a.type

    coerce(c:%):OutputForm== ( (c :: Rep ) :: MetRec) :: OutputForm
```

———-

— BLHN.dotabb —

```
"BLHN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BLHN",
          shape=ellipse]
"BLMETCT" [color="#4488FF",href="bookvol10.3.pdf#nameddest=BLMETCT"]
"BLHN" -> "BLMETCT"
```

———-

3.14 domain BLQT BlowUpWithQuadTrans

— BlowUpWithQuadTrans.input —

```
)set break resume
)sys rm -f BlowUpWithQuadTrans.output
)spool BlowUpWithQuadTrans.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show BlowUpWithQuadTrans
--R
--R BlowUpWithQuadTrans  is a domain constructor
--R Abbreviation for BlowUpWithQuadTrans is BLQT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BLQT
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                chartCoord : % -> Integer
--R coerce : List(Integer) -> %           coerce : % -> OutputForm
--R excepCoord : % -> Integer             hash : % -> SingleInteger
--R infClsPt? : % -> Boolean              latex : % -> String
--R quotValuation : % -> Integer          ramifMult : % -> Integer
--R transCoord : % -> Integer             ?~=? : (%,%) -> Boolean
--R createHN : (Integer,Integer,Integer,Integer,Integer,Boolean,Union(left,center,right,vertical,horizontal)
--R type : % -> Union(left,center,right,vertical,horizontal)
--R
--E 1

)spool
)lisp (bye)
```

———-


— BlowUpWithQuadTrans.help —

```
=====================================================================
BlowUpWithQuadTrans examples
=====================================================================

See Also:
o )show BlowUpWithQuadTrans
```

———-

3.14.1 BlowUpWithQuadTrans (BLQT)



Exports:

?=?	?~=?	chartCoord	coerce	createHN
excepCoord	hash	infClsPt?	latex	quotValuation
ramifMult	transCoord	type		

— domain BLQT BlowUpWithQuadTrans —

```
)abbrev domain BLQT BlowUpWithQuadTrans
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain is part of the PAFF package
BlowUpWithQuadTrans: Exports == Implementation where

  MetRec ==> Record( ex:Integer, tr: Integer, ch: Integer , ramif: Integer )
  outRec ==> Record( exCoord:Integer, affNeigh: Integer )
  Exports ==> BlowUpMethodCategory with

    QuadraticTransform

  Implementation ==  add
    Rep := MetRec

    coerce(la:List(Integer)):% == [la.1, la.2,la.3,  1 ]$Rep

    ramifMult a == One$Integer

    excepCoord a == a.ex

    chartCoord a == a.ch

    transCoord a == a.tr

    ramifMult a == a.ramif
```

```
    quotValuation a == One$Integer

    coerce(c:%):OutputForm==
      oo: outRec := [ excepCoord(c) , chartCoord(c) ]$outRec
      oo :: OutputForm
```

———-

— **BLQT.dotabb** —

```
"BLQT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BLQT",
          shape=ellipse]
"BLMETCT" [color="#4488FF",href="bookvol10.3.pdf#nameddest=BLMETCT"]
"BLQT" -> "BLMETCT"
```

———-

3.15 domain BOOLEAN Boolean

— **Boolean.input** —

```
)set break resume
)sys rm -f Boolean.output
)spool Boolean.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Boolean
--R Boolean  is a domain constructor
--R Abbreviation for Boolean is BOOLEAN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for BOOLEAN
--R
--R------------------------------ Operations --------------------------------
--R ?/\? : (%,%) -> %                    ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean              ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean               ?>=? : (%,%) -> Boolean
--R ?\/? : (%,%) -> %                    ^? : % -> %
--R ?and? : (%,%) -> %                   coerce : % -> OutputForm
--R convert : % -> InputForm             false : () -> %
--R hash : % -> SingleInteger            implies : (%,%) -> %
```

```
--R index : PositiveInteger -> %          latex : % -> String
--R lookup : % -> PositiveInteger         max : (%,%) -> %
--R min : (%,%) -> %                      nand : (%,%) -> %
--R nor : (%,%) -> %                      not? : % -> %
--R ?or? : (%,%) -> %                     random : () -> %
--R size : () -> NonNegativeInteger       test : % -> Boolean
--R true : () -> %                        xor : (%,%) -> %
--R ~? : % -> %                           ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Boolean.help** —

```
========================================================================
Boolean examples
========================================================================

See Also:
o )show Boolean
```

———-

3.15.1 Boolean (BOOLEAN)



See

⇒ “Reference” (REF) 19.5.1 on page 2215
⇒ “IndexedBits” (IBITS) 10.3.1 on page 1169
⇒ “Bits” (BITS) 3.12.1 on page 299

Exports:

coerce	convert	false	hash	implies
index	latex	lookup	max	min
nand	nor	not?	random	size
test	true	xor	~?	?~=?
?/\?	?<?	?<=?	?=?	?>?
?>=?	?\/?	^?	?and?	?or?

— domain BOOLEAN Boolean —

```
)abbrev domain BOOLEAN Boolean
++ Author: Stephen M. Watt
++ Date Created:
++ Change History:
++ Basic Operations: true, false, not, and, or, xor, nand, nor, implies, ^
++ Related Constructors:
++ Keywords: boolean
++ Description:
++ \spadtype{Boolean} is the elementary logic with 2 values:
++ true and false

Boolean(): Join(OrderedSet, Finite, Logic, ConvertibleTo InputForm) with
    true   : constant -> %
      ++ true is a logical constant.
    false  : constant -> %
      ++ false is a logical constant.
    _^     : % -> %
      ++ ^ n returns the negation of n.
    _not : % -> %
      ++ not n returns the negation of n.
    _and  : (%, %) -> %
      ++ a and b  returns the logical and of Boolean \spad{a} and b.
    _or  : (%, %) -> %
      ++ a or b returns the logical inclusive or
      ++ of Boolean \spad{a} and b.
    xor    : (%, %) -> %
      ++ xor(a,b) returns the logical exclusive or
      ++ of Boolean \spad{a} and b.
    nand   : (%, %) -> %
      ++ nand(a,b) returns the logical negation of \spad{a} and b.
    nor    : (%, %) -> %
      ++ nor(a,b) returns the logical negation of \spad{a} or b.
    implies: (%, %) -> %
      ++ implies(a,b) returns the logical implication
      ++ of Boolean \spad{a} and b.
    test: % -> Boolean
      ++ test(b) returns b and is provided for compatibility with the
      ++ new compiler.
  == add
```

```
    nt: % -> %

    test a        == a pretend Boolean

    nt b          == (b pretend Boolean => false; true)
    true          == EQ(2,2)$Lisp   --well, 1 is rather special
    false         == NIL$Lisp
    sample()      == true
    not b         == (test b => false; true)
    _^ b          == (test b => false; true)
    _~ b          == (test b => false; true)
    _and(a, b)    == (test a => b; false)
    _/_\(a, b)    == (test a => b; false)
    _or(a, b)     == (test a => true; b)
    _\_/(a, b)     == (test a => true; b)
    xor(a, b)     == (test a => nt b; b)
    nor(a, b)     == (test a => false; nt b)
    nand(a, b)    == (test a => nt b; true)
    a = b         == BooleanEquality(a, b)$Lisp
    implies(a, b) == (test a => b; true)
    a < b         == (test b => not(test a);false)

    size()        == 2
    index i       ==
      even?(i::Integer) => false
      true
    lookup a      ==
      a pretend Boolean => 1
      2
    random()      ==
      even?(random()$Integer) => false
      true

    convert(x:%):InputForm ==
      x pretend Boolean => convert("true"::Symbol)
      convert("false"::Symbol)

    coerce(x:%):OutputForm ==
      x pretend Boolean => message "true"
      message "false"
```

———-

— BOOLEAN.dotabb —

```
"BOOLEAN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=BOOLEAN",
           shape=ellipse]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
```

```
"BOOLEAN" -> "ALIST"
```

———————-

Chapter 4

Chapter C

4.1 domain CARD CardinalNumber

— CardinalNumber.input —

```
)set break resume
)sys rm -f CardinalNumber.output
)spool CardinalNumber.output
)set message test on
)set message auto off
)clear all
--S 1 of 20
c0 := 0 :: CardinalNumber
--R
--R
--R   (1)  0
--R                                                    Type: CardinalNumber
--E 1

--S 2 of 20
c1 := 1 :: CardinalNumber
--R
--R
--R   (2)  1
--R                                                    Type: CardinalNumber
--E 2

--S 3 of 20
c2 := 2 :: CardinalNumber
--R
--R
--R   (3)  2
```

```
--R                                                   Type: CardinalNumber
--E 3

--S 4 of 20
c3 := 3 :: CardinalNumber
--R
--R
--R   (4)  3
--R                                                   Type: CardinalNumber
--E 4

--S 5 of 20
A0 := Aleph 0
--R
--R
--R   (5)  Aleph(0)
--R                                                   Type: CardinalNumber
--E 5

--S 6 of 20
A1 := Aleph 1
--R
--R
--R   (6)  Aleph(1)
--R                                                   Type: CardinalNumber
--E 6

--S 7 of 20
finite? c2
--R
--R
--R   (7)  true
--R                                                          Type: Boolean
--E 7

--S 8 of 20
finite? A0
--R
--R
--R   (8)  false
--R                                                          Type: Boolean
--E 8

--S 9 of 20
countable? c2
--R
--R
--R   (9)  true
--R                                                          Type: Boolean
--E 9
```

```
--S 10 of 20
countable? A0
--R
--R
--R   (10)  true
--R                                                          Type: Boolean
--E 10

--S 11 of 20
countable? A1
--R
--R
--R   (11)  false
--R                                                          Type: Boolean
--E 11

--S 12 of 20
[c2 + c2, c2 + A1]
--R
--R
--R   (12)  [4,Aleph(1)]
--R                                          Type: List(CardinalNumber)
--E 12

--S 13 of 20
[c0*c2, c1*c2, c2*c2, c0*A1, c1*A1, c2*A1, A0*A1]
--R
--R
--R   (13)  [0,2,4,0,Aleph(1),Aleph(1),Aleph(1)]
--R                                          Type: List(CardinalNumber)
--E 13

--S 14 of 20
[c2**c0, c2**c1, c2**c2, A1**c0, A1**c1, A1**c2]
--R
--R
--R   (14)  [1,2,4,1,Aleph(1),Aleph(1)]
--R                                          Type: List(CardinalNumber)
--E 14

--S 15 of 20
[c2-c1, c2-c2, c2-c3, A1-c2, A1-A0, A1-A1]
--R
--R
--R   (15)  [1,0,"failed",Aleph(1),Aleph(1),"failed"]
--R                                Type: List(Union(CardinalNumber,"failed"))
--E 15

--S 16 of 20
```

```
generalizedContinuumHypothesisAssumed true
--R
--R
--R   (16)  true
--R                                                              Type: Boolean
--E 16

--S 17 of 20
[c0**A0, c1**A0, c2**A0, A0**A0, A0**A1, A1**A0, A1**A1]
--R
--R
--R   (17)  [0,1,Aleph(1),Aleph(1),Aleph(2),Aleph(1),Aleph(2)]
--R                                                 Type: List(CardinalNumber)
--E 17

--S 18 of 20
a := Aleph 0
--R
--R
--R   (18)  Aleph(0)
--R                                                   Type: CardinalNumber
--E 18

--S 19 of 20
c := 2**a
--R
--R
--R   (19)  Aleph(1)
--R                                                   Type: CardinalNumber
--E 19

--S 20 of 20
f := 2**c
--R
--R
--R   (20)  Aleph(2)
--R                                                   Type: CardinalNumber
--E 20
)spool
)lisp (bye)
```

———-

— CardinalNumber.help —

```
=====================================================================
CardinalNumber examples
=====================================================================
```

```
The CardinalNumber domain can be used for values indicating the
cardinality of sets, both finite and infinite.  For example, the
dimension operation in the category VectorSpace returns a cardinal
number.

The non-negative integers have a natural construction as cardinals

  0 = #{ }, 1 = {0}, 2 = {0, 1}, ..., n = {i | 0 <= i < n}.

The fact that 0 acts as a zero for the multiplication of cardinals is
equivalent to the axiom of choice.

Cardinal numbers can be created by conversion from non-negative integers.

  c0 := 0 :: CardinalNumber
   0
                      Type: CardinalNumber

  c1 := 1 :: CardinalNumber
   1
                      Type: CardinalNumber

  c2 := 2 :: CardinalNumber
   2
                      Type: CardinalNumber

  c3 := 3 :: CardinalNumber
   3
                      Type: CardinalNumber

They can also be obtained as the named cardinal Aleph(n).

  A0 := Aleph 0
   Aleph(0)
                      Type: CardinalNumber

  A1 := Aleph 1
   Aleph(1)
                      Type: CardinalNumber

The finite? operation tests whether a value is a finite cardinal, that
is, a non-negative integer.

  finite? c2
   true
                      Type: Boolean

  finite? A0
   false
                      Type: Boolean
```

```
Similarly, the countable?  operation determines whether a value is a
countable cardinal, that is, finite or Aleph(0).

  countable? c2
   true
                      Type: Boolean

  countable? A0
   true
                      Type: Boolean

  countable? A1
   false
                      Type: Boolean

Arithmetic operations are defined on cardinal numbers as follows:
If x = #X  and y = #Y then

  x+y  = #(X+Y) cardinality of the disjoint union
  x-y  = #(X-Y) cardinality of the relative complement
  x*y  = #(X*Y) cardinality of the Cartesian product
  x**y = #(X**Y) cardinality of the set of maps from Y to X

Here are some arithmetic examples.

  [c2 + c2, c2 + A1]
   [4, Aleph(1)]
                      Type: List CardinalNumber

  [c0*c2, c1*c2, c2*c2, c0*A1, c1*A1, c2*A1, A0*A1]
   [0, 2, 4, 0, Aleph(1), Aleph(1), Aleph(1)]
                      Type: List CardinalNumber

  [c2**c0, c2**c1, c2**c2, A1**c0, A1**c1, A1**c2]
   [1, 2, 4, 1, Aleph(1), Aleph(1)]
                      Type: List CardinalNumber

Subtraction is a partial operation: it is not defined when subtracting
a larger cardinal from a smaller one, nor when subtracting two equal
infinite cardinals.

  [c2-c1, c2-c2, c2-c3, A1-c2, A1-A0, A1-A1]
   [1, 0, "failed", Aleph(1), Aleph(1), "failed"]
                      Type: List Union(CardinalNumber,"failed")

The generalized continuum hypothesis asserts that

  2**Aleph i = Aleph(i+1)
```

```
and is independent of the axioms of set theory.

(reference: Goedel, The consistency of the continuum hypothesis,
Ann. Math. Studies, Princeton Univ. Press, 1940.)

The CardinalNumber domain provides an operation to assert whether the
hypothesis is to be assumed.

  generalizedContinuumHypothesisAssumed true
   true
                        Type: Boolean

When the generalized continuum hypothesis is assumed, exponentiation
to a transfinite power is allowed.

  [c0**A0, c1**A0, c2**A0, A0**A0, A0**A1, A1**A0, A1**A1]
   [0, 1, Aleph(1), Aleph(1), Aleph(2), Aleph(1), Aleph(2)]
                        Type: List CardinalNumber

Three commonly encountered cardinal numbers are

  a = #Z countable infinity
  c = #R the continuum
  f = #{g| g: [0,1] -> R}

In this domain, these values are obtained under the generalized
continuum hypothesis in this way.

  a := Aleph 0
   Aleph(0)
                        Type: CardinalNumber


  c := 2**a
   Aleph(1)
                        Type: CardinalNumber

  f := 2**c
   Aleph(2)
                        Type: CardinalNumber

See Also:
o )show CardinalNumber
```

———-

4.1.1 CardinalNumber (CARD)



Exports:

0	1
Aleph	coerce
countable?	finite?
generalizedContinuumHypothesisAssumed	hash
generalizedContinuumHypothesisAssumed?	latex
max	min
one?	recip
retract	retractIfCan
sample	zero?
?^?	?~=?
?*?	?**?
?-?	?+?
?<?	?<=?
?=?	?>?
?>=?	

— domain CARD CardinalNumber —

```
)abbrev domain CARD CardinalNumber
++ Author: S.M. Watt
++ Date Created: June 1986
++ Date Last Updated: May 1990
++ Basic Operations: Aleph, +, -, *, **
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: cardinal number, transfinite arithmetic
++ Examples:
++ References:
++   Goedel, "The consistency of the continuum hypothesis",
++   Ann. Math. Studies, Princeton Univ. Press, 1940
++ Description:
++ Members of the domain CardinalNumber are values indicating the
```

```
++ cardinality of sets, both finite and infinite.  Arithmetic operations
++ are defined on cardinal numbers as follows.
++
++ If \spad{x = #X}  and  \spad{y = #Y} then\br
++ \tab{5}\spad{x+y  = #(X+Y)} \tab{5}disjoint union\br
++ \tab{5}\spad{x-y  = #(X-Y)} \tab{5}relative complement\br
++ \tab{5}\spad{x*y  = #(X*Y)} \tab{5}cartesian product\br
++ \tab{5}\spad{x**y = #(X**Y)} \tab{4}\spad{X**Y = g| g:Y->X}
++
++ The non-negative integers have a natural construction as cardinals\br
++ \spad{0 = #\{\}}, \spad{1 = \{0\}},
++ \spad{2 = \{0, 1\}}, ..., \spad{n = \{i| 0 <= i < n\}}.
++
++ That \spad{0} acts as a zero for the multiplication of cardinals is
++ equivalent to the axiom of choice.
++
++ The generalized continuum hypothesis asserts \br
++ \spad{2**Aleph i = Aleph(i+1)}
++ and is independent of the axioms of set theory [Goedel 1940].
++
++ Three commonly encountered cardinal numbers are\br
++ \tab{5}\spad{a = #Z} \tab{5}countable infinity\br
++ \tab{5}\spad{c = #R} \tab{5}the continuum\br
++ \tab{5}\spad{f = # g | g:[0,1]->R\}
++
++ In this domain, these values are obtained using\br
++ \tab{5}\spad{a := Aleph 0}, \spad{c := 2**a}, \spad{f := 2**c}.

CardinalNumber: Join(OrderedSet, AbelianMonoid, Monoid,
                        RetractableTo NonNegativeInteger) with
        commutative "*"
            ++ a domain D has \spad{commutative("*")} if it has an operation
            ++ \spad{"*": (D,D) -> D} which is commutative.

        "-": (%,%) -> Union(%,"failed")
            ++ \spad{x - y} returns an element z such that
            ++ \spad{z+y=x} or "failed" if no such element exists.
            ++
            ++X c2:=2::CardinalNumber
            ++X c2-c2
            ++X A1:=Aleph 1
            ++X A1-c2

        "**": (%, %) -> %
            ++ \spad{x**y} returns \spad{#(X**Y)} where \spad{X**Y} is defined
            ++  as \spad{\{g| g:Y->X\}}.
            ++
            ++X c2:=2::CardinalNumber
            ++X c2**c2
            ++X A1:=Aleph 1
```

```
        ++X A1**c2
        ++X generalizedContinuumHypothesisAssumed true
        ++X A1**A1

    Aleph: NonNegativeInteger -> %
        ++ Aleph(n) provides the named (infinite) cardinal number.
        ++
        ++X A0:=Aleph 0

    finite?: % -> Boolean
        ++ finite?(\spad{a}) determines whether
        ++ \spad{a} is a finite cardinal, i.e. an integer.
        ++
        ++X c2:=2::CardinalNumber
        ++X finite? c2
        ++X A0:=Aleph 0
        ++X finite? A0

    countable?: % -> Boolean
        ++ countable?(\spad{a}) determines
        ++ whether \spad{a} is a countable cardinal,
        ++ i.e. an integer or \spad{Aleph 0}.
        ++
        ++X c2:=2::CardinalNumber
        ++X countable? c2
        ++X A0:=Aleph 0
        ++X countable? A0
        ++X A1:=Aleph 1
        ++X countable? A1

    generalizedContinuumHypothesisAssumed?: () -> Boolean
        ++ generalizedContinuumHypothesisAssumed?()
        ++ tests if the hypothesis is currently assumed.
        ++
        ++X generalizedContinuumHypothesisAssumed?

    generalizedContinuumHypothesisAssumed:  Boolean -> Boolean
        ++ generalizedContinuumHypothesisAssumed(bool)
        ++ is used to dictate whether the hypothesis is to be assumed.
        ++
        ++X generalizedContinuumHypothesisAssumed true
        ++X a:=Aleph 0
        ++X c:=2**a
        ++X f:=2**c
== add
    NNI ==> NonNegativeInteger
    FINord   ==> -1
    DUMMYval ==> -1

    Rep := Record(order: Integer, ival: Integer)
```

```
GCHypothesis: Reference(Boolean) := ref false

-- Creation
0           == [FINord, 0]
1           == [FINord, 1]
coerce(n:NonNegativeInteger):% == [FINord, n]
Aleph n     == [n, DUMMYval]

-- Output
ALEPHexpr := "Aleph"::OutputForm

coerce(x: %): OutputForm ==
    x.order = FINord => (x.ival)::OutputForm
    prefix(ALEPHexpr, [(x.order)::OutputForm])

-- Manipulation
x = y ==
    x.order ^= y.order => false
    finite? x          => x.ival = y.ival
    true     -- equal transfinites
x < y ==
    x.order < y.order => true
    x.order > y.order => false
    finite? x         => x.ival < y.ival
    false    -- equal transfinites
x:% + y:% ==
    finite? x and finite? y => [FINord, x.ival+y.ival]
    max(x, y)
x - y ==
    x < y     => "failed"
    finite? x => [FINord, x.ival-y.ival]
    x > y     => x
    "failed" -- equal transfinites
x:% * y:% ==
    finite? x and finite? y => [FINord, x.ival*y.ival]
    x = 0 or y = 0          => 0
    max(x, y)
n:NonNegativeInteger * x:% ==
    finite? x => [FINord, n*x.ival]
    n = 0     => 0
    x
x**y ==
    y = 0 =>
        x ^= 0 => 1
        error "0**0 not defined for cardinal numbers."
    finite? y =>
        not finite? x => x
        [FINord,x.ival**(y.ival):NNI]
    x = 0 => 0
```

```
            x = 1 => 1
            GCHypothesis() => [max(x.order-1, y.order) + 1, DUMMYval]
            error "Transfinite exponentiation only implemented under GCH"

        finite? x    == x.order = FINord
        countable? x == x.order < 1

        retract(x:%):NonNegativeInteger ==
          finite? x => (x.ival)::NNI
          error "Not finite"

        retractIfCan(x:%):Union(NonNegativeInteger, "failed") ==
          finite? x => (x.ival)::NNI
          "failed"

        -- State manipulation
        generalizedContinuumHypothesisAssumed?() == GCHypothesis()
        generalizedContinuumHypothesisAssumed b == (GCHypothesis() := b)
```

———-

— CARD.dotabb —

```
"CARD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CARD"]
"ALGEBRA-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALGEBRA"]
"CARD" -> "ALGEBRA-"
```

———-

4.2 domain CARTEN CartesianTensor

— CartesianTensor.input —

```
)set break resume
)sys rm -f CartesianTensor.output
)spool CartesianTensor.output
)set message test on
)set message auto off
)clear all
--S 1 of 48
CT := CARTEN(i0 := 1, 2, Integer)
--R
--R
--R   (1)  CartesianTensor(1,2,Integer)
```

```
--R                                                                    Type: Domain
--E 1

--S 2 of 48
t0: CT := 8
--R
--R
--R   (2)  8
--R                                          Type: CartesianTensor(1,2,Integer)
--E 2

--S 3 of 48
rank t0
--R
--R
--R   (3)  0
--R                                                  Type: NonNegativeInteger
--E 3

--S 4 of 48
v: DirectProduct(2, Integer) := directProduct [3,4]
--R
--R
--R   (4)  [3,4]
--R                                             Type: DirectProduct(2,Integer)
--E 4

--S 5 of 48
Tv: CT := v
--R
--R
--R   (5)  [3,4]
--R                                          Type: CartesianTensor(1,2,Integer)
--E 5

--S 6 of 48
m: SquareMatrix(2, Integer) := matrix [ [1,2],[4,5] ]
--R
--R
--R        +1  2+
--R   (6)  |    |
--R        +4  5+
--R                                           Type: SquareMatrix(2,Integer)
--E 6

--S 7 of 48
Tm: CT := m
--R
--R
--R        +1  2+
```

```
--R   (7)  |    |
--R        +4  5+
--R                                          Type: CartesianTensor(1,2,Integer)
--E 7

--S 8 of 48
n: SquareMatrix(2, Integer) := matrix [ [2,3],[0,1] ]
--R
--R
--R        +2  3+
--R   (8)  |    |
--R        +0  1+
--R                                               Type: SquareMatrix(2,Integer)
--E 8

--S 9 of 48
Tn: CT := n
--R
--R
--R        +2  3+
--R   (9)  |    |
--R        +0  1+
--R                                          Type: CartesianTensor(1,2,Integer)
--E 9

--S 10 of 48
t1: CT := [2, 3]
--R
--R
--R   (10)  [2,3]
--R                                          Type: CartesianTensor(1,2,Integer)
--E 10

--S 11 of 48
rank t1
--R
--R
--R   (11)  1
--R                                                    Type: PositiveInteger
--E 11

--S 12 of 48
t2: CT := [t1, t1]
--R
--R
--R         +2  3+
--R   (12)  |    |
--R         +2  3+
--R                                          Type: CartesianTensor(1,2,Integer)
--E 12
```

```
--S 13 of 48
t3: CT := [t2, t2]
--R
--R
--R          +2  3+ +2  3+
--R   (13)  [|    |,|    |]
--R          +2  3+ +2  3+
--R                                          Type: CartesianTensor(1,2,Integer)
--E 13

--S 14 of 48
tt: CT := [t3, t3]; tt := [tt, tt]
--R
--R
--R          ++2  3+  +2  3++ ++2  3+  +2  3++
--R          ||    |  |    || ||    |  |    ||
--R          |+2  3+  +2  3+| |+2  3+  +2  3+|
--R   (14)  [|              |,|              |]
--R          |+2  3+  +2  3+| |+2  3+  +2  3+|
--R          ||    |  |    || ||    |  |    ||
--R          ++2  3+  +2  3++ ++2  3+  +2  3++
--R                                             Type: CartesianTensor(1,2,Integer)
--E 14

--S 15 of 48
rank tt
--R
--R
--R   (15)  5
--R                                                          Type: PositiveInteger
--E 15

--S 16 of 48
Tmn := product(Tm, Tn)
--R
--R
--R         ++2  3+    +4  6+ +
--R         ||    |    |    | |
--R         |+0  1+    +0  2+ |
--R   (16)  |                  |
--R         |+8  12+  +10  15+|
--R         ||     |  |      ||
--R         ++0  4 +  +0   5 ++
--R                                          Type: CartesianTensor(1,2,Integer)
--E 16

--S 17 of 48
Tmv := contract(Tm,2,Tv,1)
--R
```

```
--R
--R   (17)  [11,32]
--R                                          Type: CartesianTensor(1,2,Integer)
--E 17

--S 18 of 48
Tm*Tv
--R
--R
--R   (18)  [11,32]
--R                                          Type: CartesianTensor(1,2,Integer)
--E 18

--S 19 of 48
Tmv = m * v
--R
--R
--R   (19)  [11,32]= [11,32]
--R                                  Type: Equation(CartesianTensor(1,2,Integer))
--E 19

--S 20 of 48
t0()
--R
--R
--R   (20)  8
--R                                                        Type: PositiveInteger
--E 20

--S 21 of 48
t1(1+1)
--R
--R
--R   (21)  3
--R                                                        Type: PositiveInteger
--E 21

--S 22 of 48
t2(2,1)
--R
--R
--R   (22)  2
--R                                                        Type: PositiveInteger
--E 22

--S 23 of 48
t3(2,1,2)
--R
--R
--R   (23)  3
```

```
--R                                                   Type: PositiveInteger
--E 23

--S 24 of 48
Tmn(2,1,2,1)
--R
--R
--R   (24)  0
--R                                                Type: NonNegativeInteger
--E 24

--S 25 of 48
t0[]
--R
--R
--R   (25)  8
--R                                                   Type: PositiveInteger
--E 25

--S 26 of 48
t1[2]
--R
--R
--R   (26)  3
--R                                                   Type: PositiveInteger
--E 26

--S 27 of 48
t2[2,1]
--R
--R
--R   (27)  2
--R                                                   Type: PositiveInteger
--E 27

--S 28 of 48
t3[2,1,2]
--R
--R
--R   (28)  3
--R                                                   Type: PositiveInteger
--E 28

--S 29 of 48
Tmn[2,1,2,1]
--R
--R
--R   (29)  0
--R                                                Type: NonNegativeInteger
--E 29
```

```
--S 30 of 48
cTmn := contract(Tmn,1,2)
--R
--R
--R         +12  18+
--R   (30)  |      |
--R         +0   6 +
--R                                          Type: CartesianTensor(1,2,Integer)
--E 30

--S 31 of 48
trace(m) * n
--R
--R
--R         +12  18+
--R   (31)  |      |
--R         +0   6 +
--R                                              Type: SquareMatrix(2,Integer)
--E 31

--S 32 of 48
contract(Tmn,1,2) = trace(m) * n
--R
--R
--R         +12  18+  +12  18+
--R   (32)  |      |= |      |
--R         +0   6 +  +0   6 +
--R                                  Type: Equation(CartesianTensor(1,2,Integer))
--E 32

--S 33 of 48
contract(Tmn,1,3) = transpose(m) * n
--R
--R
--R         +2  7 +  +2  7 +
--R   (33)  |     |= |     |
--R         +4  11+  +4  11+
--R                                  Type: Equation(CartesianTensor(1,2,Integer))
--E 33

--S 34 of 48
contract(Tmn,1,4) = transpose(m) * transpose(n)
--R
--R
--R         +14  4+  +14  4+
--R   (34)  |     |= |     |
--R         +19  5+  +19  5+
--R                                  Type: Equation(CartesianTensor(1,2,Integer))
--E 34
```

```
--S 35 of 48
contract(Tmn,2,3) = m * n
--R
--R
--R         +2  5 +  +2  5 +
--R   (35)  |     |= |     |
--R         +8  17+  +8  17+
--R                                Type: Equation(CartesianTensor(1,2,Integer))
--E 35

--S 36 of 48
contract(Tmn,2,4) = m * transpose(n)
--R
--R
--R         +8   2+  +8   2+
--R   (36)  |     |= |     |
--R         +23  5+  +23  5+
--R                                Type: Equation(CartesianTensor(1,2,Integer))
--E 36

--S 37 of 48
contract(Tmn,3,4) = trace(n) * m
--R
--R
--R         +3   6 +  +3   6 +
--R   (37)  |      |= |      |
--R         +12  15+  +12  15+
--R                                Type: Equation(CartesianTensor(1,2,Integer))
--E 37

--S 38 of 48
tTmn := transpose(Tmn,1,3)
--R
--R
--R         ++2  3 +  +4   6 ++
--R         ||     |  |      ||
--R         |+8  12+  +10  15+|
--R   (38)  |                 |
--R         |+0  1+    +0  2+ |
--R         ||    |    |    | |
--R         ++0  4+    +0  5+ +
--R                                          Type: CartesianTensor(1,2,Integer)
--E 38

--S 39 of 48
transpose Tmn
--R
--R
--R         ++2  8+   +4  10++
```

```
--R         ||    |   |     ||
--R         |+0  0+   +0  0 +|
--R   (39)  |                |
--R         |+3  12+  +6  15+|
--R         ||     |  |     ||
--R         ++1  4 +  +2  5 ++
--R                                          Type: CartesianTensor(1,2,Integer)
--E 39

--S 40 of 48
transpose Tm = transpose m
--R
--R
--R         +1  4+  +1  4+
--R   (40)  |    |= |    |
--R         +2  5+  +2  5+
--R                                  Type: Equation(CartesianTensor(1,2,Integer))
--E 40

--S 41 of 48
rTmn := reindex(Tmn, [1,4,2,3])
--R
--R
--R         ++2  0+   +3  1+ +
--R         ||    |   |    | |
--R         |+4  0+   +6  2+ |
--R   (41)  |                |
--R         |+8   0+  +12  4+|
--R         ||     |  |     ||
--R         ++10  0+  +15  5++
--R                                          Type: CartesianTensor(1,2,Integer)
--E 41

--S 42 of 48
tt := transpose(Tm)*Tn - Tn*transpose(Tm)
--R
--R
--R         +- 6  - 16+
--R   (42)  |         |
--R         + 2    6  +
--R                                          Type: CartesianTensor(1,2,Integer)
--E 42

--S 43 of 48
Tv*(tt+Tn)
--R
--R
--R   (43)  [- 4,- 11]
--R                                          Type: CartesianTensor(1,2,Integer)
--E 43
```

```
--S 44 of 48
reindex(product(Tn,Tn),[4,3,2,1])+3*Tn*product(Tm,Tm)
--R
--R
--R         ++46   84 +  +57   114++
--R         ||        |  |        ||
--R         |+174  212+  +228  285+|
--R   (44)  |                      |
--R         | +18  24+    +17  30+ |
--R         | |      |    |      | |
--R         + +57  63+    +63  76+ +
--R                                            Type: CartesianTensor(1,2,Integer)
--E 44

--S 45 of 48
delta:  CT := kroneckerDelta()
--R
--R
--R         +1  0+
--R   (45)  |    |
--R         +0  1+
--R                                            Type: CartesianTensor(1,2,Integer)
--E 45

--S 46 of 48
contract(Tmn, 2, delta, 1) = reindex(Tmn, [1,3,4,2])
--R
--R
--R         + +2  4+   +0  0++  + +2  4+   +0  0++
--R         | |    |   |    ||  | |    |   |    ||
--R         | +3  6+   +1  2+|  | +3  6+   +1  2+|
--R   (46)  |                |= |                |
--R         |+8   10+  +0  0+|  |+8   10+  +0  0+|
--R         ||      |  |    ||  ||      |  |    ||
--R         ++12  15+  +4  5++  ++12  15+  +4  5++
--R                                 Type: Equation(CartesianTensor(1,2,Integer))
--E 46

--S 47 of 48
epsilon:CT := leviCivitaSymbol()
--R
--R
--R         + 0   1+
--R   (47)  |      |
--R         +- 1  0+
--R                                            Type: CartesianTensor(1,2,Integer)
--E 47

--S 48 of 48
```

```
contract(epsilon*Tm*epsilon, 1,2) = 2 * determinant m
--R
--R
--R   (48)  - 6= - 6
--R                                   Type: Equation(CartesianTensor(1,2,Integer))
--E 48
)spool
)lisp (bye)
```

———-

— CartesianTensor.help —

```
=====================================================================
CartesianTensor examples
=====================================================================

CartesianTensor(i0,dim,R) provides Cartesian tensors with components
belonging to a commutative ring R.  Tensors can be described as a
generalization of vectors and matrices.  This gives a concise tensor
algebra for multilinear objects supported by the CartesianTensor
domain.  You can form the inner or outer product of any two tensors
and you can add or subtract tensors with the same number of components.
Additionally, various forms of traces and transpositions are useful.

The CartesianTensor constructor allows you to specify the minimum
index for subscripting.  In what follows we discuss in detail how to
manipulate tensors.

Here we construct the domain of Cartesian tensors of dimension 2 over the
integers, with indices starting at 1.

  CT := CARTEN(i0 := 1, 2, Integer)
   CartesianTensor(1,2,Integer)
                     Type: Domain

=====================================================================
Forming tensors
=====================================================================

Scalars can be converted to tensors of rank zero.

  t0: CT := 8
   8
                     Type: CartesianTensor(1,2,Integer)

  rank t0
   0
                     Type: NonNegativeInteger
```

```
Vectors (mathematical direct products, rather than one dimensional array
structures) can be converted to tensors of rank one.

  v: DirectProduct(2, Integer) := directProduct [3,4]
   [3, 4]
                       Type: DirectProduct(2,Integer)

  Tv: CT := v
   [3, 4]
                       Type: CartesianTensor(1,2,Integer)

Matrices can be converted to tensors of rank two.

  m: SquareMatrix(2, Integer) := matrix [ [1,2],[4,5] ]
   +1  2+
   |    |
   +4  5+
                       Type: SquareMatrix(2,Integer)

  Tm: CT := m
   +1  2+
   |    |
   +4  5+
                       Type: CartesianTensor(1,2,Integer)

  n: SquareMatrix(2, Integer) := matrix [ [2,3],[0,1] ]
   +2  3+
   |    |
   +0  1+
                       Type: SquareMatrix(2,Integer)

  Tn: CT := n
   +2  3+
   |    |
   +0  1+
                       Type: CartesianTensor(1,2,Integer)

In general, a tensor of rank k can be formed by making a list of
rank k-1 tensors or, alternatively, a k-deep nested list of lists.

  t1: CT := [2, 3]
   [2, 3]
                       Type: CartesianTensor(1,2,Integer)

  rank t1
   1
                       Type: PositiveInteger

  t2: CT := [t1, t1]
```

```
   +2  3+
   |    |
   +2  3+
                     Type: CartesianTensor(1,2,Integer)

  t3: CT := [t2, t2]

    +2  3+ +2  3+
   [|    |,|    |]
    +2  3+ +2  3+
                     Type: CartesianTensor(1,2,Integer)

  tt: CT := [t3, t3]; tt := [tt, tt]
    ++2  3+  +2  3++ ++2  3+  +2  3++
    ||    |  |    || ||    |  |    ||
    |+2  3+  +2  3+| |+2  3+  +2  3+|
   [|              |,|              |]
    |+2  3+  +2  3+| |+2  3+  +2  3+|
    ||    |  |    || ||    |  |    ||
    ++2  3+  +2  3++ ++2  3+  +2  3++
                     Type: CartesianTensor(1,2,Integer)

  rank tt
   5
                     Type: PositiveInteger

========================================================================
Multiplication
========================================================================

Given two tensors of rank k1 and k2, the outer product forms a new
tensor of rank k1+k2. Here

  Tmn(i,j,k,l) = Tm(i,j)Tn(k,l)

  Tmn := product(Tm, Tn)
    ++2  3+    +4  6+ +
    ||    |    |    | |
    |+0  1+    +0  2+ |
    |                 |
    |+8  12+  +10  15+|
    ||     |  |      ||
    ++0  4 +  +0   5 ++
                     Type: CartesianTensor(1,2,Integer)

The inner product (contract) forms a tensor of rank k1+k2-2.  This
product generalizes the vector dot product and matrix-vector product
by summing component products along two indices.

Here we sum along the second index of Tm and the first index of Tv. Here
```

```
 Tmv = sum {j=1..dim} Tm(i,j) Tv(j)

 Tmv := contract(Tm,2,Tv,1)
   [11,32]
                      Type: CartesianTensor(1,2,Integer)

The multiplication operator * is scalar multiplication or an inner
product depending on the ranks of the arguments.

If either argument is rank zero it is treated as scalar multiplication.
Otherwise, a*b is the inner product summing the last index of a with the
first index of b.

  Tm*Tv
   [11,32]
                     Type: CartesianTensor(1,2,Integer)

This definition is consistent with the inner product on matrices
and vectors.

  Tmv = m * v
   [11,32] = [11,32]
                     Type: Equation CartesianTensor(1,2,Integer)

========================================================================
Selecting Components
========================================================================

For tensors of low rank (that is, four or less), components can be selected
by applying the tensor to its indices.

  t0()
   8
                     Type: PositiveInteger

  t1(1+1)
   3
                     Type: PositiveInteger

  t2(2,1)
   2
                     Type: PositiveInteger

  t3(2,1,2)
    3
                     Type: PositiveInteger

  Tmn(2,1,2,1)
    0
```

```
                    Type: NonNegativeInteger

A general indexing mechanism is provided for a list of indices.

  t0[]
    8
                    Type: PositiveInteger

  t1[2]
    3
                    Type: PositiveInteger

  t2[2,1]
    2
                    Type: PositiveInteger

The general mechanism works for tensors of arbitrary rank, but is
somewhat less efficient since the intermediate index list must be created.

  t3[2,1,2]
    3
                    Type: PositiveInteger

  Tmn[2,1,2,1]
    0
                    Type: NonNegativeInteger

========================================================================
Contraction
========================================================================

A "contraction" between two tensors is an inner product, as we have
seen above.  You can also contract a pair of indices of a single
tensor.  This corresponds to a "trace" in linear algebra.  The
expression contract(t,k1,k2) forms a new tensor by summing the
diagonal given by indices in position k1 and k2.

This is the tensor given by
  xTmn = sum{k=1..dim} Tmn(k,k,i,j)

  cTmn := contract(Tmn,1,2)
    +12  18+
    |      |
    +0   6 +
                         Type: CartesianTensor(1,2,Integer)

Since Tmn is the outer product of matrix m and matrix n, the above is
equivalent to this.

  trace(m) * n
```

```
   +12  18+
   |      |
   +0   6 +
                        Type: SquareMatrix(2,Integer)
```

In this and the next few examples, we show all possible contractions of Tmn and their matrix algebra equivalents.

```
  contract(Tmn,1,2) = trace(m) * n
   +12  18+  +12  18+
   |      |= |      |
   +0   6 +  +0   6 +
                            Type: Equation CartesianTensor(1,2,Integer)

  contract(Tmn,1,3) = transpose(m) * n
   +2  7 +  +2  7 +
   |     |= |     |
   +4  11+  +4  11+
                            Type: Equation CartesianTensor(1,2,Integer)

  contract(Tmn,1,4) = transpose(m) * transpose(n)
   +14  4+  +14  4+
   |     |= |     |
   +19  5+  +19  5+
                            Type: Equation CartesianTensor(1,2,Integer)

  contract(Tmn,2,3) = m * n
   +2  5 +  +2  5 +
   |     |= |     |
   +8  17+  +8  17+
                            Type: Equation CartesianTensor(1,2,Integer)

  contract(Tmn,2,4) = m * transpose(n)
   +8   2+  +8   2+
   |     |= |     |
   +23  5+  +23  5+
                            Type: Equation CartesianTensor(1,2,Integer)

  contract(Tmn,3,4) = trace(n) * m
   +3   6 +  +3   6 +
   |      |= |      |
   +12  15+  +12  15+
                            Type: Equation CartesianTensor(1,2,Integer)
```

```
========================================================================
Transpositions
========================================================================
```

You can exchange any desired pair of indices using the transpose operation.

```
Here the indices in positions one and three are exchanged, that is,
  tTmn(i,j,k,l) = Tmn(k,j,i,l)

  tTmn := transpose(Tmn,1,3)
   ++2  3 +  +4   6 ++
   ||     |  |      ||
   |+8  12+  +10  15+|
   |                 |
   |+0  1+    +0  2+ |
   ||    |    |    | |
   ++0  4+    +0  5+ +
                              Type: CartesianTensor(1,2,Integer)

If no indices are specified, the first and last index are exchanged.

  transpose Tmn
   ++2  8+   +4  10++
   ||    |   |     ||
   |+0  0+   +0  0 +|
   |               |
   |+3  12+  +6  15+|
   ||     |  |     ||
   ++1  4 +  +2  5 ++
                              Type: CartesianTensor(1,2,Integer)

This is consistent with the matrix transpose.

  transpose Tm = transpose m
   +1  4+  +1  4+
   |    |= |    |
   +2  5+  +2  5+
                              Type: Equation CartesianTensor(1,2,Integer)


If a more complicated reordering of the indices is required, then the
reindex operation can be used.  This operation allows the indices to
be arbitrarily permuted.

  rTmn(i,j,k,l) = Tmn(i,l,j,k)

  rTmn := reindex(Tmn, [1,4,2,3])
   ++2  0+   +3  1+ +
   ||    |   |    | |
   |+4  0+   +6  2+ |
   |               |
   |+8   0+  +12  4+|
   ||     |  |     ||
   ++10  0+  +15  5++
                               Type: CartesianTensor(1,2,Integer)
```

```
========================================================================
Arithmetic
========================================================================

Tensors of equal rank can be added or subtracted so arithmetic
expressions can be used to produce new tensors.

  tt := transpose(Tm)*Tn - Tn*transpose(Tm)
   +- 6  - 16+
   |         |
   + 2    6  +
                              Type: CartesianTensor(1,2,Integer)


  Tv*(tt+Tn)
   [- 4,- 11]
                              Type: CartesianTensor(1,2,Integer)

  reindex(product(Tn,Tn),[4,3,2,1])+3*Tn*product(Tm,Tm)
   ++46   84 +  +57   114++
   ||        |  |        ||
   |+174  212+  +228  285+|
   |                      |
   | +18  24+    +17  30+ |
   | |      |    |      | |
   + +57  63+    +63  76+ +
                              Type: CartesianTensor(1,2,Integer)

========================================================================
Specific Tensors
========================================================================

Two specific tensors have properties which depend only on the dimension.

The Kronecker delta satisfies

             +-              -+
             |   1  if i  = j |
delta(i,j) = |                |
             |   0  if i ^= j |
             +-              -+


  delta:  CT := kroneckerDelta()
   +1  0+
   |    |
   +0  1+
                              Type: CartesianTensor(1,2,Integer)
```

```
This can be used to reindex via contraction.

  contract(Tmn, 2, delta, 1) = reindex(Tmn, [1,3,4,2])
   + +2  4+   +0  0++  + +2  4+   +0  0++
   | |    |   |    ||  | |    |   |    ||
   | +3  6+   +1  2+|  | +3  6+   +1  2+|
   |                |= |                |
   |+8   10+  +0  0+|  |+8   10+  +0  0+|
   ||      |  |    ||  ||      |  |    ||
   ++12  15+  +4  5++  ++12  15+  +4  5++
                                Type: Equation CartesianTensor(1,2,Integer)

The Levi Civita symbol determines the sign of a permutation of indices.

  epsilon:CT := leviCivitaSymbol()
   + 0   1+
   |     |
   +- 1  0+
                                 Type: CartesianTensor(1,2,Integer)

Here we have:

  epsilon(i1,...,idim)
     = +1  if i1,...,idim is an even permutation of i0,...,i0+dim-1
     = -1  if i1,...,idim is an  odd permutation of i0,...,i0+dim-1
     =  0  if i1,...,idim is not   a permutation of i0,...,i0+dim-1

This property can be used to form determinants.

  contract(epsilon*Tm*epsilon, 1,2) = 2 * determinant m
   - 6= - 6
                               Type: Equation CartesianTensor(1,2,Integer)


========================================================================
Properties of the CartesianTensor domain
========================================================================

GradedModule(R,E) denotes "E-graded R-module", that is, a collection
of R-modules indexed by an abelian monoid E. An element g of G[s] for
some specific s in E is said to be an element of G with degree s.
Sums are defined in each module G[s] so two elements of G can be added
if they have the same degree.  Morphisms can be defined and composed
by degree to give the mathematical category of graded modules.

GradedAlgebra(R,E) denotes "E-graded R-algebra".  A graded algebra is
a graded module together with a degree preserving R-bilinear map,
called the product.

  degree(product(a,b))    = degree(a) + degree(b)
```

```
  product(r*a,b)          = product(a,r*b) = r*product(a,b)
  product(a1+a2,b)        = product(a1,b) + product(a2,b)
  product(a,b1+b2)        = product(a,b1) + product(a,b2)
  product(a,product(b,c)) = product(product(a,b),c)

The domain CartesianTensor(i0, dim, R) belongs to the category
GradedAlgebra(R, NonNegativeInteger).  The non-negative integer degree
is the tensor rank and the graded algebra product is the tensor outer
product.  The graded module addition captures the notion that only
tensors of equal rank can be added.

If V is a vector space of dimension dim over R, then the tensor module
T[k](V) is defined as

 T[0](V) = R
  T[k](V) = T[k-1](V) * V


where * denotes the R-module tensor product. CartesianTensor(i0,dim,R)
is the graded algebra in which the degree k module is T[k](V).

========================================================================
Tensor Calculus
========================================================================

It should be noted here that often tensors are used in the context of
tensor-valued manifold maps.  This leads to the notion of covariant
and contravariant bases with tensor component functions transforming
in specific ways under a change of coordinates on the manifold.  This
is no more directly supported by the CartesianTensor domain than it is
by the Vector domain.  However, it is possible to have the components
implicitly represent component maps by choosing a polynomial or
expression type for the components.  In this case, it is up to the
user to satisfy any constraints which arise on the basis of this
interpretation.

See Also
o )show CartesianTensor
```

4.2.1 CartesianTensor (CARTEN)



Exports:

0	1	coerce	contract	degree
elt	hash	kroneckerDelta	latex	leviCivitaSymbol
product	rank	ravel	reindex	retract
retractIfCan	sample	transpose	unravel	?~=?
?.?	?*?	?+?	?-?	-?
?=?				

— domain CARTEN CartesianTensor —

```
)abbrev domain CARTEN CartesianTensor
++ Author: Stephen M. Watt
++ Date Created: December 1986
++ Date Last Updated: May 15, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: tensor, graded algebra
++ Examples:
++ References:
++ Description:
++ CartesianTensor(minix,dim,R) provides Cartesian tensors with
++ components belonging to a commutative ring R.  These tensors
++ can have any number of indices.  Each index takes values from
++ \spad{minix} to \spad{minix + dim - 1}.

CartesianTensor(minix, dim, R): Exports == Implementation where
    NNI ==> NonNegativeInteger
    I   ==> Integer
    DP  ==> DirectProduct
    SM  ==> SquareMatrix

    minix: Integer
    dim: NNI
```

```
R: CommutativeRing

Exports ==> Join(GradedAlgebra(R, NNI), GradedModule(I, NNI)) with

    coerce: DP(dim, R) -> %
        ++ coerce(v) views a vector as a rank 1 tensor.
        ++
        ++X v:DirectProduct(2,Integer):=directProduct [3,4]
        ++X tv:CartesianTensor(1,2,Integer):=v

    coerce: SM(dim, R)  -> %
        ++ coerce(m) views a matrix as a rank 2 tensor.
        ++
        ++X v:SquareMatrix(2,Integer):=[[1,2],[3,4]]
        ++X tv:CartesianTensor(1,2,Integer):=v

    coerce: List R -> %
        ++ coerce([r_1,...,r_dim]) allows tensors to be constructed
        ++ using lists.
        ++
        ++X v:=[2,3]
        ++X tv:CartesianTensor(1,2,Integer):=v

    coerce: List % -> %
        ++ coerce([t_1,...,t_dim]) allows tensors to be constructed
        ++ using lists.
        ++
        ++X v:=[2,3]
        ++X tv:CartesianTensor(1,2,Integer):=v
        ++X tm:CartesianTensor(1,2,Integer):=[tv,tv]

    rank: % -> NNI
        ++ rank(t) returns the tensorial rank of t (that is, the
        ++ number of indices).  This is the same as the graded module
        ++ degree.
        ++
        ++X CT:=CARTEN(1,2,Integer)
        ++X t0:CT:=8
        ++X rank t0

    elt: (%) -> R
        ++ elt(t) gives the component of a rank 0 tensor.
        ++
        ++X tv:CartesianTensor(1,2,Integer):=8
        ++X elt(tv)
        ++X tv[]

    elt: (%, I) -> R
        ++ elt(t,i) gives a component of a rank 1 tensor.
        ++
```

```
    ++X v:=[2,3]
    ++X tv:CartesianTensor(1,2,Integer):=v
    ++X elt(tv,2)
    ++X tv[2]

elt: (%, I, I) -> R
    ++ elt(t,i,j) gives a component of a rank 2 tensor.
    ++
    ++X v:=[2,3]
    ++X tv:CartesianTensor(1,2,Integer):=v
    ++X tm:CartesianTensor(1,2,Integer):=[tv,tv]
    ++X elt(tm,2,2)
    ++X tm[2,2]

elt: (%, I, I, I) -> R
    ++ elt(t,i,j,k) gives a component of a rank 3 tensor.
    ++
    ++X v:=[2,3]
    ++X tv:CartesianTensor(1,2,Integer):=v
    ++X tm:CartesianTensor(1,2,Integer):=[tv,tv]
    ++X tn:CartesianTensor(1,2,Integer):=[tm,tm]
    ++X elt(tn,2,2,2)
    ++X tn[2,2,2]

elt: (%, I, I, I, I) -> R
    ++ elt(t,i,j,k,l) gives a component of a rank 4 tensor.
    ++
    ++X v:=[2,3]
    ++X tv:CartesianTensor(1,2,Integer):=v
    ++X tm:CartesianTensor(1,2,Integer):=[tv,tv]
    ++X tn:CartesianTensor(1,2,Integer):=[tm,tm]
    ++X tp:CartesianTensor(1,2,Integer):=[tn,tn]
    ++X elt(tp,2,2,2,2)
    ++X tp[2,2,2,2]

elt: (%, List I) -> R
    ++ elt(t,[i1,...,iN]) gives a component of a rank \spad{N} tensor.
    ++
    ++X v:=[2,3]
    ++X tv:CartesianTensor(1,2,Integer):=v
    ++X tm:CartesianTensor(1,2,Integer):=[tv,tv]
    ++X tn:CartesianTensor(1,2,Integer):=[tm,tm]
    ++X tp:CartesianTensor(1,2,Integer):=[tn,tn]
    ++X tq:CartesianTensor(1,2,Integer):=[tp,tp]
    ++X elt(tq,[2,2,2,2,2])

-- This specializes the documentation from GradedAlgebra.
product: (%,%) -> %
    ++ product(s,t) is the outer product of the tensors s and t.
    ++ For example, if \spad{r = product(s,t)} for rank 2 tensors
```

```
        ++ s and t, then \spad{r} is a rank 4 tensor given by
        ++     \spad{r(i,j,k,l) = s(i,j)*t(k,l)}.
        ++
        ++X m:SquareMatrix(2,Integer):=matrix [[1,2],[4,5]]
        ++X Tm:CartesianTensor(1,2,Integer):=m
        ++X n:SquareMatrix(2,Integer):=matrix [[2,3],[0,1]]
        ++X Tn:CartesianTensor(1,2,Integer):=n
        ++X Tmn:=product(Tm,Tn)

    "*": (%, %) -> %
        ++ s*t is the inner product of the tensors s and t which contracts
        ++ the last index of s with the first index of t, that is,
        ++     \spad{t*s = contract(t,rank t, s, 1)}
        ++     \spad{t*s = sum(k=1..N, t[i1,..,iN,k]*s[k,j1,..,jM])}
        ++ This is compatible with the use of \spad{M*v} to denote
        ++ the matrix-vector inner product.
        ++
        ++X m:SquareMatrix(2,Integer):=matrix [[1,2],[4,5]]
        ++X Tm:CartesianTensor(1,2,Integer):=m
        ++X v:DirectProduct(2,Integer):=directProduct [3,4]
        ++X Tv:CartesianTensor(1,2,Integer):=v
        ++X Tm*Tv

    contract:  (%, Integer, %, Integer) -> %
        ++ contract(t,i,s,j) is the inner product of tenors s and t
        ++ which sums along the \spad{k1}-th index of
        ++ t and the \spad{k2}-th index of s.
        ++ For example, if \spad{r = contract(s,2,t,1)} for rank 3 tensors
        ++ rank 3 tensors \spad{s} and \spad{t}, then \spad{r} is
        ++ the rank 4 \spad{(= 3 + 3 - 2)} tensor  given by
        ++     \spad{r(i,j,k,l) = sum(h=1..dim,s(i,h,j)*t(h,k,l))}.
        ++
        ++X m:SquareMatrix(2,Integer):=matrix [[1,2],[4,5]]
        ++X Tm:CartesianTensor(1,2,Integer):=m
        ++X v:DirectProduct(2,Integer):=directProduct [3,4]
        ++X Tv:CartesianTensor(1,2,Integer):=v
        ++X Tmv:=contract(Tm,2,Tv,1)

    contract:  (%, Integer, Integer)    -> %
        ++ contract(t,i,j) is the contraction of tensor t which
        ++ sums along the \spad{i}-th and \spad{j}-th indices.
        ++ For example,  if
        ++ \spad{r = contract(t,1,3)} for a rank 4 tensor t, then
        ++ \spad{r} is the rank 2 \spad{(= 4 - 2)} tensor given by
        ++     \spad{r(i,j) = sum(h=1..dim,t(h,i,h,j))}.
        ++
        ++X m:SquareMatrix(2,Integer):=matrix [[1,2],[4,5]]
        ++X Tm:CartesianTensor(1,2,Integer):=m
        ++X v:DirectProduct(2,Integer):=directProduct [3,4]
        ++X Tv:CartesianTensor(1,2,Integer):=v
```

```
    ++X Tmv:=contract(Tm,2,1)

transpose: % -> %
    ++ transpose(t) exchanges the first and last indices of t.
    ++ For example, if \spad{r = transpose(t)} for a rank 4
    ++ tensor t, then \spad{r} is the rank 4 tensor given by
    ++     \spad{r(i,j,k,l) = t(l,j,k,i)}.
    ++
    ++X m:SquareMatrix(2,Integer):=matrix [[1,2],[4,5]]
    ++X Tm:CartesianTensor(1,2,Integer):=m
    ++X transpose(Tm)

transpose: (%, Integer, Integer) -> %
    ++ transpose(t,i,j) exchanges the \spad{i}-th and \spad{j}-th
    ++ indices of t. For example, if \spad{r = transpose(t,2,3)}
    ++ for a rank 4 tensor t, then \spad{r} is the rank 4 tensor
    ++ given by
    ++     \spad{r(i,j,k,l) = t(i,k,j,l)}.
    ++
    ++X m:SquareMatrix(2,Integer):=matrix [[1,2],[4,5]]
    ++X tm:CartesianTensor(1,2,Integer):=m
    ++X tn:CartesianTensor(1,2,Integer):=[tm,tm]
    ++X transpose(tn,1,2)

reindex: (%, List Integer) -> %
    ++ reindex(t,[i1,...,idim]) permutes the indices of t.
    ++ For example, if \spad{r = reindex(t, [4,1,2,3])}
    ++ for a rank 4 tensor t,
    ++ then \spad{r} is the rank for tensor given by
    ++     \spad{r(i,j,k,l) = t(l,i,j,k)}.
    ++
    ++X n:SquareMatrix(2,Integer):=matrix [[2,3],[0,1]]
    ++X tn:CartesianTensor(1,2,Integer):=n
    ++X p:=product(tn,tn)
    ++X reindex(p,[4,3,2,1])

kroneckerDelta:  () -> %
    ++ kroneckerDelta() is the rank 2 tensor defined by
    ++    \spad{kroneckerDelta()(i,j)}
    ++       \spad{= 1  if i = j}
    ++       \spad{= 0 if  i \^= j}
    ++
    ++X delta:CartesianTensor(1,2,Integer):=kroneckerDelta()

leviCivitaSymbol: () -> %
    ++ leviCivitaSymbol() is the rank \spad{dim} tensor defined by
    ++ \spad{leviCivitaSymbol()(i1,...idim) = +1/0/-1}
    ++ if \spad{i1,...,idim} is an even/is nota /is an odd permutation
    ++ of \spad{minix,...,minix+dim-1}.
    ++
```

```
        ++X lcs:CartesianTensor(1,2,Integer):=leviCivitaSymbol()

    ravel:     % -> List R
        ++ ravel(t) produces a list of components from a tensor such that
        ++   \spad{unravel(ravel(t)) = t}.
        ++
        ++X n:SquareMatrix(2,Integer):=matrix [[2,3],[0,1]]
        ++X tn:CartesianTensor(1,2,Integer):=n
        ++X ravel tn

    unravel:   List R -> %
        ++ unravel(t) produces a tensor from a list of
        ++ components such that
        ++   \spad{unravel(ravel(t)) = t}.

    sample:    () -> %
        ++ sample() returns an object of type %.

Implementation ==> add

    PERM  ==> Vector Integer  -- 1-based entries from 1..n
    INDEX ==> Vector Integer  -- 1-based entries from minix..minix+dim-1


    get   ==> elt$Rep
    set_! ==> setelt$Rep

    -- Use row-major order:
    --   x[h,i,j] <-> x[(h-minix)*dim**2+(i-minix)*dim+(j-minix)]

    Rep := IndexedVector(R,0)

    n:     Integer
    r,s:   R
    x,y,z: %

    ---- Local stuff
    dim2: NNI := dim**2
    dim3: NNI := dim**3
    dim4: NNI := dim**4

    sample()==kroneckerDelta()$%
    int2index(n: Integer, indv: INDEX): INDEX ==
        n < 0 => error "Index error (too small)"
        rnk := #indv
        for i in 1..rnk repeat
            qr := divide(n, dim)
            n  := qr.quotient
            indv.((rnk-i+1) pretend NNI) := qr.remainder + minix
        n ^= 0 => error "Index error (too big)"
```

```
    indv

index2int(indv: INDEX): Integer ==
    n: I := 0
    for i in 1..#indv repeat
        ix := indv.i - minix
        ix<0 or ix>dim-1 => error "Index error (out of range)"
        n := dim*n + ix
    n

lengthRankOrElse(v: Integer): NNI ==
    v = 1    => 0
    v = dim  => 1
    v = dim2 => 2
    v = dim3 => 3
    v = dim4 => 4
    rx := 0
    while v ^= 0 repeat
        qr := divide(v, dim)
        v  := qr.quotient
        if v ^= 0 then
            qr.remainder ^= 0 => error "Rank is not a whole number"
            rx := rx + 1
    rx

-- l must be a list of the numbers 1..#l
mkPerm(n: NNI, l: List Integer): PERM ==
    #l ^= n =>
        error "The list is not a permutation."
    p:    PERM           := new(n, 0)
    seen: Vector Boolean := new(n, false)
    for i in 1..n for e in l repeat
        e < 1 or e > n => error "The list is not a permutation."
        p.i    := e
        seen.e := true
    for e in 1..n repeat
        not seen.e => error "The list is not a permutation."
    p

-- permute s according to p into result t.
permute_!(t: INDEX, s: INDEX, p: PERM): INDEX ==
    for i in 1..#p repeat t.i := s.(p.i)
    t

-- permsign!(v) = 1, 0, or -1  according as
-- v is an even, is not, or is an odd permutation of minix..minix+#v-1.
permsign_!(v: INDEX): Integer ==
    -- sum minix..minix+#v-1.
    maxix := minix+#v-1
    psum  := (((maxix+1)*maxix - minix*(minix-1)) exquo 2)::Integer
```

```
        -- +/v ^= psum => 0
        n := 0
        for i in 1..#v repeat n := n + v.i
        n ^= psum => 0
        -- Bubble sort!  This is pretty grotesque.
        totTrans: Integer := 0
        nTrans:   Integer := 1
        while nTrans ^= 0 repeat
            nTrans := 0
            for i in 1..#v-1 for j in 2..#v repeat
                if v.i > v.j then
                    nTrans := nTrans + 1
                    e := v.i; v.i := v.j; v.j := e
            totTrans := totTrans + nTrans
        for i in 1..dim repeat
            if v.i ^= minix+i-1 then return 0
        odd? totTrans => -1
        1


    ---- Exported functions
    ravel x ==
        [get(x,i) for i in 0..#x-1]

    unravel l ==
        -- lengthRankOrElse #l gives sytnax error
        nz: NNI := # l
        lengthRankOrElse nz
        z := new(nz, 0)
        for i in 0..nz-1 for r in l repeat set_!(z, i, r)
        z

    kroneckerDelta() ==
        z := new(dim2, 0)
        for i in 1..dim for zi in 0.. by (dim+1) repeat set_!(z, zi, 1)
        z
    leviCivitaSymbol() ==
        nz := dim**dim
        z  := new(nz, 0)
        indv: INDEX := new(dim, 0)
        for i in 0..nz-1 repeat
            set_!(z, i, permsign_!(int2index(i, indv))::R)
        z

    -- from GradedModule
    degree x ==
        rank x

    rank x ==
        n := #x
```

```
    lengthRankOrElse n

elt(x) ==
    #x ^= 1    => error "Index error (the rank is not 0)"
    get(x,0)
elt(x, i: I) ==
    #x ^= dim  => error "Index error (the rank is not 1)"
    get(x,(i-minix))
elt(x, i: I, j: I) ==
    #x ^= dim2 => error "Index error (the rank is not 2)"
    get(x,(dim*(i-minix) + (j-minix)))
elt(x, i: I, j: I, k: I) ==
    #x ^= dim3 => error "Index error (the rank is not 3)"
    get(x,(dim2*(i-minix) + dim*(j-minix) + (k-minix)))
elt(x, i: I, j: I, k: I, l: I) ==
    #x ^= dim4 => error "Index error (the rank is not 4)"
    get(x,(dim3*(i-minix)+dim2*(j-minix)+dim*(k-minix)+(l-minix)))

elt(x, i: List I) ==
    #i ^= rank x => error "Index error (wrong rank)"
    n: I := 0
    for ii in i repeat
        ix := ii - minix
        ix<0 or ix>dim-1 => error "Index error (out of range)"
        n := dim*n + ix
    get(x,n)

coerce(lr: List R): % ==
    #lr ^= dim => error "Incorrect number of components"
    z := new(dim, 0)
    for r in lr for i in 0..dim-1 repeat set_!(z, i, r)
    z
coerce(lx: List %): % ==
    #lx ^= dim => error "Incorrect number of slices"
    rx := rank first lx
    for x in lx repeat
        rank x ^= rx => error "Inhomogeneous slice ranks"
    nx := # first lx
    z  := new(dim * nx, 0)
    for x in lx for offz in 0.. by nx repeat
        for i in 0..nx-1 repeat set_!(z, offz + i, get(x,i))
    z

retractIfCan(x:%):Union(R,"failed") ==
    zero? rank(x) => x()
    "failed"
Outf ==> OutputForm

mkOutf(x:%, i0:I, rnk:NNI): Outf ==
    odd? rnk =>
```

```
            rnk1  := (rnk-1) pretend NNI
            nskip := dim**rnk1
            [mkOutf(x, i0+nskip*i, rnk1) for i in 0..dim-1]::Outf
        rnk = 0 =>
            get(x,i0)::Outf
        rnk1  := (rnk-2) pretend NNI
        nskip := dim**rnk1
        matrix [[mkOutf(x, i0+nskip*(dim*i + j), rnk1)
                        for j in 0..dim-1] for i in 0..dim-1]
    coerce(x): Outf ==
        mkOutf(x, 0, rank x)

    0 == 0$R::Rep
    1 == 1$R::Rep

    --coerce(n: I): % == new(1, n::R)
    coerce(r: R): % == new(1,r)

    coerce(v: DP(dim,R)): % ==
        z := new(dim, 0)
        for i in 0..dim-1 for j in minIndex v .. maxIndex v repeat
            set_!(z, i, v.j)
        z
    coerce(m: SM(dim,R)): % ==
        z := new(dim**2, 0)
        offz := 0
        for i in 0..dim-1 repeat
            for j in 0..dim-1 repeat
                set_!(z, offz + j, m(i+1,j+1))
            offz := offz + dim
        z

    x = y ==
        #x ^= #y => false
        for i in 0..#x-1 repeat
           if get(x,i) ^= get(y,i) then return false
        true
    x + y ==
        #x ^= #y => error "Rank mismatch"
        -- z := [xi + yi for xi in x for yi in y]
        z := new(#x, 0)
        for i in 0..#x-1 repeat set_!(z, i, get(x,i) + get(y,i))
        z
    x - y ==
        #x ^= #y => error "Rank mismatch"
        -- [xi - yi for xi in x for yi in y]
        z := new(#x, 0)
        for i in 0..#x-1 repeat set_!(z, i, get(x,i) - get(y,i))
        z
    - x ==
```

```
    -- [-xi for xi in x]
    z := new(#x, 0)
    for i in 0..#x-1 repeat set_!(z, i, -get(x,i))
    z
n * x ==
    -- [n * xi for xi in x]
    z := new(#x, 0)
    for i in 0..#x-1 repeat set_!(z, i, n * get(x,i))
    z
x * n ==
    -- [n * xi for xi in x]
    z := new(#x, 0)
    for i in 0..#x-1 repeat set_!(z, i, n* get(x,i))  -- Commutative!!
    z
r * x ==
    -- [r * xi for xi in x]
    z := new(#x, 0)
    for i in 0..#x-1 repeat set_!(z, i, r * get(x,i))
    z
x * r ==
    -- [xi*r for xi in x]
    z := new(#x, 0)
    for i in 0..#x-1 repeat set_!(z, i, r* get(x,i))  -- Commutative!!
    z
product(x, y) ==
    nx := #x; ny := #y
    z  := new(nx * ny, 0)
    for i in 0..nx-1 for ioff in 0.. by ny repeat
        for j in 0..ny-1 repeat
            set_!(z, ioff + j, get(x,i) * get(y,j))
    z
x * y ==
    rx := rank x
    ry := rank y
    rx = 0 => get(x,0) * y
    ry = 0 => x * get(y,0)
    contract(x, rx, y, 1)

contract(x, i, j) ==
    rx := rank x
    i < 1 or i > rx or j < 1 or j > rx or i = j =>
        error "Improper index for contraction"
    if i > j then (i,j) := (j,i)

    rl:= (rx- j) pretend NNI; nl:= dim**rl; zol:= 1;     xol:= zol
    rm:= (j-i-1) pretend NNI; nm:= dim**rm; zom:= nl;    xom:= zom*dim
    rh:= (i - 1) pretend NNI; nh:= dim**rh; zoh:= nl*nm
    xoh:= zoh*dim**2
    xok := nl*(1 + nm*dim)
    z   := new(nl*nm*nh, 0)
```

```
        for h in 1..nh _
        for xh in 0.. by xoh for zh in 0.. by zoh repeat
            for m in 1..nm _
            for xm in xh.. by xom for zm in zh.. by zom repeat
                for l in 1..nl _
                for xl in xm.. by xol for zl in zm.. by zol repeat
                    set_!(z, zl, 0)
                    for k in 1..dim for xk in xl.. by xok repeat
                        set_!(z, zl, get(z,zl) + get(x,xk))
        z

    contract(x, i, y, j) ==
        rx := rank x
        ry := rank y

        i < 1 or i > rx or j < 1 or j > ry =>
            error "Improper index for contraction"

        rly:= (ry-j) pretend NNI;  nly:= dim**rly;  oly:= 1;    zoly:= 1
        rhy:= (j -1) pretend NNI; nhy:= dim**rhy
        ohy:= nly*dim; zohy:= zoly*nly
        rlx:= (rx-i) pretend NNI;  nlx:= dim**rlx
        olx:= 1;        zolx:= zohy*nhy
        rhx:= (i -1) pretend NNI;  nhx:= dim**rhx
        ohx:= nlx*dim;  zohx:= zolx*nlx

        z := new(nlx*nhx*nly*nhy, 0)

        for dxh in 1..nhx _
        for xh in 0.. by ohx for zhx in 0.. by zohx repeat
            for dxl in 1..nlx _
            for xl in xh.. by olx for zlx in zhx.. by zolx repeat
                for dyh in 1..nhy _
                for yh in 0.. by ohy for zhy in zlx.. by zohy repeat
                    for dyl in 1..nly _
                    for yl in yh.. by oly for zly in zhy.. by zoly repeat
                        set_!(z, zly, 0)
                        for k in 1..dim _
                        for xk in xl.. by nlx for yk in yl.. by nly repeat
                            set_!(z, zly, get(z,zly)+get(x,xk)*get(y,yk))
        z

    transpose x ==
        transpose(x, 1, rank x)
    transpose(x, i, j) ==
        rx := rank x
        i < 1 or i > rx or j < 1 or j > rx or i = j =>
            error "Improper indicies for transposition"
        if i > j then (i,j) := (j,i)
```

```
            rl:= (rx- j) pretend NNI; nl:= dim**rl; zol:= 1;      zoi := zol*nl
            rm:= (j-i-1) pretend NNI; nm:= dim**rm; zom:= nl*dim; zoj := zom*nm
            rh:= (i - 1) pretend NNI; nh:= dim**rh; zoh:= nl*nm*dim**2
            z   := new(#x, 0)
            for h in 1..nh for zh in 0..  by zoh repeat _
            for m in 1..nm for zm in zh.. by zom repeat _
            for l in 1..nl for zl in zm.. by zol repeat _
                for p in 1..dim _
                for zp in zl.. by zoi for xp in zl.. by zoj repeat
                    for q in 1..dim _
                    for zq in zp.. by zoj for xq in xp.. by zoi repeat
                        set_!(z, zq, get(x,xq))
            z

        reindex(x, l) ==
            nx := #x
            z: % := new(nx, 0)

            rx := rank x
            p  := mkPerm(rx, l)
            xiv: INDEX := new(rx, 0)
            ziv: INDEX := new(rx, 0)

            -- Use permutation
            for i in 0..#x-1 repeat
                pi := index2int(permute_!(ziv, int2index(i,xiv),p))
                set_!(z, pi, get(x,i))
            z
```

———-

— CARTEN.dotabb —

```
"CARTEN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CARTEN"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"CARTEN" -> "IVECTOR"
```

———-

4.3 domain CHAR Character

— Character.input —

```
)set break resume
```

```
)sys rm -f Character.output
)spool Character.output
)set message test on
)set message auto off
)clear all
--S 1 of 13
chars := [char "a", char "A", char "X", char "8", char "+"]
--R
--R
--R   (1)  [a,A,X,8,+]
--R                                                    Type: List(Character)
--E 1

--S 2 of 13
space()
--R
--R
--R   (2)
--R                                                          Type: Character
--E 2

--S 3 of 13
quote()
--R
--R
--R   (3)  "
--R                                                          Type: Character
--E 3

--S 4 of 13
escape()
--R
--R
--R   (4)  _
--R                                                          Type: Character
--E 4

--S 5 of 13
[ord c for c in chars]
--R
--R
--R   (5)  [97,65,88,56,43]
--R                                                   Type: List(Integer)
--E 5

--S 6 of 13
[upperCase c for c in chars]
--R
--R
--R   (6)  [A,A,X,8,+]
```

```
--R                                                    Type: List(Character)
--E 6

--S 7 of 13
[lowerCase c for c in chars]
--R
--R
--R   (7)  [a,a,x,8,+]
--R                                                    Type: List(Character)
--E 7

--S 8 of 13
[alphabetic? c for c in chars]
--R
--R
--R   (8)  [true,true,true,false,false]
--R                                                      Type: List(Boolean)
--E 8

--S 9 of 13
[upperCase? c for c in chars]
--R
--R
--R   (9)  [false,true,true,false,false]
--R                                                      Type: List(Boolean)
--E 9

--S 10 of 13
[lowerCase? c for c in chars]
--R
--R
--R   (10)  [true,false,false,false,false]
--R                                                      Type: List(Boolean)
--E 10

--S 11 of 13
[digit? c for c in chars]
--R
--R
--R   (11)  [false,false,false,true,false]
--R                                                      Type: List(Boolean)
--E 11

--S 12 of 13
[hexDigit? c for c in chars]
--R
--R
--R   (12)  [true,true,false,true,false]
--R                                                      Type: List(Boolean)
--E 12
```

```
--S 13 of 13
[alphanumeric? c for c in chars]
--R
--R
--R   (13)  [true,true,true,true,false]
--R                                                    Type: List(Boolean)
--E 13
)spool
)lisp (bye)
```

———-

— Character.help —

```
=====================================================================
Character examples
=====================================================================

The members of the domain Character are values representing letters,
numerals and other text elements.

Characters can be obtained using String notation.

  chars := [char "a", char "A", char "X", char "8", char "+"]
   [a,A,X,8,+]
                      Type: List Character

Certain characters are available by name. This is the blank character.

  space()

                      Type: Character

This is the quote that is used in strings.

  quote()
   "
                      Type: Character

This is the escape character that allows quotes and other characters
within strings.

  escape()
   -
                      Type: Character

Characters are represented as integers in a machine-dependent way.
The integer value can be obtained using the ord operation.  It is
```

```
always true that char(ord c) = c and ord(char i) = i, provided that i
is in the range 0..size()$Character-1.

  [ord c for c in chars]
   [97,65,88,56,43]
                     Type: List Integer

The lowerCase operation converts an upper case letter to the
corresponding lower case letter.  If the argument is not an upper case
letter, then it is returned unchanged.

  [upperCase c for c in chars]
    [A,A,X,8,+]
                     Type: List Character

The upperCase operation converts lower case letters to upper case.

  [lowerCase c for c in chars]
   [a,a,x,8,+]
                     Type: List Character

A number of tests are available to determine whether characters
belong to certain families.

  [alphabetic? c for c in chars]
   [true,true,true,false,false]
                     Type: List Boolean

  [upperCase? c for c in chars]
   [false,true,true,false,false]
                     Type: List Boolean

  [lowerCase? c for c in chars]
    [true,false,false,false,false]
                     Type: List Boolean

  [digit? c for c in chars]
   [false,false,false,true,false]
                     Type: List Boolean

  [hexDigit? c for c in chars]
   [true,true,false,true,false]
                     Type: List Boolean


  [alphanumeric? c for c in chars]
   [true,true,true,true,false]
                     Type: List Boolean

See Also:
o )help CharacterClass
```

```
o )help String
o )show Character
```

———-

4.3.1 Character (CHAR)



See

⇒ “CharacterClass” (CCLASS) 4.4.1 on page 367
⇒ “IndexedString” (ISTRING) 10.14.1 on page 1218
⇒ “String” (STRING) 20.31.1 on page 2574

Exports:

alphabetic?	alphanumeric?	char	coerce	digit?
escape	hash	hexDigit?	index	latex
lookup	lowerCase	lowerCase?	max	min
ord	quote	random	size	space
upperCase	upperCase?	?~=?	?<?	?<=?
?=?	?>?	?>=?		

— domain CHAR Character —

```
)abbrev domain CHAR Character
++ Author: Stephen M. Watt
++ Date Created: July 1986
++ Date Last Updated: June 20, 1991
++ Basic Operations: char
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: character, string
++ Examples:
++ References:
++ Description:
```

```
++ This domain provides the basic character data type.

Character: OrderedFinite() with
  ord: % -> Integer
    ++ ord(c) provides an integral code corresponding to the
    ++ character c.  It is always true that \spad{char ord c = c}.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [ord c for c in chars]
  char: Integer  -> %
    ++ char(i) provides a character corresponding to the integer
    ++ code i. It is always true that \spad{ord char i = i}.
    ++
    ++X [char c for c in [97,65,88,56,43]]
  char: String   -> %
    ++ char(s) provides a character from a string s of length one.
    ++
    ++X [char c for c in ["a","A","X","8","+"]]
  space: () -> %
    ++ space() provides the blank character.
    ++
    ++X space()
  quote: () -> %
    ++ quote() provides the string quote character, \spad{"}.
    ++
    ++X quote()
  escape: () -> %
    ++ escape() provides the escape character, \spad{_}, which
    ++ is used to allow quotes and other characters within
    ++ strings.
    ++
    ++X escape()
  upperCase: % -> %
    ++ upperCase(c) converts a lower case letter to the corresponding
    ++ upper case letter.  If c is not a lower case letter, then
    ++ it is returned unchanged.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [upperCase c for c in chars]
  lowerCase: % -> %
    ++ lowerCase(c) converts an upper case letter to the corresponding
    ++ lower case letter.  If c is not an upper case letter, then
    ++ it is returned unchanged.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [lowerCase c for c in chars]
  digit?: % -> Boolean
    ++ digit?(c) tests if c is a digit character,
    ++ i.e. one of 0..9.
    ++
```

```
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [digit? c for c in chars]
  hexDigit?: % -> Boolean
    ++ hexDigit?(c) tests if c is a hexadecimal numeral,
    ++ i.e. one of 0..9, a..f or A..F.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [hexDigit? c for c in chars]
  alphabetic?: % -> Boolean
    ++ alphabetic?(c) tests if c is a letter,
    ++ i.e. one of a..z or A..Z.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [alphabetic? c for c in chars]
  upperCase?: % -> Boolean
    ++ upperCase?(c) tests if c is an upper case letter,
    ++ i.e. one of A..Z.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [upperCase? c for c in chars]
  lowerCase?: % -> Boolean
    ++ lowerCase?(c) tests if c is an lower case letter,
    ++ i.e. one of a..z.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [lowerCase? c for c in chars]
  alphanumeric?: % -> Boolean
    ++ alphanumeric?(c) tests if c is either a letter or number,
    ++ i.e. one of 0..9, a..z or A..Z.
    ++
    ++X chars := [char "a", char "A", char "X", char "8", char "+"]
    ++X [alphanumeric? c for c in chars]

 == add

  Rep := SingleInteger  -- 0..255

  CC ==> CharacterClass()
  import CC

  OutChars:PrimitiveArray(OutputForm) :=
   construct [CODE_-CHAR(i)$Lisp for i in 0..255]

  minChar := minIndex OutChars

  a = b                  == a =$Rep b
  a < b                  == a <$Rep b
  size()                 == 256
  index n                == char((n - 1)::Integer)
  lookup c               == (1 + ord c)::PositiveInteger
```

```
  char(n:Integer)        == n::%
  ord c                  == convert(c)$Rep
  random()               == char(random()$Integer rem size())
  space                  == QENUM("   ", 0$Lisp)$Lisp
  quote                  == QENUM("_" ", 0$Lisp)$Lisp
  escape                 == QENUM("__ ", 0$Lisp)$Lisp
  coerce(c:%):OutputForm == OutChars(minChar + ord c)
  digit? c               == member?(c pretend Character, digit())
  hexDigit? c            == member?(c pretend Character, hexDigit())
  upperCase? c           == member?(c pretend Character, upperCase())
  lowerCase? c           == member?(c pretend Character, lowerCase())
  alphabetic? c          == member?(c pretend Character, alphabetic())
  alphanumeric? c        == member?(c pretend Character, alphanumeric())

  latex c ==
    concat("\mbox{‘", concat(new(1,c pretend Character)$String, "’}")_
       $String)$String

  char(s:String) ==
   (#s) = 1 => s(minIndex s) pretend %
   error "String is not a single character"

  upperCase c ==
    QENUM(PNAME(UPCASE(CODE_-CHAR(ord c)$Lisp)$Lisp)$Lisp,0$Lisp)$Lisp

  lowerCase c ==
    QENUM(PNAME(DOWNCASE(CODE_-CHAR(ord c)$Lisp)$Lisp)$Lisp,0$Lisp)$Lisp
```

———-

— CHAR.dotabb —

```
"CHAR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CHAR",shape=ellipse]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"CHAR" -> "FSAGG"
```

———-

4.4 domain CCLASS CharacterClass

— CharacterClass.input —

```
)set break resume
)sys rm -f CharacterClass.output
```

```
)spool CharacterClass.output
)set message test on
)set message auto off
)clear all
--S 1 of 16
cl1:=charClass[char "a",char "e",char "i",char "o",char "u",char "y"]
--R
--R
--R   (1)  "aeiouy"
--R                                                    Type: CharacterClass
--E 1

--S 2 of 16
cl2 := charClass "bcdfghjklmnpqrstvwxyz"
--R
--R
--R   (2)  "bcdfghjklmnpqrstvwxyz"
--R                                                    Type: CharacterClass
--E 2

--S 3 of 16
digit()
--R
--R
--R   (3)  "0123456789"
--R                                                    Type: CharacterClass
--E 3

--S 4 of 16
hexDigit()
--R
--R
--R   (4)  "0123456789ABCDEFabcdef"
--R                                                    Type: CharacterClass
--E 4

--S 5 of 16
upperCase()
--R
--R
--R   (5)  "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
--R                                                    Type: CharacterClass
--E 5

--S 6 of 16
lowerCase()
--R
--R
--R   (6)  "abcdefghijklmnopqrstuvwxyz"
--R                                                    Type: CharacterClass
```

```
--E 6

--S 7 of 16
alphabetic()
--R
--R
--R   (7)  "ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"
--R                                                    Type: CharacterClass
--E 7

--S 8 of 16
alphanumeric()
--R
--R
--R   (8)  "0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"
--R                                                    Type: CharacterClass
--E 8

--S 9 of 16
member?(char "a", cl1)
--R
--R
--R   (9)  true
--R                                                          Type: Boolean
--E 9

--S 10 of 16
member?(char "a", cl2)
--R
--R
--R   (10)  false
--R                                                          Type: Boolean
--E 10

--S 11 of 16
intersect(cl1, cl2)
--R
--R
--R   (11)  "y"
--R                                                    Type: CharacterClass
--E 11

--S 12 of 16
union(cl1,cl2)
--R
--R
--R   (12)  "abcdefghijklmnopqrstuvwxyz"
--R                                                    Type: CharacterClass
--E 12
```

```
--S 13 of 16
difference(cl1,cl2)
--R
--R
--R   (13)  "aeiou"
--R                                                    Type: CharacterClass
--E 13

--S 14 of 16
intersect(complement(cl1),cl2)
--R
--R
--R   (14)  "bcdfghjklmnpqrstvwxz"
--R                                                    Type: CharacterClass
--E 14

--S 15 of 16
insert!(char "a", cl2)
--R
--R
--R   (15)  "abcdfghjklmnpqrstvwxyz"
--R                                                    Type: CharacterClass
--E 15

--S 16 of 16
remove!(char "b", cl2)
--R
--R
--R   (16)  "acdfghjklmnpqrstvwxyz"
--R                                                    Type: CharacterClass
--E 16
)spool
)lisp (bye)
```

———-

— CharacterClass.help —

```
=====================================================================
CharacterClass examples
=====================================================================

The CharacterClass domain allows classes of characters to be defined
and manipulated efficiently.

Character classes can be created by giving either a string or a list
of characters.

  cl1:=charClass[char "a",char "e",char "i",char "o",char "u",char "y"]
```

```
   "aeiouy"
                      Type: CharacterClass

  cl2 := charClass "bcdfghjklmnpqrstvwxyz"
   "bcdfghjklmnpqrstvwxyz"
                      Type: CharacterClass

A number of character classes are predefined for convenience.

  digit()
   "0123456789"
                      Type: CharacterClass

  hexDigit()
   "0123456789ABCDEFabcdef"
                      Type: CharacterClass

  upperCase()
   "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
                      Type: CharacterClass

  lowerCase()
   "abcdefghijklmnopqrstuvwxyz"
                      Type: CharacterClass

  alphabetic()
   "ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"
                      Type: CharacterClass

  alphanumeric()
   "0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"
                      Type: CharacterClass

You can quickly test whether a character belongs to a class.

  member?(char "a", cl1)
   true
                      Type: Boolean

  member?(char "a", cl2)
   false
                      Type: Boolean

Classes have the usual set operations because the CharacterClass
domain belongs to the category FiniteSetAggregate(Character).

  intersect(cl1, cl2)
   "y"
                      Type: CharacterClass
```

```
  union(cl1,cl2)
   "abcdefghijklmnopqrstuvwxyz"
                      Type: CharacterClass

  difference(cl1,cl2)
   "aeiou"
                      Type: CharacterClass

  intersect(complement(cl1),cl2)
   "bcdfghjklmnpqrstvwxz"
                      Type: CharacterClass

You can modify character classes by adding or removing characters.


  insert!(char "a", cl2)
   "abcdfghjklmnpqrstvwxyz"
                      Type: CharacterClass

  remove!(char "b", cl2)
   "acdfghjklmnpqrstvwxyz"
                      Type: CharacterClass

See Also:
o )help Character
o )help String
o )show CharacterClass
```

———-

4.4.1 CharacterClass (CCLASS)



See

⇒ “Character” (CHAR) 4.3.1 on page 359
⇒ “IndexedString” (ISTRING) 10.14.1 on page 1218

⇒ "String" (STRING) 20.31.1 on page 2574

Exports:

any?	alphabetic	alphanumeric	bag	brace
brace	cardinality	charClass	coerce	complement
construct	convert	copy	count	count
dictionary	difference	digit	empty	empty?
eq?	eval	eval	eval	eval
every?	extract!	find	hash	hexDigit
index	insert!	inspect	intersect	latex
less?	lookup	lowerCase	map	map!
max	member?	members	min	more?
parts	random	reduce	reduce	reduce
remove	remove	remove!	remove!	removeDuplicates
sample	select	select!	set	size
size?	subset?	symmetricDifference	union	universe
upperCase	#?	?<?	?=?	?~=?

— domain CCLASS CharacterClass —

```
)abbrev domain CCLASS CharacterClass
++ Author: Stephen M. Watt
++ Date Created: July 1986
++ Date Last Updated: June 20, 1991
++ Basic Operations: charClass
++ Related Domains: Character, Bits
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain allows classes of characters to be defined and manipulated
++ efficiently.

CharacterClass: Join(SetCategory, ConvertibleTo String,
  FiniteSetAggregate Character, ConvertibleTo List Character) with
        charClass: String -> %
          ++ charClass(s) creates a character class which contains
          ++ exactly the characters given in the string s.
        charClass: List Character -> %
          ++ charClass(l) creates a character class which contains
          ++ exactly the characters given in the list l.
        digit: constant -> %
          ++ digit() returns the class of all characters
          ++ for which digit? is true.
        hexDigit: constant -> %
          ++ hexDigit() returns the class of all characters for which
          ++ hexDigit? is true.
```

```
    upperCase: constant -> %
      ++ upperCase() returns the class of all characters for which
      ++ upperCase? is true.
    lowerCase:  constant -> %
      ++ lowerCase() returns the class of all characters for which
      ++ lowerCase? is true.
    alphabetic  :  constant -> %
      ++ alphabetic() returns the class of all characters for which
      ++ alphabetic? is true.
    alphanumeric:  constant -> %
      ++ alphanumeric() returns the class of all characters for which
      ++ alphanumeric? is true.

  == add
    Rep := IndexedBits(0)
    N   := size()$Character

    a, b: %

    digit()         == charClass "0123456789"
    hexDigit()      == charClass "0123456789abcdefABCDEF"
    upperCase()     == charClass "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
    lowerCase()     == charClass "abcdefghijklmnopqrstuvwxyz"
    alphabetic()    == union(upperCase(), lowerCase())
    alphanumeric()  == union(alphabetic(), digit())

    a = b           == a =$Rep b

    member?(c, a)   == a(ord c)
    union(a,b)      == Or(a, b)
    intersect (a,b) == And(a, b)
    difference(a,b) == And(a, Not b)
    complement a    == Not a

    convert(cl):String ==
      construct(convert(cl)@List(Character))
    convert(cl:%):List(Character) ==
      [char(i) for i in 0..N-1 | cl.i]

    charClass(s: String) ==
      cl := new(N, false)
      for i in minIndex(s)..maxIndex(s) repeat cl(ord s.i) := true
      cl

    charClass(l: List Character) ==
      cl := new(N, false)
      for c in l repeat cl(ord c) := true
      cl

    coerce(cl):OutputForm == (convert(cl)@String)::OutputForm
```

```
        -- Stuff to make a legal SetAggregate view
        # a == (n := 0; for i in 0..N-1 | a.i repeat n := n+1; n)
        empty():% == charClass []
        brace():% == charClass []

        insert_!(c, a) == (a(ord c) := true; a)
        remove_!(c, a) == (a(ord c) := false; a)

        inspect(a) ==
            for i in 0..N-1 | a.i repeat
                 return char i
            error "Cannot take a character from an empty class."
        extract_!(a) ==
            for i in 0..N-1 | a.i repeat
                 a.i := false
                 return char i
            error "Cannot take a character from an empty class."

        map(f, a) ==
            b := new(N, false)
            for i in 0..N-1 | a.i repeat b(ord f char i) := true
            b

        temp: % := new(N, false)$Rep
        map_!(f, a) ==
            fill_!(temp, false)
            for i in 0..N-1 | a.i repeat temp(ord f char i) := true
            copyInto_!(a, temp, 0)

        parts a ==
            [char i for i in 0..N-1 | a.i]
```

———-

— CCLASS.dotabb —

```
"CCLASS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CCLASS"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"CCLASS" -> "FSAGG"
```

———-

4.5 domain CLIF CliffordAlgebra[?, ?]

4.5.1 Vector (linear) spaces

This information is originally from Paul Leopardi's presentation on the *Introduction to Clifford Algebras* and is included here as an outline with his permission. Further details are based on the book by Doran and Lasenby called *Geometric Algebra for Physicists*.

Consider the various kinds of products that can occur between vectors. There are scalar and vector products from 3D geometry. There are the complex and quaterion products. There is also the *outer* or *exterior* product.

Vector addition commutes:

$$a + b = b + a$$

Vector addtion is associative:

$$a + (b + c) = (a + b) + c$$

The identity vector exists:

$$a + 0 = a$$

Every vector has an inverse:

$$a + (-a) = 0$$

If we consider vectors to be directed line segments, thus establishing a geometric meaning for a vector, then each of these properties has a geometric meaning.

A multiplication operator exists between scalars and vectors with the properties:

$$\lambda(a + b) = \lambda a + \lambda b$$

$$(\lambda + \mu)a = \lambda a + \mu a$$

$$(\lambda\mu)a = \lambda(\mu a)$$

$$\text{If } 1\lambda = \lambda \text{ for all scalars } \lambda \text{ then } 1a = a \text{ for all vectors } a$$

These properties completely define a vector (linear) space. The + operation for scalar arithmetic is not the same as the + operation for vectors.

Definition: Isomorphic The vector space A is isomorphic to the vector space B if their exists a one-to-one correspondence between their elements which preserves sums and there is a one-to-one correspondence between the scalars which preserves sums and products.

Definition: Subspace Vector space B is a subspace of vector space A if all of the elements of B are contained in A and they share the same scalars.

Definition: Linear Combination Given vectors $a_1, \ldots, a_n$ the vector b is a linear combination of the vectors if we can find scalars λ_i such that

$$b = \lambda_1 a_1 + \ldots + \lambda_n a_n = \sum_{k=1}^{n} \lambda_i a_i$$

Definition: Linearly Independent If there exists scalars λ_i such that

$$\lambda_1 a_1 + \ldots + \lambda_n a_n = 0$$

and at least one of the λ_i is not zero then the vectors $a_1, \ldots, a_n$ are linearly dependent. If no such scalars exist then the vectors are linearly independent.

Definition: Span If every vector can be written as a linear combination of a fixed set of vectors $a_1, \ldots, a_n$ then this set of vectors is said to span the vector space.

Definition: Basis If a set of vectors $a_1, \ldots, a_n$ is linearly independent and spans a vector space A then the vectors form a basis for A.

Definition: Dimension The dimension of a vector space is the number of basis elements, which is unique since all bases of a vector space have the same number of elements.

4.5.2 Quadratic Forms[?]

For vector space $\mathbb{V}$ over field $\mathbb{F}$, characteristic $\neq 2$:

Map $f : \mathbb{V} \to \mathbb{F}$, with

$$f(\lambda x) = \lambda^2 f(x), \forall \lambda \in \mathbb{F}, x \in \mathbb{V}$$

$f(x) = b(x, x)$, where

$$b : \mathbb{V} \text{ x } \mathbb{V} \to \mathbb{F} \text{ , given by}$$

$$b(x, y) := \frac{1}{2}(f(x + y) - f(x) = f(y))$$

is a symmetric bilinear form

4.5.3 Quadratic spaces, Clifford Maps[?, ?]

A quadratic space is the pair($\mathbb{V}$,f), where f is a quadratic form on $\mathbb{V}$

A Clifford map is a vector space homomorphism

$$\rho : \mathbb{V} \to \mathbb{A}$$

where $\mathbb{A}$ is an associated algebra, and

$$(\rho v)^2 = f(v), \quad \forall v \in \mathbb{V}$$

4.5.4 Universal Clifford algebras[?]

The *universal Clifford algebra* $Cl(f)$ for the quadratic space $(\mathbb{V}, f)$ is the algebra generated by the image of the Clifford map ϕ_f such that $Cl(f)$ is the universal initial object such that $\forall$ suitable algebra $\mathbb{A}$ with Clifford map $\phi_{\mathbb{A}} \exists$ a homomorphism

$$P_{\mathbb{A}} : Cl(f) \to \mathbb{A}$$

$$\rho_{\mathbb{A}} = P_{\mathbb{A}} \circ \rho_f$$

4.5.5 Real Clifford algebras $\mathbb{R}_{p,q}$[?]

The real quadratic space $\mathbb{R}^{p,q}$ is $\mathbb{R}^{p+q}$ with

$$\phi(x) := -\sum_{k:=-q}^{-1} x_k^2 + \sum_{k=1}^{p} x_k^2$$

For each $p, q \in \mathbb{N}$, the real universal Clifford algebra for $\mathbb{R}^{p,q}$ is called $\mathbb{R}_{p,q}$

$\mathbb{R}_{p,q}$ is isomorphic to some matrix algebra over one of: $\mathbb{R}$,$\mathbb{R} \oplus \mathbb{R}$,$\mathbb{C}$, $\mathbb{H}$,$\mathbb{H} \oplus \mathbb{H}$

For example, $\mathbb{R}_{1,1} \cong \mathbb{R}(2)$

4.5.6 Notation for integer sets

For $S \subseteq \mathbb{Z}$, define

$$\sum_{k \in S} f_k := \sum_{k=\min\ S, k \in S}^{\max\ S} f_k$$

$$\prod_{k \in S} f_k := \prod_{k=\min\ S, k \in S}^{\max\ S} f_k$$

$$\mathbb{P}(S) :=\ \text{the}\ \ \textit{power set}\ \ \text{of}\ S$$

For $m \leq n \in \mathbb{Z}$, define

$$\zeta(m, n) := \{m, m+1, \ldots, n-1, n\} \backslash \{0\}$$

4.5.7 Frames for Clifford algebras[?, ?, ?]

A *frame* is an ordered basis $(\gamma_{-q}, \ldots, \gamma_p)$ for $\mathbb{R}^{p,q}$ which puts a quadratic form into the canonical form ϕ

For $p, q \in \mathbb{N}$, embed the frame for $\mathbb{R}^{p,q}$ into $\mathbb{R}_{p,q}$ via the maps

$$\gamma : \zeta(-q, p) \to \mathbb{R}^{p,q}$$

$$\rho : \mathbb{R}^{p,q} \to \mathbb{R}_{p,q}$$

$$(\rho\gamma k)^2 = \phi\gamma k =\ \text{sgn}\ k$$

4.5.8 Real frame groups[?, ?]

For $p, q \in \mathbb{N}$, define the real *frame group* $\mathbb{G}_{p,q}$ via the map

$$g : \zeta(-q, p) \to \mathbb{G}_{p,q}$$

with generators and relations

$$\langle \mu, g_k | \mu g_k = g_k \mu, \quad \mu^2 = 1,$$

$$(g_k)^2 = \begin{cases} \mu, & \text{if } k < 0 \\ 1 & \text{if } k > 0 \end{cases}$$

$$g_k g_m = \mu g_m g_k \quad \forall k \neq m \rangle$$

4.5.9 Canonical products[?, ?, ?]

The real frame group $\mathbb{G}_{p,q}$ has order 2^{p+q+1}

Each member w can be expressed as the canonically ordered product

$$w = \mu^a \prod_{k \in T} g_k$$

$$= \mu^a \prod_{k=-q, k\neq 0}^{p} g_k^{b_k}$$

where $T \subseteq \zeta(-q,p), a, b_k \in \{0,1\}$

4.5.10 Clifford algebra of frame group[?, ?, ?, ?]

For $p, q \in \mathbb{N}$ embed $\mathbb{G}_{p,q}$ into $\mathbb{R}_{p,q}$ via the map

$$\alpha \mathbb{G}_{p,q} \to \mathbb{R}_{p,q}$$

$$\alpha 1 := 1, \qquad \alpha\mu := -1$$

$$\alpha g_k := \rho\gamma_k, \qquad \alpha(gh) := (\alpha g)(\alpha h)$$

Define *basis elements* via the map


$$e : \mathbb{P}\zeta(-q,p) \to \mathbb{R}_{p,q}, \qquad e_T := \alpha \prod_{k \in T} g_k$$

Each $a \in \mathbb{R}_{p,q}$ can be expressed as

$$a = \sum_{T \subseteq \zeta(-q,p)} a_T e_T$$

4.5.11 Neutral matrix representations[?, ?, ?]

The *representation map* P_m and *representation matrix* R_m make the following diagram commute:



— **CliffordAlgebra.input** —

```
)set break resume
)sys rm -f CliffordAlgebra.output
)spool CliffordAlgebra.output
)set message test on
)set message auto off
)clear all
--S 1 of 36
K := Fraction Polynomial Integer
--R
--R
--R   (1)  Fraction(Polynomial(Integer))
--R                                                          Type: Domain
--E 1

--S 2 of 36
m := matrix [ [-1] ]
--R
--R
--R   (2)  [- 1]
--R                                                 Type: Matrix(Integer)
--E 2

--S 3 of 36
C := CliffordAlgebra(1, K, quadraticForm m)
--R
--R
--R   (3)  CliffordAlgebra(1,Fraction(Polynomial(Integer)),[[-1]])
--R                                                          Type: Domain
--E 3

--S 4 of 36
i: C := e(1)
--R
--R
```

```
--R   (4)  e
--R         1
--R                Type: CliffordAlgebra(1,Fraction(Polynomial(Integer)),[[-1]])
--E 4

--S 5 of 36
x := a + b * i
--R
--R
--R   (5)  a + b e
--R               1
--R                Type: CliffordAlgebra(1,Fraction(Polynomial(Integer)),[[-1]])
--E 5

--S 6 of 36
y := c + d * i
--R
--R
--R   (6)  c + d e
--R               1
--R                Type: CliffordAlgebra(1,Fraction(Polynomial(Integer)),[[-1]])
--E 6

--S 7 of 36
x * y
--R
--R
--R   (7)  - b d + a c + (a d + b c)e
--R                                   1
--R                Type: CliffordAlgebra(1,Fraction(Polynomial(Integer)),[[-1]])
--E 7
)clear all

--S 8 of 36
K := Fraction Polynomial Integer
--R
--R
--R   (1)  Fraction(Polynomial(Integer))
--R                                                                  Type: Domain
--E 8

--S 9 of 36
m := matrix [ [-1,0],[0,-1] ]
--R
--R
--R        +- 1   0 +
--R   (2)  |        |
--R        + 0   - 1+
--R                                                    Type: Matrix(Integer)
--E 9
```

```
--S 10 of 36
H  := CliffordAlgebra(2, K, quadraticForm m)
--R
--R
--R   (3)  CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--R                                                                  Type: Domain
--E 10

--S 11 of 36
i: H  := e(1)
--R
--R
--R   (4)  e
--R         1
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 11

--S 12 of 36
j: H  := e(2)
--R
--R
--R   (5)  e
--R         2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 12

--S 13 of 36
k: H  := i * j
--R
--R
--R   (6)  e e
--R         1 2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 13

--S 14 of 36
x := a + b * i + c * j + d * k
--R
--R
--R   (7)  a + b e  + c e  + d e e
--R              1      2      1 2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 14

--S 15 of 36
y := e + f * i + g * j + h * k
--R
--R
--R   (8)  e + f e  + g e  + h e e
```

```
--R              1      2      1 2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 15

--S 16 of 36
x + y
--R
--R
--R   (9)  e + a + (f + b)e  + (g + c)e  + (h + d)e e
--R                        1           2           1 2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 16

--S 17 of 36
x * y
--R
--R
--R   (10)
--R     - d h - c g - b f + a e + (c h - d g + a f + b e)e
--R                                                      1
--R   +
--R     (- b h + a g + d f + c e)e  + (a h + b g - c f + d e)e e
--R                               2                          1 2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 17

--S 18 of 36
y * x
--R
--R
--R   (11)
--R     - d h - c g - b f + a e + (- c h + d g + a f + b e)e
--R                                                       1
--R   +
--R     (b h + a g - d f + c e)e  + (a h - b g + c f + d e)e e
--R                              2                          1 2
--R       Type: CliffordAlgebra(2,Fraction(Polynomial(Integer)),[[-1,0],[0,-1]])
--E 18
)clear all

--S 19 of 36
K := Fraction Polynomial Integer
--R
--R
--R   (1)  Fraction(Polynomial(Integer))
--R                                                                  Type: Domain
--E 19

--S 20 of 36
Ext := CliffordAlgebra(3, K, quadraticForm 0)
```

```
--R
--R
--R   (2)
--R   CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--R                                                                  Type: Domain
--E 20

--S 21 of 36
i: Ext := e(1)
--R
--R
--R   (3)  e
--R         1
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 21

--S 22 of 36
j: Ext := e(2)
--R
--R
--R   (4)  e
--R         2
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 22

--S 23 of 36
k: Ext := e(3)
--R
--R
--R   (5)  e
--R         3
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 23

--S 24 of 36
x := x1*i + x2*j + x3*k
--R
--R
--R   (6)  x1 e  + x2 e  + x3 e
--R            1       2       3
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 24

--S 25 of 36
y := y1*i + y2*j + y3*k
--R
--R
--R   (7)  y1 e  + y2 e  + y3 e
--R            1       2       3
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
```

```
--E 25

--S 26 of 36
x + y
--R
--R
--R   (8)  (y1 + x1)e  + (y2 + x2)e  + (y3 + x3)e
--R                  1             2             3
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 26

--S 27 of 36
x * y + y * x
--R
--R
--R   (9)  0
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 27

--S 28 of 36
dual2 a == coefficient(a,[2,3]) * i + coefficient(a,[3,1]) * j + coefficient(a,[1,2]) * k
--R
--R                                                                    Type: Void
--E 28

--S 29 of 36
dual2(x*y)
--R
--R   Compiling function dual2 with type CliffordAlgebra(3,Fraction(
--R      Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]]) ->
--R      CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],
--R      [0,0,0]])
--R
--R   (11)  (x2 y3 - x3 y2)e  + (- x1 y3 + x3 y1)e  + (x1 y2 - x2 y1)e
--R                        1                    2                   3
--RType: CliffordAlgebra(3,Fraction(Polynomial(Integer)),[[0,0,0],[0,0,0],[0,0,0]])
--E 29
)clear all

--S 30 of 36
K := Fraction Integer
--R
--R
--R   (1)  Fraction(Integer)
--R                                                                 Type: Domain
--E 30

--S 31 of 36
g := matrix [ [1,0,0,0], [0,-1,0,0], [0,0,-1,0], [0,0,0,-1] ]
--R
```

```
--R
--R        +1   0    0    0 +
--R        |                 |
--R        |0  - 1   0    0 |
--R   (2)  |                 |
--R        |0   0   - 1   0 |
--R        |                 |
--R        +0   0    0   - 1+
--R                                                    Type: Matrix(Integer)
--E 31

--S 32 of 36
D := CliffordAlgebra(4,K, quadraticForm g)
--R
--R
--R   (3)
--R  CliffordAlgebra(4,Fraction(Integer),[[1,0,0,0],[0,-1,0,0],[0,0,-1,0],[0,0,0,-
--R  1]])
--R                                                              Type: Domain
--E 32

--S 33 of 36
gam := [e(i)$D for i in 1..4]
--R
--R
--R   (4)  [e ,e ,e ,e ]
--R          1  2  3  4
--RType: List(CliffordAlgebra(4,Fraction(Integer),[[1,0,0,0],[0,-1,0,0],[0,0,-1,0],[0,0,0,-1]]))
--E 33

--S 34 of 36
m := 1; n:= 2; r := 3; s := 4;
--R
--R
--R                                                    Type: PositiveInteger
--E 34

--S 35 of 36
lhs := reduce(+, [reduce(+, [ g(l,t)*gam(l)*gam(m)*gam(n)*gam(r)*gam(s)*gam(t) for l in 1..4]) for t in 1..4
--R
--R
--R   (6)  - 4e e e e
--R            1 2 3 4
--RType: CliffordAlgebra(4,Fraction(Integer),[[1,0,0,0],[0,-1,0,0],[0,0,-1,0],[0,0,0,-1]])
--E 35

--S 36 of 36
rhs := 2*(gam s * gam m*gam n*gam r + gam r*gam n*gam m*gam s)
--R
--R
```

```
--R   (7)  - 4e e e e
--R           1 2 3 4
--RType: CliffordAlgebra(4,Fraction(Integer),[[1,0,0,0],[0,-1,0,0],[0,0,-1,0],[0,0,0,-1]])
--E 36
)spool
)lisp (bye)
```

———-

— CliffordAlgebra.help —

```
========================================================================
CliffordAlgebra examples
========================================================================

CliffordAlgebra(n,K,Q) defines a vector space of dimension 2^n over
the field K with a given quadratic form Q.  If {e1..en} is a basis for
K^n then


{ 1,
  e(i)         1 <= i <= n,
  e(i1)*e(i2)  1 <= i1 < i2 <=n,
  ...,
  e(1)*e(2)*...*e(n) }

is a basis for the Clifford algebra. The algebra is defined by the relations

  e(i)*e(i) = Q(e(i))
  e(i)*e(j) = -e(j)*e(i),  for i ^= j

Examples of Clifford Algebras are gaussians (complex numbers),
quaternions, exterior algebras and spin algebras.

========================================================================
The Complex Numbers as a Clifford Algebra
========================================================================

This is the field over which we will work, rational functions with
integer coefficients.

  K := Fraction Polynomial Integer
   Fraction Polynomial Integer
                         Type: Domain

We use this matrix for the quadratic form.

  m := matrix [ [-1] ]
   [- 1]
```

```
                        Type: Matrix Integer
```

We get complex arithmetic by using this domain.

```
  C := CliffordAlgebra(1, K, quadraticForm m)
   CliffordAlgebra(1,Fraction Polynomial Integer,MATRIX)
                        Type: Domain
```

Here is i, the usual square root of -1.

```
  i: C := e(1)
   e
    1
              Type: CliffordAlgebra(1,Fraction Polynomial Integer,MATRIX)
```

Here are some examples of the arithmetic.

```
  x := a + b * i
   a + b e
          1
              Type: CliffordAlgebra(1,Fraction Polynomial Integer,MATRIX)

  y := c + d * i
   c + d e
          1
              Type: CliffordAlgebra(1,Fraction Polynomial Integer,MATRIX)

  x * y
   - b d + a c + (a d + b c)e
                            1
              Type: CliffordAlgebra(1,Fraction Polynomial Integer,MATRIX)
```

```
======================================================================
The Quaternion Numbers as a Clifford Algebra
======================================================================
```

This is the field over which we will work, rational functions with integer coefficients.

```
  K := Fraction Polynomial Integer
   Fraction Polynomial Integer
                     Type: Domain
```

We use this matrix for the quadratic form.

```
  m := matrix [ [-1,0],[0,-1] ]
   +- 1   0 +
   |        |
   + 0   - 1+
                     Type: Matrix Integer
```

```
The resulting domain is the quaternions.

  H  := CliffordAlgebra(2, K, quadraticForm m)
   CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)
                      Type: Domain

We use Hamilton's notation for i, j, k.

  i: H  := e(1)
   e
    1
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  j: H  := e(2)
   e
    2
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  k: H  := i * j
   e e
    1 2
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  x := a + b * i + c * j + d * k
   a + b e  + c e  + d e e
          1      2      1 2
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  y := e + f * i + g * j + h * k
   e + f e  + g e  + h e e
          1      2      1 2
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  x + y
   e + a + (f + b)e  + (g + c)e  + (h + d)e e
                  1           2           1 2
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  x * y
   - d h - c g - b f + a e + (c h - d g + a f + b e)e
                                                    1
   +
     (- b h + a g + d f + c e)e  + (a h + b g - c f + d e)e e
                               2                          1 2
              Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

  y * x
   - d h - c g - b f + a e + (- c h + d g + a f + b e)e
                                                      1
```

```
   +
     (b h + a g - d f + c e)e  + (a h - b g + c f + d e)e e
                             2                           1 2
                  Type: CliffordAlgebra(2,Fraction Polynomial Integer,MATRIX)

======================================================================
The Exterior Algebra on a Three Space
======================================================================

This is the field over which we will work, rational functions with
integer coefficients.

  K := Fraction Polynomial Integer
   Fraction Polynomial Integer
                  Type: Domain

If we chose the three by three zero quadratic form, we obtain
the exterior algebra on e(1),e(2),e(3).

  Ext := CliffordAlgebra(3, K, quadraticForm 0)
   CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)
                  Type: Domain

This is a three dimensional vector algebra.  We define i, j, k as the
unit vectors.

  i: Ext := e(1)
   e
    1
             Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)

  j: Ext := e(2)
   e
    2
             Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)

  k: Ext := e(3)
   e
    3
             Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)

Now it is possible to do arithmetic.

  x := x1*i + x2*j + x3*k
   x1 e  + x2 e  + x3 e
       1       2       3
             Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)

  y := y1*i + y2*j + y3*k
   y1 e  + y2 e  + y3 e
```

```
      1       2       3
            Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)
```

```
  x + y
   (y1 + x1)e  + (y2 + x2)e  + (y3 + x3)e
             1             2             3
            Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)
```

```
  x * y + y * x
   0
            Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)
```

On an n space, a grade p form has a dual n-p form. In particular, in three space the dual of a grade two element identifies

```
  e1*e2 -> e3, e2*e3 -> e1, e3*e1 -> e2.
```

```
  dual2 a == coefficient(a,[2,3]) * i + coefficient(a,[3,1]) * j + coefficient(a,[1,2]) * k
                     Type: Void
```

The vector cross product is then given by this.

```
  dual2(x*y)
   (x2 y3 - x3 y2)e  + (- x1 y3 + x3 y1)e  + (x1 y2 - x2 y1)e
                  1                     2                   3
          Type: CliffordAlgebra(3,Fraction Polynomial Integer,MATRIX)
```

The Dirac Spin Algebra

In this section we will work over the field of rational numbers.

```
  K := Fraction Integer
   Fraction Integer
                      Type: Domain
```

We define the quadratic form to be the Minkowski space-time metric.

```
  g := matrix [ [1,0,0,0], [0,-1,0,0], [0,0,-1,0], [0,0,0,-1] ]
   +1   0    0    0 +
   |                 |
   |0  - 1   0    0 |
   |                 |
   |0   0   - 1   0 |
   |                 |
   +0   0    0   - 1+
                      Type: Matrix Integer
```

We obtain the Dirac spin algebra used in Relativistic Quantum Field Theory.

```
  D := CliffordAlgebra(4,K, quadraticForm g)
   CliffordAlgebra(4,Fraction Integer,MATRIX)
                        Type: Domain
```

The usual notation for the basis is gamma with a superscript. For
Axiom input we will use gam(i):

```
  gam := [e(i)$D for i in 1..4]
   [e ,e ,e ,e ]
     1  2  3  4
                 Type: List CliffordAlgebra(4,Fraction Integer,MATRIX)
```

There are various contraction identities of the form

```
  g(l,t)*gam(l)*gam(m)*gam(n)*gam(r)*gam(s)*gam(t) =
      2*(gam(s)gam(m)gam(n)gam(r) + gam(r)*gam(n)*gam(m)*gam(s))
```

where a sum over l and t is implied.

Verify this identity for particular values of m,n,r,s.

```
  m := 1; n:= 2; r := 3; s := 4;
                       Type: PositiveInteger


  lhs := reduce(+, [reduce(+, [ g(l,t)*gam(l)*gam(m)*gam(n)*gam(r)*gam(s)*gam(t) for l in 1..4]) for t in 1
   - 4e e e e
       1 2 3 4
                       Type: CliffordAlgebra(4,Fraction Integer,MATRIX)

  rhs := 2*(gam s * gam m*gam n*gam r + gam r*gam n*gam m*gam s)
   - 4e e e e
       1 2 3 4
                       Type: CliffordAlgebra(4,Fraction Integer,MATRIX)
```

See Also:
o)help Complex
o)help Quaternion
o)show CliffordAlgebra
o $AXIOM/doc/src/algebra/clifford.spad

———-

4.5.12 CliffordAlgebra (CLIF)



See

⇒ "QuadraticForm" (QFORM) 18.1.1 on page 2120

Exports:

0	1	characteristic	coefficient	coerce
dimension	e	hash	latex	monomial
one?	recip	sample	subtractIfCan	zero?
?~=?	?*?	?**?	?^?	?+?
?-?	-?	?/?	?=?	

— domain CLIF CliffordAlgebra —

```
)abbrev domain CLIF CliffordAlgebra
++ Author: Stephen M. Watt
++ Date Created: August 1988
++ Date Last Updated: May 17, 1991
++ Basic Operations: wholeRadix, fractRadix, wholeRagits, fractRagits
++ Related Domains: QuadraticForm, Quaternion, Complex
++ Also See:
++ AMS Classifications:
++ Keywords: clifford algebra, grassman algebra, spin algebra
++ Examples:
++ References:
++
++ Description:
++ CliffordAlgebra(n, K, Q) defines a vector space of dimension \spad{2**n}
++ over K, given a quadratic form Q on \spad{K**n}.
++
++ If \spad{e[i]}, \spad{1<=i<=n} is a basis for \spad{K**n} then
++ 1, \spad{e[i]} (\spad{1<=i<=n}), \spad{e[i1]*e[i2]}
++ (\spad{1<=i1<i2<=n}),...,\spad{e[1]*e[2]*..*e[n]}
++ is a basis for the Clifford Algebra.
++
++ The algebra is defined by the relations\br
++ \tab{5}\spad{e[i]*e[j] = -e[j]*e[i]}  (\spad{i \~~= j}),\br
++ \tab{5}\spad{e[i]*e[i] = Q(e[i])}
```

```
++
++ Examples of Clifford Algebras are: gaussians, quaternions, exterior
++ algebras and spin algebras.

CliffordAlgebra(n, K, Q): T == Impl where
    n: PositiveInteger
    K: Field
    Q: QuadraticForm(n, K)

    PI ==> PositiveInteger
    NNI==> NonNegativeInteger

    T ==> Join(Ring, Algebra(K), VectorSpace(K)) with
        e: PI -> %
          ++ e(n) produces the appropriate unit element.
        monomial: (K, List PI) -> %
          ++ monomial(c,[i1,i2,...,iN]) produces the value given by
          ++ \spad{c*e(i1)*e(i2)*...*e(iN)}.
        coefficient:  (%, List PI) -> K
          ++ coefficient(x,[i1,i2,...,iN])  extracts the coefficient of
          ++ \spad{e(i1)*e(i2)*...*e(iN)} in x.
        recip: % -> Union(%, "failed")
          ++ recip(x) computes the multiplicative inverse of x or "failed"
          ++ if x is not invertible.

    Impl ==> add
        Qeelist :=  [Q unitVector(i::PositiveInteger) for i in 1..n]
        dim     :=  2**n

        Rep     := PrimitiveArray K

        New     ==> new(dim, 0$K)$Rep

        x, y, z: %
        c: K
        m: Integer

        characteristic() == characteristic()$K
        dimension()      == dim::CardinalNumber

        x = y ==
            for i in 0..dim-1 repeat
                if x.i ^= y.i then return false
            true

        x + y == (z := New; for i in 0..dim-1 repeat z.i := x.i + y.i; z)
        x - y == (z := New; for i in 0..dim-1 repeat z.i := x.i - y.i; z)
        - x   == (z := New; for i in 0..dim-1 repeat z.i := - x.i; z)
        m * x == (z := New; for i in 0..dim-1 repeat z.i := m*x.i; z)
        c * x == (z := New; for i in 0..dim-1 repeat z.i := c*x.i; z)
```

```
0            == New
1            == (z := New; z.0 := 1; z)
coerce(m): % == (z := New; z.0 := m::K; z)
coerce(c): % == (z := New; z.0 := c; z)

e b ==
    b::NNI > n => error "No such basis element"
    iz := 2**((b-1)::NNI)
    z := New; z.iz := 1; z

-- The ei*ej products could instead be precomputed in
-- a (2**n)**2 multiplication table.
addMonomProd(c1: K, b1: NNI, c2: K, b2: NNI, z: %): % ==
    c  := c1 * c2
    bz := b2
    for i in 0..n-1 | bit?(b1,i) repeat
        -- Apply rule  ei*ej = -ej*ei for i^=j
        k := 0
        for j in i+1..n-1 | bit?(b1, j) repeat k := k+1
        for j in 0..i-1   | bit?(bz, j) repeat k := k+1
        if odd? k then c := -c
        -- Apply rule  ei**2 = Q(ei)
        if bit?(bz,i) then
            c := c * Qeelist.(i+1)
            bz:= (bz - 2**i)::NNI
        else
            bz:= bz + 2**i
    z.bz := z.bz + c
    z

x * y ==
    z := New
    for ix in 0..dim-1 repeat
        if x.ix ^= 0 then for iy in 0..dim-1 repeat
            if y.iy ^= 0 then addMonomProd(x.ix,ix,y.iy,iy,z)
    z

canonMonom(c: K, lb: List PI): Record(coef: K, basel: NNI) ==
    -- 0. Check input
    for b in lb repeat b > n => error "No such basis element"

    -- 1. Apply identity ei*ej = -ej*ei, i^=j.
    -- The Rep assumes n is small so bubble sort is ok.
    -- Using bubble sort keeps the exchange info obvious.
    wasordered   := false
    exchanges := 0
    while not wasordered repeat
        wasordered := true
        for i in 1..#lb-1 repeat
```

```
            if lb.i > lb.(i+1) then
                t := lb.i; lb.i := lb.(i+1); lb.(i+1) := t
                exchanges := exchanges + 1
                wasordered := false
    if odd? exchanges then c := -c

    -- 2. Prepare the basis element
    -- Apply identity ei*ei = Q(ei).
    bz := 0
    for b in lb repeat
        bn := (b-1)::NNI
        if bit?(bz, bn) then
            c := c * Qeelist bn
            bz:= ( bz - 2**bn )::NNI
        else
            bz:= bz + 2**bn
    [c, bz::NNI]

monomial(c, lb) ==
    r := canonMonom(c, lb)
    z := New
    z r.basel := r.coef
    z
coefficient(z, lb) ==
    r := canonMonom(1, lb)
    r.coef = 0 => error "Cannot take coef of 0"
    z r.basel/r.coef

Ex ==> OutputForm

coerceMonom(c: K, b: NNI): Ex ==
    b = 0 => c::Ex
    ml := [sub("e"::Ex, i::Ex) for i in 1..n | bit?(b,i-1)]
    be := reduce("*", ml)
    c = 1 => be
    c::Ex * be

coerce(x): Ex ==
    tl := [coerceMonom(x.i,i) for i in 0..dim-1 | x.i^=0]
    null tl => "0"::Ex
    reduce("+", tl)

localPowerSets(j:NNI): List(List(PI)) ==
  l: List List PI := list []
  j = 0 => l
  Sm := localPowerSets((j-1)::NNI)
  Sn: List List PI := []
  for x in Sm repeat Sn := cons(cons(j pretend PI, x),Sn)
  append(Sn, Sm)
```

```
        powerSets(j:NNI):List List PI == map(reverse, localPowerSets j)

        Pn:List List PI := powerSets(n)

        recip(x: %): Union(%, "failed") ==
          one:% := 1
          -- tmp:c := x*yC - 1$C
          rhsEqs : List K := []
          lhsEqs: List List K := []
          lhsEqi: List K
          for pi in Pn repeat
            rhsEqs := cons(coefficient(one, pi), rhsEqs)

            lhsEqi := []
            for pj in Pn repeat
                lhsEqi := cons(coefficient(x*monomial(1,pj),pi),lhsEqi)
            lhsEqs := cons(reverse(lhsEqi),lhsEqs)
          ans := particularSolution(matrix(lhsEqs),vector(rhsEqs)_
             )$LinearSystemMatrixPackage(K, Vector K, Vector K, Matrix K)
          ans case "failed" => "failed"
          ansP := parts(ans)
          ansC:% := 0
          for pj in Pn repeat
            cj:= first ansP
            ansP := rest ansP
            ansC := ansC + cj*monomial(1,pj)
          ansC
```

———-

— CLIF.dotabb —

```
"CLIF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CLIF"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"CLIF" -> "IVECTOR"
```

———-

4.6 domain COLOR Color

— Color.input —

```
)set break resume
)sys rm -f Color.output
```

```
)spool Color.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Color
--R Color  is a domain constructor
--R Abbreviation for Color is COLOR
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for COLOR
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (DoubleFloat,%) -> %           ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                     ?=? : (%,%) -> Boolean
--R blue : () -> %                       coerce : % -> OutputForm
--R color : Integer -> %                 green : () -> %
--R hash : % -> SingleInteger            hue : % -> Integer
--R latex : % -> String                  red : () -> %
--R yellow : () -> %                     ?~=? : (%,%) -> Boolean
--R numberOfHues : () -> PositiveInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— Color.help —

```
=====================================================================
Color examples
=====================================================================

See Also:
o )show Color
```

———-

4.6.1 Color (COLOR)



See

⇒ "Palette" (PALETTE) 17.4.1 on page 1862

Exports:

blue	coerce	color	green	hash
hue	latex	numberOfHues	red	yellow
?~=?	?*?	?+?	?=?	

— domain COLOR Color —

```
)abbrev domain COLOR Color
++ Author: Jim Wen
++ Date Created: 10 May 1989
++ Date Last Updated: 19 Mar 1991 by Jon Steinbach
++ Basic Operations: red, yellow, green, blue, hue, numberOfHues, color, +, *, =
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ Color() specifies a domain of 27 colors provided in the
++ \Language{} system (the colors mix additively).

Color(): Exports == Implementation where
  I      ==> Integer
  PI     ==> PositiveInteger
  SF     ==> DoubleFloat

  Exports ==> AbelianSemiGroup with
    "*"    : (PI, %) -> %
      ++ s * c, returns the color c, whose weighted shade has been scaled by s.
    "*"    : (SF, %) -> %
      ++ s * c, returns the color c, whose weighted shade has been scaled by s.
    "+"    : (%, %) -> %
      ++ c1 + c2 additively mixes the two colors c1 and c2.
```

```
  red    : ()      -> %
    ++ red() returns the position of the red hue from total hues.
  yellow : ()      -> %
    ++ yellow() returns the position of the yellow hue from total hues.
  green  : ()      -> %
    ++ green() returns the position of the green hue from total hues.
  blue   : ()      -> %
    ++ blue() returns the position of the blue hue from total hues.
  hue    : %       -> I
    ++ hue(c) returns the hue index of the indicated color c.
  numberOfHues : ()    -> PI
    ++ numberOfHues() returns the number of total hues, set in totalHues.
  color  : Integer -> %
    ++ color(i) returns a color of the indicated hue i.

Implementation ==> add
  totalHues   ==> 27  --see  (header.h file) for the current number

  Rep := Record(hue:I, weight:SF)


  f:SF * c:% ==
    -- s * c returns the color c, whose weighted shade has been scaled by s
    zero? f => c
    -- 0 is the identitly function...or maybe an error is better?
    [c.hue, f * c.weight]

  x + y ==
   x.hue = y.hue => [x.hue, x.weight + y.weight]
   if y.weight > x.weight then  -- let x be color with bigger weight
     c := x
     x := y
     y := c
   diff := x.hue - y.hue
   if (xHueSmaller:= (diff < 0)) then diff := -diff
   if (moreThanHalf:=(diff > totalHues quo 2)) then diff := totalHues-diff
   offset : I := wholePart(round (diff::SF/(2::SF)**(x.weight/y.weight)) )
   if (xHueSmaller and ^moreThanHalf) or (^xHueSmaller and moreThanHalf) then
     ans := x.hue + offset
   else
     ans := x.hue - offset
   if (ans < 0) then ans := totalHues + ans
   else if (ans > totalHues) then ans := ans - totalHues
   [ans,1]

  x = y     == (x.hue = y.hue) and (x.weight = y.weight)
  red()     == [1,1]
  yellow()  == [11::I,1]
  green()   == [14::I,1]
  blue()    == [22::I,1]
```

```
    sample()  == red()
    hue c     == c.hue
    i:PositiveInteger * c:% == i::SF * c
    numberOfHues() == totalHues

    color i ==
      if (i<0) or (i>totalHues) then
       error concat("Color should be in the range 1..",totalHues::String)
      [i::I, 1]

    coerce(c:%):OutputForm ==
      hconcat ["Hue: "::OutputForm, (c.hue)::OutputForm,
               "  Weight: "::OutputForm, (c.weight)::OutputForm]
```

———-

— COLOR.dotabb —

```
"COLOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=COLOR"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"COLOR" -> "BASTYPE"
"COLOR" -> "KOERCE"
```

———-

4.7 domain COMM Commutator

— Commutator.input —

```
)set break resume
)sys rm -f Commutator.output
)spool Commutator.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Commutator
--R Commutator  is a domain constructor
--R Abbreviation for Commutator is COMM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for COMM
--R
```

```
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R mkcomm : (%,%) -> %                   mkcomm : Integer -> %
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Commutator.help** —

```
========================================================================
Commutator examples
========================================================================

See Also:
o )show Commutator
```

———-

4.7.1 Commutator (COMM)



See

⇒ “OrdSetInts” (OSI) 16.20.1 on page 1830
⇒ “FreeNilpotentLie” (FNLA) 7.33.1 on page 997

Exports:
coerce hash latex mkcomm ?=? ?~=?

— **domain COMM Commutator** —

```
)abbrev domain COMM Commutator
++ Author : Larry Lambe
++ Date created: 30 June 1988.
++ Updated     : 10 March 1991
++ Description:
++ A type for basic commutators

Commutator: Export == Implement where
   I   ==> Integer
   OSI ==> OrdSetInts
   O   ==> OutputForm

   Export == SetCategory with
     mkcomm : I -> %
       ++ mkcomm(i) is not documented
     mkcomm : (%,%) -> %
       ++ mkcomm(i,j) is not documented

   Implement == add
     P   :=  Record(left:%,right:%)
     Rep := Union(OSI,P)
     x,y: %
     i  : I

     x = y ==
        (x case OSI) and (y case OSI) => x::OSI = y::OSI
        (x case P) and (y case P) =>
           xx:P := x::P
           yy:P := y::P
           (xx.right = yy.right) and (xx.left = yy.left)
        false

     mkcomm(i) == i::OSI
     mkcomm(x,y) == construct(x,y)$P

     coerce(x: %): O ==
        x case OSI => x::OSI::O
        xx := x::P
        bracket([xx.left::O,xx.right::O])$O
```

— **COMM.dotabb** —

```
"COMM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=COMM"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"COMM" -> "BASTYPE"
```

```
"COMM" -> "KOERCE"
```

———-

4.8 domain COMPLEX Complex

— Complex.input —

```
)set break resume
)sys rm -f Complex.output
)spool Complex.output
)set message test on
)set message auto off
)clear all
--S 1 of 16
a := complex(4/3,5/2)
--R
--R
--R        4   5
--R   (1)  - + - %i
--R        3   2
--R                                        Type: Complex(Fraction(Integer))
--E 1

--S 2 of 16
b := complex(4/3,-5/2)
--R
--R
--R        4   5
--R   (2)  - - - %i
--R        3   2
--R                                        Type: Complex(Fraction(Integer))
--E 2

--S 3 of 16
a + b
--R
--R
--R        8
--R   (3)  -
--R        3
--R                                        Type: Complex(Fraction(Integer))
--E 3

--S 4 of 16
a - b
```

```
--R
--R
--R   (4)  5%i
--R                                              Type: Complex(Fraction(Integer))
--E 4

--S 5 of 16
a * b
--R
--R
--R        289
--R   (5)  ---
--R         36
--R                                              Type: Complex(Fraction(Integer))
--E 5

--S 6 of 16
a / b
--R
--R
--R          161   240
--R   (6)  - --- + --- %i
--R          289   289
--R                                              Type: Complex(Fraction(Integer))
--E 6

--S 7 of 16
% :: Fraction Complex Integer
--R
--R
--R        - 15 + 8%i
--R   (7)  ----------
--R         15 + 8%i
--R                                              Type: Fraction(Complex(Integer))
--E 7

--S 8 of 16
3.4 + 6.7 * %i
--R
--R
--R   (8)  3.4 + 6.7 %i
--R                                                 Type: Complex(Float)
--E 8

--S 9 of 16
conjugate a
--R
--R
--R        4   5
--R   (9)  - - - %i
```

```
--R        3   2
--R                                          Type: Complex(Fraction(Integer))
--E 9

--S 10 of 16
norm a
--R
--R
--R         289
--R   (10)  ---
--R          36
--R                                                  Type: Fraction(Integer)
--E 10

--S 11 of 16
real a
--R
--R
--R         4
--R   (11)  -
--R         3
--R                                                  Type: Fraction(Integer)
--E 11

--S 12 of 16
imag a
--R
--R
--R         5
--R   (12)  -
--R         2
--R                                                  Type: Fraction(Integer)
--E 12

--S 13 of 16
gcd(13 - 13*%i,31 + 27*%i)
--R
--R
--R   (13)  5 + %i
--R                                                   Type: Complex(Integer)
--E 13

--S 14 of 16
lcm(13 - 13*%i,31 + 27*%i)
--R
--R
--R   (14)  143 - 39%i
--R                                                   Type: Complex(Integer)
--E 14
```

```
--S 15 of 16
factor(13 - 13*%i)
--R
--R
--R   (15)  - (1 + %i)(2 + 3%i)(3 + 2%i)
--R                                                Type: Factored(Complex(Integer))
--E 15

--S 16 of 16
factor complex(2,0)
--R
--R
--R                        2
--R   (16)  - %i (1 + %i)
--R                                                Type: Factored(Complex(Integer))
--E 16
)spool
)lisp (bye)
```

———-

— Complex.help —

```
========================================================================
Complex examples
========================================================================

The Complex constructor implements complex objects over a commutative
ring R.  Typically, the ring R is Integer, Fraction Integer, Float or
DoubleFloat.  R can also be a symbolic type, like Polynomial Integer.

Complex objects are created by the complex operation.

  a := complex(4/3,5/2)
   4   5
   - + - %i
   3   2
                         Type: Complex Fraction Integer

  b := complex(4/3,-5/2)
   4   5
   - - - %i
   3   2
                         Type: Complex Fraction Integer

The standard arithmetic operations are available.

  a + b
   8
```

```
   -
   3
                        Type: Complex Fraction Integer

  a - b
   5%i
                        Type: Complex Fraction Integer

  a * b
   289
   ---
    36
                        Type: Complex Fraction Integer
```

If R is a field, you can also divide the complex objects.

```
  a / b
     161   240
   - --- + --- %i
     289   289
                        Type: Complex Fraction Integer
```

We can view the last object as a fraction of complex integers.

```
  % :: Fraction Complex Integer
   - 15 + 8%i
   ----------
     15 + 8%i
                         Type: Fraction Complex Integer
```

The predefined macro %i is defined to be complex(0,1).

```
  3.4 + 6.7 * %i
   3.4 + 6.7 %i
                       Type: Complex Float
```

You can also compute the conjugate and norm of a complex number.

```
  conjugate a
   4   5
   - - - %i
   3   2
                       Type: Complex Fraction Integer

  norm a
   289
   ---
    36
                       Type: Fraction Integer
```

```
The real and imag operations are provided to extract the real and
imaginary parts, respectively.

  real a
   4
   -
   3
                        Type: Fraction Integer

  imag a
   5
   -
   2
                        Type: Fraction Integer

The domain Complex Integer is also called the Gaussian integers.  If R
is the integers (or, more generally, a EuclideanDomain), you can compute
greatest common divisors.

  gcd(13 - 13*%i,31 + 27*%i)
   5 + %i
                        Type: Complex Integer

You can also compute least common multiples.

  lcm(13 - 13*%i,31 + 27*%i)
   143 - 39%i
                        Type: Complex Integer

You can factor Gaussian integers.


  factor(13 - 13*%i)
   - (1 + %i)(2 + 3%i)(3 + 2%i)
                        Type: Factored Complex Integer

  factor complex(2,0)
                  2
   - %i (1 + %i)
                        Type: Factored Complex Integer

See Also
o )show Complex
```

———-

4.8.1 Complex (COMPLEX)



Exports:

0	1	abs
acos	acosh	acot
acoth	acsc	acsch
argument	asec	asech
asin	asinh	associates?
atan	atanh	basis
characteristic	characteristicPolynomial	charthRoot
coerce	complex	conditionP
conjugate	convert	coordinates
cos	cosh	cot
coth	createPrimitiveElement	csc
csch	D	definingPolynomial
derivationCoordinates	differentiate	discreteLog
discriminant	divide	euclideanSize
eval	exp	expressIdealMember
exquo	extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial	factorsOfCyclicGroupSize
gcd	gcdPolynomial	generator
hash	imag	imaginary
index	init	inv
latex	lcm	lift
log	lookup	map
max	min	minimalPolynomial
multiEuclidean	nextItem	norm
nthRoot	OMwrite	one?
order	patternMatch	pi
polarCoordinates	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	rank	rational
rational?	rationalIfCan	real
recip	reduce	reducedSystem
regularRepresentation	representationType	represents
retract	retractIfCan	sample
sec	sech	sin
sinh	size	sizeLess?
solveLinearPolynomialEquation	sqrt	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
tableForDiscreteLogarithm	tan	tanh
trace	traceMatrix	unit?
unitCanonical	unitNormal	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?~=?	?/?
?<?	?<=?	?>?
?>=?	?.?	?quo?
?rem?		

— domain COMPLEX Complex —

```
)abbrev domain COMPLEX Complex
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \spadtype{Complex(R)} creates the domain of elements of the form
++ \spad{a + b * i} where \spad{a} and b come from the ring R,
++ and i is a new element such that \spad{i**2 = -1}.

Complex(R:CommutativeRing): ComplexCategory(R) with
     if R has OpenMath then OpenMath
   == add
       Rep := Record(real:R, imag:R)

       if R has OpenMath then
         writeOMComplex(dev: OpenMathDevice, x: %): Void ==
          OMputApp(dev)
          OMputSymbol(dev, "complex1", "complex__cartesian")
          OMwrite(dev, real x)
          OMwrite(dev, imag x)
          OMputEndApp(dev)

         OMwrite(x: %): String ==
          s: String := ""
          sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
          dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
          OMputObject(dev)
          writeOMComplex(dev, x)
          OMputEndObject(dev)
          OMclose(dev)
          s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
          s

         OMwrite(x: %, wholeObj: Boolean): String ==
          s: String := ""
          sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
          dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
          if wholeObj then
            OMputObject(dev)
          writeOMComplex(dev, x)
          if wholeObj then
```

```
            OMputEndObject(dev)
           OMclose(dev)
           s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
           s

          OMwrite(dev: OpenMathDevice, x: %): Void ==
           OMputObject(dev)
           writeOMComplex(dev, x)
           OMputEndObject(dev)

          OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
           if wholeObj then
             OMputObject(dev)
           writeOMComplex(dev, x)
           if wholeObj then
             OMputEndObject(dev)

       0                == [0, 0]
       1                == [1, 0]
       zero? x          == zero?(x.real) and zero?(x.imag)
--       one? x           == one?(x.real) and zero?(x.imag)
       one? x           == ((x.real) = 1) and zero?(x.imag)
       coerce(r:R):%    == [r, 0]
       complex(r, i)   == [r, i]
       real x           == x.real
       imag x           == x.imag
       x + y            == [x.real + y.real, x.imag + y.imag]
                           -- by re-defining this here, we save 5 fn calls
       x:% * y:% ==
         [x.real * y.real - x.imag * y.imag,
          x.imag * y.real + y.imag * x.real] -- here we save nine!


       if R has IntegralDomain then
         _exquo(x:%, y:%) == -- to correct bad defaulting problem
           zero? y.imag => x exquo y.real
           x * conjugate(y) exquo norm(y)
```

———-

— COMPLEX.dotabb —

```
"COMPLEX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=COMPLEX"]
"COMPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=COMPCAT"]
"COMPLEX" -> "COMPCAT"
```

———-

4.9 domain CDFMAT ComplexDoubleFloatMatrix

— ComplexDoubleFloatMatrix.input —

```
)set break resume
)sys rm -f ComplexDoubleFloatMatrix.output
)spool ComplexDoubleFloatMatrix.output
)set message test on
)set message auto off
)clear all

--S 1 of 6
)show ComplexDoubleFloatMatrix
--R
--R ComplexDoubleFloatMatrix  is a domain constructor
--R Abbreviation for ComplexDoubleFloatMatrix is CDFMAT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for CDFMAT
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,%) -> %                ?*? : (%,%) -> %
--R ?+? : (%,%) -> %                      -? : % -> %
--R ?-? : (%,%) -> %                      antisymmetric? : % -> Boolean
--R copy : % -> %                         diagonal? : % -> Boolean
--R diagonalMatrix : List(%) -> %         empty : () -> %
--R empty? : % -> Boolean                 eq? : (%,%) -> Boolean
--R horizConcat : (%,%) -> %              maxColIndex : % -> Integer
--R maxRowIndex : % -> Integer            minColIndex : % -> Integer
--R minRowIndex : % -> Integer            ncols : % -> NonNegativeInteger
--R nrows : % -> NonNegativeInteger       qnew : (Integer,Integer) -> %
--R sample : () -> %                      square? : % -> Boolean
--R squareTop : % -> %                    symmetric? : % -> Boolean
--R transpose : % -> %                    vertConcat : (%,%) -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (ComplexDoubleFloatVector,%) -> ComplexDoubleFloatVector
--R ?*? : (%,ComplexDoubleFloatVector) -> ComplexDoubleFloatVector
--R ?*? : (%,Complex(DoubleFloat)) -> %
--R ?*? : (Complex(DoubleFloat),%) -> %
--R ?**? : (%,Integer) -> % if Complex(DoubleFloat) has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,Complex(DoubleFloat)) -> % if Complex(DoubleFloat) has FIELD
--R ?=? : (%,%) -> Boolean if Complex(DoubleFloat) has SETCAT
--R any? : ((Complex(DoubleFloat) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : ComplexDoubleFloatVector -> %
--R coerce : % -> OutputForm if Complex(DoubleFloat) has SETCAT
--R column : (%,Integer) -> ComplexDoubleFloatVector
--R columnSpace : % -> List(ComplexDoubleFloatVector) if Complex(DoubleFloat) has EUCDOM
--R count : (Complex(DoubleFloat),%) -> NonNegativeInteger if $ has finiteAggregate and Complex(DoubleFloat)
```

```
--R count : ((Complex(DoubleFloat) -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R determinant : % -> Complex(DoubleFloat) if Complex(DoubleFloat) has commutative(*)
--R diagonalMatrix : List(Complex(DoubleFloat)) -> %
--R elt : (%,List(Integer),List(Integer)) -> %
--R elt : (%,Integer,Integer,Complex(DoubleFloat)) -> Complex(DoubleFloat)
--R elt : (%,Integer,Integer) -> Complex(DoubleFloat)
--R eval : (%,List(Complex(DoubleFloat)),List(Complex(DoubleFloat))) -> % if Complex(DoubleFloat
--R eval : (%,Complex(DoubleFloat),Complex(DoubleFloat)) -> % if Complex(DoubleFloat) has EVALAB
--R eval : (%,Equation(Complex(DoubleFloat))) -> % if Complex(DoubleFloat) has EVALAB(COMPLEX(DF
--R eval : (%,List(Equation(Complex(DoubleFloat)))) -> % if Complex(DoubleFloat) has EVALAB(COMP
--R every? : ((Complex(DoubleFloat) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R exquo : (%,Complex(DoubleFloat)) -> Union(%,"failed") if Complex(DoubleFloat) has INTDOM
--R fill! : (%,Complex(DoubleFloat)) -> %
--R hash : % -> SingleInteger if Complex(DoubleFloat) has SETCAT
--R inverse : % -> Union(%,"failed") if Complex(DoubleFloat) has FIELD
--R latex : % -> String if Complex(DoubleFloat) has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R listOfLists : % -> List(List(Complex(DoubleFloat)))
--R map : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Complex(DoubleFloat)),%,%,Complex(Dou
--R map : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Complex(DoubleFloat)),%,%) -> %
--R map : ((Complex(DoubleFloat) -> Complex(DoubleFloat)),%) -> %
--R map! : ((Complex(DoubleFloat) -> Complex(DoubleFloat)),%) -> %
--R matrix : List(List(Complex(DoubleFloat))) -> %
--R member? : (Complex(DoubleFloat),%) -> Boolean if $ has finiteAggregate and Complex(DoubleFlo
--R members : % -> List(Complex(DoubleFloat)) if $ has finiteAggregate
--R minordet : % -> Complex(DoubleFloat) if Complex(DoubleFloat) has commutative(*)
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,NonNegativeInteger,Complex(DoubleFloat)) -> %
--R nullSpace : % -> List(ComplexDoubleFloatVector) if Complex(DoubleFloat) has INTDOM
--R nullity : % -> NonNegativeInteger if Complex(DoubleFloat) has INTDOM
--R parts : % -> List(Complex(DoubleFloat))
--R pfaffian : % -> Complex(DoubleFloat) if Complex(DoubleFloat) has COMRING
--R qelt : (%,Integer,Integer) -> Complex(DoubleFloat)
--R qsetelt! : (%,Integer,Integer,Complex(DoubleFloat)) -> Complex(DoubleFloat)
--R rank : % -> NonNegativeInteger if Complex(DoubleFloat) has INTDOM
--R row : (%,Integer) -> ComplexDoubleFloatVector
--R rowEchelon : % -> % if Complex(DoubleFloat) has EUCDOM
--R scalarMatrix : (NonNegativeInteger,Complex(DoubleFloat)) -> %
--R setColumn! : (%,Integer,ComplexDoubleFloatVector) -> %
--R setRow! : (%,Integer,ComplexDoubleFloatVector) -> %
--R setelt : (%,List(Integer),List(Integer),%) -> %
--R setelt : (%,Integer,Integer,Complex(DoubleFloat)) -> Complex(DoubleFloat)
--R setsubMatrix! : (%,Integer,Integer,%) -> %
--R size? : (%,NonNegativeInteger) -> Boolean
--R subMatrix : (%,Integer,Integer,Integer,Integer) -> %
--R swapColumns! : (%,Integer,Integer) -> %
--R swapRows! : (%,Integer,Integer) -> %
--R transpose : ComplexDoubleFloatVector -> %
--R zero : (NonNegativeInteger,NonNegativeInteger) -> %
--R ?~=? : (%,%) -> Boolean if Complex(DoubleFloat) has SETCAT
```

```
--R
--E 1

--S 2 of 6
a:CDFMAT:=qnew(2,3)
--R
--R        +0.  0.  0.+
--R   (1)  |          |
--R        +0.  0.  0.+
--R                                              Type: ComplexDoubleFloatMatrix
--E 2

--S 3 of 6
qsetelt!(a,1,1,1.0+2*%i)
--R
--R   (2)  1. + 2. %i
--R                                                  Type: Complex(DoubleFloat)
--E 3

--S 4 of 6
a
--R
--R        +0.       0.       0.+
--R   (3)  |                    |
--R        +0.  1. + 2. %i  0.+
--R                                              Type: ComplexDoubleFloatMatrix
--E 4

--S 5 of 6
qsetelt!(a,0,0,2.0+4*%i)
--R
--R   (4)  2. + 4. %i
--R                                                  Type: Complex(DoubleFloat)
--E 5

--S 6 of 6
a
--R
--R        +2. + 4. %i      0.       0.+
--R   (5)  |                           |
--R        +    0.      1. + 2. %i  0.+
--R                                              Type: ComplexDoubleFloatMatrix
--E 6

)spool
)lisp (bye)
```

— ComplexDoubleFloatMatrix.help —

```
====================================================================
ComplexDoubleFloatMatrix examples
====================================================================
This domain creates a lisp simple array of machine doublefloats.
It provides one new function called qnew which takes an integer
that gives the array length.

NOTE: Unlike normal Axiom arrays the ComplexDoubleFloatMatrix arrays
are 0-based so the first element is 0. Axiom arrays normally
start at 1.

a:CDFMAT:=qnew(2,3)
        +0.  0.  0.+
        |          |
        +0.  0.  0.+

qsetelt!(a,1,1,1.0+2*%i)
        1. + 2. %i


a
        +0.      0.      0.+
        |                  |
        +0.  1. + 2. %i  0.+

qsetelt!(a,0,0,2.0+4*%i)
        2. + 4. %i

a
        +2. + 4. %i      0.      0.+
        |                          |
        +    0.      1. + 2. %i  0.+

See Also:
o )help Float
o )help DoubleFloat
o )show ComplexDoubleFloatMatrix
```

4.9.1 ComplexDoubleFloatMatrix (CDFMAT)



Exports:

#?	-?	?**?	?*?
?+?	?-?	?/?	?=?
?~=?	antisymmetric?	any?	coerce
column	columnSpace	copy	count
determinant	diagonal?	diagonalMatrix	elt
empty	empty?	eq?	eval
every?	exquo	fill!	hash
horizConcat	inverse	latex	less?
listOfLists	map	map!	matrix
maxColIndex	maxRowIndex	member?	members
minColIndex	minRowIndex	minordet	more?
ncols	new	nrows	nullSpace
nullity	parts	pfaffian	qelt
qnew	qsetelt!	rank	row
rowEchelon	sample	scalarMatrix	setColumn!
setRow!	setelt	setsubMatrix!	size?
square?	squareTop	subMatrix	swapColumns!
swapRows!	symmetric?	transpose	vertConcat
zero			

— domain CDFMAT ComplexDoubleFloatMatrix —

```
)abbrev domain CDFMAT ComplexDoubleFloatMatrix
++ Author: Waldek Hebisch
++ Description: This is a low-level domain which implements matrices
++ (two dimensional arrays) of complex double precision floating point
++ numbers.  Indexing is 0 based, there is no bound checking (unless
++ provided by lower level).

ComplexDoubleFloatMatrix : MatrixCategory(Complex DoubleFloat,
                         ComplexDoubleFloatVector,
                         ComplexDoubleFloatVector) with
    qnew : (Integer, Integer) -> %
```

```
      ++ qnew(n, m) creates a new uninitialized n by m matrix.
      ++
      ++X t1:CDFMAT:=qnew(3,4)

  == add

    NNI ==> Integer
    Qelt2 ==> CDAREF2$Lisp
    Qsetelt2 ==> CDSETAREF2$Lisp
    Qnrows ==> CDANROWS$Lisp
    Qncols ==> CDANCOLS$Lisp
    Qnew ==> MAKE_-CDOUBLE_-MATRIX$Lisp

    minRowIndex x == 0
    minColIndex x == 0
    nrows x == Qnrows(x)
    ncols x == Qncols(x)
    maxRowIndex x == Qnrows(x) - 1
    maxColIndex x == Qncols(x) - 1

    qelt(m, i, j) == Qelt2(m, i, j)
    qsetelt_!(m, i, j, r) == Qsetelt2(m, i, j, r)

    empty() == Qnew(0$Integer, 0$Integer)
    qnew(rows, cols) == Qnew(rows, cols)
    new(rows, cols, a) ==
        res := Qnew(rows, cols)
        for i in 0..(rows - 1) repeat
            for j in 0..(cols - 1) repeat
                Qsetelt2(res, i, j, a)
        res
```

— CDFMAT.dotabb —

```
"CDFMAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CDFMAT",
          shape=ellipse]
"COMPCAT" [color=lightblue,href="bookvol10.2.pdf#nameddest=COMPCAT"];
"CDFMAT" -> "COMPCAT"
```

4.10 domain CDFVEC ComplexDoubleFloatVector

— ComplexDoubleFloatVector.input —

```
)set break resume
)sys rm -f ComplexDoubleFloatVector.output
)spool ComplexDoubleFloatVector.output
)set message test on
)set message auto off
)clear all

--S 1 of 6
)show ComplexDoubleFloatVector
--R
--R ComplexDoubleFloatVector  is a domain constructor
--R Abbreviation for ComplexDoubleFloatVector is CDFVEC
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for CDFVEC
--R
--R------------------------------ Operations --------------------------------
--R concat : List(%) -> %                 concat : (%,%) -> %
--R copy : % -> %                         delete : (%,Integer) -> %
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)          insert : (%,%,Integer) -> %
--R qnew : Integer -> %                   reverse : % -> %
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (%,Complex(DoubleFloat)) -> % if Complex(DoubleFloat) has MONOID
--R ?*? : (Complex(DoubleFloat),%) -> % if Complex(DoubleFloat) has MONOID
--R ?*? : (Integer,%) -> % if Complex(DoubleFloat) has ABELGRP
--R ?+? : (%,%) -> % if Complex(DoubleFloat) has ABELSG
--R ?-? : (%,%) -> % if Complex(DoubleFloat) has ABELGRP
--R -? : % -> % if Complex(DoubleFloat) has ABELGRP
--R ?<? : (%,%) -> Boolean if Complex(DoubleFloat) has ORDSET
--R ?<=? : (%,%) -> Boolean if Complex(DoubleFloat) has ORDSET
--R ?=? : (%,%) -> Boolean if Complex(DoubleFloat) has SETCAT
--R ?>? : (%,%) -> Boolean if Complex(DoubleFloat) has ORDSET
--R ?>=? : (%,%) -> Boolean if Complex(DoubleFloat) has ORDSET
--R any? : ((Complex(DoubleFloat) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if Complex(DoubleFloat) has SETCAT
--R concat : (Complex(DoubleFloat),%) -> %
--R concat : (%,Complex(DoubleFloat)) -> %
--R construct : List(Complex(DoubleFloat)) -> %
--R convert : % -> InputForm if Complex(DoubleFloat) has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (Complex(DoubleFloat),%) -> NonNegativeInteger if $ has finiteAggregate and Complex(DoubleFloat)
--R count : ((Complex(DoubleFloat) -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
```

```
--R cross : (%,%) -> % if Complex(DoubleFloat) has RING
--R delete : (%,UniversalSegment(Integer)) -> %
--R dot : (%,%) -> Complex(DoubleFloat) if Complex(DoubleFloat) has RING
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,Integer) -> Complex(DoubleFloat)
--R elt : (%,Integer,Complex(DoubleFloat)) -> Complex(DoubleFloat)
--R entries : % -> List(Complex(DoubleFloat))
--R entry? : (Complex(DoubleFloat),%) -> Boolean if $ has finiteAggregate and Complex(DoubleFloa
--R eval : (%,List(Complex(DoubleFloat)),List(Complex(DoubleFloat))) -> % if Complex(DoubleFloat
--R eval : (%,Complex(DoubleFloat),Complex(DoubleFloat)) -> % if Complex(DoubleFloat) has EVALAB
--R eval : (%,Equation(Complex(DoubleFloat))) -> % if Complex(DoubleFloat) has EVALAB(COMPLEX(DF
--R eval : (%,List(Equation(Complex(DoubleFloat)))) -> % if Complex(DoubleFloat) has EVALAB(COMP
--R every? : ((Complex(DoubleFloat) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,Complex(DoubleFloat)) -> % if $ has shallowlyMutable
--R find : ((Complex(DoubleFloat) -> Boolean),%) -> Union(Complex(DoubleFloat),"failed")
--R first : % -> Complex(DoubleFloat) if Integer has ORDSET
--R hash : % -> SingleInteger if Complex(DoubleFloat) has SETCAT
--R insert : (Complex(DoubleFloat),%,Integer) -> %
--R latex : % -> String if Complex(DoubleFloat) has SETCAT
--R length : % -> Complex(DoubleFloat) if Complex(DoubleFloat) has RADCAT and Complex(DoubleFloa
--R less? : (%,NonNegativeInteger) -> Boolean
--R magnitude : % -> Complex(DoubleFloat) if Complex(DoubleFloat) has RADCAT and Complex(DoubleF
--R map : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Complex(DoubleFloat)),%,%) -> %
--R map : ((Complex(DoubleFloat) -> Complex(DoubleFloat)),%) -> %
--R map! : ((Complex(DoubleFloat) -> Complex(DoubleFloat)),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if Complex(DoubleFloat) has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (Complex(DoubleFloat),%) -> Boolean if $ has finiteAggregate and Complex(DoubleFlo
--R members : % -> List(Complex(DoubleFloat)) if $ has finiteAggregate
--R merge : (%,%) -> % if Complex(DoubleFloat) has ORDSET
--R merge : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Boolean),%,%) -> %
--R min : (%,%) -> % if Complex(DoubleFloat) has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,Complex(DoubleFloat)) -> %
--R outerProduct : (%,%) -> Matrix(Complex(DoubleFloat)) if Complex(DoubleFloat) has RING
--R parts : % -> List(Complex(DoubleFloat)) if $ has finiteAggregate
--R position : (Complex(DoubleFloat),%,Integer) -> Integer if Complex(DoubleFloat) has SETCAT
--R position : (Complex(DoubleFloat),%) -> Integer if Complex(DoubleFloat) has SETCAT
--R position : ((Complex(DoubleFloat) -> Boolean),%) -> Integer
--R qelt : (%,Integer) -> Complex(DoubleFloat)
--R qsetelt! : (%,Integer,Complex(DoubleFloat)) -> Complex(DoubleFloat) if $ has shallowlyMutabl
--R reduce : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Complex(DoubleFloat)),%) -> Comple
--R reduce : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Complex(DoubleFloat)),%,Complex(Do
--R reduce : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Complex(DoubleFloat)),%,Complex(Do
--R remove : ((Complex(DoubleFloat) -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Complex(DoubleFloat),%) -> % if $ has finiteAggregate and Complex(DoubleFloat) has
--R removeDuplicates : % -> % if $ has finiteAggregate and Complex(DoubleFloat) has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((Complex(DoubleFloat) -> Boolean),%) -> % if $ has finiteAggregate
```

```
--R setelt : (%,UniversalSegment(Integer),Complex(DoubleFloat)) -> Complex(DoubleFloat) if $ has shallowlyMu
--R setelt : (%,Integer,Complex(DoubleFloat)) -> Complex(DoubleFloat) if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if Complex(DoubleFloat) has ORDSET
--R sort : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and Complex(DoubleFloat) has ORDSET
--R sort! : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if Complex(DoubleFloat) has ORDSET
--R sorted? : (((Complex(DoubleFloat),Complex(DoubleFloat)) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R vector : List(Complex(DoubleFloat)) -> %
--R zero : NonNegativeInteger -> % if Complex(DoubleFloat) has ABELMON
--R ?~=? : (%,%) -> Boolean if Complex(DoubleFloat) has SETCAT
--R
--E 1

--S 2 of 6
t1:CDFVEC:=qnew(5)
--R
--R   (1)  [0.,0.,0.,0.,0.]
--R                                                Type: ComplexDoubleFloatVector
--E 2

-- NOTE: CDFVEC arrays are 0-based, normal Axiom arrays are 1-based
--S 3 of 6
t1.1:=1.0+2*%i
--R
--R   (2)  1. + 2. %i
--R                                                    Type: Complex(DoubleFloat)
--E 3

--S 4 of 6
t1
--R
--R   (3)  [0.,1. + 2. %i,0.,0.,0.]
--R                                                Type: ComplexDoubleFloatVector
--E 4

--S 5 of 6
t1.0:=3.0+4.0*%i
--R
--R   (4)  3. + 4. %i
--R                                                    Type: Complex(DoubleFloat)
--E 5

--S 6 of 6
t1
--R
--R   (5)  [3. + 4. %i,1. + 2. %i,0.,0.,0.]
--R                                                Type: ComplexDoubleFloatVector
```

```
--E 6

)spool
)lisp (bye)
```

— ComplexDoubleFloatVector.help —

```
====================================================================
ComplexDoubleFloatVector examples
====================================================================
This domain creates a lisp simple array of machine complex doublefloats.
It provides one new function called qnew which takes an integer
that gives the array length.

NOTE: Unlike normal Axiom arrays the ComplexDoubleFloatVector arrays
are 0-based so the first element is 0. Axiom arrays normally
start at 1.

t1:CDFVEC:=qnew(5)
     [0.,0.,0.,0.,0.]

t1.1:=1.0+2*%i
     1. + 2. %i

t1
     [0.,1. + 2. %i,0.,0.,0.]


t1.0:=3.0+4.0*%i
     3. + 4. %i

t1

     [3. + 4. %i,1. + 2. %i,0.,0.,0.]

See Also:
o )help Float
o )help DoubleFloat
o )show ComplexDoubleFloatVector
```

4.10.1 ComplexDoubleFloatVector (CDFVEC)



Exports:

#?	-?	?*?	?+?
?-?	?.?	?<=?	?<?
?=?	?>=?	?>?	?~=?
any?	coerce	concat	construct
convert	copy	copyInto!	count
cross	delete	dot	elt
empty	empty?	entries	entry?
eq?	eval	every?	fill!
find	first	hash	index?
indices	insert	latex	length
less?	magnitude	map	map!
max	maxIndex	member?	members
merge	min	minIndex	more?
new	outerProduct	parts	position
qelt	qnew	qsetelt!	reduce
remove	removeDuplicates	reverse	reverse!
sample	select	setelt	size?
sort	sort!	sorted?	swap!
vector	zero		

— domain CDFVEC ComplexDoubleFloatVector —

```
)abbrev domain CDFVEC ComplexDoubleFloatVector
++ Author: Waldek Hebisch
++ Description: This is a low-level domain which implements vectors
++ (one dimensional arrays) of complex double precision floating point
++ numbers.  Indexing is 0 based, there is no bound checking (unless
++ provided by lower level).
ComplexDoubleFloatVector : VectorCategory Complex DoubleFloat with
    qnew : Integer -> %
      ++ qnew(n) creates a new uninitialized vector of length n.
      ++
      ++X t1:CDFVEC:=qnew 7
```

```
    vector: List Complex DoubleFloat -> %
      ++ vector(l) converts the list l to a vector.
      ++
      ++X t1:List(Complex(DoubleFloat)):=[1+2*%i,3+4*%i,-5-6*%i]
      ++X t2:CDFVEC:=vector(t1)
  == add

    Qelt1 ==> CDELT$Lisp
    Qsetelt1 ==> CDSETELT$Lisp

    qelt(x, i) == Qelt1(x, i)
    qsetelt_!(x, i, s) == Qsetelt1(x, i, s)
    Qsize ==> CDLEN$Lisp
    Qnew ==> MAKE_-CDOUBLE_-VECTOR$Lisp

    #x                          == Qsize x
    minIndex x                  == 0
    empty()                     == Qnew(0$Lisp)
    qnew(n)                     == Qnew(n)
    new(n, x)                   ==
        res := Qnew(n)
        fill_!(res, x)
    qelt(x, i)                  == Qelt1(x, i)
    elt(x:%, i:Integer)         == Qelt1(x, i)
    qsetelt_!(x, i, s)          == Qsetelt1(x, i, s)
    setelt(x : %, i : Integer, s : Complex DoubleFloat) ==
        Qsetelt1(x, i, s)
    fill_!(x, s)       ==
        for i in 0..((Qsize(x)) - 1) repeat Qsetelt1(x, i, s)
        x
```

———-

— CDFVEC.dotabb —

```
"CDFVEC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CDFVEC",
          shape=ellipse]
"COMPCAT" [color=lightblue,href="bookvol10.2.pdf#nameddest=COMPCAT"];
"CDFVEC" -> "COMPCAT"
```

———-

4.11 domain CONTFRAC ContinuedFraction

— ContinuedFraction.input —

```
)set break resume
)sys rm -f ContinuedFraction.output
)spool ContinuedFraction.output
)set message test on
)set message auto off
)clear all
--S 1 of 22
c := continuedFraction(314159/100000)
--R
--R
--R              1 |     1  |     1 |     1  |     1 |     1 |     1 |
--R   (1)  3 + +---+ + +----+ + +---+ + +----+ + +---+ + +---+ + +---+
--R            | 7     | 15     | 1     | 25     | 1     | 7     | 4
--R                                              Type: ContinuedFraction(Integer)
--E 1

--S 2 of 22
partialQuotients c
--R
--R
--R   (2)  [3,7,15,1,25,1,7,4]
--R                                                    Type: Stream(Integer)
--E 2

--S 3 of 22
convergents c
--R
--R
--R           22 333 355 9208 9563 76149 314159
--R   (3)  [3,--,---,---,----,----,-----,------]
--R            7 106 113 2931 3044 24239 100000
--R                                             Type: Stream(Fraction(Integer))
--E 3

--S 4 of 22
approximants c
--R
--R
--R                                        ------
--R           22 333 355 9208 9563 76149 314159
--R   (4)  [3,--,---,---,----,----,-----,------]
--R            7 106 113 2931 3044 24239 100000
--R                                             Type: Stream(Fraction(Integer))
--E 4

--S 5 of 22
pq := partialQuotients(1/c)
--R
--R
--R   (5)  [0,3,7,15,1,25,1,7,4]
```

```
--R                                                          Type: Stream(Integer)
--E 5

--S 6 of 22
continuedFraction(first pq,repeating [1],rest pq)
--R
--R
--R          1 |     1 |     1  |     1 |     1  |     1 |     1 |     1 |
--R   (6)  +---+ + +---+ + +----+ + +---+ + +----+ + +---+ + +---+ + +---+
--R        | 3     | 7     | 15     | 1     | 25     | 1     | 7     | 4
--R                                            Type: ContinuedFraction(Integer)
--E 6

--S 7 of 22
z:=continuedFraction(3,repeating [1],repeating [3,6])
--R
--R
--R   (7)
--R           1 |     1 |     1 |     1 |     1 |     1 |     1 |     1 |     1 |
--R     3 + +---+ + +---+ + +---+ + +---+ + +---+ + +---+ + +---+ + +---+ + +---+
--R         | 3     | 6     | 3     | 6     | 3     | 6     | 3     | 6     | 3
--R   +
--R       1 |
--R     +---+ + ...
--R     | 6
--R                                            Type: ContinuedFraction(Integer)
--E 7

--S 8 of 22
dens:Stream Integer := cons(1,generate((x+->x+4),6))
--R
--R
--R   (8)  [1,6,10,14,18,22,26,30,34,38,...]
--R                                                          Type: Stream(Integer)
--E 8

--S 9 of 22
cf := continuedFraction(0,repeating [1],dens)
--R
--R
--R   (9)
--R       1 |     1 |     1  |     1  |     1  |     1  |     1  |     1  |
--R     +---+ + +---+ + +----+ + +----+ + +----+ + +----+ + +----+ + +----+
--R     | 1     | 6     | 10     | 14     | 18     | 22     | 26     | 30
--R   +
--R       1  |     1  |
--R     +----+ + +----+ + ...
--R     | 34     | 38
--R                                            Type: ContinuedFraction(Integer)
--E 9
```

```
--S 10 of 22
ccf := convergents cf
--R
--R
--R              6 61  860 15541 342762  8927353 268163352  9126481321
--R   (10)  [0,1,-,--,----,-----,------,--------,---------,----------,...]
--R              7 71 1001 18089 398959 10391023 312129649 10622799089
--R                                              Type: Stream(Fraction(Integer))
--E 10

--S 11 of 22
eConvergents := [2*e + 1 for e in ccf]
--R
--R
--R              19 193 2721 49171 1084483 28245729 848456353 28875761731
--R   (11)  [1,3,--,---,----,-----,-------,--------,---------,----------,...]
--R               7  71 1001 18089  398959 10391023 312129649 10622799089
--R                                              Type: Stream(Fraction(Integer))
--E 11

--S 12 of 22
eConvergents :: Stream Float
--R
--R
--R   (12)
--R   [1.0, 3.0, 2.7142857142 857142857, 2.7183098591 549295775,
--R    2.7182817182 817182817, 2.7182818287 356957267, 2.7182818284 585634113,
--R    2.7182818284 590458514, 2.7182818284 590452348, 2.7182818284 590452354,
--R    ...]
--R                                                        Type: Stream(Float)
--E 12

--S 13 of 22
exp 1.0
--R
--R
--R   (13)  2.7182818284 590452354
--R                                                              Type: Float
--E 13

--S 14 of 22
cf := continuedFraction(1,[(2*i+1)**2 for i in 0..],repeating [2])
--R
--R
--R   (14)
--R            1 |     9 |     25 |     49 |     81 |     121 |     169 |     225 |
--R     1 + +---+ + +---+ + +----+ + +----+ + +----+ + +-----+ + +-----+ + +-----+
--R         | 2     | 2     | 2      | 2      | 2      |  2      |  2      |  2
--R   +
```

```
--R       289 |     361 |
--R     +-----+ + +-----+ + ...
--R     |  2      |  2
--R                                              Type: ContinuedFraction(Integer)
--E 14

--S 15 of 22
ccf := convergents cf
--R
--R
--R            3 15 105 315 3465 45045 45045 765765 14549535
--R   (15)  [1,-,--,---,---,----,-----,-----,------,--------,...]
--R            2 13  76 263 2578 36979 33976 622637 11064338
--R                                               Type: Stream(Fraction(Integer))
--E 15

--S 16 of 22
piConvergents := [4/p for p in ccf]
--R
--R
--R            8 52 304 1052 10312 147916 135904 2490548 44257352
--R   (16)  [4,-,--,---,----,-----,------,------,-------,--------,...]
--R            3 15 105  315  3465  45045  45045  765765 14549535
--R                                               Type: Stream(Fraction(Integer))
--E 16

--S 17 of 22
piConvergents :: Stream Float
--R
--R
--R   (17)
--R   [4.0, 2.6666666666 666666667, 3.4666666666 666666667,
--R    2.8952380952 380952381, 3.3396825396 825396825, 2.9760461760 461760462,
--R    3.2837384837 384837385, 3.0170718170 718170718, 3.2523659347 188758953,
--R    3.0418396189 294022111, ...]
--R                                                          Type: Stream(Float)
--E 17

--S 18 of 22
continuedFraction((- 122 + 597*%i)/(4 - 4*%i))
--R
--R
--R                              1    |         1     |
--R   (18)  - 90 + 59%i + +---------+ + +-----------+
--R                       | 1 - 2%i     | - 1 + 2%i
--R                                     Type: ContinuedFraction(Complex(Integer))
--E 18

--S 19 of 22
r : Fraction UnivariatePolynomial(x,Fraction Integer)
```

```
--R
--R                                                                    Type: Void
--E 19

--S 20 of 22
r := ((x - 1) * (x - 2)) / ((x-3) * (x-4))
--R
--R
--R           2
--R          x  - 3x + 2
--R   (20)  ------------
--R          2
--R         x  - 7x + 12
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 20

--S 21 of 22
continuedFraction r
--R
--R
--R                   1    |         1     |
--R   (21)  1 + +---------+ + +-----------+
--R             | 1     9     | 16     40
--R             | - x - -     | -- x - --
--R             | 4     8     |  3      3
--R           Type: ContinuedFraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 21

--S 22 of 22
[i*i for i in convergents(z) :: Stream Float]
--R
--R
--R   (22)
--R   [9.0, 11.1111111111 11111111, 10.9944598337 9501385, 11.0002777777 77777778,
--R    10.9999860763 98799786, 11.0000006979 29731039, 10.9999999650 15834446,
--R    11.0000000017 53603304, 10.9999999999 12099531, 11.0000000000 04406066,
--R    ...]
--R                                                          Type: Stream(Float)
--E 22
)spool
)lisp (bye)
```

———-

— ContinuedFraction.help —

```
=====================================================================
ContinuedFraction examples
=====================================================================
```

Continued fractions have been a fascinating and useful tool in mathematics for well over three hundred years. Axiom implements continued fractions for fractions of any Euclidean domain. In practice, this usually means rational numbers. In this section we demonstrate some of the operations available for manipulating both finite and infinite continued fractions.

The ContinuedFraction domain is a field and therefore you can add, subtract, multiply and divide the fractions.

The continuedFraction operation converts its fractional argument to a continued fraction.

```
  c := continuedFraction(314159/100000)
        1 |     1  |     1 |     1  |     1 |     1 |     1 |
   3 + +---+ + +----+ + +---+ + +----+ + +---+ + +---+ + +---+
       | 7     | 15     | 1     | 25     | 1     | 7     | 4
                        Type: ContinuedFraction Integer
```

This display is a compact form of the bulkier

$$3 + \cfrac{1}{7 + \cfrac{1}{15 + \cfrac{1}{1 + \cfrac{1}{25 + \cfrac{1}{1 + \cfrac{1}{7 + \cfrac{1}{4}}}}}}}$$

You can write any rational number in a similar form. The fraction will be finite and you can always take the "numerators" to be 1. That is, any rational number can be written as a simple, finite continued fraction of the form

$$a(1) + \cfrac{1}{a(2) + \cfrac{1}{a(3) + \cfrac{\ddots}{}}}$$

```
                                .
                                      1
                                -------------
                                a(n-1) +  1
                                         ----
                                         a(n)
```

The a(i) are called partial quotients and the operation partialQuotients creates a stream of them.

```
  partialQuotients c
   [3,7,15,1,25,1,7,4]
                        Type: Stream Integer
```

By considering more and more of the fraction, you get the convergents. For example, the first convergent is a(1), the second is a(1) + 1/a(2) and so on.

```
  convergents c
      22 333 355 9208 9563 76149 314159
   [3,--,---,---,----,----,-----,------]
       7 106 113 2931 3044 24239 100000
                        Type: Stream Fraction Integer
```

Since this is a finite continued fraction, the last convergent is the original rational number, in reduced form. The result of approximants is always an infinite stream, though it may just repeat the "last" value.

```
  approximants c
                                  ------
      22 333 355 9208 9563 76149 314159
   [3,--,---,---,----,----,-----,------]
       7 106 113 2931 3044 24239 100000
                        Type: Stream Fraction Integer
```

Inverting c only changes the partial quotients of its fraction by inserting a 0 at the beginning of the list.

```
  pq := partialQuotients(1/c)
   [0,3,7,15,1,25,1,7,4]
                        Type: Stream Integer
```

Do this to recover the original continued fraction from this list of partial quotients. The three-argument form of the continuedFraction operation takes an element which is the whole part of the fraction, a stream of elements which are the numerators of the fraction, and a stream of elements which are the denominators of the fraction.

```
  continuedFraction(first pq,repeating [1],rest pq)
```

```
   1 |     1 |     1  |     1 |     1  |     1 |     1 |     1 |
  +---+ + +---+ + +----+ + +---+ + +----+ + +---+ + +---+ + +---+
  | 3     | 7     | 15     | 1     | 25     | 1     | 7     | 4
                       Type: ContinuedFraction Integer
```

The streams need not be finite for continuedFraction. Can you guess which irrational number has the following continued fraction? See the end of this section for the answer.

```
  z:=continuedFraction(3,repeating [1],repeating [3,6])
          1 |     1 |     1 |     1 |     1 |     1 |     1 |     1 |     1 |
    3 + +---+ + +---+ + +---+ + +---+ + +---+ + +---+ + +---+ + +---+ + +---+
        | 3     | 6     | 3     | 6     | 3     | 6     | 3     | 6     | 3
  +
      1 |
    +---+ + ...
    | 6
                       Type: ContinuedFraction Integer
```

In 1737 Euler discovered the infinite continued fraction expansion

```
       e - 1             1
       ----- = ----------------------
         2     1 +         1
                   -----------------
                   6 +       1
                       -------------
                       10 +    1
                            --------
                            14 + ...
```

We use this expansion to compute rational and floating point approximations of e. For this and other interesting expansions, see C. D. Olds, Continued Fractions, New Mathematical Library, (New York: Random House, 1963), pp. 134--139.}

By looking at the above expansion, we see that the whole part is 0 and the numerators are all equal to 1. This constructs the stream of denominators.

```
  dens:Stream Integer := cons(1,generate((x+->x+4),6))
   [1,6,10,14,18,22,26,30,34,38,...]
                       Type: Stream Integer
```

Therefore this is the continued fraction expansion for (e - 1) / 2.

```
  cf := continuedFraction(0,repeating [1],dens)
       1 |     1 |     1  |     1  |     1  |     1  |     1  |     1  |
    +---+ + +---+ + +----+ + +----+ + +----+ + +----+ + +----+ + +----+
```

```
     | 1     | 6     | 10     | 14     | 18     | 22     | 26     | 30
   +
       1  |     1  |
     +----+ + +----+ + ...
     | 34     | 38
                  Type: ContinuedFraction Integer
```

These are the rational number convergents.

```
  ccf := convergents cf
       6 61  860 15541 342762  8927353 268163352  9126481321
   [0,1,-,--,----,-----,------,--------,---------,-----------,...]
       7 71 1001 18089 398959 10391023 312129649 10622799089
                  Type: Stream Fraction Integer
```

You can get rational convergents for e by multiplying by 2 and adding 1.

```
  eConvergents := [2*e + 1 for e in ccf]
        19 193 2721 49171 1084483 28245729 848456353 28875761731
    [1,3,--,---,----,-----,-------,--------,---------,-----------,...]
         7  71 1001 18089  398959 10391023 312129649 10622799089
                  Type: Stream Fraction Integer
```

You can also compute the floating point approximations to these convergents.

```
  eConvergents :: Stream Float
   [1.0, 3.0, 2.7142857142 857142857, 2.7183098591 549295775,
    2.7182817182 817182817, 2.7182818287 356957267, 2.7182818284 585634113,
    2.7182818284 590458514, 2.7182818284 590452348, 2.7182818284 590452354,
    ...]
                      Type: Stream Float
```

Compare this to the value of e computed by the exp operation in Float.

```
  exp 1.0
   2.7182818284 590452354
                      Type: Float
```

In about 1658, Lord Brouncker established the following expansion
for 4 / pi,

$$1 + \cfrac{1}{2 + \cfrac{9}{2 + \cfrac{25}{2 + \cfrac{49}{2 + \cfrac{81}{}}}}}$$

```
                          -------
                          2 + ...
```

Let's use this expansion to compute rational and floating point approximations for pi.

```
  cf := continuedFraction(1,[(2*i+1)**2 for i in 0..],repeating [2])
           1 |     9 |     25 |     49 |     81 |     121 |     169 |     225 |
     1 + +---+ + +---+ + +----+ + +----+ + +----+ + +-----+ + +-----+ + +-----+
         | 2     | 2     | 2      | 2      | 2      |  2      |  2      |  2
   +
       289 |     361 |
     +-----+ + +-----+ + ...
     |  2      |  2
                       Type: ContinuedFraction Integer

  ccf := convergents cf
      3 15 105 315 3465 45045 45045 765765 14549535
   [1,-,--,---,---,----,-----,-----,------,--------,...]
      2 13  76 263 2578 36979 33976 622637 11064338
                       Type: Stream Fraction Integer

  piConvergents := [4/p for p in ccf]
      8 52 304 1052 10312 147916 135904 2490548 44257352
   [4,-,--,---,----,-----,------,------,-------,--------,...]
      3 15 105  315  3465  45045  45045  765765 14549535
                       Type: Stream Fraction Integer
```

As you can see, the values are converging to pi = 3.14159265358979323846..., but not very quickly.

```
  piConvergents :: Stream Float
   [4.0, 2.6666666666 666666667, 3.4666666666 666666667,
    2.8952380952 380952381, 3.3396825396 825396825, 2.9760461760 461760462,
    3.2837384837 384837385, 3.0170718170 718170718, 3.2523659347 188758953,
    3.0418396189 294022111, ...]
                       Type: Stream Float
```

You need not restrict yourself to continued fractions of integers. Here is an expansion for a quotient of Gaussian integers.

```
  continuedFraction((- 122 + 597*%i)/(4 - 4*%i))
                       1    |         1     |
   - 90 + 59%i + +---------+ + +-----------+
                 | 1 - 2%i     | - 1 + 2%i
                       Type: ContinuedFraction Complex Integer
```

This is an expansion for a quotient of polynomials in one variable with rational number coefficients.

```
  r : Fraction UnivariatePolynomial(x,Fraction Integer)
                      Type: Void

  r := ((x - 1) * (x - 2)) / ((x-3) * (x-4))
     2
    x  - 3x + 2
   ------------
    2
   x  - 7x + 12
                      Type: Fraction UnivariatePolynomial(x,Fraction Integer)

  continuedFraction r
            1    |         1     |
   1 + +---------+ + +-----------+
       | 1     9     | 16     40
       | - x - -     | -- x - --
       | 4     8     |  3      3
             Type: ContinuedFraction UnivariatePolynomial(x,Fraction Integer)
```

To conclude this section, we give you evidence that


```
    z = 3 +            1
            ------------------------
            3 +           1
                ------------------
                6 +         1
                    ---------------
                    3 +       1
                        -----------
                        6 +     1
                            -------
                            3 + ...
```

is the expansion of sqrt(11).

```
  [i*i for i in convergents(z) :: Stream Float]
   [9.0, 11.1111111111 11111111, 10.9944598337 9501385, 11.0002777777 77777778,
    10.9999860763 98799786, 11.0000006979 29731039, 10.9999999650 15834446,
    11.0000000017 53603304, 10.9999999999 12099531, 11.0000000000 04406066,
    ...]
                      Type: Stream Float
```

See Also:
o)help Stream
o)show ContinuedFraction

4.11.1 ContinuedFraction (CONTFRAC)



Exports:

0	1	approximants
associates?	characteristic	coerce
complete	continuedFraction	convergents
denominators	divide	extend
euclideanSize	expressIdealMember	exquo
extendedEuclidean	factor	gcd
gcdPolynomial	hash	inv
latex	lcm	multiEuclidean
numerators	one?	partialDenominators
partialNumerators	partialQuotients	prime?
principalIdeal	recip	reducedContinuedFraction
reducedForm	sample	sizeLess?
squareFree	squareFreePart	subtractIfCan
unit?	unitCanonical	unitNormal
wholePart	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain CONTFRAC ContinuedFraction —

```
)abbrev domain CONTFRAC ContinuedFraction
++ Author: Stephen M. Watt
++ Date Created: January 1987
++ Change History:
++   11 April   1990
++    7 October 1991 -- SMW: Treat whole part specially.  Added comments.
++ Basic Operations:
++   (Field), (Algebra),
++   approximants, complete, continuedFraction, convergents, denominators,
++   extend, numerators, partialDenominators, partialNumerators,
++   partialQuotients, reducedContinuedFraction, reducedForm, wholePart
```

```
++ Related Constructors:
++ Also See: Fraction
++ AMS Classifications: 11A55 11J70 11K50 11Y65 30B70 40A15
++ Keywords: continued fraction, convergent
++ References:
++ Description:
++ \spadtype{ContinuedFraction} implements general
++ continued fractions.  This version is not restricted to simple,
++ finite fractions and uses the \spadtype{Stream} as a
++ representation.  The arithmetic functions assume that the
++ approximants alternate below/above the convergence point.
++ This is enforced by ensuring the partial numerators and partial
++ denominators are greater than 0 in the Euclidean domain view of \spad{R}
++ (i.e. \spad{sizeLess?(0, x)}).

ContinuedFraction(R): Exports == Implementation where
  R :     EuclideanDomain
  Q   ==> Fraction R
  MT  ==> MoebiusTransform Q
  OUT ==> OutputForm

  Exports ==> Join(Algebra R,Algebra Q,Field) with
    continuedFraction:        Q -> %
      ++ continuedFraction(r) converts the fraction \spadvar{r} with
      ++ components of type \spad{R} to a continued fraction over
      ++ \spad{R}.

    continuedFraction:        (R, Stream R, Stream R) -> %
      ++ continuedFraction(b0,a,b) constructs a continued fraction in
      ++ the following way:  if \spad{a = [a1,a2,...]} and \spad{b =
      ++ [b1,b2,...]} then the result is the continued fraction
      ++ \spad{b0 + a1/(b1 + a2/(b2 + ...))}.

    reducedContinuedFraction: (R, Stream R) -> %
      ++ reducedContinuedFraction(b0,b) constructs a continued
      ++ fraction in the following way:  if \spad{b = [b1,b2,...]}
      ++ then the result is the continued fraction \spad{b0 + 1/(b1 +
      ++ 1/(b2 + ...))}.  That is, the result is the same as
      ++ \spad{continuedFraction(b0,[1,1,1,...],[b1,b2,b3,...])}.

    partialNumerators:   % -> Stream R
      ++ partialNumerators(x) extracts the numerators in \spadvar{x}.
      ++ That is, if \spad{x = continuedFraction(b0, [a1,a2,a3,...],
      ++ [b1,b2,b3,...])}, then \spad{partialNumerators(x) =
      ++ [a1,a2,a3,...]}.

    partialDenominators: % -> Stream R
      ++ partialDenominators(x) extracts the denominators in
      ++ \spadvar{x}.  That is, if \spad{x = continuedFraction(b0,
      ++ [a1,a2,a3,...], [b1,b2,b3,...])}, then
```

```
  ++ \spad{partialDenominators(x) = [b1,b2,b3,...]}.

partialQuotients:    % -> Stream R
  ++ partialQuotients(x) extracts the partial quotients in
  ++ \spadvar{x}.  That is, if \spad{x = continuedFraction(b0,
  ++ [a1,a2,a3,...], [b1,b2,b3,...])}, then
  ++ \spad{partialQuotients(x) = [b0,b1,b2,b3,...]}.

wholePart:           % -> R
  ++ wholePart(x) extracts the whole part of \spadvar{x}.  That
  ++ is, if \spad{x = continuedFraction(b0, [a1,a2,a3,...],
  ++ [b1,b2,b3,...])}, then \spad{wholePart(x) = b0}.

reducedForm:         % -> %
  ++ reducedForm(x) puts the continued fraction \spadvar{x} in
  ++ reduced form, i.e.  the function returns an equivalent
  ++ continued fraction of the form
  ++ \spad{continuedFraction(b0,[1,1,1,...],[b1,b2,b3,...])}.

approximants:        % -> Stream Q
  ++ approximants(x) returns the stream of approximants of the
  ++ continued fraction \spadvar{x}. If the continued fraction is
  ++ finite, then the stream will be infinite and periodic with
  ++ period 1.

convergents:         % -> Stream Q
  ++ convergents(x) returns the stream of the convergents of the
  ++ continued fraction \spadvar{x}. If the continued fraction is
  ++ finite, then the stream will be finite.

numerators:          % -> Stream R
  ++ numerators(x) returns the stream of numerators of the
  ++ approximants of the continued fraction \spadvar{x}. If the
  ++ continued fraction is finite, then the stream will be finite.

denominators:        % -> Stream R
  ++ denominators(x) returns the stream of denominators of the
  ++ approximants of the continued fraction \spadvar{x}. If the
  ++ continued fraction is finite, then the stream will be finite.

extend:              (%,Integer) -> %
  ++ extend(x,n) causes the first \spadvar{n} entries in the
  ++ continued fraction \spadvar{x} to be computed.  Normally
  ++ entries are only computed as needed.

complete:            % -> %
  ++ complete(x) causes all entries in \spadvar{x} to be computed.
  ++ Normally entries are only computed as needed.  If \spadvar{x}
  ++ is an infinite continued fraction, a user-initiated interrupt is
  ++ necessary to stop the computation.
```

```
 Implementation ==> add

-- isOrdered  ==> R is Integer
   isOrdered  ==> R has OrderedRing and R has multiplicativeValuation
   canReduce? ==> isOrdered or R has additiveValuation

   Rec ==> Record(num: R, den: R)
   Str ==> Stream Rec
   Rep :=  Record(value: Record(whole: R, fract: Str), reduced?: Boolean)

   import Str

   genFromSequence:     Stream Q -> %
   genReducedForm:      (Q, Stream Q, MT)    -> Stream Rec
   genFractionA:        (Stream R,Stream R)  -> Stream Rec
   genFractionB:        (Stream R,Stream R)  -> Stream Rec
   genNumDen:           (R,R, Stream Rec)    -> Stream R

   genApproximants:     (R,R,R,R,Stream Rec) -> Stream Q
   genConvergents:      (R,R,R,R,Stream Rec) -> Stream Q
   iGenApproximants:    (R,R,R,R,Stream Rec) -> Stream Q
   iGenConvergents:     (R,R,R,R,Stream Rec) -> Stream Q

   reducedForm c ==
       c.reduced? => c
       explicitlyFinite? c.value.fract =>
                     continuedFraction last complete convergents c
       canReduce? => genFromSequence approximants c
       error "Reduced form not defined for this continued fraction."

   eucWhole(a: Q): R == numer a quo denom a

   eucWhole0(a: Q): R ==
       isOrdered =>
           n := numer a
           d := denom a
           q := n quo d
           r := n - q*d
           if r < 0 then q := q - 1
           q
       eucWhole a

   x = y ==
       x := reducedForm x
       y := reducedForm y

       x.value.whole ^= y.value.whole => false

       xl := x.value.fract; yl := y.value.fract
```

```
        while not empty? xl and not empty? yl repeat
            frst.xl.den ^= frst.yl.den => return false
            xl := rst xl; yl := rst yl
        empty? xl and empty? yl

    continuedFraction q == q :: %

    if isOrdered then
        continuedFraction(wh,nums,dens) == [[wh,genFractionA(nums,dens)],false]

        genFractionA(nums,dens) ==
            empty? nums or empty? dens => empty()
            n := frst nums
            d := frst dens
            n < 0 => error "Numerators must be greater than 0."
            d < 0 => error "Denominators must be greater than 0."
            concat([n,d]$Rec, delay genFractionA(rst nums,rst dens))
    else
        continuedFraction(wh,nums,dens) == [[wh,genFractionB(nums,dens)],false]

        genFractionB(nums,dens) ==
            empty? nums or empty? dens => empty()
            n := frst nums
            d := frst dens
            concat([n,d]$Rec, delay genFractionB(rst nums,rst dens))

    reducedContinuedFraction(wh,dens) ==
        continuedFraction(wh, repeating [1], dens)

    coerce(n:Integer):% == [[n::R,empty()], true]
    coerce(r:R):%       == [[r,   empty()], true]

    coerce(a: Q): % ==
      wh := eucWhole0 a
      fr := a - wh::Q
      zero? fr => [[wh, empty()], true]

      l : List Rec := empty()
      n := numer fr
      d := denom fr
      while not zero? d repeat
        qr := divide(n,d)
        l  := concat([1,qr.quotient],l)
        n  := d
        d  := qr.remainder
      [[wh, construct rest reverse_! l], true]

    characteristic() == characteristic()$Q
```

```
genFromSequence apps ==
    lo := first apps; apps := rst apps
    hi := first apps; apps := rst apps
    while eucWhole0 lo ^= eucWhole0 hi repeat
        lo := first apps; apps := rst apps
        hi := first apps; apps := rst apps
    wh := eucWhole0 lo
    [[wh, genReducedForm(wh::Q, apps, moebius(1,0,0,1))], canReduce?]

genReducedForm(wh0, apps, mt) ==
    lo: Q := first apps - wh0; apps := rst apps
    hi: Q := first apps - wh0; apps := rst apps
    lo = hi and zero? eval(mt, lo) => empty()
    mt  := recip mt
    wlo := eucWhole eval(mt, lo)
    whi := eucWhole eval(mt, hi)
    while wlo ^= whi repeat
        wlo := eucWhole eval(mt, first apps - wh0); apps := rst apps
        whi := eucWhole eval(mt, first apps - wh0); apps := rst apps
    concat([1,wlo], delay genReducedForm(wh0, apps, shift(mt, -wlo::Q)))

wholePart c ==
  c.value.whole
partialNumerators c ==
  map(x1+->x1.num, c.value.fract)$StreamFunctions2(Rec,R)
partialDenominators c ==
  map(x1+->x1.den, c.value.fract)$StreamFunctions2(Rec,R)
partialQuotients c ==
  concat(c.value.whole, partialDenominators c)

approximants c ==
  empty? c.value.fract => repeating [c.value.whole::Q]
  genApproximants(1,0,c.value.whole,1,c.value.fract)
convergents c ==
  empty? c.value.fract => concat(c.value.whole::Q, empty())
  genConvergents (1,0,c.value.whole,1,c.value.fract)
numerators c ==
  empty? c.value.fract => concat(c.value.whole, empty())
  genNumDen(1,c.value.whole,c.value.fract)
denominators c ==
  genNumDen(0,1,c.value.fract)

extend(x,n) == (extend(x.value.fract,n); x)
complete(x) == (complete(x.value.fract); x)

iGenApproximants(pm2,qm2,pm1,qm1,fr) == delay
  nd := frst fr
  pm := nd.num*pm2 + nd.den*pm1
  qm := nd.num*qm2 + nd.den*qm1
```

```
  genApproximants(pm1,qm1,pm,qm,rst fr)

genApproximants(pm2,qm2,pm1,qm1,fr) ==
  empty? fr => repeating [pm1/qm1]
  concat(pm1/qm1,iGenApproximants(pm2,qm2,pm1,qm1,fr))

iGenConvergents(pm2,qm2,pm1,qm1,fr) == delay
  nd := frst fr
  pm := nd.num*pm2 + nd.den*pm1
  qm := nd.num*qm2 + nd.den*qm1
  genConvergents(pm1,qm1,pm,qm,rst fr)

genConvergents(pm2,qm2,pm1,qm1,fr) ==
  empty? fr => concat(pm1/qm1, empty())
  concat(pm1/qm1,iGenConvergents(pm2,qm2,pm1,qm1,fr))

genNumDen(m2,m1,fr) ==
  empty? fr => concat(m1,empty())
  concat(m1,delay genNumDen(m1,m2*frst(fr).num + m1*frst(fr).den,rst fr))

gen  ==> genFromSequence
apx  ==> approximants

c, d: %
a: R
q: Q
n: Integer

0 == (0$R) :: %
1 == (1$R) :: %

c + d   == genFromSequence map((x,y) +-> x + y, apx c, apx d)
c - d   == genFromSequence map((x,y) +-> x - y, apx c, rest apx d)
- c     == genFromSequence map(x +-> - x, rest apx c)
c * d   == genFromSequence map((x,y) +-> x * y, apx c, apx d)
a * d   == genFromSequence map(x +-> a * x, apx d)
q * d   == genFromSequence map(x +-> q * x, apx d)
n * d   == genFromSequence map(x +-> n * x, apx d)
c / d   == genFromSequence map((x,y) +-> x / y, apx c, rest apx d)
recip c ==(c = 0 => "failed";
   genFromSequence map(x +-> 1/x, rest apx c))

showAll?: () -> Boolean
showAll?() ==
  NULL(_$streamsShowAll$Lisp)$Lisp => false
  true

zagRec(t:Rec):OUT == zag(t.num :: OUT,t.den :: OUT)

coerce(c:%): OUT ==
```

```
      wh := c.value.whole
      fr := c.value.fract
      empty? fr => wh :: OUT
      count : NonNegativeInteger := _$streamCount$Lisp
      l : List OUT := empty()
      for n in 1..count while not empty? fr repeat
        l  := concat(zagRec frst fr,l)
        fr := rst fr
      if showAll?() then
        for n in (count + 1).. while explicitEntries? fr repeat
          l  := concat(zagRec frst fr,l)
          fr := rst fr
      if not explicitlyEmpty? fr then l := concat("..." :: OUT,l)
      l := reverse_! l
      e := reduce("+",l)
      zero? wh => e
      (wh :: OUT) + e
```

———-

— CONTFRAC.dotabb —

```
"CONTFRAC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=CONTFRAC"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"CONTFRAC" -> "PFECAT"
```

———-

Chapter 5

Chapter D

5.1 domain DBASE Database

— Database.input —

```
)set break resume
)sys rm -f Database.output
)spool Database.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Database
--R
--R Database(S) where
--R   S: OrderedSet with
--R       ?.? : (%,Symbol) -> String
--R       display : % -> Void
--R       fullDisplay : % -> Void  is a domain constructor
--R Abbreviation for Database is DBASE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DBASE
--R
--R------------------------------ Operations --------------------------------
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                coerce : List(S) -> %
--R coerce : % -> OutputForm              display : % -> Void
--R ?.? : (%,QueryEquation) -> %          fullDisplay : % -> Void
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R ?.? : (%,Symbol) -> DataList(String)
```

```
--R fullDisplay : (%,PositiveInteger,PositiveInteger) -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Database.help** —

```
=====================================================================
Database examples
=====================================================================

See Also:
o )show Database
```

———-

5.1.1 Database (DBASE)



See

⇒ “DataList” (DLIST) 5.2.1 on page 447
⇒ “IndexCard” (ICARD) 10.2.1 on page 1163
⇒ “QueryEquation” (QEQUAT) 18.4.1 on page 2135

Exports:

coerce	display	fullDisplay	hash	latex
?+?	?-?	?=?	?~=?	?.?

— **domain DBASE Database** —

```
)abbrev domain DBASE Database
++ Author: Mark Botch
```

```
++ Description:
++ This domain implements a simple view of a database whose fields are
++ indexed by symbols

Database(S): Exports == Implementation where
  S: OrderedSet with
    elt: (%,Symbol) -> String
      ++ elt(x,s) returns an element of x indexed by s
    display: % -> Void
      ++ display(x) displays x in some form
    fullDisplay: % -> Void
      ++ fullDisplay(x) displays x in detail
  Exports == SetCategory with
    elt: (%,QueryEquation) -> %
      ++ elt(db,q) returns all elements of \axiom{db} which satisfy \axiom{q}.
    elt: (%,Symbol) -> DataList String
      ++ elt(db,s) returns the \axiom{s} field of each element of \axiom{db}.
    _+: (%,%) -> %
      ++ db1+db2 returns the merge of databases db1 and db2
    _-: (%,%) -> %
      ++ db1-db2 returns the difference of databases db1 and db2 i.e. consisting
      ++ of elements in db1 but not in db2
    coerce: List S -> %
      ++ coerce(l) makes a database out of a list
    display: % -> Void
      ++ display(db) prints a summary line for each entry in \axiom{db}.
    fullDisplay: % -> Void
      ++ fullDisplay(db) prints full details of each entry in \axiom{db}.
    fullDisplay: (%,PositiveInteger,PositiveInteger) -> Void
      ++ fullDisplay(db,start,end ) prints full details of entries in the range
      ++ \axiom{start..end} in \axiom{db}.
  Implementation == List S add
    s: Symbol
    Rep := List S
    coerce(u: List S):% == u@%
    elt(data: %,s: Symbol) == [x.s for x in data] :: DataList(String)
    elt(data: %,eq: QueryEquation) ==
      field := variable eq
      val := value eq
      [x for x in data | stringMatches?(val,x.field)$Lisp]
    x+y==removeDuplicates_! merge(x,y)
    x-y==mergeDifference(copy(x::Rep),y::Rep)$MergeThing(S)
    coerce(data): OutputForm == (#data):: OutputForm
    display(data) ==  for x in data repeat display x
    fullDisplay(data) == for x in data repeat fullDisplay x
    fullDisplay(data,n,m) == for x in data for i in 1..m repeat
      if i >= n then fullDisplay x
```

———-

— DBASE.dotabb —

```
"DBASE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DBASE"]
"STRICAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=STRICAT"]
"DBASE" -> "STRICAT"
```

———-

5.2 domain DLIST DataList

— DataList.input —

```
)set break resume
)sys rm -f DataList.output
)spool DataList.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DataList
--R
--R DataList(S: OrderedSet)  is a domain constructor
--R Abbreviation for DataList is DLIST
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DLIST
--R
--R------------------------------ Operations ------------------------------
--R children : % -> List(%)               coerce : % -> List(S)
--R coerce : List(S) -> %                 concat : (%,S) -> %
--R concat : List(%) -> %                 concat : (S,%) -> %
--R concat : (%,%) -> %                   concat! : (%,S) -> %
--R concat! : (%,%) -> %                  construct : List(S) -> %
--R copy : % -> %                         cycleEntry : % -> %
--R cycleTail : % -> %                    cyclic? : % -> Boolean
--R datalist : List(S) -> %               delete : (%,Integer) -> %
--R delete! : (%,Integer) -> %            distance : (%,%) -> Integer
--R ?.sort : (%,sort) -> %                ?.unique : (%,unique) -> %
--R elt : (%,Integer,S) -> S              ?.? : (%,Integer) -> S
--R ?.last : (%,last) -> S                ?.rest : (%,rest) -> %
--R ?.first : (%,first) -> S              ?.value : (%,value) -> S
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(S)                eq? : (%,%) -> Boolean
--R explicitlyFinite? : % -> Boolean      first : % -> S
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
```

```
--R insert : (S,%,Integer) -> %          insert : (%,%,Integer) -> %
--R insert! : (S,%,Integer) -> %         insert! : (%,%,Integer) -> %
--R last : % -> S                       leaf? : % -> Boolean
--R leaves : % -> List(S)               list : S -> %
--R map : (((S,S) -> S),%,%) -> %       map : ((S -> S),%) -> %
--R new : (NonNegativeInteger,S) -> %   nodes : % -> List(%)
--R possiblyInfinite? : % -> Boolean    qelt : (%,Integer) -> S
--R rest : % -> %                       reverse : % -> %
--R sample : () -> %                    second : % -> S
--R tail : % -> %                       third : % -> S
--R value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R convert : % -> InputForm if S has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R cycleLength : % -> NonNegativeInteger
--R cycleSplit! : % -> % if $ has shallowlyMutable
--R delete : (%,UniversalSegment(Integer)) -> %
--R delete! : (%,UniversalSegment(Integer)) -> %
--R ?.count : (%,count) -> NonNegativeInteger
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R find : ((S -> Boolean),%) -> Union(S,"failed")
--R first : (%,NonNegativeInteger) -> %
--R hash : % -> SingleInteger if S has SETCAT
--R last : (%,NonNegativeInteger) -> %
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R merge : (((S,S) -> Boolean),%,%) -> %
--R merge : (%,%) -> % if S has ORDSET
```

```
--R merge! : (((S,S) -> Boolean),%,%) -> %
--R merge! : (%,%) -> % if S has ORDSET
--R min : (%,%) -> % if S has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R position : ((S -> Boolean),%) -> Integer
--R position : (S,%) -> Integer if S has SETCAT
--R position : (S,%,Integer) -> Integer if S has SETCAT
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R reduce : (((S,S) -> S),%,S,S) -> S if $ has finiteAggregate and S has SETCAT
--R reduce : (((S,S) -> S),%,S) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%) -> S if $ has finiteAggregate
--R remove : (S,%) -> % if $ has finiteAggregate and S has SETCAT
--R remove : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : ((S -> Boolean),%) -> %
--R remove! : (S,%) -> % if S has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and S has SETCAT
--R removeDuplicates! : % -> % if S has SETCAT
--R rest : (%,NonNegativeInteger) -> %
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((S -> Boolean),%) -> %
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R setelt : (%,UniversalSegment(Integer),S) -> S if $ has shallowlyMutable
--R setelt : (%,last,S) -> S if $ has shallowlyMutable
--R setelt : (%,rest,%) -> % if $ has shallowlyMutable
--R setelt : (%,first,S) -> S if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setfirst! : (%,S) -> S if $ has shallowlyMutable
--R setlast! : (%,S) -> S if $ has shallowlyMutable
--R setrest! : (%,%) -> % if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : (((S,S) -> Boolean),%) -> %
--R sort : % -> % if S has ORDSET
--R sort! : (((S,S) -> Boolean),%) -> % if $ has shallowlyMutable
--R sort! : % -> % if $ has shallowlyMutable and S has ORDSET
--R sorted? : (((S,S) -> Boolean),%) -> Boolean
--R sorted? : % -> Boolean if S has ORDSET
--R split! : (%,Integer) -> % if $ has shallowlyMutable
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **DataList.help** —

```
=====================================================================
DataList examples
=====================================================================

See Also:
o )show DataList
```

———-

5.2.1 DataList (DLIST)



See

⇒ “IndexCard” (ICARD) 10.2.1 on page 1163
⇒ “Database” (DBASE) 5.1.1 on page 442
⇒ “QueryEquation” (QEQUAT) 18.4.1 on page 2135

Exports:

any?	child?	children	coerce
concat	concat!	construct	convert
copy	copyInto!	count	cycleEntry
cycleLength	cycleSplit!	cycleTail	cyclic?
datalist	delete	delete!	distance
elt	empty	empty?	entries
entry?	eq?	eval	every?
explicitlyFinite?	fill!	find	first
hash	index?	indices	insert
insert!	last	latex	leaf?
leaves	less?	list	map
map!	max	maxIndex	member?
members	merge	merge!	min
minIndex	more?	new	node?
nodes	parts	position	possiblyInfinite?
qelt	qsetelt!	reduce	remove
remove!	removeDuplicates	removeDuplicates!	rest
reverse	reverse!	sample	second
select	select!	setchildren!	setelt
setfirst!	setlast!	setrest!	setvalue!
size?	sort	sort!	sorted?
split!	swap!	tail	third
value	#?	?<?	?<=?
?=?	?>?	?>=?	?.?
?~=?	?.count	?.sort	?.unique
?.last	?.rest	?.first	?.value

— domain DLIST DataList —

```
)abbrev domain DLIST DataList
++ Author: Mark Botch
++ Description:
++ This domain provides some nice functions on lists

DataList(S:OrderedSet) : Exports == Implementation where
  Exports == ListAggregate(S) with
    coerce: List S -> %
      ++ coerce(l) creates a datalist from l
    coerce: % -> List S
      ++ coerce(x) returns the list of elements in x
    datalist: List S -> %
      ++ datalist(l) creates a datalist from l
    elt: (%,"unique") -> %
      ++ \axiom{l.unique} returns \axiom{l} with duplicates removed.
      ++ Note: \axiom{l.unique = removeDuplicates(l)}.
    elt: (%,"sort") -> %
      ++ \axiom{l.sort} returns \axiom{l} with elements sorted.
```

```
      ++ Note: \axiom{l.sort = sort(l)}
    elt: (%,"count") -> NonNegativeInteger
      ++ \axiom{l."count"} returns the number of elements in \axiom{l}.
  Implementation == List(S) add
    elt(x,"unique") == removeDuplicates(x)
    elt(x,"sort") == sort(x)
    elt(x,"count") == #x
    coerce(x:List S) == x pretend %
    coerce(x:%):List S == x pretend (List S)
    coerce(x:%): OutputForm == (x :: List S) :: OutputForm
    datalist(x:List S) == x::%
```

———-

— **DLIST.dotabb** —

```
"DLIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DLIST"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"DLIST" -> "FLAGG"
```

———-

5.3 domain DECIMAL DecimalExpansion

— **DecimalExpansion.input** —

```
)set break resume
)sys rm -f DecimalExpansion.output
)spool DecimalExpansion.output
)set message test on
)set message auto off
)clear all
--S 1 of 7
r := decimal(22/7)
--R
--R
--R          ------
--R   (1)  3.142857
--R                                                  Type: DecimalExpansion
--E 1

--S 2 of 7
r + decimal(6/7)
--R
```

```
--R
--R   (2)  4
--R                                                          Type: DecimalExpansion
--E 2

--S 3 of 7
[decimal(1/i) for i in 350..354]
--R
--R
--R   (3)
--R        ______    ______          __    ________________________________
--R   [0.00285714, 0.002849, 0.0028409, 0.00283286118980169971671388101983,
--R       ____________________________________________________________
--R    0.00282485875706214689265536723163841807909604519774011299435]
--R                                                 Type: List(DecimalExpansion)
--E 3

--S 4 of 7
decimal(1/2049)
--R
--R
--R   (4)
--R   0.
--R     OVERBAR
--R        000488042947779404587603709126403123474865788189360663738408979990239l4
--R          104441190824792581747193753050268423621278672523182040019521717911176
--R          183504148365056124938994631527574426549536359199609565641776476329917
--R          032698877501220107369448511469009272816007808687164470473401659346022
--R          449975597852611029770619814543679843826256710590531966813079551
--R                                                          Type: DecimalExpansion
--E 4

--S 5 of 7
p := decimal(1/4)*x**2 + decimal(2/3)*x + decimal(4/9)
--R
--R
--R             2     _      _
--R   (5)  0.25x  + 0.6x + 0.4
--R                                          Type: Polynomial(DecimalExpansion)
--E 5

--S 6 of 7
q := differentiate(p, x)
--R
--R
--R                _
--R   (6)  0.5x + 0.6
--R                                          Type: Polynomial(DecimalExpansion)
--E 6
```

```
--S 7 of 7
g := gcd(p, q)
--R
--R
--R              _
--R   (7)  x + 1.3
--R                                          Type: Polynomial(DecimalExpansion)
--E 7
)spool
)lisp (bye)
```

— DecimalExpansion.help —

```
========================================================================
DecimalExpansion examples
========================================================================

All rationals have repeating decimal expansions.  Operations to access
the individual digits of a decimal expansion can be obtained by
converting the value to RadixExpansion(10).

The operation decimal is used to create this expansion of type
DecimalExpansion.

  r := decimal(22/7)
      ------
    3.142857
                       Type: DecimalExpansion

Arithmetic is exact.

  r + decimal(6/7)
   4
                       Type: DecimalExpansion

The period of the expansion can be short or long ...

  [decimal(1/i) for i in 350..354]
        ------    ------         --    ---------------------------------
   [0.00285714, 0.002849, 0.0028409, 0.00283286118980169971671388101983,
       ------------------------------------------------------------
    0.00282485875706214689265536723163841807909604519774011299435]
                       Type: List DecimalExpansion

or very long.

  decimal(1/2049)
```

```
   ------------------------------------------------------------------------
  0.000488042947779404587603709126403123474865788189360663738408979990239 14
   ------------------------------------------------------------------------
   1044411908247925817471937530502684236212786725231820400195217179111 76
   ------------------------------------------------------------------------
   1835041483650561249389946315275744265495363591996095656417764763299 17
   ------------------------------------------------------------------------
   0326988775012201073694485114690092728160078086871644704734016593460 22
   ------------------------------------------------------------------
   4499755978526110297706198145436798438262567105905319668130795 51
                  Type: DecimalExpansion
```

These numbers are bona fide algebraic objects.


```
  p := decimal(1/4)*x**2 + decimal(2/3)*x + decimal(4/9)
        2     _      _
   0.25x  + 0.6x + 0.4
                  Type: Polynomial DecimalExpansion

  q := differentiate(p, x)
           _
   0.5x + 0.6
                  Type: Polynomial DecimalExpansion

  g := gcd(p, q)
         _
   x + 1.3
                  Type: Polynomial DecimalExpansion
```

See Also:
-)help RadixExpansion
-)help BinaryExpansion
-)help HexadecimalExpansion
-)show DecimalExpansion

5.3.1 DecimalExpansion (DECIMAL)



See

⇒ “RadixExpansion” (RADIX) 19.2.1 on page 2171
⇒ “BinaryExpansion” (BINARY) 3.7.1 on page 276
⇒ “HexadecimalExpansion” (HEXADEC) 9.3.1 on page 1112

Exports:

0	1	abs
associates?	ceiling	characteristic
charthRoot	coerce	conditionP
convert	D	decimal
denom	denominator	differentiate
divide	euclideanSize	eval
expressIdealMember	exquo	extendedEuclidean
factor	factorPolynomial	factorSquareFreePolynomial
floor	fractionPart	gcd
gcdPolynomial	hash	init
inv	latex	lcm
map	max	min
multiEuclidean	negative?	nextItem
numer	numerator	one?
patternMatch	positive?	prime?
principalIdeal	random	recip
reducedSystem	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
zero?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?.?
?quo?	?rem?	

— domain DECIMAL DecimalExpansion —

```
)abbrev domain DECIMAL DecimalExpansion
++ Author: Stephen M. Watt
++ Date Created: October, 1986
++ Date Last Updated: May 15, 1991
++ Basic Operations:
++ Related Domains: RadixExpansion
++ Also See:
++ AMS Classifications:
++ Keywords: radix, base, repeating decimal
++ Examples:
++ References:
++ Description:
++ This domain allows rational numbers to be presented as repeating
++ decimal expansions.

DecimalExpansion(): Exports == Implementation where
  Exports ==> QuotientFieldCategory(Integer) with
    coerce: % -> Fraction Integer
      ++ coerce(d) converts a decimal expansion to a rational number.
    coerce: % -> RadixExpansion(10)
      ++ coerce(d) converts a decimal expansion to a radix expansion
      ++ with base 10.
    fractionPart: % -> Fraction Integer
      ++ fractionPart(d) returns the fractional part of a decimal expansion.
    decimal: Fraction Integer -> %
      ++ decimal(r) converts a rational number to a decimal expansion.

  Implementation ==> RadixExpansion(10) add
    decimal r == r :: %
    coerce(x:%): RadixExpansion(10) == x pretend RadixExpansion(10)
```

———-

— DECIMAL.dotabb —

```
"DECIMAL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DECIMAL"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"DECIMAL" -> "PFECAT"
```

———-

5.4 Denavit-Hartenberg Matrices

5.4.1 Homogeneous Transformations

The study of robot manipulation is concerned with the relationship between objects, and between objects and manipulators. In this chapter we will develop the representation necessary to describe these relationships. Similar problems of representation have already been solved in the field of computer graphics, where the relationship between objects must also be described. Homogeneous transformations are used in this field and in computer vision [Duda] [Robserts63] [Roberts65]. These transformations were employed by Denavit to describe linkages [Denavit] and are now used to describe manipulators [Pieper] [Paul72] [Paul77b].

We will first establish notation for vectors and planes and then introduce transformations on them. These transformations consist primarily of translation and rotation. We will then show that these transformations can also be considered as coordinate frames in which to represent objects, including the manipulator. The inverse transformation will then be introduced. A later section describes the general rotation transformation representing a rotation about a vector. An algorithm is then described to find the equivalent axis and angle of rotations represented by any given transformation. A brief section on stretching and scaling transforms is included together with a section on the perspective transformation. The chapter concludes with a section on transformation equations.

5.4.2 Notation

In describing the relationship between objects we will make use of point vectors, planes, and coordinate frames. Point vectors are denoted by lower case, bold face characters. Planes are denoted by script characters, and coordinate frames by upper case, bold face characters. For example:

vectors	$\mathbf{v}$, $\mathbf{x1}$, $\mathbf{x}$
planes	$\mathcal{P}$, $\mathcal{Q}$
coordinate frames	$\mathbf{I}$, $\mathbf{A}$, $\mathbf{CONV}$

We will use point vectors, planes, and coordinate frames as variables which have associated values. For example, a point vector has as value its three Cartesian coordinate components.

If we wish to describe a point in space, which we will call p, with respect to a coordinate frame $\mathbf{E}$, we will use a vector which we will call $\mathbf{v}$. We will write this as

$$^{E}\mathbf{v}$$

The leading superscript describes the defining coordinate frame.

We might also wish to describe this same point, p, with respect to a different coordinate frame, for example $\mathbf{H}$, using a vector $\mathbf{w}$ as

$$^{H}\mathbf{w}$$

v and **w** are two vectors which probably have different component values and $\mathbf{v} \neq \mathbf{w}$ even though both vectors describe the same point p. The case might also exist of a vector **a** describing a point 3 inches above any frame

$$^{F^1}\mathbf{a} \qquad ^{F^2}\mathbf{a}$$

In this case the vectors are identical but describe different points. Frequently, the defining frame will be obvious from the text and the superscripts will be left off. In many cases the name of the vector will be the same as the name of the object described, for example, the tip of a pin might be described by a vector **tip** with respect to a frame **BASE** as

$$^{BASE}\mathbf{tip}$$

If it were obvious from the text that we were describing the vector with respect to **BASE** then we might simply write

$$\mathbf{tip}$$

If we also wish to describe this point with respect to another coordinate frame say, **HAND**, then we must use another vector to describe this relationship, for example

$$^{HAND}\mathbf{tv}$$

$^{HAND}\mathbf{tv}$ and **tip** both describe the same feature but have different values. In order to refer to individual components of coordinate frames, point vectors, or planes, we add subscripts to indicate the particular component. For example, the vector $^{HAND}\mathbf{tv}$ has components $^{HAND}\mathbf{tv_x}$, $^{HAND}\mathbf{tv_y}$, $^{HAND}\mathbf{tv_z}$.

5.4.3 Vectors

The homogeneous coordinate representation of objects in n-space is an $(n+1)$-space entity such that a particular perspective projection recreates the n-space. This can also be viewed as the addition of an extra coordinate to each vector, a scale factor, such that the vector has the same meaning if each component, including the scale factor, is multiplied by a constant.

A point vector

$$\mathbf{v} = a\mathbf{i} + b\mathbf{j} + c\mathbf{k} \tag{1.1}$$

where **i**, **j**, and **k** are unit vectors along the x, y, and z coordinate axes, respectively, is represented in homogeneous coordinates as a column matrix

$$\mathbf{v} = \begin{bmatrix} \mathbf{x} \\ \mathbf{y} \\ \mathbf{z} \\ \mathbf{w} \end{bmatrix} \tag{1.2}$$

where

$$\begin{aligned} \mathbf{a} &= \mathbf{x}/\mathbf{w} \\ \mathbf{b} &= \mathbf{y}/\mathbf{w} \\ \mathbf{c} &= \mathbf{z}/\mathbf{w} \end{aligned} \tag{1.3}$$

Thus the vector $3\mathbf{i} + 4\mathbf{j} + 5\mathbf{k}$ can be represented as $[3, 4, 5, 1]^{\mathrm{T}}$ or as $[6, 8, 10, 2]^{\mathrm{T}}$ or again as $[-30, -40, -50, -10]^{\mathrm{T}}$, etc. The superscript T indicates the transpose of the row vector into a column vector. The vector at the origin, the null vector, is represented as $[0, 0, 0, n]^{\mathrm{T}}$ where n is any non-zero scale factor. The vector $[0, 0, 0, 0]^{\mathrm{T}}$ is undefined. Vectors of the form $[a, b, c, 0]^{\mathrm{T}}$ represent vectors at infinity and are used to represent directions; the addition of any other finite vector does not change their value in any way.

We will also make use of the vector dot and cross products. Given two vectors

$$\begin{aligned} \mathbf{a} &= a_x\mathbf{i} + a_y\mathbf{j} + a_z\mathbf{k} \\ \mathbf{b} &= b_x\mathbf{i} + b_y\mathbf{j} + b_z\mathbf{k} \end{aligned} \tag{1.4}$$

we define the vector dot product, indicated by "$\cdot$" as

$$\mathbf{a} \cdot \mathbf{b} = a_x b_x + a_y b_y + a_z b_z \tag{1.5}$$

The dot product of two vectors is a scalar. The cross product, indicated by an "$\times$", is another vector perpendicular to the plane formed by the vectors of the product and is defined by

$$\mathbf{a} \times \mathbf{b} = (a_y b_z - a_z b_y)\mathbf{i} + (a_z b_x - a_x b_z)\mathbf{j} + (a_x b_y - a_y b_x)\mathbf{k} \tag{1.6}$$

This definition is easily remembered as the expansion of the determinant

$$\mathbf{a} \times \mathbf{b} = \begin{vmatrix} \mathbf{i} & \mathbf{j} & \mathbf{k} \\ a_x & a_y & a_z \\ b_x & b_y & b_z \end{vmatrix} \tag{1.7}$$

5.4.4 Planes

A plane is represented as a row matrix

$$\mathcal{P} = [a, b, c, d] \tag{1.8}$$

such that if a point $\mathbf{v}$ lies in a plane $\mathcal{P}$ the matrix product

$$\mathcal{P}\ \mathbf{v} = 0 \tag{1.9}$$

or in expanded form

$$xa + yb + zc + wd = 0 \tag{1.10}$$

If we define a constant

$$m = +\sqrt{a^2 + b^2 + c^2} \tag{1.11}$$

and divide Equation 1.10 by wm we obtain

$$\frac{x}{w}\frac{a}{m} + \frac{y}{w}\frac{b}{m} + \frac{z}{w}\frac{c}{m} = -\frac{d}{m} \tag{1.12}$$

The left hand side of Equation 1.12 is the vector dot product of two vectors $(x/w)\mathbf{i} + (y/w)\mathbf{j} + (z/w)\mathbf{k}$ and $(a/m)\mathbf{i} + (b/m)\mathbf{j} + (c/m)\mathbf{k}$ and represents the directed distance of the point $(x/w)\mathbf{i} + (y/w)\mathbf{j} + (z/w)\mathbf{k}$ along the vector
$(a/m)\mathbf{i} + (b/m)\mathbf{j} + (c/m)\mathbf{k}$. The vector $(a/m)\mathbf{i} + (b/m)\mathbf{j} + (c/m)\mathbf{k}$ can be interpreted as the outward pointing normal of a plane situated a distance $-d/m$ from the origin in the direction of the normal. Thus a plane $\mathcal{P}$ parallel to the x,y plane, one unit along the z axis, is represented as

$$\mathcal{P} = [0, 0, 1, -1] \tag{1.13}$$

$$\text{or as} \quad \mathcal{P} = [0, 0, 2, -2] \tag{1.14}$$

$$\text{or as} \quad \mathcal{P} = [0, 0, -100, 100] \tag{1.15}$$

A point $\mathbf{v} = [10, 20, 1, 1]$ should lie in this plane

$$[0, 0, -100, 100] \begin{bmatrix} 10 \\ 20 \\ 1 \\ 1 \end{bmatrix} = 0 \tag{1.16}$$

or

$$[0, 0, 1, -1] \begin{bmatrix} -5 \\ -10 \\ -.5 \\ -.5 \end{bmatrix} = 0 \tag{1.17}$$

The point $\mathbf{v} = [0, 0, 2, 1]$ lies above the plane

$$[0, 0, 2, -2] \begin{bmatrix} 0 \\ 0 \\ 2 \\ 1 \end{bmatrix} = 2 \tag{1.18}$$

and $\mathcal{P}$ **v** is indeed positive, indicating that the point is outside the plane in the direction of the outward pointing normal. A point $\mathbf{v} = [0, 0, 0, 1]$ lies below the plane

$$[0, 0, 1, -1] \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix} = -1 \tag{1.19}$$

The plane $[0, 0, 0, 0]$ is undefined.

5.4.5 Transformations

A transformation of the space **H** is a 4x4 matrix and can represent translation, rotation, stretching, and perspective transformations. Given a point **u**, its transformation **v** is represented by the matrix product

$$\mathbf{v} = \mathbf{H}\mathbf{u} \tag{1.20}$$

The corresponding plane transformation $\mathcal{P}$ to $\mathcal{Q}$ is

$$\mathcal{Q}{=}\mathcal{P}\ \mathbf{H^{-1}} \tag{1.21}$$

as we requre that the condition

$$\mathcal{Q}\ \mathbf{v} = \mathcal{P}\ \mathbf{u} \tag{1.22}$$

is invariant under all transformations. To verify this we substitute from Equations 1.20 and 1.21 into the left hand side of 1.22 and we obtain on the right hand side $\mathbf{H^{-1}H}$ which is the identity matrix **I**

$$\mathcal{P}\ \mathbf{H^{-1}H}\mathbf{u} = \mathcal{P}\ \mathbf{u} \tag{1.23}$$

5.4.6 Translation Transformation

The transformation **H** corresponding to a translation by a vector $a\mathbf{i} + b\mathbf{j} + c\mathbf{k}$ is

$$\mathbf{H} = \mathbf{Trans}(\mathbf{a}, \mathbf{b}, \mathbf{c}) = \begin{bmatrix} 1 & 0 & 0 & a \\ 0 & 1 & 0 & b \\ 0 & 0 & 1 & c \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.24}$$

Given a vector $\mathbf{u} = [x, y, z, w]^{\mathrm{T}}$ the transformed vector **v** is given by

$$\mathbf{H} = \mathbf{Trans}(\mathbf{a}, \mathbf{b}, \mathbf{c}) = \begin{bmatrix} 1 & 0 & 0 & a \\ 0 & 1 & 0 & b \\ 0 & 0 & 1 & c \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ w \end{bmatrix} \tag{1.25}$$

$$\mathbf{v} = \begin{bmatrix} x + aw \\ y + bw \\ z + cw \\ w \end{bmatrix} = \begin{bmatrix} x/w + a \\ y/w + b \\ z/w + c \\ 1 \end{bmatrix} \tag{1.26}$$

The translation may also be interpreted as the addition of the two vectors $(x/w)\mathbf{i} + (y/w)\mathbf{j} + (z/w)\mathbf{k}$ and $a\mathbf{i} + b\mathbf{j} + c\mathbf{k}$.

Every element of a transformation matrix may be multiplied by a non-zero constant without changing the transformation, in the same manner as points and planes. Consider the vector $2\mathbf{i} + 3\mathbf{j} + 2\mathbf{k}$ translated by, or added to
$4\mathbf{i}$ - $3\mathbf{j}$ + $7\mathbf{k}$

$$\begin{bmatrix} 6 \\ 0 \\ 9 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 & 4 \\ 0 & 1 & 0 & -3 \\ 0 & 0 & 1 & 7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 2 \\ 3 \\ 2 \\ 1 \end{bmatrix} \tag{1.27}$$

If we multiply the transmation matrix elements by, say, -5, and the vector elements by 2, we obtain

$$\begin{bmatrix} -60 \\ 0 \\ -90 \\ -10 \end{bmatrix} = \begin{bmatrix} -5 & 0 & 0 & -20 \\ 0 & -5 & 0 & 15 \\ 0 & 0 & -5 & -35 \\ 0 & 0 & 0 & -5 \end{bmatrix} \begin{bmatrix} 4 \\ 6 \\ 4 \\ 2 \end{bmatrix} \tag{1.28}$$

which corresponds to the vector $[6, 0, 9, 1]^{\mathrm{T}}$ as before. The point $[2, 3, 2, 1]$ lies in the plane $[1, 0, 0, -2]$

$$[1, 0, 0, -2] \begin{bmatrix} 2 \\ 3 \\ 2 \\ 1 \end{bmatrix} = 0 \tag{1.29}$$

The transformed point is, as we have already found, $[6, 0, 9, 1]^{\mathrm{T}}$. We will now compute the transformed plane. The inverse of the transform is

$$\begin{bmatrix} 1 & 0 & 0 & -4 \\ 0 & 1 & 0 & 3 \\ 0 & 0 & 1 & -7 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

and the transformed plane

$$[1\ 0\ 0\ -6] = [1\ 0\ 0\ -2] \begin{bmatrix} 1 & 0 & 0 & -4 \\ 0 & 1 & 0 & 3 \\ 0 & 0 & 1 & -7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.30}$$

Once again the transformed point lies in the transformed plane

$$[1\ 0\ 0\ -6] \begin{bmatrix} 6 \\ 0 \\ 9 \\ 1 \end{bmatrix} = 0 \tag{1.31}$$

The general translation operation can be represented in Axiom as

— **translate** —

```
translate(x,y,z) ==
 matrix(_
  [[1,0,0,x],_
   [0,1,0,y],_
   [0,0,1,z],_
   [0,0,0,1]])
```

———-

5.4.7 Rotation Transformations

The transformations corresponding to rotations about the x, y, and z axes by an angle θ are

$$\mathbf{Rot}(\mathbf{x}, \theta) = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & cos\ \theta & -sin\ \theta & 0 \\ 0 & sin\ \theta & cos\ \theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.32}$$

Rotations can be described in Axiom as functions that return matrices. We can define a function for each of the rotation matrices that correspond to the rotations about each axis. Note that the sine and cosine functions in Axiom expect their argument to be in radians rather than degrees. This conversion is

$$radians = \frac{degrees * \pi}{180}$$

The Axiom code for $\mathbf{Rot}(\mathbf{x}, \mathbf{degree})$ is

— **rotatex** —

```
rotatex(degree) ==
 angle := degree * pi() / 180::R
 cosAngle := cos(angle)
 sinAngle := sin(angle)
 matrix(_
  [[1,     0,           0,      0], _
   [0, cosAngle, -sinAngle, 0], _
   [0, sinAngle,  cosAngle, 0], _
   [0,     0,           0,      1]])
```

———-

$$\mathbf{Rot}(\mathbf{y},\theta) = \begin{bmatrix} cos\ \theta & 0 & sin\ \theta & 0 \\ 0 & 1 & 0 & 0 \\ -sin\ \theta & 0 & cos\ \theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.33}$$

The Axiom code for $\mathbf{Rot}(\mathbf{y},\mathbf{degree})$ is

— **rotatey** —

```
rotatey(degree) ==
 angle := degree * pi() / 180::R
 cosAngle := cos(angle)
 sinAngle := sin(angle)
 matrix(_
  [[ cosAngle, 0, sinAngle, 0], _
   [    0,       1,     0,      0], _
   [-sinAngle, 0, cosAngle, 0], _
   [    0,       0,     0,      1]])
```

———-

$$\mathbf{Rot}(\mathbf{z},\theta) = \begin{bmatrix} cos\ \theta & -sin\ \theta & 0 & 0 \\ sin\ \theta & cos\ \theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.34}$$

And the Axiom code for $\mathbf{Rot}(\mathbf{z},\mathbf{degree})$ is

— **rotatez** —

```
rotatez(degree) ==
 angle := degree * pi() / 180::R
 cosAngle := cos(angle)
 sinAngle := sin(angle)
 matrix(_
```

```
[[cosAngle, -sinAngle, 0, 0], _
 [sinAngle,  cosAngle, 0, 0], _
 [   0,           0,       1, 0], _
 [   0,           0,       0, 1]])
```

Let us interpret these rotations by means of an example. Given a point $\mathbf{u} = 7\mathbf{i} + 3\mathbf{j} + 2\mathbf{k}$ what is the effect of rotating it 90° about the $\mathbf{z}$ axis to $\mathbf{v}$? The transform is obtained from Equation 1.34 with $sin\ \theta = 1$ and $cos\ \theta = 0$.

$$\begin{bmatrix} -3 \\ 7 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & -1 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 7 \\ 3 \\ 2 \\ 1 \end{bmatrix} \tag{1.35}$$

Let us now rotate $\mathbf{v}$ 90° about the y axis to $\mathbf{w}$. The transform is obtained from Equation 1.33 and we have

$$\begin{bmatrix} 2 \\ 7 \\ 3 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} -3 \\ 7 \\ 2 \\ 1 \end{bmatrix} \tag{1.36}$$

If we combine these two rotations we have

$$\mathbf{v} = \mathbf{Rot}(\mathbf{z}, \mathbf{90})\mathbf{u} \tag{1.37}$$

$$\text{and} \quad \mathbf{w} = \mathbf{Rot}(\mathbf{y}, \mathbf{90})\mathbf{v} \tag{1.38}$$

Substituting for $\mathbf{v}$ from Equation 1.37 into Equation 1.38 we obtain

$$\mathbf{w} = \mathbf{Rot}(\mathbf{y}, \mathbf{90})\ \mathbf{Rot}(\mathbf{z}, \mathbf{90})\ \mathbf{u} \tag{1.39}$$

$$\mathbf{Rot}(\mathbf{y}, \mathbf{90})\ \mathbf{Rot}(\mathbf{z}, \mathbf{90}) = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 & -1 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.40}$$

$$\mathbf{Rot}(\mathbf{y}, \mathbf{90})\ \mathbf{Rot}(\mathbf{z}, \mathbf{90}) = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.41}$$

thus

$$\mathbf{w} = \begin{bmatrix} 2 \\ 7 \\ 3 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 7 \\ 3 \\ 2 \\ 1 \end{bmatrix} \tag{1.42}$$

as we obtained before.

If we reverse the order of rotations and first rotate 90° about the y axis and then 90° about the z axis, we obtain a different position

$$\mathbf{Rot}(\mathbf{z}, \mathbf{90})\mathbf{Rot}(\mathbf{y}, \mathbf{90}) = \begin{bmatrix} 0 & -1 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 0 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.43}$$

and the point $\mathbf{u}$ transforms into $\mathbf{w}$ as

$$\begin{bmatrix} -3 \\ 2 \\ -7 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 7 \\ 3 \\ 2 \\ 1 \end{bmatrix} \tag{1.44}$$

We should expect this, as matrix multiplication is noncommutative.

$$\mathbf{AB} \neq \mathbf{BA} \tag{1.45}$$

We will now combine the original rotation with a translation $4\mathbf{i} - 3\mathbf{j} + 7\mathbf{k}$. We obtain the translation from Equation 1.27 and the rotation from Equation 1.41. The matrix expression is

$$\mathbf{Trans}(\mathbf{4}, \mathbf{-3}, \mathbf{7})\mathbf{Rot}(\mathbf{y}, \mathbf{90})\mathbf{Rot}(\mathbf{z}, \mathbf{90}) = \begin{bmatrix} 1 & 0 & 0 & 4 \\ 0 & 1 & 0 & -3 \\ 0 & 0 & 1 & 7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & -3 \\ 0 & 1 & 0 & 7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.46}$$

and our point $\mathbf{w} = 7\mathbf{i} + 3\mathbf{j} + 2\mathbf{k}$ transforms into $\mathbf{x}$ as

$$\begin{bmatrix} 6 \\ 4 \\ 10 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & -3 \\ 0 & 1 & 0 & 7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 7 \\ 3 \\ 2 \\ 1 \end{bmatrix} \tag{1.47}$$

5.4.8 Coordinate Frames

We can interpret the elements of the homogeneous transformation as four vectors describing a second coordinate frame. The vector $[0,0,0,1]^{\mathrm{T}}$ lies at the origin of the second coordinate frame. Its transformation corresponds to the right hand column of the transformation matrix. Consider the transform in Equation 1.47

$$\begin{bmatrix} 4 \\ -3 \\ 7 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & -3 \\ 0 & 1 & 0 & 7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix} \tag{1.48}$$

The transform of the null vector is $[4,-3,7,1]^{\mathrm{T}}$, the right hand column. If we transform vectors corresponding to unit vectors along the x, y, and z axes, we obtain $[4,-2,7,1]^{\mathrm{T}}$, $[4,-3,8,1]^{\mathrm{T}}$, and $[5,-3,7,1]^{\mathrm{T}}$, respectively. Those four vectors form a coordinate frame.

The direction of these unit vectors is formed by subtracting the vector representing the origin of this coordinate frame and extending the vectors to infinity by reducing their scale factors to zero. The direction of the x, y, and z axes of this frame are $[0,1,0,0]^{\mathrm{T}}$, $[0,0,1,0]^{\mathrm{T}}$, and $[1,0,0,0]^{\mathrm{T}}$, respectively. These direction vectors correspond to the first three columns of the transformation matrix. The transformation matrix thus describes the three axis directions and the position of the origin of a coordinate frame rotated and translated away from the reference coordinate frame. When a vector is transformed, as in Equation 1.47, the original vector can be considered as a vector described in the coordinate frame. The transformed vector is the same vector described with respect to the reference coordinate frame.

5.4.9 Relative Transformations

The rotations and translations we have been describing have all been made with respect to the fixed reference coordinate frame. Thus, in the example given,

$$\mathbf{Trans}(\mathbf{4},\mathbf{-3},\mathbf{7})\mathbf{Rot}(\mathbf{y},\mathbf{90})\mathbf{Rot}(\mathbf{z},\mathbf{90}) = \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & -3 \\ 0 & 1 & 0 & 7 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.49}$$

the frame is first rotated around the reference z axis by 90°, then rotated 90° around the reference y axis, and finally translated by $4\mathbf{i}-3\mathbf{j}+7\mathbf{k}$. We may also interpret the operation in the reverse order, from left to right, as follows: the object is first translated by $4\mathbf{i}-3\mathbf{j}+7\mathbf{k}$; it is then rotated 90° around the current frames axes, which in this case are the same as the reference axes; it is then rotated 90° about the newly rotated (current) frames axes.

In general, if we postmultiply a transform representing a frame by a second transformation describing a rotation and/or translation, we make that translation and/or rotation with respect to the frame axes described by the first transformation. If we premultiply the frame transformation by a transformation representing a translation and/or rotation, then that translation and/or rotation is made with respect to the base reference coordinate frame.

Thus, given a frame $\mathbf{C}$ and a transformation $\mathbf{T}$, corresponding to a rotation of 90° about the z axis, and a translation of 10 units in the x direction, we obtain a new position $\mathbf{X}$ when the change is made in the base coordinates $\mathbf{X} = \mathbf{TC}$

$$\begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 20 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 0 & -1 & 0 & 10 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 & 20 \\ 0 & 0 & -1 & 10 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.50}$$

and a new position $\mathbf{Y}$ when the change is made relative to the frame axes as $\mathbf{Y} = \mathbf{CT}$

$$\begin{bmatrix} 0 & -1 & 0 & 30 \\ 0 & 0 & -1 & 10 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 & 20 \\ 0 & 0 & -1 & 10 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 & -1 & 0 & 10 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.51}$$

5.4.10 Objects

Transformations are used to describe the position and orientation of objects. An object is described by six points with respect to a coordinate frame fixed in the object.

If we rotate the object 90° about the z axis and then 90° about the y axis, followed by a translation of four units in the x direction, we can describe the transformation as

$$\mathbf{Trans}(\mathbf{4},\mathbf{0},\mathbf{0})\mathbf{Rot}(\mathbf{y},\mathbf{90})\mathbf{Rot}(\mathbf{z},\mathbf{90}) = \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.52}$$

The transformation matrix represents the operation of rotation and translation on a coordinate frame originally aligned with the reference coordinate frame. We may transform the six points of the object as

$$\begin{bmatrix} 4 & 4 & 6 & 6 & 4 & 4 \\ 1 & -1 & -1 & 1 & 1 & -1 \\ 0 & 0 & 0 & 0 & 4 & 4 \\ 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & -1 & -1 & 1 & 1 & -1 \\ 0 & 0 & 0 & 0 & 4 & 4 \\ 0 & 0 & 2 & 2 & 0 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix} \tag{1.53}$$

It can be seen that the object described bears the same fixed relationship to its coordinate frame, whose position and orientation are described by the transformation. Given an object described by a reference coordinate frame, and a transformation representing the position and orientation of the object's axes, the object can be simply reconstructed, without the necessity of transforming all the points, by noting the direction and orientation of key features with respect to the describing frame's coordinate axes. By drawing the transformed coordinate frame, the object can be related to the new axis directions.

5.4.11 Inverse Transformations

We are now in a position to develop the inverse transformation as the transform which carries the transformed coordinate frame back to the original frame. This is simply the description of the reference coordinate frame with respect to the transformed frame. Suppose the direction of the reference frame x axis is $[0,0,1,0]^{\mathrm{T}}$ with respect to the transformed frame. The y and z axes are $[1,0,0,0]^{\mathrm{T}}$ and $[0,1,0,0]^{\mathrm{T}}$, respectively. The location of the origin is $[0,0,-4,1]^{\mathrm{T}}$ with respect to the transformed frame and thus the inverse transformation is

$$\mathbf{T^{-1}} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & -4 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.54}$$

That this is indeed the tranform inverse is easily verifyed by multiplying it by the transform $\mathbf{T}$ to obtain the identity transform

$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & -4 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 & 0 & 1 & 4 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.55}$$

In general, given a transform with elements

$$\mathbf{T} = \begin{bmatrix} n_x & o_x & a_x & p_x \\ n_y & o_y & a_y & p_y \\ n_z & o_z & a_z & p_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.56}$$

then the inverse is

$$\mathbf{T^{-1}} = \begin{bmatrix} n_x & n_y & n_z & -\mathbf{p}\cdot\mathbf{n} \\ o_x & o_y & o_z & -\mathbf{p}\cdot\mathbf{o} \\ a_x & a_y & a_z & -\mathbf{p}\cdot\mathbf{a} \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.57}$$

where $\mathbf{p}$, $\mathbf{n}$, $\mathbf{o}$, and $\mathbf{a}$ are the four column vectors and "$\cdot$" represents the vector dot product. This result is easily verified by postmultiplying Equation 1.56 by Equation 1.57.

5.4.12 General Rotation Transformation

We state the rotation transformations for rotations about the x, y, and z axes (Equations 1.32, 1.33 and 1.34). These transformations have a simple geometric interpretation. For example, in the case of a rotation about the z axis, the column representing the z axis will remain constant, while the column elements representing the x and y axes will vary.

We will now develop the transformation matrix representing a rotation around an arbitrary vector **k** located at the origin. In order to do this we will imagine that **k** is the z axis unit vector of a coordinate frame **C**

$$\mathbf{C} = \begin{bmatrix} n_x & o_x & a_x & p_x \\ n_y & o_y & a_y & p_y \\ n_z & o_z & a_z & p_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.58}$$

$$\mathbf{k} = a_x\mathbf{i} + a_y\mathbf{j} + a_z\mathbf{k} \tag{1.59}$$

Rotating around the vector **k** is then equivalent to rotating around the z axis of the frame **C**.

$$\mathbf{Rot}(\mathbf{k}, \theta) = \mathbf{Rot}({}^{\mathbf{C}}\mathbf{z}, \theta) \tag{1.60}$$

If we are given a frame **T** described with respect to the reference coordinate frame, we can find a frame **X** which describes the same frame with respect to frame **C** as

$$\mathbf{T} = \mathbf{CX} \tag{1.61}$$

where **X** describes the position of **T** with respect to frame **C**. Solving for **X** we obtain

$$\mathbf{X} = \mathbf{C^{-1}T} \tag{1.62}$$

Rotation **T** around **k** is equivalent to rotating **X** around the z axis of frame **C**

$$\mathbf{Rot}(\mathbf{k}, \theta)\mathbf{T} = \mathbf{CRot}(\mathbf{z}, \theta)\mathbf{X} \tag{1.63}$$

$$\mathbf{Rot}(\mathbf{k}, \theta)\mathbf{T} = \mathbf{CRot}(\mathbf{z}, \theta)\mathbf{C^{-1}T}. \tag{1.64}$$

Thus

$$\mathbf{Rot}(\mathbf{k}, \theta) = \mathbf{CRot}(\mathbf{z}, \theta)\mathbf{C^{-1}} \tag{1.65}$$

However, we have only **k**, the z axis of the frame **C**. By expanding equation 1.65 we will discover that $\mathbf{CRot}(\mathbf{z}, \theta)\mathbf{C^{-1}}$ is a function of **k** only.

Multiplying $\mathbf{Rot}(\mathbf{z}, \theta)$ on the right by $\mathbf{C^{-1}}$ we obtain

$$\mathbf{Rot}(\mathbf{z}, \theta)\mathbf{C^{-1}} = \begin{bmatrix} cos\theta & -sin\theta & 0 & 0 \\ sin\theta & cos\theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} n_x & n_y & n_z & 0 \\ o_x & o_x & o_z & 0 \\ a_x & a_y & a_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$= \begin{bmatrix} n_x cos\theta - o_x sin\theta & n_y cos\theta - o_y sin\theta & n_z cos\theta - o_z sin\theta & 0 \\ n_x sin\theta + o_x cos\theta & n_y sin\theta + o_y cos\theta & n_z sin\theta + o_z cos\theta & 0 \\ a_x & a_y & a_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.66}$$

premultiplying by

$$\mathbf{C} = \begin{bmatrix} n_x & o_x & a_x & 0 \\ n_y & o_y & a_y & 0 \\ n_z & o_z & a_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.67}$$

we obtain $\mathbf{CRot(z}, \theta)\mathbf{C^{-1}}$

$$\begin{bmatrix} n_x n_x cos\theta - n_x o_x sin\theta + n_x o_x sin\theta + o_x o_x cos\theta + a_x a_x \\ n_y n_x cos\theta - n_y o_x sin\theta + n_x o_y sin\theta + o_x o_y cos\theta + a_y a_x \\ n_z n_x cos\theta - n_z o_x sin\theta + n_x o_z sin\theta + o_x o_z cos\theta + a_z a_x \\ 0 \end{bmatrix}$$

$$\begin{matrix} n_x n_y cos\theta - n_x o_y sin\theta + n_y o_x sin\theta + o_y o_x cos\theta + a_x a_y \\ n_y n_y cos\theta - n_y o_y sin\theta + n_y o_y sin\theta + o_y o_y cos\theta + a_y a_y \\ n_z n_y cos\theta - n_z o_y sin\theta + n_y o_z sin\theta + o_y o_z cos\theta + a_z a_y \\ 0 \end{matrix} \tag{1.68}$$

$$\begin{bmatrix} n_x n_z cos\theta - n_x o_z sin\theta + n_z o_x sin\theta + o_z o_x cos\theta + a_x a_x & 0 \\ n_y n_z cos\theta - n_y o_z sin\theta + n_z o_y sin\theta + o_z o_y cos\theta + a_y a_z & 0 \\ n_z n_z cos\theta - n_z o_z sin\theta + n_z o_z sin\theta + o_z o_z cos\theta + a_z a_z & 0 \\ 0 & 1 \end{bmatrix}$$

Simplifying, using the following relationships:
the dot product of any row or column of $\mathbf{C}$ with any other row or column is zero, as the vectors are orthogonal;
the dot product of any row or column of $\mathbf{C}$ with itself is $\mathbf{1}$ as the vectors are of unit magnitude;
the z unit vector is the vector cross product of the x and y vectors or

$$\mathbf{a} = \mathbf{n} \times \mathbf{o} \tag{1.69}$$

which has components

$$a_x = n_y o_z - n_z o_y$$

$$a_y = n_z o_x - n_x o_z$$

$$a_z = n_x o_y - n_y o_x$$

the versine, abbreviated **vers** θ, is defined as **vers** $\theta = (1 - cos\ \theta)$, $k_x = a_x$, $k_y = a_y$ and $k_z = a_z$. We obtain $\mathbf{Rot}(\mathbf{k}, \theta) =$

$$\begin{bmatrix} k_x k_x vers\theta + cos\theta & k_y k_x vers\theta - k_z sin\theta & k_z k_x vers\theta + k_y sin\theta & 0 \\ k_x k_y vers\theta + k_z sin\theta & k_y k_y vers\theta + cos\theta & k_z k_y vers\theta - k_x sin\theta & 0 \\ k_x k_z vers\theta - k_y sin\theta & k_y k_z vers\theta + k_x sin\theta & k_z k_z vers\theta + cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.70}$$

This is an important result and should be thoroughly understood before proceeding further.

From this general rotation transformation we can obtain each of the elementary rotation transforms. For example $\mathbf{Rot}(\mathbf{x}, \theta)$ is $\mathbf{Rot}(\mathbf{k}, \theta)$ where $k_x = 1$, $k_y = 0$, and $k_z = 0$. Substituting these values of $\mathbf{k}$ into Equation 1.70 we obtain

$$\mathbf{Rot}(\mathbf{x}, \theta) = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & cos\theta & -sin\theta & 0 \\ 0 & sin\theta & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.71}$$

as before.

5.4.13 Equivalent Angle and Axis of Rotation

Given any arbitrary rotational transformation, we can use Equation 1.70 to obtain an axis about which an equivalent rotation θ is made as follows. Given a rotational transformation $\mathbf{R}$

$$\mathbf{R} = \begin{bmatrix} n_x & o_x & a_x & 0 \\ n_y & o_y & a_y & 0 \\ n_z & o_z & a_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.72}$$

we may equate $\mathbf{R}$ to $\mathbf{Rot(k,}\theta\mathbf{)}$

$$\begin{bmatrix} n_x & o_x & a_x & 0 \\ n_y & o_y & a_y & 0 \\ n_z & o_z & a_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} =$$

$$\begin{bmatrix} k_x k_x vers\theta + cos\theta & k_y k_x vers\theta - k_z sin\theta & k_z k_x vers\theta + k_y sin\theta & 0 \\ k_x k_y vers\theta + k_z sin\theta & k_y k_y vers\theta + cos\theta & k_z k_y vers\theta - k_x sin\theta & 0 \\ k_x k_z vers\theta - k_y sin\theta & k_y k_z vers\theta + k_x sin\theta & k_z k_z vers\theta + cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.73}$$

Summing the diagonal terms of Equation 1.73 we obtain

$$n_x + o_y + a_z + 1 = k_x^2 vers\theta + cos\theta + k_y^2 vers\theta + cos\theta + k_z^2 vers\theta + cos\theta + 1 \tag{1.74}$$

$$\begin{aligned} n_x + o_y + a_z &= (k_x^2 + k_y^2 + k_z^2)vers\theta + 3cos\theta \\ &= 1 + 2cos\theta \end{aligned} \tag{1.75}$$

and the cosine of the angle of rotation is

$$cos\theta = \frac{1}{2}(n_x + o_y + a_z - 1) \tag{1.76}$$

Differencing pairs of off-diagonal terms in Equation 1.73 we obtain

$$o_z - a_y = 2k_x sin\theta \tag{1.77}$$

$$a_x - n_z = 2k_y sin\theta \tag{1.78}$$

$$n_y - o_x = 2k_z sin\theta \tag{1.79}$$

Squaring and adding Equations 1.77-1.79 we obtain an expression for $sin\theta$

$$(o_z - a_y)^2 + (a_x - n_z)^2 + (n_y - o_x)^2 = 4sin^2\theta \tag{1.80}$$

and the sine of the angle of rotation is

$$sin\ \theta = \pm\frac{1}{2}\sqrt{(o_z - a_y)^2 + (a_x - n_z)^2 + (n_y - o_x)^2} \tag{1.81}$$

We may define the rotation to be positive about the vector $\mathbf{k}$ such that $0 \leq \theta \leq 180°$. In this case the + sign is appropriate in Equation 1.81 and thus the angle of rotation θ is uniquely defined as

$$tan\ \theta = \frac{\sqrt{(o_z - a_y)^2 + (a_x - n_z)^2 + (n_y - o_x)^2}}{(n_x + o_y + a_z - 1)} \tag{1.82}$$

The components of $\mathbf{k}$ may be obtained from Equations 1.77-1.79 as

$$k_x = \frac{o_z - a_y}{2sin\theta} \tag{1.83}$$

$$k_y = \frac{a_x - n_z}{2sin\theta} \tag{1.84}$$

$$k_z = \frac{n_y - o_x}{2sin\theta} \tag{1.85}$$

When the angle of rotation is very small, the axis of rotation is physically not well defined due to the small magnitude of both numerator and denominator in Equations 1.83-1.85. If the resulting angle is small, the vector $\mathbf{k}$ should be renormalized to ensure that $|\mathbf{k}| = 1$. When the angle of rotation approaches 180° the vector $\mathbf{k}$ is once again poorly defined by Equation 1.83-1.85 as the magnitude of the sine is again decreasing. The axis of rotation is, however, physically well defined in this case. When $\theta < 150°$, the denominator of Equations

1.83-1.85 is less than 1. As the angle increases to 180° the rapidly decreasing magnitude of both numerator and denominator leads to considerable inaccuracies in the determination of **k**. At $\theta = 180°$, Equations 1.83-1.85 are of the form 0/0, yielding no information at all about a physically well defined vector **k**. If the angle of rotation is greater than 90°, then we must follow a different approach in determining **k**. Equating the diagonal elements of Equation 1.73 we obtain

$$k_x^2 vers\theta + cos\theta = n_x \tag{1.86}$$

$$k_y^2 vers\theta + cos\theta = o_y \tag{1.87}$$

$$k_z^2 vers\theta + cos\theta = a_z \tag{1.88}$$

Substituting for $cos\theta$ and $vers\theta$ from Equation 1.76 and solving for the elements of **k** we obtain further

$$k_x = \pm\sqrt{\frac{n_x - cos\theta}{1 - cos\theta}} \tag{1.89}$$

$$k_y = \pm\sqrt{\frac{o_y - cos\theta}{1 - cos\theta}} \tag{1.90}$$

$$k_z = \pm\sqrt{\frac{a_z - cos\theta}{1 - cos\theta}} \tag{1.91}$$

The largest component of **k** defined by Equations 1.89-1.91 corresponds to the most positive component of n_x, o_y, and a_z. For this largest element, the sign of the radical can be obtained from Equations 1.77-1.79. As the sine of the angle of rotation θ must be positive, then the sign of the component of **k** defined by Equations 1.77-1.79 must be the same as the sign of the left hand side of these equations. Thus we may combine Equations 1.89-1.91 with the information contained in Equations 1.77-1.79 as follows

$$k_x = sgn(o_z - a_y)\sqrt{\frac{(n_x - cos\theta)}{1 - cos\theta}} \tag{1.92}$$

$$k_y = sgn(a_x - n_z)\sqrt{\frac{(o_y - cos\theta)}{1 - cos\theta}} \tag{1.93}$$

$$k_z = sgn(n_y - o_x)\sqrt{\frac{(a_z - cos\theta)}{1 - cos\theta}} \tag{1.94}$$

where $sgn(e) = +1$ if $e \geq 0$ and $sgn(e) = -1$ if $e \leq 0$.

Only the largest element of **k** is determined from Equations 1.92-1.94, corresponding to the most positive element of n_x, o_y, and a_z. The remaining elements are more accurately determined by the following equations formed by summing pairs of off-diagonal elements of Equation 1.73

$$n_y + o_x = 2k_x k_y vers\theta \tag{1.95}$$

$$o_z + a_y = 2k_y k_z vers\theta \tag{1.96}$$

$$n_z + a_x = 2k_z k_x vers\theta \tag{1.97}$$

If k_x is largest then

$$k_y = \frac{n_y + o_x}{2k_x vers\theta} \quad \text{from Equation 1.95} \tag{1.98}$$

$$k_z = \frac{a_x + n_z}{2k_x vers\theta} \quad \text{from Equation 1.97} \tag{1.99}$$

If k_y is largest then

$$k_x = \frac{n_y + o_x}{2k_y vers\theta} \quad \text{from Equation 1.95} \tag{1.100}$$

$$k_z = \frac{o_z + a_y}{2k_y vers\theta} \quad \text{from Equation 1.96} \tag{1.101}$$

If k_z is largest then

$$k_x = \frac{a_x + n_z}{2k_z vers\theta} \quad \text{from Equation 1.97} \tag{1.102}$$

$$k_y = \frac{o_z + a_y}{2k_z vers\theta} \quad \text{from Equation 1.96} \tag{1.103}$$

5.4.14 Example 1.1

Determine the equivalent axis and angle of rotation for the matrix given in Equations 1.41

$$\mathbf{Rot(y, 90)Rot(z, 90)} = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.104}$$

We first determine **cos** θ from Equation 1.76

$$cos\theta = \frac{1}{2}(0 + 0 + 0 - 1) = -\frac{1}{2} \tag{1.105}$$

and $sin\ \theta$ from Equation 1.81

$$sin\theta = \frac{1}{2}\sqrt{(1-0)^2+(1-0)^2+(1-0)^2} = \frac{\sqrt{3}}{2} \tag{1.106}$$

Thus

$$\theta = tan^{-1}\left(\frac{\sqrt{3}}{2}\Big/\frac{-1}{2}\right) = 120^\circ \tag{1.107}$$

As $\theta > 90$, we determine the largest component of $\mathbf{k}$ corresponding to the largest element on the diagonal. As all diagonal elements are equal in this example we may pick any one. We will pick k_x given by Equation 1.92

$$k_x = +\sqrt{(0+\frac{1}{2})\Big/(1+\frac{1}{2})} = \frac{1}{\sqrt{3}} \tag{1.108}$$

As we have determined k_x we may now determine k_y and k_z from Equations 1.98 and 1.99, respectively

$$k_y = \frac{1+0}{\sqrt{3}} = \frac{1}{\sqrt{3}} \tag{1.109}$$

$$k_z = \frac{1+0}{\sqrt{3}} = \frac{1}{\sqrt{3}} \tag{1.110}$$

In summary, then

$$\mathbf{Rot(y,90)Rot(z,90)} = \mathbf{Rot(k,120)} \tag{1.111}$$

where

$$\mathbf{k} = \frac{1}{\sqrt{3}}\mathbf{i} + \frac{1}{\sqrt{3}}\mathbf{j} + \frac{1}{\sqrt{3}}\mathbf{k} \tag{1.112}$$

Any combination of rotations is always equivalent to a single rotation about some axis $\mathbf{k}$ by an angle θ, an important result that we will make use of later.

5.4.15 Stretching and Scaling

A transform $\mathbf{T}$

$$\mathbf{T} = \begin{bmatrix} a & 0 & 0 & 0 \\ 0 & b & 0 & 0 \\ 0 & 0 & c & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.113}$$

will stretch objects uniformly along the x axis by a factor a, along the y axis by a factor b, and along the z axis by a factor c. Consider any point on an object $x\mathbf{i}+y\mathbf{j}+z\mathbf{k}$; its tranform is

$$\begin{bmatrix} ax \\ by \\ cz \\ 1 \end{bmatrix} = \begin{bmatrix} a & 0 & 0 & 0 \\ 0 & b & 0 & 0 \\ 0 & 0 & c & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} \tag{1.114}$$

indicating stretching as stated. Thus a cube could be transformed into a rectangular parallelepiped by such a transform.

The Axiom code to perform this scale change is:

— **scale** —

```
scale(scalex, scaley, scalez) ==
 matrix(_
  [[scalex, 0      ,0     , 0], _
   [0     , scaley ,0     , 0], _
   [0     , 0,      scalez, 0], _
   [0     , 0,      0     , 1]])
```

———-

The transform $\mathbf{S}$ where

$$\mathbf{S} = \begin{bmatrix} s & 0 & 0 & 0 \\ 0 & s & 0 & 0 \\ 0 & 0 & s & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.115}$$

will scale any object by the factor s.

5.4.16 Perspective Transformations

Consider the image formed of an object by a simple lens.

The axis of the lens is along the y axis for convenience. An object point x,y,z is imaged at x',y',z' if the lens has a focal length f (f is considered positive). y' represents the image distance and varies with object distance y. If we plot points on a plane perpendicular to the y axis located at y' (the film plane in a camera), then a perspective image is formed.

We will first obtain values of x', y', and z', then introduce a perspective transformation and show that the same values are obtained.

Based on the fact that a ray passing through the center of the lens is undeviated we may write

$$\frac{z}{y} = \frac{z'}{y'} \tag{1.116}$$

$$\text{and } \frac{x}{y} = \frac{x'}{y'} \tag{1.117}$$

Based on the additional fact that a ray parallel to the lens axis passes through the focal point f, we may write

$$\frac{z}{f} = \frac{z'}{y' + f} \tag{1.118}$$

$$\text{and } \frac{x}{f} = \frac{x'}{y' + f} \tag{1.119}$$

Notice that x', y', and z' are negative and that f is positive. Eliminating y' between Equations 1.116 and 1.118 we obtain

$$\frac{z}{f} = \frac{z'}{(\frac{z'y}{z} + f)} \tag{1.120}$$

and solving for z' we obtain the result

$$z' = \frac{z}{(1 - \frac{y}{f})} \tag{1.121}$$

Working with Equations 1.117 and 1.119 we can similarly obtain

$$x' = \frac{x}{(1 - \frac{y}{f})} \tag{1.122}$$

In order to obtain the image distance y' we rewrite Equations 1.116 and 1.118 as

$$\frac{z}{z'} = \frac{y}{y'} \tag{1.123}$$

and

$$\frac{z}{z'} = \frac{f}{y' + f} \tag{1.124}$$

thus

$$\frac{y}{y'} = \frac{f}{y' + f} \tag{1.125}$$

and solving for y' we obtain the result

$$y' = \frac{y}{(1 - \frac{y}{f})} \tag{1.126}$$

The homogeneous transformation $\mathbf{P}$ which produces the same result is

$$\mathbf{P} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & -\frac{1}{f} & 0 & 1 \end{bmatrix} \tag{1.127}$$

as any point $x\mathbf{i} + y\mathbf{j} + z\mathbf{k}$ transforms as

$$\begin{bmatrix} x \\ y \\ z \\ 1 - \frac{y}{f} \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & -\frac{1}{f} & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} \tag{1.128}$$

The image point x', y',, z', obtained by dividing through by the weight factor $(1 - \frac{y}{f})$, is

$$\frac{x}{(1 - \frac{y}{f})}\mathbf{i} + \frac{y}{(1 - \frac{y}{f})}\mathbf{j} + \frac{z}{(1 - \frac{y}{f})}\mathbf{k} \tag{1.129}$$

This is the same result that we obtained above.

A transform similar to $\mathbf{P}$ but with $-\frac{1}{f}$ at the bottom of the first column produces a perspective transformation along the x axis. If the $-\frac{1}{f}$ term is in the third column then the projection is along the z axis.

5.4.17 Transform Equations

We will frequently be required to deal with transform equations in which a coordinate frame is described in two or more ways. A manipulator is positioned with respect to base coordinates by a transform $\mathbf{Z}$. The end of the manipulator is described by a transform ${}^{Z}\mathbf{T}_6$, and the end effector is described by ${}^{T_6}\mathbf{E}$. An object is positioned with respect to base coordinates by a transform $\mathbf{B}$, and finally the manipulator end effector is positioned with respect to the object by ${}^{B}\mathbf{G}$. We have two descriptions of the position of the end effector, one with respect to the object and one with respect to the manipulator. As both positions are the same, we may equate the two descriptions

$$\mathbf{Z}\,{}^{Z}\mathbf{T}_6\,{}^{T_6}\mathbf{E} = \mathbf{B}\,{}^{B}\mathbf{G} \tag{1.130}$$

If we wish to solve Equation 1.130 for the manipulator transform $\mathbf{T}_6$ we must premultiply Equation 1.130 by $\mathbf{Z}^{-1}$ and postmultiply by $\mathbf{E}^{-1}$ to obtain

$$\mathbf{T}_6 = \mathbf{Z}^{-1}\mathbf{B}\mathbf{G}\mathbf{E}^{-1} \tag{1.131}$$

As a further example, consider that the position of the object **B** is unknown, but that the manipulator is moved such that the end effector is positioned over the object correctly. We may then solve for **B** from Equation 1.130 by postmultiplying by $\mathbf{G}^{-1}$.

$$\mathbf{B} = \mathbf{Z}\mathbf{T}_6\mathbf{E}\mathbf{G}^{-1} \tag{1.133}$$

5.4.18 Summary


Homogeneous transformations may be readily used to describe the positions and orientations of coordinate frames in space. If a coordinate frame is embedded in an object then the position and orientation of the object are also readily described.

The description of object A in terms of object B by means of a homogeneous transformation may be inverted to obtain the description of object B in terms of object A. This is not a property of a simple vector description of the relative displacement of one object with respect to another.

Transformations may be interpreted as a product of rotation and translation transformations. If they are intrepreted from left to right, then the rotations and translations are in terms of the currently defined coordinate frame. If they are interpreted from right to left, then the rotations and translations are described with respect to the reference coordinate frame.

Homogeneous transformations describe coordinate frames in terms of rectangular components, which are the sines and cosines of angles. This description may be related to rotations in which case the description is in terms of a vector and angle of rotation.

5.4.19 DenavitHartenbergMatrix (DHMATRIX)



Exports:

antisymmetric?	any?	coerce	column	copy
count	determinant	diagonal?	diagonalMatrix	elt
empty	empty?	eq?	eval	every?
exquo	fill!	hash	horizConcat	identity
inverse	latex	less?	listOfLists	map
map!	matrix	maxColIndex	maxRowIndex	member?
members	minColIndex	minordet	minRowIndex	more?
ncols	new	nrows	nullSpace	nullity
parts	qelt	qsetelt!	rank	rotatex
rotatey	rotatez	row	rowEchelon	sample
scalarMatrix	scale	setColumn!	setRow!	setelt
setsubMatrix!	size?	square?	squareTop	subMatrix
swapColumns!	swapRows!	symmetric?	translate	transpose
vertConcat	zero	#?	?**?	?/?
?=?	?~=?	?*?	?+?	-?
?-?				

— domain DHMATRIX DenavitHartenbergMatrix —

```
)abbrev domain DHMATRIX DenavitHartenbergMatrix

++ Author: Timothy Daly
++ Date Created: June 26, 1991
++ Date Last Updated: 26 June 1991
++ Description:
++ 4x4 Matrices for coordinate transformations\br
++ This package contains functions to create 4x4 matrices
++ useful for rotating and transforming coordinate systems.
++ These matrices are useful for graphics and robotics.
++ (Reference: Robot Manipulators Richard Paul MIT Press 1981)
++
++ A Denavit-Hartenberg Matrix is a 4x4 Matrix of the form:\br
++ \tab{5}\spad{nx ox ax px}\br
++ \tab{5}\spad{ny oy ay py}\br
++ \tab{5}\spad{nz oz az pz}\br
++ \tab{5}\spad{0  0  0  1}\br
++ (n, o, and a are the direction cosines)

DenavitHartenbergMatrix(R): Exports == Implementation where
  R : Join(Field,  TranscendentalFunctionCategory)

-- for the implementation of dhmatrix
  minrow ==> 1
  mincolumn ==> 1
--
  nx ==> x(1,1)::R
  ny ==> x(2,1)::R
```

```
  nz ==> x(3,1)::R
  ox ==> x(1,2)::R
  oy ==> x(2,2)::R
  oz ==> x(3,2)::R
  ax ==> x(1,3)::R
  ay ==> x(2,3)::R
  az ==> x(3,3)::R
  px ==> x(1,4)::R
  py ==> x(2,4)::R
  pz ==> x(3,4)::R
  row ==> Vector(R)
  col ==> Vector(R)
  radians ==> pi()/180

  Exports ==> MatrixCategory(R,row,col) with
   "*": (%, Point R) -> Point R
     ++ t*p applies the dhmatrix t to point p
   identity: () -> %
     ++ identity() create the identity dhmatrix
   rotatex: R -> %
     ++ rotatex(r) returns a dhmatrix for rotation about axis x for r degrees
   rotatey: R -> %
     ++ rotatey(r) returns a dhmatrix for rotation about axis y for r degrees
   rotatez: R -> %
     ++ rotatez(r) returns a dhmatrix for rotation about axis z for r degrees
   scale: (R,R,R) -> %
     ++ scale(sx,sy,sz) returns a dhmatrix for scaling in the x, y and z
     ++ directions
   translate: (R,R,R) -> %
     ++ translate(x,y,z) returns a dhmatrix for translation by x, y, and z

  Implementation ==> Matrix(R) add

    identity() == matrix([[1,0,0,0],[0,1,0,0],[0,0,1,0],[0,0,0,1]])

--    inverse(x) == (inverse(x pretend (Matrix R))$Matrix(R)) pretend %
--    dhinverse(x) == matrix( _
--        [[nx,ny,nz,-(px*nx+py*ny+pz*nz)],_
--         [ox,oy,oz,-(px*ox+py*oy+pz*oz)],_
--         [ax,ay,az,-(px*ax+py*ay+pz*az)],_
--         [ 0, 0, 0, 1]])

    d * p ==
       v := p pretend Vector R
       v := concat(v, 1$R)
       v := d * v
       point ([v.1, v.2, v.3]$List(R))

\getchunk{rotatex}
```

```
\getchunk{rotatey}

\getchunk{rotatez}

\getchunk{scale}

\getchunk{translate}
```

———-

— **DHMATRIX.dotabb** —

```
"DHMATRIX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DHMATRIX"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"DHMATRIX" -> "IVECTOR"
```

———-

5.5 domain DEQUEUE Dequeue

— **Dequeue.input** —

```
)set break resume
)sys rm -f Dequeue.output
)spool Dequeue.output
)set message test on
)set message auto off
)clear all

--S 1 of 63
a:Dequeue INT:= dequeue [1,2,3,4,5]
--R
--R
--R   (1)  [1,2,3,4,5]
--R                                                    Type: Dequeue(Integer)
--E 1

--S 2 of 63
dequeue! a
--R
--R
--R   (2)  1
--R                                                     Type: PositiveInteger
--E 2
```

```
--S 3 of 63
a
--R
--R
--R   (3)  [2,3,4,5]
--R                                                    Type: Dequeue(Integer)
--E 3

--S 4 of 63
extract! a
--R
--R
--R   (4)  2
--R                                                     Type: PositiveInteger
--E 4

--S 5 of 63
a
--R
--R
--R   (5)  [3,4,5]
--R                                                    Type: Dequeue(Integer)
--E 5

--S 6 of 63
enqueue!(9,a)
--R
--R
--R   (6)  9
--R                                                     Type: PositiveInteger
--E 6

--S 7 of 63
a
--R
--R
--R   (7)  [3,4,5,9]
--R                                                    Type: Dequeue(Integer)
--E 7

--S 8 of 63
insert!(8,a)
--R
--R
--R   (8)  [3,4,5,9,8]
--R                                                    Type: Dequeue(Integer)
--E 8

--S 9 of 63
```

```
a
--R
--R
--R   (9)  [3,4,5,9,8]
--R                                                  Type: Dequeue(Integer)
--E 9

--S 10 of 63
front a
--R
--R
--R   (10)  3
--R                                                   Type: PositiveInteger
--E 10

--S 11 of 63
back a
--R
--R
--R   (11)  8
--R                                                   Type: PositiveInteger
--E 11

--S 12 of 63
bottom! a
--R
--R
--R   (12)  8
--R                                                   Type: PositiveInteger
--E 12

--S 13 of 63
a
--R
--R
--R   (13)  [3,4,5,9]
--R                                                  Type: Dequeue(Integer)
--E 13

--S 14 of 63
depth a
--R
--R
--R   (14)  4
--R                                                   Type: PositiveInteger
--E 14

--S 15 of 63
height a
--R
```

```
--R
--R   (15)  4
--R                                                    Type: PositiveInteger
--E 15

--S 16 of 63
insertBottom!(6,a)
--R
--R
--R   (16)  6
--R                                                    Type: PositiveInteger
--E 16

--S 17 of 63
a
--R
--R
--R   (17)  [3,4,5,9,6]
--R                                                   Type: Dequeue(Integer)
--E 17

--S 18 of 63
extractBottom! a
--R
--R
--R   (18)  6
--R                                                    Type: PositiveInteger
--E 18

--S 19 of 63
a
--R
--R
--R   (19)  [3,4,5,9]
--R                                                   Type: Dequeue(Integer)
--E 19

--S 20 of 63
insertTop!(7,a)
--R
--R
--R   (20)  7
--R                                                    Type: PositiveInteger
--E 20

--S 21 of 63
a
--R
--R
--R   (21)  [7,3,4,5,9]
```

```
--R                                                    Type: Dequeue(Integer)
--E 21

--S 22 of 63
extractTop! a
--R
--R
--R   (22)  7
--R                                                     Type: PositiveInteger
--E 22

--S 23 of 63
a
--R
--R
--R   (23)  [3,4,5,9]
--R                                                    Type: Dequeue(Integer)
--E 23

--S 24 of 63
top a
--R
--R
--R   (24)  3
--R                                                     Type: PositiveInteger
--E 24

--S 25 of 63
a
--R
--R
--R   (25)  [3,4,5,9]
--R                                                    Type: Dequeue(Integer)
--E 25

--S 26 of 63
top! a
--R
--R
--R   (26)  3
--R                                                     Type: PositiveInteger
--E 26

--S 27 of 63
a
--R
--R
--R   (27)  [4,5,9]
--R                                                    Type: Dequeue(Integer)
--E 27
```

```
--S 28 of 63
reverse! a
--R
--R
--R   (28)  [9,5,4]
--R                                                    Type: Dequeue(Integer)
--E 28

--S 29 of 63
rotate! a
--R
--R
--R   (29)  [5,4,9]
--R                                                    Type: Dequeue(Integer)
--E 29

--S 30 of 63
inspect a
--R
--R
--R   (30)  5
--R                                                    Type: PositiveInteger
--E 30

--S 31 of 63
empty? a
--R
--R
--R   (31)  false
--R                                                            Type: Boolean
--E 31

--S 32 of 63
#a
--R
--R
--R   (32)  3
--R                                                    Type: PositiveInteger
--E 32

--S 33 of 63
length a
--R
--R
--R   (33)  3
--R                                                    Type: PositiveInteger
--E 33

--S 34 of 63
```

```
less?(a,9)
--R
--R
--R   (34)  true
--R                                                    Type: Boolean
--E 34

--S 35 of 63
more?(a,9)
--R
--R
--R   (35)  false
--R                                                    Type: Boolean
--E 35

--S 36 of 63
size?(a,#a)
--R
--R
--R   (36)  true
--R                                                    Type: Boolean
--E 36

--S 37 of 63
size?(a,9)
--R
--R
--R   (37)  false
--R                                                    Type: Boolean
--E 37

--S 38 of 63
parts a
--R
--R
--R   (38)  [5,4,9]
--R                                               Type: List(Integer)
--E 38

--S 39 of 63
bag([1,2,3,4,5])$Dequeue(INT)
--R
--R
--R   (39)  [1,2,3,4,5]
--R                                            Type: Dequeue(Integer)
--E 39

--S 40 of 63
b:=empty()$(Dequeue INT)
--R
```

```
--R
--R   (40)  []
--R                                                    Type: Dequeue(Integer)
--E 40

--S 41 of 63
empty? b
--R
--R
--R   (41)  true
--R                                                             Type: Boolean
--E 41

--S 42 of 63
sample()$Dequeue(INT)
--R
--R
--R   (42)  []
--R                                                    Type: Dequeue(Integer)
--E 42

--S 43 of 63
c:=copy a
--R
--R
--R   (43)  [5,4,9]
--R                                                    Type: Dequeue(Integer)
--E 43

--S 44 of 63
eq?(a,c)
--R
--R
--R   (44)  false
--R                                                             Type: Boolean
--E 44

--S 45 of 63
eq?(a,a)
--R
--R
--R   (45)  true
--R                                                             Type: Boolean
--E 45

--S 46 of 63
(a=c)@Boolean
--R
--R
--R   (46)  true
```

```
--R                                                        Type: Boolean
--E 46

--S 47 of 63
(a=a)@Boolean
--R
--R
--R   (47)  true
--R                                                        Type: Boolean
--E 47

--S 48 of 63
a~=c
--R
--R
--R   (48)  false
--R                                                        Type: Boolean
--E 48

--S 49 of 63
any?(x+->(x=4),a)
--R
--R
--R   (49)  true
--R                                                        Type: Boolean
--E 49

--S 50 of 63
any?(x+->(x=11),a)
--R
--R
--R   (50)  false
--R                                                        Type: Boolean
--E 50

--S 51 of 63
every?(x+->(x=11),a)
--R
--R
--R   (51)  false
--R                                                        Type: Boolean
--E 51

--S 52 of 63
count(4,a)
--R
--R
--R   (52)  1
--R                                                  Type: PositiveInteger
--E 52
```

```
--S 53 of 63
count(x+->(x>2),a)
--R
--R
--R   (53)  3
--R                                                    Type: PositiveInteger
--E 53

--S 54 of 63
map(x+->x+10,a)
--R
--R
--R   (54)  [15,14,19]
--R                                                    Type: Dequeue(Integer)
--E 54

--S 55 of 63
a
--R
--R
--R   (55)  [5,4,9]
--R                                                    Type: Dequeue(Integer)
--E 55

--S 56 of 63
map!(x+->x+10,a)
--R
--R
--R   (56)  [15,14,19]
--R                                                    Type: Dequeue(Integer)
--E 56

--S 57 of 63
a
--R
--R
--R   (57)  [15,14,19]
--R                                                    Type: Dequeue(Integer)
--E 57

--S 58 of 63
members a
--R
--R
--R   (58)  [15,14,19]
--R                                                      Type: List(Integer)
--E 58

--S 59 of 63
```

```
member?(14,a)
--R
--R
--R   (59)  true
--R                                                              Type: Boolean
--E 59

--S 60 of 63
coerce a
--R
--R
--R   (60)  [15,14,19]
--R                                                           Type: OutputForm
--E 60

--S 61 of 63
hash a
--R
--R
--I   (61)  4999531
--R                                                         Type: SingleInteger
--E 61

--S 62 of 63
latex a
--R
--R
--R   (62)  "\mbox{\bf Unimplemented}"
--R                                                              Type: String
--E 62

--S 63 of 63
)show Dequeue
--R
--R Dequeue(S: SetCategory)  is a domain constructor
--R Abbreviation for Dequeue is DEQUEUE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DEQUEUE
--R
--R------------------------------ Operations --------------------------------
--R back : % -> S                        bag : List(S) -> %
--R bottom! : % -> S                     copy : % -> %
--R depth : % -> NonNegativeInteger      dequeue : List(S) -> %
--R dequeue : () -> %                    dequeue! : % -> S
--R empty : () -> %                      empty? : % -> Boolean
--R enqueue! : (S,%) -> S                eq? : (%,%) -> Boolean
--R extract! : % -> S                    extractBottom! : % -> S
--R extractTop! : % -> S                 front : % -> S
--R height : % -> NonNegativeInteger     insert! : (S,%) -> %
--R insertBottom! : (S,%) -> S           insertTop! : (S,%) -> S
```

```
--R inspect : % -> S                        length : % -> NonNegativeInteger
--R map : ((S -> S),%) -> %                 pop! : % -> S
--R push! : (S,%) -> S                      reverse! : % -> %
--R rotate! : % -> %                        sample : () -> %
--R top : % -> S                            top! : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 63

)spool
)lisp (bye)
```

———-

— Dequeue.help —

```
=====================================================================
Dequeue examples
=====================================================================

A Dequeue is a double-ended queue so elements can be added to
either end.

Here we create an dequeue of integers from a list. Notice that the
order in the list is the order in the dequeue.

   a:Dequeue INT:= dequeue [1,2,3,4,5]
      [1,2,3,4,5]
```

```
We can remove the top of the dequeue using dequeue!:

   dequeue! a
      1

Notice that the use of dequeue! is destructive (destructive operations
in Axiom usually end with ! to indicate that the underylying data
structure is changed).

   a
      [2,3,4,5]

The extract! operation is another name for the dequeue! operation and
has the same effect. This operation treats the dequeue as a BagAggregate:

   extract! a
      2

and you can see that it also has destructively modified the dequeue:

   a
      [3,4,5]

Next we use enqueue! to add a new element to the end of the dequeue:

   enqueue!(9,a)
      9

Again, the enqueue! operation is destructive so the dequeue is changed:

   a
      [3,4,5,9]

Another name for enqueue! is insert!, which treats the dequeue as a
BagAggregate:

   insert!(8,a)
      [3,4,5,9,8]

and it modifies the dequeue:

   a
      [3,4,5,9,8]

The front operation returns the item at the front of the dequeue:

   front a
      3
```

```
The back operation returns the item at the back of the dequeue:

   back a
      8

The bottom! operation returns the item at the back of the dequeue:

   bottom! a
      8

and it modifies the dequeue:

   a
      [3,4,5,9]

The depth function returns the number of elements in the dequeue:

   depth a
      4

The height function returns the number of elements in the dequeue:

   height a
      4

The insertBottom! function adds the element at the end:

   insertBottom!(6,a)
      6

and it modifies the dequeue:

   a
      [3,4,5,9,6]

The extractBottom! function removes the element at the end:

   extractBottom! a
      6

and it modifies the dequeue:

   a
      [3,4,5,9]

The insertTop! function adds the element at the top:

   insertTop!(7,a)
      7
```

```
and it modifies the dequeue:

   a
      [7,3,4,5,9]

The extractTop! function adds the element at the top:

   extractTop! a
      7

and it modifies the dequeue:

   a
      [3,4,5,9]

The top function returns the top element:

   top a
      3

and it does not modifies the dequeue:

   a
      [3,4,5,9]

The top! function returns the top element:

   top! a
      3

and it modifies the dequeue:

   a
      [4,5,9]

The reverse! operation destructively reverses the elements of the dequeue:

   reverse! a
      [9,5,4]

The rotate! operation moves the top element to the bottom:

   rotate! a
      [5,4,9]


The inspect function returns the top of the dequeue without modification,
viewed as a BagAggregate:

   inspect a
```

```
      5

The empty? operation returns true only if there are no element on the
dequeue, otherwise it returns false:

   empty? a
      false

The # (length) operation:

   #a
       3

The length operation does the same thing:

   length a
       3

The less? predicate will compare the dequeue length to an integer:

   less?(a,9)
        true

The more? predicate will compare the dequeue length to an integer:

   more?(a,9)
        false

The size? operation will compare the dequeue length to an integer:

   size?(a,#a)
        true

and since the last computation must alwasy be true we try:

   size?(a,9)
        false

The parts function will return  the dequeue as a list of its elements:

   parts a
        [5,4,9]

If we have a BagAggregate of elements we can use it to construct a dequeue:

   bag([1,2,3,4,5])$Dequeue(INT)
        [1,2,3,4,5]

The empty function will construct an empty dequeue of a given type:
```

```
   b:=empty()$(Dequeue INT)
        []
```

and the empty? predicate allows us to find out if a dequeue is empty:

```
   empty? b
        true
```

The sample function returns a sample, empty dequeue:

```
   sample()$Dequeue(INT)
        []
```

We can copy a dequeue and it does not share storage so subsequent
modifications of the original dequeue will not affect the copy:

```
   c:=copy a
        [5,4,9]
```

The eq? function is only true if the lists are the same reference,
so even though c is a copy of a, they are not the same:

```
   eq?(a,c)
        false
```

However, a clearly shares a reference with itself:

```
   eq?(a,a)
        true
```

But we can compare a and c for equality:

```
   (a=c)@Boolean
        true
```

and clearly a is equal to itself:

```
   (a=a)@Boolean
        true
```

and since a and c are equal, they are clearly NOT not-equal:

```
   a~=c
        false
```

We can use the any? function to see if a predicate is true for any element:

```
   any?(x+->(x=4),a)
        true
```

```
or false for every element:

   any?(x+->(x=11),a)
        false

We can use the every? function to check every element satisfies a predicate:

   every?(x+->(x=11),a)
        false

We can count the elements that are equal to an argument of this type:

   count(4,a)
        1

or we can count against a boolean function:

   count(x+->(x>2),a)
        3

You can also map a function over every element, returning a new dequeue:

   map(x+->x+10,a)
        [15,14,19]

Notice that the orignal dequeue is unchanged:

   a
        [5,4,9]

You can use map! to map a function over every element and change
the original dequeue since map! is destructive:

   map!(x+->x+10,a)
       [15,14,19]

Notice that the orignal dequeue has been changed:

   a
       [15,14,19]

The member function can also get the element of the dequeue as a list:

   members a
       [15,14,19]


and using member? we can test if the dequeue holds a given element:

   member?(14,a)
       true
```

```
See Also:
o )show Stack
o )show ArrayStack
o )show Queue
o )show Dequeue
o )show Heap
o )show BagAggregate
```

———-

5.5.1 Dequeue (DEQUEUE)



See

⇒ “Stack” (STACK) 20.28.1 on page 2530
⇒ “ArrayStack” (ASTACK) 2.10.1 on page 65
⇒ “Queue” (QUEUE) 18.5.1 on page 2150
⇒ “Heap” (HEAP) 9.2.1 on page 1104

Exports:

any?	back	bag	bottom!	coerce
copy	count	depth	dequeue	dequeue!
empty	empty?	enqueue!	eq?	eval
every?	extract!	extractBottom!	extractTop!	front
height	hash	insert!	insertBottom!	insertTop!
inspect	latex	length	less?	map
map!	member?	members	more?	parts
pop!	push!	reverse!	rotate!	sample
size?	top	top!	#?	?=?
?~=?				

— **domain DEQUEUE Dequeue** —

```
)abbrev domain DEQUEUE Dequeue
++ Author: Michael Monagan and Stephen Watt
++ Date Created:June 86 and July 87
++ Date Last Updated:Feb 92
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Linked list implementation of a Dequeue

Dequeue(S:SetCategory): DequeueAggregate S with
    dequeue: List S -> %
      ++ dequeue([x,y,...,z]) creates a dequeue with first (top or front)
      ++ element x, second element y,...,and last (bottom or back) element z.
      ++
      ++E g:Dequeue INT:= dequeue [1,2,3,4,5]

 -- Inherited Signatures repeated for examples documentation

    dequeue_! : % -> S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X dequeue! a
      ++X a
    extract_! : % -> S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X extract! a
      ++X a
    enqueue_! : (S,%) -> S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X enqueue! (9,a)
      ++X a
    insert_! : (S,%) -> %
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X insert! (8,a)
      ++X a
    inspect : % -> S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X inspect a
    front : % -> S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
```

```
  ++X front a
back : % -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X back a
rotate_! : % -> %
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X rotate! a
length : % -> NonNegativeInteger
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X length a
less? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X less?(a,9)
more? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X more?(a,9)
size? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X size?(a,5)
bag : List S -> %
  ++
  ++X bag([1,2,3,4,5])$Dequeue(INT)
empty? : % -> Boolean
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X empty? a
empty : () -> %
  ++
  ++X b:=empty()$(Dequeue INT)
sample : () -> %
  ++
  ++X sample()$Dequeue(INT)
copy : % -> %
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X copy a
eq? : (%,%) -> Boolean
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X b:=copy a
  ++X eq?(a,b)
map :  ((S -> S),%) -> %
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
```

```
  ++X map(x+->x+10,a)
  ++X a
depth : % -> NonNegativeInteger
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X depth a
dequeue : () -> %
  ++
  ++X a:Dequeue INT:= dequeue ()
height : % -> NonNegativeInteger
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X height a
top : % -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X top a
bottom_! : % -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X bottom! a
  ++X a
extractBottom_! : % -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X extractBottom! a
  ++X a
extractTop_! : % -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X extractTop! a
  ++X a
insertBottom_! : (S,%) -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X insertBottom! a
  ++X a
insertTop_! : (S,%) -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X insertTop! a
  ++X a
pop_! : % -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
  ++X pop! a
  ++X a
push_! : (S,%) -> S
  ++
  ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
```

```
    ++X push! a
    ++X a
  reverse_! : % -> %
    ++
    ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
    ++X reverse! a
    ++X a
  top_! : % -> S
    ++
    ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
    ++X top! a
    ++X a
  if $ has shallowlyMutable then
    map! :  ((S -> S),%) -> %
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X map!(x+->x+10,a)
      ++X a
  if S has SetCategory then
    latex : % -> String
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X latex a
    hash : % -> SingleInteger
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X hash a
    coerce : % -> OutputForm
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X coerce a
    "=": (%,%) -> Boolean
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X b:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X (a=b)@Boolean
    "~=" : (%,%) -> Boolean
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X b:=copy a
      ++X (a~=b)
  if % has finiteAggregate then
    every? : ((S -> Boolean),%) -> Boolean
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X every?(x+->(x=4),a)
    any? : ((S -> Boolean),%) -> Boolean
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X any?(x+->(x=4),a)
```

```
    count :  ((S -> Boolean),%) -> NonNegativeInteger
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X count(x+->(x>2),a)
    _# : % -> NonNegativeInteger
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X #a
    parts : % -> List S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X parts a
    members : % -> List S
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X members a
  if % has finiteAggregate and S has SetCategory then
    member? : (S,%) -> Boolean
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X member?(3,a)
    count : (S,%) -> NonNegativeInteger
      ++
      ++X a:Dequeue INT:= dequeue [1,2,3,4,5]
      ++X count(4,a)

== Queue S add
  Rep := Reference List S
  bottom! d == extractBottom! d
  dequeue d == ref copy d
  extractBottom! d ==
      if empty? d then error "empty dequeue"
      p := deref d
      n := maxIndex p
      n = 1 =>
         r := first p
         setref(d,[])
         r
      q := rest(p,(n-2)::NonNegativeInteger)
      r := first rest q
      q.rest := []
      r
  top! d == extractTop! d
  extractTop! d ==
      if empty? d then error "empty dequeue"
      e := top d
      setref(d,rest deref d)
      e
  height d == # deref d
  depth d == # deref d
```

```
    insertTop!(e,d) == (setref(d,cons(e,deref d)); e)
    lastTail==> LAST$Lisp
    insertBottom!(e,d) ==
        if empty? d then setref(d, list e)
        else lastTail.(deref d).rest := list e
        e
    top d == if empty? d then error "empty dequeue" else first deref d
    reverse! d == (setref(d,reverse deref d); d)
```

———-

— **DEQUEUE.dotabb** —

```
"DEQUEUE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DEQUEUE"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"DEQUEUE" -> "FLAGG-"
"DEQUEUE" -> "FLAGG"
```

———-

5.6 domain DERHAM DeRhamComplex

— **DeRhamComplex.input** —

```
)set break resume
)sys rm -f DeRhamComplex.output
)spool DeRhamComplex.output
)set message test on
)set message auto off
)clear all
--S 1 of 34
coefRing := Integer
--R
--R
--R   (1)  Integer
--R                                                          Type: Domain
--E 1

--S 2 of 34
lv : List Symbol := [x,y,z]
--R
--R
--R   (2)  [x,y,z]
```

```
--R                                                          Type: List(Symbol)
--E 2

--S 3 of 34
der := DERHAM(coefRing,lv)
--R
--R
--R   (3)  DeRhamComplex(Integer,[x,y,z])
--R                                                          Type: Domain
--E 3

--S 4 of 34
R := Expression coefRing
--R
--R
--R   (4)  Expression(Integer)
--R                                                          Type: Domain
--E 4

--S 5 of 34
f : R := x**2*y*z-5*x**3*y**2*z**5
--R
--R
--R            3 2 5    2
--R   (5)  - 5x y z  + x y z
--R                                                 Type: Expression(Integer)
--E 5

--S 6 of 34
g : R := z**2*y*cos(z)-7*sin(x**3*y**2)*z**2
--R
--R
--R            2     3 2       2
--R   (6)  - 7z sin(x y ) + y z cos(z)
--R                                                 Type: Expression(Integer)
--E 6

--S 7 of 34
h : R :=x*y*z-2*x**3*y*z**2
--R
--R
--R            3   2
--R   (7)  - 2x y z  + x y z
--R                                                 Type: Expression(Integer)
--E 7

--S 8 of 34
dx : der := generator(1)
--R
--R
```

```
--R   (8)  dx
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 8

--S 9 of 34
dy : der := generator(2)
--R
--R
--R   (9)  dy
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 9

--S 10 of 34
dz : der := generator(3)
--R
--R
--R   (10)  dz
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 10

--S 11 of 34
[dx,dy,dz] := [generator(i)$der for i in 1..3]
--R
--R
--R   (11)  [dx,dy,dz]
--R                                    Type: List(DeRhamComplex(Integer,[x,y,z]))
--E 11

--S 12 of 34
alpha : der := f*dx + g*dy + h*dz
--R
--R
--R   (12)
--R          3   2                    2     3 2       2
--R     (- 2x y z  + x y z)dz + (- 7z sin(x y ) + y z cos(z))dy
--R   +
--R          3 2 5    2
--R     (- 5x y z  + x y z)dx
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 12

--S 13 of 34
beta  : der := cos(tan(x*y*z)+x*y*z)*dx + x*dy
--R
--R
--R   (13)  x dy + cos(tan(x y z) + x y z)dx
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 13

--S 14 of 34
```

```
exteriorDifferential alpha
--R
--R
--R   (14)
--R         2                  3 2                     3 2
--R     (y z sin(z) + 14z sin(x y ) - 2y z cos(z) - 2x z  + x z)dy dz
--R   +
--R         3 2 4     2   2          2
--R     (25x y z  - 6x y z  + y z - x y)dx dz
--R   +
--R           2 2 2     3 2       3   5    2
--R     (- 21x y z cos(x y ) + 10x y z  - x z)dx dy
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 14

--S 15 of 34
exteriorDifferential %
--R
--R
--R   (15)  0
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 15

--S 16 of 34
gamma := alpha * beta
--R
--R
--R   (16)
--R        4   2    2              3   2
--R     (2x y z  - x y z)dy dz + (2x y z  - x y z)cos(tan(x y z) + x y z)dx dz
--R   +
--R       2     3 2       2                                    4 2 5    3
--R   ((7z sin(x y ) - y z cos(z))cos(tan(x y z) + x y z) - 5x y z  + x y z)dx dy
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 16

--S 17 of 34
exteriorDifferential(gamma) - (exteriorDifferential(alpha)*beta - alpha * exteriorDifferential(b
--R
--R
--R   (17)  0
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 17

--S 18 of 34
a : BOP := operator('a)
--R
--R
--R   (18)  a
--R                                                     Type: BasicOperator
```

```
--E 18

--S 19 of 34
b : BOP := operator('b)
--R
--R
--R   (19)  b
--R                                                        Type: BasicOperator
--E 19

--S 20 of 34
c : BOP := operator('c)
--R
--R
--R   (20)  c
--R                                                        Type: BasicOperator
--E 20

--S 21 of 34
sigma := a(x,y,z) * dx + b(x,y,z) * dy + c(x,y,z) * dz
--R
--R
--R   (21)  c(x,y,z)dz + b(x,y,z)dy + a(x,y,z)dx
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 21

--S 22 of 34
theta  := a(x,y,z) * dx * dy + b(x,y,z) * dx * dz + c(x,y,z) * dy * dz
--R
--R
--R   (22)  c(x,y,z)dy dz + b(x,y,z)dx dz + a(x,y,z)dx dy
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 22

--S 23 of 34
totalDifferential(a(x,y,z))$der
--R
--R
--R   (23)  a  (x,y,z)dz + a  (x,y,z)dy + a  (x,y,z)dx
--R          ,3             ,2             ,1
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 23

--S 24 of 34
exteriorDifferential sigma
--R
--R
--R   (24)
--R     (c  (x,y,z) - b  (x,y,z))dy dz + (c  (x,y,z) - a  (x,y,z))dx dz
--R       ,2           ,3                  ,1           ,3
```

```
--R   +
--R     (b  (x,y,z) - a  (x,y,z))dx dy
--R       ,1           ,2
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 24

--S 25 of 34
exteriorDifferential theta
--R
--R
--R   (25)  (c  (x,y,z) - b  (x,y,z) + a  (x,y,z))dx dy dz
--R           ,1           ,2           ,3
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 25

--S 26 of 34
one : der := 1
--R
--R
--R   (26)  1
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 26

--S 27 of 34
g1 : der := a([x,t,y,u,v,z,e]) * one
--R
--R
--R   (27)  a(x,t,y,u,v,z,e)
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 27

--S 28 of 34
h1 : der := a([x,y,x,t,x,z,y,r,u,x]) * one
--R
--R
--R   (28)  a(x,y,x,t,x,z,y,r,u,x)
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 28

--S 29 of 34
exteriorDifferential g1
--R
--R
--R   (29)  a  (x,t,y,u,v,z,e)dz + a  (x,t,y,u,v,z,e)dy + a  (x,t,y,u,v,z,e)dx
--R          ,6                     ,3                     ,1
--R                                          Type: DeRhamComplex(Integer,[x,y,z])
--E 29

--S 30 of 34
exteriorDifferential h1
```

```
--R
--R
--R   (30)
--R     a  (x,y,x,t,x,z,y,r,u,x)dz
--R      ,6
--R   +
--R     (a  (x,y,x,t,x,z,y,r,u,x) + a  (x,y,x,t,x,z,y,r,u,x))dy
--R       ,7                         ,2
--R   +
--R         a   (x,y,x,t,x,z,y,r,u,x) + a  (x,y,x,t,x,z,y,r,u,x)
--R          ,10                         ,5
--R       +
--R         a  (x,y,x,t,x,z,y,r,u,x) + a  (x,y,x,t,x,z,y,r,u,x)
--R          ,3                         ,1
--R    *
--R       dx
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 30

--S 31 of 34
coefficient(gamma, dx*dy)
--R
--R
--R            2     3 2       2                                    4 2 5    3
--R   (31)  (7z sin(x y ) - y z cos(z))cos(tan(x y z) + x y z) - 5x y z  + x y z
--R                                                    Type: Expression(Integer)
--E 31

--S 32 of 34
coefficient(gamma, one)
--R
--R
--R   (32)  0
--R                                                    Type: Expression(Integer)
--E 32

--S 33 of 34
coefficient(g1,one)
--R
--R
--R   (33)  a(x,t,y,u,v,z,e)
--R                                                    Type: Expression(Integer)
--E 33

--S 34 of 34
gamma := alpha * beta
--R
--R
--R   (34)
--R        4   2    2              3   2
```

```
--R     (2x y z  - x y z)dy dz + (2x y z  - x y z)cos(tan(x y z) + x y z)dx dz
--R   +
--R       2     3 2       2                                    4 2 5    3
--R   ((7z sin(x y ) - y z cos(z))cos(tan(x y z) + x y z) - 5x y z  + x y z)dx dy
--R                                        Type: DeRhamComplex(Integer,[x,y,z])
--E 34
)spool
)lisp (bye)
```

———-

— DeRhamComplex.help —

```
====================================================================
DeRhamComplex examples
====================================================================

The domain constructor DeRhamComplex creates the class of differential
forms of arbitrary degree over a coefficient ring.  The De Rham
complex constructor takes two arguments: a ring, coefRing, and a list
of coordinate variables.

This is the ring of coefficients.

  coefRing := Integer
   Integer
                      Type: Domain

These are the coordinate variables.

  lv : List Symbol := [x,y,z]
   [x,y,z]
                      Type: List Symbol


This is the De Rham complex of Euclidean three-space using coordinates
x, y and z.

  der := DERHAM(coefRing,lv)
   DeRhamComplex(Integer,[x,y,z])
                      Type: Domain

This complex allows us to describe differential forms having
expressions of integers as coefficients.  These coefficients can
involve any number of variables, for example, f(x,t,r,y,u,z).  As
we've chosen to work with ordinary Euclidean three-space, expressions
involving these forms are treated as functions of x, y and z with the
additional arguments t, r and u regarded as symbolic constants.
```

Here are some examples of coefficients.

```
  R := Expression coefRing
   Expression Integer
                    Type: Domain

  f : R := x**2*y*z-5*x**3*y**2*z**5
       3 2 5    2
   - 5x y z  + x y z
                    Type: Expression Integer

  g : R := z**2*y*cos(z)-7*sin(x**3*y**2)*z**2
       2     3 2       2
   - 7z sin(x y ) + y z cos(z)
                    Type: Expression Integer

  h : R :=x*y*z-2*x**3*y*z**2
       3   2
   - 2x y z  + x y z
                    Type: Expression Integer
```

We now define the multiplicative basis elements for the exterior algebra over R.

```
  dx : der := generator(1)
   dx
                    Type: DeRhamComplex(Integer,[x,y,z])

  dy : der := generator(2)
   dy
                    Type: DeRhamComplex(Integer,[x,y,z])

  dz : der := generator(3)
   dz
                    Type: DeRhamComplex(Integer,[x,y,z])
```

This is an alternative way to give the above assignments.

```
  [dx,dy,dz] := [generator(i)$der for i in 1..3]
    [dx,dy,dz]
                    Type: List DeRhamComplex(Integer,[x,y,z])
```

Now we define some one-forms.

```
  alpha : der := f*dx + g*dy + h*dz
          3   2                   2     3 2       2
     (- 2x y z  + x y z)dz + (- 7z sin(x y ) + y z cos(z))dy
   +
          3 2 5    2
     (- 5x y z  + x y z)dx
```

```
                    Type: DeRhamComplex(Integer,[x,y,z])

  beta  : der := cos(tan(x*y*z)+x*y*z)*dx + x*dy
    x dy + cos(tan(x y z) + x y z)dx
                    Type: DeRhamComplex(Integer,[x,y,z])
```

A well-known theorem states that the composition of exteriorDifferential with itself is the zero map for continuous forms. Let's verify this theorem for alpha.

```
  exteriorDifferential alpha
        2                  3 2                     3 2
     (y z sin(z) + 14z sin(x y ) - 2y z cos(z) - 2x z  + x z)dy dz
   +
         3 2 4     2   2          2
     (25x y z  - 6x y z  + y z - x y)dx dz
   +
           2 2 2     3 2       3   5    2
     (- 21x y z cos(x y ) + 10x y z  - x z)dx dy
                    Type: DeRhamComplex(Integer,[x,y,z])
```

We see a lengthy output of the last expression, but nevertheless, the composition is zero.

```
  exteriorDifferential %
    0
                    Type: DeRhamComplex(Integer,[x,y,z])
```

Now we check that exteriorDifferential is a "graded derivation" D, that is, D satisfies:

```
  D(a*b) = D(a)*b + (-1)**degree(a)*a*D(b)

  gamma := alpha * beta
        4   2    2               3   2
     (2x y z  - x y z)dy dz + (2x y z  - x y z)cos(tan(x y z) + x y z)dx dz
   +
       2     3 2       2                                    4 2 5    3
    ((7z sin(x y ) - y z cos(z))cos(tan(x y z) + x y z) - 5x y z  + x y z)dx dy
                    Type: DeRhamComplex(Integer,[x,y,z])
```

We try this for the one-forms alpha and beta.

```
  exteriorDifferential(gamma) - (exteriorDifferential(alpha)*beta - alpha * exteriorDifferential
    0
                    Type: DeRhamComplex(Integer,[x,y,z])
```

Now we define some "basic operators"

```
  a : BOP := operator('a)
```

```
    a
                        Type: BasicOperator

  b : BOP := operator('b)
    b
                        Type: BasicOperator

  c : BOP := operator('c)
    c
                        Type: BasicOperator
```

We also define some indeterminate one- and two-forms using these operators.

```
  sigma := a(x,y,z) * dx + b(x,y,z) * dy + c(x,y,z) * dz
    c(x,y,z)dz + b(x,y,z)dy + a(x,y,z)dx
                        Type: DeRhamComplex(Integer,[x,y,z])

  theta  := a(x,y,z) * dx * dy + b(x,y,z) * dx * dz + c(x,y,z) * dy * dz
    c(x,y,z)dy dz + b(x,y,z)dx dz + a(x,y,z)dx dy
                        Type: DeRhamComplex(Integer,[x,y,z])
```

This allows us to get formal definitions for the "gradient" ...

```
  totalDifferential(a(x,y,z))$der
   (23)  a  (x,y,z)dz + a  (x,y,z)dy + a  (x,y,z)dx
          ,3             ,2             ,1
                        Type: DeRhamComplex(Integer,[x,y,z])
```

the "curl" ...

```
  exteriorDifferential sigma
     (c  (x,y,z) - b  (x,y,z))dy dz + (c  (x,y,z) - a  (x,y,z))dx dz
       ,2           ,3                  ,1           ,3
   +
     (b  (x,y,z) - a  (x,y,z))dx dy
       ,1           ,2
                        Type: DeRhamComplex(Integer,[x,y,z])
```

and the "divergence."

```
  exteriorDifferential theta
    (c  (x,y,z) - b  (x,y,z) + a  (x,y,z))dx dy dz
      ,1           ,2           ,3
                        Type: DeRhamComplex(Integer,[x,y,z])
```

Note that the De Rham complex is an algebra with unity. This element 1 is the basis for elements for zero-forms, that is, functions in our space.

```
  one : der := 1
```

```
   1
                      Type: DeRhamComplex(Integer,[x,y,z])
```

To convert a function to a function lying in the De Rham complex, multiply the function by "one."

```
  g1 : der := a([x,t,y,u,v,z,e]) * one
    a(x,t,y,u,v,z,e)
                      Type: DeRhamComplex(Integer,[x,y,z])
```

A current limitation of Axiom forces you to write functions with more than four arguments using square brackets in this way.

```
  h1 : der := a([x,y,x,t,x,z,y,r,u,x]) * one
    a(x,y,x,t,x,z,y,r,u,x)
                       Type: DeRhamComplex(Integer,[x,y,z])
```

Now note how the system keeps track of where your coordinate functions are located in expressions.

```
  exteriorDifferential g1
    a  (x,t,y,u,v,z,e)dz + a  (x,t,y,u,v,z,e)dy + a  (x,t,y,u,v,z,e)dx
     ,6                    ,3                    ,1
                       Type: DeRhamComplex(Integer,[x,y,z])

  exteriorDifferential h1
     a  (x,y,x,t,x,z,y,r,u,x)dz
      ,6
   +
     (a  (x,y,x,t,x,z,y,r,u,x) + a  (x,y,x,t,x,z,y,r,u,x))dy
       ,7                        ,2
   +
         a   (x,y,x,t,x,z,y,r,u,x) + a  (x,y,x,t,x,z,y,r,u,x)
          ,10                        ,5
       +
         a  (x,y,x,t,x,z,y,r,u,x) + a  (x,y,x,t,x,z,y,r,u,x)
          ,3                        ,1
    *
       dx
                      Type: DeRhamComplex(Integer,[x,y,z])
```

In this example of Euclidean three-space, the basis for the De Rham complex consists of the eight forms: 1, dx, dy, dz, dx*dy, dx*dz, dy*dz, and dx*dy*dz.

```
  coefficient(gamma, dx*dy)
       2     3 2       2                                  4 2 5    3
    (7z sin(x y ) - y z cos(z))cos(tan(x y z) + x y z) - 5x y z  + x y z
                      Type: Expression Integer

  coefficient(gamma, one)
```


```
    0
                        Type: Expression Integer

  coefficient(g1,one)
    a(x,t,y,u,v,z,e)
                        Type: Expression Integer

See Also:
o )help Operator
o )show DeRhamComplex
```

———-

5.6.1 DeRhamComplex (DERHAM)



See

⇒ “ExtAlgBasis” (EAB) 6.8.1 on page 713
⇒ “AntiSymm” (ANTISYM) 2.8.1 on page 40

Exports:

0	1	characteristic	coefficient
coerce	degree	exteriorDifferential	generator
hash	homogeneous?	latex	leadingBasisTerm
leadingCoefficient	map	one?	recip
reductum	retract	retractable?	retractIfCan
sample	subtractIfCan	totalDifferential	zero?
?~=?	?*?	?**?	?^?
?+?	?-?	-?	?=?

— domain DERHAM DeRhamComplex —

```
)abbrev domain DERHAM DeRhamComplex
++ Author: Larry A. Lambe
++ Date    : 01/26/91.
```

```
++ Revised : 12/01/91.
++
++ based on code from '89 (AntiSymmetric)
++
++ Needs: LeftAlgebra, ExtAlgBasis, FreeMod(Ring,OrderedSet)
++
++ Description:
++ The deRham complex of Euclidean space, that is, the
++ class of differential forms of arbitary degree over a coefficient ring.
++ See Flanders, Harley, Differential Forms, With Applications to the Physical
++ Sciences, New York, Academic Press, 1963.

DeRhamComplex(CoefRing,listIndVar:List Symbol): Export == Implement where
  CoefRing :  Join(Ring, OrderedSet)
  ASY     ==> AntiSymm(R,listIndVar)
  DIFRING ==> DifferentialRing
  LALG    ==> LeftAlgebra
  FMR     ==> FreeMod(R,EAB)
  I       ==> Integer
  L       ==> List
  EAB     ==> ExtAlgBasis  -- these are exponents of basis elements in order
  NNI     ==> NonNegativeInteger
  O       ==> OutputForm
  R       ==> Expression(CoefRing)

  Export == Join(LALG(R), RetractableTo(R)) with
      leadingCoefficient : %           -> R
        ++ leadingCoefficient(df) returns the leading
        ++ coefficient of differential form df.
      leadingBasisTerm   : %           -> %
        ++ leadingBasisTerm(df) returns the leading
        ++ basis term of differential form df.
      reductum           : %           -> %
        ++ reductum(df), where df is a differential form,
        ++ returns df minus the leading
        ++ term of df if df has two or more terms, and
        ++ 0 otherwise.
      coefficient        : (%,%)     -> R
        ++ coefficient(df,u), where df is a differential form,
        ++ returns the coefficient of df containing the basis term u
        ++ if such a term exists, and 0 otherwise.
      generator          : NNI         -> %
        ++ generator(n) returns the nth basis term for a differential form.
      homogeneous?       : %           -> Boolean
        ++  homogeneous?(df) tests if all of the terms of
        ++  differential form df have the same degree.
      retractable?       : %           -> Boolean
        ++  retractable?(df) tests if differential form df is a 0-form,
        ++  i.e., if degree(df) = 0.
      degree             : %           -> I
```

```
        ++  degree(df) returns the homogeneous degree of differential form df.
      map                : (R -> R, %) -> %
        ++  map(f,df) replaces each coefficient x of differential
        ++  form df by \spad{f(x)}.
      totalDifferential    : R -> %
        ++  totalDifferential(x) returns the total differential
        ++  (gradient) form for element x.
      exteriorDifferential : % -> %
        ++  exteriorDifferential(df) returns the exterior
        ++  derivative (gradient, curl, divergence, ...) of
        ++  the differential form df.

  Implement == ASY add
      Rep := ASY

      dim := #listIndVar

      totalDifferential(f) ==
        divs:=[differentiate(f,listIndVar.i)*generator(i)$ASY for i in 1..dim]
        reduce("+",divs)

      termDiff : (R, %) -> %
      termDiff(r,e) ==
        totalDifferential(r) * e

      exteriorDifferential(x) ==
        x = 0 => 0
        termDiff(leadingCoefficient(x)$Rep,leadingBasisTerm x) + exteriorDifferential(reductum x)

      lv := [concat("d",string(liv))$String::Symbol for liv in listIndVar]

      displayList:EAB -> O
      displayList(x):O ==
        le: L I := exponents(x)$EAB
--      reduce(_*,[(lv.i)::O for i in 1..dim | le.i = 1])$L(O)
--        reduce(_*,[(lv.i)::O for i in 1..dim | one?(le.i)])$L(O)
        reduce(_*,[(lv.i)::O for i in 1..dim | ((le.i) = 1)])$L(O)

      makeTerm:(R,EAB) -> O
      makeTerm(r,x) ==
      -- we know that r ^= 0
        x = Nul(dim)$EAB  => r::O
--        one? r => displayList(x)
        (r = 1) => displayList(x)
--      r = 1 => displayList(x)
        r::O * displayList(x)

      terms : % -> List Record(k: EAB, c: R)
      terms(a) ==
        -- it is the case that there are at least two terms in a
```

```
        a pretend List Record(k: EAB, c: R)

      coerce(a):O ==
        a           = 0$Rep => 0$I::O
        ta := terms a
--      reductum(a) = 0$Rep => makeTerm(leadingCoefficient a, a.first.k)
        null ta.rest => makeTerm(ta.first.c, ta.first.k)
        reduce(_+,[makeTerm(t.c,t.k) for t in ta])$L(O)
```

———-

— DERHAM.dotabb —

```
"DERHAM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DERHAM"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"DERHAM" -> "FS"
```

———-

5.7 domain DSTREE DesingTree

— DesingTree.input —

```
)set break resume
)sys rm -f DesingTree.output
)spool DesingTree.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DesingTree
--R
--R DesingTree(S: SetCategory)  is a domain constructor
--R Abbreviation for DesingTree is DSTREE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DSTREE
--R
--R------------------------------ Operations --------------------------------
--R children : % -> List(%)               copy : % -> %
--R cyclic? : % -> Boolean                distance : (%,%) -> Integer
--R ?.value : (%,value) -> S              empty : () -> %
--R empty? : % -> Boolean                 encode : % -> String
--R eq? : (%,%) -> Boolean                fullOut : % -> OutputForm
```

```
--R fullOutput : () -> Boolean            fullOutput : Boolean -> Boolean
--R leaf? : % -> Boolean                  leaves : % -> List(S)
--R map : ((S -> S),%) -> %               nodes : % -> List(%)
--R sample : () -> %                      tree : List(S) -> %
--R tree : S -> %                         tree : (S,List(%)) -> %
--R value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— DesingTree.help —

```
=====================================================================
DesingTree examples
=====================================================================

See Also:
o )show DesingTree
```

———-

5.7.1 DesingTree (DSTREE)



Exports:

#?	?.value	?=?	?~=?	any?
child?	children	coerce	copy	count
cyclic?	distance	empty	empty?	encode
eq?	eval	every?	fullOut	fullOutput
hash	latex	leaf?	leaves	less?
map	map!	member?	members	more?
node?	nodes	parts	sample	setchildren!
setelt	setvalue!	size?	tree	value

— domain DSTREE DesingTree —

```
)abbrev domain DSTREE DesingTree
++ Authors: Gaetan Hache
++ Date Created: jan 1998
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This category is part of the PAFF package
DesingTree(S: SetCategory): T==C where

 T == DesingTreeCategory(S) with

    encode: % -> String
       ++ encode(t) returns a string indicating the "shape" of the tree

    fullOut: % -> OutputForm
      ++ fullOut(tr) yields a full output of tr (see function fullOutput).

    fullOutput: Boolean -> Boolean
      ++ fullOutput(b) sets a flag such that when true,
```

```
      ++ a coerce to OutputForm yields the full output of
      ++ tr, otherwise encode(tr) is output (see encode function).
      ++ The default is false.

    fullOutput: () -> Boolean
      ++ fullOutput returns the value of the flag set by fullOutput(b).

 C == add
    Rep ==> Record(value: S, args: List %)

    fullOut(t:%): OutputForm ==
      empty? children t => (value t) ::OutputForm
      prefix((value t)::OutputForm, [fullOut(tr) for tr in children t])

    fullOutputFlag:Boolean:=false()

    fullOutput(f)== fullOutputFlag:=f

    fullOutput == fullOutputFlag

    leaves(t)==
      empty?(chdr:=children(t)) => list(value(t))
      concat([leaves(subt) for subt in chdr])

    t1=t2 == value t1 = value t2 and children t1 = children t2

    coerce(t:%):OutputForm==
      ^fullOutput() => encode(t) :: OutputForm
      fullOut(t)

    tree(s,ls) == ([s,ls]:Rep):%

    tree(s:S) == ([s,[]]:Rep):%

    tree(ls:List(S))==
      empty?(ls) =>
        error "Cannot create a tree with an empty list"
      f:=first(ls)
      empty?(rs:=rest(ls)) =>
        tree(f)
      tree(f,[tree(rs)])

    value t == (t:Rep).value

    children t == ((t:Rep).args):List %

    setchildren_!(t,ls) == ((t:Rep).args:=ls;t pretend %)

    setvalue_!(t,s) == ((t:Rep).value:=s;s)
```

```
    encode(t)==
      empty?(chtr:=children(t)) => empty()$String
      concat([concat(["U",encode(arb),"."]) for arb in chtr])
```

———-

— **DSTREE.dotabb** —

```
"DSTREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DSTREE"];
"DSTRCAT"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=DSTRCAT"]
"DSTREE" -> "DSTRCAT"
```

———-

5.8 domain DSMP DifferentialSparseMultivariatePolynomial

— **DifferentialSparseMultivariatePolynomial.input** —

```
)set break resume
)sys rm -f DifferentialSparseMultivariatePolynomial.output
)spool DifferentialSparseMultivariatePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DifferentialSparseMultivariatePolynomial
--R
--R DifferentialSparseMultivariatePolynomial(R: Ring,S: OrderedSet,V: DifferentialVariableCatego
--R Abbreviation for DifferentialSparseMultivariatePolynomial is DSMP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DSMP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> % if R has DIFRING
--R D : (%,List(V)) -> %                  D : (%,V) -> %
--R 1 : () -> %                           0 : () -> %
```

```
--R ?^? : (%,PositiveInteger) -> %        coefficients : % -> List(R)
--R coerce : S -> %                       coerce : V -> %
--R coerce : R -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              degree : % -> IndexedExponents(V)
--R differentiate : (%,List(V)) -> %      differentiate : (%,V) -> %
--R eval : (%,List(V),List(%)) -> %       eval : (%,V,%) -> %
--R eval : (%,List(V),List(R)) -> %       eval : (%,V,R) -> %
--R eval : (%,%,%) -> %                   eval : (%,Equation(%)) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             initial : % -> %
--R isobaric? : % -> Boolean              latex : % -> String
--R leader : % -> V                       leadingCoefficient : % -> R
--R leadingMonomial : % -> %              map : ((R -> R),%) -> %
--R monomial? : % -> Boolean              monomials : % -> List(%)
--R one? : % -> Boolean                   order : % -> NonNegativeInteger
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R retract : % -> S                      retract : % -> V
--R retract : % -> R                      sample : () -> %
--R separant : % -> %                     variables : % -> List(V)
--R weight : % -> NonNegativeInteger      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if R has DIFRING
--R D : (%,List(V),List(NonNegativeInteger)) -> %
--R D : (%,V,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List(V),List(NonNegativeInteger)) -> %
--R coefficient : (%,V,NonNegativeInteger) -> %
--R coefficient : (%,IndexedExponents(V)) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : SparseMultivariatePolynomial(R,S) -> %
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
```

```
--R content : (%,V) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if R has KONVERT(INFORM) and V has KONVERT(INFORM)
--R convert : % -> Pattern(Integer) if R has KONVERT(PATTERN(INT)) and V has KONVERT(PATTERN(INT
--R convert : % -> Pattern(Float) if R has KONVERT(PATTERN(FLOAT)) and V has KONVERT(PATTERN(FLO
--R degree : (%,S) -> NonNegativeInteger
--R degree : (%,List(V)) -> List(NonNegativeInteger)
--R degree : (%,V) -> NonNegativeInteger
--R differentialVariables : % -> List(S)
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if R has DIFRING
--R differentiate : % -> % if R has DIFRING
--R differentiate : (%,List(V),List(NonNegativeInteger)) -> %
--R differentiate : (%,V,NonNegativeInteger) -> %
--R discriminant : (%,V) -> % if R has COMRING
--R eval : (%,List(S),List(R)) -> % if R has DIFRING
--R eval : (%,S,R) -> % if R has DIFRING
--R eval : (%,List(S),List(%)) -> % if R has DIFRING
--R eval : (%,S,%) -> % if R has DIFRING
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R isExpt : % -> Union(Record(var: V,exponent: NonNegativeInteger),"failed")
--R isPlus : % -> Union(List(%),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R mainVariable : % -> Union(V,"failed")
--R makeVariable : % -> (NonNegativeInteger -> %) if R has DIFRING
--R makeVariable : S -> (NonNegativeInteger -> %)
--R mapExponents : ((IndexedExponents(V) -> IndexedExponents(V)),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List(V)) -> List(NonNegativeInteger)
--R minimumDegree : (%,V) -> NonNegativeInteger
--R minimumDegree : % -> IndexedExponents(V)
--R monicDivide : (%,%,V) -> Record(quotient: %,remainder: %)
--R monomial : (%,List(V),List(NonNegativeInteger)) -> %
```

```
--R monomial : (%,V,NonNegativeInteger) -> %
--R monomial : (R,IndexedExponents(V)) -> %
--R multivariate : (SparseUnivariatePolynomial(%),V) -> %
--R multivariate : (SparseUnivariatePolynomial(R),V) -> %
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,S) -> NonNegativeInteger
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if R
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if R has P
--R pomopo! : (%,R,IndexedExponents(V),%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,V) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LIN
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R resultant : (%,%,V) -> % if R has COMRING
--R retract : % -> SparseMultivariatePolynomial(R,S)
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(SparseMultivariatePolynomial(R,S),"failed")
--R retractIfCan : % -> Union(S,"failed")
--R retractIfCan : % -> Union(V,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if R has
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List(V)) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,V) -> SparseUnivariatePolynomial(%)
--R weight : (%,S) -> NonNegativeInteger
--R weights : (%,S) -> List(NonNegativeInteger)
--R weights : % -> List(NonNegativeInteger)
--R
--E 1

)spool
)lisp (bye)
```


— DifferentialSparseMultivariatePolynomial.help —

```
==========================================================================
DifferentialSparseMultivariatePolynomial examples
==========================================================================

See Also:
o )show DifferentialSparseMultivariatePolynomial
```

———-

5.8.1 DifferentialSparseMultivariatePolynomial (DSMP)



See

⇒ “OrderlyDifferentialVariable” (ODVAR) 16.17.1 on page 1821
⇒ “SequentialDifferentialVariable” (SDVAR) 20.7.1 on page 2357
⇒ “OrderlyDifferentialPolynomial” (ODPOL) 16.16.1 on page 1817
⇒ “SequentialDifferentialPolynomial” (SDPOL) 20.6.1 on page 2351

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	convert
D	degree	differentialVariables
differentiate	discriminant	eval
exquo	factor	factorPolynomial
factorSquareFreePolynomial	gcd	gcdPolynomial
ground	ground?	hash
initial	isExpt	isobaric?
isPlus	isTimes	latex
lcm	leader	leadingCoefficient
leadingMonomial	makeVariable	map
mapExponents	max	min
minimumDegree	monicDivide	monomial
monomials	monomial?	multivariate
numberOfMonomials	one?	order
patternMatch	pomopo!	prime?
primitiveMonomials	primitivePart	recip
reducedSystem	reductum	resultant
retract	retractIfCan	sample
separant	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
totalDegree	unit?	unitCanonical
unitNormal	univariate	variables
weight	weights	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?~=?	?/?
?<?	?<=?	?>?
?>=?		

— domain DSMP DifferentialSparseMultivariatePolynomial —

```
)abbrev domain DSMP DifferentialSparseMultivariatePolynomial
++ Author:  William Sit
++ Date Created: 19 July 1990
++ Date Last Updated: 13 September 1991
++ Basic Operations:DifferentialPolynomialCategory
++ Related Constructors:
++ See Also:
++ AMS Classifications:12H05
++ Keywords: differential indeterminates, ranking, differential polynomials,
++           order, weight, leader, separant, initial, isobaric
++ References:Kolchin, E.R. "Differential Algebra and Algebraic Groups"
++   (Academic Press, 1973).
++ Description:
```

```
++ \spadtype{DifferentialSparseMultivariatePolynomial} implements
++ an ordinary differential polynomial ring by combining a
++ domain belonging to the category \spadtype{DifferentialVariableCategory}
++ with the domain \spadtype{SparseMultivariatePolynomial}.

DifferentialSparseMultivariatePolynomial(R, S, V):
     Exports == Implementation where
  R: Ring
  S: OrderedSet
  V: DifferentialVariableCategory S
  E   ==> IndexedExponents(V)
  PC  ==> PolynomialCategory(R,IndexedExponents(V),V)
  PCL ==> PolynomialCategoryLifting
  P   ==> SparseMultivariatePolynomial(R, V)
  SUP ==> SparseUnivariatePolynomial
  SMP ==> SparseMultivariatePolynomial(R, S)

  Exports ==> Join(DifferentialPolynomialCategory(R,S,V,E),
                   RetractableTo SMP)

  Implementation ==> P add
    retractIfCan(p:$):Union(SMP, "failed") ==
      zero? order p =>
        map(x+->retract(x)@S :: SMP,y+->y::SMP, p)$PCL(
                                  IndexedExponents V, V, R, $, SMP)
      "failed"

    coerce(p:SMP):$ ==
      map(x+->x::V::$, y+->y::$, p)$PCL(IndexedExponents S, S, R, SMP, $)
```

———-

— DSMP.dotabb —

```
"DSMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DSMP"]
"DPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DPOLCAT"]
"DSMP" -> "DPOLCAT"
```

———-

5.9 domain DIRPROD DirectProduct

— DirectProduct.input —

```
)set break resume
```

```
)sys rm -f DirectProduct.output
)spool DirectProduct.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DirectProduct
--R
--R DirectProduct(dim: NonNegativeInteger,R: Type)  is a domain constructor
--R Abbreviation for DirectProduct is DIRPROD
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DIRPROD
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if R has RING             1 : () -> % if R has MONOID
--R 0 : () -> % if R has CABMON           coerce : % -> Vector(R)
--R copy : % -> %                         directProduct : Vector(R) -> %
--R ?.? : (%,Integer) -> R                elt : (%,Integer,R) -> R
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(R)                eq? : (%,%) -> Boolean
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
--R map : ((R -> R),%) -> %               qelt : (%,Integer) -> R
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (PositiveInteger,%) -> % if R has ABELSG
--R ?*? : (NonNegativeInteger,%) -> % if R has CABMON
--R ?*? : (R,%) -> % if R has RING
--R ?*? : (%,R) -> % if R has RING
--R ?*? : (%,%) -> % if R has MONOID
--R ?*? : (Integer,%) -> % if R has RING
--R ?**? : (%,PositiveInteger) -> % if R has MONOID
--R ?**? : (%,NonNegativeInteger) -> % if R has MONOID
--R ?+? : (%,%) -> % if R has ABELSG
--R ?-? : (%,%) -> % if R has RING
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has OAMONS or R has ORDRING
--R ?<=? : (%,%) -> Boolean if R has OAMONS or R has ORDRING
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R ?>? : (%,%) -> Boolean if R has OAMONS or R has ORDRING
--R ?>=? : (%,%) -> Boolean if R has OAMONS or R has ORDRING
--R D : (%,(R -> R)) -> % if R has RING
--R D : (%,(R -> R),NonNegativeInteger) -> % if R has RING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL) and R has RING
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL) and R has RING
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL) and R has RING
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL) and R has RING
--R D : (%,NonNegativeInteger) -> % if R has DIFRING and R has RING
--R D : % -> % if R has DIFRING and R has RING
--R ?^? : (%,PositiveInteger) -> % if R has MONOID
```

```
--R ?^? : (%,NonNegativeInteger) -> % if R has MONOID
--R abs : % -> % if R has ORDRING
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R characteristic : () -> NonNegativeInteger if R has RING
--R coerce : R -> % if R has SETCAT
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT)) and R has SETCAT
--R coerce : Integer -> % if R has RETRACT(INT) and R has SETCAT or R has RING
--R coerce : % -> OutputForm if R has SETCAT
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R differentiate : (%,(R -> R)) -> % if R has RING
--R differentiate : (%,(R -> R),NonNegativeInteger) -> % if R has RING
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL) and R
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL) and R has RING
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL) and R has RING
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL) and R has RING
--R differentiate : (%,NonNegativeInteger) -> % if R has DIFRING and R has RING
--R differentiate : % -> % if R has DIFRING and R has RING
--R dimension : () -> CardinalNumber if R has FIELD
--R dot : (%,%) -> R if R has RING
--R entry? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,R) -> % if $ has shallowlyMutable
--R first : % -> R if Integer has ORDSET
--R hash : % -> SingleInteger if R has SETCAT
--R index : PositiveInteger -> % if R has FINITE
--R latex : % -> String if R has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R lookup : % -> PositiveInteger if R has FINITE
--R map! : ((R -> R),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if R has OAMONS or R has ORDRING
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R min : (%,%) -> % if R has OAMONS or R has ORDRING
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R negative? : % -> Boolean if R has ORDRING
--R one? : % -> Boolean if R has MONOID
--R parts : % -> List(R) if $ has finiteAggregate
--R positive? : % -> Boolean if R has ORDRING
--R qsetelt! : (%,Integer,R) -> R if $ has shallowlyMutable
--R random : () -> % if R has FINITE
--R recip : % -> Union(%,"failed") if R has MONOID
--R reducedSystem : Matrix(%) -> Matrix(R) if R has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R)) if R has RING
```

```
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LINE
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT) and R has RING
--R retract : % -> R if R has SETCAT
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT)) and R has SETCAT
--R retract : % -> Integer if R has RETRACT(INT) and R has SETCAT
--R retractIfCan : % -> Union(R,"failed") if R has SETCAT
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT)) and R has SETCAT
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT) and R has SETCAT
--R setelt : (%,Integer,R) -> R if $ has shallowlyMutable
--R sign : % -> Integer if R has ORDRING
--R size : () -> NonNegativeInteger if R has FINITE
--R size? : (%,NonNegativeInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed") if R has CABMON
--R sup : (%,%) -> % if R has OAMONS
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R unitVector : PositiveInteger -> % if R has RING
--R zero? : % -> Boolean if R has CABMON
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— DirectProduct.help —

```
=====================================================================
DirectProduct examples
=====================================================================

See Also:
o )show DirectProduct
```

———-

5.9.1 DirectProduct (DIRPROD)



Exports:

0	1	abs	any?	characteristic
coerce	copy	count	D	differentiate
dimension	directProduct	dot	elt	empty
empty?	entries	entry?	eq?	eval
every?	fill!	first	hash	index
index?	indices	latex	less?	lookup
map	map!	max	maxIndex	member?
members	min	minIndex	more?	negative?
one?	parts	positive?	qelt	qsetelt!
random	recip	reducedSystem	retract	retractIfCan
sample	setelt	sign	size	size?
subtractIfCan	sup	swap!	unitVector	zero?
#?	?*?	?**?	?+?	?-?
?/?	?<?	?<=?	?=?	?>?
?>=?	?^?	?~=?	-?	?.?

— domain DIRPROD DirectProduct —

```
)abbrev domain DIRPROD DirectProduct
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors: Vector, IndexedVector
++ Also See: OrderedDirectProduct
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type represents the finite direct or cartesian product of an
++ underlying component type. This contrasts with simple vectors in that
++ the members can be viewed as having constant length. Thus many
++ categorical properties can by lifted from the underlying component type.
```

```
++ Component extraction operations are provided but no updating operations.
++ Thus new direct product elements can either be created by converting
++ vector elements using the \spadfun{directProduct} function
++ or by taking appropriate linear combinations of basis vectors provided
++ by the \spad{unitVector} operation.

DirectProduct(dim:NonNegativeInteger, R:Type):
  DirectProductCategory(dim, R) == Vector R add

      Rep := Vector R

      coerce(z:%):Vector(R)        == copy(z)$Rep pretend Vector(R)
      coerce(r:R):%                == new(dim, r)$Rep

      parts x == VEC2LIST(x)$Lisp

      directProduct z ==
        size?(z, dim) => copy(z)$Rep
        error "Not of the correct length"


      if R has SetCategory then
        same?: % -> Boolean
        same? z == every?(x +-> x = z(minIndex z), z)

        x = y == _and/[qelt(x,i)$Rep = qelt(y,i)$Rep for i in 1..dim]

        retract(z:%):R ==
          same? z => z(minIndex z)
          error "Not retractable"

        retractIfCan(z:%):Union(R, "failed") ==
          same? z => z(minIndex z)
          "failed"


      if R has AbelianSemiGroup then
        u:% + v:% == map(_+ , u, v)$Rep

      if R has AbelianMonoid then
        0 == zero(dim)$Vector(R) pretend %

      if R has Monoid then
        1 == new(dim, 1)$Vector(R) pretend %
        u:% * r:R       == map(x +-> x * r, u)
        r:R * u:%       == map(x +-> r * x, u)
        x:% * y:% == [x.i * y.i for i in 1..dim]$Vector(R) pretend %

      if R has CancellationAbelianMonoid then
        subtractIfCan(u:%, v:%):Union(%,"failed") ==
```

```
          w := new(dim,0)$Vector(R)
          for i in 1..dim repeat
            (c:=subtractIfCan(qelt(u, i)$Rep, qelt(v,i)$Rep)) case "failed" =>
                    return "failed"
            qsetelt_!(w, i, c::R)$Rep
          w pretend %

      if R has Ring then

        u:% * v:%                    == map(_* , u, v)$Rep

        recip z ==
          w := new(dim,0)$Vector(R)
          for i in minIndex w .. maxIndex w repeat
            (u := recip qelt(z, i)) case "failed" => return "failed"
            qsetelt_!(w, i, u::R)
          w pretend %

        unitVector i ==
          v:= new(dim,0)$Vector(R)
          v.i := 1
          v pretend %

      if R has OrderedSet then
        x < y ==
          for i in 1..dim repeat
             qelt(x,i) < qelt(y,i) => return true
             qelt(x,i) > qelt(y,i) => return false
          false

      if R has OrderedAbelianMonoidSup then sup(x, y) == map(sup, x, y)

--)bo $noSubsumption := false
```

———-

— DIRPROD.dotabb —

```
"DIRPROD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DIRPROD"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"DIRPROD" -> "DIRPCAT"
```

———-

5.10 domain DPMM DirectProductMatrixModule

— DirectProductMatrixModule.input —

```
)set break resume
)sys rm -f DirectProductMatrixModule.output
)spool DirectProductMatrixModule.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DirectProductMatrixModule
--R
--R DirectProductMatrixModule(n: PositiveInteger,R: Ring,M: SquareMatrixCategory(n,R,DirectProduct(n,R),Dire
--R Abbreviation for DirectProductMatrixModule is DPMM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DPMM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (M,%) -> %                      ?*? : (PositiveInteger,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (R,%) -> %
--R ?+? : (%,%) -> %                      -? : % -> %
--R ?-? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 0 : () -> %                           coerce : % -> OutputForm
--R coerce : % -> Vector(S)               copy : % -> %
--R directProduct : Vector(S) -> %        ?.? : (%,Integer) -> S
--R elt : (%,Integer,S) -> S              empty : () -> %
--R empty? : % -> Boolean                 entries : % -> List(S)
--R eq? : (%,%) -> Boolean                hash : % -> SingleInteger
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
--R latex : % -> String                   map : ((S -> S),%) -> %
--R qelt : (%,Integer) -> S               sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (%,%) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S has MONOID or
--R ?*? : (S,%) -> % if S has RING
--R ?*? : (%,S) -> % if S has RING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S
--R ?**? : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING o
--R ?/? : (%,S) -> % if S has FIELD
--R ?<? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?<=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R D : % -> % if S has DIFRING and S has RING
--R D : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
```

```
--R D : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,(S -> S)) -> % if S has RING
--R D : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R 1 : () -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S has MON
--R ?^? : (%,PositiveInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S ha
--R ?^? : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S
--R abs : % -> % if S has ORDRING
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R characteristic : () -> NonNegativeInteger if S has RING
--R coerce : Fraction(Integer) -> % if S has RETRACT(FRAC(INT)) and S has SETCAT
--R coerce : Integer -> % if S has RETRACT(INT) and S has SETCAT or S has RING
--R coerce : S -> % if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R differentiate : % -> % if S has DIFRING and S has RING
--R differentiate : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R differentiate : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S
--R differentiate : (%,(S -> S)) -> % if S has RING
--R differentiate : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R dimension : () -> CardinalNumber if S has FIELD
--R dot : (%,%) -> S if S has RING
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R first : % -> S if Integer has ORDSET
--R index : PositiveInteger -> % if S has FINITE
--R less? : (%,NonNegativeInteger) -> Boolean
--R lookup : % -> PositiveInteger if S has FINITE
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has OAMONS or S has ORDRING
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R min : (%,%) -> % if S has OAMONS or S has ORDRING
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R negative? : % -> Boolean if S has ORDRING
--R one? : % -> Boolean if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S
--R parts : % -> List(S) if $ has finiteAggregate
--R positive? : % -> Boolean if S has ORDRING
```

```
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R random : () -> % if S has FINITE
--R recip : % -> Union(%,"failed") if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S
--R reducedSystem : Matrix(%) -> Matrix(Integer) if S has LINEXP(INT) and S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if S has LIN
--R reducedSystem : Matrix(%) -> Matrix(S) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(S),vec: Vector(S)) if S has RING
--R retract : % -> Fraction(Integer) if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retract : % -> Integer if S has RETRACT(INT) and S has SETCAT
--R retract : % -> S if S has SETCAT
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retractIfCan : % -> Union(Integer,"failed") if S has RETRACT(INT) and S has SETCAT
--R retractIfCan : % -> Union(S,"failed") if S has SETCAT
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R sign : % -> Integer if S has ORDRING
--R size : () -> NonNegativeInteger if S has FINITE
--R size? : (%,NonNegativeInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R sup : (%,%) -> % if S has OAMONS
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R unitVector : PositiveInteger -> % if S has RING
--R
--E 1

)spool
)lisp (bye)
```

———-


— DirectProductMatrixModule.help —

```
=====================================================================
DirectProductMatrixModule examples
=====================================================================

See Also:
o )show DirectProductMatrixModule
```

———-

5.10.1 DirectProductMatrixModule (DPMM)



See

⇒ "OppositeMonogenicLinearOperator" (OMLO) 16.11.1 on page 1773
⇒ "OrdinaryDifferentialRing" (ODR) 16.18.1 on page 1824
⇒ "DirectProductModule" (DPMO) 5.11.1 on page 544

Exports:

0	1	coerce	copy	directProduct
elt	empty	empty?	entries	eq?
hash	index?	indices	latex	map
qelt	sample	zero?	D	abs
any?	characteristic	coerce	count	differentiate
dimension	dot	entry?	eval	every?
fill!	first	index	less?	lookup
map!	max	maxIndex	member?	members
min	minIndex	more?	negative?	one?
parts	positive?	qsetelt!	random	recip
reducedSystem	retract	retractIfCan	setelt	sign
size	size?	subtractIfCan	sup	swap!
unitVector	#?	?*?	?**?	?/?
?<?	?<=?	?>?	?>=?	?^?
?^?	-?	?-?	?=?	?.?
?~=?				

— domain DPMM DirectProductMatrixModule —

```
)abbrev domain DPMM DirectProductMatrixModule
++ Author:  Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
```

```
++ References:
++ Description:
++ This constructor provides a direct product type with a
++ left matrix-module view.

DirectProductMatrixModule(n, R, M, S): DPcategory == DPcapsule where
    n: PositiveInteger
    R: Ring
    RowCol ==> DirectProduct(n,R)
    M: SquareMatrixCategory(n,R,RowCol,RowCol)
    S: LeftModule(R)

    DPcategory == Join(DirectProductCategory(n,S), LeftModule(R), LeftModule(M))

    DPcapsule == DirectProduct(n, S) add
        Rep := Vector(S)
        r:R * x:$ == [r*x.i for i in 1..n]
        m:M * x:$ == [ +/[m(i,j)*x.j for j in 1..n] for i in 1..n]
```

———-

— DPMM.dotabb —

```
"DPMM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DPMM"]
"SMATCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=SMATCAT"]
"DPMM" -> "SMATCAT"
```

———-

5.11 domain DPMO DirectProductModule

— DirectProductModule.input —

```
)set break resume
)sys rm -f DirectProductModule.output
)spool DirectProductModule.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DirectProductModule
--R
--R DirectProductModule(n: NonNegativeInteger,R: Ring,S: LeftModule(R))  is a domain constructor
```

```
--R Abbreviation for DirectProductModule is DPMO
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DPMO
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?*? : (Integer,%) -> %
--R ?*? : (R,%) -> %                      ?+? : (%,%) -> %
--R -? : % -> %                           ?-? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                0 : () -> %
--R coerce : % -> OutputForm              coerce : % -> Vector(S)
--R copy : % -> %                         directProduct : Vector(S) -> %
--R ?.? : (%,Integer) -> S                elt : (%,Integer,S) -> S
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(S)                eq? : (%,%) -> Boolean
--R hash : % -> SingleInteger             index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)          latex : % -> String
--R map : ((S -> S),%) -> %               qelt : (%,Integer) -> S
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (%,%) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S ha
--R ?*? : (S,%) -> % if S has RING
--R ?*? : (%,S) -> % if S has RING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S h
--R ?**? : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and
--R ?/? : (%,S) -> % if S has FIELD
--R ?<? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?<=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R D : % -> % if S has DIFRING and S has RING
--R D : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R D : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,(S -> S)) -> % if S has RING
--R D : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R 1 : () -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S has MON
--R ?^? : (%,PositiveInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S ha
--R ?^? : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING or S has LINEXP(INT) and S
--R abs : % -> % if S has ORDRING
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R characteristic : () -> NonNegativeInteger if S has RING
--R coerce : Fraction(Integer) -> % if S has RETRACT(FRAC(INT)) and S has SETCAT
--R coerce : Integer -> % if S has RETRACT(INT) and S has SETCAT or S has RING
--R coerce : S -> % if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
```

```
--R differentiate : % -> % if S has DIFRING and S has RING
--R differentiate : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R differentiate : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,(S -> S)) -> % if S has RING
--R differentiate : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R dimension : () -> CardinalNumber if S has FIELD
--R dot : (%,%) -> S if S has RING
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R first : % -> S if Integer has ORDSET
--R index : PositiveInteger -> % if S has FINITE
--R less? : (%,NonNegativeInteger) -> Boolean
--R lookup : % -> PositiveInteger if S has FINITE
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has OAMONS or S has ORDRING
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R min : (%,%) -> % if S has OAMONS or S has ORDRING
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R negative? : % -> Boolean if S has ORDRING
--R one? : % -> Boolean if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S has MONOID
--R parts : % -> List(S) if $ has finiteAggregate
--R positive? : % -> Boolean if S has ORDRING
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R random : () -> % if S has FINITE
--R recip : % -> Union(%,"failed") if S has DIFRING and S has RING or S has LINEXP(INT) and S has RING or S
--R reducedSystem : Matrix(%) -> Matrix(Integer) if S has LINEXP(INT) and S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if S has LINE
--R reducedSystem : Matrix(%) -> Matrix(S) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(S),vec: Vector(S)) if S has RING
--R retract : % -> Fraction(Integer) if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retract : % -> Integer if S has RETRACT(INT) and S has SETCAT
--R retract : % -> S if S has SETCAT
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retractIfCan : % -> Union(Integer,"failed") if S has RETRACT(INT) and S has SETCAT
--R retractIfCan : % -> Union(S,"failed") if S has SETCAT
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R sign : % -> Integer if S has ORDRING
--R size : () -> NonNegativeInteger if S has FINITE
--R size? : (%,NonNegativeInteger) -> Boolean
```

```
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R sup : (%,%) -> % if S has OAMONS
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R unitVector : PositiveInteger -> % if S has RING
--R
--E 1

)spool
)lisp (bye)
```

———-


— **DirectProductModule.help** —

```
=====================================================================
DirectProductModule examples
=====================================================================

See Also:
o )show DirectProductModule
```

———-

5.11.1 DirectProductModule (DPMO)



See

⇒ “OppositeMonogenicLinearOperator” (OMLO) 16.11.1 on page 1773
⇒ “OrdinaryDifferentialRing” (ODR) 16.18.1 on page 1824
⇒ “DirectProductMatrixModule” (DPMM) 5.10.1 on page 540

Exports:

0	1	abs	any?	characteristic
coerce	copy	count	D	differentiate
dimension	directProduct	dot	elt	empty
empty?	entries	entry?	eval	every?
eq?	fill!	first	hash	index
index?	indices	latex	less?	lookup
map	map!	max	maxIndex	member?
members	min	minIndex	more?	negative?
one?	parts	positive?	qelt	qsetelt!
random	recip	reducedSystem	retract	retractIfCan
sample	setelt	sign	size	size?
subtractIfCan	sup	swap!	unitVector	zero?
#?	?*?	?**?	?/?	?<?
?<=?	?>?	?>=?	?^?	?+?
-?	?-?	?=?	?.?	?~=?

— domain DPMO DirectProductModule —

```
)abbrev domain DPMO DirectProductModule
++ Author:  Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
++ This constructor provides a direct product of R-modules
++ with an R-module view.

DirectProductModule(n, R, S): DPcategory == DPcapsule where
    n: NonNegativeInteger
    R: Ring
    S: LeftModule(R)

    DPcategory == Join(DirectProductCategory(n,S), LeftModule(R))
    --  with if S has Algebra(R) then Algebra(R)
    --  <above line leads to matchMmCond: unknown form of condition>

    DPcapsule == DirectProduct(n,S) add
        Rep := Vector(S)
        r:R * x:$ == [r * x.i for i in 1..n]
```

— **DPMO.dotabb** —

```
"DPMO" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DPMO"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"DPMO" -> "DIRPCAT"
```

———-

5.12 domain DIRRING DirichletRing

The Dirichlet Ring is the ring of arithmetical functions

$$f : \mathbb{N}_+ \to R$$

(see `http://en.wikipedia.org/wiki/Arithmetic_function`) together with the Dirichlet convolution (see `http://en.wikipedia.org/wiki/Dirichlet_convolution`) as multiplication and component-wise addition. Since we can consider the values an arithmetic functions assumes as the coefficients of a Dirichlet generating series, we call R the coefficient ring of a function.

In general we only assume that the coefficient ring R is a ring. If R happens to be commutative, then so is the Dirichlet ring, and in this case it is even an algebra.

Apart from the operations inherited from those categories, we only provide some convenient coercion functions.

— **DirichletRing.input** —

```
)set break resume
)sys rm -f DirichletRing.output
)spool DirichletRing.output
)set message test on
)set message auto off
)clear all

--S 1 of 21
t1:DIRRING INT := (n:PI):INT +-> moebiusMu n
--R
--R
--R   (1)  [1,- 1,- 1,0,- 1,1,- 1,0,0,1,...]
--R                                                    Type: DirichletRing(Integer)
--E 1

--S 2 of 21
[t1.i for i in 1..4]
--R
--R
```

```
--R   (2)  [1,- 1,- 1,0]
--R                                                    Type: List(Integer)
--E 2

--S 3 of 21
t2:DIRRING INT := [moebiusMu n for n in 1..]
--R
--R
--R   (3)  [1,- 1,- 1,0,- 1,1,- 1,0,0,1,...]
--R                                          Type: DirichletRing(Integer)
--E 3

--S 4 of 21
[t2.i for i in 1..4]
--R
--R
--R   (4)  [1,- 1,- 1,0]
--R                                                    Type: List(Integer)
--E 4

--S 5 of 21
DIRRING INT has CommutativeRing
--R
--R
--R   (5)  true
--R                                                           Type: Boolean
--E 5

--S 6 of 21
mu:DIRRING FRAC INT := (n:PI):FRAC INT +-> moebiusMu n
--R
--R
--R   (6)  [1,- 1,- 1,0,- 1,1,- 1,0,0,1,...]
--R                                  Type: DirichletRing(Fraction(Integer))
--E 6

--S 7 of 21
phi:DIRRING FRAC INT := (n:PI):FRAC INT +-> eulerPhi n
--R
--R
--R   (7)  [1,1,2,2,4,2,6,4,6,4,...]
--R                                  Type: DirichletRing(Fraction(Integer))
--E 7

--S 8 of 21
t3:=[(recip mu * phi).n for n in 1..10]
--R
--R
--R   (8)  [1,2,3,4,5,6,7,8,9,10]
--R                                        Type: List(Fraction(Integer))
```

```
--E 8

--S 9 of 21
t4:=[(phi * recip mu).n for n in 1..10]
--R
--R
--R   (9)  [1,2,3,4,5,6,7,8,9,10]
--R                                                Type: List(Fraction(Integer))
--E 9

--S 10 of 21
reduce(_and,[(x = y)@Boolean for x in t3 for y in t4])
--R
--R
--R   (10)  true
--R                                                                Type: Boolean
--E 10

--S 11 of 21
DIRRING FRAC INT has Algebra FRAC INT
--R
--R
--R   (11)  true
--R                                                                Type: Boolean
--E 11

--S 12 of 21
t5:=[(1/2 * phi).n for n in 1..10]
--R
--R
--R          1 1
--R   (12)  [-,-,1,1,2,1,3,2,3,2]
--R          2 2
--R                                                Type: List(Fraction(Integer))
--E 12

--S 13 of 21
t6:=[eulerPhi n/2 for n in 1..10]
--R
--R
--R          1 1
--R   (13)  [-,-,1,1,2,1,3,2,3,2]
--R          2 2
--R                                                Type: List(Fraction(Integer))
--E 13

--S 14 of 21
reduce(_and,[(x = y)@Boolean for x in t5 for y in t6])
--R
--R
```

```
--R   (14)  true
--R                                                                Type: Boolean
--E 14

--S 15 of 21
t7:=[(recip mu).n for n in 1..10]
--R
--R
--R   (15)  [1,1,1,1,1,1,1,1,1,1]
--R                                            Type: List(Fraction(Integer))
--E 15

--S 16 of 21
t8:=[1 for n in 1..10]
--R
--R
--R   (16)  [1,1,1,1,1,1,1,1,1,1]
--R                                              Type: List(PositiveInteger)
--E 16

--S 17 of 21
reduce(_and,[(x = y)@Boolean for x in t7 for y in t8])
--R
--R
--R   (17)  true
--R                                                                Type: Boolean
--E 17

--S 18 of 21
t9:=[(recip mu * phi).n for n in 1..10]
--R
--R
--R   (18)  [1,2,3,4,5,6,7,8,9,10]
--R                                            Type: List(Fraction(Integer))
--E 18

--S 19 of 21
t10:=[n for n in 1..10]
--R
--R
--R   (19)  [1,2,3,4,5,6,7,8,9,10]
--R                                              Type: List(PositiveInteger)
--E 19

--S 20 of 21
reduce(_and,[(x = y)@Boolean for x in t9 for y in t10])
--R
--R
--R   (20)  true
--R                                                                Type: Boolean
```

```
--E 20

--S 21 of 21
)show DirichletRing
--R
--R DirichletRing(Coef: Ring)  is a domain constructor
--R Abbreviation for DirichletRing is DIRRING
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DIRRING
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : % -> Stream(Coef)
--R coerce : Stream(Coef) -> %            coerce : Integer -> %
--R coerce : % -> OutputForm              ?.? : (%,PositiveInteger) -> Coef
--R hash : % -> SingleInteger             latex : % -> String
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R sample : () -> %                      zero? : % -> Boolean
--R zeta : () -> %                        ?~=? : (%,%) -> Boolean
--R ?*? : (%,Coef) -> % if Coef has COMRING
--R ?*? : (Coef,%) -> % if Coef has COMRING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R additive? : (%,PositiveInteger) -> Boolean
--R associates? : (%,%) -> Boolean if Coef has COMRING
--R characteristic : () -> NonNegativeInteger
--R coerce : % -> % if Coef has COMRING
--R coerce : Coef -> % if Coef has COMRING
--R coerce : % -> (PositiveInteger -> Coef)
--R coerce : (PositiveInteger -> Coef) -> %
--R exquo : (%,%) -> Union(%,"failed") if Coef has COMRING
--R multiplicative? : (%,PositiveInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit? : % -> Boolean if Coef has COMRING
--R unitCanonical : % -> % if Coef has COMRING
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has COMRING
--R
--E 21

)spool
)lisp (bye)
```


— **DirichletRing.help** —

```
====================================================================
DirichletRing examples
====================================================================

See Also:
o )show DirichletRing
```

———-

5.12.1 DirichletRing (DIRRING)



Exports:

0	1	?*?	?**?	?+?
?-?	-?	?=?	?^?	?.?
? =?	additive?	associates?	characteristic	coerce
exquo	hash	latex	multiplicative?	one?
recip	sample	subtractIfCan	unit?	unitCanonical
unitNormal	zero?	zeta		

— **domain DIRRING DirichletRing** —

```
)abbrev domain DIRRING DirichletRing
++ Author: Martin Rubey
++ Description: DirichletRing is the ring of arithmetical functions
++ with Dirichlet convolution as multiplication
DirichletRing(Coef: Ring):
            Exports == Implementation where

    PI ==> PositiveInteger
    FUN ==> PI -> Coef

    Exports ==> Join(Ring, Eltable(PI, Coef)) with
```

```
    if Coef has CommutativeRing then
        IntegralDomain

    if Coef has CommutativeRing then
        Algebra Coef

    coerce: FUN -> %
    coerce: % -> FUN
    coerce: Stream Coef -> %
    coerce: % -> Stream Coef

    zeta: constant -> %
      ++ zeta() returns the function which is constantly one

    multiplicative?: (%, PI) -> Boolean
      ++ multiplicative?(a, n) returns true if the first
      ++ n coefficients of a are multiplicative

    additive?: (%, PI) -> Boolean
      ++ additive?(a, n) returns true if the first
      ++ n coefficients of a are additive

  Implementation ==> add

      Rep := Record(function: FUN)

      per(f: Rep): % == f pretend %
      rep(a: %): Rep == a pretend Rep

      elt(a: %, n: PI): Coef ==
          f: FUN := (rep a).function
          f n

      coerce(a: %): FUN == (rep a).function

      coerce(f: FUN): % == per [f]

      indices: Stream Integer
              := integers(1)$StreamTaylorSeriesOperations(Integer)

      coerce(a: %): Stream Coef ==
          f: FUN := (rep a).function
          map((n: Integer): Coef +-> f(n::PI), indices)
             $StreamFunctions2(Integer, Coef)

      coerce(f: Stream Coef): % ==
          ((n: PI): Coef +-> f.(n::Integer))::%

      coerce(f: %): OutputForm == f::Stream Coef::OutputForm
```

```
1: % ==
    ((n: PI): Coef +-> (if one? n then 1$Coef else 0$Coef))::%

0: % ==
    ((n: PI): Coef +-> 0$Coef)::%

zeta: % ==
    ((n: PI): Coef +-> 1$Coef)::%

(f: %) + (g: %) ==
    ((n: PI): Coef +-> f(n)+g(n))::%

- (f: %) ==
    ((n: PI): Coef +-> -f(n))::%

(a: Integer) * (f: %) ==
    ((n: PI): Coef +-> a*f(n))::%

(a: Coef) * (f: %) ==
    ((n: PI): Coef +-> a*f(n))::%

import IntegerNumberTheoryFunctions

(f: %) * (g: %) ==
  conv := (n: PI): Coef +-> _
    reduce((a: Coef, b: Coef): Coef +-> a + b, _
      [f(d::PI) * g((n quo d)::PI) for d in divisors(n::Integer)], 0)
                $ListFunctions2(Coef, Coef)
  conv::%

unit?(a: %): Boolean == not (recip(a(1$PI))$Coef case "failed")

qrecip: (%, Coef, PI) -> Coef
qrecip(f: %, f1inv: Coef, n: PI): Coef ==
  if one? n then f1inv
  else
      -f1inv * reduce(_+, [f(d::PI) * qrecip(f, f1inv, (n quo d)::PI) _
                           for d in rest divisors(n)], 0) _
                    $ListFunctions2(Coef, Coef)

recip f ==
    if (f1inv := recip(f(1$PI))$Coef) case "failed" then "failed"
    else
        mp := (n: PI): Coef +-> qrecip(f, f1inv, n)

        mp::%::Union(%, "failed")

multiplicative?(a, n) ==
    for i in 2..n repeat
```

```
            fl := factors(factor i)$Factored(Integer)
            rl := [a.(((f.factor)::PI)**((f.exponent)::PI)) for f in fl]
            if a.(i::PI) ~= reduce((r:Coef, s:Coef):Coef +-> r*s, rl)
            then
                output(i::OutputForm)$OutputPackage
                output(rl::OutputForm)$OutputPackage
                return false
        true

    additive?(a, n) ==
        for i in 2..n repeat
            fl := factors(factor i)$Factored(Integer)
            rl := [a.(((f.factor)::PI)**((f.exponent)::PI)) for f in fl]
            if a.(i::PI) ~= reduce((r:Coef, s:Coef):Coef +-> r+s, rl)
            then
                output(i::OutputForm)$OutputPackage
                output(rl::OutputForm)$OutputPackage
                return false
        true
```

———-

— DIRRING.dotabb —

```
"DIRRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DIRRING"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"DIRRING" -> "FLAGG"
```

———-

5.13 domain DMP DistributedMultivariatePolynomial

— DistributedMultivariatePolynomial.input —

```
)set break resume
)sys rm -f DistributedMultivariatePolynomial.output
)spool DistributedMultivariatePolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 10
(d1,d2,d3) : DMP([z,y,x],FRAC INT)
--R
--R                                                              Type: Void
```

```
--E 1

--S 2 of 10
d1 := -4*z + 4*y**2*x + 16*x**2 + 1
--R
--R
--R                 2       2
--R   (2)  - 4z + 4y x + 16x  + 1
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 2

--S 3 of 10
d2 := 2*z*y**2 + 4*x + 1
--R
--R
--R            2
--R   (3)  2z y  + 4x + 1
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 3

--S 4 of 10
d3 := 2*z*x**2 - 2*y**2 - x
--R
--R
--R            2     2
--R   (4)  2z x  - 2y  - x
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 4

--S 5 of 10
groebner [d1,d2,d3]
--R
--R
--R   (5)
--R        1568  6   1264  5    6   4   182  3   2047  2    103      2857
--R   [z - ---- x  - ---- x  + --- x  + --- x  - ---- x  - ---- x - -----,
--R        2745       305      305      549       610      2745     10980
--R     2    112  6    84  5   1264  4    13  3    84  2   1772       2
--R    y  + ---- x  - --- x  - ---- x  - --- x  + --- x  + ---- x + ----,
--R         2745       305       305      549      305      2745     2745
--R     7   29  6   17  4   11  3    1  2   15     1
--R    x  + -- x  - -- x  - -- x  + -- x  + -- x + -]
--R          4      16       8      32      16     4
--R     Type: List(DistributedMultivariatePolynomial([z,y,x],Fraction(Integer)))
--E 5

--S 6 of 10
(n1,n2,n3) : HDMP([z,y,x],FRAC INT)
--R
--R                                                                  Type: Void
```

```
--E 6

--S 7 of 10
n1 := d1
--R
--R
--R          2       2
--R   (7)  4y x + 16x  - 4z + 1
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 7

--S 8 of 10
n2 := d2
--R
--R
--R            2
--R   (8)  2z y  + 4x + 1
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 8

--S 9 of 10
n3 := d3
--R
--R
--R            2     2
--R   (9)  2z x  - 2y  - x
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 9

--S 10 of 10
groebner [n1,n2,n3]
--R
--R
--R   (10)
--R     4     3   3  2   1     1   4   29  3   1  2   7        9     1
--R   [y  + 2x  - - x  + - z - -, x  + -- x  - - y  - - z x - -- x - -,
--R               2      2     8        4      8      4       16     4
--R       2        1   2      2       1     2    2   1
--R    z y  + 2x + -, y x + 4x  - z + -, z x  - y  - - x,
--R               2                 4             2
--R     2     2     2   1     3
--R    z  - 4y  + 2x  - - z - - x]
--R                     4     2
--RType: List(HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer)))
--E 10
)spool
)lisp (bye)
```

— DistributedMultivariatePolynomial.help —

```
====================================================================
MultivariatePolynomial
DistributedMultivariatePolynomial
HomogeneousDistributedMultivariatePolynomial
GeneralDistributedMultivariatePolynomial
====================================================================

DistributedMultivariatePolynomial which is abbreviated as DMP and
HomogeneousDistributedMultivariatePolynomial, which is abbreviated
as HDMP, are very similar to MultivariatePolynomial except that
they are represented and displayed in a non-recursive manner.

  (d1,d2,d3) : DMP([z,y,x],FRAC INT)
                     Type: Void

The constructor DMP orders its monomials lexicographically while
HDMP orders them by total order refined by reverse lexicographic
order.

  d1 := -4*z + 4*y**2*x + 16*x**2 + 1
            2       2
   - 4z + 4y x + 16x  + 1
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  d2 := 2*z*y**2 + 4*x + 1
       2
   2z y  + 4x + 1
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  d3 := 2*z*x**2 - 2*y**2 - x
       2     2
   2z x  - 2y  - x
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

These constructors are mostly used in Groebner basis calculations.

  groebner [d1,d2,d3]
        1568  6   1264  5    6   4   182  3   2047  2    103      2857
   [z - ---- x  - ---- x  + --- x  + --- x  - ---- x  - ---- x - -----,
        2745       305      305      549       610      2745     10980
     2    112  6    84  5   1264  4    13  3    84  2   1772       2
    y  + ---- x  - --- x  - ---- x  - --- x  + --- x  + ---- x + ----,
         2745      305       305      549      305      2745     2745
     7   29  6   17  4   11  3    1  2   15     1
    x  + -- x  - -- x  - -- x  + -- x  + -- x + -]
           4      16       8      32      16     4
       Type: List DistributedMultivariatePolynomial([z,y,x],Fraction Integer)
```

```
  (n1,n2,n3) : HDMP([z,y,x],FRAC INT)
                      Type: Void

  n1 := d1
     2       2
   4y x + 16x  - 4z + 1
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  n2 := d2
       2
   2z y  + 4x + 1
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  n3 := d3
       2     2
   2z x  - 2y  - x
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)
```

Note that we get a different Groebner basis when we use the HDMP polynomials, as expected.


```
  groebner [n1,n2,n3]
     4     3   3  2   1     1   4   29  3   1  2   7        9     1
   [y  + 2x  - - x  + - z - -, x  + -- x  - - y  - - z x - -- x - -,
              2      2     8        4      8      4       16     4
      2        1   2      2       1     2    2   1
    z y  + 2x + -, y x + 4x  - z + -, z x  - y  - - x,
               2                  4             2
     2     2     2   1     3
    z  - 4y  + 2x  - - z - - x]
                   4     2
       Type: List HomogeneousDistributedMultivariatePolynomial([z,y,x],
                                                          Fraction Integer)
```

GeneralDistributedMultivariatePolynomial is somewhat more flexible in the sense that as well as accepting a list of variables to specify the variable ordering, it also takes a predicate on exponent vectors to specify the term ordering. With this polynomial type the user can experiment with the effect of using completely arbitrary term orderings. This flexibility is mostly important for algorithms such as Groebner basis calculations which can be very sensitive to term ordering.

See Also:
o)help Polynomial
o)help UnivariatePolynomial
o)help MultivariatePolynomial
o)help HomogeneousDistributedMultivariatePolynomial
o)help GeneralDistributedMultivariatePolynomial
o)show DistributedMultivariatePolynomial

———-

5.13.1 DistributedMultivariatePolynomial (DMP)



See

⇒ “GeneralDistributedMultivariatePolynomial” (GDMP) 8.1.1 on page 1022
⇒ “HomogeneousDistributedMultivariatePolynomial” (HDMP) 9.10.1 on page 1149

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	convert	D
degree	differentiate	discriminant
eval	exquo	factor
factorPolynomial	factorSquareFreePolynomial	gcd
gcdPolynomial	ground	ground?
hash	isExpt	isPlus
isTimes	latex	lcm
leadingCoefficient	leadingMonomial	mainVariable
map	mapExponents	max
min	minimumDegree	monicDivide
monomial	monomial?	monomials
multivariate	numberOfMonomials	one?
patternMatch	pomopo!	prime?
primitiveMonomials	primitivePart	recip
reducedSystem	reductum	resultant
retract	retractIfCan	reorder
retract	solveLinearPolynomialEquation	sample
squareFree	squareFreePolynomial	squareFreePart
subtractIfCan	totalDegree	unit?
unitCanonical	unitNormal	univariate
variables	zero?	?*?
?**?	?+?	?-?
-?	?=?	?^?
?~=?	?/?	?<?
?<=?	?>?	?>=?

— domain DMP DistributedMultivariatePolynomial —

```
)abbrev domain DMP DistributedMultivariatePolynomial
++ Author: Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, degree, eval, coefficient, monomial, differentiate,
++ resultant, gcd, leadingCoefficient
++ Related Constructors: GeneralDistributedMultivariatePolynomial,
++ HomogeneousDistributedMultivariatePolynomial
++ Also See: Polynomial
++ AMS Classifications:
++ Keywords: polynomial, multivariate, distributed
++ References:
++ Description:
++ This type supports distributed multivariate polynomials
++ whose variables are from a user specified list of symbols.
++ The coefficient ring may be non commutative,
++ but the variables are assumed to commute.
```

```
++ The term ordering is lexicographic specified by the variable
++ list parameter with the most significant variable first in the list.

DistributedMultivariatePolynomial(vl,R): public == private where
  vl : List Symbol
  R  : Ring
  E   ==> DirectProduct(#vl,NonNegativeInteger)
  OV  ==> OrderedVariableList(vl)
  public == PolynomialCategory(R,E,OV) with
      reorder: (%,List Integer) -> %
        ++ reorder(p, perm) applies the permutation perm to the variables
        ++ in a polynomial and returns the new correctly ordered polynomial

  private ==
    GeneralDistributedMultivariatePolynomial(vl,R,E)
```

———-

— DMP.dotabb —

```
"DMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DMP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"DMP" -> "PFECAT"
"DMP" -> "DIRPCAT"
```

———-

5.14 domain DIV Divisor

— Divisor.input —

```
)set break resume
)sys rm -f Divisor.output
)spool Divisor.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Divisor
--R
--R Divisor(S: SetCategoryWithDegree)  is a domain constructor
--R Abbreviation for Divisor is DIV
```

```
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DIV
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Integer,S) -> %                ?*? : (Integer,%) -> %
--R ?*? : (%,Integer) -> %                ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?+? : (S,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                0 : () -> %
--R coefficient : (S,%) -> Integer        coerce : S -> %
--R coerce : % -> OutputForm              collect : % -> %
--R concat : (%,%) -> %                   degree : % -> Integer
--R divOfPole : % -> %                    divOfZero : % -> %
--R effective? : % -> Boolean             hash : % -> SingleInteger
--R incr : % -> %                         latex : % -> String
--R mapGen : ((S -> S),%) -> %            nthCoef : (%,Integer) -> Integer
--R nthFactor : (%,Integer) -> S          reductum : % -> %
--R retract : % -> S                      sample : () -> %
--R size : % -> NonNegativeInteger        split : % -> List(%)
--R supp : % -> List(S)                   suppOfPole : % -> List(S)
--R suppOfZero : % -> List(S)             zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R head : % -> Record(gen: S,exp: Integer)
--R highCommonTerms : (%,%) -> % if Integer has OAMON
--R mapCoef : ((Integer -> Integer),%) -> %
--R retractIfCan : % -> Union(S,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R terms : % -> List(Record(gen: S,exp: Integer))
--R
--E 1

)spool
)lisp (bye)
```

———-


— Divisor.help —

```
=====================================================================
Divisor examples
=====================================================================

See Also:
o )show Divisor
```

———-

5.14.1 Divisor (DIV)



Exports:

0	-?	?*?	?+?
?-?	?<=?	?=?	?~=?
coefficient	coerce	collect	concat
degree	divOfPole	divOfZero	effective?
hash	head	highCommonTerms	incr
latex	mapCoef	mapGen	nthCoef
nthFactor	reductum	retract	retractIfCan
sample	size	split	subtractIfCan
supp	suppOfPole	suppOfZero	terms
zero?			

— domain DIV Divisor —

```
)abbrev domain DIV Divisor
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is part of the PAFF package
Divisor(S:SetCategoryWithDegree):Exports == Implementation where

  PT      ==> Record(gen:S,exp: Integer)
  INT     ==> Integer
  BOOLEAN ==> Boolean
  LIST    ==> List

  Exports == DivisorCategory(S) with

    head: % -> PT

    reductum: % -> %
```

```
Implementation == List PT add

  Rep := List PT

  incr(d)==
    [ [ pt.gen , pt.exp + 1 ] for pt in d ]

  inOut: PT -> OutputForm

  inOut(pp)==
    one?(pp.exp) => pp.gen :: OutputForm
    bl:OutputForm:= " " ::OutputForm
    (pp.exp :: OutputForm) * hconcat(bl,pp.gen :: OutputForm)

  coerce(d:%):OutputForm==
    zero?(d) => ("0"::OutputForm)
    ll:List OutputForm:=[inOut df  for df in d]
    reduce("+",ll)

  reductum(d)==
    zero?(d) => d
    dl:Rep:= d pretend Rep
    dlr := rest dl
    empty?(dlr) => 0
    dlr

  head(d)==
    zero?(d) => error "Cannot take head of zero"
    dl:Rep:= d pretend Rep
    first dl

  coerce(s:S) == [[s,1]$PT]::%

  split(a) ==
    zero?(a) => []
    [[r]::% for r in a]

  coefficient(s,a)==
    r:INT:=0
    for pt in terms(a) repeat
      if pt.gen=s then
        r:=pt.exp
    r

  terms(a)==a::Rep

  0==empty()$Rep

  supp(a)==
```

```
    aa:=terms(collect(a))
    [p.gen for p in aa | ^zero?(p.exp)]

  suppOfZero(a)==
    aa:=terms(collect(a))
    [p.gen for p in aa | (p.exp) > 0 ]

  suppOfPole(a)==
    aa:=terms(collect(a))
    [p.gen for p in aa | p.exp < 0 ]

  divOfZero(a)==
    aa:=terms(collect(a))
    [p for p in aa | (p.exp) > 0 ]::%

  divOfPole(a)==
    aa:=terms(collect(a))
    [p for p in aa | p.exp < 0 ]::%

  zero?(a)==
    ((collect(a)::Rep)=empty()$Rep)::BOOLEAN

  collect(d)==
    a:=d::Rep
    empty?(a) => 0
    t:Rep:=empty()
    ff:PT:=first(a)
    one?(#(a)) =>
      if zero?(ff.exp) then
        t::%
      else
        a::%
    inList?:Boolean:=false()
    newC:INT
    restred:=terms(collect((rest(a)::%)))
    zero?(ff.exp) =>
      restred::%
    for bb in restred repeat
      b:=bb::PT
      if b.gen=ff.gen then
        newC:=b.exp+ff.exp
        if ^zero?(newC) then
          t:=concat(t,[b.gen,newC]$PT)
        inList?:=true()
      else
        t:=concat(t,b)
    if ^inList? then
      t:=cons(ff,t)
    t::%
```

```
    a:% + b:% ==
      collect(concat(a pretend Rep,b pretend Rep))

    a:% - b:% ==
      a + (-1)*b

    -a:% == (-1)*a

    n:INT * a:% ==
      zero?(n) => 0
      t:Rep:=empty()
      for p in a pretend Rep repeat
        t:=concat(t,[ p.gen, n*p.exp]$PT)
      t::%

    a:% <= b:% ==
      bma:= b - a
      effective? bma => true
      false

    effective?(a)== empty?(suppOfPole(a))

    degree(d:%):Integer==
      reduce("+",[(p.exp * degree(p.gen)) for p in d @ Rep],0$INT)
```

———-

— DIV.dotabb —

```
"DIV" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DIV",shape=ellipse]
"DIVCAT" [color=lightblue,href="bookvol10.2.pdf#nameddest=DIVCAT"];
"FLAGG" [color=lightblue,href="bookvol10.2.pdf#nameddest=FLAGG"];
"DIV" -> "DIVCAT"
"DIV" -> "FLAGG"
```

———-

5.15 domain DFLOAT DoubleFloat

Greg Vanuxem has added some functionality to allow the user to modify the printed format of floating point numbers. The format of the numbers follows the common lisp format specification for floats. First we include Greg's email to show the use of this feature:

```
PS: For those who use the Doublefloat domain
    there is an another (undocumented) patch that adds a
    lisp format to the DoubleFloat output routine. Copy
```

```
    int/algebra/DFLOAT.spad to your working directory,
    patch it, compile it and ")lib" it when necessary.


(1) -> )boot $useBFasDefault:=false

(SPADLET |$useBFasDefault| NIL)
Value = NIL
(1) -> a:= matrix [ [0.5978,0.2356], [0.4512,0.2355] ]

        +      0.5978               0.2356       +
   (1)  |                                        |
        +0.45119999999999999  0.23549999999999999+
                              Type: Matrix DoubleFloat
(2) -> )lib DFLOAT
   DoubleFloat is now explicitly exposed in frame initial
   DoubleFloat will be automatically loaded when needed
from /home/greg/Axiom/DFLOAT.nrlib/code
(2) -> doubleFloatFormat("~,4,,F")

   (2)  "~G"
                              Type: String
(3) -> a

        +0.5978  0.2356+
   (3)  |              |
        +0.4512  0.2355+
                              Type: Matrix DoubleFloat
```

So it is clear that he has added a new function called `doubleFloatFormat` which takes a string argument that specifies the common lisp format control string (¨~,4,,F¨). For reference we quote from the common lisp manual [**?**]. On page 582 we find:

> A format directive consists of a tilde (~), optional prefix parameters separated by commas, optional colon (:) and at-sign (@) modifiers, and a single character indicating what kind of directive this is. The alphabetic case of the directive character is ignored. The prefix parameters are generally integers, notated as optionally signed decimal numbers.
>
> X3J13 voted in June 1987 (80) to specify that if both colon and at-sign modifiers are present, they may appear in either order; thus ~:@R and ~@:R mean the same thing. However, it is traditional to put the colon first, and all examples in the book put colon before at-signs.

On page 588 we find:

> ~F

Fixed-format floating-point. The next *arg* is printed as a floating point number.

The full form is ~*w*,*d*,*k*,*overfowchar*,*padchar*F. The parameter *w* is the width of the filed to be printed; *d* is the number of digits to print after the decimal point; *k* is a scale factor that defaults to zero.

Exactly *w* characters will be output. First, leading copies of the character *padchar* (which defaults to a space) are printed, if necessary, to pad the field on the left. If the *arg* is negative, then a minus sign is printed; if the *arg* is not negative, then a plus signed is printed if and only if the @ modifier was specified. Then a sequence of digits, containing a single embedded decimal point, is printed; this represents the magnitude of the value of *arg* times 10^k, rounded to *d* fractional digits. (When rounding up and rounding down would produce printed values equidistant from the scaled value of *arg*, then the implementation is free to use either one. For example, printing the argument 6.375 using the format ~4.2F may correctly produce either 6.37 or 6.38.) Leading zeros are not permitted, except that a single zero digit is output before the decimal point if the printed value is less than 1, and this single zero digit is not output after all if $w = d + 1$.

If it is impossible to print the value in the required format in the field of width *w*, then one of two actions is taken. If the parameter *overflowchar* is specified, then *w* copies of that parameter are printed instead of the scaled value of *arg*. If the *overflowchar* parameter is omitted, then the scaled value is printed using more than *w* characters, as many more as may be needed.

If the *w* parameter is omitted, then the field is of variable width. In effect, a value is chosen for *w* in such a way that no leading pad characters need to be printed and exactly *d* characters will follow the decimal point. For example, the directive ~,2F will print exactly two digits after the decimal point and as many as necessary before the decimal point.

If the parameter *d* is omitted, then there is no constraint on the number of digits to appear after the decimal point. A value is chosen for *d* in such a way that as many digits as possible may be printed subject to the width constraint imposed by the parameter *w* and the constraint that no trailing zero digits may appear in the fraction, except that if the fraction to be printed is zero, then a single zero digit should appear after the decimal point if permitted by the width constraint.

If both *w* and *d* are omitted, then the effect is to print the value using ordinary free-format output; `prin1` uses this format for any number whose magnitude is either zero or between 10^{-3} (inclusive) and 10^7 (exclusive).

If *w* is omitted, then if the magnitude of *arg* is so large (or, if *d* is also omitted, so small) that more than 100 digits would have to be printed, then an implementation is free, at its discretion, to print the number using exponential notation instead, as if by the directive ~E (with all parameters of ~E defaulted, not taking their valued from the ~F directive).

If *arg* is a rational number, then it is coerced to be a `single-float` and then printed. (Alternatively, an implementation is permitted to process a rational number by any other method that has essentially the same behavior but avoids

such hazards as loss of precision or overflow because of the coercion. However, note that if *w* and *d* are unspecified and the number has no exact decimal representation, for example 1/3, some precision cutoff must be chosen by the implementation; only a finite number of digits may be printed.)

If *arg* is a complex number or some non-numeric object, then it is printed using the format directive ~*w*D, thereby printing it in decimal radix and a minimum field width of *w*. (If it is desired to print each of the real part and imaginary part of a complex number using a ~F directive, then this must be done explicitly with two ~F directives and code to extract the two parts of the complex number.)

A key difficulty is creating test suites which generate DoubleFloats. We need to be bit-exact in the results. This can be achieved using the common lisp `integer-decode-float` function. We cover that function in two different ways, with `machineFraction` which translates the results into an Axiom **Fraction(Integer)** and `integerDecode` which just returns a list of the multiple values from the `integer-decode-float` function.

— DoubleFloat.input —

```
)set break resume
)sys rm -f DoubleFloat.output
)spool DoubleFloat.output
)set message test on
)set message auto off
)clear all

--S 1 of 13
2.71828
--R
--R
--R   (1)  2.71828
--R                                                          Type: Float
--E 1

--S 2 of 13
2.71828@DoubleFloat
--R
--R
--R   (2)  2.71828
--R                                                    Type: DoubleFloat
--E 2

--S 3 of 13
2.71828 :: DoubleFloat
--R
--R
--R   (3)  2.71828
--R                                                    Type: DoubleFloat
--E 3
```

```
--S 4 of 13
eApprox : DoubleFloat := 2.71828
--R
--R
--R   (4)  2.71828
--R                                                          Type: DoubleFloat
--E 4

--S 5 of 13
avg : List DoubleFloat -> DoubleFloat
--R
--R                                                                Type: Void
--E 5

--S 6 of 13
avg l ==
  empty? l => 0 :: DoubleFloat
  reduce(_+,l) / #l
--R
--R                                                                Type: Void
--E 6

--S 7 of 13
avg []
--R
--R   Compiling function avg with type List(DoubleFloat) -> DoubleFloat
--R
--R   (7)  0.
--R                                                          Type: DoubleFloat
--E 7

--S 8 of 13
avg [3.4,9.7,-6.8]
--R
--R
--R   (8)  2.0999999999999996
--R                                                          Type: DoubleFloat
--E 8

--S 9 of 13
cos(3.1415926)$DoubleFloat
--R
--R
--R   (9)  - 0.99999999999999856
--R                                                          Type: DoubleFloat
--E 9

--S 10 of 13
cos(3.1415926 :: DoubleFloat)
```

```
--R
--R
--R   (10)  - 0.99999999999999856
--R                                                        Type: DoubleFloat
--E 10

--S 11 of 13
a:DFLOAT := -1.0/3.0
--R
--R
--R   (11)  - 0.33333333333333337
--R                                                        Type: DoubleFloat
--E 11

--S 12 of 13
integerDecode a
--R
--R
--R   (12)  [6004799503160662,- 54,- 1]
--R                                                   Type: List(Integer)
--E 12

--S 13 of 13
machineFraction a
--R
--R
--R           3002399751580331
--R   (13)  - ----------------
--R           9007199254740992
--R                                               Type: Fraction(Integer)
--E 13

)spool
)lisp (bye)
```

———-

— DoubleFloat.help —

```
====================================================================
DoubleFloat examples
====================================================================

Axiom provides two kinds of floating point numbers.  The domain Float
(abbreviation FLOAT) implements a model of arbitrary precision
floating point numbers.  The domain DoubleFloat (abbreviation DFLOAT)
is intended to make available hardware floating point arithmetic in
Axiom.  The actual model of floating point DoubleFloat that provides
```

```
is system-dependent.  For example, on the IBM system 370 Axiom uses
IBM double precision which has fourteen hexadecimal digits of
precision or roughly sixteen decimal digits.  Arbitrary precision
floats allow the user to specify the precision at which arithmetic
operations are computed.  Although this is an attractive facility, it
comes at a cost. Arbitrary-precision floating-point arithmetic
typically takes twenty to two hundred times more time than hardware
floating point.

The usual arithmetic and elementary functions are available for
DoubleFloat.  By default, floating point numbers that you enter into
Axiom are of type Float.

  2.71828
   2.71828
                      Type: Float

You must therefore tell Axiom that you want to use DoubleFloat values
and operations.  The following are some conservative guidelines for
getting Axiom to use DoubleFloat.

To get a value of type DoubleFloat, use a target with @, ...

  2.71828@DoubleFloat
   2.71828
                      Type: DoubleFloat

a conversion, ...

  2.71828 :: DoubleFloat
   2.71828
                      Type: DoubleFloat

or an assignment to a declared variable.  It is more efficient if you
use a target rather than an explicit or implicit conversion.

  eApprox : DoubleFloat := 2.71828
   2.71828
                      Type: DoubleFloat

You also need to declare functions that work with DoubleFloat.

  avg : List DoubleFloat -> DoubleFloat
                      Type: Void

  avg l ==
    empty? l => 0 :: DoubleFloat
    reduce(_+,l) / #l
                      Type: Void
```

```
  avg []
   0.
                      Type: DoubleFloat

  avg [3.4,9.7,-6.8]
   2.1000000000000001
                      Type: DoubleFloat
```

Use package-calling for operations from DoubleFloat unless the
arguments themselves are already of type DoubleFloat.

```
  cos(3.1415926)$DoubleFloat
   -0.99999999999999856
                      Type: DoubleFloat

  cos(3.1415926 :: DoubleFloat)
   -0.99999999999999856
                      Type: DoubleFloat
```

By far, the most common usage of DoubleFloat is for functions to be
graphed.

You can get the exact machine-specific bits of a DoubleFloat in two ways.
The first is to use the integerDecode function to break the DoubleFloat
into components.

```
  a := -1.0/3.0

    -0.33333333333333331

  integerDecode a

    [6004799503160661,- 54,- 1]
```

This is the mantissa, exact to 54 bits, the power of 2, and the sign.
Thus it is:

```
    6004799503160661 * 2^-54
```

You can get the same information as a fraction with


```
   machineFraction a

     6004799503160661
  - ------------------
    18014398509481984
```

where the denominator 18014398509481984 is 2^54

```
See Also:
o )help Float
o )show DoubleFloat
```

5.15.1 DoubleFloat (DFLOAT)



Exports:

0	1	abs	acos
acosh	acot	acoth	acsc
acsch	airyAi	airyBi	asec
asech	asin	asinh	associates?
atan	atanh	base	besselI
besselJ	besselK	besselY	Beta
bits	ceiling	characteristic	coerce
convert	cos	cosh	cot
coth	csc	csch	D
decreasePrecision	differentiate	digamma	digits
divide	doubleFloatFormat	euclideanSize	exp
expressIdealMember	exp1	exponent	exquo
extendedEuclidean	factor	float	floor
fractionPart	Gamma	gcd	gcdPolynomial
hash	increasePrecision	integerDecode	inv
latex	lcm	log	log10
log2	machineFraction	mantissa	max
min	multiEuclidean	negative?	norm
nthRoot	OMwrite	one?	order
patternMatch	pi	polygamma	positive?
precision	prime?	principalIdeal	rationalApproximation
recip	retract	retractIfCan	round
sample	sec	sech	sign
sin	sinh	sizeLess?	sqrt
squareFree	squareFreePart	subtractIfCan	tan
tanh	truncate	unit?	unitCanonical
unitNormal	wholePart	zero?	?*?
?**?	?+?	?-?	-?
?/?	?<?	?<=?	?=?
?>?	?>=?	?^?	?quo?
?rem?	?~=?		

— domain DFLOAT DoubleFloat —

```
)abbrev domain DFLOAT DoubleFloat
++ Author: Michael Monagan
++ Date Created:
++   January 1988
++ Change History:
++ Basic Operations: exp1, hash, log2, log10, rationalApproximation, / , **
++ Related Constructors:
++ Keywords: small float
++ Description:
++ \spadtype{DoubleFloat} is intended to make accessible
++ hardware floating point arithmetic in Axiom, either native double
++ precision, or IEEE. On most machines, there will be hardware support for
```

```
++ the arithmetic operations: ++ +, *, / and possibly also the
++ sqrt operation.
++ The operations exp, log, sin, cos, atan are normally coded in
++ software based on minimax polynomial/rational approximations.
++
++ Some general comments about the accuracy of the operations:
++ the operations +, *, / and sqrt are expected to be fully accurate.
++ The operations exp, log, sin, cos and atan are not expected to be
++ fully accurate.  In particular, sin and cos
++ will lose all precision for large arguments.
++
++ The Float domain provides an alternative to the DoubleFloat domain.
++ It provides an arbitrary precision model of floating point arithmetic.
++ This means that accuracy problems like those above are eliminated
++ by increasing the working precision where necessary.  \spadtype{Float}
++ provides some special functions such as erf, the error function
++ in addition to the elementary functions.  The disadvantage of Float is that
++ it is much more expensive than small floats when the latter can be used.

DoubleFloat(): Join(FloatingPointSystem, DifferentialRing, OpenMath,
   TranscendentalFunctionCategory, SpecialFunctionCategory, _
   ConvertibleTo InputForm) with
      _/   : (%, Integer) -> %
        ++ x / i computes the division from x by an integer i.
      _*_* : (%,%) -> %
        ++ x ** y returns the yth power of x (equal to \spad{exp(y log x)}).
      exp1 : () -> %
        ++ exp1() returns the natural log base \spad{2.718281828...}.
      hash : % -> Integer
        ++ hash(x) returns the hash key for x
      log2 :  % -> %
        ++ log2(x) computes the logarithm with base 2 for x.
      log10: % -> %
        ++ log10(x) computes the logarithm with base 10 for x.
      atan : (%,%) -> %
        ++ atan(x,y) computes the arc tangent from x with phase y.
      Gamma: % -> %
        ++ Gamma(x) is the Euler Gamma function.
      Beta : (%,%) -> %
        ++ Beta(x,y) is \spad{Gamma(x) * Gamma(y)/Gamma(x+y)}.
      doubleFloatFormat : String -> String
        ++ change the output format for doublefloats using lisp format strings
      rationalApproximation: (%, NonNegativeInteger) -> Fraction Integer
        ++ rationalApproximation(f, n) computes a rational approximation
        ++ r to f with relative error \spad{< 10**(-n)}.
      rationalApproximation: (%, NonNegativeInteger, NonNegativeInteger) -> _
            Fraction Integer
        ++ rationalApproximation(f, n, b) computes a rational
        ++ approximation r to f with relative error \spad{< b**(-n)}
        ++ (that is, \spad{|(r-f)/f| < b**(-n)}).
```

```
      machineFraction : % -> Fraction Integer
        ++ machineFraction(x) returns a bit-exact fraction of the machine
        ++ floating point number using the common lisp integer-decode-float
        ++ function. See Steele, ISBN 0-13-152414-3 p354
        ++ This function can be used to print results which do not depend
        ++ on binary-to-decimal conversions
        ++
        ++X a:DFLOAT:=-1.0/3.0
        ++X machineFraction a
      integerDecode : % -> List Integer
        ++ integerDecode(x) returns the multiple values of the  common
        ++ lisp integer-decode-float function.
        ++ See Steele, ISBN 0-13-152414-3 p354. This function can be used
        ++ to ensure that the results are bit-exact and do not depend on
        ++ the binary-to-decimal conversions.
        ++
        ++X a:DFLOAT:=-1.0/3.0
        ++X integerDecode a

== add
  format: String := "~G"
  MER ==> Record(MANTISSA:Integer,EXPONENT:Integer)

  manexp: % -> MER

  doubleFloatFormat(s:String): String ==
    ss: String := format
    format := s
    ss

  OMwrite(x: %): String ==
    s: String := ""
    sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
    dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
    OMputObject(dev)
    OMputFloat(dev, convert x)
    OMputEndObject(dev)
    OMclose(dev)
    s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
    s

  OMwrite(x: %, wholeObj: Boolean): String ==
    s: String := ""
    sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
    dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
    if wholeObj then
      OMputObject(dev)
    OMputFloat(dev, convert x)
    if wholeObj then
      OMputEndObject(dev)
```

```
    OMclose(dev)
    s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
    s

  OMwrite(dev: OpenMathDevice, x: %): Void ==
    OMputObject(dev)
    OMputFloat(dev, convert x)
    OMputEndObject(dev)

  OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
    if wholeObj then
      OMputObject(dev)
    OMputFloat(dev, convert x)
    if wholeObj then
      OMputEndObject(dev)

  checkComplex(x:%):% == C_-TO_-R(x)$Lisp
  -- In AKCL we used to have to make the arguments to ASIN ACOS ACOSH ATANH
  -- complex to get the correct behaviour.
  --makeComplex(x: %):% == COMPLEX(x, 0$%)$Lisp

  machineFraction(df:%):Fraction(Integer) ==
    numer:Integer:=INTEGER_-DECODE_-FLOAT_-NUMERATOR(df)$Lisp
    denom:Integer:=INTEGER_-DECODE_-FLOAT_-DENOMINATOR(df)$Lisp
    sign:Integer:=INTEGER_-DECODE_-FLOAT_-SIGN(df)$Lisp
    sign*numer/denom

  integerDecode(df:%):List(Integer) ==
    numer:Integer:=INTEGER_-DECODE_-FLOAT_-NUMERATOR(df)$Lisp
    exp:Integer:=INTEGER_-DECODE_-FLOAT_-EXPONENT(df)$Lisp
    sign:Integer:=INTEGER_-DECODE_-FLOAT_-SIGN(df)$Lisp
    [numer,exp,sign]

  base()           == FLOAT_-RADIX(0$%)$Lisp
  mantissa x       == manexp(x).MANTISSA
  exponent x       == manexp(x).EXPONENT
  precision()      == FLOAT_-DIGITS(0$%)$Lisp
  bits()           ==
    base() = 2 => precision()
    base() = 16 => 4*precision()
    wholePart(precision()*log2(base()::%))::PositiveInteger
  max()            == MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp
  min()            == MOST_-NEGATIVE_-DOUBLE_-FLOAT$Lisp
  order(a) == precision() + exponent a - 1
  0                == FLOAT(0$Lisp,MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp)$Lisp
  1                == FLOAT(1$Lisp,MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp)$Lisp
  -- rational approximation to e accurate to 23 digits
  exp1()  == FLOAT(534625820200,MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp)$Lisp / _
             FLOAT(196677847971,MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp)$Lisp
  pi()    == FLOAT(PI$Lisp,MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp)$Lisp
```

```
coerce(x:%):OutputForm ==
  x >= 0 => message(FORMAT(NIL$Lisp,format,x)$Lisp pretend String)
  - (message(FORMAT(NIL$Lisp,format,-x)$Lisp pretend String))
convert(x:%):InputForm == convert(x pretend DoubleFloat)$InputForm
x < y            == DFLESSTHAN(x,y)$Lisp
- x             == DFUNARYMINUS(x)$Lisp
x + y            == DFADD(x,y)$Lisp
x:% - y:%        == DFSUBTRACT(x,y)$Lisp
x:% * y:%        == DFMULTIPLY(x,y)$Lisp
i:Integer * x:%  == DFINTEGERMULTIPLY(i,x)$Lisp
max(x,y)         == DFMAX(x,y)$Lisp
min(x,y)         == DFMIN(x,y)$Lisp
x = y            == DFEQL(x,y)$Lisp
x:% / i:Integer  == DFINTEGERDIVIDE(x,i)$Lisp
sqrt x           == checkComplex DFSQRT(x)$Lisp
log10 x          == checkComplex DFLOG(x,10)$Lisp
x:% ** i:Integer == DFINTEGEREXPT(x,i)$Lisp
x:% ** y:%       == checkComplex DFEXPT(x,y)$Lisp
coerce(i:Integer):% == FLOAT(i,MOST_-POSITIVE_-DOUBLE_-FLOAT$Lisp)$Lisp
exp x            == DFEXP(x)$Lisp
log x            == checkComplex DFLOGE(x)$Lisp
log2 x           == checkComplex DFLOG(x,2)$Lisp
sin x            == DFSIN(x)$Lisp
cos x            == DFCOS(x)$Lisp
tan x            == DFTAN(x)$Lisp
cot x            == COT(x)$Lisp
sec x            == SEC(x)$Lisp
csc x            == CSC(x)$Lisp
asin x           == checkComplex DFASIN(x)$Lisp -- can be complex
acos x           == checkComplex DFACOS(x)$Lisp -- can be complex
atan x           == DFATAN(x)$Lisp
acsc x           == checkComplex ACSC(x)$Lisp
acot x           == ACOT(x)$Lisp
asec x           == checkComplex ASEC(x)$Lisp
sinh x           == SINH(x)$Lisp
cosh x           == COSH(x)$Lisp
tanh x           == TANH(x)$Lisp
csch x           == CSCH(x)$Lisp
coth x           == COTH(x)$Lisp
sech x           == SECH(x)$Lisp
asinh x          == DFASINH(x)$Lisp
acosh x          == checkComplex DFACOSH(x)$Lisp -- can be complex
atanh x          == checkComplex DFATANH(x)$Lisp -- can be complex
acsch x          == ACSCH(x)$Lisp
acoth x          == checkComplex ACOTH(x)$Lisp
asech x          == checkComplex ASECH(x)$Lisp
x:% / y:%        == DFDIVIDE(x,y)$Lisp
negative? x      == DFMINUSP(x)$Lisp
zero? x          == ZEROP(x)$Lisp
hash x           == HASHEQ(x)$Lisp
```

```
   recip(x)         == (zero? x => "failed"; 1 / x)
   differentiate x  == 0

   SFSFUN           ==> DoubleFloatSpecialFunctions()
   sfx              ==> x pretend DoubleFloat
   sfy              ==> y pretend DoubleFloat
   airyAi x         == airyAi(sfx)$SFSFUN pretend %
   airyBi x         == airyBi(sfx)$SFSFUN pretend %
   besselI(x,y)     == besselI(sfx,sfy)$SFSFUN pretend %
   besselJ(x,y)     == besselJ(sfx,sfy)$SFSFUN pretend %
   besselK(x,y)     == besselK(sfx,sfy)$SFSFUN pretend %
   besselY(x,y)     == besselY(sfx,sfy)$SFSFUN pretend %
   Beta(x,y)        == Beta(sfx,sfy)$SFSFUN pretend %
   digamma x        == digamma(sfx)$SFSFUN pretend %
   Gamma x          == Gamma(sfx)$SFSFUN pretend %
-- not implemented in SFSFUN
--   Gamma(x,y)       == Gamma(sfx,sfy)$SFSFUN pretend %
   polygamma(x,y)   ==
       if (n := retractIfCan(x:%):Union(Integer, "failed")) case Integer _
          and n >= 0
       then polygamma(n::Integer::NonNegativeInteger,sfy)$SFSFUN pretend %
       else error "polygamma: first argument should be a nonnegative integer"

   wholePart x            == TRUNCATE(x)$Lisp
   float(ma,ex,b)   == ma*(b::%)**ex
   convert(x:%):DoubleFloat == x pretend DoubleFloat
   convert(x:%):Float == convert(x pretend DoubleFloat)$Float
   rationalApproximation(x, d) == rationalApproximation(x, d, 10)

   atan(x,y) ==
      x = 0 =>
         y > 0 => pi()/2
         y < 0 => -pi()/2
         0
      -- Only count on first quadrant being on principal branch.
      theta := atan abs(y/x)
      if x < 0 then theta := pi() - theta
      if y < 0 then theta := - theta
      theta

   retract(x:%):Fraction(Integer) ==
     rationalApproximation(x, (precision() - 1)::NonNegativeInteger, base())

   retractIfCan(x:%):Union(Fraction Integer, "failed") ==
     rationalApproximation(x, (precision() - 1)::NonNegativeInteger, base())

   retract(x:%):Integer ==
     x = ((n := wholePart x)::%) => n
     error "Not an integer"
```

```
   retractIfCan(x:%):Union(Integer, "failed") ==
     x = ((n := wholePart x)::%) => n
     "failed"

   sign(x) == retract FLOAT_-SIGN(x,1)$Lisp

   abs x   == FLOAT_-SIGN(1,x)$Lisp

   manexp(x) ==
      zero? x => [0,0]
      s := sign x; x := abs x
      if x > max()$% then return [s*mantissa(max())+1,exponent max()]
      me:Record(man:%,exp:Integer) := MANEXP(x)$Lisp
      two53:= base()**precision()
      [s*wholePart(two53 * me.man ),me.exp-precision()]

-- rationalApproximation(y,d,b) ==
--    this is the quotient remainder algorithm (requires wholePart operation)
--    x := y
--    if b < 2 then error "base must be > 1"
--    tol := (b::%)**d
--    p0,p1,q0,q1 : Integer
--    p0 := 0; p1 := 1; q0 := 1; q1 := 0
--    repeat
--       a := wholePart x
--       x := fractionPart x
--       p2 := p0+a*p1
--       q2 := q0+a*q1
--       if x = 0 or tol*abs(q2*y-(p2::%)) < abs(q2*y) then
--          return (p2/q2)
--       (p0,p1) := (p1,p2)
--       (q0,q1) := (q1,q2)
--       x := 1/x

   rationalApproximation(f,d,b) ==
      -- this algorithm expresses f as n / d where d = BASE ** k
      -- then all arithmetic operations are done over the integers
      (nu, ex) := manexp f
      BASE := base()
      ex >= 0 => (nu * BASE ** (ex::NonNegativeInteger))::Fraction(Integer)
      de :Integer := BASE**((-ex)::NonNegativeInteger)
      b < 2 => error "base must be > 1"
      tol := b**d
      s := nu; t := de
      p0:Integer := 0; p1:Integer := 1; q0:Integer := 1; q1:Integer := 0
      repeat
         (q,r) := divide(s, t)
         p2 := q*p1+p0
         q2 := q*q1+q0
         r = 0 or tol*abs(nu*q2-de*p2) < de*abs(p2) => return(p2/q2)
```

```
         (p0,p1) := (p1,p2)
         (q0,q1) := (q1,q2)
         (s,t) := (t,r)

   x:% ** r:Fraction Integer ==
      zero? x =>
         zero? r => error "0**0 is undefined"
         negative? r => error "division by 0"
         0
--      zero? r or one? x => 1
      zero? r or (x = 1) => 1
--      one?  r => x
      (r = 1) => x
      n := numer r
      d := denom r
      negative? x =>
         odd? d =>
            odd? n => return -((-x)**r)
            return ((-x)**r)
         error "negative root"
      d = 2 => sqrt(x) ** n
      x ** (n::% / d::%)
```

———-

— DFLOAT.dotabb —

```
"DFLOAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DFLOAT",
          shape=ellipse]
"FRAC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FRAC"]
"DFLOAT" -> "FRAC"
```

———-

5.16 domain DFMAT DoubleFloatMatrix

— DoubleFloatMatrix.input —

```
)set break resume
)sys rm -f DoubleFloatMatrix.output
)spool DoubleFloatMatrix.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 6
)show DoubleFloatMatrix
--R
--R DoubleFloatMatrix  is a domain constructor
--R Abbreviation for DoubleFloatMatrix is DFMAT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DFMAT
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,%) -> %               ?*? : (%,DoubleFloat) -> %
--R ?*? : (DoubleFloat,%) -> %           ?*? : (%,%) -> %
--R ?+? : (%,%) -> %                     -? : % -> %
--R ?-? : (%,%) -> %                     antisymmetric? : % -> Boolean
--R coerce : DoubleFloatVector -> %      copy : % -> %
--R diagonal? : % -> Boolean             diagonalMatrix : List(%) -> %
--R empty : () -> %                      empty? : % -> Boolean
--R eq? : (%,%) -> Boolean               fill! : (%,DoubleFloat) -> %
--R horizConcat : (%,%) -> %             maxColIndex : % -> Integer
--R maxRowIndex : % -> Integer           minColIndex : % -> Integer
--R minRowIndex : % -> Integer           ncols : % -> NonNegativeInteger
--R nrows : % -> NonNegativeInteger      parts : % -> List(DoubleFloat)
--R qnew : (Integer,Integer) -> %        sample : () -> %
--R square? : % -> Boolean               squareTop : % -> %
--R symmetric? : % -> Boolean            transpose : % -> %
--R vertConcat : (%,%) -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (DoubleFloatVector,%) -> DoubleFloatVector
--R ?*? : (%,DoubleFloatVector) -> DoubleFloatVector
--R ?**? : (%,Integer) -> % if DoubleFloat has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,DoubleFloat) -> % if DoubleFloat has FIELD
--R ?=? : (%,%) -> Boolean if DoubleFloat has SETCAT
--R any? : ((DoubleFloat -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if DoubleFloat has SETCAT
--R column : (%,Integer) -> DoubleFloatVector
--R columnSpace : % -> List(DoubleFloatVector) if DoubleFloat has EUCDOM
--R count : (DoubleFloat,%) -> NonNegativeInteger if $ has finiteAggregate and DoubleFloat has SETCAT
--R count : ((DoubleFloat -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R determinant : % -> DoubleFloat if DoubleFloat has commutative(*)
--R diagonalMatrix : List(DoubleFloat) -> %
--R elt : (%,List(Integer),List(Integer)) -> %
--R elt : (%,Integer,Integer,DoubleFloat) -> DoubleFloat
--R elt : (%,Integer,Integer) -> DoubleFloat
--R eval : (%,List(DoubleFloat),List(DoubleFloat)) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat ha
--R eval : (%,DoubleFloat,DoubleFloat) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat has SETCAT
--R eval : (%,Equation(DoubleFloat)) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat has SETCAT
--R eval : (%,List(Equation(DoubleFloat))) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat has SETCA
--R every? : ((DoubleFloat -> Boolean),%) -> Boolean if $ has finiteAggregate
--R exquo : (%,DoubleFloat) -> Union(%,"failed") if DoubleFloat has INTDOM
```

```
--R hash : % -> SingleInteger if DoubleFloat has SETCAT
--R inverse : % -> Union(%,"failed") if DoubleFloat has FIELD
--R latex : % -> String if DoubleFloat has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R listOfLists : % -> List(List(DoubleFloat))
--R map : (((DoubleFloat,DoubleFloat) -> DoubleFloat),%,%,DoubleFloat) -> %
--R map : (((DoubleFloat,DoubleFloat) -> DoubleFloat),%,%) -> %
--R map : ((DoubleFloat -> DoubleFloat),%) -> %
--R map! : ((DoubleFloat -> DoubleFloat),%) -> %
--R matrix : List(List(DoubleFloat)) -> %
--R member? : (DoubleFloat,%) -> Boolean if $ has finiteAggregate and DoubleFloat has SETCAT
--R members : % -> List(DoubleFloat) if $ has finiteAggregate
--R minordet : % -> DoubleFloat if DoubleFloat has commutative(*)
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,NonNegativeInteger,DoubleFloat) -> %
--R nullSpace : % -> List(DoubleFloatVector) if DoubleFloat has INTDOM
--R nullity : % -> NonNegativeInteger if DoubleFloat has INTDOM
--R pfaffian : % -> DoubleFloat if DoubleFloat has COMRING
--R qelt : (%,Integer,Integer) -> DoubleFloat
--R qsetelt! : (%,Integer,Integer,DoubleFloat) -> DoubleFloat
--R rank : % -> NonNegativeInteger if DoubleFloat has INTDOM
--R row : (%,Integer) -> DoubleFloatVector
--R rowEchelon : % -> % if DoubleFloat has EUCDOM
--R scalarMatrix : (NonNegativeInteger,DoubleFloat) -> %
--R setColumn! : (%,Integer,DoubleFloatVector) -> %
--R setRow! : (%,Integer,DoubleFloatVector) -> %
--R setelt : (%,List(Integer),List(Integer),%) -> %
--R setelt : (%,Integer,Integer,DoubleFloat) -> DoubleFloat
--R setsubMatrix! : (%,Integer,Integer,%) -> %
--R size? : (%,NonNegativeInteger) -> Boolean
--R subMatrix : (%,Integer,Integer,Integer,Integer) -> %
--R swapColumns! : (%,Integer,Integer) -> %
--R swapRows! : (%,Integer,Integer) -> %
--R transpose : DoubleFloatVector -> %
--R zero : (NonNegativeInteger,NonNegativeInteger) -> %
--R ?~=? : (%,%) -> Boolean if DoubleFloat has SETCAT
--R
--E 1

--S 2 of 6
a:DFMAT:=qnew(2,3)
--R
--R        +0.  0.  0.+
--R   (1)  |          |
--R        +0.  0.  0.+
--R                                                  Type: DoubleFloatMatrix
--E 2

--S 3 of 6
qsetelt!(a,1,1,1.0)
```

```
--R
--R   (2)  1.
--R                                                    Type: DoubleFloat
--E 3

--S 4 of 6
a
--R
--R        +0.  0.  0.+
--R   (3)  |          |
--R        +0.  1.  0.+
--R                                              Type: DoubleFloatMatrix
--E 4

--S 5 of 6
qsetelt!(a,0,0,2.0)
--R
--R   (4)  2.
--R                                                    Type: DoubleFloat
--E 5

--S 6 of 6
a
--R
--R        +2.  0.  0.+
--R   (5)  |          |
--R        +0.  1.  0.+
--R                                              Type: DoubleFloatMatrix
--E 6

)spool
)lisp (bye)
```

———-

— DoubleFloatMatrix.help —

```
=====================================================================
DoubleFloatMatrix examples
=====================================================================
This domain creates a lisp simple array of machine doublefloats.
It provides one new function called qnew which takes an integer
that gives the array length.

NOTE: Unlike normal Axiom arrays the DoubleFloatMatrix arrays
are 0-based so the first element is 0. Axiom arrays normally
start at 1.
```

```
a:DFMAT:=qnew(2,3)
        +0.  0.  0.+
        |         |
        +0.  0.  0.+

qsetelt!(a,1,1,1.0)
        1.


a
        +0.  0.  0.+
        |         |
        +0.  1.  0.+

qsetelt!(a,0,0,2.0)
        2.

a
        +2.  0.  0.+
        |         |
        +0.  1.  0.+


See Also:
o )help Float
o )help DoubleFloat
o )show DoubleFloatMatrix
```

5.16.1 DoubleFloatMatrix (DFMAT)



Exports:

#?	-?	?**?	?*?
?+?	?-?	?/?	?=?
?~=?	antisymmetric?	any?	coerce
coerce	column	columnSpace	copy
count	count	determinant	diagonal?
diagonalMatrix	diagonalMatrix	elt	elt
elt	empty	empty?	eq?
eval	eval	eval	eval
every?	exquo	fill!	hash
horizConcat	inverse	latex	less?
listOfLists	map	map	map
map!	matrix	maxColIndex	maxRowIndex
member?	members	minColIndex	minRowIndex
minordet	more?	ncols	new
nrows	nullSpace	nullity	parts
pfaffian	qelt	qnew	qsetelt!
rank	row	rowEchelon	sample
scalarMatrix	setColumn!	setRow!	setelt
setelt	setsubMatrix!	size?	square?
squareTop	subMatrix	swapColumns!	swapRows!
symmetric?	transpose	transpose	vertConcat
zero			

— domain DFMAT DoubleFloatMatrix —

```
)abbrev domain DFMAT DoubleFloatMatrix
++ Author: Waldek Hebisch
++ Description: This is a low-level domain which implements matrices
++ (two dimensional arrays) of double precision floating point
++ numbers.  Indexing is 0 based, there is no bound checking (unless
++ provided by lower level).
DoubleFloatMatrix : MatrixCategory(DoubleFloat,
                        DoubleFloatVector,
                        DoubleFloatVector) with
    qnew : (Integer, Integer) -> %
      ++ qnew(n, m) creates a new uninitialized n by m matrix.
      ++
      ++X t1:DFMAT:=qnew(3,4)

  == add

    Qelt2 ==> DAREF2$Lisp
    Qsetelt2 ==> DSETAREF2$Lisp
    Qnrows ==> DANROWS$Lisp
    Qncols ==> DANCOLS$Lisp
    Qnew ==> MAKE_-DOUBLE_-MATRIX$Lisp
    Qnew1 ==> MAKE_-DOUBLE_-MATRIX1$Lisp
```

```
    minRowIndex x == 0
    minColIndex x == 0
    nrows x == Qnrows(x)
    ncols x == Qncols(x)
    maxRowIndex x == Qnrows(x) - 1
    maxColIndex x == Qncols(x) - 1

    qelt(m, i, j) == Qelt2(m, i, j)
    qsetelt_!(m, i, j, r) == Qsetelt2(m, i, j, r)

    empty() == Qnew(0$Integer, 0$Integer)
    qnew(rows, cols) == Qnew(rows, cols)
    new(rows, cols, a) == Qnew1(rows, cols, a)
```

———-

— DFMAT.dotabb —

```
"DFMAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DFMAT",
          shape=ellipse]
"VECTCAT" [color=lightblue,href="bookvol10.2.pdf#nameddest=VECTCAT"];
"MATCAT" [color=lightblue,href="bookvol10.2.pdf#nameddest=MATCAT"];
"DFMAT" -> "VECTCAT"
"DFMAT" -> "MATCAT"
```

———-

5.17 domain DFVEC DoubleFloatVector

— DoubleFloatVector.input —

```
)set break resume
)sys rm -f DoubleFloatVector.output
)spool DoubleFloatVector.output
)set message test on
)set message auto off
)clear all

--S 1 of 6
)show DoubleFloatVector
--R
--R DoubleFloatVector  is a domain constructor
--R Abbreviation for DoubleFloatVector is DFVEC
```

```
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DFVEC
--R
--R------------------------------ Operations --------------------------------
--R concat : List(%) -> %                concat : (%,%) -> %
--R concat : (DoubleFloat,%) -> %        concat : (%,DoubleFloat) -> %
--R copy : % -> %                        delete : (%,Integer) -> %
--R ?.? : (%,Integer) -> DoubleFloat     empty : () -> %
--R empty? : % -> Boolean                entries : % -> List(DoubleFloat)
--R eq? : (%,%) -> Boolean               index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)         insert : (%,%,Integer) -> %
--R qelt : (%,Integer) -> DoubleFloat    qnew : Integer -> %
--R reverse : % -> %                     sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (%,DoubleFloat) -> % if DoubleFloat has MONOID
--R ?*? : (DoubleFloat,%) -> % if DoubleFloat has MONOID
--R ?*? : (Integer,%) -> % if DoubleFloat has ABELGRP
--R ?+? : (%,%) -> % if DoubleFloat has ABELSG
--R ?-? : (%,%) -> % if DoubleFloat has ABELGRP
--R -? : % -> % if DoubleFloat has ABELGRP
--R ?<? : (%,%) -> Boolean if DoubleFloat has ORDSET
--R ?<=? : (%,%) -> Boolean if DoubleFloat has ORDSET
--R ?=? : (%,%) -> Boolean if DoubleFloat has SETCAT
--R ?>? : (%,%) -> Boolean if DoubleFloat has ORDSET
--R ?>=? : (%,%) -> Boolean if DoubleFloat has ORDSET
--R any? : ((DoubleFloat -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if DoubleFloat has SETCAT
--R construct : List(DoubleFloat) -> %
--R convert : % -> InputForm if DoubleFloat has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (DoubleFloat,%) -> NonNegativeInteger if $ has finiteAggregate and DoubleFloat has SETCAT
--R count : ((DoubleFloat -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R cross : (%,%) -> % if DoubleFloat has RING
--R delete : (%,UniversalSegment(Integer)) -> %
--R dot : (%,%) -> DoubleFloat if DoubleFloat has RING
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R elt : (%,Integer,DoubleFloat) -> DoubleFloat
--R entry? : (DoubleFloat,%) -> Boolean if $ has finiteAggregate and DoubleFloat has SETCAT
--R eval : (%,List(DoubleFloat),List(DoubleFloat)) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat ha
--R eval : (%,DoubleFloat,DoubleFloat) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat has SETCAT
--R eval : (%,Equation(DoubleFloat)) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat has SETCAT
--R eval : (%,List(Equation(DoubleFloat))) -> % if DoubleFloat has EVALAB(DFLOAT) and DoubleFloat has SETCA
--R every? : ((DoubleFloat -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,DoubleFloat) -> % if $ has shallowlyMutable
--R find : ((DoubleFloat -> Boolean),%) -> Union(DoubleFloat,"failed")
--R first : % -> DoubleFloat if Integer has ORDSET
--R hash : % -> SingleInteger if DoubleFloat has SETCAT
--R insert : (DoubleFloat,%,Integer) -> %
--R latex : % -> String if DoubleFloat has SETCAT
--R length : % -> DoubleFloat if DoubleFloat has RADCAT and DoubleFloat has RING
```

```
--R less? : (%,NonNegativeInteger) -> Boolean
--R magnitude : % -> DoubleFloat if DoubleFloat has RADCAT and DoubleFloat has RING
--R map : (((DoubleFloat,DoubleFloat) -> DoubleFloat),%,%) -> %
--R map : ((DoubleFloat -> DoubleFloat),%) -> %
--R map! : ((DoubleFloat -> DoubleFloat),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if DoubleFloat has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (DoubleFloat,%) -> Boolean if $ has finiteAggregate and DoubleFloat has SETCAT
--R members : % -> List(DoubleFloat) if $ has finiteAggregate
--R merge : (%,%) -> % if DoubleFloat has ORDSET
--R merge : (((DoubleFloat,DoubleFloat) -> Boolean),%,%) -> %
--R min : (%,%) -> % if DoubleFloat has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,DoubleFloat) -> %
--R outerProduct : (%,%) -> Matrix(DoubleFloat) if DoubleFloat has RING
--R parts : % -> List(DoubleFloat) if $ has finiteAggregate
--R position : (DoubleFloat,%,Integer) -> Integer if DoubleFloat has SETCAT
--R position : (DoubleFloat,%) -> Integer if DoubleFloat has SETCAT
--R position : ((DoubleFloat -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,DoubleFloat) -> DoubleFloat if $ has shallowlyMutable
--R reduce : (((DoubleFloat,DoubleFloat) -> DoubleFloat),%) -> DoubleFloat if $ has finiteAggreg
--R reduce : (((DoubleFloat,DoubleFloat) -> DoubleFloat),%,DoubleFloat) -> DoubleFloat if $ has
--R reduce : (((DoubleFloat,DoubleFloat) -> DoubleFloat),%,DoubleFloat,DoubleFloat) -> DoubleFlo
--R remove : ((DoubleFloat -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (DoubleFloat,%) -> % if $ has finiteAggregate and DoubleFloat has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and DoubleFloat has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((DoubleFloat -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),DoubleFloat) -> DoubleFloat if $ has shallowlyMutable
--R setelt : (%,Integer,DoubleFloat) -> DoubleFloat if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if DoubleFloat has ORDSET
--R sort : (((DoubleFloat,DoubleFloat) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and DoubleFloat has ORDSET
--R sort! : (((DoubleFloat,DoubleFloat) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if DoubleFloat has ORDSET
--R sorted? : (((DoubleFloat,DoubleFloat) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R zero : NonNegativeInteger -> % if DoubleFloat has ABELMON
--R ?~=? : (%,%) -> Boolean if DoubleFloat has SETCAT
--R
--E 1

--S 2 of 6
t1:DFVEC:=qnew 17
--R
--R   (1)  [0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.]
--R                                                    Type: DoubleFloatVector
--E 2
```

```
-- NOTE: DFVEC arrays are 0-based, normal Axiom arrays are 1-based
--S 3 of 6
t1.1:=1.0

   (3)  1.
                                                                Type: DoubleFloat
--E 3

--S 4 of 6
t1

   (4)  [0.,1.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.]
                                                          Type: DoubleFloatVector
--E 4

--S 5 of 6
t1.0:=2.0

   (5)  2.
                                                                Type: DoubleFloat
--E 5

--S 6 of 6
t1

   (6)  [2.,1.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.]
                                                          Type: DoubleFloatVector
--E 6

)spool
)lisp (bye)
```

———-

— DoubleFloatVector.help —

```
====================================================================
DoubleFloatVector examples
====================================================================
This domain creates a lisp simple array of machine doublefloats.
It provides one new function called qnew which takes an integer
that gives the array length.

NOTE: Unlike normal Axiom arrays the DoubleFloatVector arrays
are 0-based so the first element is 0. Axiom arrays normally
start at 1.
```

```
a:DFVEC:=qnew 17

     [0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.]

a.1:=1.0
     1.


a
     [0.,1.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.]

a.0:=2.0
     2.

a
     [2.,1.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.,0.]


See Also:
o )help Float
o )help DoubleFloat
o )show DoubleFloatVector
```

5.17.1 DoubleFloatVector (DFVEC)



Exports:

#?	-?	?*?	?+?	?-?
?.?	?<=?	?<?	?=?	?>=?
?>?	?~=?	any?	coerce	concat
construct	convert	copy	copyInto!	count
cross	delete	dot	elt	empty
empty?	entries	entry?	eq?	eval
every?	fill!	find	first	hash
index?	indices	insert	latex	length
less?	magnitude	map	map!	max
maxIndex	member?	members	merge	min
minIndex	more?	new	outerProduct	parts
position	qelt	qnew	qsetelt!	reduce
remove	removeDuplicates	reverse	reverse!	sample
select	setelt	size?	sort	sort!
sorted?	swap!	zero		

— domain DFVEC DoubleFloatVector —

```
)abbrev domain DFVEC DoubleFloatVector
++ Author: Waldek Hebisch
++ Description: This is a low-level domain which implements vectors
++ (one dimensional arrays) of double precision floating point
++ numbers.  Indexing is 0 based, there is no bound checking (unless
++ provided by lower level).
DoubleFloatVector : VectorCategory DoubleFloat with
    qnew : Integer -> %
      ++ qnew(n) creates a new uninitialized vector of length n.
      ++
      ++X t1:DFVEC:=qnew(7)
  == add

    Qelt1 ==> DELT$Lisp
    Qsetelt1 ==> DSETELT$Lisp

    qelt(x, i) == Qelt1(x, i)
    qsetelt_!(x, i, s) == Qsetelt1(x, i, s)
    Qsize ==> DLEN$Lisp
    Qnew ==> MAKE_-DOUBLE_-VECTOR$Lisp
    Qnew1 ==> MAKE_-DOUBLE_-VECTOR1$Lisp

    #x                          == Qsize x
    minIndex x                  == 0
    empty()                     == Qnew(0$Lisp)
    qnew(n)                     == Qnew(n)
    new(n, x)                   == Qnew1(n, x)
    qelt(x, i)                  == Qelt1(x, i)
    elt(x:%, i:Integer)         == Qelt1(x, i)
    qsetelt_!(x, i, s)          == Qsetelt1(x, i, s)
```

```
    setelt(x : %, i : Integer, s : DoubleFloat) == Qsetelt1(x, i, s)
    fill_!(x, s)       ==
        for i in 0..((Qsize(x)) - 1) repeat Qsetelt1(x, i, s)
        x
```

———-

— DFVEC.dotabb —

```
"DFVEC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DFVEC",
          shape=ellipse]
"VECTCAT" [color=lightblue,href="bookvol10.2.pdf#nameddest=VECTCAT"];
"DFVEC" -> "VECTCAT"
```

———-

5.18 domain DROPT DrawOption

— DrawOption.input —

```
)set break resume
)sys rm -f DrawOption.output
)spool DrawOption.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show DrawOption
--R
--R DrawOption  is a domain constructor
--R Abbreviation for DrawOption is DROPT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for DROPT
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               adaptive : Boolean -> %
--R clip : List(Segment(Float)) -> %     clip : Boolean -> %
--R coerce : % -> OutputForm             curveColor : Palette -> %
--R curveColor : Float -> %              hash : % -> SingleInteger
--R latex : % -> String                  pointColor : Palette -> %
--R pointColor : Float -> %              range : List(Segment(Float)) -> %
--R style : String -> %                  title : String -> %
--R toScale : Boolean -> %               tubePoints : PositiveInteger -> %
```

```
--R tubeRadius : Float -> %                unit : List(Float) -> %
--R var1Steps : PositiveInteger -> %       var2Steps : PositiveInteger -> %
--R ?~=? : (%,%) -> Boolean
--R colorFunction : ((DoubleFloat,DoubleFloat,DoubleFloat) -> DoubleFloat) -> %
--R colorFunction : ((DoubleFloat,DoubleFloat) -> DoubleFloat) -> %
--R colorFunction : (DoubleFloat -> DoubleFloat) -> %
--R coord : (Point(DoubleFloat) -> Point(DoubleFloat)) -> %
--R coordinates : (Point(DoubleFloat) -> Point(DoubleFloat)) -> %
--R option : (List(%),Symbol) -> Union(Any,"failed")
--R option? : (List(%),Symbol) -> Boolean
--R range : List(Segment(Fraction(Integer))) -> %
--R ranges : List(Segment(Float)) -> %
--R space : ThreeSpace(DoubleFloat) -> %
--R viewpoint : Record(theta: DoubleFloat,phi: DoubleFloat,scale: DoubleFloat,scaleX: DoubleFloat,scaleY: D
--R
--E 1

)spool
)lisp (bye)
```

———-


— DrawOption.help —

```
========================================================================
DrawOption examples
========================================================================

See Also:
o )show DrawOption
```

———-

5.18.1 DrawOption (DROPT)



Exports:

adaptive	clip	coerce	colorFunction	coord
coordinates	curveColor	hash	latex	option
option?	pointColor	range	ranges	space
style	title	toScale	tubePoints	tubeRadius
unit	var1Steps	var2Steps	viewpoint	?=?
?~=?				

— domain DROPT DrawOption —

```
)abbrev domain DROPT DrawOption
++ Author: Stephen Watt
++ Date Created: 1 March 1990
++ Date Last Updated: 31 Oct 1990, Jim Wen
++ Basic Operations: adaptive, clip, title, style, toScale, coordinates,
++ pointColor, curveColor, colorFunction, tubeRadius, range, ranges,
++ var1Steps, var2Steps, tubePoints, unit
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ DrawOption allows the user to specify defaults for the
++ creation and rendering of plots.

DrawOption(): Exports == Implementation where
 RANGE ==> List Segment Float
 UNIT  ==> List Float
 PAL   ==> Palette
 POINT ==> Point(DoubleFloat)
 SEG   ==> Segment Float
 SF     ==> DoubleFloat
 SPACE3 ==> ThreeSpace(DoubleFloat)
 VIEWPT ==> Record(theta:SF, phi:SF, scale:SF, scaleX:SF, scaleY:SF, scaleZ:SF, deltaX:SF, delta

 Exports ==> SetCategory with
  adaptive : Boolean -> %
    ++ adaptive(b) turns adaptive 2D plotting on if b is true, or off if b is
    ++ false. This option is expressed in the form \spad{adaptive == b}.
  clip : Boolean -> %
    ++ clip(b) turns 2D clipping on if b is true, or off if b is false.
    ++ This option is expressed in the form \spad{clip == b}.
  viewpoint : VIEWPT -> %
    ++ viewpoint(vp) creates a viewpoint data structure corresponding to the
    ++ list of values. The values are interpreted as [theta, phi, scale,
    ++ scaleX, scaleY, scaleZ, deltaX, deltaY].  This option is expressed
    ++ in the form \spad{viewpoint == ls}.
  title  : String -> %
```

```
    ++ title(s) specifies a title for a plot by the indicated string s.
    ++ This option is expressed in the form \spad{title == s}.
  style  : String -> %
    ++ style(s) specifies the drawing style in which the graph will be plotted
    ++ by the indicated string s. This option is expressed in the
    ++ form \spad{style == s}.
  toScale : Boolean -> %
    ++ toScale(b) specifies whether or not a plot is to be drawn to scale;
    ++ if b is true it is drawn to scale, if b is false it is not. This option
    ++ is expressed in the form \spad{toScale == b}.
  clip : List SEG -> %
    ++ clip([l]) provides ranges for user-defined clipping as specified
    ++ in the list l. This option is expressed in the form \spad{clip == [l]}.
  coordinates : (POINT -> POINT) -> %
    ++ coordinates(p) specifies a change of coordinate systems of point p.
    ++ This option is expressed in the form \spad{coordinates == p}.
  pointColor : Float -> %
    ++ pointColor(v) specifies a color, v, for 2D graph points. This option
    ++ is expressed in the form \spad{pointColor == v}.
  pointColor : PAL -> %
    ++ pointColor(p) specifies a color index for 2D graph points from the
    ++ spadcolors palette p. This option is expressed in the
    ++ form \spad{pointColor == p}.
  curveColor : Float -> %
    ++ curveColor(v) specifies a color, v, for 2D graph curves.
    ++ This option is expressed in the form \spad{curveColor == v}.
  curveColor : PAL -> %
    ++ curveColor(p) specifies a color index for 2D graph curves from the
    ++ spadcolors palette p.
    ++ This option is expressed in the form \spad{curveColor ==p}.
  colorFunction : (SF -> SF) -> %
    ++ colorFunction(f(z)) specifies the color based upon the z-component of
    ++ three dimensional plots. This option is expressed in the
    ++ form \spad{colorFunction == f(z)}.
  colorFunction : ((SF,SF) -> SF) -> %
    ++ colorFunction(f(u,v)) specifies the color for three dimensional plots
    ++ as a function based upon the two parametric variables. This option
    ++ is expressed in the form \spad{colorFunction == f(u,v)}.
  colorFunction : ((SF,SF,SF) -> SF) -> %
    ++ colorFunction(f(x,y,z)) specifies the color for three dimensional
    ++ plots as a function of x, y, and z coordinates. This option is
    ++ expressed in the form \spad{colorFunction == f(x,y,z)}.
  tubeRadius : Float -> %
    ++ tubeRadius(r) specifies a radius, r, for a tube plot around a 3D curve;
    ++ is expressed in the form \spad{tubeRadius == 4}.
  range : List SEG -> %
    ++ range([l]) provides a user-specified range l.
    ++ This option is expressed in the form \spad{range == [l]}.
  range : List Segment Fraction Integer -> %
    ++ range([i]) provides a user-specified range i.
```

```
    ++ This option is expressed in the form \spad{range == [i]}.
  ranges : RANGE -> %
    ++ ranges(l) provides a list of user-specified ranges l.
    ++ This option is expressed in the form \spad{ranges == l}.
  space : SPACE3 -> %
    ++ space specifies the space into which we will draw.  If none is given
    ++ then a new space is created.
  var1Steps : PositiveInteger -> %
    ++ var1Steps(n) indicates the number of subdivisions, n, of the first
    ++ range variable. This option is expressed in the
    ++ form \spad{var1Steps == n}.
  var2Steps : PositiveInteger -> %
    ++ var2Steps(n) indicates the number of subdivisions, n,  of the second
    ++ range variable. This option is expressed in the
    ++ form \spad{var2Steps == n}.
  tubePoints : PositiveInteger -> %
    ++ tubePoints(n) specifies the number of points, n, defining the circle
    ++ which creates the tube around a 3D curve, the default is 6.
    ++ This option is expressed in the form \spad{tubePoints == n}.
  coord : (POINT->POINT) -> %
    ++ coord(p) specifies a change of coordinates of point p.
    ++ This option is expressed in the form \spad{coord == p}.
  unit   : UNIT -> %
    ++ unit(lf) will mark off the units according to the indicated list lf.
    ++ This option is expressed in the form \spad{unit == [f1,f2]}.
  option : (List %, Symbol) -> Union(Any, "failed")
    ++ option() is not to be used at the top level;
    ++ option determines internally which drawing options are indicated in
    ++ a draw command.
  option?: (List %, Symbol) -> Boolean
    ++ option?() is not to be used at the top level;
    ++ option? internally returns true for drawing options which are
    ++ indicated in a draw command, or false for those which are not.
Implementation ==> add
  import AnyFunctions1(String)
  import AnyFunctions1(Segment Float)
  import AnyFunctions1(VIEWPT)
  import AnyFunctions1(List Segment Float)
  import AnyFunctions1(List Segment Fraction Integer)
  import AnyFunctions1(List Integer)
  import AnyFunctions1(PositiveInteger)
  import AnyFunctions1(Boolean)
  import AnyFunctions1(RANGE)
  import AnyFunctions1(UNIT)
  import AnyFunctions1(Float)
  import AnyFunctions1(POINT -> POINT)
  import AnyFunctions1(SF -> SF)
  import AnyFunctions1((SF,SF) -> SF)
  import AnyFunctions1((SF,SF,SF) -> SF)
  import AnyFunctions1(POINT)
```

```
import AnyFunctions1(PAL)
import AnyFunctions1(SPACE3)

Rep := Record(keyword:Symbol, value:Any)

length:List SEG -> NonNegativeInteger
-- these lists will become tuples in a later version
length tup == # tup

lengthR:List Segment Fraction Integer -> NonNegativeInteger
-- these lists will become tuples in a later version
lengthR tup == # tup

lengthI:List Integer -> NonNegativeInteger
-- these lists will become tuples in a later version
lengthI tup == # tup

viewpoint vp ==
  ["viewpoint"::Symbol, vp::Any]

title s == ["title"::Symbol, s::Any]
style s == ["style"::Symbol, s::Any]
toScale b == ["toScale"::Symbol, b::Any]
clip(b:Boolean) == ["clipBoolean"::Symbol, b::Any]
adaptive b == ["adaptive"::Symbol, b::Any]

pointColor(x:Float) == ["pointColorFloat"::Symbol, x::Any]
pointColor(c:PAL) == ["pointColorPalette"::Symbol, c::Any]
curveColor(x:Float) == ["curveColorFloat"::Symbol, x::Any]
curveColor(c:PAL) == ["curveColorPalette"::Symbol, c::Any]
colorFunction(f:SF -> SF) == ["colorFunction1"::Symbol, f::Any]
colorFunction(f:(SF,SF) -> SF) == ["colorFunction2"::Symbol, f::Any]
colorFunction(f:(SF,SF,SF) -> SF) == ["colorFunction3"::Symbol, f::Any]
clip(tup:List SEG) ==
  length tup > 3 =>
    error "clip: at most 3 segments may be specified"
  ["clipSegment"::Symbol, tup::Any]
coordinates f == ["coordinates"::Symbol, f::Any]
tubeRadius x == ["tubeRadius"::Symbol, x::Any]
range(tup:List Segment Float) ==
  ((n := length tup) > 3) =>
    error "range: at most 3 segments may be specified"
  n < 2 =>
    error "range: at least 2 segments may be specified"
  ["rangeFloat"::Symbol, tup::Any]
range(tup:List Segment Fraction Integer) ==
  ((n := lengthR tup) > 3) =>
    error "range: at most 3 segments may be specified"
  n < 2 =>
    error "range: at least 2 segments may be specified"
```

```
    ["rangeRat"::Symbol, tup::Any]

  ranges s               == ["ranges"::Symbol, s::Any]
  space s                == ["space"::Symbol, s::Any]
  var1Steps s            == ["var1Steps"::Symbol, s::Any]
  var2Steps s            == ["var2Steps"::Symbol, s::Any]
  tubePoints s           == ["tubePoints"::Symbol, s::Any]
  coord s                == ["coord"::Symbol, s::Any]
  unit s                 == ["unit"::Symbol, s::Any]
  coerce(x:%):OutputForm == x.keyword::OutputForm = x.value::OutputForm
  x:% = y:%              == x.keyword = y.keyword and x.value = y.value

  option?(l, s) ==
    for x in l repeat
      x.keyword = s => return true
    false

  option(l, s) ==
    for x in l repeat
      x.keyword = s => return(x.value)
    "failed"
```

———-

— DROPT.dotabb —

```
"DROPT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=DROPT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"DROPT" -> "ALIST"
```

———-

5.19 domain D01AJFA d01ajfAnnaType

— d01ajfAnnaType.input —

```
)set break resume
)sys rm -f d01ajfAnnaType.output
)spool d01ajfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show d01ajfAnnaType
--R
--R d01ajfAnnaType  is a domain constructor
--R Abbreviation for d01ajfAnnaType is D01AJFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01AJFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R hash : % -> SingleInteger            latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Doubl
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletio
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01ajfAnnaType.help —

```
=====================================================================
d01ajfAnnaType examples
=====================================================================

See Also:
o )show d01ajfAnnaType
```

———-

5.19.1 d01ajfAnnaType (D01AJFA)



Exports:
coerce hash latex measure numericalIntegration ?~=? ?=?

— domain D01AJFA d01ajfAnnaType —

```
)abbrev domain D01AJFA d01ajfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01ajfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01AJF, a general numerical integration routine which
++ can handle some singularities in the input function.  The function
++ \axiomFun{measure} measures the usefulness of the routine D01AJF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01ajfAnnaType(): NumericalIntegrationCategory == Result add
  EF2   ==> ExpressionFunctions2
  EDF   ==> Expression DoubleFloat
  LDF   ==> List DoubleFloat
  SDF   ==> Stream DoubleFloat
  DF    ==> DoubleFloat
  FI    ==> Fraction Integer
  EFI   ==> Expression Fraction Integer
  SOCDF ==> Segment OrderedCompletion DoubleFloat
  NIA   ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
  INT   ==> Integer
  BOP   ==> BasicOperator
  S     ==> Symbol
  ST    ==> String
```

```
  LST   ==> List String
  RT    ==> RoutinesTable
  Rep:=Result
  import Rep, NagIntegrationPackage, d01AgentsPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    pp:SDF := singularitiesOf(args)
    not (empty?(pp)$SDF) =>
      [0.1,"d01ajf: There is a possible problem at the following point(s): "
           commaSeparate(sdf2lst(pp)) ,ext]
    [getMeasure(R,d01ajf :: S)$RT,
       "The general routine d01ajf is our default",ext]

  numericalIntegration(args:NIA,hints:Result) ==
    ArgsFn := map(x+->convert(x)$DF,args.fn)$EF2(DF,Float)
    b:Float := getButtonValue("d01ajf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 75*fEvals
    f : Union(fn:FileName,fp:Asp1(F)) := [retract(ArgsFn)$Asp1(F)]
    d01ajf(getlo(args.range),gethi(args.range),args.abserr,_
           args.relerr,4*iw,iw,-1,f)
```

———-

— D01AJFA.dotabb —

```
"D01AJFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01AJFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"D01AJFA" -> "STRING"
```

———-

5.20 domain D01AKFA d01akfAnnaType

— d01akfAnnaType.input —

```
)set break resume
)sys rm -f d01akfAnnaType.output
)spool d01akfAnnaType.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show d01akfAnnaType
--R
--R d01akfAnnaType  is a domain constructor
--R Abbreviation for d01akfAnnaType is D01AKFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01AKFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompl
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Order
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedComple
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Ordere
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01akfAnnaType.help —

```
=====================================================================
d01akfAnnaType examples
=====================================================================

See Also:
o )show d01akfAnnaType
```

———-

5.20.1 d01akfAnnaType (D01AKFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01AKFA d01akfAnnaType —

```
)abbrev domain D01AKFA d01akfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01akfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01AKF, a numerical integration routine which is
++ is suitable for oscillating, non-singular functions.  The function
++ \axiomFun{measure} measures the usefulness of the routine D01AKF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01akfAnnaType(): NumericalIntegrationCategory == Result add
  EF2   ==> ExpressionFunctions2
  EDF   ==> Expression DoubleFloat
  LDF   ==> List DoubleFloat
  SDF   ==> Stream DoubleFloat
  DF    ==> DoubleFloat
  FI    ==> Fraction Integer
  EFI   ==> Expression Fraction Integer
  SOCDF ==> Segment OrderedCompletion DoubleFloat
  NIA   ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
  INT   ==> Integer
  BOP   ==> BasicOperator
  S     ==> Symbol
  ST    ==> String
```

```
  LST   ==> List String
  RT    ==> RoutinesTable
  Rep:=Result
  import Rep, d01AgentsPackage, NagIntegrationPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    pp:SDF := singularitiesOf(args)
    not (empty?(pp)$SDF) =>
      [0.0,"d01akf: There is a possible problem at the following point(s): "
              commaSeparate(sdf2lst(pp)) ,ext]
    o:Float := functionIsOscillatory(args)
    one := 1.0
    m:Float := (getMeasure(R,d01akf@S)$RT)*(one-one/(one+sqrt(o)))**2
    m > 0.8 => [m,"d01akf: The expression shows much oscillation",ext]
    m > 0.6 => [m,"d01akf: The expression shows some oscillation",ext]
    m > 0.5 => [m,"d01akf: The expression shows little oscillation",ext]
    [m,"d01akf: The expression shows little or no oscillation",ext]

  numericalIntegration(args:NIA,hints:Result) ==
    ArgsFn := map(x+->convert(x)$DF,args.fn)$EF2(DF,Float)
    b:Float := getButtonValue("d01akf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 75*fEvals
    f : Union(fn:FileName,fp:Asp1(F)) := [retract(ArgsFn)$Asp1(F)]
    d01akf(getlo(args.range),gethi(args.range),args.abserr,_
           args.relerr,4*iw,iw,-1,f)
```

———-

— D01AKFA.dotabb —

```
"D01AKFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01AKFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"D01AKFA" -> "STRING"
```

———-

5.21 domain D01ALFA d01alfAnnaType

— d01alfAnnaType.input —

```
)set break resume
)sys rm -f d01alfAnnaType.output
```

```
)spool d01alfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01alfAnnaType
--R
--R d01alfAnnaType  is a domain constructor
--R Abbreviation for d01alfAnnaType is D01ALFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01ALFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletio
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01alfAnnaType.help —

```
====================================================================
d01alfAnnaType examples
====================================================================

See Also:
o )show d01alfAnnaType
```

———-

5.21.1 d01alfAnnaType (D01ALFA)



Exports:
coerce hash latex measure numericalIntegration ?~=? ?=?

— domain D01ALFA d01alfAnnaType —

```
)abbrev domain D01ALFA d01alfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01alfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01ALF, a general numerical integration routine which
++ can handle a list of singularities.  The
++ function \axiomFun{measure} measures the usefulness of the routine D01ALF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01alfAnnaType(): NumericalIntegrationCategory == Result add
  EF2   ==> ExpressionFunctions2
  EDF   ==> Expression DoubleFloat
  LDF   ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
  DF  ==> DoubleFloat
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
  INT  ==> Integer
  BOP  ==> BasicOperator
  S  ==> Symbol
  ST  ==> String
```

```
  LST  ==> List String
  RT  ==> RoutinesTable
  Rep:=Result
  import Rep, d01AgentsPackage, NagIntegrationPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    streamOfZeros:SDF := singularitiesOf(args)
    listOfZeros:LST := removeDuplicates!(sdf2lst(streamOfZeros))
    numberOfZeros:INT := # listOfZeros
    (numberOfZeros > 15)@Boolean =>
      [0.0,"d01alf: The list of singularities is too long", ext]
    positive?(numberOfZeros) =>
      l:LDF := entries(complete(streamOfZeros)$SDF)$SDF
      lany:Any := coerce(l)$AnyFunctions1(LDF)
      ex:Record(key:S,entry:Any) := [d01alfextra@S,lany]
      ext := insert!(ex,ext)$Result
      st:ST := "Recommended is d01alf with the singularities "
                     commaSeparate(listOfZeros)
      m :=
--        one?(numberOfZeros) => 0.4
        (numberOfZeros = 1) => 0.4
        getMeasure(R,d01alf@S)$RT
      [m, st, ext]
    [0.0, "d01alf: A list of suitable singularities has not been found", ext]

  numericalIntegration(args:NIA,hints:Result) ==
    la:Any := coerce(search((d01alfextra@S),hints)$Result)@Any
    listOfZeros:LDF := retract(la)$AnyFunctions1(LDF)
    l:= removeDuplicates(listOfZeros)$LDF
    n:Integer := (#(l))$List(DF)
    M:Matrix DF := matrix([l])$(Matrix DF)
    b:Float := getButtonValue("d01alf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 75*fEvals
    ArgsFn := map(x+->convert(x)$DF,args.fn)$EF2(DF,Float)
    f : Union(fn:FileName,fp:Asp1(F)) := [retract(ArgsFn)$Asp1(F)]
    d01alf(getlo(args.range),gethi(args.range),n,M,_
           args.abserr,args.relerr,2*n*iw,n*iw,-1,f)
```

———-

— D01ALFA.dotabb —

```
"D01ALFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01ALFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"D01ALFA" -> "STRING"
```

———-

5.22 domain D01AMFA d01amfAnnaType

— d01amfAnnaType.input —

```
)set break resume
)sys rm -f d01amfAnnaType.output
)spool d01amfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01amfAnnaType
--R
--R d01amfAnnaType  is a domain constructor
--R Abbreviation for d01amfAnnaType is D01AMFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01AMFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompl
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Order
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedComple
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Ordere
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01amfAnnaType.help —

```
=====================================================================
d01amfAnnaType examples
=====================================================================

See Also:
o )show d01amfAnnaType
```

———-

5.22.1 d01amfAnnaType (D01AMFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01AMFA d01amfAnnaType —

```
)abbrev domain D01AMFA d01amfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01amfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01AMF, a general numerical integration routine which
++ can handle infinite or semi-infinite range of the input function.  The
++ function \axiomFun{measure} measures the usefulness of the routine D01AMF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01amfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
  DF  ==> DoubleFloat
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
```

```
  INT  ==> Integer
  BOP  ==> BasicOperator
  S  ==> Symbol
  ST  ==> String
  LST  ==> List String
  RT  ==> RoutinesTable
  Rep:=Result
  import Rep, d01AgentsPackage, NagIntegrationPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    Range:=rangeIsFinite(args)
    pp:SDF := singularitiesOf(args)
    not (empty?(pp)$SDF) =>
      [0.0,"d01amf: There is a possible problem at the following point(s): "
                    commaSeparate(sdf2lst(pp)), ext]
    [getMeasure(R,d01amf@S)$RT, "d01amf is a reasonable choice if the "
         "integral is infinite or semi-infinite and d01transform cannot "
           "do better than using general routines",ext]

  numericalIntegration(args:NIA,hints:Result) ==
    r:INT
    bound:DF
    ArgsFn := map(x+->convert(x)$DF,args.fn)$EF2(DF,Float)
    b:Float := getButtonValue("d01amf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 150*fEvals
    f : Union(fn:FileName,fp:Asp1(F)) := [retract(ArgsFn)$Asp1(F)]
    Range:=rangeIsFinite(args)
    if (Range case upperInfinite) then
      bound := getlo(args.range)
      r := 1
    else if (Range case lowerInfinite) then
      bound := gethi(args.range)
      r := -1
    else
      bound := 0$DF
      r := 2
    d01amf(bound,r,args.abserr,args.relerr,4*iw,iw,-1,f)
```

— D01AMFA.dotabb —

```
"D01AMFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01AMFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"D01AMFA" -> "STRING"
```

———-

5.23 domain D01ANFA d01anfAnnaType

— **d01anfAnnaType.input** —

```
)set break resume
)sys rm -f d01anfAnnaType.output
)spool d01anfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01anfAnnaType
--R
--R d01anfAnnaType  is a domain constructor
--R Abbreviation for d01anfAnnaType is D01ANFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01ANFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R
--E 1

)spool
)lisp (bye)
```

———-


— **d01anfAnnaType.help** —

```
==========================================================================
d01anfAnnaType examples
==========================================================================

See Also:
o )show d01anfAnnaType
```

———-

5.23.1 d01anfAnnaType (D01ANFA)



Exports:
coerce hash latex measure numericalIntegration ?~=? ?=?

— domain D01ANFA d01anfAnnaType —

```
)abbrev domain D01ANFA d01anfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01anfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01ANF, a numerical integration routine which can
++ handle weight functions of the form cos(\omega x) or sin(\omega x).  The
++ function \axiomFun{measure} measures the usefulness of the routine D01ANF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01anfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
  DF  ==> DoubleFloat
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
```

```
  INT  ==> Integer
  BOP  ==> BasicOperator
  S  ==> Symbol
  ST  ==> String
  LST  ==> List String
  RT  ==> RoutinesTable
  Rep:=Result
  import Rep, d01WeightsPackage, d01AgentsPackage, NagIntegrationPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    weight:Union(Record(op:BOP,w:DF),"failed") :=
      exprHasWeightCosWXorSinWX(args)
    weight case "failed" =>
      [0.0,"d01anf: A suitable weight has not been found", ext]
    weight case Record(op:BOP,w:DF) =>
      wany := coerce(weight)$AnyFunctions1(Record(op:BOP,w:DF))
      ex:Record(key:S,entry:Any) := [d01anfextra@S,wany]
      ext := insert!(ex,ext)$Result
      ws:ST := string(name(weight.op)$BOP)$S "(" df2st(weight.w)
                          string(args.var)$S ")"
      [getMeasure(R,d01anf@S)$RT,
        "d01anf: The expression has a suitable weight:- " ws, ext]

  numericalIntegration(args:NIA,hints:Result) ==
    a:INT
    r:Any := coerce(search((d01anfextra@S),hints)$Result)@Any
    rec:Record(op:BOP,w:DF) := retract(r)$AnyFunctions1(Record(op:BOP,w:DF))
    Var := args.var :: EDF
    o:BOP := rec.op
    den:EDF := o((rec.w*Var)$EDF)
    Argsfn:EDF := args.fn/den
    if (name(o) = cos@S)@Boolean then a := 1
    else a := 2
    b:Float := getButtonValue("d01anf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 75*fEvals
    ArgsFn := map(x+->convert(x)$DF,Argsfn)$EF2(DF,Float)
    f : Union(fn:FileName,fp:Asp1(G)) := [retract(ArgsFn)$Asp1(G)]
    d01anf(getlo(args.range),gethi(args.range),rec.w,a,_
           args.abserr,args.relerr,4*iw,iw,-1,f)
```

———-

— D01ANFA.dotabb —

```
"D01ANFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01ANFA"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
```

```
"D01ANFA" -> "ALIST"
```

———-

5.24 domain D01APFA d01apfAnnaType

— **d01apfAnnaType.input** —

```
)set break resume
)sys rm -f d01apfAnnaType.output
)spool d01apfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01apfAnnaType
--R
--R d01apfAnnaType  is a domain constructor
--R Abbreviation for d01apfAnnaType is D01APFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01APFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompl
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Order
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedComple
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Ordere
--R
--E 1

)spool
)lisp (bye)
```


———-

— **d01apfAnnaType.help** —

```
=====================================================================
d01apfAnnaType examples
=====================================================================
```

```
See Also:
o )show d01apfAnnaType
```

5.24.1 d01apfAnnaType (D01APFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01APFA d01apfAnnaType —

```
)abbrev domain D01APFA d01apfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01apfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01APF, a general numerical integration routine which
++ can handle end point singularities of the algebraico-logarithmic form
++ w(x) = (x-a)^c * (b-x)^d.  The
++ function \axiomFun{measure} measures the usefulness of the routine D01APF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01apfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
  DF  ==> DoubleFloat
```

```
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
  INT  ==> Integer
  BOP  ==> BasicOperator
  S  ==> Symbol
  ST  ==> String
  LST  ==> List String
  RT  ==> RoutinesTable
  Rep:=Result
  import Rep, NagIntegrationPackage, d01AgentsPackage, d01WeightsPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    d := (c := 0$DF)
    if ((a := exprHasAlgebraicWeight(args)) case LDF) then
      if  (a.1 > -1) then c := a.1
      if  (a.2 > -1) then d := a.2
    l:INT := exprHasLogarithmicWeights(args)
--    (zero? c) and (zero? d) and (one? l) =>
    (zero? c) and (zero? d) and (l = 1) =>
        [0.0,"d01apf: A suitable singularity has not been found", ext]
    out:LDF := [c,d,l :: DF]
    outany:Any := coerce(out)$AnyFunctions1(LDF)
    ex:Record(key:S,entry:Any) := [d01apfextra@S,outany]
    ext := insert!(ex,ext)$Result
    st:ST :=  "Recommended is d01apf with c = " df2st(c) ", d = "
                            df2st(d) " and l = " string(l)$ST
    [getMeasure(R,d01apf@S)$RT, st, ext]

  numericalIntegration(args:NIA,hints:Result) ==

    Var:EDF := coerce(args.var)$EDF
    la:Any := coerce(search((d01apfextra@S),hints)$Result)@Any
    list:LDF := retract(la)$AnyFunctions1(LDF)
    Fac1:EDF := (Var - (getlo(args.range) :: EDF))$EDF
    Fac2:EDF := ((gethi(args.range) :: EDF) - Var)$EDF
    c := first(list)$LDF
    d := second(list)$LDF
    l := (retract(third(list)$LDF)@INT)$DF
    thebiz:EDF := (Fac1**(c :: EDF))*(Fac2**(d :: EDF))
    if l > 1 then
      if l = 2 then
        thebiz := thebiz*log(Fac1)
      else if l = 3 then
        thebiz := thebiz*log(Fac2)
      else
        thebiz := thebiz*log(Fac1)*log(Fac2)
```

```
    Fn :=  (args.fn/thebiz)$EDF
    ArgsFn := map(x+->convert(x)$DF,Fn)$EF2(DF,Float)
    b:Float := getButtonValue("d01apf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 75*fEvals
    f : Union(fn:FileName,fp:Asp1(G)) := [retract(ArgsFn)$Asp1(G)]
    d01apf(getlo(args.range),gethi(args.range),c,d,l,_
           args.abserr,args.relerr,4*iw,iw,-1,f)
```

———-

— **D01APFA.dotabb** —

```
"D01APFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01APFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"D01APFA" -> "STRING"
```

———-

5.25 domain D01AQFA d01aqfAnnaType

— **d01aqfAnnaType.input** —

```
)set break resume
)sys rm -f d01aqfAnnaType.output
)spool d01aqfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01aqfAnnaType
--R
--R d01aqfAnnaType  is a domain constructor
--R Abbreviation for d01aqfAnnaType is D01AQFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01AQFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
```

```
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedComple
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Ordere
--R
--E 1

)spool
)lisp (bye)
```

———-


— **d01aqfAnnaType.help** —

```
=====================================================================
d01aqfAnnaType examples
=====================================================================

See Also:
o )show d01aqfAnnaType
```

———-

5.25.1 d01aqfAnnaType (D01AQFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— **domain D01AQFA d01aqfAnnaType** —

```
)abbrev domain D01AQFA d01aqfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
```

```
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01aqfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01AQF, a general numerical integration routine which
++ can solve an integral of the form
++ /home/bjd/Axiom/anna/hypertex/bitmaps/d01aqf.xbm
++ The function \axiomFun{measure} measures the usefulness of the routine
++ D01AQF for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01aqfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
  DF  ==> DoubleFloat
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
  INT  ==> Integer
  BOP  ==> BasicOperator
  S  ==> Symbol
  ST  ==> String
  LST  ==> List String
  RT  ==> RoutinesTable
  Rep:=Result
  import Rep, d01AgentsPackage, NagIntegrationPackage

  measure(R:RT,args:NIA) ==
    ext:Result := empty()$Result
    Den := denominator(args.fn)
--    one? Den =>
    (Den = 1) =>
      [0.0,"d01aqf: A suitable weight function has not been found", ext]
    listOfZeros:LDF := problemPoints(args.fn,args.var,args.range)
    numberOfZeros := (#(listOfZeros))$LDF
    zero?(numberOfZeros) =>
      [0.0,"d01aqf: A suitable weight function has not been found", ext]
    numberOfZeros = 1 =>
      s:SDF := singularitiesOf(args)
      more?(s,1)$SDF =>
        [0.0,"d01aqf: Too many singularities have been found", ext]
      cFloat:Float := (convert(first(listOfZeros)$LDF)@Float)$DF
      cString:ST := (convert(cFloat)@ST)$Float
      lany:Any := coerce(listOfZeros)$AnyFunctions1(LDF)
      ex:Record(key:S,entry:Any) := [d01aqfextra@S,lany]
      ext := insert!(ex,ext)$Result
```

```
      [getMeasure(R,d01aqf@S)$RT, "Recommended is d01aqf with the "
        "hilbertian weight function of 1/(x-c) where c = " cString, ext]
    [0.0,"d01aqf: More than one factor has been found and so does not "
                "have a suitable weight function",ext]

  numericalIntegration(args:NIA,hints:Result) ==
    Args := copy args
    ca:Any :=  coerce(search((d01aqfextra@S),hints)$Result)@Any
    c:DF := first(retract(ca)$AnyFunctions1(LDF))$LDF
    ci:FI := df2fi(c)$ExpertSystemToolsPackage
    Var:EFI := Args.var :: EFI
    Gx:EFI := (Var-(ci::EFI))*(edf2efi(Args.fn)$ExpertSystemToolsPackage)
    ArgsFn := map(x+->convert(x)$FI,Gx)$EF2(FI,Float)
    b:Float := getButtonValue("d01aqf","functionEvaluations")$AttributeButtons
    fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
    iw:INT := 75*fEvals
    f : Union(fn:FileName,fp:Asp1(G)) := [retract(ArgsFn)$Asp1(G)]
    d01aqf(getlo(Args.range),gethi(Args.range),c,_
           Args.abserr,Args.relerr,4*iw,iw,-1,f)
```

———-

— D01AQFA.dotabb —

```
"D01AQFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01AQFA"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"D01AQFA" -> "STRING"
"D01AQFA" -> "PFECAT"
```

———-

5.26 domain D01ASFA d01asfAnnaType

— d01asfAnnaType.input —

```
)set break resume
)sys rm -f d01asfAnnaType.output
)spool d01asfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show d01asfAnnaType
--R
--R d01asfAnnaType  is a domain constructor
--R Abbreviation for d01asfAnnaType is D01ASFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01ASFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01asfAnnaType.help —

```
==========================================================================
d01asfAnnaType examples
==========================================================================

See Also:
o )show d01asfAnnaType
```

———-

5.26.1 d01asfAnnaType (D01ASFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01ASFA d01asfAnnaType —

```
)abbrev domain D01ASFA d01asfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01asfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01ASF, a numerical integration routine which can
++ handle weight functions of the form cos(\omega x) or sin(\omega x) on an
++ semi-infinite range.  The
++ function \axiomFun{measure} measures the usefulness of the routine D01ASF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01asfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
  DF  ==> DoubleFloat
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
  MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
  INT  ==> Integer
  BOP  ==> BasicOperator
  S  ==> Symbol
```

```
ST  ==> String
LST  ==> List String
RT  ==> RoutinesTable
Rep:=Result
import Rep, d01WeightsPackage, d01AgentsPackage, NagIntegrationPackage

measure(R:RT,args:NIA) ==
  ext:Result := empty()$Result
  Range := rangeIsFinite(args)
  not(Range case upperInfinite) =>
    [0.0,"d01asf is not a suitable routine for infinite integrals",ext]
  weight: Union(Record(op:BOP,w:DF),"failed") :=
    exprHasWeightCosWXorSinWX(args)
  weight case "failed" =>
    [0.0,"d01asf: A suitable weight has not been found", ext]
  weight case Record(op:BOP,w:DF) =>
    wany := coerce(weight)$AnyFunctions1(Record(op:BOP,w:DF))
    ex:Record(key:S,entry:Any) := [d01asfextra@S,wany]
    ext := insert!(ex,ext)$Result
    ws:ST := string(name(weight.op)$BOP)$S "(" df2st(weight.w)
                        string(args.var)$S ")"
    [getMeasure(R,d01asf@S)$RT,
      "d01asf: A suitable weight has been found:- " ws, ext]

numericalIntegration(args:NIA,hints:Result) ==
  i:INT
  r:Any := coerce(search((d01asfextra@S),hints)$Result)@Any
  rec:Record(op:BOP,w:DF) := retract(r)$AnyFunctions1(Record(op:BOP,w:DF))
  Var := args.var :: EDF
  o:BOP := rec.op
  den:EDF := o((rec.w*Var)$EDF)
  Argsfn:EDF := args.fn/den
  if (name(o) = cos@S)@Boolean then i := 1
  else i := 2
  b:Float := getButtonValue("d01asf","functionEvaluations")$AttributeButtons
  fEvals:INT := wholePart exp(1.1513*(1.0/(2.0*(1.0-b))))
  iw:INT := 75*fEvals
  ArgsFn := map(x +-> convert(x)$DF,Argsfn)$EF2(DF,Float)
  f : Union(fn:FileName,fp:Asp1(G)) := [retract(ArgsFn)$Asp1(G)]
  err :=
    positive?(args.abserr) => args.abserr
    args.relerr
  d01asf(getlo(args.range),rec.w,i,err,50,4*iw,2*iw,-1,f)
```

———-

— D01ASFA.dotabb —

```
"D01ASFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01ASFA"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"D01ASFA" -> "ALIST"
```

———-

5.27 domain D01FCFA d01fcfAnnaType

— d01fcfAnnaType.input —

```
)set break resume
)sys rm -f d01fcfAnnaType.output
)spool d01fcfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01fcfAnnaType
--R
--R d01fcfAnnaType  is a domain constructor
--R Abbreviation for d01fcfAnnaType is D01FCFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01FCFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompl
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Order
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedComple
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Ordere
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01fcfAnnaType.help —

```
=====================================================================
d01fcfAnnaType examples
```

```
=======================================================================

See Also:
o )show d01fcfAnnaType
```

5.27.1 d01fcfAnnaType (D01FCFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01FCFA d01fcfAnnaType —

```
)abbrev domain D01FCFA d01fcfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01fcfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01FCF, a numerical integration routine which can
++ handle multi-dimensional quadrature over a finite region.  The
++ function \axiomFun{measure} measures the usefulness of the routine D01GBF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01fcfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
```

```
DF  ==> DoubleFloat
FI  ==> Fraction Integer
EFI  ==> Expression Fraction Integer
SOCDF  ==> Segment OrderedCompletion DoubleFloat
NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
INT  ==> Integer
BOP  ==> BasicOperator
S  ==> Symbol
ST  ==> String
LST  ==> List String
RT  ==> RoutinesTable
Rep:=Result
import Rep, d01AgentsPackage, NagIntegrationPackage

measure(R:RT,args:MDNIA) ==
  ext:Result := empty()$Result
  segs := args.range
  vars := variables(args.fn)$EDF
  for i in 1..# vars repeat
    nia:NIA := [vars.i,args.fn,segs.i,args.abserr,args.relerr]
    not rangeIsFinite(nia) case finite => return
      [0.0,"d01fcf is not a suitable routine for infinite integrals",ext]
  [getMeasure(R,d01fcf@S)$RT, "Recommended is d01fcf", ext]

numericalIntegration(args:MDNIA,hints:Result) ==
  import Integer
  segs := args.range
  dim := # segs
  err := args.relerr
  low:Matrix DF := matrix([[getlo(segs.i) for i in 1..dim]])$(Matrix DF)
  high:Matrix DF := matrix([[gethi(segs.i) for i in 1..dim]])$(Matrix DF)
  b:Float := getButtonValue("d01fcf","functionEvaluations")$AttributeButtons
  a:Float:= exp(1.1513*(1.0/(2.0*(1.0-b))))
  alpha:INT := 2**dim+2*dim**2+2*dim+1
  d:Float := max(1.e-3,nthRoot(convert(err)@Float,4))$Float
  minpts:INT := (fEvals := wholePart(a))*wholePart(alpha::Float/d)
  maxpts:INT := 5*minpts
  lenwrk:INT := (dim+2)*(1+(33*fEvals))
  ArgsFn := map(x+->convert(x)$DF,args.fn)$EF2(DF,Float)
  f : Union(fn:FileName,fp:Asp4(FUNCTN)) := [retract(ArgsFn)$Asp4(FUNCTN)]
  out:Result := d01fcf(dim,low,high,maxpts,err,lenwrk,minpts,-1,f)
  changeName(finval@Symbol,result@Symbol,out)
```

———-

— D01FCFA.dotabb —

```
"D01FCFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01FCFA"]
"TRANFUN" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TRANFUN"]
"D01FCFA" -> "TRANFUN"
```

———-

5.28 domain D01GBFA d01gbfAnnaType

— **d01gbfAnnaType.input** —

```
)set break resume
)sys rm -f d01gbfAnnaType.output
)spool d01gbfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01gbfAnnaType
--R
--R d01gbfAnnaType  is a domain constructor
--R Abbreviation for d01gbfAnnaType is D01GBFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01GBFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(Double
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion
--R
--E 1

)spool
)lisp (bye)
```

———-


— **d01gbfAnnaType.help** —

```
=======================================================================
d01gbfAnnaType examples
```

```
=============================================================================

See Also:
o )show d01gbfAnnaType
```

5.28.1 d01gbfAnnaType (D01GBFA)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01GBFA d01gbfAnnaType —

```
)abbrev domain D01GBFA d01gbfAnnaType
++ Author: Brian Dupee
++ Date Created: March 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{d01gbfAnnaType} is a domain of
++ \axiomType{NumericalIntegrationCategory}
++ for the NAG routine D01GBF, a numerical integration routine which can
++ handle multi-dimensional quadrature over a finite region.  The
++ function \axiomFun{measure} measures the usefulness of the routine D01GBF
++ for the given problem.  The function \axiomFun{numericalIntegration}
++ performs the integration by using \axiomType{NagIntegrationPackage}.

d01gbfAnnaType(): NumericalIntegrationCategory == Result add
  EF2  ==> ExpressionFunctions2
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
```

```
DF  ==> DoubleFloat
FI  ==> Fraction Integer
EFI  ==> Expression Fraction Integer
SOCDF  ==> Segment OrderedCompletion DoubleFloat
NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
MDNIA  ==> Record(fn:EDF,range:List SOCDF,abserr:DF,relerr:DF)
INT  ==> Integer
BOP  ==> BasicOperator
S  ==> Symbol
ST  ==> String
LST  ==> List String
RT  ==> RoutinesTable
Rep:=Result
import Rep, d01AgentsPackage, NagIntegrationPackage

measure(R:RT,args:MDNIA) ==
  ext:Result := empty()$Result
  (rel := args.relerr) < 0.01 :: DF =>
    [0.1, "d01gbf: The relative error requirement is too small",ext]
  segs := args.range
  vars := variables(args.fn)$EDF
  for i in 1..# vars repeat
    nia:NIA := [vars.i,args.fn,segs.i,args.abserr,rel]
    not rangeIsFinite(nia) case finite => return
      [0.0,"d01gbf is not a suitable routine for infinite integrals",ext]
  [getMeasure(R,d01gbf@S)$RT, "Recommended is d01gbf", ext]

numericalIntegration(args:MDNIA,hints:Result) ==
  import Integer
  segs := args.range
  dim:INT := # segs
  low:Matrix DF := matrix([[getlo(segs.i) for i in 1..dim]])$(Matrix DF)
  high:Matrix DF := matrix([[gethi(segs.i) for i in 1..dim]])$(Matrix DF)
  b:Float := getButtonValue("d01gbf","functionEvaluations")$AttributeButtons
  a:Float:= exp(1.1513*(1.0/(2.0*(1.0-b))))
  maxcls:INT := 1500*(dim+1)*(fEvals:INT := wholePart(a))
  mincls:INT := 300*fEvals
  c:Float := nthRoot((maxcls::Float)/4.0,dim)$Float
  lenwrk:INT := 3*dim*(d:INT := wholePart(c))+10*dim
  wrkstr:Matrix DF := matrix([[0$DF for i in 1..lenwrk]])$(Matrix DF)
  ArgsFn := map(x+->convert(x)$DF,args.fn)$EF2(DF,Float)
  f : Union(fn:FileName,fp:Asp4(FUNCTN)) := [retract(ArgsFn)$Asp4(FUNCTN)]
  out:Result := _
     d01gbf(dim,low,high,maxcls,args.relerr,lenwrk,mincls,wrkstr,-1,f)
  changeName(finest@Symbol,result@Symbol,out)
```

— D01GBFA.dotabb —

```
"D01GBFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01GBFA"]
"RADCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RADCAT"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"D01GBFA" -> "FIELD"
"D01GBFA" -> "RADCAT"
"D01GBFA" -> "FLAGG"
```

———-

5.29 domain D01TRNS d01TransformFunctionType

— d01TransformFunctionType.input —

```
)set break resume
)sys rm -f d01TransformFunctionType.output
)spool d01TransformFunctionType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d01TransformFunctionType
--R
--R d01TransformFunctionType  is a domain constructor
--R Abbreviation for d01TransformFunctionType is D01TRNS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D01TRNS
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompl
--R measure : (RoutinesTable,Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Order
--R numericalIntegration : (Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedComple
--R numericalIntegration : (Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Ordere
--R
--E 1

)spool
)lisp (bye)
```

———-


— d01TransformFunctionType.help —

```
=====================================================================
d01TransformFunctionType examples
=====================================================================

See Also:
o )show d01TransformFunctionType
```

———-

5.29.1 d01TransformFunctionType (D01TRNS)



Exports:
coerce hash latex measure numericalIntegration ?=? ?~=?

— domain D01TRNS d01TransformFunctionType —

```
)abbrev domain D01TRNS d01TransformFunctionType
++ Author: Brian Dupee
++ Date Created: April 1994
++ Date Last Updated: December 1997
++ Basic Operations: measure, numericalIntegration
++ Related Constructors: Result, RoutinesTable
++ Description:
++ Since an infinite integral cannot be evaluated numerically
++ it is necessary to transform the integral onto finite ranges.
++ \axiomType{d01TransformFunctionType} uses the mapping \spad{x -> 1/x}
++ and contains the functions \axiomFun{measure} and
++ \axiomFun{numericalIntegration}.

EDF  ==> Expression DoubleFloat
```

```
EEDF  ==> Equation Expression DoubleFloat
FI  ==> Fraction Integer
EFI  ==> Expression Fraction Integer
EEFI  ==> Equation Expression Fraction Integer
EF2  ==> ExpressionFunctions2
DF  ==> DoubleFloat
F  ==> Float
SOCDF  ==> Segment OrderedCompletion DoubleFloat
OCDF  ==> OrderedCompletion DoubleFloat
NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
INT     ==> Integer
PI  ==> PositiveInteger
HINT  ==> Record(str:String,fn:EDF,range:SOCDF,ext:Result)
S  ==> Symbol
ST  ==> String
LST  ==> List String
Measure  ==> Record(measure:F,explanations:ST,extra:Result)
MS  ==> Record(measure:F,name:ST,explanations:LST,extra:Result)

d01TransformFunctionType():NumericalIntegrationCategory == Result add
  Rep:=Result
  import d01AgentsPackage,Rep

  rec2any(re:Record(str:ST,fn:EDF,range:SOCDF)):Any ==
    coerce(re)$AnyFunctions1(Record(str:ST,fn:EDF,range:SOCDF))

  changeName(ans:Result,name:ST):Result ==
    sy:S := coerce(name "Answer")$S
    anyAns:Any := coerce(ans)$AnyFunctions1(Result)
    construct([[sy,anyAns]])$Result

  getIntegral(args:NIA,hint:HINT) : Result ==
   Args := copy args
   Args.fn := hint.fn
   Args.range := hint.range
   integrate(Args::NumericalIntegrationProblem)$AnnaNumericalIntegrationPackage

  transformFunction(args:NIA) : NIA ==
    Args := copy args
    Var := Args.var :: EFI                -- coerce Symbol to EFI
    NewVar:EFI := inv(Var)$EFI            -- invert it
    VarEqn:EEFI:=equation(Var,NewVar)$EEFI -- turn it into an equation
    Afn:EFI := edf2efi(Args.fn)$ExpertSystemToolsPackage
    Afn := subst(Afn,VarEqn)$EFI          -- substitute into function
    Var2:EFI := Var**2
    Afn:= simplify(Afn/Var2)$TranscendentalManipulations(FI,EFI)
    Args.fn:= map(x+->convert(x)$FI,Afn)$EF2(FI,DF)
    Args

  doit(seg:SOCDF,args:NIA):MS ==
```

```
    Args := copy args
    Args.range := seg
    measure(Args::NumericalIntegrationProblem)$AnnaNumericalIntegrationPackage

  transform(c:Boolean,args:NIA):Measure ==
    if c then
      l := coerce(recip(lo(args.range)))@OCDF
      Seg:SOCDF := segment(0$OCDF,l)
    else
      h := coerce(recip(hi(args.range)))@OCDF
      Seg:SOCDF := segment(h,0$OCDF)
    Args := transformFunction(args)
    m:MS := doit(Seg,Args)
    out1:ST :=
       "The recommendation is to transform the function and use " m.name
    out2:List(HINT) := [[m.name,Args.fn,Seg,m.extra]]
    out2Any:Any := coerce(out2)$AnyFunctions1(List(HINT))
    ex:Record(key:S,entry:Any) := [d01transformextra@S,out2Any]
    extr:Result := construct([ex])$Result
    [m.measure,out1,extr]

  split(c:PI,args:NIA):Measure ==
    Args := copy args
    Args.relerr := Args.relerr/2
    Args.abserr := Args.abserr/2
    if (c = 1)@Boolean then
      seg1:SOCDF := segment(-1$OCDF,1$OCDF)
    else if (c = 2)@Boolean then
      seg1 := segment(lo(Args.range),1$OCDF)
    else
      seg1 := segment(-1$OCDF,hi(Args.range))
    m1:MS := doit(seg1,Args)
    Args := transformFunction Args
    if (c = 2)@Boolean then
      seg2:SOCDF := segment(0$OCDF,1$OCDF)
    else if (c = 3)@Boolean then
      seg2 := segment(-1$OCDF,0$OCDF)
    else seg2 := seg1
    m2:MS := doit(seg2,Args)
    m1m:F := m1.measure
    m2m:F := m2.measure
    m:F := m1m*m2m/((m1m*m2m)+(1.0-m1m)*(1.0-m2m))
    out1:ST := "The recommendation is to transform the function and use "
                               m1.name " and " m2.name
    out2:List(HINT) :=
             [[m1.name,args.fn,seg1,m1.extra],[m2.name,Args.fn,seg2,m2.extra]]
    out2Any:Any := coerce(out2)$AnyFunctions1(List(HINT))
    ex:Record(key:S,entry:Any) := [d01transformextra@S,out2Any]
    extr:Result := construct([ex])$Result
    [m,out1,extr]
```

```
  measure(R:RoutinesTable,args:NIA) ==
    Range:=rangeIsFinite(args)
    Range case bothInfinite => split(1,args)
    Range case upperInfinite =>
      positive?(lo(args.range))$OCDF =>
        transform(true,args)
      split(2,args)
    Range case lowerInfinite =>
      negative?(hi(args.range))$OCDF =>
        transform(false,args)
      split(3,args)

  numericalIntegration(args:NIA,hints:Result) ==
    mainResult:DF := mainAbserr:DF := 0$DF
    ans:Result := empty()$Result
    hla:Any := coerce(search((d01transformextra@S),hints)$Result)@Any
    hintList := retract(hla)$AnyFunctions1(List(HINT))
    methodName:ST := empty()$ST
    repeat
      if (empty?(hintList)$(List(HINT)))
        then leave
      item := first(hintList)$List(HINT)
      a:Result := getIntegral(args,item)
      anyRes := coerce(search((result@S),a)$Result)@Any
      midResult := retract(anyRes)$AnyFunctions1(DF)
      anyErr := coerce(search((abserr pretend S),a)$Result)@Any
      midAbserr := retract(anyErr)$AnyFunctions1(DF)
      mainResult := mainResult+midResult
      mainAbserr := mainAbserr+midAbserr
      if (methodName = item.str)@Boolean then
        methodName := concat([item.str,"1"])$ST
      else
        methodName := item.str
      ans := concat(ans,changeName(a,methodName))$ExpertSystemToolsPackage
      hintList := rest(hintList)$(List(HINT))
    anyResult := coerce(mainResult)$AnyFunctions1(DF)
    anyAbserr := coerce(mainAbserr)$AnyFunctions1(DF)
    recResult:Record(key:S,entry:Any):=[result@S,anyResult]
    recAbserr:Record(key:S,entry:Any):=[abserr pretend S,anyAbserr]
    insert!(recAbserr,insert!(recResult,ans))$Result
```

———-

— D01TRNS.dotabb —

```
"D01TRNS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D01TRNS"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
```

```
"D01TRNS" -> "FS"
```

———-

5.30 domain D02BBFA d02bbfAnnaType

— **d02bbfAnnaType.input** —

```
)set break resume
)sys rm -f d02bbfAnnaType.output
)spool d02bbfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d02bbfAnnaType
--R
--R d02bbfAnnaType  is a domain constructor
--R Abbreviation for d02bbfAnnaType is D02BBFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D02BBFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R ODESolve : Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)),yinit: List(
--R measure : (RoutinesTable,Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat))
--R
--E 1

)spool
)lisp (bye)
```

———-


— **d02bbfAnnaType.help** —

```
==========================================================================
d02bbfAnnaType examples
==========================================================================

See Also:
o )show d02bbfAnnaType
```

———-

5.30.1 d02bbfAnnaType (D02BBFA)



Exports:
coerce hash latex measure ODESolve ?=? ?~=?

— domain D02BBFA d02bbfAnnaType —

```
)abbrev domain D02BBFA d02bbfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1995
++ Date Last Updated: January 1996
++ Basic Operations:
++ Description:
++ \axiomType{d02bbfAnnaType} is a domain of
++ \axiomType{OrdinaryDifferentialEquationsInitialValueProblemSolverCategory}
++ for the NAG routine D02BBF, a ODE routine which uses an
++ Runge-Kutta method to solve a system of differential
++ equations.  The function \axiomFun{measure} measures the
++ usefulness of the routine D02BBF for the given problem.  The
++ function \axiomFun{ODESolve} performs the integration by using
++ \axiomType{NagOrdinaryDifferentialEquationsPackage}.

d02bbfAnnaType():OrdinaryDifferentialEquationsSolverCategory == Result add
  -- Runge Kutta

  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  MDF  ==> Matrix DoubleFloat
  DF  ==> DoubleFloat
  F  ==> Float
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
```

```
VEDF  ==> Vector Expression DoubleFloat
VEF  ==> Vector Expression Float
EF  ==> Expression Float
VDF  ==> Vector DoubleFloat
VMF  ==> Vector MachineFloat
MF  ==> MachineFloat
ODEA  ==> Record(xinit:DF,xend:DF,fn:VEDF,yinit:LDF,intvals:LDF,_
                   g:EDF,abserr:DF,relerr:DF)
RSS  ==> Record(stiffnessFactor:F,stabilityFactor:F)
INT  ==> Integer
EF2  ==> ExpressionFunctions2

import d02AgentsPackage, NagOrdinaryDifferentialEquationsPackage
import AttributeButtons

accuracyCF(ode:ODEA):F ==
  b := getButtonValue("d02bbf","accuracy")$AttributeButtons
  accuracyIntensityValue := combineFeatureCompatibility(b,accuracyIF(ode))
  accuracyIntensityValue > 0.999 => 0$F
  0.8*exp(-((10*accuracyIntensityValue)**3)$F/266)$F

stiffnessCF(stiffnessIntensityValue:F):F ==
  b := getButtonValue("d02bbf","stiffness")$AttributeButtons
  0.5*exp(-(2*combineFeatureCompatibility(b,stiffnessIntensityValue))**2)$F

stabilityCF(stabilityIntensityValue:F):F ==
  b := getButtonValue("d02bbf","stability")$AttributeButtons
  0.5 * cos(combineFeatureCompatibility(b,stabilityIntensityValue))$F

expenseOfEvaluationCF(ode:ODEA):F ==
  b := getButtonValue("d02bbf","expense")$AttributeButtons
  expenseOfEvaluationIntensityValue :=
    combineFeatureCompatibility(b,expenseOfEvaluationIF(ode))
  0.35+0.2*exp(-(2.0*expenseOfEvaluationIntensityValue)**3)$F

measure(R:RoutinesTable,args:ODEA) ==
  m := getMeasure(R,d02bbf :: Symbol)$RoutinesTable
  ssf := stiffnessAndStabilityOfODEIF args
  m := combineFeatureCompatibility(m,[accuracyCF(args),
          stiffnessCF(ssf.stiffnessFactor),
            expenseOfEvaluationCF(args),
              stabilityCF(ssf.stabilityFactor)])
  [m,"Runge-Kutta Merson method"]

ODESolve(ode:ODEA) ==
  i:LDF := ode.intvals
  M := inc(# i)$INT
  irelab := 0$INT
  if positive?(a := ode.abserr) then
    inc(irelab)$INT
```

```
    if positive?(r := ode.relerr) then
      inc(irelab)$INT
    if positive?(a+r) then
      tol:DF := a + r
    else
      tol := float(1,-4,10)$DF
    asp7:Union(fn:FileName,fp:Asp7(FCN)) :=
      [retract(vedf2vef(ode.fn)$ExpertSystemToolsPackage)$Asp7(FCN)]
    asp8:Union(fn:FileName,fp:Asp8(OUTPUT)) :=
      [coerce(ldf2vmf(i)$ExpertSystemToolsPackage)$Asp8(OUTPUT)]
    d02bbf(ode.xend,M,# ode.fn,irelab,ode.xinit,matrix([ode.yinit])$MDF,
             tol,-1,asp7,asp8)
```

———-

— D02BBFA.dotabb —

```
"D02BBFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D02BBFA"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"D02BBFA" -> "IVECTOR"
```

———-

5.31 domain D02BHFA d02bhfAnnaType

— d02bhfAnnaType.input —

```
)set break resume
)sys rm -f d02bhfAnnaType.output
)spool d02bhfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d02bhfAnnaType
--R
--R d02bhfAnnaType  is a domain constructor
--R Abbreviation for d02bhfAnnaType is D02BHFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D02BHFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
```

```
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R ODESolve : Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)),yinit: List(
--R measure : (RoutinesTable,Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)
--R
--E 1

)spool
)lisp (bye)
```

———-


— d02bhfAnnaType.help —

```
========================================================================
d02bhfAnnaType examples
========================================================================

See Also:
o )show d02bhfAnnaType
```

———-

5.31.1 d02bhfAnnaType (D02BHFA)



Exports:
coerce hash latex measure ODESolve ?=? ?~=?

— domain D02BHFA d02bhfAnnaType —

```
)abbrev domain D02BHFA d02bhfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1995
```

```
++ Date Last Updated: January 1996
++ Basic Operations:
++ Description:
++ \axiomType{d02bhfAnnaType} is a domain of
++ \axiomType{OrdinaryDifferentialEquationsInitialValueProblemSolverCategory}
++ for the NAG routine D02BHF, a ODE routine which uses an
++ Runge-Kutta method to solve a system of differential
++ equations.  The function \axiomFun{measure} measures the
++ usefulness of the routine D02BHF for the given problem.  The
++ function \axiomFun{ODESolve} performs the integration by using
++ \axiomType{NagOrdinaryDifferentialEquationsPackage}.

d02bhfAnnaType():OrdinaryDifferentialEquationsSolverCategory == Result add
  -- Runge Kutta
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  MDF  ==> Matrix DoubleFloat
  DF  ==> DoubleFloat
  F  ==> Float
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  VEDF  ==> Vector Expression DoubleFloat
  VEF  ==> Vector Expression Float
  EF  ==> Expression Float
  VDF  ==> Vector DoubleFloat
  VMF  ==> Vector MachineFloat
  MF  ==> MachineFloat
  ODEA  ==> Record(xinit:DF,xend:DF,fn:VEDF,yinit:LDF,intvals:LDF,_
                     g:EDF,abserr:DF,relerr:DF)
  RSS  ==> Record(stiffnessFactor:F,stabilityFactor:F)
  INT  ==> Integer
  EF2  ==> ExpressionFunctions2

  import d02AgentsPackage, NagOrdinaryDifferentialEquationsPackage
  import AttributeButtons

  accuracyCF(ode:ODEA):F ==
    b := getButtonValue("d02bhf","accuracy")$AttributeButtons
    accuracyIntensityValue := combineFeatureCompatibility(b,accuracyIF(ode))
    accuracyIntensityValue > 0.999 => 0$F
    0.8*exp(-((10*accuracyIntensityValue)**3)$F/266)$F

  stiffnessCF(stiffnessIntensityValue:F):F ==
    b := getButtonValue("d02bhf","stiffness")$AttributeButtons
    0.5*exp(-(2*combineFeatureCompatibility(b,stiffnessIntensityValue))**2)$F

  stabilityCF(stabilityIntensityValue:F):F ==
    b := getButtonValue("d02bhf","stability")$AttributeButtons
    0.5 * cos(combineFeatureCompatibility(b,stabilityIntensityValue))$F
```

```
  expenseOfEvaluationCF(ode:ODEA):F ==
    b := getButtonValue("d02bhf","expense")$AttributeButtons
    expenseOfEvaluationIntensityValue :=
      combineFeatureCompatibility(b,expenseOfEvaluationIF(ode))
    0.35+0.2*exp(-(2.0*expenseOfEvaluationIntensityValue)**3)$F

  measure(R:RoutinesTable,args:ODEA) ==
    m := getMeasure(R,d02bhf :: Symbol)$RoutinesTable
    ssf := stiffnessAndStabilityOfODEIF args
    m := combineFeatureCompatibility(m,[accuracyCF(args),
           stiffnessCF(ssf.stiffnessFactor),
             expenseOfEvaluationCF(args),
               stabilityCF(ssf.stabilityFactor)])
    [m,"Runge-Kutta Merson method"]

  ODESolve(ode:ODEA) ==
    irelab := 0$INT
    if positive?(a := ode.abserr) then
      inc(irelab)$INT
    if positive?(r := ode.relerr) then
      inc(irelab)$INT
    if positive?(a+r) then
      tol := max(a,r)$DF
    else
      tol:DF := float(1,-4,10)$DF
    asp7:Union(fn:FileName,fp:Asp7(FCN)) :=
      [retract(e:VEF := vedf2vef(ode.fn)$ExpertSystemToolsPackage)$Asp7(FCN)]
    asp9:Union(fn:FileName,fp:Asp9(G)) :=
      [retract(edf2ef(ode.g)$ExpertSystemToolsPackage)$Asp9(G)]
    d02bhf(ode.xend,# e,irelab,0$DF,ode.xinit,matrix([ode.yinit])$MDF,
             tol,-1,asp9,asp7)
```

———-

— D02BHFA.dotabb —

```
"D02BHFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D02BHFA"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"D02BHFA" -> "IVECTOR"
```

———-

5.32 domain D02CJFA d02cjfAnnaType

— d02cjfAnnaType.input —

```
)set break resume
)sys rm -f d02cjfAnnaType.output
)spool d02cjfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d02cjfAnnaType
--R
--R d02cjfAnnaType  is a domain constructor
--R Abbreviation for d02cjfAnnaType is D02CJFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D02CJFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R ODESolve : Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)),y
--R measure : (RoutinesTable,Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(D
--R
--E 1

)spool
)lisp (bye)
```

———-


— d02cjfAnnaType.help —

```
=====================================================================
d02cjfAnnaType examples
=====================================================================

See Also:
o )show d02cjfAnnaType
```

———-

5.32.1 d02cjfAnnaType (D02CJFA)



Exports:
coerce hash latex measure ODESolve ?=? ?~=?

— domain D02CJFA d02cjfAnnaType —

```
)abbrev domain D02CJFA d02cjfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1995
++ Date Last Updated: January 1996
++ Basic Operations:
++ Description:
++ \axiomType{d02cjfAnnaType} is a domain of
++ \axiomType{OrdinaryDifferentialEquationsInitialValueProblemSolverCategory}
++ for the NAG routine D02CJF, a ODE routine which uses an
++ Adams-Moulton-Bashworth method to solve a system of differential
++ equations.  The function \axiomFun{measure} measures the
++ usefulness of the routine D02CJF for the given problem.  The
++ function \axiomFun{ODESolve} performs the integration by using
++ \axiomType{NagOrdinaryDifferentialEquationsPackage}.

d02cjfAnnaType():OrdinaryDifferentialEquationsSolverCategory == Result add
  -- Adams
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  MDF  ==> Matrix DoubleFloat
  DF  ==> DoubleFloat
  F  ==> Float
  FI  ==> Fraction Integer
  EFI  ==> Expression Fraction Integer
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  VEDF  ==> Vector Expression DoubleFloat
  VEF  ==> Vector Expression Float
  EF  ==> Expression Float
  VDF  ==> Vector DoubleFloat
  VMF  ==> Vector MachineFloat
```

```
MF  ==> MachineFloat
ODEA  ==> Record(xinit:DF,xend:DF,fn:VEDF,yinit:LDF,intvals:LDF,_
                    g:EDF,abserr:DF,relerr:DF)
RSS  ==> Record(stiffnessFactor:F,stabilityFactor:F)
INT  ==> Integer
EF2  ==> ExpressionFunctions2

import d02AgentsPackage, NagOrdinaryDifferentialEquationsPackage

accuracyCF(ode:ODEA):F ==
  b := getButtonValue("d02cjf","accuracy")$AttributeButtons
  accuracyIntensityValue := combineFeatureCompatibility(b,accuracyIF(ode))
  accuracyIntensityValue > 0.9999 => 0$F
  0.6*(cos(accuracyIntensityValue*(pi()$F)/2)$F)**0.755

stiffnessCF(ode:ODEA):F ==
  b := getButtonValue("d02cjf","stiffness")$AttributeButtons
  ssf := stiffnessAndStabilityOfODEIF ode
  stiffnessIntensityValue :=
    combineFeatureCompatibility(b,ssf.stiffnessFactor)
  0.5*exp(-(1.1*stiffnessIntensityValue)**3)$F

measure(R:RoutinesTable,args:ODEA) ==
  m := getMeasure(R,d02cjf :: Symbol)$RoutinesTable
  m := combineFeatureCompatibility(m,[accuracyCF(args), stiffnessCF(args)])
  [m,"Adams method"]

ODESolve(ode:ODEA) ==
  i:LDF := ode.intvals
  if empty?(i) then
    i := [ode.xend]
  M := inc(# i)$INT
  if positive?((a := ode.abserr)*(r := ode.relerr))$DF then
    ire:String := "D"
  else
    if positive?(a) then
      ire:String := "A"
    else
      ire:String := "R"
  tol := max(a,r)$DF
  asp7:Union(fn:FileName,fp:Asp7(FCN)) :=
    [retract(e:VEF := vedf2vef(ode.fn)$ExpertSystemToolsPackage)$Asp7(FCN)]
  asp8:Union(fn:FileName,fp:Asp8(OUTPUT)) :=
    [coerce(ldf2vmf(i)$ExpertSystemToolsPackage)$Asp8(OUTPUT)]
  asp9:Union(fn:FileName,fp:Asp9(G)) :=
    [retract(edf2ef(ode.g)$ExpertSystemToolsPackage)$Asp9(G)]
  d02cjf(ode.xend,M,# e,tol,ire,ode.xinit,matrix([ode.yinit])$MDF,
           -1,asp9,asp7,asp8)
```

———-

— **D02CJFA.dotabb** —

```
"D02CJFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D02CJFA"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"D02CJFA" -> "IVECTOR"
```

———-

5.33 domain D02EJFA d02ejfAnnaType

— **d02ejfAnnaType.input** —

```
)set break resume
)sys rm -f d02ejfAnnaType.output
)spool d02ejfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d02ejfAnnaType
--R
--R d02ejfAnnaType  is a domain constructor
--R Abbreviation for d02ejfAnnaType is D02EJFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D02EJFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R ODESolve : Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)),yinit: List(
--R measure : (RoutinesTable,Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat))
--R
--E 1

)spool
)lisp (bye)
```

———-


— **d02ejfAnnaType.help** —

```
========================================================================
d02ejfAnnaType examples
========================================================================

See Also:
o )show d02ejfAnnaType
```

———-

5.33.1 d02ejfAnnaType (D02EJFA)



Exports:
coerce hash latex measure ODESolve ?=? ?~=?

— domain D02EJFA d02ejfAnnaType —

```
)abbrev domain D02EJFA d02ejfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1995
++ Date Last Updated: January 1996
++ Basic Operations:
++ Description:
++ \axiomType{d02ejfAnnaType} is a domain of
++ \axiomType{OrdinaryDifferentialEquationsInitialValueProblemSolverCategory}
++ for the NAG routine D02EJF, a ODE routine which uses a backward
++ differentiation formulae method to handle a stiff system
++ of differential equations.  The function \axiomFun{measure} measures
++ the usefulness of the routine D02EJF for the given problem.  The
++ function \axiomFun{ODESolve} performs the integration by using
++ \axiomType{NagOrdinaryDifferentialEquationsPackage}.

d02ejfAnnaType():OrdinaryDifferentialEquationsSolverCategory == Result add
  -- BDF "Stiff"
  EDF  ==> Expression DoubleFloat
```

```
LDF  ==> List DoubleFloat
MDF  ==> Matrix DoubleFloat
DF  ==> DoubleFloat
F  ==> Float
FI  ==> Fraction Integer
EFI  ==> Expression Fraction Integer
SOCDF  ==> Segment OrderedCompletion DoubleFloat
VEDF  ==> Vector Expression DoubleFloat
VEF  ==> Vector Expression Float
EF  ==> Expression Float
VDF  ==> Vector DoubleFloat
VMF  ==> Vector MachineFloat
MF  ==> MachineFloat
ODEA  ==> Record(xinit:DF,xend:DF,fn:VEDF,yinit:LDF,intvals:LDF,_
                  g:EDF,abserr:DF,relerr:DF)
RSS  ==> Record(stiffnessFactor:F,stabilityFactor:F)
INT  ==> Integer
EF2  ==> ExpressionFunctions2

import d02AgentsPackage, NagOrdinaryDifferentialEquationsPackage

accuracyCF(ode:ODEA):F ==
  b := getButtonValue("d02ejf","accuracy")$AttributeButtons
  accuracyIntensityValue :=  combineFeatureCompatibility(b,accuracyIF(ode))
  accuracyIntensityValue > 0.999 => 0$F
  0.5*exp(-((10*accuracyIntensityValue)**3)$F/250)$F

intermediateResultsCF(ode:ODEA):F ==
  intermediateResultsIntensityValue := intermediateResultsIF(ode)
  i := 0.5 * exp(-(intermediateResultsIntensityValue/1.649)**3)$F
  a := accuracyCF(ode)
  i+(0.5-i)*(0.5-a)

stabilityCF(ode:ODEA):F ==
  b := getButtonValue("d02ejf","stability")$AttributeButtons
  ssf := stiffnessAndStabilityOfODEIF ode
  stabilityIntensityValue :=
    combineFeatureCompatibility(b,ssf.stabilityFactor)
  0.68 - 0.5 * exp(-(stabilityIntensityValue)**3)$F

expenseOfEvaluationCF(ode:ODEA):F ==
  b := getButtonValue("d02ejf","expense")$AttributeButtons
  expenseOfEvaluationIntensityValue :=
    combineFeatureCompatibility(b,expenseOfEvaluationIF(ode))
  0.5 * exp(-(1.7*expenseOfEvaluationIntensityValue)**3)$F

systemSizeCF(args:ODEA):F ==
  (1$F - systemSizeIF(args))/2.0

measure(R:RoutinesTable,args:ODEA) ==
```

```
    arg := copy args
    m := getMeasure(R,d02ejf :: Symbol)$RoutinesTable
    m := combineFeatureCompatibility(m,[intermediateResultsCF(arg),
           accuracyCF(arg),
             systemSizeCF(arg),
               expenseOfEvaluationCF(arg),
                 stabilityCF(arg)])
    [m,"BDF method for Stiff Systems"]

  ODESolve(ode:ODEA) ==
    i:LDF := ode.intvals
    m := inc(# i)$INT
    if positive?((a := ode.abserr)*(r := ode.relerr))$DF then
      ire:String := "D"
    else
      if positive?(a) then
        ire:String := "A"
      else
        ire:String := "R"
    if positive?(a+r)$DF then
      tol := max(a,r)$DF
    else
      tol := float(1,-4,10)$DF
    asp7:Union(fn:FileName,fp:Asp7(FCN)) :=
      [retract(e:VEF := vedf2vef(ode.fn)$ExpertSystemToolsPackage)$Asp7(FCN)]
    asp31:Union(fn:FileName,fp:Asp31(PEDERV)) :=
      [retract(e)$Asp31(PEDERV)]
    asp8:Union(fn:FileName,fp:Asp8(OUTPUT)) :=
      [coerce(ldf2vmf(i)$ExpertSystemToolsPackage)$Asp8(OUTPUT)]
    asp9:Union(fn:FileName,fp:Asp9(G)) :=
      [retract(edf2ef(ode.g)$ExpertSystemToolsPackage)$Asp9(G)]
    n:INT := # ode.yinit
    iw:INT := (12+n)*n+50
    ans := d02ejf(ode.xend,m,n,ire,iw,ode.xinit,matrix([ode.yinit])$MDF,
             tol,-1,asp9,asp7,asp31,asp8)
```

———-

— D02EJFA.dotabb —

```
"D02EJFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D02EJFA"]
"RADCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RADCAT"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FIELD-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FIELD"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"D02EJFA" -> "FLAGG"
"D02EJFA" -> "FIELD-"
"D02EJFA" -> "FIELD"
```

```
"D02EJFA" -> "RADCAT"
```

———-

5.34 domain D03EEFA d03eefAnnaType

— **d03eefAnnaType.input** —

```
)set break resume
)sys rm -f d03eefAnnaType.output
)spool d03eefAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d03eefAnnaType
--R
--R d03eefAnnaType  is a domain constructor
--R Abbreviation for d03eefAnnaType is D03EEFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D03EEFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R PDESolve : Record(pde: List(Expression(DoubleFloat)),constraints: List(Record(start: DoubleFloat,finish
--R measure : (RoutinesTable,Record(pde: List(Expression(DoubleFloat)),constraints: List(Record(start: Doubl
--R
--E 1

)spool
)lisp (bye)
```

———-


— **d03eefAnnaType.help** —

```
==========================================================================
d03eefAnnaType examples
==========================================================================

See Also:
o )show d03eefAnnaType
```

———-

5.34.1 d03eefAnnaType (D03EEFA)



Exports:
coerce hash latex measure PDESolve ?=? ?~=?

— domain D03EEFA d03eefAnnaType —

```
)abbrev domain D03EEFA d03eefAnnaType
++ Author: Brian Dupee
++ Date Created: June 1996
++ Date Last Updated: June 1996
++ Basic Operations:
++ Description:
++ \axiomType{d03eefAnnaType} is a domain of
++ \axiomType{PartialDifferentialEquationsSolverCategory}
++ for the NAG routines D03EEF/D03EDF.

d03eefAnnaType():PartialDifferentialEquationsSolverCategory == Result add
  -- 2D Elliptic PDE
  LEDF  ==> List Expression DoubleFloat
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  MDF  ==> Matrix DoubleFloat
  DF  ==> DoubleFloat
  F  ==> Float
  FI  ==> Fraction Integer
  VEF  ==> Vector Expression Float
  EF  ==> Expression Float
  MEF  ==> Matrix Expression Float
  NNI  ==> NonNegativeInteger
  INT  ==> Integer
  PDEC  ==> Record(start:DF, finish:DF, grid:NNI, boundaryType:INT,
                   dStart:MDF, dFinish:MDF)
```

```
PDEB  ==> Record(pde:LEDF, constraints:List PDEC,
                   f:List LEDF, st:String, tol:DF)

import d03AgentsPackage, NagPartialDifferentialEquationsPackage
import ExpertSystemToolsPackage

measure(R:RoutinesTable,args:PDEB) ==
  (# (args.constraints) > 2)@Boolean =>
    [0$F,"d03eef/d03edf is unsuitable for PDEs of order more than 2"]
  elliptic?(args) =>
    m := getMeasure(R,d03eef :: Symbol)$RoutinesTable
    [m,"d03eef/d03edf is suitable"]
  [0$F,"d03eef/d03edf is unsuitable for hyperbolic or parabolic PDEs"]

PDESolve(args:PDEB) ==
  xcon := first(args.constraints)
  ycon := second(args.constraints)
  nx := xcon.grid
  ny := ycon.grid
  p := args.pde
  x1 := xcon.start
  x2 := xcon.finish
  y1 := ycon.start
  y2 := ycon.finish
  lda := ((4*(nx+1)*(ny+1)+2) quo 3)$INT
  scheme:String :=
   central?((x2-x1)/2,(y2-y1)/2,args.pde) => "C"
   "U"
  asp73:Union(fn:FileName,fp:Asp73(PDEF)) :=
   [retract(vector([edf2ef u for u in p])$VEF)$Asp73(PDEF)]
  asp74:Union(fn:FileName,fp:Asp74(BNDY)) :=
   [retract(matrix([[edf2ef v for v in w] for w in args.f])$MEF)$Asp74(BNDY)]
  fde := d03eef(x1,x2,y1,y2,nx,ny,lda,scheme,-1,asp73,asp74)
  ub := new(1,nx*ny,0$DF)$MDF
  A := search(a::Symbol,fde)$Result
  A case "failed" => empty()$Result
  AA := A::Any
  fdea := retract(AA)$AnyFunctions1(MDF)
  r := search(rhs::Symbol,fde)$Result
  r case "failed" => empty()$Result
  rh := r::Any
  fderhs := retract(rh)$AnyFunctions1(MDF)
  d03edf(nx,ny,lda,15,args.tol,0,fdea,fderhs,ub,-1)
```

———-

— D03EEFA.dotabb —

```
"D03EEFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D03EEFA"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"D03EEFA" -> "FS"
```

———-

5.35 domain D03FAFA d03fafAnnaType

— d03fafAnnaType.input —

```
)set break resume
)sys rm -f d03fafAnnaType.output
)spool d03fafAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show d03fafAnnaType
--R
--R d03fafAnnaType  is a domain constructor
--R Abbreviation for d03fafAnnaType is D03FAFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for D03FAFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R PDESolve : Record(pde: List(Expression(DoubleFloat)),constraints: List(Record(start: DoubleF
--R measure : (RoutinesTable,Record(pde: List(Expression(DoubleFloat)),constraints: List(Record(
--R
--E 1

)spool
)lisp (bye)
```


———-

— d03fafAnnaType.help —

```
=====================================================================
d03fafAnnaType examples
=====================================================================
```

```
See Also:
o )show d03fafAnnaType
```

5.35.1 d03fafAnnaType (D03FAFA)



Exports:
coerce hash latex measure PDESolve ?=? ?~=?

— domain D03FAFA d03fafAnnaType —

```
)abbrev domain D03FAFA d03fafAnnaType
++ Author: Brian Dupee
++ Date Created: July 1996
++ Date Last Updated: July 1996
++ Basic Operations:
++ Description:
++ \axiomType{d03fafAnnaType} is a domain of
++ \axiomType{PartialDifferentialEquationsSolverCategory}
++ for the NAG routine D03FAF.

d03fafAnnaType():PartialDifferentialEquationsSolverCategory == Result add
  -- 3D Helmholtz PDE
  LEDF  ==> List Expression DoubleFloat
  EDF  ==> Expression DoubleFloat
  LDF  ==> List DoubleFloat
  MDF  ==> Matrix DoubleFloat
  DF  ==> DoubleFloat
  F  ==> Float
  FI  ==> Fraction Integer
  VEF  ==> Vector Expression Float
  EF  ==> Expression Float
  MEF  ==> Matrix Expression Float
```

```
  NNI  ==> NonNegativeInteger
  INT  ==> Integer
  PDEC  ==> Record(start:DF, finish:DF, grid:NNI, boundaryType:INT,
                   dStart:MDF, dFinish:MDF)
  PDEB  ==> Record(pde:LEDF, constraints:List PDEC,
                   f:List LEDF, st:String, tol:DF)

  import d03AgentsPackage, NagPartialDifferentialEquationsPackage
  import ExpertSystemToolsPackage

  measure(R:RoutinesTable,args:PDEB) ==
    (# (args.constraints) < 3)@Boolean =>
      [0$F,"d03faf is unsuitable for PDEs of order other than 3"]
    [0$F,"d03faf isn't finished"]
```

———-

— D03FAFAs.dotabb —

```
"D03FAFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=D03FAFA"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"D03FAFA" -> "FLAGG"
```

———-

Chapter 6

Chapter E

6.1 domain EQ Equation

— Equation.input —

```
)set break resume
)sys rm -f Equation.output
)spool Equation.output
)set message test on
)set message auto off
)clear all
--S 1 of 12
eq1 := 3*x + 4*y = 5
--R
--R
--R   (1)  4y + 3x= 5
--R                                        Type: Equation(Polynomial(Integer))
--E 1

--S 2 of 12
eq2 := 2*x + 2*y = 3
--R
--R
--R   (2)  2y + 2x= 3
--R                                        Type: Equation(Polynomial(Integer))
--E 2

--S 3 of 12
lhs eq1
--R
--R
--R   (3)  4y + 3x
```

```
--R                                                    Type: Polynomial(Integer)
--E 3

--S 4 of 12
rhs eq1
--R
--R
--R   (4)  5
--R                                                    Type: Polynomial(Integer)
--E 4

--S 5 of 12
eq1 + eq2
--R
--R
--R   (5)  6y + 5x= 8
--R                                          Type: Equation(Polynomial(Integer))
--E 5

--S 6 of 12
eq1 * eq2
--R
--R
--R          2             2
--R   (6)  8y  + 14x y + 6x = 15
--R                                          Type: Equation(Polynomial(Integer))
--E 6

--S 7 of 12
2*eq2 - eq1
--R
--R
--R   (7)  x= 1
--R                                          Type: Equation(Polynomial(Integer))
--E 7

--S 8 of 12
eq1**2
--R
--R
--R           2             2
--R   (8)  16y  + 24x y + 9x = 25
--R                                          Type: Equation(Polynomial(Integer))
--E 8

--S 9 of 12
if x+1 = y then "equal" else "unequal"
--R
--R
--R   (9)  "unequal"
```

```
--R                                                                Type: String
--E 9

--S 10 of 12
eqpol := x+1 = y
--R
--R
--R   (10)  x + 1= y
--R                                          Type: Equation(Polynomial(Integer))
--E 10

--S 11 of 12
if eqpol then "equal" else "unequal"
--R
--R
--R   (11)  "unequal"
--R                                                                Type: String
--E 11

--S 12 of 12
eqpol::Boolean
--R
--R
--R   (12)  false
--R                                                               Type: Boolean
--E 12
)spool
)lisp (bye)
```

———-

— Equation.help —

```
=====================================================================
Equation examples
=====================================================================

The Equation domain provides equations as mathematical objects.  These
are used, for example, as the input to various solve operations.

Equations are created using the equals symbol, =.

  eq1 := 3*x + 4*y = 5
   4y + 3x= 5
                         Type: Equation Polynomial Integer

  eq2 := 2*x + 2*y = 3
   2y + 2x= 3
                         Type: Equation Polynomial Integer
```

```
The left- and right-hand sides of an equation are accessible using
the operations lhs and rhs.

  lhs eq1
   4y + 3x
                          Type: Polynomial Integer

  rhs eq1
   5
                          Type: Polynomial Integer

Arithmetic operations are supported and operate on both sides of the
equation.

  eq1 + eq2
   6y + 5x= 8
                          Type: Equation Polynomial Integer

  eq1 * eq2
     2             2
   8y  + 14x y + 6x = 15
                          Type: Equation Polynomial Integer

  2*eq2 - eq1
   x= 1
                          Type: Equation Polynomial Integer

Equations may be created for any type so the arithmetic operations
will be defined only when they make sense.  For example, exponentiation
is not defined for equations involving non-square matrices.

  eq1**2
      2              2
   16y  + 24x y + 9x = 25
                           Type: Equation Polynomial Integer

Note that an equals symbol is also used to test for equality of values
in certain contexts.  For example, x+1 and y are unequal as polynomials.

  if x+1 = y then "equal" else "unequal"
   "unequal"
                            Type: String

  eqpol := x+1 = y
   x + 1= y
                            Type: Equation Polynomial Integer

If an equation is used where a Boolean value is required, then
it is evaluated using the equality test from the operand type.
```

```
  if eqpol then "equal" else "unequal"
   "unequal"
                              Type: String


If one wants a Boolean value rather than an equation, all one has to
do is ask!

  eqpol::Boolean
   false
                              Type: Boolean

See Also:
o )show Equation
```

———-

6.1.1 Equation (EQ)



Exports:

0	1	characteristic	coerce	commutator
conjugate	D	differentiate	dimension	equation
eval	factorAndSplit	hash	inv	latex
leftOne	leftZero	lhs	map	one?
recip	rhs	rightOne	rightZero	sample
subst	subtractIfCan	swap	zero?	?~=?
-?	?=?	?*?	?**?	?+?
?-?	?/?	?=?	?^?	

— domain EQ Equation —

```
)abbrev domain EQ Equation
--FOR THE BENEFIT  OF LIBAXO GENERATION
```

```
++ Author: Stephen M. Watt, enhancements by Johannes Grabmeier
++ Date Created: April 1985
++ Date Last Updated: June 3, 1991; September 2, 1992
++ Basic Operations: =
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
++ Equations as mathematical objects.  All properties of the basis domain,
++ e.g. being an abelian group are carried over the equation domain, by
++ performing the structural operations on the left and on the
++ right hand side.
--   The interpreter translates "=" to "equation".  Otherwise, it will
--   find a modemap for "=" in the domain of the arguments.

Equation(S: Type): public == private where
  Ex ==> OutputForm
  public ==> Type with
    "=": (S, S) -> $
        ++ a=b creates an equation.
    equation: (S, S) -> $
        ++ equation(a,b) creates an equation.
    swap: $ -> $
        ++ swap(eq) interchanges left and right hand side of equation eq.
    lhs: $ -> S
        ++ lhs(eqn) returns the left hand side of equation eqn.
    rhs: $ -> S
        ++ rhs(eqn) returns the right hand side of equation eqn.
    map: (S -> S, $) -> $
        ++ map(f,eqn) constructs a new equation by applying f to both
        ++ sides of eqn.
    if S has InnerEvalable(Symbol,S) then
             InnerEvalable(Symbol,S)
    if S has SetCategory then
        SetCategory
        CoercibleTo Boolean
        if S has Evalable(S) then
           eval: ($, $) -> $
               ++ eval(eqn, x=f) replaces x by f in equation eqn.
           eval: ($, List $) -> $
               ++ eval(eqn, [x1=v1, ... xn=vn]) replaces xi by vi in equation eqn.
    if S has AbelianSemiGroup then
        AbelianSemiGroup
        "+": (S, $) -> $
            ++ x+eqn produces a new equation by adding x to both sides of
            ++ equation eqn.
        "+": ($, S) -> $
```

```
        ++ eqn+x produces a new equation by adding x to  both sides of
        ++ equation eqn.
    if S has AbelianGroup then
        AbelianGroup
        leftZero : $ -> $
          ++ leftZero(eq) subtracts the left hand side.
        rightZero : $ -> $
          ++ rightZero(eq) subtracts the right hand side.
        "-": (S, $) -> $
            ++ x-eqn produces a new equation by subtracting both sides of
            ++ equation eqn from x.
        "-": ($, S) -> $
            ++ eqn-x produces a new equation by subtracting x from  both sides of
            ++ equation eqn.
    if S has SemiGroup then
        SemiGroup
        "*": (S, $) -> $
            ++ x*eqn produces a new equation by multiplying both sides of
            ++ equation eqn by x.
        "*": ($, S) -> $
            ++ eqn*x produces a new equation by multiplying both sides of
            ++ equation eqn by x.
    if S has Monoid then
        Monoid
        leftOne : $ -> Union($,"failed")
          ++ leftOne(eq) divides by the left hand side, if possible.
        rightOne : $ -> Union($,"failed")
          ++ rightOne(eq) divides by the right hand side, if possible.
    if S has Group then
        Group
        leftOne : $ -> Union($,"failed")
          ++ leftOne(eq) divides by the left hand side.
        rightOne : $ -> Union($,"failed")
          ++ rightOne(eq) divides by the right hand side.
    if S has Ring then
      Ring
      BiModule(S,S)
    if S has CommutativeRing then
      Module(S)
      --Algebra(S)
    if S has IntegralDomain then
      factorAndSplit : $ -> List $
        ++ factorAndSplit(eq) make the right hand side 0 and
        ++ factors the new left hand side. Each factor is equated
        ++ to 0 and put into the resulting list without repetitions.
    if S has PartialDifferentialRing(Symbol) then
      PartialDifferentialRing(Symbol)
    if S has Field then
      VectorSpace(S)
      "/": ($, $) -> $
```

```
        ++ e1/e2 produces a new equation by dividing the left and right
        ++ hand sides of equations e1 and e2.
    inv: $ -> $
        ++ inv(x) returns the multiplicative inverse of x.
  if S has ExpressionSpace then
      subst: ($, $) -> $
          ++ subst(eq1,eq2) substitutes eq2 into both sides of eq1
          ++ the lhs of eq2 should be a kernel

private ==> add
  Rep := Record(lhs: S, rhs: S)
  eq1,eq2: $
  s : S
  if S has IntegralDomain then
      factorAndSplit eq ==
        (S has factor : S -> Factored S) =>
          eq0 := rightZero eq
          [equation(rcf.factor,0) for rcf in factors factor lhs eq0]
        [eq]
  l:S = r:S      == [l, r]
  equation(l, r) == [l, r]    -- hack!  See comment above.
  lhs eqn        == eqn.lhs
  rhs eqn        == eqn.rhs
  swap eqn     == [rhs eqn, lhs eqn]
  map(fn, eqn)   == equation(fn(eqn.lhs), fn(eqn.rhs))

  if S has InnerEvalable(Symbol,S) then
      s:Symbol
      ls:List Symbol
      x:S
      lx:List S
      eval(eqn,s,x) == eval(eqn.lhs,s,x) = eval(eqn.rhs,s,x)
      eval(eqn,ls,lx) == eval(eqn.lhs,ls,lx) = eval(eqn.rhs,ls,lx)
  if S has Evalable(S) then
      eval(eqn1:$, eqn2:$):$ ==
         eval(eqn1.lhs, eqn2 pretend Equation S) =
             eval(eqn1.rhs, eqn2 pretend Equation S)
      eval(eqn1:$, leqn2:List $):$ ==
         eval(eqn1.lhs, leqn2 pretend List Equation S) =
             eval(eqn1.rhs, leqn2 pretend List Equation S)
  if S has SetCategory then
      eq1 = eq2 == (eq1.lhs = eq2.lhs)@Boolean and
                   (eq1.rhs = eq2.rhs)@Boolean
      coerce(eqn:$):Ex == eqn.lhs::Ex = eqn.rhs::Ex
      coerce(eqn:$):Boolean == eqn.lhs = eqn.rhs
  if S has AbelianSemiGroup then
      eq1 + eq2 == eq1.lhs + eq2.lhs = eq1.rhs + eq2.rhs
      s + eq2 == [s,s] + eq2
      eq1 + s == eq1 + [s,s]
  if S has AbelianGroup then
```

```
    - eq == (- lhs eq) = (-rhs eq)
    s - eq2 == [s,s] - eq2
    eq1 - s == eq1 - [s,s]
    leftZero eq == 0 = rhs eq - lhs eq
    rightZero eq == lhs eq - rhs eq = 0
    0 == equation(0$S,0$S)
    eq1 - eq2 == eq1.lhs - eq2.lhs = eq1.rhs - eq2.rhs
  if S has SemiGroup then
    eq1:$ * eq2:$ == eq1.lhs * eq2.lhs = eq1.rhs * eq2.rhs
    l:S   * eqn:$ == l       * eqn.lhs = l       * eqn.rhs
    l:S * eqn:$  ==  l * eqn.lhs    =    l * eqn.rhs
    eqn:$ * l:S  ==  eqn.lhs * l    =    eqn.rhs * l
    -- We have to be a bit careful here: raising to a +ve integer is OK
    -- (since it's the equivalent of repeated multiplication)
    -- but other powers may cause contradictions
    -- Watch what else you add here! JHD 2/Aug 1990
  if S has Monoid then
    1 == equation(1$S,1$S)
    recip eq ==
      (lh := recip lhs eq) case "failed" => "failed"
      (rh := recip rhs eq) case "failed" => "failed"
      [lh :: S, rh :: S]
    leftOne eq ==
      (re := recip lhs eq) case "failed" => "failed"
      1 = rhs eq * re
    rightOne eq ==
      (re := recip rhs eq) case "failed" => "failed"
      lhs eq * re = 1
  if S has Group then
    inv eq == [inv lhs eq, inv rhs eq]
    leftOne eq == 1 = rhs eq * inv rhs eq
    rightOne eq == lhs eq * inv rhs eq = 1
  if S has Ring then
    characteristic() == characteristic()$S
    i:Integer * eq:$ == (i::S) * eq
  if S has IntegralDomain then
    factorAndSplit eq ==
      (S has factor : S -> Factored S) =>
        eq0 := rightZero eq
        [equation(rcf.factor,0) for rcf in factors factor lhs eq0]
      (S has Polynomial Integer) =>
        eq0 := rightZero eq
        MF ==> MultivariateFactorize(Symbol, IndexedExponents Symbol, _
           Integer, Polynomial Integer)
        p : Polynomial Integer := (lhs eq0) pretend Polynomial Integer
        [equation((rcf.factor) pretend S,0) for rcf in factors factor(p)$MF]
      [eq]
  if S has PartialDifferentialRing(Symbol) then
    differentiate(eq:$, sym:Symbol):$ ==
       [differentiate(lhs eq, sym), differentiate(rhs eq, sym)]
```

```
    if S has Field then
        dimension() == 2 :: CardinalNumber
        eq1:$ / eq2:$ == eq1.lhs / eq2.lhs = eq1.rhs / eq2.rhs
        inv eq == [inv lhs eq, inv rhs eq]
    if S has ExpressionSpace then
        subst(eq1,eq2) ==
            eq3 := eq2 pretend Equation S
            [subst(lhs eq1,eq3),subst(rhs eq1,eq3)]
```

———-

— EQ.dotabb —

```
"EQ" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EQ"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"EQ" -> "PFECAT"
```

———-

6.2 domain EQTBL EqTable

— EqTable.input —

```
)set break resume
)sys rm -f EqTable.output
)spool EqTable.output
)set message test on
)set message auto off
)clear all
--S 1 of 6
e: EqTable(List Integer, Integer) := table()
--R
--R
--R   (1)  table()
--R                                          Type: EqTable(List(Integer),Integer)
--E 1

--S 2 of 6
l1 := [1,2,3]
--R
--R
--R   (2)  [1,2,3]
--R                                                  Type: List(PositiveInteger)
--E 2
```

```
--S 3 of 6
l2 := [1,2,3]
--R
--R
--R   (3)  [1,2,3]
--R                                                Type: List(PositiveInteger)
--E 3

--S 4 of 6
e.l1 := 111
--R
--R
--R   (4)  111
--R                                                     Type: PositiveInteger
--E 4

--S 5 of 6
e.l2 := 222
--R
--R
--R   (5)  222
--R                                                     Type: PositiveInteger
--E 5

--S 6 of 6
e.l1
--R
--R
--R   (6)  111
--R                                                     Type: PositiveInteger
--E 6
)spool
)lisp (bye)
```

———-

— EqTable.help —

```
=====================================================================
EqTable examples
=====================================================================

The EqTable domain provides tables where the keys are compared using
eq?.  Keys are considered equal only if they are the same instance of
a structure.  This is useful if the keys are themselves updatable
structures.  Otherwise, all operations are the same as for type Table.

The operation table is here used to create a table where the keys are
```

```
lists of integers.

  e: EqTable(List Integer, Integer) := table()
   table()
                    Type: EqTable(List Integer,Integer)

These two lists are equal according to =, but not according to eq?.

  l1 := [1,2,3]
   [1,2,3]
                    Type: List PositiveInteger

  l2 := [1,2,3]
   [1,2,3]
                    Type: List PositiveInteger
Because the two lists are not eq?, separate values can be stored under
each.


  e.l1 := 111
   111
                    Type: PositiveInteger

  e.l2 := 222
   222
                    Type: PositiveInteger

  e.l1
   111
                    Type: PositiveInteger

See Also:
o )help Table
o )show EqTable
```

6.2.1 EqTable (EQTBL)



See

⇒ “HashTable” (HASHTBL) 9.1.1 on page 1089
⇒ “InnerTable” (INTABL) 10.27.1 on page 1303
⇒ “Table” (TABLE) 21.1.1 on page 2631
⇒ “StringTable” (STRTBL) 20.32.1 on page 2578
⇒ “GeneralSparseTable” (GSTBL) 8.5.1 on page 1048
⇒ “SparseTable” (STBL) 20.16.1 on page 2418

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	elt	empty
empty?	entries	entry?	eq?	eval
every?	extract!	fill!	find	first
hash	index?	indices	insert!	inspect
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
select	select!	setelt	size?	swap!
table	table	#?	?=?	?~=?
?.?				

— domain EQTBL EqTable —

```
)abbrev domain EQTBL EqTable
++ Author: Stephen M. Watt
++ Date Created:
++ Date Last Updated: June 21, 1991
++ Basic Operations:
++ Related Domains: HashTable, Table, StringTable
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
```

```
++ Description:
++ This domain provides tables where the keys are compared using
++ \spadfun{eq?}.  Thus keys are considered equal only if they
++ are the same instance of a structure.

EqTable(Key: SetCategory, Entry: SetCategory) ==
      HashTable(Key, Entry, "EQ")
```

———-

— EQTBL.dotabb —

```
"EQTBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EQTBL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"EQTBL" -> "TBAGG"
```

———-

6.3 domain EMR EuclideanModularRing

— EuclideanModularRing.input —

```
)set break resume
)sys rm -f EuclideanModularRing.output
)spool EuclideanModularRing.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show EuclideanModularRing
--R
--R EuclideanModularRing(S: CommutativeRing,R: UnivariatePolynomialCategory(S),Mod: AbelianMonoi
--R Abbreviation for EuclideanModularRing is EMR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for EMR
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        associates? : (%,%) -> Boolean
```

```
--R coerce : % -> R                          coerce : % -> %
--R coerce : Integer -> %                    coerce : % -> OutputForm
--R ?.? : (%,R) -> R                         gcd : List(%) -> %
--R gcd : (%,%) -> %                         hash : % -> SingleInteger
--R inv : % -> %                             latex : % -> String
--R lcm : List(%) -> %                       lcm : (%,%) -> %
--R modulus : % -> Mod                       one? : % -> Boolean
--R ?quo? : (%,%) -> %                       recip : % -> Union(%,"failed")
--R reduce : (R,Mod) -> %                    ?rem? : (%,%) -> %
--R sample : () -> %                         sizeLess? : (%,%) -> Boolean
--R unit? : % -> Boolean                     unitCanonical : % -> %
--R zero? : % -> Boolean                     ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R exQuo : (%,%) -> Union(%,"failed")
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— EuclideanModularRing.help —

```
====================================================================
EuclideanModularRing examples
====================================================================

See Also:
o )show EuclideanModularRing
```

———-

6.3.1 EuclideanModularRing (EMR)



See

⇒ "ModularRing" (MODRING) 14.10.1 on page 1608
⇒ "ModularField" (MODFIELD) 14.9.1 on page 1606

Exports:

0	1	associates?	characteristic	coerce
divide	euclideanSize	exQuo	expressIdealMember	exquo
extendedEuclidean	gcd	gcdPolynomial	hash	inv
latex	lcm	modulus	multiEuclidean	one?
principalIdeal	recip	reduce	sample	sizeLess?
subtractIfCan	unit?	unitCanonical	unitNormal	zero?
?~=?	?*?	?**?	?^?	?+?
?-?	-?	?=?	?.?	?quo?
?rem?				

— domain EMR EuclideanModularRing —

```
)abbrev domain EMR EuclideanModularRing
++ Author: Mark Botch
++ Description:
++ These domains are used for the factorization and gcds
++ of univariate polynomials over the integers in order to work modulo
++ different  primes.
++ See \spadtype{ModularRing}, \spadtype{ModularField}

EuclideanModularRing(S,R,Mod,reduction:(R,Mod) -> R,
                     merge:(Mod,Mod) -> Union(Mod,"failed"),
                      exactQuo : (R,R,Mod) -> Union(R,"failed")) : C == T
 where
  S    :  CommutativeRing
  R    :  UnivariatePolynomialCategory S
  Mod  :  AbelianMonoid

  C == EuclideanDomain with
   modulus :   %     -> Mod
```

```
     ++ modulus(x) is not documented
   coerce  :   %     -> R
     ++ coerce(x) is not documented
   reduce  : (R,Mod) -> %
     ++ reduce(r,m) is not documented
   exQuo   :  (%,%)  -> Union(%,"failed")
     ++ exQuo(x,y) is not documented
   recip   :    %    -> Union(%,"failed")
     ++ recip(x) is not documented
   inv     :    %    -> %
     ++ inv(x) is not documented
   elt     : (%, R)  -> R
     ++ elt(x,r) or x.r is not documented

  T == ModularRing(R,Mod,reduction,merge,exactQuo) add

    --representation
      Rep:= Record(val:R,modulo:Mod)
    --declarations
      x,y,z: %

      divide(x,y) ==
        t:=merge(x.modulo,y.modulo)
        t case "failed" => error "incompatible moduli"
        xm:=t::Mod
        yv:=y.val
        invlcy:R
--        if one? leadingCoefficient yv then invlcy:=1
        if (leadingCoefficient yv = 1) then invlcy:=1
        else
          invlcy:=(inv reduce((leadingCoefficient yv)::R,xm)).val
          yv:=reduction(invlcy*yv,xm)
        r:=monicDivide(x.val,yv)
        [reduce(invlcy*r.quotient,xm),reduce(r.remainder,xm)]

      if R has fmecg:(R,NonNegativeInteger,S,R)->R
         then x rem y  ==
           t:=merge(x.modulo,y.modulo)
           t case "failed" => error "incompatible moduli"
           xm:=t::Mod
           yv:=y.val
           invlcy:R
--           if not one? leadingCoefficient yv then
           if not (leadingCoefficient yv = 1) then
             invlcy:=(inv reduce((leadingCoefficient yv)::R,xm)).val
             yv:=reduction(invlcy*yv,xm)
           dy:=degree yv
           xv:=x.val
           while (d:=degree xv - dy)>=0 repeat
                 xv:=reduction(fmecg(xv,d::NonNegativeInteger,
```

```
                                    leadingCoefficient xv,yv),xm)
                xv = 0 => return [xv,xm]$Rep
          [xv,xm]$Rep
        else x rem y  ==
          t:=merge(x.modulo,y.modulo)
          t case "failed" => error "incompatible moduli"
          xm:=t::Mod
          yv:=y.val
          invlcy:R
--          if not one? leadingCoefficient yv then
          if not (leadingCoefficient yv = 1) then
            invlcy:=(inv reduce((leadingCoefficient yv)::R,xm)).val
            yv:=reduction(invlcy*yv,xm)
          r:=monicDivide(x.val,yv)
          reduce(r.remainder,xm)

      euclideanSize x == degree x.val

      unitCanonical x ==
        zero? x => x
        degree(x.val) = 0 => 1
--        one? leadingCoefficient(x.val) => x
        (leadingCoefficient(x.val) = 1) => x
        invlcx:%:=inv reduce((leadingCoefficient(x.val))::R,x.modulo)
        invlcx * x

      unitNormal x ==
--        zero?(x) or one?(leadingCoefficient(x.val)) => [1, x, 1]
        zero?(x) or ((leadingCoefficient(x.val)) = 1) => [1, x, 1]
        lcx := reduce((leadingCoefficient(x.val))::R,x.modulo)
        invlcx:=inv lcx
        degree(x.val) = 0 => [lcx, 1, invlcx]
        [lcx, invlcx * x, invlcx]

      elt(x : %,s : R) : R == reduction(elt(x.val,s),x.modulo)
```

— EMR.dotabb —

```
"EMR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EMR"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"EMR" -> "PFECAT"
```

6.4 domain EXIT Exit

— Exit.input —

```
)set break resume
)sys rm -f Exit.output
)spool Exit.output
)set message test on
)set message auto off
)clear all
--S 1
n := 0
--R
--R
--R   (1)  0
--R                                                    Type: NonNegativeInteger
--E 1

--S 2
gasp(): Exit ==
  free n
  n := n + 1
  error "Oh no!"
--R
--R   Function declaration gasp : () -> Exit has been added to workspace.
--R                                                                  Type: Void
--E 2

--S 3
half(k) ==
  if odd? k then gasp()
  else k quo 2
--R
--R                                                                  Type: Void
--E 3

--S 4
half 4
--R
--R   Compiling function gasp with type () -> Exit
--R   Compiling function half with type PositiveInteger -> Integer
--R
--R   (4)  2
--R                                                      Type: PositiveInteger
--E 4

--S 5
half 3
```

```
--R
--R
--RDaly Bug
--R   Error signalled from user code in function gasp:
--R      Oh no!
--E 5

--S 6
n
--R
--R
--R   (5)  1
--R                                                    Type: NonNegativeInteger
--E 6
)spool
)lisp (bye)
```

———-

— Exit.help —

```
========================================================================
Exit examples
========================================================================

A function that does not return directly to its caller has Exit as its
return type.  The operation error is an example of one which does not
return to its caller.  Instead, it causes a return to top-level.

  n := 0

The function gasp is given return type Exit since it is guaranteed
never to return a value to its caller.

  gasp(): Exit ==
    free n
    n := n + 1
    error "Oh no!"

The return type of half is determined by resolving the types of the
two branches of the if.

  half(k) ==
    if odd? k then gasp()
    else k quo 2

Because gasp has the return type Exit, the type of if in half is
resolved to be Integer.
```

```
  half 4


  half 3

  n

See Also:
o )show Exit
```

———-

6.4.1 Exit (EXIT)



Exports:
coerce hash latex ?=? ?~=?

— domain EXIT Exit —

```
)abbrev domain EXIT Exit
++ Author: Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: May 30, 1991
++ Basic Operations:
++ Related Domains: ErrorFunctions, ResolveLatticeCompletion, Void
++ Also See:
++ AMS Classifications:
++ Keywords: exit, throw, error, non-local return
++ Examples:
++ References:
++ Description:
++ A function which does not return directly to its caller should
++ have Exit as its return type.
++
```

```
++ Note that It is convenient to have a formal \spad{coerce} into each type
++ from type Exit. This allows, for example, errors to be raised in
++ one half of a type-balanced \spad{if}.

Exit: SetCategory == add
        coerce(n:%) == error "Cannot use an Exit value."
        n1 = n2     == error "Cannot use an Exit value."
```

———-

— EXIT.dotabb —

```
"EXIT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EXIT"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"EXIT" -> "BASTYPE"
"EXIT" -> "KOERCE"
```

———-

6.5 domain EXPEXPAN ExponentialExpansion

— ExponentialExpansion.input —

```
)set break resume
)sys rm -f ExponentialExpansion.output
)spool ExponentialExpansion.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ExponentialExpansion
--R
--R ExponentialExpansion(R: Join(OrderedSet,RetractableTo(Integer),LinearlyExplicitRingOver(Inte
--R Abbreviation for ExponentialExpansion is EXPEXPAN
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for EXPEXPAN
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
```

```
--R ?-? : (%,%) -> %                    -? : % -> %
--R ?/? : (%,%) -> %                    ?=? : (%,%) -> Boolean
--R 1 : () -> %                         0 : () -> %
--R ?^? : (%,Integer) -> %              ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean      coerce : Fraction(Integer) -> %
--R coerce : % -> %                     coerce : Integer -> %
--R coerce : % -> OutputForm            denominator : % -> %
--R factor : % -> Factored(%)           gcd : List(%) -> %
--R gcd : (%,%) -> %                    hash : % -> SingleInteger
--R inv : % -> %                        latex : % -> String
--R lcm : List(%) -> %                  lcm : (%,%) -> %
--R numerator : % -> %                  one? : % -> Boolean
--R prime? : % -> Boolean               ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")      ?rem? : (%,%) -> %
--R sample : () -> %                    sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)       squareFreePart : % -> %
--R unit? : % -> Boolean                unitCanonical : % -> %
--R zero? : % -> Boolean                ?~=? : (%,%) -> Boolean
--R ?*? : (%,UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)) -> %
--R ?*? : (UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen),%) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen),UnivariatePuiseuxSeriesWithExpone
--R ?<? : (%,%) -> Boolean if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has ORDSET
--R ?<=? : (%,%) -> Boolean if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has ORDSET
--R ?>? : (%,%) -> Boolean if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has ORDSET
--R ?>=? : (%,%) -> Boolean if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has ORDSET
--R D : (%,(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) -> UnivariatePuiseuxSeriesWithEx
--R D : (%,(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) -> UnivariatePuiseuxSeriesWithEx
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity
--R D : (%,Symbol,NonNegativeInteger) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen
--R D : (%,List(Symbol)) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has PDRING
--R D : (%,Symbol) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has PDRING(SYMBOL
--R D : (%,NonNegativeInteger) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has D
--R D : % -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has DIFRING
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has OINTDOM
--R ceiling : % -> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) if UnivariatePuiseuxSerie
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and UnivariatePuiseuxSeriesWithExponentialSingularit
--R coerce : UnivariatePuiseuxSeries(FE,var,cen) -> %
--R coerce : Symbol -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has RETRACT(SYMB
--R coerce : UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) -> %
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and UnivariatePuiseuxSeriesWithExpon
--R convert : % -> DoubleFloat if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has REAL
--R convert : % -> Float if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has REAL
--R convert : % -> InputForm if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has KONVERT
--R convert : % -> Pattern(Float) if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has KO
--R convert : % -> Pattern(Integer) if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has D
--R denom : % -> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)
```

```
--R differentiate : (%,(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) -> Univa
--R differentiate : (%,(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) -> Univa
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if UnivariatePuiseuxSeriesWit
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if UnivariatePuiseuxSeriesWithExponential
--R differentiate : (%,List(Symbol)) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R
--R differentiate : (%,Symbol) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,va
--R differentiate : (%,NonNegativeInteger) -> % if UnivariatePuiseuxSeriesWithExponentialSingula
--R differentiate : % -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) ha
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R ?.? : (%,UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)) -> % if Univariate
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,Symbol,UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)) -> % if Un
--R eval : (%,List(Symbol),List(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen))
--R eval : (%,List(Equation(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)))) -
--R eval : (%,Equation(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen))) -> % if
--R eval : (%,UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen),UnivariatePuiseuxS
--R eval : (%,List(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)),List(Univari
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R floor : % -> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) if UnivariatePu
--R fractionPart : % -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R init : () -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has STEP
--R limitPlus : % -> Union(OrderedCompletion(FE),"failed")
--R map : ((UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) -> UnivariatePuiseux
--R max : (%,%) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has ORDS
--R min : (%,%) -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has ORDS
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R negative? : % -> Boolean if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)
--R nextItem : % -> Union(%,"failed") if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,
--R numer : % -> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R positive? : % -> Boolean if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has INS
--R reducedSystem : Matrix(%) -> Matrix(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,v
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(UnivariatePuiseuxSeriesWithExpon
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if UnivariatePuiseuxSeriesWithExponentialSingul
--R retract : % -> UnivariatePuiseuxSeries(FE,var,cen)
--R retract : % -> Integer if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) ha
--R retract : % -> Fraction(Integer) if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,v
--R retract : % -> Symbol if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has
--R retract : % -> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)
--R retractIfCan : % -> Union(UnivariatePuiseuxSeries(FE,var,cen),"failed")
```

```
--R retractIfCan : % -> Union(Integer,"failed") if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,va
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if UnivariatePuiseuxSeriesWithExponentialSingulari
--R retractIfCan : % -> Union(Symbol,"failed") if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var
--R retractIfCan : % -> Union(UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen),"failed")
--R sign : % -> Integer if UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) has OINTDOM
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if Univa
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R wholePart : % -> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen) if UnivariatePuiseuxSer
--R
--E 1

)spool
)lisp (bye)
```

———-


— **ExponentialExpansion.help** —

```
=====================================================================
ExponentialExpansion examples
=====================================================================

See Also:
o )show ExponentialExpansion
```

———-

6.5.1 ExponentialExpansion (EXPEXPAN)



See

⇒ “ExponentialOfUnivariatePuiseuxSeries” (EXPUPXS) 6.7.1 on page 709
⇒ “UnivariatePuiseuxSeriesWithExponentialSingularity” (UPXSSING) 22.7.1 on page 2819

Exports:

0	1	associates?
abs	ceiling	characteristic
charthRoot	coerce	conditionP
convert	D	denom
denominator	differentiate	divide
euclideanSize	expressIdealMember	eval
exquo	extendedEuclidean	factor
factorSquareFreePolynomial	factorPolynomial	floor
fractionPart	gcd	gcdPolynomial
hash	init	inv
latex	lcm	limitPlus
map	max	min
multiEuclidean	negative?	nextItem
numer	numerator	one?
patternMatch	positive?	prime?
principalIdeal	random	recip
reducedSystem	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
zero?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?.?
?quo?	?rem?	

— domain EXPEXPAN ExponentialExpansion —

```
)abbrev domain EXPEXPAN ExponentialExpansion
++ Author: Clifton J. Williamson
++ Date Created: 13 August 1992
++ Date Last Updated: 27 August 1992
++ Basic Operations:
++ Related Domains: UnivariatePuiseuxSeries(FE,var,cen),
++                  ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)
++ Also See:
++ AMS Classifications:
++ Keywords: limit, functional expression, power series
++ Examples:
++ References:
++ Description:
++ UnivariatePuiseuxSeriesWithExponentialSingularity is a domain used to
++ represent essential singularities of functions.  Objects in this domain
++ are quotients of sums, where each term in the sum is a univariate Puiseux
++ series times the exponential of a univariate Puiseux series.
```

```
ExponentialExpansion(R,FE,var,cen): Exports == Implementation where
  R   : Join(OrderedSet,RetractableTo Integer,_
             LinearlyExplicitRingOver Integer,GcdDomain)
  FE  : Join(AlgebraicallyClosedField,TranscendentalFunctionCategory,_
             FunctionSpace R)
  var : Symbol
  cen : FE
  RN       ==> Fraction Integer
  UPXS     ==> UnivariatePuiseuxSeries(FE,var,cen)
  EXPUPXS  ==> ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)
  UPXSSING ==> UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen)
  OFE      ==> OrderedCompletion FE
  Result   ==> Union(OFE,"failed")
  PxRec    ==> Record(k: Fraction Integer,c:FE)
  Term     ==> Record(%coef:UPXS,%expon:EXPUPXS,%expTerms:List PxRec)
  TypedTerm ==> Record(%term:Term,%type:String)
  SIGNEF   ==> ElementaryFunctionSign(R,FE)

  Exports ==> Join(QuotientFieldCategory UPXSSING,RetractableTo UPXS) with
    limitPlus : % -> Union(OFE,"failed")
      ++ limitPlus(f(var)) returns \spad{limit(var -> a+,f(var))}.
    coerce: UPXS -> %
      ++ coerce(f) converts a \spadtype{UnivariatePuiseuxSeries} to
      ++ an \spadtype{ExponentialExpansion}.

  Implementation ==> Fraction(UPXSSING) add
    coeff : Term -> UPXS
    exponent : Term -> EXPUPXS
    upxssingIfCan : % -> Union(UPXSSING,"failed")
    seriesQuotientLimit: (UPXS,UPXS) -> Union(OFE,"failed")
    seriesQuotientInfinity: (UPXS,UPXS) -> Union(OFE,"failed")

    Rep := Fraction UPXSSING

    ZEROCOUNT : RN := 1000/1

    coeff term == term.%coef
    exponent term == term.%expon

    --!! why is this necessary?
    --!! code can run forever in retractIfCan if original assignment
    --!! for 'ff' is used
    upxssingIfCan f ==
--      one? denom f => numer f
      (denom f = 1) => numer f
      "failed"

    retractIfCan(f:%):Union(UPXS,"failed") ==
      --ff := (retractIfCan$Rep)(f)@Union(UPXSSING,"failed")
```

```
    --ff case "failed" => "failed"
    (ff := upxssingIfCan f) case "failed" => "failed"
    (fff := retractIfCan(ff::UPXSSING)@Union(UPXS,"failed")) case "failed" =>
      "failed"
    fff :: UPXS

  f:UPXSSING / g:UPXSSING ==
    (rec := recip g) case "failed" => f /$Rep g
    f * (rec :: UPXSSING) :: %

  f:% / g:% ==
    (rec := recip numer g) case "failed" => f /$Rep g
    (rec :: UPXSSING) * (denom g) * f

  coerce(f:UPXS) == f :: UPXSSING :: %

  seriesQuotientLimit(num,den) ==
    -- limit of the quotient of two series
    series := num / den
    (ord := order(series,1)) > 0 => 0
    coef := coefficient(series,ord)
    member?(var,variables coef) => "failed"
    ord = 0 => coef :: OFE
    (sig := sign(coef)$SIGNEF) case "failed" => return "failed"
    (sig :: Integer) = 1 => plusInfinity()
    minusInfinity()

  seriesQuotientInfinity(num,den) ==
    -- infinite limit: plus or minus?
    -- look at leading coefficients of series to tell
    (numOrd := order(num,ZEROCOUNT)) = ZEROCOUNT => "failed"
    (denOrd := order(den,ZEROCOUNT)) = ZEROCOUNT => "failed"
    cc := coefficient(num,numOrd)/coefficient(den,denOrd)
    member?(var,variables cc) => "failed"
    (sig := sign(cc)$SIGNEF) case "failed" => return "failed"
    (sig :: Integer) = 1 => plusInfinity()
    minusInfinity()

  limitPlus f ==
    zero? f => 0
    (den := denom f) = 1 => limitPlus numer f
    (numerTerm := dominantTerm(num := numer f)) case "failed" => "failed"
    numType := (numTerm := numerTerm :: TypedTerm).%type
    (denomTerm := dominantTerm den) case "failed" => "failed"
    denType := (denTerm := denomTerm :: TypedTerm).%type
    numExpon := exponent numTerm.%term; denExpon := exponent denTerm.%term
    numCoef := coeff numTerm.%term; denCoef := coeff denTerm.%term
    -- numerator tends to zero exponentially
    (numType = "zero") =>
      -- denominator tends to zero exponentially
```

```
        (denType = "zero") =>
          (exponDiff := numExpon - denExpon) = 0 =>
            seriesQuotientLimit(numCoef,denCoef)
          expCoef := coefficient(exponDiff,order exponDiff)
          (sig := sign(expCoef)$SIGNEF) case "failed" => return "failed"
          (sig :: Integer) = -1 => 0
          seriesQuotientInfinity(numCoef,denCoef)
        0 -- otherwise limit is zero
      -- numerator is a Puiseux series
      (numType = "series") =>
        -- denominator tends to zero exponentially
        (denType = "zero") =>
          seriesQuotientInfinity(numCoef,denCoef)
        -- denominator is a series
        (denType = "series") => seriesQuotientLimit(numCoef,denCoef)
        0
      -- remaining case: numerator tends to infinity exponentially
      -- denominator tends to infinity exponentially
      (denType = "infinity") =>
        (exponDiff := numExpon - denExpon) = 0 =>
          seriesQuotientLimit(numCoef,denCoef)
        expCoef := coefficient(exponDiff,order exponDiff)
        (sig := sign(expCoef)$SIGNEF) case "failed" => return "failed"
        (sig :: Integer) = -1 => 0
        seriesQuotientInfinity(numCoef,denCoef)
      -- denominator tends to zero exponentially or is a series
      seriesQuotientInfinity(numCoef,denCoef)
```

———-

— EXPEXPAN.dotabb —

```
"EXPEXPAN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EXPEXPAN"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ACF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACF"]
"EXPEXPAN" -> "ACF"
"EXPEXPAN" -> "FS"
```

———-

6.6 domain EXPR Expression

— Expression.input —

```
)set break resume
```

```
)sys rm -f Expression.output
)spool Expression.output
)set message test on
)set message auto off
)clear all
--S 1 of 23
sin(x) + 3*cos(x)**2
--R
--R
--R                          2
--R   (1)  sin(x) + 3cos(x)
--R                                                    Type: Expression(Integer)
--E 1

--S 2 of 23
tan(x) - 3.45*x
--R
--R
--R   (2)  tan(x) - 3.45 x
--R                                                      Type: Expression(Float)
--E 2

--S 3 of 23
(tan sqrt 7 - sin sqrt 11)**2 / (4 - cos(x - y))
--R
--R
--R               +-+ 2         +--+      +-+         +--+ 2
--R        - tan(\|7 )  + 2sin(\|11 )tan(\|7 ) - sin(\|11 )
--R   (3)  ------------------------------------------------
--R                          cos(y - x) - 4
--R                                                    Type: Expression(Integer)
--E 3

--S 4 of 23
log(exp  x)@Expression(Integer)
--R
--R
--R   (4)  x
--R                                                    Type: Expression(Integer)
--E 4

--S 5 of 23
log(exp  x)@Expression(Complex Integer)
--R
--R
--R              x
--R   (5)  log(%e )
--R                                          Type: Expression(Complex(Integer))
--E 5
```

```
--S 6 of 23
sqrt 3 + sqrt(2 + sqrt(-5))
--R
--R
--R         +-----------+
--R         | +---+         +-+
--R   (6)  \|\|- 5  + 2  + \|3
--R                                                    Type: AlgebraicNumber
--E 6

--S 7 of 23
% :: Expression Integer
--R
--R
--R         +-----------+
--R         | +---+         +-+
--R   (7)  \|\|- 5  + 2  + \|3
--R                                                 Type: Expression(Integer)
--E 7

--S 8 of 23
height mainKernel sin(x + 4)
--R
--R
--R   (8)  2
--R                                                    Type: PositiveInteger
--E 8

--S 9 of 23
e := (sin(x) - 4)**2 / ( 1 - 2*y*sqrt(- y) )
--R
--R
--R               2
--R        - sin(x)  + 8sin(x) - 16
--R   (9)  ------------------------
--R                 +---+
--R              2y\|- y  - 1
--R                                                 Type: Expression(Integer)
--E 9

--S 10 of 23
numer e
--R
--R
--R                2
--R   (10)  - sin(x)  + 8sin(x) - 16
--R      Type: SparseMultivariatePolynomial(Integer,Kernel(Expression(Integer)))
--E 10

--S 11 of 23
```

```
denom e
--R
--R
--R           +---+
--R   (11)  2y\|- y  - 1
--R      Type: SparseMultivariatePolynomial(Integer,Kernel(Expression(Integer)))
--E 11

--S 12 of 23
D(e, x)
--R
--R
--R                                        +---+
--R         (4y cos(x)sin(x) - 16y cos(x))\|- y  - 2cos(x)sin(x) + 8cos(x)
--R   (12)  ------------------------------------------------------------
--R                                  +---+     3
--R                               4y\|- y  + 4y  - 1
--R                                                    Type: Expression(Integer)
--E 12

--S 13 of 23
D(e, [x, y], [1, 2])
--R
--R
--R   (13)
--R                7       4                      7        4         +---+
--R       ((- 2304y  + 960y )cos(x)sin(x) + (9216y  - 3840y )cos(x))\|- y
--R     +
--R              9        6       3
--R       (- 960y  + 2160y  - 180y  - 3)cos(x)sin(x)
--R     +
--R             9        6       3
--R       (3840y  - 8640y  + 720y  + 12)cos(x)
--R  /
--R            12        9        6       3      +---+        11        8       5
--R       (256y   - 1792y  + 1120y  - 112y  + 1)\|- y  - 1024y   + 1792y  - 448y
--R     +
--R          2
--R       16y
--R                                                    Type: Expression(Integer)
--E 13

--S 14 of 23
complexNumeric(cos(2 - 3*%i))
--R
--R
--R   (14)  - 4.1896256909 688072301 + 9.1092278937 55336598 %i
--R                                                        Type: Complex(Float)
--E 14
```

```
--S 15 of 23
numeric(tan 3.8)
--R
--R
--R   (15)  0.7735560905 0312607286
--R                                                                Type: Float
--E 15

--S 16 of 23
e2 := cos(x**2 - y + 3)
--R
--R
--R                  2
--R   (16)  cos(y - x  - 3)
--R                                                 Type: Expression(Integer)
--E 16

--S 17 of 23
e3 := asin(e2) - %pi/2
--R
--R
--R                2
--R   (17)  - y + x  + 3
--R                                                 Type: Expression(Integer)
--E 17

--S 18 of 23
e3 :: Polynomial Integer
--R
--R
--R                2
--R   (18)  - y + x  + 3
--R                                                 Type: Polynomial(Integer)
--E 18

--S 19 of 23
e3 :: DMP([x, y], Integer)
--R
--R
--R          2
--R   (19)  x  - y + 3
--R                      Type: DistributedMultivariatePolynomial([x,y],Integer)
--E 19

--S 20 of 23
sin %pi
--R
--R
--R   (20)  0
--R                                                 Type: Expression(Integer)
```

```
--E 20

--S 21 of 23
cos(%pi / 4)
--R
--R
--R          +-+
--R         \|2
--R   (21)  ----
--R           2
--R                                                  Type: Expression(Integer)
--E 21

--S 22 of 23
tan(x)**6 + 3*tan(x)**4 + 3*tan(x)**2 + 1
--R
--R
--R               6          4          2
--R   (22)  tan(x)  + 3tan(x)  + 3tan(x)  + 1
--R                                                  Type: Expression(Integer)
--E 22

--S 23 of 23
simplify %
--R
--R
--R            1
--R   (23)  -------
--R               6
--R         cos(x)
--R                                                  Type: Expression(Integer)
--E 23
)spool
)lisp (bye)
```

———-

— Expression.help —

```
=====================================================================
Expression examples
=====================================================================

Expression is a constructor that creates domains whose objects
can have very general symbolic forms.  Here are some examples:

This is an object of type Expression Integer.

  sin(x) + 3*cos(x)**2
```

```
This is an object of type Expression Float.

  tan(x) - 3.45*x

This object contains symbolic function applications, sums,
products, square roots, and a quotient.

  (tan sqrt 7 - sin sqrt 11)**2 / (4 - cos(x - y))

As you can see, Expression actually takes an argument domain.  The
coefficients of the terms within the expression belong to the argument
domain.  Integer and Float, along with Complex Integer and Complex
Float are the most common coefficient domains.

The choice of whether to use a Complex coefficient domain or not is
important since Axiom can perform some simplifications on real-valued
objects

  log(exp  x)@Expression(Integer)

... which are not valid on complex ones.

  log(exp  x)@Expression(Complex Integer)

Many potential coefficient domains, such as AlgebraicNumber, are not
usually used because Expression can subsume them.

  sqrt 3 + sqrt(2 + sqrt(-5))

  % :: Expression Integer

Note that we sometimes talk about "an object of type Expression."
This is not really correct because we should say, for example, "an
object of type Expression Integer" or "an object of type Expression
Float."  By a similar abuse of language, when we refer to an
"expression" in this section we will mean an object of type Expression
R for some domain R.

The Axiom documentation contains many examples of the use of
Expression.  For the rest of this section, we'll give you some
pointers to those examples plus give you some idea of how to
manipulate expressions.

It is important for you to know that Expression creates domains that
have category Field.  Thus you can invert any non-zero expression and
you shouldn't expect an operation like factor to give you much
information.  You can imagine expressions as being represented as
quotients of "multivariate" polynomials where the "variables" are
kernels. A kernel can either be a symbol such as x or a symbolic
```

```
function application like sin(x + 4).  The second example is actually
a nested kernel since the argument to sin contains the kernel x.

  height mainKernel sin(x + 4)

Actually, the argument to sin is an expression, and so the structure
of Expression is recursive. See Kernel which demonstrates how to
extract the kernels in an expression.

Use the HyperDoc Browse facility to see what operations are applicable
to expression.  At the time of this writing, there were 262 operations
with 147 distinct name in Expression Integer.  For example, numer and
denom extract the numerator and denominator of an expression.

  e := (sin(x) - 4)**2 / ( 1 - 2*y*sqrt(- y) )

  numer e

  denom e

Use D to compute partial derivatives.

  D(e, x)

  D(e, [x, y], [1, 2])

When an expression involves no ‘‘symbol kernels’’ (for example, x), it
may be possible to numerically evaluate the expression.

If you suspect the evaluation will create a complex number, use
complexNumeric.

  complexNumeric(cos(2 - 3*%i))

If you know it will be real, use numeric.

  numeric(tan 3.8)

The numeric operation will display an error message if the evaluation
yields a calue with an non-zero imaginary part.  Both of these
operations have an optional second argument n which specifies that the
accuracy of the approximation be up to n decimal places.

When an expression involves no "symbolic application" kernels, it
may be possible to convert it a polynomial or rational function in the
variables that are present.

  e2 := cos(x**2 - y + 3)

  e3 := asin(e2) - %pi/2
```

```
  e3 :: Polynomial Integer

This also works for the polynomial types where specific variables
and their ordering are given.

  e3 :: DMP([x, y], Integer)

Finally, a certain amount of simplication takes place as expressions
are constructed.

  sin %pi

  cos(%pi / 4)


For simplications that involve multiple terms of the expression, use
simplify.

  tan(x)**6 + 3*tan(x)**4 + 3*tan(x)**2 + 1

  simplify %

See Also:
o )show Kernel
o )show Expression
```

6.6.1 Expression (EXPR)



See

⇒ “Pi” (HACKPI) 17.16.1 on page 1943

Exports:

0	1	abs	acos
acosh	acot	acoth	acsc
acsch	airyAi	airyBi	applyQuote
asec	asech	asin	asinh
associates?	atan	atanh	belong?
besselI	besselJ	besselK	besselY
Beta	binomial	box	characteristic
charthRoot	Ci	coerce	commutator
conjugate	convert	cos	cosh
cot	coth	csc	csch
D	definingPolynomial	denom	denominator
differentiate	digamma	dilog	distribute
divide	Ei	elt	erf
euclideanSize	eval	even?	exp
expressIdealMember	exquo	extendedEuclidean	factor
factorPolynomial	factorial	factorials	freeOf?
Gamma	gcd	gcdPolynomial	ground
ground?	hash	height	integral
inv	is?	isExpt	isMult
isPlus	isPower	isTimes	kernel
kernels	latex	lcm	li
log	mainKernel	map	max
min	minPoly	multiEuclidean	nthRoot
number?	numer	numerator	odd?
one?	operator	operators	paren
patternMatch	permutation	pi	polygamma
prime?	principalIdeal	product	recip
reduce	reducedSystem	retract	retractIfCan
rootOf	rootsOf	sample	sec
sech	Si	simplifyPower	sin
sinh	sizeLess?	sqrt	squareFree
squareFreePart	squareFreePolynomial	subst	subtractIfCan
summation	tan	tanh	tower
unit?	unitCanonical	unitNormal	univariate
variables	zero?	zeroOf	zerosOf
?<?	?<=?	?=?	?>?
?>=?	?~=?	?*?	?**?
?+?	-?	?-?	?/?
?^?	?quo?	?rem?	

— domain EXPR Expression —

```
)abbrev domain EXPR Expression
++ Author: Manuel Bronstein
++ Date Created: 19 July 1988
```

```
++ Date Last Updated: October 1993 (P.Gianni), February 1995 (MB)
++ Keywords: operator, kernel, function.
++ Description:
++ Top-level mathematical expressions involving symbolic functions.

Expression(R:OrderedSet): Exports == Implementation where
  Q   ==> Fraction Integer
  K   ==> Kernel %
  MP  ==> SparseMultivariatePolynomial(R, K)
  AF  ==> AlgebraicFunction(R, %)
  EF  ==> ElementaryFunction(R, %)
  CF  ==> CombinatorialFunction(R, %)
  LF  ==> LiouvillianFunction(R, %)
  AN  ==> AlgebraicNumber
  KAN ==> Kernel AN
  FSF ==> FunctionalSpecialFunction(R, %)
  ESD ==> ExpressionSpace_&(%)
  FSD ==> FunctionSpace_&(%, R)
  SYMBOL ==> "%symbol"
  ALGOP  ==> "%alg"
  POWER  ==> "%power"::Symbol
  SUP    ==> SparseUnivariatePolynomial

  Exports ==> FunctionSpace R with
    if R has IntegralDomain then
      AlgebraicallyClosedFunctionSpace R
      TranscendentalFunctionCategory
      CombinatorialOpsCategory
      LiouvillianFunctionCategory
      SpecialFunctionCategory
      reduce: % -> %
        ++ reduce(f) simplifies all the unreduced algebraic quantities
        ++ present in f by applying their defining relations.
      number?: % -> Boolean
        ++ number?(f) tests if f is rational
      simplifyPower: (%,Integer) -> %
        ++ simplifyPower?(f,n) is not documented
      if R has GcdDomain then
        factorPolynomial : SUP  % -> Factored SUP %
          ++ factorPolynomial(p) is not documented
        squareFreePolynomial : SUP % -> Factored SUP %
          ++ squareFreePolynomial(p) is not documented
      if R has RetractableTo Integer then RetractableTo AN

  Implementation ==> add
    import KernelFunctions2(R, %)

    retNotUnit     : % -> R
    retNotUnitIfCan: % -> Union(R, "failed")
```

```
    belong? op == true

    retNotUnit x ==
      (u := constantIfCan(k := retract(x)@K)) case R => u::R
      error "Not retractable"

    retNotUnitIfCan x ==
      (r := retractIfCan(x)@Union(K,"failed")) case "failed" => "failed"
      constantIfCan(r::K)

    if R has IntegralDomain then
      reduc  : (%, List Kernel %) -> %
      commonk   : (%, %) -> List K
      commonk0  : (List K, List K) -> List K
      toprat    : % -> %
      algkernels: List K -> List K
      evl       : (MP, K, SparseUnivariatePolynomial %) -> Fraction MP
      evl0      : (MP, K) -> SparseUnivariatePolynomial Fraction MP

      Rep := Fraction MP
      0                == 0$Rep
      1                == 1$Rep
--      one? x           == one?(x)$Rep
      one? x           == (x = 1)$Rep
      zero? x          == zero?(x)$Rep
      - x:%            == -$Rep x
      n:Integer * x:%  == n *$Rep x
      coerce(n:Integer) ==  coerce(n)$Rep@Rep::%
      x:% * y:%        == reduc(x *$Rep y, commonk(x, y))
      x:% + y:%        == reduc(x +$Rep y, commonk(x, y))
      (x:% - y:%):%    == reduc(x -$Rep y, commonk(x, y))
      x:% / y:%        == reduc(x /$Rep y, commonk(x, y))

      number?(x:%):Boolean ==
        if R has RetractableTo(Integer) then
          ground?(x) or ((retractIfCan(x)@Union(Q,"failed")) case Q)
        else
          ground?(x)

      simplifyPower(x:%,n:Integer):% ==
        k : List K := kernels x
        is?(x,POWER) =>
          -- Look for a power of a number in case we can do a simplification
          args : List % := argument first k
          not(#args = 2) => error "Too many arguments to **"
          number?(args.1) =>
             reduc((args.1) **$Rep n, algkernels kernels (args.1))**(args.2)
          (first args)**(n*second(args))
        reduc(x **$Rep n, algkernels k)
```

```
      x:% ** n:NonNegativeInteger ==
        n = 0 => 1$%
        n = 1 => x
        simplifyPower(numerator x,n pretend Integer) /
           simplifyPower(denominator x,n pretend Integer)

      x:% ** n:Integer ==
        n = 0 => 1$%
        n = 1 => x
        n = -1 => 1/x
        simplifyPower(numerator x,n) /
           simplifyPower(denominator x,n)

      x:% ** n:PositiveInteger ==
        n = 1 => x
        simplifyPower(numerator x,n pretend Integer) /
           simplifyPower(denominator x,n pretend Integer)

      x:% < y:%        == x <$Rep y
      x:% = y:%        == x =$Rep y
      numer x          == numer(x)$Rep
      denom x          == denom(x)$Rep
      coerce(p:MP):%   == coerce(p)$Rep
      reduce x         == reduc(x, algkernels kernels x)
      commonk(x, y)    == commonk0(algkernels kernels x, algkernels kernels y)
      algkernels l     == select_!(x +-> has?(operator x, ALGOP), l)
      toprat f == ratDenom(f,algkernels kernels f)$AlgebraicManipulations(R, %)

      x:MP / y:MP ==
       reduc(x /$Rep y,commonk0(algkernels variables x,algkernels variables y))

-- since we use the reduction from FRAC SMP which asssumes that the
-- variables are independent, we must remove algebraic from the denominators
      reducedSystem(m:Matrix %):Matrix(R) ==
        mm:Matrix(MP) := reducedSystem(map(toprat, m))$Rep
        reducedSystem(mm)$MP

-- since we use the reduction from FRAC SMP which asssumes that the
-- variables are independent, we must remove algebraic from the denominators
      reducedSystem(m:Matrix %, v:Vector %):
       Record(mat:Matrix R, vec:Vector R) ==
        r:Record(mat:Matrix MP, vec:Vector MP) :=
          reducedSystem(map(toprat, m), map(toprat, v))$Rep
        reducedSystem(r.mat, r.vec)$MP

-- The result MUST be left sorted deepest first   MB 3/90
      commonk0(x, y) ==
        ans := empty()$List(K)
        for k in reverse_! x repeat if member?(k, y) then ans := concat(k, ans)
        ans
```

```
rootOf(x:SparseUnivariatePolynomial %, v:Symbol) == rootOf(x,v)$AF
pi()                      == pi()$EF
exp x                     == exp(x)$EF
log x                     == log(x)$EF
sin x                     == sin(x)$EF
cos x                     == cos(x)$EF
tan x                     == tan(x)$EF
cot x                     == cot(x)$EF
sec x                     == sec(x)$EF
csc x                     == csc(x)$EF
asin x                    == asin(x)$EF
acos x                    == acos(x)$EF
atan x                    == atan(x)$EF
acot x                    == acot(x)$EF
asec x                    == asec(x)$EF
acsc x                    == acsc(x)$EF
sinh x                    == sinh(x)$EF
cosh x                    == cosh(x)$EF
tanh x                    == tanh(x)$EF
coth x                    == coth(x)$EF
sech x                    == sech(x)$EF
csch x                    == csch(x)$EF
asinh x                   == asinh(x)$EF
acosh x                   == acosh(x)$EF
atanh x                   == atanh(x)$EF
acoth x                   == acoth(x)$EF
asech x                   == asech(x)$EF
acsch x                   == acsch(x)$EF

abs x                     == abs(x)$FSF
Gamma x                   == Gamma(x)$FSF
Gamma(a, x)               == Gamma(a, x)$FSF
Beta(x,y)                 == Beta(x,y)$FSF
digamma x                 == digamma(x)$FSF
polygamma(k,x)            == polygamma(k,x)$FSF
besselJ(v,x)              == besselJ(v,x)$FSF
besselY(v,x)              == besselY(v,x)$FSF
besselI(v,x)              == besselI(v,x)$FSF
besselK(v,x)              == besselK(v,x)$FSF
airyAi x                  == airyAi(x)$FSF
airyBi x                  == airyBi(x)$FSF

x:% ** y:%                == x **$CF y
factorial x               == factorial(x)$CF
binomial(n, m)            == binomial(n, m)$CF
permutation(n, m)         == permutation(n, m)$CF
factorials x              == factorials(x)$CF
factorials(x, n)          == factorials(x, n)$CF
summation(x:%, n:Symbol)          == summation(x, n)$CF
```

```
summation(x:%, s:SegmentBinding %) == summation(x, s)$CF
product(x:%, n:Symbol)             == product(x, n)$CF
product(x:%, s:SegmentBinding %)   == product(x, s)$CF

erf x                              == erf(x)$LF
Ei x                               == Ei(x)$LF
Si x                               == Si(x)$LF
Ci x                               == Ci(x)$LF
li x                               == li(x)$LF
dilog x                            == dilog(x)$LF
fresnelS x                         == fresnelS(x)$LF
fresnelC x                         == fresnelC(x)$LF
integral(x:%, n:Symbol)            == integral(x, n)$LF
integral(x:%, s:SegmentBinding %)  == integral(x, s)$LF

operator op ==
  belong?(op)$AF  => operator(op)$AF
  belong?(op)$EF  => operator(op)$EF
  belong?(op)$CF  => operator(op)$CF
  belong?(op)$LF  => operator(op)$LF
  belong?(op)$FSF => operator(op)$FSF
  belong?(op)$FSD => operator(op)$FSD
  belong?(op)$ESD => operator(op)$ESD
  nullary? op and has?(op, SYMBOL) => operator(kernel(name op)$K)
  (n := arity op) case "failed" => operator name op
  operator(name op, n::NonNegativeInteger)

reduc(x, l) ==
  for k in l repeat
    p := minPoly k
    x := evl(numer x, k, p) /$Rep evl(denom x, k, p)
  x

evl0(p, k) ==
  numer univariate(p::Fraction(MP),
              k)$PolynomialCategoryQuotientFunctions(IndexedExponents K,
                                                     K,R,MP,Fraction MP)

-- uses some operations from Rep instead of % in order not to
-- reduce recursively during those operations.
evl(p, k, m) ==
  degree(p, k) < degree m => p::Fraction(MP)
  (((evl0(p, k) pretend SparseUnivariatePolynomial($)) rem m)
     pretend SparseUnivariatePolynomial Fraction MP) (k::MP::Fraction(MP))

if R has GcdDomain then
  noalg?: SUP % -> Boolean

  noalg? p ==
    while p ^= 0 repeat
```

```
      not empty? algkernels kernels leadingCoefficient p => return false
      p := reductum p
    true

  gcdPolynomial(p:SUP %, q:SUP %) ==
    noalg? p and noalg? q => gcdPolynomial(p, q)$Rep
    gcdPolynomial(p, q)$GcdDomain_&(%)

  factorPolynomial(x:SUP %) : Factored SUP % ==
    uf:= factor(x pretend SUP(Rep))$SupFractionFactorizer(
                                    IndexedExponents K,K,R,MP)
    uf pretend Factored SUP %

  squareFreePolynomial(x:SUP %) : Factored SUP % ==
    uf:= squareFree(x pretend SUP(Rep))$SupFractionFactorizer(
                                    IndexedExponents K,K,R,MP)
    uf pretend Factored SUP %

if R is AN then
  -- this is to force the coercion R -> EXPR R to be used
  -- instead of the coercioon AN -> EXPR R which loops.
  -- simpler looking code will fail! MB 10/91
  coerce(x:AN):% == (monomial(x, 0$IndexedExponents(K))$MP)::%

if (R has RetractableTo Integer) then
  x:% ** r:Q                          == x **$AF r
  minPoly k                           == minPoly(k)$AF
  definingPolynomial x                == definingPolynomial(x)$AF
  retract(x:%):Q                      == retract(x)$Rep
  retractIfCan(x:%):Union(Q, "failed") == retractIfCan(x)$Rep

  if not(R is AN) then
    k2expr  : KAN -> %
    smp2expr: SparseMultivariatePolynomial(Integer, KAN) -> %
    R2AN    : R  -> Union(AN, "failed")
    k2an    : K  -> Union(AN, "failed")
    smp2an  : MP -> Union(AN, "failed")


    coerce(x:AN):% == smp2expr(numer x) / smp2expr(denom x)
    k2expr k       == map(x+->x::%, k)$ExpressionSpaceFunctions2(AN, %)

    smp2expr p ==
      map(k2expr,x+->x::%,p)_
        $PolynomialCategoryLifting(IndexedExponents KAN,
             KAN, Integer, SparseMultivariatePolynomial(Integer, KAN), %)

    retractIfCan(x:%):Union(AN, "failed") ==
      ((n:= smp2an numer x) case AN) and ((d:= smp2an denom x) case AN)
           => (n::AN) / (d::AN)
```

```
      "failed"

    R2AN r ==
      (u := retractIfCan(r::%)@Union(Q, "failed")) case Q => u::Q::AN
      "failed"

    k2an k ==
      not(belong?(op := operator k)$AN) => "failed"
      arg:List(AN) := empty()
      for x in argument k repeat
        if (a := retractIfCan(x)@Union(AN, "failed")) case "failed" then
          return "failed"
        else arg := concat(a::AN, arg)
      (operator(op)$AN) reverse_!(arg)

    smp2an p ==
      (x1 := mainVariable p) case "failed" => R2AN leadingCoefficient p
      up := univariate(p, k := x1::K)
      (t  := k2an k) case "failed" => "failed"
      ans:AN := 0
      while not ground? up repeat
        (c:=smp2an leadingCoefficient up) case "failed" => return "failed"
        ans := ans + (c::AN) * (t::AN) ** (degree up)
        up  := reductum up
      (c := smp2an leadingCoefficient up) case "failed" => "failed"
      ans + c::AN

  if R has ConvertibleTo InputForm then
    convert(x:%):InputForm == convert(x)$Rep
    import MakeUnaryCompiledFunction(%, %, %)
    eval(f:%, op: BasicOperator, g:%, x:Symbol):% ==
      eval(f,[op],[g],x)
    eval(f:%, ls:List BasicOperator, lg:List %, x:Symbol) ==
      -- handle subsrcipted symbols by renaming -> eval -> renaming back
      llsym:List List Symbol:=[variables g for g in lg]
      lsym:List Symbol:= removeDuplicates concat llsym
      lsd:List Symbol:=select (scripted?,lsym)
      empty? lsd=> eval(f,ls,[compiledFunction(g, x) for g in lg])
      ns:List Symbol:=[new()$Symbol for i in lsd]
      lforwardSubs:List Equation % := [(i::%)= (j::%) for i in lsd for j in ns]
      lbackwardSubs:List Equation % := [(j::%)= (i::%) for i in lsd for j in ns]
      nlg:List % :=[subst(g,lforwardSubs) for g in lg]
      res:% :=eval(f, ls, [compiledFunction(g, x) for g in nlg])
      subst(res,lbackwardSubs)
  if R has PatternMatchable Integer then
    patternMatch(x:%, p:Pattern Integer,
     l:PatternMatchResult(Integer, %)) ==
      patternMatch(x, p, l)$PatternMatchFunctionSpace(Integer, R, %)

  if R has PatternMatchable Float then
```

```
      patternMatch(x:%, p:Pattern Float,
       l:PatternMatchResult(Float, %)) ==
        patternMatch(x, p, l)$PatternMatchFunctionSpace(Float, R, %)

  else  -- R is not an integral domain
    operator op ==
      belong?(op)$FSD => operator(op)$FSD
      belong?(op)$ESD => operator(op)$ESD
      nullary? op and has?(op, SYMBOL) => operator(kernel(name op)$K)
      (n := arity op) case "failed" => operator name op
      operator(name op, n::NonNegativeInteger)

    if R has Ring then
      Rep := MP
      0              == 0$Rep
      1              == 1$Rep
      - x:%          == -$Rep x
      n:Integer *x:% == n *$Rep x
      x:% * y:%      == x *$Rep y
      x:% + y:%      == x +$Rep y
      x:% = y:%      == x =$Rep y
      x:% < y:%      == x <$Rep y
      numer x        == x@Rep
      coerce(p:MP):% == p

      reducedSystem(m:Matrix %):Matrix(R) ==
        reducedSystem(m)$Rep

      reducedSystem(m:Matrix %, v:Vector %):
       Record(mat:Matrix R, vec:Vector R) ==
        reducedSystem(m, v)$Rep

      if R has ConvertibleTo InputForm then
        convert(x:%):InputForm == convert(x)$Rep

      if R has PatternMatchable Integer then
        kintmatch: (K,Pattern Integer,PatternMatchResult(Integer,Rep))
                                  -> PatternMatchResult(Integer, Rep)

        kintmatch(k, p, l) ==
          patternMatch(k, p, l pretend PatternMatchResult(Integer, %)
            )$PatternMatchKernel(Integer, %)
              pretend PatternMatchResult(Integer, Rep)

        patternMatch(x:%, p:Pattern Integer,
         l:PatternMatchResult(Integer, %)) ==
          patternMatch(x@Rep, p,
                       l pretend PatternMatchResult(Integer, Rep),
                        kintmatch
                         )$PatternMatchPolynomialCategory(Integer,
```

```
                        IndexedExponents K, K, R, Rep)
                          pretend PatternMatchResult(Integer, %)

      if R has PatternMatchable Float then
        kfltmatch: (K, Pattern Float, PatternMatchResult(Float, Rep))
                                  -> PatternMatchResult(Float, Rep)

        kfltmatch(k, p, l) ==
          patternMatch(k, p, l pretend PatternMatchResult(Float, %)
            )$PatternMatchKernel(Float, %)
              pretend PatternMatchResult(Float, Rep)

        patternMatch(x:%, p:Pattern Float,
         l:PatternMatchResult(Float, %)) ==
          patternMatch(x@Rep, p,
                       l pretend PatternMatchResult(Float, Rep),
                        kfltmatch
                         )$PatternMatchPolynomialCategory(Float,
                          IndexedExponents K, K, R, Rep)
                            pretend PatternMatchResult(Float, %)

    else   -- R is not even a ring
      if R has AbelianMonoid then
        import ListToMap(K, %)

        kereval        : (K, List K, List %) -> %
        subeval        : (K, List K, List %) -> %

        Rep := FreeAbelianGroup K

        0              == 0$Rep
        x:% + y:%      == x +$Rep y
        x:% = y:%      == x =$Rep y
        x:% < y:%      == x <$Rep y
        coerce(k:K):%  == coerce(k)$Rep
        kernels x      == [f.gen for f in terms x]
        coerce(x:R):%  == (zero? x => 0; constantKernel(x)::%)
        retract(x:%):R == (zero? x => 0; retNotUnit x)
        coerce(x:%):OutputForm == coerce(x)$Rep
        kereval(k, lk, lv) ==
         match(lk, lv, k, (x2:K):% +-> map(x1 +-> eval(x1, lk, lv), x2))

        subeval(k, lk, lv) ==
          match(lk, lv, k,
           (x:K):% +->
             kernel(operator x, [subst(a, lk, lv) for a in argument x]))

        isPlus x ==
          empty?(l := terms x) or empty? rest l => "failed"
          [t.exp *$Rep t.gen for t in l]$List(%)
```

```
          isMult x ==
            empty?(l := terms x) or not empty? rest l => "failed"
            t := first l
            [t.exp, t.gen]

          eval(x:%, lk:List K, lv:List %) ==
            _+/[t.exp * kereval(t.gen, lk, lv) for t in terms x]

          subst(x:%, lk:List K, lv:List %) ==
            _+/[t.exp * subeval(t.gen, lk, lv) for t in terms x]

          retractIfCan(x:%):Union(R, "failed") ==
            zero? x => 0
            retNotUnitIfCan x

          if R has AbelianGroup then -(x:%) == -$Rep x

--      else      -- R is not an AbelianMonoid
--        if R has SemiGroup then
--    Rep := FreeGroup K
--    1              == 1$Rep
--    x:% * y:%      == x *$Rep y
--    x:% = y:%      == x =$Rep y
--    coerce(k:K):%  == k::Rep
--    kernels x      == [f.gen for f in factors x]
--    coerce(x:R):%  == (one? x => 1; constantKernel x)
--    retract(x:%):R == (one? x => 1; retNotUnit x)
--    coerce(x:%):OutputForm == coerce(x)$Rep

--    retractIfCan(x:%):Union(R, "failed") ==
--      one? x => 1
--      retNotUnitIfCan x

--    if R has Group then inv(x:%):% == inv(x)$Rep

        else   -- R is nothing
            import ListToMap(K, %)

            Rep := K

            x:% < y:%      == x <$Rep y
            x:% = y:%      == x =$Rep y
            coerce(k:K):%  == k
            kernels x      == [x pretend K]
            coerce(x:R):%  == constantKernel x
            retract(x:%):R == retNotUnit x
            retractIfCan(x:%):Union(R, "failed") == retNotUnitIfCan x
            coerce(x:%):OutputForm               == coerce(x)$Rep
```

```
            eval(x:%, lk:List K, lv:List %) ==
              match(lk, lv, x pretend K,
               (x1:K):% +-> map(x2 +-> eval(x2, lk, lv), x1))

            subst(x, lk, lv) ==
              match(lk, lv, x pretend K,
               (x1:K):% +->
                 kernel(operator x1, [subst(a, lk, lv) for a in argument x1]))

            if R has ConvertibleTo InputForm then
              convert(x:%):InputForm == convert(x)$Rep

--          if R has PatternMatchable Integer then
--            convert(x:%):Pattern(Integer) == convert(x)$Rep
--
--            patternMatch(x:%, p:Pattern Integer,
--             l:PatternMatchResult(Integer, %)) ==
--              patternMatch(x pretend K,p,l)$PatternMatchKernel(Integer, %)
--
--          if R has PatternMatchable Float then
--            convert(x:%):Pattern(Float) == convert(x)$Rep
--
--            patternMatch(x:%, p:Pattern Float,
--             l:PatternMatchResult(Float, %)) ==
--              patternMatch(x pretend K, p, l)$PatternMatchKernel(Float, %)
```

———-

— **EXPR.dotabb** —

```
"EXPR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EXPR"]
"ACFS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACFS"]
"EXPR" -> "ACFS"
```

———-

6.7 domain EXPUPXS ExponentialOfUnivariatePuiseuxSeries

— **ExponentialOfUnivariatePuiseuxSeries.input** —

```
)set break resume
)sys rm -f ExponentialOfUnivariatePuiseuxSeries.output
)spool ExponentialOfUnivariatePuiseuxSeries.output
)set message test on
```

```
)set message auto off
)clear all

--S 1 of 1
)show ExponentialOfUnivariatePuiseuxSeries
--R
--R ExponentialOfUnivariatePuiseuxSeries(FE: Join(Field,OrderedSet),var: Symbol,cen: FE)  is a d
--R Abbreviation for ExponentialOfUnivariatePuiseuxSeries is EXPUPXS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for EXPUPXS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (FE,%) -> %                      ?*? : (%,FE) -> %
--R ?*? : (%,%) -> %                       ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %         ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                       ?-? : (%,%) -> %
--R -? : % -> %                            ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean                ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                 ?>=? : (%,%) -> Boolean
--R 1 : () -> %                            0 : () -> %
--R ?^? : (%,PositiveInteger) -> %         center : % -> FE
--R coerce : Integer -> %                  coerce : % -> OutputForm
--R complete : % -> %                      degree : % -> Fraction(Integer)
--R ?.? : (%,Fraction(Integer)) -> FE      hash : % -> SingleInteger
--R inv : % -> % if FE has FIELD           latex : % -> String
--R leadingCoefficient : % -> FE           leadingMonomial : % -> %
--R map : ((FE -> FE),%) -> %              max : (%,%) -> %
--R min : (%,%) -> %                       monomial? : % -> Boolean
--R one? : % -> Boolean                    order : % -> Fraction(Integer)
--R pole? : % -> Boolean                   recip : % -> Union(%,"failed")
--R reductum : % -> %                      sample : () -> %
--R variable : % -> Symbol                 zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if FE has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if FE has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if FE has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if FE has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if FE has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if FE has FIELD
--R ?/? : (%,FE) -> % if FE has FIELD
--R D : % -> % if FE has *: (Fraction(Integer),FE) -> FE
--R D : (%,NonNegativeInteger) -> % if FE has *: (Fraction(Integer),FE) -> FE
--R D : (%,Symbol) -> % if FE has *: (Fraction(Integer),FE) -> FE and FE has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if FE has *: (Fraction(Integer),FE) -> FE and FE has PDRING(SYMBOL
--R D : (%,Symbol,NonNegativeInteger) -> % if FE has *: (Fraction(Integer),FE) -> FE and FE has
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if FE has *: (Fraction(Integer),FE) -> FE
--R ?^? : (%,Integer) -> % if FE has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
```

```
--R acos : % -> % if FE has ALGEBRA(FRAC(INT))
--R acosh : % -> % if FE has ALGEBRA(FRAC(INT))
--R acot : % -> % if FE has ALGEBRA(FRAC(INT))
--R acoth : % -> % if FE has ALGEBRA(FRAC(INT))
--R acsc : % -> % if FE has ALGEBRA(FRAC(INT))
--R acsch : % -> % if FE has ALGEBRA(FRAC(INT))
--R approximate : (%,Fraction(Integer)) -> FE if FE has **: (FE,Fraction(Integer)) -> FE and FE has coerce:
--R asec : % -> % if FE has ALGEBRA(FRAC(INT))
--R asech : % -> % if FE has ALGEBRA(FRAC(INT))
--R asin : % -> % if FE has ALGEBRA(FRAC(INT))
--R asinh : % -> % if FE has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if FE has INTDOM
--R atan : % -> % if FE has ALGEBRA(FRAC(INT))
--R atanh : % -> % if FE has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if FE has CHARNZ
--R coefficient : (%,Fraction(Integer)) -> FE
--R coerce : % -> % if FE has INTDOM
--R coerce : Fraction(Integer) -> % if FE has ALGEBRA(FRAC(INT))
--R coerce : FE -> % if FE has COMRING
--R cos : % -> % if FE has ALGEBRA(FRAC(INT))
--R cosh : % -> % if FE has ALGEBRA(FRAC(INT))
--R cot : % -> % if FE has ALGEBRA(FRAC(INT))
--R coth : % -> % if FE has ALGEBRA(FRAC(INT))
--R csc : % -> % if FE has ALGEBRA(FRAC(INT))
--R csch : % -> % if FE has ALGEBRA(FRAC(INT))
--R differentiate : % -> % if FE has *: (Fraction(Integer),FE) -> FE
--R differentiate : (%,NonNegativeInteger) -> % if FE has *: (Fraction(Integer),FE) -> FE
--R differentiate : (%,Symbol) -> % if FE has *: (Fraction(Integer),FE) -> FE and FE has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if FE has *: (Fraction(Integer),FE) -> FE and FE has PDRING(SYMBOL
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if FE has *: (Fraction(Integer),FE) -> FE and FE has
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if FE has *: (Fraction(Integer),FE) -> FE
--R divide : (%,%) -> Record(quotient: %,remainder: %) if FE has FIELD
--R ?.? : (%,%) -> % if Fraction(Integer) has SGROUP
--R euclideanSize : % -> NonNegativeInteger if FE has FIELD
--R eval : (%,FE) -> Stream(FE) if FE has **: (FE,Fraction(Integer)) -> FE
--R exp : % -> % if FE has ALGEBRA(FRAC(INT))
--R exponent : % -> UnivariatePuiseuxSeries(FE,var,cen)
--R exponential : UnivariatePuiseuxSeries(FE,var,cen) -> %
--R exponentialOrder : % -> Fraction(Integer)
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if FE has FIELD
--R exquo : (%,%) -> Union(%,"failed") if FE has INTDOM
--R extend : (%,Fraction(Integer)) -> %
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if FE has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if FE has FIELD
--R factor : % -> Factored(%) if FE has FIELD
--R gcd : (%,%) -> % if FE has FIELD
--R gcd : List(%) -> % if FE has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R integrate : (%,Symbol) -> % if FE has integrate: (FE,Symbol) -> FE and FE has variables: FE -> List(Symb
```

```
--R integrate : % -> % if FE has ALGEBRA(FRAC(INT))
--R lcm : (%,%) -> % if FE has FIELD
--R lcm : List(%) -> % if FE has FIELD
--R log : % -> % if FE has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(Fraction(Integer))) -> %
--R monomial : (%,SingletonAsOrderedSet,Fraction(Integer)) -> %
--R monomial : (FE,Fraction(Integer)) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if FE has FIELD
--R multiplyExponents : (%,Fraction(Integer)) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R nthRoot : (%,Integer) -> % if FE has ALGEBRA(FRAC(INT))
--R order : (%,Fraction(Integer)) -> Fraction(Integer)
--R pi : () -> % if FE has ALGEBRA(FRAC(INT))
--R prime? : % -> Boolean if FE has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if FE has FIELD
--R ?quo? : (%,%) -> % if FE has FIELD
--R ?rem? : (%,%) -> % if FE has FIELD
--R sec : % -> % if FE has ALGEBRA(FRAC(INT))
--R sech : % -> % if FE has ALGEBRA(FRAC(INT))
--R series : (NonNegativeInteger,Stream(Record(k: Fraction(Integer),c: FE))) -> %
--R sin : % -> % if FE has ALGEBRA(FRAC(INT))
--R sinh : % -> % if FE has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if FE has FIELD
--R sqrt : % -> % if FE has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if FE has FIELD
--R squareFreePart : % -> % if FE has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if FE has ALGEBRA(FRAC(INT))
--R tanh : % -> % if FE has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: Fraction(Integer),c: FE))
--R truncate : (%,Fraction(Integer),Fraction(Integer)) -> %
--R truncate : (%,Fraction(Integer)) -> %
--R unit? : % -> Boolean if FE has INTDOM
--R unitCanonical : % -> % if FE has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if FE has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```


———-

— ExponentialOfUnivariatePuiseuxSeries.help —

```
=====================================================================
ExponentialOfUnivariatePuiseuxSeries examples
=====================================================================
```

```
See Also:
o )show ExponentialOfUnivariatePuiseuxSeries
```

6.7.1 ExponentialOfUnivariatePuiseuxSeries (EXPUPXS)



See

⇒ "UnivariatePuiseuxSeriesWithExponentialSingularity" (UPXSSING) 22.7.1 on page 2819
⇒ "ExponentialExpansion" (EXPEXPAN) 6.5.1 on page 681

Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coerce	complete	cos	cosh
cot	coth	csc	csch
D	degree	differentiate	divide
euclideanSize	eval	exp	exponent
exponential	exponentialOrder	expressIdealMember	exquo
extend	extendedEuclidean	factor	gcd
gcdPolynomial	hash	integrate	inv
latex	lcm	leadingCoefficient	leadingMonomial
log	map	max	min
monomial	monomial?	multiEuclidean	multiplyExponents
multiplyExponents	nthRoot	one?	order
pi	pole?	prime?	principalIdeal
recip	reductum	sample	sec
sech	series	sin	sinh
sizeLess?	sqrt	squareFree	squareFreePart
subtractIfCan	tan	tanh	terms
truncate	unit?	unitCanonical	unitNormal
variable	variables	zero?	?*?
?**?	?+?	?-?	-?
?<?	?<=?	?=?	?>?
?>=?	?^?	?.?	?~=?
?/?	?quo?	?rem?	

— domain EXPUPXS ExponentialOfUnivariatePuiseuxSeries —

```
)abbrev domain EXPUPXS ExponentialOfUnivariatePuiseuxSeries
++ Author: Clifton J. Williamson
++ Date Created: 4 August 1992
++ Date Last Updated: 27 August 1992
++ Basic Operations:
++ Related Domains: UnivariatePuiseuxSeries(FE,var,cen)
++ Also See:
++ AMS Classifications:
++ Keywords: limit, functional expression, power series, essential singularity
++ Examples:
++ References:
++ Description:
++ ExponentialOfUnivariatePuiseuxSeries is a domain used to represent
++ essential singularities of functions.  An object in this domain is a
++ function of the form \spad{exp(f(x))}, where \spad{f(x)} is a Puiseux
++ series with no terms of non-negative degree.  Objects are ordered
++ according to order of singularity, with functions which tend more
```

```
++ rapidly to zero or infinity considered to be larger.  Thus, if
++ \spad{order(f(x)) < order(g(x))}, i.e. the first non-zero term of
++ \spad{f(x)} has lower degree than the first non-zero term of \spad{g(x)},
++ then \spad{exp(f(x)) > exp(g(x))}.  If \spad{order(f(x)) = order(g(x))},
++ then the ordering is essentially random.  This domain is used
++ in computing limits involving functions with essential singularities.

ExponentialOfUnivariatePuiseuxSeries(FE,var,cen):_
      Exports == Implementation where
  FE  : Join(Field,OrderedSet)
  var : Symbol
  cen : FE
  UPXS ==> UnivariatePuiseuxSeries(FE,var,cen)

  Exports ==> Join(UnivariatePuiseuxSeriesCategory(FE),OrderedAbelianMonoid) _
        with
    exponential : UPXS -> %
      ++ exponential(f(x)) returns \spad{exp(f(x))}.
      ++ Note: the function does NOT check that \spad{f(x)} has no
      ++ non-negative terms.
    exponent : % -> UPXS
      ++ exponent(exp(f(x))) returns \spad{f(x)}
    exponentialOrder: % -> Fraction Integer
      ++ exponentialOrder(exp(c * x **(-n) + ...)) returns \spad{-n}.
      ++ exponentialOrder(0) returns \spad{0}.

  Implementation ==> UPXS add

    Rep := UPXS

    exponential f == complete f
    exponent f == f pretend UPXS
    exponentialOrder f == order(exponent f,0)

    zero? f == empty? entries complete terms f

    f = g ==
    -- we redefine equality because we know that we are dealing with
    -- a FINITE series, so there is no danger in computing all terms
      (entries complete terms f) = (entries complete terms g)

    f < g ==
      zero? f => not zero? g
      zero? g => false
      (ordf := exponentialOrder f) > (ordg := exponentialOrder g) => true
      ordf < ordg => false
      (fCoef := coefficient(f,ordf)) = (gCoef := coefficient(g,ordg)) =>
        reductum(f) < reductum(g)
      fCoef < gCoef  -- this is "random" if FE is EXPR INT
```

```
    coerce(f:%):OutputForm ==
      ("%e" :: OutputForm) ** ((coerce$Rep)(complete f)@OutputForm)
```

———-

— **EXPUPXS.dotabb** —

```
"EXPUPXS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EXPUPXS"]
"UPXSCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=UPXSCAT"]
"EXPUPXS" -> "UPXSCAT"
```

———-

6.8 domain EAB ExtAlgBasis

— **ExtAlgBasis.input** —

```
)set break resume
)sys rm -f ExtAlgBasis.output
)spool ExtAlgBasis.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ExtAlgBasis
--R
--R ExtAlgBasis  is a domain constructor
--R Abbreviation for ExtAlgBasis is EAB
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for EAB
--R
--R------------------------------ Operations ------------------------------
--R ?<? : (%,%) -> Boolean               ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean               ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean              Nul : NonNegativeInteger -> %
--R coerce : List(Integer) -> %          coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger     exponents : % -> List(Integer)
--R hash : % -> SingleInteger            latex : % -> String
--R max : (%,%) -> %                     min : (%,%) -> %
--R ?~=? : (%,%) -> Boolean
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **ExtAlgBasis.help** —

```
=====================================================================
ExtAlgBasis examples
=====================================================================

See Also:
o )show ExtAlgBasis
```

———-

6.8.1 ExtAlgBasis (EAB)



See

⇒ “AntiSymm” (ANTISYM) 2.8.1 on page 40
⇒ “DeRhamComplex” (DERHAM) 5.6.1 on page 517

Exports:

coerce	degree	exponents	hash	latex
max	min	Nul	?~=?	?<?
?<=?	?=?	?>?	?>=?	

— **domain EAB ExtAlgBasis** —

```
)abbrev domain EAB ExtAlgBasis
++ Author: Larry Lambe
++ Date created: 03/14/89
++ Description:
++ A domain used in the construction of the exterior algebra on a set
++ X over a ring R.  This domain represents the set of all ordered
```

```
++ subsets of the set X, assumed to be in correspondance with
++ {1,2,3, ...}.  The ordered subsets are themselves ordered
++ lexicographically and are in bijective correspondance with an ordered
++ basis of the exterior algebra.  In this domain we are dealing strictly
++ with the exponents of basis elements which can only be 0 or 1.
-- Thus we really have L({0,1}).
++
++ The multiplicative identity element of the exterior algebra corresponds
++ to the empty subset of X.  A coerce from List Integer to an
++ ordered basis element is provided to allow the convenient input of
++ expressions. Another exported function forgets the ordered structure
++ and simply returns the list corresponding to an ordered subset.

ExtAlgBasis(): Export == Implement where
   I   ==> Integer
   L   ==> List
   NNI ==> NonNegativeInteger

   Export == OrderedSet with
     coerce     : L I -> %
        ++ coerce(l) converts a list of 0's and 1's into a basis
        ++ element, where 1 (respectively 0) designates that the
        ++ variable of the corresponding index of l is (respectively, is not)
        ++ present.
        ++ Error: if an element of l is not 0 or 1.
     degree     : %   -> NNI
        ++ degree(x) gives the numbers of 1's in x, i.e., the number
        ++ of non-zero exponents in the basis element that x represents.
     exponents  : %   -> L I
        ++ exponents(x) converts a domain element into a list of zeros
        ++ and ones corresponding to the exponents in the basis element
        ++ that x represents.
--   subscripts : %   -> L I
        -- subscripts(x) looks at the exponents in x and converts
        -- them to the proper subscripts
     Nul        : NNI -> %
        ++ Nul() gives the basis element 1 for the algebra generated
        ++ by n generators.

   Implement == add
     Rep := L I
     x,y :  %

     x = y == x =$Rep y

     x < y ==
       null x            => not null y
       null y            => false
       first x = first y => rest x < rest y
       first x > first y
```

```
     coerce(li:(L I)) ==
       for x in li repeat
         if x ^= 1 and x ^= 0 then error "coerce: values can only be 0 and 1"
       li

     degree x         == (_+/x)::NNI

     exponents x      == copy(x @ Rep)

--   subscripts x     ==
--      cntr:I := 1
--      result: L I := []
--      for j in x repeat
--        if j = 1 then result := cons(cntr,result)
--        cntr:=cntr+1
--      reverse_! result

     Nul n            == [0 for i in 1..n]

     coerce x         == coerce(x @ Rep)$(L I)
```

———-

— **EAB.dotabb** —

```
"EAB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=EAB"]
"PID" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PID"]
"OAGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAGROUP"]
"EAB" -> "PID"
"EAB" -> "OAGROUP"
```

———-

6.9 domain E04DGFA e04dgfAnnaType

— **e04dgfAnnaType.input** —

```
)set break resume
)sys rm -f e04dgfAnnaType.output
)spool e04dgfAnnaType.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show e04dgfAnnaType
--R
--R e04dgfAnnaType  is a domain constructor
--R Abbreviation for e04dgfAnnaType is E04DGFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04DGFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)))
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -
--R
--E 1

)spool
)lisp (bye)
```

———-


— e04dgfAnnaType.help —

```
======================================================================
e04dgfAnnaType examples
======================================================================

See Also:
o )show e04dgfAnnaType
```

———-

6.9.1 e04dgfAnnaType (E04DGFA)



See

⇒ "E04FDFA" (e04fdfAnnaType) 6.10.1 on page 720
⇒ "E04GCFA" (e04gcfAnnaType) 6.11.1 on page 724
⇒ "E04JAFA" (e04jafAnnaType) 6.12.1 on page 728
⇒ "E04MBFA" (e04mbfAnnaType) 6.13.1 on page 731
⇒ "E04NAFA" (e04nafAnnaType) 6.14.1 on page 735
⇒ "E04UCFA" (e04ucfAnnaType) 6.15.1 on page 738

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04DGFA e04dgfAnnaType —

```
)abbrev domain E04DGFA e04dgfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: February 1996
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04dgfAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04DGF, a general optimization routine which
++ can handle some singularities in the input function.  The function
++ \axiomFun{measure} measures the usefulness of the routine E04DGF
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04dgfAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
```

```
MDF  ==> Matrix DoubleFloat
MPDF  ==> Matrix Polynomial DoubleFloat
MF  ==> Matrix Float
MEF  ==> Matrix Expression Float
LEDF  ==> List Expression DoubleFloat
VEF  ==> Vector Expression Float
NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
LSA  ==> Record(lfn:LEDF, init:LDF)
EF2  ==> ExpressionFunctions2
MI  ==> Matrix Integer
INT  ==> Integer
F  ==> Float
NNI  ==> NonNegativeInteger
S  ==> Symbol
LS  ==> List Symbol
MVCF  ==> MultiVariableCalculusFunctions
ESTOOLS2 ==> ExpertSystemToolsPackage2
SDF  ==> Stream DoubleFloat
LSDF  ==> List Stream DoubleFloat
SOCDF  ==> Segment OrderedCompletion DoubleFloat
OCDF  ==> OrderedCompletion DoubleFloat

Rep:=Result
import Rep, NagOptimisationPackage, ExpertSystemToolsPackage

measure(R:RoutinesTable,args:NOA) ==
  string:String := "e04dgf is "
  positive?(#(args.cf) + #(args.lb) + #(args.ub)) =>
    string := concat(string,"unsuitable for constrained problems. ")
    [0.0,string]
  string := concat(string,"recommended")
  [getMeasure(R,e04dgf@Symbol)$RoutinesTable, string]

numericalOptimization(args:NOA) ==
  argsFn:EDF := args.fn
  n:NNI := #(variables(argsFn)$EDF)
  fu:DF := float(4373903597,-24,10)$DF
  it:INT := max(50,5*n)
  lin:DF := float(9,-1,10)$DF
  ma:DF := float(1,20,10)$DF
  op:DF := float(326,-14,10)$DF
  x:MDF := mat(args.init,n)
  ArgsFn:Expression Float := edf2ef(argsFn)
  f:Union(fn:FileName,fp:Asp49(OBJFUN)) := [retract(ArgsFn)$Asp49(OBJFUN)]
  e04dgf(n,1$DF,fu,it,lin,true,ma,op,1,1,n,0,x,-1,f)
```

— **E04DGFA.dotabb** —

```
"E04DGFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04DGFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"E04DGFA" -> "STRING"
```

———-

6.10 domain E04FDFA e04fdfAnnaType

— **e04fdfAnnaType.input** —

```
)set break resume
)sys rm -f e04fdfAnnaType.output
)spool e04fdfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show e04fdfAnnaType
--R
--R e04fdfAnnaType  is a domain constructor
--R Abbreviation for e04fdfAnnaType is E04FDFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04FDFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat))) -> Record(r
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedComp
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedCompl
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -> Result
--R
--E 1

)spool
)lisp (bye)
```


———-

— **e04fdfAnnaType.help** —

```
========================================================================
e04fdfAnnaType examples
========================================================================

See Also:
o )show e04fdfAnnaType
```

6.10.1 e04fdfAnnaType (E04FDFA)



See

⇒ “E04DGFA” (e04dgfAnnaType) 6.9.1 on page 717
⇒ “E04GCFA” (e04gcfAnnaType) 6.11.1 on page 724
⇒ “E04JAFA” (e04jafAnnaType) 6.12.1 on page 728
⇒ “E04MBFA” (e04mbfAnnaType) 6.13.1 on page 731
⇒ “E04NAFA” (e04nafAnnaType) 6.14.1 on page 735
⇒ “E04UCFA” (e04ucfAnnaType) 6.15.1 on page 738

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04FDFA e04fdfAnnaType —

```
)abbrev domain E04FDFA e04fdfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: February 1996
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04fdfAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04FDF, a general optimization routine which
++ can handle some singularities in the input function.  The function
++ \axiomFun{measure} measures the usefulness of the routine E04FDF
```

```
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04fdfAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
  MDF  ==> Matrix DoubleFloat
  MPDF  ==> Matrix Polynomial DoubleFloat
  MF  ==> Matrix Float
  MEF  ==> Matrix Expression Float
  LEDF  ==> List Expression DoubleFloat
  VEF  ==> Vector Expression Float
  NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
  LSA  ==> Record(lfn:LEDF, init:LDF)
  EF2  ==> ExpressionFunctions2
  MI  ==> Matrix Integer
  INT  ==> Integer
  F  ==> Float
  NNI  ==> NonNegativeInteger
  S  ==> Symbol
  LS  ==> List Symbol
  MVCF  ==> MultiVariableCalculusFunctions
  ESTOOLS2 ==> ExpertSystemToolsPackage2
  SDF  ==> Stream DoubleFloat
  LSDF  ==> List Stream DoubleFloat
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  OCDF  ==> OrderedCompletion DoubleFloat

  Rep:=Result
  import Rep, NagOptimisationPackage
  import e04AgentsPackage,ExpertSystemToolsPackage

  measure(R:RoutinesTable,args:NOA) ==
    argsFn := args.fn
    string:String := "e04fdf is "
    positive?(#(args.cf) + #(args.lb) + #(args.ub)) =>
      string := concat(string,"unsuitable for constrained problems. ")
      [0.0,string]
    n:NNI := #(variables(argsFn)$EDF)
    (n>1)@Boolean =>
      string := concat(string,"unsuitable for single instances of multivariate problems. ")
      [0.0,string]
    sumOfSquares(argsFn) case "failed" =>
      string := concat(string,"unsuitable.")
      [0.0,string]
```

```
    string := concat(string,"recommended since the function is a sum of squares.")
    [getMeasure(R,e04fdf@Symbol)$RoutinesTable, string]

  measure(R:RoutinesTable,args:LSA) ==
    string:String := "e04fdf is recommended"
    [getMeasure(R,e04fdf@Symbol)$RoutinesTable, string]

  numericalOptimization(args:NOA) ==
    argsFn := args.fn
    lw:INT := 14
    x := mat(args.init,1)
    (a := sumOfSquares(argsFn)) case EDF =>
      ArgsFn := vector([edf2ef(a)])$VEF
      f : Union(fn:FileName,fp:Asp50(LSFUN1)) := [retract(ArgsFn)$Asp50(LSFUN1)]
      out:Result := e04fdf(1,1,1,lw,x,-1,f)
      changeNameToObjf(fsumsq@Symbol,out)
    empty()$Result

  numericalOptimization(args:LSA) ==
    argsFn := copy args.lfn
    m:INT := #(argsFn)
    n:NNI := #(variables(args))
    nn:INT := n
    lw:INT :=
--      one?(nn) => 9+5*m
      (nn = 1) => 9+5*m
      nn*(7+n+2*m+((nn-1) quo 2)$INT)+3*m
    x := mat(args.init,n)
    ArgsFn := vector([edf2ef(i)$ExpertSystemToolsPackage for i in argsFn])$VEF
    f : Union(fn:FileName,fp:Asp50(LSFUN1)) := [retract(ArgsFn)$Asp50(LSFUN1)]
    out:Result := e04fdf(m,n,1,lw,x,-1,f)
    changeNameToObjf(fsumsq@Symbol,out)
```

— E04FDFA.dotabb —

```
"E04FDFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04FDFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"E04FDFA" -> "STRING"
```

6.11 domain E04GCFA e04gcfAnnaType

— e04gcfAnnaType.input —

```
)set break resume
)sys rm -f e04gcfAnnaType.output
)spool e04gcfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show e04gcfAnnaType
--R
--R e04gcfAnnaType  is a domain constructor
--R Abbreviation for e04gcfAnnaType is E04GCFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04GCFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat))) -> Record(r
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedComp
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedCompl
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -> Result
--R
--E 1

)spool
)lisp (bye)
```

———-


— e04gcfAnnaType.help —

```
==========================================================================
e04gcfAnnaType examples
==========================================================================

See Also:
o )show e04gcfAnnaType
```

———-

6.11.1 e04gcfAnnaType (E04GCFA)



See

⇒ "E04DGFA" (e04dgfAnnaType) 6.9.1 on page 717
⇒ "E04FDFA" (e04fdfAnnaType) 6.10.1 on page 720
⇒ "E04JAFA" (e04jafAnnaType) 6.12.1 on page 728
⇒ "E04MBFA" (e04mbfAnnaType) 6.13.1 on page 731
⇒ "E04NAFA" (e04nafAnnaType) 6.14.1 on page 735
⇒ "E04UCFA" (e04ucfAnnaType) 6.15.1 on page 738

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04GCFA e04gcfAnnaType —

```
)abbrev domain E04GCFA e04gcfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: February 1996
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04gcfAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04GCF, a general optimization routine which
++ can handle some singularities in the input function.  The function
++ \axiomFun{measure} measures the usefulness of the routine E04GCF
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04gcfAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
```

```
MDF  ==> Matrix DoubleFloat
MPDF  ==> Matrix Polynomial DoubleFloat
MF  ==> Matrix Float
MEF  ==> Matrix Expression Float
LEDF  ==> List Expression DoubleFloat
VEF  ==> Vector Expression Float
NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
LSA  ==> Record(lfn:LEDF, init:LDF)
EF2  ==> ExpressionFunctions2
MI  ==> Matrix Integer
INT  ==> Integer
F  ==> Float
NNI  ==> NonNegativeInteger
S  ==> Symbol
LS  ==> List Symbol
MVCF  ==> MultiVariableCalculusFunctions
ESTOOLS2 ==> ExpertSystemToolsPackage2
SDF  ==> Stream DoubleFloat
LSDF  ==> List Stream DoubleFloat
SOCDF  ==> Segment OrderedCompletion DoubleFloat
OCDF  ==> OrderedCompletion DoubleFloat

Rep:=Result
import Rep, NagOptimisationPackage,ExpertSystemContinuityPackage
import e04AgentsPackage,ExpertSystemToolsPackage

measure(R:RoutinesTable,args:NOA) ==
  argsFn:EDF := args.fn
  string:String := "e04gcf is "
  positive?(#(args.cf) + #(args.lb) + #(args.ub)) =>
    string := concat(string,"unsuitable for constrained problems. ")
    [0.0,string]
  n:NNI := #(variables(argsFn)$EDF)
  (n>1)@Boolean =>
    string := concat(string,"unsuitable for single instances of multivariate problems. ")
    [0.0,string]
  a := coerce(float(10,0,10))$OCDF
  seg:SOCDF := -a..a
  sings := singularitiesOf(argsFn,variables(argsFn)$EDF,seg)
  s := #(sdf2lst(sings))
  positive? s =>
    string := concat(string,"not recommended for discontinuous functions.")
    [0.0,string]
  sumOfSquares(args.fn) case "failed" =>
    string := concat(string,"unsuitable.")
    [0.0,string]
  string := concat(string,"recommended since the function is a sum of squares.")
  [getMeasure(R,e04gcf@Symbol)$RoutinesTable, string]

measure(R:RoutinesTable,args:LSA) ==
```

```
    string:String := "e04gcf is "
    a := coerce(float(10,0,10))$OCDF
    seg:SOCDF := -a..a
    sings := concat([singularitiesOf(i,variables(args),seg) for i in args.lfn])$SDF
    s := #(sdf2lst(sings))
    positive? s =>
      string := concat(string,"not recommended for discontinuous functions.")
      [0.0,string]
    string := concat(string,"recommended.")
    m := getMeasure(R,e04gcf@Symbol)$RoutinesTable
    m := m-(1-exp(-(expenseOfEvaluation(args))**3))
    [m, string]

  numericalOptimization(args:NOA) ==
    argsFn:EDF := args.fn
    lw:INT := 16
    x := mat(args.init,1)
    (a := sumOfSquares(argsFn)) case EDF =>
      ArgsFn := vector([edf2ef(a)$ExpertSystemToolsPackage])$VEF
      f : Union(fn:FileName,fp:Asp19(LSFUN2)) := [retract(ArgsFn)$Asp19(LSFUN2)]
      out:Result := e04gcf(1,1,1,lw,x,-1,f)
      changeNameToObjf(fsumsq@Symbol,out)
    empty()$Result

  numericalOptimization(args:LSA) ==
    argsFn := copy args.lfn
    m:NNI := #(argsFn)
    n:NNI := #(variables(args))
    lw:INT :=
--      one?(n) => 11+5*m
      (n = 1) => 11+5*m
      2*n*(4+n+m)+3*m
    x := mat(args.init,n)
    ArgsFn := vector([edf2ef(i)$ExpertSystemToolsPackage for i in argsFn])$VEF
    f : Union(fn:FileName,fp:Asp19(LSFUN2)) := [retract(ArgsFn)$Asp19(LSFUN2)]
    out:Result := e04gcf(m,n,1,lw,x,-1,f)
    changeNameToObjf(fsumsq@Symbol,out)
```

———-

— E04GCFA.dotabb —

```
"E04GCFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04GCFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"E04GCFA" -> "STRING"
```

———-

6.12 domain E04JAFA e04jafAnnaType

— **e04jafAnnaType.input** —

```
)set break resume
)sys rm -f e04jafAnnaType.output
)spool e04jafAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show e04jafAnnaType
--R
--R e04jafAnnaType  is a domain constructor
--R Abbreviation for e04jafAnnaType is E04JAFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04JAFA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat))) -> Record(r
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedComp
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedCompl
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -> Result
--R
--E 1

)spool
)lisp (bye)
```

———-


— **e04jafAnnaType.help** —

```
==========================================================================
e04jafAnnaType examples
==========================================================================

See Also:
o )show e04jafAnnaType
```

———-

6.12.1 e04jafAnnaType (E04JAFA)



See

⇒ "E04DGFA" (e04dgfAnnaType) 6.9.1 on page 717
⇒ "E04FDFA" (e04fdfAnnaType) 6.10.1 on page 720
⇒ "E04GCFA" (e04gcfAnnaType) 6.11.1 on page 724
⇒ "E04MBFA" (e04mbfAnnaType) 6.13.1 on page 731
⇒ "E04NAFA" (e04nafAnnaType) 6.14.1 on page 735
⇒ "E04UCFA" (e04ucfAnnaType) 6.15.1 on page 738

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04JAFA e04jafAnnaType —

```
)abbrev domain E04JAFA e04jafAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: February 1996
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04jafAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04JAF, a general optimization routine which
++ can handle some singularities in the input function.  The function
++ \axiomFun{measure} measures the usefulness of the routine E04JAF
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04jafAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
```

```
  MDF  ==> Matrix DoubleFloat
  MPDF  ==> Matrix Polynomial DoubleFloat
  MF  ==> Matrix Float
  MEF  ==> Matrix Expression Float
  LEDF  ==> List Expression DoubleFloat
  VEF  ==> Vector Expression Float
  NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
  LSA  ==> Record(lfn:LEDF, init:LDF)
  EF2  ==> ExpressionFunctions2
  MI  ==> Matrix Integer
  INT  ==> Integer
  F  ==> Float
  NNI  ==> NonNegativeInteger
  S  ==> Symbol
  LS  ==> List Symbol
  MVCF  ==> MultiVariableCalculusFunctions
  ESTOOLS2 ==> ExpertSystemToolsPackage2
  SDF  ==> Stream DoubleFloat
  LSDF  ==> List Stream DoubleFloat
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  OCDF  ==> OrderedCompletion DoubleFloat

  Rep:=Result
  import Rep, NagOptimisationPackage
  import e04AgentsPackage,ExpertSystemToolsPackage

  bound(a:LOCDF,b:LOCDF):Integer ==
    empty?(concat(a,b)) => 1
--    one?(#(removeDuplicates(a))) and  zero?(first(a)) => 2
    (#(removeDuplicates(a)) = 1) and  zero?(first(a)) => 2
--    one?(#(removeDuplicates(a))) and one?(#(removeDuplicates(b))) => 3
    (#(removeDuplicates(a)) = 1) and (#(removeDuplicates(b)) = 1) => 3
    0

  measure(R:RoutinesTable,args:NOA) ==
    string:String := "e04jaf is "
    if positive?(#(args.cf)) then
      if not simpleBounds?(args.cf) then
        string :=
          concat(string,"suitable for simple bounds only, not constraint functions.")
    (# string) < 20 =>
      if zero?(#(args.lb) + #(args.ub)) then
        string := concat(string, "usable if there are no constraints")
        [getMeasure(R,e04jaf@Symbol)$RoutinesTable*0.5,string]
      else
        string := concat(string,"recommended")
        [getMeasure(R,e04jaf@Symbol)$RoutinesTable, string]
    [0.0,string]

  numericalOptimization(args:NOA) ==
```

```
    argsFn:EDF := args.fn
    n:NNI := #(variables(argsFn)$EDF)
    ibound:INT := bound(args.lb,args.ub)
    m:INT := n
    lw:INT := max(13,12 * m + ((m * (m - 1)) quo 2)$INT)$INT
    bl := mat(finiteBound(args.lb,float(1,6,10)$DF),n)
    bu := mat(finiteBound(args.ub,float(1,6,10)$DF),n)
    x := mat(args.init,n)
    ArgsFn:EF := edf2ef(argsFn)
    fr:Union(fn:FileName,fp:Asp24(FUNCT1)) := [retract(ArgsFn)$Asp24(FUNCT1)]
    out:Result := e04jaf(n,ibound,n+2,lw,bl,bu,x,-1,fr)
    changeNameToObjf(f@Symbol,out)
```

———-

— E04JAFA.dotabb —

```
"E04JAFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04JAFA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"E04JAFA" -> "STRING"
```

———-

6.13 domain E04MBFA e04mbfAnnaType

— e04mbfAnnaType.input —

```
)set break resume
)sys rm -f e04mbfAnnaType.output
)spool e04mbfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show e04mbfAnnaType
--R
--R e04mbfAnnaType  is a domain constructor
--R Abbreviation for e04mbfAnnaType is E04MBFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04MBFA
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
```

```
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat))) -> Record(r
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedComp
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedCompl
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -> Result
--R
--E 1

)spool
)lisp (bye)
```

———-


— **e04mbfAnnaType.help** —

```
==========================================================================
e04mbfAnnaType examples
==========================================================================

See Also:
o )show e04mbfAnnaType
```

———-

6.13.1 e04mbfAnnaType (E04MBFA)



See

⇒ “E04DGFA” (e04dgfAnnaType) 6.9.1 on page 717
⇒ “E04FDFA” (e04fdfAnnaType) 6.10.1 on page 720
⇒ “E04GCFA” (e04gcfAnnaType) 6.11.1 on page 724
⇒ “E04JAFA” (e04jafAnnaType) 6.12.1 on page 728
⇒ “E04NAFA” (e04nafAnnaType) 6.14.1 on page 735
⇒ “E04UCFA” (e04ucfAnnaType) 6.15.1 on page 738

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04MBFA e04mbfAnnaType —

```
)abbrev domain E04MBFA e04mbfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: February 1996
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04mbfAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04MBF, an optimization routine for Linear functions.
++ The function
++ \axiomFun{measure} measures the usefulness of the routine E04MBF
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04mbfAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
  MDF  ==> Matrix DoubleFloat
  MPDF  ==> Matrix Polynomial DoubleFloat
  MF  ==> Matrix Float
  MEF  ==> Matrix Expression Float
  LEDF  ==> List Expression DoubleFloat
  VEF  ==> Vector Expression Float
  NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
  LSA  ==> Record(lfn:LEDF, init:LDF)
  EF2  ==> ExpressionFunctions2
  MI  ==> Matrix Integer
  INT  ==> Integer
  F  ==> Float
  NNI  ==> NonNegativeInteger
  S  ==> Symbol
  LS  ==> List Symbol
  MVCF  ==> MultiVariableCalculusFunctions
  ESTOOLS2 ==> ExpertSystemToolsPackage2
  SDF  ==> Stream DoubleFloat
  LSDF  ==> List Stream DoubleFloat
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  OCDF  ==> OrderedCompletion DoubleFloat
```

```
  Rep:=Result
  import Rep, NagOptimisationPackage
  import e04AgentsPackage,ExpertSystemToolsPackage

  measure(R:RoutinesTable,args:NOA) ==
    (not linear?([args.fn])) or (not linear?(args.cf)) =>
      [0.0,"e04mbf is for a linear objective function and constraints only."]
    [getMeasure(R,e04mbf@Symbol)$RoutinesTable,"e04mbf is recommended" ]

  numericalOptimization(args:NOA) ==
    argsFn:EDF := args.fn
    c := args.cf
    listVars:List LS := concat(variables(argsFn)$EDF,[variables(z)$EDF for z in c])
    n:NNI := #(v := removeDuplicates(concat(listVars)$LS)$LS)
    A:MDF := linearMatrix(args.cf,n)
    nclin:NNI := # linearPart(c)
    nrowa:NNI := max(1,nclin)
    bl:MDF := mat(finiteBound(args.lb,float(1,21,10)$DF),n)
    bu:MDF := mat(finiteBound(args.ub,float(1,21,10)$DF),n)
    cvec:MDF := mat(coefficients(retract(argsFn)@PDF)$PDF,n)
    x := mat(args.init,n)
    lwork:INT :=
      nclin < n => 2*nclin*(nclin+4)+2+6*n+nrowa
      2*(n+3)*n+4*nclin+nrowa
    out:Result := e04mbf(20,1,n,nclin,n+nclin,nrowa,A,bl,bu,cvec,true,2*n,lwork,x,-1)
    changeNameToObjf(objlp@Symbol,out)
```

———-

— E04MBFA.dotabb —

```
"E04MBFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04MBFA"]
"TRANFUN" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TRANFUN"]
"E04MBFA" -> "TRANFUN"
```

———-

6.14 domain E04NAFA e04nafAnnaType

— e04nafAnnaType.input —

```
)set break resume
)sys rm -f e04nafAnnaType.output
)spool e04nafAnnaType.output
```

```
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show e04nafAnnaType
--R
--R e04nafAnnaType  is a domain constructor
--R Abbreviation for e04nafAnnaType is E04NAFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04NAFA
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)))
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -
--R
--E 1

)spool
)lisp (bye)
```

———-


— e04nafAnnaType.help —

```
==========================================================================
e04nafAnnaType examples
==========================================================================

See Also:
o )show e04nafAnnaType
```

———-

6.14.1 e04nafAnnaType (E04NAFA)



See

⇒ "E04DGFA" (e04dgfAnnaType) 6.9.1 on page 717
⇒ "E04FDFA" (e04fdfAnnaType) 6.10.1 on page 720
⇒ "E04GCFA" (e04gcfAnnaType) 6.11.1 on page 724
⇒ "E04JAFA" (e04jafAnnaType) 6.12.1 on page 728
⇒ "E04MBFA" (e04mbfAnnaType) 6.13.1 on page 731
⇒ "E04UCFA" (e04ucfAnnaType) 6.15.1 on page 738

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04NAFA e04nafAnnaType —

```
)abbrev domain E04NAFA e04nafAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: February 1996
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04nafAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04NAF, an optimization routine for Quadratic functions.
++ The function
++ \axiomFun{measure} measures the usefulness of the routine E04NAF
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04nafAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
```

```
MDF  ==> Matrix DoubleFloat
MPDF  ==> Matrix Polynomial DoubleFloat
MF  ==> Matrix Float
MEF  ==> Matrix Expression Float
LEDF  ==> List Expression DoubleFloat
VEF  ==> Vector Expression Float
NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
LSA  ==> Record(lfn:LEDF, init:LDF)
EF2  ==> ExpressionFunctions2
MI  ==> Matrix Integer
INT  ==> Integer
F  ==> Float
NNI  ==> NonNegativeInteger
S  ==> Symbol
LS  ==> List Symbol
MVCF  ==> MultiVariableCalculusFunctions
ESTOOLS2 ==> ExpertSystemToolsPackage2
SDF  ==> Stream DoubleFloat
LSDF  ==> List Stream DoubleFloat
SOCDF  ==> Segment OrderedCompletion DoubleFloat
OCDF  ==> OrderedCompletion DoubleFloat

Rep:=Result
import Rep, NagOptimisationPackage
import e04AgentsPackage,ExpertSystemToolsPackage

measure(R:RoutinesTable,args:NOA) ==
  string:String := "e04naf is "
  argsFn:EDF := args.fn
  if not (quadratic?(argsFn) and linear?(args.cf)) then
    string :=
      concat(string,"for a quadratic function with linear constraints only.")
  (# string) < 20 =>
    string := concat(string,"recommended")
    [getMeasure(R,e04naf@Symbol)$RoutinesTable, string]
  [0.0,string]

numericalOptimization(args:NOA) ==
  argsFn:EDF := args.fn
  c := args.cf
  listVars:List LS := concat(variables(argsFn)$EDF,[variables(z)$EDF for z in c])
  n:NNI := #(v := sort(removeDuplicates(concat(listVars)$LS)$LS)$LS)
  A:MDF := linearMatrix(c,n)
  nclin:NNI := # linearPart(c)
  nrowa:NNI := max(1,nclin)
  big:DF := float(1,10,10)$DF
  fea:MDF := new(1,n+nclin,float(1053,-11,10)$DF)$MDF
  bl:MDF := mat(finiteBound(args.lb,float(1,21,10)$DF),n)
  bu:MDF := mat(finiteBound(args.ub,float(1,21,10)$DF),n)
  alin:EDF := splitLinear(argsFn)
```

```
    p:PDF := retract(alin)@PDF
    pl:List PDF := [coefficient(p,i,1)$PDF for i in v]
    cvec:MDF := mat([pdf2df j for j in pl],n)
    h1:MPDF := hessian(p,v)$MVCF(S,PDF,VPDF,LS)
    hess:MDF := map(pdf2df,h1)$ESTOOLS2(PDF,DF)
    h2:MEF := map(df2ef,hess)$ESTOOLS2(DF,EF)
    x := mat(args.init,n)
    istate:MI := zero(1,n+nclin)$MI
    lwork:INT := 2*n*(n+2*nclin)+nrowa
    qphess:Union(fn:FileName,fp:Asp20(QPHESS)) := [retract(h2)$Asp20(QPHESS)]
    out:Result := e04naf(20,1,n,nclin,n+nclin,nrowa,n,n,big,A,bl,bu,cvec,fea,
                         hess,true,false,true,2*n,lwork,x,istate,-1,qphess)
    changeNameToObjf(obj@Symbol,out)
```

———-

— E04NAFA.dotabb —

```
"E04NAFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04NAFA"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"E04NAFA" -> "FS"
```

———-

6.15 domain E04UCFA e04ucfAnnaType

— e04ucfAnnaType.input —

```
)set break resume
)sys rm -f e04ucfAnnaType.output
)spool e04ucfAnnaType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show e04ucfAnnaType
--R
--R e04ucfAnnaType  is a domain constructor
--R Abbreviation for e04ucfAnnaType is E04UCFA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for E04UCFA
--R
--R------------------------------ Operations --------------------------------
```

```
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R measure : (RoutinesTable,Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)))
--R measure : (RoutinesTable,Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List
--R numericalOptimization : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(
--R numericalOptimization : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -
--R
--E 1

)spool
)lisp (bye)
```

———-


— e04ucfAnnaType.help —

```
====================================================================
e04ucfAnnaType examples
====================================================================

See Also:
o )show e04ucfAnnaType
```

———-

6.15.1 e04ucfAnnaType (E04UCFA)



See

⇒ “E04DGFA” (e04dgfAnnaType) 6.9.1 on page 717
⇒ “E04FDFA” (e04fdfAnnaType) 6.10.1 on page 720
⇒ “E04GCFA” (e04gcfAnnaType) 6.11.1 on page 724
⇒ “E04JAFA” (e04jafAnnaType) 6.12.1 on page 728
⇒ “E04MBFA” (e04mbfAnnaType) 6.13.1 on page 731
⇒ “E04NAFA” (e04nafAnnaType) 6.14.1 on page 735

Exports:
coerce hash latex measure numericalOptimization ?=? ?~=?

— domain E04UCFA e04ucfAnnaType —

```
)abbrev domain E04UCFA e04ucfAnnaType
++ Author: Brian Dupee
++ Date Created: February 1996
++ Date Last Updated: November 1997
++ Basic Operations: measure, numericalOptimization
++ Related Constructors: Result, RoutinesTable
++ Description:
++ \axiomType{e04ucfAnnaType} is a domain of \axiomType{NumericalOptimization}
++ for the NAG routine E04UCF, a general optimization routine which
++ can handle some singularities in the input function.  The function
++ \axiomFun{measure} measures the usefulness of the routine E04UCF
++ for the given problem.  The function \axiomFun{numericalOptimization}
++ performs the optimization by using \axiomType{NagOptimisationPackage}.

e04ucfAnnaType(): NumericalOptimizationCategory == Result add
  DF  ==> DoubleFloat
  EF  ==> Expression Float
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  VPDF  ==> Vector Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  LOCDF  ==> List OrderedCompletion DoubleFloat
  MDF  ==> Matrix DoubleFloat
  MPDF  ==> Matrix Polynomial DoubleFloat
  MF  ==> Matrix Float
  MEF  ==> Matrix Expression Float
  LEDF  ==> List Expression DoubleFloat
  VEF  ==> Vector Expression Float
  NOA  ==> Record(fn:EDF, init:LDF, lb:LOCDF, cf:LEDF, ub:LOCDF)
  LSA  ==> Record(lfn:LEDF, init:LDF)
  EF2  ==> ExpressionFunctions2
  MI  ==> Matrix Integer
  INT  ==> Integer
  F  ==> Float
  NNI  ==> NonNegativeInteger
  S  ==> Symbol
  LS  ==> List Symbol
  MVCF  ==> MultiVariableCalculusFunctions
  ESTOOLS2 ==> ExpertSystemToolsPackage2
  SDF  ==> Stream DoubleFloat
  LSDF  ==> List Stream DoubleFloat
  SOCDF  ==> Segment OrderedCompletion DoubleFloat
  OCDF  ==> OrderedCompletion DoubleFloat
```

```
Rep:=Result
import Rep,NagOptimisationPackage
import e04AgentsPackage,ExpertSystemToolsPackage

measure(R:RoutinesTable,args:NOA) ==
  zero?(#(args.lb) + #(args.ub)) =>
    [0.0,"e04ucf is not recommended if there are no bounds specified"]
  zero?(#(args.cf)) =>
    string:String := "e04ucf is usable but not always recommended if there are no constraints"
    [getMeasure(R,e04ucf@Symbol)$RoutinesTable*0.5,string]
  [getMeasure(R,e04ucf@Symbol)$RoutinesTable,"e04ucf is recommended"]

numericalOptimization(args:NOA) ==
  Args := sortConstraints(args)
  argsFn := Args.fn
  c := Args.cf
  listVars:List LS := concat(variables(argsFn)$EDF,[variables(z)$EDF for z in c])
  n:NNI := #(v := sort(removeDuplicates(concat(listVars)$LS)$LS)$LS)
  lin:NNI := #(linearPart(c))
  nlcf := nonLinearPart(c)
  nonlin:NNI := #(nlcf)
  if empty?(nlcf) then
    nlcf := new(n,coerce(first(v)$LS)$EDF)$LEDF
  nrowa:NNI := max(1,lin)
  nrowj:NNI := max(1,nonlin)
  A:MDF := linearMatrix(c,n)
  bl:MDF := mat(finiteBound(Args.lb,float(1,25,10)$DF),n)
  bu:MDF := mat(finiteBound(Args.ub,float(1,25,10)$DF),n)
  liwork:INT := 3*n+lin+2*nonlin
  lwork:INT :=
    zero?(lin+nonlin) => 20*n
    zero?(nonlin) => 2*n*(n+10)+11*lin
    2*n*(n+nonlin+10)+(11+n)*lin + 21*nonlin
  cra:DF := float(1,-2,10)$DF
  fea:DF := float(1053671201,-17,10)$DF
  fun:DF := float(4373903597,-24,10)$DF
  infb:DF := float(1,15,10)$DF
  lint:DF := float(9,-1,10)$DF
  maji:INT := max(50,3*(n+lin)+10*nonlin)
  mini:INT := max(50,3*(n+lin+nonlin))
  nonf:DF := float(105,-10,10)$DF
  opt:DF := float(326,-10,10)$DF
  ste:DF := float(2,0,10)$DF
  istate:MI := zero(1,n+lin+nonlin)$MI
  cjac:MDF :=
    positive?(nonlin) => zero(nrowj,n)$MDF
    zero(nrowj,1)$MDF
  clambda:MDF := zero(1,n+lin+nonlin)$MDF
  r:MDF := zero(n,n)$MDF
  x:MDF := mat(Args.init,n)
```

```
    VectCF:VEF := vector([edf2ef e for e in nlcf])$VEF
    ArgsFn:EF := edf2ef(argsFn)
    fasp : Union(fn:FileName,fp:Asp49(OBJFUN)) := [retract(ArgsFn)$Asp49(OBJFUN)]
    casp : Union(fn:FileName,fp:Asp55(CONFUN)) := [retract(VectCF)$Asp55(CONFUN)]
    e04ucf(n,lin,nonlin,nrowa,nrowj,n,A,bl,bu,liwork,lwork,false,cra,3,fea,
            fun,true,infb,infb,fea,lint,true,maji,1,mini,0,-1,nonf,opt,ste,1,
             1,n,n,3,istate,cjac,clambda,r,x,-1,casp,fasp)
```

———-

— **E04UCFA.dotabb** —

```
"E04UCFA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=E04UCFA"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"E04UCFA" -> "PFECAT"
```

———-

Chapter 7

Chapter F

7.1 domain FR Factored

— Factored.input —

```
)set break resume
)sys rm -f Factored.output
)spool Factored.output
)set message test on
)set message auto off
)clear all
--S 1 of 38
g := factor(4312)
--R
--R
--R         3 2
--R   (1)  2 7 11
--R                                                  Type: Factored(Integer)
--E 1

--S 2 of 38
unit(g)
--R
--R
--R   (2)  1
--R                                                    Type: PositiveInteger
--E 2

--S 3 of 38
numberOfFactors(g)
--R
--R
```

```
--R   (3)  3
--R                                                        Type: PositiveInteger
--E 3

--S 4 of 38
[nthFactor(g,i) for i in 1..numberOfFactors(g)]
--R
--R
--R   (4)  [2,7,11]
--R                                                          Type: List(Integer)
--E 4

--S 5 of 38
[nthExponent(g,i) for i in 1..numberOfFactors(g)]
--R
--R
--R   (5)  [3,2,1]
--R                                                          Type: List(Integer)
--E 5

--S 6 of 38
[nthFlag(g,i) for i in 1..numberOfFactors(g)]
--R
--R
--R   (6)  ["prime","prime","prime"]
--R                               Type: List(Union("nil","sqfr","irred","prime"))
--E 6

--S 7 of 38
factorList(g)
--R
--R
--R   (7)
--R   [[flg= "prime",fctr= 2,xpnt= 3], [flg= "prime",fctr= 7,xpnt= 2],
--R    [flg= "prime",fctr= 11,xpnt= 1]]
--RType: List(Record(flg: Union("nil","sqfr","irred","prime"),fctr: Integer,xpnt: Integer))
--E 7

--S 8 of 38
factors(g)
--R
--R
--R   (8)
--R   [[factor= 2,exponent= 3],[factor= 7,exponent= 2],[factor= 11,exponent= 1]]
--R                         Type: List(Record(factor: Integer,exponent: Integer))
--E 8

--S 9 of 38
first(%).factor
--R
```

```
--R
--R   (9)  2
--R                                                    Type: PositiveInteger
--E 9

--S 10 of 38
g := factor(4312)
--R
--R
--R          3 2
--R   (10)  2 7 11
--R                                                 Type: Factored(Integer)
--E 10

--S 11 of 38
expand(g)
--R
--R
--R   (11)  4312
--R                                                    Type: PositiveInteger
--E 11

--S 12 of 38
reduce(*,[t.factor for t in factors(g)])
--R
--R
--R   (12)  154
--R                                                    Type: PositiveInteger
--E 12

--S 13 of 38
g := factor(4312)
--R
--R
--R          3 2
--R   (13)  2 7 11
--R                                                 Type: Factored(Integer)
--E 13

--S 14 of 38
f := factor(246960)
--R
--R
--R          4 2   3
--R   (14)  2 3 5 7
--R                                                 Type: Factored(Integer)
--E 14

--S 15 of 38
f * g
```

```
--R
--R
--R          7 2   5
--R   (15)  2 3 5 7 11
--R                                                    Type: Factored(Integer)
--E 15

--S 16 of 38
f**500
--R
--R
--R          2000 1000 500 1500
--R   (16)  2    3    5   7
--R                                                    Type: Factored(Integer)
--E 16

--S 17 of 38
gcd(f,g)
--R
--R
--R          3 2
--R   (17)  2 7
--R                                                    Type: Factored(Integer)
--E 17

--S 18 of 38
lcm(f,g)
--R
--R
--R          4 2   3
--R   (18)  2 3 5 7 11
--R                                                    Type: Factored(Integer)
--E 18

--S 19 of 38
f + g
--R
--R
--R          3 2
--R   (19)  2 7 641
--R                                                    Type: Factored(Integer)
--E 19

--S 20 of 38
f - g
--R
--R
--R          3 2
--R   (20)  2 7 619
--R                                                    Type: Factored(Integer)
```

```
--E 20

--S 21 of 38
zero?(factor(0))
--R
--R
--R   (21)  true
--R                                                    Type: Boolean
--E 21

--S 22 of 38
zero?(g)
--R
--R
--R   (22)  false
--R                                                    Type: Boolean
--E 22

--S 23 of 38
one?(factor(1))
--R
--R
--R   (23)  true
--R                                                    Type: Boolean
--E 23

--S 24 of 38
one?(f)
--R
--R
--R   (24)  false
--R                                                    Type: Boolean
--E 24

--S 25 of 38
0$Factored(Integer)
--R
--R
--R   (25)  0
--R                                          Type: Factored(Integer)
--E 25

--S 26 of 38
1$Factored(Integer)
--R
--R
--R   (26)  1
--R                                          Type: Factored(Integer)
--E 26
```

```
--S 27 of 38
nilFactor(24,2)
--R
--R
--R           2
--R   (27)  24
--R                                                Type: Factored(Integer)
--E 27

--S 28 of 38
nthFlag(%,1)
--R
--R
--R   (28)  "nil"
--R                                                 Type: Union("nil",...)
--E 28

--S 29 of 38
sqfrFactor(30,2)
--R
--R
--R           2
--R   (29)  30
--R                                                Type: Factored(Integer)
--E 29

--S 30 of 38
irreducibleFactor(13,10)
--R
--R
--R           10
--R   (30)  13
--R                                                Type: Factored(Integer)
--E 30

--S 31 of 38
primeFactor(11,5)
--R
--R
--R           5
--R   (31)  11
--R                                                Type: Factored(Integer)
--E 31

--S 32 of 38
h := factor(-720)
--R
--R
--R            4 2
--R   (32)  - 2 3 5
```

```
--R                                                    Type: Factored(Integer)
--E 32

--S 33 of 38
h - makeFR(unit(h),factorList(h))
--R
--R
--R   (33)  0
--R                                                    Type: Factored(Integer)
--E 33

--S 34 of 38
p := (4*x*x-12*x+9)*y*y + (4*x*x-12*x+9)*y + 28*x*x - 84*x + 63
--R
--R
--R            2            2      2                  2
--R   (34)  (4x  - 12x + 9)y  + (4x  - 12x + 9)y + 28x  - 84x + 63
--R                                                    Type: Polynomial(Integer)
--E 34

--S 35 of 38
fp := factor(p)
--R
--R
--R                 2  2
--R   (35)  (2x - 3) (y  + y + 7)
--R                                          Type: Factored(Polynomial(Integer))
--E 35

--S 36 of 38
D(p,x)
--R
--R
--R                   2
--R   (36)  (8x - 12)y  + (8x - 12)y + 56x - 84
--R                                                    Type: Polynomial(Integer)
--E 36

--S 37 of 38
D(fp,x)
--R
--R
--R                    2
--R   (37)  4(2x - 3)(y  + y + 7)
--R                                          Type: Factored(Polynomial(Integer))
--E 37

--S 38 of 38
numberOfFactors(%)
--R
```

```
--R
--R   (38)  3
--R                                                    Type: PositiveInteger
--E 38
)spool
)lisp (bye)
```

———-

— Factored.help —

```
====================================================================
Factored examples
====================================================================

Factored creates a domain whose objects are kept in factored form as
long as possible.  Thus certain operations like * (multiplication) and
gcd are relatively easy to do.  Others, such as addition, require
somewhat more work, and the result may not be completely factored
unless the argument domain R provides a factor operation.  Each object
consists of a unit and a list of factors, where each factor consists
of a member of R (the base), an exponent, and a flag indicating what
is known about the base.  A flag may be one of "nil", "sqfr", "irred"
or "prime", which mean that nothing is known about the base, it is
square-free, it is irreducible, or it is prime, respectively.  The
current restriction to factored objects of integral domains allows
simplification to be performed without worrying about multiplication
order.

====================================================================
Decomposing Factored Objects
====================================================================

In this section we will work with a factored integer.

  g := factor(4312)
     3 2
    2 7 11
                          Type: Factored Integer

Let's begin by decomposing g into pieces.  The only possible
units for integers are 1 and -1.

  unit(g)
    1
                          Type: PositiveInteger

There are three factors.
```

```
  numberOfFactors(g)
    3
                          Type: PositiveInteger
```

We can make a list of the bases, ...

```
  [nthFactor(g,i) for i in 1..numberOfFactors(g)]
    [2,7,11]
                          Type: List Integer
```

and the exponents, ...

```
  [nthExponent(g,i) for i in 1..numberOfFactors(g)]
    [3,2,1]
                          Type: List Integer
```

and the flags. You can see that all the bases (factors) are prime.

```
  [nthFlag(g,i) for i in 1..numberOfFactors(g)]
    ["prime","prime","prime"]
                          Type: List Union("nil","sqfr","irred","prime")
```

A useful operation for pulling apart a factored object into a list
of records of the components is factorList.

```
  factorList(g)
    [[flg= "prime",fctr= 2,xpnt= 3], [flg= "prime",fctr= 7,xpnt= 2],
     [flg= "prime",fctr= 11,xpnt= 1]]
           Type: List Record(flg: Union("nil","sqfr","irred","prime"),
                             fctr: Integer,xpnt: Integer)
```

If you don't care about the flags, use factors.

```
  factors(g)
    [[factor= 2,exponent= 3],[factor= 7,exponent= 2],[factor= 11,exponent= 1]]
                          Type: List Record(factor: Integer,exponent: Integer)
```

Neither of these operations returns the unit.

```
  first(%).factor
    2
                          Type: PositiveInteger
```

```
========================================================================
Expanding Factored Objects
========================================================================
```

Recall that we are working with this factored integer.

```
  g := factor(4312)
```

```
     3 2
    2 7 11
                          Type: Factored Integer

To multiply out the factors with their multiplicities, use expand.

  expand(g)
    4312
                          Type: PositiveInteger

If you would like, say, the distinct factors multiplied together but
with multiplicity one, you could do it this way.

  reduce(*,[t.factor for t in factors(g)])
    154
                          Type: PositiveInteger

================================================================
Arithmetic with Factored Objects
================================================================

We're still working with this factored integer.

  g := factor(4312)
     3 2
    2 7 11
                          Type: Factored Integer

We'll also define this factored integer.

  f := factor(246960)
     4 2   3
    2 3 5 7
                          Type: Factored Integer

Operations involving multiplication and division are particularly
easy with factored objects.

  f * g
     7 2   5
    2 3 5 7 11
                          Type: Factored Integer

  f**500
     2000 1000 500 1500
    2    3    5   7
                          Type: Factored Integer

  gcd(f,g)
     3 2
```

```
   2 7
                        Type: Factored Integer

  lcm(f,g)
     4 2   3
    2 3 5 7 11
                        Type: Factored Integer
```

If we use addition and subtraction things can slow down because
we may need to compute greatest common divisors.

```
  f + g
     3 2
    2 7 641
                        Type: Factored Integer

  f - g
     3 2
    2 7 619
                        Type: Factored Integer
```

Test for equality with 0 and 1 by using zero? and one?, respectively.

```
  zero?(factor(0))
    true
                        Type: Boolean

  zero?(g)
    false
                        Type: Boolean

  one?(factor(1))
    true
                        Type: Boolean

  one?(f)
    false
                        Type: Boolean
```

Another way to get the zero and one factored objects is to use
package calling.

```
  0$Factored(Integer)
    0
                        Type: Factored Integer

  1$Factored(Integer)
    1
                        Type: Factored Integer
```

```
=====================================================================
Creating New Factored Objects
=====================================================================

The map operation is used to iterate across the unit and bases of a
factored object.

The following four operations take a base and an exponent and create a
factored object.  They differ in handling the flag component.

  nilFactor(24,2)
      2
    24
                          Type: Factored Integer

This factor has no associated information.

  nthFlag(%,1)
    "nil"
                          Type: Union("nil",...)

This factor is asserted to be square-free.

  sqfrFactor(30,2)
      2
    30
                          Type: Factored Integer

This factor is asserted to be irreducible.

  irreducibleFactor(13,10)
      10
    13
                          Type: Factored Integer

This factor is asserted to be prime.

  primeFactor(11,5)
      5
    11
                          Type: Factored Integer

A partial inverse to factorList is makeFR.

  h := factor(-720)
       4 2
    - 2 3 5
                          Type: Factored Integer

The first argument is the unit and the second is a list of records as
```

```
returned by factorList.

  h - makeFR(unit(h),factorList(h))
    0
                          Type: Factored Integer

========================================================================
Factored Objects with Variables
========================================================================

Some of the operations available for polynomials are also available
for factored polynomials.

  p := (4*x*x-12*x+9)*y*y + (4*x*x-12*x+9)*y + 28*x*x - 84*x + 63
       2            2      2                   2
    (4x  - 12x + 9)y  + (4x  - 12x + 9)y + 28x  - 84x + 63
                          Type: Polynomial Integer

  fp := factor(p)
            2  2
    (2x - 3) (y  + y + 7)
                          Type: Factored Polynomial Integer

You can differentiate with respect to a variable.

  D(p,x)
              2
    (8x - 12)y  + (8x - 12)y + 56x - 84
                          Type: Polynomial Integer


  D(fp,x)
               2
    4(2x - 3)(y  + y + 7)
                          Type: Factored Polynomial Integer

  numberOfFactors(%)
    3
                          Type: PositiveInteger

See Also:
o )help FactoredFunctions2
o )show Factored
```

———-

7.1.1 Factored (FR)



Exports:

0	1	associates?	characteristic	coerce
convert	D	differentiate	eval	expand
exponent	exquo	factor	factorList	factors
flagFactor	gcd	gcdPolynomial	hash	irreducibleFactor
latex	lcm	makeFR	map	nilFactor
nthExponent	nthFactor	nthFlag	numberOfFactors	one?
prime?	primeFactor	rational	rational?	rationalIfCan
recip	retract	retractIfCan	sample	sqfrFactor
squareFree	squareFreePart	subtractIfCan	unit	unit?
unitCanonical	unitNormal	unitNormalize	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?	?.?		

— domain FR Factored —

```
)abbrev domain FR Factored
++ Author: Robert S. Sutor
++ Date Created: 1985
++ Change History:
++   21 Jan 1991  J Grabmeier     Corrected a bug in exquo.
++   16 Aug 1994  R S Sutor       Improved convert to InputForm
++ Basic Operations:
++   expand, exponent, factorList, factors, flagFactor, irreducibleFactor,
++   makeFR, map, nilFactor, nthFactor, nthFlag, numberOfFactors,
++   primeFactor, sqfrFactor, unit, unitNormalize,
++ Related Constructors: FactoredFunctionUtilities, FactoredFunctions2
++ Also See:
++ AMS Classifications: 11A51, 11Y05
++ Keywords: factorization, prime, square-free, irreducible, factor
++ References:
++ Description:
++ \spadtype{Factored} creates a domain whose objects are kept in
++ factored form as long as possible.  Thus certain operations like
```

```
++ multiplication and gcd are relatively easy to do.  Others, like
++ addition require somewhat more work, and unless the argument
++ domain provides a factor function, the result may not be
++ completely factored.  Each object consists of a unit and a list of
++ factors, where a factor has a member of R (the "base"), and
++ exponent and a flag indicating what is known about the base.  A
++ flag may be one of "nil", "sqfr", "irred" or "prime", which respectively mean
++ that nothing is known about the base, it is square-free, it is
++ irreducible, or it is prime.  The current
++ restriction to integral domains allows simplification to be
++ performed without worrying about multiplication order.

Factored(R: IntegralDomain): Exports == Implementation where
  fUnion ==> Union("nil", "sqfr", "irred", "prime")
  FF     ==> Record(flg: fUnion, fctr: R, xpnt: Integer)
  SRFE   ==> Set(Record(factor:R, exponent:Integer))

  Exports ==> Join(IntegralDomain, DifferentialExtension R, Algebra R,
                   FullyEvalableOver R, FullyRetractableTo R) with
   expand: % -> R
    ++ expand(f) multiplies the unit and factors together, yielding an
    ++ "unfactored" object. Note: this is purposely not called
    ++ \spadfun{coerce} which would cause the interpreter to do this
    ++ automatically.
    ++
    ++X f:=nilFactor(y-x,3)
    ++X expand(f)

   exponent:  % -> Integer
    ++ exponent(u) returns the exponent of the first factor of
    ++ \spadvar{u}, or 0 if the factored form consists solely of a unit.
    ++
    ++X f:=nilFactor(y-x,3)
    ++X exponent(f)

   makeFR  : (R, List FF) -> %
    ++ makeFR(unit,listOfFactors) creates a factored object (for
    ++ use by factoring code).
    ++
    ++X f:=nilFactor(x-y,3)
    ++X g:=factorList f
    ++X makeFR(z,g)

   factorList : % -> List FF
    ++ factorList(u) returns the list of factors with flags (for
    ++ use by factoring code).
    ++
    ++X f:=nilFactor(x-y,3)
    ++X factorList f
```

```
nilFactor: (R, Integer) -> %
 ++ nilFactor(base,exponent) creates a factored object with
 ++ a single factor with no information about the kind of
 ++ base (flag = "nil").
 ++
 ++X nilFactor(24,2)
 ++X nilFactor(x-y,3)

factors: % -> List Record(factor:R, exponent:Integer)
 ++ factors(u) returns a list of the factors in a form suitable
 ++ for iteration. That is, it returns a list where each element
 ++ is a record containing a base and exponent.  The original
 ++ object is the product of all the factors and the unit (which
 ++ can be extracted by \axiom{unit(u)}).
 ++
 ++X f:=x*y^3-3*x^2*y^2+3*x^3*y-x^4
 ++X factors f
 ++X g:=makeFR(z,factorList f)
 ++X factors g

irreducibleFactor: (R, Integer) -> %
 ++ irreducibleFactor(base,exponent) creates a factored object with
 ++ a single factor whose base is asserted to be irreducible
 ++ (flag = "irred").
 ++
 ++X a:=irreducibleFactor(3,1)
 ++X nthFlag(a,1)

nthExponent: (%, Integer) -> Integer
 ++ nthExponent(u,n) returns the exponent of the nth factor of
 ++ \spadvar{u}.  If \spadvar{n} is not a valid index for a factor
 ++ (for example, less than 1 or too big), 0 is returned.
 ++
 ++X a:=factor 9720000
 ++X nthExponent(a,2)

nthFactor:  (%,Integer) -> R
 ++ nthFactor(u,n) returns the base of the nth factor of
 ++ \spadvar{u}.  If \spadvar{n} is not a valid index for a factor
 ++ (for example, less than 1 or too big), 1 is returned.  If
 ++ \spadvar{u} consists only of a unit, the unit is returned.
 ++
 ++X a:=factor 9720000
 ++X nthFactor(a,2)

nthFlag:    (%,Integer) -> fUnion
 ++ nthFlag(u,n) returns the information flag of the nth factor of
 ++ \spadvar{u}.  If \spadvar{n} is not a valid index for a factor
 ++ (for example, less than 1 or too big), "nil" is returned.
 ++
```

```
 ++X a:=factor 9720000
 ++X nthFlag(a,2)

numberOfFactors : %  -> NonNegativeInteger
 ++ numberOfFactors(u) returns the number of factors in \spadvar{u}.
 ++
 ++X a:=factor 9720000
 ++X numberOfFactors a

primeFactor:   (R,Integer) -> %
 ++ primeFactor(base,exponent) creates a factored object with
 ++ a single factor whose base is asserted to be prime
 ++ (flag = "prime").
 ++
 ++X a:=primeFactor(3,4)
 ++X nthFlag(a,1)

sqfrFactor:   (R,Integer) -> %
 ++ sqfrFactor(base,exponent) creates a factored object with
 ++ a single factor whose base is asserted to be square-free
 ++ (flag = "sqfr").
 ++
 ++X a:=sqfrFactor(3,5)
 ++X nthFlag(a,1)

flagFactor: (R,Integer, fUnion) -> %
 ++ flagFactor(base,exponent,flag) creates a factored object with
 ++ a single factor whose base is asserted to be properly
 ++ described by the information flag.

unit:    % -> R
 ++ unit(u) extracts the unit part of the factorization.
 ++
 ++X f:=x*y^3-3*x^2*y^2+3*x^3*y-x^4
 ++X unit f
 ++X g:=makeFR(z,factorList f)
 ++X unit g

unitNormalize: % -> %
 ++ unitNormalize(u) normalizes the unit part of the factorization.
 ++ For example, when working with factored integers, this operation will
 ++ ensure that the bases are all positive integers.

map:     (R -> R, %) -> %
 ++ map(fn,u) maps the function \userfun{fn} across the factors of
 ++ \spadvar{u} and creates a new factored object. Note: this clears
 ++ the information flags (sets them to "nil") because the effect of
 ++ \userfun{fn} is clearly not known in general.
 ++
 ++X m(a:Factored Polynomial Integer):Factored Polynomial Integer == a^2
```

```
    ++X f:=x*y^3-3*x^2*y^2+3*x^3*y-x^4
    ++X map(m,f)
    ++X g:=makeFR(z,factorList f)
    ++X map(m,g)

    -- the following operations are conditional on R

   if R has GcdDomain then GcdDomain
   if R has RealConstant then RealConstant
   if R has UniqueFactorizationDomain then UniqueFactorizationDomain

   if R has ConvertibleTo InputForm then ConvertibleTo InputForm

   if R has IntegerNumberSystem then
      rational?    : % -> Boolean
        ++ rational?(u) tests if \spadvar{u} is actually a
        ++ rational number (see \spadtype{Fraction Integer}).
      rational     : % -> Fraction Integer
        ++ rational(u) assumes spadvar{u} is actually a rational number
        ++ and does the conversion to rational number
        ++ (see \spadtype{Fraction Integer}).
      rationalIfCan: % -> Union(Fraction Integer, "failed")
        ++ rationalIfCan(u) returns a rational number if u
        ++ really is one, and "failed" otherwise.

   if R has Eltable(%, %) then Eltable(%, %)
   if R has Evalable(%) then Evalable(%)
   if R has InnerEvalable(Symbol, %) then InnerEvalable(Symbol, %)

  Implementation ==> add

  -- Representation:
    -- Note: exponents are allowed to be integers so that some special cases
    -- may be used in simplications
    Rep := Record(unt:R, fct:List FF)

    if R has ConvertibleTo InputForm then
      convert(x:%):InputForm ==
        empty?(lf := reverse factorList x) => convert(unit x)@InputForm
        l := empty()$List(InputForm)
        for rec in lf repeat
--          one?(rec.fctr) => l
          ((rec.fctr) = 1) => l
          iFactor : InputForm := binary( convert("::" :: Symbol)@InputForm, [convert(rec.fctr)@I
          iExpon  : InputForm := convert(rec.xpnt)@InputForm
          iFun    : List InputForm :=
            rec.flg case "nil" =>
               [convert("nilFactor" :: Symbol)@InputForm, iFactor, iExpon]$List(InputForm)
            rec.flg case "sqfr" =>
               [convert("sqfrFactor" :: Symbol)@InputForm, iFactor, iExpon]$List(InputForm)
```

```
            rec.flg case "prime" =>
               [convert("primeFactor" :: Symbol)@InputForm, iFactor, iExpon]$List(InputForm)
            rec.flg case "irred" =>
               [convert("irreducibleFactor" :: Symbol)@InputForm, iFactor, iExpon]$List(InputForm)
            nil$List(InputForm)
          l := concat( iFun pretend InputForm, l )
--        one?(rec.xpnt) =>
--          l := concat(convert(rec.fctr)@InputForm, l)
--        l := concat(convert(rec.fctr)@InputForm ** rec.xpnt, l)
        empty? l => convert(unit x)@InputForm
        if unit x ^= 1 then l := concat(convert(unit x)@InputForm,l)
        empty? rest l => first l
        binary(convert(_*::Symbol)@InputForm, l)@InputForm

    orderedR? := R has OrderedSet

  -- Private function signatures:
    reciprocal              : % -> %
    qexpand                 : % -> R
    negexp?                 : % -> Boolean
    SimplifyFactorization   : List FF -> List FF
    LispLessP               : (FF, FF) -> Boolean
    mkFF                    : (R, List FF) -> %
    SimplifyFactorization1  : (FF, List FF) -> List FF
    stricterFlag            : (fUnion, fUnion) -> fUnion

    nilFactor(r, i)      == flagFactor(r, i, "nil")
    sqfrFactor(r, i)     == flagFactor(r, i, "sqfr")
    irreducibleFactor(r, i)      == flagFactor(r, i, "irred")
    primeFactor(r, i)    == flagFactor(r, i, "prime")
    unit? u              == (empty? u.fct) and (not zero? u.unt)
    factorList u         == u.fct
    unit u               == u.unt
    numberOfFactors u    == # u.fct
    0                    == [1, [["nil", 0, 1]$FF]]
    zero? u              == # u.fct = 1 and
                             (first u.fct).flg case "nil" and
                              zero? (first u.fct).fctr and
--                               one? u.unt
                               (u.unt = 1)
    1                    == [1, empty()]
    one? u               == empty? u.fct and u.unt = 1
    mkFF(r, x)           == [r, x]
    coerce(j:Integer):%  == (j::R)::%
    characteristic()     == characteristic()$R
    i:Integer * u:%      == (i :: %) * u
    r:R * u:%            == (r :: %) * u
    factors u            == [[fe.fctr, fe.xpnt] for fe in factorList u]
    expand u             == retract u
    negexp? x           == "or"/[negative?(y.xpnt) for y in factorList x]
```

```
    makeFR(u, l) ==
-- normalizing code to be installed when contents are handled better
-- current squareFree returns the content as a unit part.
--        if (not unit?(u)) then
--            l := cons(["nil", u, 1]$FF,l)
--            u := 1
        unitNormalize mkFF(u, SimplifyFactorization l)

    if R has IntegerNumberSystem then
      rational? x     == true
      rationalIfCan x == rational x

      rational x ==
        convert(unit x)@Integer *
           _*/[(convert(f.fctr)@Integer)::Fraction(Integer)
                                  ** f.xpnt for f in factorList x]

    if R has Eltable(R, R) then
      elt(x:%, v:%) == x(expand v)

    if R has Evalable(R) then
      eval(x:%, l:List Equation %) ==
        eval(x,[expand lhs e = expand rhs e for e in l]$List(Equation R))

    if R has InnerEvalable(Symbol, R) then
      eval(x:%, ls:List Symbol, lv:List %) ==
        eval(x, ls, [expand v for v in lv]$List(R))

    if R has RealConstant then
  --! negcount and rest commented out since RealConstant doesn't support
  --! positive? or negative?
  --  negcount: % -> Integer
  --  positive?(x:%):Boolean == not(zero? x) and even?(negcount x)
  --  negative?(x:%):Boolean == not(zero? x) and odd?(negcount x)
  --  negcount x ==
  --    n := count(negative?(#1.fctr), factorList x)$List(FF)
  --    negative? unit x => n + 1
  --    n

      convert(x:%):Float ==
        convert(unit x)@Float *
                _*/[convert(f.fctr)@Float ** f.xpnt for f in factorList x]

      convert(x:%):DoubleFloat ==
        convert(unit x)@DoubleFloat *
          _*/[convert(f.fctr)@DoubleFloat ** f.xpnt for f in factorList x]

    u:% * v:% ==
      zero? u or zero? v => 0
```

```
--      one? u => v
      (u = 1) => v
--      one? v => u
      (v = 1) => u
      mkFF(unit u * unit v,
          SimplifyFactorization concat(factorList u, copy factorList v))

    u:% ** n:NonNegativeInteger ==
      mkFF(unit(u)**n, [[x.flg, x.fctr, n * x.xpnt] for x in factorList u])

    SimplifyFactorization x ==
      empty? x => empty()
      x := sort_!(LispLessP, x)
      x := SimplifyFactorization1(first x, rest x)
      if orderedR? then x := sort_!(LispLessP, x)
      x

    SimplifyFactorization1(f, x) ==
      empty? x =>
        zero?(f.xpnt) => empty()
        list f
      f1 := first x
      f.fctr = f1.fctr =>
        SimplifyFactorization1([stricterFlag(f.flg, f1.flg),
                                    f.fctr, f.xpnt + f1.xpnt], rest x)
      l := SimplifyFactorization1(first x, rest x)
      zero?(f.xpnt) => l
      concat(f, l)


    coerce(x:%):OutputForm ==
      empty?(lf := reverse factorList x) => (unit x)::OutputForm
      l := empty()$List(OutputForm)
      for rec in lf repeat
--        one?(rec.fctr) => l
        ((rec.fctr) = 1) => l
--        one?(rec.xpnt) =>
        ((rec.xpnt) = 1) =>
          l := concat(rec.fctr :: OutputForm, l)
        l := concat(rec.fctr::OutputForm ** rec.xpnt::OutputForm, l)
      empty? l => (unit x) :: OutputForm
      e :=
        empty? rest l => first l
        reduce(_*, l)
      1 = unit x => e
      (unit x)::OutputForm * e

    retract(u:%):R ==
      negexp? u =>  error "Negative exponent in factored object"
      qexpand u
```

```
    qexpand u ==
      unit u *
         _*/[y.fctr ** (y.xpnt::NonNegativeInteger) for y in factorList u]

    retractIfCan(u:%):Union(R, "failed") ==
      negexp? u => "failed"
      qexpand u

    LispLessP(y, y1) ==
      orderedR? => y.fctr < y1.fctr
      GGREATERP(y.fctr, y1.fctr)$Lisp => false
      true

    stricterFlag(fl1, fl2) ==
      fl1 case "prime"   => fl1
      fl1 case "irred"   =>
        fl2 case "prime" => fl2
        fl1
      fl1 case "sqfr"    =>
        fl2 case "nil"   => fl1
        fl2
      fl2

    if R has IntegerNumberSystem
      then
        coerce(r:R):% ==
          factor(r)$IntegerFactorizationPackage(R) pretend %
      else
        if R has UniqueFactorizationDomain
          then
            coerce(r:R):% ==
              zero? r => 0
              unit? r => mkFF(r, empty())
              unitNormalize(squareFree(r) pretend %)
          else
            coerce(r:R):% ==
--              one? r => 1
              (r = 1) => 1
              unitNormalize mkFF(1, [["nil", r, 1]$FF])

    u = v ==
      (unit u = unit v) and # u.fct = # v.fct and
        set(factors u)$SRFE =$SRFE set(factors v)$SRFE

    - u ==
      zero? u => u
      mkFF(- unit u, factorList u)

    recip u  ==
```

```
    not empty? factorList u => "failed"
    (r := recip unit u) case "failed" => "failed"
    mkFF(r::R, empty())

  reciprocal u ==
    mkFF((recip unit u)::R,
                 [[y.flg, y.fctr, - y.xpnt]$FF for y in factorList u])

  exponent u ==  -- exponent of first factor
    empty?(fl := factorList u) or zero? u => 0
    first(fl).xpnt

  nthExponent(u, i) ==
    l := factorList u
    zero? u or i < 1 or i > #l => 0
    (l.(minIndex(l) + i - 1)).xpnt

  nthFactor(u, i) ==
    zero? u => 0
    zero? i => unit u
    l := factorList u
    negative? i or i > #l => 1
    (l.(minIndex(l) + i - 1)).fctr

  nthFlag(u, i) ==
    l := factorList u
    zero? u or i < 1 or i > #l => "nil"
    (l.(minIndex(l) + i - 1)).flg

  flagFactor(r, i, fl) ==
    zero? i => 1
    zero? r => 0
    unitNormalize mkFF(1, [[fl, r, i]$FF])

  differentiate(u:%, deriv: R -> R) ==
    ans := deriv(unit u) * ((u exquo unit(u)::%)::%)
    ans + (_+/[fact.xpnt * deriv(fact.fctr) *
     ((u exquo nilFactor(fact.fctr, 1))::%) for fact in factorList u])

  map(fn, u) ==
   fn(unit u) * _*/[irreducibleFactor(fn(f.fctr),f.xpnt) for f in factorList u]

  u exquo v ==
    empty?(x1 := factorList v) =>  unitNormal(retract v).associate *  u
    empty? factorList u => "failed"
    v1 := u * reciprocal v
    goodQuotient:Boolean := true
    while (goodQuotient and (not empty? x1)) repeat
      if x1.first.xpnt < 0
        then goodQuotient := false
```

```
          else x1 := rest x1
      goodQuotient => v1
      "failed"

    unitNormal u == -- does a bunch of work, but more canonical
      (ur := recip(un := unit u)) case "failed" => [1, u, 1]
      as := ur::R
      vl := empty()$List(FF)
      for x in factorList u repeat
        ucar := unitNormal(x.fctr)
        e := abs(x.xpnt)::NonNegativeInteger
        if x.xpnt < 0
          then  --  associate is recip of unit
            un := un * (ucar.associate ** e)
            as := as * (ucar.unit ** e)
          else
            un := un * (ucar.unit ** e)
            as := as * (ucar.associate ** e)
--        if not one?(ucar.canonical) then
        if not ((ucar.canonical) = 1) then
          vl := concat([x.flg, ucar.canonical, x.xpnt], vl)
      [mkFF(un, empty()), mkFF(1, reverse_! vl), mkFF(as, empty())]

    unitNormalize u ==
      uca := unitNormal u
      mkFF(unit(uca.unit)*unit(uca.canonical),factorList(uca.canonical))

    if R has GcdDomain then
      u + v ==
        zero? u => v
        zero? v => u
        v1 := reciprocal(u1 := gcd(u, v))
        (expand(u * v1) + expand(v * v1)) * u1

      gcd(u, v) ==
--        one? u or one? v => 1
        (u = 1) or (v = 1) => 1
        zero? u => v
        zero? v => u
        f1 := empty()$List(Integer)  -- list of used factor indices in x
        f2 := f1      -- list of indices corresponding to a given factor
        f3 := empty()$List(List Integer)    -- list of f2-like lists
        x := concat(factorList u, factorList v)
        for i in minIndex x .. maxIndex x repeat
          if not member?(i, f1) then
            f1 := concat(i, f1)
            f2 := [i]
            for j in i+1..maxIndex x repeat
              if x.i.fctr = x.j.fctr then
                  f1 := concat(j, f1)
```

```
                f2 := concat(j, f2)
            f3 := concat(f2, f3)
        x1 := empty()$List(FF)
        while not empty? f3 repeat
          f1 := first f3
          if #f1 > 1 then
            i  := first f1
            y  := copy x.i
            f1 := rest f1
            while not empty? f1 repeat
              i := first f1
              if x.i.xpnt < y.xpnt then y.xpnt := x.i.xpnt
              f1 := rest f1
            x1 := concat(y, x1)
          f3 := rest f3
        if orderedR? then x1 := sort_!(LispLessP, x1)
        mkFF(1, x1)

    else   -- R not a GCD domain
      u + v ==
        zero? u => v
        zero? v => u
        irreducibleFactor(expand u + expand v, 1)

    if R has UniqueFactorizationDomain then
      prime? u ==
        not(empty?(l := factorList u)) and (empty? rest l) and
--                        one?(l.first.xpnt) and (l.first.flg case "prime")
                        ((l.first.xpnt) = 1) and (l.first.flg case "prime")
```

———-

— **FR.dotabb** —

```
"FR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FR"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FR" -> "ALIST"
```

———-

7.2 domain FILE File

— **File.input** —

```
)set break resume
```

```
)sys rm -f File.output
)spool File.output
)set message test on
)set message auto off
)clear all
--S 1 of 12
ifile:File List Integer:=open("jazz1","output")
--R
--R
--R   (1)  "jazz1"
--R                                                  Type: File(List(Integer))
--E 1

--S 2 of 12
write!(ifile, [-1,2,3])
--R
--R
--R   (2)  [- 1,2,3]
--R                                                        Type: List(Integer)
--E 2

--S 3 of 12
write!(ifile, [10,-10,0,111])
--R
--R
--R   (3)  [10,- 10,0,111]
--R                                                        Type: List(Integer)
--E 3

--S 4 of 12
write!(ifile, [7])
--R
--R
--R   (4)  [7]
--R                                                        Type: List(Integer)
--E 4

--S 5 of 12
reopen!(ifile, "input")
--R
--R
--R   (5)  "jazz1"
--R                                                  Type: File(List(Integer))
--E 5

--S 6 of 12
read! ifile
--R
--R
--R   (6)  [- 1,2,3]
```

```
--R                                                    Type: List(Integer)
--E 6

--S 7 of 12
read! ifile
--R
--R
--R   (7)  [10,- 10,0,111]
--R                                                    Type: List(Integer)
--E 7

--S 8 of 12
readIfCan! ifile
--R
--R
--R   (8)  [7]
--R                                          Type: Union(List(Integer),...)
--E 8

--S 9 of 12
readIfCan! ifile
--R
--R
--R   (9)  "failed"
--R                                               Type: Union("failed",...)
--E 9

--S 10 of 12
iomode ifile
--R
--R
--R   (10)  "input"
--R                                                       Type: String
--E 10

--S 11 of 12
name ifile
--R
--R
--R   (11)  "jazz1"
--R                                                    Type: FileName
--E 11

--S 12 of 12
close! ifile
--R
--R
--R   (12)  "jazz1"
--R                                               Type: File(List(Integer))
--E 12
```

```
)system rm jazz1
)spool
)lisp (bye)
```

———-

— File.help —

```
========================================================================
File examples
========================================================================

The File(S) domain provides a basic interface to read and write values
of type S in files.

Before working with a file, it must be made accessible to Axiom with
the open operation.

  ifile:File List Integer:=open("/tmp/jazz1","output")
    "jazz1"
                        Type: File List Integer

The open function arguments are a FileNam} and a String specifying the
mode.  If a full pathname is not specified, the current default
directory is assumed.  The mode must be one of "input" or "output".
If it is not specified, "input" is assumed.  Once the file has been
opened, you can read or write data.

The operations read and write are provided.

  write!(ifile, [-1,2,3])
    [- 1,2,3]
                        Type: List Integer

  write!(ifile, [10,-10,0,111])
    [10,- 10,0,111]
                        Type: List Integer

  write!(ifile, [7])
    [7]
                        Type: List Integer

You can change from writing to reading (or vice versa) by reopening a file.

  reopen!(ifile, "input")
    "jazz1"
                        Type: File List Integer

  read! ifile
```

```
    [- 1,2,3]
                          Type: List Integer

  read! ifile
    [10,- 10,0,111]
                          Type: List Integer
```

The read operation can cause an error if one tries to read more data than is in the file. To guard against this possibility the readIfCan operation should be used.

```
  readIfCan! ifile
    [7]
                          Type: Union(List Integer,...)

  readIfCan! ifile
    "failed"
                          Type: Union("failed",...)
```

You can find the current mode of the file, and the file's name.

```
  iomode ifile
    "input"
                          Type: String

  name ifile
    "jazz1"
                          Type: FileName
```

When you are finished with a file, you should close it.

```
  close! ifile
    "jazz1"
                          Type: File List Integer


  )system rm /tmp/jazz1
```

A limitation of the underlying LISP system is that not all values can be represented in a file. In particular, delayed values containing compiled functions cannot be saved.

See Also:
o)help TextFile
o)help KeyedAccessFile
o)help Library
o)help Filename
o)show File

———-

7.2.1 File (FILE)



See

⇒ "TextFile" (TEXTFILE) 21.5.1 on page 2661
⇒ "BinaryFile" (BINFILE) 3.8.1 on page 279
⇒ "KeyedAccessFile" (KAFILE) 12.2.1 on page 1381
⇒ "Library" (LIB) 13.2.1 on page 1396

Exports:

close!	coerce	flush	hash	iomode
latex	name	open	readIfCan!	read!
reopen!	write!	?=?	?~=?	

— domain FILE File —

```
)abbrev domain FILE File
++ Author: Stephen M. Watt, Victor Miller
++ Date Created: 1984
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain provides a basic model of files to save arbitrary values.
++ The operations provide sequential access to the contents.

File(S:SetCategory): FileCategory(FileName, S) with
        readIfCan_!: % -> Union(S, "failed")
            ++ readIfCan!(f) returns a value from the file f, if possible.
            ++ If f is not open for reading, or if f is at the end of file
            ++ then \spad{"failed"} is the result.
```

```
== add
    FileState ==> SExpression
    IOMode    ==> String

    Rep:=Record(fileName:    FileName,   _
                fileState:   FileState,  _
                fileIOmode:  IOMode)

    defstream(fn: FileName, mode: IOMode): FileState ==
        mode = "input"  =>
          not readable? fn => error ["File is not readable", fn]
          MAKE_-INSTREAM(fn::String)$Lisp
        mode = "output" =>
          not writable? fn => error ["File is not writable", fn]
          MAKE_-OUTSTREAM(fn::String)$Lisp
        error ["IO mode must be input or output", mode]

    f1 = f2 ==
        f1.fileName = f2.fileName
    coerce(f: %): OutputForm ==
        f.fileName::OutputForm

    open fname ==
        open(fname, "input")
    open(fname, mode) ==
        fstream := defstream(fname, mode)
        [fname, fstream, mode]
    reopen_!(f, mode) ==
        fname := f.fileName
        f.fileState := defstream(fname, mode)
        f.fileIOmode:= mode
        f
    close_! f ==
        SHUT(f.fileState)$Lisp
        f.fileIOmode := "closed"
        f
    name f ==
        f.fileName
    iomode f ==
        f.fileIOmode
    read_! f ==
        f.fileIOmode ^= "input" =>
            error "File not in read state"
        x := VMREAD(f.fileState)$Lisp
        PLACEP(x)$Lisp =>
            error "End of file"
        x
    readIfCan_! f ==
        f.fileIOmode ^= "input" =>
            error "File not in read state"
```

```
            x: S := VMREAD(f.fileState)$Lisp
            PLACEP(x)$Lisp => "failed"
            x
        write_!(f, x) ==
            f.fileIOmode ^= "output" =>
                error "File not in write state"
            z := PRINT_-FULL(x, f.fileState)$Lisp
            TERPRI(f.fileState)$Lisp
            x

        flush f ==
            f.fileIOmode ^= "output" => error "File not in write state"
            FORCE_-OUTPUT(f.fileState)$Lisp
```

———-

— FILE.dotabb —

```
"FILE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FILE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"FILE" -> "STRING"
```

———-

7.3 domain FNAME FileName

— FileName.input —

```
)set break resume
)sys rm -f FileName.output
)spool FileName.output
)set message test on
)set message auto off
)clear all
--S 1 of 18
fn: FileName
--R
--R                                                                Type: Void
--E 1

--S 2 of 18
fn := "fname.input"
--R
--R
```

```
--R   (2)  "fname.input"
--R                                                        Type: FileName
--E 2

--S 3 of 18
directory fn
--R
--R
--R   (3)  ""
--R                                                          Type: String
--E 3

--S 4 of 18
name fn
--R
--R
--R   (4)  "fname"
--R                                                          Type: String
--E 4

--S 5 of 18
extension fn
--R
--R
--R   (5)  "input"
--R                                                          Type: String
--E 5

--S 6 of 18
fn := filename("/tmp", "fname", "input")
--R
--R
--R   (6)  "/tmp/fname.input"
--R                                                        Type: FileName
--E 6

--S 7 of 18
objdir := "/tmp"
--R
--R
--R   (7)  "/tmp"
--R                                                          Type: String
--E 7

--S 8 of 18
fn := filename(objdir, "table", "spad")
--R
--R
--R   (8)  "/tmp/table.spad"
--R                                                        Type: FileName
```

```
--E 8

--S 9 of 18
fn := filename("", "letter", "")
--R
--R
--R   (9)  "letter"
--R                                                    Type: FileName
--E 9

--S 10 of 18
exists? "/etc/passwd"
--R
--R
--R   (10)  true
--R                                                     Type: Boolean
--E 10

--S 11 of 18
readable? "/etc/passwd"
--R
--R
--R   (11)  true
--R                                                     Type: Boolean
--E 11

--S 12 of 18
readable? "/etc/security/passwd"
--R
--R
--R   (12)  false
--R                                                     Type: Boolean
--E 12

--S 13 of 18
readable? "/ect/passwd"
--R
--R
--R   (13)  false
--R                                                     Type: Boolean
--E 13

--S 14 of 18
writable? "/etc/passwd"
--R
--R
--R   (14)  true
--R                                                     Type: Boolean
--E 14
```

```
--S 15 of 18
writable? "/dev/null"
--R
--R
--R   (15)  true
--R                                                          Type: Boolean
--E 15

--S 16 of 18
writable? "/etc/DoesNotExist"
--R
--R
--R   (16)  true
--R                                                          Type: Boolean
--E 16

--S 17 of 18
writable? "/tmp/DoesNotExist"
--R
--R
--R   (17)  true
--R                                                          Type: Boolean
--E 17

--S 18 of 18
fn := new(objdir, "xxx", "yy")
--R
--R
--I   (18)  "/tmp/xxx1419.yy"
--R                                                        Type: FileName
--E 18
)spool
)lisp (bye)
```

———-

— FileName.help —

```
=====================================================================
FileName examples
=====================================================================

The FileName domain provides an interface to the computer's file
system.  Functions are provided to manipulate file names and to test
properties of files.

The simplest way to use file names in the Axiom interpreter is to rely
on conversion to and from strings.  The syntax of these strings
depends on the operating system.
```

```
  fn: FileName
                        Type: Void
```

On Linux, this is a proper file syntax:

```
  fn := "fname.input"
    "fname.input"
                        Type: FileName
```

Although it is very convenient to be able to use string notation
for file names in the interpreter, it is desirable to have a portable
way of creating and manipulating file names from within programs.

A measure of portability is obtained by considering a file name to
consist of three parts: the directory, the name, and the extension.

```
  directory fn
    ""
                      Type: String

  name fn
    "fname"
                      Type: String

  extension fn
    "input"
                      Type: String
```

The meaning of these three parts depends on the operating system.
For example, on CMS the file "SPADPROF INPUT M" would have directory
"M", name "SPADPROF" and extension "INPUT".

It is possible to create a filename from its parts.

```
  fn := filename("/tmp", "fname", "input")
    "/tmp/fname.input"
                      Type: FileName
```

When writing programs, it is helpful to refer to directories via
variables.

```
  objdir := "/tmp"
    "/tmp"
                      Type: String

  fn := filename(objdir, "table", "spad")
    "/tmp/table.spad"
                      Type: FileName
```

```
If the directory or the extension is given as an empty string, then
a default is used.  On AIX, the defaults are the current directory
and no extension.

  fn := filename("", "letter", "")
    "letter"
                      Type: FileName

Three tests provide information about names in the file system.

The exists? operation tests whether the named file exists.

  exists? "/etc/passwd"
    true
                      Type: Boolean

The operation readable? tells whether the named file can be read.  If
the file does not exist, then it cannot be read.

  readable? "/etc/passwd"
    true
                      Type: Boolean

  readable? "/etc/security/passwd"
    false
                      Type: Boolean

  readable? "/ect/passwd"
    false
                      Type: Boolean

Likewise, the operation writable? tells whether the named file can be
written.  If the file does not exist, the test is determined by the
properties of the directory.

  writable? "/etc/passwd"
    true
                      Type: Boolean

  writable? "/dev/null"
    true
                      Type: Boolean

  writable? "/etc/DoesNotExist"
    true
                      Type: Boolean

  writable? "/tmp/DoesNotExist"
    true
                      Type: Boolean
```


```
The new operation constructs the name of a new writable file.  The
argument sequence is the same as for filename, except that the name
part is actually a prefix for a constructed unique name.

The resulting file is in the specified directory with the given
extension, and the same defaults are used.

  fn := new(objdir, "xxx", "yy")
    "/tmp/xxx1419.yy"
                      Type: FileName

See Also:
o )show FileName
```

7.3.1 FileName (FNAME)



Exports:

coerce	directory	exists?	extension	filename
hash	latex	name	new	readable?
writable?	?=?	?~=?		

— domain FNAME FileName —

```
)abbrev domain FNAME FileName
++ Author: Stephen M. Watt
++ Date Created: 1985
++ Date Last Updated: June 20, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
```

```
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain provides an interface to names in the file system.

FileName(): FileNameCategory == add

        f1 = f2                  == EQUAL(f1, f2)$Lisp
        coerce(f: %): OutputForm == f::String::OutputForm

        coerce(f: %): String     == NAMESTRING(f)$Lisp
        coerce(s: String): %     == PARSE_-NAMESTRING(s)$Lisp

        filename(d,n,e)          == fnameMake(d,n,e)$Lisp

        directory(f:%): String   == fnameDirectory(f)$Lisp
        name(f:%): String        == fnameName(f)$Lisp
        extension(f:%): String   == fnameType(f)$Lisp

        exists? f                == fnameExists?(f)$Lisp
        readable? f              == fnameReadable?(f)$Lisp
        writable? f              == fnameWritable?(f)$Lisp

        new(d,pref,e)            == fnameNew(d,pref,e)$Lisp
```

———-

— FNAME.dotabb —

```
"FNAME" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FNAME"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"FNAME" -> "STRING"
```

———-

7.4 domain FDIV FiniteDivisor

— FiniteDivisor.input —

```
)set break resume
)sys rm -f FiniteDivisor.output
)spool FiniteDivisor.output
)set message test on
```

```
)set message auto off
)clear all

--S 1 of 1
)show FiniteDivisor
--R
--R FiniteDivisor(F: Field,UP: UnivariatePolynomialCategory(F),UPUP: UnivariatePolynomialCategor
--R Abbreviation for FiniteDivisor is FDIV
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FDIV
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           coerce : % -> OutputForm
--R divisor : (R,UP,UP,UP,F) -> %         divisor : (F,F,Integer) -> %
--R divisor : (F,F) -> %                  divisor : R -> %
--R finiteBasis : % -> Vector(R)          hash : % -> SingleInteger
--R lSpaceBasis : % -> Vector(R)          latex : % -> String
--R principal? : % -> Boolean             reduce : % -> %
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R decompose : % -> Record(id: FractionalIdeal(UP,Fraction(UP),UPUP,R),principalPart: R)
--R divisor : FractionalIdeal(UP,Fraction(UP),UPUP,R) -> %
--R generator : % -> Union(R,"failed")
--R ideal : % -> FractionalIdeal(UP,Fraction(UP),UPUP,R)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— FiniteDivisor.help —

```
=====================================================================
FiniteDivisor examples
=====================================================================

See Also:
o )show FiniteDivisor
```

———-

7.4.1 FiniteDivisor (FDIV)



See

⇒ "FractionalIdeal" (FRIDEAL) 7.25.1 on page 965
⇒ "FramedModule" (FRMOD) 7.26.1 on page 970
⇒ "HyperellipticFiniteDivisor" (HELLFDIV) 9.11.1 on page 1153

Exports:

0	coerce	decompose	divisor	finiteBasis
generator	hash	ideal	lSpaceBasis	latex
principal?	reduce	sample	subtractIfCan	zero?
?~=?	?*?	?+?	?-?	-?
?=?				

— domain FDIV FiniteDivisor —

```
)abbrev domain FDIV FiniteDivisor
++ Author: Manuel Bronstein
++ Date Created: 1987
++ Date Last Updated: 29 July 1993
++ Description:
++ This domains implements finite rational divisors on a curve, that
++ is finite formal sums SUM(n * P) where the n's are integers and the
++ P's are finite rational points on the curve.
++ Keywords: divisor, algebraic, curve.
++ Examples: )r FDIV INPUT

FiniteDivisor(F, UP, UPUP, R): Exports == Implementation where
  F   : Field
  UP  : UnivariatePolynomialCategory F
  UPUP: UnivariatePolynomialCategory Fraction UP
  R   : FunctionFieldCategory(F, UP, UPUP)

  N   ==> NonNegativeInteger
  RF  ==> Fraction UP
  ID  ==> FractionalIdeal(UP, RF, UPUP, R)

  Exports ==> FiniteDivisorCategory(F, UP, UPUP, R) with
```

```
    finiteBasis: % -> Vector R
      ++ finiteBasis(d) returns a basis for d as a module over K[x].
    lSpaceBasis: % -> Vector R
      ++ lSpaceBasis(d) returns a basis for \spad{L(d) = {f | (f) >= -d}}
      ++ as a module over \spad{K[x]}.

  Implementation ==> add
    if hyperelliptic()$R case UP then
      Rep := HyperellipticFiniteDivisor(F, UP, UPUP, R)

      0                       == 0$Rep
      coerce(d:$):OutputForm  == coerce(d)$Rep
      d1 = d2                 == d1 =$Rep d2
      n * d                   == n *$Rep d
      d1 + d2                 == d1 +$Rep d2
      - d                     == -$Rep d
      ideal d                 == ideal(d)$Rep
      reduce d                == reduce(d)$Rep
      generator d             == generator(d)$Rep
      decompose d             == decompose(d)$Rep
      divisor(i:ID)           == divisor(i)$Rep
      divisor(f:R)            == divisor(f)$Rep
      divisor(a, b)           == divisor(a, b)$Rep
      divisor(a, b, n)        == divisor(a, b, n)$Rep
      divisor(h, d, dp, g, r) == divisor(h, d, dp, g, r)$Rep

    else
      Rep := Record(id:ID, fbasis:Vector(R))

      import CommonDenominator(UP, RF, Vector RF)
      import UnivariatePolynomialCommonDenominator(UP, RF, UPUP)

      makeDivisor : (UP, UPUP, UP) -> %
      intReduce   : (R, UP) -> R

      ww := integralBasis()$R

      0                       == [1, empty()]
      divisor(i:ID)           == [i, empty()]
      divisor(f:R)            == divisor ideal [f]
      coerce(d:%):OutputForm  == ideal(d)::OutputForm
      ideal d                 == d.id
      decompose d             == [ideal d, 1]
      d1 = d2                 == basis(ideal d1) = basis(ideal d2)
      n * d                   == divisor(ideal(d) ** n)
      d1 + d2                 == divisor(ideal d1 * ideal d2)
      - d                     == divisor inv ideal d
      divisor(h, d, dp, g, r) == makeDivisor(d, lift h - (r * dp)::RF::UPUP, g)

      intReduce(h, b) ==
```

```
        v := integralCoordinates(h).num
        integralRepresents(
                     [qelt(v, i) rem b for i in minIndex v .. maxIndex v], 1)

      divisor(a, b) ==
        x := monomial(1, 1)$UP
        not ground? gcd(d := x - a::UP, retract(discriminant())@UP) =>
                                          error "divisor: point is singular"
        makeDivisor(d, monomial(1, 1)$UPUP - b::UP::RF::UPUP, 1)

      divisor(a, b, n) ==
        not(ground? gcd(d := monomial(1, 1)$UP - a::UP,
            retract(discriminant())@UP)) and
                  ((n exquo rank()) case "failed") =>
                                   error "divisor: point is singular"
        m:N :=
          n < 0 => (-n)::N
          n::N
        g := makeDivisor(d**m,(monomial(1,1)$UPUP - b::UP::RF::UPUP)**m,1)
        n < 0 => -g
        g

      reduce d ==
        (i := minimize(j := ideal d)) = j => d
        #(n := numer i) ^= 2 => divisor i
        cd := splitDenominator lift n(1 + minIndex n)
        b  := gcd(cd.den * retract(retract(n minIndex n)@RF)@UP,
                  retract(norm reduce(cd.num))@UP)
        e  := cd.den * denom i
        divisor ideal([(b / e)::R,
          reduce map((s:RF):RF+->(retract(s)@UP rem b)/e, cd.num)]$Vector(R))

      finiteBasis d ==
        if empty?(d.fbasis) then
          d.fbasis := normalizeAtInfinity
                        basis module(ideal d)$FramedModule(UP, RF, UPUP, R, ww)
        d.fbasis

      generator d ==
        bsis := finiteBasis d
        for i in minIndex bsis .. maxIndex bsis repeat
          integralAtInfinity? qelt(bsis, i) =>
            return primitivePart qelt(bsis,i)
        "failed"

      lSpaceBasis d ==
        map_!(primitivePart, reduceBasisAtInfinity finiteBasis(-d))

-- b = center, hh = integral function, g = gcd(b, discriminant)
      makeDivisor(b, hh, g) ==
```

```
        b := gcd(b, retract(norm(h := reduce hh))@UP)
        h := intReduce(h, b)
        if not ground? gcd(g, b) then h := intReduce(h ** rank(), b)
        divisor ideal [b::RF::R, h]$Vector(R)
```

— FDIV.dotabb —

```
"FDIV" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FDIV"]
"FDIVCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FDIVCAT"]
"FDIV" -> "FDIVCAT"
```

7.5 domain FF FiniteField

— FiniteField.input —

```
)set break resume
)sys rm -f FiniteField.output
)spool FiniteField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteField
--R
--R FiniteField(p: PositiveInteger,n: PositiveInteger)  is a domain constructor
--R Abbreviation for FiniteField is FF
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FF
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PrimeField(p),%) -> %          ?*? : (%,PrimeField(p)) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,PrimeField(p)) -> %          ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,Integer) -> %
```

```
--R ?^? : (%,PositiveInteger) -> %        algebraic? : % -> Boolean
--R associates? : (%,%) -> Boolean        basis : () -> Vector(%)
--R coerce : PrimeField(p) -> %           coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber      factor : % -> Factored(%)
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             inGroundField? : % -> Boolean
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R norm : % -> PrimeField(p)             one? : % -> Boolean
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R retract : % -> PrimeField(p)          sample : () -> %
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               trace : % -> PrimeField(p)
--R transcendent? : % -> Boolean          unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R D : % -> % if PrimeField(p) has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R Frobenius : % -> % if PrimeField(p) has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R charthRoot : % -> % if PrimeField(p) has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if PrimeField(p) has FINITE
--R coordinates : Vector(%) -> Matrix(PrimeField(p))
--R coordinates : % -> Vector(PrimeField(p))
--R createNormalElement : () -> % if PrimeField(p) has FINITE
--R createPrimitiveElement : () -> % if PrimeField(p) has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(PrimeField(p))
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R differentiate : % -> % if PrimeField(p) has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if PrimeField(p) has CHARNZ or PrimeField(p) h
--R discreteLog : % -> NonNegativeInteger if PrimeField(p) has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if PrimeField(p) has FI
```

```
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R generator : () -> % if PrimeField(p) has FINITE
--R index : PositiveInteger -> % if PrimeField(p) has FINITE
--R init : () -> % if PrimeField(p) has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(PrimeField(p))) -> % if PrimeField(p) ha
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(PrimeField(p)),"failed") if
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(PrimeField(p)) if PrimeField(p) has FI
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(PrimeField(p)) if PrimeField(p) has
--R lookup : % -> PositiveInteger if PrimeField(p) has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if PrimeField(p) ha
--R minimalPolynomial : % -> SparseUnivariatePolynomial(PrimeField(p))
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if PrimeField(p) has FINITE
--R norm : (%,PositiveInteger) -> % if PrimeField(p) has FINITE
--R normal? : % -> Boolean if PrimeField(p) has FINITE
--R normalElement : () -> % if PrimeField(p) has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if PrimeField(p) has CHARNZ or PrimeField(p
--R order : % -> PositiveInteger if PrimeField(p) has FINITE
--R primeFrobenius : % -> % if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if PrimeField(p) has CHARNZ or PrimeField(p) ha
--R primitive? : % -> Boolean if PrimeField(p) has FINITE
--R primitiveElement : () -> % if PrimeField(p) has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if PrimeField(p) has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if PrimeField(p) has FINI
--R represents : Vector(PrimeField(p)) -> %
--R retractIfCan : % -> Union(PrimeField(p),"failed")
--R size : () -> NonNegativeInteger if PrimeField(p) has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if PrimeFie
--R trace : (%,PositiveInteger) -> % if PrimeField(p) has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— FiniteField.help —

```
=====================================================================
FiniteField examples
=====================================================================

See Also:
o )show FiniteField
```

———-

7.5.1 FiniteField (FF)



See

⇒ “FiniteFieldExtensionByPolynomial” (FFP) 7.10.1 on page 820
⇒ “FiniteFieldExtension” (FFX) 7.9.1 on page 815
⇒ “InnerFiniteField” (IFF) 10.21.1 on page 1251

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
hash	index	inGroundField?
init	inv	latex
lcm	linearAssociatedExp	linearAssociatedLog
linearAssociatedOrder	lookup	minimalPolynomial
multiEuclidean	nextItem	norm
normal?	normalElement	one?
order	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	recip	representationType
represents	retract	retractIfCan
sample	size	sizeLess?
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain FF FiniteField —

```
)abbrev domain FF FiniteField
++ Author: Mark Botch
++ Date Created: ???
++ Date Last Updated: 29 May 1990
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: field, extension field, algebraic extension,
++  finite extension, finite field, Galois field
++ Reference:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics an
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
```

```
++  AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteField(p,n) implements finite fields with p**n elements.
++ This packages checks that p is prime.
++ For a non-checking version, see \spadtype{InnerFiniteField}.

FiniteField(p:PositiveInteger, n:PositiveInteger): _
   FiniteAlgebraicExtensionField(PrimeField p) ==_
   FiniteFieldExtensionByPolynomial(PrimeField p,_
       createIrreduciblePoly(n)$FiniteFieldPolynomialPackage(PrimeField p))
  -- old code for generating irreducible polynomials:
  -- now "better" order (sparse polys first)
  -- generateIrredPoly(n)$IrredPolyOverFiniteField(GF))
```

———-

— **FF.dotabb** —

```
"FF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FF"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"FF" -> "FAXF"
```

———-

7.6 domain FFCG FiniteFieldCyclicGroup

— **FiniteFieldCyclicGroup.input** —

```
)set break resume
)sys rm -f FiniteFieldCyclicGroup.output
)spool FiniteFieldCyclicGroup.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldCyclicGroup
--R
--R FiniteFieldCyclicGroup(p: PositiveInteger,extdeg: PositiveInteger)  is a domain constructor
--R Abbreviation for FiniteFieldCyclicGroup is FFCG
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFCG
--R
--R------------------------------ Operations --------------------------------
```

```
--R ?*? : (PrimeField(p),%) -> %          ?*? : (%,PrimeField(p)) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,PrimeField(p)) -> %          ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,Integer) -> %
--R ?^? : (%,PositiveInteger) -> %        algebraic? : % -> Boolean
--R associates? : (%,%) -> Boolean        basis : () -> Vector(%)
--R coerce : PrimeField(p) -> %           coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber      factor : % -> Factored(%)
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             inGroundField? : % -> Boolean
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R norm : % -> PrimeField(p)             one? : % -> Boolean
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R retract : % -> PrimeField(p)          sample : () -> %
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               trace : % -> PrimeField(p)
--R transcendent? : % -> Boolean          unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R D : % -> % if PrimeField(p) has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R Frobenius : % -> % if PrimeField(p) has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R charthRoot : % -> % if PrimeField(p) has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if PrimeField(p) has FINITE
--R coordinates : Vector(%) -> Matrix(PrimeField(p))
--R coordinates : % -> Vector(PrimeField(p))
--R createNormalElement : () -> % if PrimeField(p) has FINITE
--R createPrimitiveElement : () -> % if PrimeField(p) has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(PrimeField(p))
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R differentiate : % -> % if PrimeField(p) has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if PrimeField(p) has CHARNZ or Pri
--R discreteLog : % -> NonNegativeInteger if PrimeField(p) has FINITE
```

```
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if PrimeField(p) has FI
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if PrimeField(p) has FINITE
--R getZechTable : () -> PrimitiveArray(SingleInteger)
--R index : PositiveInteger -> % if PrimeField(p) has FINITE
--R init : () -> % if PrimeField(p) has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(PrimeField(p))) -> % if PrimeField(p) has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(PrimeField(p)),"failed") if PrimeField(p
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(PrimeField(p)) if PrimeField(p) has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(PrimeField(p)) if PrimeField(p) has FINITE
--R lookup : % -> PositiveInteger if PrimeField(p) has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if PrimeField(p) has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(PrimeField(p))
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if PrimeField(p) has FINITE
--R norm : (%,PositiveInteger) -> % if PrimeField(p) has FINITE
--R normal? : % -> Boolean if PrimeField(p) has FINITE
--R normalElement : () -> % if PrimeField(p) has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R order : % -> PositiveInteger if PrimeField(p) has FINITE
--R primeFrobenius : % -> % if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R primitive? : % -> Boolean if PrimeField(p) has FINITE
--R primitiveElement : () -> % if PrimeField(p) has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if PrimeField(p) has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if PrimeField(p) has FINITE
--R represents : Vector(PrimeField(p)) -> %
--R retractIfCan : % -> Union(PrimeField(p),"failed")
--R size : () -> NonNegativeInteger if PrimeField(p) has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if PrimeField(p) has FI
--R trace : (%,PositiveInteger) -> % if PrimeField(p) has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```


— **FiniteFieldCyclicGroup.help** —

```
==========================================================================
FiniteFieldCyclicGroup examples
==========================================================================

See Also:
o )show FiniteFieldCyclicGroup
```

———-

7.6.1 FiniteFieldCyclicGroup (FFCG)



See

⇒ “FiniteFieldCyclicGroupExtensionByPolynomial” (FFCGP) 7.8.1 on page 804
⇒ “FiniteFieldCyclicGroupExtension” (FFCGX) 7.7.1 on page 799

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
getZechTable	hash	index
inGroundField?	init	inv
latex	lcm	linearAssociatedExp
linearAssociatedLog	linearAssociatedOrder	lookup
minimalPolynomial	multiEuclidean	nextItem
norm	normal?	normalElement
one?	order	prime?
primeFrobenius	primitive?	primitiveElement
principalIdeal	random	recip
representationType	represents	retract
retractIfCan	sample	size
sizeLess?	squareFree	squareFreePart
subtractIfCan	tableForDiscreteLogarithm	trace
transcendenceDegree	transcendent?	unit?
unitCanonical	unitNormal	zero?
?*?	?**?	?+?
?-?	-?	?/?
?=?	?^?	?~=?
?quo?	?rem?	

— domain FFCG FiniteFieldCyclicGroup —

```
)abbrev domain FFCG FiniteFieldCyclicGroup
++ Authors: J.Grabmeier, A.Scheerhorn
++ Date Created: 04.04.1991
++ Date Last Updated:
++ Basic Operations:
++ Related Constructors:  FiniteFieldCyclicGroupExtensionByPolynomial,
++  FiniteFieldPolynomialPackage
++ Also See: FiniteField, FiniteFieldNormalBasis
++ AMS Classifications:
++ Keywords: finite field, primitive elements, cyclic group
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encycoldia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++ Description:
```

```
++ FiniteFieldCyclicGroup(p,n) implements a finite field extension of degee n
++ over the prime field with p elements. Its elements are represented by
++ powers of a primitive element, i.e. a generator of the multiplicative
++ (cyclic) group. As primitive element we choose the root of the extension
++ polynomial, which is created by createPrimitivePoly from
++ \spadtype{FiniteFieldPolynomialPackage}. The Zech logarithms are stored
++ in a table of size half of the field size, and use \spadtype{SingleInteger}
++ for representing field elements, hence, there are restrictions
++ on the size of the field.

FiniteFieldCyclicGroup(p,extdeg):_
  Exports == Implementation where
  p : PositiveInteger
  extdeg   : PositiveInteger
  PI       ==> PositiveInteger
  FFPOLY         ==> FiniteFieldPolynomialPackage(PrimeField(p))
  SI       ==> SingleInteger
  Exports  ==> FiniteAlgebraicExtensionField(PrimeField(p)) with
    getZechTable:() -> PrimitiveArray(SingleInteger)
      ++ getZechTable() returns the zech logarithm table of the field.
      ++ This table is used to perform additions in the field quickly.
  Implementation ==> FiniteFieldCyclicGroupExtensionByPolynomial(PrimeField(p),_
                          createPrimitivePoly(extdeg)$FFPOLY)
```

———-

— FFCG.dotabb —

```
"FFCG" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFCG"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"FFCG" -> "FAXF"
```

———-

7.7 domain FFCGX FiniteFieldCyclicGroupExtension

— FiniteFieldCyclicGroupExtension.input —

```
)set break resume
)sys rm -f FiniteFieldCyclicGroupExtension.output
)spool FiniteFieldCyclicGroupExtension.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show FiniteFieldCyclicGroupExtension
--R
--R FiniteFieldCyclicGroupExtension(GF: FiniteFieldCategory,extdeg: PositiveInteger)  is a domain constructo
--R Abbreviation for FiniteFieldCyclicGroupExtension is FFCGX
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFCGX
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (GF,%) -> %                    ?*? : (%,GF) -> %
--R ?*? : (Fraction(Integer),%) -> %     ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %      ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                     -? : % -> %
--R ?/? : (%,GF) -> %                    ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean               D : % -> % if GF has FINITE
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,Integer) -> %               ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean            associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)              coerce : GF -> %
--R coerce : Fraction(Integer) -> %      coerce : % -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R coordinates : % -> Vector(GF)        degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber     factor : % -> Factored(%)
--R gcd : List(%) -> %                   gcd : (%,%) -> %
--R hash : % -> SingleInteger            inGroundField? : % -> Boolean
--R inv : % -> %                         latex : % -> String
--R lcm : List(%) -> %                   lcm : (%,%) -> %
--R norm : % -> GF                       one? : % -> Boolean
--R prime? : % -> Boolean                ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")       ?rem? : (%,%) -> %
--R represents : Vector(GF) -> %         retract : % -> GF
--R sample : () -> %                     sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)        squareFreePart : % -> %
--R trace : % -> GF                      transcendent? : % -> Boolean
--R unit? : % -> Boolean                 unitCanonical : % -> %
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : % -> % if GF has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if GF has CHARNZ or GF has FINITE
--R charthRoot : % -> % if GF has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if GF has FINITE
```

```
--R coordinates : Vector(%) -> Matrix(GF)
--R createNormalElement : () -> % if GF has FINITE
--R createPrimitiveElement : () -> % if GF has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(GF)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if GF has FINITE
--R differentiate : % -> % if GF has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if GF has CHARNZ or GF has FINITE
--R discreteLog : % -> NonNegativeInteger if GF has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if GF has F
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R generator : () -> % if GF has FINITE
--R getZechTable : () -> PrimitiveArray(SingleInteger)
--R index : PositiveInteger -> % if GF has FINITE
--R init : () -> % if GF has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(GF)) -> % if GF has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(GF),"failed") if GF has FINI
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R lookup : % -> PositiveInteger if GF has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if GF has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(GF)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if GF has FINITE
--R norm : (%,PositiveInteger) -> % if GF has FINITE
--R normal? : % -> Boolean if GF has FINITE
--R normalElement : () -> % if GF has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if GF has CHARNZ or GF has FINITE
--R order : % -> PositiveInteger if GF has FINITE
--R primeFrobenius : % -> % if GF has CHARNZ or GF has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if GF has CHARNZ or GF has FINITE
--R primitive? : % -> Boolean if GF has FINITE
--R primitiveElement : () -> % if GF has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if GF has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if GF has FINITE
--R retractIfCan : % -> Union(GF,"failed")
--R size : () -> NonNegativeInteger if GF has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if GF has F
--R trace : (%,PositiveInteger) -> % if GF has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
```

```
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FiniteFieldCyclicGroupExtension.help** —

```
=====================================================================
FiniteFieldCyclicGroupExtension examples
=====================================================================

See Also:
o )show FiniteFieldCyclicGroupExtension
```

———-

7.7.1 FiniteFieldCyclicGroupExtension (FFCGX)



See

⇒ “FiniteFieldCyclicGroupExtensionByPolynomial” (FFCGP) 7.8.1 on page 804
⇒ “FiniteFieldCyclicGroup” (FFCG) 7.6.1 on page 794

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
getZechTable	hash	index
inGroundField?	init	inv
latex	lcm	linearAssociatedExp
linearAssociatedLog	linearAssociatedOrder	lookup
minimalPolynomial	multiEuclidean	nextItem
norm	normal?	normalElement
one?	order	prime?
primeFrobenius	primitive?	primitiveElement
principalIdeal	random	recip
representationType	represents	retract
retractIfCan	sample	size
sizeLess?	squareFree	squareFreePart
subtractIfCan	tableForDiscreteLogarithm	trace
transcendenceDegree	transcendent?	unit?
unitCanonical	unitNormal	zero?
?*?	?**?	?+?
?-?	-?	?/?
?=?	?^?	?~=?
?quo?	?rem?	

— domain FFCGX FiniteFieldCyclicGroupExtension —

```
)abbrev domain FFCGX FiniteFieldCyclicGroupExtension
++ Authors: J.Grabmeier, A.Scheerhorn
++ Date Created: 04.04.1991
++ Date Last Updated:
++ Basic Operations:
++ Related Constructors:  FiniteFieldCyclicGroupExtensionByPolynomial,
++  FiniteFieldPolynomialPackage
++ Also See: FiniteFieldExtension, FiniteFieldNormalBasisExtension
++ AMS Classifications:
++ Keywords: finite field, primitive elements, cyclic group
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encycoldia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
```

```
++  AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldCyclicGroupExtension(GF,n)  implements a extension of degree n
++ over the ground field GF. Its elements are represented by powers of
++ a primitive element, i.e. a generator of the multiplicative (cyclic) group.
++ As primitive element we choose the root of the extension polynomial, which
++ is created by createPrimitivePoly from
++ \spadtype{FiniteFieldPolynomialPackage}. Zech logarithms are stored
++ in a table of size half of the field size, and use \spadtype{SingleInteger}
++ for representing field elements, hence, there are restrictions
++ on the size of the field.

FiniteFieldCyclicGroupExtension(GF,extdeg):_
  Exports == Implementation where
  GF       : FiniteFieldCategory
  extdeg   : PositiveInteger
  PI       ==> PositiveInteger
  FFPOLY         ==> FiniteFieldPolynomialPackage(GF)
  SI       ==> SingleInteger
  Exports  ==> FiniteAlgebraicExtensionField(GF) with
    getZechTable:() -> PrimitiveArray(SingleInteger)
      ++ getZechTable() returns the zech logarithm table of the field.
      ++ This table is used to perform additions in the field quickly.
  Implementation ==> FiniteFieldCyclicGroupExtensionByPolynomial(GF,_
                          createPrimitivePoly(extdeg)$FFPOLY)
```

———-

— FFCGX.dotabb —

```
"FFCGX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFCGX"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"FFCGX" -> "FAXF"
```

———-

7.8 domain FFCGP FiniteFieldCyclicGroupExtensionByPolynomial

— FiniteFieldCyclicGroupExtensionByPolynomial.input —

```
)set break resume
)sys rm -f FiniteFieldCyclicGroupExtensionByPolynomial.output
```

```
)spool FiniteFieldCyclicGroupExtensionByPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldCyclicGroupExtensionByPolynomial
--R
--R FiniteFieldCyclicGroupExtensionByPolynomial(GF: FiniteFieldCategory,defpol: SparseUnivariate
--R Abbreviation for FiniteFieldCyclicGroupExtensionByPolynomial is FFCGP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFCGP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (GF,%) -> %                      ?*? : (%,GF) -> %
--R ?*? : (Fraction(Integer),%) -> %       ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                       ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %         ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %        ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                       -? : % -> %
--R ?/? : (%,GF) -> %                      ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                 D : % -> % if GF has FINITE
--R 1 : () -> %                            0 : () -> %
--R ?^? : (%,Integer) -> %                 ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean              associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)                coerce : GF -> %
--R coerce : Fraction(Integer) -> %        coerce : % -> %
--R coerce : Integer -> %                  coerce : % -> OutputForm
--R coordinates : % -> Vector(GF)          degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber       factor : % -> Factored(%)
--R gcd : List(%) -> %                     gcd : (%,%) -> %
--R hash : % -> SingleInteger              inGroundField? : % -> Boolean
--R inv : % -> %                           latex : % -> String
--R lcm : List(%) -> %                     lcm : (%,%) -> %
--R norm : % -> GF                         one? : % -> Boolean
--R prime? : % -> Boolean                  ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")         ?rem? : (%,%) -> %
--R represents : Vector(GF) -> %           retract : % -> GF
--R sample : () -> %                       sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)          squareFreePart : % -> %
--R trace : % -> GF                       transcendent? : % -> Boolean
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : % -> % if GF has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
```

```
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if GF has CHARNZ or GF has FINITE
--R charthRoot : % -> % if GF has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if GF has FINITE
--R coordinates : Vector(%) -> Matrix(GF)
--R createNormalElement : () -> % if GF has FINITE
--R createPrimitiveElement : () -> % if GF has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(GF)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if GF has FINITE
--R differentiate : % -> % if GF has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if GF has CHARNZ or GF has FINITE
--R discreteLog : % -> NonNegativeInteger if GF has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if GF has FINITE
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if GF has FINITE
--R getZechTable : () -> PrimitiveArray(SingleInteger)
--R index : PositiveInteger -> % if GF has FINITE
--R init : () -> % if GF has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(GF)) -> % if GF has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(GF),"failed") if GF has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R lookup : % -> PositiveInteger if GF has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if GF has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(GF)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if GF has FINITE
--R norm : (%,PositiveInteger) -> % if GF has FINITE
--R normal? : % -> Boolean if GF has FINITE
--R normalElement : () -> % if GF has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if GF has CHARNZ or GF has FINITE
--R order : % -> PositiveInteger if GF has FINITE
--R primeFrobenius : % -> % if GF has CHARNZ or GF has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if GF has CHARNZ or GF has FINITE
--R primitive? : % -> Boolean if GF has FINITE
--R primitiveElement : () -> % if GF has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if GF has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if GF has FINITE
--R retractIfCan : % -> Union(GF,"failed")
--R size : () -> NonNegativeInteger if GF has FINITE
```

```
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if GF has F
--R trace : (%,PositiveInteger) -> % if GF has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FiniteFieldCyclicGroupExtensionByPolynomial.help** —

```
=====================================================================
FiniteFieldCyclicGroupExtensionByPolynomial examples
=====================================================================

See Also:
o )show FiniteFieldCyclicGroupExtensionByPolynomial
```

———-

7.8.1 FiniteFieldCyclicGroupExtensionByPolynomial (FFCGP)



See

⇒ “FiniteFieldCyclicGroupExtension” (FFCGX) 7.7.1 on page 799
⇒ “FiniteFieldCyclicGroup” (FFCG) 7.6.1 on page 794

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
getZechTable	hash	index
inGroundField?	init	inv
latex	lcm	linearAssociatedExp
linearAssociatedLog	linearAssociatedOrder	lookup
minimalPolynomial	multiEuclidean	nextItem
norm	normal?	normalElement
one?	order	prime?
primeFrobenius	primitive?	primitiveElement
principalIdeal	random	recip
representationType	represents	retract
retractIfCan	sample	size
sizeLess?	squareFree	squareFreePart
subtractIfCan	tableForDiscreteLogarithm	trace
transcendenceDegree	transcendent?	unit?
unitCanonical	unitNormal	zero?
?*?	?**?	?+?
?-?	-?	?/?
?=?	?^?	?~=?
?quo?	?rem?	

— domain FFCGP FiniteFieldCyclicGroupExtensionByPolynomial —

```
)abbrev domain FFCGP FiniteFieldCyclicGroupExtensionByPolynomial
++ Authors: J.Grabmeier, A.Scheerhorn
++ Date Created: 26.03.1991
++ Date Last Updated: 31 March 1991
++ Basic Operations:
++ Related Constructors: FiniteFieldFunctions
++ Also See: FiniteFieldExtensionByPolynomial,
++  FiniteFieldNormalBasisExtensionByPolynomial
++ AMS Classifications:
++ Keywords: finite field, primitive elements, cyclic group
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encycoldia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
```

```
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
++  AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldCyclicGroupExtensionByPolynomial(GF,defpol)  implements a
++ finite extension field of the ground field GF. Its elements are
++ represented by powers of a primitive element, i.e. a generator of the
++ multiplicative (cyclic) group. As primitive
++ element we choose the root of the extension polynomial defpol,
++ which MUST be primitive (user responsibility). Zech logarithms are stored
++ in a table of size half of the field size, and use \spadtype{SingleInteger}
++ for representing field elements, hence, there are restrictions
++ on the size of the field.

FiniteFieldCyclicGroupExtensionByPolynomial(GF,defpol):_
  Exports == Implementation where
  GF    : FiniteFieldCategory               -- the ground field
  defpol: SparseUnivariatePolynomial GF     -- the extension polynomial
  -- the root of defpol is used as the primitive element

  PI    ==> PositiveInteger
  NNI   ==> NonNegativeInteger
  I     ==> Integer
  SI    ==> SingleInteger
  SUP   ==> SparseUnivariatePolynomial
  SAE   ==> SimpleAlgebraicExtension(GF,SUP GF,defpol)
  V     ==> Vector GF
  FFP   ==> FiniteFieldExtensionByPolynomial(GF,defpol)
  FFF   ==> FiniteFieldFunctions(GF)
  OUT   ==> OutputForm
  ARR   ==> PrimitiveArray(SI)
  TBL   ==> Table(PI,NNI)


  Exports ==> FiniteAlgebraicExtensionField(GF)  with

    getZechTable:() -> ARR
      ++ getZechTable() returns the zech logarithm table of the field
      ++ it is used to perform additions in the field quickly.
  Implementation ==>  add

-- global variables ================================================

    Rep:= SI
    -- elements are represented by small integers in the range
    -- (-1)..(size()-2). The (-1) representing the field element zero,
    -- the other small integers representing the corresponding power
    -- of the primitive element, the root of the defining polynomial

    -- it would be very nice if we could use the representation
    -- Rep:= Union("zero", IntegerMod(size()$GF ** degree(defpol) -1)),
```

```
    -- why doesn't the compiler like this ?

    extdeg:NNI  :=degree(defpol)$(SUP GF)::NNI
    -- the extension degree

    sizeFF:NNI:=(size()$GF ** extdeg) pretend NNI
    -- the size of the field

    if sizeFF > 2**20 then
      error "field too large for this representation"

    sizeCG:SI:=(sizeFF - 1) pretend SI
    -- the order of the cyclic group

    sizeFG:SI:=(sizeCG quo (size()$GF-1)) pretend SI
    -- the order of the factor group


    zechlog:ARR:=new(((sizeFF+1) quo 2)::NNI,-1::SI)$ARR
    -- the table for the zech logarithm

    alpha :=new()$Symbol :: OutputForm
    -- get a new symbol for the output representation of
    -- the elements

    primEltGF:GF:=
      odd?(extdeg)$I => -$GF coefficient(defpol,0)$(SUP GF)
      coefficient(defpol,0)$(SUP GF)
    -- the corresponding primitive element of the groundfield
    -- equals the trace of the primitive element w.r.t. the groundfield

    facOfGroupSize := nil()$(List Record(factor:Integer,exponent:Integer))
    -- the factorization of sizeCG

    initzech?:Boolean:=true
    -- gets false after initialization of the zech logarithm array

    initelt?:Boolean:=true
    -- gets false after initialization of the normal element

    normalElt:SI:=0
    -- the global variable containing a normal element

-- functions ===============================================================

    -- for completeness we have to give a dummy implementation for
    -- 'tableForDiscreteLogarithm', although this function is not
    -- necessary in the cyclic group representation case

    tableForDiscreteLogarithm(fac) == table()$TBL
```

```
    getZechTable() == zechlog
    initializeZech:() -> Void
    initializeElt: () -> Void

    order(x:$):PI ==
      zero?(x) =>
        error"order: order of zero undefined"
      (sizeCG quo gcd(sizeCG,x pretend NNI))::PI

    primitive?(x:$) ==
--      zero?(x) or one?(x) => false
      zero?(x) or (x = 1) => false
      gcd(x::Rep,sizeCG)$Rep = 1$Rep => true
      false

    coordinates(x:$) ==
      x=0 => new(extdeg,0)$(Vector GF)
      primElement:SAE:=convert(monomial(1,1)$(SUP GF))$SAE
-- the primitive element in the corresponding algebraic extension
      coordinates(primElement **$SAE (x pretend SI))$SAE

    x:$ + y:$ ==
      if initzech? then initializeZech()
      zero? x => y
      zero? y => x
      d:Rep:=positiveRemainder(y -$Rep x,sizeCG)$Rep
      (d pretend SI) <= shift(sizeCG,-$SI (1$SI)) =>
        zechlog.(d pretend SI) =$SI -1::SI => 0
        addmod(x,zechlog.(d pretend SI) pretend Rep,sizeCG)$Rep
      --d:Rep:=positiveRemainder(x -$Rep y,sizeCG)$Rep
      d:Rep:=(sizeCG -$SI d)::Rep
      addmod(y,zechlog.(d pretend SI) pretend Rep,sizeCG)$Rep
      --positiveRemainder(x +$Rep zechlog.(d pretend SI) -$Rep d,sizeCG)$Rep


    initializeZech() ==
      zechlog:=createZechTable(defpol)$FFF
      -- set initialization flag
      initzech? := false
      void()$Void

    basis(n:PI) ==
      extensionDegree() rem n ^= 0 =>
        error("argument must divide extension degree")
      m:=sizeCG quo (size()$GF**n-1)
      [index((1+i*m) ::PI) for i in 0..(n-1)]::Vector $

    n:I * x:$ == ((n::GF)::$) * x
```

```
minimalPolynomial(a) ==
  f:SUP $:=monomial(1,1)$(SUP $) - monomial(a,0)$(SUP $)
  u:$:=Frobenius(a)
  while not(u = a) repeat
    f:=f * (monomial(1,1)$(SUP $) - monomial(u,0)$(SUP $))
    u:=Frobenius(u)
  p:SUP GF:=0$(SUP GF)
  while not zero?(f)$(SUP $) repeat
    g:GF:=retract(leadingCoefficient(f)$(SUP $))
    p:=p+monomial(g,_
                  degree(f)$(SUP $))$(SUP GF)
    f:=reductum(f)$(SUP $)
  p

factorsOfCyclicGroupSize() ==
  if empty? facOfGroupSize then initializeElt()
  facOfGroupSize

representationType() == "cyclic"

definingPolynomial() == defpol

random() ==
  positiveRemainder(random()$Rep,sizeFF pretend Rep)$Rep -$Rep 1$Rep

represents(v) ==
  u:FFP:=represents(v)$FFP
  u =$FFP 0$FFP => 0
  discreteLog(u)$FFP pretend Rep



coerce(e:GF):$ ==
  zero?(e)$GF => 0
  log:I:=discreteLog(primEltGF,e)$GF::NNI *$I sizeFG
  -- version before 10.20.92: log pretend Rep
  -- 1$GF is coerced to sizeCG pretend Rep by old version
  -- now 1$GF is coerced to 0$Rep which is correct.
  positiveRemainder(log,sizeCG) pretend Rep


retractIfCan(x:$) ==
  zero? x => 0$GF
  u:= (x::Rep) exquo$Rep (sizeFG pretend Rep)
  u = "failed" => "failed"
  primEltGF **$GF ((u::$) pretend SI)

retract(x:$) ==
  a:=retractIfCan(x)
```

```
    a="failed" => error "element not in groundfield"
    a :: GF

  basis() == [index(i :: PI) for i in 1..extdeg]::Vector $


  inGroundField?(x) ==
    zero? x=> true
    positiveRemainder(x::Rep,sizeFG pretend Rep)$Rep =$Rep 0$Rep => true
    false

  discreteLog(b:$,x:$) ==
    zero? x => "failed"
    e:= extendedEuclidean(b,sizeCG,x)$Rep
    e = "failed" => "failed"
    e1:Record(coef1:$,coef2:$) := e :: Record(coef1:$,coef2:$)
    positiveRemainder(e1.coef1,sizeCG)$Rep pretend NNI

  - x:$ ==
      zero? x => 0
      characteristic() =$I 2 => x
      addmod(x,shift(sizeCG,-1)$SI pretend Rep,sizeCG)

  generator() == 1$SI
  createPrimitiveElement() == 1$SI
  primitiveElement() == 1$SI

  discreteLog(x:$) ==
    zero? x => error "discrete logarithm error"
    x pretend NNI

  normalElement() ==
    if initelt? then initializeElt()
    normalElt::$

  initializeElt() ==
    facOfGroupSize := factors(factor(sizeCG)$Integer)
    normalElt:=createNormalElement() pretend SI
    initelt?:=false
    void()$Void

  extensionDegree() == extdeg pretend PI

  characteristic() == characteristic()$GF

  lookup(x:$) ==
    x =$Rep (-$Rep 1$Rep) => sizeFF pretend PI
    (x +$Rep 1$Rep) pretend PI

  index(a:PI) ==
```

```
      positiveRemainder(a,sizeFF)$I pretend Rep -$Rep 1$Rep

    0 == (-$Rep 1$Rep)

    1 == 0$Rep

-- to get a "exponent like" output form
    coerce(x:$):OUT ==
      x =$Rep (-$Rep 1$Rep) => "0"::OUT
      x =$Rep 0$Rep => "1"::OUT
      y:I:=lookup(x)-1
      alpha **$OUT (y::OUT)

    x:$ = y:$ ==  x =$Rep y

    x:$ * y:$ ==
      x = 0 => 0
      y = 0 => 0
      addmod(x,y,sizeCG)$Rep

    a:GF * x:$ == coerce(a)@$ * x
    x:$/a:GF == x/coerce(a)@$

--    x:$ / a:GF ==
--      a = 0$GF => error "division by zero"
--      x * inv(coerce(a))

    inv(x:$)  ==
      zero?(x) => error "inv: not invertible"
--      one?(x) => 1
      (x = 1) => 1
      sizeCG -$Rep x

    x:$ ** n:PI == x ** n::I

    x:$ ** n:NNI == x ** n::I

    x:$ ** n:I ==
      m:Rep:=positiveRemainder(n,sizeCG)$I pretend Rep
      m =$Rep 0$Rep => 1
      x = 0 => 0
      mulmod(m,x,sizeCG::Rep)$Rep
```

———-

— FFCGP.dotabb —

```
"FFCGP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFCGP"]
```

```
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FFCGP" -> "ALIST"
```

———-

7.9 domain FFX FiniteFieldExtension

— FiniteFieldExtension.input —

```
)set break resume
)sys rm -f FiniteFieldExtension.output
)spool FiniteFieldExtension.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldExtension
--R
--R FiniteFieldExtension(GF: FiniteFieldCategory,n: PositiveInteger)  is a domain constructor
--R Abbreviation for FiniteFieldExtension is FFX
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFX
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (GF,%) -> %                    ?*? : (%,GF) -> %
--R ?*? : (Fraction(Integer),%) -> %     ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %      ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                     -? : % -> %
--R ?/? : (%,GF) -> %                    ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean               D : % -> % if GF has FINITE
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,Integer) -> %               ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean            associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)              coerce : GF -> %
--R coerce : Fraction(Integer) -> %      coerce : % -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R coordinates : % -> Vector(GF)        degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber     factor : % -> Factored(%)
--R gcd : List(%) -> %                   gcd : (%,%) -> %
--R hash : % -> SingleInteger            inGroundField? : % -> Boolean
--R inv : % -> %                         latex : % -> String
--R lcm : List(%) -> %                   lcm : (%,%) -> %
--R norm : % -> GF                       one? : % -> Boolean
```

```
--R prime? : % -> Boolean                ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")       ?rem? : (%,%) -> %
--R represents : Vector(GF) -> %         retract : % -> GF
--R sample : () -> %                     sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)        squareFreePart : % -> %
--R trace : % -> GF                      transcendent? : % -> Boolean
--R unit? : % -> Boolean                 unitCanonical : % -> %
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : % -> % if GF has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if GF has CHARNZ or GF has FINITE
--R charthRoot : % -> % if GF has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if GF has FINITE
--R coordinates : Vector(%) -> Matrix(GF)
--R createNormalElement : () -> % if GF has FINITE
--R createPrimitiveElement : () -> % if GF has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(GF)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if GF has FINITE
--R differentiate : % -> % if GF has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if GF has CHARNZ or GF has FINITE
--R discreteLog : % -> NonNegativeInteger if GF has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if GF has FINITE
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if GF has FINITE
--R index : PositiveInteger -> % if GF has FINITE
--R init : () -> % if GF has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(GF)) -> % if GF has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(GF),"failed") if GF has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R lookup : % -> PositiveInteger if GF has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if GF has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(GF)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if GF has FINITE
```

```
--R norm : (%,PositiveInteger) -> % if GF has FINITE
--R normal? : % -> Boolean if GF has FINITE
--R normalElement : () -> % if GF has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if GF has CHARNZ or GF has FINITE
--R order : % -> PositiveInteger if GF has FINITE
--R primeFrobenius : % -> % if GF has CHARNZ or GF has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if GF has CHARNZ or GF has FINITE
--R primitive? : % -> Boolean if GF has FINITE
--R primitiveElement : () -> % if GF has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if GF has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if GF has FINITE
--R retractIfCan : % -> Union(GF,"failed")
--R size : () -> NonNegativeInteger if GF has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if GF has F
--R trace : (%,PositiveInteger) -> % if GF has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— FiniteFieldExtension.help —

```
=====================================================================
FiniteFieldExtension examples
=====================================================================

See Also:
o )show FiniteFieldExtension
```

———-

7.9.1 FiniteFieldExtension (FFX)



See

⇒ “FiniteFieldExtensionByPolynomial” (FFP) 7.10.1 on page 820
⇒ “InnerFiniteField” (IFF) 10.21.1 on page 1251
⇒ “FiniteField” (FF) 7.5.1 on page 789

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
hash	index	inGroundField?
init	inv	latex
lcm	linearAssociatedExp	linearAssociatedLog
linearAssociatedOrder	lookup	minimalPolynomial
multiEuclidean	nextItem	norm
normal?	normalElement	one?
order	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	recip	representationType
represents	retract	retractIfCan
sample	size	sizeLess?
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain FFX FiniteFieldExtension —

```
)abbrev domain FFX FiniteFieldExtension
++ Authors: R.Sutor, J. Grabmeier, A. Scheerhorn
++ Date Created:
++ Date Last Updated: 31 March 1991
++ Basic Operations:
++ Related Constructors: FiniteFieldExtensionByPolynomial,
++  FiniteFieldPolynomialPackage
++ Also See: FiniteFieldCyclicGroupExtension,
++  FiniteFieldNormalBasisExtension
++ AMS Classifications:
++ Keywords: field, extension field, algebraic extension,
++   finite extension, finite field, Galois field
++ Reference:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics an
```

```
++   Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
++   AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldExtensionByPolynomial(GF, n) implements an extension
++ of the finite field GF of degree n generated by the extension
++ polynomial constructed by createIrreduciblePoly from
++ \spadtype{FiniteFieldPolynomialPackage}.

FiniteFieldExtension(GF, n): Exports == Implementation where
  GF: FiniteFieldCategory
  n : PositiveInteger
  Exports ==> FiniteAlgebraicExtensionField(GF)
  -- MonogenicAlgebra(GF, SUP) with  -- have to check this
  Implementation ==> FiniteFieldExtensionByPolynomial(GF,
       createIrreduciblePoly(n)$FiniteFieldPolynomialPackage(GF))
  -- old code for generating irreducible polynomials:
  -- now "better" order (sparse polys first)
  -- generateIrredPoly(n)$IrredPolyOverFiniteField(GF))
```

———-

— **FFX.dotabb** —

```
"FFX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFX"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"FFX" -> "FAXF"
```

———-

7.10 domain FFP FiniteFieldExtensionByPolynomial

— **FiniteFieldExtensionByPolynomial.input** —

```
)set break resume
)sys rm -f FiniteFieldExtensionByPolynomial.output
)spool FiniteFieldExtensionByPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldExtensionByPolynomial
--R
```

```
--R FiniteFieldExtensionByPolynomial(GF: FiniteFieldCategory,defpol: SparseUnivariatePolynomial(
--R Abbreviation for FiniteFieldExtensionByPolynomial is FFP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (GF,%) -> %                    ?*? : (%,GF) -> %
--R ?*? : (Fraction(Integer),%) -> %     ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %      ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                     -? : % -> %
--R ?/? : (%,GF) -> %                    ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean               D : % -> % if GF has FINITE
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,Integer) -> %               ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean            associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)              coerce : GF -> %
--R coerce : Fraction(Integer) -> %      coerce : % -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R coordinates : % -> Vector(GF)        degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber     factor : % -> Factored(%)
--R gcd : List(%) -> %                   gcd : (%,%) -> %
--R hash : % -> SingleInteger            inGroundField? : % -> Boolean
--R inv : % -> %                         latex : % -> String
--R lcm : List(%) -> %                   lcm : (%,%) -> %
--R norm : % -> GF                       one? : % -> Boolean
--R prime? : % -> Boolean                ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")       ?rem? : (%,%) -> %
--R represents : Vector(GF) -> %         retract : % -> GF
--R sample : () -> %                     sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)        squareFreePart : % -> %
--R trace : % -> GF                      transcendent? : % -> Boolean
--R unit? : % -> Boolean                 unitCanonical : % -> %
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : % -> % if GF has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if GF has CHARNZ or GF has FINITE
--R charthRoot : % -> % if GF has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if GF has FINITE
--R coordinates : Vector(%) -> Matrix(GF)
--R createNormalElement : () -> % if GF has FINITE
--R createPrimitiveElement : () -> % if GF has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(GF)
```

```
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if GF has FINITE
--R differentiate : % -> % if GF has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if GF has CHARNZ or GF has FINITE
--R discreteLog : % -> NonNegativeInteger if GF has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if GF has FINITE
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if GF has FINITE
--R index : PositiveInteger -> % if GF has FINITE
--R init : () -> % if GF has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(GF)) -> % if GF has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(GF),"failed") if GF has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R lookup : % -> PositiveInteger if GF has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if GF has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(GF)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if GF has FINITE
--R norm : (%,PositiveInteger) -> % if GF has FINITE
--R normal? : % -> Boolean if GF has FINITE
--R normalElement : () -> % if GF has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if GF has CHARNZ or GF has FINITE
--R order : % -> PositiveInteger if GF has FINITE
--R primeFrobenius : % -> % if GF has CHARNZ or GF has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if GF has CHARNZ or GF has FINITE
--R primitive? : % -> Boolean if GF has FINITE
--R primitiveElement : () -> % if GF has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if GF has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if GF has FINITE
--R retractIfCan : % -> Union(GF,"failed")
--R size : () -> NonNegativeInteger if GF has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if GF has FINITE
--R trace : (%,PositiveInteger) -> % if GF has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
```

```
)lisp (bye)
```

———-


— **FiniteFieldExtensionByPolynomial.help** —

```
==========================================================================
FiniteFieldExtensionByPolynomial examples
==========================================================================

See Also:
o )show FiniteFieldExtensionByPolynomial
```

———-

7.10.1 FiniteFieldExtensionByPolynomial (FFP)



See

⇒ “FiniteFieldExtension” (FFX) 7.9.1 on page 815
⇒ “InnerFiniteField” (IFF) 10.21.1 on page 1251
⇒ “FiniteField” (FF) 7.5.1 on page 789

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
hash	index	inGroundField?
init	inv	latex
lcm	linearAssociatedExp	linearAssociatedLog
linearAssociatedOrder	lookup	minimalPolynomial
multiEuclidean	nextItem	norm
normal?	normalElement	one?
order	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	recip	representationType
represents	retract	retractIfCan
sample	size	sizeLess?
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?/?
?=?	?^?	?~=?
?quo?	?rem?	

— domain FFP FiniteFieldExtensionByPolynomial —

```
)abbrev domain FFP FiniteFieldExtensionByPolynomial
++ Authors: R.Sutor, J. Grabmeier, O. Gschnitzer, A. Scheerhorn
++ Date Created:
++ Date Last Updated: 31 March 1991
++ Basic Operations:
++ Related Constructors:
++ Also See: FiniteFieldCyclicGroupExtensionByPolynomial,
++  FiniteFieldNormalBasisExtensionByPolynomial
++ AMS Classifications:
++ Keywords: field, extension field, algebraic extension,
++   finite extension, finite field, Galois field
++ Reference:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics an
++   Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
```

```
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
++   AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldExtensionByPolynomial(GF, defpol) implements the extension
++ of the finite field GF generated by the extension polynomial
++ defpol which MUST be irreducible.
++ Note: the user has the responsibility to ensure that
++ defpol is irreducible.

FiniteFieldExtensionByPolynomial(GF:FiniteFieldCategory,_
  defpol:SparseUnivariatePolynomial GF): Exports == Implementation where
--  GF     : FiniteFieldCategory
--  defpol : SparseUnivariatePolynomial GF

  PI   ==> PositiveInteger
  NNI  ==> NonNegativeInteger
  SUP  ==> SparseUnivariatePolynomial
  I    ==> Integer
  R    ==> Record(key:PI,entry:NNI)
  TBL  ==> Table(PI,NNI)
  SAE  ==> SimpleAlgebraicExtension(GF,SUP GF,defpol)
  OUT  ==> OutputForm

  Exports ==> FiniteAlgebraicExtensionField(GF)

  Implementation ==>  add

-- global variables ======================================================

    Rep:=SAE

    extdeg:PI        := degree(defpol)$(SUP GF) pretend PI
    -- the extension degree

    alpha            := new()$Symbol :: OutputForm
    -- a new symbol for the output form of field elements

    sizeCG:Integer := size()$GF**extdeg - 1
    -- the order of the multiplicative group

    facOfGroupSize := nil()$(List Record(factor:Integer,exponent:Integer))
    -- the factorization of sizeCG

    normalElt:PI:=1
    -- for the lookup of the normal Element computed by
    -- createNormalElement

    primitiveElt:PI:=1
    -- for the lookup of the primitive Element computed by
    -- createPrimitiveElement()
```

```
    initlog?:Boolean:=true
    -- gets false after initialization of the discrete logarithm table

    initelt?:Boolean:=true
    -- gets false after initialization of the primitive and the
    -- normal element


    discLogTable:Table(PI,TBL):=table()$Table(PI,TBL)
    -- tables indexed by the factors of sizeCG,
    -- discLogTable(factor) is a table  with keys
    -- primitiveElement() ** (i * (sizeCG quo factor)) and entries i for
    -- i in 0..n-1, n computed in initialize() in order to use
    -- the minimal size limit 'limit' optimal.

-- functions ===============================================================

--    createNormalElement() ==
--      a:=primitiveElement()
--      nElt:=generator()
--      for i in 1.. repeat
--        normal? nElt => return nElt
--        nElt:=nElt*a
--      nElt

    generator() == reduce(monomial(1,1)$SUP(GF))$Rep
    norm x   == resultant(defpol, lift x)

    initializeElt: () -> Void
    initializeLog: () -> Void
    basis(n:PI) ==
      (extdeg rem n) ^= 0 => error "argument must divide extension degree"
      a:$:=norm(primitiveElement(),n)
      vector [a**i for i in 0..n-1]

    degree(x) ==
      y:$:=1
      m:=zero(extdeg,extdeg+1)$(Matrix GF)
      for i in 1..extdeg+1 repeat
        setColumn_!(m,i,coordinates(y))$(Matrix GF)
        y:=y*x
      rank(m)::PI

    minimalPolynomial(x:$) ==
      y:$:=1
      m:=zero(extdeg,extdeg+1)$(Matrix GF)
      for i in 1..extdeg+1 repeat
        setColumn_!(m,i,coordinates(y))$(Matrix GF)
        y:=y*x
```

```
      v:=first nullSpace(m)$(Matrix GF)
      +/[monomial(v.(i+1),i)$(SUP GF) for i in 0..extdeg]


    normal?(x) ==
      l:List List GF:=[entries coordinates x]
      a:=x
      for i in 2..extdeg repeat
        a:=Frobenius(a)
        l:=concat(l,entries coordinates a)$(List List GF)
      ((rank matrix(l)$(Matrix GF)) = extdeg::NNI) => true
      false


    a:GF * x:$ == a *$Rep x
    n:I * x:$ == n *$Rep x
    -x == -$Rep x
    random() == random()$Rep
    coordinates(x:$) == coordinates(x)$Rep
    represents(v) == represents(v)$Rep
    coerce(x:GF):$ == coerce(x)$Rep
    definingPolynomial() == defpol
    retract(x) == retract(x)$Rep
    retractIfCan(x) == retractIfCan(x)$Rep
    index(x) == index(x)$Rep
    lookup(x) == lookup(x)$Rep
    x:$/y:$ == x /$Rep y
    x:$/a:GF == x/coerce(a)
--    x:$ / a:GF ==
--      a = 0$GF => error "division by zero"
--      x * inv(coerce(a))
    x:$ * y:$ == x *$Rep y
    x:$ + y:$ == x +$Rep y
    x:$ - y:$ == x -$Rep y
    x:$ = y:$ == x =$Rep y
    basis() == basis()$Rep
    0 == 0$Rep
    1 == 1$Rep

    factorsOfCyclicGroupSize() ==
      if empty? facOfGroupSize then initializeElt()
      facOfGroupSize

    representationType() == "polynomial"

    tableForDiscreteLogarithm(fac) ==
      if initlog? then initializeLog()
      tbl:=search(fac::PI,discLogTable)$Table(PI,TBL)
      tbl case "failed" =>
        error "tableForDiscreteLogarithm: argument must be prime divisor_
```

```
 of the order of the multiplicative group"
      tbl pretend TBL

    primitiveElement() ==
      if initelt? then initializeElt()
      index(primitiveElt)

    normalElement() ==
      if initelt? then initializeElt()
      index(normalElt)

    initializeElt() ==
      facOfGroupSize:=factors(factor(sizeCG)$Integer)
      -- get a primitive element
      pE:=createPrimitiveElement()
      primitiveElt:=lookup(pE)
      -- create a normal element
      nElt:=generator()
      while not normal? nElt repeat
        nElt:=nElt*pE
      normalElt:=lookup(nElt)
      -- set elements initialization flag
      initelt? := false
      void()$Void

    initializeLog() ==
      if initelt? then initializeElt()
-- set up tables for discrete logarithm
      limit:Integer:=30
    -- the minimum size for the discrete logarithm table
      for f in facOfGroupSize repeat
        fac:=f.factor
        base:$:=primitiveElement() ** (sizeCG quo fac)
        l:Integer:=length(fac)$Integer
        n:Integer:=0
        if odd?(l)$Integer then n:=shift(fac,-(l quo 2))
                          else n:=shift(1,(l quo 2))
        if n < limit then
          d:=(fac-1) quo limit + 1
          n:=(fac-1) quo d + 1
        tbl:TBL:=table()$TBL
        a:$:=1
        for i in (0::NNI)..(n-1)::NNI repeat
          insert_!([lookup(a),i::NNI]$R,tbl)$TBL
          a:=a*base
        insert_!([fac::PI,copy(tbl)$TBL]_
               $Record(key:PI,entry:TBL),discLogTable)$Table(PI,TBL)
      -- set logarithm initialization flag
      initlog? := false
      -- tell user about initialization
```

```
      --print("discrete logarithm tables initialized"::OUT)
      void()$Void

    coerce(e:$):OutputForm == outputForm(lift(e),alpha)

    extensionDegree() == extdeg

    size() == (sizeCG + 1) pretend NNI

--  sizeOfGroundField() == size()$GF

    inGroundField?(x) ==
      retractIfCan(x) = "failed" => false
      true

    characteristic() == characteristic()$GF
```

———-

— **FFP.dotabb** —

```
"FFP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFP"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FFP" -> "ALIST"
```

———-

7.11 domain FFNB FiniteFieldNormalBasis

— **FiniteFieldNormalBasis.input** —

```
)set break resume
)sys rm -f FiniteFieldNormalBasis.output
)spool FiniteFieldNormalBasis.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldNormalBasis
--R
--R FiniteFieldNormalBasis(p: PositiveInteger,extdeg: PositiveInteger)  is a domain constructor
--R Abbreviation for FiniteFieldNormalBasis is FFNB
--R This constructor is exposed in this frame.
```

```
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFNB
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PrimeField(p),%) -> %          ?*? : (%,PrimeField(p)) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,PrimeField(p)) -> %          ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,Integer) -> %
--R ?^? : (%,PositiveInteger) -> %        algebraic? : % -> Boolean
--R associates? : (%,%) -> Boolean        basis : () -> Vector(%)
--R coerce : PrimeField(p) -> %           coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber      factor : % -> Factored(%)
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             inGroundField? : % -> Boolean
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R norm : % -> PrimeField(p)             one? : % -> Boolean
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R retract : % -> PrimeField(p)          sample : () -> %
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               trace : % -> PrimeField(p)
--R transcendent? : % -> Boolean          unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R D : % -> % if PrimeField(p) has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
--R Frobenius : % -> % if PrimeField(p) has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R charthRoot : % -> % if PrimeField(p) has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if PrimeField(p) has FINITE
--R coordinates : Vector(%) -> Matrix(PrimeField(p))
--R coordinates : % -> Vector(PrimeField(p))
--R createNormalElement : () -> % if PrimeField(p) has FINITE
--R createPrimitiveElement : () -> % if PrimeField(p) has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(PrimeField(p))
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if PrimeField(p) has FINITE
```

```
--R differentiate : % -> % if PrimeField(p) has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if PrimeField(p) has CHARNZ or Pri
--R discreteLog : % -> NonNegativeInteger if PrimeField(p) has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if PrimeFie
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R generator : () -> % if PrimeField(p) has FINITE
--R getMultiplicationMatrix : () -> Matrix(PrimeField(p))
--R getMultiplicationTable : () -> Vector(List(Record(value: PrimeField(p),index: SingleInteger)
--R index : PositiveInteger -> % if PrimeField(p) has FINITE
--R init : () -> % if PrimeField(p) has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(PrimeField(p))) -> % if PrimeField(p) ha
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(PrimeField(p)),"failed") if
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(PrimeField(p)) if PrimeField(p) has FI
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(PrimeField(p)) if PrimeField(p) has
--R lookup : % -> PositiveInteger if PrimeField(p) has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if PrimeField(p) ha
--R minimalPolynomial : % -> SparseUnivariatePolynomial(PrimeField(p))
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if PrimeField(p) has FINITE
--R norm : (%,PositiveInteger) -> % if PrimeField(p) has FINITE
--R normal? : % -> Boolean if PrimeField(p) has FINITE
--R normalElement : () -> % if PrimeField(p) has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if PrimeField(p) has CHARNZ or PrimeField(p
--R order : % -> PositiveInteger if PrimeField(p) has FINITE
--R primeFrobenius : % -> % if PrimeField(p) has CHARNZ or PrimeField(p) has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if PrimeField(p) has CHARNZ or PrimeField(p) ha
--R primitive? : % -> Boolean if PrimeField(p) has FINITE
--R primitiveElement : () -> % if PrimeField(p) has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if PrimeField(p) has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if PrimeField(p) has FINI
--R represents : Vector(PrimeField(p)) -> %
--R retractIfCan : % -> Union(PrimeField(p),"failed")
--R size : () -> NonNegativeInteger if PrimeField(p) has FINITE
--R sizeMultiplication : () -> NonNegativeInteger
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if PrimeFie
--R trace : (%,PositiveInteger) -> % if PrimeField(p) has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **FiniteFieldNormalBasis.help** —

```
=====================================================================
FiniteFieldNormalBasis examples
=====================================================================

See Also:
o )show FiniteFieldNormalBasis
```

———-

7.11.1 FiniteFieldNormalBasis (FFNB)



See

⇒ “FiniteFieldNormalBasisExtensionByPolynomial” (FFNBP) 7.13.1 on page 841
⇒ “FiniteFieldNormalBasisExtension” (FFNBX) 7.12.1 on page 835

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
getMultiplicationMatrix	getMultiplicationTable	hash
index	inGroundField?	init
inv	latex	lcm
linearAssociatedExp	linearAssociatedLog	linearAssociatedOrder
lookup	minimalPolynomial	multiEuclidean
nextItem	norm	normal?
normalElement	one?	order
prime?	primeFrobenius	primitive?
primitiveElement	principalIdeal	random
recip	representationType	represents
retract	retractIfCan	sample
size	sizeLess?	sizeMultiplication
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain FFNB FiniteFieldNormalBasis —

```
)abbrev domain FFNB FiniteFieldNormalBasis
++ Authors: J.Grabmeier, A.Scheerhorn
++ Date Created: 26.03.1991
++ Date Last Updated:
++ Basic Operations:
++ Related Constructors: FiniteFieldNormalBasisExtensionByPolynomial,
++  FiniteFieldPolynomialPackage
++ Also See: FiniteField, FiniteFieldCyclicGroup
++ AMS Classifications:
++ Keywords: finite field, normal basis
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
```

```
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
++   AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldNormalBasis(p,n) implements a
++ finite extension field of degree n over the prime field with p elements.
++ The elements are represented by coordinate vectors with respect to
++ a normal basis,
++ i.e. a basis consisting of the conjugates (q-powers) of an element, in
++ this case called normal element.
++ This is chosen as a root of the extension polynomial
++ created by createNormalPoly

FiniteFieldNormalBasis(p,extdeg):_
  Exports == Implementation where
  p : PositiveInteger
  extdeg: PositiveInteger                    -- the extension degree
  NNI     ==> NonNegativeInteger
  FFF  ==> FiniteFieldFunctions(PrimeField(p))
  TERM    ==> Record(value:PrimeField(p),index:SingleInteger)
  Exports ==> FiniteAlgebraicExtensionField(PrimeField(p))  with
    getMultiplicationTable: ()   -> Vector List TERM
      ++ getMultiplicationTable() returns the multiplication
      ++ table for the normal basis of the field.
      ++ This table is used to perform multiplications between field elements.
    getMultiplicationMatrix: ()  -> Matrix PrimeField(p)
      ++ getMultiplicationMatrix() returns the multiplication table in
      ++ form of a matrix.
    sizeMultiplication:()   -> NNI
      ++ sizeMultiplication() returns the number of entries in the
      ++ multiplication table of the field. Note: The time of multiplication
      ++ of field elements depends on this size.

  Implementation ==> FiniteFieldNormalBasisExtensionByPolynomial(PrimeField(p),_
                   createLowComplexityNormalBasis(extdeg)$FFF)
```

———-

— FFNB.dotabb —

```
"FFNB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFNB"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"FFNB" -> "FAXF"
```

———-

7.12 domain FFNBX FiniteFieldNormalBasisExtension

— FiniteFieldNormalBasisExtension.input —

```
)set break resume
)sys rm -f FiniteFieldNormalBasisExtension.output
)spool FiniteFieldNormalBasisExtension.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldNormalBasisExtension
--R
--R FiniteFieldNormalBasisExtension(GF: FiniteFieldCategory,extdeg: PositiveInteger)  is a domai
--R Abbreviation for FiniteFieldNormalBasisExtension is FFNBX
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFNBX
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (GF,%) -> %                      ?*? : (%,GF) -> %
--R ?*? : (Fraction(Integer),%) -> %       ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                       ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %         ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %        ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                       -? : % -> %
--R ?/? : (%,GF) -> %                      ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                 D : % -> % if GF has FINITE
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                 ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean              associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)                coerce : GF -> %
--R coerce : Fraction(Integer) -> %        coerce : % -> %
--R coerce : Integer -> %                  coerce : % -> OutputForm
--R coordinates : % -> Vector(GF)          degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber       factor : % -> Factored(%)
--R gcd : List(%) -> %                     gcd : (%,%) -> %
--R hash : % -> SingleInteger              inGroundField? : % -> Boolean
--R inv : % -> %                           latex : % -> String
--R lcm : List(%) -> %                     lcm : (%,%) -> %
--R norm : % -> GF                         one? : % -> Boolean
--R prime? : % -> Boolean                  ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")         ?rem? : (%,%) -> %
--R represents : Vector(GF) -> %           retract : % -> GF
--R sample : () -> %                       sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)          squareFreePart : % -> %
--R trace : % -> GF                       transcendent? : % -> Boolean
--R unit? : % -> Boolean                  unitCanonical : % -> %
```

```
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : % -> % if GF has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if GF has CHARNZ or GF has FINITE
--R charthRoot : % -> % if GF has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if GF has FINITE
--R coordinates : Vector(%) -> Matrix(GF)
--R createNormalElement : () -> % if GF has FINITE
--R createPrimitiveElement : () -> % if GF has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(GF)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if GF has FINITE
--R differentiate : % -> % if GF has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if GF has CHARNZ or GF has FINITE
--R discreteLog : % -> NonNegativeInteger if GF has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if GF has FINITE
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if GF has FINITE
--R getMultiplicationMatrix : () -> Matrix(GF)
--R getMultiplicationTable : () -> Vector(List(Record(value: GF,index: SingleInteger)))
--R index : PositiveInteger -> % if GF has FINITE
--R init : () -> % if GF has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(GF)) -> % if GF has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(GF),"failed") if GF has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R lookup : % -> PositiveInteger if GF has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if GF has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(GF)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if GF has FINITE
--R norm : (%,PositiveInteger) -> % if GF has FINITE
--R normal? : % -> Boolean if GF has FINITE
--R normalElement : () -> % if GF has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if GF has CHARNZ or GF has FINITE
--R order : % -> PositiveInteger if GF has FINITE
```

```
--R primeFrobenius : % -> % if GF has CHARNZ or GF has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if GF has CHARNZ or GF has FINITE
--R primitive? : % -> Boolean if GF has FINITE
--R primitiveElement : () -> % if GF has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if GF has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if GF has FINITE
--R retractIfCan : % -> Union(GF,"failed")
--R size : () -> NonNegativeInteger if GF has FINITE
--R sizeMultiplication : () -> NonNegativeInteger
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if GF has F
--R trace : (%,PositiveInteger) -> % if GF has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— FiniteFieldNormalBasisExtension.help —

```
=====================================================================
FiniteFieldNormalBasisExtension examples
=====================================================================

See Also:
o )show FiniteFieldNormalBasisExtension
```

———-

7.12.1 FiniteFieldNormalBasisExtension (FFNBX)



See

⇒ "FiniteFieldNormalBasisExtensionByPolynomial" (FFNBP) 7.13.1 on page 841
⇒ "FiniteFieldNormalBasis" (FFNB) 7.11.1 on page 829

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
getMultiplicationMatrix	getMultiplicationTable	hash
index	inGroundField?	init
inv	latex	lcm
linearAssociatedExp	linearAssociatedLog	linearAssociatedOrder
lookup	minimalPolynomial	multiEuclidean
nextItem	norm	normal?
normalElement	one?	order
prime?	primeFrobenius	primitive?
primitiveElement	principalIdeal	random
recip	representationType	represents
retract	retractIfCan	sample
size	sizeLess?	sizeMultiplication
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain FFNBX FiniteFieldNormalBasisExtension —

```
)abbrev domain FFNBX FiniteFieldNormalBasisExtension
++ Authors: J.Grabmeier, A.Scheerhorn
++ Date Created: 26.03.1991
++ Date Last Updated:
++ Basic Operations:
++ Related Constructors: FiniteFieldNormalBasisExtensionByPolynomial,
++  FiniteFieldPolynomialPackage
++ Also See: FiniteFieldExtension, FiniteFieldCyclicGroupExtension
++ AMS Classifications:
++ Keywords: finite field, normal basis
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
```

```
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
++   AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldNormalBasisExtensionByPolynomial(GF,n)  implements a
++ finite extension field of degree n over the ground field GF.
++ The elements are represented by coordinate vectors with respect
++ to a normal basis,
++ i.e. a basis consisting of the conjugates (q-powers) of an element, in
++ this case called normal element. This is chosen as a root of the extension
++ polynomial, created by createNormalPoly from
++ \spadtype{FiniteFieldPolynomialPackage}

FiniteFieldNormalBasisExtension(GF,extdeg):_
  Exports == Implementation where
  GF    : FiniteFieldCategory               -- the ground field
  extdeg: PositiveInteger                   -- the extension degree
  NNI     ==> NonNegativeInteger
  FFF         ==> FiniteFieldFunctions(GF)
  TERM    ==> Record(value:GF,index:SingleInteger)
  Exports ==> FiniteAlgebraicExtensionField(GF)  with
    getMultiplicationTable: ()   -> Vector List TERM
      ++ getMultiplicationTable() returns the multiplication
      ++ table for the normal basis of the field.
      ++ This table is used to perform multiplications between field elements.
    getMultiplicationMatrix: ()  -> Matrix GF
      ++ getMultiplicationMatrix() returns the multiplication table in
      ++ form of a matrix.
    sizeMultiplication:()   -> NNI
      ++ sizeMultiplication() returns the number of entries in the
      ++ multiplication table of the field. Note: the time of multiplication
      ++ of field elements depends on this size.

  Implementation ==> FiniteFieldNormalBasisExtensionByPolynomial(GF,_
                     createLowComplexityNormalBasis(extdeg)$FFF)
```

———-

— FFNBX.dotabb —

```
"FFNBX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFNBX"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"FFNBX" -> "FAXF"
```

———-

7.13 domain FFNBP FiniteFieldNormalBasisExtensionByPolynomial

— FiniteFieldNormalBasisExtensionByPolynomial.input —

```
)set break resume
)sys rm -f FiniteFieldNormalBasisExtensionByPolynomial.output
)spool FiniteFieldNormalBasisExtensionByPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FiniteFieldNormalBasisExtensionByPolynomial
--R
--R FiniteFieldNormalBasisExtensionByPolynomial(GF: FiniteFieldCategory,uni: Union(SparseUnivari
--R Abbreviation for FiniteFieldNormalBasisExtensionByPolynomial is FFNBP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FFNBP
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (GF,%) -> %                      ?*? : (%,GF) -> %
--R ?*? : (Fraction(Integer),%) -> %       ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                       ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %         ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %        ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                       -? : % -> %
--R ?/? : (%,GF) -> %                      ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                 D : % -> % if GF has FINITE
--R 1 : () -> %                            0 : () -> %
--R ?^? : (%,Integer) -> %                 ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean              associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)                coerce : GF -> %
--R coerce : Fraction(Integer) -> %        coerce : % -> %
--R coerce : Integer -> %                  coerce : % -> OutputForm
--R coordinates : % -> Vector(GF)          degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber       factor : % -> Factored(%)
--R gcd : List(%) -> %                     gcd : (%,%) -> %
--R hash : % -> SingleInteger              inGroundField? : % -> Boolean
--R inv : % -> %                           latex : % -> String
--R lcm : List(%) -> %                     lcm : (%,%) -> %
--R norm : % -> GF                         one? : % -> Boolean
--R prime? : % -> Boolean                  ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")         ?rem? : (%,%) -> %
--R represents : Vector(GF) -> %           retract : % -> GF
--R sample : () -> %                       sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)          squareFreePart : % -> %
--R trace : % -> GF                       transcendent? : % -> Boolean
```

```
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if GF has FINITE
--R Frobenius : % -> % if GF has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if GF has CHARNZ or GF has FINITE
--R charthRoot : % -> % if GF has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if GF has FINITE
--R coordinates : Vector(%) -> Matrix(GF)
--R createNormalElement : () -> % if GF has FINITE
--R createPrimitiveElement : () -> % if GF has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(GF)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if GF has FINITE
--R differentiate : % -> % if GF has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if GF has CHARNZ or GF has FINITE
--R discreteLog : % -> NonNegativeInteger if GF has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if GF has FINITE
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if GF has FINITE
--R getMultiplicationMatrix : () -> Matrix(GF)
--R getMultiplicationTable : () -> Vector(List(Record(value: GF,index: SingleInteger)))
--R index : PositiveInteger -> % if GF has FINITE
--R init : () -> % if GF has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(GF)) -> % if GF has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(GF),"failed") if GF has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(GF) if GF has FINITE
--R lookup : % -> PositiveInteger if GF has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if GF has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(GF)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if GF has FINITE
--R norm : (%,PositiveInteger) -> % if GF has FINITE
--R normal? : % -> Boolean if GF has FINITE
--R normalElement : () -> % if GF has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if GF has CHARNZ or GF has FINITE
```

```
--R order : % -> PositiveInteger if GF has FINITE
--R primeFrobenius : % -> % if GF has CHARNZ or GF has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if GF has CHARNZ or GF has FINITE
--R primitive? : % -> Boolean if GF has FINITE
--R primitiveElement : () -> % if GF has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if GF has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if GF has FINITE
--R retractIfCan : % -> Union(GF,"failed")
--R size : () -> NonNegativeInteger if GF has FINITE
--R sizeMultiplication : () -> NonNegativeInteger
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if GF has F
--R trace : (%,PositiveInteger) -> % if GF has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— FiniteFieldNormalBasisExtensionByPolynomial.help —

```
=====================================================================
FiniteFieldNormalBasisExtensionByPolynomial examples
=====================================================================

See Also:
o )show FiniteFieldNormalBasisExtensionByPolynomial
```

———-

7.13.1 FiniteFieldNormalBasisExtensionByPolynomial (FFNBP)



See

⇒ "FiniteFieldNormalBasisExtension" (FFNBX) 7.12.1 on page 835
⇒ "FiniteFieldNormalBasis" (FFNB) 7.11.1 on page 829

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
differentiate	dimension	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
getMultiplicationMatrix	getMultiplicationTable	hash
index	inGroundField?	init
inv	latex	lcm
linearAssociatedExp	linearAssociatedLog	linearAssociatedOrder
lookup	minimalPolynomial	multiEuclidean
nextItem	norm	normal?
normalElement	one?	order
prime?	primeFrobenius	primitive?
primitiveElement	principalIdeal	recip
random	representationType	represents
retract	retractIfCan	sample
size	sizeLess?	sizeMultiplication
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain FFNBP FiniteFieldNormalBasisExtensionByPolynomial —

```
)abbrev domain FFNBP FiniteFieldNormalBasisExtensionByPolynomial
++ Authors: J.Grabmeier, A.Scheerhorn
++ Date Created: 26.03.1991
++ Date Last Updated: 08 May 1991
++ Basic Operations:
++ Related Constructors: InnerNormalBasisFieldFunctions, FiniteFieldFunctions,
++ Also See: FiniteFieldExtensionByPolynomial,
++  FiniteFieldCyclicGroupExtensionByPolynomial
++ AMS Classifications:
++ Keywords: finite field, normal basis
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics and
```

```
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM .
++   AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ FiniteFieldNormalBasisExtensionByPolynomial(GF,uni) implements a
++ finite extension of the ground field GF. The elements are
++ represented by coordinate vectors with respect to. a normal basis,
++ i.e. a basis
++ consisting of the conjugates (q-powers) of an element, in this case
++ called normal element, where q is the size of GF.
++ The normal element is chosen as a root of the extension
++ polynomial, which MUST be normal over GF  (user responsibility)

FiniteFieldNormalBasisExtensionByPolynomial(GF,uni): Exports == _
    Implementation where
  GF    : FiniteFieldCategory            -- the ground field
  uni   : Union(SparseUnivariatePolynomial GF,_
           Vector List Record(value:GF,index:SingleInteger))

  PI   ==> PositiveInteger
  NNI  ==> NonNegativeInteger
  I    ==> Integer
  SI   ==> SingleInteger
  SUP  ==> SparseUnivariatePolynomial
  V    ==> Vector GF
  M    ==> Matrix GF
  OUT  ==> OutputForm
  TERM ==> Record(value:GF,index:SI)
  R    ==> Record(key:PI,entry:NNI)
  TBL  ==> Table(PI,NNI)
  FFF    ==> FiniteFieldFunctions(GF)
  INBFF  ==> InnerNormalBasisFieldFunctions(GF)

  Exports ==> FiniteAlgebraicExtensionField(GF)  with

      getMultiplicationTable: ()   -> Vector List TERM
        ++ getMultiplicationTable() returns the multiplication
        ++ table for the normal basis of the field.
        ++ This table is used to perform multiplications between field elements.
      getMultiplicationMatrix:()     -> M
        ++ getMultiplicationMatrix() returns the multiplication table in
        ++ form of a matrix.
      sizeMultiplication:()   -> NNI
        ++ sizeMultiplication() returns the number of entries in the
        ++ multiplication table of the field.
        ++ Note: the time of multiplication
        ++ of field elements depends on this size.
  Implementation ==> add

-- global variables ================================================
```

```
Rep:= V     -- elements are represented by vectors over GF

alpha       :=new()$Symbol :: OutputForm
-- get a new Symbol for the output representation of the elements

initlog?:Boolean:=true
-- gets false after initialization of the logarithm table

initelt?:Boolean:=true
-- gets false after initialization of the primitive element

initmult?:Boolean:=true
-- gets false after initialization of the multiplication
-- table or the primitive element

extdeg:PI   :=1

defpol:SUP(GF):=0$SUP(GF)
-- the defining polynomial

multTable:Vector List TERM:=new(1,nil()$(List TERM))
-- global variable containing the multiplication table

if uni case (Vector List TERM) then
  multTable:=uni :: (Vector List TERM)
  extdeg:= (#multTable) pretend PI
  vv:V:=new(extdeg,0)$V
  vv.1:=1$GF
  setFieldInfo(multTable,1$GF)$INBFF
  defpol:=minimalPolynomial(vv)$INBFF
  initmult?:=false
 else
  defpol:=uni :: SUP(GF)
  extdeg:=degree(defpol)$(SUP GF) pretend PI
  multTable:Vector List TERM:=new(extdeg,nil()$(List TERM))

basisOutput : List OUT :=
  qs:OUT:=(q::Symbol)::OUT
  append([alpha, alpha **$OUT qs],_
    [alpha **$OUT (qs **$OUT i::OUT) for i in 2..extdeg-1] )


facOfGroupSize :=nil()$(List Record(factor:Integer,exponent:Integer))
-- the factorization of the cyclic group size


traceAlpha:GF:=-$GF coefficient(defpol,(degree(defpol)-1)::NNI)
-- the inverse of the trace of the normalElt
-- is computed here. It defines the imbedding of
```

```
    -- GF in the extension field

    primitiveElt:PI:=1
    -- for the lookup the primitive Element computed by createPrimitiveElement()

    discLogTable:Table(PI,TBL):=table()$Table(PI,TBL)
    -- tables indexed by the factors of sizeCG,
    -- discLogTable(factor) is a table with keys
    -- primitiveElement() ** (i * (sizeCG quo factor)) and entries i for
    -- i in 0..n-1, n computed in initialize() in order to use
    -- the minimal size limit 'limit' optimal.

-- functions ===============================================================

    initializeLog: ()     -> Void
    initializeElt: ()     -> Void
    initializeMult: ()     -> Void


    coerce(v:GF):$  == new(extdeg,v /$GF traceAlpha)$Rep
    represents(v)   ==  v::$

    degree(a) ==
      d:PI:=1
      b:= qPot(a::Rep,1)$INBFF
      while (b^=a) repeat
        b:= qPot(b::Rep,1)$INBFF
        d:=d+1
      d

    linearAssociatedExp(x,f) ==
      xm:SUP(GF):=monomial(1$GF,extdeg)$(SUP GF) - 1$(SUP GF)
      r:= (f * pol(x::Rep)$INBFF) rem xm
      vectorise(r,extdeg)$(SUP GF)
    linearAssociatedLog(x) ==  pol(x::Rep)$INBFF
    linearAssociatedOrder(x) ==
      xm:SUP(GF):=monomial(1$GF,extdeg)$(SUP GF) - 1$(SUP GF)
      xm quo gcd(xm,pol(x::Rep)$INBFF)
    linearAssociatedLog(b,x) ==
      zero? x => 0
      xm:SUP(GF):=monomial(1$GF,extdeg)$(SUP GF) - 1$(SUP GF)
      e:= extendedEuclidean(pol(b::Rep)$INBFF,xm,pol(x::Rep)$INBFF)$(SUP GF)
      e = "failed" => "failed"
      e1:= e :: Record(coef1:(SUP GF),coef2:(SUP GF))
      e1.coef1

    getMultiplicationTable() ==
      if initmult? then initializeMult()
      multTable
    getMultiplicationMatrix() ==
```

```
      if initmult? then initializeMult()
      createMultiplicationMatrix(multTable)$FFF
    sizeMultiplication() ==
      if initmult? then initializeMult()
      sizeMultiplication(multTable)$FFF

    trace(a:$) == retract trace(a,1)
    norm(a:$) == retract norm(a,1)
    generator() == normalElement(extdeg)$INBFF
    basis(n:PI) ==
      (extdeg rem n) ^= 0 => error "argument must divide extension degree"
      [Frobenius(trace(normalElement,n),i) for i in 0..(n-1)]::(Vector $)

    a:GF * x:$ == a *$Rep x

    x:$/a:GF == x/coerce(a)
--    x:$ / a:GF ==
--      a = 0$GF => error "division by zero"
--      x * inv(coerce(a))


    coordinates(x:$)  == x::Rep

    Frobenius(e) == qPot(e::Rep,1)$INBFF
    Frobenius(e,n) == qPot(e::Rep,n)$INBFF

    retractIfCan(x) ==
      inGroundField?(x) =>
        x.1 *$GF traceAlpha
      "failed"

    retract(x) ==
      inGroundField?(x) =>
        x.1 *$GF traceAlpha
      error("element not in ground field")

-- to get a "normal basis like" output form
    coerce(x:$):OUT ==
      l:List OUT:=nil()$(List OUT)
      n : PI := extdeg
--      one? n => (x.1) :: OUT
      (n = 1) => (x.1) :: OUT
      for i in 1..n for b in basisOutput repeat
        if not zero? x.i then
          mon : OUT :=
--              one? x.i => b
            (x.i = 1) => b
            ((x.i)::OUT) *$OUT b
          l:=cons(mon,l)$(List OUT)
      null(l)$(List OUT) => (0::OUT)
```

```
      r:=reduce("+",l)$(List OUT)
      r

    initializeElt() ==
      facOfGroupSize := factors factor(size()$GF**extdeg-1)$I
      -- get a primitive element
      primitiveElt:=lookup(createPrimitiveElement())
      initelt?:=false
      void()$Void

    initializeMult() ==
      multTable:=createMultiplicationTable(defpol)$FFF
      setFieldInfo(multTable,traceAlpha)$INBFF
      -- reset initialize flag
      initmult?:=false
      void()$Void

    initializeLog() ==
      if initelt? then initializeElt()
      -- set up tables for discrete logarithm
      limit:Integer:=30
      -- the minimum size for the discrete logarithm table
      for f in facOfGroupSize repeat
        fac:=f.factor
        base:$:=index(primitiveElt)**((size()$GF**extdeg -$I 1$I) quo$I fac)
        l:Integer:=length(fac)$Integer
        n:Integer:=0
        if odd?(l)$I then n:=shift(fac,-$I (l quo$I 2))$I
                     else n:=shift(1,l quo$I 2)$I
        if n <$I limit then
          d:=(fac -$I 1$I) quo$I limit +$I 1$I
          n:=(fac -$I 1$I) quo$I d +$I 1$I
        tbl:TBL:=table()$TBL
        a:$:=1
        for i in (0::NNI)..(n-1)::NNI repeat
          insert_!([lookup(a),i::NNI]$R,tbl)$TBL
          a:=a*base
        insert_!([fac::PI,copy(tbl)$TBL]_
              $Record(key:PI,entry:TBL),discLogTable)$Table(PI,TBL)
      initlog?:=false
      -- tell user about initialization
      --print("discrete logarithm table initialized"::OUT)
      void()$Void

    tableForDiscreteLogarithm(fac) ==
      if initlog? then initializeLog()
      tbl:=search(fac::PI,discLogTable)$Table(PI,TBL)
      tbl case "failed" =>
        error "tableForDiscreteLogarithm: argument must be prime _
divisor of the order of the multiplicative group"
```

```
    tbl :: TBL

  primitiveElement() ==
    if initelt? then initializeElt()
    index(primitiveElt)

  factorsOfCyclicGroupSize() ==
    if empty? facOfGroupSize then initializeElt()
    facOfGroupSize

  extensionDegree() == extdeg

  sizeOfGroundField() == size()$GF pretend NNI

  definingPolynomial() == defpol

  trace(a,d) ==
    v:=trace(a::Rep,d)$INBFF
    erg:=v
    for i in 2..(extdeg quo d) repeat
      erg:=concat(erg,v)$Rep
    erg

  characteristic() == characteristic()$GF

  random() == random(extdeg)$INBFF

  x:$ * y:$ ==
    if initmult? then initializeMult()
    setFieldInfo(multTable,traceAlpha)$INBFF
    x::Rep *$INBFF y::Rep


  1 == new(extdeg,inv(traceAlpha)$GF)$Rep

  0 == zero(extdeg)$Rep

  size() == size()$GF ** extdeg

  index(n:PI) == index(extdeg,n)$INBFF

  lookup(x:$) == lookup(x::Rep)$INBFF


  basis() ==
    a:=basis(extdeg)$INBFF
    vector([e::$ for e in entries a])


  x:$ ** e:I ==
```

```
      if initmult? then initializeMult()
      setFieldInfo(multTable,traceAlpha)$INBFF
      (x::Rep) **$INBFF e

    normal?(x) == normal?(x::Rep)$INBFF

    -(x:$) == -$Rep x
    x:$ + y:$ == x +$Rep y
    x:$ - y:$ == x -$Rep y
    x:$ = y:$ == x =$Rep y
    n:I * x:$ == x *$Rep (n::GF)




    representationType() == "normal"

    minimalPolynomial(a) ==
      if initmult? then initializeMult()
      setFieldInfo(multTable,traceAlpha)$INBFF
      minimalPolynomial(a::Rep)$INBFF

-- is x an element of the ground field GF ?
    inGroundField?(x) ==
      erg:=true
      for i in 2..extdeg repeat
        not(x.i =$GF x.1) => erg:=false
      erg

    x:$ / y:$ ==
      if initmult? then initializeMult()
      setFieldInfo(multTable,traceAlpha)$INBFF
      x::Rep /$INBFF y::Rep

    inv(a) ==
      if initmult? then initializeMult()
      setFieldInfo(multTable,traceAlpha)$INBFF
      inv(a::Rep)$INBFF

    norm(a,d) ==
      if initmult? then initializeMult()
      setFieldInfo(multTable,traceAlpha)$INBFF
      norm(a::Rep,d)$INBFF

    normalElement() == normalElement(extdeg)$INBFF
```

———-

— **FFNBP.dotabb** —

```
"FFNBP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FFNBP"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FFNBP" -> "ALIST"
```

———-

7.14 domain FARRAY FlexibleArray

— **FlexibleArray.input** —

```
)set break resume
)sys rm -f FlexibleArray.output
)spool FlexibleArray.output
)set message test on
)set message auto off
)clear all
--S 1 of 16
flexibleArray [i for i in 1..6]
--R
--R
--R   (1)  [1,2,3,4,5,6]
--R                                          Type: FlexibleArray(PositiveInteger)
--E 1

--S 2 of 16
f : FARRAY INT := new(6,0)
--R
--R
--R   (2)  [0,0,0,0,0,0]
--R                                                  Type: FlexibleArray(Integer)
--E 2

--S 3 of 16
for i in 1..6 repeat f.i := i; f
--R
--R
--R   (3)  [1,2,3,4,5,6]
--R                                                  Type: FlexibleArray(Integer)
--E 3

--S 4 of 16
physicalLength f
--R
```

```
--R
--R   (4)  6
--R                                                    Type: PositiveInteger
--E 4

--S 5 of 16
concat!(f,11)
--R
--R
--R   (5)  [1,2,3,4,5,6,11]
--R                                                 Type: FlexibleArray(Integer)
--E 5

--S 6 of 16
physicalLength f
--R
--R
--R   (6)  10
--R                                                    Type: PositiveInteger
--E 6

--S 7 of 16
physicalLength!(f,15)
--R
--R
--R   (7)  [1,2,3,4,5,6,11]
--R                                                 Type: FlexibleArray(Integer)
--E 7

--S 8 of 16
concat!(f,f)
--R
--R
--R   (8)  [1,2,3,4,5,6,11,1,2,3,4,5,6,11]
--R                                                 Type: FlexibleArray(Integer)
--E 8

--S 9 of 16
insert!(22,f,1)
--R
--R
--R   (9)  [22,1,2,3,4,5,6,11,1,2,3,4,5,6,11]
--R                                                 Type: FlexibleArray(Integer)
--E 9

--S 10 of 16
g := f(10..)
--R
--R
--R   (10)  [2,3,4,5,6,11]
```

```
--R                                                    Type: FlexibleArray(Integer)
--E 10

--S 11 of 16
insert!(g,f,1)
--R
--R
--R   (11)  [2,3,4,5,6,11,22,1,2,3,4,5,6,11,1,2,3,4,5,6,11]
--R                                                    Type: FlexibleArray(Integer)
--E 11

--S 12 of 16
merge!(sort! f, sort! g)
--R
--R
--R   (12)  [1,1,2,2,2,2,3,3,3,3,4,4,4,4,5,5,5,5,6,6,6,6,11,11,11,11,22]
--R                                                    Type: FlexibleArray(Integer)
--E 12

--S 13 of 16
removeDuplicates! f
--R
--R
--R   (13)  [1,2,3,4,5,6,11,22]
--R                                                    Type: FlexibleArray(Integer)
--E 13

--S 14 of 16
select!(i +-> even? i,f)
--R
--R
--R   (14)  [2,4,6,22]
--R                                                    Type: FlexibleArray(Integer)
--E 14

--S 15 of 16
physicalLength f
--R
--R
--R   (15)  8
--R                                                          Type: PositiveInteger
--E 15

--S 16 of 16
shrinkable(false)$FlexibleArray(Integer)
--R
--R
--R   (16)  true
--R                                                                  Type: Boolean
--E 16
```

```
)spool
)lisp (bye)
```

———-

— FlexibleArray.help —

```
====================================================================
FlexibleArray
====================================================================

The FlexibleArray domain constructor creates one-dimensional
arrays of elements of the same type.  Flexible arrays are an attempt
to provide a data type that has the best features of both
one-dimensional arrays (fast, random access to elements) and lists
(flexibility).  They are implemented by a fixed block of storage.
When necessary for expansion, a new, larger block of storage is
allocated and the elements from the old storage area are copied into
the new block.

Flexible arrays have available most of the operations provided by
OneDimensionalArray Vector.  Since flexible arrays are also of
category ExtensibleLinearAggregate they have operations concat!,
delete!, insert!, merge!, remove!, removeDuplicates!, and select!.  In
addition, the operations physicalLength and physicalLength! provide
user-control over expansion and contraction.

A convenient way to create a flexible array is to apply the operation
flexibleArray to a list of values.

  flexibleArray [i for i in 1..6]
    [1,2,3,4,5,6]
                    Type: FlexibleArray PositiveInteger

Create a flexible array of six zeroes.

  f : FARRAY INT := new(6,0)
    [0,0,0,0,0,0]
                    Type: FlexibleArray Integer

For i=1..6 set the i-th element to i.  Display f.

  for i in 1..6 repeat f.i := i; f
    [1,2,3,4,5,6]
                    Type: FlexibleArray Integer

Initially, the physical length is the same as the number of elements.

  physicalLength f
```

```
    6
                    Type: PositiveInteger

Add an element to the end of f.

  concat!(f,11)
    [1,2,3,4,5,6,11]
                    Type: FlexibleArray Integer

See that its physical length has grown.

  physicalLength f
    10
                    Type: PositiveInteger

Make f grow to have room for 15 elements.

  physicalLength!(f,15)
    [1,2,3,4,5,6,11]
                    Type: FlexibleArray Integer

Concatenate the elements of f to itself.  The physical length
allows room for three more values at the end.

  concat!(f,f)
    [1,2,3,4,5,6,11,1,2,3,4,5,6,11]
                    Type: FlexibleArray Integer

Use insert! to add an element to the front of a flexible array.

  insert!(22,f,1)
    [22,1,2,3,4,5,6,11,1,2,3,4,5,6,11]
                    Type: FlexibleArray Integer

Create a second flexible array from f consisting of the elements from
index 10 forward.

  g := f(10..)
    [2,3,4,5,6,11]
                    Type: FlexibleArray Integer

Insert this array at the front of f.

  insert!(g,f,1)
    [2,3,4,5,6,11,22,1,2,3,4,5,6,11,1,2,3,4,5,6,11]
                    Type: FlexibleArray Integer

Merge the flexible array f into g after sorting each in place.

  merge!(sort! f, sort! g)
```

```
    [1,1,2,2,2,2,3,3,3,3,4,4,4,4,5,5,5,5,6,6,6,6,11,11,11,11,22]
                    Type: FlexibleArray Integer

Remove duplicates in place.

  removeDuplicates! f
    [1,2,3,4,5,6,11,22]
                    Type: FlexibleArray Integer

Remove all odd integers.

  select!(i +-> even? i,f)
    [2,4,6,22]
                    Type: FlexibleArray Integer

All these operations have shrunk the physical length of f.

  physicalLength f
    8
                    Type: PositiveInteger


To force Axiom not to shrink flexible arrays call the shrinkable
operation with the argument false.  You must package call this
operation.  The previous value is returned.

  shrinkable(false)$FlexibleArray(Integer)
    true
                    Type: Boolean

See Also:
o )help OneDimensionalArray
o )help Vector
o )help ExtensibleLinearAggregate
o )show FlexibleArray
```

———-

7.14.1 FlexibleArray (FARRAY)



See

⇒ "PrimitiveArray" (PRIMARR) 17.30.1 on page 2075
⇒ "Tuple" (TUPLE) 21.12.1 on page 2721
⇒ "IndexedFlexibleArray" (IFARRAY) 10.10.1 on page 1191
⇒ "IndexedOneDimensionalArray" (IARRAY1) 10.13.1 on page 1212
⇒ "OneDimensionalArray" (ARRAY1) 16.3.1 on page 1740

Exports:

any?	coerce	concat	concat!	construct
convert	copy	copyInto!	count	delete
delete!	elt	empty	empty?	entries
entry?	eq?	eval	every?	fill!
find	first	flexibleArray	hash	index?
indices	insert	insert!	latex	less?
map	map!	max	maxIndex	member?
members	merge	merge!	min	minIndex
more?	new	parts	physicalLength	physicalLength!
position	qelt	qsetelt!	reduce	remove
remove!	removeDuplicates	removeDuplicates!	reverse	reverse!
sample	select	select!	setelt	shrinkable
size?	sort	sort!	sorted?	swap!
#?	?<?	?<=?	?=?	?>?
?>=?	?~=?	?.?		

— domain FARRAY FlexibleArray —

```
)abbrev domain FARRAY FlexibleArray
++ Author: Mark Botch
++ Description:
++ A FlexibleArray is the notion of an array intended to allow for growth
++ at the end only.  Hence the following efficient operations
++ \spad{append(x,a)} meaning append item x at the end of the array \spad{a}
++ \spad{delete(a,n)} meaning delete the last item from the array \spad{a}
++ Flexible arrays support the other operations inherited from
++ \spadtype{ExtensibleLinearAggregate}. However, these are not efficient.
```

```
++ Flexible arrays combine the \spad{O(1)} access time property of arrays
++ with growing and shrinking at the end in \spad{O(1)} (average) time.
++ This is done by using an ordinary array which may have zero or more
++ empty slots at the end.  When the array becomes full it is copied
++ into a new larger (50% larger) array.  Conversely, when the array
++ becomes less than 1/2 full, it is copied into a smaller array.
++ Flexible arrays provide for an efficient implementation of many
++ data structures in particular heaps, stacks and sets.

FlexibleArray(S: Type) == Implementation where
  ARRAYMININDEX ==> 1       -- if you want to change this, be my guest
  Implementation ==> IndexedFlexibleArray(S, ARRAYMININDEX)
-- Join(OneDimensionalArrayAggregate S, ExtensibleLinearAggregate S)
```

———-

— **FARRAY.dotabb** —

```
"FARRAY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FARRAY"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"FARRAY" -> "A1AGG"
```

———-

7.15 domain FLOAT Float

As reported in bug number 4733 (rounding of negative numbers) errors were observed in operations such as

```
-> round(-3.9)
-> truncate(-3.9)
```

The problem is the unexpected behaviour of the shift with negative integer arguments.

```
-> shift(-7,-1)
```

returns -4 while the code here in float expects the value to be -3. shift uses the lisp function ASH 'arithmetic shift left' but the spad code expects an unsigned 'logical' shift. See

```
http://www.lispworks.com/reference/HyperSpec/Body/f_ash.htm#ash
```

A new internal function shift2 is defined in terms of shift to compensate for the use of ASH and provide the required function.

It is currently unknown whether the unexpected behaviour of shift for negative arguments will cause bugs in other parts of Axiom.

— **Float.input** —

```
)set break resume
)sys rm -f Float.output
)spool Float.output
)set message test on
)set message auto off
)clear all
--S 1 of 64
1.234
--R
--R
--R   (1)  1.234
--R                                                          Type: Float
--E 1

--S 2 of 64
1.234E2
--R
--R
--R   (2)  123.4
--R                                                          Type: Float
--E 2

--S 3 of 64
sqrt(1.2 + 2.3 / 3.4 ** 4.5)
--R
--R
--R   (3)  1.0996972790 671286226
--R                                                          Type: Float
--E 3

--S 4 of 64
i := 3 :: Float
--R
--R
--R   (4)  3.0
--R                                                          Type: Float
--E 4

--S 5 of 64
i :: Integer
--R
--R
--R   (5)  3
--R                                                       Type: Integer
--E 5

--S 6 of 64
i :: Fraction Integer
--R
--R
```

```
--R   (6)  3
--R                                                    Type: Fraction(Integer)
--E 6

--S 7 of 64
r := 3/7 :: Float
--R
--R
--R   (7)  0.4285714285 7142857143
--R                                                                 Type: Float
--E 7

--S 8 of 64
r :: Fraction Integer
--R
--R
--R        3
--R   (8)  -
--R        7
--R                                                    Type: Fraction(Integer)
--E 8

--S 9 of 64
r :: Integer
--R
--R
--RDaly Bug
--R   Cannot convert from type Float to Integer for value
--R   0.4285714285 7142857143
--R
--E 9

--S 10 of 64
truncate 3.6
--R
--R
--R   (9)  3.0
--R                                                                 Type: Float
--E 10

--S 11 of 64
round 3.6
--R
--R
--R   (10)  4.0
--R                                                                 Type: Float
--E 11

--S 12 of 64
truncate(-3.6)
```

```
--R
--R
--R   (11)  - 3.0
--R                                                          Type: Float
--E 12

--S 13 of 64
round(-3.6)
--R
--R
--R   (12)  - 4.0
--R                                                          Type: Float
--E 13

--S 14 of 64
fractionPart 3.6
--R
--R
--R   (13)  0.6
--R                                                          Type: Float
--E 14

--S 15 of 64
digits 40
--R
--R
--R   (14)  20
--R                                                 Type: PositiveInteger
--E 15

--S 16 of 64
sqrt 0.2
--R
--R
--R   (15)  0.4472135954 9995793928 1834733746 2552470881
--R                                                          Type: Float
--E 16

--S 17 of 64
pi()$Float
--R
--R
--R   (16)  3.1415926535 8979323846 2643383279 502884197
--R                                                          Type: Float
--E 17

--S 18 of 64
digits 500
--R
--R
```

```
--R   (17)  40
--R                                                    Type: PositiveInteger
--E 18

--S 19 of 64
pi()$Float
--R
--R
--R   (18)
--R  3.1415926535 8979323846 2643383279 5028841971 6939937510 5820974944 592307816
--R  4 0628620899 8628034825 3421170679 8214808651 3282306647 0938446095 505822317
--R  2 5359408128 4811174502 8410270193 8521105559 6446229489 5493038196 442881097
--R  5 6659334461 2847564823 3786783165 2712019091 4564856692 3460348610 454326648
--R  2 1339360726 0249141273 7245870066 0631558817 4881520920 9628292540 917153643
--R  6 7892590360 0113305305 4882046652 1384146951 9415116094 3305727036 575959195
--R  3 0921861173 8193261179 3105118548 0744623799 6274956735 1885752724 891227938
--R  1 830119491
--R                                                                 Type: Float
--E 19

--S 20 of 64
digits 20
--R
--R
--R   (19)  500
--R                                                    Type: PositiveInteger
--E 20

--S 21 of 64
outputSpacing 0; x := sqrt 0.2
--R
--R
--R   (20)  0.44721359549995793928
--R                                                                 Type: Float
--E 21

--S 22 of 64
outputSpacing 5; x
--R
--R
--R   (21)  0.44721 35954 99957 93928
--R                                                                 Type: Float
--E 22

--S 23 of 64
y := x/10**10
--R
--R
--R   (22)  0.44721 35954 99957 93928 E -10
--R                                                                 Type: Float
```

```
--E 23

--S 24 of 64
outputFloating(); x
--R
--R
--R   (23)  0.44721 35954 99957 93928 E 0
--R                                                                  Type: Float
--E 24

--S 25 of 64
outputFixed(); y
--R
--R
--R   (24)  0.00000 00000 44721 35954 99957 93928
--R                                                                  Type: Float
--E 25

--S 26 of 64
outputFloating 2; y
--R
--R
--R   (25)  0.45 E -10
--R                                                                  Type: Float
--E 26

--S 27 of 64
outputFixed 2; x
--R
--R
--R   (26)  0.45
--R                                                                  Type: Float
--E 27

--S 28 of 64
outputGeneral()
--R
--R                                                                   Type: Void
--E 28

--S 29 of 64
a: Matrix Fraction Integer := matrix [ [1/(i+j+1) for j in 0..9] for i in 0..9]
--R
--R
--R         +    1   1   1   1   1   1   1   1    1+
--R         |1   -   -   -   -   -   -   -   -   --|
--R         |    2   3   4   5   6   7   8   9   10|
--R         |                                      |
--R         |1   1   1   1   1   1   1   1    1   1|
--R         |-   -   -   -   -   -   -   -   --  --|
```

```
--R         |2   3   4   5   6   7   8   9   10  11|
--R         |                                       |
--R         |1   1   1   1   1   1   1    1   1   1|
--R         |-   -   -   -   -   -   -   --  --  --|
--R         |3   4   5   6   7   8   9   10  11  12|
--R         |                                       |
--R         |1   1   1   1   1   1    1   1   1   1|
--R         |-   -   -   -   -   -   --  --  --  --|
--R         |4   5   6   7   8   9   10  11  12  13|
--R         |                                       |
--R         |1   1   1   1   1    1   1   1   1   1|
--R         |-   -   -   -   -   --  --  --  --  --|
--R         |5   6   7   8   9   10  11  12  13  14|
--R   (28)  |                                       |
--R         |1   1   1   1    1   1   1   1   1   1|
--R         |-   -   -   -   --  --  --  --  --  --|
--R         |6   7   8   9   10  11  12  13  14  15|
--R         |                                       |
--R         |1   1   1    1   1   1   1   1   1   1|
--R         |-   -   -   --  --  --  --  --  --  --|
--R         |7   8   9   10  11  12  13  14  15  16|
--R         |                                       |
--R         |1   1    1   1   1   1   1   1   1   1|
--R         |-   -   --  --  --  --  --  --  --  --|
--R         |8   9   10  11  12  13  14  15  16  17|
--R         |                                       |
--R         |1    1   1   1   1   1   1   1   1   1|
--R         |-   --  --  --  --  --  --  --  --  --|
--R         |9   10  11  12  13  14  15  16  17  18|
--R         |                                       |
--R         | 1   1   1   1   1   1   1   1   1   1|
--R         |--  --  --  --  --  --  --  --  --  --|
--R         +10  11  12  13  14  15  16  17  18  19+
--R                                          Type: Matrix(Fraction(Integer))
--E 29

--S 30 of 64
d:= determinant a
--R
--R
--R                                  1
--R   (29)  ------------------------------------------------
--R         46206893947914691316295628839036278726983680000000000
--R                                                    Type: Fraction(Integer)
--E 30

--S 31 of 64
d :: Float
--R
--R
```

```
--R   (30)  0.21641 79226 43149 18691 E -52
--R                                                                    Type: Float
--E 31

--S 32 of 64
b: Matrix DoubleFloat := matrix [ [1/(i+j+1$DoubleFloat) for j in 0..9] for i in 0..9]
--R
--R
--R   (31)
--R   [
--R     [1., 0.5, 0.33333333333333331, 0.25, 0.20000000000000001,
--R      0.16666666666666666, 0.14285714285714285, 0.125, 0.1111111111111111,
--R      0.10000000000000001]
--R     ,
--R
--R     [0.5, 0.33333333333333331, 0.25, 0.20000000000000001, 0.16666666666666666,
--R      0.14285714285714285, 0.125, 0.1111111111111111, 0.10000000000000001,
--R      9.0909090909090912E-2]
--R     ,
--R
--R     [0.33333333333333331, 0.25, 0.20000000000000001, 0.16666666666666666,
--R      0.14285714285714285, 0.125, 0.1111111111111111, 0.10000000000000001,
--R      9.0909090909090912E-2, 8.3333333333333329E-2]
--R     ,
--R
--R     [0.25, 0.20000000000000001, 0.16666666666666666, 0.14285714285714285,
--R      0.125, 0.1111111111111111, 0.10000000000000001, 9.0909090909090912E-2,
--R      8.3333333333333329E-2, 7.6923076923076927E-2]
--R     ,
--R
--R     [0.20000000000000001, 0.16666666666666666, 0.14285714285714285, 0.125,
--R      0.1111111111111111, 0.10000000000000001, 9.0909090909090912E-2,
--R      8.3333333333333329E-2, 7.6923076923076927E-2, 7.1428571428571425E-2]
--R     ,
--R
--R     [0.16666666666666666, 0.14285714285714285, 0.125, 0.1111111111111111,
--R      0.10000000000000001, 9.0909090909090912E-2, 8.3333333333333329E-2,
--R      7.6923076923076927E-2, 7.1428571428571425E-2, 6.6666666666666666E-2]
--R     ,
--R
--R     [0.14285714285714285, 0.125, 0.1111111111111111, 0.10000000000000001,
--R      9.0909090909090912E-2, 8.3333333333333329E-2, 7.6923076923076927E-2,
--R      7.1428571428571425E-2, 6.6666666666666666E-2, 6.25E-2]
--R     ,
--R
--R     [0.125, 0.1111111111111111, 0.10000000000000001, 9.0909090909090912E-2,
--R      8.3333333333333329E-2, 7.6923076923076927E-2, 7.1428571428571425E-2,
--R      6.6666666666666666E-2, 6.25E-2, 5.8823529411764705E-2]
--R     ,
--R
```

```
--R     [0.1111111111111111, 0.10000000000000001, 9.0909090909090912E-2,
--R      8.3333333333333329E-2, 7.6923076923076927E-2, 7.1428571428571425E-2,
--R      6.6666666666666666E-2, 6.25E-2, 5.8823529411764705E-2,
--R      5.5555555555555552E-2]
--R     ,
--R
--R     [0.10000000000000001, 9.0909090909090912E-2, 8.3333333333333329E-2,
--R      7.6923076923076927E-2, 7.1428571428571425E-2, 6.6666666666666666E-2,
--R      6.25E-2, 5.8823529411764705E-2, 5.5555555555555552E-2,
--R      5.2631578947368418E-2]
--R     ]
--R                                                    Type: Matrix(DoubleFloat)
--E 32

--S 33 of 64
determinant b
--R
--R
--R   (32)  2.1643677945721411E-53
--R                                                        Type: DoubleFloat
--E 33

--S 34 of 64
digits 40
--R
--R
--R   (33)  20
--R                                                   Type: PositiveInteger
--E 34

--S 35 of 64
c: Matrix Float := matrix [ [1/(i+j+1$Float) for j in 0..9] for i in 0..9]
--R
--R
--R   (34)
--R   [
--R     [1.0, 0.5, 0.33333 33333 33333 33333 33333 33333 33333 33333, 0.25, 0.2,
--R      0.16666 66666 66666 66666 66666 66666 66666 66667,
--R      0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1]
--R     ,
--R
--R     [0.5, 0.33333 33333 33333 33333 33333 33333 33333 33333, 0.25, 0.2,
--R      0.16666 66666 66666 66666 66666 66666 66666 66667,
--R      0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1]
--R     ,
--R
--R     [0.33333 33333 33333 33333 33333 33333 33333 33333, 0.25, 0.2,
```

```
--R      0.16666 66666 66666 66666 66666 66666 66666 66667,
--R      0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4]
--R     ,
--R
--R     [0.25, 0.2, 0.16666 66666 66666 66666 66666 66666 66666 66667,
--R      0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2]
--R     ,
--R
--R     [0.2, 0.16666 66666 66666 66666 66666 66666 66666 66667,
--R      0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2,
--R      0.07142 85714 28571 42857 14285 71428 57142 85714 3]
--R     ,
--R
--R     [0.16666 66666 66666 66666 66666 66666 66666 66667,
--R      0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2,
--R      0.07142 85714 28571 42857 14285 71428 57142 85714 3,
--R      0.06666 66666 66666 66666 66666 66666 66666 66666 7]
--R     ,
--R
--R     [0.14285 71428 57142 85714 28571 42857 14285 71429, 0.125,
--R      0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2,
--R      0.07142 85714 28571 42857 14285 71428 57142 85714 3,
--R      0.06666 66666 66666 66666 66666 66666 66666 66666 7, 0.0625]
--R     ,
--R
--R     [0.125, 0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2,
--R      0.07142 85714 28571 42857 14285 71428 57142 85714 3,
--R      0.06666 66666 66666 66666 66666 66666 66666 66666 7, 0.0625,
--R      0.05882 35294 11764 70588 23529 41176 47058 82352 9]
```

```
--R     ,
--R
--R     [0.11111 11111 11111 11111 11111 11111 11111 11111, 0.1,
--R      0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2,
--R      0.07142 85714 28571 42857 14285 71428 57142 85714 3,
--R      0.06666 66666 66666 66666 66666 66666 66666 66666 7, 0.0625,
--R      0.05882 35294 11764 70588 23529 41176 47058 82352 9,
--R      0.05555 55555 55555 55555 55555 55555 55555 55555 6]
--R     ,
--R
--R     [0.1, 0.09090 90909 09090 90909 09090 90909 09090 90909 1,
--R      0.08333 33333 33333 33333 33333 33333 33333 33333 4,
--R      0.07692 30769 23076 92307 69230 76923 07692 30769 2,
--R      0.07142 85714 28571 42857 14285 71428 57142 85714 3,
--R      0.06666 66666 66666 66666 66666 66666 66666 66666 7, 0.0625,
--R      0.05882 35294 11764 70588 23529 41176 47058 82352 9,
--R      0.05555 55555 55555 55555 55555 55555 55555 55555 6,
--R      0.05263 15789 47368 42105 26315 78947 36842 10526 3]
--R     ]
--R                                                    Type: Matrix(Float)
--E 35

--S 36 of 64
determinant c
--R
--R
--R   (35)  0.21641 79226 43149 18690 60594 98362 26174 36159 E -52
--R                                                                Type: Float
--E 36

--S 37 of 64
digits 20
--R
--R
--R   (36)  40
--R                                                  Type: PositiveInteger
--E 37

)clear all

--S 38 of 64
outputFixed()
--R
--R                                                                 Type: Void
--E 38

--S 39 of 64
a:=3.0
```

```
--R
--R
--R   (2)  3.0
--R                                                          Type: Float
--E 39

--S 40 of 64
b:=3.1
--R
--R
--R   (3)  3.1
--R                                                          Type: Float
--E 40

--S 41 of 64
c:=numeric pi()
--R
--R
--R   (4)  3.14159 26535 89793 2385
--R                                                          Type: Float
--E 41

--S 42 of 64
d:=0.0
--R
--R
--R   (5)  0.0
--R                                                          Type: Float
--E 42

--S 43 of 64
outputFixed 2
--R
--R                                                           Type: Void
--E 43

--S 44 of 64
a
--R
--R
--R   (7)  3.00
--R                                                          Type: Float
--E 44

--S 45 of 64
b
--R
--R
--R   (8)  3.10
--R                                                          Type: Float
```

```
--E 45

--S 46 of 64
c
--R
--R
--R   (9)  3.14
--R                                                    Type: Float
--E 46

--S 47 of 64
d
--R
--R
--R   (10)  0.00
--R                                                    Type: Float
--E 47

--S 48 of 64
outputFixed 0
--R
--R                                                     Type: Void
--E 48

--S 49 of 64
a
--R
--R
--R   (12)  3.0
--R                                                    Type: Float
--E 49

--S 50 of 64
b
--R
--R
--R   (13)  3.
--R                                                    Type: Float
--E 50

--S 51 of 64
c
--R
--R
--R   (14)  3.
--R                                                    Type: Float
--E 51

--S 52 of 64
31.1
```

```
--R
--R
--R   (15)  31.
--R                                                    Type: Float
--E 52

--S 53 of 64
310.1
--R
--R
--R   (16)  310.
--R                                                    Type: Float
--E 53

--S 54 of 64
d
--R
--R
--R   (17)  0.0
--R                                                    Type: Float
--E 54

--S 55 of 64
outputFixed(0)
--R                                                     Type: Void
--E 55

--S 56 of 64
1.1
--R
--R   (19)  1.
--R                                                    Type: Float
--E 56

--S 57 of 64
3111.1
--R
--R   (20)  3111.
--R                                                    Type: Float
--E 57

--S 58 of 64
1234567890.1
--R
--R   (21)  12345 67890.
--R                                                    Type: Float
--E 58

--S 59 of 64
outputFixed(12)
```

```
--R                                                                  Type: Void
--E 59

--S 60 of 64
1234567890.1
--R
--R   (23)  12345 67890.09999 99999 99
--R                                                                Type: Float
--E 60

--S 61 of 64
outputFixed(15)
--R                                                                  Type: Void
--E 61

--S 62 of 64
1234567890.1
--R
--R   (25)  12345 67890.09999 99999 98545
--R                                                                Type: Float
--E 62

--S 63 of 64
outputFixed(2)
--R                                                                  Type: Void
--E 63

--S 64 of 64
1234567890.1
--R
--R   (27)  12345 67890.10
--R                                                                Type: Float
--E 64

)spool
)lisp (bye)
```

———-

— Float.help —

```
=====================================================================
Float
=====================================================================

Axiom provides two kinds of floating point numbers.  The domain Float
implements a model of arbitrary precision floating point numbers.  The
domain DoubleFloat is intended to make available hardware floating
point arithmetic in Axiom.  The actual model of floating point that
```

```
DoubleFloat provides is system-dependent.  For example, on the IBM
system 370 Axiom uses IBM double precision which has fourteen
hexadecimal digits of precision or roughly sixteen decimal digits.
Arbitrary precision floats allow the user to specify the precision at
which arithmetic operations are computed.  Although this is an
attractive facility, it comes at a cost.  Arbitrary-precision
floating-point arithmetic typically takes twenty to two hundred times
more time than hardware floating point.

========================================================================
Introduction to Float
========================================================================

Scientific notation is supported for input and output of floating
point numbers.  A floating point number is written as a string of
digits containing a decimal point optionally followed by the letter
"E", and then the exponent.

We begin by doing some calculations using arbitrary precision floats.
The default precision is twenty decimal digits.

  1.234
   1.234
                        Type: Float

A decimal base for the exponent is assumed, so the number
1.234E2 denotes 1.234x10^2.

  1.234E2
    123.4
                        Type: Float
The normal arithmetic operations are available for floating point numbers.

  sqrt(1.2 + 2.3 / 3.4 ** 4.5)
    1.0996972790 671286226
                        Type: Float

========================================================================
Conversion Functions
========================================================================

You can use conversion to go back and forth between Integer, Fraction
Integer and Float, as appropriate.

  i := 3 :: Float
    3.0
                        Type: Float

  i :: Integer
    3
```

```
                    Type: Integer

  i :: Fraction Integer
    3
                    Type: Fraction Integer
```

Since you are explicitly asking for a conversion, you must take responsibility for any loss of exactness.

```
  r := 3/7 :: Float
    0.4285714285 7142857143
                    Type: Float

  r :: Fraction Integer
    3
    -
    7
                    Type: Fraction Integer
```

This conversion cannot be performed: use truncate or round if that is what you intend.

```
  r :: Integer
   Cannot convert from type Float to Integer for value
   0.4285714285 7142857143
```

The operations truncate and round truncate ...

```
   truncate 3.6
    3.0
                    Type: Float
```

and round to the nearest integral Float respectively.

```
  round 3.6
    4.0
                    Type: Float

  truncate(-3.6)
    - 3.0
                    Type: Float

  round(-3.6)
    - 4.0
                    Type: Float
```

The operation fractionPart computes the fractional part of x, that is, x - truncate x.

```
  fractionPart 3.6
```

```
    0.6
                        Type: Float

The operation digits allows the user to set the precision.  It returns
the previous value it was using.

  digits 40
    20
                        Type: PositiveInteger

  sqrt 0.2
    0.4472135954 9995793928 1834733746 2552470881
                        Type: Float

  pi()$Float
    3.1415926535 8979323846 2643383279 502884197
                        Type: Float

The precision is only limited by the computer memory available.
Calculations at 500 or more digits of precision are not difficult.

  digits 500
    40
                        Type: PositiveInteger

  pi()$Float
  3.1415926535 8979323846 2643383279 5028841971 6939937510 5820974944 592307816
  4 0628620899 8628034825 3421170679 8214808651 3282306647 0938446095 505822317
  2 5359408128 4811174502 8410270193 8521105559 6446229489 5493038196 442881097
  5 6659334461 2847564823 3786783165 2712019091 4564856692 3460348610 454326648
  2 1339360726 0249141273 7245870066 0631558817 4881520920 9628292540 917153643
  6 7892590360 0113305305 4882046652 1384146951 9415116094 3305727036 575959195
  3 0921861173 8193261179 3105118548 0744623799 6274956735 1885752724 891227938
  1 830119491
                        Type: Float

Reset digits to its default value.

  digits 20
    500
                        Type: PositiveInteger

Numbers of type Float are represented as a record of two
integers, namely, the mantissa and the exponent where the base of the
exponent is binary.  That is, the floating point number (m,e)
represents the number m x 2^e.  A consequence of using a binary
base is that decimal numbers can not, in general, be represented
exactly.

================================================================
```

```
Output Functions
================================================================

A number of operations exist for specifying how numbers of type Float
are to be displayed.  By default, spaces are inserted every ten digits
in the output for readability. Note that you cannot include spaces in
the input form of a floating point number, though you can use
underscores.

Output spacing can be modified with the outputSpacing operation.  This
inserts no spaces and then displays the value of x.

  outputSpacing 0; x := sqrt 0.2
    0.44721359549995793928
                       Type: Float

Issue this to have the spaces inserted every 5 digits.

  outputSpacing 5; x
    0.44721 35954 99957 93928
                       Type: Float

By default, the system displays floats in either fixed format
or scientific format, depending on the magnitude of the number.

  y := x/10**10
    0.44721 35954 99957 93928 E -10
                       Type: Float

A particular format may be requested with the operations
outputFloating and outputFixed.

  outputFloating(); x
    0.44721 35954 99957 93928 E 0
                       Type: Float

  outputFixed(); y
    0.00000 00000 44721 35954 99957 93928
                       Type: Float

Additionally, you can ask for n digits to be displayed after the
decimal point.

  outputFloating 2; y
    0.45 E -10
                       Type: Float

  outputFixed 2; x
    0.45
                       Type: Float
```

This resets the output printing to the default behavior.

```
  outputGeneral()
                      Type: Void
```

```
========================================================================
An Example: Determinant of a Hilbert Matrix
========================================================================
```

Consider the problem of computing the determinant of a 10 by 10 Hilbert matrix. The (i,j)-th entry of a Hilbert matrix is given by 1/(i+j+1).

First do the computation using rational numbers to obtain the exact result.

```
  a: Matrix Fraction Integer:=matrix[ [1/(i+j+1) for j in 0..9] for i in 0..9]
         +    1   1   1   1   1   1   1   1    1+
         |1   -   -   -   -   -   -   -   -   --|
         |    2   3   4   5   6   7   8   9   10|
         |                                      |
         |1   1   1   1   1   1   1   1    1   1|
         |-   -   -   -   -   -   -   -   --  --|
         |2   3   4   5   6   7   8   9   10  11|
         |                                      |
         |1   1   1   1   1   1   1    1   1   1|
         |-   -   -   -   -   -   -   --  --  --|
         |3   4   5   6   7   8   9   10  11  12|
         |                                      |
         |1   1   1   1   1   1    1   1   1   1|
         |-   -   -   -   -   -   --  --  --  --|
         |4   5   6   7   8   9   10  11  12  13|
         |                                      |
         |1   1   1   1   1    1   1   1   1   1|
         |-   -   -   -   -   --  --  --  --  --|
         |5   6   7   8   9   10  11  12  13  14|
         |                                      |
         |1   1   1   1    1   1   1   1   1   1|
         |-   -   -   -   --  --  --  --  --  --|
         |6   7   8   9   10  11  12  13  14  15|
         |                                      |
         |1   1   1    1   1   1   1   1   1   1|
         |-   -   -   --  --  --  --  --  --  --|
         |7   8   9   10  11  12  13  14  15  16|
         |                                      |
         |1   1    1   1   1   1   1   1   1   1|
         |-   -   --  --  --  --  --  --  --  --|
         |8   9   10  11  12  13  14  15  16  17|
         |                                      |
```

```
        |1    1   1   1   1   1   1   1   1   1|
        |-   --  --  --  --  --  --  --  --  --|
        |9   10  11  12  13  14  15  16  17  18|
        |                                       |
        | 1   1   1   1   1   1   1   1   1   1|
        |--  --  --  --  --  --  --  --  --  --|
        +10  11  12  13  14  15  16  17  18  19+
                    Type: Matrix Fraction Integer
```

This version of determinant uses Gaussian elimination.

```
  d:= determinant a
                              1
    ---------------------------------------------------
    46206893947914691316295628839036278726983680000000000
                    Type: Fraction Integer

  d :: Float
    0.21641 79226 43149 18691 E -52
                    Type: Float
```

Now use hardware floats. Note that a semicolon (;) is used to prevent
the display of the matrix.

```
  b: Matrix DoubleFloat:=matrix[ [1/(i+j+1\$DoubleFloat) for j in 0..9] for i in 0..9];


                    Type: Matrix DoubleFloat
```

The result given by hardware floats is correct only to four
significant digits of precision. In the jargon of numerical analysis,
the Hilbert matrix is said to be "ill-conditioned."

```
  determinant b
    2.1643677945721411E-53
                    Type: DoubleFloat
```

Now repeat the computation at a higher precision using Float.

```
  digits 40
    20
                    Type: PositiveInteger

  c: Matrix Float := matrix [ [1/(i+j+1\$Float) for j in 0..9] for i in 0..9];
                    Type: Matrix Float


  determinant c
    0.21641 79226 43149 18690 60594 98362 26174 36159 E -52
                    Type: Float
```

```
Reset digits to its default value.

  digits 20
    40
                        Type: PositiveInteger

See Also:
o )help DoubleFloat
o )show Float
```

7.15.1 Float (FLOAT)



Exports:

0	1	abs	acos
acosh	acot	acoth	acsc
acsch	asec	asech	asin
asinh	associates?	atan	atanh
base	bits	ceiling	characteristic
coerce	convert	cos	cosh
cot	coth	csc	csch
D	decreasePrecision	differentiate	digits
divide	euclideanSize	exp	expressIdealMember
exp1	exponent	exquo	extendedEuclidean
factor	float	floor	fractionPart
gcd	gcdPolynomial	hash	increasePrecision
inv	latex	lcm	log
log10	log2	mantissa	max
min	multiEuclidean	negative?	norm
normalize	nthRoot	OMwrite	one?
order	outputFixed	outputFloating	outputGeneral
outputSpacing	patternMatch	pi	positive?
precision	prime?	principalIdeal	rationalApproximation
recip	relerror	retract	retractIfCan
round	sample	sec	sech
shift	sign	sin	sinh
sizeLess?	sqrt	squareFree	squareFreePart
subtractIfCan	tan	tanh	truncate
unit?	unitCanonical	unitNormal	wholePart
zero?	?*?	?**?	?+?
?-?	-?	?/?	?<?
?<=?	?=?	?>?	?>=?
?^?	?~=?	?quo?	?rem?

— domain FLOAT Float —

```
)abbrev domain FLOAT Float

B ==> Boolean
I ==> Integer
S ==> String
PI ==> PositiveInteger
RN ==> Fraction Integer
SF ==> DoubleFloat
N ==> NonNegativeInteger

++ Author: Michael Monagan
++ Date Created:
++   December 1987
++ Change History:
```

```
++   19 Jun 1990
++ Basic Operations: outputFloating, outputFixed, outputGeneral, outputSpacing,
++   atan, convert, exp1, log2, log10, normalize, rationalApproximation,
++   relerror, shift, / , **
++ Keywords: float, floating point, number
++ Description:
++ \spadtype{Float} implements arbitrary precision floating point arithmetic.
++ The number of significant digits of each operation can be set
++ to an arbitrary value (the default is 20 decimal digits).
++ The operation \spad{float(mantissa,exponent,base)} for integer
++ \spad{mantissa}, \spad{exponent} specifies the number
++ \spad{mantissa * base ** exponent}
++ The underlying representation for floats is binary
++ not decimal. The implications of this are described below.
++
++ The model adopted is that arithmetic operations are rounded to
++ to nearest unit in the last place, that is, accurate to within
++ \spad{2**(-bits)}. Also, the elementary functions and constants are
++ accurate to one unit in the last place.
++ A float is represented as a record of two integers, the mantissa
++ and the exponent.  The base of the representation is binary, hence
++ a \spad{Record(m:mantissa,e:exponent)} represents the number
++ \spad{m * 2 ** e}.
++ Though it is not assumed that the underlying integers are represented
++ with a binary base, the code will be most efficient when this is the
++ the case (this is true in most implementations of Lisp).
++ The decision to choose the base to be binary has some unfortunate
++ consequences.  First, decimal numbers like 0.3 cannot be represented
++ exactly.  Second, there is a further loss of accuracy during
++ conversion to decimal for output.  To compensate for this, if d
++ digits of precision are specified, \spad{1 + ceiling(log2 d)} bits are used.
++ Two numbers that are displayed identically may therefore be
++ not equal.  On the other hand, a significant efficiency loss would
++ be incurred if we chose to use a decimal base when the underlying
++ integer base is binary.
++
++ Algorithms used:
++ For the elementary functions, the general approach is to apply
++ identities so that the taylor series can be used, and, so
++ that it will converge within \spad{O( sqrt n )} steps.  For example,
++ using the identity \spad{exp(x) = exp(x/2)**2}, we can compute
++ \spad{exp(1/3)} to n digits of precision as follows.  We have
++ \spad{exp(1/3) = exp(2 ** (-sqrt s) / 3) ** (2 ** sqrt s)}.
++ The taylor series will converge in less than sqrt n steps and the
++ exponentiation requires sqrt n multiplications for a total of
++ \spad{2 sqrt n} multiplications.  Assuming integer multiplication costs
++ \spad{O( n**2 )} the overall running time is \spad{O( sqrt(n) n**2 )}.
++ This approach is the best known approach for precisions up to
++ about 10,000 digits at which point the methods of Brent
++ which are \spad{O( log(n) n**2 )} become competitive.  Note also that
```

```
++ summing the terms of the taylor series for the elementary
++ functions is done using integer operations.  This avoids the
++ overhead of floating point operations and results in efficient
++ code at low precisions.  This implementation makes no attempt
++ to reuse storage, relying on the underlying system to do
++ \spadgloss{garbage collection}.  I estimate that the efficiency of this
++ package at low precisions could be improved by a factor of 2
++ if in-place operations were available.
++
++ Running times: in the following, n is the number of bits of precision\br
++ \spad{*}, \spad{/}, \spad{sqrt}, \spad{pi}, \spad{exp1}, \spad{log2},
++ \spad{log10}: \spad{ O( n**2 )} \br
++ \spad{exp}, \spad{log}, \spad{sin}, \spad{atan}: \spad{O(sqrt(n) n**2)}\br
++ The other elementary functions are coded in terms of the ones above.

Float():
 Join(FloatingPointSystem, DifferentialRing, ConvertibleTo String, OpenMath,_
  CoercibleTo DoubleFloat, TranscendentalFunctionCategory, ConvertibleTo InputForm) with
   _/  : (%, I) -> %
      ++ x / i computes the division from x by an integer i.
   _*_*: (%, %) -> %
      ++ x ** y computes \spad{exp(y log x)} where \spad{x >= 0}.
   normalize: % -> %
      ++ normalize(x) normalizes x at current precision.
   relerror : (%, %) -> I
      ++ relerror(x,y) computes the absolute value of \spad{x - y} divided by
      ++ y, when \spad{y \^= 0}.
   shift: (%, I) -> %
      ++ shift(x,n) adds n to the exponent of float x.
   rationalApproximation: (%, N) -> RN
     ++ rationalApproximation(f, n) computes a rational approximation
     ++ r to f with relative error \spad{< 10**(-n)}.
   rationalApproximation: (%, N, N) -> RN
     ++ rationalApproximation(f, n, b) computes a rational
     ++ approximation r to f with relative error \spad{< b**(-n)}, that is
     ++ \spad{|(r-f)/f| < b**(-n)}.
   log2 : () -> %
      ++ log2() returns \spad{ln 2}, i.e. \spad{0.6931471805...}.
   log10: () -> %
      ++ log10() returns \spad{ln 10}: \spad{2.3025809299...}.
   exp1 : () -> %
      ++ exp1() returns  exp 1: \spad{2.7182818284...}.
   atan : (%,%) -> %
      ++ atan(x,y) computes the arc tangent from x with phase y.
   log2 : % -> %
      ++ log2(x) computes the logarithm for x to base 2.
   log10: % -> %
      ++ log10(x) computes the logarithm for x to base 10.
   convert: SF -> %
      ++ convert(x) converts a \spadtype{DoubleFloat} x to a \spadtype{Float}.
```

```
  outputFloating: () -> Void
     ++ outputFloating() sets the output mode to floating (scientific) notation, i.e.
     ++ \spad{mantissa * 10 exponent} is displayed as  \spad{0.mantissa E exponent}.
  outputFloating: N -> Void
     ++ outputFloating(n) sets the output mode to floating (scientific) notation
     ++ with n significant digits displayed after the decimal point.
  outputFixed: () -> Void
     ++ outputFixed() sets the output mode to fixed point notation;
     ++ the output will contain a decimal point.
  outputFixed: N -> Void
     ++ outputFixed(n) sets the output mode to fixed point notation,
     ++ with n digits displayed after the decimal point.
  outputGeneral: () -> Void
     ++ outputGeneral() sets the output mode (default mode) to general
     ++ notation; numbers will be displayed in either fixed or floating
     ++ (scientific) notation depending on the magnitude.
  outputGeneral: N -> Void
     ++ outputGeneral(n) sets the output mode to general notation
     ++ with n significant digits displayed.
  outputSpacing: N -> Void
     ++ outputSpacing(n) inserts a space after n (default 10) digits on output;
     ++ outputSpacing(0) means no spaces are inserted.
  arbitraryPrecision
  arbitraryExponent
 == add
  BASE ==> 2
  BITS:Reference(PI) := ref 68 -- 20 digits
  LENGTH ==> INTEGER_-LENGTH$Lisp
  ISQRT ==> approxSqrt$IntegerRoots(I)
  Rep := Record( mantissa:I, exponent:I )
  StoredConstant ==> Record( precision:PI, value:% )
  UCA ==> Record( unit:%, coef:%, associate:% )
  inc ==> increasePrecision
  dec ==> decreasePrecision

  -- local utility operations
  shift2 : (I,I) -> I           -- WSP: fix bug in shift
  times : (%,%) -> %            -- multiply x and y with no rounding
  itimes: (I,%) -> %            -- multiply by a small integer
  chop: (%,PI) -> %             -- chop x at p bits of precision
  dvide: (%,%) -> %             -- divide x by y with no rounding
  square: (%,I) -> %            -- repeated squaring with chopping
  power: (%,I) -> %             -- x ** n with chopping
  plus: (%,%) -> %              -- addition with no rounding
  sub: (%,%) -> %               -- subtraction with no rounding
  negate: % -> %                -- negation with no rounding
  ceillog10base2: PI -> PI      -- rational approximation
  floorln2: PI -> PI            -- rational approximation

  atanSeries: % -> %            -- atan(x) by taylor series |x| < 1/2
```

```
   atanInverse: I -> %           -- atan(1/n) for n an integer > 1
   expInverse: I -> %            -- exp(1/n) for n an integer
   expSeries: % -> %             -- exp(x) by taylor series  |x| < 1/2
   logSeries: % -> %             -- log(x) by taylor series 1/2 < x < 2
   sinSeries: % -> %             -- sin(x) by taylor series |x| < 1/2
   cosSeries: % -> %             -- cos(x) by taylor series |x| < 1/2
   piRamanujan: () -> %          -- pi using Ramanujans series

   writeOMFloat(dev: OpenMathDevice, x: %): Void ==
      OMputApp(dev)
      OMputSymbol(dev, "bigfloat1", "bigfloat")
      OMputInteger(dev, mantissa x)
      OMputInteger(dev, 2)
      OMputInteger(dev, exponent x)
      OMputEndApp(dev)

   OMwrite(x: %): String ==
      s: String := ""
      sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
      dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
      OMputObject(dev)
      writeOMFloat(dev, x)
      OMputEndObject(dev)
      OMclose(dev)
      s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
      s

   OMwrite(x: %, wholeObj: Boolean): String ==
      s: String := ""
      sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
      dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
      if wholeObj then
         OMputObject(dev)
      writeOMFloat(dev, x)
      if wholeObj then
         OMputEndObject(dev)
      OMclose(dev)
      s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
      s

   OMwrite(dev: OpenMathDevice, x: %): Void ==
      OMputObject(dev)
      writeOMFloat(dev, x)
      OMputEndObject(dev)

   OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
      if wholeObj then
         OMputObject(dev)
      writeOMFloat(dev, x)
      if wholeObj then
```

```
        OMputEndObject(dev)

   shift2(x,y) == sign(x)*shift(sign(x)*x,y)

   asin x ==
      zero? x => 0
      negative? x => -asin(-x)
--      one? x => pi()/2
      (x = 1) => pi()/2
      x > 1 => error "asin: argument > 1 in magnitude"
      inc 5; r := atan(x/sqrt(sub(1,times(x,x)))); dec 5
      normalize r

   acos x ==
      zero? x => pi()/2
      negative? x => (inc 3; r := pi()-acos(-x); dec 3; normalize r)
--      one? x => 0
      (x = 1) => 0
      x > 1 => error "acos: argument > 1 in magnitude"
      inc 5; r := atan(sqrt(sub(1,times(x,x)))/x); dec 5
      normalize r

   atan(x,y) ==
      x = 0 =>
         y > 0 => pi()/2
         y < 0 => -pi()/2
         0
      -- Only count on first quadrant being on principal branch.
      theta := atan abs(y/x)
      if x < 0 then theta := pi() - theta
      if y < 0 then theta := - theta
      theta

   atan x ==
      zero? x => 0
      negative? x => -atan(-x)
      if x > 1 then
         inc 4
         r := if zero? fractionPart x and x < [bits(),0] then atanInverse wholePart x
                 else atan(1/x)
         r := pi/2 - r
         dec 4
         return normalize r
      -- make |x| < 0( 2**(-sqrt p) ) < 1/2 to speed series convergence
      -- by using the formula  atan(x) = 2*atan(x/(1+sqrt(1+x**2)))
      k := ISQRT (bits()-100)::I quo 5
      k := max(0,2 + k + order x)
      inc(2*k)
      for i in 1..k repeat x := x/(1+sqrt(1+x*x))
      t := atanSeries x
```

```
      dec(2*k)
      t := shift(t,k)
      normalize t

   atanSeries x ==
      -- atan(x) = x (1 - x**2/3 + x**4/5 - x**6/7 + ...)  |x| < 1
      p := bits() + LENGTH bits() + 2
      s:I := d:I := shift(1,p)
      y := times(x,x)
      t := m := - shift2(y.mantissa,y.exponent+p)
      for i in 3.. by 2 while t ^= 0 repeat
         s := s + t quo i
         t := (m * t) quo d
      x * [s,-p]

   atanInverse n ==
      -- compute atan(1/n) for an integer n > 1
      -- atan n = 1/n - 1/n**3/3 + 1/n**5/4 - ...
      --   pi = 16 atan(1/5) - 4 atan(1/239)
      n2 := -n*n
      e:I := bits() + LENGTH bits() + LENGTH n + 1
      s:I := shift(1,e) quo n
      t:I := s quo n2
      for k in 3.. by 2 while t ^= 0 repeat
         s := s + t quo k
         t := t quo n2
      normalize [s,-e]

   sin x ==
      s := sign x; x := abs x; p := bits(); inc 4
      if x > [6,0] then (inc p; x := 2*pi*fractionPart(x/pi/2); bits p)
      if x > [3,0] then (inc p; s := -s; x := x - pi; bits p)
      if x > [3,-1] then (inc p; x := pi - x; dec p)
      -- make |x| < 0( 2**(-sqrt p) ) < 1/2 to speed series convergence
      -- by using the formula  sin(3*x/3) = 3 sin(x/3) - 4 sin(x/3)**3
      -- the running time is 0( sqrt p M(p) ) assuming |x| < 1
      k := ISQRT (bits()-100)::I quo 4
      k := max(0,2 + k + order x)
      if k > 0 then (inc k; x := x / 3**k::N)
      r := sinSeries x
      for i in 1..k repeat r := itimes(3,r)-shift(r**3,2)
      bits p
      s * r

   sinSeries x ==
      -- sin(x) = x (1 - x**2/3! + x**4/5! - x**6/7! + ... |x| < 1/2
      p := bits() + LENGTH bits() + 2
      y := times(x,x)
      s:I := d:I := shift(1,p)
      m:I := - shift2(y.mantissa,y.exponent+p)
```

```
    t:I := m quo 6
    for i in 4.. by 2 while t ^= 0 repeat
       s := s + t
       t := (m * t) quo (i*(i+1))
       t := t quo d
    x * [s,-p]

cos x ==
  s:I := 1; x := abs x; p := bits(); inc 4
  if x > [6,0] then (inc p; x := 2*pi*fractionPart(x/pi/2); dec p)
  if x > [3,0] then (inc p; s := -s; x := x-pi; dec p)
  if x > [1,0] then
      -- take care of the accuracy problem near pi/2
      inc p; x := pi/2-x; bits p; x := normalize x
      return (s * sin x)
   -- make |x| < 0( 2**(-sqrt p) ) < 1/2 to speed series convergence
   -- by using the formula  cos(2*x/2) = 2 cos(x/2)**2 - 1
   -- the running time is 0( sqrt p M(p) ) assuming |x| < 1
  k := ISQRT (bits()-100)::I quo 3
  k := max(0,2 + k + order x)
   -- need to increase precision by more than k, otherwise recursion
   -- causes loss of accuracy.
   -- Michael Monagan suggests adding a factor of log(k)
  if k > 0 then (inc(k+length(k)**2); x := shift(x,-k))
  r := cosSeries x
  for i in 1..k repeat r := shift(r*r,1)-1
  bits p
  s * r



cosSeries x ==
   -- cos(x) = 1 - x**2/2! + x**4/4! - x**6/6! + ... |x| < 1/2
   p := bits() + LENGTH bits() + 1
   y := times(x,x)
   s:I := d:I := shift(1,p)
   m:I := - shift2(y.mantissa,y.exponent+p)
   t:I := m quo 2
   for i in 3.. by 2 while t ^= 0 repeat
      s := s + t
      t := (m * t) quo (i*(i+1))
      t := t quo d
   normalize [s,-p]

tan x ==
   s := sign x; x := abs x; p := bits(); inc 6
   if x > [3,0] then (inc p; x := pi()*fractionPart(x/pi()); dec p)
   if x > [3,-1] then (inc p; x := pi()-x; s := -s; dec p)
   if x > 1 then (c := cos x; t := sqrt(1-c*c)/c)
   else (c := sin x; t := c/sqrt(1-c*c))
```

```
      bits p
      s * t

   P:StoredConstant := [1,[1,2]]
   pi() ==
      -- We use Ramanujan's identity to compute pi.
      -- The running time is quadratic in the precision.
      -- This is about twice as fast as Machin's identity on Lisp/VM
      --   pi = 16 atan(1/5) - 4 atan(1/239)
      bits() <= P.precision => normalize P.value
      (P := [bits(), piRamanujan()]) value

   piRamanujan() ==
      -- Ramanujans identity for 1/pi
      -- Reference: Shanks and Wrench, Math Comp, 1962
      -- "Calculation of pi to 100,000 Decimals".
      n := bits() + LENGTH bits() + 11
      t:I := shift(1,n) quo 882
      d:I := 4*882**2
      s:I := 0
      for i in 2.. by 2 for j in 1123.. by 21460 while t ^= 0 repeat
         s := s + j*t
         m := -(i-1)*(2*i-1)*(2*i-3)
         t := (m*t) quo (d*i**3)
      1 / [s,-n-2]

   sinh x ==
      zero? x => 0
      lost:I := max(- order x,0)
      2*lost > bits() => x
      inc(5+lost); e := exp x; s := (e-1/e)/2; dec(5+lost)
      normalize s

   cosh x ==
      (inc 5; e := exp x; c := (e+1/e)/2; dec 5; normalize c)

   tanh x ==
      zero? x => 0
      lost:I := max(- order x,0)
      2*lost > bits() => x
      inc(6+lost); e := exp x; e := e*e; t := (e-1)/(e+1); dec(6+lost)
      normalize t

   asinh x ==
      p := min(0,order x)
      if zero? x or 2*p < -bits() then return x
      inc(5-p); r := log(x+sqrt(1+x*x)); dec(5-p)
      normalize r

   acosh x ==
```

```
      if x < 1 then error "invalid argument to acosh"
      inc 5; r := log(x+sqrt(sub(times(x,x),1))); dec 5
      normalize r

   atanh x ==
      if x > 1 or x < -1 then error "invalid argument to atanh"
      p := min(0,order x)
      if zero? x or 2*p < -bits() then return x
      inc(5-p); r := log((x+1)/(1-x))/2; dec(5-p)
      normalize r

   log x ==
      negative? x => error "negative log"
      zero? x => error "log 0 generated"
      p := bits(); inc 5
      -- apply  log(x) = n log 2 + log(x/2**n)  so that  1/2 < x < 2
      if (n := order x) < 0 then n := n+1
      l := if n = 0 then 0 else (x := shift(x,-n); n * log2)
      -- speed the series convergence by finding m and k such that
      -- | exp(m/2**k) x - 1 |  <  1 / 2 ** O(sqrt p)
      -- write  log(exp(m/2**k) x) as m/2**k + log x
      k := ISQRT (p-100)::I quo 3
      if k > 1 then
         k := max(1,k+order(x-1))
         inc k
         ek := expInverse (2**k::N)
         dec(p quo 2); m := order square(x,k); inc(p quo 2)
         m := (6847196937 * m) quo 9878417065   -- m := m log 2
         x := x * ek ** (-m)
         l := l + [m,-k]
      l := l + logSeries x
      bits p
      normalize l

   logSeries x ==
      -- log(x) = 2 y (1 + y**2/3 + y**4/5 ...)  for  y = (x-1) / (x+1)
      -- given 1/2 < x < 2 on input we have -1/3 < y < 1/3
      p := bits() + (g := LENGTH bits() + 3)
      inc g; y := (x-1)/(x+1); dec g
      s:I := d:I := shift(1,p)
      z := times(y,y)
      t := m := shift2(z.mantissa,z.exponent+p)
      for i in 3.. by 2 while t ^= 0 repeat
         s := s + t quo i
         t := m * t quo d
      y * [s,1-p]

   L2:StoredConstant := [1,1]
   log2() ==
      --  log x  =  2 * sum( ((x-1)/(x+1))**(2*k+1)/(2*k+1), k=1.. )
```

```
      --  log 2  =  2 * sum( 1/9**k / (2*k+1), k=0..n ) / 3
      n := bits() :: N
      n <= L2.precision => normalize L2.value
      n := n + LENGTH n + 3  -- guard bits
      s:I := shift(1,n+1) quo 3
      t:I := s quo 9
      for k in 3.. by 2 while t ^= 0 repeat
         s := s + t quo k
         t := t quo 9
      L2 := [bits(),[s,-n]]
      normalize L2.value

   L10:StoredConstant := [1,[1,1]]
   log10() ==
      --  log x  =  2 * sum( ((x-1)/(x+1))**(2*k+1)/(2*k+1), k=0.. )
      --  log 5/4  =  2 * sum( 1/81**k / (2*k+1), k=0.. ) / 9
      n := bits() :: N
      n <= L10.precision => normalize L10.value
      n := n + LENGTH n + 5  -- guard bits
      s:I := shift(1,n+1) quo 9
      t:I := s quo 81
      for k in 3.. by 2 while t ^= 0 repeat
         s := s + t quo k
         t := t quo 81
      -- We have log 10 = log 5 + log 2 and log 5/4 = log 5 - 2 log 2
      inc 2; L10 := [bits(),[s,-n] + 3*log2]; dec 2
      normalize L10.value

   log2(x) == (inc 2; r := log(x)/log2; dec 2; normalize r)
   log10(x) == (inc 2; r := log(x)/log10; dec 2; normalize r)

   exp(x) ==
      -- exp(n+x) = exp(1)**n exp(x) for n such that |x| < 1
      p := bits(); inc 5; e1:% := 1
      if (n := wholePart x) ^= 0 then
         inc LENGTH n; e1 := exp1 ** n; dec LENGTH n
         x := fractionPart x
      if zero? x then (bits p; return normalize e1)
      -- make |x| < O( 2**(-sqrt p) ) < 1/2 to speed series convergence
      -- by repeated use of the formula exp(2*x/2) = exp(x/2)**2
      -- results in an overall running time of O( sqrt p M(p) )
      k := ISQRT (p-100)::I quo 3
      k := max(0,2 + k + order x)
      if k > 0 then (inc k; x := shift(x,-k))
      e := expSeries x
      if k > 0 then e := square(e,k)
      bits p
      e * e1

   expSeries x ==
```

```
      -- exp(x) = 1 + x + x**2/2 + ... + x**i/i!  valid for all x
      p := bits() + LENGTH bits() + 1
      s:I := d:I := shift(1,p)
      t:I := n:I := shift2(x.mantissa,x.exponent+p)
      for i in 2.. while t ^= 0 repeat
         s := s + t
         t := (n * t) quo i
         t := t quo d
      normalize [s,-p]

   expInverse k ==
      -- computes exp(1/k) via continued fraction
      p0:I := 2*k+1; p1:I := 6*k*p0+1
      q0:I := 2*k-1; q1:I := 6*k*q0+1
      for i in 10*k.. by 4*k while 2 * LENGTH p0 < bits() repeat
         (p0,p1) := (p1,i*p1+p0)
         (q0,q1) := (q1,i*q1+q0)
      dvide([p1,0],[q1,0])

   E:StoredConstant := [1,[1,1]]
   exp1() ==
      if bits() > E.precision then E := [bits(),expInverse 1]
      normalize E.value

   sqrt x ==
      negative? x => error "negative sqrt"
      m := x.mantissa; e := x.exponent
      l := LENGTH m
      p := 2 * bits() - l + 2
      if odd?(e-l) then p := p - 1
      i := shift2(x.mantissa,p)
      -- ISQRT uses a variable precision newton iteration
      i := ISQRT i
      normalize [i,(e-p) quo 2]

   bits() == BITS()
   bits(n) == (t := bits(); BITS() := n; t)
   precision() == bits()
   precision(n) == bits(n)
   increasePrecision n == (b := bits(); bits((b + n)::PI); b)
   decreasePrecision n == (b := bits(); bits((b - n)::PI); b)
   ceillog10base2 n == ((13301 * n + 4003) quo 4004) :: PI
   digits() == max(1,4004 * (bits()-1) quo 13301)::PI
   digits(n) == (t := digits(); bits (1 + ceillog10base2 n); t)

   order(a) == LENGTH a.mantissa + a.exponent - 1
   relerror(a,b) == order((a-b)/b)
   0 == [0,0]
   1 == [1,0]
   base() == BASE
```

```
mantissa x == x.mantissa
exponent x == x.exponent
one? a == a = 1
zero? a == zero?(a.mantissa)
negative? a == negative?(a.mantissa)
positive? a == positive?(a.mantissa)

chop(x,p) ==
   e : I := LENGTH x.mantissa - p
   if e > 0 then x := [shift2(x.mantissa,-e),x.exponent+e]
   x
float(m,e) == normalize [m,e]
float(m,e,b) ==
   m = 0 => 0
   inc 4; r := m * [b,0] ** e; dec 4
   normalize r
normalize x ==
   m := x.mantissa
   m = 0 => 0
   e : I := LENGTH m - bits()
   if e > 0 then
      y := shift2(m,1-e)
      if odd? y then
         y := (if y>0 then y+1 else y-1) quo 2
         if LENGTH y > bits() then
            y := y quo 2
            e := e+1
      else y := y quo 2
      x := [y,x.exponent+e]
   x
shift(x:%,n:I) == [x.mantissa,x.exponent+n]

x = y ==
   order x = order y and sign x = sign y and zero? (x - y)
x < y ==
   y.mantissa = 0 => x.mantissa < 0
   x.mantissa = 0 => y.mantissa > 0
   negative? x and positive? y => true
   negative? y and positive? x => false
   order x < order y => positive? x
   order x > order y => negative? x
   negative? (x-y)

abs x == if negative? x then -x else normalize x
ceiling x ==
   if negative? x then return (-floor(-x))
   if zero? fractionPart x then x else truncate x + 1
wholePart x == shift2(x.mantissa,x.exponent)
floor x == if negative? x then -ceiling(-x) else truncate x
round x == (half := [sign x,-1]; truncate(x + half))
```

```
sign x == if x.mantissa < 0 then -1 else 1
truncate x ==
   if x.exponent >= 0 then return x
   normalize [shift2(x.mantissa,x.exponent),0]
recip(x) == if x=0 then "failed" else 1/x
differentiate x == 0

- x == normalize negate x
negate x == [-x.mantissa,x.exponent]
x + y == normalize plus(x,y)
x - y == normalize plus(x,negate y)
sub(x,y) == plus(x,negate y)
plus(x,y) ==
   mx := x.mantissa; my := y.mantissa
   mx = 0 => y
   my = 0 => x
   ex := x.exponent; ey := y.exponent
   ex = ey => [mx+my,ex]
   de := ex + LENGTH mx - ey - LENGTH my
   de > bits()+1 => x
   de < -(bits()+1) => y
   if ex < ey then (mx,my,ex,ey) := (my,mx,ey,ex)
   mw := my + shift2(mx,ex-ey)
   [mw,ey]

x:% * y:% == normalize times (x,y)
x:I * y:% ==
   if LENGTH x > bits() then normalize [x,0] * y
   else normalize [x * y.mantissa,y.exponent]
x:% / y:% == normalize dvide(x,y)
x:% / y:I ==
   if LENGTH y > bits() then x / normalize [y,0] else x / [y,0]
inv x == 1 / x

times(x:%,y:%) == [x.mantissa * y.mantissa, x.exponent + y.exponent]
itimes(n:I,y:%) == [n * y.mantissa,y.exponent]

dvide(x,y) ==
   ew := LENGTH y.mantissa - LENGTH x.mantissa + bits() + 1
   mw := shift2(x.mantissa,ew) quo y.mantissa
   ew := x.exponent - y.exponent - ew
   [mw,ew]

square(x,n) ==
   ma := x.mantissa; ex := x.exponent
   for k in 1..n repeat
      ma := ma * ma; ex := ex + ex
      l:I := bits()::I - LENGTH ma
      ma := shift2(ma,l); ex := ex - l
   [ma,ex]
```

```
power(x,n) ==
   y:% := 1; z:% := x
   repeat
      if odd? n then y := chop( times(y,z), bits() )
      if (n := n quo 2) = 0 then return y
      z := chop( times(z,z), bits() )

x:% ** y:% ==
   x = 0 =>
      y = 0 => error "0**0 is undefined"
      y < 0 => error "division by 0"
      y > 0 => 0
   y = 0 => 1
   y = 1 => x
   x = 1 => 1
   p := abs order y + 5
   inc p; r := exp(y*log(x)); dec p
   normalize r

x:% ** r:RN ==
   x = 0 =>
      r = 0 => error "0**0 is undefined"
      r < 0 => error "division by 0"
      r > 0 => 0
   r = 0 => 1
   r = 1 => x
   x = 1 => 1
   n := numer r
   d := denom r
   negative? x =>
      odd? d =>
         odd? n => return -((-x)**r)
         return ((-x)**r)
      error "negative root"
   if d = 2 then
      inc LENGTH n; y := sqrt(x); y := y**n; dec LENGTH n
      return normalize y
   y := [n,0]/[d,0]
   x ** y

x:% ** n:I ==
   x = 0 =>
      n = 0 => error "0**0 is undefined"
      n < 0 => error "division by 0"
      n > 0 => 0
   n = 0 => 1
   n = 1 => x
   x = 1 => 1
   p := bits()
```

```
      bits(p + LENGTH n + 2)
      y := power(x,abs n)
      if n < 0 then y := dvide(1,y)
      bits p
      normalize y

   -- Utility routines for conversion to decimal
   ceilLength10: I -> I
   chop10: (%,I) -> %
   convert10:(%,I) -> %
   floorLength10: I -> I
   length10: I -> I
   normalize10: (%,I) -> %
   quotient10: (%,%,I) -> %
   power10: (%,I,I) -> %
   times10: (%,%,I) -> %

   convert10(x,d) ==
      m := x.mantissa; e := x.exponent
      --!! deal with bits here
      b := bits(); (q,r) := divide(abs e, b)
      b := 2**b::N; r := 2**r::N
      -- compute 2**e = b**q * r
      h := power10([b,0],q,d+5)
      h := chop10([r*h.mantissa,h.exponent],d+5)
      if e < 0 then h := quotient10([m,0],h,d)
      else times10([m,0],h,d)

   ceilLength10 n == 146 * LENGTH n quo 485 + 1
   floorLength10 n == 643 *  LENGTH n quo 2136
--   length10 n == DECIMAL_-LENGTH(n)$Lisp
   length10 n ==
      ln := LENGTH(n:=abs n)
      upper := 76573 * ln quo 254370
      lower := 21306 * (ln-1) quo 70777
      upper = lower => upper + 1
      n := n quo (10**lower::N)
      while n >= 10 repeat
         n:= n quo 10
         lower := lower + 1
      lower + 1

   chop10(x,p) ==
      e : I := floorLength10 x.mantissa - p
      if e > 0 then x := [x.mantissa quo 10**e::N,x.exponent+e]
      x
   normalize10(x,p) ==
      ma := x.mantissa
      ex := x.exponent
      e : I := length10 ma - p
```

```
      if e > 0 then
         ma := ma quo 10**(e-1)::N
         ex := ex + e
         (ma,r) := divide(ma, 10)
         if r > 4 then
            ma := ma + 1
            if ma = 10**p::N then (ma := 1; ex := ex + p)
      [ma,ex]
   times10(x,y,p) == normalize10(times(x,y),p)
   quotient10(x,y,p) ==
      ew := floorLength10 y.mantissa - ceilLength10 x.mantissa + p + 2
      if ew < 0 then ew := 0
      mw := (x.mantissa * 10**ew::N) quo y.mantissa
      ew := x.exponent - y.exponent - ew
      normalize10([mw,ew],p)
   power10(x,n,d) ==
      x = 0 => 0
      n = 0 => 1
      n = 1 => x
      x = 1 => 1
      p:I := d + LENGTH n + 1
      e:I := n
      y:% := 1
      z:% := x
      repeat
         if odd? e then y := chop10(times(y,z),p)
         if (e := e quo 2) = 0 then return y
         z := chop10(times(z,z),p)

   --------------------------------
   -- Output routines for Floats --
   --------------------------------
   zero ==> char("0")
   separator ==> space()$Character

   SPACING : Reference(N) := ref 10
   OUTMODE : Reference(S) := ref "general"
   OUTPREC : Reference(I) := ref(-1)

   fixed : % -> S
   floating : % -> S
   general : % -> S

   padFromLeft(s:S):S ==
      zero? SPACING() => s
      n:I := #s - 1
      t := new( (n + 1 + n quo SPACING()) :: N , separator )
      for i in 0..n for j in minIndex t .. repeat
         t.j := s.(i + minIndex s)
         if (i+1) rem SPACING() = 0 then j := j+1
```

```
      t
   padFromRight(s:S):S ==
      SPACING() = 0 => s
      n:I := #s - 1
      t := new( (n + 1 + n quo SPACING()) :: N , separator )
      for i in n..0 by -1 for j in maxIndex t .. by -1 repeat
         t.j := s.(i + minIndex s)
         if (n-i+1) rem SPACING() = 0 then j := j-1
      t

   fixed f ==
      d := if OUTPREC() = -1 then digits::I else OUTPREC()
      dpos:N:= if (d > 0) then d::N else 1::N
      zero? f =>
        OUTPREC() = -1 => "0.0"
        concat("0",concat(".",padFromLeft new(dpos,zero)))
      zero? exponent f =>
        concat(padFromRight convert(mantissa f)@S,
               concat(".",padFromLeft new(dpos,zero)))
      negative? f => concat("-", fixed abs f)
      bl := LENGTH(f.mantissa) + f.exponent
      dd :=
        OUTPREC() = -1 => d
        bl > 0 => (146*bl) quo 485 + 1 + d
        d
      g := convert10(abs f,dd)
      m := g.mantissa
      e := g.exponent
      if OUTPREC() ^= -1 then
         -- round g to OUTPREC digits after the decimal point
         l := length10 m
         if -e > OUTPREC() and -e < 2*digits::I then
            g := normalize10(g,l+e+OUTPREC())
            m := g.mantissa; e := g.exponent
      s := convert(m)@S; n := #s; o := e+n
      p := if OUTPREC() = -1 then n::I else OUTPREC()
      t:S
      if e >= 0 then
         s := concat(s, new(e::N, zero))
         t := ""
      else if o <= 0 then
         t := concat(new((-o)::N,zero), s)
         s := "0"
      else
         t := s(o + minIndex s .. n + minIndex s - 1)
         s := s(minIndex s .. o + minIndex s - 1)
      n := #t
      if OUTPREC() = -1 then
         t := rightTrim(t,zero)
         if t = "" then t := "0"
```

```
      else if n > p then t := t(minIndex t .. p + minIndex t- 1)
                    else t := concat(t, new((p-n)::N,zero))
      concat(padFromRight s, concat(".", padFromLeft t))

   floating f ==
      zero? f => "0.0"
      negative? f => concat("-", floating abs f)
      t:S := if zero? SPACING() then "E" else " E "
      zero? exponent f =>
        s := convert(mantissa f)@S
        concat ["0.", padFromLeft s, t, convert(#s)@S]
      -- base conversion to decimal rounded to the requested precision
      d := if OUTPREC() = -1 then digits::I else OUTPREC()
      g := convert10(f,d); m := g.mantissa; e := g.exponent
      -- I'm assuming that length10 m = # s given n > 0
      s := convert(m)@S; n := #s; o := e+n
      s := padFromLeft s
      concat ["0.", s, t, convert(o)@S]

   general(f) ==
      zero? f => "0.0"
      negative? f => concat("-", general abs f)
      d := if OUTPREC() = -1 then digits::I else OUTPREC()
      zero? exponent f =>
        d := d + 1
        s := convert(mantissa f)@S
        OUTPREC() ^= -1 and (e := #s) > d =>
          t:S := if zero? SPACING() then "E" else " E "
          concat ["0.", padFromLeft s, t, convert(e)@S]
        padFromRight concat(s, ".0")
      -- base conversion to decimal rounded to the requested precision
      g := convert10(f,d); m := g.mantissa; e := g.exponent
      -- I'm assuming that length10 m = # s given n > 0
      s := convert(m)@S; n := #s; o := n + e
      -- Note: at least one digit is displayed after the decimal point
      -- and trailing zeroes after the decimal point are dropped
      if o > 0 and o <= max(n,d) then
         -- fixed format: add trailing zeroes before the decimal point
         if o > n then s := concat(s, new((o-n)::N,zero))
         t := rightTrim(s(o + minIndex s .. n + minIndex s - 1), zero)
         if t = "" then t := "0" else t := padFromLeft t
         s := padFromRight s(minIndex s .. o + minIndex s - 1)
         concat(s, concat(".", t))
      else if o <= 0 and o >= -5 then
         -- fixed format: up to 5 leading zeroes after the decimal point
         concat("0.",padFromLeft concat(new((-o)::N,zero),rightTrim(s,zero)))
      else
         -- print using E format written  0.mantissa E exponent
         t := padFromLeft rightTrim(s,zero)
         s := if zero? SPACING() then "E" else " E "
```

```
      concat ["0.", t, s, convert(e+n)@S]

outputSpacing n == SPACING() := n
outputFixed() == (OUTMODE() := "fixed"; OUTPREC() := -1)
outputFixed n == (OUTMODE() := "fixed"; OUTPREC() := n::I)
outputGeneral() == (OUTMODE() := "general"; OUTPREC() := -1)
outputGeneral n == (OUTMODE() := "general"; OUTPREC() := n::I)
outputFloating() == (OUTMODE() := "floating"; OUTPREC() := -1)
outputFloating n == (OUTMODE() := "floating"; OUTPREC() := n::I)

convert(f):S ==
   b:Integer :=
     OUTPREC() = -1 and not zero? f =>
       bits(length(abs mantissa f)::PositiveInteger)
     0
   s :=
     OUTMODE() = "fixed" => fixed f
     OUTMODE() = "floating" => floating f
     OUTMODE() = "general" => general f
     empty()$String
   if b > 0 then bits(b::PositiveInteger)
   s = empty()$String => error "bad output mode"
   s

coerce(f):OutputForm ==
  f >= 0 => message(convert(f)@S)
  - (coerce(-f)@OutputForm)

convert(f):InputForm ==
  convert [convert("float"::Symbol), convert mantissa f,
           convert exponent f, convert base()]$List(InputForm)

-- Conversion routines
convert(x:%):Float == x pretend Float
convert(x:%):SF == makeSF(x.mantissa,x.exponent)$Lisp
coerce(x:%):SF == convert(x)@SF
convert(sf:SF):% == float(mantissa sf,exponent sf,base()$SF)

retract(f:%):RN == rationalApproximation(f,(bits()-1)::N,BASE)

retractIfCan(f:%):Union(RN, "failed") ==
  rationalApproximation(f,(bits()-1)::N,BASE)

retract(f:%):I ==
  (f = (n := wholePart f)::%) => n
  error "Not an integer"

retractIfCan(f:%):Union(I, "failed") ==
  (f = (n := wholePart f)::%) => n
  "failed"
```

```
   rationalApproximation(f,d) == rationalApproximation(f,d,10)

   rationalApproximation(f,d,b) ==
      t: Integer
      nu := f.mantissa; ex := f.exponent
      if ex >= 0 then return ((nu*BASE**(ex::N))/1)
      de := BASE**((-ex)::N)
      if b < 2 then error "base must be > 1"
      tol := b**d
      s := nu; t := de
      p0,p1,q0,q1 : Integer
      p0 := 0; p1 := 1; q0 := 1; q1 := 0
      repeat
         (q,r) := divide(s, t)
         p2 := q*p1+p0
         q2 := q*q1+q0
         if r = 0 or tol*abs(nu*q2-de*p2) < de*abs(p2) then return (p2/q2)
         (p0,p1) := (p1,p2)
         (q0,q1) := (q1,q2)
         (s,t) := (t,r)
```

———-

— FLOAT.dotabb —

```
"FLOAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLOAT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FLOAT" -> "ALIST"
```

———-

7.16 domain FC FortranCode

— FortranCode.input —

```
)set break resume
)sys rm -f FortranCode.output
)spool FortranCode.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show FortranCode
--R
--R FortranCode  is a domain constructor
--R Abbreviation for FortranCode is FC
--R This constructor is exposed in this frame.
--R Issue )edit NIL to see algebra source code for FC
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                assign : (Symbol,String) -> %
--R block : List(%) -> %                  call : String -> %
--R coerce : % -> OutputForm              comment : List(String) -> %
--R comment : String -> %                 cond : (Switch,%,%) -> %
--R cond : (Switch,%) -> %                continue : SingleInteger -> %
--R getCode : % -> SExpression            goto : SingleInteger -> %
--R hash : % -> SingleInteger             latex : % -> String
--R printCode : % -> Void                 returns : Expression(Float) -> %
--R returns : () -> %                     save : () -> %
--R stop : () -> %                        whileLoop : (Switch,%) -> %
--R ?~=? : (%,%) -> Boolean
--R assign : (Symbol,List(Polynomial(Integer)),Expression(Complex(Float))) -> %
--R assign : (Symbol,List(Polynomial(Integer)),Expression(Float)) -> %
--R assign : (Symbol,List(Polynomial(Integer)),Expression(Integer)) -> %
--R assign : (Symbol,Vector(Expression(Complex(Float)))) -> %
--R assign : (Symbol,Vector(Expression(Float))) -> %
--R assign : (Symbol,Vector(Expression(Integer))) -> %
--R assign : (Symbol,Matrix(Expression(Complex(Float)))) -> %
--R assign : (Symbol,Matrix(Expression(Float))) -> %
--R assign : (Symbol,Matrix(Expression(Integer))) -> %
--R assign : (Symbol,Expression(Complex(Float))) -> %
--R assign : (Symbol,Expression(Float)) -> %
--R assign : (Symbol,Expression(Integer)) -> %
--R assign : (Symbol,List(Polynomial(Integer)),Expression(MachineComplex)) -> %
--R assign : (Symbol,List(Polynomial(Integer)),Expression(MachineFloat)) -> %
--R assign : (Symbol,List(Polynomial(Integer)),Expression(MachineInteger)) -> %
--R assign : (Symbol,Vector(Expression(MachineComplex))) -> %
--R assign : (Symbol,Vector(Expression(MachineFloat))) -> %
--R assign : (Symbol,Vector(Expression(MachineInteger))) -> %
--R assign : (Symbol,Matrix(Expression(MachineComplex))) -> %
--R assign : (Symbol,Matrix(Expression(MachineFloat))) -> %
--R assign : (Symbol,Matrix(Expression(MachineInteger))) -> %
--R assign : (Symbol,Vector(MachineComplex)) -> %
--R assign : (Symbol,Vector(MachineFloat)) -> %
--R assign : (Symbol,Vector(MachineInteger)) -> %
--R assign : (Symbol,Matrix(MachineComplex)) -> %
--R assign : (Symbol,Matrix(MachineFloat)) -> %
--R assign : (Symbol,Matrix(MachineInteger)) -> %
--R assign : (Symbol,Expression(MachineComplex)) -> %
--R assign : (Symbol,Expression(MachineFloat)) -> %
--R assign : (Symbol,Expression(MachineInteger)) -> %
--R code : % -> Union(nullBranch: null,assignmentBranch: Record(var: Symbol,arrayIndex: List(Pol
```

```
--R common : (Symbol,List(Symbol)) -> %
--R forLoop : (SegmentBinding(Polynomial(Integer)),Polynomial(Integer),%) -> %
--R forLoop : (SegmentBinding(Polynomial(Integer)),%) -> %
--R operation : % -> Union(Null: null,Assignment: assignment,Conditional: conditional,Return: return,Block:
--R printStatement : List(OutputForm) -> %
--R repeatUntilLoop : (Switch,%) -> %
--R returns : Expression(Complex(Float)) -> %
--R returns : Expression(Integer) -> %
--R returns : Expression(MachineComplex) -> %
--R returns : Expression(MachineInteger) -> %
--R returns : Expression(MachineFloat) -> %
--R setLabelValue : SingleInteger -> SingleInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FortranCode.help** —

```
=====================================================================
FortranCode examples
=====================================================================

See Also:
o )show FortranCode
```

———-

7.16.1 FortranCode (FC)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266

⇒ "FortranProgram" (FORTRAN) 7.18.1 on page 926
⇒ "ThreeDimensionalMatrix" (M3D) 21.7.1 on page 2671
⇒ "SimpleFortranProgram" (SFORT) 20.11.1 on page 2373
⇒ "Switch" (SWITCH) 20.36.1 on page 2597
⇒ "FortranTemplate" (FTEM) 7.20.1 on page 937
⇒ "FortranExpression" (FEXPR) 7.17.1 on page 917

Exports:

assign	block	call	code	coerce
comment	common	cond	continue	forLoop
getCode	goto	hash	latex	operation
printCode	printStatement	repeatUntilLoop	returns	save
setLabelValue	stop	whileLoop	?=?	? =?

— domain FC FortranCode —

```
)abbrev domain FC FortranCode
++ Author: Mike Dewar
++ Date Created: April 1991
++ Date Last Updated: 22 March 1994
++                    26 May 1994 Added common, MCD
++                    21 June 1994 Changed print to printStatement, MCD
++                    30 June 1994 Added stop, MCD
++                    12 July 1994 Added assign for String, MCD
++                     9 January 1995 Added fortran2Lines to getCall, MCD
++ Basic Operations:
++ Related Constructors: FortranProgram, Switch, FortranType
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain builds representations of program code segments for use with
++ the FortranProgram domain.

FortranCode(): public == private where
  L ==> List
  PI ==> PositiveInteger
  PIN ==> Polynomial Integer
  SEX ==> SExpression
  O ==> OutputForm
  OP ==> Union(Null:"null",
               Assignment:"assignment",
               Conditional:"conditional",
               Return:"return",
               Block:"block",
               Comment:"comment",
               Call:"call",
               For:"for",
               While:"while",
```

```
              Repeat:"repeat",
              Goto:"goto",
              Continue:"continue",
              ArrayAssignment:"arrayAssignment",
              Save:"save",
              Stop:"stop",
              Common:"common",
              Print:"print")
  ARRAYASS ==> Record(var:Symbol, rand:O, ints2Floats?:Boolean)
  EXPRESSION ==> Record(ints2Floats?:Boolean,expr:O)
  ASS ==> Record(var:Symbol,
                 arrayIndex:L PIN,
                 rand:EXPRESSION
                )
  COND ==> Record(switch: Switch(),
                  thenClause: $,
                  elseClause: $
                 )
  RETURN ==> Record(empty?:Boolean,value:EXPRESSION)
  BLOCK ==> List $
  COMMENT ==> List String
  COMMON ==> Record(name:Symbol,contents:List Symbol)
  CALL ==> String
  FOR ==> Record(range:SegmentBinding PIN, span:PIN,  body:$)
  LABEL ==> SingleInteger
  LOOP ==> Record(switch:Switch(),body:$)
  PRINTLIST ==> List O
  OPREC ==> Union(nullBranch:"null", assignmentBranch:ASS,
                  arrayAssignmentBranch:ARRAYASS,
                  conditionalBranch:COND, returnBranch:RETURN,
                  blockBranch:BLOCK, commentBranch:COMMENT, callBranch:CALL,
                  forBranch:FOR, labelBranch:LABEL, loopBranch:LOOP,
                  commonBranch:COMMON, printBranch:PRINTLIST)

  public == SetCategory with
    coerce: $ -> O
      ++ coerce(f) returns an object of type OutputForm.
    forLoop: (SegmentBinding PIN,$) -> $
     ++ forLoop(i=1..10,c) creates a representation of a FORTRAN DO loop with
     ++ \spad{i} ranging over the values 1 to 10.
    forLoop: (SegmentBinding PIN,PIN,$) -> $
     ++ forLoop(i=1..10,n,c) creates a representation of a FORTRAN DO loop with
     ++ \spad{i} ranging over the values 1 to 10 by n.
    whileLoop: (Switch,$) -> $
     ++ whileLoop(s,c) creates a while loop in FORTRAN.
    repeatUntilLoop: (Switch,$) -> $
     ++ repeatUntilLoop(s,c) creates a repeat ... until loop in FORTRAN.
    goto: SingleInteger -> $
      ++ goto(l) creates a representation of a FORTRAN GOTO statement
    continue: SingleInteger -> $
```

```
  ++ continue(l) creates a representation of a FORTRAN CONTINUE labelled
  ++ with l
comment: String -> $
  ++ comment(s) creates a representation of the String s as a single FORTRAN
  ++ comment.
comment: List String -> $
  ++ comment(s) creates a representation of the Strings s as a multi-line
  ++ FORTRAN comment.
call: String -> $
  ++ call(s) creates a representation of a FORTRAN CALL statement
returns: () -> $
  ++ returns() creates a representation of a FORTRAN RETURN statement.
returns: Expression MachineFloat -> $
  ++ returns(e) creates a representation of a FORTRAN RETURN statement
  ++ with a returned value.
returns: Expression MachineInteger -> $
  ++ returns(e) creates a representation of a FORTRAN RETURN statement
  ++ with a returned value.
returns: Expression MachineComplex -> $
  ++ returns(e) creates a representation of a FORTRAN RETURN statement
  ++ with a returned value.
returns: Expression Float -> $
  ++ returns(e) creates a representation of a FORTRAN RETURN statement
  ++ with a returned value.
returns: Expression Integer -> $
  ++ returns(e) creates a representation of a FORTRAN RETURN statement
  ++ with a returned value.
returns: Expression Complex Float -> $
  ++ returns(e) creates a representation of a FORTRAN RETURN statement
  ++ with a returned value.
cond: (Switch,$) -> $
  ++ cond(s,e) creates a representation of the FORTRAN expression
  ++ IF (s) THEN e.
cond: (Switch,$,$) -> $
  ++ cond(s,e,f) creates a representation of the FORTRAN expression
  ++ IF (s) THEN e ELSE f.
assign: (Symbol,String) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Expression MachineInteger) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Expression MachineFloat) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Expression MachineComplex) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Matrix MachineInteger) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
```

```
    ++ x=y.
  assign: (Symbol,Matrix MachineFloat) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Matrix MachineComplex) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Vector MachineInteger) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Vector MachineFloat) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Vector MachineComplex) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Matrix Expression MachineInteger) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Matrix Expression MachineFloat) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Matrix Expression MachineComplex) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Vector Expression MachineInteger) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Vector Expression MachineFloat) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Vector Expression MachineComplex) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,L PIN,Expression MachineInteger) -> $
    ++ assign(x,l,y) creates a representation of the assignment of \spad{y}
    ++ to the \spad{l}'th element of array \spad{x} (\spad{l} is a list of
    ++ indices).
  assign: (Symbol,L PIN,Expression MachineFloat) -> $
    ++ assign(x,l,y) creates a representation of the assignment of \spad{y}
    ++ to the \spad{l}'th element of array \spad{x} (\spad{l} is a list of
    ++ indices).
  assign: (Symbol,L PIN,Expression MachineComplex) -> $
    ++ assign(x,l,y) creates a representation of the assignment of \spad{y}
    ++ to the \spad{l}'th element of array \spad{x} (\spad{l} is a list of
    ++ indices).
  assign: (Symbol,Expression Integer) -> $
    ++ assign(x,y) creates a representation of the FORTRAN expression
    ++ x=y.
  assign: (Symbol,Expression Float) -> $
```

```
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Expression Complex Float) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Matrix Expression Integer) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Matrix Expression Float) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Matrix Expression Complex Float) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Vector Expression Integer) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Vector Expression Float) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,Vector Expression Complex Float) -> $
  ++ assign(x,y) creates a representation of the FORTRAN expression
  ++ x=y.
assign: (Symbol,L PIN,Expression Integer) -> $
  ++ assign(x,l,y) creates a representation of the assignment of \spad{y}
  ++ to the \spad{l}'th element of array \spad{x} (\spad{l} is a list of
  ++ indices).
assign: (Symbol,L PIN,Expression Float) -> $
  ++ assign(x,l,y) creates a representation of the assignment of \spad{y}
  ++ to the \spad{l}'th element of array \spad{x} (\spad{l} is a list of
  ++ indices).
assign: (Symbol,L PIN,Expression Complex Float) -> $
  ++ assign(x,l,y) creates a representation of the assignment of \spad{y}
  ++ to the \spad{l}'th element of array \spad{x} (\spad{l} is a list of
  ++ indices).
block: List($) -> $
  ++ block(l) creates a representation of the statements in l as a block.
stop: () -> $
  ++ stop() creates a representation of a STOP statement.
save: () -> $
  ++ save() creates a representation of a SAVE statement.
printStatement: List O -> $
  ++ printStatement(l) creates a representation of a PRINT statement.
common: (Symbol,List Symbol) -> $
  ++ common(name,contents) creates a representation a named common block.
operation: $ -> OP
  ++ operation(f) returns the name of the operation represented by \spad{f}.
code: $ -> OPREC
  ++ code(f) returns the internal representation of the object represented
  ++ by \spad{f}.
```

```
    printCode: $ -> Void
      ++ printCode(f) prints out \spad{f} in FORTRAN notation.
    getCode: $ -> SEX
      ++ getCode(f) returns a Lisp list of strings representing \spad{f}
      ++ in Fortran notation.  This is used by the FortranProgram domain.
    setLabelValue:SingleInteger -> SingleInteger
      ++ setLabelValue(i) resets the counter which produces labels to i

  private == add
    import Void
    import ASS
    import COND
    import RETURN
    import L PIN
    import O
    import SEX
    import FortranType
    import TheSymbolTable

    Rep := Record(op: OP, data: OPREC)

    -- We need to be able to generate unique labels
    labelValue:SingleInteger := 25000::SingleInteger
    setLabelValue(u:SingleInteger):SingleInteger == labelValue := u
    newLabel():SingleInteger ==
      labelValue := labelValue + 1$SingleInteger
      labelValue

    commaSep(l:List String):List(String) ==
      [(l.1),:[:[",",u] for u in rest(l)]]

    getReturn(rec:RETURN):SEX ==
      returnToken : SEX := convert("RETURN"::Symbol::O)$SEX
      elt(rec,empty?)$RETURN =>
        getStatement(returnToken,NIL$Lisp)$Lisp
      rt : EXPRESSION := elt(rec,value)$RETURN
      rv : O := elt(rt,expr)$EXPRESSION
      getStatement([returnToken,convert(rv)$SEX]$Lisp,
                   elt(rt,ints2Floats?)$EXPRESSION )$Lisp

    getStop():SEX ==
      fortran2Lines(LIST("STOP")$Lisp)$Lisp

    getSave():SEX ==
      fortran2Lines(LIST("SAVE")$Lisp)$Lisp

    getCommon(u:COMMON):SEX ==
      fortran2Lines(APPEND(LIST("COMMON"," /",string (u.name),"/ ")$Lisp,_
                    addCommas(u.contents)$Lisp)$Lisp)$Lisp
```

```
getPrint(l:PRINTLIST):SEX ==
  ll : SEX := LIST("PRINT*")$Lisp
  for i in l repeat
    ll := APPEND(ll,CONS(",",expression2Fortran(i)$Lisp)$Lisp)$Lisp
  fortran2Lines(ll)$Lisp

getBlock(rec:BLOCK):SEX ==
  indentFortLevel(convert(1@Integer)$SEX)$Lisp
  expr : SEX := LIST()$Lisp
  for u in rec repeat
    expr := APPEND(expr,getCode(u))$Lisp
  indentFortLevel(convert(-1@Integer)$SEX)$Lisp
  expr

getBody(f:$):SEX ==
  operation(f) case Block => getCode f
  indentFortLevel(convert(1@Integer)$SEX)$Lisp
  expr := getCode f
  indentFortLevel(convert(-1@Integer)$SEX)$Lisp
  expr

getElseIf(f:$):SEX ==
  rec := code f
  expr :=
   fortFormatElseIf(elt(rec.conditionalBranch,switch)$COND::O)$Lisp
  expr :=
   APPEND(expr,getBody elt(rec.conditionalBranch,thenClause)$COND)$Lisp
  elseBranch := elt(rec.conditionalBranch,elseClause)$COND
  not(operation(elseBranch) case Null) =>
    operation(elseBranch) case Conditional =>
      APPEND(expr,getElseIf elseBranch)$Lisp
    expr := APPEND(expr, getStatement(ELSE::O,NIL$Lisp)$Lisp)$Lisp
    expr := APPEND(expr, getBody elseBranch)$Lisp
  expr

getContinue(label:SingleInteger):SEX ==
  lab : O := label::O
  if (width(lab) > 6) then error "Label too big"
  cnt : O := "CONTINUE"::O
  --sp  : O := hspace(6-width lab)
  sp  : O := hspace(_$fortIndent$Lisp -width lab)
  LIST(STRCONC(STRINGIMAGE(lab)$Lisp,sp,cnt)$Lisp)$Lisp

getGoto(label:SingleInteger):SEX ==
 fortran2Lines(
  LIST(STRCONC("GOTO ",STRINGIMAGE(label::O)$Lisp)$Lisp)$Lisp)$Lisp

getRepeat(repRec:LOOP):SEX ==
  sw : Switch := NOT elt(repRec,switch)$LOOP
  lab := newLabel()
```

```
    bod := elt(repRec,body)$LOOP
    APPEND(getContinue lab,getBody bod,
         fortFormatIfGoto(sw::O,lab)$Lisp)$Lisp

  getWhile(whileRec:LOOP):SEX ==
    sw := NOT elt(whileRec,switch)$LOOP
    lab1 := newLabel()
    lab2 := newLabel()
    bod := elt(whileRec,body)$LOOP
    APPEND(fortFormatLabelledIfGoto(sw::O,lab1,lab2)$Lisp,
         getBody bod, getBody goto(lab1), getContinue lab2)$Lisp

  getArrayAssign(rec:ARRAYASS):SEX ==
    getfortarrayexp((rec.var)::O,rec.rand,rec.ints2Floats?)$Lisp

  getAssign(rec:ASS):SEX ==
    indices : L PIN := elt(rec,arrayIndex)$ASS
    if indices = []::(L PIN) then
      lhs := elt(rec,var)$ASS::O
    else
      lhs := cons(elt(rec,var)$ASS::PIN,indices)::O
      -- Must get the index brackets correct:
      lhs := (cdr car cdr convert(lhs)$SEX::SEX)::O -- Yuck!
    elt(elt(rec,rand)$ASS,ints2Floats?)$EXPRESSION =>
      assignment2Fortran1(lhs,elt(elt(rec,rand)$ASS,expr)$EXPRESSION)$Lisp
    integerAssignment2Fortran1(lhs,elt(elt(rec,rand)$ASS,expr)$EXPRESSION)$Lisp

  getCond(rec:COND):SEX ==
    expr := APPEND(fortFormatIf(elt(rec,switch)$COND::O)$Lisp,
                   getBody elt(rec,thenClause)$COND)$Lisp
    elseBranch := elt(rec,elseClause)$COND
    if not(operation(elseBranch) case Null) then
      operation(elseBranch) case Conditional =>
        expr := APPEND(expr,getElseIf elseBranch)$Lisp
      expr := APPEND(expr,getStatement(ELSE::O,NIL$Lisp)$Lisp,
                     getBody elseBranch)$Lisp
    APPEND(expr,getStatement(ENDIF::O,NIL$Lisp)$Lisp)$Lisp

  getComment(rec:COMMENT):SEX ==
    convert([convert(concat("C     ",c)$String)@SEX for c in rec])@SEX

  getCall(rec:CALL):SEX ==
    expr := concat("CALL ",rec)$String
    #expr > 1320 => error "Fortran CALL too large"
    fortran2Lines(convert([convert(expr)@SEX ])@SEX)$Lisp

  getFor(rec:FOR):SEX ==
    rnge : SegmentBinding PIN := elt(rec,range)$FOR
    increment : PIN := elt(rec,span)$FOR
    lab : SingleInteger := newLabel()
```

```
    declare!(variable rnge,fortranInteger())
    expr := fortFormatDo(variable rnge, (lo segment rnge)::O,_
      (hi segment rnge)::O,increment::O,lab)$Lisp
    APPEND(expr, getBody elt(rec,body)$FOR, getContinue(lab))$Lisp

  getCode(f:$):SEX ==
    opp:OP := operation f
    rec:OPREC:= code f
    opp case Assignment => getAssign(rec.assignmentBranch)
    opp case ArrayAssignment => getArrayAssign(rec.arrayAssignmentBranch)
    opp case Conditional => getCond(rec.conditionalBranch)
    opp case Return => getReturn(rec.returnBranch)
    opp case Block => getBlock(rec.blockBranch)
    opp case Comment => getComment(rec.commentBranch)
    opp case Call => getCall(rec.callBranch)
    opp case For => getFor(rec.forBranch)
    opp case Continue => getContinue(rec.labelBranch)
    opp case Goto => getGoto(rec.labelBranch)
    opp case Repeat => getRepeat(rec.loopBranch)
    opp case While => getWhile(rec.loopBranch)
    opp case Save => getSave()
    opp case Stop => getStop()
    opp case Print => getPrint(rec.printBranch)
    opp case Common => getCommon(rec.commonBranch)
    error "Unsupported program construct."
    convert(0)@SEX

  printCode(f:$):Void ==
    displayLines1$Lisp getCode f
    void()$Void

  code (f:$):OPREC ==
    elt(f,data)$Rep

  operation (f:$):OP ==
    elt(f,op)$Rep

  common(name:Symbol,contents:List Symbol):$ ==
    [["common"]$OP,[[name,contents]$COMMON]$OPREC]$Rep

  stop():$ ==
    [["stop"]$OP,["null"]$OPREC]$Rep

  save():$ ==
    [["save"]$OP,["null"]$OPREC]$Rep

  printStatement(l:List O):$ ==
    [["print"]$OP,[l]$OPREC]$Rep

  comment(s:List String):$ ==
```

```
    [["comment"]$OP,[s]$OPREC]$Rep

  comment(s:String):$ ==
    [["comment"]$OP,[list s]$OPREC]$Rep

  forLoop(r:SegmentBinding PIN,body:$):$ ==
    [["for"]$OP,[[r,(incr segment r)::PIN,body]$FOR]$OPREC]$Rep

  forLoop(r:SegmentBinding PIN,increment:PIN,body:$):$ ==
    [["for"]$OP,[[r,increment,body]$FOR]$OPREC]$Rep

  goto(l:SingleInteger):$ ==
    [["goto"]$OP,[l]$OPREC]$Rep

  continue(l:SingleInteger):$ ==
    [["continue"]$OP,[l]$OPREC]$Rep

  whileLoop(sw:Switch,b:$):$ ==
    [["while"]$OP,[[sw,b]$LOOP]$OPREC]$Rep

  repeatUntilLoop(sw:Switch,b:$):$ ==
    [["repeat"]$OP,[[sw,b]$LOOP]$OPREC]$Rep

  returns():$ ==
    v := [false,0::O]$EXPRESSION
    [["return"]$OP,[[true,v]$RETURN]$OPREC]$Rep

  returns(v:Expression MachineInteger):$ ==
    [["return"]$OP,[[false,[false,v::O]$EXPRESSION]$RETURN]$OPREC]$Rep

  returns(v:Expression MachineFloat):$ ==
    [["return"]$OP,[[false,[false,v::O]$EXPRESSION]$RETURN]$OPREC]$Rep

  returns(v:Expression MachineComplex):$ ==
    [["return"]$OP,[[false,[false,v::O]$EXPRESSION]$RETURN]$OPREC]$Rep

  returns(v:Expression Integer):$ ==
    [["return"]$OP,[[false,[false,v::O]$EXPRESSION]$RETURN]$OPREC]$Rep

  returns(v:Expression Float):$ ==
    [["return"]$OP,[[false,[false,v::O]$EXPRESSION]$RETURN]$OPREC]$Rep

  returns(v:Expression Complex Float):$ ==
    [["return"]$OP,[[false,[false,v::O]$EXPRESSION]$RETURN]$OPREC]$Rep

  block(l:List $):$ ==
    [["block"]$OP,[l]$OPREC]$Rep

  cond(sw:Switch,thenC:$):$ ==
    [["conditional"]$OP,
```

```
    [[sw,thenC,[["null"]$OP,["null"]$OPREC]$Rep]$COND]$OPREC]$Rep

cond(sw:Switch,thenC:$,elseC:$):$ ==
  [["conditional"]$OP,[[sw,thenC,elseC]$COND]$OPREC]$Rep

coerce(f : $):O ==
  (f.op)::O

assign(v:Symbol,rhs:String):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[false,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix MachineInteger):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,false]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix MachineFloat):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix MachineComplex):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector MachineInteger):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,false]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector MachineFloat):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector MachineComplex):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix Expression MachineInteger):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,false]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix Expression MachineFloat):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix Expression MachineComplex):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector Expression MachineInteger):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,false]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector Expression MachineFloat):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector Expression MachineComplex):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,index:L PIN,rhs:Expression MachineInteger):$ ==
  [["assignment"]$OP,[[v,index,[false,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep
```

```
assign(v:Symbol,index:L PIN,rhs:Expression MachineFloat):$ ==
  [["assignment"]$OP,[[v,index,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,index:L PIN,rhs:Expression MachineComplex):$ ==
  [["assignment"]$OP,[[v,index,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Expression MachineInteger):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[false,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Expression MachineFloat):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Expression MachineComplex):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix Expression Integer):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,false]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix Expression Float):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Matrix Expression Complex Float):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector Expression Integer):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,false]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector Expression Float):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,rhs:Vector Expression Complex Float):$ ==
  [["arrayAssignment"]$OP,[[v,rhs::O,true]$ARRAYASS]$OPREC]$Rep

assign(v:Symbol,index:L PIN,rhs:Expression Integer):$ ==
  [["assignment"]$OP,[[v,index,[false,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,index:L PIN,rhs:Expression Float):$ ==
  [["assignment"]$OP,[[v,index,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,index:L PIN,rhs:Expression Complex Float):$ ==
  [["assignment"]$OP,[[v,index,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Expression Integer):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[false,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Expression Float):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep

assign(v:Symbol,rhs:Expression Complex Float):$ ==
  [["assignment"]$OP,[[v,nil()::L PIN,[true,rhs::O]$EXPRESSION]$ASS]$OPREC]$Rep
```

```
    call(s:String):$ ==
      [["call"]$OP,[s]$OPREC]$Rep
```

———-

— **FC.dotabb** —

```
"FC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FC"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"COMPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=COMPCAT"]
"FC" -> "COMPCAT"
"FC" -> "FS"
```

———-

7.17 domain FEXPR FortranExpression

— **FortranExpression.input** —

```
)set break resume
)sys rm -f FortranExpression.output
)spool FortranExpression.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FortranExpression
--R
--R FortranExpression(basicSymbols: List(Symbol),subscriptedSymbols: List(Symbol),R: FortranMach
--R Abbreviation for FortranExpression is FEXPR
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FEXPR
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?*? : (Integer,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (R,%) -> %                      ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      -? : % -> %
--R ?-? : (%,%) -> %                      ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R D : (%,Symbol) -> %                   D : (%,List(Symbol)) -> %
```

```
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       abs : % -> %
--R acos : % -> %                        asin : % -> %
--R atan : % -> %                        belong? : BasicOperator -> Boolean
--R box : List(%) -> %                   box : % -> %
--R coerce : % -> Expression(R)          coerce : Integer -> %
--R coerce : R -> %                      coerce : Kernel(%) -> %
--R coerce : % -> OutputForm             cos : % -> %
--R cosh : % -> %                        differentiate : (%,Symbol) -> %
--R distribute : (%,%) -> %              distribute : % -> %
--R elt : (BasicOperator,%,%) -> %       elt : (BasicOperator,%) -> %
--R eval : (%,%,%) -> %                  eval : (%,Equation(%)) -> %
--R eval : (%,Kernel(%),%) -> %          exp : % -> %
--R freeOf? : (%,Symbol) -> Boolean      freeOf? : (%,%) -> Boolean
--R hash : % -> SingleInteger            height : % -> NonNegativeInteger
--R is? : (%,Symbol) -> Boolean          kernel : (BasicOperator,%) -> %
--R kernels : % -> List(Kernel(%))       latex : % -> String
--R log : % -> %                         log10 : % -> %
--R max : (%,%) -> %                     min : (%,%) -> %
--R one? : % -> Boolean                  paren : List(%) -> %
--R paren : % -> %                       pi : () -> %
--R recip : % -> Union(%,"failed")       retract : Symbol -> %
--R retract : Expression(R) -> %         retract : % -> R
--R retract : % -> Kernel(%)             sample : () -> %
--R sin : % -> %                         sinh : % -> %
--R sqrt : % -> %                        subst : (%,Equation(%)) -> %
--R tan : % -> %                         tanh : % -> %
--R tower : % -> List(Kernel(%))         useNagFunctions : () -> Boolean
--R variables : % -> List(Symbol)        zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,Symbol,NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R definingPolynomial : % -> % if $ has RING
--R differentiate : (%,List(Symbol)) -> %
--R differentiate : (%,Symbol,NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> %
--R elt : (BasicOperator,List(%)) -> %
--R elt : (BasicOperator,%,%,%,%) -> %
--R elt : (BasicOperator,%,%,%) -> %
--R eval : (%,BasicOperator,(% -> %)) -> %
--R eval : (%,BasicOperator,(List(%) -> %)) -> %
--R eval : (%,List(BasicOperator),List((List(%) -> %))) -> %
--R eval : (%,List(BasicOperator),List((% -> %))) -> %
--R eval : (%,Symbol,(% -> %)) -> %
--R eval : (%,Symbol,(List(%) -> %)) -> %
--R eval : (%,List(Symbol),List((List(%) -> %))) -> %
```

```
--R eval : (%,List(Symbol),List((% -> %))) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R eval : (%,List(Kernel(%)),List(%)) -> %
--R even? : % -> Boolean if $ has RETRACT(INT)
--R is? : (%,BasicOperator) -> Boolean
--R kernel : (BasicOperator,List(%)) -> %
--R mainKernel : % -> Union(Kernel(%),"failed")
--R map : ((% -> %),Kernel(%)) -> %
--R minPoly : Kernel(%) -> SparseUnivariatePolynomial(%) if $ has RING
--R odd? : % -> Boolean if $ has RETRACT(INT)
--R operator : BasicOperator -> BasicOperator
--R operators : % -> List(BasicOperator)
--R retract : Polynomial(Float) -> % if R has RETRACT(FLOAT)
--R retract : Fraction(Polynomial(Float)) -> % if R has RETRACT(FLOAT)
--R retract : Expression(Float) -> % if R has RETRACT(FLOAT)
--R retract : Polynomial(Integer) -> % if R has RETRACT(INT)
--R retract : Fraction(Polynomial(Integer)) -> % if R has RETRACT(INT)
--R retract : Expression(Integer) -> % if R has RETRACT(INT)
--R retractIfCan : Polynomial(Float) -> Union(%,"failed") if R has RETRACT(FLOAT)
--R retractIfCan : Fraction(Polynomial(Float)) -> Union(%,"failed") if R has RETRACT(FLOAT)
--R retractIfCan : Expression(Float) -> Union(%,"failed") if R has RETRACT(FLOAT)
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed") if R has RETRACT(INT)
--R retractIfCan : Fraction(Polynomial(Integer)) -> Union(%,"failed") if R has RETRACT(INT)
--R retractIfCan : Expression(Integer) -> Union(%,"failed") if R has RETRACT(INT)
--R retractIfCan : Symbol -> Union(%,"failed")
--R retractIfCan : Expression(R) -> Union(%,"failed")
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Kernel(%),"failed")
--R subst : (%,List(Kernel(%)),List(%)) -> %
--R subst : (%,List(Equation(%))) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R useNagFunctions : Boolean -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— FortranExpression.help —

```
=====================================================================
FortranExpression examples
=====================================================================

See Also:
o )show FortranExpression
```

———-

7.17.1 FortranExpression (FEXPR)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266
⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “FortranProgram” (FORTRAN) 7.18.1 on page 926
⇒ “ThreeDimensionalMatrix” (M3D) 21.7.1 on page 2671
⇒ “SimpleFortranProgram” (SFORT) 20.11.1 on page 2373
⇒ “Switch” (SWITCH) 20.36.1 on page 2597
⇒ “FortranTemplate” (FTEM) 7.20.1 on page 937

Exports:

0	1	abs	acos	asin
atan	belong?	box	characteristic	coerce
cos	cosh	D	definingPolynomial	differentiate
distribute	elt	eval	even?	exp
freeOf?	hash	height	is?	kernel
kernels	latex	log	log10	mainKernel
map	max	min	minPoly	odd?
one?	operator	operators	paren	pi
recip	retract	retractIfCan	sample	sin
sinh	sqrt	subst	subtractIfCan	tan
tanh	tower	useNagFunctions	variables	zero?
?*?	?**?	?+?	-?	?-?
?<?	?<=?	?=?	?>?	?>=?
?^?	?~=?			

— domain FEXPR FortranExpression —

```
)abbrev domain FEXPR FortranExpression
++ Author: Mike Dewar
```

```
++ Date Created:  December 1993
++ Date Last Updated: 19 May 1994
++                     7 July 1994 added %power to f77Functions
++                    12 July 1994 added RetractableTo(R)
++ Basic Operations:
++ Related Domains:
++ Also See: FortranMachineTypeCategory, MachineInteger, MachineFloat,
++  MachineComplex
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A domain of expressions involving functions which can be
++ translated into standard Fortran-77, with some extra extensions from
++ the NAG Fortran Library.

FortranExpression(basicSymbols,subscriptedSymbols,R):
                                Exports==Implementation where
  basicSymbols : List Symbol
  subscriptedSymbols : List Symbol
  R : FortranMachineTypeCategory

  EXPR ==> Expression
  EXF2 ==> ExpressionFunctions2
  S    ==> Symbol
  L    ==> List
  BO   ==> BasicOperator
  FRAC ==> Fraction
  POLY ==> Polynomial

  Exports ==> Join(ExpressionSpace,Algebra(R),RetractableTo(R),
                  PartialDifferentialRing(Symbol)) with
    retract : EXPR R -> $
      ++ retract(e) takes e and transforms it into a
      ++ FortranExpression checking that it contains no non-Fortran
      ++ functions, and that it only contains the given basic symbols
      ++ and subscripted symbols which correspond to scalar and array
      ++ parameters respectively.
    retractIfCan : EXPR R -> Union($,"failed")
      ++ retractIfCan(e) takes e and tries to transform it into a
      ++ FortranExpression checking that it contains no non-Fortran
      ++ functions, and that it only contains the given basic symbols
      ++ and subscripted symbols which correspond to scalar and array
      ++ parameters respectively.
    retract : S -> $
      ++ retract(e) takes e and transforms it into a FortranExpression
      ++ checking that it is one of the given basic symbols
      ++ or subscripted symbols which correspond to scalar and array
      ++ parameters respectively.
```

```
    retractIfCan : S -> Union($,"failed")
      ++ retractIfCan(e) takes e and tries to transform it into a
      ++ FortranExpression checking that it is one of the given basic symbols
      ++ or subscripted symbols which correspond to scalar and array
      ++ parameters respectively.
    coerce : $ -> EXPR R
      ++ coerce(x) is not documented
    if (R has RetractableTo(Integer)) then
      retract : EXPR Integer -> $
        ++ retract(e) takes e and transforms it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
        ++ parameters respectively.
      retractIfCan : EXPR Integer -> Union($,"failed")
        ++ retractIfCan(e) takes e and tries to transform it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
        ++ parameters respectively.
      retract : FRAC POLY  Integer -> $
        ++ retract(e) takes e and transforms it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
        ++ parameters respectively.
      retractIfCan : FRAC POLY  Integer -> Union($,"failed")
        ++ retractIfCan(e) takes e and tries to transform it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
        ++ parameters respectively.
      retract : POLY  Integer -> $
        ++ retract(e) takes e and transforms it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
        ++ parameters respectively.
      retractIfCan : POLY  Integer -> Union($,"failed")
        ++ retractIfCan(e) takes e and tries to transform it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
        ++ parameters respectively.
    if (R has RetractableTo(Float)) then
      retract : EXPR Float -> $
        ++ retract(e) takes e and transforms it into a
        ++ FortranExpression checking that it contains no non-Fortran
        ++ functions, and that it only contains the given basic symbols
        ++ and subscripted symbols which correspond to scalar and array
```

```
    ++ parameters respectively.
  retractIfCan : EXPR Float -> Union($,"failed")
    ++ retractIfCan(e) takes e and tries to transform it into a
    ++ FortranExpression checking that it contains no non-Fortran
    ++ functions, and that it only contains the given basic symbols
    ++ and subscripted symbols which correspond to scalar and array
    ++ parameters respectively.
  retract : FRAC POLY  Float -> $
    ++ retract(e) takes e and transforms it into a
    ++ FortranExpression checking that it contains no non-Fortran
    ++ functions, and that it only contains the given basic symbols
    ++ and subscripted symbols which correspond to scalar and array
    ++ parameters respectively.
  retractIfCan : FRAC POLY  Float -> Union($,"failed")
    ++ retractIfCan(e) takes e and tries to transform it into a
    ++ FortranExpression checking that it contains no non-Fortran
    ++ functions, and that it only contains the given basic symbols
    ++ and subscripted symbols which correspond to scalar and array
    ++ parameters respectively.
  retract : POLY  Float -> $
    ++ retract(e) takes e and transforms it into a
    ++ FortranExpression checking that it contains no non-Fortran
    ++ functions, and that it only contains the given basic symbols
    ++ and subscripted symbols which correspond to scalar and array
    ++ parameters respectively.
  retractIfCan : POLY  Float -> Union($,"failed")
    ++ retractIfCan(e) takes e and tries to transform it into a
    ++ FortranExpression checking that it contains no non-Fortran
    ++ functions, and that it only contains the given basic symbols
    ++ and subscripted symbols which correspond to scalar and array
    ++ parameters respectively.
abs    : $ -> $
  ++ abs(x) represents the Fortran intrinsic function ABS
sqrt   : $ -> $
  ++ sqrt(x) represents the Fortran intrinsic function SQRT
exp    : $ -> $
  ++ exp(x) represents the Fortran intrinsic function EXP
log    : $ -> $
  ++ log(x) represents the Fortran intrinsic function LOG
log10  : $ -> $
  ++ log10(x) represents the Fortran intrinsic function LOG10
sin    : $ -> $
  ++ sin(x) represents the Fortran intrinsic function SIN
cos    : $ -> $
  ++ cos(x) represents the Fortran intrinsic function COS
tan    : $ -> $
  ++ tan(x) represents the Fortran intrinsic function TAN
asin   : $ -> $
  ++ asin(x) represents the Fortran intrinsic function ASIN
acos   : $ -> $
```

```
      ++ acos(x) represents the Fortran intrinsic function ACOS
    atan   : $ -> $
      ++ atan(x) represents the Fortran intrinsic function ATAN
    sinh   : $ -> $
      ++ sinh(x) represents the Fortran intrinsic function SINH
    cosh   : $ -> $
      ++ cosh(x) represents the Fortran intrinsic function COSH
    tanh   : $ -> $
      ++ tanh(x) represents the Fortran intrinsic function TANH
    pi     : () -> $
      ++ pi(x) represents the NAG Library function X01AAF which returns
      ++  an approximation to the value of pi
    variables : $ -> L S
      ++ variables(e) return a list of all the variables in \spad{e}.
    useNagFunctions : () -> Boolean
      ++ useNagFunctions() indicates whether NAG functions are being used
      ++  for mathematical and machine constants.
    useNagFunctions : Boolean -> Boolean
      ++ useNagFunctions(v) sets the flag which controls whether NAG functions
      ++  are being used for mathematical and machine constants.  The previous
      ++  value is returned.

  Implementation ==> EXPR R add

    -- The standard FORTRAN-77 intrinsic functions, plus nthRoot which
    -- can be translated into an arithmetic expression:
    f77Functions : L S := [abs,sqrt,exp,log,log10,sin,cos,tan,asin,acos,
                           atan,sinh,cosh,tanh,nthRoot,%power]
    nagFunctions : L S := [pi, X01AAF]
    useNagFunctionsFlag : Boolean := true

    -- Local functions to check for "unassigned" symbols etc.

    mkEqn(s1:Symbol,s2:Symbol):Equation EXPR(R) ==
      equation(s2::EXPR(R),script(s1,scripts(s2))::EXPR(R))

    fixUpSymbols(u:EXPR R):Union(EXPR R,"failed") ==
      -- If its a univariate expression then just fix it up:
      syms   : L S := variables(u)
--      one?(#basicSymbols) and zero?(#subscriptedSymbols) =>
      (#basicSymbols = 1) and zero?(#subscriptedSymbols) =>
--        not one?(#syms) => "failed"
        not (#syms = 1) => "failed"
        subst(u,equation(first(syms)::EXPR(R),first(basicSymbols)::EXPR(R)))
      -- We have one variable but it is subscripted:
--      zero?(#basicSymbols) and one?(#subscriptedSymbols) =>
      zero?(#basicSymbols) and (#subscriptedSymbols = 1) =>
        -- Make sure we don't have both X and X_i
        for s in syms repeat
          not scripted?(s) => return "failed"
```

```
--        not one?(#(syms:=removeDuplicates! [name(s) for s in syms]))=> "failed"
        not ((#(syms:=removeDuplicates! [name(s) for s in syms])) = 1)=> "failed"
        sym : Symbol := first subscriptedSymbols
        subst(u,[mkEqn(sym,i) for i in variables(u)])
      "failed"

    extraSymbols?(u:EXPR R):Boolean ==
      syms   : L S := [name(v) for v in variables(u)]
      extras : L S := setDifference(syms,
                                    setUnion(basicSymbols,subscriptedSymbols))
      not empty? extras

    checkSymbols(u:EXPR R):EXPR(R) ==
      syms   : L S := [name(v) for v in variables(u)]
      extras : L S := setDifference(syms,
                                    setUnion(basicSymbols,subscriptedSymbols))
      not empty? extras =>
        m := fixUpSymbols(u)
        m case EXPR(R) => m::EXPR(R)
        error("Extra symbols detected:",[string(v) for v in extras]$L(String))
      u

    notSymbol?(v:BO):Boolean ==
      s : S := name v
      member?(s,basicSymbols) or
        scripted?(s) and member?(name s,subscriptedSymbols) => false
      true

    extraOperators?(u:EXPR R):Boolean ==
      ops    : L S := [name v for v in operators(u) | notSymbol?(v)]
      if useNagFunctionsFlag then
        fortranFunctions : L S := append(f77Functions,nagFunctions)
      else
        fortranFunctions : L S := f77Functions
      extras : L S := setDifference(ops,fortranFunctions)
      not empty? extras

    checkOperators(u:EXPR R):Void ==
      ops    : L S := [name v for v in operators(u) | notSymbol?(v)]
      if useNagFunctionsFlag then
        fortranFunctions : L S := append(f77Functions,nagFunctions)
      else
        fortranFunctions : L S := f77Functions
      extras : L S := setDifference(ops,fortranFunctions)
      not empty? extras =>
        error("Non FORTRAN-77 functions detected:",[string(v) for v in extras])
      void()

    checkForNagOperators(u:EXPR R):$ ==
      useNagFunctionsFlag =>
```

```
      import Pi
      import PiCoercions(R)
      piOp : BasicOperator := operator X01AAF
      piSub : Equation EXPR R :=
        equation(pi()$Pi::EXPR(R),kernel(piOp,0::EXPR(R))$EXPR(R))
      subst(u,piSub) pretend $
    u pretend $

  -- Conditional retractions:

  if R has RetractableTo(Integer) then

    retractIfCan(u:POLY Integer):Union($,"failed") ==
      retractIfCan((u::EXPR Integer)$EXPR(Integer))@Union($,"failed")

    retract(u:POLY Integer):$ ==
      retract((u::EXPR Integer)$EXPR(Integer))@$

    retractIfCan(u:FRAC POLY Integer):Union($,"failed") ==
      retractIfCan((u::EXPR Integer)$EXPR(Integer))@Union($,"failed")

    retract(u:FRAC POLY  Integer):$ ==
      retract((u::EXPR Integer)$EXPR(Integer))@$

    int2R(u:Integer):R == u::R

    retractIfCan(u:EXPR Integer):Union($,"failed") ==
      retractIfCan(map(int2R,u)$EXF2(Integer,R))@Union($,"failed")

    retract(u:EXPR Integer):$ ==
      retract(map(int2R,u)$EXF2(Integer,R))@$

  if R has RetractableTo(Float) then

    retractIfCan(u:POLY Float):Union($,"failed") ==
      retractIfCan((u::EXPR Float)$EXPR(Float))@Union($,"failed")

    retract(u:POLY Float):$ ==
      retract((u::EXPR Float)$EXPR(Float))@$

    retractIfCan(u:FRAC POLY Float):Union($,"failed") ==
      retractIfCan((u::EXPR Float)$EXPR(Float))@Union($,"failed")

    retract(u:FRAC POLY  Float):$ ==
      retract((u::EXPR Float)$EXPR(Float))@$

    float2R(u:Float):R == (u::R)

    retractIfCan(u:EXPR Float):Union($,"failed") ==
      retractIfCan(map(float2R,u)$EXF2(Float,R))@Union($,"failed")
```

```
      retract(u:EXPR Float):$ ==
        retract(map(float2R,u)$EXF2(Float,R))@$

    -- Exported Functions

    useNagFunctions():Boolean == useNagFunctionsFlag
    useNagFunctions(v:Boolean):Boolean ==
      old := useNagFunctionsFlag
      useNagFunctionsFlag := v
      old

    log10(x:$):$ ==
      kernel(operator log10,x)

    pi():$ == kernel(operator X01AAF,0)

    coerce(u:$):EXPR R == u pretend EXPR(R)

    retractIfCan(u:EXPR R):Union($,"failed") ==
      if (extraSymbols? u) then
        m := fixUpSymbols(u)
        m case "failed" => return "failed"
        u := m::EXPR(R)
      extraOperators? u => "failed"
      checkForNagOperators(u)

    retract(u:EXPR R):$ ==
      u:=checkSymbols(u)
      checkOperators(u)
      checkForNagOperators(u)

    retractIfCan(u:Symbol):Union($,"failed") ==
      not (member?(u,basicSymbols) or
           scripted?(u) and member?(name u,subscriptedSymbols)) => "failed"
      (((u::EXPR(R))$(EXPR R))pretend Rep)::$

    retract(u:Symbol):$ ==
      res : Union($,"failed") := retractIfCan(u)
      res case "failed" => error("Illegal Symbol Detected:",u::String)
      res::$
```

———-

— FEXPR.dotabb —

```
"FEXPR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FEXPR"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
```

```
"FEXPR" -> "ALIST"
```

———-

7.18 domain FORTRAN FortranProgram

— **FortranProgram.input** —

```
)set break resume
)sys rm -f FortranProgram.output
)spool FortranProgram.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FortranProgram
--R
--R FortranProgram(name: Symbol,returnType: Union(fst: FortranScalarType,void: void),arguments: List(Symbol)
--R Abbreviation for FortranProgram is FORTRAN
--R This constructor is exposed in this frame.
--R Issue )edit NIL to see algebra source code for FORTRAN
--R
--R------------------------------ Operations --------------------------------
--R coerce : Expression(Float) -> %       coerce : Expression(Integer) -> %
--R coerce : List(FortranCode) -> %       coerce : FortranCode -> %
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R coerce : Equation(Expression(Complex(Float))) -> %
--R coerce : Equation(Expression(Float)) -> %
--R coerce : Equation(Expression(Integer)) -> %
--R coerce : Expression(Complex(Float)) -> %
--R coerce : Equation(Expression(MachineComplex)) -> %
--R coerce : Equation(Expression(MachineFloat)) -> %
--R coerce : Equation(Expression(MachineInteger)) -> %
--R coerce : Expression(MachineComplex) -> %
--R coerce : Expression(MachineFloat) -> %
--R coerce : Expression(MachineInteger) -> %
--R coerce : Record(localSymbols: SymbolTable,code: List(FortranCode)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FortranProgram.help** —

```
==========================================================================
FortranProgram examples
==========================================================================

See Also:
o )show FortranProgram
```

———-

7.18.1 FortranProgram (FORTRAN)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266
⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “ThreeDimensionalMatrix” (M3D) 21.7.1 on page 2671
⇒ “SimpleFortranProgram” (SFORT) 20.11.1 on page 2373
⇒ “Switch” (SWITCH) 20.36.1 on page 2597
⇒ “FortranTemplate” (FTEM) 7.20.1 on page 937
⇒ “FortranExpression” (FEXPR) 7.17.1 on page 917

Exports:
coerce outputAsFortran

— **domain FORTRAN FortranProgram** —

```
)abbrev domain FORTRAN FortranProgra\\
++ Author: Mike Dewar
++ Date Created: October 1992
++ Date Last Updated: 13 January 1994
++                    23 January 1995 Added support for intrinsic functions
++ Basic Operations:
```

```
++ Related Constructors: FortranType, FortranCode, Switch
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \axiomType{FortranProgram} allows the user to build and manipulate simple
++ models of FORTRAN subprograms.  These can then be transformed into
++ actual FORTRAN notation.

FortranProgram(name,returnType,arguments,symbols): Exports == Implement where
  name       : Symbol
  returnType : Union(fst:FortranScalarType,void:"void")
  arguments  : List Symbol
  symbols    : SymbolTable

  FC     ==> FortranCode
  EXPR   ==> Expression
  INT    ==> Integer
  CMPX   ==> Complex
  MINT   ==> MachineInteger
  MFLOAT ==> MachineFloat
  MCMPLX ==> MachineComplex
  REP    ==> Record(localSymbols : SymbolTable, code : List FortranCode)

  Exports ==> FortranProgramCategory with
    coerce : FortranCode -> $
        ++ coerce(fc) is not documented
    coerce : List FortranCode -> $
        ++ coerce(lfc) is not documented
    coerce : REP -> $
        ++ coerce(r) is not documented
    coerce : EXPR MINT -> $
        ++ coerce(e) is not documented
    coerce : EXPR MFLOAT -> $
        ++ coerce(e) is not documented
    coerce : EXPR MCMPLX -> $
        ++ coerce(e) is not documented
    coerce : Equation EXPR MINT -> $
        ++ coerce(eq) is not documented
    coerce : Equation EXPR MFLOAT -> $
        ++ coerce(eq) is not documented
    coerce : Equation EXPR MCMPLX -> $
        ++ coerce(eq) is not documented
    coerce : EXPR INT -> $
        ++ coerce(e) is not documented
    coerce : EXPR Float -> $
        ++ coerce(e) is not documented
    coerce : EXPR CMPX Float -> $
        ++ coerce(e) is not documented
```

```
    coerce : Equation EXPR INT -> $
        ++ coerce(eq) is not documented
    coerce : Equation EXPR Float -> $
        ++ coerce(eq) is not documented
    coerce : Equation EXPR CMPX Float -> $
        ++ coerce(eq) is not documented

  Implement ==> add

    Rep := REP

    import SExpression
    import TheSymbolTable
    import FortranCode

    makeRep(b:List FortranCode):$ ==
      construct(empty()$SymbolTable,b)$REP

    codeFrom(u:$):List FortranCode ==
      elt(u::Rep,code)$REP

    outputAsFortran(p:$):Void ==
      setLabelValue(25000::SingleInteger)$FC
      -- Do this first to catch any extra type declarations:
      tempName := "FPTEMP"::Symbol
      newSubProgram(tempName)
      initialiseIntrinsicList()$Lisp
      body : List SExpression := [getCode(l)$FortranCode for l in codeFrom(p)]
      intrinsics : SExpression := getIntrinsicList()$Lisp
      endSubProgram()
      fortFormatHead(returnType::OutputForm, name::OutputForm, _
                     arguments::OutputForm)$Lisp
      printTypes(symbols)$SymbolTable
      printTypes((p::Rep).localSymbols)$SymbolTable
      printTypes(tempName)$TheSymbolTable
      fortFormatIntrinsics(intrinsics)$Lisp
      clearTheSymbolTable(tempName)
      for expr in body repeat displayLines1(expr)$Lisp
      dispStatement(END::OutputForm)$Lisp
      void()$Void

    mkString(l:List Symbol):String ==
      unparse(convert(l::OutputForm)@InputForm)$InputForm

    checkVariables(user:List Symbol,target:List Symbol):Void ==
      -- We don't worry about whether the user has subscripted the
      -- variables or not.
      setDifference(map(name$Symbol,user),target) ^= empty()$List(Symbol) =>
        s1 : String := mkString(user)
        s2 : String := mkString(target)
```

```
      error ["Incompatible variable lists:", s1, s2]
    void()$Void

  coerce(u:EXPR MINT) : $ ==
    checkVariables(variables(u)$EXPR(MINT),arguments)
    l : List(FC) := [assign(name,u)$FC,returns()$FC]
    makeRep l

  coerce(u:Equation EXPR MINT) : $ ==
    retractIfCan(lhs u)@Union(Kernel(EXPR MINT),"failed") case "failed" =>
      error "left hand side is not a kernel"
    vList : List Symbol := variables lhs u
    #vList ^= #arguments =>
      error "Incorrect number of arguments"
    veList : List EXPR MINT := [w::EXPR(MINT) for w in vList]
    aeList : List EXPR MINT := [w::EXPR(MINT) for w in arguments]
    eList : List Equation EXPR MINT :=
      [equation(w,v) for w in veList for v in aeList]
    (subst(rhs u,eList))::$

  coerce(u:EXPR MFLOAT) : $ ==
    checkVariables(variables(u)$EXPR(MFLOAT),arguments)
    l : List(FC) := [assign(name,u)$FC,returns()$FC]
    makeRep l

  coerce(u:Equation EXPR MFLOAT) : $ ==
    retractIfCan(lhs u)@Union(Kernel(EXPR MFLOAT),"failed") case "failed" =>
      error "left hand side is not a kernel"
    vList : List Symbol := variables lhs u
    #vList ^= #arguments =>
      error "Incorrect number of arguments"
    veList : List EXPR MFLOAT := [w::EXPR(MFLOAT) for w in vList]
    aeList : List EXPR MFLOAT := [w::EXPR(MFLOAT) for w in arguments]
    eList : List Equation EXPR MFLOAT :=
      [equation(w,v) for w in veList for v in aeList]
    (subst(rhs u,eList))::$

  coerce(u:EXPR MCMPLX) : $ ==
    checkVariables(variables(u)$EXPR(MCMPLX),arguments)
    l : List(FC) := [assign(name,u)$FC,returns()$FC]
    makeRep l

  coerce(u:Equation EXPR MCMPLX) : $ ==
    retractIfCan(lhs u)@Union(Kernel EXPR MCMPLX,"failed") case "failed"=>
      error "left hand side is not a kernel"
    vList : List Symbol := variables lhs u
    #vList ^= #arguments =>
      error "Incorrect number of arguments"
    veList : List EXPR MCMPLX := [w::EXPR(MCMPLX) for w in vList]
    aeList : List EXPR MCMPLX := [w::EXPR(MCMPLX) for w in arguments]
```

```
    eList : List Equation EXPR MCMPLX :=
      [equation(w,v) for w in veList for v in aeList]
    (subst(rhs u,eList))::$


  coerce(u:REP):$ ==
    u@Rep

  coerce(u:$):OutputForm ==
    coerce(name)$Symbol

  coerce(c:List FortranCode):$ ==
    makeRep c

  coerce(c:FortranCode):$ ==
    makeRep [c]

  coerce(u:EXPR INT) : $ ==
    checkVariables(variables(u)$EXPR(INT),arguments)
    l : List(FC) := [assign(name,u)$FC,returns()$FC]
    makeRep l

  coerce(u:Equation EXPR INT) : $ ==
    retractIfCan(lhs u)@Union(Kernel(EXPR INT),"failed") case "failed" =>
      error "left hand side is not a kernel"
    vList : List Symbol := variables lhs u
    #vList ^= #arguments =>
      error "Incorrect number of arguments"
    veList : List EXPR INT := [w::EXPR(INT) for w in vList]
    aeList : List EXPR INT := [w::EXPR(INT) for w in arguments]
    eList : List Equation EXPR INT :=
      [equation(w,v) for w in veList for v in aeList]
    (subst(rhs u,eList))::$

  coerce(u:EXPR Float) : $ ==
    checkVariables(variables(u)$EXPR(Float),arguments)
    l : List(FC) := [assign(name,u)$FC,returns()$FC]
    makeRep l

  coerce(u:Equation EXPR Float) : $ ==
    retractIfCan(lhs u)@Union(Kernel(EXPR Float),"failed") case "failed" =>
      error "left hand side is not a kernel"
    vList : List Symbol := variables lhs u
    #vList ^= #arguments =>
      error "Incorrect number of arguments"
    veList : List EXPR Float := [w::EXPR(Float) for w in vList]
    aeList : List EXPR Float := [w::EXPR(Float) for w in arguments]
    eList : List Equation EXPR Float :=
      [equation(w,v) for w in veList for v in aeList]
    (subst(rhs u,eList))::$
```

```
    coerce(u:EXPR Complex Float) : $ ==
      checkVariables(variables(u)$EXPR(Complex Float),arguments)
      l : List(FC) := [assign(name,u)$FC,returns()$FC]
      makeRep l

    coerce(u:Equation EXPR CMPX Float) : $ ==
      retractIfCan(lhs u)@Union(Kernel EXPR CMPX Float,"failed") case "failed"=>
        error "left hand side is not a kernel"
      vList : List Symbol := variables lhs u
      #vList ^= #arguments =>
        error "Incorrect number of arguments"
      veList : List EXPR CMPX Float := [w::EXPR(CMPX Float) for w in vList]
      aeList : List EXPR CMPX Float := [w::EXPR(CMPX Float) for w in arguments]
      eList : List Equation EXPR CMPX Float :=
        [equation(w,v) for w in veList for v in aeList]
      (subst(rhs u,eList))::$
```

———-

— **FORTRAN.dotabb** —

```
"FORTRAN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FORTRAN"]
"COMPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=COMPCAT"]
"FORTRAN" -> "COMPCAT"
```

———-

7.19 domain FST FortranScalarType

— **FortranScalarType.input** —

```
)set break resume
)sys rm -f FortranScalarType.output
)spool FortranScalarType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FortranScalarType
--R FortranScalarType  is a domain constructor
--R Abbreviation for FortranScalarType is FST
--R This constructor is exposed in this frame.
```

```
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FST
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                character? : % -> Boolean
--R coerce : % -> SExpression             coerce : % -> Symbol
--R coerce : Symbol -> %                  coerce : String -> %
--R coerce : % -> OutputForm              complex? : % -> Boolean
--R double? : % -> Boolean                doubleComplex? : % -> Boolean
--R integer? : % -> Boolean               logical? : % -> Boolean
--R real? : % -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FortranScalarType.help** —

```
=====================================================================
FortranScalarType examples
=====================================================================

See Also:
o )show FortranScalarType
```

———-

7.19.1 FortranScalarType (FST)



See

⇒ “FortranType” (FT) 7.21.1 on page 941
⇒ “SymbolTable” (SYMTAB) 20.38.1 on page 2616
⇒ “TheSymbolTable” (SYMS) 21.6.1 on page 2665

Exports:
character? coerce complex? double? doubleComplex? integer? logical? real? ?=?

— domain FST FortranScalarType —

```
)abbrev domain FST FortranScalarType
++ Author: Mike Dewar
++ Date Created:  October 1992
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Creates and manipulates objects which correspond to the
++ basic FORTRAN data types: REAL, INTEGER, COMPLEX, LOGICAL and CHARACTER

FortranScalarType() : exports == implementation where

  exports == CoercibleTo OutputForm with
    coerce : String -> $
      ++ coerce(s) transforms the string s into an element of
      ++ FortranScalarType provided s is one of "real", "double precision",
      ++ "complex", "logical", "integer", "character", "REAL",
      ++ "COMPLEX", "LOGICAL", "INTEGER", "CHARACTER",
      ++ "DOUBLE PRECISION"
    coerce : Symbol -> $
      ++ coerce(s) transforms the symbol s into an element of
      ++ FortranScalarType provided s is one of real, complex,double precision,
      ++ logical, integer, character, REAL, COMPLEX, LOGICAL,
      ++ INTEGER, CHARACTER, DOUBLE PRECISION
    coerce : $ -> Symbol
      ++ coerce(x) returns the symbol associated with x
    coerce : $ -> SExpression
      ++ coerce(x) returns the s-expression associated with x
    real?  : $ -> Boolean
      ++ real?(t) tests whether t is equivalent to the FORTRAN type REAL.
    double? : $ -> Boolean
      ++ double?(t) tests whether t is equivalent to the FORTRAN type
      ++ DOUBLE PRECISION
    integer?  : $ -> Boolean
      ++ integer?(t) tests whether t is equivalent to the FORTRAN type INTEGER.
    complex?  : $ -> Boolean
      ++ complex?(t) tests whether t is equivalent to the FORTRAN type COMPLEX.
    doubleComplex?  : $ -> Boolean
      ++ doubleComplex?(t) tests whether t is equivalent to the (non-standard)
```

```
    ++ FORTRAN type DOUBLE COMPLEX.
  character?  : $ -> Boolean
    ++ character?(t) tests whether t is equivalent to the FORTRAN type
    ++ CHARACTER.
  logical?  : $ -> Boolean
    ++ logical?(t) tests whether t is equivalent to the FORTRAN type LOGICAL.
  "=" : ($,$) -> Boolean
    ++ x=y tests for equality

implementation == add

  U == Union(RealThing:"real",
             IntegerThing:"integer",
             ComplexThing:"complex",
             CharacterThing:"character",
             LogicalThing:"logical",
             DoublePrecisionThing:"double precision",
             DoubleComplexThing:"double complex")
  Rep := U

  doubleSymbol : Symbol := "double precision"::Symbol
  upperDoubleSymbol : Symbol := "DOUBLE PRECISION"::Symbol
  doubleComplexSymbol : Symbol := "double complex"::Symbol
  upperDoubleComplexSymbol : Symbol := "DOUBLE COMPLEX"::Symbol

  u = v ==
    u case RealThing and v case RealThing => true
    u case IntegerThing and v case IntegerThing => true
    u case ComplexThing and v case ComplexThing => true
    u case LogicalThing and v case LogicalThing => true
    u case CharacterThing and v case CharacterThing => true
    u case DoublePrecisionThing and v case DoublePrecisionThing => true
    u case DoubleComplexThing and v case DoubleComplexThing => true
    false

  coerce(t:$):OutputForm ==
    t case RealThing => coerce(REAL)$Symbol
    t case IntegerThing => coerce(INTEGER)$Symbol
    t case ComplexThing => coerce(COMPLEX)$Symbol
    t case CharacterThing => coerce(CHARACTER)$Symbol
    t case DoublePrecisionThing => coerce(upperDoubleSymbol)$Symbol
    t case DoubleComplexThing => coerce(upperDoubleComplexSymbol)$Symbol
    coerce(LOGICAL)$Symbol

  coerce(t:$):SExpression ==
    t case RealThing => convert(real::Symbol)@SExpression
    t case IntegerThing => convert(integer::Symbol)@SExpression
    t case ComplexThing => convert(complex::Symbol)@SExpression
    t case CharacterThing => convert(character::Symbol)@SExpression
    t case DoublePrecisionThing => convert(doubleSymbol)@SExpression
```

```
    t case DoubleComplexThing => convert(doubleComplexSymbol)@SExpression
    convert(logical::Symbol)@SExpression

  coerce(t:$):Symbol ==
    t case RealThing => real::Symbol
    t case IntegerThing => integer::Symbol
    t case ComplexThing => complex::Symbol
    t case CharacterThing => character::Symbol
    t case DoublePrecisionThing => doubleSymbol
    t case DoublePrecisionThing => doubleComplexSymbol
    logical::Symbol

  coerce(s:Symbol):$ ==
    s = real => ["real"]$Rep
    s = REAL => ["real"]$Rep
    s = integer => ["integer"]$Rep
    s = INTEGER => ["integer"]$Rep
    s = complex => ["complex"]$Rep
    s = COMPLEX => ["complex"]$Rep
    s = character => ["character"]$Rep
    s = CHARACTER => ["character"]$Rep
    s = logical => ["logical"]$Rep
    s = LOGICAL => ["logical"]$Rep
    s = doubleSymbol => ["double precision"]$Rep
    s = upperDoubleSymbol => ["double precision"]$Rep
    s = doubleComplexSymbol => ["double complex"]$Rep
    s = upperDoubleCOmplexSymbol => ["double complex"]$Rep

  coerce(s:String):$ ==
    s = "real" => ["real"]$Rep
    s = "integer" => ["integer"]$Rep
    s = "complex" => ["complex"]$Rep
    s = "character" => ["character"]$Rep
    s = "logical" => ["logical"]$Rep
    s = "double precision" => ["double precision"]$Rep
    s = "double complex" => ["double complex"]$Rep
    s = "REAL" => ["real"]$Rep
    s = "INTEGER" => ["integer"]$Rep
    s = "COMPLEX" => ["complex"]$Rep
    s = "CHARACTER" => ["character"]$Rep
    s = "LOGICAL" => ["logical"]$Rep
    s = "DOUBLE PRECISION" => ["double precision"]$Rep
    s = "DOUBLE COMPLEX" => ["double complex"]$Rep
    error concat([s," is invalid as a Fortran Type"])$String

  real?(t:$):Boolean == t case RealThing

  double?(t:$):Boolean == t case DoublePrecisionThing

  logical?(t:$):Boolean == t case LogicalThing
```

```
    integer?(t:$):Boolean == t case IntegerThing

    character?(t:$):Boolean == t case CharacterThing

    complex?(t:$):Boolean == t case ComplexThing

    doubleComplex?(t:$):Boolean == t case DoubleComplexThing
```

———-

— FST.dotabb —

```
"FST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FST"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FST" -> "ALIST"
```

———-

7.20 domain FTEM FortranTemplate

— FortranTemplate.input —

```
)set break resume
)sys rm -f FortranTemplate.output
)spool FortranTemplate.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FortranTemplate
--R FortranTemplate  is a domain constructor
--R Abbreviation for FortranTemplate is FTEM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FTEM
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                close! : % -> %
--R coerce : % -> OutputForm              flush : % -> Void
--R fortranCarriageReturn : () -> Void    fortranLiteral : String -> Void
--R hash : % -> SingleInteger             iomode : % -> String
--R latex : % -> String                   name : % -> FileName
--R open : (FileName,String) -> %         open : FileName -> %
```

```
--R read! : % -> String                    reopen! : (%,String) -> %
--R write! : (%,String) -> String          ?~=? : (%,%) -> Boolean
--R fortranLiteralLine : String -> Void
--R processTemplate : FileName -> FileName
--R processTemplate : (FileName,FileName) -> FileName
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FortranTemplate.help** —

```
=====================================================================
FortranTemplate examples
=====================================================================

See Also:
o )show FortranTemplate
```

———-

7.20.1 FortranTemplate (FTEM)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266
⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “FortranProgram” (FORTRAN) 7.18.1 on page 926
⇒ “ThreeDimensionalMatrix” (M3D) 21.7.1 on page 2671
⇒ “SimpleFortranProgram” (SFORT) 20.11.1 on page 2373
⇒ “Switch” (SWITCH) 20.36.1 on page 2597
⇒ “FortranExpression” (FEXPR) 7.17.1 on page 917

Exports:

close!	coerce	fortranCarriageReturn	fortranLiteral	fortranLiteralLine
hash	iomode	latex	name	open
processTemplate	read!	reopen!	write!	?=?
?~=?				

— domain FTEM FortranTemplate —

```
)abbrev domain FTEM FortranTemplate
++ Author: Mike Dewar
++ Date Created:  October 1992
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Code to manipulate Fortran templates

FortranTemplate() : specification == implementation where

  specification == FileCategory(FileName, String) with

    processTemplate : (FileName, FileName) -> FileName
      ++ processTemplate(tp,fn) processes the template tp, writing the
      ++ result out to fn.
    processTemplate : (FileName) -> FileName
      ++ processTemplate(tp) processes the template tp, writing the
      ++ result to the current FORTRAN output stream.
    fortranLiteralLine : String -> Void
      ++ fortranLiteralLine(s) writes s to the current Fortran output stream,
      ++ followed by a carriage return
    fortranLiteral : String -> Void
      ++ fortranLiteral(s) writes s to the current Fortran output stream
    fortranCarriageReturn : () -> Void
      ++ fortranCarriageReturn() produces a carriage return on the current
      ++ Fortran output stream

  implementation == TextFile add

    import TemplateUtilities
    import FortranOutputStackPackage

    Rep := TextFile

    fortranLiteralLine(s:String):Void ==
      PRINTEXP(s,_$fortranOutputStream$Lisp)$Lisp
```

```
    TERPRI(_$fortranOutputStream$Lisp)$Lisp

  fortranLiteral(s:String):Void ==
    PRINTEXP(s,_$fortranOutputStream$Lisp)$Lisp

  fortranCarriageReturn():Void ==
    TERPRI(_$fortranOutputStream$Lisp)$Lisp

  writePassiveLine!(line:String):Void ==
  -- We might want to be a bit clever here and look for new SubPrograms etc.
    fortranLiteralLine line

  processTemplate(tp:FileName, fn:FileName):FileName ==
    pushFortranOutputStack(fn)
    processTemplate(tp)
    popFortranOutputStack()
    fn

  getLine(fp:TextFile):String ==
    line : String := stripCommentsAndBlanks readLine!(fp)
    while not empty?(line) and elt(line,maxIndex line) = char "__" repeat
      setelt(line,maxIndex line,char " ")
      line := concat(line, stripCommentsAndBlanks readLine!(fp))$String
    line

  processTemplate(tp:FileName):FileName ==
    fp : TextFile := open(tp,"input")
    active : Boolean := true
    line : String
    endInput : Boolean := false
    while not (endInput or endOfFile? fp) repeat
      if active then
        line := getLine fp
        line = "endInput" => endInput := true
        if line = "beginVerbatim" then
          active := false
        else
          not empty? line => interpretString line
      else
        line := readLine!(fp)
        if line = "endVerbatim" then
          active := true
        else
          writePassiveLine! line
    close!(fp)
    if not active then
      error concat(["Missing 'endVerbatim' line in ",tp::String])$String
    string(_$fortranOutputFile$Lisp)::FileName
```

———-

— **FTEM.dotabb** —

```
"FTEM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FTEM"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"FTEM" -> "STRING"
```

———-

7.21 domain FT FortranType

— **FortranType.input** —

```
)set break resume
)sys rm -f FortranType.output
)spool FortranType.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FortranType
--R
--R FortranType  is a domain constructor
--R Abbreviation for FortranType is FT
--R This constructor is exposed in this frame.
--R Issue )edit NIL to see algebra source code for FT
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean               coerce : FortranScalarType -> %
--R coerce : % -> OutputForm             external? : % -> Boolean
--R fortranCharacter : () -> %           fortranComplex : () -> %
--R fortranDouble : () -> %              fortranDoubleComplex : () -> %
--R fortranInteger : () -> %             fortranLogical : () -> %
--R fortranReal : () -> %                hash : % -> SingleInteger
--R latex : % -> String                  ?~=? : (%,%) -> Boolean
--R construct : (Union(fst: FortranScalarType,void: void),List(Polynomial(Integer)),Boolean) ->
--R construct : (Union(fst: FortranScalarType,void: void),List(Symbol),Boolean) -> %
--R dimensionsOf : % -> List(Polynomial(Integer))
--R scalarTypeOf : % -> Union(fst: FortranScalarType,void: void)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FortranType.help** —

```
====================================================================
FortranType examples
====================================================================

See Also:
o )show FortranType
```

———-

7.21.1 FortranType (FT)



See

⇒ “FortranScalarType” (FST) 7.19.1 on page 932
⇒ “SymbolTable” (SYMTAB) 20.38.1 on page 2616
⇒ “TheSymbolTable” (SYMS) 21.6.1 on page 2665

Exports:

coerce	construct	dimensionsOf	external?
fortranCharacter	fortranComplex	fortranDouble	fortranDoubleComplex
fortranInteger	fortranLogical	fortranReal	hash
latex	scalarTypeOf	?=?	?~=?

— **domain FT FortranType** —

```
)abbrev domain FT FortranType
++ Author: Mike Dewar
++ Date Created:  October 1992
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See:
```

```
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Creates and manipulates objects which correspond to FORTRAN
++ data types, including array dimensions.

FortranType() : exports == implementation where

  FST    ==> FortranScalarType
  FSTU   ==> Union(fst:FST,void:"void")

  exports == SetCategory with
    coerce : $ -> OutputForm
      ++ coerce(x) provides a printable form for x
    coerce : FST -> $
      ++ coerce(t) creates an element from a scalar type
    scalarTypeOf : $ -> FSTU
      ++ scalarTypeOf(t) returns the FORTRAN data type of t
    dimensionsOf : $ -> List Polynomial Integer
      ++ dimensionsOf(t) returns the dimensions of t
    external? : $ -> Boolean
      ++ external?(u) returns true if u is declared to be EXTERNAL
    construct : (FSTU,List Symbol,Boolean) -> $
      ++ construct(type,dims) creates an element of FortranType
    construct : (FSTU,List Polynomial Integer,Boolean) -> $
      ++ construct(type,dims) creates an element of FortranType
    fortranReal : () -> $
      ++ fortranReal() returns REAL, an element of FortranType
    fortranDouble : () -> $
      ++ fortranDouble() returns DOUBLE PRECISION, an element of FortranType
    fortranInteger : () -> $
      ++ fortranInteger() returns INTEGER, an element of FortranType
    fortranLogical : () -> $
      ++ fortranLogical() returns LOGICAL, an element of FortranType
    fortranComplex : () -> $
      ++ fortranComplex() returns COMPLEX, an element of FortranType
    fortranDoubleComplex: () -> $
      ++ fortranDoubleComplex() returns DOUBLE COMPLEX, an element of
      ++ FortranType
    fortranCharacter : () -> $
      ++ fortranCharacter() returns CHARACTER, an element of FortranType

  implementation == add

    Dims == List Polynomial Integer
    Rep := Record(type : FSTU, dimensions : Dims, external : Boolean)

    coerce(a:$):OutputForm ==
```

```
 t : OutputForm
 if external?(a) then
  if scalarTypeOf(a) case void then
    t := "EXTERNAL"::OutputForm
  else
    t := blankSeparate(["EXTERNAL"::OutputForm,
                        coerce(scalarTypeOf a)$FSTU])$OutputForm
 else
  t := coerce(scalarTypeOf a)$FSTU
 empty? dimensionsOf(a) => t
 sub(t,
     paren([u::OutputForm for u in dimensionsOf(a)])$OutputForm)$OutputForm

scalarTypeOf(u:$):FSTU ==
  u.type

dimensionsOf(u:$):Dims ==
  u.dimensions

external?(u:$):Boolean ==
  u.external

construct(t:FSTU, d:List Symbol, e:Boolean):$ ==
  e and not empty? d => error "EXTERNAL objects cannot have dimensions"
  not(e) and t case void => error "VOID objects must be EXTERNAL"
  construct(t,[l::Polynomial(Integer) for l in d],e)$Rep

construct(t:FSTU, d:List Polynomial Integer, e:Boolean):$ ==
  e and not empty? d => error "EXTERNAL objects cannot have dimensions"
  not(e) and t case void => error "VOID objects must be EXTERNAL"
  construct(t,d,e)$Rep

coerce(u:FST):$ ==
  construct([u]$FSTU,[]@List Polynomial Integer,false)

fortranReal():$ == ("real"::FST)::$

fortranDouble():$ == ("double precision"::FST)::$

fortranInteger():$ == ("integer"::FST)::$

fortranComplex():$ == ("complex"::FST)::$

fortranDoubleComplex():$ == ("double complex"::FST)::$

fortranCharacter():$ == ("character"::FST)::$

fortranLogical():$ == ("logical"::FST)::$
```

———-

— **FT.dotabb** —

```
"FT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FT"]
"PID" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PID"]
"OAGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAGROUP"]
"FT" -> "PID"
"FT" -> "OAGROUP"
```

———-

7.22 domain FCOMP FourierComponent

— **FourierComponent.input** —

```
)set break resume
)sys rm -f FourierComponent.output
)spool FourierComponent.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FourierComponent
--R
--R FourierComponent(E: OrderedSet)  is a domain constructor
--R Abbreviation for FourierComponent is FCOMP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FCOMP
--R
--R------------------------------ Operations --------------------------------
--R ?<? : (%,%) -> Boolean               ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean               ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean              argument : % -> E
--R coerce : % -> OutputForm             cos : E -> %
--R hash : % -> SingleInteger            latex : % -> String
--R max : (%,%) -> %                     min : (%,%) -> %
--R sin : E -> %                         sin? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— FourierComponent.help —

```
====================================================================
FourierComponent examples
====================================================================

See Also:
o )show FourierComponent
```

———-

7.22.1 FourierComponent (FCOMP)



See

⇒ "FourierSeries" (FSERIES) 7.23.1 on page 948

Exports:

argument	coerce	cos	hash	latex
max	min	sin	sin?	?~=?
?<?	?<=?	?=?	?>?	?>=?

— domain FCOMP FourierComponent —

```
)abbrev domain FCOMP FourierComponent
++ Author: James Davenport
++ Date Created: 17 April 1992
++ Date Last Updated: 12 June 1992
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
```

```
++ Description:
++ This domain creates kernels for use in Fourier series

FourierComponent(E:OrderedSet):
       OrderedSet with
         sin: E -> $
         ++ sin(x) makes a sin kernel for use in Fourier series
         cos: E -> $
         ++ cos(x) makes a cos kernel for use in Fourier series
         sin?: $ -> Boolean
         ++ sin?(x) returns true if term is a sin, otherwise false
         argument: $ -> E
         ++ argument(x) returns the argument of a given sin/cos expressions
    ==
  add
   --representations
   Rep:=Record(SinIfTrue:Boolean, arg:E)
   e:E
   x,y:$
   sin e == [true,e]
   cos e == [false,e]
   sin? x == x.SinIfTrue
   argument x == x.arg
   coerce(x):OutputForm ==
     hconcat((if x.SinIfTrue then "sin" else "cos")::OutputForm,
              bracket((x.arg)::OutputForm))
   x<y ==
     x.arg < y.arg => true
     y.arg < x.arg => false
     x.SinIfTrue => false
     y.SinIfTrue
```

———-

— FCOMP.dotabb —

```
"FCOMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FCOMP"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"FCOMP" -> "ORDSET"
```

———-

7.23 domain FSERIES FourierSeries

— FourierSeries.input —

```
)set break resume
)sys rm -f FourierSeries.output
)spool FourierSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FourierSeries
--R
--R FourierSeries(R: Join(CommutativeRing,Algebra(Fraction(Integer))),E: Join(OrderedSet,AbelianGroup))  is
--R Abbreviation for FourierSeries is FSERIES
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FSERIES
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : FourierComponent(E) -> %
--R coerce : R -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   makeCos : (E,R) -> %
--R makeSin : (E,R) -> %                  one? : % -> Boolean
--R recip : % -> Union(%,"failed")        sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— FourierSeries.help —

```
=====================================================================
FourierSeries examples
=====================================================================

See Also:
```

```
o )show FourierSeries
```

7.23.1 FourierSeries (FSERIES)



See

⇒ "FourierComponent" (FCOMP) 7.22.1 on page 945

Exports:

0	1	characteristic	coerce	hash
latex	makeCos	makeSin	one?	recip
sample	subtractIfCan	zero?	?~=?	?*?
?**?	?^?	?+?	?-?	-?
?=?				

— domain FSERIES FourierSeries —

```
)abbrev domain FSERIES FourierSeries
++ Author: James Davenport
++ Date Created: 17 April 1992
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain converts terms into Fourier series

FourierSeries(R:Join(CommutativeRing,Algebra(Fraction Integer)),
              E:Join(OrderedSet,AbelianGroup)):
       Algebra(R) with
         if E has canonical and R has canonical then canonical
```

```
        coerce: R -> $
          ++ coerce(r) converts coefficients into Fourier Series
        coerce: FourierComponent(E) -> $
          ++ coerce(c) converts sin/cos terms into Fourier Series
        makeSin: (E,R) -> $
          ++ makeSin(e,r) makes a sin expression with given
          ++ argument and coefficient
        makeCos: (E,R) -> $
          ++ makeCos(e,r) makes a sin expression with given
          ++argument and coefficient
  == FreeModule(R,FourierComponent(E))
add
 --representations
 Term := Record(k:FourierComponent(E),c:R)
 Rep  := List Term
 multiply : (Term,Term) -> $
 w,x1,x2:$
 t1,t2:Term
 n:NonNegativeInteger
 z:Integer
 e:FourierComponent(E)
 a:E
 r:R
 1 == [[cos 0,1]]
 coerce e ==
    sin? e and zero? argument e => 0
    if argument e < 0  then
         not sin? e => e:=cos(- argument e)
         return [[sin(- argument e),-1]]
    [[e,1]]
 multiply(t1,t2) ==
   r:=(t1.c*t2.c)*(1/2)
   s1:=argument t1.k
   s2:=argument t2.k
   sum:=s1+s2
   diff:=s1-s2
   sin? t1.k =>
     sin? t2.k =>
       makeCos(diff,r) + makeCos(sum,-r)
     makeSin(sum,r) + makeSin(diff,r)
   sin? t2.k =>
     makeSin(sum,r) + makeSin(diff,r)
   makeCos(diff,r) + makeCos(sum,r)
 x1*x2 ==
   null x1 => 0
   null x2 => 0
   +/[+/[multiply(t1,t2) for t2 in x2] for t1 in x1]
 makeCos(a,r) ==
    a<0 => [[cos(-a),r]]
    [[cos a,r]]
```

```
   makeSin(a,r) ==
      zero? a => []
      a<0 => [[sin(-a),-r]]
      [[sin a,r]]
```

———-

— **FSERIES.dotabb** —

```
"FSERIES" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FSERIES"]
"PID" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PID"]
"OAGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAGROUP"]
"FSERIES" -> "PID"
"FSERIES" -> "OAGROUP"
```

———-

7.24 domain FRAC Fraction

— **Fraction.input** —

```
)set break resume
)sys rm -f Fraction.output
)spool Fraction.output
)set message test on
)set message auto off
)clear all
--S 1 of 12
a := 11/12
--R
--R
--R        11
--R   (1)  --
--R        12
--R                                                  Type: Fraction(Integer)
--E 1

--S 2 of 12
b := 23/24
--R
--R
--R        23
--R   (2)  --
--R        24
```

```
--R                                                    Type: Fraction(Integer)
--E 2

--S 3 of 12
3 - a*b**2 + a + b/a
--R
--R
--R        313271
--R   (3)  ------
--R         76032
--R                                                    Type: Fraction(Integer)
--E 3

--S 4 of 12
numer(a)
--R
--R
--R   (4)  11
--R                                                      Type: PositiveInteger
--E 4

--S 5 of 12
denom(b)
--R
--R
--R   (5)  24
--R                                                      Type: PositiveInteger
--E 5

--S 6 of 12
r := (x**2 + 2*x + 1)/(x**2 - 2*x + 1)
--R
--R
--R         2
--R        x  + 2x + 1
--R   (6)  -----------
--R         2
--R        x  - 2x + 1
--R                                        Type: Fraction(Polynomial(Integer))
--E 6

--S 7 of 12
factor(r)
--R
--R
--R         2
--R        x  + 2x + 1
--R   (7)  -----------
--R         2
--R        x  - 2x + 1
```

```
--R                                Type: Factored(Fraction(Polynomial(Integer)))
--E 7

--S 8 of 12
map(factor,r)
--R
--R
--R               2
--R        (x + 1)
--R   (8)  --------
--R               2
--R        (x - 1)
--R                                Type: Fraction(Factored(Polynomial(Integer)))
--E 8

--S 9 of 12
continuedFraction(7/12)
--R
--R
--R          1 |     1 |     1 |     1 |
--R   (9)  +---+ + +---+ + +---+ + +---+
--R        | 1     | 1     | 2     | 2
--R                                            Type: ContinuedFraction(Integer)
--E 9

--S 10 of 12
partialFraction(7,12)
--R
--R
--R              3   1
--R   (10)  1 - -- + -
--R              2   3
--R             2
--R                                              Type: PartialFraction(Integer)
--E 10

--S 11 of 12
g := 2/3 + 4/5*%i
--R
--R
--R         2   4
--R   (11)  - + - %i
--R         3   5
--R                                            Type: Complex(Fraction(Integer))
--E 11

--S 12 of 12
g :: FRAC COMPLEX INT
--R
--R
```

```
--R         10 + 12%i
--R   (12)  ---------
--R             15
--R                                          Type: Fraction(Complex(Integer))
--E 12

)spool
)lisp (bye)
```

———-

— Fraction.help —

```
=====================================================================
Fraction examples
=====================================================================

The Fraction domain implements quotients.  The elements must
belong to a domain of category IntegralDomain: multiplication
must be commutative and the product of two non-zero elements must not
be zero.  This allows you to make fractions of most things you would
think of, but don't expect to create a fraction of two matrices!  The
abbreviation for Fraction is FRAC.

Use / to create a fraction.

  a := 11/12
    11
    --
    12
                    Type: Fraction Integer

  b := 23/24
    23
    --
    24
                    Type: Fraction Integer

The standard arithmetic operations are available.

  3 - a*b**2 + a + b/a
    313271
    ------
     76032
                    Type: Fraction Integer

Extract the numerator and denominator by using numer and denom,
respectively.
```

```
  numer(a)
    11
                    Type: PositiveInteger

  denom(b)
    24
                    Type: PositiveInteger
```

Operations like max, min, negative?, positive? and zero?
are all available if they are provided for the numerators and
denominators.

Don't expect a useful answer from factor, gcd or lcm if you apply
them to fractions.

```
  r := (x**2 + 2*x + 1)/(x**2 - 2*x + 1)
     2
    x  + 2x + 1
    -----------
     2
    x  - 2x + 1
                  Type: Fraction Polynomial Integer
```

Since all non-zero fractions are invertible, these operations have trivial
definitions.

```
  factor(r)
     2
    x  + 2x + 1
    -----------
     2
    x  - 2x + 1
                  Type: Factored Fraction Polynomial Integer
```

Use map to apply factor to the numerator and denominator, which is
probably what you mean.

```
  map(factor,r)
           2
    (x + 1)
    --------
           2
    (x - 1)
                  Type: Fraction Factored Polynomial Integer
```

Other forms of fractions are available. Use continuedFraction to
create a continued fraction.

```
  continuedFraction(7/12)
      1 |     1 |     1 |     1 |
```

```
    +---+ + +---+ + +---+ + +---+
    | 1     | 1     | 2     | 2
                  Type: ContinuedFraction Integer
```

Use partialFraction to create a partial fraction.

```
  partialFraction(7,12)
          3   1
     1 - -- + -
          2   3
         2
                  Type: PartialFraction Integer
```

Use conversion to create alternative views of fractions with objects moved in and out of the numerator and denominator.


```
  g := 2/3 + 4/5*%i
     2   4
     - + - %i
     3   5
                  Type: Complex Fraction Integer

  g :: FRAC COMPLEX INT
    10 + 12%i
    ---------
        15
                  Type: Fraction Complex Integer
```

See Also:
o)help ContinuedFraction
o)help PartialFraction
o)help Integer
o)show Fraction

———————-

7.24.1 Fraction (FRAC)



See

⇒ "Localize" (LO) 13.13.1 on page 1491
⇒ "LocalAlgebra" (LA) 13.12.1 on page 1488

Exports:

0	1	abs
associates?	characteristic	charthRoot
ceiling	coerce	conditionP
convert	D	denom
denominator	differentiate	divide
euclideanSize	eval	expressIdealMember
exquo	extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial	floor
fractionPart	gcd	gcdPolynomial
hash	init	inv
latex	lcm	map
max	min	multiEuclidean
negative?	nextItem	numer
numerator	OMwrite	one?
patternMatch	positive?	prime?
principalIdeal	random	recip
reducedSystem	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
zero?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?.?
?quo?	?rem?	

— domain FRAC Fraction —

```
)abbrev domain FRAC Fraction
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated: 12 February 1992
++ Basic Functions: Field, numer, denom
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: fraction, localization
++ References:
++ Description:
++ Fraction takes an IntegralDomain S and produces
++ the domain of Fractions with numerators and denominators from S.
++ If S is also a GcdDomain, then gcd's between numerator and
++ denominator will be cancelled during all operations.

Fraction(S: IntegralDomain): QuotientFieldCategory S with
       if S has IntegerNumberSystem and S has OpenMath then OpenMath
       if S has canonical and S has GcdDomain and S has canonicalUnitNormal
          then canonical
           ++ \spad{canonical} means that equal elements are in fact identical.
  == LocalAlgebra(S, S, S) add
    Rep:= Record(num:S, den:S)
    coerce(d:S):% == [d,1]
    zero?(x:%) == zero? x.num


    if S has GcdDomain and S has canonicalUnitNormal then
      retract(x:%):S ==
--        one?(x.den) => x.num
        ((x.den) = 1) => x.num
        error "Denominator not equal to 1"

      retractIfCan(x:%):Union(S, "failed") ==
--        one?(x.den) => x.num
        ((x.den) = 1) => x.num
        "failed"
    else
      retract(x:%):S ==
        (a:= x.num exquo x.den) case "failed" =>
           error "Denominator not equal to 1"
        a
      retractIfCan(x:%):Union(S,"failed") == x.num exquo x.den

    if S has EuclideanDomain then
      wholePart x ==
--        one?(x.den) => x.num
        ((x.den) = 1) => x.num
        x.num quo x.den
```

```
    if S has IntegerNumberSystem then

      floor x ==
--        one?(x.den) => x.num
        ((x.den) = 1) => x.num
        x < 0 => -ceiling(-x)
        wholePart x

      ceiling x ==
--        one?(x.den) => x.num
        ((x.den) = 1) => x.num
        x < 0 => -floor(-x)
        1 + wholePart x

      if S has OpenMath then
        -- TODO: somwhere this file does something which redefines the division
        -- operator. Doh!

        writeOMFrac(dev: OpenMathDevice, x: %): Void ==
          OMputApp(dev)
          OMputSymbol(dev, "nums1", "rational")
          OMwrite(dev, x.num, false)
          OMwrite(dev, x.den, false)
          OMputEndApp(dev)

        OMwrite(x: %): String ==
          s: String := ""
          sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
          dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
          OMputObject(dev)
          writeOMFrac(dev, x)
          OMputEndObject(dev)
          OMclose(dev)
          s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
          s

        OMwrite(x: %, wholeObj: Boolean): String ==
          s: String := ""
          sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
          dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
          if wholeObj then
            OMputObject(dev)
          writeOMFrac(dev, x)
          if wholeObj then
            OMputEndObject(dev)
          OMclose(dev)
          s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
          s

        OMwrite(dev: OpenMathDevice, x: %): Void ==
```

```
          OMputObject(dev)
          writeOMFrac(dev, x)
          OMputEndObject(dev)

        OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
          if wholeObj then
            OMputObject(dev)
          writeOMFrac(dev, x)
          if wholeObj then
            OMputEndObject(dev)

    if S has GcdDomain then
      cancelGcd: % -> S
      normalize: % -> %

      normalize x ==
        zero?(x.num) => 0
--        one?(x.den) => x
        ((x.den) = 1) => x
        uca := unitNormal(x.den)
        zero?(x.den := uca.canonical) => error "division by zero"
        x.num := x.num * uca.associate
        x

      recip x ==
        zero?(x.num) => "failed"
        normalize [x.den, x.num]

      cancelGcd x ==
--        one?(x.den) => x.den
        ((x.den) = 1) => x.den
        d := gcd(x.num, x.den)
        xn := x.num exquo d
        xn case "failed" =>
          error "gcd not gcd in QF cancelGcd (numerator)"
        xd := x.den exquo d
        xd case "failed" =>
          error "gcd not gcd in QF cancelGcd (denominator)"
        x.num := xn :: S
        x.den := xd :: S
        d

      nn:S / dd:S ==
        zero? dd => error "division by zero"
        cancelGcd(z := [nn, dd])
        normalize z

      x + y  ==
        zero? y => x
        zero? x => y
```

```
        z := [x.den,y.den]
        d := cancelGcd z
        g := [z.den * x.num + z.num * y.num, d]
        cancelGcd g
        g.den := g.den * z.num * z.den
        normalize g

      -- We can not rely on the defaulting mechanism
      -- to supply a definition for -, even though this
      -- definition would do, for thefollowing reasons:
      --  1) The user could have defined a subtraction
      --     in Localize, which would not work for
      --     QuotientField;
      --  2) even if he doesn't, the system currently
      --     places a default definition in Localize,
      --     which uses Localize's +, which does not
      --     cancel gcds
      x - y  ==
        zero? y => x
        z := [x.den, y.den]
        d := cancelGcd z
        g := [z.den * x.num - z.num * y.num, d]
        cancelGcd g
        g.den := g.den * z.num * z.den
        normalize g

      x:% * y:%  ==
        zero? x or zero? y => 0
--        one? x => y
        (x = 1) => y
--        one? y => x
        (y = 1) => x
        (x, y) := ([x.num, y.den], [y.num, x.den])
        cancelGcd x; cancelGcd y;
        normalize [x.num * y.num, x.den * y.den]

      n:Integer * x:% ==
        y := [n::S, x.den]
        cancelGcd y
        normalize [x.num * y.num, y.den]

      nn:S * x:% ==
        y := [nn, x.den]
        cancelGcd y
        normalize [x.num * y.num, y.den]

      differentiate(x:%, deriv:S -> S) ==
        y := [deriv(x.den), x.den]
        d := cancelGcd(y)
        y.num := deriv(x.num) * y.den - x.num * y.num
```

```
        (d, y.den) := (y.den, d)
        cancelGcd y
        y.den := y.den * d * d
        normalize y

      if S has canonicalUnitNormal then
        x = y == (x.num = y.num) and (x.den = y.den)
    --x / dd == (cancelGcd (z:=[x.num,dd*x.den]); normalize z)

--        one? x == one? (x.num) and one? (x.den)
        one? x == ((x.num) = 1) and ((x.den) = 1)
                  -- again assuming canonical nature of representation

    else
      nn:S/dd:S == if zero? dd then error "division by zero" else [nn,dd]

      recip x ==
        zero?(x.num) => "failed"
        [x.den, x.num]

    if (S has RetractableTo Fraction Integer) then
      retract(x:%):Fraction(Integer) == retract(retract(x)@S)

      retractIfCan(x:%):Union(Fraction Integer, "failed") ==
        (u := retractIfCan(x)@Union(S, "failed")) case "failed" => "failed"
        retractIfCan(u::S)

    else if (S has RetractableTo Integer) then
      retract(x:%):Fraction(Integer) ==
        retract(numer x) / retract(denom x)

      retractIfCan(x:%):Union(Fraction Integer, "failed") ==
        (n := retractIfCan numer x) case "failed" => "failed"
        (d := retractIfCan denom x) case "failed" => "failed"
        (n::Integer) / (d::Integer)

    QFP ==> SparseUnivariatePolynomial %
    DP ==> SparseUnivariatePolynomial S
    import UnivariatePolynomialCategoryFunctions2(%,QFP,S,DP)
    import UnivariatePolynomialCategoryFunctions2(S,DP,%,QFP)

    if S has GcdDomain then
       gcdPolynomial(pp,qq) ==
          zero? pp => qq
          zero? qq => pp
          zero? degree pp or zero? degree qq => 1
          denpp:="lcm"/[denom u for u in coefficients pp]
          ppD:DP:=map(x+->retract(x*denpp),pp)
          denqq:="lcm"/[denom u for u in coefficients qq]
          qqD:DP:=map(x+->retract(x*denqq),qq)
```

```
          g:=gcdPolynomial(ppD,qqD)
          zero? degree g => 1
--          one? (lc:=leadingCoefficient g) => map(#1::%,g)
          ((lc:=leadingCoefficient g) = 1) => map(x+->x::%,g)
          map(x+->x/lc,g)

    if (S has PolynomialFactorizationExplicit) then
       -- we'll let the solveLinearPolynomialEquations operator
       -- default from Field
       pp,qq: QFP
       lpp: List QFP
       import Factored SparseUnivariatePolynomial %
       if S has CharacteristicNonZero then
          if S has canonicalUnitNormal and S has GcdDomain then
             charthRoot x ==
               n:= charthRoot x.num
               n case "failed" => "failed"
               d:=charthRoot x.den
               d case "failed" => "failed"
               n/d
          else
             charthRoot x ==
               -- to find x = p-th root of n/d
               -- observe that xd is p-th root of n*d**(p-1)
               ans:=charthRoot(x.num *
                      (x.den)**(characteristic()$%-1)::NonNegativeInteger)
               ans case "failed" => "failed"
               ans / x.den
          clear: List % -> List S
          clear l ==
             d:="lcm"/[x.den for x in l]
             [ x.num * (d exquo x.den)::S for x in l]
          mat: Matrix %
          conditionP mat ==
            matD: Matrix S
            matD:= matrix [ clear l for l in listOfLists mat ]
            ansD := conditionP matD
            ansD case "failed" => "failed"
            ansDD:=ansD :: Vector(S)
            [ ansDD(i)::% for i in 1..#ansDD]$Vector(%)

       factorPolynomial(pp) ==
          zero? pp => 0
          denpp:="lcm"/[denom u for u in coefficients pp]
          ppD:DP:=map(x+->retract(x*denpp),pp)
          ff:=factorPolynomial ppD
          den1:%:=denpp::%
          lfact:List Record(flg:Union("nil", "sqfr", "irred", "prime"),
                            fctr:QFP, xpnt:Integer)
          lfact:= [[w.flg,
```

```
                  if leadingCoefficient w.fctr =1 then
                         map(x+->x::%,w.fctr)
                  else (lc:=(leadingCoefficient w.fctr)::%;
                         den1:=den1/lc**w.xpnt;
                          map(x+->x::%/lc,w.fctr)),
                w.xpnt] for w in factorList ff]
      makeFR(map(x+->x::%/den1,unit(ff)),lfact)
   factorSquareFreePolynomial(pp) ==
      zero? pp => 0
      degree pp = 0 => makeFR(pp,empty())
      lcpp:=leadingCoefficient pp
      pp:=pp/lcpp
      denpp:="lcm"/[denom u for u in coefficients pp]
      ppD:DP:=map(x+->retract(x*denpp),pp)
      ff:=factorSquareFreePolynomial ppD
      den1:%:=denpp::%/lcpp
      lfact:List Record(flg:Union("nil", "sqfr", "irred", "prime"),
                        fctr:QFP, xpnt:Integer)
      lfact:= [[w.flg,
                  if leadingCoefficient w.fctr =1 then
                         map(x+->x::%,w.fctr)
                  else (lc:=(leadingCoefficient w.fctr)::%;
                         den1:=den1/lc**w.xpnt;
                          map(x+->x::%/lc,w.fctr)),
                w.xpnt] for w in factorList ff]
      makeFR(map(x+->x::%/den1,unit(ff)),lfact)
```

———-

— FRAC.dotabb —

```
"FRAC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FRAC"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"FRAC" -> "PFECAT"
```

———-

7.25 domain FRIDEAL FractionalIdeal

— FractionalIdeal.input —

```
)set break resume
)sys rm -f FractionalIdeal.output
)spool FractionalIdeal.output
```

```
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FractionalIdeal
--R
--R FractionalIdeal(R: EuclideanDomain,F: QuotientFieldCategory(R),UP: UnivariatePolynomialCateg
--R Abbreviation for FractionalIdeal is FRIDEAL
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FRIDEAL
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R basis : % -> Vector(A)                coerce : % -> OutputForm
--R commutator : (%,%) -> %               conjugate : (%,%) -> %
--R denom : % -> R                        hash : % -> SingleInteger
--R ideal : Vector(A) -> %                inv : % -> %
--R latex : % -> String                   minimize : % -> %
--R norm : % -> F                         numer : % -> Vector(A)
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R sample : () -> %                      ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R randomLC : (NonNegativeInteger,Vector(A)) -> A
--R
--E 1

)spool
)lisp (bye)
```

———-


— FractionalIdeal.help —

```
=====================================================================
FractionalIdeal examples
=====================================================================

See Also:
o )show FractionalIdeal
```

———-

7.25.1 FractionalIdeal (FRIDEAL)



See

⇒ "FramedModule" (FRMOD) 7.26.1 on page 970
⇒ "HyperellipticFiniteDivisor" (HELLFDIV) 9.11.1 on page 1153
⇒ "FiniteDivisor" (FDIV) 7.4.1 on page 783

Exports:

1	basis	coerce	commutator	conjugate
denom	hash	ideal	inv	latex
minimize	norm	numer	one?	randomLC
recip	sample	?~=?	?**?	?^?
?*?	?**?	?/?	?=?	?^?

— domain FRIDEAL FractionalIdeal —

```
)abbrev domain FRIDEAL FractionalIdeal
++ Author: Manuel Bronstein
++ Date Created: 27 Jan 1989
++ Date Last Updated: 30 July 1993
++ Keywords: ideal, algebra, module.
++ Examples: )r FRIDEAL INPUT
++ Description:
++ Fractional ideals in a framed algebra.

FractionalIdeal(R, F, UP, A): Exports == Implementation where
  R : EuclideanDomain
  F : QuotientFieldCategory R
  UP: UnivariatePolynomialCategory F
  A : Join(FramedAlgebra(F, UP), RetractableTo F)

  VF  ==> Vector F
  VA  ==> Vector A
  UPA ==> SparseUnivariatePolynomial A
  QF  ==> Fraction UP

  Exports ==> Group with
    ideal   : VA -> %
```

```
    ++ ideal([f1,...,fn]) returns the ideal \spad{(f1,...,fn)}.
  basis   : %  -> VA
    ++ basis((f1,...,fn)) returns the vector \spad{[f1,...,fn]}.
  norm    : %  -> F
    ++ norm(I) returns the norm of the ideal I.
  numer   : %  -> VA
    ++ numer(1/d * (f1,...,fn)) = the vector \spad{[f1,...,fn]}.
  denom   : %  -> R
    ++ denom(1/d * (f1,...,fn)) returns d.
  minimize: %  -> %
    ++ minimize(I) returns a reduced set of generators for \spad{I}.
  randomLC: (NonNegativeInteger, VA) -> A
    ++ randomLC(n,x) should be local but conditional.

Implementation ==> add
  import CommonDenominator(R, F, VF)
  import MatrixCommonDenominator(UP, QF)
  import InnerCommonDenominator(R, F, List R, List F)
  import MatrixCategoryFunctions2(F, Vector F, Vector F, Matrix F,
                    UP, Vector UP, Vector UP, Matrix UP)
  import MatrixCategoryFunctions2(UP, Vector UP, Vector UP,
                    Matrix UP, F, Vector F, Vector F, Matrix F)
  import MatrixCategoryFunctions2(UP, Vector UP, Vector UP,
                    Matrix UP, QF, Vector QF, Vector QF, Matrix QF)

  Rep := Record(num:VA, den:R)

  poly    : % -> UPA
  invrep  : Matrix F -> A
  upmat   : (A, NonNegativeInteger) -> Matrix UP
  summat  : % -> Matrix UP
  num2O   : VA -> OutputForm
  agcd    : List A -> R
  vgcd    : VF -> R
  mkIdeal : (VA, R) -> %
  intIdeal: (List A, R) -> %
  ret?    : VA -> Boolean
  tryRange: (NonNegativeInteger, VA, R, %) -> Union(%, "failed")

  1               == [[1]$VA, 1]
  numer i         == i.num
  denom i         == i.den
  mkIdeal(v, d)   == [v, d]
  invrep m        == represents(transpose(m) * coordinates(1$A))
  upmat(x, i)     == map(s +-> monomial(s, i)$UP, regularRepresentation x)
  ret? v          == any?(s+->retractIfCan(s)@Union(F,"failed") case F, v)
  x = y           == denom(x) = denom(y) and numer(x) = numer(y)
  agcd l  == reduce("gcd", [vgcd coordinates a for a in l]$List(R), 0)

  norm i ==
```

```
    ("gcd"/[retract(u)@R for u in coefficients determinant summat i])
            / denom(i) ** rank()$A

  tryRange(range, nm, nrm, i) ==
    for j in 0..10 repeat
      a := randomLC(10 * range, nm)
      unit? gcd((retract(norm a)@R exquo nrm)::R, nrm) =>
                              return intIdeal([nrm::F::A, a], denom i)
    "failed"

  summat i ==
    m := minIndex(v := numer i)
    reduce("+",
          [upmat(qelt(v, j + m), j) for j in 0..#v-1]$List(Matrix UP))

  inv i ==
    m  := inverse(map(s+->s::QF, summat i))::Matrix(QF)
    cd  := splitDenominator(denom(i)::F::UP::QF * m)
    cd2 := splitDenominator coefficients(cd.den)
    invd:= cd2.den / reduce("gcd", cd2.num)
    d   := reduce("max", [degree p for p in parts(cd.num)])
    ideal
      [invd * invrep map(s+->coefficient(s, j), cd.num) for j in 0..d]$VA

  ideal v ==
    d := reduce("lcm", [commonDenominator coordinates qelt(v, i)
                        for i in minIndex v .. maxIndex v]$List(R))
    intIdeal([d::F * qelt(v, i) for i in minIndex v .. maxIndex v], d)

  intIdeal(l, d) ==
    lr := empty()$List(R)
    nr := empty()$List(A)
    for x in removeDuplicates l repeat
      if (u := retractIfCan(x)@Union(F, "failed")) case F
        then lr := concat(retract(u::F)@R, lr)
        else nr := concat(x, nr)
    r    := reduce("gcd", lr, 0)
    g    := agcd nr
    a    := (r quo (b := gcd(gcd(d, r), g)))::F::A
    d    := d quo b
    r ^= 0 and ((g exquo r) case R) => mkIdeal([a], d)
    invb := inv(b::F)
    va:VA := [invb * m for m in nr]
    zero? a => mkIdeal(va, d)
    mkIdeal(concat(a, va), d)

  vgcd v ==
    reduce("gcd",
           [retract(v.i)@R for i in minIndex v .. maxIndex v]$List(R))
```

```
    poly i ==
      m := minIndex(v := numer i)
      +/[monomial(qelt(v, i + m), i) for i in 0..#v-1]

    i1 * i2 ==
      intIdeal(coefficients(poly i1 * poly i2), denom i1 * denom i2)

    i:$ ** m:Integer ==
      m < 0 => inv(i) ** (-m)
      n := m::NonNegativeInteger
      v := numer i
      intIdeal([qelt(v, j) ** n for j in minIndex v .. maxIndex v],
               denom(i) ** n)

    num2O v ==
      paren [qelt(v, i)::OutputForm
             for i in minIndex v .. maxIndex v]$List(OutputForm)

    basis i ==
      v := numer i
      d := inv(denom(i)::F)
      [d * qelt(v, j) for j in minIndex v .. maxIndex v]

    coerce(i:$):OutputForm ==
      nm := num2O numer i
--      one? denom i => nm
      (denom i = 1) => nm
      (1::Integer::OutputForm) / (denom(i)::OutputForm) * nm

    if F has Finite then
      randomLC(m, v) ==
        +/[random()$F * qelt(v, j) for j in minIndex v .. maxIndex v]
    else
      randomLC(m, v) ==
        +/[(random()$Integer rem m::Integer) * qelt(v, j)
            for j in minIndex v .. maxIndex v]

    minimize i ==
      n := (#(nm := numer i))
--      one?(n) or (n < 3 and ret? nm) => i
      (n = 1) or (n < 3 and ret? nm) => i
      nrm    := retract(norm mkIdeal(nm, 1))@R
      for range in 1..5 repeat
        (u := tryRange(range, nm, nrm, i)) case $ => return(u::$)
      i
```

———-

— **FRIDEAL.dotabb** —

```
"FRIDEAL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FRIDEAL"]
"FRAMALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRAMALG"]
"FRIDEAL" -> "FRAMALG"
```

———-

7.26 domain FRMOD FramedModule

— **FramedModule.input** —

```
)set break resume
)sys rm -f FramedModule.output
)spool FramedModule.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FramedModule
--R
--R FramedModule(R: EuclideanDomain,F: QuotientFieldCategory(R),UP: UnivariatePolynomialCategory(F),A: Frame
--R Abbreviation for FramedModule is FRMOD
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FRMOD
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?**? : (%,PositiveInteger) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R ?^? : (%,PositiveInteger) -> %        basis : % -> Vector(A)
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   module : Vector(A) -> %
--R norm : % -> F                         one? : % -> Boolean
--R recip : % -> Union(%,"failed")        sample : () -> %
--R ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R module : FractionalIdeal(R,F,UP,A) -> % if A has RETRACT(F)
--R
--E 1

)spool
)lisp (bye)
```

———-


— FramedModule.help —

```
====================================================================
FramedModule examples
====================================================================

See Also:
o )show FramedModule
```

———-

7.26.1 FramedModule (FRMOD)



See

⇒ “FractionalIdeal” (FRIDEAL) 7.25.1 on page 965
⇒ “HyperellipticFiniteDivisor” (HELLFDIV) 9.11.1 on page 1153
⇒ “FiniteDivisor” (FDIV) 7.4.1 on page 783

Exports:

1	basis	coerce	hash	latex
module	norm	one?	recip	sample
?~=?	?**?	?^?	?*?	?**?
?=?				

— domain FRMOD FramedModule —

```
)abbrev domain FRMOD FramedModule
++ Author: Manuel Bronstein
++ Date Created: 27 Jan 1989
++ Date Last Updated: 24 Jul 1990
++ Keywords: ideal, algebra, module.
++ Description:
++ Module representation of fractional ideals.
```

```
FramedModule(R, F, UP, A, ibasis): Exports == Implementation where
  R     : EuclideanDomain
  F     : QuotientFieldCategory R
  UP    : UnivariatePolynomialCategory F
  A     : FramedAlgebra(F, UP)
  ibasis: Vector A

  VR  ==> Vector R
  VF  ==> Vector F
  VA  ==> Vector A
  M   ==> Matrix F

  Exports ==> Monoid with
    basis : %  -> VA
      ++ basis((f1,...,fn)) = the vector \spad{[f1,...,fn]}.
    norm  : %  -> F
      ++ norm(f) returns the norm of the module f.
    module: VA -> %
      ++ module([f1,...,fn]) = the module generated by \spad{(f1,...,fn)}
      ++ over R.
    if A has RetractableTo F then
      module: FractionalIdeal(R, F, UP, A) -> %
        ++ module(I) returns I viewed has a module over R.

  Implementation ==> add
    import MatrixCommonDenominator(R, F)
    import ModularHermitianRowReduction(R)

    Rep  := VA

    iflag?:Reference(Boolean) := ref true
    wflag?:Reference(Boolean) := ref true
    imat := new(#ibasis, #ibasis, 0)$M
    wmat := new(#ibasis, #ibasis, 0)$M

    rowdiv      : (VR, R)  -> VF
    vectProd    : (VA, VA) -> VA
    wmatrix     : VA -> M
    W2A         : VF -> A
    intmat      : () -> M
    invintmat   : () -> M
    getintmat   : () -> Boolean
    getinvintmat: () -> Boolean

    1                     == ibasis
    module(v:VA)          == v
    basis m               == m pretend VA
    rowdiv(r, f)          == [r.i / f for i in minIndex r..maxIndex r]
    coerce(m:%):OutputForm == coerce(basis m)$VA
```

```
W2A v                  == represents(v * intmat())
wmatrix v              == coordinates(v) * invintmat()

getinvintmat() ==
  m := inverse(intmat())::M
  for i in minRowIndex m .. maxRowIndex m repeat
    for j in minColIndex m .. maxColIndex m repeat
      imat(i, j) := qelt(m, i, j)
  false

getintmat() ==
  m := coordinates ibasis
  for i in minRowIndex m .. maxRowIndex m repeat
    for j in minColIndex m .. maxColIndex m repeat
      wmat(i, j) := qelt(m, i, j)
  false

invintmat() ==
  if iflag?() then iflag?() := getinvintmat()
  imat

intmat() ==
  if wflag?() then wflag?() := getintmat()
  wmat

vectProd(v1, v2) ==
  k := minIndex(v := new(#v1 * #v2, 0)$VA)
  for i in minIndex v1 .. maxIndex v1 repeat
    for j in minIndex v2 .. maxIndex v2 repeat
      qsetelt_!(v, k, qelt(v1, i) * qelt(v2, j))
      k := k + 1
  v pretend VA

norm m ==
  #(basis m) ^= #ibasis => error "Module not of rank n"
  determinant(coordinates(basis m) * invintmat())

m1 * m2 ==
  m := rowEch((cd := splitDenominator wmatrix(
                                  vectProd(basis m1, basis m2))).num)
  module [u for i in minRowIndex m .. maxRowIndex m |
                       (u := W2A rowdiv(row(m, i), cd.den)) ^= 0]$VA

if A has RetractableTo F then
  module(i:FractionalIdeal(R, F, UP, A)) ==
    module(basis i) * module(ibasis)
```

— **FRMOD.dotabb** —

```
"FRMOD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FRMOD"]
"FRAMALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRAMALG"]
"FRMOD" -> "FRAMALG"
```

———-

7.27 domain FAGROUP FreeAbelianGroup

— **FreeAbelianGroup.input** —

```
)set break resume
)sys rm -f FreeAbelianGroup.output
)spool FreeAbelianGroup.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FreeAbelianGroup
--R
--R FreeAbelianGroup(S: SetCategory)  is a domain constructor
--R Abbreviation for FreeAbelianGroup is FAGROUP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FAGROUP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,S) -> %                ?*? : (%,Integer) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (S,%) -> %                      ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                0 : () -> %
--R coefficient : (S,%) -> Integer        coerce : S -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   mapGen : ((S -> S),%) -> %
--R nthCoef : (%,Integer) -> Integer      nthFactor : (%,Integer) -> S
--R retract : % -> S                      sample : () -> %
--R size : % -> NonNegativeInteger        zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
```

```
--R highCommonTerms : (%,%) -> % if Integer has OAMON
--R mapCoef : ((Integer -> Integer),%) -> %
--R max : (%,%) -> % if S has ORDSET
--R min : (%,%) -> % if S has ORDSET
--R retractIfCan : % -> Union(S,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R terms : % -> List(Record(gen: S,exp: Integer))
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FreeAbelianGroup.help** —

```
=====================================================================
FreeAbelianGroup examples
=====================================================================

See Also:
o )show FreeAbelianGroup
```

———-

7.27.1 FreeAbelianGroup (FAGROUP)



See

⇒ “ListMonoidOps” (LMOPS) 13.10.1 on page 1477
⇒ “FreeMonoid” (FMONOID) 7.32.1 on page 991
⇒ “FreeGroup” (FGROUP) 7.29.1 on page 980
⇒ “InnerFreeAbelianMonoid” (IFAMON) 10.22.1 on page 1254
⇒ “FreeAbelianMonoid” (FAMONOID) 7.28.1 on page 977

Exports:

0	coefficient	coerce	hash	highCommonTerms
latex	mapCoef	mapGen	max	min
nthCoef	nthFactor	retract	retractIfCan	sample
size	subtractIfCan	terms	zero?	?~=?
?*?	?<?	?<=?	?>?	?>=?
?+?	?-?	-?	?=?	

— domain FAGROUP FreeAbelianGroup —

```
)abbrev domain FAGROUP FreeAbelianGroup
++ Free abelian group on any set of generators
++ Author: Manuel Bronstein
++ Date Created: November 1989
++ Date Last Updated: 6 June 1991
++ Description:
++ The free abelian group on a set S is the monoid of finite sums of
++ the form \spad{reduce(+,[ni * si])} where the si's are in S, and the ni's
++ are integers. The operation is commutative.

FreeAbelianGroup(S:SetCategory): Exports == Implementation where
  Exports ==> Join(AbelianGroup, Module Integer,
                   FreeAbelianMonoidCategory(S, Integer)) with
    if S has OrderedSet then OrderedSet

  Implementation ==> InnerFreeAbelianMonoid(S, Integer, 1) add
    - f == mapCoef("-", f)

    if S has OrderedSet then
      inmax: List Record(gen: S, exp: Integer) -> Record(gen: S, exp:Integer)

      inmax l ==
        mx := first l
        for t in rest l repeat
          if mx.gen < t.gen then mx := t
        mx

      -- lexicographic order
      a < b ==
        zero? a  =>
          zero? b => false
          0 < (inmax terms b).exp
        ta := inmax terms a
        zero? b => ta.exp < 0
        tb := inmax terms b
        ta.gen < tb.gen => 0 < tb.exp
        tb.gen < ta.gen => ta.exp < 0
        ta.exp < tb.exp => true
        tb.exp < ta.exp => false
```

```
        lc := ta.exp * ta.gen
        (a - lc) < (b - lc)
```

———-

— **FAGROUP.dotabb** —

```
"FAGROUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FAGROUP"]
"PID" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PID"]
"OAGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAGROUP"]
"FAGROUP" -> "PID"
"FAGROUP" -> "OAGROUP"
```

———-

7.28 domain FAMONOID FreeAbelianMonoid

— **FreeAbelianMonoid.input** —

```
)set break resume
)sys rm -f FreeAbelianMonoid.output
)spool FreeAbelianMonoid.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FreeAbelianMonoid
--R
--R FreeAbelianMonoid(S: SetCategory)  is a domain constructor
--R Abbreviation for FreeAbelianMonoid is FAMONOID
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FAMONOID
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (NonNegativeInteger,S) -> %     ?*? : (PositiveInteger,%) -> %
--R ?+? : (S,%) -> %                      ?+? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                0 : () -> %
--R coerce : S -> %                       coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R mapGen : ((S -> S),%) -> %            nthFactor : (%,Integer) -> S
--R retract : % -> S                      sample : () -> %
--R size : % -> NonNegativeInteger        zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
```

```
--R ?*? : (NonNegativeInteger,%) -> %
--R coefficient : (S,%) -> NonNegativeInteger
--R highCommonTerms : (%,%) -> % if NonNegativeInteger has OAMON
--R mapCoef : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R nthCoef : (%,Integer) -> NonNegativeInteger
--R retractIfCan : % -> Union(S,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R terms : % -> List(Record(gen: S,exp: NonNegativeInteger))
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FreeAbelianMonoid.help** —

```
=====================================================================
FreeAbelianMonoid examples
=====================================================================

See Also:
o )show FreeAbelianMonoid
```

———-

7.28.1 FreeAbelianMonoid (FAMONOID)



See

⇒ “ListMonoidOps” (LMOPS) 13.10.1 on page 1477
⇒ “FreeMonoid” (FMONOID) 7.32.1 on page 991
⇒ “FreeGroup” (FGROUP) 7.29.1 on page 980
⇒ “InnerFreeAbelianMonoid” (IFAMON) 10.22.1 on page 1254
⇒ “FreeAbelianGroup” (FAGROUP) 7.27.1 on page 974

Exports:

0	coefficient	coerce	hash	highCommonTerms
latex	mapCoef	mapGen	nthCoef	nthFactor
retract	retractIfCan	sample	size	subtractIfCan
terms	zero?	?~=?	?*?	?+?
?=?				

— domain FAMONOID FreeAbelianMonoid —

```
)abbrev domain FAMONOID FreeAbelianMonoid
++ Free abelian monoid on any set of generators
++ Author: Manuel Bronstein
++ Date Created: November 1989
++ Date Last Updated: 6 June 1991
++ Description:
++ The free abelian monoid on a set S is the monoid of finite sums of
++ the form \spad{reduce(+,[ni * si])} where the si's are in S, and the ni's
++ are non-negative integers. The operation is commutative.

FreeAbelianMonoid(S: SetCategory):
  FreeAbelianMonoidCategory(S, NonNegativeInteger)
    == InnerFreeAbelianMonoid(S, NonNegativeInteger, 1)
```

———-

— FAMONOID.dotabb —

```
"FAMONOID" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FAMONOID"]
"OAMONS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAMONS"]
"FAMONOID" -> "OAMONS"
```

———-

7.29 domain FGROUP FreeGroup

— FreeGroup.input —

```
)set break resume
)sys rm -f FreeGroup.output
)spool FreeGroup.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show FreeGroup
--R
--R FreeGroup(S: SetCategory)  is a domain constructor
--R Abbreviation for FreeGroup is FGROUP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FGROUP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,S) -> %                      ?*? : (S,%) -> %
--R ?*? : (%,%) -> %                      ?**? : (S,Integer) -> %
--R ?**? : (%,Integer) -> %               ?**? : (%,PositiveInteger) -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           ?^? : (%,Integer) -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : S -> %
--R coerce : % -> OutputForm              commutator : (%,%) -> %
--R conjugate : (%,%) -> %                hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R mapGen : ((S -> S),%) -> %            nthExpon : (%,Integer) -> Integer
--R nthFactor : (%,Integer) -> S          one? : % -> Boolean
--R recip : % -> Union(%,"failed")        retract : % -> S
--R sample : () -> %                      size : % -> NonNegativeInteger
--R ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R factors : % -> List(Record(gen: S,exp: Integer))
--R mapExpon : ((Integer -> Integer),%) -> %
--R retractIfCan : % -> Union(S,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FreeGroup.help** —

```
=====================================================================
FreeGroup examples
=====================================================================

See Also:
o )show FreeGroup
```

———-

7.29.1 FreeGroup (FGROUP)



See

⇒ "ListMonoidOps" (LMOPS) 13.10.1 on page 1477
⇒ "FreeMonoid" (FMONOID) 7.32.1 on page 991
⇒ "InnerFreeAbelianMonoid" (IFAMON) 10.22.1 on page 1254
⇒ "FreeAbelianMonoid" (FAMONOID) 7.28.1 on page 977
⇒ "FreeAbelianGroup" (FAGROUP) 7.27.1 on page 974

Exports:

1	coerce	commutator	conjugate	factors
hash	inv	latex	mapExpon	mapGen
nthExpon	nthFactor	one?	recip	retract
retractIfCan	sample	size	?~=?	?**?
?^?	?*?	?/?	?=?	

— domain FGROUP FreeGroup —

```
)abbrev domain FGROUP FreeGroup
++ Free group on any set of generators
++ Author: Stephen M. Watt
++ Date Created: ???
++ Date Last Updated: 6 June 1991
++ Description:
++ The free group on a set S is the group of finite products of
++ the form \spad{reduce(*,[si ** ni])} where the si's are in S, and the ni's
++ are integers. The multiplication is not commutative.

FreeGroup(S: SetCategory): Join(Group, RetractableTo S) with
        "*":    (S, $) -> $
          ++ s * x returns the product of x by s on the left.
        "*":    ($, S) -> $
          ++ x * s returns the product of x by s on the right.
        "**"         : (S, Integer) -> $
          ++ s ** n returns the product of s by itself n times.
        size         : $ -> NonNegativeInteger
          ++ size(x) returns the number of monomials in x.
```

```
        nthExpon     : ($, Integer) -> Integer
          ++ nthExpon(x, n) returns the exponent of the n^th monomial of x.
        nthFactor    : ($, Integer) -> S
          ++ nthFactor(x, n) returns the factor of the n^th monomial of x.
        mapExpon     : (Integer -> Integer, $) -> $
          ++ mapExpon(f, a1\^e1 ... an\^en) returns
          ++ \spad{a1\^f(e1) ... an\^f(en)}.
        mapGen       : (S -> S, $) -> $
          ++ mapGen(f, a1\^e1 ... an\^en) returns
          ++ \spad{f(a1)\^e1 ... f(an)\^en}.
        factors      : $ -> List Record(gen: S, exp: Integer)
          ++ factors(a1\^e1,...,an\^en) returns \spad{[[a1, e1],...,[an, en]]}.
    == ListMonoidOps(S, Integer, 1) add
        Rep := ListMonoidOps(S, Integer, 1)

        1                       == makeUnit()
        one? f                  == empty? listOfMonoms f
        s:S ** n:Integer        == makeTerm(s, n)
        f:$ * s:S               == rightMult(f, s)
        s:S * f:$               == leftMult(s, f)
        inv f                   == reverse_! mapExpon("-", f)
        factors f               == copy listOfMonoms f
        mapExpon(f, x)          == mapExpon(f, x)$Rep
        mapGen(f, x)            == mapGen(f, x)$Rep
        coerce(f:$):OutputForm  == outputForm(f, "*", "**", 1)

        f:$ * g:$ ==
            one? f => g
            one? g => f
            r := reverse listOfMonoms f
            q := copy listOfMonoms g
            while not empty? r and not empty? q and r.first.gen = q.first.gen
                and r.first.exp = -q.first.exp repeat
                     r := rest r
                     q := rest q
            empty? r => makeMulti q
            empty? q => makeMulti reverse_! r
            r.first.gen = q.first.gen =>
              setlast_!(h := reverse_! r,
                                [q.first.gen, q.first.exp + r.first.exp])
              makeMulti concat_!(h, rest q)
            makeMulti concat_!(reverse_! r, q)
```

———-

— FGROUP.dotabb —

```
"FGROUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FGROUP"]
```

```
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"FGROUP" -> "FLAGG"
"FGROUP" -> "FLAGG-"
```

———-

7.30 domain FM FreeModule

— FreeModule.input —

```
)set break resume
)sys rm -f FreeModule.output
)spool FreeModule.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FreeModule
--R FreeModule(R: Ring,S: OrderedSet)  is a domain constructor
--R Abbreviation for FreeModule is FM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R leadingCoefficient : % -> R           leadingSupport : % -> S
--R map : ((R -> R),%) -> %               monomial : (R,S) -> %
--R reductum : % -> %                     sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **FreeModule.help** —

```
====================================================================
FreeModule examples
====================================================================

See Also:
o )show FreeModule
```

———-

7.30.1 FreeModule (FM)



See

⇒ “PolynomialRing” (PR) 17.27.1 on page 2058
⇒ “SparseUnivariatePolynomial” (SUP) 20.18.1 on page 2434
⇒ “UnivariatePolynomial” (UP) 22.4.1 on page 2794

Exports:

0	coerce	hash	latex	leadingCoefficient
leadingSupport	map	monomial	reductum	sample
subtractIfCan	zero?	?~=?	?*?	?+?
?-?	-?	?=?		

— **domain FM FreeModule** —

```
)abbrev domain FM FreeModule
++ Author: Dave Barton, James Davenport, Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: BiModule(R,R)
++ Related Constructors:
++ Also See:
++ AMS Classifications:
```

```
++ Keywords:
++ References:
++ Description:
++ A bi-module is a free module
++ over a ring with generators indexed by an ordered set.
++ Each element can be expressed as a finite linear combination of
++ generators. Only non-zero terms are stored.

FreeModule(R:Ring,S:OrderedSet):
        Join(BiModule(R,R),IndexedDirectProductCategory(R,S)) with
    if R has CommutativeRing then Module(R)
 == IndexedDirectProductAbelianGroup(R,S) add
    --representations
       Term:=  Record(k:S,c:R)
       Rep:=  List Term
    --declarations
       x,y: %
       r: R
       n: Integer
       f: R -> R
       s: S
    --define
       if R has EntireRing then
         r * x  ==
             zero? r => 0
--             one? r => x
             (r = 1) => x
           --map(r*#1,x)
             [[u.k,r*u.c] for u in x ]
       else
         r * x  ==
             zero? r => 0
--             one? r => x
             (r = 1) => x
           --map(r*#1,x)
             [[u.k,a] for u in x | (a:=r*u.c) ^= 0$R]
       if R has EntireRing then
         x * r  ==
             zero? r => 0
--             one? r => x
             (r = 1) => x
           --map(r*#1,x)
             [[u.k,u.c*r] for u in x ]
       else
         x * r  ==
             zero? r => 0
--             one? r => x
             (r = 1) => x
           --map(r*#1,x)
             [[u.k,a] for u in x | (a:=u.c*r) ^= 0$R]
```

```
       coerce(x) : OutputForm ==
         null x => (0$R) :: OutputForm
         le : List OutputForm := nil
         for rec in reverse x repeat
           rec.c = 1 => le := cons(rec.k :: OutputForm, le)
           le := cons(rec.c :: OutputForm *  rec.k :: OutputForm, le)
         reduce("+",le)
```

———-

— FM.dotabb —

```
"FM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FM"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FM" -> "FLAGG"
```

———-

7.31 domain FM1 FreeModule1

— FreeModule1.input —

```
)set break resume
)sys rm -f FreeModule1.output
)spool FreeModule1.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FreeModule1
--R
--R FreeModule1(R: Ring,S: OrderedSet)  is a domain constructor
--R Abbreviation for FreeModule1 is FM1
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FM1
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (S,R) -> %                      ?*? : (R,S) -> %
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
```

```
--R 0 : () -> %                          coefficient : (%,S) -> R
--R coefficients : % -> List(R)          coerce : S -> %
--R coerce : % -> OutputForm             hash : % -> SingleInteger
--R latex : % -> String                  leadingCoefficient : % -> R
--R leadingMonomial : % -> S             map : ((R -> R),%) -> %
--R monom : (S,R) -> %                   monomial? : % -> Boolean
--R monomials : % -> List(%)             reductum : % -> %
--R retract : % -> S                     sample : () -> %
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R leadingTerm : % -> Record(k: S,c: R)
--R listOfTerms : % -> List(Record(k: S,c: R))
--R numberOfMonomials : % -> NonNegativeInteger
--R retractIfCan : % -> Union(S,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— FreeModule1.help —

```
=====================================================================
FreeModule1 examples
=====================================================================

See Also:
o )show FreeModule1
```

———-

7.31.1 FreeModule1 (FM1)



Exports:

0	coefficient	coefficients	coerce	hash
latex	leadingCoefficient	leadingMonomial	leadingTerm	listOfTerms
map	monom	monomial?	monomials	numberOfMonomials
reductum	retract	retractIfCan	sample	subtractIfCan
zero?	?~=?	?*?	?+?	?-?
-?	?=?			

— **domain FM1 FreeModule1** —

```
)abbrev domain FM1 FreeModule1
++ Author: Michel Petitot petitot@lifl.fr
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain implements linear combinations
++ of elements from the domain \spad{S} with coefficients
++ in the domain \spad{R} where \spad{S} is an ordered set
++ and \spad{R} is a ring (which may be non-commutative).
++ This domain is used by domains of non-commutative algebra such as:
++ XDistributedPolynomial, XRecursivePolynomial.

FreeModule1(R:Ring,S:OrderedSet): FMcat == FMdef where
  EX ==> OutputForm
  TERM ==> Record(k:S,c:R)

  FMcat == FreeModuleCat(R,S) with
    "*":(S,R) -> %
```

```
    ++ \spad{s*r} returns the product \spad{r*s}
    ++ used by \spadtype{XRecursivePolynomial}
FMdef == FreeModule(R,S) add
  -- representation
    Rep := List TERM

  -- declarations
    lt: List TERM
    x : %
    r : R
    s : S

  -- define
    numberOfMonomials p ==
       # (p::Rep)

    listOfTerms(x) == x:List TERM

    leadingTerm x == x.first
    leadingMonomial x == x.first.k
    coefficients x == [t.c for t in x]
    monomials x == [ monom (t.k, t.c) for t in x]

    retractIfCan x ==
       numberOfMonomials(x) ^= 1 => "failed"
       x.first.c = 1 => x.first.k
       "failed"

    coerce(s:S):% == [[s,1$R]]
    retract x ==
       (rr := retractIfCan x) case "failed" => error "FM1.retract impossible"
       rr :: S

    if R has noZeroDivisors then
       r * x  ==
           r = 0 => 0
           [[u.k,r * u.c]$TERM for u in x]
       x * r  ==
           r = 0 => 0
           [[u.k,u.c * r]$TERM for u in x]
     else
       r * x  ==
           r = 0 => 0
           [[u.k,a] for u in x | not (a:=r*u.c)= 0$R]
       x * r  ==
           r = 0 => 0
           [[u.k,a] for u in x | not (a:=u.c*r)= 0$R]

    r * s ==
      r = 0 => 0
```

```
        [[s,r]$TERM]

      s * r ==
        r = 0 => 0
        [[s,r]$TERM]

      monom(b,r):% == [[b,r]$TERM]

      outTerm(r:R, s:S):EX ==
            r=1  => s::EX
            r::EX * s::EX

      coerce(a:%):EX ==
            empty? a => (0$R)::EX
            reduce(_+, reverse_! [outTerm(t.c, t.k) for t in a])$List(EX)

      coefficient(x,s) ==
         null x => 0$R
         x.first.k > s => coefficient(rest x,s)
         x.first.k = s => x.first.c
         0$R
```

———-

— FM1.dotabb —

```
"FM1" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FM1"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FM1" -> "FLAGG"
```

———-

7.32 domain FMONOID FreeMonoid

— FreeMonoid.input —

```
)set break resume
)sys rm -f FreeMonoid.output
)spool FreeMonoid.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show FreeMonoid
--R
--R FreeMonoid(S: SetCategory)  is a domain constructor
--R Abbreviation for FreeMonoid is FMONOID
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FMONOID
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,S) -> %                      ?*? : (S,%) -> %
--R ?*? : (%,%) -> %                      ?**? : (%,PositiveInteger) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : S -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R hclf : (%,%) -> %                     hcrf : (%,%) -> %
--R latex : % -> String                   mapGen : ((S -> S),%) -> %
--R nthFactor : (%,Integer) -> S          one? : % -> Boolean
--R recip : % -> Union(%,"failed")        retract : % -> S
--R sample : () -> %                      size : % -> NonNegativeInteger
--R ?~=? : (%,%) -> Boolean
--R ?**? : (S,NonNegativeInteger) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
--R ?^? : (%,NonNegativeInteger) -> %
--R divide : (%,%) -> Union(Record(lm: %,rm: %),"failed")
--R factors : % -> List(Record(gen: S,exp: NonNegativeInteger))
--R lquo : (%,%) -> Union(%,"failed")
--R mapExpon : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R max : (%,%) -> % if S has ORDSET
--R min : (%,%) -> % if S has ORDSET
--R nthExpon : (%,Integer) -> NonNegativeInteger
--R overlap : (%,%) -> Record(lm: %,mm: %,rm: %)
--R retractIfCan : % -> Union(S,"failed")
--R rquo : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— FreeMonoid.help —

```
=====================================================================
FreeMonoid examples
=====================================================================
```

```
See Also:
o )show FreeMonoid
```

———-

7.32.1 FreeMonoid (FMONOID)



See

⇒ “ListMonoidOps” (LMOPS) 13.10.1 on page 1477
⇒ “FreeGroup” (FGROUP) 7.29.1 on page 980
⇒ “InnerFreeAbelianMonoid” (IFAMON) 10.22.1 on page 1254
⇒ “FreeAbelianMonoid” (FAMONOID) 7.28.1 on page 977
⇒ “FreeAbelianGroup” (FAGROUP) 7.27.1 on page 974

Exports:

1	coerce	divide	factors	hash
hclf	hcrf	latex	lquo	mapExpon
mapGen	max	min	nthExpon	nthFactor
one?	overlap	recip	rquo	retract
retractIfCan	sample	size	?~=?	?**?
?<?	?<=?	?>?	?>=?	?^?
?*?	?=?			

— domain FMONOID FreeMonoid —

```
)abbrev domain FMONOID FreeMonoid
++ Free monoid on any set of generators
++ Author: Stephen M. Watt
++ Date Created: ???
++ Date Last Updated: 6 June 1991
++ Description:
++ The free monoid on a set S is the monoid of finite products of
++ the form \spad{reduce(*,[si ** ni])} where the si's are in S, and the ni's
++ are nonnegative integers. The multiplication is not commutative.
```

```
FreeMonoid(S: SetCategory): FMcategory == FMdefinition where
    NNI ==> NonNegativeInteger
    REC ==> Record(gen: S, exp: NonNegativeInteger)
    Ex  ==> OutputForm

    FMcategory ==> Join(Monoid, RetractableTo S) with
        "*":    (S, $) -> $
          ++ s * x returns the product of x by s on the left.
        "*":    ($, S) -> $
          ++ x * s returns the product of x by s on the right.
        "**":   (S, NonNegativeInteger) -> $
          ++ s ** n returns the product of s by itself n times.
        hclf:   ($, $) -> $
          ++ hclf(x, y) returns the highest common left factor of x and y,
          ++ i.e. the largest d such that \spad{x = d a} and \spad{y = d b}.
        hcrf:   ($, $) -> $
          ++ hcrf(x, y) returns the highest common right factor of x and y,
          ++ i.e. the largest d such that \spad{x = a d} and \spad{y = b d}.
        lquo:   ($, $) -> Union($, "failed")
          ++ lquo(x, y) returns the exact left quotient of x by y i.e.
          ++ q such that \spad{x = y * q},
          ++ "failed" if x is not of the form \spad{y * q}.
        rquo:   ($, $) -> Union($, "failed")
          ++ rquo(x, y) returns the exact right quotient of x by y i.e.
          ++ q such that \spad{x = q * y},
          ++ "failed" if x is not of the form \spad{q * y}.
        divide:   ($, $) -> Union(Record(lm: $, rm: $), "failed")
          ++ divide(x, y) returns the left and right exact quotients of
          ++ x by y, i.e. \spad{[l, r]} such that \spad{x = l * y * r},
          ++ "failed" if x is not of the form \spad{l * y * r}.
        overlap: ($, $) -> Record(lm: $, mm: $, rm: $)
          ++ overlap(x, y) returns \spad{[l, m, r]} such that
          ++ \spad{x = l * m}, \spad{y = m * r} and l and r have no overlap,
          ++ i.e. \spad{overlap(l, r) = [l, 1, r]}.
        size         :   $ -> NNI
          ++ size(x) returns the number of monomials in x.
        factors      : $ -> List Record(gen: S, exp: NonNegativeInteger)
          ++ factors(a1\^e1,...,an\^en) returns \spad{[[a1, e1],...,[an, en]]}.
        nthExpon     : ($, Integer) -> NonNegativeInteger
          ++ nthExpon(x, n) returns the exponent of the n^th monomial of x.
        nthFactor    : ($, Integer) -> S
          ++ nthFactor(x, n) returns the factor of the n^th monomial of x.
        mapExpon     : (NNI -> NNI, $) -> $
          ++ mapExpon(f, a1\^e1 ... an\^en) returns \spad{a1\^f(e1) ... an\^f(en)}.
        mapGen       : (S -> S, $) -> $
          ++ mapGen(f, a1\^e1 ... an\^en) returns \spad{f(a1)\^e1 ... f(an)\^en}.
        if S has OrderedSet then OrderedSet

    FMdefinition ==> ListMonoidOps(S, NonNegativeInteger, 1) add
```

```
        Rep := ListMonoidOps(S, NonNegativeInteger, 1)

        1               == makeUnit()
        one? f          == empty? listOfMonoms f
        coerce(f:$): Ex == outputForm(f, "*", "**", 1)
        hcrf(f, g)      == reverse_! hclf(reverse f, reverse g)
        f:$ * s:S       == rightMult(f, s)
        s:S * f:$       == leftMult(s, f)
        factors f       == copy listOfMonoms f
        mapExpon(f, x)  == mapExpon(f, x)$Rep
        mapGen(f, x)    == mapGen(f, x)$Rep
        s:S ** n:NonNegativeInteger == makeTerm(s, n)

        f:$ * g:$ ==
--            one? f => g
            (f = 1) => g
--            one? g => f
            (g = 1) => f
            lg := listOfMonoms g
            ls := last(lf := listOfMonoms f)
            ls.gen = lg.first.gen =>
                setlast_!(h := copy lf,[lg.first.gen,lg.first.exp+ls.exp])
                makeMulti concat(h, rest lg)
            makeMulti concat(lf, lg)

        overlap(la, ar) ==
--            one? la or one? ar => [la, 1, ar]
            (la = 1) or (ar = 1) => [la, 1, ar]
            lla := la0 := listOfMonoms la
            lar := listOfMonoms ar
            l:List(REC) := empty()
            while not empty? lla repeat
              if lla.first.gen = lar.first.gen then
                if lla.first.exp < lar.first.exp and empty? rest lla then
                      return [makeMulti l,
                                makeTerm(lla.first.gen, lla.first.exp),
                                  makeMulti concat([lar.first.gen,
                                    (lar.first.exp - lla.first.exp)::NNI],
                                                                rest lar)]
                if lla.first.exp >= lar.first.exp then
                  if (ru:= lquo(makeMulti rest lar,
                     makeMulti rest lla)) case $ then
                      if lla.first.exp > lar.first.exp then
                        l := concat_!(l, [lla.first.gen,
                                  (lla.first.exp - lar.first.exp)::NNI])
                        m := concat([lla.first.gen, lar.first.exp],
                                                          rest lla)
                      else m := lla
                      return [makeMulti l, makeMulti m, ru::$]
              l  := concat_!(l, lla.first)
```

```
            lla := rest lla
          [makeMulti la0, 1, makeMulti lar]

        divide(lar, a) ==
--            one? a => [lar, 1]
          (a = 1) => [lar, 1]
          Na   : Integer := #(la := listOfMonoms a)
          Nlar : Integer := #(llar := listOfMonoms lar)
          l:List(REC) := empty()
          while Na <= Nlar repeat
            if llar.first.gen = la.first.gen and
               llar.first.exp >= la.first.exp then
              -- Can match a portion of this lar factor.
              -- Now match tail.
              (q:=lquo(makeMulti rest llar,makeMulti rest la))case $ =>
                 if llar.first.exp > la.first.exp then
                     l := concat_!(l, [la.first.gen,
                                 (llar.first.exp - la.first.exp)::NNI])
                 return [makeMulti l, q::$]
            l    := concat_!(l, first llar)
            llar  := rest llar
            Nlar := Nlar - 1
          "failed"

        hclf(f, g) ==
          h:List(REC) := empty()
          for f0 in listOfMonoms f for g0 in listOfMonoms g repeat
              f0.gen ^= g0.gen => return makeMulti h
              h := concat_!(h, [f0.gen, min(f0.exp, g0.exp)])
              f0.exp ^= g0.exp => return makeMulti h
          makeMulti h

        lquo(aq, a) ==
          size a > #(laq := copy listOfMonoms aq) => "failed"
          for a0 in listOfMonoms a repeat
              a0.gen ^= laq.first.gen or a0.exp > laq.first.exp =>
                                                    return "failed"
              if a0.exp = laq.first.exp then laq := rest laq
              else setfirst_!(laq, [laq.first.gen,
                                    (laq.first.exp - a0.exp)::NNI])
          makeMulti laq

        rquo(qa, a) ==
          (u := lquo(reverse qa, reverse a)) case "failed" => "failed"
          reverse_!(u::$)

        if S has OrderedSet then
          a < b ==
            la := listOfMonoms a
            lb := listOfMonoms b
```

```
            na: Integer := #la
            nb: Integer := #lb
            while na > 0 and nb > 0 repeat
                la.first.gen > lb.first.gen => return false
                la.first.gen < lb.first.gen => return true
                if la.first.exp = lb.first.exp then
                    la:=rest la
                    lb:=rest lb
                    na:=na - 1
                    nb:=nb - 1
                else if la.first.exp > lb.first.exp then
                    la:=concat([la.first.gen,
                           (la.first.exp - lb.first.exp)::NNI], rest lb)
                    lb:=rest lb
                    nb:=nb - 1
                else
                    lb:=concat([lb.first.gen,
                             (lb.first.exp-la.first.exp)::NNI], rest la)
                    la:=rest la
                    na:=na-1
            empty? la and not empty? lb
```

———-

— FMONOID.dotabb —

```
"FMONOID" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FMONOID"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"FMONOID" -> "FLAGG-"
"FMONOID" -> "FLAGG"
```

———-

7.33 domain FNLA FreeNilpotentLie

— FreeNilpotentLie.input —

```
)set break resume
)sys rm -f FreeNilpotentLie.output
)spool FreeNilpotentLie.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show FreeNilpotentLie
--R FreeNilpotentLie(n: NonNegativeInteger,class: NonNegativeInteger,R: CommutativeRing)  is a d
--R Abbreviation for FreeNilpotentLie is FNLA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FNLA
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           antiCommutator : (%,%) -> %
--R associator : (%,%,%) -> %             coerce : % -> OutputForm
--R commutator : (%,%) -> %               deepExpand : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R sample : () -> %                      shallowExpand : % -> OutputForm
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R dimension : () -> NonNegativeInteger
--R generator : NonNegativeInteger -> %
--R leftPower : (%,PositiveInteger) -> %
--R plenaryPower : (%,PositiveInteger) -> %
--R rightPower : (%,PositiveInteger) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— FreeNilpotentLie.help —

```
=====================================================================
FreeNilpotentLie examples
=====================================================================

See Also:
o )show FreeNilpotentLie
```

———-

7.33.1 FreeNilpotentLie (FNLA)



See

⇒ "OrdSetInts" (OSI) 16.20.1 on page 1830
⇒ "Commutator" (COMM) 4.7.1 on page 397

Exports:

0	antiCommutator	associator	coerce	commutator
deepExpand	dimension	generator	hash	latex
leftPower	plenaryPower	rightPower	sample	shallowExpand
subtractIfCan	zero?	?~=?	?*?	?**?
?+?	?-?	-?	?=?	

— **domain FNLA FreeNilpotentLie** —

```
)abbrev domain FNLA FreeNilpotentLie
++ Author: Larry Lambe
++ Date Created: July 1988
++ Date Last Updated: March 13 1991
++ Related Constructors: OrderedSetInts, Commutator
++ AMS Classification: Primary 17B05, 17B30; Secondary 17A50
++ Keywords: free Lie algebra, Hall basis, basic commutators
++ Related Constructors:  HallBasis, FreeMod, Commutator, OrdSetInts
++ Description:
++ Generate the Free Lie Algebra over a ring R with identity;
++ A P. Hall basis is generated by a package call to HallBasis.

FreeNilpotentLie(n:NNI,class:NNI,R: CommutativeRing): Export == Implement where
   B   ==> Boolean
   Com ==> Commutator
   HB  ==> HallBasis
   I   ==> Integer
   NNI ==> NonNegativeInteger
   O   ==> OutputForm
   OSI ==> OrdSetInts
   FM  ==> FreeModule(R,OSI)
   VI  ==> Vector Integer
   VLI ==> Vector List Integer
```

```
lC  ==> leadingCoefficient
lS  ==> leadingSupport

Export ==> NonAssociativeAlgebra(R) with
  dimension : () -> NNI
    ++ dimension() is the rank of this Lie algebra
  deepExpand    : %   -> O
    ++ deepExpand(x) is not documented
  shallowExpand    : %   -> O
    ++ shallowExpand(x) is not documented
  generator : NNI -> %
    ++ generator(i) is the ith Hall Basis element

Implement ==> FM add
  Rep := FM
  f,g : %

  coms:VLI
  coms := generate(n,class)$HB

  dimension == #coms

  have : (I,I) -> %
    -- have(left,right) is a lookup function for basic commutators
    -- already generated; if the nth basic commutator is
    -- [left,wt,right], then have(left,right) = n
  have(i,j) ==
     wt:I := coms(i).2 + coms(j).2
     wt > class => 0
     lo:I := 1
     hi:I := dimension
     while hi-lo > 1 repeat
       mid:I := (hi+lo) quo 2
       if coms(mid).2 < wt then lo := mid else hi := mid
     while coms(hi).1 < i repeat hi := hi + 1
     while coms(hi).3 < j repeat hi := hi + 1
     monomial(1,hi::OSI)$FM

  generator(i) ==
    i > dimension => 0$Rep
    monomial(1,i::OSI)$FM

  putIn : I -> %
  putIn(i) ==
    monomial(1$R,i::OSI)$FM

  brkt : (I,%) -> %
  brkt(k,f) ==
    f = 0 => 0
    dg:I := value lS f
```

```
      reductum(f) = 0 =>
        k = dg  => 0
        k > dg  => -lC(f)*brkt(dg, putIn(k))
        inHallBasis?(n,k,dg,coms(dg).1) => lC(f)*have(k, dg)
        lC(f)*( brkt(coms(dg).1, _
         brkt(k,putIn coms(dg).3)) - brkt(coms(dg).3, _
          brkt(k,putIn coms(dg).1) ))
      brkt(k,monomial(lC f,lS f)$FM)+brkt(k,reductum f)

    f*g ==
      reductum(f) = 0 =>
        lC(f)*brkt(value(lS f),g)
      monomial(lC f,lS f)$FM*g + reductum(f)*g

    Fac : I -> Com
      -- an auxilliary function used for output of Free Lie algebra
      -- elements (see expand)
    Fac(m) ==
      coms(m).1 = 0 => mkcomm(m)$Com
      mkcomm(Fac coms(m).1, Fac coms(m).3)

    shallowE : (R,OSI) -> 0
    shallowE(r,s) ==
      k := value s
      r = 1 =>
        k <= n => s::0
        mkcomm(mkcomm(coms(k).1)$Com,mkcomm(coms(k).3)$Com)$Com::0
      k <= n => r::0 * s::0
      r::0 * mkcomm(mkcomm(coms(k).1)$Com,mkcomm(coms(k).3)$Com)$Com::0

    shallowExpand(f) ==
      f = 0           => 0::0
      reductum(f) = 0 => shallowE(lC f,lS f)
      shallowE(lC f,lS f) + shallowExpand(reductum f)

    deepExpand(f) ==
      f = 0          => 0::0
      reductum(f) = 0 =>
        lC(f)=1 => Fac(value(lS f))::0
        lC(f)::0 * Fac(value(lS f))::0
      lC(f)=1 => Fac(value(lS f))::0 + deepExpand(reductum f)
      lC(f)::0 * Fac(value(lS f))::0 + deepExpand(reductum f)
```

———-

— FNLA.dotabb —

```
"FNLA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FNLA"]
```

```
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"FNLA" -> "IVECTOR"
```

———-

7.34 domain FPARFRAC FullPartialFractionExpansion

— **FullPartialFractionExpansion.input** —

```
)set break resume
)sys rm -f FullPartialFractionExpansion.output
)spool FullPartialFractionExpansion.output
)set message test on
)set message auto off
)clear all
--S 1 of 16
Fx := FRAC UP(x, FRAC INT)
--R
--R
--R   (1)  Fraction(UnivariatePolynomial(x,Fraction Integer))
--R                                                              Type: Domain
--E 1

--S 2 of 16
f : Fx := 36 / (x**5-2*x**4-2*x**3+4*x**2+x-2)
--R
--R
--R                     36
--R   (2)  ----------------------------
--R         5     4     3     2
--R        x  - 2x  - 2x  + 4x  + x - 2
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 2

--S 3 of 16
g := fullPartialFraction f
--R
--R
--R          4       4        --+      - 3%A - 6
--R   (3)  ----- - ----- +    >        ---------
--R        x - 2   x + 1      --+              2
--R                          2         (x - %A)
--R                        %A  - 1= 0
--RType: FullPartialFractionExpansion(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 3
```

```
--S 4 of 16
g :: Fx
--R
--R
--R                     36
--R   (4)  ----------------------------
--R         5     4     3     2
--R        x  - 2x  - 2x  + 4x  + x - 2
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 4

--S 5 of 16
g5 := D(g, 5)
--R
--R
--R              480         480         --+      2160%A + 4320
--R   (5)  - -------- + -------- +    >         -------------
--R                 6           6      --+                 7
--R          (x - 2)     (x + 1)      2            (x - %A)
--R                                 %A  - 1= 0
--RType: FullPartialFractionExpansion(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 5

--S 6 of 16
f5 := D(f, 5)
--R
--R
--R   (6)
--R                10           9            8            7            6
--R       - 544320x   + 4354560x  - 14696640x  + 28615680x  - 40085280x
--R     +
--R                5            4            3           2
--R       46656000x  - 39411360x  + 18247680x  - 5870880x  + 3317760x + 246240
--R  /
--R        20      19      18      17       16       15       14        13
--R       x   - 12x   + 53x   - 76x   - 159x   + 676x   - 391x   - 1596x
--R     +
--R             12        11        10        9        8        7        6        5
--R       2527x   + 1148x   - 4977x   + 1372x  + 4907x  - 3444x  - 2381x  + 2924x
--R     +
--R           4        3       2
--R       276x  - 1184x  + 208x  + 192x - 64
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 6

--S 7 of 16
g5::Fx - f5
--R
--R
--R   (7)  0
```

```
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 7

--S 8 of 16
f : Fx := (x**5 * (x-1)) / ((x**2 + x + 1)**2 * (x-2)**3)
--R
--R
--R                       6    5
--R                      x  - x
--R   (8)  ----------------------------------
--R         7     6     5     3     2
--R        x  - 4x  + 3x  + 9x  - 6x  - 4x - 8
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 8

--S 9 of 16
g := fullPartialFraction f
--R
--R
--R   (9)
--R      1952       464        32                          179       135
--R      ----       ---        --                        - ---- %A + ----
--R      2401       343        49            --+           2401      2401
--R     ------ + -------- + -------- +       >           ----------------
--R      x - 2          2          3         --+              x - %A
--R              (x - 2)    (x - 2)      2
--R                                    %A  + %A + 1= 0
--R   +
--R                       37        20
--R                      ---- %A + ----
--R           --+        1029      1029
--R           >          --------------
--R           --+                   2
--R       2                 (x - %A)
--R     %A  + %A + 1= 0
--RType: FullPartialFractionExpansion(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)
--E 9

--S 10 of 16
g :: Fx - f
--R
--R
--R   (10)  0
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 10

--S 11 of 16
f : Fx := (2*x**7-7*x**5+26*x**3+8*x) / (x**8-5*x**6+6*x**4+4*x**2-8)
--R
--R
```

```
--R             7     5      3
--R           2x  - 7x  + 26x  + 8x
--R   (11)  ------------------------
--R          8     6     4     2
--R         x  - 5x  + 6x  + 4x  - 8
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 11

--S 12 of 16
g := fullPartialFraction f
--R
--R
--R                         1                                          1
--R                         -                                          -
--R            --+          2         --+           1          --+     2
--R   (12)     >        ------ +     >        --------- +     >     ------
--R            --+      x - %A       --+              3       --+   x - %A
--R           2                     2          (x - %A)       2
--R         %A  - 2= 0            %A  - 2= 0               %A  + 1= 0
--RType: FullPartialFractionExpansion(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 12

--S 13 of 16
g :: Fx - f
--R
--R
--R   (13)  0
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 13

--S 14 of 16
f:Fx := x**3 / (x**21 + 2*x**20 + 4*x**19 + 7*x**18 + 10*x**17 + 17*x**16 + 22*x**15 + 30*x**14 + 36*x**13 +
--R
--R
--R   (14)
--R      3
--R     x
--R  /
--R        21     20     19     18      17      16      15      14      13      12
--R       x   + 2x   + 4x   + 7x   + 10x   + 17x   + 22x   + 30x   + 36x   + 40x
--R     +
--R          11      10      9      8      7      6      5      4      3     2
--R       47x   + 46x   + 49x  + 43x  + 38x  + 32x  + 23x  + 19x  + 10x  + 7x  + 2x
--R     +
--R       1
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 14

--S 15 of 16
g := fullPartialFraction f
```

```
--R
--R
--R   (15)
--R                  1                          1      19
--R                  - %A                       - %A - --
--R        --+       2              --+         9      27
--R        >         ------ +       >           ---------
--R        --+      x - %A          --+           x - %A
--R       2                     2
--R     %A  + 1= 0            %A  + %A + 1= 0
--R   +
--R                       1       1
--R                      -- %A - --
--R           --+        27      27
--R           >          ----------
--R           --+                2
--R       2               (x - %A)
--R     %A  + %A + 1= 0
--R   +
--R     SIGMA
--R          5     2
--R        %A  + %A  + 1= 0
--R    ,
--R               96556567040   4   420961732891   3    59101056149   2
--R            - ------------ %A  + ------------ %A  - ------------ %A
--R              912390759099       912390759099       912390759099
--R          +
--R              373545875923      529673492498
--R            - ------------ %A + ------------
--R              912390759099      912390759099
--R       /
--R          x - %A
--R   +
--R     SIGMA
--R          5     2
--R        %A  + %A  + 1= 0
--R    ,
--R           5580868   4    2024443   3    4321919   2    84614        5070620
--R        - -------- %A  - -------- %A  + -------- %A  - ------- %A - --------
--R          94070601       94070601       94070601       1542141      94070601
--R        ------------------------------------------------------------------------
--R                                              2
--R                                     (x - %A)
--R   +
--R     SIGMA
--R          5     2
--R        %A  + %A  + 1= 0
--R    ,
--R         1610957   4    2763014   3    2016775   2    266953        4529359
--R        -------- %A  + -------- %A  - -------- %A  + -------- %A + --------
```

```
--R        94070601       94070601       94070601       94070601      94070601
--R        ------------------------------------------------------------------
--R                                          3
--R                                       (x - %A)
--RType: FullPartialFractionExpansion(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 15

--S 16 of 16
g :: Fx - f
--R
--R
--R   (16)  0
--R                    Type: Fraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 16
)spool
)lisp (bye)
```

———-

— FullPartialFractionExpansion.help —

```
=====================================================================
FullPartialFractionExpansion expansion
=====================================================================

The domain FullPartialFractionExpansion implements factor-free
conversion of quotients to full partial fractions.

Our examples will all involve quotients of univariate polynomials
with rational number coefficients.

  Fx := FRAC UP(x, FRAC INT)
    Fraction UnivariatePolynomial(x,Fraction Integer)
                    Type: Domain

Here is a simple-looking rational function.

  f : Fx := 36 / (x**5-2*x**4-2*x**3+4*x**2+x-2)
                36
    ----------------------------
     5     4     3     2
    x  - 2x  - 2x  + 4x  + x - 2
                    Type: Fraction UnivariatePolynomial(x,Fraction Integer)

We use fullPartialFraction to convert it to an object of type
FullPartialFractionExpansion.

  g := fullPartialFraction f
      4       4        --+      - 3%A - 6
```

```
    ----- - ----- +    >        ---------
    x - 2   x + 1      --+              2
                      2         (x - %A)
                    %A  - 1= 0
Type: FullPartialFractionExpansion(Fraction Integer,
                                   UnivariatePolynomial(x,Fraction Integer))
```

Use a coercion to change it back into a quotient.

```
  g :: Fx
                36
    ----------------------------
     5     4     3     2
    x  - 2x  - 2x  + 4x  + x - 2
                 Type: Fraction UnivariatePolynomial(x,Fraction Integer)
```

Full partial fractions differentiate faster than rational functions.

```
  g5 := D(g, 5)
         480         480         --+      2160%A + 4320
    - -------- + -------- +    >        -------------
              6           6      --+                7
       (x - 2)     (x + 1)      2           (x - %A)
                              %A  - 1= 0
Type: FullPartialFractionExpansion(Fraction Integer,
                                   UnivariatePolynomial(x,Fraction Integer))
```

```
  f5 := D(f, 5)
                 10           9            8            7            6
       - 544320x   + 4354560x  - 14696640x  + 28615680x  - 40085280x
     +
                 5            4            3           2
       46656000x  - 39411360x  + 18247680x  - 5870880x  + 3317760x + 246240
  /
        20      19      18      17       16       15       14        13
       x   - 12x   + 53x   - 76x   - 159x   + 676x   - 391x   - 1596x
     +
            12        11        10        9        8        7        6        5
       2527x   + 1148x   - 4977x   + 1372x  + 4907x  - 3444x  - 2381x  + 2924x
     +
           4        3       2
       276x  - 1184x  + 208x  + 192x - 64
                      Type: Fraction UnivariatePolynomial(x,Fraction Integer)
```

We can check that the two forms represent the same function.

```
  g5::Fx - f5
    0
                      Type: Fraction UnivariatePolynomial(x,Fraction Integer)
```

Here are some examples that are more complicated.

```
  f : Fx := (x**5 * (x-1)) / ((x**2 + x + 1)**2 * (x-2)**3)
                  6    5
                 x  - x
    ----------------------------------
     7     6     5     3     2
    x  - 4x  + 3x  + 9x  - 6x  - 4x - 8
                     Type: Fraction UnivariatePolynomial(x,Fraction Integer)

  g := fullPartialFraction f
      1952       464        32                          179       135
      ----       ---        --                        - ---- %A + ----
      2401       343        49            --+           2401      2401
     ------ + -------- + -------- +       >           ----------------
      x - 2          2          3         --+              x - %A
               (x - 2)    (x - 2)      2
                                     %A  + %A + 1= 0
   +
                       37        20
                      ---- %A + ----
            --+       1029      1029
            >         --------------
            --+                 2
       2                 (x - %A)
     %A  + %A + 1= 0
Type: FullPartialFractionExpansion(Fraction Integer,
                                   UnivariatePolynomial(x,Fraction Integer))

  g :: Fx - f
    0
                     Type: Fraction UnivariatePolynomial(x,Fraction Integer)

  f : Fx := (2*x**7-7*x**5+26*x**3+8*x) / (x**8-5*x**6+6*x**4+4*x**2-8)
        7     5      3
      2x  - 7x  + 26x  + 8x
    ------------------------
     8     6     4     2
    x  - 5x  + 6x  + 4x  - 8
                     Type: Fraction UnivariatePolynomial(x,Fraction Integer)

  g := fullPartialFraction f
                  1                                            1
                  -                                            -
       --+        2        --+          1          --+        2
       >       ------ +    >        --------- +    >       ------
       --+     x - %A      --+              3      --+     x - %A
      2                   2          (x - %A)      2
    %A  - 2= 0          %A  - 2= 0               %A  + 1= 0
Type: FullPartialFractionExpansion(Fraction Integer,
```

```
                                UnivariatePolynomial(x,Fraction Integer))

g :: Fx - f
  0
                    Type: Fraction UnivariatePolynomial(x,Fraction Integer)

f:Fx := x**3 / (x**21 + 2*x**20 + 4*x**19 + 7*x**18 + 10*x**17 + 17*x**16 + 22*x**15 + 30*x**1
    3
   x
/
      21     20     19     18      17      16      15      14      13      12
     x   + 2x   + 4x   + 7x   + 10x   + 17x   + 22x   + 30x   + 36x   + 40x
   +
        11      10      9      8      7      6      5      4      3     2
    47x   + 46x   + 49x  + 43x  + 38x  + 32x  + 23x  + 19x  + 10x  + 7x  + 2x
   +
     1
                     Type: Fraction UnivariatePolynomial(x,Fraction Integer)

g := fullPartialFraction f
                 1                          1      19
                 - %A                       - %A - --
      --+        2              --+         9      27
      >         ------ +        >           ---------
      --+       x - %A          --+           x - %A
     2                     2
   %A  + 1= 0            %A  + %A + 1= 0
 +
                      1       1
                     -- %A - --
         --+         27      27
         >           ----------
         --+                  2
    2                (x - %A)
   %A  + %A + 1= 0
 +
   SIGMA
        5     2
      %A  + %A  + 1= 0
  ,
             96556567040   4   420961732891   3    59101056149   2
          - ------------ %A  + ------------ %A  - ------------ %A
            912390759099       912390759099       912390759099
        +
            373545875923      529673492498
          - ------------ %A + ------------
            912390759099      912390759099
     /
        x - %A
 +
```

```
     SIGMA
          5     2
         %A  + %A  + 1= 0
    ,
           5580868   4    2024443   3    4321919   2    84614         5070620
         - -------- %A  - -------- %A  + -------- %A  - ------- %A - --------
           94070601        94070601        94070601       1542141      94070601
         ------------------------------------------------------------------------
                                                2
                                          (x - %A)
   +
     SIGMA
          5     2
         %A  + %A  + 1= 0
    ,
          1610957   4    2763014   3    2016775   2    266953         4529359
         -------- %A  + -------- %A  - -------- %A  + -------- %A + --------
         94070601        94070601        94070601       94070601      94070601
         ------------------------------------------------------------------------
                                                3
                                          (x - %A)
Type: FullPartialFractionExpansion(Fraction Integer,UnivariatePolynomial(x,Fraction Integer))

This verification takes much longer than the conversion to partial fractions.

  g :: Fx - f
    0
                      Type: Fraction UnivariatePolynomial(x,Fraction Integer)


Use PartialFraction for standard partial fraction decompositions.

For more information, see the paper: Bronstein, M and Salvy, B.
"Full Partial Fraction Decomposition of Rational Functions,"
Proceedings of ISSAC'93, Kiev, ACM Press.

See Also:
o )help PartialFraction
o )show FullPartialFractionExpansion
```

———-

7.34.1 FullPartialFractionExpansion (FPARFRAC)



Exports:

coerce	construct	convert	D	differentiate
hash	latex	polyPart	fracPart	fullPartialFraction
?~=?	?+?	?=?		

— domain FPARFRAC FullPartialFractionExpansion —

```
)abbrev domain FPARFRAC FullPartialFractionExpansion
++ Author: Manuel Bronstein
++ Date Created: 9 December 1992
++ Date Last Updated: 6 October 1993
++ References: M.Bronstein & B.Salvy,
++             Full Partial Fraction Decomposition of Rational Functions,
++             in Proceedings of ISSAC'93, Kiev, ACM Press.
++ Description:
++ Full partial fraction expansion of rational functions

FullPartialFractionExpansion(F, UP): Exports == Implementation where
  F  : Join(Field, CharacteristicZero)
  UP : UnivariatePolynomialCategory F

  N   ==> NonNegativeInteger
  Q   ==> Fraction Integer
  O   ==> OutputForm
  RF  ==> Fraction UP
  SUP ==> SparseUnivariatePolynomial RF
  REC ==> Record(exponent: N, center: UP, num: UP)
  ODV ==> OrderlyDifferentialVariable Symbol
  ODP ==> OrderlyDifferentialPolynomial UP
  ODF ==> Fraction ODP
  FPF ==> Record(polyPart: UP, fracPart: List REC)

  Exports ==> Join(SetCategory, ConvertibleTo RF)  with
    "+":                 (UP, $) -> $
      ++ p + x returns the sum of p and x
```

```
    fullPartialFraction: RF -> $
      ++ fullPartialFraction(f) returns \spad{[p, [[j, Dj, Hj]...]]} such that
      ++ \spad{f = p(x) + sum_{[j,Dj,Hj] in l} sum_{Dj(a)=0} Hj(a)/(x - a)\^j}.
    polyPart:            $ -> UP
      ++ polyPart(f) returns the polynomial part of f.
    fracPart:            $  -> List REC
      ++ fracPart(f) returns the list of summands of the fractional part of f.
    construct:           List REC -> $
      ++ construct(l) is the inverse of fracPart.
    differentiate:       $ -> $
      ++ differentiate(f) returns the derivative of f.
    D:                    $ -> $
      ++ D(f) returns the derivative of f.
    differentiate:       ($, N) -> $
      ++ differentiate(f, n) returns the n-th derivative of f.
    D: ($, NonNegativeInteger) -> $
      ++ D(f, n) returns the n-th derivative of f.

  Implementation ==> add
    Rep := FPF

    fullParFrac: (UP, UP, UP, N) -> List REC
    outputexp  : (O, N) -> O
    output     : (N, UP, UP) -> O
    REC2RF     : (UP, UP, N) -> RF
    UP2SUP     : UP -> SUP
    diffrec    : REC -> REC
    FP2O       : List REC -> O

-- create a differential variable
    u  := new()$Symbol
    u0 := makeVariable(u, 0)$ODV
    alpha := u::O
    x  := monomial(1, 1)$UP
    xx := x::O
    zr := (0$N)::O

    construct l     == [0, l]
    D r             == differentiate r
    D(r, n)         == differentiate(r,n)
    polyPart f      == f.polyPart
    fracPart f      == f.fracPart
    p:UP + f:$      == [p + polyPart f, fracPart f]

    differentiate f ==
      differentiate(polyPart f) + construct [diffrec rec for rec in fracPart f]

    differentiate(r, n) ==
      for i in 1..n repeat r := differentiate r
      r
```

```
-- diffrec(sum_{rec.center(a) = 0} rec.num(a) / (x - a)^e) =
--         sum_{rec.center(a) = 0} -e rec.num(a) / (x - a)^{e+1}
--                 where e = rec.exponent
    diffrec rec ==
      e := rec.exponent
      [e + 1, rec.center, - e * rec.num]

    convert(f:$):RF ==
      ans := polyPart(f)::RF
      for rec in fracPart f repeat
        ans := ans + REC2RF(rec.center, rec.num, rec.exponent)
      ans

    UP2SUP p == map((z1:F):RF +-> z1::UP::RF, p)_
        $UnivariatePolynomialCategoryFunctions2(F, UP, RF, SUP)

    -- returns Trace_k^k(a) (h(a) / (x - a)^n)  where d(a) = 0
    REC2RF(d, h, n) ==
--      one?(m := degree d) =>
      ((m := degree d) = 1) =>
        a   := - (leadingCoefficient reductum d) / (leadingCoefficient d)
        h(a)::UP / (x - a::UP)**n
      dd  := UP2SUP d
      hh  := UP2SUP h
      aa  := monomial(1, 1)$SUP
      p   := (x::RF::SUP - aa)**n rem dd
      rec := extendedEuclidean(p, dd, hh)::Record(coef1:SUP, coef2:SUP)
      t   := rec.coef1     -- we want Trace_k^k(a)(t) now
      ans := coefficient(t, 0)
      for i in 1..degree(d)-1 repeat
        t   := (t * aa) rem dd
        ans := ans + coefficient(t, i)
      ans

    fullPartialFraction f ==
      qr := divide(numer f, d := denom f)
      qr.quotient + construct concat
                    [fullParFrac(qr.remainder, d, rec.factor, rec.exponent::N)
                                          for rec in factors squareFree denom f]

    fullParFrac(a, d, q, n) ==
      ans:List REC := empty()
      em := e := d quo (q ** n)
      rec := extendedEuclidean(e, q, 1)::Record(coef1:UP,coef2:UP)
      bm := b := rec.coef1                  -- b = inverse of e modulo q
      lvar:List(ODV) := [u0]
      um := 1::ODP
      un := (u1 := u0::ODP)**n
      lval:List(UP)  := [q1 := q := differentiate(q0 := q)]
```

```
      h:ODF := a::ODP / (e * un)
      rec := extendedEuclidean(q1, q0, 1)::Record(coef1:UP,coef2:UP)
      c := rec.coef1                        -- c = inverse of q' modulo q
      cm := 1::UP
      cn  := (c ** n) rem q0
      for m in 1..n repeat
        p    := retract(em * un * um * h)@ODP
        pp   := retract(eval(p, lvar, lval))@UP
        h    := inv(m::Q) * differentiate h
        q    := differentiate q
        lvar := concat(makeVariable(u, m), lvar)
        lval := concat(inv((m+1)::F) * q, lval)
        qq   := q0 quo gcd(pp, q0)                    -- new center
        if (degree(qq) > 0) then
          ans  := concat([(n + 1 - m)::N, qq, (pp * bm * cn * cm) rem qq], ans)
        cm   := (c * cm) rem q0     -- cm = c**m modulo q now
        um   := u1 * um             -- um = u**m now
        em   := e * em              -- em = e**{m+1} now
        bm   := (b * bm) rem q0     -- bm = b**{m+1} modulo q now
      ans

    coerce(f:$):O ==
      ans := FP2O(l := fracPart f)
      zero?(p := polyPart f) =>
        empty? l => (0$N)::O
        ans
      p::O + ans

    FP2O l ==
      empty? l => empty()
      rec := first l
      ans := output(rec.exponent, rec.center, rec.num)
      for rec in rest l repeat
        ans := ans + output(rec.exponent, rec.center, rec.num)
      ans

    output(n, d, h) ==
--      one? degree d =>
      (degree d) = 1 =>
        a := - leadingCoefficient(reductum d) / leadingCoefficient(d)
        h(a)::O / outputexp((x - a::UP)::O, n)
      sum(outputForm(makeSUP h, alpha) / outputexp(xx - alpha, n),
          outputForm(makeSUP d, alpha) = zr)

    outputexp(f, n) ==
--      one? n => f
      (n = 1) => f
      f ** (n::O)
```

———-

— **FPARFRAC.dotabb** —

```
"FPARFRAC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FPARFRAC"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FPARFRAC" -> "ALIST"
```

———-

7.35 domain FUNCTION FunctionCalled

— **FunctionCalled.input** —

```
)set break resume
)sys rm -f FunctionCalled.output
)spool FunctionCalled.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show FunctionCalled
--R
--R FunctionCalled(f: Symbol)  is a domain constructor
--R Abbreviation for FunctionCalled is FUNCTION
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FUNCTION
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R hash : % -> SingleInteger            latex : % -> String
--R name : % -> Symbol                   ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-

— **FunctionCalled.help** —


```
==========================================================================
```

```
FunctionCalled examples
=======================================================================

See Also:
o )show FunctionCalled
```

———-

7.35.1 FunctionCalled (FUNCTION)



Exports:
coerce hash latex name ?=? ?~=?

— domain FUNCTION FunctionCalled —

```
)abbrev domain FUNCTION FunctionCalled
++ Author: Mark Botch
++ Description:
++ This domain implements named functions

FunctionCalled(f:Symbol): SetCategory with
    name: % -> Symbol
      ++ name(x) returns the symbol
  == add
   name r                 == f
   coerce(r:%):OutputForm == f::OutputForm
   x = y                  == true
   latex(x:%):String      == latex f
```

———-

— FUNCTION.dotabb —

```
"FUNCTION" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FUNCTION"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"FUNCTION" -> "ALIST"
```

Chapter 8

Chapter G

8.1 domain GDMP GeneralDistributedMultivariatePolynomial

— GeneralDistributedMultivariatePolynomial.input —

```
)set break resume
)sys rm -f GeneralDistributedMultivariatePolynomial.output
)spool GeneralDistributedMultivariatePolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 10
(d1,d2,d3) : DMP([z,y,x],FRAC INT)
--R
--R                                                                    Type: Void
--E 1

--S 2 of 10
d1 := -4*z + 4*y**2*x + 16*x**2 + 1
--R
--R
--R                 2       2
--R   (2)  - 4z + 4y x + 16x  + 1
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 2

--S 3 of 10
d2 := 2*z*y**2 + 4*x + 1
--R
--R
```

```
--R            2
--R   (3)  2z y  + 4x + 1
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 3

--S 4 of 10
d3 := 2*z*x**2 - 2*y**2 - x
--R
--R
--R            2     2
--R   (4)  2z x  - 2y  - x
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 4

--S 5 of 10
groebner [d1,d2,d3]
--R
--R
--R   (5)
--R        1568  6   1264  5    6   4   182  3   2047  2    103      2857
--R   [z - ---- x  - ---- x  + --- x  + --- x  - ---- x  - ---- x - -----,
--R        2745       305      305      549       610      2745     10980
--R     2    112  6    84  5   1264  4    13  3    84  2   1772       2
--R    y  + ---- x  - --- x  - ---- x  - --- x  + --- x  + ---- x + ----,
--R         2745      305       305      549      305      2745     2745
--R     7   29  6   17  4   11  3    1  2   15     1
--R    x  + -- x  - -- x  - -- x  + -- x  + -- x + -]
--R          4      16       8      32      16     4
--R     Type: List(DistributedMultivariatePolynomial([z,y,x],Fraction(Integer)))
--E 5

--S 6 of 10
(n1,n2,n3) : HDMP([z,y,x],FRAC INT)
--R
--R                                                                    Type: Void
--E 6

--S 7 of 10
n1 := d1
--R
--R
--R          2       2
--R   (7)  4y x + 16x  - 4z + 1
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 7

--S 8 of 10
n2 := d2
--R
--R
```

```
--R            2
--R   (8)  2z y  + 4x + 1
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 8

--S 9 of 10
n3 := d3
--R
--R
--R            2     2
--R   (9)  2z x  - 2y  - x
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 9

--S 10 of 10
groebner [n1,n2,n3]
--R
--R
--R   (10)
--R     4     3   3  2   1     1   4   29  3   1  2   7        9     1
--R   [y  + 2x  - - x  + - z - -, x  + -- x  - - y  - - z x - -- x - -,
--R               2      2     8        4      8      4       16     4
--R       2        1   2      2       1     2    2   1
--R    z y  + 2x + -, y x + 4x  - z + -, z x  - y  - - x,
--R                2                  4              2
--R     2     2     2   1     3
--R    z  - 4y  + 2x  - - z - - x]
--R                     4     2
--RType: List(HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer)))
--E 10
)spool
)lisp (bye)
```

———-

— GeneralDistributedMultivariatePolynomial.help —

```
====================================================================
MultivariatePolynomial
DistributedMultivariatePolynomial
HomogeneousDistributedMultivariatePolynomial
GeneralDistributedMultivariatePolynomial
====================================================================

DistributedMultivariatePolynomial which is abbreviated as DMP and
HomogeneousDistributedMultivariatePolynomial, which is abbreviated
as HDMP, are very similar to MultivariatePolynomial except that
they are represented and displayed in a non-recursive manner.
```

```
  (d1,d2,d3) : DMP([z,y,x],FRAC INT)
                      Type: Void
```

The constructor DMP orders its monomials lexicographically while HDMP orders them by total order refined by reverse lexicographic order.

```
  d1 := -4*z + 4*y**2*x + 16*x**2 + 1
            2       2
   - 4z + 4y x + 16x  + 1
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  d2 := 2*z*y**2 + 4*x + 1
       2
   2z y  + 4x + 1
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  d3 := 2*z*x**2 - 2*y**2 - x
       2     2
   2z x  - 2y  - x
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)
```

These constructors are mostly used in Groebner basis calculations.

```
  groebner [d1,d2,d3]
        1568  6   1264  5    6   4   182  3   2047  2    103      2857
   [z - ---- x  - ---- x  + --- x  + --- x  - ---- x  - ---- x - -----,
        2745       305      305      549       610      2745     10980
     2    112  6    84  5   1264  4    13  3    84  2   1772       2
    y  + ---- x  - --- x  - ---- x  - --- x  + --- x  + ---- x + ----,
         2745      305       305      549      305      2745     2745
     7   29  6   17  4   11  3    1  2   15     1
    x  + -- x  - -- x  - -- x  + -- x  + -- x + -]
          4      16       8      32      16     4
       Type: List DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  (n1,n2,n3) : HDMP([z,y,x],FRAC INT)
                      Type: Void

  n1 := d1
     2       2
   4y x + 16x  - 4z + 1
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  n2 := d2
       2
    2z y  + 4x + 1
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  n3 := d3
```

```
      2     2
  2z x  - 2y  - x
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)
```

Note that we get a different Groebner basis when we use the HDMP polynomials, as expected.


```
  groebner [n1,n2,n3]
     4     3   3  2   1     1   4   29  3   1  2   7        9     1
   [y  + 2x  - - x  + - z - -, x  + -- x  - - y  - - z x - -- x - -,
              2      2     8        4      8      4       16     4
      2        1   2      2       1     2    2   1
    z y  + 2x + -, y x + 4x  - z + -, z x  - y  - - x,
                2                 4              2
     2     2     2   1     3
    z  - 4y  + 2x  - - z - - x]
                    4     2
      Type: List HomogeneousDistributedMultivariatePolynomial([z,y,x],
                                                          Fraction Integer)
```

GeneralDistributedMultivariatePolynomial is somewhat more flexible in the sense that as well as accepting a list of variables to specify the variable ordering, it also takes a predicate on exponent vectors to specify the term ordering. With this polynomial type the user can experiment with the effect of using completely arbitrary term orderings. This flexibility is mostly important for algorithms such as Groebner basis calculations which can be very sensitive to term ordering.

See Also:
-)help Polynomial
-)help UnivariatePolynomial
-)help MultivariatePolynomial
-)help HomogeneousDistributedMultivariatePolynomial
-)help DistributedMultivariatePolynomial
-)show GeneralDistributedMultivariatePolynomial

———-

8.1.1 GeneralDistributedMultivariatePolynomial (GDMP)



See

⇒ "DistributedMultivariatePolynomial" (DMP) 5.13.1 on page 559
⇒ "HomogeneousDistributedMultivariatePolynomial" (HDMP) 9.10.1 on page 1149

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	D
degree	differentiate	discriminant
eval	exquo	factor
factorPolynomial	factorSquareFreePolynomial	gcd
gcdPolynomial	ground	ground?
hash	isExpt	isPlus
isTimes	latex	lcm
leadingCoefficient	leadingMonomial	mainVariable
map	mapExponents	max
min	minimumDegree	monicDivide
monomial	monomial?	monomials
multivariate	numberOfMonomials	one?
patternMatch	pomopo!	prime?
primitiveMonomials	primitivePart	recip
reducedSystem	reductum	reorder
resultant	retract	retractIfCan
sample	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
totalDegree	unit?	unitCanonical
unitNormal	univariate	variables
zero?	?*?	?**?
?+?	?-?	-?
?=?	?~=?	?<?
?<=?	?>?	?>=?
?^?		

— domain GDMP GeneralDistributedMultivariatePolynomial —

```
)abbrev domain GDMP GeneralDistributedMultivariatePolynomial
++ Author: Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, degree, eval, coefficient, monomial, differentiate,
++ resultant, gcd, leadingCoefficient
++ Related Constructors: DistributedMultivariatePolynomial,
++ HomogeneousDistributedMultivariatePolynomial
++ Also See: Polynomial
++ AMS Classifications:
++ Keywords: polynomial, multivariate, distributed
++ References:
++ Description:
++ This type supports distributed multivariate polynomials
++ whose variables are from a user specified list of symbols.
++ The coefficient ring may be non commutative,
++ but the variables are assumed to commute.
++ The term ordering is specified by its third parameter.
++ Suggested types which define term orderings include:
++ \spadtype{DirectProduct}, \spadtype{HomogeneousDirectProduct},
++ \spadtype{SplitHomogeneousDirectProduct} and finally
++ \spadtype{OrderedDirectProduct} which accepts an arbitrary user
++ function to define a term ordering.

GeneralDistributedMultivariatePolynomial(vl,R,E): public == private where
  vl: List Symbol
  R: Ring
  E: DirectProductCategory(#vl,NonNegativeInteger)
  OV  ==> OrderedVariableList(vl)
  SUP ==> SparseUnivariatePolynomial
  NNI ==> NonNegativeInteger

  public == PolynomialCategory(R,E,OV) with
      reorder: (%,List Integer) -> %
        ++ reorder(p, perm) applies the permutation perm to the variables
        ++ in a polynomial and returns the new correctly ordered polynomial

  private == PolynomialRing(R,E) add
    --representations
      Term := Record(k:E,c:R)
      Rep := List Term
      n := #vl
      Vec ==> Vector(NonNegativeInteger)
      zero?(p : %): Boolean == null(p : Rep)

      totalDegree p ==
         zero? p => 0
```

```
   "max"/[reduce("+",(t.k)::(Vector NNI), 0) for t in p]

monomial(p:%, v: OV,e: NonNegativeInteger):% ==
   locv := lookup v
   p*monomial(1,
      directProduct [if z=locv then e else 0 for z in 1..n]$Vec)

coerce(v: OV):% == monomial(1,v,1)

listCoef(p : %): List R ==
  rec : Term
  [rec.c for rec in (p:Rep)]

mainVariable(p: %) ==
   zero?(p) => "failed"
   for v in vl repeat
     vv := variable(v)::OV
     if degree(p,vv)>0 then return vv
   "failed"

ground?(p) == mainVariable(p) case "failed"

retract(p : %): R ==
    not ground? p => error "not a constant"
    leadingCoefficient p

retractIfCan(p : %): Union(R,"failed") ==
  ground?(p) => leadingCoefficient p
  "failed"

degree(p: %,v: OV) == degree(univariate(p,v))
minimumDegree(p: %,v: OV) == minimumDegree(univariate(p,v))
differentiate(p: %,v: OV) ==
      multivariate(differentiate(univariate(p,v)),v)

degree(p: %,lv: List OV) == [degree(p,v) for v in lv]
minimumDegree(p: %,lv: List OV) == [minimumDegree(p,v) for v in lv]

numberOfMonomials(p:%) ==
  l : Rep := p : Rep
  null(l) => 1
  #l

monomial?(p : %): Boolean ==
  l : Rep := p : Rep
  null(l) or null rest(l)

if R has OrderedRing then
  maxNorm(p : %): R ==
    l : List R := nil
```

```
      r,m : R
      m := 0
      for r in listCoef(p) repeat
        if r > m then m := r
        else if (-r) > m then m := -r
      m

  --trailingCoef(p : %) ==
  --  l : Rep := p : Rep
  --  null l => 0
  --  r : Term := last l
  --  r.c

  --leadingPrimitiveMonomial(p : %) ==
  --  ground?(p) => 1$%
  --  r : Term := first(p:Rep)
  --  r := [r.k,1$R]$Term     -- new cell
  -- list(r)$Rep :: %

-- The following 2 defs are inherited from PolynomialRing

  --leadingMonomial(p : %) ==
  --  ground?(p) => p
  --  r : Term := first(p:Rep)
  --  r := [r.k,r.c]$Term     -- new cell
  --  list(r)$Rep :: %

  --reductum(p : %): % ==
  --  ground? p => 0$%
  --  (rest(p:Rep)):%

  if R has Field then
    (p : %) / (r : R) == inv(r) * p

  variables(p: %) ==
     maxdeg:Vector(NonNegativeInteger) := new(n,0)
     while not zero?(p) repeat
        tdeg := degree p
        p := reductum p
        for i in 1..n repeat
          maxdeg.i := max(maxdeg.i, tdeg.i)
     [index(i:PositiveInteger) for i in 1..n | maxdeg.i^=0]

  reorder(p: %,perm: List Integer):% ==
     #perm ^= n => error "must be a complete permutation of all vars"
     q := [[directProduct [term.k.j for j in perm]$Vec,term.c]$Term
                     for term in p]
     sort((z1,z2) +-> z1.k > z2.k,q)

  --coerce(dp:DistributedMultivariatePolynomial(vl,R)):% ==
```

```
--   q:=dp:List(Term)
--   sort(#1.k > #2.k,q):%

univariate(p: %,v: OV):SUP(%) ==
   zero?(p) => 0
   exp := degree p
   locv := lookup v
   deg:NonNegativeInteger := 0
   nexp := directProduct [if i=locv then (deg :=exp.i;0) else exp.i
                                  for i in 1..n]$Vec
   monomial(monomial(leadingCoefficient p,nexp),deg)+
               univariate(reductum p,v)

eval(p: %,v: OV,val:%):% == univariate(p,v)(val)

eval(p: %,v: OV,val:R):% == eval(p,v,val::%)$%

eval(p: %,lv: List OV,lval: List R):% ==
   lv = [] => p
   eval(eval(p,first lv,(first lval)::%)$%, rest lv, rest lval)$%

-- assume Lvar are sorted correctly
evalSortedVarlist(p: %,Lvar: List OV,Lpval: List %):% ==
  v := mainVariable p
  v case "failed" => p
  pv := v:: OV
  Lvar=[] or Lpval=[] => p
  mvar := Lvar.first
  mvar > pv => evalSortedVarlist(p,Lvar.rest,Lpval.rest)
  pval := Lpval.first
  pts:SUP(%):= map(x+->evalSortedVarlist(x,Lvar,Lpval),univariate(p,pv))
  mvar=pv => pts(pval)
  multivariate(pts,pv)

eval(p:%,Lvar:List OV,Lpval:List %) ==
  nlvar:List OV := sort((x,y) +-> x > y,Lvar)
  nlpval :=
     Lvar = nlvar => Lpval
     nlpval := [Lpval.position(mvar,Lvar) for mvar in nlvar]
  evalSortedVarlist(p,nlvar,nlpval)

multivariate(p1:SUP(%),v: OV):% ==
  0=p1 => 0
  degree p1 = 0 => leadingCoefficient p1
  leadingCoefficient(p1)*(v::%)**degree(p1) +
            multivariate(reductum p1,v)

univariate(p: %):SUP(R) ==
  (v := mainVariable p) case "failed" =>
               monomial(leadingCoefficient p,0)
```

```
    q := univariate(p,v:: OV)
    ans:SUP(R) := 0
    while q ^= 0 repeat
      ans := ans + monomial(ground leadingCoefficient q,degree q)
      q := reductum q
    ans

  multivariate(p:SUP(R),v: OV):% ==
    0=p => 0
    (leadingCoefficient p)*monomial(1,v,degree p) +
                   multivariate(reductum p,v)

  if R has GcdDomain then
    content(p: %):R ==
      zero?(p) => 0
      "gcd"/[t.c for t in p]



    if R has EuclideanDomain and not(R has FloatingPointSystem)  then
      gcd(p: %,q:%):% ==
        gcd(p,q)$PolynomialGcdPackage(E,OV,R,%)

    else gcd(p: %,q:%):% ==
        r : R
        (pv := mainVariable(p)) case "failed" =>
          (r := leadingCoefficient p) = 0$R => q
          gcd(r,content q)::%
        (qv := mainVariable(q)) case "failed" =>
          (r := leadingCoefficient q) = 0$R => p
          gcd(r,content p)::%
        pv<qv => gcd(p,content univariate(q,qv))
        qv<pv => gcd(q,content univariate(p,pv))
        multivariate(gcd(univariate(p,pv),univariate(q,qv)),pv)

  coerce(p: %) : OutputForm ==
    zero?(p) => (0$R) :: OutputForm
    l,lt : List OutputForm
    lt := nil
    vl1 := [v::OutputForm for v in vl]
    for t in reverse p repeat
      l := nil
      for i in 1..#vl1 repeat
        t.k.i = 0 => l
        t.k.i = 1 => l := cons(vl1.i,l)
        l := cons(vl1.i ** t.k.i ::OutputForm,l)
      l := reverse l
      if (t.c ^= 1) or (null l) then l := cons(t.c :: OutputForm,l)
      1 = #l => lt := cons(first l,lt)
      lt := cons(reduce("*",l),lt)
```

```
        1 = #lt => first lt
        reduce("+",lt)
```

———-

— GDMP.dotabb —

```
"GDMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GDMP"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"GDMP" -> "ALIST"
```

———-

8.2 domain GMODPOL GeneralModulePolynomial

— GeneralModulePolynomial.input —

```
)set break resume
)sys rm -f GeneralModulePolynomial.output
)spool GeneralModulePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GeneralModulePolynomial
--R
--R GeneralModulePolynomial(vl: List(Symbol),R: CommutativeRing,IS: OrderedSet,E: DirectProductC
--R Abbreviation for GeneralModulePolynomial is GMODPOL
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GMODPOL
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,P) -> %                      ?*? : (P,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           build : (R,IS,E) -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> R
--R leadingExponent : % -> E              leadingIndex : % -> IS
--R multMonom : (R,E,%) -> %              reductum : % -> %
--R sample : () -> %                      unitVector : IS -> %
```

```
--R zero? : % -> Boolean                    ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R leadingMonomial : % -> ModuleMonomial(IS,E,ff)
--R monomial : (R,ModuleMonomial(IS,E,ff)) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **GeneralModulePolynomial.help** —

```
=====================================================================
GeneralModulePolynomial examples
=====================================================================

See Also:
o )show GeneralModulePolynomial
```

———-

8.2.1 GeneralModulePolynomial (GMODPOL)



See

⇒ “ModuleMonomial” (MODMONOM) 14.11.1 on page 1612

Exports:

0	build	coerce	hash	latex
leadingCoefficient	leadingExponent	leadingIndex	leadingMonomial	monomial
multMonom	reductum	sample	subtractIfCan	unitVector
zero?	?~=?	?*?	?+?	?-?
-?	?=?			

— domain GMODPOL GeneralModulePolynomial —

```
)abbrev domain GMODPOL GeneralModulePolynomial
++ Author: Mark Botch
++ Description:
++ This package is undocumented

GeneralModulePolynomial(vl, R, IS, E, ff, P): public  ==  private where
  vl: List(Symbol)
  R: CommutativeRing
  IS: OrderedSet
  NNI ==> NonNegativeInteger
  E: DirectProductCategory(#vl, NNI)
  MM ==> Record(index:IS, exponent:E)
  ff: (MM, MM) -> Boolean
  OV  ==> OrderedVariableList(vl)
  P: PolynomialCategory(R, E, OV)
  ModMonom ==> ModuleMonomial(IS, E, ff)


  public  ==  Join(Module(P), Module(R))  with
    leadingCoefficient: $ -> R
      ++ leadingCoefficient(x) is not documented
    leadingMonomial: $ -> ModMonom
      ++ leadingMonomial(x) is not documented
    leadingExponent: $ -> E
      ++ leadingExponent(x) is not documented
    leadingIndex: $ -> IS
      ++ leadingIndex(x) is not documented
    reductum: $ -> $
      ++ reductum(x) is not documented
    monomial: (R, ModMonom) -> $
      ++ monomial(r,x) is not documented
    unitVector: IS -> $
      ++ unitVector(x) is not documented
    build: (R, IS, E) -> $
      ++ build(r,i,e) is not documented
    multMonom: (R, E, $) -> $
      ++ multMonom(r,e,x) is not documented
    "*": (P,$) -> $
      ++ p*x is not documented


  private  ==  FreeModule(R, ModMonom)  add
        Rep:= FreeModule(R, ModMonom)
        leadingMonomial(p:$):ModMonom == leadingSupport(p)$Rep
        leadingExponent(p:$):E == exponent(leadingMonomial p)
        leadingIndex(p:$):IS == index(leadingMonomial p)
        unitVector(i:IS):$ == monomial(1,[i, 0$E]$ModMonom)
```

```
---------------------------------------------------------------------------

       build(c:R, i:IS, e:E):$  ==  monomial(c, construct(i, e))

---------------------------------------------------------------------------

    ----   WARNING: assumes c ^= 0

       multMonom(c:R, e:E, mp:$):$  ==
           zero? mp => mp
           monomial(c * leadingCoefficient mp, [leadingIndex mp,
                    e + leadingExponent mp]) + multMonom(c, e, reductum mp)

---------------------------------------------------------------------------


       ((p:P) * (mp:$)):$  ==
           zero? p => 0
           multMonom(leadingCoefficient p, degree p, mp) +
              reductum(p) * mp


           ———————-
```

— **GMODPOL.dotabb** —

```
"GMODPOL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GMODPOL"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"GMODPOL" -> "PFECAT"
"GMODPOL" -> "DIRPCAT"
```

```
           ———————-
```

8.3 domain GCNAALG GenericNonAssociativeAlgebra

— **GenericNonAssociativeAlgebra.input** —

```
)set break resume
)sys rm -f GenericNonAssociativeAlgebra.output
)spool GenericNonAssociativeAlgebra.output
)set message test on
)set message auto off
```

```
)clear all

--S 1 of 1
)show GenericNonAssociativeAlgebra
--R
--R GenericNonAssociativeAlgebra(R: CommutativeRing,n: PositiveInteger,ls: List(Symbol),gamma: V
--R Abbreviation for GenericNonAssociativeAlgebra is GCNAALG
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GCNAALG
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           alternative? : () -> Boolean
--R antiAssociative? : () -> Boolean      antiCommutative? : () -> Boolean
--R antiCommutator : (%,%) -> %           associative? : () -> Boolean
--R associator : (%,%,%) -> %             basis : () -> Vector(%)
--R coerce : % -> OutputForm              commutative? : () -> Boolean
--R commutator : (%,%) -> %               flexible? : () -> Boolean
--R generic : Vector(%) -> %              generic : Vector(Symbol) -> %
--R generic : Symbol -> %                 generic : () -> %
--R hash : % -> SingleInteger             jacobiIdentity? : () -> Boolean
--R jordanAdmissible? : () -> Boolean     jordanAlgebra? : () -> Boolean
--R latex : % -> String                   leftAlternative? : () -> Boolean
--R lieAdmissible? : () -> Boolean        lieAlgebra? : () -> Boolean
--R powerAssociative? : () -> Boolean     rank : () -> PositiveInteger
--R rightAlternative? : () -> Boolean     sample : () -> %
--R someBasis : () -> Vector(%)           zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (SquareMatrix(n,Fraction(Polynomial(R))),%) -> %
--R ?*? : (Fraction(Polynomial(R)),%) -> %
--R ?*? : (%,Fraction(Polynomial(R))) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R apply : (Matrix(Fraction(Polynomial(R))),%) -> %
--R associatorDependence : () -> List(Vector(Fraction(Polynomial(R)))) if Fraction(Polynomial(R)
--R coerce : Vector(Fraction(Polynomial(R))) -> %
--R conditionsForIdempotents : () -> List(Polynomial(R)) if R has INTDOM
--R conditionsForIdempotents : Vector(%) -> List(Polynomial(R)) if R has INTDOM
--R conditionsForIdempotents : () -> List(Polynomial(Fraction(Polynomial(R))))
--R conditionsForIdempotents : Vector(%) -> List(Polynomial(Fraction(Polynomial(R))))
--R convert : Vector(Fraction(Polynomial(R))) -> %
--R convert : % -> Vector(Fraction(Polynomial(R)))
--R coordinates : Vector(%) -> Matrix(Fraction(Polynomial(R)))
--R coordinates : % -> Vector(Fraction(Polynomial(R)))
--R coordinates : (Vector(%),Vector(%)) -> Matrix(Fraction(Polynomial(R)))
--R coordinates : (%,Vector(%)) -> Vector(Fraction(Polynomial(R)))
--R ?.? : (%,Integer) -> Fraction(Polynomial(R))
--R generic : (Vector(Symbol),Vector(%)) -> %
```

```
--R generic : (Symbol,Vector(%)) -> %
--R genericLeftDiscriminant : () -> Fraction(Polynomial(R)) if R has INTDOM
--R genericLeftMinimalPolynomial : % -> SparseUnivariatePolynomial(Fraction(Polynomial(R))) if R has INTDOM
--R genericLeftNorm : % -> Fraction(Polynomial(R)) if R has INTDOM
--R genericLeftTrace : % -> Fraction(Polynomial(R)) if R has INTDOM
--R genericLeftTraceForm : (%,%) -> Fraction(Polynomial(R)) if R has INTDOM
--R genericRightDiscriminant : () -> Fraction(Polynomial(R)) if R has INTDOM
--R genericRightMinimalPolynomial : % -> SparseUnivariatePolynomial(Fraction(Polynomial(R))) if R has INTDOM
--R genericRightNorm : % -> Fraction(Polynomial(R)) if R has INTDOM
--R genericRightTrace : % -> Fraction(Polynomial(R)) if R has INTDOM
--R genericRightTraceForm : (%,%) -> Fraction(Polynomial(R)) if R has INTDOM
--R leftCharacteristicPolynomial : % -> SparseUnivariatePolynomial(Fraction(Polynomial(R)))
--R leftDiscriminant : () -> Fraction(Polynomial(R))
--R leftDiscriminant : Vector(%) -> Fraction(Polynomial(R))
--R leftMinimalPolynomial : % -> SparseUnivariatePolynomial(Fraction(Polynomial(R))) if Fraction(Polynomial
--R leftNorm : % -> Fraction(Polynomial(R))
--R leftPower : (%,PositiveInteger) -> %
--R leftRankPolynomial : () -> SparseUnivariatePolynomial(Fraction(Polynomial(R))) if R has INTDOM
--R leftRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(Fraction(Polynomial(R)))) if Fraction(
--R leftRecip : % -> Union(%,"failed") if Fraction(Polynomial(R)) has INTDOM
--R leftRegularRepresentation : % -> Matrix(Fraction(Polynomial(R)))
--R leftRegularRepresentation : (%,Vector(%)) -> Matrix(Fraction(Polynomial(R)))
--R leftTrace : % -> Fraction(Polynomial(R))
--R leftTraceMatrix : () -> Matrix(Fraction(Polynomial(R)))
--R leftTraceMatrix : Vector(%) -> Matrix(Fraction(Polynomial(R)))
--R leftUnit : () -> Union(%,"failed") if Fraction(Polynomial(R)) has INTDOM
--R leftUnits : () -> Union(Record(particular: %,basis: List(%)),"failed")
--R noncommutativeJordanAlgebra? : () -> Boolean
--R plenaryPower : (%,PositiveInteger) -> %
--R recip : % -> Union(%,"failed") if Fraction(Polynomial(R)) has INTDOM
--R represents : Vector(Fraction(Polynomial(R))) -> %
--R represents : (Vector(Fraction(Polynomial(R))),Vector(%)) -> %
--R rightCharacteristicPolynomial : % -> SparseUnivariatePolynomial(Fraction(Polynomial(R)))
--R rightDiscriminant : () -> Fraction(Polynomial(R))
--R rightDiscriminant : Vector(%) -> Fraction(Polynomial(R))
--R rightMinimalPolynomial : % -> SparseUnivariatePolynomial(Fraction(Polynomial(R))) if Fraction(Polynomial
--R rightNorm : % -> Fraction(Polynomial(R))
--R rightPower : (%,PositiveInteger) -> %
--R rightRankPolynomial : () -> SparseUnivariatePolynomial(Fraction(Polynomial(R))) if R has INTDOM
--R rightRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(Fraction(Polynomial(R)))) if Fraction
--R rightRecip : % -> Union(%,"failed") if Fraction(Polynomial(R)) has INTDOM
--R rightRegularRepresentation : % -> Matrix(Fraction(Polynomial(R)))
--R rightRegularRepresentation : (%,Vector(%)) -> Matrix(Fraction(Polynomial(R)))
--R rightTrace : % -> Fraction(Polynomial(R))
--R rightTraceMatrix : () -> Matrix(Fraction(Polynomial(R)))
--R rightTraceMatrix : Vector(%) -> Matrix(Fraction(Polynomial(R)))
--R rightUnit : () -> Union(%,"failed") if Fraction(Polynomial(R)) has INTDOM
--R rightUnits : () -> Union(Record(particular: %,basis: List(%)),"failed")
--R structuralConstants : () -> Vector(Matrix(Fraction(Polynomial(R))))
--R structuralConstants : Vector(%) -> Vector(Matrix(Fraction(Polynomial(R))))
```

```
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit : () -> Union(%,"failed") if Fraction(Polynomial(R)) has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— **GenericNonAssociativeAlgebra.help** —

```
=====================================================================
GenericNonAssociativeAlgebra examples
=====================================================================

See Also:
o )show GenericNonAssociativeAlgebra
```

———-

8.3.1 GenericNonAssociativeAlgebra (GCNAALG)



Exports:

0	alternative?
antiAssociative?	antiCommutative?
antiCommutator	apply
associative?	associator
associatorDependence	basis
coerce	commutative?
commutator	conditionsForIdempotents
convert	convert
coordinates	coordinates
coordinates	coordinates
flexible?	generic
genericLeftDiscriminant	genericLeftMinimalPolynomial
genericLeftNorm	genericLeftTrace
genericLeftTraceForm	genericRightDiscriminant
genericRightMinimalPolynomial	genericRightNorm
genericRightTrace	genericRightTraceForm
hash	jacobiIdentity?
jordanAdmissible?	jordanAlgebra?
latex	leftAlternative?
leftCharacteristicPolynomial	leftDiscriminant
leftDiscriminant	leftMinimalPolynomial
leftNorm	leftPower
leftRankPolynomial	leftRankPolynomial
leftRecip	leftRegularRepresentation
leftRegularRepresentation	leftTrace
leftTraceMatrix	leftTraceMatrix
leftUnit	leftUnits
lieAdmissible?	lieAlgebra?
noncommutativeJordanAlgebra?	plenaryPower
powerAssociative?	rank
recip	represents
rightAlternative?	rightCharacteristicPolynomial
rightDiscriminant	rightDiscriminant
rightMinimalPolynomial	rightNorm
rightPower	rightRankPolynomial
rightRankPolynomial	rightRecip
rightRegularRepresentation	rightRegularRepresentation
rightTrace	rightTraceMatrix
rightTraceMatrix	rightUnit
rightUnits	sample
someBasis	structuralConstants
structuralConstants	subtractIfCan
unit	zero?
?*?	?**?
?+?	?-?
-?	?=?
?.?	?~=?

— domain GCNAALG GenericNonAssociativeAlgebra —

```
)abbrev domain GCNAALG GenericNonAssociativeAlgebra
++ Authors: J. Grabmeier, R. Wisbauer
++ Date Created: 26 June 1991
++ Date Last Updated: 26 June 1991
++ Basic Operations: generic
++ Related Constructors: AlgebraPackage
++ Also See:
++ AMS Classifications:
++ Keywords: generic element. rank polynomial
++ Reference:
++  A. Woerz-Busekros: Algebra in Genetics
++  Lectures Notes in Biomathematics 36,
++  Springer-Verlag,  Heidelberg, 1980
++ Description:
++ AlgebraGenericElementPackage allows you to create generic elements
++ of an algebra, i.e. the scalars are extended to include symbolic
++ coefficients

GenericNonAssociativeAlgebra(R : CommutativeRing, n : PositiveInteger,_
  ls : List Symbol, gamma: Vector Matrix R ): public == private where

  NNI ==> NonNegativeInteger
  V   ==> Vector
  PR  ==> Polynomial R
  FPR ==> Fraction Polynomial R
  SUP ==> SparseUnivariatePolynomial
  S   ==> Symbol

  public ==> Join(FramedNonAssociativeAlgebra(FPR), _
      LeftModule(SquareMatrix(n,FPR)) ) with

    coerce : Vector FPR -> %
      ++ coerce(v) assumes that it is called with a vector
      ++ of length equal to the dimension of the algebra, then
      ++ a linear combination with the basis element is formed
    leftUnits:() -> Union(Record(particular: %, basis: List %), "failed")
      ++ leftUnits() returns the affine space of all left units of the
      ++ algebra, or \spad{"failed"} if there is none
    rightUnits:() -> Union(Record(particular: %, basis: List %), "failed")
      ++ rightUnits() returns the affine space of all right units of the
      ++ algebra, or \spad{"failed"} if there is none
    generic : () -> %
      ++ generic() returns a generic element, i.e. the linear combination
      ++ of the fixed basis with the symbolic coefficients
      ++ \spad{%x1,%x2,..}
    generic : Symbol -> %
      ++ generic(s) returns a generic element, i.e. the linear combination
```

```
    ++ of the fixed basis with the symbolic coefficients
    ++ \spad{s1,s2,..}
  generic : Vector Symbol -> %
    ++ generic(vs) returns a generic element, i.e. the linear combination
    ++ of the fixed basis with the symbolic coefficients
    ++ \spad{vs};
    ++ error, if the vector of symbols is too short
  generic : Vector % -> %
    ++ generic(ve) returns a generic element, i.e. the linear combination
    ++ of \spad{ve} basis with the symbolic coefficients
    ++ \spad{%x1,%x2,..}
  generic : (Symbol, Vector %) -> %
    ++ generic(s,v) returns a generic element, i.e. the linear combination
    ++ of v with the symbolic coefficients
    ++ \spad{s1,s2,..}
  generic : (Vector Symbol, Vector %) -> %
    ++ generic(vs,ve) returns a generic element, i.e. the linear combination
    ++ of \spad{ve} with the symbolic coefficients \spad{vs}
    ++ error, if the vector of symbols is shorter than the vector of
    ++ elements
  if R has IntegralDomain then
    leftRankPolynomial : () -> SparseUnivariatePolynomial FPR
      ++ leftRankPolynomial() returns the left minimimal polynomial
      ++ of the generic element
    genericLeftMinimalPolynomial : % -> SparseUnivariatePolynomial FPR
      ++ genericLeftMinimalPolynomial(a) substitutes the coefficients
      ++ of {em a} for the generic coefficients in
      ++ \spad{leftRankPolynomial()}
    genericLeftTrace : % -> FPR
      ++ genericLeftTrace(a) substitutes the coefficients
      ++ of \spad{a} for the generic coefficients into the
      ++ coefficient of the second highest term in
      ++ \spadfun{leftRankPolynomial} and changes the sign.
      ++  This is a linear form
    genericLeftNorm : % -> FPR
      ++ genericLeftNorm(a) substitutes the coefficients
      ++ of \spad{a} for the generic coefficients into the
      ++ coefficient of the constant term in \spadfun{leftRankPolynomial}
      ++ and changes the sign if the degree of this polynomial is odd.
      ++ This is a form of degree k
    rightRankPolynomial : () -> SparseUnivariatePolynomial FPR
      ++ rightRankPolynomial() returns the right minimimal polynomial
      ++ of the generic element
    genericRightMinimalPolynomial : % -> SparseUnivariatePolynomial FPR
      ++ genericRightMinimalPolynomial(a) substitutes the coefficients
      ++ of \spad{a} for the generic coefficients in
      ++ \spadfun{rightRankPolynomial}
    genericRightTrace : % -> FPR
      ++ genericRightTrace(a) substitutes the coefficients
      ++ of \spad{a} for the generic coefficients into the
```

```
      ++ coefficient of the second highest term in
      ++ \spadfun{rightRankPolynomial} and changes the sign
    genericRightNorm : % -> FPR
      ++ genericRightNorm(a) substitutes the coefficients
      ++ of \spad{a} for the generic coefficients into the
      ++ coefficient of the constant term in \spadfun{rightRankPolynomial}
      ++ and changes the sign if the degree of this polynomial is odd
    genericLeftTraceForm : (%,%) -> FPR
      ++ genericLeftTraceForm (a,b) is defined to be
      ++ \spad{genericLeftTrace (a*b)}, this defines
      ++ a symmetric bilinear form on the algebra
    genericLeftDiscriminant: () -> FPR
      ++ genericLeftDiscriminant() is the determinant of the
      ++ generic left trace forms of all products of basis element,
      ++ if the generic left trace form is associative, an algebra
      ++ is separable if the generic left discriminant is invertible,
      ++ if it is non-zero, there is some ring extension which
      ++ makes the algebra separable
    genericRightTraceForm : (%,%) -> FPR
      ++ genericRightTraceForm (a,b) is defined to be
      ++ \spadfun{genericRightTrace (a*b)}, this defines
      ++ a symmetric bilinear form on the algebra
    genericRightDiscriminant: () -> FPR
      ++ genericRightDiscriminant() is the determinant of the
      ++ generic left trace forms of all products of basis element,
      ++ if the generic left trace form is associative, an algebra
      ++ is separable if the generic left discriminant is invertible,
      ++ if it is non-zero, there is some ring extension which
      ++ makes the algebra separable
    conditionsForIdempotents: Vector % -> List Polynomial R
      ++ conditionsForIdempotents([v1,...,vn]) determines a complete list
      ++ of polynomial equations for the coefficients of idempotents
      ++ with respect to the \spad{R}-module basis \spad{v1},...,\spad{vn}
    conditionsForIdempotents: () -> List Polynomial R
      ++ conditionsForIdempotents() determines a complete list
      ++ of polynomial equations for the coefficients of idempotents
      ++ with respect to the fixed \spad{R}-module basis

private ==> AlgebraGivenByStructuralConstants(FPR,n,ls,_
       coerce(gamma)$CoerceVectorMatrixPackage(R) ) add

  listOfNumbers : List String :=  [STRINGIMAGE(q)$Lisp for q in 1..n]
  symbolsForCoef : V Symbol :=
      [concat("%", concat("x", i))::Symbol  for i in listOfNumbers]
  genericElement : % :=
    v : Vector PR :=
      [monomial(1$PR, [symbolsForCoef.i],[1]) for i in 1..n]
    convert map(coerce,v)$VectorFunctions2(PR,FPR)

  eval : (FPR, %) -> FPR
```

```
eval(rf,a) ==
  -- for the moment we only substitute the numerators
  -- of the coefficients
  coefOfa : List PR :=
    map(numer, entries coordinates a)$ListFunctions2(FPR,PR)
  ls : List PR :=[monomial(1$PR, [s],[1]) for s in entries symbolsForCoef]
  lEq : List Equation PR := []
  for i in 1..maxIndex ls repeat
    lEq := cons(equation(ls.i,coefOfa.i)$Equation(PR) , lEq)
  top : PR := eval(numer(rf),lEq)$PR
  bot : PR := eval(numer(rf),lEq)$PR
  top/bot


if R has IntegralDomain then

  genericLeftTraceForm(a,b) == genericLeftTrace(a*b)
  genericLeftDiscriminant() ==
    listBasis : List % := entries basis()$%
    m : Matrix FPR := matrix
      [[genericLeftTraceForm(a,b) for a in listBasis] for b in listBasis]
    determinant m

  genericRightTraceForm(a,b) == genericRightTrace(a*b)
  genericRightDiscriminant() ==
    listBasis : List % := entries basis()$%
    m : Matrix FPR := matrix
      [[genericRightTraceForm(a,b) for a in listBasis] for b in listBasis]
    determinant m



  leftRankPoly : SparseUnivariatePolynomial FPR := 0
  initLeft? : Boolean :=true

  initializeLeft: () -> Void
  initializeLeft() ==
    -- reset initialize flag
    initLeft?:=false
    leftRankPoly := leftMinimalPolynomial genericElement
    void()$Void

  rightRankPoly : SparseUnivariatePolynomial FPR := 0
  initRight? : Boolean :=true

  initializeRight: () -> Void
  initializeRight() ==
    -- reset initialize flag
    initRight?:=false
    rightRankPoly := rightMinimalPolynomial genericElement
```

```
    void()$Void

  leftRankPolynomial() ==
    if initLeft? then initializeLeft()
    leftRankPoly

  rightRankPolynomial() ==
    if initRight? then initializeRight()
    rightRankPoly

  genericLeftMinimalPolynomial a ==
    if initLeft? then initializeLeft()
    map(x+->eval(x,a),leftRankPoly)$SUP(FPR)

  genericRightMinimalPolynomial a ==
    if initRight? then initializeRight()
    map(x+->eval(x,a),rightRankPoly)$SUP(FPR)

  genericLeftTrace a ==
    if initLeft? then initializeLeft()
    d1 : NNI := (degree leftRankPoly - 1) :: NNI
    rf : FPR := coefficient(leftRankPoly, d1)
    rf := eval(rf,a)
    - rf

  genericRightTrace a ==
    if initRight? then initializeRight()
    d1 : NNI := (degree rightRankPoly - 1) :: NNI
    rf : FPR := coefficient(rightRankPoly, d1)
    rf := eval(rf,a)
    - rf

  genericLeftNorm a ==
    if initLeft? then initializeLeft()
    rf : FPR := coefficient(leftRankPoly, 1)
    if odd? degree leftRankPoly then rf := - rf
    rf

  genericRightNorm a ==
    if initRight? then initializeRight()
    rf : FPR := coefficient(rightRankPoly, 1)
    if odd? degree rightRankPoly then rf := - rf
    rf

conditionsForIdempotents(b: V %) : List Polynomial R ==
  x : % := generic(b)
  map(numer,entries coordinates(x*x-x,b))$ListFunctions2(FPR,PR)

conditionsForIdempotents(): List Polynomial R ==
  x : % := genericElement
```

```
    map(numer,entries coordinates(x*x-x))$ListFunctions2(FPR,PR)

  generic() ==  genericElement

  generic(vs:V S, ve: V %): % ==
    maxIndex v > maxIndex ve =>
      error "generic: too little symbols"
    v : Vector PR :=
      [monomial(1$PR, [vs.i],[1]) for i in 1..maxIndex ve]
    represents(map(coerce,v)$VectorFunctions2(PR,FPR),ve)

  generic(s: S, ve: V %): % ==
    lON : List String :=  [STRINGIMAGE(q)$Lisp for q in 1..maxIndex ve]
    sFC : Vector Symbol :=
      [concat(s pretend String, i)::Symbol  for i in lON]
    generic(sFC, ve)

  generic(ve : V %) ==
    lON : List String :=  [STRINGIMAGE(q)$Lisp for q in 1..maxIndex ve]
    sFC : Vector Symbol :=
      [concat("%", concat("x", i))::Symbol  for i in lON]
    v : Vector PR :=
      [monomial(1$PR, [sFC.i],[1]) for i in 1..maxIndex ve]
    represents(map(coerce,v)$VectorFunctions2(PR,FPR),ve)

  generic(vs:V S): % == generic(vs, basis()$%)

  generic(s: S): % == generic(s, basis()$%)

  -- variations on eval
  --coefOfa : List FPR := entries coordinates a
  --ls : List Symbol := entries symbolsForCoef
  -- a very dangerous sequential implementation for  the moment,
  -- because the compiler doesn't manage the parallel code
  -- also doesn't run:
  -- not known that (Fraction (Polynomial R)) has (has (Polynomial R)
  --  (Evalable (Fraction (Polynomial R))))
  --res : FPR := rf
  --for eq in lEq repeat res := eval(res,eq)$FPR
  --res
  --rf
  --eval(rf, le)$FPR
  --eval(rf, entries symbolsForCoef, coefOfa)$FPR
  --eval(rf, ls, coefOfa)$FPR
  --le : List Equation PR := [equation(lh,rh) for lh in ls for rh in coefOfa]
```

———-

— **GCNAALG.dotabb** —

```
"GCNAALG" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GCNAALG"]
"FRNAALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRNAALG"]
"GCNAALG" -> "FRNAALG"
```

———-

8.4 domain GPOLSET GeneralPolynomialSet

— **GeneralPolynomialSet.input** —

```
)set break resume
)sys rm -f GeneralPolynomialSet.output
)spool GeneralPolynomialSet.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GeneralPolynomialSet
--R
--R GeneralPolynomialSet(R: Ring,E: OrderedAbelianMonoidSup,VarSet: OrderedSet,P: RecursivePolyn
--R Abbreviation for GeneralPolynomialSet is GPOLSET
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GPOLSET
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> List(P)
--R coerce : % -> OutputForm              collect : (%,VarSet) -> %
--R collectUnder : (%,VarSet) -> %        collectUpper : (%,VarSet) -> %
--R construct : List(P) -> %              convert : List(P) -> %
--R copy : % -> %                         empty : () -> %
--R empty? : % -> Boolean                 eq? : (%,%) -> Boolean
--R hash : % -> SingleInteger             latex : % -> String
--R mainVariables : % -> List(VarSet)     map : ((P -> P),%) -> %
--R mvar : % -> VarSet                    retract : List(P) -> %
--R sample : () -> %                      trivialIdeal? : % -> Boolean
--R variables : % -> List(VarSet)         ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R any? : ((P -> Boolean),%) -> Boolean if $ has finiteAggregate
--R convert : % -> InputForm if P has KONVERT(INFORM)
--R count : ((P -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (P,%) -> NonNegativeInteger if $ has finiteAggregate and P has SETCAT
--R eval : (%,List(Equation(P))) -> % if P has EVALAB(P) and P has SETCAT
```

```
--R eval : (%,Equation(P)) -> % if P has EVALAB(P) and P has SETCAT
--R eval : (%,P,P) -> % if P has EVALAB(P) and P has SETCAT
--R eval : (%,List(P),List(P)) -> % if P has EVALAB(P) and P has SETCAT
--R every? : ((P -> Boolean),%) -> Boolean if $ has finiteAggregate
--R find : ((P -> Boolean),%) -> Union(P,"failed")
--R headRemainder : (P,%) -> Record(num: P,den: R) if R has INTDOM
--R less? : (%,NonNegativeInteger) -> Boolean
--R mainVariable? : (VarSet,%) -> Boolean
--R map! : ((P -> P),%) -> % if $ has shallowlyMutable
--R member? : (P,%) -> Boolean if $ has finiteAggregate and P has SETCAT
--R members : % -> List(P) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(P) if $ has finiteAggregate
--R reduce : (((P,P) -> P),%) -> P if $ has finiteAggregate
--R reduce : (((P,P) -> P),%,P) -> P if $ has finiteAggregate
--R reduce : (((P,P) -> P),%,P,P) -> P if $ has finiteAggregate and P has SETCAT
--R remainder : (P,%) -> Record(rnum: R,polnum: P,den: R) if R has INTDOM
--R remove : ((P -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (P,%) -> % if $ has finiteAggregate and P has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and P has SETCAT
--R retractIfCan : List(P) -> Union(%,"failed")
--R rewriteIdealWithHeadRemainder : (List(P),%) -> List(P) if R has INTDOM
--R rewriteIdealWithRemainder : (List(P),%) -> List(P) if R has INTDOM
--R roughBase? : % -> Boolean if R has INTDOM
--R roughEqualIdeals? : (%,%) -> Boolean if R has INTDOM
--R roughSubIdeal? : (%,%) -> Boolean if R has INTDOM
--R roughUnitIdeal? : % -> Boolean if R has INTDOM
--R select : ((P -> Boolean),%) -> % if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : (%,VarSet) -> Record(under: %,floor: %,upper: %)
--R triangular? : % -> Boolean if R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— GeneralPolynomialSet.help —

```
=====================================================================
GeneralPolynomialSet examples
=====================================================================

See Also:
o )show GeneralPolynomialSet
```

———-

8.4.1 GeneralPolynomialSet (GPOLSET)



Exports:

any?	coerce
collect	collectUnder
collectUpper	construct
convert	copy
count	empty
empty?	eq?
eval	every?
find	hash
headRemainder	latex
less?	mainVariables
mainVariable?	map
map!	member?
members	more?
mvar	parts
reduce	remainder
remove	removeDuplicates
retract	retractIfCan
rewriteIdealWithHeadRemainder	rewriteIdealWithRemainder
roughBase?	roughEqualIdeals?
roughSubIdeal?	roughUnitIdeal?
sample	select
size?	sort
triangular?	trivialIdeal?
variables	#?
?=?	?~=?

— domain GPOLSET GeneralPolynomialSet —

```
)abbrev domain GPOLSET GeneralPolynomialSet
++ Author: Marc Moreno Maza
++ Date Created: 04/26/1994
++ Date Last Updated: 12/15/1998
```

```
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: polynomial, multivariate, ordered variables set
++ References:
++ Description:
++ A domain for polynomial sets.

GeneralPolynomialSet(R,E,VarSet,P) : Exports == Implementation where

  R:Ring
  VarSet:OrderedSet
  E:OrderedAbelianMonoidSup
  P:RecursivePolynomialCategory(R,E,VarSet)
  LP ==> List P
  PtoP ==> P -> P

  Exports ==  PolynomialSetCategory(R,E,VarSet,P)  with

     convert : LP -> $
       ++ \axiom{convert(lp)} returns the polynomial set whose members
       ++ are the polynomials of \axiom{lp}.

     finiteAggregate
     shallowlyMutable

  Implementation == add

     Rep := List P

     construct lp ==
       (removeDuplicates(lp)$List(P))::$

     copy ps ==
       construct(copy(members(ps)$$)$LP)$$

     empty() ==
       []

     parts ps ==
       ps pretend LP

     map (f : PtoP, ps : $) : $ ==
       construct(map(f,members(ps))$LP)$$

     map! (f : PtoP, ps : $) : $  ==
       construct(map!(f,members(ps))$LP)$$

     member? (p,ps) ==
```

```
      member?(p,members(ps))$LP

    ps1 = ps2 ==
      {p for p in parts(ps1)} =$(Set P) {p for p in parts(ps2)}

    coerce(ps:$) : OutputForm ==
      lp : List(P) := sort(infRittWu?,members(ps))$(List P)
      brace([p::OutputForm for p in lp]$List(OutputForm))$OutputForm

    mvar ps ==
      empty? ps => error"Error from GPOLSET in mvar : #1 is empty"
      lv : List VarSet := variables(ps)
      empty? lv =>
       error "Error from GPOLSET in mvar : every polynomial in #1 is constant"
      reduce(max,lv)$(List VarSet)

    retractIfCan(lp) ==
      (construct(lp))::Union($,"failed")

    coerce(ps:$) : (List P) ==
      ps pretend (List P)

    convert(lp:LP) : $ ==
      construct lp
```

———-

— GPOLSET.dotabb —

```
"GPOLSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GPOLSET"]
"RPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RPOLCAT"]
"GPOLSET" -> "RPOLCAT"
```

———-

8.5 domain GSTBL GeneralSparseTable

— GeneralSparseTable.input —

```
)set break resume
)sys rm -f GeneralSparseTable.output
)spool GeneralSparseTable.output
)set message test on
)set message auto off
```

```
)set break resume
)clear all
--S 1 of 7
patrons: GeneralSparseTable(String, Integer, KeyedAccessFile(Integer), 0) := table() ;
--E 1

--S 2 of 7
patrons."Smith" := 10500
--E 2

--S 3 of 7
patrons."Jones" := 22000
--E 3

--S 4 of 7
patrons."Jones"
--E 4

--S 5 of 7
patrons."Stingy"
--E 5

--S 6 of 7
reduce(+, entries patrons)
--E 6

--S 7 of 7
)system rm -r kaf*.sdata
--E 7
)spool
)lisp (bye)
```

———-

— GeneralSparseTable.help —

```
====================================================================
GeneralSparseTable
====================================================================

Sometimes when working with tables there is a natural value to use as
the entry in all but a few cases.  The GeneralSparseTable constructor
can be used to provide any table type with a default value for
entries.

Suppose we launched a fund-raising campaign to raise fifty thousand
dollars.  To record the contributions, we want a table with strings as
keys (for the names) and integer entries (for the amount).  In a data
base of cash contributions, unless someone has been explicitly
```

```
entered, it is reasonable to assume they have made a zero dollar
contribution.

This creates a keyed access file with default entry 0.

  patrons: GeneralSparseTable(String, Integer, KeyedAccessFile(Integer), 0) := table() ;

Now patrons can be used just as any other table.  Here we record two gifts.

  patrons."Smith" := 10500

  patrons."Jones" := 22000

Now let us look up the size of the contributions from Jones and Stingy.

  patrons."Jones"

  patrons."Stingy"

Have we met our seventy thousand dollar goal?


  reduce(+, entries patrons)

So the project is cancelled and we can delete the data base:

  )system rm -r kaf*.sdata

See Also:
o )show GeneralSparseTable
```

8.5.1 GeneralSparseTable (GSTBL)



See

⇒ “HashTable” (HASHTBL) 9.1.1 on page 1089
⇒ “InnerTable” (INTABL) 10.27.1 on page 1303
⇒ “Table” (TABLE) 21.1.1 on page 2631
⇒ “EqTable” (EQTBL) 6.2.1 on page 669
⇒ “StringTable” (STRTBL) 20.32.1 on page 2578
⇒ “SparseTable” (STBL) 20.16.1 on page 2418

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	elt	empty
empty?	entries	entry?	eq?	eval
every?	extract!	fill!	find	first
hash	index?	indices	insert!	inspect
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
select	select!	setelt	size?	swap!
table	#?	?=?	?~=?	?.?

— domain GSTBL GeneralSparseTable —

```
)abbrev domain GSTBL GeneralSparseTable
++ Author: Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: June 21, 1991
++ Basic Operations:
++ Related Domains: Table
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
++ A sparse table has a default entry, which is returned if no other
++ value has been explicitly stored for a key.

GeneralSparseTable(Key, Entry, Tbl, dent): TableAggregate(Key, Entry) == Impl
  where
    Key, Entry: SetCategory
    Tbl:  TableAggregate(Key, Entry)
    dent: Entry

    Impl ==> Tbl add
        Rep := Tbl

        elt(t:%, k:Key) ==
            (u := search(k, t)$Rep) case "failed" => dent
```

```
            u::Entry

        setelt(t:%, k:Key, e:Entry) ==
            e = dent => (remove_!(k, t); e)
            setelt(t, k, e)$Rep

        search(k:Key, t:%) ==
            (u := search(k, t)$Rep) case "failed" => dent
            u
```

———-

— GSTBL.dotabb —

```
"GSTBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GSTBL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"GSTBL" -> "TBAGG"
```

———-

8.6 domain GTSET GeneralTriangularSet

— GeneralTriangularSet.input —

```
)set break resume
)sys rm -f GeneralTriangularSet.output
)spool GeneralTriangularSet.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GeneralTriangularSet
--R
--R GeneralTriangularSet(R: IntegralDomain,E: OrderedAbelianMonoidSup,V: OrderedSet,P: Recursive
--R Abbreviation for GeneralTriangularSet is GTSET
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GTSET
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               algebraic? : (V,%) -> Boolean
--R algebraicVariables : % -> List(V)    coerce : % -> List(P)
--R coerce : % -> OutputForm             collect : (%,V) -> %
--R collectQuasiMonic : % -> %           collectUnder : (%,V) -> %
```

```
--R collectUpper : (%,V) -> %            construct : List(P) -> %
--R copy : % -> %                        degree : % -> NonNegativeInteger
--R empty : () -> %                      empty? : % -> Boolean
--R eq? : (%,%) -> Boolean               extend : (%,P) -> %
--R first : % -> Union(P,"failed")       hash : % -> SingleInteger
--R headReduce : (P,%) -> P              headReduced? : % -> Boolean
--R headReduced? : (P,%) -> Boolean      infRittWu? : (%,%) -> Boolean
--R initiallyReduce : (P,%) -> P         initiallyReduced? : % -> Boolean
--R initials : % -> List(P)              last : % -> Union(P,"failed")
--R latex : % -> String                  mainVariable? : (V,%) -> Boolean
--R mainVariables : % -> List(V)         map : ((P -> P),%) -> %
--R mvar : % -> V                        normalized? : % -> Boolean
--R normalized? : (P,%) -> Boolean       reduceByQuasiMonic : (P,%) -> P
--R removeZero : (P,%) -> P              rest : % -> Union(%,"failed")
--R retract : List(P) -> %               sample : () -> %
--R stronglyReduce : (P,%) -> P          stronglyReduced? : % -> Boolean
--R trivialIdeal? : % -> Boolean         variables : % -> List(V)
--R zeroSetSplit : List(P) -> List(%)    ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R any? : ((P -> Boolean),%) -> Boolean if $ has finiteAggregate
--R autoReduced? : (%,((P,List(P)) -> Boolean)) -> Boolean
--R basicSet : (List(P),(P -> Boolean),((P,P) -> Boolean)) -> Union(Record(bas: %,top: List(P)),"failed")
--R basicSet : (List(P),((P,P) -> Boolean)) -> Union(Record(bas: %,top: List(P)),"failed")
--R coHeight : % -> NonNegativeInteger if V has FINITE
--R convert : % -> InputForm if P has KONVERT(INFORM)
--R count : ((P -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (P,%) -> NonNegativeInteger if $ has finiteAggregate and P has SETCAT
--R eval : (%,List(Equation(P))) -> % if P has EVALAB(P) and P has SETCAT
--R eval : (%,Equation(P)) -> % if P has EVALAB(P) and P has SETCAT
--R eval : (%,P,P) -> % if P has EVALAB(P) and P has SETCAT
--R eval : (%,List(P),List(P)) -> % if P has EVALAB(P) and P has SETCAT
--R every? : ((P -> Boolean),%) -> Boolean if $ has finiteAggregate
--R extendIfCan : (%,P) -> Union(%,"failed")
--R find : ((P -> Boolean),%) -> Union(P,"failed")
--R headRemainder : (P,%) -> Record(num: P,den: R) if R has INTDOM
--R initiallyReduced? : (P,%) -> Boolean
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((P -> P),%) -> % if $ has shallowlyMutable
--R member? : (P,%) -> Boolean if $ has finiteAggregate and P has SETCAT
--R members : % -> List(P) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(P) if $ has finiteAggregate
--R quasiComponent : % -> Record(close: List(P),open: List(P))
--R reduce : (P,%,((P,P) -> P),((P,P) -> Boolean)) -> P
--R reduce : (((P,P) -> P),%) -> P if $ has finiteAggregate
--R reduce : (((P,P) -> P),%,P) -> P if $ has finiteAggregate
--R reduce : (((P,P) -> P),%,P,P) -> P if $ has finiteAggregate and P has SETCAT
--R reduced? : (P,%,((P,P) -> Boolean)) -> Boolean
--R remainder : (P,%) -> Record(rnum: R,polnum: P,den: R) if R has INTDOM
--R remove : ((P -> Boolean),%) -> % if $ has finiteAggregate
```

```
--R remove : (P,%) -> % if $ has finiteAggregate and P has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and P has SETCAT
--R retractIfCan : List(P) -> Union(%,"failed")
--R rewriteIdealWithHeadRemainder : (List(P),%) -> List(P) if R has INTDOM
--R rewriteIdealWithRemainder : (List(P),%) -> List(P) if R has INTDOM
--R rewriteSetWithReduction : (List(P),%,((P,P) -> P),((P,P) -> Boolean)) -> List(P)
--R roughBase? : % -> Boolean if R has INTDOM
--R roughEqualIdeals? : (%,%) -> Boolean if R has INTDOM
--R roughSubIdeal? : (%,%) -> Boolean if R has INTDOM
--R roughUnitIdeal? : % -> Boolean if R has INTDOM
--R select : (%,V) -> Union(P,"failed")
--R select : ((P -> Boolean),%) -> % if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : (%,V) -> Record(under: %,floor: %,upper: %)
--R stronglyReduced? : (P,%) -> Boolean
--R triangular? : % -> Boolean if R has INTDOM
--R zeroSetSplitIntoTriangularSystems : List(P) -> List(Record(close: %,open: List(P)))
--R
--E 1

)spool
)lisp (bye)
```

———-


— GeneralTriangularSet.help —

```
=====================================================================
GeneralTriangularSet examples
=====================================================================

See Also:
o )show GeneralTriangularSet
```

———-

8.6.1 GeneralTriangularSet (GTSET)



See

⇒ “WuWenTsunTriangularSet” (WUTSET) 24.2.1 on page 2894

Exports:

algebraic?	algebraicVariables
any?	autoReduced?
basicSet	coerce
collect	collectQuasiMonic
collectUnder	collectUpper
coHeight	construct
convert	copy
count	degree
empty	empty?
eq?	eval
every?	extend
extendIfCan	find
first	hash
headReduce	headReduced?
headReduced?	headRemainder
infRittWu?	initiallyReduce
initiallyReduced?	initials
last	latex
less?	mainVariable?
mainVariables	map
map!	member?
members	more?
mvar	normalized?
normalized?	parts
quasiComponent	reduce
reduceByQuasiMonic	reduced?
remainder	remove
removeDuplicates	removeZero
rest	retract
retractIfCan	rewriteIdealWithHeadRemainder
rewriteIdealWithRemainder	rewriteSetWithReduction
roughBase?	roughEqualIdeals?
roughSubIdeal?	roughUnitIdeal?
sample	select
size?	sort
stronglyReduce	stronglyReduced?
triangular?	trivialIdeal?
variables	zeroSetSplit
zeroSetSplitIntoTriangularSystems	#?
?=?	?~=?

— domain GTSET GeneralTriangularSet —

```
)abbrev domain GTSET GeneralTriangularSet
++ Author: Marc Moreno Maza (marc@nag.co.uk)
```

```
++ Date Created: 10/06/1995
++ Date Last Updated: 06/12/1996
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References :
++  [1] P. AUBRY, D. LAZARD and M. MORENO MAZA "On the Theories
++      of Triangular Sets" Journal of Symbol. Comp. (to appear)
++ Description:
++ A domain constructor of the category \axiomType{TriangularSetCategory}.
++ The only requirement for a list of polynomials to be a member of such
++ a domain is the following: no polynomial is constant and two distinct
++ polynomials have distinct main variables. Such a triangular set may
++ not be auto-reduced or consistent. Triangular sets are stored
++ as sorted lists w.r.t. the main variables of their members but they
++ are displayed in reverse order.

GeneralTriangularSet(R,E,V,P) : Exports == Implementation where

  R : IntegralDomain
  E : OrderedAbelianMonoidSup
  V : OrderedSet
  P : RecursivePolynomialCategory(R,E,V)
  N ==> NonNegativeInteger
  Z ==> Integer
  B ==> Boolean
  LP ==> List P
  PtoP ==> P -> P

  Exports ==  TriangularSetCategory(R,E,V,P)

  Implementation == add

     Rep ==> LP

     rep(s:$):Rep == s pretend Rep
     per(l:Rep):$ == l pretend $

     copy ts ==
       per(copy(rep(ts))$LP)
     empty() ==
       per([])
     empty?(ts:$) ==
       empty?(rep(ts))
     parts ts ==
       rep(ts)
     members ts ==
       rep(ts)
```

```
map (f : PtoP, ts : $) : $ ==
  construct(map(f,rep(ts))$LP)$$
map! (f : PtoP, ts : $) : $  ==
  construct(map!(f,rep(ts))$LP)$$
member? (p,ts) ==
  member?(p,rep(ts))$LP

unitIdealIfCan() ==
  "failed"::Union($,"failed")
roughUnitIdeal? ts ==
  false

-- the following assume that rep(ts) is decreasingly sorted
-- w.r.t. the main variavles of the polynomials in rep(ts)
coerce(ts:$) : OutputForm ==
  lp : List(P) := reverse(rep(ts))
  brace([p::OutputForm for p in lp]$List(OutputForm))$OutputForm
mvar ts ==
  empty? ts => error"failed in mvar : $ -> V from GTSET"
  mvar(first(rep(ts)))$P
first ts ==
  empty? ts => "failed"::Union(P,"failed")
  first(rep(ts))::Union(P,"failed")
last ts ==
  empty? ts => "failed"::Union(P,"failed")
  last(rep(ts))::Union(P,"failed")
rest ts ==
  empty? ts => "failed"::Union($,"failed")
  per(rest(rep(ts)))::Union($,"failed")
coerce(ts:$) : (List P) ==
  rep(ts)
collectUpper (ts,v) ==
  empty? ts => ts
  lp := rep(ts)
  newlp : Rep := []
  while (not empty? lp) and (mvar(first(lp)) > v) repeat
    newlp := cons(first(lp),newlp)
    lp := rest lp
  per(reverse(newlp))
collectUnder (ts,v) ==
  empty? ts => ts
  lp := rep(ts)
  while (not empty? lp) and (mvar(first(lp)) >= v) repeat
    lp := rest lp
  per(lp)

-- for another domain of TSETCAT build on this domain GTSET
-- the following operations must be redefined
extendIfCan(ts:$,p:P) ==
  ground? p => "failed"::Union($,"failed")
```

```
       empty? ts => (per([unitCanonical(p)]$LP))::Union($,"failed")
       not (mvar(ts) < mvar(p)) => "failed"::Union($,"failed")
       (per(cons(p,rep(ts))))::Union($,"failed")
```

———-

— **GTSET.dotabb** —

```
"GTSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GTSET"]
"RPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RPOLCAT"]
"GTSET" -> "RPOLCAT"
```

———-

8.7 domain GSERIES GeneralUnivariatePowerSeries

— **GeneralUnivariatePowerSeries.input** —

```
)set break resume
)sys rm -f GeneralUnivariatePowerSeries.output
)spool GeneralUnivariatePowerSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GeneralUnivariatePowerSeries
--R
--R GeneralUnivariatePowerSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for GeneralUnivariatePowerSeries is GSERIES
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GSERIES
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coerce : Variable(var) -> %          coerce : Integer -> %
--R coerce : % -> OutputForm             complete : % -> %
--R degree : % -> Fraction(Integer)      hash : % -> SingleInteger
```

```
--R latex : % -> String                    leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %               map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean               one? : % -> Boolean
--R order : % -> Fraction(Integer)         pole? : % -> Boolean
--R recip : % -> Union(%,"failed")         reductum : % -> %
--R sample : () -> %                       variable : % -> Symbol
--R zero? : % -> Boolean                   ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRING(SYMB
--R D : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRIN
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and C
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Integer),Coef) -
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Fraction(Integer)) -> Coef if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,Fraction(Integer)) -> Coef
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R coerce : UnivariatePuiseuxSeries(Coef,var,cen) -> %
--R coerce : Coef -> % if Coef has COMRING
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(var)) -> %
--R differentiate : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRING(SYM
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRI
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Integer),Coef)
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,%) -> % if Fraction(Integer) has SGROUP
--R ?.? : (%,Fraction(Integer)) -> Coef
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,Fraction(Integer)) -> %
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolyno
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef ->
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(Fraction(Integer))) -> %
--R monomial : (%,SingletonAsOrderedSet,Fraction(Integer)) -> %
--R monomial : (Coef,Fraction(Integer)) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyExponents : (%,Fraction(Integer)) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,Fraction(Integer)) -> Fraction(Integer)
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R ?quo? : (%,%) -> % if Coef has FIELD
--R ?rem? : (%,%) -> % if Coef has FIELD
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : (NonNegativeInteger,Stream(Record(k: Fraction(Integer),c: Coef))) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R squareFree : % -> Factored(%) if Coef has FIELD
--R squareFreePart : % -> % if Coef has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: Fraction(Integer),c: Coef))
--R truncate : (%,Fraction(Integer),Fraction(Integer)) -> %
--R truncate : (%,Fraction(Integer)) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **GeneralUnivariatePowerSeries.help** —

```
=======================================================================
GeneralUnivariatePowerSeries examples
=======================================================================

See Also:
o )show GeneralUnivariatePowerSeries
```

———-

8.7.1 GeneralUnivariatePowerSeries (GSERIES)



Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coerce	complete	cos	cosh
cot	coth	csc	csch
D	degree	differentiate	divide
euclideanSize	eval	exp	expressIdealMember
exquo	extend	extendedEuclidean	factor
gcd	gcdPolynomial	hash	integrate
inv	latex	lcm	leadingCoefficient
leadingMonomial	log	map	monomial
monomial?	multiEuclidean	multiplyExponents	nthRoot
one?	order	pi	pole?
prime?	principalIdeal	recip	reductum
sample	sec	sech	series
sin	sinh	sizeLess?	sqrt
squareFree	squareFreePart	subtractIfCan	tan
tanh	terms	truncate	unit?
unitCanonical	unitNormal	variable	variables
zero?	?+?	?-?	-?
?=?	?^?	?~=?	?*?
?**?	?/?	?.?	
?quo?	?rem?		

— domain GSERIES GeneralUnivariatePowerSeries —

```
)abbrev domain GSERIES GeneralUnivariatePowerSeries
++ Author: Clifton J. Williamson
++ Date Created: 22 September 1993
++ Date Last Updated: 23 September 1993
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: series, Puiseux
++ Examples:
++ References:
++ Description:
++ This is a category of univariate Puiseux series constructed
++ from univariate Laurent series.  A Puiseux series is represented
++ by a pair \spad{[r,f(x)]}, where r is a positive rational number and
++ \spad{f(x)} is a Laurent series.  This pair represents the Puiseux
++ series \spad{f(x\^r)}.

GeneralUnivariatePowerSeries(Coef,var,cen): Exports == Implementation where
```

```
Coef : Ring
var  : Symbol
cen  : Coef
I      ==> Integer
UTS    ==> UnivariateTaylorSeries
ULS    ==> UnivariateLaurentSeries
UPXS   ==> UnivariatePuiseuxSeries
EFULS  ==> ElementaryFunctionsUnivariateLaurentSeries
EFUPXS ==> ElementaryFunctionsUnivariatePuiseuxSeries
FS2UPS ==> FunctionSpaceToUnivariatePowerSeries

Exports ==> UnivariatePuiseuxSeriesCategory Coef with
  coerce: Variable(var) -> %
    ++ coerce(var) converts the series variable \spad{var} into a
    ++ Puiseux series.
  coerce: UPXS(Coef,var,cen) -> %
    ++ coerce(f) converts a Puiseux series to a general power series.
  differentiate: (%,Variable(var)) -> %
    ++ \spad{differentiate(f(x),x)} returns the derivative of
    ++ \spad{f(x)} with respect to \spad{x}.
  if Coef has Algebra Fraction Integer then
    integrate: (%,Variable(var)) -> %
      ++ \spad{integrate(f(x))} returns an anti-derivative of the power
      ++ series \spad{f(x)} with constant coefficient 0.
      ++ We may integrate a series when we can divide coefficients
      ++ by integers.

Implementation ==> UnivariatePuiseuxSeries(Coef,var,cen) add

  coerce(upxs:UPXS(Coef,var,cen)) == upxs pretend %

  puiseux: % -> UPXS(Coef,var,cen)
  puiseux f == f pretend UPXS(Coef,var,cen)

  if Coef has Algebra Fraction Integer then

    differentiate f ==
      str1 : String := "'differentiate' unavailable on this domain;  "
      str2 : String := "use 'approximate' first"
      error concat(str1,str2)

    differentiate(f:%,v:Variable(var)) == differentiate f

    if Coef has PartialDifferentialRing(Symbol) then
      differentiate(f:%,s:Symbol) ==
        (s = variable(f)) =>
          str1 : String := "'differentiate' unavailable on this domain;  "
          str2 : String := "use 'approximate' first"
          error concat(str1,str2)
        dcds := differentiate(center f,s)
```

```
      deriv := differentiate(puiseux f) :: %
      map(x+->differentiate(x,s),f) - dcds * deriv

  integrate f ==
    str1 : String := "'integrate' unavailable on this domain;  "
    str2 : String := "use 'approximate' first"
    error concat(str1,str2)

  integrate(f:%,v:Variable(var)) == integrate f

  if Coef has integrate: (Coef,Symbol) -> Coef and _
     Coef has variables: Coef -> List Symbol then

    integrate(f:%,s:Symbol) ==
      (s = variable(f)) =>
        str1 : String := "'integrate' unavailable on this domain;  "
        str2 : String := "use 'approximate' first"
        error concat(str1,str2)
      not entry?(s,variables center f) => map(x+->integrate(x,s),f)
      error "integrate: center is a function of variable of integration"

  if Coef has TranscendentalFunctionCategory and _
     Coef has PrimitiveFunctionCategory and _
     Coef has AlgebraicallyClosedFunctionSpace Integer then

    integrateWithOneAnswer: (Coef,Symbol) -> Coef
    integrateWithOneAnswer(f,s) ==
      res := integrate(f,s)$FunctionSpaceIntegration(Integer,Coef)
      res case Coef => res :: Coef
      first(res :: List Coef)

    integrate(f:%,s:Symbol) ==
      (s = variable(f)) =>
        str1 : String := "'integrate' unavailable on this domain;  "
        str2 : String := "use 'approximate' first"
        error concat(str1,str2)
      not entry?(s,variables center f) =>
        map(x+->integrateWithOneAnswer(x,s),f)
      error "integrate: center is a function of variable of integration"
```

———-

— **GSERIES.dotabb** —

```
"GSERIES" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GSERIES"]
"ACFS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACFS"]
"GSERIES" -> "ACFS"
```

———-

8.8 domain GRIMAGE GraphImage

— GraphImage.input —

```
)set break resume
)sys rm -f GraphImage.output
)spool GraphImage.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GraphImage
--R
--R GraphImage  is a domain constructor
--R Abbreviation for GraphImage is GRIMAGE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GRIMAGE
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R graphImage : () -> %                  hash : % -> SingleInteger
--R key : % -> Integer                    latex : % -> String
--R makeGraphImage : % -> %               units : % -> List(Float)
--R ?~=? : (%,%) -> Boolean
--R appendPoint : (%,Point(DoubleFloat)) -> Void
--R coerce : List(List(Point(DoubleFloat))) -> %
--R component : (%,Point(DoubleFloat),Palette,Palette,PositiveInteger) -> Void
--R component : (%,Point(DoubleFloat)) -> Void
--R component : (%,List(Point(DoubleFloat)),Palette,Palette,PositiveInteger) -> Void
--R figureUnits : List(List(Point(DoubleFloat))) -> List(DoubleFloat)
--R makeGraphImage : (List(List(Point(DoubleFloat))),List(Palette),List(Palette),List(PositiveIn
--R makeGraphImage : (List(List(Point(DoubleFloat))),List(Palette),List(Palette),List(PositiveIn
--R makeGraphImage : List(List(Point(DoubleFloat))) -> %
--R point : (%,Point(DoubleFloat),Palette) -> Void
--R pointLists : % -> List(List(Point(DoubleFloat)))
--R putColorInfo : (List(List(Point(DoubleFloat))),List(Palette)) -> List(List(Point(DoubleFloat
--R ranges : (%,List(Segment(Float))) -> List(Segment(Float))
--R ranges : % -> List(Segment(Float))
--R units : (%,List(Float)) -> List(Float)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **GraphImage.help** —

```
====================================================================
GraphImage examples
====================================================================

See Also:
o )show GraphImage
```

———-

8.8.1 GraphImage (GRIMAGE)



Exports:

appendPoint	coerce	component	figureUnits	graphImage
hash	key	latex	makeGraphImage	point
pointLists	putColorInfo	ranges	units	?~=?
?=?				

— **domain GRIMAGE GraphImage** —

```
)abbrev domain GRIMAGE GraphImage
++ Author: Jim Wen
++ Date Created: 27 April 1989
++ Date Last Updated: 1995 September 20, Mike Richardson (MGR)
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
```

```
++ TwoDimensionalGraph creates virtual two dimensional graphs
++ (to be displayed on TwoDimensionalViewports).

GraphImage (): Exports == Implementation where

  VIEW    ==> VIEWPORTSERVER$Lisp
  sendI   ==> SOCK_-SEND_-INT
  sendSF  ==> SOCK_-SEND_-FLOAT
  sendSTR ==> SOCK_-SEND_-STRING
  getI    ==> SOCK_-GET_-INT
  getSF   ==> SOCK_-GET_-FLOAT

  typeGRAPH  ==> 2
  typeVIEW2D ==> 3

  makeGRAPH  ==> (-1)$SingleInteger
  makeVIEW2D ==> (-1)$SingleInteger

  I   ==> Integer
  PI  ==> PositiveInteger
  NNI ==> NonNegativeInteger
  SF  ==> DoubleFloat
  F   ==> Float
  L   ==> List
  P   ==> Point(SF)
  V   ==> Vector
  SEG ==> Segment
  RANGESF   ==> L SEG SF
  RANGEF    ==> L SEG F
  UNITSF   ==> L SF
  UNITF    ==> L F
  PAL ==> Palette
  E   ==> OutputForm
  DROP ==> DrawOption
  PP ==> PointPackage(SF)
  COORDSYS ==> CoordinateSystems(SF)

  Exports ==> SetCategory with
    graphImage      :  ()                                          -> $
      ++ graphImage() returns an empty graph with 0 point lists
      ++ of the domain \spadtype{GraphImage}.  A graph image contains
      ++ the graph data component of a two dimensional viewport.
    makeGraphImage  :  $                                           -> $
      ++ makeGraphImage(gi) takes the given graph, \spad{gi} of the
      ++ domain \spadtype{GraphImage}, and sends it's data to the
      ++ viewport manager where it waits to be included in a two-dimensional
      ++ viewport window.  \spad{gi} cannot be an empty graph, and it's
      ++ elements must have been created using the \spadfun{point} or
      ++ \spadfun{component} functions, not by a previous
      ++ \spadfun{makeGraphImage}.
```

```
makeGraphImage  :  (L L P)                                  -> $
  ++ makeGraphImage(llp) returns a graph of the domain
  ++ \spadtype{GraphImage} which is composed of the points and
  ++ lines from the list of lists of points, \spad{llp}, with
  ++ default point size and default point and line colours. The graph
  ++ data is then sent to the viewport manager where it waits to be
  ++ included in a two-dimensional viewport window.
makeGraphImage  :  (L L P,L PAL,L PAL,L PI)                 -> $
  ++ makeGraphImage(llp,lpal1,lpal2,lp) returns a graph of the
  ++ domain \spadtype{GraphImage} which is composed of the points
  ++ and lines from the list of lists of points, \spad{llp}, whose
  ++ point colors are indicated by the list of palette colors,
  ++ \spad{lpal1}, and whose lines are colored according to the list
  ++ of palette colors, \spad{lpal2}.  The paramater lp is a list of
  ++ integers which denote the size of the data points.  The graph
  ++ data is then sent to the viewport manager where it waits to be
  ++ included in a two-dimensional viewport window.
makeGraphImage  :  (L L P,L PAL,L PAL,L PI,L DROP)           -> $
  ++ makeGraphImage(llp,lpal1,lpal2,lp,lopt) returns a graph of
  ++ the domain \spadtype{GraphImage} which is composed of the
  ++ points and lines from the list of lists of points, \spad{llp},
  ++ whose point colors are indicated by the list of palette colors,
  ++ \spad{lpal1}, and whose lines are colored according to the list
  ++ of palette colors, \spad{lpal2}.  The paramater lp is a list of
  ++ integers which denote the size of the data points, and \spad{lopt}
  ++ is the list of draw command options.  The graph data is then sent
  ++ to the viewport manager where it waits to be included in a
  ++ two-dimensional viewport window.
pointLists      :  $                                        -> L L P
  ++ pointLists(gi) returns the list of lists of points which compose
  ++ the given graph, \spad{gi}, of the domain \spadtype{GraphImage}.
key             :  $                                        -> I
  ++ key(gi) returns the process ID of the given graph, \spad{gi},
  ++ of the domain \spadtype{GraphImage}.
ranges          :  $                                        -> RANGEF
  ++ ranges(gi) returns the list of ranges of the point components from
  ++ the indicated graph, \spad{gi}, of the domain \spadtype{GraphImage}.
ranges          :  ($,RANGEF)                               -> RANGEF
  ++ ranges(gi,lr) modifies the list of ranges for the given graph,
  ++ \spad{gi} of the domain \spadtype{GraphImage}, to be that of the
  ++ list of range segments, \spad{lr}, and returns the new range list
  ++ for \spad{gi}.
units           :  $                                        -> UNITF
  ++ units(gi) returns the list of unit increments for the x and y
  ++ axes of the indicated graph, \spad{gi}, of the domain
  ++ \spadtype{GraphImage}.
units           :  ($,UNITF)                                -> UNITF
  ++ units(gi,lu) modifies the list of unit increments for the x and y
  ++ axes of the given graph, \spad{gi} of the domain
  ++ \spadtype{GraphImage}, to be that of the list of unit increments,
```

```
  ++ \spad{lu}, and returns the new list of units for \spad{gi}.
component       :  ($,L P,PAL,PAL,PI)                          -> Void
  ++ component(gi,lp,pal1,pal2,p) sets the components of the
  ++ graph, \spad{gi} of the domain \spadtype{GraphImage}, to the
  ++ values given.  The point list for \spad{gi} is set to the list
  ++ \spad{lp}, the color of the points in \spad{lp} is set to
  ++ the palette color \spad{pal1}, the color of the lines which
  ++ connect the points \spad{lp} is set to the palette color
  ++ \spad{pal2}, and the size of the points in \spad{lp} is given
  ++ by the integer p.
component       :  ($,P)                                       -> Void
  ++ component(gi,pt) modifies the graph \spad{gi} of the domain
  ++ \spadtype{GraphImage} to contain one point component, \spad{pt}
  ++ whose point color, line color and point size are determined by
  ++ the default functions \spadfun{pointColorDefault},
  ++ \spadfun{lineColorDefault}, and \spadfun{pointSizeDefault}.
component       :  ($,P,PAL,PAL,PI)                            -> Void
  ++ component(gi,pt,pal1,pal2,ps) modifies the graph \spad{gi} of
  ++ the domain \spadtype{GraphImage} to contain one point component,
  ++ \spad{pt} whose point color is set to the palette color \spad{pal1},
  ++ line color is set to the palette color \spad{pal2}, and point
  ++ size is set to the positive integer \spad{ps}.
appendPoint     :  ($,P)                                       -> Void
  ++ appendPoint(gi,pt) appends the point \spad{pt} to the end
  ++ of the list of points component for the graph, \spad{gi}, which is
  ++ of the domain \spadtype{GraphImage}.
point           :  ($,P,PAL)                                   -> Void
  ++ point(gi,pt,pal) modifies the graph \spad{gi} of the domain
  ++ \spadtype{GraphImage} to contain one point component, \spad{pt}
  ++ whose point color is set to be the palette color \spad{pal}, and
  ++ whose line color and point size are determined by the default
  ++ functions \spadfun{lineColorDefault} and \spadfun{pointSizeDefault}.
coerce          :  L L P                                       -> $
  ++ coerce(llp)
  ++ component(gi,pt) creates and returns a graph of the domain
  ++ \spadtype{GraphImage} which is composed of the list of list
  ++ of points given by \spad{llp}, and whose point colors, line colors
  ++ and point sizes are determined by the default functions
  ++ \spadfun{pointColorDefault}, \spadfun{lineColorDefault}, and
  ++ \spadfun{pointSizeDefault}.  The graph data is then sent to the
  ++ viewport manager where it waits to be included in a two-dimensional
  ++ viewport window.
coerce          :  $                                           -> E
  ++ coerce(gi) returns the indicated graph, \spad{gi}, of domain
  ++ \spadtype{GraphImage} as output of the domain \spadtype{OutputForm}.
putColorInfo    : (L L P,L PAL)                                -> L L P
  ++ putColorInfo(llp,lpal) takes a list of list of points, \spad{llp},
  ++ and returns the points with their hue and shade components
  ++ set according to the list of palette colors, \spad{lpal}.
figureUnits : L L P                       -> UNITSF
```

```
  Implementation ==> add
    import Color()
    import Palette()
    import ViewDefaultsPackage()
    import PlotTools()
    import DrawOptionFunctions0
    import P
    import PP
    import COORDSYS

    Rep := Record(key: I, rangesField: RANGESF, unitsField: UNITSF, _
       llPoints: L L P, pointColors: L PAL, lineColors: L PAL, pointSizes: L PI, _
       optionsField: L DROP)

--%Internal Functions

    graph       : RANGEF                          -> $
    scaleStep   : SF                           -> SF
    makeGraph   :  $                           -> $


    numberCheck(nums:Point SF):Void ==
      for i in minIndex(nums)..maxIndex(nums) repeat
        COMPLEXP(nums.(i::PositiveInteger))$Lisp =>
          error "An unexpected complex number was encountered in the calculations."


    doOptions(g:Rep):Void ==
      lr : RANGEF := ranges(g.optionsField,ranges g)
      if (#lr > 1$I) then
        g.rangesField := [segment(convert(lo(lr.1))@SF,convert(hi(lr.1))@SF)$(Segment(SF)),
                          segment(convert(lo(lr.2))@SF,convert(hi(lr.2))@SF)$(Segment(SF))]
      else
        g.rangesField := []
      lu : UNITF := units(g.optionsField,units g)
      if (#lu > 1$I) then
        g.unitsField := [convert(lu.1)@SF,convert(lu.2)@SF]
      else
        g.unitsField := []
    -- etc - graphimage specific stuff...

    putColorInfo(llp,listOfPalettes) ==
      llp2 : L L P := []
      for lp in llp for pal in listOfPalettes repeat
        lp2 : L P := []
        daHue   := (hue(hue pal))::SF
        daShade := (shade pal)::SF
        for p in lp repeat
          if (d := dimension p) < 3 then
```

```
        p := extend(p,[daHue,daShade])
      else
        p.3 := daHue
        d < 4 => p := extend(p,[daShade])
        p.4 := daShade
      lp2 := cons(p,lp2)
    llp2 := cons(reverse_! lp2,llp2)
  reverse_! llp2

graph demRanges ==
  null demRanges =>  [ 0, [], [], [], [], [], [], [] ]
  demRangesSF : RANGESF := _
    [ segment(convert(lo demRanges.1)@SF,convert(hi demRanges.1)@SF)$(Segment(SF)), _
      segment(convert(lo demRanges.1)@SF,convert(hi demRanges.1)@SF)$(Segment(SF)) ]
  [ 0, demRangesSF, [], [], [], [], [], [] ]

scaleStep(range) ==                          -- MGR

  adjust:NNI
  tryStep:SF
  scaleDown:SF
  numerals:String
  adjust := 0
  while range < 100.0::SF repeat
    adjust := adjust + 1
    range := range * 10.0::SF -- might as well take big steps
  tryStep := range/10.0::SF
  numerals := string(((retract(ceiling(tryStep)$SF)$SF)@I))$String
  scaleDown := (10@I **$I (((#(numerals)@I) - 1$I) pretend PI))::SF
  scaleDown*ceiling(tryStep/scaleDown - 0.5::SF)/((10 **$I adjust)::SF)

figureUnits(listOfListsOfPoints) ==
    -- figure out the min/max and divide by 10 for unit markers
  xMin := xMax := xCoord first first listOfListsOfPoints
  yMin := yMax := yCoord first first listOfListsOfPoints
  if xMin ~= xMin then xMin:=max()
  if xMax ~= xMax then xMax:=min()
  if yMin ~= yMin then yMin:=max()
  if yMax ~= yMax then yMax:=min()
  for pL in listOfListsOfPoints repeat
    for p in pL repeat
      if ((px := (xCoord p)) < xMin) then
        xMin := px
      if px > xMax then
        xMax := px
      if ((py := (yCoord p)) < yMin) then
        yMin := py
      if py > yMax then
        yMax := py
  if xMin = xMax then
```

```
      xMin := xMin - convert(0.5)$Float
      xMax := xMax + convert(0.5)$Float
    if yMin = yMax then
      yMin := yMin - convert(0.5)$Float
      yMax := yMax + convert(0.5)$Float
    [scaleStep(xMax-xMin),scaleStep(yMax-yMin)]

  plotLists(graf:Rep,listOfListsOfPoints:L L P,listOfPointColors:L PAL,listOfLineColors:L PAL,listOfPoint
    givenLen := #listOfListsOfPoints
      -- take out point lists that are actually empty
    listOfListsOfPoints := [ l for l in listOfListsOfPoints | ^null l ]
    if (null listOfListsOfPoints) then
      error "GraphImage was given a list that contained no valid point lists"
    if ((len := #listOfListsOfPoints) ^= givenLen) then
      sayBrightly(["   Warning: Ignoring pointless point list"::E]$List(E))$Lisp
    graf.llPoints := listOfListsOfPoints
      -- do point colors
    if ((givenLen := #listOfPointColors) > len) then
       -- pad or discard elements if given list has length different from the point list
      graf.pointColors := concat(listOfPointColors,
          new((len - givenLen)::NonNegativeInteger + 1, pointColorDefault()))
    else graf.pointColors := first(listOfPointColors, len)
      -- do line colors
    if ((givenLen := #listOfLineColors) > len) then
      graf.lineColors := concat(listOfLineColors,
           new((len - givenLen)::NonNegativeInteger + 1, lineColorDefault()))
    else graf.lineColors := first(listOfLineColors, len)
      -- do point sizes
    if ((givenLen := #listOfPointSizes) > len) then
      graf.pointSizes := concat(listOfPointSizes,
           new((len - givenLen)::NonNegativeInteger + 1, pointSizeDefault()))
    else graf.pointSizes := first(listOfPointSizes, len)
    graf

  makeGraph graf ==
    doOptions(graf)
    (s := #(graf.llPoints)) = 0 =>
      error "You are trying to make a graph with no points"
    key graf ^= 0 =>
      error "You are trying to draw over an existing graph"
    transform := coord(graf.optionsField,cartesian$COORDSYS)$DrawOptionFunctions0
    graf.llPoints:= putColorInfo(graf.llPoints,graf.pointColors)
    if null(ranges graf) then  -- figure out best ranges for points
      graf.rangesField := calcRanges(graf.llPoints)  --::V SEG SF
    if null(units graf) then  -- figure out best ranges for points
      graf.unitsField := figureUnits(graf.llPoints)  --::V SEG SF
    sayBrightly(["   Graph data being transmitted to the viewport manager..."::E]$List(E))$Lisp
    sendI(VIEW,typeGRAPH)$Lisp
    sendI(VIEW,makeGRAPH)$Lisp
    tonto := (graf.rangesField)::RANGESF
```

```
      sendSF(VIEW,lo(first tonto))$Lisp
      sendSF(VIEW,hi(first tonto))$Lisp
      sendSF(VIEW,lo(second tonto))$Lisp
      sendSF(VIEW,hi(second tonto))$Lisp
      sendSF(VIEW,first (graf.unitsField))$Lisp
      sendSF(VIEW,second (graf.unitsField))$Lisp
      sendI(VIEW,s)$Lisp     -- how many lists of points are being sent
      for aList in graf.llPoints for pColor in graf.pointColors for lColor in graf.lineColors fo
        sendI(VIEW,#aList)$Lisp  -- how many points in this list
        for p in aList repeat
          aPoint := transform p
          sendSF(VIEW,xCoord aPoint)$Lisp
          sendSF(VIEW,yCoord aPoint)$Lisp
          sendSF(VIEW,hue(p)$PP)$Lisp  -- ?use aPoint as well...?
          sendSF(VIEW,shade(p)$PP)$Lisp
        hueShade := hue hue pColor + shade pColor * numberOfHues()
        sendI(VIEW,hueShade)$Lisp
        hueShade := (hue hue lColor -1)*5 + shade lColor
        sendI(VIEW,hueShade)$Lisp
        sendI(VIEW,s)$Lisp
      graf.key := getI(VIEW)$Lisp
      graf


--%Exported Functions
    makeGraphImage(graf:$)    == makeGraph graf
    key graf                  == graf.key
    pointLists graf           == graf.llPoints
    ranges graf                ==
      null graf.rangesField => []
      [segment(convert(lo graf.rangesField.1)@F,convert(hi graf.rangesField.1)@F), _
       segment(convert(lo graf.rangesField.2)@F,convert(hi graf.rangesField.2)@F)]
    ranges(graf,rangesList)     ==
      graf.rangesField :=
        [segment(convert(lo rangesList.1)@SF,convert(hi rangesList.1)@SF), _
         segment(convert(lo rangesList.2)@SF,convert(hi rangesList.2)@SF)]
      rangesList
    units graf                ==
      null(graf.unitsField) => []
      [convert(graf.unitsField.1)@F,convert(graf.unitsField.2)@F]
    units (graf,unitsToBe)    ==
      graf.unitsField := [convert(unitsToBe.1)@SF,convert(unitsToBe.2)@SF]
      unitsToBe
    graphImage                == graph []

    makeGraphImage(llp) ==
      makeGraphImage(llp,
        [pointColorDefault() for i in 1..(l:=#llp)],
         [lineColorDefault() for i in 1..l],
          [pointSizeDefault() for i in 1..l])
```

```
makeGraphImage(llp,lpc,llc,lps) ==
  makeGraphImage(llp,lpc,llc,lps,[])

makeGraphImage(llp,lpc,llc,lps,opts) ==
  graf := graph(ranges(opts,[]))
  graf.optionsField := opts
  graf := plotLists(graf,llp,lpc,llc,lps)
  transform := coord(graf.optionsField,cartesian$COORDSYS)$DrawOptionFunctions0
  for aList in graf.llPoints repeat
    for p in aList repeat
      aPoint := transform p
      numberCheck aPoint
  makeGraph graf

component (graf:$,ListOfPoints:L P,PointColor:PAL,LineColor:PAL,PointSize:PI) ==
  graf.llPoints    := append(graf.llPoints,[ListOfPoints])
  graf.pointColors := append(graf.pointColors,[PointColor])
  graf.lineColors  := append(graf.lineColors,[LineColor])
  graf.pointSizes  := append(graf.pointSizes,[PointSize])

component (graf,aPoint) ==
  component(graf,aPoint,pointColorDefault(),lineColorDefault(),pointSizeDefault())

component (graf:$,aPoint:P,PointColor:PAL,LineColor:PAL,PointSize:PI) ==
  component (graf,[aPoint],PointColor,LineColor,PointSize)

appendPoint (graf,aPoint) ==
  num : I  := #(graf.llPoints) - 1
  num < 0 => error "No point lists to append to!"
  (graf.llPoints.num) := append((graf.llPoints.num),[aPoint])

point (graf,aPoint,PointColor) ==
  component(graf,aPoint,PointColor,lineColorDefault(),pointSizeDefault())

coerce (llp : L L P) : $ ==
  makeGraphImage(llp,
      [pointColorDefault() for i in 1..(l:=#llp)],
       [lineColorDefault() for i in 1..l],
        [pointSizeDefault() for i in 1..l])

coerce (graf : $) : E ==
  hconcat( ["Graph with " :: E,(p := # pointLists graf) :: E,
     (p=1 => " point list"; " point lists") :: E])
```

———-

— **GRIMAGE.dotabb** —

```
"GRIMAGE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GRIMAGE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"GRIMAGE" -> "STRING"
```

8.9 domain GOPT GuessOption

— GuessOption.input —

```
)set break resume
)sys rm -f GuessOption.output
)spool GuessOption.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GuessOption
--R
--R GuessOption  is a domain constructor
--R Abbreviation for GuessOption is GOPT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GOPT
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                allDegrees : Boolean -> %
--R checkExtraValues : Boolean -> %       coerce : % -> OutputForm
--R debug : Boolean -> %                  displayKind : Symbol -> %
--R functionName : Symbol -> %            functionNames : List(Symbol) -> %
--R hash : % -> SingleInteger             indexName : Symbol -> %
--R latex : % -> String                   one : Boolean -> %
--R safety : NonNegativeInteger -> %      variableName : Symbol -> %
--R ?~=? : (%,%) -> Boolean
--R Somos : Union(PositiveInteger,Boolean) -> %
--R check : Union(skip,MonteCarlo,deterministic) -> %
--R homogeneous : Union(PositiveInteger,Boolean) -> %
--R maxDegree : Union(NonNegativeInteger,arbitrary) -> %
--R maxDerivative : Union(NonNegativeInteger,arbitrary) -> %
--R maxLevel : Union(NonNegativeInteger,arbitrary) -> %
--R maxMixedDegree : NonNegativeInteger -> %
--R maxPower : Union(PositiveInteger,arbitrary) -> %
--R maxShift : Union(NonNegativeInteger,arbitrary) -> %
--R maxSubst : Union(PositiveInteger,arbitrary) -> %
--R option : (List(%),Symbol) -> Union(Any,"failed")
--R
```

```
--E 1

)spool
)lisp (bye)
```

———-


— **GuessOption.help** —

```
=====================================================================
GuessOption examples
=====================================================================

See Also:
o )show GuessOption
```

———-

8.9.1 GuessOption (GOPT)



Exports:

?=?	?~=?	Somos	allDegrees	check
checkExtraValues	coerce	debug	displayKind	functionName
functionNames	hash	homogeneous	indexName	latex
maxDegree	maxDerivative	maxLevel	maxMixedDegree	maxPower
maxShift	maxSubst	one	option	safety variableName

— **domain GOPT GuessOption** —

```
)abbrev domain GOPT GuessOption
++ Author: Martin Rubey
++ Description: GuessOption is a domain whose elements are various options used
++ by Guess.
GuessOption(): Exports == Implementation where
```

```
Exports == SetCategory with

  maxDerivative: Union(NonNegativeInteger, "arbitrary") -> %
    ++ maxDerivative(d) specifies the maximum derivative in an algebraic
    ++ differential equation.  This option is expressed in the form
    ++ \spad{maxDerivative == d}.

  maxShift: Union(NonNegativeInteger, "arbitrary") -> %
    ++ maxShift(d) specifies the maximum shift in a recurrence
    ++ equation.  This option is expressed in the form \spad{maxShift == d}.

  maxSubst: Union(PositiveInteger, "arbitrary") -> %
    ++ maxSubst(d) specifies the maximum degree of the monomial substituted
    ++ into the function we are looking for.  That is, if \spad{maxSubst ==
    ++ d}, we look for polynomials such that $p(f(x), f(x^2), ...,
    ++ f(x^d))=0$.  equation.  This option is expressed in the form
    ++ \spad{maxSubst == d}.

  maxPower: Union(PositiveInteger, "arbitrary") -> %
    ++ maxPower(d) specifies the maximum degree in an algebraic differential
    ++ equation. For example, the degree of (f'')^3 f' is 4. maxPower(-1)
    ++ specifies that the maximum exponent can be arbitrary. This option is
    ++ expressed in the form \spad{maxPower == d}.

  homogeneous: Union(PositiveInteger, Boolean) -> %
    ++ homogeneous(d) specifies whether we allow only homogeneous algebraic
    ++ differential equations.  This option is expressed in the form
    ++ \spad{homogeneous == d}.  If true, then maxPower must be
    ++ set, too, and ADEs with constant total degree are allowed.
    ++ If a PositiveInteger is given, only ADE's with this total degree are
    ++ allowed.

  Somos: Union(PositiveInteger, Boolean) -> %
    ++ Somos(d) specifies whether we want that the total degree of the
    ++ differential operators is constant, and equal to d, or maxDerivative
    ++ if true. If true, maxDerivative must be set, too.

  maxLevel: Union(NonNegativeInteger, "arbitrary") -> %
    ++ maxLevel(d) specifies the maximum number of recursion levels operators
    ++ guessProduct and guessSum will be applied. This option is expressed in
    ++ the form spad{maxLevel == d}.

  maxDegree: Union(NonNegativeInteger, "arbitrary") -> %
    ++ maxDegree(d) specifies the maximum degree of the coefficient
    ++ polynomials in an algebraic differential equation or a recursion with
    ++ polynomial coefficients. For rational functions with an exponential
    ++ term, \spad{maxDegree} bounds the degree of the denominator
    ++ polynomial.
    ++ This option is expressed in the form \spad{maxDegree == d}.
```

```
maxMixedDegree: NonNegativeInteger -> %
  ++ maxMixedDegree(d) specifies the maximum q-degree of the coefficient
  ++ polynomials in a recurrence with polynomial coefficients, in the case
  ++ of mixed shifts.  Although slightly inconsistent, maxMixedDegree(0)
  ++ specifies that no mixed shifts are allowed. This option is expressed
  ++ in the form \spad{maxMixedDegree == d}.

allDegrees: Boolean -> %
  ++ allDegrees(d) specifies whether all possibilities of the degree vector
  ++ - taking into account maxDegree - should be tried. This is mainly
  ++ interesting for rational interpolation. This option is expressed in
  ++ the form \spad{allDegrees == d}.

safety: NonNegativeInteger -> %
  ++ safety(d) specifies the number of values reserved for testing any
  ++ solutions found. This option is expressed in the form \spad{safety ==
  ++ d}.

check: Union("skip", "MonteCarlo", "deterministic") -> %
  ++ check(d) specifies how we want to check the solution.  If
  ++ the value is "skip", we return the solutions found by the
  ++ interpolation routine without checking.  If the value is
  ++ "MonteCarlo", we use a probabilistic check.  This option is
  ++ expressed in the form \spad{check == d}

checkExtraValues: Boolean -> %
  ++ checkExtraValues(d) specifies whether we want to check the
  ++ solution beyond the order given by the degree bounds. This
  ++ option is expressed in the form \spad{checkExtraValues == d}

one: Boolean -> %
  ++ one(d) specifies whether we are happy with one solution. This option
  ++ is expressed in the form \spad{one == d}.

debug: Boolean -> %
  ++ debug(d) specifies whether we want additional output on the
  ++ progress. This option is expressed in the form \spad{debug == d}.

functionName: Symbol -> %
  ++ functionName(d) specifies the name of the function given by the
  ++ algebraic differential equation or recurrence. This option is
  ++ expressed in the form \spad{functionName == d}.

functionNames: List(Symbol) -> %
  ++ functionNames(d) specifies the names for the function in
  ++ algebraic dependence. This option is
  ++ expressed in the form \spad{functionNames == d}.

variableName: Symbol -> %
```

```
      ++ variableName(d) specifies the variable used in by the algebraic
      ++ differential equation. This option is expressed in the form
      ++ \spad{variableName == d}.

    indexName: Symbol -> %
      ++ indexName(d) specifies the index variable used for the formulas. This
      ++ option is expressed in the form \spad{indexName == d}.

    displayKind: Symbol -> %
      ++ displayKind(d) specifies kind of the result: generating function,
      ++ recurrence or equation. This option should not be set by the
      ++ user, but rather by the HP-specification.

    option : (List %, Symbol) -> Union(Any, "failed")
      ++ option(l, option) returns which options are given.

  Implementation ==> add
    import AnyFunctions1(Boolean)
    import AnyFunctions1(Symbol)
    import AnyFunctions1(NonNegativeInteger)
    import AnyFunctions1(Union(NonNegativeInteger, "arbitrary"))
    import AnyFunctions1(Union(PositiveInteger, "arbitrary"))
    import AnyFunctions1(Union(PositiveInteger, Boolean))
    import AnyFunctions1(Union("skip", "MonteCarlo", "deterministic"))

    Rep := Record(keyword: Symbol, value: Any)

    maxLevel d       == ['maxLevel,       d::Any]
    maxDerivative d  == ['maxDerivative,  d::Any]
    maxShift d       == maxDerivative d
    maxSubst d       ==
        if d case PositiveInteger
        then maxDerivative((d::Integer-1)::NonNegativeInteger)
        else maxDerivative d
    maxDegree d        == ['maxDegree,        d::Any]
    maxMixedDegree d   == ['maxMixedDegree,   d::Any]
    allDegrees d       == ['allDegrees,       d::Any]
    maxPower d         == ['maxPower,         d::Any]
    safety d           == ['safety,           d::Any]
    homogeneous d      == ['homogeneous,      d::Any]
    Somos d            == ['Somos,            d::Any]
    debug d            == ['debug,            d::Any]
    check d            == ['check,            d::Any]
    checkExtraValues d == ['checkExtraValues, d::Any]
    one d              == ['one,              d::Any]
    functionName d     == ['functionName,     d::Any]
    functionNames d ==
        ['functionNames, coerce(d)$AnyFunctions1(List(Symbol))]
    variableName d     == ['variableName,     d::Any]
    indexName d        == ['indexName,        d::Any]
```

```
    displayKind d      == ['displayKind,      d::Any]

    coerce(x:%):OutputForm == x.keyword::OutputForm = x.value::OutputForm
    x:% = y:%              == x.keyword = y.keyword and x.value = y.value

    option(l, s) ==
      for x in l repeat
        x.keyword = s => return(x.value)
      "failed"
```

———-

— **GOPT.dotabb** —

```
"GOPT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GOPT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"GOPT" -> "ALIST"
```

———-

8.10 domain GOPT0 GuessOptionFunctions0

— **GuessOptionFunctions0.input** —

```
)set break resume
)sys rm -f GuessOptionFunctions0.output
)spool GuessOptionFunctions0.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show GuessOptionFunctions0
--R
--R GuessOptionFunctions0  is a domain constructor
--R Abbreviation for GuessOptionFunctions0 is GOPT0
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for GOPT0
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R hash : % -> SingleInteger            latex : % -> String
--R one : List(GuessOption) -> Boolean   ?~=? : (%,%) -> Boolean
--R Somos : List(GuessOption) -> Union(PositiveInteger,Boolean)
```

```
--R allDegrees : List(GuessOption) -> Boolean
--R check : List(GuessOption) -> Union(skip,MonteCarlo,deterministic)
--R checkExtraValues : List(GuessOption) -> Boolean
--R checkOptions : List(GuessOption) -> Void
--R debug : List(GuessOption) -> Boolean
--R displayAsGF : List(GuessOption) -> Boolean
--R functionName : List(GuessOption) -> Symbol
--R homogeneous : List(GuessOption) -> Union(PositiveInteger,Boolean)
--R indexName : List(GuessOption) -> Symbol
--R maxDegree : List(GuessOption) -> Union(NonNegativeInteger,arbitrary)
--R maxDerivative : List(GuessOption) -> Union(NonNegativeInteger,arbitrary)
--R maxLevel : List(GuessOption) -> Union(NonNegativeInteger,arbitrary)
--R maxMixedDegree : List(GuessOption) -> NonNegativeInteger
--R maxPower : List(GuessOption) -> Union(PositiveInteger,arbitrary)
--R maxShift : List(GuessOption) -> Union(NonNegativeInteger,arbitrary)
--R maxSubst : List(GuessOption) -> Union(PositiveInteger,arbitrary)
--R safety : List(GuessOption) -> NonNegativeInteger
--R variableName : List(GuessOption) -> Symbol
--R
--E 1

)spool
)lisp (bye)
```

———-


— GuessOptionFunctions0.help —

```
=====================================================================
GuessOptionFunctions0 examples
=====================================================================

See Also:
o )show GuessOptionFunctions0
```

———-

8.10.1 GuessOptionFunctions0 (GOPT0)



Exports:

?=?	?~=?	MonteCarlo	Somos	allDegrees
check	checkOptions	coerce	debug	displayAsGF
functionName	hash	homogeneous	indexName	latex
maxDegree	maxDerivative	maxLevel	maxMixedDegree	maxPower
maxShift	maxSubst	one	safety	variableName

— domain GOPT0 GuessOptionFunctions0 —

```
)abbrev domain GOPT0 GuessOptionFunctions0
++ Author: Martin Rubey
++ Description:
++ GuessOptionFunctions0 provides operations that extract the
++ values of options for Guess.
GuessOptionFunctions0(): Exports == Implementation where

  LGOPT ==> List GuessOption

  Exports == SetCategory with

    maxDerivative: LGOPT -> Union(NonNegativeInteger, "arbitrary")
      ++ maxDerivative returns the specified maxDerivative.

    maxShift: LGOPT -> Union(NonNegativeInteger, "arbitrary")
      ++ maxShift returns the specified maxShift.

    maxSubst: LGOPT -> Union(PositiveInteger, "arbitrary")
      ++ maxSubst returns the specified maxSubst.

    maxPower: LGOPT -> Union(PositiveInteger, "arbitrary")
      ++ maxPower returns the specified maxPower.

    homogeneous: LGOPT -> Union(PositiveInteger, Boolean)
      ++ homogeneous returns whether we allow only homogeneous algebraic
      ++ differential equations, default being false
```

```
Somos: LGOPT -> Union(PositiveInteger, Boolean)
  ++ Somos returns whether we allow only Somos-like operators, default
  ++ being false

maxLevel: LGOPT -> Union(NonNegativeInteger, "arbitrary")
  ++ maxLevel returns the specified maxLevel.

maxDegree: LGOPT -> Union(NonNegativeInteger, "arbitrary")
  ++ maxDegree returns the specified maxDegree.

maxMixedDegree: LGOPT -> NonNegativeInteger
  ++ maxMixedDegree returns the specified maxMixedDegree.

allDegrees: LGOPT -> Boolean
  ++ allDegrees returns whether all possibilities of the degree vector
  ++ should be tried, the default being false.

safety: LGOPT -> NonNegativeInteger
  ++ safety returns the specified safety or 1 as default.

check: LGOPT -> Union("skip", "MonteCarlo", "deterministic")
  ++ check(d) specifies how we want to check the solution.  If
  ++ the value is "skip", we return the solutions found by the
  ++ interpolation routine without checking.  If the value is
  ++ "MonteCarlo", we use a probabilistic check.  The default is
  ++ "deterministic".

checkExtraValues: LGOPT -> Boolean
  ++ checkExtraValues(d) specifies whether we want to check the
  ++ solution beyond the order given by the degree bounds.  The
  ++ default is true.

one: LGOPT -> Boolean
  ++ one returns whether we need only one solution, default being true.

functionName: LGOPT -> Symbol
  ++ functionName returns the name of the function given by the algebraic
  ++ differential equation, default being f

variableName: LGOPT -> Symbol
  ++ variableName returns the name of the variable used in by the
  ++ algebraic differential equation, default being x

indexName: LGOPT -> Symbol
  ++ indexName returns the name of the index variable used for the
  ++ formulas, default being n

displayAsGF: LGOPT -> Boolean
  ++ displayAsGF specifies whether the result is a generating function
```

```
      ++ or a recurrence. This option should not be set by the user, but rather
      ++ by the HP-specification, therefore, there is no default.

    debug: LGOPT -> Boolean
      ++ debug returns whether we want additional output on the progress,
      ++ default being false

    checkOptions: LGOPT -> Void
      ++ checkOptions checks whether the given options are consistent, and
      ++ yields an error otherwise

  Implementation == add

    maxLevel l ==
      if (opt := option(l, 'maxLevel)) case "failed" then
        "arbitrary"
      else
        retract(opt::Any)$AnyFunctions1(Union(NonNegativeInteger, "arbitrary"))

    maxDerivative l ==
      if (opt := option(l, 'maxDerivative)) case "failed" then
        "arbitrary"
      else
        retract(opt::Any)$AnyFunctions1(Union(NonNegativeInteger, "arbitrary"))

    maxShift l == maxDerivative l

    maxSubst l ==
        d := maxDerivative l
        if d case NonNegativeInteger
        then (d+1)::PositiveInteger
        else d

    maxDegree l ==
      if (opt := option(l, 'maxDegree)) case "failed" then
        "arbitrary"
      else
        retract(opt::Any)$AnyFunctions1(Union(NonNegativeInteger, "arbitrary"))

    maxMixedDegree l ==
      if (opt := option(l, 'maxMixedDegree)) case "failed" then
        0
      else
        retract(opt :: Any)$AnyFunctions1(NonNegativeInteger)

    allDegrees l ==
      if (opt := option(l, 'allDegrees)) case "failed" then
        false
      else
        retract(opt :: Any)$AnyFunctions1(Boolean)
```

```
maxPower l ==
  if (opt := option(l, 'maxPower)) case "failed" then
    "arbitrary"
  else
    retract(opt :: Any)$AnyFunctions1(Union(PositiveInteger, "arbitrary"))

safety l ==
  if (opt := option(l, 'safety)) case "failed" then
    1$NonNegativeInteger
  else
    retract(opt :: Any)$AnyFunctions1(NonNegativeInteger)

check l ==
   if (opt := option(l, 'check)) case "failed" then
       "deterministic"
   else
       retract(opt::Any)$AnyFunctions1(_
                           Union("skip", "MonteCarlo", "deterministic"))

checkExtraValues l ==
   if (opt := option(l, 'checkExtraValues)) case "failed" then
       true
   else
       retract(opt :: Any)$AnyFunctions1(Boolean)

one l ==
  if (opt := option(l, 'one)) case "failed" then
    true
  else
    retract(opt :: Any)$AnyFunctions1(Boolean)

debug l ==
  if (opt := option(l, 'debug)) case "failed" then
    false
  else
    retract(opt :: Any)$AnyFunctions1(Boolean)

homogeneous l ==
  if (opt := option(l, 'homogeneous)) case "failed" then
    false
  else
    retract(opt :: Any)$AnyFunctions1(Union(PositiveInteger, Boolean))

Somos l ==
  if (opt := option(l, 'Somos)) case "failed" then
    false
  else
    retract(opt :: Any)$AnyFunctions1(Union(PositiveInteger, Boolean))
```

```
variableName l ==
  if (opt := option(l, 'variableName)) case "failed" then
    'x
  else
    retract(opt :: Any)$AnyFunctions1(Symbol)

functionName l ==
  if (opt := option(l, 'functionName)) case "failed" then
    'f
  else
    retract(opt :: Any)$AnyFunctions1(Symbol)

indexName l ==
  if (opt := option(l, 'indexName)) case "failed" then
    'n
  else
    retract(opt :: Any)$AnyFunctions1(Symbol)

displayAsGF l ==
  if (opt := option(l, 'displayAsGF)) case "failed" then
    error "GuessOption: displayAsGF not set"
  else
    retract(opt :: Any)$AnyFunctions1(Boolean)

NNI ==> NonNegativeInteger
PI  ==> PositiveInteger

checkOptions l ==
  maxD := maxDerivative l
  maxP := maxPower l
  homo := homogeneous l
  Somo := Somos l

  if Somo case PI then
      if one? Somo then
          error "Guess: Somos must be Boolean or at least two"

      if maxP case PI and one? maxP then
          error "Guess: Somos requires that maxPower is at least two"

      if maxD case NNI and maxD > Somo then
          err:String:=concat [_
            "Guess: if Somos is an integer, it should be larger than ",_
            "maxDerivative/maxShift or at least as big as maxSubst" ]
          error err
  else
      if Somo then
          if maxP case PI and one? maxP then
              error "Guess: Somos requires that maxPower is at least two"
```

```
            if not (maxD case NNI) or zero? maxD or one? maxD then
                err:String:= concat [_
                  "Guess: Somos==true requires that maxDerivative/maxShift",_
                  " is an integer, at least two, or maxSubst is an ",_
                  "integer, at least three" ]
                error err

            if not (maxP case PI) and homo case Boolean and not homo then
                err:String:= concat [_
                  "Guess: Somos requires that maxPower is set or ", _
                  "homogeneous is not false" ]
                error err

    if homo case PI then
        if maxP case PI and maxP ~= homo then
            err:String:= _
              "Guess: only one of homogeneous and maxPower may be an integer"
            error err

        if maxD case NNI and zero? maxD then
            err:String:= concat [_
              "Guess: homogeneous requires that maxShift/maxDerivative ",_
              "is at least one or maxSubst is at least two" ]
            error err
    else
        if homo then
            if not maxP case PI then
                err:String:= concat [_
                  "Guess: homogeneous==true requires that maxPower is ", _
                  "an integer" ]
                error err

            if maxD case NNI and zero? maxD then
                err:String:= concat [_
                  "Guess: homogeneous requires that maxShift/maxDerivative",_
                  " is at least one or maxSubst is at least two" ]
                error err
```

— GOPT0.dotabb —

```
"GOPT0" [color="#88FF44",href="bookvol10.3.pdf#nameddest=GOPT0"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"GOPT0" -> "STRING"
```

Chapter 9

Chapter H

9.1 domain HASHTBL HashTable

— HashTable.input —

```
)set break resume
)sys rm -f HashTable.output
)spool HashTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show HashTable
--R
--R HashTable(Key: SetCategory,Entry: SetCategory,hashfn: String)  is a domain constructor
--R Abbreviation for HashTable is HASHTBL
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for HASHTBL
--R
--R------------------------------ Operations --------------------------------
--R copy : % -> %                          dictionary : () -> %
--R elt : (%,Key,Entry) -> Entry           ?.? : (%,Key) -> Entry
--R empty : () -> %                        empty? : % -> Boolean
--R entries : % -> List(Entry)             eq? : (%,%) -> Boolean
--R index? : (Key,%) -> Boolean            indices : % -> List(Key)
--R key? : (Key,%) -> Boolean              keys : % -> List(Key)
--R map : ((Entry -> Entry),%) -> %        qelt : (%,Key) -> Entry
--R sample : () -> %                       setelt : (%,Key,Entry) -> Entry
--R table : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
```

```
--R any? : ((Entry -> Boolean),%) -> Boolean if $ has finiteAggregate
--R any? : ((Record(key: Key,entry: Entry) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R bag : List(Record(key: Key,entry: Entry)) -> %
--R coerce : % -> OutputForm if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R construct : List(Record(key: Key,entry: Entry)) -> %
--R convert : % -> InputForm if Record(key: Key,entry: Entry) has KONVERT(INFORM)
--R count : ((Entry -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (Entry,%) -> NonNegativeInteger if $ has finiteAggregate and Entry has SETCAT
--R count : (Record(key: Key,entry: Entry),%) -> NonNegativeInteger if $ has finiteAggregate and
--R count : ((Record(key: Key,entry: Entry) -> Boolean),%) -> NonNegativeInteger if $ has finite
--R dictionary : List(Record(key: Key,entry: Entry)) -> %
--R entry? : (Entry,%) -> Boolean if $ has finiteAggregate and Entry has SETCAT
--R eval : (%,List(Equation(Entry))) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,Equation(Entry)) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,Entry,Entry) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,List(Entry),List(Entry)) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,List(Record(key: Key,entry: Entry)),List(Record(key: Key,entry: Entry))) -> % if R
--R eval : (%,Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> % if Record(key: K
--R eval : (%,Equation(Record(key: Key,entry: Entry))) -> % if Record(key: Key,entry: Entry) has
--R eval : (%,List(Equation(Record(key: Key,entry: Entry)))) -> % if Record(key: Key,entry: Entr
--R every? : ((Entry -> Boolean),%) -> Boolean if $ has finiteAggregate
--R every? : ((Record(key: Key,entry: Entry) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R extract! : % -> Record(key: Key,entry: Entry)
--R fill! : (%,Entry) -> % if $ has shallowlyMutable
--R find : ((Record(key: Key,entry: Entry) -> Boolean),%) -> Union(Record(key: Key,entry: Entry)
--R first : % -> Entry if Key has ORDSET
--R hash : % -> SingleInteger if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R insert! : (Record(key: Key,entry: Entry),%) -> %
--R inspect : % -> Record(key: Key,entry: Entry)
--R latex : % -> String if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : (((Entry,Entry) -> Entry),%,%) -> %
--R map : ((Record(key: Key,entry: Entry) -> Record(key: Key,entry: Entry)),%) -> %
--R map! : ((Entry -> Entry),%) -> % if $ has shallowlyMutable
--R map! : ((Record(key: Key,entry: Entry) -> Record(key: Key,entry: Entry)),%) -> % if $ has sh
--R maxIndex : % -> Key if Key has ORDSET
--R member? : (Entry,%) -> Boolean if $ has finiteAggregate and Entry has SETCAT
--R member? : (Record(key: Key,entry: Entry),%) -> Boolean if $ has finiteAggregate and Record(k
--R members : % -> List(Entry) if $ has finiteAggregate
--R members : % -> List(Record(key: Key,entry: Entry)) if $ has finiteAggregate
--R minIndex : % -> Key if Key has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(Entry) if $ has finiteAggregate
--R parts : % -> List(Record(key: Key,entry: Entry)) if $ has finiteAggregate
--R qsetelt! : (%,Key,Entry) -> Entry if $ has shallowlyMutable
--R reduce : (((Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> Record(key: Key,
--R reduce : (((Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> Record(key: Key,
--R reduce : (((Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> Record(key: Key,
--R remove : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Record(key: Key,entry: Entry),%) -> % if $ has finiteAggregate and Record(key: Key
```

```
--R remove! : (Key,%) -> Union(Entry,"failed")
--R remove! : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : (Record(key: Key,entry: Entry),%) -> % if $ has finiteAggregate
--R removeDuplicates : % -> % if $ has finiteAggregate and Record(key: Key,entry: Entry) has SETCAT
--R search : (Key,%) -> Union(Entry,"failed")
--R select : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R swap! : (%,Key,Key) -> Void if $ has shallowlyMutable
--R table : List(Record(key: Key,entry: Entry)) -> %
--R ?~=? : (%,%) -> Boolean if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **HashTable.help** —

```
=====================================================================
HashTable examples
=====================================================================

See Also:
o )show HashTable
```

———-

9.1.1 HashTable (HASHTBL)



See

⇒ “InnerTable” (INTABL) 10.27.1 on page 1303

⇒ "Table" (TABLE) 21.1.1 on page 2631
⇒ "EqTable" (EQTBL) 6.2.1 on page 669
⇒ "StringTable" (STRTBL) 20.32.1 on page 2578
⇒ "GeneralSparseTable" (GSTBL) 8.5.1 on page 1048
⇒ "SparseTable" (STBL) 20.16.1 on page 2418

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	entry?	elt
empty	empty?	entries	eq?	eval
every?	extract!	fill!	find	first
hash	index?	indices	insert!	inspect
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
select	select!	setelt	size?	swap!
table	#?	?=?	?~=?	?.?

— domain HASHTBL HashTable —

```
)abbrev domain HASHTBL HashTable
++ Author: Stephen M. Watt
++ Date Created: 1985
++ Date Last Updated: June 21, 1991
++ Basic Operations:
++ Related Domains: Table, EqTable, StringTable
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain provides access to the underlying Lisp hash tables.
++ By varying the hashfn parameter, tables suited for different
++ purposes can be obtained.

HashTable(Key, Entry, hashfn): Exports == Implementation where
    Key, Entry: SetCategory
    hashfn: String --  Union("EQ", "UEQUAL", "CVEC", "ID")

    Exports ==> TableAggregate(Key, Entry) with
                    finiteAggregate

    Implementation ==> add
        Pair ==> Record(key: Key, entry: Entry)
        Ex   ==> OutputForm
        failMsg := GENSYM()$Lisp
```

```
        t1 = t2              == EQ(t1, t2)$Lisp
        keys t               == HKEYS(t)$Lisp
        # t                  == HASH_-TABLE_-COUNT(t)$Lisp
        setelt(t, k, e)      == HPUT(t,k,e)$Lisp
        remove_!(k:Key, t:%) ==
          r := HGET(t,k,failMsg)$Lisp
          not EQ(r,failMsg)$Lisp =>
            HREM(t, k)$Lisp
            r pretend Entry
          "failed"

        empty() ==
            MAKE_-HASHTABLE(INTERN(hashfn)$Lisp,
                            INTERN("STRONG")$Lisp)$Lisp

        search(k:Key, t:%)  ==
            r := HGET(t, k, failMsg)$Lisp
            not EQ(r, failMsg)$Lisp => r pretend Entry
            "failed"
```

———-

— HASHTBL.dotabb —

```
"HASHTBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HASHTBL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"HASHTBL" -> "TBAGG"
```

———-

9.2 domain HEAP Heap

— Heap.input —

```
)set break resume
)sys rm -f Heap.output
)spool Heap.output
)set message test on
)set message auto off
)clear all

--S 1 of 42
a:Heap INT:= heap [1,2,3,4,5]
--R
```

```
--R
--R   (1)  [5,4,2,1,3]
--R                                                    Type: Heap(Integer)
--E 1

--S 2 of 42
bag([1,2,3,4,5])$Heap(INT)
--R
--R
--R   (2)  [5,4,3,1,2]
--R                                                    Type: Heap(Integer)
--E 2

--S 3 of 42
c:=copy a
--R
--R
--R   (3)  [5,4,2,1,3]
--R                                                    Type: Heap(Integer)
--E 3

--S 4 of 42
empty? a
--R
--R
--R   (4)  false
--R                                                         Type: Boolean
--E 4

--S 5 of 42
b:=empty()$(Heap INT)
--R
--R
--R   (5)  []
--R                                                    Type: Heap(Integer)
--E 5

--S 6 of 42
empty? b
--R
--R
--R   (6)  true
--R                                                         Type: Boolean
--E 6

--S 7 of 42
eq?(a,c)
--R
--R
--R   (7)  false
```

```
--R                                                                  Type: Boolean
--E 7

--S 8 of 42
extract! a
--R
--R
--R   (8)  5
--R                                                 Type: PositiveInteger
--E 8

--S 8 of 42
h:=heap [17,-4,9,-11,2,7,-7]
--R
--R
--R   (9)  [17,2,9,- 11,- 4,7,- 7]
--R                                                   Type: Heap(Integer)
--E 8

--S 9 of 42
[extract!(h) while not empty?(h)]
--R
--R
--R   (10)  [17,9,7,2,- 4,- 7,- 11]
--R                                                   Type: List(Integer)
--E 9

--S 10 of 42
heapsort(x) == (empty? x => []; cons(extract!(x),heapsort x))
--R
--R                                                              Type: Void
--E 10

--S 11 of 42
h1 := heapsort heap [17,-4,9,-11,2,7,-7]
--R
--R   Compiling function heapsort with type Heap(Integer) -> List(Integer)
--R
--R
--R   (12)  [17,9,7,2,- 4,- 7,- 11]
--R                                                    Type: List Integer
--E 11

--S 12 of 42
(a=c)@Boolean
--R
--R
--R   (13)  false
--R                                                                   Type: Boolean
--E 12
```

```
--S 13 of 42
(a~=c)
--R
--R
--R   (14)  true
--R                                                        Type: Boolean
--E 13

--S 14 of 42
a
--R
--R
--R   (15)  [4,3,2,1]
--R                                           Type: Heap(Integer)
--E 14

--S 15 of 42
inspect a
--R
--R
--R   (16)  4
--R                                        Type: PositiveInteger
--E 15

--S 16 of 42
insert!(9,a)
--R
--R
--R   (17)  [9,4,2,1,3]
--R                                           Type: Heap(Integer)
--E 16

--S 17 of 42
map(x+->x+10,a)
--R
--R
--R   (18)  [19,14,12,11,13]
--R                                           Type: Heap(Integer)
--E 17

--S 18 of 42
a
--R
--R
--R   (19)  [9,4,2,1,3]
--R                                           Type: Heap(Integer)
--E 18

--S 19 of 42
```

```
map!(x+->x+10,a)
--R
--R
--R   (20)  [19,14,12,11,13]
--R                                                    Type: Heap(Integer)
--E 19

--S 20 of 42
a
--R
--R
--R   (21)  [19,14,12,11,13]
--R                                                    Type: Heap(Integer)
--E 20

--S 21 of 42
max a
--R
--R
--R   (22)  19
--R                                                 Type: PositiveInteger
--E 21

--S 22 of 42
merge(a,c)
--R
--R
--R   (23)  [19,14,12,11,13,5,4,2,1,3]
--R                                                    Type: Heap(Integer)
--E 22

--S 23 of 42
a
--R
--R
--R   (24)  [19,14,12,11,13]
--R                                                    Type: Heap(Integer)
--E 23

--S 24 of 42
merge!(a,c)
--R
--R
--R   (25)  [19,14,12,11,13,5,4,2,1,3]
--R                                                    Type: Heap(Integer)
--E 24

--S 25 of 42
a
--R
```

```
--R
--R   (26)  [19,14,12,11,13,5,4,2,1,3]
--R                                                    Type: Heap(Integer)
--E 25

--S 26 of 42
c
--R
--R
--R   (27)  [5,4,2,1,3]
--R                                                    Type: Heap(Integer)
--E 26

--S 27 of 42
sample()$Heap(INT)
--R
--R
--R   (28)  []
--R                                                    Type: Heap(Integer)
--E 27

--S 28 of 42
#a
--R
--R
--R   (29)  10
--R                                                 Type: PositiveInteger
--E 28

--S 29 of 42
any?(x+->(x=14),a)
--R
--R
--R   (30)  true
--R                                                           Type: Boolean
--E 29

--S 30 of 42
every?(x+->(x=11),a)
--R
--R
--R   (31)  false
--R                                                           Type: Boolean
--E 30

--S 31 of 42
parts a
--R
--R
--R   (32)  [19,14,12,11,13,5,4,2,1,3]
```

```
--R                                                    Type: List(Integer)
--E 31

--S 32 of 42
size?(a,9)
--R
--R
--R   (33)  false
--R                                                          Type: Boolean
--E 32

--S 33 of 42
more?(a,9)
--R
--R
--R   (34)  true
--R                                                          Type: Boolean
--E 33

--S 34 of 42
less?(a,9)
--R
--R
--R   (35)  false
--R                                                          Type: Boolean
--E 34

--S 35 of 42
members a
--R
--R
--R   (36)  [19,14,12,11,13,5,4,2,1,3]
--R                                                    Type: List(Integer)
--E 35

--S 36 of 42
member?(14,a)
--R
--R
--R   (37)  true
--R                                                          Type: Boolean
--E 36

--S 37 of 42
latex a
--R
--R
--R   (38)  "\mbox{\bf Unimplemented}"
--R                                                           Type: String
--E 37
```

```
--S 38 of 42
hash a
--R
--R
--I   (39)  36647017
--R                                                    Type: SingleInteger
--E 38

--S 39 of 42
count(14,a)
--R
--R
--R   (40)  1
--R                                                  Type: PositiveInteger
--E 39

--S 40 of 42
count(x+->(x>13),a)
--R
--R
--R   (41)  2
--R                                                  Type: PositiveInteger
--E 40

--S 41 of 42
coerce a
--R
--R
--R   (42)  [19,14,12,11,13,5,4,2,1,3]
--R                                                      Type: OutputForm
--E 41

--S 42 of 42
)show Heap
--R
--R Heap(S: OrderedSet)  is a domain constructor
--R Abbreviation for Heap is HEAP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for HEAP
--R
--R------------------------------ Operations --------------------------------
--R bag : List(S) -> %                    copy : % -> %
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                extract! : % -> S
--R heap : List(S) -> %                   insert! : (S,%) -> %
--R inspect : % -> S                      map : ((S -> S),%) -> %
--R max : % -> S                         merge : (%,%) -> %
--R merge! : (%,%) -> %                  sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
```

```
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 42

)spool
)lisp (bye)
```

———-

— Heap.help —

```
=====================================================================
Heap examples
=====================================================================

The domain Heap(S) implements a priority queue of objects of type S
such that the operation extract! removes and returns the maximum
element.  The implementation represents heaps as flexible arrays The
representation and algorithms give complexity of O(log(n)) for
insertion and extractions, and O(n) for construction.

Create a heap of five elements:

   a:Heap INT:= heap [1,2,3,4,5]
        [5,4,2,1,3]

Use bag to convert a Bag into a Heap:

   bag([1,2,3,4,5])$Heap(INT)
        [5,4,3,1,2]
```

```
The operation copy can be used to copy a Heap:

   c:=copy a
        [5,4,2,1,3]

Use empty? to check if the heap is empty:

   empty? a
        false

Use empty to create a new, empty heap:

   b:=empty()$(Heap INT)
        []

and we can see that the newly created heap is empty:

   empty? b
        true

The eq? function compares the reference of one heap to another:

   eq?(a,c)
        false

The extract! function removes largest element of the heap:

   extract! a
        5

Now extract! elements repeatedly until none are left, collecting
the elements in a list.

  [extract!(h) while not empty?(h)]
    [9,7,3,2,- 4,- 7]
                      Type: List Integer

Another way to produce the same result is by defining a heapsort function.

  heapsort(x) == (empty? x => []; cons(extract!(x),heapsort x))
                      Type: Void

Create another sample heap.

  h1 := heap [17,-4,9,-11,2,7,-7]
    [17,2,9,- 11,- 4,7,- 7]
                      Type: Heap Integer

Apply heapsort to present elements in order.
```

```
  heapsort h1
    [17,9,7,2,- 4,- 7,- 11]
                      Type: List Integer
```

Heaps can be compared with =

```
   (a=c)@Boolean
        false
```

and ~=

```
   (a~=c)
       true
```

The inspect function shows the largest element in the heap:

```
   inspect a
       4
```

The insert! function adds an element to the heap:

```
   insert!(9,a)
       [9,4,2,1,3]
```

The map function applies a function to every element of the heap
and returns a new heap:

```
   map(x+->x+10,a)
       [19,14,12,11,13]
```

The original heap is unchanged:

```
   a
       [9,4,2,1,3]
```

The map! function applies a function to every element of the heap
and returns the original heap with modifications:

```
   map!(x+->x+10,a)
       [19,14,12,11,13]
```

The original heap has been modified:

```
   a
       [19,14,12,11,13]
```

The max function returns the largest element in the heap:

```
   max a
```

```
       19

The merge function takes two heaps and creates a new heap with
all of the elements:

   merge(a,c)
       [19,14,12,11,13,5,4,2,1,3]

Notice that the original heap is unchanged:

   a
       [19,14,12,11,13]

The merge! function takes two heaps and modifies the first heap
argument to contain all of the elements:

   merge!(a,c)
       [19,14,12,11,13,5,4,2,1,3]

Notice that the first argument was modified:

   a
       [19,14,12,11,13,5,4,2,1,3]

but the second argument was not:

   c
       [5,4,2,1,3]

A new, empty heap can be created with sample:

   sample()$Heap(INT)
       []

The # function gives the size of the heap:

   #a
       10

The any? function tests each element against a predicate function
and returns true if any pass:

   any?(x+->(x=14),a)
       true

The every? function tests each element against a predicate function
and returns true if they all pass:

   every?(x+->(x=11),a)
       false
```

```
The parts function returns a list of the elements in the heap:

   parts a
       [19,14,12,11,13,5,4,2,1,3]

The size? predicate compares the size of the heap to a value:

   size?(a,9)
       false

The more? predicate asks if the heap size is larger than a value:

   more?(a,9)
       true

The less? predicate asks if the heap size is smaller than a value:

   less?(a,9)
       false

The members function returns a list of the elements of the heap:

   members a
       [19,14,12,11,13,5,4,2,1,3]

The member? predicate asks if an element is in the heap:

   member?(14,a)
       true

The count function has two forms, one of which counts the number
of copies of an element in the heap:

   count(14,a)
       1


The second form of the count function accepts a predicate to test
against each member of the heap and counts the number of true results:

   count(x+->(x>13),a)
       2

See Also:
o )show Stack
o )show ArrayStack
o )show Queue
o )show Dequeue
o )show Heap
o )show BagAggregate
```

———-

9.2.1 Heap (HEAP)



See

⇒ “Stack” (STACK) 20.28.1 on page 2530
⇒ “ArrayStack” (ASTACK) 2.10.1 on page 65
⇒ “Queue” (QUEUE) 18.5.1 on page 2150
⇒ “Dequeue” (DEQUEUE) 5.5.1 on page 499

Exports:

any?	bag	coerce	copy	count
empty	empty?	eq?	eval	every?
extract!	hash	heap	insert!	inspect
latex	less?	map	map!	max
member?	members	merge	merge!	more?
parts	sample	size?	#?	?=?
?~=?				

— domain HEAP Heap —

```
)abbrev domain HEAP Heap
++ Author: Michael Monagan and Stephen Watt
++ Date Created:June 86 and July 87
++ Date Last Updated:Feb 92
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
```

```
++ Heap implemented in a flexible array to allow for insertions
++ Complexity: O(log n) insertion, extraction and O(n) construction
--% Dequeue and Heap data types

Heap(S:OrderedSet): Exports == Implementation where
  Exports == PriorityQueueAggregate S with
    heap : List S -> %
      ++ heap(ls) creates a heap of elements consisting of the
      ++ elements of ls.
      ++
      ++E i:Heap INT := heap [1,6,3,7,5,2,4]

 -- Inherited Signatures repeated for examples documentation

    bag : List S -> %
      ++
      ++X bag([1,2,3,4,5])$Heap(INT)
    copy : % -> %
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X copy a
    empty? : % -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X empty? a
    empty : () -> %
      ++
      ++X b:=empty()$(Heap INT)
    eq? : (%,%) -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X b:=copy a
      ++X eq?(a,b)
    extract_! : % -> S
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X extract! a
      ++X a
    insert_! : (S,%) -> %
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X insert!(8,a)
      ++X a
    inspect : % -> S
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X inspect a
    map :  ((S -> S),%) -> %
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
```

```
    ++X map(x+->x+10,a)
    ++X a
  max : % -> S
    ++
    ++X a:Heap INT:= heap [1,2,3,4,5]
    ++X max a
  merge : (%,%) -> %
    ++
    ++X a:Heap INT:= heap [1,2,3,4,5]
    ++X b:Heap INT:= heap [6,7,8,9,10]
    ++X merge(a,b)
  merge! : (%,%) -> %
    ++
    ++X a:Heap INT:= heap [1,2,3,4,5]
    ++X b:Heap INT:= heap [6,7,8,9,10]
    ++X merge!(a,b)
    ++X a
    ++X b
  sample : () -> %
    ++
    ++X sample()$Heap(INT)
  less? : (%,NonNegativeInteger) -> Boolean
    ++
    ++X a:Heap INT:= heap [1,2,3,4,5]
    ++X less?(a,9)
  more? : (%,NonNegativeInteger) -> Boolean
    ++
    ++X a:Heap INT:= heap [1,2,3,4,5]
    ++X more?(a,9)
  size? : (%,NonNegativeInteger) -> Boolean
    ++
    ++X a:Heap INT:= heap [1,2,3,4,5]
    ++X size?(a,5)
  if $ has shallowlyMutable then
    map! :  ((S -> S),%) -> %
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X map!(x+->x+10,a)
      ++X a
  if S has SetCategory then
    latex : % -> String
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X latex a
    hash : % -> SingleInteger
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X hash a
    coerce : % -> OutputForm
      ++
```

```
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X coerce a
    "=": (%,%) -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X b:Heap INT:= heap [1,2,3,4,5]
      ++X (a=b)@Boolean
    "~=" : (%,%) -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X b:=copy a
      ++X (a~=b)
  if % has finiteAggregate then
    every? : ((S -> Boolean),%) -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X every?(x+->(x=4),a)
    any? : ((S -> Boolean),%) -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X any?(x+->(x=4),a)
    count :  ((S -> Boolean),%) -> NonNegativeInteger
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X count(x+->(x>2),a)
    _# : % -> NonNegativeInteger
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X #a
    parts : % -> List S
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X parts a
    members : % -> List S
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X members a
  if % has finiteAggregate and S has SetCategory then
    member? : (S,%) -> Boolean
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X member?(3,a)
    count : (S,%) -> NonNegativeInteger
      ++
      ++X a:Heap INT:= heap [1,2,3,4,5]
      ++X count(4,a)

Implementation == IndexedFlexibleArray(S,0) add
  Rep := IndexedFlexibleArray( S,0)
  empty() == empty()$Rep
```

```
heap l ==
  n := #l
  h := empty()
  n = 0 => h
  for x in l repeat insert_!(x,h)
  h
siftUp: (%,Integer,Integer) -> Void
siftUp(r,i,n) ==
   -- assertion 0 <= i < n
   t := r.i
   while (j := 2*i+1) < n repeat
      if (k := j+1) < n and r.j < r.k then j := k
      if t < r.j then (r.i := r.j; r.j := t; i := j) else leave

extract_! r ==
   -- extract the maximum from the heap O(log n)
   n := #r :: Integer
   n = 0 => error "empty heap"
   t := r(0)
   r(0) := r(n-1)
   delete_!(r,n-1)
   n = 1 => t
   siftUp(r,0,n-1)
   t

insert_!(x,r) ==
   -- Williams' insertion algorithm O(log n)
   j := (#r) :: Integer
   r:=concat_!(r,concat(x,empty()$Rep))
   while j > 0 repeat
      i := (j-1) quo 2
      if r(i) >= x then leave
      r(j) := r(i)
      j := i
   r(j):=x
   r

max r == if #r = 0 then error "empty heap" else r.0
inspect r == max r

makeHeap(r:%):% ==
   -- Floyd's heap construction algorithm O(n)
   n := #r
   for k in n quo 2 -1 .. 0 by -1 repeat siftUp(r,k,n)
   r
bag l == makeHeap construct(l)$Rep
merge(a,b) == makeHeap concat(a,b)
merge_!(a,b) == makeHeap concat_!(a,b)
```

———-

— **HEAP.dotabb** —

```
"HEAP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HEAP"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"HEAP" -> "A1AGG"
```

———-

9.3 domain HEXADEC HexadecimalExpansion

— **HexadecimalExpansion.input** —

```
)set break resume
)sys rm -f HexadecimalExpansion.output
)spool HexadecimalExpansion.output
)set message test on
)set message auto off
)clear all
--S 1 of 7
r := hex(22/7)
--R
--R
--R          ---
--R   (1)  3.249
--R                                                  Type: HexadecimalExpansion
--E 1

--S 2 of 7
r + hex(6/7)
--R
--R
--R   (2)  4
--R                                                  Type: HexadecimalExpansion
--E 2

--S 3 of 7
[hex(1/i) for i in 350..354]
--R
--R
--R   (3)
--R       ---------------    ---------      -----    ----------------------
--R   [0.00BB3EE721A54D88, 0.00BAB6561, 0.00BA2E8, 0.00B9A7862A0FF465879D5F,
--R       ----------------------------
```

```
--R    0.00B92143FA36F5E02E4850FE8DBD78]
--R                                                Type: List(HexadecimalExpansion)
--E 3

--S 4 of 7
hex(1/1007)
--R
--R
--R   (4)
--R   0.
--R     OVERBAR
--R        0041149783F0BF2C7D13933192AF6980619EE345E91EC2BB9D5CCA5C071E40926E54E8D
--R          DAE24196C0B2F8A0AAD60DBA57F5D4C8536262210C74F1
--R                                                       Type: HexadecimalExpansion
--E 4

--S 5 of 7
p := hex(1/4)*x**2 + hex(2/3)*x + hex(4/9)
--R
--R
--R            2     _      ___
--R   (5)  0.4x  + 0.Ax + 0.71C
--R                                          Type: Polynomial(HexadecimalExpansion)
--E 5

--S 6 of 7
q := D(p, x)
--R
--R
--R                 _
--R   (6)  0.8x + 0.A
--R                                          Type: Polynomial(HexadecimalExpansion)
--E 6

--S 7 of 7
g := gcd(p, q)
--R
--R
--R              _
--R   (7)  x + 1.5
--R                                          Type: Polynomial(HexadecimalExpansion)
--E 7
)spool
)lisp (bye)
```

— HexadecimalExpansion.help —

```
======================================================================
HexadecimalExpansion
======================================================================

All rationals have repeating hexadecimal expansions.  The operation
hex returns these expansions of type HexadecimalExpansion.  Operations
to access the individual numerals of a hexadecimal expansion can be
obtained by converting the value to RadixExpansion(16).  More examples
of expansions are available in the DecimalExpansion, BinaryExpansion,
and RadixExpansion.

This is a hexadecimal expansion of a rational number.

  r := hex(22/7)
      ---
    3.249
                      Type: HexadecimalExpansion

Arithmetic is exact.

  r + hex(6/7)
    4
                      Type: HexadecimalExpansion

The period of the expansion can be short or long ...

  [hex(1/i) for i in 350..354]
       ---------------    ---------      -----    ----------------------
   [0.00BB3EE721A54D88, 0.00BAB6561, 0.00BA2E8, 0.00B9A7862A0FF465879D5F,
       ----------------------------
    0.00B92143FA36F5E02E4850FE8DBD78]
                      Type: List HexadecimalExpansion

or very long!

  hex(1/1007)
     ------------------------------------------------------------------------
   0.0041149783F0BF2C7D13933192AF6980619EE345E91EC2BB9D5CCA5C071E40926E54E8D
     ---------------------------------------------
     DAE24196C0B2F8A0AAD60DBA57F5D4C8536262210C74F1
                      Type: HexadecimalExpansion

These numbers are bona fide algebraic objects.

  p := hex(1/4)*x**2 + hex(2/3)*x + hex(4/9)
        2     _      ---
    0.4x  + 0.Ax + 0.71C
                      Type: Polynomial HexadecimalExpansion


  q := D(p, x)
```

```
                _
    0.8x + 0.A
                                Type: Polynomial HexadecimalExpansion

  g := gcd(p, q)
            _
    x + 1.5
                                Type: Polynomial HexadecimalExpansion

See Also:
o )help RadixExpansion
o )help BinaryExpansion
o )help DecimalExpansion
o )show HexadecimalExpansion
```

9.3.1 HexadecimalExpansion (HEXADEC)



See

⇒ “RadixExpansion” (RADIX) 19.2.1 on page 2171
⇒ “BinaryExpansion” (BINARY) 3.7.1 on page 276
⇒ “DecimalExpansion” (DECIMAL) 5.3.1 on page 453

Exports:

0	1
abs	associates?
ceiling	characteristic
charthRoot	coerce
conditionP	convert
D	denom
denominator	differentiate
divide	euclideanSize
eval	expressIdealMember
exquo	extendedEuclidean
factor	factorPolynomial
factorSquareFreePolynomial	floor
fractionPart	gcd
gcdPolynomial	hash
hex	init
inv	latex
lcm	map
max	min
multiEuclidean	negative?
nextItem	numer
numerator	one?
patternMatch	positive?
prime?	principalIdeal
random	recip
reducedSystem	retract
retractIfCan	sample
sign	sizeLess?
solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial
subtractIfCan	unit?
unitCanonical	unitNormal
wholePart	zero?
?*?	?**?
?+?	?-?
-?	?/?
?=?	?^?
?~=?	?<?
?<=?	?>?
?>=?	?.?
?quo?	?rem?

— domain HEXADEC HexadecimalExpansion —

```
)abbrev domain HEXADEC HexadecimalExpansion
++ Author: Clifton J. Williamson
```

```
++ Date Created: April 26, 1990
++ Date Last Updated: May 15, 1991
++ Basic Operations:
++ Related Domains: RadixExpansion
++ Also See:
++ AMS Classifications:
++ Keywords: radix, base, hexadecimal
++ Examples:
++ References:
++ Description:
++ This domain allows rational numbers to be presented as repeating
++ hexadecimal expansions.

HexadecimalExpansion(): Exports == Implementation where
  Exports ==> QuotientFieldCategory(Integer) with
    coerce: % -> Fraction Integer
      ++ coerce(h) converts a hexadecimal expansion to a rational number.
    coerce: % -> RadixExpansion(16)
      ++ coerce(h) converts a hexadecimal expansion to a radix expansion
      ++ with base 16.
    fractionPart: % -> Fraction Integer
      ++ fractionPart(h) returns the fractional part of a hexadecimal expansion.
    hex: Fraction Integer -> %
      ++ hex(r) converts a rational number to a hexadecimal expansion.

  Implementation ==> RadixExpansion(16) add
    hex r == r :: %
    coerce(x:%): RadixExpansion(16) == x pretend RadixExpansion(16)
```

———-

— HEXADEC.dotabb —

```
"HEXADEC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HEXADEC"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"HEXADEC" -> "PFECAT"
```

———-

9.4 package HTMLFORM HTMLFormat

Here I have put some information about 'how to use' and 'the benefits of' this HTML formatter. Also some information for programmers if they want to extend this package.

If you want information about creating output formatters in general then, rather than duplicating content here I refer you to mathml.spad.pamphlet containing the MathMLFormat

domain by Arthur C. Ralfs. This contains useful information for writers of output formatters.

9.4.1 Overview

This package allows users to cut and paste output from the Axiom command line to a HTML page. This output is enabled by typing:

```
)set output html on
```

After this the command line will output html (in addition to other formats that are enabled) and this html code can then be copied and pasted into a HTML document.

The HTML produced is well formed XML, that is, all tags have equivalent closing tags.

9.4.2 Why output to HTML?

In some ways HTMLFormat is a compromise between the standard text output and specialised formats like MathMLFormat. The potential quality is never going to be as good as output to a specialised maths renderer but on the other hand it is a lot better than the clunky fixed width font text output. The quality is not the only issue though, the direct output in any format is unlikely to be exactly what the user wants, so possibly more important than quality is the ability to edit the output.

HTMLFormat has advantages that the other output formats don't, for instance,

- It works with any browser without the need for plugins (as far as I know most computers should have the required fonts)
- Users can easily annotate and add comments using colour, bold, underline and so on.
- Annotations can easily be done with whatever html editor or text editor you are familiar with.
- Edits to the output will cause the width of columns and so on to be automatically adjusted, no need to try to insert spaces to get the superscripts to line up again!
- It is very easy to customise output so, for instance, we can fit a lot of information in a compact space on the page.

9.5 Using the formatter

We can cause the command line interpreter to output in html by typing the following:

```
)set output html on
```

After this the command line will output html (in addition to other formats that are enabled) and this html code can then be copied and pasted into an existing HTML document.

If you do not already have an html page to copy the output to then you can create one with a text editor and entering the following:

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
 "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" >
 <head>
  <title>Enter Your Title Here</title>
 </head>
 <body>
  Copy and paste the output from command line here.
 </body>
</html>
```

Or using any program that will export to html such as OpenOffice.org writer.

9.6 Form of the output

```
HTMLFormat does not try to interpret syntax, for instance in an example like:
(1) -> integral(x^x,x)
it just takes what OutputForm provides and does not try to replace
%A with the bound variable x.
```

9.7 Matrix Formatting

A big requirement for me is to fit big matrices on ordinary web pages.

At the moment the default output for a matrix is a grid, however it easy to modify this for a single matrix, or a whole page or whole site by using css (cascading style sheets). For instance we can get a more conventional looking matrix by adding the following style to the top of the page after the ¡head¿ tag:

```
<style type="text/css">
#matl {border-left-style:solid}
#matr {border-right-style:solid}
#matlt {border-left-style:solid;border-top-style:solid}
#matrt {border-right-style:solid;border-top-style:solid}
#matlb {border-left-style:solid;border-bottom-style:solid}
#matrb {border-right-style:solid;border-bottom-style:solid}
</style>
```

There are many other possibilities, for instance we can generate a matrix with bars either side to indicate a determinant. All we have to do is change the css for the site, page or individual element.

9.8 Programmers Guide

This package converts from OutputForm, which is a hierarchical tree structure, to html which uses tags arranged in a hierarchical tree structure. So the package converts from one tree (graph) structure to another.

This conversion is done in two stages using an intermediate Tree String structure. This Tree String structure represents HTML where:

- leafs represents unstructured text
- string in leafs contains the text
- non-leafs represents xml elements
- string in non-leafs represents xml attributes

This is created by traversing OutputForm while building up the Tree String structure.

The second stage is to convert the Tree Structure to text. All text output is done using:

```
sayTeX$Lisp
```

I have not produced and output to String as I don't know a way to append to a long string efficiently and I don't know how to insert carriage- returns into a String.

9.8.1 Future Developments

There would be some benefits in creating a XMLFormat category which would contain common elements for all xml formatted outputs such as HTMLFormat, MathMLFormat, SVGFormat and X3DFormat. However programming effort might be better spent creating a version of OutputForm which has better syntax information.

— HTMLFormat.input —

```
)set break resume
)sys rm -f HTMLFormat.output
)spool HTMLFormat.output
)set message test on
)set message auto off
)clear all

--S 1 of 9
)show HTMLFormat
--R HTMLFormat  is a domain constructor
--R Abbreviation for HTMLFormat is HTMLFORM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for HTMLFORM
```

```
--R
--R------------------------------- Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : OutputForm -> String
--R coerce : % -> OutputForm              coerceL : OutputForm -> String
--R coerceS : OutputForm -> String        display : String -> Void
--R exprex : OutputForm -> String         hash : % -> SingleInteger
--R latex : % -> String                   ?~=? : (%,%) -> Boolean
--R
--E 1

--S 2 of 9
coerce("3+4"::OutputForm)$HTMLFORM
--R
--R"3+4"
--R
--R   (1)  " "
--R                                                            Type: String
--E 2

--S 3 of 9
coerce("sqrt(3+4)"::OutputForm)$HTMLFORM
--R
--R"sqrt(3+4)"
--R
--R   (2)  " "
--R                                                            Type: String
--E 3

--S 4 of 9
coerce(sqrt(3+4)::OutputForm)$HTMLFORM
--R
--R&radic;7
--R
--R   (3)  " "
--R                                                            Type: String
--E 4

--S 5 of 9
coerce(sqrt(3+x)::OutputForm)$HTMLFORM
--R
--R<table border='0' id='root'>
--R<tr id='root'>
--R<td id='root'>
--R&radic;
--R</td>
--R<td id='root' style='border-top-style:solid'>
--Rx+3
--R</td>
--R</tr>
--R</table>
```

```
--R
--R   (4)  " "
--R                                                          Type: String
--E 5

--S 6 of 9
coerceS(sqrt(3+x)::OutputForm)$HTMLFORM
--R
--R<table border='0' id='root'>
--R<tr id='root'>
--R<td id='root'>
--R&radic;
--R</td>
--R<td id='root' style='border-top-style:solid'>
--Rx+3
--R</td>
--R</tr>
--R</table>
--R
--R   (5)  " "
--R                                                          Type: String
--E 6

--S 7 of 9
coerceL(sqrt(3+x)::OutputForm)$HTMLFORM
--R
--R<table border='0' id='root'>
--R<tr id='root'>
--R<td id='root'>
--R&radic;
--R</td>
--R<td id='root' style='border-top-style:solid'>
--Rx+3
--R</td>
--R</tr>
--R</table>
--R
--R   (6)  " "
--R                                                          Type: String
--E 7

--S 8 of 9
exprex(sqrt(3+x)::OutputForm)$HTMLFORM
--R
--R
--R   (7)  "{{ROOT}{{+}{x}{3}}}"
--R                                                          Type: String
--E 8

--S 9 of 9
```

```
display(coerce(sqrt(3+x)::OutputForm)$HTMLFORM)$HTMLFORM
--R
--R<table border='0' id='root'>
--R<tr id='root'>
--R<td id='root'>
--R&radic;
--R</td>
--R<td id='root' style='border-top-style:solid'>
--Rx+3
--R</td>
--R</tr>
--R</table>
--R
--R                                                                    Type: Void
--E 9
)spool
)lisp (bye)
```

———-

— HTMLFormat.help —

```
========================================================================
HTMLFormat examples
========================================================================

coerce("3+4"::OutputForm)$HTMLFORM
  "3+4"

coerce("sqrt(3+4)"::OutputForm)$HTMLFORM
  "sqrt(3+4)"

coerce(sqrt(3+4)::OutputForm)$HTMLFORM
  &radic;7

coerce(sqrt(3+x)::OutputForm)$HTMLFORM
  <table border='0' id='root'>
  <tr id='root'>
  <td id='root'>
  &radic;
  </td>
  <td id='root' style='border-top-style:solid'>
  x+3
  </td>
  </tr>
  </table>

coerceS(sqrt(3+x)::OutputForm)$HTMLFORM
  <table border='0' id='root'>
```

```
  <tr id='root'>
  <td id='root'>
  &radic;
  </td>
  <td id='root' style='border-top-style:solid'>
  x+3
  </td>
  </tr>
  </table>

coerceL(sqrt(3+x)::OutputForm)$HTMLFORM
  <table border='0' id='root'>
  <tr id='root'>
  <td id='root'>
  &radic;
  </td>
  <td id='root' style='border-top-style:solid'>
  x+3
  </td>
  </tr>
  </table>


exprex(sqrt(3+x)::OutputForm)$HTMLFORM
  "{{ROOT}{{+}{x}{3}}}"

display(coerce(sqrt(3+x)::OutputForm)$HTMLFORM)$HTMLFORM
  <table border='0' id='root'>
  <tr id='root'>
  <td id='root'>
  &radic;
  </td>
  <td id='root' style='border-top-style:solid'>
  x+3
  </td>
  </tr>
  </table>

See Also:
o )show HTMLFormat
```

———-

9.8.2 HTMLFormat (HTMLFORM)



See

⇐ "SetCategory" (SETCAT) **??** on page **??**

Exports:

?=?	? =?	coerce	coerceL	coerceS
display	exprex	hash	latex	

— domain HTMLFORM HTMLFormat —

```
)abbrev domain HTMLFORM HTMLFormat
++ Author: Martin J Baker, Arthur C. Ralfs, Robert S. Sutor
++ Date: January 2010
++ Description:
++ HtmlFormat provides a coercion from OutputForm to html.
HTMLFormat(): public == private where
  E      ==> OutputForm
  I      ==> Integer
  L      ==> List
  S      ==> String

  public == SetCategory with
    coerce:    E -> S
      ++ coerce(o) changes o in the standard output format to html format.
      ++
      ++X coerce(sqrt(3+x)::OutputForm)$HTMLFORM
    coerceS:   E -> S
      ++ coerceS(o) changes o in the standard output format to html
      ++ format and displays formatted result.
      ++
      ++X coerceS(sqrt(3+x)::OutputForm)$HTMLFORM
    coerceL:   E -> S
      ++ coerceL(o) changes o in the standard output format to html
      ++ format and displays result as one long string.
      ++
      ++X coerceL(sqrt(3+x)::OutputForm)$HTMLFORM
    exprex:    E -> S
```

```
    ++ exprex(o) coverts \spadtype{OutputForm} to \spadtype{String}
    ++
    ++X exprex(sqrt(3+x)::OutputForm)$HTMLFORM
  display:   S -> Void
    ++ display(o) prints the string returned by coerce.
    ++
    ++X display(coerce(sqrt(3+x)::OutputForm)$HTMLFORM)$HTMLFORM

private == add
  import OutputForm
  import Character
  import Integer
  import List OutputForm
  import List String

  expr: E
  prec,opPrec: I
  str:  S
  blank         : S := " \  "

  maxPrec       : I   := 1000000
  minPrec       : I   := 0

  unaryOps      : L S := ["-"]$(L S)
  unaryPrecs    : L I := [700]$(L I)

  -- the precedence of / in the following is relatively low because
  -- the bar obviates the need for parentheses.
  binaryOps     : L S := ["+->","|","^","/","<",">","=","OVER"]$(L S)
  binaryPrecs   : L I := [0,0,900,700,400,400,400,700]$(L I)
  naryOps       : L S := ["-","+","*",blank,",",";"," ","ROW","",
     " \cr ","&","/\","\/"]$(L S)
  naryPrecs     : L I := [700,700,800,800,110,110,0,0,0,0,0,600,600]$(L I)
  naryNGOps     : L S := ["ROW","&"]$(L S)
  plexOps       : L S := ["SIGMA","SIGMA2","PI","PI2","INTSIGN",_
                          "INDEFINTEGRAL"]$(L S)
  plexPrecs     : L I := [700,800,700,800,700,700]$(L I)
  specialOps    : L S := ["MATRIX","BRACKET","BRACE","CONCATB","VCONCAT",_
                          "AGGLST","CONCAT","OVERBAR","ROOT","SUB","TAG",_
                          "SUPERSUB","ZAG","AGGSET","SC","PAREN",_
                          "SEGMENT","QUOTE","theMap", "SLASH"]

  -- the next two lists provide translations for some strings for
  -- which HTML has some special character codes.
  specialStrings : L S :=
    ["cos", "cot", "csc", "log", "sec", "sin", "tan", _
     "cosh", "coth", "csch", "sech", "sinh", "tanh", _
     "acos","asin","atan","erf","...","$","infinity","Gamma", _
     "%pi","%e","%i"]
  specialStringsInHTML : L S :=
```

```
    ["cos","cot","csc","log","sec","sin","tan", _
     "cosh","coth","csch","sech","sinh","tanh", _
     "arccos","arcsin","arctan","erf","&#x2026;","$","&#x221E;",_
     "&#x0413;","&#x003C0;","&#x02147;","&#x02148;"]

  debug := false

  atomize:E -> L E

  formatBinary:(S,L E, I) -> Tree S

  formatFunction:(Tree S,L E, I) -> Tree S

  formatMatrix:L E -> Tree S

  formatNary:(S,L E, I) -> Tree S

  formatNaryNoGroup:(S,L E, I) -> Tree S

  formatNullary:S -> Tree S

  formatPlex:(S,L E, I) -> Tree S

  formatSpecial:(S,L E, I) -> Tree S

  formatUnary:(S,  E, I) -> Tree S

  formatHtml:(E,I) -> Tree S

  precondition:E -> E
    -- this function is applied to the OutputForm expression before
    -- doing anything else.

  outputTree:Tree S -> Void
    -- This function traverses the tree and linierises it into a string.
    -- To get the formatting we use a nested set of tables. It also checks
    -- for +- and removes the +. it may also need to remove the outer
    -- set of brackets.

  stringify:E -> S

  coerce(expr : E): S ==
    outputTree formatHtml(precondition expr, minPrec)
    " "

  coerceS(expr : E): S ==
    outputTree formatHtml(precondition expr, minPrec)
    " "

  coerceL(expr : E): S ==
```

```
    outputTree formatHtml(precondition expr, minPrec)
    " "

  display(html : S): Void ==
    sayTeX$Lisp html
    void()$Void

  newNode(tag:S,node: Tree S): (Tree S) ==
    t := tree(S,[node])
    setvalue!(t,tag)
    t

  newNodes(tag:S,nodes: L Tree S): (Tree S) ==
    t := tree(S,nodes)
    setvalue!(t,tag)
    t

  -- returns true if this can be represented without a table
  notTable?(node: Tree S): Boolean ==
    empty?(node) => true
    leaf?(node) => true
    prefix?("table",value(node))$String => false
    c := children(node)
    for a in c repeat
      if not notTable?(a) then return false
    true

  -- this retuns a string representation of OutputForm arguments
  -- it is used when debug is true to trace the calling of functions
  -- in this package
  argsToString(args : L E): S ==
    sop : S := exprex first args
    args := rest args
    s : S := concat ["{",sop]
    for a in args repeat
        s1 : S := exprex a
        s := concat [s,s1]
    s := concat [s,"}"]

  exprex(expr : E): S ==
    -- This breaks down an expression into atoms and returns it as
    -- a string.  It's for developmental purposes to help understand
    -- the expressions.
    a : E
    expr := precondition expr
    (ATOM(expr)$Lisp@Boolean) or (stringify expr = "NOTHING") =>
      concat ["{",stringify expr,"}"]
    le : L E := (expr pretend L E)
    op := first le
    sop : S := exprex op
```

```
    args : L E := rest le
    nargs : I := #args
    s : S := concat ["{",sop]
    if nargs > 0  then
      for a in args repeat
        s1 : S := exprex a
        s := concat [s,s1]
    s := concat [s,"}"]

  atomize(expr : E): L E ==
    -- This breaks down an expression into a flat list of atomic
    -- expressions.
    -- expr should be preconditioned.
    le : L E := nil()
    a : E
    letmp : L E
    (ATOM(expr)$Lisp@Boolean) or (stringify expr = "NOTHING") =>
      le := append(le,list(expr))
    letmp := expr pretend L E
    for a in letmp repeat
      le := append(le,atomize a)
    le

  -- output html test using tables and
  -- remove unnecessary '+' at end of first string
  -- when second string starts with '-'
  outputTree(t: Tree S): Void ==
    endWithPlus:Boolean := false -- if the last string ends with '+'
    -- and the next string starts with '-' then the '+' needs to be
    -- removed
    if empty?(t) then
      --if debug then sayTeX$Lisp "outputTree empty"
      return void()$Void
    if leaf?(t) then
      --if debug then sayTeX$Lisp concat("outputTree leaf:",value(t))
      sayTeX$Lisp value(t)
      return void()$Void
    tagName := copy value(t)
    tagPos := position(char(" "),tagName,1)$String
    if tagPos > 1 then
      tagName := split(tagName,char(" ")).1
      --sayTeX$Lisp "outputTree: tagPos="string(tagPos)" "tagName
    if value(t) ~= "" then sayTeX$Lisp concat ["<",value(t),">"]
    c := children(t)
    enableGrid:Boolean := (#c > 1) and not notTable?(t)
    if enableGrid then
      if tagName = "table" then enableGrid := false
      if tagName = "tr" then enableGrid := false
    b:List Boolean := [leaf?(c1) for c1 in c]
    -- if all children are strings then no need to wrap in table
```

```
    allString: Boolean := true
    for c1 in c repeat if not leaf?(c1) then allString := false
    if allString then
      s:String := ""
      for c1 in c repeat s := concat(s,value(c1))
      sayTeX$Lisp s
      if value(t) ~= "" then sayTeX$Lisp concat ["</",tagName,">"]
      return void()$Void
    if enableGrid then
      sayTeX$Lisp "<table border='0'>"
      sayTeX$Lisp "<tr>"
    for c1 in c repeat
      if enableGrid then sayTeX$Lisp "<td>"
      outputTree(c1)
      if enableGrid then sayTeX$Lisp "</td>"
    if enableGrid then
      sayTeX$Lisp "</tr>"
      sayTeX$Lisp "</table>"
    if value(t) ~= "" then sayTeX$Lisp concat ["</",tagName,">"]
    void()$Void

  stringify expr == (mathObject2String$Lisp expr)@S

  precondition expr ==
    outputTran$Lisp expr

  -- I dont know what SC is so put it in a table for now
  formatSC(args : L E, prec : I)  : Tree S ==
    if debug then sayTeX$Lisp "formatSC: "concat [" args=",_
      argsToString(args)," prec=",string(prec)$S]
    null args => tree("")
    cells:L Tree S := [_
      newNode("td id='sc' style='border-bottom-style:solid'",_
      formatHtml(a,prec)) for a in args]
    row:Tree S := newNodes("tr id='sc'",cells)
    newNode("table border='0' id='sc'",row)

  -- to build an overbar we put it in a single column,
  -- single row table and set the top border to solid
  buildOverbar(content : Tree S) : Tree S ==
    if debug then sayTeX$Lisp "buildOverbar"
    cell:Tree S := _
      newNode("td id='overbar' style='border-top-style:solid'",content)
    row:Tree S := newNode("tr id='overbar'",cell)
    newNode("table border='0' id='overbar'",row)

  -- to build an square root we put it in a double column,
  -- single row table and set the top border of the second column to
  -- solid
  buildRoot(content : Tree S) : Tree S ==
```

```
    if debug then sayTeX$Lisp "buildRoot"
    if leaf?(content) then
      -- root of a single term so no need for overbar
      return newNodes("",[tree("&radic;"),content])
    cell1:Tree S := newNode("td id='root'",tree("&radic;"))
    cell2:Tree S := _
      newNode("td id='root' style='border-top-style:solid'",content)
    row:Tree S := newNodes("tr id='root'",[cell1,cell2])
    newNode("table border='0' id='root'",row)

  -- to build an 'n'th root we put it in a double column,
  -- single row table and set the top border of the second column to
  -- solid
  buildNRoot(content : Tree S,nth: Tree S) : Tree S ==
    if debug then sayTeX$Lisp "buildNRoot"
    power:Tree S := newNode("sup",nth)
    if leaf?(content) then
      -- root of a single term so no need for overbar
      return newNodes("",[power,tree("&radic;"),content])
    cell1:Tree S := newNodes("td id='nroot'",[power,tree("&radic;")])
    cell2:Tree S := _
      newNode("td id='nroot' style='border-top-style:solid'",content)
    row:Tree S := newNodes("tr id='nroot'",[cell1,cell2])
    newNode("table border='0' id='nroot'",row)

  -- formatSpecial handles "theMap","AGGLST","AGGSET","TAG","SLASH",
  -- "VCONCAT", "CONCATB","CONCAT","QUOTE","BRACKET","BRACE","PAREN",
  -- "OVERBAR","ROOT", "SEGMENT","SC","MATRIX","ZAG"
  -- note "SUB" and "SUPERSUB" are handled directly by formatHtml
  formatSpecial(op : S, args : L E, prec : I) : Tree S ==
    if debug then sayTeX$Lisp _
      "formatSpecial: " concat ["op=",op," args=",argsToString(args),_
        " prec=",string(prec)$S]
    arg : E
    prescript : Boolean := false
    op = "theMap" => tree("theMap(...)")
    op = "AGGLST" =>
      formatNary(",",args,prec)
    op = "AGGSET" =>
      formatNary(";",args,prec)
    op = "TAG" =>
      newNodes("",[formatHtml(first args,prec),tree("&#x02192;"),_
        formatHtml(second args,prec)])
      --RightArrow
    op = "SLASH" =>
      newNodes("",[formatHtml(first args, prec),tree("/"),_
        formatHtml(second args,prec)])
    op = "VCONCAT" =>
      newNodes("table",[newNode("td",formatHtml(u, minPrec))_
         for u in args]::L Tree S)
```

```
  op = "CONCATB" =>
    formatNary(" ",args,prec)
  op = "CONCAT" =>
    formatNary("",args,minPrec)
  op = "QUOTE" =>
    newNodes("",[tree("'"),formatHtml(first args, minPrec)])
  op = "BRACKET" =>
    newNodes("",[tree("["),formatHtml(first args, minPrec),tree("]")])
  op = "BRACE" =>
    newNodes("",[tree("{"),formatHtml(first args, minPrec),tree("}")])
  op = "PAREN" =>
    newNodes("",[tree("("),formatHtml(first args, minPrec),tree(")")])
  op = "OVERBAR" =>
    null args => tree("")
    buildOverbar(formatHtml(first args,minPrec))
  op = "ROOT" and #args < 1 => tree("")
  op = "ROOT" and #args = 1 => _
    buildRoot(formatHtml(first args, minPrec))
  op = "ROOT" and #args > 1 => _
    buildNRoot(formatHtml(first args, minPrec),_
      formatHtml(second args, minPrec))
  op = "SEGMENT" =>
    -- '..' indicates a range in a list for example
    tmp : Tree S := newNodes("",[formatHtml(first args, minPrec),_
      tree("..")])
    null rest args =>  tmp
    newNodes("",[tmp,formatHtml(first rest args, minPrec)])
  op = "SC" => formatSC(args,minPrec)
  op = "MATRIX" => formatMatrix rest args
  op = "ZAG" =>
    -- {{+}{3}{{ZAG}{1}{7}}{{ZAG}{1}{15}}{{ZAG}{1}{1}}{{ZAG}{1}{25}}_
    --      {{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
    -- to format continued fraction traditionally need to intercept
    -- it at the formatNary of the "+"
    newNodes("",[tree(" \zag{"),formatHtml(first args, minPrec),
      tree("}{"),
      formatHtml(first rest args,minPrec),tree("}")])
  tree("formatSpecial not implemented:"op)

formatSuperSub(expr : E, args : L E, opPrec : I) : Tree S ==
  -- This one produces ordinary derivatives with differential notation,
  -- it needs a little more work yet.
  -- first have to divine the semantics, add cases as needed
  if debug then sayTeX$Lisp _
    "formatSuperSub: " concat ["expr=",stringify expr," args=",_
      argsToString(args)," prec=",string(opPrec)$S]
  atomE : L E := atomize(expr)
  op : S := stringify first atomE
  op ~= "SUPERSUB" => tree("Mistake in formatSuperSub: no SUPERSUB")
  #args ~= 1 => tree("Mistake in SuperSub: #args <> 1")
```

```
  var : E := first args
  -- should be looking at something like {{SUPERSUB}{var}{ }{,,...,}}
  -- for example here's the second derivative of y w.r.t. x
  -- {{{SUPERSUB}{y}{ }{,,}}{x}}, expr is the first {} and args is the
  -- {x}
  funcS : S := stringify first rest atomE
  bvarS : S := stringify first args
  -- count the number of commas
  commaS : S := stringify first rest rest rest atomE
  commaTest : S := ","
  ndiffs : I := 0
  while position(commaTest,commaS,1) > 0 repeat
    ndiffs := ndiffs+1
    commaTest := commaTest","
  res:Tree S := newNodes("",_
    [tree("&#x02146;"string(ndiffs)""funcS"&#x02146;"),_
      formatHtml(first args,minPrec),tree(""string(ndiffs)"&#x02061;"),_
        formatHtml(first args,minPrec),tree(")")])
  res

-- build structure such as integral as a table
buildPlex3(main:Tree S,supsc:Tree S,op:Tree S,subsc:Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildPlex"
  ssup:Tree S := newNode("td id='plex'",supsc)
  sop:Tree S := newNode("td id='plex'",op)
  ssub:Tree S := newNode("td id='plex'",subsc)
  m:Tree S := newNode("td rowspan='3' id='plex'",main)
  rows:(List Tree S) := [newNodes("tr id='plex'",[ssup,m]),_
    newNode("tr id='plex'",sop),newNode("tr id='plex'",ssub)]
  newNodes("table border='0' id='plex'",rows)

-- build structure such as integral as a table
buildPlex2(main : Tree S,supsc : Tree S,op : Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildPlex"
  ssup:Tree S := newNode("td id='plex'",supsc)
  sop:Tree S := newNode("td id='plex'",op)
  m:Tree S := newNode("td rowspan='2' id='plex'",main)
  rows:(List Tree S) := [newNodes("tr id='plex'",[sop,m]),_
    newNode("tr id='plex'",ssup)]
  newNodes("table border='0' id='plex'",rows)

-- format an integral
-- args.1 = "NOTHING"
-- args.2 = bound variable
-- args.3 = body, thing being integrated
--
-- axiom replaces the bound variable with somthing like
-- %A and puts the original variable used
-- in the input command as a superscript on the integral sign.
formatIntSign(args : L E, opPrec : I) : Tree S ==
```

```
    -- the original OutputForm expression looks something like this:
    -- {{INTSIGN}{NOTHING or lower limit?}
    -- {bvar or upper limit?}{{*}{integrand}{{CONCAT}{d}{axiom var}}}}
    -- the args list passed here consists of the rest of this list, i.e.
    -- starting at the NOTHING or ...
    if debug then sayTeX$Lisp "formatIntSign: " concat [" args=",_
      argsToString(args)," prec=",string(opPrec)$S]
    (stringify first args) = "NOTHING" =>
      buildPlex2(formatHtml(args.3,opPrec),tree("&int;"),_
        formatHtml(args.2,opPrec)) -- could use &#x0222B; or &int;
    buildPlex3(formatHtml(first args,opPrec),formatHtml(args.3,opPrec),_
      tree("&int;"),formatHtml(args.2,opPrec))

  -- plex ops are "SIGMA","SIGMA2","PI","PI2","INTSIGN","INDEFINTEGRAL"
  -- expects 2 or 3 args
  formatPlex(op : S, args : L E, prec : I) : Tree S ==
    if debug then sayTeX$Lisp "formatPlex: " concat ["op=",op," args=",_
      argsToString(args)," prec=",string(prec)$S]
    checkarg:Boolean := false
    hold : S
    p : I := position(op,plexOps)
    p < 1 => error "unknown plex op"
    op = "INTSIGN" => formatIntSign(args,minPrec)
    opPrec := plexPrecs.p
    n : I := #args
    (n ~= 2) and (n ~= 3) => error "wrong number of arguments for plex"
    s : Tree S :=
      op = "SIGMA"   =>
        checkarg := true
        tree("&#x02211;")
      -- Sum
      op = "SIGMA2"   =>
        checkarg := true
        tree("&#x02211;")
      -- Sum
      op = "PI"      =>
        checkarg := true
        tree("&#x0220F;")
      -- Product
      op = "PI2"     =>
        checkarg := true
        tree("&#x0220F;")
      -- Product
      op = "INTSIGN" => tree("&#x0222B;")
      -- Integral, int
      op = "INDEFINTEGRAL" => tree("&#x0222B;")
      -- Integral, int
      tree("formatPlex: unexpected op:"op)
    -- if opPrec < prec then perhaps we should parenthesize?
    -- but we need to be careful we don't get loads of unnecessary
```

```
    -- brackets
    if n=2 then return buildPlex2(formatHtml(first args,minPrec),_
      formatHtml(args.2,minPrec),s)
    buildPlex3(formatHtml(first args,minPrec),formatHtml(args.2,minPrec),_
      s,formatHtml(args.3,minPrec))

  -- an example is: op=ROW arg={{ROW}{1}{2}}
  formatMatrixRow(op : S, arg : E, prec : I,y:I,h:I)  : L Tree S ==
    if debug then sayTeX$Lisp "formatMatrixRow: " concat ["op=",op,_
      " args=",stringify arg," prec=",string(prec)$S]
    ATOM(arg)$Lisp@Boolean => [_
      tree("formatMatrixRow does not contain row")]
    l : L E := (arg pretend L E)
    op : S := stringify first l
    args : L E := rest l
    --sayTeX$Lisp "formatMatrixRow op="op" args="argsToString(args)
    w:I := #args
    cells:(List Tree S) := empty()
    for x in 1..w repeat
      --sayTeX$Lisp "formatMatrixRow: x="string(x)$S" width="string(w)$S
      attrib:S := "td id='mat'"
      if x=1 then attrib := "td id='matl'"
      if x=w then attrib := "td id='matr'"
      if y=1 then attrib := "td id='matt'"
      if y=h then attrib := "td id='matb'"
      if x=1 and y=1 then attrib := "td id='matlt'"
      if x=1 and y=h then attrib := "td id='matlb'"
      if x=w and y=1  then attrib := "td id='matrt'"
      if x=w and y=h  then attrib := "td id='matrb'"
      cells := append(cells,[newNode(attrib,formatHtml(args.(x),prec))])
    cells

  -- an example is: op=MATRIX args={{ROW}{1}{2}}{{ROW}{3}{4}}
  formatMatrixContent(op : S, args : L E, prec : I)  : L Tree S ==
    if debug then sayTeX$Lisp "formatMatrixContent: " concat ["op=",op,_
      " args=",argsToString(args)," prec=",string(prec)$S]
    y:I := 0
    rows:(List Tree S) := [newNodes("tr id='mat'",_
      formatMatrixRow("ROW",e,prec,y:=y+1,#args)) for e in args]
    rows

  formatMatrix(args : L E) : Tree S ==
    -- format for args is [[ROW ...],[ROW ...],[ROW ...]]
    -- generate string for formatting columns (centered)
    if debug then sayTeX$Lisp "formatMatrix: " concat ["args=",_
      argsToString(args)]
    newNodes("table border='1' id='mat'",_
      formatMatrixContent("MATRIX",args,minPrec))

  -- output arguments in column table
```

```
buildColumnTable(elements : List Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildColumnTable"
  cells:(List Tree S) := [newNode("td id='col'",j) for j in elements]
  rows:(List Tree S) := [newNode("tr id='col'",i) for i in cells]
  newNodes("table border='0' id='col'",rows)

-- build superscript structure as either sup tag or
-- if it contains anything that won't go into a
-- sup tag then build it as a table
buildSuperscript(main : Tree S,super : Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildSuperscript"
  notTable?(super) => newNodes("",[main,newNode("sup",super)])
  m:Tree S := newNode("td rowspan='2' id='sup'",main)
  su:Tree S := newNode("td id='sup'",super)
  e:Tree S := newNode("td id='sup'",tree(" "))
  rows:(List Tree S) := [newNodes("tr id='sup'",[m,su]),_
    newNode("tr id='sup'",e)]
  newNodes("table border='0' id='sup'",rows)

-- build subscript structure as either sub tag or
-- if it contains anything that won't go into a
-- sub tag then build it as a table
buildSubscript(main : Tree S,subsc : Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildSubscript"
  notTable?(subsc) => newNodes("",[main,newNode("sub",subsc)])
  m:Tree S := newNode("td rowspan='2' id='sub'",main)
  su:Tree S := newNode("td id='sub'",subsc)
  e:Tree S := newNode("td id='sub'",tree(" "))
  rows:(List Tree S) := [newNodes("tr id='sub'",[m,e]),_
    newNode("tr id='sub'",su)]
  newNodes("table border='0' id='sub'",rows)

formatSub(expr : E, args : L E, opPrec : I) : Tree S ==
  -- format subscript
  -- this function expects expr to start with SUB
  -- it expects first args to be the operator or value that
  -- the subscript is applied to
  -- and the rest args to be the subscript
  if debug then sayTeX$Lisp "formatSub: " concat ["expr=",_
    stringify expr," args=",argsToString(args)," prec=",_
      string(opPrec)$S]
  atomE : L E := atomize(expr)
  if empty?(atomE) then
    if debug then sayTeX$Lisp "formatSub: expr=empty"
    return tree("formatSub: expr=empty")
  op : S := stringify first atomE
  op ~= "SUB" =>
    if debug then sayTeX$Lisp "formatSub: expr~=SUB"
    tree("formatSub: expr~=SUB")
  -- assume args.1 is the expression and args.2 is its subscript
```

```
  if #args < 2 then
    if debug then sayTeX$Lisp concat("formatSub: num args=",_
      string(#args)$String)$String
    return tree(concat("formatSub: num args=",_
      string(#args)$String)$String)
  if #args > 2 then
    if debug then sayTeX$Lisp concat("formatSub: num args=",_
      string(#args)$String)$String
    return buildSubscript(formatHtml(first args,opPrec),_
      newNodes("",[formatHtml(e,opPrec) for e in rest args]))
  buildSubscript(formatHtml(first args,opPrec),_
    formatHtml(args.2,opPrec))

formatFunction(op : Tree S, args : L E, prec : I) : Tree S ==
  if debug then sayTeX$Lisp "formatFunction: " concat ["args=",_
    argsToString(args)," prec=",string(prec)$S]
  newNodes("",[op,tree("("),formatNary(",",args,minPrec),tree(")")])

formatNullary(op : S) : Tree S ==
  if debug then sayTeX$Lisp "formatNullary: " concat ["op=",op]
  op = "NOTHING" => empty()$Tree(S)
  tree(op"()")

-- implement operation with single argument
-- an example is minus '-'
-- prec is precidence of operator, used to force brackets where
-- more tightly bound operation is next to less tightly bound operation
formatUnary(op : S, arg : E, prec : I) : Tree S ==
  if debug then sayTeX$Lisp "formatUnary: " concat ["op=",op," arg=",_
    stringify arg," prec=",string(prec)$S]
  p : I := position(op,unaryOps)
  p < 1 => error "unknown unary op"
  opPrec := unaryPrecs.p
  s : Tree S := newNodes("",[tree(op),formatHtml(arg,opPrec)])
  opPrec < prec => newNodes("",[tree("("),s,tree(")")])
  s

-- output division with numerator above the denominator
-- implemented as a table
buildOver(top : Tree S,bottom : Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildOver"
  topCell:Tree S := newNode("td",top)
  bottomCell:Tree S := newNode("td style='border-top-style:solid'",_
    bottom)
  rows:(List Tree S) := [newNode("tr id='col'",topCell),_
    newNode("tr id='col'",bottomCell)]
  newNodes("table border='0' id='col'",rows)

-- op may be: "|","^","/","OVER","+->"
-- note: "+" and "*" are n-ary ops
```

```
formatBinary(op : S, args : L E, prec : I) : Tree S ==
  if debug then sayTeX$Lisp "formatBinary: " concat ["op=",op,_
    " args=",argsToString(args)," prec=",string(prec)$S]
  p : I := position(op,binaryOps)
  p < 1 => error "unknown binary op"
  opPrec := binaryPrecs.p
  -- if base op is product or sum need to add parentheses
  if ATOM(first args)$Lisp@Boolean then
    opa:S := stringify first args
  else
    la : L E := (first args pretend L E)
    opa : S := stringify first la
  if (opa = "SIGMA" or opa = "SIGMA2" or opa = "PI" or opa = "PI2")_
    and op = "^" then
      s1 : Tree S := newNodes("",[tree("("),formatHtml(first args,_
        opPrec),tree(")")])
  else
    s1 : Tree S := formatHtml(first args, opPrec)
  s2 : Tree S := formatHtml(first rest args, opPrec)
  op = "|" => newNodes("",[s1,tree(op),s2])
  op = "^" => buildSuperscript(s1,s2)
  op = "/" => newNodes("",[s1,tree(op),s2])
  op = "OVER" => buildOver(s1,s2)
  op = "+->" => newNodes("",[s1,tree("|&mdash;&rsaquo;"),s2])
  newNodes("",[s1,tree(op),s2])

-- build a zag from a table with a right part and a
-- upper and lower left part
buildZag(top:Tree S,lowerLeft:Tree S,lowerRight:Tree S) : Tree S ==
  if debug then sayTeX$Lisp "buildZag"
  cellTop:Tree S := _
    newNode("td colspan='2' id='zag' style='border-bottom-style:solid'",_
     top)
  cellLowerLeft:Tree S := newNodes("td id='zag'",[lowerLeft,tree("+")])
  cellLowerRight:Tree S := newNode("td id='zag'",lowerRight)
  row1:Tree S := newNodes("tr id='zag'",[cellTop])
  row2:Tree S := newNodes("tr id='zag'",[cellLowerLeft,cellLowerRight])
  newNodes("table border='0' id='zag'",[row1,row2])

formatZag(args : L E,nestLevel:I)  : Tree S ==
  -- args will be a list of things like this {{ZAG}{1}{7}}, the ZAG
  -- must be there, the '1' and '7' could conceivably be more complex
  -- expressions
  --
  -- ex 1. continuedFraction(314159/100000)
  -- {{+}{3}{{ZAG}{1}{7}}{{ZAG}{1}{15}}{{ZAG}{1}{1}}{{ZAG}{1}{25}}
  -- {{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
  -- this is the preconditioned output form
  -- including "op", the args list would be the rest of this
  -- i.e op = '+' and args = {{3}{{ZAG}{1}{7}}{{ZAG}{1}{15}}
```

```
    -- {{ZAG}{1}{1}}{{ZAG}{1}{25}}{{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
    --
    -- ex 2. continuedFraction(14159/100000)
    -- this one doesn't have the leading integer
    -- {{+}{{ZAG}{1}{7}}{{ZAG}{1}{15}}{{ZAG}{1}{1}}{{ZAG}{1}{25}}
    -- {{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
    --
    -- ex 3. continuedFraction(3,repeating [1], repeating [3,6])
    -- {{+}{3}{{ZAG}{1}{3}}{{ZAG}{1}{6}}{{ZAG}{1}{3}}{{ZAG}{1}{6}}
    -- {{ZAG}{1}{3}}{{ZAG}{1}{6}}{{ZAG}{1}{3}}{{ZAG}{1}{6}}
    -- {{ZAG}{1}{3}}{{ZAG}{1}{6}}{...}}
    --
    -- In each of these examples the args list consists of the terms
    -- following the '+' op
    -- so the first arg could be a "ZAG" or something
    -- else, but the second arg looks like it has to be "ZAG", so maybe
    -- test for #args > 1 and args.2 contains "ZAG".
    -- Note that since the resulting tables are nested we need
    -- to handle the whole continued fraction at once, i.e. we can't
    -- just look for, e.g., {{ZAG}{1}{6}}
    --
    -- we will assume that the font starts at 16px and reduce it by 4
    -- <span style='font-size:16px'>outer zag</span>
    -- <span style='font-size:14px'>next zag</span>
    -- <span style='font-size:12px'>next zag</span>
    -- <span style='font-size:10px'>next zag</span>
    -- <span style='font-size:9px'>lowest zag</span>
    if debug then sayTeX$Lisp "formatZag: " concat ["args=",_
      argsToString(args)]
    tmpZag : L E := first args pretend L E
    fontAttrib : S :=
      nestLevel < 2 => "span style='font-size:16px'"
      nestLevel = 2 => "span style='font-size:14px'"
      nestLevel = 3 => "span style='font-size:12px'"
      nestLevel = 4 => "span style='font-size:10px'"
      "span style='font-size:9px'"
    -- may want to test that tmpZag contains 'ZAG'
    #args > 1 =>
      newNode(fontAttrib,buildZag(formatHtml(first rest tmpZag,minPrec),_
        formatHtml(first rest rest tmpZag,minPrec),_
          formatZag(rest args,nestLevel+1)))
    (first args = "..."):: E)@Boolean => tree("&#x2026;")
    op:S := stringify first args
    position("ZAG",op,1) > 0 =>
      newNode(fontAttrib,buildOver(formatHtml(first rest tmpZag,minPrec),_
        formatHtml(first rest rest tmpZag,minPrec)))
    tree("formatZag: Last argument in ZAG construct unknown operator: "op)

  -- returns true if this term starts with a minus '-' sign
  -- this is used so that we can suppress any plus '+' in front
```

```
-- of the - so we dont get terms like +-
neg?(arg : E) : Boolean ==
  if debug then sayTeX$Lisp "neg?: " concat ["arg=",argsToString([arg])]
  ATOM(arg)$Lisp@Boolean => false
  l : L E := (arg pretend L E)
  op : S := stringify first l
  op = "-" => true
  false

formatNary(op : S, args : L E, prec : I) : Tree S ==
  if debug then sayTeX$Lisp "formatNary: " concat ["op=",op," args=",_
    argsToString(args)," prec=",string(prec)$S]
  formatNaryNoGroup(op, args, prec)

-- possible op values are:
-- ",",";","*"," ","ROW","+","-"
-- an example is content of matrix which gives:
-- {{ROW}{1}{2}}{{ROW}{3}{4}}
-- or AGGLST which gives op=, args={{1}{2}}
--
-- need to:
-- format ZAG
-- check for +-
-- add brackets for sigma or pi or root ("SIGMA","SIGMA2","PI","PI2")
formatNaryNoGroup(op : S, args : L E, prec : I)  : Tree S ==
  if debug then sayTeX$Lisp "formatNaryNoGroup: " concat ["op=",op,_
    " args=",argsToString(args)," prec=",string(prec)$S]
  checkargs:Boolean := false
  null args => empty()$Tree(S)
  p : I := position(op,naryOps)
  p < 1 => error "unknown nary op"
  -- need to test for "ZAG" case and divert it here
  (#args > 1) and (position("ZAG",stringify first rest args,1) > 0) =>
       tmpS : S := stringify first args
       position("ZAG",tmpS,1) > 0 => formatZag(args,1)
       newNodes("",[formatHtml(first args,minPrec),tree("+"),_
        formatZag(rest args,1)])
  -- At least for the ops "*","+","-" we need to test to see if a
  -- sigma or pi is one of their arguments because we might need
  -- parentheses as indicated
  -- by the problem with summation(operator(f)(i),i=1..n)+1 versus
  -- summation(operator(f)(i)+1,i=1..n) having identical displays as of
  -- 2007-12-21
  l := empty()$Tree(S)
  opPrec := naryPrecs.p
  -- if checkargs is true check each arg except last one to see if it's
  -- a sigma or pi and if so add parentheses. Other op's may have to be
  -- checked for in future
  count:I := 1
  tags : (L Tree S)
```

```
    if opPrec < prec then tags := [tree("("),formatHtml(args.1,opPrec)]
    if opPrec >= prec then tags := [formatHtml(args.1,opPrec)]
    for a in rest args repeat
      if op ~= "+" or not neg?(a) then tags := append(tags,[tree(op)])
      tags := append(tags,[formatHtml(a,opPrec)])
    if opPrec < prec then tags := append(tags,[tree(")")])
    newNodes("",tags)

  -- expr is a tree structure
  -- prec is the precision of integers
  -- formatHtml returns a string for this node in the tree structure
  -- and calls recursivly to evaluate sub expressions
  formatHtml(arg : E,prec : I) : Tree S ==
    if debug then sayTeX$Lisp "formatHtml: " concat ["arg=",_
      argsToString([arg])," prec=",string(prec)$S]
    i,len : Integer
    intSplitLen : Integer := 20
    ATOM(arg)$Lisp@Boolean =>
      if debug then sayTeX$Lisp "formatHtml atom: " concat ["expr=",_
        stringify arg," prec=",string(prec)$S]
      str := stringify arg
      (i := position(str,specialStrings)) > 0 =>
        tree(specialStringsInHTML.i)
      tree(str)
    l : L E := (arg pretend L E)
    null l => tree(blank)
    op : S := stringify first l
    args : L E := rest l
    nargs : I := #args
    -- need to test here in case first l is SUPERSUB case and then
    -- pass first l and args to formatSuperSub.
    position("SUPERSUB",op,1) > 0 =>
      formatSuperSub(first l,args,minPrec)
    -- now test for SUB
    position("SUB",op,1) > 0 =>
      formatSub(first l,args,minPrec)
    -- special cases
    -- specialOps are:
    -- MATRIX, BRACKET, BRACE, CONCATB, VCONCAT
    -- AGGLST, CONCAT, OVERBAR, ROOT, SUB, TAG
    -- SUPERSUB, ZAG, AGGSET, SC, PAREN
    -- SEGMENT, QUOTE, theMap, SLASH
    member?(op, specialOps) => formatSpecial(op,args,prec)
    -- specialOps are:
    -- SIGMA, SIGMA2, PI, PI2, INTSIGN, INDEFINTEGRAL
    member?(op, plexOps)    => formatPlex(op,args,prec)
    -- nullary case: function with no aguments
    0 = nargs => formatNullary op
    -- unary case: function with one agument such as '-'
    (1 = nargs) and member?(op, unaryOps) =>
```

```
        formatUnary(op, first args, prec)
      -- binary case
      -- binary ops include special processing for | ^ / OVER and +->
      (2 = nargs) and member?(op, binaryOps) =>
        formatBinary(op, args, prec)
      -- nary case: including '+' and '*'
      member?(op,naryNGOps) => formatNaryNoGroup(op,args, prec)
      member?(op,naryOps) => formatNary(op,args, prec)

      op1 := formatHtml(first l,minPrec)
      formatFunction(op1,args,prec)
```

———-

— **HTMLFORM.dotabb** —

```
"HTMLFORM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HTMLFORM"]
"STRING" [color="#4488FF",href="bookvol10.2.pdf#nameddest=STRING"]
"HTMLFORM" -> "STRING"
```

———-

9.9 domain HDP HomogeneousDirectProduct

— **HomogeneousDirectProduct.input** —

```
)set break resume
)sys rm -f HomogeneousDirectProduct.output
)spool HomogeneousDirectProduct.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show HomogeneousDirectProduct
--R
--R HomogeneousDirectProduct(dim: NonNegativeInteger,S: OrderedAbelianMonoidSup)  is a domain constructor
--R Abbreviation for HomogeneousDirectProduct is HDP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for HDP
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if S has RING             1 : () -> % if S has MONOID
--R 0 : () -> % if S has CABMON           coerce : % -> Vector(S)
```

```
--R copy : % -> %                          directProduct : Vector(S) -> %
--R ?.? : (%,Integer) -> S                 elt : (%,Integer,S) -> S
--R empty : () -> %                        empty? : % -> Boolean
--R entries : % -> List(S)                 eq? : (%,%) -> Boolean
--R index? : (Integer,%) -> Boolean        indices : % -> List(Integer)
--R map : ((S -> S),%) -> %                qelt : (%,Integer) -> S
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (PositiveInteger,%) -> % if S has ABELSG
--R ?*? : (NonNegativeInteger,%) -> % if S has CABMON
--R ?*? : (S,%) -> % if S has RING
--R ?*? : (%,S) -> % if S has RING
--R ?*? : (%,%) -> % if S has MONOID
--R ?*? : (Integer,%) -> % if S has RING
--R ?**? : (%,PositiveInteger) -> % if S has MONOID
--R ?**? : (%,NonNegativeInteger) -> % if S has MONOID
--R ?+? : (%,%) -> % if S has ABELSG
--R ?-? : (%,%) -> % if S has RING
--R ?/? : (%,S) -> % if S has FIELD
--R ?<? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?<=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R D : (%,(S -> S)) -> % if S has RING
--R D : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R D : % -> % if S has DIFRING and S has RING
--R ?^? : (%,PositiveInteger) -> % if S has MONOID
--R ?^? : (%,NonNegativeInteger) -> % if S has MONOID
--R abs : % -> % if S has ORDRING
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R characteristic : () -> NonNegativeInteger if S has RING
--R coerce : S -> % if S has SETCAT
--R coerce : Fraction(Integer) -> % if S has RETRACT(FRAC(INT)) and S has SETCAT
--R coerce : Integer -> % if S has RETRACT(INT) and S has SETCAT or S has RING
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R differentiate : (%,(S -> S)) -> % if S has RING
--R differentiate : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
```

```
--R differentiate : % -> % if S has DIFRING and S has RING
--R dimension : () -> CardinalNumber if S has FIELD
--R dot : (%,%) -> S if S has RING
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R first : % -> S if Integer has ORDSET
--R hash : % -> SingleInteger if S has SETCAT
--R index : PositiveInteger -> % if S has FINITE
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R lookup : % -> PositiveInteger if S has FINITE
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has OAMONS or S has ORDRING
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R min : (%,%) -> % if S has OAMONS or S has ORDRING
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R negative? : % -> Boolean if S has ORDRING
--R one? : % -> Boolean if S has MONOID
--R parts : % -> List(S) if $ has finiteAggregate
--R positive? : % -> Boolean if S has ORDRING
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R random : () -> % if S has FINITE
--R recip : % -> Union(%,"failed") if S has MONOID
--R reducedSystem : Matrix(%) -> Matrix(S) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(S),vec: Vector(S)) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if S has LINE
--R reducedSystem : Matrix(%) -> Matrix(Integer) if S has LINEXP(INT) and S has RING
--R retract : % -> S if S has SETCAT
--R retract : % -> Fraction(Integer) if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retract : % -> Integer if S has RETRACT(INT) and S has SETCAT
--R retractIfCan : % -> Union(S,"failed") if S has SETCAT
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retractIfCan : % -> Union(Integer,"failed") if S has RETRACT(INT) and S has SETCAT
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R sign : % -> Integer if S has ORDRING
--R size : () -> NonNegativeInteger if S has FINITE
--R size? : (%,NonNegativeInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed") if S has CABMON
--R sup : (%,%) -> % if S has OAMONS
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R unitVector : PositiveInteger -> % if S has RING
--R zero? : % -> Boolean if S has CABMON
```

```
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **HomogeneousDirectProduct.help** —

```
=====================================================================
HomogeneousDirectProduct examples
=====================================================================

See Also:
o )show HomogeneousDirectProduct
```

———-

9.9.1 HomogeneousDirectProduct (HDP)



See

⇒ “OrderedDirectProduct” (ODP) 16.13.1 on page 1783
⇒ “SplitHomogeneousDirectProduct” (SHDP) 20.23.1 on page 2476

Exports:

0	1	abs	any?	characteristic
coerce	copy	count	D	differentiate
dimension	directProduct	dot	elt	empty
empty?	entries	entry?	eq?	eval
every?	fill!	first	hash	index
index?	indices	latex	less?	lookup
map	map!	max	maxIndex	member?
members	min	minIndex	more?	negative?
one?	parts	positive?	qelt	qsetelt!
random	recip	reducedSystem	retract	retractIfCan
sample	setelt	sign	size	size?
subtractIfCan	sup	swap!	unitVector	zero?
#?	?*?	?**?	?+?	?-?
?/?	?<?	?<=?	?=?	?>?
?>=?	?^?	?~=?	-?	?.?

— domain HDP HomogeneousDirectProduct —

```
)abbrev domain HDP HomogeneousDirectProduct
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors: Vector, DirectProduct
++ Also See: OrderedDirectProduct, SplitHomogeneousDirectproduct
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type represents the finite direct or cartesian product of an
++ underlying ordered component type. The vectors are ordered first
++ by the sum of their components, and then refined using a reverse
++ lexicographic ordering. This type is a suitable third argument for
++ \spadtype{GeneralDistributedMultivariatePolynomial}.

HomogeneousDirectProduct(dim,S) : T == C where
   dim : NonNegativeInteger
   S         : OrderedAbelianMonoidSup

   T == DirectProductCategory(dim,S)
   C == DirectProduct(dim,S) add
        Rep:=Vector(S)
        v1:% < v2:% ==
 -- reverse lexicographical ordering
          n1:S:=0
          n2:S:=0
          for i in 1..dim repeat
            n1:= n1+qelt(v1,i)
```

```
          n2:=n2+qelt(v2,i)
        n1<n2 => true
        n2<n1 => false
        for i in reverse(1..dim) repeat
          if qelt(v2,i) < qelt(v1,i) then return true
          if qelt(v1,i) < qelt(v2,i) then return false
        false
```

———-

— HDP.dotabb —

```
"HDP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HDP"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"HDP" -> "DIRPCAT"
```

———-

9.10 domain HDMP HomogeneousDistributedMultivariatePolynomial

— HomogeneousDistributedMultivariatePolynomial.input —

```
)set break resume
)sys rm -f HomogeneousDistributedMultivariatePolynomial.output
)spool HomogeneousDistributedMultivariatePolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 10
(d1,d2,d3) : DMP([z,y,x],FRAC INT)
--R
--R                                                                Type: Void
--E 1

--S 2 of 10
d1 := -4*z + 4*y**2*x + 16*x**2 + 1
--R
--R
--R                 2       2
--R   (2)  - 4z + 4y x + 16x  + 1
--R          Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 2
```

```
--S 3 of 10
d2 := 2*z*y**2 + 4*x + 1
--R
--R
--R            2
--R   (3)  2z y  + 4x + 1
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 3

--S 4 of 10
d3 := 2*z*x**2 - 2*y**2 - x
--R
--R
--R            2     2
--R   (4)  2z x  - 2y  - x
--R           Type: DistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 4

--S 5 of 10
groebner [d1,d2,d3]
--R
--R
--R   (5)
--R        1568  6   1264  5    6   4   182  3   2047  2    103      2857
--R   [z - ---- x  - ---- x  + --- x  + --- x  - ---- x  - ---- x - -----,
--R        2745       305      305      549       610      2745     10980
--R     2    112  6    84  5   1264  4    13  3    84  2   1772       2
--R    y  + ---- x  - --- x  - ---- x  - --- x  + --- x  + ---- x + ----,
--R         2745      305       305      549      305      2745     2745
--R     7   29  6   17  4   11  3    1  2   15     1
--R    x  + -- x  - -- x  - -- x  + -- x  + -- x + -]
--R          4      16       8      32      16     4
--R     Type: List(DistributedMultivariatePolynomial([z,y,x],Fraction(Integer)))
--E 5

--S 6 of 10
(n1,n2,n3) : HDMP([z,y,x],FRAC INT)
--R
--R                                                                  Type: Void
--E 6

--S 7 of 10
n1 := d1
--R
--R
--R          2       2
--R   (7)  4y x + 16x  - 4z + 1
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 7
```

```
--S 8 of 10
n2 := d2
--R
--R
--R            2
--R   (8)  2z y  + 4x + 1
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 8

--S 9 of 10
n3 := d3
--R
--R
--R            2     2
--R   (9)  2z x  - 2y  - x
--RType: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer))
--E 9

--S 10 of 10
groebner [n1,n2,n3]
--R
--R
--R   (10)
--R     4     3   3  2   1     1   4   29  3   1  2   7        9     1
--R   [y  + 2x  - - x  + - z - -, x  + -- x  - - y  - - z x - -- x - -,
--R              2      2     8        4      8      4       16     4
--R       2        1   2      2       1     2    2   1
--R    z y  + 2x + -, y x + 4x  - z + -, z x  - y  - - x,
--R               2                  4             2
--R     2     2     2   1     3
--R    z  - 4y  + 2x  - - z - - x]
--R                    4     2
--RType: List(HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction(Integer)))
--E 10
)spool
)lisp (bye)
```

———-

— HomogeneousDistributedMultivariatePolynomial.help —

```
====================================================================
MultivariatePolynomial
DistributedMultivariatePolynomial
HomogeneousDistributedMultivariatePolynomial
GeneralDistributedMultivariatePolynomial
====================================================================
```

```
DistributedMultivariatePolynomial which is abbreviated as DMP and
HomogeneousDistributedMultivariatePolynomial, which is abbreviated
as HDMP, are very similar to MultivariatePolynomial except that
they are represented and displayed in a non-recursive manner.

  (d1,d2,d3) : DMP([z,y,x],FRAC INT)
                      Type: Void

The constructor DMP orders its monomials lexicographically while
HDMP orders them by total order refined by reverse lexicographic
order.

  d1 := -4*z + 4*y**2*x + 16*x**2 + 1
            2       2
   - 4z + 4y x + 16x  + 1
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  d2 := 2*z*y**2 + 4*x + 1
       2
   2z y  + 4x + 1
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  d3 := 2*z*x**2 - 2*y**2 - x
       2     2
   2z x  - 2y  - x
            Type: DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

These constructors are mostly used in Groebner basis calculations.

  groebner [d1,d2,d3]
        1568  6   1264  5    6   4   182  3   2047  2    103      2857
   [z - ---- x  - ---- x  + --- x  + --- x  - ---- x  - ---- x - -----,
        2745       305      305      549       610      2745     10980
     2    112  6    84  5   1264  4    13  3    84  2   1772       2
    y  + ---- x  - --- x  - ---- x  - --- x  + --- x  + ---- x + ----,
         2745      305       305      549      305      2745     2745
     7   29  6   17  4   11  3    1  2   15     1
    x  + -- x  - -- x  - -- x  + -- x  + -- x + -]
          4      16       8      32      16     4
       Type: List DistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  (n1,n2,n3) : HDMP([z,y,x],FRAC INT)
                      Type: Void

  n1 := d1
     2       2
   4y x + 16x  - 4z + 1
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)

  n2 := d2
```

```
      2
  2z y  + 4x + 1
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)

 n3 := d3
      2     2
  2z x  - 2y  - x
 Type: HomogeneousDistributedMultivariatePolynomial([z,y,x],Fraction Integer)
```


Note that we get a different Groebner basis when we use the HDMP polynomials, as expected.

```
  groebner [n1,n2,n3]
     4     3   3  2   1     1   4   29  3   1  2   7        9     1
   [y  + 2x  - - x  + - z - -, x  + -- x  - - y  - - z x - -- x - -,
              2      2     8        4      8      4       16     4
      2        1   2      2       1     2    2   1
    z y  + 2x + -, y x + 4x  - z + -, z x  - y  - - x,
               2                  4             2
     2     2     2   1     3
    z  - 4y  + 2x  - - z - - x]
                   4     2
      Type: List HomogeneousDistributedMultivariatePolynomial([z,y,x],
                                                               Fraction Integer)
```

GeneralDistributedMultivariatePolynomial is somewhat more flexible in the sense that as well as accepting a list of variables to specify the variable ordering, it also takes a predicate on exponent vectors to specify the term ordering. With this polynomial type the user can experiment with the effect of using completely arbitrary term orderings. This flexibility is mostly important for algorithms such as Groebner basis calculations which can be very sensitive to term ordering.

See Also:
o)help Polynomial
o)help UnivariatePolynomial
o)help MultivariatePolynomial
o)help DistributedMultivariatePolynomial
o)help GeneralDistributedMultivariatePolynomial
o)show HomogeneousDistributedMultivariatePolynomial

9.10.1 HomogeneousDistributedMultivariatePolynomial (HDMP)



See

⇒ "GeneralDistributedMultivariatePolynomial" (GDMP) 8.1.1 on page 1022
⇒ "DistributedMultivariatePolynomial" (DMP) 5.13.1 on page 559

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	convert
D	degree	differentiate
discriminant	eval	exquo
factor	factorPolynomial	factorSquareFreePolynomial
gcd	gcdPolynomial	ground
ground?	hash	isExpt
isPlus	isTimes	latex
lcm	leadingCoefficient	leadingMonomial
mainVariable	map	mapExponents
max	min	minimumDegree
monicDivide	monomial	monomial?
monomials	multivariate	numberOfMonomials
one?	patternMatch	pomopo!
prime?	primitiveMonomials	primitivePart
recip	reducedSystem	reductum
reorder	resultant	retract
retractIfCan	sample	solveLinearPolynomialEquation
squareFree	squareFreePart	squareFreePolynomial
subtractIfCan	totalDegree	unit?
unitCanonical	unitNormal	univariate
variables	zero?	?*?
?**?	?+?	?-?
-?	?=?	?^?
?~=?	?/?	?<?
?<=?	?>?	?>=?
?^?		

— domain HDMP HomogeneousDistributedMultivariatePolynomial —

```
)abbrev domain HDMP HomogeneousDistributedMultivariatePolynomial
++ Author: Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, degree, eval, coefficient, monomial, differentiate,
++ resultant, gcd, leadingCoefficient
++ Related Constructors: DistributedMultivariatePolynomial,
++ GeneralDistributedMultivariatePolynomial
++ Also See: Polynomial
++ AMS Classifications:
++ Keywords: polynomial, multivariate, distributed
++ References:
++ Description:
```

```
++ This type supports distributed multivariate polynomials
++ whose variables are from a user specified list of symbols.
++ The coefficient ring may be non commutative,
++ but the variables are assumed to commute.
++ The term ordering is total degree ordering refined by reverse
++ lexicographic ordering with respect to the position that the variables
++ appear in the list of variables parameter.

HomogeneousDistributedMultivariatePolynomial(vl,R): public == private where
  vl : List Symbol
  R  : Ring
  E   ==> HomogeneousDirectProduct(#vl,NonNegativeInteger)
  OV  ==> OrderedVariableList(vl)
  public == PolynomialCategory(R,E,OV) with
      reorder: (%,List Integer) -> %
        ++ reorder(p, perm) applies the permutation perm to the variables
        ++ in a polynomial and returns the new correctly ordered polynomial
  private ==
    GeneralDistributedMultivariatePolynomial(vl,R,E)
```

———-

— HDMP.dotabb —

```
"HDMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HDMP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"HDMP" -> "PFECAT"
"HDMP" -> "DIRPCAT"
```

———-

9.11 domain HELLFDIV HyperellipticFiniteDivisor

— HyperellipticFiniteDivisor.input —

```
)set break resume
)sys rm -f HyperellipticFiniteDivisor.output
)spool HyperellipticFiniteDivisor.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show HyperellipticFiniteDivisor
--R
--R HyperellipticFiniteDivisor(F: Field,UP: UnivariatePolynomialCategory(F),UPUP: UnivariatePoly
--R Abbreviation for HyperellipticFiniteDivisor is HELLFDIV
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for HELLFDIV
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           coerce : % -> OutputForm
--R divisor : (R,UP,UP,UP,F) -> %         divisor : (F,F,Integer) -> %
--R divisor : (F,F) -> %                  divisor : R -> %
--R hash : % -> SingleInteger             latex : % -> String
--R principal? : % -> Boolean             reduce : % -> %
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R decompose : % -> Record(id: FractionalIdeal(UP,Fraction(UP),UPUP,R),principalPart: R)
--R divisor : FractionalIdeal(UP,Fraction(UP),UPUP,R) -> %
--R generator : % -> Union(R,"failed")
--R ideal : % -> FractionalIdeal(UP,Fraction(UP),UPUP,R)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— HyperellipticFiniteDivisor.help —

```
=====================================================================
HyperellipticFiniteDivisor examples
=====================================================================

See Also:
o )show HyperellipticFiniteDivisor
```

———-

9.11.1 HyperellipticFiniteDivisor (HELLFDIV)



See

⇒ "FractionalIdeal" (FRIDEAL) 7.25.1 on page 965
⇒ "FramedModule" (FRMOD) 7.26.1 on page 970
⇒ "FiniteDivisor" (FDIV) 7.4.1 on page 783

Exports:

0	coerce	decompose	divisor	hash
ideal	generator	latex	principal?	reduce
sample	subtractIfCan	zero?	?~=?	?*?
?+?	?-?	-?	?=?	

— domain HELLFDIV HyperellipticFiniteDivisor —

```
)abbrev domain HELLFDIV HyperellipticFiniteDivisor
++ Author: Manuel Bronstein
++ Date Created: 19 May 1993
++ Date Last Updated: 20 July 1998
++ Keywords: divisor, algebraic, curve.
++ Description:
++ This domains implements finite rational divisors on an hyperelliptic curve,
++ that is finite formal sums SUM(n * P) where the n's are integers and the
++ P's are finite rational points on the curve.
++ The equation of the curve must be  y^2 = f(x) and f must have odd degree.

HyperellipticFiniteDivisor(F, UP, UPUP, R): Exports == Implementation where
  F   : Field
  UP  : UnivariatePolynomialCategory F
  UPUP: UnivariatePolynomialCategory Fraction UP
  R   : FunctionFieldCategory(F, UP, UPUP)

  O   ==> OutputForm
  Z   ==> Integer
  RF  ==> Fraction UP
  ID  ==> FractionalIdeal(UP, RF, UPUP, R)
  ERR ==> error "divisor: incomplete implementation for hyperelliptic curves"
```

```
  Exports ==> FiniteDivisorCategory(F, UP, UPUP, R)

  Implementation ==> add
    if (uhyper:Union(UP, "failed") := hyperelliptic()$R) case "failed" then
              error "HyperellipticFiniteDivisor: curve must be hyperelliptic"

-- we use the semi-reduced representation from D.Cantor, "Computing in the
-- Jacobian of a HyperellipticCurve", Mathematics of Computation, vol 48,
-- no.177, January 1987, 95-101.
-- The representation [a,b,f] for D means D = [a,b] + div(f)
-- and [a,b] is a semi-reduced representative on the Jacobian
    Rep := Record(center:UP, polyPart:UP, principalPart:R, reduced?:Boolean)

    hyper:UP := uhyper::UP
    gen:Z    := ((degree(hyper)::Z - 1) exquo 2)::Z     -- genus of the curve
    dvd:O    := "div"::Symbol::O
    zer:O    := 0::Z::O

    makeDivisor  : (UP, UP, R) -> %
    intReduc     : (R, UP) -> R
    princ?       : % -> Boolean
    polyIfCan    : R -> Union(UP, "failed")
    redpolyIfCan : (R, UP) -> Union(UP, "failed")
    intReduce    : (R, UP) -> R
    mkIdeal      : (UP, UP) -> ID
    reducedTimes : (Z, UP, UP) -> %
    reducedDouble: (UP, UP) -> %

    0                    == divisor(1$R)
    divisor(g:R)         == [1, 0, g, true]
    makeDivisor(a, b, g) == [a, b, g, false]
--    princ? d             == one?(d.center) and zero?(d.polyPart)
    princ? d             == (d.center = 1) and zero?(d.polyPart)
    ideal d     == ideal([d.principalPart]) * mkIdeal(d.center, d.polyPart)
    decompose d == [ideal makeDivisor(d.center, d.polyPart, 1),d.principalPart]
    mkIdeal(a, b) == ideal [a::RF::R, reduce(monomial(1, 1)$UPUP-b::RF::UPUP)]

-- keep the sum reduced if d1 and d2 are both reduced at the start
    d1 + d2 ==
      a1  := d1.center;   a2 := d2.center
      b1  := d1.polyPart; b2 := d2.polyPart
      rec := principalIdeal [a1, a2, b1 + b2]
      d   := rec.generator
      h   := rec.coef              -- d = h1 a1 + h2 a2 + h3(b1 + b2)
      a   := ((a1 * a2) exquo d**2)::UP
      b:UP:= first(h) * a1 * b2
      b   := b + second(h) * a2 * b1
      b   := b + third(h) * (b1*b2 + hyper)
      b   := (b exquo d)::UP rem a
      dd  := makeDivisor(a, b, d::RF * d1.principalPart * d2.principalPart)
```

```
      d1.reduced? and d2.reduced? => reduce dd
      dd

-- if is cheaper to keep on reducing as we exponentiate if d is already reduced
    n:Z * d:% ==
      zero? n => 0
      n < 0 => (-n) * (-d)
      divisor(d.principalPart ** n) + divisor(mkIdeal(d.center,d.polyPart)**n)

    divisor(i:ID) ==
--      one?(n := #(v := basis minimize i)) => divisor v minIndex v
      (n := #(v := basis minimize i)) = 1 => divisor v minIndex v
      n ^= 2 => ERR
      a := v minIndex v
      h := v maxIndex v
      (u := polyIfCan a) case UP =>
        (w := redpolyIfCan(h, u::UP)) case UP => makeDivisor(u::UP, w::UP, 1)
        ERR
      (u := polyIfCan h) case UP =>
        (w := redpolyIfCan(a, u::UP)) case UP => makeDivisor(u::UP, w::UP, 1)
        ERR
      ERR

    polyIfCan a ==
      (u := retractIfCan(a)@Union(RF, "failed")) case "failed" => "failed"
      (v := retractIfCan(u::RF)@Union(UP, "failed")) case "failed" => "failed"
      v::UP

    redpolyIfCan(h, a) ==
      degree(p := lift h) ^= 1 => "failed"
      q := - coefficient(p, 0) / coefficient(p, 1)
      rec := extendedEuclidean(denom q, a)
      not ground?(rec.generator) => "failed"
      ((numer(q) * rec.coef1) exquo rec.generator)::UP rem a

    coerce(d:%):O ==
      r := bracket [d.center::O, d.polyPart::O]
      g := prefix(dvd, [d.principalPart::O])
--      z := one?(d.principalPart)
      z := (d.principalPart = 1)
      princ? d => (z => zer; g)
      z => r
      r + g

    reduce d ==
      d.reduced? => d
      degree(a := d.center) <= gen => (d.reduced? := true; d)
      b  := d.polyPart
      a0 := ((hyper - b**2) exquo a)::UP
      b0 := (-b) rem a0
```

```
      g  := d.principalPart * reduce(b::RF::UPUP-monomial(1,1)$UPUP)/a0::RF::R
      reduce makeDivisor(a0, b0, g)

    generator d ==
      d := reduce d
      princ? d => d.principalPart
      "failed"

    - d ==
      a := d.center
      makeDivisor(a, - d.polyPart, inv(a::RF * d.principalPart))

    d1 = d2 ==
      d1 := reduce d1
      d2 := reduce d2
      d1.center = d2.center and d1.polyPart = d2.polyPart
        and d1.principalPart = d2.principalPart

    divisor(a, b) ==
      x := monomial(1, 1)$UP
      not ground? gcd(d := x - a::UP, retract(discriminant())@UP) =>
                                  error "divisor: point is singular"
      makeDivisor(d, b::UP, 1)

    intReduce(h, b) ==
      v := integralCoordinates(h).num
      integralRepresents(
                [qelt(v, i) rem b for i in minIndex v .. maxIndex v], 1)

-- with hyperelliptic curves, it is cheaper to keep divisors in reduced form
    divisor(h, a, dp, g, r) ==
      h  := h - (r * dp)::RF::R
      a  := gcd(a, retract(norm h)@UP)
      h  := intReduce(h, a)
      if not ground? gcd(g, a) then h := intReduce(h ** rank(), a)
      hh := lift h
      b  := - coefficient(hh, 0) / coefficient(hh, 1)
      rec := extendedEuclidean(denom b, a)
      not ground?(rec.generator) => ERR
      bb := ((numer(b) * rec.coef1) exquo rec.generator)::UP rem a
      reduce makeDivisor(a, bb, 1)
```

———-

— HELLFDIV.dotabb —

```
"HELLFDIV" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HELLFDIV"]
"FDIVCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FDIVCAT"]
```

```
"HELLFDIV" -> "FDIVCAT"
```

———————-

Chapter 10

Chapter I

10.1 domain ICP InfClsPt

— InfClsPt.input —

```
)set break resume
)sys rm -f InfClsPt.output
)spool InfClsPt.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InfClsPt
--R InfClsPt(K: Field,symb: List Symbol,BLMET: BlowUpMethodCategory)  is a domain constructor
--R Abbreviation for InfClsPt is ICP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ICP
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               actualExtensionV : % -> K
--R chartV : % -> BLMET                  coerce : % -> OutputForm
--R degree : % -> PositiveInteger        excpDivV : % -> Divisor Places K
--R fullOut : % -> OutputForm            fullOutput : () -> Boolean
--R fullOutput : Boolean -> Boolean      hash : % -> SingleInteger
--R latex : % -> String                  localPointV : % -> AffinePlane K
--R multV : % -> NonNegativeInteger      pointV : % -> ProjectivePlane K
--R setchart! : (%,BLMET) -> BLMET       symbNameV : % -> Symbol
--R ?~=? : (%,%) -> Boolean
--R create : (ProjectivePlane K,DistributedMultivariatePolynomial(symb,K)) -> %
--R create : (ProjectivePlane K,DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],K),AffinePlane K
--R curveV : % -> DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],K)
```

```
--R localParamV : % -> List NeitherSparseOrDensePowerSeries K
--R setcurve! : (%,DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],K)) -> Distribute
--R setexcpDiv! : (%,Divisor Places K) -> Divisor Places K
--R setlocalParam! : (%,List NeitherSparseOrDensePowerSeries K) -> List NeitherSparseOrDensePowe
--R setlocalPoint! : (%,AffinePlane K) -> AffinePlane K
--R setmult! : (%,NonNegativeInteger) -> NonNegativeInteger
--R setpoint! : (%,ProjectivePlane K) -> ProjectivePlane K
--R setsubmult! : (%,NonNegativeInteger) -> NonNegativeInteger
--R setsymbName! : (%,Symbol) -> Symbol
--R subMultV : % -> NonNegativeInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— InfClsPt.help —

```
=====================================================================
InfClsPt examples
=====================================================================

See Also:
o )show InfClsPt
```

———-

10.1.1 InfClsPt (ICP)



Exports:

?=?	?~=?	actualExtensionV
chartV	coerce	create
curveV	degree	excpDivV
fullOut	fullOutput	hash
latex	localParamV	localPointV
multV	pointV	setchart!
setcurve!	setexcpDiv!	setlocalParam!
setlocalPoint!	setmult!	setpoint!
setsubmult!	setsymbName!	subMultV
symbNameV		

— domain ICP InfClsPt —

```
)abbrev domain ICP InfClsPt
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain is part of the PAFF package
InfClsPt(K,symb,BLMET):Exports == Implementation where
  K:Field
  symb: List Symbol
  BLMET : BlowUpMethodCategory

  E         ==> DirectProduct(#symb,NonNegativeInteger)
  PolyRing  ==> DistributedMultivariatePolynomial(symb,K)
  ProjPt    ==> ProjectivePlane(K)
  PCS       ==> NeitherSparseOrDensePowerSeries(K)
  Plc       ==> Places(K)
  DIVISOR   ==> Divisor(Plc)

  Exports == InfinitlyClosePointCategory(K,symb,PolyRing,E,ProjPt,_
                                         PCS,Plc,DIVISOR,BLMET) with
    fullOut: % -> OutputForm
      ++ fullOut(tr) yields a full output of tr (see function fullOutput).

    fullOutput: Boolean -> Boolean
      ++ fullOutput(b) sets a flag such that when true, a coerce to
      ++ OutputForm yields the full output of tr, otherwise encode(tr) is
      ++ output (see encode function). The default is false.

    fullOutput: () -> Boolean
      ++ fullOutput returns the value of the flag set by fullOutput(b).

  Implementation == InfinitlyClosePoint(K,symb,PolyRing,E,ProjPt,_
                                        PCS,Plc,DIVISOR,BLMET)
```

———-

— **ICP.dotabb** —

```
"ICP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ICP"]
"INFCLSPT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INFCLSPT"]
"PLACES" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLACES"]
"ICP" -> "INFCLSPT"
"ICP" -> "PLACES"
```

———-

10.2 domain ICARD IndexCard

— **IndexCard.input** —

```
)set break resume
)sys rm -f IndexCard.output
)spool IndexCard.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexCard
--R IndexCard  is a domain constructor
--R Abbreviation for IndexCard is ICARD
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ICARD
--R
--R------------------------------ Operations ------------------------------
--R ?<? : (%,%) -> Boolean               ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean               ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean              coerce : String -> %
--R coerce : % -> OutputForm             display : % -> Void
--R ?.? : (%,Symbol) -> String           fullDisplay : % -> Void
--R hash : % -> SingleInteger            latex : % -> String
--R max : (%,%) -> %                     min : (%,%) -> %
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexCard.help** —

```
==========================================================================
IndexCard examples
==========================================================================

See Also:
o )show IndexCard
```

———-

10.2.1 IndexCard (ICARD)



See

⇒ “DataList” (DLIST) 5.2.1 on page 447
⇒ “Database” (DBASE) 5.1.1 on page 442
⇒ “QueryEquation” (QEQUAT) 18.4.1 on page 2135

Exports:

coerce	display	fullDisplay	hash	latex
max	min	?~=?	?<?	?<=?
?=?	?>?	?>=?	?.?	

— **domain ICARD IndexCard** —

```
)abbrev domain ICARD IndexCard
++ Author: Mark Botch
++ Description:
++ This domain implements a container of information about the AXIOM library

IndexCard() : Exports == Implementation where
  Exports == OrderedSet with
    elt: (%,Symbol) -> String
      ++ elt(ic,s) selects a particular field from \axiom{ic}.  Valid fields
```

```
    ++ are \axiom{name, nargs, exposed, type, abbreviation, kind, origin,
    ++ params, condition, doc}.
  display: % -> Void
    ++ display(ic) prints a summary of information contained in \axiom{ic}.
  fullDisplay: % -> Void
    ++ fullDisplay(ic) prints all of the information contained in \axiom{ic}.
  coerce: String -> %
    ++ coerce(s) converts \axiom{s} into an \axiom{IndexCard}.  Warning: if
    ++ \axiom{s} is not of the right format then an error will occur
Implementation == add
  x<y==(x pretend String) < (y pretend String)
  x=y==(x pretend String) = (y pretend String)
  display(x) ==
    name : OutputForm := dbName(x)$Lisp
    type : OutputForm := dbPart(x,4,1$Lisp)$Lisp
    output(hconcat(name,hconcat(" : ",type)))$OutputPackage
  fullDisplay(x) ==
    name : OutputForm := dbName(x)$Lisp
    type : OutputForm := dbPart(x,4,1$Lisp)$Lisp
    origin:OutputForm :=
        hconcat(alqlGetOrigin(x$Lisp)$Lisp,alqlGetParams(x$Lisp)$Lisp)
    fromPart : OutputForm := hconcat(" from ",origin)
    condition : String := dbPart(x,6,1$Lisp)$Lisp
    ifPart : OutputForm :=
      condition = "" => empty()
      hconcat(" if ",condition::OutputForm)
    exposed? : String := SUBSTRING(dbPart(x,3,1)$Lisp,0,1)$Lisp
    exposedPart : OutputForm :=
      exposed? = "n" => " (unexposed)"
      empty()
    firstPart := hconcat(name,hconcat(" : ",type))
    secondPart := hconcat(fromPart,hconcat(ifPart,exposedPart))
    output(hconcat(firstPart,secondPart))$OutputPackage
  coerce(s:String): % == (s pretend %)
  coerce(x): OutputForm == (x pretend String)::OutputForm
  elt(x,sel) ==
    s := PNAME(sel)$Lisp pretend String
    s = "name" => dbName(x)$Lisp
    s = "nargs" => dbPart(x,2,1$Lisp)$Lisp
    s = "exposed" => SUBSTRING(dbPart(x,3,1)$Lisp,0,1)$Lisp
    s = "type" => dbPart(x,4,1$Lisp)$Lisp
    s = "abbreviation" => dbPart(x,5,1$Lisp)$Lisp
    s = "kind" => alqlGetKindString(x)$Lisp
    s = "origin" => alqlGetOrigin(x)$Lisp
    s = "params" => alqlGetParams(x)$Lisp
    s = "condition" => dbPart(x,6,1$Lisp)$Lisp
    s = "doc" => dbComments(x)$Lisp
    error "unknown selector"
```

———-

— **ICARD.dotabb** —

```
"ICARD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ICARD"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"ICARD" -> "STRING"
```

———-

10.3 domain IBITS IndexedBits

— **IndexedBits.input** —

```
)set break resume
)sys rm -f IndexedBits.output
)spool IndexedBits.output
)set message test on
)set message auto off
)clear all
--S 1 of 13
a:IBITS(32):=new(32,false)
--R
--R
--R   (1)  "00000000000000000000000000000000"
--R                                                    Type: IndexedBits(32)
--E 1

--S 2 of 13
b:IBITS(32):=new(32,true)
--R
--R
--R   (2)  "11111111111111111111111111111111"
--R                                                    Type: IndexedBits(32)
--E 2

--S 3 of 13
elt(a,3)
--R
--R
--R   (3)  false
--R                                                           Type: Boolean
--E 3

--S 4 of 13
```

```
setelt(a,3,true)
--R
--R
--R   (4)  true
--R                                                          Type: Boolean
--E 4

--S 5 of 13
a
--R
--R
--R   (5)  "00000000000000000000000000000100"
--R                                                  Type: IndexedBits(32)
--E 5

--S 6 of 13
#a
--R
--R
--R   (6)  32
--R                                                  Type: PositiveInteger
--E 6

--S 7 of 13
(a=a)$IBITS(32)
--R
--R
--R   (7)  true
--R                                                          Type: Boolean
--E 7

--S 8 of 13
(a=b)$IBITS(32)
--R
--R
--R   (8)  false
--R                                                          Type: Boolean
--E 8

--S 9 of 13
(a ~= b)
--R
--R
--R   (9)  true
--R                                                          Type: Boolean
--E 9

--S 10 of 13
Or(a,b)
--R
```

```
--R
--R   (10)  "11111111111111111111111111111111"
--R                                                    Type: IndexedBits(32)
--E 10

--S 11 of 13
And(a,b)
--R
--R
--R   (11)  "00000000000000000000000000000100"
--R                                                    Type: IndexedBits(32)
--E 11

--S 12 of 13
Not(a)
--R
--R
--R   (12)  "11111111111111111111111111111011"
--R                                                    Type: IndexedBits(32)
--E 12

--S 13 of 13
c:=copy a
--R
--R
--R   (13)  "00000000000000000000000000000100"
--R                                                    Type: IndexedBits(32)
--E 13
)spool
)lisp (bye)
```

———-

— IndexedBits.help —

```
====================================================================
IndexedBits
====================================================================

a:IBITS(32):=new(32,false)
  "00000000000000000000000000000000"

b:IBITS(32):=new(32,true)
  "11111111111111111111111111111111"

elt(a,3)
  false

setelt(a,3,true)
```

```
  true

a
  "00000000000000000000000000000100"

#a
  32

(a=a)$IBITS(32)
  true

(a=b)$IBITS(32)
  false

(a ~= b)
  true

Or(a,b)
  "11111111111111111111111111111111"


And(a,b)
  "00000000000000000000000000000100"

Not(a)
  "11111111111111111111111111111011"

c:=copy a
  "00000000000000000000000000000100"

See Also:
o )show IndexedBits
```

10.3.1 IndexedBits (IBITS)



See

⇒ "Reference" (REF) 19.5.1 on page 2215
⇒ "Boolean" (BOOLEAN) 3.15.1 on page 306
⇒ "Bits" (BITS) 3.12.1 on page 299

Exports:

And	any?	coerce	concat	construct
convert	copy	copyInto!	count	count
delete	elt	empty	empty?	entries
entry?	eq?	eval	every?	fill!
find	first	hash	index?	indices
insert	latex	less?	map	map!
max	maxIndex	member?	members	merge
min	minIndex	more?	nand	new
nor	Not	not?	Or	parts
position	qelt	qsetelt!	reduce	removeDuplicates
reverse	reverse!	sample	select	size?
sort	sort!	sorted?	swap!	xor
#?	?.?	?/\?	?<?	?<=?
?=?	?>?	?>=?	?\/?	^?
?.?	~?	?~=?	?or?	?and?

— domain IBITS IndexedBits —

```
)abbrev domain IBITS IndexedBits
++ Author: Stephen Watt and Michael Monagan
++ Date Created: July 86
++ Change History:  Oct 87
++ Basic Operations: range
++ Related Constructors:
++ Keywords: indexed bits
++ Description:
++ \spadtype{IndexedBits} is a domain to compactly represent
++ large quantities of Boolean data.
```

```
IndexedBits(mn:Integer): BitAggregate() with
        -- temporaries until parser gets better
        Not: % -> %
            ++ Not(n) returns the bit-by-bit logical Not of n.
        Or : (%, %) -> %
            ++ Or(n,m)  returns the bit-by-bit logical Or of
            ++ n and m.
        And: (%, %) -> %
            ++ And(n,m)  returns the bit-by-bit logical And of
            ++ n and m.
    == add

        range: (%, Integer) -> Integer
          --++ range(j,i) returnes the range i of the boolean j.

        minIndex u  == mn

        range(v, i) ==
          i >= 0 and i < #v => i
          error "Index out of range"

        coerce(v):OutputForm ==
            t:Character := char "1"
            f:Character := char "0"
            s := new(#v, space()$Character)$String
            for i in minIndex(s)..maxIndex(s) for j in mn.. repeat
              s.i := if v.j then t else f
            s::OutputForm

        new(n, b)       == BVEC_-MAKE_-FULL(n,TRUTH_-TO_-BIT(b)$Lisp)$Lisp
        empty()         == BVEC_-MAKE_-FULL(0,0)$Lisp
        copy v          == BVEC_-COPY(v)$Lisp
        #v              == BVEC_-SIZE(v)$Lisp
        v = u           == BVEC_-EQUAL(v, u)$Lisp
        v < u           == BVEC_-GREATER(u, v)$Lisp
        _and(u, v)      == (#v=#u => BVEC_-AND(v,u)$Lisp; map("and",v,u))
        _or(u, v)       == (#v=#u => BVEC_-OR(v, u)$Lisp; map("or", v,u))
        xor(v,u)        == (#v=#u => BVEC_-XOR(v,u)$Lisp; map("xor",v,u))
        setelt(v:%, i:Integer, f:Boolean) ==
          BVEC_-SETELT(v, range(v, abs(i-mn)), TRUTH_-TO_-BIT(f)$Lisp)$Lisp
        elt(v:%, i:Integer) ==
          BIT_-TO_-TRUTH(BVEC_-ELT(v, range(v, abs(i-mn)))$Lisp)$Lisp

        Not v           == BVEC_-NOT(v)$Lisp
        And(u, v)       == (#v=#u => BVEC_-AND(v,u)$Lisp; map("and",v,u))
        Or(u, v)        == (#v=#u => BVEC_-OR(v, u)$Lisp; map("or", v,u))
```

———-

— **IBITS.dotabb** —

```
"IBITS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IBITS"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"IBITS" -> "STRING"
```

———-

10.4 domain IDPAG IndexedDirectProductAbelianGroup

— **IndexedDirectProductAbelianGroup.input** —

```
)set break resume
)sys rm -f IndexedDirectProductAbelianGroup.output
)spool IndexedDirectProductAbelianGroup.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedDirectProductAbelianGroup
--R IndexedDirectProductAbelianGroup(A: AbelianGroup,S: OrderedSet)  is a domain constructor
--R Abbreviation for IndexedDirectProductAbelianGroup is IDPAG
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IDPAG
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,%) -> %               ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 0 : () -> %                          coerce : % -> OutputForm
--R hash : % -> SingleInteger            latex : % -> String
--R leadingCoefficient : % -> A          leadingSupport : % -> S
--R map : ((A -> A),%) -> %              monomial : (A,S) -> %
--R reductum : % -> %                    sample : () -> %
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— IndexedDirectProductAbelianGroup.help —

```
====================================================================
IndexedDirectProductAbelianGroup examples
====================================================================

See Also:
o )show IndexedDirectProductAbelianGroup
```

———-

10.4.1 IndexedDirectProductAbelianGroup (IDPAG)



See

⇒ “IndexedDirectProductObject” (IDPO) 10.6.1 on page 1179
⇒ “IndexedDirectProductAbelianMonoid” (IDPAM) 10.5.1 on page 1175
⇒ “IndexedDirectProductOrderedAbelianMonoid” (IDPOAM) 10.7.1 on page 1182
⇒ “IndexedDirectProductOrderedAbelianMonoidSup” (IDPOAMS) 10.8.1 on page 1184

Exports:

0	coerce	hash	latex	leadingCoefficient
leadingSupport	map	monomial	reductum	sample
subtractIfCan	zero?	?~=?	?*?	?+?
?-?	-?	?=?		

— domain IDPAG IndexedDirectProductAbelianGroup —

```
)abbrev domain IDPAG IndexedDirectProductAbelianGroup
++ Author: Mark Botch
++ Description:
++ Indexed direct products of abelian groups over an abelian group \spad{A} of
++ generators indexed by the ordered set S.
++ All items have finite support: only non-zero terms are stored.
```

```
IndexedDirectProductAbelianGroup(A:AbelianGroup,S:OrderedSet):
    Join(AbelianGroup,IndexedDirectProductCategory(A,S))
 ==  IndexedDirectProductAbelianMonoid(A,S) add
    --representations
       Term:=  Record(k:S,c:A)
       Rep:=  List Term
       x,y: %
       r: A
       n: Integer
       f: A -> A
       s: S
       -x == [[u.k,-u.c] for u in x]
       n * x  ==
             n = 0 => 0
             n = 1 => x
             [[u.k,a] for u in x | (a:=n*u.c) ^= 0$A]

       qsetrest!: (Rep, Rep) -> Rep
       qsetrest!(l: Rep, e: Rep): Rep == RPLACD(l, e)$Lisp

       x - y ==
                null x => -y
                null y => x
                endcell: Rep := empty()
                res:  Rep := empty()
                while not empty? x and not empty? y repeat
                        newcell := empty()
                        if x.first.k = y.first.k then
                                r:= x.first.c - y.first.c
                                if not zero? r then
                                        newcell := cons([x.first.k, r], empty())
                                x := rest x
                                y := rest y
                        else if x.first.k > y.first.k then
                                newcell := cons(x.first, empty())
                                x := rest x
                        else
                                newcell := cons([y.first.k,-y.first.c], empty())
                                y := rest y
                        if not empty? newcell then
                                if not empty? endcell then
                                        qsetrest!(endcell, newcell)
                                        endcell := newcell
                                else
                                        res     := newcell;
                                        endcell := res
                if empty? x then end := - y
                else end := x
                if empty? res then res := end
                else qsetrest!(endcell, end)
```

```
               res

--       x - y  ==
--          empty? x => - y
--          empty? y => x
--          y.first.k > x.first.k => cons([y.first.k,-y.first.c],(x - y.rest))
--          x.first.k > y.first.k => cons(x.first,(x.rest - y))
--          r:= x.first.c - y.first.c
--          r = 0 => x.rest - y.rest
--          cons([x.first.k,r],(x.rest - y.rest))
```

———-

— IDPAG.dotabb —

```
"IDPAG" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IDPAG"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"IDPC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=IDPC"]
"IDPAG" -> "IDPC"
"IDPAG" -> "ORDSET"
```

———-

10.5 domain IDPAM IndexedDirectProductAbelianMonoid

— IndexedDirectProductAbelianMonoid.input —

```
)set break resume
)sys rm -f IndexedDirectProductAbelianMonoid.output
)spool IndexedDirectProductAbelianMonoid.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedDirectProductAbelianMonoid
--R IndexedDirectProductAbelianMonoid(A: AbelianMonoid,S: OrderedSet)  is a domain constructor
--R Abbreviation for IndexedDirectProductAbelianMonoid is IDPAM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IDPAM
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?+? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                0 : () -> %
```

```
--R coerce : % -> OutputForm                hash : % -> SingleInteger
--R latex : % -> String                     leadingCoefficient : % -> A
--R leadingSupport : % -> S                 map : ((A -> A),%) -> %
--R monomial : (A,S) -> %                   reductum : % -> %
--R sample : () -> %                        zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedDirectProductAbelianMonoid.help** —

```
=====================================================================
IndexedDirectProductAbelianMonoid examples
=====================================================================

See Also:
o )show IndexedDirectProductAbelianMonoid
```

———-

10.5.1 IndexedDirectProductAbelianMonoid (IDPAM)



See

⇒ “IndexedDirectProductObject” (IDPO) 10.6.1 on page 1179
⇒ “IndexedDirectProductOrderedAbelianMonoid” (IDPOAM) 10.7.1 on page 1182
⇒ “IndexedDirectProductOrderedAbelianMonoidSup” (IDPOAMS) 10.8.1 on page 1184
⇒ “IndexedDirectProductAbelianGroup” (IDPAG) 10.4.1 on page 1172

Exports:

0	coerce	hash	latex	leadingCoefficient
leadingSupport	map	monomial	reductum	sample
zero?	?~=?	?*?	?+?	?=?

— domain IDPAM IndexedDirectProductAbelianMonoid —

```
)abbrev domain IDPAM IndexedDirectProductAbelianMonoid
++ Author: Mark Botch
++ Description:
++ Indexed direct products of abelian monoids over an abelian monoid
++ \spad{A} of generators indexed by the ordered set S. All items have
++ finite support. Only non-zero terms are stored.

IndexedDirectProductAbelianMonoid(A:AbelianMonoid,S:OrderedSet):
    Join(AbelianMonoid,IndexedDirectProductCategory(A,S))
 ==  IndexedDirectProductObject(A,S) add
    --representations
       Term:=  Record(k:S,c:A)
       Rep:=  List Term
       x,y: %
       r: A
       n: NonNegativeInteger
       f: A -> A
       s: S
       0  == []
       zero? x ==  null x

        -- PERFORMANCE CRITICAL; Should build list up
        --  by merging 2 sorted lists.   Doing this will
        -- avoid the recursive calls (very useful if there is a
        -- large number of vars in a polynomial.
--       x + y  ==
--          null x => y
--          null y => x
--          y.first.k > x.first.k => cons(y.first,(x + y.rest))
--          x.first.k > y.first.k => cons(x.first,(x.rest + y))
--          r:= x.first.c + y.first.c
--          r = 0 => x.rest + y.rest
--          cons([x.first.k,r],(x.rest + y.rest))
       qsetrest!: (Rep, Rep) -> Rep
       qsetrest!(l: Rep, e: Rep): Rep == RPLACD(l, e)$Lisp

       x + y ==
        null x => y
        null y => x
        endcell: Rep := empty()
        res:  Rep := empty()
        while not empty? x and not empty? y repeat
            newcell := empty()
```

```
            if x.first.k = y.first.k then
                r:= x.first.c + y.first.c
                if not zero? r then
                    newcell := cons([x.first.k, r], empty())
                x := rest x
                y := rest y
            else if x.first.k > y.first.k then
                newcell := cons(x.first, empty())
                x := rest x
            else
                newcell := cons(y.first, empty())
                y := rest y
            if not empty? newcell then
                if not empty? endcell then
                    qsetrest!(endcell, newcell)
                    endcell := newcell
                else
                    res     := newcell;
                    endcell := res
        if empty? x then end := y
        else end := x
        if empty? res then res := end
        else qsetrest!(endcell, end)
        res

      n * x  ==
            n = 0 => 0
            n = 1 => x
            [[u.k,a] for u in x | (a:=n*u.c) ^= 0$A]

      monomial(r,s) == (r = 0 => 0; [[s,r]])
      map(f,x) == [[tm.k,a] for tm in x | (a:=f(tm.c)) ^= 0$A]

      reductum x     == (null x => 0; rest x)
      leadingCoefficient x  == (null x => 0; x.first.c)
```

———-

— **IDPAM.dotabb** —

```
"IDPAM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IDPAM"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"IDPC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=IDPC"]
"IDPAM" -> "IDPC"
"IDPAM" -> "ORDSET"
```

———-

10.6 domain IDPO IndexedDirectProductObject

— **IndexedDirectProductObject.input** —

```
)set break resume
)sys rm -f IndexedDirectProductObject.output
)spool IndexedDirectProductObject.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedDirectProductObject
--R IndexedDirectProductObject(A: SetCategory,S: OrderedSet)  is a domain constructor
--R Abbreviation for IndexedDirectProductObject is IDPO
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IDPO
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R leadingCoefficient : % -> A           leadingSupport : % -> S
--R map : ((A -> A),%) -> %               monomial : (A,S) -> %
--R reductum : % -> %                     ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedDirectProductObject.help** —

```
=====================================================================
IndexedDirectProductObject examples
=====================================================================

See Also:
o )show IndexedDirectProductObject
```

———-

10.6.1 IndexedDirectProductObject (IDPO)



See

⇒ "IndexedDirectProductAbelianMonoid" (IDPAM) 10.5.1 on page 1175
⇒ "IndexedDirectProductOrderedAbelianMonoid" (IDPOAM) 10.7.1 on page 1182
⇒ "IndexedDirectProductOrderedAbelianMonoidSup" (IDPOAMS) 10.8.1 on page 1184
⇒ "IndexedDirectProductAbelianGroup" (IDPAG) 10.4.1 on page 1172

Exports:

coerce	hash	latex	leadingCoefficient	leadingSupport
map	monomial	reductum	?=?	?~=?

— domain IDPO IndexedDirectProductObject —

```
)abbrev domain IDPO IndexedDirectProductObject
++ Author: Mark Botch
++ Description:
++ Indexed direct products of objects over a set \spad{A}
++ of generators indexed by an ordered set S. All items have finite support.

IndexedDirectProductObject(A:SetCategory,S:OrderedSet): _
  IndexedDirectProductCategory(A,S)
 == add
    --representations
       Term:=  Record(k:S,c:A)
       Rep:=  List Term
    --declarations
       x,y: %
       f: A -> A
       s: S
    --define
       x = y ==
         while not null x and _^ null y repeat
           x.first.k ^= y.first.k => return false
           x.first.c ^= y.first.c => return false
           x:=x.rest
           y:=y.rest
         null x and null y
```

```
       coerce(x:%):OutputForm ==
          bracket [rarrow(t.k :: OutputForm, t.c :: OutputForm) for t in x]

       -- sample():% == [[sample()$S,sample()$A]$Term]$Rep

       monomial(r,s) == [[s,r]]
       map(f,x) == [[tm.k,f(tm.c)] for tm in x]

       reductum x     ==
          rest x
       leadingCoefficient x  ==
          null x => error "Can't take leadingCoefficient of empty product element"
          x.first.c
       leadingSupport x  ==
          null x => error "Can't take leadingCoefficient of empty product element"
          x.first.k
```

———-

— **IDPO.dotabb** —

```
"IDPO" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IDPO"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"IDPC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=IDPC"]
"IDPO" -> "IDPC"
"IDPO" -> "ORDSET"
```

———-

10.7 domain IDPOAM IndexedDirectProductOrdered-AbelianMonoid

— **IndexedDirectProductOrderedAbelianMonoid.input** —

```
)set break resume
)sys rm -f IndexedDirectProductOrderedAbelianMonoid.output
)spool IndexedDirectProductOrderedAbelianMonoid.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show IndexedDirectProductOrderedAbelianMonoid
--R IndexedDirectProductOrderedAbelianMonoid(A: OrderedAbelianMonoid,S: OrderedSet)  is a domain constructo
--R Abbreviation for IndexedDirectProductOrderedAbelianMonoid is IDPOAM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IDPOAM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?+? : (%,%) -> %
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               0 : () -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> A
--R leadingSupport : % -> S               map : ((A -> A),%) -> %
--R max : (%,%) -> %                      min : (%,%) -> %
--R monomial : (A,S) -> %                 reductum : % -> %
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedDirectProductOrderedAbelianMonoid.help** —

```
=====================================================================
IndexedDirectProductOrderedAbelianMonoid examples
=====================================================================

See Also:
o )show IndexedDirectProductOrderedAbelianMonoid
```

———-

10.7.1 IndexedDirectProductOrderedAbelianMonoid (IDPOAM)



See

⇒ "IndexedDirectProductObject" (IDPO) 10.6.1 on page 1179
⇒ "IndexedDirectProductAbelianMonoid" (IDPAM) 10.5.1 on page 1175
⇒ "IndexedDirectProductOrderedAbelianMonoidSup" (IDPOAMS) 10.8.1 on page 1184
⇒ "IndexedDirectProductAbelianGroup" (IDPAG) 10.4.1 on page 1172

Exports:

0	coerce	hash	latex	leadingCoefficient
leadingSupport	map	max	min	monomial
reductum	sample	zero?	?~=?	?*?
?+?	?<?	?<=?	?=?	?>?
?>=?				

— **domain IDPOAM IndexedDirectProductOrderedAbelianMonoid** —

```
)abbrev domain IDPOAM IndexedDirectProductOrderedAbelianMonoid
++ Author: Mark Botch
++ Description:
++ Indexed direct products of ordered abelian monoids \spad{A} of
++ generators indexed by the ordered set S.
++ The inherited order is lexicographical.
++ All items have finite support: only non-zero terms are stored.

IndexedDirectProductOrderedAbelianMonoid(A:OrderedAbelianMonoid,S:OrderedSet):
    Join(OrderedAbelianMonoid,IndexedDirectProductCategory(A,S))
 ==  IndexedDirectProductAbelianMonoid(A,S) add
    --representations
       Term:=  Record(k:S,c:A)
       Rep:=  List Term
       x,y: %
       x<y ==
         empty? y => false
         empty? x => true   -- note careful order of these two lines
         y.first.k > x.first.k => true
```

```
        y.first.k < x.first.k => false
        y.first.c > x.first.c => true
        y.first.c < x.first.c => false
        x.rest < y.rest
```

———-

— **IDPOAM.dotabb** —

```
"IDPOAM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IDPOAM"]
"OAMON" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAMON"]
"IDPOAM" -> "OAMON"
```

———-

10.8 domain IDPOAMS IndexedDirectProductOrdered-AbelianMonoidSup

— **IndexedDirectProductOrderedAbelianMonoidSup.input** —

```
)set break resume
)sys rm -f IndexedDirectProductOrderedAbelianMonoidSup.output
)spool IndexedDirectProductOrderedAbelianMonoidSup.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedDirectProductOrderedAbelianMonoidSup
--R IndexedDirectProductOrderedAbelianMonoidSup(A: OrderedAbelianMonoidSup,S: OrderedSet)  is a domain const
--R Abbreviation for IndexedDirectProductOrderedAbelianMonoidSup is IDPOAMS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IDPOAMS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?+? : (%,%) -> %
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               0 : () -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> A
--R leadingSupport : % -> S               map : ((A -> A),%) -> %
--R max : (%,%) -> %                      min : (%,%) -> %
```

```
--R monomial : (A,S) -> %                  reductum : % -> %
--R sample : () -> %                       sup : (%,%) -> %
--R zero? : % -> Boolean                   ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedDirectProductOrderedAbelianMonoidSup.help** —

```
=====================================================================
IndexedDirectProductOrderedAbelianMonoidSup examples
=====================================================================

See Also:
o )show IndexedDirectProductOrderedAbelianMonoidSup
```

———-

10.8.1 IndexedDirectProductOrderedAbelianMonoidSup (IDPOAMS)



See

⇒ “IndexedDirectProductObject” (IDPO) 10.6.1 on page 1179
⇒ “IndexedDirectProductAbelianMonoid” (IDPAM) 10.5.1 on page 1175
⇒ “IndexedDirectProductOrderedAbelianMonoid” (IDPOAM) 10.7.1 on page 1182
⇒ “IndexedDirectProductAbelianGroup” (IDPAG) 10.4.1 on page 1172

Exports:

0	coerce	hash	latex	leadingCoefficient
leadingSupport	map	max	min	monomial
reductum	sample	subtractIfCan	sup	zero?
?~=?	?*?	?+?	?<?	?<=?
?=?	?>?	?>=?		

— domain IDPOAMS IndexedDirectProductOrderedAbelianMonoidSup —

```
)abbrev domain IDPOAMS IndexedDirectProductOrderedAbelianMonoidSup
++ Author: Mark Botch
++ Description:
++ Indexed direct products of ordered abelian monoid sups \spad{A},
++ generators indexed by the ordered set S.
++ All items have finite support: only non-zero terms are stored.

IndexedDirectProductOrderedAbelianMonoidSup(A:OrderedAbelianMonoidSup,S:OrderedSet):
    Join(OrderedAbelianMonoidSup,IndexedDirectProductCategory(A,S))
 ==  IndexedDirectProductOrderedAbelianMonoid(A,S) add
    --representations
       Term:=  Record(k:S,c:A)
       Rep:=  List Term
       x,y: %
       r: A
       s: S

       subtractIfCan(x,y) ==
         empty? y => x
         empty? x => "failed"
         x.first.k < y.first.k => "failed"
         x.first.k > y.first.k =>
             t:= subtractIfCan(x.rest, y)
             t case "failed" => "failed"
             cons( x.first, t)
         u:=subtractIfCan(x.first.c, y.first.c)
         u case "failed" => "failed"
         zero? u => subtractIfCan(x.rest, y.rest)
         t:= subtractIfCan(x.rest, y.rest)
         t case "failed" => "failed"
         cons([x.first.k,u],t)

       sup(x,y) ==
         empty? y => x
         empty? x => y
         x.first.k < y.first.k => cons(y.first,sup(x,y.rest))
         x.first.k > y.first.k => cons(x.first,sup(x.rest,y))
         u:=sup(x.first.c, y.first.c)
         cons([x.first.k,u],sup(x.rest,y.rest))
```

———-

— **IDPOAMS.dotabb** —

```
"IDPOAMS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IDPOAMS"]
"OAMONS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAMONS"]
"IDPOAMS" -> "OAMONS"
```

———-

10.9 domain INDE IndexedExponents

— **IndexedExponents.input** —

```
)set break resume
)sys rm -f IndexedExponents.output
)spool IndexedExponents.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedExponents
--R
--R IndexedExponents(Varset: OrderedSet)  is a domain constructor
--R Abbreviation for IndexedExponents is INDE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INDE
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?+? : (%,%) -> %
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               0 : () -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   leadingSupport : % -> Varset
--R max : (%,%) -> %                      min : (%,%) -> %
--R reductum : % -> %                     sample : () -> %
--R sup : (%,%) -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R leadingCoefficient : % -> NonNegativeInteger
--R map : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
```

```
--R monomial : (NonNegativeInteger,Varset) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedExponents.help** —

```
=====================================================================
IndexedExponents examples
=====================================================================

See Also:
o )show IndexedExponents
```

———-

10.9.1 IndexedExponents (INDE)



See

⇒ “Polynomial” (POLY) 17.25.1 on page 2043
⇒ “MultivariatePolynomial” (MPOLY) 14.16.1 on page 1649
⇒ “SparseMultivariatePolynomial” (SMP) 20.14.1 on page 2390

Exports:

0	coerce	hash	latex	leadingCoefficient
leadingSupport	map	max	min	monomial
reductum	sample	subtractIfCan	sup	zero?
?~=?	?*?	?+?	?<?	?<=?
?=?	?>?	?>=?		

— domain INDE IndexedExponents —

```
)abbrev domain INDE IndexedExponents
++ Author: James Davenport
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ IndexedExponents of an ordered set of variables gives a representation
++ for the degree of polynomials in commuting variables. It gives an ordered
++ pairing of non negative integer exponents with variables

IndexedExponents(Varset:OrderedSet): C == T where
  C == Join(OrderedAbelianMonoidSup,
            IndexedDirectProductCategory(NonNegativeInteger,Varset))
  T == IndexedDirectProductOrderedAbelianMonoidSup(NonNegativeInteger,Varset) add
      Term:=  Record(k:Varset,c:NonNegativeInteger)
      Rep:=  List Term
      x:%
      t:Term
      coerceOF(t):OutputForm ==     --++ converts term to OutputForm
         t.c = 1 => (t.k)::OutputForm
         (t.k)::OutputForm ** (t.c)::OutputForm
      coerce(x):OutputForm == ++ converts entire exponents to OutputForm
         null x => 1::Integer::OutputForm
         null rest x => coerceOF(first x)
         reduce("*",[coerceOF t for t in x])
```

———-

— INDE.dotabb —

```
"INDE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INDE"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"INDE" -> "FLAGG"
```

———-

10.10 domain IFARRAY IndexedFlexibleArray

— IndexedFlexibleArray.input —

```
)set break resume
)sys rm -f IndexedFlexibleArray.output
)spool IndexedFlexibleArray.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedFlexibleArray
--R
--R IndexedFlexibleArray(S: Type,mn: Integer)  is a domain constructor
--R Abbreviation for IndexedFlexibleArray is IFARRAY
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IFARRAY
--R
--R------------------------------ Operations --------------------------------
--R concat : List(%) -> %                 concat : (%,%) -> %
--R concat : (S,%) -> %                   concat : (%,S) -> %
--R concat! : (%,S) -> %                  concat! : (%,%) -> %
--R construct : List(S) -> %              copy : % -> %
--R delete : (%,Integer) -> %             delete! : (%,Integer) -> %
--R ?.? : (%,Integer) -> S                elt : (%,Integer,S) -> S
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(S)                eq? : (%,%) -> Boolean
--R flexibleArray : List(S) -> %          index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)          insert : (%,%,Integer) -> %
--R insert : (S,%,Integer) -> %           insert! : (S,%,Integer) -> %
--R insert! : (%,%,Integer) -> %          map : (((S,S) -> S),%,%) -> %
--R map : ((S -> S),%) -> %               new : (NonNegativeInteger,S) -> %
--R qelt : (%,Integer) -> S               reverse : % -> %
--R sample : () -> %                      shrinkable : Boolean -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R convert : % -> InputForm if S has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R delete : (%,UniversalSegment(Integer)) -> %
```

```
--R delete! : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R find : ((S -> Boolean),%) -> Union(S,"failed")
--R first : % -> S if Integer has ORDSET
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R merge : (%,%) -> % if S has ORDSET
--R merge : (((S,S) -> Boolean),%,%) -> %
--R merge! : (((S,S) -> Boolean),%,%) -> %
--R merge! : (%,%) -> % if S has ORDSET
--R min : (%,%) -> % if S has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R physicalLength : % -> NonNegativeInteger
--R physicalLength! : (%,Integer) -> %
--R position : (S,%,Integer) -> Integer if S has SETCAT
--R position : (S,%) -> Integer if S has SETCAT
--R position : ((S -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R reduce : (((S,S) -> S),%) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S,S) -> S if $ has finiteAggregate and S has SETCAT
--R remove : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (S,%) -> % if $ has finiteAggregate and S has SETCAT
--R remove! : ((S -> Boolean),%) -> %
--R remove! : (S,%) -> % if S has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and S has SETCAT
--R removeDuplicates! : % -> % if S has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((S -> Boolean),%) -> %
--R setelt : (%,UniversalSegment(Integer),S) -> S if $ has shallowlyMutable
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if S has ORDSET
--R sort : (((S,S) -> Boolean),%) -> %
```

```
--R sort! : % -> % if $ has shallowlyMutable and S has ORDSET
--R sort! : (((S,S) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if S has ORDSET
--R sorted? : (((S,S) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedFlexibleArray.help** —

```
=====================================================================
IndexedFlexibleArray examples
=====================================================================

See Also:
o )show IndexedFlexibleArray
```

———-

10.10.1 IndexedFlexibleArray (IFARRAY)



See

⇒ “PrimitiveArray” (PRIMARR) 17.30.1 on page 2075
⇒ “Tuple” (TUPLE) 21.12.1 on page 2721
⇒ “FlexibleArray” (FARRAY) 7.14.1 on page 856
⇒ “IndexedOneDimensionalArray” (IARRAY1) 10.13.1 on page 1212
⇒ “OneDimensionalArray” (ARRAY1) 16.3.1 on page 1740

Exports:

concat	concat!	construct	copy
delete	delete!	elt	empty
empty?	entries	eq?	flexibleArray
index?	indices	insert	insert!
map	new	qelt	reverse
sample	shrinkable	any?	coerce
convert	copyInto!	count	delete
delete!	entry?	eval	every?
fill!	find	first	hash
latex	less?	map!	max
maxIndex	member?	members	merge
merge!	min	minIndex	more?
parts	physicalLength	physicalLength!	position
qsetelt!	reduce	remove	remove!
removeDuplicates	removeDuplicates!	reverse!	select
select!	setelt	size?	sort
sort!	sorted?	swap!	#?
?<?	?<=?	?=?	?>?
?>=?	?~=?	?.?	

— domain IFARRAY IndexedFlexibleArray —

```
)abbrev domain IFARRAY IndexedFlexibleArray
++ Author: Michael Monagan July/87, modified SMW June/91
++ Description:
++ A FlexibleArray is the notion of an array intended to allow for growth
++ at the end only.  Hence the following efficient operations\br
++ \spad{append(x,a)} meaning append item x at the end of the array \spad{a}\br
++ \spad{delete(a,n)} meaning delete the last item from the array \spad{a}\br
++ Flexible arrays support the other operations inherited from
++ \spadtype{ExtensibleLinearAggregate}. However, these are not efficient.
++ Flexible arrays combine the \spad{O(1)} access time property of arrays
++ with growing and shrinking at the end in \spad{O(1)} (average) time.
++ This is done by using an ordinary array which may have zero or more
++ empty slots at the end.  When the array becomes full it is copied
++ into a new larger (50% larger) array.  Conversely, when the array
++ becomes less than 1/2 full, it is copied into a smaller array.
++ Flexible arrays provide for an efficient implementation of many
++ data structures in particular heaps, stacks and sets.

IndexedFlexibleArray(S:Type, mn: Integer): Exports == Implementation where
  A ==> PrimitiveArray S
  I ==> Integer
  N ==> NonNegativeInteger
  U ==> UniversalSegment Integer
  Exports ==
   Join(OneDimensionalArrayAggregate S,ExtensibleLinearAggregate S) with
```

```
    flexibleArray : List S -> %
     ++ flexibleArray(l) creates a flexible array from the list of elements l
     ++
     ++X T1:=IndexedFlexibleArray(Integer,20)
     ++X flexibleArray([i for i in 1..10])$T1

    physicalLength : % -> NonNegativeInteger
     ++ physicalLength(x) returns the number of elements x can
     ++ accomodate before growing
     ++
     ++X T1:=IndexedFlexibleArray(Integer,20)
     ++X t2:=flexibleArray([i for i in 1..10])$T1
     ++X physicalLength t2

    physicalLength_!: (%, I) -> %
     ++ physicalLength!(x,n) changes the physical length of x to be n and
     ++ returns the new array.
     ++
     ++X T1:=IndexedFlexibleArray(Integer,20)
     ++X t2:=flexibleArray([i for i in 1..10])$T1
     ++X physicalLength!(t2,15)

    shrinkable: Boolean -> Boolean
     ++ shrinkable(b) sets the shrinkable attribute of flexible arrays to b
     ++ and returns the previous value
     ++
     ++X T1:=IndexedFlexibleArray(Integer,20)
     ++X shrinkable(false)$T1

  Implementation == add
    Rep := Record(physLen:I, logLen:I, f:A)
    shrinkable? : Boolean := true
    growAndFill : (%, I, S) -> %
    growWith    : (%, I, S) -> %
    growAdding  : (%, I, %) -> %
    shrink: (%, I)    -> %
    newa  : (N, A) -> A

    physicalLength(r) == (r.physLen) pretend NonNegativeInteger
    physicalLength_!(r, n) ==
       r.physLen = 0  => error "flexible array must be non-empty"
       growWith(r, n, r.f.0)

    empty()      == [0, 0, empty()]
    #r           == (r.logLen)::N
    fill_!(r, x) == (fill_!(r.f, x); r)
    maxIndex r   == r.logLen - 1 + mn
    minIndex r   == mn
    new(n, a)    == [n, n, new(n, a)]
```

```
shrinkable(b) ==
  oldval := shrinkable?
  shrinkable? := b
  oldval

flexibleArray l ==
   n := #l
   n = 0 => empty()
   x := l.1
   a := new(n,x)
   for i in mn + 1..mn + n-1 for y in rest l repeat a.i := y
   a

-- local utility operations
newa(n, a) ==
   zero? n => empty()
   new(n, a.0)

growAdding(r, b, s) ==
   b = 0 => r
   #r > 0 => growAndFill(r, b, (r.f).0)
   #s > 0 => growAndFill(r, b, (s.f).0)
   error "no default filler element"

growAndFill(r, b, x) ==
   (r.logLen := r.logLen + b) <= r.physLen => r
   -- enlarge by 50% + b
   n := r.physLen + r.physLen quo 2 + 1
   if r.logLen > n then n := r.logLen
   growWith(r, n, x)

growWith(r, n, x) ==
   y := new(n::N, x)$PrimitiveArray(S)
   a := r.f
   for k in 0 .. r.physLen-1 repeat y.k := a.k
   r.physLen := n
   r.f := y
   r

shrink(r, i) ==
   r.logLen := r.logLen - i
   negative?(n := r.logLen) => error "internal bug in flexible array"
   2*n+2 > r.physLen => r
   not shrinkable? => r
   if n < r.logLen
     then error "cannot shrink flexible array to indicated size"
   n = 0 => empty()
   r.physLen := n
   y := newa(n::N, a := r.f)
   for k in 0 .. n-1 repeat y.k := a.k
```

```
      r.f := y
      r

   copy r ==
      n := #r
      a := r.f
      v := newa(n, a := r.f)
      for k in 0..n-1 repeat v.k := a.k
      [n, n, v]


   elt(r:%, i:I) ==
      i < mn or i >= r.logLen + mn =>
          error "index out of range"
      r.f.(i-mn)

   setelt(r:%, i:I, x:S) ==
      i < mn or i >= r.logLen + mn =>
          error "index out of range"
      r.f.(i-mn) := x

   -- operations inherited from extensible aggregate
   merge(g, a, b)   == merge_!(g, copy a, b)
   concat(x:S, r:%) == insert_!(x, r, mn)

   concat_!(r:%, x:S) ==
      growAndFill(r, 1, x)
      r.f.(r.logLen-1) := x
      r

   concat_!(a:%, b:%) ==
      if eq?(a, b) then b := copy b
      n := #a
      growAdding(a, #b, b)
      copyInto_!(a, b, n + mn)

   remove_!(g:(S->Boolean), a:%) ==
      k:I := 0
      for i in 0..maxIndex a - mn repeat
         if not g(a.i) then (a.k := a.i; k := k+1)
      shrink(a, #a - k)

   delete_!(r:%, i1:I) ==
      i := i1 - mn
      i < 0 or i > r.logLen => error "index out of range"
      for k in i..r.logLen-2 repeat r.f.k := r.f.(k+1)
      shrink(r, 1)

   delete_!(r:%, i:U) ==
      l := lo i - mn; m := maxIndex r - mn
```

```
      h := (hasHi i => hi i - mn; m)
      l < 0 or h > m => error "index out of range"
      for j in l.. for k in h+1..m repeat r.f.j := r.f.k
      shrink(r, max(0,h-l+1))

   insert_!(x:S, r:%, i1:I):% ==
      i := i1 - mn
      n := r.logLen
      i < 0 or i > n => error "index out of range"
      growAndFill(r, 1, x)
      for k in n-1 .. i by -1 repeat r.f.(k+1) := r.f.k
      r.f.i := x
      r

   insert_!(a:%, b:%, i1:I):% ==
      i := i1 - mn
      if eq?(a, b) then b := copy b
      m := #a; n := #b
      i < 0 or i > n => error "index out of range"
      growAdding(b, m, a)
      for k in n-1 .. i by -1 repeat b.f.(m+k) := b.f.k
      for k in m-1 .. 0 by -1 repeat b.f.(i+k) := a.f.k
      b

   merge_!(g, a, b) ==
      m := #a; n := #b; growAdding(a, n, b)
      for i in m-1..0 by -1 for j in m+n-1.. by -1 repeat a.f.j := a.f.i
      i := n; j := 0
      for k in 0.. while i < n+m and j < n repeat
         if g(a.f.i,b.f.j) then (a.f.k := a.f.i; i := i+1)
         else (a.f.k := b.f.j; j := j+1)
      for k in k.. for j in j..n-1 repeat a.f.k := b.f.j
      a

   select_!(g:(S->Boolean), a:%) ==
      k:I := 0
      for i in 0..maxIndex a - mn repeat_
         if g(a.f.i) then (a.f.k := a.f.i;k := k+1)
      shrink(a, #a - k)

   if S has SetCategory then
     removeDuplicates_! a ==
        ct := #a
        ct < 2 => a

        i     := mn
        nlim  := mn + ct
        nlim0 := nlim
        while i < nlim repeat
           j := i+1
```

```
            for k in j..nlim-1 | a.k ^= a.i repeat
                a.j := a.k
                j := j+1
            nlim := j
            i := i+1
          nlim ^= nlim0 => delete_!(a, i..)
          a
```

———-

— **IFARRAY.dotabb** —

```
"IFARRAY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IFARRAY"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"IFARRAY" -> "A1AGG"
```

———-

10.11 domain ILIST IndexedList

— **IndexedList.input** —

```
)set break resume
)sys rm -f IndexedList.output
)spool IndexedList.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedList
--R
--R IndexedList(S: Type,mn: Integer)  is a domain constructor
--R Abbreviation for IndexedList is ILIST
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ILIST
--R
--R------------------------------ Operations --------------------------------
--R children : % -> List(%)               concat : (%,S) -> %
--R concat : List(%) -> %                 concat : (S,%) -> %
--R concat : (%,%) -> %                   concat! : (%,S) -> %
--R concat! : (%,%) -> %                  construct : List(S) -> %
--R copy : % -> %                         cycleEntry : % -> %
--R cycleTail : % -> %                    cyclic? : % -> Boolean
```

```
--R delete : (%,Integer) -> %            delete! : (%,Integer) -> %
--R distance : (%,%) -> Integer          elt : (%,Integer,S) -> S
--R ?.? : (%,Integer) -> S               ?.last : (%,last) -> S
--R ?.rest : (%,rest) -> %               ?.first : (%,first) -> S
--R ?.value : (%,value) -> S             empty : () -> %
--R empty? : % -> Boolean                entries : % -> List(S)
--R eq? : (%,%) -> Boolean               explicitlyFinite? : % -> Boolean
--R first : % -> S                       index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)         insert : (S,%,Integer) -> %
--R insert : (%,%,Integer) -> %          insert! : (S,%,Integer) -> %
--R insert! : (%,%,Integer) -> %         last : % -> S
--R leaf? : % -> Boolean                 leaves : % -> List(S)
--R list : S -> %                        map : (((S,S) -> S),%,%) -> %
--R map : ((S -> S),%) -> %              new : (NonNegativeInteger,S) -> %
--R nodes : % -> List(%)                 possiblyInfinite? : % -> Boolean
--R qelt : (%,Integer) -> S              rest : % -> %
--R reverse : % -> %                     sample : () -> %
--R second : % -> S                      tail : % -> %
--R third : % -> S                       value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R convert : % -> InputForm if S has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R cycleLength : % -> NonNegativeInteger
--R cycleSplit! : % -> % if $ has shallowlyMutable
--R delete : (%,UniversalSegment(Integer)) -> %
--R delete! : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R find : ((S -> Boolean),%) -> Union(S,"failed")
--R first : (%,NonNegativeInteger) -> %
--R hash : % -> SingleInteger if S has SETCAT
--R last : (%,NonNegativeInteger) -> %
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
```

```
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R merge : (((S,S) -> Boolean),%,%) -> %
--R merge : (%,%) -> % if S has ORDSET
--R merge! : (((S,S) -> Boolean),%,%) -> %
--R merge! : (%,%) -> % if S has ORDSET
--R min : (%,%) -> % if S has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R position : ((S -> Boolean),%) -> Integer
--R position : (S,%) -> Integer if S has SETCAT
--R position : (S,%,Integer) -> Integer if S has SETCAT
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R reduce : (((S,S) -> S),%,S,S) -> S if $ has finiteAggregate and S has SETCAT
--R reduce : (((S,S) -> S),%,S) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%) -> S if $ has finiteAggregate
--R remove : (S,%) -> % if $ has finiteAggregate and S has SETCAT
--R remove : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : ((S -> Boolean),%) -> %
--R remove! : (S,%) -> % if S has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and S has SETCAT
--R removeDuplicates! : % -> % if S has SETCAT
--R rest : (%,NonNegativeInteger) -> %
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((S -> Boolean),%) -> %
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R setelt : (%,UniversalSegment(Integer),S) -> S if $ has shallowlyMutable
--R setelt : (%,last,S) -> S if $ has shallowlyMutable
--R setelt : (%,rest,%) -> % if $ has shallowlyMutable
--R setelt : (%,first,S) -> S if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setfirst! : (%,S) -> S if $ has shallowlyMutable
--R setlast! : (%,S) -> S if $ has shallowlyMutable
--R setrest! : (%,%) -> % if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : (((S,S) -> Boolean),%) -> %
--R sort : % -> % if S has ORDSET
--R sort! : (((S,S) -> Boolean),%) -> % if $ has shallowlyMutable
--R sort! : % -> % if $ has shallowlyMutable and S has ORDSET
--R sorted? : (((S,S) -> Boolean),%) -> Boolean
--R sorted? : % -> Boolean if S has ORDSET
--R split! : (%,Integer) -> % if $ has shallowlyMutable
```

```
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedList.help** —

```
=====================================================================
IndexedList examples
=====================================================================

See Also:
o )show IndexedList
```

———-

10.11.1 IndexedList (ILIST)



See

⇒ “List” (LIST) 13.9.1 on page 1472
⇒ “AssociationList” (ALIST) 2.42.1 on page 220

Exports:

any?	child?	children	coerce
concat	convert	concat!	copyInto!
construct	copy	count	cycleEntry
cycleLength	cycleSplit!	cycleTail	cyclic?
delete	delete!	distance	elt
empty	empty?	entries	entry?
eq?	eval	every?	explicitlyFinite?
fill!	find	first	hash
index?	indices	insert	insert!
last	latex	leaf?	leaves
less?	list	map	map!
max	maxIndex	member?	members
merge	merge!	min	minIndex
more?	new	node?	nodes
parts	position	possiblyInfinite?	qelt
qsetelt!	reduce	remove	remove!
removeDuplicates	removeDuplicates!	rest	reverse
reverse!	sample	second	select
select!	setchildren!	setelt	setfirst!
setlast!	setrest!	setvalue!	size?
sort	sort!	sorted?	split!
swap!	tail	third	value
#?	?<?	?<=?	?=?
?>?	?>=?	?~=?	?.?
?.last	?.rest	?.first	?.value

— domain ILIST IndexedList —

```
)abbrev domain ILIST IndexedList
++ Author: Michael Monagan
++ Date Created: Sep 1987
++ Change History:
++ Basic Operations:
++   \#, concat, concat!, construct, copy, elt, elt, empty,
++   empty?, eq?, first, member?, merge!, mergeSort, minIndex,
++   parts, removeDuplicates!, rest, rest, reverse, reverse!,
++   setelt, setfirst!, setrest!, sort!, split!
++ Related Constructors: List
++ Also See:
++ AMS Classification:
++ Keywords: list, aggregate, index
++ Description:
++ \spadtype{IndexedList} is a basic implementation of the functions
++ in \spadtype{ListAggregate}, often using functions in the underlying
++ LISP system. The second parameter to the constructor (\spad{mn})
++ is the beginning index of the list. That is, if \spad{l} is a
++ list, then \spad{elt(l,mn)} is the first value. This constructor
```

```
++ is probably best viewed as the implementation of singly-linked
++ lists that are addressable by index rather than as a mere wrapper
++ for LISP lists.

IndexedList(S:Type, mn:Integer): Exports == Implementation where
 cycleMax ==> 1000        -- value used in checking for cycles

-- The following seems to be a bit out of date, but is kept in case
-- a knowledgeable person wants to update it:
--   The following LISP dependencies are divided into two groups
--   Those that are required
--   CONS, EQ, NIL, NULL, QCAR, QCDR, RPLACA, RPLACD
--   Those that are included for efficiency only
--   NEQ, LIST, CAR, CDR, NCONC2, NREVERSE, LENGTH
--   Also REVERSE, since it's called in Polynomial Ring

 Qfirst  ==> QCAR$Lisp
 Qrest   ==> QCDR$Lisp
 Qnull   ==> NULL$Lisp
 Qeq     ==> EQ$Lisp
 Qneq    ==> NEQ$Lisp
 Qcons   ==> CONS$Lisp
 Qpush   ==> PUSH$Lisp

 Exports ==> ListAggregate S
 Implementation ==>
  add
   #x                  == LENGTH(x)$Lisp
   concat(s:S,x:%)     == CONS(s,x)$Lisp
   eq?(x,y)            == EQ(x,y)$Lisp
   first x             == SPADfirst(x)$Lisp
   elt(x,"first")      == SPADfirst(x)$Lisp
   empty()             == NIL$Lisp
   empty? x            == NULL(x)$Lisp
   rest x              == CDR(x)$Lisp
   elt(x,"rest")       == CDR(x)$Lisp
   setfirst_!(x,s)     ==
      empty? x => error "Cannot update an empty list"
      Qfirst RPLACA(x,s)$Lisp
   setelt(x,"first",s) ==
      empty? x => error "Cannot update an empty list"
      Qfirst RPLACA(x,s)$Lisp
   setrest_!(x,y)      ==
      empty? x => error "Cannot update an empty list"
      Qrest RPLACD(x,y)$Lisp
   setelt(x,"rest",y)  ==
      empty? x => error "Cannot update an empty list"
      Qrest RPLACD(x,y)$Lisp
   construct l         == l pretend %
   parts s             == s pretend List S
```

```
reverse_! x          == NREVERSE(x)$Lisp
reverse x            == REVERSE(x)$Lisp
minIndex x           == mn

rest(x, n) ==
   for i in 1..n repeat
      if Qnull x then error "index out of range"
      x := Qrest x
   x

copy x ==
   y := empty()
   for i in 0.. while not Qnull x repeat
      if Qeq(i,cycleMax) and cyclic? x then error "cyclic list"
      y := Qcons(Qfirst x,y)
      x := Qrest x
   (NREVERSE(y)$Lisp)@%

if S has SetCategory then
  coerce(x):OutputForm ==
     -- displays cycle with overbar over the cycle
     y := empty()$List(OutputForm)
     s := cycleEntry x
     while Qneq(x, s) repeat
       y := concat((first x)::OutputForm, y)
       x := rest x
     y := reverse_! y
     empty? s => bracket y
     -- cyclic case: z is cylic part
     z := list((first x)::OutputForm)
     while Qneq(s, rest x) repeat
        x := rest x
        z := concat((first x)::OutputForm, z)
     bracket concat_!(y, overbar commaSeparate reverse_! z)

  x = y ==
    Qeq(x,y) => true
    while not Qnull x and not Qnull y repeat
       Qfirst x ^=$S Qfirst y => return false
       x := Qrest x
       y := Qrest y
    Qnull x and Qnull y

  latex(x : %): String ==
    s : String := "\left["
    while not Qnull x repeat
      s := concat(s, latex(Qfirst x)$S)$String
      x := Qrest x
      if not Qnull x then s := concat(s, ", ")$String
    concat(s, " \right]")$String
```

```
     member?(s,x) ==
        while not Qnull x repeat
           if s = Qfirst x then return true else x := Qrest x
        false

   -- Lots of code from parts of AGGCAT, repeated here to
   -- get faster compilation
   concat_!(x:%,y:%) ==
      Qnull x =>
        Qnull y => x
        Qpush(first y,x)
        QRPLACD(x,rest y)$Lisp
        x
      z:=x
      while not Qnull Qrest z repeat
        z:=Qrest z
      QRPLACD(z,y)$Lisp
      x

   -- Then a quicky:
   if S has SetCategory then
     removeDuplicates_! l ==
       p := l
       while not Qnull p repeat
--       p := setrest_!(p, remove_!(#1 = Qfirst p, Qrest p))
-- far too expensive - builds closures etc.
         pp:=p
         f:S:=Qfirst p
         p:=Qrest p
         while not Qnull (pr:=Qrest pp) repeat
           if (Qfirst pr)@S = f then QRPLACD(pp,Qrest pr)$Lisp
           else pp:=pr
       l

   -- then sorting
   mergeSort: ((S, S) -> Boolean, %, Integer) -> %

   sort_!(f, l)       == mergeSort(f, l, #l)

   merge_!(f, p, q) ==
     Qnull p => q
     Qnull q => p
     Qeq(p, q) => error "cannot merge a list into itself"
     if f(Qfirst p, Qfirst q)
       then (r := t := p; p := Qrest p)
       else (r := t := q; q := Qrest q)
     while not Qnull p and not Qnull q repeat
       if f(Qfirst p, Qfirst q)
         then (QRPLACD(t, p)$Lisp; t := p; p := Qrest p)
```

```
        else (QRPLACD(t, q)$Lisp; t := q; q := Qrest q)
    QRPLACD(t, if Qnull p then q else p)$Lisp
    r

  split_!(p, n) ==
     n < 1 => error "index out of range"
     p := rest(p, (n - 1)::NonNegativeInteger)
     q := Qrest p
     QRPLACD(p, NIL$Lisp)$Lisp
     q

  mergeSort(f, p, n) ==
    if n = 2 and f(first rest p, first p) then p := reverse_! p
    n < 3 => p
    l := (n quo 2)::NonNegativeInteger
    q := split_!(p, l)
    p := mergeSort(f, p, l)
    q := mergeSort(f, q, n - l)
    merge_!(f, p, q)
```

———-

— ILIST.dotabb —

```
"ILIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ILIST",
         shape=ellipse]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"ILIST" -> "STRING"
```

———-

10.12 domain IMATRIX IndexedMatrix

— IndexedMatrix.input —

```
)set break resume
)sys rm -f IndexedMatrix.output
)spool IndexedMatrix.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedMatrix
```

```
--R
--R IndexedMatrix(R: Ring,mnRow: Integer,mnCol: Integer)  is a domain constructor
--R Abbreviation for IndexedMatrix is IMATRIX
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IMATRIX
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Integer,%) -> %               ?*? : (%,R) -> %
--R ?*? : (R,%) -> %                     ?*? : (%,%) -> %
--R ?+? : (%,%) -> %                     -? : % -> %
--R ?-? : (%,%) -> %                     antisymmetric? : % -> Boolean
--R copy : % -> %                        diagonal? : % -> Boolean
--R diagonalMatrix : List(%) -> %        diagonalMatrix : List(R) -> %
--R elt : (%,Integer,Integer,R) -> R     elt : (%,Integer,Integer) -> R
--R empty : () -> %                      empty? : % -> Boolean
--R eq? : (%,%) -> Boolean               fill! : (%,R) -> %
--R horizConcat : (%,%) -> %             listOfLists : % -> List(List(R))
--R map : (((R,R) -> R),%,%,R) -> %      map : (((R,R) -> R),%,%) -> %
--R map : ((R -> R),%) -> %              map! : ((R -> R),%) -> %
--R matrix : List(List(R)) -> %          maxColIndex : % -> Integer
--R maxRowIndex : % -> Integer           minColIndex : % -> Integer
--R minRowIndex : % -> Integer           ncols : % -> NonNegativeInteger
--R nrows : % -> NonNegativeInteger      parts : % -> List(R)
--R qelt : (%,Integer,Integer) -> R      sample : () -> %
--R square? : % -> Boolean               squareTop : % -> %
--R symmetric? : % -> Boolean            transpose : % -> %
--R vertConcat : (%,%) -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (IndexedVector(R,mnCol),%) -> IndexedVector(R,mnCol)
--R ?*? : (%,IndexedVector(R,mnRow)) -> IndexedVector(R,mnRow)
--R ?**? : (%,Integer) -> % if R has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : IndexedVector(R,mnRow) -> %
--R coerce : % -> OutputForm if R has SETCAT
--R column : (%,Integer) -> IndexedVector(R,mnRow)
--R columnSpace : % -> List(IndexedVector(R,mnRow)) if R has EUCDOM
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R determinant : % -> R if R has commutative(*)
--R elt : (%,List(Integer),List(Integer)) -> %
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R hash : % -> SingleInteger if R has SETCAT
```

```
--R inverse : % -> Union(%,"failed") if R has FIELD
--R latex : % -> String if R has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R minordet : % -> R if R has commutative(*)
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,NonNegativeInteger,R) -> %
--R nullSpace : % -> List(IndexedVector(R,mnRow)) if R has INTDOM
--R nullity : % -> NonNegativeInteger if R has INTDOM
--R pfaffian : % -> R if R has COMRING
--R qsetelt! : (%,Integer,Integer,R) -> R
--R rank : % -> NonNegativeInteger if R has INTDOM
--R row : (%,Integer) -> IndexedVector(R,mnCol)
--R rowEchelon : % -> % if R has EUCDOM
--R scalarMatrix : (NonNegativeInteger,R) -> %
--R setColumn! : (%,Integer,IndexedVector(R,mnRow)) -> %
--R setRow! : (%,Integer,IndexedVector(R,mnCol)) -> %
--R setelt : (%,List(Integer),List(Integer),%) -> %
--R setelt : (%,Integer,Integer,R) -> R
--R setsubMatrix! : (%,Integer,Integer,%) -> %
--R size? : (%,NonNegativeInteger) -> Boolean
--R subMatrix : (%,Integer,Integer,Integer,Integer) -> %
--R swapColumns! : (%,Integer,Integer) -> %
--R swapRows! : (%,Integer,Integer) -> %
--R transpose : IndexedVector(R,mnCol) -> %
--R zero : (NonNegativeInteger,NonNegativeInteger) -> %
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— IndexedMatrix.help —

```
=====================================================================
IndexedMatrix examples
=====================================================================

See Also:
o )show IndexedMatrix
```

———-

10.12.1 IndexedMatrix (IMATRIX)



See

⇒ "Matrix" (MATRIX) 14.7.1 on page 1590
⇒ "RectangularMatrix" (RMATRIX) 19.4.1 on page 2211
⇒ "SquareMatrix" (SQMATRIX) 20.27.1 on page 2514

Exports:

any?	antisymmetric?	coerce	column	copy
count	determinant	diagonal?	diagonalMatrix	elt
empty	empty?	eq?	eval	every?
exquo	fill!	hash	horizConcat	inverse
latex	less?	listOfLists	map	map!
matrix	maxColIndex	maxRowIndex	member?	members
minColIndex	minordet	minRowIndex	more?	ncols
new	nrows	nullSpace	nullity	parts
qelt	qsetelt!	rank	row	rowEchelon
sample	scalarMatrix	setColumn!	setRow!	setelt
setsubMatrix!	size?	square?	squareTop	subMatrix
swapColumns!	swapRows!	symmetric?	transpose	vertConcat
zero	#?	?*?	?**?	?/?
?=?	?~=?	?+?	-?	?-?

— domain IMATRIX IndexedMatrix —

```
)abbrev domain IMATRIX IndexedMatrix
++ Author: Grabmeier, Gschnitzer, Williamson
++ Date Created: 1987
++ Date Last Updated: July 1990
++ Basic Operations:
++ Related Domains: Matrix, RectangularMatrix, SquareMatrix,
++   StorageEfficientMatrixOperations
++ Also See:
++ AMS Classifications:
++ Keywords: matrix, linear algebra
++ Examples:
++ References:
```

```
++ Description:
++ An \spad{IndexedMatrix} is a matrix where the minimal row and column
++ indices are parameters of the type.  The domains Row and Col
++ are both IndexedVectors.
++ The index of the 'first' row may be obtained by calling the
++ function \spadfun{minRowIndex}.  The index of the 'first' column may
++ be obtained by calling the function \spadfun{minColIndex}.  The index of
++ the first element of a 'Row' is the same as the index of the
++ first column in a matrix and vice versa.

IndexedMatrix(R,mnRow,mnCol): Exports == Implementation where
  R : Ring
  mnRow, mnCol : Integer
  Row ==> IndexedVector(R,mnCol)
  Col ==> IndexedVector(R,mnRow)
  MATLIN ==> MatrixLinearAlgebraFunctions(R,Row,Col,$)

  Exports ==> MatrixCategory(R,Row,Col)

  Implementation ==>
    InnerIndexedTwoDimensionalArray(R,mnRow,mnCol,Row,Col) add

      swapRows_!(x,i1,i2) ==
        (i1 < minRowIndex(x)) or (i1 > maxRowIndex(x)) or _
           (i2 < minRowIndex(x)) or (i2 > maxRowIndex(x)) =>
             error "swapRows!: index out of range"
        i1 = i2 => x
        minRow := minRowIndex x
        xx := x pretend PrimitiveArray(PrimitiveArray(R))
        n1 := i1 - minRow; n2 := i2 - minRow
        row1 := qelt(xx,n1)
        qsetelt_!(xx,n1,qelt(xx,n2))
        qsetelt_!(xx,n2,row1)
        xx pretend $

      if R has commutative("*") then

        determinant x == determinant(x)$MATLIN
        minordet    x == minordet(x)$MATLIN

      if R has EuclideanDomain then

        rowEchelon  x == rowEchelon(x)$MATLIN

      if R has IntegralDomain then

        rank        x == rank(x)$MATLIN
        nullity     x == nullity(x)$MATLIN
        nullSpace   x == nullSpace(x)$MATLIN
```

```
      if R has Field then

        inverse     x == inverse(x)$MATLIN
```

———-

— **IMATRIX.dotabb** —

```
"IMATRIX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IMATRIX"]
"MATCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=MATCAT"]
"VECTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=VECTCAT"]
"IMATRIX" -> "MATCAT"
"IMATRIX" -> "VECTCAT"
```

———-

10.13 domain IARRAY1 IndexedOneDimensionalArray

— **IndexedOneDimensionalArray.input** —

```
)set break resume
)sys rm -f IndexedOneDimensionalArray.output
)spool IndexedOneDimensionalArray.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedOneDimensionalArray
--R
--R IndexedOneDimensionalArray(S: Type,mn: Integer)  is a domain constructor
--R Abbreviation for IndexedOneDimensionalArray is IARRAY1
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IARRAY1
--R
--R------------------------------ Operations --------------------------------
--R concat : List(%) -> %                concat : (%,%) -> %
--R concat : (S,%) -> %                  concat : (%,S) -> %
--R construct : List(S) -> %             copy : % -> %
--R delete : (%,Integer) -> %            ?.? : (%,Integer) -> S
--R elt : (%,Integer,S) -> S             empty : () -> %
--R empty? : % -> Boolean                entries : % -> List(S)
--R eq? : (%,%) -> Boolean               index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)         insert : (%,%,Integer) -> %
```

```
--R insert : (S,%,Integer) -> %           map : (((S,S) -> S),%,%) -> %
--R map : ((S -> S),%) -> %               new : (NonNegativeInteger,S) -> %
--R qelt : (%,Integer) -> S               reverse : % -> %
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R convert : % -> InputForm if S has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R delete : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R find : ((S -> Boolean),%) -> Union(S,"failed")
--R first : % -> S if Integer has ORDSET
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R merge : (%,%) -> % if S has ORDSET
--R merge : (((S,S) -> Boolean),%,%) -> %
--R min : (%,%) -> % if S has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R position : (S,%,Integer) -> Integer if S has SETCAT
--R position : (S,%) -> Integer if S has SETCAT
--R position : ((S -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R reduce : (((S,S) -> S),%) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S,S) -> S if $ has finiteAggregate and S has SETCAT
--R remove : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (S,%) -> % if $ has finiteAggregate and S has SETCAT
```

```
--R removeDuplicates : % -> % if $ has finiteAggregate and S has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),S) -> S if $ has shallowlyMutable
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if S has ORDSET
--R sort : (((S,S) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and S has ORDSET
--R sort! : (((S,S) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if S has ORDSET
--R sorted? : (((S,S) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IndexedOneDimensionalArray.help** —

```
=====================================================================
IndexedOneDimensionalArray examples
=====================================================================

See Also:
o )show IndexedOneDimensionalArray
```

———-

10.13.1 IndexedOneDimensionalArray (IARRAY1)



See

⇒ "PrimitiveArray" (PRIMARR) 17.30.1 on page 2075
⇒ "Tuple" (TUPLE) 21.12.1 on page 2721
⇒ "IndexedFlexibleArray" (IFARRAY) 10.10.1 on page 1191
⇒ "FlexibleArray" (FARRAY) 7.14.1 on page 856
⇒ "OneDimensionalArray" (ARRAY1) 16.3.1 on page 1740

Exports:

concat	construct	copy	delete	elt
empty	empty?	entries	eq?	index?
indices	insert	insert	map	map
new	qelt	reverse	sample	any?
coerce	convert	copyInto!	count	count
delete	entry?	eval	eval	eval
eval	every?	fill!	find	first
hash	latex	less?	map!	max
maxIndex	member?	members	merge	merge
min	minIndex	more?	parts	position
position	position	qsetelt!	reduce	reduce
reduce	remove	remove	removeDuplicates	reverse!
select	setelt	setelt	size?	sort
sort	sort!	sort!	sorted?	sorted?
swap!	#?	?<?	?<=?	?=?
?>?	?>=?	?~=?	?.?	

— domain IARRAY1 IndexedOneDimensionalArray —

```
)abbrev domain IARRAY1 IndexedOneDimensionalArray
++ Author Micheal Monagan Aug/87
++ Description:
++ This is the basic one dimensional array data type.

IndexedOneDimensionalArray(S:Type, mn:Integer):
 OneDimensionalArrayAggregate S == add
   Qmax ==> QVMAXINDEX$Lisp
   Qsize ==> QVSIZE$Lisp
--   Qelt ==> QVELT$Lisp
--   Qsetelt ==> QSETVELT$Lisp
   Qelt ==> ELT$Lisp
   Qsetelt ==> SETELT$Lisp
--   Qelt1 ==> QVELT_-1$Lisp
--   Qsetelt1 ==> QSETVELT_-1$Lisp
   Qnew ==> MAKE_-ARRAY$Lisp
   I ==> Integer

   #x              == Qsize x
   fill_!(x, s)    == (for i in 0..Qmax x repeat Qsetelt(x, i, s); x)
   minIndex x      == mn
```

```
   empty()          == Qnew(0$Lisp)
   new(n, s)        == fill_!(Qnew n,s)

   map_!(f, s1)  ==
      n:Integer := Qmax(s1)
      n < 0 => s1
      for i in 0..n repeat Qsetelt(s1, i, f(Qelt(s1,i)))
      s1

   map(f, s1)       ==
      n:Integer := Qmax(s1)
      n < 0 => s1
      ss2:% := Qnew(n+1)
      for i in 0..n repeat Qsetelt(ss2, i, f(Qelt(s1,i)))
      ss2

   map(f, a, b)   ==
      maxind:Integer := min(Qmax a, Qmax b)
      maxind < 0 => empty()
      c:% := Qnew(maxind+1)
      for i in 0..maxind repeat
        Qsetelt(c, i, f(Qelt(a,i),Qelt(b,i)))
      c

   if zero? mn then
     qelt(x, i)       == Qelt(x, i)
     qsetelt_!(x, i, s) == Qsetelt(x, i, s)

     elt(x:%, i:I) ==
       negative? i or i > maxIndex(x) => error "index out of range"
       qelt(x, i)

     setelt(x:%, i:I, s:S) ==
       negative? i or i > maxIndex(x) => error "index out of range"
       qsetelt_!(x, i, s)

--   else if one? mn then
   else if (mn = 1) then
     maxIndex x       == Qsize x
     qelt(x, i)       == Qelt(x, i-1)
     qsetelt_!(x, i, s) == Qsetelt(x, i-1, s)

     elt(x:%, i:I) ==
       QSLESSP(i,1$Lisp)$Lisp or QSLESSP(Qsize x,i)$Lisp =>
         error "index out of range"
       Qelt(x, i-1)

     setelt(x:%, i:I, s:S) ==
       QSLESSP(i,1$Lisp)$Lisp or QSLESSP(Qsize x,i)$Lisp =>
         error "index out of range"
```

```
      Qsetelt(x, i-1, s)

   else
      qelt(x, i)       == Qelt(x, i - mn)
      qsetelt_!(x, i, s) == Qsetelt(x, i - mn, s)

      elt(x:%, i:I) ==
        i < mn or i > maxIndex(x) => error "index out of range"
        qelt(x, i)

      setelt(x:%, i:I, s:S) ==
        i < mn or i > maxIndex(x) => error "index out of range"
        qsetelt_!(x, i, s)
```

———-

— IARRAY1.dotabb —

```
"IARRAY1" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IARRAY1"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"IARRAY1" -> "A1AGG"
```

———-

10.14 domain ISTRING IndexedString

— IndexedString.input —

```
)set break resume
)sys rm -f IndexedString.output
)spool IndexedString.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedString
--R
--R IndexedString(mn: Integer)  is a domain constructor
--R Abbreviation for IndexedString is ISTRING
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ISTRING
--R
--R------------------------------ Operations --------------------------------
```

```
--R coerce : Character -> %                concat : List(%) -> %
--R concat : (%,%) -> %                    concat : (Character,%) -> %
--R concat : (%,Character) -> %            construct : List(Character) -> %
--R copy : % -> %                          delete : (%,Integer) -> %
--R ?.? : (%,%) -> %                       ?.? : (%,Integer) -> Character
--R empty : () -> %                        empty? : % -> Boolean
--R entries : % -> List(Character)         eq? : (%,%) -> Boolean
--R hash : % -> Integer                    index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)           insert : (%,%,Integer) -> %
--R leftTrim : (%,Character) -> %          lowerCase : % -> %
--R lowerCase! : % -> %                    prefix? : (%,%) -> Boolean
--R qelt : (%,Integer) -> Character        reverse : % -> %
--R rightTrim : (%,Character) -> %         sample : () -> %
--R split : (%,Character) -> List(%)       suffix? : (%,%) -> Boolean
--R trim : (%,CharacterClass) -> %         trim : (%,Character) -> %
--R upperCase : % -> %                     upperCase! : % -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if Character has ORDSET
--R ?<=? : (%,%) -> Boolean if Character has ORDSET
--R ?=? : (%,%) -> Boolean if Character has SETCAT
--R ?>? : (%,%) -> Boolean if Character has ORDSET
--R ?>=? : (%,%) -> Boolean if Character has ORDSET
--R any? : ((Character -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if Character has SETCAT
--R convert : % -> InputForm if Character has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (Character,%) -> NonNegativeInteger if $ has finiteAggregate and Character has SETCA
--R count : ((Character -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R delete : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R elt : (%,Integer,Character) -> Character
--R entry? : (Character,%) -> Boolean if $ has finiteAggregate and Character has SETCAT
--R eval : (%,List(Character),List(Character)) -> % if Character has EVALAB(CHAR) and Character
--R eval : (%,Character,Character) -> % if Character has EVALAB(CHAR) and Character has SETCAT
--R eval : (%,Equation(Character)) -> % if Character has EVALAB(CHAR) and Character has SETCAT
--R eval : (%,List(Equation(Character))) -> % if Character has EVALAB(CHAR) and Character has SE
--R every? : ((Character -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,Character) -> % if $ has shallowlyMutable
--R find : ((Character -> Boolean),%) -> Union(Character,"failed")
--R first : % -> Character if Integer has ORDSET
--R hash : % -> SingleInteger if Character has SETCAT
--R insert : (Character,%,Integer) -> %
--R latex : % -> String if Character has SETCAT
--R leftTrim : (%,CharacterClass) -> %
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : (((Character,Character) -> Character),%,%) -> %
--R map : ((Character -> Character),%) -> %
--R map! : ((Character -> Character),%) -> % if $ has shallowlyMutable
--R match : (%,%,Character) -> NonNegativeInteger
--R match? : (%,%,Character) -> Boolean
```

```
--R max : (%,%) -> % if Character has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (Character,%) -> Boolean if $ has finiteAggregate and Character has SETCAT
--R members : % -> List(Character) if $ has finiteAggregate
--R merge : (%,%) -> % if Character has ORDSET
--R merge : (((Character,Character) -> Boolean),%,%) -> %
--R min : (%,%) -> % if Character has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,Character) -> %
--R parts : % -> List(Character) if $ has finiteAggregate
--R position : (CharacterClass,%,Integer) -> Integer
--R position : (%,%,Integer) -> Integer
--R position : (Character,%,Integer) -> Integer if Character has SETCAT
--R position : (Character,%) -> Integer if Character has SETCAT
--R position : ((Character -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,Character) -> Character if $ has shallowlyMutable
--R reduce : (((Character,Character) -> Character),%) -> Character if $ has finiteAggregate
--R reduce : (((Character,Character) -> Character),%,Character) -> Character if $ has finiteAggregate
--R reduce : (((Character,Character) -> Character),%,Character,Character) -> Character if $ has finiteAggreg
--R remove : ((Character -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Character,%) -> % if $ has finiteAggregate and Character has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and Character has SETCAT
--R replace : (%,UniversalSegment(Integer),%) -> %
--R reverse! : % -> % if $ has shallowlyMutable
--R rightTrim : (%,CharacterClass) -> %
--R select : ((Character -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),Character) -> Character if $ has shallowlyMutable
--R setelt : (%,Integer,Character) -> Character if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if Character has ORDSET
--R sort : (((Character,Character) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and Character has ORDSET
--R sort! : (((Character,Character) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if Character has ORDSET
--R sorted? : (((Character,Character) -> Boolean),%) -> Boolean
--R split : (%,CharacterClass) -> List(%)
--R substring? : (%,%,Integer) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if Character has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— IndexedString.help —

```
=======================================================================
IndexedString examples
=======================================================================

See Also:
o )show IndexedString
```

———-

10.14.1 IndexedString (ISTRING)



See

⇒ “Character” (CHAR) 4.3.1 on page 359
⇒ “CharacterClass” (CCLASS) 4.4.1 on page 367
⇒ “String” (STRING) 20.31.1 on page 2574

Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	delete	elt
empty	empty?	entries	entry?	eq?
eval	every?	fill!	find	first
hash	index?	indices	insert	latex
leftTrim	less?	lowerCase	lowerCase!	map
map!	match	match?	max	maxIndex
member?	members	merge	min	minIndex
more?	new	parts	prefix?	position
qelt	qsetelt!	reduce	remove	removeDuplicates
replace	reverse	reverse!	rightTrim	sample
select	setelt	size?	sort	sort!
sorted?	split	suffix?	substring?	swap!
trim	upperCase	upperCase!	#?	?<?
?<=?	?=?	?>?	?>=?	?~=?
?.?				

— domain ISTRING IndexedString —

```
)abbrev domain ISTRING IndexedString
++ Authors: Stephen Watt, Michael Monagan, Manuel Bronstein 1986 .. 1991
-- The following Lisp dependencies are divided into two groups
-- Those that are required
-- QENUM QESET QCSIZE MAKE-FULL-CVEC EQ QSLESSP QSGREATERP
-- Those that can are included for efficiency only
-- COPY STRCONC SUBSTRING STRPOS RPLACSTR DOWNCASE UPCASE CGREATERP
++ Description:
++ This domain implements low-level strings

IndexedString(mn:Integer): Export == Implementation where
  B ==> Boolean
  C ==> Character
  I ==> Integer
  N ==> NonNegativeInteger
  U ==> UniversalSegment Integer

  Export ==> StringAggregate() with
      hash: % -> I
        ++ hash(x) provides a hashing function for strings

  Implementation ==> add
    -- These assume Character's Rep is Small I
    Qelt    ==> QENUM$Lisp
    Qequal  ==> EQUAL$Lisp
    Qsetelt ==> QESET$Lisp
    Qsize   ==> QCSIZE$Lisp
    Cheq    ==> EQL$Lisp
    Chlt    ==> QSLESSP$Lisp
    Chgt    ==> QSGREATERP$Lisp

    c: Character
    cc: CharacterClass

--  new n                 == MAKE_-FULL_-CVEC(n, space$C)$Lisp
    new(n, c)             == MAKE_-FULL_-CVEC(n, c)$Lisp
    empty()               == MAKE_-FULL_-CVEC(0$Lisp)$Lisp
    empty?(s)             == Qsize(s) = 0
    #s                    == Qsize(s)
    s = t                 == Qequal(s, t)
    s < t                 == CGREATERP(t,s)$Lisp
    concat(s:%,t:%)       == STRCONC(s,t)$Lisp
    copy s                == COPY_-SEQ(s)$Lisp
    insert(s:%, t:%, i:I) == concat(concat(s(mn..i-1), t), s(i..))
    coerce(s:%):OutputForm == outputForm(s pretend String)
    minIndex s            == mn
    upperCase_! s         == map_!(upperCase, s)
```

```
lowerCase_! s          == map_!(lowerCase, s)

latex s             == concat("\mbox{``", concat(s pretend String, "''}"))

replace(s, sg, t) ==
  l := lo(sg) - mn
  m := #s
  n := #t
  h:I := if hasHi sg then hi(sg) - mn else maxIndex s - mn
  l < 0 or h >= m or h < l-1 => error "index out of range"
  r := new((m-(h-l+1)+n)::N, space$C)
  for k in 0.. for i in 0..l-1 repeat Qsetelt(r, k, Qelt(s, i))
  for k in k.. for i in 0..n-1 repeat Qsetelt(r, k, Qelt(t, i))
  for k in k.. for i in h+1..m-1 repeat Qsetelt(r, k, Qelt(s, i))
  r

setelt(s:%, i:I, c:C) ==
  i < mn or i > maxIndex(s) => error "index out of range"
  Qsetelt(s, i - mn, c)
  c

substring?(part, whole, startpos) ==
  np:I := Qsize part
  nw:I := Qsize whole
  (startpos := startpos - mn) < 0 => error "index out of bounds"
  np > nw - startpos => false
  for ip in 0..np-1 for iw in startpos.. repeat
      not Cheq(Qelt(part, ip), Qelt(whole, iw)) => return false
  true

position(s:%, t:%, startpos:I) ==
  (startpos := startpos - mn) < 0 => error "index out of bounds"
  startpos >= Qsize t => mn - 1
  r:I := STRPOS(s, t, startpos, NIL$Lisp)$Lisp
  EQ(r, NIL$Lisp)$Lisp => mn - 1
  r + mn

position(c: Character, t: %, startpos: I) ==
  (startpos := startpos - mn) < 0 => error "index out of bounds"
  startpos >= Qsize t => mn - 1
  for r in startpos..Qsize t - 1 repeat
      if Cheq(Qelt(t, r), c) then return r + mn
  mn - 1

position(cc: CharacterClass, t: %, startpos: I) ==
  (startpos := startpos - mn) < 0 => error "index out of bounds"
  startpos >= Qsize t => mn - 1
  for r in startpos..Qsize t - 1 repeat
      if member?(Qelt(t,r), cc) then return r + mn
  mn - 1
```

```
suffix?(s, t) ==
  (m := maxIndex s) > (n := maxIndex t) => false
  substring?(s, t, mn + n - m)

split(s, c) ==
  n := maxIndex s
  for i in mn..n while s.i = c repeat 0
  l := empty()$List(%)
  j:Integer -- j is conditionally intialized
  while i <= n and (j := position(c, s, i)) >= mn repeat
      l := concat(s(i..j-1), l)
      for i in j..n while s.i = c repeat 0
  if i <= n then l := concat(s(i..n), l)
  reverse_! l

split(s, cc) ==
  n := maxIndex s
  for i in mn..n while member?(s.i,cc) repeat 0
  l := empty()$List(%)
  j:Integer -- j is conditionally intialized
  while i <= n and (j := position(cc, s, i)) >= mn repeat
      l := concat(s(i..j-1), l)
      for i in j..n while member?(s.i,cc) repeat 0
  if i <= n then l := concat(s(i..n), l)
  reverse_! l

leftTrim(s, c) ==
  n := maxIndex s
  for i in mn .. n while s.i = c repeat 0
  s(i..n)

leftTrim(s, cc) ==
  n := maxIndex s
  for i in mn .. n while member?(s.i,cc) repeat 0
  s(i..n)

rightTrim(s, c) ==
  for j in maxIndex s .. mn by -1 while s.j = c repeat 0
  s(minIndex(s)..j)

rightTrim(s, cc) ==
  for j in maxIndex s .. mn by -1 while member?(s.j, cc) repeat 0
  s(minIndex(s)..j)

concat l ==
  t := new(+/[#s for s in l], space$C)
  i := mn
  for s in l repeat
      copyInto_!(t, s, i)
```

```
          i := i + #s
      t

    copyInto_!(y, x, s) ==
      m := #x
      n := #y
      s := s - mn
      s < 0 or s+m > n => error "index out of range"
      RPLACSTR(y, s, m, x, 0, m)$Lisp
      y

    elt(s:%, i:I) ==
      i < mn or i > maxIndex(s) => error "index out of range"
      Qelt(s, i - mn)

    elt(s:%, sg:U) ==
      l := lo(sg) - mn
      h := if hasHi sg then hi(sg) - mn else maxIndex s - mn
      l < 0 or h >= #s => error "index out of bound"
      SUBSTRING(s, l, max(0, h-l+1))$Lisp

    hash(s:$):Integer ==
      n:I := Qsize s
      zero? n => 0
--      one? n => ord(s.mn)
      (n = 1) => ord(s.mn)
      ord(s.mn) * ord s(mn+n-1) * ord s(mn + n quo 2)

    match(pattern,target,wildcard) ==
      stringMatch(pattern,target,CHARACTER(wildcard)$Lisp)$Lisp

    match?(pattern, target, dontcare) ==
      n := maxIndex pattern
      p := position(dontcare, pattern, m := minIndex pattern)::N
      p = m-1 => pattern = target
      (p ^= m) and not prefix?(pattern(m..p-1), target) => false
      i := p      -- index into target
      q := position(dontcare, pattern, p + 1)::N
      while q ^= m-1 repeat
         s := pattern(p+1..q-1)
         i := position(s, target, i)::N
         i = m-1 => return false
         i := i + #s
         p := q
         q := position(dontcare, pattern, q + 1)::N
      (p ^= n) and not suffix?(pattern(p+1..n), target) => false
      true
```

———-

— **ISTRING.dotabb** —

```
"ISTRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ISTRING",
          shape=ellipse]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"ISTRING" -> "FSAGG"
```

———-

10.15 domain IARRAY2 IndexedTwoDimensionalArray

An IndexedTwoDimensionalArray is a 2-dimensional array where the minimal row and column indices are parameters of the type. Rows and columns are returned as IndexedOneDimensionalArray's with minimal indices matching those of the IndexedTwoDimensionalArray. The index of the 'first' row may be obtained by calling the function 'minRowIndex'. The index of the 'first' column may be obtained by calling the function 'minColIndex'. The index of the first element of a 'Row' is the same as the index of the first column in an array and vice versa.

— **IndexedTwoDimensionalArray.input** —

```
)set break resume
)sys rm -f IndexedTwoDimensionalArray.output
)spool IndexedTwoDimensionalArray.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedTwoDimensionalArray
--R
--R IndexedTwoDimensionalArray(R: Type,mnRow: Integer,mnCol: Integer)  is a domain constructor
--R Abbreviation for IndexedTwoDimensionalArray is IARRAY2
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IARRAY2
--R
--R------------------------------ Operations --------------------------------
--R copy : % -> %                          elt : (%,Integer,Integer,R) -> R
--R elt : (%,Integer,Integer) -> R         empty : () -> %
--R empty? : % -> Boolean                  eq? : (%,%) -> Boolean
--R fill! : (%,R) -> %                     map : (((R,R) -> R),%,%,R) -> %
--R map : (((R,R) -> R),%,%) -> %          map : ((R -> R),%) -> %
--R map! : ((R -> R),%) -> %               maxColIndex : % -> Integer
--R maxRowIndex : % -> Integer             minColIndex : % -> Integer
--R minRowIndex : % -> Integer             ncols : % -> NonNegativeInteger
```

```
--R nrows : % -> NonNegativeInteger       parts : % -> List(R)
--R qelt : (%,Integer,Integer) -> R       sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if R has SETCAT
--R column : (%,Integer) -> IndexedOneDimensionalArray(R,mnRow)
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if R has SETCAT
--R latex : % -> String if R has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,NonNegativeInteger,R) -> %
--R qsetelt! : (%,Integer,Integer,R) -> R
--R row : (%,Integer) -> IndexedOneDimensionalArray(R,mnCol)
--R setColumn! : (%,Integer,IndexedOneDimensionalArray(R,mnRow)) -> %
--R setRow! : (%,Integer,IndexedOneDimensionalArray(R,mnCol)) -> %
--R setelt : (%,Integer,Integer,R) -> R
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— IndexedTwoDimensionalArray.help —

```
=====================================================================
IndexedTwoDimensionalArray examples
=====================================================================

See Also:
o )show IndexedTwoDimensionalArray
```

———-

10.15.1 IndexedTwoDimensionalArray (IARRAY2)



See

⇒ "InnerIndexedTwoDimensionalArray" (IIARRAY2) 10.23.1 on page 1258
⇒ "TwoDimensionalArray" (ARRAY2) 21.13.1 on page 2732

Exports:

any?	coerce	column	copy	count
count	elt	empty	empty?	eq?
eval	every?	fill!	hash	latex
less?	maxColIndex	maxRowIndex	map	map!
member?	members	minColIndex	minRowIndex	more?
ncols	new	nrows	parts	qelt
qsetelt!	row	sample	setColumn!	setRow!
setelt	size?	#?	?=?	?~=?

— domain IARRAY2 IndexedTwoDimensionalArray —

```
)abbrev domain IARRAY2 IndexedTwoDimensionalArray
++ Author: Mark Botch
++ Description:
++ This domain implements two dimensional arrays

IndexedTwoDimensionalArray(R,mnRow,mnCol):Exports == Implementation where
  R : Type
  mnRow, mnCol : Integer
  Row ==> IndexedOneDimensionalArray(R,mnCol)
  Col ==> IndexedOneDimensionalArray(R,mnRow)

  Exports ==> TwoDimensionalArrayCategory(R,Row,Col)

  Implementation ==>
    InnerIndexedTwoDimensionalArray(R,mnRow,mnCol,Row,Col)
```

———-

— IARRAY2.dotabb —

```
"IARRAY2" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IARRAY2"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"ARR2CAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ARR2CAT"]
"IARRAY2" -> "ARR2CAT"
"IARRAY2" -> "A1AGG"
```

———-

10.16 domain IVECTOR IndexedVector

— IndexedVector.input —

```
)set break resume
)sys rm -f IndexedVector.output
)spool IndexedVector.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IndexedVector
--R
--R IndexedVector(R: Type,mn: Integer)  is a domain constructor
--R Abbreviation for IndexedVector is IVECTOR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IVECTOR
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if R has ABELGRP          concat : List(%) -> %
--R concat : (%,%) -> %                   concat : (R,%) -> %
--R concat : (%,R) -> %                   construct : List(R) -> %
--R copy : % -> %                         delete : (%,Integer) -> %
--R ?.? : (%,Integer) -> R                elt : (%,Integer,R) -> R
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(R)                eq? : (%,%) -> Boolean
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
--R insert : (%,%,Integer) -> %           insert : (R,%,Integer) -> %
--R map : (((R,R) -> R),%,%) -> %         map : ((R -> R),%) -> %
--R new : (NonNegativeInteger,R) -> %     qelt : (%,Integer) -> R
--R reverse : % -> %                      sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (%,R) -> % if R has MONOID
--R ?*? : (R,%) -> % if R has MONOID
```

```
--R ?*? : (Integer,%) -> % if R has ABELGRP
--R ?+? : (%,%) -> % if R has ABELSG
--R ?-? : (%,%) -> % if R has ABELGRP
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if R has SETCAT
--R convert : % -> InputForm if R has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R cross : (%,%) -> % if R has RING
--R delete : (%,UniversalSegment(Integer)) -> %
--R dot : (%,%) -> R if R has RING
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,R) -> % if $ has shallowlyMutable
--R find : ((R -> Boolean),%) -> Union(R,"failed")
--R first : % -> R if Integer has ORDSET
--R hash : % -> SingleInteger if R has SETCAT
--R latex : % -> String if R has SETCAT
--R length : % -> R if R has RADCAT and R has RING
--R less? : (%,NonNegativeInteger) -> Boolean
--R magnitude : % -> R if R has RADCAT and R has RING
--R map! : ((R -> R),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if R has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R merge : (%,%) -> % if R has ORDSET
--R merge : (((R,R) -> Boolean),%,%) -> %
--R min : (%,%) -> % if R has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R outerProduct : (%,%) -> Matrix(R) if R has RING
--R parts : % -> List(R) if $ has finiteAggregate
--R position : (R,%,Integer) -> Integer if R has SETCAT
--R position : (R,%) -> Integer if R has SETCAT
--R position : ((R -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,R) -> R if $ has shallowlyMutable
--R reduce : (((R,R) -> R),%) -> R if $ has finiteAggregate
--R reduce : (((R,R) -> R),%,R) -> R if $ has finiteAggregate
```

```
--R reduce : (((R,R) -> R),%,R,R) -> R if $ has finiteAggregate and R has SETCAT
--R remove : ((R -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (R,%) -> % if $ has finiteAggregate and R has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and R has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((R -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),R) -> R if $ has shallowlyMutable
--R setelt : (%,Integer,R) -> R if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if R has ORDSET
--R sort : (((R,R) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and R has ORDSET
--R sort! : (((R,R) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if R has ORDSET
--R sorted? : (((R,R) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R zero : NonNegativeInteger -> % if R has ABELMON
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— IndexedVector.help —

```
=====================================================================
IndexedVector examples
=====================================================================

See Also:
o )show IndexedVector
```

———-

10.16.1 IndexedVector (IVECTOR)



Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	cross	delete
dot	elt	empty	empty?	entries
entry?	eq?	eval	every?	fill!
find	first	hash	index?	indices
insert	latex	length	less?	magnitude
map!	max	maxIndex	member?	members
merge	min	minIndex	more?	new
outerProduct	parts	position	qelt	qsetelt!
reduce	remove	removeDuplicates	reverse	reverse!
sample	select	setelt	size?	sort
sort!	sorted?	swap!	zero	#?
?*?	?+?	?-?	?<?	?<=?
?=?	?>?	?>=?	?~=?	-?
?.?				

— domain IVECTOR IndexedVector —

```
)abbrev domain IVECTOR IndexedVector
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors: Vector, DirectProduct
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type represents vector like objects with varying lengths
++ and a user-specified initial index.

IndexedVector(R:Type, mn:Integer):
```

```
  VectorCategory R == IndexedOneDimensionalArray(R, mn)
```

———-

— **IVECTOR.dotabb** —

```
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"VECTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=VECTCAT"]
"IVECTOR" -> "VECTCAT"
```

———-

10.17 domain ITUPLE InfiniteTuple

— **InfiniteTuple.input** —

```
)set break resume
)sys rm -f InfiniteTuple.output
)spool InfiniteTuple.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InfiniteTuple
--R
--R InfiniteTuple(S: Type)  is a domain constructor
--R Abbreviation for InfiniteTuple is ITUPLE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ITUPLE
--R
--R------------------------------ Operations ------------------------------
--R coerce : % -> OutputForm              construct : % -> Stream(S)
--R generate : ((S -> S),S) -> %          map : ((S -> S),%) -> %
--R select : ((S -> Boolean),%) -> %
--R filterUntil : ((S -> Boolean),%) -> %
--R filterWhile : ((S -> Boolean),%) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **InfiniteTuple.help** —

```
====================================================================
InfiniteTuple examples
====================================================================

See Also:
o )show InfiniteTuple
```

———-

10.17.1 InfiniteTuple (ITUPLE)



Exports:
coerce construct filterUntil filterWhile generate map select

— **domain ITUPLE InfiniteTuple** —

```
)abbrev domain ITUPLE InfiniteTuple
++ Author: Clifton J. Williamson
++ Date Created: 16 February 1990
++ Date Last Updated: 16 February 1990
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This package implements 'infinite tuples' for the interpreter.
++ The representation is a stream.

InfiniteTuple(S:Type): Exports == Implementation where

  Exports ==> CoercibleTo OutputForm with
    map: (S -> S, %) -> %
```

```
      ++ map(f,t) replaces the tuple t
      ++ by \spad{[f(x) for x in t]}.
    filterWhile: (S -> Boolean, %) -> %
      ++ filterWhile(p,t) returns \spad{[x for x in t while p(x)]}.
    filterUntil: (S -> Boolean, %) -> %
      ++ filterUntil(p,t) returns \spad{[x for x in t while not p(x)]}.
    select: (S -> Boolean, %) -> %
      ++ select(p,t) returns \spad{[x for x in t | p(x)]}.
    generate: (S -> S,S) -> %
      ++ generate(f,s) returns \spad{[s,f(s),f(f(s)),...]}.
    construct: % -> Stream S
      ++ construct(t) converts an infinite tuple to a stream.

  Implementation ==> Stream S add
    generate(f,x) == generate(f,x)$Stream(S) pretend %
    filterWhile(f, x) == filterWhile(f,x pretend Stream(S))$Stream(S) pretend %
    filterUntil(f, x) == filterUntil(f,x pretend Stream(S))$Stream(S) pretend %
    select(f, x) == select(f,x pretend Stream(S))$Stream(S) pretend %
    construct x == x pretend Stream(S)
--    coerce x ==
--      coerce(x)$Stream(S)
```

———-

— ITUPLE.dotabb —

```
"ITUPLE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ITUPLE"]
"TYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TYPE"]
"ITUPLE" -> "TYPE"
```

———-

10.18 domain INFCLSPT InfinitlyClosePoint

— InfinitlyClosePoint.input —

```
)set break resume
)sys rm -f InfinitlyClosePoint.output
)spool InfinitlyClosePoint.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show InfinitlyClosePoint
--R InfinitlyClosePoint(K: Field,symb: List Symbol,PolyRing: PolynomialCategory(K,E,OrderedVariableList symb
--R Abbreviation for InfinitlyClosePoint is INFCLSPT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INFCLSPT
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                actualExtensionV : % -> K
--R chartV : % -> BLMET                   coerce : % -> OutputForm
--R create : (ProjPt,PolyRing) -> %       degree : % -> PositiveInteger
--R excpDivV : % -> DIVISOR               fullOut : % -> OutputForm
--R fullOutput : () -> Boolean            fullOutput : Boolean -> Boolean
--R hash : % -> SingleInteger             latex : % -> String
--R localParamV : % -> List PCS           localPointV : % -> AffinePlane K
--R multV : % -> NonNegativeInteger       pointV : % -> ProjPt
--R setchart! : (%,BLMET) -> BLMET        setpoint! : (%,ProjPt) -> ProjPt
--R symbNameV : % -> Symbol               ?~=? : (%,%) -> Boolean
--R create : (ProjPt,DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],K),AffinePlane K,NonNegativ
--R curveV : % -> DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],K)
--R setcurve! : (%,DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],K)) -> DistributedMultivariat
--R setexcpDiv! : (%,DIVISOR) -> DIVISOR
--R setlocalParam! : (%,List PCS) -> List PCS
--R setlocalPoint! : (%,AffinePlane K) -> AffinePlane K
--R setmult! : (%,NonNegativeInteger) -> NonNegativeInteger
--R setsubmult! : (%,NonNegativeInteger) -> NonNegativeInteger
--R setsymbName! : (%,Symbol) -> Symbol
--R subMultV : % -> NonNegativeInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— InfinitlyClosePoint.help —

```
=====================================================================
InfinitlyClosePoint examples
=====================================================================

See Also:
o )show InfinitlyClosePoint
```

———-

10.18.1 InfinitlyClosePoint (INFCLSPT)



Exports:

?=?	?~=?	actualExtensionV
chartV	coerce	create
curveV	degree	excpDivV
fullOut	fullOutput	fullOutput
hash	latex	localParamV
localPointV	multV	pointV
setchart!	setcurve!	setexcpDiv!
setlocalParam!	setlocalPoint!	setmult!
setpoint!	setsubmult!	setsymbName!
subMultV	symbNameV	

— domain INFCLSPT InfinitlyClosePoint —

```
)abbrev domain INFCLSPT InfinitlyClosePoint
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain is part of the PAFF package
InfinitlyClosePoint(K,symb,PolyRing,E,ProjPt,PCS,Plc,DIVISOR,BLMET):Exports == Implementation wh
  K:Field
  symb: List Symbol
  E:DirectProductCategory(#symb,NonNegativeInteger)
  OV ==> OrderedVariableList(symb)
  PolyRing:  PolynomialCategory(K,E,OV)

  bls      ==> ['X,'Y]
  BlUpRing ==> DistributedMultivariatePolynomial(bls , K)
  E2       ==> DirectProduct( #bls , NonNegativeInteger )
  outRec   ==> Record(name:Symbol,mult:NonNegativeInteger)
  AFP      ==> AffinePlane(K)
  OV2      ==> OrderedVariableList( bls )

  PCS: LocalPowerSeriesCategory(K)
```

```
ProjPt:ProjectiveSpaceCategory(K)
Plc: PlacesCategory(K,PCS)
DIVISOR: DivisorCategory(Plc)
BLMET : BlowUpMethodCategory

bigoutRecBLQT ==> Record(dominate:ProjPt,_
                     name:Symbol,_
                     mult:NonNegativeInteger,_
                     defCurve:BlUpRing,_
                     localPoint:AFP,_
                     chart:BLMET,_
                     expD:DIVISOR)

bigoutRecHN  ==> Record(dominate:ProjPt,_
                     name:Symbol,_
                     mult:NonNegativeInteger,_
                     defCurve:BlUpRing,_
                     localPoint:AFP,_
                     chart:BLMET,_
                     subMultip: NonNegativeInteger,_
                     expD:DIVISOR)


representation   ==>  Record(point:ProjPt,_
                             curve:BlUpRing,_
                             localPoint:AFP,_
                             mult:NonNegativeInteger,_
                             chrt:BLMET,_
                             subMultiplicity:NonNegativeInteger,_
                             excpDiv:DIVISOR,_
                             localParam:List(PCS),_
                             actualExtension:K,_
                             symbName:Symbol)


Exports == InfinitlyClosePointCategory(K,symb,PolyRing,E,ProjPt,PCS,Plc,DIVISOR,BLMET) with

  fullOut: % -> OutputForm
    ++ fullOut(tr) yields a full output of tr (see function fullOutput).

  fullOutput: Boolean -> Boolean
    ++ fullOutput(b) sets a flag such that when true, a coerce to
    ++ OutputForm yields the full output of tr, otherwise encode(tr) is
    ++ output (see encode function). The default is false.

  fullOutput: () -> Boolean
    ++ fullOutput returns the value of the flag set by fullOutput(b).

Implementation == representation add
  Rep := representation
```

```
polyRing2BiRing: (PolyRing, Integer) -> BlUpRing
polyRing2BiRing(pol,nV)==
  zero? pol => 0$BlUpRing
  d:= degree pol
  lc:= leadingCoefficient pol
  dd: List NonNegativeInteger := entries d
  ddr:=vector([dd.i for i in 1..#dd | ^(i=nV)])$Vector(NonNegativeInteger)
  ddre:E2 := directProduct( ddr )$E2
  monomial(lc,ddre)$BlUpRing  + polyRing2BiRing( reductum pol , nV )

projPt2affPt: (ProjPt, Integer) -> AFP
projPt2affPt(pt,nV)==
  ll:= pt :: List(K)
  l:= [ ll.i for i in 1..#ll | ^(i = nV )]
  affinePoint( l)

fullOut(a)==
  oo: bigoutRecBLQT
  oo2: bigoutRecHN
  BLMET has BlowUpWithQuadTrans =>
    oo:=  [ pointV(a), symbNameV(a), multV(a), curveV(a), _
          localPointV(a), chartV(a),  excpDivV(a) ]$bigoutRecBLQT
    oo :: OutputForm
  BLMET has BlowUpWithHamburgerNoether =>
    oo2:=  [ pointV(a), symbNameV(a), multV(a), curveV(a), _
          localPointV(a), chartV(a), subMultV(a), excpDivV(a) ]$bigoutRecHN
    oo2 :: OutputForm

fullOutputFlag:Boolean:=false()

fullOutput(f)== fullOutputFlag:=f

fullOutput == fullOutputFlag

coerce(a:%):OutputForm==
  fullOutput() => fullOut(a)
  oo:outRec:= [ symbNameV(a) , multV(a) ]$outRec
  oo :: OutputForm

degree(a)==
  K has PseudoAlgebraicClosureOfPerfectFieldCategory  => extDegree actualExtensionV a
  1

create(pointA,curveA,localPointA,multA,chartA,subM,excpDivA,atcL,aName)==  -- CHH
  ([pointA,curveA,localPointA,multA,chartA,subM,excpDivA,empty()$List(PCS),atcL,aName]$Rep):

create(pointA,curveA)==
  nV := lastNonNul pointA
  localPointA := projPt2affPt(pointA,nV)
```

```
    multA:NonNegativeInteger:=0$NonNegativeInteger
    chartA:BLMET
    if BLMET has QuadraticTransform then chartA:=( [0,0, nV] :: List Integer ) :: BLMET   -- CHH
    if BLMET has HamburgerNoether then
      chartA := createHN( 0,0,nV,0,0,true,"right")   -- A changer le "right"
    excpDivA:DIVISOR:= 0$DIVISOR
    actL:K:=definingField pointA
    aName:Symbol:=new(P)$Symbol
    affCurvA : BlUpRing := polyRing2BiRing(curveA,nV)
    create(pointA,affCurvA,localPointA,multA,chartA,0$NonNegativeInteger,excpDivA,actL,aName)

  subMultV(a:%)== (a:Rep)(subMultiplicity)

  setsubmult_!(a:%,sm:NonNegativeInteger)== (a:Rep)(subMultiplicity) := sm

  pointV(a:%)     ==(a:Rep)(point)

  symbNameV(a:%)     ==(a:Rep)(symbName)

  curveV(a:%)  ==(a:Rep)(curve)

  localPointV(a:%)   ==(a:Rep)(localPoint)

  multV(a:%)    ==(a:Rep)(mult)

  chartV(a:%)   ==(a:Rep)(chrt)  -- CHH

  excpDivV(a:%) ==(a:Rep)(excpDiv)

  localParamV(a:%) ==(a:Rep)(localParam)

  actualExtensionV(a:%) == (a:Rep)(actualExtension)

  setpoint_!(a:%,n:ProjPt)       ==(a:Rep)(point):=n

  setcurve_!(a:%,n:BlUpRing)   ==(a:Rep)(curve):=n

  setlocalPoint_!(a:%,n:AFP)  ==(a:Rep)(localPoint):=n

  setmult_!(a:%,n:NonNegativeInteger)         ==(a:Rep)(mult):=n

  setchart_!(a:%,n:BLMET)  ==(a:Rep)(chrt):=n  -- CHH

  setlocalParam_!(a:%,n:List(PCS)) ==(a:Rep)(localParam):=n

  setexcpDiv_!(a:%,n:DIVISOR) ==(a:Rep)(excpDiv):=n

  setsymbName_!(a:%,n:Symbol) ==(a:Rep)(symbName):=n
```

———-

— **INFCLSPT.dotabb** —

```
"INFCLSPT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INFCLSPT"]
"INFCLCT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=INFCLCT"]
"INFCLSPT" -> "INFCLCT"
```

———-

10.19 domain INFCLSPS InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField

— **InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField.input** —

```
)set break resume
)sys rm -f InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField.output
)spool InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField
--R InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField(K: FiniteFieldCategory,symb: List
--R Abbreviation for InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField is INFCLSPS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INFCLSPS
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                chartV : % -> BLMET
--R coerce : % -> OutputForm              degree : % -> PositiveInteger
--R fullOut : % -> OutputForm             fullOutput : () -> Boolean
--R fullOutput : Boolean -> Boolean       hash : % -> SingleInteger
--R latex : % -> String                   multV : % -> NonNegativeInteger
--R setchart! : (%,BLMET) -> BLMET        symbNameV : % -> Symbol
--R ?~=? : (%,%) -> Boolean
--R actualExtensionV : % -> PseudoAlgebraicClosureOfFiniteField K
--R create : (ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField K,DistributedMultivariatePo
--R create : (ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField K,DistributedMultivariatePo
--R curveV : % -> DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],PseudoAlgebraicClo
--R excpDivV : % -> Divisor PlacesOverPseudoAlgebraicClosureOfFiniteField K
--R localParamV : % -> List NeitherSparseOrDensePowerSeries PseudoAlgebraicClosureOfFiniteField
--R localPointV : % -> AffinePlane PseudoAlgebraicClosureOfFiniteField K
```

```
--R pointV : % -> ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField K
--R setcurve! : (%,DistributedMultivariatePolynomial([construct,QUOTEX,QUOTEY],PseudoAlgebraicClosureOfFinit
--R setexcpDiv! : (%,Divisor PlacesOverPseudoAlgebraicClosureOfFiniteField K) -> Divisor PlacesOverPseudoAlg
--R setlocalParam! : (%,List NeitherSparseOrDensePowerSeries PseudoAlgebraicClosureOfFiniteField K) -> List
--R setlocalPoint! : (%,AffinePlane PseudoAlgebraicClosureOfFiniteField K) -> AffinePlane PseudoAlgebraicClo
--R setmult! : (%,NonNegativeInteger) -> NonNegativeInteger
--R setpoint! : (%,ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField K) -> ProjectivePlaneOverPseudoAlg
--R setsubmult! : (%,NonNegativeInteger) -> NonNegativeInteger
--R setsymbName! : (%,Symbol) -> Symbol
--R subMultV : % -> NonNegativeInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— **InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField.help**
—

```
=====================================================================
InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField examples
=====================================================================

See Also:
o )show InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField
```

———-

10.19.1 InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField (INFCLSPS)



Exports:

?=?	?~=?	actualExtensionV
chartV	coerce	create
curveV	degree	excpDivV
fullOut	fullOutput	hash
latex	localParamV	localPointV
multV	pointV	setchart!
setcurve!	setexcpDiv!	setlocalParam!
setlocalPoint!	setmult!	setpoint!
setsubmult!	setsymbName!	subMultV
symbNameV		

— **domain INFCLSPS InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField** —

```
)abbrev domain INFCLSPS InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain is part of the PAFF package
InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField(K,symb,BLMET):_
 Exports == Implementation where

  K:FiniteFieldCategory
  symb: List Symbol
  BLMET : BlowUpMethodCategory

  E           ==> DirectProduct(#symb,NonNegativeInteger)
  KK          ==> PseudoAlgebraicClosureOfFiniteField(K)
  PolyRing    ==> DistributedMultivariatePolynomial(symb,KK)
  ProjPt      ==> ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField(K)
  PCS         ==> NeitherSparseOrDensePowerSeries(KK)
  Plc         ==> PlacesOverPseudoAlgebraicClosureOfFiniteField(K)
  DIVISOR     ==> Divisor(Plc)

  Exports == InfinitlyClosePointCategory(KK,symb,PolyRing,E,ProjPt,_
                                         PCS,Plc,DIVISOR,BLMET) with

    fullOut: % -> OutputForm
      ++ fullOut(tr) yields a full output of tr (see function fullOutput).

    fullOutput: Boolean -> Boolean

      ++ fullOutput(b) sets a flag such that when true, a coerce to OutputForm
      ++  yields the full output of tr, otherwise encode(tr) is output
      ++ (see encode function). The default is false.

    fullOutput: () -> Boolean
```

```
      ++ fullOutput returns the value of the flag set by fullOutput(b).

  Implementation == InfinitlyClosePoint(KK,symb,PolyRing,E,ProjPt,_
                                        PCS,Plc,DIVISOR,BLMET)
```

———-

— **INFCLSPS.dotabb** —

```
"INFCLSPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INFCLSPS"]
"PROJPLPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PROJPLPS"]
"INFCLSPS" -> "PROJPLPS"
```

———-

10.20 domain IAN InnerAlgebraicNumber

— **InnerAlgebraicNumber.input** —

```
)set break resume
)sys rm -f InnerAlgebraicNumber.output
)spool InnerAlgebraicNumber.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerAlgebraicNumber
--R
--R InnerAlgebraicNumber  is a domain constructor
--R Abbreviation for InnerAlgebraicNumber is IAN
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IAN
--R
--R------------------------------- Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?*? : (Integer,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?**? : (%,PositiveInteger) -> %
--R ?**? : (%,Integer) -> %               ?+? : (%,%) -> %
--R -? : % -> %                           ?-? : (%,%) -> %
--R ?/? : (%,%) -> %                      ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R D : % -> %                            D : (%,NonNegativeInteger) -> %
--R 1 : () -> %                           0 : () -> %
```

```
--R ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean
--R box : List(%) -> %
--R coerce : Integer -> %
--R coerce : Fraction(Integer) -> %
--R coerce : % -> OutputForm
--R convert : % -> DoubleFloat
--R differentiate : % -> %
--R distribute : % -> %
--R elt : (BasicOperator,%) -> %
--R eval : (%,Equation(%)) -> %
--R factor : % -> Factored(%)
--R freeOf? : (%,%) -> Boolean
--R gcd : List(%) -> %
--R height : % -> NonNegativeInteger
--R is? : (%,Symbol) -> Boolean
--R kernels : % -> List(Kernel(%))
--R lcm : (%,%) -> %
--R max : (%,%) -> %
--R norm : (%,List(Kernel(%))) -> %
--R nthRoot : (%,Integer) -> %
--R paren : List(%) -> %
--R prime? : % -> Boolean
--R recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %
--R retract : % -> Integer
--R rootOf : Polynomial(%) -> %
--R sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)
--R subst : (%,Equation(%)) -> %
--R trueEqual : (%,%) -> Boolean
--R unitCanonical : % -> %
--R zeroOf : Polynomial(%) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?**? : (%,Fraction(Integer)) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coerce : SparseMultivariatePolynomial(Integer,Kernel(%)) -> %
--R definingPolynomial : % -> % if $ has RING
--R denom : % -> SparseMultivariatePolynomial(Integer,Kernel(%))
--R differentiate : (%,NonNegativeInteger) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R elt : (BasicOperator,List(%)) -> %
--R elt : (BasicOperator,%,%,%,%) -> %
--R elt : (BasicOperator,%,%,%) -> %
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,BasicOperator,(% -> %)) -> %
--R eval : (%,BasicOperator,(List(%) -> %)) -> %
--R eval : (%,List(BasicOperator),List((List(%) -> %))) -> %
--R ?^? : (%,Integer) -> %
--R belong? : BasicOperator -> Boolean
--R box : % -> %
--R coerce : % -> %
--R coerce : Kernel(%) -> %
--R convert : % -> Complex(Float)
--R convert : % -> Float
--R distribute : (%,%) -> %
--R elt : (BasicOperator,%,%) -> %
--R eval : (%,%,%) -> %
--R eval : (%,Kernel(%),%) -> %
--R freeOf? : (%,Symbol) -> Boolean
--R gcd : (%,%) -> %
--R hash : % -> SingleInteger
--R inv : % -> %
--R kernel : (BasicOperator,%) -> %
--R latex : % -> String
--R lcm : List(%) -> %
--R min : (%,%) -> %
--R norm : (%,Kernel(%)) -> %
--R one? : % -> Boolean
--R paren : % -> %
--R ?quo? : (%,%) -> %
--R reduce : % -> %
--R retract : % -> Fraction(Integer)
--R retract : % -> Kernel(%)
--R sample : () -> %
--R sqrt : % -> %
--R squareFreePart : % -> %
--R tower : % -> List(Kernel(%))
--R unit? : % -> Boolean
--R zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
```

```
--R eval : (%,List(BasicOperator),List((% -> %))) -> %
--R eval : (%,Symbol,(% -> %)) -> %
--R eval : (%,Symbol,(List(%) -> %)) -> %
--R eval : (%,List(Symbol),List((List(%) -> %))) -> %
--R eval : (%,List(Symbol),List((% -> %))) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R eval : (%,List(Kernel(%)),List(%)) -> %
--R even? : % -> Boolean if $ has RETRACT(INT)
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R is? : (%,BasicOperator) -> Boolean
--R kernel : (BasicOperator,List(%)) -> %
--R mainKernel : % -> Union(Kernel(%),"failed")
--R map : ((% -> %),Kernel(%)) -> %
--R minPoly : Kernel(%) -> SparseUnivariatePolynomial(%) if $ has RING
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R norm : (SparseUnivariatePolynomial(%),List(Kernel(%))) -> SparseUnivariatePolynomial(%)
--R norm : (SparseUnivariatePolynomial(%),Kernel(%)) -> SparseUnivariatePolynomial(%)
--R numer : % -> SparseMultivariatePolynomial(Integer,Kernel(%))
--R odd? : % -> Boolean if $ has RETRACT(INT)
--R operator : BasicOperator -> BasicOperator
--R operators : % -> List(BasicOperator)
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R reducedSystem : Matrix(%) -> Matrix(Fraction(Integer))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Fraction(Integer)),vec: Vector(Fraction(Inte
--R reducedSystem : Matrix(%) -> Matrix(Integer)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer))
--R retractIfCan : % -> Union(Fraction(Integer),"failed")
--R retractIfCan : % -> Union(Integer,"failed")
--R retractIfCan : % -> Union(Kernel(%),"failed")
--R rootOf : SparseUnivariatePolynomial(%) -> %
--R rootOf : (SparseUnivariatePolynomial(%),Symbol) -> %
--R rootsOf : Polynomial(%) -> List(%)
--R rootsOf : SparseUnivariatePolynomial(%) -> List(%)
--R rootsOf : (SparseUnivariatePolynomial(%),Symbol) -> List(%)
--R subst : (%,List(Kernel(%)),List(%)) -> %
--R subst : (%,List(Equation(%))) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R zeroOf : SparseUnivariatePolynomial(%) -> %
--R zeroOf : (SparseUnivariatePolynomial(%),Symbol) -> %
--R zerosOf : Polynomial(%) -> List(%)
--R zerosOf : SparseUnivariatePolynomial(%) -> List(%)
--R zerosOf : (SparseUnivariatePolynomial(%),Symbol) -> List(%)
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **InnerAlgebraicNumber.help** —

```
==========================================================================
InnerAlgebraicNumber examples
==========================================================================

See Also:
o )show InnerAlgebraicNumber
```

———-

10.20.1 InnerAlgebraicNumber (IAN)



See

⇒ “AlgebraicNumber” (AN) 2.6.1 on page 35

Exports:

0	1	associates?	belong?
box	characteristic	coerce	convert
D	definingPolynomial	denom	differentiate
distribute	divide	elt	euclideanSize
eval	even?	expressIdealMember	exquo
extendedEuclidean	factor	freeOf?	gcd
gcdPolynomial	hash	height	inv
is?	kernel	kernels	latex
lcm	mainKernel	map	max
min	minPoly	multiEuclidean	norm
nthRoot	numer	odd?	one?
operator	operators	paren	prime?
principalIdeal	recip	reduce	reducedSystem
retract	retractIfCan	rootOf	rootsOf
sample	sizeLess?	sqrt	squareFree
squareFreePart	subst	subtractIfCan	tower
trueEqual	unit?	unitCanonical	unitNormal
zero?	zeroOf	zerosOf	?*?
?**?	?+?	-?	?-?
?/?	?<?	?<=?	?=?
?>?	?>=?	?^?	?~=?
?*?	?**?	?quo?	?rem?

— domain IAN InnerAlgebraicNumber —

```
)abbrev domain IAN InnerAlgebraicNumber
++ Author: Manuel Bronstein
++ Date Created: 22 March 1988
++ Date Last Updated: 4 October 1995 (JHD)
++ Keywords: algebraic, number.
++ Description:
++ Algebraic closure of the rational numbers.

InnerAlgebraicNumber(): Exports == Implementation where
  Z   ==> Integer
  FE  ==> Expression Z
  K   ==> Kernel %
  P   ==> SparseMultivariatePolynomial(Z, K)
  ALGOP ==> "%alg"
  SUP ==>  SparseUnivariatePolynomial

  Exports ==> Join(ExpressionSpace, AlgebraicallyClosedField,
                   RetractableTo Z, RetractableTo Fraction Z,
                   LinearlyExplicitRingOver Z, RealConstant,
                   LinearlyExplicitRingOver Fraction Z,
                   CharacteristicZero,
                   ConvertibleTo Complex Float, DifferentialRing) with
```

```
    coerce : P -> %
      ++ coerce(p) returns p viewed as an algebraic number.
    numer  : % -> P
      ++ numer(f) returns the numerator of f viewed as a
      ++ polynomial in the kernels over Z.
    denom  : % -> P
      ++ denom(f) returns the denominator of f viewed as a
      ++ polynomial in the kernels over Z.
    reduce : % -> %
      ++ reduce(f) simplifies all the unreduced algebraic numbers
      ++ present in f by applying their defining relations.
    trueEqual : (%,%) -> Boolean
      ++ trueEqual(x,y) tries to determine if the two numbers are equal
    norm : (SUP(%),Kernel %) -> SUP(%)
      ++ norm(p,k) computes the norm of the polynomial p
      ++ with respect to the extension generated by kernel k
    norm : (SUP(%),List Kernel %) -> SUP(%)
      ++ norm(p,l) computes the norm of the polynomial p
      ++ with respect to the extension generated by kernels l
    norm : (%,Kernel %) -> %
      ++ norm(f,k) computes the norm of the algebraic number f
      ++ with respect to the extension generated by kernel k
    norm : (%,List Kernel %) -> %
      ++ norm(f,l) computes the norm of the algebraic number f
      ++ with respect to the extension generated by kernels l
  Implementation ==> FE add

    Rep := FE

    -- private
    mainRatDenom(f:%):% ==
       ratDenom(f::Rep::FE)$AlgebraicManipulations(Integer, FE)::Rep::%
--        mv:= mainVariable denom f
--        mv case "failed" => f
--        algv:=mv::K
--       q:=univariate(f, algv, minPoly(algv))_
--       $PolynomialCategoryQuotientFunctions(IndexedExponents K,K,Integer,P,%)
--       q(algv::%)

    findDenominator(z:SUP %):Record(num:SUP %,den:%) ==
       zz:=z
       while not(zz=0) repeat
          dd:=(denom leadingCoefficient zz)::%
          not(dd=1) =>
             rec:=findDenominator(dd*z)
             return [rec.num,rec.den*dd]
          zz:=reductum zz
       [z,1]
    makeUnivariate(p:P,k:Kernel %):SUP % ==
      map(x+->x::%,univariate(p,k))$SparseUnivariatePolynomialFunctions2(P,%)
```

```
    -- public
    a,b:%
    differentiate(x:%):% == 0
    zero? a == zero? numer a
--    one? a == one? numer a and one? denom a
    one? a == (numer a = 1) and (denom a = 1)
    x:% / y:%        == mainRatDenom(x /$Rep y)
    x:% ** n:Integer ==
      n < 0 => mainRatDenom (x **$Rep n)
      x **$Rep n
    trueEqual(a,b) ==
       -- if two algebraic numbers have the same norm (after deleting repeated
       -- roots, then they are certainly conjugates. Note that we start with a
       -- monic polynomial, so don't have to check for constant factors.
       -- this will be fooled by sqrt(2) and -sqrt(2), but the = in
       -- AlgebraicNumber knows what to do about this.
       ka:=reverse tower a
       kb:=reverse tower b
       empty? ka and empty? kb => retract(a)@Fraction Z = retract(b)@Fraction Z
       pa,pb:SparseUnivariatePolynomial %
       pa:=monomial(1,1)-monomial(a,0)
       pb:=monomial(1,1)-monomial(b,0)
       na:=map(retract,norm(pa,ka))_
         $SparseUnivariatePolynomialFunctions2(%,Fraction Z)
       nb:=map(retract,norm(pb,kb))_
         $SparseUnivariatePolynomialFunctions2(%,Fraction Z)
       (sa:=squareFreePart(na)) = (sb:=squareFreePart(nb)) => true
       g:=gcd(sa,sb)
       (dg:=degree g) = 0 => false
       -- of course, if these have a factor in common, then the
       -- answer is really ambiguous, so we ought to be using Duval-type
       -- technology
       dg = degree sa or dg = degree sb => true
       false
    norm(z:%,k:Kernel %): % ==
       p:=minPoly k
       n:=makeUnivariate(numer z,k)
       d:=makeUnivariate(denom z,k)
       resultant(n,p)/resultant(d,p)
    norm(z:%,l:List Kernel %): % ==
       for k in l repeat
           z:=norm(z,k)
       z
    norm(z:SUP %,k:Kernel %):SUP % ==
       p:=map(x +-> x::SUP %,minPoly k)_
         $SparseUnivariatePolynomialFunctions2(%,SUP %)
       f:=findDenominator z
       zz:=map(x +-> makeUnivariate(numer x,k),f.num)_
         $SparseUnivariatePolynomialFunctions2( %,SUP %)
       zz:=swap(zz)$CommuteUnivariatePolynomialCategory(%,SUP %,SUP SUP %)
```

```
       resultant(p,zz)/norm(f.den,k)
    norm(z:SUP %,l:List Kernel %): SUP % ==
       for k in l repeat
           z:=norm(z,k)
       z
    belong? op           == belong?(op)$ExpressionSpace_&(%) or has?(op, ALGOP)

    convert(x:%):Float ==
      retract map(y +-> y::Float, x pretend FE)$ExpressionFunctions2(Z,Float)

    convert(x:%):DoubleFloat ==
      retract map(y +-> y::DoubleFloat,x pretend FE)_
        $ExpressionFunctions2(Z, DoubleFloat)

    convert(x:%):Complex(Float) ==
      retract map(y +-> y::Complex(Float),x pretend FE)_
        $ExpressionFunctions2(Z, Complex Float)
```

———-

— IAN.dotabb —

```
"IAN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IAN"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"COMPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=COMPCAT"]
"ACF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACF"]
"IAN" -> "ACF"
"IAN" -> "FS"
"IAN" -> "COMPCAT"
```

———-

10.21 domain IFF InnerFiniteField

— InnerFiniteField.input —

```
)set break resume
)sys rm -f InnerFiniteField.output
)spool InnerFiniteField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show InnerFiniteField
--R
--R InnerFiniteField(p: PositiveInteger,n: PositiveInteger)  is a domain constructor
--R Abbreviation for InnerFiniteField is IFF
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IFF
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean             associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)               coerce : InnerPrimeField(p) -> %
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> PositiveInteger         dimension : () -> CardinalNumber
--R factor : % -> Factored(%)             gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inGroundField? : % -> Boolean         inv : % -> %
--R latex : % -> String                   lcm : List(%) -> %
--R lcm : (%,%) -> %                      norm : % -> InnerPrimeField(p)
--R one? : % -> Boolean                   prime? : % -> Boolean
--R ?quo? : (%,%) -> %                    recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %                    retract : % -> InnerPrimeField(p)
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)         squareFreePart : % -> %
--R trace : % -> InnerPrimeField(p)       transcendent? : % -> Boolean
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (InnerPrimeField(p),%) -> %
--R ?*? : (%,InnerPrimeField(p)) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,InnerPrimeField(p)) -> %
--R D : (%,NonNegativeInteger) -> % if InnerPrimeField(p) has FINITE
--R D : % -> % if InnerPrimeField(p) has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if InnerPrimeField(p) has FINITE
--R Frobenius : % -> % if InnerPrimeField(p) has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if InnerPrimeField(p) has CHARNZ or InnerPrimeField(p) has FINITE
--R charthRoot : % -> % if InnerPrimeField(p) has FINITE
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if InnerPrimeField(p) has FINITE
--R coordinates : Vector(%) -> Matrix(InnerPrimeField(p))
```

```
--R coordinates : % -> Vector(InnerPrimeField(p))
--R createNormalElement : () -> % if InnerPrimeField(p) has FINITE
--R createPrimitiveElement : () -> % if InnerPrimeField(p) has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(InnerPrimeField(p))
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> % if InnerPrimeField(p) has FINITE
--R differentiate : % -> % if InnerPrimeField(p) has FINITE
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if InnerPrimeField(p) has CHARNZ o
--R discreteLog : % -> NonNegativeInteger if InnerPrimeField(p) has FINITE
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> PositiveInteger
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if InnerPri
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R generator : () -> % if InnerPrimeField(p) has FINITE
--R index : PositiveInteger -> % if InnerPrimeField(p) has FINITE
--R init : () -> % if InnerPrimeField(p) has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(InnerPrimeField(p))) -> % if InnerPrimeF
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(InnerPrimeField(p)),"failed"
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(InnerPrimeField(p)) if InnerPrimeField
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(InnerPrimeField(p)) if InnerPrimeFie
--R lookup : % -> PositiveInteger if InnerPrimeField(p) has FINITE
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if InnerPrimeField(
--R minimalPolynomial : % -> SparseUnivariatePolynomial(InnerPrimeField(p))
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed") if InnerPrimeField(p) has FINITE
--R norm : (%,PositiveInteger) -> % if InnerPrimeField(p) has FINITE
--R normal? : % -> Boolean if InnerPrimeField(p) has FINITE
--R normalElement : () -> % if InnerPrimeField(p) has FINITE
--R order : % -> OnePointCompletion(PositiveInteger) if InnerPrimeField(p) has CHARNZ or InnerPr
--R order : % -> PositiveInteger if InnerPrimeField(p) has FINITE
--R primeFrobenius : % -> % if InnerPrimeField(p) has CHARNZ or InnerPrimeField(p) has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if InnerPrimeField(p) has CHARNZ or InnerPrimeF
--R primitive? : % -> Boolean if InnerPrimeField(p) has FINITE
--R primitiveElement : () -> % if InnerPrimeField(p) has FINITE
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if InnerPrimeField(p) has FINITE
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if InnerPrimeField(p) has
--R represents : Vector(InnerPrimeField(p)) -> %
--R retractIfCan : % -> Union(InnerPrimeField(p),"failed")
--R size : () -> NonNegativeInteger if InnerPrimeField(p) has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if InnerPri
--R trace : (%,PositiveInteger) -> % if InnerPrimeField(p) has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
```

```
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **InnerFiniteField.help** —

```
==========================================================================
InnerFiniteField examples
==========================================================================

See Also:
o )show InnerFiniteField
```

———-

10.21.1 InnerFiniteField (IFF)



See

⇒ “FiniteFieldExtensionByPolynomial” (FFP) 7.10.1 on page 820
⇒ “FiniteFieldExtension” (FFX) 7.9.1 on page 815
⇒ “FiniteField” (FF) 7.5.1 on page 789

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
coordinates	createNormalElement	createPrimitiveElement
D	definingPolynomial	degree
dimension	differentiate	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
hash	index	inGroundField?
init	inv	latex
lcm	linearAssociatedExp	linearAssociatedLog
linearAssociatedOrder	lookup	minimalPolynomial
multiEuclidean	nextItem	norm
normal?	normalElement	one?
order	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	recip	representationType
represents	retract	retractIfCan
sample	size	sizeLess?
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain IFF InnerFiniteField —

```
)abbrev domain IFF InnerFiniteField
++ Author: Mark Botch
++ Date Created: ???
++ Date Last Updated: 29 May 1990
++ Basic Operations:
++ Related Constructors: FiniteFieldExtensionByPolynomial,
++  FiniteFieldPolynomialPackage
++ Also See: FiniteFieldCyclicGroup, FiniteFieldNormalBasis
++ AMS Classifications:
++ Keywords: field, extension field, algebraic extension,
++   finite extension, finite field, Galois field
++ Reference:
++  R.Lidl, H.Niederreiter: Finite Field, Encyclopedia of Mathematics an
++   Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
```

```
++  J. Grabmeier, A. Scheerhorn: Finite Fields in AXIOM.
++   AXIOM Technical Report Series, ATR/5 NP2522.
++ Description:
++ InnerFiniteField(p,n) implements finite fields with \spad{p**n} elements
++ where p is assumed prime but does not check.
++ For a version which checks that p is prime, see \spadtype{FiniteField}.

InnerFiniteField(p:PositiveInteger, n:PositiveInteger) ==
     FiniteFieldExtension(InnerPrimeField p, n)
```

———-

— **IFF.dotabb** —

```
"IFF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IFF"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"IFF" -> "FAXF"
```

———-

10.22 domain IFAMON InnerFreeAbelianMonoid

— **InnerFreeAbelianMonoid.input** —

```
)set break resume
)sys rm -f InnerFreeAbelianMonoid.output
)spool InnerFreeAbelianMonoid.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerFreeAbelianMonoid
--R
--R InnerFreeAbelianMonoid(S: SetCategory,E: CancellationAbelianMonoid,un: E)  is a domain constructor
--R Abbreviation for InnerFreeAbelianMonoid is IFAMON
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IFAMON
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (E,S) -> %                      ?*? : (PositiveInteger,%) -> %
--R ?+? : (S,%) -> %                      ?+? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                0 : () -> %
--R coefficient : (S,%) -> E              coerce : S -> %
```

```
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   mapCoef : ((E -> E),%) -> %
--R mapGen : ((S -> S),%) -> %            nthCoef : (%,Integer) -> E
--R nthFactor : (%,Integer) -> S          retract : % -> S
--R sample : () -> %                      size : % -> NonNegativeInteger
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R highCommonTerms : (%,%) -> % if E has OAMON
--R retractIfCan : % -> Union(S,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R terms : % -> List(Record(gen: S,exp: E))
--R
--E 1

)spool
)lisp (bye)
```

———-


— **InnerFreeAbelianMonoid.help** —

```
=====================================================================
InnerFreeAbelianMonoid examples
=====================================================================

See Also:
o )show InnerFreeAbelianMonoid
```

———-

10.22.1 InnerFreeAbelianMonoid (IFAMON)



See

⇒ “ListMonoidOps” (LMOPS) 13.10.1 on page 1477

⇒ “FreeMonoid” (FMONOID) 7.32.1 on page 991
⇒ “FreeGroup” (FGROUP) 7.29.1 on page 980
⇒ “FreeAbelianMonoid” (FAMONOID) 7.28.1 on page 977
⇒ “FreeAbelianGroup” (FAGROUP) 7.27.1 on page 974

Exports:

0	coefficient	coerce	hash	highCommonTerms
latex	mapCoef	mapGen	nthCoef	nthFactor
retract	retractIfCan	sample	size	subtractIfCan
terms	zero?	?~=?	?*?	?+?
?=?				

— domain IFAMON InnerFreeAbelianMonoid —

```
)abbrev domain IFAMON InnerFreeAbelianMonoid
++ Author: Manuel Bronstein
++ Date Created: November 1989
++ Date Last Updated: 6 June 1991
++ Description:
++ Internal implementation of a free abelian monoid on any set of generators

InnerFreeAbelianMonoid(S: SetCategory, E:CancellationAbelianMonoid, un:E):
  FreeAbelianMonoidCategory(S, E) == ListMonoidOps(S, E, un) add
        Rep := ListMonoidOps(S, E, un)

        0                           == makeUnit()
        zero? f                     == empty? listOfMonoms f
        terms f                     == copy listOfMonoms f
        nthCoef(f, i)               == nthExpon(f, i)
        nthFactor(f, i)             == nthFactor(f, i)$Rep
        s:S + f:$                   == plus(s, un, f)
        f:$ + g:$                   == plus(f, g)
        (f:$ = g:$):Boolean         == commutativeEquality(f,g)
        n:E * s:S                   == makeTerm(s, n)
        n:NonNegativeInteger * f:$ == mapExpon(x +-> n*x, f)
        coerce(f:$):OutputForm      == outputForm(f, "+", (x,y) +-> y*x, 0)
        mapCoef(f, x)               == mapExpon(f, x)
        mapGen(f, x)                == mapGen(f, x)$Rep

        coefficient(s, f) ==
          for x in terms f repeat
            x.gen = s => return(x.exp)
          0

        if E has OrderedAbelianMonoid then
          highCommonTerms(f, g) ==
            makeMulti [[x.gen, min(x.exp, n)] for x in listOfMonoms f |
                                        (n := coefficient(x.gen, g)) > 0]
```

———-

— **IFAMON.dotabb** —

```
"IFAMON" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IFAMON"]
"OAMON" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAMON"]
"IFAMON" -> "OAMON"
```

———-

10.23 domain IIARRAY2 InnerIndexedTwoDimensionalArray

This is an internal type which provides an implementation of 2-dimensional arrays as PrimitiveArray's of PrimitiveArray's.

— **InnerIndexedTwoDimensionalArray.input** —

```
)set break resume
)sys rm -f InnerIndexedTwoDimensionalArray.output
)spool InnerIndexedTwoDimensionalArray.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerIndexedTwoDimensionalArray
--R
--R InnerIndexedTwoDimensionalArray(R: Type,mnRow: Integer,mnCol: Integer,Row: FiniteLinearAggre
--R Abbreviation for InnerIndexedTwoDimensionalArray is IIARRAY2
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IIARRAY2
--R
--R------------------------------ Operations --------------------------------
--R column : (%,Integer) -> Col           copy : % -> %
--R elt : (%,Integer,Integer,R) -> R      elt : (%,Integer,Integer) -> R
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                fill! : (%,R) -> %
--R map : (((R,R) -> R),%,%,R) -> %       map : (((R,R) -> R),%,%) -> %
--R map : ((R -> R),%) -> %               map! : ((R -> R),%) -> %
--R maxColIndex : % -> Integer            maxRowIndex : % -> Integer
--R minColIndex : % -> Integer            minRowIndex : % -> Integer
--R ncols : % -> NonNegativeInteger       nrows : % -> NonNegativeInteger
--R parts : % -> List(R)                  qelt : (%,Integer,Integer) -> R
--R row : (%,Integer) -> Row              sample : () -> %
```

```
--R setRow! : (%,Integer,Row) -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if R has SETCAT
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if R has SETCAT
--R latex : % -> String if R has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,NonNegativeInteger,R) -> %
--R qsetelt! : (%,Integer,Integer,R) -> R
--R setColumn! : (%,Integer,Col) -> %
--R setelt : (%,Integer,Integer,R) -> R
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— InnerIndexedTwoDimensionalArray.help —

```
=====================================================================
InnerIndexedTwoDimensionalArray examples
=====================================================================

See Also:
o )show InnerIndexedTwoDimensionalArray
```

———-

10.23.1 InnerIndexedTwoDimensionalArray (IIARRAY2)



See

⇒ "IndexedTwoDimensionalArray" (IARRAY2) 10.15.1 on page 1225
⇒ "TwoDimensionalArray" (ARRAY2) 21.13.1 on page 2732

Exports:

any?	coerce	column	copy	count
elt	empty	empty?	eq?	eval
every?	fill!	hash	latex	less?
map	map!	maxColIndex	maxRowIndex	member?
members	minColIndex	minRowIndex	more?	ncols
new	nrows	parts	qelt	qsetelt!
row	sample	setColumn!	setelt	setRow!
size?	#?	?=?	?~=?	

— domain IIARRAY2 InnerIndexedTwoDimensionalArray —

```
)abbrev domain IIARRAY2 InnerIndexedTwoDimensionalArray
++ Author: Mark Botch
++ Description:
++ There is no description for this domain

InnerIndexedTwoDimensionalArray(R,mnRow,mnCol,Row,Col):_
       Exports == Implementation where
  R : Type
  mnRow, mnCol : Integer
  Row : FiniteLinearAggregate R
  Col : FiniteLinearAggregate R

  Exports ==> TwoDimensionalArrayCategory(R,Row,Col)

  Implementation ==> add

    Rep := PrimitiveArray PrimitiveArray R

--% Predicates
```

```
    empty? m == empty?(m)$Rep

--% Primitive array creation

    empty() == empty()$Rep

    new(rows,cols,a) ==
      rows = 0 =>
        error "new: arrays with zero rows are not supported"
--      cols = 0 =>
--        error "new: arrays with zero columns are not supported"
      arr : PrimitiveArray PrimitiveArray R := new(rows,empty())
      for i in minIndex(arr)..maxIndex(arr) repeat
        qsetelt_!(arr,i,new(cols,a))
      arr

--% Size inquiries

    minRowIndex m == mnRow
    minColIndex m == mnCol
    maxRowIndex m == nrows m + mnRow - 1
    maxColIndex m == ncols m + mnCol - 1

    nrows m == (# m)$Rep

    ncols m ==
      empty? m => 0
      # m(minIndex(m)$Rep)

--% Part selection/assignment

    qelt(m,i,j) ==
      qelt(qelt(m,i - minRowIndex m)$Rep,j - minColIndex m)

    elt(m:%,i:Integer,j:Integer) ==
      i < minRowIndex(m) or i > maxRowIndex(m) =>
        error "elt: index out of range"
      j < minColIndex(m) or j > maxColIndex(m) =>
        error "elt: index out of range"
      qelt(m,i,j)

    qsetelt_!(m,i,j,r) ==
      setelt(qelt(m,i - minRowIndex m)$Rep,j - minColIndex m,r)

    setelt(m:%,i:Integer,j:Integer,r:R) ==
      i < minRowIndex(m) or i > maxRowIndex(m) =>
        error "setelt: index out of range"
      j < minColIndex(m) or j > maxColIndex(m) =>
        error "setelt: index out of range"
```

```
      qsetelt_!(m,i,j,r)

    if R has SetCategory then
        latex(m : %) : String ==
          s : String := "\left[ \begin{array}{"
          j : Integer
          for j in minColIndex(m)..maxColIndex(m) repeat
            s := concat(s,"c")$String
          s := concat(s,"} ")$String
          i : Integer
          for i in minRowIndex(m)..maxRowIndex(m) repeat
            for j in minColIndex(m)..maxColIndex(m) repeat
              s := concat(s, latex(qelt(m,i,j))$R)$String
              if j < maxColIndex(m) then s := concat(s, " & ")$String
            if i < maxRowIndex(m) then s := concat(s, " \\ ")$String
          concat(s, "\end{array} \right]")$String
```

———-

— IIARRAY2.dotabb —

```
"IIARRAY2" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IIARRAY2"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"IIARRAY2" -> "STRING"
```

———-

10.24 domain IPADIC InnerPAdicInteger

— InnerPAdicInteger.input —

```
)set break resume
)sys rm -f InnerPAdicInteger.output
)spool InnerPAdicInteger.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerPAdicInteger
--R
--R InnerPAdicInteger(p: Integer,unBalanced?: Boolean)  is a domain constructor
--R Abbreviation for InnerPAdicInteger is IPADIC
--R This constructor is not exposed in this frame.
```

```
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IPADIC
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        associates? : (%,%) -> Boolean
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              complete : % -> %
--R digits : % -> Stream(Integer)         extend : (%,Integer) -> %
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R moduloP : % -> Integer                modulus : () -> Integer
--R one? : % -> Boolean                   order : % -> NonNegativeInteger
--R ?quo? : (%,%) -> %                    quotientByP : % -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R sqrt : (%,Integer) -> %               unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R approximate : (%,Integer) -> Integer
--R characteristic : () -> NonNegativeInteger
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R root : (SparseUnivariatePolynomial(Integer),Integer) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— InnerPAdicInteger.help —

```
=============================================================================
InnerPAdicInteger examples
=============================================================================

See Also:
o )show InnerPAdicInteger
```

———-

10.24.1 InnerPAdicInteger (IPADIC)



See

⇒ “PAdicInteger” (PADIC) 17.1.1 on page 1847
⇒ “BalancedPAdicInteger” (BPADIC) 3.2.1 on page 242
⇒ “PAdicRationalConstructor” (PADICRC) 17.3.1 on page 1856
⇒ “PAdicRational” (PADICRAT) 17.2.1 on page 1851
⇒ “BalancedPAdicRational” (BPADICRT) 3.3.1 on page 246

Exports:

0	1	approximate	associates?
characteristic	coerce	complete	digits
divide	euclideanSize	expressIdealMember	exquo
extend	extendedEuclidean	gcd	gcdPolynomial
hash	latex	lcm	multiEuclidean
moduloP	modulus	one?	order
principalIdeal	quotientByP	recip	root
sample	sizeLess?	sqrt	subtractIfCan
unit?	unitCanonical	unitNormal	zero?
?~=?	?*?	?**?	?^?
?+?	?-?	-?	?=?
?quo?	?rem?		

— domain IPADIC InnerPAdicInteger —

```
)abbrev domain IPADIC InnerPAdicInteger
```

```
++ Author: Clifton J. Williamson
++ Date Created: 20 August 1989
++ Date Last Updated: 15 May 1990
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Keywords: p-adic, completion
++ Examples:
++ References:
++ Description:
++ This domain implements Zp, the p-adic completion of the integers.
++ This is an internal domain.

InnerPAdicInteger(p,unBalanced?): Exports == Implementation where
  p           : Integer
  unBalanced? : Boolean
  I   ==> Integer
  NNI ==> NonNegativeInteger
  OUT ==> OutputForm
  L   ==> List
  ST  ==> Stream
  SUP ==> SparseUnivariatePolynomial

  Exports ==> PAdicIntegerCategory p

  Implementation ==> add

    PEXPR := p :: OUT

    Rep := ST I

    characteristic() == 0
    euclideanSize(x) == order(x)

    stream(x:%):ST I == x pretend ST(I)
    padic(x:ST I):% == x pretend %
    digits x == stream x

    extend(x,n) == extend(x,n + 1)$Rep
    complete x == complete(x)$Rep

--     notBalanced?:() -> Boolean
--     notBalanced?() == unBalanced?

    modP:I -> I
    modP n ==
      unBalanced? or (p = 2) => positiveRemainder(n,p)
      symmetricRemainder(n,p)
```

```
modPInfo:I -> Record(digit:I,carry:I)
modPInfo n ==
  dv := divide(n,p)
  r0 := dv.remainder; q := dv.quotient
  if (r := modP r0) ^= r0 then q := q + ((r0 - r) quo p)
  [r,q]

invModP: I -> I
invModP n == invmod(n,p)

modulus()     == p
moduloP x     == (empty? x => 0; frst x)
quotientByP x == (empty? x => x; rst x)

approximate(x,n) ==
  n <= 0 or empty? x => 0
  frst x + p * approximate(rst x,n - 1)

x = y ==
  st : ST I := stream(x - y)
  n : I := _$streamCount$Lisp
  for i in 0..n repeat
    empty? st => return true
    frst st ^= 0 => return false
    st := rst st
  empty? st

order x ==
  st := stream x
  for i in 0..1000 repeat
    empty? st => return 0
    frst st ^= 0 => return i
    st := rst st
  error "order: series has more than 1000 leading zero coefs"

0 == padic concat(0$I,empty())
1 == padic concat(1$I,empty())

intToPAdic: I -> ST I
intToPAdic n == delay
  n = 0 => empty()
  modp := modPInfo n
  concat(modp.digit,intToPAdic modp.carry)

intPlusPAdic: (I,ST I) -> ST I
intPlusPAdic(n,x) == delay
  empty? x => intToPAdic n
  modp := modPInfo(n + frst x)
  concat(modp.digit,intPlusPAdic(modp.carry,rst x))
```

```
intMinusPAdic: (I,ST I) -> ST I
intMinusPAdic(n,x) == delay
  empty? x => intToPAdic n
  modp := modPInfo(n - frst x)
  concat(modp.digit,intMinusPAdic(modp.carry,rst x))

plusAux: (I,ST I,ST I) -> ST I
plusAux(n,x,y) == delay
  empty? x and empty? y => intToPAdic n
  empty? x => intPlusPAdic(n,y)
  empty? y => intPlusPAdic(n,x)
  modp := modPInfo(n + frst x + frst y)
  concat(modp.digit,plusAux(modp.carry,rst x,rst y))

minusAux: (I,ST I,ST I) -> ST I
minusAux(n,x,y) == delay
  empty? x and empty? y => intToPAdic n
  empty? x => intMinusPAdic(n,y)
  empty? y => intPlusPAdic(n,x)
  modp := modPInfo(n + frst x - frst y)
  concat(modp.digit,minusAux(modp.carry,rst x,rst y))

x + y == padic plusAux(0,stream x,stream y)
x - y == padic minusAux(0,stream x,stream y)
- y   == padic intMinusPAdic(0,stream y)
coerce(n:I) == padic intToPAdic n

intMult:(I,ST I) -> ST I
intMult(n,x) == delay
  empty? x => empty()
  modp := modPInfo(n * frst x)
  concat(modp.digit,intPlusPAdic(modp.carry,intMult(n,rst x)))

(n:I) * (x:%) ==
  padic intMult(n,stream x)

timesAux:(ST I,ST I) -> ST I
timesAux(x,y) == delay
  empty? x or empty? y => empty()
  modp := modPInfo(frst x * frst y)
  car := modp.digit
  cdr : ST I --!!
  cdr := plusAux(modp.carry,intMult(frst x,rst y),timesAux(rst x,y))
  concat(car,cdr)

(x:%) * (y:%) == padic timesAux(stream x,stream y)

quotientAux:(ST I,ST I) -> ST I
quotientAux(x,y) == delay
```

```
    empty? x => error "quotientAux: first argument"
    empty? y => empty()
    modP frst x = 0 =>
      modP frst y = 0 => quotientAux(rst x,rst y)
      error "quotient: quotient not integral"
    z0 := modP(invModP frst x * frst y)
    yy : ST I --!!
    yy := rest minusAux(0,y,intMult(z0,x))
    concat(z0,quotientAux(x,yy))

  recip x ==
    empty? x or modP frst x = 0 => "failed"
    padic quotientAux(stream x,concat(1,empty()))

  iExquo: (%,%,I) -> Union(%,"failed")
  iExquo(xx,yy,n) ==
    n > 1000 =>
      error "exquo: quotient by series with many leading zero coefs"
    empty? yy => "failed"
    empty? xx => 0
    zero? frst yy =>
      zero? frst xx => iExquo(rst xx,rst yy,n + 1)
      "failed"
    (rec := recip yy) case "failed" => "failed"
    xx * (rec :: %)

  x exquo y == iExquo(stream x,stream y,0)

  divide(x,y) ==
    (z:=x exquo y) case "failed" => [0,x]
    [z, 0]

  iSqrt: (I,I,I,%) -> %
  iSqrt(pn,an,bn,bSt) == delay
    bn1 := (empty? bSt => bn; bn + pn * frst(bSt))
    c := (bn1 - an*an) quo pn
    aa := modP(c * invmod(2*an,p))
    nSt := (empty? bSt => bSt; rst bSt)
    concat(aa,iSqrt(pn*p,an + pn*aa,bn1,nSt))

  sqrt(b,a) ==
    p = 2 =>
      error "sqrt: no square roots in Z2 yet"
    not zero? modP(a*a - (bb := moduloP b)) =>
      error "sqrt: not a square root (mod p)"
    b := (empty? b => b; rst b)
    a := modP a
    concat(a,iSqrt(p,a,bb,b))

  iRoot: (SUP I,I,I,I) -> ST I
```

```
iRoot(f,alpha,invFpx0,pPow) == delay
  num := -((f(alpha) exquo pPow) :: I)
  digit := modP(num * invFpx0)
  concat(digit,iRoot(f,alpha + digit * pPow,invFpx0,p * pPow))

root(f,x0) ==
  x0 := modP x0
  not zero? modP f(x0) =>
    error "root: not a root (mod p)"
  fpx0 := modP (differentiate f)(x0)
  zero? fpx0 =>
    error "root: approximate root must be a simple root (mod p)"
  invFpx0 := modP invModP fpx0
  padic concat(x0,iRoot(f,x0,invFpx0,p))

termOutput:(I,I) -> OUT
termOutput(k,c) ==
  k = 0 => c :: OUT
  mon := (k = 1 => PEXPR; PEXPR ** (k :: OUT))
  c = 1 => mon
  c = -1 => -mon
  (c :: OUT) * mon

showAll?:() -> Boolean
-- check a global Lisp variable
showAll?() == true

coerce(x:%):OUT ==
  empty?(st := stream x) => 0 :: OUT
  n : NNI ; count : NNI := _$streamCount$Lisp
  l : L OUT := empty()
  for n in 0..count while not empty? st repeat
    if frst(st) ^= 0 then
      l := concat(termOutput(n :: I,frst st),l)
    st := rst st
  if showAll?() then
    for n in (count + 1).. while explicitEntries? st and _
          not eq?(st,rst st) repeat
      if frst(st) ^= 0 then
        l := concat(termOutput(n pretend I,frst st),l)
      st := rst st
  l :=
    explicitlyEmpty? st => l
    eq?(st,rst st) and frst st = 0 => l
    concat(prefix("O" :: OUT,[PEXPR ** (n :: OUT)]),l)
  empty? l => 0 :: OUT
  reduce("+",reverse_! l)
```

— IPADIC.dotabb —

```
"IPADIC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IPADIC"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"PADICCT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PADICCT"]
"IPADIC" -> "PADICCT"
"IPADIC" -> "FLAGG"
```

———-

10.25 domain IPF InnerPrimeField

— InnerPrimeField.input —

```
)set break resume
)sys rm -f InnerPrimeField.output
)spool InnerPrimeField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerPrimeField
--R
--R InnerPrimeField(p: PositiveInteger)  is a domain constructor
--R Abbreviation for InnerPrimeField is IPF
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IPF
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R D : % -> %                            D : (%,NonNegativeInteger) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R algebraic? : % -> Boolean             associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)               charthRoot : % -> %
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R convert : % -> Integer                coordinates : % -> Vector(%)
--R createPrimitiveElement : () -> %      degree : % -> PositiveInteger
```

```
--R differentiate : % -> %                 dimension : () -> CardinalNumber
--R factor : % -> Factored(%)              gcd : List(%) -> %
--R gcd : (%,%) -> %                       hash : % -> SingleInteger
--R inGroundField? : % -> Boolean          index : PositiveInteger -> %
--R init : () -> %                         inv : % -> %
--R latex : % -> String                    lcm : List(%) -> %
--R lcm : (%,%) -> %                       lookup : % -> PositiveInteger
--R norm : % -> %                          one? : % -> Boolean
--R order : % -> PositiveInteger           prime? : % -> Boolean
--R primeFrobenius : % -> %                primitive? : % -> Boolean
--R primitiveElement : () -> %             ?quo? : (%,%) -> %
--R random : () -> %                       recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %                     represents : Vector(%) -> %
--R retract : % -> %                       sample : () -> %
--R size : () -> NonNegativeInteger        sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)          squareFreePart : % -> %
--R trace : % -> %                         transcendent? : % -> Boolean
--R unit? : % -> Boolean                   unitCanonical : % -> %
--R zero? : % -> Boolean                   ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R Frobenius : % -> % if $ has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if $ has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed")
--R conditionP : Matrix(%) -> Union(Vector(%),"failed")
--R coordinates : Vector(%) -> Matrix(%)
--R createNormalElement : () -> % if $ has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(%)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> %
--R discreteLog : % -> NonNegativeInteger
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed")
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R extensionDegree : () -> PositiveInteger
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer))
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if $ has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(%)) -> % if $ has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(%) if $ has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(%),"failed") if $ has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(%) if $ has FINITE
```

```
--R minimalPolynomial : % -> SparseUnivariatePolynomial(%)
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if $ has FINITE
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed")
--R norm : (%,PositiveInteger) -> % if $ has FINITE
--R normal? : % -> Boolean if $ has FINITE
--R normalElement : () -> % if $ has FINITE
--R order : % -> OnePointCompletion(PositiveInteger)
--R primeFrobenius : (%,NonNegativeInteger) -> %
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R representationType : () -> Union("prime",polynomial,normal,cyclic)
--R retractIfCan : % -> Union(%,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger)
--R trace : (%,PositiveInteger) -> % if $ has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— InnerPrimeField.help —

```
=====================================================================
InnerPrimeField examples
=====================================================================

See Also:
o )show InnerPrimeField
```

———-

10.25.1 InnerPrimeField (IPF)



See

⇒ "PrimeField" (PF) 17.29.1 on page 2070

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	coerce	conditionP
convert	coordinates	createPrimitiveElement
createNormalElement	D	definingPolynomial
degree	differentiate	dimension
discreteLog	divide	euclideanSize
expressIdealMember	exquo	extendedEuclidean
extensionDegree	factor	factorsOfCyclicGroupSize
Frobenius	gcd	gcdPolynomial
generator	hash	inGroundField?
index	init	inv
latex	lcm	linearAssociatedExp
linearAssociatedLog	linearAssociatedOrder	lookup
minimalPolynomial	multiEuclidean	nextItem
norm	normal?	normalElement
one?	order	prime?
primeFrobenius	primitive?	primitiveElement
principalIdeal	random	recip
representationType	represents	retract
retractIfCan	sample	size
sizeLess?	squareFree	squareFreePart
subtractIfCan	tableForDiscreteLogarithm	trace
transcendenceDegree	transcendent?	unit?
unitCanonical	unitNormal	zero?
?*?	?**?	?+?
?-?	-?	?/?
?=?	?^?	?~=?
?quo?	?rem?	

— domain IPF InnerPrimeField —

```
)abbrev domain IPF InnerPrimeField
++ Authors: N.N., J.Grabmeier, A.Scheerhorn
++ Date Created: ?, November 1990, 26.03.1991
++ Date Last Updated: 12 April 1991
++ Basic Operations:
++ Related Constructors: PrimeField
++ Also See:
++ AMS Classifications:
++ Keywords: prime characteristic, prime field, finite field
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encycoldia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++  AXIOM Technical Report Series, to appear.
++ Description:
++ InnerPrimeField(p) implements the field with p elements.
++ Note: argument p MUST be a prime (this domain does not check).
++ See \spadtype{PrimeField} for a domain that does check.

InnerPrimeField(p:PositiveInteger): Exports == Implementation where

  I   ==> Integer
  NNI ==> NonNegativeInteger
  PI  ==> PositiveInteger
  TBL ==> Table(PI,NNI)
  R   ==> Record(key:PI,entry:NNI)
  SUP ==> SparseUnivariatePolynomial
  OUT ==> OutputForm

  Exports ==> Join(FiniteFieldCategory,FiniteAlgebraicExtensionField($),_
               ConvertibleTo(Integer))

  Implementation ==> IntegerMod p add

    initializeElt:() -> Void
    initializeLog:() -> Void

-- global variables ====================================================

    primitiveElt:PI:=1
    -- for the lookup the primitive Element computed by createPrimitiveElement()

    sizeCG  :=(p-1) pretend NonNegativeInteger
    -- the size of the cyclic group

    facOfGroupSize := nil()$(List Record(factor:Integer,exponent:Integer))
    -- the factorization of the cyclic group size
```

```
    initlog?:Boolean:=true
    -- gets false after initialization of the logarithm table

    initelt?:Boolean:=true
    -- gets false after initialization of the primitive Element


    discLogTable:Table(PI,TBL):=table()$Table(PI,TBL)
    -- tables indexed by the factors of the size q of the cyclic group
    -- discLogTable.factor is a table of with keys
    -- primitiveElement() ** (i * (q quo factor)) and entries i for
    -- i in 0..n-1, n computed in initialize() in order to use
    -- the minimal size limit 'limit' optimal.

-- functions ===============================================================

    generator() == 1

    -- This uses x**(p-1)=1 (mod p), so x**(q(p-1)+r) = x**r (mod p)
    x:$ ** n:Integer ==
      zero?(n) => 1
      zero?(x) => 0
      r := positiveRemainder(n,p-1)::NNI
      ((x pretend IntegerMod p) **$IntegerMod(p) r) pretend $

    if p <= convert(max()$SingleInteger)@Integer then
      q := p::SingleInteger

      recip x ==
        zero?(y := convert(x)@Integer :: SingleInteger) => "failed"
        invmod(y, q)::Integer::$
    else
      recip x ==
        zero?(y := convert(x)@Integer) => "failed"
        invmod(y, p)::$

    convert(x:$) == x pretend I

    normalElement() == 1

    createNormalElement() == 1

    characteristic() == p

    factorsOfCyclicGroupSize() ==
      p=2 => facOfGroupSize -- this fixes an infinite loop of functions
                            -- calls, problem was that factors factor(1)
                            -- is the empty list
      if empty? facOfGroupSize then initializeElt()
      facOfGroupSize
```

```
    representationType() == "prime"

    tableForDiscreteLogarithm(fac) ==
      if initlog? then initializeLog()
      tbl:=search(fac::PI,discLogTable)$Table(PI,TBL)
      tbl case "failed" =>
        error "tableForDiscreteLogarithm: argument must be prime divisor_
 of the order of the multiplicative group"
      tbl pretend TBL

    primitiveElement() ==
      if initelt? then initializeElt()
      index(primitiveElt)

    initializeElt() ==
      facOfGroupSize:=factors(factor(sizeCG)$I)$(Factored I)
      -- get a primitive element
      primitiveElt:=lookup(createPrimitiveElement())
      -- set initialization flag
      initelt? := false
      void$Void

    initializeLog() ==
      if initelt? then initializeElt()
      -- set up tables for discrete logarithm
      limit:Integer:=30
      -- the minimum size for the discrete logarithm table
      for f in facOfGroupSize repeat
        fac:=f.factor
        base:$:=primitiveElement() ** (sizeCG quo fac)
        l:Integer:=length(fac)$Integer
        n:Integer:=0
        if odd?(l)$Integer then n:=shift(fac,-(l quo 2))
                          else n:=shift(1,(l quo 2))
        if n < limit then
          d:=(fac-1) quo limit + 1
          n:=(fac-1) quo d + 1
        tbl:TBL:=table()$TBL
        a:$:=1
        for i in (0::NNI)..(n-1)::NNI repeat
          insert_!([lookup(a),i::NNI]$R,tbl)$TBL
          a:=a*base
        insert_!([fac::PI,copy(tbl)$TBL]_
               $Record(key:PI,entry:TBL),discLogTable)$Table(PI,TBL)
      -- tell user about initialization
      --    print("discrete logarithm table initialized"::OUT)
      -- set initialization flag
      initlog? := false
      void$Void
```

```
    degree(x):PI == 1::PositiveInteger
    extensionDegree():PI == 1::PositiveInteger

--    sizeOfGroundField() == p::NonNegativeInteger

    inGroundField?(x)  == true

    coordinates(x) == new(1,x)$(Vector $)

    represents(v)  == v.1

    retract(x) == x

    retractIfCan(x) == x

    basis() == new(1,1::$)$(Vector $)
    basis(n:PI) ==
      n = 1 => basis()
      error("basis: argument must divide extension degree")

    definingPolynomial() ==
      monomial(1,1)$(SUP $) - monomial(1,0)$(SUP $)


    minimalPolynomial(x) ==
      monomial(1,1)$(SUP $) - monomial(x,0)$(SUP $)

    charthRoot x == x
```

———-

— **IPF.dotabb** —

```
"IPF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IPF"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"IPF" -> "TBAGG"
```

———-

10.26 domain ISUPS InnerSparseUnivariatePowerSeries

— **InnerSparseUnivariatePowerSeries.input** —

```
)set break resume
```

```
)sys rm -f InnerSparseUnivariatePowerSeries.output
)spool InnerSparseUnivariatePowerSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerSparseUnivariatePowerSeries
--R
--R InnerSparseUnivariatePowerSeries(Coef: Ring)  is a domain constructor
--R Abbreviation for InnerSparseUnivariatePowerSeries is ISUPS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ISUPS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                   ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        center : % -> Coef
--R coefficient : (%,Integer) -> Coef     coerce : Integer -> %
--R coerce : % -> OutputForm              complete : % -> %
--R degree : % -> Integer                 ?.? : (%,Integer) -> Coef
--R extend : (%,Integer) -> %             hash : % -> SingleInteger
--R iCompose : (%,%) -> %                 latex : % -> String
--R leadingCoefficient : % -> Coef        leadingMonomial : % -> %
--R map : ((Coef -> Coef),%) -> %         monomial : (Coef,Integer) -> %
--R monomial? : % -> Boolean              one? : % -> Boolean
--R order : (%,Integer) -> Integer        order : % -> Integer
--R pole? : % -> Boolean                  recip : % -> Union(%,"failed")
--R reductum : % -> %                     sample : () -> %
--R taylorQuoByVar : % -> %               truncate : (%,Integer) -> %
--R variable : % -> Symbol                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (Integer,Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (Integer,Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (Integer,Coef) -> Coef and Coef has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if Coef has *: (Integer,Coef) -> Coef and Coef has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Integer,Coef) -> Coef and Coef has PD
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Integer,Coef) -> Coef and
--R ?^? : (%,NonNegativeInteger) -> %
--R approximate : (%,Integer) -> Coef if Coef has **: (Coef,Integer) -> Coef and Coef has coerce
--R associates? : (%,%) -> Boolean if Coef has INTDOM
```

```
--R cAcos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAcosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAcot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAcoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAcsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAcsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAsec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAsech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAsin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAsinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAtan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cAtanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cCos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cCosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cCot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cCoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cCsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cCsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cExp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cLog : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cPower : (%,Coef) -> % if Coef has ALGEBRA(FRAC(INT))
--R cRationalPower : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R cSec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cSech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cSin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cSinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cTan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cTanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coerce : Coef -> % if Coef has COMRING
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : % -> % if Coef has *: (Integer,Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (Integer,Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (Integer,Coef) -> Coef and Coef has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (Integer,Coef) -> Coef and Coef has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Integer,Coef) -> Coef and Coef has Pl
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Integer,Coef) -> Coef and
--R ?.? : (%,%) -> % if Integer has SGROUP
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Integer) -> Coef
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R getRef : % -> Reference(OrderedCompletion(Integer))
--R getStream : % -> Stream(Record(k: Integer,c: Coef))
--R iExquo : (%,%,Boolean) -> Union(%,"failed")
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R makeSeries : (Reference(OrderedCompletion(Integer)),Stream(Record(k: Integer,c: Coef))) -> %
--R monomial : (%,List(SingletonAsOrderedSet),List(Integer)) -> %
--R monomial : (%,SingletonAsOrderedSet,Integer) -> %
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
```

```
--R multiplyExponents : (%,PositiveInteger) -> %
--R series : Stream(Record(k: Integer,c: Coef)) -> %
--R seriesToOutputForm : (Stream(Record(k: Integer,c: Coef)),Reference(OrderedCompletion(Integer
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R terms : % -> Stream(Record(k: Integer,c: Coef))
--R truncate : (%,Integer,Integer) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— InnerSparseUnivariatePowerSeries.help —

```
=====================================================================
InnerSparseUnivariatePowerSeries examples
=====================================================================

See Also:
o )show InnerSparseUnivariatePowerSeries
```

———-

10.26.1 InnerSparseUnivariatePowerSeries (ISUPS)



Exports:

0	1	approximate	associates?
cAcos	cAcosh	cAcot	cAcoth
cAcsc	cAcsch	cAsec	cAsech
cAsin	cAsinh	cAtan	cAtanh
cCos	cCosh	cCot	cCoth
cCsc	cCsch	center	cExp
cLog	coefficient	cPower	cRationalPower
cSec	cSech	cSin	cSinh
cTan	cTanh	characteristic	charthRoot
coerce	complete	D	differentiate
degree	eval	exquo	extend
getRef	getStream	hash	iCompose
iExquo	integrate	latex	leadingCoefficient
leadingMonomial	makeSeries	map	monomial
monomial?	multiplyCoefficients	multiplyExponents	one?
order	pole?	recip	reductum
sample	series	seriesToOutputForm	subtractIfCan
taylorQuoByVar	terms	truncate	unit?
unitCanonical	unitNormal	variable	variables
zero?	?*?	?**?	?+?
?-?	-?	?=?	?^?
?.?	?~=?	?/?	?^?
?.?			

— domain ISUPS InnerSparseUnivariatePowerSeries —

```
)abbrev domain ISUPS InnerSparseUnivariatePowerSeries
++ Author: Clifton J. Williamson
++ Date Created: 28 October 1994
++ Date Last Updated: 9 March 1995
++ Basic Operations:
++ Related Domains: SparseUnivariateTaylorSeries, SparseUnivariateLaurentSeries
++   SparseUnivariatePuiseuxSeries
++ Also See:
++ AMS Classifications:
++ Keywords: sparse, series
++ Examples:
++ References:
++ Description:
++ InnerSparseUnivariatePowerSeries is an internal domain
++ used for creating sparse Taylor and Laurent series.

InnerSparseUnivariatePowerSeries(Coef): Exports == Implementation where
  Coef  : Ring
  B    ==> Boolean
  COM  ==> OrderedCompletion Integer
  I    ==> Integer
```

```
L    ==> List
NNI  ==> NonNegativeInteger
OUT  ==> OutputForm
PI   ==> PositiveInteger
REF  ==> Reference OrderedCompletion Integer
RN   ==> Fraction Integer
Term ==> Record(k:Integer,c:Coef)
SG   ==> String
ST   ==> Stream Term

Exports ==> UnivariatePowerSeriesCategory(Coef,Integer) with
  makeSeries: (REF,ST) -> %
    ++ makeSeries(refer,str) creates a power series from the reference
    ++ \spad{refer} and the stream \spad{str}.
  getRef: % -> REF
    ++ getRef(f) returns a reference containing the order to which the
    ++ terms of f have been computed.
  getStream: % -> ST
    ++ getStream(f) returns the stream of terms representing the series f.
  series: ST -> %
    ++ series(st) creates a series from a stream of non-zero terms,
    ++ where a term is an exponent-coefficient pair.  The terms in the
    ++ stream should be ordered by increasing order of exponents.
  monomial?: % -> B
    ++ monomial?(f) tests if f is a single monomial.
  multiplyCoefficients: (I -> Coef,%) -> %
    ++ multiplyCoefficients(fn,f) returns the series
    ++ \spad{sum(fn(n) * an * x^n,n = n0..)},
    ++ where f is the series \spad{sum(an * x^n,n = n0..)}.
  iExquo: (%,%,B) -> Union(%,"failed")
    ++ iExquo(f,g,taylor?) is the quotient of the power series f and g.
    ++ If \spad{taylor?} is \spad{true}, then we must have
    ++ \spad{order(f) >= order(g)}.
  taylorQuoByVar: % -> %
    ++ taylorQuoByVar(a0 + a1 x + a2 x**2 + ...)
    ++ returns \spad{a1 + a2 x + a3 x**2 + ...}
  iCompose: (%,%) -> %
    ++ iCompose(f,g) returns \spad{f(g(x))}.  This is an internal function
    ++ which should only be called for Taylor series \spad{f(x)} and
    ++ \spad{g(x)} such that the constant coefficient of \spad{g(x)} is zero.
  seriesToOutputForm: (ST,REF,Symbol,Coef,RN) -> OutputForm
    ++ seriesToOutputForm(st,refer,var,cen,r) prints the series
    ++ \spad{f((var - cen)^r)}.
  if Coef has Algebra Fraction Integer then
    integrate: % -> %
      ++ integrate(f(x)) returns an anti-derivative of the power series
      ++ \spad{f(x)} with constant coefficient 0.
      ++ Warning: function does not check for a term of degree -1.
    cPower: (%,Coef) -> %
      ++ cPower(f,r) computes \spad{f^r}, where f has constant coefficient 1.
```

```
    ++ For use when the coefficient ring is commutative.
  cRationalPower: (%,RN) -> %
    ++ cRationalPower(f,r) computes \spad{f^r}.
    ++ For use when the coefficient ring is commutative.
  cExp: % -> %
    ++ cExp(f) computes the exponential of the power series f.
    ++ For use when the coefficient ring is commutative.
  cLog: % -> %
    ++ cLog(f) computes the logarithm of the power series f.
    ++ For use when the coefficient ring is commutative.
  cSin: % -> %
    ++ cSin(f) computes the sine of the power series f.
    ++ For use when the coefficient ring is commutative.
  cCos: % -> %
    ++ cCos(f) computes the cosine of the power series f.
    ++ For use when the coefficient ring is commutative.
  cTan: % -> %
    ++ cTan(f) computes the tangent of the power series f.
    ++ For use when the coefficient ring is commutative.
  cCot: % -> %
    ++ cCot(f) computes the cotangent of the power series f.
    ++ For use when the coefficient ring is commutative.
  cSec: % -> %
    ++ cSec(f) computes the secant of the power series f.
    ++ For use when the coefficient ring is commutative.
  cCsc: % -> %
    ++ cCsc(f) computes the cosecant of the power series f.
    ++ For use when the coefficient ring is commutative.
  cAsin: % -> %
    ++ cAsin(f) computes the arcsine of the power series f.
    ++ For use when the coefficient ring is commutative.
  cAcos: % -> %
    ++ cAcos(f) computes the arccosine of the power series f.
    ++ For use when the coefficient ring is commutative.
  cAtan: % -> %
    ++ cAtan(f) computes the arctangent of the power series f.
    ++ For use when the coefficient ring is commutative.
  cAcot: % -> %
    ++ cAcot(f) computes the arccotangent of the power series f.
    ++ For use when the coefficient ring is commutative.
  cAsec: % -> %
    ++ cAsec(f) computes the arcsecant of the power series f.
    ++ For use when the coefficient ring is commutative.
  cAcsc: % -> %
    ++ cAcsc(f) computes the arccosecant of the power series f.
    ++ For use when the coefficient ring is commutative.
  cSinh: % -> %
    ++ cSinh(f) computes the hyperbolic sine of the power series f.
    ++ For use when the coefficient ring is commutative.
  cCosh: % -> %
```

```
        ++ cCosh(f) computes the hyperbolic cosine of the power series f.
        ++ For use when the coefficient ring is commutative.
      cTanh: % -> %
        ++ cTanh(f) computes the hyperbolic tangent of the power series f.
        ++ For use when the coefficient ring is commutative.
      cCoth: % -> %
        ++ cCoth(f) computes the hyperbolic cotangent of the power series f.
        ++ For use when the coefficient ring is commutative.
      cSech: % -> %
        ++ cSech(f) computes the hyperbolic secant of the power series f.
        ++ For use when the coefficient ring is commutative.
      cCsch: % -> %
        ++ cCsch(f) computes the hyperbolic cosecant of the power series f.
        ++ For use when the coefficient ring is commutative.
      cAsinh: % -> %
        ++ cAsinh(f) computes the inverse hyperbolic sine of the power
        ++ series f.  For use when the coefficient ring is commutative.
      cAcosh: % -> %
        ++ cAcosh(f) computes the inverse hyperbolic cosine of the power
        ++ series f.  For use when the coefficient ring is commutative.
      cAtanh: % -> %
        ++ cAtanh(f) computes the inverse hyperbolic tangent of the power
        ++ series f.  For use when the coefficient ring is commutative.
      cAcoth: % -> %
        ++ cAcoth(f) computes the inverse hyperbolic cotangent of the power
        ++ series f.  For use when the coefficient ring is commutative.
      cAsech: % -> %
        ++ cAsech(f) computes the inverse hyperbolic secant of the power
        ++ series f.  For use when the coefficient ring is commutative.
      cAcsch: % -> %
        ++ cAcsch(f) computes the inverse hyperbolic cosecant of the power
        ++ series f.  For use when the coefficient ring is commutative.

  Implementation ==> add
    import REF

    Rep := Record(%ord: REF,%str: Stream Term)
    -- when the value of 'ord' is n, this indicates that all non-zero
    -- terms of order up to and including n have been computed;
    -- when 'ord' is plusInfinity, all terms have been computed;
    -- lazy evaluation of 'str' has the side-effect of modifying the value
    -- of 'ord'

--% Local functions

    makeTerm:        (Integer,Coef) -> Term
    getCoef:         Term -> Coef
    getExpon:        Term -> Integer
    iSeries:         (ST,REF) -> ST
    iExtend:         (ST,COM,REF) -> ST
```

```
    iTruncate0:      (ST,REF,REF,COM,I,I) -> ST
    iTruncate:       (%,COM,I) -> %
    iCoefficient:    (ST,Integer) -> Coef
    iOrder:          (ST,COM,REF) -> I
    iMap1:           ((Coef,I) -> Coef,I -> I,B,ST,REF,REF,Integer) -> ST
    iMap2:           ((Coef,I) -> Coef,I -> I,B,%) -> %
    iPlus1:          ((Coef,Coef) -> Coef,ST,REF,ST,REF,REF,I) -> ST
    iPlus2:          ((Coef,Coef) -> Coef,%,%) -> %
    productByTerm:   (Coef,I,ST,REF,REF,I) -> ST
    productLazyEval: (ST,REF,ST,REF,COM) -> Void
    iTimes:          (ST,REF,ST,REF,REF,I) -> ST
    iDivide:         (ST,REF,ST,REF,Coef,I,REF,I) -> ST
    divide:          (%,I,%,I,Coef) -> %
    compose0:        (ST,REF,ST,REF,I,%,%,I,REF,I) -> ST
    factorials?:     () -> Boolean
    termOutput:      (RN,Coef,OUT) -> OUT
    showAll?:        () -> Boolean

--% macros

    makeTerm(exp,coef) == [exp,coef]
    getCoef term == term.c
    getExpon term == term.k

    makeSeries(refer,x) == [refer,x]
    getRef ups == ups.%ord
    getStream ups == ups.%str

--% creation and destruction of series

    monomial(coef,expon) ==
      nix : ST := empty()
      st :=
        zero? coef => nix
        concat(makeTerm(expon,coef),nix)
      makeSeries(ref plusInfinity(),st)

    monomial? ups == (not empty? getStream ups) and (empty? rst getStream ups)

    coerce(n:I)    == n :: Coef :: %
    coerce(r:Coef) == monomial(r,0)

    iSeries(x,refer) ==
      empty? x => (setelt(refer,plusInfinity()); empty())
      setelt(refer,(getExpon frst x) :: COM)
      concat(frst x,iSeries(rst x,refer))

    series(x:ST) ==
      empty? x => 0
      n := getExpon frst x; refer := ref(n :: COM)
```

```
      makeSeries(refer,iSeries(x,refer))

--% values

    characteristic() == characteristic()$Coef

    0 == monomial(0,0)
    1 == monomial(1,0)

    iExtend(st,n,refer) ==
      (elt refer) < n =>
        explicitlyEmpty? st => (setelt(refer,plusInfinity()); st)
        explicitEntries? st => iExtend(rst st,n,refer)
        iExtend(lazyEvaluate st,n,refer)
      st

    extend(x,n) == (iExtend(getStream x,n :: COM,getRef x); x)
    complete x  == (iExtend(getStream x,plusInfinity(),getRef x); x)

    iTruncate0(x,xRefer,refer,minExp,maxExp,n) == delay
      explicitlyEmpty? x => (setelt(refer,plusInfinity()); empty())
      nn := n :: COM
      while (elt xRefer) < nn repeat lazyEvaluate x
      explicitEntries? x =>
        (nx := getExpon(xTerm := frst x)) > maxExp =>
          (setelt(refer,plusInfinity()); empty())
        setelt(refer,nx :: COM)
        (nx :: COM) >= minExp =>
          concat(makeTerm(nx,getCoef xTerm),_
                 iTruncate0(rst x,xRefer,refer,minExp,maxExp,nx + 1))
        iTruncate0(rst x,xRefer,refer,minExp,maxExp,nx + 1)
      -- can't have elt(xRefer) = infty unless all terms have been computed
      degr := retract(elt xRefer)@I
      setelt(refer,degr :: COM)
      iTruncate0(x,xRefer,refer,minExp,maxExp,degr + 1)

    iTruncate(ups,minExp,maxExp) ==
      x := getStream ups; xRefer := getRef ups
      explicitlyEmpty? x => 0
      explicitEntries? x =>
        deg := getExpon frst x
        refer := ref((deg - 1) :: COM)
        makeSeries(refer,iTruncate0(x,xRefer,refer,minExp,maxExp,deg))
      -- can't have elt(xRefer) = infty unless all terms have been computed
      degr := retract(elt xRefer)@I
      refer := ref(degr :: COM)
      makeSeries(refer,iTruncate0(x,xRefer,refer,minExp,maxExp,degr + 1))

    truncate(ups,n) == iTruncate(ups,minusInfinity(),n)
    truncate(ups,n1,n2) ==
```

```
      if n1 > n2 then (n1,n2) := (n2,n1)
      iTruncate(ups,n1 :: COM,n2)

    iCoefficient(st,n) ==
      explicitEntries? st =>
        term := frst st
        (expon := getExpon term) > n => 0
        expon = n => getCoef term
        iCoefficient(rst st,n)
      0

    coefficient(x,n)   == (extend(x,n); iCoefficient(getStream x,n))
    elt(x:%,n:Integer) == coefficient(x,n)

    iOrder(st,n,refer) ==
      explicitlyEmpty? st => error "order: series has infinite order"
      explicitEntries? st =>
        ((r := getExpon frst st) :: COM) >= n => retract(n)@Integer
        r
      -- can't have elt(xRefer) = infty unless all terms have been computed
      degr := retract(elt refer)@I
      (degr :: COM) >= n => retract(n)@Integer
      iOrder(lazyEvaluate st,n,refer)

    order x    == iOrder(getStream x,plusInfinity(),getRef x)
    order(x,n) == iOrder(getStream x,n :: COM,getRef x)

    terms x    == getStream x

--% predicates

    zero? ups ==
      x := getStream ups; ref := getRef ups
      whatInfinity(n := elt ref) = 1 => explicitlyEmpty? x
      count : NNI := _$streamCount$Lisp
      for i in 1..count repeat
        explicitlyEmpty? x => return true
        explicitEntries? x => return false
        lazyEvaluate x
      false

    ups1 = ups2 == zero?(ups1 - ups2)

--% arithmetic

    iMap1(cFcn,eFcn,check?,x,xRefer,refer,n) == delay
      -- when this function is called, all terms in 'x' of order < n have been
      -- computed and we compute the eFcn(n)th order coefficient of the result
      explicitlyEmpty? x => (setelt(refer,plusInfinity()); empty())
      -- if terms in 'x' up to order n have not been computed,
```

```
    -- apply lazy evaluation
    nn := n :: COM
    while (elt xRefer) < nn repeat lazyEvaluate x
    -- 'x' may now be empty: retest
    explicitlyEmpty? x => (setelt(refer,plusInfinity()); empty())
    -- must have nx >= n
    explicitEntries? x =>
      xCoef := getCoef(xTerm := frst x); nx := getExpon xTerm
      newCoef := cFcn(xCoef,nx); m := eFcn nx
      setelt(refer,m :: COM)
      not check? =>
        concat(makeTerm(m,newCoef),_
               iMap1(cFcn,eFcn,check?,rst x,xRefer,refer,nx + 1))
      zero? newCoef => iMap1(cFcn,eFcn,check?,rst x,xRefer,refer,nx + 1)
      concat(makeTerm(m,newCoef),_
             iMap1(cFcn,eFcn,check?,rst x,xRefer,refer,nx + 1))
    -- can't have elt(xRefer) = infty unless all terms have been computed
    degr := retract(elt xRefer)@I
    setelt(refer,eFcn(degr) :: COM)
    iMap1(cFcn,eFcn,check?,x,xRefer,refer,degr + 1)

  iMap2(cFcn,eFcn,check?,ups) ==
    -- 'eFcn' must be a strictly increasing function,
    -- i.e. i < j => eFcn(i) < eFcn(j)
    xRefer := getRef ups; x := getStream ups
    explicitlyEmpty? x => 0
    explicitEntries? x =>
      deg := getExpon frst x
      refer := ref(eFcn(deg - 1) :: COM)
      makeSeries(refer,iMap1(cFcn,eFcn,check?,x,xRefer,refer,deg))
    -- can't have elt(xRefer) = infty unless all terms have been computed
    degr := retract(elt xRefer)@I
    refer := ref(eFcn(degr) :: COM)
    makeSeries(refer,iMap1(cFcn,eFcn,check?,x,xRefer,refer,degr + 1))

  map(fcn,x)                == iMap2((y,n) +-> fcn(y), z +->z,      true, x)
  differentiate x           == iMap2((y,n) +-> n*y,    z +-> z - 1, true, x)
  multiplyCoefficients(f,x) == iMap2((y,n) +-> f(n)*y, z +-> z,     true, x)
  multiplyExponents(x,n)    == iMap2((y,m) +-> y,      z +-> n*z,   false, x)

  iPlus1(op,x,xRefer,y,yRefer,refer,n) == delay
    -- when this function is called, all terms in 'x' and 'y' of order < n
    -- have been computed and we are computing the nth order coefficient of
    -- the result; note the 'op' is either '+' or '-'
    explicitlyEmpty? x =>
      iMap1((x1,m) +-> op(0,x1), z +-> z, false, y, yRefer, refer, n)
    explicitlyEmpty? y =>
      iMap1((x1,m) +-> op(x1,0), z +-> z, false, x, xRefer, refer, n)
    -- if terms up to order n have not been computed,
    -- apply lazy evaluation
```

```
nn := n :: COM
while (elt xRefer) < nn repeat lazyEvaluate x
while (elt yRefer) < nn repeat lazyEvaluate y
-- 'x' or 'y' may now be empty: retest
explicitlyEmpty? x =>
  iMap1((x1,m) +-> op(0,x1), z +-> z, false, y, yRefer, refer, n)
explicitlyEmpty? y =>
  iMap1((x1,m) +-> op(x1,0), z +-> z, false, x, xRefer, refer, n)
-- must have nx >= n, ny >= n
-- both x and y have explicit terms
explicitEntries?(x) and explicitEntries?(y) =>
  xCoef := getCoef(xTerm := frst x); nx := getExpon xTerm
  yCoef := getCoef(yTerm := frst y); ny := getExpon yTerm
  nx = ny =>
    setelt(refer,nx :: COM)
    zero? (coef := op(xCoef,yCoef)) =>
      iPlus1(op,rst x,xRefer,rst y,yRefer,refer,nx + 1)
    concat(makeTerm(nx,coef),_
           iPlus1(op,rst x,xRefer,rst y,yRefer,refer,nx + 1))
  nx < ny =>
    setelt(refer,nx :: COM)
    concat(makeTerm(nx,op(xCoef,0)),_
           iPlus1(op,rst x,xRefer,y,yRefer,refer,nx + 1))
  setelt(refer,ny :: COM)
  concat(makeTerm(ny,op(0,yCoef)),_
         iPlus1(op,x,xRefer,rst y,yRefer,refer,ny + 1))
-- y has no term of degree n
explicitEntries? x =>
  xCoef := getCoef(xTerm := frst x); nx := getExpon xTerm
  -- can't have elt(yRefer) = infty unless all terms have been computed
  (degr := retract(elt yRefer)@I) < nx =>
    setelt(refer,elt yRefer)
    iPlus1(op,x,xRefer,y,yRefer,refer,degr + 1)
  setelt(refer,nx :: COM)
  concat(makeTerm(nx,op(xCoef,0)),_
         iPlus1(op,rst x,xRefer,y,yRefer,refer,nx + 1))
-- x has no term of degree n
explicitEntries? y =>
  yCoef := getCoef(yTerm := frst y); ny := getExpon yTerm
  -- can't have elt(xRefer) = infty unless all terms have been computed
  (degr := retract(elt xRefer)@I) < ny =>
    setelt(refer,elt xRefer)
    iPlus1(op,x,xRefer,y,yRefer,refer,degr + 1)
  setelt(refer,ny :: COM)
  concat(makeTerm(ny,op(0,yCoef)),_
         iPlus1(op,x,xRefer,rst y,yRefer,refer,ny + 1))
-- neither x nor y has a term of degree n
setelt(refer,xyRef := min(elt xRefer,elt yRefer))
-- can't have xyRef = infty unless all terms have been computed
iPlus1(op,x,xRefer,y,yRefer,refer,retract(xyRef)@I + 1)
```

```
iPlus2(op,ups1,ups2) ==
  xRefer := getRef ups1; x := getStream ups1
  xDeg :=
    explicitlyEmpty? x => return map(z +-> op(0$Coef,z),ups2)
    explicitEntries? x => (getExpon frst x) - 1
    -- can't have elt(xRefer) = infty unless all terms have been computed
    retract(elt xRefer)@I
  yRefer := getRef ups2; y := getStream ups2
  yDeg :=
    explicitlyEmpty? y => return map(z +-> op(z,0$Coef),ups1)
    explicitEntries? y => (getExpon frst y) - 1
    -- can't have elt(yRefer) = infty unless all terms have been computed
    retract(elt yRefer)@I
  deg := min(xDeg,yDeg); refer := ref(deg :: COM)
  makeSeries(refer,iPlus1(op,x,xRefer,y,yRefer,refer,deg + 1))

x + y == iPlus2((xi,yi) +-> xi + yi, x, y)
x - y == iPlus2((xi,yi) +-> xi - yi, x, y)
- y   == iMap2((x,n) +-> -x, z +-> z, false, y)

-- gives correct defaults for I, NNI and PI
n:I   * x:% == (zero? n => 0; map(z +-> n*z, x))
n:NNI * x:% == (zero? n => 0; map(z +-> n*z, x))
n:PI  * x:% == (zero? n => 0; map(z +-> n*z, x))

productByTerm(coef,expon,x,xRefer,refer,n) ==
  iMap1((y,m) +-> coef*y, z +-> z+expon, true, x, xRefer, refer, n)

productLazyEval(x,xRefer,y,yRefer,nn) ==
  explicitlyEmpty?(x) or explicitlyEmpty?(y) => void()
  explicitEntries? x =>
    explicitEntries? y => void()
    xDeg := (getExpon frst x) :: COM
    while (xDeg + elt(yRefer)) < nn repeat lazyEvaluate y
    void()
  explicitEntries? y =>
    yDeg := (getExpon frst y) :: COM
    while (yDeg + elt(xRefer)) < nn repeat lazyEvaluate x
    void()
  lazyEvaluate x
  -- if x = y, then y may now have explicit entries
  if lazy? y then lazyEvaluate y
  productLazyEval(x,xRefer,y,yRefer,nn)

iTimes(x,xRefer,y,yRefer,refer,n) == delay
  -- when this function is called, we are computing the nth order
  -- coefficient of the product
  productLazyEval(x,xRefer,y,yRefer,n :: COM)
  explicitlyEmpty?(x) or explicitlyEmpty?(y) =>
```

```
      (setelt(refer,plusInfinity()); empty())
    -- must have nx + ny >= n
    explicitEntries?(x) and explicitEntries?(y) =>
      xCoef := getCoef(xTerm := frst x); xExpon := getExpon xTerm
      yCoef := getCoef(yTerm := frst y); yExpon := getExpon yTerm
      expon := xExpon + yExpon
      setelt(refer,expon :: COM)
      scRefer := ref(expon :: COM)
      scMult := productByTerm(xCoef,xExpon,rst y,yRefer,scRefer,yExpon + 1)
      prRefer := ref(expon :: COM)
      pr := iTimes(rst x,xRefer,y,yRefer,prRefer,expon + 1)
      sm := iPlus1((a,b) +-> a+b,scMult,scRefer,pr,prRefer,refer,expon + 1)
      zero?(coef := xCoef * yCoef) => sm
      concat(makeTerm(expon,coef),sm)
    explicitEntries? x =>
      xExpon := getExpon frst x
      -- can't have elt(yRefer) = infty unless all terms have been computed
      degr := retract(elt yRefer)@I
      setelt(refer,(xExpon + degr) :: COM)
      iTimes(x,xRefer,y,yRefer,refer,xExpon + degr + 1)
    explicitEntries? y =>
      yExpon := getExpon frst y
      -- can't have elt(xRefer) = infty unless all terms have been computed
      degr := retract(elt xRefer)@I
      setelt(refer,(yExpon + degr) :: COM)
      iTimes(x,xRefer,y,yRefer,refer,yExpon + degr + 1)
    -- can't have elt(xRefer) = infty unless all terms have been computed
    xDegr := retract(elt xRefer)@I
    yDegr := retract(elt yRefer)@I
    setelt(refer,(xDegr + yDegr) :: COM)
    iTimes(x,xRefer,y,yRefer,refer,xDegr + yDegr + 1)

  ups1:% * ups2:% ==
    xRefer := getRef ups1; x := getStream ups1
    xDeg :=
      explicitlyEmpty? x => return 0
      explicitEntries? x => (getExpon frst x) - 1
      -- can't have elt(xRefer) = infty unless all terms have been computed
      retract(elt xRefer)@I
    yRefer := getRef ups2; y := getStream ups2
    yDeg :=
      explicitlyEmpty? y => return 0
      explicitEntries? y => (getExpon frst y) - 1
      -- can't have elt(yRefer) = infty unless all terms have been computed
      retract(elt yRefer)@I
    deg := xDeg + yDeg + 1; refer := ref(deg :: COM)
    makeSeries(refer,iTimes(x,xRefer,y,yRefer,refer,deg + 1))

  iDivide(x,xRefer,y,yRefer,rym,m,refer,n) == delay
    -- when this function is called, we are computing the nth order
```

```
    -- coefficient of the result
    explicitlyEmpty? x => (setelt(refer,plusInfinity()); empty())
    -- if terms up to order n - m have not been computed,
    -- apply lazy evaluation
    nm := (n + m) :: COM
    while (elt xRefer) < nm repeat lazyEvaluate x
    -- 'x' may now be empty: retest
    explicitlyEmpty? x => (setelt(refer,plusInfinity()); empty())
    -- must have nx >= n + m
    explicitEntries? x =>
      newCoef := getCoef(xTerm := frst x) * rym; nx := getExpon xTerm
      prodRefer := ref(nx :: COM)
      prod := productByTerm(-newCoef,nx - m,rst y,yRefer,prodRefer,1)
      sumRefer := ref(nx :: COM)
      sum := iPlus1((a,b)+->a+b,rst x,xRefer,prod,prodRefer,sumRefer,nx + 1)
      setelt(refer,(nx - m) :: COM); term := makeTerm(nx - m,newCoef)
      concat(term,iDivide(sum,sumRefer,y,yRefer,rym,m,refer,nx - m + 1))
    -- can't have elt(xRefer) = infty unless all terms have been computed
    degr := retract(elt xRefer)@I
    setelt(refer,(degr - m) :: COM)
    iDivide(x,xRefer,y,yRefer,rym,m,refer,degr - m + 1)

  divide(ups1,deg1,ups2,deg2,r) ==
    xRefer := getRef ups1; x := getStream ups1
    yRefer := getRef ups2; y := getStream ups2
    refer := ref((deg1 - deg2) :: COM)
    makeSeries(refer,iDivide(x,xRefer,y,yRefer,r,deg2,refer,deg1 - deg2 + 1))

  iExquo(ups1,ups2,taylor?) ==
    xRefer := getRef ups1; x := getStream ups1
    yRefer := getRef ups2; y := getStream ups2
    n : I := 0
    -- try to find first non-zero term in y
    -- give up after 1000 lazy evaluations
    while not explicitEntries? y repeat
      explicitlyEmpty? y => return "failed"
      lazyEvaluate y
      (n := n + 1) > 1000 => return "failed"
    yCoef := getCoef(yTerm := frst y); ny := getExpon yTerm
    (ry := recip yCoef) case "failed" => "failed"
    nn := ny :: COM
    if taylor? then
      while (elt(xRefer) < nn) repeat
        explicitlyEmpty? x => return 0
        explicitEntries? x => return "failed"
        lazyEvaluate x
    -- check if ups2 is a monomial
    empty? rst y => iMap2((y1,m) +-> y1*(ry::Coef),z +->z-ny, false, ups1)
    explicitlyEmpty? x => 0
    nx :=
```

```
    explicitEntries? x =>
      ((deg := getExpon frst x) < ny) and taylor? => return "failed"
      deg - 1
    -- can't have elt(xRefer) = infty unless all terms have been computed
    retract(elt xRefer)@I
  divide(ups1,nx,ups2,ny,ry :: Coef)

taylorQuoByVar ups ==
  iMap2((y,n) +-> y, z +-> z-1,false,ups - monomial(coefficient(ups,0),0))

compose0(x,xRefer,y,yRefer,yOrd,y1,yn0,n0,refer,n) == delay
  -- when this function is called, we are computing the nth order
  -- coefficient of the composite
  explicitlyEmpty? x => (setelt(refer,plusInfinity()); empty())
  -- if terms in 'x' up to order n have not been computed,
  -- apply lazy evaluation
  nn := n :: COM; yyOrd := yOrd :: COM
  while (yyOrd * elt(xRefer)) < nn repeat lazyEvaluate x
  explicitEntries? x =>
    xCoef := getCoef(xTerm := frst x); n1 := getExpon xTerm
    zero? n1 =>
      setelt(refer,n1 :: COM)
      concat(makeTerm(n1,xCoef),_
             compose0(rst x,xRefer,y,yRefer,yOrd,y1,yn0,n0,refer,n1 + 1))
    yn1 := yn0 * y1 ** ((n1 - n0) :: NNI)
    z := getStream yn1; zRefer := getRef yn1
    degr := yOrd * n1; prodRefer := ref((degr - 1) :: COM)
    prod := iMap1((s,k)+->xCoef*s,m+->m,true,z,zRefer,prodRefer,degr)
    coRefer := ref((degr + yOrd - 1) :: COM)
    co := compose0(rst x,xRefer,y,yRefer,yOrd,y1,yn1,n1,coRefer,degr+yOrd)
    setelt(refer,(degr - 1) :: COM)
    iPlus1((a,b)+->a+b,prod,prodRefer,co,coRefer,refer,degr)
  -- can't have elt(xRefer) = infty unless all terms have been computed
  degr := yOrd * (retract(elt xRefer)@I + 1)
  setelt(refer,(degr - 1) :: COM)
  compose0(x,xRefer,y,yRefer,yOrd,y1,yn0,n0,refer,degr)

iCompose(ups1,ups2) ==
  x := getStream ups1; xRefer := getRef ups1
  y := getStream ups2; yRefer := getRef ups2
  -- try to compute the order of 'ups2'
  n : I := _$streamCount$Lisp
  for i in 1..n while not explicitEntries? y repeat
    explicitlyEmpty? y => coefficient(ups1,0) :: %
    lazyEvaluate y
  explicitlyEmpty? y => coefficient(ups1,0) :: %
  yOrd : I :=
    explicitEntries? y => getExpon frst y
    retract(elt yRefer)@I
  compRefer := ref((-1) :: COM)
```

```
      makeSeries(compRefer,_
                 compose0(x,xRefer,y,yRefer,yOrd,ups2,1,0,compRefer,0))

    if Coef has Algebra Fraction Integer then

      integrate x == iMap2((y,n) +-> 1/(n+1)*y, z +-> z+1, true, x)

--% Fixed point computations

      Ys ==> Y$ParadoxicalCombinatorsForStreams(Term)

      integ0: (ST,REF,REF,I) -> ST
      integ0(x,intRef,ansRef,n) == delay
        nLess1 := (n - 1) :: COM
        while (elt intRef) < nLess1 repeat lazyEvaluate x
        explicitlyEmpty? x => (setelt(ansRef,plusInfinity()); empty())
        explicitEntries? x =>
          xCoef := getCoef(xTerm := frst x); nx := getExpon xTerm
          setelt(ansRef,(n1 := (nx + 1)) :: COM)
          concat(makeTerm(n1,inv(n1 :: RN) * xCoef),_
                 integ0(rst x,intRef,ansRef,n1))
        -- can't have elt(intRef) = infty unless all terms have been computed
        degr := retract(elt intRef)@I; setelt(ansRef,(degr + 1) :: COM)
        integ0(x,intRef,ansRef,degr + 2)

      integ1: (ST,REF,REF) -> ST
      integ1(x,intRef,ansRef) == integ0(x,intRef,ansRef,1)

      lazyInteg: (Coef,() -> ST,REF,REF) -> ST
      lazyInteg(a,xf,intRef,ansRef) ==
        ansStr : ST := integ1(delay xf,intRef,ansRef)
        concat(makeTerm(0,a),ansStr)

      cPower(f,r) ==
        -- computes f^r.  f should have constant coefficient 1.
        fp := differentiate f
        fInv := iExquo(1,f,false) :: %; y := r * fp * fInv
        yRef := getRef y; yStr := getStream y
        intRef := ref((-1) :: COM); ansRef := ref(0 :: COM)
        ansStr :=
         Ys(s+->lazyInteg(1,iTimes(s,ansRef,yStr,yRef,intRef,0),intRef,ansRef))
        makeSeries(ansRef,ansStr)

      iExp: (%,Coef) -> %
      iExp(f,cc) ==
        -- computes exp(f).  cc = exp coefficient(f,0)
        fp := differentiate f
        fpRef := getRef fp; fpStr := getStream fp
        intRef := ref((-1) :: COM); ansRef := ref(0 :: COM)
        ansStr :=
```

```
         Ys(s+->lazyInteg(cc,
                  iTimes(s,ansRef,fpStr,fpRef,intRef,0),intRef,ansRef))
        makeSeries(ansRef,ansStr)

      sincos0: (Coef,Coef,L ST,REF,REF,ST,REF,ST,REF) -> L ST
      sincos0(sinc,cosc,list,sinRef,cosRef,fpStr,fpRef,fpStr2,fpRef2) ==
        sinStr := first list; cosStr := second list
        prodRef1 := ref((-1) :: COM); prodRef2 := ref((-1) :: COM)
        prodStr1 := iTimes(cosStr,cosRef,fpStr,fpRef,prodRef1,0)
        prodStr2 := iTimes(sinStr,sinRef,fpStr2,fpRef2,prodRef2,0)
        [lazyInteg(sinc,prodStr1,prodRef1,sinRef),_
         lazyInteg(cosc,prodStr2,prodRef2,cosRef)]

      iSincos: (%,Coef,Coef,I) -> Record(%sin: %, %cos: %)
      iSincos(f,sinc,cosc,sign) ==
        fp := differentiate f
        fpRef := getRef fp; fpStr := getStream fp
--        fp2 := (one? sign => fp; -fp)
        fp2 := ((sign = 1) => fp; -fp)
        fpRef2 := getRef fp2; fpStr2 := getStream fp2
        sinRef := ref(0 :: COM); cosRef := ref(0 :: COM)
        sincos :=
         Ys(s+->sincos0(sinc,cosc,s,sinRef,cosRef,fpStr,fpRef,fpStr2,fpRef2),2)
        sinStr := (zero? sinc => rst first sincos; first sincos)
        cosStr := (zero? cosc => rst second sincos; second sincos)
        [makeSeries(sinRef,sinStr),makeSeries(cosRef,cosStr)]

      tan0: (Coef,ST,REF,ST,REF,I) -> ST
      tan0(cc,ansStr,ansRef,fpStr,fpRef,sign) ==
        sqRef := ref((-1) :: COM)
        sqStr := iTimes(ansStr,ansRef,ansStr,ansRef,sqRef,0)
        one : % := 1; oneStr := getStream one; oneRef := getRef one
        yRef := ref((-1) :: COM)
        yStr : ST :=
--          one? sign => iPlus1(#1 + #2,oneStr,oneRef,sqStr,sqRef,yRef,0)
          (sign = 1) => iPlus1((a,b)+->a+b,oneStr,oneRef,sqStr,sqRef,yRef,0)
          iPlus1((a,b)+->a-b,oneStr,oneRef,sqStr,sqRef,yRef,0)
        intRef := ref((-1) :: COM)
        lazyInteg(cc,iTimes(yStr,yRef,fpStr,fpRef,intRef,0),intRef,ansRef)

      iTan: (%,%,Coef,I) -> %
      iTan(f,fp,cc,sign) ==
        -- computes the tangent (and related functions) of f.
        fpRef := getRef fp; fpStr := getStream fp
        ansRef := ref(0 :: COM)
        ansStr := Ys(s+->tan0(cc,s,ansRef,fpStr,fpRef,sign))
        zero? cc => makeSeries(ansRef,rst ansStr)
        makeSeries(ansRef,ansStr)

--% Error Reporting
```

```
      TRCONST : SG := "series expansion involves transcendental constants"
      NPOWERS : SG := "series expansion has terms of negative degree"
      FPOWERS : SG := "series expansion has terms of fractional degree"
      MAYFPOW : SG := "series expansion may have terms of fractional degree"
      LOGS : SG := "series expansion has logarithmic term"
      NPOWLOG : SG :=
         "series expansion has terms of negative degree or logarithmic term"
      NOTINV : SG := "leading coefficient not invertible"

--% Rational powers and transcendental functions

      orderOrFailed : % -> Union(I,"failed")
      orderOrFailed uts ==
      -- returns the order of x or "failed"
      -- if -1 is returned, the series is identically zero
        x := getStream uts
        for n in 0..1000 repeat
          explicitlyEmpty? x => return -1
          explicitEntries? x => return getExpon frst x
          lazyEvaluate x
        "failed"

      RATPOWERS : Boolean := Coef has "**": (Coef,RN) -> Coef
      TRANSFCN  : Boolean := Coef has TranscendentalFunctionCategory

      cRationalPower(uts,r) ==
        (ord0 := orderOrFailed uts) case "failed" =>
          error "**: series with many leading zero coefficients"
        order := ord0 :: I
        (n := order exquo denom(r)) case "failed" =>
          error "**: rational power does not exist"
        cc := coefficient(uts,order)
        (ccInv := recip cc) case "failed" => error concat("**: ",NOTINV)
        ccPow :=
--          one? cc => cc
          (cc = 1) => cc
--          one? denom r =>
          (denom r) = 1 =>
            not negative?(num := numer r) => cc ** (num :: NNI)
            (ccInv :: Coef) ** ((-num) :: NNI)
          RATPOWERS => cc ** r
          error "** rational power of coefficient undefined"
        uts1 := (ccInv :: Coef) * uts
        uts2 := uts1 * monomial(1,-order)
        monomial(ccPow,(n :: I) * numer(r)) * cPower(uts2,r :: Coef)

      cExp uts ==
        zero?(cc := coefficient(uts,0)) => iExp(uts,1)
        TRANSFCN => iExp(uts,exp cc)
```

```
        error concat("exp: ",TRCONST)

      cLog uts ==
        zero?(cc := coefficient(uts,0)) =>
          error "log: constant coefficient should not be 0"
--        one? cc => integrate(differentiate(uts) * (iExquo(1,uts,true) :: %))
        (cc = 1) => integrate(differentiate(uts) * (iExquo(1,uts,true) :: %))
        TRANSFCN =>
          y := iExquo(1,uts,true) :: %
          (log(cc) :: %) + integrate(y * differentiate(uts))
        error concat("log: ",TRCONST)

      sincos: % -> Record(%sin: %, %cos: %)
      sincos uts ==
        zero?(cc := coefficient(uts,0)) => iSincos(uts,0,1,-1)
        TRANSFCN => iSincos(uts,sin cc,cos cc,-1)
        error concat("sincos: ",TRCONST)

      cSin uts == sincos(uts).%sin
      cCos uts == sincos(uts).%cos

      cTan uts ==
        zero?(cc := coefficient(uts,0)) => iTan(uts,differentiate uts,0,1)
        TRANSFCN => iTan(uts,differentiate uts,tan cc,1)
        error concat("tan: ",TRCONST)

      cCot uts ==
        zero? uts => error "cot: cot(0) is undefined"
        zero?(cc := coefficient(uts,0)) => error error concat("cot: ",NPOWERS)
        TRANSFCN => iTan(uts,-differentiate uts,cot cc,1)
        error concat("cot: ",TRCONST)

      cSec uts ==
        zero?(cc := coefficient(uts,0)) => iExquo(1,cCos uts,true) :: %
        TRANSFCN =>
          cosUts := cCos uts
          zero? coefficient(cosUts,0) => error concat("sec: ",NPOWERS)
          iExquo(1,cosUts,true) :: %
        error concat("sec: ",TRCONST)

      cCsc uts ==
        zero? uts => error "csc: csc(0) is undefined"
        TRANSFCN =>
          sinUts := cSin uts
          zero? coefficient(sinUts,0) => error concat("csc: ",NPOWERS)
          iExquo(1,sinUts,true) :: %
        error concat("csc: ",TRCONST)

      cAsin uts ==
        zero?(cc := coefficient(uts,0)) =>
```

```
    integrate(cRationalPower(1 - uts*uts,-1/2) * differentiate(uts))
  TRANSFCN =>
    x := 1 - uts * uts
    cc = 1 or cc = -1 =>
      -- compute order of 'x'
      (ord := orderOrFailed x) case "failed" =>
        error concat("asin: ",MAYFPOW)
      (order := ord :: I) = -1 => return asin(cc) :: %
      odd? order => error concat("asin: ",FPOWERS)
      c0 := asin(cc) :: %
      c0 + integrate(cRationalPower(x,-1/2) * differentiate(uts))
    c0 := asin(cc) :: %
    c0 + integrate(cRationalPower(x,-1/2) * differentiate(uts))
  error concat("asin: ",TRCONST)

cAcos uts ==
  zero? uts =>
    TRANSFCN => acos(0)$Coef :: %
    error concat("acos: ",TRCONST)
  TRANSFCN =>
    x := 1 - uts * uts
    cc := coefficient(uts,0)
    cc = 1 or cc = -1 =>
      -- compute order of 'x'
      (ord := orderOrFailed x) case "failed" =>
        error concat("acos: ",MAYFPOW)
      (order := ord :: I) = -1 => return acos(cc) :: %
      odd? order => error concat("acos: ",FPOWERS)
      c0 := acos(cc) :: %
      c0 + integrate(-cRationalPower(x,-1/2) * differentiate(uts))
    c0 := acos(cc) :: %
    c0 + integrate(-cRationalPower(x,-1/2) * differentiate(uts))
  error concat("acos: ",TRCONST)

cAtan uts ==
  zero?(cc := coefficient(uts,0)) =>
    y := iExquo(1,(1 :: %) + uts*uts,true) :: %
    integrate(y * (differentiate uts))
  TRANSFCN =>
    (y := iExquo(1,(1 :: %) + uts*uts,true)) case "failed" =>
      error concat("atan: ",LOGS)
    (atan(cc) :: %) + integrate((y :: %) * (differentiate uts))
  error concat("atan: ",TRCONST)

cAcot uts ==
  TRANSFCN =>
    (y := iExquo(1,(1 :: %) + uts*uts,true)) case "failed" =>
      error concat("acot: ",LOGS)
    cc := coefficient(uts,0)
    (acot(cc) :: %) + integrate(-(y :: %) * (differentiate uts))
```

```
    error concat("acot: ",TRCONST)

  cAsec uts ==
    zero?(cc := coefficient(uts,0)) =>
      error "asec: constant coefficient should not be 0"
    TRANSFCN =>
      x := uts * uts - 1
      y :=
        cc = 1 or cc = -1 =>
          -- compute order of 'x'
          (ord := orderOrFailed x) case "failed" =>
            error concat("asec: ",MAYFPOW)
          (order := ord :: I) = -1 => return asec(cc) :: %
          odd? order => error concat("asec: ",FPOWERS)
          cRationalPower(x,-1/2) * differentiate(uts)
        cRationalPower(x,-1/2) * differentiate(uts)
      (z := iExquo(y,uts,true)) case "failed" =>
        error concat("asec: ",NOTINV)
      (asec(cc) :: %) + integrate(z :: %)
    error concat("asec: ",TRCONST)

  cAcsc uts ==
    zero?(cc := coefficient(uts,0)) =>
      error "acsc: constant coefficient should not be 0"
    TRANSFCN =>
      x := uts * uts - 1
      y :=
        cc = 1 or cc = -1 =>
          -- compute order of 'x'
          (ord := orderOrFailed x) case "failed" =>
            error concat("acsc: ",MAYFPOW)
          (order := ord :: I) = -1 => return acsc(cc) :: %
          odd? order => error concat("acsc: ",FPOWERS)
          -cRationalPower(x,-1/2) * differentiate(uts)
        -cRationalPower(x,-1/2) * differentiate(uts)
      (z := iExquo(y,uts,true)) case "failed" =>
        error concat("asec: ",NOTINV)
      (acsc(cc) :: %) + integrate(z :: %)
    error concat("acsc: ",TRCONST)

  sinhcosh: % -> Record(%sinh: %, %cosh: %)
  sinhcosh uts ==
    zero?(cc := coefficient(uts,0)) =>
      tmp := iSincos(uts,0,1,1)
      [tmp.%sin,tmp.%cos]
    TRANSFCN =>
      tmp := iSincos(uts,sinh cc,cosh cc,1)
      [tmp.%sin,tmp.%cos]
    error concat("sinhcosh: ",TRCONST)
```

```
cSinh uts == sinhcosh(uts).%sinh
cCosh uts == sinhcosh(uts).%cosh

cTanh uts ==
  zero?(cc := coefficient(uts,0)) => iTan(uts,differentiate uts,0,-1)
  TRANSFCN => iTan(uts,differentiate uts,tanh cc,-1)
  error concat("tanh: ",TRCONST)

cCoth uts ==
  tanhUts := cTanh uts
  zero? tanhUts => error "coth: coth(0) is undefined"
  zero? coefficient(tanhUts,0) => error concat("coth: ",NPOWERS)
  iExquo(1,tanhUts,true) :: %

cSech uts ==
  coshUts := cCosh uts
  zero? coefficient(coshUts,0) => error concat("sech: ",NPOWERS)
  iExquo(1,coshUts,true) :: %

cCsch uts ==
  sinhUts := cSinh uts
  zero? coefficient(sinhUts,0) => error concat("csch: ",NPOWERS)
  iExquo(1,sinhUts,true) :: %

cAsinh uts ==
  x := 1 + uts * uts
  zero?(cc := coefficient(uts,0)) => cLog(uts + cRationalPower(x,1/2))
  TRANSFCN =>
    (ord := orderOrFailed x) case "failed" =>
      error concat("asinh: ",MAYFPOW)
    (order := ord :: I) = -1 => return asinh(cc) :: %
    odd? order => error concat("asinh: ",FPOWERS)
    -- the argument to 'log' must have a non-zero constant term
    cLog(uts + cRationalPower(x,1/2))
  error concat("asinh: ",TRCONST)

cAcosh uts ==
  zero? uts =>
    TRANSFCN => acosh(0)$Coef :: %
    error concat("acosh: ",TRCONST)
  TRANSFCN =>
    cc := coefficient(uts,0); x := uts*uts - 1
    cc = 1 or cc = -1 =>
      -- compute order of 'x'
      (ord := orderOrFailed x) case "failed" =>
        error concat("acosh: ",MAYFPOW)
      (order := ord :: I) = -1 => return acosh(cc) :: %
      odd? order => error concat("acosh: ",FPOWERS)
      -- the argument to 'log' must have a non-zero constant term
      cLog(uts + cRationalPower(x,1/2))
```

```
    cLog(uts + cRationalPower(x,1/2))
  error concat("acosh: ",TRCONST)

cAtanh uts ==
  half := inv(2 :: RN) :: Coef
  zero?(cc := coefficient(uts,0)) =>
    half * (cLog(1 + uts) - cLog(1 - uts))
  TRANSFCN =>
    cc = 1 or cc = -1 => error concat("atanh: ",LOGS)
    half * (cLog(1 + uts) - cLog(1 - uts))
  error concat("atanh: ",TRCONST)

cAcoth uts ==
  zero? uts =>
    TRANSFCN => acoth(0)$Coef :: %
    error concat("acoth: ",TRCONST)
  TRANSFCN =>
    cc := coefficient(uts,0); half := inv(2 :: RN) :: Coef
    cc = 1 or cc = -1 => error concat("acoth: ",LOGS)
    half * (cLog(uts + 1) - cLog(uts - 1))
  error concat("acoth: ",TRCONST)

cAsech uts ==
  zero? uts => error "asech: asech(0) is undefined"
  TRANSFCN =>
    zero?(cc := coefficient(uts,0)) =>
      error concat("asech: ",NPOWLOG)
    x := 1 - uts * uts
    cc = 1 or cc = -1 =>
      -- compute order of 'x'
      (ord := orderOrFailed x) case "failed" =>
        error concat("asech: ",MAYFPOW)
      (order := ord :: I) = -1 => return asech(cc) :: %
      odd? order => error concat("asech: ",FPOWERS)
      (utsInv := iExquo(1,uts,true)) case "failed" =>
        error concat("asech: ",NOTINV)
      cLog((1 + cRationalPower(x,1/2)) * (utsInv :: %))
    (utsInv := iExquo(1,uts,true)) case "failed" =>
      error concat("asech: ",NOTINV)
    cLog((1 + cRationalPower(x,1/2)) * (utsInv :: %))
  error concat("asech: ",TRCONST)

cAcsch uts ==
  zero? uts => error "acsch: acsch(0) is undefined"
  TRANSFCN =>
    zero?(cc := coefficient(uts,0)) => error concat("acsch: ",NPOWLOG)
    x := uts * uts + 1
    -- compute order of 'x'
    (ord := orderOrFailed x) case "failed" =>
      error concat("acsc: ",MAYFPOW)
```

```
          (order := ord :: I) = -1 => return acsch(cc) :: %
          odd? order => error concat("acsch: ",FPOWERS)
          (utsInv := iExquo(1,uts,true)) case "failed" =>
            error concat("acsch: ",NOTINV)
          cLog((1 + cRationalPower(x,1/2)) * (utsInv :: %))
        error concat("acsch: ",TRCONST)

--% Output forms

    -- check a global Lisp variable
    factorials?() == false

    termOutput(k,c,vv) ==
    -- creates a term c * vv ** k
      k = 0 => c :: OUT
      mon := (k = 1 => vv; vv ** (k :: OUT))
--       if factorials?() and k > 1 then
--         c := factorial(k)$IntegerCombinatoricFunctions * c
--         mon := mon / hconcat(k :: OUT,"!" :: OUT)
      c = 1 => mon
      c = -1 => -mon
      (c :: OUT) * mon

    -- check a global Lisp variable
    showAll?() == true

    seriesToOutputForm(st,refer,var,cen,r) ==
      vv :=
        zero? cen => var :: OUT
        paren(var :: OUT - cen :: OUT)
      l : L OUT := empty()
      while explicitEntries? st repeat
        term := frst st
        l := concat(termOutput(getExpon(term) * r,getCoef term,vv),l)
        st := rst st
      l :=
        explicitlyEmpty? st => l
        (deg := retractIfCan(elt refer)@Union(I,"failed")) case I =>
          concat(prefix("O" :: OUT,[vv ** ((((deg :: I) + 1) * r) :: OUT)]),l)
        l
      empty? l => (0$Coef) :: OUT
      reduce("+",reverse_! l)
```

— ISUPS.dotabb —

```
"ISUPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ISUPS"]
```

```
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ISUPS" -> "ALIST"
```

———-

10.27 domain INTABL InnerTable

— InnerTable.input —

```
)set break resume
)sys rm -f InnerTable.output
)spool InnerTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerTable
--R
--R InnerTable(Key: SetCategory,Entry: SetCategory,addDom) where
--R   addDom: TableAggregate(Key,Entry) with
--R        finiteAggregate  is a domain constructor
--R Abbreviation for InnerTable is INTABL
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INTABL
--R
--R------------------------------ Operations --------------------------------
--R copy : % -> %                         dictionary : () -> %
--R elt : (%,Key,Entry) -> Entry          ?.? : (%,Key) -> Entry
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(Entry)            eq? : (%,%) -> Boolean
--R index? : (Key,%) -> Boolean           indices : % -> List(Key)
--R key? : (Key,%) -> Boolean             keys : % -> List(Key)
--R map : ((Entry -> Entry),%) -> %       qelt : (%,Key) -> Entry
--R sample : () -> %                      setelt : (%,Key,Entry) -> Entry
--R table : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R any? : ((Entry -> Boolean),%) -> Boolean if $ has finiteAggregate
--R any? : ((Record(key: Key,entry: Entry) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R bag : List(Record(key: Key,entry: Entry)) -> %
--R coerce : % -> OutputForm if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R construct : List(Record(key: Key,entry: Entry)) -> %
--R convert : % -> InputForm if Record(key: Key,entry: Entry) has KONVERT(INFORM)
--R count : ((Entry -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (Entry,%) -> NonNegativeInteger if $ has finiteAggregate and Entry has SETCAT
```

```
--R count : (Record(key: Key,entry: Entry),%) -> NonNegativeInteger if $ has finiteAggregate and
--R count : ((Record(key: Key,entry: Entry) -> Boolean),%) -> NonNegativeInteger if $ has finite
--R dictionary : List(Record(key: Key,entry: Entry)) -> %
--R entry? : (Entry,%) -> Boolean if $ has finiteAggregate and Entry has SETCAT
--R eval : (%,List(Equation(Entry))) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,Equation(Entry)) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,Entry,Entry) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,List(Entry),List(Entry)) -> % if Entry has EVALAB(Entry) and Entry has SETCAT
--R eval : (%,List(Record(key: Key,entry: Entry)),List(Record(key: Key,entry: Entry))) -> % if R
--R eval : (%,Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> % if Record(key: K
--R eval : (%,Equation(Record(key: Key,entry: Entry))) -> % if Record(key: Key,entry: Entry) has
--R eval : (%,List(Equation(Record(key: Key,entry: Entry)))) -> % if Record(key: Key,entry: Entr
--R every? : ((Entry -> Boolean),%) -> Boolean if $ has finiteAggregate
--R every? : ((Record(key: Key,entry: Entry) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R extract! : % -> Record(key: Key,entry: Entry)
--R fill! : (%,Entry) -> % if $ has shallowlyMutable
--R find : ((Record(key: Key,entry: Entry) -> Boolean),%) -> Union(Record(key: Key,entry: Entry)
--R first : % -> Entry if Key has ORDSET
--R hash : % -> SingleInteger if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R insert! : (Record(key: Key,entry: Entry),%) -> %
--R inspect : % -> Record(key: Key,entry: Entry)
--R latex : % -> String if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : (((Entry,Entry) -> Entry),%,%) -> %
--R map : ((Record(key: Key,entry: Entry) -> Record(key: Key,entry: Entry)),%) -> %
--R map! : ((Entry -> Entry),%) -> % if $ has shallowlyMutable
--R map! : ((Record(key: Key,entry: Entry) -> Record(key: Key,entry: Entry)),%) -> % if $ has sh
--R maxIndex : % -> Key if Key has ORDSET
--R member? : (Entry,%) -> Boolean if $ has finiteAggregate and Entry has SETCAT
--R member? : (Record(key: Key,entry: Entry),%) -> Boolean if $ has finiteAggregate and Record(k
--R members : % -> List(Entry) if $ has finiteAggregate
--R members : % -> List(Record(key: Key,entry: Entry)) if $ has finiteAggregate
--R minIndex : % -> Key if Key has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(Entry) if $ has finiteAggregate
--R parts : % -> List(Record(key: Key,entry: Entry)) if $ has finiteAggregate
--R qsetelt! : (%,Key,Entry) -> Entry if $ has shallowlyMutable
--R reduce : (((Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> Record(key: Key,
--R reduce : (((Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> Record(key: Key,
--R reduce : (((Record(key: Key,entry: Entry),Record(key: Key,entry: Entry)) -> Record(key: Key,
--R remove : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Record(key: Key,entry: Entry),%) -> % if $ has finiteAggregate and Record(key: Key
--R remove! : (Key,%) -> Union(Entry,"failed")
--R remove! : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : (Record(key: Key,entry: Entry),%) -> % if $ has finiteAggregate
--R removeDuplicates : % -> % if $ has finiteAggregate and Record(key: Key,entry: Entry) has SET
--R search : (Key,%) -> Union(Entry,"failed")
--R select : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((Record(key: Key,entry: Entry) -> Boolean),%) -> % if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
```

```
--R swap! : (%,Key,Key) -> Void if $ has shallowlyMutable
--R table : List(Record(key: Key,entry: Entry)) -> %
--R ?~=? : (%,%) -> Boolean if Record(key: Key,entry: Entry) has SETCAT or Entry has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **InnerTable.help** —

```
=====================================================================
InnerTable examples
=====================================================================

See Also:
o )show InnerTable
```

———-

10.27.1 InnerTable (INTABL)



See

⇒ “HashTable” (HASHTBL) 9.1.1 on page 1089
⇒ “Table” (TABLE) 21.1.1 on page 2631
⇒ “EqTable” (EQTBL) 6.2.1 on page 669
⇒ “StringTable” (STRTBL) 20.32.1 on page 2578
⇒ “GeneralSparseTable” (GSTBL) 8.5.1 on page 1048
⇒ “SparseTable” (STBL) 20.16.1 on page 2418

Exports:

any?	any?	bag	coerce	construct
convert	copy	count	dictionary	entry?
elt	empty	empty?	entries	eq?
eval	every?	extract!	fill!	find
first	hash	index?	indices	insert!
inspect	key?	keys	latex	less?
map	map!	maxIndex	member?	members
minIndex	more?	parts	sample	qelt
qsetelt!	reduce	remove	remove!	removeDuplicates
search	select	select!	setelt	size?
swap!	table	?.?	#?	?=?
?~=?				

— domain INTABL InnerTable —

```
)abbrev domain INTABL InnerTable
++ Author: Barry Trager
++ Date Created: 1992
++ Date Last Updated: Sept 15, 1992
++ Basic Operations:
++ Related Domains: HashTable, AssociationList, Table
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain is used to provide a conditional "add" domain
++ for the implementation of \spadtype{Table}.

InnerTable(Key: SetCategory, Entry: SetCategory, addDom):Exports == Implementation where
    addDom : TableAggregate(Key, Entry) with
                    finiteAggregate
    Exports ==> TableAggregate(Key, Entry) with
                    finiteAggregate
    Implementation ==> addDom
```

———-

— INTABL.dotabb —

```
"INTABL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INTABL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"INTABL" -> "TBAGG"
```

———-

10.28 domain ITAYLOR InnerTaylorSeries

— InnerTaylorSeries.input —

```
)set break resume
)sys rm -f InnerTaylorSeries.output
)spool InnerTaylorSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InnerTaylorSeries
--R
--R InnerTaylorSeries(Coef: Ring)  is a domain constructor
--R Abbreviation for InnerTaylorSeries is ITAYLOR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ITAYLOR
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,Integer) -> %                ?*? : (%,Coef) -> %
--R ?*? : (Coef,%) -> %                   ?*? : (%,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coefficients : % -> Stream(Coef)      coerce : Integer -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   one? : % -> Boolean
--R order : % -> NonNegativeInteger       pole? : % -> Boolean
--R recip : % -> Union(%,"failed")        sample : () -> %
--R series : Stream(Coef) -> %            zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R characteristic : () -> NonNegativeInteger
--R coerce : % -> % if Coef has INTDOM
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R order : (%,NonNegativeInteger) -> NonNegativeInteger
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **InnerTaylorSeries.help** —

```
=====================================================================
InnerTaylorSeries examples
=====================================================================

See Also:
o )show InnerTaylorSeries
```

———-

10.28.1 InnerTaylorSeries (ITAYLOR)



See

⇒ “UnivariateTaylorSeries” (UTS) 22.9.1 on page 2844

Exports:

0	1	associates?	characteristic	coefficients
coerce	exquo	hash	latex	one?
order	pole?	recip	sample	series
subtractIfCan	unit?	unitCanonical	unitNormal	zero?
?~=?	?*?	?**?	?^?	?+?
?-?	-?	?=?		

— **domain ITAYLOR InnerTaylorSeries** —

```
)abbrev domain ITAYLOR InnerTaylorSeries
++ Author: Clifton J. Williamson
++ Date Created: 21 December 1989
```

```
++ Date Last Updated: 25 February 1989
++ Basic Operations:
++ Related Domains: UnivariateTaylorSeries(Coef,var,cen)
++ Also See:
++ AMS Classifications:
++ Keywords: stream, dense Taylor series
++ Examples:
++ References:
++ Description:
++ Internal package for dense Taylor series.
++ This is an internal Taylor series type in which Taylor series
++ are represented by a \spadtype{Stream} of \spadtype{Ring} elements.
++ For univariate series, the \spad{Stream} elements are the Taylor
++ coefficients. For multivariate series, the \spad{n}th Stream element
++ is a form of degree n in the power series variables.

InnerTaylorSeries(Coef): Exports == Implementation where
  Coef  : Ring
  I   ==> Integer
  NNI ==> NonNegativeInteger
  ST  ==> Stream Coef
  STT ==> StreamTaylorSeriesOperations Coef

  Exports ==> Ring with
    coefficients: % -> Stream Coef
      ++\spad{coefficients(x)} returns a stream of ring elements.
      ++ When x is a univariate series, this is a stream of Taylor
      ++ coefficients. When x is a multivariate series, the
      ++ \spad{n}th element of the stream is a form of
      ++ degree n in the power series variables.
    series: Stream Coef -> %
      ++\spad{series(s)} creates a power series from a stream of
      ++ ring elements.
      ++ For univariate series types, the stream s should be a stream
      ++ of Taylor coefficients. For multivariate series types, the
      ++ stream s should be a stream of forms the \spad{n}th element
      ++ of which is a
      ++ form of degree n in the power series variables.
    pole?: % -> Boolean
      ++\spad{pole?(x)} tests if the series x has a pole.
      ++ Note: this is false when x is a Taylor series.
    order: % -> NNI
      ++\spad{order(x)} returns the order of a power series x,
      ++ i.e. the degree of the first non-zero term of the series.
    order: (%,NNI) -> NNI
      ++\spad{order(x,n)} returns the minimum of n and the order of x.
    "*" : (Coef,%)->%
      ++\spad{c*x} returns the product of c and the series x.
    "*" : (%,Coef)->%
      ++\spad{x*c} returns the product of c and the series x.
```

```
    "*" : (%,Integer)->%
      ++\spad{x*i} returns the product of integer i and the series x.
    if Coef has IntegralDomain then IntegralDomain
      --++ An IntegralDomain provides 'exquo'

  Implementation ==> add

    Rep := Stream Coef

--% declarations
    x,y: %

--% definitions

    -- In what follows, we will be calling operations on Streams
    -- which are NOT defined in the package Stream.  Thus, it is
    -- necessary to explicitly pass back and forth between Rep and %.
    -- This will be done using the functions 'stream' and 'series'.

    stream : % -> Stream Coef
    stream x  == x pretend Stream(Coef)
    series st == st pretend %

    0 == coerce(0)$STT
    1 == coerce(1)$STT

    x = y ==
      -- tests if two power series are equal
      -- difference must be a finite stream of zeroes of length <= n + 1,
      -- where n = $streamCount$Lisp
      st : ST := stream(x - y)
      n : I := _$streamCount$Lisp
      for i in 0..n repeat
        empty? st => return true
        frst st ^= 0 => return false
        st := rst st
      empty? st

    coefficients x == stream x

    x + y            == stream(x) +$STT stream(y)
    x - y            == stream(x) -$STT stream(y)
    (x:%) * (y:%)    == stream(x) *$STT stream(y)
    - x              == -$STT (stream x)
    (i:I) * (x:%)    == (i::Coef) *$STT stream x
    (x:%) * (i:I)    == stream(x) *$STT (i::Coef)
    (c:Coef) * (x:%) == c *$STT stream x
    (x:%) * (c:Coef) == stream(x) *$STT c

    recip x ==
```

```
      (rec := recip$STT stream x) case "failed" => "failed"
      series(rec :: ST)

    if Coef has IntegralDomain then

      x exquo y ==
        (quot := stream(x) exquo$STT stream(y)) case "failed" => "failed"
        series(quot :: ST)

    x:% ** n:NNI ==
      n = 0 => 1
      expt(x,n :: PositiveInteger)$RepeatedSquaring(%)

    characteristic() == characteristic()$Coef
    pole? x == false

    iOrder: (ST,NNI,NNI) -> NNI
    iOrder(st,n,n0) ==
      (n = n0) or (empty? st) => n0
      zero? frst st => iOrder(rst st,n + 1,n0)
      n

    order(x,n) == iOrder(stream x,0,n)

    iOrder2: (ST,NNI) -> NNI
    iOrder2(st,n) ==
      empty? st => error "order: series has infinite order"
      zero? frst st => iOrder2(rst st,n + 1)
      n

    order x == iOrder2(stream x,0)
```

———-

— **ITAYLOR.dotabb** —

```
"ITAYLOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ITAYLOR"]
"ALGEBRA" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ALGEBRA"]
"ITAYLOR" -> "ALGEBRA"
```

———-

10.29 domain INFORM InputForm

— **InputForm.input** —

```
)set break resume
)sys rm -f InputForm.output
)spool InputForm.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show InputForm
--R
--R InputForm  is a domain constructor
--R Abbreviation for InputForm is INFORM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INFORM
--R
--R------------------------------ Operations ------------------------------
--R #? : % -> Integer                    ?*? : (%,%) -> %
--R ?**? : (%,Integer) -> %              ?+? : (%,%) -> %
--R ?/? : (%,%) -> %                     ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R atom? : % -> Boolean                 binary : (%,List(%)) -> %
--R car : % -> %                         cdr : % -> %
--R coerce : % -> OutputForm             convert : SExpression -> %
--R convert : % -> SExpression           convert : OutputForm -> %
--R convert : DoubleFloat -> %           convert : Integer -> %
--R convert : Symbol -> %                convert : String -> %
--R convert : List(%) -> %               declare : List(%) -> Symbol
--R destruct : % -> List(%)              ?.? : (%,List(Integer)) -> %
--R ?.? : (%,Integer) -> %               eq : (%,%) -> Boolean
--R expr : % -> OutputForm               flatten : % -> %
--R float : % -> DoubleFloat             float? : % -> Boolean
--R hash : % -> SingleInteger            integer : % -> Integer
--R integer? : % -> Boolean              interpret : % -> Any
--R lambda : (%,List(Symbol)) -> %       latex : % -> String
--R list? : % -> Boolean                 null? : % -> Boolean
--R pair? : % -> Boolean                 parse : String -> %
--R string : % -> String                 string? : % -> Boolean
--R symbol : % -> Symbol                 symbol? : % -> Boolean
--R unparse : % -> String                ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R compile : (Symbol,List(%)) -> Symbol
--R function : (%,List(Symbol),Symbol) -> %
--R
--E 1

)spool
)lisp (bye)
```


— **InputForm.help** —

```
=====================================================================
InputForm examples
=====================================================================

See Also:
o )show InputForm
```

———-

10.29.1 InputForm (INFORM)



Exports:

0	1	atom?	binary	car
cdr	coerce	compile	convert	declare
destruct	eq	expr	flatten	float
float?	function	hash	integer	integer?
interpret	lambda	latex	list?	null?
pair?	parse	string	string?	symbol
symbol?	unparse	#	?~=?	?**?
?*?	?+?	?/?	?=?	?.?

— **domain INFORM InputForm** —

```
)abbrev domain INFORM InputForm
++ Author: Manuel Bronstein
++ Date Created: ???
++ Date Last Updated: 19 April 1991
++ Description:
++ Domain of parsed forms which can be passed to the interpreter.
++ This is also the interface between algebra code and facilities
++ in the interpreter.
```

```
--)boot $noSubsumption := true

InputForm():
  Join(SExpressionCategory(String,Symbol,Integer,DoubleFloat,OutputForm),
       ConvertibleTo SExpression) with
    interpret: % -> Any
      ++ interpret(f) passes f to the interpreter.
    convert  : SExpression -> %
      ++ convert(s) makes s into an input form.
    binary   : (%, List %) -> %
      ++ \spad{binary(op, [a1,...,an])} returns the input form
      ++ corresponding to  \spad{a1 op a2 op ... op an}.
      ++
      ++X a:=[1,2,3]::List(InputForm)
      ++X binary(_+::InputForm,a)

    function : (%, List Symbol, Symbol) -> %
      ++ \spad{function(code, [x1,...,xn], f)} returns the input form
      ++ corresponding to \spad{f(x1,...,xn) == code}.
    lambda   : (%, List Symbol) -> %
      ++ \spad{lambda(code, [x1,...,xn])} returns the input form
      ++ corresponding to \spad{(x1,...,xn) +-> code} if \spad{n > 1},
      ++ or to \spad{x1 +-> code} if \spad{n = 1}.
    "+"      : (%, %) -> %
      ++ \spad{a + b} returns the input form corresponding to \spad{a + b}.
    "*"      : (%, %) -> %
      ++ \spad{a * b} returns the input form corresponding to \spad{a * b}.
    "/"      : (%, %) -> %
      ++ \spad{a / b} returns the input form corresponding to \spad{a / b}.
    "**"     : (%, NonNegativeInteger) -> %
      ++ \spad{a ** b} returns the input form corresponding to \spad{a ** b}.
    "**"     : (%, Integer) -> %
      ++ \spad{a ** b} returns the input form corresponding to \spad{a ** b}.
    0        : constant -> %
      ++ \spad{0} returns the input form corresponding to 0.
    1        : constant -> %
      ++ \spad{1} returns the input form corresponding to 1.
    flatten  : % -> %
      ++ flatten(s) returns an input form corresponding to s with
      ++ all the nested operations flattened to triples using new
      ++ local variables.
      ++ If s is a piece of code, this speeds up
      ++ the compilation tremendously later on.
    unparse  : % -> String
      ++ unparse(f) returns a string s such that the parser
      ++ would transform s to f.
      ++ Error: if f is not the parsed form of a string.
    parse : String -> %
      ++ parse(s) is the inverse of unparse. It parses a string to InputForm.
```

```
    declare  : List %   -> Symbol
      ++ declare(t) returns a name f such that f has been
      ++ declared to the interpreter to be of type t, but has
      ++ not been assigned a value yet.
      ++ Note: t should be created as \spad{devaluate(T)$Lisp} where T is the
      ++ actual type of f (this hack is required for the case where
      ++ T is a mapping type).
    compile  : (Symbol, List %) -> Symbol
      ++ \spad{compile(f, [t1,...,tn])} forces the interpreter to compile
      ++ the function f with signature \spad{(t1,...,tn) -> ?}.
      ++ returns the symbol f if successful.
      ++ Error: if f was not defined beforehand in the interpreter,
      ++ or if the ti's are not valid types, or if the compiler fails.
 == SExpression add
    Rep := SExpression

    mkProperOp: Symbol -> %
    strsym    : % -> String
    tuplify   : List Symbol -> %
    flatten0  : (%, Symbol, NonNegativeInteger) ->
                                            Record(lst: List %, symb:%)

    0                       == convert(0::Integer)
    1                       == convert(1::Integer)
    convert(x:%):SExpression == x pretend SExpression
    convert(x:SExpression):% == x

    conv(ll : List %): % ==
      convert(ll pretend List SExpression)$SExpression pretend %

    lambda(f,l) == conv([convert("+->"::Symbol),tuplify l,f]$List(%))

    interpret x ==
      v := interpret(x)$Lisp
      mkObj(unwrap(objVal(v)$Lisp)$Lisp, objMode(v)$Lisp)$Lisp

    convert(x:DoubleFloat):% ==
      zero? x => 0
--      one? x => 1
      (x = 1) => 1
      convert(x)$Rep

    flatten s ==
      -- will not compile if I use 'or'
      atom? s => s
      every?(atom?,destruct s)$List(%) => s
      sy := new()$Symbol
      n:NonNegativeInteger := 0
      l2 := [flatten0(x, sy, n := n + 1) for x in rest(l := destruct s)]
      conv(concat(convert("SEQ"::Symbol)@%,
```

```
      concat(concat [u.lst for u in l2], conv(
         [convert("exit"::Symbol)@%, 1$%, conv(concat(first l,
             [u.symb for u in l2]))@%]$List(%))@%)))@%

  flatten0(s, sy, n) ==
    atom? s => [nil(), s]
    a := convert(concat(string sy, convert(n)@String)::Symbol)@%
    l2 := [flatten0(x, sy, n := n+1) for x in rest(l := destruct s)]
    [concat(concat [u.lst for u in l2], conv([convert(
      "LET"::Symbol)@%, a, conv(concat(first l,
           [u.symb for u in l2]))@%]$List(%))@%), a]

  strsym s ==
    string? s => string s
    symbol? s => string symbol s
    error "strsym: form is neither a string or symbol"

  -- given a function this will attempt to recreate the input string
  unparse x ==
    atom?(s:% := unparseInputForm(x)$Lisp) => strsym s
    concat [strsym a for a in destruct s]

  parse(s:String):% ==
    ncParseFromString(s)$Lisp

  declare signature ==
    declare(name := new()$Symbol, signature)$Lisp
    name

  compile(name, types) ==
    symbol car cdr car
      selectLocalMms(mkProperOp name, convert(name)@%,
        types, nil$List(%))$Lisp

  mkProperOp name ==
    op := mkAtree(nme := convert(name)@%)$Lisp
    transferPropsToNode(nme, op)$Lisp
    convert op

  binary(op, args) ==
    (n := #args) < 2 => error "Need at least 2 arguments"
    n = 2 => convert([op, first args, last args]$List(%))
    convert([op, first args, binary(op, rest args)]$List(%))

  tuplify l ==
    empty? rest l => convert first l
    conv
      concat(convert("Tuple"::Symbol), [convert x for x in l]$List(%))

  function(f, l, name) ==
```

```
      nn := convert(new(1 + #l, convert(nil()$List(%)))$List(%))@%
      conv([convert("DEF"::Symbol), conv(cons(convert(name)@%,
                        [convert(x)@% for x in l])), nn, nn, f]$List(%))

    s1 + s2 ==
      s1 = 0 => s2
      s2 = 0 => s1
      conv [convert("+"::Symbol), s1, s2]$List(%)

    s1 * s2 ==
      s1 = 0 or s2 = 0 => 0
      s1 = 1 => s2
      s2 = 1 => s1
      conv [convert("*"::Symbol), s1, s2]$List(%)

    s1:% ** n:Integer ==
      s1 = 0 and n > 0 => 0
      s1 = 1 or zero? n => 1
--      one? n => s1
      (n = 1) => s1
      conv [convert("**"::Symbol), s1, convert n]$List(%)

    s1:% ** n:NonNegativeInteger == s1 ** (n::Integer)

    s1 / s2 ==
      s2 = 1 => s1
      conv [convert("/"::Symbol), s1, s2]$List(%)
```

———-

— **INFORM.dotabb** —

```
"INFORM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INFORM"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"INFORM" -> "ALIST"
```

———-

10.30 domain INT Integer

The function **one?** has been rewritten back to its original form. The NAG version called a lisp primitive that exists only in Codemist Common Lisp and is not defined in Common Lisp.

— **Integer.input** —

```
)set break resume
)sys rm -f Integer.output
)spool Integer.output
)set message test on
)set message auto off
)clear all
--S 1 of 42
2**(5678 - 4856 + 2 * 17)
--R
--R
--R   (1)
--R  48048107704350081471815409251259243912395261398716822634738556100880842000 76_
--R   30829308634252709141208374307457227821149607627692202643343568752733498024 9_
--R   53930242542523045817764949544214392905306388478705146745768073877141698859 8_
--R   15495632935288783334250628775936
--R                                                        Type: PositiveInteger
--E 1

--S 2 of 42
x := -101
--R
--R
--R   (2)  - 101
--R                                                               Type: Integer
--E 2

--S 3 of 42
abs(x)
--R
--R
--R   (3)  101
--R                                                        Type: PositiveInteger
--E 3

--S 4 of 42
sign(x)
--R
--R
--R   (4)  - 1
--R                                                               Type: Integer
--E 4

--S 5 of 42
x < 0
--R
--R
--R   (5)  true
--R                                                               Type: Boolean
--E 5
```

```
--S 6 of 42
x <= -1
--R
--R
--R   (6)  true
--R                                                    Type: Boolean
--E 6

--S 7 of 42
negative?(x)
--R
--R
--R   (7)  true
--R                                                    Type: Boolean
--E 7

--S 8 of 42
x > 0
--R
--R
--R   (8)  false
--R                                                    Type: Boolean
--E 8

--S 9 of 42
x >= 1
--R
--R
--R   (9)  false
--R                                                    Type: Boolean
--E 9

--S 10 of 42
positive?(x)
--R
--R
--R   (10)  false
--R                                                    Type: Boolean
--E 10

--S 11 of 42
zero?(x)
--R
--R
--R   (11)  false
--R                                                    Type: Boolean
--E 11

--S 12 of 42
one?(x)
```

```
--R
--R
--R   (12)  false
--R                                                    Type: Boolean
--E 12

--S 13 of 42
(x = -101)@Boolean
--R
--R
--R   (13)  true
--R                                                    Type: Boolean
--E 13

--S 14 of 42
odd?(x)
--R
--R
--R   (14)  true
--R                                                    Type: Boolean
--E 14

--S 15 of 42
even?(x)
--R
--R
--R   (15)  false
--R                                                    Type: Boolean
--E 15

--S 16 of 42
gcd(56788,43688)
--R
--R
--R   (16)  4
--R                                            Type: PositiveInteger
--E 16

--S 17 of 42
lcm(56788,43688)
--R
--R
--R   (17)  620238536
--R                                            Type: PositiveInteger
--E 17

--S 18 of 42
max(678,567)
--R
--R
```

```
--R   (18)  678
--R                                                    Type: PositiveInteger
--E 18

--S 19 of 42
min(678,567)
--R
--R
--R   (19)  567
--R                                                    Type: PositiveInteger
--E 19

--S 20 of 42
reduce(max,[2,45,-89,78,100,-45])
--R
--R
--R   (20)  100
--R                                                    Type: PositiveInteger
--E 20

--S 21 of 42
reduce(min,[2,45,-89,78,100,-45])
--R
--R
--R   (21)  - 89
--R                                                           Type: Integer
--E 21

--S 22 of 42
reduce(gcd,[2,45,-89,78,100,-45])
--R
--R
--R   (22)  1
--R                                                    Type: PositiveInteger
--E 22

--S 23 of 42
reduce(lcm,[2,45,-89,78,100,-45])
--R
--R
--R   (23)  1041300
--R                                                    Type: PositiveInteger
--E 23

--S 24 of 42
13 / 4
--R
--R
--R         13
--R   (24)  --
```

```
--R          4
--R                                                    Type: Fraction(Integer)
--E 24

--S 25 of 42
13 quo 4
--R
--R
--R   (25)  3
--R                                                      Type: PositiveInteger
--E 25

--S 26 of 42
13 rem 4
--R
--R
--R   (26)  1
--R                                                      Type: PositiveInteger
--E 26

--S 27 of 42
zero?(167604736446952 rem 2003644)
--R
--R
--R   (27)  true
--R                                                           Type: Boolean
--E 27

--S 28 of 42
d := divide(13,4)
--R
--R
--R   (28)  [quotient= 3,remainder= 1]
--R                           Type: Record(quotient: Integer,remainder: Integer)
--E 28

--S 29 of 42
d.quotient
--R
--R
--R   (29)  3
--R                                                      Type: PositiveInteger
--E 29

--S 30 of 42
d.remainder
--R
--R
--R   (30)  1
--R                                                      Type: PositiveInteger
```

```
--E 30

--S 31 of 42
factor 102400
--R
--R
--R          12 2
--R   (31)  2  5
--R                                                  Type: Factored(Integer)
--E 31

--S 32 of 42
prime? 7
--R
--R
--R   (32)  true
--R                                                           Type: Boolean
--E 32

--S 33 of 42
prime? 8
--R
--R
--R   (33)  false
--R                                                           Type: Boolean
--E 33

--S 34 of 42
nextPrime 100
--R
--R
--R   (34)  101
--R                                                  Type: PositiveInteger
--E 34

--S 35 of 42
prevPrime 100
--R
--R
--R   (35)  97
--R                                                  Type: PositiveInteger
--E 35

--S 36 of 42
primes(100,175)
--R
--R
--R   (36)  [173,167,163,157,151,149,139,137,131,127,113,109,107,103,101]
--R                                                     Type: List(Integer)
--E 36
```

```
--S 37 of 42
factor(2 :: Complex Integer)
--R
--R
--R                        2
--R   (37)  - %i (1 + %i)
--R                                              Type: Factored(Complex(Integer))
--E 37

--S 38 of 42
[fibonacci(k) for k in 0..]
--R
--R
--R   (38)  [0,1,1,2,3,5,8,13,21,34,...]
--R                                                        Type: Stream(Integer)
--E 38

--S 39 of 42
[legendre(i,11) for i in 0..10]
--R
--R
--R   (39)  [0,1,- 1,1,1,1,- 1,- 1,- 1,1,- 1]
--R                                                          Type: List(Integer)
--E 39

--S 40 of 42
[jacobi(i,15) for i in 0..9]
--R
--R
--R   (40)  [0,1,1,0,1,0,0,- 1,1,0]
--R                                                          Type: List(Integer)
--E 40

--S 41 of 42
[eulerPhi i for i in 1..]
--R
--R
--R   (41)  [1,1,2,2,4,2,6,4,6,4,...]
--R                                                        Type: Stream(Integer)
--E 41

--S 42 of 42
[moebiusMu i for i in 1..]
--R
--R
--R   (42)  [1,- 1,- 1,0,- 1,1,- 1,0,0,1,...]
--R                                                        Type: Stream(Integer)
--E 42
)spool
```

```
)lisp (bye)
```

———-

— Integer.help —

```
========================================================================
Integer examples
========================================================================

Axiom provides many operations for manipulating arbitrary precision
integers.  In this section we will show some of those that come from
Integer itself plus some that are implemented in other packages.

\subsection{Basic Functions}

The size of an integer in Axiom is only limited by the amount of
computer storage you have available.  The usual arithmetic operations
are available.

  2**(5678 - 4856 + 2 * 17)
  48048107704350081471815409251259243912395261398716822634738556100880842000076_
   30829308634252709141208374307457227821149607627692202643343568752733498024 9_
   53930242542523045817764949544214392905306388478705146745768073877141698859 8_
   15495632935288783334250628775936
                        Type: PositiveInteger

There are a number of ways of working with the sign of an integer.
Let's use this x as an example.

  x := -101
    - 101
                        Type: Integer

First of all, there is the absolute value function.

  abs(x)
    101
                        Type: PositiveInteger

The sign operation returns -1 if its argument is negative, 0 if zero
and 1 if positive.

  sign(x)
    - 1
                        Type: Integer

You can determine if an integer is negative in several other ways.
```

```
  x < 0
    true
                          Type: Boolean

  x <= -1
    true
                          Type: Boolean

  negative?(x)
    true
                          Type: Boolean
```

Similarly, you can find out if it is positive.

```
  x > 0
    false
                          Type: Boolean

  x >= 1
    false
                          Type: Boolean

  positive?(x)
    false
                          Type: Boolean
```

This is the recommended way of determining whether an integer is zero.

```
  zero?(x)
    false
                          Type: Boolean
```

Use the zero? operation whenever you are testing any mathematical object for equality with zero. This is usually more efficient that using = (think of matrices: it is easier to tell if a matrix is zero by just checking term by term than constructing another "zero" matrix and comparing the two matrices term by term) and also avoids the problem that = is usually used for creating equations.

This is the recommended way of determining whether an integer is equal to one.

```
  one?(x)
    false
                         Type: Boolean
```

This syntax is used to test equality using =. It says that you want a Boolean (true or false) answer rather than an equation.

```
  (x = -101)@Boolean
```

```
    true
                        Type: Boolean
```

The operations odd? and even? determine whether an integer is odd or even, respectively. They each return a Boolean object.

```
  odd?(x)
    true
                        Type: Boolean

  even?(x)
    false
                        Type: Boolean
```

The operation gcd computes the greatest common divisor of two integers.

```
  gcd(56788,43688)
    4
                        Type: PositiveInteger
```

The operation lcm computes their least common multiple.

```
  lcm(56788,43688)
    620238536
                        Type: PositiveInteger
```

To determine the maximum of two integers, use max.

```
  max(678,567)
    678
                        Type: PositiveInteger
```

To determine the minimum, use min.

```
  min(678,567)
    567
                        Type: PositiveInteger
```

The reduce operation is used to extend binary operations to more than two arguments. For example, you can use reduce to find the maximum integer in a list or compute the least common multiple of all integers in the list.

```
  reduce(max,[2,45,-89,78,100,-45])
    100
                        Type: PositiveInteger

  reduce(min,[2,45,-89,78,100,-45])
    - 89
                        Type: Integer
```

```
  reduce(gcd,[2,45,-89,78,100,-45])
    1
                        Type: PositiveInteger

  reduce(lcm,[2,45,-89,78,100,-45])
    1041300
                        Type: PositiveInteger
```

The infix operator "/" is not used to compute the quotient of integers.
Rather, it is used to create rational numbers as described in Fraction.

```
  13 / 4
     13
     --
      4
                        Type: Fraction Integer
```

The infix operation quo computes the integer quotient.

```
  13 quo 4
    3
                        Type: PositiveInteger
```

The infix operation rem computes the integer remainder.

```
  13 rem 4
    1
                        Type: PositiveInteger
```

One integer is evenly divisible by another if the remainder is zero.
The operation exquo can also be used.

```
  zero?(167604736446952 rem 2003644)
    true
                        Type: Boolean
```

The operation divide returns a record of the quotient and remainder
and thus is more efficient when both are needed.

```
  d := divide(13,4)
    [quotient= 3,remainder= 1]
                        Type: Record(quotient: Integer,remainder: Integer)

  d.quotient
    3
                        Type: PositiveInteger
```

See help on Records for details on Records.

```
  d.remainder
    1
                        Type: PositiveInteger

========================================================================
Primes and Factorization
========================================================================

Use the operation factor to factor integers.  It returns an object of
type Factored Integer.

  factor 102400
     12 2
    2  5
                        Type: Factored Integer

The operation prime? returns true or false depending on whether its
argument is a prime.

  prime? 7
    true
                        Type: Boolean

  prime? 8
    false
                        Type: Boolean

The operation nextPrime returns the least prime number greater than
its argument.

  nextPrime 100
    101
                        Type: PositiveInteger

The operation prevPrime returns the greatest prime number less than
its argument.

  prevPrime 100
    97
                        Type: PositiveInteger

To compute all primes between two integers (inclusively), use the
operation primes.

  primes(100,175)
    [173,167,163,157,151,149,139,137,131,127,113,109,107,103,101]
                        Type: List Integer

You might sometimes want to see the factorization of an integer
when it is considered a Gaussian integer.
```

```
  factor(2 :: Complex Integer)
                  2
    - %i (1 + %i)
                       Type: Factored Complex Integer
```

```
=====================================================================
Some Number Theoretic Functions
=====================================================================
```

Axiom provides several number theoretic operations for integers.

The operation fibonacci computes the Fibonacci numbers. The algorithm has running time O(log^3n) for argument n.

```
  [fibonacci(k) for k in 0..]
    [0,1,1,2,3,5,8,13,21,34,...]
                       Type: Stream Integer
```

The operation legendre computes the Legendre symbol for its two integer arguments where the second one is prime. If you know the second argument to be prime, use jacobi instead where no check is made.

```
  [legendre(i,11) for i in 0..10]
    [0,1,- 1,1,1,1,- 1,- 1,- 1,1,- 1]
                       Type: List Integer
```

The operation jacobi computes the Jacobi symbol for its two integer arguments. By convention, 0 is returned if the greatest common divisor of the numerator and denominator is not 1.

```
  [jacobi(i,15) for i in 0..9]
    [0,1,1,0,1,0,0,- 1,1,0]
                       Type: List Integer
```

The operation eulerPhi computes the values of Euler's \phi-function where \phi(n) equals the number of positive integers less than or equal to n that are relatively prime to the positive integer n.

```
  [eulerPhi i for i in 1..]
    [1,1,2,2,4,2,6,4,6,4,...]
                       Type: Stream Integer
```


The operation moebiusMu computes the Moebius mu function.

```
  [moebiusMu i for i in 1..]
    [1,- 1,- 1,0,- 1,1,- 1,0,0,1,...]
                       Type: Stream Integer
```

```
See Also:
o )help Complex
o )help Factored
o )help Records
o )help Fraction
o )help RadixExpansion
o )help HexadecimalExpansion
o )help BinaryExpansion
o )help DecimalExpansion
o )help IntegerNumberTheoryFunctions
o )help RomanNumeral
o )show Integer
```

———-

10.30.1 Integer (INT)



See

⇒ “NonNegativeInteger” (NNI) 15.5.1 on page 1706
⇒ “PositiveInteger” (PI) 17.28.1 on page 2066
⇒ “RomanNumeral” (ROMAN) 19.12.1 on page 2292

Exports:

0	1	abs	addmod
associates?	base	binomial	bit?
characteristic	coerce	convert	copy
D	dec	differentiate	divide
euclideanSize	even?	expressIdealMember	exquo
extendedEuclidean	extendedEuclidean	factor	factorial
gcd	gcdPolynomial	hash	inc
init	invmod	latex	lcm
length	mask	max	min
mulmod	multiEuclidean	negative?	nextItem
odd?	OMwrite	one?	patternMatch
permutation	positive?	positiveRemainder	powmod
prime?	principalIdeal	random	rational
rational?	rationalIfCan	recip	reducedSystem
retract	retractIfCan	sample	shift
sign	sizeLess?	squareFree	squareFreePart
submod	subtractIfCan	symmetricRemainder	unit?
unitCanonical	unitNormal	zero?	?*?
?**?	?+?	?-?	-?
?<?	?<=?	?=?	?>?
?>=?	?^?	?~=?	?quo?
?rem?			

— domain INT Integer —

```
)abbrev domain INT Integer
++ Author: Mark Botch
++ Date Created:
++ Change History:
++ Basic Operations:
++ Related Constructors:
++ Keywords: integer
++ Description:
++ \spadtype{Integer} provides the domain of arbitrary precision integers.

Integer: Join(IntegerNumberSystem, ConvertibleTo String, OpenMath) with
    random   : % -> %
      ++ random(n) returns a random integer from 0 to \spad{n-1}.
    canonical
      ++ mathematical equality is data structure equality.
    canonicalsClosed
      ++ two positives multiply to give positive.
    noetherian
      ++ ascending chain condition on ideals.
    infinite
      ++ nextItem never returns "failed".
 == add
```

```
ZP ==> SparseUnivariatePolynomial %
ZZP ==> SparseUnivariatePolynomial Integer
x,y: %
n: NonNegativeInteger

writeOMInt(dev: OpenMathDevice, x: %): Void ==
  if x < 0 then
    OMputApp(dev)
    OMputSymbol(dev, "arith1", "unary__minus")
    OMputInteger(dev, (-x) pretend Integer)
    OMputEndApp(dev)
  else
    OMputInteger(dev, x pretend Integer)

OMwrite(x: %): String ==
  s: String := ""
  sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
  dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
  OMputObject(dev)
  writeOMInt(dev, x)
  OMputEndObject(dev)
  OMclose(dev)
  s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
  s

OMwrite(x: %, wholeObj: Boolean): String ==
  s: String := ""
  sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
  dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
  if wholeObj then
    OMputObject(dev)
  writeOMInt(dev, x)
  if wholeObj then
    OMputEndObject(dev)
  OMclose(dev)
  s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
  s

OMwrite(dev: OpenMathDevice, x: %): Void ==
  OMputObject(dev)
  writeOMInt(dev, x)
  OMputEndObject(dev)

OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
  if wholeObj then
    OMputObject(dev)
  writeOMInt(dev, x)
  if wholeObj then
    OMputEndObject(dev)
```

```
      zero? x == ZEROP(x)$Lisp
--      one? x == ONEP(x)$Lisp
      one? x == x = 1
      0 == 0$Lisp
      1 == 1$Lisp
      base()  == 2$Lisp
      copy x  == x
      inc  x  == x + 1
      dec  x  == x - 1
      hash x == SXHASH(x)$Lisp
      negative? x == MINUSP(x)$Lisp
      coerce(x):OutputForm == outputForm(x pretend Integer)
      coerce(m:Integer):% == m pretend %
      convert(x:%):Integer == x pretend Integer
      length a == INTEGER_-LENGTH(a)$Lisp
      addmod(a, b, p) ==
         (c:=a + b) >= p => c - p
         c
      submod(a, b, p) ==
         (c:=a - b) < 0 => c + p
         c
      mulmod(a, b, p) == (a * b) rem p
      convert(x:%):Float       == coerce(x pretend Integer)$Float
      convert(x:%):DoubleFloat  == coerce(x pretend Integer)$DoubleFloat
      convert(x:%):InputForm   == convert(x pretend Integer)$InputForm
      convert(x:%):String      == string(x pretend Integer)$String

      latex(x:%):String ==
        s : String := string(x pretend Integer)$String
        (-1 < (x pretend Integer)) and ((x  pretend Integer) < 10) => s
        concat("{", concat(s, "}")$String)$String

      positiveRemainder(a, b) ==
        negative?(r := a rem b) =>
           negative? b => r - b
           r + b
        r

      reducedSystem(m:Matrix %):Matrix(Integer) ==
        m pretend Matrix(Integer)

      reducedSystem(m:Matrix %, v:Vector %):
       Record(mat:Matrix(Integer), vec:Vector(Integer)) ==
        [m pretend Matrix(Integer), vec pretend Vector(Integer)]

      abs(x) == ABS(x)$Lisp
      random() == random()$Lisp
      random(x) == RANDOM(x)$Lisp
      x = y == EQL(x,y)$Lisp
      x < y == (x<y)$Lisp
```

```
      - x == (-x)$Lisp
      x + y == (x+y)$Lisp
      x - y == (x-y)$Lisp
      x * y == (x*y)$Lisp
      (m:Integer) * (y:%) == (m*y)$Lisp -- for subsumption problem
      x ** n == EXPT(x,n)$Lisp
      odd? x == ODDP(x)$Lisp
      max(x,y) == MAX(x,y)$Lisp
      min(x,y) == MIN(x,y)$Lisp
      divide(x,y) == DIVIDE2(x,y)$Lisp
      x quo y == QUOTIENT2(x,y)$Lisp
      x rem y == REMAINDER2(x,y)$Lisp
      shift(x, y) == ASH(x,y)$Lisp
      x exquo y ==
         zero? y => "failed"
         zero?(x rem y) => x quo y
         "failed"
--      recip(x) == if one? x or x=-1 then x else "failed"
      recip(x) == if (x = 1) or x=-1 then x else "failed"
      gcd(x,y) == GCD(x,y)$Lisp
      UCA ==> Record(unit:%,canonical:%,associate:%)
      unitNormal x ==
         x < 0 => [-1,-x,-1]$UCA
         [1,x,1]$UCA
      unitCanonical x == abs x
      solveLinearPolynomialEquation(lp:List ZP,p:ZP):Union(List ZP,"failed") ==
         solveLinearPolynomialEquation(lp pretend List ZZP,
               p pretend ZZP)$IntegerSolveLinearPolynomialEquation pretend
                     Union(List ZP,"failed")
      squareFreePolynomial(p:ZP):Factored ZP ==
        squareFree(p)$UnivariatePolynomialSquareFree(%,ZP)
      factorPolynomial(p:ZP):Factored ZP ==
         -- GaloisGroupFactorizer doesn't factor the content
         -- so we have to do this by hand
         pp:=primitivePart p
         leadingCoefficient pp = leadingCoefficient p =>
             factor(p)$GaloisGroupFactorizer(ZP)
         mergeFactors(factor(pp)$GaloisGroupFactorizer(ZP),
                       map((x1:%):ZP+->x1::ZP,
                           factor((leadingCoefficient p exquo
                                   leadingCoefficient pp)
                                  ::%))$FactoredFunctions2(%,ZP)
                            )$FactoredFunctionUtilities(ZP)
      factorSquareFreePolynomial(p:ZP):Factored ZP ==
           factorSquareFree(p)$GaloisGroupFactorizer(ZP)
      gcdPolynomial(p:ZP, q:ZP):ZP ==
         zero? p => unitCanonical q
         zero? q => unitCanonical p
         gcd([p,q])$HeuGcd(ZP)
--    myNextPrime: (%,NonNegativeInteger) -> %
```

```
--    myNextPrime(x,n) ==
--       nextPrime(x)$IntegerPrimesPackage(%)
--    TT:=InnerModularGcd(%,ZP,67108859 pretend %,myNextPrime)
--    gcdPolynomial(p,q) == modularGcd(p,q)$TT
```

———-

— **INT.dotabb** —

```
"INT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INT",
          shape=ellipse]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"INT" -> "STRING"
"INT" -> "PFECAT"
```

———-

10.31 domain ZMOD IntegerMod

— **IntegerMod.input** —

```
)set break resume
)sys rm -f IntegerMod.output
)spool IntegerMod.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IntegerMod
--R
--R IntegerMod(p: PositiveInteger)  is a domain constructor
--R Abbreviation for IntegerMod is ZMOD
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ZMOD
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : Integer -> %
```

```
--R coerce : % -> OutputForm                convert : % -> Integer
--R hash : % -> SingleInteger               index : PositiveInteger -> %
--R init : () -> %                          latex : % -> String
--R lookup : % -> PositiveInteger           one? : % -> Boolean
--R random : () -> %                        recip : % -> Union(%,"failed")
--R sample : () -> %                        size : () -> NonNegativeInteger
--R zero? : % -> Boolean                    ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R nextItem : % -> Union(%,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **IntegerMod.help** —

```
=====================================================================
IntegerMod examples
=====================================================================

See Also:
o )show IntegerMod
```

———-

10.31.1 IntegerMod (ZMOD)



Exports:

0	1	characteristic	coerce	convert
hash	index	init	latex	lookup
nextItem	one?	random	recip	sample
size	subtractIfCan	zero?	?~=?	?*?
?**?	?^?	?+?	?-?	-?
?=?				

— domain ZMOD IntegerMod —

```
)abbrev domain ZMOD IntegerMod
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ IntegerMod(n) creates the ring of integers reduced modulo the integer n.

IntegerMod(p:PositiveInteger):
 Join(CommutativeRing, Finite, ConvertibleTo Integer, StepThrough) == add
  size()           == p
  characteristic() == p
  lookup x == (zero? x => p; (convert(x)@Integer) :: PositiveInteger)

-- Code is duplicated for the optimizer to kick in.
  if p <= convert(max()$SingleInteger)@Integer then
    Rep:= SingleInteger
    q := p::SingleInteger

    bloodyCompiler: Integer -> %
    bloodyCompiler n == positiveRemainder(n, p)$Integer :: Rep

    convert(x:%):Integer == convert(x)$Rep
    coerce(x):OutputForm == coerce(x)$Rep
    coerce(n:Integer):%  == bloodyCompiler n
    0                    == 0$Rep
    1                    == 1$Rep
    init                 == 0$Rep
    nextItem(n)          ==
                              m:=n+1
                              m=0 => "failed"
                              m
    x = y                == x =$Rep y
    x:% * y:%            == mulmod(x, y, q)
```

```
    n:Integer * x:%      == mulmod(bloodyCompiler n, x, q)
    x + y                == addmod(x, y, q)
    x - y                == submod(x, y, q)
    random()             == random(q)$Rep
    index a              == positiveRemainder(a::%, q)
    - x                  == (zero? x => 0; q -$Rep x)

    x:% ** n:NonNegativeInteger ==
      n < p => powmod(x, n::Rep, q)
      powmod(convert(x)@Integer, n, p)$Integer :: Rep

    recip x ==
       (c1, c2, g) := extendedEuclidean(x, q)$Rep
--       not one? g => "failed"
       not (g = 1) => "failed"
       positiveRemainder(c1, q)

  else
    Rep:= Integer

    convert(x:%):Integer == convert(x)$Rep
    coerce(n:Integer):%  == positiveRemainder(n::Rep, p)
    coerce(x):OutputForm == coerce(x)$Rep
    0                    == 0$Rep
    1                    == 1$Rep
    init                 == 0$Rep
    nextItem(n)          ==
                              m:=n+1
                              m=0 => "failed"
                              m
    x = y                == x =$Rep y
    x:% * y:%            == mulmod(x, y, p)
    n:Integer * x:%      == mulmod(positiveRemainder(n::Rep, p), x, p)
    x + y                == addmod(x, y, p)
    x - y                == submod(x, y, p)
    random()             == random(p)$Rep
    index a              == positiveRemainder(a::Rep, p)
    - x                  == (zero? x => 0; p -$Rep x)
    x:% ** n:NonNegativeInteger == powmod(x, n::Rep, p)

    recip x ==
       (c1, c2, g) := extendedEuclidean(x, p)$Rep
--       not one? g => "failed"
       not (g = 1) => "failed"
       positiveRemainder(c1, p)
```

———————-

— ZMOD.dotabb —

```
"ZMOD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ZMOD"]
"BMODULE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BMODULE"]
"ZMOD" -> "BMODULE"
```

———-

10.32 domain INTFTBL IntegrationFunctionsTable

— IntegrationFunctionsTable.input —

```
)set break resume
)sys rm -f IntegrationFunctionsTable.output
)spool IntegrationFunctionsTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IntegrationFunctionsTable
--R
--R IntegrationFunctionsTable  is a domain constructor
--R Abbreviation for IntegrationFunctionsTable is INTFTBL
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INTFTBL
--R
--R------------------------------ Operations ------------------------------
--R clearTheFTable : () -> Void           showTheFTable : () -> %
--R entries : % -> List(Record(key: Record(var: Symbol,fn: Expression(DoubleFloat),range: Segmen
--R entry : Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion(Doub
--R fTable : List(Record(key: Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Orde
--R insert! : Record(key: Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedC
--R keys : % -> List(Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedComple
--R showAttributes : Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedComple
--R
--E 1

)spool
)lisp (bye)
```

———-


— IntegrationFunctionsTable.help —

```
=====================================================================
IntegrationFunctionsTable examples
=====================================================================

See Also:
o )show IntegrationFunctionsTable
```

———-

10.32.1 IntegrationFunctionsTable (INTFTBL)



Exports:
clearTheFTable entries entry fTable insert! keys showAttributes showTheFTable

— domain INTFTBL IntegrationFunctionsTable —

```
)abbrev domain INTFTBL IntegrationFunctionsTable
++ Author: Brian Dupee
++ Date Created: March 1995
++ Date Last Updated: June 1995
++ Description:
++ There is no description for this domain

IntegrationFunctionsTable(): E == I where
  EF2  ==> ExpressionFunctions2
  EFI  ==> Expression Fraction Integer
  FI  ==> Fraction Integer
  LEDF  ==> List Expression DoubleFloat
  KEDF  ==> Kernel Expression DoubleFloat
  EEDF  ==> Equation Expression DoubleFloat
  EDF  ==> Expression DoubleFloat
  PDF  ==> Polynomial DoubleFloat
  LDF  ==> List DoubleFloat
  SDF  ==> Stream DoubleFloat
```

```
DF  ==> DoubleFloat
F  ==> Float
ST  ==> String
LST  ==> List String
SI  ==> SingleInteger
SOCDF  ==> Segment OrderedCompletion DoubleFloat
OCDF  ==> OrderedCompletion DoubleFloat
OCEDF  ==> OrderedCompletion Expression DoubleFloat
EOCEFI  ==> Equation OrderedCompletion Expression Fraction Integer
OCEFI   ==> OrderedCompletion Expression Fraction Integer
OCFI    ==> OrderedCompletion Fraction Integer
NIA  ==> Record(var:Symbol,fn:EDF,range:SOCDF,abserr:DF,relerr:DF)
INT  ==> Integer
CTYPE  ==> Union(continuous: "Continuous at the end points",
           lowerSingular: "There is a singularity at the lower end point",
            upperSingular: "There is a singularity at the upper end point",
             bothSingular: "There are singularities at both end points",
              notEvaluated: "End point continuity not yet evaluated")
RTYPE  ==> Union(finite: "The range is finite",
            lowerInfinite: "The bottom of range is infinite",
              upperInfinite: "The top of range is infinite",
                bothInfinite: "Both top and bottom points are infinite",
                  notEvaluated: "Range not yet evaluated")
STYPE  ==> Union(str:SDF,
                 notEvaluated:"Internal singularities not yet evaluated")
ATT  ==> Record(endPointContinuity:CTYPE,
                 singularitiesStream:STYPE,range:RTYPE)
ROA  ==> Record(key:NIA,entry:ATT)

E ==> with

  showTheFTable:() -> $
    ++ showTheFTable() returns the current table of functions.
  clearTheFTable : () -> Void
    ++ clearTheFTable() clears the current table of functions.
  keys : $ -> List(NIA)
    ++ keys(f) returns the list of keys of f
  fTable: List Record(key:NIA,entry:ATT) -> $
    ++ fTable(l) creates a functions table from the elements of l.
  insert!:Record(key:NIA,entry:ATT) -> $
    ++ insert!(r) inserts an entry r into theIFTable
  showAttributes:NIA -> Union(ATT,"failed")
    ++ showAttributes(x) is not documented
  entries : $ -> List Record(key:NIA,entry:ATT)
    ++ entries(x) is not documented
  entry:NIA -> ATT
    ++ entry(n) is not documented
I ==> add

  Rep := Table(NIA,ATT)
```

```
    import Rep

    theFTable:$ := empty()$Rep

    showTheFTable():$ ==
      theFTable

    clearTheFTable():Void ==
      theFTable := empty()$Rep
      void()$Void

    fTable(l:List Record(key:NIA,entry:ATT)):$ ==
      theFTable := table(l)$Rep

    insert!(r:Record(key:NIA,entry:ATT)):$ ==
      insert!(r,theFTable)$Rep

    keys(t:$):List NIA ==
      keys(t)$Rep

    showAttributes(k:NIA):Union(ATT,"failed") ==
      search(k,theFTable)$Rep

    entries(t:$):List Record(key:NIA,entry:ATT) ==
      members(t)$Rep

    entry(k:NIA):ATT ==
      qelt(theFTable,k)$Rep
```

———-

— INTFTBL.dotabb —

```
"INTFTBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INTFTBL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"INTFTBL" -> "TBAGG"
```

———-

10.33 domain IR IntegrationResult

— IntegrationResult.input —

```
)set break resume
```

```
)sys rm -f IntegrationResult.output
)spool IntegrationResult.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show IntegrationResult
--R
--R IntegrationResult(F: Field)  is a domain constructor
--R Abbreviation for IntegrationResult is IR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IR
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,Fraction(Integer)) -> %      ?*? : (Fraction(Integer),%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           coerce : F -> %
--R coerce : % -> OutputForm              differentiate : (%,(F -> F)) -> F
--R elem? : % -> Boolean                  hash : % -> SingleInteger
--R integral : (F,F) -> %                 latex : % -> String
--R ratpart : % -> F                      retract : % -> F
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R differentiate : (%,Symbol) -> F if F has PDRING(SYMBOL)
--R integral : (F,Symbol) -> % if F has RETRACT(SYMBOL)
--R logpart : % -> List(Record(scalar: Fraction(Integer),coeff: SparseUnivariatePolynomial(F),lo
--R mkAnswer : (F,List(Record(scalar: Fraction(Integer),coeff: SparseUnivariatePolynomial(F),log
--R notelem : % -> List(Record(integrand: F,intvar: F))
--R retractIfCan : % -> Union(F,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-

— IntegrationResult.help —


```
=====================================================================
IntegrationResult examples
=====================================================================

See Also:
```

```
o )show IntegrationResult
```

———-

10.33.1 IntegrationResult (IR)



Exports:

0	coerce	differentiate	elem?	hash
integral	latex	logpart	mkAnswer	notelem
ratpart	retract	retractIfCan	subtractIfCan	sample
zero?	?~=?	?*?	?+?	?-?
-?	?=?			

— domain IR IntegrationResult —

```
)abbrev domain IR IntegrationResult
++ Author: Barry Trager, Manuel Bronstein
++ Date Created: 1987
++ Date Last Updated: 12 August 1992
++ Keywords: integration.
++ Description:
++ The result of a transcendental integration.
++ If a function f has an elementary integral g, then g can be written
++ in the form \spad{g = h + c1 log(u1) + c2 log(u2) + ... + cn log(un)}
++ where h, which is in the same field than f, is called the rational
++ part of the integral, and \spad{c1 log(u1) + ... cn log(un)} is called the
++ logarithmic part of the integral. This domain manipulates integrals
++ represented in that form, by keeping both parts separately. The logs
++ are not explicitly computed.

IntegrationResult(F:Field): Exports == Implementation where
  O   ==> OutputForm
  B   ==> Boolean
  Z   ==> Integer
  Q   ==> Fraction Integer
```

```
SE  ==> Symbol
UP  ==> SparseUnivariatePolynomial F
LOG ==> Record(scalar:Q, coeff:UP, logand:UP)
NE  ==> Record(integrand:F, intvar:F)

Exports ==> (Module Q, RetractableTo F) with
  mkAnswer: (F, List LOG, List NE) -> %
    ++ mkAnswer(r,l,ne) creates an integration result from
    ++ a rational part r, a logarithmic part l, and a non-elementary part ne.
  ratpart : % -> F
    ++ ratpart(ir) returns the rational part of an integration result
  logpart : % -> List LOG
    ++ logpart(ir) returns the logarithmic part of an integration result
  notelem : % -> List NE
    ++ notelem(ir) returns the non-elementary part of an integration result
  elem?   : % -> B
    ++ elem?(ir) tests if an integration result is elementary over F?
  integral: (F, F) -> %
    ++ integral(f,x) returns the formal integral of f with respect to x
  differentiate: (%, F -> F) -> F
    ++ differentiate(ir,D) differentiates ir with respect to the derivation D.
  if F has PartialDifferentialRing(SE) then
    differentiate: (%, Symbol) -> F
      ++ differentiate(ir,x) differentiates ir with respect to x
  if F has RetractableTo Symbol then
    integral: (F, Symbol) -> %
      ++ integral(f,x) returns the formal integral of f with respect to x

Implementation ==> add
  Rep := Record(ratp: F, logp: List LOG, nelem: List NE)

  timelog : (Q, LOG) -> LOG
  timene  : (Q, NE)  -> NE
  LOG2O   : LOG      -> O
  NE2O    : NE       -> O
  Q2F     : Q        -> F
  nesimp  : List NE  -> List NE
  neselect: (List NE, F) -> F
  pLogDeriv: (LOG, F -> F) -> F
  pNeDeriv : (NE,  F -> F) -> F


  alpha:O := new()$Symbol :: O

  - u               == (-1$Z) * u
  0                 == mkAnswer(0, empty(), empty())
  coerce(x:F):%     == mkAnswer(x, empty(), empty())
  ratpart u         == u.ratp
  logpart u         == u.logp
  notelem u         == u.nelem
```

```
    elem? u           == empty? notelem u
    mkAnswer(x, l, n) == [x, l, nesimp n]
    timelog(r, lg)    == [r * lg.scalar, lg.coeff, lg.logand]
    integral(f:F,x:F) == (zero? f => 0; mkAnswer(0, empty(), [[f, x]]))
    timene(r, ne)     == [Q2F(r) * ne.integrand, ne.intvar]
    n:Z * u:%         == (n::Q) * u
    Q2F r             == numer(r)::F / denom(r)::F
    neselect(l, x)    == _+/[ne.integrand for ne in l | ne.intvar = x]

    if F has RetractableTo Symbol then
      integral(f:F, x:Symbol):% == integral(f, x::F)

    LOG2O rec ==
--      one? degree rec.coeff =>
      (degree rec.coeff) = 1 =>
        -- deg 1 minimal poly doesn't get sigma
        lastc := - coefficient(rec.coeff, 0) / coefficient(rec.coeff, 1)
        lg    := (rec.logand) lastc
        logandp := prefix("log"::Symbol::O, [lg::O])
        (cc := Q2F(rec.scalar) * lastc) = 1 => logandp
        cc = -1 => - logandp
        cc::O * logandp
      coeffp:O := (outputForm(rec.coeff, alpha) = 0::Z::O)@O
      logandp :=
           alpha * prefix("log"::Symbol::O, [outputForm(rec.logand, alpha)])
      if (cc := Q2F(rec.scalar)) ^= 1 then
        logandp := cc::O * logandp
      sum(logandp, coeffp)

    nesimp l ==
      [[u,x] for x in removeDuplicates_!([ne.intvar for ne in l]$List(F))
                                          | (u := neselect(l, x)) ^= 0]

    if (F has LiouvillianFunctionCategory) and (F has RetractableTo Symbol) then
      retractIfCan u ==
        empty? logpart u =>
          ratpart u +
             _+/[integral(ne.integrand, retract(ne.intvar)@Symbol)$F
                for ne in notelem u]
        "failed"

    else
      retractIfCan u ==
        elem? u and empty? logpart u => ratpart u
        "failed"

    r:Q * u:% ==
      r = 0 => 0
      mkAnswer(Q2F(r) * ratpart u, map(x1+->timelog(r, x1), logpart u),
                                      map(x2+->timene(r, x2), notelem u))
```

```
    -- Initial attempt, quick and dirty, no simplification
    u + v ==
      mkAnswer(ratpart u + ratpart v, concat(logpart u, logpart v),
                                    nesimp concat(notelem u, notelem v))

    if F has PartialDifferentialRing(Symbol) then
      differentiate(u:%, x:Symbol):F ==
        differentiate(u, x1+->differentiate(x1, x))

    differentiate(u:%, derivation:F -> F):F ==
      derivation ratpart u +
          _+/[pLogDeriv(log, derivation) for log in logpart u]
               + _+/[pNeDeriv(ne, derivation) for ne in notelem u]

    pNeDeriv(ne, derivation) ==
--      one? derivation(ne.intvar) => ne.integrand
      (derivation(ne.intvar) = 1) => ne.integrand
      zero? derivation(ne.integrand) => 0
      error "pNeDeriv: cannot differentiate not elementary part into F"

    pLogDeriv(log, derivation) ==
      map(derivation, log.coeff) ^= 0 =>
        error "pLogDeriv: can only handle logs with constant coefficients"
--      one?(n := degree(log.coeff)) =>
      ((n := degree(log.coeff)) = 1) =>
        c   := - (leadingCoefficient reductum log.coeff)
                                       / (leadingCoefficient log.coeff)
        ans := (log.logand) c
        Q2F(log.scalar) * c * derivation(ans) / ans
      numlog := map(derivation, log.logand)
      diflog := extendedEuclidean(log.logand, log.coeff,
                                    numlog)::Record(coef1:UP, coef2:UP)
      algans := diflog.coef1
      ans:F := 0
      for i in 0..(n-1) repeat
        algans := algans * monomial(1, 1) rem log.coeff
        ans := ans + coefficient(algans, i)
      Q2F(log.scalar) * ans

    coerce(u:%):O ==
      (r := retractIfCan u) case F => r::F::O
      l := reverse_! [LOG2O f for f in logpart u]$List(O)
      if ratpart u ^= 0 then l := concat(ratpart(u)::O, l)
      if not elem? u then l := concat([NE2O f for f in notelem u], l)
      null l => 0::O
      reduce("+", l)

    NE2O ne ==
      int((ne.integrand)::O * hconcat ["d"::Symbol::O, (ne.intvar)::O])
```

———-

— IR.dotabb —

```
"IR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IR"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"IR" -> "ALIST"
```

———-

10.34 domain INTRVL Interval

— Interval.input —

```
)set break resume
)sys rm -f Interval.output
)spool Interval.output
)set message test on
)set message auto off
)clear all

--S 1 of 13
t1:=0::Interval(Float)
--R
--R
--R   (1)  [0.0,0.0]
--R                                                    Type: Interval Float
--E 1

--S 2 of 13
t2:=1::Interval(Float)
--R
--R
--R   (2)  [1.0,1.0]
--R                                                    Type: Interval Float
--E 2

--S 3 of 13
t3:=3*t1
--R
--R
--R   (3)  [- 0.3 E -20,0.3 E -20]
--R                                                    Type: Interval Float
```

```
--E 3

--S 4 of 13
t4:=1/4*t2
--R
--R
--R        [1.0,1.0]
--R   (4)  ---------
--R        [4.0,4.0]
--R                                                Type: Fraction Interval Float
--E 4

--S 5 of 13
acos(t3)
--R
--R
--R   (5)  [1.5707963267 948966192,1.5707963267 948966192]
--R                                                      Type: Interval Float
--E 5

--S 6 of 13
t6:=t4*t4
--R
--R
--R         [1.0,1.0]
--R   (6)  -----------
--R        [16.0,16.0]
--R                                                Type: Fraction Interval Float
--E 6

--S 7 of 13
sup(t6)
--R
--R
--R   (7)  0.0625000000 0000000000 1
--R                                                              Type: Float
--E 7

--S 8 of 13
inf(t6)
--R
--R
--R   (8)  0.0624999999 9999999999 9
--R                                                              Type: Float
--E 8

--S 9 of 13
width(t6)
--R
--R
```

```
--R   (9)  0.1 E -20
--R                                                                Type: Float
--E 9

--S 10 of 13
positive? t3
--R
--R
--R   (10)  false
--R                                                               Type: Boolean
--E 10

--S 11 of 13
negative? t3
--R
--R
--R   (11)  false
--R                                                               Type: Boolean
--E 11

--S 12 of 13
contains?(t3,0.3)
--R
--R
--R   (12)  false
--R                                                               Type: Boolean
--E 12

--S 13 of 13
)show Interval
--R
--R Interval R: Join(FloatingPointSystem,TranscendentalFunctionCategory)  is a domain constructor
--R Abbreviation for Interval is INTRVL
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for INTRVL
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Fraction Integer) -> %
--R ?**? : (%,%) -> %                     ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        acos : % -> %
--R acosh : % -> %                        acot : % -> %
--R acoth : % -> %                        acsc : % -> %
--R acsch : % -> %                        asec : % -> %
--R asech : % -> %                        asin : % -> %
```

```
--R asinh : % -> %                          associates? : (%,%) -> Boolean
--R atan : % -> %                           atanh : % -> %
--R coerce : Integer -> %                   coerce : % -> %
--R coerce : Integer -> %                   coerce : % -> OutputForm
--R contains? : (%,R) -> Boolean            cos : % -> %
--R cosh : % -> %                           cot : % -> %
--R coth : % -> %                           csc : % -> %
--R csch : % -> %                           exp : % -> %
--R gcd : List % -> %                       gcd : (%,%) -> %
--R hash : % -> SingleInteger               inf : % -> R
--R interval : Fraction Integer -> %        interval : R -> %
--R interval : (R,R) -> %                   latex : % -> String
--R lcm : List % -> %                       lcm : (%,%) -> %
--R log : % -> %                           max : (%,%) -> %
--R min : (%,%) -> %                       negative? : % -> Boolean
--R nthRoot : (%,Integer) -> %             one? : % -> Boolean
--R pi : () -> %                           positive? : % -> Boolean
--R qinterval : (R,R) -> %                 recip : % -> Union(%,"failed")
--R retract : % -> Integer                 sample : () -> %
--R sec : % -> %                           sech : % -> %
--R sin : % -> %                           sinh : % -> %
--R sqrt : % -> %                          sup : % -> R
--R tan : % -> %                           tanh : % -> %
--R unit? : % -> Boolean                   unitCanonical : % -> %
--R width : % -> R                         zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R exquo : (%,%) -> Union(%,"failed")
--R gcdPolynomial : (SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> SparseUnivari
--R retractIfCan : % -> Union(Integer,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 13

)spool
)lisp (bye)
```

———-

— Interval.help —

```
=====================================================================
Interval examples
=====================================================================
```

```
t1:=0::Interval(Float)
   [0.0,0.0]

t2:=1::Interval(Float)
   [1.0,1.0]

t3:=3*t1
   [- 0.3 E -20,0.3 E -20]

t4:=1/4*t2
   [1.0,1.0]
   ---------
   [4.0,4.0]

acos(t3)
   [1.5707963267 948966192,1.5707963267 948966192]

t6:=t4*t4
   [1.0,1.0]
   -----------
   [16.0,16.0]

sup(t6)
   0.0625000000 0000000000 1

inf(t6)
   0.0624999999 9999999999 9


width(t6)
   0.1 E -20

positive? t3
   false

negative? t3
   false

contains?(t3,0.3)
   false
```

10.34.1 Interval (INTRVL)



Exports:

0	1	acos	acosh	acot
acoth	acsc	acsch	asec	asech
asin	asinh	associates?	atan	atanh
characteristic	coerce	contains?	cos	cosh
cot	coth	csc	csch	exp
exquo	gcd	gcdPolynomial	hash	inf
interval	latex	lcm	log	max
min	negative?	nthRoot	one?	pi
positive?	qinterval	recip	retract	retractIfCan
sample	sec	sech	sin	sinh
sqrt	subtractIfCan	sup	tan	tanh
unit?	unitCanonical	unitNormal	width	zero?
?*?	?**?	?+?	?-?	-?
?<?	?<=?	?=?	?>?	?>=?
?^?	?~=?			

— domain INTRVL Interval —

```
)abbrev domain INTRVL Interval
++ Author: Mike Dewar
++ Date Created: November 1996
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain is an implementation of interval arithmetic and transcendental
++ functions over intervals.

Interval(R:Join(FloatingPointSystem,TranscendentalFunctionCategory)): IntervalCategory(R) == add
```

```
  import Integer
--  import from R

  Rep := Record(Inf:R, Sup:R)

  roundDown(u:R):R ==
    if zero?(u) then float(-1,-(bits() pretend Integer))
                else float(mantissa(u) - 1,exponent(u))

  roundUp(u:R):R   ==
    if zero?(u) then float(1, -(bits()) pretend Integer)
                else float(mantissa(u) + 1,exponent(u))

  -- Sometimes the float representation does not use all the bits (e.g. when
  -- representing an integer in software using arbitrary-length Integers as
  -- your mantissa it is convenient to keep them exact).  This function
  -- normalises things so that rounding etc. works as expected.  It is only
  -- called when creating new intervals.
  normaliseFloat(u:R):R ==
    zero? u => u
    m : Integer := mantissa u
    b : Integer := bits() pretend Integer
    l : Integer := length(m)
    if l < b then
      BASE : Integer := base()$R pretend Integer
      float(m*BASE**((b-l) pretend PositiveInteger),exponent(u)-b+l)
    else
      u

  interval(i:R,s:R):% ==
    i > s =>  [roundDown normaliseFloat s,roundUp normaliseFloat i]
    [roundDown normaliseFloat i,roundUp normaliseFloat s]

  interval(f:R):% ==
    zero?(f) => 0
    one?(f)  => 1
    -- This next part is necessary to allow e.g. mapping between Expressions:
    -- AXIOM assumes that Integers stay as Integers!
--    import from Union(value1:Integer,failed:"failed")
    fnew : R := normaliseFloat f
    retractIfCan(f)@Union(Integer,"failed") case "failed" =>
      [roundDown fnew, roundUp fnew]
    [fnew,fnew]

  qinterval(i:R,s:R):% ==
    [roundDown normaliseFloat i,roundUp normaliseFloat s]

  exactInterval(i:R,s:R):% == [i,s]
  exactSupInterval(i:R,s:R):% == [roundDown i,s]
```

```
exactInfInterval(i:R,s:R):% == [i,roundUp s]

inf(u:%):R == u.Inf
sup(u:%):R == u.Sup
width(u:%):R == u.Sup - u.Inf

contains?(u:%,f:R):Boolean == (f > inf(u)) and (f < sup(u))

positive?(u:%):Boolean == inf(u) > 0
negative?(u:%):Boolean == sup(u) < 0

_< (a:%,b:%):Boolean ==
  if inf(a) < inf(b) then
    true
  else if inf(a) > inf(b) then
    false
  else
    sup(a) < sup(b)

_+ (a:%,b:%):% ==
  -- A couple of blatent hacks to preserve the Ring Axioms!
  if zero?(a) then return(b) else if zero?(b) then return(a)
  if a = b then return qinterval(2*inf(a),2*sup(a))
  qinterval(inf(a) + inf(b), sup(a) + sup(b))


_- (a:%,b:%):% ==
  if zero?(a) then return(-b) else if zero?(b) then return(a)
  if a = b then 0 else qinterval(inf(a) - sup(b), sup(a) - inf(b))


_* (a:%,b:%):% ==
  -- A couple of blatent hacks to preserve the Ring Axioms!
  if one?(a) then return(b) else if one?(b) then return(a)
  if zero?(a) then return(0) else if zero?(b) then return(0)
  prods : List R :=  sort [inf(a)*inf(b),sup(a)*sup(b),
                           inf(a)*sup(b),sup(a)*inf(b)]
  qinterval(first prods, last prods)


_* (a:Integer,b:%):% ==
  if (a > 0) then
    qinterval(a*inf(b),a*sup(b))
  else if (a < 0) then
    qinterval(a*sup(b),a*inf(b))
  else
    0

_* (a:PositiveInteger,b:%):% == qinterval(a*inf(b),a*sup(b))
```

```
  _*_* (a:%,n:PositiveInteger):% ==
    contains?(a,0) and zero?((n pretend Integer) rem 2) =>
      interval(0,max(inf(a)**n,sup(a)**n))
    interval(inf(a)**n,sup(a)**n)


  _^ (a:%,n:PositiveInteger):% ==
    contains?(a,0) and zero?((n pretend Integer) rem 2) =>
      interval(0,max(inf(a)**n,sup(a)**n))
    interval(inf(a)**n,sup(a)**n)

  _- (a:%):% == exactInterval(-sup(a),-inf(a))

  _= (a:%,b:%):Boolean == (inf(a)=inf(b)) and (sup(a)=sup(b))
  _~_= (a:%,b:%):Boolean == (inf(a)~=inf(b)) or (sup(a)~=sup(b))

  1 ==
    one : R := normaliseFloat 1
    [one,one]

  0 == [0,0]

  recip(u:%):Union(%,"failed") ==
   contains?(u,0) => "failed"
   vals:List R := sort [1/inf(u),1/sup(u)]$List(R)
   qinterval(first vals, last vals)


  unit?(u:%):Boolean == contains?(u,0)

  _exquo(u:%,v:%):Union(%,"failed") ==
   contains?(v,0) => "failed"
   one?(v) => u
   u=v => 1
   u=-v => -1
   vals:List R := sort [inf(u)/inf(v),inf(u)/sup(v),sup(u)/inf(v),sup(u)/sup(v)]$List(R)
   qinterval(first vals, last vals)


  gcd(u:%,v:%):% == 1

  coerce(u:Integer):% ==
    ur := normaliseFloat(u::R)
    exactInterval(ur,ur)


  interval(u:Fraction Integer):% ==
--    import   log2 : % -> %
--             coerce : Integer -> %
--             retractIfCan : % -> Union(value1:Integer,failed:"failed")
```

```
--    from Float
    flt := u::R

    -- Test if the representation in R is exact
    --den := denom(u)::Float
    bin : Union(Integer,"failed") := retractIfCan(log2(denom(u)::Float))
    bin case Integer and length(numer u)$Integer < (bits() pretend Integer) =>
      flt := normaliseFloat flt
      exactInterval(flt,flt)

    qinterval(flt,flt)


  retractIfCan(u:%):Union(Integer,"failed") ==
    not zero? width(u) => "failed"
    retractIfCan inf u


  retract(u:%):Integer ==
    not zero? width(u) =>
      error "attempt to retract a non-Integer interval to an Integer"
    retract inf u


  coerce(u:%):OutputForm ==
    bracket([coerce inf(u), coerce sup(u)]$List(OutputForm))

  characteristic():NonNegativeInteger == 0


  -- Explicit export from TranscendentalFunctionCategory
  pi():% == qinterval(pi(),pi())

  -- From ElementaryFunctionCategory
  log(u:%):% ==
    positive?(u) => qinterval(log inf u, log sup u)
    error "negative logs in interval"


  exp(u:%):% == qinterval(exp inf u, exp sup u)

  _*_* (u:%,v:%):% ==
    zero?(v) => if zero?(u) then error "0**0 is undefined" else 1
    one?(u)  => 1
    expts : List R :=  sort [inf(u)**inf(v),sup(u)**sup(v),
                            inf(u)**sup(v),sup(u)**inf(v)]
    qinterval(first expts, last expts)

  -- From TrigonometricFunctionCategory
```

```
-- This function checks whether an interval contains a value of the form
-- 'offset + 2 n pi'.
hasTwoPiMultiple(offset:R,ipi:R,i:%):Boolean ==
  next : Integer := retract ceiling( (inf(i) - offset)/(2*ipi) )
  contains?(i,offset+2*next*ipi)


-- This function checks whether an interval contains a value of the form
-- 'offset + n pi'.
hasPiMultiple(offset:R,ipi:R,i:%):Boolean ==
  next : Integer := retract ceiling( (inf(i) - offset)/ipi )
  contains?(i,offset+next*ipi)


sin(u:%):% ==
  ipi : R := pi()$R
  hasOne? : Boolean := hasTwoPiMultiple(ipi/(2::R),ipi,u)
  hasMinusOne? : Boolean := hasTwoPiMultiple(3*ipi/(2::R),ipi,u)

  if hasOne? and hasMinusOne? then
    exactInterval(-1,1)
  else
    vals : List R := sort [sin inf u, sin sup u]
    if hasOne? then
      exactSupInterval(first vals, 1)
    else if hasMinusOne? then
      exactInfInterval(-1,last vals)
    else
      qinterval(first vals, last vals)



cos(u:%):% ==
  ipi : R := pi()
  hasOne? : Boolean := hasTwoPiMultiple(0,ipi,u)
  hasMinusOne? : Boolean := hasTwoPiMultiple(ipi,ipi,u)

  if hasOne? and hasMinusOne? then
    exactInterval(-1,1)
  else
    vals : List R := sort [cos inf u, cos sup u]
    if hasOne? then
      exactSupInterval(first vals, 1)
    else if hasMinusOne? then
      exactInfInterval(-1,last vals)
    else
      qinterval(first vals, last vals)
```

```
  tan(u:%):% ==
    ipi : R := pi()
    if width(u) > ipi then
      error "Interval contains a singularity"
    else
      -- Since we know the interval is less than pi wide, monotonicity implies
      -- that there is no singularity.  If there is a singularity on a endpoint
      -- of the interval the user will see the error generated by R.
      lo : R := tan inf u
      hi : R := tan sup u

      lo > hi => error "Interval contains a singularity"
      qinterval(lo,hi)



  csc(u:%):% ==
    ipi : R := pi()
    if width(u) > ipi then
      error "Interval contains a singularity"
    else
--      import from Integer
      -- singularities are at multiples of Pi
      if hasPiMultiple(0,ipi,u) then error "Interval contains a singularity"
      vals : List R := sort [csc inf u, csc sup u]
      if hasTwoPiMultiple(ipi/(2::R),ipi,u) then
        exactInfInterval(1,last vals)
      else if hasTwoPiMultiple(3*ipi/(2::R),ipi,u) then
        exactSupInterval(first vals,-1)
      else
        qinterval(first vals, last vals)



  sec(u:%):% ==
    ipi : R := pi()
    if width(u) > ipi then
      error "Interval contains a singularity"
    else
--      import from Integer
      -- singularities are at Pi/2 + n Pi
      if hasPiMultiple(ipi/(2::R),ipi,u) then
        error "Interval contains a singularity"
      vals : List R := sort [sec inf u, sec sup u]
      if hasTwoPiMultiple(0,ipi,u) then
        exactInfInterval(1,last vals)
      else if hasTwoPiMultiple(ipi,ipi,u) then
        exactSupInterval(first vals,-1)
      else
        qinterval(first vals, last vals)
```

```
cot(u:%):% ==
  ipi : R := pi()
  if width(u) > ipi then
    error "Interval contains a singularity"
  else
    -- Since we know the interval is less than pi wide, monotonicity implies
    -- that there is no singularity.  If there is a singularity on a endpoint
    -- of the interval the user will see the error generated by R.
    hi : R := cot inf u
    lo : R := cot sup u

    lo > hi => error "Interval contains a singularity"
    qinterval(lo,hi)



-- From ArcTrigonometricFunctionCategory

asin(u:%):% ==
  lo : R := inf(u)
  hi : R := sup(u)
  if (lo < -1) or (hi > 1) then error "asin only defined on the region -1..1"
  qinterval(asin lo,asin hi)


acos(u:%):% ==
  lo : R := inf(u)
  hi : R := sup(u)
  if (lo < -1) or (hi > 1) then error "acos only defined on the region -1..1"
  qinterval(acos hi,acos lo)


atan(u:%):% == qinterval(atan inf u, atan sup u)

acot(u:%):% == qinterval(acot sup u, acot inf u)

acsc(u:%):% ==
  lo : R := inf(u)
  hi : R := sup(u)
  if ((lo <= -1) and (hi >= -1)) or ((lo <= 1) and (hi >= 1)) then
    error "acsc not defined on the region -1..1"
  qinterval(acsc hi, acsc lo)


asec(u:%):% ==
  lo : R := inf(u)
```

```
  hi : R := sup(u)
  if ((lo < -1) and (hi > -1)) or ((lo < 1) and (hi > 1)) then
    error "asec not defined on the region -1..1"
  qinterval(asec lo, asec hi)


-- From HyperbolicFunctionCategory

tanh(u:%):% == qinterval(tanh inf u, tanh sup u)

sinh(u:%):% == qinterval(sinh inf u, sinh sup u)

sech(u:%):% ==
  negative? u => qinterval(sech inf u, sech sup u)
  positive? u => qinterval(sech sup u, sech inf u)
  vals : List R := sort [sech inf u, sech sup u]
  exactSupInterval(first vals,1)


cosh(u:%):% ==
  negative? u => qinterval(cosh sup u, cosh inf u)
  positive? u => qinterval(cosh inf u, cosh sup u)
  vals : List R := sort [cosh inf u, cosh sup u]
  exactInfInterval(1,last vals)


csch(u:%):% ==
  contains?(u,0) => error "csch: singularity at zero"
  qinterval(csch sup u, csch inf u)


coth(u:%):% ==
  contains?(u,0) => error "coth: singularity at zero"
  qinterval(coth sup u, coth inf u)


-- From ArcHyperbolicFunctionCategory

acosh(u:%):% ==
  inf(u)<1 => error "invalid argument: acosh only defined on the region 1.."
  qinterval(acosh inf u, acosh sup u)


acoth(u:%):% ==
  lo : R := inf(u)
  hi : R := sup(u)
  if ((lo <= -1) and (hi >= -1)) or ((lo <= 1) and (hi >= 1)) then
    error "acoth not defined on the region -1..1"
  qinterval(acoth hi, acoth lo)
```

```
  acsch(u:%):% ==
    contains?(u,0) => error "acsch: singularity at zero"
    qinterval(acsch sup u, acsch inf u)


  asech(u:%):% ==
    lo : R := inf(u)
    hi : R := sup(u)
    if  (lo <= 0) or (hi > 1) then
      error "asech only defined on the region 0 < x <= 1"
    qinterval(asech hi, asech lo)


  asinh(u:%):% == qinterval(asinh inf u, asinh sup u)

  atanh(u:%):% ==
    lo : R := inf(u)
    hi : R := sup(u)
    if  (lo <= -1) or (hi >= 1) then
      error "atanh only defined on the region -1 < x < 1"
    qinterval(atanh lo, atanh hi)


  -- From RadicalCategory
  _*_* (u:%,n:Fraction Integer):% == interval(inf(u)**n,sup(u)**n)
```

———-

— INTRVL.dotabb —

```
"INTRVL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=INTRVL"]
"INTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=INTCAT"]
"INTRVL" -> "INTCAT"
```

———-

Chapter 11

Chapter J

Chapter 12

Chapter K

12.1 domain KERNEL Kernel

— Kernel.input —

```
)set break resume
)sys rm -f Kernel.output
)spool Kernel.output
)set message test on
)set message auto off
)clear all
--S 1 of 19
x :: Expression Integer
--R
--R
--R   (1)  x
--R                                                    Type: Expression(Integer)
--E 1

--S 2 of 19
kernel x
--R
--R
--R   (2)  x
--R                                          Type: Kernel(Expression(Integer))
--E 2

--S 3 of 19
sin(x) + cos(x)
--R
--R
--R   (3)  sin(x) + cos(x)
```

```
--R                                                    Type: Expression(Integer)
--E 3

--S 4 of 19
kernels %
--R
--R
--R   (4)  [sin(x),cos(x)]
--R                                       Type: List(Kernel(Expression(Integer)))
--E 4

--S 5 of 19
sin(x)**2 + sin(x) + cos(x)
--R
--R
--R              2
--R   (5)  sin(x)  + sin(x) + cos(x)
--R                                                    Type: Expression(Integer)
--E 5

--S 6 of 19
kernels %
--R
--R
--R   (6)  [sin(x),cos(x)]
--R                                       Type: List(Kernel(Expression(Integer)))
--E 6

--S 7 of 19
kernels(1 :: Expression Integer)
--R
--R
--R   (7)  []
--R                                       Type: List(Kernel(Expression(Integer)))
--E 7

--S 8 of 19
mainKernel(cos(x) + tan(x))
--R
--R
--R   (8)  tan(x)
--R                                  Type: Union(Kernel(Expression(Integer)),...)
--E 8

--S 9 of 19
height kernel x
--R
--R
--R   (9)  1
--R                                                       Type: PositiveInteger
```

```
--E 9

--S 10 of 19
height mainKernel(sin x)
--R
--R
--R   (10)  2
--R                                                    Type: PositiveInteger
--E 10

--S 11 of 19
height mainKernel(sin cos x)
--R
--R
--R   (11)  3
--R                                                    Type: PositiveInteger
--E 11

--S 12 of 19
height mainKernel(sin cos (tan x + sin x))
--R
--R
--R   (12)  4
--R                                                    Type: PositiveInteger
--E 12

--S 13 of 19
operator mainKernel(sin cos (tan x + sin x))
--R
--R
--R   (13)  sin
--R                                                     Type: BasicOperator
--E 13

--S 14 of 19
name mainKernel(sin cos (tan x + sin x))
--R
--R
--R   (14)  sin
--R                                                            Type: Symbol
--E 14

--S 15 of 19
f := operator 'f
--R
--R
--R   (15)  f
--R                                                     Type: BasicOperator
--E 15
```

```
--S 16 of 19
e := f(x, y, 10)
--R
--R
--R   (16)  f(x,y,10)
--R                                                  Type: Expression(Integer)
--E 16

--S 17 of 19
is?(e, f)
--R
--R
--R   (17)  true
--R                                                             Type: Boolean
--E 17

--S 18 of 19
is?(e, 'f)
--R
--R
--R   (18)  true
--R                                                             Type: Boolean
--E 18

--S 19 of 19
argument mainKernel e
--R
--R
--R   (19)  [x,y,10]
--R                                          Type: List(Expression(Integer))
--E 19
)spool
)lisp (bye)
```

———-

— Kernel.help —

```
====================================================================
Kernel examples
====================================================================

A kernel is a symbolic function application (such as sin(x+ y))
or a symbol (such as x).  More precisely, a non-symbol
kernel over a set S is an operator applied to a given list of
arguments from S.  The operator has type BasicOperator
and the kernel object is usually part of an Expression object.

Kernels are created implicitly for you when you create expressions.
```

```
  x :: Expression Integer
    x
                          Type: Expression Integer
```

You can directly create a "symbol" kernel by using the kernel operation.

```
  kernel x
    x
                          Type: Kernel Expression Integer
```

This expression has two different kernels.

```
  sin(x) + cos(x)
    sin(x) + cos(x)
                          Type: Expression Integer
```

The operator kernels returns a list of the kernels in an object of type Expression.

```
  kernels %
    [sin(x),cos(x)]
                          Type: List Kernel Expression Integer
```

This expression also has two different kernels.

```
  sin(x)**2 + sin(x) + cos(x)
          2
    sin(x)  + sin(x) + cos(x)
                          Type: Expression Integer
```

The sin(x) kernel is used twice.

```
  kernels %
    [sin(x),cos(x)]
                          Type: List Kernel Expression Integer
```

An expression need not contain any kernels.

```
  kernels(1 :: Expression Integer)
    []
                          Type: List Kernel Expression Integer
```

If one or more kernels are present, one of them is designated the main kernel.

```
  mainKernel(cos(x) + tan(x))
    tan(x)
                          Type: Union(Kernel Expression Integer,...)
```

```
Kernels can be nested. Use height  to determine the nesting depth.

  height kernel x
    1
                          Type: PositiveInteger

This has height 2 because the x has height 1 and then we apply an
operator to that.

  height mainKernel(sin x)
    2
                          Type: PositiveInteger

  height mainKernel(sin cos x)
    3
                          Type: PositiveInteger

  height mainKernel(sin cos (tan x + sin x))
    4
                          Type: PositiveInteger

Use the operator operation to extract the operator component of the
kernel.  The operator has type BasicOperator.

  operator mainKernel(sin cos (tan x + sin x))
    sin
                          Type: BasicOperator

Use the name operation to extract the name of the operator component
of the kernel.  The name has type Symbol.  This is really just a
shortcut for a two-step process of extracting the operator and then
calling name on the operator.

  name mainKernel(sin cos (tan x + sin x))
    sin
                          Type: Symbol

Axiom knows about functions such as sin, cos and so on and can make
kernels and then expressions using them.  To create a kernel and
expression using an arbitrary operator, use operator.

Now f can be used to create symbolic function applications.

  f := operator 'f
    f
                         Type: BasicOperator

  e := f(x, y, 10)
    f(x,y,10)
                         Type: Expression Integer
```

```
Use the is? operation to learn if the operator component of a kernel
is equal to a given operator.

  is?(e, f)
    true
                        Type: Boolean

You can also use a symbol or a string as the second argument to is?.

  is?(e, 'f)
    true
                        Type: Boolean

Use the argument operation to get a list containing the argument
component of a kernel.


  argument mainKernel e
    [x,y,10]
                        Type: List Expression Integer

Conceptually, an object of type Expression can be thought of a
quotient of multivariate polynomials, where the "variables" are
kernels.  The arguments of the kernels are again expressions and so
the structure recurses.  See Expression for examples of using kernels
to take apart expression objects.

See Also:
o )help Expression
o )help BasicOperator
o )show Kernel
```

———-

12.1.1 Kernel (KERNEL)



See

⇒ "MakeCachableSet" (MKCHSET) 14.5.1 on page 1538

Exports:

argument	coerce	convert	hash	height
is?	kernel	latex	max	min
name	operator	position	setPosition	symbolIfCan
?~=?	?<?	?<=?	?=?	?>?
?>=?				

— domain KERNEL Kernel —

```
)abbrev domain KERNEL Kernel
++ Author: Manuel Bronstein
++ Date Created: 22 March 1988
++ Date Last Updated: 10 August 1994
++ Description:
++ A kernel over a set S is an operator applied to a given list
++ of arguments from S.

Kernel(S:OrderedSet): Exports == Implementation where
  O  ==> OutputForm
  N  ==> NonNegativeInteger
  OP ==> BasicOperator

  SYMBOL  ==> "%symbol"
  PMPRED  ==> "%pmpredicate"
  PMOPT   ==> "%pmoptional"
  PMMULT  ==> "%pmmultiple"
  PMCONST ==> "%pmconstant"
  SPECIALDISP  ==> "%specialDisp"
  SPECIALEQUAL ==> "%specialEqual"
  SPECIALINPUT ==> "%specialInput"

  Exports ==> Join(CachableSet, Patternable S) with
    name    : % -> Symbol
```

```
    ++ name(op(a1,...,an)) returns the name of op.
  operator: % -> OP
    ++ operator(op(a1,...,an)) returns the operator op.
  argument: % -> List S
    ++ argument(op(a1,...,an)) returns \spad{[a1,...,an]}.
  height  : % -> N
    ++ height(k) returns the nesting level of k.
  kernel  : (OP, List S, N) -> %
    ++ kernel(op, [a1,...,an], m) returns the kernel \spad{op(a1,...,an)}
    ++ of nesting level m.
    ++ Error: if op is k-ary for some k not equal to m.
  kernel  : Symbol -> %
    ++ kernel(x) returns x viewed as a kernel.
  symbolIfCan: % -> Union(Symbol, "failed")
    ++ symbolIfCan(k) returns k viewed as a symbol if k is a symbol, and
    ++ "failed" otherwise.
  is?     : (%, OP) -> Boolean
    ++ is?(op(a1,...,an), f) tests if op = f.
  is?     : (%, Symbol) -> Boolean
    ++ is?(op(a1,...,an), s) tests if the name of op is s.
  if S has ConvertibleTo InputForm then ConvertibleTo InputForm

Implementation ==> add
  import SortedCache(%)

  Rep := Record(op:OP, arg:List S, nest:N, posit:N)

  clearCache()

  B2Z   : Boolean -> Integer
  triage: (%, %)  -> Integer
  preds : OP      -> List Any

  is?(k:%, s:Symbol) == is?(operator k, s)
  is?(k:%, o:OP)     == (operator k) = o
  name k             == name operator k
  height k           == k.nest
  operator k         == k.op
  argument k         == k.arg
  position k         == k.posit
  setPosition(k, n)  == k.posit := n
  B2Z flag           == (flag => -1; 1)
  kernel s           == kernel(assert(operator(s,0),SYMBOL), nil(), 1)

  preds o ==
    (u := property(o, PMPRED)) case "failed" => nil()
    (u::None) pretend List(Any)

  symbolIfCan k ==
    has?(operator k, SYMBOL) => name operator k
```

```
    "failed"

  k1 = k2 ==
    if k1.posit = 0 then enterInCache(k1, triage)
    if k2.posit = 0 then enterInCache(k2, triage)
    k1.posit = k2.posit

  k1 < k2 ==
    if k1.posit = 0 then enterInCache(k1, triage)
    if k2.posit = 0 then enterInCache(k2, triage)
    k1.posit < k2.posit

  kernel(fn, x, n) ==
    ((u := arity fn) case N) and (#x ^= u::N)
                                  => error "Wrong number of arguments"
    enterInCache([fn, x, n, 0]$Rep, triage)

  -- SPECIALDISP contains a map List S -> OutputForm
  -- it is used when the converting the arguments first is not good,
  -- for instance with formal derivatives.
  coerce(k:%):OutputForm ==
    (v := symbolIfCan k) case Symbol => v::Symbol::OutputForm
    (f := property(o := operator k, SPECIALDISP)) case None =>
      ((f::None) pretend (List S -> OutputForm)) (argument k)
    l := [x::OutputForm for x in argument k]$List(OutputForm)
    (u := display o) case "failed" => prefix(name(o)::OutputForm, l)
    (u::(List OutputForm -> OutputForm)) l

  triage(k1, k2) ==
    k1.nest   ^= k2.nest   => B2Z(k1.nest   < k2.nest)
    k1.op ^= k2.op => B2Z(k1.op < k2.op)
    (n1 := #(argument k1)) ^= (n2 := #(argument k2)) => B2Z(n1 < n2)
    ((func := property(operator k1, SPECIALEQUAL)) case None) and
      (((func::None) pretend ((%, %) -> Boolean)) (k1, k2)) => 0
    for x1 in argument(k1) for x2 in argument(k2) repeat
      x1 ^= x2 => return B2Z(x1 < x2)
    0

  if S has ConvertibleTo InputForm then
    convert(k:%):InputForm ==
      (v := symbolIfCan k) case Symbol => convert(v::Symbol)@InputForm
      (f := property(o := operator k, SPECIALINPUT)) case None =>
        ((f::None) pretend (List S -> InputForm)) (argument k)
      l := [convert x for x in argument k]$List(InputForm)
      (u := input operator k) case "failed" =>
        convert concat(convert name operator k, l)
      (u::(List InputForm -> InputForm)) l

  if S has ConvertibleTo Pattern Integer then
    convert(k:%):Pattern(Integer) ==
```

```
        o := operator k
        (v := symbolIfCan k) case Symbol =>
          s  := patternVariable(v::Symbol,
                      has?(o, PMCONST), has?(o, PMOPT), has?(o, PMMULT))
          empty?(l := preds o) => s
          setPredicates(s, l)
        o [convert x for x in k.arg]$List(Pattern Integer)

    if S has ConvertibleTo Pattern Float then
      convert(k:%):Pattern(Float) ==
        o := operator k
        (v := symbolIfCan k) case Symbol =>
          s  := patternVariable(v::Symbol,
                      has?(o, PMCONST), has?(o, PMOPT), has?(o, PMMULT))
          empty?(l := preds o) => s
          setPredicates(s, l)
        o [convert x for x in k.arg]$List(Pattern Float)
```

———-

— **KERNEL.dotabb** —

```
"KERNEL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=KERNEL"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"KERNEL" -> "ALIST"
```

———-

12.2 domain KAFILE KeyedAccessFile

— **KeyedAccessFile.input** —

```
)set break resume
)sys rm -f KeyedAccessFile.output
)spool KeyedAccessFile.output
)set message test on
)set message auto off
)clear all

--S 1 of 20
ey: KeyedAccessFile(Integer) := open("editor.year", "output")
--R
--R
--R   (1)  "editor.year"
```

```
--R                                                Type: KeyedAccessFile(Integer)
--E 1

--S 2 of 20
ey."Char":= 1986
--R
--R
--R   (2)  1986
--R                                                   Type: PositiveInteger
--E 2

--S 3 of 20
ey."Caviness" := 1985
--R
--R
--R   (3)  1985
--R                                                   Type: PositiveInteger
--E 3

--S 4 of 20
ey."Fitch"    := 1984
--R
--R
--R   (4)  1984
--R                                                   Type: PositiveInteger
--E 4

--S 5 of 20
ey."Char"
--R
--R
--R   (5)  1986
--R                                                   Type: PositiveInteger
--E 5

--S 6 of 20
ey("Char")
--R
--R
--R   (6)  1986
--R                                                   Type: PositiveInteger
--E 6

--S 7 of 20
ey "Char"
--R
--R
--R   (7)  1986
--R                                                   Type: PositiveInteger
--E 7
```

```
--S 8 of 20
search("Char", ey)
--R
--R
--R   (8)  1986
--R                                                    Type: Union(Integer,...)
--E 8

--S 9 of 20
search("Smith", ey)
--R
--R
--R   (9)  "failed"
--R                                                  Type: Union("failed",...)
--E 9

--S 10 of 20
remove!("Char", ey)
--R
--R
--R   (10)  1986
--R                                                    Type: Union(Integer,...)
--E 10

--S 11 of 20
keys ey
--R
--R
--R   (11)  ["Fitch","Caviness"]
--R                                                         Type: List(String)
--E 11

--S 12 of 20
#ey
--R
--R
--R   (12)  2
--R                                                      Type: PositiveInteger
--E 12

--S 13 of 20
KE := Record(key: String, entry: Integer)
--R
--R
--R   (13)  Record(key: String,entry: Integer)
--R                                                              Type: Domain
--E 13

--S 14 of 20
```

```
reopen!(ey, "output")
--R
--R
--R   (14)  "editor.year"
--R                                                Type: KeyedAccessFile(Integer)
--E 14

--S 15 of 20
write!(ey, ["van Hulzen", 1983]$KE)
--R
--R
--R   (15)  [key= "van Hulzen",entry= 1983]
--R                                       Type: Record(key: String,entry: Integer)
--E 15

--S 16 of 20
write!(ey, ["Calmet", 1982]$KE)
--R
--R
--R   (16)  [key= "Calmet",entry= 1982]
--R                                       Type: Record(key: String,entry: Integer)
--E 16

--S 17 of 20
write!(ey, ["Wang", 1981]$KE)
--R
--R
--R   (17)  [key= "Wang",entry= 1981]
--R                                       Type: Record(key: String,entry: Integer)
--E 17

--S 18 of 20
close! ey
--R
--R
--R   (18)  "editor.year"
--R                                                Type: KeyedAccessFile(Integer)
--E 18

--S 19 of 20
keys ey
--R
--R
--R   (19)  ["Wang","Calmet","van Hulzen","Fitch","Caviness"]
--R                                                          Type: List(String)
--E 19

--S 20 of 20
members ey
--R
```

```
--R
--R   (20)  [1981,1982,1983,1984,1985]
--R                                                    Type: List(Integer)
--E 20

)system rm -r editor.year

)spool
)lisp (bye)
```

———-

— KeyedAccessFile.help —

```
====================================================================
KeyedAccessFile examples
====================================================================

The domain KeyedAccessFile(S) provides files which can be used
as associative tables.  Data values are stored in these files and can
be retrieved according to their keys.  The keys must be strings so
this type behaves very much like the StringTable(S) domain.  The
difference is that keyed access files reside in secondary storage
while string tables are kept in memory.

Before a keyed access file can be used, it must first be opened.
A new file can be created by opening it for output.

  ey: KeyedAccessFile(Integer) := open("editor.year", "output")

Just as for vectors, tables or lists, values are saved in a keyed
access file by setting elements.

  ey."Char":= 1986

  ey."Caviness" := 1985

  ey."Fitch"    := 1984

Values are retrieved using application, in any of its syntactic forms.

  ey."Char"

  ey("Char")

  ey "Char"

Attempting to retrieve a non-existent element in this way causes an
error.  If it is not known whether a key exists, you should use the
```

```
search operation.

  search("Char", ey)

  search("Smith", ey)

When an entry is no longer needed, it can be removed from the file.

  remove!("Char", ey)

The keys operation returns a list of all the keys for a given file.

  keys ey

The # operation gives the number of entries.

  #ey

The table view of keyed access files provides safe operations.  That
is, if the Axiom program is terminated between file operations, the
file is left in a consistent, current state.  This means, however,
that the operations are somewhat costly.  For example, after each
update the file is closed.

Here we add several more items to the file, then check its contents.

  KE := Record(key: String, entry: Integer)

  reopen!(ey, "output")

If many items are to be added to a file at the same time, then it is
more efficient to use the write operation.

  write!(ey, ["van Hulzen", 1983]$KE)

  write!(ey, ["Calmet", 1982]$KE)

  write!(ey, ["Wang", 1981]$KE)

  close! ey

The read operation is also available from the file view, but it
returns elements in a random order.  It is generally clearer and more
efficient to use the keys operation and to extract elements by key.

  keys ey


  members ey

  )system rm -r editor.year
```

```
See Also:
o )help Table
o )help StringTable
o )help File
o )help TextFile
o )help Library
o )show KeyedAccessFile
```

———-

12.2.1 KeyedAccessFile (KAFILE)



See

⇒ “File” (FILE) 7.2.1 on page 772
⇒ “TextFile” (TEXTFILE) 21.5.1 on page 2661
⇒ “BinaryFile” (BINFILE) 3.8.1 on page 279
⇒ “Library” (LIB) 13.2.1 on page 1396

Exports:

any?	any?	bag	close!	coerce
construct	convert	copy	count	count
dictionary	elt	empty	empty?	entries
entry?	eq?	eval	every?	every?
extract!	fill!	find	first	hash
index?	indices	insert!	inspect	iomode
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	name	open	pack!	parts
parts	qelt	qsetelt!	read!	reduce
remove	remove!	removeDuplicates	reopen!	sample
search	select	select!	setelt	size?
swap!	table	write!	#?	?~=?
?=?	?.?			

— domain KAFILE KeyedAccessFile —

```
)abbrev domain KAFILE KeyedAccessFile
++ Author: Stephen M. Watt
++ Date Created: 1985
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain allows a random access file to be viewed both as a table
++ and as a file object. The KeyedAccessFile format is a directory
++ containing a single file called ‘‘index.kaf’’. This file is a random
++ access file. The first thing in the file is an integer which is the
++ byte offset of an association list (the dictionary) at the end of
++ the file. The association list is of the form
++ ((key . byteoffset) (key . byteoffset)...)
++ where the byte offset is the number of bytes from the beginning of
++ the file. This offset contains an s-expression for the value of the key.

KeyedAccessFile(Entry): KAFcategory == KAFcapsule where
    Name  ==> FileName
    Key   ==> String
    Entry :   SetCategory

    KAFcategory ==
        Join(FileCategory(Name, Record(key: Key, entry: Entry)),
             TableAggregate(Key, Entry)) with
                 finiteAggregate
```

```
            pack_!: % -> %
                ++ pack!(f) reorganizes the file f on disk to recover
                ++ unused space.

KAFcapsule == add

    CLASS     ==> 131   -- an arbitrary no. greater than 127
    FileState ==> SExpression
    IOMode    ==> String


    Cons:= Record(car: SExpression, cdr: SExpression)
    Rep := Record(fileName:    Name,     _
                  fileState:   FileState,   _
                  fileIOmode:  IOMode)

    defstream(fn: Name, mode: IOMode): FileState ==
        kafstring:=concat(fn::String,"/index.kaf")::FileName
        mode = "input"  =>
          not readable? kafstring => error ["File is not readable", fn]
          RDEFINSTREAM(fn)$Lisp
        mode = "output" =>
          not writable? fn => error ["File is not writable", fn]
          RDEFOUTSTREAM(fn)$Lisp
        error ["IO mode must be input or output", mode]

    ---- From Set ----
    f1 = f2 ==
        f1.fileName = f2.fileName
    coerce(f: %): OutputForm ==
        f.fileName::OutputForm

    ---- From FileCategory ----
    open fname ==
        open(fname, "either")
    open(fname, mode) ==
        mode = "either" =>
            exists? fname =>
                open(fname, "input")
            writable? fname =>
                reopen_!(open(fname, "output"), "input")
            error "File does not exist and cannot be created"
        [fname, defstream(fname, mode), mode]
    reopen_!(f, mode) ==
        close_! f
        if mode ^= "closed" then
            f.fileState := defstream(f.fileName, mode)
            f.fileIOmode  := mode
        f
    close_! f  ==
```

```
        if f.fileIOmode ^= "closed" then
            RSHUT(f.fileState)$Lisp
            f.fileIOmode  := "closed"
        f
    read_! f ==
        f.fileIOmode ^= "input" => error ["File not in read state",f]
        ks: List Symbol := RKEYIDS(f.fileName)$Lisp
        null ks => error ["Attempt to read empty file", f]
        ix := random()$Integer rem #ks
        k: String := PNAME(ks.ix)$Lisp
        [k, SPADRREAD(k, f.fileState)$Lisp]
    write_!(f, pr) ==
        f.fileIOmode ^= "output" => error ["File not in write state",f]
        SPADRWRITE(pr.key, pr.entry, f.fileState)$Lisp
        pr
    name f ==
        f.fileName
    iomode f ==
        f.fileIOmode

    ---- From TableAggregate ----
    empty() ==
        fn := new("", "kaf", "sdata")$Name
        open fn
    keys f ==
        close_! f
        l: List SExpression := RKEYIDS(f.fileName)$Lisp
        [PNAME(n)$Lisp for n in l]
    # f ==
        # keys f
    elt(f,k) ==
        reopen_!(f, "input")
        SPADRREAD(k, f.fileState)$Lisp
    setelt(f,k,e) ==
        -- Leaves f in a safe, closed state.  For speed use "write".
        reopen_!(f, "output")
        UNWIND_-PROTECT(write_!(f, [k,e]), close_! f)$Lisp
        close_! f
        e
    search(k,f) ==
        not member?(k, keys f) => "failed"   -- can't trap RREAD error
        reopen_!(f, "input")
        (SPADRREAD(k, f.fileState)$Lisp)@Entry
    remove_!(k:String,f:%)  ==
        result := search(k,f)
        result case "failed" => result
        close_! f
        RDROPITEMS(NAMESTRING(f.fileName)$Lisp, LIST(k)$Lisp)$Lisp
        result
    pack_! f ==
```

```
close_! f
RPACKFILE(f.fileName)$Lisp
f
```

———-

— **KAFILE.dotabb** —

```
"KAFILE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=KAFILE"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"KAFILE" -> "TBAGG"
```

———-

Chapter 13

Chapter L

13.1 domain LAUPOL LaurentPolynomial

— LaurentPolynomial.input —

```
)set break resume
)sys rm -f LaurentPolynomial.output
)spool LaurentPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show LaurentPolynomial
--R
--R LaurentPolynomial(R: IntegralDomain,UP: UnivariatePolynomialCategory(R))  is a domain constructor
--R Abbreviation for LaurentPolynomial is LAUPOL
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LAUPOL
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : % -> % if UP has DIFRING          D : (%,(UP -> UP)) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        associates? : (%,%) -> Boolean
--R coefficient : (%,Integer) -> R        coerce : UP -> %
--R coerce : R -> %                       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R convert : % -> Fraction(UP)           degree : % -> Integer
```

```
--R hash : % -> SingleInteger             latex : % -> String
--R leadingCoefficient : % -> R           monomial : (R,Integer) -> %
--R monomial? : % -> Boolean              one? : % -> Boolean
--R order : % -> Integer                  recip : % -> Union(%,"failed")
--R reductum : % -> %                     retract : % -> UP
--R retract : % -> R                      sample : () -> %
--R trailingCoefficient : % -> R          unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if UP has DIFRING
--R D : (%,Symbol) -> % if UP has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if UP has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if UP has PDRING(SYMBOL)
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if UP has PDRING(SYMBOL)
--R D : (%,(UP -> UP),NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT))
--R differentiate : % -> % if UP has DIFRING
--R differentiate : (%,NonNegativeInteger) -> % if UP has DIFRING
--R differentiate : (%,Symbol) -> % if UP has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if UP has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if UP has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if UP has PDRING(SYMBOL)
--R differentiate : (%,(UP -> UP),NonNegativeInteger) -> %
--R differentiate : (%,(UP -> UP)) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R gcd : (%,%) -> % if R has FIELD
--R gcd : List(%) -> % if R has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R lcm : (%,%) -> % if R has FIELD
--R lcm : List(%) -> % if R has FIELD
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if R has FIELD
--R ?quo? : (%,%) -> % if R has FIELD
--R ?rem? : (%,%) -> % if R has FIELD
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(UP,"failed")
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
```

```
--R separate : Fraction(UP) -> Record(polyPart: %,fracPart: Fraction(UP)) if R has FIELD
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **LaurentPolynomial.help** —

```
=====================================================================
LaurentPolynomial examples
=====================================================================

See Also:
o )show LaurentPolynomial
```

———-

13.1.1 LaurentPolynomial (LAUPOL)



Exports:

0	1	associates?
characteristic	charthRoot	coefficient
coerce	convert	D
degree	differentiate	divide
euclideanSize	expressIdealMember	exquo
extendedEuclidean	gcd	gcdPolynomial
hash	latex	lcm
leadingCoefficient	monomial	monomial?
multiEuclidean	one?	order
principalIdeal	recip	reductum
retract	retractIfCan	sample
separate	sizeLess?	subtractIfCan
trailingCoefficient	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?=?	?^?
?~=?	?quo?	?rem?

— domain LAUPOL LaurentPolynomial —

```
)abbrev domain LAUPOL LaurentPolynomial
++ Author: Manuel Bronstein
++ Date Created: May 1988
++ Date Last Updated: 26 Apr 1990
++ Description:
++ Univariate polynomials with negative and positive exponents.

LaurentPolynomial(R, UP): Exports == Implementation where
  R : IntegralDomain
  UP: UnivariatePolynomialCategory R

  O   ==> OutputForm
  B   ==> Boolean
  N   ==> NonNegativeInteger
  Z   ==> Integer
  RF  ==> Fraction UP

  Exports ==> Join(DifferentialExtension UP, IntegralDomain,
          ConvertibleTo RF, FullyRetractableTo R, RetractableTo UP) with
    monomial?          : %  -> B
      ++ monomial?(x) is not documented
    degree             : %  -> Z
      ++ degree(x) is not documented
    order              : %  -> Z
      ++ order(x) is not documented
    reductum           : %  -> %
      ++ reductum(x) is not documented
```

```
    leadingCoefficient : %  -> R
      ++ leadingCoefficient is not documented
    trailingCoefficient: %  -> R
      ++ trailingCoefficient is not documented
    coefficient        : (%, Z) -> R
      ++ coefficient(x,n) is not documented
    monomial           : (R, Z) -> %
      ++ monomial(x,n) is not documented
    if R has CharacteristicZero then CharacteristicZero
    if R has CharacteristicNonZero then CharacteristicNonZero
    if R has Field then
      EuclideanDomain
      separate: RF -> Record(polyPart:%, fracPart:RF)
        ++ separate(x) is not documented

  Implementation ==> add
    Rep := Record(polypart: UP, order0: Z)

    poly   : %  -> UP
    check0 : (Z, UP) -> %
    mkgpol : (Z, UP) -> %
    gpol   : (UP, Z) -> %
    toutput: (R, Z, O) -> O
    monTerm: (R, Z, O) -> O

    0                == [0, 0]
    1                == [1, 0]
    p = q            == p.order0 = q.order0 and p.polypart = q.polypart
    poly p           == p.polypart
    order p          == p.order0
    gpol(p, n)       == [p, n]
    monomial(r, n)   == check0(n, r::UP)
    coerce(p:UP):%   == mkgpol(0, p)
    reductum p       == check0(order p, reductum poly p)
    n:Z * p:%        == check0(order p, n * poly p)
    characteristic() == characteristic()$R
    coerce(n:Z):%    == n::R::%
    degree p         == degree(poly p)::Z + order p
    monomial? p      == monomial? poly p
    coerce(r:R):%    == gpol(r::UP, 0)
    convert(p:%):RF  == poly(p) * (monomial(1, 1)$UP)::RF ** order p
    p:% * q:%        == check0(order p + order q, poly p * poly q)
    - p              == gpol(- poly p, order p)
    check0(n, p)     == (zero? p => 0; gpol(p, n))
    trailingCoefficient p   == coefficient(poly p, 0)
    leadingCoefficient p    == leadingCoefficient poly p

    coerce(p:%):O ==
      zero? p => 0::Z::O
      l := nil()$List(O)
```

```
      v := monomial(1, 1)$UP :: O
      while p ^= 0 repeat
        l := concat(l, toutput(leadingCoefficient p, degree p, v))
        p := reductum p
      reduce("+", l)

    coefficient(p, n) ==
      (m := n - order p) < 0 => 0
      coefficient(poly p, m::N)

    differentiate(p:%, derivation:UP -> UP) ==
      t := monomial(1, 1)$UP
      mkgpol(order(p) - 1,
              derivation(poly p) * t + order(p) * poly(p) * derivation t)

    monTerm(r, n, v) ==
      zero? n => r::O
--      one? n => v
      (n = 1) => v
      v ** (n::O)

    toutput(r, n, v) ==
      mon := monTerm(r, n, v)
--      zero? n or one? r => mon
      zero? n or (r = 1) => mon
      r = -1 => - mon
      r::O * mon

    recip p ==
      (q := recip poly p) case "failed" => "failed"
      gpol(q::UP, - order p)

    p + q ==
      zero? q => p
      zero? p => q
      (d := order p - order q) > 0 =>
                    gpol(poly(p) * monomial(1, d::N) + poly q, order q)
      d < 0 => gpol(poly(p) + poly(q) * monomial(1, (-d)::N), order p)
      mkgpol(order p, poly(p) + poly q)

    mkgpol(n, p) ==
      zero? p => 0
      d := order(p, monomial(1, 1)$UP)
      gpol((p exquo monomial(1, d))::UP, n + d::Z)

    p exquo q ==
      (r := poly(p) exquo poly q) case "failed" => "failed"
      check0(order p - order q, r::UP)

    retractIfCan(p:%):Union(UP, "failed") ==
```

```
      order(p) < 0 => error "Not retractable"
      poly(p) * monomial(1, order(p)::N)$UP

    retractIfCan(p:%):Union(R, "failed") ==
      order(p) ^= 0 => "failed"
      retractIfCan poly p

    if R has Field then
      gcd(p, q) == gcd(poly p, poly q)::%

      separate f ==
        n  := order(q := denom f, monomial(1, 1))
        q  := (q exquo (tn := monomial(1, n)$UP))::UP
        bc := extendedEuclidean(tn,q,numer f)::Record(coef1:UP,coef2:UP)
        qr := divide(bc.coef1, q)
        [mkgpol(-n, bc.coef2 + tn * qr.quotient), qr.remainder / q]

-- returns (z, r) s.t. p = q z + r,
-- and degree(r) < degree(q), order(r) >= min(order(p), order(q))
      divide(p, q) ==
        c  := min(order p, order q)
        qr := divide(poly(p) * monomial(1, (order p - c)::N)$UP, poly q)
        [mkgpol(c - order q, qr.quotient), mkgpol(c, qr.remainder)]

      euclideanSize p == degree poly p

      extendedEuclidean(a, b, c) ==
        (bc := extendedEuclidean(poly a, poly b, poly c)) case "failed"
          => "failed"
        [mkgpol(order c - order a, bc.coef1),
                                    mkgpol(order c - order b, bc.coef2)]
```

———-

— LAUPOL.dotabb —

```
"LAUPOL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LAUPOL"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"LAUPOL" -> "PFECAT"
```

———-

13.2 domain LIB Library

— Library.input —

```
)set break resume
)sys rm -f Library.output
)spool Library.output
)set message test on
)set message auto off
)clear all

--S 1 of 7
stuff := library "Neat.stuff"
--R
--R
--R   (1)  "Neat.stuff"
--R                                                        Type: Library
--E 1

--S 2 of 7
stuff.int := 32**2
--R
--R
--R   (2)  1024
--R                                                  Type: PositiveInteger
--E 2

--S 3 of 7
stuff."poly" := x**2 + 1
--R
--R
--R         2
--R   (3)  x  + 1
--R                                               Type: Polynomial(Integer)
--E 3

--S 4 of 7
stuff.str := "Hello"
--R
--R
--R   (4)  "Hello"
--R                                                        Type: String
--E 4

--S 5 of 7
keys stuff
--R
--R
--R   (5)  ["str","poly","int"]
--R                                                   Type: List(String)
--E 5

--S 6 of 7
stuff.poly
```

```
--R
--R
--R         2
--R   (6)  x  + 1
--R                                                    Type: Polynomial(Integer)
--E 6

--S 7 of 7
stuff("poly")
--R
--R
--R         2
--R   (7)  x  + 1
--R                                                    Type: Polynomial(Integer)
--E 7

)system rm -rf Neat.stuff
)spool
)lisp (bye)
```

———-

— Library.help —

```
=====================================================================
Library examples
=====================================================================

The Library domain provides a simple way to store Axiom values
in a file.  This domain is similar to KeyedAccessFile but fewer
declarations are needed and items of different types can be saved
together in the same file.

To create a library, you supply a file name.

  stuff := library "Neat.stuff"

Now values can be saved by key in the file.  The keys should be
mnemonic, just as the field names are for records.  They can be given
either as strings or symbols.

  stuff.int := 32**2

  stuff."poly" := x**2 + 1

  stuff.str := "Hello"

You obtain the set of available keys using the keys operation.
```

```
  keys stuff

You extract values by giving the desired key in this way.

  stuff.poly


  stuff("poly")

When the file is no longer needed, you should remove it from the
file system.

  )system rm -rf Neat.stuff

See Also:
o )help File
o )help TextFile
o )help KeyedAccessFile
o )show Library
```

13.2.1 Library (LIB)



See

⇒ “File” (FILE) 7.2.1 on page 772
⇒ “TextFile” (TEXTFILE) 21.5.1 on page 2661
⇒ “BinaryFile” (BINFILE) 3.8.1 on page 279
⇒ “KeyedAccessFile” (KAFILE) 12.2.1 on page 1381

Exports:

any?	any?	bag	close!	coerce
copy	construct	convert	count	dictionary
elt	empty	empty?	entries	entry?
eq?	eval	every?	every?	extract!
fill!	find	first	hash	index?
indices	insert!	inspect	key?	keys
latex	less?	library	map	map!
maxIndex	member?	members	minIndex	more?
pack!	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
select	select!	setelt	size?	swap!
table	#?	?=?	?~=?	?.?

— domain LIB Library —

```
)abbrev domain LIB Library
++ Author: Stephen M. Watt
++ Date Created: 1985
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains: KeyedAccessFile
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This domain provides a simple way to save values in files.

Library(): TableAggregate(String, Any) with
         library:  FileName -> %
             ++ library(ln) creates a new library file.
         pack_!: % -> %
             ++ pack!(f) reorganizes the file f on disk to recover
             ++ unused space.

         elt : (%, Symbol) -> Any
             ++ elt(lib,k) or lib.k  extracts the value corresponding to
             ++ the key \spad{k} from the library \spad{lib}.

         setelt : (%, Symbol, Any) -> Any
             ++ \spad{lib.k := v} saves the value \spad{v} in the library
             ++ \spad{lib}.  It can later be extracted using the key \spad{k}.

         close_!: % -> %
          ++ close!(f) returns the library f closed to input and output.

    == KeyedAccessFile(Any) add
```

```
        Rep := KeyedAccessFile(Any)
        library f == open f
        elt(f:%,v:Symbol) == elt(f, string v)
        setelt(f:%, v:Symbol, val:Any) == setelt(f, string v, val)
```

———-

— **LIB.dotabb** —

```
"LIB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LIB"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"LIB" -> "ALIST"
```

———-

13.3 domain LEXP LieExponentials

— **LieExponentials.input** —

```
)set break resume
)sys rm -f LieExponentials.output
)spool LieExponentials.output
)set message test on
)set message auto off
)clear all
--S 1 of 13
a: Symbol := 'a
--R
--R
--R   (1)  a
--R                                                    Type: Symbol
--E 1

--S 2 of 13
b: Symbol := 'b
--R
--R
--R   (2)  b
--R                                                    Type: Symbol
--E 2

--S 3 of 13
coef := Fraction(Integer)
--R
```

```
--R
--R   (3)  Fraction(Integer)
--R                                                                Type: Domain
--E 3

--S 4 of 13
group := LieExponentials(Symbol, coef, 3)
--R
--R
--R   (4)  LieExponentials(Symbol,Fraction(Integer),3)
--R                                                                Type: Domain
--E 4

--S 5 of 13
lpoly := LiePolynomial(Symbol, coef)
--R
--R
--R   (5)  LiePolynomial(Symbol,Fraction(Integer))
--R                                                                Type: Domain
--E 5

--S 6 of 13
poly := XPBWPolynomial(Symbol, coef)
--R
--R
--R   (6)  XPBWPolynomial(Symbol,Fraction(Integer))
--R                                                                Type: Domain
--E 6

--S 7 of 13
ea := exp(a::lpoly)$group
--R
--R
--R         [a]
--R   (7)  e
--R                            Type: LieExponentials(Symbol,Fraction(Integer),3)
--E 7

--S 8 of 13
eb := exp(b::lpoly)$group
--R
--R
--R         [b]
--R   (8)  e
--R                            Type: LieExponentials(Symbol,Fraction(Integer),3)
--E 8

--S 9 of 13
g: group := ea*eb
--R
```

```
--R
--R             1     2        1   2
--R             - [a b ]       - [a b]
--R          [b] 2        [a b] 2       [a]
--R   (9)  e   e        e     e       e
--R                            Type: LieExponentials(Symbol,Fraction(Integer),3)
--E 9

--S 10 of 13
g :: poly
--R
--R
--R   (10)
--R                     1                              1          1
--R     1 + [a] + [b] + - [a][a] + [a b] + [b][a] + - [b][b] + - [a][a][a]
--R                     2                              2          6
--R   +
--R     1   2                1     2    1                          1
--R     - [a b] + [a b][a] + - [a b ] + - [b][a][a] + [b][a b] + - [b][b][a]
--R     2                    2          2                          2
--R   +
--R     1
--R     - [b][b][b]
--R     6
--R                               Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 10

--S 11 of 13
log(g)$group
--R
--R
--R                     1          1   2      1     2
--R   (11)  [a] + [b] + - [a b] + -- [a b] + -- [a b ]
--R                     2         12         12
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 11

--S 12 of 13
g1: group := inv(g)
--R
--R
--R          - [b] - [a]
--R   (12)  e     e
--R                               Type: LieExponentials(Symbol,Fraction(Integer),3)
--E 12

--S 13 of 13
g*g1
--R
--R
```

```
--R   (13)  1
--R                              Type: LieExponentials(Symbol,Fraction(Integer),3)
--E 13
)spool
)lisp (bye)
```

———-

— LieExponentials.help —

```
=====================================================================
LieExponentials examples
=====================================================================

  a: Symbol := 'a
    a
                          Type: Symbol

  b: Symbol := 'b
    b
                          Type: Symbol

=====================================================================
Declarations of domains
=====================================================================

  coef := Fraction(Integer)
    Fraction Integer
                          Type: Domain

  group := LieExponentials(Symbol, coef, 3)
    LieExponentials(Symbol,Fraction Integer,3)
                          Type: Domain

  lpoly := LiePolynomial(Symbol, coef)
    LiePolynomial(Symbol,Fraction Integer)
                          Type: Domain

  poly := XPBWPolynomial(Symbol, coef)
    XPBWPolynomial(Symbol,Fraction Integer)
                          Type: Domain

=====================================================================
Calculations
=====================================================================

  ea := exp(a::lpoly)$group
     [a]
    e
```

```
                        Type: LieExponentials(Symbol,Fraction Integer,3)

  eb := exp(b::lpoly)$group
     [b]
    e
                        Type: LieExponentials(Symbol,Fraction Integer,3)

  g: group := ea*eb
         1     2        1   2
         - [a b ]       - [a b]
     [b] 2        [a b] 2       [a]
    e   e        e     e       e
                        Type: LieExponentials(Symbol,Fraction Integer,3)

  g :: poly
                    1                              1          1
     1 + [a] + [b] + - [a][a] + [a b] + [b][a] + - [b][b] + - [a][a][a]
                    2                              2          6
   +
     1   2                1     2    1                          1
     - [a b] + [a b][a] + - [a b ] + - [b][a][a] + [b][a b] + - [b][b][a]
     2                    2          2                          2
   +
     1
     - [b][b][b]
     6
                        Type: XPBWPolynomial(Symbol,Fraction Integer)

  log(g)$group
                1          1   2      1     2
    [a] + [b] + - [a b] + -- [a b] + -- [a b ]
                2          12         12
                        Type: LiePolynomial(Symbol,Fraction Integer)


  g1: group := inv(g)
     - [b] - [a]
    e     e
                        Type: LieExponentials(Symbol,Fraction Integer,3)

  g*g1
    1
                        Type: LieExponentials(Symbol,Fraction Integer,3)
```

See Also:
o)show LieExponentials

———-

13.3.1 LieExponentials (LEXP)



Exports:

1	coerce	commutator	conjugate
exp	hash	identification	inv
latex	log	listOfTerms	LyndonBasis
LyndonCoordinates	mirror	one?	recip
sample	varList	?~=?	?^?
?*?	?**?	?/?	?=?

— domain LEXP LieExponentials —

```
)abbrev domain LEXP LieExponentials
++ Author: Michel Petitot (petitot@lifl.fr).
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ Management of the Lie Group associated with a
++ free nilpotent Lie algebra. Every Lie bracket with
++ length greater than \axiom{Order} are assumed to be null.
++ The implementation inherits from the \spadtype{XPBWPolynomial}
++ domain constructor: Lyndon coordinates are exponential coordinates
++ of the second kind.

LieExponentials(VarSet, R, Order): XDPcat == XDPdef where

  EX     ==> OutputForm
  PI     ==> PositiveInteger
  NNI    ==> NonNegativeInteger
  I      ==> Integer
```

```
RN     ==> Fraction(I)
R      : Join(CommutativeRing, Module RN)
Order  : PI
VarSet : OrderedSet
LWORD  ==> LyndonWord(VarSet)
LWORDS ==> List LWORD
BASIS  ==> PoincareBirkhoffWittLyndonBasis(VarSet)
TERM   ==> Record(k:BASIS, c:R)
LTERMS ==> List(TERM)
LPOLY  ==> LiePolynomial(VarSet,R)
XDPOLY ==> XDistributedPolynomial(VarSet,R)
PBWPOLY==> XPBWPolynomial(VarSet, R)
TERM1  ==> Record(k:LWORD, c:R)
EQ     ==> Equation(R)

XDPcat == Group with
  exp         : LPOLY -> $
    ++ \axiom{exp(p)} returns the exponential of \axiom{p}.
  log         : $ -> LPOLY
    ++ \axiom{log(p)} returns the logarithm of \axiom{p}.
  listOfTerms : $ -> LTERMS
    ++ \axiom{listOfTerms(p)} returns the internal representation of \axiom{p}.
  coerce      : $ -> XDPOLY
    ++ \axiom{coerce(g)} returns the internal representation of \axiom{g}.
  coerce      : $ -> PBWPOLY
    ++ \axiom{coerce(g)} returns the internal representation of \axiom{g}.
  mirror      : $ -> $
    ++ \axiom{mirror(g)} is the mirror of the internal representation of \axiom{g}.
  varList     : $ -> List VarSet
    ++ \axiom{varList(g)} returns the list of variables of \axiom{g}.
  LyndonBasis : List VarSet -> List LPOLY
    ++ \axiom{LyndonBasis(lv)} returns the Lyndon basis of the nilpotent free
    ++ Lie algebra.
  LyndonCoordinates: $ -> List TERM1
    ++ \axiom{LyndonCoordinates(g)} returns the exponential coordinates of \axiom{g}.
  identification: ($,$) -> List EQ
    ++ \axiom{identification(g,h)} returns the list of equations \axiom{g_i = h_i},
    ++ where \axiom{g_i} (resp. \axiom{h_i}) are exponential coordinates
    ++ of \axiom{g} (resp. \axiom{h}).

XDPdef == PBWPOLY add

  -- Representation
     Rep := PBWPOLY

  -- local functions
     compareTerm1s: (TERM1, TERM1) -> Boolean
     out: TERM1 -> EX
     ident: (List TERM1, List TERM1) -> List EQ
```

```
-- functions locales
   ident(l1, l2) ==
     import(TERM1)
     null l1 => [equation(0$R,t.c)$EQ for t in l2]
     null l2 => [equation(t.c, 0$R)$EQ for t in l1]
     u1 : LWORD := l1.first.k; c1 :R := l1.first.c
     u2 : LWORD := l2.first.k; c2 :R := l2.first.c
     u1 = u2 =>
        r: R := c1 - c2
        r = 0 => ident(rest l1, rest l2)
        cons(equation(c1,c2)$EQ , ident(rest l1, rest l2))
     lexico(u1, u2)$LWORD =>
        cons(equation(0$R,c2)$EQ , ident(l1, rest l2))
     cons(equation(c1,0$R)$EQ , ident(rest l1, l2))

   -- ordre lexico decroissant
   compareTerm1s(u:TERM1, v:TERM1):Boolean == lexico(v.k, u.k)$LWORD

   out(t:TERM1):EX ==
     t.c =$R 1 => char("e")$Character :: EX ** t.k ::EX
     char("e")$Character :: EX ** (t.c::EX * t.k::EX)

-- definitions
   identification(x,y) ==
      l1: List TERM1 := LyndonCoordinates x
      l2: List TERM1 := LyndonCoordinates y
      ident(l1, l2)

   LyndonCoordinates x ==
     lt: List TERM1 := [[l::LWORD, t.c]$TERM1 for t in listOfTerms x | _
                         (l := retractIfCan(t.k)$BASIS) case LWORD ]
     lt := sort(compareTerm1s,lt)

   x:$ * y:$ == product(x::Rep, y::Rep, Order::I::NNI)$Rep

   exp p == exp(p::Rep , Order::I::NNI)$Rep

   log p == LiePolyIfCan(log(p,Order::I::NNI))$Rep :: LPOLY

   coerce(p:$):EX ==
      p = 1$$ => 1$R :: EX
      lt : List TERM1 := LyndonCoordinates p
      reduce(_*, [out t for t in lt])$List(EX)


   LyndonBasis(lv) ==
     [LiePoly(l)$LPOLY for l in LyndonWordsList(lv,Order)$LWORD]

   coerce(p:$):PBWPOLY == p::Rep
```

```
       inv x ==
         x = 1 => 1
         lt:LTERMS := listOfTerms mirror x
         lt:= [[t.k, (odd? length(t.k)$BASIS => - t.c; t.c)]$TERM for t in lt ]
         lt pretend $
```

———-

— LEXP.dotabb —

```
"LEXP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LEXP"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"LEXP" -> "FLAGG-"
"LEXP" -> "FLAGG"
```

———-

13.4 domain LPOLY LiePolynomial

— LiePolynomial.input —

```
)set break resume
)sys rm -f LiePolynomial.output
)spool LiePolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 28
RN := Fraction Integer
--R
--R
--R   (1)  Fraction(Integer)
--R                                                          Type: Domain
--E 1

--S 2 of 28
Lpoly := LiePolynomial(Symbol,RN)
--R
--R
--R   (2)  LiePolynomial(Symbol,Fraction(Integer))
--R                                                          Type: Domain
--E 2
```

```
--S 3 of 28
Dpoly := XDPOLY(Symbol,RN)
--R
--R
--R   (3)  XDistributedPolynomial(Symbol,Fraction(Integer))
--R                                                              Type: Domain
--E 3

--S 4 of 28
Lword := LyndonWord Symbol
--R
--R
--R   (4)  LyndonWord(Symbol)
--R                                                              Type: Domain
--E 4

--S 5 of 28
a:Symbol := 'a
--R
--R
--R   (5)  a
--R                                                              Type: Symbol
--E 5

--S 6 of 28
b:Symbol := 'b
--R
--R
--R   (6)  b
--R                                                              Type: Symbol
--E 6

--S 7 of 28
c:Symbol := 'c
--R
--R
--R   (7)  c
--R                                                              Type: Symbol
--E 7

--S 8 of 28
aa: Lpoly := a
--R
--R
--R   (8)  [a]
--R                                 Type: LiePolynomial(Symbol,Fraction(Integer))
--E 8

--S 9 of 28
bb: Lpoly := b
```

```
--R
--R
--R   (9)  [b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 9

--S 10 of 28
cc: Lpoly := c
--R
--R
--R   (10)  [c]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 10

--S 11 of 28
p : Lpoly := [aa,bb]
--R
--R
--R   (11)  [a b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 11

--S 12 of 28
q : Lpoly := [p,bb]
--R
--R
--R            2
--R   (12)  [a b ]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 12

--S 13 of 28
liste : List Lword := LyndonWordsList([a,b], 4)
--R
--R
--R                          2       2    3     2 2      3
--R   (13)  [[a],[b],[a b],[a b],[a b ],[a b],[a b ],[a b ]]
--R                                                Type: List(LyndonWord(Symbol))
--E 13

--S 14 of 28
r: Lpoly := p + q + 3*LiePoly(liste.4)$Lpoly
--R
--R
--R                    2         2
--R   (14)  [a b] + 3[a b] + [a b ]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 14

--S 15 of 28
```

```
s:Lpoly := [p,r]
--R
--R
--R             2                2
--R   (15)  - 3[a b a b] + [a b a b ]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 15

--S 16 of 28
t:Lpoly  := s  + 2*LiePoly(liste.3) - 5*LiePoly(liste.5)
--R
--R
--R                       2       2                 2
--R   (16)  2[a b] - 5[a b ] - 3[a b a b] + [a b a b ]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 16

--S 17 of 28
degree t
--R
--R
--R   (17)  5
--R                                                    Type: PositiveInteger
--E 17

--S 18 of 28
mirror t
--R
--R
--R                         2       2                 2
--R   (18)  - 2[a b] - 5[a b ] - 3[a b a b] + [a b a b ]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 18

--S 19 of 28
Jacobi(p: Lpoly, q: Lpoly, r: Lpoly): Lpoly == _
   [ [p,q]$Lpoly, r] + [ [q,r]$Lpoly, p] + [ [r,p]$Lpoly, q]
--R
--R   Function declaration Jacobi : (LiePolynomial(Symbol,Fraction(Integer
--R      )),LiePolynomial(Symbol,Fraction(Integer)),LiePolynomial(Symbol,
--R      Fraction(Integer))) -> LiePolynomial(Symbol,Fraction(Integer))
--R      has been added to workspace.
--R                                                                 Type: Void
--E 19

--S 20 of 28
test: Lpoly := Jacobi(a,b,b)
--R
--R   Compiling function Jacobi with type (LiePolynomial(Symbol,Fraction(
--R      Integer)),LiePolynomial(Symbol,Fraction(Integer)),LiePolynomial(
```

```
--R      Symbol,Fraction(Integer))) -> LiePolynomial(Symbol,Fraction(
--R      Integer))
--R
--R   (20)  0
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 20

--S 21 of 28
test: Lpoly := Jacobi(p,q,r)
--R
--R
--R   (21)  0
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 21

--S 22 of 28
test: Lpoly := Jacobi(r,s,t)
--R
--R
--R   (22)  0
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 22

--S 23 of 28
eval(p, a, p)$Lpoly
--R
--R
--R             2
--R   (23)  [a b ]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 23

--S 24 of 28
eval(p, [a,b], [2*bb, 3*aa])$Lpoly
--R
--R
--R   (24)  - 6[a b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 24

--S 25 of 28
r: Lpoly := [p,c]
--R
--R
--R   (25)  [a b c] + [a c b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 25

--S 26 of 28
r1: Lpoly := eval(r, [a,b,c], [bb, cc, aa])$Lpoly
```

```
--R
--R
--R   (26)  - [a b c]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 26

--S 27 of 28
r2: Lpoly := eval(r, [a,b,c], [cc, aa, bb])$Lpoly
--R
--R
--R   (27)  - [a c b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 27

--S 28 of 28
r + r1 + r2
--R
--R
--R   (28)  0
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 28
)spool

)lisp (bye)
```

———-

— LiePolynomial.help —

```
========================================================================
LiePolynomial examples
========================================================================

========================================================================
Declaration of domains
========================================================================

  RN := Fraction Integer
    Fraction Integer
                    Type: Domain

  Lpoly := LiePolynomial(Symbol,RN)
    LiePolynomial(Symbol,Fraction Integer)
                    Type: Domain

  Dpoly := XDPOLY(Symbol,RN)
    XDistributedPolynomial(Symbol,Fraction Integer)
                    Type: Domain
```

```
  Lword := LyndonWord Symbol
    LyndonWord Symbol
                    Type: Domain

========================================================================
Initialisation
========================================================================

  a:Symbol := 'a
    a
                    Type: Symbol

  b:Symbol := 'b
    b
                    Type: Symbol

  c:Symbol := 'c
    c
                    Type: Symbol

  aa: Lpoly := a
    [a]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  bb: Lpoly := b
    [b]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  cc: Lpoly := c
    [c]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  p : Lpoly := [aa,bb]
    [a b]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  q : Lpoly := [p,bb]
        2
    [a b ]
                    Type: LiePolynomial(Symbol,Fraction Integer)

All the Lyndon words of order 4

  liste : List Lword := LyndonWordsList([a,b], 4)
                    2       2    3     2 2      3
    [[a],[b],[a b],[a b],[a b ],[a b],[a b ],[a b ]]
                    Type: List LyndonWord Symbol

  r: Lpoly := p + q + 3*LiePoly(liste.4)$Lpoly
               2         2
```

```
    [a b] + 3[a b] + [a b ]
                     Type: LiePolynomial(Symbol,Fraction Integer)

  s:Lpoly := [p,r]
         2                 2
    - 3[a b a b] + [a b a b ]
                     Type: LiePolynomial(Symbol,Fraction Integer)

  t:Lpoly  := s  + 2*LiePoly(liste.3) - 5*LiePoly(liste.5)
                  2       2                 2
    2[a b] - 5[a b ] - 3[a b a b] + [a b a b ]
                     Type: LiePolynomial(Symbol,Fraction Integer)

  degree t
    5
                     Type: PositiveInteger

  mirror t
                    2       2                 2
    - 2[a b] - 5[a b ] - 3[a b a b] + [a b a b ]
                     Type: LiePolynomial(Symbol,Fraction Integer)

========================================================================
Jacobi Relation
========================================================================

 Jacobi(p: Lpoly, q: Lpoly, r: Lpoly): Lpoly == _
   [ [p,q]\$Lpoly, r] + [ [q,r]\$Lpoly, p] + [ [r,p]\$Lpoly, q]
                     Type: Void

========================================================================
Tests
========================================================================

  test: Lpoly := Jacobi(a,b,b)
    0
                     Type: LiePolynomial(Symbol,Fraction Integer)

  test: Lpoly := Jacobi(p,q,r)
    0
                     Type: LiePolynomial(Symbol,Fraction Integer)

  test: Lpoly := Jacobi(r,s,t)
    0
                     Type: LiePolynomial(Symbol,Fraction Integer)

========================================================================
Evaluation
========================================================================
```

```
  eval(p, a, p)$Lpoly
        2
    [a b ]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  eval(p, [a,b], [2*bb, 3*aa])$Lpoly
    - 6[a b]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  r: Lpoly := [p,c]
    [a b c] + [a c b]
                    Type: LiePolynomial(Symbol,Fraction Integer)


  r1: Lpoly := eval(r, [a,b,c], [bb, cc, aa])$Lpoly
    - [a b c]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  r2: Lpoly := eval(r, [a,b,c], [cc, aa, bb])$Lpoly
    - [a c b]
                    Type: LiePolynomial(Symbol,Fraction Integer)

  r + r1 + r2
    0
                    Type: LiePolynomial(Symbol,Fraction Integer)

See Also:
o )help LyndonWord
o )help XDistributedPolynomial
o )show LiePolynomial
```

13.4.1 LiePolynomial (LPOLY)



Exports:

0	coef	coefficient	coefficients
coerce	construct	degree	eval
hash	latex	leadingCoefficient	leadingMonomial
leadingTerm	LiePoly	LiePolyIfCan	listOfTerms
lquo	map	mirror	monom
monomial?	monomials	numberOfMonomials	reductum
retract	retractIfCan	rquo	sample
subtractIfCan	trunc	varList	zero?
?~=?	?*?	?/?	?+?
?-?	-?	?=?	

— domain LPOLY LiePolynomial —

```
)abbrev domain LPOLY LiePolynomial
++ Author: Michel Petitot (petitot@lifl.fr).
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Free Lie Algebras by C. Reutenauer (Oxford science publications).
++ Description:
++ This type supports Lie polynomials in Lyndon basis
++ see Free Lie Algebras by C. Reutenauer
++ (Oxford science publications).

LiePolynomial(VarSet:OrderedSet, R:CommutativeRing) : Public == Private where
   MAGMA   ==> Magma(VarSet)
   LWORD   ==> LyndonWord(VarSet)
   WORD    ==> OrderedFreeMonoid(VarSet)
   XDPOLY  ==> XDistributedPolynomial(VarSet,R)
   XRPOLY  ==> XRecursivePolynomial(VarSet,R)
   NNI     ==> NonNegativeInteger
   RN      ==> Fraction Integer
   EX      ==> OutputForm
   TERM    ==> Record(k: LWORD, c: R)

   Public == Join(FreeLieAlgebra(VarSet,R), FreeModuleCat(R,LWORD)) with
      LiePolyIfCan: XDPOLY -> Union($, "failed")
        ++ \axiom{LiePolyIfCan(p)} returns \axiom{p} in Lyndon basis
        ++ if \axiom{p} is a Lie polynomial, otherwise \axiom{"failed"}
        ++ is returned.
      construct: (LWORD, LWORD) -> $
        ++ \axiom{construct(x,y)} returns the Lie bracket \axiom{[x,y]}.
```

```
    construct: (LWORD, $) -> $
      ++ \axiom{construct(x,y)} returns the Lie bracket \axiom{[x,y]}.
    construct: ($, LWORD) -> $
      ++ \axiom{construct(x,y)} returns the Lie bracket \axiom{[x,y]}.

  Private ==  FreeModule1(R, LWORD) add
      import(TERM)

    --representation
      Rep :=  List TERM

    -- fonctions locales
      cr1 : (LWORD, $    ) -> $
      cr2 : ($, LWORD    ) -> $
      crw : (LWORD, LWORD) -> $     -- crochet de 2 mots de Lyndon
      DPoly: LWORD -> XDPOLY
      lquo1: (XRPOLY , LWORD) -> XRPOLY
      lyndon: (LWORD, LWORD) -> $
      makeLyndon: (LWORD, LWORD) -> LWORD
      rquo1: (XRPOLY , LWORD) -> XRPOLY
      RPoly: LWORD -> XRPOLY
      eval1: (LWORD, VarSet, $) -> $                      -- 08/03/98
      eval2: (LWORD, List VarSet, List $) -> $            -- 08/03/98


    -- Evaluation
      eval1(lw,v,nv) ==                                   -- 08/03/98
        not member?(v, varList(lw)$LWORD) => LiePoly lw
        (s := retractIfCan(lw)$LWORD) case VarSet =>
           if (s::VarSet) = v then nv else LiePoly lw
        l: LWORD := left lw
        r: LWORD := right lw
        construct(eval1(l,v,nv), eval1(r,v,nv))

      eval2(lw,lv,lnv) ==                                 -- 08/03/98
        p: Integer
        (s := retractIfCan(lw)$LWORD) case VarSet =>
           p := position(s::VarSet, lv)$List(VarSet)
           if p=0 then lw::$ else elt(lnv,p)$List($)
        l: LWORD := left lw
        r: LWORD := right lw
        construct(eval2(l,lv,lnv), eval2(r,lv,lnv))

      eval(p:$, v: VarSet, nv: $): $ ==                   -- 08/03/98
        +/ [t.c * eval1(t.k, v, nv) for t in p]

      eval(p:$, lv: List(VarSet), lnv: List($)): $ ==     -- 08/03/98
        +/ [t.c * eval2(t.k, lv, lnv) for t in p]

      lquo1(p,lw) ==
```

```
    constant? p => 0$XRPOLY
    retractable? lw => lquo(p, retract lw)$XRPOLY
    lquo1(lquo1(p, left lw),right lw) - lquo1(lquo1(p, right lw),left lw)
  rquo1(p,lw) ==
    constant? p => 0$XRPOLY
    retractable? lw => rquo(p, retract lw)$XRPOLY
    rquo1(rquo1(p, left lw),right lw) - rquo1(rquo1(p, right lw),left lw)

  coef(p, lp) == coef(p, lp::XRPOLY)$XRPOLY

  lquo(p, lp) ==
    lp = 0 => 0$XRPOLY
    +/ [t.c * lquo1(p,t.k) for t in lp]

  rquo(p, lp) ==
    lp = 0 => 0$XRPOLY
    +/ [t.c * rquo1(p,t.k) for t in lp]

  LiePolyIfCan p ==         -- inefficace a cause de la rep. de XDPOLY
     not quasiRegular? p => "failed"
     p1: XDPOLY := p ; r:$ := 0
     while p1 ^= 0 repeat
       t: Record(k:WORD, c:R) := mindegTerm p1
       w: WORD := t.k; coef:R := t.c
       (l := lyndonIfCan(w)$LWORD) case "failed" => return "failed"
       lp:$ := coef * LiePoly(l::LWORD)
       r := r + lp
       p1 := p1 - lp::XDPOLY
     r

--definitions locales
  makeLyndon(u,v) == (u::MAGMA * v::MAGMA) pretend LWORD

  crw(u,v) ==               -- u et v sont des mots de Lyndon
    u = v => 0
    lexico(u,v) => lyndon(u,v)
    - lyndon (v,u)

  lyndon(u,v) ==            -- u et v sont des mots de Lyndon tq u < v
    retractable? u => monom(makeLyndon(u,v),1)
    u1: LWORD := left u
    u2: LWORD := right u
    lexico(u2,v) => cr1(u1, lyndon(u2,v)) + cr2(lyndon(u1,v), u2)
    monom(makeLyndon(u,v),1)

  cr1 (l, p) ==
      +/[t.c * crw(l, t.k) for t in p]

  cr2 (p, l) ==
      +/[t.c * crw(t.k, l) for t in p]
```

```
        DPoly w ==
           retractable? w => retract(w) :: XDPOLY
           l:XDPOLY := DPoly left w
           r:XDPOLY := DPoly right w
           l*r - r*l

        RPoly w ==
           retractable? w => retract(w) :: XRPOLY
           l:XRPOLY := RPoly left w
           r:XRPOLY := RPoly right w
           l*r - r*l

      -- definitions

        coerce(v:VarSet) == monom(v::LWORD , 1)

        construct(x:$ , y:$):$ ==
            +/[t.c * cr1(t.k, y) for t in x]

        construct(l:LWORD , p:$):$ == cr1(l,p)
        construct(p:$ , l:LWORD):$ == cr2(p,l)
        construct(u:LWORD , v:LWORD):$ == crw(u,v)

        coerce(p:$):XDPOLY ==
            +/ [t.c * DPoly(t.k) for t in p]

        coerce(p:$):XRPOLY ==
            +/ [t.c * RPoly(t.k) for t in p]

        LiePoly(l) == monom(l,1)

        varList p ==
          le : List VarSet := "setUnion"/[varList(t.k)$LWORD for t in p]
          sort(le)$List(VarSet)

        mirror p ==
          [[t.k, (odd? length t.k => t.c; -t.c)]$TERM for t in p]

        trunc(p, n) ==
          degree(p) > n => trunc( reductum p , n)
          p

        degree p ==
          null p => 0
          length( p.first.k)$LWORD

      --  listOfTerms p == p pretend List TERM

--        coerce(x) : EX ==
```

```
--           null x => (0$R) :: EX
--           le : List EX := nil
--           for rec in x repeat
--             rec.c = 1$R => le := cons(rec.k :: EX, le)
--             le := cons(mkBinary("*"::EX,  rec.c :: EX, rec.k :: EX), le)
--           1 = #le => first le
--           mkNary("+" :: EX,le)
```

———-

— **LPOLY.dotabb** —

```
"LPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LPOLY"]
"FLALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLALG"]
"LPOLY" -> "FLALG"
```

———-

13.5 domain LSQM LieSquareMatrix

— **LieSquareMatrix.input** —

```
)set break resume
)sys rm -f LieSquareMatrix.output
)spool LieSquareMatrix.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show LieSquareMatrix
--R
--R LieSquareMatrix(n: PositiveInteger,R: CommutativeRing)  is a domain constructor
--R Abbreviation for LieSquareMatrix is LSQM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LSQM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : % -> % if R has DIFRING           D : (%,(R -> R)) -> %
```

```
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       alternative? : () -> Boolean
--R antiAssociative? : () -> Boolean     antiCommutative? : () -> Boolean
--R antiCommutator : (%,%) -> %          antisymmetric? : % -> Boolean
--R apply : (Matrix(R),%) -> %           associative? : () -> Boolean
--R associator : (%,%,%) -> %            basis : () -> Vector(%)
--R coerce : % -> Matrix(R)              coerce : R -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R commutative? : () -> Boolean         commutator : (%,%) -> %
--R convert : % -> Vector(R)             convert : Vector(R) -> %
--R coordinates : % -> Vector(R)         copy : % -> %
--R diagonal? : % -> Boolean             diagonalMatrix : List(R) -> %
--R diagonalProduct : % -> R             ?.? : (%,Integer) -> R
--R elt : (%,Integer,Integer) -> R       elt : (%,Integer,Integer,R) -> R
--R empty : () -> %                      empty? : % -> Boolean
--R eq? : (%,%) -> Boolean               flexible? : () -> Boolean
--R hash : % -> SingleInteger            jacobiIdentity? : () -> Boolean
--R jordanAdmissible? : () -> Boolean    jordanAlgebra? : () -> Boolean
--R latex : % -> String                  leftAlternative? : () -> Boolean
--R leftDiscriminant : Vector(%) -> R    leftDiscriminant : () -> R
--R leftNorm : % -> R                    leftTrace : % -> R
--R leftTraceMatrix : () -> Matrix(R)    lieAdmissible? : () -> Boolean
--R lieAlgebra? : () -> Boolean          listOfLists : % -> List(List(R))
--R map : ((R -> R),%) -> %              map : (((R,R) -> R),%,%) -> %
--R matrix : List(List(R)) -> %          maxColIndex : % -> Integer
--R maxRowIndex : % -> Integer           minColIndex : % -> Integer
--R minRowIndex : % -> Integer           ncols : % -> NonNegativeInteger
--R nrows : % -> NonNegativeInteger      one? : % -> Boolean
--R powerAssociative? : () -> Boolean    qelt : (%,Integer,Integer) -> R
--R rank : () -> PositiveInteger         recip : % -> Union(%,"failed")
--R represents : Vector(R) -> %          retract : % -> R
--R rightAlternative? : () -> Boolean    rightDiscriminant : () -> R
--R rightNorm : % -> R                   rightTrace : % -> R
--R rightTraceMatrix : () -> Matrix(R)   sample : () -> %
--R scalarMatrix : R -> %                someBasis : () -> Vector(%)
--R square? : % -> Boolean               symmetric? : % -> Boolean
--R trace : % -> R                       zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (DirectProduct(n,R),%) -> DirectProduct(n,R)
--R ?*? : (%,DirectProduct(n,R)) -> DirectProduct(n,R)
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Integer) -> % if R has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R D : (%,NonNegativeInteger) -> % if R has DIFRING
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
```

```
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R associatorDependence : () -> List(Vector(R)) if R has INTDOM
--R characteristic : () -> NonNegativeInteger
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT))
--R column : (%,Integer) -> DirectProduct(n,R)
--R conditionsForIdempotents : Vector(%) -> List(Polynomial(R))
--R conditionsForIdempotents : () -> List(Polynomial(R))
--R coordinates : (%,Vector(%)) -> Vector(R)
--R coordinates : (Vector(%),Vector(%)) -> Matrix(R)
--R coordinates : Vector(%) -> Matrix(R)
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R determinant : % -> R if R has commutative(*)
--R diagonal : % -> DirectProduct(n,R)
--R differentiate : % -> % if R has DIFRING
--R differentiate : (%,NonNegativeInteger) -> % if R has DIFRING
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,(R -> R)) -> %
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R inverse : % -> Union(%,"failed") if R has FIELD
--R leftCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R)
--R leftMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if R has INTDOM
--R leftPower : (%,PositiveInteger) -> %
--R leftRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if R has FIELD
--R leftRecip : % -> Union(%,"failed") if R has INTDOM
--R leftRegularRepresentation : (%,Vector(%)) -> Matrix(R)
--R leftRegularRepresentation : % -> Matrix(R)
--R leftTraceMatrix : Vector(%) -> Matrix(R)
--R leftUnit : () -> Union(%,"failed") if R has INTDOM
--R leftUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if R has INTDOM
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((R -> R),%) -> % if $ has shallowlyMutable
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R minordet : % -> R if R has commutative(*)
--R more? : (%,NonNegativeInteger) -> Boolean
--R noncommutativeJordanAlgebra? : () -> Boolean
--R nullSpace : % -> List(DirectProduct(n,R)) if R has INTDOM
--R nullity : % -> NonNegativeInteger if R has INTDOM
```

```
--R parts : % -> List(R) if $ has finiteAggregate
--R plenaryPower : (%,PositiveInteger) -> %
--R rank : % -> NonNegativeInteger if R has INTDOM
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R represents : (Vector(R),Vector(%)) -> %
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R rightCharacteristicPolynomial : % -> SparseUnivariatePolynomial(R)
--R rightDiscriminant : Vector(%) -> R
--R rightMinimalPolynomial : % -> SparseUnivariatePolynomial(R) if R has INTDOM
--R rightPower : (%,PositiveInteger) -> %
--R rightRankPolynomial : () -> SparseUnivariatePolynomial(Polynomial(R)) if R has FIELD
--R rightRecip : % -> Union(%,"failed") if R has INTDOM
--R rightRegularRepresentation : (%,Vector(%)) -> Matrix(R)
--R rightRegularRepresentation : % -> Matrix(R)
--R rightTraceMatrix : Vector(%) -> Matrix(R)
--R rightUnit : () -> Union(%,"failed") if R has INTDOM
--R rightUnits : () -> Union(Record(particular: %,basis: List(%)),"failed") if R has INTDOM
--R row : (%,Integer) -> DirectProduct(n,R)
--R rowEchelon : % -> % if R has EUCDOM
--R size? : (%,NonNegativeInteger) -> Boolean
--R structuralConstants : Vector(%) -> Vector(Matrix(R))
--R structuralConstants : () -> Vector(Matrix(R))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit : () -> Union(%,"failed") if R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— LieSquareMatrix.help —

```
=====================================================================
LieSquareMatrix examples
=====================================================================

See Also:
o )show LieSquareMatrix
```

———-

13.5.1 LieSquareMatrix (LSQM)



See

⇒ “AssociatedLieAlgebra” (LIE) 2.41.1 on page 213
⇒ “AssociatedJordanAlgebra” (JORDAN) 2.40.1 on page 208

Exports:

0	1	alternative?
antiAssociative?	antiCommutator	antisymmetric?
any?	apply	associative?
associator	associatorDependence	basis
characteristic	coerce	column
commutative?	commutator	conditionsForIdempotents
convert	coordinates	copy
count	D	determinant
diagonal	diagonal?	diagonalMatrix
diagonalProduct	differentiate	elt
empty	empty?	eq?
eval	every?	exquo
flexible?	hash	inverse
jacobiIdentity?	jordanAdmissible?	jordanAlgebra?
latex	leftAlternative?	leftCharacteristicPolynomial
leftDiscriminant	leftDiscriminant	leftMinimalPolynomial
leftNorm	leftPower	leftRankPolynomial
leftRecip	leftRegularRepresentation	leftRegularRepresentation
leftTrace	leftTraceMatrix	leftUnit
leftUnits	less?	lieAdmissible?
lieAlgebra?	listOfLists	map
map!	matrix	maxColIndex
maxRowIndex	member?	members
minColIndex	minordet	minRowIndex
more?	ncols	noncommutativeJordanAlgebra?
nrows	nullSpace	nullity
one?	parts	plenaryPower
powerAssociative?	qelt	rank
recip	reducedSystem	represents
retract	retractIfCan	rightAlternative?
rightCharacteristicPolynomial	rightDiscriminant	rightMinimalPolynomial
rightNorm	rightPower	rightRankPolynomial
rightRecip	rightRegularRepresentation	rightTrace
rightTraceMatrix	rightUnit	rightUnits
row	rowEchelon	sample
scalarMatrix	size?	someBasis
square?	structuralConstants	structuralConstants
subtractIfCan	symmetric?	trace
unit	zero?	#?
?~=?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?.?		

— domain LSQM LieSquareMatrix —

```
)abbrev domain LSQM LieSquareMatrix
++ Author: J. Grabmeier
++ Date Created: 07 March 1991
++ Date Last Updated: 08 March 1991
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ LieSquareMatrix(n,R) implements the Lie algebra of the n by n
++ matrices over the commutative ring R.
++ The Lie bracket (commutator) of the algebra is given by\br
++ \spad{a*b := (a *$SQMATRIX(n,R) b - b *$SQMATRIX(n,R) a)},\br
++ where \spadfun{*$SQMATRIX(n,R)} is the usual matrix multiplication.

LieSquareMatrix(n,R): Exports == Implementation where

  n    : PositiveInteger
  R    : CommutativeRing

  Row ==> DirectProduct(n,R)
  Col ==> DirectProduct(n,R)

  Exports ==> Join(SquareMatrixCategory(n,R,Row,Col), CoercibleTo Matrix R,_
      FramedNonAssociativeAlgebra R) --with

  Implementation ==> AssociatedLieAlgebra (R,SquareMatrix(n, R)) add

    Rep :=  AssociatedLieAlgebra (R,SquareMatrix(n, R))
      -- local functions
    n2 : PositiveInteger := n*n

    convDM : DirectProduct(n2,R) -> %
    conv : DirectProduct(n2,R) ->  SquareMatrix(n,R)
      --++ converts n2-vector to (n,n)-matrix row by row
    conv v  ==
      cond : Matrix(R) := new(n,n,0$R)$Matrix(R)
      z : Integer := 0
      for i in 1..n repeat
        for j in 1..n  repeat
          z := z+1
          setelt(cond,i,j,v.z)
      squareMatrix(cond)$SquareMatrix(n, R)


    coordinates(a:%,b:Vector(%)):Vector(R) ==
      -- only valid for b canonicalBasis
      res : Vector R := new(n2,0$R)
```

```
      z : Integer := 0
      for i in 1..n repeat
        for j in 1..n repeat
          z := z+1
          res.z := elt(a,i,j)$%
      res


    convDM v ==
      sq := conv v
      coerce(sq)$Rep :: %

    basis() ==
      n2 : PositiveInteger := n*n
      ldp : List DirectProduct(n2,R) :=
        [unitVector(i::PositiveInteger)$DirectProduct(n2,R) for i in 1..n2]
      res:Vector % := vector map(convDM,_
        ldp)$ListFunctions2(DirectProduct(n2,R), %)

    someBasis() == basis()
    rank() == n*n


--    transpose: % -> %
--      ++ computes the transpose of a matrix
--    squareMatrix: Matrix R -> %
--      ++ converts a Matrix to a LieSquareMatrix
--    coerce: % -> Matrix R
--      ++ converts a LieSquareMatrix to a Matrix
--    symdecomp : % -> Record(sym:%,antisym:%)
--    if R has commutative("*") then
--      minorsVect: -> Vector(Union(R,"uncomputed")) --range: 1..2**n-1
--    if R has commutative("*") then central
--    if R has commutative("*") and R has unitsKnown then unitsKnown
```

———-

— LSQM.dotabb —

```
"LSQM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LSQM"]
"FRNAALG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRNAALG"]
"LSQM" -> "FRNAALG"
```

———-

13.6 domain LODO LinearOrdinaryDifferentialOperator

— LinearOrdinaryDifferentialOperator.input —

```
)set break resume
)sys rm -f LinearOrdinaryDifferentialOperator.output
)spool LinearOrdinaryDifferentialOperator.output
)set message test on
)set message auto off
)clear all
--S 1 of 16
Dx: LODO(EXPR INT, f +-> D(f, x))
--R
--R                                                                  Type: Void
--E 1

--S 2 of 16
Dx := D()
--R
--R
--R   (2)  D
--IType: LinearOrdinaryDifferentialOperator(Expression(Integer),...
--E 2

--S 3 of 16
Dop:= Dx^3 + G/x^2*Dx + H/x^3 - 1
--R
--R
--R                         3
--R         3    G     - x  + H
--R   (3)  D  + -- D + --------
--R              2         3
--R             x         x
--IType: LinearOrdinaryDifferentialOperator(Expression(Integer),...
--E 3

--S 4 of 16
n == 3
--R
--R                                                                  Type: Void
--E 4

--S 5 of 16
phi == reduce(+,[subscript(s,[i])*exp(x)/x^i for i in 0..n])
--R
--R                                                                  Type: Void
--E 5
```

```
--S 6 of 16
phi1 ==  Dop(phi) / exp x
--R
--R                                                                   Type: Void
--E 6

--S 7 of 16
phi2 == phi1 *x**(n+3)
--R
--R                                                                   Type: Void
--E 7

--S 8 of 16
phi3 == retract(phi2)@(POLY INT)
--R
--R                                                                   Type: Void
--E 8

--S 9 of 16
pans == phi3 ::UP(x,POLY INT)
--R
--R                                                                   Type: Void
--E 9

--S 10 of 16
pans1 == [coefficient(pans, (n+3-i) :: NNI) for i in 2..n+1]
--R
--R                                                                   Type: Void
--E 10

--S 11 of 16
leq == solve(pans1,[subscript(s,[i]) for i in 1..n])
--R
--R                                                                   Type: Void
--E 11

--S 12 of 16
leq
--R
--R   Compiling body of rule n to compute value of type PositiveInteger
--R   Compiling body of rule phi to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi1 to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi2 to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi3 to compute value of type Polynomial(
--R      Integer)
--R   Compiling body of rule pans to compute value of type
--R      UnivariatePolynomial(x,Polynomial(Integer))
```

```
--R   Compiling body of rule pans1 to compute value of type List(
--R      Polynomial(Integer))
--R   Compiling body of rule leq to compute value of type List(List(
--R      Equation(Fraction(Polynomial(Integer)))))
--I   Compiling function G3491 with type Integer -> Boolean
--R
--R   (12)
--R                           2                                  3        2
--R         s G     3s H + s G  + 6s G     (9s G + 54s )H + s G  + 18s G  + 72s G
--R          0        0     0       0         0       0      0        0        0
--R   [[s = ---,s = ------------------,s = ------------------------------------]]
--R      1   3   2          18          3                    162
--R                         Type: List List Equation Fraction Polynomial Integer
--E 12

--S 13 of 16
n==4
--R
--R   Compiled code for n has been cleared.
--R   Compiled code for leq has been cleared.
--R   Compiled code for pans1 has been cleared.
--R   Compiled code for phi2 has been cleared.
--R   Compiled code for phi has been cleared.
--R   Compiled code for phi3 has been cleared.
--R   Compiled code for phi1 has been cleared.
--R   Compiled code for pans has been cleared.
--R   1 old definition(s) deleted for function or rule n
--R                                                                  Type: Void
--E 13

--S 14 of 16
leq
--R
--R   Compiling body of rule n to compute value of type PositiveInteger
--R   Compiling body of rule phi to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi1 to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi2 to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi3 to compute value of type Polynomial(
--R      Integer)
--R   Compiling body of rule pans to compute value of type
--R      UnivariatePolynomial(x,Polynomial(Integer))
--R   Compiling body of rule pans1 to compute value of type List(
--R      Polynomial(Integer))
--R   Compiling body of rule leq to compute value of type List(List(
--R      Equation(Fraction(Polynomial(Integer)))))
--R
--R   (14)
```

```
--R   [
--R                             2
--R          s G      3s H + s G  + 6s G
--R           0         0     0       0
--R     [s = ---, s = ------------------,
--R       1   3    2          18
--R                                3        2
--R          (9s G + 54s )H + s G  + 18s G  + 72s G
--R             0       0      0        0        0
--R      s = ---------------------------------------,
--R       3                    162
--R
--R       s  =
--R        4
--R                  2         2                          4        3         2
--R              27s H  + (18s G  + 378s G + 1296s )H + s G  + 36s G  + 396s G
--R                 0         0         0         0      0        0         0
--R           +
--R             1296s G
--R                  0
--R        /
--R           1944
--R       ]
--R     ]
--R                    Type: List(List(Equation(Fraction(Polynomial(Integer)))))
--E 14

--S 15 of 16
n==7
--R
--R   Compiled code for n has been cleared.
--R   Compiled code for leq has been cleared.
--R   Compiled code for pans1 has been cleared.
--R   Compiled code for phi2 has been cleared.
--R   Compiled code for phi has been cleared.
--R   Compiled code for phi3 has been cleared.
--R   Compiled code for phi1 has been cleared.
--R   Compiled code for pans has been cleared.
--R   1 old definition(s) deleted for function or rule n
--R                                                                    Type: Void
--E 15

--S 16 of 16
leq
--R
--R   Compiling body of rule n to compute value of type PositiveInteger
--R   Compiling body of rule phi to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi1 to compute value of type Expression(
--R      Integer)
```

```
--R   Compiling body of rule phi2 to compute value of type Expression(
--R      Integer)
--R   Compiling body of rule phi3 to compute value of type Polynomial(
--R      Integer)
--R   Compiling body of rule pans to compute value of type
--R      UnivariatePolynomial(x,Polynomial(Integer))
--R   Compiling body of rule pans1 to compute value of type List(
--R      Polynomial(Integer))
--R   Compiling body of rule leq to compute value of type List(List(
--R      Equation(Fraction(Polynomial(Integer)))))
--R
--R   (16)
--R   [
--R                             2
--R          s G      3s H + s G  + 6s G
--R           0         0     0       0
--R     [s = ---, s = ------------------,
--R       1   3    2          18
--R                               3        2
--R          (9s G + 54s )H + s G  + 18s G  + 72s G
--R             0       0      0        0        0
--R      s = ------------------------------------,
--R       3                    162
--R
--R       s  =
--R        4
--R                  2         2                          4        3         2
--R             27s H  + (18s G  + 378s G + 1296s )H + s G  + 36s G  + 396s G
--R                0         0         0         0      0        0         0
--R           +
--R             1296s G
--R                  0
--R        /
--R           1944
--R       ,
--R
--R       s  =
--R        5
--R                               2         3          2
--R             (135s G + 2268s )H  + (30s G  + 1350s G  + 16416s G + 38880s )H
--R                  0         0          0          0           0          0
--R           +
--R                5        4          3          2
--R             s G  + 60s G  + 1188s G  + 9504s G  + 25920s G
--R              0        0          0          0           0
--R        /
--R           29160
--R       ,
--R
--R       s  =
```

```
--R        6
--R                3          2                        2
--R             405s H  + (405s G  + 18468s G + 174960s )H
--R                 0          0           0           0
--R           +
--R                 4          3           2                                6
--R             (45s G  + 3510s G  + 88776s G  + 777600s G + 1166400s )H + s G
--R                 0          0           0            0            0      0
--R           +
--R                 5          4           3           2
--R             90s G  + 2628s G  + 27864s G  + 90720s G
--R                0          0           0           0
--R        /
--R           524880
--R       ,
--R
--R       s  =
--R        7
--R                              3
--R             (2835s G + 91854s )H
--R                   0          0
--R           +
--R                    3           2                            2
--R             (945s G  + 81648s G  + 2082996s G + 14171760s )H
--R                  0           0             0             0
--R           +
--R                    5          4            3             2
--R             (63s G  + 7560s G  + 317520s G  + 5554008s G  + 34058880s G)H
--R                 0          0            0             0              0
--R           +
--R                7         6          5           4             3              2
--R             s G  + 126s G  + 4788s G  + 25272s G  - 1744416s G  - 26827200s G
--R              0         0          0           0             0              0
--R           +
--R             - 97977600s G
--R                         0
--R        /
--R           11022480
--R       ]
--R     ]
--R                        Type: List List Equation Fraction Polynomial Integer
--E 16
)spool
```

———-

— LinearOrdinaryDifferentialOperator.help —

```
=====================================================================
LinearOrdinaryDifferentialOperator examples
=====================================================================

LinearOrdinaryDifferentialOperator(A, diff) is the domain of linear
ordinary differential operators with coefficients in a ring A with a
given derivation.

=====================================================================
Differential Operators with Series Coefficients
=====================================================================

Problem:
  Find the first few coefficients of exp(x)/x^i of Dop phi where

    Dop := D^3 + G/x^2 * D + H/x^3 - 1
    phi := sum(s[i]*exp(x)/x^i, i = 0..)

Solution:

Define the differential.

  Dx: LODO(EXPR INT, f +-> D(f, x))
                          Type: Void

  Dx := D()
   D
     Type: LinearOrdinaryDifferentialOperator(Expression Integer,
      theMap LAMBDA-CLOSURE(NIL,NIL,NIL,G1404 envArg,
              SPADCALL(G1404,QUOTE x,
               ELT(*1;anonymousFunction;0;frame0;internal;MV,0))))

Now define the differential operator Dop.

  Dop:= Dx^3 + G/x^2*Dx + H/x^3 - 1
                        3
     3    G     - x  + H
    D  + -- D + --------
          2         3
         x         x
     Type: LinearOrdinaryDifferentialOperator(Expression Integer,
      theMap LAMBDA-CLOSURE(NIL,NIL,NIL,G1404 envArg,
              SPADCALL(G1404,QUOTE x,
               ELT(*1;anonymousFunction;0;frame0;internal;MV,0))))

  n == 3
                          Type: Void

  phi == reduce(+,[subscript(s,[i])*exp(x)/x^i for i in 0..n])
                          Type: Void
```

```
phi1 ==  Dop(phi) / exp x
                        Type: Void

phi2 == phi1 *x**(n+3)
                        Type: Void

phi3 == retract(phi2)@(POLY INT)
                        Type: Void

pans == phi3 ::UP(x,POLY INT)
                        Type: Void

pans1 == [coefficient(pans, (n+3-i) :: NNI) for i in 2..n+1]
                        Type: Void

leq == solve(pans1,[subscript(s,[i]) for i in 1..n])
                        Type: Void
```

Evaluate this for several values of n.

```
leq
                        2                                  3        2
      s G     3s H + s G  + 6s G     (9s G + 54s )H + s G  + 18s G  + 72s G
       0        0     0       0         0       0      0        0        0
[[s = ---,s = ------------------,s = ---------------------------------------]]
   1   3   2          18          3                    162
                       Type: List List Equation Fraction Polynomial Integer

n==4
                        Type: Void

leq
 [
                          2
        s G      3s H + s G  + 6s G
         0         0     0       0
   [s = ---, s = ------------------,
     1   3    2          18
                            3        2
        (9s G + 54s )H + s G  + 18s G  + 72s G
           0       0      0        0        0
    s = ---------------------------------------,
     3                    162

     s  =
      4
                2         2                           4        3         2
           27s H  + (18s G  + 378s G + 1296s )H + s G  + 36s G  + 396s G
              0         0         0         0      0        0         0
```

```
          +
            1296s G
                 0
       /
          1944
      ]
    ]
                        Type: List List Equation Fraction Polynomial Integer

n==7
                         Type: Void

leq
 [
                            2
         s G      3s H + s G  + 6s G
          0         0     0       0
    [s = ---, s = ------------------,
      1   3    2          18
                              3       2
         (9s G + 54s )H + s G  + 18s G  + 72s G
            0       0      0        0        0
     s = ---------------------------------------,
      3                    162

      s  =
       4
                 2         2                          4        3         2
            27s H  + (18s G  + 378s G + 1296s )H + s G  + 36s G  + 396s G
               0          0         0         0      0        0         0
          +
            1296s G
                 0
       /
          1944
      ,

      s  =
       5
                             2         3          2
            (135s G + 2268s )H  + (30s G  + 1350s G  + 16416s G + 38880s )H
                 0          0          0          0           0          0
          +
               5        4          3          2
            s G  + 60s G  + 1188s G  + 9504s G  + 25920s G
             0        0          0          0           0
       /
          29160
      ,
```


```
      s  =
       6
                 3          2                        2
            405s H  + (405s G  + 18468s G + 174960s )H
                0           0           0           0
          +
                 4          3           2                                  6
            (45s G  + 3510s G  + 88776s G  + 777600s G + 1166400s )H + s G
                0           0           0            0            0      0
          +
                 5          4           3           2
            90s G  + 2628s G  + 27864s G  + 90720s G
               0           0           0           0
       /
          524880
      ,

      s  =
       7
                              3
            (2835s G + 91854s )H
                  0          0
          +
                   3          2                             2
            (945s G  + 81648s G  + 2082996s G + 14171760s )H
                 0           0             0             0
          +
                 5          4            3             2
            (63s G  + 7560s G  + 317520s G  + 5554008s G  + 34058880s G)H
                0           0            0             0              0
          +
               7         6          5           4             3              2
            s G  + 126s G  + 4788s G  + 25272s G  - 1744416s G  - 26827200s G
             0         0          0           0             0              0
          +
            - 97977600s G
                       0
       /
          11022480
        ]
      ]
                                Type: List List Equation Fraction Polynomial Integer
```

See Also:
o)show LinearOrdinaryDifferentialOperator

———————-

13.6.1 LinearOrdinaryDifferentialOperator (LODO)



See

⇒ "LinearOrdinaryDifferentialOperator1" (LODO1) 13.7.1 on page 1447
⇒ "LinearOrdinaryDifferentialOperator2" (LODO2) 13.8.1 on page 1459

Exports:

0	1	adjoint
apply	characteristic	coefficient
coefficients	coerce	content
D	degree	directSum
exquo	hash	latex
leadingCoefficient	leftDivide	leftExactQuotient
leftExtendedGcd	leftGcd	leftLcm
leftQuotient	leftRemainder	minimumDegree
monicLeftDivide	monicRightDivide	monomial
one?	primitivePart	recip
reductum	retract	retractIfCan
rightDivide	rightExactQuotient	rightExtendedGcd
rightGcd	rightLcm	rightQuotient
rightRemainder	sample	subtractIfCan
symmetricPower	symmetricProduct	symmetricSquare
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?.?
?~=?		

— domain LODO LinearOrdinaryDifferentialOperator —

```
)abbrev domain LODO LinearOrdinaryDifferentialOperator
++ Author: Manuel Bronstein
++ Date Created: 9 December 1993
++ Date Last Updated: 15 April 1994
++ Keywords: differential operator
++ Description:
++ \spad{LinearOrdinaryDifferentialOperator} defines a ring of
```

```
++ differential operators with coefficients in a ring A with a given
++ derivation.
++ Multiplication of operators corresponds to functional composition:\br
++ \spad{(L1 * L2).(f) = L1 L2 f}

LinearOrdinaryDifferentialOperator(A:Ring, diff: A -> A):
    LinearOrdinaryDifferentialOperatorCategory A
      == SparseUnivariateSkewPolynomial(A, 1, diff) add
        Rep := SparseUnivariateSkewPolynomial(A, 1, diff)

        outputD := "D"@String :: Symbol :: OutputForm

        coerce(l:%):OutputForm == outputForm(l, outputD)
        elt(p:%, a:A):A        == apply(p, 0, a)

        if A has Field then
            import LinearOrdinaryDifferentialOperatorsOps(A, %)

            symmetricProduct(a, b) == symmetricProduct(a, b, diff)
            symmetricPower(a, n)   == symmetricPower(a, n, diff)
            directSum(a, b)        == directSum(a, b, diff)
```

———-

— LODO.dotabb —

```
"LODO" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LODO"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"LODO" -> "ALIST"
```

———-

13.7 domain LODO1 LinearOrdinaryDifferentialOperator1

— LinearOrdinaryDifferentialOperator1.input —

```
)set break resume
)sys rm -f LinearOrdinaryDifferentialOperator1.output
)spool LinearOrdinaryDifferentialOperator1.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 20
RFZ := Fraction UnivariatePolynomial('x, Integer)
--R
--R
--R   (1)  Fraction(UnivariatePolynomial(x,Integer))
--R                                                                    Type: Domain
--E 1

--S 2 of 20
x : RFZ := 'x
--R
--R
--R   (2)  x
--R                              Type: Fraction(UnivariatePolynomial(x,Integer))
--E 2

--S 3 of 20
Dx : LODO1 RFZ := D()
--R
--R
--R   (3)  D
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 3

--S 4 of 20
b : LODO1 RFZ := 3*x**2*Dx**2 + 2*Dx + 1/x
--R
--R
--R          2 2        1
--R   (4)  3x D  + 2D + -
--R                     x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 4

--S 5 of 20
a : LODO1 RFZ := b*(5*x*Dx + 7)
--R
--R
--R           3 3       2        2         7
--R   (5)  15x D  + (51x  + 10x)D  + 29D + -
--R                                       x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 5

--S 6 of 20
p := x**2 + 1/x**2
--R
--R
--R         4
--R        x  + 1
```

```
--R   (6)  ------
--R           2
--R          x
--R                                Type: Fraction(UnivariatePolynomial(x,Integer))
--E 6

--S 7 of 20
(a*b - b*a) p
--R
--R
--R             4
--R        - 75x  + 540x - 75
--R   (7)  ------------------
--R                 4
--R                x
--R                                Type: Fraction(UnivariatePolynomial(x,Integer))
--E 7

--S 8 of 20
ld := leftDivide(a,b)
--R
--R
--R   (8)  [quotient= 5x D + 7,remainder= 0]
--IType: Record(quotient: LinearOrdinaryDifferentialOperator1(Fraction(...
--E 8

--S 9 of 20
a = b * ld.quotient + ld.remainder
--R
--R
--R           3 3       2        2         7     3 3       2        2         7
--R   (9)  15x D  + (51x  + 10x)D  + 29D + -= 15x D  + (51x  + 10x)D  + 29D + -
--R                                        x                                  x
--RType: Equation(LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer))))
--E 9

--S 10 of 20
rd := rightDivide(a,b)
--R
--R
--R                                                 5
--R   (10)  [quotient= 5x D + 7,remainder= 10D + -]
--R                                                 x
--IType: Record(quotient: LinearOrdinaryDifferentialOperator1(...
--E 10

--S 11 of 20
a = rd.quotient * b + rd.remainder
--R
--R
```

```
--R            3 3       2        2         7     3 3       2        2         7
--R   (11)  15x D  + (51x  + 10x)D  + 29D + -= 15x D  + (51x  + 10x)D  + 29D + -
--R                                          x                                 x
--RType: Equation(LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer))))
--E 11

--S 12 of 20
rightQuotient(a,b)
--R
--R
--R   (12)  5x D + 7
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 12

--S 13 of 20
rightRemainder(a,b)
--R
--R
--R               5
--R   (13)  10D + -
--R               x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 13

--S 14 of 20
leftExactQuotient(a,b)
--R
--R
--R   (14)  5x D + 7
--RType: Union(LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer))),...)
--E 14

--S 15 of 20
e := leftGcd(a,b)
--R
--R
--R           2 2        1
--R   (15)  3x D  + 2D + -
--R                      x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 15

--S 16 of 20
leftRemainder(a, e)
--R
--R
--R   (16)  0
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 16
```

```
--S 17 of 20
rightRemainder(a, e)
--R
--R
--R               5
--R   (17)  10D + -
--R               x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 17

--S 18 of 20
f := rightLcm(a,b)
--R
--R
--R            3 3       2        2         7
--R   (18)  15x D  + (51x  + 10x)D  + 29D + -
--R                                        x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 18

--S 19 of 20
rightRemainder(f, b)
--R
--R
--R               5
--R   (19)  10D + -
--R               x
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 19

--S 20 of 20
leftRemainder(f, b)
--R
--R
--R   (20)  0
--RType: LinearOrdinaryDifferentialOperator1(Fraction(UnivariatePolynomial(x,Integer)))
--E 20
)spool
)lisp (bye)
```

———-

— LinearOrdinaryDifferentialOperator1.help —

```
====================================================================
LinearOrdinaryDifferentialOperator1 example
====================================================================

LinearOrdinaryDifferentialOperator1(A) is the domain of linear
```

```
ordinary differential operators with coefficients in the differential
ring A.

=====================================================================
Differential Operators with Rational Function Coefficients
=====================================================================

This example shows differential operators with rational function
coefficients.  In this case operator multiplication is non-commutative and,
since the coefficients form a field, an operator division algorithm exists.

We begin by defining RFZ to be the rational functions in x with
integer coefficients and Dx to be the differential operator for d/dx.

  RFZ := Fraction UnivariatePolynomial('x, Integer)
    Fraction UnivariatePolynomial(x,Integer)
                          Type: Domain

  x : RFZ := 'x
    x
                          Type: Fraction UnivariatePolynomial(x,Integer)

  Dx : LODO1 RFZ := D()
    D
                          Type: LinearOrdinaryDifferentialOperator1
                                  Fraction UnivariatePolynomial(x,Integer)

Operators are created using the usual arithmetic operations.

  b : LODO1 RFZ := 3*x**2*Dx**2 + 2*Dx + 1/x
      2 2         1
    3x D  + 2D + -
                x
                          Type: LinearOrdinaryDifferentialOperator1
                                 Fraction UnivariatePolynomial(x,Integer)

  a : LODO1 RFZ := b*(5*x*Dx + 7)
       3 3       2        2         7
    15x D  + (51x  + 10x)D  + 29D + -
                                    x
                        Type: LinearOrdinaryDifferentialOperator1
                                 Fraction UnivariatePolynomial(x,Integer)

Operator multiplication corresponds to functional composition.

  p := x**2 + 1/x**2
     4
    x  + 1
    ------
       2
```

```
     x
                        Type: Fraction UnivariatePolynomial(x,Integer)
```

Since operator coefficients depend on x, the multiplication is not commutative.

```
  (a*b - b*a) p
         4
    - 75x  + 540x - 75
    ------------------
             4
            x
                        Type: Fraction UnivariatePolynomial(x,Integer)
```

When the coefficients of operator polynomials come from a field, as in this case, it is possible to define operator division. Division on the left and division on the right yield different results when the multiplication is non-commutative.

The results of leftDivide and rightDivide are quotient-remainder pairs satisfying:

```
  leftDivide(a,b) = [q, r] such that  a = b*q + r
  rightDivide(a,b) = [q, r] such that a = q*b + r
```

In both cases, the degree of the remainder, r, is less than the degree of b.

```
  ld := leftDivide(a,b)
    [quotient= 5x D + 7,remainder= 0]
      Type: Record(quotient: LinearOrdinaryDifferentialOperator1
                               Fraction UnivariatePolynomial(x,Integer),
                   remainder: LinearOrdinaryDifferentialOperator1
                               Fraction UnivariatePolynomial(x,Integer))

  a = b * ld.quotient + ld.remainder
       3 3       2         2          7     3 3       2         2          7
    15x D  + (51x  + 10x)D  + 29D + -= 15x D  + (51x  + 10x)D  + 29D + -
      Type: Equation LinearOrdinaryDifferentialOperator1
                      Fraction UnivariatePolynomial(x,Integer)
```

The operations of left and right division are so-called because the quotient is obtained by dividing a on that side by b.

```
  rd := rightDivide(a,b)
    [quotient= 5x D + 7,remainder= 10D + -]
      Type: Record(quotient: LinearOrdinaryDifferentialOperator1
                               Fraction UnivariatePolynomial(x,Integer),
                   remainder: LinearOrdinaryDifferentialOperator1
                               Fraction UnivariatePolynomial(x,Integer))
```

```
  a = rd.quotient * b + rd.remainder
       3 3       2        2         7     3 3       2        2         7
    15x D  + (51x  + 10x)D  + 29D + -= 15x D  + (51x  + 10x)D  + 29D + -
     Type: Equation LinearOrdinaryDifferentialOperator1
                     Fraction UnivariatePolynomial(x,Integer)
```

Operations rightQuotient and rightRemainder are available if only one
of the quotient or remainder are of interest to you. This is the
quotient from right division.

```
  rightQuotient(a,b)
    5x D + 7
     Type: LinearOrdinaryDifferentialOperator1
             Fraction UnivariatePolynomial(x,Integer)
```

This is the remainder from right division. The corresponding "left"
functions, leftQuotient and leftRemainder are also available.

```
  rightRemainder(a,b)
          5
    10D + -
          x
      Type: LinearOrdinaryDifferentialOperator1
              Fraction UnivariatePolynomial(x,Integer)
```

For exact division, operations leftExactQuotient and rightExactQuotient
are supplied. These return the quotient but only if the remainder is zero.
The call rightExactQuotient(a,b) would yield an error.

```
  leftExactQuotient(a,b)
    5x D + 7
     Type: Union(LinearOrdinaryDifferentialOperator1
                   Fraction UnivariatePolynomial(x,Integer),...)
```

The division operations allow the computation of left and right greatest
common divisors, leftGcd and rightGcd via remainder sequences, and
consequently the computation of left and right least common multiples,
rightLcm and leftLcm.

```
  e := leftGcd(a,b)
      2 2       1
    3x D  + 2D + -
                x
     Type: LinearOrdinaryDifferentialOperator1
             Fraction UnivariatePolynomial(x,Integer)
```

Note that a greatest common divisor doesn't necessarily divide a and b
on both sides. Here the left greatest common divisor does not divide
a on the right.

```
  leftRemainder(a, e)
    0
      Type: LinearOrdinaryDifferentialOperator1
              Fraction UnivariatePolynomial(x,Integer)

  rightRemainder(a, e)
          5
    10D + -
          x
      Type: LinearOrdinaryDifferentialOperator1
              Fraction UnivariatePolynomial(x,Integer)
```

Similarly, a least common multiple is not necessarily divisible from both sides.


```
  f := rightLcm(a,b)
       3 3       2        2         7
    15x D  + (51x  + 10x)D  + 29D + -
      Type: LinearOrdinaryDifferentialOperator1
              Fraction UnivariatePolynomial(x,Integer)

  rightRemainder(f, b)
          5
    10D + -
          x
      Type: LinearOrdinaryDifferentialOperator1
              Fraction UnivariatePolynomial(x,Integer)

  leftRemainder(f, b)
    0
      Type: LinearOrdinaryDifferentialOperator1
              Fraction UnivariatePolynomial(x,Integer)
```

See Also:
o)show LinearOrdinaryDifferentialOperator1

13.7.1 LinearOrdinaryDifferentialOperator1 (LODO1)



See

⇒ "LinearOrdinaryDifferentialOperator" (LODO) 13.6.1 on page 1437
⇒ "LinearOrdinaryDifferentialOperator2" (LODO2) 13.8.1 on page 1459

Exports:

0	1	adjoint	apply
characteristic	coefficient	coefficients	coerce
content	D	degree	directSum
exquo	hash	latex	leadingCoefficient
leftDivide	leftExactQuotient	leftExtendedGcd	leftGcd
leftLcm	leftQuotient	leftRemainder	minimumDegree
monicLeftDivide	monicRightDivide	monomial	one?
primitivePart	recip	reductum	retract
retractIfCan	rightDivide	rightExactQuotient	rightExtendedGcd
rightGcd	rightLcm	rightQuotient	rightRemainder
sample	subtractIfCan	symmetricPower	symmetricProduct
symmetricSquare	zero?	?*?	?**?
?+?	?-?	-?	?=?
?^?	?.?	?~=?	

— domain LODO1 LinearOrdinaryDifferentialOperator1 —

```
)abbrev domain LODO1 LinearOrdinaryDifferentialOperator1
++ Author: Manuel Bronstein
++ Date Created: 9 December 1993
++ Date Last Updated: 31 January 1994
++ Keywords: differential operator
++ Description:
++ \spad{LinearOrdinaryDifferentialOperator1} defines a ring of
++ differential operators with coefficients in a differential ring A.
++ Multiplication of operators corresponds to functional composition:\br
++ \spad{(L1 * L2).(f) = L1 L2 f}

LinearOrdinaryDifferentialOperator1(A:DifferentialRing) ==
  LinearOrdinaryDifferentialOperator(A, differentiate$A)
```

———-

— **LODO1.dotabb** —

```
"LODO1" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LODO1"]
"LODOCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=LODOCAT"]
"LODO1" -> "LODOCAT"
```

———-

13.8 domain LODO2 LinearOrdinaryDifferentialOperator2

— **LinearOrdinaryDifferentialOperator2.input** —

```
)set break resume
)sys rm -f LinearOrdinaryDifferentialOperator2.output
)spool LinearOrdinaryDifferentialOperator2.output
)set message test on
)set message auto off
)clear all
--S 1 of 26
Q  := Fraction Integer
--R
--R
--R   (1)  Fraction(Integer)
--R                                                          Type: Domain
--E 1

--S 2 of 26
PQ := UnivariatePolynomial('x, Q)
--R
--R
--R   (2)  UnivariatePolynomial(x,Fraction(Integer))
--R                                                          Type: Domain
--E 2

--S 3 of 26
x: PQ := 'x
--R
--R
--R   (3)  x
```

```
--R                                Type: UnivariatePolynomial(x,Fraction(Integer))
--E 3

--S 4 of 26
Dx: LODO2(Q, PQ) := D()
--R
--R
--R   (4)  D
--RType: LinearOrdinaryDifferentialOperator2(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 4

--S 5 of 26
a := Dx  + 1
--R
--R
--R   (5)  D + 1
--RType: LinearOrdinaryDifferentialOperator2(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 5

--S 6 of 26
b := a + 1/2*Dx**2 - 1/2
--R
--R
--R        1  2       1
--R   (6)  - D  + D + -
--R        2          2
--RType: LinearOrdinaryDifferentialOperator2(Fraction(Integer),UnivariatePolynomial(x,Fraction(Integer)))
--E 6

--S 7 of 26
p := 4*x**2 + 2/3
--R
--R
--R          2   2
--R   (7)  4x  + -
--R              3
--R                                Type: UnivariatePolynomial(x,Fraction(Integer))
--E 7

--S 8 of 26
a p
--R
--R
--R          2        2
--R   (8)  4x  + 8x + -
--R                   3
--R                                Type: UnivariatePolynomial(x,Fraction(Integer))
--E 8

--S 9 of 26
```

```
(a * b) p = a b p
--R
--R
--R          2         37    2         37
--R   (9)  2x  + 12x + --= 2x  + 12x + --
--R                    3               3
--R                    Type: Equation(UnivariatePolynomial(x,Fraction(Integer)))
--E 9

--S 10 of 26
c := (1/9)*b*(a + b)^2
--R
--R
--R          1  6    5  5   13  4   19  3   79  2    7     1
--R   (10)  -- D  + -- D  + -- D  + -- D  + -- D  + -- D + -
--R         72      36      24      18      72      12     8
--RType: LinearOrdinaryDifferentialOperator2(Fraction(Integer),UnivariatePolynomial(x,Fraction(I
--E 10

--S 11 of 26
(a**2 - 3/4*b + c) (p + 1)
--R
--R
--R           2   44     541
--R   (11)  3x  + -- x + ---
--R               3      36
--R                              Type: UnivariatePolynomial(x,Fraction(Integer))
--E 11
)clear all
--S 12 of 26
PZ := UnivariatePolynomial(x,Integer)
--R
--R
--R   (1)  UnivariatePolynomial(x,Integer)
--R                                                                  Type: Domain
--E 12

--S 13 of 26
x:PZ := 'x
--R
--R
--R   (2)  x
--R                                       Type: UnivariatePolynomial(x,Integer)
--E 13

--S 14 of 26
Mat  := SquareMatrix(3,PZ)
--R
--R
--R   (3)  SquareMatrix(3,UnivariatePolynomial(x,Integer))
```

```
--R                                                                    Type: Domain
--E 14

--S 15 of 26
Vect := DPMM(3, PZ, Mat, PZ)
--R
--R
--R   (4)
--R  DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),SquareMatrix(3,Un
--R  ivariatePolynomial(x,Integer)),UnivariatePolynomial(x,Integer))
--R                                                                    Type: Domain
--E 15

--S 16 of 26
Modo := LODO2(Mat, Vect)
--R
--R
--R   (5)
--R  LinearOrdinaryDifferentialOperator2(SquareMatrix(3,UnivariatePolynomial(x,Int
--R  eger)),DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),SquareMatr
--R  ix(3,UnivariatePolynomial(x,Integer)),UnivariatePolynomial(x,Integer)))
--R                                                                    Type: Domain
--E 16

--S 17 of 26
m:Mat := matrix [ [x^2,1,0],[1,x^4,0],[0,0,4*x^2] ]
--R
--R
--R        + 2         +
--R        |x   1    0 |
--R        |           |
--R   (6)  |     4     |
--R        |1   x    0 |
--R        |           |
--R        |          2|
--R        +0   0   4x +
--R                        Type: SquareMatrix(3,UnivariatePolynomial(x,Integer))
--E 17

--S 18 of 26
p:Vect := directProduct [3*x^2+1,2*x,7*x^3+2*x]
--R
--R
--R           2          3
--R   (7)  [3x  + 1,2x,7x  + 2x]
--IType: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),...
--E 18

--S 19 of 26
q: Vect := m * p
```

```
--R
--R
--R           4    2        5     2        5     3
--R   (8)  [3x  + x  + 2x,2x  + 3x  + 1,28x  + 8x ]
--IType: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),...
--E 19

--S 20 of 26
Dx : Modo := D()
--R
--R
--R   (9)  D
--IType: LinearOrdinaryDifferentialOperator2(SquareMatrix(...
--E 20

--S 21 of 26
a : Modo := Dx  + m
--R
--R
--R             + 2         +
--R             |x   1    0 |
--R             |           |
--R   (10)  D + |     4     |
--R             |1   x    0 |
--R             |           |
--R             |          2|
--R             +0   0   4x +
--IType: LinearOrdinaryDifferentialOperator2(SquareMatrix(...
--E 21

--S 22 of 26
b : Modo := m*Dx  + 1
--R
--R
--R         + 2         +
--R         |x   1    0 |    +1  0  0+
--R         |           |    |       |
--R   (11)  |     4     |D + |0  1  0|
--R         |1   x    0 |    |       |
--R         |           |    +0  0  1+
--R         |          2|
--R         +0   0   4x +
--IType: LinearOrdinaryDifferentialOperator2(SquareMatrix(...
--E 22

--S 23 of 26
c := a*b
--R
--R
--R   (12)
```

```
--R   + 2         +     + 4             4    2                 +    + 2         +
--R   |x   1    0 |     |x  + 2x + 2    x  + x            0     |    |x   1    0 |
--R   |           | 2   |                                      |    |           |
--R   |     4     |D  + |   4    2     8     3                 |D + |     4     |
--R   |1   x    0 |     |  x  + x     x  + 4x  + 2        0     |    |1   x    0 |
--R   |           |     |                                      |    |           |
--R   |          2|     |                              4       |    |          2|
--R   +0   0   4x +     +     0            0        16x  + 8x + 1+    +0   0   4x +
--IType: LinearOrdinaryDifferentialOperator2(SquareMatrix(3,...
--E 23

--S 24 of 26
a p
--R
--R
--R            4    2        5     2        5     3      2
--R   (13)  [3x  + x  + 8x,2x  + 3x  + 3,28x  + 8x  + 21x  + 2]
--IType: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),...
--E 24

--S 25 of 26
b p
--R
--R
--R            3     2       4         4     3     2
--R   (14)  [6x  + 3x  + 3,2x  + 8x,84x  + 7x  + 8x  + 2x]
--IType: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),...
--E 25

--S 26 of 26
(a + b + c) (p + q)
--R
--R
--R   (15)
--R       8      7      6      5      4      3      2
--R   [10x  + 12x  + 16x  + 30x  + 85x  + 94x  + 40x  + 40x + 17,
--R       12      9      8      7     6      5      4      3      2
--R    10x   + 10x  + 12x  + 92x  + 6x  + 32x  + 72x  + 28x  + 49x  + 32x + 19,
--R         8       7        6        5       4       3      2
--R    2240x  + 224x  + 1280x  + 3508x  + 492x  + 751x  + 98x  + 18x + 4]
--IType: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),...
--E 26
)spool
)lisp (bye)
```

———-

— LinearOrdinaryDifferentialOperator2.help —

```
=====================================================================
LinearOrdinaryDifferentialOperator2
=====================================================================

LinearOrdinaryDifferentialOperator2(A, M) is the domain of linear
ordinary differential operators with coefficients in the differential
ring A and operating on M, an A-module.  This includes the cases of
operators which are polynomials in D acting upon scalar or vector
expressions of a single variable.  The coefficients of the operator
polynomials can be integers, rational functions, matrices or elements
of other domains.

=====================================================================
Differential Operators with Constant Coefficients
=====================================================================

This example shows differential operators with rational number
coefficients operating on univariate polynomials.

We begin by making type assignments so we can conveniently refer
to univariate polynomials in x over the rationals.

  Q  := Fraction Integer
    Fraction Integer
                          Type: Domain

  PQ := UnivariatePolynomial('x, Q)
    UnivariatePolynomial(x,Fraction Integer)
                          Type: Domain

  x: PQ := 'x
    x
                          Type: UnivariatePolynomial(x,Fraction Integer)

Now we assign Dx to be the differential operator D corresponding to d/dx.

  Dx: LODO2(Q, PQ) := D()
    D
     Type: LinearOrdinaryDifferentialOperator2(Fraction Integer,
             UnivariatePolynomial(x,Fraction Integer))

New operators are created as polynomials in D().

  a := Dx  + 1
    D + 1
     Type: LinearOrdinaryDifferentialOperator2(Fraction Integer,
             UnivariatePolynomial(x,Fraction Integer))

  b := a + 1/2*Dx**2 - 1/2
    1  2       1
```

```
    - D  + D + -
    2          2
      Type: LinearOrdinaryDifferentialOperator2(Fraction Integer,
              UnivariatePolynomial(x,Fraction Integer))
```

To apply the operator a to the value p the usual function call syntax is used.

```
  p := 4*x**2 + 2/3
      2   2
    4x  + -
          3
                     Type: UnivariatePolynomial(x,Fraction Integer)

  a p
      2        2
    4x  + 8x + -
               3
                     Type: UnivariatePolynomial(x,Fraction Integer)
```

Operator multiplication is defined by the identity (a*b)p = a(b(p))

```
  (a * b) p = a b p
      2         37    2         37
    2x  + 12x + --= 2x  + 12x + --
                 3               3
                     Type: Equation UnivariatePolynomial(x,Fraction Integer)
```

Exponentiation follows from multiplication.

```
  c := (1/9)*b*(a + b)^2
      1  6    5  5   13  4   19  3   79  2    7     1
     -- D  + -- D  + -- D  + -- D  + -- D  + -- D + -
     72      36      24      18      72      12     8
      Type: LinearOrdinaryDifferentialOperator2(Fraction Integer,
              UnivariatePolynomial(x,Fraction Integer))
```

Finally, note that operator expressions may be applied directly.

```
  (a**2 - 3/4*b + c) (p + 1)
       2   44     541
     3x  + -- x + ---
            3      36
                     Type: UnivariatePolynomial(x,Fraction Integer)
```

```
========================================================================
Differential Operators with Matrix Coefficients Operating on Vectors}
========================================================================
```

This is another example of linear ordinary differential operators with

non-commutative multiplication. Unlike the rational function case, the differential ring of square matrices (of a given dimension) with univariate polynomial entries does not form a field. Thus the number of operations available is more limited.

In this section, the operators have three by three matrix coefficients with polynomial entries.

```
  PZ := UnivariatePolynomial(x,Integer)
    UnivariatePolynomial(x,Integer)
                            Type: Domain

  x:PZ := 'x
    x
                            Type: UnivariatePolynomial(x,Integer)

  Mat  := SquareMatrix(3,PZ)
    SquareMatrix(3,UnivariatePolynomial(x,Integer))
                            Type: Domain
```

The operators act on the vectors considered as a Mat-module.

```
  Vect := DPMM(3, PZ, Mat, PZ)
  DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),SquareMatrix(3,Un
  ivariatePolynomial(x,Integer)),UnivariatePolynomial(x,Integer))
                            Type: Domain

  Modo := LODO2(Mat, Vect)
  LinearOrdinaryDifferentialOperator2(SquareMatrix(3,UnivariatePolynomial(x,Int
  eger)),DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),SquareMatr
  ix(3,UnivariatePolynomial(x,Integer)),UnivariatePolynomial(x,Integer)))
                            Type: Domain
```

The matrix m is used as a coefficient and the vectors p and q are operated upon.

```
  m:Mat := matrix [ [x^2,1,0],[1,x^4,0],[0,0,4*x^2] ]
        + 2         +
        |x   1    0 |
        |           |
        |     4     |
        |1   x    0 |
        |           |
        |          2|
        +0   0   4x +
                          Type: SquareMatrix(3,UnivariatePolynomial(x,Integer))

  p:Vect := directProduct [3*x^2+1,2*x,7*x^3+2*x]
       2          3
    [3x  + 1,2x,7x  + 2x]
```

```
   Type: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
            SquareMatrix(3,UnivariatePolynomial(x,Integer)),
               UnivariatePolynomial(x,Integer))

  q: Vect := m * p
       4    2        5     2        5     3
    [3x  + x  + 2x,2x  + 3x  + 1,28x  + 8x ]
      Type: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
         SquareMatrix(3,UnivariatePolynomial(x,Integer)),
            UnivariatePolynomial(x,Integer))
```

Now form a few operators.

```
  Dx : Modo := D()
    D
      Type: LinearOrdinaryDifferentialOperator2(
             SquareMatrix(3,UnivariatePolynomial(x,Integer)),
             DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
             SquareMatrix(3,UnivariatePolynomial(x,Integer)),
             UnivariatePolynomial(x,Integer)))

  a : Modo := Dx  + m
              + 2         +
              |x   1    0 |
              |           |
         D + |     4     |
              |1   x    0 |
              |           |
              |          2|
              +0   0   4x +
    Type: LinearOrdinaryDifferentialOperator2(
              SquareMatrix(3,UnivariatePolynomial(x,Integer)),
              DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
              SquareMatrix(3,UnivariatePolynomial(x,Integer)),
              UnivariatePolynomial(x,Integer)))

  b : Modo := m*Dx  + 1
         + 2         +
         |x   1    0 |    +1  0  0+
         |           |    |       |
         |     4     |D + |0  1  0|
         |1   x    0 |    |       |
         |           |    +0  0  1+
         |          2|
         +0   0   4x +
     Type: LinearOrdinaryDifferentialOperator2(
              SquareMatrix(3,UnivariatePolynomial(x,Integer)),
              DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
              SquareMatrix(3,UnivariatePolynomial(x,Integer)),
              UnivariatePolynomial(x,Integer)))
```

```
  c := a*b
  + 2         +     + 4              4    2                  +    + 2          +
  |x   1    0 |     |x  + 2x + 2    x  + x            0      |    |x   1    0 |
  |           | 2   |                                       |    |           |
  |     4     |D  + |   4    2     8     3                  |D + |     4     |
  |1   x    0 |     |  x  + x     x  + 4x  + 2        0      |    |1   x    0 |
  |           |     |                                       |    |           |
  |          2|     |                              4        |    |          2|
  +0   0   4x +     +     0             0        16x  + 8x + 1+    +0   0   4x +
    Type: LinearOrdinaryDifferentialOperator2(
            SquareMatrix(3,UnivariatePolynomial(x,Integer)),
            DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
            SquareMatrix(3,UnivariatePolynomial(x,Integer)),
            UnivariatePolynomial(x,Integer)))

These operators can be applied to vector values.


  a p
        4    2        5     2        5     3      2
     [3x  + x  + 8x,2x  + 3x  + 3,28x  + 8x  + 21x  + 2]
       Type: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
               SquareMatrix(3,UnivariatePolynomial(x,Integer)),
                  UnivariatePolynomial(x,Integer))

  b p
        3     2       4         4     3     2
     [6x  + 3x  + 3,2x  + 8x,84x  + 7x  + 8x  + 2x]
        Type: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
                SquareMatrix(3,UnivariatePolynomial(x,Integer)),
                  UnivariatePolynomial(x,Integer))

  (a + b + c) (p + q)
       8      7      6      5      4      3      2
    [10x  + 12x  + 16x  + 30x  + 85x  + 94x  + 40x  + 40x + 17,
        12      9      8      7     6      5      4      3      2
     10x   + 10x  + 12x  + 92x  + 6x  + 32x  + 72x  + 28x  + 49x  + 32x + 19,
          8       7       6       5       4       3      2
     2240x  + 224x  + 1280x  + 3508x  + 492x  + 751x  + 98x  + 18x + 4]
      Type: DirectProductMatrixModule(3,UnivariatePolynomial(x,Integer),
              SquareMatrix(3,UnivariatePolynomial(x,Integer)),
                UnivariatePolynomial(x,Integer))

See Also:
o )show LinearOrdinaryDifferentialOperator2
```

13.8.1 LinearOrdinaryDifferentialOperator2 (LODO2)



See

⇒ "LinearOrdinaryDifferentialOperator" (LODO) 13.6.1 on page 1437
⇒ "LinearOrdinaryDifferentialOperator1" (LODO1) 13.7.1 on page 1447

Exports:

0	1	adjoint	apply
characteristic	coefficient	coefficients	coerce
content	D	degree	directSum
exquo	hash	latex	leadingCoefficient
leftDivide	leftExactQuotient	leftExtendedGcd	leftGcd
leftLcm	leftQuotient	leftRemainder	minimumDegree
monicLeftDivide	monicRightDivide	monomial	one?
primitivePart	recip	reductum	retract
retractIfCan	rightDivide	rightExactQuotient	rightExtendedGcd
rightGcd	rightLcm	rightQuotient	rightRemainder
sample	subtractIfCan	symmetricPower	symmetricProduct
symmetricSquare	zero?	?*?	?**?
?+?	?-?	-?	?=?
?^?	?.?	?~=?	

— domain LODO2 LinearOrdinaryDifferentialOperator2 —

```
)abbrev domain LODO2 LinearOrdinaryDifferentialOperator2
++ Author: Stephen M. Watt, Manuel Bronstein
++ Date Created: 1986
++ Date Last Updated: 1 February 1994
++ Keywords: differential operator
++ Description:
++ \spad{LinearOrdinaryDifferentialOperator2} defines a ring of
++ differential operators with coefficients in a differential ring A
++ and acting on an A-module M.
++ Multiplication of operators corresponds to functional composition:\br
++ \spad{(L1 * L2).(f) = L1 L2 f}

LinearOrdinaryDifferentialOperator2(A, M): Exports == Implementation where
```

```
  A: DifferentialRing
  M: LeftModule A with
      differentiate: $ -> $
        ++ differentiate(x) returns the derivative of x

  Exports ==> Join(LinearOrdinaryDifferentialOperatorCategory A, Eltable(M, M))

  Implementation ==> LinearOrdinaryDifferentialOperator(A, differentiate$A) add
      elt(p:%, m:M):M ==
        apply(p, differentiate, m)$ApplyUnivariateSkewPolynomial(A, M, %)
```

———-

— LODO2.dotabb —

```
"LODO2" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LODO2"]
"LODOCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=LODOCAT"]
"LODO2" -> "LODOCAT"
```

———-

13.9 domain LIST List

— List.input —

```
)set break resume
)sys rm -f List.output
)spool List.output
)set message test on
)set message auto off
)clear all
--S 1 of 34
[2, 4, 5, 6]
--R
--R
--R   (1)  [2,4,5,6]
--R                                                  Type: List(PositiveInteger)
--E 1

--S 2 of 34
[1]
--R
--R
--R   (2)  [1]
```

```
--R                                                    Type: List(PositiveInteger)
--E 2

--S 3 of 34
list(1)
--R
--R
--R   (3)  [1]
--R                                                    Type: List(PositiveInteger)
--E 3

--S 4 of 34
append([1,2,3],[5,6,7])
--R
--R
--R   (4)  [1,2,3,5,6,7]
--R                                                    Type: List(PositiveInteger)
--E 4

--S 5 of 34
cons(10,[9,8,7])
--R
--R
--R   (5)  [10,9,8,7]
--R                                                    Type: List(PositiveInteger)
--E 5

--S 6 of 34
empty? [x+1]
--R
--R
--R   (6)  false
--R                                                             Type: Boolean
--E 6

--S 7 of 34
([] = nil)@Boolean
--R
--R
--R   (7)  true
--R                                                             Type: Boolean
--E 7

--S 8 of 34
k := [4,3,7,3,8,5,9,2]
--R
--R
--R   (8)  [4,3,7,3,8,5,9,2]
--R                                                    Type: List(PositiveInteger)
--E 8
```

```
--S 9 of 34
first k
--R
--R
--R   (9)  4
--R                                                    Type: PositiveInteger
--E 9

--S 10 of 34
k.first
--R
--R
--R   (10)  4
--R                                                    Type: PositiveInteger
--E 10

--S 11 of 34
k.1
--R
--R
--R   (11)  4
--R                                                    Type: PositiveInteger
--E 11

--S 12 of 34
k(1)
--R
--R
--R   (12)  4
--R                                                    Type: PositiveInteger
--E 12

--S 13 of 34
n := #k
--R
--R
--R   (13)  8
--R                                                    Type: PositiveInteger
--E 13

--S 14 of 34
last k
--R
--R
--R   (14)  2
--R                                                    Type: PositiveInteger
--E 14

--S 15 of 34
```

```
k.last
--R
--R
--R   (15)  2
--R                                                    Type: PositiveInteger
--E 15

--S 16 of 34
k.(#k)
--R
--R
--R   (16)  2
--R                                                    Type: PositiveInteger
--E 16

--S 17 of 34
k := [4,3,7,3,8,5,9,2]
--R
--R
--R   (17)  [4,3,7,3,8,5,9,2]
--R                                          Type: List(PositiveInteger)
--E 17

--S 18 of 34
k.1 := 999
--R
--R
--R   (18)  999
--R                                                    Type: PositiveInteger
--E 18

--S 19 of 34
k
--R
--R
--R   (19)  [999,3,7,3,8,5,9,2]
--R                                          Type: List(PositiveInteger)
--E 19

--S 20 of 34
k := [1,2]
--R
--R
--R   (20)  [1,2]
--R                                          Type: List(PositiveInteger)
--E 20

--S 21 of 34
m := cons(0,k)
--R
```

```
--R
--R   (21)  [0,1,2]
--R                                                    Type: List(Integer)
--E 21

--S 22 of 34
m.2 := 99
--R
--R
--R   (22)  99
--R                                                 Type: PositiveInteger
--E 22

--S 23 of 34
m
--R
--R
--R   (23)  [0,99,2]
--R                                                    Type: List(Integer)
--E 23

--S 24 of 34
k
--R
--R
--R   (24)  [99,2]
--R                                                Type: List(PositiveInteger)
--E 24

--S 25 of 34
k := [1,2,3]
--R
--R
--R   (25)  [1,2,3]
--R                                                Type: List(PositiveInteger)
--E 25

--S 26 of 34
rest k
--R
--R
--R   (26)  [2,3]
--R                                                Type: List(PositiveInteger)
--E 26

--S 27 of 34
removeDuplicates [4,3,4,3,5,3,4]
--R
--R
--R   (27)  [4,3,5]
```

```
--R                                                   Type: List(PositiveInteger)
--E 27

--S 28 of 34
reverse [1,2,3,4,5,6]
--R
--R
--R   (28)  [6,5,4,3,2,1]
--R                                                   Type: List(PositiveInteger)
--E 28

--S 29 of 34
member?(1/2,[3/4,5/6,1/2])
--R
--R
--R   (29)  true
--R                                                            Type: Boolean
--E 29

--S 30 of 34
member?(1/12,[3/4,5/6,1/2])
--R
--R
--R   (30)  false
--R                                                            Type: Boolean
--E 30

--S 31 of 34
reverse(rest(reverse(k)))
--R
--R
--R   (31)  [1,2]
--R                                                   Type: List(PositiveInteger)
--E 31

--S 32 of 34
[1..3,10,20..23]
--R
--R
--R   (32)  [1..3,10..10,20..23]
--R                                      Type: List(Segment(PositiveInteger))
--E 32

--S 33 of 34
expand [1..3,10,20..23]
--R
--R
--R   (33)  [1,2,3,10,20,21,22,23]
--R                                                      Type: List(Integer)
--E 33
```

```
--S 34 of 34
expand [1..]
--R
--R
--R   (34)  [1,2,3,4,5,6,7,8,9,10,...]
--R                                                    Type: Stream(Integer)
--E 34
)spool
)lisp (bye)
```

———-

— List.help —

```
========================================================================
List examples
========================================================================

A list is a finite collection of elements in a specified order that
can contain duplicates.  A list is a convenient structure to work with
because it is easy to add or remove elements and the length need not
be constant.  There are many different kinds of lists in Axiom, but
the default types (and those used most often) are created by the List
constructor.  For example, there are objects of type List Integer,
List Float and List Polynomial Fraction Integer.  Indeed, you can even
have List List List Boolean (that is, lists of lists of lists of
Boolean values).  You can have lists of any type of Axiom object.

========================================================================
Creating Lists
========================================================================

The easiest way to create a list with, for example, the elements
2, 4, 5, 6 is to enclose the elements with square brackets and
separate the elements with commas.

The spaces after the commas are optional, but they do improve the
readability.

  [2, 4, 5, 6]
    [2,4,5,6]
                          Type: List PositiveInteger

To create a list with the single element 1, you can use either [1] or
the operation list.

  [1]
    [1]
```

```
                          Type: List PositiveInteger

  list(1)
    [1]
                          Type: List PositiveInteger

Once created, two lists k and m can be concatenated by issuing
append(k,m).  append does not physically join the lists, but rather
produces a new list with the elements coming from the two arguments.

  append([1,2,3],[5,6,7])
    [1,2,3,5,6,7]
                           Type: List PositiveInteger

Use cons to append an element onto the front of a list.

  cons(10,[9,8,7])
    [10,9,8,7]
                           Type: List PositiveInteger

========================================================================
Accessing List Elements
========================================================================

To determine whether a list has any elements, use the operation empty?.

  empty? [x+1]
    false
                           Type: Boolean

Alternatively, equality with the list constant nil can be tested.

  ([] = nil)@Boolean
    true
                           Type: Boolean

We'll use this in some of the following examples.

  k := [4,3,7,3,8,5,9,2]
    [4,3,7,3,8,5,9,2]
                           Type: List PositiveInteger

Each of the next four expressions extracts the first element of k.

  first k
    4
                           Type: PositiveInteger

  k.first
    4
```

```
                              Type: PositiveInteger

  k.1
    4
                              Type: PositiveInteger

  k(1)
    4
                              Type: PositiveInteger
```

The last two forms generalize to k.i and k(i), respectively, where 1 <= i <= n and n equals the length of k.

This length is calculated by #.

```
  n := #k
    8
                              Type: PositiveInteger
```

Performing an operation such as k.i is sometimes referred to as indexing into k or elting into k. The latter phrase comes about because the name of the operation that extracts elements is called elt. That is, k.3 is just alternative syntax for elt(k,3). It is important to remember that list indices begin with 1. If we issue k := [1,3,2,9,5] then k.4 returns 9. It is an error to use an index that is not in the range from 1 to the length of the list.

The last element of a list is extracted by any of the following three expressions.

```
  last k
    2
                                 Type: PositiveInteger

  k.last
    2
                                 Type: PositiveInteger
```

This form computes the index of the last element and then extracts the element from the list.

```
  k.(#k)
    2
                                 Type: PositiveInteger
```

```
=====================================================================
Changing List Elements
=====================================================================
```

We'll use this in some of the following examples.

```
  k := [4,3,7,3,8,5,9,2]
    [4,3,7,3,8,5,9,2]
                              Type: List PositiveInteger
```

List elements are reset by using the k.i form on the left-hand side of an assignment. This expression resets the first element of k to 999.

```
  k.1 := 999
    999
                              Type: PositiveInteger
```

As with indexing into a list, it is an error to use an index that is not within the proper bounds. Here you see that k was modified.

```
  k
    [999,3,7,3,8,5,9,2]
                              Type: List PositiveInteger
```

The operation that performs the assignment of an element to a particular position in a list is called setelt. This operation is destructive in that it changes the list. In the above example, the assignment returned the value 999 and k was modified. For this reason, lists are called mutable objects: it is possible to change part of a list (mutate it) rather than always returning a new list reflecting the intended modifications.

Moreover, since lists can share structure, changes to one list can sometimes affect others.

```
  k := [1,2]
    [1,2]
                               Type: List PositiveInteger

  m := cons(0,k)
    [0,1,2]
                               Type: List Integer
```

Change the second element of m.

```
  m.2 := 99
    99
                               Type: PositiveInteger
```

See, m was altered.

```
  m
    [0,99,2]
                               Type: List Integer
```

```
But what about k?  It changed too!

  k
    [99,2]
                                Type: List PositiveInteger

========================================================================
Other Functions
========================================================================

An operation that is used frequently in list processing is that
which returns all elements in a list after the first element.

  k := [1,2,3]
    [1,2,3]
                                Type: List PositiveInteger

Use the rest operation to do this.

  rest k
    [2,3]
                                Type: List PositiveInteger

To remove duplicate elements in a list k, use removeDuplicates.

  removeDuplicates [4,3,4,3,5,3,4]
    [4,3,5]
                                Type: List PositiveInteger

To get a list with elements in the order opposite to those in a list
k, use reverse.

  reverse [1,2,3,4,5,6]
    [6,5,4,3,2,1]
                                Type: List PositiveInteger

To test whether an element is in a list, use member?: member?(a,k)
returns true or false depending on whether a is in k or not.

  member?(1/2,[3/4,5/6,1/2])
    true
                                Type: Boolean

  member?(1/12,[3/4,5/6,1/2])
    false
                                Type: Boolean

We can get a list containing all but the last of the elements in a
given non-empty list k.
```

```
  reverse(rest(reverse(k)))
    [1,2]
                              Type: List PositiveInteger

========================================================================
Dot, Dot
========================================================================

Certain lists are used so often that Axiom provides an easy way of
constructing them.  If n and m are integers, then expand [n..m]
creates a list containing n, n+1, ... m.  If n > m then the list is
empty.  It is actually permissible to leave off the m in the dot-dot
construction (see below).

The dot-dot notation can be used more than once in a list construction
and with specific elements being given.  Items separated by dots are
called segments.

  [1..3,10,20..23]
    [1..3,10..10,20..23]
                              Type: List Segment PositiveInteger

Segments can be expanded into the range of items between the endpoints
by using expand.

  expand [1..3,10,20..23]
    [1,2,3,10,20,21,22,23]
                              Type: List Integer


What happens if we leave off a number on the right-hand side of ..?

  expand [1..]
    [1,2,3,4,5,6,7,8,9,10,...]
                              Type: Stream Integer

What is created in this case is a Stream which is a generalization of
a list.

See Also:
o )help Stream
o )show List
```

13.9.1 List (LIST)



See

⇒ "IndexedList" (ILIST) 10.11.1 on page 1200
⇒ "AssociationList" (ALIST) 2.42.1 on page 220

Exports:

any?	append	child?	children	coerce
concat	concat!	cons	construct	convert
copy	copyInto!	count	cycleEntry	cycleLength
cycleSplit!	cycleTail	cyclic?	delete	delete!
distance	elt	empty	empty?	entries
entry?	eq?	eval	every?	explicitlyFinite?
fill!	find	first	hash	index?
indices	insert	insert!	last	latex
leaf?	leaves	less?	list	map
map!	max	maxIndex	member?	members
merge	merge!	min	minIndex	more?
node?	new	nil	nodes	null
OMwrite	parts	position	possiblyInfinite?	qelt
qsetelt!	reduce	remove	remove!	removeDuplicates
removeDuplicates!	rest	reverse	reverse!	sample
second	select	select!	setDifference	setIntersection
setUnion	setchildren!	setelt	setfirst!	setlast!
setrest!	setvalue!	size?	sort	sort!
sorted?	split!	swap!	tail	third
value	#?	?<?	?<=?	?=?
?>?	?>=?	?.?	?~=?	?.?
?.last	?.rest	?.first	?.value	

— domain LIST List —

```
)abbrev domain LIST List
++ Author: Michael Monagan
++ Date Created: Sep 1987
++ Change History:
```

```
++ Related Constructors: ListFunctions2, ListFunctions3, ListToMap
++ Also See: IndexList, ListAggregate
++ AMS Classification:
++ Keywords: list, index, aggregate, lisp
++ Description:
++ \spadtype{List} implements singly-linked lists that are
++ addressable by indices; the index of the first element
++ is 1. In addition to the operations provided by
++ \spadtype{IndexedList}, this constructor provides some
++ LISP-like functions such as \spadfun{null} and \spadfun{cons}.

List(S:Type): Exports == Implementation where
 LISTMININDEX ==> 1       -- this is the minimum list index

 Exports ==> ListAggregate S with
  nil             : ()     -> %
    ++ nil() returns the empty list.
  null            : %      -> Boolean
    ++ null(u) tests if list \spad{u} is the
    ++ empty list.
  cons            : (S, %) -> %
    ++ cons(element,u) appends \spad{element} onto the front
    ++ of list \spad{u} and returns the new list. This new list
    ++ and the old one will share some structure.
  append          : (%, %) -> %
    ++ append(u1,u2) appends the elements of list \spad{u1}
    ++ onto the front of list \spad{u2}. This new list
    ++ and \spad{u2} will share some structure.
  if S has SetCategory then
    setUnion        : (%, %) -> %
      ++ setUnion(u1,u2) appends the two lists u1 and u2, then
      ++ removes all duplicates. The order of elements in the
      ++ resulting list is unspecified.
    setIntersection : (%, %) -> %
      ++ setIntersection(u1,u2) returns a list of the elements
      ++ that lists \spad{u1} and \spad{u2} have in common.
      ++ The order of elements in the resulting list is unspecified.
    setDifference   : (%, %) -> %
      ++ setDifference(u1,u2) returns a list of the elements
      ++ of \spad{u1} that are not also in \spad{u2}.
      ++ The order of elements in the resulting list is unspecified.
  if S has OpenMath then OpenMath

 Implementation ==>
   IndexedList(S, LISTMININDEX) add
      nil()                   == NIL$Lisp
      null l                  == NULL(l)$Lisp
      cons(s, l)              == CONS(s, l)$Lisp
      append(l:%, t:%)        == APPEND(l, t)$Lisp
```

```
if S has OpenMath then
  writeOMList(dev: OpenMathDevice, x: %): Void ==
    OMputApp(dev)
    OMputSymbol(dev, "list1", "list")
    -- The following didn't compile because the compiler isn't
    -- convinced that 'xval' is a S.  Duhhh! MCD.
    --for xval in x repeat
    --  OMwrite(dev, xval, false)
    while not null x repeat
      OMwrite(dev,first x,false)
      x := rest x
    OMputEndApp(dev)

  OMwrite(x: %): String ==
    s: String := ""
    sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
    dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
    OMputObject(dev)
    writeOMList(dev, x)
    OMputEndObject(dev)
    OMclose(dev)
    s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
    s

  OMwrite(x: %, wholeObj: Boolean): String ==
    s: String := ""
    sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
    dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
    if wholeObj then
      OMputObject(dev)
    writeOMList(dev, x)
    if wholeObj then
      OMputEndObject(dev)
    OMclose(dev)
    s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
    s

  OMwrite(dev: OpenMathDevice, x: %): Void ==
    OMputObject(dev)
    writeOMList(dev, x)
    OMputEndObject(dev)

  OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
    if wholeObj then
      OMputObject(dev)
    writeOMList(dev, x)
    if wholeObj then
      OMputEndObject(dev)

if S has SetCategory then
```

```
        setUnion(l1:%,l2:%)      == removeDuplicates concat(l1,l2)

        setIntersection(l1:%,l2:%) ==
          u :% := empty()
          l1 := removeDuplicates l1
          while not empty? l1 repeat
            if member?(first l1,l2) then u := cons(first l1,u)
            l1 := rest l1
          u

        setDifference(l1:%,l2:%) ==
          l1 := removeDuplicates l1
          lu:% := empty()
          while not empty? l1 repeat
            l11:=l1.1
            if not member?(l11,l2) then lu := concat(l11,lu)
            l1 := rest l1
          lu

      if S has ConvertibleTo InputForm then
        convert(x:%):InputForm ==
          convert concat(convert("construct"::Symbol)@InputForm,
                [convert a for a in (x pretend List S)]$List(InputForm))
```

———-

— **LIST.dotabb** —

```
"LIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LIST",
          shape=ellipse]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"LIST" -> "ALIST"
```

———-

13.10 domain LMOPS ListMonoidOps

— **ListMonoidOps.input** —

```
)set break resume
)sys rm -f ListMonoidOps.output
)spool ListMonoidOps.output
)set message test on
)set message auto off
```

```
)clear all

--S 1 of 1
)show ListMonoidOps
--R
--R ListMonoidOps(S: SetCategory,E: AbelianMonoid,un: E)  is a domain constructor
--R Abbreviation for ListMonoidOps is LMOPS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LMOPS
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : S -> %
--R coerce : % -> OutputForm             hash : % -> SingleInteger
--R latex : % -> String                  leftMult : (S,%) -> %
--R makeTerm : (S,E) -> %                makeUnit : () -> %
--R mapExpon : ((E -> E),%) -> %         mapGen : ((S -> S),%) -> %
--R nthExpon : (%,Integer) -> E          nthFactor : (%,Integer) -> S
--R plus : (%,%) -> %                    plus : (S,E,%) -> %
--R retract : % -> S                     reverse : % -> %
--R reverse! : % -> %                    rightMult : (%,S) -> %
--R size : % -> NonNegativeInteger       ?~=? : (%,%) -> Boolean
--R commutativeEquality : (%,%) -> Boolean
--R listOfMonoms : % -> List(Record(gen: S,exp: E))
--R makeMulti : List(Record(gen: S,exp: E)) -> %
--R outputForm : (%,((OutputForm,OutputForm) -> OutputForm),((OutputForm,OutputForm) -> OutputFo
--R retractIfCan : % -> Union(S,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— ListMonoidOps.help —

```
=====================================================================
ListMonoidOps examples
=====================================================================

See Also:
o )show ListMonoidOps
```

———-

13.10.1 ListMonoidOps (LMOPS)



See

⇒ “FreeMonoid” (FMONOID) 7.32.1 on page 991
⇒ “FreeGroup” (FGROUP) 7.29.1 on page 980
⇒ “InnerFreeAbelianMonoid” (IFAMON) 10.22.1 on page 1254
⇒ “FreeAbelianMonoid” (FAMONOID) 7.28.1 on page 977
⇒ “FreeAbelianGroup” (FAGROUP) 7.27.1 on page 974

Exports:

coerce	commutativeEquality	hash	latex	leftMult
listOfMonoms	makeTerm	makeUnit	mapExpon	mapGen
makeMulti	nthExpon	nthFactor	outputForm	plus
retract	retractIfCan	reverse	reverse!	rightMult
size	?=?	?~=?		

— domain LMOPS ListMonoidOps —

```
)abbrev domain LMOPS ListMonoidOps
++ Author: Manuel Bronstein
++ Date Created: November 1989
++ Date Last Updated: 6 June 1991
++ Description:
++ This internal package represents monoid (abelian or not, with or
++ without inverses) as lists and provides some common operations
++ to the various flavors of monoids.

ListMonoidOps(S, E, un): Exports == Implementation where
  S : SetCategory
  E : AbelianMonoid
  un: E

  REC ==> Record(gen:S, exp: E)
  O   ==> OutputForm

  Exports ==> Join(SetCategory, RetractableTo S) with
    outputForm    : ($, (O, O) -> O, (O, O) -> O, Integer) -> O
```

```
    ++ outputForm(l, fop, fexp, unit) converts the monoid element
    ++ represented by l to an \spadtype{OutputForm}.
    ++ Argument unit is the output form
    ++ for the \spadignore{unit} of the monoid (e.g. 0 or 1),
    ++ \spad{fop(a, b)} is the
    ++ output form for the monoid operation applied to \spad{a} and b
    ++ (e.g. \spad{a + b}, \spad{a * b}, \spad{ab}),
    ++ and \spad{fexp(a, n)} is the output form
    ++ for the exponentiation operation applied to \spad{a} and n
    ++ (e.g. \spad{n a}, \spad{n * a}, \spad{a ** n}, \spad{a\^n}).
  listOfMonoms  : $ -> List REC
    ++ listOfMonoms(l) returns the list of the monomials forming l.
  makeTerm      : (S, E) -> $
    ++ makeTerm(s, e) returns the monomial s exponentiated by e
    ++ (e.g. s^e or e * s).
  makeMulti     : List REC -> $
    ++ makeMulti(l) returns the element whose list of monomials is l.
  nthExpon      : ($, Integer) -> E
    ++ nthExpon(l, n) returns the exponent of the n^th monomial of l.
  nthFactor     : ($, Integer) -> S
    ++ nthFactor(l, n) returns the factor of the n^th monomial of l.
  reverse       : $ -> $
    ++ reverse(l) reverses the list of monomials forming l. This
    ++ has some effect if the monoid is non-abelian, i.e.
    ++ \spad{reverse(a1\^e1 ... an\^en) = an\^en ... a1\^e1} which is different.
  reverse_!     : $ -> $
    ++ reverse!(l) reverses the list of monomials forming l, destroying
    ++ the element l.
  size          : $ -> NonNegativeInteger
    ++ size(l) returns the number of monomials forming l.
  makeUnit      : () -> $
    ++ makeUnit() returns the unit element of the monomial.
  rightMult     : ($, S) -> $
    ++ rightMult(a, s) returns \spad{a * s} where \spad{*}
    ++ is the monoid operation,
    ++ which is assumed non-commutative.
  leftMult      : (S, $) -> $
    ++ leftMult(s, a) returns \spad{s * a} where
    ++ \spad{*} is the monoid operation,
    ++ which is assumed non-commutative.
  plus          : (S, E, $) -> $
    ++ plus(s, e, x) returns \spad{e * s + x} where \spad{+}
    ++ is the monoid operation,
    ++ which is assumed commutative.
  plus          : ($, $) -> $
    ++ plus(x, y) returns \spad{x + y} where \spad{+}
    ++ is the monoid operation,
    ++ which is assumed commutative.
  commutativeEquality: ($, $) -> Boolean
    ++ commutativeEquality(x,y) returns true if x and y are equal
```

```
    ++ assuming commutativity
  mapExpon      : (E -> E, $) -> $
    ++ mapExpon(f, a1\^e1 ... an\^en) returns \spad{a1\^f(e1) ... an\^f(en)}.
  mapGen        : (S -> S, $) -> $
    ++ mapGen(f, a1\^e1 ... an\^en) returns \spad{f(a1)\^e1 ... f(an)\^en}.

Implementation ==> add
  Rep := List REC

  localplus: ($, $) -> $

  makeUnit()       == empty()$Rep
  size l           == # listOfMonoms l
  coerce(s:S):$    == [[s, un]]
  coerce(l:$):O    == coerce(l)$Rep
  makeTerm(s, e)   == (zero? e => makeUnit(); [[s, e]])
  makeMulti l      == l
  f = g            == f =$Rep g
  listOfMonoms l   == l pretend List(REC)
  nthExpon(f, i)   == f.(i-1+minIndex f).exp
  nthFactor(f, i)  == f.(i-1+minIndex f).gen
  reverse l        == reverse(l)$Rep
  reverse_! l      == reverse_!(l)$Rep
  mapGen(f, l)     == [[f(x.gen), x.exp] for x in l]

  mapExpon(f, l) ==
    ans:List(REC) := empty()
    for x in l repeat
      if (a := f(x.exp)) ^= 0 then ans := concat([x.gen, a], ans)
    reverse_! ans

  outputForm(l, op, opexp, id) ==
    empty? l => id::OutputForm
    l:List(O) :=
       [(p.exp = un => p.gen::O; opexp(p.gen::O, p.exp::O)) for p in l]
    reduce(op, l)

  retractIfCan(l:$):Union(S, "failed") ==
    not empty? l and empty? rest l and l.first.exp = un => l.first.gen
    "failed"

  rightMult(f, s) ==
    empty? f => s::$
    s = f.last.gen => (setlast_!(h := copy f, [s, f.last.exp + un]); h)
    concat(f, [s, un])

  leftMult(s, f) ==
    empty? f => s::$
    s = f.first.gen => concat([s, f.first.exp + un], rest f)
    concat([s, un], f)
```

```
    commutativeEquality(s1:$, s2:$):Boolean ==
      #s1 ^= #s2 => false
      for t1 in s1 repeat
          if not member?(t1,s2) then return false
      true

    plus_!(s:S, n:E, f:$):$ ==
      h := g := concat([s, n], f)
      h1 := rest h
      while not empty? h1 repeat
        s = h1.first.gen =>
          l :=
            zero?(m := n + h1.first.exp) => rest h1
            concat([s, m], rest h1)
          setrest_!(h, l)
          return rest g
        h := h1
        h1 := rest h1
      g

    plus(s, n, f) == plus_!(s,n,copy f)

    plus(f, g) ==
      #f < #g => localplus(f, g)
      localplus(g, f)

    localplus(f, g) ==
      g := copy g
      for x in f repeat
        g := plus(x.gen, x.exp, g)
      g
```

———-

— LMOPS.dotabb —

```
"LMOPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LMOPS"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"LMOPS" -> "FLAGG"
"LMOPS" -> "FLAGG-"
```

———-

13.11 domain LMDICT ListMultiDictionary

— ListMultiDictionary.input —

```
)set break resume
)sys rm -f ListMultiDictionary.output
)spool ListMultiDictionary.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ListMultiDictionary
--R
--R ListMultiDictionary(S: SetCategory)  is a domain constructor
--R Abbreviation for ListMultiDictionary is LMDICT
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LMDICT
--R
--R------------------------------ Operations --------------------------------
--R bag : List(S) -> %                    construct : List(S) -> %
--R copy : % -> %                         dictionary : List(S) -> %
--R dictionary : () -> %                  duplicates? : % -> Boolean
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                extract! : % -> S
--R insert! : (S,%) -> %                  inspect : % -> S
--R map : ((S -> S),%) -> %               removeDuplicates! : % -> %
--R sample : () -> %                     substitute : (S,S,%) -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R convert : % -> InputForm if S has KONVERT(INFORM)
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R duplicates : % -> List(Record(entry: S,count: NonNegativeInteger))
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R find : ((S -> Boolean),%) -> Union(S,"failed")
--R hash : % -> SingleInteger if S has SETCAT
--R insert! : (S,%,NonNegativeInteger) -> %
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
```

```
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R reduce : (((S,S) -> S),%) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S,S) -> S if $ has finiteAggregate and S has SETCAT
--R remove : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (S,%) -> % if $ has finiteAggregate and S has SETCAT
--R remove! : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : (S,%) -> % if $ has finiteAggregate
--R removeDuplicates : % -> % if $ has finiteAggregate and S has SETCAT
--R select : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— ListMultiDictionary.help —

```
=====================================================================
ListMultiDictionary examples
=====================================================================

See Also:
o )show ListMultiDictionary
```

———-

13.11.1 ListMultiDictionary (LMDICT)



Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	dictionary	duplicates
duplicates?	empty	empty?	eq?	eval
extract!	every?	find	hash	insert!
inspect	latex	less?	map	map!
member?	members	more?	parts	reduce
remove	remove!	removeDuplicates	removeDuplicates!	sample
select	select!	size?	substitute	#?
?~=?	?=?			

— domain LMDICT ListMultiDictionary —

```
)abbrev domain LMDICT ListMultiDictionary
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated: 13 June 1994 Frederic Lehobey
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ The \spadtype{ListMultiDictionary} domain implements a
++ dictionary with duplicates
++ allowed.  The representation is a list with duplicates represented
++ explicitly.  Hence most operations will be relatively inefficient
++ when the number of entries in the dictionary becomes large.
++ If the objects in the dictionary belong to an ordered set,
++ the entries are maintained in ascending order.

ListMultiDictionary(S:SetCategory): EE == II where

 NNI ==> NonNegativeInteger
```

```
D ==> Record(entry:S, count:NonNegativeInteger)

EE ==> MultiDictionary(S) with
  finiteAggregate
  duplicates?: % -> Boolean
    ++ duplicates?(d) tests if dictionary d has duplicate entries.
  substitute : (S, S, %) -> %
    ++ substitute(x,y,d) replace x's with y's in dictionary d.
II ==> add
  Rep := Reference List S

  sub: (S, S, S) -> S

  coerce(s:%):OutputForm ==
    prefix("dictionary"::OutputForm, [x::OutputForm for x in parts s])

  #s                 == # parts s
  copy s             == dictionary copy parts s
  empty? s           == empty? parts s
  bag l              == dictionary l
  dictionary()       == dictionary empty()

  empty():% == ref empty()

  dictionary(ls:List S):% ==
    empty? ls => empty()
    lmd := empty()
    for x in ls repeat insert_!(x,lmd)
    lmd

  if S has ConvertibleTo InputForm then
    convert(lmd:%):InputForm ==
      convert [convert("dictionary"::Symbol)@InputForm,
       convert(parts lmd)@InputForm]

  map(f, s)          == dictionary map(f, parts s)
  map_!(f, s)        == dictionary map_!(f, parts s)
  parts s            == deref s
  sub(x, y, z)       == (z = x => y; z)
  insert_!(x, s, n)  == (for i in 1..n repeat insert_!(x, s); s)
  substitute(x, y, s) == dictionary map(z1 +-> sub(x, y, z1), parts s)
  removeDuplicates_! s == dictionary removeDuplicates_! parts s

  inspect s ==
    empty? s => error "empty dictionary"
    first parts s

  extract_! s ==
    empty? s => error "empty dictionary"
    x := first(p := parts s)
```

```
    setref(s, rest p)
    x

  duplicates? s ==
    empty?(p := parts s) => false
    q := rest p
    while not empty? q repeat
      first p = first q => return true
      p := q
      q := rest q
    false

  remove_!(p: S->Boolean, lmd:%):% ==
    for x in removeDuplicates parts lmd | p(x) repeat remove_!(x,lmd)
    lmd

  select_!(p: S->Boolean, lmd:%):% == remove_!((z:S):Boolean+->not p(z), lmd)

  duplicates(lmd:%):List D ==
    ld: List D := empty()
    for x in removeDuplicates parts lmd | (n := count(x, lmd)) >
     1$NonNegativeInteger repeat
      ld := cons([x, n], ld)
    ld

  if S has OrderedSet then
     s = t == parts s = parts t

     remove_!(x:S, s:%) ==
        p := deref s
        while not empty? p and x = first p repeat p := rest p
        setref(s, p)
        empty? p => s
        q := rest p
        while not empty? q and x > first q repeat (p := q; q := rest q)
        while not empty? q and x = first q repeat q := rest q
        p.rest := q
        s

     insert_!(x, s) ==
        p := deref s
        empty? p or x < first p =>
           setref(s, concat(x, p))
           s
        q := rest p
        while not empty? q and x > first q repeat (p := q; q := rest q)
        p.rest := concat(x, q)
        s

  else
```

```
      remove_!(x:S, s:%) == (setref(s, remove_!(x, parts s)); s)

      s = t ==
         a := copy s
         while not empty? a repeat
            x := inspect a
            count(x, s) ^= count(x, t) => return false
            remove_!(x, a)
         true

      insert_!(x, s) ==
         p := deref s
         while not empty? p repeat
            x = first p =>
               p.rest := concat(x, rest p)
               s
            p := rest p
         setref(s, concat(x, deref s))
         s
```

———-

— LMDICT.dotabb —

```
"LMDICT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LMDICT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"LMDICT" -> "ALIST"
```

———-

13.12 domain LA LocalAlgebra

— LocalAlgebra.input —

```
)set break resume
)sys rm -f LocalAlgebra.output
)spool LocalAlgebra.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show LocalAlgebra
--R
```

```
--R LocalAlgebra(A: Algebra(R),R: CommutativeRing,S: SubsetCategory(Monoid,R))  is a domain constructor
--R Abbreviation for LocalAlgebra is LA
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LA
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?/? : (A,S) -> %
--R ?/? : (%,S) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R denom : % -> S                        hash : % -> SingleInteger
--R latex : % -> String                   numer : % -> A
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?<? : (%,%) -> Boolean if A has ORDRING
--R ?<=? : (%,%) -> Boolean if A has ORDRING
--R ?>? : (%,%) -> Boolean if A has ORDRING
--R ?>=? : (%,%) -> Boolean if A has ORDRING
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if A has ORDRING
--R characteristic : () -> NonNegativeInteger
--R max : (%,%) -> % if A has ORDRING
--R min : (%,%) -> % if A has ORDRING
--R negative? : % -> Boolean if A has ORDRING
--R positive? : % -> Boolean if A has ORDRING
--R sign : % -> Integer if A has ORDRING
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```


———-

— LocalAlgebra.help —

```
====================================================================
LocalAlgebra examples
====================================================================
```

```
See Also:
o )show LocalAlgebra
```

13.12.1 LocalAlgebra (LA)



See

⇒ “Localize” (LO) 13.13.1 on page 1491
⇒ “Fraction” (FRAC) 7.24.1 on page 956

Exports:

0	1	abs	characteristic	coerce
denom	hash	latex	max	min
negative?	numer	one?	positive?	recip
sample	sign	subtractIfCan	zero?	?~=?
?*?	?**?	?<?	?<=?	?>?
?>=?	?^?	?+?	?-?	-?
?/?	?=?			

— domain LA LocalAlgebra —

```
)abbrev domain LA LocalAlgebra
++ Author: Dave Barton, Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ LocalAlgebra produces the localization of an algebra, i.e.
++ fractions whose numerators come from some R algebra.
```

```
LocalAlgebra(A: Algebra R,
             R: CommutativeRing,
             S: SubsetCategory(Monoid, R)): Algebra R with
          if A has OrderedRing then OrderedRing
          _/ : (%,S) -> %
            ++ x / d divides the element x by d.
          _/ : (A,S) -> %
            ++ a / d divides the element \spad{a} by d.
          numer: % -> A
            ++ numer x returns the numerator of x.
          denom: % -> S
            ++ denom x returns the denominator of x.
 == Localize(A, R, S) add
        1 == 1$A / 1$S
        x:% * y:% == (numer(x) * numer(y)) / (denom(x) * denom(y))
        characteristic() == characteristic()$A
```

———-

— LA.dotabb —

```
"LA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LA"]
"OAGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAGROUP"]
"LA" -> "OAGROUP"
```

———-

13.13 domain LO Localize

— Localize.input —

```
)set break resume
)sys rm -f Localize.output
)spool Localize.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Localize
--R
--R Localize(M: Module(R),R: CommutativeRing,S: SubsetCategory(Monoid,R))  is a domain constructor
--R Abbreviation for Localize is LO
```

```
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for LO
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?/? : (M,S) -> %
--R ?/? : (%,S) -> %                      ?=? : (%,%) -> Boolean
--R 0 : () -> %                           coerce : % -> OutputForm
--R denom : % -> S                        hash : % -> SingleInteger
--R latex : % -> String                   numer : % -> M
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?<? : (%,%) -> Boolean if M has OAGROUP
--R ?<=? : (%,%) -> Boolean if M has OAGROUP
--R ?>? : (%,%) -> Boolean if M has OAGROUP
--R ?>=? : (%,%) -> Boolean if M has OAGROUP
--R max : (%,%) -> % if M has OAGROUP
--R min : (%,%) -> % if M has OAGROUP
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— Localize.help —

```
=====================================================================
Localize examples
=====================================================================

See Also:
o )show Localize
```

———-

13.13.1 Localize (LO)



See

⇒ "LocalAlgebra" (LA) 13.12.1 on page 1488
⇒ "Fraction" (FRAC) 7.24.1 on page 956

Exports:

0	coerce	denom	hash	latex
max	min	numer	sample	subtractIfCan
zero?	?~=?	?*?	?<?	?<=?
?>?	?>=?	?+?	?-?	-?
?/?	?=?			

— domain LO Localize —

```
)abbrev domain LO Localize
++ Author: Dave Barton, Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: + - / numer denom
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: localization
++ References:
++ Description:
++ Localize(M,R,S) produces fractions with numerators
++ from an R module M and denominators from some multiplicative subset D of R.

Localize(M:Module R,
         R:CommutativeRing,
         S:SubsetCategory(Monoid, R)): Module R with
      if M has OrderedAbelianGroup then OrderedAbelianGroup
      _/ :(%,S) -> %
         ++ x / d divides the element x by d.
      _/ :(M,S) -> %
         ++ m / d divides the element m by d.
      numer: % -> M
```

```
        ++ numer x returns the numerator of x.
      denom: % -> S
        ++ denom x returns the denominator of x.
 ==
  add
    --representation
      Rep:= Record(num:M,den:S)
    --declarations
      x,y: %
      n: Integer
      m: M
      r: R
      d: S
    --definitions
      0 == [0,1]
      zero? x == zero? (x.num)
      -x== [-x.num,x.den]
      x=y == y.den*x.num = x.den*y.num
      numer x == x.num
      denom x == x.den
      if M has OrderedAbelianGroup then
        x < y ==
--              if y.den::R < 0 then (x,y):=(y,x)
--              if x.den::R < 0 then (x,y):=(y,x)
             y.den*x.num < x.den*y.num
      x+y == [y.den*x.num+x.den*y.num, x.den*y.den]
      n*x == [n*x.num,x.den]
      r*x == if r=x.den then [x.num,1] else [r*x.num,x.den]
      x/d ==
        zero?(u:S:=d*x.den) => error "division by zero"
        [x.num,u]
      m/d == if zero? d then error "division by zero" else [m,d]
      coerce(x:%):OutputForm ==
--        one?(xd:=x.den) => (x.num)::OutputForm
        ((xd:=x.den) = 1) => (x.num)::OutputForm
        (x.num)::OutputForm / (xd::OutputForm)
      latex(x:%): String ==
--        one?(xd:=x.den) => latex(x.num)
        ((xd:=x.den) = 1) => latex(x.num)
        nl : String := concat("{", concat(latex(x.num), "}")$String)$String
        dl : String := concat("{", concat(latex(x.den), "}")$String)$String
        concat("{ ", concat(nl, concat(" \over ", concat(dl, " }")$String)$String)$String)$Strin
```

———-

— LO.dotabb —

```
"LO" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LO"]
```

```
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"LO" -> "STRING"
```

———-

13.14 domain LWORD LyndonWord

— LyndonWord.input —

```
)set break resume
)sys rm -f LyndonWord.output
)spool LyndonWord.output
)set message test on
)set message auto off
)clear all
--S 1 of 22
a:Symbol :='a
--R
--R
--R   (1)  a
--R                                                    Type: Symbol
--E 1

--S 2 of 22
b:Symbol :='b
--R
--R
--R   (2)  b
--R                                                    Type: Symbol
--E 2

--S 3 of 22
c:Symbol :='c
--R
--R
--R   (3)  c
--R                                                    Type: Symbol
--E 3

--S 4 of 22
lword:= LyndonWord(Symbol)
--R
--R
--R   (4)  LyndonWord(Symbol)
--R                                                    Type: Domain
--E 4
```

```
--S 5 of 22
magma := Magma(Symbol)
--R
--R
--R   (5)  Magma(Symbol)
--R                                                                Type: Domain
--E 5

--S 6 of 22
word := OrderedFreeMonoid(Symbol)
--R
--R
--R   (6)  OrderedFreeMonoid(Symbol)
--R                                                                Type: Domain
--E 6

--S 7 of 22
LyndonWordsList1([a,b,c],3)$lword
--R
--R
--R   (7)
--R   [[[a],[b],[c]], [[a b],[a c],[b c]],
--R       2     2       2                    2    2       2
--R    [[a b],[a c],[a b ],[a b c],[a c b],[a c ],[b c],[b c ]]]
--R                          Type: OneDimensionalArray(List(LyndonWord(Symbol)))
--E 7

--S 8 of 22
LyndonWordsList([a,b,c],3)$lword
--R
--R
--R   (8)
--R                                          2      2        2
--R   [[a], [b], [c], [a b], [a c], [b c], [a b], [a c], [a b ], [a b c], [a c b],
--R        2     2        2
--R    [a c ], [b c], [b c ]]
--R                                                Type: List(LyndonWord(Symbol))
--E 8

--S 9 of 22
lw := LyndonWordsList([a,b],5)$lword
--R
--R
--R   (9)
--R                       2        2     3      2 2       3     4      3 2
--R   [[a], [b], [a b], [a b], [a b ], [a b], [a b ], [a b ], [a b], [a b ],
--R      2          2 3           2       4
--R    [a b a b], [a b ], [a b a b ], [a b ]]
--R                                                Type: List(LyndonWord(Symbol))
```

```
--E 9

--S 10 of 22
w1 : word := lw.4 :: word
--R
--R
--R          2
--R   (10)  a b
--R                                              Type: OrderedFreeMonoid(Symbol)
--E 10

--S 11 of 22
w2 : word := lw.5 :: word
--R
--R
--R            2
--R   (11)  a b
--R                                              Type: OrderedFreeMonoid(Symbol)
--E 11

--S 12 of 22
factor(a::word)$lword
--R
--R
--R   (12)  [[a]]
--R                                               Type: List(LyndonWord(Symbol))
--E 12

--S 13 of 22
factor(w1*w2)$lword
--R
--R
--R            2     2
--R   (13)  [[a b a b ]]
--R                                               Type: List(LyndonWord(Symbol))
--E 13

--S 14 of 22
factor(w2*w2)$lword
--R
--R
--R              2      2
--R   (14)  [[a b ],[a b ]]
--R                                               Type: List(LyndonWord(Symbol))
--E 14

--S 15 of 22
factor(w2*w1)$lword
--R
--R
```

```
--R              2    2
--R   (15)  [[a b ],[a b]]
--R                                                Type: List(LyndonWord(Symbol))
--E 15

--S 16 of 22
lyndon?(w1)$lword
--R
--R
--R   (16)  true
--R                                                                   Type: Boolean
--E 16

--S 17 of 22
lyndon?(w1*w2)$lword
--R
--R
--R   (17)  true
--R                                                                   Type: Boolean
--E 17

--S 18 of 22
lyndon?(w2*w1)$lword
--R
--R
--R   (18)  false
--R                                                                   Type: Boolean
--E 18

--S 19 of 22
lyndonIfCan(w1)$lword
--R
--R
--R           2
--R   (19)  [a b]
--R                                          Type: Union(LyndonWord(Symbol),...)
--E 19

--S 20 of 22
lyndonIfCan(w2*w1)$lword
--R
--R
--R   (20)  "failed"
--R                                               Type: Union("failed",...)
--E 20

--S 21 of 22
lyndon(w1)$lword
--R
--R
```

```
--R           2
--R   (21)  [a b]
--R                                                    Type: LyndonWord(Symbol)
--E 21

--S 22 of 22
lyndon(w1*w2)$lword
--R
--R
--R           2     2
--R   (22)  [a b a b ]
--R                                                    Type: LyndonWord(Symbol)
--E 22
)spool
)lisp (bye)
```

———-

— LyndonWord.help —

```
====================================================================
LyndonWord examples
====================================================================

A function f in [0,1] is called acyclic if C(F) consists of n
different objects. The canonical representative of the orbit of an
acyclic function is usually called a Lyndon Word. If f is acyclic,
then all elements in the orbit C(f) are acyclic as well, and we call
C(f) an acyclic orbit.

====================================================================
Initialisations
====================================================================

  a:Symbol :='a
    a
                              Type: Symbol

  b:Symbol :='b
    b
                              Type: Symbol

  c:Symbol :='c
    c
                              Type: Symbol

  lword:= LyndonWord(Symbol)
    LyndonWord Symbol
                              Type: Domain
```

```
  magma := Magma(Symbol)
    Magma Symbol
                              Type: Domain

  word := OrderedFreeMonoid(Symbol)
    OrderedFreeMonoid Symbol
                              Type: Domain
```

All Lyndon words of with a, b, c to order 3

```
  LyndonWordsList1([a,b,c],3)$lword
   [[[a],[b],[c]], [[a b],[a c],[b c]],
       2     2       2                      2    2       2
    [[a b],[a c],[a b ],[a b c],[a c b],[a c ],[b c],[b c ]]]
                              Type: OneDimensionalArray List LyndonWord Symbol
```

All Lyndon words of with a, b, c to order 3 in flat list

```
  LyndonWordsList([a,b,c],3)$lword
                                          2      2        2
   [[a], [b], [c], [a b], [a c], [b c], [a b], [a c], [a b ], [a b c], [a c b],
        2     2        2
    [a c ], [b c], [b c ]]
                              Type: List LyndonWord Symbol
```

All Lyndon words of with a, b to order 5

```
  lw := LyndonWordsList([a,b],5)$lword
                       2        2     3      2 2       3     4      3 2
   [[a], [b], [a b], [a b], [a b ], [a b], [a b ], [a b ], [a b], [a b ],
      2          2 3           2       4
    [a b a b], [a b ], [a b a b ], [a b ]]
                              Type: List LyndonWord Symbol

  w1 : word := lw.4 :: word
     2
    a b
                               Type: OrderedFreeMonoid Symbol

  w2 : word := lw.5 :: word
       2
    a b
                               Type: OrderedFreeMonoid Symbol
```

Let's try factoring

```
  factor(a::word)$lword
    [[a]]
                               Type: List LyndonWord Symbol
```

```
  factor(w1*w2)$lword
       2     2
    [[a b a b ]]
                              Type: List LyndonWord Symbol

  factor(w2*w2)$lword
         2      2
    [[a b ],[a b ]]
                              Type: List LyndonWord Symbol

  factor(w2*w1)$lword
         2    2
    [[a b ],[a b]]
                              Type: List LyndonWord Symbol

========================================================================
Checks and coercions
========================================================================

  lyndon?(w1)$lword
    true
                              Type: Boolean

  lyndon?(w1*w2)$lword
    true
                              Type: Boolean

  lyndon?(w2*w1)$lword
    false
                              Type: Boolean

  lyndonIfCan(w1)$lword
      2
    [a b]
                              Type: Union(LyndonWord Symbol,...)


  lyndonIfCan(w2*w1)$lword
    "failed"
                              Type: Union("failed",...)

  lyndon(w1)$lword
      2
    [a b]
                              Type: LyndonWord Symbol

  lyndon(w1*w2)$lword
      2     2
    [a b a b ]
                              Type: LyndonWord Symbol
```

```
See Also:
o )show LyndonWord
```

13.14.1 LyndonWord (LWORD)



Exports:

coerce	factor	hash	latex	left
length	lexico	lyndon	lyndon?	lyndonIfCan
LyndonWordsList	LyndonWordsList1	max	min	retract
retractIfCan	retractable?	right	varList	?<?
?<=?	?=?	?>?	?>=?	?~=?

— domain LWORD LyndonWord —

```
)abbrev domain LWORD LyndonWord
++ Author: Michel Petitot (petitot@lifl.fr).
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Free Lie Algebras by C. Reutenauer (Oxford science publications).
++ Description:
++ Lyndon words over arbitrary (ordered) symbols:
++ see Free Lie Algebras by C. Reutenauer (Oxford science publications).
++ A Lyndon word is a word which is smaller than any of its right factors
++ w.r.t. the pure lexicographical ordering.
```

```
++ If \axiom{a} and \axiom{b} are two Lyndon words such that \axiom{a < b}
++ holds w.r.t lexicographical ordering then \axiom{a*b} is a Lyndon word.
++ Parenthesized Lyndon words can be generated from symbols by using the
++ following rule:\br
++ \axiom{[[a,b],c]} is a Lyndon word iff \axiom{a*b < c <= b} holds.\br
++ Lyndon words are internally represented by binary trees using the
++ \spadtype{Magma} domain constructor.
++ Two ordering are provided: lexicographic and
++ length-lexicographic.

LyndonWord(VarSet:OrderedSet):Public == Private where
   OFMON ==> OrderedFreeMonoid(VarSet)
   PI    ==> PositiveInteger
   NNI   ==> NonNegativeInteger
   I     ==> Integer
   OF    ==> OutputForm
   ARRAY1==> OneDimensionalArray

   Public == Join(OrderedSet,RetractableTo VarSet) with
      retractable?  : $ -> Boolean
        ++ \axiom{retractable?(x)} tests if \axiom{x} is a tree
        ++ with only one entry.
      left          : $ -> $
        ++ \axiom{left(x)} returns left subtree of \axiom{x} or
        ++ error if retractable?(x) is true.
      right  :  $ -> $
        ++ \axiom{right(x)} returns right subtree of \axiom{x} or
        ++ error if retractable?(x) is true.
      length :  $ -> PI
        ++ \axiom{length(x)} returns the number of entries in \axiom{x}.
      lexico :  ($,$) -> Boolean
        ++ \axiom{lexico(x,y)} returns \axiom{true} iff  \axiom{x} is smaller than
        ++ \axiom{y} w.r.t. the lexicographical ordering induced by \axiom{VarSet}.
      coerce :  $ -> OFMON
        ++ \axiom{coerce(x)} returns the element of \axiomType{OrderedFreeMonoid}(VarSet)
        ++ corresponding to \axiom{x}.
      coerce :  $ -> Magma VarSet
        ++ \axiom{coerce(x)} returns the element of \axiomType{Magma}(VarSet)
        ++ corresponding to \axiom{x}.
      factor :  OFMON -> List $
        ++ \axiom{factor(x)} returns the decreasing factorization into Lyndon words.
      lyndon?:  OFMON -> Boolean
        ++ \axiom{lyndon?(w)} test if \axiom{w} is a Lyndon word.
      lyndon :  OFMON -> $
        ++ \axiom{lyndon(w)} convert \axiom{w} into a Lyndon word,
        ++ error if \axiom{w} is not a Lyndon word.
      lyndonIfCan : OFMON -> Union($, "failed")
        ++ \axiom{lyndonIfCan(w)} convert \axiom{w} into a Lyndon word.
      varList     : $ -> List VarSet
        ++ \axiom{varList(x)} returns the list of distinct entries of \axiom{x}.
```

```
    LyndonWordsList1: (List VarSet, PI)  -> ARRAY1 List $
      ++ \axiom{LyndonWordsList1(vl, n)} returns an array of lists of Lyndon
      ++ words over the alphabet \axiom{vl}, up to order \axiom{n}.
    LyndonWordsList : (List VarSet, PI)  -> List $
      ++ \axiom{LyndonWordsList(vl, n)} returns the list of Lyndon
      ++ words over the alphabet \axiom{vl}, up to order \axiom{n}.

  Private == Magma(VarSet) add
    -- Representation
      Rep:= Magma(VarSet)

    -- Fonctions locales
      LetterList : OFMON -> List VarSet
      factor1    : (List $, $, List $) -> List $

    -- Definitions
      lyndon? w ==
        w = 1$OFMON => false
        f: OFMON := rest w
        while f ^= 1$OFMON repeat
          not lexico(w,f) => return false
          f := rest f
        true

      lyndonIfCan w ==
        l: List $ := factor w
        # l = 1 => first l
        "failed"

      lyndon w ==
        l: List $ := factor w
        # l = 1 => first l
        error "This word is not a Lyndon word"

      LetterList w ==
        w = 1 => []
        cons(first w , LetterList rest w)

      factor1 (gauche, x, droite) ==
        g: List $ := gauche; d: List $ := droite
        while not null g repeat             ++ (l in g or l=x) et u in d
          lexico(  g.first , x ) =>         ++  => right(l) >= u
             x  := g.first *$Rep x          -- crochetage
             null(d) => g := rest g
             g := cons( x, rest g)          -- mouvement a droite
             x  := first d
             d := rest d
          d := cons( x , d)                 -- mouvement a gauche
          x  := first g
          g := rest g
```

```
  return cons(x, d)

factor w ==
  w = 1 => []
  l : List $ := reverse [ u::$ for u in LetterList w]
  factor1( rest l, first l , [] )

x < y ==                      -- lexicographique par longueur
  lx,ly: PI
  lx:= length x ; ly:= length y
  lx = ly => lexico(x,y)
  lx < ly

coerce(x:$):OF == bracket(x::OFMON::OF)
coerce(x:$):Magma VarSet == x::Rep

LyndonWordsList1 (vl,n) ==    -- a ameliorer !!!!!!!!!!!
     null vl => error "empty list"
     base: ARRAY1 List $ := new(n::I::NNI ,[])

    -- mots de longueur 1
     lbase1:List $ := [w::$ for w in sort(vl)]
     base.1 := lbase1

    -- calcul des mots de longueur ll
     for ll in 2..n:I  repeat
        lbase1 := []
        for a in base(1) repeat              -- lettre + mot
           for b in base(ll-1) repeat
              if lexico(a,b) then lbase1:=cons(a*b,lbase1)

        for i in 2..ll-1 repeat              -- mot + mot
          for a in base(i) repeat
            for b in base(ll-i) repeat
              if lexico(a,b) and (lexico(b,right a) or b = right a )
              then lbase1:=cons(a*b,lbase1)

        base(ll):= sort_!(lexico, lbase1)
     return base

LyndonWordsList (vl,n) ==
    v:ARRAY1 List $ := LyndonWordsList1(vl,n)
    "append"/ [v.i for i in 1..n]
```

———-

— **LWORD.dotabb** —

```
"LWORD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=LWORD"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"LWORD" -> "A1AGG"
```

———-

Chapter 14

Chapter M

14.1 domain MCMPLX MachineComplex

— MachineComplex.input —

```
)set break resume
)sys rm -f MachineComplex.output
)spool MachineComplex.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MachineComplex
--R
--R MachineComplex  is a domain constructor
--R Abbreviation for MachineComplex is MCMPLX
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MCMPLX
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,MachineFloat) -> %          ?*? : (MachineFloat,%) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean              ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean               ?>=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       associates? : (%,%) -> Boolean
--R basis : () -> Vector(%)              coerce : % -> Complex(Float)
--R coerce : Complex(Integer) -> %       coerce : Complex(Float) -> %
```

```
--R coerce : MachineFloat -> %           coerce : Integer -> %
--R coerce : % -> %                      coerce : Integer -> %
--R coerce : % -> OutputForm             conjugate : % -> %
--R discriminant : () -> MachineFloat    generator : () -> %
--R hash : % -> SingleInteger            imag : % -> MachineFloat
--R imaginary : () -> %                  latex : % -> String
--R max : (%,%) -> %                     min : (%,%) -> %
--R norm : % -> MachineFloat             one? : % -> Boolean
--R rank : () -> PositiveInteger         real : % -> MachineFloat
--R recip : % -> Union(%,"failed")       retract : % -> MachineFloat
--R retract : % -> Integer               sample : () -> %
--R trace : % -> MachineFloat            unit? : % -> Boolean
--R unitCanonical : % -> %               zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if MachineFloat has FIELD
--R ?*? : (Fraction(Integer),%) -> % if MachineFloat has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Integer) -> % if MachineFloat has FIELD
--R ?**? : (%,Fraction(Integer)) -> % if MachineFloat has RADCAT and MachineFloat has TRANFUN
--R ?**? : (%,%) -> % if MachineFloat has TRANFUN
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if MachineFloat has FIELD
--R D : % -> % if MachineFloat has DIFRING
--R D : (%,NonNegativeInteger) -> % if MachineFloat has DIFRING
--R D : (%,Symbol) -> % if MachineFloat has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if MachineFloat has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if MachineFloat has PDRING(SYMBOL)
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if MachineFloat has PDRING(SYMBOL)
--R D : (%,(MachineFloat -> MachineFloat),NonNegativeInteger) -> %
--R D : (%,(MachineFloat -> MachineFloat)) -> %
--R ?^? : (%,Integer) -> % if MachineFloat has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if MachineFloat has RNS
--R acos : % -> % if MachineFloat has TRANFUN
--R acosh : % -> % if MachineFloat has TRANFUN
--R acot : % -> % if MachineFloat has TRANFUN
--R acoth : % -> % if MachineFloat has TRANFUN
--R acsc : % -> % if MachineFloat has TRANFUN
--R acsch : % -> % if MachineFloat has TRANFUN
--R argument : % -> MachineFloat if MachineFloat has TRANFUN
--R asec : % -> % if MachineFloat has TRANFUN
--R asech : % -> % if MachineFloat has TRANFUN
--R asin : % -> % if MachineFloat has TRANFUN
--R asinh : % -> % if MachineFloat has TRANFUN
--R atan : % -> % if MachineFloat has TRANFUN
--R atanh : % -> % if MachineFloat has TRANFUN
--R characteristic : () -> NonNegativeInteger
--R characteristicPolynomial : % -> SparseUnivariatePolynomial(MachineFloat)
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and MachineFloat has EUCDOM and MachineF
--R charthRoot : % -> % if MachineFloat has FFIELDC
```

```
--R coerce : Fraction(Integer) -> % if MachineFloat has FIELD or MachineFloat has RETRACT(FRAC(INT))
--R coerce : Complex(MachineInteger) -> %
--R coerce : Complex(MachineFloat) -> %
--R complex : (MachineFloat,MachineFloat) -> %
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and MachineFloat has EUCDOM and Mach
--R convert : % -> Vector(MachineFloat)
--R convert : Vector(MachineFloat) -> %
--R convert : % -> SparseUnivariatePolynomial(MachineFloat)
--R convert : SparseUnivariatePolynomial(MachineFloat) -> %
--R convert : % -> Pattern(Integer) if MachineFloat has KONVERT(PATTERN(INT))
--R convert : % -> Pattern(Float) if MachineFloat has KONVERT(PATTERN(FLOAT))
--R convert : % -> Complex(Float) if MachineFloat has REAL
--R convert : % -> Complex(DoubleFloat) if MachineFloat has REAL
--R convert : % -> InputForm if MachineFloat has KONVERT(INFORM)
--R coordinates : (%,Vector(%)) -> Vector(MachineFloat)
--R coordinates : (Vector(%),Vector(%)) -> Matrix(MachineFloat)
--R coordinates : % -> Vector(MachineFloat)
--R coordinates : Vector(%) -> Matrix(MachineFloat)
--R cos : % -> % if MachineFloat has TRANFUN
--R cosh : % -> % if MachineFloat has TRANFUN
--R cot : % -> % if MachineFloat has TRANFUN
--R coth : % -> % if MachineFloat has TRANFUN
--R createPrimitiveElement : () -> % if MachineFloat has FFIELDC
--R csc : % -> % if MachineFloat has TRANFUN
--R csch : % -> % if MachineFloat has TRANFUN
--R definingPolynomial : () -> SparseUnivariatePolynomial(MachineFloat)
--R derivationCoordinates : (Vector(%),(MachineFloat -> MachineFloat)) -> Matrix(MachineFloat) if MachineFlo
--R differentiate : % -> % if MachineFloat has DIFRING
--R differentiate : (%,NonNegativeInteger) -> % if MachineFloat has DIFRING
--R differentiate : (%,Symbol) -> % if MachineFloat has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if MachineFloat has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if MachineFloat has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if MachineFloat has PDRING(SYMBOL)
--R differentiate : (%,(MachineFloat -> MachineFloat),NonNegativeInteger) -> %
--R differentiate : (%,(MachineFloat -> MachineFloat)) -> %
--R discreteLog : % -> NonNegativeInteger if MachineFloat has FFIELDC
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if MachineFloat has FFIELDC
--R discriminant : Vector(%) -> MachineFloat
--R divide : (%,%) -> Record(quotient: %,remainder: %) if MachineFloat has EUCDOM
--R ?.? : (%,MachineFloat) -> % if MachineFloat has ELTAB(MFLOAT,MFLOAT)
--R euclideanSize : % -> NonNegativeInteger if MachineFloat has EUCDOM
--R eval : (%,List(MachineFloat),List(MachineFloat)) -> % if MachineFloat has EVALAB(MFLOAT)
--R eval : (%,MachineFloat,MachineFloat) -> % if MachineFloat has EVALAB(MFLOAT)
--R eval : (%,Equation(MachineFloat)) -> % if MachineFloat has EVALAB(MFLOAT)
--R eval : (%,List(Equation(MachineFloat))) -> % if MachineFloat has EVALAB(MFLOAT)
--R eval : (%,List(Symbol),List(MachineFloat)) -> % if MachineFloat has IEVALAB(SYMBOL,MFLOAT)
--R eval : (%,Symbol,MachineFloat) -> % if MachineFloat has IEVALAB(SYMBOL,MFLOAT)
--R exp : % -> % if MachineFloat has TRANFUN
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if MachineFloat has EUCDOM
--R exquo : (%,MachineFloat) -> Union(%,"failed") if MachineFloat has INTDOM
```

```
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if MachineFloat has EUCD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if MachineFloat has
--R factor : % -> Factored(%) if MachineFloat has EUCDOM and MachineFloat has PFECAT or MachineF
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if MachineF
--R gcd : (%,%) -> % if MachineFloat has EUCDOM
--R gcd : List(%) -> % if MachineFloat has EUCDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R index : PositiveInteger -> % if MachineFloat has FINITE
--R init : () -> % if MachineFloat has FFIELDC
--R inv : % -> % if MachineFloat has FIELD
--R lcm : (%,%) -> % if MachineFloat has EUCDOM
--R lcm : List(%) -> % if MachineFloat has EUCDOM
--R lift : % -> SparseUnivariatePolynomial(MachineFloat)
--R log : % -> % if MachineFloat has TRANFUN
--R lookup : % -> PositiveInteger if MachineFloat has FINITE
--R map : ((MachineFloat -> MachineFloat),%) -> %
--R minimalPolynomial : % -> SparseUnivariatePolynomial(MachineFloat) if MachineFloat has FIELD
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if MachineFloat has EUCDOM
--R nextItem : % -> Union(%,"failed") if MachineFloat has FFIELDC
--R nthRoot : (%,Integer) -> % if MachineFloat has RADCAT and MachineFloat has TRANFUN
--R order : % -> PositiveInteger if MachineFloat has FFIELDC
--R order : % -> OnePointCompletion(PositiveInteger) if MachineFloat has FFIELDC
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pi : () -> % if MachineFloat has TRANFUN
--R polarCoordinates : % -> Record(r: MachineFloat,phi: MachineFloat) if MachineFloat has RNS an
--R prime? : % -> Boolean if MachineFloat has EUCDOM and MachineFloat has PFECAT or MachineFloat
--R primeFrobenius : (%,NonNegativeInteger) -> % if MachineFloat has FFIELDC
--R primeFrobenius : % -> % if MachineFloat has FFIELDC
--R primitive? : % -> Boolean if MachineFloat has FFIELDC
--R primitiveElement : () -> % if MachineFloat has FFIELDC
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if MachineFloat has EUCDOM
--R ?quo? : (%,%) -> % if MachineFloat has EUCDOM
--R random : () -> % if MachineFloat has FINITE
--R rational : % -> Fraction(Integer) if MachineFloat has INS
--R rational? : % -> Boolean if MachineFloat has INS
--R rationalIfCan : % -> Union(Fraction(Integer),"failed") if MachineFloat has INS
--R reduce : SparseUnivariatePolynomial(MachineFloat) -> %
--R reduce : Fraction(SparseUnivariatePolynomial(MachineFloat)) -> Union(%,"failed") if MachineF
--R reducedSystem : Matrix(%) -> Matrix(Integer) if MachineFloat has LINEXP(INT)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(MachineFloat),vec: Vector(Machin
--R reducedSystem : Matrix(%) -> Matrix(MachineFloat)
--R regularRepresentation : (%,Vector(%)) -> Matrix(MachineFloat)
--R regularRepresentation : % -> Matrix(MachineFloat)
--R ?rem? : (%,%) -> % if MachineFloat has EUCDOM
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if MachineFloat has FFIEL
```

```
--R represents : (Vector(MachineFloat),Vector(%)) -> %
--R represents : Vector(MachineFloat) -> %
--R retract : % -> Fraction(Integer) if MachineFloat has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if MachineFloat has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(MachineFloat,"failed")
--R retractIfCan : % -> Union(Integer,"failed")
--R sec : % -> % if MachineFloat has TRANFUN
--R sech : % -> % if MachineFloat has TRANFUN
--R sin : % -> % if MachineFloat has TRANFUN
--R sinh : % -> % if MachineFloat has TRANFUN
--R size : () -> NonNegativeInteger if MachineFloat has FINITE
--R sizeLess? : (%,%) -> Boolean if MachineFloat has EUCDOM
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R sqrt : % -> % if MachineFloat has RADCAT and MachineFloat has TRANFUN
--R squareFree : % -> Factored(%) if MachineFloat has EUCDOM and MachineFloat has PFECAT or MachineFloat has
--R squareFreePart : % -> % if MachineFloat has EUCDOM and MachineFloat has PFECAT or MachineFloat has FIELD
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if Machi
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if MachineFloat has FFI
--R tan : % -> % if MachineFloat has TRANFUN
--R tanh : % -> % if MachineFloat has TRANFUN
--R traceMatrix : Vector(%) -> Matrix(MachineFloat)
--R traceMatrix : () -> Matrix(MachineFloat)
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— MachineComplex.help —

```
=====================================================================
MachineComplex examples
=====================================================================

See Also:
o )show MachineComplex
```

———-

14.1.1 MachineComplex (MCMPLX)



See

⇒ “MachineInteger” (MINT) 14.3.1 on page 1525
⇒ “MachineFloat” (MFLOAT) 14.2.1 on page 1515

Exports:

0	1	abs
acos	acosh	acot
acoth	acsc	acsch
argument	asec	asech
asin	asinh	associates?
atan	atanh	basis
characteristic	characteristicPolynomial	charthRoot
coerce	complex	conditionP
conjugate	convert	coordinates
cos	cosh	cot
coth	createPrimitiveElement	csc
csch	D	definingPolynomial
derivationCoordinates	differentiate	discreteLog
discriminant	divide	euclideanSize
eval	exp	expressIdealMember
exquo	extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial	gcdPolynomial
gcd	factorsOfCyclicGroupSize	generator
hash	imag	imaginary
index	init	inv
latex	lcm	lift
log	lookup	map
max	min	minimalPolynomial
multiEuclidean	nextItem	norm
nthRoot	one?	order
patternMatch	pi	polarCoordinates
prime?	primeFrobenius	primitive?
primitiveElement	principalIdeal	random
rank	rational	rational?
rationalIfCan	real	recip
reduce	reducedSystem	regularRepresentation
representationType	represents	retract
retractIfCan	sample	sec
sech	sin	sinh
size	solveLinearPolynomialEquation	sizeLess?
sqrt	squareFree	squareFreePart
squareFreePolynomial	tableForDiscreteLogarithm	subtractIfCan
tan	tanh	trace
traceMatrix	traceMatrix	unit?
unitCanonical	unitNormal	zero?
?*?	?**?	?+?
?-?	-?	?<?
?<=?	?=?	?>?
?>=?	?^?	?~=?
?/?	?.?	?quo?
?rem?		

— domain MCMPLX MachineComplex —

```
)abbrev domain MCMPLX MachineComplex
++ Date Created:  December 1993
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See: FortranExpression, FortranMachineTypeCategory, MachineInteger,
++  MachineFloat
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A domain which models the complex number representation
++ used by machines in the AXIOM-NAG link.

MachineComplex():Exports == Implementation where

  Exports ==> Join (FortranMachineTypeCategory,
                    ComplexCategory(MachineFloat)) with
    coerce : Complex Float -> $
      ++ coerce(u) transforms u into a MachineComplex
    coerce : Complex Integer -> $
      ++ coerce(u) transforms u into a MachineComplex
    coerce : Complex MachineFloat -> $
      ++ coerce(u) transforms u into a MachineComplex
    coerce : Complex MachineInteger -> $
      ++ coerce(u) transforms u into a MachineComplex
    coerce : $ -> Complex Float
      ++ coerce(u) transforms u into a COmplex Float

  Implementation ==> Complex MachineFloat add

    coerce(u:Complex Float):$ ==
      complex(real(u)::MachineFloat,imag(u)::MachineFloat)

    coerce(u:Complex Integer):$ ==
      complex(real(u)::MachineFloat,imag(u)::MachineFloat)

    coerce(u:Complex MachineInteger):$ ==
      complex(real(u)::MachineFloat,imag(u)::MachineFloat)

    coerce(u:Complex MachineFloat):$ ==
      complex(real(u),imag(u))

    coerce(u:$):Complex Float ==
      complex(real(u)::Float,imag(u)::Float)
```

———-

— **MCMPLX.dotabb** —

```
"MCMPLX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MCMPLX"]
"COMPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=COMPCAT"]
"MCMPLX" -> "COMPCAT"
```

———-

14.2 domain MFLOAT MachineFloat

— **MachineFloat.input** —

```
)set break resume
)sys rm -f MachineFloat.output
)spool MachineFloat.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MachineFloat
--R
--R MachineFloat  is a domain constructor
--R Abbreviation for MachineFloat is MFLOAT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MFLOAT
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R abs : % -> %                          associates? : (%,%) -> Boolean
--R base : () -> PositiveInteger          bits : () -> PositiveInteger
--R ceiling : % -> %                      coerce : MachineInteger -> %
--R coerce : % -> Float                   coerce : Float -> %
--R coerce : Fraction(Integer) -> %       coerce : Integer -> %
```

```
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R convert : % -> Pattern(Float)         convert : % -> DoubleFloat
--R convert : % -> Float                  digits : () -> PositiveInteger
--R exponent : % -> Integer               factor : % -> Factored(%)
--R float : (Integer,Integer) -> %        floor : % -> %
--R fractionPart : % -> %                 gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R mantissa : % -> Integer               max : (%,%) -> %
--R maximumExponent : () -> Integer       min : (%,%) -> %
--R minimumExponent : () -> Integer       negative? : % -> Boolean
--R norm : % -> %                         nthRoot : (%,Integer) -> %
--R one? : % -> Boolean                   order : % -> Integer
--R positive? : % -> Boolean              precision : () -> PositiveInteger
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R retract : % -> Float                  retract : % -> Fraction(Integer)
--R retract : % -> Integer                round : % -> %
--R sample : () -> %                      sign : % -> Integer
--R sizeLess? : (%,%) -> Boolean          sqrt : % -> %
--R squareFree : % -> Factored(%)         squareFreePart : % -> %
--R truncate : % -> %                     unit? : % -> Boolean
--R unitCanonical : % -> %                wholePart : % -> Integer
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R base : PositiveInteger -> PositiveInteger
--R bits : PositiveInteger -> PositiveInteger if $ has arbitraryPrecision
--R changeBase : (Integer,Integer,PositiveInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R decreasePrecision : Integer -> PositiveInteger if $ has arbitraryPrecision
--R digits : PositiveInteger -> PositiveInteger if $ has arbitraryPrecision
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R float : (Integer,Integer,PositiveInteger) -> %
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R increasePrecision : Integer -> PositiveInteger if $ has arbitraryPrecision
--R max : () -> % if not(has($,arbitraryExponent)) and not(has($,arbitraryPrecision))
--R maximumExponent : Integer -> Integer
--R min : () -> % if not(has($,arbitraryExponent)) and not(has($,arbitraryPrecision))
--R minimumExponent : Integer -> Integer
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
```

```
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R precision : PositiveInteger -> PositiveInteger
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R retractIfCan : % -> Union(Float,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed")
--R retractIfCan : % -> Union(Integer,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **MachineFloat.help** —

```
=====================================================================
MachineFloat examples
=====================================================================

See Also:
o )show MachineFloat
```

———-

14.2.1 MachineFloat (MFLOAT)



See

⇒ “MachineInteger” (MINT) 14.3.1 on page 1525
⇒ “MachineComplex” (MCMPLX) 14.1.1 on page 1510

Exports:

1	0	abs	associates?
base	bits	ceiling	coerce
changeBase	characteristic	convert	decreasePrecision
digits	exponent	divide	euclideanSize
expressIdealMember	exquo	extendedEuclidean	factor
float	floor	fractionPart	gcd
gcdPolynomial	hash	increasePrecision	inv
latex	lcm	mantissa	max
maximumExponent	min	minimumExponent	multiEuclidean
negative?	norm	nthRoot	one?
order	patternMatch	positive?	precision
prime?	principalIdeal	recip	retract
retractIfCan	round	sample	sign
sizeLess?	sqrt	squareFree	squareFreePart
subtractIfCan	truncate	unit?	unitCanonical
unitNormal	wholePart	zero?	?*?
?**?	?+?	?-?	-?
?/?	?<?	?<=?	?=?
?>?	?>=?	?~=?	?^?
?quo?	?rem?		

— domain MFLOAT MachineFloat —

```
)abbrev domain MFLOAT MachineFloat
++ Author: Mike Dewar
++ Date Created:  December 1993
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See: FortranExpression, FortranMachineTypeCategory, MachineInteger,
++  MachineComplex
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A domain which models the floating point representation
++ used by machines in the AXIOM-NAG link.

MachineFloat(): Exports == Implementation where

  PI  ==> PositiveInteger
  NNI ==> NonNegativeInteger
  F   ==> Float
  I   ==> Integer
  S   ==> String
  FI  ==> Fraction Integer
```

```
SUP ==> SparseUnivariatePolynomial
SF  ==> DoubleFloat

Exports ==> Join(FloatingPointSystem,FortranMachineTypeCategory,Field,
    RetractableTo(Float),RetractableTo(Fraction(Integer)),CharacteristicZero) with
  precision : PI -> PI
    ++ precision(p) sets the number of digits in the model to p
  precision : () -> PI
    ++ precision() returns the number of digits in the model
  base   : PI -> PI
    ++ base(b) sets the base of the model to b
  base   : () -> PI
    ++ base() returns the base of the model
  maximumExponent : I -> I
    ++ maximumExponent(e) sets the maximum exponent in the model to e
  maximumExponent : () -> I
    ++ maximumExponent() returns the maximum exponent in the model
  minimumExponent : I -> I
    ++ minimumExponent(e) sets the minimum exponent in the model to e
  minimumExponent : () -> I
    ++ minimumExponent() returns the minimum exponent in the model
  coerce : $ -> F
    ++ coerce(u) transforms a MachineFloat to a standard Float
  coerce : MachineInteger -> $
    ++ coerce(u) transforms a MachineInteger into a MachineFloat
  mantissa  : $ -> I
    ++ mantissa(u) returns the mantissa of u
  exponent  : $ -> I
    ++ exponent(u) returns the exponent of u
  changeBase : (I,I,PI) -> $
    ++ changeBase(exp,man,base) is not documented

Implementation ==> add

  import F
  import FI

  Rep := Record(mantissa:I,exponent:I)

  -- Parameters of the Floating Point Representation
  P : PI := 16      -- Precision
  B : PI := 2       -- Base
  EMIN : I := -1021 -- Minimum Exponent
  EMAX : I :=  1024 -- Maximum Exponent

  -- Useful constants
  POWER : PI := 53  -- The maximum power of B which will yield P
                    -- decimal digits.
  MMAX  : PI := B**POWER
```

```
-- locals
locRound:(FI)->I
checkExponent:($)->$
normalise:($)->$
newPower:(PI,PI)->Void

retractIfCan(u:$):Union(FI,"failed") ==
  mantissa(u)*(B/1)**(exponent(u))

wholePart(u:$):Integer ==
   man:I:=mantissa u
   exp:I:=exponent u
   f:=
       positive? exp => man*B**(exp pretend PI)
       zero? exp => man
       wholePart(man/B**((-exp) pretend PI))
normalise(u:$):$ ==
  -- We want the largest possible mantissa, to ensure a canonical
  -- representation.
  exp : I  := exponent u
  man : I  := mantissa u
  BB  : I  := B pretend I
  sgn : I := sign man ; man := abs man
  zero? man => [0,0]$Rep
  if man < MMAX then
    while man < MMAX repeat
      exp := exp - 1
      man := man * BB
  if man > MMAX then
    q1:FI:= man/1
    BBF:FI:=BB/1
    while wholePart(q1) > MMAX repeat
      q1:= q1 / BBF
      exp:=exp + 1
    man := locRound(q1)
  positive?(sgn) => checkExponent [man,exp]$Rep
  checkExponent [-man,exp]$Rep

mantissa(u:$):I == elt(u,mantissa)$Rep
exponent(u:$):I == elt(u,exponent)$Rep

newPower(base:PI,prec:PI):Void ==
  power   : PI := 1
  target  : PI := 10**prec
  current : PI := base
  while (current := current*base) < target repeat power := power+1
  POWER := power
  MMAX  := B**POWER
  void()
```

```
changeBase(exp:I,man:I,base:PI):$ ==
  newExp : I  := 0
  f      : FI := man*(base pretend I)::FI**exp
  sign   : I  := sign f
  f      : FI := abs f
  newMan : I  := wholePart f
  zero? f => [0,0]$Rep
  BB     : FI := (B pretend I)::FI
  if newMan < MMAX then
    while newMan < MMAX repeat
      newExp := newExp - 1
      f := f*BB
      newMan := wholePart f
  if newMan > MMAX then
    while newMan > MMAX repeat
      newExp := newExp + 1
      f := f/BB
      newMan := wholePart f
  [sign*newMan,newExp]$Rep

checkExponent(u:$):$ ==
  exponent(u) < EMIN or exponent(u) > EMAX =>
    message :S := concat(["Exponent out of range: ",
                          convert(EMIN)@S, "..", convert(EMAX)@S])$S
    error message
  u

coerce(u:$):OutputForm ==
  coerce(u::F)

coerce(u:MachineInteger):$ ==
  checkExponent changeBase(0,retract(u)@Integer,10)

coerce(u:$):F ==
  oldDigits : PI := digits(P)$F
  r : F := float(mantissa u,exponent u,B)$Float
  digits(oldDigits)$F
  r

coerce(u:F):$ ==
  checkExponent changeBase(exponent(u)$F,mantissa(u)$F,base()$F)

coerce(u:I):$ ==
   checkExponent changeBase(0,u,10)

coerce(u:FI):$ == (numer u)::$/(denom u)::$

retract(u:$):FI ==
  value : Union(FI,"failed") := retractIfCan(u)
```

```
    value case "failed" => error "Cannot retract to a Fraction Integer"
    value::FI

  retract(u:$):F == u::F

  retractIfCan(u:$):Union(F,"failed") == u::F::Union(F,"failed")

  retractIfCan(u:$):Union(I,"failed") ==
    value:FI := mantissa(u)*(B pretend I)::FI**exponent(u)
    zero? fractionPart(value) => wholePart(value)::Union(I,"failed")
    "failed"::Union(I,"failed")

  retract(u:$):I ==
    result : Union(I,"failed") := retractIfCan u
    result = "failed" => error "Not an Integer"
    result::I

  precision(p: PI):PI ==
    old : PI := P
    newPower(B,p)
    P := p
    old

  precision():PI == P

  base(b:PI):PI ==
    old : PI := b
    newPower(b,P)
    B := b
    old

  base():PI == B

  maximumExponent(u:I):I ==
    old : I := EMAX
    EMAX := u
    old

  maximumExponent():I == EMAX

  minimumExponent(u:I):I ==
    old : I := EMIN
    EMIN := u
    old

  minimumExponent():I == EMIN

  0 == [0,0]$Rep
  1 == changeBase(0,1,10)
```

```
    zero?(u:$):Boolean == u=[0,0]$Rep



    f1:$
    f2:$


    locRound(x:FI):I ==
      abs(fractionPart(x)) >= 1/2 => wholePart(x)+sign(x)
      wholePart(x)

    recip f1 ==
      zero? f1 => "failed"
      normalise [ locRound(B**(2*POWER)/mantissa f1),-(exponent f1 + 2*POWER)]

    f1 * f2 ==
      normalise [mantissa(f1)*mantissa(f2),exponent(f1)+exponent(f2)]$Rep

    f1 **(p:FI) ==
      ((f1::F)**p)::%

--inline
    f1 / f2 ==
      zero? f2 => error "division by zero"
      zero? f1 => 0
      f1=f2 => 1
      normalise [locRound(mantissa(f1)*B**(2*POWER)/mantissa(f2)),
         exponent(f1)-(exponent f2 + 2*POWER)]

    inv(f1) == 1/f1

    f1 exquo f2 == f1/f2

    divide(f1,f2) == [ f1/f2,0]

    f1 quo f2 == f1/f2
    f1 rem f2 == 0
    u:I * f1 ==
      normalise [u*mantissa(f1),exponent(f1)]$Rep

    f1 = f2 == mantissa(f1)=mantissa(f2) and exponent(f1)=exponent(f2)

    f1 + f2 ==
      m1 : I := mantissa f1
      m2 : I := mantissa f2
      e1 : I := exponent f1
      e2 : I := exponent f2
      e1 > e2 =>
--insignificance
```

```
        e1 > e2 + POWER + 2 =>
              zero? f1 => f2
              f1
        normalise [m1*(B pretend I)**((e1-e2) pretend NNI)+m2,e2]$Rep
      e2 > e1 + POWER +2 =>
              zero? f2 => f1
              f2
      normalise [m2*(B pretend I)**((e2-e1) pretend NNI)+m1,e1]$Rep

    - f1 == [- mantissa f1,exponent f1]$Rep

    f1 - f2 == f1 + (-f2)

    f1 < f2 ==
      m1 : I := mantissa f1
      m2 : I := mantissa f2
      e1 : I := exponent f1
      e2 : I := exponent f2
      sign(m1) = sign(m2) =>
        e1 < e2 => true
        e1 = e2 and m1 < m2 => true
        false
      sign(m1) = 1 => false
      sign(m1) = 0 and sign(m2) = -1 => false
      true

    characteristic():NNI == 0
```

———-

— MFLOAT.dotabb —

```
"MFLOAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MFLOAT"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"MFLOAT" -> "STRING"
```

———-

14.3 domain MINT MachineInteger

— MachineInteger.input —

```
)set break resume
)sys rm -f MachineInteger.output
```

```
)spool MachineInteger.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MachineInteger
--R
--R MachineInteger  is a domain constructor
--R Abbreviation for MachineInteger is MINT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MINT
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R D : (%,NonNegativeInteger) -> %       D : % -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        abs : % -> %
--R addmod : (%,%,%) -> %                 associates? : (%,%) -> Boolean
--R base : () -> %                        binomial : (%,%) -> %
--R bit? : (%,%) -> Boolean               coerce : Integer -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              convert : % -> Integer
--R convert : % -> InputForm              convert : % -> Pattern(Integer)
--R convert : % -> Float                  convert : % -> DoubleFloat
--R copy : % -> %                         dec : % -> %
--R differentiate : % -> %                even? : % -> Boolean
--R factor : % -> Factored(%)             factorial : % -> %
--R gcd : (%,%) -> %                      gcd : List(%) -> %
--R hash : % -> %                         hash : % -> SingleInteger
--R inc : % -> %                          init : () -> %
--R invmod : (%,%) -> %                   latex : % -> String
--R lcm : (%,%) -> %                      lcm : List(%) -> %
--R length : % -> %                       mask : % -> %
--R max : (%,%) -> %                      maxint : () -> PositiveInteger
--R min : (%,%) -> %                      mulmod : (%,%,%) -> %
--R negative? : % -> Boolean              odd? : % -> Boolean
--R one? : % -> Boolean                   permutation : (%,%) -> %
--R positive? : % -> Boolean              positiveRemainder : (%,%) -> %
--R powmod : (%,%,%) -> %                 prime? : % -> Boolean
--R ?quo? : (%,%) -> %                    random : () -> %
--R random : % -> %                       rational : % -> Fraction(Integer)
--R rational? : % -> Boolean              recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %                    retract : % -> Integer
--R sample : () -> %                      shift : (%,%) -> %
```

```
--R sign : % -> Integer                    sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)          squareFreePart : % -> %
--R submod : (%,%,%) -> %                  symmetricRemainder : (%,%) -> %
--R unit? : % -> Boolean                   unitCanonical : % -> %
--R zero? : % -> Boolean                   ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coerce : Expression(Integer) -> Expression(%)
--R differentiate : (%,NonNegativeInteger) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R maxint : PositiveInteger -> PositiveInteger
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed")
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R rationalIfCan : % -> Union(Fraction(Integer),"failed")
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer))
--R reducedSystem : Matrix(%) -> Matrix(Integer)
--R retractIfCan : % -> Union(Integer,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— MachineInteger.help —

```
=====================================================================
MachineInteger examples
=====================================================================

See Also:
o )show MachineInteger
```

———-

14.3.1 MachineInteger (MINT)



See

⇒ "MachineFloat" (MFLOAT) 14.2.1 on page 1515
⇒ "MachineComplex" (MCMPLX) 14.1.1 on page 1510

Exports:

0	1	abs	addmod	associates?
base	binomial	bit?	characteristic	coerce
convert	copy	D	dec	differentiate
divide	euclideanSize	even?	expressIdealMember	exquo
extendedEuclidean	factor	factorial	gcd	gcdPolynomial
hash	inc	init	invmod	latex
lcm	length	mask	max	maxint
min	mulmod	multiEuclidean	negative?	nextItem
odd?	one?	patternMatch	permutation	positive?
positiveRemainder	powmod	prime?	principalIdeal	random
rational	rationalIfCan	rational?	recip	reducedSystem
retract	retractIfCan	sample	shift	sign
sizeLess?	squareFree	squareFreePart	submod	subtractIfCan
symmetricRemainder	unit?	unitCanonical	unitNormal	zero?
?~=?	?*?	?**?	?^?	?+?
?-?	-?	?<?	?<=?	?=?
?>?	?>=?	?quo?	?rem?	

— domain MINT MachineInteger —

```
)abbrev domain MINT MachineInteger
++ Author: Mike Dewar
++ Date Created:  December 1993
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See: FortranExpression, FortranMachineTypeCategory, MachineFloat,
++  MachineComplex
++ AMS Classifications:
++ Keywords:
```

```
++ Examples:
++ References:
++ Description:
++ A domain which models the integer representation
++ used by machines in the AXIOM-NAG link.

MachineInteger(): Exports == Implementation where

  S ==> String

  Exports ==> Join(FortranMachineTypeCategory,IntegerNumberSystem) with
    maxint : PositiveInteger -> PositiveInteger
     ++ maxint(u) sets the maximum integer in the model to u
    maxint : () -> PositiveInteger
     ++ maxint() returns the maximum integer in the model
    coerce : Expression Integer -> Expression $
     ++ coerce(x) returns x with coefficients in the domain

  Implementation  ==> Integer add

    MAXINT : PositiveInteger := 2**32

    maxint():PositiveInteger == MAXINT

    maxint(new:PositiveInteger):PositiveInteger ==
      old := MAXINT
      MAXINT := new
      old

    coerce(u:Expression Integer):Expression($) ==
      map(coerce,u)$ExpressionFunctions2(Integer,$)

    coerce(u:Integer):$ ==
      import S
      abs(u) > MAXINT =>
        message: S := concat [convert(u)@S,"  > MAXINT(",convert(MAXINT)@S,")"]
        error message
      u pretend $

    retract(u:$):Integer == u pretend Integer

    retractIfCan(u:$):Union(Integer,"failed") == u pretend Integer
```

———-

— MINT.dotabb —

```
"MINT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MINT"]
```

```
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"MINT" -> "STRING"
```

———-

14.4 domain MAGMA Magma

— **Magma.input** —

```
)set break resume
)sys rm -f Magma.output
)spool Magma.output
)set message test on
)set message auto off
)clear all
--S 1 of 22
x:Symbol :='x
--R
--R
--R   (1)  x
--R                                                    Type: Symbol
--E 1

--S 2 of 22
y:Symbol :='y
--R
--R
--R   (2)  y
--R                                                    Type: Symbol
--E 2

--S 3 of 22
z:Symbol :='z
--R
--R
--R   (3)  z
--R                                                    Type: Symbol
--E 3

--S 4 of 22
word := OrderedFreeMonoid(Symbol)
--R
--R
--R   (4)  OrderedFreeMonoid(Symbol)
--R                                                    Type: Domain
--E 4
```

```
--S 5 of 22
tree := Magma(Symbol)
--R
--R
--R   (5)  Magma(Symbol)
--R                                                        Type: Domain
--E 5

--S 6 of 22
a:tree := x*x
--R
--R
--R   (6)  [x,x]
--R                                              Type: Magma(Symbol)
--E 6

--S 7 of 22
b:tree := y*y
--R
--R
--R   (7)  [y,y]
--R                                              Type: Magma(Symbol)
--E 7

--S 8 of 22
c:tree := a*b
--R
--R
--R   (8)  [[x,x],[y,y]]
--R                                              Type: Magma(Symbol)
--E 8

--S 9 of 22
left c
--R
--R
--R   (9)  [x,x]
--R                                              Type: Magma(Symbol)
--E 9

--S 10 of 22
right c
--R
--R
--R   (10)  [y,y]
--R                                              Type: Magma(Symbol)
--E 10

--S 11 of 22
```

```
length c
--R
--R
--R   (11)  4
--R                                                  Type: PositiveInteger
--E 11

--S 12 of 22
c::word
--R
--R
--R          2 2
--R   (12)  x y
--R                                        Type: OrderedFreeMonoid(Symbol)
--E 12

--S 13 of 22
a < b
--R
--R
--R   (13)  true
--R                                                       Type: Boolean
--E 13

--S 14 of 22
a < c
--R
--R
--R   (14)  true
--R                                                       Type: Boolean
--E 14

--S 15 of 22
b < c
--R
--R
--R   (15)  true
--R                                                       Type: Boolean
--E 15

--S 16 of 22
first c
--R
--R
--R   (16)  x
--R                                                        Type: Symbol
--E 16

--S 17 of 22
rest c
```

```
--R
--R
--R   (17)  [x,[y,y]]
--R                                                    Type: Magma(Symbol)
--E 17

--S 18 of 22
rest rest c
--R
--R
--R   (18)  [y,y]
--R                                                    Type: Magma(Symbol)
--E 18

--S 19 of 22
ax:tree := a*x
--R
--R
--R   (19)  [[x,x],x]
--R                                                    Type: Magma(Symbol)
--E 19

--S 20 of 22
xa:tree := x*a
--R
--R
--R   (20)  [x,[x,x]]
--R                                                    Type: Magma(Symbol)
--E 20

--S 21 of 22
xa < ax
--R
--R
--R   (21)  true
--R                                                          Type: Boolean
--E 21

--S 22 of 22
lexico(xa,ax)
--R
--R
--R   (22)  false
--R                                                          Type: Boolean
--E 22
)spool
)lisp (bye)
```

— Magma.help —

```
====================================================================
Magma examples
====================================================================

Initialisations

  x:Symbol :='x
    x
                          Type: Symbol

  y:Symbol :='y
    y
                          Type: Symbol

  z:Symbol :='z
    z
                          Type: Symbol

  word := OrderedFreeMonoid(Symbol)
    OrderedFreeMonoid Symbol
                          Type: Domain

  tree := Magma(Symbol)
    Magma Symbol
                          Type: Domain

Let's make some trees

  a:tree := x*x
    [x,x]
                          Type: Magma Symbol

  b:tree := y*y
    [y,y]
                          Type: Magma Symbol

  c:tree := a*b
    [[x,x],[y,y]]
                          Type: Magma Symbol

Query the trees

  left c
    [x,x]
                          Type: Magma Symbol

  right c
```

```
    [y,y]
                          Type: Magma Symbol

  length c
    4
                          Type: PositiveInteger

Coerce to the monoid

  c::word
     2 2
    x y
                          Type: OrderedFreeMonoid Symbol

Check ordering

  a < b
    true
                          Type: Boolean

  a < c
    true
                          Type: Boolean

  b < c
    true
                          Type: Boolean

Navigate the tree

  first c
    x
                          Type: Symbol

  rest c
    [x,[y,y]]
                          Type: Magma Symbol

  rest rest c
    [y,y]
                          Type: Magma Symbol

Check ordering

  ax:tree := a*x
    [[x,x],x]
                          Type: Magma Symbol

  xa:tree := x*a
    [x,[x,x]]
```

```
                                Type: Magma Symbol


  xa < ax
    true
                                Type: Boolean

  lexico(xa,ax)
    false
                                Type: Boolean

See Also:
o )show Magma
```

———-

14.4.1 Magma (MAGMA)



Exports:

coerce	first	hash	latex	left
length	lexico	max	min	mirror
rest	retract	retractIfCan	retractable?	right
varList	?~=?	?*?	?<?	?<=?
?=?	?>?	?>=?		

— domain MAGMA Magma —

```
)abbrev domain MAGMA Magma
++ Author: Michel Petitot (petitot@lifl.fr).
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
```

```
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type is the basic representation of
++ parenthesized words (binary trees over arbitrary symbols)
++ useful in \spadtype{LiePolynomial}.

Magma(VarSet:OrderedSet):Public == Private where
   WORD ==> OrderedFreeMonoid(VarSet)
   EX   ==> OutputForm

   Public == Join(OrderedSet,RetractableTo VarSet) with
      "*"           : ($,$) -> $
        ++ \axiom{x*y} returns the tree \axiom{[x,y]}.
      coerce        : $ -> WORD
        ++ \axiom{coerce(x)} returns the element of
        ++\axiomType{OrderedFreeMonoid}(VarSet)
        ++ corresponding to \axiom{x} by removing parentheses.
      first         : $ -> VarSet
        ++ \axiom{first(x)} returns the first entry of the tree \axiom{x}.
      left          : $ -> $
        ++ \axiom{left(x)} returns left subtree of \axiom{x} or
        ++ error if retractable?(x) is true.
      length        : $ -> PositiveInteger
        ++ \axiom{length(x)} returns the number of entries in \axiom{x}.
      lexico        : ($,$) -> Boolean
        ++ \axiom{lexico(x,y)} returns \axiom{true} iff  \axiom{x} is smaller
        ++ than \axiom{y} w.r.t. the lexicographical ordering induced by
        ++ \axiom{VarSet}.
        ++ N.B. This operation does not take into account the tree structure of
        ++ its arguments. Thus this is not a total ordering.
      mirror        : $ -> $
        ++ \axiom{mirror(x)} returns the reversed word of \axiom{x}.
        ++ That is \axiom{x} itself if retractable?(x) is true and
        ++ \axiom{mirror(z) * mirror(y)} if \axiom{x} is \axiom{y*z}.
      rest          : $ -> $
        ++ \axiom{rest(x)} return \axiom{x} without the first entry or
        ++ error if retractable?(x) is true.
      retractable?  : $ -> Boolean
        ++ \axiom{retractable?(x)} tests if \axiom{x} is a tree with
        ++ only one entry.
      right         : $ -> $
        ++ \axiom{right(x)} returns right subtree of \axiom{x} or
        ++ error if retractable?(x) is true.
      varList       : $ -> List VarSet
        ++ \axiom{varList(x)} returns the list of distinct entries of \axiom{x}.

   Private == add
    -- representation
```

```
    VWORD := Record(left:$ ,right:$)
    Rep:= Union(VarSet,VWORD)

    recursif: ($,$) -> Boolean

  -- define
    x:$ = y:$ ==
      x case VarSet =>
         y case VarSet => x::VarSet = y::VarSet
         false
      y case VWORD => x::VWORD = y::VWORD
      false

    varList x ==
      x case VarSet => [x::VarSet]
      lv: List VarSet := setUnion(varList x.left, varList x.right)
      sort_!(lv)

    left x ==
      x case VarSet => error "x has only one entry"
      x.left

    right x ==
      x case VarSet => error "x has only one entry"
      x.right
    retractable? x == (x case VarSet)

    retract x ==
       x case VarSet => x::VarSet
       error "Not retractable"

    retractIfCan x == (retractable? x => x::VarSet ; "failed")
    coerce(l:VarSet):$  == l

    mirror x ==
      x case VarSet => x
      [mirror x.right, mirror x.left]$VWORD

    coerce(x:$): WORD ==
      x case VarSet => x::VarSet::WORD
      x.left::WORD * x.right::WORD

    coerce(x:$):EX ==
       x case VarSet => x::VarSet::EX
       bracket [x.left::EX, x.right::EX]

    x * y == [x,y]$VWORD

    first x ==
       x case VarSet => x::VarSet
```

```
      first x.left

   rest x ==
      x case VarSet => error "rest$Magma: inexistant rest"
      lx:$ := x.left
      lx case VarSet => x.right
      [rest lx , x.right]$VWORD

   length x ==
      x case VarSet => 1
      length(x.left) + length(x.right)

   recursif(x,y) ==
      x case VarSet =>
         y case VarSet => x::VarSet < y::VarSet
         true
      y case VarSet => false
      x.left =  y.left =>  x.right <  y.right
      x.left < y.left

   lexico(x,y) ==      -- peut etre amelioree !!!!!!!!!!!
      x case VarSet =>
         y case VarSet => x::VarSet < y::VarSet
         x::VarSet <= first y
      y case VarSet => first x < retract y
      fx:VarSet := first x ; fy:VarSet := first y
      fx = fy => lexico(rest x , rest y)
      fx < fy

   x < y ==           -- recursif par longueur
      lx,ly: PositiveInteger
      lx:= length x ; ly:= length y
      lx = ly => recursif(x,y)
      lx < ly
```

———-

— MAGMA.dotabb —

```
"MAGMA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MAGMA"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"MAGMA" -> "FLAGG"
"MAGMA" -> "FLAGG-"
```

———-

14.5 domain MKCHSET MakeCachableSet

— MakeCachableSet.input —

```
)set break resume
)sys rm -f MakeCachableSet.output
)spool MakeCachableSet.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MakeCachableSet
--R
--R MakeCachableSet(S: SetCategory)  is a domain constructor
--R Abbreviation for MakeCachableSet is MKCHSET
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MKCHSET
--R
--R------------------------------ Operations --------------------------------
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               coerce : S -> %
--R coerce : % -> S                       coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R max : (%,%) -> %                      min : (%,%) -> %
--R ?~=? : (%,%) -> Boolean
--R position : % -> NonNegativeInteger
--R setPosition : (%,NonNegativeInteger) -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— MakeCachableSet.help —

```
=====================================================================
MakeCachableSet examples
=====================================================================

See Also:
o )show MakeCachableSet
```

———-

14.5.1 MakeCachableSet (MKCHSET)



See

⇒ "Kernel" (KERNEL) 12.1.1 on page 1372

Exports:

coerce	hash	latex	max	min	position
setPosition	?~=?	?<?	?<=?	?=?	?>?
?>=?					

— domain MKCHSET MakeCachableSet —

```
)abbrev domain MKCHSET MakeCachableSet
++ Author: Manuel Bronstein
++ Date Created: ???
++ Date Last Updated: 14 May 1991
++ Description:
++ MakeCachableSet(S) returns a cachable set which is equal to S as a set.

MakeCachableSet(S:SetCategory): Exports == Implementation where
  Exports ==> Join(CachableSet, CoercibleTo S) with
    coerce: S -> %
      ++ coerce(s) returns s viewed as an element of %.

  Implementation ==> add
    import SortedCache(%)

    Rep := Record(setpart: S, pos: NonNegativeInteger)

    clearCache()

    position x             == x.pos
    setPosition(x, n)      == (x.pos := n; void)
    coerce(x:%):S          == x.setpart
    coerce(x:%):OutputForm == x::S::OutputForm
    coerce(s:S):%          == enterInCache([s, 0]$Rep, x+->(s = x::S))

    x < y ==
```

```
      if position(x) = 0 then enterInCache(x, x1+->(x::S = x1::S))
      if position(y) = 0 then enterInCache(y, x1+->(y::S = x1::S))
      position(x) < position(y)

    x = y ==
      if position(x) = 0 then enterInCache(x, x1+->(x::S = x1::S))
      if position(y) = 0 then enterInCache(y, x1+->(y::S = x1::S))
      position(x) = position(y)
```

———-

— **MKCHSET.dotabb** —

```
"MKCHSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MKCHSET"]
"CACHSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=CACHSET"]
"MKCHSET" -> "CACHSET"
```

———-

14.6 domain MMLFORM MathMLFormat

— **MathMLFormat.input** —

```
)set break resume
)sys rm -f MathMLFormat.output
)spool MathMLFormat.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MathMLFormat
--R MathMLFormat  is a domain constructor
--R Abbreviation for MathMLFormat is MMLFORM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MMLFORM
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : OutputForm -> String
--R coerce : % -> OutputForm              coerceL : OutputForm -> String
--R coerceS : OutputForm -> String        display : String -> Void
--R exprex : OutputForm -> String         hash : % -> SingleInteger
--R latex : % -> String                   ?~=? : (%,%) -> Boolean
--R
```

```
--E 1

)spool
)lisp (bye)
```

———-

— **MathMLFormat.help** —

```
=====================================================================
MathMLFormat examples
=====================================================================

See Also:
o )show MathMLFormat
```

———-

Both this code and documentation are still under development and I don't pretend they are anywhere close to perfect or even finished. However the code does work and I hope it might be useful to somebody both for it's ability to output MathML from Axiom and as an example of how to write a new output form.

14.6.1 Introduction to Mathematical Markup Language

MathML exists in two forms: presentation and content. At this time (2007-02-11) the package only has a presentation package. A content package is in the works however it is more difficult. Unfortunately Axiom does not make its semantics easily available. The **OutputForm** domain mediates between the individual Axiom domains and the user visible output but **OutputForm** does not provide full semantic information. From my currently incomplete understanding of Axiom it appears that remedying this would entail going back to the individual domains and rewriting a lot of code. However some semantics are conveyed directly by **OutputForm** and other things can be deduced from **OutputForm** or from the original user command.

14.6.2 Displaying MathML

The MathML string produced by ")set output mathml on" can be pasted directly into an appropriate xhtml page and then viewed in Firefox or some other MathML aware browser. The boiler plate code needed for a test page, testmathml.xml, is:

```
<?xml version="1.0" ?>

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1 plus MathML 2.0//EN"
                      "http://www.w3.org/Math/DTD/mathml2/xhtml-math11-f.dtd" [
```

```
<!ENTITY mathml "http://www.w3.org/1998/Math/MathML">
]>

<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:xlink="http://www.w3.org/1999/xlink" >


  <head>
    <title>MathML Test </title>
  </head>

  <body>

  </body>
</html>
```

Paste the MathML string into the body element and it should display nicely in Firefox.

14.6.3 Test Cases

Here's a list of test cases that currently format correctly:

1. (x+y)**2
2. integrate(x**x,x)
3. integral(x**x,x)
4. (5 + sqrt 63 + sqrt 847)**(1/3)
5. set [1,2,3]
6. multiset [x rem 5 for x in primes(2,1000)]
7. series(sin(a*x),x=0)
8. matrix [[x**i + y**j for i in 1..10] for j in 1..10]
9. y := operator 'y a. D(y(x,z),[x,x,z,x]) b. D(y x,x,2)
10. x := series 'x a. sin(1+x)
11. series(1/log(y),y=1)
12. y:UTS(FLOAT,'z,0) := exp(z)
13. a. c := continuedFraction(314159/100000) b. c := continuedFraction(314159/100000)

The **TexFormat** domain has the capability to format an object with subscripts, superscripts, presubscripts and presuperscripts however I don't know of any Axiom command that produces such an object. In fact at present I see the case of "SUPERSUB" being used for putting primes in the superscript position to denote ordinary differentiation. I also only see the "SUB" case being used to denote partial derivatives.

14.6.4)set output mathml on

Making mathml appear as output during a normal Axiom session by invoking ")set output mathml on" proved to be a bit tedious and seems to be undocumented. I document my experience here in case it proves useful to somebody else trying to get a new output format from Axiom.

In **MathMLFormat** the functions *coerce(expr : OutputForm) : String* and *display(s : String) : Void* provide the desired mathml output. Note that this package was constructed by close examination of Robert Sutor's **TexFormat** domain and much remains from that source. To have mathml displayed as output we need to get Axiom to call display(coerce(expr)) at the appropriate place. Here's what I did to get that to happen. Note that my starting point here was an attempt by Andrey Grozin to do the same. To figure things out I searched through files for "tex" to see what was done for the **TexFormat** domain, and used grep to find which files had mention of **TexFormat**.

14.6.5 File src/interp/setvars.boot.pamphlet

Create an output mathml section by analogy to the tex section. Remember to add the code chunk "outputmathmlCode" at the end.

setvars.boot is a bootstrap file which means that it has to be precompiled into lisp code and then that code has to be inserted back into setvars.boot. To do this extract the boot code by running "notangle" on it. I did this from the "tmp" directory. From inside axiom run ")lisp (boottran::boottocl "tmp/setvars.boot") which put "setvars.clisp" into "int/interp/setvars.clisp". Then replace the lisp in "setvars.boot.pamphlet" with that in the newly generated "setvars.clisp".

The relevant code chunks appearing in "setvars.boot.pamphlet" are:

```
outputmathmlCode
setOutputMathml
describeSetOutputMathml
```

and the relevant variables are:

```
setOutputMathml
$mathmlOutputStream
$mathmlOutputFile
$mathmlFormat
describeSetOutputMathml
```

14.6.6 File setvart.boot.pamphlet

Create an output mathml section in "setvart.boot.pamphlet" again patterned after the tex section. I changed the default file extension from ".stex" to ".smml".

To the "sectionoutput" table I added the line

```
mathml                    created output in MathML style      Off:CONSOLE
```

Added the code chunk "outputmathml" to the code chunk "output" in "sectionoutput".

Relevant code chunks:

```
outputmathml
```

Relevant variables:

```
setOutputMathml
$mathmlFormat
$mathmlOutputFile
```

Note when copying the tex stuff I changed occurrences of "tex" to "mathml", "Tex" to "Mathml" and "TeX" to "MathML".

14.6.7 File src/algebra/Makefile.pamphlet

The file "src/algebra/tex.spad.pamphlet" contains the domain **TexFormat** (TEX) and the package **TexFormat1** (TEX1). However the sole function of **TexFormat1** is to *coerce* objects from a domain into **OutputForm** and then apply **TexFormat** to them. It is to save programmers the trouble of doing the coercion themselves from inside spad code. It does not appear to be used for the main purpose of delivering Axiom output in TeX format. In order to keep the mathml package as simple as possible, and because I didn't see much use for this, I didn't copy the **TexFormat1** package. So no analog of the TEX1 entries in "Makefile.pamphlet" were needed. One curiosity I don't understand is why TEX1 appears in layer 4 when it seems to depend on TEX which appears in layer 14.

Initially I added "$OUT/MMLFORM.o" to layer 14 and "mathml.spad.pamphlet" to completed spad files in layer 14. When trying to compile the build failed at MMLFORM. It left "MMLFORM.erlib" in "int/algebra" instead of "MMLFORM.NRLIB" which confused me at first because mathml.spad compiled under a running axiom. By examining the file "obj/tmp/trace" I saw that a new dependency had been introduced, compared to TexFormat, with the function eltName depending on the domain FSAGG in layer 16. So the lines had to be moved from layer 14 to layer 17.

Added appropriate lines to "SPADFILES" and "DOCFILES".

14.6.8 File src/algebra/exposed.lsp.pamphlet

Add the line "(|MathMLFormat| . MMLFORM)"

14.6.9 File src/algebra/Lattice.pamphlet

I don't see that this file is used anywhere but I made the appropriate changes anyway by searching for "TEX" and mimicing everything for MMLFORM.

14.6.10 File src/doc/axiom.bib.pamphlet

Added mathml.spad subsection to "src/doc/axiom.bib.pamphlet".

14.6.11 File interp/i-output.boot.pamphlet

This is where the *coerce* and *display* functions from MathMLFormat actually get called. The following was added:

```
mathmlFormat expr ==
  mml := '(MathMLFormat)
  mmlrep := '(String)
  formatFn := getFunctionFromDomain("coerce",mml,[$OutputForm])
  displayFn := getFunctionFromDomain("display",mml,[mmlrep])
  SPADCALL(SPADCALL(expr,formatFn),displayFn)
  TERPRI $mathmlOutputStream
  FORCE_-OUTPUT $mathmlOutputStream
  NIL
```

Note that compared to the texFormat function there are a couple of differences. Since **MathMLFormat** is currently a package rather than a domain there is the "mmlrep" variable whereas in texFormat the argument of the "display" function is an instance of the domain. Also the *coerce* function here only has one argument, namely "$OutputForm".

Also for the function "output(expr,domain)" add lines for mathml, e.g. "if $mathmlFormat then mathmlFormat expr".

After these changes Axiom compiled with mathml enabled under)set output.

14.6.12 Public Declarations

The declarations

```
  E      ==> OutputForm
  I      ==> Integer
  L      ==> List
  S      ==> String
  US     ==> UniversalSegment(Integer)
```

provide abbreviations for domains used heavily in the code. The publicly exposed functions are:

coerce: E -> S This function is the main one for converting an expression in domain OutputForm into a MathML string.

coerceS: E -> S This function is for use from the command line. It converts an OutputForm expression into a MathML string and does some formatting so that the output is not one long line. If you take the output from this function, stick it in an emacs buffer in nxml-mode

and then indent according to mode, you'll get something that's nicer to look at than what comes from coerce. Note that coerceS returns the same value as coerce but invokes a display function as well so that the result will be printed twice in different formats. The need for this is that the output from coerce is automatically formatted with line breaks by Axiom's output routine that are not in the right place.

coerceL: E -> S Similar to coerceS except that the displayed result is the MathML string in one long line. These functions can be used, for instance, to get the MathML for the previous result by typing coerceL(

exprex: E -> S Converts **OutputForm** to **String** with the structure preserved with braces. This is useful in developing this package. Actually this is not quite accurate. The function *precondition* is first applied to the **OutputForm** expression before *exprex*. Raw **OutputForm** and the nature of the *precondition* function is still obscure to me at the time of this writing (2007-02-14), however I probably need to understand it to make sure I'm not missing any semantics. The spad function *precondition* is just a wrapper for the lisp function outputTran$Lisp, which I guess is compiled from boot.

display: S -> Void This one prints the string returned by coerce as one long line, adding "math" tags: $...$. Thus the output from this can be stuck directly into an appropriate html/xhtml page and will be displayed nicely by a MathML aware browser.

displayF: S -> Void This function doesn't exist yet but it would be nice to have a humanly readable formatted output as well. The basics do exist in the coerceS function however the formatting still needs some work to be really good.

— public declarations —

```
)abbrev domain MMLFORM MathMLFormat
++ Author: Arthur C. Ralfs
++ Date: January 2007
++ Basic Operations: coerce, coerceS, coerceL, exprex, display
++ Description:
++ This package is based on the TeXFormat domain by Robert S. Sutor
++ \spadtype{MathMLFormat} provides a coercion from \spadtype{OutputForm}
++ to MathML format.

MathMLFormat(): public == private where
  E      ==> OutputForm
  I      ==> Integer
  L      ==> List
  S      ==> String
  US     ==> UniversalSegment(Integer)

  public == SetCategory with
    coerce:    E -> S
      ++ coerceS(o) changes o in the standard output format to MathML
      ++ format.
    coerceS:   E -> S
      ++ coerceS(o) changes o in the standard output format to MathML
```

```
    ++ format and displays formatted result.
  coerceL:   E -> S
    ++ coerceS(o) changes o in the standard output format to MathML
    ++ format and displays result as one long string.
  exprex:    E -> S
    ++ coverts \spadtype{OutputForm} to \spadtype{String} with the
    ++ structure preserved with braces.  Actually this is not quite
    ++ accurate.  The function \spadfun{precondition} is first
    ++ applied to the
    ++ \spadtype{OutputForm} expression before \spadfun{exprex}.
    ++ The raw \spadtype{OutputForm} and
    ++ the nature of the \spadfun{precondition} function is
    ++ still obscure to me
    ++ at the time of this writing (2007-02-14).
  display:   S -> Void
    ++ prints the string returned by coerce, adding <math ...> tags.
```

———-

14.6.13 Private Constant Declarations

— private constant declarations —

```
private == add
  import OutputForm
  import Character
  import Integer
  import List OutputForm
  import List String

  -- local variable declarations and definitions

  expr: E
  prec,opPrec: I
  str:  S
  blank         : S := " \  "

  maxPrec       : I   := 1000000
  minPrec       : I   := 0

  unaryOps      : L S := ["-","^"]$(L S)
  unaryPrecs    : L I := [700,260]$(L I)

  -- the precedence of / in the following is relatively low because
  -- the bar obviates the need for parentheses.
  binaryOps     : L S := ["+->","|","**","/","<",">","=","OVER"]$(L S)
  binaryPrecs   : L I := [0,0,900, 700,400,400,400,   700]$(L I)
```

```
naryOps       : L S := ["-","+","*",blank,",",";"," ","ROW","",
   " \cr ","&","</mtd></mtr><mtr><mtd>"]$(L S)
naryPrecs     : L I := [700,700,800,  800,110,110,  0,    0, 0,
         0,  0,   0]$(L I)
naryNGOps     : L S := ["ROW","&"]$(L S)

plexOps       : L S := ["SIGMA","SIGMA2","PI","PI2","INTSIGN","INDEFINTEGRAL"]$(L S)
plexPrecs     : L I := [    700, 800,     700, 800 , 700,      700]$(L I)

specialOps    : L S := ["MATRIX","BRACKET","BRACE","CONCATB","VCONCAT",  _
                        "AGGLST","CONCAT","OVERBAR","ROOT","SUB","TAG", _
                        "SUPERSUB","ZAG","AGGSET","SC","PAREN", _
                        "SEGMENT","QUOTE","theMap","SLASH" ]

-- the next two lists provide translations for some strings for
-- which MML provides special macros.

specialStrings : L S :=
  ["cos", "cot", "csc", "log", "sec", "sin", "tan",
    "cosh", "coth", "csch", "sech", "sinh", "tanh",
      "acos","asin","atan","erf","...","$","infinity"]
specialStringsInMML : L S :=
  ["<mo>cos</mo>","<mo>cot</mo>","<mo>csc</mo>","<mo>log</mo>","<mo>sec</mo>","<mo>sin</mo>","<mo>tan</m
    "<mo>cosh</mo>","<mo>coth</mo>","<mo>csch</mo>","<mo>sech</mo>","<mo>sinh</mo>","<mo>tanh</mo>",
      "<mo>arccos</mo>","<mo>arcsin</mo>","<mo>arctan</mo>","<mo>erf</mo>","<mo>&#x2026;</mo>","<mo>$</m
```

———-

14.6.14 Private Function Declarations

These are the local functions:

addBraces:S -> S

addBrackets:S -> S

atomize:E -> L E

displayElt:S -> Void function for recursively displaying mathml nicely formatted

eltLimit:(S,I,S) -> I demarcates end postion of mathml element with name:S starting at position i:I in mathml string s:S and returns end of end tag as i:I position in mathml string, i.e. find start and end of substring: <name ...>...</name>

eltName:(I,S) -> S find name of mathml element starting at position i:I in string s:S

group:S -> S

formatBinary:(S,L E, I) -> S

formatFunction:(S,L E, I) -> S

formatMatrix:L E -> S

formatNary:(S,L E, I) -> S

formatNaryNoGroup:(S,L E, I) -> S

formatNullary:S -> S

formatPlex:(S,L E, I) -> S

formatSpecial:(S,L E, I) -> S

formatUnary:(S, E, I) -> S

formatMml:(E,I) -> S

newWithNum:I -> $ this is a relic from tex.spad and is not used here so far. I'll probably remove it.

parenthesize:S -> S

precondition:E -> E this function is applied to the OutputForm expression before doing anything else.

postcondition:S -> S this function is applied after all other OutputForm -> MathML transformations. In the TexFormat domain the ungroup function first peels off the outermost set of braces however I have replaced braces with <mrow>s here and sometimes the outermost set of <mrow>s is necessary to get proper display in Firefox. For instance with getting the correct size of brackets on a matrix the whole expression needs to be enclosed in a mrow element. It also checks for +− and removes the +.

stringify:E -> S

tagEnd:(S,I,S) -> I finds closing ">" of start or end tag for mathML element for formatting MathML string for human readability. No analog in TexFormat.

ungroup:S -> S

— private function declarations —

```
-- local function signatures

addBraces:      S -> S
addBrackets:    S -> S
atomize:        E -> L E
displayElt:     S -> Void
  ++ function for recursively displaying mathml nicely formatted
eltLimit:       (S,I,S) -> I
  ++ demarcates end postion of mathml element with name:S starting at
  ++ position i:I in mathml string s:S and returns end of end tag as
  ++  i:I position in mathml string, i.e. find start and end of
  ++  substring:  <name ...>...</name>
eltName:        (I,S) -> S
  ++ find name of mathml element starting at position i:I in string s:S
group:          S -> S
formatBinary:   (S,L E, I) -> S
```

```
formatFunction: (S,L E, I) -> S
formatIntSign:  (L E, I) -> S
formatMatrix:   L E -> S
formatNary:     (S,L E, I) -> S
formatNaryNoGroup: (S,L E, I) -> S
formatNullary:  S -> S
formatPlex:     (S,L E, I) -> S
formatSpecial:  (S,L E, I) -> S
formatSub:      (E, L E, I) -> S
formatSuperSub: (E, L E, I) -> S
formatSuperSub1: (E, L E, I) -> S
formatUnary:    (S,  E, I) -> S
formatMml:      (E,I) -> S
formatZag:      L E -> S
formatZag1:     L E -> S
newWithNum:     I -> $
parenthesize:   S -> S
precondition:   E -> E
postcondition:  S -> S
stringify:      E -> S
tagEnd:         (S,I,S) -> I
  ++  finds closing ">" of start or end tag for mathML element
ungroup:        S -> S
```

———-

14.6.15 Public Function Definitions

Note that I use the function sayTeX$Lisp much as I would printf in a C program. I've noticed in grepping the code that there are other "say" functions, sayBrightly and sayMessage for instance, but I have no idea what the difference is between them at this point. sayTeX$Lisp does the job so for the time being I'll use that until I learn more.

The functions coerceS and coerceL should probably be changed to display functions, *i.e.* *displayS* and *display L*, returning Void. I really only need the one coerce function.

— public function definitions —

```
-- public function definitions

coerce(expr : E): S ==
  s : S := postcondition formatMml(precondition expr, minPrec)
  s

coerceS(expr : E): S ==
  s : S := postcondition formatMml(precondition expr, minPrec)
  sayTeX$Lisp "<math xmlns=_"http://www.w3.org/1998/Math/MathML_" mathsize=_"big_" display=_"block_">"
```

```
      displayElt(s)
      sayTeX$Lisp "</math>"
      s

    coerceL(expr : E): S ==
      s : S := postcondition formatMml(precondition expr, minPrec)
      sayTeX$Lisp "<math xmlns=_"http://www.w3.org/1998/Math/MathML_" mathsize=_"big_" display=_
      sayTeX$Lisp s
      sayTeX$Lisp "</math>"
      s

    display(mathml : S): Void ==
      sayTeX$Lisp "<math xmlns=_"http://www.w3.org/1998/Math/MathML_" mathsize=_"big_" display=_
      sayTeX$Lisp mathml
      sayTeX$Lisp "</math>"
      void()$Void



    exprex(expr : E): S ==
      -- This breaks down an expression into atoms and returns it as
      -- a string.  It's for developmental purposes to help understand
      -- the expressions.
      a : E
      expr := precondition expr
--      sayTeX$Lisp "0: "stringify expr
      (ATOM(expr)$Lisp@Boolean) or (stringify expr = "NOTHING") =>
        concat ["{",stringify expr,"}"]
      le : L E := (expr pretend L E)
      op := first le
      sop : S := exprex op
      args : L E := rest le
      nargs : I := #args
--      sayTeX$Lisp concat ["1: ",stringify first le," : ",string(nargs)$S]
      s : S := concat ["{",sop]
      if nargs > 0  then
        for a in args repeat
--        sayTeX$Lisp concat ["2: ",stringify a]
          s1 : S := exprex a
          s := concat [s,s1]
      s := concat [s,"}"]
```

———-

14.6.16 Private Function Definitions

Display Functions

displayElt(mathml:S):Void

eltName(pos:I,mathml:S):S

eltLimit(name:S,pos:I,mathml:S):I

tagEnd(name:S,pos:I,mathml:S):I

— display functions —

```
    displayElt(mathML:S): Void ==
      -- Takes a string of syntactically complete mathML
      -- and formats it for display.
--      sayTeX$Lisp "****displayElt1****"
--      sayTeX$Lisp mathML
      enT:I -- marks end of tag, e.g. "<name>"
      enE:I -- marks end of element, e.g. "<name> ... </name>"
      end:I -- marks end of mathML string
      u:US
      end := #mathML
      length:I := 60
--      sayTeX$Lisp "****displayElt1.1****"
      name:S := eltName(1,mathML)
--      sayTeX$Lisp name
--      sayTeX$Lisp concat("****displayElt1.2****",name)
      enE := eltLimit(name,2+#name,mathML)
--      sayTeX$Lisp "****displayElt2****"
      if enE < length then
--        sayTeX$Lisp "****displayElt3****"
        u := segment(1,enE)$US
        sayTeX$Lisp mathML.u
      else
--        sayTeX$Lisp "****displayElt4****"
        enT := tagEnd(name,1,mathML)
        u := segment(1,enT)$US
        sayTeX$Lisp mathML.u
        u := segment(enT+1,enE-#name-3)$US
        displayElt(mathML.u)
        u := segment(enE-#name-2,enE)$US
        sayTeX$Lisp mathML.u
      if end > enE then
--        sayTeX$Lisp "****displayElt5****"
        u := segment(enE+1,end)$US
        displayElt(mathML.u)

      void()$Void
```

```
eltName(pos:I,mathML:S): S ==
  -- Assuming pos is the position of "<" for a start tag of a mathML
  -- element finds and returns the element's name.
  i:I := pos+1
  --sayTeX$Lisp "eltName:mathmML string: "mathML
  while member?(mathML.i,lowerCase()$CharacterClass)$CharacterClass repeat
     i := i+1
  u:US := segment(pos+1,i-1)
  name:S := mathML.u

eltLimit(name:S,pos:I,mathML:S): I ==
  -- Finds the end of a mathML element like "<name ...> ... </name>"
  -- where pos is the position of the space after name in the start tag
  -- although it could point to the closing ">".  Returns the position
  -- of the ">" in the end tag.
  pI:I := pos
  startI:I
  endI:I
  startS:S := concat ["<",name]
  endS:S := concat ["</",name,">"]
  level:I := 1
  --sayTeX$Lisp "eltLimit: element name: "name
  while (level > 0) repeat
    startI := position(startS,mathML,pI)$String

    endI := position(endS,mathML,pI)$String

    if (startI = 0) then
      level := level-1
      --sayTeX$Lisp "****eltLimit 1******"
      pI := tagEnd(name,endI,mathML)
    else
      if (startI < endI) then
        level := level+1
        pI := tagEnd(name,startI,mathML)
      else
        level := level-1
        pI := tagEnd(name,endI,mathML)
  pI


tagEnd(name:S,pos:I,mathML:S):I ==
  -- Finds the closing ">" for either a start or end tag of a mathML
  -- element, so the return value is the position of ">" in mathML.
  pI:I := pos
  while  (mathML.pI ^= char ">") repeat
    pI := pI+1
  u:US := segment(pos,pI)$US
  --sayTeX$Lisp "tagEnd: "mathML.u
  pI
```

———-

Formatting Functions

Still need to format `\zag` in formatSpecial!

In formatPlex the case op = "INTSIGN" is now passed off to formatIntSign which is a change from the TexFormat domain. This is done here for presentation mark up to replace the ugly bound variable that Axiom delivers. For content mark up this has to be done anyway.

The formatPlex function also allows for op = "INDEFINTEGRAL". However I don't know what Axiom command gives rise to this case. The INTSIGN case already allows for both definite and indefinite integrals.

In the function formatSpecial various cases are handled including SUB and SUPERSUB. These cases are now caught in formatMml and so the code in formatSpecial doesn't get executed. The only cases I know of using these are partial derivatives for SUB and ordinary derivatives or SUPERSUB however in TexFormat the capability is there to handle multiscripts, i.e. an object with subscripts, superscripts, pre-subscripts and pre-superscripts but I am so far unaware of any Axiom command that produces such a multiscripted object.

Another question is how to represent derivatives. At present I have differential notation for partials and prime notation for ordinary derivatives, but it would be nice to allow for different derivative notations in different circumstances, maybe some options to)set output mathml on.

Ordinary derivatives are formatted in formatSuperSub and there are 2 versions, formatSuperSub and formatSuperSub1, which at this point have to be switched by swapping names.

— **formatting functions** —

```
atomize(expr : E): L E ==
  -- This breaks down an expression into a flat list of atomic expressions.
  -- expr should be preconditioned.
  le : L E := nil()
  a : E
  letmp : L E
  (ATOM(expr)$Lisp@Boolean) or (stringify expr = "NOTHING") =>
    le := append(le,list(expr))
  letmp := expr pretend L E
  for a in letmp repeat
    le := append(le,atomize a)
  le

ungroup(str: S): S ==
  len : I := #str
  len < 14 => str
  lrow : S :=  "<mrow>"
```

```
      rrow : S :=  "</mrow>"
      -- drop leading and trailing mrows
      u1 : US := segment(1,6)$US
      u2 : US := segment(len-6,len)$US
      if (str.u1 =$S lrow) and (str.u2 =$S rrow) then
        u : US := segment(7,len-7)$US
        str := str.u
      str

    postcondition(str: S): S ==
--      str := ungroup str
      len : I := #str
      plusminus : S := "<mo>+</mo><mo>-</mo>"
      pos : I := position(plusminus,str,1)
      if pos > 0 then
        ustart:US := segment(1,pos-1)$US
        uend:US := segment(pos+20,len)$US
        str := concat [str.ustart,"<mo>-</mo>",str.uend]
        if pos < len-18 then
          str := postcondition(str)
      str

    stringify expr == (mathObject2String$Lisp expr)@S

    group str ==
      concat ["<mrow>",str,"</mrow>"]

    addBraces str ==
      concat ["<mo>{</mo>",str,"<mo>}</mo>"]

    addBrackets str ==
      concat ["<mo>[</mo>",str,"<mo>]</mo>"]

    parenthesize str ==
      concat ["<mo>(</mo>",str,"<mo>)</mo>"]

    precondition expr ==
      outputTran$Lisp expr

    formatSpecial(op : S, args : L E, prec : I) : S ==
      arg : E
      prescript : Boolean := false
      op = "theMap" => "<mtext>theMap(...)</mtext>"
      op = "AGGLST" =>
        formatNary(",",args,prec)
      op = "AGGSET" =>
        formatNary(";",args,prec)
      op = "TAG" =>
        group concat [formatMml(first args,prec),
                      "<mo>&#x02192;</mo>",
```

```
                formatMml(second args,prec)]
              --RightArrow
op = "SLASH" =>
  group concat [formatMml(first args,prec),
    "<mo>/</mo>",formatMml(second args,prec)]
op = "VCONCAT" =>
  group concat("<mtable><mtr>",
              concat(concat([concat("<mtd>",concat(formatMml(u, minPrec),"</mtd>"))
                             for u in args]::L S),
                     "</mtr></mtable>"))
op = "CONCATB" =>
  formatNary(" ",args,prec)
op = "CONCAT" =>
  formatNary("",args,minPrec)
op = "QUOTE" =>
  group concat("<mo>'</mo>",formatMml(first args, minPrec))
op = "BRACKET" =>
  group addBrackets ungroup formatMml(first args, minPrec)
op = "BRACE" =>
  group addBraces ungroup formatMml(first args, minPrec)
op = "PAREN" =>
  group parenthesize ungroup formatMml(first args, minPrec)
op = "OVERBAR" =>
  null args => ""
  group concat ["<mover accent='true'><mrow>",_
               formatMml(first args,minPrec),_
               "</mrow><mo stretchy='true'>&#x000AF;</mo></mover>"]
  --OverBar
op = "ROOT" =>
  null args => ""
  tmp : S := group formatMml(first args, minPrec)
  null rest args => concat ["<msqrt>",tmp,"</msqrt>"]
  group concat
    ["<mroot><mrow>",tmp,"</mrow>",_
      formatMml(first rest args, minPrec),"</mroot>"]
op = "SEGMENT" =>
  tmp : S := concat [formatMml(first args, minPrec),"<mo>..</mo>"]
  group
    null rest args =>  tmp
    concat [tmp,formatMml(first rest args, minPrec)]
-- SUB should now be diverted in formatMml although I'll leave
-- the code here for now.
op = "SUB" =>
  group concat ["<msub>",formatMml(first args, minPrec),
    formatSpecial("AGGLST",rest args,minPrec),"</msub>"]
-- SUPERSUB should now be diverted in formatMml although I'll leave
-- the code here for now.
op = "SUPERSUB" =>
  base:S := formatMml(first args, minPrec)
  args := rest args
```

```
        if #args = 1 then
           "<msub><mrow>"base"</mrow><mrow>"_
            formatMml(first args, minPrec)"</mrow></msub>"
        else if #args = 2 then
        -- it would be nice to substitue &#x2032; for , in the case of
        -- an ordinary derivative, it looks a lot better.
          "<msubsup><mrow>"base"</mrow><mrow>"_
           formatMml(first args,minPrec)_
            "</mrow><mrow>"_
             formatMml(first rest args, minPrec)_
              "</mrow></msubsup>"
        else if #args = 3 then
          "<mmultiscripts><mrow>"base"</mrow><mrow>"_
           formatMml(first args,minPrec)"</mrow><mrow>"_
            formatMml(first rest args,minPrec)"</mrow><mprescripts/><mrow>"_
             formatMml(first rest rest args,minPrec)_
              "</mrow><none/></mmultiscripts>"
        else if #args = 4 then
         "<mmultiscripts><mrow>"base"</mrow><mrow>"_
           formatMml(first args,minPrec)"</mrow><mrow>"_
            formatMml(first rest args,minPrec)"</mrow><mprescripts/><mrow>"_
             formatMml(first rest rest args,minPrec)_
              "</mrow><mrow>"formatMml(first rest rest rest args,minPrec)_
               "</mrow></mmultiscripts>"
        else
          "<mtext>Problem with multiscript object</mtext>"
      op = "SC" =>
        -- need to handle indentation someday
        null args => ""
        tmp := formatNaryNoGroup("</mtd></mtr><mtr><mtd>", args, minPrec)
        group concat ["<mtable><mtr><mtd>",tmp,"</mtd></mtr></mtable>"]
      op = "MATRIX" => formatMatrix rest args
      op = "ZAG" =>
-- {{+}{3}{{ZAG}{1}{7}}{{ZAG}{1}{15}}{{ZAG}{1}{1}}
-- {{ZAG}{1}{25}}{{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
-- to format continued fraction traditionally need to intercept it at the
-- formatNary of the "+"
        concat [" \zag{",formatMml(first args, minPrec),"}{",
          formatMml(first rest args,minPrec),"}"]
      concat ["<mtext>not done yet for: ",op,"</mtext>"]

    formatSub(expr : E, args : L E, opPrec : I) : S ==
      -- This one produces differential notation partial derivatives.
      -- It doesn't work in all cases and may not be workable, use
      -- formatSub1 below for now.
      -- At this time this is only to handle partial derivatives.
      -- If the SUB case handles anything else I'm not aware of it.
      -- This an example of the 4th partial of y(x,z) w.r.t. x,x,z,x
      -- {{{SUB}{y}{{CONCAT}{{CONCAT}{{CONCAT}{{CONCAT}{,}{1}}
      -- {{CONCAT}{,}{1}}}{{CONCAT}{,}{2}}}{{CONCAT}{,}{1}}}}{x}{z}}
```

```
      atomE : L E := atomize(expr)
      op : S := stringify first atomE
      op ^= "SUB" => "<mtext>Mistake in formatSub: no SUB</mtext>"
      stringify first rest rest atomE ^= "CONCAT" => _
         "<mtext>Mistake in formatSub: no CONCAT</mtext>"
      -- expecting form for atomE like
      --[{SUB}{func}{CONCAT}...{CONCAT}{,}{n}{CONCAT}{,}{n}...{CONCAT}{,}{n}],
      --counting the first CONCATs before the comma gives the number of
      --derivatives
      ndiffs : I := 0
      tmpLE : L E := rest rest atomE
      while stringify first tmpLE = "CONCAT" repeat
        ndiffs := ndiffs+1
        tmpLE := rest tmpLE
      numLS : L S := nil
      i : I := 1
      while i < ndiffs repeat
        numLS := append(numLS,list(stringify first rest tmpLE))
        tmpLE := rest rest rest tmpLE
        i := i+1
      numLS := append(numLS,list(stringify first rest tmpLE))
      -- numLS contains the numbers of the bound variables as strings
      -- for the differentiations, thus for the differentiation [x,x,z,x]
      -- for y(x,z) numLS = ["1","1","2","1"]
      posLS : L S := nil
      i := 0
--    sayTeX$Lisp "formatSub: nargs = "string(#args)
      while i < #args repeat
        posLS := append(posLS,list(string(i+1)))
        i := i+1
      -- posLS contains the positions of the bound variables in args
      -- as a list of strings, e.g. for the above example ["1","2"]
      tmpS: S := stringify atomE.2
      if ndiffs = 1 then
        s : S := "<mfrac><mo>&#x02202;</mo><mi>"tmpS"</mi><mrow>"
      else
        s : S := "<mfrac><mrow><msup><mo>&#x02202;</mo><mn>"string(ndiffs)"</mn></msup><mi>"tmpS"</mi></mrow
      -- need to find the order of the differentiation w.r.t. the i-th
      -- variable
      i := 1
      j : I
      k : I
      tmpS: S
      while i < #posLS+1 repeat
        j := 0
        k := 1
        while k < #numLS + 1 repeat
          if numLS.k = string i then j := j + 1
          k := k+1
        if j > 0 then
```

```
        tmpS := stringify args.i
        if j = 1 then
          s := s"<mo>&#x02202;</mo><mi>"tmpS"</mi>"
        else
          s := s"<mo>&#x02202;</mo><msup><mi>"tmpS_
                "</mi><mn>"string(j)"</mn></msup>"
      i := i + 1
    s := s"</mrow></mfrac><mo>(</mo>"
    i := 1
    while i < #posLS+1 repeat
      tmpS := stringify args.i
      s := s"<mi>"tmpS"</mi>"
      if i < #posLS then s := s"<mo>,</mo>"
      i := i+1
    s := s"<mo>)</mo>"

  formatSub1(expr : E, args : L E, opPrec : I) : S ==
    -- This one produces partial derivatives notated by ",n" as
    -- subscripts.
    -- At this time this is only to handle partial derivatives.
    -- If the SUB case handles anything else I'm not aware of it.
    -- This an example of the 4th partial of y(x,z) w.r.t. x,x,z,x
    -- {{{SUB}{y}{{CONCAT}{{CONCAT}{{CONCAT}{{CONCAT}{,}{1}}
    -- {{CONCAT}{,}{1}}}}{{CONCAT}{,}{2}}}}{{CONCAT}{,}{1}}}}{x}{z}},
    -- here expr is everything in the first set of braces and
    -- args is {{x}{z}}
    atomE : L E := atomize(expr)
    op : S := stringify first atomE
    op ^= "SUB" => "<mtext>Mistake in formatSub: no SUB</mtext>"
    stringify first rest rest atomE ^= "CONCAT" => "<mtext>Mistake in formatSub: no CONCAT</mt
    -- expecting form for atomE like
    --[{SUB}{func}{CONCAT}...{CONCAT}{,}{n}{CONCAT}{,}{n}...{CONCAT}{,}{n}],
    --counting the first CONCATs before the comma gives the number of
    --derivatives
    ndiffs : I := 0
    tmpLE : L E := rest rest atomE
    while stringify first tmpLE = "CONCAT" repeat
      ndiffs := ndiffs+1
      tmpLE := rest tmpLE
    numLS : L S := nil
    i : I := 1
    while i < ndiffs repeat
      numLS := append(numLS,list(stringify first rest tmpLE))
      tmpLE := rest rest rest tmpLE
      i := i+1
    numLS := append(numLS,list(stringify first rest tmpLE))
    -- numLS contains the numbers of the bound variables as strings
    -- for the differentiations, thus for the differentiation [x,x,z,x]
    -- for y(x,z) numLS = ["1","1","2","1"]
    posLS : L S := nil
```

```
      i := 0
 --     sayTeX$Lisp "formatSub: nargs = "string(#args)
      while i < #args repeat
        posLS := append(posLS,list(string(i+1)))
        i := i+1
      -- posLS contains the positions of the bound variables in args
      -- as a list of strings, e.g. for the above example ["1","2"]
      funcS: S := stringify atomE.2
      s : S := "<msub><mi>"funcS"</mi><mrow>"
      i := 1
      while i < #numLS+1 repeat
        s := s"<mo>,</mo><mn>"numLS.i"</mn>"
        i := i + 1
      s := s"</mrow></msub><mo>(</mo>"
      i := 1
      while i < #posLS+1 repeat
--        tmpS := stringify args.i
        tmpS := formatMml(first args,minPrec)
        args := rest args
        s := s"<mi>"tmpS"</mi>"
        if i < #posLS then s := s"<mo>,</mo>"
        i := i+1
      s := s"<mo>)</mo>"

    formatSuperSub(expr : E, args : L E, opPrec : I) : S ==
      -- this produces prime notation ordinary derivatives.
      -- first have to divine the semantics, add cases as needed
--      WriteLine$Lisp "SuperSub1 begin"
      atomE : L E := atomize(expr)
      op : S := stringify first atomE
--      WriteLine$Lisp "op: "op
      op ^= "SUPERSUB" => _
          "<mtext>Mistake in formatSuperSub: no SUPERSUB1</mtext>"
      #args ^= 1 => "<mtext>Mistake in SuperSub1: #args <> 1</mtext>"
      var : E := first args
      -- should be looking at something like {{SUPERSUB}{var}{ }{,,...,}} for
      -- example here's the second derivative of y w.r.t. x
      -- {{{SUPERSUB}{y}{ }{,,}}{x}}, expr is the first {} and args is the
      -- {x}
      funcS : S := stringify first rest atomE
--      WriteLine$Lisp "funcS: "funcS
      bvarS : S := stringify first args
--      WriteLine$Lisp "bvarS: "bvarS
      -- count the number of commas
      commaS : S := stringify first rest rest rest atomE
      commaTest : S := ","
      i : I := 0
      while position(commaTest,commaS,1) > 0 repeat
        i := i+1
        commaTest := commaTest","
```

```
      s : S := "<msup><mi>"funcS"</mi><mrow>"
--      WriteLine$Lisp "s: "s
      j : I := 0
      while j < i repeat
        s := s"<mo>&#x02032;</mo>"
        j := j + 1
      s := s"</mrow></msup><mo>&#x02061;</mo><mo>(</mo>"_
           formatMml(first args,minPrec)"<mo>)</mo>"

    formatSuperSub1(expr : E, args : L E, opPrec : I) : S ==
      -- This one produces ordinary derivatives with differential notation,
      -- it needs a little more work yet.
      -- first have to divine the semantics, add cases as needed
--      WriteLine$Lisp "SuperSub begin"
      atomE : L E := atomize(expr)
      op : S := stringify first atomE
      op ^= "SUPERSUB" => _
         "<mtext>Mistake in formatSuperSub: no SUPERSUB</mtext>"
      #args ^= 1 => "<mtext>Mistake in SuperSub: #args <> 1</mtext>"
      var : E := first args
      -- should be looking at something like {{SUPERSUB}{var}{ }{,,...,}} for
      -- example here's the second derivative of y w.r.t. x
      -- {{{SUPERSUB}{y}{ }{,,}}{x}}, expr is the first {} and args is the
      -- {x}
      funcS : S := stringify first rest atomE
      bvarS : S := stringify first args
      -- count the number of commas
      commaS : S := stringify first rest rest rest atomE
      commaTest : S := ","
      ndiffs : I := 0
      while position(commaTest,commaS,1) > 0 repeat
        ndiffs := ndiffs+1
        commaTest := commaTest","
      s : S := "<mfrac><mrow><msup><mo>&#x02146;</mo><mn>"string(ndiffs)_
       "</mn></msup><mi>"funcS"</mi></mrow><mrow><mo>&#x02146;</mo><msup><mi>"_
        formatMml(first args,minPrec)"</mi><mn>"string(ndiffs)_
         "</mn></msup></mrow></mfrac><mo>&#x02061;</mo><mo>(</mo><mi>"_
          formatMml(first args,minPrec)"</mi><mo>)</mo>"

    formatPlex(op : S, args : L E, prec : I) : S ==
      checkarg:Boolean := false
      hold : S
      p : I := position(op,plexOps)
      p < 1 => error "unknown plex op"
      op = "INTSIGN" => formatIntSign(args,minPrec)
      opPrec := plexPrecs.p
      n : I := #args
      (n ^= 2) and (n ^= 3) => error "wrong number of arguments for plex"
      s : S :=
        op = "SIGMA"   =>
```

```
         checkarg := true
         "<mo>&#x02211;</mo>"
        -- Sum
        op = "SIGMA2"   =>
         checkarg := true
         "<mo>&#x02211;</mo>"
        -- Sum
        op = "PI"      =>
         checkarg := true
         "<mo>&#x0220F;</mo>"
        -- Product
        op = "PI2"     =>
         checkarg := true
         "<mo>&#x0220F;</mo>"
        -- Product
--        op = "INTSIGN" => "<mo>&#x0222B;</mo>"
        -- Integral, int
        op = "INDEFINTEGRAL" => "<mo>&#x0222B;</mo>"
        -- Integral, int
        "????"
      hold := formatMml(first args,minPrec)
      args := rest args
      if op ^= "INDEFINTEGRAL" then
        if hold ^= "" then
          s := concat ["<munderover>",s,group hold]
        else
          s := concat ["<munderover>",s,group " "]
        if not null rest args then
          hold := formatMml(first args,minPrec)
          if hold ^= "" then
            s := concat [s,group hold,"</munderover>"]
          else
            s := concat [s,group " ","</munderover>"]
          args := rest args
        -- if checkarg true need to test op arg for "+" at least
        -- and wrap parentheses if so
        if checkarg then
          la : L E := (first args pretend L E)
          opa : S := stringify first la
          if opa = "+" then
            s :=
              concat [s,"<mo>(</mo>",formatMml(first args,minPrec),"<mo>)</mo>"]
          else s := concat [s,formatMml(first args,minPrec)]
        else s := concat [s,formatMml(first args,minPrec)]
      else
        hold := group concat [hold,formatMml(first args,minPrec)]
        s := concat [s,hold]
--      if opPrec < prec then s := parenthesize s
-- getting ugly parentheses on fractions
      group s
```

```
formatIntSign(args : L E, opPrec : I) : S ==
  -- the original OutputForm expression looks something like this:
  -- {{INTSIGN}{NOTHING or lower limit?}
  -- {bvar or upper limit?}{{*}{integrand}{{CONCAT}{d}{axiom var}}}}
  -- the args list passed here consists of the rest of this list, i.e.
  -- starting at the NOTHING or ...
  (stringify first args) = "NOTHING" =>
    -- the bound variable is the second one in the argument list
    bvar : E := first rest args
    bvarS : S := stringify bvar
    tmpS : S
    i : I := 0
    u1 : US
    u2 : US
    -- this next one atomizes the integrand plus differential
    atomE : L E := atomize(first rest rest args)
    -- pick out the bound variable used by axiom
    varRS : S := stringify last(atomE)
    tmpLE : L E := ((first rest rest args) pretend L E)
    integrand : S := formatMml(first rest tmpLE,minPrec)
    -- replace the bound variable, i.e. axiom uses someting of the form
    -- %A for the bound variable and puts the original variable used
    -- in the input command as a superscript on the integral sign.
    -- I'm assuming that the axiom variable is 2 characters.
    while (i := position(varRS,integrand,i+1)) > 0 repeat
      u1 := segment(1,i-1)$US
      u2 := segment(i+2,#integrand)$US
      integrand := concat [integrand.u1,bvarS,integrand.u2]
    concat ["<mrow><mo>&#x0222B;</mo>" integrand _
            "<mo>&#x02146;</mo><mi>" bvarS "</mi></mrow>"]

  lowlim : S := stringify first args
  highlim : S := stringify first rest args
  bvar : E := last atomize(first rest rest args)
  bvarS : S := stringify bvar
  tmpLE : L E := ((first rest rest args) pretend L E)
  integrand : S := formatMml(first rest tmpLE,minPrec)
  concat ["<mrow><munderover><mo>&#x0222B;</mo><mi>" lowlim "</mi><mi>" highlim "</mi></mund


formatMatrix(args : L E) : S ==
  -- format for args is [[ROW ...],[ROW ...],[ROW ...]]
  -- generate string for formatting columns (centered)
  group addBrackets concat
    ["<mtable><mtr><mtd>",formatNaryNoGroup("</mtd></mtr><mtr><mtd>",args,minPrec),
      "</mtd></mtr></mtable>"]

formatFunction(op : S, args : L E, prec : I) : S ==
  group concat ["<mo>",op,"</mo>",parenthesize formatNary(",",args,minPrec)]
```

```
    formatNullary(op : S) ==
      op = "NOTHING" => ""
      group concat ["<mo>",op,"</mo><mo>(</mo><mo>)</mo>"]

    formatUnary(op : S, arg : E, prec : I) ==
      p : I := position(op,unaryOps)
      p < 1 => error "unknown unary op"
      opPrec := unaryPrecs.p
      s : S := concat ["<mo>",op,"</mo>",formatMml(arg,opPrec)]
      opPrec < prec => group parenthesize s
      op = "-" => s
      group s

    formatBinary(op : S, args : L E, prec : I) : S ==
      p : I := position(op,binaryOps)
      p < 1 => error "unknown binary op"
      opPrec := binaryPrecs.p
      -- if base op is product or sum need to add parentheses
      if ATOM(first args)$Lisp@Boolean then
        opa:S := stringify first args
      else
        la : L E := (first args pretend L E)
        opa : S := stringify first la
      if (opa = "SIGMA" or opa = "SIGMA2" or opa = "PI" or opa = "PI2") _
         and op = "**" then
        s1:S:=concat ["<mo>(</mo>",formatMml(first args, opPrec),"<mo>)</mo>"]
      else
       s1 : S := formatMml(first args, opPrec)
      s2 : S := formatMml(first rest args, opPrec)
      op :=
        op = "|"     =>  s := concat ["<mrow>",s1,"</mrow><mo>",op,"</mo><mrow>",s2,"</mrow>"]
        op = "**"    =>  s := concat ["<msup><mrow>",s1,"</mrow><mrow>",s2,"</mrow></msup>"]
        op = "/"     =>  s := concat ["<mfrac><mrow>",s1,"</mrow><mrow>",s2,"</mrow></mfrac>"]
        op = "OVER"  =>  s := concat ["<mfrac><mrow>",s1,"</mrow><mrow>",s2,"</mrow></mfrac>"]
        op = "+->"   =>  s := concat ["<mrow>",s1,"</mrow><mo>",op,"</mo><mrow>",s2,"</mrow>"]
        s := concat ["<mrow>",s1,"</mrow><mo>",op,"</mo><mrow>",s2,"</mrow>"]
      group
        op = "OVER" => s
--        opPrec < prec => parenthesize s
-- ugly parentheses?
        s

    formatNary(op : S, args : L E, prec : I) : S ==
      group formatNaryNoGroup(op, args, prec)

    formatNaryNoGroup(op : S, args : L E, prec : I) : S ==
      checkargs:Boolean := false
      null args => ""
      p : I := position(op,naryOps)
```

```
      p < 1 => error "unknown nary op"
      -- need to test for "ZAG" case and divert it here
      -- ex 1. continuedFraction(314159/100000)
      -- {{+}{3}{{ZAG}{1}{7}}{{ZAG}{1}{15}}{{ZAG}{1}{1}}{{ZAG}{1}{25}}
      -- {{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
      -- this is the preconditioned output form
      -- including "op", the args list would be the rest of this
      -- i.e op = '+' and args = {{3}{{ZAG}{1}{7}}{{ZAG}{1}{15}}
      -- {{ZAG}{1}{1}}{{ZAG}{1}{25}}{{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
      -- ex 2. continuedFraction(14159/100000)
      -- this one doesn't have the leading integer
      -- {{+}{{ZAG}{1}{7}}{{ZAG}{1}{15}}{{ZAG}{1}{1}}{{ZAG}{1}{25}}
      -- {{ZAG}{1}{1}}{{ZAG}{1}{7}}{{ZAG}{1}{4}}}
      --
      -- ex 3. continuedFraction(3,repeating [1], repeating [3,6])
      -- {{+}{3}{{ZAG}{1}{3}}{{ZAG}{1}{6}}{{ZAG}{1}{3}}{{ZAG}{1}{6}}
      -- {{ZAG}{1}{3}}{{ZAG}{1}{6}}{{ZAG}{1}{3}}{{ZAG}{1}{6}}
      -- {{ZAG}{1}{3}}{{ZAG}{1}{6}}{...}}
      -- In each of these examples the args list consists of the terms
      -- following the '+' op
      -- so the first arg could be a "ZAG" or something
      -- else, but the second arg looks like it has to be "ZAG", so maybe
      -- test for #args > 1 and args.2 contains "ZAG".
      -- Note that since the resulting MathML <mfrac>s are nested we need
      -- to handle the whole continued fraction at once, i.e. we can't
      -- just look for, e.g., {{ZAG}{1}{6}}
      (#args > 1) and (position("ZAG",stringify first rest args,1) > 0) =>
           tmpS : S := stringify first args
           position("ZAG",tmpS,1) > 0 => formatZag(args)
--         position("ZAG",tmpS,1) > 0 => formatZag1(args)
           concat [formatMml(first args,minPrec) "<mo>+</mo>" _
                   formatZag(rest args)]
      -- At least for the ops "*","+","-" we need to test to see if a sigma
      -- or pi is one of their arguments because we might need parentheses
      -- as indicated by the problem with
      -- summation(operator(f)(i),i=1..n)+1 versus
      -- summation(operator(f)(i)+1,i=1..n) having identical displays as
      -- of 2007-21-21
      op :=
        op = ","     => "<mo>,</mo>" --originally , \:
        op = ";"     => "<mo>;</mo>" --originally ; \: should figure these out
        op = "*"     => "<mspace width='0.3em'/>"
        -- InvisibleTimes
        op = " "     => "<mspace width='0.5em'/>"
        op = "ROW"   => "</mtd><mtd>"
        op = "+"     =>
            checkargs := true
            "<mo>+</mo>"
        op = "-"     =>
            checkargs := true
```

```
            "<mo>-</mo>"
        op
      l : L S := nil
      opPrec := naryPrecs.p
      -- if checkargs is true check each arg except last one to see if it's
      -- a sigma or pi and if so add parentheses. Other op's may have to be
      -- checked for in future
      count:I := 1
      for a in args repeat
--        WriteLine$Lisp "checking args"
        if checkargs then
          if count < #args then
            -- check here for sum or product
            if ATOM(a)$Lisp@Boolean then
              opa:S := stringify a
            else
              la : L E := (a pretend L E)
              opa : S := stringify first la
            if opa = "SIGMA" or opa = "SIGMA2" or _
               opa = "PI" or opa = "PI2" then
              l := concat(op,concat(_
                    concat ["<mo>(</mo>",formatMml(a,opPrec),_
                            "<mo>)</mo>"],l)$L(S))$L(S)
            else l := concat(op,concat(formatMml(a,opPrec),l)$L(S))$L(S)
          else l := concat(op,concat(formatMml(a,opPrec),l)$L(S))$L(S)
        else l := concat(op,concat(formatMml(a,opPrec),l)$L(S))$L(S)
        count := count + 1
      s : S := concat reverse rest l
      opPrec < prec => parenthesize s
      s

    formatZag(args : L E) : S ==
    -- args will be a list of things like this {{ZAG}{1}{7}}, the ZAG
    -- must be there, the '1' and '7' could conceivably be more complex
    -- expressions
      tmpZag : L E := first args pretend L E
      -- may want to test that tmpZag contains 'ZAG'
      #args > 1 => "<mfrac>"formatMml(first rest tmpZag,minPrec)"<mrow><mn>"formatMml(first rest rest tmpZag
      -- EQUAL(tmpZag, "...")$Lisp => "<mo>&#x2026;</mo>"
      (first args = "..."::E)@Boolean => "<mo>&#x2026;</mo>"
      position("ZAG",stringify first args,1) > 0 =>
          "<mfrac>"formatMml(first rest tmpZag,minPrec)formatMml(first rest rest tmpZag,minPrec)"</mfrac>"
      "<mtext>formatZag: Unexpected kind of ZAG</mtext>"


    formatZag1(args : L E) : S ==
    -- make alternative ZAG format without diminishing fonts, maybe
    -- use a table
    -- {{ZAG}{1}{7}}
      tmpZag : L E := first args pretend L E
```

```
    #args > 1 => "<mfrac>"formatMml(first rest tmpZag,minPrec)"<mrow><mn>"formatMml(first rest
    (first args = "...":: E)@Boolean => "<mo>&#x2026;</mo>"
    error "formatZag1: Unexpected kind of ZAG"


  formatMml(expr : E,prec : I) ==
    i,len : Integer
    intSplitLen : Integer := 20
    ATOM(expr)$Lisp@Boolean =>
      str := stringify expr
      len := #str
      -- this bit seems to deal with integers
      INTEGERP$Lisp expr =>
        i := expr pretend Integer
        if (i < 0) or (i > 9)
          then
            group
               nstr : String := ""
               -- insert some blanks into the string, if too long
               while ((len := #str) > intSplitLen) repeat
                 nstr := concat [nstr," ",
                   elt(str,segment(1,intSplitLen)$US)]
                 str := elt(str,segment(intSplitLen+1)$US)
               empty? nstr => concat ["<mn>",str,"</mn>"]
               nstr :=
                 empty? str => nstr
                 concat [nstr," ",str]
               concat ["<mn>",elt(nstr,segment(2)$US),"</mn>"]
          else str := concat ["<mn>",str,"</mn>"]
      str = "%pi" => "<mi>&#x003C0;</mi>"
      -- pi
      str = "%e"  => "<mi>&#x02147;</mi>"
      -- ExponentialE
      str = "%i"  => "<mi>&#x02148;</mi>"
      -- ImaginaryI
      len > 0 and str.1 = char "%" => concat(concat("<mi>",str),"</mi>")
       -- should handle floats
      len > 1 and digit? str.1 => concat ["<mn>",str,"</mn>"]
      -- presumably this is a literal string
      len > 0 and str.1 = char "_"" =>
        concat(concat("<mtext>",str),"</mtext>")
      len = 1 and str.1 = char " " => " "
      (i := position(str,specialStrings)) > 0 =>
        specialStringsInMML.i
      (i := position(char " ",str)) > 0 =>
        -- We want to preserve spacing, so use a roman font.
        -- What's this for?  Leave the \rm in for now so I can see
        -- where it arises.  Removed 2007-02-14
        concat(concat("<mtext>",str),"</mtext>")
      -- if we get to here does that mean it's a variable?
```

```
      concat ["<mi>",str,"</mi>"]
    l : L E := (expr pretend L E)
    null l => blank
    op : S := stringify first l
    args : L E := rest l
    nargs : I := #args
    -- need to test here in case first l is SUPERSUB case and then
    -- pass first l and args to formatSuperSub.
    position("SUPERSUB",op,1) > 0 =>
      formatSuperSub(first l,args,minPrec)
    -- now test for SUB
    position("SUB",op,1) > 0 =>
      formatSub1(first l,args,minPrec)

    -- special cases
    member?(op, specialOps) => formatSpecial(op,args,prec)
    member?(op, plexOps)    => formatPlex(op,args,prec)

    -- nullary case
    0 = nargs => formatNullary op

    -- unary case
    (1 = nargs) and member?(op, unaryOps) =>
      formatUnary(op, first args, prec)

    -- binary case
    (2 = nargs) and member?(op, binaryOps) =>
      formatBinary(op, args, prec)

    -- nary case
    member?(op,naryNGOps) => formatNaryNoGroup(op,args, prec)
    member?(op,naryOps) => formatNary(op,args, prec)

    op := formatMml(first l,minPrec)
    formatFunction(op,args,prec)
```

———-

14.6.17 Mathematical Markup Language Form

— MathMLFormat.input —

```
)set break resume
)spool MathMLFormat.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 5
)set output mathml on

--R
--E 1

--S 2 of 5
1/2
--R
--R
--R        1
--R   (1)  -
--R        2
--R<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big" display="block">
--R<mrow><mfrac><mrow><mn>1</mn></mrow><mrow><mn>2</mn></mrow></mfrac></mrow>
--R</math>
--R
--R                                                    Type: Fraction Integer
--E 2

--S 3 of 5
1/(x+5)
--R
--R
--R          1
--R   (2)  -----
--R        x + 5
--R<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big" display="block">
--R<mrow><mfrac><mrow><mn>1</mn></mrow><mrow><mrow><mi>x</mi><mo>+</mo><mn>5</mn></mrow></mrow><
--R</math>
--R
--R                                          Type: Fraction Polynomial Integer
--E 3

--S 4 of 5
(x+3)/(y-5)
--R
--R
--R        x + 3
--R   (3)  -----
--R        y - 5
--R<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big" display="block">
--R<mrow><mfrac><mrow><mrow><mi>x</mi><mo>+</mo><mn>3</mn></mrow></mrow><mrow><mrow><mi>y</mi><m
--R</math>
--R
--R                                          Type: Fraction Polynomial Integer
--E 4

--S 5 of 5
```

```
)show MathMLFormat
--R MathMLFormat  is a domain constructor
--R Abbreviation for MathMLFormat is MMLFORM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MMLFORM
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : OutputForm -> String
--R coerce : % -> OutputForm             coerceL : OutputForm -> String
--R coerceS : OutputForm -> String       display : String -> Void
--R exprex : OutputForm -> String        hash : % -> SingleInteger
--R latex : % -> String                  ?~=? : (%,%) -> Boolean
--R
--E 5

)spool
)lisp (bye)
```

———-

— MathMLFormat.help —

```
========================================================================
MathMLFormat examples
========================================================================

MathML is an HTML-like markup language for mathematics. It uses the
"knuckle" syntax of HTML such as "<mo>" to introduce a math operator
and "</mo>" to mark the end of the operator. Axiom can generate
MathML output and does so when it communicates to the browser front end.

This output is enabled by

  )set output mathml on

after which you'll see the MathML markup as well as the algebra.
Note that you can turn off the algebra output with

  )set output algebra off

but we don't do that here so you can compare the output.

  1/2

    1/2

  <math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big"
        display="block">
```

```
 <mrow>
  <mn>1</mn>
  <mo>/</mo>
  <mn>2</mn>
 </mrow>
</math>


1/(x+5)

  1/(x + 5)

<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big"
      display="block">
 <mrow>
  <mn>1</mn>
  <mo>/</mo>
  <mrow>
   <mo>(</mo>
   <mi>x</mi>
   <mo>+</mo>
   <mn>5</mn>
   <mo>)</mo>
  </mrow>
 </mrow>
</math>

(x+3)/(y-5)

   (x + 3)/(y - 5)


<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big"
      display="block">
 <mrow>
  <mrow>
   <mo>(</mo>
   <mi>x</mi>
   <mo>+</mo>
   <mn>3</mn>
   <mo>)</mo>
  </mrow>
  <mo>/</mo>
  <mrow>
   <mo>(</mo>
   <mi>y</mi>
   <mo>-</mo>
   <mn>5</mn>
   <mo>)</mo>
  </mrow>
 </mrow>
```

```
  R</math>

See Also:
o )show MathMLFormat
```

———-

14.6.18 MathMLForm (MMLFORM)



Exports:

coerce	coerceL	coerceS	display	exprex
hash	latex	?=?	?~=?	

— **domain MMLFORM MathMLFormat** —

```
\getchunk{public declarations}
\getchunk{private constant declarations}
\getchunk{private function declarations}
\getchunk{public function definitions}
\getchunk{display functions}
\getchunk{formatting functions}
```

———-

— **MMLFORM.dotabb** —

```
"MMLFORM" [color="#FF4488",href="bookvol10.4.pdf#nameddest=MMLFORM"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"MMLFORM" -> "FSAGG"
```

———-

14.7 domain MATRIX Matrix

— Matrix.input —

```
)set break resume
)sys rm -f Matrix.output
)spool Matrix.output
)set message test on
)set message auto off
)clear all
--S 1 of 38
m : Matrix(Integer) := new(3,3,0)
--R
--R
--R        +0  0  0+
--R        |       |
--R   (1)  |0  0  0|
--R        |       |
--R        +0  0  0+
--R                                                  Type: Matrix(Integer)
--E 1

--S 2 of 38
setelt(m,2,3,5)
--R
--R
--R   (2)  5
--R                                                  Type: PositiveInteger
--E 2

--S 3 of 38
m(1,2) := 10
--R
--R
--R   (3)  10
--R                                                  Type: PositiveInteger
--E 3

--S 4 of 38
m
--R
--R
--R        +0  10  0+
--R        |        |
--R   (4)  |0  0   5|
--R        |        |
--R        +0  0   0+
--R                                                  Type: Matrix(Integer)
```

```
--E 4

--S 5 of 38
matrix [ [1,2,3,4],[0,9,8,7] ]
--R
--R
--R        +1  2  3  4+
--R   (5)  |          |
--R        +0  9  8  7+
--R                                                  Type: Matrix(Integer)
--E 5

--S 6 of 38
dm := diagonalMatrix [1,x**2,x**3,x**4,x**5]
--R
--R
--R        +1  0   0   0   0 +
--R        |                 |
--R        |    2            |
--R        |0  x   0   0   0 |
--R        |                 |
--R        |        3        |
--R   (6)  |0  0   x   0   0 |
--R        |                 |
--R        |            4    |
--R        |0  0   0   x   0 |
--R        |                 |
--R        |                5|
--R        +0  0   0   0   x +
--R                                        Type: Matrix(Polynomial(Integer))
--E 6

--S 7 of 38
setRow!(dm,5,vector [1,1,1,1,1])
--R
--R
--R        +1  0   0   0   0+
--R        |                |
--R        |    2           |
--R        |0  x   0   0   0|
--R        |                |
--R   (7)  |        3       |
--R        |0  0   x   0   0|
--R        |                |
--R        |            4   |
--R        |0  0   0   x   0|
--R        |                |
--R        +1  1   1   1   1+
--R                                        Type: Matrix(Polynomial(Integer))
--E 7
```

```
--S 8 of 38
setColumn!(dm,2,vector [y,y,y,y,y])
--R
--R
--R        +1  y  0   0   0+
--R        |                |
--R        |0  y  0   0   0|
--R        |                |
--R        |       3        |
--R   (8)  |0  y  x   0   0|
--R        |                |
--R        |           4    |
--R        |0  y  0   x   0|
--R        |                |
--R        +1  y  1   1   1+
--R                                              Type: Matrix(Polynomial(Integer))
--E 8

--S 9 of 38
cdm := copy(dm)
--R
--R
--R        +1  y  0   0   0+
--R        |                |
--R        |0  y  0   0   0|
--R        |                |
--R        |       3        |
--R   (9)  |0  y  x   0   0|
--R        |                |
--R        |           4    |
--R        |0  y  0   x   0|
--R        |                |
--R        +1  y  1   1   1+
--R                                              Type: Matrix(Polynomial(Integer))
--E 9

--S 10 of 38
setelt(dm,4,1,1-x**7)
--R
--R
--R             7
--R   (10)  - x  + 1
--R                                                     Type: Polynomial(Integer)
--E 10

--S 11 of 38
[dm,cdm]
--R
--R
```

```
--R          +   1      y  0   0   0+ +1  y  0   0   0+
--R          |                      | |               |
--R          |   0      y  0   0   0| |0  y  0   0   0|
--R          |                      | |               |
--R          |              3       | |       3       |
--R   (11)  [|   0      y  x   0   0|,|0  y  x   0   0|]
--R          |                      | |               |
--R          |   7             4    | |           4   |
--R          |- x  + 1  y  0   x   0| |0  y  0   x   0|
--R          |                      | |               |
--R          +   1      y  1   1   1+ +1  y  1   1   1+
--R                                        Type: List(Matrix(Polynomial(Integer)))
--E 11

--S 12 of 38
subMatrix(dm,2,3,2,4)
--R
--R
--R         +y  0   0+
--R   (12)  |        |
--R         |    3   |
--R         +y  x   0+
--R                                             Type: Matrix(Polynomial(Integer))
--E 12

--S 13 of 38
d := diagonalMatrix [1.2,-1.3,1.4,-1.5]
--R
--R
--R         +1.2   0.0   0.0   0.0 +
--R         |                      |
--R         |0.0  - 1.3  0.0   0.0 |
--R   (13)  |                      |
--R         |0.0   0.0   1.4   0.0 |
--R         |                      |
--R         +0.0   0.0   0.0  - 1.5+
--R                                                        Type: Matrix(Float)
--E 13

--S 14 of 38
e := matrix [ [6.7,9.11],[-31.33,67.19] ]
--R
--R
--R         +  6.7    9.11 +
--R   (14)  |              |
--R         +- 31.33  67.19+
--R                                                        Type: Matrix(Float)
--E 14

--S 15 of 38
```

```
setsubMatrix!(d,1,2,e)
--R
--R
--R         +1.2    6.7    9.11    0.0 +
--R         |                          |
--R         |0.0  - 31.33  67.19   0.0 |
--R   (15)  |                          |
--R         |0.0    0.0     1.4    0.0 |
--R         |                          |
--R         +0.0    0.0     0.0   - 1.5+
--R                                                    Type: Matrix(Float)
--E 15

--S 16 of 38
d
--R
--R
--R         +1.2    6.7    9.11    0.0 +
--R         |                          |
--R         |0.0  - 31.33  67.19   0.0 |
--R   (16)  |                          |
--R         |0.0    0.0     1.4    0.0 |
--R         |                          |
--R         +0.0    0.0     0.0   - 1.5+
--R                                                    Type: Matrix(Float)
--E 16

--S 17 of 38
a := matrix [ [1/2,1/3,1/4],[1/5,1/6,1/7] ]
--R
--R
--R         +1  1  1+
--R         |-  -  -|
--R         |2  3  4|
--R   (17)  |       |
--R         |1  1  1|
--R         |-  -  -|
--R         +5  6  7+
--R                                        Type: Matrix(Fraction(Integer))
--E 17

--S 18 of 38
b := matrix [ [3/5,3/7,3/11],[3/13,3/17,3/19] ]
--R
--R
--R         +3   3    3+
--R         |-   -   --|
--R         |5   7   11|
--R   (18)  |          |
--R         | 3   3   3|
```

```
--R         |--  --  --|
--R         +13  17  19+
--R                                                Type: Matrix(Fraction(Integer))
--E 18

--S 19 of 38
horizConcat(a,b)
--R
--R
--R         +1  1  1  3   3    3+
--R         |-  -  -  -   -   --|
--R         |2  3  4  5   7   11|
--R   (19)  |                   |
--R         |1  1  1   3   3   3|
--R         |-  -  -  --  --  --|
--R         +5  6  7  13  17  19+
--R                                                Type: Matrix(Fraction(Integer))
--E 19

--S 20 of 38
vab := vertConcat(a,b)
--R
--R
--R         +1   1   1 +
--R         |-   -   - |
--R         |2   3   4 |
--R         |          |
--R         |1   1   1 |
--R         |-   -   - |
--R         |5   6   7 |
--R   (20)  |          |
--R         |3   3    3|
--R         |-   -   --|
--R         |5   7   11|
--R         |          |
--R         | 3   3   3|
--R         |--  --  --|
--R         +13  17  19+
--R                                                Type: Matrix(Fraction(Integer))
--E 20

--S 21 of 38
transpose vab
--R
--R
--R         +1  1  3    3+
--R         |-  -  -   --|
--R         |2  5  5   13|
--R         |            |
--R         |1  1  3    3|
```

```
--R   (21)  |-  -  -   --|
--R         |3  6  7   17|
--R         |            |
--R         |1  1   3   3|
--R         |-  -  --  --|
--R         +4  7  11  19+
--R                                          Type: Matrix(Fraction(Integer))
--E 21

--S 22 of 38
m := matrix [ [1,2],[3,4] ]
--R
--R
--R         +1  2+
--R   (22)  |    |
--R         +3  4+
--R                                                Type: Matrix(Integer)
--E 22

--S 23 of 38
4 * m * (-5)
--R
--R
--R         +- 20  - 40+
--R   (23)  |          |
--R         +- 60  - 80+
--R                                                Type: Matrix(Integer)
--E 23

--S 24 of 38
n := matrix([ [1,0,-2],[-3,5,1] ])
--R
--R
--R         + 1   0  - 2+
--R   (24)  |           |
--R         +- 3  5   1 +
--R                                                Type: Matrix(Integer)
--E 24

--S 25 of 38
m * n
--R
--R
--R         +- 5  10   0 +
--R   (25)  |            |
--R         +- 9  20  - 2+
--R                                                Type: Matrix(Integer)
--E 25

--S 26 of 38
```

```
vec := column(n,3)
--R
--R
--R   (26)  [- 2,1]
--R                                                    Type: Vector(Integer)
--E 26

--S 27 of 38
vec * m
--R
--R
--R   (27)  [1,0]
--R                                                    Type: Vector(Integer)
--E 27

--S 28 of 38
m * vec
--R
--R
--R   (28)  [0,- 2]
--R                                                    Type: Vector(Integer)
--E 28

--S 29 of 38
hilb := matrix([ [1/(i + j) for i in 1..3] for j in 1..3])
--R
--R
--R         +1  1  1+
--R         |-  -  -|
--R         |2  3  4|
--R         |       |
--R         |1  1  1|
--R   (29)  |-  -  -|
--R         |3  4  5|
--R         |       |
--R         |1  1  1|
--R         |-  -  -|
--R         +4  5  6+
--R                                        Type: Matrix(Fraction(Integer))
--E 29

--S 30 of 38
inverse(hilb)
--R
--R
--R         + 72    - 240   180 +
--R         |                   |
--R   (30)  |- 240   900   - 720|
--R         |                   |
--R         + 180   - 720   600 +
```

```
--R                                    Type: Union(Matrix(Fraction(Integer)),...)
--E 30

--S 31 of 38
mm := matrix([ [1,2,3,4], [5,6,7,8], [9,10,11,12], [13,14,15,16] ])
--R
--R
--R         +1   2   3   4 +
--R         |               |
--R         |5   6   7   8 |
--R   (31)  |               |
--R         |9   10  11  12|
--R         |               |
--R         +13  14  15  16+
--R                                                    Type: Matrix(Integer)
--E 31

--S 32 of 38
inverse(mm)
--R
--R
--R   (32)  "failed"
--R                                                 Type: Union("failed",...)
--E 32

--S 33 of 38
determinant(mm)
--R
--R
--R   (33)  0
--R                                                  Type: NonNegativeInteger
--E 33

--S 34 of 38
trace(mm)
--R
--R
--R   (34)  34
--R                                                     Type: PositiveInteger
--E 34

--S 35 of 38
rank(mm)
--R
--R
--R   (35)  2
--R                                                     Type: PositiveInteger
--E 35

--S 36 of 38
```

```
nullity(mm)
--R
--R
--R   (36)  2
--R                                                    Type: PositiveInteger
--E 36

--S 37 of 38
nullSpace(mm)
--R
--R
--R   (37)  [[1,- 2,1,0],[2,- 3,0,1]]
--R                                              Type: List(Vector(Integer))
--E 37

--S 38 of 38
rowEchelon(mm)
--R
--R
--R         +1  2  3  4 +
--R         |           |
--R         |0  4  8  12|
--R   (38)  |           |
--R         |0  0  0  0 |
--R         |           |
--R         +0  0  0  0 +
--R                                                 Type: Matrix(Integer)
--E 38
)spool
)lisp (bye)
```

———-

— Matrix.help —

```
====================================================================
Matrix examples
====================================================================

The Matrix domain provides arithmetic operations on matrices
and standard functions from linear algebra.
This domain is similar to the TwoDimensionalArray domain, except
that the entries for Matrix must belong to a  Ring.

====================================================================
Creating Matrices
====================================================================

There are many ways to create a matrix from a collection of values or
```

```
from existing matrices.

If the matrix has almost all items equal to the same value, use new to
create a matrix filled with that value and then reset the entries that
are different.

  m : Matrix(Integer) := new(3,3,0)
    +0  0  0+
    |       |
    |0  0  0|
    |       |
    +0  0  0+
                        Type: Matrix Integer

To change the entry in the second row, third column to 5, use setelt.

  setelt(m,2,3,5)
    5
                        Type: PositiveInteger

An alternative syntax is to use assignment.

  m(1,2) := 10
    10
                        Type: PositiveInteger

The matrix was destructively modified.

  m
    +0  10  0+
    |        |
    |0  0   5|
    |        |
    +0  0   0+
                        Type: Matrix Integer

If you already have the matrix entries as a list of lists, use matrix.

  matrix [ [1,2,3,4],[0,9,8,7] ]
    +1  2  3  4+
    |          |
    +0  9  8  7+
                        Type: Matrix Integer

If the matrix is diagonal, use diagonalMatrix.

  dm := diagonalMatrix [1,x**2,x**3,x**4,x**5]
        +1  0   0   0   0 +
        |                 |
        |    2            |
```

```
       |0  x   0   0   0 |
       |                 |
       |        3        |
       |0  0   x   0   0 |
       |                 |
       |            4    |
       |0  0   0   x   0 |
       |                 |
       |                5|
       +0  0   0   0   x +
                    Type: Matrix Polynomial Integer
```

Use setRow and setColumn to change a row or column of a matrix.

```
  setRow!(dm,5,vector [1,1,1,1,1])
       +1  0   0   0   0+
       |                 |
       |    2            |
       |0  x   0   0   0|
       |                 |
       |        3        |
       |0  0   x   0   0|
       |                 |
       |            4    |
       |0  0   0   x   0|
       |                 |
       +1  1   1   1   1+
                    Type: Matrix Polynomial Integer

  setColumn!(dm,2,vector [y,y,y,y,y])
       +1  y  0   0   0+
       |                |
       |0  y  0   0   0|
       |                |
       |       3        |
       |0  y  x   0   0|
       |                |
       |           4    |
       |0  y  0   x   0|
       |                |
       +1  y  1   1   1+
                    Type: Matrix Polynomial Integer
```

Use copy to make a copy of a matrix.

```
  cdm := copy(dm)
       +1  y  0   0   0+
       |                |
       |0  y  0   0   0|
       |                |
```

```
       |       3       |
       |0  y  x   0   0|
       |               |
       |           4   |
       |0  y  0   x   0|
       |               |
       +1  y  1   1   1+
                  Type: Matrix Polynomial Integer
```

This is useful if you intend to modify a matrix destructively but want a copy of the original.

```
  setelt(dm,4,1,1-x**7)
        7
     - x  + 1
                  Type: Polynomial Integer

  [dm,cdm]
         +   1      y  0   0   0+ +1  y  0   0   0+
         |                       | |               |
         |   0      y  0   0   0| |0  y  0   0   0|
         |                       | |               |
         |              3        | |       3       |
        [|   0      y  x   0   0|,|0  y  x   0   0|]
         |                       | |               |
         |   7              4    | |           4   |
         |- x  + 1  y  0   x   0| |0  y  0   x   0|
         |                       | |               |
         +   1      y  1   1   1+ +1  y  1   1   1+
                  Type: List Matrix Polynomial Integer
```

Use subMatrix to extract part of an existing matrix. The syntax is subMatrix(m, firstrow, lastrow, firstcol, lastcol).

```
  subMatrix(dm,2,3,2,4)
        +y  0   0+
        |        |
        |    3   |
        +y  x   0+
                  Type: Matrix Polynomial Integer
```

To change a submatrix, use setsubMatrix.

```
  d := diagonalMatrix [1.2,-1.3,1.4,-1.5]
        +1.2   0.0   0.0   0.0 +
        |                      |
        |0.0  - 1.3  0.0   0.0 |
        |                      |
        |0.0   0.0   1.4   0.0 |
        |                      |
```

```
        +0.0   0.0   0.0  - 1.5+
                    Type: Matrix Float
```

If e is too big to fit where you specify, an error message is displayed. Use subMatrix to extract part of e, if necessary.

```
  e := matrix [ [6.7,9.11],[-31.33,67.19] ]
        +  6.7    9.11 +
        |              |
        +- 31.33  67.19+
                    Type: Matrix Float
```

This changes the submatrix of d whose upper left corner is at the first row and second column and whose size is that of e.

```
  setsubMatrix!(d,1,2,e)
        +1.2    6.7    9.11    0.0 +
        |                          |
        |0.0  - 31.33  67.19   0.0 |
        |                          |
        |0.0    0.0     1.4    0.0 |
        |                          |
        +0.0    0.0     0.0   - 1.5+
                      Type: Matrix Float

  d
        +1.2    6.7    9.11    0.0 +
        |                          |
        |0.0  - 31.33  67.19   0.0 |
        |                          |
        |0.0    0.0     1.4    0.0 |
        |                          |
        +0.0    0.0     0.0   - 1.5+
                      Type: Matrix Float
```

Matrices can be joined either horizontally or vertically to make new matrices.

```
  a := matrix [ [1/2,1/3,1/4],[1/5,1/6,1/7] ]
        +1  1  1+
        |-  -  -|
        |2  3  4|
        |       |
        |1  1  1|
        |-  -  -|
        +5  6  7+
                        Type: Matrix Fraction Integer

  b := matrix [ [3/5,3/7,3/11],[3/13,3/17,3/19] ]
        +3   3    3+
```

```
       |-   -   --|
       |5   7   11|
       |          |
       | 3   3   3|
       |--  --  --|
       +13  17  19+
                        Type: Matrix Fraction Integer
```

Use horizConcat to append them side to side. The two matrices must have the same number of rows.

```
  horizConcat(a,b)
       +1  1  1  3   3    3+
       |-  -  -  -   -   --|
       |2  3  4  5   7   11|
       |                   |
       |1  1  1   3   3   3|
       |-  -  -  --  --  --|
       +5  6  7  13  17  19+
                        Type: Matrix Fraction Integer
```

Use vertConcat to stack one upon the other. The two matrices must have the same number of columns.

```
  vab := vertConcat(a,b)
       +1   1   1 +
       |-   -   - |
       |2   3   4 |
       |          |
       |1   1   1 |
       |-   -   - |
       |5   6   7 |
       |          |
       |3   3    3|
       |-   -   --|
       |5   7   11|
       |          |
       | 3   3   3|
       |--  --  --|
       +13  17  19+
                        Type: Matrix Fraction Integer
```

The operation transpose is used to create a new matrix by reflection across the main diagonal.

```
  transpose vab
       +1  1  3    3+
       |-  -  -   --|
       |2  5  5   13|
       |            |
```

```
        |1  1  3    3|
        |-  -  -   --|
        |3  6  7   17|
        |            |
        |1  1   3   3|
        |-  -  --  --|
        +4  7  11  19+
                              Type: Matrix Fraction Integer

========================================================================
Operations on Matrices
========================================================================

Axiom provides both left and right scalar multiplication.

  m := matrix [ [1,2],[3,4] ]
        +1  2+
        |    |
        +3  4+
                               Type: Matrix Integer

  4 * m * (-5)
        +- 20  - 40+
        |          |
        +- 60  - 80+
                               Type: Matrix Integer

You can add, subtract, and multiply matrices provided, of course, that
the matrices have compatible dimensions.  If not, an error message is
displayed.

  n := matrix([ [1,0,-2],[-3,5,1] ])
        + 1   0  - 2+
        |            |
        +- 3  5   1 +
                               Type: Matrix Integer

This following product is defined but n * m is not.

  m * n
        +- 5  10   0 +
        |            |
        +- 9  20  - 2+
                               Type: Matrix Integer

The operations nrows and ncols return the number of rows and columns
of a matrix.  You can extract a row or a column of a matrix using the
operations row and column.  The object returned is a Vector.

Here is the third column of the matrix n.
```

```
  vec := column(n,3)
     [- 2,1]
                          Type: Vector Integer
```

You can multiply a matrix on the left by a "row vector" and on the right by a "column vector".

```
  vec * m
     [1,0]
                          Type: Vector Integer
```

Of course, the dimensions of the vector and the matrix must be compatible or an error message is returned.

```
  m * vec
    [0,- 2]
                          Type: Vector Integer
```

The operation inverse computes the inverse of a matrix if the matrix is invertible, and returns "failed" if not.

This Hilbert matrix is invertible.

```
  hilb := matrix([ [1/(i + j) for i in 1..3] for j in 1..3])
         +1  1  1+
         |-  -  -|
         |2  3  4|
         |       |
         |1  1  1|
         |-  -  -|
         |3  4  5|
         |       |
         |1  1  1|
         |-  -  -|
         +4  5  6+
                          Type: Matrix Fraction Integer

  inverse(hilb)
         + 72    - 240   180 +
         |                   |
         |- 240   900   - 720|
         |                   |
         + 180   - 720   600 +
                          Type: Union(Matrix Fraction Integer,...)
```

This matrix is not invertible.

```
  mm := matrix([ [1,2,3,4], [5,6,7,8], [9,10,11,12], [13,14,15,16] ])
         +1   2   3   4 +
```

```
        |             |
        |5   6   7   8 |
        |             |
        |9   10  11  12|
        |             |
        +13  14  15  16+
                              Type: Matrix Integer

  inverse(mm)
     "failed"
                              Type: Union("failed",...)
```

The operation determinant computes the determinant of a matrix
provided that the entries of the matrix belong to a CommutativeRing.

The above matrix mm is not invertible and, hence, must have determinant 0.

```
  determinant(mm)
    0
                              Type: NonNegativeInteger
```

The operation trace computes the trace of a square matrix.

```
  trace(mm)
    34
                              Type: PositiveInteger
```

The operation rank computes the rank of a matrix: the maximal number
of linearly independent rows or columns.

```
  rank(mm)
    2
                              Type: PositiveInteger
```

The operation nullity computes the nullity of a matrix: the dimension
of its null space.

```
  nullity(mm)
    2
                              Type: PositiveInteger
```

The operation nullSpace returns a list containing a basis for the null
space of a matrix. Note that the nullity is the number of elements in
a basis for the null space.

```
  nullSpace(mm)
    [[1,- 2,1,0],[2,- 3,0,1]]
                              Type: List Vector Integer
```


The operation rowEchelon returns the row echelon form of a matrix. It

```
is easy to see that the rank of this matrix is two and that its
nullity is also two.

  rowEchelon(mm)
         +1  2  3  4 +
         |           |
         |0  4  8  12|
         |           |
         |0  0  0  0 |
         |           |
         +0  0  0  0 +
                              Type: Matrix Integer

See Also
o )help OneDimensionalArray
o )help TwoDimensionalArray
o )help Vector
o )help Permanent
o )show Matrix
```

14.7.1 Matrix (MATRIX)



See

⇒ “IndexedMatrix” (IMATRIX) 10.12.1 on page 1208
⇒ “RectangularMatrix” (RMATRIX) 19.4.1 on page 2211
⇒ “SquareMatrix” (SQMATRIX) 20.27.1 on page 2514

Exports:

antisymmetric?	any?	coerce	column	convert
copy	count	determinant	diagonal?	diagonalMatrix
elt	empty	empty?	eq?	eval
every?	exquo	fill!	hash	horizConcat
inverse	latex	less?	listOfLists	map
map!	matrix	maxColIndex	maxRowIndex	member?
members	minColIndex	minordet	minRowIndex	more?
ncols	new	nrows	nullSpace	nullity
parts	qelt	qsetelt!	rank	row
rowEchelon	sample	scalarMatrix	setColumn!	setRow!
setelt	setelt	setsubMatrix!	size?	square?
squareTop	subMatrix	swapColumns!	swapRows!	symmetric?
transpose	vertConcat	zero	#?	?**?
?/?	?=?	?~=?	?*?	?+?
-?	?-?			

— domain MATRIX Matrix —

```
)abbrev domain MATRIX Matrix
++ Author: Grabmeier, Gschnitzer, Williamson
++ Date Created: 1987
++ Date Last Updated: July 1990
++ Basic Operations:
++ Related Domains: IndexedMatrix, RectangularMatrix, SquareMatrix
++ Also See:
++ AMS Classifications:
++ Keywords: matrix, linear algebra
++ Examples:
++ References:
++ Description:
++ \spadtype{Matrix} is a matrix domain where 1-based indexing is used
++ for both rows and columns.

Matrix(R): Exports == Implementation where
  R : Ring
  Row ==> Vector R
  Col ==> Vector R
  mnRow ==> 1
  mnCol ==> 1
  MATLIN ==> MatrixLinearAlgebraFunctions(R,Row,Col,$)
  MATSTOR ==> StorageEfficientMatrixOperations(R)

  Exports ==> MatrixCategory(R,Row,Col) with
    diagonalMatrix: Vector R -> $
      ++ \spad{diagonalMatrix(v)} returns a diagonal matrix where the elements
      ++ of v appear on the diagonal.

    if R has ConvertibleTo InputForm then ConvertibleTo InputForm
```

```
    if R has Field then
      inverse: $ -> Union($,"failed")
        ++ \spad{inverse(m)} returns the inverse of the matrix m.
        ++ If the matrix is not invertible, "failed" is returned.
        ++ Error: if the matrix is not square.
--     matrix: Vector Vector R -> $
--       ++ \spad{matrix(v)} converts the vector of vectors v to a matrix, where
--       ++ the vector of vectors is viewed as a vector of the rows of the
--       ++ matrix
--     diagonalMatrix: Vector $ -> $
--       ++ \spad{diagonalMatrix([m1,...,mk])} creates a block diagonal matrix
--       ++ M with block matrices m1,...,mk down the diagonal,
--       ++ with 0 block matrices elsewhere.
--     vectorOfVectors: $ -> Vector Vector R
--       ++ \spad{vectorOfVectors(m)} returns the rows of the matrix m as a
--       ++ vector of vectors

  Implementation ==>
   InnerIndexedTwoDimensionalArray(R,mnRow,mnCol,Row,Col) add
    minr ==> minRowIndex
    maxr ==> maxRowIndex
    minc ==> minColIndex
    maxc ==> maxColIndex
    mini ==> minIndex
    maxi ==> maxIndex

    minRowIndex x == mnRow
    minColIndex x == mnCol

    swapRows_!(x,i1,i2) ==
        (i1 < minRowIndex(x)) or (i1 > maxRowIndex(x)) or _
           (i2 < minRowIndex(x)) or (i2 > maxRowIndex(x)) =>
             error "swapRows!: index out of range"
        i1 = i2 => x
        minRow := minRowIndex x
        xx := x pretend PrimitiveArray(PrimitiveArray(R))
        n1 := i1 - minRow; n2 := i2 - minRow
        row1 := qelt(xx,n1)
        qsetelt_!(xx,n1,qelt(xx,n2))
        qsetelt_!(xx,n2,row1)
        xx pretend $

    positivePower:($,Integer,NonNegativeInteger) -> $
    positivePower(x,n,nn) ==
--      one? n => x
      (n = 1) => x
      -- no need to allocate space for 3 additional matrices
      n = 2 => x * x
      n = 3 => x * x * x
      n = 4 => (y := x * x; y * y)
```

```
      a := new(nn,nn,0) pretend Matrix(R)
      b := new(nn,nn,0) pretend Matrix(R)
      c := new(nn,nn,0) pretend Matrix(R)
      xx := x pretend Matrix(R)
      power_!(a,b,c,xx,n :: NonNegativeInteger)$MATSTOR pretend $

    x:$ ** n:NonNegativeInteger ==
      not((nn := nrows x) = ncols x) =>
        error "**: matrix must be square"
      zero? n => scalarMatrix(nn,1)
      positivePower(x,n,nn)

    if R has commutative("*") then

        determinant x == determinant(x)$MATLIN
        minordet    x == minordet(x)$MATLIN

    if R has EuclideanDomain then

        rowEchelon  x == rowEchelon(x)$MATLIN

    if R has IntegralDomain then

        rank        x == rank(x)$MATLIN
        nullity     x == nullity(x)$MATLIN
        nullSpace   x == nullSpace(x)$MATLIN

    if R has Field then

        inverse     x == inverse(x)$MATLIN

        x:$ ** n:Integer ==
          nn := nrows x
          not(nn = ncols x) =>
            error "**: matrix must be square"
          zero? n => scalarMatrix(nn,1)
          positive? n => positivePower(x,n,nn)
          (xInv := inverse x) case "failed" =>
            error "**: matrix must be invertible"
          positivePower(xInv :: $,-n,nn)

--     matrix(v: Vector Vector R) ==
--       (rows := # v) = 0 => new(0,0,0)
--       -- error check: this is a top level function
--       cols := # v.mini(v)
--       for k in (mini(v) + 1)..maxi(v) repeat
--         cols ^= # v.k => error "matrix: rows of different lengths"
--       ans := new(rows,cols,0)
--       for i in minr(ans)..maxr(ans) for k in mini(v)..maxi(v) repeat
--         vv := v.k
```

```
--         for j in minc(ans)..maxc(ans) for l in mini(vv)..maxi(vv) repeat
--           ans(i,j) := vv.l
--       ans

    diagonalMatrix(v: Vector R) ==
      n := #v; ans := zero(n,n)
      for i in minr(ans)..maxr(ans) for j in minc(ans)..maxc(ans) _
          for k in mini(v)..maxi(v) repeat qsetelt_!(ans,i,j,qelt(v,k))
      ans

--     diagonalMatrix(vec: Vector $) ==
--       rows : NonNegativeInteger := 0
--       cols : NonNegativeInteger := 0
--       for r in mini(vec)..maxi(vec) repeat
--         mat := vec.r
--         rows := rows + nrows mat; cols := cols + ncols mat
--       ans := zero(rows,cols)
--       loR := minr ans; loC := minc ans
--       for r in mini(vec)..maxi(vec) repeat
--         mat := vec.r
--         hiR := loR + nrows(mat) - 1; hiC := loC + nrows(mat) - 1
--         for i in loR..hiR for k in minr(mat)..maxr(mat) repeat
--           for j in loC..hiC for l in minc(mat)..maxc(mat) repeat
--             ans(i,j) := mat(k,l)
--         loR := hiR + 1; loC := hiC + 1
--       ans

--     vectorOfVectors x ==
--       vv : Vector Vector R := new(nrows x,0)
--       cols := ncols x
--       for k in mini(vv)..maxi(vv) repeat
--         vv.k := new(cols,0)
--       for i in minr(x)..maxr(x) for k in mini(vv)..maxi(vv) repeat
--         v := vv.k
--         for j in minc(x)..maxc(x) for l in mini(v)..maxi(v) repeat
--           v.l := x(i,j)
--       vv

    if R has ConvertibleTo InputForm then
      convert(x:$):InputForm ==
         convert [convert("matrix"::Symbol)@InputForm,
                  convert listOfLists x]$List(InputForm)
```

———-

— MATRIX.dotabb —

```
"MATRIX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MATRIX"]
```

```
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"MATRIX" -> "ALIST"
```

———-

14.8 domain MODMON ModMonic

— ModMonic.input —

```
)set break resume
)sys rm -f ModMonic.output
)spool ModMonic.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ModMonic
--R
--R ModMonic(R: Ring,Rep: UnivariatePolynomialCategory(R))  is a domain constructor
--R Abbreviation for ModMonic is MODMON
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MODMON
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R An : % -> Vector(R)                   D : (%,(R -> R)) -> %
--R D : % -> %                            D : (%,NonNegativeInteger) -> %
--R 1 : () -> %                           UnVectorise : Vector(R) -> %
--R Vectorise : % -> Vector(R)            0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficients : % -> List(R)
--R coerce : Rep -> %                     coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      differentiate : % -> %
--R ?.? : (%,%) -> %                      ?.? : (%,R) -> R
--R eval : (%,%,%) -> %                   eval : (%,Equation(%)) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             init : () -> % if R has STEP
--R latex : % -> String                   leadingCoefficient : % -> R
--R leadingMonomial : % -> %              lift : % -> Rep
--R map : ((R -> R),%) -> %               modulus : () -> Rep
--R monomial? : % -> Boolean              monomials : % -> List(%)
```

```
--R one? : % -> Boolean                    pow : () -> PrimitiveArray(%)
--R pseudoRemainder : (%,%) -> %           recip : % -> Union(%,"failed")
--R reduce : Rep -> %                      reductum : % -> %
--R retract : % -> R                       sample : () -> %
--R setPoly : Rep -> Rep                   zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R D : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R D : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R D : (%,List(SingletonAsOrderedSet)) -> %
--R D : (%,SingletonAsOrderedSet) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R coefficient : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : SingletonAsOrderedSet -> %
--R composite : (Fraction(%),%) -> Union(Fraction(%),"failed") if R has INTDOM
--R composite : (%,%) -> Union(%,"failed") if R has INTDOM
--R computePowers : () -> PrimitiveArray(%)
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SingletonAsOrderedSet has KONVERT(INFORM) and R has KONVERT(INFO
--R convert : % -> Pattern(Integer) if SingletonAsOrderedSet has KONVERT(PATTERN(INT)) and R has
--R convert : % -> Pattern(Float) if SingletonAsOrderedSet has KONVERT(PATTERN(FLOAT)) and R has
--R degree : (%,List(SingletonAsOrderedSet)) -> List(NonNegativeInteger)
--R degree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R differentiate : (%,(R -> R),%) -> %
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
```

```
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> %
--R differentiate : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R differentiate : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R differentiate : (%,List(SingletonAsOrderedSet)) -> %
--R differentiate : (%,SingletonAsOrderedSet) -> %
--R discriminant : % -> R if R has COMRING
--R discriminant : (%,SingletonAsOrderedSet) -> % if R has COMRING
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R divideExponents : (%,NonNegativeInteger) -> Union(%,"failed")
--R ?.? : (%,Fraction(%)) -> Fraction(%) if R has INTDOM
--R elt : (Fraction(%),R) -> R if R has FIELD
--R elt : (Fraction(%),Fraction(%)) -> Fraction(%) if R has INTDOM
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R eval : (%,List(SingletonAsOrderedSet),List(%)) -> %
--R eval : (%,SingletonAsOrderedSet,%) -> %
--R eval : (%,List(SingletonAsOrderedSet),List(R)) -> %
--R eval : (%,SingletonAsOrderedSet,R) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if R has PFI
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) i
--R frobenius : % -> % if R has FFIELDC
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R index : PositiveInteger -> % if R has FINITE
--R integrate : % -> % if R has ALGEBRA(FRAC(INT))
--R isExpt : % -> Union(Record(var: SingletonAsOrderedSet,exponent: NonNegativeInteger),"failed")
--R isPlus : % -> Union(List(%),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R karatsubaDivide : (%,NonNegativeInteger) -> Record(quotient: %,remainder: %)
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R lookup : % -> PositiveInteger if R has FINITE
--R mainVariable : % -> Union(SingletonAsOrderedSet,"failed")
--R makeSUP : % -> SparseUnivariatePolynomial(R)
--R mapExponents : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List(SingletonAsOrderedSet)) -> List(NonNegativeInteger)
--R minimumDegree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
```

```
--R minimumDegree : % -> NonNegativeInteger
--R monicDivide : (%,%) -> Record(quotient: %,remainder: %)
--R monicDivide : (%,%,SingletonAsOrderedSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (R,NonNegativeInteger) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R multiplyExponents : (%,NonNegativeInteger) -> %
--R multivariate : (SparseUnivariatePolynomial(%),SingletonAsOrderedSet) -> %
--R multivariate : (SparseUnivariatePolynomial(R),SingletonAsOrderedSet) -> %
--R nextItem : % -> Union(%,"failed") if R has STEP
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,%) -> NonNegativeInteger if R has INTDOM
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pomopo! : (%,R,NonNegativeInteger,%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if R has FIELD
--R pseudoDivide : (%,%) -> Record(coef: R,quotient: %,remainder: %) if R has INTDOM
--R pseudoQuotient : (%,%) -> % if R has INTDOM
--R ?quo? : (%,%) -> % if R has FIELD
--R random : () -> % if R has FINITE
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R ?rem? : (%,%) -> % if R has FIELD
--R resultant : (%,%) -> R if R has COMRING
--R resultant : (%,%,SingletonAsOrderedSet) -> % if R has COMRING
--R retract : % -> SingletonAsOrderedSet
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(SingletonAsOrderedSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R separate : (%,%) -> Record(primePart: %,commonPart: %) if R has GCDDOM
--R shiftLeft : (%,NonNegativeInteger) -> %
--R shiftRight : (%,NonNegativeInteger) -> %
--R size : () -> NonNegativeInteger if R has FINITE
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynom
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(
--R subResultantGcd : (%,%) -> % if R has INTDOM
--R subtractIfCan : (%,%) -> Union(%,"failed")
```

```
--R totalDegree : (%,List(SingletonAsOrderedSet)) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,SingletonAsOrderedSet) -> SparseUnivariatePolynomial(%)
--R unmakeSUP : SparseUnivariatePolynomial(R) -> %
--R variables : % -> List(SingletonAsOrderedSet)
--R vectorise : (%,NonNegativeInteger) -> Vector(R)
--R
--E 1

)spool
)lisp (bye)
```

———-


— ModMonic.help —

```
========================================================================
ModMonic examples
========================================================================

See Also:
o )show ModMonic
```

———-

14.8.1 ModMonic (MODMON)



Exports:

0	1	An	associates?
binomThmExpt	characteristic	charthRoot	coefficient
coefficients	coerce	composite	computePowers
conditionP	content	convert	D
degree	differentiate	discriminant	divide
divideExponents	elt	euclideanSize	eval
expressIdealMember	exquo	extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial	frobenius	gcd
gcdPolynomial	ground	ground?	hash
index	init	integrate	isExpt
isPlus	isTimes	karatsubaDivide	latex
lcm	leadingCoefficient	leadingMonomial	lift
lookup	mainVariable	makeSUP	map
mapExponents	max	min	minimumDegree
modulus	monicDivide	monomial	monomial?
monomials	multiEuclidean	multiplyExponents	multivariate
nextItem	numberOfMonomials	one?	order
patternMatch	pomopo!	pow	prime?
primitiveMonomials	primitivePart	principalIdeal	pseudoDivide
pseudoQuotient	pseudoRemainder	random	recip
reduce	reducedSystem	reductum	resultant
retract	retractIfCan	sample	separate
setPoly	shiftLeft	shiftRight	size
sizeLess?	solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subResultantGcd	subtractIfCan	totalDegree
unit?	unitCanonical	unitNormal	univariate
unmakeSUP	UnVectorise	variables	vectorise
Vectorise	zero?	?*?	?**?
?+?	?-?	-?	?=?
?^?	?.?	?~=?	?/?
?<?	?<=?	?>?	?>=?
?quo?	?rem?		

— domain MODMON ModMonic —

```
)abbrev domain MODMON ModMonic
++ Author: Mark Botch
++ Description:
++ This package has not been documented
-- following line prevents caching ModMonic
)bo PUSH('ModMonic, $mutableDomains)

ModMonic(R,Rep): C == T
 where
  R: Ring
  Rep: UnivariatePolynomialCategory(R)
  C == UnivariatePolynomialCategory(R) with
```

```
--operations
  setPoly : Rep -> Rep
      ++ setPoly(x) is not documented
  modulus : -> Rep
      ++ modulus() is not documented
  reduce: Rep -> %
      ++ reduce(x) is not documented
  lift: % -> Rep --reduce lift = identity
      ++ lift(x) is not documented
  coerce: Rep -> %
      ++ coerce(x) is not documented
  Vectorise: % -> Vector(R)
      ++ Vectorise(x) is not documented
  UnVectorise: Vector(R) -> %
      ++ UnVectorise(v) is not documented
  An: % -> Vector(R)
      ++ An(x) is not documented
  pow : -> PrimitiveArray(%)
      ++ pow() is not documented
  computePowers : -> PrimitiveArray(%)
      ++ computePowers() is not documented
  if R has FiniteFieldCategory then
     frobenius: % -> %
      ++ frobenius(x) is not documented
  --LinearTransf: (%,Vector(R)) -> SquareMatrix<deg> R
--assertions
  if R has Finite then Finite
T == add
  --constants
    m:Rep := monomial(1,1)$Rep --| degree(m) > 0 and LeadingCoef(m) = R$1
    d := degree(m)$Rep
    d1 := (d-1):NonNegativeInteger
    twod := 2*d1+1
    frobenius?:Boolean := R has FiniteFieldCategory
    --VectorRep:= DirectProduct(d:NonNegativeInteger,R)
  --declarations
    x,y: %
    p: Rep
    d,n: Integer
    e,k1,k2: NonNegativeInteger
    c: R
    --vect: Vector(R)
    power:PrimitiveArray(%)
    frobeniusPower:PrimitiveArray(%)
    computeFrobeniusPowers : () -> PrimitiveArray(%)
  --representations
  --mutable m    --take this out??
  --define
    power := new(0,0)
    frobeniusPower := new(0,0)
```

```
setPoly (mon : Rep) ==
  mon =$Rep m => mon
  oldm := m
  leadingCoefficient mon ^= 1 => error "polynomial must be monic"
  -- following copy code needed since FFPOLY can modify mon
  copymon:Rep:= 0
  while not zero? mon repeat
     copymon := monomial(leadingCoefficient mon, degree mon)$Rep + copymon
     mon := reductum mon
  m := copymon
  d := degree(m)$Rep
  d1 := (d-1)::NonNegativeInteger
  twod := 2*d1+1
  power := computePowers()
  if frobenius? then
    degree(oldm)>1 and not((oldm exquo$Rep m) case "failed") =>
        for i in 1..d1 repeat
          frobeniusPower(i) := reduce lift frobeniusPower(i)
    frobeniusPower := computeFrobeniusPowers()
  m
modulus == m
if R has Finite then
   size == d * size$R
   random == UnVectorise([random()$R for i in 0..d1])
0 == 0$Rep
1 == 1$Rep
c * x == c *$Rep x
n * x == (n::R) *$Rep x
coerce(c:R):% == monomial(c,0)$Rep
coerce(x:%):OutputForm == coerce(x)$Rep
coefficient(x,e):R == coefficient(x,e)$Rep
reductum(x) == reductum(x)$Rep
leadingCoefficient x == (leadingCoefficient x)$Rep
degree x == (degree x)$Rep
lift(x) == x pretend Rep
reduce(p) == (monicDivide(p,m)$Rep).remainder
coerce(p) == reduce(p)
x = y == x =$Rep y
x + y == x +$Rep y
- x == -$Rep x
x * y ==
  p := x *$Rep y
  ans:=0$Rep
  while (n:=degree p)>d1 repeat
     ans:=ans + leadingCoefficient(p)*power.(n-d)
     p := reductum p
  ans+p
Vectorise(x) == [coefficient(lift(x),i) for i in 0..d1]
UnVectorise(vect) ==
  reduce(+/[monomial(vect.(i+1),i) for i in 0..d1])
```

```
      computePowers ==
           mat : PrimitiveArray(%):= new(d,0)
           mat.0:= reductum(-m)$Rep
           w: % := monomial$Rep (1,1)
           for i in 1..d1 repeat
              mat.i := w *$Rep mat.(i-1)
              if degree mat.i=d then
                mat.i:= reductum mat.i + leadingCoefficient mat.i * mat.0
           mat
      if frobenius? then
          computeFrobeniusPowers() ==
            mat : PrimitiveArray(%):= new(d,1)
            mat.1:= mult := monomial(1, size$R)$%
            for i in 2..d1 repeat
               mat.i := mult * mat.(i-1)
            mat

          frobenius(a:%):% ==
            aq:% := 0
            while a^=0 repeat
              aq:= aq + leadingCoefficient(a)*frobeniusPower(degree a)
              a := reductum a
            aq

      pow == power
      monomial(c,e)==
         if e<d then monomial(c,e)$Rep
         else
            if e<=twod then
               c * power.(e-d)
            else
               k1:=e quo twod
               k2 := (e-k1*twod)::NonNegativeInteger
               reduce((power.d1 **k1)*monomial(c,k2))
      if R has Field then

         (x:% exquo y:%):Union(%, "failed") ==
            uv := extendedEuclidean(y, modulus(), x)$Rep
            uv case "failed" => "failed"
            return reduce(uv.coef1)

         recip(y:%):Union(%, "failed") ==  1 exquo y
         divide(x:%, y:%) ==
            (q := (x exquo y)) case "failed" => error "not divisible"
            [q, 0]

--     An(MM) == Vectorise(-(reduce(reductum(m))::MM))
--     LinearTransf(vect,MM) ==
--       ans:= 0::SquareMatrix<d>(R)
--       for i in 1..d do setelt(ans,i,1,vect.i)
```

```
--       for j in 2..d do
--          setelt(ans,1,j, elt(ans,d,j-1) * An(MM).1)
--          for i in 2..d do
--            setelt(ans,i,j, elt(ans,i-1,j-1) + elt(ans,d,j-1) * An(MM).i)
--       ans
```

———-

— MODMON.dotabb —

```
"MODMON" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MODMON"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"MODMON" -> "PFECAT"
```

———-

14.9 domain MODFIELD ModularField

— ModularField.input —

```
)set break resume
)sys rm -f ModularField.output
)spool ModularField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ModularField
--R
--R ModularField(R: CommutativeRing,Mod: AbelianMonoid,reduction: ((R,Mod) -> R),merge: ((Mod,Mo
--R Abbreviation for ModularField is MODFIELD
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MODFIELD
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
```

```
--R associates? : (%,%) -> Boolean        coerce : % -> R
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R factor : % -> Factored(%)             gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R modulus : % -> Mod                    one? : % -> Boolean
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        reduce : (R,Mod) -> %
--R ?rem? : (%,%) -> %                    sample : () -> %
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R exQuo : (%,%) -> Union(%,"failed")
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— ModularField.help —

```
=====================================================================
ModularField examples
=====================================================================

See Also:
o )show ModularField
```

———-

14.9.1 ModularField (MODFIELD)



See

⇒ "ModularRing" (MODRING) 14.10.1 on page 1608
⇒ "EuclideanModularRing" (EMR) 6.3.1 on page 672

Exports:

0	1	associates?	characteristic	coerce
divide	euclideanSize	expressIdealMember	exquo	exQuo
extendedEuclidean	factor	gcd	gcdPolynomial	hash
inv	latex	lcm	modulus	multiEuclidean
one?	prime?	principalIdeal	recip	reduce
sample	sizeLess?	squareFree	squareFreePart	subtractIfCan
unit?	unitCanonical	unitNormal	zero?	?*?
?**?	?+?	?-?	-?	?/?
?=?	?^?	?~=?	?quo?	?rem?

— domain MODFIELD ModularField —

```
)abbrev domain MODFIELD ModularField
++ Author: Mark Botch
++ Description:
++ These domains are used for the factorization and gcds
++ of univariate polynomials over the integers in order to work modulo
++ different  primes.
++ See \spadtype{ModularRing}, \spadtype{EuclideanModularRing}

ModularField(R,Mod,reduction:(R,Mod) -> R,
               merge:(Mod,Mod) -> Union(Mod,"failed"),
                      exactQuo : (R,R,Mod) -> Union(R,"failed")) : C == T
 where
  R    :  CommutativeRing
  Mod  :  AbelianMonoid

  C == Field with
    modulus: % -> Mod
      ++ modulus(x) is not documented
```

```
    coerce: % -> R
      ++ coerce(x) is not documented
    reduce: (R,Mod) -> %
      ++ reduce(r,m) is not documented
    exQuo: (%,%) -> Union(%,"failed")
      ++ exQuo(x,y) is not documented

  T == ModularRing(R,Mod,reduction,merge,exactQuo)
```

———-

— **MODFIELD.dotabb** —

```
"MODFIELD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MODFIELD"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"MODFIELD" -> "FIELD"
```

———-

14.10 domain MODRING ModularRing

— **ModularRing.input** —

```
)set break resume
)sys rm -f ModularRing.output
)spool ModularRing.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ModularRing
--R ModularRing(R: CommutativeRing,Mod: AbelianMonoid,reduction: ((R,Mod) -> R),merge: ((Mod,Mod) -> Union(
--R Abbreviation for ModularRing is MODRING
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MODRING
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : % -> R
```

```
--R coerce : Integer -> %                  coerce : % -> OutputForm
--R hash : % -> SingleInteger              inv : % -> %
--R latex : % -> String                    modulus : % -> Mod
--R one? : % -> Boolean                    recip : % -> Union(%,"failed")
--R reduce : (R,Mod) -> %                  sample : () -> %
--R zero? : % -> Boolean                   ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R exQuo : (%,%) -> Union(%,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **ModularRing.help** —

```
=====================================================================
ModularRing examples
=====================================================================

See Also:
o )show ModularRing
```

———-

14.10.1 ModularRing (MODRING)



See

⇒ "EuclideanModularRing" (EMR) 6.3.1 on page 672
⇒ "ModularField" (MODFIELD) 14.9.1 on page 1606

Exports:

0	1	characteristic	coerce	exQuo
hash	inv	latex	modulus	one?
recip	reduce	sample	subtractIfCan	zero?
?~=?	?*?	?**?	?^?	?+?
?-?	-?	?=?		

— domain MODRING ModularRing —

```
)abbrev domain MODRING ModularRing
++ Author: P.Gianni, B.Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ These domains are used for the factorization and gcds
++ of univariate polynomials over the integers in order to work modulo
++ different  primes.
++ See \spadtype{EuclideanModularRing} ,\spadtype{ModularField}

ModularRing(R,Mod,reduction:(R,Mod) -> R,
               merge:(Mod,Mod) -> Union(Mod,"failed"),
                      exactQuo : (R,R,Mod) -> Union(R,"failed")) : C == T
 where
  R    :  CommutativeRing
  Mod  :  AbelianMonoid

  C == Ring with
    modulus: % -> Mod
      ++ modulus(x) is not documented
    coerce: % -> R
      ++ coerce(x) is not documented
    reduce: (R,Mod) -> %
      ++ reduce(r,m) is not documented
    exQuo: (%,%) -> Union(%,"failed")
      ++ exQuo(x,y) is not documented
    recip: % -> Union(%,"failed")
      ++ recip(x) is not documented
    inv: % -> %
      ++ inv(x) is not documented

  T == add
```

```
    --representation
      Rep:= Record(val:R,modulo:Mod)
    --declarations
      x,y: %

    --define
      modulus(x)   == x.modulo
      coerce(x)    == x.val
      coerce(i:Integer):% == [i::R,0]$Rep
      i:Integer * x:% == (i::%)*x
      coerce(x):OutputForm == (x.val)::OutputForm
      reduce (a:R,m:Mod) == [reduction(a,m),m]$Rep

      characteristic():NonNegativeInteger == characteristic()$R
      0 == [0$R,0$Mod]$Rep
      1 == [1$R,0$Mod]$Rep
      zero? x == zero? x.val
--      one? x == one? x.val
      one? x == (x.val = 1)

      newmodulo(m1:Mod,m2:Mod) : Mod ==
        r:=merge(m1,m2)
        r case "failed" => error "incompatible moduli"
        r::Mod

      x=y ==
        x.val = y.val => true
        x.modulo = y.modulo => false
        (x-y).val = 0
      x+y == reduce((x.val +$R y.val),newmodulo(x.modulo,y.modulo))
      x-y == reduce((x.val -$R y.val),newmodulo(x.modulo,y.modulo))
      -x  == reduce ((-$R x.val),x.modulo)
      x*y == reduce((x.val *$R y.val),newmodulo(x.modulo,y.modulo))

      exQuo(x,y) ==
        xm:=x.modulo
        if xm ^=$Mod y.modulo then xm:=newmodulo(xm,y.modulo)
        r:=exactQuo(x.val,y.val,xm)
        r case "failed"=> "failed"
        [r::R,xm]$Rep

      --if R has EuclideanDomain then
      recip x ==
        r:=exactQuo(1$R,x.val,x.modulo)
        r case "failed" => "failed"
        [r,x.modulo]$Rep

      inv x ==
        if (u:=recip x) case "failed" then error("not invertible")
        else u::%
```

———-

— **MODRING.dotabb** —

```
"MODRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MODRING"]
"BMODULE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BMODULE"]
"MODRING" -> "BMODULE"
```

———-

14.11 domain MODMONOM ModuleMonomial

— **ModuleMonomial.input** —

```
)set break resume
)sys rm -f ModuleMonomial.output
)spool ModuleMonomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ModuleMonomial
--R ModuleMonomial(IS: OrderedSet,E: SetCategory,ff: ((Record(index: IS,exponent: E),Record(index: IS,expone
--R Abbreviation for ModuleMonomial is MODMONOM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MODMONOM
--R
--R------------------------------ Operations --------------------------------
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R construct : (IS,E) -> %               exponent : % -> E
--R hash : % -> SingleInteger             index : % -> IS
--R latex : % -> String                   max : (%,%) -> %
--R min : (%,%) -> %                      ?~=? : (%,%) -> Boolean
--R coerce : % -> Record(index: IS,exponent: E)
--R coerce : Record(index: IS,exponent: E) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— ModuleMonomial.help —

```
====================================================================
ModuleMonomial examples
====================================================================

See Also:
o )show ModuleMonomial
```

———-

14.11.1 ModuleMonomial (MODMONOM)



See

⇒ “GeneralModulePolynomial” (GMODPOL) 8.2.1 on page 1029

Exports:

coerce	construct	exponent	hash	index
latex	max	min	?~=?	?<?
?<=?	?=?	?>?	?>=?	

— domain MODMONOM ModuleMonomial —

```
)abbrev domain MODMONOM ModuleMonomial
++ Author: Mark Botch
++ Description:
++ This package has no documentation

ModuleMonomial(IS: OrderedSet,
               E: SetCategory,
               ff:(MM, MM) -> Boolean): T == C where

   MM ==> Record(index:IS, exponent:E)
```

```
   T == OrderedSet  with
    exponent: $ -> E
      ++ exponent(x) is not documented
    index: $ -> IS
      ++ index(x) is not documented
    coerce: MM -> $
      ++ coerce(x) is not documented
    coerce: $ -> MM
      ++ coerce(x) is not documented
    construct: (IS, E) -> $
      ++ construct(i,e) is not documented
   C == MM  add
        Rep:= MM
        x:$ < y:$ == ff(x::Rep, y::Rep)
        exponent(x:$):E == x.exponent
        index(x:$): IS == x.index
        coerce(x:$):MM == x::Rep::MM
        coerce(x:MM):$ == x::Rep::$
        construct(i:IS, e:E):$ == [i, e]$MM::Rep::$
```

———-

— MODMONOM.dotabb —

```
"MODMONOM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MODMONOM"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"MODMONOM" -> "ORDSET"
```

———-

14.12 domain MODOP ModuleOperator

— ModuleOperator.input —

```
)set break resume
)sys rm -f ModuleOperator.output
)spool ModuleOperator.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ModuleOperator
```

```
--R
--R ModuleOperator(R: Ring,M: LeftModule(R))  is a domain constructor
--R Abbreviation for ModuleOperator is MODOP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MODOP
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coerce : BasicOperator -> %           coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R ?.? : (%,M) -> M                      evaluate : (%,(M -> M)) -> %
--R hash : % -> SingleInteger             latex : % -> String
--R one? : % -> Boolean                   opeval : (BasicOperator,M) -> M
--R recip : % -> Union(%,"failed")        retract : % -> BasicOperator
--R retract : % -> R                      sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,R) -> % if R has COMRING
--R ?*? : (R,%) -> % if R has COMRING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (BasicOperator,Integer) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R adjoint : (%,%) -> % if R has COMRING
--R adjoint : % -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R conjug : R -> R if R has COMRING
--R evaluateInverse : (%,(M -> M)) -> %
--R makeop : (R,FreeGroup(BasicOperator)) -> %
--R retractIfCan : % -> Union(BasicOperator,"failed")
--R retractIfCan : % -> Union(R,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— ModuleOperator.help —

```
=====================================================================
ModuleOperator examples
```

```
================================================================================

See Also:
o )show ModuleOperator
```

14.12.1 ModuleOperator (MODOP)



See

⇒ "Operator" (OP) 16.10.1 on page 1770

Exports:

0	1	adjoint	characteristic	charthRoot
coerce	conjug	evaluate	evaluateInverse	hash
latex	makeop	one?	opeval	recip
retract	retractIfCan	sample	subtractIfCan	zero?
?*?	?**?	?+?	?-?	-?
?=?	?^?	?.?	?~=?	

— domain MODOP ModuleOperator —

```
)abbrev domain MODOP ModuleOperator
++ Author: Manuel Bronstein
++ Date Created: 15 May 1990
++ Date Last Updated: 17 June 1993
++ Description:
++ Algebra of ADDITIVE operators on a module.

ModuleOperator(R: Ring, M:LeftModule(R)): Exports == Implementation where
  O    ==> OutputForm
  OP   ==> BasicOperator
  FG   ==> FreeGroup OP
  RM   ==> Record(coef:R, monom:FG)
  TERM ==> List RM
```

```
FAB  ==> FreeAbelianGroup TERM
OPADJ   ==> "%opAdjoint"
OPEVAL  ==> "%opEval"
INVEVAL ==> "%invEval"

Exports ==> Join(Ring, RetractableTo R, RetractableTo OP,
                 Eltable(M, M)) with
  if R has CharacteristicZero then CharacteristicZero
  if R has CharacteristicNonZero then CharacteristicNonZero
  if R has CommutativeRing then
    Algebra(R)
    adjoint: $ -> $
      ++ adjoint(op) returns the adjoint of the operator \spad{op}.
    adjoint: ($, $) -> $
      ++ adjoint(op1, op2) sets the adjoint of op1 to be op2.
      ++ op1 must be a basic operator
    conjug  : R -> R
      ++ conjug(x)should be local but conditional
  evaluate: ($, M -> M) -> $
    ++ evaluate(f, u +-> g u) attaches the map g to f.
    ++ f must be a basic operator
    ++ g MUST be additive, i.e. \spad{g(a + b) = g(a) + g(b)} for
    ++ any \spad{a}, \spad{b} in M.
    ++ This implies that \spad{g(n a) = n g(a)} for
    ++ any \spad{a} in M and integer \spad{n > 0}.
  evaluateInverse: ($, M -> M) -> $
    ++ evaluateInverse(x,f) is not documented
  "**": (OP, Integer) -> $
    ++ op**n is not documented
  "**": ($, Integer) -> $
    ++ op**n is not documented
  opeval  : (OP, M) -> M
    ++ opeval should be local but conditional
  makeop   : (R, FG) -> $
    ++ makeop should be local but conditional

Implementation ==> FAB add
  import NoneFunctions1($)
  import BasicOperatorFunctions1(M)

  Rep := FAB

  inv      : TERM -> $
  termeval : (TERM, M) -> M
  rmeval   : (RM, M) -> M
  monomeval: (FG, M) -> M
  opInvEval: (OP, M) -> M
  mkop     : (R, FG) -> $
  termprod0: (Integer, TERM, TERM) -> $
  termprod : (Integer, TERM, TERM) -> TERM
```

```
    termcopy : TERM -> TERM
    trm2O    : (Integer, TERM) -> O
    term2O   : TERM -> O
    rm2O     : (R, FG) -> O
    nocopy   : OP -> $

    1                   == makeop(1, 1)
    coerce(n:Integer):$ == n::R::$
    coerce(r:R):$       == (zero? r => 0; makeop(r, 1))
    coerce(op:OP):$     == nocopy copy op
    nocopy(op:OP):$     == makeop(1, op::FG)
    elt(x:$, r:M)       == +/[t.exp * termeval(t.gen, r) for t in terms x]
    rmeval(t, r)        == t.coef * monomeval(t.monom, r)
    termcopy t          == [[rm.coef, rm.monom] for rm in t]
    characteristic()    == characteristic()$R
    mkop(r, fg)         == [[r, fg]$RM]$TERM :: $
    evaluate(f, g)   == nocopy setProperty(retract(f)@OP,OPEVAL,g pretend None)

    if R has OrderedSet then
      makeop(r, fg) == (r >= 0 => mkop(r, fg); - mkop(-r, fg))
    else makeop(r, fg) == mkop(r, fg)

    inv(t:TERM):$ ==
      empty? t => 1
      c := first(t).coef
      m := first(t).monom
      inv(rest t) * makeop(1, inv m) * (recip(c)::R::$)

    x:$ ** i:Integer ==
      i = 0 => 1
      i > 0 => expt(x,i pretend PositiveInteger)$RepeatedSquaring($)
      (inv(retract(x)@TERM)) ** (-i)

    evaluateInverse(f, g) ==
      nocopy setProperty(retract(f)@OP, INVEVAL, g pretend None)

    coerce(x:$):O ==
      zero? x => (0$R)::O
      reduce(_+, [trm2O(t.exp, t.gen) for t in terms x])$List(O)

    trm2O(c, t) ==
--      one? c => term2O t
      (c = 1) => term2O t
      c = -1 => - term2O t
      c::O * term2O t

    term2O t ==
      reduce(_*, [rm2O(rm.coef, rm.monom) for rm in t])$List(O)

    rm2O(c, m) ==
```

```
--      one? c => m::0
      (c = 1) => m::0
--      one? m => c::0
      (m = 1) => c::0
      c::0 * m::0

    x:$ * y:$ ==
      +/[ +/[termprod0(t.exp * s.exp, t.gen, s.gen) for s in terms y]
          for t in terms x]

    termprod0(n, x, y) ==
      n >= 0 => termprod(n, x, y)::$
      - (termprod(-n, x, y)::$)

    termprod(n, x, y) ==
      lc := first(xx := termcopy x)
      lc.coef := n * lc.coef
      rm := last xx
--      one?(first(y).coef) =>
      ((first(y).coef) = 1) =>
        rm.monom := rm.monom * first(y).monom
        concat_!(xx, termcopy rest y)
--      one?(rm.monom) =>
      ((rm.monom) = 1) =>
        rm.coef := rm.coef * first(y).coef
        rm.monom := first(y).monom
        concat_!(xx, termcopy rest y)
      concat_!(xx, termcopy y)

    if M has ExpressionSpace then
      opeval(op, r) ==
        (func := property(op, OPEVAL)) case "failed" => kernel(op, r)
        ((func::None) pretend (M -> M)) r

    else
      opeval(op, r) ==
        (func := property(op, OPEVAL)) case "failed" =>
          error "eval: operator has no evaluation function"
        ((func::None) pretend (M -> M)) r

    opInvEval(op, r) ==
      (func := property(op, INVEVAL)) case "failed" =>
         error "eval: operator has no inverse evaluation function"
      ((func::None) pretend (M -> M)) r

    termeval(t, r)  ==
      for rm in reverse t repeat r := rmeval(rm, r)
      r

    monomeval(m, r) ==
```

```
      for rec in reverse_! factors m repeat
        e := rec.exp
        g := rec.gen
        e > 0 =>
          for i in 1..e repeat r := opeval(g, r)
        e < 0 =>
          for i in 1..(-e) repeat r := opInvEval(g, r)
      r

    recip x ==
      (r := retractIfCan(x)@Union(R, "failed")) case "failed" => "failed"
      (r1 := recip(r::R)) case "failed" => "failed"
      r1::R::$

    retractIfCan(x:$):Union(R, "failed") ==
      (r:= retractIfCan(x)@Union(TERM,"failed")) case "failed" => "failed"
      empty?(t := r::TERM) => 0$R
      empty? rest t =>
        rm := first t
--        one?(rm.monom) => rm.coef
        (rm.monom = 1) => rm.coef
        "failed"
      "failed"

    retractIfCan(x:$):Union(OP, "failed") ==
      (r:= retractIfCan(x)@Union(TERM,"failed")) case "failed" => "failed"
      empty?(t := r::TERM) => "failed"
      empty? rest t =>
        rm := first t
--        one?(rm.coef) => retractIfCan(rm.monom)
        (rm.coef = 1) => retractIfCan(rm.monom)
        "failed"
      "failed"

    if R has CommutativeRing then
      termadj  : TERM -> $
      rmadj    : RM -> $
      monomadj : FG -> $
      opadj    : OP -> $

      r:R * x:$        == r::$ * x
      x:$ * r:R        == x * (r::$)
      adjoint x        == +/[t.exp * termadj(t.gen) for t in terms x]
      rmadj t          == conjug(t.coef) * monomadj(t.monom)
      adjoint(op, adj) == nocopy setProperty(retract(op)@OP, OPADJ, adj::None)

      termadj t ==
        ans:$ := 1
        for rm in t repeat ans := rmadj(rm) * ans
        ans
```

```
      monomadj m ==
        ans:$ := 1
        for rec in factors m repeat ans := (opadj(rec.gen) ** rec.exp) * ans
        ans

      opadj op ==
        (adj := property(op, OPADJ)) case "failed" =>
           error "adjoint: operator does not have a defined adjoint"
        (adj::None) pretend $

      if R has conjugate:R -> R then conjug r == conjugate r else conjug r == r
```

———-

— **MODOP.dotabb** —

```
"MODOP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MODOP"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"MODOP" -> "FLAGG"
"MODOP" -> "FLAGG-"
```

———-

14.13 domain MOEBIUS MoebiusTransform

— **MoebiusTransform.input** —

```
)set break resume
)sys rm -f MoebiusTransform.output
)spool MoebiusTransform.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MoebiusTransform
--R
--R MoebiusTransform(F: Field)  is a domain constructor
--R Abbreviation for MoebiusTransform is MOEBIUS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MOEBIUS
--R
```

```
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R coerce : % -> OutputForm              commutator : (%,%) -> %
--R conjugate : (%,%) -> %                eval : (%,F) -> F
--R hash : % -> SingleInteger             inv : % -> %
--R latex : % -> String                   moebius : (F,F,F,F) -> %
--R one? : % -> Boolean                   recip : % -> %
--R recip : () -> %                       recip : % -> Union(%,"failed")
--R sample : () -> %                      scale : (%,F) -> %
--R scale : F -> %                        shift : (%,F) -> %
--R shift : F -> %                        ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R eval : (%,OnePointCompletion(F)) -> OnePointCompletion(F)
--R
--E 1

)spool
)lisp (bye)
```

———-


— MoebiusTransform.help —

```
=====================================================================
MoebiusTransform examples
=====================================================================

See Also:
o )show MoebiusTransform
```

———-

14.13.1 MoebiusTransform (MOEBIUS)



Exports:

1	coerce	commutator	conjugate	eval
hash	inv	latex	moebius	one?
recip	sample	scale	shift	?~=?
?**?	?^?	?*?	?/?	?=?
?^?				

— domain MOEBIUS MoebiusTransform —

```
)abbrev domain MOEBIUS MoebiusTransform
++ Author: Stephen "Say" Watt
++ Date Created: January 1987
++ Date Last Updated: 11 April 1990
++ Keywords:
++ Examples:
++ References:
++ Description:
++ MoebiusTransform(F) is the domain of fractional linear (Moebius)
++ transformations over F. This a domain of 2-by-2 matrices acting on P1(F).

MoebiusTransform(F): Exports == Implementation where
  F : Field
  OUT ==> OutputForm
  P1F ==> OnePointCompletion F         -- projective 1-space over F

  Exports ==> Group with

    moebius: (F,F,F,F) -> %
      ++ moebius(a,b,c,d) returns \spad{matrix [[a,b],[c,d]]}.
    shift: F -> %
      ++ shift(k) returns \spad{matrix [[1,k],[0,1]]} representing the map
      ++ \spad{x -> x + k}.
    scale: F -> %
      ++ scale(k) returns \spad{matrix [[k,0],[0,1]]} representing the map
      ++ \spad{x -> k * x}.
```

```
  recip: () -> %
    ++ recip() returns \spad{matrix [[0,1],[1,0]]} representing the map
    ++ \spad{x -> 1 / x}.
  shift: (%,F) -> %
    ++ shift(m,h) returns \spad{shift(h) * m}
    ++ (see shift from MoebiusTransform).
  scale: (%,F) -> %
    ++ scale(m,h) returns \spad{scale(h) * m}
    ++ (see shift from MoebiusTransform).
  recip: % -> %
    ++ recip(m) = recip() * m
  eval: (%,F) -> F
    ++ eval(m,x) returns \spad{(a*x + b)/(c*x + d)}
    ++ where \spad{m = moebius(a,b,c,d)}
    ++ (see moebius from MoebiusTransform).
  eval: (%,P1F) -> P1F
    ++ eval(m,x) returns \spad{(a*x + b)/(c*x + d)}
    ++ where \spad{m = moebius(a,b,c,d)}
    ++ (see moebius from MoebiusTransform).

Implementation ==> add

  Rep := Record(a: F,b: F,c: F,d: F)

  moebius(aa,bb,cc,dd) == [aa,bb,cc,dd]

  a(t:%):F == t.a
  b(t:%):F == t.b
  c(t:%):F == t.c
  d(t:%):F == t.d

  1 == moebius(1,0,0,1)
  t * s ==
    moebius(b(t)*c(s) + a(t)*a(s), b(t)*d(s) + a(t)*b(s), _
            d(t)*c(s) + c(t)*a(s), d(t)*d(s) + c(t)*b(s))
  inv t == moebius(d(t),-b(t),-c(t),a(t))

  shift f == moebius(1,f,0,1)
  scale f == moebius(f,0,0,1)
  recip() == moebius(0,1,1,0)

  shift(t,f) == moebius(a(t) + f*c(t), b(t) + f*d(t), c(t), d(t))
  scale(t,f) == moebius(f*a(t),f*b(t),c(t),d(t))
  recip t    == moebius(c(t),d(t),a(t),b(t))

  eval(t:%,f:F) == (a(t)*f + b(t))/(c(t)*f + d(t))
  eval(t:%,f:P1F) ==
    (ff := retractIfCan(f)@Union(F,"failed")) case "failed" =>
      (a(t)/c(t)) :: P1F
    zero?(den := c(t) * (fff := ff :: F) + d(t)) => infinity()
```

```
      ((a(t) * fff + b(t))/den) :: P1F

    coerce t ==
      var := "%x" :: OUT
      num := (a(t) :: OUT) * var + (b(t) :: OUT)
      den := (c(t) :: OUT) * var + (d(t) :: OUT)
      rarrow(var,num/den)

    proportional?: (List F,List F) -> Boolean
    proportional?(list1,list2) ==
      empty? list1 => empty? list2
      empty? list2 => false
      zero? (x1 := first list1) =>
        (zero? first list2) and proportional?(rest list1,rest list2)
      zero? (x2 := first list2) => false
      map((f1:F):F +-> f1/x1, list1) = map((g1:F):F +-> g1/x2, list2)

    t = s ==
      list1 : List F := [a(t),b(t),c(t),d(t)]
      list2 : List F := [a(s),b(s),c(s),d(s)]
      proportional?(list1,list2)
```

———-

— **MOEBIUS.dotabb** —

```
"MOEBIUS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MOEBIUS"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"MOEBIUS" -> "FIELD"
"MOEBIUS" -> "FLAGG-"
```

———-

14.14 domain MRING MonoidRing

— **MonoidRing.input** —

```
)set break resume
)sys rm -f MonoidRing.output
)spool MonoidRing.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show MonoidRing
--R
--R MonoidRing(R: Ring,M: Monoid)  is a domain constructor
--R Abbreviation for MonoidRing is MRING
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MRING
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficient : (%,M) -> R
--R coefficients : % -> List(R)           coerce : R -> %
--R coerce : M -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   map : ((R -> R),%) -> %
--R monomial : (R,M) -> %                 monomial? : % -> Boolean
--R monomials : % -> List(%)              one? : % -> Boolean
--R recip : % -> Union(%,"failed")        retract : % -> R
--R retract : % -> M                      sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,R) -> % if R has COMRING
--R ?*? : (R,%) -> % if R has COMRING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R coerce : List(Record(coef: R,monom: M)) -> %
--R index : PositiveInteger -> % if M has FINITE and R has FINITE
--R leadingCoefficient : % -> R if M has ORDSET
--R leadingMonomial : % -> M if M has ORDSET
--R lookup : % -> PositiveInteger if M has FINITE and R has FINITE
--R numberOfMonomials : % -> NonNegativeInteger
--R random : () -> % if M has FINITE and R has FINITE
--R reductum : % -> % if M has ORDSET
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(M,"failed")
--R size : () -> NonNegativeInteger if M has FINITE and R has FINITE
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R terms : % -> List(Record(coef: R,monom: M))
--R
--E 1

)spool
)lisp (bye)
```

———-


— MonoidRing.help —

```
====================================================================
MonoidRing examples
====================================================================

See Also:
o )show MonoidRing
```

———-

14.14.1 MonoidRing (MRING)



Exports:

0	1	characteristic	charthRoot	coefficient
coefficients	coerce	hash	index	latex
leadingCoefficient	leadingMonomial	lookup	map	monomial
monomial?	monomials	numberOfMonomials	one?	random
recip	reductum	retract	retractIfCan	sample
size	subtractIfCan	terms	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?			

— domain MRING MonoidRing —

```
)abbrev domain MRING MonoidRing
++ Authors: Stephan M. Watt; revised by Johannes Grabmeier
++ Date Created: January 1986
++ Date Last Updated: 14 December 1995, Mike Dewar
++ Basic Operations: *, +, monomials, coefficients
++ Related Constructors: Polynomial
++ Also See:
```

```
++ AMS Classifications:
++ Keywords: monoid ring, group ring, polynomials in non-commuting
++  indeterminates
++ References:
++ Description:
++ \spadtype{MonoidRing}(R,M), implements the algebra
++ of all maps from the monoid M to the commutative ring R with
++ finite support.
++ Multiplication of two maps f and g is defined
++ to map an element c of M to the (convolution) sum over f(a)g(b)
++ such that ab = c. Thus M can be identified with a canonical
++ basis and the maps can also be considered as formal linear combinations
++ of the elements in M. Scalar multiples of a basis element are called
++ monomials. A prominent example is the class of polynomials
++ where the monoid is a direct product of the natural numbers
++ with pointwise addition. When M is
++ \spadtype{FreeMonoid Symbol}, one gets polynomials
++ in infinitely many non-commuting variables. Another application
++ area is representation theory of finite groups G, where modules
++ over \spadtype{MonoidRing}(R,G) are studied.

MonoidRing(R: Ring, M: Monoid): MRcategory == MRdefinition where
    Term ==> Record(coef: R, monom: M)

    MRcategory ==> Join(Ring, RetractableTo M, RetractableTo R) with
        monomial         : (R, M) -> %
          ++ monomial(r,m) creates a scalar multiple of the basis element m.
        coefficient : (%, M) -> R
          ++ coefficient(f,m) extracts the coefficient of m in f with respect
          ++ to the canonical basis M.
        coerce:   List Term -> %
          ++ coerce(lt) converts a list of terms and
          ++ coefficients to a member of the domain.
        terms       : % -> List Term
          ++ terms(f) gives the list of non-zero coefficients combined
          ++ with their corresponding basis element as records.
          ++ This is the internal representation.
        map         : (R -> R, %) -> %
          ++ map(fn,u) maps function fn onto the coefficients
          ++ of the non-zero monomials of u.
        monomial?   : % -> Boolean
          ++ monomial?(f) tests if f is a single monomial.
        coefficients: % -> List R
          ++ coefficients(f) lists all non-zero coefficients.
        monomials: % -> List %
           ++ monomials(f) gives the list of all monomials whose
           ++ sum is f.
        numberOfMonomials: % -> NonNegativeInteger
           ++ numberOfMonomials(f) is the number of non-zero coefficients
           ++ with respect to the canonical basis.
```

```
      if R has CharacteristicZero then CharacteristicZero
      if R has CharacteristicNonZero then CharacteristicNonZero
      if R has CommutativeRing then Algebra(R)
      if (R has Finite and M has Finite) then Finite
      if M has OrderedSet then
        leadingMonomial   : % -> M
          ++ leadingMonomial(f) gives the monomial of f whose
          ++ corresponding monoid element is the greatest
          ++ among all those with non-zero coefficients.
        leadingCoefficient: % -> R
          ++ leadingCoefficient(f) gives the coefficient of f, whose
          ++ corresponding monoid element is the greatest
          ++ among all those with non-zero coefficients.
        reductum          : % -> %
          ++ reductum(f) is f minus its leading monomial.

  MRdefinition ==> add
      Ex ==> OutputForm
      Cf ==> coef
      Mn ==> monom

      Rep  := List Term

      coerce(x: List Term): % == x :: %

      monomial(r:R, m:M)  ==
        r = 0 => empty()
        [[r, m]]

      if (R has Finite and M has Finite) then
        size() == size()$R ** size()$M

        index k ==
          -- use p-adic decomposition of k
          -- coefficient of p**j determines coefficient of index(i+p)$M
          i:Integer := k rem size()
          p:Integer := size()$R
          n:Integer := size()$M
          ans:% := 0
          for j in 0.. while i > 0 repeat
            h := i rem p
            -- we use index(p) = 0$R
            if h ^= 0 then
              c : R := index(h :: PositiveInteger)$R
              m : M := index((j+n) :: PositiveInteger)$M
              --ans := ans + c *$% m
              ans := ans + monomial(c, m)$%
            i := i quo p
          ans
```

```
  lookup(z : %) : PositiveInteger ==
    -- could be improved, if M has OrderedSet
    -- z = index lookup z, n = lookup index n
    -- use p-adic decomposition of k
    -- coefficient of p**j determines coefficient of index(i+p)$M
    zero?(z) => size()$% pretend PositiveInteger
    liTe : List Term := terms z  -- all non-zero coefficients
    p  : Integer := size()$R
    n  : Integer := size()$M
    res : Integer := 0
    for te in liTe repeat
      -- assume that lookup(p)$R = 0
      l:NonNegativeInteger:=lookup(te.Mn)$M
      ex : NonNegativeInteger := (n=l => 0;l)
      co : Integer := lookup(te.Cf)$R
      res := res + co * p ** ex
    res pretend PositiveInteger

  random() == index( (1+(random()$Integer rem size()$%) )_
    pretend PositiveInteger)$%

0                   == empty()
1                   == [[1, 1]]
terms a             == (copy a) pretend List(Term)
monomials a         == [[t] for t in a]
coefficients a      == [t.Cf for t in a]
coerce(m:M):%       == [[1, m]]
coerce(r:R): % ==
-- coerce of ring
  r = 0 => 0
  [[r,    1]]
coerce(n:Integer): % ==
-- coerce of integers
  n = 0 => 0
  [[n::R, 1]]
- a                 == [[ -t.Cf, t.Mn] for t in a]
if R has noZeroDivisors
   then
    (r:R) * (a:%) ==
      r = 0 => 0
      [[r*t.Cf, t.Mn] for t in a]
   else
    (r:R) * (a:%) ==
      r = 0 => 0
      [[rt, t.Mn] for t in a | (rt:=r*t.Cf) ^= 0]
if R has noZeroDivisors
   then
    (n:Integer) * (a:%) ==
      n = 0 => 0
      [[n*t.Cf, t.Mn] for t in a]
```

```
           else
            (n:Integer) * (a:%) ==
              n = 0 => 0
              [[nt, t.Mn] for t in a | (nt:=n*t.Cf) ^= 0]
        map(f, a)           == [[ft, t.Mn] for t in a | (ft:=f(t.Cf)) ^= 0]
        numberOfMonomials a == #a

        retractIfCan(a:%):Union(M, "failed") ==
--          one?(#a) and one?(a.first.Cf) => a.first.Mn
          ((#a) = 1) and ((a.first.Cf) = 1) => a.first.Mn
          "failed"

        retractIfCan(a:%):Union(R, "failed") ==
--          one?(#a) and one?(a.first.Mn) => a.first.Cf
          ((#a) = 1) and ((a.first.Mn) = 1) => a.first.Cf
          "failed"

        if R has noZeroDivisors then
          if M has Group then
            recip a ==
              lt := terms a
              #lt ^= 1 => "failed"
              (u := recip lt.first.Cf) case "failed" => "failed"
              --(u::R) * inv lt.first.Mn
              monomial((u::R), inv lt.first.Mn)$%
          else
            recip a ==
              #a ^= 1 or a.first.Mn ^= 1 => "failed"
              (u := recip a.first.Cf) case "failed" => "failed"
              u::R::%

        mkTerm(r:R, m:M):Ex ==
            r=1 => m::Ex
            r=0 or m=1 => r::Ex
            r::Ex * m::Ex

        coerce(a:%):Ex ==
            empty? a => (0$Integer)::Ex
            empty? rest a => mkTerm(a.first.Cf, a.first.Mn)
            reduce(_+, [mkTerm(t.Cf, t.Mn) for t in a])$List(Ex)

        if M has OrderedSet then -- we mean totally ordered
            -- Terms are stored in decending order.
            leadingCoefficient a == (empty? a => 0; a.first.Cf)
            leadingMonomial a    == (empty? a => 1; a.first.Mn)
            reductum a           == (empty? a => a; rest a)

            a = b ==
                #a ^= #b => false
                for ta in a for tb in b repeat
```

```
            ta.Cf ^= tb.Cf or ta.Mn ^= tb.Mn => return false
        true

    a + b ==
        c:% := empty()
        while not empty? a and not empty? b repeat
          ta := first a; tb := first b
          ra := rest a;  rb := rest b
          c :=
            ta.Mn > tb.Mn => (a := ra; concat_!(c, ta))
            ta.Mn < tb.Mn => (b := rb; concat_!(c, tb))
            a := ra; b := rb
            not zero?(r := ta.Cf+tb.Cf) =>
                                concat_!(c, [r, ta.Mn])
            c
        concat_!(c, concat(a, b))

    coefficient(a, m) ==
        for t in a repeat
            if t.Mn = m then return t.Cf
            if t.Mn < m then return 0
        0


    if M has OrderedMonoid then

    -- we use that multiplying an ordered list of monoid elements
    -- by a single element respects the ordering

      if R has noZeroDivisors then
        a:% * b:% ==
          +/[[[ta.Cf*tb.Cf, ta.Mn*tb.Mn]$Term
            for tb in b ] for ta in reverse a]
      else
        a:% * b:% ==
          +/[[[r, ta.Mn*tb.Mn]$Term
            for tb in b | not zero?(r := ta.Cf*tb.Cf)]
              for ta in reverse a]
    else -- M hasn't OrderedMonoid

    -- we cannot assume that mutiplying an ordered list of
    -- monoid elements by a single element respects the ordering:
    -- we have to order and to collect equal terms
      ge : (Term,Term) -> Boolean
      ge(s,t) == t.Mn <= s.Mn

      sortAndAdd : List Term -> List Term
      sortAndAdd(liTe) ==  -- assume liTe not empty
        liTe := sort(ge,liTe)
        m : M :=  (first liTe).Mn
```

```
            cf : R := (first liTe).Cf
            res : List Term := []
            for te in rest liTe repeat
              if m = te.Mn then
                cf := cf + te.Cf
              else
                if not zero? cf then res := cons([cf,m]$Term, res)
                m := te.Mn
                cf := te.Cf
            if not zero? cf then res := cons([cf,m]$Term, res)
            reverse res


          if R has noZeroDivisors then
            a:% * b:% ==
              zero? a => a
              zero? b => b  -- avoid calling sortAndAdd with []
              +/[sortAndAdd [[ta.Cf*tb.Cf, ta.Mn*tb.Mn]$Term
                for tb in b ] for ta in reverse a]
          else
            a:% * b:% ==
              zero? a => a
              zero? b => b  -- avoid calling sortAndAdd with []
              +/[sortAndAdd [[r, ta.Mn*tb.Mn]$Term
                for tb in b | not zero?(r := ta.Cf*tb.Cf)]
                  for ta in reverse a]


      else -- M hasn't OrderedSet
          -- Terms are stored in random order.
        a = b ==
          #a ^= #b => false
          brace(a pretend List(Term)) =$Set(Term) brace(b pretend List(Term))

        coefficient(a, m) ==
          for t in a repeat
            t.Mn = m => return t.Cf
          0

        addterm(Tabl: AssociationList(M,R), r:R, m:M):R ==
            (u := search(m, Tabl)) case "failed" => Tabl.m := r
            zero?(r := r + u::R) => (remove_!(m, Tabl); 0)
            Tabl.m := r

        a + b ==
            Tabl := table()$AssociationList(M,R)
            for t in a repeat
                Tabl t.Mn := t.Cf
            for t in b repeat
                addterm(Tabl, t.Cf, t.Mn)
```

```
            [[Tabl m, m]$Term for m in keys Tabl]

        a:% * b:% ==
            Tabl := table()$AssociationList(M,R)
            for ta in a repeat
                for tb in (b pretend List(Term)) repeat
                    addterm(Tabl, ta.Cf*tb.Cf, ta.Mn*tb.Mn)
            [[Tabl.m, m]$Term for m in keys Tabl]
```

———-

— **MRING.dotabb** —

```
"MRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MRING"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"MRING" -> "FLAGG"
"MRING" -> "FLAGG-"
```

———-

14.15 domain MSET Multiset

— **Multiset.input** —

```
)set break resume
)sys rm -f Multiset.output
)spool Multiset.output
)set message test on
)set message auto off
)clear all
--S 1 of 14
s := multiset [1,2,3,4,5,4,3,2,3,4,5,6,7,4,10]
--R
--R
--R   (1)  {1,2: 2,3: 3,4: 4,2: 5,6,7,10}
--R                                          Type: Multiset(PositiveInteger)
--E 1

--S 2 of 14
insert!(3,s)
--R
--R
--R   (2)  {1,2: 2,4: 3,4: 4,2: 5,6,7,10}
```

```
--R                                                Type: Multiset(PositiveInteger)
--E 2

--S 3 of 14
remove!(3,s,1)
--R
--R
--R   (3)  {1,2: 2,3: 3,4: 4,2: 5,6,7,10}
--R                                                Type: Multiset(PositiveInteger)
--E 3

--S 4 of 14
s
--R
--R
--R   (4)  {1,2: 2,3: 3,4: 4,2: 5,6,7,10}
--R                                                Type: Multiset(PositiveInteger)
--E 4

--S 5 of 14
remove!(5,s)
--R
--R
--R   (5)  {1,2: 2,3: 3,4: 4,6,7,10}
--R                                                Type: Multiset(PositiveInteger)
--E 5

--S 6 of 14
s
--R
--R
--R   (6)  {1,2: 2,3: 3,4: 4,6,7,10}
--R                                                Type: Multiset(PositiveInteger)
--E 6

--S 7 of 14
count(5,s)
--R
--R
--R   (7)  0
--R                                                       Type: NonNegativeInteger
--E 7

--S 8 of 14
t := multiset [2,2,2,-9]
--R
--R
--R   (8)  {3: 2,- 9}
--R                                                        Type: Multiset(Integer)
--E 8
```

```
--S 9 of 14
U := union(s,t)
--R
--R
--R   (9)  {1,5: 2,3: 3,4: 4,6,7,10,- 9}
--R                                                    Type: Multiset(Integer)
--E 9

--S 10 of 14
I := intersect(s,t)
--R
--R
--R   (10)  {5: 2}
--R                                                    Type: Multiset(Integer)
--E 10

--S 11 of 14
difference(s,t)
--R
--R
--R   (11)  {1,3: 3,4: 4,6,7,10}
--R                                                    Type: Multiset(Integer)
--E 11

--S 12 of 14
S := symmetricDifference(s,t)
--R
--R
--R   (12)  {1,3: 3,4: 4,6,7,10,- 9}
--R                                                    Type: Multiset(Integer)
--E 12

--S 13 of 14
(U = union(S,I))@Boolean
--R
--R
--R   (13)  true
--R                                                           Type: Boolean
--E 13

--S 14 of 14
t1 := multiset [1,2,2,3]; [t1 < t, t1 < s, t < s, t1 <= s]
--R
--R
--R   (14)  [false,true,false,true]
--R                                                       Type: List(Boolean)
--E 14
)spool
)lisp (bye)
```

———-

— Multiset.help —

```
====================================================================
Multiset examples
====================================================================

The domain Multiset(R) is similar to Set(R) except that multiplicities
(counts of duplications) are maintained and displayed.  Use the
operation multiset to create multisets from lists.  All the standard
operations from sets are available for multisets.  An element with
multiplicity greater than one has the multiplicity displayed first,
then a colon, and then the element.

Create a multiset of integers.

  s := multiset [1,2,3,4,5,4,3,2,3,4,5,6,7,4,10]
    {1,2: 2,3: 3,4: 4,2: 5,6,7,10}
                          Type: Multiset PositiveInteger

The operation insert! adds an element to a multiset.

  insert!(3,s)
    {1,2: 2,4: 3,4: 4,2: 5,6,7,10}
                          Type: Multiset PositiveInteger

Use remove! to remove an element.  If a third argument is present, it
specifies how many instances to remove. Otherwise all instances of the
element are removed.  Display the resulting multiset.

  remove!(3,s,1); s

    {1,2: 2,3: 3,4: 4,2: 5,6,7,10}
                          Type: Multiset PositiveInteger

  remove!(5,s); s
    {1,2: 2,3: 3,4: 4,6,7,10}
                          Type: Multiset PositiveInteger

The operation count returns the number of copies of a given value.

  count(5,s)
    0
                          Type: NonNegativeInteger

A second multiset.

  t := multiset [2,2,2,-9]
```

```
    {3: 2,- 9}
                          Type: Multiset Integer

The union of two multisets is additive.

  U := union(s,t)
    {1,5: 2,3: 3,4: 4,6,7,10,- 9}
                          Type: Multiset Integer

The intersect operation gives the elements that are in common, with
additive multiplicity.

  I := intersect(s,t)
    {5: 2}
                          Type: Multiset Integer

The difference of s and t consists of the elements that s has but t
does not.  Elements are regarded as indistinguishable, so that if s
and t have any element in common, the difference does not contain that
element.

  difference(s,t)
    {1,3: 3,4: 4,6,7,10}
                          Type: Multiset Integer

The symmetricDifference is the union of difference(s, t) and difference(t, s).

  S := symmetricDifference(s,t)
    {1,3: 3,4: 4,6,7,10,- 9}
                          Type: Multiset Integer

Check that the union of the symmetricDifference and the intersect
equals the union of the elements.

  (U = union(S,I))@Boolean
    true
                          Type: Boolean


Check some inclusion relations.

  t1 := multiset [1,2,2,3]; [t1 < t, t1 < s, t < s, t1 <= s]
    [false,true,false,true]
                          Type: List Boolean

See Also:
o )show Multiset
```

———-

14.15.1 Multiset (MSET)



Exports:

any?	bag	brace	coerce	construct
convert	copy	count	dictionary	difference
duplicates	empty	empty?	eq?	eval
every?	extract!	find	hash	insert!
inspect	intersect	latex	less?	map
map!	members	member?	more?	multiset
parts	reduce	remove	remove!	removeDuplicates
sample	select	select!	set	size?
subset?	symmetricDifference	union	#?	?<?
?=?	?~=?			

— domain MSET Multiset —

```
)abbrev domain MSET Multiset
++ Author:Stephen M. Watt, William H. Burge, Richard D. Jenks, Frederic Lehobey
++ Date Created:NK
++ Date Last Updated: 14 June 1994
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A multiset is a set with multiplicities.

Multiset(S: SetCategory): MultisetAggregate S with
        finiteAggregate
        shallowlyMutable
        multiset: () -> %
```

```
      ++ multiset()$D creates an empty multiset of domain D.
    multiset: S -> %
      ++ multiset(s) creates a multiset with singleton s.
    multiset: List S -> %
      ++ multiset(ls) creates a multiset with elements from \spad{ls}.
    members: % -> List S
      ++ members(ms) returns a list of the elements of \spad{ms}
      ++ without their multiplicity. See also \spadfun{parts}.
    remove: (S,%,Integer) -> %
      ++ remove(x,ms,number) removes at most \spad{number} copies of
      ++ element x if \spad{number} is positive, all of them if
      ++ \spad{number} equals zero, and all but at most \spad{-number} if
      ++ \spad{number} is negative.
    remove: ( S -> Boolean ,%,Integer) -> %
      ++ remove(p,ms,number) removes at most \spad{number} copies of
      ++ elements x such that \spad{p(x)} is \spadfun{true}
      ++ if \spad{number} is positive, all of them if
      ++ \spad{number} equals zero, and all but at most \spad{-number} if
      ++ \spad{number} is negative.
    remove_!: (S,%,Integer) -> %
      ++ remove!(x,ms,number) removes destructively at most \spad{number}
      ++ copies of element x if \spad{number} is positive, all
      ++ of them if \spad{number} equals zero, and all but at most
      ++ \spad{-number} if \spad{number} is negative.
    remove_!: ( S -> Boolean ,%,Integer) -> %
      ++ remove!(p,ms,number) removes destructively at most \spad{number}
      ++ copies of elements x such that \spad{p(x)} is
      ++ \spadfun{true} if \spad{number} is positive, all of them if
      ++ \spad{number} equals zero, and all but at most \spad{-number} if
      ++ \spad{number} is negative.

== add

    Tbl ==> Table(S, Integer)
    tbl ==> table$Tbl
    Rep := Record(count: Integer, table: Tbl)

    n: Integer
    ms, m1, m2: %
    t,  t1, t2: Tbl
    D ==> Record(entry: S, count: NonNegativeInteger)
    K ==> Record(key: S, entry: Integer)

    elt(t:Tbl, s:S):Integer ==
      a := search(s,t)$Tbl
      a case "failed" => 0
      a::Integer

    empty():% == [0,tbl()]
    multiset():% == empty()
```

```
dictionary():% == empty() -- DictionaryOperations
set():% == empty()
brace():% == empty()

construct(l:List S):% ==
    t := tbl()
    n := 0
    for e in l repeat
      t.e := inc t.e
      n := inc n
    [n, t]
multiset(l:List S):% == construct l
bag(l:List S):% == construct l         -- BagAggregate
dictionary(l:List S):% == construct l -- DictionaryOperations
set(l:List S):% == construct l
brace(l:List S):% == construct l

multiset(s:S):% == construct [s]

if S has ConvertibleTo InputForm then
  convert(ms:%):InputForm ==
    convert [convert("multiset"::Symbol)@InputForm,
     convert(parts ms)@InputForm]

members(ms:%):List S == keys ms.table

coerce(ms:%):OutputForm ==
    l: List OutputForm := empty()
    t := ms.table
    colon := ": " :: OutputForm
    for e in keys t repeat
        ex := e::OutputForm
        n := t.e
        item :=
          n > 1 => hconcat [n :: OutputForm,colon, ex]
          ex
        l := cons(item,l)
    brace l

duplicates(ms:%):List D == -- MultiDictionary
  ld : List D := empty()
  t := ms.table
  for e in keys t | (n := t.e) > 1 repeat
    ld := cons([e,n::NonNegativeInteger],ld)
  ld

extract_!(ms:%):S ==         -- BagAggregate
  empty? ms => error "extract: Empty multiset"
  ms.count := dec ms.count
  t := ms.table
```

```
  e := inspect(t).key
  if (n := t.e) > 1 then t.e := dec n
   else remove_!(e,t)
  e

inspect(ms:%):S == inspect(ms.table).key  -- BagAggregate

insert_!(e:S,ms:%):% ==                   -- BagAggregate
    ms.count   := inc ms.count
    ms.table.e := inc ms.table.e
    ms

member?(e:S,ms:%):Boolean == member?(e,keys ms.table)

empty?(ms:%):Boolean == ms.count = 0

#(ms:%):NonNegativeInteger == ms.count::NonNegativeInteger

count(e:S, ms:%):NonNegativeInteger == ms.table.e::NonNegativeInteger

remove_!(e:S, ms:%, max:Integer):% ==
  zero? max => remove_!(e,ms)
  t := ms.table
  if member?(e, keys t) then
    ((n := t.e) <= max) =>
      remove_!(e,t)
      ms.count := ms.count-n
    max > 0 =>
      t.e := n-max
      ms.count := ms.count-max
    (n := n+max) > 0 =>
      t.e := -max
      ms.count := ms.count-n
  ms

remove_!(p: S -> Boolean, ms:%, max:Integer):% ==
  zero? max => remove_!(p,ms)
  t := ms.table
  for e in keys t | p(e) repeat
    ((n := t.e) <= max) =>
      remove_!(e,t)
      ms.count := ms.count-n
    max > 0 =>
      t.e := n-max
      ms.count := ms.count-max
    (n := n+max) > 0 =>
      t.e := -max
      ms.count := ms.count-n
  ms
```

```
remove(e:S, ms:%, max:Integer):% == remove_!(e, copy ms, max)

remove(p: S -> Boolean,ms:%,max:Integer):% == remove_!(p, copy ms, max)

remove_!(e:S, ms:%):% == -- DictionaryOperations
  t := ms.table
  if member?(e, keys t) then
    ms.count := ms.count-t.e
    remove_!(e, t)
  ms

remove_!(p:S ->Boolean, ms:%):% == -- DictionaryOperations
  t := ms.table
  for e in keys t | p(e) repeat
    ms.count := ms.count-t.e
    remove_!(e, t)
  ms

select_!(p: S -> Boolean, ms:%):% == -- DictionaryOperations
  remove_!((s1:S):Boolean+->not p(s1), ms)

removeDuplicates_!(ms:%):% == -- MultiDictionary
  t := ms.table
  l := keys t
  for e in l repeat t.e := 1
  ms.count := #l
  ms

insert_!(e:S,ms:%,more:NonNegativeInteger):% == -- MultiDictionary
    ms.count   := ms.count+more
    ms.table.e := ms.table.e+more
    ms

map_!(f: S->S, ms:%):% == -- HomogeneousAggregate
  t := ms.table
  t1 := tbl()
  for e in keys t repeat
    t1.f(e) := t.e
    remove_!(e, t)
  ms.table := t1
  ms

map(f: S -> S, ms:%):% == map_!(f, copy ms) -- HomogeneousAggregate

parts(m:%):List S ==
  l := empty()$List(S)
  t := m.table
  for e in keys t repeat
    for i in 1..t.e repeat
      l := cons(e,l)
```

```
          l

        union(m1:%, m2:%):% ==
            t := tbl()
            t1:= m1.table
            t2:= m2.table
            for e in keys t1 repeat t.e := t1.e
            for e in keys t2 repeat t.e := t2.e + t.e
            [m1.count + m2.count, t]

        intersect(m1:%, m2:%):% ==
--          if #m1 > #m2 then intersect(m2, m1)
            t := tbl()
            t1:= m1.table
            t2:= m2.table
            n := 0
            for e in keys t1 repeat
              m := min(t1.e,t2.e)
              m > 0 =>
                m := t1.e + t2.e
                t.e := m
                n := n + m
            [n, t]

        difference(m1:%, m2:%):% ==
            t := tbl()
            t1:= m1.table
            t2:= m2.table
            n := 0
            for e in keys t1 repeat
              k1 := t1.e
              k2 := t2.e
              k1 > 0 and k2 = 0 =>
                t.e := k1
                n := n + k1
            n = 0 => empty()
            [n, t]

        symmetricDifference(m1:%, m2:%):% ==
            union(difference(m1,m2), difference(m2,m1))

        m1 = m2 ==
            m1.count ^= m2.count => false
            t1 := m1.table
            t2 := m2.table
            for e in keys t1 repeat
                t1.e ^= t2.e => return false
            for e in keys t2 repeat
                t1.e ^= t2.e => return false
            true
```

```
        m1 < m2 ==
            m1.count >= m2.count => false
            t1 := m1.table
            t2 := m2.table
            for e in keys t1 repeat
                t1.e > t2.e => return false
            m1.count < m2.count

        subset?(m1:%, m2:%):Boolean ==
            m1.count > m2.count => false
            t1 := m1.table
            t2 := m2.table
            for e in keys t1 repeat t1.e > t2.e => return false
            true
```

———-

— **MSET.dotabb** —

```
"MSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MSET"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"MSET" -> "ALIST"
```

———-

14.16 domain MPOLY MultivariatePolynomial

— **MultivariatePolynomial.input** —

```
)set break resume
)sys rm -f MultivariatePolynomial.output
)spool MultivariatePolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 9
m : MPOLY([x,y],INT) := (x^2 - x*y^3 +3*y)^2
--R
--R
--R         4     3 3     6       2     4      2
--R   (1)  x  - 2y x  + (y  + 6y)x  - 6y x + 9y
--R                                  Type: MultivariatePolynomial([x,y],Integer)
--E 1
```

```
--S 2 of 9
m :: MPOLY([y,x],INT)
--R
--R
--R         2 6       4     3 3     2     2     4
--R   (2)  x y  - 6x y  - 2x y  + 9y  + 6x y + x
--R                                  Type: MultivariatePolynomial([y,x],Integer)
--E 2

--S 3 of 9
p : MPOLY([x,y],POLY INT)
--R
--R                                                                    Type: Void
--E 3

--S 4 of 9
p :: POLY INT
--R
--R
--R   (4)  p
--R                                                  Type: Polynomial(Integer)
--E 4

--S 5 of 9
% :: MPOLY([a,b],POLY INT)
--R
--R
--R   (5)  p
--R                      Type: MultivariatePolynomial([a,b],Polynomial(Integer))
--E 5

--S 6 of 9
q : UP(x, FRAC MPOLY([y,z],INT))
--R
--R                                                                    Type: Void
--E 6

--S 7 of 9
q := (x^2 - x*(z+1)/y +2)^2
--R
--R
--R                              2    2
--R         4   - 2z - 2  3   4y  + z  + 2z + 1  2   - 4z - 4
--R   (7)  x  + -------- x  + ----------------- x  + -------- x + 4
--R                 y                  2                 y
--R                                   y
--RType: UnivariatePolynomial(x,Fraction(MultivariatePolynomial([y,z],Integer)))
--E 7
```

```
--S 8 of 9
q :: UP(z, FRAC MPOLY([x,y],INT))
--R
--R
--R   (8)
--R    2           3     2             2 4       3      2      2           2
--R   x   2   - 2y x  + 2x  - 4y x     y x  - 2y x  + (4y  + 1)x  - 4y x + 4y
--R   -- z  + ------------------- z + ---------------------------------------
--R    2               2                                 2
--R   y               y                                 y
--RType: UnivariatePolynomial(z,Fraction(MultivariatePolynomial([x,y],Integer)))
--E 8

--S 9 of 9
q :: MPOLY([x,z], FRAC UP(y,INT))
--R
--R
--R                                                 2
--R         4      2     2  3     1  2    2     4y  + 1  2      4     4
--R   (9)  x  + (- - z - -)x  + (-- z  + -- z + -------)x  + (- - z - -)x + 4
--R               y     y        2       2         2           y     y
--R                             y       y         y
--RType: MultivariatePolynomial([x,z],Fraction(UnivariatePolynomial(y,Integer)))
--E 9
)spool
)lisp (bye)
```

———-

— MultivariatePolynomial.help —

```
=====================================================================
MultivariatePolynomial examples
=====================================================================

The domain constructor MultivariatePolynomial is similar to Polynomial
except that it specifies the variables to be used.  Polynomial are
available for MultivariatePolynomial.  The abbreviation for
MultivariatePolynomial is MPOLY.  The type expressions

  MultivariatePolynomial([x,y],Integer)
  MPOLY([x,y],INT)

refer to the domain of multivariate polynomials in the variables x and
y where the coefficients are restricted to be integers.  The first
variable specified is the main variable and the display of the polynomial
reflects this.

This polynomial appears with terms in descending powers of the variable x.
```

```
  m : MPOLY([x,y],INT) := (x^2 - x*y^3 +3*y)^2
     4     3 3     6       2     4      2
    x  - 2y x  + (y  + 6y)x  - 6y x + 9y
                     Type: MultivariatePolynomial([x,y],Integer)
```

It is easy to see a different variable ordering by doing a conversion.

```
  m :: MPOLY([y,x],INT)
     2 6       4     3 3     2     2     4
    x y  - 6x y  - 2x y  + 9y  + 6x y + x
                     Type: MultivariatePolynomial([y,x],Integer)
```

You can use other, unspecified variables, by using Polynomial in the coefficient type of MPOLY.

```
  p : MPOLY([x,y],POLY INT)
                     Type: Void
```

Conversions can be used to re-express such polynomials in terms of the other variables. For example, you can first push all the variables into a polynomial with integer coefficients.

```
  p :: POLY INT
    p
                     Type: Polynomial Integer
```

Now pull out the variables of interest.

```
  % :: MPOLY([a,b],POLY INT)
    p
                     Type: MultivariatePolynomial([a,b],Polynomial Integer)
```

Restriction:
Axiom does not allow you to create types where MultivariatePolynomial is contained in the coefficient type of Polynomial. Therefore, MPOLY([x,y],POLY INT) is legal but POLY MPOLY([x,y],INT) is not.

Multivariate polynomials may be combined with univariate polynomials to create types with special structures.

```
  q : UP(x, FRAC MPOLY([y,z],INT))
                          Type: Void
```

This is a polynomial in x whose coefficients are quotients of polynomials in y and z.

```
  q := (x^2 - x*(z+1)/y +2)^2
                              2    2
         4   - 2z - 2  3   4y  + z  + 2z + 1  2   - 4z - 4
```

```
   (7)  x  + -------- x  + ----------------- x  + -------- x + 4
                y                  2                 y
                                  y
 Type: UnivariatePolynomial(x,Fraction MultivariatePolynomial([y,z],Integer))
```

Use conversions for structural rearrangements. z does not appear in a denominator and so it can be made the main variable.

```
  q :: UP(z, FRAC MPOLY([x,y],INT))
    2            3     2             2 4       3      2      2            2
   x   2   - 2y x  + 2x  - 4y x     y x  - 2y x  + (4y  + 1)x  - 4y x + 4y
   -- z  + -------------------- z + ---------------------------------------
    2               2                                 2
   y               y                                 y
 Type: UnivariatePolynomial(z,Fraction MultivariatePolynomial([x,y],Integer))
```

Or you can make a multivariate polynomial in x and z whose coefficients are fractions in polynomials in y.


```
  q :: MPOLY([x,z], FRAC UP(y,INT))
     4      2     2  3     1  2    2     4y  + 1  2      4     4
    x  + (- - z - -)x  + (-- z  + -- z + -------)x  + (- - z - -)x + 4
            y     y        2       2         2           y     y
                          y       y         y
 Type: MultivariatePolynomial([x,z],Fraction UnivariatePolynomial(y,Integer))
```

A conversion like q :: MPOLY([x,y], FRAC UP(z,INT)) is not possible in this example because y appears in the denominator of a fraction. As you can see, Axiom provides extraordinary flexibility in the manipulation and display of expressions via its conversion facility.

See Also:
o)help DistributedMultivariatePolynomial
o)help UnivariatePolynomial
o)help Polynomial
o)show MultivariatePolynomial

———————

14.16.1 MultivariatePolynomial (MPOLY)



See

⇒ “Polynomial” (POLY) 17.25.1 on page 2043
⇒ “SparseMultivariatePolynomial” (SMP) 20.14.1 on page 2390
⇒ “IndexedExponents” (INDE) 10.9.1 on page 1187

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	convert
D	degree	differentiate
discriminant	eval	exquo
factor	factorPolynomial	factorSquareFreePolynomial
gcd	gcdPolynomial	ground
ground?	hash	isExpt
isPlus	isTimes	latex
lcm	leadingCoefficient	leadingMonomial
mainVariable	map	mapExponents
max	min	minimumDegree
monicDivide	monomial	monomial?
monomials	multivariate	numberOfMonomials
one?	patternMatch	pomopo!
prime?	primitivePart	primitiveMonomials
recip	reducedSystem	reductum
resultant	retract	retractIfCan
sample	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
totalDegree	unit?	unitCanonical
unitNormal	univariate	variables
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?
?/?	?<?	?<=?
?>?	?>=?	

— domain MPOLY MultivariatePolynomial —

```
)abbrev domain MPOLY MultivariatePolynomial
++ Author: Dave Barton, Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, degree, eval, coefficient, monomial, differentiate,
++ resultant, gcd
++ Related Constructors: SparseMultivariatePolynomial, Polynomial
++ Also See:
++ AMS Classifications:
++ Keywords: polynomial, multivariate
++ References:
++ Description:
++ This type is the basic representation of sparse recursive multivariate
++ polynomials whose variables are from a user specified list of symbols.
++ The ordering is specified by the position of the variable in the list.
++ The coefficient ring may be non commutative,
++ but the variables are assumed to commute.
```

```
MultivariatePolynomial(vl:List Symbol, R:Ring)
   ==  SparseMultivariatePolynomial(--SparseUnivariatePolynomial,
          R, OrderedVariableList vl)
```

———-

— **MPOLY.dotabb** —

```
"MPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MPOLY"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"MPOLY" -> "PFECAT"
```

———-

14.17 domain MYEXPR MyExpression

— **MyExpression.input** —

```
)set break resume
)sys rm -f MyExpression.output
)spool MyExpression.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MyExpression
--R MyExpression(q: Symbol,R: Join(Ring,OrderedSet,IntegralDomain))  is a domain constructor
--R Abbreviation for MyExpression is MYEXPR
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MYEXPR
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?*? : (Integer,%) -> %
--R ?*? : (%,%) -> %                      ?**? : (%,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R -? : % -> %                           ?-? : (%,%) -> %
--R ?/? : (%,%) -> %                      ?<? : (%,%) -> Boolean
--R ?<=? : (%,%) -> Boolean               ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> Boolean                ?>=? : (%,%) -> Boolean
--R D : (%,Symbol) -> %                   D : (%,List Symbol) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        applyQuote : (Symbol,%,%) -> %
```

```
--R applyQuote : (Symbol,%) -> %          associates? : (%,%) -> Boolean
--R belong? : BasicOperator -> Boolean    binomial : (%,%) -> %
--R box : List % -> %                     box : % -> %
--R coerce : Integer -> %                 coerce : % -> %
--R coerce : R -> %                       coerce : Symbol -> %
--R coerce : Kernel % -> %                coerce : % -> OutputForm
--R denominator : % -> %                  differentiate : (%,Symbol) -> %
--R distribute : (%,%) -> %               distribute : % -> %
--R elt : (BasicOperator,%,%) -> %        elt : (BasicOperator,%) -> %
--R eval : (%,List %,List %) -> %         eval : (%,%,%) -> %
--R eval : (%,Equation %) -> %            eval : (%,List Equation %) -> %
--R eval : (%,Kernel %,%) -> %            factorial : % -> %
--R factorials : % -> %                   factorials : (%,Symbol) -> %
--R freeOf? : (%,Symbol) -> Boolean       freeOf? : (%,%) -> Boolean
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             height : % -> NonNegativeInteger
--R is? : (%,Symbol) -> Boolean           kernel : (BasicOperator,%) -> %
--R kernels : % -> List Kernel %          latex : % -> String
--R map : ((% -> %),Kernel %) -> %        max : (%,%) -> %
--R min : (%,%) -> %                      numerator : % -> %
--R one? : % -> Boolean                   paren : List % -> %
--R paren : % -> %                        permutation : (%,%) -> %
--R product : (%,Symbol) -> %             recip : % -> Union(%,"failed")
--R retract : % -> Integer                retract : % -> R
--R retract : % -> Symbol                 retract : % -> Kernel %
--R sample : () -> %                      subst : (%,Equation %) -> %
--R summation : (%,Symbol) -> %           tower : % -> List Kernel %
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R variables : % -> List Symbol          zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?*? : (%,R) -> % if R has COMRING
--R ?*? : (R,%) -> % if R has COMRING
--R ?*? : (%,Fraction Integer) -> % if R has INTDOM
--R ?*? : (Fraction Integer,%) -> % if R has INTDOM
--R ?**? : (%,Integer) -> % if R has GROUP or R has INTDOM
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (SparseMultivariatePolynomial(R,Kernel %),SparseMultivariatePolynomial(R,Kernel %)) ->
--R D : (%,Symbol,NonNegativeInteger) -> %
--R D : (%,List Symbol,List NonNegativeInteger) -> %
--R ?^? : (%,Integer) -> % if R has GROUP or R has INTDOM
--R ?^? : (%,NonNegativeInteger) -> %
--R applyQuote : (Symbol,List %) -> %
--R applyQuote : (Symbol,%,%,%,%) -> %
--R applyQuote : (Symbol,%,%,%) -> %
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R coerce : Fraction Integer -> % if R has INTDOM or R has RETRACT FRAC INT
--R coerce : Fraction MyUnivariatePolynomial(q,R) -> %
--R coerce : MyUnivariatePolynomial(q,R) -> %
```

```
--R coerce : Polynomial R -> % if R has RING
--R coerce : Fraction Polynomial R -> % if R has INTDOM
--R coerce : Fraction Polynomial Fraction R -> % if R has INTDOM
--R coerce : Polynomial Fraction R -> % if R has INTDOM
--R coerce : Fraction R -> % if R has INTDOM
--R coerce : SparseMultivariatePolynomial(R,Kernel %) -> % if R has RING
--R commutator : (%,%) -> % if R has GROUP
--R conjugate : (%,%) -> % if R has GROUP
--R convert : % -> InputForm if R has KONVERT INFORM
--R convert : Factored % -> % if R has INTDOM
--R convert : % -> Pattern Float if R has KONVERT PATTERN FLOAT
--R convert : % -> Pattern Integer if R has KONVERT PATTERN INT
--R definingPolynomial : % -> % if $ has RING
--R denom : % -> SparseMultivariatePolynomial(R,Kernel %) if R has INTDOM
--R differentiate : (%,List Symbol) -> %
--R differentiate : (%,Symbol,NonNegativeInteger) -> %
--R differentiate : (%,List Symbol,List NonNegativeInteger) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has INTDOM
--R elt : (BasicOperator,List %) -> %
--R elt : (BasicOperator,%,%,%,%) -> %
--R elt : (BasicOperator,%,%,%) -> %
--R euclideanSize : % -> NonNegativeInteger if R has INTDOM
--R eval : (%,Symbol,NonNegativeInteger,(% -> %)) -> % if R has RING
--R eval : (%,Symbol,NonNegativeInteger,(List % -> %)) -> % if R has RING
--R eval : (%,List Symbol,List NonNegativeInteger,List (List % -> %)) -> % if R has RING
--R eval : (%,List Symbol,List NonNegativeInteger,List (% -> %)) -> % if R has RING
--R eval : (%,List BasicOperator,List %,Symbol) -> % if R has KONVERT INFORM
--R eval : (%,BasicOperator,%,Symbol) -> % if R has KONVERT INFORM
--R eval : % -> % if R has KONVERT INFORM
--R eval : (%,List Symbol) -> % if R has KONVERT INFORM
--R eval : (%,Symbol) -> % if R has KONVERT INFORM
--R eval : (%,BasicOperator,(% -> %)) -> %
--R eval : (%,BasicOperator,(List % -> %)) -> %
--R eval : (%,List BasicOperator,List (List % -> %)) -> %
--R eval : (%,List BasicOperator,List (% -> %)) -> %
--R eval : (%,Symbol,(% -> %)) -> %
--R eval : (%,Symbol,(List % -> %)) -> %
--R eval : (%,List Symbol,List (List % -> %)) -> %
--R eval : (%,List Symbol,List (% -> %)) -> %
--R eval : (%,List Kernel %,List %) -> %
--R even? : % -> Boolean if $ has RETRACT INT
--R expressIdealMember : (List %,%) -> Union(List %,"failed") if R has INTDOM
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has INTDOM
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has INTDOM
--R factor : % -> Factored % if R has INTDOM
--R gcd : (%,%) -> % if R has INTDOM
--R gcd : List % -> % if R has INTDOM
--R gcdPolynomial : (SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> SparseUnivariatePolynomia
--R inv : % -> % if R has GROUP or R has INTDOM
```

```
--R is? : (%,BasicOperator) -> Boolean
--R isExpt : (%,Symbol) -> Union(Record(var: Kernel %,exponent: Integer),"failed") if R has RING
--R isExpt : (%,BasicOperator) -> Union(Record(var: Kernel %,exponent: Integer),"failed") if R h
--R isExpt : % -> Union(Record(var: Kernel %,exponent: Integer),"failed") if R has SGROUP
--R isMult : % -> Union(Record(coef: Integer,var: Kernel %),"failed") if R has ABELSG
--R isPlus : % -> Union(List %,"failed") if R has ABELSG
--R isPower : % -> Union(Record(val: %,exponent: Integer),"failed") if R has RING
--R isTimes : % -> Union(List %,"failed") if R has SGROUP
--R kernel : (BasicOperator,List %) -> %
--R lcm : (%,%) -> % if R has INTDOM
--R lcm : List % -> % if R has INTDOM
--R mainKernel : % -> Union(Kernel %,"failed")
--R minPoly : Kernel % -> SparseUnivariatePolynomial % if $ has RING
--R multiEuclidean : (List %,%) -> Union(List %,"failed") if R has INTDOM
--R numer : % -> SparseMultivariatePolynomial(R,Kernel %) if R has RING
--R odd? : % -> Boolean if $ has RETRACT INT
--R operator : BasicOperator -> BasicOperator
--R operators : % -> List BasicOperator
--R patternMatch : (%,Pattern Float,PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R patternMatch : (%,Pattern Integer,PatternMatchResult(Integer,%)) -> PatternMatchResult(Integ
--R prime? : % -> Boolean if R has INTDOM
--R principalIdeal : List % -> Record(coef: List %,generator: %) if R has INTDOM
--R product : (%,SegmentBinding %) -> %
--R ?quo? : (%,%) -> % if R has INTDOM
--R reducedSystem : Matrix % -> Matrix Integer if R has LINEXP INT and R has RING
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix Integer,vec: Vector Integer) if R
--R reducedSystem : Matrix % -> Matrix R if R has RING
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix R,vec: Vector R) if R has RING
--R ?rem? : (%,%) -> % if R has INTDOM
--R retract : % -> Fraction Integer if R has INTDOM and R has RETRACT INT or R has RETRACT FRAC
--R retract : % -> Fraction MyUnivariatePolynomial(q,R)
--R retract : % -> MyUnivariatePolynomial(q,R)
--R retract : % -> Polynomial R if R has RING
--R retract : % -> Fraction Polynomial R if R has INTDOM
--R retractIfCan : % -> Union(Fraction Integer,"failed") if R has INTDOM and R has RETRACT INT o
--R retractIfCan : % -> Union(Integer,"failed")
--R retractIfCan : % -> Union(MyUnivariatePolynomial(q,R),"failed")
--R retractIfCan : % -> Union(Polynomial R,"failed") if R has RING
--R retractIfCan : % -> Union(Fraction Polynomial R,"failed") if R has INTDOM
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Symbol,"failed")
--R retractIfCan : % -> Union(Kernel %,"failed")
--R sizeLess? : (%,%) -> Boolean if R has INTDOM
--R squareFree : % -> Factored % if R has INTDOM
--R squareFreePart : % -> % if R has INTDOM
--R subst : (%,List Kernel %,List %) -> %
--R subst : (%,List Equation %) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R summation : (%,SegmentBinding %) -> %
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
```

```
--R univariate : (%,Kernel %) -> Fraction SparseUnivariatePolynomial % if R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— **MyExpression.help** —

```
=====================================================================
MyExpression examples
=====================================================================

See Also:
o )show MyExpression
```

———-

14.17.1 MyExpression (MYEXPR)



See

⇒ “MyUnivariatePolynomial” (MYUP) 14.18.1 on page 1662

Exports:

0	1	applyQuote	associates?
belong?	binomial	box	characteristic
charthRoot	coerce	commutator	conjugate
convert	D	definingPolynomial	denom
denominator	differentiate	distribute	divide
elt	euclideanSize	eval	even?
expressIdealMember	exquo	extendedEuclidean	factor
factorial	factorials	freeOf?	gcd
gcdPolynomial	ground	ground?	hash
height	inv	is?	is?
isExpt	isMult	isPlus	isPower
isTimes	kernel	kernels	latex
lcm	mainKernel	map	max
min	minPoly	multiEuclidean	numer
numerator	odd?	one?	operator
operators	paren	patternMatch	permutation
prime?	principalIdeal	product	recip
reducedSystem	retract	retractIfCan	sample
sizeLess?	squareFree	squareFreePart	subst
subtractIfCan	summation	tower	unit?
unitCanonical	unitNormal	univariate	variables
zero?	?*?	?**?	?+?
-?	?-?	?/?	?<?
?<=?	?=?	?>?	?>=?
?^?	?~=?	?quo?	?rem?

— domain MYEXPR MyExpression —

```
)abbrev domain MYEXPR MyExpression
++ Author: Mark Botch
++ Description:
++ This domain has no description

MyExpression(q: Symbol, R): Exports == Implementation where

  R: Join(Ring, OrderedSet, IntegralDomain)
  UP ==> MyUnivariatePolynomial(q, R)

  Exports == Join(FunctionSpace R, IntegralDomain,
               RetractableTo UP, RetractableTo Symbol,
               RetractableTo Integer, CombinatorialOpsCategory,
               PartialDifferentialRing Symbol) with
             _* : (%,%) -> %
             _/ : (%,%) -> %
             _*_* : (%,%) -> %
             numerator : % -> %
             denominator : % -> %
             ground? : % -> Boolean
```

```
            coerce: Fraction UP -> %
            retract: % -> Fraction UP

  Implementation == Expression R add
    Rep := Expression R

    iunivariate(p: Polynomial R): UP ==
        poly: SparseUnivariatePolynomial(Polynomial R)
             := univariate(p, q)$(Polynomial R)
        map((z1:Polynomial R):R +-> retract(z1), poly)_
          $UnivariatePolynomialCategoryFunctions2(Polynomial R,
                    SparseUnivariatePolynomial Polynomial R,
                    R, UP)

    retract(p: %): Fraction UP ==
        poly: Fraction Polynomial R := retract p
        upoly: UP := iunivariate numer poly
        vpoly: UP := iunivariate denom poly

        upoly / vpoly

    retract(p: %): UP == iunivariate retract p

    coerce(r: Fraction UP): % ==
       num: SparseUnivariatePolynomial R := makeSUP numer r
       den: SparseUnivariatePolynomial R := makeSUP denom r
       u: Polynomial R := multivariate(num, q)
       v: Polynomial R := multivariate(den, q)

       quot: Fraction Polynomial R := u/v

       quot::(Expression R)
```

———-

— MYEXPR.dotabb —

```
"MYEXPR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MYEXPR"]
"MYUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MYUP"]
"MYEXPR" -> "MYUP"
```

———-

14.18 domain MYUP MyUnivariatePolynomial

— MyUnivariatePolynomial.input —

```
)set break resume
)sys rm -f MyUnivariatePolynomial.output
)spool MyUnivariatePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show MyUnivariatePolynomial
--R MyUnivariatePolynomial(x: Symbol,R: Ring)  is a domain constructor
--R Abbreviation for MyUnivariatePolynomial is MYUP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for MYUP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> %
--R D : (%,NonNegativeInteger) -> %       1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coefficients : % -> List R            coerce : Symbol -> %
--R coerce : Polynomial R -> %            coerce : Variable x -> %
--R coerce : R -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              degree : % -> NonNegativeInteger
--R differentiate : % -> %                ?.? : (%,%) -> %
--R ?.? : (%,R) -> R                      eval : (%,List %,List %) -> %
--R eval : (%,%,%) -> %                   eval : (%,Equation %) -> %
--R eval : (%,List Equation %) -> %       ground : % -> R
--R ground? : % -> Boolean                hash : % -> SingleInteger
--R init : () -> % if R has STEP          latex : % -> String
--R leadingCoefficient : % -> R           leadingMonomial : % -> %
--R map : ((R -> R),%) -> %               monomial? : % -> Boolean
--R monomials : % -> List %               one? : % -> Boolean
--R primitiveMonomials : % -> List %      pseudoRemainder : (%,%) -> %
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R retract : % -> Symbol                 retract : % -> R
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction Integer,%) -> % if R has ALGEBRA FRAC INT
--R ?*? : (%,Fraction Integer) -> % if R has ALGEBRA FRAC INT
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
```

```
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List Symbol,List NonNegativeInteger) -> % if R has PDRING SYMBOL
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING SYMBOL
--R D : (%,List Symbol) -> % if R has PDRING SYMBOL
--R D : (%,Symbol) -> % if R has PDRING SYMBOL
--R D : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R D : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R D : (%,List SingletonAsOrderedSet) -> %
--R D : (%,SingletonAsOrderedSet) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R coefficient : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction Integer -> % if R has ALGEBRA FRAC INT or R has RETRACT FRAC INT
--R coerce : SingletonAsOrderedSet -> %
--R composite : (Fraction %,%) -> Union(Fraction %,"failed") if R has INTDOM
--R composite : (%,%) -> Union(%,"failed") if R has INTDOM
--R conditionP : Matrix % -> Union(Vector %,"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SingletonAsOrderedSet has KONVERT INFORM and R has KONVERT INFORM
--R convert : % -> Pattern Integer if SingletonAsOrderedSet has KONVERT PATTERN INT and R has KONVERT PATTEI
--R convert : % -> Pattern Float if SingletonAsOrderedSet has KONVERT PATTERN FLOAT and R has KONVERT PATTEI
--R degree : (%,List SingletonAsOrderedSet) -> List NonNegativeInteger
--R degree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R differentiate : (%,(R -> R),%) -> %
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List Symbol,List NonNegativeInteger) -> % if R has PDRING SYMBOL
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING SYMBOL
--R differentiate : (%,List Symbol) -> % if R has PDRING SYMBOL
--R differentiate : (%,Symbol) -> % if R has PDRING SYMBOL
--R differentiate : (%,NonNegativeInteger) -> %
--R differentiate : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R differentiate : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R differentiate : (%,List SingletonAsOrderedSet) -> %
--R differentiate : (%,SingletonAsOrderedSet) -> %
--R discriminant : % -> R if R has COMRING
--R discriminant : (%,SingletonAsOrderedSet) -> % if R has COMRING
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R divideExponents : (%,NonNegativeInteger) -> Union(%,"failed")
--R ?.? : (%,Fraction %) -> Fraction % if R has INTDOM
--R elt : (Fraction %,R) -> R if R has FIELD
```

```
--R elt : (Fraction %,Fraction %) -> Fraction % if R has INTDOM
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R eval : (%,List SingletonAsOrderedSet,List %) -> %
--R eval : (%,SingletonAsOrderedSet,%) -> %
--R eval : (%,List SingletonAsOrderedSet,List R) -> %
--R eval : (%,SingletonAsOrderedSet,R) -> %
--R expressIdealMember : (List %,%) -> Union(List %,"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R factor : % -> Factored % if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial % if
--R factorSquareFreePolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolyno
--R fmecg : (%,NonNegativeInteger,R,%) -> %
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List % -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> SparseUnivari
--R integrate : % -> % if R has ALGEBRA FRAC INT
--R isExpt : % -> Union(Record(var: SingletonAsOrderedSet,exponent: NonNegativeInteger),"failed"
--R isPlus : % -> Union(List %,"failed")
--R isTimes : % -> Union(List %,"failed")
--R karatsubaDivide : (%,NonNegativeInteger) -> Record(quotient: %,remainder: %)
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List % -> % if R has GCDDOM
--R mainVariable : % -> Union(SingletonAsOrderedSet,"failed")
--R makeSUP : % -> SparseUnivariatePolynomial R
--R mapExponents : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List SingletonAsOrderedSet) -> List NonNegativeInteger
--R minimumDegree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R minimumDegree : % -> NonNegativeInteger
--R monicDivide : (%,%) -> Record(quotient: %,remainder: %)
--R monicDivide : (%,%,SingletonAsOrderedSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (R,NonNegativeInteger) -> %
--R multiEuclidean : (List %,%) -> Union(List %,"failed") if R has FIELD
--R multiplyExponents : (%,NonNegativeInteger) -> %
--R multivariate : (SparseUnivariatePolynomial %,SingletonAsOrderedSet) -> %
--R multivariate : (SparseUnivariatePolynomial R,SingletonAsOrderedSet) -> %
--R nextItem : % -> Union(%,"failed") if R has STEP
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,%) -> NonNegativeInteger if R has INTDOM
--R patternMatch : (%,Pattern Integer,PatternMatchResult(Integer,%)) -> PatternMatchResult(Integ
--R patternMatch : (%,Pattern Float,PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pomopo! : (%,R,NonNegativeInteger,%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitivePart : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
```

```
--R primitivePart : % -> % if R has GCDDOM
--R principalIdeal : List % -> Record(coef: List %,generator: %) if R has FIELD
--R pseudoDivide : (%,%) -> Record(coef: R,quotient: %,remainder: %) if R has INTDOM
--R pseudoQuotient : (%,%) -> % if R has INTDOM
--R ?quo? : (%,%) -> % if R has FIELD
--R reducedSystem : Matrix % -> Matrix R
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix R,vec: Vector R)
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix Integer,vec: Vector Integer) if R has LINEXP
--R reducedSystem : Matrix % -> Matrix Integer if R has LINEXP INT
--R ?rem? : (%,%) -> % if R has FIELD
--R resultant : (%,%) -> R if R has COMRING
--R resultant : (%,%,SingletonAsOrderedSet) -> % if R has COMRING
--R retract : % -> SingletonAsOrderedSet
--R retract : % -> Integer if R has RETRACT INT
--R retract : % -> Fraction Integer if R has RETRACT FRAC INT
--R retractIfCan : % -> Union(Symbol,"failed")
--R retractIfCan : % -> Union(SingletonAsOrderedSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT INT
--R retractIfCan : % -> Union(Fraction Integer,"failed") if R has RETRACT FRAC INT
--R retractIfCan : % -> Union(R,"failed")
--R separate : (%,%) -> Record(primePart: %,commonPart: %) if R has GCDDOM
--R shiftLeft : (%,NonNegativeInteger) -> %
--R shiftRight : (%,NonNegativeInteger) -> %
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R solveLinearPolynomialEquation : (List SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> Uni
--R squareFree : % -> Factored % if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial % if R has P
--R subResultantGcd : (%,%) -> % if R has INTDOM
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List SingletonAsOrderedSet) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial R
--R univariate : (%,SingletonAsOrderedSet) -> SparseUnivariatePolynomial %
--R unmakeSUP : SparseUnivariatePolynomial R -> %
--R variables : % -> List SingletonAsOrderedSet
--R vectorise : (%,NonNegativeInteger) -> Vector R
--R
--E 1

)spool
)lisp (bye)
```


———-

— MyUnivariatePolynomial.help —

```
========================================================================
MyUnivariatePolynomial examples
========================================================================

See Also:
o )show MyUnivariatePolynomial
```

14.18.1 MyUnivariatePolynomial (MYUP)



See

⇒ “MyExpression” (MYEXPR) 14.17.1 on page 1655

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
composite	conditionP	content
convert	D	degree
differentiate	discriminant	divide
divideExponents	elt	euclideanSize
eval	expressIdealMember	exquo
extendedEuclidean	factor	factorPolynomial
factorSquareFreePolynomial	fmecg	gcd
gcdPolynomial	ground	ground?
hash	init	integrate
isExpt	isPlus	isTimes
karatsubaDivide	latex	lcm
leadingCoefficient	leadingMonomial	mainVariable
makeSUP	map	mapExponents
max	min	minimumDegree
monicDivide	monomial	monomial?
monomials	multiEuclidean	multiplyExponents
multivariate	nextItem	numberOfMonomials
one?	order	patternMatch
pomopo!	prime?	primitiveMonomials
primitivePart	principalIdeal	pseudoDivide
pseudoQuotient	pseudoRemainder	recip
reducedSystem	reductum	resultant
retract	retractIfCan	sample
separate	shiftLeft	shiftRight
sizeLess?	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subResultantGcd
subtractIfCan	totalDegree	unit?
unitCanonical	unitNormal	univariate
unmakeSUP	variables	vectorise
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?.?
?~=?	?/?	?<?
?<=?	?>?	?>=?
?^?	?quo?	?rem?

— domain MYUP MyUnivariatePolynomial —

```
)abbrev domain MYUP MyUnivariatePolynomial
++ Author: Mark Botch
++ Description:
++ This domain has no description

MyUnivariatePolynomial(x:Symbol, R:Ring):
```

```
  UnivariatePolynomialCategory(R) with
    RetractableTo Symbol;
    coerce: Variable(x) -> %
      ++ coerce(x) converts the variable x to a univariate polynomial.
    fmecg: (%,NonNegativeInteger,R,%) -> %
        ++ fmecg(p1,e,r,p2) finds x : p1 - r * x**e * p2
    if R has univariate: (R, Symbol) -> SparseUnivariatePolynomial R
    then coerce: R -> %
    coerce: Polynomial R -> %
   == SparseUnivariatePolynomial(R) add
    Rep := SparseUnivariatePolynomial(R)
    coerce(p: %):OutputForm  == outputForm(p, outputForm x)
    coerce(x: Symbol): % == monomial(1, 1)
    coerce(v: Variable(x)):% == monomial(1, 1)
    retract(p: %): Symbol ==
        retract(p)@SingletonAsOrderedSet
        x
    if R has univariate: (R, Symbol) -> SparseUnivariatePolynomial R
    then coerce(p: R): % == univariate(p, x)$R

    coerce(p: Polynomial R): % ==
        poly: SparseUnivariatePolynomial(Polynomial R)
             := univariate(p, x)$(Polynomial R)
        map((z1:Polynomial R):R +-> retract(z1), poly)_
             $UnivariatePolynomialCategoryFunctions2(Polynomial R,
                    SparseUnivariatePolynomial Polynomial R, R, %)
```

———-

— MYUP.dotabb —

```
"MYUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MYUP"]
"MYEXPR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=MYEXPR"]
"MYUP" -> "MYEXPR"
```

———-

Chapter 15

Chapter N

15.1 domain NSDPS NeitherSparseOrDensePowerSeries

— NeitherSparseOrDensePowerSeries.input —

```
)set break resume
)sys rm -f NeitherSparseOrDensePowerSeries.output
)spool NeitherSparseOrDensePowerSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NeitherSparseOrDensePowerSeries
--R
--R NeitherSparseOrDensePowerSeries(K: Field)  is a domain constructor
--R Abbreviation for NeitherSparseOrDensePowerSeries is NSDPS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for NSDPS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,K) -> %                      ?*? : (K,%) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean        center : % -> K
--R children : % -> List(%)               coefOfFirstNonZeroTerm : % -> K
```

```
--R coefficient : (%,Integer) -> K        coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              complete : % -> %
--R concat : (%,%) -> %                   concat : List(%) -> %
--R copy : % -> %                         cycleEntry : % -> %
--R cycleTail : % -> %                    cyclic? : % -> Boolean
--R degree : % -> Integer                 delay : (() -> %) -> %
--R delete : (%,Integer) -> %             distance : (%,%) -> Integer
--R ?.rest : (%,rest) -> %                ?.? : (%,Integer) -> K
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                explicitEntries? : % -> Boolean
--R explicitlyEmpty? : % -> Boolean       explicitlyFinite? : % -> Boolean
--R extend : (%,Integer) -> %             factor : % -> Factored(%)
--R filterUpTo : (%,Integer) -> %         findCoef : (%,Integer) -> K
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)          insert : (%,%,Integer) -> %
--R inv : % -> %                          latex : % -> String
--R lazy? : % -> Boolean                  lazyEvaluate : % -> %
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R leadingCoefficient : % -> K           leadingMonomial : % -> %
--R leaf? : % -> Boolean                  map : ((K -> K),%) -> %
--R monomial : (K,Integer) -> %           monomial? : % -> Boolean
--R nodes : % -> List(%)                  one? : % -> Boolean
--R order : % -> Integer                  order : % -> Integer
--R order : (%,Integer) -> Integer        pole? : % -> Boolean
--R posExpnPart : % -> %                  possiblyInfinite? : % -> Boolean
--R prime? : % -> Boolean                 printInfo : () -> Boolean
--R printInfo : Boolean -> Boolean        ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R ?rem? : (%,%) -> %                    removeFirstZeroes : % -> %
--R removeZeroes : % -> %                 removeZeroes : (Integer,%) -> %
--R rest : % -> %                         rst : % -> %
--R sample : () -> %                      sbt : (%,%) -> %
--R series : (Integer,K,%) -> %           shift : (%,Integer) -> %
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               tail : % -> %
--R truncate : (%,Integer) -> %           unit? : % -> Boolean
--R unitCanonical : % -> %                variable : % -> Symbol
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,K) -> % if K has FIELD
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if K has *: (Integer,K) -> K and K has PD
--R D : (%,Symbol,NonNegativeInteger) -> % if K has *: (Integer,K) -> K and K has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if K has *: (Integer,K) -> K and K has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if K has *: (Integer,K) -> K and K has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if K has *: (Integer,K) -> K
--R D : % -> % if K has *: (Integer,K) -> K
```

```
--R ?^? : (%,NonNegativeInteger) -> %
--R any? : ((Record(k: Integer,c: K) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R approximate : (%,Integer) -> K if K has **: (K,Integer) -> K and K has coerce: Symbol -> K
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if K has CHARNZ
--R child? : (%,%) -> Boolean if Record(k: Integer,c: K) has SETCAT
--R coerce : % -> Stream(Record(k: Integer,c: K))
--R coerce : Stream(Record(k: Integer,c: K)) -> %
--R coerce : K -> % if K has COMRING
--R concat : (Record(k: Integer,c: K),%) -> %
--R concat : (%,Record(k: Integer,c: K)) -> %
--R concat! : (%,%) -> % if $ has shallowlyMutable
--R concat! : (%,Record(k: Integer,c: K)) -> % if $ has shallowlyMutable
--R construct : List(Record(k: Integer,c: K)) -> %
--R convert : % -> InputForm if Record(k: Integer,c: K) has KONVERT(INFORM)
--R count : ((Record(k: Integer,c: K) -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (Record(k: Integer,c: K),%) -> NonNegativeInteger if $ has finiteAggregate and Record(k: Integer
--R cycleLength : % -> NonNegativeInteger
--R cycleSplit! : % -> % if $ has shallowlyMutable
--R delete : (%,UniversalSegment(Integer)) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if K has *: (Integer,K) -> K and K has PI
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if K has *: (Integer,K) -> K and K has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if K has *: (Integer,K) -> K and K has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if K has *: (Integer,K) -> K and K has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if K has *: (Integer,K) -> K
--R differentiate : % -> % if K has *: (Integer,K) -> K
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R ?.value : (%,value) -> Record(k: Integer,c: K)
--R ?.first : (%,first) -> Record(k: Integer,c: K)
--R ?.last : (%,last) -> Record(k: Integer,c: K)
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,Integer) -> Record(k: Integer,c: K)
--R elt : (%,Integer,Record(k: Integer,c: K)) -> Record(k: Integer,c: K)
--R ?.? : (%,%) -> % if Integer has SGROUP
--R entries : % -> List(Record(k: Integer,c: K))
--R entry? : (Record(k: Integer,c: K),%) -> Boolean if $ has finiteAggregate and Record(k: Integer,c: K) has
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,List(Equation(Record(k: Integer,c: K)))) -> % if Record(k: Integer,c: K) has EVALAB(Record(k:
--R eval : (%,Equation(Record(k: Integer,c: K))) -> % if Record(k: Integer,c: K) has EVALAB(Record(k: Integ
--R eval : (%,Record(k: Integer,c: K),Record(k: Integer,c: K)) -> % if Record(k: Integer,c: K) has EVALAB(R
--R eval : (%,List(Record(k: Integer,c: K)),List(Record(k: Integer,c: K))) -> % if Record(k: Integer,c: K) h
--R eval : (%,K) -> Stream(K) if K has **: (K,Integer) -> K
--R every? : ((Record(k: Integer,c: K) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R fill! : (%,Record(k: Integer,c: K)) -> % if $ has shallowlyMutable
--R find : ((Record(k: Integer,c: K) -> Boolean),%) -> Union(Record(k: Integer,c: K),"failed")
--R findTerm : (%,Integer) -> Record(k: Integer,c: K)
```

```
--R first : % -> Record(k: Integer,c: K)
--R first : (%,NonNegativeInteger) -> %
--R frst : % -> Record(k: Integer,c: K)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R insert : (Record(k: Integer,c: K),%,Integer) -> %
--R last : % -> Record(k: Integer,c: K)
--R last : (%,NonNegativeInteger) -> %
--R leaves : % -> List(Record(k: Integer,c: K))
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : ((Record(k: Integer,c: K) -> Record(k: Integer,c: K)),%) -> %
--R map : (((Record(k: Integer,c: K),Record(k: Integer,c: K)) -> Record(k: Integer,c: K)),%,%) -
--R map! : ((Record(k: Integer,c: K) -> Record(k: Integer,c: K)),%) -> % if $ has shallowlyMutab
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (Record(k: Integer,c: K),%) -> Boolean if $ has finiteAggregate and Record(k: Inte
--R members : % -> List(Record(k: Integer,c: K)) if $ has finiteAggregate
--R minIndex : % -> Integer if Integer has ORDSET
--R monomial : (%,SingletonAsOrderedSet,Integer) -> %
--R monomial : (%,List(SingletonAsOrderedSet),List(Integer)) -> %
--R monomial2series : (List(%),List(NonNegativeInteger),Integer) -> %
--R more? : (%,NonNegativeInteger) -> Boolean
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R multiplyExponents : (%,PositiveInteger) -> %
--R new : (NonNegativeInteger,Record(k: Integer,c: K)) -> %
--R node? : (%,%) -> Boolean if Record(k: Integer,c: K) has SETCAT
--R numberOfComputedEntries : % -> NonNegativeInteger
--R orderIfNegative : % -> Union(Integer,"failed")
--R parts : % -> List(Record(k: Integer,c: K)) if $ has finiteAggregate
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R qelt : (%,Integer) -> Record(k: Integer,c: K)
--R qsetelt! : (%,Integer,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowly
--R reduce : (((Record(k: Integer,c: K),Record(k: Integer,c: K)) -> Record(k: Integer,c: K)),%)
--R reduce : (((Record(k: Integer,c: K),Record(k: Integer,c: K)) -> Record(k: Integer,c: K)),%,R
--R reduce : (((Record(k: Integer,c: K),Record(k: Integer,c: K)) -> Record(k: Integer,c: K)),%,R
--R remove : (Record(k: Integer,c: K),%) -> % if $ has finiteAggregate and Record(k: Integer,c:
--R remove : ((Record(k: Integer,c: K) -> Boolean),%) -> %
--R removeDuplicates : % -> % if $ has finiteAggregate and Record(k: Integer,c: K) has SETCAT
--R rest : (%,NonNegativeInteger) -> %
--R second : % -> Record(k: Integer,c: K)
--R select : ((Record(k: Integer,c: K) -> Boolean),%) -> %
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,value,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMuta
--R setelt : (%,first,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMuta
--R setelt : (%,rest,%) -> % if $ has shallowlyMutable
--R setelt : (%,last,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMutab
--R setelt : (%,UniversalSegment(Integer),Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if
--R setelt : (%,Integer,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMu
--R setfirst! : (%,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMutable
--R setlast! : (%,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMutable
--R setrest! : (%,%) -> % if $ has shallowlyMutable
--R setvalue! : (%,Record(k: Integer,c: K)) -> Record(k: Integer,c: K) if $ has shallowlyMutable
```

```
--R size? : (%,NonNegativeInteger) -> Boolean
--R split! : (%,Integer) -> % if $ has shallowlyMutable
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R terms : % -> Stream(Record(k: Integer,c: K))
--R third : % -> Record(k: Integer,c: K)
--R truncate : (%,Integer,Integer) -> %
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R value : % -> Record(k: Integer,c: K)
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **NeitherSparseOrDensePowerSeries.help** —

```
========================================================================
NeitherSparseOrDensePowerSeries examples
========================================================================

See Also:
o )show NeitherSparseOrDensePowerSeries
```

———-

15.1.1 NeitherSparseOrDensePowerSeries (NSDPS)



Exports:

0
1
#?
-?
?**?
?*?
?+?
?-?
?.?
?.first
?.last
?.rest
?.value
?/?
?=?
?^?
?~=?
?quo?
?rem?
D
any?
approximate
associates?
center
characteristic
charthRoot
child?
children
coefOfFirstNonZeroTerm
coefficient
coerce
complete
concat
concat!
construct
convert
copy
count
cycleEntry
cycleLength
cycleSplit!
cycleTail
cyclic?
degree
delay
delete
differentiate
distance
divide
elt
empty
empty?
entries
entry?
eq?
euclideanSize
eval
every?
explicitEntries?
explicitlyEmpty?
explicitlyFinite?
expressIdealMember
exquo
extend
extendedEuclidean
factor
fill!
filterUpTo
find
findCoef
findTerm
first
frst
gcd
gcdPolynomial
hash
index?
indices
insert
inv
last
latex
lazy?
lazyEvaluate
lcm
leadingCoefficient
leadingMonomial
leaf?
leaves
less?
map
map!
maxIndex
member?
members
minIndex
monomial
monomial2series
monomial?
more?
multiEuclidean
multiplyExponents
new
node?
nodes
numberOfComputedEntries
one?
order
orderIfNegative
parts
pole?
posExpnPart
possiblyInfinite?
prime?
principalIdeal
printInfo
qelt
qsetelt!
recip
reduce
reductum
remove
removeDuplicates
removeFirstZeroes
removeZeroes
rest
rst
sample
sbt
second
select
series
setchildren!
setelt
setfirst!
setlast!
setrest!
setvalue!
shift
size?
sizeLess?
split!
squareFree
squareFreePart
subtractIfCan
swap!
tail
terms
third
truncate
unit?
unitCanonical
unitNormal
value
variable
variables
zero?

— domain NSDPS NeitherSparseOrDensePowerSeries —

```
)abbrev domain NSDPS NeitherSparseOrDensePowerSeries
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain is part of the PAFF package
NeitherSparseOrDensePowerSeries(K):Exports == Implementation where
  K:Field

  SI   ==> SingleInteger
  INT  ==> Integer
  TERM ==> Record(k:INT,c:K)
  SER  ==> Stream(TERM)
  NNI  ==> NonNegativeInteger

  Exports ==> Join(LocalPowerSeriesCategory(K),LazyStreamAggregate(TERM)) with

    findTerm: (%,Integer) -> TERM

  Implementation ==> SER add

    Rep:=SER

    var : Symbol := 't

    multC: (K,INT,%) -> %

    orderIfNegative(s:%)==
      zero?(s) => "failed"
      f:=frst(s)
      f.k >= 0 => "failed"
      zero?(f.c) => orderIfNegative(rest(s))
      f.k

    posExpnPart(s)==
      zero?(s) => 0
      o:=order s
      (o >= 0) => s
      posExpnPart(rst s)

    findTerm(s,n)==
      empty?(s) =>  [n,0]$TERM
      f:=frst(s)
      f.k > n => [n,0]$TERM
      f.k = n => f
      findTerm(rst(s),n)
```

```
findCoef(s,i)==findTerm(s,i).c

coerce(s:%):SER == s::Rep

coerce(s:SER):%==s

localVarForPrintInfo:Boolean:=false()

printInfo==localVarForPrintInfo

printInfo(flag)==localVarForPrintInfo:=flag

outTerm: TERM -> OutputForm

removeZeroes(s)== delay
  zero?(s) => 0
  f:=frst(s)
  zero?(f.c) => removeZeroes(rst(s))
  concat(f,removeZeroes(rst(s)))

inv(ra)==
  a:=removeFirstZeroes ra
  o:=-order(a)
  aa:=shift(a,o)
  aai:=recip aa
  aai case "failed" => _
    error "Big problem in inv function from CreateSeries"
  shift(aai,o)

iDiv: (%,%,K) -> %
iDiv(x,y,ry0) == delay
 empty? x => 0$%
 sx:TERM:=frst x
 c0:K:=ry0 * sx.c
 nT:TERM:=[sx.k, c0]
 tc0:%:=series(sx.k,c0,0$%)
 concat(nT,iDiv(rst x - tc0 * rst y,y,ry0))

recip x ==
  empty? x => "failed"
  rh1:TERM:=frst x
  ^zero?(rh1.k) => "failed"
  ic:K:= inv(rh1.c)
  delay
    concat([0,ic]$TERM,iDiv(- ic * rst x,x,ic))

removeFirstZeroes(s)==
  zero?(s) => 0
  f:=frst(s)
  zero?(f.c) => removeFirstZeroes(rst(s))
```

```
    s

  sbt(sa,sbb)== delay
    sb:=removeFirstZeroes(sbb)
    o:=order sb
    ^(o > 0) => _
       error "Cannot substitute by a series of order less than 1  !!!!!"
    empty?(sa) or empty?(sb) => 0
    fa:TERM:=frst(sa)
    fb:TERM:=frst(sb)
    firstElem:TERM:=[fa.k*fb.k, fa.c*(fb.c**fa.k)]
    zero?(fa.c) => sbt(rst(sa),sb)
    concat(firstElem,  rest((fa.c) * sb ** (fa.k)) + sbt(rst(sa),sb)  )

  coerce(s:%):OutputForm==
    zero?(s) => "0" :: OutputForm
    count:SI:= _$streamCount$Lisp
    lstTerm:List TERM:=empty()
    rs:%:= s
    for i in 1..count while  ^empty?(rs) repeat
      fs:=frst rs
      rs:=rst rs
      lstTerm:=concat(lstTerm,fs)
    listOfOutTerm:List OutputForm:=_
      [outTerm(t) for t in lstTerm | ^zero?(t.c) ]
    out:OutputForm:=
      if empty?(listOfOutTerm) then
        "0" :: OutputForm
      else
        reduce("+", listOfOutTerm)
    empty?(rs) => out
    out +  ("..." :: OutputForm)

  outTerm(t)==
    ee:=t.k
    cc:=t.c
    oe:OutputForm:=ee::OutputForm
    oc:OutputForm:=cc::OutputForm
    symb:OutputForm:= var :: OutputForm
    one?(cc) and one?(ee) => symb
    zero?(ee) => oc
    one?(cc) => symb ** oe
    one?(ee) => oc * symb
    oc * symb ** oe

  removeZeroes(n,s)== delay
    n < 0 => s
    zero?(s) => 0
    f:=frst(s)
    zero?(f.c) => removeZeroes(n-1, rst(s))
```

```
    concat(f,removeZeroes(n-1, rst(s)))

  order(s:%)==
    zero?(s) => error _
     "From order (PlaneCurveLocalPowerSeries): cannot compute the order of 0"
    f:=frst(s)
    zero?(f.c) => order(rest(s))
    f.k

  monomial2series(lpar,lexp,sh)==
    shift(reduce("*",[s**e for s in lpar for e in lexp]),sh)

  coefOfFirstNonZeroTerm(s:%)==
    zero?(s) => error _
     "From order (PlaneCurveLocalPowerSeries): cannot find the coefOfFirstNonZeroTerm"
    f:=frst(s)
    zero?(f.c) => coefOfFirstNonZeroTerm(rest(s))
    f.c

  degreeOfTermLower?: (TERM,INT) -> Boolean
  degreeOfTermLower?(t,n)== t.k < n

  filterUpTo(s,n)==filterWhile(degreeOfTermLower?(#1,n),s)

  series(exp,coef,s)==cons([exp,coef]$TERM,s)

  a:% ** n:NNI == -- delay
    zero?(n) => 1
    expt(a,n :: PositiveInteger)$RepeatedSquaring(%)

  0 == empty()

  1 == construct([[0,1]$TERM])

  zero?(a)==empty?(a::Rep)

  shift(s,n)== delay
    zero?(s) => 0
    fs:=frst(s)
    es:=fs.k
    concat([es+n,fs.c]$TERM,shift(rest(s),n))

  a:% + b:% == delay
      zero?(a) => b
      zero?(b) => a
      fa:=frst(a)
      fb:=frst(b)
      ea:=fa.k
      eb:=fb.k
      nc:K
```

```
        ea = eb => concat([ea,fa.c+fb.c]$TERM,rest(a) + rest(b))
        ea > eb => concat([eb,fb.c]$TERM,a + rest(b))
        eb > ea => concat([ea,fa.c]$TERM,rest(a) + b)

    - a:% == --delay
      multC( (-1) :: K , 0 , a)

    a:% - b:% == --delay
      a+(-b)

    multC(coef,n,s)== delay
        zero?(coef) => 0
        zero?(s) => 0
        f:=frst(s)
        concat([f.k+n,coef*f.c]$TERM,multC(coef,n,rest(s)))

    coef:K * s:% == delay
        zero?(coef) => 0
        zero?(s) => 0
        f:=frst(s)
        concat([f.k,coef*f.c]$TERM, coef *$% rest(s))

    s:% * coef:K == coef * s

    s1:% * s2:%== delay
        zero?(s1) or zero?(s2) => 0
        f1:TERM:=frst(s1)
        f2:TERM:=frst(s2)
        e1:INT:=f1.k; e2:INT:=f2.k
        c1:K:=f1.c;   c2:K:=f2.c
        concat([e1+e2,c1*c2]$TERM,_
               multC(c1,e1,rest(s2))+multC(c2,e2,rest(s1))+rest(s1)*rest(s2))
```

———-

— **NSDPS.dotabb** —

```
"NSDPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NSDPS"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"NSDPS" -> "ALIST"
```

———-

15.2 domain NSMP NewSparseMultivariatePolynomial

Based on the **PseudoRemainderSequence** package, the domain constructor **NewSparseMulitvariatePolynomial** extends the constructor **SparseMultivariatePolynomial**. It also provides some additional operations related to polynomial system solving by means of triangular sets.

— NewSparseMultivariatePolynomial.input —

```
)set break resume
)sys rm -f NewSparseMultivariatePolynomial.output
)spool NewSparseMultivariatePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NewSparseMultivariatePolynomial
--R
--R NewSparseMultivariatePolynomial(R: Ring,VarSet: OrderedSet)  is a domain constructor
--R Abbreviation for NewSparseMultivariatePolynomial is NSMP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for NSMP
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,List(VarSet)) -> %             D : (%,VarSet) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficients : % -> List(R)
--R coerce : VarSet -> %                  coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R deepestInitial : % -> %               deepestTail : % -> %
--R differentiate : (%,VarSet) -> %       eval : (%,VarSet,%) -> %
--R eval : (%,VarSet,R) -> %              eval : (%,%,%) -> %
--R eval : (%,Equation(%)) -> %           ground : % -> R
--R ground? : % -> Boolean                hash : % -> SingleInteger
--R head : % -> %                         headReduce : (%,%) -> %
--R headReduced? : (%,%) -> Boolean       infRittWu? : (%,%) -> Boolean
--R init : % -> %                         initiallyReduce : (%,%) -> %
--R iteratedInitials : % -> List(%)       latex : % -> String
--R lazyPquo : (%,%,VarSet) -> %          lazyPquo : (%,%) -> %
--R lazyPrem : (%,%,VarSet) -> %          lazyPrem : (%,%) -> %
--R leadingCoefficient : % -> R           leadingMonomial : % -> %
--R leastMonomial : % -> %                mainCoefficients : % -> List(%)
--R mainMonomial : % -> %                 mainMonomials : % -> List(%)
```

```
--R map : ((R -> R),%) -> %                mdeg : % -> NonNegativeInteger
--R monic? : % -> Boolean                  monicModulo : (%,%) -> %
--R monomial? : % -> Boolean               monomials : % -> List(%)
--R mvar : % -> VarSet                     normalized? : (%,%) -> Boolean
--R one? : % -> Boolean                    pquo : (%,%,VarSet) -> %
--R pquo : (%,%) -> %                      prem : (%,%,VarSet) -> %
--R prem : (%,%) -> %                      quasiMonic? : % -> Boolean
--R recip : % -> Union(%,"failed")         reduced? : (%,%) -> Boolean
--R reductum : (%,VarSet) -> %             reductum : % -> %
--R retract : % -> VarSet                  retract : % -> R
--R sample : () -> %                       supRittWu? : (%,%) -> Boolean
--R tail : % -> %                          variables : % -> List(VarSet)
--R zero? : % -> Boolean                   ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R D : (%,VarSet,NonNegativeInteger) -> %
--R LazardQuotient : (%,%,NonNegativeInteger) -> % if R has INTDOM
--R LazardQuotient2 : (%,%,%,NonNegativeInteger) -> % if R has INTDOM
--R RittWuCompare : (%,%) -> Union(Boolean,"failed")
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R coefficient : (%,VarSet,NonNegativeInteger) -> %
--R coefficient : (%,IndexedExponents(VarSet)) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : SparseMultivariatePolynomial(R,VarSet) -> %
--R coerce : % -> SparseMultivariatePolynomial(R,VarSet)
--R coerce : % -> Polynomial(R) if VarSet has KONVERT(SYMBOL)
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,VarSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> Polynomial(R) if VarSet has KONVERT(SYMBOL)
--R convert : % -> String if R has RETRACT(INT) and VarSet has KONVERT(SYMBOL)
--R convert : Polynomial(R) -> % if VarSet has KONVERT(SYMBOL)
--R convert : Polynomial(Integer) -> % if R has ALGEBRA(INT) and VarSet has KONVERT(SYMBOL) and not(has(R,Al
--R convert : Polynomial(Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT)) and VarSet has KONVERT(SYMBOL)
--R convert : % -> InputForm if R has KONVERT(INFORM) and VarSet has KONVERT(INFORM)
--R convert : % -> Pattern(Integer) if R has KONVERT(PATTERN(INT)) and VarSet has KONVERT(PATTERN(INT))
```

```
--R convert : % -> Pattern(Float) if R has KONVERT(PATTERN(FLOAT)) and VarSet has KONVERT(PATTER
--R degree : (%,List(VarSet)) -> List(NonNegativeInteger)
--R degree : (%,VarSet) -> NonNegativeInteger
--R degree : % -> IndexedExponents(VarSet)
--R differentiate : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R differentiate : (%,VarSet,NonNegativeInteger) -> %
--R differentiate : (%,List(VarSet)) -> %
--R discriminant : (%,VarSet) -> % if R has COMRING
--R eval : (%,List(VarSet),List(%)) -> %
--R eval : (%,List(VarSet),List(R)) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R exactQuotient : (%,%) -> % if R has INTDOM
--R exactQuotient : (%,R) -> % if R has INTDOM
--R exactQuotient! : (%,%) -> % if R has INTDOM
--R exactQuotient! : (%,R) -> % if R has INTDOM
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R extendedSubResultantGcd : (%,%) -> Record(gcd: %,coef1: %,coef2: %) if R has INTDOM
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcd : (R,%) -> R if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R halfExtendedSubResultantGcd1 : (%,%) -> Record(gcd: %,coef1: %) if R has INTDOM
--R halfExtendedSubResultantGcd2 : (%,%) -> Record(gcd: %,coef2: %) if R has INTDOM
--R headReduced? : (%,List(%)) -> Boolean
--R initiallyReduced? : (%,List(%)) -> Boolean
--R initiallyReduced? : (%,%) -> Boolean
--R isExpt : % -> Union(Record(var: VarSet,exponent: NonNegativeInteger),"failed")
--R isPlus : % -> Union(List(%),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R lastSubResultant : (%,%) -> % if R has INTDOM
--R lazyPremWithDefault : (%,%,VarSet) -> Record(coef: %,gap: NonNegativeInteger,remainder: %)
--R lazyPremWithDefault : (%,%) -> Record(coef: %,gap: NonNegativeInteger,remainder: %)
--R lazyPseudoDivide : (%,%,VarSet) -> Record(coef: %,gap: NonNegativeInteger,quotient: %,remain
--R lazyPseudoDivide : (%,%) -> Record(coef: %,gap: NonNegativeInteger,quotient: %,remainder: %)
--R lazyResidueClass : (%,%) -> Record(polnum: %,polden: %,power: NonNegativeInteger)
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R leadingCoefficient : (%,VarSet) -> %
--R mainContent : % -> % if R has GCDDOM
--R mainPrimitivePart : % -> % if R has GCDDOM
--R mainSquareFreePart : % -> % if R has GCDDOM
--R mainVariable : % -> Union(VarSet,"failed")
--R mapExponents : ((IndexedExponents(VarSet) -> IndexedExponents(VarSet)),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
```

```
--R minimumDegree : (%,List(VarSet)) -> List(NonNegativeInteger)
--R minimumDegree : (%,VarSet) -> NonNegativeInteger
--R minimumDegree : % -> IndexedExponents(VarSet)
--R monicDivide : (%,%,VarSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R monomial : (%,VarSet,NonNegativeInteger) -> %
--R monomial : (R,IndexedExponents(VarSet)) -> %
--R multivariate : (SparseUnivariatePolynomial(%),VarSet) -> %
--R multivariate : (SparseUnivariatePolynomial(R),VarSet) -> %
--R nextsubResultant2 : (%,%,%,%) -> % if R has INTDOM
--R normalized? : (%,List(%)) -> Boolean
--R numberOfMonomials : % -> NonNegativeInteger
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if R
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if R has PA
--R pomopo! : (%,R,IndexedExponents(VarSet),%) -> %
--R primPartElseUnitCanonical : % -> % if R has INTDOM
--R primPartElseUnitCanonical! : % -> % if R has INTDOM
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,VarSet) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R primitivePart! : % -> % if R has GCDDOM
--R pseudoDivide : (%,%) -> Record(quotient: %,remainder: %)
--R reduced? : (%,List(%)) -> Boolean
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LINE
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R resultant : (%,%) -> % if R has INTDOM
--R resultant : (%,%,VarSet) -> % if R has COMRING
--R retract : % -> SparseMultivariatePolynomial(R,VarSet)
--R retract : Polynomial(R) -> % if VarSet has KONVERT(SYMBOL) and not(has(R,Algebra(Fraction(Integer)))) an
--R retract : Polynomial(Integer) -> % if R has ALGEBRA(INT) and VarSet has KONVERT(SYMBOL) and not(has(R,Al
--R retract : Polynomial(Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT)) and VarSet has KONVERT(SYMBOL)
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(SparseMultivariatePolynomial(R,VarSet),"failed")
--R retractIfCan : Polynomial(R) -> Union(%,"failed") if VarSet has KONVERT(SYMBOL) and not(has(R,Algebra(Fr
--R retractIfCan : Polynomial(Integer) -> Union(%,"failed") if R has ALGEBRA(INT) and VarSet has KONVERT(SYM
--R retractIfCan : Polynomial(Fraction(Integer)) -> Union(%,"failed") if R has ALGEBRA(FRAC(INT)) and VarSet
--R retractIfCan : % -> Union(VarSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if R has
--R subResultantChain : (%,%) -> List(%) if R has INTDOM
--R subResultantGcd : (%,%) -> % if R has INTDOM
```

```
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List(VarSet)) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,VarSet) -> SparseUnivariatePolynomial(%)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **NewSparseMultivariatePolynomial.help** —

```
====================================================================
NewSparseMultivariatePolynomial examples
====================================================================

See Also:
o )show NewSparseMultivariatePolynomial
```

———-

15.2.1 NewSparseMultivariatePolynomial (NSMP)



See

⇒ “NewSparseUnivariatePolynomial” (NSUP) 15.3.1 on page 1695

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	D
degree	deepestInitial	deepestTail
differentiate	discriminant	eval
exactQuotient	exactQuotient!	exquo
extendedSubResultantGcd	factor	factorPolynomial
factorSquareFreePolynomial	gcd	gcdPolynomial
halfExtendedSubResultantGcd1	ground	ground?
halfExtendedSubResultantGcd2	hash	head
headReduce	headReduced?	infRittWu?
init	initiallyReduce	initiallyReduced?
isExpt	isPlus	isTimes
iteratedInitials	lastSubResultant	latex
LazardQuotient	LazardQuotient2	lazyPremWithDefault
lazyPquo	lazyPrem	lazyPseudoDivide
lazyResidueClass	lcm	leadingCoefficient
leadingMonomial	leastMonomial	mainCoefficients
mainContent	mainMonomial	mainMonomials
mainPrimitivePart	mainSquareFreePart	mainVariable
map	mapExponents	max
mdeg	min	minimumDegree
monic?	monicDivide	monicModulo
monomial	monomial?	monomials
multivariate	mvar	nextsubResultant2
normalized?	numberOfMonomials	one?
patternMatch	pomopo!	pquo
primPartElseUnitCanonical!	primPartElseUnitCanonical	prem
prime?	primitiveMonomials	primitivePart
primitivePart!	pseudoDivide	reducedSystem
resultant	retract	retractIfCan
RittWuCompare	quasiMonic?	recip
reduced?	reductum	retract
sample	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subResultantChain
subResultantGcd	supRittWu?	subtractIfCan
tail	totalDegree	unit?
unitCanonical	unitNormal	univariate
univariate	variables	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?~=?	?/?
?<?	?<=?	?>?
?>=?		

— domain NSMP NewSparseMultivariatePolynomial —

```
)abbrev domain NSMP NewSparseMultivariatePolynomial
++ Author: Marc Moreno Maza
++ Date Created: 22/04/94
++ Date Last Updated: 14/12/1998
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A post-facto extension for \axiomType{SMP} in order
++ to speed up operations related to pseudo-division and gcd.
++ This domain is based on the \axiomType{NSUP} constructor which is
++ itself a post-facto extension of the \axiomType{SUP} constructor.

NewSparseMultivariatePolynomial(R,VarSet) : Exports == Implementation where
  R:Ring
  VarSet:OrderedSet
  N ==> NonNegativeInteger
  Z ==> Integer
  SUP ==> NewSparseUnivariatePolynomial
  SMPR ==> SparseMultivariatePolynomial(R, VarSet)
  SUP2 ==> NewSparseUnivariatePolynomialFunctions2($,$)

  Exports == Join(RecursivePolynomialCategory(R,IndexedExponents VarSet,_
                 VarSet), CoercibleTo(SMPR),RetractableTo(SMPR))

  Implementation ==  SparseMultivariatePolynomial(R, VarSet) add

     D := NewSparseUnivariatePolynomial($)
     VPoly:=  Record(v:VarSet,ts:D)
     Rep:= Union(R,VPoly)

    --local function
     PSimp: (D,VarSet) -> %

     PSimp(up,mv) ==
       if degree(up) = 0 then leadingCoefficient(up) else [mv,up]$VPoly

     coerce (p:$):SMPR ==
       p pretend SMPR

     coerce (p:SMPR):$ ==
       p pretend $
```

```
retractIfCan (p:$) : Union(SMPR,"failed") ==
  (p pretend SMPR)::Union(SMPR,"failed")

mvar p ==
  p case R => error" Error in mvar from NSMP : #1 has no variables."
  p.v

mdeg p ==
  p case R => 0$N
  degree(p.ts)$D

init p ==
  p case R => error" Error in init from NSMP : #1 has no variables."
  leadingCoefficient(p.ts)$D

head p ==
  p case R => p
  ([p.v,leadingMonomial(p.ts)$D]$VPoly)::Rep

tail p ==
  p case R => 0$$
  red := reductum(p.ts)$D
  ground?(red)$D => (ground(red)$D)::Rep
  ([p.v,red]$VPoly)::Rep

iteratedInitials p ==
  p case R => []
  p := leadingCoefficient(p.ts)$D
  cons(p,iteratedInitials(p))

localDeepestInitial (p : $) : $ ==
  p case R => p
  localDeepestInitial leadingCoefficient(p.ts)$D

deepestInitial p ==
  p case R =>
    error"Error in deepestInitial from NSMP : #1 has no variables."
  localDeepestInitial leadingCoefficient(p.ts)$D

mainMonomial p ==
  zero? p =>
    error"Error in mainMonomial from NSMP : the argument is zero"
  p case R => 1$$
  monomial(1$$,p.v,degree(p.ts)$D)

leastMonomial p ==
  zero? p =>
    error"Error in leastMonomial from NSMP : the argument is zero"
  p case R => 1$$
  monomial(1$$,p.v,minimumDegree(p.ts)$D)
```

```
    mainCoefficients p ==
      zero? p =>
        error"Error in mainCoefficients from NSMP : the argument is zero"
      p case R => [p]
      coefficients(p.ts)$D

    leadingCoefficient(p:$,x:VarSet):$ ==
      (p case R) => p
      p.v = x => leadingCoefficient(p.ts)$D
      zero? (d := degree(p,x)) => p
      coefficient(p,x,d)

    localMonicModulo(a:$,b:$):$ ==
      -- b is assumed to have initial 1
      a case R => a
      a.v < b.v => a
      mM: $
      if a.v > b.v
        then
          m : D := map((a1:%):% +-> localMonicModulo(a1,b),a.ts)$SUP2
        else
          m : D := monicModulo(a.ts,b.ts)$D
      if ground?(m)$D
         then
           mM := (ground(m)$D)::Rep
         else
           mM := ([a.v,m]$VPoly)::Rep
      mM

    monicModulo (a,b) ==
      b case R => error"Error in monicModulo from NSMP : #2 is constant"
      ib : $ := init(b)@$
      not ground?(ib)$$ =>
        error"Error in monicModulo from NSMP : #2 is not monic"
      mM : $
--      if not one?(ib)$$
      if not ((ib) = 1)$$
        then
          r : R := ground(ib)$$
          rec : Union(R,"failed"):= recip(r)$R
          (rec case "failed") =>
            error"Error in monicModulo from NSMP : #2 is not monic"
          a case R => a
          a := (rec::R) * a
          b := (rec::R) * b
          mM := ib * localMonicModulo (a,b)
        else
          mM := localMonicModulo (a,b)
      mM
```

```
prem(a:$, b:$): $ ==
  -- with pseudoRemainder$NSUP
  b case R =>
    error "in prem$NSMP: ground? #2"
  db: N := degree(b.ts)$D
  lcb: $ := leadingCoefficient(b.ts)$D
  test: Z := degree(a,b.v)::Z - db
  delta: Z := max(test + 1$Z, 0$Z)
  (a case R) or (a.v < b.v) => lcb ** (delta::N) * a
  a.v = b.v =>
    r: D := pseudoRemainder(a.ts,b.ts)$D
    ground?(r) => return (ground(r)$D)::Rep
    ([a.v,r]$VPoly)::Rep
  while not zero?(a) and not negative?(test) repeat
    term := monomial(leadingCoefficient(a,b.v),b.v,test::N)
    a := lcb * a - term * b
    delta := delta - 1$Z
    test := degree(a,b.v)::Z - db
  lcb ** (delta::N) * a

pquo (a:$, b:$)  : $ ==
  cPS := lazyPseudoDivide (a,b)
  c := (cPS.coef) ** (cPS.gap)
  c * cPS.quotient

pseudoDivide(a:$, b:$): Record (quotient : $, remainder : $) ==
  -- from RPOLCAT
  cPS := lazyPseudoDivide(a,b)
  c := (cPS.coef) ** (cPS.gap)
  [c * cPS.quotient, c * cPS.remainder]

lazyPrem(a:$, b:$): $ ==
  -- with lazyPseudoRemainder$NSUP
  -- Uses leadingCoefficient: ($, V) -> $
  b case R =>
    error "in lazyPrem$NSMP: ground? #2"
  (a case R) or (a.v < b.v) =>  a
  a.v = b.v => PSimp(lazyPseudoRemainder(a.ts,b.ts)$D,a.v)
  db: N := degree(b.ts)$D
  lcb: $ := leadingCoefficient(b.ts)$D
  test: Z := degree(a,b.v)::Z - db
  while not zero?(a) and not negative?(test) repeat
    term := monomial(leadingCoefficient(a,b.v),b.v,test::N)
    a := lcb * a - term * b
    test := degree(a,b.v)::Z - db
  a

lazyPquo (a:$, b:$) : $ ==
  -- with lazyPseudoQuotient$NSUP
```

```
    b case R =>
      error " in lazyPquo$NSMP: #2 is conctant"
    (a case R) or (a.v < b.v) => 0
    a.v = b.v => PSimp(lazyPseudoQuotient(a.ts,b.ts)$D,a.v)
    db: N := degree(b.ts)$D
    lcb: $ := leadingCoefficient(b.ts)$D
    test: Z := degree(a,b.v)::Z - db
    q := 0$$
    test: Z := degree(a,b.v)::Z - db
    while not zero?(a) and not negative?(test) repeat
      term := monomial(leadingCoefficient(a,b.v),b.v,test::N)
      a := lcb * a - term * b
      q := lcb * q + term
      test := degree(a,b.v)::Z - db
    q

  lazyPseudoDivide(a:$, b:$): Record(coef:$, gap: N,quotient:$, remainder:$) ==
    -- with lazyPseudoDivide$NSUP
    b case R =>
      error " in lazyPseudoDivide$NSMP: #2 is conctant"
    (a case R) or (a.v < b.v) => [1$$,0$N,0$$,a]
    a.v = b.v =>
      cgqr := lazyPseudoDivide(a.ts,b.ts)
      [cgqr.coef, cgqr.gap, PSimp(cgqr.quotient,a.v), PSimp(cgqr.remainder,a.v)]
    db: N := degree(b.ts)$D
    lcb: $ := leadingCoefficient(b.ts)$D
    test: Z := degree(a,b.v)::Z - db
    q := 0$$
    delta: Z := max(test + 1$Z, 0$Z)
    while not zero?(a) and not negative?(test) repeat
      term := monomial(leadingCoefficient(a,b.v),b.v,test::N)
      a := lcb * a - term * b
      q := lcb * q + term
      delta := delta - 1$Z
      test := degree(a,b.v)::Z - db
    [lcb, (delta::N), q, a]

  lazyResidueClass(a:$, b:$): Record(polnum:$, polden:$, power:N) ==
    -- with lazyResidueClass$NSUP
    b case R =>
      error " in lazyResidueClass$NSMP: #2 is conctant"
    lcb: $ := leadingCoefficient(b.ts)$D
    (a case R) or (a.v < b.v) => [a,lcb,0]
    a.v = b.v =>
      lrc := lazyResidueClass(a.ts,b.ts)$D
      [PSimp(lrc.polnum,a.v), lrc.polden, lrc.power]
    db: N := degree(b.ts)$D
    test: Z := degree(a,b.v)::Z - db
    pow: N := 0
    while not zero?(a) and not negative?(test) repeat
```

```
        term := monomial(leadingCoefficient(a,b.v),b.v,test::N)
        a := lcb * a - term * b
        pow := pow + 1
        test := degree(a,b.v)::Z - db
      [a, lcb, pow]

    if R has IntegralDomain
    then

      packD := PseudoRemainderSequence($,D)

      exactQuo(x:$, y:$):$ ==
        ex: Union($,"failed") := x exquo$$ y
        (ex case $) => ex::$
        error "in exactQuotient$NSMP: bad args"

      LazardQuotient(x:$, y:$, n: N):$ ==
        zero?(n) => error("LazardQuotient$NSMP : n = 0")
--        one?(n) => x
        (n = 1) => x
        a: N := 1
        while n >= (b := 2*a) repeat a := b
        c: $ := x
        n := (n - a)::N
        repeat
--          one?(a) => return c
          (a = 1) => return c
          a := a quo 2
          c := exactQuo(c*c,y)
          if n >= a then ( c := exactQuo(c*x,y) ; n := (n - a)::N )

      LazardQuotient2(p:$, a:$, b:$, n: N) ==
        zero?(n) => error " in LazardQuotient2$NSMP: bad #4"
--        one?(n) => p
        (n = 1) => p
        c: $  := LazardQuotient(a,b,(n-1)::N)
        exactQuo(c*p,b)

      next_subResultant2(p:$, q:$, z:$, s:$) ==
        PSimp(next_sousResultant2(p.ts,q.ts,z.ts,s)$packD,p.v)

      subResultantGcd(a:$, b:$): $ ==
        (a case R) or (b case R) =>
          error "subResultantGcd$NSMP: one arg is constant"
        a.v ~= b.v =>
          error "subResultantGcd$NSMP: mvar(#1) ~= mvar(#2)"
        PSimp(subResultantGcd(a.ts,b.ts),a.v)

      halfExtendedSubResultantGcd1(a:$,b:$): Record (gcd: $, coef1: $) ==
        (a case R) or (b case R) =>
```

```
      error "halfExtendedSubResultantGcd1$NSMP: one arg is constant"
    a.v ~= b.v =>
      error "halfExtendedSubResultantGcd1$NSMP: mvar(#1) ~= mvar(#2)"
    hesrg := halfExtendedSubResultantGcd1(a.ts,b.ts)$D
    [PSimp(hesrg.gcd,a.v), PSimp(hesrg.coef1,a.v)]

  halfExtendedSubResultantGcd2(a:$,b:$): Record (gcd: $, coef2: $) ==
    (a case R) or (b case R) =>
      error "halfExtendedSubResultantGcd2$NSMP: one arg is constant"
    a.v ~= b.v =>
      error "halfExtendedSubResultantGcd2$NSMP: mvar(#1) ~= mvar(#2)"
    hesrg := halfExtendedSubResultantGcd2(a.ts,b.ts)$D
    [PSimp(hesrg.gcd,a.v), PSimp(hesrg.coef2,a.v)]

  extendedSubResultantGcd(a:$,b:$): Record (gcd: $, coef1: $, coef2: $) ==
    (a case R) or (b case R) =>
      error "extendedSubResultantGcd$NSMP: one arg is constant"
    a.v ~= b.v =>
      error "extendedSubResultantGcd$NSMP: mvar(#1) ~= mvar(#2)"
    esrg := extendedSubResultantGcd(a.ts,b.ts)$D
    [PSimp(esrg.gcd,a.v),PSimp(esrg.coef1,a.v),PSimp(esrg.coef2,a.v)]

  resultant(a:$, b:$): $ ==
    (a case R) or (b case R) =>
      error "resultant$NSMP: one arg is constant"
    a.v ~= b.v =>
      error "resultant$NSMP: mvar(#1) ~= mvar(#2)"
    resultant(a.ts,b.ts)$D

  subResultantChain(a:$, b:$): List $ ==
    (a case R) or (b case R) =>
      error "subResultantChain$NSMP: one arg is constant"
    a.v ~= b.v =>
      error "subResultantChain$NSMP: mvar(#1) ~= mvar(#2)"
    [PSimp(up,a.v) for up in subResultantsChain(a.ts,b.ts)]

  lastSubResultant(a:$, b:$): $ ==
    (a case R) or (b case R) =>
      error "lastSubResultant$NSMP: one arg is constant"
    a.v ~= b.v =>
      error "lastSubResultant$NSMP: mvar(#1) ~= mvar(#2)"
    PSimp(lastSubResultant(a.ts,b.ts),a.v)

  if R has EuclideanDomain
  then

    exactQuotient (a:$,b:R) ==
--        one? b => a
      (b = 1) => a
      a case R => (a::R quo$R b)::$
```

```
          ([a.v, map((a1:%):% +-> exactQuotient(a1,b),a.ts)$SUP2]$VPoly)::Rep

        exactQuotient! (a:$,b:R) ==
--          one? b => a
          (b = 1) => a
          a case R => (a::R quo$R b)::$
          a.ts := map((a1:%):% +-> exactQuotient!(a1,b),a.ts)$SUP2
          a

      else

        exactQuotient (a:$,b:R) ==
--          one? b => a
          (b = 1) => a
          a case R => ((a::R exquo$R b)::R)::$
          ([a.v, map((a1:%):% +-> exactQuotient(a1,b),a.ts)$SUP2]$VPoly)::Rep

        exactQuotient! (a:$,b:R) ==
--          one? b => a
          (b = 1) => a
          a case R => ((a::R exquo$R b)::R)::$
          a.ts := map((a1:%):% +-> exactQuotient!(a1,b),a.ts)$SUP2
          a

    if R has GcdDomain
    then

      localGcd(r:R,p:$):R ==
        p case R => gcd(r,p::R)$R
        gcd(r,content(p))$R

      gcd(r:R,p:$):R ==
--        one? r => r
        (r = 1) => r
        zero? p => r
        localGcd(r,p)

      content p ==
        p case R => p
        up : D := p.ts
        r := 0$R
--        while (not zero? up) and (not one? r) repeat
        while (not zero? up) and (not (r = 1)) repeat
          r := localGcd(r,leadingCoefficient(up))
          up := reductum up
        r

      primitivePart! p ==
        zero? p => p
        p case R => 1$$
```

```
        cp := content(p)
        p.ts :=
          unitCanonical(map((a1:%):% +-> exactQuotient!(a1,cp),p.ts)$SUP2)$D
        p
```

———-

— **NSMP.dotabb** —

```
"NSMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NSMP"]
"RPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RPOLCAT"]
"NSMP" -> "RPOLCAT"
```

———-

15.3 domain NSUP NewSparseUnivariatePolynomial

Based on the **PseudoRemainderSequence** package, the domain constructor **NewSparseUnivariatePolynomial** extends the constructur **SparseUnivariatePolynomial**.

— **NewSparseUnivariatePolynomial.input** —

```
)set break resume
)sys rm -f NewSparseUnivariatePolynomial.output
)spool NewSparseUnivariatePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NewSparseUnivariatePolynomial
--R
--R NewSparseUnivariatePolynomial(R: Ring)  is a domain constructor
--R Abbreviation for NewSparseUnivariatePolynomial is NSUP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for NSUP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> %
```

```
--R D : (%,NonNegativeInteger) -> %       1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coefficients : % -> List(R)           coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      differentiate : % -> %
--R ?.? : (%,%) -> %                      ?.? : (%,R) -> R
--R eval : (%,%,%) -> %                   eval : (%,Equation(%)) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             init : () -> % if R has STEP
--R latex : % -> String                   lazyPseudoQuotient : (%,%) -> %
--R leadingCoefficient : % -> R           leadingMonomial : % -> %
--R map : ((R -> R),%) -> %               monicModulo : (%,%) -> %
--R monomial? : % -> Boolean              monomials : % -> List(%)
--R one? : % -> Boolean                   pseudoRemainder : (%,%) -> %
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R retract : % -> R                      sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R D : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R D : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R D : (%,List(SingletonAsOrderedSet)) -> %
--R D : (%,SingletonAsOrderedSet) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R coefficient : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : SparseUnivariatePolynomial(R) -> %
--R coerce : % -> SparseUnivariatePolynomial(R)
--R coerce : SingletonAsOrderedSet -> %
--R composite : (Fraction(%),%) -> Union(Fraction(%),"failed") if R has INTDOM
--R composite : (%,%) -> Union(%,"failed") if R has INTDOM
```

```
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SingletonAsOrderedSet has KONVERT(INFORM) and R has KONVERT(INFO
--R convert : % -> Pattern(Integer) if SingletonAsOrderedSet has KONVERT(PATTERN(INT)) and R has
--R convert : % -> Pattern(Float) if SingletonAsOrderedSet has KONVERT(PATTERN(FLOAT)) and R has
--R degree : (%,List(SingletonAsOrderedSet)) -> List(NonNegativeInteger)
--R degree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R differentiate : (%,(R -> R),%) -> %
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> %
--R differentiate : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R differentiate : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R differentiate : (%,List(SingletonAsOrderedSet)) -> %
--R differentiate : (%,SingletonAsOrderedSet) -> %
--R discriminant : % -> R if R has COMRING
--R discriminant : (%,SingletonAsOrderedSet) -> % if R has COMRING
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R divideExponents : (%,NonNegativeInteger) -> Union(%,"failed")
--R ?.? : (%,Fraction(%)) -> Fraction(%) if R has INTDOM
--R elt : (Fraction(%),R) -> R if R has FIELD
--R elt : (Fraction(%),Fraction(%)) -> Fraction(%) if R has INTDOM
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R eval : (%,List(SingletonAsOrderedSet),List(%)) -> %
--R eval : (%,SingletonAsOrderedSet,%) -> %
--R eval : (%,List(SingletonAsOrderedSet),List(R)) -> %
--R eval : (%,SingletonAsOrderedSet,R) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R extendedResultant : (%,%) -> Record(resultant: R,coef1: %,coef2: %) if R has INTDOM
--R extendedSubResultantGcd : (%,%) -> Record(gcd: %,coef1: %,coef2: %) if R has INTDOM
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R fmecg : (%,NonNegativeInteger,R,%) -> %
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R halfExtendedResultant1 : (%,%) -> Record(resultant: R,coef1: %) if R has INTDOM
--R halfExtendedResultant2 : (%,%) -> Record(resultant: R,coef2: %) if R has INTDOM
```

```
--R halfExtendedSubResultantGcd1 : (%,%) -> Record(gcd: %,coef1: %) if R has INTDOM
--R halfExtendedSubResultantGcd2 : (%,%) -> Record(gcd: %,coef2: %) if R has INTDOM
--R integrate : % -> % if R has ALGEBRA(FRAC(INT))
--R isExpt : % -> Union(Record(var: SingletonAsOrderedSet,exponent: NonNegativeInteger),"failed")
--R isPlus : % -> Union(List(%),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R karatsubaDivide : (%,NonNegativeInteger) -> Record(quotient: %,remainder: %)
--R lastSubResultant : (%,%) -> % if R has INTDOM
--R lazyPseudoDivide : (%,%) -> Record(coef: R,gap: NonNegativeInteger,quotient: %,remainder: %)
--R lazyPseudoRemainder : (%,%) -> %
--R lazyResidueClass : (%,%) -> Record(polnum: %,polden: R,power: NonNegativeInteger)
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R mainVariable : % -> Union(SingletonAsOrderedSet,"failed")
--R makeSUP : % -> SparseUnivariatePolynomial(R)
--R mapExponents : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List(SingletonAsOrderedSet)) -> List(NonNegativeInteger)
--R minimumDegree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R minimumDegree : % -> NonNegativeInteger
--R monicDivide : (%,%) -> Record(quotient: %,remainder: %)
--R monicDivide : (%,%,SingletonAsOrderedSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (R,NonNegativeInteger) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R multiplyExponents : (%,NonNegativeInteger) -> %
--R multivariate : (SparseUnivariatePolynomial(%),SingletonAsOrderedSet) -> %
--R multivariate : (SparseUnivariatePolynomial(R),SingletonAsOrderedSet) -> %
--R nextItem : % -> Union(%,"failed") if R has STEP
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,%) -> NonNegativeInteger if R has INTDOM
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if S
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if Singlet
--R pomopo! : (%,R,NonNegativeInteger,%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if R has FIELD
--R pseudoDivide : (%,%) -> Record(coef: R,quotient: %,remainder: %) if R has INTDOM
--R pseudoQuotient : (%,%) -> % if R has INTDOM
--R ?quo? : (%,%) -> % if R has FIELD
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LIN
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R ?rem? : (%,%) -> % if R has FIELD
--R resultant : (%,%) -> R if R has COMRING
```

```
--R resultant : (%,%,SingletonAsOrderedSet) -> % if R has COMRING
--R retract : % -> SparseUnivariatePolynomial(R)
--R retract : % -> SingletonAsOrderedSet
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(SparseUnivariatePolynomial(R),"failed")
--R retractIfCan : % -> Union(SingletonAsOrderedSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R separate : (%,%) -> Record(primePart: %,commonPart: %) if R has GCDDOM
--R shiftLeft : (%,NonNegativeInteger) -> %
--R shiftRight : (%,NonNegativeInteger) -> %
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynom
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(
--R subResultantGcd : (%,%) -> % if R has INTDOM
--R subResultantsChain : (%,%) -> List(%) if R has INTDOM
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List(SingletonAsOrderedSet)) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,SingletonAsOrderedSet) -> SparseUnivariatePolynomial(%)
--R unmakeSUP : SparseUnivariatePolynomial(R) -> %
--R variables : % -> List(SingletonAsOrderedSet)
--R vectorise : (%,NonNegativeInteger) -> Vector(R)
--R
--E 1

)spool
)lisp (bye)
```

———-


— NewSparseUnivariatePolynomial.help —

```
=====================================================================
NewSparseUnivariatePolynomial examples
=====================================================================

See Also:
o )show NewSparseUnivariatePolynomial
```

———-

15.3.1 NewSparseUnivariatePolynomial (NSUP)



See

⇒ “NewSparseMultivariatePolynomial” (NSMP) 15.2.1 on page 1680

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
composite	conditionP	content
convert	D	degree
differentiate	discriminant	divide
divideExponents	elt	euclideanSize
eval	expressIdealMember	exquo
extendedEuclidean	extendedResultant	extendedSubResultantGcd
factor	factorPolynomial	factorSquareFreePolynomial
fmecg	gcd	gcdPolynomial
ground	ground?	halfExtendedResultant1
halfExtendedResultant2	halfExtendedSubResultantGcd1	halfExtendedSubResultantGcd2
hash	init	integrate
isExpt	isPlus	isTimes
karatsubaDivide	lastSubResultant	latex
lazyPseudoDivide	lazyPseudoQuotient	lazyPseudoRemainder
lazyResidueClass	lcm	leadingCoefficient
leadingMonomial	mainVariable	makeSUP
map	mapExponents	max
min	minimumDegree	monicDivide
monicModulo	monomial	monomial?
monomials	multiEuclidean	multiplyExponents
multivariate	nextItem	numberOfMonomials
one?	order	patternMatch
pomopo!	prime?	primitiveMonomials
primitivePart	principalIdeal	pseudoDivide
pseudoQuotient	pseudoRemainder	recip
reducedSystem	reductum	resultant
retract	retractIfCan	sample
separate	shiftLeft	shiftRight
sizeLess?	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subResultantGcd
subResultantsChain	subtractIfCan	totalDegree
totalDegree	unit?	unitCanonical
unitNormal	univariate	unmakeSUP
variables	vectorise	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?.?	?~=?
?/?	?<?	?<=?
?>?	?>=?	?quo?
?rem?		

— domain NSUP NewSparseUnivariatePolynomial —

```
)abbrev domain NSUP NewSparseUnivariatePolynomial
++ Author: Marc Moreno Maza
++ Date Created: 23/07/98
++ Date Last Updated: 14/12/98
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A post-facto extension for \axiomType{SUP} in order
++ to speed up operations related to pseudo-division and gcd for
++ both \axiomType{SUP} and, consequently, \axiomType{NSMP}.

NewSparseUnivariatePolynomial(R): Exports == Implementation where

  R:Ring
  NNI ==> NonNegativeInteger
  SUPR ==> SparseUnivariatePolynomial R

  Exports == Join(UnivariatePolynomialCategory(R),
   CoercibleTo(SUPR),RetractableTo(SUPR)) with
     fmecg : (%,NNI,R,%) -> %
        ++ \axiom{fmecg(p1,e,r,p2)} returns \axiom{p1 - r * x**e * p2}
        ++ where \axiom{x} is \axiom{monomial(1,1)}
     monicModulo : ($, $) -> $
        ++ \axiom{monicModulo(a,b)} returns \axiom{r} such that \axiom{r} is
        ++ reduced w.r.t. \axiom{b} and \axiom{b} divides \axiom{a -r}
        ++ where \axiom{b} is monic.
     lazyResidueClass: ($,$) -> Record(polnum:$, polden:R, power:NNI)
        ++ \axiom{lazyResidueClass(a,b)} returns \axiom{[r,c,n]} such that
        ++ \axiom{r} is reduced w.r.t. \axiom{b} and \axiom{b} divides
        ++ \axiom{c^n * a - r} where \axiom{c} is \axiom{leadingCoefficient(b)}
        ++ and \axiom{n} is as small as possible with the previous properties.
     lazyPseudoRemainder: ($,$) -> $
        ++ \axiom{lazyPseudoRemainder(a,b)} returns \axiom{r} if
        ++ \axiom{lazyResidueClass(a,b)} returns \axiom{[r,c,n]}.
        ++ This lazy pseudo-remainder is computed by means of the
        ++ fmecg from NewSparseUnivariatePolynomial operation.
     lazyPseudoDivide: ($,$) -> Record(coef:R,gap:NNI,quotient:$,remainder:$)
        ++ \axiom{lazyPseudoDivide(a,b)} returns \axiom{[c,g,q,r]} such that
        ++ \axiom{c^n * a = q*b +r} and \axiom{lazyResidueClass(a,b)} returns
        ++ \axiom{[r,c,n]} where
        ++ \axiom{n + g = max(0, degree(b) - degree(a) + 1)}.
     lazyPseudoQuotient: ($,$) -> $
        ++ \axiom{lazyPseudoQuotient(a,b)} returns \axiom{q} if
        ++ \axiom{lazyPseudoDivide(a,b)} returns \axiom{[c,g,q,r]}
     if R has IntegralDomain
```

```
    then
      subResultantsChain: ($, $) -> List $
        ++ \axiom{subResultantsChain(a,b)} returns the list of the non-zero
        ++ sub-resultants of \axiom{a} and \axiom{b} sorted by increasing
        ++ degree.
      lastSubResultant: ($, $) -> $
        ++ \axiom{lastSubResultant(a,b)} returns \axiom{resultant(a,b)}
        ++ if \axiom{a} and \axiom{b} has no non-trivial gcd
        ++ in \axiom{R^(-1) P}
        ++ otherwise the non-zero sub-resultant with smallest index.
      extendedSubResultantGcd: ($, $) -> Record(gcd: $, coef1: $, coef2: $)
        ++ \axiom{extendedSubResultantGcd(a,b)} returns \axiom{[g,ca, cb]}
        ++ such that \axiom{g} is a gcd of \axiom{a} and \axiom{b} in
        ++ \axiom{R^(-1) P} and \axiom{g = ca * a + cb * b}
      halfExtendedSubResultantGcd1: ($, $) -> Record(gcd: $, coef1: $)
        ++ \axiom{halfExtendedSubResultantGcd1(a,b)} returns \axiom{[g,ca]}
        ++ such that \axiom{extendedSubResultantGcd(a,b)} returns
        ++ \axiom{[g,ca, cb]}
      halfExtendedSubResultantGcd2: ($, $) -> Record(gcd: $, coef2: $)
        ++ \axiom{halfExtendedSubResultantGcd2(a,b)} returns \axiom{[g,cb]}
        ++ such that \axiom{extendedSubResultantGcd(a,b)} returns
        ++ \axiom{[g,ca, cb]}
      extendedResultant: ($, $) -> Record(resultant: R, coef1: $, coef2: $)
        ++ \axiom{extendedResultant(a,b)} returns  \axiom{[r,ca,cb]} such that
        ++ \axiom{r} is the resultant of \axiom{a} and \axiom{b} and
        ++ \axiom{r = ca * a + cb * b}
      halfExtendedResultant1: ($, $) -> Record(resultant: R, coef1: $)
        ++ \axiom{halfExtendedResultant1(a,b)} returns \axiom{[r,ca]}
        ++ such that \axiom{extendedResultant(a,b)}  returns
        ++ \axiom{[r,ca, cb]}
      halfExtendedResultant2: ($, $) -> Record(resultant: R, coef2: $)
        ++ \axiom{halfExtendedResultant2(a,b)} returns \axiom{[r,ca]} such
        ++ that \axiom{extendedResultant(a,b)} returns \axiom{[r,ca, cb]}

  Implementation == SparseUnivariatePolynomial(R) add

    Term == Record(k:NonNegativeInteger,c:R)
    Rep ==> List Term

    rep(s:$):Rep == s pretend Rep
    per(l:Rep):$ == l pretend $

    coerce (p:$):SUPR ==
      p pretend SUPR

    coerce (p:SUPR):$ ==
      p pretend $

    retractIfCan (p:$) : Union(SUPR,"failed") ==
      (p pretend SUPR)::Union(SUPR,"failed")
```

```
    monicModulo(x,y) ==
                zero? y =>
                   error "in monicModulo$NSUP: division by 0"
                ground? y =>
                   error "in monicModulo$NSUP: ground? #2"
                yy := rep y
--                not one? (yy.first.c) =>
                not ((yy.first.c) = 1) =>
                   error "in monicModulo$NSUP: not monic #2"
                xx := rep x; empty? xx => x
                e := yy.first.k; y := per(yy.rest)
                -- while (not empty? xx) repeat
                repeat
                  if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
                  xx:= rep fmecg(per rest(xx), u, xx.first.c, y)
                  if empty? xx then break
                per xx

    lazyResidueClass(x,y) ==
                zero? y =>
                   error "in lazyResidueClass$NSUP: division by 0"
                ground? y =>
                   error "in lazyResidueClass$NSUP: ground? #2"
                yy := rep y; co := yy.first.c; xx: Rep := rep x
                empty? xx => [x, co, 0]
                pow: NNI := 0; e := yy.first.k; y := per(yy.rest);
                repeat
                  if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
                  xx:= rep fmecg(co * per rest(xx), u, xx.first.c, y)
                  pow := pow + 1
                  if empty? xx then break
                [per xx, co, pow]

    lazyPseudoRemainder(x,y) ==
                zero? y =>
                   error "in lazyPseudoRemainder$NSUP: division by 0"
                ground? y =>
                   error "in lazyPseudoRemainder$NSUP: ground? #2"
                ground? x => x
                yy := rep y; co := yy.first.c
--                one? co => monicModulo(x,y)
                (co = 1) => monicModulo(x,y)
                (co = -1) => - monicModulo(-x,-y)
                xx:= rep x; e := yy.first.k; y := per(yy.rest)
                repeat
                  if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
                  xx:= rep fmecg(co * per rest(xx), u, xx.first.c, y)
                  if empty? xx then break
                per xx
```

```
lazyPseudoDivide(x,y) ==
           zero? y =>
              error "in lazyPseudoDivide$NSUP: division by 0"
           ground? y =>
              error "in lazyPseudoDivide$NSUP: ground? #2"
           yy := rep y; e := yy.first.k;
           xx: Rep := rep x; co := yy.first.c
           (empty? xx) or (xx.first.k < e) => [co,0,0,x]
           pow: NNI := subtractIfCan(xx.first.k,e)::NNI + 1
           qq: Rep := []; y := per(yy.rest)
           repeat
             if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
             qq := cons([u::NNI, xx.first.c]$Term, rep (co * per qq))
             xx := rep fmecg(co * per rest(xx), u, xx.first.c, y)
             pow := subtractIfCan(pow,1)::NNI
             if empty? xx then break
           [co, pow, per reverse qq, per xx]

lazyPseudoQuotient(x,y) ==
           zero? y =>
              error "in lazyPseudoQuotient$NSUP: division by 0"
           ground? y =>
              error "in lazyPseudoQuotient$NSUP: ground? #2"
           yy := rep y; e := yy.first.k; xx: Rep := rep x
           (empty? xx) or (xx.first.k < e) => 0
           qq: Rep := []; co := yy.first.c; y := per(yy.rest)
           repeat
             if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
             qq := cons([u::NNI, xx.first.c]$Term, rep (co * per qq))
             xx := rep fmecg(co * per rest(xx), u, xx.first.c, y)
             if empty? xx then break
           per reverse qq

if R has IntegralDomain
then
  pack ==> PseudoRemainderSequence(R, %)

  subResultantGcd(p1,p2) == subResultantGcd(p1,p2)$pack

  subResultantsChain(p1,p2) == chainSubResultants(p1,p2)$pack

  lastSubResultant(p1,p2) == lastSubResultant(p1,p2)$pack

  resultant(p1,p2) == resultant(p1,p2)$pack

  extendedResultant(p1,p2) ==
     re: Record(coef1: $, coef2: $, resultant: R) := resultantEuclidean(p1,p2)$pack
     [re.resultant, re.coef1, re.coef2]
```

```
halfExtendedResultant1(p1:$, p2: $): Record(resultant: R, coef1: $) ==
   re: Record(coef1: $, resultant: R) := semiResultantEuclidean1(p1, p2)$pack
   [re.resultant, re.coef1]

halfExtendedResultant2(p1:$, p2: $): Record(resultant: R, coef2: $) ==
   re: Record(coef2: $, resultant: R) := semiResultantEuclidean2(p1, p2)$pack
   [re.resultant, re.coef2]

extendedSubResultantGcd(p1,p2) ==
   re: Record(coef1: $, coef2: $, gcd: $) := subResultantGcdEuclidean(p1,p2)$pack
   [re.gcd, re.coef1, re.coef2]

halfExtendedSubResultantGcd1(p1:$, p2: $): Record(gcd: $, coef1: $) ==
   re: Record(coef1: $, gcd: $) := semiSubResultantGcdEuclidean1(p1, p2)$pack
   [re.gcd, re.coef1]

halfExtendedSubResultantGcd2(p1:$, p2: $): Record(gcd: $, coef2: $) ==
   re: Record(coef2: $, gcd: $) := semiSubResultantGcdEuclidean2(p1, p2)$pack
   [re.gcd, re.coef2]

pseudoDivide(x,y) ==
         zero? y =>
            error "in pseudoDivide$NSUP: division by 0"
         ground? y =>
            error "in pseudoDivide$NSUP: ground? #2"
         yy := rep y; e := yy.first.k
         xx: Rep := rep x; co := yy.first.c
         (empty? xx) or (xx.first.k < e) => [co,0,x]
         pow: NNI := subtractIfCan(xx.first.k,e)::NNI + 1
         qq: Rep := []; y := per(yy.rest)
         repeat
           if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
           qq := cons([u::NNI, xx.first.c]$Term, rep (co * per qq))
           xx := rep fmecg(co * per rest(xx), u, xx.first.c, y)
           pow := subtractIfCan(pow,1)::NNI
           if empty? xx then break
         zero? pow => [co, per reverse qq, per xx]
         default: R := co ** pow
         q := default * (per reverse qq)
         x := default * (per xx)
         [co, q, x]

pseudoQuotient(x,y) ==
         zero? y =>
            error "in pseudoDivide$NSUP: division by 0"
         ground? y =>
            error "in pseudoDivide$NSUP: ground? #2"
         yy := rep y; e := yy.first.k; xx: Rep := rep x
         (empty? xx) or (xx.first.k < e) => 0
         pow: NNI := subtractIfCan(xx.first.k,e)::NNI + 1
```

```
            qq: Rep := []; co := yy.first.c; y := per(yy.rest)
            repeat
              if (u:=subtractIfCan(xx.first.k,e)) case "failed" then break
              qq := cons([u::NNI, xx.first.c]$Term, rep (co * per qq))
              xx := rep fmecg(co * per rest(xx), u, xx.first.c, y)
              pow := subtractIfCan(pow,1)::NNI
              if empty? xx then break
            zero? pow => per reverse qq
            (co ** pow) * (per reverse qq)
```

———-

— **NSUP.dotabb** —

```
"NSUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NSUP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"NSUP" -> "PFECAT"
```

———-

15.4 domain NONE None

— **None.input** —

```
)set break resume
)sys rm -f None.output
)spool None.output
)set message test on
)set message auto off
)clear all
--S 1 of 3
[ ]
--R
--R
--R   (1)  []
--R                                                    Type: List(None)
--E 1

--S 2 of 3
[ ] :: List Float
--R
--R
--R   (2)  []
--R                                                   Type: List(Float)
```

```
--E 2

--S 3 of 3
[ ]$List(NonNegativeInteger)
--R
--R
--R   (3)  []
--R                                                Type: List(NonNegativeInteger)
--E 3
)spool
)lisp (bye)
```

———-

— None.help —

```
====================================================================
None examples
====================================================================

The None domain is not very useful for interactive work but it is
provided nevertheless for completeness of the Axiom type system.

Probably the only place you will ever see it is if you enter an
empty list with no type information.

  [ ]
    []
                        Type: List None

Such an empty list can be converted into an empty list of any other
type.

  [ ] :: List Float
    []
                        Type: List Float


If you wish to produce an empty list of a particular type directly,
such as List NonNegativeInteger, do it this way.

  [ ]$List(NonNegativeInteger)
    []
                        Type: List NonNegativeInteger

See Also:
o )show None
```

———-

15.4.1 None (NONE)



See

⇒ “Any” (ANY) 2.9.1 on page 50

Exports:
coerce hash latex ?=? ?~=?

— domain NONE None —

```
)abbrev domain NONE None
++ Author: Mark Botch
++ Date Created:
++ Change History:
++ Basic Functions: coerce
++ Related Constructors: NoneFunctions1
++ Also See: Any
++ AMS Classification:
++ Keywords: none, empty
++ Description:
++ \spadtype{None} implements a type with no objects. It is mainly
++ used in technical situations where such a thing is needed (e.g.
++ the interpreter and some of the internal \spadtype{Expression} code).

None():SetCategory == add
    coerce(none:%):OutputForm == "NONE" :: OutputForm
    x:% = y:% == EQ(x,y)$Lisp
```

———-

— NONE.dotabb —

```
"NONE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NONE"]
```

```
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"NONE" -> "BASTYPE"
"NONE" -> "KOERCE"
```

———-

15.5 domain NNI NonNegativeInteger

— NonNegativeInteger.input —

```
)set break resume
)sys rm -f NonNegativeInteger.output
)spool NonNegativeInteger.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NonNegativeInteger
--R NonNegativeInteger  is a domain constructor
--R Abbreviation for NonNegativeInteger is NNI
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for NNI
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coerce : % -> OutputForm              gcd : (%,%) -> %
--R hash : % -> SingleInteger             latex : % -> String
--R max : (%,%) -> %                      min : (%,%) -> %
--R one? : % -> Boolean                   ?quo? : (%,%) -> %
--R random : % -> %                       recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %                    sample : () -> %
--R shift : (%,Integer) -> %              sup : (%,%) -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R exquo : (%,%) -> Union(%,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
```

```
--R
--E 1

)spool
)lisp (bye)
```

———-


— **NonNegativeInteger.help** —

```
==========================================================================
NonNegativeInteger examples
==========================================================================

See Also:
o )show NonNegativeInteger
```

———-

15.5.1 NonNegativeInteger (NNI)



See

⇒ “Integer” (INT) 10.30.1 on page 1329
⇒ “PositiveInteger” (PI) 17.28.1 on page 2066
⇒ “RomanNumeral” (ROMAN) 19.12.1 on page 2292

Exports:

0	1	coerce	divide	exquo
gcd	hash	latex	max	min
one?	random	recip	sample	shift
subtractIfCan	sup	zero?	?~=?	?*?
?**?	?^?	?+?	?<?	?<=?
?=?	?>?	?>=?	?quo?	?rem?

— **domain NNI NonNegativeInteger** —

```
)abbrev domain NNI NonNegativeInteger
++ Author: Mark Botch
++ Date Created:
++ Change History:
++ Basic Operations:
++ Related Constructors:
++ Keywords: integer
++ Description:
++ \spadtype{NonNegativeInteger} provides functions for non-negative integers.

NonNegativeInteger: Join(OrderedAbelianMonoidSup,Monoid) with
            _quo : (%,%) -> %
              ++ a quo b returns the quotient of \spad{a} and b, forgetting
              ++ the remainder.
            _rem : (%,%) -> %
              ++ a rem b returns the remainder of \spad{a} and b.
            gcd  : (%,%) -> %
              ++ gcd(a,b) computes the greatest common divisor of two
              ++ non negative integers \spad{a} and b.
            divide: (%,%) -> Record(quotient:%,remainder:%)
              ++ divide(a,b) returns a record containing both
              ++ remainder and quotient.
            _exquo: (%,%) -> Union(%,"failed")
              ++ exquo(a,b) returns the quotient of \spad{a} and b, or "failed"
              ++ if b is zero or \spad{a} rem b is zero.
            shift: (%, Integer) -> %
              ++ shift(a,i) shift \spad{a} by i bits.
            random   : % -> %
              ++ random(n) returns a random integer from 0 to \spad{n-1}.
            commutative("*")
              ++ commutative("*") means multiplication is commutative,
              ++ that is, \spad{x*y = y*x}.

  == SubDomain(Integer,#1 >= 0) add
      x,y:%
      sup(x,y) == MAX(x,y)$Lisp
      shift(x:%, n:Integer):% == ASH(x,n)$Lisp
      subtractIfCan(x, y) ==
        c:Integer := (x pretend Integer) - (y pretend Integer)
        c < 0 => "failed"
        c pretend %
```

———-

— **NNI.dotabb** —

```
"NNI" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NNI",shape=ellipse]
"OAMONS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAMONS"]
```

```
"NNI" -> "OAMONS"
```

———-

15.6 domain NOTTING NottinghamGroup

— **NottinghamGroup.input** —

```
)set break resume
)sys rm -f NottinghamGroup.output
)spool NottinghamGroup.output
)set message test on
)set message auto off
)clear all

--S 1 of 8
x:=monomial(1,1)$UFPS PF 1783
--R
--R
--R   (1)  x
--R                          Type: UnivariateFormalPowerSeries(PrimeField(1783))
--E 1

--S 2 of 8
s:=retract(sin x)$NOTTING PF 1783
--R
--R
--R                3        5       7       9      11
--R   (2)  x + 297x  + 1679x  + 427x  + 316x  + O(x  )
--R                                     Type: NottinghamGroup(PrimeField(1783))
--E 2

--S 3 of 8
s^2
--R
--R
--R                3       5        7        9      11
--R   (3)  x + 594x  + 535x  + 1166x  + 1379x  + O(x  )
--R                                     Type: NottinghamGroup(PrimeField(1783))
--E 3

--S 4 of 8
s^-1
--R
--R
--R                 3       5       7        9      11
```

```
--R   (4)  x + 1486x  + 847x  + 207x  + 1701x  + O(x  )
--R                                       Type: NottinghamGroup(PrimeField(1783))
--E 4

--S 5 of 8
s^-1*s
--R
--R
--R               11
--R   (5)  x + O(x  )
--R                                       Type: NottinghamGroup(PrimeField(1783))
--E 5

--S 6 of 8
s*s^-1
--R
--R
--R               11
--R   (6)  x + O(x  )
--R                                       Type: NottinghamGroup(PrimeField(1783))
--E 6

--S 7 of 8
sample()$NOTTING(PF(1783))
--R
--R   (7)  x
--R                                       Type: NottinghamGroup(PrimeField(1783))
--E 7

--S 8 of 8
)show NottinghamGroup
--R
--R NottinghamGroup(F: FiniteFieldCategory)  is a domain constructor
--R Abbreviation for NottinghamGroup is NOTTING
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for NOTTING
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R coerce : % -> OutputForm              commutator : (%,%) -> %
--R conjugate : (%,%) -> %                hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R sample : () -> %                      ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R retract : UnivariateFormalPowerSeries(F) -> %
```

```
--R
--E 8

)spool
)lisp (bye)
```

———-

— NottinghamGroup.help —

```
=====================================================================
NottinghamGroup examples
=====================================================================
                              n
If F is a finite field with p  elements, then we may form the group
of all formal power series {t(1+a t+a t+...)} where u(0)=0 and
 ,                                1   2
u (0)=1 and $a is an element of F.
            i
The group operation is substitution (composition).
This is called the Nottingham Group.

The Nottingham Group is the projective limit of finite p-groups.
Every finite p-group can be embedded in the Nottingham Group.

   x:=monomial(1,1)$UFPS PF 1783
     x

   s:=retract(sin x)$NOTTING PF 1783
             3        5       7       9      11
     x + 297x  + 1679x  + 427x  + 316x  + O(x  )

   s^2
             3       5        7        9      11
     x + 594x  + 535x  + 1166x  + 1379x  + O(x  )

   s^-1
              3       5       7        9      11
     x + 1486x  + 847x  + 207x  + 1701x  + O(x  )


   s^-1*s
            11
     x + O(x  )

   s*s^-1
               11
        x + O(x  )
```

```
See Also:
o )show NottinghamGroup
o )show UnivariateFormalPowerSeries
```

———-

15.6.1 NottinghamGroup (NOTTING)



Exports:

1	coerce	commutator	conjugate	hash
inv	latex	one?	recip	sample
^=	retract	*	**	/
=	^			

— domain NOTTING NottinghamGroup —

```
)abbrev domain NOTTING NottinghamGroup
++ Author: Mark Botch
++ Description:
++ This is an implmenentation of the Nottingham Group

NottinghamGroup(F:FiniteFieldCategory): Group with
  retract: UnivariateFormalPowerSeries F -> %
 == add
  Rep:=UnivariateFormalPowerSeries F

  coerce f == coerce(f::Rep)$UnivariateFormalPowerSeries(F)

  retract f ==
    if zero? coefficient(f,0) and one? coefficient(f,1)
    then f::Rep
    else error"The leading term must be x"

  1 == monomial(1,1)
```

```
  f*g == f.g

  inv f == revert f
```

———-

— **NOTTING.dotabb** —

```
"NOTTING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NOTTING"]
"UFPS" [color="#4488FF",href="bookvol10.3.pdf#nameddest=UFPS"]
"NOTTING" -> "UFPS"
```

———-

15.7 domain NIPROB NumericalIntegrationProblem

— **NumericalIntegrationProblem.input** —

```
)set break resume
)sys rm -f NumericalIntegrationProblem.output
)spool NumericalIntegrationProblem.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NumericalIntegrationProblem
--R
--R NumericalIntegrationProblem  is a domain constructor
--R Abbreviation for NumericalIntegrationProblem is NIPROB
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for NIPROB
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R coerce : Union(nia: Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCom
--R coerce : Record(fn: Expression(DoubleFloat),range: List(Segment(OrderedCompletion(DoubleFloa
--R coerce : Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(OrderedCompletion(Dou
--R retract : % -> Union(nia: Record(var: Symbol,fn: Expression(DoubleFloat),range: Segment(Orde
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **NumericalIntegrationProblem.help** —

```
=====================================================================
NumericalIntegrationProblem examples
=====================================================================

See Also:
o )show NumericalIntegrationProblem
```

———-

15.7.1 NumericalIntegrationProblem (NIPROB)



Exports:
coerce hash latex retract ?=? ?~=?

— **domain NIPROB NumericalIntegrationProblem** —

```
)abbrev domain NIPROB NumericalIntegrationProblem
++ Author: Brian Dupee
++ Date Created: December 1997
++ Date Last Updated: December 1997
++ Basic Operations: coerce, retract
++ Related Constructors: Union
++ Description:
++ \axiomType{NumericalIntegrationProblem} is a \axiom{domain}
++ for the representation of Numerical Integration problems for use
```

```
++ by ANNA.
++
++ The representation is a Union of two record types - one for integration of
++ a function of one variable:
++
++ \axiomType{Record}(var:\axiomType{Symbol},\br
++ fn:\axiomType{Expression DoubleFloat},\br
++ range:\axiomType{Segment OrderedCompletion DoubleFloat},\br
++ abserr:\axiomType{DoubleFloat},\br
++ relerr:\axiomType{DoubleFloat},)
++
++ and one for multivariate integration:
++
++ \axiomType{Record}(fn:\axiomType{Expression DoubleFloat},\br
++ range:\axiomType{List Segment OrderedCompletion DoubleFloat},\br
++ abserr:\axiomType{DoubleFloat},\br
++ relerr:\axiomType{DoubleFloat},).
++

NumericalIntegrationProblem(): EE == II where

 EDFA   ==> Expression DoubleFloat
 SOCDFA ==> Segment OrderedCompletion DoubleFloat
 DFA    ==> DoubleFloat
 NIAA   ==> Record(var:Symbol,fn:EDFA,range:SOCDFA,abserr:DFA,relerr:DFA)
 MDNIAA ==> Record(fn:EDFA,range:List SOCDFA,abserr:DFA,relerr:DFA)

 EE ==> SetCategory with
    coerce: NIAA -> %
      ++ coerce(x) is not documented
    coerce: MDNIAA -> %
      ++ coerce(x) is not documented
    coerce: Union(nia:NIAA,mdnia:MDNIAA) -> %
      ++ coerce(x) is not documented
    coerce: % -> OutputForm
      ++ coerce(x) is not documented
    retract: % -> Union(nia:NIAA,mdnia:MDNIAA)
      ++ retract(x) is not documented

 II ==> add
      Rep := Union(nia:NIAA,mdnia:MDNIAA)

      coerce(s:NIAA) == [s]
      coerce(s:MDNIAA) == [s]
      coerce(s:Union(nia:NIAA,mdnia:MDNIAA)) == s
      coerce(x:%):OutputForm ==
        (x) case nia => (x.nia)::OutputForm
        (x.mdnia)::OutputForm
      retract(x:%):Union(nia:NIAA,mdnia:MDNIAA) ==
        (x) case nia => [x.nia]
```

```
        [x.mdnia]
```

———-

— **NIPROB.dotabb** —

```
"NIPROB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NIPROB"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"NIPROB" -> "BASTYPE"
"NIPROB" -> "KOERCE"
```

———-

15.8 domain ODEPROB NumericalODEProblem

— **NumericalODEProblem.input** —

```
)set break resume
)sys rm -f NumericalODEProblem.output
)spool NumericalODEProblem.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NumericalODEProblem
--R
--R NumericalODEProblem  is a domain constructor
--R Abbreviation for NumericalODEProblem is ODEPROB
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ODEPROB
--R
--R------------------------------- Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R coerce : Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)),yinit: List(Dou
--R retract : % -> Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFloat)),yinit: Li
--R
--E 1

)spool
)lisp (bye)
```

———-


— NumericalODEProblem.help —

```
====================================================================
NumericalODEProblem examples
====================================================================

See Also:
o )show NumericalODEProblem
```

———-

15.8.1 NumericalODEProblem (ODEPROB)



Exports:
coerce hash latex retract ?=? ?~=?

— domain ODEPROB NumericalODEProblem —

```
)abbrev domain ODEPROB NumericalODEProblem
++ Author: Brian Dupee
++ Date Created: December 1997
++ Date Last Updated: December 1997
++ Basic Operations: coerce, retract
++ Related Constructors: Union
++ Description:
++ \axiomType{NumericalODEProblem} is a \axiom{domain}
++ for the representation of Numerical ODE problems for use
++ by ANNA.
++
++ The representation is of type:
++
++ \axiomType{Record}(xinit:\axiomType{DoubleFloat},\br
```

```
++ xend:\axiomType{DoubleFloat},\br
++ fn:\axiomType{Vector Expression DoubleFloat},\br
++ yinit:\axiomType{List DoubleFloat},intvals:\axiomType{List DoubleFloat},\br
++ g:\axiomType{Expression DoubleFloat},abserr:\axiomType{DoubleFloat},\br
++ relerr:\axiomType{DoubleFloat})
++

NumericalODEProblem(): EE == II where

 DFB   ==> DoubleFloat
 VEDFB ==> Vector Expression DoubleFloat
 LDFB  ==> List DoubleFloat
 EDFB  ==> Expression DoubleFloat
 ODEAB ==> Record(xinit:DFB,xend:DFB,fn:VEDFB,yinit:LDFB,intvals:LDFB,g:EDFB,abserr:DFB,relerr:DFB)

 EE ==> SetCategory with
    coerce: ODEAB -> %
      ++ coerce(x) is not documented
    coerce: % -> OutputForm
      ++ coerce(x) is not documented
    retract: % -> ODEAB
      ++ retract(x) is not documented

 II ==> add
      Rep := ODEAB

      coerce(s:ODEAB) == s
      coerce(x:%):OutputForm ==
        (retract(x))::OutputForm
      retract(x:%):ODEAB == x :: Rep
```

———-

— ODEPROB.dotabb —

```
"ODEPROB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ODEPROB"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"ODEPROB" -> "BASTYPE"
"ODEPROB" -> "KOERCE"
```

———-

15.9 domain OPTPROB NumericalOptimizationProblem

— NumericalOptimizationProblem.input —

```
)set break resume
)sys rm -f NumericalOptimizationProblem.output
)spool NumericalOptimizationProblem.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NumericalOptimizationProblem
--R
--R NumericalOptimizationProblem  is a domain constructor
--R Abbreviation for NumericalOptimizationProblem is OPTPROB
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OPTPROB
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R coerce : Union(noa: Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(Orde
--R coerce : Record(lfn: List(Expression(DoubleFloat)),init: List(DoubleFloat)) -> %
--R coerce : Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: List(OrderedCompleti
--R retract : % -> Union(noa: Record(fn: Expression(DoubleFloat),init: List(DoubleFloat),lb: Lis
--R
--E 1

)spool
)lisp (bye)
```

———-


— NumericalOptimizationProblem.help —

```
==========================================================================
NumericalOptimizationProblem examples
==========================================================================

See Also:
o )show NumericalOptimizationProblem
```

———-

15.9.1 NumericalOptimizationProblem (OPTPROB)



Exports:
coerce hash latex retract ?=? ?~=?

— domain OPTPROB NumericalOptimizationProblem —

```
)abbrev domain OPTPROB NumericalOptimizationProblem
++ Author: Brian Dupee
++ Date Created: December 1997
++ Date Last Updated: December 1997
++ Basic Operations: coerce, retract
++ Related Constructors: Union
++ Description:
++ \axiomType{NumericalOptimizationProblem} is a \axiom{domain}
++ for the representation of Numerical Optimization problems for use
++ by ANNA.
++
++ The representation is a Union of two record types - one for otimization of
++ a single function of one or more variables:
++
++ \axiomType{Record}(\br
++ fn:\axiomType{Expression DoubleFloat},\br
++ init:\axiomType{List DoubleFloat},\br
++ lb:\axiomType{List OrderedCompletion DoubleFloat},\br
++ cf:\axiomType{List Expression DoubleFloat},\br
++ ub:\axiomType{List OrderedCompletion DoubleFloat})
++
++ and one for least-squares problems i.e. optimization of a set of
++ observations of a data set:
++
++ \axiomType{Record}(lfn:\axiomType{List Expression DoubleFloat},\br
++ init:\axiomType{List DoubleFloat}).

NumericalOptimizationProblem(): EE == II where

 LDFD     ==> List DoubleFloat
```

```
LEDFD    ==> List Expression DoubleFloat
LSAD     ==> Record(lfn:LEDFD, init:LDFD)
UNOALSAD ==> Union(noa:NOAD,lsa:LSAD)
EDFD     ==> Expression DoubleFloat
LOCDFD   ==> List OrderedCompletion DoubleFloat
NOAD     ==> Record(fn:EDFD, init:LDFD, lb:LOCDFD, cf:LEDFD, ub:LOCDFD)

EE ==> SetCategory with
   coerce: NOAD -> %
     ++ coerce(x) is not documented
   coerce: LSAD -> %
     ++ coerce(x) is not documented
   coerce: UNOALSAD -> %
     ++ coerce(x) is not documented
   coerce: % -> OutputForm
     ++ coerce(x) is not documented
   retract: % -> UNOALSAD
     ++ retract(x) is not documented

II ==> add
     Rep := UNOALSAD

     coerce(s:NOAD) == [s]
     coerce(s:LSAD) == [s]
     coerce(x:UNOALSAD) == x
     coerce(x:%):OutputForm ==
       (x) case noa => (x.noa)::OutputForm
       (x.lsa)::OutputForm
     retract(x:%):UNOALSAD ==
       (x) case noa => [x.noa]
       [x.lsa]
```

———-

— OPTPROB.dotabb —

```
"OPTPROB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OPTPROB"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"OPTPROB" -> "BASTYPE"
"OPTPROB" -> "KOERCE"
```

———-

15.10 domain PDEPROB NumericalPDEProblem

— NumericalPDEProblem.input —

```
)set break resume
)sys rm -f NumericalPDEProblem.output
)spool NumericalPDEProblem.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show NumericalPDEProblem
--R
--R NumericalPDEProblem  is a domain constructor
--R Abbreviation for NumericalPDEProblem is PDEPROB
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PDEPROB
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R coerce : Record(pde: List(Expression(DoubleFloat)),constraints: List(Record(start: DoubleFloat,finish: D
--R retract : % -> Record(pde: List(Expression(DoubleFloat)),constraints: List(Record(start: DoubleFloat,fi
--R
--E 1

)spool
)lisp (bye)
```

———-


— NumericalPDEProblem.help —

```
=====================================================================
NumericalPDEProblem examples
=====================================================================

See Also:
o )show NumericalPDEProblem
```

———-

15.10.1 NumericalPDEProblem (PDEPROB)



Exports:
coerce hash latex retract ?=? ?~=?

— domain PDEPROB NumericalPDEProblem —

```
)abbrev domain PDEPROB NumericalPDEProblem
++ Author: Brian Dupee
++ Date Created: December 1997
++ Date Last Updated: December 1997
++ Basic Operations: coerce, retract
++ Related Constructors: Union
++ Description:
++ \axiomType{NumericalPDEProblem} is a \axiom{domain}
++ for the representation of Numerical PDE problems for use
++ by ANNA.
++
++ The representation is of type:
++
++ \axiomType{Record}(pde:\axiomType{List Expression DoubleFloat}, \br
++ constraints:\axiomType{List PDEC}, \br
++ f:\axiomType{List List Expression DoubleFloat},\br
++ st:\axiomType{String},\br
++ tol:\axiomType{DoubleFloat})
++
++ where \axiomType{PDEC} is of type:
++
++ \axiomType{Record}(start:\axiomType{DoubleFloat}, \br
++ finish:\axiomType{DoubleFloat},\br
++ grid:\axiomType{NonNegativeInteger},\br
++ boundaryType:\axiomType{Integer},\br
++ dStart:\axiomType{Matrix DoubleFloat}, \br
++ dFinish:\axiomType{Matrix DoubleFloat})

NumericalPDEProblem(): EE == II where
```

```
DFC   ==> DoubleFloat
NNIC  ==> NonNegativeInteger
INTC  ==> Integer
MDFC  ==> Matrix DoubleFloat
PDECC ==> Record(start:DFC, finish:DFC, grid:NNIC, boundaryType:INTC,
               dStart:MDFC, dFinish:MDFC)
LEDFC ==> List Expression DoubleFloat
PDEBC ==> Record(pde:LEDFC, constraints:List PDECC, f:List LEDFC,
                  st:String, tol:DFC)

EE ==> SetCategory with
   coerce: PDEBC -> %
     ++ coerce(x) is not documented
   coerce: % -> OutputForm
     ++ coerce(x) is not documented
   retract: % -> PDEBC
     ++ retract(x) is not documented

II ==> add
     Rep := PDEBC

     coerce(s:PDEBC) == s
     coerce(x:%):OutputForm ==
       (retract(x))::OutputForm
     retract(x:%):PDEBC == x :: Rep
```

———-

— PDEPROB.dotabb —

```
"PDEPROB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PDEPROB"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"PDEPROB" -> "BASTYPE"
"PDEPROB" -> "KOERCE"
```

———-

Chapter 16

Chapter O

16.1 domain OCT Octonion


The octonions have the following multiplication table:

1	i	j	k	E	I	J	K
i	-1	k	$-j$	I	$-E$	$-K$	J
j	$-k$	-1	i	J	K	$-E$	$-I$
k	j	$-i$	-1	K	$-J$	I	$-E$
E	$-I$	$-J$	$-K$	-1	i	j	k
I	E	$-K$	J	$-i$	-1	$-k$	j
J	K	E	$-I$	$-j$	k	-1	$-i$
K	$-J$	I	E	$-k$	$-j$	i	-1

There are 3 different kinds of associativity. An algebra is

- **power-associative** if the subalgebra generated by any one element is associative. That is, given any element e then $e * (e * e) = (e * e) * e$.
- **alternative** if the subalgebra generated by any two elements is associative That is, given any two elements, a and b then $a * (a * b) = (a * a) * b$ and $a * (b * a) = (a * b) * a$ and $b * (a * a) = (b * a) * a$.
- **associative** if the subalgebra generated by any three elements is associative. That is, given any three elements a, b, and c then $a * (b * c) = (a * b) * c$.

The Octonions are power-associative and alternative but not associative, since $I * (J * K) \neq (I * J) * K$.



— Octonion.input —

```
)set break resume
)sys rm -f Octonion.output
)spool Octonion.output
)set message test on
)set message auto off
)clear all
--S 1 of 15
oci1 := octon(1,2,3,4,5,6,7,8)
--R
--R
--R   (1)  1 + 2i + 3j + 4k + 5E + 6I + 7J + 8K
--R                                                    Type: Octonion(Integer)
--E 1

--S 2 of 15
oci2 := octon(7,2,3,-4,5,6,-7,0)
--R
--R
--R   (2)  7 + 2i + 3j - 4k + 5E + 6I - 7J
--R                                                    Type: Octonion(Integer)
--E 2

--S 3 of 15
oci3 := octon(quatern(-7,-12,3,-10), quatern(5,6,9,0))
```

```
--R
--R
--R   (3)  - 7 - 12i + 3j - 10k + 5E + 6I + 9J
--R                                                    Type: Octonion(Integer)
--E 3

--S 4 of 15
(oci1 * oci2) * oci3 - oci1 * (oci2 * oci3)
--R
--R
--R   (4)  2696i - 2928j - 4072k + 16E - 1192I + 832J + 2616K
--R                                                    Type: Octonion(Integer)
--E 4

--S 5 of 15
[real oci1, imagi oci1, imagj oci1, imagk oci1, _
 imagE oci1, imagI oci1, imagJ oci1, imagK oci1]
--R
--R
--R   (5)  [1,2,3,4,5,6,7,8]
--R                                                 Type: List(PositiveInteger)
--E 5

--S 6 of 15
q : Quaternion Polynomial Integer := quatern(q1, qi, qj, qk)
--R
--R
--R   (6)  q1 + qi i + qj j + qk k
--R                                       Type: Quaternion(Polynomial(Integer))
--E 6

--S 7 of 15
E : Octonion Polynomial Integer:= octon(0,0,0,0,1,0,0,0)
--R
--R
--R   (7)  E
--R                                         Type: Octonion(Polynomial(Integer))
--E 7

--S 8 of 15
q * E
--R
--R
--R   (8)  q1 E + qi I + qj J + qk K
--R                                         Type: Octonion(Polynomial(Integer))
--E 8

--S 9 of 15
E * q
--R
```

```
--R
--R   (9)  q1 E - qi I - qj J - qk K
--R                                          Type: Octonion(Polynomial(Integer))
--E 9

--S 10 of 15
q * 1$(Octonion Polynomial Integer)
--R
--R
--R   (10)  q1 + qi i + qj j + qk k
--R                                          Type: Octonion(Polynomial(Integer))
--E 10

--S 11 of 15
1$(Octonion Polynomial Integer) * q
--R
--R
--R   (11)  q1 + qi i + qj j + qk k
--R                                          Type: Octonion(Polynomial(Integer))
--E 11

--S 12 of 15
o : Octonion Polynomial Integer := octon(o1, oi, oj, ok, oE, oI, oJ, oK)
--R
--R
--R   (12)  o1 + oi i + oj j + ok k + oE E + oI I + oJ J + oK K
--R                                          Type: Octonion(Polynomial(Integer))
--E 12

--S 13 of 15
norm o
--R
--R
--R           2     2     2     2     2     2     2     2
--R   (13)  ok  + oj  + oi  + oK  + oJ  + oI  + oE  + o1
--R                                                  Type: Polynomial(Integer)
--E 13

--S 14 of 15
p : Octonion Polynomial Integer := octon(p1, pi, pj, pk, pE, pI, pJ, pK)
--R
--R
--R   (14)  p1 + pi i + pj j + pk k + pE E + pI I + pJ J + pK K
--R                                          Type: Octonion(Polynomial(Integer))
--E 14

--S 15 of 15
norm(o*p)-norm(p)*norm(o)
--R
--R
```

```
--R   (15)  0
--R                                                  Type: Polynomial(Integer)
--E 15
)spool
)lisp (bye)
```

———-

— Octonion.help —

```
=====================================================================
Octonion examples
=====================================================================

The Octonions, also called the Cayley-Dixon algebra, defined over a
commutative ring are an eight-dimensional non-associative algebra.
Their construction from quaternions is similar to the construction
of quaternions from complex numbers.

As Octonion creates an eight-dimensional algebra, you have to give
eight components to construct an octonion.

  oci1 := octon(1,2,3,4,5,6,7,8)
    1 + 2i + 3j + 4k + 5E + 6I + 7J + 8K
                              Type: Octonion Integer

  oci2 := octon(7,2,3,-4,5,6,-7,0)
    7 + 2i + 3j - 4k + 5E + 6I - 7J
                              Type: Octonion Integer

Or you can use two quaternions to create an octonion.

  oci3 := octon(quatern(-7,-12,3,-10), quatern(5,6,9,0))
    - 7 - 12i + 3j - 10k + 5E + 6I + 9J
                              Type: Octonion Integer

You can easily demonstrate the non-associativity of multiplication.

  (oci1 * oci2) * oci3 - oci1 * (oci2 * oci3)
    2696i - 2928j - 4072k + 16E - 1192I + 832J + 2616K
                              Type: Octonion Integer

As with the quaternions, we have a real part, the imaginary parts
i, j, k, and four additional imaginary parts E, I, J and K. These
parts correspond to the canonical basis (1,i,j,k,E,I,J,K).

For each basis element there is a component operation to extract the
coefficient of the basis element for a given octonion.
```

```
  [real oci1, imagi oci1, imagj oci1, imagk oci1, _
   imagE oci1, imagI oci1, imagJ oci1, imagK oci1]
    [1,2,3,4,5,6,7,8]
                              Type: List PositiveInteger
```

A basis with respect to the quaternions is given by (1,E). However, you might ask, what then are the commuting rules? To answer this, we create some generic elements.

We do this in Axiom by simply changing the ground ring from Integer to Polynomial Integer.

```
  q : Quaternion Polynomial Integer := quatern(q1, qi, qj, qk)
    q1 + qi i + qj j + qk k
                              Type: Quaternion Polynomial Integer

  E : Octonion Polynomial Integer:= octon(0,0,0,0,1,0,0,0)
    E
                              Type: Octonion Polynomial Integer
```

Note that quaternions are automatically converted to octonions in the obvious way.

```
  q * E
    q1 E + qi I + qj J + qk K
                              Type: Octonion Polynomial Integer

  E * q
    q1 E - qi I - qj J - qk K
                              Type: Octonion Polynomial Integer

  q * 1$(Octonion Polynomial Integer)
    q1 + qi i + qj j + qk k
                              Type: Octonion Polynomial Integer

  1$(Octonion Polynomial Integer) * q
    q1 + qi i + qj j + qk k
                              Type: Octonion Polynomial Integer
```

Finally, we check that the norm, defined as the sum of the squares of the coefficients, is a multiplicative map.

```
  o : Octonion Polynomial Integer := octon(o1, oi, oj, ok, oE, oI, oJ, oK)
    o1 + oi i + oj j + ok k + oE E + oI I + oJ J + oK K
                              Type: Octonion Polynomial Integer

  norm o
      2     2     2     2     2     2     2     2
    ok  + oj  + oi  + oK  + oJ  + oI  + oE  + o1
                              Type: Polynomial Integer
```

```
  p : Octonion Polynomial Integer := octon(p1, pi, pj, pk, pE, pI, pJ, pK)
    p1 + pi i + pj j + pk k + pE E + pI I + pJ J + pK K
                                Type: Octonion Polynomial Integer


Since the result is 0, the norm is multiplicative.

  norm(o*p)-norm(p)*norm(o)
    0
                                Type: Polynomial Integer

See Also:
o )help Quaternion
o )show Octonion
```

———-

16.1.1 Octonion (OCT)



Exports:

0	1	abs	characteristic	charthRoot
coerce	conjugate	convert	eval	hash
imagE	imagI	imagJ	imagK	imagi
imagj	imagk	index	inv	latex
lookup	map	max	min	norm
octon	one?	random	rational	rational?
rationalIfCan	real	recip	retract	retractIfCan
sample	size	subtractIfCan	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?	?<?	?<=?	?>?
?>=?	?.?			

— domain OCT Octonion —

```
)abbrev domain OCT Octonion
++ Author: R. Wisbauer, J. Grabmeier
++ Date Created: 05 September 1990
++ Date Last Updated: 20 September 1990
++ Basic Operations: _+,_*,octon,image,imagi,imagj,imagk,
++  imagE,imagI,imagJ,imagK
++ Related Constructors: Quaternion
++ Also See: AlgebraGivenByStructuralConstants
++ AMS Classifications:
++ Keywords: octonion, non-associative algebra, Cayley-Dixon
++ References: e.g. I.L Kantor, A.S. Solodovnikov:
++  Hypercomplex Numbers, Springer Verlag Heidelberg, 1989,
++  ISBN 0-387-96980-2
++ Description:
++ Octonion implements octonions (Cayley-Dixon algebra) over a
++ commutative ring, an eight-dimensional non-associative
++ algebra, doubling the quaternions in the same way as doubling
++ the complex numbers to get the quaternions
++ the main constructor function is octon which takes 8
++ arguments: the real part, the i imaginary part, the j
++ imaginary part, the k imaginary part, (as with quaternions)
++ and in addition the imaginary parts E, I, J, K.

--)boot $noSubsumption := true
Octonion(R:CommutativeRing): export == impl where

  QR ==> Quaternion R

  export ==> Join(OctonionCategory R, FullyRetractableTo QR)  with
    octon: (QR,QR) -> %
      ++ octon(qe,qE) constructs an octonion from two quaternions
      ++ using the relation O = Q + QE.
  impl ==> add
    Rep := Record(e: QR,E: QR)

    0 == [0,0]
    1 == [1,0]

    a,b,c,d,f,g,h,i : R
    p,q : QR
    x,y : %

    real  x == real (x.e)
    imagi x == imagI (x.e)
    imagj x == imagJ (x.e)
    imagk x == imagK (x.e)
    imagE x == real (x.E)
    imagI x == imagI (x.E)
    imagJ x == imagJ (x.E)
    imagK x == imagK (x.E)
```

```
    octon(a,b,c,d,f,g,h,i) == [quatern(a,b,c,d)$QR,quatern(f,g,h,i)$QR]
    octon(p,q) == [p,q]
    coerce(q) == [q,0$QR]
    retract(x):QR ==
      not(zero? imagE x and zero? imagI x and zero? imagJ x and zero? imagK x)=>
        error "Cannot retract octonion to quaternion."
      quatern(real x, imagi x,imagj x, imagk x)$QR
    retractIfCan(x):Union(QR,"failed") ==
      not(zero? imagE x and zero? imagI x and zero? imagJ x and zero? imagK x)=>
        "failed"
      quatern(real x, imagi x,imagj x, imagk x)$QR
    x * y == [x.e*y.e-(conjugate y.E)*x.E, y.E*x.e + x.E*(conjugate y.e)]
```

———-

— OCT.dotabb —

```
"OCT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OCT"]
"OC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OC"]
"QUATCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=QUATCAT"]
"OCT" -> "OC"
"OCT" -> "QUATCAT"
```

———-

16.2 domain ODEIFTBL ODEIntensityFunctionsTable

— ODEIntensityFunctionsTable.input —

```
)set break resume
)sys rm -f ODEIntensityFunctionsTable.output
)spool ODEIntensityFunctionsTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ODEIntensityFunctionsTable
--R
--R ODEIntensityFunctionsTable  is a domain constructor
--R Abbreviation for ODEIntensityFunctionsTable is ODEIFTBL
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ODEIFTBL
--R
```

```
--R------------------------------ Operations ------------------------------
--R clearTheIFTable : () -> Void          showTheIFTable : () -> %
--R iFTable : List(Record(key: Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression
--R insert! : Record(key: Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(Doub
--R keys : % -> List(Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(DoubleFlo
--R showIntensityFunctions : Record(xinit: DoubleFloat,xend: DoubleFloat,fn: Vector(Expression(D
--R
--E 1

)spool
)lisp (bye)
```

———-


— ODEIntensityFunctionsTable.help —

```
=====================================================================
ODEIntensityFunctionsTable examples
=====================================================================

See Also:
o )show ODEIntensityFunctionsTable
```

———-

16.2.1 ODEIntensityFunctionsTable (ODEIFTBL)



Exports:
clearTheIFTable iFTable insert! keys showIntensityFunctions showTheIFTable

— domain ODEIFTBL ODEIntensityFunctionsTable —

```
)abbrev domain ODEIFTBL ODEIntensityFunctionsTable
```

```
++ Author: Brian Dupee
++ Date Created: May 1994
++ Date Last Updated: January 1996
++ Basic Operations: showTheIFTable, insert!
++ Description:
++ \axiom{ODEIntensityFunctionsTable()} provides a dynamic table and a set of
++ functions to store details found out about sets of ODE's.

ODEIntensityFunctionsTable(): E == I where
  LEDF  ==> List Expression DoubleFloat
  LEEDF  ==> List Equation Expression DoubleFloat
  EEDF  ==> Equation Expression DoubleFloat
  VEDF  ==> Vector Expression DoubleFloat
  MEDF  ==> Matrix Expression DoubleFloat
  MDF  ==> Matrix DoubleFloat
  EDF  ==> Expression DoubleFloat
  DF  ==> DoubleFloat
  F  ==> Float
  INT  ==> Integer
  CDF  ==> Complex DoubleFloat
  LDF  ==> List DoubleFloat
  LF  ==> List Float
  S  ==> Symbol
  LS  ==> List Symbol
  MFI  ==> Matrix Fraction Integer
  LFI  ==> List Fraction Integer
  FI  ==> Fraction Integer
  ODEA  ==> Record(xinit:DF,xend:DF,fn:VEDF,yinit:LDF,intvals:LDF,g:EDF,abserr:DF,relerr:DF)
  ON  ==> Record(additions:INT,multiplications:INT,exponentiations:INT,functionCalls:INT)
  RVE   ==> Record(val:EDF,exponent:INT)
  RSS  ==> Record(stiffnessFactor:F,stabilityFactor:F)
  ATT  ==> Record(stiffness:F,stability:F,expense:F,accuracy:F,intermediateResults:F)
  ROA  ==> Record(key:ODEA,entry:ATT)

  E ==> with
    showTheIFTable:() -> $
      ++ showTheIFTable() returns the current table of intensity functions.
    clearTheIFTable : () -> Void
      ++ clearTheIFTable() clears the current table of intensity functions.
    keys : $ -> List(ODEA)
      ++ keys(tab) returns the list of keys of f
    iFTable: List Record(key:ODEA,entry:ATT) -> $
      ++ iFTable(l) creates an intensity-functions table from the elements
      ++ of l.
    insert!:Record(key:ODEA,entry:ATT) -> $
      ++ insert!(r) inserts an entry r into theIFTable
    showIntensityFunctions:ODEA -> Union(ATT,"failed")
      ++ showIntensityFunctions(k) returns the entries in the
      ++ table of intensity functions k.
```

```
  I ==> add
    Rep := Table(ODEA,ATT)
    import Rep

    theIFTable:$ := empty()$Rep

    showTheIFTable():$ ==
      theIFTable

    clearTheIFTable():Void ==
      theIFTable := empty()$Rep
      void()$Void

    iFTable(l:List Record(key:ODEA,entry:ATT)):$ ==
      theIFTable := table(l)$Rep

    insert!(r:Record(key:ODEA,entry:ATT)):$ ==
      insert!(r,theIFTable)$Rep

    keys(t:$):List ODEA ==
      keys(t)$Rep

    showIntensityFunctions(k:ODEA):Union(ATT,"failed") ==
      search(k,theIFTable)$Rep
```

———-

— ODEIFTBL.dotabb —

```
"ODEIFTBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ODEIFTBL"]
"Domain" [color="#88FF44"]
"ODEIFTBL" -> "Domain"
```

———-

16.3 domain ARRAY1 OneDimensionalArray

— OneDimensionalArray.input —

```
)set break resume
)sys rm -f OneDimensionalArray.output
)spool OneDimensionalArray.output
)set message test on
)set message auto off
```

```
)clear all
--S 1 of 9
oneDimensionalArray [i**2 for i in 1..10]
--R
--R
--R   (1)  [1,4,9,16,25,36,49,64,81,100]
--R                                  Type: OneDimensionalArray(PositiveInteger)
--E 1

--S 2 of 9
a : ARRAY1 INT := new(10,0)
--R
--R
--R   (2)  [0,0,0,0,0,0,0,0,0,0]
--R                                          Type: OneDimensionalArray(Integer)
--E 2

--S 3 of 9
for i in 1..10 repeat a.i := i; a
--R
--R
--R   (3)  [1,2,3,4,5,6,7,8,9,10]
--R                                          Type: OneDimensionalArray(Integer)
--E 3

--S 4 of 9
map!(i +-> i ** 2,a); a
--R
--R
--R   (4)  [1,4,9,16,25,36,49,64,81,100]
--R                                          Type: OneDimensionalArray(Integer)
--E 4

--S 5 of 9
reverse! a
--R
--R
--R   (5)  [100,81,64,49,36,25,16,9,4,1]
--R                                          Type: OneDimensionalArray(Integer)
--E 5

--S 6 of 9
swap!(a,4,5); a
--R
--R
--R   (6)  [100,81,64,36,49,25,16,9,4,1]
--R                                          Type: OneDimensionalArray(Integer)
--E 6

--S 7 of 9
```

```
sort! a
--R
--R
--R   (7)  [1,4,9,16,25,36,49,64,81,100]
--R                                          Type: OneDimensionalArray(Integer)
--E 7

--S 8 of 9
b := a(6..10)
--R
--R
--R   (8)  [36,49,64,81,100]
--R                                          Type: OneDimensionalArray(Integer)
--E 8

--S 9 of 9
copyInto!(a,b,1)
--R
--R
--R   (9)  [36,49,64,81,100,36,49,64,81,100]
--R                                          Type: OneDimensionalArray(Integer)
--E 9
)spool
)lisp (bye)
```

———-

— OneDimensionalArray.help —

```
=====================================================================
OneDimensionalArray examples
=====================================================================

The OneDimensionalArray domain is used for storing data in a
one-dimensional indexed data structure.  Such an array is a
homogeneous data structure in that all the entries of the array must
belong to the same Axiom domain.  Each array has a fixed length
specified by the user and arrays are not extensible.  The indexing of
one-dimensional arrays is one-based.  This means that the "first"
element of an array is given the index 1.

To create a one-dimensional array, apply the operation
oneDimensionalArray to a list.

  oneDimensionalArray [i**2 for i in 1..10]
    [1,4,9,16,25,36,49,64,81,100]
                    Type: OneDimensionalArray PositiveInteger

Another approach is to first create a, a one-dimensional array of 10
```

```
0's.  OneDimensionalArray has the convenient abbreviation ARRAY1.

  a : ARRAY1 INT := new(10,0)
    [0,0,0,0,0,0,0,0,0,0]
                    Type: OneDimensionalArray Integer

Set each i-th element to i, then display the result.

  for i in 1..10 repeat a.i := i; a
    [1,2,3,4,5,6,7,8,9,10]
                    Type: OneDimensionalArray Integer

Square each element by mapping the function i +-> i^2 onto each element.

  map!(i +-> i ** 2,a); a
    [1,4,9,16,25,36,49,64,81,100]
                    Type: OneDimensionalArray Integer

Reverse the elements in place.

  reverse! a
    [100,81,64,49,36,25,16,9,4,1]
                    Type: OneDimensionalArray Integer

Swap the 4th and 5th element.

  swap!(a,4,5); a
    [100,81,64,36,49,25,16,9,4,1]
                    Type: OneDimensionalArray Integer

Sort the elements in place.

  sort! a
    [1,4,9,16,25,36,49,64,81,100]
                    Type: OneDimensionalArray Integer

Create a new one-dimensional array b containing the last 5 elements of a.

  b := a(6..10)
    [36,49,64,81,100]
                    Type: OneDimensionalArray Integer

Replace the first 5 elements of a with those of b.


  copyInto!(a,b,1)
    [36,49,64,81,100,36,49,64,81,100]
                    Type: OneDimensionalArray Integer

See Also:
o )help Vector
```

```
o )help FlexibleArray
o )show OneDimensionalArray
```

———-

16.3.1 OneDimensionalArray (ARRAY1)



See

⇒ “PrimitiveArray” (PRIMARR) 17.30.1 on page 2075
⇒ “Tuple” (TUPLE) 21.12.1 on page 2721
⇒ “IndexedFlexibleArray” (IFARRAY) 10.10.1 on page 1191
⇒ “FlexibleArray” (FARRAY) 7.14.1 on page 856
⇒ “IndexedOneDimensionalArray” (IARRAY1) 10.13.1 on page 1212

Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	delete	elt
empty	empty?	entries	entry?	eq?
eval	every?	fill!	find	first
hash	index?	indices	insert	latex
less?	map	map!	max	maxIndex
member?	members	merge	min	minIndex
more?	new	oneDimensionalArray	parts	position
qelt	qsetelt!	reduce	remove	removeDuplicates
reverse	reverse!	sample	select	setelt
size?	sort	sort!	sorted?	swap!
#?	?<?	?<=?	?=?	?>?
?>=?	?~=?	?.?		

— **domain ARRAY1 OneDimensionalArray** —

```
)abbrev domain ARRAY1 OneDimensionalArray
++ Author: Mark Botch
```

```
++ Description:
++ This is the domain of 1-based one dimensional arrays

OneDimensionalArray(S:Type): Exports == Implementation where
  ARRAYMININDEX ==> 1       -- if you want to change this, be my guest
  Exports == OneDimensionalArrayAggregate S with
   oneDimensionalArray: List S -> %
    ++ oneDimensionalArray(l) creates an array from a list of elements l
    ++
    ++X oneDimensionalArray [i**2 for i in 1..10]

   oneDimensionalArray: (NonNegativeInteger, S) -> %
    ++ oneDimensionalArray(n,s) creates an array from n copies of element s
    ++
    ++X oneDimensionalArray(10,0.0)

  Implementation == IndexedOneDimensionalArray(S, ARRAYMININDEX) add
    oneDimensionalArray(u) ==
      n := #u
      n = 0 => empty()
      a := new(n, first u)
      for i in 2..n for x in rest u repeat a.i := x
      a
    oneDimensionalArray(n,s) == new(n,s)
```

———-

— ARRAY1.dotabb —

```
"ARRAY1" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ARRAY1"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"ARRAY1" -> "A1AGG"
```

———-

16.4 domain ONECOMP OnePointCompletion

— OnePointCompletion.input —

```
)set break resume
)sys rm -f OnePointCompletion.output
)spool OnePointCompletion.output
)set message test on
)set message auto off
```

```
)clear all

--S 1 of 1
)show OnePointCompletion
--R
--R OnePointCompletion(R: SetCategory)  is a domain constructor
--R Abbreviation for OnePointCompletion is ONECOMP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ONECOMP
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if R has ABELGRP          ?=? : (%,%) -> Boolean
--R 1 : () -> % if R has ORDRING          0 : () -> % if R has ABELGRP
--R coerce : R -> %                       coerce : % -> OutputForm
--R finite? : % -> Boolean                hash : % -> SingleInteger
--R infinite? : % -> Boolean              infinity : () -> %
--R latex : % -> String                   retract : % -> R
--R ?~=? : (%,%) -> Boolean
--R ?*? : (PositiveInteger,%) -> % if R has ABELGRP
--R ?*? : (NonNegativeInteger,%) -> % if R has ABELGRP
--R ?*? : (Integer,%) -> % if R has ABELGRP
--R ?*? : (%,%) -> % if R has ORDRING
--R ?**? : (%,NonNegativeInteger) -> % if R has ORDRING
--R ?**? : (%,PositiveInteger) -> % if R has ORDRING
--R ?+? : (%,%) -> % if R has ABELGRP
--R ?-? : (%,%) -> % if R has ABELGRP
--R ?<? : (%,%) -> Boolean if R has ORDRING
--R ?<=? : (%,%) -> Boolean if R has ORDRING
--R ?>? : (%,%) -> Boolean if R has ORDRING
--R ?>=? : (%,%) -> Boolean if R has ORDRING
--R ?^? : (%,NonNegativeInteger) -> % if R has ORDRING
--R ?^? : (%,PositiveInteger) -> % if R has ORDRING
--R abs : % -> % if R has ORDRING
--R characteristic : () -> NonNegativeInteger if R has ORDRING
--R coerce : Integer -> % if R has ORDRING or R has RETRACT(INT)
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT))
--R max : (%,%) -> % if R has ORDRING
--R min : (%,%) -> % if R has ORDRING
--R negative? : % -> Boolean if R has ORDRING
--R one? : % -> Boolean if R has ORDRING
--R positive? : % -> Boolean if R has ORDRING
--R rational : % -> Fraction(Integer) if R has INS
--R rational? : % -> Boolean if R has INS
--R rationalIfCan : % -> Union(Fraction(Integer),"failed") if R has INS
--R recip : % -> Union(%,"failed") if R has ORDRING
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
```

```
--R sample : () -> % if R has ABELGRP
--R sign : % -> Integer if R has ORDRING
--R subtractIfCan : (%,%) -> Union(%,"failed") if R has ABELGRP
--R zero? : % -> Boolean if R has ABELGRP
--R
--E 1

)spool
)lisp (bye)
```

———-


— **OnePointCompletion.help** —

```
=====================================================================
OnePointCompletion examples
=====================================================================

See Also:
o )show OnePointCompletion
```

———-

16.4.1 OnePointCompletion (ONECOMP)



See

⇒ “OrderedCompletion” (ORDCOMP) 16.12.1 on page 1776

Exports:

0	1	abs	characteristic	coerce
coerce	finite?	hash	infinite?	infinity
latex	max	min	negative?	one?
positive?	rational	rational?	rationalIfCan	recip
retract	retractIfCan	sample	sign	subtractIfCan
zero?	-?	?=?	?~=?	?*?
?**?	?+?	?-?	?<?	?<=?
?>?	?>=?	?^?		

— domain ONECOMP OnePointCompletion —

```
)abbrev domain ONECOMP OnePointCompletion
++ Author: Manuel Bronstein
++ Date Created: 4 Oct 1989
++ Date Last Updated: 1 Nov 1989
++ Description:
++ Completion with infinity.
++ Adjunction of a complex infinity to a set.

OnePointCompletion(R:SetCategory): Exports == Implementation where
  B ==> Boolean

  Exports ==> Join(SetCategory, FullyRetractableTo R) with
    infinity : () -> %
      ++  infinity() returns infinity.
    finite?  : %  -> B
      ++ finite?(x) tests if x is finite.
    infinite?: %  -> B
      ++ infinite?(x) tests if x is infinite.
    if R has AbelianGroup then AbelianGroup
    if R has OrderedRing then OrderedRing
    if R has IntegerNumberSystem then
      rational?: % -> Boolean
        ++ rational?(x) tests if x is a finite rational number.
      rational : % -> Fraction Integer
        ++ rational(x) returns x as a finite rational number.
        ++ Error: if x is not a rational number.
      rationalIfCan: % -> Union(Fraction Integer, "failed")
        ++ rationalIfCan(x) returns x as a finite rational number if
        ++ it is one, "failed" otherwise.

  Implementation ==> add
    Rep := Union(R, "infinity")

    coerce(r:R):%          == r
    retract(x:%):R         == (x case R => x::R; error "Not finite")
    finite? x              == x case R
    infinite? x            == x case "infinity"
    infinity()             == "infinity"
```

```
retractIfCan(x:%):Union(R, "failed") == (x case R => x::R; "failed")

coerce(x:%):OutputForm ==
  x case "infinity" => "infinity"::OutputForm
  x::R::OutputForm

x = y ==
  x case "infinity" => y case "infinity"
  y case "infinity" => false
  x::R = y::R

if R has AbelianGroup then
  0 == 0$R

  n:Integer * x:% ==
    x case "infinity" =>
      zero? n => error "Undefined product"
      infinity()
    n * x::R

  - x ==
    x case "infinity" => error "Undefined inverse"
    - (x::R)

  x + y ==
    x case "infinity" => x
    y case "infinity" => y
    x::R + y::R

if R has OrderedRing then
  fininf: R -> %

  1                == 1$R
  characteristic() == characteristic()$R

  fininf r ==
    zero? r => error "Undefined product"
    infinity()

  x:% * y:% ==
    x case "infinity" =>
      y case "infinity" => y
      fininf(y::R)
    y case "infinity" => fininf(x::R)
    x::R * y::R

  recip x ==
    x case "infinity" => 0
    zero?(x::R) => infinity()
    (u := recip(x::R)) case "failed" => "failed"
```

```
        u::R::%

      x < y ==
        x case "infinity" => false     -- do not change the order
        y case "infinity" => true      -- of those two tests
        x::R < y::R

    if R has IntegerNumberSystem then
      rational? x == finite? x
      rational  x == rational(retract(x)@R)

      rationalIfCan x ==
        (r:= retractIfCan(x)@Union(R,"failed")) case "failed" =>"failed"
        rational(r::R)
```

———-

— ONECOMP.dotabb —

```
"ONECOMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ONECOMP"]
"FRETRCT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRETRCT"]
"ONECOMP" -> "FRETRCT"
```

———-

16.5 domain OMCONN OpenMathConnection

— OpenMathConnection.input —

```
)set break resume
)sys rm -f OpenMathConnection.output
)spool OpenMathConnection.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OpenMathConnection
--R OpenMathConnection  is a domain constructor
--R Abbreviation for OpenMathConnection is OMCONN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OMCONN
--R
--R------------------------------ Operations --------------------------------
```

```
--R OMcloseConn : % -> Void                OMmakeConn : SingleInteger -> %
--R OMbindTCP : (%,SingleInteger) -> Boolean
--R OMconnInDevice : % -> OpenMathDevice
--R OMconnOutDevice : % -> OpenMathDevice
--R OMconnectTCP : (%,String,SingleInteger) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **OpenMathConnection.help** —

```
=====================================================================
OpenMathConnection examples
=====================================================================

See Also:
o )show OpenMathConnection
```

———-

16.5.1 OpenMathConnection (OMCONN)



See

⇒ “OpenMathEncoding” (OMENC) 16.7.1 on page 1755
⇒ “OpenMathDevice” (OMDEV) 16.6.1 on page 1750

Exports:

OMbindTCP	OMcloseConn	OMconnectTCP	OMconnInDevice
OMconnOutDevice	OMmakeConn		

— **domain OMCONN OpenMathConnection** —

```
)abbrev domain OMCONN OpenMathConnection
++ Author: Vilya Harvey
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \spadtype{OpenMathConnection} provides low-level functions
++ for handling connections to and from \spadtype{OpenMathDevice}s.

OpenMathConnection(): with
  OMmakeConn    : SingleInteger -> % ++ \spad{OMmakeConn}
  OMcloseConn   : % -> Void ++ \spad{OMcloseConn}
  OMconnInDevice: %-> OpenMathDevice ++ \spad{OMconnInDevice:}
  OMconnOutDevice: %-> OpenMathDevice ++ \spad{OMconnOutDevice:}
  OMconnectTCP  : (%, String, SingleInteger) -> Boolean ++ \spad{OMconnectTCP}
  OMbindTCP     : (%, SingleInteger) -> Boolean ++ \spad{OMbindTCP}
 == add
  OMmakeConn(timeout: SingleInteger): % == OM_-MAKECONN(timeout)$Lisp
  OMcloseConn(conn: %): Void == OM_-CLOSECONN(conn)$Lisp

  OMconnInDevice(conn: %): OpenMathDevice ==
    OM_-GETCONNINDEV(conn)$Lisp
  OMconnOutDevice(conn: %): OpenMathDevice ==
    OM_-GETCONNOUTDEV(conn)$Lisp

  OMconnectTCP(conn: %, host: String, port: SingleInteger): Boolean ==
    OM_-CONNECTTCP(conn, host, port)$Lisp
  OMbindTCP(conn: %, port: SingleInteger): Boolean ==
    OM_-BINDTCP(conn, port)$Lisp
```

———-

— OMCONN.dotabb —

```
"OMCONN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OMCONN"]
"Domain" [color="#88FF44"]
"OMCONN" -> "Domain"
```

———-

16.6 domain OMDEV OpenMathDevice

— OpenMathDevice.input —

```
)set break resume
)sys rm -f OpenMathDevice.output
)spool OpenMathDevice.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OpenMathDevice
--R OpenMathDevice  is a domain constructor
--R Abbreviation for OpenMathDevice is OMDEV
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OMDEV
--R
--R------------------------------ Operations --------------------------------
--R OMclose : % -> Void                  OMgetApp : % -> Void
--R OMgetAtp : % -> Void                 OMgetAttr : % -> Void
--R OMgetBVar : % -> Void                OMgetBind : % -> Void
--R OMgetEndApp : % -> Void              OMgetEndAtp : % -> Void
--R OMgetEndAttr : % -> Void             OMgetEndBVar : % -> Void
--R OMgetEndBind : % -> Void             OMgetEndError : % -> Void
--R OMgetEndObject : % -> Void           OMgetError : % -> Void
--R OMgetFloat : % -> DoubleFloat        OMgetInteger : % -> Integer
--R OMgetObject : % -> Void              OMgetString : % -> String
--R OMgetType : % -> Symbol              OMgetVariable : % -> Symbol
--R OMputApp : % -> Void                 OMputAtp : % -> Void
--R OMputAttr : % -> Void                OMputBVar : % -> Void
--R OMputBind : % -> Void                OMputEndApp : % -> Void
--R OMputEndAtp : % -> Void              OMputEndAttr : % -> Void
--R OMputEndBVar : % -> Void             OMputEndBind : % -> Void
--R OMputEndError : % -> Void            OMputEndObject : % -> Void
--R OMputError : % -> Void               OMputObject : % -> Void
--R OMputString : (%,String) -> Void
--R OMgetSymbol : % -> Record(cd: String,name: String)
--R OMopenFile : (String,String,OpenMathEncoding) -> %
--R OMopenString : (String,OpenMathEncoding) -> %
--R OMputFloat : (%,DoubleFloat) -> Void
--R OMputInteger : (%,Integer) -> Void
--R OMputSymbol : (%,String,String) -> Void
--R OMputVariable : (%,Symbol) -> Void
--R OMsetEncoding : (%,OpenMathEncoding) -> Void
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **OpenMathDevice.help** —

```
=====================================================================
OpenMathDevice examples
=====================================================================

See Also:
o )show OpenMathDevice
```

———-

16.6.1 OpenMathDevice (OMDEV)



See

⇒ “OpenMathEncoding” (OMENC) 16.7.1 on page 1755
⇒ “OpenMathConnection” (OMCONN) 16.5.1 on page 1747

Exports:

OMclose	OMgetApp	OMgetAtp	OMgetAttr
OMgetBVar	OMgetBind	OMgetEndApp	OMgetEndAtp
OMgetEndAttr	OMgetEndBVar	OMgetEndBind	OMgetEndError
OMgetEndObject	OMgetError	OMgetFloat	OMgetInteger
OMgetObject	OMgetString	OMgetType	OMgetVariable
OMputApp	OMputAtp	OMputAttr	OMputBVar
OMputBind	OMputEndApp	OMputEndAtp	OMputEndAttr
OMputEndBVar	OMputEndBind	OMputEndError	OMputEndObject
OMputError	OMputObject	OMputString	OMgetSymbol
OMopenFile	OMopenString	OMputFloat	OMputInteger
OMputSymbol	OMputVariable	OMsetEncoding	

— domain OMDEV OpenMathDevice —

```
)abbrev domain OMDEV OpenMathDevice
++ Author: Vilya Harvey
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \spadtype{OpenMathDevice} provides support for reading
++ and writing openMath objects to files, strings etc.  It also provides
++ access to low-level operations from within the interpreter.

OpenMathDevice(): with
  OMopenFile    : (String, String, OpenMathEncoding) -> %
  ++ OMopenFile(f,mode,enc) opens file \axiom{f} for reading or writing
  ++ OpenMath objects (depending on \axiom{mode} which can be "r", "w"
  ++ or "a" for read, write and append respectively), in the encoding
  ++ \axiom{enc}.
  OMopenString  : (String, OpenMathEncoding) -> %
  ++ OMopenString(s,mode) opens the string \axiom{s} for reading or writing
  ++ OpenMath objects in encoding \axiom{enc}.
  OMclose       : % -> Void
  ++ OMclose(dev) closes \axiom{dev}, flushing output if necessary.
  OMsetEncoding : (%, OpenMathEncoding) -> Void
  ++ OMsetEncoding(dev,enc) sets the encoding used for reading or writing
  ++ OpenMath objects to or from \axiom{dev} to \axiom{enc}.
  OMputApp      : % -> Void
  ++ OMputApp(dev) writes a begin application token to \axiom{dev}.
  OMputAtp      : % -> Void
  ++ OMputAtp(dev) writes a begin attribute pair token to \axiom{dev}.
  OMputAttr     : % -> Void
  ++ OMputAttr(dev) writes a begin attribute token to \axiom{dev}.
  OMputBind     : % -> Void
  ++ OMputBind(dev) writes a begin binder token to \axiom{dev}.
  OMputBVar     : % -> Void
  ++ OMputBVar(dev) writes a begin bound variable list token to \axiom{dev}.
  OMputError    : % -> Void
  ++ OMputError(dev) writes a begin error token to \axiom{dev}.
  OMputObject   : % -> Void
  ++ OMputObject(dev) writes a begin object token to \axiom{dev}.
  OMputEndApp   : % -> Void
  ++ OMputEndApp(dev) writes an end application token to \axiom{dev}.
  OMputEndAtp   : % -> Void
  ++ OMputEndAtp(dev) writes an end attribute pair token to \axiom{dev}.
```

```
OMputEndAttr  : % -> Void
++ OMputEndAttr(dev) writes an end attribute token to \axiom{dev}.
OMputEndBind  : % -> Void
++ OMputEndBind(dev) writes an end binder token to \axiom{dev}.
OMputEndBVar  : % -> Void
++ OMputEndBVar(dev) writes an end bound variable list token to \axiom{dev}.
OMputEndError : % -> Void
++ OMputEndError(dev) writes an end error token to \axiom{dev}.
OMputEndObject: % -> Void
++ OMputEndObject(dev) writes an end object token to \axiom{dev}.
OMputInteger  : (%, Integer) -> Void
++ OMputInteger(dev,i) writes the integer \axiom{i} to \axiom{dev}.
OMputFloat    : (%, DoubleFloat) -> Void
++ OMputFloat(dev,i) writes the float \axiom{i} to \axiom{dev}.
OMputVariable : (%, Symbol) -> Void
++ OMputVariable(dev,i) writes the variable \axiom{i} to \axiom{dev}.
OMputString   : (%, String) -> Void
++ OMputString(dev,i) writes the string \axiom{i} to \axiom{dev}.
OMputSymbol   : (%, String, String) -> Void
++ OMputSymbol(dev,cd,s) writes the symbol \axiom{s} from CD \axiom{cd}
++ to \axiom{dev}.

OMgetApp      : % -> Void
++ OMgetApp(dev) reads a begin application token from \axiom{dev}.
OMgetAtp      : % -> Void
++ OMgetAtp(dev) reads a begin attribute pair token from \axiom{dev}.
OMgetAttr     : % -> Void
++ OMgetAttr(dev) reads a begin attribute token from \axiom{dev}.
OMgetBind     : % -> Void
++ OMgetBind(dev) reads a begin binder token from \axiom{dev}.
OMgetBVar     : % -> Void
++ OMgetBVar(dev) reads a begin bound variable list token from \axiom{dev}.
OMgetError    : % -> Void
++ OMgetError(dev) reads a begin error token from \axiom{dev}.
OMgetObject   : % -> Void
++ OMgetObject(dev) reads a begin object token from \axiom{dev}.
OMgetEndApp   : % -> Void
++ OMgetEndApp(dev) reads an end application token from \axiom{dev}.
OMgetEndAtp   : % -> Void
++ OMgetEndAtp(dev) reads an end attribute pair token from \axiom{dev}.
OMgetEndAttr  : % -> Void
++ OMgetEndAttr(dev) reads an end attribute token from \axiom{dev}.
OMgetEndBind  : % -> Void
++ OMgetEndBind(dev) reads an end binder token from \axiom{dev}.
OMgetEndBVar  : % -> Void
++ OMgetEndBVar(dev) reads an end bound variable list token from \axiom{dev}.
OMgetEndError : % -> Void
++ OMgetEndError(dev) reads an end error token from \axiom{dev}.
OMgetEndObject: % -> Void
++ OMgetEndObject(dev) reads an end object token from \axiom{dev}.
```

```
 OMgetInteger  : % -> Integer
 ++ OMgetInteger(dev) reads an integer from \axiom{dev}.
 OMgetFloat    : % -> DoubleFloat
 ++ OMgetFloat(dev) reads a float from \axiom{dev}.
 OMgetVariable : % -> Symbol
 ++ OMgetVariable(dev) reads a variable from \axiom{dev}.
 OMgetString   : % -> String
 ++ OMgetString(dev) reads a string from \axiom{dev}.
 OMgetSymbol   : % -> Record(cd:String, name:String)
 ++ OMgetSymbol(dev) reads a symbol from \axiom{dev}.

 OMgetType     : % -> Symbol
 ++ OMgetType(dev) returns the type of the next object on \axiom{dev}.
== add
 OMopenFile(fname: String, fmode: String, enc: OpenMathEncoding): % ==
   OM_-OPENFILEDEV(fname, fmode, enc)$Lisp
 OMopenString(str: String, enc: OpenMathEncoding): % ==
   OM_-OPENSTRINGDEV(str, enc)$Lisp
 OMclose(dev: %): Void ==
   OM_-CLOSEDEV(dev)$Lisp
 OMsetEncoding(dev: %, enc: OpenMathEncoding): Void ==
   OM_-SETDEVENCODING(dev, enc)$Lisp

 OMputApp(dev: %): Void == OM_-PUTAPP(dev)$Lisp
 OMputAtp(dev: %): Void == OM_-PUTATP(dev)$Lisp
 OMputAttr(dev: %): Void == OM_-PUTATTR(dev)$Lisp
 OMputBind(dev: %): Void == OM_-PUTBIND(dev)$Lisp
 OMputBVar(dev: %): Void == OM_-PUTBVAR(dev)$Lisp
 OMputError(dev: %): Void == OM_-PUTERROR(dev)$Lisp
 OMputObject(dev: %): Void == OM_-PUTOBJECT(dev)$Lisp
 OMputEndApp(dev: %): Void == OM_-PUTENDAPP(dev)$Lisp
 OMputEndAtp(dev: %): Void == OM_-PUTENDATP(dev)$Lisp
 OMputEndAttr(dev: %): Void == OM_-PUTENDATTR(dev)$Lisp
 OMputEndBind(dev: %): Void == OM_-PUTENDBIND(dev)$Lisp
 OMputEndBVar(dev: %): Void == OM_-PUTENDBVAR(dev)$Lisp
 OMputEndError(dev: %): Void == OM_-PUTENDERROR(dev)$Lisp
 OMputEndObject(dev: %): Void == OM_-PUTENDOBJECT(dev)$Lisp
 OMputInteger(dev: %, i: Integer): Void == OM_-PUTINT(dev, i)$Lisp
 OMputFloat(dev: %, f: DoubleFloat): Void == OM_-PUTFLOAT(dev, f)$Lisp
 --OMputByteArray(dev: %, b: Array Byte): Void == OM_-PUTBYTEARRAY(dev, b)$Lisp
 OMputVariable(dev: %, v: Symbol): Void == OM_-PUTVAR(dev, v)$Lisp
 OMputString(dev: %, s: String): Void == OM_-PUTSTRING(dev, s)$Lisp
 OMputSymbol(dev: %, cd: String, nm: String): Void == OM_-PUTSYMBOL(dev, cd, nm)$Lisp

 OMgetApp(dev: %): Void == OM_-GETAPP(dev)$Lisp
 OMgetAtp(dev: %): Void == OM_-GETATP(dev)$Lisp
 OMgetAttr(dev: %): Void == OM_-GETATTR(dev)$Lisp
 OMgetBind(dev: %): Void == OM_-GETBIND(dev)$Lisp
 OMgetBVar(dev: %): Void == OM_-GETBVAR(dev)$Lisp
 OMgetError(dev: %): Void == OM_-GETERROR(dev)$Lisp
```

```
  OMgetObject(dev: %): Void == OM_-GETOBJECT(dev)$Lisp
  OMgetEndApp(dev: %): Void == OM_-GETENDAPP(dev)$Lisp
  OMgetEndAtp(dev: %): Void == OM_-GETENDATP(dev)$Lisp
  OMgetEndAttr(dev: %): Void == OM_-GETENDATTR(dev)$Lisp
  OMgetEndBind(dev: %): Void == OM_-GETENDBIND(dev)$Lisp
  OMgetEndBVar(dev: %): Void == OM_-GETENDBVAR(dev)$Lisp
  OMgetEndError(dev: %): Void == OM_-GETENDERROR(dev)$Lisp
  OMgetEndObject(dev: %): Void == OM_-GETENDOBJECT(dev)$Lisp
  OMgetInteger(dev: %): Integer == OM_-GETINT(dev)$Lisp
  OMgetFloat(dev: %): DoubleFloat == OM_-GETFLOAT(dev)$Lisp
  --OMgetByteArray(dev: %): Array Byte == OM_-GETBYTEARRAY(dev)$Lisp
  OMgetVariable(dev: %): Symbol == OM_-GETVAR(dev)$Lisp
  OMgetString(dev: %): String == OM_-GETSTRING(dev)$Lisp
  OMgetSymbol(dev: %): Record(cd:String, name:String) == OM_-GETSYMBOL(dev)$Lisp

  OMgetType(dev: %): Symbol == OM_-GETTYPE(dev)$Lisp
```

———-

— OMDEV.dotabb —

```
"OMDEV" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OMDEV"]
"Domain" [color="#88FF44"]
"OMDEV" -> "Domain"
```

———-

16.7 domain OMENC OpenMathEncoding

— OpenMathEncoding.input —

```
)set break resume
)sys rm -f OpenMathEncoding.output
)spool OpenMathEncoding.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OpenMathEncoding
--R OpenMathEncoding  is a domain constructor
--R Abbreviation for OpenMathEncoding is OMENC
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OMENC
```

```
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                OMencodingBinary : () -> %
--R OMencodingSGML : () -> %              OMencodingUnknown : () -> %
--R OMencodingXML : () -> %               coerce : % -> OutputForm
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **OpenMathEncoding.help** —

```
=====================================================================
OpenMathEncoding examples
=====================================================================

See Also:
o )show OpenMathEncoding
```

———-

16.7.1 OpenMathEncoding (OMENC)



See

⇒ “OpenMathDevice” (OMDEV) 16.6.1 on page 1750
⇒ “OpenMathConnection” (OMCONN) 16.5.1 on page 1747

Exports:

coerce	hash	latex	OMencodingBinary	OMencodingSGML
OMencodingUnknown	OMencodingXML	?=?	?~=?	

— domain OMENC OpenMathEncoding —

```
)abbrev domain OMENC OpenMathEncoding
++ Author: Vilya Harvey
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \spadtype{OpenMathEncoding} is the set of valid OpenMath encodings.

OpenMathEncoding(): SetCategory with
  OMencodingUnknown : () -> %
  ++ OMencodingUnknown() is the constant for unknown encoding types. If this
  ++ is used on an input device, the encoding will be autodetected.
  ++ It is invalid to use it on an output device.
  OMencodingXML     : () -> %
  ++ OMencodingXML() is the constant for the OpenMath XML encoding.
  OMencodingSGML    : () -> %
  ++ OMencodingSGML() is the constant for the deprecated OpenMath SGML encoding.
  OMencodingBinary  : () -> %
  ++ OMencodingBinary() is the constant for the OpenMath binary encoding.
 == add
  Rep := SingleInteger

  =(u,v) == (u=v)$Rep

  import Rep

  coerce(u) ==
    u::Rep = 0$Rep => "Unknown"::OutputForm
    u::Rep = 1$Rep => "Binary"::OutputForm
    u::Rep = 2::Rep => "XML"::OutputForm
    u::Rep = 3::Rep => "SGML"::OutputForm
    error "Bogus OpenMath Encoding Type"

  OMencodingUnknown(): % == 0::Rep
  OMencodingBinary(): % == 1::Rep
  OMencodingXML(): % == 2::Rep
  OMencodingSGML(): % == 3::Rep
```

———-

— **OMENC.dotabb** —

```
"OMENC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OMENC"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"OMENC" -> "BASTYPE"
"OMENC" -> "KOERCE"
```

———-

16.8 domain OMERR OpenMathError

— **OpenMathError.input** —

```
)set break resume
)sys rm -f OpenMathError.output
)spool OpenMathError.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OpenMathError
--R
--R OpenMathError  is a domain constructor
--R Abbreviation for OpenMathError is OMERR
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OMERR
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R errorInfo : % -> List(Symbol)        hash : % -> SingleInteger
--R latex : % -> String                  ?~=? : (%,%) -> Boolean
--R errorKind : % -> OpenMathErrorKind
--R omError : (OpenMathErrorKind,List(Symbol)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **OpenMathError.help** —

```
=============================================================
OpenMathError examples
=============================================================

See Also:
o )show OpenMathError
```

———-

16.8.1 OpenMathError (OMERR)



See

⇒ “OpenMathErrorKind” (OMERRK) 16.9.1 on page 1761

Exports:

coerce	errorInfo	errorKind	hash	latex
omError	?=?	? =?		

— domain OMERR OpenMathError —

```
)abbrev domain OMERR OpenMathError
++ Author: Vilya Harvey
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \spadtype{OpenMathError} is the domain of OpenMath errors.

OpenMathError() : SetCategory with
  errorKind : % -> OpenMathErrorKind
  ++ errorKind(u) returns the type of error which u represents.
```

```
  errorInfo : % -> List Symbol
  ++ errorInfo(u) returns information about the error u.
  omError   : (OpenMathErrorKind, List Symbol) -> %
  ++ omError(k,l) creates an instance of OpenMathError.
 == add
  Rep := Record(err:OpenMathErrorKind, info:List Symbol)

  import List String

  coerce(e:%):OutputForm ==
    OMParseError? e.err => message "Error parsing OpenMath object"
    infoSize := #(e.info)
    OMUnknownCD? e.err =>
--      not one? infoSize => error "Malformed info list in OMUnknownCD"
      not (infoSize = 1) => error "Malformed info list in OMUnknownCD"
      message concat("Cannot handle CD ",string first e.info)
    OMUnknownSymbol? e.err =>
      not 2=infoSize => error "Malformed info list in OMUnknownSymbol"
      message concat ["Cannot handle Symbol ",
                      string e.info.2, " from CD ", string e.info.1]
    OMReadError? e.err =>
      message "OpenMath read error"
    error "Malformed OpenMath Error"

  omError(e:OpenMathErrorKind,i:List Symbol):% == [e,i]$Rep

  errorKind(e:%):OpenMathErrorKind == e.err
  errorInfo(e:%):List Symbol == e.info
```

———-

— OMERR.dotabb —

```
"OMERR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OMERR"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"OMERR" -> "ALIST"
```

———-

16.9 domain OMERRK OpenMathErrorKind

— OpenMathErrorKind.input —

```
)set break resume
```

```
)sys rm -f OpenMathErrorKind.output
)spool OpenMathErrorKind.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OpenMathErrorKind
--R OpenMathErrorKind  is a domain constructor
--R Abbreviation for OpenMathErrorKind is OMERRK
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OMERRK
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                OMParseError? : % -> Boolean
--R OMReadError? : % -> Boolean           OMUnknownCD? : % -> Boolean
--R OMUnknownSymbol? : % -> Boolean       coerce : Symbol -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— OpenMathErrorKind.help —

```
=====================================================================
OpenMathErrorKind examples
=====================================================================

See Also:
o )show OpenMathErrorKind
```

———-

16.9.1 OpenMathErrorKind (OMERRK)



See

⇒ "OpenMathError" (OMERR) 16.8.1 on page 1758

Exports:
OMParseError? OMReadError? OMUnknownCD? OMUnknownSymbol? coerce hash latex ?=? ?~

— domain OMERRK OpenMathErrorKind —

```
)abbrev domain OMERRK OpenMathErrorKind
++ Author: Vilya Harvey
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \spadtype{OpenMathErrorKind} represents different kinds
++ of OpenMath errors: specifically parse errors, unknown CD or symbol
++ errors, and read errors.

OpenMathErrorKind() : SetCategory with
  coerce           : Symbol -> %
  ++ coerce(u) creates an OpenMath error object of an appropriate type if
  ++ \axiom{u} is one of \axiom{OMParseError}, \axiom{OMReadError},
  ++ \axiom{OMUnknownCD} or \axiom{OMUnknownSymbol}, otherwise it
  ++ raises a runtime error.
  OMParseError?    : % -> Boolean
  ++ OMParseError?(u) tests whether u is an OpenMath parsing error.
  OMUnknownCD?     : % -> Boolean
  ++ OMUnknownCD?(u) tests whether u is an OpenMath unknown CD error.
  OMUnknownSymbol? : % -> Boolean
  ++ OMUnknownSymbol?(u) tests whether u is an OpenMath unknown symbol error.
```

```
  OMReadError?     : % -> Boolean
  ++ OMReadError?(u) tests whether u is an OpenMath read error.
 == add
  Rep := Union(parseError:"OMParseError", unknownCD:"OMUnknownCD",
               unknownSymbol:"OMUnknownSymbol",readError:"OMReadError")

  OMParseError?(u) == (u case parseError)$Rep
  OMUnknownCD?(u) == (u case unknownCD)$Rep
  OMUnknownSymbol?(u) == (u case unknownSymbol)$Rep
  OMReadError?(u) == (u case readError)$Rep

  coerce(s:Symbol):% ==
    s = OMParseError    => ["OMParseError"]$Rep
    s = OMUnknownCD     => ["OMUnknownCD"]$Rep
    s = OMUnknownSymbol => ["OMUnknownSymbol"]$Rep
    s = OMReadError     => ["OMReadError"]$Rep
    error concat(string s, " is not a valid OpenMathErrorKind.")

  a = b == (a=b)$Rep

  coerce(e:%):OutputForm == coerce(e)$Rep
```

———-

— OMERRK.dotabb —

```
"OMERRK" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OMERRK"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"OMERRK" -> "ALIST"
```

———-

16.10 domain OP Operator

— Operator.input —

```
)set break resume
)sys rm -f Operator.output
)spool Operator.output
)set message test on
)set message auto off
)clear all
--S 1 of 21
R := SQMATRIX(2, INT)
```

```
--R
--R
--R   (1)  SquareMatrix(2,Integer)
--R                                                                Type: Domain
--E 1

--S 2 of 21
t := operator("tilde") :: OP(R)
--R
--R
--R   (2)  tilde
--R                                      Type: Operator(SquareMatrix(2,Integer))
--E 2

--S 3 of 21
)set expose add constructor Operator
--R
--I   Operator is now explicitly exposed in frame frame0
--E 3

--S 4 of 21
evaluate(t, m +-> transpose m)
--R
--R
--R   (3)  tilde
--R                                      Type: Operator(SquareMatrix(2,Integer))
--E 4

--S 5 of 21
s : R := matrix [ [0, 1], [1, 0] ]
--R
--R
--R        +0  1+
--R   (4)  |    |
--R        +1  0+
--R                                            Type: SquareMatrix(2,Integer)
--E 5

--S 6 of 21
rho := t * s
--R
--R
--R             +0  1+
--R   (5)  tilde|    |
--R             +1  0+
--R                                      Type: Operator(SquareMatrix(2,Integer))
--E 6

--S 7 of 21
z := rho**4 - 1
```

```
--R
--R
--R                    +0  1+     +0  1+     +0  1+     +0  1+
--R   (6)  - 1 + tilde|    |tilde|    |tilde|    |tilde|    |
--R                    +1  0+     +1  0+     +1  0+     +1  0+
--R                                        Type: Operator(SquareMatrix(2,Integer))
--E 7

--S 8 of 21
m:R := matrix [ [1, 2], [3, 4] ]
--R
--R
--R         +1  2+
--R   (7)  |    |
--R         +3  4+
--R                                              Type: SquareMatrix(2,Integer)
--E 8

--S 9 of 21
z m
--R
--R
--R         +0  0+
--R   (8)  |    |
--R         +0  0+
--R                                              Type: SquareMatrix(2,Integer)
--E 9

--S 10 of 21
rho m
--R
--R
--R         +3  1+
--R   (9)  |    |
--R         +4  2+
--R                                              Type: SquareMatrix(2,Integer)
--E 10

--S 11 of 21
rho rho m
--R
--R
--R          +4  3+
--R   (10)  |    |
--R         +2  1+
--R                                              Type: SquareMatrix(2,Integer)
--E 11

--S 12 of 21
(rho^3) m
```

```
--R
--R
--R         +2  4+
--R   (11)  |    |
--R         +1  3+
--R                                                Type: SquareMatrix(2,Integer)
--E 12

--S 13 of 21
b := t * s - s * t
--R
--R
--R           +0  1+             +0  1+
--R   (12)  - |    |tilde + tilde|    |
--R           +1  0+             +1  0+
--R                                    Type: Operator(SquareMatrix(2,Integer))
--E 13

--S 14 of 21
b m
--R
--R
--R         +1  - 3+
--R   (13)  |      |
--R         +3  - 1+
--R                                                Type: SquareMatrix(2,Integer)
--E 14

--S 15 of 21
L n ==
  n = 0 => 1
  n = 1 => x
  (2*n-1)/n * x * L(n-1) - (n-1)/n * L(n-2)
--R
--R                                                                    Type: Void
--E 15

--S 16 of 21
dx := operator("D") :: OP(POLY FRAC INT)
--R
--R
--R   (15)  D
--R                                 Type: Operator(Polynomial(Fraction(Integer)))
--E 16

--S 17 of 21
evaluate(dx, p +-> D(p, 'x))
--R
--R
--R   (16)  D
```

```
--R                                Type: Operator(Polynomial(Fraction(Integer)))
--E 17

--S 18 of 21
E n == (1 - x**2) * dx**2 - 2 * x * dx + n*(n+1)
--R
--R                                                                  Type: Void
--E 18

--S 19 of 21
L 15
--R
--R   Compiling function L with type Integer -> Polynomial(Fraction(
--R      Integer))
--R   Compiling function L as a recurrence relation.
--R
--R   (18)
--R     9694845  15   35102025  13   50702925  11   37182145  9   14549535  7
--R     ------- x   - -------- x   + -------- x   - -------- x  + -------- x
--R       2048          2048           2048           2048          2048
--R   +
--R       2909907  5   255255  3   6435
--R     - ------- x  + ------ x  - ---- x
--R         2048        2048       2048
--R                                          Type: Polynomial(Fraction(Integer))
--E 19

--S 20 of 21
E 15
--R
--R   Compiling function E with type PositiveInteger -> Operator(
--R      Polynomial(Fraction(Integer)))
--R
--R                         2      2
--R   (19)  240 - 2x D - (x  - 1)D
--R                                Type: Operator(Polynomial(Fraction(Integer)))
--E 20

--S 21 of 21
(E 15)(L 15)
--R
--R
--R   (20)  0
--R                                          Type: Polynomial(Fraction(Integer))
--E 21
)spool
)lisp (bye)
```

— Operator.help —

```
=====================================================================
Operator examples
=====================================================================

Given any ring R, the ring of the Integer-linear operators over R is
called Operator(R).  To create an operator over R, first create a
basic operator using the operation operator, and then convert it to
Operator(R) for the R you want.

We choose R to be the two by two matrices over the integers.

  R := SQMATRIX(2, INT)
    SquareMatrix(2,Integer)
                              Type: Domain

Create the operator tilde on R.

  t := operator("tilde") :: OP(R)
    tilde
                              Type: Operator SquareMatrix(2,Integer)

Since Operator is unexposed we must either package-call operations
from it, or expose it explicitly.  For convenience we will do the latter.

Expose Operator.

  )set expose add constructor Operator

To attach an evaluation function (from R to R) to an operator over R,
use evaluate(op, f) where op is an operator over R and f is a function
R -> R.  This needs to be done only once when the operator is defined.
Note that f must be Integer-linear (that is, f(ax+y) = a f(x) + f(y)
for any integer a, and any x and y in R).

We now attach the transpose map to the above operator t.

  evaluate(t, m +-> transpose m)
    tilde
                         Type: Operator SquareMatrix(2,Integer)

Operators can be manipulated formally as in any ring: + is the
pointwise addition and * is composition.  Any element x of R can be
converted to an operator op(x) over R, and the evaluation function of
op(x) is left-multiplication by x.

Multiplying on the left by this matrix swaps the two rows.
```

```
  s : R := matrix [ [0, 1], [1, 0] ]
        +0  1+
        |    |
        +1  0+
                        Type: SquareMatrix(2,Integer)
```

Can you guess what is the action of the following operator?

```
  rho := t * s
             +0  1+
        tilde|    |
             +1  0+
                        Type: Operator SquareMatrix(2,Integer)
```

Hint: applying rho four times gives the identity, so rho^4-1 should return 0 when applied to any two by two matrix.

```
  z := rho**4 - 1
                  +0  1+     +0  1+     +0  1+     +0  1+
        - 1 + tilde|    |tilde|    |tilde|    |tilde|    |
                  +1  0+     +1  0+     +1  0+     +1  0+
                      Type: Operator SquareMatrix(2,Integer)
```

Now check with this matrix.

```
  m:R := matrix [ [1, 2], [3, 4] ]
        +1  2+
        |    |
        +3  4+
                        Type: SquareMatrix(2,Integer)

  z m
        +0  0+
        |    |
        +0  0+
                        Type: SquareMatrix(2,Integer)
```

As you have probably guessed by now, rho acts on matrices by rotating the elements clockwise.

```
  rho m
        +3  1+
        |    |
        +4  2+
                        Type: SquareMatrix(2,Integer)

  rho rho m
         +4  3+
         |    |
         +2  1+
```

```
                    Type: SquareMatrix(2,Integer)
```

```
  (rho^3) m
         +2  4+
         |    |
         +1  3+
                    Type: SquareMatrix(2,Integer)
```

Do the swapping of rows and transposition commute? We can check by computing their bracket.

```
  b := t * s - s * t
           +0  1+             +0  1+
         - |    |tilde + tilde|    |
           +1  0+             +1  0+
                    Type: Operator SquareMatrix(2,Integer)
```

Now apply it to m.

```
  b m
         +1  - 3+
         |      |
         +3  - 1+
                    Type: SquareMatrix(2,Integer)
```

Next we demonstrate how to define a differential operator on a polynomial ring.

This is the recursive definition of the n-th Legendre polynomial.

```
  L n ==
    n = 0 => 1
    n = 1 => x
    (2*n-1)/n * x * L(n-1) - (n-1)/n * L(n-2)
                     Type: Void
```

Create the differential operator d/dx on polynomials in x over the rational numbers.

```
  dx := operator("D") :: OP(POLY FRAC INT)
     D
                     Type: Operator Polynomial Fraction Integer
```

Now attach the map to it.

```
  evaluate(dx, p +-> D(p, 'x))
    D
                     Type: Operator Polynomial Fraction Integer
```

This is the differential equation satisfied by the n-th Legendre polynomial.

```
  E n == (1 - x**2) * dx**2 - 2 * x * dx + n*(n+1)
                        Type: Void
```

Now we verify this for n = 15. Here is the polynomial.

```
  L 15
     9694845  15   35102025  13   50702925  11   37182145  9   14549535  7
     ------- x   - -------- x   + -------- x   - -------- x  + -------- x
       2048          2048           2048           2048          2048
   +
       2909907  5   255255  3   6435
     - ------- x  + ------ x  - ---- x
         2048        2048       2048
                        Type: Polynomial Fraction Integer
```

Here is the operator.


```
  E 15
    240 - 2x D - (x  - 1)D
                        Type: Operator Polynomial Fraction Integer
```

Here is the evaluation.

```
  (E 15)(L 15)
    0
                        Type: Polynomial Fraction Integer
```

See Also:
o)show Operator

16.10.1 Operator (OP)



See

⇒ "ModuleOperator" (MODOP) 14.12.1 on page 1615

Exports:

0	1	adjoint	characteristic	charthRoot
coerce	conjug	evaluate	evaluateInverse	makeop
hash	latex	one?	opeval	recip
retract	retractIfCan	sample	subtractIfCan	zero?
?~=?	?*?	?**?	?^?	?.?
?+?	?-?	-?	?=?	

— **domain OP Operator** —

```
)abbrev domain OP Operator
++ Author: Manuel Bronstein
++ Date Created: 15 May 1990
++ Date Last Updated: 12 February 1993
++ Description:
++ Algebra of ADDITIVE operators over a ring.

Operator(R: Ring) == ModuleOperator(R,R)
```

———-

— **OP.dotabb** —

```
"OP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OP"]
"ALGEBRA" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ALGEBRA"]
"OP" -> "ALGEBRA"
```

———-

16.11 domain OMLO OppositeMonogenicLinearOperator

— **OppositeMonogenicLinearOperator.input** —

```
)set break resume
)sys rm -f OppositeMonogenicLinearOperator.output
)spool OppositeMonogenicLinearOperator.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show OppositeMonogenicLinearOperator
--R
--R OppositeMonogenicLinearOperator(P: MonogenicLinearOperator(R),R: Ring)  is a domain construc
--R Abbreviation for OppositeMonogenicLinearOperator is OMLO
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OMLO
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : % -> % if P has DIFRING           1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> R
--R one? : % -> Boolean                   op : P -> %
--R po : % -> P                           recip : % -> Union(%,"failed")
--R reductum : % -> %                     sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R D : (%,NonNegativeInteger) -> % if P has DIFRING
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : R -> % if R has COMRING
--R differentiate : % -> % if P has DIFRING
--R differentiate : (%,NonNegativeInteger) -> % if P has DIFRING
--R minimumDegree : % -> NonNegativeInteger
--R monomial : (R,NonNegativeInteger) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— OppositeMonogenicLinearOperator.help —

```
====================================================================
OppositeMonogenicLinearOperator examples
====================================================================
```

```
See Also:
o )show OppositeMonogenicLinearOperator
```

———-

16.11.1 OppositeMonogenicLinearOperator (OMLO)



See

⇒ “OrdinaryDifferentialRing” (ODR) 16.18.1 on page 1824
⇒ “DirectProductModule” (DPMO) 5.11.1 on page 544
⇒ “DirectProductMatrixModule” (DPMM) 5.10.1 on page 540

Exports:

0	1	characteristic	coefficient	coerce
D	degree	differentiate	hash	latex
leadingCoefficient	minimumDegree	monomial	one?	op
po	recip	reductum	sample	subtractIfCan
zero?	?^?	?~=?	?*?	?**?
?+?	?-?	-?	?=?	

— domain OMLO OppositeMonogenicLinearOperator —

```
)abbrev domain OMLO OppositeMonogenicLinearOperator
++ Author: Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: May 30, 1991
++ Basic Operations:
++ Related Domains: MonogenicLinearOperator
++ Also See:
++ AMS Classifications:
++ Keywords: opposite ring
++ Examples:
++ References:
++ Description:
```

```
++ This constructor creates the \spadtype{MonogenicLinearOperator} domain
++ which is ‘‘opposite’’ in the ring sense to P.
++ That is, as sets \spad{P = $} but \spad{a * b} in \spad{$} is equal to
++ \spad{b * a} in P.

OppositeMonogenicLinearOperator(P, R): OPRcat == OPRdef where
   P: MonogenicLinearOperator(R)
   R: Ring

   OPRcat == MonogenicLinearOperator(R) with
        if P has DifferentialRing then DifferentialRing
        op: P -> $  ++ op(p) creates a value in $ equal to p in P.
        po: $ -> P  ++ po(q) creates a value in P equal to q in $.

   OPRdef  == P add
        Rep := P
        x, y: $
        a: P
        op a == a: $
        po x == x: P
        x*y == (y:P) *$P (x:P)
        coerce(x): OutputForm == prefix(op::OutputForm, [coerce(x:P)$P])
```

———-

— OMLO.dotabb —

```
"OMLO" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OMLO"]
"MLO" [color="#4488FF",href="bookvol10.2.pdf#nameddest=MLO"]
"OMLO" -> "MLO"
```

———-

16.12 domain ORDCOMP OrderedCompletion

— OrderedCompletion.input —

```
)set break resume
)sys rm -f OrderedCompletion.output
)spool OrderedCompletion.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show OrderedCompletion
--R
--R OrderedCompletion(R: SetCategory)  is a domain constructor
--R Abbreviation for OrderedCompletion is ORDCOMP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ORDCOMP
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if R has ABELGRP          ?=? : (%,%) -> Boolean
--R 1 : () -> % if R has ORDRING          0 : () -> % if R has ABELGRP
--R coerce : R -> %                       coerce : % -> OutputForm
--R finite? : % -> Boolean                hash : % -> SingleInteger
--R infinite? : % -> Boolean              latex : % -> String
--R minusInfinity : () -> %               plusInfinity : () -> %
--R retract : % -> R                      whatInfinity : % -> SingleInteger
--R ?~=? : (%,%) -> Boolean
--R ?*? : (PositiveInteger,%) -> % if R has ABELGRP
--R ?*? : (NonNegativeInteger,%) -> % if R has ABELGRP
--R ?*? : (Integer,%) -> % if R has ABELGRP
--R ?*? : (%,%) -> % if R has ORDRING
--R ?**? : (%,NonNegativeInteger) -> % if R has ORDRING
--R ?**? : (%,PositiveInteger) -> % if R has ORDRING
--R ?+? : (%,%) -> % if R has ABELGRP
--R ?-? : (%,%) -> % if R has ABELGRP
--R ?<? : (%,%) -> Boolean if R has ORDRING
--R ?<=? : (%,%) -> Boolean if R has ORDRING
--R ?>? : (%,%) -> Boolean if R has ORDRING
--R ?>=? : (%,%) -> Boolean if R has ORDRING
--R ?^? : (%,NonNegativeInteger) -> % if R has ORDRING
--R ?^? : (%,PositiveInteger) -> % if R has ORDRING
--R abs : % -> % if R has ORDRING
--R characteristic : () -> NonNegativeInteger if R has ORDRING
--R coerce : Integer -> % if R has ORDRING or R has RETRACT(INT)
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT))
--R max : (%,%) -> % if R has ORDRING
--R min : (%,%) -> % if R has ORDRING
--R negative? : % -> Boolean if R has ORDRING
--R one? : % -> Boolean if R has ORDRING
--R positive? : % -> Boolean if R has ORDRING
--R rational : % -> Fraction(Integer) if R has INS
--R rational? : % -> Boolean if R has INS
--R rationalIfCan : % -> Union(Fraction(Integer),"failed") if R has INS
--R recip : % -> Union(%,"failed") if R has ORDRING
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R sample : () -> % if R has ABELGRP
```

```
--R sign : % -> Integer if R has ORDRING
--R subtractIfCan : (%,%) -> Union(%,"failed") if R has ABELGRP
--R zero? : % -> Boolean if R has ABELGRP
--R
--E 1

)spool
)lisp (bye)
```

———-


— OrderedCompletion.help —

```
=====================================================================
OrderedCompletion examples
=====================================================================

See Also:
o )show OrderedCompletion
```

———-

16.12.1 OrderedCompletion (ORDCOMP)



See

⇒ “OnePointCompletion” (ONECOMP) 16.4.1 on page 1743

Exports:

0	1	abs	characteristic	coerce
finite?	hash	infinite?	latex	max
min	minusInfinity	negative?	one?	plusInfinity
positive?	rational	rational?	rationalIfCan	recip
retract	retractIfCan	sample	sign	subtractIfCan
whatInfinity	zero?	?~=?	?*?	?**?
?+?	?-?	?<?	?<=?	?>?
?>=?	?^?	-?	?=?	

— domain ORDCOMP OrderedCompletion —

```
)abbrev domain ORDCOMP OrderedCompletion
++ Author: Manuel Bronstein
++ Date Created: 4 Oct 1989
++ Date Last Updated: 1 Nov 1989
++ Description:
++ Completion with + and - infinity.
++ Adjunction of two real infinites quantities to a set.

OrderedCompletion(R:SetCategory): Exports == Implementation where
  B ==> Boolean

  Exports ==> Join(SetCategory, FullyRetractableTo R) with
    plusInfinity : () -> %        ++ plusInfinity() returns +infinity.
    minusInfinity: () -> %        ++ minusInfinity() returns  -infinity.
    finite?      : %  -> B
      ++ finite?(x) tests if x is finite.
    infinite?    : %  -> B
      ++ infinite?(x) tests if x is +infinity or -infinity,
    whatInfinity : %  -> SingleInteger
      ++ whatInfinity(x) returns 0 if x is finite,
      ++ 1 if x is +infinity, and -1 if x is -infinity.
    if R has AbelianGroup then AbelianGroup
    if R has OrderedRing then OrderedRing
    if R has IntegerNumberSystem then
      rational?: % -> Boolean
        ++ rational?(x) tests if x is a finite rational number.
      rational : % -> Fraction Integer
        ++ rational(x) returns x as a finite rational number.
        ++ Error: if x cannot be so converted.
      rationalIfCan: % -> Union(Fraction Integer, "failed")
        ++ rationalIfCan(x) returns x as a finite rational number if
        ++ it is one and "failed" otherwise.

  Implementation ==> add
    Rep := Union(fin:R, inf:B)  -- true = +infinity, false = -infinity

    coerce(r:R):%          == [r]
    retract(x:%):R         == (x case fin => x.fin; error "Not finite")
```

```
finite? x              == x case fin
infinite? x            == x case inf
plusInfinity()         == [true]
minusInfinity()        == [false]

retractIfCan(x:%):Union(R, "failed") ==
  x case fin => x.fin
  "failed"

coerce(x:%):OutputForm ==
  x case fin => (x.fin)::OutputForm
  e := "infinity"::OutputForm
  x.inf => empty() + e
  - e

whatInfinity x ==
  x case fin => 0
  x.inf => 1
  -1

x = y ==
  x case inf =>
    y case inf => not xor(x.inf, y.inf)
    false
  y case inf => false
  x.fin = y.fin

if R has AbelianGroup then
  0 == [0$R]

  n:Integer * x:% ==
    x case inf =>
      n > 0 => x
      n < 0 => [not(x.inf)]
      error "Undefined product"
    [n * x.fin]

  - x ==
    x case inf => [not(x.inf)]
    [- (x.fin)]

  x + y ==
    x case inf =>
      y case fin => x
      xor(x.inf, y.inf) => error "Undefined sum"
      x
    y case inf => y
    [x.fin + y.fin]

if R has OrderedRing then
```

```
      fininf: (B, R) -> %

      1               == [1$R]
      characteristic() == characteristic()$R

      fininf(b, r) ==
        r > 0 => [b]
        r < 0 => [not b]
        error "Undefined product"

      x:% * y:% ==
        x case inf =>
          y case inf =>
            xor(x.inf, y.inf) => minusInfinity()
            plusInfinity()
          fininf(x.inf, y.fin)
        y case inf => fininf(y.inf, x.fin)
        [x.fin * y.fin]

      recip x ==
        x case inf => 0
        (u := recip(x.fin)) case "failed" => "failed"
        [u::R]

      x < y ==
        x case inf =>
          y case inf =>
            xor(x.inf, y.inf) => y.inf
            false
          not(x.inf)
        y case inf => y.inf
        x.fin < y.fin

    if R has IntegerNumberSystem then
      rational? x == finite? x
      rational  x == rational(retract(x)@R)

      rationalIfCan x ==
        (r:= retractIfCan(x)@Union(R,"failed")) case "failed" =>"failed"
        rational(r::R)
```

———-

— ORDCOMP.dotabb —

```
"ORDCOMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ORDCOMP"]
"FRETRCT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FRETRCT"]
"ORDCOMP" -> "FRETRCT"
```

16.13 domain ODP OrderedDirectProduct

— OrderedDirectProduct.input —

```
)set break resume
)sys rm -f OrderedDirectProduct.output
)spool OrderedDirectProduct.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OrderedDirectProduct
--R
--R OrderedDirectProduct(dim: NonNegativeInteger,S: OrderedAbelianMonoidSup,f: ((Vector(S),Vecto
--R Abbreviation for OrderedDirectProduct is ODP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ODP
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if S has RING             1 : () -> % if S has MONOID
--R 0 : () -> % if S has CABMON           coerce : % -> Vector(S)
--R copy : % -> %                         directProduct : Vector(S) -> %
--R ?.? : (%,Integer) -> S                elt : (%,Integer,S) -> S
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(S)                eq? : (%,%) -> Boolean
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
--R map : ((S -> S),%) -> %               qelt : (%,Integer) -> S
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (PositiveInteger,%) -> % if S has ABELSG
--R ?*? : (NonNegativeInteger,%) -> % if S has CABMON
--R ?*? : (S,%) -> % if S has RING
--R ?*? : (%,S) -> % if S has RING
--R ?*? : (%,%) -> % if S has MONOID
--R ?*? : (Integer,%) -> % if S has RING
--R ?**? : (%,PositiveInteger) -> % if S has MONOID
--R ?**? : (%,NonNegativeInteger) -> % if S has MONOID
--R ?+? : (%,%) -> % if S has ABELSG
--R ?-? : (%,%) -> % if S has RING
--R ?/? : (%,S) -> % if S has FIELD
--R ?<? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?<=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
```

```
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R D : (%,(S -> S)) -> % if S has RING
--R D : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R D : % -> % if S has DIFRING and S has RING
--R ?^? : (%,PositiveInteger) -> % if S has MONOID
--R ?^? : (%,NonNegativeInteger) -> % if S has MONOID
--R abs : % -> % if S has ORDRING
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R characteristic : () -> NonNegativeInteger if S has RING
--R coerce : S -> % if S has SETCAT
--R coerce : Fraction(Integer) -> % if S has RETRACT(FRAC(INT)) and S has SETCAT
--R coerce : Integer -> % if S has RETRACT(INT) and S has SETCAT or S has RING
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R differentiate : (%,(S -> S)) -> % if S has RING
--R differentiate : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R differentiate : % -> % if S has DIFRING and S has RING
--R dimension : () -> CardinalNumber if S has FIELD
--R dot : (%,%) -> S if S has RING
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R first : % -> S if Integer has ORDSET
--R hash : % -> SingleInteger if S has SETCAT
--R index : PositiveInteger -> % if S has FINITE
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R lookup : % -> PositiveInteger if S has FINITE
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has OAMONS or S has ORDRING
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
```

```
--R min : (%,%) -> % if S has OAMONS or S has ORDRING
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R negative? : % -> Boolean if S has ORDRING
--R one? : % -> Boolean if S has MONOID
--R parts : % -> List(S) if $ has finiteAggregate
--R positive? : % -> Boolean if S has ORDRING
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R random : () -> % if S has FINITE
--R recip : % -> Union(%,"failed") if S has MONOID
--R reducedSystem : Matrix(%) -> Matrix(S) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(S),vec: Vector(S)) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if S has LINEXP(INT) and S has RING
--R retract : % -> S if S has SETCAT
--R retract : % -> Fraction(Integer) if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retract : % -> Integer if S has RETRACT(INT) and S has SETCAT
--R retractIfCan : % -> Union(S,"failed") if S has SETCAT
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if S has RETRACT(FRAC(INT)) and S has
--R retractIfCan : % -> Union(Integer,"failed") if S has RETRACT(INT) and S has SETCAT
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R sign : % -> Integer if S has ORDRING
--R size : () -> NonNegativeInteger if S has FINITE
--R size? : (%,NonNegativeInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed") if S has CABMON
--R sup : (%,%) -> % if S has OAMONS
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R unitVector : PositiveInteger -> % if S has RING
--R zero? : % -> Boolean if S has CABMON
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— OrderedDirectProduct.help —

```
=====================================================================
OrderedDirectProduct examples
=====================================================================

See Also:
o )show OrderedDirectProduct
```

———-

16.13.1 OrderedDirectProduct (ODP)



See

⇒ "HomogeneousDirectProduct" (HDP) 9.9.1 on page 1142
⇒ "SplitHomogeneousDirectProduct" (SHDP) 20.23.1 on page 2476

Exports:

0	1	abs	any?	characteristic
coerce	copy	count	D	differentiate
dimension	directProduct	dot	elt	empty
empty?	entries	entry?	eq?	eval
every?	fill!	first	hash	index
index?	indices	latex	less?	lookup
map	map!	max	maxIndex	member?
members	min	minIndex	more?	negative?
one?	parts	positive?	qelt	qsetelt!
random	recip	reducedSystem	retract	retractIfCan
sample	setelt	sign	size	size?
subtractIfCan	sup	swap!	unitVector	zero?
#?	?*?	?**?	?+?	?-?
?/?	?<?	?<=?	?=?	?>?
?>=?	?^?	?~=?	-?	?.?

— domain ODP OrderedDirectProduct —

```
)abbrev domain ODP OrderedDirectProduct
-- all direct product category domains must be compiled
-- without subsumption, set SourceLevelSubset to EQUAL
--)bo $noSubsumption := true

++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors: Vector, DirectProduct
++ Also See: HomogeneousDirectProduct, SplitHomogeneousDirectProduct
++ AMS Classifications:
```

```
++ Keywords:
++ References:
++ Description:
++ This type represents the finite direct or cartesian product of an
++ underlying ordered component type. The ordering on the type is determined
++ by its third argument which represents the less than function on
++ vectors. This type is a suitable third argument for
++ \spadtype{GeneralDistributedMultivariatePolynomial}.

OrderedDirectProduct(dim:NonNegativeInteger,
                     S:OrderedAbelianMonoidSup,
                      f:(Vector(S),Vector(S))->Boolean):T
                             == C where
   T == DirectProductCategory(dim,S)
   C == DirectProduct(dim,S) add
        Rep:=Vector(S)
        x:% < y:% == f(x::Rep,y::Rep)
```

———-

— ODP.dotabb —

```
"ODP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ODP"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"ODP" -> "DIRPCAT"
```

———-

16.14 domain OFMONOID OrderedFreeMonoid

— OrderedFreeMonoid.input —

```
)set break resume
)sys rm -f OrderedFreeMonoid.output
)spool OrderedFreeMonoid.output
)set message test on
)set message auto off
)clear all

--S 1 of 24
m1:=(x*y*y*z)$OFMONOID(Symbol)
--R
--R
--R           2
```

```
--R   (1)  x y z
--R                                                Type: OrderedFreeMonoid(Symbol)
--E 1

--S 2 of 24
m2:=(x*y)$OFMONOID(Symbol)
--R
--R
--R   (2)  x y
--R                                                Type: OrderedFreeMonoid(Symbol)
--E 2

--S 3 of 24
lquo(m1,m2)
--R
--R
--R   (3)  y z
--R                                    Type: Union(OrderedFreeMonoid(Symbol),...)
--E 3

--S 4 of 24
m3:=(y*y)$OFMONOID(Symbol)
--R
--R
--R         2
--R   (4)  y
--R                                                Type: OrderedFreeMonoid(Symbol)
--E 4

--S 5 of 24
divide(m1,m2)
--R
--R
--R   (5)  [lm= y z,rm= "failed"]
--IType: Union(Record(lm: Union(OrderedFreeMonoid(Symbol),"failed"),...
--E 5

--S 6 of 24
divide(m1,m3)
--R
--R
--R   (6)  [lm= "failed",rm= "failed"]
--IType: Union(Record(lm: Union(OrderedFreeMonoid(Symbol),"failed"),...
--E 6

--S 7 of 24
m4:=(y^3)$OFMONOID(Symbol)
--R
--R
--R         3
```

```
--R   (7)  y
--R                                                 Type: OrderedFreeMonoid(Symbol)
--E 7

--S 8 of 24
divide(m1,m4)
--R
--R
--R   (8)  [lm= "failed",rm= "failed"]
--IType: Union(Record(lm: Union(OrderedFreeMonoid(Symbol),"failed"),...
--E 8

)set function compile on


-- Build the non-commutative algebra h=k[x,y] and then make computations
-- in h using some predefined rules for x and y. For example, giving
--   x*y*x=y*x*y
--   x*x=a*x+b
--   y*y=a*y+b
-- where a dn b are generic elements of k.
-- Then reduce the polynomials in x and y according to the previous rules.
-- That is, given
--   (x+y)^2   ( = x^2+x*y+y*x+y^2)
-- should reduce to
--   a*(x+y)+2*b+x*y+y*x

-- Generic elements of k (OVAR is OrderedVariableList)

--S 9 of 24
C ==> OVAR [a,b]
--R
--R                                                                  Type: Void
--E 9

-- Commutative Field: k = Q[a,b]
-- Q = Fraction Integer
-- SMP = SparseMultivariatePolynomials

--S 10 of 24
K ==> SMP(FRAC INT,C)
--R
--R                                                                  Type: Void
--E 10

-- Non-commutative variables

--S 11 of 24
V ==> OVAR [x,y]
--R
```

```
--R                                                                    Type: Void
--E 11

-- Non-commuative algebra k=k[x,y]
-- XDPOLY XDistributedPolynomial

--S 12 of 24
H ==> XDPOLY(V,K)
--R
--R                                                                    Type: Void
--E 12

-- Free Monoid

--S 13 of 24
M ==> OFMONOID V
--R
--R                                                                    Type: Void
--E 13

-- Substitution rules are applied to words from the monoid over the
-- variables and retun polynomials

--S 14 of 24
subs(w:M):H ==
  -- x*y*x = y*x*y
  n1:=lquo(w,(x::V*y::V*x::V)$M)$M
  n1 case "failed" => monom(w,1)$H
      -- x*x = a*x+b
    n2:=lquo(w,(x::V^2)$M)$M
    n2 case "failed" => monom(w,1)$H
      -- y*y = a*y+b
      n3:lquo(w,(y::V^2)$M)$M
      n3 case "failed" => monom(w,1)$H
      monom(n3,1)$H * (a::K*y::V+b::K)$M * monom(n3,1)$H
    monom(n2,1)$H * (a::K*x::V+b::K)$H * monom(n2,1)$H
  monom(n1,1)$H * (y::V*x::V*y::V)$H * monom(n1,1)$H
--R
--R   Function declaration subs : OrderedFreeMonoid(OrderedVariableList([x
--R      ,y])) -> XDistributedPolynomial(OrderedVariableList([x,y]),
--R      SparseMultivariatePolynomial(Fraction(Integer),
--R      OrderedVariableList([a,b]))) has been added to workspace.
--R                                                                    Type: Void
--E 14

-- Apply rules to a term. Keep coefficients
--S 15 of 24
newterm(x:Record(k:M,c:K)):H == x.c*subs(x,k)
--R
--R   Function declaration newterm : Record(k: OrderedFreeMonoid(
```

```
--R      OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(
--R      Fraction(Integer),OrderedVariableList([a,b]))) ->
--R      XDistributedPolynomial(OrderedVariableList([x,y]),
--R      SparseMultivariatePolynomial(Fraction(Integer),
--R      OrderedVariableList([a,b]))) has been added to workspace.
--R                                                                  Type: Void
--E 15

-- Reconstruct the polynomial term by term

--S 16 of 24
newpoly(t:H):H == reduce(+,map(newterm,listOfTerms(t)))
--R
--R   Function declaration newpoly : XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b]))) -> XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b]))) has been added to
--R      workspace.
--R                                                                  Type: Void
--E 16

-- Example calcuations

--S 17 of 24
p1:(x::V+y::V)$H^2
--R
--R
--RDaly Bug
--R   Category, domain or package constructor ^ is not available.
--E 17

--S 18 of 24
newpoly(p1)
--R
--R   Compiling function newpoly with type XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b]))) -> XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b])))
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fract
--R                                  Variable(k)
--R
```

```
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--R   AXIOM will attempt to step through and interpret the code.
--R   Compiling function newterm with type Record(k: OrderedFreeMonoid(
--R      OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(
--R      Fraction(Integer),OrderedVariableList([a,b]))) ->
--R      XDistributedPolynomial(OrderedVariableList([x,y]),
--R      SparseMultivariatePolynomial(Fraction(Integer),
--R      OrderedVariableList([a,b])))
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R
--RDaly Bug
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fraction(Integer)
--R                                 Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--E 18

--S 19 of 24
p2:=(x::V+y::V)$H^3
--R
--R
--R          3    2               2      2            2     3
--R   (17)  y  + y x + y x y + y x  + x y  + x y x + x y + x
--IType: XDistributedPolynomial(OrderedVariableList([x,y]),...
--E 19

--S 20 of 24
pNew:=newpoly(p2)
--R
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fraction(Integer)
--R                                 Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--R   AXIOM will attempt to step through and interpret the code.
```

```
--R   Compiling function newterm with type Record(k: OrderedFreeMonoid
--R      OrderedVariableList [x,y],c: SparseMultivariatePolynomial(
--R      Fraction Integer,OrderedVariableList [a,b])) ->
--R      XDistributedPolynomial(OrderedVariableList [x,y],
--R      SparseMultivariatePolynomial(Fraction Integer,OrderedVariableList
--R      [a,b]))
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R
--RDaly Bug
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fract
--R                                 Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--E 20

-- But the rules should be applied more than once
--S 21 of 24
while pNew ~= p2 repeat
  p2 := pNew
  pNew := newpoly(p2)
--R
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fract
--R                                 Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--R   AXIOM will attempt to step through and interpret the code.
--R   Compiling function newterm with type Record(k: OrderedFreeMonoid(
--R      OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(
--R      Fraction(Integer),OrderedVariableList([a,b]))) ->
--R      XDistributedPolynomial(OrderedVariableList([x,y]),
--R      SparseMultivariatePolynomial(Fraction(Integer),
--R      OrderedVariableList([a,b])))
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
```

```
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R
--RDaly Bug
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fraction(Integer)
--R                                  Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--E 21

--S 22 of 24
pNew
--R
--R
--R   (18)  pNew
--R                                                        Type: Variable pNew
--E 22

--S 23 of 24
reduce(p:H):H ==
  p2 := newpoly(p)
  p3 := newpoly(p2)
  while p3 ~= p2 repeat
    p2 := p3
    p3 := newpoly(p2)
  p3
--R
--R   Function declaration reduce : XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b]))) -> XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b]))) has been added to
--R      workspace.
--R   Compiled code for newpoly has been cleared.
--R                                                                Type: Void
--E 23

--S 24 of 24
reduce(p2)
--R
--R   Compiling function newpoly with type XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b]))) -> XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b])))
--R   Compiling function reduce with type XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
```

```
--R      Integer),OrderedVariableList([a,b]))) -> XDistributedPolynomial(
--R      OrderedVariableList([x,y]),SparseMultivariatePolynomial(Fraction(
--R      Integer),OrderedVariableList([a,b])))
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fract
--R                                 Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--R   AXIOM will attempt to step through and interpret the code.
--R   Compiling function newterm with type Record(k: OrderedFreeMonoid(
--R      OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(
--R      Fraction(Integer),OrderedVariableList([a,b]))) ->
--R      XDistributedPolynomial(OrderedVariableList([x,y]),
--R      SparseMultivariatePolynomial(Fraction(Integer),
--R      OrderedVariableList([a,b])))
--R   There are no library operations named subs
--R      Use HyperDoc Browse or issue
--R                                )what op subs
--R      to learn if there is any operation containing " subs " in its
--R      name.
--R
--RDaly Bug
--R   Cannot find a definition or applicable library operation named subs
--R      with argument type(s)
--RRecord(k: OrderedFreeMonoid(OrderedVariableList([x,y])),c: SparseMultivariatePolynomial(Fract
--R                                 Variable(k)
--R
--R      Perhaps you should use "@" to indicate the required return type,
--R      or "$" to specify which version of the function you need.
--E 24

)spool
)lisp (bye)
```

———-

— OrderedFreeMonoid.help —

```
=====================================================================
OrderedFreeMonoid examples
=====================================================================
```

```
m1:=(x*y*y*z)$OFMONOID(Symbol)

m2:=(x*y)$OFMONOID(Symbol)

lquo(m1,m2)

m3:=(y*y)$OFMONOID(Symbol)

div(m1,m2)

div(m1,m3)

m4:=(y^3)$OFMONOID(Symbol)

div(m1,m4)

Build the non-commutative algebra h=k[x,y] and then make computations
in h using some predefined rules for x and y. For example, giving

   x*y*x=y*x*y
   x*x=a*x+b
   y*y=a*y+b

where a dn b are generic elements of k.

Then reduce the polynomials in x and y according to the previous rules.
That is, given

   (x+y)^2   ( = x^2+x*y+y*x+y^2)

should reduce to

   a*(x+y)+2*b+x*y+y*x

We can reduce the clutter of the work by defining macros for the types
of the domains we need to create. So first we create those macros.

We create generic elements of k. First we define a macro for the domain of
ordered variables (OVAR is OrderedVariableList)

  C ==> OVAR [a,b]

Next we define a macro for the commutative field domain k = Q[a,b]
where Q is Fraction(Integer) and SMP is SparseMultivariatePolynomials

  K ==> SMP(FRAC INT,C)

Now we need some non-commutative variables so we create a macro for that.

  V ==> OVAR [x,y]
```

```
And now we need to define the non-commuative algebra k=k[x,y].
We use the domain XDistributedPolynomial (XDPOLY) as a macro.

  H ==> XDPOLY(V,K)

The non-commutative variables are in an Ordered Free Monoid

  M ==> OFMONOID V

We have three rules to apply. So we create a function that examines one
term. Substitution rules are applied to words from the monoid over the
variables and retun polynomials. If any rule matches we construct the
substitution, create a new monomial term and return it.

  subs(w:M):H ==
    -- x*y*x = y*x*y
    n1:=lquo(w,(x::V*y::V*x::V)$M)$M
    n1 case "failed" => monom(w,1)$H
        -- x*x = a*x+b
      n2:=lquo(w,(x::V^2)$M)$M
      n2 case "failed" => monom(w,1)$H
        -- y*y = a*y+b
        n3:lquo(w,(y::V^2)$M)$M
        n3 case "failed" => monom(w,1)$H
        monom(n3,1)$H * (a::K*y::V+b::K)$M * monom(n3,1)$H
      monom(n2,1)$H * (a::K*x::V+b::K)$H * monom(n2,1)$H
    monom(n1,1)$H * (y::V*x::V*y::V)$H * monom(n1,1)$H

We apply these rules to a term, remembering the coefficient

  newterm(x:Record(k:M,c:K)):H == x.c*subs(x,k)


And now we create a function to reconstruct the polynomial term by term.

  newpoly(t:H):H == reduce(+,map(newterm,listOfTerms(t)))


For example,

  p1:(x::V+y::V)$H^2

  newpoly(p1)

  p2:=(x::V+y::V)$H^3

  pNew:=newpoly(p2)

But the rules should be applied more than once so we create a function
```

```
to iterate the rules until nothing changes.

  reduce(p:H):H ==
    p2 := newpoly(p)
    p3 := newpoly(p2)
    while p3 ~= p2 repeat
      p2 := p3
      p3 := newpoly(p2)
    p3


And we can see it work

  reduce(p2)

See Also:
o )show OrderedFreeMonoid
```

———-

16.14.1 OrderedFreeMonoid (OFMONOID)



Exports:

1	coerce	factors	first	hash
hclf	hcrf	latex	length	lexico
lquo	max	min	mirror	nthExpon
nthFactor	one?	overlap	recip	rest
retract	retractIfCan	rquo	sample	size
varList	?*?	?**?	?<?	?<=?
?=?	?>?	?>=?	?^?	?~=?
?div?				

— domain OFMONOID OrderedFreeMonoid —

```
)abbrev domain OFMONOID OrderedFreeMonoid
```

```
++ Author: Michel Petitot petitot@lifl.fr
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ The free monoid on a set \spad{S} is the monoid of finite products of
++ the form \spad{reduce(*,[si ** ni])} where the si's are in S, and the ni's
++ are non-negative integers. The multiplication is not commutative.
++ For two elements \spad{x} and \spad{y} the relation \spad{x < y}
++ holds if either \spad{length(x) < length(y)} holds or if these lengths
++ are equal and if \spad{x} is smaller than \spad{y} w.r.t. the
++ lexicographical ordering induced by \spad{S}.
++ This domain inherits implementation from \spadtype{FreeMonoid}.

OrderedFreeMonoid(S: OrderedSet): OFMcategory == OFMdefinition where
  NNI ==> NonNegativeInteger
  REC ==> Record(gen:S, exp:NNI)
  RESULT ==> Union(Record(lm:Union(%,"failed"),rm:Union(%,"failed")),"failed")

  OFMcategory == Join(OrderedMonoid, RetractableTo S) with
    "*":    (S, %) -> %
      ++ \spad{s*x} returns the product of \spad{x} by \spad{s} on the left.
      ++
      ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
      ++X x*m1
    "*":    (%, S) -> %
      ++ \spad{x*s} returns the product of \spad{x} by \spad{s} on the right.
      ++
      ++X m1:=(y**3)$OFMONOID(Symbol)
      ++X m1*x
    "**":   (S, NNI) -> %
      ++ \spad{s**n} returns the product of \spad{s} by itself \spad{n} times.
      ++
      ++X m1:=(y**3)$OFMONOID(Symbol)
    first: % -> S
      ++ \spad{first(x)} returns the first letter of \spad{x}.
      ++
      ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
      ++X first m1
    rest:  % -> %
      ++ \spad{rest(x)} returns \spad{x} except the first letter.
      ++
      ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
      ++X rest m1
```

```
mirror: % -> %
  ++ \spad{mirror(x)} returns the reversed word of \spad{x}.
  ++
  ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
  ++X mirror m1
lexico: (%,%) -> Boolean
  ++ \spad{lexico(x,y)} returns \spad{true}
  ++ iff \spad{x} is smaller than \spad{y}
  ++ w.r.t. the pure lexicographical ordering induced by \spad{S}.
  ++
  ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
  ++X m2:=(x*y)$OFMONOID(Symbol)
  ++X lexico(m1,m2)
  ++X lexico(m2,m1)
hclf:   (%, %) -> %
  ++ \spad{hclf(x, y)} returns the highest common left factor
  ++ of \spad{x} and \spad{y},
  ++ that is the largest \spad{d} such that \spad{x = d a}
  ++ and \spad{y = d b}.
  ++
  ++X m1:=(x*y*z)$OFMONOID(Symbol)
  ++X m2:=(x*y)$OFMONOID(Symbol)
  ++X hclf(m1,m2)
hcrf:   (%, %) -> %
  ++ \spad{hcrf(x, y)} returns the highest common right
  ++ factor of \spad{x} and \spad{y},
  ++ that is the largest \spad{d} such that \spad{x = a d}
  ++ and \spad{y = b d}.
  ++
  ++X m1:=(x*y*z)$OFMONOID(Symbol)
  ++X m2:=(y*z)$OFMONOID(Symbol)
  ++X hcrf(m1,m2)
lquo:   (%, %) -> Union(%, "failed")
  ++ \spad{lquo(x, y)} returns the exact left quotient of \spad{x}
  ++  by \spad{y} that is \spad{q} such that \spad{x = y * q},
  ++ "failed" if \spad{x} is not of the form \spad{y * q}.
  ++
  ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
  ++X m2:=(x*y)$OFMONOID(Symbol)
  ++X lquo(m1,m2)
rquo:   (%, %) -> Union(%, "failed")
  ++ \spad{rquo(x, y)} returns the exact right quotient of \spad{x}
  ++ by \spad{y} that is \spad{q} such that \spad{x = q * y},
  ++ "failed" if \spad{x} is not of the form \spad{q * y}.
  ++
  ++X m1:=(q*y^3)$OFMONOID(Symbol)
  ++X m2:=(y^2)$OFMONOID(Symbol)
  ++X lquo(m1,m2)
lquo:   (%, S) -> Union(%, "failed")
  ++ \spad{lquo(x, s)} returns the exact left quotient of \spad{x}
```

```
    ++ by \spad{s}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X lquo(m1,x)
  rquo:   (%, S) -> Union(%, "failed")
    ++ \spad{rquo(x, s)} returns the exact right quotient
    ++ of \spad{x} by \spad{s}.
    ++
    ++X m1:=(x*y)$OFMONOID(Symbol)
    ++X div(m1,y)
  divide: (%, %) -> RESULT
    ++ \spad{divide(x,y)} returns the left and right exact quotients of
    ++ \spad{x} by \spad{y}, that is \spad{[l,r]} such that \spad{x = l*y*r}.
    ++ "failed" is returned iff \spad{x} is not of the form \spad{l * y * r}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X m2:=(x*y)$OFMONOID(Symbol)
    ++X divide(m1,m2)
  overlap: (%, %) -> Record(lm: %, mm: %, rm: %)
    ++ \spad{overlap(x, y)} returns \spad{[l, m, r]} such that
    ++ \spad{x = l * m} and \spad{y = m * r} hold and such that
    ++ \spad{l} and \spad{r} have no overlap,
    ++ that is \spad{overlap(l, r) = [l, 1, r]}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X m2:=(x*y)$OFMONOID(Symbol)
    ++X overlap(m1,m2)
  size:   % -> NNI
    ++ \spad{size(x)} returns the number of monomials in \spad{x}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X size(m1,2)
  nthExpon:  (%, Integer) -> NNI
    ++ \spad{nthExpon(x, n)} returns the exponent of the
    ++ \spad{n-th} monomial of \spad{x}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X nthExpon(m1,2)
  nthFactor: (%, Integer) -> S
    ++ \spad{nthFactor(x, n)} returns the factor of the \spad{n-th}
    ++ monomial of \spad{x}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X nthFactor(m1,2)
  factors: % -> List REC
    ++ \spad{factors(a1\^e1,...,an\^en)} returns
    ++ \spad{[[a1, e1],...,[an, en]]}.
    ++
    ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
    ++X factors m1
```

```
    length: % -> NNI
      ++ \spad{length(x)} returns the length of \spad{x}.
      ++
      ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
      ++X length m1
    varList: % -> List S
      ++ \spad{varList(x)} returns the list of variables of \spad{x}.
      ++
      ++X m1:=(x*y*y*z)$OFMONOID(Symbol)
      ++X varList m1

  OFMdefinition == FreeMonoid(S) add
    Rep := ListMonoidOps(S, NNI, 1)

    -- definitions
    lquo(w:%, l:S) ==
      x: List REC := listOfMonoms(w)$Rep
      null x        => "failed"
      fx: REC := first x
      fx.gen ^= l  => "failed"
      fx.exp = 1   => makeMulti rest(x)
      makeMulti [[fx.gen, (fx.exp - 1)::NNI ]$REC, :rest x]

    rquo(w:%, l:S) ==
      u:% := reverse w
      (r := lquo (u,l)) case "failed" => "failed"
      reverse_! (r::%)

    divide(left:%,right:%) ==
      a:=lquo(left,right)
      b:=rquo(left,right)
      [a,b]

    length x == reduce("+" ,[f.exp for f in listOfMonoms x], 0)

    varList x ==
      le: List S := [t.gen for t in listOfMonoms x]
      sort_! removeDuplicates(le)

    first w ==
      x: List REC := listOfMonoms w
      null x => error "empty word !!!"
      x.first.gen

    rest w ==
      x: List REC := listOfMonoms w
      null x => error "empty word !!!"
      fx: REC := first x
      fx.exp = 1 => makeMulti rest x
      makeMulti [[fx.gen , (fx.exp - 1)::NNI ]$REC , :rest x]
```

```
    lexico(a,b) ==         --  ordre lexicographique
      la := listOfMonoms a
      lb := listOfMonoms b
      while (not null la) and (not null lb) repeat
        la.first.gen > lb.first.gen => return false
        la.first.gen < lb.first.gen => return true
        if la.first.exp = lb.first.exp then
          la:=rest la
          lb:=rest lb
        else if la.first.exp > lb.first.exp then
          la:=concat([la.first.gen,
                 (la.first.exp - lb.first.exp)::NNI], rest lb)
          lb:=rest lb
        else
          lb:=concat([lb.first.gen,
                   (lb.first.exp-la.first.exp)::NNI], rest la)
          la:=rest la
      empty? la and not empty? lb


    a < b ==               --  ordre lexicographique par longueur
      la:NNI := length a; lb:NNI := length b
      la = lb =>  lexico(a,b)
      la < lb

    mirror x == reverse(x)$Rep
```

———-

— OFMONOID.dotabb —

```
"OFMONOID" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OFMONOID"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"OFMONOID" -> "FLAGG"
"OFMONOID" -> "FLAGG-"
```

———-

16.15 domain OVAR OrderedVariableList

— OrderedVariableList.input —

```
)set break resume
```

```
)sys rm -f OrderedVariableList.output
)spool OrderedVariableList.output
)set message test on
)set message auto off
)clear all
--S 1 of 5
ls:List Symbol:=['x,'a,'z]
--R
--R
--R   (1)  [x,a,z]
--R                                                    Type: List(Symbol)
--E 1

--S 2 of 5
Z:=OVAR ls
--R
--R
--R   (2)  OrderedVariableList([x,a,z])
--R                                                          Type: Domain
--E 2

--S 3 of 5
size()$Z
--R
--R
--R   (3)  3
--R                                                 Type: NonNegativeInteger
--E 3

--S 4 of 5
lv:=[index(i::PI)$Z for i in 1..size()$Z]
--R
--I   Compiling function G1408 with type Integer -> Boolean
--I   Compiling function G1572 with type NonNegativeInteger -> Boolean
--R
--R   (4)  [x,a,z]
--R                                  Type: List(OrderedVariableList([x,a,z]))
--E 4

--S 5 of 5
sorted?(>,lv)
--R
--R
--R   (5)  true
--R                                                          Type: Boolean
--E 5
)spool
)lisp (bye)
```

— OrderedVariableList.help —

```
==========================================================================
OrderedVariableList examples
==========================================================================

The domain OrderedVariableList provides symbols which are restricted
to a particular list and have a definite ordering. Those two features
are specified by a List Symbol object that is the argument to the
domain.

This is a sample ordering of three symbols.

  ls:List Symbol:=['x,'a,'z]
    [x,a,z]
                                Type: List Symbol

Let's build the domain

  Z:=OVAR ls
    OrderedVariableList [x,a,z]
                                Type: Domain

How many variables does it have?

  size()$Z
    3
                                Type: NonNegativeInteger

They are (in the imposed order)


  lv:=[index(i::PI)$Z for i in 1..size()$Z]
    [x,a,z]
                                Type: List OrderedVariableList [x,a,z]

Check that the ordering is right

  sorted?(>,lv)
    true
                                Type: Boolean

See Also:
o )show OrderedVariableList
```

16.15.1 OrderedVariableList (OVAR)



Exports:

coerce	convert	hash	index	latex
lookup	max	min	random	size
variable	?~=?	?<?	?<=?	?=?
?>?	?>=?			

— domain OVAR OrderedVariableList —

```
)abbrev domain OVAR OrderedVariableList
++ Author: Mark Botch
++ Description:
++ This domain implements ordered variables

OrderedVariableList(VariableList:List Symbol):
  Join(OrderedFinite, ConvertibleTo Symbol, ConvertibleTo InputForm,
       ConvertibleTo Pattern Float, ConvertibleTo Pattern Integer) with
         variable: Symbol -> Union(%,"failed")
                ++ variable(s) returns a member of the variable set or failed
    == add
       VariableList := removeDuplicates VariableList
       Rep := PositiveInteger
       s1,s2:%
       convert(s1):Symbol == VariableList.((s1::Rep)::PositiveInteger)
       coerce(s1):OutputForm == (convert(s1)@Symbol)::OutputForm
       convert(s1):InputForm == convert(convert(s1)@Symbol)
       convert(s1):Pattern(Integer) == convert(convert(s1)@Symbol)
       convert(s1):Pattern(Float) == convert(convert(s1)@Symbol)
       index i   == i::%
       lookup j  == j :: Rep
       size ()   == #VariableList
       variable(exp:Symbol) ==
            for i in 1.. for exp2 in VariableList repeat
                if exp=exp2 then return i::PositiveInteger::%
            "failed"
       s1 < s2 == s2 <$Rep s1
```

```
      s1 = s2 == s1 =$Rep s2
      latex(x:%):String      == latex(convert(x)@Symbol)
```

———-

— **OVAR.dotabb** —

```
"OVAR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OVAR"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"OVAR" -> "ALIST"
```

———-

16.16 domain ODPOL OrderlyDifferentialPolynomial

— **OrderlyDifferentialPolynomial.input** —

```
)set break resume
)sys rm -f OrderlyDifferentialPolynomial.output
)spool OrderlyDifferentialPolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 36
dpol:= ODPOL(FRAC INT)
--R
--R
--R   (1)  OrderlyDifferentialPolynomial(Fraction(Integer))
--R                                                              Type: Domain
--E 1

--S 2 of 36
w := makeVariable('w)$dpol
--R
--R
--R   (2)  theMap(DPOLCAT-;makeVariable;AM;17!0,0)
--RType: (NonNegativeInteger -> OrderlyDifferentialPolynomial(Fraction(Integer)))
--E 2

--S 3 of 36
z := makeVariable('z)$dpol
--R
--R
--R   (3)  theMap(DPOLCAT-;makeVariable;AM;17!0,0)
```

```
--RType: (NonNegativeInteger -> OrderlyDifferentialPolynomial(Fraction(Integer)))
--E 3

--S 4 of 36
w.5
--R
--R
--R   (4)  w
--R         5
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 4

--S 5 of 36
w 0
--R
--R
--R   (5)  w
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 5

--S 6 of 36
[z.i for i in 1..5]
--R
--R
--R   (6)  [z ,z ,z ,z ,z ]
--R          1  2  3  4  5
--R                 Type: List(OrderlyDifferentialPolynomial(Fraction(Integer)))
--E 6

--S 7 of 36
f:= w.4 - w.1 * w.1 * z.3
--R
--R
--R               2
--R   (7)  w  - w  z
--R         4    1  3
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 7

--S 8 of 36
g:=(z.1)**3 * (z.2)**2 - w.2
--R
--R
--R          3  2
--R   (8)  z  z   - w
--R         1  2     2
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 8

--S 9 of 36
```

```
D(f)
--R
--R
--R              2
--R   (9)  w  - w  z  - 2w w z
--R         5    1  4     1 2 3
--R                      Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 9

--S 10 of 36
D(f,4)
--R
--R
--R   (10)
--R            2                                  2
--R     w  - w  z  - 8w w z  + (- 12w w  - 12w  )z  - 2w z w
--R      8    1  7     1 2 6         1 3      2   5     1 3 5
--R   +
--R                                        2
--R     (- 8w w  - 24w w )z  - 8w z w  - 6w  z
--R          1 4      2 3  4     2 3 4     3  3
--R                      Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 10

--S 11 of 36
df:=makeVariable(f)$dpol
--R
--R
--R   (11)  theMap(DPOLCAT-;makeVariable;AM;17!0,0)
--RType: (NonNegativeInteger -> OrderlyDifferentialPolynomial(Fraction(Integer)))
--E 11

--S 12 of 36
df.4
--R
--R
--R   (12)
--R            2                                  2
--R     w  - w  z  - 8w w z  + (- 12w w  - 12w  )z  - 2w z w
--R      8    1  7     1 2 6         1 3      2   5     1 3 5
--R   +
--R                                        2
--R     (- 8w w  - 24w w )z  - 8w z w  - 6w  z
--R          1 4      2 3  4     2 3 4     3  3
--R                      Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 12

--S 13 of 36
order(g)
--R
```

```
--R
--R   (13)  2
--R                                                        Type: PositiveInteger
--E 13

--S 14 of 36
order(g, 'w)
--R
--R
--R   (14)  2
--R                                                        Type: PositiveInteger
--E 14

--S 15 of 36
differentialVariables(g)
--R
--R
--R   (15)  [z,w]
--R                                                           Type: List(Symbol)
--E 15

--S 16 of 36
degree(g)
--R
--R
--R           2  3
--R   (16)  z  z
--R          2  1
--R                  Type: IndexedExponents(OrderlyDifferentialVariable(Symbol))
--E 16

--S 17 of 36
degree(g, 'w)
--R
--R
--R   (17)  1
--R                                                        Type: PositiveInteger
--E 17

--S 18 of 36
weights(g)
--R
--R
--R   (18)  [7,2]
--R                                              Type: List(NonNegativeInteger)
--E 18

--S 19 of 36
weights(g,'w)
--R
```

```
--R
--R   (19)  [2]
--R                                                Type: List(NonNegativeInteger)
--E 19

--S 20 of 36
weight(g)
--R
--R
--R   (20)  7
--R                                                   Type: PositiveInteger
--E 20

--S 21 of 36
isobaric?(g)
--R
--R
--R   (21)  false
--R                                                           Type: Boolean
--E 21

--S 22 of 36
eval(g,['w::Symbol],[f])
--R
--R
--R                  2                           2        3  2
--R   (22)  - w  + w  z  + 4w w z  + (2w w  + 2w  )z  + z  z
--R            6    1  5     1 2 4      1 3     2   3    1  2
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 22

--S 23 of 36
eval(g,variables(w.0),[f])
--R
--R
--R           3  2
--R   (23)  z  z   - w
--R          1  2     2
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 23

--S 24 of 36
monomials(g)
--R
--R
--R            3  2
--R   (24)  [z  z  ,- w ]
--R           1  2     2
--R                 Type: List(OrderlyDifferentialPolynomial(Fraction(Integer)))
--E 24
```

```
--S 25 of 36
variables(g)
--R
--R
--R   (25)  [z ,w ,z ]
--R           2  2  1
--R                                Type: List(OrderlyDifferentialVariable(Symbol))
--E 25

--S 26 of 36
gcd(f,g)
--R
--R
--R   (26)  1
--R                          Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 26

--S 27 of 36
groebner([f,g])
--R
--R
--R                  2     3  2
--R   (27)  [w  - w  z ,z  z   - w ]
--R           4    1  3  1  2     2
--R                 Type: List(OrderlyDifferentialPolynomial(Fraction(Integer)))
--E 27

--S 28 of 36
lg:=leader(g)
--R
--R
--R   (28)  z
--R          2
--R                                      Type: OrderlyDifferentialVariable(Symbol)
--E 28

--S 29 of 36
sg:=separant(g)
--R
--R
--R            3
--R   (29)  2z  z
--R           1  2
--R                          Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 29

--S 30 of 36
ig:=initial(g)
--R
```

```
--R
--R           3
--R   (30)  z
--R          1
--R                        Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 30

--S 31 of 36
g1 := D g
--R
--R
--R            3               2  3
--R   (31)  2z  z z  - w  + 3z  z
--R           1  2 3    3     1  2
--R                        Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 31

--S 32 of 36
lg1:= leader g1
--R
--R
--R   (32)  z
--R          3
--R                                    Type: OrderlyDifferentialVariable(Symbol)
--E 32

--S 33 of 36
pdf:=D(f, lg1)
--R
--R
--R             2
--R   (33)  - w
--R            1
--R                        Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 33

--S 34 of 36
prf:=sg * f- pdf * g1
--R
--R
--R            3         2        2  2  3
--R   (34)  2z  z w  - w  w  + 3w  z  z
--R           1  2 4    1  3     1  1  2
--R                        Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 34

--S 35 of 36
lcf:=leadingCoefficient univariate(prf, lg)
--R
--R
```

```
--R           2  2
--R   (35)  3w  z
--R          1  1
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 35

--S 36 of 36
ig * prf - lcf * g * lg
--R
--R
--R           6         2  3        2  2
--R   (36)  2z  z w  - w  z  w  + 3w  z  w z
--R          1  2 4    1  1  3     1  1  2 2
--R                       Type: OrderlyDifferentialPolynomial(Fraction(Integer))
--E 36
)spool
)lisp (bye)
```

———-

— OrderlyDifferentialPolynomial.help —

```
=====================================================================
OrderlyDifferentialPolynomial examples
=====================================================================

Many systems of differential equations may be transformed to equivalent
systems of ordinary differential equations where the equations are expressed
polynomially in terms of the unknown functions.  In Axiom, the domain
constructors OrderlyDifferentialPolynomial (abbreviated ODPOL) and
SequentialDifferentialPolynomial (abbreviation SDPOL) implement two
domains of ordinary differential polynomials over any differential
ring.  In the simplest case, this differential ring is usually either
the ring of integers, or the field of rational numbers.  However,
Axiom can handle ordinary differential polynomials over a field of
rational functions in a single indeterminate.

The two domains ODPOL and SDPOL are almost identical, the only difference
being the choice of a different ranking, which is an ordering of the
derivatives of the indeterminates.  The first domain uses an orderly ranking,
that is, derivatives of higher order are ranked higher, and derivatives of
the same order are ranked alphabetically.  The second domain uses a
sequential ranking, where derivatives are ordered first alphabetically
by the differential indeterminates, and then by order.  A more general
domain constructor, DifferentialSparseMultivariatePolynomial (abbreviation
DSMP) allows both a user-provided list of differential indeterminates
as well as a user-defined ranking.  We shall illustrate ODPOL(FRAC INT),
which constructs a domain of ordinary differential polynomials in an
arbitrary number of differential indeterminates with rational numbers
```

```
as coefficients.

  dpol:= ODPOL(FRAC INT)
    OrderlyDifferentialPolynomial Fraction Integer
                            Type: Domain

A differential indeterminate w may be viewed as an infinite sequence of
algebraic indeterminates, which are the derivatives of w. To facilitate
referencing these, Axiom provides the operation makeVariable to convert
an element of type Symbol to a map from the natural numbers to the
differential polynomial ring.

  w := makeVariable('w)$dpol
    theMap(DPOLCAT-;makeVariable;AM;17!0,0)
 Type: (NonNegativeInteger -> OrderlyDifferentialPolynomial Fraction Integer)

  z := makeVariable('z)$dpol
    theMap(DPOLCAT-;makeVariable;AM;17!0,0)
 Type: (NonNegativeInteger -> OrderlyDifferentialPolynomial Fraction Integer)

The fifth derivative of w can be obtained by applying the map w to the
number 5.  Note that the order of differentiation is given as a subscript
(except when the order is 0).

  w.5
    w
     5
                      Type: OrderlyDifferentialPolynomial Fraction Integer

  w 0
    w
                      Type: OrderlyDifferentialPolynomial Fraction Integer

The first five derivatives of z can be generated by a list.

  [z.i for i in 1..5]
    [z ,z ,z ,z ,z ]
      1  2  3  4  5
                    Type: List OrderlyDifferentialPolynomial Fraction Integer

The usual arithmetic can be used to form a differential polynomial from
the derivatives.

  f:= w.4 - w.1 * w.1 * z.3
           2
    w  - w  z
     4    1  3
                    Type: OrderlyDifferentialPolynomial Fraction Integer

  g:=(z.1)**3 * (z.2)**2 - w.2
```

```
     3  2
   z  z   - w
    1  2     2
                  Type: OrderlyDifferentialPolynomial Fraction Integer
```

The operation D computes the derivative of any differential polynomial.

```
  D(f)
          2
    w  - w  z  - 2w w z
     5    1  4     1 2 3
                  Type: OrderlyDifferentialPolynomial Fraction Integer
```

The same operation can compute higher derivatives, like the fourth derivative.

```
  D(f,4)
           2                                2
     w  - w  z  - 8w w z  + (- 12w w  - 12w  )z  - 2w z w
      8    1  7     1 2 6         1 3      2   5     1 3 5
   +
                                      2
     (- 8w w  - 24w w )z  - 8w z w  - 6w  z
          1 4      2 3  4     2 3 4     3  3
                        Type: OrderlyDifferentialPolynomial Fraction Integer
```

The operation makeVariable creates a map to facilitate referencing the
derivatives of f, similar to the map w.

```
  df:=makeVariable(f)$dpol
    theMap(DPOLCAT-;makeVariable;AM;17!0,0)
 Type: (NonNegativeInteger -> OrderlyDifferentialPolynomial Fraction Integer)
```

The fourth derivative of f may be referenced easily.

```
  df.4
           2                                2
     w  - w  z  - 8w w z  + (- 12w w  - 12w  )z  - 2w z w
      8    1  7     1 2 6         1 3      2   5     1 3 5
   +
                                      2
     (- 8w w  - 24w w )z  - 8w z w  - 6w  z
          1 4      2 3  4     2 3 4     3  3
                  Type: OrderlyDifferentialPolynomial Fraction Integer
```

The operation order returns the order of a differential polynomial,
or the order in a specified differential indeterminate.

```
  order(g)
    2
                  Type: PositiveInteger
```

```
  order(g, 'w)
    2
                    Type: PositiveInteger
```

The operation differentialVariables returns a list of differential indeterminates occurring in a differential polynomial.

```
  differentialVariables(g)
    [z,w]
                    Type: List Symbol
```

The operation degree returns the degree, or the degree in the differential indeterminate specified.

```
  degree(g)
       2  3
     z  z
      2  1
                    Type: IndexedExponents OrderlyDifferentialVariable Symbol

  degree(g, 'w)
    1
                    Type: PositiveInteger
```

The operation weights returns a list of weights of differential monomials appearing in differential polynomial, or a list of weights in a specified differential indeterminate.

```
  weights(g)
    [7,2]
                    Type: List NonNegativeInteger

  weights(g,'w)
    [2]
                    Type: List NonNegativeInteger
```

The operation weight returns the maximum weight of all differential monomials appearing in the differential polynomial.

```
  weight(g)
    7
                    Type: PositiveInteger
```

A differential polynomial is isobaric if the weights of all differential monomials appearing in it are equal.

```
  isobaric?(g)
    false
                    Type: Boolean
```

To substitute differentially, use eval. Note that we must coerce 'w to Symbol, since in ODPOL, differential indeterminates belong to the domain Symbol. Compare this result to the next, which substitutes algebraically (no substitution is done since w.0 does not appear in g).

```
eval(g,['w::Symbol],[f])
           2                          2        3  2
   - w  + w  z  + 4w w z  + (2w w  + 2w  )z  + z  z
      6    1  5     1 2 4      1 3     2   3    1  2
                  Type: OrderlyDifferentialPolynomial Fraction Integer

eval(g,variables(w.0),[f])
     3  2
   z  z   - w
    1  2     2
                  Type: OrderlyDifferentialPolynomial Fraction Integer
```

Since OrderlyDifferentialPolynomial belongs to PolynomialCategory, all the operations defined in the latter category, or in packages for the latter category, are available.

```
monomials(g)
      3  2
   [z  z  ,- w ]
     1  2     2
                  Type: List OrderlyDifferentialPolynomial Fraction Integer

variables(g)
  [z ,w ,z ]
    2  2  1
                  Type: List OrderlyDifferentialVariable Symbol

gcd(f,g)
  1
                  Type: OrderlyDifferentialPolynomial Fraction Integer

groebner([f,g])
          2     3  2
   [w  - w  z ,z  z   - w ]
     4    1  3  1  2     2
                  Type: List OrderlyDifferentialPolynomial Fraction Integer
```

The next three operations are essential for elimination procedures in differential polynomial rings. The operation leader returns the leader of a differential polynomial, which is the highest ranked derivative of the differential indeterminates that occurs.

```
lg:=leader(g)
   z
```

```
     2
                    Type: OrderlyDifferentialVariable Symbol
```

The operation separant returns the separant of a differential polynomial, which is the partial derivative with respect to the leader.

```
  sg:=separant(g)
       3
    2z  z
      1  2
                    Type: OrderlyDifferentialPolynomial Fraction Integer
```

The operation initial returns the initial, which is the leading coefficient when the given differential polynomial is expressed as a polynomial in the leader.

```
  ig:=initial(g)
      3
    z
     1
                    Type: OrderlyDifferentialPolynomial Fraction Integer
```

Using these three operations, it is possible to reduce f modulo the differential ideal generated by g. The general scheme is to first reduce the order, then reduce the degree in the leader. First, eliminate z.3 using the derivative of g.

```
  g1 := D g
       3               2  3
    2z  z z  - w  + 3z  z
      1  2 3    3     1  2
                    Type: OrderlyDifferentialPolynomial Fraction Integer
```

Find its leader.

```
  lg1:= leader g1
    z
     3
                    Type: OrderlyDifferentialVariable Symbol
```

Differentiate f partially with respect to this leader.

```
  pdf:=D(f, lg1)
        2
    - w
       1
                    Type: OrderlyDifferentialPolynomial Fraction Integer
```

Compute the partial remainder of f with respect to g.

```
  prf:=sg * f- pdf * g1
       3         2        2  2  3
    2z  z w  - w  w  + 3w  z  z
      1  2 4    1  3     1  1  2
                    Type: OrderlyDifferentialPolynomial Fraction Integer

Note that high powers of lg still appear in prf.  Compute the leading
coefficient of prf as a polynomial in the leader of g.


  lcf:=leadingCoefficient univariate(prf, lg)
       2  2
    3w  z
      1  1
                    Type: OrderlyDifferentialPolynomial Fraction Integer

Finally, continue eliminating the high powers of lg appearing in prf to
obtain the (pseudo) remainder of f modulo g and its derivatives.

  ig * prf - lcf * g * lg
       6         2  3        2  2
    2z  z w  - w  z  w  + 3w  z  w z
      1  2 4    1  1  3     1  1  2 2
                    Type: OrderlyDifferentialPolynomial Fraction Integer

See Also:
o )show OrderlyDifferentialPolynomial
```

16.16.1 OrderlyDifferentialPolynomial (ODPOL)



See

⇒ “OrderlyDifferentialVariable” (ODVAR) 16.17.1 on page 1821
⇒ “SequentialDifferentialVariable” (SDVAR) 20.7.1 on page 2357

⇒ "DifferentialSparseMultivariatePolynomial" (DSMP) 5.8.1 on page 528
⇒ "SequentialDifferentialPolynomial" (SDPOL) 20.6.1 on page 2351

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	D
degree	differentialVariables	differentiate
discriminant	eval	exquo
factor	factorPolynomial	factorSquareFreePolynomial
gcd	gcdPolynomial	ground
ground?	hash	initial
isExpt	isobaric?	isPlus
isTimes	latex	lcm
leader	leadingCoefficient	leadingMonomial
mainVariable	map	mapExponents
max	min	minimumDegree
monicDivide	monomial	monomial?
monomials	multivariate	numberOfMonomials
one?	order	patternMatch
pomopo!	prime?	primitiveMonomials
primitivePart	recip	reducedSystem
reductum	resultant	retract
retractIfCan	sample	separant
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	totalDegree
totalDegree	unit?	unitCanonical
unitNormal	univariate	univariate
variables	weight	weights
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?
?/?	?<?	?<=?
?>?	?>=?	

— domain ODPOL OrderlyDifferentialPolynomial —

```
)abbrev domain ODPOL OrderlyDifferentialPolynomial
++ Author:  William Sit
++ Date Created: 24 September, 1991
++ Date Last Updated: 7 February, 1992
++ Basic Operations:DifferentialPolynomialCategory
++ Related Constructors: DifferentialSparseMultivariatePolynomial
++ See Also:
++ AMS Classifications:12H05
++ Keywords: differential indeterminates, ranking, differential polynomials,
++           order, weight, leader, separant, initial, isobaric
```

```
++ References:Kolchin, E.R. "Differential Algebra and Algebraic Groups"
++   (Academic Press, 1973).
++ Description:
++ \spadtype{OrderlyDifferentialPolynomial} implements
++ an ordinary differential polynomial ring in arbitrary number
++ of differential indeterminates, with coefficients in a
++ ring.  The ranking on the differential indeterminate is orderly.
++ This is analogous to the domain \spadtype{Polynomial}.

OrderlyDifferentialPolynomial(R):
     Exports == Implementation where
  R: Ring
  S  ==> Symbol
  V  ==> OrderlyDifferentialVariable S
  E   ==> IndexedExponents(V)
  SMP ==> SparseMultivariatePolynomial(R, S)
  Exports ==> Join(DifferentialPolynomialCategory(R,S,V,E),
                   RetractableTo SMP)

  Implementation ==> DifferentialSparseMultivariatePolynomial(R,S,V)
```

———-

— ODPOL.dotabb —

```
"ODPOL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ODPOL"]
"DPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DPOLCAT"]
"ODPOL" -> "DPOLCAT"
```

———-

16.17 domain ODVAR OrderlyDifferentialVariable

— OrderlyDifferentialVariable.input —

```
)set break resume
)sys rm -f OrderlyDifferentialVariable.output
)spool OrderlyDifferentialVariable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OrderlyDifferentialVariable
```

```
--R
--R OrderlyDifferentialVariable(S: OrderedSet)  is a domain constructor
--R Abbreviation for OrderlyDifferentialVariable is ODVAR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ODVAR
--R
--R------------------------------ Operations ------------------------------
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               coerce : S -> %
--R coerce : % -> OutputForm              differentiate : % -> %
--R hash : % -> SingleInteger             latex : % -> String
--R max : (%,%) -> %                      min : (%,%) -> %
--R order : % -> NonNegativeInteger       retract : % -> S
--R variable : % -> S                     weight : % -> NonNegativeInteger
--R ?~=? : (%,%) -> Boolean
--R differentiate : (%,NonNegativeInteger) -> %
--R makeVariable : (S,NonNegativeInteger) -> %
--R retractIfCan : % -> Union(S,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— OrderlyDifferentialVariable.help —

```
=====================================================================
OrderlyDifferentialVariable examples
=====================================================================

See Also:
o )show OrderlyDifferentialVariable
```

———-

16.17.1 OrderlyDifferentialVariable (ODVAR)



See

⇒ "SequentialDifferentialVariable" (SDVAR) 20.7.1 on page 2357
⇒ "DifferentialSparseMultivariatePolynomial" (DSMP) 5.8.1 on page 528
⇒ "OrderlyDifferentialPolynomial" (ODPOL) 16.16.1 on page 1817
⇒ "SequentialDifferentialPolynomial" (SDPOL) 20.6.1 on page 2351

Exports:

coerce	differentiate	hash	latex	makeVariable
max	min	order	retract	retractIfCan
variable	weight	?~=?	?<?	?<=?
?=?	?>?	?>=?		

— domain ODVAR OrderlyDifferentialVariable —

```
)abbrev domain ODVAR OrderlyDifferentialVariable
++ Author:  William Sit
++ Date Created: 19 July 1990
++ Date Last Updated: 13 September 1991
++ Basic Operations:differentiate, order, variable,<
++ Related Domains: OrderedVariableList,
++                  SequentialDifferentialVariable.
++ See Also: DifferentialVariableCategory
++ AMS Classifications:12H05
++ Keywords: differential indeterminates, orderly ranking.
++ References:Kolchin, E.R. "Differential Algebra and Algebraic Groups"
++   (Academic Press, 1973).
++ Description:
++ \spadtype{OrderlyDifferentialVariable} adds a commonly used orderly
++ ranking to the set of derivatives of an ordered list of differential
++ indeterminates.  An orderly ranking is a ranking \spadfun{<} of the
++ derivatives with the property that for two derivatives u and v,
++ u \spadfun{<} v if the \spadfun{order} of u is less than that of v.
++ This domain belongs to \spadtype{DifferentialVariableCategory}.  It
++ defines \spadfun{weight} to be just \spadfun{order}, and it
++ defines an orderly ranking \spadfun{<} on derivatives u via the
++ lexicographic order on the pair
```

```
++ (\spadfun{order}(u), \spadfun{variable}(u)).

OrderlyDifferentialVariable(S:OrderedSet):DifferentialVariableCategory(S)
  == add
    Rep := Record(var:S, ord:NonNegativeInteger)
    makeVariable(s,n) == [s, n]
    variable v     == v.var
    order v        == v.ord
```

———-

— ODVAR.dotabb —

```
"ODVAR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ODVAR"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"RETRACT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RETRACT"]
"ODVAR" -> "ORDSET"
"ODVAR" -> "RETRACT"
```

———-

16.18 domain ODR OrdinaryDifferentialRing

— OrdinaryDifferentialRing.input —

```
)set break resume
)sys rm -f OrdinaryDifferentialRing.output
)spool OrdinaryDifferentialRing.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OrdinaryDifferentialRing
--R
--R OrdinaryDifferentialRing(Kernels: SetCategory,R: PartialDifferentialRing(Kernels),var: Kerne
--R Abbreviation for OrdinaryDifferentialRing is ODR
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ODR
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,%) -> %                      ?*? : (%,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
```

```
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                D : % -> %
--R D : (%,NonNegativeInteger) -> %       1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coerce : % -> R                       coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R differentiate : % -> %                hash : % -> SingleInteger
--R inv : % -> % if R has FIELD           latex : % -> String
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if R has FIELD
--R ?*? : (Fraction(Integer),%) -> % if R has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Integer) -> % if R has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if R has FIELD
--R ?^? : (%,Integer) -> % if R has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has FIELD
--R characteristic : () -> NonNegativeInteger
--R coerce : % -> % if R has FIELD
--R coerce : Fraction(Integer) -> % if R has FIELD
--R differentiate : (%,NonNegativeInteger) -> %
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed") if R has FIELD
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R factor : % -> Factored(%) if R has FIELD
--R gcd : (%,%) -> % if R has FIELD
--R gcd : List(%) -> % if R has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R lcm : (%,%) -> % if R has FIELD
--R lcm : List(%) -> % if R has FIELD
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R prime? : % -> Boolean if R has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if R has FIELD
--R ?quo? : (%,%) -> % if R has FIELD
--R ?rem? : (%,%) -> % if R has FIELD
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R squareFree : % -> Factored(%) if R has FIELD
--R squareFreePart : % -> % if R has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit? : % -> Boolean if R has FIELD
--R unitCanonical : % -> % if R has FIELD
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has FIELD
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **OrdinaryDifferentialRing.help** —

```
=====================================================================
OrdinaryDifferentialRing examples
=====================================================================

See Also:
o )show OrdinaryDifferentialRing
```

———-

16.18.1 OrdinaryDifferentialRing (ODR)



See

⇒ “OppositeMonogenicLinearOperator” (OMLO) 16.11.1 on page 1773
⇒ “DirectProductModule” (DPMO) 5.11.1 on page 544
⇒ “DirectProductMatrixModule” (DPMM) 5.10.1 on page 540

Exports:

0	1	associates?	characteristic
coerce	D	differentiate	divide
euclideanSize	expressIdealMember	exquo	extendedEuclidean
factor	gcd	gcdPolynomial	hash
inv	latex	lcm	multiEuclidean
one?	prime?	principalIdeal	recip
sample	sizeLess?	squareFree	squareFreePart
subtractIfCan	unit?	unitCanonical	unitNormal
zero?	?*?	?**?	?+?
?-?	-?	?=?	?^?
?~=?	?/?	?quo?	?rem?

— domain ODR OrdinaryDifferentialRing —

```
)abbrev domain ODR OrdinaryDifferentialRing
++ Author: Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: June 3, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: differential ring
++ Examples:
++ References:
++ Description:
++ This constructor produces an ordinary differential ring from
++ a partial differential ring by specifying a variable.

OrdinaryDifferentialRing(Kernels,R,var): DRcategory == DRcapsule where
    Kernels:SetCategory
    R: PartialDifferentialRing(Kernels)
    var : Kernels
    DRcategory == Join(BiModule($,$), DifferentialRing) with
        if R has Field then Field
        coerce: R -> $
            ++ coerce(r) views r as a value in the ordinary differential ring.
        coerce: $ -> R
            ++ coerce(p) views p as a valie in the partial differential ring.
    DRcapsule == R add
        n: Integer
        Rep := R
        coerce(u:R):$ == u::Rep::$
        coerce(p:$):R == p::Rep::R
        differentiate p       == differentiate(p, var)

        if R has Field then
            p / q     == ((p::R) /$R (q::R))::$
            p ** n    == ((p::R) **$R n)::$
```

```
inv(p)    == (inv(p::R)$R)::$
```

———-

— ODR.dotabb —

```
"ODR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ODR"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"ODR" -> "FIELD"
```

———-

16.19 domain OWP OrdinaryWeightedPolynomials

— OrdinaryWeightedPolynomials.input —

```
)set break resume
)sys rm -f OrdinaryWeightedPolynomials.output
)spool OrdinaryWeightedPolynomials.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OrdinaryWeightedPolynomials
--R
--R OrdinaryWeightedPolynomials(R: Ring,vl: List(Symbol),wl: List(NonNegativeInteger),wtlevel: N
--R Abbreviation for OrdinaryWeightedPolynomials is OWP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OWP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : Polynomial(R) -> %
--R coerce : % -> Polynomial(R)           coerce : Integer -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   one? : % -> Boolean
--R recip : % -> Union(%,"failed")        sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,R) -> % if R has COMRING
```

```
--R ?*? : (R,%) -> % if R has COMRING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> Union(%,"failed") if R has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R changeWeightLevel : NonNegativeInteger -> Void
--R characteristic : () -> NonNegativeInteger
--R coerce : R -> % if R has COMRING
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **OrdinaryWeightedPolynomials.help** —

```
=====================================================================
OrdinaryWeightedPolynomials examples
=====================================================================

See Also:
o )show OrdinaryWeightedPolynomials
```

———-

16.19.1 OrdinaryWeightedPolynomials (OWP)



Exports:

0	1	changeWeightLevel	characteristic	coerce
hash	latex	one?	recip	sample
subtractIfCan	zero?	?*?	?**?	?+?
?-?	-?	?=?	?^?	?~=?
?/?				

— domain OWP OrdinaryWeightedPolynomials —

```
)abbrev domain OWP OrdinaryWeightedPolynomials
++ Author: James Davenport
++ Date Created:  17 April 1992
++ Date Last Updated: 12 July 1992
++ Basic Functions: Ring, changeWeightLevel
++ Related Constructors: WeightedPolynomials
++ Also See: PolynomialRing
++ AMS classifications:
++ Keywords:
++ References:
++ Description:
++ This domain represents truncated weighted polynomials over the
++ "Polynomial" type. The variables must be
++ specified, as must the weights.
++ The representation is sparse
++ in the sense that only non-zero terms are represented.

OrdinaryWeightedPolynomials(R:Ring,
                            vl:List Symbol, wl:List NonNegativeInteger,
                             wtlevel:NonNegativeInteger):
       Ring with
         if R has CommutativeRing then Algebra(R)
         coerce: $ -> Polynomial(R)
           ++ coerce(p) converts back into a Polynomial(R), ignoring weights
         coerce: Polynomial(R) -> $
           ++ coerce(p) coerces a Polynomial(R) into Weighted form,
           ++ applying weights and ignoring terms
         if R has Field then "/": ($,$) -> Union($,"failed")
           ++ x/y division (only works if minimum weight
           ++ of divisor is zero, and if R is a Field)
         changeWeightLevel: NonNegativeInteger -> Void
           ++ changeWeightLevel(n) This changes the weight level to the
           ++ new value given:
           ++ NB: previously calculated terms are not affected
    == WeightedPolynomials(R,Symbol,IndexedExponents(Symbol),
                           Polynomial(R),
                            vl,wl,wtlevel)
```

———-

— **OWP.dotabb** —

```
"OWP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OWP"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"OWP" -> "FIELD"
```

———-

16.20 domain OSI OrdSetInts

— **OrdSetInts.input** —

```
)set break resume
)sys rm -f OrdSetInts.output
)spool OrdSetInts.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OrdSetInts
--R OrdSetInts  is a domain constructor
--R Abbreviation for OrdSetInts is OSI
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OSI
--R
--R------------------------------ Operations --------------------------------
--R ?<? : (%,%) -> Boolean               ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean               ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean              coerce : Integer -> %
--R coerce : % -> OutputForm             hash : % -> SingleInteger
--R latex : % -> String                  max : (%,%) -> %
--R min : (%,%) -> %                     value : % -> Integer
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-

— **OrdSetInts.help** —


```
=======================================================================
```

```
OrdSetInts examples
===================================================================

See Also:
o )show OrdSetInts
```

———-

16.20.1 OrdSetInts (OSI)



See

⇒ “Commutator” (COMM) 4.7.1 on page 397
⇒ “FreeNilpotentLie” (FNLA) 7.33.1 on page 997

Exports:

coerce	hash	latex	max	min
value	?~=?	?<?	?<=?	?=?
?>?	?>=?			

— domain OSI OrdSetInts —

```
)abbrev domain OSI OrdSetInts
++ Author: Larry Lambe
++ Date created: 14 August 1988
++ Date Last Updated: 11 March 1991
++ Description:
++ A domain used in order to take the free R-module on the
++ Integers I.  This is actually the forgetful functor from OrderedRings
++ to OrderedSets applied to I

OrdSetInts: Export == Implement where
   I  ==> Integer
   L  ==> List
   O  ==> OutputForm

   Export == OrderedSet with
```

```
    coerce : Integer -> %
       ++ coerce(i) returns the element corresponding to i
    value  : % -> I
       ++ value(x) returns the integer associated with x

  Implement == add
    Rep := Integer
    x,y: %

    x = y == x =$Rep y
    x < y == x <$Rep y

    coerce(i:Integer):% == i

    value(x) == x:Rep

    coerce(x):O ==
      sub(e::Symbol::O, coerce(x)$Rep)$O
```

———-

— **OSI.dotabb** —

```
"OSI" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OSI"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"OSI" -> "ALIST"
```

———-

16.21 domain OUTFORM OutputForm

— **OutputForm.input** —

```
)set break resume
)sys rm -f OutputForm.output
)spool OutputForm.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show OutputForm
--R
--R OutputForm  is a domain constructor
```

```
--R Abbreviation for OutputForm is OUTFORM
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OUTFORM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?**? : (%,%) -> %
--R ?+? : (%,%) -> %                      -? : % -> %
--R ?-? : (%,%) -> %                      ?/? : (%,%) -> %
--R ?<? : (%,%) -> %                      ?<=? : (%,%) -> %
--R ?=? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R ?>? : (%,%) -> %                      ?>=? : (%,%) -> %
--R ?SEGMENT : % -> %                     ?..? : (%,%) -> %
--R ?^=? : (%,%) -> %                     ?and? : (%,%) -> %
--R assign : (%,%) -> %                   binomial : (%,%) -> %
--R blankSeparate : List(%) -> %          box : % -> %
--R brace : List(%) -> %                  brace : % -> %
--R bracket : List(%) -> %                bracket : % -> %
--R center : % -> %                       center : (%,Integer) -> %
--R coerce : % -> OutputForm              commaSeparate : List(%) -> %
--R ?div? : (%,%) -> %                    dot : % -> %
--R ?.? : (%,List(%)) -> %                empty : () -> %
--R exquo : (%,%) -> %                    hash : % -> SingleInteger
--R hconcat : List(%) -> %                hconcat : (%,%) -> %
--R height : () -> Integer                height : % -> Integer
--R hspace : Integer -> %                 infix : (%,%,%) -> %
--R infix : (%,List(%)) -> %              infix? : % -> Boolean
--R int : (%,%,%) -> %                    int : (%,%) -> %
--R int : % -> %                          label : (%,%) -> %
--R latex : % -> String                   left : % -> %
--R left : (%,Integer) -> %               matrix : List(List(%)) -> %
--R message : String -> %                 messagePrint : String -> Void
--R not? : % -> %                         ?or? : (%,%) -> %
--R outputForm : DoubleFloat -> %         outputForm : String -> %
--R outputForm : Symbol -> %              outputForm : Integer -> %
--R over : (%,%) -> %                     overbar : % -> %
--R overlabel : (%,%) -> %                paren : List(%) -> %
--R paren : % -> %                        pile : List(%) -> %
--R postfix : (%,%) -> %                  prefix : (%,List(%)) -> %
--R presub : (%,%) -> %                   presuper : (%,%) -> %
--R prime : % -> %                        print : % -> Void
--R prod : (%,%,%) -> %                   prod : (%,%) -> %
--R prod : % -> %                         ?quo? : (%,%) -> %
--R quote : % -> %                        rarrow : (%,%) -> %
--R ?rem? : (%,%) -> %                    right : % -> %
--R right : (%,Integer) -> %              root : (%,%) -> %
--R root : % -> %                         rspace : (Integer,Integer) -> %
--R scripts : (%,List(%)) -> %            semicolonSeparate : List(%) -> %
--R slash : (%,%) -> %                    string : % -> %
--R sub : (%,%) -> %                      subHeight : % -> Integer
--R sum : (%,%,%) -> %                    sum : (%,%) -> %
```

```
--R sum : % -> %                              super : (%,%) -> %
--R superHeight : % -> Integer                supersub : (%,List(%)) -> %
--R vconcat : List(%) -> %                    vconcat : (%,%) -> %
--R vspace : Integer -> %                     width : () -> Integer
--R width : % -> Integer                      zag : (%,%) -> %
--R ?~=? : (%,%) -> Boolean
--R differentiate : (%,NonNegativeInteger) -> %
--R dot : (%,NonNegativeInteger) -> %
--R prime : (%,NonNegativeInteger) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— OutputForm.help —

```
========================================================================
OutputForm examples
========================================================================

See Also:
o )show OutputForm
```

———-

16.21.1 OutputForm (OUTFORM)



Exports:

assign	binomial	blankSeparate	box	brace
bracket	center	coerce	commaSeparate	differentiate
dot	empty	exquo	hash	hconcat
height	hspace	infix	infix?	int
label	latex	left	matrix	message
messagePrint	not?	outputForm	over	overbar
overlabel	paren	pile	postfix	prefix
presub	presuper	prime	print	prod
quote	rarrow	right	root	rspace
scripts	semicolonSeparate	slash	string	sub
subHeight	sum	super	superHeight	supersub
vconcat	vspace	width	zag	?*?
?**?	?+?	-?	?-?	?/?
?<?	?<=?	?=?	?>?	?>=?
?SEGMENT	?..?	?^=?	?and?	?div?
?.?	?or?	?quo?	?rem?	?~=?

— domain OUTFORM OutputForm —

```
)abbrev domain OUTFORM OutputForm
++ Keywords: output, I/O, expression
++ SMW March/88
++ Description:
++ This domain is used to create and manipulate mathematical expressions
++ for output.  It is intended to provide an insulating layer between
++ the expression rendering software (e.g.FORTRAN, TeX, or Script) and
++ the output coercions in the various domains.

OutputForm(): SetCategory with
        --% Printing
        print  : $ -> Void
          ++ print(u) prints the form u.
        message: String -> $
          ++ message(s) creates an form with no string quotes
          ++ from string s.
        messagePrint: String -> Void
          ++ messagePrint(s) prints s without string quotes. Note:
          ++ \spad{messagePrint(s)} is equivalent to \spad{print message(s)}.
        --% Creation of atomic forms
        outputForm: Integer -> $
          ++ outputForm(n) creates an form for integer n.
        outputForm: Symbol  -> $
          ++ outputForm(s) creates an form for symbol s.
        outputForm: String  -> $
          ++ outputForm(s) creates an form for string s.
        outputForm: DoubleFloat  -> $
          ++ outputForm(sf) creates an form for small float sf.
        empty   : () -> $
          ++ empty() creates an empty form.
```

```
--% Sizings
width: $ -> Integer
  ++ width(f) returns the width of form f (an integer).
height: $ -> Integer
  ++ height(f) returns the height of form f (an integer).
width: -> Integer
  ++ width() returns the width of the display area (an integer).
height: -> Integer
  ++ height() returns the height of the display area (an integer).
subHeight: $ -> Integer
  ++ subHeight(f) returns the height of form f below the base line.
superHeight: $ -> Integer
  ++ superHeight(f) returns the height of form f above the base line.
 --% Space manipulations
hspace: Integer -> $  ++ hspace(n) creates white space of width n.
vspace: Integer -> $  ++ vspace(n) creates white space of height n.
rspace: (Integer,Integer) -> $
  ++ rspace(n,m) creates rectangular white space, n wide by m high.
--% Area adjustments
left: ($,Integer) -> $
  ++ left(f,n) left-justifies form f within space of width n.
right: ($,Integer) -> $
  ++ right(f,n) right-justifies form f within space of width n.
center: ($,Integer) -> $
  ++ center(f,n) centers form f within space of width n.
left: $ -> $
  ++ left(f) left-justifies form f in total space.
right: $ -> $
  ++ right(f) right-justifies form f in total space.
center:   $ -> $
  ++ center(f) centers form f in total space.

--% Area manipulations
hconcat:  ($,$) -> $
  ++ hconcat(f,g) horizontally concatenate forms f and g.
vconcat:  ($,$) -> $
  ++ vconcat(f,g) vertically concatenates forms f and g.
hconcat:  List $ -> $
  ++ hconcat(u) horizontally concatenates all forms in list u.
vconcat:  List $ -> $
  ++ vconcat(u) vertically concatenates all forms in list u.

--% Application formers
prefix:  ($, List $) -> $
  ++ prefix(f,l) creates a form depicting the n-ary prefix
  ++ application of f to a tuple of arguments given by list l.
infix:   ($, List $) -> $
  ++ infix(f,l) creates a form depicting the n-ary application
  ++ of infix operation f to a tuple of arguments l.
```

```
infix:   ($, $, $) -> $
  ++ infix(op, a, b) creates a form which prints as: a op b.
postfix: ($, $)    -> $
  ++ postfix(op, a)  creates a form which prints as: a op.
infix?: $ -> Boolean
  ++ infix?(op) returns true if op is an infix operator,
  ++ and false otherwise.
elt:     ($, List $) -> $
  ++ elt(op,l) creates a form for application of op
  ++ to list of arguments l.

--% Special forms
string:  $ -> $
  ++ string(f) creates f with string quotes.
label:   ($, $) -> $
  ++ label(n,f) gives form f an equation label n.
box:     $ -> $
  ++ box(f) encloses f in a box.
matrix:  List List $ -> $
  ++ matrix(llf) makes llf (a list of lists of forms) into
  ++ a form which displays as a matrix.
zag:     ($, $) -> $
  ++ zag(f,g) creates a form for the continued fraction form for f over g.
root:    $ -> $
  ++ root(f) creates a form for the square root of form f.
root:    ($, $) -> $
  ++ root(f,n) creates a form for the nth root of form f.
over:    ($, $) -> $
  ++ over(f,g) creates a form for the vertical fraction of f over g.
slash:   ($, $) -> $
  ++ slash(f,g) creates a form for the horizontal fraction of f over g.
assign:  ($, $) -> $
  ++ assign(f,g) creates a form for the assignment \spad{f := g}.
rarrow:  ($, $) -> $
  ++ rarrow(f,g) creates a form for the mapping \spad{f -> g}.
differentiate: ($, NonNegativeInteger) -> $
  ++ differentiate(f,n) creates a form for the nth derivative of f,
  ++ e.g. \spad{f'}, \spad{f''}, \spad{f'''},
  ++ "f super \spad{iv}".
binomial: ($, $) -> $
  ++ binomial(n,m) creates a form for the binomial coefficient of n and m.

--% Scripts
sub:     ($, $) -> $
  ++ sub(f,n) creates a form for f subscripted by n.
super:   ($, $) -> $
  ++ super(f,n) creates a form for f superscripted by n.
presub:  ($, $) -> $
  ++ presub(f,n) creates a form for f presubscripted by n.
presuper:($, $) -> $
```

```
  ++ presuper(f,n) creates a form for f presuperscripted by n.
scripts: ($, List $) -> $
    ++ \spad{scripts(f, [sub, super, presuper, presub])}
    ++  creates a form for f with scripts on all 4 corners.
supersub:($, List $) -> $
    ++ supersub(a,[sub1,super1,sub2,super2,...])
    ++ creates a form with each subscript aligned
    ++ under each superscript.

--% Diacritical marks
quote:   $ -> $
  ++ quote(f) creates the form f with a prefix quote.
dot:     $ -> $
  ++ dot(f) creates the form with a one dot overhead.
dot:     ($, NonNegativeInteger) -> $
  ++ dot(f,n) creates the form f with n dots overhead.
prime:   $ -> $
  ++ prime(f) creates the form f followed by a suffix prime (single quote).
prime:   ($, NonNegativeInteger) -> $
  ++ prime(f,n) creates the form f followed by n primes.
overbar: $ -> $
  ++ overbar(f) creates the form f with an overbar.
overlabel: ($, $) -> $
  ++ overlabel(x,f) creates the form f with "x overbar" over the top.

--% Plexes
sum:     ($)       -> $
  ++ sum(expr) creates the form prefixing expr by a capital sigma.
sum:     ($, $)    -> $
  ++ sum(expr,lowerlimit) creates the form prefixing expr by
  ++ a capital sigma with a lowerlimit.
sum:     ($, $, $) -> $
  ++ sum(expr,lowerlimit,upperlimit) creates the form prefixing expr by
  ++ a capital sigma with both a lowerlimit and upperlimit.
prod:    ($)       -> $
  ++ prod(expr) creates the form prefixing expr by a capital pi.
prod:    ($, $)    -> $
  ++ prod(expr,lowerlimit) creates the form prefixing expr by
  ++ a capital pi with a lowerlimit.
prod:    ($, $, $) -> $
  ++ prod(expr,lowerlimit,upperlimit) creates the form prefixing expr by
  ++ a capital pi with both a lowerlimit and upperlimit.
int:     ($)       -> $
  ++ int(expr) creates the form prefixing expr with an integral sign.
int:     ($, $)    -> $
  ++ int(expr,lowerlimit) creates the form prefixing expr by an
  ++ integral sign with a lowerlimit.
int:     ($, $, $) -> $
  ++ int(expr,lowerlimit,upperlimit) creates the form prefixing expr by
  ++ an integral sign with both a lowerlimit and upperlimit.
```

```
--% Matchfix forms
brace:   $ -> $
  ++ brace(f) creates the form enclosing f in braces (curly brackets).
brace:   List $ -> $
  ++ brace(lf) creates the form separating the elements of lf
  ++ by commas and encloses the result in curly brackets.
bracket: $ -> $
  ++ bracket(f) creates the form enclosing f in square brackets.
bracket: List $ -> $
  ++ bracket(lf) creates the form separating the elements of lf
  ++ by commas and encloses the result in square brackets.
paren:   $ -> $
  ++ paren(f) creates the form enclosing f in parentheses.
paren:   List $ -> $
  ++ paren(lf) creates the form separating the elements of lf
  ++ by commas and encloses the result in parentheses.

--% Separators for aggregates
pile:     List $ -> $
  ++ pile(l) creates the form consisting of the elements of l which
  ++ displays as a pile, i.e. the elements begin on a new line and
  ++ are indented right to the same margin.

commaSeparate: List $ -> $
  ++ commaSeparate(l) creates the form separating the elements of l
  ++ by commas.
semicolonSeparate:  List $ -> $
  ++ semicolonSeparate(l) creates the form separating the elements of l
  ++ by semicolons.
blankSeparate: List $ -> $
  ++ blankSeparate(l) creates the form separating the elements of l
  ++ by blanks.
--% Specific applications
"=":     ($, $) -> $
  ++ f = g creates the equivalent infix form.
"^=":    ($, $) -> $
  ++ f ^= g creates the equivalent infix form.
"<":     ($, $) -> $
  ++ f < g creates the equivalent infix form.
">":     ($, $) -> $
  ++ f > g creates the equivalent infix form.
"<=":    ($, $) -> $
  ++ f <= g creates the equivalent infix form.
">=":    ($, $) -> $
  ++ f >= g creates the equivalent infix form.
"+":     ($, $) -> $
  ++ f + g creates the equivalent infix form.
"-":     ($, $) -> $
  ++ f - g creates the equivalent infix form.
```

```
    "-":     ($)    -> $
      ++ - f creates the equivalent prefix form.
    "*":     ($, $) -> $
      ++ f * g creates the equivalent infix form.
    "/":     ($, $) -> $
      ++ f / g creates the equivalent infix form.
    "**":    ($, $) -> $
      ++ f ** g creates the equivalent infix form.
    "div":   ($, $) -> $
      ++ f div g creates the equivalent infix form.
    "rem":   ($, $) -> $
      ++ f rem g creates the equivalent infix form.
    "quo":   ($, $) -> $
      ++ f quo g creates the equivalent infix form.
    "exquo": ($, $) -> $
      ++ exquo(f,g) creates the equivalent infix form.
    "and":   ($, $) -> $
      ++ f and g creates the equivalent infix form.
    "or":    ($, $) -> $
      ++ f or g creates the equivalent infix form.
    "not":   ($)    -> $
      ++ not f creates the equivalent prefix form.
    SEGMENT: ($,$)  -> $
      ++ SEGMENT(x,y) creates the infix form: \spad{x..y}.
    SEGMENT: ($)    -> $
      ++ SEGMENT(x) creates the prefix form: \spad{x..}.

== add
    import NumberFormats

    -- Todo:
    --   program forms, greek letters
    --   infix, prefix, postfix, matchfix support in OUT BOOT
    --   labove rabove, corresponding overs.
    --   better super script, overmark, undermark
    --   bug in product, paren blankSeparate []
    --   uniformize integrals, products, etc as plexes.

    cons ==> CONS$Lisp
    car  ==> CAR$Lisp
    cdr  ==> CDR$Lisp

    Rep := List $

    a, b: $
    l: List $
    s: String
    e: Symbol
    n: Integer
    nn:NonNegativeInteger
```

```
sform:    String  -> $
eform:    Symbol  -> $
iform:    Integer -> $

print x              == mathprint(x)$Lisp
message s            == (empty? s => empty(); s pretend $)
messagePrint s       == print message s
(a:$ = b:$):Boolean  == EQUAL(a, b)$Lisp
(a:$ = b:$):$        == [sform "=",     a, b]
coerce(a):OutputForm  == a pretend OutputForm
outputForm n          == n pretend $
outputForm e          == e pretend $
outputForm(f:DoubleFloat) == f pretend $
sform s               == s pretend $
eform e               == e pretend $
iform n               == n pretend $

outputForm s ==
  sform concat(quote()$Character, concat(s, quote()$Character))

width(a) == outformWidth(a)$Lisp
height(a) == height(a)$Lisp
subHeight(a) == subspan(a)$Lisp
superHeight(a) == superspan(a)$Lisp
height() == 20
width() == 66

center(a,w)   == hconcat(hspace((w - width(a)) quo 2),a)
left(a,w)     == hconcat(a,hspace((w - width(a))))
right(a,w)    == hconcat(hspace(w - width(a)),a)
center(a)     == center(a,width())
left(a)       == left(a,width())
right(a)      == right(a,width())

vspace(n) ==
  n = 0 => empty()
  vconcat(sform " ",vspace(n - 1))

hspace(n) ==
  n = 0 => empty()
  sform(fillerSpaces(n)$Lisp)

rspace(n, m) ==
  n = 0 or m = 0 => empty()
  vconcat(hspace n, rspace(n, m - 1))

matrix ll ==
    lv:$ := [LIST2VEC$Lisp l for l in ll]
    CONS(eform MATRIX, LIST2VEC$Lisp lv)$Lisp
```

```
pile l              == cons(eform SC, l)
commaSeparate l     == cons(eform AGGLST,  l)
semicolonSeparate l == cons(eform AGGSET,  l)
blankSeparate l     ==
   c:=eform CONCATB
   l1:$:=[]
   for u in reverse l repeat
       if EQCAR(u,c)$Lisp
          then l1:=[:cdr u,:l1]
          else l1:=[u,:l1]
   cons(c, l1)

brace a        == [eform BRACE,   a]
brace l        == brace commaSeparate l
bracket a      == [eform BRACKET, a]
bracket l      == bracket commaSeparate l
paren a        == [eform PAREN,   a]
paren l        == paren commaSeparate l

sub     (a,b)  == [eform SUB, a, b]
super   (a, b) == [eform SUPERSUB,a,sform " ",b]
presub(a,b) == [eform SUPERSUB,a,sform " ",sform " ",sform " ",b]
presuper(a, b) == [eform SUPERSUB,a,sform " ",sform " ",b]
scripts (a, l) ==
    null l => a
    null rest l => sub(a, first l)
    cons(eform SUPERSUB, cons(a, l))
supersub(a, l) ==
    if odd?(#l) then l := append(l, [empty()])
    cons(eform ALTSUPERSUB, cons(a, l))

hconcat(a,b)  == [eform CONCAT, a, b]
hconcat l     == cons(eform CONCAT, l)
vconcat(a,b)  == [eform VCONCAT, a, b]
vconcat l     == cons(eform VCONCAT, l)

a ^= b      == [sform "^=",    a, b]
a < b       == [sform "<",     a, b]
a > b       == [sform ">",     a, b]
a <= b      == [sform "<=",    a, b]
a >= b      == [sform ">=",    a, b]

a + b       == [sform "+",     a, b]
a - b       == [sform "-",     a, b]
- a         == [sform "-",     a]
a * b       == [sform "*",     a, b]
a / b       == [sform "/",     a, b]
a ** b      == [sform "**",    a, b]
a div b     == [sform "div",   a, b]
```

```
a rem b     == [sform "rem",   a, b]
a quo b     == [sform "quo",   a, b]
a exquo b   == [sform "exquo", a, b]
a and b     == [sform "and",   a, b]
a or b      == [sform "or",    a, b]
not a       == [sform "not",   a]
SEGMENT(a,b)== [eform SEGMENT, a, b]
SEGMENT(a)  == [eform SEGMENT, a]
binomial(a,b)==[eform BINOMIAL, a, b]

empty() == [eform NOTHING]

infix? a ==
    e:$ :=
        IDENTP$Lisp a => a
        STRINGP$Lisp a => INTERN$Lisp a
        return false
    if GET(e,QUOTE(INFIXOP$Lisp)$Lisp)$Lisp then true else false

elt(a, l) ==
    cons(a, l)
prefix(a,l)   ==
    not infix? a => cons(a, l)
    hconcat(a, paren commaSeparate l)
infix(a, l) ==
    null l => empty()
    null rest l => first l
    infix? a => cons(a, l)
    hconcat [first l, a, infix(a, rest l)]
infix(a,b,c)  ==
    infix? a => [a, b, c]
    hconcat [b, a, c]
postfix(a, b) ==
    hconcat(b, a)

string a   == [eform STRING,  a]
quote  a   == [eform QUOTE,   a]
overbar a  == [eform OVERBAR, a]
dot a      == super(a, sform ".")
prime a    == super(a, sform ",")
dot(a,nn)   == (s := new(nn, char "."); super(a, sform s))
prime(a,nn) == (s := new(nn, char ","); super(a, sform s))

overlabel(a,b) == [eform OVERLABEL, a, b]
box a      == [eform BOX,     a]
zag(a,b)   == [eform ZAG,     a, b]
root a     == [eform ROOT,    a]
root(a,b)  == [eform ROOT,    a, b]
over(a,b)  == [eform OVER,    a, b]
slash(a,b) == [eform SLASH,   a, b]
```

```
        assign(a,b)== [eform LET,     a, b]

        label(a,b) == [eform EQUATNUM, a, b]
        rarrow(a,b)== [eform TAG, a, b]
        differentiate(a, nn)==
            zero? nn => a
            nn < 4 => prime(a, nn)
            r := FormatRoman(nn::PositiveInteger)
            s := lowerCase(r::String)
            super(a, paren sform s)

        sum(a)     == [eform SIGMA,  empty(), a]
        sum(a,b)   == [eform SIGMA,  b, a]
        sum(a,b,c) == [eform SIGMA2, b, c, a]
        prod(a)    == [eform PI,     empty(), a]
        prod(a,b)  == [eform PI,     b, a]
        prod(a,b,c)== [eform PI2,    b, c, a]
        int(a)     == [eform INTSIGN,empty(), empty(), a]
        int(a,b)   == [eform INTSIGN,b, empty(), a]
        int(a,b,c) == [eform INTSIGN,b, c, a]
```

———-

— **OUTFORM.dotabb** —

```
"OUTFORM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OUTFORM",
          shape=ellipse]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"OUTFORM" -> "FLAGG"
```

———-

Chapter 17

Chapter P

17.1 domain PADIC PAdicInteger

— PAdicInteger.input —

```
)set break resume
)sys rm -f PAdicInteger.output
)spool PAdicInteger.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PAdicInteger
--R
--R PAdicInteger(p: Integer)  is a domain constructor
--R Abbreviation for PAdicInteger is PADIC
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PADIC
--R
--R------------------------------- Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        associates? : (%,%) -> Boolean
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              complete : % -> %
--R digits : % -> Stream(Integer)         extend : (%,Integer) -> %
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R hash : % -> SingleInteger             latex : % -> String
```

```
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R moduloP : % -> Integer                modulus : () -> Integer
--R one? : % -> Boolean                   order : % -> NonNegativeInteger
--R ?quo? : (%,%) -> %                    quotientByP : % -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R sqrt : (%,Integer) -> %               unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R approximate : (%,Integer) -> Integer
--R characteristic : () -> NonNegativeInteger
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R root : (SparseUnivariatePolynomial(Integer),Integer) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— PAdicInteger.help —

```
=====================================================================
PAdicInteger examples
=====================================================================

See Also:
o )show PAdicInteger
```

———-

17.1.1 PAdicInteger (PADIC)



See

⇒ "InnerPAdicInteger" (IPADIC) 10.24.1 on page 1262
⇒ "BalancedPAdicInteger" (BPADIC) 3.2.1 on page 242
⇒ "PAdicRationalConstructor" (PADICRC) 17.3.1 on page 1856
⇒ "PAdicRational" (PADICRAT) 17.2.1 on page 1851
⇒ "BalancedPAdicRational" (BPADICRT) 3.3.1 on page 246

Exports:

0	1	approximate	associates?
characteristic	coerce	complete	digits
divide	euclideanSize	expressIdealMember	exquo
extend	extendedEuclidean	gcd	gcdPolynomial
hash	latex	lcm	lcm
moduloP	modulus	multiEuclidean	one?
order	principalIdeal	quotientByP	recip
root	sample	sizeLess?	sqrt
subtractIfCan	unit?	unitCanonical	unitNormal
zero?	?*?	?**?	?+?
?-?	-?	?=?	?^?
?~=?	?quo?	?rem?	

— domain PADIC PAdicInteger —

```
)abbrev domain PADIC PAdicInteger
++ Author: Clifton J. Williamson
++ Date Created: 20 August 1989
++ Date Last Updated: 15 May 1990
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Keywords: p-adic, completion
++ Examples:
++ References:
```

```
++ Description:
++ Stream-based implementation of Zp: p-adic numbers are represented as
++ sum(i = 0.., a[i] * p^i), where the a[i] lie in 0,1,...,(p - 1).

PAdicInteger(p:Integer) == InnerPAdicInteger(p,true$Boolean)
```

———-

— PADIC.dotabb —

```
"PADIC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PADIC"]
"PADICCT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PADICCT"]
"PADIC" -> "PADICCT"
```

———-

17.2 domain PADICRAT PAdicRational

— PAdicRational.input —

```
)set break resume
)sys rm -f PAdicRational.output
)spool PAdicRational.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PAdicRational
--R
--R PAdicRational(p: Integer)  is a domain constructor
--R Abbreviation for PAdicRational is PADICRAT
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PADICRAT
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,PAdicInteger(p)) -> %        ?*? : (PAdicInteger(p),%) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
```

```
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean        coerce : PAdicInteger(p) -> %
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R denom : % -> PAdicInteger(p)          denominator : % -> %
--R factor : % -> Factored(%)             gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R numer : % -> PAdicInteger(p)          numerator : % -> %
--R one? : % -> Boolean                   prime? : % -> Boolean
--R ?quo? : (%,%) -> %                    recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %                    removeZeroes : (Integer,%) -> %
--R removeZeroes : % -> %                 retract : % -> PAdicInteger(p)
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)         squareFreePart : % -> %
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (PAdicInteger(p),PAdicInteger(p)) -> %
--R ?<? : (%,%) -> Boolean if PAdicInteger(p) has ORDSET
--R ?<=? : (%,%) -> Boolean if PAdicInteger(p) has ORDSET
--R ?>? : (%,%) -> Boolean if PAdicInteger(p) has ORDSET
--R ?>=? : (%,%) -> Boolean if PAdicInteger(p) has ORDSET
--R D : (%,(PAdicInteger(p) -> PAdicInteger(p))) -> %
--R D : (%,(PAdicInteger(p) -> PAdicInteger(p)),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if PAdicInteger(p) has DIFRING
--R D : % -> % if PAdicInteger(p) has DIFRING
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if PAdicInteger(p) has OINTDOM
--R approximate : (%,Integer) -> Fraction(Integer)
--R ceiling : % -> PAdicInteger(p) if PAdicInteger(p) has INS
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and PAdicInteger(p) has PFECAT or PAdicInteger(p) ha
--R coerce : Symbol -> % if PAdicInteger(p) has RETRACT(SYMBOL)
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and PAdicInteger(p) has PFECAT
--R continuedFraction : % -> ContinuedFraction(Fraction(Integer))
--R convert : % -> DoubleFloat if PAdicInteger(p) has REAL
--R convert : % -> Float if PAdicInteger(p) has REAL
--R convert : % -> InputForm if PAdicInteger(p) has KONVERT(INFORM)
--R convert : % -> Pattern(Float) if PAdicInteger(p) has KONVERT(PATTERN(FLOAT))
--R convert : % -> Pattern(Integer) if PAdicInteger(p) has KONVERT(PATTERN(INT))
--R differentiate : (%,(PAdicInteger(p) -> PAdicInteger(p))) -> %
--R differentiate : (%,(PAdicInteger(p) -> PAdicInteger(p)),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if PAdicInteger(p) has PDRING(SYMBOL)
```

```
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if PAdicInteger(p) has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if PAdicInteger(p) has DIFRING
--R differentiate : % -> % if PAdicInteger(p) has DIFRING
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R ?.? : (%,PAdicInteger(p)) -> % if PAdicInteger(p) has ELTAB(PADIC(p),PADIC(p))
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,Symbol,PAdicInteger(p)) -> % if PAdicInteger(p) has IEVALAB(SYMBOL,PADIC(p))
--R eval : (%,List(Symbol),List(PAdicInteger(p))) -> % if PAdicInteger(p) has IEVALAB(SYMBOL,PAD
--R eval : (%,List(Equation(PAdicInteger(p)))) -> % if PAdicInteger(p) has EVALAB(PADIC(p))
--R eval : (%,Equation(PAdicInteger(p))) -> % if PAdicInteger(p) has EVALAB(PADIC(p))
--R eval : (%,PAdicInteger(p),PAdicInteger(p)) -> % if PAdicInteger(p) has EVALAB(PADIC(p))
--R eval : (%,List(PAdicInteger(p)),List(PAdicInteger(p))) -> % if PAdicInteger(p) has EVALAB(PA
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R floor : % -> PAdicInteger(p) if PAdicInteger(p) has INS
--R fractionPart : % -> % if PAdicInteger(p) has EUCDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R init : () -> % if PAdicInteger(p) has STEP
--R map : ((PAdicInteger(p) -> PAdicInteger(p)),%) -> %
--R max : (%,%) -> % if PAdicInteger(p) has ORDSET
--R min : (%,%) -> % if PAdicInteger(p) has ORDSET
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R negative? : % -> Boolean if PAdicInteger(p) has OINTDOM
--R nextItem : % -> Union(%,"failed") if PAdicInteger(p) has STEP
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R positive? : % -> Boolean if PAdicInteger(p) has OINTDOM
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if PAdicInteger(p) has INS
--R reducedSystem : Matrix(%) -> Matrix(PAdicInteger(p))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(PAdicInteger(p)),vec: Vector(PAd
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if PAdicInteger(p) has LINEXP(INT)
--R retract : % -> Integer if PAdicInteger(p) has RETRACT(INT)
--R retract : % -> Fraction(Integer) if PAdicInteger(p) has RETRACT(INT)
--R retract : % -> Symbol if PAdicInteger(p) has RETRACT(SYMBOL)
--R retractIfCan : % -> Union(Integer,"failed") if PAdicInteger(p) has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if PAdicInteger(p) has RETRACT(INT)
--R retractIfCan : % -> Union(Symbol,"failed") if PAdicInteger(p) has RETRACT(SYMBOL)
--R retractIfCan : % -> Union(PAdicInteger(p),"failed")
--R sign : % -> Integer if PAdicInteger(p) has OINTDOM
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynom
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(
--R subtractIfCan : (%,%) -> Union(%,"failed")
```

```
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R wholePart : % -> PAdicInteger(p) if PAdicInteger(p) has EUCDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— **PAdicRational.help** —

```
=====================================================================
PAdicRational examples
=====================================================================

See Also:
o )show PAdicRational
```

———-

17.2.1 PAdicRational (PADICRAT)



See

⇒ “InnerPAdicInteger” (IPADIC) 10.24.1 on page 1262
⇒ “PAdicInteger” (PADIC) 17.1.1 on page 1847
⇒ “BalancedPAdicInteger” (BPADIC) 3.2.1 on page 242
⇒ “PAdicRationalConstructor” (PADICRC) 17.3.1 on page 1856
⇒ “BalancedPAdicRational” (BPADICRT) 3.3.1 on page 246

Exports:

0	1	abs
approximate	associates?	ceiling
characteristic	charthRoot	coerce
conditionP	continuedFraction	convert
D	denom	denominator
differentiate	divide	euclideanSize
eval	expressIdealMember	exquo
extendedEuclidean	factor	factorPolynomial
factorSquareFreePolynomial	floor	fractionPart
gcd	gcdPolynomial	hash
init	inv	latex
lcm	map	max
min	multiEuclidean	negative?
nextItem	numer	numerator
one?	patternMatch	positive?
prime?	principalIdeal	random
recip	reducedSystem	removeZeroes
retract	retractIfCan	sample
sign	sizeLess?	solveLinearPolynomialEquation
squareFree	squareFreePart	squareFreePolynomial
subtractIfCan	unit?	unitCanonical
unitNormal	wholePart	zero?
?*?	?**?	?+?
?-?	-?	?/?
?=?	?^?	?~=?
?<?	?<=?	?>?
?>=?	?.?	?quo?
?rem?		

— domain PADICRAT PAdicRational —

```
)abbrev domain PADICRAT PAdicRational
++ Author: Clifton J. Williamson
++ Date Created: 15 May 1990
++ Date Last Updated: 15 May 1990
++ Keywords: p-adic, complementation
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: p-adic, completion
++ Examples:
++ References:
++ Description:
++ Stream-based implementation of Qp: numbers are represented as
++ sum(i = k.., a[i] * p^i) where the a[i] lie in 0,1,...,(p - 1).

PAdicRational(p:Integer) == PAdicRationalConstructor(p,PAdicInteger p)
```

———-

— **PADICRAT.dotabb** —

```
"PADICRAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PADICRAT"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"PADICRAT" -> "PFECAT"
```

———-

17.3 domain PADICRC PAdicRationalConstructor

— **PAdicRationalConstructor.input** —

```
)set break resume
)sys rm -f PAdicRationalConstructor.output
)spool PAdicRationalConstructor.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PAdicRationalConstructor
--R
--R PAdicRationalConstructor(p: Integer,PADIC: PAdicIntegerCategory(p))  is a domain constructor
--R Abbreviation for PAdicRationalConstructor is PADICRC
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PADICRC
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,PADIC) -> %                  ?*? : (PADIC,%) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (PADIC,PADIC) -> %              ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                D : (%,(PADIC -> PADIC)) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean        coerce : PADIC -> %
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
```

```
--R denom : % -> PADIC                    denominator : % -> %
--R factor : % -> Factored(%)             gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R map : ((PADIC -> PADIC),%) -> %       numer : % -> PADIC
--R numerator : % -> %                    one? : % -> Boolean
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R removeZeroes : (Integer,%) -> %       removeZeroes : % -> %
--R retract : % -> PADIC                  sample : () -> %
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               unit? : % -> Boolean
--R unitCanonical : % -> %                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?<? : (%,%) -> Boolean if PADIC has ORDSET
--R ?<=? : (%,%) -> Boolean if PADIC has ORDSET
--R ?>? : (%,%) -> Boolean if PADIC has ORDSET
--R ?>=? : (%,%) -> Boolean if PADIC has ORDSET
--R D : (%,(PADIC -> PADIC),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if PADIC has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if PADIC has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if PADIC has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if PADIC has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if PADIC has DIFRING
--R D : % -> % if PADIC has DIFRING
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if PADIC has OINTDOM
--R approximate : (%,Integer) -> Fraction(Integer)
--R ceiling : % -> PADIC if PADIC has INS
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and PADIC has PFECAT or PADIC has CHARNZ
--R coerce : Symbol -> % if PADIC has RETRACT(SYMBOL)
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and PADIC has PFECAT
--R continuedFraction : % -> ContinuedFraction(Fraction(Integer))
--R convert : % -> DoubleFloat if PADIC has REAL
--R convert : % -> Float if PADIC has REAL
--R convert : % -> InputForm if PADIC has KONVERT(INFORM)
--R convert : % -> Pattern(Float) if PADIC has KONVERT(PATTERN(FLOAT))
--R convert : % -> Pattern(Integer) if PADIC has KONVERT(PATTERN(INT))
--R differentiate : (%,(PADIC -> PADIC)) -> %
--R differentiate : (%,(PADIC -> PADIC),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if PADIC has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if PADIC has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if PADIC has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if PADIC has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if PADIC has DIFRING
--R differentiate : % -> % if PADIC has DIFRING
```

```
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R ?.? : (%,PADIC) -> % if PADIC has ELTAB(PADIC,PADIC)
--R euclideanSize : % -> NonNegativeInteger
--R eval : (%,Symbol,PADIC) -> % if PADIC has IEVALAB(SYMBOL,PADIC)
--R eval : (%,List(Symbol),List(PADIC)) -> % if PADIC has IEVALAB(SYMBOL,PADIC)
--R eval : (%,List(Equation(PADIC))) -> % if PADIC has EVALAB(PADIC)
--R eval : (%,Equation(PADIC)) -> % if PADIC has EVALAB(PADIC)
--R eval : (%,PADIC,PADIC) -> % if PADIC has EVALAB(PADIC)
--R eval : (%,List(PADIC),List(PADIC)) -> % if PADIC has EVALAB(PADIC)
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if PADIC has
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) i
--R floor : % -> PADIC if PADIC has INS
--R fractionPart : % -> % if PADIC has EUCDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynom
--R init : () -> % if PADIC has STEP
--R max : (%,%) -> % if PADIC has ORDSET
--R min : (%,%) -> % if PADIC has ORDSET
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R negative? : % -> Boolean if PADIC has OINTDOM
--R nextItem : % -> Union(%,"failed") if PADIC has STEP
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if PADIC ha
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if PA
--R positive? : % -> Boolean if PADIC has OINTDOM
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R random : () -> % if PADIC has INS
--R reducedSystem : Matrix(%) -> Matrix(PADIC)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(PADIC),vec: Vector(PADIC))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if PADIC has
--R reducedSystem : Matrix(%) -> Matrix(Integer) if PADIC has LINEXP(INT)
--R retract : % -> Integer if PADIC has RETRACT(INT)
--R retract : % -> Fraction(Integer) if PADIC has RETRACT(INT)
--R retract : % -> Symbol if PADIC has RETRACT(SYMBOL)
--R retractIfCan : % -> Union(Integer,"failed") if PADIC has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if PADIC has RETRACT(INT)
--R retractIfCan : % -> Union(Symbol,"failed") if PADIC has RETRACT(SYMBOL)
--R retractIfCan : % -> Union(PADIC,"failed")
--R sign : % -> Integer if PADIC has OINTDOM
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if PADIC
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R wholePart : % -> PADIC if PADIC has EUCDOM
--R
--E 1

)spool
```

```
)lisp (bye)
```

———-


— **PAdicRationalConstructor.help** —

```
==========================================================================
PAdicRationalConstructor examples
==========================================================================

See Also:
o )show PAdicRationalConstructor
```

———-

17.3.1 PAdicRationalConstructor (PADICRC)



See

⇒ “InnerPAdicInteger” (IPADIC) 10.24.1 on page 1262
⇒ “PAdicInteger” (PADIC) 17.1.1 on page 1847
⇒ “BalancedPAdicInteger” (BPADIC) 3.2.1 on page 242
⇒ “PAdicRational” (PADICRAT) 17.2.1 on page 1851
⇒ “BalancedPAdicRational” (BPADICRT) 3.3.1 on page 246

Exports:

0	1	abs
approximate	associates?	ceiling
characteristic	charthRoot	coerce
conditionP	continuedFraction	convert
D	denom	denominator
differentiate	divide	euclideanSize
eval	expressIdealMember	exquo
extendedEuclidean	factor	factorPolynomial
factorSquareFreePolynomial	floor	fractionPart
gcd	gcdPolynomial	gcd
hash	init	inv
latex	lcm	map
max	min	multiEuclidean
negative?	nextItem	numer
numerator	one?	patternMatch
positive?	prime?	principalIdeal
random	recip	reducedSystem
removeZeroes	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
zero?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?.?
?quo?	?rem?	

— domain PADICRC PAdicRationalConstructor —

```
)abbrev domain PADICRC PAdicRationalConstructor
++ Author: Clifton J. Williamson
++ Date Created: 10 May 1990
++ Date Last Updated: 10 May 1990
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Keywords: p-adic, completion
++ Examples:
++ References:
++ Description:
++ This is the category of stream-based representations of Qp.

PAdicRationalConstructor(p,PADIC): Exports == Implementation where
  p     :   Integer
```

```
  PADIC :   PAdicIntegerCategory p
  CF    ==> ContinuedFraction
  I     ==> Integer
  NNI   ==> NonNegativeInteger
  OUT   ==> OutputForm
  L     ==> List
  RN    ==> Fraction Integer
  ST    ==> Stream

  Exports ==> QuotientFieldCategory(PADIC) with
    approximate: (%,I) -> RN
      ++ \spad{approximate(x,n)} returns a rational number y such that
      ++ \spad{y = x (mod p^n)}.
    continuedFraction: % -> CF RN
      ++ \spad{continuedFraction(x)} converts the p-adic rational number x
      ++ to a continued fraction.
    removeZeroes: % -> %
      ++ \spad{removeZeroes(x)} removes leading zeroes from the
      ++ representation of the p-adic rational \spad{x}.
      ++ A p-adic rational is represented by (1) an exponent and
      ++ (2) a p-adic integer which may have leading zero digits.
      ++ When the p-adic integer has a leading zero digit, a 'leading zero'
      ++ is removed from the p-adic rational as follows:
      ++ the number is rewritten by increasing the exponent by 1 and
      ++ dividing the p-adic integer by p.
      ++ Note: \spad{removeZeroes(f)} removes all leading zeroes from f.
    removeZeroes: (I,%) -> %
      ++ \spad{removeZeroes(n,x)} removes up to n leading zeroes from
      ++ the p-adic rational \spad{x}.

  Implementation ==> add

    PEXPR := p :: OUT

--% representation

    Rep := Record(expon:I,pint:PADIC)

    getExpon: % -> I
    getZp   : % -> PADIC
    makeQp  : (I,PADIC) -> %

    getExpon x    == x.expon
    getZp x       == x.pint
    makeQp(r,int) == [r,int]

--% creation

    0 == makeQp(0,0)
    1 == makeQp(0,1)
```

```
    coerce(x:I)     == x :: PADIC :: %
    coerce(r:RN)    == (numer(r) :: %)/(denom(r) :: %)
    coerce(x:PADIC) == makeQp(0,x)

--% normalizations

    removeZeroes x ==
      empty? digits(xx := getZp x) => 0
      zero? moduloP xx =>
        removeZeroes makeQp(getExpon x + 1,quotientByP xx)
      x

    removeZeroes(n,x) ==
      n <= 0 => x
      empty? digits(xx := getZp x) => 0
      zero? moduloP xx =>
        removeZeroes(n - 1,makeQp(getExpon x + 1,quotientByP xx))
      x

--% arithmetic

    x = y ==
      EQ(x,y)$Lisp => true
      n := getExpon(x) - getExpon(y)
      n >= 0 =>
        (p**(n :: NNI) * getZp(x)) = getZp(y)
      (p**((- n) :: NNI) * getZp(y)) = getZp(x)

    x + y ==
      n := getExpon(x) - getExpon(y)
      n >= 0 =>
        makeQp(getExpon y,getZp(y) + p**(n :: NNI) * getZp(x))
      makeQp(getExpon x,getZp(x) + p**((-n) :: NNI) * getZp(y))

    -x == makeQp(getExpon x,-getZp(x))

    x - y ==
      n := getExpon(x) - getExpon(y)
      n >= 0 =>
        makeQp(getExpon y,p**(n :: NNI) * getZp(x) - getZp(y))
      makeQp(getExpon x,getZp(x) - p**((-n) :: NNI) * getZp(y))

    n:I * x:% == makeQp(getExpon x,n * getZp x)
    x:% * y:% == makeQp(getExpon x + getExpon y,getZp x * getZp y)

    x:% ** n:I ==
      zero? n => 1
      positive? n => expt(x,n :: PositiveInteger)$RepeatedSquaring(%)
      inv expt(x,(-n) :: PositiveInteger)$RepeatedSquaring(%)
```

```
    recip x ==
      x := removeZeroes(1000,x)
      zero? moduloP(xx := getZp x) => "failed"
      (inv := recip xx) case "failed" => "failed"
      makeQp(- getExpon x,inv :: PADIC)

    inv x ==
      (inv := recip x) case "failed" => error "inv: no inverse"
      inv :: %

    x:% / y:% == x * inv y
    x:PADIC / y:PADIC == (x :: %) / (y :: %)
    x:PADIC * y:% == makeQp(getExpon y,x * getZp y)

    approximate(x,n) ==
      k := getExpon x
      (p :: RN) ** k * approximate(getZp x,n - k)

    cfStream: % -> Stream RN
    cfStream x == delay
--    zero? x => empty()
      invx := inv x; x0 := approximate(invx,1)
      concat(x0,cfStream(invx - (x0 :: %)))

    continuedFraction x ==
      x0 := approximate(x,1)
      reducedContinuedFraction(x0,cfStream(x - (x0 :: %)))

    termOutput:(I,I) -> OUT
    termOutput(k,c) ==
      k = 0 => c :: OUT
      mon := (k = 1 => PEXPR; PEXPR ** (k :: OUT))
      c = 1 => mon
      c = -1 => -mon
      (c :: OUT) * mon

    showAll?:() -> Boolean
    -- check a global Lisp variable
    showAll?() == true

    coerce(x:%):OUT ==
      x := removeZeroes(_$streamCount$Lisp,x)
      m := getExpon x; zp := getZp x
      uu := digits zp
      l : L OUT := empty()
      empty? uu => 0 :: OUT
      n : NNI ; count : NNI := _$streamCount$Lisp
      for n in 0..count while not empty? uu repeat
        if frst(uu) ^= 0 then
```

```
          l := concat(termOutput((n :: I) + m,frst(uu)),l)
        uu := rst uu
      if showAll?() then
        for n in (count + 1).. while explicitEntries? uu and _
              not eq?(uu,rst uu) repeat
          if frst(uu) ^= 0 then
            l := concat(termOutput((n::I) + m,frst(uu)),l)
          uu := rst uu
      l :=
        explicitlyEmpty? uu => l
        eq?(uu,rst uu) and frst uu = 0 => l
        concat(prefix("O" :: OUT,[PEXPR ** ((n :: I) + m) :: OUT]),l)
      empty? l => 0 :: OUT
      reduce("+",reverse_! l)
```

———-

— PADICRC.dotabb —

```
"PADICRC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PADICRC"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"PADICRC" -> "PFECAT"
```

———-

17.4 domain PALETTE Palette

— Palette.input —

```
)set break resume
)sys rm -f Palette.output
)spool Palette.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Palette
--R Palette  is a domain constructor
--R Abbreviation for Palette is PALETTE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PALETTE
--R
--R------------------------------ Operations --------------------------------
```

```
--R ?=? : (%,%) -> Boolean                bright : Color -> %
--R coerce : Color -> %                   coerce : % -> OutputForm
--R dark : Color -> %                     dim : Color -> %
--R hash : % -> SingleInteger             hue : % -> Color
--R latex : % -> String                   light : Color -> %
--R pastel : Color -> %                   shade : % -> Integer
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Palette.help** —

```
========================================================================
Palette examples
========================================================================

See Also:
o )show Palette
```

———-

17.4.1 Palette (PALETTE)



See

⇒ “Color” (COLOR) 4.6.1 on page 394

Exports:

bright	coerce	dark	dim	hash
hue	latex	light	pastel	shade
?~=?	?=?			

— domain PALETTE Palette —

```
)abbrev domain PALETTE Palette
++ Author: Jim Wen
++ Date Created: May 10th 1989
++ Date Last Updated: Jan 19th 1990
++ Basic Operations: dark, dim, bright, pastel, light, hue, shade, coerce
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: dim,bright,pastel,coerce
++ References:
++ Description:
++ This domain describes four groups of color shades (palettes).

Palette(): Exports == Implementation where
  I      ==> Integer
  C      ==> Color
  SHADE  ==> ["Dark","Dim","Bright","Pastel","Light"]

  Exports ==> SetCategory with
    dark   : C  -> %
      ++ dark(c) sets the shade of the indicated hue of c to it's lowest value.
    dim    : C  -> %
      ++ dim(c) sets the shade of a hue, c,  above dark, but below bright.
    bright : C  -> %
      ++ bright(c) sets the shade of a hue, c, above dim, but below pastel.
    pastel : C  -> %
      ++ pastel(c) sets the shade of a hue, c,  above bright, but below light.
    light  : C  -> %
      ++ light(c) sets the shade of a hue, c,  to it's highest value.
    hue    : %  -> C
      ++ hue(p) returns the hue field of the indicated palette p.
    shade  : %  -> I
      ++ shade(p) returns the shade index of the indicated palette p.
    coerce : C  -> %
      ++ coerce(c) sets the average shade for the palette to that of the
      ++ indicated color c.

  Implementation ==> add
    Rep := Record(shadeField:I, hueField:C)

    dark   c == [1,c]
    dim    c == [2,c]
    bright c == [3,c]
    pastel c == [4,c]
    light  c == [5,c]
    hue    p == p.hueField
    shade  p == p.shadeField
```

```
    sample() == bright(sample())
    coerce(c:Color):% == bright c
    coerce(p:%):OutputForm ==
      hconcat ["[",coerce(p.hueField),"] from the ",_
               SHADE.(p.shadeField)," palette"]
```

———-

— PALETTE.dotabb —

```
"PALETTE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PALETTE"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"PALETTE" -> "BASTYPE"
"PALETTE" -> "KOERCE"
```

———-

17.5 domain PARPCURV ParametricPlaneCurve

— ParametricPlaneCurve.input —

```
)set break resume
)sys rm -f ParametricPlaneCurve.output
)spool ParametricPlaneCurve.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ParametricPlaneCurve
--R
--R ParametricPlaneCurve(ComponentFunction: Type)  is a domain constructor
--R Abbreviation for ParametricPlaneCurve is PARPCURV
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PARPCURV
--R
--R------------------------------ Operations --------------------------------
--R coordinate : (%,NonNegativeInteger) -> ComponentFunction
--R curve : (ComponentFunction,ComponentFunction) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **ParametricPlaneCurve.help** —

```
====================================================================
ParametricPlaneCurve examples
====================================================================

See Also:
o )show ParametricPlaneCurve
```

———-

17.5.1 ParametricPlaneCurve (PARPCURV)



See

⇒ “ParametricSpaceCurve” (PARSCURV) 17.6.1 on page 1867
⇒ “ParametricSurface” (PARSURF) 17.7.1 on page 1870

Exports:
coordinate curve

— **domain PARPCURV ParametricPlaneCurve** —

```
)abbrev domain PARPCURV ParametricPlaneCurve
++ Author: Clifton J. Williamson
++ Date Created: 24 May 1990
++ Date Last Updated: 24 May 1990
++ Basic Operations: curve, coordinate
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: parametric curve, graphics
++ References:
```

```
++ Description:
++ ParametricPlaneCurve is used for plotting parametric plane
++ curves in the affine plane.

ParametricPlaneCurve(ComponentFunction): Exports == Implementation where
  ComponentFunction : Type
  NNI             ==> NonNegativeInteger

  Exports ==> with
    curve: (ComponentFunction,ComponentFunction) -> %
      ++ curve(c1,c2) creates a plane curve from 2 component functions \spad{c1}
      ++ and \spad{c2}.
    coordinate: (%,NNI) -> ComponentFunction
      ++ coordinate(c,i) returns a coordinate function for c using 1-based
      ++ indexing according to i. This indicates what the function for the
      ++ coordinate component i of the plane curve is.

  Implementation ==> add

    Rep := Record(xCoord:ComponentFunction,yCoord:ComponentFunction)

    curve(x,y) == [x,y]
    coordinate(c,n) ==
      n = 1 => c.xCoord
      n = 2 => c.yCoord
      error "coordinate: index out of bounds"
```

— PARPCURV.dotabb —

```
"PARPCURV" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PARPCURV"]
"TYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TYPE"]
"PARPCURV" -> "TYPE"
```

17.6 domain PARSCURV ParametricSpaceCurve

— ParametricSpaceCurve.input —

```
)set break resume
)sys rm -f ParametricSpaceCurve.output
)spool ParametricSpaceCurve.output
```

```
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ParametricSpaceCurve
--R
--R ParametricSpaceCurve(ComponentFunction: Type)  is a domain constructor
--R Abbreviation for ParametricSpaceCurve is PARSCURV
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PARSCURV
--R
--R------------------------------ Operations --------------------------------
--R coordinate : (%,NonNegativeInteger) -> ComponentFunction
--R curve : (ComponentFunction,ComponentFunction,ComponentFunction) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **ParametricSpaceCurve.help** —

```
=====================================================================
ParametricSpaceCurve examples
=====================================================================

See Also:
o )show ParametricSpaceCurve
```

———-

17.6.1 ParametricSpaceCurve (PARSCURV)



See

⇒ "ParametricPlaneCurve" (PARPCURV) 17.5.1 on page 1865
⇒ "ParametricSurface" (PARSURF) 17.7.1 on page 1870

Exports:
coordinate curve

— domain PARSCURV ParametricSpaceCurve —

```
)abbrev domain PARSCURV ParametricSpaceCurve
++ Author: Clifton J. Williamson
++ Date Created: 24 May 1990
++ Date Last Updated: 24 May 1990
++ Basic Operations: curve, coordinate
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: parametric curve, graphics
++ References:
++ Description:
++ ParametricSpaceCurve is used for plotting parametric space
++ curves in affine 3-space.

ParametricSpaceCurve(ComponentFunction): Exports == Implementation where
  ComponentFunction : Type
  NNI             ==> NonNegativeInteger

  Exports ==> with
    curve: (ComponentFunction,ComponentFunction,ComponentFunction) -> %
      ++ curve(c1,c2,c3) creates a space curve from 3 component functions
      ++ \spad{c1}, \spad{c2}, and \spad{c3}.
    coordinate: (%,NNI) -> ComponentFunction
      ++ coordinate(c,i) returns a coordinate function of c using 1-based
      ++ indexing according to i. This indicates what the function for the
      ++ coordinate component, i, of the space curve is.

  Implementation ==> add

    Rep := Record(xCoord:ComponentFunction,_
                  yCoord:ComponentFunction,_
                  zCoord:ComponentFunction)

    curve(x,y,z) == [x,y,z]
    coordinate(c,n) ==
      n = 1 => c.xCoord
      n = 2 => c.yCoord
      n = 3 => c.zCoord
      error "coordinate: index out of bounds"
```

———-

— **PARSCURV.dotabb** —

```
"PARSCURV" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PARSCURV"]
"TYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TYPE"]
"PARSCURV" -> "TYPE"
```

———-

17.7 domain PARSURF ParametricSurface

— **ParametricSurface.input** —

```
)set break resume
)sys rm -f ParametricSurface.output
)spool ParametricSurface.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ParametricSurface
--R
--R ParametricSurface(ComponentFunction: Type)  is a domain constructor
--R Abbreviation for ParametricSurface is PARSURF
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PARSURF
--R
--R------------------------------ Operations --------------------------------
--R coordinate : (%,NonNegativeInteger) -> ComponentFunction
--R surface : (ComponentFunction,ComponentFunction,ComponentFunction) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-

— **ParametricSurface.help** —


```
==========================================================================
```

```
ParametricSurface examples
==========================================================================

See Also:
o )show ParametricSurface
```

———-

17.7.1 ParametricSurface (PARSURF)



See

⇒ “ParametricPlaneCurve” (PARPCURV) 17.5.1 on page 1865
⇒ “ParametricSpaceCurve” (PARSCURV) 17.6.1 on page 1867

Exports:
coordinate surface

— domain PARSURF ParametricSurface —

```
)abbrev domain PARSURF ParametricSurface
++ Author: Clifton J. Williamson
++ Date Created: 24 May 1990
++ Date Last Updated: 24 May 1990
++ Basic Operations: surface, coordinate
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: parametric surface, graphics
++ References:
++ Description:
++ ParametricSurface is used for plotting parametric surfaces in
++ affine 3-space.

ParametricSurface(ComponentFunction): Exports == Implementation where
  ComponentFunction : Type
```

```
  NNI             ==> NonNegativeInteger

  Exports ==> with
    surface: (ComponentFunction,ComponentFunction,ComponentFunction) -> %
      ++ surface(c1,c2,c3) creates a surface from 3 parametric component
      ++ functions \spad{c1}, \spad{c2}, and \spad{c3}.
    coordinate: (%,NNI) -> ComponentFunction
      ++ coordinate(s,i) returns a coordinate function of s using 1-based
      ++ indexing according to i.  This indicates what the function for the
      ++ coordinate component, i, of the surface is.

  Implementation ==> add

    Rep := Record(xCoord:ComponentFunction,_
                  yCoord:ComponentFunction,_
                  zCoord:ComponentFunction)

    surface(x,y,z) == [x,y,z]
    coordinate(c,n) ==
      n = 1 => c.xCoord
      n = 2 => c.yCoord
      n = 3 => c.zCoord
      error "coordinate: index out of bounds"
```

———-

— PARSURF.dotabb —

```
"PARSURF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PARSURF"]
"TYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TYPE"]
"PARSURF" -> "TYPE"
```

———-

17.8 domain PFR PartialFraction

— PartialFraction.input —

```
)set break resume
)sys rm -f PartialFraction.output
)spool PartialFraction.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 22
partialFraction(1,factorial 10)
--R
--R
--R        159   23   12   1
--R   (1)  --- - -- - -- + -
--R          8    4    2   7
--R         2    3    5
--R                                              Type: PartialFraction(Integer)
--E 1

--S 2 of 22
f := padicFraction(%)
--R
--R
--R        1    1    1    1    1    1    2    1    2   2    2   1
--R   (2)  - + -- + -- + -- + -- + -- - -- - -- - -- - - - - -- + -
--R        2    4    5    6    7    8    2    3    4   5    2   7
--R             2    2    2    2    2    3    3    3        5
--R                                              Type: PartialFraction(Integer)
--E 2

--S 3 of 22
compactFraction(f)
--R
--R
--R        159   23   12   1
--R   (3)  --- - -- - -- + -
--R          8    4    2   7
--R         2    3    5
--R                                              Type: PartialFraction(Integer)
--E 3

--S 4 of 22
numberOfFractionalTerms(f)
--R
--R
--R   (4)  12
--R                                                 Type: PositiveInteger
--E 4

--S 5 of 22
nthFractionalTerm(f,3)
--R
--R
--R         1
--R   (5)  --
--R         5
--R        2
```

```
--R                                                  Type: PartialFraction(Integer)
--E 5

--S 6 of 22
partialFraction(1,- 13 + 14 * %i)
--R
--R
--R             1         4
--R   (6)  - ------- + -------
--R          1 + 2%i   3 + 8%i
--R                                       Type: PartialFraction(Complex(Integer))
--E 6

--S 7 of 22
% :: Fraction Complex Integer
--R
--R
--R              %i
--R   (7)  - ----------
--R          14 + 13%i
--R                                                Type: Fraction(Complex(Integer))
--E 7

--S 8 of 22
u : FR UP(x, FRAC INT) := reduce(*,[primeFactor(x+i,i) for i in 1..4])
--R
--R
--R                       2       3       4
--R   (8)  (x + 1)(x + 2) (x + 3) (x + 4)
--R                     Type: Factored(UnivariatePolynomial(x,Fraction(Integer)))
--E 8

--S 9 of 22
partialFraction(1,u)
--R
--R
--R   (9)
--R     1     1      7     17  2         139   607  3   10115  2   391     44179
--R    ---    - x + --   - -- x  - 12x - ---   --- x  + ----- x  + --- x + -----
--R    648    4     16      8              8    324       432        4       324
--R   ----- + -------- + ------------------- + ---------------------------------
--R   x + 1          2                3                           4
--R            (x + 2)          (x + 3)                     (x + 4)
--R              Type: PartialFraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 9

--S 10 of 22
padicFraction %
--R
--R
```

```
--R   (10)
--R       1       1         1        17        3          1       607       403
--R      ---      -        --        --        -          -       ---       ---
--R      648      4        16         8        4          2       324       432
--R     ----- + ----- - -------- - ----- + -------- - -------- + ----- + --------
--R     x + 1   x + 2          2   x + 3          2          3   x + 4          2
--R                     (x + 2)            (x + 3)    (x + 3)            (x + 4)
--R   +
--R        13          1
--R        --         --
--R        36         12
--R     -------- + --------
--R             3          4
--R     (x + 4)    (x + 4)
--R             Type: PartialFraction(UnivariatePolynomial(x,Fraction(Integer)))
--E 10

--S 11 of 22
fraction:=Fraction(Polynomial(Integer))
--R
--R
--R   (11)  Fraction(Polynomial(Integer))
--R                                                                  Type: Domain
--E 11

--S 12 of 22
up:=UnivariatePolynomial(y,fraction)
--R
--R
--R   (12)  UnivariatePolynomial(y,Fraction(Polynomial(Integer)))
--R                                                                  Type: Domain
--E 12

--S 13 of 22
pfup:=PartialFraction(up)
--R
--R
--R   (13)
--R   PartialFraction(UnivariatePolynomial(y,Fraction(Polynomial(Integer))))
--R                                                                  Type: Domain
--E 13

--S 14 of 22
a:=x+1/(y+1)
--R
--R
--R         x y + x + 1
--R   (14)  -----------
--R            y + 1
--R                                        Type: Fraction(Polynomial(Integer))
```

```
--E 14

--S 15 of 22
b:=partialFraction(a,y)$PartialFractionPackage(Integer)
--R
--R
--R               1
--R   (15)  x + -----
--R             y + 1
--R Type: PartialFraction(UnivariatePolynomial(y,Fraction(Polynomial(Integer))))
--E 15

--S 16 of 22
c:=b::pfup
--R
--R
--R               1
--R   (16)  x + -----
--R             y + 1
--R Type: PartialFraction(UnivariatePolynomial(y,Fraction(Polynomial(Integer))))
--E 16

--S 17 of 22
cw:=(wholePart c)::Expression(Integer)
--R
--R
--R   (17)  x
--R                                                  Type: Expression(Integer)
--E 17

--S 18 of 22
m:=numberOfFractionalTerms(c)
--R
--R
--R   (18)  1
--R                                                     Type: PositiveInteger
--E 18

--S 19 of 22
crList:=[nthFractionalTerm(c,i) for i in 1..m]
--R
--R
--R            1
--R   (19)  [-----]
--R          y + 1
--RType: List(PartialFraction(UnivariatePolynomial(y,Fraction(Polynomial(Integer)))))
--E 19

--S 20 of 22
cc:=reduce(+,crList)
```

```
--R
--R
--R           1
--R   (20)  -----
--R         y + 1
--R Type: PartialFraction(UnivariatePolynomial(y,Fraction(Polynomial(Integer))))
--E 20

--S 21 of 22
ccx:=cc::(Fraction(up))::(Expression(Integer))
--R
--R
--R           1
--R   (21)  -----
--R         y + 1
--R                                                    Type: Expression(Integer)
--E 21

--S 22 of 22
sin(cw)*cos(ccx)+sin(ccx)*cos(cw)
--R
--R
--R               1                          1
--R   (22)  cos(-----)sin(x) + cos(x)sin(-----)
--R             y + 1                      y + 1
--R                                                    Type: Expression(Integer)
--E 22

)spool
)lisp (bye)
```

———-

— PartialFraction.help —

```
=====================================================================
PartialFraction examples
=====================================================================

A partial fraction is a decomposition of a quotient into a sum of
quotients where the denominators of the summands are powers of
primes. Most people first encounter partial fractions when they are
learning integral calculus.  For a technical discussion of partial
fractions, see, for example, Lang's Algebra. For example, the rational
number 1/6 is decomposed into 1/2-1/3.  You can compute partial
fractions of quotients of objects from domains belonging to the
category EuclideanDomain.  For example, Integer, Complex Integer, and
UnivariatePolynomial(x, Fraction Integer) all belong to EuclideanDomain.
In the examples following, we demonstrate how to decompose quotients of
```

each of these kinds of object into partial fractions.

It is necessary that we know how to factor the denominator when we want to compute a partial fraction. Although the interpreter can often do this automatically, it may be necessary for you to include a call to factor. In these examples, it is not necessary to factor the denominators explicitly.

The main operation for computing partial fractions is called partialFraction and we use this to compute a decomposition of 1/10!. The first argument to partialFraction is the numerator of the quotient and the second argument is the factored denominator.

```
  partialFraction(1,factorial 10)
    159   23   12   1
    --- - -- - -- + -
      8    4    2   7
     2    3    5
                          Type: PartialFraction Integer
```

Since the denominators are powers of primes, it may be possible to expand the numerators further with respect to those primes. Use the operation padicFraction to do this.

```
  f := padicFraction(%)
    1    1    1    1    1    1    2    1    2   2    2   1
    - + -- + -- + -- + -- + -- - -- - -- - -- - - - -- + -
    2    4    5    6    7    8    2    3    4   5    2   7
        2    2    2    2    2    3    3    3        5
                          Type: PartialFraction Integer
```

The operation compactFraction returns an expanded fraction into the usual form. The compacted version is used internally for computational efficiency.

```
  compactFraction(f)
    159   23   12   1
    --- - -- - -- + -
      8    4    2   7
     2    3    5
                          Type: PartialFraction Integer
```

You can add, subtract, multiply and divide partial fractions. In addition, you can extract the parts of the decomposition. numberOfFractionalTerms computes the number of terms in the fractional part. This does not include the whole part of the fraction, which you get by calling wholePart. In this example, the whole part is just 0.

```
  numberOfFractionalTerms(f)
    12
                          Type: PositiveInteger
```

The operation nthFractionalTerm returns the individual terms in the decomposition. Notice that the object returned is a partial fraction itself. firstNumer and firstDenom extract the numerator and denominator of the first term of the fraction.

```
nthFractionalTerm(f,3)
    1
   --
    5
   2
                          Type: PartialFraction Integer
```

Given two gaussian integers, you can decompose their quotient into a partial fraction.

```
partialFraction(1,- 13 + 14 * %i)
       1         4
  - ------- + -------
    1 + 2%i   3 + 8%i
                          Type: PartialFraction Complex Integer
```

To convert back to a quotient, simply use a conversion.

```
% :: Fraction Complex Integer
        %i
  - ---------
    14 + 13%i
                          Type: Fraction Complex Integer
```

To conclude this section, we compute the decomposition of

$$\frac{1}{(x+1)(x+2)^2(x+3)(x+4)}$$

The polynomials in this object have type UnivariatePolynomial(x, Fraction Integer).

We use the primeFactor operation to create the denominator in factored form directly.

```
u : FR UP(x, FRAC INT) := reduce(*,[primeFactor(x+i,i) for i in 1..4])
                2       3       4
  (x + 1)(x + 2) (x + 3) (x + 4)
                Type: Factored UnivariatePolynomial(x,Fraction Integer)
```

These are the compact and expanded partial fractions for the quotient.


```
partialFraction(1,u)
   1     1      7     17  2         139   607  3   10115  2   391     44179
  ---    - x + --   - -- x  - 12x - ---   --- x  + ----- x  + --- x + -----
  648    4     16      8             8    324       432        4       324
 ----- + -------- + ------------------- + ---------------------------------
 x + 1          2               3                           4
         (x + 2)          (x + 3)                     (x + 4)
            Type: PartialFraction UnivariatePolynomial(x,Fraction Integer)

padicFraction %
     1       1         1        17        3          1       607       403
    ---      -        --        --        -          -       ---       ---
    648      4        16         8        4          2       324       432
   ----- + ----- - -------- - ----- + -------- - -------- + ----- + --------
   x + 1   x + 2          2   x + 3          2          3   x + 4          2
                  (x + 2)            (x + 3)    (x + 3)            (x + 4)
 +
      13          1
      --         --
      36         12
    -------- + --------
           3          4
    (x + 4)    (x + 4)
            Type: PartialFraction UnivariatePolynomial(x,Fraction Integer)
```

See Also:
o)help Factored
o)help Complex
o)help FullPartialFractionExpansionXmpPage
o)show PartialFraction

———————-

17.8.1 PartialFraction (PFR)



Exports:

0	1	associates?	characteristic
coerce	compactFraction	divide	euclideanSize
expressIdealMember	exquo	extendedEuclidean	extendedEuclidean
factor	firstDenom	firstNumer	gcd
gcdPolynomial	hash	inv	latex
lcm	multiEuclidean	nthFractionalTerm	numberOfFractionalTerms
one?	padicallyExpand	padicFraction	partialFraction
prime?	principalIdeal	recip	sample
sizeLess?	squareFree	squareFreePart	subtractIfCan
unit?	unitCanonical	unitNormal	wholePart
zero?	?*?	?**?	?+?
?-?	-?	?/?	?=?
?^?	?~=?	?quo?	?rem?

— domain PFR PartialFraction —

```
)abbrev domain PFR PartialFraction
++ Author: Robert S. Sutor
++ Date Created: 1986
++ Change History:
++   05/20/91 BMT Converted to the new library
++ Basic Operations: (Field), (Algebra),
++   coerce, compactFraction, firstDenom, firstNumer,
++   nthFractionalTerm, numberOfFractionalTerms, padicallyExpand,
++   padicFraction, partialFraction, wholePart
++ Related Constructors:
++ Also See: ContinuedFraction
++ AMS Classifications:
++ Keywords: partial fraction, factorization, euclidean domain
++ References:
++ Description:
++ The domain \spadtype{PartialFraction} implements partial fractions
++ over a euclidean domain \spad{R}.  This requirement on the
```

```
++ argument domain allows us to normalize the fractions.  Of
++ particular interest are the 2 forms for these fractions.  The
++ ``compact'' form has only one fractional term per prime in the
++ denominator, while the ``p-adic'' form expands each numerator
++ p-adically via the prime p in the denominator.  For computational
++ efficiency, the compact form is used, though the p-adic form may
++ be gotten by calling the function padicFraction}.  For a
++ general euclidean domain, it is not known how to factor the
++ denominator.  Thus the function partialFraction takes as its
++ second argument an element of \spadtype{Factored(R)}.

PartialFraction(R: EuclideanDomain): Cat == Capsule where
  FRR  ==> Factored R
  SUPR ==> SparseUnivariatePolynomial R

  Cat == Join(Field, Algebra R) with
    coerce: % -> Fraction R
      ++ coerce(p) sums up the components of the partial fraction and
      ++ returns a single fraction.
      ++
      ++X a:=(13/74)::PFR(INT)
      ++X a::FRAC(INT)

    coerce:  Fraction FRR -> %
      ++ coerce(f) takes a fraction with numerator and denominator in
      ++ factored form and creates a partial fraction.  It is
      ++ necessary for the parts to be factored because it is not
      ++ known in general how to factor elements of \spad{R} and
      ++ this is needed to decompose into partial fractions.
      ++
      ++X (13/74)::PFR(INT)

    compactFraction: % -> %
      ++ compactFraction(p) normalizes the partial fraction \spad{p}
      ++ to the compact representation. In this form, the partial
      ++ fraction has only one fractional term per prime in the
      ++ denominator.
      ++
      ++X a:=partialFraction(1,factorial 10)
      ++X b:=padicFraction(a)
      ++X compactFraction(b)

    firstDenom: % -> FRR
      ++ firstDenom(p) extracts the denominator of the first fractional
      ++ term. This returns 1 if there is no fractional part (use
      ++ wholePart from PartialFraction to get the whole part).
      ++
      ++X a:=partialFraction(1,factorial 10)
      ++X firstDenom(a)
```

```
firstNumer:  % -> R
  ++ firstNumer(p) extracts the numerator of the first fractional
  ++ term. This returns 0 if there is no fractional part (use
  ++ wholePart from PartialFraction to get the whole part).
  ++
  ++X a:=partialFraction(1,factorial 10)
  ++X firstNumer(a)

nthFractionalTerm:  (%,Integer) -> %
  ++ nthFractionalTerm(p,n) extracts the nth fractional term from
  ++ the partial fraction \spad{p}.  This returns 0 if the index
  ++ \spad{n} is out of range.
  ++
  ++X a:=partialFraction(1,factorial 10)
  ++X b:=padicFraction(a)
  ++X nthFractionalTerm(b,3)

numberOfFractionalTerms: % -> Integer
  ++ numberOfFractionalTerms(p) computes the number of fractional
  ++ terms in \spad{p}. This returns 0 if there is no fractional
  ++ part.
  ++
  ++X a:=partialFraction(1,factorial 10)
  ++X b:=padicFraction(a)
  ++X numberOfFractionalTerms(b)

padicallyExpand: (R,R) -> SUPR
  ++ padicallyExpand(p,x) is a utility function that expands
  ++ the second argument \spad{x} ``p-adically'' in
  ++ the first.

padicFraction: % -> %
  ++ padicFraction(q) expands the fraction p-adically in the primes
  ++ \spad{p} in the denominator of \spad{q}. For example,
  ++ \spad{padicFraction(3/(2**2)) = 1/2 + 1/(2**2)}.
  ++ Use compactFraction from PartialFraction to
  ++ return to compact form.
  ++
  ++X a:=partialFraction(1,factorial 10)
  ++X padicFraction(a)

partialFraction: (R, FRR) -> %
  ++ partialFraction(numer,denom) is the main function for
  ++ constructing partial fractions. The second argument is the
  ++ denominator and should be factored.
  ++
  ++X partialFraction(1,factorial 10)

wholePart: % -> R
  ++ wholePart(p) extracts the whole part of the partial fraction
```

```
    ++ \spad{p}.
    ++
    ++X a:=(74/13)::PFR(INT)
    ++X wholePart(a)

Capsule == add

  -- some constructor assignments and macros

  Ex     ==> OutputForm
  fTerm  ==> Record(num: R, den: FRR)           -- den should have
                                                -- unit = 1 and only
                                                -- 1 factor
  LfTerm ==> List Record(num: R, den: FRR)
  QR     ==> Record(quotient: R, remainder: R)

  Rep    := Record(whole:R, fract: LfTerm)

  -- private function signatures

  copypf: % -> %
  LessThan: (fTerm, fTerm) -> Boolean
  multiplyFracTerms: (fTerm, fTerm) -> %
  normalizeFracTerm: fTerm -> %
  partialFractionNormalized: (R, FRR) -> %

  -- declarations

  a,b: %
  n: Integer
  r: R

  -- private function definitions

  copypf(a: %): % == [a.whole,copy a.fract]$%

  LessThan(s: fTerm, t: fTerm) ==
    -- have to wait until FR has < operation
    if (GGREATERP(s.den,t.den)$Lisp : Boolean) then false
    else true

  multiplyFracTerms(s : fTerm, t : fTerm) ==
    nthFactor(s.den,1) = nthFactor(t.den,1) =>
      normalizeFracTerm([s.num * t.num, s.den * t.den]$fTerm) : Rep
    i : Union(Record(coef1: R, coef2: R),"failed")
    coefs : Record(coef1: R, coef2: R)
    i := extendedEuclidean(expand t.den, expand s.den,s.num * t.num)
    i case "failed" => error "PartialFraction: not in ideal"
    coefs := (i :: Record(coef1: R, coef2: R))
    c : % := copypf 0$%
```

```
    d : %
    if coefs.coef2 ^= 0$R then
      c := normalizeFracTerm ([coefs.coef2, t.den]$fTerm)
    if coefs.coef1 ^= 0$R then
      d := normalizeFracTerm ([coefs.coef1, s.den]$fTerm)
      c.whole := c.whole + d.whole
      not (null d.fract) => c.fract := append(d.fract,c.fract)
    c

  normalizeFracTerm(s : fTerm) ==
    -- makes sure num is "less than" den, whole may be non-zero
    qr : QR := divide(s.num, (expand s.den))
    qr.remainder = 0$R => [qr.quotient, nil()$LfTerm]
    -- now verify num and den are coprime
    f : R := nthFactor(s.den,1)
    nexpon : Integer := nthExponent(s.den,1)
    expon  : Integer := 0
    q : QR := divide(qr.remainder, f)
    while (q.remainder = 0$R) and (expon < nexpon) repeat
      expon := expon + 1
      qr.remainder := q.quotient
      q := divide(qr.remainder,f)
    expon = 0 => [qr.quotient,[[qr.remainder, s.den]$fTerm]$LfTerm]
    expon = nexpon => (qr.quotient + qr.remainder) :: %
    [qr.quotient,[[qr.remainder, nilFactor(f,nexpon-expon)]$fTerm]$LfTerm]

  partialFractionNormalized(nm: R, dn : FRR) ==
    -- assume unit dn = 1
    nm = 0$R   => 0$%
    dn = 1$FRR => nm :: %
    qr : QR := divide(nm, expand dn)
    c : % := [0$R,[[qr.remainder,
      nilFactor(nthFactor(dn,1), nthExponent(dn,1))]$fTerm]$LfTerm]
    d : %
    for i in 2..numberOfFactors(dn) repeat
      d :=
        [0$R,[[1$R,nilFactor(nthFactor(dn,i), nthExponent(dn,i))]$fTerm]$LfTerm]
      c := c * d
    (qr.quotient :: %) + c

  -- public function definitions

  padicFraction(a : %) ==
    b: % := compactFraction a
    null b.fract => b
    l : LfTerm := nil
    s : fTerm
    f : R
    e,d: Integer
    for s in b.fract repeat
```

```
      e := nthExponent(s.den,1)
      e = 1 => l := cons(s,l)
      f := nthFactor(s.den,1)
      d := degree(sp := padicallyExpand(f,s.num))
      while (sp ^= 0$SUPR) repeat
        l := cons([leadingCoefficient sp,nilFactor(f,e-d)]$fTerm, l)
        d := degree(sp := reductum sp)
    [b.whole, sort(LessThan,l)]$%

  compactFraction(a : %) ==
    -- only one power for each distinct denom will remain
    2 > # a.fract => a
    af : LfTerm := reverse a.fract
    bf : LfTerm := nil
    bw : R := a.whole
    b : %
    s : fTerm := [(first af).num,(first af).den]$fTerm
    f : R := nthFactor(s.den,1)
    e : Integer := nthExponent(s.den,1)
    t : fTerm
    for t in rest af repeat
      f = nthFactor(t.den,1) =>
        s.num := s.num + (t.num *
          (f **$R ((e - nthExponent(t.den,1)) : NonNegativeInteger)))
      b := normalizeFracTerm s
      bw := bw + b.whole
      if not (null b.fract) then bf := cons(first b.fract,bf)
      s := [t.num, t.den]$fTerm
      f := nthFactor(s.den,1)
      e := nthExponent(s.den,1)
    b := normalizeFracTerm s
    [bw + b.whole,append(b.fract,bf)]$%

  0 == [0$R, nil()$LfTerm]
  1 == [1$R, nil()$LfTerm]
  characteristic() == characteristic()$R

  coerce(r): % == [r, nil()$LfTerm]
  coerce(n): % == [(n :: R), nil()$LfTerm]
  coerce(a): Fraction R ==
    q : Fraction R := (a.whole :: Fraction R)
    s : fTerm
    for s in a.fract repeat
      q := q + (s.num / (expand s.den))
    q
  coerce(q: Fraction FRR): % ==
    u : R := (recip unit denom q):: R
    r1 : R := u * expand numer q
    partialFractionNormalized(r1, u * denom q)
```

```
a exquo b ==
  b = 0$% => "failed"
  b = 1$% => a
  br : Fraction R := inv (b :: Fraction R)
  a * partialFraction(numer br,(denom br) :: FRR)
recip a == (1$% exquo a)

firstDenom a ==         -- denominator of 1st fractional term
  null a.fract => 1$FRR
  (first a.fract).den
firstNumer a ==         -- numerator of 1st fractional term
  null a.fract => 0$R
  (first a.fract).num
numberOfFractionalTerms a == # a.fract
nthFractionalTerm(a,n) ==
  l : LfTerm := a.fract
  (n < 1) or (n > # l) => 0$%
  [0$R,[l.n]$LfTerm]$%
wholePart a == a.whole

partialFraction(nm: R, dn : FRR) ==
  nm = 0$R => 0$%
  -- move inv unit of den to numerator
  u : R := unit dn
  u := (recip u) :: R
  partialFractionNormalized(u * nm,u * dn)

padicallyExpand(p : R, r : R) ==
  -- expands r as a sum of powers of p, with coefficients
  -- r = HornerEval(padicallyExpand(p,r),p)
  qr : QR := divide(r, p)
  qr.quotient = 0$R => qr.remainder :: SUPR
  (qr.remainder :: SUPR) + monomial(1$R,1$NonNegativeInteger)$SUPR *
    padicallyExpand(p,qr.quotient)

a = b ==
  a.whole ^= b.whole => false  -- must verify this
  (null a.fract) =>
    null b.fract => a.whole = b.whole
    false
  null b.fract => false
  -- oh, no! following is temporary
  (a :: Fraction R) = (b :: Fraction R)

- a ==
  s: fTerm
  l: LfTerm := nil
  for s in reverse a.fract repeat l := cons([- s.num,s.den]$fTerm,l)
  [- a.whole,l]
```

```
    r * a ==
      r = 0$R => 0$%
      r = 1$R => a
      b : % := (r * a.whole) :: %
      c : %
      s : fTerm
      for s in reverse a.fract repeat
        c := normalizeFracTerm [r * s.num, s.den]$fTerm
        b.whole := b.whole + c.whole
        not (null c.fract) => b.fract := append(c.fract, b.fract)
      b

    n * a == (n :: R) * a

    a + b ==
      compactFraction
        [a.whole + b.whole,
          sort(LessThan,append(a.fract,copy b.fract))]$%

    a * b ==
      null a.fract => a.whole * b
      null b.fract => b.whole * a
      af : % := [0$R, a.fract]$%   --     a - a.whole
      c: % := (a.whole * b) + (b.whole * af)
      s,t : fTerm
      for s in a.fract repeat
        for t in b.fract repeat
          c := c + multiplyFracTerms(s,t)
      c

    coerce(a): Ex ==
      null a.fract => a.whole :: Ex
      s : fTerm
      l : List Ex
      if a.whole = 0 then l := nil else l := [a.whole :: Ex]
      for s in a.fract repeat
        s.den = 1$FRR => l := cons(s.num :: Ex, l)
        l := cons(s.num :: Ex /  s.den :: Ex, l)
      # l = 1 => first l
      reduce("+", reverse l)
```

———-

— PFR.dotabb —

```
"PFR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PFR"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
```

```
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"PFR" -> "FIELD"
"PFR" -> "FLAGG-"
"PFR" -> "FLAGG"
```

———-

17.9 domain PRTITION Partition

— Partition.input —

```
)set break resume
)sys rm -f Partition.output
)spool Partition.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Partition
--R
--R Partition  is a domain constructor
--R Abbreviation for Partition is PRTITION
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PRTITION
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (PositiveInteger,%) -> %        ?+? : (%,%) -> %
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               0 : () -> %
--R coerce : % -> List(Integer)           coerce : % -> OutputForm
--R conjugate : % -> %                    convert : % -> List(Integer)
--R hash : % -> SingleInteger             latex : % -> String
--R max : (%,%) -> %                      min : (%,%) -> %
--R partition : List(Integer) -> %        pdct : % -> Integer
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R powers : List(Integer) -> List(List(Integer))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Partition.help** —

```
====================================================================
Partition examples
====================================================================

See Also:
o )show Partition
```

———-

17.9.1 Partition (PRTITION)



See

⇒ “SymmetricPolynomial” (SYMPOLY) 20.39.1 on page 2622

Exports:

0	coerce	conjugate	convert	hash
latex	max	min	partition	pdct
powers	sample	subtractIfCan	zero?	?~=?
?*?	?+?	?<?	?<=?	?=?
?>?	?>=?			

— **domain PRTITION Partition** —

```
)abbrev domain PRTITION Partition
++ Author: William H. Burge
++ Date Created: 29 October 1987
++ Date Last Updated: 23 Sept 1991
++ Keywords:
++ Examples:
++ References:
++ Description:
```

```
++ Domain for partitions of positive integers
++ Partition is an OrderedCancellationAbelianMonoid which is used
++ as the basis for symmetric polynomial representation of the
++ sums of powers in SymmetricPolynomial.  Thus, \spad{(5 2 2 1)} will
++ represent \spad{s5 * s2**2 * s1}.

Partition: Exports == Implementation where
  L   ==> List
  I   ==> Integer
  OUT ==> OutputForm
  NNI ==> NonNegativeInteger
  UN  ==> Union(%,"failed")

  Exports ==> Join(OrderedCancellationAbelianMonoid,
                   ConvertibleTo List Integer) with
    partition: L I -> %
      ++ partition(li) converts a list of integers li to a partition
    powers: L I -> L L I
      ++ powers(li) returns a list of 2-element lists.  For each 2-element
      ++ list, the first element is an entry of li and the second
      ++ element is the multiplicity with which the first element
      ++ occurs in li.  There is a 2-element list for each value
      ++ occurring in l.
    pdct: % -> I
      ++ \spad{pdct(a1**n1 a2**n2 ...)} returns
      ++ \spad{n1! * a1**n1 * n2! * a2**n2 * ...}.
      ++ This function is used in the package \spadtype{CycleIndicators}.
    conjugate: % -> %
      ++ conjugate(p) returns the conjugate partition of a partition p
    coerce:% -> List Integer
      ++ coerce(p) coerces a partition into a list of integers

  Implementation ==> add

    import PartitionsAndPermutations

    Rep := List Integer
    0 == nil()

    coerce (s:%) == s pretend List Integer
    convert x == copy(x pretend L I)

    partition list == sort((i1:Integer,i2:Integer):Boolean +-> i2 < i1,list)

    x < y ==
      empty? x => not empty? y
      empty? y => false
      first x = first y => rest x < rest y
      first x < first y
```

```
    x = y ==
        EQUAL(x,y)$Lisp
--      empty? x => empty? y
--      empty? y => false
--      first x = first y => rest x = rest y
--      false

    x + y ==
      empty? x => y
      empty? y => x
      first x > first y => concat(first x,rest(x) + y)
      concat(first y,x + rest(y))
    n:NNI * x:% == (zero? n => 0; x + (subtractIfCan(n,1) :: NNI) * x)

    dp: (I,%) -> %
    dp(i,x) ==
      empty? x => 0
      first x = i => rest x
      concat(first x,dp(i,rest x))

    remv: (I,%) -> UN
    remv(i,x) == (member?(i,x) => dp(i,x); "failed")

    subtractIfCan(x, y) ==
      empty? x =>
        empty? y => 0
        "failed"
      empty? y => x
      (aa := remv(first y,x)) case "failed" => "failed"
      subtractIfCan((aa :: %), rest y)

    li1 : L I  --!! 'bite' won't compile without this
    bite: (I,L I) -> L I
    bite(i,li) ==
      empty? li => concat(0,nil())
      first li = i =>
        li1 := bite(i,rest li)
        concat(first(li1) + 1,rest li1)
      concat(0,li)

    li : L I  --!!  'powers' won't compile without this
    powers l ==
      empty? l => nil()
      li := bite(first l,rest l)
      concat([first l,first(li) + 1],powers(rest li))

    conjugate x == conjugate(x pretend Rep)$PartitionsAndPermutations

    mkterm: (I,I) -> OUT
    mkterm(i1,i2) ==
```

```
      i2 = 1 => (i1 :: OUT) ** (" " :: OUT)
      (i1 :: OUT) ** (i2 :: OUT)

    mkexp1: L L I -> L OUT
    mkexp1 lli ==
      empty? lli => nil()
      li := first lli
      empty?(rest lli) and second(li) = 1 =>
        concat(first(li) :: OUT,nil())
      concat(mkterm(first li,second li),mkexp1(rest lli))

    coerce(x:%):OUT ==
        empty? (x pretend Rep) => coerce(x pretend Rep)$Rep
        paren(reduce("*",mkexp1(powers(x pretend Rep))))

    pdct x ==
      */[factorial(second a) * (first(a) ** (second(a) pretend NNI))
                 for a in powers(x pretend Rep)]
```

———-

— PRTITION.dotabb —

```
"PRTITION" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PRTITION"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"PRTITION" -> "FLAGG-"
"PRTITION" -> "FLAGG"
```

———-

17.10 domain PATTERN Pattern

— Pattern.input —

```
)set break resume
)sys rm -f Pattern.output
)spool Pattern.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Pattern
```

```
--R
--R Pattern(R: SetCategory)  is a domain constructor
--R Abbreviation for Pattern is PATTERN
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PATTERN
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?**? : (%,%) -> %
--R ?+? : (%,%) -> %                      ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           addBadValue : (%,Any) -> %
--R coerce : Symbol -> %                  coerce : R -> %
--R coerce : % -> OutputForm              constant? : % -> Boolean
--R convert : List(%) -> %                copy : % -> %
--R depth : % -> NonNegativeInteger       generic? : % -> Boolean
--R getBadValues : % -> List(Any)         hasPredicate? : % -> Boolean
--R hasTopPredicate? : % -> Boolean       hash : % -> SingleInteger
--R inR? : % -> Boolean                   latex : % -> String
--R multiple? : % -> Boolean              optional? : % -> Boolean
--R predicates : % -> List(Any)           quoted? : % -> Boolean
--R resetBadValues : % -> %               retract : % -> Symbol
--R retract : % -> R                      symbol? : % -> Boolean
--R variables : % -> List(%)              ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R elt : (BasicOperator,List(%)) -> %
--R isExpt : % -> Union(Record(val: %,exponent: NonNegativeInteger),"failed")
--R isList : % -> Union(List(%),"failed")
--R isOp : % -> Union(Record(op: BasicOperator,arg: List(%)),"failed")
--R isOp : (%,BasicOperator) -> Union(List(%),"failed")
--R isPlus : % -> Union(List(%),"failed")
--R isPower : % -> Union(Record(val: %,exponent: %),"failed")
--R isQuotient : % -> Union(Record(num: %,den: %),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R optpair : List(%) -> Union(List(%),"failed")
--R patternVariable : (Symbol,Boolean,Boolean,Boolean) -> %
--R retractIfCan : % -> Union(Symbol,"failed")
--R retractIfCan : % -> Union(R,"failed")
--R setPredicates : (%,List(Any)) -> %
--R setTopPredicate : (%,List(Symbol),Any) -> %
--R topPredicate : % -> Record(var: List(Symbol),pred: Any)
--R withPredicates : (%,List(Any)) -> %
--R
--E 1

)spool
)lisp (bye)
```


— Pattern.help —

```
====================================================================
Pattern examples
====================================================================

See Also:
o )show Pattern
```

———-

17.10.1 Pattern (PATTERN)



Exports:

0	1	addBadValue	coerce	constant?
convert	copy	depth	elt	generic?
getBadValues	hasPredicate?	hasTopPredicate?	hash	inR?
isExpt	isList	isOp	isOp	isPlus
isPower	isQuotient	isTimes	latex	multiple?
optional?	optpair	patternVariable	predicates	quoted?
resetBadValues	retract	retractIfCan	setPredicates	setTopPredicate
symbol?	topPredicate	variables	withPredicates	?*?
?**?	?+?	?/?	?=?	?~=?

— domain PATTERN Pattern —

```
)abbrev domain PATTERN Pattern
++ Author: Manuel Bronstein
++ Date Created: 10 Nov 1988
++ Date Last Updated: 20 June 1991
++ Keywords: pattern, matching.
++ Description:
++ Patterns for use by the pattern matcher.
-- Not exposed.
```

```
-- Patterns are optimized for quick answers to structural questions.

Pattern(R:SetCategory): Exports == Implementation where
  B   ==> Boolean
  SI  ==> SingleInteger
  Z   ==> Integer
  SY  ==> Symbol
  O   ==> OutputForm
  BOP ==> BasicOperator
  QOT ==> Record(num:%, den:%)
  REC ==> Record(val:%, exponent:NonNegativeInteger)
  RSY ==> Record(tag:SI, val: SY, pred:List Any, bad:List Any)
  KER ==> Record(tag:SI, op:BOP, arg:List %)
  PAT ==> Union(ret:R, ker: KER, exp:REC, qot: QOT, sym:RSY)

-- the following MUST be the name of the formal exponentiation operator
  POWER ==> "%power"::Symbol

-- the 4 SYM_ constants must be disting powers of 2 (bitwise arithmetic)
  SYM_GENERIC  ==> 1::SI
  SYM_MULTIPLE ==> 2::SI
  SYM_OPTIONAL ==> 4::SI

  PAT_PLUS     ==> 1::SI
  PAT_TIMES    ==> 2::SI
  PAT_LIST     ==> 3::SI
  PAT_ZERO     ==> 4::SI
  PAT_ONE      ==> 5::SI
  PAT_EXPT     ==> 6::SI

  Exports ==> Join(SetCategory, RetractableTo R, RetractableTo SY) with
    0            : constant -> %              ++ 0
    1            : constant -> %              ++ 1
    isPlus       : %  -> Union(List %, "failed")
      ++ isPlus(p) returns \spad{[a1,...,an]} if \spad{n > 1}
      ++  and \spad{p = a1 + ... + an},
      ++ and "failed" otherwise.
    isTimes      : %  -> Union(List %, "failed")
      ++ isTimes(p) returns \spad{[a1,...,an]} if \spad{n > 1} and
      ++ \spad{p = a1 * ... * an}, and
      ++ "failed" otherwise.
    isOp         : (%, BOP) -> Union(List %, "failed")
      ++ isOp(p, op) returns \spad{[a1,...,an]} if \spad{p = op(a1,...,an)}, and
      ++ "failed" otherwise.
    isOp         : %  -> Union(Record(op:BOP, arg:List %), "failed")
      ++ isOp(p) returns \spad{[op, [a1,...,an]]} if
      ++ \spad{p = op(a1,...,an)}, and
      ++ "failed" otherwise;
    isExpt       : %  -> Union(REC, "failed")
      ++ isExpt(p) returns \spad{[q, n]} if \spad{n > 0} and \spad{p = q ** n},
```

```
  ++ and "failed" otherwise.
isQuotient   : %  -> Union(QOT, "failed")
  ++ isQuotient(p) returns \spad{[a, b]} if \spad{p = a / b}, and
  ++ "failed" otherwise.
isList       : %  -> Union(List %, "failed")
  ++ isList(p) returns \spad{[a1,...,an]} if \spad{p = [a1,...,an]},
  ++ "failed" otherwise;
isPower      : %  -> Union(Record(val:%, exponent:%), "failed")
  ++ isPower(p) returns \spad{[a, b]} if \spad{p = a ** b}, and
  ++ "failed" otherwise.
elt          : (BOP, List %) -> %
  ++ \spad{elt(op, [a1,...,an])} returns \spad{op(a1,...,an)}.
"+"          : (%, %) -> %
  ++ \spad{a + b} returns the pattern \spad{a + b}.
"*"          : (%, %) -> %
  ++ \spad{a * b} returns the pattern \spad{a * b}.
"**"         : (%, NonNegativeInteger) -> %
  ++ \spad{a ** n} returns the pattern \spad{a ** n}.
"**"         : (%, %) -> %
  ++ \spad{a ** b} returns the pattern \spad{a ** b}.
"/"          : (%, %) -> %
  ++ \spad{a / b} returns the pattern \spad{a / b}.
depth        : % -> NonNegativeInteger
  ++ depth(p) returns the nesting level of p.
convert      : List % -> %
  ++ \spad{convert([a1,...,an])} returns the pattern \spad{[a1,...,an]}.
copy         : %  -> %
  ++ copy(p) returns a recursive copy of p.
inR?         : %  -> B
  ++ inR?(p) tests if p is an atom (i.e. an element of R).
quoted?      : %  -> B
  ++ quoted?(p) tests if p is of the form 's for a symbol s.
symbol?      : %  -> B
  ++ symbol?(p) tests if p is a symbol.
constant?    : %  -> B
  ++ constant?(p) tests if p contains no matching variables.
generic?     : %  -> B
  ++ generic?(p) tests if p is a single matching variable.
multiple?    : %  -> B
  ++ multiple?(p) tests if p is a single matching variable
  ++ allowing list matching or multiple term matching in a
  ++ sum or product.
optional?    : %  -> B
  ++ optional?(p) tests if p is a single matching variable
  ++ which can match an identity.
hasPredicate?: %  -> B
  ++ hasPredicate?(p) tests if p has predicates attached to it.
predicates   : %  -> List Any
  ++ predicates(p) returns \spad{[p1,...,pn]} such that the predicate
  ++ attached to p is p1 and ... and pn.
```

```
    setPredicates: (%, List Any) -> %
      ++ \spad{setPredicates(p, [p1,...,pn])} attaches the predicate
      ++ p1 and ... and pn to p.
    withPredicates:(%, List Any) -> %
      ++ \spad{withPredicates(p, [p1,...,pn])} makes a copy of p and attaches
      ++ the predicate p1 and ... and pn to the copy, which is
      ++ returned.
    patternVariable: (SY, B, B, B) -> %
      ++ patternVariable(x, c?, o?, m?) creates a pattern variable x,
      ++ which is constant if \spad{c? = true}, optional if \spad{o? = true},
      ++ and multiple if \spad{m? = true}.
    setTopPredicate: (%, List SY, Any) -> %
      ++ \spad{setTopPredicate(x, [a1,...,an], f)} returns x with
      ++ the top-level predicate set to \spad{f(a1,...,an)}.
    topPredicate: % -> Record(var:List SY, pred:Any)
      ++ topPredicate(x) returns \spad{[[a1,...,an], f]} where the top-level
      ++ predicate of x is \spad{f(a1,...,an)}.
      ++ Note: n is 0 if x has no top-level
      ++ predicate.
    hasTopPredicate?: % -> B
      ++ hasTopPredicate?(p) tests if p has a top-level predicate.
    resetBadValues: % -> %
      ++ resetBadValues(p) initializes the list of "bad values" for p
      ++ to \spad{[]}.
      ++ Note: p is not allowed to match any of its "bad values".
    addBadValue: (%, Any) -> %
      ++ addBadValue(p, v) adds v to the list of "bad values" for p.
      ++ Note: p is not allowed to match any of its "bad values".
    getBadValues: % -> List Any
      ++ getBadValues(p) returns the list of "bad values" for p.
      ++ Note: p is not allowed to match any of its "bad values".
    variables: % -> List %
      ++ variables(p) returns the list of matching variables
      ++ appearing in p.
    optpair: List % -> Union(List %, "failed")
      ++ optpair(l) returns l has the form \spad{[a, b]} and
      ++ a is optional, and
      ++ "failed" otherwise;

  Implementation ==> add
    Rep := Record(cons?: B, pat:PAT, lev: NonNegativeInteger,
                  topvar: List SY, toppred: Any)

    dummy:BOP := operator(new()$Symbol)
    nopred    := coerce(0$Integer)$AnyFunctions1(Integer)

    mkPat     : (B, PAT, NonNegativeInteger) -> %
    mkrsy     : (SY, B, B, B)  -> RSY
    SYM2O     : RSY -> O
    PAT2O     : PAT -> O
```

```
patcopy   : PAT -> PAT
bitSet?   : (SI ,  SI) -> B
pateq?    : (PAT, PAT) -> B
LPAT2O    : ((O, O) -> O, List %) -> O
taggedElt : (SI, List %) -> %
isTaggedOp: (%, SI) -> Union(List %, "failed")
incmax    : List % -> NonNegativeInteger

coerce(r:R):%   == mkPat(true, [r], 0)
mkPat(c, p, l)  == [c, p, l, empty(), nopred]
hasTopPredicate? x == not empty?(x.topvar)
topPredicate x  == [x.topvar, x.toppred]
setTopPredicate(x, l, f) == (x.topvar := l; x.toppred := f; x)
constant? p     == p.cons?
depth p         == p.lev
inR? p          == p.pat case ret
symbol? p       == p.pat case sym
isPlus p        == isTaggedOp(p, PAT_PLUS)
isTimes p       == isTaggedOp(p, PAT_TIMES)
isList p        == isTaggedOp(p, PAT_LIST)
isExpt p        == (p.pat case exp => p.pat.exp; "failed")
isQuotient p    == (p.pat case qot => p.pat.qot; "failed")
hasPredicate? p == not empty? predicates p
quoted? p       == symbol? p and zero?(p.pat.sym.tag)
generic? p      == symbol? p and bitSet?(p.pat.sym.tag, SYM_GENERIC)
multiple? p     == symbol? p and bitSet?(p.pat.sym.tag,SYM_MULTIPLE)
optional? p     == symbol? p and bitSet?(p.pat.sym.tag,SYM_OPTIONAL)
bitSet?(a, b)   == And(a, b) ^= 0
coerce(p:%):O   == PAT2O(p.pat)
p1:% ** p2:%    == taggedElt(PAT_EXPT, [p1, p2])
LPAT2O(f, l)    == reduce(f, [x::O for x in l])$List(O)
retract(p:%):R  == (inR? p => p.pat.ret; error "Not retractable")
convert(l:List %):%                 == taggedElt(PAT_LIST, l)
retractIfCan(p:%):Union(R,"failed") ==(inR? p => p.pat.ret;"failed")
withPredicates(p, l)                == setPredicates(copy p, l)
coerce(sy:SY):%          == patternVariable(sy, false, false, false)
copy p  == [constant? p, patcopy(p.pat), p.lev, p.topvar, p.toppred]

-- returns [a, b] if #l = 2 and optional? a, "failed" otherwise
optpair l ==
  empty? rest rest l =>
    b := first rest l
    optional?(a := first l) => l
    optional? b => reverse l
    "failed"
  "failed"

incmax l ==
  1 + reduce("max", [p.lev for p in l], 0)$List(NonNegativeInteger)
```

```
    p1 = p2 ==
      (p1.cons? = p2.cons?) and (p1.lev = p2.lev) and
        (p1.topvar = p2.topvar) and
          ((EQ(p1.toppred, p2.toppred)$Lisp) pretend B) and
            pateq?(p1.pat, p2.pat)

    isPower p ==
      (u := isTaggedOp(p, PAT_EXPT)) case "failed" => "failed"
      [first(u::List(%)), second(u::List(%))]

    taggedElt(n, l) ==
      mkPat(every?(constant?, l), [[n, dummy, l]$KER], incmax l)

    elt(o, l) ==
      is?(o, POWER) and #l = 2 => first(l) ** last(l)
      mkPat(every?(constant?, l), [[0, o, l]$KER], incmax l)

    isOp p ==
      (p.pat case ker) and zero?(p.pat.ker.tag) =>
        [p.pat.ker.op, p.pat.ker.arg]
      "failed"

    isTaggedOp(p,t) ==
      (p.pat case ker) and (p.pat.ker.tag = t) => p.pat.ker.arg
      "failed"

    if R has Monoid then
      1 == 1::R::%
    else
      1 == taggedElt(PAT_ONE,  empty())

    if R has AbelianMonoid then
      0 == 0::R::%
    else
      0 == taggedElt(PAT_ZERO, empty())

    p:% ** n:NonNegativeInteger ==
      p = 0 and n > 0 => 0
      p = 1 or zero? n => 1
--      one? n => p
      (n = 1) => p
      mkPat(constant? p, [[p, n]$REC], 1 + (p.lev))

    p1 / p2 ==
      p2 = 1 => p1
      mkPat(constant? p1 and constant? p2, [[p1, p2]$QOT],
                                        1 + max(p1.lev, p2.lev))

    p1 + p2 ==
      p1 = 0 => p2
```

```
    p2 = 0 => p1
    (u1 := isPlus p1) case List(%) =>
      (u2 := isPlus p2) case List(%) =>
        taggedElt(PAT_PLUS, concat(u1::List %, u2::List %))
      taggedElt(PAT_PLUS, concat(u1::List %, p2))
    (u2 := isPlus p2) case List(%) =>
      taggedElt(PAT_PLUS, concat(p1, u2::List %))
    taggedElt(PAT_PLUS, [p1, p2])

  p1 * p2 ==
    p1 = 0 or p2 = 0 => 0
    p1 = 1 => p2
    p2 = 1 => p1
    (u1 := isTimes p1) case List(%) =>
      (u2 := isTimes p2) case List(%) =>
        taggedElt(PAT_TIMES, concat(u1::List %, u2::List %))
      taggedElt(PAT_TIMES, concat(u1::List %, p2))
    (u2 := isTimes p2) case List(%) =>
      taggedElt(PAT_TIMES, concat(p1, u2::List %))
    taggedElt(PAT_TIMES, [p1, p2])

  isOp(p, o) ==
    (p.pat case ker) and zero?(p.pat.ker.tag) and (p.pat.ker.op =o) =>
      p.pat.ker.arg
    "failed"

  predicates p ==
    symbol? p => p.pat.sym.pred
    empty()

  setPredicates(p, l) ==
    generic? p => (p.pat.sym.pred := l; p)
    error "Can only attach predicates to generic symbol"

  resetBadValues p ==
    generic? p => (p.pat.sym.bad := empty()$List(Any); p)
    error "Can only attach bad values to generic symbol"

  addBadValue(p, a) ==
    generic? p =>
      if not member?(a, p.pat.sym.bad) then
        p.pat.sym.bad := concat(a, p.pat.sym.bad)
      p
    error "Can only attach bad values to generic symbol"

  getBadValues p ==
    generic? p => p.pat.sym.bad
    error "Not a generic symbol"

  SYM2O p ==
```

```
    sy := (p.val)::O
    empty?(p.pred) => sy
    paren infix(" | "::O, sy,
      reduce("and",[sub("f"::O, i::O) for i in 1..#(p.pred)])$List(O))

  variables p ==
    constant? p => empty()
    generic? p => [p]
    q := p.pat
    q case ret => empty()
    q case exp => variables(q.exp.val)
    q case qot => concat_!(variables(q.qot.num), variables(q.qot.den))
    q case ker => concat [variables r for r in q.ker.arg]
    empty()

  PAT2O p ==
    p case ret => (p.ret)::O
    p case sym => SYM2O(p.sym)
    p case exp => (p.exp.val)::O ** (p.exp.exponent)::O
    p case qot => (p.qot.num)::O / (p.qot.den)::O
    p.ker.tag = PAT_PLUS  => LPAT2O("+", p.ker.arg)
    p.ker.tag = PAT_TIMES => LPAT2O("*", p.ker.arg)
    p.ker.tag = PAT_LIST => (p.ker.arg)::O
    p.ker.tag = PAT_ZERO => 0::Integer::O
    p.ker.tag = PAT_ONE  => 1::Integer::O
    l := [x::O for x in p.ker.arg]$List(O)
    (u:=display(p.ker.op)) case "failed" =>prefix(name(p.ker.op)::O,l)
    (u::(List O -> O)) l

  patcopy p ==
    p case ret => [p.ret]
    p case sym =>
      [[p.sym.tag, p.sym.val, copy(p.sym.pred), copy(p.sym.bad)]$RSY]
    p case ker=>[[p.ker.tag,p.ker.op,[copy x for x in p.ker.arg]]$KER]
    p case qot => [[copy(p.qot.num), copy(p.qot.den)]$QOT]
    [[copy(p.exp.val), p.exp.exponent]$REC]

  pateq?(p1, p2) ==
    p1 case ret => (p2 case ret) and (p1.ret = p2.ret)
    p1 case qot =>
      (p2 case qot) and (p1.qot.num = p2.qot.num)
                    and (p1.qot.den = p2.qot.den)
    p1 case sym =>
      (p2 case sym) and (p1.sym.val = p2.sym.val)
                    and {p1.sym.pred} =$Set(Any) {p2.sym.pred}
                      and {p1.sym.bad} =$Set(Any) {p2.sym.bad}
    p1 case ker =>
      (p2 case ker) and (p1.ker.tag = p2.ker.tag)
             and (p1.ker.op = p2.ker.op) and (p1.ker.arg = p2.ker.arg)
    (p2 case exp) and (p1.exp.exponent = p2.exp.exponent)
```

```
                  and (p1.exp.val = p2.exp.val)

    retractIfCan(p:%):Union(SY, "failed") ==
      symbol? p => p.pat.sym.val
      "failed"

    mkrsy(t, c?, o?, m?) ==
      c? => [0, t, empty(), empty()]
      mlt := (m? => SYM_MULTIPLE; 0)
      opt := (o? => SYM_OPTIONAL; 0)
      [Or(Or(SYM_GENERIC, mlt), opt), t, empty(), empty()]

    patternVariable(sy, c?, o?, m?) ==
      rsy := mkrsy(sy, c?, o?, m?)
      mkPat(zero?(rsy.tag), [rsy], 0)
```

———-

— **PATTERN.dotabb** —

```
"PATTERN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PATTERN"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"PATTERN" -> "ALIST"
```

———-

17.11 domain PATLRES PatternMatchListResult

— **PatternMatchListResult.input** —

```
)set break resume
)sys rm -f PatternMatchListResult.output
)spool PatternMatchListResult.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PatternMatchListResult
--R
--R PatternMatchListResult(R: SetCategory,S: SetCategory,L: ListAggregate(S))  is a domain const
--R Abbreviation for PatternMatchListResult is PATLRES
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PATLRES
```

```
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R failed : () -> %                      failed? : % -> Boolean
--R hash : % -> SingleInteger             latex : % -> String
--R new : () -> %                         ?~=? : (%,%) -> Boolean
--R atoms : % -> PatternMatchResult(R,S)
--R lists : % -> PatternMatchResult(R,L)
--R makeResult : (PatternMatchResult(R,S),PatternMatchResult(R,L)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **PatternMatchListResult.help** —

```
=====================================================================
PatternMatchListResult examples
=====================================================================

See Also:
o )show PatternMatchListResult
```

———-

17.11.1 PatternMatchListResult (PATLRES)



See

⇒ “PatternMatchResult” (PATRES) 17.12.1 on page 1906

Exports:

atoms	coerce	failed	failed?	hash
latex	lists	makeResult	new	?=?
?~=?				

— domain PATLRES PatternMatchListResult —

```
)abbrev domain PATLRES PatternMatchListResult
++ Author: Manuel Bronstein
++ Date Created: 4 Dec 1989
++ Date Last Updated: 4 Dec 1989
++ Keywords: pattern, matching, list.
++ Description:
++ A PatternMatchListResult is an object internally returned by the
++ pattern matcher when matching on lists.
++ It is either a failed match, or a pair of PatternMatchResult,
++ one for atoms (elements of the list), and one for lists.
-- not exported

PatternMatchListResult(R:SetCategory, S:SetCategory, L:ListAggregate S):
  SetCategory with
    failed?   : %  -> Boolean
      ++ failed?(r) tests if r is a failed match.
    failed    : () -> %
      ++ failed() returns a failed match.
    new       : () -> %
      ++ new() returns a new empty match result.
    makeResult: (PatternMatchResult(R,S), PatternMatchResult(R,L)) -> %
      ++ makeResult(r1,r2) makes the combined result [r1,r2].
    atoms     : %  -> PatternMatchResult(R, S)
      ++ atoms(r) returns the list of matches that match atoms
      ++ (elements of the lists).
    lists     : %  -> PatternMatchResult(R, L)
      ++ lists(r) returns the list of matches that match lists.
 == add
  Rep := Record(a:PatternMatchResult(R, S), l:PatternMatchResult(R, L))

  new()              == [new(), new()]
  atoms r            == r.a
  lists r            == r.l
  failed()           == [failed(), failed()]
  failed? r          == failed?(atoms r)
  x = y              == (atoms x = atoms y) and (lists x = lists y)

  makeResult(r1, r2) ==
    failed? r1 or failed? r2 => failed()
    [r1, r2]

  coerce(r:%):OutputForm ==
    failed? r => atoms(r)::OutputForm
    RecordPrint(r, Rep)$Lisp
```

———-

— **PATLRES.dotabb** —

```
"PATLRES" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PATLRES"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"PATLRES" -> "FLAGG"
```

———-

17.12 domain PATRES PatternMatchResult

— **PatternMatchResult.input** —

```
)set break resume
)sys rm -f PatternMatchResult.output
)spool PatternMatchResult.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PatternMatchResult
--R
--R PatternMatchResult(R: SetCategory,S: SetCategory)  is a domain constructor
--R Abbreviation for PatternMatchResult is PATRES
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PATRES
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               addMatch : (Pattern(R),S,%) -> %
--R coerce : % -> OutputForm             failed : () -> %
--R failed? : % -> Boolean               hash : % -> SingleInteger
--R latex : % -> String                  new : () -> %
--R union : (%,%) -> %                  ?~=? : (%,%) -> Boolean
--R addMatchRestricted : (Pattern(R),S,%,S) -> %
--R construct : List(Record(key: Symbol,entry: S)) -> %
--R destruct : % -> List(Record(key: Symbol,entry: S))
--R getMatch : (Pattern(R),%) -> Union(S,"failed")
--R insertMatch : (Pattern(R),S,%) -> %
--R satisfy? : (%,Pattern(R)) -> Union(Boolean,"failed")
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **PatternMatchResult.help** —

```
=====================================================================
PatternMatchResult examples
=====================================================================

See Also:
o )show PatternMatchResult
```

———-

17.12.1 PatternMatchResult (PATRES)



See

⇒ “PatternMatchListResult” (PATLRES) 17.11.1 on page 1903

Exports:

addMatch	addMatchRestricted	coerce	construct	destruct
failed	failed?	getMatch	hash	insertMatch
latex	new	satisfy?	union	?=?
?~=?				

— **domain PATRES PatternMatchResult** —

```
)abbrev domain PATRES PatternMatchResult
++ Author: Manuel Bronstein
++ Date Created: 28 Nov 1989
++ Date Last Updated: 5 Jul 1990
++ Keywords: pattern, matching.
```

```
++ Description:
++ A PatternMatchResult is an object internally returned by the
++ pattern matcher; It is either a failed match, or a list of
++ matches of the form (var, expr) meaning that the variable var
++ matches the expression expr.
-- not exported

PatternMatchResult(R:SetCategory, S:SetCategory): SetCategory with
  failed?           : %  -> Boolean
    ++ failed?(r) tests if r is a failed match.
  failed            : () -> %
    ++ failed() returns a failed match.
  new               : () -> %
    ++ new() returns a new empty match result.
  union             : (%, %) -> %
    ++ union(a, b) makes the set-union of two match results.
  getMatch          : (Pattern R, %) -> Union(S, "failed")
    ++ getMatch(var, r) returns the expression that var matches
    ++ in the result r, and "failed" if var is not matched in r.
  addMatch          : (Pattern R, S, %) -> %
    ++ addMatch(var, expr, r) adds the match (var, expr) in r,
    ++ provided that expr satisfies the predicates attached to var,
    ++ and that var is not matched to another expression already.
  insertMatch       : (Pattern R, S, %) -> %
    ++ insertMatch(var, expr, r) adds the match (var, expr) in r,
    ++ without checking predicates or previous matches for var.
  addMatchRestricted: (Pattern R, S, %, S) -> %
    ++ addMatchRestricted(var, expr, r, val) adds the match
    ++ (var, expr) in r,
    ++ provided that expr satisfies the predicates attached to var,
    ++ that var is not matched to another expression already,
    ++ and that either var is an optional pattern variable or that
    ++ expr is not equal to val (usually an identity).
  destruct          : % -> List Record(key:Symbol, entry:S)
    ++ destruct(r) returns the list of matches (var, expr) in r.
    ++ Error: if r is a failed match.
  construct         : List Record(key:Symbol, entry:S) -> %
    ++ construct([v1,e1],...,[vn,en]) returns the match result
    ++ containing the matches (v1,e1),...,(vn,en).
  satisfy?          : (%, Pattern R) -> Union(Boolean, "failed")
    ++ satisfy?(r, p) returns true if the matches satisfy the
    ++ top-level predicate of p, false if they don't, and "failed"
    ++ if not enough variables of p are matched in r to decide.

 == add
  LR ==> AssociationList(Symbol, S)

  import PatternFunctions1(R, S)

  Rep := Union(LR, "failed")
```

```
  new()                == empty()
  failed()             == "failed"
  failed? x            == x case "failed"
  insertMatch(p, x, l) == concat([retract p, x], l::LR)
  construct l          == construct(l)$LR
  destruct l           == entries(l::LR)$LR

-- returns "failed" if not all the variables of the pred. are matched
  satisfy?(r, p) ==
    failed? r => false
    lr := r::LR
    lv := [if (u := search(v, lr)) case "failed" then return "failed"
                        else  u::S for v in topPredicate(p).var]$List(S)
    satisfy?(lv, p)

  union(x, y) ==
    failed? x or failed? y => failed()
    removeDuplicates concat(x::LR, y::LR)

  x = y ==
    failed? x => failed? y
    failed? y => false
    x::LR =$LR y::LR

  coerce(x:%):OutputForm ==
    failed? x => "Does not match"::OutputForm
    destruct(x)::OutputForm

  addMatchRestricted(p, x, l, ident) ==
    (not optional? p) and (x = ident) => failed()
    addMatch(p, x, l)

  addMatch(p, x, l) ==
    failed?(l) or not(satisfy?(x, p)) => failed()
    al := l::LR
    sy := retract(p)@Symbol
    (r := search(sy, al)) case "failed" => insertMatch(p, x, l)
    r::S = x => l
    failed()

  getMatch(p, l) ==
    failed? l => "failed"
    search(retract(p)@Symbol, l::LR)
```

———-

— PATRES.dotabb —

```
"PATRES" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PATRES"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"PATRES" -> "TBAGG"
```

———-

17.13 domain PENDTREE PendantTree

— PendantTree.input —

```
)set break resume
)sys rm -f PendantTree.output
)spool PendantTree.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PendantTree
--R
--R PendantTree(S: SetCategory)  is a domain constructor
--R Abbreviation for PendantTree is PENDTREE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PENDTREE
--R
--R------------------------------ Operations --------------------------------
--R children : % -> List(%)              coerce : % -> Tree(S)
--R copy : % -> %                        cyclic? : % -> Boolean
--R distance : (%,%) -> Integer          ?.right : (%,right) -> %
--R ?.left : (%,left) -> %               ?.value : (%,value) -> S
--R empty : () -> %                      empty? : % -> Boolean
--R eq? : (%,%) -> Boolean               leaf? : % -> Boolean
--R leaves : % -> List(S)                left : % -> %
--R map : ((S -> S),%) -> %              nodes : % -> List(%)
--R ptree : (%,%) -> %                   ptree : S -> %
--R right : % -> %                       sample : () -> %
--R value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
```

```
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,right,%) -> % if $ has shallowlyMutable
--R setelt : (%,left,%) -> % if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setleft! : (%,%) -> % if $ has shallowlyMutable
--R setright! : (%,%) -> % if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-

— PendantTree.help —


```
=====================================================================
PendantTree examples
=====================================================================

See Also:
o )show PendantTree
```

———-

A PendantTree(S)is either a leaf? and is an S or has a left and a right both PendantTree(S)'s

17.13.1 PendantTree (PENDTREE)



See

⇒ “Tree” (TREE) 21.10.1 on page 2710
⇒ “BinaryTree” (BTREE) 3.11.1 on page 294
⇒ “BinarySearchTree” (BSTREE) 3.9.1 on page 287
⇒ “BinaryTournament” (BTOURN) 3.10.1 on page 291
⇒ “BalancedBinaryTree” (BBTREE) 3.1.1 on page 236

Exports:

any?	child?	children	coerce	copy
count	cyclic?	distance	empty	empty?
eq?	eval	every?	hash	latex
leaf?	leaves	left	less?	map
map!	member?	members	more?	node?
nodes	parts	ptree	right	sample
setchildren!	setelt	setleft!	setright!	setvalue!
size?	value	#?	?=?	?~=?
?.right	?.left	?.value		

— domain PENDTREE PendantTree —

```
)abbrev domain PENDTREE PendantTree
++ Author: Mark Botch
++ Description:
++ This domain has no description

PendantTree(S: SetCategory): T == C where
 T == BinaryRecursiveAggregate(S) with
   ptree : S->%
    ++ ptree(s) is a leaf? pendant tree
    ++
    ++X t1:=ptree([1,2,3])

   ptree:(%, %)->%
    ++ ptree(x,y) is not documented
    ++
```

```
    ++X t1:=ptree([1,2,3])
    ++X ptree(t1,ptree([1,2,3]))

   coerce:%->Tree S
    ++ coerce(x) is not documented
    ++
    ++X t1:=ptree([1,2,3])
    ++X t2:=ptree(t1,ptree([1,2,3]))
    ++X t2::Tree List PositiveInteger

 C == add
     Rep := Tree S
     import Tree S
     coerce (t:%):Tree S == t pretend Tree S
     ptree(n) == tree(n,[])$Rep pretend %
     ptree(l,r) == tree(value(r:Rep)$Rep,cons(l,children(r:Rep)$Rep)):%
     leaf? t == empty?(children(t)$Rep)
     t1=t2 == (t1:Rep) = (t2:Rep)
     left b ==
       leaf? b => error "ptree:no left"
       first(children(b)$Rep)
     right b ==
       leaf? b => error "ptree:no right"
       tree(value(b)$Rep,rest (children(b)$Rep))
     value b ==
       leaf? b => value(b)$Rep
       error "the pendant tree has no value"
     coerce(b:%): OutputForm ==
       leaf? b => value(b)$Rep :: OutputForm
       paren blankSeparate [left b::OutputForm,right b ::OutputForm]
```

———-

— PENDTREE.dotabb —

```
"PENDTREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PENDTREE"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"PENDTREE" -> "FLAGG-"
```

———-

17.14 domain PERM Permutation

— Permutation.input —

```
)set break resume
)sys rm -f Permutation.output
)spool Permutation.output
)set message test on
)set message auto off
)clear all
--S 1 of 8
p := coercePreimagesImages([[1,2,3],[1,2,3]])
--R
--R
--R   (1)  1
--R                                          Type: Permutation(PositiveInteger)
--E 1

--S 2 of 8
movedPoints p    -- should return {}
--R
--R
--R   (2)  {}
--R                                                Type: Set(PositiveInteger)
--E 2

--S 3 of 8
even? p          -- should return true
--R
--R
--R   (3)  true
--R                                                              Type: Boolean
--E 3

--S 4 of 8
p := coercePreimagesImages([[0,1,2,3],[3,0,2,1]])$PERM ZMOD 4
--R
--R
--R   (4)  (1 0 3)
--R                                            Type: Permutation(IntegerMod(4))
--E 4

--S 5 of 8
fixedPoints p    -- should return {2}
--R
--R
--R   (5)  {2}
--R                                              Type: Set(IntegerMod(4))
--E 5

--S 6 of 8
q := coercePreimagesImages([[0,1,2,3],[1,0]])$PERM ZMOD 4
--R
--R
```

```
--R   (6)  (1 0)
--R                                                Type: Permutation(IntegerMod(4))
--E 6

--S 7 of 8
fixedPoints(p*q) -- should return {2,0}
--R
--R
--R   (7)  {2,0}
--R                                                   Type: Set(IntegerMod(4))
--E 7

--S 8 of 8
even?(p*q)       -- should return false
--R
--R
--R   (8)  false
--R                                                                Type: Boolean
--E 8
)spool
)lisp (bye)
```

———-

— Permutation.help —

```
====================================================================
Permutation Examples
====================================================================

We represent a permutation as two lists of equal length representing preimages
and images of moved points. I.e., fixed points do not occur in either of these
lists. This enables us to compute the set of fixed points and the set of moved
points easily.

  p := coercePreimagesImages([[1,2,3],[1,2,3]])
    1
                      Type: Permutation PositiveInteger

  movedPoints p
    {}
                      Type: Set PositiveInteger

  even? p
    true
                       Type: Boolean

  p := coercePreimagesImages([[0,1,2,3],[3,0,2,1]])$PERM ZMOD 4
    (1 0 3)
```

```
                        Type: Permutation IntegerMod 4


  fixedPoints p
    {2}
                        Type: Set IntegerMod 4

  q := coercePreimagesImages([[0,1,2,3],[1,0]])$PERM ZMOD 4
    (1 0)
                        Type: Permutation IntegerMod 4

  fixedPoints(p*q)
    {2,0}
                        Type: Set IntegerMod 4
  even?(p*q)
    false
                        Type: Boolean

See Also:
o )show Permutation
```

17.14.1 Permutation (PERM)



Exports:

1	coerce	coerceImages
coerceListOfPairs	coercePreimagesImages	commutator
conjugate	cycle	cyclePartition
cycles	degree	eval
even?	fixedPoints	hash
inv	latex	listRepresentation
max	min	movedPoints
numberOfCycles	odd?	one?
orbit	order	recip
sample	sign	sort
?*?	?**?	?/?
?<?	?=?	?^?
?.?	?~=?	?<=?
?>?	?>=?	

— domain PERM Permutation —

```
)abbrev domain PERM Permutation
++ Authors: Johannes Grabmeier, Holger Gollan, Martin Rubey
++ Date Created: 19 May 1989
++ Date Last Updated: 2 June 2006
++ Basic Operations: _*, degree, movedPoints, cyclePartition, order,
++  numberOfCycles, sign, even?, odd?
++ Related Constructors: PermutationGroup, PermutationGroupExamples
++ Also See: RepresentationTheoryPackage1
++ AMS Classifications:
++ Keywords:
++ Reference: G. James/A. Kerber: The Representation Theory of the Symmetric
++   Group. Encycl. of Math. and its Appl., Vol. 16., Cambridge
++ Description:
++ Permutation(S) implements the group of all bijections
++ on a set S, which move only a finite number of points.
++ A permutation is considered as a map from S into S. In particular
++ multiplication is defined as composition of maps:\br
++ pi1 * pi2 = pi1 o pi2.\br
++ The internal representation of permuatations are two lists
++ of equal length representing preimages and images.

Permutation(S:SetCategory): public == private where

  B        ==> Boolean
  PI       ==> PositiveInteger
  I        ==> Integer
  L        ==> List
  NNI      ==> NonNegativeInteger
  V        ==> Vector
  PT       ==> Partition
  OUTFORM  ==> OutputForm
  RECCYPE  ==> Record(cycl: L L S, permut: %)
```

```
RECPRIM  ==> Record(preimage: L S, image : L S)

public ==> PermutationCategory S with

  listRepresentation:  %               ->  RECPRIM
    ++ listRepresentation(p) produces a representation rep of
    ++ the permutation p as a list of preimages and images, i.e
    ++ p maps (rep.preimage).k to (rep.image).k for all
    ++ indices k. Elements of \spad{S} not in (rep.preimage).k
    ++ are fixed points, and these are the only fixed points of the
    ++ permutation.
  coercePreimagesImages : List List S   ->  %
    ++ coercePreimagesImages(lls) coerces the representation lls
    ++ of a permutation as a list of preimages and images to a permutation.
    ++ We assume that both preimage and image do not contain repetitions.
    ++
    ++X p := coercePreimagesImages([[1,2,3],[1,2,3]])
    ++X q := coercePreimagesImages([[0,1,2,3],[3,0,2,1]])$PERM ZMOD 4
  coerce            :  List List S      ->  %
    ++ coerce(lls) coerces a list of cycles lls to a
    ++ permutation, each cycle being a list with no
    ++ repetitions, is coerced to the permutation, which maps
    ++ ls.i to ls.i+1, indices modulo the length of the list,
    ++ then these permutations are mutiplied.
    ++ Error: if repetitions occur in one cycle.
  coerce            :  List S           ->  %
    ++ coerce(ls) coerces a cycle ls, i.e. a list with not
    ++ repetitions to a permutation, which maps ls.i to
    ++ ls.i+1, indices modulo the length of the list.
    ++ Error: if repetitions occur.
  coerceListOfPairs :  List List S      ->  %
    ++ coerceListOfPairs(lls) coerces a list of pairs lls to a
    ++ permutation.
    ++ Error: if not consistent, i.e. the set of the first elements
    ++ coincides with the set of second elements.
  --coerce            :  %                ->  OUTFORM
    ++ coerce(p) generates output of the permutation p with domain
    ++ OutputForm.
  degree            :  %                ->  NonNegativeInteger
    ++ degree(p) retuns the number of points moved by the
    ++ permutation p.
  movedPoints       :  %                ->  Set S
    ++ movedPoints(p) returns the set of points moved by the permutation p.
    ++
    ++X p := coercePreimagesImages([[1,2,3],[1,2,3]])
    ++X movedPoints p
  cyclePartition    :  %                ->  Partition
    ++ cyclePartition(p) returns the cycle structure of a permutation
    ++ p including cycles of length 1 only if S is finite.
  order             :  %                ->  NonNegativeInteger
```

```
    ++ order(p) returns the order of a permutation p as a group element.
  numberOfCycles    :  %               ->  NonNegativeInteger
    ++ numberOfCycles(p) returns the number of non-trivial cycles of
    ++ the permutation p.
  sign              :  %               ->  Integer
    ++ sign(p) returns the signum of the permutation p, +1 or -1.
  even?             :  %               ->  Boolean
    ++ even?(p) returns true if and only if p is an even permutation,
    ++ i.e. sign(p) is 1.
    ++
    ++X p := coercePreimagesImages([[1,2,3],[1,2,3]])
    ++X even? p
  odd?              :  %               ->  Boolean
    ++ odd?(p) returns true if and only if p is an odd permutation
    ++ i.e. sign(p) is -1.
  sort              :  L %             ->  L %
    ++ sort(lp) sorts a list of permutations lp according to
    ++ cycle structure first according to length of cycles,
    ++ second, if S has \spadtype{Finite} or S has
    ++ \spadtype{OrderedSet} according to lexicographical order of
    ++ entries in cycles of equal length.
  if S has Finite then
    fixedPoints     :  %               ->  Set S
      ++ fixedPoints(p) returns the points fixed by the permutation p.
      ++X p := coercePreimagesImages([[0,1,2,3],[3,0,2,1]])$PERM ZMOD 4
      ++X fixedPoints p
  if S has IntegerNumberSystem or S has Finite then
    coerceImages    :  L S             ->  %
      ++ coerceImages(ls) coerces the list ls to a permutation
      ++ whose image is given by ls and the preimage is fixed
      ++ to be [1,...,n].
      ++ Note: {coerceImages(ls)=coercePreimagesImages([1,...,n],ls)}.
      ++ We assume that both preimage and image do not contain repetitions.

private ==> add

  -- representation of the object:

  Rep  := V L S

  -- import of domains and packages

  import OutputForm
  import Vector List S

  -- variables

  p,q      : %
  exp      : I
```

```
    -- local functions first, signatures:

    smaller? : (S,S) -> B
    rotateCycle: L S -> L S
    coerceCycle: L L S -> %
    smallerCycle?: (L S, L S)  -> B
    shorterCycle?:(L S, L S)  -> B
    permord:(RECCYPE,RECCYPE)  -> B
    coerceToCycle:(%,B) -> L L S
    duplicates?: L S -> B

    smaller?(a:S, b:S): B ==
      S has OrderedSet => a <$S b
      S has Finite     => lookup a < lookup b
      false

    rotateCycle(cyc: L S): L S ==
      -- smallest element is put in first place
      -- doesn't change cycle if underlying set
      -- is not ordered or not finite.
      min:S := first cyc
      minpos:I := 1           -- 1 = minIndex cyc
      for i in 2..maxIndex cyc repeat
        if smaller?(cyc.i,min) then
          min  := cyc.i
          minpos := i
--      one? minpos => cyc
      (minpos = 1) => cyc
      concat(last(cyc,((#cyc-minpos+1)::NNI)),first(cyc,(minpos-1)::NNI))

    coerceCycle(lls : L L S): % ==
      perm : % := 1
      for lists in reverse lls repeat
        perm := cycle lists * perm
      perm

    smallerCycle?(cyca: L S, cycb: L S): B ==
      #cyca ^= #cycb =>
        #cyca < #cycb
      for i in cyca for j in cycb repeat
        i ^= j => return smaller?(i, j)
      false

    shorterCycle?(cyca: L S, cycb: L S): B ==
      #cyca < #cycb

    permord(pa: RECCYPE, pb : RECCYPE): B ==
      for i in pa.cycl for j in pb.cycl repeat
        i ^= j => return smallerCycle?(i, j)
      #pa.cycl < #pb.cycl
```

```
coerceToCycle(p: %, doSorting?: B): L L S ==
  preim := p.1
  im := p.2
  cycles := nil()$(L L S)
  while not null preim repeat
    -- start next cycle
    firstEltInCycle: S := first preim
    nextCycle : L S := list firstEltInCycle
    preim := rest preim
    nextEltInCycle := first im
    im      := rest im
    while nextEltInCycle ^= firstEltInCycle repeat
      nextCycle := cons(nextEltInCycle, nextCycle)
      i := position(nextEltInCycle, preim)
      preim := delete(preim,i)
      nextEltInCycle := im.i
      im := delete(im,i)
    nextCycle := reverse nextCycle
    -- check on 1-cycles, we don't list these
    if not null rest nextCycle then
      if doSorting? and (S has OrderedSet or S has Finite) then
          -- put smallest element in cycle first:
          nextCycle := rotateCycle nextCycle
      cycles := cons(nextCycle, cycles)
  not doSorting? => cycles
  -- sort cycles
  S has OrderedSet or S has Finite =>
    sort(smallerCycle?,cycles)$(L L S)
  sort(shorterCycle?,cycles)$(L L S)

duplicates? (ls : L S ): B ==
  x := copy ls
  while not null x repeat
    member? (first x ,rest x) => return true
    x := rest x
  false

-- now the exported functions

listRepresentation p ==
  s : RECPRIM := [p.1,p.2]

coercePreimagesImages preImageAndImage ==
  preImage: List S := []
  image: List S := []
  for i in preImageAndImage.1
    for pi in preImageAndImage.2 repeat
      if i ~= pi then
        preImage := cons(i, preImage)
```

```
          image := cons(pi, image)

    [preImage, image]

  movedPoints p == construct p.1

  degree p ==  #movedPoints p

  p = q ==
    #(preimp := p.1) ^= #(preimq := q.1) => false
    for i in 1..maxIndex preimp repeat
      pos := position(preimp.i, preimq)
      pos = 0 => return false
      (p.2).i ^= (q.2).pos => return false
    true

  orbit(p ,el) ==
    -- start with a 1-element list:
    out : Set S := brace list el
    el2 := eval(p, el)
    while el2 ^= el repeat
      -- be carefull: insert adds one element
      -- as side effect to out
      insert_!(el2, out)
      el2 := eval(p, el2)
    out

  cyclePartition p ==
    partition([#c for c in coerceToCycle(p, false)])$Partition

  order p ==
    ord: I := lcm removeDuplicates convert cyclePartition p
    ord::NNI

  sign(p) ==
    even? p => 1
    - 1

  even?(p) ==  even?(#(p.1) - numberOfCycles p)
    -- see the book of James and Kerber on symmetric groups
    -- for this formula.

  odd?(p) ==  odd?(#(p.1) - numberOfCycles p)

  pa < pb ==
    pacyc:= coerceToCycle(pa,true)
    pbcyc:= coerceToCycle(pb,true)
    for i in pacyc for j in pbcyc repeat
      i ^= j => return smallerCycle? ( i, j )
    maxIndex pacyc < maxIndex pbcyc
```

```
coerce(lls : L L S): % == coerceCycle lls

coerce(ls : L S): % == cycle ls

sort(inList : L %): L % ==
  not (S has OrderedSet or S has Finite) => inList
  ownList: L RECCYPE := nil()$(L RECCYPE)
  for sigma in inList repeat
    ownList :=
      cons([coerceToCycle(sigma,true),sigma]::RECCYPE, ownList)
  ownList := sort(permord, ownList)$(L RECCYPE)
  outList := nil()$(L %)
  for rec in ownList repeat
    outList := cons(rec.permut, outList)
  reverse outList

coerce (p: %): OUTFORM ==
  cycles: L L S := coerceToCycle(p,true)
  outfmL : L OUTFORM := nil()
  for cycle in cycles repeat
    outcycL: L OUTFORM := nil()
    for elt in cycle repeat
      outcycL := cons(elt :: OUTFORM, outcycL)
    outfmL := cons(paren blankSeparate reverse outcycL, outfmL)
  -- The identity element will be output as 1:
  null outfmL => outputForm(1@Integer)
  -- represent a single cycle in the form (a b c d)
  -- and not in the form ((a b c d)):
  null rest outfmL => first outfmL
  hconcat reverse outfmL

cycles(vs ) == coerceCycle vs

cycle(ls) ==
  #ls < 2 => 1
  duplicates? ls => error "cycle: the input contains duplicates"
  [ls, append(rest ls, list first ls)]

coerceListOfPairs(loP) ==
  preim := nil()$(L S)
  im := nil()$(L S)
  for pair in loP repeat
    if first pair ^=  second pair then
      preim := cons(first pair, preim)
      im := cons(second pair, im)
  duplicates?(preim) or duplicates?(im) or brace(preim)$(Set S) _
    ^= brace(im)$(Set S) =>
    error "coerceListOfPairs: the input cannot be interpreted as a permutation"
  [preim, im]
```

```
q * p ==
  -- use vectors for efficiency??
  preimOfp : V S := construct p.1
  imOfp : V S := construct p.2
  preimOfq := q.1
  imOfq := q.2
  preimOfqp   := nil()$(L S)
  imOfqp   := nil()$(L S)
  -- 1 = minIndex preimOfp
  for i in 1..(maxIndex preimOfp) repeat
    -- find index of image of p.i in q if it exists
    j := position(imOfp.i, preimOfq)
    if j = 0 then
      -- it does not exist
      preimOfqp := cons(preimOfp.i, preimOfqp)
      imOfqp := cons(imOfp.i, imOfqp)
    else
      -- it exists
      el := imOfq.j
      -- if the composition fixes the element, we don't
      -- have to do anything
      if el ^= preimOfp.i then
        preimOfqp := cons(preimOfp.i, preimOfqp)
        imOfqp := cons(el, imOfqp)
      -- we drop the parts of q which have to do with p
      preimOfq := delete(preimOfq, j)
      imOfq := delete(imOfq, j)
  [append(preimOfqp, preimOfq), append(imOfqp, imOfq)]

1 == new(2,empty())$Rep

inv p  == [p.2, p.1]

eval(p, el) ==
  pos := position(el, p.1)
  pos = 0 => el
  (p.2).pos

elt(p, el) == eval(p, el)

numberOfCycles p == #coerceToCycle(p, false)


if S has IntegerNumberSystem then

  coerceImages (image) ==
    preImage : L S := [i::S for i in 1..maxIndex image]
    coercePreimagesImages [preImage,image]
```

```
    if S has Finite then

      coerceImages (image) ==
        preImage : L S := [index(i::PI)::S for i in 1..maxIndex image]
        coercePreimagesImages [preImage,image]

      fixedPoints ( p ) == complement movedPoints p

      cyclePartition p ==
        pt := partition([#c for c in coerceToCycle(p, false)])$Partition
        pt +$PT conjugate(partition([#fixedPoints(p)])$PT)$PT
```

———-

— PERM.dotabb —

```
"PERM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PERM"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"PERM" -> "FSAGG"
```

———-

17.15 domain PERMGRP PermutationGroup

— PermutationGroup.input —

```
)set break resume
)sys rm -f PermutationGroup.output
)spool PermutationGroup.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PermutationGroup
--R
--R PermutationGroup(S: SetCategory)  is a domain constructor
--R Abbreviation for PermutationGroup is PERMGRP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PERMGRP
--R
--R------------------------------ Operations ------------------------------
--R ?<? : (%,%) -> Boolean               ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean               base : % -> List(S)
```

```
--R coerce : % -> OutputForm              degree : % -> NonNegativeInteger
--R hash : % -> SingleInteger             latex : % -> String
--R movedPoints : % -> Set(S)             orbit : (%,Set(S)) -> Set(Set(S))
--R orbit : (%,S) -> Set(S)               orbits : % -> Set(Set(S))
--R order : % -> NonNegativeInteger       random : % -> Permutation(S)
--R ?~=? : (%,%) -> Boolean
--R coerce : List(Permutation(S)) -> %
--R coerce : % -> List(Permutation(S))
--R ?.? : (%,NonNegativeInteger) -> Permutation(S)
--R generators : % -> List(Permutation(S))
--R initializeGroupForWordProblem : (%,Integer,Integer) -> Void
--R initializeGroupForWordProblem : % -> Void
--R member? : (Permutation(S),%) -> Boolean
--R orbit : (%,List(S)) -> Set(List(S))
--R permutationGroup : List(Permutation(S)) -> %
--R random : (%,Integer) -> Permutation(S)
--R strongGenerators : % -> List(Permutation(S))
--R wordInGenerators : (Permutation(S),%) -> List(NonNegativeInteger)
--R wordInStrongGenerators : (Permutation(S),%) -> List(NonNegativeInteger)
--R wordsForStrongGenerators : % -> List(List(NonNegativeInteger))
--R
--E 1

)spool
)lisp (bye)
```

———-


— PermutationGroup.help —

```
=====================================================================
PermutationGroup examples
=====================================================================

See Also:
o )show PermutationGroup
```

———-

17.15.1 PermutationGroup (PERMGRP)



Exports:

base	coerce	degree
hash	latex	movedPoints
orbit	orbits	order
random	generators	initializeGroupForWordProblem
member?	permutationGroup	random
strongGenerators	wordInGenerators	wordInStrongGenerators
wordsForStrongGenerators	?~=?	?.?
?<?	?<=?	?=?

— domain PERMGRP PermutationGroup —

```
)abbrev domain PERMGRP PermutationGroup
++ Authors: G. Schneider, H. Gollan, J. Grabmeier
++ Date Created: 13 February 1987
++ Date Last Updated: 24 May 1991
++ Basic Operations:
++ Related Constructors: PermutationGroupExamples, Permutation
++ Also See: RepresentationTheoryPackage1
++ AMS Classifications:
++ Keywords: permutation, permutation group, group operation, word problem
++ References:
++   C. Sims: Determining the conjugacy classes of a permutation group,
++   in Computers in Algebra and Number Theory, SIAM-AMS Proc., Vol. 4,
++    Amer. Math. Soc., Providence, R. I., 1971, pp. 191-195
++ Description:
++ PermutationGroup implements permutation groups acting
++ on a set S, i.e. all subgroups of the symmetric group of S,
++ represented as a list of permutations (generators). Note that
++ therefore the objects are not members of the \Language category
++ \spadtype{Group}.
++ Using the idea of base and strong generators by Sims,
++ basic routines and algorithms
++ are implemented so that the word problem for
++ permutation groups can be solved.
```

```
--++  Note: we plan to implement lattice operations on the subgroup
--++  lattice in a later release

PermutationGroup(S:SetCategory): public == private where

  L    ==> List
  PERM ==> Permutation
  FSET ==> Set
  I    ==> Integer
  NNI  ==> NonNegativeInteger
  V    ==> Vector
  B    ==> Boolean
  OUT   ==> OutputForm
  SYM  ==> Symbol
  REC  ==> Record ( orb : L NNI , svc : V I )
  REC2 ==> Record(order:NNI,sgset:L V NNI,_
             gpbase:L NNI,orbs:L REC,mp:L S,wd:L L NNI)
  REC3 ==> Record(elt:V NNI,lst:L NNI)
  REC4 ==> Record(bool:B,lst:L NNI)

  public ==> SetCategory with

    coerce           : %         -> L PERM S
      ++ coerce(gp) returns the generators of the group gp.
    generators           : %         -> L PERM S
      ++ generators(gp) returns the generators of the group gp.
    elt              : (%,NNI)   -> PERM S
      ++ elt(gp,i) returns the i-th generator of the group gp.
    random           : (%,I)     -> PERM S
      ++ random(gp,i) returns a random product of maximal i generators
      ++ of the group gp.
    random           : %         -> PERM S
      ++ random(gp) returns a random product of maximal 20 generators
      ++ of the group gp.
      ++ Note: random(gp)=random(gp,20).
    order            : %         -> NNI
      ++ order(gp) returns the order of the group gp.
    degree           : %         -> NNI
      ++ degree(gp) returns the number of points moved by all permutations
      ++ of the group gp.
    base             : %         -> L S
      ++ base(gp) returns a base for the group gp.
    strongGenerators : %         -> L PERM S
      ++ strongGenerators(gp) returns strong generators for
      ++ the group gp.
    wordsForStrongGenerators      : %         -> L L NNI
      ++ wordsForStrongGenerators(gp) returns the words for the strong
      ++ generators of the group gp in the original generators of
      ++ gp, represented by their indices in the list, given by
      ++ generators.
```

```
coerce           : L PERM S  -> %
  ++ coerce(ls) coerces a list of permutations ls to the group
  ++ generated by this list.
permutationGroup          : L PERM S  -> %
  ++ permutationGroup(ls) coerces a list of permutations ls to
  ++ the group generated by this list.
orbit            : (%,S)     -> FSET S
  ++ orbit(gp,el) returns the orbit of the element el under the
  ++ group gp, i.e. the set of all points gained by applying
  ++ each group element to el.
orbits           : %         -> FSET FSET S
  ++ orbits(gp) returns the orbits of the group gp, i.e.
  ++ it partitions the (finite) of all moved points.
orbit            : (%,FSET S)-> FSET FSET S
  ++ orbit(gp,els) returns the orbit of the unordered
  ++ set els under the group gp.
orbit            : (%,L S)   -> FSET L S
  ++ orbit(gp,ls) returns the orbit of the ordered
  ++ list ls under the group gp.
  ++ Note: return type is L L S temporarily because FSET L S has an error.
  -- (GILT DAS NOCH?)
member?          : (PERM S, %)-> B
  ++ member?(pp,gp) answers the question, whether the
  ++ permutation pp is in the group gp or not.
wordInStrongGenerators : (PERM S, %)-> L NNI
  ++ wordInStrongGenerators(p,gp) returns the word for the
  ++ permutation p in the strong generators of the group gp,
  ++ represented by the indices of the list, given by strongGenerators.
wordInGenerators : (PERM S, %)-> L NNI
  ++ wordInGenerators(p,gp) returns the word for the permutation p
  ++ in the original generators of the group gp,
  ++ represented by the indices of the list, given by generators.
movedPoints      : %         -> FSET S
  ++ movedPoints(gp) returns the points moved by the group gp.
"<"              : (%,%)     -> B
  ++ gp1 < gp2 returns true if and only if gp1
  ++ is a proper subgroup of gp2.
"<="             : (%,%)     -> B
  ++ gp1 <= gp2 returns true if and only if gp1
  ++ is a subgroup of gp2.
  ++ Note: because of a bug in the parser you have to call this
  ++ function explicitly by gp1 <=$(PERMGRP S) gp2.
  -- (GILT DAS NOCH?)
initializeGroupForWordProblem : %   -> Void
  ++ initializeGroupForWordProblem(gp) initializes the group gp
  ++ for the word problem.
  ++ Notes: it calls the other function of this name with parameters
  ++ 0 and 1: initializeGroupForWordProblem(gp,0,1).
  ++ Notes: (1) be careful: invoking this routine will destroy the
  ++ possibly information about your group (but will recompute it again)
```

```
    ++ (2) users need not call this function normally for the soultion of
    ++ the word problem.
  initializeGroupForWordProblem :(%,I,I) -> Void
    ++ initializeGroupForWordProblem(gp,m,n) initializes the group
    ++ gp for the word problem.
    ++ Notes: (1) with a small integer you get shorter words, but the
    ++ routine takes longer than the standard routine for longer words.
    ++ (2) be careful: invoking this routine will destroy the possibly stored
    ++ information about your group (but will recompute it again).
    ++ (3) users need not call this function normally for the soultion of
    ++ the word problem.

private ==> add

  -- representation of the object:

  Rep  := Record ( gens : L PERM S , information : REC2 )

  -- import of domains and packages

  import Permutation S
  import OutputForm
  import Symbol
  import Void

--first the local variables

  sgs               : L V NNI       := []
  baseOfGroup       : L NNI         := []
  sizeOfGroup       : NNI           := 1
  degree            : NNI           := 0
  gporb             : L REC         := []
  out               : L L V NNI     := []
  outword           : L L L NNI     := []
  wordlist          : L L NNI       := []
  basePoint         : NNI           := 0
  newBasePoint      : B             := true
  supp              : L S           := []
  ord               : NNI           := 1
  wordProblem       : B             := true

--local functions first, signatures:

  shortenWord:(L NNI, %)->L NNI
  times:(V NNI, V NNI)->V NNI
  strip:(V NNI,REC,L V NNI,L L NNI)->REC3
  orbitInternal:(%,L S )->L L S
  inv: V NNI->V NNI
  ranelt:(L V NNI,L L NNI, I)->REC3
  testIdentity:V NNI->B
```

```
    pointList: %->L S
    orbitWithSvc:(L V NNI ,NNI )->REC
    cosetRep:(NNI ,REC ,L V NNI )->REC3
    bsgs1:(L V NNI,NNI,L L NNI,I,%,I)->NNI
    computeOrbits: I->L NNI
    reduceGenerators: I->Void
    bsgs:(%, I, I)->NNI
    initialize: %->FSET PERM S
    knownGroup?: %->Void
    subgroup:(%, %)->B
    memberInternal:(PERM S, %, B)->REC4

  --local functions first, implementations:

    shortenWord ( lw : L NNI , gp : % ) : L NNI ==
      -- tries to shorten a word in the generators by removing identities
      gpgens : L PERM S := coerce gp
      orderList : L NNI := [ order gen for gen in gpgens ]
      newlw : L NNI := copy lw
      for i in 1.. maxIndex orderList repeat
        if orderList.i = 1 then
          while member?(i,newlw) repeat
          -- removing the trivial element
            pos := position(i,newlw)
            newlw := delete(newlw,pos)
      flag : B := true
      while flag repeat
        actualLength : NNI := (maxIndex newlw) pretend NNI
        pointer := actualLength
        test := newlw.pointer
        anzahl : NNI := 1
        flag := false
        while pointer > 1 repeat
          pointer := ( pointer - 1 )::NNI
          if newlw.pointer ^= test then
            -- don't get a trivial element, try next
            test := newlw.pointer
            anzahl := 1
          else
            anzahl := anzahl + 1
            if anzahl = orderList.test then
              -- we have an identity, so remove it
              for i in (pointer+anzahl)..actualLength repeat
                newlw.(i-anzahl) := newlw.i
              newlw := first(newlw, (actualLength - anzahl) :: NNI)
              flag := true
              pointer := 1
      newlw

    times ( p : V NNI , q : V NNI ) : V NNI ==
```

```
    -- internal multiplication of permutations
    [ qelt(p,qelt(q,i)) for i in 1..degree ]

  strip(element:V NNI,orbit:REC,group:L V NNI,words:L L NNI) : REC3 ==
    -- strip an element into the stabilizer
    actelt         := element
    schreierVector := orbit.svc
    point          := orbit.orb.1
    outlist        := nil()$(L NNI)
    entryLessZero  : B := false
    while ^entryLessZero repeat
      entry := schreierVector.(actelt.point)
      entryLessZero  := (entry < 0)
      if  ^entryLessZero then
        actelt := times(group.entry, actelt)
        if wordProblem then outlist := append ( words.(entry::NNI) , outlist )
    [ actelt , reverse outlist ]

  orbitInternal ( gp : % , startList : L S ) : L L S ==
    orbitList : L L S := [ startList ]
    pos  : I := 1
    while not zero? pos  repeat
      gpset : L PERM S := gp.gens
      for gen in gpset repeat
        newList  := nil()$(L S)
        workList := orbitList.pos
        for j in #workList..1 by -1 repeat
          newList := cons ( eval ( gen , workList.j ) , newList )
        if ^member?( newList , orbitList ) then
          orbitList := cons ( newList , orbitList )
          pos  := pos + 1
      pos := pos - 1
    reverse orbitList

  inv ( p : V NNI ) : V NNI ==
    -- internal inverse of a permutation
    q : V NNI := new(degree,0)$(V NNI)
    for i in 1..degree repeat q.(qelt(p,i)) := i
    q

  ranelt ( group : L V NNI , word : L L NNI , maxLoops : I ) : REC3 ==
    -- generate a "random" element
    numberOfGenerators    := # group
    randomInteger : I     := 1 + (random()$Integer rem numberOfGenerators)
    randomElement : V NNI := group.randomInteger
    words                 := nil()$(L NNI)
    if wordProblem then words := word.(randomInteger::NNI)
    if maxLoops > 0 then
      numberOfLoops : I  := 1 + (random()$Integer rem maxLoops)
    else
```

```
    numberOfLoops : I := maxLoops
  while numberOfLoops > 0 repeat
    randomInteger : I := 1 + (random()$Integer rem numberOfGenerators)
    randomElement := times ( group.randomInteger , randomElement )
    if wordProblem then words := append ( word.(randomInteger::NNI) , words)
    numberOfLoops := numberOfLoops - 1
  [ randomElement , words ]

testIdentity ( p : V NNI ) : B ==
  -- internal test for identity
  for i in 1..degree repeat qelt(p,i) ^= i => return false
  true

pointList(group : %) : L S ==
  support : FSET S :=  brace()   -- empty set !!
  for perm in group.gens repeat
    support := union(support, movedPoints perm)
  parts support

orbitWithSvc ( group : L V NNI , point : NNI ) : REC ==
  -- compute orbit with Schreier vector, "-2" means not in the orbit,
  -- "-1" means starting point, the PI correspond to generators
  newGroup := nil()$(L V NNI)
  for el in group repeat
    newGroup := cons ( inv el , newGroup )
  newGroup               := reverse newGroup
  orbit          : L NNI := [ point ]
  schreierVector : V I   := new ( degree , -2 )
  schreierVector.point   := -1
  position : I := 1
  while not zero? position repeat
    for i in 1..#newGroup repeat
      newPoint := orbit.position
      newPoint := newGroup.i.newPoint
      if ^ member? ( newPoint , orbit ) then
        orbit                  := cons ( newPoint , orbit )
        position               := position + 1
        schreierVector.newPoint := i
    position := position - 1
  [ reverse orbit , schreierVector ]

cosetRep ( point : NNI , o : REC , group : L V NNI ) : REC3 ==
  ppt          := point
  xelt : V NNI := [ n for n in 1..degree ]
  word         := nil()$(L NNI)
  oorb         := o.orb
  osvc         := o.svc
  while degree > 0 repeat
    p := osvc.ppt
    p < 0 => return [ xelt , word ]
```

```
      x    := group.p
      xelt := times ( x , xelt )
      if wordProblem then word := append ( wordlist.p , word )
      ppt  := x.ppt

  bsgs1 (group:L V NNI,number1:NNI,words:L L NNI,maxLoops:I,gp:%,diff:I)_
      : NNI ==
    -- try to get a good approximation for the strong generators and base
    for i in number1..degree repeat
      ort := orbitWithSvc ( group , i )
      k   := ort.orb
      k1  := # k
      if k1 ^= 1 then leave
    gpsgs := nil()$(L V NNI)
    words2 := nil()$(L L NNI)
    gplength : NNI := #group
    for jj in 1..gplength repeat if (group.jj).i ^= i then leave
    for k in 1..gplength repeat
      el2 := group.k
      if el2.i ^= i then
        gpsgs := cons ( el2 , gpsgs )
        if wordProblem then words2 := cons ( words.k , words2 )
      else
        gpsgs := cons ( times ( group.jj , el2 ) , gpsgs )
        if wordProblem _
          then words2 := cons ( append ( words.jj , words.k ) , words2 )
    group2 := nil()$(L V NNI)
    words3 := nil()$(L L NNI)
    j : I  := 15
    while j > 0 repeat
      -- find generators for the stabilizer
      ran := ranelt ( group , words , maxLoops )
      str := strip ( ran.elt , ort , group , words )
      el2 := str.elt
      if ^ testIdentity el2 then
        if ^ member?(el2,group2) then
          group2 := cons ( el2 , group2 )
          if wordProblem then
            help : L NNI := append ( reverse str.lst , ran.lst )
            help         := shortenWord ( help , gp )
            words3       := cons ( help , words3 )
          j := j - 2
      j := j - 1
    -- this is for word length control
    if wordProblem then maxLoops    := maxLoops - diff
    if ( null group2 ) or ( maxLoops < 0 ) then
      sizeOfGroup := k1
      baseOfGroup := [ i ]
      out         := [ gpsgs ]
      outword     := [ words2 ]
```

```
    return sizeOfGroup
  k2          := bsgs1 ( group2 , i + 1 , words3 , maxLoops , gp , diff )
  sizeOfGroup := k1 * k2
  out         := append ( out , [ gpsgs ] )
  outword     := append ( outword , [ words2 ] )
  baseOfGroup := cons ( i , baseOfGroup )
  sizeOfGroup

computeOrbits ( kkk : I ) : L NNI ==
  -- compute the orbits for the stabilizers
  sgs         := nil()
  orbitLength := nil()$(L NNI)
  gporb       := nil()
  for i in 1..#baseOfGroup repeat
    sgs         := append ( sgs , out.i )
    pt          := #baseOfGroup - i + 1
    obs         := orbitWithSvc ( sgs , baseOfGroup.pt )
    orbitLength := cons ( #obs.orb , orbitLength )
    gporb       := cons ( obs , gporb )
  gporb := reverse gporb
  reverse orbitLength

reduceGenerators ( kkk : I ) : Void ==
  -- try to reduce number of strong generators
  orbitLength := computeOrbits ( kkk )
  sgs         := nil()
  wordlist    := nil()
  for i in 1..(kkk-1) repeat
    sgs := append ( sgs , out.i )
    if wordProblem then wordlist := append ( wordlist , outword.i )
  removedGenerator := false
  baseLength : NNI := #baseOfGroup
  for nnn in kkk..(baseLength-1) repeat
    sgs := append ( sgs , out.nnn )
    if wordProblem then wordlist := append ( wordlist , outword.nnn )
    pt  := baseLength - nnn + 1
    obs := orbitWithSvc ( sgs , baseOfGroup.pt )
    i   := 1
    while not ( i > # out.nnn ) repeat
      pos  := position ( out.nnn.i , sgs )
      sgs2 := delete(sgs, pos)
      obs2 := orbitWithSvc ( sgs2 , baseOfGroup.pt )
      if # obs2.orb = orbitLength.nnn then
        test := true
        for j in (nnn+1)..(baseLength-1) repeat
          pt2  := baseLength - j + 1
          sgs2 := append ( sgs2 , out.j )
          obs2 := orbitWithSvc ( sgs2 , baseOfGroup.pt2 )
          if # obs2.orb ^= orbitLength.j then
            test := false
```

```
            leave
          if test then
            removedGenerator := true
            sgs              := delete (sgs, pos)
            if wordProblem then wordlist    := delete(wordlist, pos)
            out.nnn          := delete (out.nnn, i)
            if wordProblem then _
              outword.nnn := delete(outword.nnn, i )
          else
            i := i + 1
        else
          i := i + 1
    if removedGenerator then orbitLength := computeOrbits ( kkk )
    void()


  bsgs ( group : % ,maxLoops : I , diff : I ) : NNI ==
    -- the MOST IMPORTANT part of the package
    supp   := pointList group
    degree := # supp
    if degree = 0 then
      sizeOfGroup := 1
      sgs         := [ [ 0 ] ]
      baseOfGroup := nil()
      gporb       := nil()
      return sizeOfGroup
    newGroup := nil()$(L V NNI)
    gp       : L PERM S := group.gens
    words := nil()$(L L NNI)
    for ggg in 1..#gp repeat
      q := new(degree,0)$(V NNI)
      for i in 1..degree repeat
        newEl := eval ( gp.ggg , supp.i )
        pos2  := position ( newEl , supp )
        q.i   := pos2 pretend NNI
      newGroup := cons ( q , newGroup )
      if wordProblem then words    := cons(list ggg, words)
    if maxLoops < 1 then
      -- try to get the (approximate) base length
      if zero? (# ((group.information).gpbase)) then
        wordProblem := false
        k           := bsgs1 ( newGroup , 1 , words , 20 , group , 0 )
        wordProblem := true
        maxLoops    := (# baseOfGroup) - 1
      else
        maxLoops    := (# ((group.information).gpbase)) - 1
    k       := bsgs1 ( newGroup , 1 , words , maxLoops , group , diff )
    kkk : I := 1
    newGroup := reverse newGroup
    noAnswer : B := true
```

```
      while noAnswer repeat
        reduceGenerators kkk
-- *** Here is former "bsgs2" *** --
        -- test whether we have a base and a strong generating set
        sgs := nil()
        wordlist := nil()
        for i in 1..(kkk-1) repeat
          sgs := append ( sgs , out.i )
          if wordProblem then wordlist := append ( wordlist , outword.i )
        noresult : B := true
        for i in kkk..#baseOfGroup while noresult repeat
          sgs    := append ( sgs , out.i )
          if wordProblem then wordlist := append ( wordlist , outword.i )
          gporbi := gporb.i
          for pt in gporbi.orb while noresult repeat
            ppp   := cosetRep ( pt , gporbi , sgs )
            y1    := inv ppp.elt
            word3 := ppp.lst
            for jjj in 1..#sgs while noresult repeat
              word         := nil()$(L NNI)
              z            := times ( sgs.jjj , y1 )
              if wordProblem then word := append ( wordlist.jjj , word )
              ppp          := cosetRep ( (sgs.jjj).pt , gporbi , sgs )
              z            := times ( ppp.elt , z )
              if wordProblem then word := append ( ppp.lst , word )
              newBasePoint := false
              for j in (i-1)..1 by -1 while noresult repeat
                s := gporb.j.svc
                p := gporb.j.orb.1
                while ( degree > 0 ) and noresult repeat
                  entry := s.(z.p)
                  if entry < 0 then
                    if entry = -1 then leave
                    basePoint := j::NNI
                    noresult := false
                  else
                    ee := sgs.entry
                    z  := times ( ee , z )
                    if wordProblem then word := append ( wordlist.entry , word )
              if noresult then
                basePoint    := 1
                newBasePoint := true
                noresult := testIdentity z
        noAnswer := not (testIdentity z)
        if noAnswer then
          -- we have missed something
          word2 := nil()$(L NNI)
          if wordProblem then
            for wd in word3 repeat
              ttt := newGroup.wd
```

```
            while not (testIdentity ttt) repeat
              word2 := cons ( wd , word2 )
              ttt   := times ( ttt , newGroup.wd )
          word := append ( word , word2 )
          word := shortenWord ( word , group )
        if newBasePoint then
          for i in 1..degree repeat
            if z.i ^= i then
              baseOfGroup := append ( baseOfGroup , [ i ] )
              leave
          out := cons (list  z, out )
          if wordProblem then outword := cons (list word , outword )
        else
          out.basePoint := cons ( z , out.basePoint )
          if wordProblem then outword.basePoint := cons(word ,outword.basePoint )
        kkk := basePoint
    sizeOfGroup  := 1
    for j in 1..#baseOfGroup repeat
      sizeOfGroup := sizeOfGroup * # gporb.j.orb
    sizeOfGroup


  initialize ( group : % ) : FSET PERM S ==
    group2 := brace()$(FSET PERM S)
    gp : L PERM S := group.gens
    for gen in gp repeat
      if degree gen > 0 then insert_!(gen, group2)
    group2

  knownGroup? (gp : %) : Void ==
    -- do we know the group already?
    result := gp.information
    if result.order = 0 then
      wordProblem       := false
      ord               := bsgs ( gp , 20 , 0 )
      result            := [ ord , sgs , baseOfGroup , gporb , supp , [] ]
      gp.information    := result
    else
      ord         := result.order
      sgs         := result.sgset
      baseOfGroup := result.gpbase
      gporb       := result.orbs
      supp        := result.mp
      wordlist    := result.wd
    void

  subgroup ( gp1 : % , gp2 : % ) : B ==
    gpset1 := initialize gp1
    gpset2 := initialize gp2
    empty? difference (gpset1, gpset2) => true
```

```
      for el in parts gpset1 repeat
        not member? (el,  gp2) => return false
      true

    memberInternal ( p : PERM S , gp : % , flag : B ) : REC4 ==
      -- internal membership testing
      supp     := pointList gp
      outlist := nil()$(L NNI)
      mP : L S := parts movedPoints p
      for x in mP repeat
        not member? (x, supp) => return [ false , nil()$(L NNI) ]
      if flag then
        member? ( p , gp.gens ) => return [ true , nil()$(L NNI) ]
        knownGroup? gp
      else
        result := gp.information
        if #(result.wd) = 0 then
          initializeGroupForWordProblem gp
        else
          ord         := result.order
          sgs         := result.sgset
          baseOfGroup := result.gpbase
          gporb       := result.orbs
          supp        := result.mp
          wordlist    := result.wd
      degree := # supp
      pp := new(degree,0)$(V NNI)
      for i in 1..degree repeat
        el   := eval ( p , supp.i )
        pos  := position ( el , supp )
        pp.i := pos::NNI
      words := nil()$(L L NNI)
      if wordProblem then
        for i in 1..#sgs repeat
          lw : L NNI := [ (#sgs - i + 1)::NNI ]
          words := cons ( lw , words )
      for i in #baseOfGroup..1 by -1 repeat
        str := strip ( pp , gporb.i , sgs , words )
        pp := str.elt
        if wordProblem then outlist := append ( outlist , str.lst )
      [ testIdentity pp , reverse outlist ]

  --now the exported functions

    coerce ( gp : % ) : L PERM S == gp.gens
    generators ( gp : % ) : L PERM S == gp.gens

    strongGenerators ( group ) ==
      knownGroup? group
      degree := # supp
```

```
    strongGens := nil()$(L PERM S)
    for i in sgs repeat
      pairs := nil()$(L L S)
      for j in 1..degree repeat
        pairs := cons ( [ supp.j , supp.(i.j) ] , pairs )
      strongGens := cons ( coerceListOfPairs pairs , strongGens )
    reverse strongGens

  elt ( gp , i ) == (gp.gens).i

  movedPoints ( gp ) == brace pointList gp

  random ( group , maximalNumberOfFactors ) ==
    maximalNumberOfFactors < 1 => 1$(PERM S)
    gp : L PERM S := group.gens
    numberOfGenerators := # gp
    randomInteger : I  := 1 + (random()$Integer rem numberOfGenerators)
    randomElement      := gp.randomInteger
    numberOfLoops : I  := 1 + (random()$Integer rem maximalNumberOfFactors)
    while numberOfLoops > 0 repeat
      randomInteger : I  := 1 + (random()$Integer rem numberOfGenerators)
      randomElement := gp.randomInteger * randomElement
      numberOfLoops := numberOfLoops - 1
    randomElement

  random ( group ) == random ( group , 20 )

  order ( group ) ==
    knownGroup? group
    ord

  degree ( group ) == # pointList group

  base ( group ) ==
    knownGroup? group
    groupBase := nil()$(L S)
    for i in baseOfGroup repeat
      groupBase := cons ( supp.i , groupBase )
    reverse groupBase

  wordsForStrongGenerators ( group ) ==
    knownGroup? group
    wordlist

  coerce ( gp : L PERM S ) : % ==
    result : REC2 := [ 0 , [] , [] , [] , [] , [] ]
    group         := [ gp , result ]

  permutationGroup ( gp : L PERM S ) : % ==
    result : REC2 := [ 0 , [] , [] , [] , [] , [] ]
```

```
    group         := [ gp , result ]

  coerce(group: %) : OUT ==
    outList := nil()$(L OUT)
    gp : L PERM S := group.gens
    for i in (maxIndex gp)..1 by -1 repeat
      outList := cons(coerce gp.i, outList)
    postfix(outputForm(">":SYM),postfix(commaSeparate outList,outputForm("<":SYM)))

  orbit ( gp : % , el : S ) : FSET S ==
    elList : L S := [ el ]
    outList      := orbitInternal ( gp , elList )
    outSet       := brace()$(FSET S)
    for i in 1..#outList repeat
      insert_! ( outList.i.1 , outSet )
    outSet

  orbits ( gp ) ==
    spp    := movedPoints gp
    orbits := nil()$(L FSET S)
    while cardinality spp > 0 repeat
      el       := extract_! spp
      orbitSet := orbit ( gp , el )
      orbits   := cons ( orbitSet , orbits )
      spp      := difference ( spp , orbitSet )
    brace orbits

  member? (p,  gp) ==
    wordProblem := false
    mi := memberInternal ( p , gp , true )
    mi.bool

  wordInStrongGenerators (p, gp ) ==
    mi := memberInternal ( inv p , gp , false )
    not mi.bool => error "p is not an element of gp"
    mi.lst

  wordInGenerators (p,  gp) ==
    lll : L NNI := wordInStrongGenerators (p, gp)
    outlist := nil()$(L NNI)
    for wd in lll repeat
      outlist := append ( outlist , wordlist.wd )
    shortenWord ( outlist , gp )

  gp1 < gp2 ==
    not empty? difference ( movedPoints gp1 , movedPoints gp2 ) => false
    not subgroup ( gp1 , gp2 ) => false
    order gp1 = order gp2 => false
    true
```

```
    gp1 <= gp2 ==
      not empty?  difference ( movedPoints gp1 , movedPoints gp2 ) => false
      subgroup ( gp1 , gp2 )

    gp1 = gp2 ==
      movedPoints gp1 ^= movedPoints gp2 => false
      if #(gp1.gens) <= #(gp2.gens) then
        not subgroup ( gp1 , gp2 ) => return false
      else
        not subgroup ( gp2 , gp1 ) => return false
      order gp1 = order gp2 => true
      false

    orbit ( gp : % , startSet : FSET S ) : FSET FSET S ==
      startList : L S := parts startSet
      outList         := orbitInternal ( gp , startList )
      outSet          := brace()$(FSET FSET S)
      for i in 1..#outList repeat
        newSet : FSET S := brace outList.i
        insert_! ( newSet , outSet )
      outSet

    orbit ( gp : % , startList : L S ) : FSET L S ==
      brace orbitInternal(gp, startList)

    initializeGroupForWordProblem ( gp , maxLoops , diff ) ==
      wordProblem    := true
      ord            := bsgs ( gp , maxLoops , diff )
      gp.information := [ ord , sgs , baseOfGroup , gporb , supp , wordlist ]
      void

    initializeGroupForWordProblem ( gp ) == initializeGroupForWordProblem ( gp , 0 , 1 )
```

———-

— PERMGRP.dotabb —

```
"PERMGRP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PERMGRP"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"PERMGRP" -> "FSAGG"
```

———-

17.16 domain HACKPI Pi

— Pi.input —

```
)set break resume
)sys rm -f Pi.output
)spool Pi.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Pi
--R
--R Pi  is a domain constructor
--R Abbreviation for Pi is HACKPI
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for HACKPI
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,Integer) -> %                ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean        coerce : % -> Float
--R coerce : % -> DoubleFloat             coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              convert : % -> InputForm
--R convert : % -> DoubleFloat            convert : % -> Float
--R factor : % -> Factored(%)             gcd : List(%) -> %
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R one? : % -> Boolean                   pi : () -> %
--R prime? : % -> Boolean                 ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R retract : % -> Fraction(Integer)      retract : % -> Integer
--R sample : () -> %                      sizeLess? : (%,%) -> Boolean
--R squareFree : % -> Factored(%)         squareFreePart : % -> %
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R convert : % -> Fraction(SparseUnivariatePolynomial(Integer))
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
```

```
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R retractIfCan : % -> Union(Fraction(Integer),"failed")
--R retractIfCan : % -> Union(Integer,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— Pi.help —

```
=====================================================================
Pi examples
=====================================================================

See Also:
o )show Pi
```

———-

17.16.1 Pi (HACKPI)



See

⇒ “Expression” (EXPR) 6.6.1 on page 693

Exports:

0	1	associates?	characteristic	coerce
convert	divide	euclideanSize	expressIdealMember	exquo
extendedEuclidean	extendedEuclidean	factor	gcd	gcdPolynomial
hash	inv	latex	lcm	multiEuclidean
one?	pi	prime?	principalIdeal	recip
retract	retractIfCan	retractIfCan	sample	sizeLess?
squareFree	squareFreePart	subtractIfCan	unit?	unitCanonical
unitNormal	zero?	?*?	?**?	?+?
?-?	-?	?/?	?=?	?^?
?~=?	?quo?	?rem?		

— domain HACKPI Pi —

```
)abbrev domain HACKPI Pi
++ Author: Manuel Bronstein
++ Date Created: 21 Feb 1990
++ Date Last Updated: 12 Mai 1992
++ Description:
++ Symbolic fractions in %pi with integer coefficients;
++ The point for using Pi as the default domain for those fractions
++ is that Pi is coercible to the float types, and not Expression.

Pi(): Exports == Implementation where
  PZ ==> Polynomial Integer
  UP ==> SparseUnivariatePolynomial Integer
  RF ==> Fraction UP

  Exports ==> Join(Field, CharacteristicZero, RetractableTo Integer,
                   RetractableTo Fraction Integer, RealConstant,
                   CoercibleTo DoubleFloat, CoercibleTo Float,
                   ConvertibleTo RF, ConvertibleTo InputForm) with
    pi: () -> % ++ pi() returns the symbolic %pi.
  Implementation ==> RF add
    Rep := RF

    sympi := "%pi"::Symbol

    p2sf: UP -> DoubleFloat
    p2f : UP -> Float
    p2o : UP -> OutputForm
    p2i : UP -> InputForm
    p2p:  UP -> PZ

    pi()                    == (monomial(1, 1)$UP :: RF) pretend %
    convert(x:%):RF         == x pretend RF
    convert(x:%):Float      == x::Float
    convert(x:%):DoubleFloat == x::DoubleFloat
    coerce(x:%):DoubleFloat  == p2sf(numer x) / p2sf(denom x)
```

```
    coerce(x:%):Float       == p2f(numer x) / p2f(denom x)
    p2o p                   == outputForm(p, sympi::OutputForm)
    p2i p                   == convert p2p p

    p2p p ==
      ans:PZ := 0
      while p ^= 0 repeat
        ans := ans + monomial(leadingCoefficient(p)::PZ, sympi, degree p)
        p   := reductum p
      ans

    coerce(x:%):OutputForm ==
      (r := retractIfCan(x)@Union(UP, "failed")) case UP => p2o(r::UP)
      p2o(numer x) / p2o(denom x)

    convert(x:%):InputForm ==
      (r := retractIfCan(x)@Union(UP, "failed")) case UP => p2i(r::UP)
      p2i(numer x) / p2i(denom x)

    p2sf p ==
      map((x:Integer):DoubleFloat+->x::DoubleFloat, p)_
       $SparseUnivariatePolynomialFunctions2(Integer, DoubleFloat)
        (pi()$DoubleFloat)

    p2f p ==
      map((x:Integer):Float+->x::Float,p)_
       $SparseUnivariatePolynomialFunctions2(Integer, Float)
         (pi()$Float)
```

———-

— HACKPI.dotabb —

```
"HACKPI" [color="#88FF44",href="bookvol10.3.pdf#nameddest=HACKPI"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"HACKPI" -> "ALIST"
```

———-

17.17 domain ACPLOT PlaneAlgebraicCurvePlot

— PlaneAlgebraicCurvePlot.input —

```
)set break resume
```

```
)sys rm -f PlaneAlgebraicCurvePlot.output
)spool PlaneAlgebraicCurvePlot.output
)set message test on
)set message auto off
)clear all

--S 1 of 5
sketch:=makeSketch(x+y,x,y,-1/2..1/2,-1/2..1/2)$ACPLOT
--R
--R   (1)                    ACPLOT
--R                        1         1      1         1
--R        y + x = 0,   - - <= x <= -,   - - <= y <= -
--R                        2         2      2         2
--R                         [0.5,- 0.5]
--R                         [- 0.5,0.5]
--R                                                 Type: PlaneAlgebraicCurvePlot
--E 1

--S 2 of 5
refined:=refine(sketch,0.1)
--R
--R   (2)                      ACPLOT
--R                          1         1      1         1
--R          y + x = 0,   - - <= x <= -,   - - <= y <= -
--R                          2         2      2         2
--R                           [0.5,- 0.5]
--R          [0.49600000000000083,- 0.49600000000000083]
--R          [0.49200000000000083,- 0.49200000000000083]
--R          [0.48800000000000082,- 0.48800000000000082]
--R          [0.48400000000000082,- 0.48400000000000082]
--R          [0.48000000000000081,- 0.48000000000000081]
--R          [0.47600000000000081,- 0.47600000000000081]
--R          [0.47200000000000081,- 0.47200000000000081]
--R           [0.4680000000000008,- 0.4680000000000008]
--R           [0.4640000000000008,- 0.4640000000000008]
--R           [0.4600000000000008,- 0.4600000000000008]
--R          [0.45600000000000079,- 0.45600000000000079]
--R          [0.45200000000000079,- 0.45200000000000079]
--R          [0.44800000000000079,- 0.44800000000000079]
--R          [0.44400000000000078,- 0.44400000000000078]
--R          [0.44000000000000078,- 0.44000000000000078]
--R          [0.43600000000000078,- 0.43600000000000078]
--R          [0.43200000000000077,- 0.43200000000000077]
--R          [0.42800000000000077,- 0.42800000000000077]
--R          [0.42400000000000077,- 0.42400000000000077]
--R          [0.42000000000000076,- 0.42000000000000076]
--R          [0.41600000000000076,- 0.41600000000000076]
--R          [0.41200000000000075,- 0.41200000000000075]
--R          [0.40800000000000075,- 0.40800000000000075]
--R          [0.40400000000000075,- 0.40400000000000075]
```

```
--R          [0.40000000000000074,- 0.40000000000000074]
--R          [0.39600000000000074,- 0.39600000000000074]
--R          [0.39200000000000074,- 0.39200000000000074]
--R          [0.38800000000000073,- 0.38800000000000073]
--R          [0.38400000000000073,- 0.38400000000000073]
--R          [0.38000000000000073,- 0.38000000000000073]
--R          [0.37600000000000072,- 0.37600000000000072]
--R          [0.37200000000000072,- 0.37200000000000072]
--R          [0.36800000000000072,- 0.36800000000000072]
--R          [0.36400000000000071,- 0.36400000000000071]
--R          [0.36000000000000071,- 0.36000000000000071]
--R           [0.3560000000000007,- 0.3560000000000007]
--R           [0.3520000000000007,- 0.3520000000000007]
--R           [0.3480000000000007,- 0.3480000000000007]
--R          [0.34400000000000069,- 0.34400000000000069]
--R          [0.34000000000000069,- 0.34000000000000069]
--R          [0.33600000000000069,- 0.33600000000000069]
--R          [0.33200000000000068,- 0.33200000000000068]
--R          [0.32800000000000068,- 0.32800000000000068]
--R          [0.32400000000000068,- 0.32400000000000068]
--R          [0.32000000000000067,- 0.32000000000000067]
--R          [0.31600000000000067,- 0.31600000000000067]
--R          [0.31200000000000067,- 0.31200000000000067]
--R          [0.30800000000000066,- 0.30800000000000066]
--R          [0.30400000000000066,- 0.30400000000000066]
--R          [0.30000000000000066,- 0.30000000000000066]
--R          [0.29600000000000065,- 0.29600000000000065]
--R          [0.29200000000000065,- 0.29200000000000065]
--R          [0.28800000000000064,- 0.28800000000000064]
--R          [0.28400000000000064,- 0.28400000000000064]
--R          [0.28000000000000064,- 0.28000000000000064]
--R          [0.27600000000000063,- 0.27600000000000063]
--R          [0.27200000000000063,- 0.27200000000000063]
--R          [0.26800000000000063,- 0.26800000000000063]
--R          [0.26400000000000062,- 0.26400000000000062]
--R          [0.26000000000000062,- 0.26000000000000062]
--R          [0.25600000000000062,- 0.25600000000000062]
--R          [0.25200000000000061,- 0.25200000000000061]
--R          [0.24800000000000061,- 0.24800000000000061]
--R          [0.24400000000000061,- 0.24400000000000061]
--R           [0.2400000000000006,- 0.2400000000000006]
--R           [0.2360000000000006,- 0.2360000000000006]
--R          [0.23200000000000059,- 0.23200000000000059]
--R          [0.22800000000000059,- 0.22800000000000059]
--R          [0.22400000000000059,- 0.22400000000000059]
--R          [0.22000000000000058,- 0.22000000000000058]
--R          [0.21600000000000058,- 0.21600000000000058]
--R          [0.21200000000000058,- 0.21200000000000058]
--R          [0.20800000000000057,- 0.20800000000000057]
--R          [0.20400000000000057,- 0.20400000000000057]
```

```
--R          [0.20000000000000057,- 0.20000000000000057]
--R          [0.19600000000000056,- 0.19600000000000056]
--R          [0.19200000000000056,- 0.19200000000000056]
--R          [0.18800000000000056,- 0.18800000000000056]
--R          [0.18400000000000055,- 0.18400000000000055]
--R          [0.18000000000000055,- 0.18000000000000055]
--R          [0.17600000000000054,- 0.17600000000000054]
--R          [0.17200000000000054,- 0.17200000000000054]
--R          [0.16800000000000054,- 0.16800000000000054]
--R          [0.16400000000000053,- 0.16400000000000053]
--R          [0.16000000000000053,- 0.16000000000000053]
--R          [0.15600000000000053,- 0.15600000000000053]
--R          [0.15200000000000052,- 0.15200000000000052]
--R          [0.14800000000000052,- 0.14800000000000052]
--R          [0.14400000000000052,- 0.14400000000000052]
--R          [0.14000000000000051,- 0.14000000000000051]
--R          [0.13600000000000051,- 0.13600000000000051]
--R          [0.13200000000000051,- 0.13200000000000051]
--R           [0.1280000000000005,- 0.1280000000000005]
--R           [0.1240000000000005,- 0.1240000000000005]
--R           [0.1200000000000005,- 0.1200000000000005]
--R          [0.11600000000000049,- 0.11600000000000049]
--R          [0.11200000000000049,- 0.11200000000000049]
--R          [0.10800000000000048,- 0.10800000000000048]
--R          [0.10400000000000048,- 0.10400000000000048]
--R          [0.10000000000000048,- 0.10000000000000048]
--R        [9.6000000000000474E-2,- 9.6000000000000474E-2]
--R         [9.200000000000047E-2,- 9.200000000000047E-2]
--R        [8.8000000000000467E-2,- 8.8000000000000467E-2]
--R        [8.4000000000000463E-2,- 8.4000000000000463E-2]
--R         [8.000000000000046E-2,- 8.000000000000046E-2]
--R        [7.6000000000000456E-2,- 7.6000000000000456E-2]
--R        [7.2000000000000453E-2,- 7.2000000000000453E-2]
--R        [6.8000000000000449E-2,- 6.8000000000000449E-2]
--R        [6.4000000000000445E-2,- 6.4000000000000445E-2]
--R        [6.0000000000000442E-2,- 6.0000000000000442E-2]
--R        [5.6000000000000438E-2,- 5.6000000000000438E-2]
--R        [5.2000000000000435E-2,- 5.2000000000000435E-2]
--R        [4.8000000000000431E-2,- 4.8000000000000431E-2]
--R        [4.4000000000000428E-2,- 4.4000000000000428E-2]
--R        [4.0000000000000424E-2,- 4.0000000000000424E-2]
--R        [3.6000000000000421E-2,- 3.6000000000000421E-2]
--R        [3.2000000000000417E-2,- 3.2000000000000417E-2]
--R        [2.8000000000000417E-2,- 2.8000000000000417E-2]
--R        [2.4000000000000417E-2,- 2.4000000000000417E-2]
--R        [2.0000000000000417E-2,- 2.0000000000000417E-2]
--R        [1.6000000000000417E-2,- 1.6000000000000417E-2]
--R        [1.2000000000000417E-2,- 1.2000000000000417E-2]
--R        [8.0000000000004165E-3,- 8.0000000000004165E-3]
--R        [4.0000000000004164E-3,- 4.0000000000004164E-3]
```

```
--R        [4.163336342344337E-16,- 4.163336342344337E-16]
--R        [- 3.9999999999995837E-3,3.9999999999995837E-3]
--R        [- 7.9999999999995838E-3,7.9999999999995838E-3]
--R        [- 1.1999999999999584E-2,1.1999999999999584E-2]
--R        [- 1.5999999999999584E-2,1.5999999999999584E-2]
--R        [- 1.9999999999999584E-2,1.9999999999999584E-2]
--R        [- 2.3999999999999584E-2,2.3999999999999584E-2]
--R        [- 2.7999999999999584E-2,2.7999999999999584E-2]
--R        [- 3.1999999999999584E-2,3.1999999999999584E-2]
--R        [- 3.5999999999999588E-2,3.5999999999999588E-2]
--R        [- 3.9999999999999591E-2,3.9999999999999591E-2]
--R        [- 4.3999999999999595E-2,4.3999999999999595E-2]
--R        [- 4.7999999999999599E-2,4.7999999999999599E-2]
--R        [- 5.1999999999999602E-2,5.1999999999999602E-2]
--R        [- 5.5999999999999606E-2,5.5999999999999606E-2]
--R        [- 5.9999999999999609E-2,5.9999999999999609E-2]
--R        [- 6.3999999999999613E-2,6.3999999999999613E-2]
--R        [- 6.7999999999999616E-2,6.7999999999999616E-2]
--R         [- 7.199999999999962E-2,7.199999999999962E-2]
--R        [- 7.5999999999999623E-2,7.5999999999999623E-2]
--R        [- 7.9999999999999627E-2,7.9999999999999627E-2]
--R        [- 8.3999999999999631E-2,8.3999999999999631E-2]
--R        [- 8.7999999999999634E-2,8.7999999999999634E-2]
--R        [- 9.1999999999999638E-2,9.1999999999999638E-2]
--R        [- 9.5999999999999641E-2,9.5999999999999641E-2]
--R        [- 9.9999999999999645E-2,9.9999999999999645E-2]
--R          [- 0.10399999999999965,0.10399999999999965]
--R          [- 0.10799999999999965,0.10799999999999965]
--R          [- 0.11199999999999966,0.11199999999999966]
--R          [- 0.11599999999999966,0.11599999999999966]
--R          [- 0.11999999999999966,0.11999999999999966]
--R          [- 0.12399999999999967,0.12399999999999967]
--R          [- 0.12799999999999967,0.12799999999999967]
--R          [- 0.13199999999999967,0.13199999999999967]
--R          [- 0.13599999999999968,0.13599999999999968]
--R          [- 0.13999999999999968,0.13999999999999968]
--R          [- 0.14399999999999968,0.14399999999999968]
--R          [- 0.14799999999999969,0.14799999999999969]
--R          [- 0.15199999999999969,0.15199999999999969]
--R          [- 0.15599999999999969,0.15599999999999969]
--R           [- 0.1599999999999997,0.1599999999999997]
--R           [- 0.1639999999999997,0.1639999999999997]
--R          [- 0.16799999999999971,0.16799999999999971]
--R          [- 0.17199999999999971,0.17199999999999971]
--R          [- 0.17599999999999971,0.17599999999999971]
--R          [- 0.17999999999999972,0.17999999999999972]
--R          [- 0.18399999999999972,0.18399999999999972]
--R          [- 0.18799999999999972,0.18799999999999972]
--R          [- 0.19199999999999973,0.19199999999999973]
--R          [- 0.19599999999999973,0.19599999999999973]
```

```
--R          [- 0.19999999999999973,0.19999999999999973]
--R          [- 0.20399999999999974,0.20399999999999974]
--R          [- 0.20799999999999974,0.20799999999999974]
--R          [- 0.21199999999999974,0.21199999999999974]
--R          [- 0.21599999999999975,0.21599999999999975]
--R          [- 0.21999999999999975,0.21999999999999975]
--R          [- 0.22399999999999975,0.22399999999999975]
--R          [- 0.22799999999999976,0.22799999999999976]
--R          [- 0.23199999999999976,0.23199999999999976]
--R          [- 0.23599999999999977,0.23599999999999977]
--R          [- 0.23999999999999977,0.23999999999999977]
--R          [- 0.24399999999999977,0.24399999999999977]
--R          [- 0.24799999999999978,0.24799999999999978]
--R          [- 0.25199999999999978,0.25199999999999978]
--R          [- 0.25599999999999978,0.25599999999999978]
--R          [- 0.25999999999999979,0.25999999999999979]
--R          [- 0.26399999999999979,0.26399999999999979]
--R          [- 0.26799999999999979,0.26799999999999979]
--R           [- 0.2719999999999998,0.2719999999999998]
--R           [- 0.2759999999999998,0.2759999999999998]
--R           [- 0.2799999999999998,0.2799999999999998]
--R          [- 0.28399999999999981,0.28399999999999981]
--R          [- 0.28799999999999981,0.28799999999999981]
--R          [- 0.29199999999999982,0.29199999999999982]
--R          [- 0.29599999999999982,0.29599999999999982]
--R          [- 0.29999999999999982,0.29999999999999982]
--R          [- 0.30399999999999983,0.30399999999999983]
--R          [- 0.30799999999999983,0.30799999999999983]
--R          [- 0.31199999999999983,0.31199999999999983]
--R          [- 0.31599999999999984,0.31599999999999984]
--R          [- 0.31999999999999984,0.31999999999999984]
--R          [- 0.32399999999999984,0.32399999999999984]
--R          [- 0.32799999999999985,0.32799999999999985]
--R          [- 0.33199999999999985,0.33199999999999985]
--R          [- 0.33599999999999985,0.33599999999999985]
--R          [- 0.33999999999999986,0.33999999999999986]
--R          [- 0.34399999999999986,0.34399999999999986]
--R          [- 0.34799999999999986,0.34799999999999986]
--R          [- 0.35199999999999987,0.35199999999999987]
--R          [- 0.35599999999999987,0.35599999999999987]
--R          [- 0.35999999999999988,0.35999999999999988]
--R          [- 0.36399999999999988,0.36399999999999988]
--R          [- 0.36799999999999988,0.36799999999999988]
--R          [- 0.37199999999999989,0.37199999999999989]
--R          [- 0.37599999999999989,0.37599999999999989]
--R          [- 0.37999999999999989,0.37999999999999989]
--R           [- 0.3839999999999999,0.3839999999999999]
--R           [- 0.3879999999999999,0.3879999999999999]
--R           [- 0.3919999999999999,0.3919999999999999]
--R          [- 0.39599999999999991,0.39599999999999991]
```

```
--R          [- 0.39999999999999991,0.39999999999999991]
--R          [- 0.40399999999999991,0.40399999999999991]
--R          [- 0.40799999999999992,0.40799999999999992]
--R          [- 0.41199999999999992,0.41199999999999992]
--R          [- 0.41599999999999993,0.41599999999999993]
--R          [- 0.41999999999999993,0.41999999999999993]
--R          [- 0.42399999999999993,0.42399999999999993]
--R          [- 0.42799999999999994,0.42799999999999994]
--R          [- 0.43199999999999994,0.43199999999999994]
--R          [- 0.43599999999999994,0.43599999999999994]
--R          [- 0.43999999999999995,0.43999999999999995]
--R          [- 0.44399999999999995,0.44399999999999995]
--R          [- 0.44799999999999995,0.44799999999999995]
--R          [- 0.45199999999999996,0.45199999999999996]
--R          [- 0.45599999999999996,0.45599999999999996]
--R          [- 0.45999999999999996,0.45999999999999996]
--R          [- 0.46399999999999997,0.46399999999999997]
--R          [- 0.46799999999999997,0.46799999999999997]
--R          [- 0.47199999999999998,0.47199999999999998]
--R          [- 0.47599999999999998,0.47599999999999998]
--R          [- 0.47999999999999998,0.47999999999999998]
--R          [- 0.48399999999999999,0.48399999999999999]
--R          [- 0.48799999999999999,0.48799999999999999]
--R          [- 0.49199999999999999,0.49199999999999999]
--R                       [- 0.496,0.496]
--R                         [- 0.5,0.5]
--R                                                  Type: PlaneAlgebraicCurvePlot
--E 2

--S 3 of 5
listBranches(sketch)
--R
--R   (3)  [[[0.5,- 0.5],[- 0.5,0.5]]]
--R                                          Type: List(List(Point(DoubleFloat)))
--E 3

--S 4 of 5
listBranches(refined)
--R
--R   (4)
--R   [
--R     [[0.5,- 0.5], [0.49600000000000083,- 0.49600000000000083],
--R      [0.49200000000000083,- 0.49200000000000083],
--R      [0.48800000000000082,- 0.48800000000000082],
--R      [0.48400000000000082,- 0.48400000000000082],
--R      [0.48000000000000081,- 0.48000000000000081],
--R      [0.47600000000000081,- 0.47600000000000081],
--R      [0.47200000000000081,- 0.47200000000000081],
--R      [0.4680000000000008,- 0.4680000000000008],
--R      [0.4640000000000008,- 0.4640000000000008],
```

```
--R      [0.4600000000000008,- 0.4600000000000008],
--R      [0.4560000000000079,- 0.4560000000000079],
--R      [0.4520000000000079,- 0.4520000000000079],
--R      [0.4480000000000079,- 0.4480000000000079],
--R      [0.4440000000000078,- 0.4440000000000078],
--R      [0.4400000000000078,- 0.4400000000000078],
--R      [0.4360000000000078,- 0.4360000000000078],
--R      [0.4320000000000077,- 0.4320000000000077],
--R      [0.4280000000000077,- 0.4280000000000077],
--R      [0.4240000000000077,- 0.4240000000000077],
--R      [0.4200000000000076,- 0.4200000000000076],
--R      [0.4160000000000076,- 0.4160000000000076],
--R      [0.4120000000000075,- 0.4120000000000075],
--R      [0.4080000000000075,- 0.4080000000000075],
--R      [0.4040000000000075,- 0.4040000000000075],
--R      [0.4000000000000074,- 0.4000000000000074],
--R      [0.3960000000000074,- 0.3960000000000074],
--R      [0.3920000000000074,- 0.3920000000000074],
--R      [0.3880000000000073,- 0.3880000000000073],
--R      [0.3840000000000073,- 0.3840000000000073],
--R      [0.3800000000000073,- 0.3800000000000073],
--R      [0.3760000000000072,- 0.3760000000000072],
--R      [0.3720000000000072,- 0.3720000000000072],
--R      [0.3680000000000072,- 0.3680000000000072],
--R      [0.3640000000000071,- 0.3640000000000071],
--R      [0.3600000000000071,- 0.3600000000000071],
--R      [0.3560000000000007,- 0.3560000000000007],
--R      [0.3520000000000007,- 0.3520000000000007],
--R      [0.3480000000000007,- 0.3480000000000007],
--R      [0.3440000000000069,- 0.3440000000000069],
--R      [0.3400000000000069,- 0.3400000000000069],
--R      [0.3360000000000069,- 0.3360000000000069],
--R      [0.3320000000000068,- 0.3320000000000068],
--R      [0.3280000000000068,- 0.3280000000000068],
--R      [0.3240000000000068,- 0.3240000000000068],
--R      [0.3200000000000067,- 0.3200000000000067],
--R      [0.3160000000000067,- 0.3160000000000067],
--R      [0.3120000000000067,- 0.3120000000000067],
--R      [0.3080000000000066,- 0.3080000000000066],
--R      [0.3040000000000066,- 0.3040000000000066],
--R      [0.3000000000000066,- 0.3000000000000066],
--R      [0.2960000000000065,- 0.2960000000000065],
--R      [0.2920000000000065,- 0.2920000000000065],
--R      [0.2880000000000064,- 0.2880000000000064],
--R      [0.2840000000000064,- 0.2840000000000064],
--R      [0.2800000000000064,- 0.2800000000000064],
--R      [0.2760000000000063,- 0.2760000000000063],
--R      [0.2720000000000063,- 0.2720000000000063],
--R      [0.2680000000000063,- 0.2680000000000063],
--R      [0.2640000000000062,- 0.2640000000000062],
```

```
--R      [0.26000000000000062,- 0.26000000000000062],
--R      [0.25600000000000062,- 0.25600000000000062],
--R      [0.25200000000000061,- 0.25200000000000061],
--R      [0.24800000000000061,- 0.24800000000000061],
--R      [0.24400000000000061,- 0.24400000000000061],
--R      [0.2400000000000006,- 0.2400000000000006],
--R      [0.2360000000000006,- 0.2360000000000006],
--R      [0.23200000000000059,- 0.23200000000000059],
--R      [0.22800000000000059,- 0.22800000000000059],
--R      [0.22400000000000059,- 0.22400000000000059],
--R      [0.22000000000000058,- 0.22000000000000058],
--R      [0.21600000000000058,- 0.21600000000000058],
--R      [0.21200000000000058,- 0.21200000000000058],
--R      [0.20800000000000057,- 0.20800000000000057],
--R      [0.20400000000000057,- 0.20400000000000057],
--R      [0.20000000000000057,- 0.20000000000000057],
--R      [0.19600000000000056,- 0.19600000000000056],
--R      [0.19200000000000056,- 0.19200000000000056],
--R      [0.18800000000000056,- 0.18800000000000056],
--R      [0.18400000000000055,- 0.18400000000000055],
--R      [0.18000000000000055,- 0.18000000000000055],
--R      [0.17600000000000054,- 0.17600000000000054],
--R      [0.17200000000000054,- 0.17200000000000054],
--R      [0.16800000000000054,- 0.16800000000000054],
--R      [0.16400000000000053,- 0.16400000000000053],
--R      [0.16000000000000053,- 0.16000000000000053],
--R      [0.15600000000000053,- 0.15600000000000053],
--R      [0.15200000000000052,- 0.15200000000000052],
--R      [0.14800000000000052,- 0.14800000000000052],
--R      [0.14400000000000052,- 0.14400000000000052],
--R      [0.14000000000000051,- 0.14000000000000051],
--R      [0.13600000000000051,- 0.13600000000000051],
--R      [0.13200000000000051,- 0.13200000000000051],
--R      [0.1280000000000005,- 0.1280000000000005],
--R      [0.1240000000000005,- 0.1240000000000005],
--R      [0.1200000000000005,- 0.1200000000000005],
--R      [0.11600000000000049,- 0.11600000000000049],
--R      [0.11200000000000049,- 0.11200000000000049],
--R      [0.10800000000000048,- 0.10800000000000048],
--R      [0.10400000000000048,- 0.10400000000000048],
--R      [0.10000000000000048,- 0.10000000000000048],
--R      [9.6000000000000474E-2,- 9.6000000000000474E-2],
--R      [9.200000000000047E-2,- 9.200000000000047E-2],
--R      [8.8000000000000467E-2,- 8.8000000000000467E-2],
--R      [8.4000000000000463E-2,- 8.4000000000000463E-2],
--R      [8.000000000000046E-2,- 8.000000000000046E-2],
--R      [7.6000000000000456E-2,- 7.6000000000000456E-2],
--R      [7.2000000000000453E-2,- 7.2000000000000453E-2],
--R      [6.8000000000000449E-2,- 6.8000000000000449E-2],
--R      [6.4000000000000445E-2,- 6.4000000000000445E-2],
```

```
--R      [6.0000000000000442E-2,- 6.0000000000000442E-2],
--R      [5.6000000000000438E-2,- 5.6000000000000438E-2],
--R      [5.2000000000000435E-2,- 5.2000000000000435E-2],
--R      [4.8000000000000431E-2,- 4.8000000000000431E-2],
--R      [4.4000000000000428E-2,- 4.4000000000000428E-2],
--R      [4.0000000000000424E-2,- 4.0000000000000424E-2],
--R      [3.6000000000000421E-2,- 3.6000000000000421E-2],
--R      [3.2000000000000417E-2,- 3.2000000000000417E-2],
--R      [2.8000000000000417E-2,- 2.8000000000000417E-2],
--R      [2.4000000000000417E-2,- 2.4000000000000417E-2],
--R      [2.0000000000000417E-2,- 2.0000000000000417E-2],
--R      [1.6000000000000417E-2,- 1.6000000000000417E-2],
--R      [1.2000000000000417E-2,- 1.2000000000000417E-2],
--R      [8.0000000000004165E-3,- 8.0000000000004165E-3],
--R      [4.0000000000004164E-3,- 4.0000000000004164E-3],
--R      [4.163336342344337E-16,- 4.163336342344337E-16],
--R      [- 3.9999999999995837E-3,3.9999999999995837E-3],
--R      [- 7.9999999999995838E-3,7.9999999999995838E-3],
--R      [- 1.1999999999999584E-2,1.1999999999999584E-2],
--R      [- 1.5999999999999584E-2,1.5999999999999584E-2],
--R      [- 1.9999999999999584E-2,1.9999999999999584E-2],
--R      [- 2.3999999999999584E-2,2.3999999999999584E-2],
--R      [- 2.7999999999999584E-2,2.7999999999999584E-2],
--R      [- 3.1999999999999584E-2,3.1999999999999584E-2],
--R      [- 3.5999999999999588E-2,3.5999999999999588E-2],
--R      [- 3.9999999999999591E-2,3.9999999999999591E-2],
--R      [- 4.3999999999999595E-2,4.3999999999999595E-2],
--R      [- 4.7999999999999599E-2,4.7999999999999599E-2],
--R      [- 5.1999999999999602E-2,5.1999999999999602E-2],
--R      [- 5.5999999999999606E-2,5.5999999999999606E-2],
--R      [- 5.9999999999999609E-2,5.9999999999999609E-2],
--R      [- 6.3999999999999613E-2,6.3999999999999613E-2],
--R      [- 6.7999999999999616E-2,6.7999999999999616E-2],
--R      [- 7.199999999999962E-2,7.199999999999962E-2],
--R      [- 7.5999999999999623E-2,7.5999999999999623E-2],
--R      [- 7.9999999999999627E-2,7.9999999999999627E-2],
--R      [- 8.3999999999999631E-2,8.3999999999999631E-2],
--R      [- 8.7999999999999634E-2,8.7999999999999634E-2],
--R      [- 9.1999999999999638E-2,9.1999999999999638E-2],
--R      [- 9.5999999999999641E-2,9.5999999999999641E-2],
--R      [- 9.9999999999999645E-2,9.9999999999999645E-2],
--R      [- 0.10399999999999965,0.10399999999999965],
--R      [- 0.10799999999999965,0.10799999999999965],
--R      [- 0.11199999999999966,0.11199999999999966],
--R      [- 0.11599999999999966,0.11599999999999966],
--R      [- 0.11999999999999966,0.11999999999999966],
--R      [- 0.12399999999999967,0.12399999999999967],
--R      [- 0.12799999999999967,0.12799999999999967],
--R      [- 0.13199999999999967,0.13199999999999967],
--R      [- 0.13599999999999968,0.13599999999999968],
```

```
--R      [- 0.13999999999999968,0.13999999999999968],
--R      [- 0.14399999999999968,0.14399999999999968],
--R      [- 0.14799999999999969,0.14799999999999969],
--R      [- 0.15199999999999969,0.15199999999999969],
--R      [- 0.15599999999999969,0.15599999999999969],
--R      [- 0.1599999999999997,0.1599999999999997],
--R      [- 0.1639999999999997,0.1639999999999997],
--R      [- 0.16799999999999971,0.16799999999999971],
--R      [- 0.17199999999999971,0.17199999999999971],
--R      [- 0.17599999999999971,0.17599999999999971],
--R      [- 0.17999999999999972,0.17999999999999972],
--R      [- 0.18399999999999972,0.18399999999999972],
--R      [- 0.18799999999999972,0.18799999999999972],
--R      [- 0.19199999999999973,0.19199999999999973],
--R      [- 0.19599999999999973,0.19599999999999973],
--R      [- 0.19999999999999973,0.19999999999999973],
--R      [- 0.20399999999999974,0.20399999999999974],
--R      [- 0.20799999999999974,0.20799999999999974],
--R      [- 0.21199999999999974,0.21199999999999974],
--R      [- 0.21599999999999975,0.21599999999999975],
--R      [- 0.21999999999999975,0.21999999999999975],
--R      [- 0.22399999999999975,0.22399999999999975],
--R      [- 0.22799999999999976,0.22799999999999976],
--R      [- 0.23199999999999976,0.23199999999999976],
--R      [- 0.23599999999999977,0.23599999999999977],
--R      [- 0.23999999999999977,0.23999999999999977],
--R      [- 0.24399999999999977,0.24399999999999977],
--R      [- 0.24799999999999978,0.24799999999999978],
--R      [- 0.25199999999999978,0.25199999999999978],
--R      [- 0.25599999999999978,0.25599999999999978],
--R      [- 0.25999999999999979,0.25999999999999979],
--R      [- 0.26399999999999979,0.26399999999999979],
--R      [- 0.26799999999999979,0.26799999999999979],
--R      [- 0.2719999999999998,0.2719999999999998],
--R      [- 0.2759999999999998,0.2759999999999998],
--R      [- 0.2799999999999998,0.2799999999999998],
--R      [- 0.28399999999999981,0.28399999999999981],
--R      [- 0.28799999999999981,0.28799999999999981],
--R      [- 0.29199999999999982,0.29199999999999982],
--R      [- 0.29599999999999982,0.29599999999999982],
--R      [- 0.29999999999999982,0.29999999999999982],
--R      [- 0.30399999999999983,0.30399999999999983],
--R      [- 0.30799999999999983,0.30799999999999983],
--R      [- 0.31199999999999983,0.31199999999999983],
--R      [- 0.31599999999999984,0.31599999999999984],
--R      [- 0.31999999999999984,0.31999999999999984],
--R      [- 0.32399999999999984,0.32399999999999984],
--R      [- 0.32799999999999985,0.32799999999999985],
--R      [- 0.33199999999999985,0.33199999999999985],
--R      [- 0.33599999999999985,0.33599999999999985],
```

```
--R      [- 0.33999999999999986,0.33999999999999986],
--R      [- 0.34399999999999986,0.34399999999999986],
--R      [- 0.34799999999999986,0.34799999999999986],
--R      [- 0.35199999999999987,0.35199999999999987],
--R      [- 0.35599999999999987,0.35599999999999987],
--R      [- 0.35999999999999988,0.35999999999999988],
--R      [- 0.36399999999999988,0.36399999999999988],
--R      [- 0.36799999999999988,0.36799999999999988],
--R      [- 0.37199999999999989,0.37199999999999989],
--R      [- 0.37599999999999989,0.37599999999999989],
--R      [- 0.37999999999999989,0.37999999999999989],
--R      [- 0.3839999999999999,0.3839999999999999],
--R      [- 0.3879999999999999,0.3879999999999999],
--R      [- 0.3919999999999999,0.3919999999999999],
--R      [- 0.39599999999999991,0.39599999999999991],
--R      [- 0.39999999999999991,0.39999999999999991],
--R      [- 0.40399999999999991,0.40399999999999991],
--R      [- 0.40799999999999992,0.40799999999999992],
--R      [- 0.41199999999999992,0.41199999999999992],
--R      [- 0.41599999999999993,0.41599999999999993],
--R      [- 0.41999999999999993,0.41999999999999993],
--R      [- 0.42399999999999993,0.42399999999999993],
--R      [- 0.42799999999999994,0.42799999999999994],
--R      [- 0.43199999999999994,0.43199999999999994],
--R      [- 0.43599999999999994,0.43599999999999994],
--R      [- 0.43999999999999995,0.43999999999999995],
--R      [- 0.44399999999999995,0.44399999999999995],
--R      [- 0.44799999999999995,0.44799999999999995],
--R      [- 0.45199999999999996,0.45199999999999996],
--R      [- 0.45599999999999996,0.45599999999999996],
--R      [- 0.45999999999999996,0.45999999999999996],
--R      [- 0.46399999999999997,0.46399999999999997],
--R      [- 0.46799999999999997,0.46799999999999997],
--R      [- 0.47199999999999998,0.47199999999999998],
--R      [- 0.47599999999999998,0.47599999999999998],
--R      [- 0.47999999999999998,0.47999999999999998],
--R      [- 0.48399999999999999,0.48399999999999999],
--R      [- 0.48799999999999999,0.48799999999999999],
--R      [- 0.49199999999999999,0.49199999999999999], [- 0.496,0.496],
--R      [- 0.5,0.5]]
--R     ]
--R                                          Type: List(List(Point(DoubleFloat)))
--E 4

--S 5 of 5
)show ACPLOT
--R
--R PlaneAlgebraicCurvePlot  is a domain constructor
--R Abbreviation for PlaneAlgebraicCurvePlot is ACPLOT
--R This constructor is not exposed in this frame.
```

```
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ACPLOT
--R
--R------------------------------ Operations ------------------------------
--R coerce : % -> OutputForm              refine : (%,DoubleFloat) -> %
--R listBranches : % -> List(List(Point(DoubleFloat)))
--R makeSketch : (Polynomial(Integer),Symbol,Symbol,Segment(Fraction(Integer)),Segment(Fraction(Integer))) -
--R xRange : % -> Segment(DoubleFloat)
--R yRange : % -> Segment(DoubleFloat)
--R
--E 5


)spool
)lisp (bye)
```

———-


— PlaneAlgebraicCurvePlot.help —

```
=====================================================================
PlaneAlgebraicCurvePlot examples
=====================================================================

sketch:=makeSketch(x+y,x,y,-1/2..1/2,-1/2..1/2)$ACPLOT
```




```
refined:=refine(sketch,0.1)
```



```
                          [- 0.5,0.5]

listBranches(sketch)


   [[[0.5,- 0.5],[- 0.5,0.5]]]


listBranches(refined)

   [
     [[0.5,- 0.5], [0.49600000000000083,- 0.49600000000000083],
      [0.49200000000000083,- 0.49200000000000083],
      [0.48800000000000082,- 0.48800000000000082],
      ...
      [- 0.48399999999999999,0.48399999999999999],
      [- 0.48799999999999999,0.48799999999999999],
      [- 0.49199999999999999,0.49199999999999999], [- 0.496,0.496],
```

———-

17.17.1 PlaneAlgebraicCurvePlot (ACPLOT)



Exports:
coerce listBranches makeSketch refine xRange yRange

— domain ACPLOT PlaneAlgebraicCurvePlot —

```
)abbrev domain ACPLOT PlaneAlgebraicCurvePlot
++ Author: Clifton J. Williamson and Timothy Daly
++ Date Created: Fall 1988
++ Date Last Updated: 27 April 1990
++ Keywords: algebraic curve, non-singular, plot
++ Examples:
```

```
++ References:
++ Description:
++ Plot a NON-SINGULAR plane algebraic curve p(x,y) = 0.

PlaneAlgebraicCurvePlot(): PlottablePlaneCurveCategory _
 with

  makeSketch:(Polynomial Integer,Symbol,Symbol,Segment Fraction Integer,_
              Segment Fraction Integer) -> %
     ++ makeSketch(p,x,y,a..b,c..d) creates an ACPLOT of the
     ++ curve \spad{p = 0} in the region a <= x <= b, c <= y <= d.
     ++ More specifically, 'makeSketch' plots a non-singular algebraic curve
     ++ \spad{p = 0} in an rectangular region xMin <= x <= xMax,
     ++ yMin <= y <= yMax. The user inputs
     ++ \spad{makeSketch(p,x,y,xMin..xMax,yMin..yMax)}.
     ++ Here p is a polynomial in the variables x and y with
     ++ integer coefficients (p belongs to the domain
     ++ \spad{Polynomial Integer}). The case
     ++ where p is a polynomial in only one of the variables is
     ++ allowed.  The variables x and y are input to specify the
     ++ the coordinate axes.  The horizontal axis is the x-axis and
     ++ the vertical axis is the y-axis.  The rational numbers
     ++ xMin,...,yMax specify the boundaries of the region in
     ++ which the curve is to be plotted.
     ++
     ++X makeSketch(x+y,x,y,-1/2..1/2,-1/2..1/2)$ACPLOT

  refine:(%,DoubleFloat) -> %
     ++ refine(p,x) is not documented
     ++
     ++X sketch:=makeSketch(x+y,x,y,-1/2..1/2,-1/2..1/2)$ACPLOT
     ++X refined:=refine(sketch,0.1)

 == add

  import PointPackage DoubleFloat
  import Plot
  import RealSolvePackage

  BoundaryPts ==> Record(left:   List Point DoubleFloat,_
                         right:  List Point DoubleFloat,_
                         bottom: List Point DoubleFloat,_
                         top:    List Point DoubleFloat)

  NewPtInfo   ==> Record(newPt: Point DoubleFloat,_
                         type:  String)

  Corners     ==> Record(minXVal: DoubleFloat,_
                         maxXVal: DoubleFloat,_
                         minYVal: DoubleFloat,_
```

```
                    maxYVal: DoubleFloat)

kinte       ==> solve$RealSolvePackage()

rsolve      ==> realSolve$RealSolvePackage()

singValBetween?:(DoubleFloat,DoubleFloat,List DoubleFloat) -> Boolean

segmentInfo:(DoubleFloat -> DoubleFloat,DoubleFloat,DoubleFloat,_
             List DoubleFloat,List DoubleFloat,List DoubleFloat,_
             DoubleFloat,DoubleFloat) -> _
  Record(seg:Segment DoubleFloat,_
         left: DoubleFloat,_
         lowerVals: List DoubleFloat,_
         upperVals:List DoubleFloat)

swapCoords:Point DoubleFloat -> Point DoubleFloat

samePlottedPt?:(Point DoubleFloat,Point DoubleFloat) -> Boolean

findPtOnList:(Point DoubleFloat,List Point DoubleFloat) -> _
  Union(Point DoubleFloat,"failed")

makeCorners:(DoubleFloat,DoubleFloat,DoubleFloat,DoubleFloat) -> Corners

getXMin: Corners -> DoubleFloat

getXMax: Corners -> DoubleFloat

getYMin: Corners -> DoubleFloat

getYMax: Corners -> DoubleFloat

SFPolyToUPoly:Polynomial DoubleFloat -> _
  SparseUnivariatePolynomial DoubleFloat

RNPolyToUPoly:Polynomial Fraction Integer -> _
  SparseUnivariatePolynomial Fraction Integer

coerceCoefsToSFs:Polynomial Integer -> Polynomial DoubleFloat

coerceCoefsToRNs:Polynomial Integer -> Polynomial Fraction Integer

RNtoSF:Fraction Integer -> DoubleFloat

RNtoNF:Fraction Integer -> Float

SFtoNF:DoubleFloat -> Float

listPtsOnHorizBdry:(Polynomial Fraction Integer,Symbol,Fraction Integer,_
```

```
                    Float,Float) -> _
  List Point DoubleFloat

listPtsOnVertBdry:(Polynomial Fraction Integer,Symbol,Fraction Integer,_
                   Float,Float) -> _
  List Point DoubleFloat

listPtsInRect:(List List Float,Float,Float,Float,Float) -> _
  List Point DoubleFloat

ptsSuchThat?:(List List Float,List Float -> Boolean) -> Boolean

inRect?:(List Float,Float,Float,Float,Float) -> Boolean

onHorzSeg?:(List Float,Float,Float,Float) -> Boolean

onVertSeg?:(List Float,Float,Float,Float) -> Boolean

newX:(List List Float,List List Float,Float,Float,Float,Fraction Integer,_
      Fraction Integer) -> Fraction Integer

newY:(List List Float,List List Float,Float,Float,Float,_
      Fraction Integer,Fraction Integer) -> Fraction Integer

makeOneVarSketch:(Polynomial Integer,Symbol,Symbol,Fraction Integer,_
                  Fraction Integer,Fraction Integer,Fraction Integer,_
                  Symbol) -> %

makeLineSketch:(Polynomial Integer,Symbol,Symbol,Fraction Integer,_
                Fraction Integer,Fraction Integer,Fraction Integer) -> %

makeRatFcnSketch:(Polynomial Integer,Symbol,Symbol,Fraction Integer,_
                  Fraction Integer,Fraction Integer,Fraction Integer,_
                  Symbol) -> %

makeGeneralSketch:(Polynomial Integer,Symbol,Symbol,Fraction Integer,_
                   Fraction Integer,Fraction Integer,Fraction Integer) -> %

traceBranches:(Polynomial DoubleFloat,Polynomial DoubleFloat,_
               Polynomial DoubleFloat,Symbol,Symbol,Corners,DoubleFloat,_
               DoubleFloat,PositiveInteger, List Point DoubleFloat,_
               BoundaryPts) -> List List Point DoubleFloat

dummyFirstPt:(Point DoubleFloat,Polynomial DoubleFloat,_
              Polynomial DoubleFloat,Symbol,Symbol,List Point DoubleFloat,_
              List Point DoubleFloat,List Point DoubleFloat,_
              List Point DoubleFloat) -> Point DoubleFloat

listPtsOnSegment:(Polynomial DoubleFloat,Polynomial DoubleFloat,_
                  Polynomial DoubleFloat,Symbol,Symbol,Point DoubleFloat,_
```

```
                    Point DoubleFloat,Corners, DoubleFloat,DoubleFloat,_
                    PositiveInteger,List Point DoubleFloat,_
                    List Point DoubleFloat) -> List List Point DoubleFloat

  listPtsOnLoop:(Polynomial DoubleFloat,Polynomial DoubleFloat,_
                 Polynomial DoubleFloat,Symbol,Symbol,Point DoubleFloat,_
                 Corners, DoubleFloat,DoubleFloat,PositiveInteger,_
                 List Point DoubleFloat,List Point DoubleFloat) -> _
                 List List Point DoubleFloat

  computeNextPt:(Polynomial DoubleFloat,Polynomial DoubleFloat,_
                 Polynomial DoubleFloat,Symbol,Symbol,Point DoubleFloat,_
                 Point DoubleFloat,Corners, DoubleFloat,DoubleFloat,_
                 PositiveInteger,List Point DoubleFloat,_
                 List Point DoubleFloat) -> NewPtInfo

  newtonApprox:(SparseUnivariatePolynomial DoubleFloat, DoubleFloat, _
                DoubleFloat, PositiveInteger) -> Union(DoubleFloat, "failed")

--% representation

  Rep := Record(poly    : Polynomial Integer,_
                xVar    : Symbol,_
                yVar    : Symbol,_
                minXVal : Fraction Integer,_
                maxXVal : Fraction Integer,_
                minYVal : Fraction Integer,_
                maxYVal : Fraction Integer,_
                bdryPts : BoundaryPts,_
                hTanPts : List Point DoubleFloat,_
                vTanPts : List Point DoubleFloat,_
                branches: List List Point DoubleFloat)

--% global constants

  EPSILON : Float := .000001 -- precision to which realSolve finds roots
  PLOTERR : DoubleFloat := float(1,-3,10)
    -- maximum allowable difference in each coordinate when
    -- determining if 2 plotted points are equal

--% global flags

  NADA   : String := "nothing in particular"
  BDRY   : String := "boundary point"
  CRIT   : String := "critical point"
  BOTTOM : String := "bottom"
  TOP    : String := "top"

--% hacks
```

```
  NFtoSF: Float -> DoubleFloat
  NFtoSF x == 0 + convert(x)$Float

--% points
  makePt: (DoubleFloat,DoubleFloat) -> Point DoubleFloat
  makePt(xx,yy) == point(l : List DoubleFloat := [xx,yy])

  swapCoords(pt) == makePt(yCoord pt,xCoord pt)

  samePlottedPt?(p0,p1) ==
    -- determines if p1 lies in a square with side 2 PLOTERR
    -- centered at p0
    x0 := xCoord p0; y0 := yCoord p0
    x1 := xCoord p1; y1 := yCoord p1
    (abs(x1-x0) < PLOTERR) and (abs(y1-y0) < PLOTERR)

  findPtOnList(pt,pointList) ==
    for point in pointList repeat
      samePlottedPt?(pt,point) => return point
    "failed"

--% corners

  makeCorners(xMinSF,xMaxSF,yMinSF,yMaxSF) ==
    [xMinSF,xMaxSF,yMinSF,yMaxSF]

  getXMin(corners) == corners.minXVal
  getXMax(corners) == corners.maxXVal
  getYMin(corners) == corners.minYVal
  getYMax(corners) == corners.maxYVal

--% coercions

  SFPolyToUPoly(p) ==
  -- 'p' is of type Polynomial, but has only one variable
    zero? p => 0
    monomial(leadingCoefficient p,totalDegree p) +
       SFPolyToUPoly(reductum p)

  RNPolyToUPoly(p) ==
  -- 'p' is of type Polynomial, but has only one variable
    zero? p => 0
    monomial(leadingCoefficient p,totalDegree p) +
        RNPolyToUPoly(reductum p)

  coerceCoefsToSFs(p) ==
  -- coefficients of 'p' are coerced to be DoubleFloat's
    map(coerce,p)$PolynomialFunctions2(Integer,DoubleFloat)

  coerceCoefsToRNs(p) ==
```

```
  -- coefficients of 'p' are coerced to be DoubleFloat's
    map(coerce,p)$PolynomialFunctions2(Integer,Fraction Integer)

  RNtoSF(r) == coerce(r)@DoubleFloat
  RNtoNF(r) == coerce(r)@Float
  SFtoNF(x) == convert(x)@Float

--% computation of special points

  listPtsOnHorizBdry(pRN,y,y0,xMinNF,xMaxNF) ==
  -- strict inequality here: corners on vertical boundary
    pointList : List Point DoubleFloat := nil()
    ySF := RNtoSF(y0)
    f := eval(pRN,y,y0)
    roots : List Float := kinte(f,EPSILON)
    for root in roots repeat
      if (xMinNF < root) and (root < xMaxNF) then
        pointList := cons(makePt(NFtoSF root, ySF), pointList)
    pointList

  listPtsOnVertBdry(pRN,x,x0,yMinNF,yMaxNF) ==
    pointList : List Point DoubleFloat := nil()
    xSF := RNtoSF(x0)
    f := eval(pRN,x,x0)
    roots : List Float := kinte(f,EPSILON)
    for root in roots repeat
      if (yMinNF <= root) and (root <= yMaxNF) then
        pointList := cons(makePt(xSF, NFtoSF root), pointList)
    pointList

  listPtsInRect(points,xMin,xMax,yMin,yMax) ==
    pointList : List Point DoubleFloat := nil()
    for point in points repeat
      xx := first point; yy := second point
      if (xMin<=xx) and (xx<=xMax) and (yMin<=yy) and (yy<=yMax) then
        pointList := cons(makePt(NFtoSF xx,NFtoSF yy),pointList)
    pointList

  ptsSuchThat?(points,pred) ==
    for point in points repeat
      if pred point then return true
    false

  inRect?(point,xMinNF,xMaxNF,yMinNF,yMaxNF) ==
    xx := first point; yy := second point
    xMinNF <= xx and xx <= xMaxNF and yMinNF <= yy and yy <= yMaxNF

  onHorzSeg?(point,xMinNF,xMaxNF,yNF) ==
    xx := first point; yy := second point
    yy = yNF and xMinNF <= xx and xx <= xMaxNF
```

```
  onVertSeg?(point,yMinNF,yMaxNF,xNF) ==
    xx := first point; yy := second point
    xx = xNF and yMinNF <= yy and yy <= yMaxNF

  newX(vtanPts,singPts,yMinNF,yMaxNF,xNF,xRN,horizInc) ==
    xNewNF := xNF + RNtoNF horizInc
    xRtNF := max(xNF,xNewNF); xLftNF := min(xNF,xNewNF)
--  ptsSuchThat?(singPts,inRect?(#1,xLftNF,xRtNF,yMinNF,yMaxNF)) =>
    foo : List Float -> Boolean := x +-> inRect?(x,xLftNF,xRtNF,yMinNF,yMaxNF)
    ptsSuchThat?(singPts,foo) =>
      newX(vtanPts,singPts,yMinNF,yMaxNF,xNF,xRN,_
        horizInc/2::(Fraction Integer))
--  ptsSuchThat?(vtanPts,onVertSeg?(#1,yMinNF,yMaxNF,xNewNF)) =>
    goo : List Float -> Boolean := x +-> onVertSeg?(x,yMinNF,yMaxNF,xNewNF)
    ptsSuchThat?(vtanPts,goo) =>
      newX(vtanPts,singPts,yMinNF,yMaxNF,xNF,xRN,_
        horizInc/2::(Fraction Integer))
    xRN + horizInc

  newY(htanPts,singPts,xMinNF,xMaxNF,yNF,yRN,vertInc) ==
    yNewNF := yNF + RNtoNF vertInc
    yTopNF := max(yNF,yNewNF); yBotNF := min(yNF,yNewNF)
--  ptsSuchThat?(singPts,inRect?(#1,xMinNF,xMaxNF,yBotNF,yTopNF)) =>
    foo : List Float -> Boolean := x +-> inRect?(x,xMinNF,xMaxNF,yBotNF,yTopNF)
    ptsSuchThat?(singPts,foo) =>
      newY(htanPts,singPts,xMinNF,xMaxNF,yNF,yRN,_
        vertInc/2::(Fraction Integer))
--  ptsSuchThat?(htanPts,onHorzSeg?(#1,xMinNF,xMaxNF,yNewNF)) =>
    goo : List Float -> Boolean := x +-> onHorzSeg?(x,xMinNF,xMaxNF,yNewNF)
    ptsSuchThat?(htanPts,goo) =>
      newY(htanPts,singPts,xMinNF,xMaxNF,yNF,yRN,_
        vertInc/2::(Fraction Integer))
    yRN + vertInc

--% creation of sketches

  makeSketch(p,x,y,xRange,yRange) ==
    xMin := lo xRange; xMax := hi xRange
    yMin := lo yRange; yMax := hi yRange
    -- test input for consistency
    xMax <= xMin =>
      error "makeSketch: bad range for first variable"
    yMax <= yMin =>
      error "makeSketch: bad range for second variable"
    varList := variables p
    # varList > 2 =>
      error "makeSketch: polynomial in more than 2 variables"
    # varList = 0 =>
      error "makeSketch: constant polynomial"
```

```
    -- polynomial in 1 variable
    # varList = 1 =>
      (not member?(x,varList)) and (not member?(y,varList)) =>
        error "makeSketch: bad variables"
      makeOneVarSketch(p,x,y,xMin,xMax,yMin,yMax,first varList)
    -- polynomial in 2 variables
    (not member?(x,varList)) or (not member?(y,varList)) =>
      error "makeSketch: bad variables"
    totalDegree p = 1 =>
      makeLineSketch(p,x,y,xMin,xMax,yMin,yMax)
    -- polynomial is linear in one variable
    -- y is a rational function of x
    degree(p,y) = 1 =>
      makeRatFcnSketch(p,x,y,xMin,xMax,yMin,yMax,y)
    -- x is a rational function of y
    degree(p,x) = 1 =>
      makeRatFcnSketch(p,x,y,xMin,xMax,yMin,yMax,x)
    -- the general case
    makeGeneralSketch(p,x,y,xMin,xMax,yMin,yMax)

--% special cases

  makeOneVarSketch(p,x,y,xMin,xMax,yMin,yMax,var) ==
  -- the case where 'p' is a polynomial in only one variable
  -- the graph consists of horizontal or vertical lines
    if var = x then
      minVal := RNtoNF xMin
      maxVal := RNtoNF xMax
    else
      minVal := RNtoNF yMin
      maxVal := RNtoNF yMax
    lf : List Point DoubleFloat := nil()
    rt : List Point DoubleFloat := nil()
    bt : List Point DoubleFloat := nil()
    tp : List Point DoubleFloat := nil()
    htans : List Point DoubleFloat := nil()
    vtans : List Point DoubleFloat := nil()
    bran : List List Point DoubleFloat := nil()
    roots := kinte(p,EPSILON)
    sketchRoots : List DoubleFloat := nil()
    for root in roots repeat
      if (minVal <= root) and (root <= maxVal) then
          sketchRoots := cons(NFtoSF root,sketchRoots)
    null sketchRoots =>
      [p,x,y,xMin,xMax,yMin,yMax,[lf,rt,bt,tp],htans,vtans,bran]
    if var = x then
      yMinSF := RNtoSF yMin; yMaxSF := RNtoSF yMax
      for rootSF in sketchRoots repeat
          tp := cons(pt1 := makePt(rootSF,yMaxSF),tp)
          bt := cons(pt2 := makePt(rootSF,yMinSF),bt)
```

```
        branch : List Point DoubleFloat := [pt1,pt2]
        bran := cons(branch,bran)
  else
    xMinSF := RNtoSF xMin; xMaxSF := RNtoSF xMax
    for rootSF in sketchRoots repeat
        rt := cons(pt1 := makePt(xMaxSF,rootSF),rt)
        lf := cons(pt2 := makePt(xMinSF,rootSF),lf)
        branch : List Point DoubleFloat := [pt1,pt2]
        bran := cons(branch,bran)
  [p,x,y,xMin,xMax,yMin,yMax,[lf,rt,bt,tp],htans,vtans,bran]

makeLineSketch(p,x,y,xMin,xMax,yMin,yMax) ==
-- the case where p(x,y) = a x + b y + c with a ^= 0, b ^= 0
-- this is a line which is neither vertical nor horizontal
  xMinSF := RNtoSF xMin; xMaxSF := RNtoSF xMax
  yMinSF := RNtoSF yMin; yMaxSF := RNtoSF yMax
  -- determine the coefficients a, b, and c
  a := ground(coefficient(p,x,1)) :: DoubleFloat
  b := ground(coefficient(p,y,1)) :: DoubleFloat
  c := ground(coefficient(coefficient(p,x,0),y,0)) :: DoubleFloat
  lf : List Point DoubleFloat := nil()
  rt : List Point DoubleFloat := nil()
  bt : List Point DoubleFloat := nil()
  tp : List Point DoubleFloat := nil()
  htans : List Point DoubleFloat := nil()
  vtans : List Point DoubleFloat := nil()
  branch : List Point DoubleFloat := nil()
  bran : List List Point DoubleFloat := nil()
  -- compute x coordinate of point on line with y = yMin
  xBottom := (- b*yMinSF - c)/a
  -- compute x coordinate of point on line with y = yMax
  xTop    := (- b*yMaxSF - c)/a
  -- compute y coordinate of point on line with x = xMin
  yLeft   := (- a*xMinSF - c)/b
  -- compute y coordinate of point on line with x = xMax
  yRight  := (- a*xMaxSF - c)/b
  -- determine which of the above 4 points are in the region
  -- to be plotted and list them as a branch
  if (xMinSF < xBottom) and (xBottom < xMaxSF) then
      bt := cons(pt := makePt(xBottom,yMinSF),bt)
      branch := cons(pt,branch)
  if (xMinSF < xTop) and (xTop < xMaxSF) then
      tp := cons(pt := makePt(xTop,yMaxSF),tp)
      branch := cons(pt,branch)
  if (yMinSF <= yLeft) and (yLeft <= yMaxSF) then
      lf := cons(pt := makePt(xMinSF,yLeft),lf)
      branch := cons(pt,branch)
  if (yMinSF <= yRight) and (yRight <= yMaxSF) then
      rt := cons(pt := makePt(xMaxSF,yRight),rt)
      branch := cons(pt,branch)
```

```
    bran := cons(branch,bran)
    [p,x,y,xMin,xMax,yMin,yMax,[lf,rt,bt,tp],htans,vtans,bran]

  singValBetween?(xCurrent,xNext,xSingList) ==
    for xVal in xSingList repeat
      (xCurrent < xVal) and (xVal < xNext) => return true
    false

  segmentInfo(f,lo,hi,botList,topList,singList,minSF,maxSF) ==
    repeat
      -- 'current' is the smallest element of 'topList' and 'botList'
      -- 'currentFrom' records the list from which it was taken
      if null topList then
        if null botList then
          return [segment(lo,hi),hi,nil(),nil()]
        else
          current := first botList
          botList := rest  botList
          currentFrom := BOTTOM
      else
        if null botList then
          current := first topList
          topList := rest  topList
          currentFrom := TOP
        else
          bot := first botList
          top := first topList
          if bot < top then
            current := bot
            botList := rest botList
            currentFrom := BOTTOM
          else
            current := top
            topList := rest topList
            currentFrom := TOP
      -- 'nxt' is the next smallest element of 'topList'
      --  and 'botList'
      -- 'nextFrom' records the list from which it was taken
      if null topList then
        if null botList then
          return [segment(lo,hi),hi,nil(),nil()]
        else
          nxt := first botList
          botList := rest botList
          nextFrom := BOTTOM
      else
        if null botList then
          nxt := first topList
          topList := rest topList
          nextFrom := TOP
```

```
      else
        bot := first botList
        top := first topList
        if bot < top then
          nxt := bot
          botList := rest botList
          nextFrom := BOTTOM
        else
          nxt := top
          topList := rest topList
          nextFrom := TOP
    if currentFrom = nextFrom then
      if singValBetween?(current,nxt,singList) then
        return [segment(lo,current),nxt,botList,topList]
      else
        val := f((nxt - current)/2::DoubleFloat)
        if (val <= minSF) or (val >= maxSF) then
          return [segment(lo,current),nxt,botList,topList]
    else
      if singValBetween?(current,nxt,singList) then
        return [segment(lo,current),nxt,botList,topList]

makeRatFcnSketch(p,x,y,xMin,xMax,yMin,yMax,depVar) ==
-- the case where p(x,y) is linear in x or y
-- Thus, one variable is a rational function of the other.
-- Therefore, we may use the 2-dimensional function plotting
-- package.  The only problem is determining the intervals on
-- on which the function is to be plotted.
--!! corners: e.g. upper left corner is on graph with y' > 0
  factoredP := p ::(Factored Polynomial Integer)
  numberOfFactors(factoredP) > 1 =>
      error "reducible polynomial"  --!! sketch each factor
  dpdx := differentiate(p,x)
  dpdy := differentiate(p,y)
  pRN := coerceCoefsToRNs p
  xMinSF := RNtoSF xMin; xMaxSF := RNtoSF xMax
  yMinSF := RNtoSF yMin; yMaxSF := RNtoSF yMax
  xMinNF := RNtoNF xMin; xMaxNF := RNtoNF xMax
  yMinNF := RNtoNF yMin; yMaxNF := RNtoNF yMax
  -- 'p' is of degree 1 in the variable 'depVar'.
  -- Thus, 'depVar' is a rational function of the other variable.
  num := -coefficient(p,depVar,0)
  den :=  coefficient(p,depVar,1)
  numUPolySF := SFPolyToUPoly(coerceCoefsToSFs(num))
  denUPolySF := SFPolyToUPoly(coerceCoefsToSFs(den))
  -- this is the rational function
  f : DoubleFloat -> DoubleFloat := s +-> elt(numUPolySF,s)/elt(denUPolySF,s)
  -- values of the dependent and independent variables
  if depVar = x then
    indVarMin   := yMin;   indVarMax   := yMax
```

```
    indVarMinNF := yMinNF; indVarMaxNF := yMaxNF
    indVarMinSF := yMinSF; indVarMaxSF := yMaxSF
    depVarMin   := xMin;   depVarMax   := xMax
    depVarMinSF := xMinSF; depVarMaxSF := xMaxSF
  else
    indVarMin   := xMin;   indVarMax   := xMax
    indVarMinNF := xMinNF; indVarMaxNF := xMaxNF
    indVarMinSF := xMinSF; indVarMaxSF := xMaxSF
    depVarMin   := yMin;   depVarMax   := yMax
    depVarMinSF := yMinSF; depVarMaxSF := yMaxSF
  -- Create lists of critical points.
  htanPts := rsolve([p,dpdx],[x,y],EPSILON)
  vtanPts := rsolve([p,dpdy],[x,y],EPSILON)
  htans := listPtsInRect(htanPts,xMinNF,xMaxNF,yMinNF,yMaxNF)
  vtans := listPtsInRect(vtanPts,xMinNF,xMaxNF,yMinNF,yMaxNF)
  -- Create lists which will contain boundary points.
  lf : List Point DoubleFloat := nil()
  rt : List Point DoubleFloat := nil()
  bt : List Point DoubleFloat := nil()
  tp : List Point DoubleFloat := nil()
  -- Determine values of the independent variable at the which
  -- the rational function has a pole as well as the values of
  -- the independent variable for which there is a point on the
  -- upper or lower boundary.
  singList : List DoubleFloat :=
    roots : List Float := kinte(den,EPSILON)
    outList : List DoubleFloat := nil()
    for root in roots repeat
      if (indVarMinNF < root) and (root < indVarMaxNF) then
        outList := cons(NFtoSF root,outList)
    sort((x,y) +-> x < y, outList)
  topList : List DoubleFloat :=
    roots : List Float := kinte(eval(pRN,depVar,depVarMax),EPSILON)
    outList : List DoubleFloat := nil()
    for root in roots repeat
      if (indVarMinNF < root) and (root < indVarMaxNF) then
        outList := cons(NFtoSF root,outList)
    sort((x,y) +-> x < y, outList)
  botList : List DoubleFloat :=
    roots : List Float := kinte(eval(pRN,depVar,depVarMin),EPSILON)
    outList : List DoubleFloat := nil()
    for root in roots repeat
      if (indVarMinNF < root) and (root < indVarMaxNF) then
        outList := cons(NFtoSF root,outList)
    sort((x,y) +-> x < y, outList)
  -- We wish to determine if the graph has points on the 'left'
  -- and 'right' boundaries, so we compute the value of the
  -- rational function at the lefthand and righthand values of
  -- the dependent variable.  If the function has a singularity
  -- on the left or right boundary, then 'leftVal' or 'rightVal'
```

```
-- is given a dummy valuewhich will convince the program that
-- there is no point on the left or right boundary.
denUPolyRN := RNPolyToUPoly(coerceCoefsToRNs(den))
if elt(denUPolyRN,indVarMin) = 0$(Fraction Integer) then
  leftVal  := depVarMinSF - (abs(depVarMinSF) + 1$DoubleFloat)
else
  leftVal  := f(indVarMinSF)
if elt(denUPolyRN,indVarMax) = 0$(Fraction Integer) then
  rightVal := depVarMinSF - (abs(depVarMinSF) + 1$DoubleFloat)
else
  rightVal := f(indVarMaxSF)
-- Now put boundary points on the appropriate lists.
if depVar = x then
  if (xMinSF < leftVal) and (leftVal < xMaxSF) then
    bt := cons(makePt(leftVal,yMinSF),bt)
  if (xMinSF < rightVal) and (rightVal < xMaxSF) then
    tp := cons(makePt(rightVal,yMaxSF),tp)
  for val in botList repeat
    lf := cons(makePt(xMinSF,val),lf)
  for val in topList repeat
    rt := cons(makePt(xMaxSF,val),rt)
else
  if (yMinSF < leftVal) and (leftVal < yMaxSF) then
    lf := cons(makePt(xMinSF,leftVal),lf)
  if (yMinSF < rightVal) and (rightVal < yMaxSF) then
    rt := cons(makePt(xMaxSF,rightVal),rt)
  for val in botList repeat
    bt := cons(makePt(val,yMinSF),bt)
  for val in topList repeat
    tp := cons(makePt(val,yMaxSF),tp)
bran : List List Point DoubleFloat := nil()
-- Determine segments on which the rational function is to
-- be plotted.
if (depVarMinSF < leftVal) and (leftVal < depVarMaxSF) then
  lo := indVarMinSF
else
  if null topList then
    if null botList then
      return [p,x,y,xMin,xMax,yMin,yMax,[lf,rt,bt,tp],_
                                        htans,vtans,bran]
    else
      lo := first botList
      botList := rest botList
  else
    if null botList then
      lo := first topList
      topList := rest topList
    else
      bot := first botList
      top := first topList
```

```
        if bot < top then
          lo := bot
          botList := rest botList
        else
          lo := top
          topList := rest topList
    hi := 0$DoubleFloat  -- @#$%^&* compiler
    if (depVarMinSF < rightVal) and (rightVal < depVarMaxSF) then
      hi := indVarMaxSF
    else
      if null topList then
        if null botList then
          error "makeRatFcnSketch: plot domain"
        else
          hi := last botList
          botList := remove(hi,botList)
      else
        if null botList then
          hi := last topList
          topList := remove(hi,topList)
        else
          bot := last botList
          top := last topList
          if bot > top then
            hi := bot
            botList := remove(hi,botList)
          else
            hi := top
            topList := remove(hi,topList)
    if (depVar = x) then
      (minSF := xMinSF; maxSF := xMaxSF)
    else
      (minSF := yMinSF; maxSF := yMaxSF)
    segList : List Segment DoubleFloat := nil()
    repeat
      segInfo := segmentInfo(f,lo,hi,botList,topList,singList,_
                                 minSF,maxSF)
      segList := cons(segInfo.seg,segList)
      lo := segInfo.left
      botList := segInfo.lowerVals
      topList := segInfo.upperVals
      if lo = hi then break
    for segment in segList repeat
      RFPlot : Plot := plot(f,segment)
      curve := first(listBranches(RFPlot))
      if depVar = y then
        bran := cons(curve,bran)
      else
        bran := cons(map(swapCoords,curve),bran)
    [p,x,y,xMin,xMax,yMin,yMax,[lf,rt,bt,tp],htans,vtans,bran]
```

```
--% the general case

  makeGeneralSketch(pol,x,y,xMin,xMax,yMin,yMax) ==
    --!! corners of region should not be on curve
    --!! enlarge region if necessary
    factoredPol := pol :: (Factored Polynomial Integer)
    numberOfFactors(factoredPol) > 1 =>
        error "reducible polynomial"  --!! sketch each factor
    p := nthFactor(factoredPol,1)
    dpdx := differentiate(p,x); dpdy := differentiate(p,y)
    xMinNF := RNtoNF xMin; xMaxNF := RNtoNF xMax
    yMinNF := RNtoNF yMin; yMaxNF := RNtoNF yMax
    -- compute singular points; error if singularities in region
    singPts := rsolve([p,dpdx,dpdy],[x,y],EPSILON)
--  ptsSuchThat?(singPts,inRect?(#1,xMinNF,xMaxNF,yMinNF,yMaxNF)) =>
    foo : List Float -> Boolean := s +-> inRect?(s,xMinNF,xMaxNF,yMinNF,yMaxNF)
    ptsSuchThat?(singPts,foo) =>
      error "singular pts in region of sketch"
    -- compute critical points
    htanPts := rsolve([p,dpdx],[x,y],EPSILON)
    vtanPts := rsolve([p,dpdy],[x,y],EPSILON)
    critPts := append(htanPts,vtanPts)
    -- if there are critical points on the boundary, then enlarge
    -- the region, but be sure that the new region does not contain
    -- any singular points
    hInc : Fraction Integer := (1/20) * (xMax - xMin)
    vInc : Fraction Integer := (1/20) * (yMax - yMin)
--  if ptsSuchThat?(critPts,onVertSeg?(#1,yMinNF,yMaxNF,xMinNF)) then
    foo : List Float -> Boolean := s +-> onVertSeg?(s,yMinNF,yMaxNF,xMinNF)
    if ptsSuchThat?(critPts,foo) then
      xMin := newX(critPts,singPts,yMinNF,yMaxNF,xMinNF,xMin,-hInc)
      xMinNF := RNtoNF xMin
--  if ptsSuchThat?(critPts,onVertSeg?(#1,yMinNF,yMaxNF,xMaxNF)) then
    foo : List Float -> Boolean := s +-> onVertSeg?(s,yMinNF,yMaxNF,xMaxNF)
    if ptsSuchThat?(critPts,foo) then
      xMax := newX(critPts,singPts,yMinNF,yMaxNF,xMaxNF,xMax,hInc)
      xMaxNF := RNtoNF xMax
--  if ptsSuchThat?(critPts,onHorzSeg?(#1,xMinNF,xMaxNF,yMinNF)) then
    foo : List Float -> Boolean := s +-> onHorzSeg?(s,xMinNF,xMaxNF,yMinNF)
    if ptsSuchThat?(critPts,foo) then
      yMin := newY(critPts,singPts,xMinNF,xMaxNF,yMinNF,yMin,-vInc)
      yMinNF := RNtoNF yMin
--  if ptsSuchThat?(critPts,onHorzSeg?(#1,xMinNF,xMaxNF,yMaxNF)) then
    foo : List Float -> Boolean := s +-> onHorzSeg?(s,xMinNF,xMaxNF,yMaxNF)
    if ptsSuchThat?(critPts,foo) then
      yMax := newY(critPts,singPts,xMinNF,xMaxNF,yMaxNF,yMax,vInc)
      yMaxNF := RNtoNF yMax
    htans := listPtsInRect(htanPts,xMinNF,xMaxNF,yMinNF,yMaxNF)
    vtans := listPtsInRect(vtanPts,xMinNF,xMaxNF,yMinNF,yMaxNF)
```

```
    crits := append(htans,vtans)
    -- conversions to DoubleFloats
    xMinSF := RNtoSF xMin; xMaxSF := RNtoSF xMax
    yMinSF := RNtoSF yMin; yMaxSF := RNtoSF yMax
    corners := makeCorners(xMinSF,xMaxSF,yMinSF,yMaxSF)
    pSF := coerceCoefsToSFs p
    dpdxSF := coerceCoefsToSFs dpdx
    dpdySF := coerceCoefsToSFs dpdy
    delta := min((xMaxSF - xMinSF)/25,(yMaxSF - yMinSF)/25)
    err := min(delta/100,PLOTERR/100)
    bound : PositiveInteger := 10
    -- compute points on the boundary
    pRN := coerceCoefsToRNs(p)
    lf : List Point DoubleFloat :=
      listPtsOnVertBdry(pRN,x,xMin,yMinNF,yMaxNF)
    rt : List Point DoubleFloat :=
      listPtsOnVertBdry(pRN,x,xMax,yMinNF,yMaxNF)
    bt : List Point DoubleFloat :=
      listPtsOnHorizBdry(pRN,y,yMin,xMinNF,xMaxNF)
    tp : List Point DoubleFloat :=
      listPtsOnHorizBdry(pRN,y,yMax,xMinNF,xMaxNF)
    bdPts : BoundaryPts := [lf,rt,bt,tp]
    bran := traceBranches(pSF,dpdxSF,dpdySF,x,y,corners,delta,err,_
                          bound,crits,bdPts)
    [p,x,y,xMin,xMax,yMin,yMax,bdPts,htans,vtans,bran]

  refine(plot,stepFraction) ==
    p := plot.poly; x := plot.xVar; y := plot.yVar
    dpdx := differentiate(p,x); dpdy := differentiate(p,y)
    pSF := coerceCoefsToSFs p
    dpdxSF := coerceCoefsToSFs dpdx
    dpdySF := coerceCoefsToSFs dpdy
    xMin := plot.minXVal; xMax := plot.maxXVal
    yMin := plot.minYVal; yMax := plot.maxYVal
    xMinSF := RNtoSF xMin; xMaxSF := RNtoSF xMax
    yMinSF := RNtoSF yMin; yMaxSF := RNtoSF yMax
    corners := makeCorners(xMinSF,xMaxSF,yMinSF,yMaxSF)
    pSF := coerceCoefsToSFs p
    dpdxSF := coerceCoefsToSFs dpdx
    dpdySF := coerceCoefsToSFs dpdy
    delta :=
      stepFraction * min((xMaxSF - xMinSF)/25,(yMaxSF - yMinSF)/25)
    err := min(delta/100,PLOTERR/100)
    bound : PositiveInteger := 10
    crits := append(plot.hTanPts,plot.vTanPts)
    bdPts := plot.bdryPts
    bran := traceBranches(pSF,dpdxSF,dpdySF,x,y,corners,delta,err,_
                          bound,crits,bdPts)
    htans := plot.hTanPts; vtans := plot.vTanPts
    [p,x,y,xMin,xMax,yMin,yMax,bdPts,htans,vtans,bran]
```

```
traceBranches(pSF,dpdxSF,dpdySF,x,y,corners,delta,err,bound,_
                  crits,bdPts) ==
  -- for boundary points, trace curve from boundary to boundary
  -- add the branch to the list of branches
  -- update list of boundary points by deleting first and last
  -- points on this branch
  -- update list of critical points by deleting any critical
  -- points which were plotted
  lf := bdPts.left; rt := bdPts.right
  tp := bdPts.top ; bt := bdPts.bottom
  bdry := append(append(lf,rt),append(bt,tp))
  bran : List List Point DoubleFloat := nil()
  while not null bdry repeat
    pt := first bdry
    p0 := dummyFirstPt(pt,dpdxSF,dpdySF,x,y,lf,rt,bt,tp)
    segInfo := listPtsOnSegment(pSF,dpdxSF,dpdySF,x,y,p0,pt,_
                    corners,delta,err,bound,crits,bdry)
    bran  := cons(first segInfo,bran)
    crits := second segInfo
    bdry  := third segInfo
  -- trace loops beginning and ending with critical points
  -- add the branch to the list of branches
  -- update list of critical points by deleting any critical
  -- points which were plotted
  while not null crits repeat
    pt := first crits
    segInfo := listPtsOnLoop(pSF,dpdxSF,dpdySF,x,y,pt,_
                    corners,delta,err,bound,crits,bdry)
    bran  := cons(first segInfo,bran)
    crits := second segInfo
  bran

dummyFirstPt(p1,dpdxSF,dpdySF,x,y,lf,rt,bt,tp) ==
-- The function 'computeNextPt' requires 2 points, p0 and p1.
-- When computing the second point on a branch which starts
-- on the boundary, we use the boundary point as p1 and the
-- 'dummy' point returned by this function as p0.
  x1 := xCoord p1; y1 := yCoord p1
  zero := 0$DoubleFloat; one := 1$DoubleFloat
  px := ground(eval(dpdxSF,[x,y],[x1,y1]))
  py := ground(eval(dpdySF,[x,y],[x1,y1]))
  if px * py < zero then       -- positive slope at p1
    member?(p1,lf) or member?(p1,bt) =>
      makePt(x1 - one,y1 - one)
    makePt(x1 + one,y1 + one)
  else
    member?(p1,lf) or member?(p1,tp) =>
      makePt(x1 - one,y1 + one)
    makePt(x1 + one,y1 - one)
```

```
listPtsOnSegment(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                                delta,err,bound,crits,bdry) ==
-- p1 is a boundary point; p0 is a 'dummy' point
  bdry := remove(p1,bdry)
  pointList : List Point DoubleFloat := [p1]
  ptInfo := computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                                delta,err,bound,crits,bdry)
  p2 := ptInfo.newPt
  ptInfo.type = BDRY =>
    bdry := remove(p2,bdry)
    pointList := cons(p2,pointList)
    [pointList,crits,bdry]
  if ptInfo.type = CRIT then crits := remove(p2,crits)
  pointList := cons(p2,pointList)
  repeat
    pt0 := second pointList; pt1 := first pointList
    ptInfo := computeNextPt(pSF,dpdxSF,dpdySF,x,y,pt0,pt1,corners,_
                                 delta,err,bound,crits,bdry)
    p2 := ptInfo.newPt
    ptInfo.type = BDRY =>
      bdry := remove(p2,bdry)
      pointList := cons(p2,pointList)
      return [pointList,crits,bdry]
    if ptInfo.type = CRIT then crits := remove(p2,crits)
    pointList := cons(p2,pointList)
  --!! delete next line (compiler bug)
  [pointList,crits,bdry]


listPtsOnLoop(pSF,dpdxSF,dpdySF,x,y,p1,corners,_
                                delta,err,bound,crits,bdry) ==
  x1 := xCoord p1; y1 := yCoord p1
  px := ground(eval(dpdxSF,[x,y],[x1,y1]))
  py := ground(eval(dpdySF,[x,y],[x1,y1]))
  p0 := makePt(x1 - 1$DoubleFloat,y1 - 1$DoubleFloat)
  pointList : List Point DoubleFloat := [p1]
  ptInfo := computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                                delta,err,bound,crits,bdry)
  p2 := ptInfo.newPt
  ptInfo.type = BDRY =>
    error "boundary reached while on loop"
  if ptInfo.type = CRIT then
    p1 = p2 =>
      error "first and second points on loop are identical"
    crits := remove(p2,crits)
  pointList := cons(p2,pointList)
  repeat
    pt0 := second pointList; pt1 := first pointList
```

```
    ptInfo := computeNextPt(pSF,dpdxSF,dpdySF,x,y,pt0,pt1,corners,_
                                delta,err,bound,crits,bdry)
    p2 := ptInfo.newPt
    ptInfo.type = BDRY =>
      error "boundary reached while on loop"
    if ptInfo.type = CRIT then
      crits := remove(p2,crits)
      p1 = p2 =>
        pointList := cons(p2,pointList)
        return [pointList,crits,bdry]
    pointList := cons(p2,pointList)
  --!! delete next line (compiler bug)
  [pointList,crits,bdry]

computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                              delta,err,bound,crits,bdry) ==
-- p0=(x0,y0) and p1=(x1,y1) are the last two points on the curve.
-- The function computes the next point on the curve.
-- The function determines if the next point is a critical point
-- or a boundary point.
-- The function returns a record of the form
-- Record(newPt:Point DoubleFloat,type:String).
-- If the new point is a boundary point, then 'type' is
-- "boundary point" and 'newPt' is a boundary point to be
-- deleted from the list of boundary points yet to be plotted.
-- Similarly, if the new point is a critical point, then 'type' is
-- "critical point" and 'newPt' is a critical point to be
-- deleted from the list of critical points yet to be plotted.
-- If the new point is neither a critical point nor a boundary
-- point, then 'type' is "nothing in particular".
  xMinSF := getXMin corners; xMaxSF := getXMax corners
  yMinSF := getYMin corners; yMaxSF := getYMax corners
  x0 := xCoord p0; y0 := yCoord p0
  x1 := xCoord p1; y1 := yCoord p1
  px := ground(eval(dpdxSF,[x,y],[x1,y1]))
  py := ground(eval(dpdySF,[x,y],[x1,y1]))
  -- let m be the slope of the tangent line at p1
  -- if |m| < 1, we will increment the x-coordinate by delta
  -- (indicated by 'incVar = x'), find an approximate
  -- y-coordinate using the tangent line, then find the actual
  -- y-coordinate using a Newton iteration
  if abs(py) > abs(px) then
    incVar0 := incVar := x
    deltaX := (if x1 > x0 then delta else -delta)
    x2Approx := x1 + deltaX
    y2Approx := y1 + (-px/py)*deltaX
  -- if |m| >= 1, we interchange the roles of the x- and y-
  -- coordinates
  else
    incVar0 := incVar := y
```

```
  deltaY := (if y1 > y0 then delta else -delta)
  x2Approx := x1 + (-py/px)*deltaY
  y2Approx := y1 + deltaY
lookingFor := NADA
-- See if (x2Approx,y2Approx) is out of bounds.
-- If so, find where the line segment connecting (x1,y1) and
-- (x2Approx,y2Approx) intersects the boundary and use this
-- point as (x2Approx,y2Approx).
-- If the resulting point is on the left or right boundary,
-- we will now consider x as the 'incremented variable' and we
-- will compute the y-coordinate using a Newton iteration.
-- Similarly, if the point is on the top or bottom boundary,
-- we will consider y as the 'incremented variable' and we
-- will compute the x-coordinate using a Newton iteration.
if x2Approx >= xMaxSF then
  incVar := x
  lookingFor := BDRY
  x2Approx := xMaxSF
  y2Approx := y1 + (-px/py)*(x2Approx - x1)
else
  if x2Approx <= xMinSF then
    incVar := x
    lookingFor := BDRY
    x2Approx := xMinSF
    y2Approx := y1 + (-px/py)*(x2Approx - x1)
if y2Approx >= yMaxSF then
  incVar := y
  lookingFor := BDRY
  y2Approx := yMaxSF
  x2Approx := x1 + (-py/px)*(y2Approx - y1)
else
  if y2Approx <= yMinSF then
    incVar := y
    lookingFor := BDRY
    y2Approx := yMinSF
    x2Approx := x1 + (-py/px)*(y2Approx - y1)
-- set xLo = min(x1,x2Approx), xHi = max(x1,x2Approx)
-- set yLo = min(y1,y2Approx), yHi = max(y1,y2Approx)
if x1 < x2Approx then
  xLo := x1
  xHi := x2Approx
else
  xLo := x2Approx
  xHi := x1
if y1 < y2Approx then
  yLo := y1
  yHi := y2Approx
else
  yLo := y2Approx
  yHi := y1
```

```
-- check for critical points (x*,y*) with x* between
-- x1 and x2Approx or y* between y1 and y2Approx
-- store values of x2Approx and y2Approx
x2Approxx := x2Approx
y2Approxx := y2Approx
-- xPointList will contain all critical points (x*,y*)
-- with x* between x1 and x2Approx
xPointList : List Point DoubleFloat := nil()
-- yPointList will contain all critical points (x*,y*)
-- with y* between y1 and y2Approx
yPointList : List Point DoubleFloat := nil()
for pt in crits repeat
  xx := xCoord pt; yy := yCoord pt
  -- if x1 = x2Approx, then p1 is a point with horizontal
  -- tangent line
  -- in this case, we don't want critical points with
  -- x-coordinate x1
  if xx = x2Approx and not (xx = x1) then
    if min(abs(yy-yLo),abs(yy-yHi)) < delta then
      xPointList := cons(pt,xPointList)
  if ((xLo < xx) and (xx < xHi)) then
    if min(abs(yy-yLo),abs(yy-yHi)) < delta then
      xPointList := cons(pt,nil())
      x2Approx := xx
      if xx < x1 then xLo := xx else xHi := xx
  -- if y1 = y2Approx, then p1 is a point with vertical
  -- tangent line
  -- in this case, we don't want critical points with
  -- y-coordinate y1
  if yy = y2Approx and not (yy = y1) then
      yPointList := cons(pt,yPointList)
  if ((yLo < yy) and (yy < yHi)) then
    if min(abs(xx-xLo),abs(xx-xHi)) < delta then
      yPointList := cons(pt,nil())
      y2Approx := yy
      if yy < y1 then yLo := yy else yHi := yy
-- points in both xPointList and yPointList
if (not null xPointList) and (not null yPointList) then
  xPointList = yPointList =>
  -- this implies that the lists have only one point
    incVar := incVar0
    if incVar = x then
      y2Approx := y1 + (-px/py)*(x2Approx - x1)
    else
      x2Approx := x1 + (-py/px)*(y2Approx - y1)
    lookingFor := CRIT        -- proceed
  incVar0 = x =>
  -- first try Newton iteration with 'y' as incremented variable
    x2Temp := x1 + (-py/px)*(y2Approx - y1)
    f := SFPolyToUPoly(eval(pSF,y,y2Approx))
```

```
  x2New := newtonApprox(f,x2Temp,err,bound)
  x2New case "failed" =>
    y2Approx := y1 + (-px/py)*(x2Approx - x1)
    incVar := x
    lookingFor := CRIT      -- proceed
  y2Temp := y1 + (-px/py)*(x2Approx - x1)
  f := SFPolyToUPoly(eval(pSF,x,x2Approx))
  y2New := newtonApprox(f,y2Temp,err,bound)
  y2New case "failed" =>
    return computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                  abs((x2Approx-x1)/2),err,bound,crits,bdry)
  pt1 := makePt(x2Approx,y2New :: DoubleFloat)
  pt2 := makePt(x2New :: DoubleFloat,y2Approx)
  critPt1 := findPtOnList(pt1,crits)
  critPt2 := findPtOnList(pt2,crits)
  (critPt1 case "failed") and (critPt2 case "failed") =>
    abs(x2Approx - x1) > abs(x2Temp - x1) =>
      return [pt1,NADA]
    return [pt2,NADA]
  (critPt1 case "failed") =>
    return [critPt2::(Point DoubleFloat),CRIT]
  (critPt2 case "failed") =>
    return [critPt1::(Point DoubleFloat),CRIT]
  abs(x2Approx - x1) > abs(x2Temp - x1) =>
    return [critPt2::(Point DoubleFloat),CRIT]
  return [critPt1::(Point DoubleFloat),CRIT]
y2Temp := y1 + (-px/py)*(x2Approx - x1)
f := SFPolyToUPoly(eval(pSF,x,x2Approx))
y2New := newtonApprox(f,y2Temp,err,bound)
y2New case "failed" =>
  x2Approx := x1 + (-py/px)*(y2Approx - y1)
  incVar := y
  lookingFor := CRIT      -- proceed
x2Temp := x1 + (-py/px)*(y2Approx - y1)
f := SFPolyToUPoly(eval(pSF,y,y2Approx))
x2New := newtonApprox(f,x2Temp,err,bound)
x2New case "failed" =>
  return computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                abs((y2Approx-y1)/2),err,bound,crits,bdry)
pt1 := makePt(x2Approx,y2New :: DoubleFloat)
pt2 := makePt(x2New :: DoubleFloat,y2Approx)
critPt1 := findPtOnList(pt1,crits)
critPt2 := findPtOnList(pt2,crits)
(critPt1 case "failed") and (critPt2 case "failed") =>
  abs(y2Approx - y1) > abs(y2Temp - y1) =>
    return [pt2,NADA]
  return [pt1,NADA]
(critPt1 case "failed") =>
  return [critPt2::(Point DoubleFloat),CRIT]
(critPt2 case "failed") =>
```

```
      return [critPt1::(Point DoubleFloat),CRIT]
    abs(y2Approx - y1) > abs(y2Temp - y1) =>
      return [critPt1::(Point DoubleFloat),CRIT]
    return [critPt2::(Point DoubleFloat),CRIT]
  if (not null xPointList) and (null yPointList) then
    y2Approx := y1 + (-px/py)*(x2Approx - x1)
    incVar0 = x =>
      incVar := x
      lookingFor := CRIT        -- proceed
    f := SFPolyToUPoly(eval(pSF,x,x2Approx))
    y2New := newtonApprox(f,y2Approx,err,bound)
    y2New case "failed" =>
      x2Approx := x2Approxx
      y2Approx := y2Approxx     -- proceed
    pt := makePt(x2Approx,y2New::DoubleFloat)
    critPt := findPtOnList(pt,crits)
    critPt case "failed" =>
      return [pt,NADA]
    return [critPt :: (Point DoubleFloat),CRIT]
  if (null xPointList) and (not null yPointList) then
    x2Approx := x1 + (-py/px)*(y2Approx - y1)
    incVar0 = y =>
      incVar := y
      lookingFor := CRIT        -- proceed
    f := SFPolyToUPoly(eval(pSF,y,y2Approx))
    x2New := newtonApprox(f,x2Approx,err,bound)
    x2New case "failed" =>
      x2Approx := x2Approxx
      y2Approx := y2Approxx     -- proceed
    pt := makePt(x2New::DoubleFloat,y2Approx)
    critPt := findPtOnList(pt,crits)
    critPt case "failed" =>
      return [pt,NADA]
    return [critPt :: (Point DoubleFloat),CRIT]
  if incVar = x then
    x2 := x2Approx
    f := SFPolyToUPoly(eval(pSF,x,x2))
    y2New := newtonApprox(f,y2Approx,err,bound)
    y2New case "failed" =>
      return computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                           abs((x2-x1)/2),err,bound,crits,bdry)
    y2 := y2New :: DoubleFloat
  else
    y2 := y2Approx
    f := SFPolyToUPoly(eval(pSF,y,y2))
    x2New := newtonApprox(f,x2Approx,err,bound)
    x2New case "failed" =>
      return computeNextPt(pSF,dpdxSF,dpdySF,x,y,p0,p1,corners,_
                           abs((y2-y1)/2),err,bound,crits,bdry)
    x2 := x2New :: DoubleFloat
```

```
    pt := makePt(x2,y2)
    --!! check that 'pt' is not out of bounds
    -- check if you've gotten a critical or boundary point
    lookingFor = NADA =>
      [pt,lookingFor]
    lookingFor = BDRY =>
      bdryPt := findPtOnList(pt,bdry)
      bdryPt case "failed" =>
        error "couldn't find boundary point"
      [bdryPt :: (Point DoubleFloat),BDRY]
    critPt := findPtOnList(pt,crits)
    critPt case "failed" =>
      [pt,NADA]
    [critPt :: (Point DoubleFloat),CRIT]

--% Newton iterations

  newtonApprox(f,a0,err,bound) ==
  -- Newton iteration to approximate a root of the polynomial 'f'
  -- using an initial approximation of 'a0'
  -- Newton iteration terminates when consecutive approximations
  -- are within 'err' of each other
  -- returns "failed" if this has not been achieved after 'bound'
  -- iterations
    Df := differentiate f
    oldApprox := a0
    newApprox := a0 - elt(f,a0)/elt(Df,a0)
    i : PositiveInteger := 1
    while abs(newApprox - oldApprox) > err repeat
      i = bound => return "failed"
      oldApprox := newApprox
      newApprox := oldApprox - elt(f,oldApprox)/elt(Df,oldApprox)
      i := i+1
    newApprox

--% graphics output

  listBranches(acplot) == acplot.branches

--% terminal output

  coerce(acplot:%) ==
    pp := acplot.poly :: OutputForm
    xx := acplot.xVar :: OutputForm
    yy := acplot.yVar :: OutputForm
    xLo := acplot.minXVal :: OutputForm
    xHi := acplot.maxXVal :: OutputForm
    yLo := acplot.minYVal :: OutputForm
    yHi := acplot.maxYVal :: OutputForm
    zip := message(" = 0")
```

```
    com := message(",   ")
    les := message(" <= ")
    l : List OutputForm :=
      [pp,zip,com,xLo,les,xx,les,xHi,com,yLo,les,yy,les,yHi]
    f : List OutputForm := nil()
    for branch in acplot.branches repeat
      ll : List OutputForm := [p :: OutputForm for p in branch]
      f := cons(vconcat ll,f)
    ff := vconcat(hconcat l,vconcat f)
    vconcat(message "ACPLOT",ff)
```

———-

— ACPLOT.dotabb —

```
"ACPLOT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ACPLOT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ACPLOT" -> "ALIST"
```

———-

17.18 domain PLACES Places

— Places.input —

```
)set break resume
)sys rm -f Places.output
)spool Places.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Places
--R
--R Places(K: Field)  is a domain constructor
--R Abbreviation for Places is PLACES
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PLACES
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,%) -> Divisor(%)       ?+? : (%,%) -> Divisor(%)
--R -? : % -> Divisor(%)                  ?-? : (%,%) -> Divisor(%)
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
```

```
--R create : Symbol -> %                  create : List(K) -> %
--R degree : % -> PositiveInteger         ?.? : (%,Integer) -> K
--R foundPlaces : () -> List(%)           hash : % -> SingleInteger
--R itsALeaf! : % -> Void                 latex : % -> String
--R leaf? : % -> Boolean                  reduce : List(%) -> Divisor(%)
--R ?~=? : (%,%) -> Boolean
--R ?+? : (%,Divisor(%)) -> Divisor(%)
--R ?+? : (Divisor(%),%) -> Divisor(%)
--R ?-? : (%,Divisor(%)) -> Divisor(%)
--R ?-? : (Divisor(%),%) -> Divisor(%)
--R localParam : % -> List(NeitherSparseOrDensePowerSeries(K))
--R setDegree! : (%,PositiveInteger) -> Void
--R setFoundPlacesToEmpty : () -> List(%)
--R setParam! : (%,List(NeitherSparseOrDensePowerSeries(K))) -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— Places.help —

```
=======================================================================
Places examples
=======================================================================

See Also:
o )show Places
```

———-

17.18.1 Places (PLACES)



Exports:

-?	?*?	?+?	?-?	?.?
?=?	?~=?	coerce	create	degree
foundPlaces	hash	itsALeaf!	latex	leaf?
localParam	reduce	setDegree!	setFoundPlacesToEmpty	setParam!

— **domain PLACES Places** —

```
)abbrev domain PLACES Places
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is part of the PAFF package
Places(K):Exports == Implementation where
  K:Field
  PCS    ==>  NeitherSparseOrDensePowerSeries(K)

  Exports ==> PlacesCategory(K,PCS)

  Implementation ==>   Plcs(K,PCS)
```

———-

— **PLACES.dotabb** —

```
"PLACES" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLACES"];
"NSDPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=NSDPS"];
"PLCS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLCS"]
"PLACES" -> "NSDPS"
"PLACES" -> "PLCS"
```

———-

17.19 domain PLACESPS PlacesOverPseudoAlgebraicClosureOfFiniteField

— **PlacesOverPseudoAlgebraicClosureOfFiniteField.input** —

```
)set break resume
)sys rm -f PlacesOverPseudoAlgebraicClosureOfFiniteField.output
)spool PlacesOverPseudoAlgebraicClosureOfFiniteField.output
```

```
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PlacesOverPseudoAlgebraicClosureOfFiniteField
--R
--R PlacesOverPseudoAlgebraicClosureOfFiniteField(K: FiniteFieldCategory)  is a domain construct
--R Abbreviation for PlacesOverPseudoAlgebraicClosureOfFiniteField is PLACESPS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PLACESPS
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Integer,%) -> Divisor(%)       ?+? : (%,%) -> Divisor(%)
--R -? : % -> Divisor(%)                  ?-? : (%,%) -> Divisor(%)
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R create : Symbol -> %                  degree : % -> PositiveInteger
--R foundPlaces : () -> List(%)           hash : % -> SingleInteger
--R itsALeaf! : % -> Void                 latex : % -> String
--R leaf? : % -> Boolean                  reduce : List(%) -> Divisor(%)
--R ?~=? : (%,%) -> Boolean
--R ?+? : (%,Divisor(%)) -> Divisor(%)
--R ?+? : (Divisor(%),%) -> Divisor(%)
--R ?-? : (%,Divisor(%)) -> Divisor(%)
--R ?-? : (Divisor(%),%) -> Divisor(%)
--R create : List(PseudoAlgebraicClosureOfFiniteField(K)) -> %
--R ?.? : (%,Integer) -> PseudoAlgebraicClosureOfFiniteField(K)
--R localParam : % -> List(NeitherSparseOrDensePowerSeries(PseudoAlgebraicClosureOfFiniteField(K
--R setDegree! : (%,PositiveInteger) -> Void
--R setFoundPlacesToEmpty : () -> List(%)
--R setParam! : (%,List(NeitherSparseOrDensePowerSeries(PseudoAlgebraicClosureOfFiniteField(K)))
--R
--E 1

)spool
)lisp (bye)
```

———-


— PlacesOverPseudoAlgebraicClosureOfFiniteField.help —

```
=====================================================================
PlacesOverPseudoAlgebraicClosureOfFiniteField examples
=====================================================================

See Also:
o )show PlacesOverPseudoAlgebraicClosureOfFiniteField
```

———-

17.19.1 PlacesOverPseudoAlgebraicClosureOfFiniteField (PLACESPS)



Exports:

-?	?*?	?+?	?-?	?.?
?=?	?~=?	coerce	create	degree
foundPlaces	hash	itsALeaf!	latex	leaf?
localParam	reduce	setDegree!	setFoundPlacesToEmpty	setParam!

— **domain PLACESPS PlacesOverPseudoAlgebraicClosureOfFiniteField** —

```
)abbrev domain PLACESPS PlacesOverPseudoAlgebraicClosureOfFiniteField
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is part of the PAFF package
PlacesOverPseudoAlgebraicClosureOfFiniteField(K):Exports
 == Implementation where

  K:FiniteFieldCategory
  KK  ==> PseudoAlgebraicClosureOfFiniteField(K)
  PCS ==> NeitherSparseOrDensePowerSeries(KK)

  Exports ==> PlacesCategory(KK,PCS)

  Implementation ==>   Plcs(KK,PCS)
```

———-

— **PLACESPS.dotabb** —

```
"PLACESPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLACESPS"];
```

```
"PACOFF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PACOFF"]
"PLACESPS" -> "PACOFF"
```

———-

17.20 domain PLCS Plcs

— Plcs.input —

```
)set break resume
)sys rm -f Plcs.output
)spool Plcs.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Plcs
--R
--R Plcs(K: Field,PCS: LocalPowerSeriesCategory(K))  is a domain constructor
--R Abbreviation for Plcs is PLCS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PLCS
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Integer,%) -> Divisor(%)       ?+? : (%,%) -> Divisor(%)
--R -? : % -> Divisor(%)                  ?-? : (%,%) -> Divisor(%)
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R create : Symbol -> %                  create : List(K) -> %
--R degree : % -> PositiveInteger         ?.? : (%,Integer) -> K
--R foundPlaces : () -> List(%)           hash : % -> SingleInteger
--R itsALeaf! : % -> Void                 latex : % -> String
--R leaf? : % -> Boolean                  localParam : % -> List(PCS)
--R reduce : List(%) -> Divisor(%)        setParam! : (%,List(PCS)) -> Void
--R ?~=? : (%,%) -> Boolean
--R ?+? : (%,Divisor(%)) -> Divisor(%)
--R ?+? : (Divisor(%),%) -> Divisor(%)
--R ?-? : (%,Divisor(%)) -> Divisor(%)
--R ?-? : (Divisor(%),%) -> Divisor(%)
--R setDegree! : (%,PositiveInteger) -> Void
--R setFoundPlacesToEmpty : () -> List(%)
--R
--E 1

)spool
)lisp (bye)
```

———-


— Plcs.help —

```
=======================================================================
Plcs examples
=======================================================================

See Also:
o )show Plcs
```

———-

17.20.1 Plcs (PLCS)



Exports:

— domain PLCS Plcs —

```
)abbrev domain PLCS Plcs
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ The following is part of the PAFF package
Plcs(K:Field,PCS:LocalPowerSeriesCategory(K)):Exports == Implementation where

  nameOfPlace ==> Union( List(K), Symbol )

  rec ==> Record(theName:nameOfPlace,_
                 locPar: List PCS,_
                 deg: PositiveInteger,_
```

```
                isALeaf:Boolean,_
                inName:Symbol,_
                 actualSet:Symbol)

  Exports ==> PlacesCategory(K,PCS)

  Implementation ==>   add

    Rep:= rec

    setOfPlacesName:Symbol:=new(ActualSetOfPlacesName)$Symbol

    a:% + b:% == (a:: Divisor(%)) +$Divisor(%) (b::Divisor(%))

    a:% - b:% == (a:: Divisor(%)) -$Divisor(%) (b::Divisor(%))

    n:Integer * b:% == n *$Divisor(%) (b :: Divisor(%))

    reduce(lp)==
      lpd:List Divisor(%):= [p :: Divisor(%) for p in lp]
      reduce("+", lpd, 0$Divisor(%))

    d:Divisor(%) + b:% == d + (b::Divisor(%))

    a:% + d:Divisor(%) == (a::Divisor(%)) + d

    d:Divisor(%) - b:% == d - (b::Divisor(%))

    a:% - d:Divisor(%) == (a::Divisor(%)) - d

    -a:% == - ( a::Divisor(%))

    outName: nameOfPlace -> OutputForm

    outName(pt)==
      pt case Symbol => pt :: OutputForm
      dd:OutputForm:= ":" :: OutputForm
      llout:List(OutputForm):=[ hconcat(dd, a::OutputForm) for a in rest pt]
      lout:= cons( (first pt)::OutputForm , llout)
      out:= hconcat lout
      bracket(out)

    coerce(pt:%):OutputForm ==
      nn:OutputForm:= outName(pt.theName)
      ee:OutputForm:= degree(pt) :: OutputForm
      nn ** ee

    a:% = b:% ==
      ^(a.actualSet =$Symbol b.actualSet) =>
        a:String:=
```

```
       "From Places Domain: Cannot use old places with new places."
        " You have declared two different package PAFF or PAFFFF with the "
         "same arguments. This is not allowed because in that case the two "
          "packages used the same domain to represent the set of places. "
           "Two packages having the same arguments should be used in "
            "different frame"
     error a
  a.inName =$Symbol b.inName

elt(pl,n)==
  pt:= (pl :: Rep).theName
  pt case Symbol => _
    error "From Places domain : cannot return the coordinates of a leaf"
  elt(pt,n)$List(K)

leaf?(pl)==pl.isALeaf

itsALeaf_!(pl)==
  pl.isALeaf := true()
  void()

listOfFoundPlaces:List %:=[]

foundPlaces()==listOfFoundPlaces

setFoundPlacesToEmpty()==
  tmp:=copy listOfFoundPlaces
  listOfFoundPlaces:=[]
  setOfPlacesName:Symbol:=new(ActualSetOfPlacesName)$Symbol
  tmp

findInExistOnes: % -> %
findInExistOnes(pt)==
  ll:=listOfFoundPlaces
  found:Boolean:=false()
  fpl:%
  while ^found and  ^empty?(ll) repeat
    fpl:= first ll
    -- remember: the "=" test is on done on the symbolic name
    found:= pt.theName = fpl.theName
    ll:=rest ll
  ^found =>
    listOfFoundPlaces:=cons(pt,listOfFoundPlaces)
    pt
  fpl

create(pt:List(K)):%==
  newName:=new(SIMPLE)$Symbol
  newPt:%:=[pt,[],1,false(),newName,setOfPlacesName]$rec
  findInExistOnes(newPt)
```

```
    create(pt:Symbol):%==
      newPt:%:=[pt,[],1,false(),pt,setOfPlacesName]$rec
      findInExistOnes(newPt)

    setDegree_!(pt,d)==
      pt.deg := d
      void()

    setParam_!(pt,ls)==
      pt.locPar:=ls
      void()

    localParam(pt)==pt.locPar

    degree(pl)==pl.deg
```

———-

— PLCS.dotabb —

```
"PLCS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLCS"];
"LOCPOWC" [color=lightblue,href="bookvol10.2.pdf#nameddest=LOCPOWC"];
"PLCS" -> "LOCPOWC"
```

———-

17.21 domain PLOT Plot

— Plot.input —

```
)set break resume
)sys rm -f Plot.output
)spool Plot.output
)set message test on
)set message auto off
)clear all
--S 1 of 2
fp:=(t:DFLOAT):DFLOAT +-> sin(t)
--R
--R   (1)  theMap(Closure)
--R                                          Type: (DoubleFloat -> DoubleFloat)
--E 1
```

```
--S 2 of 2
plot(fp,-1.0..1.0)$PLOT
--R
--R
--R   (2)  PLOT(x = (- 1.)..1.   y = (- 0.8414709848078965)..0.8414709848078965)
--R                                 [- 1.,- 0.8414709848078965]
--R                        [- 0.95833333333333337,- 0.81823456433427133]
--R                        [- 0.91666666666666674,- 0.79357780324894212]
--R                        [- 0.87500000000000011,- 0.76754350223602708]
--R                        [- 0.83333333333333348,- 0.74017685319603721]
--R                        [- 0.79166666666666685,- 0.7115253607990657]
--R                        [- 0.75000000000000022,- 0.68163876002333434]
--R                        [- 0.70833333333333359,- 0.65056892982223602]
--R                        [- 0.66666666666666696,- 0.61836980306973721]
--R                        [- 0.62500000000000033,- 0.58509727294046243]
--R                        [- 0.5833333333333337,- 0.55080909588697013]
--R                        [- 0.54166666666666707,- 0.51556479138264011]
--R                        [- 0.50000000000000044,- 0.47942553860420339]
--R                        [- 0.45833333333333376,- 0.44245407023325911]
--R                        [- 0.41666666666666707,- 0.40471456356112506]
--R                        [- 0.37500000000000039,- 0.3662725290860479]
--R                         [- 0.3333333333333337,- 0.3271946967961526]
--R                        [- 0.29166666666666702,- 0.28754890033552849]
--R                        [- 0.25000000000000033,- 0.24740395925452324]
--R                        [- 0.20833333333333368,- 0.20682955954864138]
--R                        [- 0.16666666666666702,- 0.16589613269341538]
--R                        [- 0.12500000000000036,- 0.12467473338522805]
--R                     [- 8.3333333333333703E-2,- 8.3236916200310623E-2]
--R                     [- 4.1666666666667039E-2,- 4.1654611386019461E-2]
--R                    [- 3.7470027081099033E-16,- 3.7470027081099033E-16]
--R                        [4.166666666666629E-2,4.1654611386018711E-2]
--R                        [8.3333333333332954E-2,8.3236916200309874E-2]
--R                          [0.12499999999999961,0.1246747333852273]
--R                          [0.16666666666666627,0.16589613269341463]
--R                          [0.20833333333333293,0.20682955954864066]
--R                          [0.24999999999999958,0.24740395925452252]
--R                          [0.29166666666666624,0.28754890033552777]
--R                          [0.33333333333333293,0.3271946967961518 7]
--R                          [0.37499999999999961,0.36627252908604718]
--R                           [0.4166666666666663,0.4047145635611244]
--R                          [0.45833333333333298,0.44245407023325839]
--R                          [0.49999999999999967,0.47942553860420273]
--R                          [0.5416666666666663,0.51556479138263944]
--R                          [0.58333333333333293,0.55080909588696947]
--R                          [0.62499999999999956,0.58509727294046177]
--R                          [0.66666666666666619,0.61836980306973666]
--R                          [0.70833333333333282,0.65056892982223535]
--R                          [0.74999999999999944,0.68163876002333379]
--R                          [0.79166666666666607,0.71152536079906514]
```

```
--R                        [0.8333333333333327,0.74017685319603665]
--R                        [0.87499999999999933,0.76754350223602663]
--R                        [0.91666666666666596,0.79357780324894167]
--R                        [0.95833333333333259,0.81823456433427078]
--R                                 [1.,0.8414709848078965]
--R                                                                Type: Plot
--E 2
)spool
)lisp (bye)
```

———-

— Plot.help —

```
================================================================================
Plot examples
================================================================================

The Plot (PLOT) domain supports plotting of functions defined over a
real number system. Plot is limited to 2 dimensional plots.

The function plot: (F -> F,R) -> % plots the function f(x) on the
interval a..b. So we need to define a function that maps from
DoubleFloat to DoubleFloat:

  fp:=(t:DFLOAT):DFLOAT +-> sin(t)


and then feed it to the plot function with a Segment DoubleFloat

  plot(fp,-1.0..1.0)$PLOT

See Also:
o )show Plot
```

———-

17.21.1 Plot (PLOT)



Exports:

adaptive?	coerce	debug	listBranches	maxPoints
minPoints	numFunEvals	parametric?	plot	plotPolar
pointPlot	refine	screenResolution	setAdaptive	setMaxPoints
setMinPoints	setScreenResolution	tRange	xRange	yRange
zoom				

— domain PLOT Plot —

```
)abbrev domain PLOT Plot
++ Author: Michael Monagan (revised by Clifton J. Williamson)
++ Date Created: Jan 1988
++ Date Last Updated: 30 Nov 1990 by Jonathan Steinbach
++ Basic Operations: plot, pointPlot, plotPolar, parametric?, zoom, refine,
++ tRange, minPoints, setMinPoints, maxPoints, screenResolution, adaptive?,
++ setAdaptive, numFunEvals, debug
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: plot, function, parametric
++ References:
++ Description:
++ The Plot domain supports plotting of functions defined over a
++ real number system.  A real number system is a model for the real
++ numbers and as such may be an approximation.  For example
++ floating point numbers and infinite continued fractions.
++ The facilities at this point are limited to 2-dimensional plots
++ or either a single function or a parametric function.

Plot(): Exports == Implementation where
  B   ==> Boolean
  F   ==> DoubleFloat
  I   ==> Integer
  L   ==> List
  N   ==> NonNegativeInteger
```

```
  OUT ==> OutputForm
  P   ==> Point F
  RN  ==> Fraction Integer
  S   ==> String
  SEG ==> Segment
  R   ==> Segment F
  C   ==> Record(source: F -> P,ranges: L R,knots: L F,points: L P)

  Exports ==> PlottablePlaneCurveCategory with

--% function plots

    plot: (F -> F,R) -> %
      ++ plot(f,a..b) plots the function \spad{f(x)}
      ++ on the interval \spad{[a,b]}.
      ++
      ++X fp:=(t:DFLOAT):DFLOAT +-> sin(t)
      ++X plot(fp,-1.0..1.0)$PLOT

    plot: (F -> F,R,R) -> %
      ++ plot(f,a..b,c..d) plots the function \spad{f(x)} on the interval
      ++ \spad{[a,b]}; y-range of \spad{[c,d]} is noted in Plot object.

--% multiple function plots

    plot: (L(F -> F),R) -> %
      ++ plot([f1,...,fm],a..b) plots the functions \spad{y = f1(x)},...,
      ++ \spad{y = fm(x)} on the interval \spad{a..b}.
    plot: (L(F -> F),R,R) -> %
      ++ plot([f1,...,fm],a..b,c..d) plots the functions \spad{y = f1(x)},...,
      ++ \spad{y = fm(x)} on the interval \spad{a..b}; y-range of \spad{[c,d]} is
      ++ noted in Plot object.

--% parametric plots

    plot: (F -> F,F -> F,R) -> %
      ++ plot(f,g,a..b) plots the parametric curve \spad{x = f(t)},
      ++ \spad{y = g(t)} as t ranges over the interval \spad{[a,b]}.
    plot: (F -> F,F -> F,R,R,R) -> %
      ++ plot(f,g,a..b,c..d,e..f) plots the parametric curve \spad{x = f(t)},
      ++ \spad{y = g(t)} as t ranges over the interval \spad{[a,b]}; x-range
      ++ of \spad{[c,d]} and y-range of \spad{[e,f]} are noted in Plot object.

--% parametric plots

    pointPlot: (F -> P,R) -> %
      ++ pointPlot(t +-> (f(t),g(t)),a..b) plots the parametric curve
      ++ \spad{x = f(t)}, \spad{y = g(t)} as t ranges over the interval
      ++ \spad{[a,b]}.
    pointPlot: (F -> P,R,R,R) -> %
```

```
      ++ pointPlot(t +-> (f(t),g(t)),a..b,c..d,e..f) plots the parametric
      ++ curve \spad{x = f(t)}, \spad{y = g(t)} as t ranges over the interval
      ++ \spad{[a,b]}; x-range of \spad{[c,d]} and y-range of \spad{[e,f]}
      ++ are noted in Plot object.

--% polar plots

    plotPolar: (F -> F,R) -> %
      ++ plotPolar(f,a..b) plots the polar curve \spad{r = f(theta)} as
      ++ theta ranges over the interval \spad{[a,b]}; this is the same as
      ++ the parametric curve \spad{x = f(t)*cos(t)}, \spad{y = f(t)*sin(t)}.

    plotPolar: (F -> F) -> %
      ++ plotPolar(f) plots the polar curve \spad{r = f(theta)} as theta
      ++ ranges over the interval \spad{[0,2*%pi]}; this is the same as
      ++ the parametric curve \spad{x = f(t)*cos(t)}, \spad{y = f(t)*sin(t)}.

    plot: (%,R) -> %              -- change the range
        ++ plot(x,r) is not documented
    parametric?: % -> B
      ++ parametric? determines whether it is a parametric plot?

    zoom: (%,R) -> %
        ++ zoom(x,r) is not documented
    zoom: (%,R,R) -> %
        ++ zoom(x,r,s) is not documented
    refine: (%,R) -> %
        ++ refine(x,r) is not documented
    refine: % -> %
      ++ refine(p) performs a refinement on the plot p

    tRange: % -> R
      ++ tRange(p) returns the range of the parameter in a parametric plot p

    minPoints: () -> I
      ++ minPoints() returns the minimum number of points in a plot
    setMinPoints: I -> I
      ++ setMinPoints(i) sets the minimum number of points in a plot to i
    maxPoints: () -> I
      ++ maxPoints() returns the maximum number of points in a plot
    setMaxPoints: I -> I
      ++ setMaxPoints(i) sets the maximum number of points in a plot to i
    screenResolution: () -> I
      ++ screenResolution() returns the screen resolution
    setScreenResolution: I -> I
      ++ setScreenResolution(i) sets the screen resolution to i
    adaptive?: () -> B
      ++ adaptive?() determines whether plotting be done adaptively
    setAdaptive: B -> B
      ++ setAdaptive(true) turns adaptive plotting on
```

```
      ++ \spad{setAdaptive(false)} turns adaptive plotting off
    numFunEvals: () -> I
      ++ numFunEvals() returns the number of points computed
    debug: B -> B
      ++ debug(true) turns debug mode on
      ++ \spad{debug(false)} turns debug mode off

  Implementation ==> add
    import PointPackage(DoubleFloat)

--% local functions

    checkRange     : R -> R
      -- checks that left-hand endpoint is less than right-hand endpoint
    intersect      : (R,R) -> R
      -- intersection of two intervals
    union          : (R,R) -> R
      -- union of two intervals
    join           : (L C,I) -> R
    parametricRange: % -> R
    select         : (L P,P -> F,(F,F) -> F) -> F
    rangeRefine    : (C,R) -> C
    adaptivePlot   : (C,R,R,R,I) -> C
    basicPlot      : (F -> P,R) -> C
    basicRefine    : (C,R) -> C
    pt             : (F,F) -> P
    Fnan?           : F -> Boolean
    Pnan?           : P -> Boolean

--% representation

    Rep := Record( parametric: B, _
                   display: L R, _
                   bounds: L R, _
                   axisLabels: L S, _
                   functions: L C )

--% global constants

    ADAPTIVE: B := true
    MINPOINTS: I := 49
    MAXPOINTS: I := 1000
    NUMFUNEVALS: I := 0
    SCREENRES: I := 500
    ANGLEBOUND: F := cos inv (4::F)
    DEBUG: B := false

    Fnan?(x) == x ~= x
    Pnan?(x) == any?(Fnan?,x)
```

```
--% graphics output

    listBranches plot ==
      outList : L L P := nil()
      for curve in plot.functions repeat
        -- curve is C
        newl:L P:=nil()
        for p in curve.points repeat
          if not Pnan? p then newl:=cons(p,newl)
          else if not empty? newl then
                outList := concat(newl:=reverse! newl,outList)
                newl:=nil()
        if not empty? newl then outList := concat(newl:=reverse! newl,outList)
--      print(outList::OutputForm)
      outList

    checkRange r == (lo r > hi r => error "ranges cannot be negative"; r)
    intersect(s,t) == checkRange (max(lo s,lo t) .. min(hi s,hi t))
    union(s,t) == min(lo s,lo t) .. max(hi s,hi t)
    join(l,i) ==
      rr := first l
      u : R :=
        i = 0 => first(rr.ranges)
        i = 1 => second(rr.ranges)
        third(rr.ranges)
      for r in rest l repeat
        i = 0 => u := union(u,first(r.ranges))
        i = 1 => u := union(u,second(r.ranges))
        u := union(u,third(r.ranges))
      u
    parametricRange r == first(r.bounds)

    minPoints() == MINPOINTS
    setMinPoints n ==
      if n < 3 then error "three points minimum required"
      if MAXPOINTS < n then MAXPOINTS := n
      MINPOINTS := n
    maxPoints() == MAXPOINTS
    setMaxPoints n ==
      if n < 3 then error "three points minimum required"
      if MINPOINTS > n then MINPOINTS := n
      MAXPOINTS := n
    screenResolution() == SCREENRES
    setScreenResolution n ==
      if n < 2 then error "buy a new terminal"
      SCREENRES := n
    adaptive?() == ADAPTIVE
    setAdaptive b == ADAPTIVE := b
    parametric? p == p.parametric
```

```
numFunEvals() == NUMFUNEVALS
debug b == DEBUG := b

xRange plot == second plot.bounds
yRange plot == third plot.bounds
tRange plot == first plot.bounds

select(l,f,g) ==
  m := f first l
  if Fnan? m then m := 0
  for p in rest l repeat
    n := m
    m := g(m, f p)
    if Fnan? m then m := n
  m

rangeRefine(curve,nRange) ==
  checkRange nRange; l := lo nRange; h := hi nRange
  t := curve.knots; p := curve.points; f := curve.source
  while not null t and first t < l repeat
    (t := rest t; p := rest p)
  c: L F := nil(); q: L P := nil()
  while not null t and (first t) <= h repeat
    c := concat(first t,c); q := concat(first p,q)
    t := rest t; p := rest p
  if null c then return basicPlot(f,nRange)
  if first c < h then
    c := concat(h,c)
    q := concat(f h,q)
    NUMFUNEVALS := NUMFUNEVALS + 1
  t := c := reverse_! c; p := q := reverse_! q
  s := (h-l)/(minPoints()::F-1)
  if (first t) ^= l then
    t := c := concat(l,c)
    p := q := concat(f l,p)
    NUMFUNEVALS := NUMFUNEVALS + 1
  while not null rest t repeat
    n := wholePart((second(t) - first(t))/s)
    d := (second(t) - first(t))/((n+1)::F)
    for i in 1..n repeat
      t.rest := concat(first(t) + d,rest t)
      p.rest := concat(f second t,rest p)
      NUMFUNEVALS := NUMFUNEVALS + 1
      t := rest t; p := rest p
    t := rest t
    p := rest p
  xRange := select(q,xCoord,min) .. select(q,xCoord,max)
  yRange := select(q,yCoord,min) .. select(q,yCoord,max)
  [ f, [nRange,xRange,yRange], c, q]
```

```
    adaptivePlot(curve,tRange,xRange,yRange,pixelfraction) ==
      xDiff := hi xRange - lo xRange
      yDiff := hi yRange - lo yRange
      xDiff = 0 or yDiff = 0 => curve
      l := lo tRange; h := hi tRange
      (tDiff := h-l) = 0 => curve
--      if (EQL(yDiff, _$NaNvalue$Lisp)$Lisp) then yDiff := 1::F
      t := curve.knots
      #t < 3 => curve
      p := curve.points; f := curve.source
      minLength:F := 4::F/500::F
      maxLength:F := 1::F/6::F
      tLimit := tDiff/(pixelfraction*500)::F
      while not null t and first t < l repeat (t := rest t; p := rest p)
      #t < 3 => curve
      headert := t; headerp := p

      -- jitter the input points
--      while not null rest rest t repeat
--        t0 := second(t); t1 := third(t)
--        jitter := (random()$I) :: F
--        jitter := sin (jitter)
--        val := t0 + jitter * (t1-t0)/10::F
--        t.2 := val; p.2 := f val
--        t := rest t; p := rest p
--      t := headert; p := headerp

      st := t; sp := p
      todot : L L F := nil()
      todop : L L P := nil()
      while not null rest rest st repeat
        todot := concat_!(todot, st)
        todop := concat_!(todop, sp)
        st := rest st; sp := rest sp
      st := headert; sp := headerp
      todo1 := todot; todo2 := todop
      n : I := 0
      while not null todo1 repeat
        st := first(todo1)
        t0 := first(st); t1 := second(st); t2 := third(st)
        if t2 > h then leave
        t2 - t0 < tLimit =>
            todo1 := rest todo1
            todo2 := rest todo2
            if not null todo1 then (t := first(todo1); p := first(todo2))
        sp := first(todo2)
        x0 := xCoord first(sp); y0 := yCoord first(sp)
        x1 := xCoord second(sp); y1 := yCoord second(sp)
        x2 := xCoord third(sp); y2 := yCoord third(sp)
        a1 := (x1-x0)/xDiff; b1 := (y1-y0)/yDiff
```

```
a2 := (x2-x1)/xDiff; b2 := (y2-y1)/yDiff
s1 := sqrt(a1**2+b1**2); s2 := sqrt(a2**2+b2**2)
dp := a1*a2+b1*b2

s1 < maxLength and s2 < maxLength and _
  (s1 = 0::F or s2 = 0::F or
     s1 < minLength and s2 < minLength or _
     dp/s1/s2 > ANGLEBOUND) =>
        todo1 := rest todo1
        todo2 := rest todo2
        if not null todo1 then (t := first(todo1); p := first(todo2))
if n > MAXPOINTS then leave else n := n + 1
st := rest t
if not null rest rest st then
  tm := (t0+t1)/2::F
  tj := tm
  t.rest := concat(tj,rest t)
  p.rest := concat(f tj, rest p)
  todo1 := concat_!(todo1, t)
  todo2 := concat_!(todo2, p)
  t := rest t; p := rest p
  todo1 := concat_!(todo1, t)
  todo2 := concat_!(todo2, p)
  t := rest t; p := rest p
  todo1 := rest todo1; todo2 := rest todo2

  tm := (t1+t2)/2::F
  tj := tm
  t.rest := concat(tj, rest t)
  p.rest := concat(f tj, rest p)
  todo1 := concat_!(todo1, t)
  todo2 := concat_!(todo2, p)
  t := rest t; p := rest p
  todo1 := concat_!(todo1, t)
  todo2 := concat_!(todo2, p)
  todo1 := rest todo1
  todo2 := rest todo2
  if not null todo1 then (t := first(todo1); p := first(todo2))
else
  tm := (t0+t1)/2::F
  tj := tm
  t.rest := concat(tj,rest t)
  p.rest := concat(f tj, rest p)
  todo1 := concat_!(todo1, t)
  todo2 := concat_!(todo2, p)
  t := rest t; p := rest p
  todo1 := concat_!(todo1, t)
  todo2 := concat_!(todo2, p)
  t := rest t; p := rest p
```

```
          tm := (t1+t2)/2::F
          tj := tm
          t.rest := concat(tj, rest t)
          p.rest := concat(f tj, rest p)
          todo1 := concat_!(todo1, t)
          todo2 := concat_!(todo2, p)
          todo1 := rest todo1
          todo2 := rest todo2
          if not null todo1 then (t := first(todo1); p := first(todo2))
      n > 0 =>
        NUMFUNEVALS := NUMFUNEVALS + n
        t := curve.knots; p := curve.points
        xRange := select(p,xCoord,min) .. select(p,xCoord,max)
        yRange := select(p,yCoord,min) .. select(p,yCoord,max)
        [ curve.source, [tRange,xRange,yRange], t, p ]
      curve

    basicPlot(f,tRange) ==
      checkRange tRange
      l := lo tRange
      h := hi tRange
      t : L F := list l
      p : L P := list f l
      s := (h-l)/(minPoints()-1)::F
      for i in 2..minPoints()-1 repeat
        l := l+s
        t := concat(l,t)
        p := concat(f l,p)
      t := reverse_! concat(h,t)
      p := reverse_! concat(f h,p)
--      print(p::OutputForm)
      xRange : R := select(p,xCoord,min) .. select(p,xCoord,max)
      yRange : R := select(p,yCoord,min) .. select(p,yCoord,max)
      [ f, [tRange,xRange,yRange], t, p ]

    zoom(p,xRange) ==
      [p.parametric, [xRange,third(p.display)], p.bounds, _
       p.axisLabels, p.functions]
    zoom(p,xRange,yRange) ==
      [p.parametric, [xRange,yRange], p.bounds, _
       p.axisLabels, p.functions]

    basicRefine(curve,nRange) ==
      tRange:R := first curve.ranges
      -- curve := copy$C curve  -- Yet another compiler bug
      curve: C := [curve.source,curve.ranges,curve.knots,curve.points]
      t := curve.knots := copy curve.knots
      p := curve.points := copy curve.points
      l := lo nRange; h := hi nRange
      f := curve.source
```

```
      while not null rest t and first t < h repeat
        second(t) < l => (t := rest t; p := rest p)
        -- insert new point between t.0 and t.1
        tm : F := (first(t) + second(t))/2::F
--         if DEBUG then output$O (tm::E)
        pm := f tm
        NUMFUNEVALS := NUMFUNEVALS + 1
        t.rest := concat(tm,rest t); t := rest rest t
        p.rest := concat(pm,rest p); p := rest rest p
      t := curve.knots; p := curve.points
      xRange := select(p,xCoord,min) .. select(p,xCoord,max)
      yRange := select(p,yCoord,min) .. select(p,yCoord,max)
      [ curve.source, [tRange,xRange,yRange], t, p ]

    refine p == refine(p,parametricRange p)
    refine(p,nRange) ==
      NUMFUNEVALS := 0
      tRange := parametricRange p
      nRange := intersect(tRange,nRange)
      curves: L C := [basicRefine(c,nRange) for c in p.functions]
      xRange := join(curves,1); yRange := join(curves,2)
      if adaptive? then
        tlimit := if parametric? p then 8 else 1
        curves := [adaptivePlot(c,nRange,xRange,yRange, _
                   tlimit) for c in curves]
        xRange := join(curves,1); yRange := join(curves,2)
--      print(NUMFUNEVALS::OUT)
      [p.parametric, p.display, [tRange,xRange,yRange], _
       p.axisLabels, curves ]

    plot(p:%,tRange:R) ==
      -- re plot p on a new range making use of the points already
      -- computed if possible
      NUMFUNEVALS := 0
      curves: L C := [rangeRefine(c,tRange) for c in p.functions]
      xRange := join(curves,1); yRange := join(curves,2)
      if adaptive? then
        tlimit := if parametric? p then 8 else 1
        curves := [adaptivePlot(c,tRange,xRange,yRange,tlimit) for c in curves]
        xRange := join(curves,1); yRange := join(curves,2)
--      print(NUMFUNEVALS::OUT)
      [ p.parametric, [xRange,yRange], [tRange,xRange,yRange],
        p.axisLabels, curves ]

    pt(xx,yy) == point(l : L F := [xx,yy])

    myTrap: (F-> F, F) -> F
    myTrap(ff:F-> F, f:F):F ==
      s := trapNumericErrors(ff(f))$Lisp :: Union(F, "failed")
      s case "failed" => _$NaNvalue$Lisp
```

```
    r:F:=s::F
    r > max()$F or r < min()$F => _$NaNvalue$Lisp
    r

  plot(f:F -> F,xRange:R) ==
    p := basicPlot((u1:F):P +-> pt(u1,myTrap(f,u1)),xRange)
    r := p.ranges
    NUMFUNEVALS := minPoints()
    if adaptive? then
      p := adaptivePlot(p,first r,second r,third r,1)
      r := p.ranges
    [ false, rest r, r, nil(), [ p ] ]

  plot(f:F -> F,xRange:R,yRange:R) ==
    p := plot(f,xRange)
    p.display := [xRange,checkRange yRange]
    p

  plot(f:F -> F,g:F -> F,tRange:R) ==
    p := basicPlot((z1:F):P +-> pt(myTrap(f,z1),myTrap(g,z1)),tRange)
    r := p.ranges
    NUMFUNEVALS := minPoints()
    if adaptive? then
      p := adaptivePlot(p,first r,second r,third r,8)
      r := p.ranges
    [ true, rest r, r, nil(), [ p ] ]

  plot(f:F -> F,g:F -> F,tRange:R,xRange:R,yRange:R) ==
    p := plot(f,g,tRange)
    p.display := [checkRange xRange,checkRange yRange]
    p

  pointPlot(f:F -> P,tRange:R) ==
    p := basicPlot(f,tRange)
    r := p.ranges
    NUMFUNEVALS := minPoints()
    if adaptive? then
      p := adaptivePlot(p,first r,second r,third r,8)
      r := p.ranges
    [ true, rest r, r, nil(), [ p ] ]

  pointPlot(f:F -> P,tRange:R,xRange:R,yRange:R) ==
    p := pointPlot(f,tRange)
    p.display := [checkRange xRange,checkRange yRange]
    p

  plot(l:L(F -> F),xRange:R) ==
    if null l then error "empty list of functions"
    t: L C :=
      [ basicPlot((z1:F):P +-> pt(z1,myTrap(f,z1)),xRange) for f in l ]
```

```
      yRange := join(t,2)
      NUMFUNEVALS := # l * minPoints()
      if adaptive? then
        t := [adaptivePlot(p,xRange,xRange,yRange,1) _
                for f in l for p in t]
        yRange := join(t,2)
--      print(NUMFUNEVALS::OUT)
      [false, [xRange,yRange], [xRange,xRange,yRange], nil(), t ]

    plot(l:L(F -> F),xRange:R,yRange:R) ==
      p := plot(l,xRange)
      p.display := [xRange,checkRange yRange]
      p

    plotPolar(f,thetaRange) ==
      plot((u1:F):F +-> f(u1) * cos(u1),
           (v1:F):F +-> f(v1) * sin(v1),thetaRange)

    plotPolar f == plotPolar(f,segment(0,2*pi()))

--% terminal output

    coerce r ==
      spaces: OUT := coerce "   "
      xSymbol := "x = " :: OUT
      ySymbol := "y = " :: OUT
      tSymbol := "t = " :: OUT
      plotSymbol := "PLOT" :: OUT
      tRange := (parametricRange r) :: OUT
      f : L OUT := nil()
      for curve in r.functions repeat
        xRange := second(curve.ranges) :: OUT
        yRange := third(curve.ranges) :: OUT
        l : L OUT := [xSymbol,xRange,spaces,ySymbol,yRange]
        if parametric? r then
          l := concat_!([tSymbol,tRange,spaces],l)
        h : OUT := hconcat l
        l := [p::OUT for p in curve.points]
        f := concat(vconcat concat(h,l),f)
      prefix("PLOT" :: OUT, reverse_! f)
```

———-

— PLOT.dotabb —

```
"PLOT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLOT"]
"FRAC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FRAC"]
"PLOT" -> "FRAC"
```

———-

17.22 domain PLOT3D Plot3D

— **Plot3D.input** —

```
)set break resume
)sys rm -f Plot3D.output
)spool Plot3D.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Plot3D
--R
--R Plot3D  is a domain constructor
--R Abbreviation for Plot3D is PLOT3D
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PLOT3D
--R
--R------------------------------ Operations --------------------------------
--R adaptive3D? : () -> Boolean           coerce : % -> OutputForm
--R debug3D : Boolean -> Boolean          maxPoints3D : () -> Integer
--R minPoints3D : () -> Integer           numFunEvals3D : () -> Integer
--R refine : % -> %                       screenResolution3D : () -> Integer
--R setAdaptive3D : Boolean -> Boolean
--R listBranches : % -> List(List(Point(DoubleFloat)))
--R plot : (%,Segment(DoubleFloat)) -> %
--R plot : ((DoubleFloat -> DoubleFloat),(DoubleFloat -> DoubleFloat),(DoubleFloat -> DoubleFloat),(DoubleFl
--R plot : ((DoubleFloat -> DoubleFloat),(DoubleFloat -> DoubleFloat),(DoubleFloat -> DoubleFloat),(DoubleFl
--R pointPlot : ((DoubleFloat -> Point(DoubleFloat)),Segment(DoubleFloat),Segment(DoubleFloat),Segment(Doubl
--R pointPlot : ((DoubleFloat -> Point(DoubleFloat)),Segment(DoubleFloat)) -> %
--R refine : (%,Segment(DoubleFloat)) -> %
--R setMaxPoints3D : Integer -> Integer
--R setMinPoints3D : Integer -> Integer
--R setScreenResolution3D : Integer -> Integer
--R tRange : % -> Segment(DoubleFloat)
--R tValues : % -> List(List(DoubleFloat))
--R xRange : % -> Segment(DoubleFloat)
--R yRange : % -> Segment(DoubleFloat)
--R zRange : % -> Segment(DoubleFloat)
--R zoom : (%,Segment(DoubleFloat),Segment(DoubleFloat),Segment(DoubleFloat)) -> %
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **Plot3D.help** —

```
========================================================================
Plot3D examples
========================================================================

See Also:
o )show Plot3D
```

———-

17.22.1 Plot3D (PLOT3D)



Exports:

adaptive3D?	coerce	debug3D	listBranches	maxPoints3D
minPoints3D	numFunEvals3D	plot	pointPlot	refine
screenResolution3D	setAdaptive3D	setMaxPoints3D	setMinPoints3D	setScreenResolution3D
tRange	tValues	xRange	yRange	zRange
zoom				

— **domain PLOT3D Plot3D** —

```
)abbrev domain PLOT3D Plot3D
++ Author: Clifton J. Williamson based on code by Michael Monagan
++ Date Created: Jan 1989
++ Date Last Updated: 22 November 1990 (Jon Steinbach)
++ Basic Operations: pointPlot, plot, zoom, refine, tRange, tValues,
++ minPoints3D, setMinPoints3D, maxPoints3D, setMaxPoints3D,
```

```
++ screenResolution3D, setScreenResolution3D, adaptive3D?,  setAdaptive3D,
++ numFunEvals3D, debug3D
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: plot, parametric
++ References:
++ Description:
++ Plot3D supports parametric plots defined over a real
++ number system.  A real number system is a model for the real
++ numbers and as such may be an approximation.  For example,
++ floating point numbers and infinite continued fractions are
++ real number systems. The facilities at this point are limited
++ to 3-dimensional parametric plots.

Plot3D(): Exports == Implementation where
  B   ==> Boolean
  F   ==> DoubleFloat
  I   ==> Integer
  L   ==> List
  N   ==> NonNegativeInteger
  OUT ==> OutputForm
  P   ==> Point F
  S   ==> String
  R   ==> Segment F
  O   ==> OutputPackage
  C   ==> Record(source: F -> P,ranges: L R, knots: L F, points: L P)

  Exports ==> PlottableSpaceCurveCategory with

    pointPlot: (F -> P,R) -> %
      ++ pointPlot(f,g,h,a..b) plots {/emx = f(t), y = g(t), z = h(t)} as
      ++ t ranges over {/em[a,b]}.
    pointPlot: (F -> P,R,R,R,R) -> %
        ++ pointPlot(f,x,y,z,w) is not documented
    plot: (F -> F,F -> F,F -> F,F -> F,R) -> %
      ++ plot(f,g,h,a..b) plots {/emx = f(t), y = g(t), z = h(t)} as
      ++ t ranges over {/em[a,b]}.
    plot: (F -> F,F -> F,F -> F,F -> F,R,R,R,R) -> %
        ++ plot(f1,f2,f3,f4,x,y,z,w) is not documented

    plot: (%,R) -> %                        -- change the range
         ++ plot(x,r) is not documented
    zoom: (%,R,R,R) -> %
        ++ zoom(x,r,s,t) is not documented
    refine: (%,R) -> %
        ++ refine(x,r) is not documented
    refine: % -> %
        ++ refine(x) is not documented
```

```
    tRange: % -> R
      ++ tRange(p) returns the range of the parameter in a parametric plot p.
    tValues: % -> L L F
      ++ tValues(p) returns a list of lists of the values of the parameter for
      ++ which a point is computed, one list for each curve in the plot p.

    minPoints3D: () -> I
      ++ minPoints3D() returns the minimum number of points in a plot.
    setMinPoints3D: I -> I
      ++ setMinPoints3D(i) sets the minimum number of points in a plot to i.
    maxPoints3D: () -> I
      ++ maxPoints3D() returns the maximum number of points in a plot.
    setMaxPoints3D: I -> I
      ++ setMaxPoints3D(i) sets the maximum number of points in a plot to i.
    screenResolution3D: () -> I
      ++ screenResolution3D() returns the screen resolution for a 3d graph.
    setScreenResolution3D: I -> I
      ++ setScreenResolution3D(i) sets the screen resolution for a 3d graph to i.
    adaptive3D?: () -> B
      ++ adaptive3D?() determines whether plotting be done adaptively.
    setAdaptive3D: B -> B
      ++ setAdaptive3D(true) turns adaptive plotting on;
      ++ setAdaptive3D(false) turns adaptive plotting off.
    numFunEvals3D: () -> I
      ++ numFunEvals3D() returns the number of points computed.
    debug3D: B -> B
      ++ debug3D(true) turns debug mode on;
      ++ debug3D(false) turns debug mode off.

  Implementation ==> add
    import PointPackage(F)

--% local functions

    fourth         : L R -> R
    checkRange     : R -> R
      -- checks that left-hand endpoint is less than right-hand endpoint
    intersect      : (R,R) -> R
      -- intersection of two intervals
    union          : (R,R) -> R
      -- union of two intervals
    join           : (L C,I) -> R
    parametricRange: % -> R
--     setColor       : (P,F) -> F
    select         : (L P,P -> F,(F,F) -> F) -> F
--     normalizeColor : (P,F,F) -> F
    rangeRefine    : (C,R) -> C
    adaptivePlot   : (C,R,R,R,R,I,I) -> C
    basicPlot      : (F -> P,R) -> C
    basicRefine    : (C,R) -> C
```

```
    point          : (F,F,F,F) -> P

--% representation

    Rep := Record( display: L R, _
                   bounds: L R, _
                   screenres: I, _
                   axisLabels: L S, _
                   functions: L C )

--% global constants

    ADAPTIVE    : B := true
    MINPOINTS   : I := 49
    MAXPOINTS   : I := 1000
    NUMFUNEVALS : I := 0
    SCREENRES   : I := 500
    ANGLEBOUND  : F := cos inv (4::F)
    DEBUG       : B := false

    point(xx,yy,zz,col) == point(l : L F := [xx,yy,zz,col])

    fourth list == first rest rest rest list

    checkRange r == (lo r > hi r => error "ranges cannot be negative"; r)
    intersect(s,t) == checkRange (max(lo s,lo t) .. min(hi s,hi t))
    union(s:R,t:R) == min(lo s,lo t) .. max(hi s,hi t)
    join(l,i) ==
      rr := first l
      u : R :=
        i = 0 => first(rr.ranges)
        i = 1 => second(rr.ranges)
        i = 2 => third(rr.ranges)
        fourth(rr.ranges)
      for r in rest l repeat
        i = 0 => union(u,first(r.ranges))
        i = 1 => union(u,second(r.ranges))
        i = 2 => union(u,third(r.ranges))
        union(u,fourth(r.ranges))
      u
    parametricRange r == first(r.bounds)

    minPoints3D() == MINPOINTS
    setMinPoints3D n ==
      if n < 3 then error "three points minimum required"
      if MAXPOINTS < n then MAXPOINTS := n
      MINPOINTS := n
    maxPoints3D() == MAXPOINTS
    setMaxPoints3D n ==
      if n < 3 then error "three points minimum required"
```

```
      if MINPOINTS > n then MINPOINTS := n
      MAXPOINTS := n
    screenResolution3D() == SCREENRES
    setScreenResolution3D n ==
      if n < 2 then error "buy a new terminal"
      SCREENRES := n
    adaptive3D?() == ADAPTIVE
    setAdaptive3D b == ADAPTIVE := b

    numFunEvals3D() == NUMFUNEVALS
    debug3D b == DEBUG := b

--     setColor(p,c) == p.colNum := c

    xRange plot == second plot.bounds
    yRange plot == third plot.bounds
    zRange plot == fourth plot.bounds
    tRange plot == first plot.bounds

    tValues plot ==
      outList : L L F := nil()
      for curve in plot.functions repeat
        outList := concat(curve.knots,outList)
      outList

    select(l,f,g) ==
      m := f first l
      if (EQL(m, _$NaNvalue$Lisp)$Lisp) then m := 0
--      for p in rest l repeat m := g(m,fp)
      for p in rest l repeat
        fp : F := f p
        if (EQL(fp, _$NaNvalue$Lisp)$Lisp) then fp := 0
        m := g(m,fp)
      m

--     normalizeColor(p,lo,diff) ==
--       p.colNum := (p.colNum - lo)/diff

    rangeRefine(curve,nRange) ==
      checkRange nRange; l := lo nRange; h := hi nRange
      t := curve.knots; p := curve.points; f := curve.source
      while not null t and first t < l repeat
        (t := rest t; p := rest p)
      c : L F := nil(); q : L P := nil()
      while not null t and first t <= h repeat
        c := concat(first t,c); q := concat(first p,q)
        t := rest t; p := rest p
      if null c then return basicPlot(f,nRange)
      if first c < h then
        c := concat(h,c); q := concat(f h,q)
```

```
        NUMFUNEVALS := NUMFUNEVALS + 1
      t := c := reverse_! c; p := q := reverse_! q
      s := (h-l)/(MINPOINTS::F-1)
      if (first t) ^= l then
        t := c := concat(l,c); p := q := concat(f l,p)
        NUMFUNEVALS := NUMFUNEVALS + 1
      while not null rest t repeat
        n := wholePart((second(t) - first(t))/s)
        d := (second(t) - first(t))/((n+1)::F)
        for i in 1..n repeat
          t.rest := concat(first(t) + d,rest t); t1 := second t
          p.rest := concat(f t1,rest p)
          NUMFUNEVALS := NUMFUNEVALS + 1
          t := rest t; p := rest p
        t := rest t
        p := rest p
      xRange := select(q,xCoord,min) .. select(q,xCoord,max)
      yRange := select(q,yCoord,min) .. select(q,yCoord,max)
      zRange := select(q,zCoord,min) .. select(q,zCoord,max)
--       colorLo := select(q,color,min); colorHi := select(q,color,max)
--       (diff := colorHi - colorLo) = 0 =>
--         error "all points are the same color"
--       map(normalizeColor(#1,colorLo,diff),q)$ListPackage1(P)
      [f,[nRange,xRange,yRange,zRange],c,q]


    adaptivePlot(curve,tRg,xRg,yRg,zRg,pixelfraction,resolution) ==
      xDiff := hi xRg - lo xRg
      yDiff := hi yRg - lo yRg
      zDiff := hi zRg - lo zRg
--      xDiff = 0 or yDiff = 0 or zDiff = 0 => curve--!! delete this?
      if xDiff = 0::F then xDiff := 1::F
      if yDiff = 0::F then yDiff := 1::F
      if zDiff = 0::F then zDiff := 1::F
      l := lo tRg; h := hi tRg
      (tDiff := h-l) = 0 => curve
      t := curve.knots
      #t < 3 => curve
      p := curve.points; f := curve.source
      minLength:F := 4::F/resolution::F
      maxLength := 1/4::F
      tLimit := tDiff/(pixelfraction*resolution)::F
      while not null t and first t < l repeat (t := rest t; p := rest p)
      #t < 3 => curve
      headert := t; headerp := p
      st := t; sp := p
      todot : L L F := nil()
      todop : L L P := nil()
      while not null rest rest st repeat
        todot := concat_!(todot, st)
```

```
  todop := concat_!(todop, sp)
  st := rest st; sp := rest sp
st := headert; sp := headerp
todo1 := todot; todo2 := todop
n : I := 0

while not null todo1 repeat
  st := first(todo1)
  t0 := first(st); t1 := second(st); t2 := third(st)
  if t2 > h then leave
  t2 - t0 < tLimit =>
     todo1 := rest todo1
     todo2 := rest todo2;
     if not null todo1 then (t := first(todo1); p := first(todo2))
  sp := first(todo2)
  x0 := xCoord first(sp); y0 := yCoord first(sp); z0 := zCoord first(sp)
  x1 := xCoord second(sp); y1 := yCoord second(sp); z1 := zCoord second(sp)
  x2 := xCoord third(sp); y2 := yCoord third(sp); z2 := zCoord third(sp)
  a1 := (x1-x0)/xDiff; b1 := (y1-y0)/yDiff; c1 := (z1-z0)/zDiff
  a2 := (x2-x1)/xDiff; b2 := (y2-y1)/yDiff; c2 := (z2-z1)/zDiff
  s1 := sqrt(a1**2+b1**2+c1**2); s2 := sqrt(a2**2+b2**2+c2**2)
  dp := a1*a2+b1*b2+c1*c2
  s1 < maxLength and s2 < maxLength and _
     (s1 = 0 or s2 = 0 or
        s1 < minLength and s2 < minLength or _
        dp/s1/s2 > ANGLEBOUND) =>
          todo1 := rest todo1
          todo2 := rest todo2
          if not null todo1 then (t := first(todo1); p := first(todo2))
  if n = MAXPOINTS then leave else n := n + 1
  --if DEBUG then
     --r : L F := [minLength,maxLength,s1,s2,dp/s1/s2,ANGLEBOUND]
     --output(r::E)$O
  st := rest t
  if not null rest rest st then
    tm := (t0+t1)/2::F
    tj := tm
    t.rest := concat(tj,rest t)
    p.rest := concat(f tj, rest p)
    todo1 := concat_!(todo1, t)
    todo2 := concat_!(todo2, p)
    t := rest t; p := rest p
    todo1 := concat_!(todo1, t)
    todo2 := concat_!(todo2, p)
    t := rest t; p := rest p
    todo1 := rest todo1; todo2 := rest todo2

    tm := (t1+t2)/2::F
    tj := tm
    t.rest := concat(tj, rest t)
```

```
      p.rest := concat(f tj, rest p)
      todo1 := concat_!(todo1, t)
      todo2 := concat_!(todo2, p)
      t := rest t; p := rest p
      todo1 := concat_!(todo1, t)
      todo2 := concat_!(todo2, p)
      todo1 := rest todo1; todo2 := rest todo2
      if not null todo1 then (t := first(todo1); p := first(todo2))
    else
      tm := (t0+t1)/2::F
      tj := tm
      t.rest := concat(tj,rest t)
      p.rest := concat(f tj, rest p)
      todo1 := concat_!(todo1, t)
      todo2 := concat_!(todo2, p)
      t := rest t; p := rest p
      todo1 := concat_!(todo1, t)
      todo2 := concat_!(todo2, p)
      t := rest t; p := rest p

      tm := (t1+t2)/2::F
      tj := tm
      t.rest := concat(tj, rest t)
      p.rest := concat(f tj, rest p)
      todo1 := concat_!(todo1, t)
      todo2 := concat_!(todo2, p)
      todo1 := rest todo1; todo2 := rest todo2
      if not null todo1 then (t := first(todo1); p := first(todo2))
  if n > 0 then
    NUMFUNEVALS := NUMFUNEVALS + n
    t := curve.knots; p := curve.points
    xRg := select(p,xCoord,min) .. select(p,xCoord,max)
    yRg := select(p,yCoord,min) .. select(p,yCoord,max)
    zRg := select(p,zCoord,min) .. select(p,zCoord,max)
    [curve.source,[tRg,xRg,yRg,zRg],t,p]
  else curve

basicPlot(f,tRange) ==
  checkRange tRange; l := lo tRange; h := hi tRange
  t : L F := list l; p : L P := list f l
  s := (h-l)/(MINPOINTS-1)::F
  for i in 2..MINPOINTS-1 repeat
    l := l+s; t := concat(l,t)
    p := concat(f l,p)
  t := reverse_! concat(h,t)
  p := reverse_! concat(f h,p)
  xRange : R := select(p,xCoord,min) .. select(p,xCoord,max)
  yRange : R := select(p,yCoord,min) .. select(p,yCoord,max)
  zRange : R := select(p,zCoord,min) .. select(p,zCoord,max)
  [f,[tRange,xRange,yRange,zRange],t,p]
```

```
zoom(p,xRange,yRange,zRange) ==
 [[xRange,yRange,zRange],p.bounds,
  p.screenres,p.axisLabels,p.functions]

basicRefine(curve,nRange) ==
  tRange:R := first curve.ranges
  -- curve := copy$C curve  -- Yet another @#$%^&* compiler bug
  curve: C := [curve.source,curve.ranges,curve.knots,curve.points]
  t := curve.knots := copy curve.knots
  p := curve.points := copy curve.points
  l := lo nRange; h := hi nRange
  f := curve.source
  while not null rest t and first(t) < h repeat
    second(t) < l => (t := rest t; p := rest p)
    -- insert new point between t.0 and t.1
    tm:F := (first(t) + second(t))/2::F
    -- if DEBUG then output$O (tm::E)
    pm := f tm
    NUMFUNEVALS := NUMFUNEVALS + 1
    t.rest := concat(tm,rest t); t := rest rest t
    p.rest := concat(pm,rest p); p := rest rest p
  t := curve.knots; p := curve.points
  xRange := select(p,xCoord,min) .. select(p,xCoord,max)
  yRange := select(p,yCoord,min) .. select(p,yCoord,max)
  zRange := select(p,zCoord,min) .. select(p,zCoord,max)
  [curve.source,[tRange,xRange,yRange,zRange],t,p]

refine p == refine(p,parametricRange p)
refine(p,nRange) ==
  NUMFUNEVALS := 0
  tRange := parametricRange p
  nRange := intersect(tRange,nRange)
  curves: L C := [basicRefine(c,nRange) for c in p.functions]
  xRange := join(curves,1); yRange := join(curves,2)
  zRange := join(curves,3)
  scrres := p.screenres
  if adaptive3D? then
    tlimit := 8
    curves := [adaptivePlot(c,nRange,xRange,yRange,zRange, _
               tlimit,scrres := 2*scrres) for c in curves]
    xRange := join(curves,1); yRange := join(curves,2)
    zRange := join(curves,3)
  [p.display,[tRange,xRange,yRange,zRange], _
   scrres,p.axisLabels,curves]

plot(p:%,tRange:R) ==
  -- re plot p on a new range making use of the points already
  -- computed if possible
  NUMFUNEVALS := 0
```

```
      curves: L C := [rangeRefine(c,tRange) for c in p.functions]
      xRange := join(curves,1); yRange := join(curves,2)
      zRange := join(curves,3)
      if adaptive3D? then
        tlimit := 8
        curves := [adaptivePlot(c,tRange,xRange,yRange,zRange,tlimit, _
                     p.screenres) for c in curves]
        xRange := join(curves,1); yRange := join(curves,2)
        zRange := join(curves,3)
--      print(NUMFUNEVALS::OUT)
      [[xRange,yRange,zRange],[tRange,xRange,yRange,zRange],
        p.screenres,p.axisLabels,curves]

    pointPlot(f:F -> P,tRange:R) ==
      p := basicPlot(f,tRange)
      r := p.ranges
      NUMFUNEVALS := MINPOINTS
      if adaptive3D? then
       p := adaptivePlot(p,first r,second r,third r,fourth r,8,SCREENRES)
--      print(NUMFUNEVALS::OUT)
--      print(p::OUT)
      [ rest r, r, SCREENRES, nil(), [ p ] ]

    pointPlot(f:F -> P,tRange:R,xRange:R,yRange:R,zRange:R) ==
      p := pointPlot(f,tRange)
      p.display:= [checkRange xRange,checkRange yRange,checkRange zRange]
      p

    myTrap: (F-> F, F) -> F
    myTrap(ff:F-> F, f:F):F ==
      s := trapNumericErrors(ff(f))$Lisp :: Union(F, "failed")
      if (s) case "failed" then
        r:F := _$NaNvalue$Lisp
      else
        r:F := s
      r

    plot(f1:F -> F,f2:F -> F,f3:F -> F,col:F -> F,tRange:R) ==
      p := basicPlot(
       (z:F):P+->point(myTrap(f1,z),myTrap(f2,z),myTrap(f3,z),col(z)),tRange)
      r := p.ranges
      NUMFUNEVALS := MINPOINTS
      if adaptive3D? then
       p := adaptivePlot(p,first r,second r,third r,fourth r,8,SCREENRES)
--      print(NUMFUNEVALS::OUT)
      [ rest r, r, SCREENRES, nil(), [ p ] ]

    plot(f1:F -> F,f2:F -> F,f3:F -> F,col:F -> F,_
              tRange:R,xRange:R,yRange:R,zRange:R) ==
      p := plot(f1,f2,f3,col,tRange)
```

```
      p.display:= [checkRange xRange,checkRange yRange,checkRange zRange]
      p

--% terminal output

    coerce r ==
      spaces := "   " :: OUT
      xSymbol := "x = " :: OUT; ySymbol := "y = " :: OUT
      zSymbol := "z = " :: OUT; tSymbol := "t = " :: OUT
      tRange := (parametricRange r) :: OUT
      f : L OUT := nil()
      for curve in r.functions repeat
        xRange := coerce curve.ranges.1
        yRange := coerce curve.ranges.2
        zRange := coerce curve.ranges.3
        l : L OUT := [xSymbol,xRange,spaces,ySymbol,yRange,_
                      spaces,zSymbol,zRange]
        l := concat_!([tSymbol,tRange,spaces],l)
        h : OUT := hconcat l
        l := [p::OUT for p in curve.points]
        f := concat(vconcat concat(h,l),f)
      prefix("PLOT" :: OUT,reverse_! f)

----% graphics output

    listBranches plot ==
      outList : L L P := nil()
      for curve in plot.functions repeat
        outList := concat(curve.points,outList)
      outList
```

———-

— PLOT3D.dotabb —

```
"PLOT3D" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PLOT3D"]
"TRANFUN" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TRANFUN"]
"PLOT3D" -> "TRANFUN"
```

———-

17.23 domain PBWLB PoincareBirkhoffWittLyndonBasis

— PoincareBirkhoffWittLyndonBasis.input —

```
)set break resume
)sys rm -f PoincareBirkhoffWittLyndonBasis.output
)spool PoincareBirkhoffWittLyndonBasis.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PoincareBirkhoffWittLyndonBasis
--R
--R PoincareBirkhoffWittLyndonBasis(VarSet: OrderedSet)  is a domain constructor
--R Abbreviation for PoincareBirkhoffWittLyndonBasis is PBWLB
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PBWLB
--R
--R------------------------------ Operations --------------------------------
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               1 : () -> %
--R coerce : VarSet -> %                  coerce : LyndonWord(VarSet) -> %
--R coerce : % -> OutputForm              first : % -> LyndonWord(VarSet)
--R hash : % -> SingleInteger             latex : % -> String
--R length : % -> NonNegativeInteger      max : (%,%) -> %
--R min : (%,%) -> %                      rest : % -> %
--R retract : % -> LyndonWord(VarSet)     retractable? : % -> Boolean
--R varList : % -> List(VarSet)           ?~=? : (%,%) -> Boolean
--R coerce : % -> OrderedFreeMonoid(VarSet)
--R listOfTerms : % -> List(LyndonWord(VarSet))
--R retractIfCan : % -> Union(LyndonWord(VarSet),"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— PoincareBirkhoffWittLyndonBasis.help —

```
=====================================================================
PoincareBirkhoffWittLyndonBasis examples
=====================================================================

See Also:
o )show PoincareBirkhoffWittLyndonBasis
```

———-

17.23.1 PoincareBirkhoffWittLyndonBasis (PBWLB)



Exports:

1	coerce	first	hash	latex
length	listOfTerms	max	min	rest
retract	retractable?	retractIfCan	varList	?~=?
?<?	?<=?	?=?	?>?	?>=?

— domain PBWLB PoincareBirkhoffWittLyndonBasis —

```
)abbrev domain PBWLB PoincareBirkhoffWittLyndonBasis
++ Author: Michel Petitot (petitot@lifl.fr).
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain provides the internal representation
++ of polynomials in non-commutative variables written
++ over the Poincare-Birkhoff-Witt basis.
++ See the \spadtype{XPBWPolynomial} domain constructor.
++ See Free Lie Algebras by C. Reutenauer
++ (Oxford science publications).

PoincareBirkhoffWittLyndonBasis(VarSet: OrderedSet): Public == Private where
   WORD    ==> OrderedFreeMonoid(VarSet)
   LWORD   ==> LyndonWord(VarSet)
   LWORDS  ==> List(LWORD)
   PI      ==> PositiveInteger
   NNI     ==> NonNegativeInteger
   EX      ==> OutputForm
```

```
Public == Join(OrderedSet, RetractableTo LWORD) with
   1: constant -> %
      ++ \spad{1} returns the empty list.
   coerce       : $ -> WORD
      ++ \spad{coerce([l1]*[l2]*...[ln])} returns the word \spad{l1*l2*...*ln},
      ++ where \spad{[l_i]} is the backeted form of the Lyndon word \spad{l_i}.
   coerce       : VarSet -> $
      ++ \spad{coerce(v)} return \spad{v}
   first        : $ -> LWORD
      ++ \spad{first([l1]*[l2]*...[ln])} returns the Lyndon word \spad{l1}.
   length       : $ -> NNI
      ++ \spad{length([l1]*[l2]*...[ln])} returns the length of the word \spad{l1*l2*...*ln}.
   listOfTerms  : $ -> LWORDS
      ++ \spad{listOfTerms([l1]*[l2]*...[ln])} returns the list of words \spad{l1, l2, .... ln}.
   rest         : $ -> $
      ++ \spad{rest([l1]*[l2]*...[ln])} returns the list \spad{l2, .... ln}.
   retractable? : $ -> Boolean
      ++ \spad{retractable?([l1]*[l2]*...[ln])} returns true iff \spad{n}  equals \spad{1}.
   varList      : $ -> List VarSet
      ++ \spad{varList([l1]*[l2]*...[ln])} returns the list of
      ++ variables in the word \spad{l1*l2*...*ln}.

Private == add

 -- Representation
  Rep := LWORDS

 -- Locales
  recursif: ($,$) -> Boolean

 -- Define
  1 == nil

  x = y == x =$Rep y

  varList x ==
     null x => nil
     le: List VarSet := "setUnion"/ [varList$LWORD l for l in x]

  first x == first(x)$Rep
  rest x == rest(x)$Rep

  coerce(v: VarSet):$ == [ v::LWORD ]
  coerce(l: LWORD):$ == [l]
  listOfTerms(x:$):LWORDS == x pretend LWORDS

  coerce(x:$):WORD ==
    null x => 1
    x.first :: WORD *$WORD coerce(x.rest)
```

```
coerce(x:$):EX ==
  null x => outputForm(1$Integer)$EX
  reduce(_* ,[l :: EX for l in x])$List(EX)

retractable? x ==
  null x => false
  null x.rest

retract x ==
   #x ^= 1 => error "cannot convert to Lyndon word"
   x.first

retractIfCan x ==
   retractable? x => x.first
   "failed"

length x ==
   n: Integer := +/[ length l for l in x]
   n::NNI

recursif(x, y) ==
  null y => false
  null x => true
  x.first = y.first => recursif(rest(x), rest(y))
  lexico(x.first, y.first)

x < y ==
  lx: NNI := length x; ly: NNI := length y
  lx = ly => recursif(x,y)
  lx < ly
```

———-

— PBWLB.dotabb —

```
"PBWLB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PBWLB"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"PBWLB" -> "FLAGG"
```

———-

17.24 domain POINT Point

— Point.input —

```
)set break resume
)sys rm -f Point.output
)spool Point.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Point
--R
--R Point(R: Ring)  is a domain constructor
--R Abbreviation for Point is POINT
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for POINT
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if R has ABELGRP          concat : List(%) -> %
--R concat : (%,%) -> %                   concat : (R,%) -> %
--R concat : (%,R) -> %                   construct : List(R) -> %
--R convert : List(R) -> %                copy : % -> %
--R cross : (%,%) -> %                    delete : (%,Integer) -> %
--R dimension : % -> PositiveInteger      ?.? : (%,Integer) -> R
--R elt : (%,Integer,R) -> R              empty : () -> %
--R empty? : % -> Boolean                 entries : % -> List(R)
--R eq? : (%,%) -> Boolean                extend : (%,List(R)) -> %
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
--R insert : (%,%,Integer) -> %           insert : (R,%,Integer) -> %
--R map : (((R,R) -> R),%,%) -> %         map : ((R -> R),%) -> %
--R new : (NonNegativeInteger,R) -> %     point : List(R) -> %
--R qelt : (%,Integer) -> R               reverse : % -> %
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (%,R) -> % if R has MONOID
--R ?*? : (R,%) -> % if R has MONOID
--R ?*? : (Integer,%) -> % if R has ABELGRP
--R ?+? : (%,%) -> % if R has ABELSG
--R ?-? : (%,%) -> % if R has ABELGRP
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if R has SETCAT
--R convert : % -> InputForm if R has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R delete : (%,UniversalSegment(Integer)) -> %
--R dot : (%,%) -> R if R has RING
```

```
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,R) -> % if $ has shallowlyMutable
--R find : ((R -> Boolean),%) -> Union(R,"failed")
--R first : % -> R if Integer has ORDSET
--R hash : % -> SingleInteger if R has SETCAT
--R latex : % -> String if R has SETCAT
--R length : % -> R if R has RADCAT and R has RING
--R less? : (%,NonNegativeInteger) -> Boolean
--R magnitude : % -> R if R has RADCAT and R has RING
--R map! : ((R -> R),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if R has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R merge : (%,%) -> % if R has ORDSET
--R merge : (((R,R) -> Boolean),%,%) -> %
--R min : (%,%) -> % if R has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R outerProduct : (%,%) -> Matrix(R) if R has RING
--R parts : % -> List(R) if $ has finiteAggregate
--R position : (R,%,Integer) -> Integer if R has SETCAT
--R position : (R,%) -> Integer if R has SETCAT
--R position : ((R -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,R) -> R if $ has shallowlyMutable
--R reduce : (((R,R) -> R),%) -> R if $ has finiteAggregate
--R reduce : (((R,R) -> R),%,R) -> R if $ has finiteAggregate
--R reduce : (((R,R) -> R),%,R,R) -> R if $ has finiteAggregate and R has SETCAT
--R remove : ((R -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (R,%) -> % if $ has finiteAggregate and R has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and R has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((R -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),R) -> R if $ has shallowlyMutable
--R setelt : (%,Integer,R) -> R if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if R has ORDSET
--R sort : (((R,R) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and R has ORDSET
--R sort! : (((R,R) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if R has ORDSET
--R sorted? : (((R,R) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R zero : NonNegativeInteger -> % if R has ABELMON
```

```
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Point.help** —

```
=====================================================================
Point examples
=====================================================================

See Also:
o )show Point
```

———-

17.24.1 Point (POINT)



See

⇒ “SubSpaceComponentProperty” (COMPPROP) 20.34.1 on page 2592
⇒ “SubSpace” (SUBSPACE) 20.33.1 on page 2582

Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	count	cross
delete	dimension	dot	elt	empty
empty?	entries	entry?	eq?	eval
every?	extend	fill!	find	first
hash	index?	indices	insert	insert
latex	length	less?	magnitude	map
map!	max	maxIndex	member?	members
merge	merge	min	minIndex	more?
new	outerProduct	parts	point	position
qelt	qsetelt!	reduce	remove	removeDuplicates
reverse	reverse!	sample	select	setelt
size?	sort	sort!	sorted?	swap!
zero	#?	?*?	?+?	?-?
?<?	?<=?	?=?	?>?	?>=?
?.?	?~=?	-?	?.?	

— domain POINT Point —

```
)abbrev domain POINT Point
++ Author: Mark Botch
++ Description:
++ This domain implements points in coordinate space

Point(R:Ring) : Exports == Implementation where
  -- Domains for points, subspaces and properties of components in
  -- a subspace

  Exports ==> PointCategory(R)

  Implementation ==> Vector (R) add
    PI   ==> PositiveInteger

    point(l:List R):% ==
      pt := new(#l,R)
      for x in l for i in minIndex(pt).. repeat
        pt.i := x
      pt
    dimension p == (# p)::PI  -- Vector returns NonNegativeInteger...?
    convert(l:List R):% == point(l)
    cross(p0, p1) ==
      #p0 ^=3 or #p1^=3 => error "Arguments to cross must be three dimensional"
      point [p0.2 * p1.3 - p1.2 * p0.3, _
             p1.1 * p0.3 - p0.1 * p1.3, _
             p0.1 * p1.2 - p1.1 * p0.2]
    extend(p,l) == concat(p,point l)
```

———-

— **POINT.dotabb** —

```
"POINT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=POINT"]
"PTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PTCAT"]
"POINT" -> "PTCAT"
```

———-

17.25 domain POLY Polynomial

— **Polynomial.input** —

```
)set break resume
)sys rm -f Polynomial.output
)spool Polynomial.output
)set message test on
)set message auto off
--S 1 of 46
x + 1
--R
--R
--R   (1)  x + 1
--R                                                  Type: Polynomial(Integer)
--E 1

--S 2 of 46
z - 2.3
--R
--R
--R   (2)  z - 2.3
--R                                                    Type: Polynomial(Float)
--E 2

--S 3 of 46
y**2 - z + 3/4
--R
--R
--R               2   3
--R   (3)  - z + y  + -
--R                   4
--R                                       Type: Polynomial(Fraction(Integer))
--E 3

--S 4 of 46
y **2 + x*y + y
```

```
--R
--R
--R         2
--R   (4)  y  + (x + 1)y
--R                                                    Type: Polynomial(Integer)
--E 4

--S 5 of 46
% :: DMP([y,x],INT)
--R
--R
--R         2
--R   (5)  y  + y x + y
--R                        Type: DistributedMultivariatePolynomial([y,x],Integer)
--E 5

--S 6 of 46
p := (y-1)**2 * x * z
--R
--R
--R            2
--R   (6)  (x y  - 2x y + x)z
--R                                                    Type: Polynomial(Integer)
--E 6

--S 7 of 46
q := (y-1) * x * (z+5)
--R
--R
--R   (7)  (x y - x)z + 5x y - 5x
--R                                                    Type: Polynomial(Integer)
--E 7

--S 8 of 46
factor(q)
--R
--R
--R   (8)  x(y - 1)(z + 5)
--R                                          Type: Factored(Polynomial(Integer))
--E 8

--S 9 of 46
p - q**2
--R
--R
--R   (9)
--R         2 2     2     2  2          2      2       2             2
--R     (- x y  + 2x y - x )z  + ((- 10x  + x)y  + (20x  - 2x)y - 10x  + x)z
--R   +
--R          2 2      2       2
```

```
--R     - 25x y  + 50x y - 25x
--R                                                    Type: Polynomial(Integer)
--E 9

--S 10 of 46
gcd(p,q)
--R
--R
--R   (10)  x y - x
--R                                                    Type: Polynomial(Integer)
--E 10

--S 11 of 46
factor %
--R
--R
--R   (11)  x(y - 1)
--R                                          Type: Factored(Polynomial(Integer))
--E 11

--S 12 of 46
lcm(p,q)
--R
--R
--R             2             2        2
--R   (12)  (x y  - 2x y + x)z  + (5x y  - 10x y + 5x)z
--R                                                    Type: Polynomial(Integer)
--E 12

--S 13 of 46
content p
--R
--R
--R   (13)  1
--R                                                       Type: PositiveInteger
--E 13

--S 14 of 46
resultant(p,q,z)
--R
--R
--R           2 3      2 2      2      2
--R   (14)  5x y  - 15x y  + 15x y - 5x
--R                                                    Type: Polynomial(Integer)
--E 14

--S 15 of 46
resultant(p,q,x)
--R
--R
```

```
--R   (15)  0
--R                                                  Type: Polynomial(Integer)
--E 15

--S 16 of 46
mainVariable p
--R
--R
--R   (16)  z
--R                                                    Type: Union(Symbol,...)
--E 16

--S 17 of 46
mainVariable(1 :: POLY INT)
--R
--R
--R   (17)  "failed"
--R                                                  Type: Union("failed",...)
--E 17

--S 18 of 46
ground? p
--R
--R
--R   (18)  false
--R                                                               Type: Boolean
--E 18

--S 19 of 46
ground?(1 :: POLY INT)
--R
--R
--R   (19)  true
--R                                                               Type: Boolean
--E 19

--S 20 of 46
variables p
--R
--R
--R   (20)  [z,y,x]
--R                                                          Type: List(Symbol)
--E 20

--S 21 of 46
degree(p,x)
--R
--R
--R   (21)  1
--R                                                      Type: PositiveInteger
```

```
--E 21

--S 22 of 46
degree(p,y)
--R
--R
--R   (22)  2
--R                                                    Type: PositiveInteger
--E 22

--S 23 of 46
degree(p,z)
--R
--R
--R   (23)  1
--R                                                    Type: PositiveInteger
--E 23

--S 24 of 46
degree(p,[x,y,z])
--R
--R
--R   (24)  [1,2,1]
--R                                          Type: List(NonNegativeInteger)
--E 24

--S 25 of 46
minimumDegree(p,z)
--R
--R
--R   (25)  1
--R                                                    Type: PositiveInteger
--E 25

--S 26 of 46
totalDegree p
--R
--R
--R   (26)  4
--R                                                    Type: PositiveInteger
--E 26

--S 27 of 46
leadingMonomial p
--R
--R
--R            2
--R   (27)  x y z
--R                                               Type: Polynomial(Integer)
--E 27
```

```
--S 28 of 46
reductum p
--R
--R
--R   (28)  (- 2x y + x)z
--R                                                    Type: Polynomial(Integer)
--E 28

--S 29 of 46
p - leadingMonomial p - reductum p
--R
--R
--R   (29)  0
--R                                                    Type: Polynomial(Integer)
--E 29

--S 30 of 46
leadingCoefficient p
--R
--R
--R   (30)  1
--R                                                       Type: PositiveInteger
--E 30

--S 31 of 46
p
--R
--R
--R             2
--R   (31)  (x y  - 2x y + x)z
--R                                                    Type: Polynomial(Integer)
--E 31

--S 32 of 46
eval(p,x,w)
--R
--R
--R             2
--R   (32)  (w y  - 2w y + w)z
--R                                                    Type: Polynomial(Integer)
--E 32

--S 33 of 46
eval(p,x,1)
--R
--R
--R           2
--R   (33)  (y  - 2y + 1)z
--R                                                    Type: Polynomial(Integer)
```

```
--E 33

--S 34 of 46
eval(p,x,y^2 - 1)
--R
--R
--R           4     3
--R   (34)  (y  - 2y  + 2y - 1)z
--R                                                  Type: Polynomial(Integer)
--E 34

--S 35 of 46
D(p,x)
--R
--R
--R           2
--R   (35)  (y  - 2y + 1)z
--R                                                  Type: Polynomial(Integer)
--E 35

--S 36 of 46
D(p,y)
--R
--R
--R   (36)  (2x y - 2x)z
--R                                                  Type: Polynomial(Integer)
--E 36

--S 37 of 46
D(p,z)
--R
--R
--R            2
--R   (37)  x y  - 2x y + x
--R                                                  Type: Polynomial(Integer)
--E 37

--S 38 of 46
integrate(p,y)
--R
--R
--R          1    3      2
--R   (38)  (- x y  - x y  + x y)z
--R          3
--R                                        Type: Polynomial(Fraction(Integer))
--E 38

--S 39 of 46
qr := monicDivide(p,x+1,x)
--R
```

```
--R
--R                      2                           2
--R   (39)  [quotient= (y  - 2y + 1)z,remainder= (- y  + 2y - 1)z]
--R   Type: Record(quotient: Polynomial(Integer),remainder: Polynomial(Integer))
--E 39

--S 40 of 46
qr.remainder
--R
--R
--R             2
--R   (40)  (- y  + 2y - 1)z
--R                                                    Type: Polynomial(Integer)
--E 40

--S 41 of 46
p - ((x+1) * qr.quotient + qr.remainder)
--R
--R
--R   (41)  0
--R                                                    Type: Polynomial(Integer)
--E 41

--S 42 of 46
p/q
--R
--R
--R         (y - 1)z
--R   (42)  --------
--R           z + 5
--R                                          Type: Fraction(Polynomial(Integer))
--E 42

--S 43 of 46
(2/3) * x**2 - y + 4/5
--R
--R
--R               2  2   4
--R   (43)  - y + - x  + -
--R               3      5
--R                                          Type: Polynomial(Fraction(Integer))
--E 43

--S 44 of 46
% :: FRAC POLY INT
--R
--R
--R                    2
--R         - 15y + 10x  + 12
--R   (44)  -----------------
```

```
--R                 15
--R                                          Type: Fraction(Polynomial(Integer))
--E 44

--S 45 of 46
% :: POLY FRAC INT
--R
--R
--R               2  2   4
--R   (45)  - y + - x  + -
--R               3      5
--R                                          Type: Polynomial(Fraction(Integer))
--E 45

--S 46 of 46
map(numeric,%)
--R
--R
--R                                            2
--R   (46)  - 1.0 y + 0.6666666666 6666666667 x  + 0.8
--R                                                        Type: Polynomial(Float)
--E 46
)spool
)lisp (bye)
```

———-

— Polynomial.help —

```
========================================================================
Polynomial examples
========================================================================

The domain constructor Polynomial (abbreviation: POLY) provides
polynomials with an arbitrary number of unspecified variables.

It is used to create the default polynomial domains in Axiom.  Here
the coefficients are integers.

  x + 1
    x + 1
                          Type: Polynomial Integer

Here the coefficients have type Float.

  z - 2.3
    z - 2.3
                           Type: Polynomial Float
```

```
And here we have a polynomial in two variables with coefficients which
have type Fraction Integer.

  y**2 - z + 3/4
          2   3
    - z + y  + -
               4
                              Type: Polynomial Fraction Integer

The representation of objects of domains created by Polynomial is that
of recursive univariate polynomials. The term univariate means "one
variable". The term multivariate means "possibly more than one variable".

This recursive structure is sometimes obvious from the display of a polynomial.

  y **2 + x*y + y
     2
    y  + (x + 1)y
                              Type: Polynomial Integer

In this example, you see that the polynomial is stored as a polynomial
in y with coefficients that are polynomials in x with integer coefficients.
In fact, you really don't need to worry about the representation unless you
are working on an advanced application where it is critical. The polynomial
types created from DistributedMultivariatePolynomial and
NewDistributedMultivariatePolynomial are stored and displayed in a
non-recursive manner.

You see a "flat" display of the above polynomial by converting to
one of those types.

  % :: DMP([y,x],INT)
     2
    y  + y x + y
                   Type: DistributedMultivariatePolynomial([y,x],Integer)

We will demonstrate many of the polynomial facilities by using two
polynomials with integer coefficients.

By default, the interpreter expands polynomial expressions, even if they
are written in a factored format.

  p := (y-1)**2 * x * z
        2
    (x y  - 2x y + x)z
                   Type: Polynomial Integer

See Factored to see how to create objects in factored form directly.

  q := (y-1) * x * (z+5)
```

```
    (x y - x)z + 5x y - 5x
                  Type: Polynomial Integer
```

The fully factored form can be recovered by using factor.

```
  factor(q)
    x(y - 1)(z + 5)
                  Type: Factored Polynomial Integer
```

This is the same name used for the operation to factor integers. Such reuse of names is called overloading and makes it much easier to think of solving problems in general ways. Axiom facilities for factoring polynomials created with Polynomial are currently restricted to the integer and rational number coefficient cases.

The standard arithmetic operations are available for polynomials.

```
  p - q**2
         2 2     2     2  2          2      2       2             2
     (- x y  + 2x y - x )z  + ((- 10x  + x)y  + (20x  - 2x)y - 10x  + x)z
   +
          2 2      2       2
     - 25x y  + 50x y - 25x
                  Type: Polynomial Integer
```

The operation gcd is used to compute the greatest common divisor of two polynomials.

```
  gcd(p,q)
    x y - x
                  Type: Polynomial Integer
```

In the case of p and q, the gcd is obvious from their definitions. We factor the gcd to show this relationship better.

```
  factor %
    x(y - 1)
                  Type: Factored Polynomial Integer
```

The least common multiple is computed by using lcm.

```
  lcm(p,q)
       2             2        2
    (x y  - 2x y + x)z  + (5x y  - 10x y + 5x)z
                  Type: Polynomial Integer
```

Use content to compute the greatest common divisor of the coefficients of the polynomial.

```
  content p
```

```
   1
                  Type: PositiveInteger
```

Many of the operations on polynomials require you to specify a variable. For example, resultant requires you to give the variable in which the polynomials should be expressed.

This computes the resultant of the values of p and q, considering them as polynomials in the variable z. They do not share a root when thought of as polynomials in z.

```
  resultant(p,q,z)
       2 3      2 2      2      2
    5x y  - 15x y  + 15x y - 5x
                  Type: Polynomial Integer
```

This value is 0 because as polynomials in x the polynomials have a common root.

```
  resultant(p,q,x)
    0
                  Type: Polynomial Integer
```

The data type used for the variables created by Polynomial is Symbol. As mentioned above, the representation used by Polynomial is recursive and so there is a main variable for nonconstant polynomials.

The operation mainVariable returns this variable. The return type is actually a union of Symbol and "failed".

```
  mainVariable p
    z
                  Type: Union(Symbol,...)
```

The latter branch of the union is be used if the polynomial has no variables, that is, is a constant.

```
  mainVariable(1 :: POLY INT)
    "failed"
                  Type: Union("failed",...)
```

You can also use the predicate ground? to test whether a polynomial is in fact a member of its ground ring.

```
  ground? p
    false
                  Type: Boolean

  ground?(1 :: POLY INT)
    true
```

```
                  Type: Boolean
```

The complete list of variables actually used in a particular polynomial
is returned by variables. For constant polynomials, this list is empty.

```
  variables p
    [z,y,x]
                  Type: List Symbol
```

The degree operation returns the degree of a polynomial in a specific variable.

```
  degree(p,x)
    1
                  Type: PositiveInteger

  degree(p,y)
    2
                  Type: PositiveInteger

  degree(p,z)
    1
                  Type: PositiveInteger
```

If you give a list of variables for the second argument, a list of the
degrees in those variables is returned.

```
  degree(p,[x,y,z])
    [1,2,1]
                  Type: List NonNegativeInteger
```

The minimum degree of a variable in a polynomial is computed using
minimumDegree.

```
  minimumDegree(p,z)
    1
                  Type: PositiveInteger
```

The total degree of a polynomial is returned by totalDegree.

```
  totalDegree p
    4
                  Type: PositiveInteger
```

It is often convenient to think of a polynomial as a leading monomial plus
the remaining terms.

```
  leadingMonomial p
        2
     x y z
                  Type: Polynomial Integer
```

```
The reductum operation returns a polynomial consisting of the sum of
the monomials after the first.

  reductum p
    (- 2x y + x)z
                    Type: Polynomial Integer

These have the obvious relationship that the original polynomial is
equal to the leading monomial plus the reductum.

  p - leadingMonomial p - reductum p
    0
                    Type: Polynomial Integer

The value returned by leadingMonomial includes the coefficient of that term.
This is extracted by using leadingCoefficient on the original polynomial.

  leadingCoefficient p
    1
                    Type: PositiveInteger

The operation eval is used to substitute a value for a variable in a
polynomial.

  p
        2
    (x y  - 2x y + x)z
                    Type: Polynomial Integer

This value may be another variable, a constant or a polynomial.

  eval(p,x,w)
        2
    (w y  - 2w y + w)z
                    Type: Polynomial Integer

  eval(p,x,1)
      2
    (y  - 2y + 1)z
                    Type: Polynomial Integer

Actually, all the things being substituted are just polynomials,
some more trivial than others.

  eval(p,x,y^2 - 1)
      4     3
    (y  - 2y  + 2y - 1)z
                    Type: Polynomial Integer
```

Derivatives are computed using the D operation.

```
  D(p,x)
      2
    (y  - 2y + 1)z
                   Type: Polynomial Integer
```

The first argument is the polynomial and the second is the variable.

```
  D(p,y)
    (2x y - 2x)z
                   Type: Polynomial Integer
```

Even if the polynomial has only one variable, you must specify it.

```
  D(p,z)
       2
    x y  - 2x y + x
                   Type: Polynomial Integer
```

Integration of polynomials is similar and the integrate operation is used.

Integration requires that the coefficients support division. Axiom converts polynomials over the integers to polynomials over the rational numbers before integrating them.

```
  integrate(p,y)
     1    3      2
    (- x y  - x y  + x y)z
     3
                  Type: Polynomial Fraction Integer
```

It is not possible, in general, to divide two polynomials. In our example using polynomials over the integers, the operation monicDivide divides a polynomial by a monic polynomial (that is, a polynomial with leading coefficient equal to 1). The result is a record of the quotient and remainder of the division.

You must specify the variable in which to express the polynomial.

```
  qr := monicDivide(p,x+1,x)
                2                            2
    [quotient= (y  - 2y + 1)z,remainder= (- y  + 2y - 1)z]
     Type: Record(quotient: Polynomial Integer,remainder: Polynomial Integer)
```

The selectors of the components of the record are quotient and remainder. Issue this to extract the remainder.

```
  qr.remainder
        2
```

```
    (- y  + 2y - 1)z
                        Type: Polynomial Integer
```

Now that we can extract the components, we can demonstrate the relationship among them and the arguments to our original expression qr := monicDivide(p,x+1,x).

```
  p - ((x+1) * qr.quotient + qr.remainder)
    0
                        Type: Polynomial Integer
```

If the / operator is used with polynomials, a fraction object is created. In this example, the result is an object of type Fraction Polynomial Integer.

```
  p/q
    (y - 1)z
    --------
      z + 5
                        Type: Fraction Polynomial Integer
```

If you use rational numbers as polynomial coefficients, the resulting object is of type Polynomial Fraction Integer.

```
  (2/3) * x**2 - y + 4/5
         2  2   4
    - y + - x  + -
         3      5
                        Type: Polynomial Fraction Integer
```

This can be converted to a fraction of polynomials and back again, if required.

```
  % :: FRAC POLY INT
              2
    - 15y + 10x  + 12
    -----------------
            15
                        Type: Fraction Polynomial Integer

  % :: POLY FRAC INT
         2  2   4
    - y + - x  + -
         3      5
                        Type: Polynomial Fraction Integer
```

To convert the coefficients to floating point, map the numeric operation on the coefficients of the polynomial.


```
  map(numeric,%)
```

```
    - 1.0 y + 0.6666666666 6666666667 x  + 0.8
                        Type: Polynomial Float

See Also:
o )help Factored
o )help UnivariatePolynomial
o )help MultivariatePolynomial
o )help DistributedMultivariatePolynomial
o )help NewDistributedMultivariatePolynomial
o )show Polynomial
```

———-

17.25.1 Polynomial (POLY)



See

⇒ “MultivariatePolynomial” (MPOLY) 14.16.1 on page 1649
⇒ “SparseMultivariatePolynomial” (SMP) 20.14.1 on page 2390
⇒ “IndexedExponents” (INDE) 10.9.1 on page 1187

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	convert
D	degree	differentiate
discriminant	eval	exquo
factor	factorPolynomial	factorSquareFreePolynomial
gcd	gcdPolynomial	ground
ground?	hash	integrate
isExpt	isPlus	isTimes
latex	lcm	leadingCoefficient
leadingMonomial	mainVariable	map
mapExponents	max	min
minimumDegree	monicDivide	monomial
monomial?	monomials	multivariate
one?	numberOfMonomials	patternMatch
pomopo!	prime?	primitiveMonomials
primitivePart	recip	reducedSystem
reductum	resultant	retract
retractIfCan	sample	solveLinearPolynomialEquation
squareFree	squareFreePart	squareFreePolynomial
subtractIfCan	totalDegree	totalDegree
unit?	unitCanonical	unitNormal
univariate	variables	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?~=?	?/?
?<?	?<=?	?>?
?>=?		

— domain POLY Polynomial —

```
)abbrev domain POLY Polynomial
++ Author: Dave Barton, Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, degree, eval, coefficient, monomial, differentiate,
++ resultant, gcd
++ Related Constructors: SparseMultivariatePolynomial, MultivariatePolynomial
++ Also See:
++ AMS Classifications:
++ Keywords: polynomial, multivariate
++ References:
++ Description:
++ This type is the basic representation of sparse recursive multivariate
++ polynomials whose variables are arbitrary symbols. The ordering
++ is alphabetic determined by the Symbol type.
++ The coefficient ring may be non commutative,
```

```
++ but the variables are assumed to commute.

Polynomial(R:Ring):
  PolynomialCategory(R, IndexedExponents Symbol, Symbol) with
   if R has Algebra Fraction Integer then
     integrate: (%, Symbol) -> %
       ++ integrate(p,x) computes the integral of \spad{p*dx}, i.e.
       ++ integrates the polynomial p with respect to the variable x.
 == SparseMultivariatePolynomial(R, Symbol) add

    import UserDefinedPartialOrdering(Symbol)

    coerce(p:%):OutputForm ==
      (r:= retractIfCan(p)@Union(R,"failed")) case R => r::R::OutputForm
      a :=
        userOrdered?() => largest variables p
        mainVariable(p)::Symbol
      outputForm(univariate(p, a), a::OutputForm)

    if R has Algebra Fraction Integer then
      integrate(p, x) == (integrate univariate(p, x)) (x::%)
```

———-

— **POLY.dotabb** —

```
"POLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=POLY"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"POLY" -> "ALIST"
```

———-

17.26 domain IDEAL PolynomialIdeals

— **PolynomialIdeals.input** —

```
)set break resume
)sys rm -f PolynomialIdeals.output
)spool PolynomialIdeals.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
```

```
)show PolynomialIdeals
--R
--R PolynomialIdeals(F: Field,Expon: OrderedAbelianMonoidSup,VarSet: OrderedSet,DPoly: Polynomia
--R Abbreviation for PolynomialIdeals is IDEAL
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for IDEAL
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?+? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                coerce : List(DPoly) -> %
--R coerce : % -> OutputForm              dimension : % -> Integer
--R element? : (DPoly,%) -> Boolean       generators : % -> List(DPoly)
--R groebner : % -> %                     groebner? : % -> Boolean
--R groebnerIdeal : List(DPoly) -> %      hash : % -> SingleInteger
--R ideal : List(DPoly) -> %              in? : (%,%) -> Boolean
--R inRadical? : (DPoly,%) -> Boolean     intersect : List(%) -> %
--R intersect : (%,%) -> %                latex : % -> String
--R leadingIdeal : % -> %                 one? : % -> Boolean
--R quotient : (%,DPoly) -> %             quotient : (%,%) -> %
--R saturate : (%,DPoly) -> %             zero? : % -> Boolean
--R zeroDim? : % -> Boolean               ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R backOldPos : Record(mval: Matrix(F),invmval: Matrix(F),genIdeal: %) -> %
--R dimension : (%,List(VarSet)) -> Integer
--R generalPosition : (%,List(VarSet)) -> Record(mval: Matrix(F),invmval: Matrix(F),genIdeal: %)
--R relationsIdeal : List(DPoly) -> SuchThat(List(Polynomial(F)),List(Equation(Polynomial(F))))
--R saturate : (%,DPoly,List(VarSet)) -> %
--R zeroDim? : (%,List(VarSet)) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— PolynomialIdeals.help —

```
=====================================================================
PolynomialIdeals examples
=====================================================================

See Also:
o )show PolynomialIdeals
```

———-

17.26.1 PolynomialIdeals (IDEAL)



Exports:

backOldPos	coerce	dimension	element?	generalPosition
generators	groebner	groebner?	groebnerIdeal	hash
ideal	in?	inRadical?	intersect	latex
leadingIdeal	one?	quotient	relationsIdeal	saturate
zero?	zeroDim?	?~=?	?**?	?*?
?+?	?=?			

— domain IDEAL PolynomialIdeals —

```
)abbrev domain IDEAL PolynomialIdeals
++ Author: P. Gianni
++ Date Created: summer 1986
++ Date Last Updated: September 1996
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References: GTZ
++ Description:
++ This domain represents polynomial ideals with coefficients in any
++ field and supports the basic ideal operations, including intersection
++ sum and quotient.
++ An ideal is represented by a list of polynomials (the generators of
++ the ideal) and a boolean that is true if the generators are a Groebner
++ basis.
++ The algorithms used are based on Groebner basis computations. The
++ ordering is determined by the datatype of the input polynomials.
++ Users may use refinements of total degree orderings.

PolynomialIdeals(F,Expon,VarSet,DPoly) : C == T
 where
   F         :  Field
   Expon     :  OrderedAbelianMonoidSup
```

```
VarSet    :  OrderedSet
DPoly     :  PolynomialCategory(F,Expon,VarSet)

SUP      ==> SparseUnivariatePolynomial(DPoly)
NNI      ==> NonNegativeInteger
Z        ==> Integer
P        ==> Polynomial F
MF       ==> Matrix(F)
ST       ==> SuchThat(List P, List Equation P)

GenMPos  ==> Record(mval:MF,invmval:MF,genIdeal:Ideal)
Ideal    ==> %

C == SetCategory with

  "*"             :  (Ideal,Ideal)        -> Ideal
    ++ I*J computes the product of the ideal I and J.
  "**"            :   (Ideal,NNI)         -> Ideal
    ++ I**n computes the nth power of the ideal I.
  "+"             :  (Ideal,Ideal)        -> Ideal
    ++ I+J computes the ideal generated by the union of I and J.
  one?            :     Ideal             -> Boolean
    ++ one?(I) tests whether the ideal I is the unit ideal,
    ++ i.e. contains 1.
  zero?           :     Ideal             -> Boolean
    ++ zero?(I) tests whether the ideal I is the zero ideal
  element?        :  (DPoly,Ideal)        -> Boolean
    ++ element?(f,I) tests whether the polynomial f belongs to
    ++ the ideal I.
  in?             :  (Ideal,Ideal)        -> Boolean
    ++ in?(I,J) tests if the ideal I is contained in the ideal J.
  inRadical?      :  (DPoly,Ideal)        -> Boolean
    ++ inRadical?(f,I) tests if some power of the polynomial f
    ++ belongs to the ideal I.
  zeroDim?        : (Ideal,List VarSet)   -> Boolean
    ++ zeroDim?(I,lvar) tests if the ideal I is zero dimensional, i.e.
    ++ all its associated primes are maximal,
    ++ in the ring \spad{F[lvar]}
  zeroDim?        :     Ideal             -> Boolean
    ++ zeroDim?(I) tests if the ideal I is zero dimensional, i.e.
    ++ all its associated primes are maximal,
    ++ in the ring \spad{F[lvar]},
    ++ where lvar are the variables appearing  in I
  intersect       :  (Ideal,Ideal)        -> Ideal
    ++ intersect(I,J) computes the intersection of the ideals I and J.
  intersect       :   List(Ideal)         -> Ideal
    ++ intersect(LI) computes the intersection of the list of ideals LI.
  quotient        :  (Ideal,Ideal)        -> Ideal
    ++ quotient(I,J) computes the quotient of the ideals I and J,
    ++ \spad{(I:J)}.
```

```
quotient        :  (Ideal,DPoly)        -> Ideal
  ++ quotient(I,f) computes the quotient of the ideal I by the principal
  ++ ideal generated by the polynomial f, \spad{(I:(f))}.
groebner        :     Ideal             -> Ideal
  ++ groebner(I) returns a set of generators of I that are a
  ++ Groebner basis for I.
generalPosition :  (Ideal,List VarSet)      -> GenMPos
  ++ generalPosition(I,listvar) perform a random linear
  ++ transformation on the variables in listvar and returns
  ++ the transformed ideal along with the change of basis matrix.
backOldPos      :     GenMPos           -> Ideal
  ++ backOldPos(genPos) takes the result
  ++ produced by generalPosition from PolynomialIdeals
  ++ and performs the inverse transformation, returning the original ideal
  ++ \spad{backOldPos(generalPosition(I,listvar))} = I.
dimension       : (Ideal,List VarSet)   -> Z
  ++ dimension(I,lvar) gives the dimension of the ideal I,
  ++ in the ring \spad{F[lvar]}
dimension       :      Ideal            -> Z
  ++ dimension(I) gives the dimension of the ideal I.
  ++ in the ring \spad{F[lvar]}, where lvar are the variables
  ++ appearing  in I
leadingIdeal    :     Ideal             -> Ideal
  ++ leadingIdeal(I) is the ideal generated by the
  ++ leading terms of the elements of the ideal I.
ideal           :   List DPoly          ->  Ideal
  ++ ideal(polyList) constructs the ideal generated by the list
  ++ of polynomials polyList.
groebnerIdeal       :   List DPoly          ->  Ideal
  ++ groebnerIdeal(polyList) constructs the ideal generated by the list
  ++ of polynomials polyList which are assumed to be a Groebner
  ++ basis.
  ++ Note: this operation avoids a Groebner basis computation.
groebner?           :     Ideal             ->  Boolean
  ++ groebner?(I) tests if the generators of the ideal I are a
  ++ Groebner basis.
generators      :     Ideal             ->  List DPoly
  ++ generators(I) returns a list of generators for the ideal I.
coerce          :   List DPoly          ->  Ideal
  ++ coerce(polyList) converts the list of polynomials polyList
  ++ to an ideal.

saturate        :  (Ideal,DPoly)        -> Ideal
  ++ saturate(I,f) is the saturation of the ideal I
  ++ with respect to the multiplicative
  ++ set generated by the polynomial f.
saturate        :(Ideal,DPoly,List VarSet)  -> Ideal
  ++ saturate(I,f,lvar) is the saturation with respect to the prime
  ++ principal ideal which is generated by f in the polynomial ring
  ++ \spad{F[lvar]}.
```

```
    if VarSet has ConvertibleTo Symbol then
      relationsIdeal  :    List DPoly         -> ST
        ++ relationsIdeal(polyList) returns the ideal of relations among the
        ++ polynomials in polyList.

  T  == add

  ---  Representation ---
    Rep := Record(idl:List DPoly,isGr:Boolean)


              ----  Local Functions  ----

    contractGrob  :    newIdeal          ->  Ideal
    npoly         :     DPoly            ->  newPoly
    oldpoly       :     newPoly          ->  Union(DPoly,"failed")
    leadterm      :   (DPoly,VarSet)     ->  DPoly
    choosel       :   (DPoly,DPoly)      ->  DPoly
    isMonic?      :   (DPoly,VarSet)     ->  Boolean
    randomat      :     List Z           ->  Record(mM:MF,imM:MF)
    monomDim      : (Ideal,List VarSet)  ->  NNI
    variables     :       Ideal          ->  List VarSet
    subset        :     List VarSet      ->  List List VarSet
    makeleast     : (List VarSet,List VarSet)  ->  List VarSet

    newExpon:  OrderedAbelianMonoidSup
    newExpon:= Product(NNI,Expon)
    newPoly := PolynomialRing(F,newExpon)

    import GaloisGroupFactorizer(SparseUnivariatePolynomial Z)
    import GroebnerPackage(F,Expon,VarSet,DPoly)
    import GroebnerPackage(F,newExpon,VarSet,newPoly)

    newIdeal ==> List(newPoly)

    npoly(f:DPoly) : newPoly ==
      f=0$DPoly => 0$newPoly
      monomial(leadingCoefficient f,makeprod(0,degree f))$newPoly +
            npoly(reductum f)

    oldpoly(q:newPoly) : Union(DPoly,"failed") ==
      q=0$newPoly => 0$DPoly
      dq:newExpon:=degree q
      n:NNI:=selectfirst (dq)
      n^=0 => "failed"
      ((g:=oldpoly reductum q) case "failed") => "failed"
      monomial(leadingCoefficient q,selectsecond dq)$DPoly + (g::DPoly)

    leadterm(f:DPoly,lvar:List VarSet) : DPoly ==
      empty?(lf:=variables f)  or lf=lvar => f
```

```
    leadterm(leadingCoefficient univariate(f,lf.first),lvar)

  choosel(f:DPoly,g:DPoly) : DPoly ==
    g=0 => f
    (f1:=f exquo g) case "failed" => f
    choosel(f1::DPoly,g)

  contractGrob(I1:newIdeal) : Ideal ==
    J1:List(newPoly):=groebner(I1)
    while (oldpoly J1.first) case "failed" repeat J1:=J1.rest
    [[(oldpoly f)::DPoly for f in J1],true]

  makeleast(fullVars: List VarSet,leastVars:List VarSet) : List VarSet ==
    n:= # leastVars
    #fullVars < n  => error "wrong vars"
    n=0 => fullVars
    append([vv for vv in fullVars| ^member?(vv,leastVars)],leastVars)

  isMonic?(f:DPoly,x:VarSet) : Boolean ==
    ground? leadingCoefficient univariate(f,x)

  subset(lv : List VarSet) : List List VarSet ==
    #lv =1 => [lv,empty()]
    v:=lv.1
    ll:=subset(rest lv)
    l1:=[concat(v,set) for set in ll]
    concat(l1,ll)

  monomDim(listm:Ideal,lv:List VarSet) : NNI ==
    monvar: List List VarSet := []
    for f in generators listm repeat
      mvset := variables f
      #mvset > 1 => monvar:=concat(mvset,monvar)
      lv:=delete(lv,position(mvset.1,lv))
    empty? lv => 0
    lsubset : List List VarSet := sort((a,b)+->#a > #b ,subset(lv))
    for subs in lsubset repeat
      ldif:List VarSet:= lv
      for mvset in monvar while ldif ^=[] repeat
        ldif:=setDifference(mvset,subs)
      if ^(empty? ldif) then  return #subs
    0

            --    Exported  Functions   ----

              ----  is  I =  J  ?  ----
  (I:Ideal = J:Ideal) == in?(I,J) and in?(J,I)

            ----  check if f is in I  ----
  element?(f:DPoly,I:Ideal) : Boolean ==
```

```
  Id:=(groebner I).idl
  empty? Id => f = 0
  normalForm(f,Id) = 0

       ---- check if I is contained in J  ----
in?(I:Ideal,J:Ideal):Boolean ==
  J:= groebner J
  empty?(I.idl) => true
  "and"/[element?(f,J) for f in I.idl ]


      ----  groebner base for an Ideal  ----
groebner(I:Ideal) : Ideal  ==
  I.isGr =>
    "or"/[^zero? f for f in I.idl] => I
    [empty(),true]
  [groebner I.idl ,true]

      ----  Intersection of two ideals  ----
intersect(I:Ideal,J:Ideal) : Ideal ==
  empty?(Id:=I.idl) => I
  empty?(Jd:=J.idl) => J
  tp:newPoly := monomial(1,makeprod(1,0$Expon))$newPoly
  tp1:newPoly:= tp-1
  contractGrob(concat([tp*npoly f for f in Id],
               [tp1*npoly f for f in Jd]))


      ----   intersection for a list of ideals  ----

intersect(lid:List(Ideal)) : Ideal == "intersect"/[l for l in lid]

         ----  quotient by an element  ----
quotient(I:Ideal,f:DPoly) : Ideal ==
  --[[(g exquo f)::DPoly for g in (intersect(I,[f]::%)).idl ],true]
   import GroebnerInternalPackage(F,Expon,VarSet,DPoly)
   [minGbasis [(g exquo f)::DPoly
            for g in (intersect(I,[f]::%)).idl ],true]

          ----  quotient of two ideals  ----
quotient(I:Ideal,J:Ideal) : Ideal ==
  Jdl := J.idl
  empty?(Jdl) => ideal [1]
  [("intersect"/[quotient(I,f) for f in Jdl ]).idl ,true]


          ----    sum of two ideals  ----
(I:Ideal + J:Ideal) : Ideal == [groebner(concat(I.idl ,J.idl )),true]

          ----   product of two ideals  ----
```

```
(I:Ideal * J:Ideal):Ideal ==
  [groebner([:[f*g for f in I.idl ] for g in J.idl ]),true]

          ----  power of an ideal  ----
(I:Ideal ** n:NNI) : Ideal ==
  n=0 => [[1$DPoly],true]
  (I * (I**(n-1):NNI))

  ----  saturation with respect to the multiplicative set f**n ----
saturate(I:Ideal,f:DPoly) : Ideal ==
  f=0 => error "f is zero"
  tp:newPoly := (monomial(1,makeprod(1,0$Expon))$newPoly * npoly f)-1
  contractGrob(concat(tp,[npoly g for g in I.idl ]))

----  saturation with respect to a prime principal ideal in lvar ---
saturate(I:Ideal,f:DPoly,lvar:List(VarSet)) : Ideal ==
  Id := I.idl
  fullVars := "setUnion"/[variables g for g in Id]
  newVars:=makeleast(fullVars,lvar)
  subVars := [monomial(1,vv,1) for vv in newVars]
  J:List DPoly:=groebner([eval(g,fullVars,subVars) for g in Id])
  ltJ:=[leadterm(g,lvar) for g in J]
  s:DPoly:=_*/[choosel(ltg,f) for ltg in ltJ]
  fullPol:=[monomial(1,vv,1) for vv in fullVars]
  [[eval(g,newVars,fullPol) for g in (saturate(J::%,s)).idl],true]

       ----  is the ideal zero dimensional?  ----
       ----      in the ring F[lvar]?        ----
zeroDim?(I:Ideal,lvar:List VarSet) : Boolean ==
  J:=(groebner I).idl
  empty? J => false
  J = [1] => false
  n:NNI := # lvar
  #J < n => false
  for f in J while ^empty?(lvar) repeat
    x:=(mainVariable f)::VarSet
    if isMonic?(f,x) then lvar:=delete(lvar,position(x,lvar))
  empty?(lvar)

       ----  is the ideal zero dimensional?  ----
zeroDim?(I:Ideal):Boolean == zeroDim?(I,"setUnion"/[variables g for g in I.idl])

          ----  test if f is in the radical of I  ----
inRadical?(f:DPoly,I:Ideal) : Boolean ==
  f=0$DPoly => true
  tp:newPoly :=(monomial(1,makeprod(1,0$Expon))$newPoly * npoly f)-1
  Id:=I.idl
  normalForm(1$newPoly,groebner concat(tp,[npoly g for g in Id])) = 0

         ----   dimension of an ideal  ----
```

```
        ----    in the ring F[lvar]   ----
dimension(I:Ideal,lvar:List VarSet) : Z ==
  I:=groebner I
  empty?(I.idl) => # lvar
  element?(1,I) => -1
  truelist:="setUnion"/[variables f for f in I.idl]
  "or"/[^member?(vv,lvar) for vv in truelist] => error "wrong variables"
  truelist:=setDifference(lvar,setDifference(lvar,truelist))
  ed:Z:=#lvar - #truelist
  leadid:=leadingIdeal(I)
  n1:Z:=monomDim(leadid,truelist)::Z
  ed+n1

dimension(I:Ideal) : Z == dimension(I,"setUnion"/[variables g for g in I.idl])

-- leading term ideal --
leadingIdeal(I : Ideal) : Ideal ==
  Idl:= (groebner I).idl
  [[(f-reductum f) for f in Idl],true]

         ---- ideal of relations among the fi  ----
if VarSet has ConvertibleTo Symbol then

  monompol(df:List NNI,lcf:F,lv:List VarSet) : P ==
    g:P:=lcf::P
    for dd in df for v in lv repeat
      g:= monomial(g,convert v,dd)
    g

  relationsIdeal(listf : List DPoly): ST ==
    empty? listf  => [empty(),empty()]$ST
    nf:=#listf
    lvint := "setUnion"/[variables g for g in listf]
    vl: List Symbol := [convert vv for vv in lvint]
    nvar:List Symbol:=[new() for i in 1..nf]
    VarSet1:=OrderedVariableList(concat(vl,nvar))
    lv1:=[variable(vv)$VarSet1::VarSet1 for vv in nvar]
    DirP:=DirectProduct(nf,NNI)
    nExponent:=Product(Expon,DirP)
    nPoly := PolynomialRing(F,nExponent)
    gp:=GroebnerPackage(F,nExponent,VarSet1,nPoly)
    lf:List nPoly :=[]
    lp:List P:=[]
    for f in listf for i in 1..  repeat
      vec2:Vector(NNI):=new(nf,0$NNI)
      vec2.i:=1
      g:nPoly:=0$nPoly
      pol:=0$P
      while f^=0 repeat
        df:=degree(f-reductum f,lvint)
```

```
          lcf:=leadingCoefficient f
          pol:=pol+monompol(df,lcf,lvint)
          g:=g+monomial(lcf,makeprod(degree f,0))$nPoly
          f:=reductum f
        lp:=concat(pol,lp)
        lf:=concat(monomial(1,makeprod(0,directProduct vec2))-g,lf)
      npol:List P :=[v::P for v in nvar]
      leq : List Equation P :=
            [p = pol for p in npol for pol in reverse lp ]
      lf:=(groebner lf)$gp
      while lf^=[] repeat
        q:=lf.first
        dq:nExponent:=degree q
        n:=selectfirst (dq)
        if n=0 then leave "done"
        lf:=lf.rest
      solsn:List P:=[]
      for q in lf repeat
        g:Polynomial F :=0
        while q^=0 repeat
          dq:=degree q
          lcq:=leadingCoefficient q
          q:=reductum q
          vdq:=(selectsecond dq):Vector NNI
          g:=g+ lcq*
             _*/[p**vdq.j for p in npol for j in 1..]
        solsn:=concat(g,solsn)
      [solsn,leq]$ST

  coerce(Id:List DPoly) : Ideal == [Id,false]

  coerce(I:Ideal) : OutputForm ==
    Idl := I.idl
    empty? Idl => [0$DPoly] :: OutputForm
    Idl :: OutputForm

  ideal(Id:List DPoly) :Ideal  ==  [[f for f in Id|f^=0],false]

  groebnerIdeal(Id:List DPoly) : Ideal == [Id,true]

  generators(I:Ideal) : List DPoly  == I.idl

  groebner?(I:Ideal) : Boolean  ==  I.isGr

  one?(I:Ideal) : Boolean == element?(1, I)

  zero?(I:Ideal) : Boolean == empty? (groebner I).idl
```

———-

— **IDEAL.dotabb** —

```
"IDEAL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IDEAL"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"IDEAL" -> "ALIST"
```

———-

17.27 domain PR PolynomialRing

— **PolynomialRing.input** —

```
)set break resume
)sys rm -f PolynomialRing.output
)spool PolynomialRing.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PolynomialRing
--R
--R PolynomialRing(R: Ring,E: OrderedAbelianMonoid)  is a domain constructor
--R Abbreviation for PolynomialRing is PR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PR
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficient : (%,E) -> R
--R coefficients : % -> List(R)           coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> E                       ground : % -> R
--R ground? : % -> Boolean                hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> R
--R leadingMonomial : % -> %              map : ((R -> R),%) -> %
--R mapExponents : ((E -> E),%) -> %      minimumDegree : % -> E
--R monomial : (R,E) -> %                 monomial? : % -> Boolean
--R one? : % -> Boolean                   pomopo! : (%,R,E,%) -> %
--R recip : % -> Union(%,"failed")        reductum : % -> %
```

```
--R retract : % -> R                      sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : % -> % if R has INTDOM
--R content : % -> R if R has GCDDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R fmecg : (%,E,R,%) -> % if E has CABMON and R has INTDOM
--R numberOfMonomials : % -> NonNegativeInteger
--R primitivePart : % -> % if R has GCDDOM
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— PolynomialRing.help —

```
=====================================================================
PolynomialRing examples
=====================================================================

See Also:
o )show PolynomialRing
```

———-

17.27.1 PolynomialRing (PR)



See

⇒ "FreeModule" (FM) 7.30.1 on page 983
⇒ "SparseUnivariatePolynomial" (SUP) 20.18.1 on page 2434
⇒ "UnivariatePolynomial" (UP) 22.4.1 on page 2794

Exports:

0	1	associates?	binomThmExpt	characteristic
charthRoot	coerce	coefficient	coefficients	content
degree	exquo	exquo	fmecg	ground
ground?	hash	latex	leadingCoefficient	leadingMonomial
map	mapExponents	minimumDegree	monomial	monomial?
numberOfMonomials	one?	pomopo!	primitivePart	recip
reductum	retract	retractIfCan	sample	subtractIfCan
unit?	unitCanonical	unitNormal	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?	?/?		

— domain PR PolynomialRing —

```
)abbrev domain PR PolynomialRing
++ Author: Dave Barton, James Davenport, Barry Trager
++ Date Created:
++ Date Last Updated: 14.08.2000. Improved exponentiation [MMM/TTT]
++ Basic Functions: Ring, degree, coefficient, monomial, reductum
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain represents generalized polynomials with coefficients
++ (from a not necessarily commutative ring), and terms
++ indexed by their exponents (from an arbitrary ordered abelian monoid).
++ This type is used, for example,
++ by the \spadtype{DistributedMultivariatePolynomial} domain where
```

```
++ the exponent domain is a direct product of non negative integers.

PolynomialRing(R:Ring,E:OrderedAbelianMonoid): T == C
 where
  T == FiniteAbelianMonoidRing(R,E) with
    --assertions
       if R has IntegralDomain and E has CancellationAbelianMonoid then
            fmecg: (%,E,R,%) -> %
            ++ fmecg(p1,e,r,p2) finds x : p1 - r * x**e * p2
       if R has canonicalUnitNormal then canonicalUnitNormal
          ++ canonicalUnitNormal guarantees that the function
          ++ unitCanonical returns the same representative for all
          ++ associates of any particular element.

  C == FreeModule(R,E) add
    --representations
       Term:=  Record(k:E,c:R)
       Rep:=  List Term


    --declarations
       x,y,p,p1,p2: %
       n: Integer
       nn: NonNegativeInteger
       np: PositiveInteger
       e: E
       r: R
    --local operations
       1  == [[0$E,1$R]]
       characteristic  == characteristic$R
       numberOfMonomials x  == (# x)$Rep
       degree p == if null p then 0 else p.first.k
       minimumDegree p == if null p then 0 else (last p).k
       leadingCoefficient p == if null p then 0$R else p.first.c
       leadingMonomial p == if null p then 0 else [p.first]
       reductum p == if null p then p else p.rest
       retractIfCan(p:%):Union(R,"failed") ==
         null p => 0$R
         not null p.rest => "failed"
         zero?(p.first.k) => p.first.c
         "failed"
       coefficient(p,e)  ==
          for tm in p repeat
            tm.k=e => return tm.c
            tm.k < e => return 0$R
          0$R
       recip(p) ==
           null p => "failed"
           p.first.k > 0$E => "failed"
           (u:=recip(p.first.c)) case "failed" => "failed"
```

```
    (u::R)::%

coerce(r) == if zero? r then 0$% else [[0$E,r]]
coerce(n) == (n::R)::%

ground?(p): Boolean == empty? p or (empty? rest p and zero? degree p)

qsetrest!: (Rep, Rep) -> Rep
qsetrest!(l: Rep, e: Rep): Rep == RPLACD(l, e)$Lisp

times!: (R,    %) -> %
times:  (R, E, %) -> %

entireRing? := R has EntireRing

times!(r: R, x: %): % ==
  res, endcell, newend, xx: Rep
  if entireRing? then
         for tx in x repeat tx.c := r*tx.c
  else
         xx := x
         res := empty()
         while not empty? xx repeat
                 tx := first xx
                 tx.c := r * tx.c
                 if zero? tx.c then
                         xx := rest xx
                 else
                         newend := xx
                         xx := rest xx
                         if empty? res then
                                 res := newend
                                 endcell := res
                         else
                                 qsetrest!(endcell, newend)
                                 endcell := newend
         res;

 --- term * polynomial
termTimes: (R, E, Term) -> Term
termTimes(r: R, e: E, tx:Term): Term == [e+tx.k, r*tx.c]
times(tco: R, tex: E, rx: %): % ==
 if entireRing? then
         map(x1+->termTimes(tco, tex, x1), rx::Rep)
 else
         [[tex + tx.k, r] for tx in rx::Rep | not zero? (r := tco * tx.c)]



-- local addm!
```

```
addm!: (Rep, R, E, Rep) -> Rep
 -- p1 + coef*x^E * p2
 -- 'spare' (commented out) is for storage efficiency (not so good for
 -- performance though.
addm!(p1:Rep, coef:R, exp: E, p2:Rep): Rep ==
        --local res, newend, last: Rep
        res, newcell, endcell: Rep
        spare: List Rep
        res     := empty()
        endcell := empty()
        --spare   := empty()
        while not empty? p1 and not empty? p2 repeat
                tx := first p1
                ty := first p2
                exy := exp + ty.k
                newcell := empty();
                if tx.k = exy then
                        newcoef := tx.c + coef * ty.c
                        if not zero? newcoef then
                                tx.c    := newcoef
                                newcell := p1
                        --else
                        --        spare   := cons(p1, spare)
                        p1 := rest p1
                        p2 := rest p2
                else if tx.k > exy then
                        newcell := p1
                        p1      := rest p1
                else
                        newcoef := coef * ty.c
                        if not entireRing? and zero? newcoef then
                                newcell := empty()
                        --else if empty? spare then
                        --        ttt := [exy, newcoef]
                        --        newcell := cons(ttt, empty())
                        --else
                        --        newcell := first spare
                        --        spare   := rest spare
                        --        ttt := first newcell
                        --        ttt.k := exy
                        --        ttt.c := newcoef
                        else
                                ttt := [exy, newcoef]
                                newcell := cons(ttt, empty())
                        p2 := rest p2
                if not empty? newcell then
                        if empty? res then
                                res := newcell
                                endcell := res
                        else
```

```
                                    qsetrest!(endcell, newcell)
                                    endcell := newcell
            if not empty? p1 then  -- then end is const * p1
                    newcell := p1
            else  -- then end is (coef, exp) * p2
                    newcell := times(coef, exp, p2)
            empty? res => newcell
            qsetrest!(endcell, newcell)
            res
    pomopo! (p1, r, e, p2) ==  addm!(p1, r, e, p2)
    p1 * p2 ==
            xx := p1::Rep
            empty? xx => p1
            yy := p2::Rep
            empty? yy => p2
            zero? first(xx).k => first(xx).c * p2
            zero? first(yy).k => p1 * first(yy).c
            --if #xx > #yy then
            --        (xx, yy) := (yy, xx)
            --        (p1, p2) := (p2, p1)
            xx := reverse xx
            res : Rep := empty()
            for tx in xx repeat res:=addm!(res,tx.c,tx.k,yy)
            res

--      if R has EntireRing then
--          p1 * p2  ==
--             null p1 => 0
--             null p2 => 0
--             zero?(p1.first.k) => p1.first.c * p2
--             one? p2 => p1
--             +/[[[t1.k+t2.k,t1.c*t2.c]$Term for t2 in p2]
--                    for t1 in reverse(p1)]
--                    -- This 'reverse' is an efficiency improvement:
--                    -- reduces both time and space [Abbott/Bradford/Davenport]
--         else
--          p1 * p2  ==
--             null p1 => 0
--             null p2 => 0
--             zero?(p1.first.k) => p1.first.c * p2
--             one? p2 => p1
--             +/[[[t1.k+t2.k,r]$Term for t2 in p2 | (r:=t1.c*t2.c) ^= 0]
--                  for t1 in reverse(p1)]
--                   -- This 'reverse' is an efficiency improvement:
--                   -- reduces both time and space [Abbott/Bradford/Davenport]
    if R has CommutativeRing  then
      p ** np == p ** (np pretend NonNegativeInteger)
      p ^ np  == p ** (np pretend NonNegativeInteger)
      p ^ nn  == p ** nn
```

```
        p ** nn  ==
           null p => 0
           zero? nn => 1
--           one? nn => p
           (nn = 1) => p
           empty? p.rest =>
             zero?(cc:=p.first.c ** nn) => 0
             [[nn * p.first.k, cc]]
           binomThmExpt([p.first], p.rest, nn)

      if R has Field then
        unitNormal(p) ==
           null p or (lcf:R:=p.first.c) = 1 => [1,p,1]
           a := inv lcf
           [lcf::%, [[p.first.k,1],:(a * p.rest)], a::%]
        unitCanonical(p) ==
           null p or (lcf:R:=p.first.c) = 1 => p
           a := inv lcf
           [[p.first.k,1],:(a * p.rest)]
      else if R has IntegralDomain then
        unitNormal(p) ==
           null p or p.first.c = 1 => [1,p,1]
           (u,cf,a):=unitNormal(p.first.c)
           [u::%, [[p.first.k,cf],:(a * p.rest)], a::%]
        unitCanonical(p) ==
           null p or p.first.c = 1 => p
           (u,cf,a):=unitNormal(p.first.c)
           [[p.first.k,cf],:(a * p.rest)]
      if R has IntegralDomain then
        associates?(p1,p2) ==
           null p1 => null p2
           null p2 => false
           p1.first.k = p2.first.k and
             associates?(p1.first.c,p2.first.c) and
              ((p2.first.c exquo p1.first.c)::R * p1.rest = p2.rest)
        p exquo r  ==
          [(if (a:= tm.c exquo r) case "failed"
              then return "failed" else [tm.k,a])
                 for tm in p] :: Union(%,"failed")
        if E has CancellationAbelianMonoid then
          fmecg(p1:%,e:E,r:R,p2:%):% ==       -- p1 - r * X**e * p2
            rout:%:= []
            r:= - r
            for tm in p2 repeat
               e2:= e + tm.k
               c2:= r * tm.c
               c2 = 0 => "next term"
               while not null p1 and p1.first.k > e2 repeat
                 (rout:=[p1.first,:rout]; p1:=p1.rest)  --use PUSH and POP?
```

```
              null p1 or p1.first.k < e2 => rout:=[[e2,c2],:rout]
              if (u:=p1.first.c + c2) ^= 0 then rout:=[[e2, u],:rout]
              p1:=p1.rest
           NRECONC(rout,p1)$Lisp
        if R has approximate then
          p1 exquo p2  ==
            null p2 => error "Division by 0"
            p2 = 1 => p1
            p1=p2 => 1
          --(p1.lastElt.c exquo p2.lastElt.c) case "failed" => "failed"
            rout:= []@List(Term)
            while not null p1 repeat
               (a:= p1.first.c exquo p2.first.c)
               a case "failed" => return "failed"
               ee:= subtractIfCan(p1.first.k, p2.first.k)
               ee case "failed" => return "failed"
               p1:= fmecg(p1.rest, ee, a, p2.rest)
               rout:= [[ee,a], :rout]
            null p1 => reverse(rout)::%    -- nreverse?
            "failed"
        else -- R not approximate
          p1 exquo p2  ==
            null p2 => error "Division by 0"
            p2 = 1 => p1
          --(p1.lastElt.c exquo p2.lastElt.c) case "failed" => "failed"
            rout:= []@List(Term)
            while not null p1 repeat
               (a:= p1.first.c exquo p2.first.c)
               a case "failed" => return "failed"
               ee:= subtractIfCan(p1.first.k, p2.first.k)
               ee case "failed" => return "failed"
               p1:= fmecg(p1.rest, ee, a, p2.rest)
               rout:= [[ee,a], :rout]
            null p1 => reverse(rout)::%    -- nreverse?
            "failed"
      if R has Field then
         x/r == inv(r)*x
```

———-

— PR.dotabb —

```
"PR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PR"]
"FAMR" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAMR"]
"PR" -> "FAMR"
```

———-

17.28 domain PI PositiveInteger

— PositiveInteger.input —

```
)set break resume
)sys rm -f PositiveInteger.output
)spool PositiveInteger.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PositiveInteger
--R PositiveInteger  is a domain constructor
--R Abbreviation for PositiveInteger is PI
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PI
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?<? : (%,%) -> Boolean                ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean                ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean               1 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : % -> OutputForm
--R gcd : (%,%) -> %                      hash : % -> SingleInteger
--R latex : % -> String                   max : (%,%) -> %
--R min : (%,%) -> %                      one? : % -> Boolean
--R recip : % -> Union(%,"failed")        sample : () -> %
--R ?~=? : (%,%) -> Boolean
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— PositiveInteger.help —

```
==========================================================================
PositiveInteger examples
==========================================================================

See Also:
o )show PositiveInteger
```

———-

17.28.1 PositiveInteger (PI)



See

⇒ “Integer” (INT) 10.30.1 on page 1329
⇒ “NonNegativeInteger” (NNI) 15.5.1 on page 1706
⇒ “RomanNumeral” (ROMAN) 19.12.1 on page 2292

Exports:

1	coerce	gcd	hash	latex
max	min	one?	recip	sample
?^?	?~=?	?**?	?*?	?+?
?<?	?<=?	?=?	?>?	?>=?

— domain PI PositiveInteger —

```
)abbrev domain PI PositiveInteger
++ Author: Mark Botch
++ Date Created:
++ Change History:
++ Basic Operations:
++ Related Constructors:
++ Keywords: positive integer
++ Description:
++ \spadtype{PositiveInteger} provides functions for
++ positive integers.

PositiveInteger: Join(AbelianSemiGroup,OrderedSet,Monoid) with
    gcd: (%,%) -> %
      ++ gcd(a,b) computes the greatest common divisor of two
      ++ positive integers \spad{a} and b.
    commutative("*")
      ++ commutative("*") means multiplication is commutative : x*y = y*x
```

```
 == SubDomain(NonNegativeInteger,#1 > 0) add
     x:%
     y:%
```

———-

— **PI.dotabb** —

```
"PI" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PI",shape=ellipse]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"SGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=SGROUP"]
"PI" -> "ORDSET"
"PI" -> "SGROUP"
```

———-

17.29 domain PF PrimeField

— **PrimeField.input** —

```
)set break resume
)sys rm -f PrimeField.output
)spool PrimeField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PrimeField
--R
--R PrimeField(p: PositiveInteger)  is a domain constructor
--R Abbreviation for PrimeField is PF
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PF
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,%) -> %                      ?=? : (%,%) -> Boolean
--R D : % -> %                            D : (%,NonNegativeInteger) -> %
--R 1 : () -> %                           0 : () -> %
```

```
--R ?^? : (%,Integer) -> %
--R algebraic? : % -> Boolean
--R basis : () -> Vector(%)
--R coerce : Fraction(Integer) -> %
--R coerce : Integer -> %
--R convert : % -> Integer
--R createPrimitiveElement : () -> %
--R differentiate : % -> %
--R factor : % -> Factored(%)
--R gcd : (%,%) -> %
--R inGroundField? : % -> Boolean
--R init : () -> %
--R latex : % -> String
--R lcm : (%,%) -> %
--R norm : % -> %
--R order : % -> PositiveInteger
--R primeFrobenius : % -> %
--R primitiveElement : () -> %
--R random : () -> %
--R ?rem? : (%,%) -> %
--R retract : % -> %
--R size : () -> NonNegativeInteger
--R squareFree : % -> Factored(%)
--R trace : % -> %
--R unit? : % -> Boolean
--R zero? : % -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R Frobenius : % -> % if $ has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if $ has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R basis : PositiveInteger -> Vector(%)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed")
--R conditionP : Matrix(%) -> Union(Vector(%),"failed")
--R coordinates : Vector(%) -> Matrix(%)
--R createNormalElement : () -> % if $ has FINITE
--R definingPolynomial : () -> SparseUnivariatePolynomial(%)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> %
--R discreteLog : % -> NonNegativeInteger
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed")
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R extensionDegree : () -> PositiveInteger
--R ?^? : (%,PositiveInteger) -> %
--R associates? : (%,%) -> Boolean
--R charthRoot : % -> %
--R coerce : % -> %
--R coerce : % -> OutputForm
--R coordinates : % -> Vector(%)
--R degree : % -> PositiveInteger
--R dimension : () -> CardinalNumber
--R gcd : List(%) -> %
--R hash : % -> SingleInteger
--R index : PositiveInteger -> %
--R inv : % -> %
--R lcm : List(%) -> %
--R lookup : % -> PositiveInteger
--R one? : % -> Boolean
--R prime? : % -> Boolean
--R primitive? : % -> Boolean
--R ?quo? : (%,%) -> %
--R recip : % -> Union(%,"failed")
--R represents : Vector(%) -> %
--R sample : () -> %
--R sizeLess? : (%,%) -> Boolean
--R squareFreePart : % -> %
--R transcendent? : % -> Boolean
--R unitCanonical : % -> %
--R ?~=? : (%,%) -> Boolean
```

```
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer))
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R generator : () -> % if $ has FINITE
--R linearAssociatedExp : (%,SparseUnivariatePolynomial(%)) -> % if $ has FINITE
--R linearAssociatedLog : % -> SparseUnivariatePolynomial(%) if $ has FINITE
--R linearAssociatedLog : (%,%) -> Union(SparseUnivariatePolynomial(%),"failed") if $ has FINITE
--R linearAssociatedOrder : % -> SparseUnivariatePolynomial(%) if $ has FINITE
--R minimalPolynomial : % -> SparseUnivariatePolynomial(%)
--R minimalPolynomial : (%,PositiveInteger) -> SparseUnivariatePolynomial(%) if $ has FINITE
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R nextItem : % -> Union(%,"failed")
--R norm : (%,PositiveInteger) -> % if $ has FINITE
--R normal? : % -> Boolean if $ has FINITE
--R normalElement : () -> % if $ has FINITE
--R order : % -> OnePointCompletion(PositiveInteger)
--R primeFrobenius : (%,NonNegativeInteger) -> %
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R representationType : () -> Union("prime",polynomial,normal,cyclic)
--R retractIfCan : % -> Union(%,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger)
--R trace : (%,PositiveInteger) -> % if $ has FINITE
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— PrimeField.help —

```
=====================================================================
PrimeField examples
=====================================================================

See Also:
o )show PrimeField
```

———-

17.29.1 PrimeField (PF)



See

⇒ “InnerPrimeField” (IPF) 10.25.1 on page 1271

Exports:

0	1	algebraic?
associates?	basis	characteristic
charthRoot	conditionP	coordinates
coerce	convert	coordinates
createPrimitiveElement	createNormalElement	D
definingPolynomial	degree	differentiate
dimension	discreteLog	discreteLog
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	extensionDegree
factor	factorsOfCyclicGroupSize	Frobenius
gcd	gcdPolynomial	generator
hash	inGroundField?	index
init	inv	latex
lcm	linearAssociatedExp	linearAssociatedLog
linearAssociatedOrder	lookup	minimalPolynomial
multiEuclidean	nextItem	norm
normal?	normalElement	one?
order	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	recip	representationType
represents	retract	retractIfCan
sample	size	sizeLess?
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	zero?	?*?
?**?	?+?	?-?
-?	?/?	?=?
?^?	?~=?	?quo?
?rem?		

— domain PF PrimeField —

```
)abbrev domain PF PrimeField
++ Authors: N.N.,
++ Date Created: November 1990, 26.03.1991
++ Date Last Updated: 31 March 1991
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: prime characteristic, prime field, finite field
++ References:
++  R.Lidl, H.Niederreiter: Finite Field, Encycoldia of Mathematics and
++  Its Applications, Vol. 20, Cambridge Univ. Press, 1983, ISBN 0 521 30240 4
++ Description:
++ PrimeField(p) implements the field with p elements if p is a prime number.
```

```
++ Error: if p is not prime.
++ Note: this domain does not check that argument is a prime.

PrimeField(p:PositiveInteger): Exp == Impl where
  Exp ==> Join(FiniteFieldCategory,FiniteAlgebraicExtensionField($),_
    ConvertibleTo(Integer))
  Impl ==>  InnerPrimeField(p) add
    if not prime?(p)$IntegerPrimesPackage(Integer) then
      error "Argument to prime field must be a prime"
```

———-

— PF.dotabb —

```
"PF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PF"]
"FAXF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAXF"]
"PF" -> "FAXF"
```

———-

17.30 domain PRIMARR PrimitiveArray

— PrimitiveArray.input —

```
)set break resume
)sys rm -f PrimitiveArray.output
)spool PrimitiveArray.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PrimitiveArray
--R
--R PrimitiveArray(S: Type)  is a domain constructor
--R Abbreviation for PrimitiveArray is PRIMARR
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PRIMARR
--R
--R------------------------------ Operations --------------------------------
--R concat : List(%) -> %                concat : (%,%) -> %
--R concat : (S,%) -> %                  concat : (%,S) -> %
--R construct : List(S) -> %             copy : % -> %
--R delete : (%,Integer) -> %            ?.? : (%,Integer) -> S
```

```
--R elt : (%,Integer,S) -> S              empty : () -> %
--R empty? : % -> Boolean                 entries : % -> List(S)
--R eq? : (%,%) -> Boolean                index? : (Integer,%) -> Boolean
--R indices : % -> List(Integer)          insert : (%,%,Integer) -> %
--R insert : (S,%,Integer) -> %           map : (((S,S) -> S),%,%) -> %
--R map : ((S -> S),%) -> %               new : (NonNegativeInteger,S) -> %
--R qelt : (%,Integer) -> S               reverse : % -> %
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if S has ORDSET
--R ?<=? : (%,%) -> Boolean if S has ORDSET
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has ORDSET
--R ?>=? : (%,%) -> Boolean if S has ORDSET
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R convert : % -> InputForm if S has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R delete : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R find : ((S -> Boolean),%) -> Union(S,"failed")
--R first : % -> S if Integer has ORDSET
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R merge : (%,%) -> % if S has ORDSET
--R merge : (((S,S) -> Boolean),%,%) -> %
--R min : (%,%) -> % if S has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R position : (S,%,Integer) -> Integer if S has SETCAT
--R position : (S,%) -> Integer if S has SETCAT
--R position : ((S -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R reduce : (((S,S) -> S),%) -> S if $ has finiteAggregate
```

```
--R reduce : (((S,S) -> S),%,S) -> S if $ has finiteAggregate
--R reduce : (((S,S) -> S),%,S,S) -> S if $ has finiteAggregate and S has SETCAT
--R remove : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (S,%) -> % if $ has finiteAggregate and S has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and S has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((S -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),S) -> S if $ has shallowlyMutable
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if S has ORDSET
--R sort : (((S,S) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and S has ORDSET
--R sort! : (((S,S) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if S has ORDSET
--R sorted? : (((S,S) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— PrimitiveArray.help —

```
=====================================================================
PrimitiveArray examples
=====================================================================

See Also:
o )show PrimitiveArray
```

———-

17.30.1 PrimitiveArray (PRIMARR)



See

⇒ "Tuple" (TUPLE) 21.12.1 on page 2721
⇒ "IndexedFlexibleArray" (IFARRAY) 10.10.1 on page 1191
⇒ "FlexibleArray" (FARRAY) 7.14.1 on page 856
⇒ "IndexedOneDimensionalArray" (IARRAY1) 10.13.1 on page 1212
⇒ "OneDimensionalArray" (ARRAY1) 16.3.1 on page 1740

Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	delete	entry?
elt	empty	empty?	entries	eq?
eval	every?	fill!	find	first
hash	index?	indices	insert	insert
latex	less?	map	map!	max
maxIndex	member?	members	merge	min
minIndex	more?	new	parts	position
qelt	qsetelt!	reduce	remove	removeDuplicates
reverse	reverse!	sample	select	setelt
size?	sort	sort!	sorted?	swap!
#?	?.?	?~=?	?<?	?<=?
?=?	?>?	?>=?		

— domain PRIMARR PrimitiveArray —

```
)abbrev domain PRIMARR PrimitiveArray
++ Author: Mark Botch
++ Description:
++ This provides a fast array type with no bound checking on elt's.
++ Minimum index is 0 in this type, cannot be changed

PrimitiveArray(S:Type): OneDimensionalArrayAggregate S == add
   Qmax ==> QVMAXINDEX$Lisp
   Qsize ==> QVSIZE$Lisp
--   Qelt ==> QVELT$Lisp
--   Qsetelt ==> QSETVELT$Lisp
```

```
   Qelt ==> ELT$Lisp
   Qsetelt ==> SETELT$Lisp
   Qnew ==> MAKE_-ARRAY$Lisp

   #x                          == Qsize x
   minIndex x                  == 0
   empty()                     == Qnew(0$Lisp)
   new(n, x)                   == fill_!(Qnew n, x)
   qelt(x, i)                  == Qelt(x, i)
   elt(x:%, i:Integer)         == Qelt(x, i)
   qsetelt_!(x, i, s)          == Qsetelt(x, i, s)
   setelt(x:%, i:Integer, s:S) == Qsetelt(x, i, s)
   fill_!(x, s)       == (for i in 0..Qmax x repeat Qsetelt(x, i, s); x)
```

———-

— PRIMARR.dotabb —

```
"PRIMARR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PRIMARR",
          shape=ellipse]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"PRIMARR" -> "A1AGG"
```

———-

17.31 domain PRODUCT Product

— Product.input —

```
)set break resume
)sys rm -f Product.output
)spool Product.output
)set message test on
)set message auto off
)clear all

--S 1 of 6
f:=(x:INT):INT +-> 3*x
--R
--R
--R   (1)  theMap(Closure)
--R                                                  Type: (Integer -> Integer)
--E 1
```

```
--S 2 of 6
f(3)
--R
--R
--R   (2)  9
--R                                                    Type: PositiveInteger
--E 2

--S 3 of 6
g:=(x:INT):INT +-> x^3
--R
--R
--R   (3)  theMap(Closure)
--R                                                 Type: (Integer -> Integer)
--E 3

--S 4 of 6
g(3)
--R
--R
--R   (4)  27
--R                                                    Type: PositiveInteger
--E 4

--S 5 of 6
h(x:INT):Product(INT,INT) == makeprod(f x, g x)
--R
--R   Function declaration h : Integer -> Product(Integer,Integer) has
--R      been added to workspace.
--R                                                                  Type: Void
--E 5

--S 6 of 6
h(3)
--R
--R   Compiling function h with type Integer -> Product(Integer,Integer)
--R
--R   (6)  (9,27)
--R                                           Type: Product(Integer,Integer)
--E 6

)spool
)lisp (bye)
```

———-

— Product.help —

```
====================================================================
```

```
Product examples
================================================================

The direct product of two functions over the same domain is
another function over that domain whose co-domain is the product
of their co-domains.

So we can define two functions, f and g, that go from INT -> INT

   f:=(x:INT):INT +-> 3*x
   g:=(x:INT):INT +-> x^3

so
    f(3) is 9
    g(3) is 27


and we can construct the direct product of those functions h=f,g

   h(x:INT):Product(INT,INT) == makeprod(f x, g x)

so
   h(3) is (9,27)

See Also:
o )show Product
```

17.31.1 Product (PRODUCT)



Exports:

0	1	coerce	commutator	conjugate
hash	index	inv	latex	lookup
makeprod	max	min	one?	random
recip	sample	selectfirst	selectsecond	size
subtractIfCan	sup	zero?	?=?	?~=?
?*?	?**?	?+?	-?	?-?
?/?	?<?	?<=?	?>?	?>=?
?^?				

— domain PRODUCT Product —

```
)abbrev domain PRODUCT Product
++ Author: Mark Botch
++ Description:
++ This domain implements cartesian product

Product (A:SetCategory,B:SetCategory) : C == T
 where
  C == SetCategory  with
       if A has Finite and B has Finite then Finite
       if A has Monoid and B has Monoid then Monoid
       if A has AbelianMonoid and B has AbelianMonoid then AbelianMonoid
       if A has CancellationAbelianMonoid and
          B has CancellationAbelianMonoid then CancellationAbelianMonoid
       if A has Group  and B has Group  then  Group
       if A has AbelianGroup and B has AbelianGroup then  AbelianGroup
       if A has OrderedAbelianMonoidSup and B has OrderedAbelianMonoidSup
                                              then OrderedAbelianMonoidSup
       if A has OrderedSet and B has OrderedSet then  OrderedSet

       makeprod     : (A,B) -> %
        ++ makeprod(a,b) computes the product of two functions
        ++
        ++X f:=(x:INT):INT +-> 3*x
        ++X g:=(x:INT):INT +-> x^3
        ++X h(x:INT):Product(INT,INT) == makeprod(f x, g x)
        ++X h(3)
       selectfirst  :   %   -> A
        ++ selectfirst(x) is not documented
       selectsecond :   %   -> B
        ++ selectsecond(x) is not documented

  T == add

    --representations
       Rep := Record(acomp:A,bcomp:B)

    --declarations
       x,y: %
```

```
      i: NonNegativeInteger
      p: NonNegativeInteger
      a: A
      b: B
      d: Integer

   --define
      coerce(x):OutputForm == paren [(x.acomp)::OutputForm,
                                     (x.bcomp)::OutputForm]
      x=y ==
          x.acomp = y.acomp => x.bcomp = y.bcomp
          false
      makeprod(a:A,b:B) :%   == [a,b]

      selectfirst(x:%) : A   == x.acomp

      selectsecond (x:%) : B == x.bcomp

      if A has Monoid and B has Monoid then
         1 == [1$A,1$B]
         x * y == [x.acomp * y.acomp,x.bcomp * y.bcomp]
         x ** p == [x.acomp ** p ,x.bcomp ** p]

      if A has Finite and B has Finite then
         size == size$A () * size$B ()

      if A has Group and B has Group then
         inv(x) == [inv(x.acomp),inv(x.bcomp)]

      if A has AbelianMonoid and B has AbelianMonoid then
         0 == [0$A,0$B]

         x + y == [x.acomp + y.acomp,x.bcomp + y.bcomp]

         c:NonNegativeInteger * x == [c * x.acomp,c*x.bcomp]

      if A has CancellationAbelianMonoid and
         B has CancellationAbelianMonoid then
           subtractIfCan(x, y) : Union(%,"failed") ==
             (na:= subtractIfCan(x.acomp, y.acomp)) case "failed" => "failed"
             (nb:= subtractIfCan(x.bcomp, y.bcomp)) case "failed" => "failed"
             [na::A,nb::B]

      if A has AbelianGroup and B has AbelianGroup then
         - x == [- x.acomp,-x.bcomp]
         (x - y):% == [x.acomp - y.acomp,x.bcomp - y.bcomp]
         d * x == [d * x.acomp,d * x.bcomp]

      if A has OrderedAbelianMonoidSup and B has OrderedAbelianMonoidSup then
         sup(x,y) == [sup(x.acomp,y.acomp),sup(x.bcomp,y.bcomp)]
```

```
       if A has OrderedSet and B has OrderedSet then
          x < y ==
               xa:= x.acomp ; ya:= y.acomp
               xa < ya => true
               xb:= x.bcomp ; yb:= y.bcomp
               xa = ya => (xb < yb)
               false

--     coerce(x:%):Symbol ==
--      PrintableForm()
--      formList([x.acomp::Expression,x.bcomp::Expression])$PrintableForm
```

———-

— PRODUCT.dotabb —

```
"PRODUCT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PRODUCT"]
"OAMONS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAMONS"]
"PRODUCT" -> "OAMONS"
```

———-

17.32 domain PROJPL ProjectivePlane

— ProjectivePlane.input —

```
)set break resume
)sys rm -f ProjectivePlane.output
)spool ProjectivePlane.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ProjectivePlane
--R
--R ProjectivePlane(K: Field)  is a domain constructor
--R Abbreviation for ProjectivePlane is PROJPL
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PROJPL
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : List(K) -> %
```

```
--R coerce : % -> List(K)                coerce : % -> OutputForm
--R conjugate : % -> %                   definingField : % -> K
--R degree : % -> PositiveInteger        ?.? : (%,Integer) -> K
--R hash : % -> SingleInteger            homogenize : % -> %
--R homogenize : (%,Integer) -> %        lastNonNul : % -> Integer
--R lastNonNull : % -> Integer           latex : % -> String
--R list : % -> List(K)                  orbit : % -> List(%)
--R pointValue : % -> List(K)            projectivePoint : List(K) -> %
--R rational? : % -> Boolean             setelt : (%,Integer,K) -> K
--R ?~=? : (%,%) -> Boolean
--R conjugate : (%,NonNegativeInteger) -> %
--R orbit : (%,NonNegativeInteger) -> List(%)
--R rational? : (%,NonNegativeInteger) -> Boolean
--R removeConjugate : List(%) -> List(%)
--R removeConjugate : (List(%),NonNegativeInteger) -> List(%)
--R
--E 1

)spool
)lisp (bye)
```

———-


— ProjectivePlane.help —

```
=====================================================================
ProjectivePlane examples
=====================================================================

See Also:
o )show ProjectivePlane
```

———-

17.32.1 ProjectivePlane (PROJPL)



Exports:

?.?	?=?	?~=?	coerce	conjugate
definingField	degree	hash	homogenize	lastNonNul
lastNonNull	latex	list	orbit	pointValue
projectivePoint	rational?	removeConjugate	setelt	

— **domain PROJPL ProjectivePlane** —

```
)abbrev domain PROJPL ProjectivePlane
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This is part of the PAFF package, related to projective space.
ProjectivePlane(K):Exports == Implementation where
  K:Field

  Exports ==> ProjectiveSpaceCategory(K)

  Implementation ==> ProjectiveSpace(3,K)
```

———-

— **PROJPL.dotabb** —

```
"PROJPL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PROJPL"];
"PROJSP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PROJSP"];
"PROJPL" -> "PROJSP"
```

———-

17.33 domain PROJPLPS ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField

— ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField.input —

```
)set break resume
)sys rm -f ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField.output
)spool ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField
--R
--R ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField(K: FiniteFieldCategory)  is a domain
--R Abbreviation for ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField is PROJPLPS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PROJPLPS
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R conjugate : % -> %                    degree : % -> PositiveInteger
--R hash : % -> SingleInteger             homogenize : % -> %
--R homogenize : (%,Integer) -> %         lastNonNul : % -> Integer
--R lastNonNull : % -> Integer            latex : % -> String
--R orbit : % -> List(%)                  rational? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R coerce : List(PseudoAlgebraicClosureOfFiniteField(K)) -> %
--R coerce : % -> List(PseudoAlgebraicClosureOfFiniteField(K))
--R conjugate : (%,NonNegativeInteger) -> %
--R definingField : % -> PseudoAlgebraicClosureOfFiniteField(K)
--R ?.? : (%,Integer) -> PseudoAlgebraicClosureOfFiniteField(K)
--R list : % -> List(PseudoAlgebraicClosureOfFiniteField(K))
--R orbit : (%,NonNegativeInteger) -> List(%)
--R pointValue : % -> List(PseudoAlgebraicClosureOfFiniteField(K))
--R projectivePoint : List(PseudoAlgebraicClosureOfFiniteField(K)) -> %
--R rational? : (%,NonNegativeInteger) -> Boolean
--R removeConjugate : List(%) -> List(%)
--R removeConjugate : (List(%),NonNegativeInteger) -> List(%)
--R setelt : (%,Integer,PseudoAlgebraicClosureOfFiniteField(K)) -> PseudoAlgebraicClosureOfFinit
--R
--E 1

)spool
)lisp (bye)
```

———-


— **ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField.help** —

```
=====================================================================
ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField examples
=====================================================================

See Also:
o )show ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField
```

———-

17.33.1 ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField (PROJPLPS)



Exports:

?.?	?=?	?~=?	coerce	conjugate
definingField	degree	hash	homogenize	lastNonNul
lastNonNull	latex	list	orbit	orbit
pointValue	projectivePoint	rational?	removeConjugate	setelt

— **domain PROJPLPS ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField** —

```
)abbrev domain PROJPLPS ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This is part of the PAFF package, related to projective space.
ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField(K):Exp == Impl where
```

```
  K:FiniteFieldCategory

  KK   ==> PseudoAlgebraicClosureOfFiniteField(K)

  Exp  ==> ProjectiveSpaceCategory(KK)

  Impl ==> ProjectivePlane(KK)
```

———-

— PROJPLPS.dotabb —

```
"PROJPLPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PROJPLPS"];
"PACOFF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PACOFF"];
"PROJPLPS" -> "PACOFF"
```

———-

17.34 domain PROJSP ProjectiveSpace

— ProjectiveSpace.input —

```
)set break resume
)sys rm -f ProjectiveSpace.output
)spool ProjectiveSpace.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ProjectiveSpace
--R
--R ProjectiveSpace(dim: NonNegativeInteger,K: Field)  is a domain constructor
--R Abbreviation for ProjectiveSpace is PROJSP
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PROJSP
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                coerce : List(K) -> %
--R coerce : % -> List(K)                 coerce : % -> OutputForm
--R conjugate : % -> %                    definingField : % -> K
--R degree : % -> PositiveInteger         ?.? : (%,Integer) -> K
--R hash : % -> SingleInteger             homogenize : % -> %
--R homogenize : (%,Integer) -> %         lastNonNul : % -> Integer
```

```
--R lastNonNull : % -> Integer            latex : % -> String
--R list : % -> List(K)                   orbit : % -> List(%)
--R pointValue : % -> List(K)             projectivePoint : List(K) -> %
--R rational? : % -> Boolean              setelt : (%,Integer,K) -> K
--R ?~=? : (%,%) -> Boolean
--R conjugate : (%,NonNegativeInteger) -> %
--R orbit : (%,NonNegativeInteger) -> List(%)
--R rational? : (%,NonNegativeInteger) -> Boolean
--R removeConjugate : List(%) -> List(%)
--R removeConjugate : (List(%),NonNegativeInteger) -> List(%)
--R
--E 1

)spool
)lisp (bye)
```

———-


— ProjectiveSpace.help —

```
=====================================================================
ProjectiveSpace examples
=====================================================================

See Also:
o )show ProjectiveSpace
```

———-

17.34.1 ProjectiveSpace (PROJSP)



Exports:

?.?	?=?	?~=?	coerce	conjugate
definingField	degree	hash	homogenize	lastNonNul
lastNonNull	latex	list	orbit	orbit
pointValue	projectivePoint	rational?	removeConjugate	setelt

— domain PROJSP ProjectiveSpace —

```
)abbrev domain PROJSP ProjectiveSpace
++ Author: Gaetan Hache
++ Date Created: 17 nov 1992
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This is part of the PAFF package, related to projective space.
ProjectiveSpace(dim,K):Exports == Implementation where

  NNI  ==> NonNegativeInteger
  LIST ==> List

  dim:NNI
  K:Field

  Exports ==> ProjectiveSpaceCategory(K)

  Implementation ==> List(K) add

    Rep:= List(K)

    coerce(pt:%):OutputForm ==
      dd:OutputForm:= ":" :: OutputForm
      llout:List(OutputForm):=[ hconcat(dd, a::OutputForm) for a in rest pt]
      lout:= cons( (first pt)::OutputForm , llout)
      out:= hconcat lout
      oo:=paren(out)
      ee:OutputForm:= degree(pt) :: OutputForm
      oo**ee

    definingField(pt)==
      K has PseudoAlgebraicClosureOfPerfectFieldCategory => _
        maxTower(pt pretend Rep)
      1$K

    degree(pt)==
      K has PseudoAlgebraicClosureOfPerfectFieldCategory => _
        extDegree definingField pt
      1

    coerce(pt:%):List(K) == pt pretend Rep

    projectivePoint(pt:LIST(K))==
        pt :: %
```

```
list(ptt)==
  ptt pretend Rep

pointValue(ptt)==
  ptt pretend Rep

conjugate(p,e)==
  lp:Rep:=p
  pc:List(K):=[c**e for c in lp]
  projectivePoint(pc)

homogenize(ptt,nV)==
  if K has Field then
    pt:=list(ptt)$%
    zero?(pt.nV) => error "Impossible to homogenize this point"
    divPt:=pt.nV
    ([(a/divPt) for a in pt])
  else
    ptt

rational?(p,n)== p=conjugate(p,n)

rational?(p)==rational?(p,characteristic()$K)

removeConjugate(l)==removeConjugate(l,characteristic()$K)

removeConjugate(l:LIST(%),n:NNI):LIST(%)==
  if K has FiniteFieldCategory then
    allconj:LIST(%):=empty()
    conjrem:LIST(%):=empty()
    for p in l repeat
      if ^member?(p,allconj) then
        conjrem:=cons(p,conjrem)
        allconj:=concat(allconj,orbit(p,n))
    conjrem
  else
    error "The field is not finite"

conjugate(p)==conjugate(p,characteristic()$K)

orbit(p)==orbit(p,characteristic()$K)

orbit(p,e)==
  if K has FiniteFieldCategory then
    l:LIST(%):=[p]
    np:%:=conjugate(p,e)
    flag:=^(np=p)::Boolean
    while flag repeat
      l:=concat(np,l)
```

```
          np:=conjugate(np,e)
          flag:=not (np=p)::Boolean
        l
      else
        error "Cannot compute the conjugate"

    aa:% = bb:% ==
      ah:=homogenize(aa)
      bh:=homogenize(bb)
      ah =$Rep bh

    coerce(pt:LIST(K))==
        ^(dim=#pt) => error "Le point n'a pas la bonne dimension"
        reduce("and",[zero?(a) for a in pt]) => _
          error "Ce n'est pas un point projectif"
        ptt:%:= pt
        homogenize ptt

    homogenize(ptt)==
      homogenize(ptt,lastNonNull(ptt))

    nonZero?: K -> Boolean
    nonZero?(a)==
      not(zero?(a))

    lastNonNull(ptt)==
      pt:=ptt pretend Rep
      (dim pretend Integer)+1-_
        (position("nonZero?",(reverse(pt)$LIST(K)))$LIST(K))

    lastNonNul(pt)==lastNonNull(pt)
```

———-

— PROJSP.dotabb —

```
"PROJSP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PROJSP"];
"PACPERC" [color=lightblue,href="bookvol10.2.pdf#nameddest=PACPERC"];
"FPC" [color=lightblue,href="bookvol10.2.pdf#nameddest=FPC"];
"PROJSP" -> "PACPERC"
"PROJSP" -> "FPC"
```

———-

17.35 domain PACEXT PseudoAlgebraicClosureOfAlgExtOfRationalNumber

— PseudoAlgebraicClosureOfAlgExtOfRationalNumber.input —

```
)set break resume
)sys rm -f PseudoAlgebraicClosureOfAlgExtOfRationalNumber.output
)spool PseudoAlgebraicClosureOfAlgExtOfRationalNumber.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PseudoAlgebraicClosureOfAlgExtOfRationalNumber
--E 1

)spool
)lisp (bye)
```

———-


— PseudoAlgebraicClosureOfAlgExtOfRationalNumber.help —

```
=====================================================================
PseudoAlgebraicClosureOfAlgExtOfRationalNumber examples
=====================================================================

See Also:
o )show PseudoAlgebraicClosureOfAlgExtOfRationalNumber
```

———-

17.35.1 PseudoAlgebraicClosureOfAlgExtOfRationalNumber (PACEXT)



Exports:

— domain PACEXT PseudoAlgebraicClosureOfAlgExtOfRational-Number —

```
)abbrev domain PACEXT PseudoAlgebraicClosureOfAlgExtOfRationalNumber
-- PseudoAlgebraicClosureOfAlgExtOfRationalNumber
++ Authors: Gaetan Hache
++ Date Created: jan 1998
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain implement dynamic extension over the
++ PseudoAlgebraicClosureOfRationalNumber.
++ A tower extension T  of the ground field K is any sequence of field
++ extension (T : K_0, K_1, ..., K_i...,K_n) where K_0 = K
++ and for i =1,2,...,n, K_i is an extension of K_{i-1} of degree > 1
++ and defined by an irreducible polynomial p(Z) in K_{i-1}.
++ Two towers (T_1: K_01, K_11,...,K_i1,...,K_n1) and
++ (T_2: K_02, K_12,...,K_i2,...,K_n2)
++ are said to be related if T_1 <= T_2 (or T_1 >= T_2),
++ that is if K_i1 = K_i2 for i=1,2,...,n1
++ (or i=1,2,...,n2). Any algebraic operations defined for several elements
++ are only defined if all of the concerned elements are comming from
++ a set of related tour extensions.
PseudoAlgebraicClosureOfAlgExtOfRationalNumber(downLevel:K):Exp == Impl where
  K       ==> PseudoAlgebraicClosureOfRationalNumber
  INT     ==> Integer
  NNI     ==> NonNegativeInteger
  SUP     ==> SparseUnivariatePolynomial
  BOOLEAN ==> Boolean
  PI      ==> PositiveInteger
  FACTRN  ==> FactorisationOverPseudoAlgebraicClosureOfAlgExtOfRationalNumber

  recRep ==> Record(recEl:SUP(%),_
```

```
                  recTower:SUP(%),_
                  recDeg:PI,_
                  recPrevTower:%,_
                  recName:Symbol)

Exp == PseudoAlgebraicClosureOfAlgExtOfRationalNumberCategory with

  fullOutput: % -> OutputForm

  retractToGrn: % -> K

Impl == add
  Rep := Union(recRep,K)

  -- signature of local function
  replaceRecEl: (%,SUP(%)) -> %

  down: % -> %

  retractPol( pol:SUP(%) ):SUP(K)==
    zero? pol => 0$SUP(K)
    lc := leadingCoefficient pol
    d := degree pol
    rlc := retractToGrn( lc )
    monomial( rlc , d )$SUP(K) + retractPol( reductum pol )

  retractToGrn(aa)==
    aa case K => aa
    a:=(aa pretend recRep)
    el:=  a.recEl
    t:=   a.recTower
    d:=   a.recDeg * extDegree downLevel
    pt:=  a.recPrevTower
    n:= a.recName
    newElement(retractPol el, retractPol t, d, retractToGrn pt, n)$K

  newElement(pol,subF,inName)  ==
      -- pol is an irreducible polynomial over the field extension
      -- given by subF.
      -- The output of this function is a root of pol.
    dp:=degree pol
    listCoef: List % := coefficients pol
    a1:% := inv first listCoef
    b1:% := last listCoef
    rr:% := b1*a1
    one?(dp) =>
      one?(#listCoef) => 0
      - rr
    ground?(pol) => error "Cannot create a new element with a constant"
    d:PI := (dp pretend PI) * extDegree(subF)
```

```
    [monomial(1$%,1)$SUP(%),pol,d,subF,inName] :: Rep

  coerce(a:Integer):%== (a :: K)

  down(a:%) ==
    a case K => a
    aa:=(a pretend recRep)
    elel := aa.recEl
    ^ground?(elel)$SUP(%) => a
    gel:%:=ground(elel)
    down(gel)

  n:INT * a:% ==
    one?(n) => a
    zero?(a) or zero?(n) => 0
    (n < 0) => - ((-n)*a)
    mm:PositiveInteger:=(n pretend PositiveInteger)
    double(mm,a)$RepeatedDoubling(%)

  replaceRecEl(a,el)==
    a case K => a
    aa:=copy a
    aa.recEl := el
    aa

  localTower :% := downLevel

  lift(a) ==
    a case K => monomial(a,0)
    (a pretend recRep).recEl

  lift(a,b)==
    extDegree a > extDegree b => _
      error "Cannot lift something at lower level !!!!!"
    extDegree a < extDegree b => monomial(a,0)$SUP(%)
    lift a

  reduce(a)==
    localTower case K =>
      coefficient(a,0)
    ar:= a rem (localTower pretend recRep).recTower
    replaceRecEl(localTower,ar)

  maxTower(la)==
      --return an element from the list la which is in the largest
      --extension of the ground field
      --PRECONDITION: all elements in same tower, else no meaning?
    m:="max"/[extDegree(a)$% for a in la]
    first [b for b in la | extDegree(b)=m]
```

```
ground?(a)== a case K

vectorise(a,lev)==
  da:=extDegree a
  dlev:=extDegree lev
  dlev < da => _
    error "Cannot vectorise at a lower level than the element to vectorise"
  lev case K => [a]
  pa:SUP(%)
  na:%
  ^(da = dlev) =>
    pa:=  monomial(a,0)$SUP(%)
    na:=  replaceRecEl(lev,pa)
    vectorise(na,lev)$%

  prevLev:=previousTower(lev)
  a case K => error "At this point a is not suppose to be in K"
  aEl:=(a pretend recRep).recEl
  daEl:=degree definingPolynomial(a)$%
  lv:=[vectorise(c,prevLev)$% for c in entries(vectorise(aEl,daEl)$SUP(%))]
  concat lv

retractIfCan(a:%):Union(K,"failed")==
  a case K => a
  "failed"

retractIfCan(a:%):Union(Integer,"failed")==
  a case K => retractIfCan(a)$K
  "failed"

setTower!(a) ==
  if a case K then
    localTower := downLevel
  else
    localTower:=a
  void()

definingPolynomial == definingPolynomial(localTower)

a:% + b:% ==
  (a case K) and (b case K) => a +$K b
  extDegree(a) > extDegree(b) => b + a
  res1:SUP(%)
  res2:%
  if extDegree(a) = extDegree(b) then
    res1:=   b.recEl +$SUP(%) a.recEl
    res2:=   replaceRecEl(b,res1)
  else
    res1:=   b.recEl +$SUP(%) monomial(a,0)$SUP(%)
    res2:= replaceRecEl(b,res1)
```

```
  down(res2)

a:% * b:% ==
  (a case K) and (b case K) => a *$K b
  extDegree(a) > extDegree(b) => b * a
  res1:SUP(%)
  res2:%
  if extDegree(a) = extDegree(b) then
    res1:=   b.recEl *$SUP(%) a.recEl rem b.recTower
    res2:=   replaceRecEl(b,res1)
  else
    res1:=   b.recEl *$SUP(%) monomial(a,0)$SUP(%)
    res2:=  replaceRecEl(b,res1)
  down(res2)

distinguishedRootsOf(polyZero,ee) ==
    setTower!(ee)
    zero?(polyZero) => error "to lazy to give you all the roots of 0 !!!"
    factorf: Factored SUP % :=  factor(polyZero,localTower)$FACTRN(%)
    listFact:List SUP %  := [pol.fctr for pol in factorList(factorf)]
    listOfZeros:List(%):=empty()
    for p in listFact repeat
      root:=newElement(p, new(E::Symbol)$Symbol)
      listOfZeros:List(%):=concat([ root ], listOfZeros)
    listOfZeros

1 == 1$K

0 == 0$K

newElement(poll:SUP(%),inName:Symbol)==
  newElement(poll,localTower,inName)$%

--Field operations
inv(a)==
  a case K => inv(a)$K
  aRecEl:= (a pretend recRep).recEl
  aDefPoly:= (a pretend recRep).recTower
  aInv := extendedEuclidean( aRecEl , aDefPoly, 1 )
  aInv  case "failed" => error "PACOFF : division by zero"
  -- On doit retourner un Record reprsentant l'inverse de a.
  -- Ce Record est exactement le mme que celui de a sauf
  -- qu'il faut remplacer le polynme du selecteur recEl
  -- par le polynme reprsentant l'inverse de a :
  -- C'est ce que fait la fonction replaceRecEl.
  replaceRecEl( a , aInv.coef1 )

a:% / b:% == a * inv(b)

a:K * b:%==
```

```
    (a :: %) * b

  b:% * a:K == a*b

  a:% - b:% ==
    a + (-b)

  a:% * b:Fraction(Integer) ==
    bn:=numer b
    bd:=denom b
    ebn:%:= bn * 1$%
    ebd:%:= bd * 1$%
    a * ebn * inv(ebd)

  -a:% ==
     a case K => -$K a
     [-$SUP(%) (a pretend recRep).recEl,_
      (a pretend recRep).recTower,_
      (a pretend recRep).recDeg,_
      (a pretend recRep).recPrevTower,_
      (a pretend recRep).recName ]

  bb:% = aa:% ==
    b:=down bb
    a:=down aa
    ^( extDegree(b) =$NNI extDegree(a) ) => false
    (b case K)  =>  ( (retract a)@K  =$K (retract b)@K )
    rda := a :: recRep
    rdb := b :: recRep
    not (rda.recTower =$SUP(%) rdb.recTower) => false
    rdb.recEl =$SUP(%) rda.recEl

  zero?(a:%) ==
    da:=down a  -- just to be sure !!!
    ^(da case K) => false
    zero?(da)$K

  one?(a:%) ==
    da:= down a  -- just to be sure !!!
    ^(da case K) => false
    one?(da)$K

  coerce(a:K):% == a

  coerce(a:%):OutputForm ==
    a case K => ((retract a)@K) ::OutputForm
    outputForm((a pretend recRep).recEl,_
               ((a pretend recRep).recName)::OutputForm) $SUP(%)

  fullOutput(a:%):OutputForm==
```

```
      a case K => ((retract a)@K) ::OutputForm
      (a pretend recRep)::OutputForm

    definingPolynomial(a:%): SUP % ==
      a case K => monomial(1,1)$SUP(%)
      (a pretend recRep).recTower

    extDegree(a:%): PI ==
      a case K => 1
      (a pretend recRep).recDeg

    previousTower(a:%):% ==
      a case K => error "No previous extension for ground field element"
      (a pretend recRep).recPrevTower

    name(a:%):Symbol ==
      a case K => error "No name for ground field element"
      (a pretend recRep).recName

    characteristic == characteristic()$K
```

———-

— PACEXT.dotabb —

```
"PACEXT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PACEXT"];
"FACTEXT" [color="#FF4488",href="bookvol10.4.pdf#nameddest=FACTEXT"]
"PACEXT" -> "FACTEXT"
```

———-

17.36 domain PACOFF PseudoAlgebraicClosureOfFiniteField

— PseudoAlgebraicClosureOfFiniteField.input —

```
)set break resume
)sys rm -f PseudoAlgebraicClosureOfFiniteField.output
)spool PseudoAlgebraicClosureOfFiniteField.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show PseudoAlgebraicClosureOfFiniteField
--R
--R PseudoAlgebraicClosureOfFiniteField(K: FiniteFieldCategory)  is a domain constructor
--R Abbreviation for PseudoAlgebraicClosureOfFiniteField is PACOFF
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PACOFF
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,K) -> %                      ?*? : (K,%) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,K) -> %                      ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                D : % -> %
--R D : (%,NonNegativeInteger) -> %       1 : () -> %
--R 0 : () -> %                           ?^? : (%,Integer) -> %
--R ?^? : (%,PositiveInteger) -> %        algebraic? : % -> Boolean
--R associates? : (%,%) -> Boolean        charthRoot : % -> %
--R coerce : K -> %                       coerce : Fraction(Integer) -> %
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              conjugate : % -> %
--R createPrimitiveElement : () -> %      differentiate : % -> %
--R dimension : () -> CardinalNumber      extDegree : % -> PositiveInteger
--R factor : % -> Factored(%)             fullOutput : % -> OutputForm
--R gcd : List(%) -> %                    gcd : (%,%) -> %
--R ground? : % -> Boolean                hash : % -> SingleInteger
--R inGroundField? : % -> Boolean         index : PositiveInteger -> %
--R init : () -> %                        inv : % -> %
--R latex : % -> String                   lcm : List(%) -> %
--R lcm : (%,%) -> %                      lookup : % -> PositiveInteger
--R maxTower : List(%) -> %               one? : % -> Boolean
--R order : % -> PositiveInteger          previousTower : % -> %
--R prime? : % -> Boolean                 primeFrobenius : % -> %
--R primitive? : % -> Boolean             primitiveElement : () -> %
--R ?quo? : (%,%) -> %                    random : () -> %
--R recip : % -> Union(%,"failed")        ?rem? : (%,%) -> %
--R retract : % -> K                      sample : () -> %
--R setTower! : % -> Void                 size : () -> NonNegativeInteger
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               transcendent? : % -> Boolean
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R vectorise : (%,%) -> Vector(%)        zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R Frobenius : % -> % if K has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if K has FINITE
```

```
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed")
--R conditionP : Matrix(%) -> Union(Vector(%),"failed")
--R definingPolynomial : () -> SparseUnivariatePolynomial(%)
--R definingPolynomial : % -> SparseUnivariatePolynomial(%)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R differentiate : (%,NonNegativeInteger) -> %
--R discreteLog : % -> NonNegativeInteger
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed")
--R distinguishedRootsOf : (SparseUnivariatePolynomial(%),%) -> List(%)
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer))
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R lift : % -> SparseUnivariatePolynomial(%)
--R lift : (%,%) -> SparseUnivariatePolynomial(%)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R newElement : (SparseUnivariatePolynomial(%),%,Symbol) -> %
--R newElement : (SparseUnivariatePolynomial(%),Symbol) -> %
--R nextItem : % -> Union(%,"failed")
--R order : % -> OnePointCompletion(PositiveInteger)
--R primeFrobenius : (%,NonNegativeInteger) -> %
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R reduce : SparseUnivariatePolynomial(%) -> %
--R representationType : () -> Union("prime",polynomial,normal,cyclic)
--R retractIfCan : % -> Union(K,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger)
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— PseudoAlgebraicClosureOfFiniteField.help —

```
====================================================================
PseudoAlgebraicClosureOfFiniteField examples
```

```
================================================================================

See Also:
o )show PseudoAlgebraicClosureOfFiniteField
```

17.36.1 PseudoAlgebraicClosureOfFiniteField (PACOFF)



Exports:

0	1	-?
?**?	?*?	?+?
?-?	?/?	?=?
?^?	?~=?	?quo?
?rem?	D	algebraic?
associates?	characteristic	charthRoot
coerce	conditionP	conjugate
createPrimitiveElement	definingPolynomial	degree
differentiate	dimension	discreteLog
distinguishedRootsOf	divide	euclideanSize
expressIdealMember	exquo	extDegree
extendedEuclidean	extensionDegree	factor
factorsOfCyclicGroupSize	Frobenius	fullOutput
gcd	gcdPolynomial	ground?
hash	inGroundField?	index
init	inv	latex
lcm	lift	lookup
maxTower	multiEuclidean	newElement
nextItem	one?	order
previousTower	prime?	primeFrobenius
primitive?	primitiveElement	principalIdeal
random	recip	reduce
representationType	retract	retractIfCan
sample	setTower!	size
sizeLess?	squareFree	squareFreePart
subtractIfCan	tableForDiscreteLogarithm	transcendenceDegree
transcendent?	unit?	unitCanonical
unitNormal	vectorise	zero?

— domain PACOFF PseudoAlgebraicClosureOfFiniteField —

```
)abbrev domain PACOFF PseudoAlgebraicClosureOfFiniteField
++ Authors: Gaetan Hache
++ Date Created: june 1996
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain implement  dynamic extension using the simple notion of
++ tower extensions. A tower extension T  of the ground  field K is any
++ sequence of field extension (T : K_0, K_1, ..., K_i...,K_n) where K_0 = K
++ and for i =1,2,...,n, K_i is an extension of K_{i-1} of degree > 1 and
++ defined by an irreducible polynomial p(Z) in K_{i-1}.
++ Two towers (T_1: K_01, K_11,...,K_i1,...,K_n1)
++ and (T_2: K_02, K_12,...,K_i2,...,K_n2) are said to be related
++ if T_1 <= T_2 (or T_1 >= T_2), that is if K_i1 = K_i2 for i=1,2,...,n1
++ (or i=1,2,...,n2). Any algebraic operations defined for several elements
++ are only defined if all of the concerned elements are comming from
++ a set of related tour extensions.
PseudoAlgebraicClosureOfFiniteField(K):Exports == Implementation where
```

```
K:FiniteFieldCategory

INT      ==> Integer
NNI      ==> NonNegativeInteger
SUP      ==> SparseUnivariatePolynomial
BOOLEAN  ==> Boolean
PI       ==> PositiveInteger
FFFACTSE ==> FiniteFieldFactorizationWithSizeParseBySideEffect

recRep ==> Record(recEl:SUP(%),_
                  recTower:SUP(%),_
                  recDeg:PI,_
                  recPrevTower:%,_
                  recName:Symbol)

Exports == Join(PseudoAlgebraicClosureOfFiniteFieldCategory,_
                ExtensionField(K)) with

  fullOutput: % -> OutputForm

Implementation == add
  Rep := Union(recRep,K)

  -- signature of local function
  replaceRecEl: (%,SUP(%)) -> %
  down: % -> %
  localRandom: % -> %
  repPolynomial : % -> SUP(%)

  replaceRecEl(a,el)==
    a case K => a
    aa:=copy a
    aa.recEl := el
    aa

  -- local variable
  localTower :% := 1$K

  localSize :NNI := size()$K
  -- implemetation of exported function

  degree(a)==
    da:PositiveInteger:= extDegree a
    coerce(da@PositiveInteger)$OnePointCompletion(PositiveInteger)

  repPolynomial(a)==
    a case K => error "Is in ground field"
    (a pretend recRep).recEl

  inv(a)==
```

```
    a case K => inv(a)$K
    aRecEl:= repPolynomial a
    aDefPoly:= definingPolynomial a
    aInv := extendedEuclidean( aRecEl , aDefPoly, 1 )
    aInv  case "failed" => error "PACOFF : division by zero"
    down replaceRecEl( a , aInv.coef1 )

  a:% ** n:PositiveInteger ==
    zero?(a) => 0
    expt( a , n )$RepeatedSquaring(%)

  a:% ** n:NonNegativeInteger ==
    zero?(a) and zero?(n) => error " --- 0^0 not defined "
    zero?(n) => 1$%
    a ** ( n pretend PositiveInteger )

  a:% ** n:Integer ==
    n < 0 => inv( a ** ( (-n)  pretend PositiveInteger) )
    a ** ( n pretend NonNegativeInteger )

  unitNormal(a)==
    zero? a => [1,0,1]
    [a,1,inv a]

  ground?(a)== a case K

  vectorise(a,lev)==
    da:=extDegree a
    dlev:=extDegree lev
    dlev < da => _
     error "Cannot vectorise at a lower level than the element to vectorise"
    lev case K => [a]
    pa:SUP(%)
    na:%
    ^(da = dlev) =>
      pa:=  monomial(a,0)$SUP(%)
      na:=  replaceRecEl(lev,pa)
      vectorise(na,lev)$%
    prevLev:=previousTower(lev)
    a case K => _
     error "At this point a is not suppose to be in K, big error"
    aEl:=(a pretend recRep).recEl
    daEl:=degree(definingPolynomial a)$SUP(%)
    lv:=[vectorise(c,prevLev)$% for c in entries(vectorise(aEl,daEl)$SUP(%))]
    concat lv

  size == localSize

  setTower!(a) ==
    localTower:=a
```

```
    localSize:=(size()$K)**extDegree(a)
    void()

  localRandom(a) ==
      --return a random element at the extension of a
    a case K => random()$K
    subF:=previousTower(a)
    d:=degree(a.recTower)-1
    pol:=reduce("+",[monomial(localRandom(subF),i)$SUP(%) for i in 0..d])
    down replaceRecEl(a,pol)

  a:% + b:% ==
    (a case K) and (b case K) => a +$K b
    extDegree(a) > extDegree(b) => b + a
    res1:SUP(%)
    res2:%
    if extDegree(a) = extDegree(b) then
      res1:=   b.recEl +$SUP(%) a.recEl
      res2:=   replaceRecEl(b,res1)
    else
      res1:=   b.recEl +$SUP(%) monomial(a,0)$SUP(%)
      res2:= replaceRecEl(b,res1)
    down(res2)

  a:% * b:% ==
    (a case K) and (b case K) => a *$K b
    extDegree(a) > extDegree(b) => b * a
    res1:SUP(%)
    res2:%
    if extDegree(a) = extDegree(b) then
      res1:=   b.recEl *$SUP(%) a.recEl rem b.recTower
      res2:=   replaceRecEl(b,res1)
    else
      res1:=   b.recEl *$SUP(%) monomial(a,0)$SUP(%)
      res2:=  replaceRecEl(b,res1)
    down(res2)

  distinguishedRootsOf(polyZero,ee) ==
      setTower!(ee)
      zero?(polyZero) => error "to lazy to give you all the roots of 0 !!!"
      factorf: Factored SUP % :=  factor(polyZero)$FFFACTSE(%,SUP(%))
      listFact:List SUP %  := [pol.fctr for pol in factorList(factorf)]
      listOfZeros:List(%):=empty()
      for p in listFact repeat
        root:=newElement(p, new(D::Symbol)$Symbol)
        listOfZeros:List(%):=concat([ root ], listOfZeros)
      listOfZeros

  random==
    localRandom(localTower)
```

```
extDegOfGrdField:PI :=
  i: PI := 1
  while characteristic()$K ** i < size()$K repeat
    i:= i + 1
  i

charthRoot(a : %): % ==
  --return a**(1/chararcteristic )
  a case K => charthRoot(retract a)$K
  b:NNI := extDegree(a) * extDegOfGrdField
  j := subtractIfCan(b,1)
  if (j case "failed") then b:= 0
  else b:= j
  c:= (characteristic()$K) ** b
  a**c

conjugate(a)==
  a ** size()$K

1 == 1$K

0 == 0$K

newElement(pol:SUP(%),subF:%,inName:Symbol): % ==
    -- pol is an irreducible polynomial over the field extension
    -- given by subF.
    -- The output of this function is a root of pol.
  dp:=degree pol
  one?(dp) =>
    listCoef:=coefficients(pol)
    one?(#listCoef) => 0
    - last(listCoef) / first(listCoef)
  ground?(pol) => error "Cannot create a new element with a constant"
  d:PI := (dp pretend PI) * extDegree(subF)
  [monomial(1$%,1),pol,d,subF,inName] :: Rep

newElement(poll:SUP(%),inName:Symbol)==
  newElement(poll,localTower,inName)

maxTower(la)==
    --return an element from the list la which is in the largest
    --extension of the ground field
    --PRECONDITION: all elements in same tower, else no meaning?
  m:=reduce("max",[extDegree(a) for a in la])
  first [b for b in la | extDegree(b)=m]

--Field operations

a:% / b:% == a * inv(b)
```

```
a:K * b:%==
  (a :: %) * b

b:% * a:K == a*b

a:% - b:% ==
  a + (-b)

a:% * b:Fraction(Integer) ==
  bn:=numer b
  bd:=denom b
  ebn:%:= bn * 1$%
  ebd:%:= bd * 1$%
  a * ebn * inv(ebd)

-a:% ==
   a case K => -$K a
   [-$SUP(%) (a pretend recRep).recEl,_
    (a pretend recRep).recTower,_
    (a pretend recRep).recDeg,_
    (a pretend recRep).recPrevTower,_
    (a pretend recRep).recName ]

n:INT * a:% ==
  one?(n) => a
  zero?(a) or zero?(n) => 0
  (n < 0) => - ((-n)*a)
  mm:PositiveInteger:=(n pretend PositiveInteger)
  double(mm,a)$RepeatedDoubling(%)

bb:% = aa:% ==
  b:=down bb
  a:=down aa
  ^( extDegree(b) =$NNI extDegree(a) ) => false
  (b case K)  =>  ( (retract a)  =$K (retract b) )
  rda := a :: recRep
  rdb := b :: recRep
  not (rda.recTower =$SUP(%) rdb.recTower) => false
  rdb.recEl =$SUP(%) rda.recEl

zero?(a:%) ==
  da:=down a  -- just to be sure !!!
  ^(da case K) => false
  zero?(da)$K

one?(a:%) ==
  da:= down a  -- just to be sure !!!
  ^(da case K) => false
  one?(da)$K
```

```
--Coerce Functions

coerce(a:K) == a

retractIfCan(a)==
  a case K => a
  "failed"

coerce(a:%):OutputForm ==
  a case K => (retract a)::OutputForm
  outputForm((a pretend recRep).recEl,_
            ((a pretend recRep).recName)::OutputForm) $SUP(%)

fullOutput(a:%):OutputForm==
  a case K => (retract a)::OutputForm
  (a pretend recRep)::OutputForm

definingPolynomial(a:%): SUP % ==
  a case K => 1
  (a pretend recRep).recTower

extDegree(a:%): PI ==
  a case K => 1
  (a pretend recRep).recDeg

previousTower(a:%):% ==
  a case K => error "No previous extension for ground field element"
  (a pretend recRep).recPrevTower

name(a:%):Symbol ==
  a case K => error "No name for ground field element"
  (a pretend recRep).recName

-- function related to the ground field

lookup(a:%)==
  aa:=down a
  ^(aa case K) => _
    error "From NonGlobalDynamicExtensionOfFiniteField fnc Lookup: Cannot take i-dex"
  lookup(retract aa)$K

index(i)==(index(i)$K)

fromPrimeField? == characteristic()$K = size()$K

representationType == representationType()$K

characteristic == characteristic()$K
```

```
    -- implementation of local functions

    down(a:%) ==
      a case K => a
      aa:=(a pretend recRep)
      elel := aa.recEl
      ^ground?(elel) => a
      gel:%:=ground(elel)
      down(gel)
```

———-

— PACOFF.dotabb —

```
"PACOFF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PACOFF"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"PACOFF" -> "ALIST"
```

———-

17.37 domain PACRAT PseudoAlgebraicClosureOfRational-Number

— PseudoAlgebraicClosureOfRationalNumber.input —

```
)set break resume
)sys rm -f PseudoAlgebraicClosureOfRationalNumber.output
)spool PseudoAlgebraicClosureOfRationalNumber.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show PseudoAlgebraicClosureOfRationalNumber
--R
--R PseudoAlgebraicClosureOfRationalNumber  is a domain constructor
--R Abbreviation for PseudoAlgebraicClosureOfRationalNumber is PACRAT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for PACRAT
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,Fraction(Integer)) -> %      ?*? : (Fraction(Integer),%) -> %
--R ?*? : (Fraction(Integer),%) -> %      ?*? : (%,Fraction(Integer)) -> %
```

```
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,Integer) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?/? : (%,Fraction(Integer)) -> %      ?/? : (%,%) -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
--R 0 : () -> %                           ?^? : (%,Integer) -> %
--R ?^? : (%,PositiveInteger) -> %        algebraic? : % -> Boolean
--R associates? : (%,%) -> Boolean        coerce : Fraction(Integer) -> %
--R coerce : Fraction(Integer) -> %       coerce : Integer -> %
--R coerce : Fraction(Integer) -> %       coerce : % -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R conjugate : % -> %                    dimension : () -> CardinalNumber
--R extDegree : % -> PositiveInteger      factor : % -> Factored(%)
--R fullOutput : % -> OutputForm          gcd : List(%) -> %
--R gcd : (%,%) -> %                      ground? : % -> Boolean
--R hash : % -> SingleInteger             inGroundField? : % -> Boolean
--R inv : % -> %                          latex : % -> String
--R lcm : List(%) -> %                    lcm : (%,%) -> %
--R maxTower : List(%) -> %               one? : % -> Boolean
--R previousTower : % -> %                prime? : % -> Boolean
--R ?quo? : (%,%) -> %                    recip : % -> Union(%,"failed")
--R ?rem? : (%,%) -> %                    retract : % -> Fraction(Integer)
--R retract : % -> Fraction(Integer)      retract : % -> Integer
--R sample : () -> %                      setTower! : % -> Void
--R sizeLess? : (%,%) -> Boolean          squareFree : % -> Factored(%)
--R squareFreePart : % -> %               transcendent? : % -> Boolean
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R vectorise : (%,%) -> Vector(%)        zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R Frobenius : % -> % if Fraction(Integer) has FINITE
--R Frobenius : (%,NonNegativeInteger) -> % if Fraction(Integer) has FINITE
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Fraction(Integer) has CHARNZ or Fraction(Integer) has
--R definingPolynomial : % -> SparseUnivariatePolynomial(%)
--R definingPolynomial : () -> SparseUnivariatePolynomial(%)
--R degree : % -> OnePointCompletion(PositiveInteger)
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if Fraction(Integer) has CHARNZ or
--R distinguishedRootsOf : (SparseUnivariatePolynomial(%),%) -> List(%)
--R divide : (%,%) -> Record(quotient: %,remainder: %)
--R euclideanSize : % -> NonNegativeInteger
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed")
--R exquo : (%,%) -> Union(%,"failed")
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed")
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %)
--R extensionDegree : () -> OnePointCompletion(PositiveInteger)
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
```

```
--R lift : (%,%) -> SparseUnivariatePolynomial(%)
--R lift : % -> SparseUnivariatePolynomial(%)
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed")
--R newElement : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%),PositiveInteger,%,Symbol) -> %
--R newElement : (SparseUnivariatePolynomial(%),Symbol) -> %
--R newElement : (SparseUnivariatePolynomial(%),%,Symbol) -> %
--R order : % -> OnePointCompletion(PositiveInteger) if Fraction(Integer) has CHARNZ or Fraction(Integer) ha
--R primeFrobenius : % -> % if Fraction(Integer) has CHARNZ or Fraction(Integer) has FINITE
--R primeFrobenius : (%,NonNegativeInteger) -> % if Fraction(Integer) has CHARNZ or Fraction(Integer) has FI
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %)
--R reduce : SparseUnivariatePolynomial(%) -> %
--R retractIfCan : % -> Union(Fraction(Integer),"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed")
--R retractIfCan : % -> Union(Integer,"failed")
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R transcendenceDegree : () -> NonNegativeInteger
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— PseudoAlgebraicClosureOfRationalNumber.help —

```
====================================================================
PseudoAlgebraicClosureOfRationalNumber examples
====================================================================

See Also:
o )show PseudoAlgebraicClosureOfRationalNumber
```

———-

17.37.1 PseudoAlgebraicClosureOfRationalNumber (PACRAT)



Exports:

0	0	1	-?	?**?
?*?	?+?	?-?	?/?	
?=?	?^?	?~=?	?quo?	
?rem?	algebraic?	associates?	characteristic	
charthRoot	coerce	conjugate	definingPolynomial	
degree	dimension	discreteLog	distinguishedRootsOf	
divide	euclideanSize	expressIdealMember	exquo	
extDegree	extendedEuclidean	extensionDegree	factor	
Frobenius	fullOutput	gcd	gcdPolynomial	
ground?	hash	inGroundField?	inv	
latex	lcm	lift	maxTower	
multiEuclidean	newElement	one?	order	
previousTower	prime?	primeFrobenius	principalIdeal	
recip	reduce	retract	retractIfCan	
sample	setTower!	sizeLess?	squareFree	
squareFreePart	subtractIfCan	transcendenceDegree	transcendent?	
unit?	unitCanonical	unitNormal	vectorise	
zero?				

— domain PACRAT PseudoAlgebraicClosureOfRationalNumber —

```
)abbrev domain PACRAT PseudoAlgebraicClosureOfRationalNumber
++ Authors: Gaetan Hache
++ Date Created: feb 1997
++ Date Last Updated: May 2010 by Tim Daly
++ Description:
++ This domain implements dynamic extension using the simple notion of
++ tower extensions. A tower extension T of the ground field K is any
++ sequence of field extension (T : K_0, K_1, ..., K_i...,K_n) where K_0 = K
++ and for i =1,2,...,n, K_i is an extension of K_{i-1} of degree > 1 and
++ defined by an irreducible polynomial p(Z) in K_{i-1}.
++ Two towers (T_1: K_01, K_11,...,K_i1,...,K_n1) and
++ (T_2: K_02, K_12,...,K_i2,...,K_n2) are said to be related if T_1 <= T_2
```

```
++ (or T_1 >= T_2), that is if K_i1 = K_i2 for i=1,2,...,n1
++ (or i=1,2,...,n2). Any algebraic operations defined for several elements
++ are only defined if all of the concerned elements are comming from
++ a set of related tour extensions.
PseudoAlgebraicClosureOfRationalNumber:Exports == Implementation where

  INT     ==> Integer
  K       ==> Fraction Integer
  NNI     ==> NonNegativeInteger
  SUP     ==> SparseUnivariatePolynomial
  BOOLEAN ==> Boolean
  PI      ==> PositiveInteger
  FACTRN  ==> FactorisationOverPseudoAlgebraicClosureOfRationalNumber

  recRep  ==> Record(recEl:SUP(%),_
                     recTower:SUP(%),_
                     recDeg:PI,_
                     recPrevTower:%,_
                     recName:Symbol)

  Exports == PseudoAlgebraicClosureOfRationalNumberCategory with

    fullOutput: % -> OutputForm

    newElement: (SUP(%), SUP(%), PI,  %, Symbol) -> %

  Implementation == add
    Rep := Union(recRep,K)

    -- signature of local function
    replaceRecEl: (%,SUP(%)) -> %
    down: % -> %

    down(a:%) ==
      a case K => a
      aa:=(a pretend recRep)
      elel := aa.recEl
      ^ground?(elel)$SUP(%) => a
      gel:%:=ground(elel)
      down(gel)

    coerce(a:Integer):%== (a :: K)

    n:INT * a:% ==
      one?(n) => a
      zero?(a) or zero?(n) => 0
      (n < 0) => - ((-n)*a)
      mm:PositiveInteger:=(n pretend PositiveInteger)
      double(mm,a)$RepeatedDoubling(%)
```

```
replaceRecEl(a,el)==
  a case K => a
  aa:=copy a
  aa.recEl := el
  aa

-- local variable
localTower :% := 1$K

-- implemetation of exported function

lift(a) ==
  a case K => monomial(a,0)
  (a pretend recRep).recEl

lift(a,b)==
  extDegree a > extDegree b => _
      error "Cannot lift something at lower level !!!!!"
  extDegree a < extDegree b => monomial(a,0)$SUP(%)
  lift a

reduce(a)==
  localTower case K =>
    coefficient(a,0)
  ar:= a rem (localTower pretend recRep).recTower
  replaceRecEl(localTower,ar)

maxTower(la)==
    --return an element from the list la which is in the largest
    --extension of the ground field
    --PRECONDITION: all elements in same tower, else no meaning?
  m:="max"/[extDegree(a)$% for a in la]
  first [b for b in la | extDegree(b)=m]

ground?(a)== a case K

vectorise(a,lev)==
  da:=extDegree a
  dlev:=extDegree lev
  dlev < da => _
    error "Cannot vectorise at a lower level than the element to vectorise"
  lev case K => [a]
  pa:SUP(%)
  na:%
  ^(da = dlev) =>
    pa:=  monomial(a,0)$SUP(%)
    na:=  replaceRecEl(lev,pa)
    vectorise(na,lev)$%
  prevLev:=previousTower(lev)
  a case K => error "At this point a is not suppose to be in K"
```

```
    aEl:=(a pretend recRep).recEl
    daEl:=degree definingPolynomial(a)$%
    lv:=[vectorise(c,prevLev)$% for c in entries(vectorise(aEl,daEl)$SUP(%))]
    concat lv

  setTower!(a) ==
    localTower:=a
    void()

  definingPolynomial == definingPolynomial(localTower)

  a:% + b:% ==
    (a case K) and (b case K) => a +$K b
    extDegree(a) > extDegree(b) => b + a
    res1:SUP(%)
    res2:%
    if extDegree(a) = extDegree(b) then
      res1:=   b.recEl +$SUP(%) a.recEl
      res2:=   replaceRecEl(b,res1)
    else
      res1:=   b.recEl +$SUP(%) monomial(a,0)$SUP(%)
      res2:= replaceRecEl(b,res1)
    down(res2)

  a:% * b:% ==
    (a case K) and (b case K) => a *$K b
    extDegree(a) > extDegree(b) => b * a
    res1:SUP(%)
    res2:%
    if extDegree(a) = extDegree(b) then
      res1:=   b.recEl *$SUP(%) a.recEl rem b.recTower
      res2:=   replaceRecEl(b,res1)
    else
      res1:=   b.recEl *$SUP(%) monomial(a,0)$SUP(%)
      res2:=  replaceRecEl(b,res1)
    down(res2)

  distinguishedRootsOf(polyZero,ee) ==
      setTower!(ee)
      zero?(polyZero) => error "to lazy to give you all the roots of 0 !!!"
      factorf: Factored SUP % :=  factor(polyZero,ee)$FACTRN(%)
      listFact:List SUP %  := [pol.fctr for pol in factorList(factorf)]
      listOfZeros:List(%):=empty()
      for p in listFact repeat
        root:=newElement(p, new(D::Symbol)$Symbol)
        listOfZeros:List(%):=concat([ root ], listOfZeros)
      listOfZeros

  1 == 1$K
```

```
0 == 0$K

newElement(pol:SUP(%),subF:%,inName:Symbol): % ==
    -- pol is an irreducible polynomial over the field extension
    -- given by subF.
    -- The output of this function is a root of pol.
  dp:=degree pol
  one?(dp) =>
    listCoef:=coefficients(pol)
    one?(#listCoef) => 0
    - last(listCoef) / first(listCoef)
  ground?(pol) => error "Cannot create a new element with a constant"
  d:PI := (dp pretend PI) * extDegree(subF)
  [monomial(1$%,1),pol,d,subF,inName] :: Rep

newElement(poll:SUP(%),inName:Symbol)==
  newElement(poll,localTower,inName)

newElement(elPol:SUP(%),pol:SUP(%),d:PI,subF:%,inName:Symbol): % ==
  [elPol, pol,d,subF,inName] :: Rep

--Field operations
inv(a)==
  a case K => inv(a)$K
  aRecEl:= (a pretend recRep).recEl
  aDefPoly:= (a pretend recRep).recTower
  aInv := extendedEuclidean( aRecEl , aDefPoly, 1 )
  aInv  case "failed" => error "PACOFF : division by zero"
  -- On doit retourner un Record reprsentant l'inverse de a.
  -- Ce Record est exactement le mme que celui de a sauf
  -- qu'il faut remplacer le polynme du selecteur recEl
  -- par le polynme reprsentant l'inverse de a :
  -- C'est ce que fait la fonction replaceRecEl.
  replaceRecEl( a , aInv.coef1 )

a:% / b:% == a * inv(b)

a:K * b:%==
  (a :: %) * b

b:% * a:K == a*b

a:% - b:% ==
  a + (-b)

a:% * b:Fraction(Integer) ==
  bn:=numer b
  bd:=denom b
  ebn:%:= bn * 1$%
  ebd:%:= bd * 1$%
```

```
    a * ebn * inv(ebd)

  -a:% ==
     a case K => -$K a
     [-$SUP(%) (a pretend recRep).recEl,_
      (a pretend recRep).recTower,_
      (a pretend recRep).recDeg,_
      (a pretend recRep).recPrevTower,_
      (a pretend recRep).recName ]

  bb:% = aa:% ==
    b:=down bb
    a:=down aa
    ^( extDegree(b) =$NNI extDegree(a) ) => false
    (b case K)  =>  ( (retract a)@K  =$K (retract b)@K )
    rda := a :: recRep
    rdb := b :: recRep
    not (rda.recTower =$SUP(%) rdb.recTower) => false
    rdb.recEl =$SUP(%) rda.recEl

  zero?(a:%) ==
    da:=down a  -- just to be sure !!!
    ^(da case K) => false
    zero?(da)$K

  one?(a:%) ==
    da:= down a  -- just to be sure !!!
    ^(da case K) => false
    one?(da)$K

  --Coerce Functions

  coerce(a:K):% == a

  retractIfCan(a:%):Union(Integer,"failed")==
    a case K => retractIfCan(a)$K
    "failed"

  retractIfCan(a:%):Union(K,"failed")==
    a case K => a
    "failed"

  coerce(a:%):OutputForm ==
    a case K => ((retract a)@K) ::OutputForm
    outputForm((a pretend recRep).recEl,_
               ((a pretend recRep).recName)::OutputForm) $SUP(%)

  fullOutput(a:%):OutputForm==
    a case K => ((retract a)@K) ::OutputForm
    (a pretend recRep)::OutputForm
```

```
    definingPolynomial(a:%): SUP % ==
      a case K => monomial(1,1)$SUP(%)
      (a pretend recRep).recTower

    extDegree(a:%): PI ==
      a case K => 1
      (a pretend recRep).recDeg

    previousTower(a:%):% ==
      a case K => error "No previous extension for ground field element"
      (a pretend recRep).recPrevTower

    name(a:%):Symbol ==
      a case K => error "No name for ground field element"
      (a pretend recRep).recName

    -- function related to the ground field

    characteristic == characteristic()$K
```

———-

— PACRAT.dotabb —

```
"PACRAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=PRODUCT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"PACRAT" -> "ALIST"
```

———-

Chapter 18

Chapter Q

18.1 domain QFORM QuadraticForm

— QuadraticForm.input —

```
)set break resume
)sys rm -f QuadraticForm.output
)spool QuadraticForm.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show QuadraticForm
--R QuadraticForm(n: PositiveInteger,K: Field)  is a domain constructor
--R Abbreviation for QuadraticForm is QFORM
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for QFORM
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Integer,%) -> %               ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 0 : () -> %                          coerce : % -> OutputForm
--R ?.? : (%,DirectProduct(n,K)) -> K    hash : % -> SingleInteger
--R latex : % -> String                  matrix : % -> SquareMatrix(n,K)
--R sample : () -> %                     zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R quadraticForm : SquareMatrix(n,K) -> %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
```

```
--E 1

)spool
)lisp (bye)
```

———-


— **QuadraticForm.help** —

```
====================================================================
QuadraticForm examples
====================================================================

See Also:
o )show QuadraticForm
```

———-

18.1.1 QuadraticForm (QFORM)



See

⇒ “CliffordAlgebra” (CLIF) 4.5.12 on page 388

Exports:

0	coerce	hash	latex	matrix
quadraticForm	sample	subtractIfCan	zero?	?~=?
?*?	?.?	?+?	?-?	-?
?=?				

— **domain QFORM QuadraticForm** —

```
)abbrev domain QFORM QuadraticForm
++ Author: Stephen M. Watt
++ Date Created: August 1988
++ Date Last Updated: May 17, 1991
```

```
++ Basic Operations: quadraticForm, elt
++ Related Domains: Matrix, SquareMatrix
++ Also See:
++ AMS Classifications:
++ Keywords: quadratic form
++ Examples:
++ References:
++
++ Description:
++ This domain provides modest support for quadratic forms.

QuadraticForm(n, K): T == Impl where
    n: PositiveInteger
    K: Field
    SM ==> SquareMatrix
    V  ==> DirectProduct

    T ==> AbelianGroup with
        quadraticForm: SM(n, K) -> %
            ++ quadraticForm(m) creates a quadratic form from a symmetric,
            ++ square matrix m.
        matrix: % -> SM(n, K)
            ++ matrix(qf) creates a square matrix from the quadratic form qf.
        elt: (%, V(n, K)) -> K
            ++ elt(qf,v) evaluates the quadratic form qf on the vector v,
            ++ producing a scalar.

    Impl ==> SM(n,K) add
        Rep := SM(n,K)

        quadraticForm m ==
            not symmetric? m =>
                error "quadraticForm requires a symmetric matrix"
            m::%
        matrix q == q pretend SM(n,K)
        elt(q,v) == dot(v, (matrix q * v))
```

———-

— QFORM.dotabb —

```
"QFORM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=QFORM"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"QFORM" -> "FIELD"
```

———-

18.2 domain QALGSET QuasiAlgebraicSet

— **QuasiAlgebraicSet.input** —

```
)set break resume
)sys rm -f QuasiAlgebraicSet.output
)spool QuasiAlgebraicSet.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show QuasiAlgebraicSet
--R
--R QuasiAlgebraicSet(R: GcdDomain,Var: OrderedSet,Expon: OrderedAbelianMonoidSup,Dpoly: Polynom
--R Abbreviation for QuasiAlgebraicSet is QALGSET
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for QALGSET
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R definingInequation : % -> Dpoly       empty : () -> %
--R empty? : % -> Boolean                 hash : % -> SingleInteger
--R idealSimplify : % -> %                latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R definingEquations : % -> List(Dpoly)
--R quasiAlgebraicSet : (List(Dpoly),Dpoly) -> %
--R setStatus : (%,Union(Boolean,"failed")) -> %
--R simplify : % -> % if R has CHARZ and R has EUCDOM
--R status : % -> Union(Boolean,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **QuasiAlgebraicSet.help** —

```
==========================================================================
QuasiAlgebraicSet examples
==========================================================================

See Also:
o )show QuasiAlgebraicSet
```

———-

18.2.1 QuasiAlgebraicSet (QALGSET)



Exports:

coerce	definingEquations	definingInequation	empty
empty?	hash	idealSimplify	latex
quasiAlgebraicSet	setStatus	simplify	status
?=?	?~=?		

— domain QALGSET QuasiAlgebraicSet —

```
)abbrev domain QALGSET QuasiAlgebraicSet
++ Author:  William Sit
++ Date Created: March 13, 1992
++ Date Last Updated: June 12, 1992
++ Basic Operations:
++ Related Constructors:GroebnerPackage
++ See Also: QuasiAlgebraicSet2
++ AMS Classifications:
++ Keywords: Zariski closed sets, quasi-algebraic sets
++ References:William Sit, "An Algorithm for Parametric Linear Systems"
++            J. Sym. Comp., April, 1992
++ Description:
++ \spadtype{QuasiAlgebraicSet} constructs a domain representing
++ quasi-algebraic sets, which is the intersection of a Zariski
++ closed set, defined as the common zeros of a given list of
++ polynomials (the defining polynomials for equations), and a principal
++ Zariski open set, defined as the complement of the common
++ zeros of a polynomial f (the defining polynomial for the inequation).
++ This domain provides simplification of a user-given representation
++ using groebner basis computations.
++ There are two simplification routines: the first function
++ \spadfun{idealSimplify}  uses groebner
++ basis of ideals alone, while the second, \spadfun{simplify} uses both
++ groebner basis and factorization.  The resulting defining equations L
```

```
++ always form a groebner basis, and the resulting defining
++ inequation f is always reduced.  The function \spadfun{simplify} may
++ be applied several times if desired.   A third simplification
++ routine \spadfun{radicalSimplify} is provided in
++ \spadtype{QuasiAlgebraicSet2}  for comparison study only,
++ as it is inefficient compared to the other two, as well as is
++ restricted to only certain coefficient domains.  For detail analysis
++ and a comparison of the three methods, please consult the reference
++ cited.
++
++ A polynomial function q defined on the quasi-algebraic set
++ is equivalent to its reduced form with respect to L.  While
++ this may be obtained using the usual normal form
++ algorithm, there is no canonical form for q.
++
++ The ordering in groebner basis computation is determined by
++ the data type of the input polynomials.  If it is possible
++ we suggest to use refinements of total degree orderings.

QuasiAlgebraicSet(R, Var,Expon,Dpoly) : C == T
 where
   R         :  GcdDomain
   Expon     :  OrderedAbelianMonoidSup
   Var       :  OrderedSet
   Dpoly     :  PolynomialCategory(R,Expon,Var)
   NNI      ==> NonNegativeInteger
   newExpon ==> Product(NNI,Expon)
   newPoly  ==> PolynomialRing(R,newExpon)
   Ex       ==> OutputForm
   mrf      ==> MultivariateFactorize(Var,Expon,R,Dpoly)
   Status   ==> Union(Boolean,"failed") -- empty or not, or don't know

   C == Join(SetCategory, CoercibleTo OutputForm) with
  --- should be Object instead of SetCategory, bug in LIST Object ---
  --- equality is not implemented ---
     empty: () -> $
       ++ empty() returns the empty quasi-algebraic set
     quasiAlgebraicSet:   (List Dpoly, Dpoly) -> $
       ++ quasiAlgebraicSet(pl,q) returns the quasi-algebraic set
       ++ with defining equations p = 0 for p belonging to the list pl, and
       ++ defining inequation q ^= 0.
     status: $ -> Status
       ++ status(s) returns true if the quasi-algebraic set is empty,
       ++ false if it is not, and "failed" if not yet known
     setStatus: ($, Status) -> $
       ++ setStatus(s,t) returns the same representation for s, but
       ++ asserts the following: if t is true, then s is empty,
       ++ if t is false, then s is non-empty, and if t = "failed",
       ++ then no assertion is made (that is, "don't know").
       ++ Note: for internal use only, with care.
```

```
    empty?          :   $   -> Boolean
      ++ empty?(s) returns
      ++ true if the quasialgebraic set s has no points,
      ++ and false otherwise.
    definingEquations: $ -> List Dpoly
      ++ definingEquations(s) returns a list of defining polynomials
      ++ for equations, that is, for the Zariski closed part of s.
    definingInequation: $ -> Dpoly
      ++ definingInequation(s) returns a single defining polynomial for the
      ++ inequation, that is, the Zariski open part of s.
    idealSimplify:$ -> $
      ++ idealSimplify(s) returns a different and presumably simpler
      ++ representation of s with the defining polynomials for the
      ++ equations
      ++ forming a groebner basis, and the defining polynomial for the
      ++ inequation reduced with respect to the basis, using Buchberger's
      ++ algorithm.
    if (R has EuclideanDomain) and (R has CharacteristicZero) then
      simplify:$ -> $
        ++ simplify(s) returns a different and presumably simpler
        ++ representation of s with the defining polynomials for the
        ++ equations
        ++ forming a groebner basis, and the defining polynomial for the
        ++ inequation reduced with respect to the basis, using a heuristic
        ++ algorithm based on factoring.
  T  == add
    Rep := Record(status:Status,zero:List Dpoly, nzero:Dpoly)
    x:$

    import GroebnerPackage(R,Expon,Var,Dpoly)
    import GroebnerPackage(R,newExpon,Var,newPoly)
    import GroebnerInternalPackage(R,Expon,Var,Dpoly)

                      ----  Local Functions  ----

    minset   : List List Dpoly -> List List Dpoly
    overset? : (List Dpoly, List List Dpoly) -> Boolean
    npoly    : Dpoly           ->  newPoly
    oldpoly  : newPoly         ->  Union(Dpoly,"failed")


    if (R has EuclideanDomain) and (R has CharacteristicZero) then
      factorset (y:Dpoly):List Dpoly ==
        ground? y => []
        [j.factor for j in factors factor$mrf  y]

      simplify x ==
        if x.status case "failed" then
          x:=quasiAlgebraicSet(zro:=groebner x.zero, redPol(x.nzero,zro))
        (pnzero:=x.nzero)=0 => empty()
```

```
    nzro:=factorset pnzero
    mset:=minset [factorset p for p in x.zero]
    mset:=[setDifference(s,nzro) for s in mset]
    zro:=groebner [*/s for s in mset]
    member? (1$Dpoly, zro) => empty()
    [x.status, zro, primitivePart redPol(*/nzro, zro)]

npoly(f:Dpoly) : newPoly ==
  zero? f => 0
  monomial(leadingCoefficient f,makeprod(0,degree f))$newPoly +
        npoly(reductum f)

oldpoly(q:newPoly) : Union(Dpoly,"failed") ==
  q=0$newPoly => 0$Dpoly
  dq:newExpon:=degree q
  n:NNI:=selectfirst (dq)
  n^=0 => "failed"
  ((g:=oldpoly reductum q) case "failed") => "failed"
  monomial(leadingCoefficient q,selectsecond dq)$Dpoly + (g::Dpoly)

coerce x ==
  x.status = true => "Empty"::Ex
  bracket [[hconcat(f::Ex, " = 0"::Ex) for f in x.zero ]::Ex,
            hconcat( x.nzero::Ex, " != 0"::Ex)]

empty? x ==
  if x.status case "failed" then x:=idealSimplify x
  x.status :: Boolean

empty() == [true::Status, [1$Dpoly], 0$Dpoly]
status x == x.status
setStatus(x,t) == [t,x.zero,x.nzero]
definingEquations x == x.zero
definingInequation x == x.nzero
quasiAlgebraicSet(z0,n0) == ["failed", z0, n0]

idealSimplify x ==
  x.status case Boolean => x
  z0:= x.zero
  n0:= x.nzero
  empty? z0 => [false, z0, n0]
  member? (1$Dpoly, z0) => empty()
  tp:newPoly:=(monomial(1,makeprod(1,0$Expon))$newPoly * npoly n0)-1
  ngb:=groebner concat(tp, [npoly g for g in z0])
  member? (1$newPoly, ngb) => empty()
  gb:List Dpoly:=nil
  while not empty? ngb repeat
    if ((f:=oldpoly ngb.first) case Dpoly) then gb:=concat(f, gb)
    ngb:=ngb.rest
  [false::Status, gb, primitivePart redPol(n0, gb)]
```

```
    minset lset ==
      empty? lset => lset
      [s for s  in lset | ^(overset?(s,lset))]

    overset?(p,qlist) ==
      empty? qlist => false
      or/[(brace$(Set Dpoly) q) <$(Set Dpoly) (brace$(Set Dpoly) p) for q in qlist]
```

———-

— **QALGSET.dotabb** —

```
"QALGSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=QALGSET"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"QALGSET" -> "PFECAT"
```

———-

18.3 domain QUAT Quaternion

— **Quaternion.input** —

```
)set break resume
)sys rm -f Quaternion.output
)spool Quaternion.output
)set message test on
)set message auto off
)clear all
--S 1 of 13
q := quatern(2/11,-8,3/4,1)
--R
--R
--R         2        3
--R   (1)  -- - 8i + - j + k
--R        11        4
--R                                          Type: Quaternion(Fraction(Integer))
--E 1

--S 2 of 13
[real q, imagI q, imagJ q, imagK q]
--R
--R
```

```
--R          2     3
--R   (2)  [--,- 8,-,1]
--R         11     4
--R                                                Type: List(Fraction(Integer))
--E 2

--S 3 of 13
inv q
--R
--R
--R          352     15488      484       1936
--R   (3)  ------ + ------ i - ----- j - ------ k
--R        126993   126993     42331     126993
--R                                           Type: Quaternion(Fraction(Integer))
--E 3

--S 4 of 13
q^6
--R
--R
--R          2029490709319345   48251690851     144755072553     48251690851
--R   (4)  - ---------------- - ----------- i + ------------ j + ----------- k
--R             7256313856        1288408         41229056         10307264
--R                                           Type: Quaternion(Fraction(Integer))
--E 4

--S 5 of 13
r := quatern(-2,3,23/9,-89); q + r
--R
--R
--R          20        119
--R   (5)  - -- - 5i + --- j - 88k
--R          11         36
--R                                           Type: Quaternion(Fraction(Integer))
--E 5

--S 6 of 13
q * r - r * q
--R
--R
--R          2495             817
--R   (6)  - ---- i - 1418j - --- k
--R           18               18
--R                                           Type: Quaternion(Fraction(Integer))
--E 6

--S 7 of 13
i:=quatern(0,1,0,0)
--R
--R
```

```
--R   (7)  i
--R                                                    Type: Quaternion(Integer)
--E 7

--S 8 of 13
j:=quatern(0,0,1,0)
--R
--R
--R   (8)  j
--R                                                    Type: Quaternion(Integer)
--E 8

--S 9 of 13
k:=quatern(0,0,0,1)
--R
--R
--R   (9)  k
--R                                                    Type: Quaternion(Integer)
--E 9

--S 10 of 13
[i*i, j*j, k*k, i*j, j*k, k*i, q*i]
--R
--R
--R                                  2         3
--R   (10)  [- 1,- 1,- 1,k,i,j,8 + -- i + j - - k]
--R                                 11         4
--R                                    Type: List(Quaternion(Fraction(Integer)))
--E 10

--S 11 of 13
norm q
--R
--R
--R         126993
--R   (11)  ------
--R          1936
--R                                                      Type: Fraction(Integer)
--E 11

--S 12 of 13
conjugate q
--R
--R
--R          2        3
--R   (12)  -- + 8i - - j - k
--R         11        4
--R                                           Type: Quaternion(Fraction(Integer))
--E 12
```

```
--S 13 of 13
q * %
--R
--R
--R         126993
--R   (13)  ------
--R          1936
--R                                          Type: Quaternion(Fraction(Integer))
--E 13
)spool
)lisp (bye)
```

———-

— Quaternion.help —

```
=====================================================================
Quaternion examples
=====================================================================

The domain constructor Quaternion implements quaternions over
commutative rings.

The basic operation for creating quaternions is quatern.  This is a
quaternion over the rational numbers.

  q := quatern(2/11,-8,3/4,1)
     2        3
    -- - 8i + - j + k
    11        4
                        Type: Quaternion Fraction Integer

The four arguments are the real part, the i imaginary part, the j
imaginary part, and the k imaginary part, respectively.

  [real q, imagI q, imagJ q, imagK q]
      2     3
    [--,- 8,-,1]
     11     4
                        Type: List Fraction Integer

Because q is over the rationals (and nonzero), you can invert it.

  inv q
      352     15488      484       1936
    ------ + ------ i - ----- j - ------ k
    126993   126993     42331     126993
                        Type: Quaternion Fraction Integer
```

```
The usual arithmetic (ring) operations are available

  q^6
      2029490709319345   48251690851     144755072553     48251690851
    - ---------------- - ----------- i + ------------ j + ----------- k
         7256313856        1288408          41229056         10307264
                                Type: Quaternion Fraction Integer

  r := quatern(-2,3,23/9,-89); q + r
      20        119
    - -- - 5i + --- j - 88k
      11         36
                                Type: Quaternion Fraction Integer

In general, multiplication is not commutative.

  q * r - r * q
      2495             817
    - ---- i - 1418j - --- k
       18               18
                                 Type: Quaternion Fraction Integer

There are no predefined constants for the imaginary i, j, and k parts,
but you can easily define them.

  i:=quatern(0,1,0,0)
    i
                                 Type: Quaternion Integer

  j:=quatern(0,0,1,0)
    j
                                 Type: Quaternion Integer

  k:=quatern(0,0,0,1)
    k
                                 Type: Quaternion Integer

These satisfy the normal identities.

  [i*i, j*j, k*k, i*j, j*k, k*i, q*i]
                                 2         3
     [- 1,- 1,- 1,k,i,j,8 + -- i + j - - k]
                               11         4
                                Type: List Quaternion Fraction Integer

The norm is the quaternion times its conjugate.

  norm q
    126993
    ------
```


```
     1936
                                Type: Fraction Integer

  conjugate q
      2        3
     -- + 8i - - j - k
     11        4
                                Type: Quaternion Fraction Integer

  q * %
     126993
     ------
      1936
                                Type: Quaternion Fraction Integer

See Also:
o )help Octonion
o )help Complex
o )help CliffordAlgebra
o )show Quaternion
```

18.3.1 Quaternion (QUAT)



Exports:

0	1	abs	characteristic	charthRoot
coerce	conjugate	convert	D	differentiate
eval	hash	imagI	imagJ	imagK
inv	latex	map	max	min
norm	one?	quatern	rational	rational?
rationalIfCan	real	recip	reducedSystem	retract
retractIfCan	sample	subtractIfCan	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?	?<?	?<=?	?>?
?>=?	?.?			

— domain QUAT Quaternion —

```
)abbrev domain QUAT Quaternion
++ Author: Robert S. Sutor
++ Date Created: 23 May 1990
++ Change History:
++   10 September 1990
++ Basic Operations: (Algebra)
++   abs, conjugate, imagI, imagJ, imagK, norm, quatern, rational,
++   rational?, real
++ Related Constructors: QuaternionCategoryFunctions2
++ Also See: QuaternionCategory, DivisionRing
++ AMS Classifications: 11R52
++ Keywords: quaternions, division ring, algebra
++ Description:
++ \spadtype{Quaternion} implements quaternions over a
++ commutative ring. The main constructor function is \spadfun{quatern}
++ which takes 4 arguments: the real part, the i imaginary part, the j
++ imaginary part and the k imaginary part.

Quaternion(R:CommutativeRing): QuaternionCategory(R) == add
  Rep := Record(r:R,i:R,j:R,k:R)

  0 == [0,0,0,0]
  1 == [1,0,0,0]

  a,b,c,d : R
  x,y : $

  real  x == x.r
  imagI x == x.i
  imagJ x == x.j
  imagK x == x.k

  quatern(a,b,c,d) == [a,b,c,d]

  x * y == [x.r*y.r-x.i*y.i-x.j*y.j-x.k*y.k,
              x.r*y.i+x.i*y.r+x.j*y.k-x.k*y.j,
```

```
                x.r*y.j+x.j*y.r+x.k*y.i-x.i*y.k,
                  x.r*y.k+x.k*y.r+x.i*y.j-x.j*y.i]
```

— QUAT.dotabb —

```
"QUAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=QUAT"]
"QUATCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=QUATCAT"]
"QUAT" -> "QUATCAT"
```

18.4 domain QEQUAT QueryEquation

— QueryEquation.input —

```
)set break resume
)sys rm -f QueryEquation.output
)spool QueryEquation.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show QueryEquation
--R QueryEquation  is a domain constructor
--R Abbreviation for QueryEquation is QEQUAT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for QEQUAT
--R
--R------------------------------ Operations ------------------------------
--R coerce : % -> OutputForm              equation : (Symbol,String) -> %
--R value : % -> String                   variable : % -> Symbol
--R
--E 1

)spool
)lisp (bye)
```


— QueryEquation.help —

```
================================================================
QueryEquation examples
================================================================

See Also:
o )show QueryEquation
```

———-

18.4.1 QueryEquation (QEQUAT)



See

⇒ “DataList” (DLIST) 5.2.1 on page 447
⇒ “IndexCard” (ICARD) 10.2.1 on page 1163
⇒ “Database” (DBASE) 5.1.1 on page 442

Exports:
coerce equation value variable

— domain QEQUAT QueryEquation —

```
)abbrev domain QEQUAT QueryEquation
++ Author: Mark Botch
++ Description:
++ This domain implements simple database queries

QueryEquation(): Exports == Implementation where
  Exports == CoercibleTo(OutputForm) with
    equation: (Symbol,String) -> %
      ++ equation(s,"a") creates a new equation.
    variable: % -> Symbol
      ++ variable(q) returns the variable (i.e. left hand side) of \axiom{q}.
    value: % -> String
      ++ value(q) returns the value (i.e. right hand side) of \axiom{q}.
  Implementation == add
```

```
    Rep := Record(var:Symbol, val:String)
    coerce(u) == coerce(u.var)$Symbol = coerce(u.val)$String
    equation(x,s) == [x,s]
    variable q == q.var
    value q == q.val
```

———-

— **QEQUAT.dotabb** —

```
"QEQUAT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=QEQUAT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"QEQUAT" -> "ALIST"
```

———-

18.5 domain QUEUE Queue

— **Queue.input** —

```
)set break resume
)sys rm -f Queue.output
)spool Queue.output
)set message test on
)set message auto off
)clear all

--S 1 of 46
a:Queue INT:= queue [1,2,3,4,5]
--R
--R
--R   (1)  [1,2,3,4,5]
--R                                                    Type: Queue(Integer)
--E 1

--S 2 of 46
dequeue! a
--R
--R
--R   (2)  1
--R                                                 Type: PositiveInteger
--E 2

--S 3 of 46
```

```
a
--R
--R
--R   (3)  [2,3,4,5]
--R                                                    Type: Queue(Integer)
--E 3

--S 4 of 46
extract! a
--R
--R
--R   (4)  2
--R                                                   Type: PositiveInteger
--E 4

--S 5 of 46
a
--R
--R
--R   (5)  [3,4,5]
--R                                                    Type: Queue(Integer)
--E 5

--S 6 of 46
enqueue!(9,a)
--R
--R
--R   (6)  9
--R                                                   Type: PositiveInteger
--E 6

--S 7 of 46
a
--R
--R
--R   (7)  [3,4,5,9]
--R                                                    Type: Queue(Integer)
--E 7

--S 8 of 46
insert!(8,a)
--R
--R
--R   (8)  [3,4,5,9,8]
--R                                                    Type: Queue(Integer)
--E 8

--S 9 of 46
a
--R
```

```
--R
--R   (9)  [3,4,5,9,8]
--R                                                    Type: Queue(Integer)
--E 9

--S 10 of 46
inspect a
--R
--R
--R   (10)  3
--R                                                  Type: PositiveInteger
--E 10

--S 11 of 46
empty? a
--R
--R
--R   (11)  false
--R                                                          Type: Boolean
--E 11

--S 12 of 46
front a
--R
--R
--R   (12)  3
--R                                                  Type: PositiveInteger
--E 12

--S 13 of 46
back a
--R
--R
--R   (13)  8
--R                                                  Type: PositiveInteger
--E 13

--S 14 of 46
rotate! a
--R
--R
--R   (14)  [4,5,9,8,3]
--R                                                    Type: Queue(Integer)
--E 14

--S 15 of 46
#a
--R
--R
--R   (15)  5
```

```
--R                                                    Type: PositiveInteger
--E 15

--S 16 of 46
length a
--R
--R
--R   (16)  5
--R                                                    Type: PositiveInteger
--E 16

--S 17 of 46
less?(a,9)
--R
--R
--R   (17)  true
--R                                                           Type: Boolean
--E 17

--S 18 of 46
more?(a,9)
--R
--R
--R   (18)  false
--R                                                           Type: Boolean
--E 18

--S 19 of 46
size?(a,#a)
--R
--R
--R   (19)  true
--R                                                           Type: Boolean
--E 19

--S 20 of 46
size?(a,9)
--R
--R
--R   (20)  false
--R                                                           Type: Boolean
--E 20

--S 21 of 46
parts a
--R
--R
--R   (21)  [4,5,9,8,3]
--R                                                     Type: List(Integer)
--E 21
```

```
--S 22 of 46
bag([1,2,3,4,5])$Queue(INT)
--R
--R
--R   (22)  [1,2,3,4,5]
--R                                                    Type: Queue(Integer)
--E 22

--S 23 of 46
b:=empty()$(Queue INT)
--R
--R
--R   (23)  []
--R                                                    Type: Queue(Integer)
--E 23

--S 24 of 46
empty? b
--R
--R
--R   (24)  true
--R                                                           Type: Boolean
--E 24

--S 25 of 46
sample()$Queue(INT)
--R
--R
--R   (25)  []
--R                                                    Type: Queue(Integer)
--E 25

--S 26 of 46
c:=copy a
--R
--R
--R   (26)  [4,5,9,8,3]
--R                                                    Type: Queue(Integer)
--E 26

--S 27 of 46
eq?(a,c)
--R
--R
--R   (27)  false
--R                                                           Type: Boolean
--E 27

--S 28 of 46
```

```
eq?(a,a)
--R
--R
--R   (28)  true
--R                                                    Type: Boolean
--E 28

--S 29 of 46
(a=c)@Boolean
--R
--R
--R   (29)  true
--R                                                    Type: Boolean
--E 29

--S 30 of 46
(a=a)@Boolean
--R
--R
--R   (30)  true
--R                                                    Type: Boolean
--E 30

--S 31 of 46
a~=c
--R
--R
--R   (31)  false
--R                                                    Type: Boolean
--E 31

--S 32 of 46
any?(x+->(x=4),a)
--R
--R
--R   (32)  true
--R                                                    Type: Boolean
--E 32

--S 33 of 46
any?(x+->(x=11),a)
--R
--R
--R   (33)  false
--R                                                    Type: Boolean
--E 33

--S 34 of 46
every?(x+->(x=11),a)
--R
```

```
--R
--R   (34)  false
--R                                                          Type: Boolean
--E 34

--S 35 of 46
count(4,a)
--R
--R
--R   (35)  1
--R                                                  Type: PositiveInteger
--E 35

--S 36 of 46
count(x+->(x>2),a)
--R
--R
--R   (36)  5
--R                                                  Type: PositiveInteger
--E 36

--S 37 of 46
map(x+->x+10,a)
--R
--R
--R   (37)  [14,15,19,18,13]
--R                                                   Type: Queue(Integer)
--E 37

--S 38 of 46
a
--R
--R
--R   (38)  [4,5,9,8,3]
--R                                                   Type: Queue(Integer)
--E 38

--S 39 of 46
map!(x+->x+10,a)
--R
--R
--R   (39)  [14,15,19,18,13]
--R                                                   Type: Queue(Integer)
--E 39

--S 40 of 46
a
--R
--R
--R   (40)  [14,15,19,18,13]
```

```
--R                                                          Type: Queue(Integer)
--E 40

--S 41 of 46
members a
--R
--R
--R   (41)  [14,15,19,18,13]
--R                                                           Type: List(Integer)
--E 41

--S 42 of 46
member?(14,a)
--R
--R
--R   (42)  true
--R                                                                  Type: Boolean
--E 42

--S 43 of 46
coerce a
--R
--R
--R   (43)  [14,15,19,18,13]
--R                                                             Type: OutputForm
--E 43

--S 44 of 46
hash a
--R
--R
--I   (44)  4999531
--R                                                           Type: SingleInteger
--E 44

--S 45 of 46
latex a
--R
--R
--R   (45)  "\mbox{\bf Unimplemented}"
--R                                                                    Type: String
--E 45

--S 46 of 46
)show Queue
--R
--R Queue(S: SetCategory)  is a domain constructor
--R Abbreviation for Queue is QUEUE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for QUEUE
```

```
--R
--R------------------------------ Operations ------------------------------
--R back : % -> S                          bag : List(S) -> %
--R copy : % -> %                          dequeue! : % -> S
--R empty : () -> %                        empty? : % -> Boolean
--R enqueue! : (S,%) -> S                  eq? : (%,%) -> Boolean
--R extract! : % -> S                      front : % -> S
--R insert! : (S,%) -> %                   inspect : % -> S
--R length : % -> NonNegativeInteger       map : ((S -> S),%) -> %
--R queue : List(S) -> %                   rotate! : % -> %
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 46


)spool
)lisp (bye)
```

———-

— Queue.help —

```
=====================================================================
Queue examples
=====================================================================

A Queue object is represented as a list ordered by first-in, first-out.
```

```
It operates like a line of people, where the "next" person is the one
at the front of the line.

Here we create an queue of integers from a list. Notice that the
order in the list is the order in the queue.

   a:Queue INT:= queue [1,2,3,4,5]
      [1,2,3,4,5]

We can remove the top of the queue using dequeue!:

   dequeue! a
      1

Notice that the use of dequeue! is destructive (destructive operations
in Axiom usually end with ! to indicate that the underylying data
structure is changed).

   a
      [2,3,4,5]

The extract! operation is another name for the pop! operation and
has the same effect. This operation treats the queue as a BagAggregate:

   extract! a
      2

and you can see that it also has destructively modified the queue:

   a
      [3,4,5]

Next we use enqueue! to add a new element to the end of the queue:

   push!(9,a)
      9

Again, the push! operation is destructive so the queue is changed:

   a
      [3,4,5,9]

Another name for enqueue! is insert!, which treats the queue as a
BagAggregate:

   insert!(8,a)
      [3,4,5,9,8]

and it modifies the queue:
```

```
   a
      [3,4,5,9,8]
```

The inspect function returns the top of the queue without modification, viewed as a BagAggregate:

```
   inspect a
      8
```

The empty? operation returns true only if there are no element on the queue, otherwise it returns false:

```
   empty? a
      false
```

The front operation returns the front of the queue without modification:

```
   front a
      3
```

The back operation returns the back of the queue without modification:

```
   back a
      8
```

The rotate! operation moves the item at the front of the queue to the back of the queue:

```
   rotate! a
      [4,5,9,8,3]
```

The # (length) operation:

```
   #a
       5
```

The length operation does the same thing:

```
   length a
       5
```

The less? predicate will compare the queue length to an integer:

```
   less?(a,9)
        true
```

The more? predicate will compare the queue length to an integer:

```
   more?(a,9)
        false
```

```
The size? operation will compare the queue length to an integer:

   size?(a,#a)
        true

and since the last computation must alwasy be true we try:

   size?(a,9)
        false

The parts function will return  the queue as a list of its elements:

   parts a
        [8,9,3,4,5]

If we have a BagAggregate of elements we can use it to construct a queue:

   bag([1,2,3,4,5])$Queue(INT)
        [1,2,3,4,5]

The empty function will construct an empty queue of a given type:

   b:=empty()$(Queue INT)
        []

and the empty? predicate allows us to find out if a queue is empty:

   empty? b
        true

The sample function returns a sample, empty queue:

   sample()$Queue(INT)
        []

We can copy a queue and it does not share storage so subsequent
modifications of the original queue will not affect the copy:

   c:=copy a
        [4,5,9,8,3]

The eq? function is only true if the lists are the same reference,
so even though c is a copy of a, they are not the same:

   eq?(a,c)
        false

However, a clearly shares a reference with itself:
```

```
   eq?(a,a)
        true
```

But we can compare a and c for equality:

```
   (a=c)@Boolean
        true
```

and clearly a is equal to itself:

```
   (a=a)@Boolean
        true
```

and since a and c are equal, they are clearly NOT not-equal:

```
   a~=c
        false
```

We can use the any? function to see if a predicate is true for any element:

```
   any?(x+->(x=4),a)
        true
```

or false for every element:

```
   any?(x+->(x=11),a)
        false
```

We can use the every? function to check every element satisfies a predicate:

```
   every?(x+->(x=11),a)
        false
```

We can count the elements that are equal to an argument of this type:

```
   count(4,a)
        1
```

or we can count against a boolean function:

```
   count(x+->(x>2),a)
        5
```

You can also map a function over every element, returning a new queue:

```
   map(x+->x+10,a)
        [14,15,19,18,13]
```

Notice that the orignal queue is unchanged:

```
   a
        [4,5,9,8,3]

You can use map! to map a function over every element and change
the original queue since map! is destructive:

   map!(x+->x+10,a)
       [14,15,19,18,13]
o
Notice that the orignal queue has been changed:

   a
       [14,15,19,18,13]

The member function can also get the element of the queue as a list:

   members a
       [18,19,13,14,15]


and using member? we can test if the queue holds a given element:

   member?(14,a)
       true


See Also:
o )show Stack
o )show ArrayStack
o )show Queue
o )show Dequeue
o )show Heap
o )show BagAggregate
```

———————-

18.5.1 Queue (QUEUE)



See

⇒ "Stack" (STACK) 20.28.1 on page 2530
⇒ "ArrayStack" (ASTACK) 2.10.1 on page 65
⇒ "Dequeue" (DEQUEUE) 5.5.1 on page 499
⇒ "Heap" (HEAP) 9.2.1 on page 1104

Exports:

any?	back	bag	coerce	copy
count	dequeue!	empty	empty?	enqueue!
eq?	eval	every?	extract!	front
hash	insert!	inspect	latex	length
less?	map	map!	member?	members
more?	parts	queue	rotate!	sample
size?	#?	?=?	?~=?	

— domain QUEUE Queue —

```
)abbrev domain QUEUE Queue
++ Author: Michael Monagan and Stephen Watt
++ Date Created:June 86 and July 87
++ Date Last Updated:Feb 92
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Linked List implementation of a Queue
--% Dequeue and Heap data types

Queue(S:SetCategory): QueueAggregate S with
    queue: List S -> %
      ++ queue([x,y,...,z]) creates a queue with first (top)
```

```
      ++ element x, second element y,...,and last (bottom) element z.
      ++
      ++E e:Queue INT:= queue [1,2,3,4,5]

 -- Inherited Signatures repeated for examples documentation

    dequeue_! : % -> S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X dequeue! a
      ++X a
    extract_! : % -> S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X extract! a
      ++X a
    enqueue_! : (S,%) -> S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X enqueue! (9,a)
      ++X a
    insert_! : (S,%) -> %
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X insert! (8,a)
      ++X a
    inspect : % -> S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X inspect a
    front : % -> S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X front a
    back : % -> S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X back a
    rotate_! : % -> %
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X rotate! a
    length : % -> NonNegativeInteger
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X length a
    less? : (%,NonNegativeInteger) -> Boolean
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X less?(a,9)
```

```
more? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Queue INT:= queue [1,2,3,4,5]
  ++X more?(a,9)
size? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Queue INT:= queue [1,2,3,4,5]
  ++X size?(a,5)
bag : List S -> %
  ++
  ++X bag([1,2,3,4,5])$Queue(INT)
empty? : % -> Boolean
  ++
  ++X a:Queue INT:= queue [1,2,3,4,5]
  ++X empty? a
empty : () -> %
  ++
  ++X b:=empty()$(Queue INT)
sample : () -> %
  ++
  ++X sample()$Queue(INT)
copy : % -> %
  ++
  ++X a:Queue INT:= queue [1,2,3,4,5]
  ++X copy a
eq? : (%,%) -> Boolean
  ++
  ++X a:Queue INT:= queue [1,2,3,4,5]
  ++X b:=copy a
  ++X eq?(a,b)
map :  ((S -> S),%) -> %
  ++
  ++X a:Queue INT:= queue [1,2,3,4,5]
  ++X map(x+->x+10,a)
  ++X a
if $ has shallowlyMutable then
  map! :  ((S -> S),%) -> %
    ++
    ++X a:Queue INT:= queue [1,2,3,4,5]
    ++X map!(x+->x+10,a)
    ++X a
if S has SetCategory then
  latex : % -> String
    ++
    ++X a:Queue INT:= queue [1,2,3,4,5]
    ++X latex a
  hash : % -> SingleInteger
    ++
    ++X a:Queue INT:= queue [1,2,3,4,5]
    ++X hash a
```

```
    coerce : % -> OutputForm
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X coerce a
    "=": (%,%) -> Boolean
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X b:Queue INT:= queue [1,2,3,4,5]
      ++X (a=b)@Boolean
    "~=" : (%,%) -> Boolean
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X b:=copy a
      ++X (a~=b)
  if % has finiteAggregate then
    every? : ((S -> Boolean),%) -> Boolean
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X every?(x+->(x=4),a)
    any? : ((S -> Boolean),%) -> Boolean
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X any?(x+->(x=4),a)
    count :  ((S -> Boolean),%) -> NonNegativeInteger
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X count(x+->(x>2),a)
    _# : % -> NonNegativeInteger
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X #a
    parts : % -> List S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X parts a
    members : % -> List S
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X members a
  if % has finiteAggregate and S has SetCategory then
    member? : (S,%) -> Boolean
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X member?(3,a)
    count : (S,%) -> NonNegativeInteger
      ++
      ++X a:Queue INT:= queue [1,2,3,4,5]
      ++X count(4,a)

== Stack S add
```

```
    Rep := Reference List S
    lastTail==> LAST$Lisp
    enqueue_!(e,q) ==
        if null deref q then setref(q, list e)
        else lastTail.(deref q).rest := list e
        e
    insert_!(e,q) == (enqueue_!(e,q);q)
    dequeue_! q ==
        empty? q => error "empty queue"
        e := first deref q
        setref(q,rest deref q)
        e
    extract_! q == dequeue_! q
    rotate_! q == if empty? q then q else (enqueue_!(dequeue_! q,q); q)
    length q == # deref q
    front q == if empty? q then error "empty queue" else first deref q
    inspect q == front q
    back q == if empty? q then error "empty queue" else last deref q
    queue q == ref copy q
```

———-

— QUEUE.dotabb —

```
"QUEUE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=QUEUE"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"QUEUE" -> "FLAGG"
"QUEUE" -> "FLAGG-"
```

———-

Chapter 19

Chapter R

19.1 domain RADFF RadicalFunctionField

— RadicalFunctionField.input —

```
)set break resume
)sys rm -f RadicalFunctionField.output
)spool RadicalFunctionField.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show RadicalFunctionField
--R
--R RadicalFunctionField(F: UniqueFactorizationDomain,UP: UnivariatePolynomialCategory(F),UPUP: UnivariatePo
--R Abbreviation for RadicalFunctionField is RADFF
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RADFF
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Fraction(UP),%) -> %          ?*? : (%,Fraction(UP)) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       basis : () -> Vector(%)
--R branchPoint? : UP -> Boolean         branchPoint? : F -> Boolean
--R coerce : Fraction(UP) -> %           coerce : Integer -> %
--R coerce : % -> OutputForm             convert : UPUP -> %
--R convert : % -> UPUP                  definingPolynomial : () -> UPUP
```

```
--R discriminant : () -> Fraction(UP)     elt : (%,F,F) -> F
--R generator : () -> %                   genus : () -> NonNegativeInteger
--R hash : % -> SingleInteger             integral? : (%,UP) -> Boolean
--R integral? : (%,F) -> Boolean          integral? : % -> Boolean
--R integralBasis : () -> Vector(%)       latex : % -> String
--R lift : % -> UPUP                      norm : % -> Fraction(UP)
--R one? : % -> Boolean                   primitivePart : % -> %
--R ramified? : UP -> Boolean             ramified? : F -> Boolean
--R rank : () -> PositiveInteger          rationalPoint? : (F,F) -> Boolean
--R recip : % -> Union(%,"failed")        reduce : UPUP -> %
--R represents : (Vector(UP),UP) -> %     retract : % -> Fraction(UP)
--R sample : () -> %                      singular? : UP -> Boolean
--R singular? : F -> Boolean              trace : % -> Fraction(UP)
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Fraction(UP) has FIELD
--R ?*? : (Fraction(Integer),%) -> % if Fraction(UP) has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Integer) -> % if Fraction(UP) has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if Fraction(UP) has FIELD
--R D : % -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fraction(UP) has FFIELD
--R D : (%,NonNegativeInteger) -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fr
--R D : (%,Symbol) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Fraction(UP) has FIELD and Fraction(UP
--R D : (%,(Fraction(UP) -> Fraction(UP))) -> % if Fraction(UP) has FIELD
--R D : (%,(Fraction(UP) -> Fraction(UP)),NonNegativeInteger) -> % if Fraction(UP) has FIELD
--R ?^? : (%,Integer) -> % if Fraction(UP) has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R absolutelyIrreducible? : () -> Boolean
--R algSplitSimple : (%,(UP -> UP)) -> Record(num: %,den: UP,derivden: UP,gd: UP)
--R associates? : (%,%) -> Boolean if Fraction(UP) has FIELD
--R branchPointAtInfinity? : () -> Boolean
--R characteristic : () -> NonNegativeInteger
--R characteristicPolynomial : % -> UPUP
--R charthRoot : % -> Union(%,"failed") if Fraction(UP) has CHARNZ
--R charthRoot : % -> % if Fraction(UP) has FFIELDC
--R coerce : % -> % if Fraction(UP) has FIELD
--R coerce : Fraction(Integer) -> % if Fraction(UP) has FIELD or Fraction(UP) has RETRACT(FRAC(I
--R complementaryBasis : Vector(%) -> Vector(%)
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if Fraction(UP) has FFIELDC
--R convert : Vector(Fraction(UP)) -> %
--R convert : % -> Vector(Fraction(UP))
--R coordinates : Vector(%) -> Matrix(Fraction(UP))
--R coordinates : % -> Vector(Fraction(UP))
--R coordinates : (Vector(%),Vector(%)) -> Matrix(Fraction(UP))
--R coordinates : (%,Vector(%)) -> Vector(Fraction(UP))
--R createPrimitiveElement : () -> % if Fraction(UP) has FFIELDC
--R derivationCoordinates : (Vector(%),(Fraction(UP) -> Fraction(UP))) -> Matrix(Fraction(UP)) i
```

```
--R differentiate : % -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fraction(UP) has FFIELD
--R differentiate : (%,NonNegativeInteger) -> % if Fraction(UP) has DIFRING and Fraction(UP) has FIELD or Fi
--R differentiate : (%,Symbol) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Fraction(UP) has FIELD and Fraction(UP) has PDRING(
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Fraction(UP) has FIELD and Fraction(UP
--R differentiate : (%,(UP -> UP)) -> %
--R differentiate : (%,(Fraction(UP) -> Fraction(UP))) -> % if Fraction(UP) has FIELD
--R differentiate : (%,(Fraction(UP) -> Fraction(UP)),NonNegativeInteger) -> % if Fraction(UP) has FIELD
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if Fraction(UP) has FFIELDC
--R discreteLog : % -> NonNegativeInteger if Fraction(UP) has FFIELDC
--R discriminant : Vector(%) -> Fraction(UP)
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Fraction(UP) has FIELD
--R elliptic : () -> Union(UP,"failed")
--R euclideanSize : % -> NonNegativeInteger if Fraction(UP) has FIELD
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Fraction(UP) has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Fraction(UP) has FIELD
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Fraction(UP) has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Fraction(UP) has FIELD
--R factor : % -> Factored(%) if Fraction(UP) has FIELD
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if Fraction(UP) has FFI
--R gcd : (%,%) -> % if Fraction(UP) has FIELD
--R gcd : List(%) -> % if Fraction(UP) has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynom
--R hyperelliptic : () -> Union(UP,"failed")
--R index : PositiveInteger -> % if Fraction(UP) has FINITE
--R init : () -> % if Fraction(UP) has FFIELDC
--R integralAtInfinity? : % -> Boolean
--R integralBasisAtInfinity : () -> Vector(%)
--R integralCoordinates : % -> Record(num: Vector(UP),den: UP)
--R integralDerivationMatrix : (UP -> UP) -> Record(num: Matrix(UP),den: UP)
--R integralMatrix : () -> Matrix(Fraction(UP))
--R integralMatrixAtInfinity : () -> Matrix(Fraction(UP))
--R integralRepresents : (Vector(UP),UP) -> %
--R inv : % -> % if Fraction(UP) has FIELD
--R inverseIntegralMatrix : () -> Matrix(Fraction(UP))
--R inverseIntegralMatrixAtInfinity : () -> Matrix(Fraction(UP))
--R lcm : (%,%) -> % if Fraction(UP) has FIELD
--R lcm : List(%) -> % if Fraction(UP) has FIELD
--R lookup : % -> PositiveInteger if Fraction(UP) has FINITE
--R minimalPolynomial : % -> UPUP if Fraction(UP) has FIELD
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Fraction(UP) has FIELD
--R nextItem : % -> Union(%,"failed") if Fraction(UP) has FFIELDC
--R nonSingularModel : Symbol -> List(Polynomial(F)) if F has FIELD
--R normalizeAtInfinity : Vector(%) -> Vector(%)
--R numberOfComponents : () -> NonNegativeInteger
--R order : % -> OnePointCompletion(PositiveInteger) if Fraction(UP) has FFIELDC
--R order : % -> PositiveInteger if Fraction(UP) has FFIELDC
--R prime? : % -> Boolean if Fraction(UP) has FIELD
--R primeFrobenius : % -> % if Fraction(UP) has FFIELDC
```

```
--R primeFrobenius : (%,NonNegativeInteger) -> % if Fraction(UP) has FFIELDC
--R primitive? : % -> Boolean if Fraction(UP) has FFIELDC
--R primitiveElement : () -> % if Fraction(UP) has FFIELDC
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Fraction(UP) has FIELD
--R ?quo? : (%,%) -> % if Fraction(UP) has FIELD
--R ramifiedAtInfinity? : () -> Boolean
--R random : () -> % if Fraction(UP) has FINITE
--R rationalPoints : () -> List(List(F)) if F has FINITE
--R reduce : Fraction(UPUP) -> Union(%,"failed") if Fraction(UP) has FIELD
--R reduceBasisAtInfinity : Vector(%) -> Vector(%)
--R reducedSystem : Matrix(%) -> Matrix(Fraction(UP))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Fraction(UP)),vec: Vector(Fracti
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if Fraction(UP) has LINEXP(INT)
--R regularRepresentation : % -> Matrix(Fraction(UP))
--R regularRepresentation : (%,Vector(%)) -> Matrix(Fraction(UP))
--R ?rem? : (%,%) -> % if Fraction(UP) has FIELD
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if Fraction(UP) has FFIEL
--R represents : Vector(Fraction(UP)) -> %
--R represents : (Vector(Fraction(UP)),Vector(%)) -> %
--R retract : % -> Fraction(Integer) if Fraction(UP) has RETRACT(FRAC(INT))
--R retract : % -> Integer if Fraction(UP) has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(UP),"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if Fraction(UP) has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if Fraction(UP) has RETRACT(INT)
--R singularAtInfinity? : () -> Boolean
--R size : () -> NonNegativeInteger if Fraction(UP) has FINITE
--R sizeLess? : (%,%) -> Boolean if Fraction(UP) has FIELD
--R squareFree : % -> Factored(%) if Fraction(UP) has FIELD
--R squareFreePart : % -> % if Fraction(UP) has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if Fraction
--R traceMatrix : () -> Matrix(Fraction(UP))
--R traceMatrix : Vector(%) -> Matrix(Fraction(UP))
--R unit? : % -> Boolean if Fraction(UP) has FIELD
--R unitCanonical : % -> % if Fraction(UP) has FIELD
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Fraction(UP) has FIELD
--R yCoordinates : % -> Record(num: Vector(UP),den: UP)
--R
--E 1

)spool
)lisp (bye)
```

———-


— RadicalFunctionField.help —

```
==========================================================================
```

```
RadicalFunctionField examples
==============================================================================

See Also:
o )show RadicalFunctionField
```

19.1.1 RadicalFunctionField (RADFF)



See

⇒ “AlgebraicFunctionField” (ALGFF) 2.5.1 on page 27

Exports:

0	1	absolutelyIrreducible?
algSplitSimple	associates?	basis
branchPoint?	branchPointAtInfinity?	characteristic
characteristicPolynomial	charthRoot	coerce
complementaryBasis	conditionP	convert
coordinates	createPrimitiveElement	D
derivationCoordinates	definingPolynomial	differentiate
discreteLog	discriminant	divide
elliptic	elt	euclideanSize
expressIdealMember	exquo	extendedEuclidean
factor	factorsOfCyclicGroupSize	gcd
gcdPolynomial	generator	genus
hash	hyperelliptic	index
init	integral?	integralAtInfinity?
integralBasis	integralBasisAtInfinity	integralCoordinates
integralDerivationMatrix	integralMatrix	integralMatrixAtInfinity
integralRepresents	inv	inverseIntegralMatrix
inverseIntegralMatrixAtInfinity	latex	lcm
lift	lookup	minimalPolynomial
multiEuclidean	nextItem	nonSingularModel
norm	normalizeAtInfinity	numberOfComponents
one?	order	prime?
primeFrobenius	primitive?	primitiveElement
primitivePart	principalIdeal	ramified?
ramifiedAtInfinity?	random	rank
rationalPoint?	rationalPoints	recip
reduce	reduce	reduceBasisAtInfinity
reducedSystem	regularRepresentation	representationType
represents	retract	retractIfCan
sample	singular?	singularAtInfinity?
size	sizeLess?	squareFree
squareFreePart	subtractIfCan	tableForDiscreteLogarithm
trace	traceMatrix	unit?
unitCanonical	unitNormal	yCoordinates
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?
?/?	?quo?	?rem?

— domain RADFF RadicalFunctionField —

```
)abbrev domain RADFF RadicalFunctionField
++ Author: Manuel Bronstein
++ Date Created: 1987
++ Date Last Updated: 27 July 1993
++ Keywords: algebraic, curve, radical, function, field.
++ Examples: )r RADFF INPUT
```

```
++ Description:
++ Function field defined by y**n = f(x);

RadicalFunctionField(F, UP, UPUP, radicnd, n): Exports == Impl where
  F       : UniqueFactorizationDomain
  UP      : UnivariatePolynomialCategory F
  UPUP    : UnivariatePolynomialCategory Fraction UP
  radicnd : Fraction UP
  n       : NonNegativeInteger

  N   ==> NonNegativeInteger
  Z   ==> Integer
  RF  ==> Fraction UP
  QF  ==> Fraction UPUP
  UP2 ==> SparseUnivariatePolynomial UP
  REC ==> Record(factor:UP, exponent:Z)
  MOD ==> monomial(1, n)$UPUP - radicnd::UPUP
  INIT ==> if (deref brandNew?) then startUp false

  Exports ==> FunctionFieldCategory(F, UP, UPUP)

  Impl ==> SimpleAlgebraicExtension(RF, UPUP, MOD) add
    import ChangeOfVariable(F, UP, UPUP)
    import InnerCommonDenominator(UP, RF, Vector UP, Vector RF)
    import UnivariatePolynomialCategoryFunctions2(RF, UPUP, UP, UP2)

    diag        : Vector RF -> Vector $
    startUp     : Boolean -> Void
    fullVector  : (Factored UP, N) -> PrimitiveArray UP
    iBasis      : (UP, N) -> Vector UP
    inftyBasis  : (RF, N) -> Vector RF
    basisvec    : () -> Vector RF
    charOStartUp: () -> Void
    charPStartUp: () -> Void
    getInfBasis : () -> Void
    radcand     : () -> UP
    charPintbas : (UPUP, RF, Vector RF, Vector RF) -> Void

    brandNew?:Reference(Boolean) := ref true
    discPoly:Reference(RF) := ref(0$RF)
    newrad:Reference(UP) := ref(0$UP)
    n1 := (n - 1)::N
    modulus := MOD
    ibasis:Vector(RF)     := new(n, 0)
    invibasis:Vector(RF)  := new(n, 0)
    infbasis:Vector(RF)   := new(n, 0)
    invinfbasis:Vector(RF):= new(n, 0)
    mini := minIndex ibasis

    discriminant()                  == (INIT; discPoly())
```

```
    radcand()                        == (INIT; newrad())
    integralBasis()                  == (INIT; diag ibasis)
    integralBasisAtInfinity()        == (INIT; diag infbasis)
    basisvec()                       == (INIT; ibasis)
    integralMatrix()                 == diagonalMatrix basisvec()
    integralMatrixAtInfinity()       == (INIT; diagonalMatrix infbasis)
    inverseIntegralMatrix()          == (INIT; diagonalMatrix invibasis)
    inverseIntegralMatrixAtInfinity()==(INIT;diagonalMatrix invinfbasis)
    definingPolynomial()             == modulus
    ramified?(point:F)               == zero?(radcand() point)
    branchPointAtInfinity?()  == (degree(radcand()) exquo n) case "failed"
    elliptic()     == (n = 2 and degree(radcand()) = 3 => radcand(); "failed")
    hyperelliptic() == (n=2 and odd? degree(radcand()) => radcand(); "failed")
    diag v == [reduce monomial(qelt(v,i+mini), i) for i in 0..n1]

    integralRepresents(v, d) ==
      ib := basisvec()
      represents
        [qelt(ib, i) * (qelt(v, i) /$RF d) for i in mini .. maxIndex ib]

    integralCoordinates f ==
      v  := coordinates f
      ib := basisvec()
      splitDenominator
        [qelt(v,i) / qelt(ib,i) for i in mini .. maxIndex ib]$Vector(RF)

    integralDerivationMatrix d ==
      dlogp := differentiate(radicnd, d) / (n * radicnd)
      v := basisvec()
      cd := splitDenominator(
                [(i - mini) * dlogp + differentiate(qelt(v, i), d) / qelt(v, i)
                                        for i in mini..maxIndex v]$Vector(RF))
      [diagonalMatrix(cd.num), cd.den]

-- return (d0,...,d(n-1)) s.t. (1/d0, y/d1,...,y**(n-1)/d(n-1))
-- is an integral basis for the curve y**d = p
-- requires that p has no factor of multiplicity >= d
    iBasis(p, d) ==
      pl := fullVector(squareFree p, d)
      d1 := (d - 1)::N
      [*/[pl.j ** ((i * j) quo d) for j in 0..d1] for i in 0..d1]

-- returns a vector [a0,a1,...,a_{m-1}] of length m such that
-- p = a0^0 a1^1 ... a_{m-1}^{m-1}
    fullVector(p, m) ==
      ans:PrimitiveArray(UP) := new(m, 0)
      ans.0 := unit p
      l := factors p
      for i in 1..maxIndex ans repeat
        ans.i :=
```

```
          (u := find(s+->s.exponent = i, l)) case "failed" => 1
          (u::REC).factor
      ans

-- return (f0,...,f(n-1)) s.t. (f0, y f1,..., y**(n-1) f(n-1))
-- is a local integral basis at infinity for the curve y**d = p
    inftyBasis(p, m) ==
      rt := rootPoly(p(x := inv(monomial(1, 1)$UP :: RF)), m)
      m ^= rt.exponent =>
        error "Curve not irreducible after change of variable 0 -> infinity"
      a    := (rt.coef) x
      b:RF := 1
      v    := iBasis(rt.radicand, m)
      w:Vector(RF) := new(m, 0)
      for i in mini..maxIndex v repeat
        qsetelt_!(w, i, b / ((qelt(v, i)::RF) x))
        b := b * a
      w

    charPintbas(p, c, v, w) ==
      degree(p) ^= n => error "charPintbas: should not happen"
      q:UP2 := map(s+->retract(s)@UP, p)
      ib := integralBasis()$FunctionFieldIntegralBasis(UP, UP2,
                                        SimpleAlgebraicExtension(UP, UP2, q))
      not diagonal?(ib.basis)=>
         error "charPintbas: integral basis not diagonal"
      a:RF := 1
      for i in minRowIndex(ib.basis) .. maxRowIndex(ib.basis)
        for j in minColIndex(ib.basis) .. maxColIndex(ib.basis)
          for k in mini .. maxIndex v repeat
            qsetelt_!(v, k, (qelt(ib.basis, i, j) / ib.basisDen) * a)
            qsetelt_!(w, k, qelt(ib.basisInv, i, j) * inv a)
            a := a * c
      void

    charPStartUp() ==
      r      := mkIntegral modulus
      charPintbas(r.poly, r.coef, ibasis, invibasis)
      x      := inv(monomial(1, 1)$UP :: RF)
      invmod := monomial(1, n)$UPUP - (radicnd x)::UPUP
      r      := mkIntegral invmod
      charPintbas(r.poly, (r.coef) x, infbasis, invinfbasis)

    startUp b ==
      brandNew?() := b
      if zero?(p := characteristic()$F) or p > n then charOStartUp()
                                                 else charPStartUp()
      dsc:RF := ((-1)$Z ** ((n *$N n1) quo 2::N) * (n::Z)**n)$Z *
                radicnd ** n1 *
                   */[qelt(ibasis, i) ** 2 for i in mini..maxIndex ibasis]
```

```
      discPoly() := primitivePart(numer dsc) / denom(dsc)
      void

    char0StartUp() ==
      rp          := rootPoly(radicnd, n)
      rp.exponent ^= n =>
         error "RadicalFunctionField: curve is not irreducible"
      newrad()    := rp.radicand
      ib          := iBasis(newrad(), n)
      infb        := inftyBasis(radicnd, n)
      invden:RF   := 1
      for i in mini..maxIndex ib repeat
        qsetelt_!(invibasis, i, a := qelt(ib, i) * invden)
        qsetelt_!(ibasis, i, inv a)
        invden := invden / rp.coef        -- always equals 1/rp.coef**(i-mini)
        qsetelt_!(infbasis, i, a := qelt(infb, i))
        qsetelt_!(invinfbasis, i, inv a)
      void

    ramified?(p:UP) ==
      (r := retractIfCan(p)@Union(F, "failed")) case F =>
        singular?(r::F)
      (radcand() exquo p) case UP

    singular?(p:UP) ==
      (r := retractIfCan(p)@Union(F, "failed")) case F =>
        singular?(r::F)
      (radcand() exquo(p**2)) case UP

    branchPoint?(p:UP) ==
      (r := retractIfCan(p)@Union(F, "failed")) case F =>
        branchPoint?(r::F)
      ((q := (radcand() exquo p)) case UP) and
        ((q::UP exquo p) case "failed")

    singular?(point:F) ==
      zero?(radcand()  point) and
        zero?(((radcand() exquo (monomial(1,1)$UP-point::UP))::UP) point)

    branchPoint?(point:F) ==
      zero?(radcand()  point) and not
        zero?(((radcand() exquo (monomial(1,1)$UP-point::UP))::UP) point)
```

———-

— RADFF.dotabb —

```
"RADFF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RADFF"]
```

```
"FFCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FFCAT"]
"RADFF" -> "FFCAT"
```

———-

19.2 domain RADIX RadixExpansion

— RadixExpansion.input —

```
)set break resume
)sys rm -f RadixExpansion.output
)spool RadixExpansion.output
)set message test on
)set message auto off
)clear all
--S 1 of 17
111::RadixExpansion(5)
--R
--R
--R   (1)  421
--R                                                    Type: RadixExpansion(5)
--E 1

--S 2 of 17
(5/24)::RadixExpansion(2)
--R
--R
--R             --
--R   (2)  0.00110
--R                                                    Type: RadixExpansion(2)
--E 2

--S 3 of 17
(5/24)::RadixExpansion(3)
--R
--R
--R           --
--R   (3)  0.012
--R                                                    Type: RadixExpansion(3)
--E 3

--S 4 of 17
(5/24)::RadixExpansion(8)
--R
--R
--R           --
```

```
--R   (4)  0.152
--R                                                    Type: RadixExpansion(8)
--E 4

--S 5 of 17
(5/24)::RadixExpansion(10)
--R
--R
--R            _
--R   (5)  0.2083
--R                                                   Type: RadixExpansion(10)
--E 5

--S 6 of 17
(5/24)::RadixExpansion(12)
--R
--R
--R   (6)  0.26
--R                                                   Type: RadixExpansion(12)
--E 6

--S 7 of 17
(5/24)::RadixExpansion(16)
--R
--R
--R          _
--R   (7)  0.35
--R                                                   Type: RadixExpansion(16)
--E 7

--S 8 of 17
(5/24)::RadixExpansion(36)
--R
--R
--R   (8)  0.7I
--R                                                   Type: RadixExpansion(36)
--E 8

--S 9 of 17
(5/24)::RadixExpansion(38)
--R
--R
--R                    _____
--R   (9)  0 . 7 34 31 25 12
--R                                                   Type: RadixExpansion(38)
--E 9

--S 10 of 17
a := (76543/210)::RadixExpansion(8)
--R
```

```
--R
--R              ____
--R   (10)  554.37307
--R                                                    Type: RadixExpansion(8)
--E 10

--S 11 of 17
w := wholeRagits a
--R
--R
--R   (11)  [5,5,4]
--R                                                        Type: List(Integer)
--E 11

--S 12 of 17
f0 := prefixRagits a
--R
--R
--R   (12)  [3]
--R                                                        Type: List(Integer)
--E 12

--S 13 of 17
f1 := cycleRagits a
--R
--R
--R   (13)  [7,3,0,7]
--R                                                        Type: List(Integer)
--E 13

--S 14 of 17
u:RadixExpansion(8):=wholeRadix(w)+fractRadix(f0,f1)
--R
--R
--R              ____
--R   (14)  554.37307
--R                                                    Type: RadixExpansion(8)
--E 14

--S 15 of 17
v: RadixExpansion(12) := fractRadix([1,2,3,11], [0])
--R
--R
--R               _
--R   (15)  0.123B0
--R                                                   Type: RadixExpansion(12)
--E 15

--S 16 of 17
fractRagits(u)
```

```
--R
--R
--R                 -------
--R   (16)  [3,7,3,0,7,7]
--R                                                    Type: Stream(Integer)
--E 16

--S 17 of 17
a :: Fraction(Integer)
--R
--R
--R         76543
--R   (17)  -----
--R          210
--R                                                  Type: Fraction(Integer)
--E 17
)spool
)lisp (bye)
```

———-

— RadixExpansion.help —

```
========================================================================
RadixExpansion examples
========================================================================

It possible to expand numbers in general bases.

Here we expand 111 in base 5. This means
  10^2+10^1+10^0 = 4 * 5^2+2 * 5^1 + 5^0

  111::RadixExpansion(5)
    421
                              Type: RadixExpansion 5

You can expand fractions to form repeating expansions.

  (5/24)::RadixExpansion(2)
         --
    0.00110
                              Type: RadixExpansion 2

  (5/24)::RadixExpansion(3)
       --
    0.012
                              Type: RadixExpansion 3

  (5/24)::RadixExpansion(8)
```

```
      --
    0.152
                                Type: RadixExpansion 8

  (5/24)::RadixExpansion(10)
        -
    0.2083
                                Type: RadixExpansion 10

For bases from 11 to 36 the letters A through Z are used.

  (5/24)::RadixExpansion(12)
    0.26
                                Type: RadixExpansion 12

  (5/24)::RadixExpansion(16)
      -
    0.35
                                Type: RadixExpansion 16

  (5/24)::RadixExpansion(36)
    0.7I
                                Type: RadixExpansion 36

For bases greater than 36, the ragits are separated by blanks.

  (5/24)::RadixExpansion(38)
                 -----
    0 . 7 34 31 25 12
                                Type: RadixExpansion 38

The RadixExpansion type provides operations to obtain the individual
ragits.  Here is a rational number in base 8.

  a := (76543/210)::RadixExpansion(8)
          ----
     554.37307
                                Type: RadixExpansion 8

The operation wholeRagits returns a list of the ragits for the
integral part of the number.

  w := wholeRagits a
    [5,5,4]
                                Type: List Integer

The operations prefixRagits and cycleRagits return lists of the initial
and repeating ragits in the fractional part of the number.

  f0 := prefixRagits a
```

```
    [3]
                                Type: List Integer

  f1 := cycleRagits a
    [7,3,0,7]
                                Type: List Integer
```

You can construct any radix expansion by giving the whole, prefix and cycle parts. The declaration is necessary to let Axiom know the base of the ragits.

```
  u:RadixExpansion(8):=wholeRadix(w)+fractRadix(f0,f1)
          ----
    554.37307
                                Type: RadixExpansion 8
```

If there is no repeating part, then the list [0] should be used.

```
  v: RadixExpansion(12) := fractRadix([1,2,3,11], [0])
          -
    0.123B0
                                Type: RadixExpansion 12
```

If you are not interested in the repeating nature of the expansion, an infinite stream of ragits can be obtained using fractRagits.


```
  fractRagits(u)
          -------
    [3,7,3,0,7,7]
                                Type: Stream Integer
```

Of course, it's possible to recover the fraction representation:

```
  a :: Fraction(Integer)
    76543
    -----
     210
                                Type: Fraction Integer
```

See Also:
o)help DecimalExpansion
o)help BinaryExpansion
o)help HexadecimalExpansion
o)show RadixExpansion

19.2.1 RadixExpansion (RADIX)



See

⇒ “BinaryExpansion” (BINARY) 3.7.1 on page 276
⇒ “DecimalExpansion” (DECIMAL) 5.3.1 on page 453
⇒ “HexadecimalExpansion” (HEXADEC) 9.3.1 on page 1112

Exports:

0	1	abs
associates?	ceiling	characteristic
charthRoot	coerce	conditionP
convert	cycleRagits	D
denom	denominator	differentiate
divide	euclideanSize	eval
expressIdealMember	exquo	extendedEuclidean
factor	factorPolynomial	factorSquareFreePolynomial
floor	fractRadix	fractRagits
fractionPart	gcd	gcdPolynomial
hash	init	inv
latex	lcm	map
max	min	multiEuclidean
negative?	nextItem	numer
numerator	one?	patternMatch
positive?	prefixRagits	prime?
principalIdeal	random	recip
reducedSystem	retract	retractIfCan
sample	sign	sizeLess?
solveLinearPolynomialEquation	squareFree	squareFreePart
squareFreePolynomial	subtractIfCan	unit?
unitCanonical	unitNormal	wholePart
wholeRadix	wholeRagits	zero?
?.?	?*?	?**?
?+?	?-?	-?
?/?	?=?	?^?
?~=?	?<?	?<=?
?>?	?>=?	?quo?
?rem?		

— domain RADIX RadixExpansion —

```
)abbrev domain RADIX RadixExpansion
++ Author: Stephen M. Watt
++ Date Created: October 1986
++ Date Last Updated: May 15, 1991
++ Basic Operations: wholeRadix, fractRadix, wholeRagits, fractRagits
++ Related Domains: BinaryExpansion, DecimalExpansion, HexadecimalExpansion,
++    RadixUtilities
++ Also See:
++ AMS Classifications:
++ Keywords: radix, base, repeating decimal
++ Examples:
++ References:
++ Description:
++ This domain allows rational numbers to be presented as repeating
++ decimal expansions or more generally as repeating expansions in any base.
```

```
RadixExpansion(bb): Exports == Implementation where
  bb   :  Integer
  I   ==> Integer
  NNI ==> NonNegativeInteger
  OUT ==> OutputForm
  RN  ==> Fraction Integer
  ST  ==> Stream Integer
  QuoRem ==> Record(quotient: Integer, remainder: Integer)

  Exports ==> QuotientFieldCategory(Integer) with
    coerce: % -> Fraction Integer
      ++ coerce(rx) converts a radix expansion to a rational number.
    fractionPart: % -> Fraction Integer
      ++ fractionPart(rx) returns the fractional part of a radix expansion.
    wholeRagits: % -> List Integer
      ++ wholeRagits(rx) returns the ragits of the integer part
      ++ of a radix expansion.
    fractRagits: % -> Stream Integer
      ++ fractRagits(rx) returns the ragits of the fractional part
      ++ of a radix expansion.
    prefixRagits: % -> List Integer
      ++ prefixRagits(rx) returns the non-cyclic part of the ragits
      ++ of the fractional part of a radix expansion.
      ++ For example, if \spad{x = 3/28 = 0.10 714285 714285 ...},
      ++ then \spad{prefixRagits(x)=[1,0]}.
    cycleRagits: % -> List Integer
      ++ cycleRagits(rx) returns the cyclic part of the ragits of the
      ++ fractional part of a radix expansion.
      ++ For example, if \spad{x = 3/28 = 0.10 714285 714285 ...},
      ++ then \spad{cycleRagits(x) = [7,1,4,2,8,5]}.
    wholeRadix: List Integer -> %
      ++ wholeRadix(l) creates an integral radix expansion from a list
      ++ of ragits.
      ++ For example, \spad{wholeRadix([1,3,4])} will return \spad{134}.
    fractRadix: (List Integer, List Integer) -> %
      ++ fractRadix(pre,cyc) creates a fractional radix expansion
      ++ from a list of prefix ragits and a list of cyclic ragits.
      ++ e.g., \spad{fractRadix([1],[6])} will return \spad{0.16666666...}.

  Implementation ==> add
    -- The efficiency of arithmetic operations is poor.
    -- Could use a lazy eval where either rational rep
    -- or list of ragit rep (the current) or both are kept
    -- as demanded.

    bb < 2 => error "Radix base must be at least 2"
    Rep := Record(sgn: Integer,      int: List Integer,
                  pfx: List Integer, cyc: List Integer)

    q:     RN
```

```
qr:    QuoRem
a,b:   %
n:     I

radixInt:    (I, I)    -> List I
radixFrac:   (I, I, I) -> Record(pfx: List I, cyc: List I)
checkRagits: List I    -> Boolean

-- Arithmetic operations
characteristic() == 0
differentiate a == 0

0     == [1, nil(),  nil(), nil()]
1     == [1, [1], nil(), nil()]
- a   == (a = 0 => 0; [-a.sgn, a.int, a.pfx, a.cyc])
a + b == (a::RN + b::RN)::%
a - b == (a::RN - b::RN)@RN::%
n * a == (n     * a::RN)::%
a * b == (a::RN * b::RN)::%
a / b == (a::RN / b::RN)::%
(i:I) / (j:I) == (i/j)@RN :: %
a < b == a::RN < b::RN
a = b == a.sgn = b.sgn and a.int = b.int and
         a.pfx = b.pfx and a.cyc = b.cyc
numer a == numer(a::RN)
denom a == denom(a::RN)

-- Algebraic coercions
coerce(a):RN == (wholePart a) :: RN + fractionPart a
coerce(n):%  == n :: RN :: %
coerce(q):%  ==
  s := 1; if q < 0 then (s := -1; q := -q)
  qr      := divide(numer q,denom q)
  whole   := radixInt (qr.quotient,bb)
  fractn  := radixFrac(qr.remainder,denom q,bb)
  cycle   := (fractn.cyc = [0] => nil(); fractn.cyc)
  [s,whole,fractn.pfx,cycle]

retractIfCan(a):Union(RN,"failed") == a::RN
retractIfCan(a):Union(I,"failed") ==
  empty?(a.pfx) and empty?(a.cyc) => wholePart a
  "failed"

-- Exported constructor/destructors
ceiling a == ceiling(a::RN)
floor a == floor(a::RN)

wholePart a ==
  n0 := 0
  for r in a.int repeat n0 := bb*n0 + r
```

```
    a.sgn*n0
  fractionPart a ==
    n0 := 0
    for r in a.pfx repeat n0 := bb*n0 + r
    null a.cyc =>
        a.sgn*n0/bb**((#a.pfx)::NNI)
    n1 := n0
    for r in a.cyc repeat n1 := bb*n1 + r
    n := n1 - n0
    d := (bb**((#a.cyc)::NNI) - 1) * bb**((#a.pfx)::NNI)
    a.sgn*n/d

  wholeRagits  a == a.int
  fractRagits  a == concat(construct(a.pfx)@ST,repeating a.cyc)
  prefixRagits a == a.pfx
  cycleRagits  a == a.cyc

  wholeRadix li ==
    checkRagits li
    [1, li, nil(), nil()]
  fractRadix(lpfx, lcyc) ==
    checkRagits lpfx; checkRagits lcyc
    [1, nil(), lpfx, lcyc]

  -- Output

  ALPHAS : String := "ABCDEFGHIJKLMNOPQRSTUVWXYZ"

  intToExpr(i:I): OUT ==
    -- computes a digit for bases between 11 and 36
    i < 10 => i :: OUT
    elt(ALPHAS,(i-10) + minIndex(ALPHAS)) :: OUT

  exprgroup(le: List OUT): OUT ==
    empty? le      => error "exprgroup needs non-null list"
    empty? rest le => first le
    abs bb <= 36 => hconcat le
    blankSeparate le

  intgroup(li: List I): OUT ==
    empty? li      => error "intgroup needs non-null list"
    empty? rest li => intToExpr first(li)
    abs bb <= 10 => hconcat [i :: OUT for i in li]
    abs bb <= 36 => hconcat [intToExpr(i) for i in li]
    blankSeparate [i :: OUT for i in li]

  overBar(li: List I): OUT == overbar intgroup li

  coerce(a): OUT ==
    le : List OUT := nil()
```

```
    if not null a.cyc then le := concat(overBar  a.cyc,le)
    if not null a.pfx then le := concat(intgroup a.pfx,le)
    if not null le    then le := concat("." :: OUT,le)
    if not null a.int then le := concat(intgroup a.int,le)
    else le := concat(0 :: OUT,le)
    rex := exprgroup le
    if a.sgn < 0 then -rex else rex

  -- Construction utilities
  checkRagits li ==
    for i in li repeat if i < 0 or i >= bb then
      error "Each ragit (digit) must be between 0 and base-1"
    true

  radixInt(n,bas) ==
    rits: List I := nil()
    while abs n ^= 0 repeat
      qr   := divide(n,bas)
      n    := qr.quotient
      rits := concat(qr.remainder,rits)
    rits

  radixFrac(num,den,bas) ==
    -- Rits is the sequence of quotient/remainder pairs
    -- in calculating the radix expansion of the rational number.
    -- We wish to find p and c such that
    --    rits.i are distinct    for 0<=i<=p+c-1
    --    rits.i = rits.(i+p)    for i>p
    -- I.e. p is the length of the non-periodic prefix and c is
    -- the length of the cycle.

    -- Compute p and c using Floyd's algorithm.
    -- 1. Find smallest n s.t. rits.n = rits.(2*n)
    qr    := divide(bas * num, den)
    i : I := 0
    qr1i  := qr2i := qr
    rits: List QuoRem := [qr]
    until qr1i = qr2i repeat
      qr1i := divide(bas * qr1i.remainder,den)
      qrt  := divide(bas * qr2i.remainder,den)
      qr2i := divide(bas * qrt.remainder,den)
      rits := concat(qr2i, concat(qrt, rits))
      i    := i + 1
    rits := reverse_! rits
    n    := i
    -- 2. Find p = first i such that rits.i = rits.(i+n)
    ritsi := rits
    ritsn := rits; for i in 1..n repeat ritsn := rest ritsn
    i := 0
    while first(ritsi) ^= first(ritsn) repeat
```

```
      ritsi := rest ritsi
      ritsn := rest ritsn
      i     := i + 1
    p := i
    -- 3. Find c = first i such that rits.p = rits.(p+i)
    ritsn := rits; for i in 1..n repeat ritsn := rest ritsn
    rn    := first ritsn
    cfound:= false
    c : I := 0
    for i in 1..p while not cfound repeat
      ritsn := rest ritsn
      if rn = first(ritsn) then
        c := i
        cfound := true
    if not cfound then c := n
    -- 4. Now produce the lists of ragits.
    ritspfx: List I := nil()
    ritscyc: List I := nil()
    for i in 1..p repeat
      ritspfx := concat(first(rits).quotient, ritspfx)
      rits    := rest rits
    for i in 1..c repeat
      ritscyc := concat(first(rits).quotient, ritscyc)
      rits    := rest rits
    [reverse_! ritspfx, reverse_! ritscyc]
```

———-

— **RADIX.dotabb** —

```
"RADIX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RADIX"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"RADIX" -> "PFECAT"
"RADIX" -> "STRING"
```

———-

19.3 domain RECLOS RealClosure

The domain constructore **RealClosure** by Renaud Rioboo (University of Paris 6, France) provides the real closure of an ordered field. The implementation is based on interval arithmetic. Moreover, the design of this constructor and its related packages allows an easy use of other codings for real algebraic numbers. ordered field

The RealClosure domain is the end-user code, it provides usual arithmetics with real algebraic numbers, along with the functionalities of a real closed field. It also provides functions to approximate a real algebraic number by an element of the base field. This approximation may either be absolute (approximate) or relative (realtivApprox).

CAVEATS

Since real algebraic expressions are stored as depending on "real roots" which are managed like variables, there is an ordering on these. This ordering is dynamical in the sense that any new algebraic takes precedence over older ones. In particular every cretaion function raises a new "real root". This has the effect that when you type something like sqrt(2) + sqrt(2) you have two new variables which happen to be equal. To avoid this name the expression such as in s2 := sqrt(2) ; s2 + s2

Also note that computing times depend strongly on the ordering you implicitly provide. Please provide algebraics in the order which most natural to you.

LIMITATIONS

The file reclos.input show some basic use of the package. This packages uses algorithms which are published in [1] and [2] which are based on field arithmetics, inparticular for polynomial gcd related algorithms. This can be quite slow for high degree polynomials and subresultants methods usually work best. Betas versions of the package try to use these techniques in a better way and work significantly faster. These are mostly based on unpublished algorithms and cannot be distributed. Please contact the author if you have a particular problem to solve or want to use these versions.

Be aware that approximations behave as post-processing and that all computations are done excatly. They can thus be quite time consuming when depending on several "real roots".

— RealClosure.input —

```
)set break resume
)sys rm -f RealClosure.output
)spool RealClosure.output
)set message test on
)set message auto off
)clear all
--S 1 of 67
Ran := RECLOS(FRAC INT)
--R
--R
--R   (1)  RealClosure(Fraction(Integer))
--R                                                              Type: Domain
--E 1

--S 2 of 67
fourSquares(a:Ran,b:Ran,c:Ran,d:Ran):Ran==sqrt(a)+sqrt(b)-sqrt(c)-sqrt(d)
--R
--R   Function declaration fourSquares : (RealClosure(Fraction(Integer)),
--R      RealClosure(Fraction(Integer)),RealClosure(Fraction(Integer)),
```

```
--R      RealClosure(Fraction(Integer))) -> RealClosure(Fraction(Integer))
--R      has been added to workspace.
--R                                                                   Type: Void
--E 2

--S 3 of 67
squareDiff1 := fourSquares(73,548,60,586)
--R
--R   Compiling function fourSquares with type (RealClosure(Fraction(
--R      Integer)),RealClosure(Fraction(Integer)),RealClosure(Fraction(
--R      Integer)),RealClosure(Fraction(Integer))) -> RealClosure(Fraction
--R      (Integer))
--R
--R           +---+    +--+    +---+    +--+
--R   (3)  - \|586  - \|60  + \|548  + \|73
--R                                        Type: RealClosure(Fraction(Integer))
--E 3

--S 4 of 67
recip(squareDiff1)
--R
--R
--R   (4)
--R             +---+          +--+  +--+         +--+ +---+            +---+
--R     ((54602\|548  + 149602\|73 )\|60  + 49502\|73 \|548  + 9900895)\|586
--R   +
--R             +--+ +---+             +--+            +---+            +--+
--R     (154702\|73 \|548  + 30941947)\|60  + 10238421\|548  + 28051871\|73
--R                              Type: Union(RealClosure(Fraction(Integer)),...)
--E 4

--S 5 of 67
sign(squareDiff1)
--R
--R
--R   (5)  1
--R                                                      Type: PositiveInteger
--E 5

--S 6 of 67
squareDiff2 := fourSquares(165,778,86,990)
--R
--R
--R           +---+    +--+    +---+    +---+
--R   (6)  - \|990  - \|86  + \|778  + \|165
--R                                        Type: RealClosure(Fraction(Integer))
--E 6

--S 7 of 67
recip(squareDiff2)
```

```
--R
--R
--R   (7)
--R                +---+           +---+  +--+          +---+ +---+
--R       ((556778\|778  + 1209010\|165 )\|86  + 401966\|165 \|778  + 144019431)
--R    *
--R        +---+
--R       \|990
--R   +
--R              +---+ +---+              +--+             +---+             +---+
--R     (1363822\|165 \|778  + 488640503)\|86  + 162460913\|778  + 352774119\|165
--R                              Type: Union(RealClosure(Fraction(Integer)),...)
--E 7

--S 8 of 67
sign(squareDiff2)
--R
--R
--R   (8)  1
--R                                                        Type: PositiveInteger
--E 8

--S 9 of 67
squareDiff3 := fourSquares(217,708,226,692)
--R
--R
--R           +---+    +---+    +---+    +---+
--R   (9)  - \|692  - \|226  + \|708  + \|217
--R                                        Type: RealClosure(Fraction(Integer))
--E 9

--S 10 of 67
recip(squareDiff3)
--R
--R
--R   (10)
--R                +---+         +---+  +---+         +---+ +---+             +---+
--R     ((- 34102\|708  - 61598\|217 )\|226  - 34802\|217 \|708  - 13641141)\|692
--R   +
--R              +---+ +---+             +---+            +---+            +---+
--R     (- 60898\|217 \|708  - 23869841)\|226  - 13486123\|708  - 24359809\|217
--R                              Type: Union(RealClosure(Fraction(Integer)),...)
--E 10

--S 11 of 67
sign(squareDiff3)
--R
--R
--R   (11)  - 1
--R                                                              Type: Integer
```

```
--E 11

--S 12 of 67
squareDiff4 := fourSquares(155,836,162,820)
--R
--R
--R           +---+    +---+    +---+    +---+
--R   (12)  - \|820  - \|162  + \|836  + \|155
--R                                      Type: RealClosure(Fraction(Integer))
--E 12

--S 13 of 67
recip(squareDiff4)
--R
--R
--R   (13)
--R               +---+         +---+  +---+         +---+ +---+             +---+
--R     ((- 37078\|836  - 86110\|155 )\|162  - 37906\|155 \|836  - 13645107)\|820
--R   +
--R             +---+ +---+             +---+            +---+            +---+
--R     (- 85282\|155 \|836  - 30699151)\|162  - 13513901\|836  - 31384703\|155
--R                              Type: Union(RealClosure(Fraction(Integer)),...)
--E 13

--S 14 of 67
sign(squareDiff4)
--R
--R
--R   (14)  - 1
--R                                                                  Type: Integer
--E 14

--S 15 of 67
squareDiff5 := fourSquares(591,772,552,818)
--R
--R
--R           +---+    +---+    +---+    +---+
--R   (15)  - \|818  - \|552  + \|772  + \|591
--R                                      Type: RealClosure(Fraction(Integer))
--E 15

--S 16 of 67
recip(squareDiff5)
--R
--R
--R   (16)
--R              +---+         +---+  +---+         +---+ +---+             +---+
--R     ((70922\|772  + 81058\|591 )\|552  + 68542\|591 \|772  + 46297673)\|818
--R   +
--R            +---+ +---+             +---+            +---+            +---+
```

```
--R     (83438\|591 \|772  + 56359389)\|552  + 47657051\|772  + 54468081\|591
--R                                Type: Union(RealClosure(Fraction(Integer)),...)
--E 16

--S 17 of 67
sign(squareDiff5)
--R
--R
--R   (17)  1
--R                                                          Type: PositiveInteger
--E 17

--S 18 of 67
squareDiff6 := fourSquares(434,1053,412,1088)
--R
--R
--R            +----+    +---+    +----+    +---+
--R   (18)  - \|1088  - \|412  + \|1053  + \|434
--R                                          Type: RealClosure(Fraction(Integer))
--E 18

--S 19 of 67
recip(squareDiff6)
--R
--R
--R   (19)
--R                 +----+          +---+  +---+          +---+ +----+
--R       ((115442\|1053  + 179818\|434 )\|412  + 112478\|434 \|1053  + 76037291)
--R    *
--R        +----+
--R       \|1088
--R   +
--R           +---+ +----+              +---+            +----+             +---+
--R   (182782\|434 \|1053  + 123564147)\|412  + 77290639\|1053  + 120391609\|434
--R                                Type: Union(RealClosure(Fraction(Integer)),...)
--E 19

--S 20 of 67
sign(squareDiff6)
--R
--R
--R   (20)  1
--R                                                          Type: PositiveInteger
--E 20

--S 21 of 67
squareDiff7 := fourSquares(514,1049,446,1152)
--R
--R
--R            +----+    +---+    +----+    +---+
```

```
--R   (21)  - \|1152  - \|446  + \|1049  + \|514
--R                                        Type: RealClosure(Fraction(Integer))
--E 21

--S 22 of 67
recip(squareDiff7)
--R
--R
--R   (22)
--R                +----+          +---+  +---+          +---+ +----+
--R       ((349522\|1049  + 499322\|514 )\|446  + 325582\|514 \|1049  + 239072537)
--R    *
--R        +----+
--R       \|1152
--R   +
--R           +---+ +----+              +---+             +----+             +---+
--R   (523262\|514 \|1049  + 384227549)\|446  + 250534873\|1049  + 357910443\|514
--R                              Type: Union(RealClosure(Fraction(Integer)),...)
--E 22

--S 23 of 67
sign(squareDiff7)
--R
--R
--R   (23)  1
--R                                                      Type: PositiveInteger
--E 23

--S 24 of 67
squareDiff8 := fourSquares(190,1751,208,1698)
--R
--R
--R            +----+    +---+    +----+    +---+
--R   (24)  - \|1698  - \|208  + \|1751  + \|190
--R                                        Type: RealClosure(Fraction(Integer))
--E 24

--S 25 of 67
recip(squareDiff8)
--R
--R
--R   (25)
--R                     +----+          +---+  +---+          +---+ +----+
--R           (- 214702\|1751  - 651782\|190 )\|208  - 224642\|190 \|1751
--R         +
--R           - 129571901
--R    *
--R        +----+
--R       \|1698
--R   +
```

```
--R               +---+ +-----+              +---+             +-----+
--R     (- 641842\|190 \|1751  - 370209881)\|208  - 127595865\|1751
--R   +
--R                 +---+
--R     - 387349387\|190
--R                               Type: Union(RealClosure(Fraction(Integer)),...)
--E 25

--S 26 of 67
sign(squareDiff8)
--R
--R
--R   (26)  - 1
--R                                                                  Type: Integer
--E 26

--S 27 of 67
relativeApprox(squareDiff8,10**(-3))::Float
--R
--R
--R   (27)  - 0.2340527771 5937700123 E -10
--R                                                                    Type: Float
--E 27

--S 28 of 67
l := allRootsOf((x**2-2)**2-2)$Ran
--R
--R
--R   (28)  [%A33,%A34,%A35,%A36]
--R                                    Type: List(RealClosure(Fraction(Integer)))
--E 28

--S 29 of 67
removeDuplicates map(mainDefiningPolynomial,l)
--R
--R
--R           4     2
--R   (29)  [?  - 4?  + 2]
--RType: List(Union(SparseUnivariatePolynomial(RealClosure(Fraction(Integer))),"failed"))
--E 29

--S 30 of 67
map(mainCharacterization,l)
--R
--R
--R   (30)  [[- 2,- 1[,[- 1,0[,[0,1[,[1,2[]
--IType: List(Union(RightOpenIntervalRootCharacterization(...
--E 30

--S 31 of 67
```

```
[reduce(+,l),reduce(*,l)-2]
--R
--R
--R   (31)  [0,0]
--R                                   Type: List(RealClosure(Fraction(Integer)))
--E 31

--S 32 of 67
(s2, s5, s10) := (sqrt(2)$Ran, sqrt(5)$Ran, sqrt(10)$Ran)
--R
--R
--R          +--+
--R   (32)  \|10
--R                                        Type: RealClosure(Fraction(Integer))
--E 32

--S 33 of 67
eq1:=sqrt(s10+3)*sqrt(s5+2) - sqrt(s10-3)*sqrt(s5-2) = sqrt(10*s2+10)
--R
--R
--R            +---------+ +--------+    +---------+ +--------+   +-----------+
--R            | +--+      | +-+         | +--+      | +-+        |   +-+
--R   (33)  - \|\|10  - 3 \|\|5  - 2  + \|\|10  + 3 \|\|5  + 2 = \|10\|2  + 10
--R                                Type: Equation(RealClosure(Fraction(Integer)))
--E 33

--S 34 of 67
eq1::Boolean
--R
--R
--R   (34)  true
--R                                                              Type: Boolean
--E 34

--S 35 of 67
eq2:=sqrt(s5+2)*sqrt(s2+1) - sqrt(s5-2)*sqrt(s2-1) = sqrt(2*s10+2)
--R
--R
--R            +--------+ +--------+    +--------+ +--------+   +----------+
--R            | +-+      | +-+         | +-+      | +-+        |  +--+
--R   (35)  - \|\|5  - 2 \|\|2  - 1  + \|\|5  + 2 \|\|2  + 1 = \|2\|10  + 2
--R                                Type: Equation(RealClosure(Fraction(Integer)))
--E 35

--S 36 of 67
eq2::Boolean
--R
--R
--R   (36)  true
--R                                                              Type: Boolean
```

```
--E 36

--S 37 of 67
s3 := sqrt(3)$Ran
--R
--R
--R          +-+
--R   (37)  \|3
--R                                        Type: RealClosure(Fraction(Integer))
--E 37

--S 38 of 67
s7:= sqrt(7)$Ran
--R
--R
--R          +-+
--R   (38)  \|7
--R                                        Type: RealClosure(Fraction(Integer))
--E 38

--S 39 of 67
e1 := sqrt(2*s7-3*s3,3)
--R
--R
--R          +--------------+
--R         3|  +-+     +-+
--R   (39)  \|2\|7  - 3\|3
--R                                        Type: RealClosure(Fraction(Integer))
--E 39

--S 40 of 67
e2 := sqrt(2*s7+3*s3,3)
--R
--R
--R          +--------------+
--R         3|  +-+     +-+
--R   (40)  \|2\|7  + 3\|3
--R                                        Type: RealClosure(Fraction(Integer))
--E 40

--S 41 of 67
e2-e1-s3
--R
--R
--R   (41)  0
--R                                        Type: RealClosure(Fraction(Integer))
--E 41

--S 42 of 67
pol : UP(x,Ran) := x**4+(7/3)*x**2+30*x-(100/3)
```

```
--R
--R
--R          4   7  2         100
--R   (42)  x  + - x  + 30x - ---
--R              3             3
--R                 Type: UnivariatePolynomial(x,RealClosure(Fraction(Integer)))
--E 42

--S 43 of 67
r1 := sqrt(7633)$Ran
--R
--R
--R          +----+
--R   (43)  \|7633
--R                                          Type: RealClosure(Fraction(Integer))
--E 43

--S 44 of 67
alpha := sqrt(5*r1-436,3)/3
--R
--R
--R            +--------------+
--R         1 3|  +----+
--R   (44)  - \|5\|7633  - 436
--R         3
--R                                          Type: RealClosure(Fraction(Integer))
--E 44

--S 45 of 67
beta := -sqrt(5*r1+436,3)/3
--R
--R
--R              +--------------+
--R           1 3|  +----+
--R   (45)  - - \|5\|7633  + 436
--R           3
--R                                          Type: RealClosure(Fraction(Integer))
--E 45

--S 46 of 67
pol.(alpha+beta-1/3)
--R
--R
--R   (46)  0
--R                                          Type: RealClosure(Fraction(Integer))
--E 46

--S 47 of 67
qol : UP(x,Ran) := x**5+10*x**3+20*x+22
--R
```

```
--R
--R          5      3
--R   (47)  x  + 10x  + 20x + 22
--R                 Type: UnivariatePolynomial(x,RealClosure(Fraction(Integer)))
--E 47

--S 48 of 67
r2 := sqrt(153)$Ran
--R
--R
--R          +---+
--R   (48)  \|153
--R                                          Type: RealClosure(Fraction(Integer))
--E 48

--S 49 of 67
alpha2 := sqrt(r2-11,5)
--R
--R
--R          +-----------+
--R         5| +---+
--R   (49)  \|\|153  - 11
--R                                          Type: RealClosure(Fraction(Integer))
--E 49

--S 50 of 67
beta2 := -sqrt(r2+11,5)
--R
--R
--R            +-----------+
--R           5| +---+
--R   (50)  - \|\|153  + 11
--R                                          Type: RealClosure(Fraction(Integer))
--E 50

--S 51 of 67
qol(alpha2+beta2)
--R
--R
--R   (51)  0
--R                                          Type: RealClosure(Fraction(Integer))
--E 51

--S 52 of 67
dst1:=sqrt(9+4*s2)=1+2*s2
--R
--R
--R          +---------+
--R          |  +-+         +-+
--R   (52)  \|4\|2  + 9 = 2\|2  + 1
```

```
--R                                Type: Equation(RealClosure(Fraction(Integer)))
--E 52

--S 53 of 67
dst1::Boolean
--R
--R
--R   (53)  true
--R                                                                Type: Boolean
--E 53

--S 54 of 67
s6:Ran:=sqrt 6
--R
--R
--R          +-+
--R   (54)  \|6
--R                                          Type: RealClosure(Fraction(Integer))
--E 54

--S 55 of 67
dst2:=sqrt(5+2*s6)+sqrt(5-2*s6) = 2*s3
--R
--R
--R          +-----------+    +---------+
--R          |    +-+         |  +-+         +-+
--R   (55)  \|- 2\|6  + 5  + \|2\|6  + 5 = 2\|3
--R                                Type: Equation(RealClosure(Fraction(Integer)))
--E 55

--S 56 of 67
dst2::Boolean
--R
--R
--R   (56)  true
--R                                                                Type: Boolean
--E 56

--S 57 of 67
s29:Ran:=sqrt 29
--R
--R
--R          +--+
--R   (57)  \|29
--R                                          Type: RealClosure(Fraction(Integer))
--E 57

--S 58 of 67
dst4:=sqrt(16-2*s29+2*sqrt(55-10*s29)) = sqrt(22+2*s5)-sqrt(11+2*s29)+s5
--R
```

```
--R
--R   (58)
--R    +--------------------------------+
--R    |  +--------------+                    +-----------+    +----------+
--R    |  |     +--+           +--+           |  +--+          |  +-+          +-+
--R   \|2\|- 10\|29  + 55  - 2\|29  + 16 = - \|2\|29  + 11  + \|2\|5  + 22  + \|5
--R                              Type: Equation(RealClosure(Fraction(Integer)))
--E 58

--S 59 of 67
dst4::Boolean
--R
--R
--R   (59)  true
--R                                                                  Type: Boolean
--E 59

--S 60 of 67
dst6:=sqrt((112+70*s2)+(46+34*s2)*s5) = (5+4*s2)+(3+s2)*s5
--R
--R
--R          +--------------------------------+
--R          |    +-+       +-+      +-+           +-+      +-+     +-+
--R   (60)  \|(34\|2  + 46)\|5  + 70\|2  + 112 = (\|2  + 3)\|5  + 4\|2  + 5
--R                              Type: Equation(RealClosure(Fraction(Integer)))
--E 60

--S 61 of 67
dst6::Boolean
--R
--R
--R   (61)  true
--R                                                                  Type: Boolean
--E 61

--S 62 of 67
f3:Ran:=sqrt(3,5)
--R
--R
--R         5+-+
--R   (62)  \|3
--R                                        Type: RealClosure(Fraction(Integer))
--E 62

--S 63 of 67
f25:Ran:=sqrt(1/25,5)
--R
--R
--R          +--+
--R          | 1
```

```
--R   (63)  5|--
--R         \|25
--R                                          Type: RealClosure(Fraction(Integer))
--E 63

--S 64 of 67
f32:Ran:=sqrt(32/5,5)
--R
--R
--R          +--+
--R          |32
--R   (64)  5|--
--R         \| 5
--R                                          Type: RealClosure(Fraction(Integer))
--E 64

--S 65 of 67
f27:Ran:=sqrt(27/5,5)
--R
--R
--R          +--+
--R          |27
--R   (65)  5|--
--R         \| 5
--R                                          Type: RealClosure(Fraction(Integer))
--E 65

--S 66 of 67
dst5:=sqrt((f32-f27,3)) = f25*(1+f3-f3**2)
--R
--R
--R          +---------------+
--R          |   +--+    +--+                          +--+
--R          |   |27     |32       5+-+2   5+-+       | 1
--R   (66)  3|- 5|--  + 5|--  = (- \|3   + \|3  + 1) 5|--
--R         \|  \| 5    \| 5                          \|25
--R                               Type: Equation(RealClosure(Fraction(Integer)))
--E 66

--S 67 of 67
dst5::Boolean
--R
--R
--R   (67)  true
--R                                                                  Type: Boolean
--E 67
)spool
)lisp (bye)
```

— RealClosure.help —

```
=======================================================================
RealClosure examples
=======================================================================

The Real Closure 1.0 package provided by Renaud Rioboo consists of
different packages, categories and domains :

The package RealPolynomialUtilitiesPackage which needs a Field F and a
UnivariatePolynomialCategory domain with coefficients in F. It computes
some simple functions such as Sturm and Sylvester sequences sturmSequence,
sylvesterSequence.

The category RealRootCharacterizationCategory provides abstract
functions to work with "real roots" of univariate polynomials. These
resemble variables with some functionality needed to compute important
operations.

The category RealClosedField provides common operations available over
real closed fiels. These include finding all the roots of a univariate
polynomial, taking square (and higher) roots, ...

The domain RightOpenIntervalRootCharacterization is the main code that
provides the functionality of RealRootCharacterizationCategory for the
case of archimedean fields. Abstract roots are encoded with a left
closed right open interval containing the root together with a
defining polynomial for the root.

The RealClosure domain is the end-user code. It provides usual arithmetic
with real algebraic numbers, along with the functionality of a real closed
field. It also provides functions to approximate a real algebraic number
by an element of the base field. This approximation may either be absolute,
approximate or relative (relativeApprox).

=======================================================================
CAVEATS
=======================================================================

Since real algebraic expressions are stored as depending on "real
roots" which are managed like variables, there is an ordering on
these. This ordering is dynamical in the sense that any new algebraic
takes precedence over older ones. In particular every creation
function raises a new "real root". This has the effect that when you
type something like sqrt(2) + sqrt(2) you have two new variables
which happen to be equal. To avoid this name the expression such as in
s2 := sqrt(2) ; s2 + s2

Also note that computing times depend strongly on the ordering you
```

```
implicitly provide. Please provide algebraics in the order which seems
most natural to you.

=====================================================================
LIMITATIONS
=====================================================================

This packages uses algorithms which are published in [1] and [2] which
are based on field arithmetics, in particular for polynomial gcd
related algorithms. This can be quite slow for high degree polynomials
and subresultants methods usually work best. Beta versions of the
package try to use these techniques in a better way and work
significantly faster. These are mostly based on unpublished algorithms
and cannot be distributed. Please contact the author if you have a
particular problem to solve or want to use these versions.

Be aware that approximations behave as post-processing and that all
computations are done exactly. They can thus be quite time consuming when
depending on several ``real roots''.

=====================================================================
REFERENCES
=====================================================================


[1]  R. Rioboo : Real Algebraic Closure of an ordered Field : Implementation
     in Axiom.
     In proceedings of the ISSAC'92 Conference, Berkeley 1992 pp. 206-215.

[2]  Z. Ligatsikas, R. Rioboo, M. F. Roy : Generic computation of the real
     closure of an ordered field.
     In Mathematics and Computers in Simulation Volume 42, Issue 4-6,
     November 1996.

=====================================================================
EXAMPLES
=====================================================================

We shall work with the real closure of the ordered field of
rational numbers.

  Ran := RECLOS(FRAC INT)
    RealClosure Fraction Integer
                              Type: Domain

Some simple signs for square roots, these correspond to an extension
of degree 16 of the rational numbers. Examples provided by J. Abbot.

  fourSquares(a:Ran,b:Ran,c:Ran,d:Ran):Ran==sqrt(a)+sqrt(b)-sqrt(c)-sqrt(d)
                              Type: Void
```

```
These produce values very close to zero.

  squareDiff1 := fourSquares(73,548,60,586)
       +---+    +--+    +---+    +--+
    - \|586  - \|60  + \|548  + \|73
                              Type: RealClosure Fraction Integer

  recip(squareDiff1)
             +---+          +--+  +--+         +--+ +---+            +---+
     ((54602\|548  + 149602\|73 )\|60  + 49502\|73 \|548  + 9900895)\|586
   +
             +--+ +---+             +--+            +---+            +--+
     (154702\|73 \|548  + 30941947)\|60  + 10238421\|548  + 28051871\|73
                              Type: Union(RealClosure Fraction Integer,...)

  sign(squareDiff1)
    1
                              Type: PositiveInteger

  squareDiff2 := fourSquares(165,778,86,990)
       +---+    +--+    +---+    +---+
    - \|990  - \|86  + \|778  + \|165
                              Type: RealClosure Fraction Integer

  recip(squareDiff2)
                +---+           +---+  +--+          +---+ +---+
       ((556778\|778  + 1209010\|165 )\|86  + 401966\|165 \|778  + 144019431)
    *
        +---+
       \|990
   +
              +---+ +---+              +--+             +---+             +---+
     (1363822\|165 \|778  + 488640503)\|86  + 162460913\|778  + 352774119\|165
                              Type: Union(RealClosure Fraction Integer,...)

  sign(squareDiff2)
    1
                              Type: PositiveInteger

  squareDiff3 := fourSquares(217,708,226,692)
       +---+    +---+    +---+    +---+
    - \|692  - \|226  + \|708  + \|217
                              Type: RealClosure Fraction Integer

  recip(squareDiff3)
               +---+         +---+  +---+         +---+ +---+             +---+
     ((- 34102\|708  - 61598\|217 )\|226  - 34802\|217 \|708  - 13641141)\|692
   +
              +---+ +---+             +---+            +---+            +---+
```

```
   (- 60898\|217 \|708  - 23869841)\|226  - 13486123\|708  - 24359809\|217
                              Type: Union(RealClosure Fraction Integer,...)

sign(squareDiff3)
  - 1
                              Type: Integer

squareDiff4 := fourSquares(155,836,162,820)
     +---+    +---+    +---+    +---+
  - \|820  - \|162  + \|836  + \|155
                              Type: RealClosure Fraction Integer

recip(squareDiff4)
             +---+         +---+  +---+         +---+ +---+             +---+
   ((- 37078\|836  - 86110\|155 )\|162  - 37906\|155 \|836  - 13645107)\|820
 +
            +---+ +---+             +---+            +---+            +---+
   (- 85282\|155 \|836  - 30699151)\|162  - 13513901\|836  - 31384703\|155
                              Type: Union(RealClosure Fraction Integer,...)

sign(squareDiff4)
  - 1
                              Type: Integer

squareDiff5 := fourSquares(591,772,552,818)
     +---+    +---+    +---+    +---+
  - \|818  - \|552  + \|772  + \|591
                              Type: RealClosure Fraction Integer

recip(squareDiff5)
           +---+         +---+  +---+         +---+ +---+             +---+
   ((70922\|772  + 81058\|591 )\|552  + 68542\|591 \|772  + 46297673)\|818
 +
          +---+ +---+             +---+            +---+            +---+
   (83438\|591 \|772  + 56359389)\|552  + 47657051\|772  + 54468081\|591
                              Type: Union(RealClosure Fraction Integer,...)

sign(squareDiff5)
  1
                              Type: PositiveInteger

squareDiff6 := fourSquares(434,1053,412,1088)
     +----+    +---+    +----+    +---+
  - \|1088  - \|412  + \|1053  + \|434
                              Type: RealClosure Fraction Integer

recip(squareDiff6)
              +----+          +---+  +---+          +---+ +----+
     ((115442\|1053  + 179818\|434 )\|412  + 112478\|434 \|1053  + 76037291)
  *
```

```
      +----+
     \|1088
 +
         +---+ +----+              +---+            +----+             +---+
 (182782\|434 \|1053  + 123564147)\|412  + 77290639\|1053  + 120391609\|434
                            Type: Union(RealClosure Fraction Integer,...)

sign(squareDiff6)
  1
                            Type: PositiveInteger

squareDiff7 := fourSquares(514,1049,446,1152)
     +----+    +---+    +----+    +---+
  - \|1152  - \|446  + \|1049  + \|514
                            Type: RealClosure Fraction Integer

recip(squareDiff7)
              +----+          +---+  +---+          +---+ +----+
     ((349522\|1049  + 499322\|514 )\|446  + 325582\|514 \|1049  + 239072537)
  *
      +----+
     \|1152
 +
         +---+ +----+              +---+             +----+             +---+
 (523262\|514 \|1049  + 384227549)\|446  + 250534873\|1049  + 357910443\|514
                            Type: Union(RealClosure Fraction Integer,...)

sign(squareDiff7)
  1
                            Type: PositiveInteger

squareDiff8 := fourSquares(190,1751,208,1698)
     +----+    +---+    +----+    +---+
  - \|1698  - \|208  + \|1751  + \|190
                            Type: RealClosure Fraction Integer

recip(squareDiff8)
                  +----+          +---+  +---+          +---+ +----+
         (- 214702\|1751  - 651782\|190 )\|208  - 224642\|190 \|1751
       +
         - 129571901
  *
      +----+
     \|1698
 +
             +---+ +----+              +---+             +----+
   (- 641842\|190 \|1751  - 370209881)\|208  - 127595865\|1751
 +
               +---+
   - 387349387\|190
```

```
                              Type: Union(RealClosure Fraction Integer,...)

  sign(squareDiff8)
    - 1
                              Type: Integer
```

This should give three digits of precision

```
  relativeApprox(squareDiff8,10**(-3))::Float
    - 0.2340527771 5937700123 E -10
                              Type: Float
```

The sum of these 4 roots is 0

```
  l := allRootsOf((x**2-2)**2-2)$Ran
    [%A33,%A34,%A35,%A36]
                              Type: List RealClosure Fraction Integer
```

Check that they are all roots of the same polynomial

```
  removeDuplicates map(mainDefiningPolynomial,l)
      4     2
    [?  - 4?  + 2]
       Type: List Union(
                   SparseUnivariatePolynomial RealClosure Fraction Integer,
                   "failed")
```

We can see at a glance that they are separate roots

```
  map(mainCharacterization,l)
    [[- 2,- 1[,[- 1,0[,[0,1[,[1,2[]
       Type: List Union(
              RightOpenIntervalRootCharacterization(
               RealClosure Fraction Integer,
               SparseUnivariatePolynomial RealClosure Fraction Integer),
              "failed")
```

Check the sum and product

```
  [reduce(+,l),reduce(*,l)-2]
    [0,0]
                    Type: List RealClosure Fraction Integer
```

A more complicated test that involve an extension of degree 256.
This is a way of checking nested radical identities.

```
  (s2, s5, s10) := (sqrt(2)$Ran, sqrt(5)$Ran, sqrt(10)$Ran)
     +--+
    \|10
                    Type: RealClosure Fraction Integer
```

```
  eq1:=sqrt(s10+3)*sqrt(s5+2) - sqrt(s10-3)*sqrt(s5-2) = sqrt(10*s2+10)
       +---------+ +--------+    +---------+ +--------+   +-----------+
       | +--+      | +-+         | +--+      | +-+        |   +-+
    - \|\|10  - 3 \|\|5  - 2  + \|\|10  + 3 \|\|5  + 2 = \|10\|2  + 10
                    Type: Equation RealClosure Fraction Integer

  eq1::Boolean
    true
                    Type: Boolean

  eq2:=sqrt(s5+2)*sqrt(s2+1) - sqrt(s5-2)*sqrt(s2-1) = sqrt(2*s10+2)
       +--------+ +--------+    +--------+ +--------+   +----------+
       | +-+      | +-+         | +-+      | +-+        |  +--+
    - \|\|5  - 2 \|\|2  - 1  + \|\|5  + 2 \|\|2  + 1 = \|2\|10  + 2
                    Type: Equation RealClosure Fraction Integer

  eq2::Boolean
    true
                    Type: Boolean
```

Some more examples from J. M. Arnaudies

```
  s3 := sqrt(3)$Ran
     +-+
    \|3
                    Type: RealClosure Fraction Integer

  s7:= sqrt(7)$Ran
     +-+
    \|7
                    Type: RealClosure Fraction Integer

  e1 := sqrt(2*s7-3*s3,3)
     +-------------+
    3|  +-+     +-+
    \|2\|7  - 3\|3
                    Type: RealClosure Fraction Integer

  e2 := sqrt(2*s7+3*s3,3)
     +-------------+
    3|  +-+     +-+
    \|2\|7  + 3\|3
                    Type: RealClosure Fraction Integer
```

This should be null

```
  e2-e1-s3
    0
                    Type: RealClosure Fraction Integer
```

```
A quartic polynomial

  pol : UP(x,Ran) := x**4+(7/3)*x**2+30*x-(100/3)
     4   7  2         100
    x  + - x  + 30x - ---
         3             3
                  Type: UnivariatePolynomial(x,RealClosure Fraction Integer)

Add some cubic roots

  r1 := sqrt(7633)$Ran
     +----+
    \|7633
                        Type: RealClosure Fraction Integer

  alpha := sqrt(5*r1-436,3)/3
       +--------------+
    1 3|  +----+
    - \|5\|7633  - 436
    3
                        Type: RealClosure Fraction Integer

  beta := -sqrt(5*r1+436,3)/3
         +--------------+
      1 3|  +----+
    - - \|5\|7633  + 436
      3
                        Type: RealClosure Fraction Integer

this should be null

  pol.(alpha+beta-1/3)
    0
                        Type: RealClosure Fraction Integer

A quintic polynomial

  qol : UP(x,Ran) := x**5+10*x**3+20*x+22
     5      3
    x  + 10x  + 20x + 22
              Type: UnivariatePolynomial(x,RealClosure Fraction Integer)

Add some cubic roots

  r2 := sqrt(153)$Ran
     +---+
    \|153
                          Type: RealClosure Fraction Integer
```

```
  alpha2 := sqrt(r2-11,5)
     +-----------+
    5| +---+
    \|\|153  - 11
                          Type: RealClosure Fraction Integer

  beta2 := -sqrt(r2+11,5)
       +-----------+
      5| +---+
    - \|\|153  + 11
                          Type: RealClosure Fraction Integer

this should be null

  qol(alpha2+beta2)
    0
                          Type: RealClosure Fraction Integer

Finally, some examples from the book Computer Algebra by Davenport,
Siret and Tournier (page 77).  The last one is due to Ramanujan.

  dst1:=sqrt(9+4*s2)=1+2*s2
     +---------+
     |  +-+         +-+
    \|4\|2  + 9 = 2\|2  + 1
                          Type: Equation RealClosure Fraction Integer

  dst1::Boolean
    true
                          Type: Boolean

  s6:Ran:=sqrt 6
     +-+
    \|6
                          Type: RealClosure Fraction Integer

  dst2:=sqrt(5+2*s6)+sqrt(5-2*s6) = 2*s3
     +-----------+    +---------+
     |    +-+         |  +-+         +-+
    \|- 2\|6  + 5  + \|2\|6  + 5 = 2\|3
                          Type: Equation RealClosure Fraction Integer

  dst2::Boolean
    true
                          Type: Boolean

  s29:Ran:=sqrt 29
     +--+
    \|29
                          Type: RealClosure Fraction Integer
```

```
dst4:=sqrt(16-2*s29+2*sqrt(55-10*s29)) = sqrt(22+2*s5)-sqrt(11+2*s29)+s5
  +--------------------------------+
  |  +--------------+                  +-----------+    +----------+
  |  |     +--+           +--+          |  +--+          |  +-+          +-+
 \|2\|- 10\|29  + 55  - 2\|29  + 16 = - \|2\|29  + 11  + \|2\|5  + 22  + \|5
                        Type: Equation RealClosure Fraction Integer

dst4::Boolean
  true
                        Type: Boolean

dst6:=sqrt((112+70*s2)+(46+34*s2)*s5) = (5+4*s2)+(3+s2)*s5
   +--------------------------------+
   |    +-+       +-+      +-+           +-+      +-+     +-+
  \|(34\|2  + 46)\|5  + 70\|2  + 112 = (\|2  + 3)\|5  + 4\|2  + 5
                        Type: Equation RealClosure Fraction Integer

dst6::Boolean
  true
                        Type: Boolean

f3:Ran:=sqrt(3,5)
  5+-+
  \|3
                        Type: RealClosure Fraction Integer

f25:Ran:=sqrt(1/25,5)
   +--+
   | 1
  5|--
  \|25
                        Type: RealClosure Fraction Integer

f32:Ran:=sqrt(32/5,5)
   +--+
   |32
  5|--
  \| 5
                        Type: RealClosure Fraction Integer

f27:Ran:=sqrt(27/5,5)
   +--+
   |27
  5|--
  \| 5
                        Type: RealClosure Fraction Integer

dst5:=sqrt((f32-f27,3)) = f25*(1+f3-f3**2)
   +---------------+
```


```
     |   +--+    +--+                          +--+
     |   |27     |32       5+-+2   5+-+        | 1
    3|- 5|--  + 5|--  = (- \|3   + \|3  + 1) 5|--
    \|  \| 5    \| 5                          \|25
                          Type: Equation RealClosure Fraction Integer

  dst5::Boolean
    true
                          Type: Boolean
```

See Also:
o)help RightOpenIntervalRootCharacterization
o)help RealClosedField
o)help RealRootCharacterizationCategory
o)help UnivariatePolynomialCategory
o)help Field
o)help RealPolynomialUtilitiesPackage
o)show RealClosure

———-

19.3.1 RealClosure (RECLOS)



See

⇒ “RightOpenIntervalRootCharacterization” (ROIRC) 19.11.1 on page 2276

Exports:

0	1	abs	algebraicOf
allRootsOf	approximate	associates?	characteristic
coerce	divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	factor	gcd
gcdPolynomial	hash	inv	latex
lcm	mainCharacterization	mainDefiningPolynomial	mainForm
mainValue	max	multiEuclidean	min
negative?	nthRoot	one?	positive?
prime?	principalIdeal	recip	relativeApprox
rename	rename!	retract	retractIfCan
rootOf	sample	sign	sizeLess?
sqrt	squareFree	squareFreePart	subtractIfCan
unit?	unitCanonical	unitNormal	zero?
?*?	?**?	?+?	?-?
-?	?/?	?<?	?<=?
?=?	?>?	?>=?	?^?
?~=?	?quo?	?rem?	

— domain RECLOS RealClosure —

```
)abbrev domain RECLOS RealClosure
++ Author: Renaud Rioboo
++ Date Created: summer 1988
++ Date Last Updated: January 2004
++ Basic Functions: provides computations in an ordered real closure
++ Related Constructors: RightOpenIntervalRootCharacterization
++ Also See:
++ AMS Classifications:
++ Keywords: Real Algebraic Numbers
++ References:
++ Description:
++ This domain implements the real closure of an ordered field.
++ Note:
++ The code here is generic i.e. it does not depend of the way the operations
++ are done. The two macros PME and SEG should be passed as functorial
++ arguments to the domain. It does not help much to write a category
++ since non trivial methods cannot be placed there either.
++

RealClosure(TheField): PUB == PRIV where

   TheField   : Join(OrderedRing, Field, RealConstant)

--   ThePols    : UnivariatePolynomialCategory($)
--   PME       ==> ThePols
--   TheCharDom : RealRootCharacterizationCategory($, ThePols )
--   SEG       ==> TheCharDom
-- this does not work yet
```

```
   E         ==> OutputForm
   Z         ==> Integer
   SE        ==> Symbol
   B         ==> Boolean
   SUP       ==> SparseUnivariatePolynomial($)
   N         ==> PositiveInteger
   RN        ==> Fraction Z
   LF        ==> ListFunctions2($,N)
   PME       ==> SparseUnivariatePolynomial($)
   SEG       ==> RightOpenIntervalRootCharacterization($,PME)

   PUB == Join(RealClosedField,
               FullyRetractableTo TheField,
               Algebra TheField) with

       algebraicOf :   (SEG,E) -> $
             ++ \axiom{algebraicOf(char)} is the external number

       mainCharacterization :   $ -> Union(SEG,"failed")
             ++ \axiom{mainCharacterization(x)} is the main algebraic
             ++ quantity of \axiom{x} (\axiom{SEG})

       relativeApprox :     ($,$) -> RN
             ++ \axiom{relativeApprox(n,p)} gives a relative
             ++ approximation of \axiom{n}
             ++ that has precision \axiom{p}

   PRIV == add

-- local functions

       lessAlgebraic  : $ -> $
       newElementIfneeded : (SEG,E) -> $

-- Representation

       Rec := Record(seg: SEG, val:PME, outForm:E, order:N)
       Rep := Union(TheField,Rec)

-- global (mutable) variables

       orderOfCreation : N := 1$N
          -- it is internally used to sort the algebraic levels

       instanceName : Symbol := new()$Symbol
          -- this used to print the results, thus different instanciations
          -- use different names

-- now the code
```

```
relativeApprox(nbe,prec) ==
   nbe case TheField => retract(nbe)
   appr := relativeApprox(nbe.val, nbe.seg, prec)
   -- now appr has the good exact precision but is $
   relativeApprox(appr,prec)


approximate(nbe,prec) ==
   abs(nbe) < prec => 0
   nbe case TheField => retract(nbe)
   appr := approximate(nbe.val, nbe.seg, prec)
   -- now appr has the good exact precision but is $
   approximate(appr,prec)

newElementIfneeded(s,o) ==
  p := definingPolynomial(s)
  degree(p) = 1 =>
      - coefficient(p,0) / leadingCoefficient(p)
  res := [s, monomial(1,1), o, orderOfCreation ]$Rec
  orderOfCreation := orderOfCreation + 1
  res :: $

algebraicOf(s,o) ==
  pol := definingPolynomial(s)
  degree(pol) = 1 =>
    -coefficient(pol,0) / leadingCoefficient(pol)
  res := [s, monomial(1,1), o, orderOfCreation ]$Rec
  orderOfCreation := orderOfCreation + 1
  res :: $

rename!(x,o) ==
  x.outForm := o
  x

rename(x,o) ==
  [x.seg, x.val, o, x.order]$Rec

rootOf(pol,n) ==
 degree(pol) = 0 => "failed"
 degree(pol) = 1 =>
   if n=1
   then
     -coefficient(pol,0) / leadingCoefficient(pol)
   else
     "failed"
 r := rootOf(pol,n)$SEG
 r case "failed" => "failed"
 o := hconcat(instanceName :: E , orderOfCreation :: E)$E
 algebraicOf(r,o)
```

```
allRootsOf(pol:SUP):List($) ==
 degree(pol)=0 => []
 degree(pol)=1 => [-coefficient(pol,0) / leadingCoefficient(pol)]
 liste := allRootsOf(pol)$SEG
 res : List $ := []
 for term in liste repeat
    o := hconcat(instanceName :: E , orderOfCreation :: E)$E
    res := cons(algebraicOf(term,o), res)
 reverse! res

coerce(x:$):$ ==
   x case TheField => x
   [x.seg,x.val rem$PME definingPolynomial(x.seg),x.outForm,x.order]$Rec

positive?(x) ==
   x case TheField => positive?(x)$TheField
   positive?(x.val,x.seg)$SEG

negative?(x) ==
   x case TheField => negative?(x)$TheField
   negative?(x.val,x.seg)$SEG

abs(x) == sign(x)*x

sign(x) ==
   x case TheField => sign(x)$TheField
   sign(x.val,x.seg)$SEG

x < y == positive?(y-x)

x = y == zero?(x-y)

mainCharacterization(x) ==
   x case TheField => "failed"
   x.seg

mainDefiningPolynomial(x) ==
   x case TheField => "failed"
   definingPolynomial x.seg

mainForm(x) ==
   x case TheField => "failed"
   x.outForm

mainValue(x) ==
   x case TheField => "failed"
   x.val

coerce(x:$):E ==
   x case TheField => x::TheField :: E
```

```
    xx:$ := coerce(x)
    outputForm(univariate(xx.val),x.outForm)$SUP


inv(x) ==
    (res:= recip x) case "failed" => error "Division by 0"
    res :: $

recip(x) ==
  x case TheField =>
     if ((r := recip(x)$TheField) case TheField)
     then r::$
     else "failed"
  if ((r := recip(x.val,x.seg)$SEG) case "failed")
  then "failed"
  else lessAlgebraic([x.seg,r::PME,x.outForm,x.order]$Rec)

(n:Z * x:$):$ ==
    x case TheField => n *$TheField x
    zero?(n) => 0
    one?(n) => x
    [x.seg,map(z+->n*z, x.val),x.outForm,x.order]$Rec

(rn:TheField * x:$):$ ==
    x case TheField => rn *$TheField x
    zero?(rn) => 0
    one?(rn) => x
    [x.seg,map(z+->rn*z, x.val),x.outForm,x.order]$Rec

(x:$ * y:$):$ ==
    (x case TheField) and (y case TheField) => x *$TheField y
    (x case TheField) => x::TheField * y
        -- x is no longer TheField
    (y case TheField) => y::TheField * x
        -- now both are algebraic
    y.order > x.order =>
      [y.seg,map(z+->x*z , y.val),y.outForm,y.order]$Rec
    x.order > y.order =>
      [x.seg,map(z+->z*y , x.val),x.outForm,x.order]$Rec
        -- now x.exp = y.exp
        -- we will multiply the polynomials and then reduce
        -- however wee need to call lessAlgebraic
    lessAlgebraic([x.seg,
                   (x.val * y.val) rem definingPolynomial(x.seg),
                   x.outForm,
                   x.order]$Rec)

nonNull(rep:Rec):$ ==
  degree(rep.val)=0 => leadingCoefficient(rep.val)
  numberOfMonomials(rep.val) = 1 => rep
```

```
        zero?(rep.val,rep.seg)$SEG => 0
        rep

--      zero?(x) ==
--         x case TheField => zero?(x)$TheField
--         zero?(x.val,x.seg)$SEG

      zero?(x) ==
         x case TheField => zero?(x)$TheField
         false

      x + y ==
         (x case TheField) and (y case TheField) => x +$TheField y
         (x case TheField) =>
            if zero?(x)
            then
              y
            else
              nonNull([y.seg,x::PME+(y.val),y.outForm,y.order]$Rec)
            -- x is no longer TheField
         (y case TheField) =>
            if zero?(y)
            then
              x
            else
              nonNull([x.seg,(x.val)+y::PME,x.outForm,x.order]$Rec)
            -- now both are algebraic
         y.order > x.order =>
              nonNull([y.seg,x::PME+y.val,y.outForm,y.order]$Rec)
         x.order > y.order =>
              nonNull([x.seg,(x.val)+y::PME,x.outForm,x.order]$Rec)
             -- now x.exp = y.exp
             -- we simply add polynomials (since degree cannot increase)
             -- however wee need to call lessAlgebraic
         nonNull([x.seg,x.val + y.val,x.outForm,x.order])


      -x ==
         x case TheField => -$TheField (x::TheField)
         [x.seg,-$PME x.val,x.outForm,x.order]$Rec


      retractIfCan(x:$):Union(TheField,"failed") ==
         x case TheField => x
         o := x.order
         res := lessAlgebraic x
         res case TheField => res
         o = res.order => "failed"
         retractIfCan res
```

```
        retract(x:$):TheField ==
           x case TheField => x
           o := x.order
           res := lessAlgebraic x
           res case TheField => res
           o = res.order => error "Can't retract"
           retract res


        lessAlgebraic(x) ==
           x case TheField => x
           degree(x.val) = 0 => leadingCoefficient(x.val)
           def := definingPolynomial(x.seg)
           degree(def) = 1 =>
             x.val.(- coefficient(def,0) / leadingCoefficient(def))
           x

        0 == (0$TheField) :: $

        1 == (1$TheField) :: $

        coerce(rn:TheField):$ == rn :: $
```

———-

— **RECLOS.dotabb** —

```
"RECLOS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RECLOS"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"RECLOS" -> "ALIST"
```

———-

19.4 domain RMATRIX RectangularMatrix

— **RectangularMatrix.input** —

```
)set break resume
)sys rm -f RectangularMatrix.output
)spool RectangularMatrix.output
)set message test on
)set message auto off
)clear all
```

```
--S 1 of 1
)show RectangularMatrix
--R
--R RectangularMatrix(m: NonNegativeInteger,n: NonNegativeInteger,R: Ring)  is a domain construc
--R Abbreviation for RectangularMatrix is RMATRIX
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RMATRIX
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 0 : () -> %                           antisymmetric? : % -> Boolean
--R coerce : % -> Matrix(R)               coerce : % -> OutputForm
--R copy : % -> %                         diagonal? : % -> Boolean
--R elt : (%,Integer,Integer,R) -> R      elt : (%,Integer,Integer) -> R
--R empty : () -> %                       empty? : % -> Boolean
--R eq? : (%,%) -> Boolean                hash : % -> SingleInteger
--R latex : % -> String                   listOfLists : % -> List(List(R))
--R map : (((R,R) -> R),%,%) -> %         map : ((R -> R),%) -> %
--R matrix : List(List(R)) -> %           maxColIndex : % -> Integer
--R maxRowIndex : % -> Integer            minColIndex : % -> Integer
--R minRowIndex : % -> Integer            ncols : % -> NonNegativeInteger
--R nrows : % -> NonNegativeInteger       qelt : (%,Integer,Integer) -> R
--R sample : () -> %                      square? : % -> Boolean
--R symmetric? : % -> Boolean             zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (NonNegativeInteger,%) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R column : (%,Integer) -> DirectProduct(m,R)
--R convert : % -> InputForm if R has KONVERT(INFORM)
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R dimension : () -> CardinalNumber if R has FIELD
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((R -> R),%) -> % if $ has shallowlyMutable
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R nullSpace : % -> List(DirectProduct(m,R)) if R has INTDOM
--R nullity : % -> NonNegativeInteger if R has INTDOM
```

```
--R parts : % -> List(R) if $ has finiteAggregate
--R rank : % -> NonNegativeInteger if R has INTDOM
--R rectangularMatrix : Matrix(R) -> %
--R row : (%,Integer) -> DirectProduct(n,R)
--R rowEchelon : % -> % if R has EUCDOM
--R size? : (%,NonNegativeInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **RectangularMatrix.help** —

```
=====================================================================
RectangularMatrix examples
=====================================================================

See Also:
o )show RectangularMatrix
```

———-

19.4.1 RectangularMatrix (RMATRIX)



See

⇒ “IndexedMatrix” (IMATRIX) 10.12.1 on page 1208
⇒ “Matrix” (MATRIX) 14.7.1 on page 1590
⇒ “SquareMatrix” (SQMATRIX) 20.27.1 on page 2514

Exports:

0	antisymmetric?	any?	coerce	column
convert	copy	count	diagonal?	dimension
elt	empty	empty?	eq?	eval
every?	exquo	hash	latex	less?
listOfLists	map	map!	matrix	maxColIndex
maxRowIndex	member?	members	minColIndex	minRowIndex
more?	ncols	nrows	nullSpace	nullity
parts	qelt	rank	rectangularMatrix	row
rowEchelon	sample	size?	square?	subtractIfCan
symmetric?	zero?	#?	?~=?	?*?
?/?	?+?	?-?	-?	?=?

— domain RMATRIX RectangularMatrix —

```
)abbrev domain RMATRIX RectangularMatrix
++ Author: Grabmeier, Gschnitzer, Williamson
++ Date Created: 1987
++ Date Last Updated: July 1990
++ Basic Operations:
++ Related Domains: IndexedMatrix, Matrix, SquareMatrix
++ Also See:
++ AMS Classifications:
++ Keywords: matrix, linear algebra
++ Examples:
++ References:
++ Description:
++ \spadtype{RectangularMatrix} is a matrix domain where the number of rows
++ and the number of columns are parameters of the domain.

RectangularMatrix(m,n,R): Exports == Implementation where
  m,n : NonNegativeInteger
  R   : Ring
  Row ==> DirectProduct(n,R)
  Col ==> DirectProduct(m,R)
  Exports ==> Join(RectangularMatrixCategory(m,n,R,Row,Col),_
                  CoercibleTo Matrix R) with

    if R has Field then VectorSpace R

    if R has ConvertibleTo InputForm then ConvertibleTo InputForm

    rectangularMatrix: Matrix R -> $
      ++ \spad{rectangularMatrix(m)} converts a matrix of type \spadtype{Matrix}
      ++ to a matrix of type \spad{RectangularMatrix}.
    coerce: $ -> Matrix R
      ++ \spad{coerce(m)} converts a matrix of type \spadtype{RectangularMatrix}
      ++ to a matrix of type \spad{Matrix}.

  Implementation ==> Matrix R add
```

```
minr ==> minRowIndex
maxr ==> maxRowIndex
minc ==> minColIndex
maxc ==> maxColIndex
mini ==> minIndex
maxi ==> maxIndex

ZERO := new(m,n,0)$Matrix(R) pretend $
0    == ZERO

coerce(x:$):OutputForm == coerce(x pretend Matrix R)$Matrix(R)

matrix(l: List List R) ==
  -- error check: this is a top level function
  #l ^= m => error "matrix: wrong number of rows"
  for ll in l repeat
    #ll ^= n => error "matrix: wrong number of columns"
  ans : Matrix R := new(m,n,0)
  for i in minr(ans)..maxr(ans) for ll in l repeat
    for j in minc(ans)..maxc(ans) for r in ll repeat
      qsetelt_!(ans,i,j,r)
  ans pretend $

row(x,i)    == directProduct row(x pretend Matrix(R),i)
column(x,j) == directProduct column(x pretend Matrix(R),j)

coerce(x:$):Matrix(R) == copy(x pretend Matrix(R))

rectangularMatrix x ==
  (nrows(x) ^= m) or (ncols(x) ^= n) =>
    error "rectangularMatrix: matrix of bad dimensions"
  copy(x) pretend $

if R has EuclideanDomain then

  rowEchelon x == rowEchelon(x pretend Matrix(R)) pretend $

if R has IntegralDomain then

  rank x    == rank(x pretend Matrix(R))
  nullity x == nullity(x pretend Matrix(R))
  nullSpace x ==
    [directProduct c for c in nullSpace(x pretend Matrix(R))]

if R has Field then

  dimension() == (m * n) :: CardinalNumber

if R has ConvertibleTo InputForm then
  convert(x:$):InputForm ==
```

```
        convert [convert("rectangularMatrix"::Symbol)@InputForm,
                 convert(x::Matrix(R))]$List(InputForm)
```

———-

— RMATRIX.dotabb —

```
"RMATRIX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RMATRIX"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"RMATRIX" -> "ALIST"
```

———-

19.5 domain REF Reference

— Reference.input —

```
)set break resume
)sys rm -f Reference.output
)spool Reference.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Reference
--R
--R Reference(S: Type)  is a domain constructor
--R Abbreviation for Reference is REF
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for REF
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               deref : % -> S
--R elt : % -> S                         ref : S -> %
--R setelt : (%,S) -> S                  setref : (%,S) -> S
--R coerce : % -> OutputForm if S has SETCAT
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Reference.help** —

```
====================================================================
Reference examples
====================================================================

See Also:
o )show Reference
```

———-

19.5.1 Reference (REF)



See

⇒ “Boolean” (BOOLEAN) 3.15.1 on page 306
⇒ “IndexedBits” (IBITS) 10.3.1 on page 1169
⇒ “Bits” (BITS) 3.12.1 on page 299

Exports:

coerce	deref	elt	hash	latex
ref	setelt	setref	?=?	?~=?

— **domain REF Reference** —

```
)abbrev domain REF Reference
++ Author: Stephen M. Watt
++ Date Created:
++ Change History:
++ Basic Operations: deref, elt, ref, setelt, setref, =
++ Related Constructors:
++ Keywords:  reference
++ Description:
++ \spadtype{Reference} is for making a changeable instance
```

```
++ of something.

Reference(S:Type): Type with
        ref   : S -> %
          ++  ref(n) creates a pointer (reference) to the object n.
        elt   : % -> S
          ++ elt(n) returns the object n.
        setelt: (%, S) -> S
          ++ setelt(n,m) changes the value of the object n to m.
        -- alternates for when bugs don't allow the above
        deref : % -> S
          ++ deref(n) is equivalent to \spad{elt(n)}.
        setref: (%, S) -> S
          ++ setref(n,m) same as \spad{setelt(n,m)}.
        _=    : (%, %) -> Boolean
          ++ a=b tests if \spad{a} and b are equal.
        if S has SetCategory then SetCategory

    == add
        Rep := Record(value: S)

        p = q        == EQ(p, q)$Lisp
        ref v        == [v]
        elt p        == p.value
        setelt(p, v) == p.value := v
        deref p      == p.value
        setref(p, v) == p.value := v

        if S has SetCategory then
          coerce p ==
            prefix(message("ref"@String), [p.value::OutputForm])
```

———-

— REF.dotabb —

```
"REF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=REF",shape=ellipse]
"TYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TYPE"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"REF" -> "TYPE"
"REF" -> "BASTYPE"
"REF" -> "KOERCE"
```

———-

19.6 domain RGCHAIN RegularChain

— RegularChain.input —

```
)set break resume
)sys rm -f RegularChain.output
)spool RegularChain.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show RegularChain
--R
--R RegularChain(R: GcdDomain,ls: List(Symbol))  is a domain constructor
--R Abbreviation for RegularChain is RGCHAIN
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RGCHAIN
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R collectQuasiMonic : % -> %           copy : % -> %
--R degree : % -> NonNegativeInteger     empty : () -> %
--R empty? : % -> Boolean                eq? : (%,%) -> Boolean
--R hash : % -> SingleInteger            headReduced? : % -> Boolean
--R infRittWu? : (%,%) -> Boolean        initiallyReduced? : % -> Boolean
--R latex : % -> String                  normalized? : % -> Boolean
--R purelyAlgebraic? : % -> Boolean      rest : % -> Union(%,"failed")
--R sample : () -> %                     stronglyReduced? : % -> Boolean
--R trivialIdeal? : % -> Boolean         ?~=? : (%,%) -> Boolean
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R algebraic? : (OrderedVariableList(ls),%) -> Boolean
--R algebraicCoefficients? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean
--R algebraicVariables : % -> List(OrderedVariableList(ls))
--R any? : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> Boolean),%) -> Boolean if $ has
--R augment : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),List(%)) -> List(%)
--R augment : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%) -> List(%)
--R augment : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),List(%)) -> List(%)
--R augment : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> List(%)
--R autoReduced? : (%,((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),List(NewSparseMultivariat
--R basicSet : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),(NewSparseMultivariatePoly
--R basicSet : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),((NewSparseMultivariatePol
--R coHeight : % -> NonNegativeInteger if OrderedVariableList(ls) has FINITE
--R coerce : % -> List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)))
--R collect : (%,OrderedVariableList(ls)) -> %
--R collectUnder : (%,OrderedVariableList(ls)) -> %
--R collectUpper : (%,OrderedVariableList(ls)) -> %
--R construct : List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) -> %
```

```
--R convert : % -> InputForm if NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) has K
--R count : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> Boolean),%) -> NonNe
--R count : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> NonNegativeInteger
--R eval : (%,List(Equation(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))))) -> % i
--R eval : (%,Equation(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)))) -> % if NewS
--R eval : (%,NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),NewSparseMultivariatePo
--R eval : (%,List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),List(NewSparseMul
--R every? : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> Boolean),%) -> Bool
--R extend : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),List(%)) -> List(
--R extend : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%) -> List(%)
--R extend : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),List(%)) -> List(%)
--R extend : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> List(%)
--R extend : (%,NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) -> %
--R extendIfCan : (%,NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) -> Union(%,"fai
--R find : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> Boolean),%) -> Union(
--R first : % -> Union(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),"failed")
--R headReduce : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> NewSparseMult
--R headReduced? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean
--R headRemainder : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Record(num
--R initiallyReduce : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> NewSpars
--R initiallyReduced? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolea
--R initials : % -> List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)))
--R internalAugment : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%) -> %
--R internalAugment : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> %
--R intersect : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),List(%)) -> List(%)
--R intersect : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),List(%)) -> Li
--R intersect : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%) -> List(%)
--R intersect : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> List(%)
--R invertible? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean
--R invertible? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> List(Record(
--R invertibleElseSplit? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Uni
--R invertibleSet : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> List(%)
--R last : % -> Union(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),"failed")
--R lastSubResultant : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),NewSparseMult
--R lastSubResultantElseSplit : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),NewS
--R less? : (%,NonNegativeInteger) -> Boolean
--R mainVariable? : (OrderedVariableList(ls),%) -> Boolean
--R mainVariables : % -> List(OrderedVariableList(ls))
--R map : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> NewSparseMultivariateP
--R map! : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> NewSparseMultivariate
--R member? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean if $ has
--R members : % -> List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) if $ has fin
--R more? : (%,NonNegativeInteger) -> Boolean
--R mvar : % -> OrderedVariableList(ls)
--R normalized? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean
--R parts : % -> List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) if $ has finit
--R purelyAlgebraic? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean
--R purelyAlgebraicLeadingMonomial? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)
--R purelyTranscendental? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Bo
--R quasiComponent : % -> Record(close: List(NewSparseMultivariatePolynomial(R,OrderedVariableLi
```

```
--R reduce : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%,((NewSparseMultivariatePolynomial
--R reduce : (((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),NewSparseMultivariatePolynomial(R
--R reduce : (((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),NewSparseMultivariatePolynomial(R
--R reduce : (((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),NewSparseMultivariatePolynomial(R
--R reduceByQuasiMonic : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> NewSparseMultivar
--R reduced? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%,((NewSparseMultivariatePolynomi
--R remainder : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Record(rnum: R,polnum: New
--R remove : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> Boolean),%) -> % if $ has finit
--R remove : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> % if $ has finiteAggregate an
--R removeDuplicates : % -> % if $ has finiteAggregate and NewSparseMultivariatePolynomial(R,OrderedVariable
--R removeZero : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> NewSparseMultivariatePoly
--R retract : List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) -> %
--R retractIfCan : List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) -> Union(%,"failed")
--R rewriteIdealWithHeadRemainder : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%) ->
--R rewriteIdealWithRemainder : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%) -> List
--R rewriteSetWithReduction : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),%,((NewSpars
--R roughBase? : % -> Boolean if R has INTDOM
--R roughEqualIdeals? : (%,%) -> Boolean if R has INTDOM
--R roughSubIdeal? : (%,%) -> Boolean if R has INTDOM
--R roughUnitIdeal? : % -> Boolean if R has INTDOM
--R select : (%,OrderedVariableList(ls)) -> Union(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),
--R select : ((NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)) -> Boolean),%) -> % if $ has finit
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : (%,OrderedVariableList(ls)) -> Record(under: %,floor: %,upper: %)
--R squareFreePart : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> List(Record(val: NewS
--R stronglyReduce : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> NewSparseMultivariate
--R stronglyReduced? : (NewSparseMultivariatePolynomial(R,OrderedVariableList(ls)),%) -> Boolean
--R triangular? : % -> Boolean if R has INTDOM
--R variables : % -> List(OrderedVariableList(ls))
--R zeroSetSplit : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),Boolean,Boolean) -> Lis
--R zeroSetSplit : (List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))),Boolean) -> List(%)
--R zeroSetSplit : List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) -> List(%)
--R zeroSetSplitIntoTriangularSystems : List(NewSparseMultivariatePolynomial(R,OrderedVariableList(ls))) ->
--R
--E 1

)spool
)lisp (bye)
```

———-


— RegularChain.help —

```
========================================================================
RegularChain examples
========================================================================

See Also:
o )show RegularChain
```

———-

19.6.1 RegularChain (RGCHAIN)



Exports:

algebraic?
algebraicCoefficients?
algebraicVariables
any?
augment
autoReduced?
basicSet
coHeight
coerce
collect
collectQuasiMonic
collectUnder
collectUpper
construct
convert
copy
count
degree
empty
empty?
eq?
eval
every?
extend
extendIfCan
find
first
hash
headReduce
headReduced?
headRemainder
infRittWu?
initiallyReduce
initiallyReduced?
initials
internalAugment
intersect
invertible?
invertibleElseSplit?
invertibleSet
last
lastSubResultant
lastSubResultantElseSplit
latex
less?
mainVariable?
mainVariables
map
map!
member?
members
more?
mvar
normalized?
parts
purelyAlgebraic?
purelyAlgebraicLeadingMonomial?
purelyTranscendental?
quasiComponent
reduce
reduceByQuasiMonic
reduced?
remainder
remove
removeDuplicates
removeZero
rest
retract
retractIfCan
rewriteIdealWithHeadRemainder
rewriteIdealWithRemainder
rewriteSetWithReduction
roughBase?
roughEqualIdeals?
roughSubIdeal?
roughUnitIdeal?
sample
select
size?
sort
squareFreePart
stronglyReduce
stronglyReduced?
triangular?
trivialIdeal?
variables
zeroSetSplit
zeroSetSplitIntoTriangularSystems
#?
?~=?
?=?

— domain RGCHAIN RegularChain —

```
)abbrev domain RGCHAIN RegularChain
++ Author: Marc Moreno Maza
++ Date Created: 01/1999
++ Date Last Updated: 23/01/1999
++ Description:
++ A domain for regular chains (i.e. regular triangular sets) over
++ a Gcd-Domain and with a fix list of variables.
++ This is just a front-end for the \spadtype{RegularTriangularSet}
++ domain constructor.

RegularChain(R,ls): Exports == Implementation where
  R : GcdDomain
  ls: List Symbol
  V ==> OrderedVariableList ls
  E ==> IndexedExponents V
  P ==> NewSparseMultivariatePolynomial(R,V)
  TS ==> RegularTriangularSet(R,E,V,P)

  Exports ==  RegularTriangularSetCategory(R,E,V,P) with
     zeroSetSplit: (List P, Boolean, Boolean) -> List $
       ++ \spad{zeroSetSplit(lp,clos?,info?)} returns a list \spad{lts} of
       ++ regular chains such that the union of the closures of their regular
       ++ zero sets equals the affine variety associated with \spad{lp}.
       ++ Moreover, if \spad{clos?} is \spad{false} then the union of the
       ++ regular zero set of the \spad{ts} (for \spad{ts} in \spad{lts})
       ++ equals this variety.
       ++ If \spad{info?} is \spad{true} then some information is
       ++ displayed during the computations. See
       ++ zeroSetSplit from RegularTriangularSet.

  Implementation == RegularTriangularSet(R,E,V,P)
```

———-

— RGCHAIN.dotabb —

```
"RGCHAIN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RGCHAIN"]
"RSETCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RSETCAT"]
"RGCHAIN" -> "RSETCAT"
```

———-

19.7 domain REGSET RegularTriangularSet

Several domain constructors implement regular triangular sets (or regular chains). Among them **RegularTriangularSet** and **SquareFreeRegularTriangularSet**. They also implement an algorithm by Marc Moreno Maza for computing triangular decompositions of polynomial systems. This method is refined in the package **LazardSetSolvingPackage** in order to produce decompositions by means of Lazard triangular sets.

— RegularTriangularSet.input —

```
)set break resume
)sys rm -f RegularTriangularSet.output
)spool RegularTriangularSet.output
)set message test on
)set message auto off
)clear all
--S 1 of 34
R := Integer
--R
--R
--R   (1)  Integer
--R                                                          Type: Domain
--E 1

--S 2 of 34
ls : List Symbol := [x,y,z,t]
--R
--R
--R   (2)  [x,y,z,t]
--R                                                    Type: List(Symbol)
--E 2

--S 3 of 34
V := OVAR(ls)
--R
--R
--R   (3)  OrderedVariableList([x,y,z,t])
--R                                                          Type: Domain
--E 3

--S 4 of 34
E := IndexedExponents V
--R
--R
--R   (4)  IndexedExponents(OrderedVariableList([x,y,z,t]))
--R                                                          Type: Domain
--E 4

--S 5 of 34
```

```
P := NSMP(R, V)
--R
--R
--R   (5)
--R   NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--R                                                                  Type: Domain
--E 5

--S 6 of 34
x: P := 'x
--R
--R
--R   (6)  x
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 6

--S 7 of 34
y: P := 'y
--R
--R
--R   (7)  y
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 7

--S 8 of 34
z: P := 'z
--R
--R
--R   (8)  z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 8

--S 9 of 34
t: P := 't
--R
--R
--R   (9)  t
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 9

--S 10 of 34
T := REGSET(R,E,V,P)
--R
--R
--R   (10)
--R  RegularTriangularSet(Integer,IndexedExponents(OrderedVariableList([x,y,z,t]))
--R  ,OrderedVariableList([x,y,z,t]),NewSparseMultivariatePolynomial(Integer,Order
--R  edVariableList([x,y,z,t])))
--R                                                                  Type: Domain
--E 10
```

```
--S 11 of 34
p1 := x ** 31 - x ** 6 - x - y
--R
--R
--R          31    6
--R   (11)  x   - x  - x - y
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 11

--S 12 of 34
p2 := x ** 8  - z
--R
--R
--R          8
--R   (12)  x  - z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 12

--S 13 of 34
p3 := x ** 10 - t
--R
--R
--R          10
--R   (13)  x   - t
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 13

--S 14 of 34
lp := [p1, p2, p3]
--R
--R
--R           31    6          8      10
--R   (14)  [x   - x  - x - y,x  - z,x   - t]
--RType: List(NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t])))
--E 14

--S 15 of 34
zeroSetSplit(lp)$T
--R
--R
--R            5    4      2     3     8     5    3    2   4                2
--R   (15)  [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z }]
--IType: List(RegularTriangularSet(Integer,IndexedExponents(...
--E 15

--S 16 of 34
lts := zeroSetSplit(lp,false)$T
--R
--R
```

```
--R   (16)
--R      5    4      2     3     8     5    3    2   4               2
--R   [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z },
--R      3      5          2     3         2
--R    {t  - 1,z  - t,t z y  + 2z y + 1,z x  - t}, {t,z,y,x}]
--IType: List(RegularTriangularSet(Integer,IndexedExponents(...
--E 16

--S 17 of 34
[coHeight(ts) for ts in lts]
--R
--R
--R   (17)  [1,0,0]
--R                                                  Type: List(NonNegativeInteger)
--E 17

--S 18 of 34
f1 := y**2*z+2*x*y*t-2*x-z
--R
--R
--R                          2
--R   (18)  (2t y - 2)x + z y  - z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 18

--S 19 of 34
f2:=-x**3*z+ 4*x*y**2*z+4*x**2*y*t+2*y**3*t+4*x**2-10*y**2+4*x*z-10*y*t+2
--R
--R
--R              3              2        2              3      2
--R   (19)  - z x  + (4t y + 4)x  + (4z y  + 4z)x + 2t y  - 10y  - 10t y + 2
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 19

--S 20 of 34
f3 :=  2*y*z*t+x*t**2-x-2*z
--R
--R
--R           2
--R   (20)  (t  - 1)x + 2t z y - 2z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 20

--S 21 of 34
f4:=-x*z**3+4*y*z**2*t+4*x*z*t**2+2*y*t**3+4*x*z+4*z**2-10*y*t- 10*t**2+2
--R
--R
--R             3      2                2     3             2      2
--R   (21)  (- z  + (4t  + 4)z)x + (4t z  + 2t  - 10t)y + 4z  - 10t  + 2
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
```

```
--E 21

--S 22 of 34
lf := [f1, f2, f3, f4]
--R
--R
--R   (22)
--R                     2
--R   [(2t y - 2)x + z y  - z,
--R         3             2        2             3      2
--R    - z x  + (4t y + 4)x  + (4z y  + 4z)x + 2t y  - 10y  - 10t y + 2,
--R      2
--R    (t  - 1)x + 2t z y - 2z,
--R        3      2               2     3             2      2
--R    (- z  + (4t  + 4)z)x + (4t z  + 2t  - 10t)y + 4z  - 10t  + 2]
--RType: List(NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t])))
--E 22

--S 23 of 34
zeroSetSplit(lf)$T
--R
--R
--R   (23)
--R      2      8      6       2                 3            2
--R   [{t  - 1,z  - 16z  + 256z  - 256,t y - 1,(z  - 8z)x - 8z  + 16},
--R       2      2     2
--R    {3t  + 1,z  - 7t  - 1,y + t,x + z},
--R      8      6      2         3            2
--R    {t  - 10t  + 10t  - 1,z,(t  - 5t)y - 5t  + 1,x},
--R      2      2
--R    {t  + 3,z  - 4,y + t,x - z}]
--IType: List(RegularTriangularSet(Integer,IndexedExponents(...
--E 23

--S 24 of 34
lts2 := zeroSetSplit(lf,false)$T
--R
--R
--R   (24)
--R      8      6      2         3            2
--R   [{t  - 10t  + 10t  - 1,z,(t  - 5t)y - 5t  + 1,x},
--R      2      8      6       2                 3            2
--R    {t  - 1,z  - 16z  + 256z  - 256,t y - 1,(z  - 8z)x - 8z  + 16},
--R       2      2     2                      2      2
--R    {3t  + 1,z  - 7t  - 1,y + t,x + z}, {t  + 3,z  - 4,y + t,x - z}]
--IType: List(RegularTriangularSet(Integer,IndexedExponents(...
--E 24

--S 25 of 34
[coHeight(ts) for ts in lts2]
```

```
--R
--R
--R   (25)  [0,0,0,0]
--R                                                Type: List(NonNegativeInteger)
--E 25

--S 26 of 34
degrees := [degree(ts) for ts in lts2]
--R
--R
--R   (26)  [8,16,4,4]
--R                                                Type: List(NonNegativeInteger)
--E 26

--S 27 of 34
reduce(+,degrees)
--R
--R
--R   (27)  32
--R                                                   Type: PositiveInteger
--E 27

--S 28 of 34
u : R := 2
--R
--R
--R   (28)  2
--R                                                             Type: Integer
--E 28

--S 29 of 34
q1 := 2*(u-1)**2+ 2*(x-z*x+z**2)+ y**2*(x-1)**2- 2*u*x+ 2*y*t*(1-x)*(x-z)+_
      2*u*z*t*(t-y)+ u**2*t**2*(1-2*z)+ 2*u*t**2*(z-x)+ 2*u*t*y*(z-1)+_
      2*u*z*x*(y+1)+ (u**2-2*u)*z**2*t**2+ 2*u**2*z**2+ 4*u*(1-u)*z+_
      t**2*(z-x)**2
--R
--R
--R   (29)
--R       2           2  2        2                            2           2
--R     (y  - 2t y + t )x  + (- 2y  + ((2t + 4)z + 2t)y + (- 2t  + 2)z - 4t  - 2)x
--R   +
--R      2                      2       2          2
--R     y  + (- 2t z - 4t)y + (t  + 10)z  - 8z + 4t  + 2
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 29

--S 30 of 34
q2 := t*(2*z+1)*(x-z)+ y*(z+2)*(1-x)+ u*(u-2)*t+ u*(1-2*u)*z*t+_
      u*y*(x+u-z*x-1)+ u*(u+1)*z**2*t
--R
```

```
--R
--R                                                2
--R   (30)  (- 3z y + 2t z + t)x + (z + 4)y + 4t z  - 7t z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 30

--S 31 of 34
q3 := -u**2*(z-1)**2+ 2*z*(z-x)-2*(x-1)
--R
--R
--R                          2
--R   (31)  (- 2z - 2)x - 2z  + 8z - 2
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 31

--S 32 of 34
q4 := u**2+4*(z-x**2)+3*y**2*(x-1)**2- 3*t**2*(z-x)**2+_
      3*u**2*t**2*(z-1)**2+u**2*z*(z-2)+6*u*t*y*(z+x+z*x-1)
--R
--R
--R   (32)
--R        2     2      2        2                       2        2
--R     (3y  - 3t  - 4)x  + (- 6y  + (12t z + 12t)y + 6t z)x + 3y  + (12t z - 12t)y
--R   +
--R        2      2         2           2
--R     (9t  + 4)z  + (- 24t  - 4)z + 12t  + 4
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 32

--S 33 of 34
lq := [q1, q2, q3, q4]
--R
--R
--R   (33)
--R   [
--R         2           2  2
--R       (y  - 2t y + t )x
--R     +
--R            2                             2           2          2
--R       (- 2y  + ((2t + 4)z + 2t)y + (- 2t  + 2)z - 4t  - 2)x + y
--R     +
--R                          2       2          2
--R       (- 2t z - 4t)y + (t  + 10)z  - 8z + 4t  + 2
--R     ,
--R                                          2                         2
--R    (- 3z y + 2t z + t)x + (z + 4)y + 4t z  - 7t z, (- 2z - 2)x - 2z  + 8z - 2,
--R
--R          2     2      2        2                       2        2
--R       (3y  - 3t  - 4)x  + (- 6y  + (12t z + 12t)y + 6t z)x + 3y
--R     +
```

```
--R                          2      2         2            2
--R       (12t z - 12t)y + (9t  + 4)z  + (- 24t  - 4)z + 12t  + 4
--R     ]
--RType: List(NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t])))
--E 33

--S 34 of 34
zeroSetSplit(lq,true,true)$T
--R
--I[1 <4,0> -> |4|; {0}]W[2 <5,0>,<3,1> -> |8|; ...
--R   *** QCMPACK Statistics ***
--R      Table     size:  36
--R      Entries reused:  255
--R
--R   *** REGSETGCD: Gcd Statistics ***
--R      Table     size:  125
--R      Entries reused:  0
--R
--R   *** REGSETGCD: Inv Set Statistics ***
--R      Table     size:  30
--R      Entries reused:  0
--R
--R   (34)
--R   [
--R     {
--R                          24                   23                    22
--R         960725655771966t   + 386820897948702t   + 8906817198608181t
--R       +
--R                           21                     20                     19
--R         2704966893949428t   + 37304033340228264t   + 7924782817170207t
--R       +
--R                            18                     17                      16
--R         93126799040354990t   + 13101273653130910t   + 156146250424711858t
--R       +
--R                            15                     14                     13
--R         16626490957259119t   + 190699288479805763t   + 24339173367625275t
--R       +
--R                             12                     11                      10
--R         180532313014960135t   + 35288089030975378t   + 135054975747656285t
--R       +
--R                            9                     8                     7
--R         34733736952488540t  + 75947600354493972t  + 19772555692457088t
--R       +
--R                            6                    5                     4
--R         28871558573755428t  + 5576152439081664t  + 6321711820352976t
--R       +
--R                       3                   2
--R       438314209312320t  + 581105748367008t  - 60254467992576t + 1449115951104
--R       ,
--R
```

```
--R                                                                      23
--R             2660421086949130238551526573705208236166847418137289185778 4t
--R          +
--R                                                                       22
--R             4431043784246860860672948995282966642386935568550177352652 95t
--R          +
--R                                                                       21
--R             2790783932867012346791413423589883271553213058295470903102 42t
--R          +
--R                                                                        20
--R             3390276361413232465107617176615543054620626391823613392185 226t
--R          +
--R                                                                       19
--R             9414781795035405755541986452203528037197931964738138374341 29t
--R          +
--R                                                                         18
--R             1154785519467947524221169674967394935258574767418432098814 4390t
--R          +
--R                                                                        17
--R             1343609566765597789881701656699413216467215660333356417241 432t
--R          +
--R                                                                         16
--R             2323381386814787350393355161717564085989910298780066356669 9334t
--R          +
--R                                                                       15
--R             8695740205376723369508454405087907408509313364849835733864 33t
--R          +
--R                                                                         14
--R             3156155430587693487541946148696992655424175006510346082047 6969t
--R          +
--R                                                                        13
--R             1271400990287717487442065952547731879554823889855386072264 931t
--R          +
--R                                                                         12
--R             3194508991386373604480252696407954019833704955050329582516 0523t
--R          +
--R                                                                        11
--R             3738735704288144509871371560232845884439102270778010470931 960t
--R          +
--R                                                                         10
--R             2529399751239141202614460143577113158756190553299204569288 5927t
--R          +
--R                                                                        9
--R             5210239009846067123469262799870052773410471135950175008046 524t
--R          +
--R                                                                         8
--R             1508388798693029716625987056860827042740318760623871349112 9188t
--R          +
--R                                                                        7
--R             3522087234692930126383686270775779553481769125670839075109 000t
```

```
--R           +
--R                                                                          6
--R             607994520039568101308653379256888649110124424744003496928858t
--R           +
--R                                                                          5
--R             109063485243390088819991375624798602319698772346993493360368t
--R           +
--R                                                                          4
--R             140581943087190710229443253753833540210283899401966748745835t
--R           +
--R                                                                        3
--R             880715279503204500725366712655077488783478288849336052024 32t
--R           +
--R                                                                         2
--R             135882489433640933229781177155977768016065765482378657129440t
--R           +
--R             - 139572834428822622305598946074003140825166907499756465203 0t
--R           +
--R             33463769297318929927725832570930847259211711285574971392 0
--R        *
--R           z
--R       +
--R                                                                     23
--R         856717548404395287975672596450683393214963710109052116493 6t
--R       +
--R                                                                      22
--R         149792392864201791845708374032728942498797519251667250945721t
--R       +
--R                                                                     21
--R         772583717836458221574108615821597641381230030741903740215 0t
--R       +
--R                                                                       20
--R         110886225412685421449891894070861221118456055676433474219165 t
--R       +
--R                                                                     19
--R         213250494460678865219774480106826053783815789621501732672327t
--R       +
--R                                                                       18
--R         366892907516066619572917789417834351450198789841013143169988 2t
--R       +
--R                                                                     17
--R         171388906471001872879490124368748236314765459039567820048872t
--R       +
--R                                                                      16
--R         719243074691460216666023347733102248314492177164552313965898 6t
--R       +
--R                                                                       15
--R         - 128798674689690072812879965633090291959663143108437362453385t
--R       +
--R                                                                      14
```

```
--R         955301085834142590930642313292113404085602879080352643027067lt
--R       +
--R                                                                      13
--R         - 13296096245675492874538687646300437824658458709144441096603t
--R       +
--R                                                                      12
--R         947580680581414532638308551832533310688169056864427496486441 3t
--R       +
--R                                                                     11
--R         80323468792513345886165985566408492760629879479985626553933 6t
--R       +
--R                                                                      10
--R         73382027592928651659946223492075164006621743026145951733338 5t
--R       +
--R                                                                       9
--R         13080046284803673511643696131119716688805388556409172001871 8t
--R       +
--R                                                                       8
--R         42680594557412554988802295989737057470982160676977543526347 8t
--R       +
--R                                                                     7
--R         89289352685851409579131877590409330010304560151447061358060 0t
--R       +
--R                                                                      6
--R         16791525754606839566319258521813415019815981374653287970136 2t
--R       +
--R                                                                     5
--R         26975741576792298037896715414335783554411315828059140804393 6t
--R       +
--R                                                                      4
--R         38095152786465752903358082980128272408134537268020292019822 4t
--R       +
--R                                                                    3
--R         19785545294228495032998826937601341132725035339452913286656t
--R       +
--R                                                                    2
--R         36477412057384782942366635303396637763303928174935079178528t
--R       +
--R         - 37222128792790386487130804222249762732108902294858386708 8t
--R       +
--R         89079724853114348361230634484013862024728599906874105856
--R       ,
--R         3      2                  3       2
--R      (3z  - 11z  + 8z + 4)y + 2t z  + 4t z  - 5t z - t,
--R                 2
--R      (z + 1)x + z  - 4z + 1}
--R     ]
--IType: List(RegularTriangularSet(Integer,IndexedExponents(...
--E 34
)spool
```

```
)lisp (bye)
```

— RegularTriangularSet.help —

```
====================================================================
RegularTriangularSet examples
====================================================================

The RegularTriangularSet domain constructor implements regular
triangular sets.  These particular triangular sets were introduced by
M. Kalkbrener (1991) in his PhD Thesis under the name regular chains.
Regular chains and their related concepts are presented in the paper
"On the Theories of Triangular sets" By P. Aubry, D. Lazard and
M. Moreno Maza (to appear in the Journal of Symbolic Computation).
The RegularTriangularSet constructor also provides a new method
(by the third author) for solving polynomial system by means of
regular chains.  This method has two ways of solving.  One has the
same specifications as Kalkbrener's algorithm (1991) and the other is
closer to Lazard's method (Discr. App. Math, 1991).  Moreover, this
new method removes redundant component from the decompositions when
this is not too expensive.  This is always the case with
square-free regular chains.  So if you want to obtain decompositions
without redundant components just use the SquareFreeRegularTriangularSet
domain constructor or the LazardSetSolvingPackage package constructor.
See also the LexTriangularPackage and ZeroDimensionalSolvePackage for the
case of algebraic systems with a finite number of (complex) solutions.

One of the main features of regular triangular sets is that they
naturally define towers of simple extensions of a field.  This allows
to perform with multivariate polynomials the same kind of operations
as one can do in an EuclideanDomain.

The RegularTriangularSet constructor takes four arguments.  The first
one, R, is the coefficient ring of the polynomials; it must belong to
the category GcdDomain.  The second one, E, is the exponent monoid of
the polynomials; it must belong to the category OrderedAbelianMonoidSup.
The third one, V, is the ordered set of variables; it must belong to the
category OrderedSet.  The last one is the polynomial ring; it must belong
to the category RecursivePolynomialCategory(R,E,V).  The abbreviation for
RegularTriangularSet is REGSET.  See also the constructor RegularChain
which only takes two arguments, the coefficient ring and the ordered
set of variables; in that case, polynomials are necessarily built with
the NewSparseMultivariatePolynomial domain constructor.

We shall explain now how to use the constructor REGSET and how to read
the decomposition of a polynomial system by means of regular sets.
```

```
Let us give some examples.  We start with an easy one
(Donati-Traverso) in order to understand the two ways of solving
polynomial systems provided by the REGSET constructor.

Define the coefficient ring.

  R := Integer
    Integer
                                Type: Domain

Define the list of variables,

  ls : List Symbol := [x,y,z,t]
    [x,y,z,t]
                                Type: List Symbol

and make it an ordered set;

  V := OVAR(ls)
    OrderedVariableList [x,y,z,t]
                                Type: Domain

then define the exponent monoid.

  E := IndexedExponents V
    IndexedExponents OrderedVariableList [x,y,z,t]
                                Type: Domain

Define the polynomial ring.

  P := NSMP(R, V)
    NewSparseMultivariatePolynomial(Integer,OrderedVariableList [x,y,z,t])
                                Type: Domain

Let the variables be polynomial.

  x: P := 'x
    x
             Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])
  y: P := 'y
    y
             Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])

  z: P := 'z
    z
             Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])
```

```
  t: P := 't
   t
            Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])
```

Now call the RegularTriangularSet domain constructor.

```
  T := REGSET(R,E,V,P)
  RegularTriangularSet(Integer,IndexedExponents OrderedVariableList [x,y,z,t],O
  rderedVariableList [x,y,z,t],NewSparseMultivariatePolynomial(Integer,OrderedV
  ariableList [x,y,z,t]))
                               Type: Domain
```

Define a polynomial system.

```
  p1 := x ** 31 - x ** 6 - x - y
      31    6
     x   - x  - x - y
            Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])

  p2 := x ** 8  - z
     8
    x  - z
            Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])

  p3 := x ** 10 - t
     10
    x   - t
            Type: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t])

  lp := [p1, p2, p3]
      31    6          8      10
    [x   - x  - x - y,x  - z,x   - t]
            Type: List NewSparseMultivariatePolynomial(Integer,
                                     OrderedVariableList [x,y,z,t])
```

First of all, let us solve this system in the sense of Kalkbrener.

```
  zeroSetSplit(lp)$T
       5    4      2     3     8     5    3    2   4                2
    [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z }]
        Type: List RegularTriangularSet(Integer,
                    IndexedExponents OrderedVariableList [x,y,z,t],
                    OrderedVariableList [x,y,z,t],
                    NewSparseMultivariatePolynomial(Integer,
                        OrderedVariableList [x,y,z,t]))
```

And now in the sense of Lazard (or Wu and other authors).

```
  lts := zeroSetSplit(lp,false)$T
      5    4      2     3     8     5    3    2   4                2
   [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z },
      3      5          2     3         2
    {t  - 1,z  - t,t z y  + 2z y + 1,z x  - t}, {t,z,y,x}]
        Type: List RegularTriangularSet(Integer,
                    IndexedExponents OrderedVariableList [x,y,z,t],
                    OrderedVariableList [x,y,z,t],
                    NewSparseMultivariatePolynomial(Integer,
                        OrderedVariableList [x,y,z,t]))
```

We can see that the first decomposition is a subset of the second.
So how can both be correct ?

Recall first that polynomials from a domain of the category
RecursivePolynomialCategory are regarded as univariate polynomials in
their main variable. For instance the second polynomial in the first
set of each decomposition has main variable y and its initial
(i.e. its leading coefficient w.r.t. its main variable) is t z.

Now let us explain how to read the second decomposition. Note that
the non-constant initials of the first set are t^4-t and t z. Then
the solutions described by this first set are the common zeros of
its polynomials that do not cancel the polynomials t^4-t and ty z.
Now the solutions of the input system lp satisfying these equations
are described by the second and the third sets of the decomposition.
Thus, in some sense, they can be considered as degenerated solutions.
The solutions given by the first set are called the generic points of
the system; they give the general form of the solutions. The first
decomposition only provides these generic points. This latter
decomposition is useful when they are many degenerated solutions
(which is sometimes hard to compute) and when one is only interested
in general informations, like the dimension of the input system.

We can get the dimensions of each component of a decomposition as follows.

```
  [coHeight(ts) for ts in lts]
    [1,0,0]
                              Type: List NonNegativeInteger
```

Thus the first set has dimension one. Indeed t can take any value,
except 0 or any third root of 1, whereas z is completely determined
from t, y is given by z and t, and finally x is given by the other
three variables. In the second and the third sets of the second
decomposition the four variables are completely determined and thus
these sets have dimension zero.

We give now the precise specifications of each decomposition. This

```
assume some mathematical knowledge.  However, for the non-expert user,
the above explanations will be sufficient to understand the other
features of the RSEGSET constructor.

The input system lp is decomposed in the sense of Kalkbrener as
finitely many regular sets T1,...,Ts such that the radical ideal
generated by lp is the intersection of the radicals of the saturated
ideals of T1,...,Ts.  In other words, the affine variety associated
with lp is the union of the closures (w.r.t. Zarisky topology) of the
regular-zeros sets of T1,...,Ts.

N. B. The prime ideals associated with the radical of the saturated
ideal of a regular triangular set have all the same dimension;
moreover these prime ideals can be given by characteristic sets with
the same main variables.  Thus a decomposition in the sense of
Kalkbrener is unmixed dimensional.  Then it can be viewed as a lazy
decomposition into prime ideals (some of these prime ideals being
merged into unmixed dimensional ideals).

Now we explain the other way of solving by means of regular triangular
sets.  The input system lp is decomposed in the sense of Lazard as
finitely many regular triangular sets T1,...,Ts such that the affine
variety associated with lp is the union of the regular-zeros sets of
T1,...,Ts.  Thus a decomposition in the sense of Lazard is also a
decomposition in the sense of Kalkbrener; the converse is false as we
have seen before.

When the input system has a finite number of solutions, both ways of
solving provide similar decompositions as we shall see with this
second example (Caprasse).

Define a polynomial system.

  f1 := y**2*z+2*x*y*t-2*x-z
                      2
    (2t y - 2)x + z y  - z
           Type: NewSparseMultivariatePolynomial(Integer,
                    OrderedVariableList [x,y,z,t])

  f2:=-x**3*z+ 4*x*y**2*z+4*x**2*y*t+2*y**3*t+4*x**2-10*y**2+4*x*z-10*y*t+2
         3              2        2              3      2
    - z x  + (4t y + 4)x  + (4z y  + 4z)x + 2t y  - 10y  - 10t y + 2
           Type: NewSparseMultivariatePolynomial(Integer,
                    OrderedVariableList [x,y,z,t])

  f3 :=  2*y*z*t+x*t**2-x-2*z
      2
    (t  - 1)x + 2t z y - 2z
           Type: NewSparseMultivariatePolynomial(Integer,
                    OrderedVariableList [x,y,z,t])
```

```
f4:=-x*z**3+4*y*z**2*t+4*x*z*t**2+2*y*t**3+4*x*z+4*z**2-10*y*t- 10*t**2+2
      3      2               2     3            2      2
  (- z  + (4t  + 4)z)x + (4t z  + 2t  - 10t)y + 4z  - 10t  + 2
         Type: NewSparseMultivariatePolynomial(Integer,
                 OrderedVariableList [x,y,z,t])

lf := [f1, f2, f3, f4]
                  2
 [(2t y - 2)x + z y  - z,
       3             2        2              3      2
  - z x  + (4t y + 4)x  + (4z y  + 4z)x + 2t y  - 10y  - 10t y + 2,
    2
  (t  - 1)x + 2t z y - 2z,
      3      2               2     3            2      2
  (- z  + (4t  + 4)z)x + (4t z  + 2t  - 10t)y + 4z  - 10t  + 2]
         Type: List NewSparseMultivariatePolynomial(Integer,
                         OrderedVariableList [x,y,z,t])
```

First of all, let us solve this system in the sense of Kalkbrener.

```
zeroSetSplit(lf)$T
    2      8      6       2                3           2
 [{t  - 1,z  - 16z  + 256z  - 256,t y - 1,(z  - 8z)x - 8z  + 16},
     2      2     2
  {3t  + 1,z  - 7t  - 1,y + t,x + z},
    8      6      2         3           2
  {t  - 10t  + 10t  - 1,z,(t  - 5t)y - 5t  + 1,x},
    2      2
  {t  + 3,z  - 4,y + t,x - z}]
    Type: List RegularTriangularSet(Integer,
                IndexedExponents OrderedVariableList [x,y,z,t],
                OrderedVariableList [x,y,z,t],
                NewSparseMultivariatePolynomial(Integer,
                    OrderedVariableList [x,y,z,t]))
```

And now in the sense of Lazard (or Wu and other authors).

```
lts2 := zeroSetSplit(lf,false)$T
    8      6      2         3           2
 [{t  - 10t  + 10t  - 1,z,(t  - 5t)y - 5t  + 1,x},
    2      8      6       2                3           2
  {t  - 1,z  - 16z  + 256z  - 256,t y - 1,(z  - 8z)x - 8z  + 16},
     2      2     2                     2      2
  {3t  + 1,z  - 7t  - 1,y + t,x + z}, {t  + 3,z  - 4,y + t,x - z}]
     Type: List RegularTriangularSet(Integer,
                 IndexedExponents OrderedVariableList [x,y,z,t],
                 OrderedVariableList [x,y,z,t],
                 NewSparseMultivariatePolynomial(Integer,
                     OrderedVariableList [x,y,z,t]))
```

```
Up to the ordering of the components, both decompositions are identical.

Let us check that each component has a finite number of solutions.

  [coHeight(ts) for ts in lts2]
    [0,0,0,0]
                        Type: List NonNegativeInteger

Let us count the degrees of each component,

  degrees := [degree(ts) for ts in lts2]
    [8,16,4,4]
                        Type: List NonNegativeInteger

and compute their sum.

  reduce(+,degrees)
    32
                        Type: PositiveInteger

We study now the options of the zeroSetSplit operation.  As we have seen
yet, there is an optional second argument which is a boolean value. If this
value is true (this is the default) then the decomposition is computed in
the sense of Kalkbrener, otherwise it is computed in the sense of Lazard.

There is a second boolean optional argument that can be used (in that
case the first optional argument must be present).  This second option
allows you to get some information during the computations.

Therefore, we need to understand a little what is going on during the
computations.  An important feature of the algorithm is that the
intermediate computations are managed in some sense like the processes
of a Unix system.  Indeed, each intermediate computation may generate
other intermediate computations and the management of all these
computations is a crucial task for the efficiency.  Thus any
intermediate computation may be suspended, killed or resumed,
depending on algebraic considerations that determine priorities for
these processes.  The goal is of course to go as fast as possible
towards the final decomposition which means to avoid as much as
possible unnecessary computations.

To follow the computations, one needs to set to true the second
argument.  Then a lot of numbers and letters are displayed.  Between a
[ and a ] one has the state of the processes at a given time.  Just
after [ one can see the number of processes.  Then each process is
represented by two numbers between < and >.  A process consists of a
list of polynomial ps and a triangular set ts; its goal is to compute
the common zeros of ps that belong to the regular-zeros set of ts.
After the processes, the number between pipes gives the total number
```

```
of polynomials in all the sets ps.  Finally, the number between braces
gives the number of components of a decomposition that are already
computed. This number may decrease.

Let us take a third example (Czapor-Geddes-Wang) to see how this
information is displayed.

Define a polynomial system.

  u : R := 2
    2
                              Type: Integer

  q1 := 2*(u-1)**2+ 2*(x-z*x+z**2)+ y**2*(x-1)**2- 2*u*x+ 2*y*t*(1-x)*(x-z)+_
        2*u*z*t*(t-y)+ u**2*t**2*(1-2*z)+ 2*u*t**2*(z-x)+ 2*u*t*y*(z-1)+_
        2*u*z*x*(y+1)+ (u**2-2*u)*z**2*t**2+ 2*u**2*z**2+ 4*u*(1-u)*z+_
        t**2*(z-x)**2}
       2           2  2        2                              2           2
     (y  - 2t y + t )x  + (- 2y  + ((2t + 4)z + 2t)y + (- 2t  + 2)z - 4t  - 2)x
   +
      2                       2       2          2
     y  + (- 2t z - 4t)y + (t  + 10)z  - 8z + 4t  + 2
       Type: NewSparseMultivariatePolynomial(Integer,
              OrderedVariableList [x,y,z,t])

  q2 := t*(2*z+1)*(x-z)+ y*(z+2)*(1-x)+ u*(u-2)*t+ u*(1-2*u)*z*t+_
        u*y*(x+u-z*x-1)+ u*(u+1)*z**2*t}
    (- 3z y + 2t z + t)x + (z + 4)y + 4t z  - 7t z
       Type: NewSparseMultivariatePolynomial(Integer,
              OrderedVariableList [x,y,z,t])

  q3 := -u**2*(z-1)**2+ 2*z*(z-x)-2*(x-1)
    (- 2z - 2)x - 2z  + 8z - 2
       Type: NewSparseMultivariatePolynomial(Integer,
              OrderedVariableList [x,y,z,t])

  q4 := u**2+4*(z-x**2)+3*y**2*(x-1)**2- 3*t**2*(z-x)**2+_
        3*u**2*t**2*(z-1)**2+u**2*z*(z-2)+6*u*t*y*(z+x+z*x-1)}
       2     2      2        2                       2        2
    (3y  - 3t  - 4)x  + (- 6y  + (12t z + 12t)y + 6t z)x + 3y  + (12t z - 12t)y
   +
       2      2         2            2
    (9t  + 4)z  + (- 24t  - 4)z + 12t  + 4
        Type: NewSparseMultivariatePolynomial(Integer,
               OrderedVariableList [x,y,z,t])

  lq := [q1, q2, q3, q4]
   [
         2           2  2
       (y  - 2t y + t )x
```

```
    +
          2                              2           2          2
      (- 2y  + ((2t + 4)z + 2t)y + (- 2t  + 2)z - 4t  - 2)x + y
    +
                         2       2          2
      (- 2t z - 4t)y + (t  + 10)z  - 8z + 4t  + 2
    ,
                                        2                            2
   (- 3z y + 2t z + t)x + (z + 4)y + 4t z  - 7t z, (- 2z - 2)x - 2z  + 8z - 2,

        2     2      2        2                       2        2
      (3y  - 3t  - 4)x  + (- 6y  + (12t z + 12t)y + 6t z)x + 3y
    +
                          2      2         2            2
      (12t z - 12t)y + (9t  + 4)z  + (- 24t  - 4)z + 12t  + 4
    ]
       Type: List NewSparseMultivariatePolynomial(Integer,
                   OrderedVariableList [x,y,z,t])
```

Let us try the information option. N.B. The timing should be between 1 and 10 minutes, depending on your machine.

```
  zeroSetSplit(lq,true,true)$T
     [1 <4,0> -> |4|; {0}]W[2 <5,0>,<3,1> -> |8|; {0}]
     [2 <4,1>,<3,1> -> |7|; {0}]
     [1 <3,1> -> |3|; {0}]G
     [2 <4,1>,<4,1> -> |8|; {0}]W
     [3 <5,1>,<4,1>,<3,2> -> |12|; {0}]GI
     [3 <4,2>,<4,1>,<3,2> -> |11|; {0}]GWw
     [3 <4,1>,<3,2>,<5,2> -> |12|; {0}]
     [3 <3,2>,<3,2>,<5,2> -> |11|; {0}]GIwWWWw
     [4 <3,2>,<4,2>,<5,2>,<2,3> -> |14|; {0}]
     [4 <2,2>,<4,2>,<5,2>,<2,3> -> |13|; {0}]Gwww
     [5 <3,2>,<3,2>,<4,2>,<5,2>,<2,3> -> |17|; {0}]Gwwwwww
     [8 <3,2>,<4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |30|; {0}]Gwwwwww
     [8 <4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |31|; {0}]
     [8 <3,3>,<4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |30|; {0}]
     [8 <2,3>,<4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |29|; {0}]
     [8 <1,3>,<4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |28|; {0}]
     [7 <4,2>,<4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |27|; {0}]
     [6 <4,2>,<4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |23|; {0}]
     [5 <4,2>,<4,2>,<4,2>,<5,2>,<2,3> -> |19|; {0}]GIGIWwww
     [6 <5,2>,<4,2>,<4,2>,<5,2>,<3,3>,<2,3> -> |23|; {0}]
     [6 <4,3>,<4,2>,<4,2>,<5,2>,<3,3>,<2,3> -> |22|; {0}]GIGI
     [6 <3,4>,<4,2>,<4,2>,<5,2>,<3,3>,<2,3> -> |21|; {0}]
     [6 <2,4>,<4,2>,<4,2>,<5,2>,<3,3>,<2,3> -> |20|; {0}]GGG
     [5 <4,2>,<4,2>,<5,2>,<3,3>,<2,3> -> |18|; {0}]GIGIWwwwW
     [6 <5,2>,<4,2>,<5,2>,<3,3>,<3,3>,<2,3> -> |22|; {0}]
     [6 <4,3>,<4,2>,<5,2>,<3,3>,<3,3>,<2,3> -> |21|; {0}]
     GIwwWwWWWWWWWwWWWwwwww
```

```
[8 <4,2>,<5,2>,<3,3>,<3,3>,<4,3>,<2,3>,<3,4>,<3,4> -> |27|; {0}]
[8 <3,3>,<5,2>,<3,3>,<3,3>,<4,3>,<2,3>,<3,4>,<3,4> -> |26|; {0}]
[8 <2,3>,<5,2>,<3,3>,<3,3>,<4,3>,<2,3>,<3,4>,<3,4> -> |25|; {0}]
Gwwwwwwwwwwwwwwwwwww
[9 <5,2>,<3,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,4>,<3,4> -> |29|; {0}]GI
[9 <4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,4>,<3,4> -> |28|; {0}]
[9 <3,3>,<3,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,4>,<3,4> -> |27|; {0}]
[9 <2,3>,<3,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,4>,<3,4> -> |26|; {0}]
GGwwwwwwwwwwwWWwwwwwwww
[11 <3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
   -> |33|; {0}]
[11 <2,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |32|; {0}]
[11 <1,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |31|; {0}]GGGwwwwwwwwwwww
[12 <2,3>,<2,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |34|; {0}]GGwwwwwwwwwwww
[13 <3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |38|; {0}]Gwwwwwwwwwwww
[13 <2,3>,<3,3>,<4,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |39|; {0}]GGGwwwwwwwwwww
[15 <3,3>,<4,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,
  <3,3>,<3,3>,<3,4>,<3,4> -> |46|; {0}]
[14 <4,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,
  <3,3>,<3,4>,<3,4> -> |43|; {0}]GIGGGGIGGI
[14 <3,4>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,
  <3,3>,<3,4>,<3,4> -> |42|; {0}]GGG
[14 <2,4>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,
  <3,3>,<3,4>,<3,4> -> |41|; {0}]
[14 <1,4>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,
  <3,3>,<3,4>,<3,4> -> |40|; {0}]GGG
[13 <3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |39|; {0}]Gwwwwwwwwwwww
[15 <3,3>,<3,3>,<4,3>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,
  <3,3>,<3,3>,<3,4>,<3,4> -> |48|; {0}]Gwwwwwwwwwwww
[15 <4,3>,<4,3>,<3,3>,<4,3>,<4,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,3>,
  <3,3>,<3,3>,<3,4>,<3,4> -> |49|; {0}]GIGI
[15 <3,4>,<4,3>,<3,3>,<4,3>,<4,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,3>,
  <3,3>,<3,3>,<3,4>,<3,4> -> |48|; {0}]G
[14 <4,3>,<3,3>,<4,3>,<4,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,3>,<3,3>,
  <3,3>,<3,4>,<3,4> -> |45|; {0}]
[13 <3,3>,<4,3>,<4,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |41|; {0}]Gwwwwwwwwwwww
[13 <4,3>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |42|; {0}]GIGGGGIGGI
[13 <3,4>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |41|; {0}]GGGGGGGG
[13 <2,4>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |40|; {0}]
[13 <1,4>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
```

```
  <3,4>,<3,4>  -> |39|; {0}]
[13 <0,4>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |38|; {0}]
[12 <4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |38|; {1}]
[11 <4,3>,<3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |34|; {1}]
[10 <3,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |30|; {1}]
[10 <2,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |29|; {1}]GGGwwwwwwwwwwww
[11 <3,3>,<3,3>,<4,3>,<3,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |33|; {1}]GGGwwwwwwwwwwww
[12 <4,3>,<3,3>,<4,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |38|; {1}]Gwwwwwwwwwwww
[12 <3,3>,<4,3>,<5,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |39|; {1}]GGwwwwwwwwwwww
[13 <5,3>,<4,3>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |44|; {1}]GIGGGGIGGIW
[13 <4,4>,<4,3>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |43|; {1}]GGW
[13 <3,4>,<4,3>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |42|; {1}]GGG
[12 <4,3>,<4,3>,<4,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |39|; {1}]Gwwwwwwwwwwww
[12 <4,3>,<4,3>,<5,3>,<3,3>,<4,3>,<3,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |40|; {1}]Gwwwwwwwwwwww
[13 <5,3>,<5,3>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |46|; {1}]GIGIW
[13 <4,4>,<5,3>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |45|; {1}]
[13 <3,4>,<5,3>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |44|; {1}]
[13 <2,4>,<5,3>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,
  <3,4>,<3,4> -> |43|; {1}]GG
[12 <5,3>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |41|; {1}]GIGGGGIGGIW
[12 <4,4>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |40|; {1}]GGGGGGW
[12 <3,4>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |39|; {1}]
[12 <2,4>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |38|; {1}]
[12 <1,4>,<4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,
  <3,4> -> |37|; {1}]GGG
[11 <4,3>,<5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |36|; {1}]
[10 <5,3>,<3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4>
  -> |32|; {1}]
[9 <3,3>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |27|; {1}]W
```

```
  [9 <2,4>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |26|; {1}]
  [9 <1,4>,<3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |25|; {1}]
  [8 <3,3>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |24|; {1}]W
  [8 <2,4>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |23|; {1}]
  [8 <1,4>,<4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |22|; {1}]
  [7 <4,3>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |21|; {1}]w
  [7 <3,4>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |20|; {1}]
  [7 <2,4>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |19|; {1}]
  [7 <1,4>,<2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |18|; {1}]
  [6 <2,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |17|; {1}]GGwwwwww
  [7 <3,3>,<3,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |21|; {1}]GIW
  [7 <2,4>,<3,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |20|; {1}]GG
  [6 <3,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |18|; {1}]Gwwwwww
  [7 <4,3>,<4,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |23|; {1}]GIW
  [7 <3,4>,<4,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |22|; {1}]
  [6 <4,3>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |19|; {1}]GIW
  [6 <3,4>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |18|; {1}]GGW
  [6 <2,4>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |17|; {1}]
  [6 <1,4>,<3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |16|; {1}]GGG
  [5 <3,3>,<3,3>,<3,3>,<3,4>,<3,4> -> |15|; {1}]GIW
  [5 <2,4>,<3,3>,<3,3>,<3,4>,<3,4> -> |14|; {1}]GG
  [4 <3,3>,<3,3>,<3,4>,<3,4> -> |12|; {1}]
  [3 <3,3>,<3,4>,<3,4> -> |9|; {1}]W
  [3 <2,4>,<3,4>,<3,4> -> |8|; {1}]
  [3 <1,4>,<3,4>,<3,4> -> |7|; {1}]G
  [2 <3,4>,<3,4> -> |6|; {1}]G
  [1 <3,4> -> |3|; {1}]
  [1 <2,4> -> |2|; {1}]
  [1 <1,4> -> |1|; {1}]
*** QCMPACK Statistics ***
   Table     size:  36
   Entries reused:  255

*** REGSETGCD: Gcd Statistics ***
   Table     size:  125
   Entries reused:  0

*** REGSETGCD: Inv Set Statistics ***
   Table     size:  30
   Entries reused:  0

[
  {
                      24                    23                     22
      960725655771966t   + 386820897948702t   + 8906817198608181t
    +
                     21                     20                     19
      2704966893949428t   + 37304033340228264t   + 7924782817170207t
    +
                      18                     17                     16
```

```
  93126799040354990t   + 13101273653130910t   + 156146250424711858t
+
                    15                      14                      13
  16626490957259119t   + 190699288479805763t   + 24339173367625275t
+
                     12                     11                       10
  180532313014960135t   + 35288089030975378t   + 135054975747656285t
+
                    9                     8                      7
  34733736952488540t  + 75947600354493972t  + 19772555692457088t
+
                    6                    5                    4
  28871558573755428t  + 5576152439081664t  + 6321711820352976t
+
                3                   2
438314209312320t  + 581105748367008t  - 60254467992576t + 1449115951104
,

                                                                      23
    266042108694913023855152657370520823616684741813728918577 84t
  +
                                                                     22
    443104378424686086067294899528296664238693556855017735265295t
  +
                                                                    21
    279078393286701234679141342358988327155321305829547090310242t
  +
                                                                     20
    339027636141323246510761717661554305462062639182361339218 5226t
  +
                                                                    19
    941478179503540575554198645220352803719793196473813837434129t
  +
                                                                      18
    115478551946794752422116967496739493525857476741843209881443 90t
  +
                                                                     17
    134360956676559778988170165669941321646721566033335641724 1432t
  +
                                                                      16
    232338138681478735039335516171756408598991029878006635666993 34t
  +
                                                                    15
    869574020537672336950845440508790740850931336484983573386433t
  +
                                                                     14
    315615543058769348754194614869699265542417500651034608204769 69t
  +
                                                                    13
    127140099028771748744206595254773187955482388985538607226493 1t
```

```
      +
                                                                      12
        319450899138637360448025269640795401983370495505032958251605231
      +
                                                                    11
        373873570428814450987137156023284588443910227077801047093196 0t
      +
                                                                     10
        252939975123914120261446014357711315875619055329920456928859 27t
      +
                                                                   9
        521023900984606712346926279987005277341047113595017500804652 4t
      +
                                                                    8
        150838879869302971662598705686082704274031876062387134911291 88t
      +
                                                                   7
        352208723469293012638368627077577955348176912567083907510900 0t
      +
                                                                  6
        607994520039568101308653379256888649110124424744003496928858 8t
      +
                                                                  5
        109063485243390088819991375624798602319698772346993493360368 0t
      +
                                                                  4
        140581943087190710229443253753833540210283899401966748745835 2t
      +
                                                                3
        880715279503204500725366712655077488783478288849336052024 32t
      +
                                                                2
        135882489433640933229781177155977768016065765482378657129440t
      +
        - 139572834428822622305598946074003140825166907499756465203 20t
      +
        33463769297318929927725832570930847259211711285574971392 0
   *
      z
  +
                                                          23
    85671754840439528797567259645068339321496371010905211649 36t
  +
                                                            22
    14979239286420179184570837403272894249879751925166725094572 1t
  +
                                                          21
    77258371783645822157410861582159764138123003074190374021550t
  +
                                                             20
```

$$
\begin{aligned}
&110886225412685421449891894070861221118456055676433474219165 4t \\
&+ \\
&\qquad\qquad\qquad

```
                                                                        3
    19785545294228495032998826937601341132725035339452913286656t
  +
                                                                        2
    364774120573847829423666353033966377633039281749350791785 28t
  +
    - 372221287927903864871308042222497627321089022948583867 0848t
  +
    89079724853114348361230634484013862024728599906874105856
  ,
    3      2                  3       2
  (3z  - 11z  + 8z + 4)y + 2t z  + 4t z  - 5t z - t,
              2
  (z + 1)x + z  - 4z + 1}
]
  Type: List RegularTriangularSet(Integer,
              IndexedExponents OrderedVariableList [x,y,z,t],
              OrderedVariableList [x,y,z,t],
              NewSparseMultivariatePolynomial(Integer,
                OrderedVariableList [x,y,z,t]))
```

Between a sequence of processes, thus between a] and a [you can see capital letters W, G, I and lower case letters i, w. Each time a capital letter appears a non-trivial computation has be performed and its result is put in a hash-table. Each time a lower case letter appears a needed result has been found in an hash-table. The use of these hash-tables generally speed up the computations. However, on very large systems, it may happen that these hash-tables become too big to be handle by your AXIOM configuration. Then in these exceptional cases, you may prefer getting a result (even if it takes a long time) than getting nothing. Hence you need to know how to prevent the RSEGSET constructor from using these hash-tables. In that case you will be using the zeroSetSplit with five arguments. The first one is the input system lp as above. The second one is a boolean value hash? which is true iff you want to use hash-tables. The third one is boolean value clos? which is true iff you want to solve your system in the sense of Kalkbrener, the other way remaining that of Lazard. The fourth argument is boolean value info? which is true iff you want to display information during the computations. The last one is boolean value prep? which is true iff you want to use some heuristics that are performed on the input system before starting the real algorithm. The value of this flag is true when you are using zeroSetSplit with less than five arguments. Note that there is no available signature for zeroSetSplit with four arguments.


We finish this section by some remarks about both ways of solving, in the sense of Kalkbrener or in the sense of Lazard. For problems with a finite number of solutions, there are theoretically equivalent and the resulting decompositions are identical, up to the ordering of the components. However, when solving in the sense of Lazard, the

algorithm behaves differently. In that case, it becomes more incremental than in the sense of Kalkbrener. That means the polynomials of the input system are considered one after another whereas in the sense of Kalkbrener the input system is treated more globally.

This makes an important difference in positive dimension. Indeed when solving in the sense of Kalkbrener, the Primeidealkettensatz of Krull is used. That means any regular triangular containing more polynomials than the input system can be deleted. This is not possible when solving in the sense of Lazard. This explains why Kalkbrener's decompositions usually contain less components than those of Lazard. However, it may happen with some examples that the incremental process (that cannot be used when solving in the sense of Kalkbrener) provide a more efficient way of solving than the global one even if the Primeidealkettensatz is used. Thus just try both, with the various options, before concluding that you cannot solve your favorite system with zeroSetSplit. There exist more options at the development level that are not currently available in this public version.

See Also:
o)help GcdDomain
o)help OrderedAbelianMonoidSup
o)help OrderedSet
o)help RecursivePolynomialCategory
o)help RegularChain
o)help NewSparseMultivariatePolynomial
o)help ZeroDimensionalSolvePackage
o)help LexTriangularPackage
o)help LazardSetSolvingPackage
o)help SquareFreeRegularTriangularSet
o)show RegularTriangularSet

19.7.1 RegularTriangularSet (REGSET)



Exports:

algebraic?	algebraicCoefficients?
algebraicVariables	any?
augment	autoReduced?
basicSet	coerce
coHeight	collect
collectQuasiMonic	collectUnder
collectUpper	construct
convert	copy
count	degree
empty	empty?
eq?	eval
every?	extend
extendIfCan	find
first	hash
headRemainder	headReduce
headReduced?	infRittWu?
initiallyReduce	initiallyReduced?
initials	internalAugment
internalZeroSetSplit	intersect
invertible?	invertibleElseSplit?
invertibleSet	last
lastSubResultant	lastSubResultantElseSplit
latex	less?
mainVariable?	mainVariables
map	map!
member?	members
more?	mvar
normalized?	parts
preprocess	purelyAlgebraic?
purelyAlgebraicLeadingMonomial?	purelyTranscendental?
quasiComponent	reduce
reduced?	reduceByQuasiMonic
remainder	remove
removeDuplicates	removeZero
rest	retract
retractIfCan	rewriteIdealWithHeadRemainder
rewriteIdealWithRemainder	rewriteSetWithReduction
roughBase?	roughEqualIdeals?
roughSubIdeal?	roughUnitIdeal?
sample	select
size?	sort
squareFreePart	stronglyReduce
stronglyReduced?	triangular?
trivialIdeal?	variables
zeroSetSplit	zeroSetSplitIntoTriangularSystems
#?	?~=?
?=?	

— domain REGSET RegularTriangularSet —

```
)abbrev domain REGSET RegularTriangularSet
++ Author: Marc Moreno Maza
++ Date Created: 08/25/1998
++ Date Last Updated: 16/12/1998
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References :
++  [1] M. MORENO MAZA "A new algorithm for computing triangular
++      decomposition of algebraic varieties" NAG Tech. Rep. 4/98.
++ Description:
++ This domain provides an implementation of regular chains.
++ Moreover, the operation zeroSetSplit is an implementation of a new
++ algorithm for solving polynomial systems by means of regular chains.

RegularTriangularSet(R,E,V,P) : Exports == Implementation where

  R : GcdDomain
  E : OrderedAbelianMonoidSup
  V : OrderedSet
  P : RecursivePolynomialCategory(R,E,V)
  N ==> NonNegativeInteger
  Z ==> Integer
  B ==> Boolean
  LP ==> List P
  PtoP ==> P -> P
  PS ==> GeneralPolynomialSet(R,E,V,P)
  PWT ==> Record(val : P, tower : $)
  BWT ==> Record(val : Boolean, tower : $)
  LpWT ==> Record(val : (List P), tower : $)
  Split ==> List $
  iprintpack ==> InternalPrintPackage()
  polsetpack ==> PolynomialSetUtilitiesPackage(R,E,V,P)
  quasicomppack ==> QuasiComponentPackage(R,E,V,P,$)
  regsetgcdpack ==> RegularTriangularSetGcdPackage(R,E,V,P,$)
  regsetdecomppack ==> RegularSetDecompositionPackage(R,E,V,P,$)

  Exports ==  RegularTriangularSetCategory(R,E,V,P) with

     internalAugment: (P,$,B,B,B,B,B) -> List $
       ++ \axiom{internalAugment(p,ts,b1,b2,b3,b4,b5)}
       ++ is an internal subroutine, exported only for developement.
     zeroSetSplit: (LP, B, B) -> Split
       ++ \axiom{zeroSetSplit(lp,clos?,info?)} has the same specifications as
       ++ zeroSetSplit from RegularTriangularSetCategory.
```

```
      ++ Moreover, if \axiom{clos?} then solves in the sense of the Zariski closure
      ++ else solves in the sense of the regular zeros. If \axiom{info?} then
      ++ do print messages during the computations.
    zeroSetSplit: (LP, B, B, B, B) -> Split
      ++ \axiom{zeroSetSplit(lp,b1,b2.b3,b4)}
      ++ is an internal subroutine, exported only for developement.
    internalZeroSetSplit: (LP, B, B, B) -> Split
      ++ \axiom{internalZeroSetSplit(lp,b1,b2,b3)}
      ++ is an internal subroutine, exported only for developement.
    pre_process: (LP, B, B) -> Record(val: LP, towers: Split)
      ++ \axiom{pre_process(lp,b1,b2)}
      ++ is an internal subroutine, exported only for developement.

  Implementation == add

    Rep ==> LP

    rep(s:$):Rep == s pretend Rep
    per(l:Rep):$ == l pretend $

    copy ts ==
      per(copy(rep(ts))$LP)
    empty() ==
      per([])
    empty?(ts:$) ==
      empty?(rep(ts))
    parts ts ==
      rep(ts)
    members ts ==
      rep(ts)
    map (f : PtoP, ts : $) : $ ==
      construct(map(f,rep(ts))$LP)$$
    map! (f : PtoP, ts : $) : $  ==
      construct(map!(f,rep(ts))$LP)$$
    member? (p,ts) ==
      member?(p,rep(ts))$LP
    unitIdealIfCan() ==
      "failed"::Union($,"failed")
    roughUnitIdeal? ts ==
      false
    coerce(ts:$) : OutputForm ==
      lp : List(P) := reverse(rep(ts))
      brace([p::OutputForm for p in lp]$List(OutputForm))$OutputForm
    mvar ts ==
      empty? ts => error "mvar$REGSET: #1 is empty"
      mvar(first(rep(ts)))$P
    first ts ==
      empty? ts => "failed"::Union(P,"failed")
      first(rep(ts))::Union(P,"failed")
    last ts ==
```

```
    empty? ts => "failed"::Union(P,"failed")
    last(rep(ts))::Union(P,"failed")
  rest ts ==
    empty? ts => "failed"::Union($,"failed")
    per(rest(rep(ts)))::Union($,"failed")
  coerce(ts:$) : (List P) ==
    rep(ts)

  collectUpper (ts,v) ==
    empty? ts => ts
    lp := rep(ts)
    newlp : Rep := []
    while (not empty? lp) and (mvar(first(lp)) > v) repeat
      newlp := cons(first(lp),newlp)
      lp := rest lp
    per(reverse(newlp))

  collectUnder (ts,v) ==
    empty? ts => ts
    lp := rep(ts)
    while (not empty? lp) and (mvar(first(lp)) >= v) repeat
      lp := rest lp
    per(lp)

  construct(lp:List(P)) ==
    ts : $ := per([])
    empty? lp => ts
    lp := sort(infRittWu?,lp)
    while not empty? lp repeat
      eif := extendIfCan(ts,first(lp))
      not (eif case $) =>
        error"in construct : List P -> $  from REGSET : bad #1"
      ts := eif::$
      lp := rest lp
    ts

  extendIfCan(ts:$,p:P) ==
    ground? p => "failed"::Union($,"failed")
    empty? ts =>
      p := primitivePart p
      (per([p]))::Union($,"failed")
    not (mvar(ts) < mvar(p)) => "failed"::Union($,"failed")
    invertible?(init(p),ts)@Boolean =>
      (per(cons(p,rep(ts))))::Union($,"failed")
    "failed"::Union($,"failed")

  removeZero(p:P, ts:$): P ==
    (ground? p) or (empty? ts) => p
    v := mvar(p)
    ts_v_- := collectUnder(ts,v)
```

```
  if algebraic?(v,ts)
    then
      q := lazyPrem(p,select(ts,v)::P)
      zero? q => return q
      zero? removeZero(q,ts_v_-) => return 0
  empty? ts_v_- => p
  q: P := 0
  while positive? degree(p,v) repeat
     q := removeZero(init(p),ts_v_-) * mainMonomial(p) + q
     p := tail(p)
  q + removeZero(p,ts_v_-)

internalAugment(p:P,ts:$): $ ==
  -- ASSUME that adding p to ts DOES NOT require any split
  ground? p => error "in internalAugment$REGSET: ground? #1"
  first(internalAugment(p,ts,false,false,false,false,false))

internalAugment(lp:List(P),ts:$): $ ==
  -- ASSUME that adding p to ts DOES NOT require any split
  empty? lp => ts
  internalAugment(rest lp, internalAugment(first lp, ts))

internalAugment(p:P,ts:$,rem?:B,red?:B,prim?:B,sqfr?:B,extend?:B): Split ==
  -- ASSUME p is not a constant
  -- ASSUME mvar(p) is not algebraic w.r.t. ts
  -- ASSUME init(p) invertible modulo ts
  -- if rem? then REDUCE p by remainder
  -- if prim? then REPLACE p by its main primitive part
  -- if sqfr? then FACTORIZE SQUARE FREE p over R
  -- if extend? DO NOT ASSUME every pol in ts_v_+ is invertible modulo ts
  v := mvar(p)
  ts_v_- := collectUnder(ts,v)
  ts_v_+ := collectUpper(ts,v)
  if rem? then p := remainder(p,ts_v_-).polnum
  -- if rem? then p := reduceByQuasiMonic(p,ts_v_-)
  if red? then p := removeZero(p,ts_v_-)
  if prim? then p := mainPrimitivePart p
  if sqfr?
    then
      lsfp := squareFreeFactors(p)$polsetpack
      lts: Split := [per(cons(f,rep(ts_v_-))) for f in lsfp]
    else
      lts: Split := [per(cons(p,rep(ts_v_-)))]
  extend? => extend(members(ts_v_+),lts)
  [per(concat(rep(ts_v_+),rep(us))) for us in lts]

augment(p:P,ts:$): List $ ==
  ground? p => error "in augment$REGSET: ground? #1"
  algebraic?(mvar(p),ts) => error "in augment$REGSET: bad #1"
  -- ASSUME init(p) invertible modulo ts
```

```
    -- DOES NOT ASSUME anything else.
    -- THUS reduction, mainPrimitivePart and squareFree are NEEDED
    internalAugment(p,ts,true,true,true,true,true)

  extend(p:P,ts:$): List $ ==
    ground? p => error "in extend$REGSET: ground? #1"
    v := mvar(p)
    not (mvar(ts) < mvar(p)) => error "in extend$REGSET: bad #1"
    lts: List($) := []
    split: List($) := invertibleSet(init(p),ts)
    for us in split repeat
      lts := concat(augment(p,us),lts)
    lts

  invertible?(p:P,ts:$): Boolean ==
    toseInvertible?(p,ts)$regsetgcdpack

  invertible?(p:P,ts:$): List BWT ==
    toseInvertible?(p,ts)$regsetgcdpack

  invertibleSet(p:P,ts:$): Split ==
    toseInvertibleSet(p,ts)$regsetgcdpack

  lastSubResultant(p1:P,p2:P,ts:$): List PWT ==
    toseLastSubResultant(p1,p2,ts)$regsetgcdpack

  squareFreePart(p:P, ts: $): List PWT ==
    toseSquareFreePart(p,ts)$regsetgcdpack

  intersect(p:P, ts: $): List($) == decompose([p], [ts], false, false)$regsetdecomppack

  intersect(lp: LP, lts: List($)): List($) == decompose(lp, lts, false, false)$regsetdecomppack
     -- SOLVE in the regular zero sense
     -- and DO NOT PRINT info

  decompose(p:P, ts: $): List($) == decompose([p], [ts], true, false)$regsetdecomppack

  decompose(lp: LP, lts: List($)): List($) == decompose(lp, lts, true, false)$regsetdecomppack
     -- SOLVE in the closure sense
     -- and DO NOT PRINT info

  zeroSetSplit(lp:List(P)) == zeroSetSplit(lp,true,false)
     -- by default SOLVE in the closure sense
     -- and DO NOT PRINT info

  zeroSetSplit(lp:List(P), clos?: B) == zeroSetSplit(lp,clos?, false)
     -- DO NOT PRINT info

  zeroSetSplit(lp:List(P), clos?: B, info?: B) ==
    -- if clos? then SOLVE in the closure sense
```

```
  -- if info? then PRINT info
  -- by default USE hash-tables
  -- and PREPROCESS the input system
  zeroSetSplit(lp,true,clos?,info?,true)

zeroSetSplit(lp:List(P),hash?:B,clos?:B,info?:B,prep?:B) ==
  -- if hash? then USE hash-tables
  -- if info? then PRINT information
  -- if clos? then SOLVE in the closure sense
  -- if prep? then PREPROCESS the input system
  if hash?
    then
      s1, s2, s3, dom1, dom2, dom3: String
      e: String := empty()$String
      if info? then (s1,s2,s3) := ("w","g","i") else (s1,s2,s3) := (e,e,e)
      if info?
        then
          (dom1, dom2, dom3) := ("QCMPACK", "REGSETGCD: Gcd", "REGSETGCD: Inv Set")
        else
          (dom1, dom2, dom3) := (e,e,e)
      startTable!(s1,"W",dom1)$quasicomppack
      startTableGcd!(s2,"G",dom2)$regsetgcdpack
      startTableInvSet!(s3,"I",dom3)$regsetgcdpack
  lts := internalZeroSetSplit(lp,clos?,info?,prep?)
  if hash?
    then
      stopTable!()$quasicomppack
      stopTableGcd!()$regsetgcdpack
      stopTableInvSet!()$regsetgcdpack
  lts

internalZeroSetSplit(lp:LP,clos?:B,info?:B,prep?:B) ==
  -- if info? then PRINT information
  -- if clos? then SOLVE in the closure sense
  -- if prep? then PREPROCESS the input system
  if prep?
    then
      pp := pre_process(lp,clos?,info?)
      lp := pp.val
      lts := pp.towers
    else
      ts: $ := [[]]
      lts := [ts]
  lp := remove(zero?, lp)
  any?(ground?, lp) => []
  empty? lp => lts
  empty? lts => lts
  lp := sort(infRittWu?,lp)
  clos? => decompose(lp,lts, clos?, info?)$regsetdecomppack
  -- IN DIM > 0 with clos? the following is false ...
```

```
      for p in lp repeat
        lts := decompose([p],lts, clos?, info?)$regsetdecomppack
      lts

    largeSystem?(lp:LP): Boolean ==
      -- Gonnet and Gerdt and not Wu-Wang.2
      #lp > 16 => true
      #lp < 13 => false
      lts: List($) := []
      (#lp :: Z - numberOfVariables(lp,lts)$regsetdecomppack :: Z) > 3

    smallSystem?(lp:LP): Boolean ==
      -- neural, Vermeer, Liu, and not f-633 and not Hairer-2
      #lp < 5

    mediumSystem?(lp:LP): Boolean ==
      -- f-633 and not Hairer-2
      lts: List($) := []
      (numberOfVariables(lp,lts)$regsetdecomppack :: Z - #lp :: Z) < 2

--    lin?(p:P):Boolean == ground?(init(p)) and one?(mdeg(p))
    lin?(p:P):Boolean == ground?(init(p)) and (mdeg(p) = 1)

    pre_process(lp:LP,clos?:B,info?:B): Record(val: LP, towers: Split) ==
      -- if info? then PRINT information
      -- if clos? then SOLVE in the closure sense
      ts: $ := [[]];
      lts: Split := [ts]
      empty? lp => [lp,lts]
      lp1: List P := []
      lp2: List P := []
      for p in lp repeat
         ground? (tail p) => lp1 := cons(p, lp1)
         lp2 := cons(p, lp2)
      lts: Split := decompose(lp1,[ts],clos?,info?)$regsetdecomppack
      probablyZeroDim?(lp)$polsetpack =>
         largeSystem?(lp) => return [lp2,lts]
         if #lp > 7
           then
             -- Butcher (8,8) + Wu-Wang.2 (13,16)
             lp2 := crushedSet(lp2)$polsetpack
             lp2 := remove(zero?,lp2)
             any?(ground?,lp2) => return [lp2, lts]
             lp3 := [p for p in lp2 | lin?(p)]
             lp4 := [p for p in lp2 | not lin?(p)]
             if clos?
               then
                 lts := decompose(lp4,lts, clos?, info?)$regsetdecomppack
               else
                 lp4 := sort(infRittWu?,lp4)
```

```
              for p in lp4 repeat
                lts := decompose([p],lts, clos?, info?)$regsetdecomppack
            lp2 := lp3
          else
            lp2 := crushedSet(lp2)$polsetpack
            lp2 := remove(zero?,lp2)
            any?(ground?,lp2) => return [lp2, lts]
       if clos?
         then
           lts := decompose(lp2,lts, clos?, info?)$regsetdecomppack
         else
           lp2 := sort(infRittWu?,lp2)
           for p in lp2 repeat
             lts := decompose([p],lts, clos?, info?)$regsetdecomppack
       lp2 := []
       return [lp2,lts]
     smallSystem?(lp) => [lp2,lts]
     mediumSystem?(lp) => [crushedSet(lp2)$polsetpack,lts]
     lp3 := [p for p in lp2 | lin?(p)]
     lp4 := [p for p in lp2 | not lin?(p)]
     if clos?
       then
         lts := decompose(lp4,lts, clos?, info?)$regsetdecomppack
       else
         lp4 := sort(infRittWu?,lp4)
         for p in lp4 repeat
           lts := decompose([p],lts, clos?, info?)$regsetdecomppack
     if clos?
       then
         lts := decompose(lp3,lts, clos?, info?)$regsetdecomppack
       else
         lp3 := sort(infRittWu?,lp3)
         for p in lp3 repeat
           lts := decompose([p],lts, clos?, info?)$regsetdecomppack
     lp2 := []
     return [lp2,lts]
```

———-

— REGSET.dotabb —

```
"REGSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=REGSET"]
"RSETCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RSETCAT"]
"REGSET" -> "RSETCAT"
```

———-

19.8 domain RESRING ResidueRing

— ResidueRing.input —

```
)set break resume
)sys rm -f ResidueRing.output
)spool ResidueRing.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ResidueRing
--R
--R ResidueRing(F: Field,Expon: OrderedAbelianMonoidSup,VarSet: OrderedSet,FPol: PolynomialCategory(F,Expon
--R Abbreviation for ResidueRing is RESRING
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RESRING
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,F) -> %                      ?*? : (F,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : FPol -> %
--R coerce : F -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   lift : % -> FPol
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R reduce : FPol -> %                    sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```


————-

— ResidueRing.help —

```
=======================================================================
ResidueRing examples
=======================================================================

See Also:
o )show ResidueRing
```

19.8.1 ResidueRing (RESRING)



Exports:

0	1	characteristic	coerce	hash
latex	lift	one?	recip	reduce
sample	subtractIfCan	zero?	?~=?	?*?
?**?	?^?	?+?	?-?	-?
?=?				

— domain RESRING ResidueRing —

```
)abbrev domain RESRING ResidueRing
++ Author: P.Gianni
++ Date Created: December 1992
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ ResidueRing is the quotient of a polynomial ring by  an ideal.
++ The ideal is given as a list of generators. The elements of the domain
++ are equivalence classes expressed in terms of reduced elements
```

```
ResidueRing(F,Expon,VarSet,FPol,LFPol) : Dom  == Body
 where
   F       :  Field
   Expon   :  OrderedAbelianMonoidSup
   VarSet  :  OrderedSet
   FPol    :  PolynomialCategory(F, Expon, VarSet)
   LFPol   :  List FPol

   Dom   == Join(CommutativeRing, Algebra F) with
     reduce   :   FPol -> $
     ++ reduce(f) produces the equivalence class of f in the residue ring
     coerce   :   FPol -> $
     ++ coerce(f) produces the equivalence class of f in the residue ring
     lift     :     $  -> FPol
     ++ lift(x) return the canonical representative of the equivalence class x
   Body  ==  add
    --representation
      Rep:= FPol
      import GroebnerPackage(F,Expon,VarSet,FPol)
      relations:= groebner(LFPol)
      relations = [1] => error "the residue ring is the zero ring"
    --declarations
      x,y: $
    --definitions
      0 == 0$Rep
      1 == 1$Rep
      reduce(f : FPol) : $ == normalForm(f,relations)
      coerce(f : FPol) : $ == normalForm(f,relations)
      lift x  == x :: Rep :: FPol
      x + y == x +$Rep y
      -x == -$Rep x
      x*y == normalForm(lift(x *$Rep y),relations)
      (n : Integer) * x == n *$Rep x
      (a : F) * x == a *$Rep x
      x = y == x =$Rep y
      characteristic()      == characteristic()$F
      coerce(x) : OutputForm == coerce(x)$Rep
```

— RESRING.dotabb —

```
"RESRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RESRING"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"RESRING" -> "PFECAT"
```

19.9 domain RESULT Result

— Result.input —

```
)set break resume
)sys rm -f Result.output
)spool Result.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Result
--R
--R Result  is a domain constructor
--R Abbreviation for Result is RESULT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RESULT
--R
--R------------------------------ Operations --------------------------------
--R copy : % -> %                          dictionary : () -> %
--R elt : (%,Symbol,Any) -> Any            ?.? : (%,Symbol) -> Any
--R empty : () -> %                        empty? : % -> Boolean
--R entries : % -> List(Any)               eq? : (%,%) -> Boolean
--R index? : (Symbol,%) -> Boolean         indices : % -> List(Symbol)
--R key? : (Symbol,%) -> Boolean           keys : % -> List(Symbol)
--R map : ((Any -> Any),%) -> %            qelt : (%,Symbol) -> Any
--R sample : () -> %                       setelt : (%,Symbol,Any) -> Any
--R table : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R any? : ((Any -> Boolean),%) -> Boolean if $ has finiteAggregate
--R any? : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R bag : List(Record(key: Symbol,entry: Any)) -> %
--R coerce : % -> OutputForm if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R construct : List(Record(key: Symbol,entry: Any)) -> %
--R convert : % -> InputForm if Record(key: Symbol,entry: Any) has KONVERT(INFORM)
--R count : ((Any -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (Any,%) -> NonNegativeInteger if $ has finiteAggregate and Any has SETCAT
--R count : (Record(key: Symbol,entry: Any),%) -> NonNegativeInteger if $ has finiteAggregate an
--R count : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> NonNegativeInteger if $ has finit
--R dictionary : List(Record(key: Symbol,entry: Any)) -> %
--R entry? : (Any,%) -> Boolean if $ has finiteAggregate and Any has SETCAT
--R eval : (%,List(Equation(Any))) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,Equation(Any)) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,Any,Any) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,List(Any),List(Any)) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,List(Record(key: Symbol,entry: Any)),List(Record(key: Symbol,entry: Any))) -> % if
```

```
--R eval : (%,Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> % if Record(key: Symbol,entr
--R eval : (%,Equation(Record(key: Symbol,entry: Any))) -> % if Record(key: Symbol,entry: Any) has EVALAB(R
--R eval : (%,List(Equation(Record(key: Symbol,entry: Any)))) -> % if Record(key: Symbol,entry: Any) has EV
--R every? : ((Any -> Boolean),%) -> Boolean if $ has finiteAggregate
--R every? : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R extract! : % -> Record(key: Symbol,entry: Any)
--R fill! : (%,Any) -> % if $ has shallowlyMutable
--R find : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> Union(Record(key: Symbol,entry: Any),"failed"
--R first : % -> Any if Symbol has ORDSET
--R hash : % -> SingleInteger if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R insert! : (Record(key: Symbol,entry: Any),%) -> %
--R inspect : % -> Record(key: Symbol,entry: Any)
--R latex : % -> String if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : (((Any,Any) -> Any),%,%) -> %
--R map : ((Record(key: Symbol,entry: Any) -> Record(key: Symbol,entry: Any)),%) -> %
--R map! : ((Any -> Any),%) -> % if $ has shallowlyMutable
--R map! : ((Record(key: Symbol,entry: Any) -> Record(key: Symbol,entry: Any)),%) -> % if $ has shallowlyMut
--R maxIndex : % -> Symbol if Symbol has ORDSET
--R member? : (Any,%) -> Boolean if $ has finiteAggregate and Any has SETCAT
--R member? : (Record(key: Symbol,entry: Any),%) -> Boolean if $ has finiteAggregate and Record(key: Symbol
--R members : % -> List(Any) if $ has finiteAggregate
--R members : % -> List(Record(key: Symbol,entry: Any)) if $ has finiteAggregate
--R minIndex : % -> Symbol if Symbol has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(Any) if $ has finiteAggregate
--R parts : % -> List(Record(key: Symbol,entry: Any)) if $ has finiteAggregate
--R qsetelt! : (%,Symbol,Any) -> Any if $ has shallowlyMutable
--R reduce : (((Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> Record(key: Symbol,entry:
--R reduce : (((Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> Record(key: Symbol,entry:
--R reduce : (((Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> Record(key: Symbol,entry:
--R remove : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Record(key: Symbol,entry: Any),%) -> % if $ has finiteAggregate and Record(key: Symbol,entry:
--R remove! : (Symbol,%) -> Union(Any,"failed")
--R remove! : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : (Record(key: Symbol,entry: Any),%) -> % if $ has finiteAggregate
--R removeDuplicates : % -> % if $ has finiteAggregate and Record(key: Symbol,entry: Any) has SETCAT
--R search : (Symbol,%) -> Union(Any,"failed")
--R select : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R showArrayValues : Boolean -> Boolean
--R showScalarValues : Boolean -> Boolean
--R size? : (%,NonNegativeInteger) -> Boolean
--R swap! : (%,Symbol,Symbol) -> Void if $ has shallowlyMutable
--R table : List(Record(key: Symbol,entry: Any)) -> %
--R ?~=? : (%,%) -> Boolean if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R
--E 1

)spool
```

```
)lisp (bye)
```

———-


— **Result.help** —

```
==========================================================================
Result examples
==========================================================================

See Also:
o )show Result
```

———-

19.9.1 Result (RESULT)



See

⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “FortranProgram” (FORTRAN) 7.18.1 on page 926
⇒ “ThreeDimensionalMatrix” (M3D) 21.7.1 on page 2671
⇒ “SimpleFortranProgram” (SFORT) 20.11.1 on page 2373
⇒ “Switch” (SWITCH) 20.36.1 on page 2597
⇒ “FortranTemplate” (FTEM) 7.20.1 on page 937
⇒ “FortranExpression” (FEXPR) 7.17.1 on page 917

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	entry?	elt
empty	empty?	entries	eq?	eval
every?	extract!	fill!	find	first
hash	index?	indices	insert!	inspect
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
select	select!	setelt	showArrayValues	showScalarValues
size?	swap!	table	#?	?=?
?~=?	?.?			

— domain RESULT Result —

```
)abbrev domain RESULT Result
++ Author: Didier Pinchon and Mike Dewar
++ Date Created:  8 April 1994
++ Date Last Updated: 28 June 1994
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ A domain used to return the results from a call to the NAG
++ Library.  It prints as a list of names and types, though the user may
++ choose to display values automatically if he or she wishes.

Result():Exports==Implementation where

  O  ==> OutputForm

  Exports ==> TableAggregate(Symbol,Any) with
    showScalarValues : Boolean -> Boolean
      ++ showScalarValues(true) forces the values of scalar components to be
      ++  displayed rather than just their types.
    showArrayValues : Boolean -> Boolean
      ++ showArrayValues(true) forces the values of array components to be
      ++  displayed rather than just their types.
    finiteAggregate

  Implementation ==> Table(Symbol,Any) add

    -- Constant
    colon := ": "::Symbol::O
```

```
    elide := "..."::Symbol::O

    -- Flags
    showScalarValuesFlag : Boolean := false
    showArrayValuesFlag  : Boolean := false

    cleanUpDomainForm(d:SExpression):O ==
      not list? d => d::O
      #d=1 => (car d)::O
      -- If the car is an atom then we have a domain constructor, if not
      -- then we have some kind of value.  Since we often can't print these
      -- ****ers we just elide them.
      not atom? car d => elide
      prefix((car d)::O,[cleanUpDomainForm(u) for u in destruct cdr(d)]$List(O))

    display(v:Any,d:SExpression):O ==
      not list? d => error "Domain form is non-list"
      #d=1 =>
       showScalarValuesFlag => objectOf v
       cleanUpDomainForm d
      car(d) = convert("Complex"::Symbol)@SExpression =>
       showScalarValuesFlag => objectOf v
       cleanUpDomainForm d
      showArrayValuesFlag => objectOf v
      cleanUpDomainForm d

    makeEntry(k:Symbol,v:Any):O ==
      hconcat [k::O,colon,display(v,dom v)]

    coerce(r:%):O ==
      bracket [makeEntry(key,r.key) for key in reverse! keys(r)]

    showArrayValues(b:Boolean):Boolean  == showArrayValuesFlag := b
    showScalarValues(b:Boolean):Boolean == showScalarValuesFlag := b
```

———-

— RESULT.dotabb —

```
"RESULT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RESULT"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"RESULT" -> "ALIST"
```

———-

19.10 domain RULE RewriteRule

— RewriteRule.input —

```
)set break resume
)sys rm -f RewriteRule.output
)spool RewriteRule.output
)set message test on
)set message auto off
)clear all

--S 1 of 4
)show RewriteRule
--R
--R RewriteRule(Base: SetCategory,R: Join(Ring,PatternMatchable(Base),OrderedSet,ConvertibleTo(Pattern(Base)
--R Abbreviation for RewriteRule is RULE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RULE
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : Equation(F) -> %
--R coerce : % -> OutputForm              elt : (%,F,PositiveInteger) -> F
--R ?.? : (%,F) -> F                      hash : % -> SingleInteger
--R latex : % -> String                   lhs : % -> F
--R pattern : % -> Pattern(Base)          retract : % -> Equation(F)
--R rhs : % -> F                         rule : (F,F,List(Symbol)) -> %
--R rule : (F,F) -> %                    ?~=? : (%,%) -> Boolean
--R quotedOperators : % -> List(Symbol)
--R retractIfCan : % -> Union(Equation(F),"failed")
--R suchThat : (%,List(Symbol),(List(F) -> Boolean)) -> %
--R
--E 1

--S 2 of 4
logrule := rule log(x) + log(y) == log(x*y)
--R
--R   (1)  log(y) + log(x) + %B == log(x y) + %B
--R                      Type: RewriteRule(Integer,Integer,Expression(Integer))
--E 2

--S 3 of 4
f := log(sin(x)) + log(x)
--R
--R   (2)  log(sin(x)) + log(x)
--R                                                 Type: Expression(Integer)
--E 3

--S 4 of 4
```

```
logrule f
--R
--R   (3)  log(x sin(x))
--R                                                    Type: Expression(Integer)
--E 4

)spool
)lisp (bye)
```

———-

— RewriteRule.help —

```
=====================================================================
RewriteRule examples
=====================================================================
For example:

logrule := rule log(x) + log(y) == log(x*y)
   log(y) + log(x) + %C == log(x y) + %C

f := log(sin(x)) + log(x)
   log(sin(x)) + log(x)

logrule f
   log(x sin(x))


Note that you cannot write the simple form of a rule as:


rule1 := rule a*x+b == b*x+a

as this causes an infinite loop. The pattern is properly matched
but the result also properly matches and the pattern is applied
again.


See Also:
o )show ApplyRules
o )show RewriteRule
```

———-

19.10.1 RewriteRule (RULE)



See

⇒ "Ruleset" (RULESET) 19.15.1 on page 2309

Exports:

coerce	elt	hash	latex	lhs
pattern	quotedOperators	retract	retractIfCan	rhs
rule	suchThat	?.?	?~=?	?=?

— domain RULE RewriteRule —

```
)abbrev domain RULE RewriteRule
++ Author: Manuel Bronstein
++ Date Created: 24 Oct 1988
++ Date Last Updated: 26 October 1993
++ Keywords: pattern, matching, rule.
++ Description:
++ Rules for the pattern matcher

RewriteRule(Base, R, F): Exports == Implementation where
  Base   : SetCategory
  R      : Join(Ring, PatternMatchable Base, OrderedSet,
                              ConvertibleTo Pattern Base)
  F      : Join(FunctionSpace R, PatternMatchable Base,
                              ConvertibleTo Pattern Base)

  P    ==> Pattern Base

  Exports ==>
   Join(SetCategory, Eltable(F, F), RetractableTo Equation F) with
    rule    : (F, F) -> $
      ++ rule(f, g) creates the rewrite rule: \spad{f == eval(g, g is f)},
      ++ with left-hand side f and right-hand side g.
      ++
      ++X logrule := rule log(x) + log(y) == log(x*y)
      ++X f := log(sin(x)) + log(x)
      ++X logrule f
```

```
    rule    : (F, F, List Symbol) -> $
      ++ rule(f, g, [f1,...,fn]) creates the rewrite rule
      ++ \spad{f == eval(eval(g, g is f), [f1,...,fn])},
      ++ that is a rule with left-hand side f and right-hand side g;
      ++ The symbols f1,...,fn are the operators that are considered
      ++ quoted, that is they are not evaluated during any rewrite,
      ++ but just applied formally to their arguments.
    suchThat: ($, List Symbol, List F -> Boolean) -> $
      ++ suchThat(r, [a1,...,an], f) returns the rewrite rule r with
      ++ the predicate \spad{f(a1,...,an)} attached to it.
    pattern : $ -> P
      ++ pattern(r) returns the pattern corresponding to
      ++ the left hand side of the rule r.
    lhs     : $ -> F
      ++ lhs(r) returns the left hand side of the rule r.
    rhs     : $ -> F
      ++ rhs(r) returns the right hand side of the rule r.
    elt     : ($, F, PositiveInteger) -> F
      ++ elt(r,f,n) or r(f, n) applies the rule r to f at most n times.
    quotedOperators: $ -> List Symbol
      ++ quotedOperators(r) returns the list of operators
      ++ on the right hand side of r that are considered
      ++ quoted, that is they are not evaluated during any rewrite,
      ++ but just applied formally to their arguments.

  Implementation ==> add
    import ApplyRules(Base, R, F)
    import PatternFunctions1(Base, F)
    import FunctionSpaceAssertions(R, F)

    Rep := Record(pat: P, lft: F, rgt: F, qot: List Symbol)

    mkRule      : (P, F, F, List Symbol) -> $
    transformLhs: P -> Record(plus: F, times: F)
    bad?        : Union(List P, "failed") -> Boolean
    appear?     : (P, List P) -> Boolean
    opt         : F -> P
    F2Symbol    : F -> F

    pattern x               == x.pat
    lhs x                   == x.lft
    rhs x                   == x.rgt
    quotedOperators x       == x.qot
    mkRule(pt, p, s, l)     == [pt, p, s, l]
    coerce(eq:Equation F):$  == rule(lhs eq, rhs eq, empty())
    rule(l, r)              == rule(l, r, empty())
    elt(r:$, s:F) == applyRules([r pretend RewriteRule(Base, R, F)], s)

    suchThat(x, l, f) ==
      mkRule(suchThat(pattern x,l,f),  lhs x, rhs x, quotedOperators x)
```

```
    x = y ==
     (lhs x = lhs y) and (rhs x = rhs y) and
        (quotedOperators x = quotedOperators y)

    elt(r:$, s:F, n:PositiveInteger) ==
      applyRules([r pretend RewriteRule(Base, R, F)], s, n)

-- remove the extra properties from the constant symbols in f
    F2Symbol f ==
      l := select_!(z+->symbolIfCan z case Symbol, tower f)$List(Kernel F)
      eval(f, l, [symbolIfCan(k)::Symbol::F for k in l])

    retractIfCan r ==
      constant? pattern r =>
        (u:= retractIfCan(lhs r)@Union(Kernel F,"failed")) case "failed"
          => "failed"
        F2Symbol(u::Kernel(F)::F) = rhs r
      "failed"

    rule(p, s, l) ==
      lh := transformLhs(pt := convert(p)@P)
      mkRule(opt(lh.times) * (opt(lh.plus) + pt),
             lh.times * (lh.plus + p), lh.times * (lh.plus + s), l)

    opt f ==
      retractIfCan(f)@Union(R, "failed") case R => convert f
      convert optional f

-- appear?(x, [p1,...,pn]) is true if x appears as a variable in
-- a composite pattern pi.
    appear?(x, l) ==
      for p in l | p ^= x repeat
        member?(x, variables p) => return true
      false

-- a sum/product p1 @ ... @ pn is "bad" if it will not match
-- a sum/product p1 @ ... @ pn @ p(n+1)
-- in which case one should transform p1 @ ... @ pn to
-- p1 @ ... @ ?p(n+1) which does not change its meaning.
-- examples of "bad" combinations
--   sin(x) @ sin(y)     sin(x) @ x
-- examples of "good" combinations
--   sin(x) @ y
    bad? u ==
      u case List(P) =>
        for x in u::List(P) repeat
          generic? x and not appear?(x, u::List(P)) => return false
        true
      false
```

```
    transformLhs p ==
      bad? isPlus p  => [new()$Symbol :: F, 1]
      bad? isTimes p => [0, new()$Symbol :: F]
      [0, 1]

    coerce(x:$):OutputForm ==
      infix(" == "::Symbol::OutputForm,
            lhs(x)::OutputForm, rhs(x)::OutputForm)
```

———-

— **RULE.dotabb** —

```
"RULE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RULE"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"RULE" -> "FS"
```

———-

19.11 domain ROIRC RightOpenIntervalRootCharacterization

The domain RightOpenIntervalRootCharacterization is the main code that provides the functionalities of RealRootCharacterizationCategory for the case of archimedean fileds. Abstract roots are encoded with a left closed right open interval containing the root together with a defining polynomial for the root.

CAVEATS

Since real algebraic expressions are stored as depending on "real roots" which are managed like variables, there is an ordering on these. This ordering is dynamical in the sense that any new algebraic takes precedence over older ones. In particular every cretaion function raises a new "real root". This has the effect that when you type something like sqrt(2) + sqrt(2) you have two new variables which happen to be equal. To avoid this name the expression such as in s2 := sqrt(2) ; s2 + s2

Also note that computing times depend strongly on the ordering you implicitly provide. Please provide algebraics in the order which most natural to you.

LIMITATIONS

The file reclos.input show some basic use of the package. This packages uses algorithms which are published in [1] and [2] which are based on field arithmetics, inparticular for polynomial gcd related algorithms. This can be quite slow for high degree polynomials and subresultants methods usually work best. Betas versions of the package try to use these techniques in a

better way and work significantly faster. These are mostly based on unpublished algorithms and cannot be distributed. Please contact the author if you have a particular problem to solve or want to use these versions.

Be aware that approximations behave as post-processing and that all computations are done exactly. They can thus be quite time consuming when depending on several "real roots".

— RightOpenIntervalRootCharacterization.input —

```
)set break resume
)sys rm -f RightOpenIntervalRootCharacterization.output
)spool RightOpenIntervalRootCharacterization.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show RightOpenIntervalRootCharacterization
--R
--R RightOpenIntervalRootCharacterization(TheField: Join(OrderedRing,Field),ThePolDom: UnivariatePolynomial(
--R Abbreviation for RightOpenIntervalRootCharacterization is ROIRC
--R This constructor is exposed in this frame.
--R Issue )edit NIL to see algebra source code for ROIRC
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                allRootsOf : ThePolDom -> List(%)
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   left : % -> TheField
--R middle : % -> TheField                refine : % -> %
--R right : % -> TheField                 sign : (ThePolDom,%) -> Integer
--R size : % -> TheField                  zero? : (ThePolDom,%) -> Boolean
--R ?~=? : (%,%) -> Boolean
--R approximate : (ThePolDom,%,TheField) -> TheField
--R definingPolynomial : % -> ThePolDom
--R mightHaveRoots : (ThePolDom,%) -> Boolean
--R negative? : (ThePolDom,%) -> Boolean
--R positive? : (ThePolDom,%) -> Boolean
--R recip : (ThePolDom,%) -> Union(ThePolDom,"failed")
--R relativeApprox : (ThePolDom,%,TheField) -> TheField
--R rootOf : (ThePolDom,PositiveInteger) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```


———-

— RightOpenIntervalRootCharacterization.help —

```
=======================================================================
RightOpenIntervalRootCharacterization examples
=======================================================================

See Also:
o )show RightOpenIntervalRootCharacterization
```

19.11.1 RightOpenIntervalRootCharacterization (ROIRC)



See

⇒ "RealClosure" (RECLOS) 19.3.1 on page 2202

Exports:

allRootsOf	approximate	coerce	definingPolynomial	hash
latex	left	middle	mightHaveRoots	negative?
positive?	recip	refine	relativeApprox	right
rootOf	sign	size	zero?	?=?
?~=?				

— domain ROIRC RightOpenIntervalRootCharacterization —

```
)abbrev domain ROIRC RightOpenIntervalRootCharacterization
++ Author: Renaud Rioboo
++ Date Created: summer 1992
++ Date Last Updated: January 2004
++ Basic Functions: provides computations with real roots of olynomials
++ Related Constructors: RealRootCharacterizationCategory, RealClosure
++ Also See:
++ AMS Classifications:
++ Keywords: Real Algebraic Numbers
++ References:
++ Description:
++ \axiomType{RightOpenIntervalRootCharacterization} provides work with
```

```
++ interval root coding.

RightOpenIntervalRootCharacterization(TheField,ThePolDom) : PUB == PRIV where

  TheField : Join(OrderedRing,Field)
  ThePolDom : UnivariatePolynomialCategory(TheField)


  Z           ==>  Integer
  P           ==>  ThePolDom
  N           ==>  NonNegativeInteger
  B           ==>  Boolean
  UTIL        ==>  RealPolynomialUtilitiesPackage(TheField,ThePolDom)
  RRCC        ==>  RealRootCharacterizationCategory
  O ==> OutputForm
  TwoPoints ==> Record(low:TheField , high:TheField)

  PUB == RealRootCharacterizationCategory(TheField, ThePolDom) with

      left    :             $            -> TheField
           ++ \axiom{left(rootChar)} is the left bound of the isolating
           ++ interval
      right   :             $            -> TheField
           ++ \axiom{right(rootChar)} is the right bound of the isolating
           ++ interval
      size    :             $            -> TheField
           ++ The size of the isolating interval
      middle  :             $            -> TheField
           ++ \axiom{middle(rootChar)} is the middle of the isolating
           ++ interval
      refine  :             $            ->    $
           ++ \axiom{refine(rootChar)} shrinks isolating interval around
           ++ \axiom{rootChar}
      mightHaveRoots :     (P,$)         ->    B
           ++ \axiom{mightHaveRoots(p,r)} is false if \axiom{p.r} is not 0
      relativeApprox :     (P,$,TheField) -> TheField
           ++ \axiom{relativeApprox(exp,c,p) = a} is relatively close to exp
           ++ as a polynomial in c ip to precision p

  PRIV == add



-- local functions


   makeChar:             (TheField,TheField,ThePolDom) ->     $
   refine! :                          $            ->     $
   sturmIsolate : (List(P), TheField, TheField,N,N)    -> List TwoPoints
   isolate :                        List(P)        -> List TwoPoints
```

```
   rootBound :                                P           ->   TheField
--   varStar :                                   P          ->     N
   linearRecip :                          ( P , $)        -> Union(P, "failed")
   linearZero? :                        (TheField,$)      ->     B
   linearSign :                            (P,$)          ->     Z
   sturmNthRoot : (List(P), TheField, TheField,N,N,N)  -> Union(TwoPoints,"failed")
   addOne :                                P              ->      P
   minus :                                 P              ->      P
   translate :                    (P,TheField)            ->      P
   dilate :                       (P,TheField)            ->      P
   invert :                                P              ->      P
   evalOne :                               P              ->   TheField
   hasVarsl:                     List(TheField)           ->      B
   hasVars:                                P              ->      B

-- Representation

   Rep:= Record(low:TheField,high:TheField,defPol:ThePolDom)

-- and now the code !


   size(rootCode) ==
     rootCode.high - rootCode.low

   relativeApprox(pval,rootCode,prec) ==
     -- beurk !
     dPol := rootCode.defPol
     degree(dPol) = 1 =>
       c := -coefficient(dPol,0)/leadingCoefficient(dPol)
       pval.c
     pval := pval rem dPol
     degree(pval) = 0 => leadingCoefficient(pval)
     zero?(pval,rootCode)  => 0
     while mightHaveRoots(pval,rootCode) repeat
          rootCode := refine(rootCode)
     dpval := differentiate(pval)
     degree(dpval) = 0 =>
       l := left(rootCode)
       r := right(rootCode)
       a := pval.l
       b := pval.r
       while ( abs(2*(a-b)/(a+b)) > prec ) repeat
         rootCode := refine(rootCode)
         l := left(rootCode)
         r := right(rootCode)
         a := pval.l
         b := pval.r
       (a+b)/(2::TheField)
     zero?(dpval,rootCode) =>
```

```
      relativeApprox(pval,
                     [left(rootCode),
                       right(rootCode),
                         gcd(dpval,rootCode.defPol)]$Rep,
                     prec)
    while mightHaveRoots(dpval,rootCode) repeat
         rootCode := refine(rootCode)
    l := left(rootCode)
    r := right(rootCode)
    a := pval.l
    b := pval.r
    while ( abs(2*(a-b)/(a+b)) > prec ) repeat
      rootCode := refine(rootCode)
      l := left(rootCode)
      r := right(rootCode)
      a := pval.l
      b := pval.r
    (a+b)/(2::TheField)

  approximate(pval,rootCode,prec) ==
    -- glurp
    dPol := rootCode.defPol
    degree(dPol) = 1 =>
      c := -coefficient(dPol,0)/leadingCoefficient(dPol)
      pval.c
    pval := pval rem dPol
    degree(pval) = 0 => leadingCoefficient(pval)
    dpval := differentiate(pval)
    degree(dpval) = 0 =>
      l := left(rootCode)
      r := right(rootCode)
      while ( abs((a := pval.l) - (b := pval.r)) > prec ) repeat
        rootCode := refine(rootCode)
        l := left(rootCode)
        r := right(rootCode)
      (a+b)/(2::TheField)
    zero?(dpval,rootCode) =>
       approximate(pval,
                   [left(rootCode),
                    right(rootCode),
                     gcd(dpval,rootCode.defPol)]$Rep,
                   prec)
    while mightHaveRoots(dpval,rootCode) repeat
         rootCode := refine(rootCode)
    l := left(rootCode)
    r := right(rootCode)
    while ( abs((a := pval.l) - (b := pval.r)) > prec ) repeat
      rootCode := refine(rootCode)
      l := left(rootCode)
      r := right(rootCode)
```

```
    (a+b)/(2::TheField)


  addOne(p) == p.(monomial(1,1)+(1::P))

  minus(p) == p.(monomial(-1,1))

  translate(p,a) == p.(monomial(1,1)+(a::P))

  dilate(p,a) == p.(monomial(a,1))

  evalOne(p) == "+" / coefficients(p)

  invert(p) ==
       d := degree(p)
       mapExponents(z +-> (d-z)::N, p)

  rootBound(p) ==
    res : TheField := 1
    raw :TheField := 1+boundOfCauchy(p)$UTIL
    while (res < raw) repeat
      res := 2*(res)
    res

  sturmNthRoot(lp,l,r,vl,vr,n) ==
   nv := (vl - vr)::N
   nv < n => "failed"
   ((nv = 1) and (n = 1)) => [l,r]
   int := (l+r)/(2::TheField)
   lt:List(TheField):=[]
   for t in lp repeat
       lt := cons(t.int , lt)
   vi := sturmVariationsOf(reverse! lt)$UTIL
   o :Z := n - vl + vi
   if o > 0
   then
      sturmNthRoot(lp,int,r,vi,vr,o::N)
   else
      sturmNthRoot(lp,l,int,vl,vi,n)

  sturmIsolate(lp,l,r,vl,vr) ==
   r <= l => error "ROIRC: sturmIsolate: bad bounds"
   n := (vl - vr)::N
   zero?(n) => []
   one?(n) => [[l,r]]
   int := (l+r)/(2::TheField)
   vi := sturmVariationsOf( [t.int for t in lp ] )$UTIL
   append(sturmIsolate(lp,l,int,vl,vi),sturmIsolate(lp,int,r,vi,vr))

  isolate(lp) ==
```

```
    b := rootBound(first(lp))
    l1,l2 : List(TheField)
    (l1,l2) := ([] , [])
    for t in reverse(lp) repeat
      if odd?(degree(t))
      then
       (l1,l2):= (cons(-leadingCoefficient(t),l1),
                  cons(leadingCoefficient(t),l2))
      else
       (l1,l2):= (cons(leadingCoefficient(t),l1),
                  cons(leadingCoefficient(t),l2))
    sturmIsolate(lp,
                 -b,
                 b,
                 sturmVariationsOf(l1)$UTIL,
                 sturmVariationsOf(l2)$UTIL)

  rootOf(pol,n) ==
   ls := sturmSequence(pol)$UTIL
   pol := unitCanonical(first(ls)) -- this one is SqFR
   degree(pol) = 0 => "failed"
   numberOfMonomials(pol) = 1 => ([0,1,monomial(1,1)]$Rep)::$
   b := rootBound(pol)
   l1,l2 : List(TheField)
   (l1,l2) := ([] , [])
   for t in reverse(ls) repeat
     if odd?(degree(t))
     then
      (l1,l2):= (cons(leadingCoefficient(t),l1),
                 cons(-leadingCoefficient(t),l2))
     else
      (l1,l2):= (cons(leadingCoefficient(t),l1),
                 cons(leadingCoefficient(t),l2))
   res := sturmNthRoot(ls,
                       -b,
                       b,
                       sturmVariationsOf(l2)$UTIL,
                       sturmVariationsOf(l1)$UTIL,
                       n)
   res case "failed" => "failed"
   makeChar(res.low,res.high,pol)

  allRootsOf(pol) ==
   ls := sturmSequence(unitCanonical pol)$UTIL
   pol := unitCanonical(first(ls)) -- this one is SqFR
   degree(pol) = 0 => []
   numberOfMonomials(pol) = 1 => [[0,1,monomial(1,1)]$Rep]
   [ makeChar(term.low,term.high,pol) for term in isolate(ls) ]
```

```
   hasVarsl(l:List(TheField)) ==
    null(l) => false
    f := sign(first(l))
    for term in rest(l) repeat
      if f*term < 0 then return(true)
    false

   hasVars(p:P) ==
    zero?(p) => error "ROIRC: hasVars: null polynonial"
    zero?(coefficient(p,0)) => true
    hasVarsl(coefficients(p))


   mightHaveRoots(p,rootChar) ==
      a := rootChar.low
      q := translate(p,a)
      not(hasVars(q)) => false
--      varStar(q) = 0 => false
      a := (rootChar.high) - a
      q := dilate(q,a)
      sign(coefficient(q,0))*sign(evalOne(q)) <= 0 => true
      q := minus(addOne(q))
      not(hasVars(q)) => false
--      varStar(q) = 0 => false
      q := invert(q)
      hasVars(addOne(q))
--      ^(varStar(addOne(q)) = 0)

   coerce(rootChar:$):O ==
     commaSeparate([ hconcat("[" :: O , (rootChar.low)::O),
                     hconcat((rootChar.high)::O,"[" ::O ) ])

   c1 = c2 ==
     mM := max(c1.low,c2.low)
     Mm := min(c1.high,c2.high)
     mM >= Mm => false
     rr : ThePolDom := gcd(c1.defPol,c2.defPol)
     degree(rr) = 0 => false
     sign(rr.mM) * sign(rr.Mm) <= 0

   makeChar(left,right,pol) ==
-- The following lines of code, which check for a possible error,
-- cause major performance problems and were removed by Renaud Rioboo,
-- the original author. They were originally inserted for debugging.
--    right <= left => error "ROIRC: makeChar: Bad interval"
--    (pol.left * pol.right) > 0 => error "ROIRC: makeChar: Bad pol"
    res :$ := [left,right,leadingMonomial(pol)+reductum(pol)]$Rep -- safe copy
    while zero?(pol.(res.high)) repeat refine!(res)
    while (res.high * res.low < 0 ) repeat refine!(res)
    zero?(pol.(res.low)) => [res.low,res.high,monomial(1,1)-(res.low)::P]
```

```
 res

definingPolynomial(rootChar) == rootChar.defPol

linearRecip(toTest,rootChar) ==
   c := - inv(leadingCoefficient(toTest)) * coefficient(toTest,0)
   r := recip(rootChar.defPol.c)
   if (r case "failed")
   then
     if (c - rootChar.low) * (c - rootChar.high) <= 0
     then
       "failed"
     else
       newPol := (rootChar.defPol exquo toTest)::P
       ((1$ThePolDom - inv(newPol.c)*newPol) exquo toTest)::P
   else
      ((1$ThePolDom - (r::TheField)*rootChar.defPol) exquo toTest)::P

recip(toTest,rootChar) ==
  degree(toTest) = 0 or degree(rootChar.defPol) <= degree(toTest) =>
    error "IRC: recip: Not reduced"
  degree(rootChar.defPol) = 1 =>
    error "IRC: recip: Linear Defining Polynomial"
  degree(toTest) = 1 =>
    linearRecip(toTest, rootChar)
  d := extendedEuclidean((rootChar.defPol),toTest)
  (degree(d.generator) = 0 ) =>
      d.coef2
  d.generator := unitCanonical(d.generator)
  (d.generator.(rootChar.low) *
   d.generator.(rootChar.high)<= 0) => "failed"
  newPol := (rootChar.defPol exquo (d.generator))::P
  degree(newPol) = 1 =>
    c := - inv(leadingCoefficient(newPol)) * coefficient(newPol,0)
    inv(toTest.c)::P
  degree(toTest) = 1 =>
    c := - coefficient(toTest,0)/ leadingCoefficient(toTest)
    ((1$ThePolDom - inv(newPol.(c))*newPol) exquo toTest)::P
  d := extendedEuclidean(newPol,toTest)
  d.coef2

linearSign(toTest,rootChar) ==
   c := - inv(leadingCoefficient(toTest)) * coefficient(toTest,0)
   ev := sign(rootChar.defPol.c)
   if zero?(ev)
   then
     if (c - rootChar.low) * (c - rootChar.high) <= 0
     then
       0
     else
```

```
        sign(toTest.(rootChar.high))
    else
      if (ev*sign(rootChar.defPol.(rootChar.high)) <= 0 )
      then
        sign(toTest.(rootChar.high))
      else
        sign(toTest.(rootChar.low))

  sign(toTest,rootChar) ==
    degree(toTest) = 0 or degree(rootChar.defPol) <= degree(toTest) =>
      error "IRC: sign: Not reduced"
    degree(rootChar.defPol) = 1 =>
      error "IRC: sign: Linear Defining Polynomial"
    degree(toTest) = 1 =>
     linearSign(toTest, rootChar)
    s := sign(leadingCoefficient(toTest))
    toTest := monomial(1,degree(toTest))+
              inv(leadingCoefficient(toTest))*reductum(toTest)
    delta := gcd(toTest,rootChar.defPol)
    newChar := [rootChar.low,rootChar.high,rootChar.defPol]$Rep
    if degree(delta) > 0
    then
      if sign(delta.(rootChar.low) * delta.(rootChar.high)) <= 0
      then
       return(0)
      else
       newChar.defPol := (newChar.defPol exquo delta) :: P
       toTest := toTest rem (newChar.defPol)
    degree(toTest) = 0 => s * sign(leadingCoefficient(toTest))
    degree(toTest) = 1 => s * linearSign(toTest, newChar)
    while mightHaveRoots(toTest,newChar) repeat
      newChar := refine(newChar)
    s*sign(toTest.(newChar.low))

  linearZero?(c,rootChar) ==
     zero?((rootChar.defPol).c) and
      (c - rootChar.low) * (c - rootChar.high) <= 0

  zero?(toTest,rootChar) ==
    degree(toTest) = 0 or degree(rootChar.defPol) <= degree(toTest) =>
      error "IRC: zero?: Not reduced"
    degree(rootChar.defPol) = 1 =>
      error "IRC: zero?: Linear Defining Polynomial"
    degree(toTest) = 1 =>
     linearZero?(- inv(leadingCoefficient(toTest)) * coefficient(toTest,0),
                 rootChar)
    toTest := monomial(1,degree(toTest))+
              inv(leadingCoefficient(toTest))*reductum(toTest)
    delta := gcd(toTest,rootChar.defPol)
    degree(delta) = 0 => false
```

```
    sign(delta.(rootChar.low) * delta.(rootChar.high)) <= 0


  refine!(rootChar) ==
    -- this is not a safe function, it can work with badly created object
    -- we do not assume (rootChar.defPol).(rootChar.high) <> 0
       int := middle(rootChar)
       s1 := sign((rootChar.defPol).(rootChar.low))
       zero?(s1) =>
         rootChar.high := int
         rootChar.defPol := monomial(1,1) - (rootChar.low)::P
         rootChar
       s2 := sign((rootChar.defPol).int)
       zero?(s2) =>
         rootChar.low := int
         rootChar.defPol := monomial(1,1) - int::P
         rootChar
       if (s1*s2 < 0)
       then
         rootChar.high := int
       else
         rootChar.low := int
       rootChar

  refine(rootChar) ==
    -- we assume (rootChar.defPol).(rootChar.high) <> 0
       int := middle(rootChar)
       s:= (rootChar.defPol).int * (rootChar.defPol).(rootChar.high)
       zero?(s) => [int,rootChar.high,monomial(1,1)-int::P]
       if s < 0
       then
         [int,rootChar.high,rootChar.defPol]
       else
         [rootChar.low,int,rootChar.defPol]

  left(rootChar) == rootChar.low

  right(rootChar) == rootChar.high

  middle(rootChar) == (rootChar.low + rootChar.high)/(2::TheField)

--   varStar(p) == -- if 0 no roots in [0,:infty[
--     res : N := 0
--     lsg := sign(coefficient(p,0))
--     l := [ sign(i) for i in reverse!(coefficients(p))]
--     for sg in l repeat
--      if (sg ^= lsg) then res := res + 1
--      lsg := sg
--     res
```

———-

— **ROIRC.dotabb** —

```
"ROIRC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ROIRC"]
"RRCC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RRCC"]
"ROIRC" -> "RRCC"
```

———-

19.12 domain ROMAN RomanNumeral

— **RomanNumeral.input** —

```
)set break resume
)sys rm -f RomanNumeral.output
)spool RomanNumeral.output
)set message test on
)set message auto off
)clear all
--S 1 of 15
f := operator 'f
--R
--R
--R   (1)  f
--R                                                    Type: BasicOperator
--E 1

--S 2 of 15
D(f x,x,7)
--R
--R
--R         (vii)
--R   (2)  f     (x)
--R
--R                                                 Type: Expression(Integer)
--E 2

--S 3 of 15
a := roman(1978 - 1965)
--R
--R
--R   (3)  XIII
--R                                                     Type: RomanNumeral
--E 3
```

```
--S 4 of 15
x : UTS(ROMAN,'x,0) := x
--R
--R
--R   (4)  x
--R                                Type: UnivariateTaylorSeries(RomanNumeral,x,0)
--E 4

--S 5 of 15
recip(1 - x - x**2)
--R
--R
--R   (5)
--R                 2        3      4         5         6        7          8
--R     I + x + II x  + III x  + V x  + VIII x  + XIII x  + XXI x  + XXXIV x
--R   +
--R         9           10      11
--R     LV x  + LXXXIX x   + O(x  )
--R                    Type: Union(UnivariateTaylorSeries(RomanNumeral,x,0),...)
--E 5

--S 6 of 15
m : MATRIX FRAC ROMAN
--R
--R                                                                    Type: Void
--E 6

--S 7 of 15
m := matrix [ [1/(i + j) for i in 1..3] for j in 1..3]
--R
--R
--R        + I    I    I+
--R        |--   ---  --|
--R        |II   III  IV|
--R        |            |
--R        | I    I   I |
--R   (7)  |---  --   - |
--R        |III  IV   V |
--R        |            |
--R        | I    I    I|
--R        |--    -   --|
--R        +IV    V   VI+
--R                                          Type: Matrix(Fraction(RomanNumeral))
--E 7

--S 8 of 15
inverse m
--R
--R
```

```
--R        +LXXII   - CCXL    CLXXX +
--R        |                        |
--R   (8)  |- CCXL    CM     - DCCXX|
--R        |                        |
--R        +CLXXX   - DCCXX    DC   +
--R                              Type: Union(Matrix(Fraction(RomanNumeral)),...)
--E 8

--S 9 of 15
y := factorial 10
--R
--R
--R   (9)  3628800
--R                                                          Type: PositiveInteger
--E 9

--S 10 of 15
roman y
--R
--R
--R   (10)
--R  ((((I))))((((I))))((((I)))) (((I)))(((I)))(((I)))(((I)))(((I)))(((I))) ((I))(
--R  (I)) MMMMMMMMDCCC
--R                                                             Type: RomanNumeral
--E 10

--S 11 of 15
a := roman(78)
--R
--R
--R   (11)  LXXVIII
--R                                                             Type: RomanNumeral
--E 11

--S 12 of 15
b := roman(87)
--R
--R
--R   (12)  LXXXVII
--R                                                             Type: RomanNumeral
--E 12

--S 13 of 15
a + b
--R
--R
--R   (13)  CLXV
--R                                                             Type: RomanNumeral
--E 13
```

```
--S 14 of 15
a * b
--R
--R
--R   (14)  MMMMMMDCCLXXXVI
--R                                                    Type: RomanNumeral
--E 14

--S 15 of 15
b rem a
--R
--R
--R   (15)  IX
--R                                                    Type: RomanNumeral
--E 15
)spool
)lisp (bye)
```

———-

— RomanNumeral.help —

```
====================================================================
RomanNumeral Examples
====================================================================

The Roman numeral package was added to Axiom in MCMLXXXVI for use in
denoting higher order derivatives.

For example, let f be a symbolic operator.

  f := operator 'f
    f
                                  Type: BasicOperator

This is the seventh derivative of f with respect to x.
  D(f x,x,7)
     (vii)
    f     (x)
                                  Type: Expression Integer

You can have integers printed as Roman numerals by declaring variables to
be of type RomanNumeral (abbreviation ROMAN).

  a := roman(1978 - 1965)
    XIII
                                  Type: RomanNumeral

This package now has a small but devoted group of followers that claim
```

this domain has shown its efficacy in many other contexts. They claim
that Roman numerals are every bit as useful as ordinary integers.

In a sense, they are correct, because Roman numerals form a ring and you
can therefore construct polynomials with Roman numeral coefficients,
matrices over Roman numerals, etc..

```
x : UTS(ROMAN,'x,0) := x
  x
                          Type: UnivariateTaylorSeries(RomanNumeral,x,0)
```

Was Fibonacci Italian or ROMAN?

```
recip(1 - x - x**2)
              2        3      4         5         6        7          8
   I + x + II x  + III x  + V x  + VIII x  + XIII x  + XXI x  + XXXIV x
 +
       9           10      11
   LV x  + LXXXIX x   + O(x  )
                 Type: Union(UnivariateTaylorSeries(RomanNumeral,x,0),...)
```

You can also construct fractions with Roman numeral numerators and
denominators, as this matrix Hilberticus illustrates.

```
m : MATRIX FRAC ROMAN
                         Type: Void
```

```
m := matrix [ [1/(i + j) for i in 1..3] for j in 1..3]
      + I    I    I+
      |--   ---  --|
      |II   III  IV|
      |            |
      | I    I   I |
      |---  --   - |
      |III  IV   V |
      |            |
      | I    I    I|
      |--    -   --|
      +IV    V   VI+
                         Type: Matrix Fraction RomanNumeral
```

Note that the inverse of the matrix has integral ROMAN entries.

```
inverse m
      +LXXII   - CCXL    CLXXX +
      |                       |
      |- CCXL    CM     - DCCXX|
      |                       |
      +CLXXX   - DCCXX    DC   +
                         Type: Union(Matrix Fraction RomanNumeral,...)
```

```
Unfortunately, the spoil-sports say that the fun stops when the
numbers get big---mostly because the Romans didn't establish
conventions about representing very large numbers.

  y := factorial 10
    3628800
                          Type: PositiveInteger

You work it out!

  roman y
  ((((I))))((((I))))((((I)))) (((I)))(((I)))(((I)))(((I)))(((I)))(((I))) ((I))(
  (I)) MMMMMMMMDCCC
                           Type: RomanNumeral

Issue the system command )show RomanNumeral to display the full
list of operations defined by RomanNumeral.


  a := roman(78)
    LXXVIII
                      Type: RomanNumeral

  b := roman(87)
    LXXXVII
                      Type: RomanNumeral

  a + b
    CLXV
                      Type: RomanNumeral


  a * b
    MMMMMMDCCLXXXVI
                      Type: RomanNumeral

  b rem a
    IX
                      Type: RomanNumeral

See Also:
o )help Integer
o )help Complex
o )help Factored
o )help Records
o )help Fraction
o )help RadixExpansion
o )help HexadecimalExpansion
o )help BinaryExpansion
o )help DecimalExpansion
```

```
o )help IntegerNumberTheoryFunctions
o )show RomanNumeral
```

19.12.1 RomanNumeral (ROMAN)



See

⇒ “Integer” (INT) 10.30.1 on page 1329
⇒ “NonNegativeInteger” (NNI) 15.5.1 on page 1706
⇒ “PositiveInteger” (PI) 17.28.1 on page 2066

Exports:

0	1	abs	addmod
associates?	base	binomial	bit?
characteristic	coerce	convert	copy
D	dec	differentiate	divide
euclideanSize	even?	expressIdealMember	exquo
extendedEuclidean	extendedEuclidean	factor	factorial
gcd	gcdPolynomial	hash	inc
init	invmod	latex	lcm
length	mask	max	min
mulmod	multiEuclidean	negative?	nextItem
odd?	one?	patternMatch	permutation
positive?	positiveRemainder	powmod	prime?
principalIdeal	random	rational	rational?
rationalIfCan	recip	reducedSystem	retract
retractIfCan	roman	sample	shift
sign	sizeLess?	squareFree	squareFreePart
submod	subtractIfCan	symmetricRemainder	unit?
unitCanonical	unitNormal	zero?	?*?
?**?	?+?	?-?	-?
?<?	?<=?	?=?	?>?
?>=?	?^?	?~=?	?quo?
?rem?			

— domain ROMAN RomanNumeral —

```
)abbrev domain ROMAN RomanNumeral
++ Author: Mark Botch
++ Date Created:
++ Change History:
++ Related Constructors:
++ Keywords: roman numerals
++ Description:
++ \spadtype{RomanNumeral} provides functions for converting
++ integers to roman numerals.

RomanNumeral(): IntegerNumberSystem with
    canonical
      ++ mathematical equality is data structure equality.
    canonicalsClosed
      ++ two positives multiply to give positive.
    noetherian
      ++ ascending chain condition on ideals.
    convert: Symbol  -> %
      ++ convert(n) creates a roman numeral for symbol n.
    roman  : Symbol  -> %
      ++ roman(n) creates a roman numeral for symbol n.
    roman  : Integer -> %
      ++ roman(n) creates a roman numeral for n.
```

```
  == Integer add
        import NumberFormats()

        roman(n:Integer) == n::%
        roman(sy:Symbol) == convert sy
        convert(sy:Symbol):%    == ScanRoman(string sy)::%

        coerce(r:%):OutputForm ==
            n := convert(r)@Integer
            -- okay, we stretch it
            zero? n => n::OutputForm
            negative? n => - ((-r)::OutputForm)
            FormatRoman(n::PositiveInteger)::Symbol::OutputForm
```

———-

— ROMAN.dotabb —

```
"ROMAN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ROMAN"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ROMAN" -> "ALIST"
```

———-

19.13 domain ROUTINE RoutinesTable

— RoutinesTable.input —

```
)set break resume
)sys rm -f RoutinesTable.output
)spool RoutinesTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show RoutinesTable
--R
--R RoutinesTable  is a domain constructor
--R Abbreviation for RoutinesTable is ROUTINE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ROUTINE
--R
```

```
--R------------------------------ Operations --------------------------------
--R concat : (%,%) -> %                    copy : % -> %
--R deleteRoutine! : (%,Symbol) -> %      dictionary : () -> %
--R elt : (%,Symbol,Any) -> Any           ?.? : (%,Symbol) -> Any
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(Any)              eq? : (%,%) -> Boolean
--R getMeasure : (%,Symbol) -> Float      index? : (Symbol,%) -> Boolean
--R indices : % -> List(Symbol)           key? : (Symbol,%) -> Boolean
--R keys : % -> List(Symbol)              map : ((Any -> Any),%) -> %
--R qelt : (%,Symbol) -> Any              routines : () -> %
--R sample : () -> %                      selectFiniteRoutines : % -> %
--R selectNonFiniteRoutines : % -> %      selectODEIVPRoutines : % -> %
--R selectPDERoutines : % -> %            setelt : (%,Symbol,Any) -> Any
--R showTheRoutinesTable : () -> %        table : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R any? : ((Any -> Boolean),%) -> Boolean if $ has finiteAggregate
--R any? : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R bag : List(Record(key: Symbol,entry: Any)) -> %
--R changeMeasure : (%,Symbol,Float) -> %
--R changeThreshhold : (%,Symbol,Float) -> %
--R coerce : % -> OutputForm if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R construct : List(Record(key: Symbol,entry: Any)) -> %
--R convert : % -> InputForm if Record(key: Symbol,entry: Any) has KONVERT(INFORM)
--R count : ((Any -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R count : (Any,%) -> NonNegativeInteger if $ has finiteAggregate and Any has SETCAT
--R count : (Record(key: Symbol,entry: Any),%) -> NonNegativeInteger if $ has finiteAggregate and Record(key
--R count : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R dictionary : List(Record(key: Symbol,entry: Any)) -> %
--R entry? : (Any,%) -> Boolean if $ has finiteAggregate and Any has SETCAT
--R eval : (%,List(Equation(Any))) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,Equation(Any)) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,Any,Any) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,List(Any),List(Any)) -> % if Any has EVALAB(ANY) and Any has SETCAT
--R eval : (%,List(Record(key: Symbol,entry: Any)),List(Record(key: Symbol,entry: Any))) -> % if Record(key
--R eval : (%,Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> % if Record(key: Symbol,entr
--R eval : (%,Equation(Record(key: Symbol,entry: Any))) -> % if Record(key: Symbol,entry: Any) has EVALAB(Re
--R eval : (%,List(Equation(Record(key: Symbol,entry: Any)))) -> % if Record(key: Symbol,entry: Any) has EVA
--R every? : ((Any -> Boolean),%) -> Boolean if $ has finiteAggregate
--R every? : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R extract! : % -> Record(key: Symbol,entry: Any)
--R fill! : (%,Any) -> % if $ has shallowlyMutable
--R find : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> Union(Record(key: Symbol,entry: Any),"failed")
--R first : % -> Any if Symbol has ORDSET
--R getExplanations : (%,String) -> List(String)
--R hash : % -> SingleInteger if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R insert! : (Record(key: Symbol,entry: Any),%) -> %
--R inspect : % -> Record(key: Symbol,entry: Any)
--R latex : % -> String if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
```

```
--R map : (((Any,Any) -> Any),%,%) -> %
--R map : ((Record(key: Symbol,entry: Any) -> Record(key: Symbol,entry: Any)),%) -> %
--R map! : ((Any -> Any),%) -> % if $ has shallowlyMutable
--R map! : ((Record(key: Symbol,entry: Any) -> Record(key: Symbol,entry: Any)),%) -> % if $ has
--R maxIndex : % -> Symbol if Symbol has ORDSET
--R member? : (Any,%) -> Boolean if $ has finiteAggregate and Any has SETCAT
--R member? : (Record(key: Symbol,entry: Any),%) -> Boolean if $ has finiteAggregate and Record(
--R members : % -> List(Any) if $ has finiteAggregate
--R members : % -> List(Record(key: Symbol,entry: Any)) if $ has finiteAggregate
--R minIndex : % -> Symbol if Symbol has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(Any) if $ has finiteAggregate
--R parts : % -> List(Record(key: Symbol,entry: Any)) if $ has finiteAggregate
--R qsetelt! : (%,Symbol,Any) -> Any if $ has shallowlyMutable
--R recoverAfterFail : (%,String,Integer) -> Union(String,"failed")
--R reduce : (((Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> Record(key: Sy
--R reduce : (((Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> Record(key: Sy
--R reduce : (((Record(key: Symbol,entry: Any),Record(key: Symbol,entry: Any)) -> Record(key: Sy
--R remove : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Record(key: Symbol,entry: Any),%) -> % if $ has finiteAggregate and Record(key: Sy
--R remove! : (Symbol,%) -> Union(Any,"failed")
--R remove! : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R remove! : (Record(key: Symbol,entry: Any),%) -> % if $ has finiteAggregate
--R removeDuplicates : % -> % if $ has finiteAggregate and Record(key: Symbol,entry: Any) has SE
--R search : (Symbol,%) -> Union(Any,"failed")
--R select : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R select! : ((Record(key: Symbol,entry: Any) -> Boolean),%) -> % if $ has finiteAggregate
--R selectIntegrationRoutines : % -> %
--R selectMultiDimensionalRoutines : % -> %
--R selectOptimizationRoutines : % -> %
--R selectSumOfSquaresRoutines : % -> %
--R size? : (%,NonNegativeInteger) -> Boolean
--R swap! : (%,Symbol,Symbol) -> Void if $ has shallowlyMutable
--R table : List(Record(key: Symbol,entry: Any)) -> %
--R ?~=? : (%,%) -> Boolean if Any has SETCAT or Record(key: Symbol,entry: Any) has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— RoutinesTable.help —

```
=====================================================================
RoutinesTable examples
=====================================================================
```

```
See Also:
o )show RoutinesTable
```

———————-

19.13.1 RoutinesTable (ROUTINE)



Exports:

any?	bag
changeMeasure	changeThreshhold
coerce	concat
construct	convert
copy	count
deleteRoutine!	dictionary
elt	empty
empty?	entries
entry?	eq?
eval	every?
extract!	fill!
find	first
getExplanations	getMeasure
hash	index?
indices	insert!
inspect	key?
keys	latex
less?	map
map!	maxIndex
member?	members
minIndex	more?
parts	qelt
qsetelt!	recoverAfterFail
reduce	remove
remove!	removeDuplicates
routines	sample
search	select
select!	selectFiniteRoutines
selectIntegrationRoutines	selectNonFiniteRoutines
selectMultiDimensionalRoutines	selectODEIVPRoutines
selectOptimizationRoutines	selectPDERoutines
selectSumOfSquaresRoutines	setelt
showTheRoutinesTable	size?
swap!	table
#?	?=?
?~=?	?.?

— domain ROUTINE RoutinesTable —

```
)abbrev domain ROUTINE RoutinesTable
++ Author: Brian Dupee
++ Date Created: August 1994
++ Date Last Updated: December 1997
++ Basic Operations: routines, getMeasure
++ Related Constructors: TableAggregate(Symbol,Any)
++ Description:
++ \axiomType{RoutinesTable} implements a database and associated tuning
```

```
++ mechanisms for a set of known NAG routines

RoutinesTable(): E == I where
  F  ==> Float
  ST  ==> String
  LST  ==> List String
  Rec  ==> Record(key:Symbol,entry:Any)
  RList  ==> List(Record(key:Symbol,entry:Any))
  IFL  ==> List(Record(ifail:Integer,instruction:ST))
  Entry  ==> Record(chapter:ST, type:ST, domainName: ST,
                    defaultMin:F, measure:F, failList:IFL, explList:LST)

  E ==> TableAggregate(Symbol,Any) with

    concat:(%,%) -> %
      ++ concat(x,y) merges two tables x and y
    routines:() -> %
      ++ routines() initialises a database of known NAG routines
    selectIntegrationRoutines:% -> %
      ++ selectIntegrationRoutines(R) chooses only those routines from
      ++ the database which are for integration
    selectOptimizationRoutines:% -> %
      ++ selectOptimizationRoutines(R) chooses only those routines from
      ++ the database which are for integration
    selectPDERoutines:% -> %
      ++ selectPDERoutines(R) chooses only those routines from the
      ++ database which are for the solution of PDE's
    selectODEIVPRoutines:% -> %
      ++ selectODEIVPRoutines(R) chooses only those routines from the
      ++ database which are for the solution of ODE's
    selectFiniteRoutines:% -> %
      ++ selectFiniteRoutines(R) chooses only those routines from the
      ++ database which are designed for use with finite expressions
    selectSumOfSquaresRoutines:% -> %
      ++ selectSumOfSquaresRoutines(R) chooses only those routines from the
      ++ database which are designed for use with sums of squares
    selectNonFiniteRoutines:% -> %
      ++ selectNonFiniteRoutines(R) chooses only those routines from the
      ++ database which are designed for use with non-finite expressions.
    selectMultiDimensionalRoutines:% -> %
      ++ selectMultiDimensionalRoutines(R) chooses only those routines from
      ++ the database which are designed for use with multi-dimensional
      ++ expressions
    changeThreshhold:(%,Symbol,F) -> %
      ++ changeThreshhold(R,s,newValue) changes the value below which,
      ++ given a NAG routine generating a higher measure, the routines will
      ++ make no attempt to generate a measure.
    changeMeasure:(%,Symbol,F) -> %
      ++ changeMeasure(R,s,newValue) changes the maximum value for a
      ++ measure of the given NAG routine.
```

```
    getMeasure:(%,Symbol) -> F
      ++ getMeasure(R,s) gets the current value of the maximum measure for
      ++ the given NAG routine.
    getExplanations:(%,ST) -> LST
      ++ getExplanations(R,s) gets the explanations of the output parameters for
      ++ the given NAG routine.
    deleteRoutine!:(%,Symbol) -> %
      ++ deleteRoutine!(R,s) destructively deletes the given routine from
      ++ the current database of NAG routines
    showTheRoutinesTable:() -> %
      ++ showTheRoutinesTable() returns the current table of NAG routines.
    recoverAfterFail:(%,ST,Integer) ->  Union(ST,"failed")
      ++ recoverAfterFail(routs,routineName,ifailValue) acts on the
      ++ instructions given by the ifail list
    finiteAggregate

  I ==> Result add

    Rep := Result
    import Rep

    theRoutinesTable:% := routines()

    showTheRoutinesTable():% == theRoutinesTable

    integrationRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
      (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
        elt(a,chapter) = "Integration"
      false

    selectIntegrationRoutines(R:%):% == select(integrationRoutine?,R)

    optimizationRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
      (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
        elt(a,chapter) = "Optimization"
      false

    selectOptimizationRoutines(R:%):% == select(optimizationRoutine?,R)

    PDERoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
      (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
        elt(a,chapter) = "PDE"
      false

    selectPDERoutines(R:%):% == select(PDERoutine?,R)

    ODERoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
      (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
        elt(a,chapter) = "ODE"
      false
```

```
selectODEIVPRoutines(R:%):% == select(ODERoutine?,R)

sumOfSquaresRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
  (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
    elt(a,type) = "SS"
  false

selectSumOfSquaresRoutines(R:%):% == select(sumOfSquaresRoutine?,R)

finiteRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
  (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
    elt(a,type) = "One-dimensional finite"
  false

selectFiniteRoutines(R:%):% == select(finiteRoutine?,R)

infiniteRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
  (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
    elt(a,type) = "One-dimensional infinite"
  false

semiInfiniteRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
  (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
    elt(a,type) = "One-dimensional semi-infinite"
  false

nonFiniteRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
  (semiInfiniteRoutine?(r) or infiniteRoutine?(r))

selectNonFiniteRoutines(R:%):% == select(nonFiniteRoutine?,R)

multiDimensionalRoutine?(r:Record(key:Symbol,entry:Any)):Boolean ==
  (a := retractIfCan(r.entry)$AnyFunctions1(Entry)) case Entry =>
    elt(a,type) = "Multi-dimensional"
  false

selectMultiDimensionalRoutines(R:%):% == select(multiDimensionalRoutine?,R)

concat(a:%,b:%):% ==
  membersOfa := (members(a)@List(Record(key:Symbol,entry:Any)))
  membersOfb := (members(b)@List(Record(key:Symbol,entry:Any)))
  allMembers:=
    concat(membersOfa,membersOfb)$List(Record(key:Symbol,entry:Any))
  construct(allMembers)

changeThreshhold(R:%,s:Symbol,newValue:F):% ==
  (a := search(s,R)) case Any =>
    e := retract(a)$AnyFunctions1(Entry)
    e.defaultMin := newValue
```

```
    a := coerce(e)$AnyFunctions1(Entry)
    insert!([s,a],R)
  error("changeThreshhold","Cannot find routine of that name")$ErrorFunctions

changeMeasure(R:%,s:Symbol,newValue:F):% ==
  (a := search(s,R)) case Any =>
    e := retract(a)$AnyFunctions1(Entry)
    e.measure := newValue
    a := coerce(e)$AnyFunctions1(Entry)
    insert!([s,a],R)
  error("changeMeasure","Cannot find routine of that name")$ErrorFunctions

getMeasure(R:%,s:Symbol):F ==
  (a := search(s,R)) case Any =>
    e := retract(a)$AnyFunctions1(Entry)
    e.measure
  error("getMeasure","Cannot find routine of that name")$ErrorFunctions

deleteRoutine!(R:%,s:Symbol):% ==
  (a := search(s,R)) case Any =>
    e:Record(key:Symbol,entry:Any) := [s,a]
    remove!(e,R)
  error("deleteRoutine!","Cannot find routine of that name")$ErrorFunctions

routines():% ==
  f := "One-dimensional finite"
  s := "One-dimensional semi-infinite"
  i := "One-dimensional infinite"
  m := "Multi-dimensional"
  int := "Integration"
  ode := "ODE"
  pde := "PDE"
  opt := "Optimization"
  d01ajfExplList:LST := ["result:  Calculated value of the integral",
                         "iw:  iw(1) contains the actual number of sub-intervals used, t
                          "w:  contains the end-points of the sub-intervals used along w
                           "abserr:  the estimate of the absolute error of the result",
                            "ifail:  the error warning parameter",
                             "method:  details of the method used and measures of all me
                              "attributes:  a list of the attributes pertaining to the i
  d01asfExplList:LST := ["result:  Calculated value of the integral",
                         "iw:  iw(1) contains the actual number of sub-intervals used, t
                          "lst:  contains the actual number of sub-intervals used",
                           "erlst:  contains the error estimates over the sub-intervals"
                            "rslst:  contains the integral contributions of the sub-inte
                             "ierlst:  contains the error flags corresponding to the val
                              "abserr:  the estimate of the absolute error of the result
                               "ifail:  the error warning parameter",
                                "method:  details of the method used and measures of all
                                 "attributes:  a list of the attributes pertaining to th
```

```
d01fcfExplList:LST := ["result:  Calculated value of the integral",
                       "acc:  the estimate of the relative error of the result",
                        "minpts:  the number of integrand evaluations",
                         "ifail:  the error warning parameter",
                          "method:  details of the method used and measures of all methods",
                           "attributes:  a list of the attributes pertaining to the integrand whic
d01transExplList:LST := ["result:  Calculated value of the integral",
                          "abserr:  the estimate of the absolute error of the result",
                           "method:  details of the method and transformation used and measures of
                            "d01***AnnaTypeAnswer:  the individual results from the routines",
                             "attributes:  a list of the attributes pertaining to the integrand whi
d02bhfExplList:LST := ["x:  the value of x at the end of the calculation",
                       "y:  the computed values of Y\[1\]..Y\[n\] at x",
                        "tol:   the (possible) estimate of the error; this is not guarunteed",
                         "ifail:  the error warning parameter",
                          "method:  details of the method used and measures of all methods",
                           "intensityFunctions:  a list of the attributes and values pertaining t
d02bbfExplList:LST := concat(["result:  the computed values of the solution at the required points"],c
d03eefExplList:LST := ["See the NAG On-line Documentation for D03EEF/D03EDF",
                       "u:  the computed solution u[i][j] is returned in u(i+(j-1)*ngx),for i = 1
e04fdfExplList:LST := ["x:  the position of the minimum",
                       "objf:  the value of the objective function at x",
                        "ifail:  the error warning parameter",
                         "method:  details of the method used and measures of all methods",
                          "attributes:  a list of the attributes pertaining to the function or 1
e04dgfExplList:LST := concat(e04fdfExplList,
                             ["objgrd:  the values of the derivatives at x",
                              "iter:  the number of iterations performed"])$LST
e04jafExplList:LST := concat(e04fdfExplList,
                             ["bu:  the values of the upper bounds used",
                              "bl:  the values of the lower bounds used"])$LST
e04ucfExplList:LST := concat(e04dgfExplList,
                             ["istate:  the status of every constraint at x",
                              "clamda:  the QP multipliers for the last QP sub-problem",
                               "For other output parameters see the NAG On-line Documentation fo
e04mbfExplList:LST := concat(e04fdfExplList,
                             ["istate:  the status of every constraint at x",
                              "clamda:  the Lagrange multipliers for each constraint"])$LST
d01ajfIfail:IFL := [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"],
                    [5,"delete"], [6,"delete"]]
d01akfIfail:IFL := [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"]]
d01alfIfail:IFL := [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"],
                    [5,"delete"], [6,"delete"], [7,"delete"]]
d01amfIfail:IFL := [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"],
                    [5,"delete"], [6,"delete"]]
d01anfIfail:IFL := [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"],
                    [5,"delete"], [6,"delete"], [7,"delete"]]
d01apfIfail:IFL :=
  [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"], [5,"delete"]]
d01aqfIfail:IFL :=
```

```
  [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"], [5,"delete"]]
d01asfIfail:IFL := [[1,"incrFunEvals"], [2,"delete"], [3,"delete"], [4,"delete"],
      [5,"delete"], [6,"delete"], [7,"delete"], [8,"delete"], [9,"delete"]]
d01fcfIfail:IFL := [[1,"delete"], [2,"incrFunEvals"], [3,"delete"]]
d01gbfIfail:IFL := [[1,"delete"], [2,"incrFunEvals"]]
d02bbfIfail:IFL :=
  [[1,"delete"], [2,"decrease tolerance"], [3,"increase tolerance"],
   [4,"delete"], [5,"delete"], [6,"delete"], [7,"delete"]]
d02bhfIfail:IFL :=
  [[1,"delete"], [2,"decrease tolerance"], [3,"increase tolerance"],
   [4,"no action"], [5,"delete"], [6,"delete"], [7,"delete"]]
d02cjfIfail:IFL :=
  [[1,"delete"], [2,"decrease tolerance"], [3,"increase tolerance"],
   [4,"delete"], [5,"delete"], [6,"no action"], [7,"delete"]]
d02ejfIfail:IFL :=
  [[1,"delete"], [2,"decrease tolerance"], [3,"increase tolerance"],
   [4,"delete"], [5,"delete"], [6,"no action"], [7,"delete"], [8,"delete"],
    [9,"delete"]]
e04dgfIfail:IFL := [[3,"delete"], [4,"no action"], [6,"delete"],
                    [7,"delete"], [8,"delete"], [9,"delete"]]
e04fdfIfail:IFL :=
  [[1,"delete"], [2,"delete"], [3,"delete"], [4,"delete"],
    [5,"no action"], [6,"no action"], [7,"delete"], [8,"delete"]]
e04gcfIfail:IFL := [[1,"delete"], [2,"delete"], [3,"delete"], [4,"delete"],
  [5,"no action"], [6,"no action"], [7,"delete"], [8,"delete"], [9,"delete"]]
e04jafIfail:IFL := [[1,"delete"], [2,"delete"], [3,"delete"], [4,"delete"],
  [5,"no action"], [6,"no action"], [7,"delete"], [8,"delete"], [9,"delete"]]
e04mbfIfail:IFL :=
  [[1,"delete"], [2,"delete"], [3,"delete"], [4,"delete"], [5,"delete"]]
e04nafIfail:IFL :=
  [[1,"delete"], [2,"delete"], [3,"delete"], [4,"delete"], [5,"delete"],
    [6,"delete"], [7,"delete"], [8,"delete"], [9,"delete"]]
e04ucfIfail:IFL := [[1,"delete"], [2,"delete"], [3,"delete"], [4,"delete"],
  [5,"delete"], [6,"delete"], [7,"delete"], [8,"delete"], [9,"delete"]]
d01ajfEntry:Entry := [int, f, "d01ajfAnnaType",0.4,0.4,d01ajfIfail,d01ajfExplList]
d01akfEntry:Entry := [int, f, "d01akfAnnaType",0.6,1.0,d01akfIfail,d01ajfExplList]
d01alfEntry:Entry := [int, f, "d01alfAnnaType",0.6,0.6,d01alfIfail,d01ajfExplList]
d01amfEntry:Entry := [int, i, "d01amfAnnaType",0.5,0.5,d01amfIfail,d01ajfExplList]
d01anfEntry:Entry := [int, f, "d01anfAnnaType",0.6,0.9,d01anfIfail,d01ajfExplList]
d01apfEntry:Entry := [int, f, "d01apfAnnaType",0.7,0.7,d01apfIfail,d01ajfExplList]
d01aqfEntry:Entry := [int, f, "d01aqfAnnaType",0.6,0.7,d01aqfIfail,d01ajfExplList]
d01asfEntry:Entry := [int, s, "d01asfAnnaType",0.6,0.9,d01asfIfail,d01asfExplList]
d01transEntry:Entry:=[int, i, "d01TransformFunctionType",0.6,0.9,[],d01transExplList]
d01gbfEntry:Entry := [int, m, "d01gbfAnnaType",0.6,0.6,d01gbfIfail,d01fcfExplList]
d01fcfEntry:Entry := [int, m, "d01fcfAnnaType",0.5,0.5,d01fcfIfail,d01fcfExplList]
d02bbfEntry:Entry := [ode, "IVP", "d02bbfAnnaType",0.7,0.5,d02bbfIfail,d02bbfExplList]
d02bhfEntry:Entry := [ode, "IVP", "d02bhfAnnaType",0.7,0.49,d02bhfIfail,d02bhfExplList]
d02cjfEntry:Entry := [ode, "IVP", "d02cjfAnnaType",0.7,0.5,d02cjfIfail,d02bbfExplList]
d02ejfEntry:Entry := [ode, "IVP", "d02ejfAnnaType",0.7,0.5,d02ejfIfail,d02bbfExplList]
d03eefEntry:Entry := [pde, "2", "d03eefAnnaType",0.6,0.5,[],d03eefExplList]
```

```
    --d03fafEntry:Entry := [pde, "3", "d03fafAnnaType",0.6,0.5,[],[]]
    e04dgfEntry:Entry := [opt, "CGA", "e04dgfAnnaType",0.4,0.4,e04dgfIfail,e04dgfExplList]
    e04fdfEntry:Entry := [opt, "SS", "e04fdfAnnaType",0.7,0.7,e04fdfIfail,e04fdfExplList]
    e04gcfEntry:Entry := [opt, "SS", "e04gcfAnnaType",0.8,0.8,e04gcfIfail,e04fdfExplList]
    e04jafEntry:Entry := [opt, "QNA", "e04jafAnnaType",0.5,0.5,e04jafIfail,e04jafExplList]
    e04mbfEntry:Entry := [opt, "LP", "e04mbfAnnaType",0.7,0.7,e04mbfIfail,e04mbfExplList]
    e04nafEntry:Entry := [opt, "QP", "e04nafAnnaType",0.7,0.7,e04nafIfail,e04mbfExplList]
    e04ucfEntry:Entry := [opt, "SQP", "e04ucfAnnaType",0.6,0.6,e04ucfIfail,e04ucfExplList]
    rl:RList :=
      [["d01apf" :: Symbol, coerce(d01apfEntry)$AnyFunctions1(Entry)],_
       ["d01aqf" :: Symbol, coerce(d01aqfEntry)$AnyFunctions1(Entry)],_
       ["d01alf" :: Symbol, coerce(d01alfEntry)$AnyFunctions1(Entry)],_
       ["d01anf" :: Symbol, coerce(d01anfEntry)$AnyFunctions1(Entry)],_
       ["d01akf" :: Symbol, coerce(d01akfEntry)$AnyFunctions1(Entry)],_
       ["d01ajf" :: Symbol, coerce(d01ajfEntry)$AnyFunctions1(Entry)],_
       ["d01asf" :: Symbol, coerce(d01asfEntry)$AnyFunctions1(Entry)],_
       ["d01amf" :: Symbol, coerce(d01amfEntry)$AnyFunctions1(Entry)],_
       ["d01transform" :: Symbol, coerce(d01transEntry)$AnyFunctions1(Entry)],_
       ["d01gbf" :: Symbol, coerce(d01gbfEntry)$AnyFunctions1(Entry)],_
       ["d01fcf" :: Symbol, coerce(d01fcfEntry)$AnyFunctions1(Entry)],_
       ["d02bbf" :: Symbol, coerce(d02bbfEntry)$AnyFunctions1(Entry)],_
       ["d02bhf" :: Symbol, coerce(d02bhfEntry)$AnyFunctions1(Entry)],_
       ["d02cjf" :: Symbol, coerce(d02cjfEntry)$AnyFunctions1(Entry)],_
       ["d02ejf" :: Symbol, coerce(d02ejfEntry)$AnyFunctions1(Entry)],_
       ["d03eef" :: Symbol, coerce(d03eefEntry)$AnyFunctions1(Entry)],_
       --["d03faf" :: Symbol, coerce(d03fafEntry)$AnyFunctions1(Entry)],
       ["e04dgf" :: Symbol, coerce(e04dgfEntry)$AnyFunctions1(Entry)],_
       ["e04fdf" :: Symbol, coerce(e04fdfEntry)$AnyFunctions1(Entry)],_
       ["e04gcf" :: Symbol, coerce(e04gcfEntry)$AnyFunctions1(Entry)],_
       ["e04jaf" :: Symbol, coerce(e04jafEntry)$AnyFunctions1(Entry)],_
       ["e04mbf" :: Symbol, coerce(e04mbfEntry)$AnyFunctions1(Entry)],_
       ["e04naf" :: Symbol, coerce(e04nafEntry)$AnyFunctions1(Entry)],_
       ["e04ucf" :: Symbol, coerce(e04ucfEntry)$AnyFunctions1(Entry)]]
    construct(rl)

  getIFL(s:Symbol,l:%):Union(IFL,"failed") ==
    o := search(s,l)$%
    o case "failed" => "failed"
    e := retractIfCan(o)$AnyFunctions1(Entry)
    e case "failed" => "failed"
    e.failList

  getInstruction(l:IFL,ifailValue:Integer):Union(ST,"failed") ==
    output := empty()$ST
    for i in 1..#l repeat
      if ((l.i).ifail=ifailValue)@Boolean then
        output := (l.i).instruction
    empty?(output)$ST => "failed"
    output
```

```
    recoverAfterFail(routs:%,routineName:ST,
                     ifailValue:Integer):Union(ST,"failed") ==
      name := routineName :: Symbol
      failedList := getIFL(name,routs)
      failedList case "failed" => "failed"
      empty? failedList => "failed"
      instr := getInstruction(failedList,ifailValue)
      instr case "failed" => concat(routineName," failed")$ST
      (instr = "delete")@Boolean =>
        deleteRoutine!(routs,name)
        concat(routineName," failed - trying alternatives")$ST
      instr

    getExplanations(R:%,routineName:ST):LST ==
      name := routineName :: Symbol
      (a := search(name,R)) case Any =>
        e := retract(a)$AnyFunctions1(Entry)
        e.explList
      empty()$LST
```

———-

— ROUTINE.dotabb —

```
"ROUTINE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ROUTINE"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"ROUTINE" -> "ALIST"
```

———-

19.14 domain RULECOLD RuleCalled

— RuleCalled.input —

```
)set break resume
)sys rm -f RuleCalled.output
)spool RuleCalled.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show RuleCalled
--R
```

```
--R RuleCalled(f: Symbol)  is a domain constructor
--R Abbreviation for RuleCalled is RULECOLD
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RULECOLD
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R hash : % -> SingleInteger            latex : % -> String
--R name : % -> Symbol                   ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **RuleCalled.help** —

```
========================================================================
RuleCalled examples
========================================================================

See Also:
o )show RuleCalled
```

———-

19.14.1 RuleCalled (RULECOLD)



Exports:
coerce hash latex name ?=? ?~=?

— **domain RULECOLD RuleCalled** —

```
)abbrev domain RULECOLD RuleCalled
++ Author: Mark Botch
++ Description:
++ This domain implements named rules

RuleCalled(f:Symbol): SetCategory with
        name: % -> Symbol
                ++ name(x) returns the symbol
 == add
  name r                 == f
  coerce(r:%):OutputForm == f::OutputForm
  x = y                  == true
  latex(x:%):String      == latex f
```

———-

— RULECOLD.dotabb —

```
"RULECOLD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RULECOLD"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"RULECOLD" -> "ALIST"
```

———-

19.15 domain RULESET Ruleset

— Ruleset.input —

```
)set break resume
)sys rm -f Ruleset.output
)spool Ruleset.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Ruleset
--R
--R Ruleset(Base: SetCategory,R: Join(Ring,PatternMatchable(Base),OrderedSet,ConvertibleTo(Patte
--R Abbreviation for Ruleset is RULESET
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for RULESET
--R
--R------------------------------ Operations --------------------------------
```

```
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R elt : (%,F,PositiveInteger) -> F      ?.? : (%,F) -> F
--R hash : % -> SingleInteger             latex : % -> String
--R ?~=? : (%,%) -> Boolean
--R rules : % -> List(RewriteRule(Base,R,F))
--R ruleset : List(RewriteRule(Base,R,F)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Ruleset.help** —

```
========================================================================
Ruleset examples
========================================================================

See Also:
o )show Ruleset
```

———-

19.15.1 Ruleset (RULESET)



See

⇒ “RewriteRule” (RULE) 19.10.1 on page 2271

Exports:

coerce	elt	hash	latex	rules
ruleset	?=?	?~=?	?.?	

— **domain RULESET Ruleset** —

```
)abbrev domain RULESET Ruleset
++ Author: Manuel Bronstein
++ Date Created: 20 Mar 1990
++ Date Last Updated: 29 Jun 1990
++ Keywords: pattern, matching, rule.
++ Description:
++ Sets of rules for the pattern matcher.
++ A ruleset is a set of pattern matching rules grouped together.

Ruleset(Base, R, F): Exports == Implementation where
  Base   : SetCategory
  R      : Join(Ring, PatternMatchable Base, OrderedSet,
                                ConvertibleTo Pattern Base)
  F      : Join(FunctionSpace R, PatternMatchable Base,
                                ConvertibleTo Pattern Base)

  RR ==> RewriteRule(Base, R, F)

  Exports ==> Join(SetCategory, Eltable(F, F)) with
    ruleset: List RR -> $
      ++ ruleset([r1,...,rn]) creates the rule set \spad{{r1,...,rn}}.
    rules  : $ -> List RR
      ++ rules(r) returns the rules contained in r.
    elt    : ($, F, PositiveInteger) -> F
      ++ elt(r,f,n) or r(f, n) applies all the rules of r to f at most n times.

  Implementation ==> add
    import ApplyRules(Base, R, F)

    Rep := Set RR

    ruleset l                       == {l}$Rep
    coerce(x:$):OutputForm          == coerce(x)$Rep
    x = y                           == x =$Rep y
    elt(x:$, f:F)                   == applyRules(rules x, f)
    elt(r:$, s:F, n:PositiveInteger) == applyRules(rules r, s, n)
    rules x                         == parts(x)$Rep
```

———-

— RULESET.dotabb —

```
"RULESET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=RULESET"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"RULESET" -> "FS"
```

———-

Chapter 20

Chapter S

20.1 domain FORMULA ScriptFormulaFormat

— ScriptFormulaFormat.input —

```
)set break resume
)sys rm -f ScriptFormulaFormat.output
)spool ScriptFormulaFormat.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ScriptFormulaFormat
--R
--R ScriptFormulaFormat  is a domain constructor
--R Abbreviation for ScriptFormulaFormat is FORMULA
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for FORMULA
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : OutputForm -> %
--R coerce : % -> OutputForm             display : % -> Void
--R display : (%,Integer) -> Void        epilogue : % -> List(String)
--R formula : % -> List(String)          hash : % -> SingleInteger
--R latex : % -> String                  new : () -> %
--R prologue : % -> List(String)         ?~=? : (%,%) -> Boolean
--R convert : (OutputForm,Integer) -> %
--R setEpilogue! : (%,List(String)) -> List(String)
--R setFormula! : (%,List(String)) -> List(String)
--R setPrologue! : (%,List(String)) -> List(String)
--R
```

```
--E 1

)spool
)lisp (bye)
```

———-


— **ScriptFormulaFormat.help** —

```
=====================================================================
ScriptFormulaFormat examples
=====================================================================

See Also:
o )show ScriptFormulaFormat
```

———-

20.1.1 ScriptFormulaFormat (FORMULA)



Exports:

coerce	display	epilogue	formula	hash
latex	new	prologue	convert	setEpilogue!
setFormula!	setPrologue!	?=?	?~=?	

— **domain FORMULA ScriptFormulaFormat** —

```
)abbrev domain FORMULA ScriptFormulaFormat
++ Author: Robert S. Sutor
++ Date Created: 1987 through 1990
++ Change History:
++ Basic Operations: coerce, convert, display, epilogue,
++   formula, new, prologue, setEpilogue!, setFormula!, setPrologue!
++ Related Constructors: ScriptFormulaFormat1
```

```
++ Also See: TexFormat
++ AMS Classifications:
++ Keywords: output, format, SCRIPT, BookMaster, formula
++ References:
++   SCRIPT Mathematical Formula Formatter User's Guide, SH20-6453,
++   IBM Corporation, Publishing Systems Information Development,
++   Dept. G68, P.O. Box 1900, Boulder, Colorado, USA 80301-9191.
++ Description:
++ \spadtype{ScriptFormulaFormat} provides a coercion from
++ \spadtype{OutputForm} to IBM SCRIPT/VS Mathematical Formula Format.
++ The basic SCRIPT formula format object consists of three parts:  a
++ prologue, a formula part and an epilogue.  The functions
++ \spadfun{prologue}, \spadfun{formula} and \spadfun{epilogue}
++ extract these parts, respectively.  The central parts of the expression
++ go into the formula part.  The other parts can be set
++ (\spadfun{setPrologue!}, \spadfun{setEpilogue!}) so that contain the
++ appropriate tags for printing.  For example, the prologue and
++ epilogue might simply contain ":df."  and ":edf."  so that the
++ formula section will be printed in display math mode.

ScriptFormulaFormat(): public == private where
  E      ==> OutputForm
  I      ==> Integer
  L      ==> List
  S      ==> String

  public == SetCategory with
    coerce:   E -> %
      ++ coerce(o) changes o in the standard output format to
      ++ SCRIPT formula format.
    convert:  (E,I) -> %
      ++ convert(o,step) changes o in standard output format to
      ++ SCRIPT formula format and also adds the given step number.
      ++ This is useful if you want to create equations with given numbers
      ++ or have the equation numbers correspond to the interpreter step
      ++ numbers.
    display:  (%, I) -> Void
      ++ display(t,width) outputs the formatted code t so that each
      ++ line has length less than or equal to \spadvar{width}.
    display:  % -> Void
      ++ display(t) outputs the formatted code t so that each
      ++ line has length less than or equal to the value set by
      ++ the system command \spadsyscom{set output length}.
    epilogue: % -> L S
      ++ epilogue(t) extracts the epilogue section of a formatted object t.
    formula:      % -> L S
      ++ formula(t) extracts the formula section of a formatted object t.
    new:      () -> %
      ++ new() create a new, empty object. Use \spadfun{setPrologue!},
      ++ \spadfun{setFormula!} and \spadfun{setEpilogue!} to set the
```

```
      ++ various components of this object.
    prologue: % -> L S
      ++ prologue(t) extracts the prologue section of a formatted object t.
    setEpilogue!: (%, L S) -> L S
      ++ setEpilogue!(t,strings) sets the epilogue section of a
      ++ formatted object t to strings.
    setFormula!:  (%, L S) -> L S
      ++ setFormula!(t,strings) sets the formula section of a
      ++ formatted object t to strings.
    setPrologue!: (%, L S) -> L S
      ++ setPrologue!(t,strings) sets the prologue section of a
      ++ formatted object t to strings.

  private == add
    import OutputForm
    import Character
    import Integer
    import List OutputForm
    import List String

    Rep := Record(prolog : L S, formula : L S, epilog : L S)

    -- local variables declarations and definitions

    expr: E
    prec,opPrec: I
    str:  S
    blank         : S := " @@ "

    maxPrec       : I   := 1000000
    minPrec       : I   := 0

    splitChars    : S   := " <>[](){}+*=,-%"

    unaryOps      : L S := ["-","^"]$(L S)
    unaryPrecs    : L I := [700,260]$(L I)

    -- the precedence of / in the following is relatively low because
    -- the bar obviates the need for parentheses.
    binaryOps     : L S := ["+->","|","**","/","<",">","=","OVER"]$(L S)
    binaryPrecs   : L I := [0,0,900, 700,400,400,400,   700]$(L I)

    naryOps       : L S := ["-","+","*",blank,",",";"," ","ROW","",
                            " habove "," here "," labove "]$(L S)
    naryPrecs     : L I := [700,700,800,  800,110,110,  0,    0, 0,
                             0,  0,  0]$(L I)
--  naryNGOps     : L S := ["ROW"," here "]$(L S)
    naryNGOps     : L S := nil$(L S)

    plexOps       : L S := ["SIGMA","PI","INTSIGN","INDEFINTEGRAL"]$(L S)
```

```
plexPrecs     : L I := [    700, 800,      700,            700]$(L I)

specialOps    : L S := ["MATRIX","BRACKET","BRACE","CONCATB",     _
                        "AGGLST","CONCAT","OVERBAR","ROOT","SUB", _
                        "SUPERSUB","ZAG","AGGSET","SC","PAREN"]

-- the next two lists provide translations for some strings for
-- which the formula formatter provides special variables.

specialStrings : L S :=
  ["5","..."]
specialStringsInFormula : L S :=
  [" alpha "," ellipsis "]

-- local function signatures

addBraces:      S -> S
addBrackets:    S -> S
group:          S -> S
formatBinary:   (S,L E, I) -> S
formatFunction: (S,L E, I) -> S
formatMatrix:   L E -> S
formatNary:     (S,L E, I) -> S
formatNaryNoGroup: (S,L E, I) -> S
formatNullary:  S -> S
formatPlex:     (S,L E, I) -> S
formatSpecial:  (S,L E, I) -> S
formatUnary:    (S,  E, I) -> S
formatFormula:      (E,I) -> S
parenthesize:   S -> S
precondition:   E -> E
postcondition:  S -> S
splitLong:      (S,I) -> L S
splitLong1:     (S,I) -> L S
stringify:      E -> S

-- public function definitions

new() : % == [[".eq set blank @",":df."]$(L S),
  [""]$(L S), [":edf."]$(L S)]$Rep

coerce(expr : E): % ==
  f : % := new()$%
  f.formula := [postcondition
    formatFormula(precondition expr, minPrec)]$(L S)
  f

convert(expr : E, stepNum : I): % ==
  f : % := new()$%
  f.formula := concat(["<leqno lparen ",string(stepNum)$S,
```

```
      " rparen>"], [postcondition
        formatFormula(precondition expr, minPrec)]$(L S))
    f

  display(f : %, len : I) ==
    s,t : S
    for s in f.prolog repeat sayFORMULA(s)$Lisp
    for s in f.formula repeat
      for t in splitLong(s, len) repeat sayFORMULA(t)$Lisp
    for s in f.epilog repeat sayFORMULA(s)$Lisp
    void()$Void

  display(f : %) ==
    display(f, _$LINELENGTH$Lisp pretend I)

  prologue(f : %) == f.prolog
  formula(f : %)  == f.formula
  epilogue(f : %) == f.epilog

  setPrologue!(f : %, l : L S) == f.prolog := l
  setFormula!(f : %, l : L S)  == f.formula := l
  setEpilogue!(f : %, l : L S) == f.epilog := l

  coerce(f : %): E ==
    s,t : S
    l : L S := nil
    for s in f.prolog repeat l := concat(s,l)
    for s in f.formula repeat
      for t in splitLong(s, (_$LINELENGTH$Lisp pretend Integer) - 4) repeat
        l := concat(t,l)
    for s in f.epilog repeat l := concat(s,l)
    (reverse l) :: E

  -- local function definitions

  postcondition(str: S): S ==
    len : I := #str
    len < 4 => str
    plus : Character := char "+"
    minus: Character := char "-"
    for i in 1..(len-1) repeat
      if (str.i =$Character plus) and (str.(i+1) =$Character minus)
        then setelt(str,i,char " ")$S
    str

  stringify expr == object2String(expr)$Lisp pretend S

  splitLong(str : S, len : I): L S ==
    -- this blocks into lines
    if len < 20 then len := _$LINELENGTH$Lisp
```

```
    splitLong1(str, len)

  splitLong1(str : S, len : I) ==
    l : List S := nil
    s : S := ""
    ls : I := 0
    ss : S
    lss : I
    for ss in split(str,char " ") repeat
      lss := #ss
      if ls + lss > len then
        l := concat(s,l)$List(S)
        s := ""
        ls := 0
      lss > len => l := concat(ss,l)$List(S)
      ls := ls + lss + 1
      s := concat(s,concat(ss," ")$S)$S
    if ls > 0 then l := concat(s,l)$List(S)
    reverse l

  group str ==
    concat ["<",str,">"]

  addBraces str ==
    concat ["left lbrace ",str," right rbrace"]

  addBrackets str ==
    concat ["left lb ",str," right rb"]

  parenthesize str ==
    concat ["left lparen ",str," right rparen"]

  precondition expr ==
    outputTran(expr)$Lisp

  formatSpecial(op : S, args : L E, prec : I) : S ==
    op = "AGGLST" =>
      formatNary(",",args,prec)
    op = "AGGSET" =>
      formatNary(";",args,prec)
    op = "CONCATB" =>
      formatNary(" ",args,prec)
    op = "CONCAT" =>
      formatNary("",args,prec)
    op = "BRACKET" =>
      group addBrackets formatFormula(first args, minPrec)
    op = "BRACE" =>
      group addBraces formatFormula(first args, minPrec)
    op = "PAREN" =>
      group parenthesize formatFormula(first args, minPrec)
```

```
      op = "OVERBAR" =>
        null args => ""
        group concat [formatFormula(first args, minPrec)," bar"]
      op = "ROOT" =>
        null args => ""
        tmp : S := formatFormula(first args, minPrec)
        null rest args => group concat ["sqrt ",tmp]
        group concat ["midsup adjust(u 1.5 r 9) ",
          formatFormula(first rest args, minPrec)," sqrt ",tmp]
      op = "SC" =>
        formatNary(" labove ",args,prec)
      op = "SUB" =>
        group concat [formatFormula(first args, minPrec)," sub ",
          formatSpecial("AGGLST",rest args,minPrec)]
      op = "SUPERSUB" =>
        -- variable name
        form : List S := [formatFormula(first args, minPrec)]
        -- subscripts
        args := rest args
        null args => concat form
        tmp : S := formatFormula(first args, minPrec)
        if tmp ^= "" then form := append(form,[" sub ",tmp])$(List S)
        -- superscripts
        args := rest args
        null args => group concat form
        tmp : S := formatFormula(first args, minPrec)
        if tmp ^= "" then form := append(form,[" sup ",tmp])$(List S)
        -- presuperscripts
        args := rest args
        null args => group concat form
        tmp : S := formatFormula(first args, minPrec)
        if tmp ^= "" then form := append(form,[" presup ",tmp])$(List S)
        -- presubscripts
        args := rest args
        null args => group concat form
        tmp : S := formatFormula(first args, minPrec)
        if tmp ^= "" then form := append(form,[" presub ",tmp])$(List S)
        group concat form
      op = "MATRIX" => formatMatrix rest args
--    op = "ZAG" =>
--      concat ["\zag{",formatFormula(first args, minPrec),"}{",
--        formatFormula(first rest args,minPrec),"}"]
      concat ["not done yet for ",op]

    formatPlex(op : S, args : L E, prec : I) : S ==
      hold : S
      p : I := position(op,plexOps)
      p < 1 => error "unknown Script Formula Formatter unary op"
      opPrec := plexPrecs.p
      n : I := #args
```

```
    (n ^= 2) and (n ^= 3) => error "wrong number of arguments for plex"
    s : S :=
      op = "SIGMA"   => "sum"
      op = "PI"      => "product"
      op = "INTSIGN" => "integral"
      op = "INDEFINTEGRAL" => "integral"
      "????"
    hold := formatFormula(first args,minPrec)
    args := rest args
    if op ^= "INDEFINTEGRAL" then
      if hold ^= "" then
        s := concat [s," from",group concat ["\displaystyle ",hold]]
      if not null rest args then
        hold := formatFormula(first args,minPrec)
        if hold ^= "" then
          s := concat [s," to",group concat ["\displaystyle ",hold]]
        args := rest args
      s := concat [s," ",formatFormula(first args,minPrec)]
    else
      hold := group concat [hold," ",formatFormula(first args,minPrec)]
      s := concat [s," ",hold]
    if opPrec < prec then s := parenthesize s
    group s

  formatMatrix(args : L E) : S ==
    -- format for args is [[ROW ...],[ROW ...],[ROW ...]]
    group addBrackets formatNary(" habove ",args,minPrec)

  formatFunction(op : S, args : L E, prec : I) : S ==
    group concat [op, " ", parenthesize formatNary(",",args,minPrec)]

  formatNullary(op : S) ==
    op = "NOTHING" => ""
    group concat [op,"()"]

  formatUnary(op : S, arg : E, prec : I) ==
    p : I := position(op,unaryOps)
    p < 1 => error "unknown Script Formula Formatter unary op"
    opPrec := unaryPrecs.p
    s : S := concat [op,formatFormula(arg,opPrec)]
    opPrec < prec => group parenthesize s
    op = "-" => s
    group s

  formatBinary(op : S, args : L E, prec : I) : S ==
    p : I := position(op,binaryOps)
    p < 1 => error "unknown Script Formula Formatter binary op"
    op :=
      op = "**"    => " sup "
      op = "/"     => " over "
```

```
      op = "OVER"  => " over "
      op
    opPrec := binaryPrecs.p
    s : S := formatFormula(first args, opPrec)
    s := concat [s,op,formatFormula(first rest args, opPrec)]
    group
      op = " over " => s
      opPrec < prec => parenthesize s
      s

  formatNary(op : S, args : L E, prec : I) : S ==
    group formatNaryNoGroup(op, args, prec)

  formatNaryNoGroup(op : S, args : L E, prec : I) : S ==
    null args => ""
    p : I := position(op,naryOps)
    p < 1 => error "unknown Script Formula Formatter nary op"
    op :=
      op = ","     => ", @@ "
      op = ";"     => "; @@ "
      op = "*"     => blank
      op = " "     => blank
      op = "ROW"   => " here "
      op
    l : L S := nil
    opPrec := naryPrecs.p
    for a in args repeat
      l := concat(op,concat(formatFormula(a,opPrec),l)$L(S))$L(S)
    s : S := concat reverse rest l
    opPrec < prec => parenthesize s
    s

  formatFormula(expr,prec) ==
    i : Integer
    ATOM(expr)$Lisp pretend Boolean =>
      str := stringify expr
      INTEGERP(expr)$Lisp =>
        i := expr : Integer
        if (i < 0) or (i > 9) then group str else str
      (i := position(str,specialStrings)) > 0 =>
        specialStringsInFormula.i
      str
    l : L E := (expr pretend L E)
    null l => blank
    op : S := stringify first l
    args : L E := rest l
    nargs : I := #args

    -- special cases
    member?(op, specialOps) => formatSpecial(op,args,prec)
```

```
      member?(op, plexOps)    => formatPlex(op,args,prec)

      -- nullary case
      0 = nargs => formatNullary op

      -- unary case
      (1 = nargs) and member?(op, unaryOps) =>
        formatUnary(op, first args, prec)

      -- binary case
      (2 = nargs) and member?(op, binaryOps) =>
        formatBinary(op, args, prec)

      -- nary case
      member?(op,naryNGOps) => formatNaryNoGroup(op,args, prec)
      member?(op,naryOps) => formatNary(op,args, prec)
      op := formatFormula(first l,minPrec)
      formatFunction(op,args,prec)
```

———-

— **FORMULA.dotabb** —

```
"FORMULA" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FORMULA"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"FORMULA" -> "STRING"
```

———-

20.2 domain SEG Segment

— **Segment.input** —

```
)set break resume
)sys rm -f Segment.output
)spool Segment.output
)set message test on
)set message auto off
)clear all
--S 1 of 10
s := 3..10
--R
--R
--R   (1)  3..10
```

```
--R                                                  Type: Segment(PositiveInteger)
--E 1

--S 2 of 10
lo s
--R
--R
--R   (2)  3
--R                                                     Type: PositiveInteger
--E 2

--S 3 of 10
hi s
--R
--R
--R   (3)  10
--R                                                     Type: PositiveInteger
--E 3

--S 4 of 10
t := 10..3 by -2
--R
--R
--R   (4)  10..3 by - 2
--R                                                  Type: Segment(PositiveInteger)
--E 4

--S 5 of 10
incr s
--R
--R
--R   (5)  1
--R                                                     Type: PositiveInteger
--E 5

--S 6 of 10
incr t
--R
--R
--R   (6)  - 2
--R                                                           Type: Integer
--E 6

--S 7 of 10
l := [1..3, 5, 9, 15..11 by -1]
--R
--R
--R   (7)  [1..3,5..5,9..9,15..11 by - 1]
--R                                          Type: List(Segment(PositiveInteger))
--E 7
```

```
--S 8 of 10
expand s
--R
--R
--R   (8)  [3,4,5,6,7,8,9,10]
--R                                                    Type: List(Integer)
--E 8

--S 9 of 10
expand t
--R
--R
--R   (9)  [10,8,6,4]
--R                                                    Type: List(Integer)
--E 9

--S 10 of 10
expand l
--R
--R
--R   (10)  [1,2,3,5,9,15,14,13,12,11]
--R                                                    Type: List(Integer)
--E 10
)spool
)lisp (bye)
```

———-

— Segment.help —

```
====================================================================
Segment examples
====================================================================

The Segment domain provides a generalized interval type.

Segments are created using the .. construct by indicating the
(included) end points.

  s := 3..10
    3..10
                            Type: Segment PositiveInteger

The first end point is called the lo and the second is called hi.

  lo s
    3
                            Type: PositiveInteger
```

```
These names are used even though the end points might belong to an
unordered set.

  hi s
    10
                              Type: PositiveInteger

In addition to the end points, each segment has an integer "increment".
An increment can be specified using the "by" construct.

  t := 10..3 by -2
    10..3 by - 2
                              Type: Segment PositiveInteger

This part can be obtained using the incr function.

  incr s
    1
                              Type: PositiveInteger

Unless otherwise specified, the increment is 1.

  incr t
    - 2
                              Type: Integer

A single value can be converted to a segment with equal end points.
This happens if segments and single values are mixed in a list.

  l := [1..3, 5, 9, 15..11 by -1]
    [1..3,5..5,9..9,15..11 by - 1]
                               Type: List Segment PositiveInteger

If the underlying type is an ordered ring, it is possible to perform
additional operations.  The expand operation creates a list of points
in a segment.

  expand s
    [3,4,5,6,7,8,9,10]
                               Type: List Integer

If k > 0, then expand(l..h by k) creates the list [l, l+k, ..., lN]
where lN <= h < lN+k.  If k < 0, then lN >= h > lN+k.

  expand t
    [10,8,6,4]
                               Type: List Integer

It is also possible to expand a list of segments.  This is equivalent
```


```
to appending lists obtained by expanding each segment individually.

  expand l
    [1,2,3,5,9,15,14,13,12,11]
                                  Type: List Integer

See Also:
o )help UniversalSegment
o )help SegmentBinding
o )show Segment
```

———-

20.2.1 Segment (SEG)



See

⇒ “SegmentBinding” (SEGBIND) 20.3.1 on page 2330
⇒ “UniversalSegment” (UNISEG) 22.11.1 on page 2863

Exports:

BY	coerce	convert	expand	hash
hi	high	incr	latex	lo
low	map	segment	?=?	?~=?
?..?				

— domain SEG Segment —

```
)abbrev domain SEG Segment
++ Author:  Stephen M. Watt
++ Date Created:  December 1986
++ Date Last Updated: June 3, 1991
++ Basic Operations:
++ Related Domains:
++ Also See:
```

```
++ AMS Classifications:
++ Keywords: range, segment
++ Examples:
++ References:
++ Description:
++ This type is used to specify a range of values from type \spad{S}.

Segment(S:Type): SegmentCategory(S) with
    if S has SetCategory then SetCategory
    if S has OrderedRing then SegmentExpansionCategory(S, List S)
  == add

    Rep := Record(low: S, high: S, incr: Integer)

    a..b == [a,b,1]
    lo s == s.low
    low s == s.low
    hi s == s.high
    high s == s.high
    incr s == s.incr
    segment(a,b) == [a,b,1]
    BY(s, r) == [lo s, hi s, r]

    if S has SetCategory then
      (s1:%) = (s2:%) ==
        s1.low = s2.low and s1.high=s2.high and s1.incr = s2.incr

      coerce(s:%):OutputForm ==
        seg := SEGMENT(s.low::OutputForm, s.high::OutputForm)
        s.incr = 1 => seg
        infix(" by "::OutputForm, seg, s.incr::OutputForm)

    convert a == [a,a,1]

    if S has OrderedRing then
      expand(ls: List %):List S ==
        lr := nil()$List(S)
        for s in ls repeat
          l := lo s
          h := hi s
          inc := (incr s)::S
          zero? inc => error "Cannot expand a segment with an increment of zero"
          if inc > 0 then
            while l <= h repeat
              lr := concat(l, lr)
              l := l + inc
          else
            while l >= h repeat
              lr := concat(l, lr)
              l := l + inc
```

```
        reverse_! lr

      expand(s : %) == expand([s]$List(%))$%
      map(f : S->S, s : %): List S ==
        lr := nil()$List(S)
        l := lo s
        h := hi s
        inc := (incr s)::S
        if inc > 0 then
          while l <= h repeat
            lr := concat(f l, lr)
            l := l + inc
        else
          while l >= h repeat
            lr := concat(f l, lr)
            l := l + inc
        reverse_! lr
```

———-

— SEG.dotabb —

```
"SEG" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SEG"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"SEG" -> "FLAGG"
```

———-

20.3 domain SEGBIND SegmentBinding

— SegmentBinding.input —

```
)set break resume
)sys rm -f SegmentBinding.output
)spool SegmentBinding.output
)set message test on
)set message auto off
)clear all
--S 1 of 5
x = a..b
--R
--R
--R   (1)  x= a..b
--R                                                Type: SegmentBinding Symbol
```

```
--E 1

--S 2 of 5
sum(i**2, i = 0..n)
--R
--R
--R          3     2
--R        2n  + 3n  + n
--R   (2)  -------------
--R              6
--R                                          Type: Fraction Polynomial Integer
--E 2

--S 3 of 5
sb := y = 1/2..3/2
--R
--R
--R            1    3
--R   (3)  y= (-)..(-)
--R            2    2
--R                                       Type: SegmentBinding Fraction Integer
--E 3

--S 4 of 5
variable(sb)
--R
--R
--R   (4)  y
--R                                                              Type: Symbol
--E 4

--S 5 of 5
segment(sb)
--R
--R
--R         1    3
--R   (5)  (-)..(-)
--R         2    2
--R                                          Type: Segment Fraction Integer
--E 5
)spool
)lisp (bye)
```

———-

— SegmentBinding.help —

```
====================================================================
SegmentBinding examples
```

```
================================================================

The SegmentBinding type is used to indicate a range for a named symbol.

First give the symbol, then an = and finally a segment of values.

  x = a..b
    x= a..b
                              Type: SegmentBinding Symbol

This is used to provide a convenient syntax for arguments to certain
operations.

  sum(i**2, i = 0..n)
      3     2
    2n  + 3n  + n
    -------------
          6
                              Type: Fraction Polynomial Integer

  draw(x**2, x = -2..2)
    TwoDimensionalViewport: "x*x"
                              Type: TwoDimensionalViewport


The left-hand side must be of type Symbol but the right-hand side can
be a segment over any type.

  sb := y = 1/2..3/2
        1    3
    y= (-)..(-)
        2    2
                              Type: SegmentBinding Fraction Integer

The left- and right-hand sides can be obtained using the variable and
segment operations.


  variable(sb)
    y
                              Type: Symbol

  segment(sb)
     1    3
    (-)..(-)
     2    2
                              Type: Segment Fraction Integer

See Also:
o )help Segment
o )help UniversalSegment
```

```
o )show SegmentBinding
```

20.3.1 SegmentBinding (SEGBIND)



See

⇒ "Segment" (SEG) 20.2.1 on page 2325
⇒ "UniversalSegment" (UNISEG) 22.11.1 on page 2863

Exports:

coerce	equation	hash	latex	segment
variable	?=?	?~=?		

— domain SEGBIND SegmentBinding —

```
)abbrev domain SEGBIND SegmentBinding
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains: Equation, Segment, Symbol
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
++ This domain is used to provide the function argument syntax \spad{v=a..b}.
++ This is used, for example, by the top-level \spadfun{draw} functions.

SegmentBinding(S:Type): Type with
  equation: (Symbol, Segment S) -> %
      ++ equation(v,a..b) creates a segment binding value with variable
```

```
      ++ \spad{v} and segment \spad{a..b}.  Note that the interpreter parses
      ++ \spad{v=a..b} to this form.
  variable: % -> Symbol
      ++ variable(segb) returns the variable from the left hand side of
      ++ the \spadtype{SegmentBinding}.  For example, if \spad{segb} is
      ++ \spad{v=a..b}, then \spad{variable(segb)} returns \spad{v}.
  segment : % -> Segment S
      ++ segment(segb) returns the segment from the right hand side of
      ++ the \spadtype{SegmentBinding}.  For example, if \spad{segb} is
      ++ \spad{v=a..b}, then \spad{segment(segb)} returns \spad{a..b}.

  if S has SetCategory then SetCategory
 == add
  Rep := Record(var:Symbol, seg:Segment S)
  equation(x,s) == [x, s]
  variable b    == b.var
  segment b     == b.seg

  if S has SetCategory then

     b1 = b2       == variable b1 = variable b2 and segment b1 = segment b2

     coerce(b:%):OutputForm ==
       variable(b)::OutputForm = segment(b)::OutputForm
```

———-

— SEGBIND.dotabb —

```
"SEGBIND" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SEGBIND"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SEGBIND" -> "ALIST"
```

———-

20.4 domain SET Set

— Set.input —

```
)set break resume
)sys rm -f Set.output
)spool Set.output
)set message test on
)set message auto off
```

```
)clear all
--S 1 of 20
s := set [x**2-1, y**2-1, z**2-1]
--R
--R
--R          2      2      2
--R   (1)  {x  - 1,y  - 1,z  - 1}
--R                                                Type: Set(Polynomial(Integer))
--E 1

--S 2 of 20
t := set [x**i - i+1 for i in 2..10 | prime? i]
--R
--R
--R          2      3      5      7
--R   (2)  {x  - 1,x  - 2,x  - 4,x  - 6}
--R                                                Type: Set(Polynomial(Integer))
--E 2

--S 3 of 20
i := intersect(s,t)
--R
--R
--R          2
--R   (3)  {x  - 1}
--R                                                Type: Set(Polynomial(Integer))
--E 3

--S 4 of 20
u := union(s,t)
--R
--R
--R          2      3      5      7      2      2
--R   (4)  {x  - 1,x  - 2,x  - 4,x  - 6,y  - 1,z  - 1}
--R                                                Type: Set(Polynomial(Integer))
--E 4

--S 5 of 20
difference(s,t)
--R
--R
--R          2      2
--R   (5)  {y  - 1,z  - 1}
--R                                                Type: Set(Polynomial(Integer))
--E 5

--S 6 of 20
symmetricDifference(s,t)
--R
--R
```

```
--R          3      5      7      2      2
--R   (6)  {x  - 2,x  - 4,x  - 6,y  - 1,z  - 1}
--R                                                Type: Set(Polynomial(Integer))
--E 6

--S 7 of 20
member?(y, s)
--R
--R
--R   (7)  false
--R                                                                   Type: Boolean
--E 7

--S 8 of 20
member?((y+1)*(y-1), s)
--R
--R
--R   (8)  true
--R                                                                   Type: Boolean
--E 8

--S 9 of 20
subset?(i, s)
--R
--R
--R   (9)  true
--R                                                                   Type: Boolean
--E 9

--S 10 of 20
subset?(u, s)
--R
--R
--R   (10)  false
--R                                                                   Type: Boolean
--E 10

--S 11 of 20
gs := set [g for i in 1..11 | primitive?(g := i::PF 11)]
--R
--R
--R   (11)  {2,6,7,8}
--R                                                  Type: Set(PrimeField(11))
--E 11

--S 12 of 20
complement gs
--R
--R
--R   (12)  {1,3,4,5,9,10,0}
```

```
--R                                                  Type: Set(PrimeField(11))
--E 12

--S 13 of 20
a := set [i**2 for i in 1..5]
--R
--R
--R   (13)  {1,4,9,16,25}
--R                                                Type: Set(PositiveInteger)
--E 13

--S 14 of 20
insert!(32, a)
--R
--R
--R   (14)  {1,4,9,16,25,32}
--R                                                Type: Set(PositiveInteger)
--E 14

--S 15 of 20
remove!(25, a)
--R
--R
--R   (15)  {1,4,9,16,32}
--R                                                Type: Set(PositiveInteger)
--E 15

--S 16 of 20
a
--R
--R
--R   (16)  {1,4,9,16,32}
--R                                                Type: Set(PositiveInteger)
--E 16

--S 17 of 20
b := b0 := set [i**2 for i in 1..5]
--R
--R
--R   (17)  {1,4,9,16,25}
--R                                                Type: Set(PositiveInteger)
--E 17

--S 18 of 20
b := union(b, {32})
--R
--R
--R   (18)  {1,4,9,16,25,32}
--R                                                Type: Set(PositiveInteger)
--E 18
```

```
--S 19 of 20
b := difference(b, {25})
--R
--R
--R   (19)  {1,4,9,16,32}
--R                                                  Type: Set(PositiveInteger)
--E 19

--S 20 of 20
b0
--R
--R
--R   (20)  {1,4,9,16,25}
--R                                                  Type: Set(PositiveInteger)
--E 20
)spool
)lisp (bye)
```

———-

— Set.help —

```
====================================================================
Set examples
====================================================================

The Set domain allows one to represent explicit finite sets of values.
These are similar to lists, but duplicate elements are not allowed.

Sets can be created by giving a fixed set of values ...

  s := set [x**2-1, y**2-1, z**2-1]
      2      2      2
    {x  - 1,y  - 1,z  - 1}
                          Type: Set Polynomial Integer

or by using a collect form, just as for lists.  In either case, the
set is formed from a finite collection of values.

  t := set [x**i - i+1 for i in 2..10 | prime? i]
      2      3      5      7
    {x  - 1,x  - 2,x  - 4,x  - 6}
                          Type: Set Polynomial Integer

The basic operations on sets are intersect, union, difference, and
symmetricDifference.

  i := intersect(s,t)
```

```
     2
   {x  - 1}
                          Type: Set Polynomial Integer

  u := union(s,t)
     2      3      5      7      2      2
   {x  - 1,x  - 2,x  - 4,x  - 6,y  - 1,z  - 1}
                          Type: Set Polynomial Integer
```

The set difference(s,t) contains those members of s which are not in t.

```
  difference(s,t)
     2      2
   {y  - 1,z  - 1}
                          Type: Set Polynomial Integer
```

The set symmetricDifference(s,t) contains those elements which are in s or t but not in both.

```
  symmetricDifference(s,t)
     3      5      7      2      2
   {x  - 2,x  - 4,x  - 6,y  - 1,z  - 1}
                          Type: Set Polynomial Integer
```

Set membership is tested using the member? operation.

```
  member?(y, s)
    false
                          Type: Boolean

  member?((y+1)*(y-1), s)
    true
                          Type: Boolean
```

The subset? function determines whether one set is a subset of another.

```
  subset?(i, s)
    true
                          Type: Boolean

  subset?(u, s)
    false
                          Type: Boolean
```

When the base type is finite, the absolute complement of a set is defined. This finds the set of all multiplicative generators of PrimeField 11---the integers mod 11.

```
  gs := set [g for i in 1..11 | primitive?(g := i::PF 11)]
    {2,6,7,8}
```

```
                          Type: Set PrimeField 11
```

The following values are not generators.

```
  complement gs
    {1,3,4,5,9,10,0}
                          Type: Set PrimeField 11
```

Often the members of a set are computed individually; in addition,
values can be inserted or removed from a set over the course of a
computation.

There are two ways to do this:

```
  a := set [i**2 for i in 1..5]
    {1,4,9,16,25}
                          Type: Set PositiveInteger
```

One is to view a set as a data structure and to apply updating operations.

```
  insert!(32, a)
    {1,4,9,16,25,32}
                          Type: Set PositiveInteger

  remove!(25, a)
    {1,4,9,16,32}
                          Type: Set PositiveInteger

  a
    {1,4,9,16,32}
                          Type: Set PositiveInteger
```

The other way is to view a set as a mathematical entity and to
create new sets from old.

```
  b := b0 := set [i**2 for i in 1..5]
    {1,4,9,16,25}
                          Type: Set PositiveInteger


  b := union(b, {32})
    {1,4,9,16,25,32}
                          Type: Set PositiveInteger

  b := difference(b, {25})
    {1,4,9,16,32}
                          Type: Set PositiveInteger

  b0
    {1,4,9,16,25}
                          Type: Set PositiveInteger
```

```
See Also:
o )help List
o )show Set
```

20.4.1 Set (SET)



Exports:

any?	bag	brace	cardinality	coerce
complement	construct	convert	copy	count
dictionary	difference	empty	empty?	eq?
eval	every?	extract!	find	hash
index	insert!	inspect	intersect	latex
less?	lookup	map	map!	max
member?	members	min	more?	parts
random	reduce	remove	remove!	removeDuplicates
sample	select	select!	set	size
size?	subset?	symmetricDifference	union	universe
#?	?~=?	?<?	?=?	

— domain SET Set —

```
)abbrev domain SET Set
++ Author: Michael Monagan; revised by Richard Jenks
++ Date Created: August 87 through August 88
++ Date Last Updated: May 1991
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
```

```
++ References:
++ Description:
++ A set over a domain D models the usual mathematical notion of a finite set
++ of elements from D.
++ Sets are unordered collections of distinct elements
++ (that is, order and duplication does not matter).
++ The notation \spad{set [a,b,c]} can be used to create
++ a set and the usual operations such as union and intersection are available
++ to form new sets.
++ In our implementation, \Language{} maintains the entries in
++ sorted order.  Specifically, the parts function returns the entries
++ as a list in ascending order and
++ the extract operation returns the maximum entry.
++ Given two sets s and t where \spad{#s = m} and \spad{#t = n},
++ the complexity of\br
++ \tab{5}\spad{s = t} is \spad{O(min(n,m))}\br
++ \tab{5}\spad{s < t} is \spad{O(max(n,m))}\br
++ \tab{5}\spad{union(s,t)}, \spad{intersect(s,t)}, \spad{minus(s,t)},\br
++ \tab{10 \spad{symmetricDifference(s,t)} is \spad{O(max(n,m))}\br
++ \tab{5}\spad{member(x,t)} is \spad{O(n log n)}\br
++ \tab{5}\spad{insert(x,t)} and \spad{remove(x,t)} is \spad{O(n)}

Set(S:SetCategory): FiniteSetAggregate S == add
   Rep := FlexibleArray(S)
   # s       == _#$Rep s
   brace()   == empty()
   set()     == empty()
   empty()   == empty()$Rep
   copy s    == copy(s)$Rep
   parts s   == parts(s)$Rep
   inspect s == (empty? s => error "Empty set"; s(maxIndex s))

   extract_! s ==
     x := inspect s
     delete_!(s, maxIndex s)
     x

   find(f, s) == find(f, s)$Rep

   map(f, s) == map_!(f,copy s)

   map_!(f,s) ==
     map_!(f,s)$Rep
     removeDuplicates_! s

   reduce(f, s) == reduce(f, s)$Rep

   reduce(f, s, x) == reduce(f, s, x)$Rep

   reduce(f, s, x, y) == reduce(f, s, x, y)$Rep
```

```
if S has ConvertibleTo InputForm then
  convert(x:%):InputForm ==
     convert [convert("set"::Symbol)@InputForm,
                       convert(parts x)@InputForm]

if S has OrderedSet then
  s = t == s =$Rep t
  max s == inspect s
  min s == (empty? s => error "Empty set"; s(minIndex s))

  construct l ==
    zero?(n := #l) => empty()
    a := new(n, first l)
    for i in minIndex(a).. for x in l repeat a.i := x
    removeDuplicates_! sort_! a

  insert_!(x, s) ==
    n := inc maxIndex s
    k := minIndex s
    while k < n and x > s.k repeat k := inc k
    k < n and s.k = x => s
    insert_!(x, s, k)

  member?(x, s) == -- binary search
    empty? s => false
    t := maxIndex s
    b := minIndex s
    while b < t repeat
      m := (b+t) quo 2
      if x > s.m then b := m+1 else t := m
    x = s.t

  remove_!(x:S, s:%) ==
    n := inc maxIndex s
    k := minIndex s
    while k < n and x > s.k repeat k := inc k
    k < n and x = s.k => delete_!(s, k)
    s

  -- the set operations are implemented as variations of merging
  intersect(s, t) ==
    m := maxIndex s
    n := maxIndex t
    i := minIndex s
    j := minIndex t
    r := empty()
    while i <= m and j <= n repeat
      s.i = t.j => (concat_!(r, s.i); i := i+1; j := j+1)
      if s.i < t.j then i := i+1 else j := j+1
```

```
    r

  difference(s:%, t:%) ==
    m := maxIndex s
    n := maxIndex t
    i := minIndex s
    j := minIndex t
    r := empty()
    while i <= m and j <= n repeat
      s.i = t.j => (i := i+1; j := j+1)
      s.i < t.j => (concat_!(r, s.i); i := i+1)
      j := j+1
    while i <= m repeat (concat_!(r, s.i); i := i+1)
    r

  symmetricDifference(s, t) ==
    m := maxIndex s
    n := maxIndex t
    i := minIndex s
    j := minIndex t
    r := empty()
    while i <= m and j <= n repeat
      s.i < t.j => (concat_!(r, s.i); i := i+1)
      s.i > t.j => (concat_!(r, t.j); j := j+1)
      i := i+1; j := j+1
    while i <= m repeat (concat_!(r, s.i); i := i+1)
    while j <= n repeat (concat_!(r, t.j); j := j+1)
    r

  subset?(s, t) ==
    m := maxIndex s
    n := maxIndex t
    m > n => false
    i := minIndex s
    j := minIndex t
    while i <= m and j <= n repeat
      s.i = t.j => (i := i+1; j := j+1)
      s.i > t.j => j := j+1
      return false
    i > m

  union(s:%, t:%) ==
    m := maxIndex s
    n := maxIndex t
    i := minIndex s
    j := minIndex t
    r := empty()
    while i <= m and j <= n repeat
      s.i = t.j => (concat_!(r, s.i); i := i+1; j := j+1)
      s.i < t.j => (concat_!(r, s.i); i := i+1)
```

```
        (concat_!(r, t.j); j := j+1)
      while i <= m repeat (concat_!(r, s.i); i := i+1)
      while j <= n repeat (concat_!(r, t.j); j := j+1)
      r

    else
      insert_!(x, s) ==
        for k in minIndex s .. maxIndex s repeat
          s.k = x => return s
        insert_!(x, s, inc maxIndex s)

      remove_!(x:S, s:%) ==
        n := inc maxIndex s
        k := minIndex s
        while k < n repeat
          x = s.k => return delete_!(s, k)
          k := inc k
        s
```

———-

— **SET.dotabb** —

```
"SET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SET"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SET" -> "ALIST"
```

———-

20.5 domain SETMN SetOfMIntegersInOneToN

— **SetOfMIntegersInOneToN.input** —

```
)set break resume
)sys rm -f SetOfMIntegersInOneToN.output
)spool SetOfMIntegersInOneToN.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SetOfMIntegersInOneToN
--R
--R SetOfMIntegersInOneToN(m: PositiveInteger,n: PositiveInteger)  is a domain constructor
```

```
--R Abbreviation for SetOfMIntegersInOneToN is SETMN
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SETMN
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R enumerate : () -> Vector(%)           hash : % -> SingleInteger
--R index : PositiveInteger -> %          latex : % -> String
--R lookup : % -> PositiveInteger         random : () -> %
--R size : () -> NonNegativeInteger       ?~=? : (%,%) -> Boolean
--R delta : (%,PositiveInteger,PositiveInteger) -> NonNegativeInteger
--R elements : % -> List(PositiveInteger)
--R incrementKthElement : (%,PositiveInteger) -> Union(%,"failed")
--R member? : (PositiveInteger,%) -> Boolean
--R replaceKthElement : (%,PositiveInteger,PositiveInteger) -> Union(%,"failed")
--R setOfMinN : List(PositiveInteger) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— SetOfMIntegersInOneToN.help —

```
=====================================================================
SetOfMIntegersInOneToN examples
=====================================================================

See Also:
o )show SetOfMIntegersInOneToN
```

———-

20.5.1 SetOfMIntegersInOneToN (SETMN)



Exports:

coerce	delta	elements	enumerate	hash
incrementKthElement	index	latex	lookup	member?
random	replaceKthElement	setOfMinN	size	?=?
?~=?				

— domain SETMN SetOfMIntegersInOneToN —

```
)abbrev domain SETMN SetOfMIntegersInOneToN
++ Author: Manuel Bronstein
++ Date Created: 10 January 1994
++ Date Last Updated: 10 January 1994
++ Description:
++ \spadtype{SetOfMIntegersInOneToN} implements the subsets of M integers
++ in the interval \spad{[1..n]}

SetOfMIntegersInOneToN(m, n): Exports == Implementation where
  PI ==> PositiveInteger
  N  ==> NonNegativeInteger
  U  ==> Union(%, "failed")
  n,m: PI

  Exports ==> Finite with
    incrementKthElement: (%, PI) -> U
      ++ incrementKthElement(S,k) increments the k^{th} element of S,
      ++ and returns "failed" if the result is not a set of M integers
      ++ in \spad{1..n} any more.
    replaceKthElement:   (%, PI, PI) -> U
      ++ replaceKthElement(S,k,p) replaces the k^{th} element of S by p,
      ++ and returns "failed" if the result is not a set of M integers
      ++ in \spad{1..n} any more.
    elements: % -> List PI
      ++ elements(S) returns the list of the elements of S in increasing order.
    setOfMinN: List PI -> %
      ++ setOfMinN([a_1,...,a_m]) returns the set {a_1,...,a_m}.
```

```
      ++ Error if {a_1,...,a_m} is not a set of M integers in \spad{1..n}.
    enumerate: () -> Vector %
      ++ enumerate() returns a vector of all the sets of M integers in
      ++ \spad{1..n}.
    member?:   (PI, %) -> Boolean
      ++ member?(p, s) returns true is p is in s, false otherwise.
    delta: (%, PI, PI) -> N
      ++ delta(S,k,p) returns the number of elements of S which are strictly
      ++ between p and the k^{th} element of S.

  Implementation ==> add
    Rep := Record(bits:Bits, pos:N)

    reallyEnumerate: () -> Vector %
    enum: (N, N, PI) -> List Bits

    all:Reference Vector % := ref empty()
    sz:Reference N := ref 0

    s1 = s2                == s1.bits =$Bits s2.bits
    coerce(s:%):OutputForm == brace [i::OutputForm for i in elements s]
    random()               == index((1 + (random()$Integer rem size()))::PI)
    reallyEnumerate()      == [[b, i] for b in enum(m, n, n) for i in 1..]
    member?(p, s)          == s.bits.p

    enumerate() ==
      if empty? all() then all() := reallyEnumerate()
      all()

-- enumerates the sets of p integers in 1..q, returns them as sets in 1..n
-- must have p <= q
    enum(p, q, n) ==
      zero? p or zero? q => empty()
      p = q =>
        b := new(n, false)$Bits
        for i in 1..p repeat b.i := true
        [b]
      q1 := (q - 1)::N
      l := enum((p - 1)::N, q1, n)
      if empty? l then l := [new(n, false)$Bits]
      for s in l repeat s.q := true
      concat_!(enum(p, q1, n), l)

    size() ==
      if zero? sz() then
         sz() := binomial(n, m)$IntegerCombinatoricFunctions(Integer) :: N
      sz()

    lookup s ==
      if empty? all() then all() := reallyEnumerate()
```

```
    if zero?(s.pos) then s.pos := position(s, all()) :: N
    s.pos :: PI

  index p ==
    p > size() => error "index: argument too large"
    if empty? all() then all() := reallyEnumerate()
    all().p

  setOfMinN l ==
    s := new(n, false)$Bits
    count:N := 0
    for i in l repeat
      count := count + 1
      count > m or zero? i or i > n or s.i =>
        error "setOfMinN: improper set of integers"
      s.i := true
    count < m => error "setOfMinN: improper set of integers"
    [s, 0]

  elements s ==
    b := s.bits
    l:List PI := empty()
    found:N := 0
    i:PI := 1
    while found < m repeat
        if b.i then
            l := concat(i, l)
            found := found + 1
        i := i + 1
    reverse_! l

  incrementKthElement(s, k) ==
    b := s.bits
    found:N := 0
    i:N := 1
    while found < k repeat
        if b.i then found := found + 1
        i := i + 1
    i > n or b.i => "failed"
    newb := copy b
    newb.i := true
    newb.((i-1)::N) := false
    [newb, 0]

  delta(s, k, p) ==
    b := s.bits
    count:N := found:N := 0
    i:PI := 1
    while found < k repeat
        if b.i then
```

```
            found := found + 1
            if i > p and found < k then count := count + 1
          i := i + 1
      count

    replaceKthElement(s, k, p) ==
      b := s.bits
      found:N := 0
      i:PI := 1
      while found < k repeat
          if b.i then found := found + 1
          if found < k then i := i + 1
      b.p and i ^= p => "failed"
      newb := copy b
      newb.p := true
      newb.i := false
      [newb, (i = p => s.pos; 0)]
```

———-

— **SETMN.dotabb** —

```
"SETMN" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SETMN"]
"IVECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=IVECTOR"]
"SETMN" -> "IVECTOR"
```

———-

20.6 domain SDPOL SequentialDifferentialPolynomial

— **SequentialDifferentialPolynomial.input** —

```
)set break resume
)sys rm -f SequentialDifferentialPolynomial.output
)spool SequentialDifferentialPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SequentialDifferentialPolynomial
--R SequentialDifferentialPolynomial R: Ring  is a domain constructor
--R Abbreviation for SequentialDifferentialPolynomial is SDPOL
--R This constructor is not exposed in this frame.
```

```
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SDPOL
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> % if R has DIFRING
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficients : % -> List R
--R coerce : Symbol -> %                  coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R eval : (%,List %,List %) -> %         eval : (%,%,%) -> %
--R eval : (%,Equation %) -> %            eval : (%,List Equation %) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             initial : % -> %
--R isobaric? : % -> Boolean              latex : % -> String
--R leadingCoefficient : % -> R           leadingMonomial : % -> %
--R map : ((R -> R),%) -> %               monomial? : % -> Boolean
--R monomials : % -> List %               one? : % -> Boolean
--R order : % -> NonNegativeInteger       primitiveMonomials : % -> List %
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R retract : % -> Symbol                 retract : % -> R
--R sample : () -> %                      separant : % -> %
--R weight : % -> NonNegativeInteger      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction Integer,%) -> % if R has ALGEBRA FRAC INT
--R ?*? : (%,Fraction Integer) -> % if R has ALGEBRA FRAC INT
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List Symbol,List NonNegativeInteger) -> % if R has PDRING SYMBOL
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING SYMBOL
--R D : (%,List Symbol) -> % if R has PDRING SYMBOL
--R D : (%,Symbol) -> % if R has PDRING SYMBOL
--R D : (%,NonNegativeInteger) -> % if R has DIFRING
--R D : (%,List SequentialDifferentialVariable Symbol,List NonNegativeInteger) -> %
--R D : (%,SequentialDifferentialVariable Symbol,NonNegativeInteger) -> %
--R D : (%,List SequentialDifferentialVariable Symbol) -> %
--R D : (%,SequentialDifferentialVariable Symbol) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
```

```
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List SequentialDifferentialVariable Symbol,List NonNegativeInteger) -> %
--R coefficient : (%,SequentialDifferentialVariable Symbol,NonNegativeInteger) -> %
--R coefficient : (%,IndexedExponents SequentialDifferentialVariable Symbol) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction Integer -> % if R has ALGEBRA FRAC INT or R has RETRACT FRAC INT
--R coerce : SparseMultivariatePolynomial(R,Symbol) -> %
--R coerce : SequentialDifferentialVariable Symbol -> %
--R conditionP : Matrix % -> Union(Vector %,"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SequentialDifferentialVariable Symbol) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SequentialDifferentialVariable Symbol has KONVERT INFORM and R has KONVERT I
--R convert : % -> Pattern Integer if SequentialDifferentialVariable Symbol has KONVERT PATTERN INT and R ha
--R convert : % -> Pattern Float if SequentialDifferentialVariable Symbol has KONVERT PATTERN FLOAT and R ha
--R degree : (%,Symbol) -> NonNegativeInteger
--R degree : (%,List SequentialDifferentialVariable Symbol) -> List NonNegativeInteger
--R degree : (%,SequentialDifferentialVariable Symbol) -> NonNegativeInteger
--R degree : % -> IndexedExponents SequentialDifferentialVariable Symbol
--R differentialVariables : % -> List Symbol
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List Symbol,List NonNegativeInteger) -> % if R has PDRING SYMBOL
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING SYMBOL
--R differentiate : (%,List Symbol) -> % if R has PDRING SYMBOL
--R differentiate : (%,Symbol) -> % if R has PDRING SYMBOL
--R differentiate : (%,NonNegativeInteger) -> % if R has DIFRING
--R differentiate : % -> % if R has DIFRING
--R differentiate : (%,List SequentialDifferentialVariable Symbol,List NonNegativeInteger) -> %
--R differentiate : (%,SequentialDifferentialVariable Symbol,NonNegativeInteger) -> %
--R differentiate : (%,List SequentialDifferentialVariable Symbol) -> %
--R differentiate : (%,SequentialDifferentialVariable Symbol) -> %
--R discriminant : (%,SequentialDifferentialVariable Symbol) -> % if R has COMRING
--R eval : (%,List Symbol,List R) -> % if R has DIFRING
--R eval : (%,Symbol,R) -> % if R has DIFRING
--R eval : (%,List Symbol,List %) -> % if R has DIFRING
--R eval : (%,Symbol,%) -> % if R has DIFRING
--R eval : (%,List SequentialDifferentialVariable Symbol,List %) -> %
--R eval : (%,SequentialDifferentialVariable Symbol,%) -> %
--R eval : (%,List SequentialDifferentialVariable Symbol,List R) -> %
--R eval : (%,SequentialDifferentialVariable Symbol,R) -> %
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R factor : % -> Factored % if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial % if R has PFECAT
--R factorSquareFreePolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial % if R
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List % -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> SparseUnivariatePolynomia
--R isExpt : % -> Union(Record(var: SequentialDifferentialVariable Symbol,exponent: NonNegativeInteger),"fa
--R isPlus : % -> Union(List %,"failed")
```

```
--R isTimes : % -> Union(List %,"failed")
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List % -> % if R has GCDDOM
--R leader : % -> SequentialDifferentialVariable Symbol
--R mainVariable : % -> Union(SequentialDifferentialVariable Symbol,"failed")
--R makeVariable : % -> (NonNegativeInteger -> %) if R has DIFRING
--R makeVariable : Symbol -> (NonNegativeInteger -> %)
--R mapExponents : ((IndexedExponents SequentialDifferentialVariable Symbol -> IndexedExponents
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List SequentialDifferentialVariable Symbol) -> List NonNegativeInteger
--R minimumDegree : (%,SequentialDifferentialVariable Symbol) -> NonNegativeInteger
--R minimumDegree : % -> IndexedExponents SequentialDifferentialVariable Symbol
--R monicDivide : (%,%,SequentialDifferentialVariable Symbol) -> Record(quotient: %,remainder: %
--R monomial : (%,List SequentialDifferentialVariable Symbol,List NonNegativeInteger) -> %
--R monomial : (%,SequentialDifferentialVariable Symbol,NonNegativeInteger) -> %
--R monomial : (R,IndexedExponents SequentialDifferentialVariable Symbol) -> %
--R multivariate : (SparseUnivariatePolynomial %,SequentialDifferentialVariable Symbol) -> %
--R multivariate : (SparseUnivariatePolynomial R,SequentialDifferentialVariable Symbol) -> %
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,Symbol) -> NonNegativeInteger
--R patternMatch : (%,Pattern Integer,PatternMatchResult(Integer,%)) -> PatternMatchResult(Integ
--R patternMatch : (%,Pattern Float,PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pomopo! : (%,R,IndexedExponents SequentialDifferentialVariable Symbol,%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitivePart : (%,SequentialDifferentialVariable Symbol) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R reducedSystem : Matrix % -> Matrix R
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix R,vec: Vector R)
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix Integer,vec: Vector Integer) if R
--R reducedSystem : Matrix % -> Matrix Integer if R has LINEXP INT
--R resultant : (%,%,SequentialDifferentialVariable Symbol) -> % if R has COMRING
--R retract : % -> SparseMultivariatePolynomial(R,Symbol)
--R retract : % -> SequentialDifferentialVariable Symbol
--R retract : % -> Integer if R has RETRACT INT
--R retract : % -> Fraction Integer if R has RETRACT FRAC INT
--R retractIfCan : % -> Union(SparseMultivariatePolynomial(R,Symbol),"failed")
--R retractIfCan : % -> Union(Symbol,"failed")
--R retractIfCan : % -> Union(SequentialDifferentialVariable Symbol,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT INT
--R retractIfCan : % -> Union(Fraction Integer,"failed") if R has RETRACT FRAC INT
--R retractIfCan : % -> Union(R,"failed")
--R solveLinearPolynomialEquation : (List SparseUnivariatePolynomial %,SparseUnivariatePolynomia
--R squareFree : % -> Factored % if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial %
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List SequentialDifferentialVariable Symbol) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
```

```
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial R
--R univariate : (%,SequentialDifferentialVariable Symbol) -> SparseUnivariatePolynomial %
--R variables : % -> List SequentialDifferentialVariable Symbol
--R weight : (%,Symbol) -> NonNegativeInteger
--R weights : (%,Symbol) -> List NonNegativeInteger
--R weights : % -> List NonNegativeInteger
--R
--E 1

)spool
)lisp (bye)
```

———-


— **SequentialDifferentialPolynomial.help** —

```
=====================================================================
SequentialDifferentialPolynomial examples
=====================================================================

See Also:
o )show SequentialDifferentialPolynomial
```

———-

20.6.1 SequentialDifferentialPolynomial (SDPOL)



See

⇒ “OrderlyDifferentialVariable” (ODVAR) 16.17.1 on page 1821
⇒ “SequentialDifferentialVariable” (SDVAR) 20.7.1 on page 2357
⇒ “DifferentialSparseMultivariatePolynomial” (DSMP) 5.8.1 on page 528
⇒ “OrderlyDifferentialPolynomial” (ODPOL) 16.16.1 on page 1817

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	convert
D	degree	differentialVariables
differentiate	discriminant	eval
exquo	factor	factorPolynomial
factorSquareFreePolynomial	gcd	gcdPolynomial
ground	ground?	hash
initial	isExpt	isobaric?
isPlus	isTimes	latex
lcm	leader	leadingCoefficient
leadingMonomial	mainVariable	makeVariable
map	mapExponents	max
min	minimumDegree	monicDivide
monomial	monomial?	monomials
multivariate	numberOfMonomials	one?
order	patternMatch	pomopo!
prime?	primitiveMonomials	primitivePart
recip	reducedSystem	reductum
resultant	retract	retractIfCan
sample	separant	solveLinearPolynomialEquation
squareFree	squareFreePart	squareFreePolynomial
subtractIfCan	totalDegree	unit?
unitCanonical	unitNormal	univariate
variables	weight	weights
zero?	?^?	?*?
?**?	?+?	?-?
-?	?=?	?~=?
?/?	?<?	?<=?
?>?	?>=?	

— domain SDPOL SequentialDifferentialPolynomial —

```
)abbrev domain SDPOL SequentialDifferentialPolynomial
++ Author:  William Sit
++ Date Created: 24 September, 1991
++ Date Last Updated: 7 February, 1992
++ Basic Operations:DifferentialPolynomialCategory
++ Related Constructors: DifferentialSparseMultivariatePolynomial
++ See Also:
++ AMS Classifications:12H05
++ Keywords: differential indeterminates, ranking, differential polynomials,
++           order, weight, leader, separant, initial, isobaric
++ References:Kolchin, E.R. "Differential Algebra and Algebraic Groups"
++   (Academic Press, 1973).
```

```
++ Description:
++ \spadtype{SequentialDifferentialPolynomial} implements
++ an ordinary differential polynomial ring in arbitrary number
++ of differential indeterminates, with coefficients in a
++ ring.  The ranking on the differential indeterminate is sequential.

SequentialDifferentialPolynomial(R):
     Exports == Implementation where
  R: Ring
  S  ==> Symbol
  V  ==> SequentialDifferentialVariable S
  E   ==> IndexedExponents(V)
  SMP ==> SparseMultivariatePolynomial(R, S)
  Exports ==> Join(DifferentialPolynomialCategory(R,S,V,E),
                   RetractableTo SMP)

  Implementation ==> DifferentialSparseMultivariatePolynomial(R,S,V)
```

———-

— SDPOL.dotabb —

```
"SDPOL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SDPOL"]
"DPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DPOLCAT"]
"SDPOL" -> "DPOLCAT"
```

———-

20.7 domain SDVAR SequentialDifferentialVariable

— SequentialDifferentialVariable.input —

```
)set break resume
)sys rm -f SequentialDifferentialVariable.output
)spool SequentialDifferentialVariable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SequentialDifferentialVariable
--R
--R SequentialDifferentialPolynomial(R: Ring)  is a domain constructor
--R Abbreviation for SequentialDifferentialPolynomial is SDPOL
```

```
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SDPOL
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> % if R has DIFRING
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficients : % -> List(R)
--R coerce : Symbol -> %                  coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R eval : (%,%,%) -> %                   eval : (%,Equation(%)) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             initial : % -> %
--R isobaric? : % -> Boolean              latex : % -> String
--R leadingCoefficient : % -> R           leadingMonomial : % -> %
--R map : ((R -> R),%) -> %               monomial? : % -> Boolean
--R monomials : % -> List(%)              one? : % -> Boolean
--R order : % -> NonNegativeInteger       recip : % -> Union(%,"failed")
--R reductum : % -> %                     retract : % -> Symbol
--R retract : % -> R                      sample : () -> %
--R separant : % -> %                     weight : % -> NonNegativeInteger
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if R has DIFRING
--R D : (%,List(SequentialDifferentialVariable(Symbol)),List(NonNegativeInteger)) -> %
--R D : (%,SequentialDifferentialVariable(Symbol),NonNegativeInteger) -> %
--R D : (%,List(SequentialDifferentialVariable(Symbol))) -> %
--R D : (%,SequentialDifferentialVariable(Symbol)) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
```

```
--R coefficient : (%,List(SequentialDifferentialVariable(Symbol)),List(NonNegativeInteger)) -> %
--R coefficient : (%,SequentialDifferentialVariable(Symbol),NonNegativeInteger) -> %
--R coefficient : (%,IndexedExponents(SequentialDifferentialVariable(Symbol))) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : SparseMultivariatePolynomial(R,Symbol) -> %
--R coerce : SequentialDifferentialVariable(Symbol) -> %
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SequentialDifferentialVariable(Symbol)) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SequentialDifferentialVariable(Symbol) has KONVERT(INFORM) and R has KONVERT
--R convert : % -> Pattern(Integer) if SequentialDifferentialVariable(Symbol) has KONVERT(PATTERN(INT)) and
--R convert : % -> Pattern(Float) if SequentialDifferentialVariable(Symbol) has KONVERT(PATTERN(FLOAT)) and
--R degree : (%,Symbol) -> NonNegativeInteger
--R degree : (%,List(SequentialDifferentialVariable(Symbol))) -> List(NonNegativeInteger)
--R degree : (%,SequentialDifferentialVariable(Symbol)) -> NonNegativeInteger
--R degree : % -> IndexedExponents(SequentialDifferentialVariable(Symbol))
--R differentialVariables : % -> List(Symbol)
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if R has DIFRING
--R differentiate : % -> % if R has DIFRING
--R differentiate : (%,List(SequentialDifferentialVariable(Symbol)),List(NonNegativeInteger)) -> %
--R differentiate : (%,SequentialDifferentialVariable(Symbol),NonNegativeInteger) -> %
--R differentiate : (%,List(SequentialDifferentialVariable(Symbol))) -> %
--R differentiate : (%,SequentialDifferentialVariable(Symbol)) -> %
--R discriminant : (%,SequentialDifferentialVariable(Symbol)) -> % if R has COMRING
--R eval : (%,List(Symbol),List(R)) -> % if R has DIFRING
--R eval : (%,Symbol,R) -> % if R has DIFRING
--R eval : (%,List(Symbol),List(%)) -> % if R has DIFRING
--R eval : (%,Symbol,%) -> % if R has DIFRING
--R eval : (%,List(SequentialDifferentialVariable(Symbol)),List(%)) -> %
--R eval : (%,SequentialDifferentialVariable(Symbol),%) -> %
--R eval : (%,List(SequentialDifferentialVariable(Symbol)),List(R)) -> %
--R eval : (%,SequentialDifferentialVariable(Symbol),R) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if R has PFE
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynom
--R isExpt : % -> Union(Record(var: SequentialDifferentialVariable(Symbol),exponent: NonNegativeInteger),"fa
```

```
--R isPlus : % -> Union(List(%),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R leader : % -> SequentialDifferentialVariable(Symbol)
--R mainVariable : % -> Union(SequentialDifferentialVariable(Symbol),"failed")
--R makeVariable : % -> (NonNegativeInteger -> %) if R has DIFRING
--R makeVariable : Symbol -> (NonNegativeInteger -> %)
--R mapExponents : ((IndexedExponents(SequentialDifferentialVariable(Symbol)) -> IndexedExponent
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List(SequentialDifferentialVariable(Symbol))) -> List(NonNegativeInteger)
--R minimumDegree : (%,SequentialDifferentialVariable(Symbol)) -> NonNegativeInteger
--R minimumDegree : % -> IndexedExponents(SequentialDifferentialVariable(Symbol))
--R monicDivide : (%,%,SequentialDifferentialVariable(Symbol)) -> Record(quotient: %,remainder:
--R monomial : (%,List(SequentialDifferentialVariable(Symbol)),List(NonNegativeInteger)) -> %
--R monomial : (%,SequentialDifferentialVariable(Symbol),NonNegativeInteger) -> %
--R monomial : (R,IndexedExponents(SequentialDifferentialVariable(Symbol))) -> %
--R multivariate : (SparseUnivariatePolynomial(%),SequentialDifferentialVariable(Symbol)) -> %
--R multivariate : (SparseUnivariatePolynomial(R),SequentialDifferentialVariable(Symbol)) -> %
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,Symbol) -> NonNegativeInteger
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pomopo! : (%,R,IndexedExponents(SequentialDifferentialVariable(Symbol)),%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,SequentialDifferentialVariable(Symbol)) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R resultant : (%,%,SequentialDifferentialVariable(Symbol)) -> % if R has COMRING
--R retract : % -> SparseMultivariatePolynomial(R,Symbol)
--R retract : % -> SequentialDifferentialVariable(Symbol)
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(SparseMultivariatePolynomial(R,Symbol),"failed")
--R retractIfCan : % -> Union(Symbol,"failed")
--R retractIfCan : % -> Union(SequentialDifferentialVariable(Symbol),"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynom
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List(SequentialDifferentialVariable(Symbol))) -> NonNegativeInteger
```

```
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,SequentialDifferentialVariable(Symbol)) -> SparseUnivariatePolynomial(%)
--R variables : % -> List(SequentialDifferentialVariable(Symbol))
--R weight : (%,Symbol) -> NonNegativeInteger
--R weights : (%,Symbol) -> List(NonNegativeInteger)
--R weights : % -> List(NonNegativeInteger)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **SequentialDifferentialVariable.help** —

```
=====================================================================
SequentialDifferentialVariable examples
=====================================================================

See Also:
o )show SequentialDifferentialVariable
```

———-

20.7.1 SequentialDifferentialVariable (SDVAR)



See

⇒ “OrderlyDifferentialVariable” (ODVAR) 16.17.1 on page 1821
⇒ “DifferentialSparseMultivariatePolynomial” (DSMP) 5.8.1 on page 528

⇒ "OrderlyDifferentialPolynomial" (ODPOL) 16.16.1 on page 1817
⇒ "SequentialDifferentialPolynomial" (SDPOL) 20.6.1 on page 2351

Exports:

coerce	differentiate	hash	latex	makeVariable
max	min	order	retract	retractIfCan
variable	weight	?~=?	?<?	?<=?
?=?	?>?	?>=?		

— domain SDVAR SequentialDifferentialVariable —

```
)abbrev domain SDVAR SequentialDifferentialVariable
++ Author:  William Sit
++ Date Created: 19 July 1990
++ Date Last Updated: 13 September 1991
++ Basic Operations:differentiate, order, variable, <
++ Related Domains: OrderedVariableList,
++                  OrderlyDifferentialVariable.
++ See Also:DifferentialVariableCategory
++ AMS Classifications:12H05
++ Keywords: differential indeterminates, sequential ranking.
++ References:Kolchin, E.R. "Differential Algebra and Algebraic Groups"
++   (Academic Press, 1973).
++ Description:
++ \spadtype{OrderlyDifferentialVariable} adds a commonly used sequential
++ ranking to the set of derivatives of an ordered list of differential
++ indeterminates.  A sequential ranking is a ranking \spadfun{<} of the
++ derivatives with the property that for any derivative v,
++ there are only a finite number of derivatives u with u \spadfun{<} v.
++ This domain belongs to \spadtype{DifferentialVariableCategory}.  It
++ defines \spadfun{weight} to be just \spadfun{order}, and it
++ defines a sequential ranking \spadfun{<} on derivatives u by the
++ lexicographic order on the pair
++ (\spadfun{variable}(u), \spadfun{order}(u)).

SequentialDifferentialVariable(S:OrderedSet):DifferentialVariableCategory(S)
  == add
    Rep := Record(var:S, ord:NonNegativeInteger)
    makeVariable(s,n) == [s, n]
    variable v     == v.var
    order v        == v.ord
    v < u ==
      variable v = variable u => order v < order u
      variable v < variable u
```

———-

— SDVAR.dotabb —

```
"SDVAR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SDVAR"]
"ORDSET" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ORDSET"]
"RETRACT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RETRACT"]
"SDVAR" -> "ORDSET"
"SDVAR" -> "RETRACT"
```

———-

20.8 domain SEX SExpression

— SExpression.input —

```
)set break resume
)sys rm -f SExpression.output
)spool SExpression.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SExpression
--R
--R SExpression  is a domain constructor
--R Abbreviation for SExpression is SEX
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SEX
--R
--R------------------------------ Operations --------------------------------
--R #? : % -> Integer                    ?=? : (%,%) -> Boolean
--R atom? : % -> Boolean                 car : % -> %
--R cdr : % -> %                         coerce : % -> OutputForm
--R convert : OutputForm -> %            convert : DoubleFloat -> %
--R convert : Integer -> %               convert : Symbol -> %
--R convert : String -> %                convert : List(%) -> %
--R destruct : % -> List(%)              ?.? : (%,List(Integer)) -> %
--R ?.? : (%,Integer) -> %               eq : (%,%) -> Boolean
--R expr : % -> OutputForm               float : % -> DoubleFloat
--R float? : % -> Boolean                hash : % -> SingleInteger
--R integer : % -> Integer               integer? : % -> Boolean
--R latex : % -> String                  list? : % -> Boolean
--R null? : % -> Boolean                 pair? : % -> Boolean
--R string : % -> String                 string? : % -> Boolean
--R symbol : % -> Symbol                 symbol? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **SExpression.help** —

```
=====================================================================
SExpression examples
=====================================================================

See Also:
o )show SExpression
```

———-

20.8.1 SExpression (SEX)



See

⇒ “SExpressionOf” (SEXOF) 20.9.1 on page 2362

Exports:

atom?	car	cdr	coerce	convert
destruct	eq	expr	float	float?
hash	integer	integer?	latex	list?
null?	pair?	string	string?	symbol
symbol?	#?	?.?	?=?	?~=?

— **domain SEX SExpression** —

```
)abbrev domain SEX SExpression
++ Author: S.M.Watt
++ Date Created: July 1987
++ Date Last Modified: 23 May 1991
```

```
++ Description:
++ This domain allows the manipulation of the usual Lisp values;

SExpression()
       == SExpressionOf(String, Symbol, Integer, DoubleFloat, OutputForm)
```

———-

— **SEX.dotabb** —

```
"SEX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SEX"]
"STRICAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=STRICAT"]
"SEX" -> "STRICAT"
```

———-

20.9 domain SEXOF SExpressionOf

— **SExpressionOf.input** —

```
)set break resume
)sys rm -f SExpressionOf.output
)spool SExpressionOf.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SExpressionOf
--R
--R SExpressionOf(Str: SetCategory,Sym: SetCategory,Int: SetCategory,Flt: SetCategory,Expr: SetCategory)  is
--R Abbreviation for SExpressionOf is SEXOF
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SEXOF
--R
--R------------------------------ Operations --------------------------------
--R #? : % -> Integer                    ?=? : (%,%) -> Boolean
--R atom? : % -> Boolean                 car : % -> %
--R cdr : % -> %                         coerce : % -> OutputForm
--R convert : Expr -> %                  convert : Flt -> %
--R convert : Int -> %                   convert : Sym -> %
--R convert : Str -> %                   convert : List(%) -> %
--R destruct : % -> List(%)              ?.? : (%,List(Integer)) -> %
--R ?.? : (%,Integer) -> %               eq : (%,%) -> Boolean
```

```
--R expr : % -> Expr                    float : % -> Flt
--R float? : % -> Boolean               hash : % -> SingleInteger
--R integer : % -> Int                  integer? : % -> Boolean
--R latex : % -> String                 list? : % -> Boolean
--R null? : % -> Boolean                pair? : % -> Boolean
--R string : % -> Str                   string? : % -> Boolean
--R symbol : % -> Sym                   symbol? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **SExpressionOf.help** —

```
=====================================================================
SExpressionOf examples
=====================================================================

See Also:
o )show SExpressionOf
```

———-

20.9.1 SExpressionOf (SEXOF)



See

⇒ “SExpression” (SEX) 20.8.1 on page 2360

Exports:

atom?	car	cdr	coerce	convert
destruct	eq	expr	float	float?
hash	integer	integer?	latex	list?
null?	pair?	string	string?	symbol
symbol?	#?	?.?	?=?	?~=?

— domain SEXOF SExpressionOf —

```
)abbrev domain SEXOF SExpressionOf
++ Author: S.M.Watt
++ Date Created: July 1987
++ Date Last Modified: 23 May 1991
++ Description:
++ This domain allows the manipulation of Lisp values over
++ arbitrary atomic types.
-- Allows the names of the atomic types to be chosen.
-- *** Warning *** Although the parameters are declared only to be Sets,
-- *** Warning *** they must have the appropriate representations.

SExpressionOf(Str, Sym, Int, Flt, Expr): Decl == Body where
    Str, Sym, Int, Flt, Expr: SetCategory

    Decl ==> SExpressionCategory(Str, Sym, Int, Flt, Expr)

    Body ==> add
        Rep := Expr

        dotex:OutputForm := INTERN(".")$Lisp

        coerce(b:%):OutputForm ==
            null? b => paren empty()
            atom? b => coerce(b)$Rep
            r := b
            while not atom? r repeat r := cdr r
            l1 := [b1::OutputForm for b1 in (l := destruct b)]
            not null? r =>
              paren blankSeparate concat_!(l1, [dotex, r::OutputForm])
            #l = 2 and (first(l1) = QUOTE)@Boolean => quote first rest l1
            paren blankSeparate l1

        b1 = b2        == EQUAL(b1,b2)$Lisp
        eq(b1, b2)     == EQ(b1,b2)$Lisp

        null? b      == NULL(b)$Lisp
        atom? b      == ATOM(b)$Lisp
        pair? b      == CONSP(b)$Lisp

        list?    b   == CONSP(b)$Lisp or NULL(b)$Lisp
        string?  b   == STRINGP(b)$Lisp
        symbol?  b   == IDENTP(b)$Lisp
```

```
        integer? b   == INTEGERP(b)$Lisp
        float?   b   == RNUMP(b)$Lisp

        destruct b == (list? b    => b pretend List %; error "Non-list")
        string b == (STRINGP(b)$Lisp=> b pretend Str;error "Non-string")
        symbol b == (IDENTP(b)$Lisp => b pretend Sym;error "Non-symbol")
        float   b == (RNUMP(b)$Lisp  => b pretend Flt;error "Non-float")
        integer b == (INTEGERP(b)$Lisp => b pretend Int;error "Non-integer")
        expr    b == b pretend Expr

        convert(l:  List %) == l  pretend %
        convert(st: Str)    == st pretend %
        convert(sy: Sym)    == sy pretend %
        convert(n:  Int)    == n  pretend %
        convert(f:  Flt)    == f  pretend %
        convert(e:  Expr)   == e  pretend %

        car b        == CAR(b)$Lisp
        cdr b        == CDR(b)$Lisp
        #   b        == LENGTH(b)$Lisp
        elt(b:%, i:Integer)       == destruct(b).i
        elt(b:%, li:List Integer) ==
          for i in li repeat b := destruct(b).i
          b
```

———-

— SEXOF.dotabb —

```
"SEXOF" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SEXOF"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"SEXOF" -> "FLAGG"
"SEXOF" -> "FLAGG-"
```

———-

20.10 domain SAE SimpleAlgebraicExtension

— SimpleAlgebraicExtension.input —

```
)set break resume
)sys rm -f SimpleAlgebraicExtension.output
)spool SimpleAlgebraicExtension.output
```

```
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SimpleAlgebraicExtension
--R
--R SimpleAlgebraicExtension(R: CommutativeRing,UP: UnivariatePolynomialCategory(R),M: UP)  is a domain cons
--R Abbreviation for SimpleAlgebraicExtension is SAE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SAE
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        basis : () -> Vector(%)
--R coerce : R -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              convert : UP -> %
--R convert : % -> UP                     convert : Vector(R) -> %
--R convert : % -> Vector(R)              coordinates : % -> Vector(R)
--R definingPolynomial : () -> UP         discriminant : () -> R
--R discriminant : Vector(%) -> R         generator : () -> %
--R hash : % -> SingleInteger             inv : % -> % if R has FIELD
--R latex : % -> String                   lift : % -> UP
--R norm : % -> R                         one? : % -> Boolean
--R rank : () -> PositiveInteger          recip : % -> Union(%,"failed")
--R reduce : UP -> %                      represents : Vector(R) -> %
--R retract : % -> R                      sample : () -> %
--R trace : % -> R                        traceMatrix : () -> Matrix(R)
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if R has FIELD
--R ?*? : (Fraction(Integer),%) -> % if R has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Integer) -> % if R has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if R has FIELD
--R D : (%,(R -> R)) -> % if R has FIELD
--R D : (%,(R -> R),NonNegativeInteger) -> % if R has FIELD
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has FIELD and R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has FIELD and R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has FIELD and R has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if R has FIELD and R has PDRING(SYMBOL)
--R D : (%,NonNegativeInteger) -> % if R has DIFRING and R has FIELD or R has FFIELDC
--R D : % -> % if R has DIFRING and R has FIELD or R has FFIELDC
--R ?^? : (%,Integer) -> % if R has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
```

```
--R associates? : (%,%) -> Boolean if R has FIELD
--R characteristic : () -> NonNegativeInteger
--R characteristicPolynomial : % -> UP
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R charthRoot : % -> % if R has FFIELDC
--R coerce : Fraction(Integer) -> % if R has FIELD or R has RETRACT(FRAC(INT))
--R coerce : % -> % if R has FIELD
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if R has FFIELDC
--R coordinates : Vector(%) -> Matrix(R)
--R coordinates : (Vector(%),Vector(%)) -> Matrix(R)
--R coordinates : (%,Vector(%)) -> Vector(R)
--R createPrimitiveElement : () -> % if R has FFIELDC
--R derivationCoordinates : (Vector(%),(R -> R)) -> Matrix(R) if R has FIELD
--R differentiate : (%,(R -> R)) -> % if R has FIELD
--R differentiate : (%,(R -> R),NonNegativeInteger) -> % if R has FIELD
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has FIELD and R has PDRI
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has FIELD and R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has FIELD and R has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if R has FIELD and R has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> % if R has DIFRING and R has FIELD or R has FFIELD
--R differentiate : % -> % if R has DIFRING and R has FIELD or R has FFIELDC
--R discreteLog : (%,%) -> Union(NonNegativeInteger,"failed") if R has FFIELDC
--R discreteLog : % -> NonNegativeInteger if R has FFIELDC
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed") if R has FIELD
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R factor : % -> Factored(%) if R has FIELD
--R factorsOfCyclicGroupSize : () -> List(Record(factor: Integer,exponent: Integer)) if R has FF
--R gcd : (%,%) -> % if R has FIELD
--R gcd : List(%) -> % if R has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R index : PositiveInteger -> % if R has FINITE
--R init : () -> % if R has FFIELDC
--R lcm : (%,%) -> % if R has FIELD
--R lcm : List(%) -> % if R has FIELD
--R lookup : % -> PositiveInteger if R has FINITE
--R minimalPolynomial : % -> UP if R has FIELD
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R nextItem : % -> Union(%,"failed") if R has FFIELDC
--R order : % -> OnePointCompletion(PositiveInteger) if R has FFIELDC
--R order : % -> PositiveInteger if R has FFIELDC
--R prime? : % -> Boolean if R has FIELD
--R primeFrobenius : % -> % if R has FFIELDC
--R primeFrobenius : (%,NonNegativeInteger) -> % if R has FFIELDC
--R primitive? : % -> Boolean if R has FFIELDC
--R primitiveElement : () -> % if R has FFIELDC
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if R has FIELD
```

```
--R ?quo? : (%,%) -> % if R has FIELD
--R random : () -> % if R has FINITE
--R reduce : Fraction(UP) -> Union(%,"failed") if R has FIELD
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LIN
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R regularRepresentation : % -> Matrix(R)
--R regularRepresentation : (%,Vector(%)) -> Matrix(R)
--R ?rem? : (%,%) -> % if R has FIELD
--R representationType : () -> Union("prime",polynomial,normal,cyclic) if R has FFIELDC
--R represents : (Vector(R),Vector(%)) -> %
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R size : () -> NonNegativeInteger if R has FINITE
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R squareFree : % -> Factored(%) if R has FIELD
--R squareFreePart : % -> % if R has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tableForDiscreteLogarithm : Integer -> Table(PositiveInteger,NonNegativeInteger) if R has FFIELDC
--R traceMatrix : Vector(%) -> Matrix(R)
--R unit? : % -> Boolean if R has FIELD
--R unitCanonical : % -> % if R has FIELD
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has FIELD
--R
--E 1

)spool
)lisp (bye)
```

———-


— SimpleAlgebraicExtension.help —

```
=====================================================================
SimpleAlgebraicExtension examples
=====================================================================

See Also:
o )show SimpleAlgebraicExtension
```

———-

20.10.1 SimpleAlgebraicExtension (SAE)



Exports:

0	1	associates?
basis	characteristic	characteristicPolynomial
charthRoot	coerce	conditionP
convert	coordinates	createPrimitiveElement
D	definingPolynomial	derivationCoordinates
differentiate	discreteLog	discriminant
divide	euclideanSize	expressIdealMember
exquo	extendedEuclidean	factor
factorsOfCyclicGroupSize	gcd	gcdPolynomial
generator	hash	index
init	inv	latex
lcm	lift	lookup
minimalPolynomial	multiEuclidean	nextItem
norm	one?	order
prime?	primeFrobenius	primitive?
primitiveElement	principalIdeal	random
rank	recip	reduce
reducedSystem	regularRepresentation	representationType
represents	retract	retractIfCan
sample	size	sizeLess?
squareFree	squareFreePart	subtractIfCan
tableForDiscreteLogarithm	trace	traceMatrix
unit?	unitCanonical	unitNormal
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?
?/?	?quo?	?rem?

— domain SAE SimpleAlgebraicExtension —

```
)abbrev domain SAE SimpleAlgebraicExtension
++ Author: Barry Trager, Manuel Bronstein, Clifton Williamson
```

```
++ Date Created: 1986
++ Date Last Updated: 9 May 1994
++ Keywords: ring, algebraic, extension
++ Description:
++ Algebraic extension of a ring by a single polynomial.
++ Domain which represents simple algebraic extensions of arbitrary
++ rings. The first argument to the domain, R, is the underlying ring,
++ the second argument is a domain of univariate polynomials over K,
++ while the last argument specifies the defining minimal polynomial.
++ The elements of the domain are canonically represented as polynomials
++ of degree less than that of the minimal polynomial with coefficients
++ in R. The second argument is both the type of the third argument and
++ the underlying representation used by \spadtype{SAE} itself.

SimpleAlgebraicExtension(R:CommutativeRing,
 UP:UnivariatePolynomialCategory R, M:UP): MonogenicAlgebra(R, UP) == add
    --sqFr(pb): FactorS(Poly) from UnivPolySquareFree(Poly)

    --degree(M) > 0 and M must be monic if R is not a field.
    if (r := recip leadingCoefficient M) case "failed" then
                                    error "Modulus cannot be made monic"
    Rep := UP
    x,y :$
    c: R

    mkDisc   : Boolean -> Void
    mkDiscMat: Boolean -> Void

    M   := r::R * M
    d   := degree M
    d1  := subtractIfCan(d,1)::NonNegativeInteger
    discmat:Matrix(R) := zero(d, d)
    nodiscmat?:Reference(Boolean) := ref true
    disc:Reference(R) := ref 0
    nodisc?:Reference(Boolean) := ref true
    bsis := [monomial(1, i)$Rep for i in 0..d1]$Vector(Rep)

    if R has Finite then
         size == size$R ** d
         random == represents([random()$R for i in 0..d1])
    0 == 0$Rep
    1 == 1$Rep
    c * x == c *$Rep x
    n:Integer * x == n *$Rep x
    coerce(n:Integer):$   == coerce(n)$Rep
    coerce(c) == monomial(c,0)$Rep
    coerce(x):OutputForm == coerce(x)$Rep
    lift(x) == x pretend Rep
    reduce(p:UP):$ == (monicDivide(p,M)$Rep).remainder
    x = y == x =$Rep y
```

```
x + y == x +$Rep y
- x == -$Rep x
x * y == reduce((x *$Rep y) pretend UP)
coordinates(x) == [coefficient(lift(x),i) for i in 0..d1]
represents(vect) == +/[monomial(vect.(i+1),i) for i in 0..d1]
definingPolynomial()  == M
characteristic()      == characteristic()$R
rank()                == d::PositiveInteger
basis()               == copy(bsis@Vector(Rep) pretend Vector($))
--!! I inserted 'copy' in the definition of 'basis'  -- cjw 7/19/91

if R has Field then
  minimalPolynomial x == squareFreePart characteristicPolynomial x

if R has Field then
  coordinates(x:$,bas: Vector $) ==
    (m := inverse transpose coordinates bas) case "failed" =>
      error "coordinates: second argument must be a basis"
    (m :: Matrix R) * coordinates(x)

else if R has IntegralDomain then
  coordinates(x:$,bas: Vector $) ==
    -- we work over the quotient field of R to invert a matrix
    qf := Fraction R
    imatqf := InnerMatrixQuotientFieldFunctions(R,Vector R,Vector R,_
               Matrix R,qf,Vector qf,Vector qf,Matrix qf)
    mat := transpose coordinates bas
    (m := inverse(mat)$imatqf) case "failed" =>
      error "coordinates: second argument must be a basis"
    coordsQF: Vector qf :=
      map(y +-> y::qf,coordinates x)$VectorFunctions2(R,qf)
    -- here are the coordinates as elements of the quotient field:
    vecQF := (m :: Matrix qf) * coordsQF
    vec : Vector R := new(d,0)
    for i in 1..d repeat
      xi := qelt(vecQF,i)
      denom(xi) = 1 => qsetelt_!(vec,i,numer xi)
      error "coordinates: coordinates are not integral over ground ring"
    vec

reducedSystem(m:Matrix $):Matrix(R) ==
  reducedSystem(map(lift, m)$MatrixCategoryFunctions2($, Vector $,
           Vector $, Matrix $, UP, Vector UP, Vector UP, Matrix UP))

reducedSystem(m:Matrix $, v:Vector $):Record(mat:Matrix R,vec:Vector R) ==
  reducedSystem(map(lift, m)$MatrixCategoryFunctions2($, Vector $,
           Vector $, Matrix $, UP, Vector UP, Vector UP, Matrix UP),
                               map(lift, v)$VectorFunctions2($, UP))

discriminant() ==
```

```
    if nodisc?() then mkDisc false
    disc()

  mkDisc b ==
    nodisc?() := b
    disc() := discriminant M
    void

  traceMatrix() ==
    if nodiscmat?() then mkDiscMat false
    discmat

  mkDiscMat b ==
    nodiscmat?() := b
    mr := minRowIndex discmat; mc := minColIndex discmat
    for i in 0..d1 repeat
      for j in 0..d1 repeat
        qsetelt_!(discmat,mr + i,mc + j,trace reduce monomial(1,i + j))
    void

  trace x ==          --this could be coded perhaps more efficiently
    xn := x;  ans := coefficient(lift xn, 0)
    for n in 1..d1 repeat
      (xn := generator() * xn;  ans := coefficient(lift xn, n) + ans)
    ans

  if R has Finite then
     index k ==
       i:Integer := k rem size()
       p:Integer := size()$R
       ans:$ := 0
       for j in 0.. while i > 0 repeat
         h := i rem p
         -- index(p) = 0$R
         if h ^= 0 then
           -- here was a bug: "index" instead of
           -- "coerce", otherwise it wouldn't work for
           -- Rings R where "coerce: I-> R" is not surjective
           a := index(h :: PositiveInteger)$R
           ans := ans + reduce monomial(a, j)
         i := i quo p
       ans
     lookup(z : $) : PositiveInteger ==
       -- z = index lookup z, n = lookup index n
       -- the answer is merely the Horner evaluation of the
       -- representation with the size of R (as integers).
       zero?(z) => size()$$ pretend PositiveInteger
       p  :            Integer := size()$R
       co :            Integer := lookup(leadingCoefficient z)$R
       n  : NonNegativeInteger := degree(z)
```

```
         while not zero?(z := reductum z) repeat
          co := co * p ** ((n - (n := degree z)) pretend
            NonNegativeInteger) + lookup(leadingCoefficient z)$R
         n = 0 => co pretend PositiveInteger
         (co * p ** n) pretend PositiveInteger

--
--   KA:=BasicPolynomialFunctions(Poly)
--   minPoly(x) ==
--      ffe:= SqFr(resultant(M::KA, KA.var - lift(x)::KA)).fs.first
--      ffe.flag = "SQFR" => ffe.f
--      mdeg:= (degree(ffe.f) // K.characteristic)::Integer
--      mat:= Zero()::Matrix<mdeg+1,deg+mdeg+1>(K)
--      xi:=L.1;  setelt(mat,1,1,K.1);  setelt(mat,1,(deg+1),K.1)
--      for i in 1..mdeg repeat
--         xi:= x * xi;  xp:= lift(xi)
--         while xp ^= KA.0 repeat
--            setelt(mat,(mdeg+1),(degree(xp)+1),LeadingCoef(xp))
--            xp:=reductum(xp)
--         setelt(mat,(mdeg+1),(deg+i+1),K.1)
--         EchelonLastRow(mat)
--         if and/(elt(mat,(i+1),j) = K.0 for j in 1..deg)
--           then return unitNormal(+/(elt(mat,(i+1),(deg+j+1))*(B::KA)**j
--                                       for j in 0..i)).a
--      ffe.f
```

———-

— SAE.dotabb —

```
"SAE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SAE"]
"MONOGEN" [color="#4488FF",href="bookvol10.2.pdf#nameddest=MONOGEN"]
"SAE" -> "MONOGEN"
```

———-

20.11 domain SFORT SimpleFortranProgram

— SimpleFortranProgram.input —

```
)set break resume
)sys rm -f SimpleFortranProgram.output
)spool SimpleFortranProgram.output
)set message test on
```

```
)set message auto off
)clear all

--S 1 of 1
)show SimpleFortranProgram
--R
--R SimpleFortranProgram(R: OrderedSet,FS: FunctionSpace(R))  is a domain constructor
--R Abbreviation for SimpleFortranProgram is SFORT
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SFORT
--R
--R------------------------------ Operations --------------------------------
--R coerce : % -> OutputForm              outputAsFortran : % -> Void
--R fortran : (Symbol,FortranScalarType,FS) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— SimpleFortranProgram.help —

```
========================================================================
SimpleFortranProgram examples
========================================================================

See Also:
o )show SimpleFortranProgram
```

———-

20.11.1 SimpleFortranProgram (SFORT)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266
⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “FortranProgram” (FORTRAN) 7.18.1 on page 926
⇒ “ThreeDimensionalMatrix” (M3D) 21.7.1 on page 2671
⇒ “Switch” (SWITCH) 20.36.1 on page 2597
⇒ “FortranTemplate” (FTEM) 7.20.1 on page 937
⇒ “FortranExpression” (FEXPR) 7.17.1 on page 917

Exports:
coerce fortran outputAsFortran

— domain SFORT SimpleFortranProgram —

```
)abbrev domain SFORT SimpleFortranProgram
-- Because of a bug in the compiler:
)bo $noSubsumption:=true

++ Author: Mike Dewar
++ Date Created: November 1992
++ Date Last Updated:
++ Basic Operations:
++ Related Constructors: FortranType, FortranCode, Switch
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ \axiomType{SimpleFortranProgram(f,type)} provides a simple model of some
++ FORTRAN subprograms, making it possible to coerce objects of various
++ domains into a FORTRAN subprogram called \axiom{f}.
++ These can then be translated into legal FORTRAN code.

SimpleFortranProgram(R,FS): Exports == Implementation where
  R  : OrderedSet
  FS : FunctionSpace(R)

  FST ==> FortranScalarType

  Exports ==> FortranProgramCategory with
    fortran : (Symbol,FST,FS) -> $
    ++fortran(fname,ftype,body) builds an object of type
    ++\axiomType{FortranProgramCategory}. The three arguments specify
    ++the name, the type and the body of the program.

  Implementation ==> add

    Rep := Record(name : Symbol, type : FST, body : FS )
```

```
    fortran(fname, ftype, res) ==
      construct(fname,ftype,res)$Rep

    nameOf(u:$):Symbol == u . name

    typeOf(u:$):Union(FST,"void") == u . type

    bodyOf(u:$):FS == u . body

    argumentsOf(u:$):List Symbol == variables(bodyOf u)$FS

    coerce(u:$):OutputForm ==
      coerce(nameOf u)$Symbol

    outputAsFortran(u:$):Void ==
      ftype := (checkType(typeOf(u)::OutputForm)$Lisp)::OutputForm
      fname := nameOf(u)::OutputForm
      args := argumentsOf(u)
      nargs:=args::OutputForm
      val  := bodyOf(u)::OutputForm
      fortFormatHead(ftype,fname,nargs)$Lisp
      fortFormatTypes(ftype,args)$Lisp
      dispfortexp1$Lisp ["="::OutputForm, fname, val]@List(OutputForm)
      dispfortexp1$Lisp "RETURN"::OutputForm
      dispfortexp1$Lisp "END"::OutputForm
      void()$Void
```

———-

— SFORT.dotabb —

```
"SFORT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SFORT"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"SFORT" -> "FS"
```

———-

20.12 domain SINT SingleInteger

The definition of **one?** has been rewritten as it relies on calling **ONEP** which is a function specific to Codemist Common Lisp but is not defined in Common Lisp.

— SingleInteger.input —

```
)set break resume
```

```
)sys rm -f SingleInteger.output
)spool SingleInteger.output
)set message test on
)set message auto off
)clear all
--S 1 of 11
min()$SingleInteger
--R
--R
--R   (1)  - 2147483648
--R                                                    Type: SingleInteger
--E 1

--S 2 of 11
max()$SingleInteger
--R
--R
--R   (2)  2147483647
--R                                                    Type: SingleInteger
--E 2

--S 3 of 11
a := 1234 :: SingleInteger
--R
--R
--R   (3)  1234
--R                                                    Type: SingleInteger
--E 3

--S 4 of 11
b := 124$SingleInteger
--R
--R
--R   (4)  124
--R                                                    Type: SingleInteger
--E 4

--S 5 of 11
gcd(a,b)
--R
--R
--R   (5)  2
--R                                                    Type: SingleInteger
--E 5

--S 6 of 11
lcm(a,b)
--R
--R
--R   (6)  76508
```

```
--R                                                    Type: SingleInteger
--E 6

--S 7 of 11
mulmod(5,6,13)$SingleInteger
--R
--R
--R   (7)  4
--R                                                    Type: SingleInteger
--E 7

--S 8 of 11
positiveRemainder(37,13)$SingleInteger
--R
--R
--R   (8)  11
--R                                                    Type: SingleInteger
--E 8

--S 9 of 11
And(3,4)$SingleInteger
--R
--R
--R   (9)  0
--R                                                    Type: SingleInteger
--E 9

--S 10 of 11
shift(1,4)$SingleInteger
--R
--R
--R   (10)  16
--R                                                    Type: SingleInteger
--E 10

--S 11 of 11
shift(31,-1)$SingleInteger
--R
--R
--R   (11)  15
--R                                                    Type: SingleInteger
--E 11
)spool
)lisp (bye)
```

———-

— SingleInteger.help —

```
=====================================================================
SingleInteger examples
=====================================================================

The SingleInteger domain is intended to provide support in Axiom
for machine integer arithmetic.  It is generally much faster than
(bignum) Integer arithmetic but suffers from a limited range of
values.  Since Axiom can be implemented on top of various dialects of
Lisp, the actual representation of small integers may not correspond
exactly to the host machines integer representation.

You can discover the minimum and maximum values in your implementation
by using min and max.

  min()$SingleInteger
    - 2147483648
                              Type: SingleInteger

  max()$SingleInteger
    2147483647
                              Type: SingleInteger

To avoid confusion with Integer, which is the default type for
integers, you usually need to work with declared variables.

  a := 1234 :: SingleInteger
    1234
                              Type: SingleInteger

or use package calling

  b := 124$SingleInteger
    124
                              Type: SingleInteger

You can add, multiply and subtract SingleInteger objects, and ask for
the greatest common divisor (gcd).

  gcd(a,b)
    2
                              Type: SingleInteger

The least common multiple (lcm) is also available.

  lcm(a,b)
    76508
                              Type: SingleInteger

Operations mulmod, addmod, submod, and invmod are similar - they provide
arithmetic modulo a given small integer.
```

```
Here is 5 * 6 mod 13.

  mulmod(5,6,13)$SingleInteger
    4
                              Type: SingleInteger

To reduce a small integer modulo a prime, use positiveRemainder.

  positiveRemainder(37,13)$SingleInteger
    11
                              Type: SingleInteger

Operations And, Or, xor, and Not provide bit level operations on small
integers.

  And(3,4)$SingleInteger
    0
                              Type: SingleInteger

Use shift(int,numToShift) to shift bits, where i is shifted left if
numToShift is positive, right if negative.

  shift(1,4)$SingleInteger
    16
                              Type: SingleInteger


  shift(31,-1)$SingleInteger
    15
                              Type: SingleInteger

Many other operations are available for small integers, including many
of those provided for Integer.

See Also:
o )help Integer
o )show SingleInteger
```

———-

20.12.1 SingleInteger (SINT)



Exports:

0	1	abs	addmod
And	associates?	base	binomial
bit?	characteristic	coerce	convert
copy	D	dec	differentiate
divide	euclideanSize	even?	expressIdealMember
exquo	extendedEuclidean	factor	factorial
gcd	gcdPolynomial	hash	inc
init	invmod	latex	lcm
length	mask	max	min
mulmod	multiEuclidean	negative?	nextItem
Not	not?	odd?	OMwrite
one?	Or	patternMatch	permutation
principalIdeal	positive?	positiveRemainder	powmod
prime?	random	rational	rationalIfCan
rational?	recip	reducedSystem	retract
retractIfCan	sample	shift	sign
sizeLess?	squareFree	squareFreePart	subtractIfCan
submod	symmetricRemainder	unit?	unitCanonical
unitNormal	xor	zero?	?*?
?**?	?+?	?-?	-?
?/\?	?<?	?<=?	?=?
?>?	?>=?	?\/?	?^?
?	?~=?	?quo?	?rem?

— domain SINT SingleInteger —

```
)abbrev domain SINT SingleInteger

-- following patch needed to deal with *:(I,%) -> %
-- affects behavior of SourceLevelSubset
--)bo $noSubsets := true
-- No longer - JHD !! still needed 5/3/91 BMT
```

```
++ Author:  Michael Monagan
++ Date Created:
++    January 1988
++ Change History:
++ Basic Operations: max, min,
++    not, and, or, xor, Not, And, Or
++ Related Constructors:
++ Keywords: single integer
++ Description:
++ SingleInteger is intended to support machine integer arithmetic.

-- MAXINT, BASE (machine integer constants)
-- MODULUS, MULTIPLIER (random number generator constants)


-- Lisp dependencies
-- EQ, ABSVAL, TIMES, INTEGER-LENGTH, HASHEQ, REMAINDER
-- QSLESSP, QSGREATERP, QSADD1, QSSUB1, QSMINUS, QSPLUS, QSDIFFERENCE
-- QSTIMES, QSREMAINDER, QSODDP, QSZEROP, QSMAX, QSMIN, QSNOT, QSAND
-- QSOR, QSXOR, QSLEFTSHIFT, QSADDMOD, QSDIFMOD, QSMULTMOD


SingleInteger(): Join(IntegerNumberSystem,Logic,OpenMath) with
   canonical
      ++ \spad{canonical} means that mathematical equality is
      ++ implied by data structure equality.
   canonicalsClosed
      ++ \spad{canonicalClosed} means two positives multiply to
      ++ give positive.
   noetherian
      ++ \spad{noetherian} all ideals are finitely generated
      ++ (in fact principal).

   max      : () -> %
      ++ max() returns the largest single integer.
   min      : () -> %
      ++ min() returns the smallest single integer.

   -- bit operations
   "not":   % -> %
      ++ not(n) returns the bit-by-bit logical not of the single integer n.
   "~"  :   % -> %
      ++  ~ n returns the bit-by-bit logical not of the single integer n.
   "/\": (%, %) -> %
      ++ n /\ m  returns the bit-by-bit logical and of
      ++ the single integers n and m.
   "\/" : (%, %) -> %
      ++ n \/ m  returns the bit-by-bit logical or of
      ++ the single integers n and m.
```

```
  "xor": (%, %) -> %
     ++ xor(n,m)  returns the bit-by-bit logical xor of
     ++ the single integers n and m.
  Not  : % -> %
     ++ Not(n) returns the bit-by-bit logical not of the single integer n.
  And  : (%,%) -> %
     ++ And(n,m)  returns the bit-by-bit logical and of
     ++ the single integers n and m.
  Or   : (%,%) -> %
     ++ Or(n,m)  returns the bit-by-bit logical or of
     ++ the single integers n and m.

== add

  seed : % := 1$Lisp               -- for random()
  MAXINT ==> MOST_-POSITIVE_-FIXNUM$Lisp
  MININT ==> MOST_-NEGATIVE_-FIXNUM$Lisp
  BASE ==> 67108864$Lisp           -- 2**26
  MULTIPLIER ==> 314159269$Lisp    -- from Knuth's table
  MODULUS ==> 2147483647$Lisp      -- 2**31-1

  writeOMSingleInt(dev: OpenMathDevice, x: %): Void ==
   if x < 0 then
     OMputApp(dev)
     OMputSymbol(dev, "arith1", "unary_minus")
     OMputInteger(dev, convert(-x))
     OMputEndApp(dev)
   else
     OMputInteger(dev, convert(x))

  OMwrite(x: %): String ==
   s: String := ""
   sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
   dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
   OMputObject(dev)
   writeOMSingleInt(dev, x)
   OMputEndObject(dev)
   OMclose(dev)
   s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
   s

  OMwrite(x: %, wholeObj: Boolean): String ==
   s: String := ""
   sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
   dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
   if wholeObj then
     OMputObject(dev)
   writeOMSingleInt(dev, x)
   if wholeObj then
     OMputEndObject(dev)
```

```
    OMclose(dev)
    s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
    s

   OMwrite(dev: OpenMathDevice, x: %): Void ==
    OMputObject(dev)
    writeOMSingleInt(dev, x)
    OMputEndObject(dev)

   OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
    if wholeObj then
      OMputObject(dev)
    writeOMSingleInt(dev, x)
    if wholeObj then
      OMputEndObject(dev)

   reducedSystem m      == m pretend Matrix(Integer)
   coerce(x):OutputForm == (convert(x)@Integer)::OutputForm
   convert(x:%):Integer == x pretend Integer
   i:Integer * y:%      == i::% * y
   0         == 0$Lisp
   1         == 1$Lisp
   base()    == 2$Lisp
   max()     == MAXINT
   min()     == MININT
   x = y     == EQL(x,y)$Lisp
   _~ x      == LOGNOT(x)$Lisp
   not(x)    == LOGNOT(x)$Lisp
   _/_\(x,y) == LOGAND(x,y)$Lisp
   _\_/(x,y) == LOGIOR(x,y)$Lisp
   Not(x)    == LOGNOT(x)$Lisp
   And(x,y)  == LOGAND(x,y)$Lisp
   Or(x,y)   == LOGIOR(x,y)$Lisp
   xor(x,y)  == LOGXOR(x,y)$Lisp
   x < y     == QSLESSP(x,y)$Lisp
   inc x     == QSADD1(x)$Lisp
   dec x     == QSSUB1(x)$Lisp
   - x       == QSMINUS(x)$Lisp
   x + y     == QSPLUS(x,y)$Lisp
   x:% - y:% == QSDIFFERENCE(x,y)$Lisp
   x:% * y:% == QSTIMES(x,y)$Lisp
   x:% ** n:NonNegativeInteger == ((EXPT(x, n)$Lisp) pretend Integer)::%
   x quo y   == QSQUOTIENT(x,y)$Lisp
   x rem y   == QSREMAINDER(x,y)$Lisp
   divide(x, y)   == CONS(QSQUOTIENT(x,y)$Lisp,QSREMAINDER(x,y)$Lisp)$Lisp
   gcd(x,y)  == GCD(x,y)$Lisp
   abs(x)    == QSABSVAL(x)$Lisp
   odd?(x)   == QSODDP(x)$Lisp
   zero?(x)  == QSZEROP(x)$Lisp
--   one?(x)   == ONEP(x)$Lisp
```

```
   one?(x)   == x = 1
   max(x,y)  == QSMAX(x,y)$Lisp
   min(x,y)  == QSMIN(x,y)$Lisp
   hash(x)   == SXHASH(x)$Lisp
   length(x) == INTEGER_-LENGTH(x)$Lisp
   shift(x,n)    == QSLEFTSHIFT(x,n)$Lisp
   mulmod(a,b,p) == QSMULTMOD(a,b,p)$Lisp
   addmod(a,b,p) == QSADDMOD(a,b,p)$Lisp
   submod(a,b,p) == QSDIFMOD(a,b,p)$Lisp
   negative?(x)  == QSMINUSP$Lisp x


   reducedSystem(m, v) ==
        [m pretend Matrix(Integer), v pretend Vector(Integer)]

   positiveRemainder(x,n) ==
      r := QSREMAINDER(x,n)$Lisp
      QSMINUSP(r)$Lisp =>
          QSMINUSP(n)$Lisp => QSDIFFERENCE(x, n)$Lisp
          QSPLUS(r, n)$Lisp
      r

   coerce(x:Integer):% ==
      (x <= max pretend Integer) and (x >= min pretend Integer) =>
        x pretend %
      error "integer too large to represent in a machine word"

   random() ==
      seed := REMAINDER(TIMES(MULTIPLIER,seed)$Lisp,MODULUS)$Lisp
      REMAINDER(seed,BASE)$Lisp

   random(n) == RANDOM(n)$Lisp

   UCA ==> Record(unit:%,canonical:%,associate:%)
   unitNormal x ==
      x < 0 => [-1,-x,-1]$UCA
      [1,x,1]$UCA

)bo $noSubsets := false
```

— SINT.dotabb —

```
"SINT" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SINT",shape=ellipse]
"PID" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PID"]
"OAGROUP" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OAGROUP"]
"SINT" -> "PID"
```

```
"SINT" -> "OAGROUP"
```

———-

20.13 domain SAOS SingletonAsOrderedSet

— **SingletonAsOrderedSet.input** —

```
)set break resume
)sys rm -f SingletonAsOrderedSet.output
)spool SingletonAsOrderedSet.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SingletonAsOrderedSet
--R SingletonAsOrderedSet  is a domain constructor
--R Abbreviation for SingletonAsOrderedSet is SAOS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SAOS
--R
--R------------------------------ Operations --------------------------------
--R ?<? : (%,%) -> Boolean               ?<=? : (%,%) -> Boolean
--R ?=? : (%,%) -> Boolean               ?>? : (%,%) -> Boolean
--R ?>=? : (%,%) -> Boolean              coerce : % -> OutputForm
--R convert : % -> Symbol                create : () -> %
--R hash : % -> SingleInteger            latex : % -> String
--R max : (%,%) -> %                     min : (%,%) -> %
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— **SingletonAsOrderedSet.help** —

```
=====================================================================
SingletonAsOrderedSet examples
=====================================================================

See Also:
```

```
o )show SingletonAsOrderedSet
```

20.13.1 SingletonAsOrderedSet (SAOS)



Exports:

coerce	convert	create	hash	latex
max	min	?~=?	?<?	?<=?
?=?	?>?	?>=?		

— domain SAOS SingletonAsOrderedSet —

```
)abbrev domain SAOS SingletonAsOrderedSet
++ Author: Mark Botch
++ Description:
++ This trivial domain lets us build Univariate Polynomials
++ in an anonymous variable

SingletonAsOrderedSet(): OrderedSet with
              create:() -> %
              convert:% -> Symbol
  ==  add
   create() == "?" pretend %
   a<b == false -- only one element
   coerce(a) == outputForm "?"  -- CJW doesn't like this: change ?
   a=b == true  -- only one element
   min(a,b) == a  -- only one element
   max(a,b) == a  -- only one element
   convert a == coerce("?")
```

— SAOS.dotabb —

```
"SAOS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SAOS"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SAOS" -> "ALIST"
```

———-

20.14 domain SMP SparseMultivariatePolynomial

— **SparseMultivariatePolynomial.input** —

```
)set break resume
)sys rm -f SparseMultivariatePolynomial.output
)spool SparseMultivariatePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseMultivariatePolynomial
--R
--R SparseMultivariatePolynomial(R: Ring,VarSet: OrderedSet)  is a domain constructor
--R Abbreviation for SparseMultivariatePolynomial is SMP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SMP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,List(VarSet)) -> %             D : (%,VarSet) -> %
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coefficients : % -> List(R)
--R coerce : VarSet -> %                  coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R differentiate : (%,VarSet) -> %       eval : (%,VarSet,%) -> %
--R eval : (%,VarSet,R) -> %              eval : (%,%,%) -> %
--R eval : (%,Equation(%)) -> %           ground : % -> R
--R ground? : % -> Boolean                hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> R
--R leadingMonomial : % -> %              map : ((R -> R),%) -> %
--R monomial? : % -> Boolean              monomials : % -> List(%)
--R one? : % -> Boolean                  recip : % -> Union(%,"failed")
--R reductum : % -> %                    retract : % -> VarSet
--R retract : % -> R                     sample : () -> %
```

```
--R variables : % -> List(VarSet)         zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R D : (%,VarSet,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R coefficient : (%,VarSet,NonNegativeInteger) -> %
--R coefficient : (%,IndexedExponents(VarSet)) -> R
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : % -> % if R has INTDOM
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,VarSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if R has KONVERT(INFORM) and VarSet has KONVERT(INFORM)
--R convert : % -> Pattern(Integer) if R has KONVERT(PATTERN(INT)) and VarSet has KONVERT(PATTER
--R convert : % -> Pattern(Float) if R has KONVERT(PATTERN(FLOAT)) and VarSet has KONVERT(PATTER
--R degree : (%,List(VarSet)) -> List(NonNegativeInteger)
--R degree : (%,VarSet) -> NonNegativeInteger
--R degree : % -> IndexedExponents(VarSet)
--R differentiate : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R differentiate : (%,VarSet,NonNegativeInteger) -> %
--R differentiate : (%,List(VarSet)) -> %
--R discriminant : (%,VarSet) -> % if R has COMRING
--R eval : (%,List(VarSet),List(%)) -> %
--R eval : (%,List(VarSet),List(R)) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R isExpt : % -> Union(Record(var: VarSet,exponent: NonNegativeInteger),"failed")
--R isPlus : % -> Union(List(%),"failed")
```

```
--R isTimes : % -> Union(List(%),"failed")
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R mainVariable : % -> Union(VarSet,"failed")
--R mapExponents : ((IndexedExponents(VarSet) -> IndexedExponents(VarSet)),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List(VarSet)) -> List(NonNegativeInteger)
--R minimumDegree : (%,VarSet) -> NonNegativeInteger
--R minimumDegree : % -> IndexedExponents(VarSet)
--R monicDivide : (%,%,VarSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List(VarSet),List(NonNegativeInteger)) -> %
--R monomial : (%,VarSet,NonNegativeInteger) -> %
--R monomial : (R,IndexedExponents(VarSet)) -> %
--R multivariate : (SparseUnivariatePolynomial(%),VarSet) -> %
--R multivariate : (SparseUnivariatePolynomial(R),VarSet) -> %
--R numberOfMonomials : % -> NonNegativeInteger
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if R
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if R has P
--R pomopo! : (%,R,IndexedExponents(VarSet),%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,VarSet) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R reducedSystem : Matrix(%) -> Matrix(R)
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LIN
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R resultant : (%,%,VarSet) -> % if R has COMRING
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(VarSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if R has
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List(VarSet)) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,VarSet) -> SparseUnivariatePolynomial(%)
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **SparseMultivariatePolynomial.help** —

```
==========================================================================
SparseMultivariatePolynomial examples
==========================================================================

See Also:
o )show SparseMultivariatePolynomial
```

———-

20.14.1 SparseMultivariatePolynomial (SMP)



See

⇒ “Polynomial” (POLY) 17.25.1 on page 2043
⇒ “MultivariatePolynomial” (MPOLY) 14.16.1 on page 1649
⇒ “IndexedExponents” (INDE) 10.9.1 on page 1187

Exports:

0	1	associates?
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
conditionP	content	convert
D	degree	differentiate
discriminant	eval	exquo
factor	factorPolynomial	factorSquareFreePolynomial
gcd	gcdPolynomial	ground
ground?	hash	latex
isExpt	isPlus	isTimes
lcm	leadingCoefficient	leadingMonomial
mainVariable	map	mapExponents
max	min	minimumDegree
monicDivide	monomial	monomial?
monomials	multivariate	numberOfMonomials
one?	patternMatch	pomopo!
prime?	primitivePart	primitiveMonomials
recip	reducedSystem	reductum
resultant	retract	retractIfCan
sample	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
totalDegree	unit?	unitCanonical
unitNormal	univariate	variables
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?
?/?	?<?	?<=?
?>?	?>=?	

— domain SMP SparseMultivariatePolynomial —

```
)abbrev domain SMP SparseMultivariatePolynomial
++ Author: Dave Barton, Barry Trager
++ Date Created:
++ Date Last Updated: 30 November 1994
++ Fix History:
++ 30 Nov 94: added gcdPolynomial for float-type coefficients
++ Basic Functions: Ring, degree, eval, coefficient, monomial, differentiate,
++ resultant, gcd
++ Related Constructors: Polynomial, MultivariatePolynomial
++ Also See:
++ AMS Classifications:
++ Keywords: polynomial, multivariate
++ References:
++ Description:
++ This type is the basic representation of sparse recursive multivariate
```

```
++ polynomials. It is parameterized by the coefficient ring and the
++ variable set which may be infinite. The variable ordering is determined
++ by the variable set parameter. The coefficient ring may be non-commutative,
++ but the variables are assumed to commute.

SparseMultivariatePolynomial(R: Ring,VarSet: OrderedSet): C == T where
  pgcd ==> PolynomialGcdPackage(IndexedExponents VarSet,VarSet,R,%)
  C == PolynomialCategory(R,IndexedExponents(VarSet),VarSet)
  SUP ==> SparseUnivariatePolynomial
  T == add
    --constants
    --D := F(%) replaced by next line until compiler support completed

    --representations
      D := SparseUnivariatePolynomial(%)
      VPoly:=  Record(v:VarSet,ts:D)
      Rep:=  Union(R,VPoly)

    --local function


    --declarations
      fn: R -> R
      n: Integer
      k: NonNegativeInteger
      kp:PositiveInteger
      k1:NonNegativeInteger
      c: R
      mvar: VarSet
      val : R
      var:VarSet
      up: D
      p,p1,p2,pval: %
      Lval : List(R)
      Lpval : List(%)
      Lvar : List(VarSet)

    --define
      0  == 0$R::%
      1  == 1$R::%


      zero? p == p case R and zero?(p)$R
--      one? p == p case R and one?(p)$R
      one? p == p case R and ((p) = 1)$R
    -- a local function
      red(p:%):% ==
         p case R => 0
         if ground?(reductum p.ts) then
           leadingCoefficient(reductum p.ts) else [p.v,reductum p.ts]$VPoly
```

```
      numberOfMonomials(p): NonNegativeInteger ==
        p case R =>
          zero?(p)$R => 0
          1
        +/[numberOfMonomials q for q in coefficients(p.ts)]

      coerce(mvar):% == [mvar,monomial(1,1)$D]$VPoly

      monomial? p ==
        p case R => true
        sup : D := p.ts
        1 ^= numberOfMonomials(sup) => false
        monomial? leadingCoefficient(sup)$D

--    local
      moreThanOneVariable?: % -> Boolean

      moreThanOneVariable? p ==
         p case R => false
         q:=p.ts
         any?(x1+->not ground? x1 ,coefficients q) => true
         false

      -- if we already know we use this (slighlty) faster function
      univariateKnown: % -> SparseUnivariatePolynomial R

      univariateKnown p ==
        p case R => (leadingCoefficient p) :: SparseUnivariatePolynomial(R)
        monomial( leadingCoefficient p,degree p.ts)+ univariateKnown(red p)

      univariate p ==
        p case R =>(leadingCoefficient p) :: SparseUnivariatePolynomial(R)
        moreThanOneVariable?  p => error "not univariate"
        monomial( leadingCoefficient p,degree p.ts)+ univariate(red p)

      multivariate (u:SparseUnivariatePolynomial(R),var:VarSet) ==
        ground? u => (leadingCoefficient u) ::%
        [var,monomial(leadingCoefficient u,degree u)$D]$VPoly +
           multivariate(reductum u,var)

      univariate(p:%,mvar:VarSet):SparseUnivariatePolynomial(%) ==
        p case R or mvar>p.v  => monomial(p,0)$D
        pt:=p.ts
        mvar=p.v => pt
        monomial(1,p.v,degree pt)*univariate(leadingCoefficient pt,mvar)+
          univariate(red p,mvar)

--  a local functions, used in next definition
      unlikeUnivReconstruct(u:SparseUnivariatePolynomial(%),mvar:VarSet):% ==
```

```
        zero? (d:=degree u) => coefficient(u,0)
        monomial(leadingCoefficient u,mvar,d)+
            unlikeUnivReconstruct(reductum u,mvar)

      multivariate(u:SparseUnivariatePolynomial(%),mvar:VarSet):% ==
        ground? u => coefficient(u,0)
        uu:=u
        while not zero? uu repeat
          cc:=leadingCoefficient uu
          cc case R or mvar > cc.v => uu:=reductum uu
          return unlikeUnivReconstruct(u,mvar)
        [mvar,u]$VPoly

      ground?(p:%):Boolean ==
        p case R => true
        false

--      const p ==
--        p case R => p
--        error "the polynomial is not a constant"

      monomial(p,mvar,k1) ==
        zero? k1 or zero? p => p
        p case R or mvar>p.v => [mvar,monomial(p,k1)$D]$VPoly
        p*[mvar,monomial(1,k1)$D]$VPoly

      monomial(c:R,e:IndexedExponents(VarSet)):% ==
        zero? e => (c::%)
        monomial(1,leadingSupport e, leadingCoefficient e) *
            monomial(c,reductum e)

      coefficient(p:%, e:IndexedExponents(VarSet)) : R ==
        zero? e =>
          p case R  => p::R
          coefficient(coefficient(p.ts,0),e)
        p case R => 0
        ve := leadingSupport e
        vp := p.v
        ve < vp =>
          coefficient(coefficient(p.ts,0),e)
        ve > vp => 0
        coefficient(coefficient(p.ts,leadingCoefficient e),reductum e)

--    coerce(e:IndexedExponents(VarSet)) : % ==
--      e = 0 => 1
--      monomial(1,leadingSupport e, leadingCoefficient e) *
--          (reductum e)::%

--    retract(p:%):IndexedExponents(VarSet) ==
--      q:Union(IndexedExponents(VarSet),"failed"):=retractIfCan p
```

```
--      q :: IndexedExponents(VarSet)

--    retractIfCan(p:%):Union(IndexedExponents(VarSet),"failed") ==
--      p = 0 => degree p
--      reductum(p)=0 and leadingCoefficient(p)=1 => degree p
--      "failed"

      coerce(n) == n::R::%
      coerce(c) == c::%
      characteristic == characteristic$R

      recip(p) ==
        p case R => (uu:=recip(p::R);uu case "failed" => "failed"; uu::%)
        "failed"

      - p ==
          p case R => -$R p
          [p.v, - p.ts]$VPoly
      n * p  ==
          p case R => n * p::R
          mvar:=p.v
          up:=n*p.ts
          if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
      c * p  ==
          c = 1 => p
          p case R => c * p::R
          mvar:=p.v
          up:=c*p.ts
          if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
      p1 + p2  ==
         p1 case R and p2 case R => p1 +$R p2
         p1 case R => [p2.v, p1::D + p2.ts]$VPoly
         p2 case R => [p1.v,  p1.ts + p2::D]$VPoly
         p1.v = p2.v =>
              mvar:=p1.v
              up:=p1.ts+p2.ts
              if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
         p1.v < p2.v =>
              [p2.v, p1::D + p2.ts]$VPoly
         [p1.v, p1.ts + p2::D]$VPoly

      p1 - p2  ==
         p1 case R and p2 case R => p1 -$R p2
         p1 case R => [p2.v, p1::D - p2.ts]$VPoly
         p2 case R => [p1.v,  p1.ts - p2::D]$VPoly
         p1.v = p2.v =>
              mvar:=p1.v
              up:=p1.ts-p2.ts
              if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
         p1.v < p2.v =>
```

```
          [p2.v, p1::D - p2.ts]$VPoly
      [p1.v, p1.ts - p2::D]$VPoly

   p1 = p2  ==
      p1 case R =>
          p2 case R => p1 =$R p2
          false
      p2 case R => false
      p1.v = p2.v => p1.ts = p2.ts
      false

   p1 * p2  ==
      p1 case R => p1::R * p2
      p2 case R =>
         mvar:=p1.v
         up:=p1.ts*p2
         if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
      p1.v = p2.v =>
         mvar:=p1.v
         up:=p1.ts*p2.ts
         if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
      p1.v > p2.v =>
         mvar:=p1.v
         up:=p1.ts*p2
         if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
         --- p1.v < p2.v
      mvar:=p2.v
      up:=p1*p2.ts
      if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly

   p ^ kp == p ** (kp pretend NonNegativeInteger)
   p ** kp == p ** (kp pretend NonNegativeInteger )
   p ^ k == p ** k
   p ** k  ==
      p case R => p::R ** k
      -- univariate special case
      not moreThanOneVariable? p =>
          multivariate( (univariateKnown p) ** k , p.v)
      mvar:=p.v
      up:=p.ts ** k
      if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly

   if R has IntegralDomain then
      UnitCorrAssoc ==> Record(unit:%,canonical:%,associate:%)
      unitNormal(p) ==
         u,c,a:R
         p case R =>
           (u,c,a):= unitNormal(p::R)$R
           [u::%,c::%,a::%]$UnitCorrAssoc
         (u,c,a):= unitNormal(leadingCoefficient(p))$R
```

```
            [u::%,(a*p)::%,a::%]$UnitCorrAssoc
          unitCanonical(p) ==
            p case R => unitCanonical(p::R)$R
            (u,c,a):= unitNormal(leadingCoefficient(p))$R
            a*p
          unit? p ==
            p case R => unit?(p::R)$R
            false
          associates?(p1,p2) ==
            p1 case R => p2 case R and associates?(p1,p2)$R
            p2 case VPoly and p1.v = p2.v and associates?(p1.ts,p2.ts)

          if R has approximate then
            p1  exquo  p2  ==
              p1 case R and p2 case R =>
                a:= (p1::R  exquo  p2::R)
                if a case "failed" then "failed" else a::%
              zero? p1 => p1
--              one? p2 => p1
              (p2 = 1) => p1
              p1 case R or p2 case VPoly and p1.v < p2.v => "failed"
              p2 case R or p1.v > p2.v =>
                 a:= (p1.ts  exquo  p2::D)
                 a case "failed" => "failed"
                 [p1.v,a]$VPoly::%
              -- The next test is useful in the case that R has inexact
              -- arithmetic (in particular when it is Interval(...)).
              -- In the case where the test succeeds, empirical evidence
              -- suggests that it can speed up the computation several times,
              -- but in other cases where there are a lot of variables
              -- and p1 and p2 differ only in the low order terms (e.g. p1=p2+1)
              -- it slows exquo down by about 15-20%.
              p1 = p2 => 1
              a:= p1.ts  exquo  p2.ts
              a case "failed" => "failed"
              mvar:=p1.v
              up:SUP %:=a
              if ground? (up) then
                leadingCoefficient(up) else [mvar,up]$VPoly::%
          else
            p1  exquo  p2  ==
              p1 case R and p2 case R =>
                a:= (p1::R  exquo  p2::R)
                if a case "failed" then "failed" else a::%
              zero? p1 => p1
--              one? p2 => p1
              (p2 = 1) => p1
              p1 case R or p2 case VPoly and p1.v < p2.v => "failed"
              p2 case R or p1.v > p2.v =>
                 a:= (p1.ts  exquo  p2::D)
```

```
                a case "failed" => "failed"
                [p1.v,a]$VPoly::%
            a:= p1.ts  exquo  p2.ts
            a case "failed" => "failed"
            mvar:=p1.v
            up:SUP %:=a
            if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly::%

      map(fn,p) ==
         p case R => fn(p)
         mvar:=p.v
         up:=map(x1+->map(fn,x1),p.ts)
         if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly

      if R has Field then
        (p : %) / (r : R) == inv(r) * p

      if R has GcdDomain then
        content(p) ==
           p case R => p
           c :R :=0
           up:=p.ts
--           while not(zero? up) and not(one? c) repeat
           while not(zero? up) and not(c = 1) repeat
               c:=gcd(c,content leadingCoefficient(up))
               up := reductum up
           c

      if R has EuclideanDomain and
          R has CharacteristicZero and
           not(R has FloatingPointSystem)  then

        content(p,mvar) ==
          p case R => p
          gcd(coefficients univariate(p,mvar))$pgcd

        gcd(p1,p2) ==  gcd(p1,p2)$pgcd

        gcd(lp:List %) ==  gcd(lp)$pgcd

        gcdPolynomial(a:SUP $,b:SUP $):SUP $ == gcd(a,b)$pgcd

      else if R has GcdDomain then
        content(p,mvar) ==
          p case R => p
          content univariate(p,mvar)

        gcd(p1,p2) ==
           p1 case R =>
              p2 case R => gcd(p1,p2)$R::%
```

```
            zero? p1 => p2
            gcd(p1, content(p2.ts))
         p2 case R =>
            zero? p2 => p1
            gcd(p2, content(p1.ts))
         p1.v < p2.v => gcd(p1, content(p2.ts))
         p1.v > p2.v => gcd(content(p1.ts), p2)
         mvar:=p1.v
         up:=gcd(p1.ts, p2.ts)
         if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly

      if R has FloatingPointSystem then
         -- eventually need a better notion of gcd's over floats
         -- this essentially computes the gcds of the monomial contents
         gcdPolynomial(a:SUP $,b:SUP $):SUP $ ==
            ground? (a) =>
                zero? a => b
                gcd(leadingCoefficient a, content b)::SUP $
            ground?(b) =>
                zero? b => b
                gcd(leadingCoefficient b, content a)::SUP $
            conta := content a
            mona:SUP $ := monomial(conta, minimumDegree a)
            if mona ^= 1 then
                 a := (a exquo mona)::SUP $
            contb := content b
            monb:SUP $ := monomial(contb, minimumDegree b)
            if monb ^= 1 then
                 b := (b exquo monb)::SUP $
            mong:SUP $  := monomial(gcd(conta, contb),
                                    min(degree mona, degree monb))
            degree(a) >= degree b =>
                 not((a exquo b) case "failed") =>
                      mong * b
                 mong
            not((b exquo a) case "failed") => mong * a
            mong

      coerce(p):OutputForm ==
        p case R => (p::R)::OutputForm
        outputForm(p.ts,p.v::OutputForm)

      coefficients p ==
        p case R => list(p :: R)$List(R)
        "append"/[coefficients(p1)$% for p1 in coefficients(p.ts)]

      retract(p:%):R ==
        p case R => p :: R
        error "cannot retract nonconstant polynomial"
```

```
      retractIfCan(p:%):Union(R, "failed") ==
        p case R => p::R
        "failed"

--      leadingCoefficientRecursive(p:%):% ==
--         p case R => p
--         leadingCoefficient p.ts

      mymerge:(List VarSet,List VarSet) ->List VarSet
      mymerge(l:List VarSet,m:List VarSet):List VarSet  ==
         empty? l => m
         empty? m => l
         first l = first m =>
            empty? rest l =>
                 setrest!(l,rest m)
                 l
            empty? rest m => l
            setrest!(l, mymerge(rest l, rest m))
            l
         first l > first m =>
            empty? rest l =>
                setrest!(l,m)
                l
            setrest!(l, mymerge(rest l, m))
            l
         empty? rest m =>
             setrest!(m,l)
             m
         setrest!(m,mymerge(l,rest m))
         m

      variables p ==
         p case R => empty()
         lv:List VarSet:=empty()
         q := p.ts
         while not zero? q repeat
           lv:=mymerge(lv,variables leadingCoefficient q)
           q := reductum q
         cons(p.v,lv)

      mainVariable p ==
         p case R => "failed"
         p.v

      eval(p,mvar,pval) == univariate(p,mvar)(pval)
      eval(p,mvar,val) ==  univariate(p,mvar)(val)

      evalSortedVarlist(p,Lvar,Lpval):% ==
        p case R => p
        empty? Lvar or empty? Lpval => p
```

```
    mvar := Lvar.first
    mvar > p.v => evalSortedVarlist(p,Lvar.rest,Lpval.rest)
    pval := Lpval.first
    pts := map(x1+->evalSortedVarlist(x1,Lvar,Lpval),p.ts)
    mvar=p.v =>
         pval case R => pts (pval::R)
         pts pval
    multivariate(pts,p.v)

  eval(p,Lvar,Lpval) ==
    empty? rest Lvar => evalSortedVarlist(p,Lvar,Lpval)
    sorted?((x1,x2) +-> x1 > x2, Lvar) => evalSortedVarlist(p,Lvar,Lpval)
    nlvar := sort((x1,x2) +-> x1 > x2,Lvar)
    nlpval :=
       Lvar = nlvar => Lpval
       nlpval := [Lpval.position(mvar,Lvar) for mvar in nlvar]
    evalSortedVarlist(p,nlvar,nlpval)

  eval(p,Lvar,Lval) ==
    eval(p,Lvar,[val::% for val in Lval]$(List %)) -- kill?

  degree(p,mvar) ==
    p case R => 0
    mvar= p.v => degree p.ts
    mvar > p.v => 0    -- might as well take advantage of the order
    max(degree(leadingCoefficient p.ts,mvar),degree(red p,mvar))

  degree(p,Lvar)  == [degree(p,mvar)  for mvar in Lvar]

  degree p ==
    p case R => 0
    degree(leadingCoefficient(p.ts)) + monomial(degree(p.ts), p.v)

  minimumDegree p ==
    p case R => 0
    md := minimumDegree p.ts
    minimumDegree(coefficient(p.ts,md)) + monomial(md, p.v)

  minimumDegree(p,mvar) ==
    p case R => 0
    mvar = p.v => minimumDegree p.ts
    md:=minimumDegree(leadingCoefficient p.ts,mvar)
    zero? (p1:=red p) => md
    min(md,minimumDegree(p1,mvar))

  minimumDegree(p,Lvar) ==
    [minimumDegree(p,mvar) for mvar in Lvar]

  totalDegree(p, Lvar) ==
    ground? p => 0
```

```
        null setIntersection(Lvar, variables p) => 0
        u := univariate(p, mv := mainVariable(p)::VarSet)
        weight:NonNegativeInteger := (member?(mv,Lvar) => 1; 0)
        tdeg:NonNegativeInteger := 0
        while u ^= 0 repeat
            termdeg:NonNegativeInteger := weight*degree u +
                           totalDegree(leadingCoefficient u, Lvar)
            tdeg := max(tdeg, termdeg)
            u := reductum u
        tdeg

      if R has CommutativeRing then
        differentiate(p,mvar) ==
          p case R => 0
          mvar=p.v =>
             up:=differentiate p.ts
             if ground? up then leadingCoefficient(up) else [mvar,up]$VPoly
          up:=map(x1 +-> differentiate(x1,mvar),p.ts)
          if ground? up then leadingCoefficient(up) else [p.v,up]$VPoly

      leadingCoefficient(p) ==
         p case R => p
         leadingCoefficient(leadingCoefficient(p.ts))

--      trailingCoef(p) ==
--        p case R => p
--        coef(p.ts,0) case R => coef(p.ts,0)
--        trailingCoef(red p)
--      TrailingCoef(p) == trailingCoef(p)

      leadingMonomial p ==
          p case R => p
          monomial(leadingMonomial leadingCoefficient(p.ts),
                   p.v, degree(p.ts))

      reductum(p) ==
          p case R => 0
          p - leadingMonomial p


--        if R is Integer then
--           pgcd := PolynomialGcdPackage(%,VarSet)
--           gcd(p1,p2) ==
--               gcd(p1,p2)$pgcd
--
--        else if R is RationalNumber then
--           gcd(p1,p2) ==
--               mrat:= MRationalFactorize(VarSet,%)
--               gcd(p1,p2)$mrat
--
```

```
--        else gcd(p1,p2) ==
--           p1 case R =>
--              p2 case R => gcd(p1,p2)$R::%
--              p1 = 0 => p2
--              gcd(p1, content(p2.ts))
--           p2 case R =>
--              p2 = 0 => p1
--              gcd(p2, content(p1.ts))
--           p1.v < p2.v => gcd(p1, content(p2.ts))
--           p1.v > p2.v => gcd(content(p1.ts), p2)
--           PSimp(p1.v, gcd(p1.ts, p2.ts))
```

———-

— **SMP.dotabb** —

```
"SMP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SMP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"SMP" -> "PFECAT"
```

———-

20.15 domain SMTS SparseMultivariateTaylorSeries

— **SparseMultivariateTaylorSeries.input** —

```
)set break resume
)sys rm -f SparseMultivariateTaylorSeries.output
)spool SparseMultivariateTaylorSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 10
xts:=x::TaylorSeries Fraction Integer
--R
--R
--R   (1)  x
--R                                        Type: TaylorSeries(Fraction(Integer))
--E 1

--S 2 of 10
yts:=y::TaylorSeries Fraction Integer
--R
```

```
--R
--R   (2)  y
--R                                        Type: TaylorSeries(Fraction(Integer))
--E 2

--S 3 of 10
zts:=z::TaylorSeries Fraction Integer
--R
--R
--R   (3)  z
--R                                        Type: TaylorSeries(Fraction(Integer))
--E 3

--S 4 of 10
t1:=sin(xts)
--R
--R
--R            1  3    1   5     1   7      1    9
--R   (4)  x - - x  + --- x  - ---- x  + ------ x  + O(11)
--R            6      120      5040      362880
--R                                        Type: TaylorSeries(Fraction(Integer))
--E 4

--S 5 of 10
coefficient(t1,3)
--R
--R
--R          1  3
--R   (5)  - - x
--R          6
--R                                          Type: Polynomial(Fraction(Integer))
--E 5

--S 6 of 10
coefficient(t1,monomial(3,x)$IndexedExponents Symbol)
--R
--R
--R          1
--R   (6)  - -
--R          6
--R                                                        Type: Fraction(Integer)
--E 6

--S 7 of 10
t2:=sin(xts + yts)
--R
--R
--R   (7)
--R                   1  3   1    2   1  2    1  3
--R     (y + x) + (- - y  - - x y  - - x y - - x )
```

```
--R                 6      2        2       6
--R   +
--R       1   5    1    4    1  2 3    1  3 2    1  4     1   5
--R     (--- y  + -- x y  + -- x y  + -- x y  + -- x y + --- x )
--R      120      24        12        12        24       120
--R   +
--R     PAREN
--R              1   7    1     6    1   2 5    1   3 4    1   4 3    1   5 2
--R          - ---- y  - --- x y  - --- x y  - --- x y  - --- x y  - --- x y
--R            5040      720        240        144        144        240
--R        +
--R             1   6      1   7
--R          - --- x y - ---- x
--R            720       5040
--R   +
--R     PAREN
--R              1    9     1      8     1    2 7     1   3 6     1   4 5
--R          ------ y  + ----- x y  + ----- x y  + ---- x y  + ---- x y
--R          362880      40320        10080        4320        2880
--R        +
--R             1   5 4     1   6 3     1    7 2     1    8       1    9
--R          ---- x y  + ---- x y  + ----- x y  + ----- x y + ------ x
--R          2880        4320        10080        40320       362880
--R   +
--R     O(11)
--R                                        Type: TaylorSeries(Fraction(Integer))
--E 7

--S 8 of 10
coefficient(t2,3)
--R
--R
--R          1  3   1    2   1  2    1  3
--R   (8)  - - y  - - x y  - - x y - - x
--R          6      2        2       6
--R                                          Type: Polynomial(Fraction(Integer))
--E 8

--S 9 of 10
coefficient(t2,monomial(3,x)$IndexedExponents Symbol)
--R
--R
--R          1
--R   (9)  - -
--R          6
--R                                                     Type: Fraction(Integer)
--E 9

--S 10 of 10
polynomial(t2,5)
```

```
--R
--R
--R   (10)
--R      1   5    1    4     1  2   1  3     1  3   1    2     1  4   1  2
--R     --- y  + -- x y  + (-- x  - -)y  + (-- x  - - x)y  + (-- x  - - x  + 1)y
--R     120      24         12      6       12      2         24      2
--R   +
--R      1   5   1  3
--R     --- x  - - x  + x
--R     120      6
--R                                          Type: Polynomial(Fraction(Integer))
--E 10

)spool
)lisp (bye)
```

———-

— SparseMultivariateTaylorSeries.help —

```
=====================================================================
SparseMultivariateTaylorSeries examples
=====================================================================

Assume we have three variables which get expressed as sparse
multivariate taylor series.

  xts:=x::TaylorSeries Fraction Integer
  yts:=y::TaylorSeries Fraction Integer
  zts:=z::TaylorSeries Fraction Integer

These will cause traditional routines to expand in series form:

  t1:=sin(xts)

         1  3    1   5     1   7      1    9
     x - - x  + --- x  - ---- x  + ------ x  + O(11)
         6      120      5040      362880


We can ask for a specific coefficient, in this case, the coefficient
of the third power.

  coefficient(t1,3)

       1  3
     - - x
       6
```

And we can get that coefficient, expressed as a monomial.

```
  coefficient(t1,monomial(3,x)$IndexedExponents Symbol)

      1
    - -
      6
```

In a multivariate version we get a polynomial in x and y

```
  t2:=sin(xts + yts)

                 1  3   1    2   1  2    1  3
    (y + x) + (- - y  - - x y  - - x y - - x )
                 6      2        2       6
  +
     1   5    1    4    1  2 3    1  3 2    1  4     1   5
    (--- y  + -- x y  + -- x y  + -- x y  + -- x y + --- x )
     120      24        12        12        24       120
  +
    PAREN
             1   7    1     6    1   2 5    1   3 4    1   4 3    1   5 2
        - ---- y  - --- x y  - --- x y  - --- x y  - --- x y  - --- x y
          5040      720        240        144        144        240
       +
            1   6      1   7
        - --- x y - ---- x
          720       5040
  +
    PAREN
           1    9     1      8     1    2 7     1   3 6     1   4 5
        ------ y  + ----- x y  + ----- x y  + ---- x y  + ---- x y
        362880      40320        10080        4320        2880
       +
          1   5 4     1   6 3     1    7 2     1    8       1    9
        ---- x y  + ---- x y  + ----- x y  + ----- x y + ------ x
        2880        4320        10080        40320       362880
  +
    O(11)
```

We can ask for the third coefficient which is

```
  coefficient(t2,3)

      1  3   1    2   1  2    1  3
    - - y  - - x y  - - x y - - x
      6      2        2       6
```

```
And we can ask for the third coefficient of that coefficient in x

  coefficient(t2,monomial(3,x)$IndexedExponents Symbol)

      1
    - -
      6


And we can convert that result to a polynomial

  polynomial(t2,5)

     1   5    1    4     1  2   1  3     1  3   1    2     1  4   1  2
    --- y  + -- x y  + (-- x  - -)y  + (-- x  - - x)y  + (-- x  - - x  + 1)y
    120      24         12      6       12      2         24      2
   +
     1   5   1  3
    --- x  - - x  + x
    120      6

See Also:
o )show SparseMultivariateTaylorSeries
o )display op coefficient
```

20.15.1 SparseMultivariateTaylorSeries (SMTS)



See

⇒ “TaylorSeries” (TS) 21.3.1 on page 2638

Exports:

0	1	acos	acosh	acot
acoth	acsc	acsch	asec	asech
asin	asinh	associates?	atan	atanh
characteristic	charthRoot	coefficient	coerce	complete
cos	cosh	cot	coth	csc
csch	csubst	D	degree	differentiate
eval	exp	exquo	extend	fintegrate
hash	integrate	latex	leadingCoefficient	leadingMonomial
log	map	monomial	monomial?	nthRoot
one?	order	pi	pole?	polynomial
recip	reductum	sample	sec	sech
sin	sinh	sqrt	subtractIfCan	tan
tanh	unit?	unitCanonical	unitNormal	variables
zero?	?*?	?**?	?+?	?-?
-?	?=?	?^?	?~=?	

— domain SMTS SparseMultivariateTaylorSeries —

```
)abbrev domain SMTS SparseMultivariateTaylorSeries
++ Authors: William Burge, Stephen Watt, Clifton Williamson
++ Date Created: 15 August 1988
++ Date Last Updated: 18 May 1991
++ Basic Operations:
++ Related Domains:
++ Also See: UnivariateTaylorSeries
++ AMS Classifications:
++ Keywords: multivariate, Taylor, series
++ Examples:
++ References:
++ Description:
++ This domain provides multivariate Taylor series with variables
++ from an arbitrary ordered set.  A Taylor series is represented
++ by a stream of polynomials from the polynomial domain SMP.
++ The nth element of the stream is a form of degree n.  SMTS is an
++ internal domain.

SparseMultivariateTaylorSeries(Coef,Var,SMP):_
 Exports == Implementation where
  Coef : Ring
  Var  : OrderedSet
  SMP  : PolynomialCategory(Coef,IndexedExponents Var,Var)
  I   ==> Integer
  L   ==> List
  NNI ==> NonNegativeInteger
  OUT ==> OutputForm
  PS  ==> InnerTaylorSeries SMP
  RN  ==> Fraction Integer
  ST  ==> Stream
```

```
StS ==> Stream SMP
STT ==> StreamTaylorSeriesOperations SMP
STF ==> StreamTranscendentalFunctions SMP
ST2 ==> StreamFunctions2
ST3 ==> StreamFunctions3

Exports ==> MultivariateTaylorSeriesCategory(Coef,Var) with
  coefficient: (%,NNI) -> SMP
    ++ \spad{coefficient(s, n)} gives the terms of total degree n.
    ++
    ++X xts:=x::TaylorSeries Fraction Integer
    ++X t1:=sin(xts)
    ++X coefficient(t1,3)

  coerce: Var -> %
    ++ \spad{coerce(var)} converts a variable to a Taylor series
  coerce: SMP -> %
    ++ \spad{coerce(poly)} regroups the terms by total degree and forms
    ++ a series.
  "*":(SMP,%)->%
    ++\spad{smp*ts} multiplies a TaylorSeries by a monomial SMP.
  csubst:(L Var,L StS) -> (SMP -> StS)
    ++\spad{csubst(a,b)} is for internal use only

  if Coef has Algebra Fraction Integer then
    integrate: (%,Var,Coef) -> %
      ++\spad{integrate(s,v,c)} is the integral of s with respect
      ++ to v and having c as the constant of integration.
    fintegrate: (() -> %,Var,Coef) -> %
      ++\spad{fintegrate(f,v,c)} is the integral of \spad{f()} with respect
      ++ to v and having c as the constant of integration.
      ++ The evaluation of \spad{f()} is delayed.

Implementation ==> PS add

  Rep := StS -- Below we use the fact that Rep of PS is Stream SMP.
  extend(x,n) == extend(x,n + 1)$Rep
  complete x == complete(x)$Rep

  evalstream:(%,L Var,L SMP) -> StS
  evalstream(s:%,lv:(L Var),lsmp:(L SMP)):(ST SMP) ==
    scan(0,_+$SMP,
      map((z1:SMP):SMP+->eval(z1,lv,lsmp),s pretend StS))$ST2(SMP,SMP)

  addvariable:(Var,InnerTaylorSeries Coef) -> %
  addvariable(v,s) ==
    ints := integers(0)$STT pretend ST NNI
    map((n1:NNI,c2:Coef):SMP+->monomial(c2 :: SMP,v,n1)$SMP,
           ints,s pretend ST Coef)$ST3(NNI,Coef,SMP)
```

```
    -- We can extract a polynomial giving the terms of given total degree
    coefficient(s,n) == elt(s,n + 1)$Rep  -- 1-based indexing for streams

    -- Here we have to take into account that we reduce the degree of each
    -- term of the stream by a constant
    coefficient(s:%,lv:List Var,ln:List NNI):% ==
      map ((z1:SMP):SMP +-> coefficient(z1,lv,ln),rest(s,reduce(_+,ln)))

    -- the coefficient of a particular monomial:
    coefficient(s:%,m:IndexedExponents Var):Coef ==
      n:=leadingCoefficient(mon:=m)
      while not zero?(mon:=reductum mon) repeat
        n:=n+leadingCoefficient mon
      coefficient(coefficient(s,n),m)

--% creation of series

    coerce(r:Coef) == monom(r::SMP,0)$STT
    smp:SMP * p:% == (((smp) *  (p pretend Rep))$STT)pretend %
    r:Coef * p:% == (((r::SMP) *  (p pretend Rep))$STT)pretend %
    p:% * r:Coef == (((r::SMP) * ( p pretend Rep))$STT)pretend %
    mts(p:SMP):% ==
      (uv := mainVariable p) case "failed" => monom(p,0)$STT
      v := uv :: Var
      s : % := 0
      up := univariate(p,v)
      while not zero? up repeat
        s := s + monomial(1,v,degree up) * mts(leadingCoefficient up)
        up := reductum up
      s

    coerce(p:SMP) == mts p
    coerce(v:Var) == v :: SMP :: %

    monomial(r:%,v:Var,n:NNI) ==
      r * monom(monomial(1,v,n)$SMP,n)$STT

--% evaluation

    substvar: (SMP,L Var,L %) -> %
    substvar(p,vl,q) ==
      null vl => monom(p,0)$STT
      (uv := mainVariable p) case "failed" => monom(p,0)$STT
      v := uv :: Var
      v = first vl =>
        s : % := 0
        up := univariate(p,v)
        while not zero? up repeat
          c := leadingCoefficient up
          s := s + first q ** degree up * substvar(c,rest vl,rest q)
```

```
      up := reductum up
    s
  substvar(p,rest vl,rest q)

sortmfirst:(SMP,L Var,L %) -> %
sortmfirst(p,vl,q) ==
  nlv : L Var := sort((v1:Var,v2:Var):Boolean +-> v1 > v2,vl)
  nq : L % := [q position$(L Var) (i,vl) for i in nlv]
  substvar(p,nlv,nq)

csubst(vl,q) == (p1:SMP):StS+->sortmfirst(p1,vl,q pretend L(%)) pretend StS

restCheck(s:StS):StS ==
  -- checks that stream is null or first element is 0
  -- returns empty() or rest of stream
  empty? s => s
  not zero? frst s =>
    error "eval: constant coefficient should be 0"
  rst s

eval(s:%,v:L Var,q:L %) ==
  #v ^= #q =>
    error "eval: number of variables should equal number of values"
  nq : L StS := [restCheck(i pretend StS) for i in q]
  addiag(map(csubst(v,nq),s pretend StS)$ST2(SMP,StS))$STT pretend %

substmts(v:Var,p:SMP,q:%):% ==
  up := univariate(p,v)
  ss : % := 0
  while not zero? up repeat
    d:=degree up
    c:SMP:=leadingCoefficient up
    ss := ss + c* q ** d
    up := reductum up
  ss

substream(v:Var,p:SMP,q:StS):StS==
  substmts(v,p,q pretend %) pretend StS

comp1:(Var,StS,StS) -> StS
comp1(v,r,t)==
  addiag(map((p1:SMP):StS +-> substream(v,p1,t),r)$ST2(SMP,StS))$STT

comp(v:Var,s:StS,t:StS):StS == delay
  empty? s => s
  f := frst s; r : StS := rst s;
  empty? r => s
  empty? t => concat(f,comp1(v,r,empty()$StS))
  not zero? frst t =>
    error "eval: constant coefficient should be zero"
```

```
      concat(f,comp1(v,r,rst t))

    eval(s:%,v:Var,t:%) == comp(v,s pretend StS,t pretend StS)

--% differentiation and integration

    differentiate(s:%,v:Var):% ==
      empty? s => 0
      map((z1:SMP):SMP +-> differentiate(z1,v),rst s)

    if Coef has Algebra Fraction Integer then

      stream(x:%):Rep == x pretend Rep

      (x:%) ** (r:RN) == powern(r,stream x)$STT
      (r:RN) * (x:%)  ==
        map((z1:SMP):SMP +-> r*z1,stream x)$ST2(SMP,SMP) pretend %
      (x:%) * (r:RN)  ==
        map((z1:SMP):SMP +-> z1*r,stream x)$ST2(SMP,SMP) pretend %

      exp x == exp(stream x)$STF
      log x == log(stream x)$STF

      sin x == sin(stream x)$STF
      cos x == cos(stream x)$STF
      tan x == tan(stream x)$STF
      cot x == cot(stream x)$STF
      sec x == sec(stream x)$STF
      csc x == csc(stream x)$STF

      asin x == asin(stream x)$STF
      acos x == acos(stream x)$STF
      atan x == atan(stream x)$STF
      acot x == acot(stream x)$STF
      asec x == asec(stream x)$STF
      acsc x == acsc(stream x)$STF

      sinh x == sinh(stream x)$STF
      cosh x == cosh(stream x)$STF
      tanh x == tanh(stream x)$STF
      coth x == coth(stream x)$STF
      sech x == sech(stream x)$STF
      csch x == csch(stream x)$STF

      asinh x == asinh(stream x)$STF
      acosh x == acosh(stream x)$STF
      atanh x == atanh(stream x)$STF
      acoth x == acoth(stream x)$STF
      asech x == asech(stream x)$STF
      acsch x == acsch(stream x)$STF
```

```
    intsmp(v:Var,p: SMP): SMP ==
      up := univariate(p,v)
      ss : SMP := 0
      while not zero? up repeat
        d := degree up
        c := leadingCoefficient up
        ss := ss + inv((d+1) :: RN) * monomial(c,v,d+1)$SMP
        up := reductum up
      ss

    fintegrate(f,v,r) ==
      concat(r::SMP,delay map((z1:SMP):SMP +-> intsmp(v,z1),f() pretend StS))
    integrate(s,v,r) ==
      concat(r::SMP,map((z1:SMP):SMP +-> intsmp(v,z1),s pretend StS))

  -- If there is more than one term of the same order, group them.
  tout(p:SMP):OUT ==
    pe := p :: OUT
    monomial? p => pe
    paren pe

  showAll?: () -> Boolean
  -- check a global Lisp variable
  showAll?() == true

  coerce(s:%):OUT ==
    uu := s pretend Stream(SMP)
    empty? uu => (0$SMP) :: OUT
    n : NNI; count : NNI := _$streamCount$Lisp
    l : List OUT := empty()
    for n in 0..count while not empty? uu repeat
      if frst(uu) ^= 0 then l := concat(tout frst uu,l)
      uu := rst uu
    if showAll?() then
      for n in n.. while explicitEntries? uu and _
             not eq?(uu,rst uu) repeat
        if frst(uu) ^= 0 then l := concat(tout frst uu,l)
        uu := rst uu
    l :=
      explicitlyEmpty? uu => l
      eq?(uu,rst uu) and frst uu = 0 => l
      concat(prefix("0" :: OUT,[n :: OUT]),l)
    empty? l => (0$SMP) :: OUT
    reduce("+",reverse_! l)
  if Coef has Field then
       stream(x:%):Rep == x pretend Rep
       SF2==> StreamFunctions2
       p:% / r:Coef ==
         (map((z1:SMP):SMP +-> z1/$SMP r,stream p)$SF2(SMP,SMP)) pretend %
```

———-

— **SMTS.dotabb** —

```
"SMTS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SMTS"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"SMTS" -> "PFECAT"
```

———-

20.16 domain STBL SparseTable

— **SparseTable.input** —

```
)set break resume
)sys rm -f SparseTable.output
)spool SparseTable.output
)set message test on
)set message auto off
)clear all
--S 1 of 7
t: SparseTable(Integer, String, "Try again!") := table()
--R
--R
--R   (1)  table()
--R                                  Type: SparseTable(Integer,String,Try again!)
--E 1

--S 2 of 7
t.3 := "Number three"
--R
--R
--R   (2)  "Number three"
--R                                                              Type: String
--E 2

--S 3 of 7
t.4 := "Number four"
--R
--R
--R   (3)  "Number four"
--R                                                              Type: String
--E 3
```

```
--S 4 of 7
t.3
--R
--R
--R   (4)  "Number three"
--R                                                          Type: String
--E 4

--S 5 of 7
t.2
--R
--R
--R   (5)  "Try again!"
--R                                                          Type: String
--E 5

--S 6 of 7
keys t
--R
--R
--R   (6)  [4,3]
--R                                                 Type: List(Integer)
--E 6

--S 7 of 7
entries t
--R
--R
--R   (7)  ["Number four","Number three"]
--R                                                  Type: List(String)
--E 7
)spool
)lisp (bye)
```

———-

— SparseTable.help —

```
====================================================================
SparseTable examples
====================================================================

The SparseTable domain provides a general purpose table type with
default entries.

Here we create a table to save strings under integer keys.  The value
"Try again!" is returned if no other value has been stored for a key.
```

```
  t: SparseTable(Integer, String, "Try again!") := table()
    table()
                            Type: SparseTable(Integer,String,Try again!)

Entries can be stored in the table.

  t.3 := "Number three"
    "Number three"
                            Type: String

  t.4 := "Number four"
    "Number four"
                            Type: String

These values can be retrieved as usual, but if a look up fails the
default entry will be returned.

  t.3
    "Number three"
                            Type: String

  t.2
    "Try again!"
                            Type: String

To see which values are explicitly stored, the keys and entries
functions can be used.

  keys t
    [4,3]
                            Type: List Integer


  entries t
    ["Number four","Number three"]
                            Type: List String

If a specific table representation is required, the GeneralSparseTable
constructor should be used.  The domain SparseTable(K, E, dflt)} is
equivalent to GeneralSparseTable(K,E,Table(K,E), dflt).

See Also:
o )help Table
o )help GeneralSparseTable
o )show SparseTable
```

———-

20.16.1 SparseTable (STBL)



See

⇒ "HashTable" (HASHTBL) 9.1.1 on page 1089
⇒ "InnerTable" (INTABL) 10.27.1 on page 1303
⇒ "Table" (TABLE) 21.1.1 on page 2631
⇒ "EqTable" (EQTBL) 6.2.1 on page 669
⇒ "StringTable" (STRTBL) 20.32.1 on page 2578
⇒ "GeneralSparseTable" (GSTBL) 8.5.1 on page 1048

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	elt	empty
empty?	entries	entry?	eq?	eval
every?	extract!	fill!	find	first
hash	index?	indices	insert!	inspect
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
setelt	select	select!	size?	swap!
table	#?	?=?	?~=?	?.?

— domain STBL SparseTable —

```
)abbrev domain STBL SparseTable
++ Author: Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: June 21, 1991
++ Basic Operations:
++ Related Domains: Table
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
```

```
++ A sparse table has a default entry, which is returned if no other
++ value has been explicitly stored for a key.

SparseTable(Key:SetCategory, Ent:SetCategory, dent:Ent) ==
        GeneralSparseTable(Key, Ent, Table(Key, Ent), dent)
```

———-

— **STBL.dotabb** —

```
"STBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STBL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"STBL" -> "TBAGG"
```

———-

20.17 domain SULS SparseUnivariateLaurentSeries

— **SparseUnivariateLaurentSeries.input** —

```
)set break resume
)sys rm -f SparseUnivariateLaurentSeries.output
)spool SparseUnivariateLaurentSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseUnivariateLaurentSeries
--R
--R SparseUnivariateLaurentSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for SparseUnivariateLaurentSeries is SULS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SULS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coefficient : (%,Integer) -> Coef    coerce : Variable(var) -> %
```

```
--R coerce : Integer -> %                coerce : % -> OutputForm
--R complete : % -> %                    degree : % -> Integer
--R ?.? : (%,Integer) -> Coef            extend : (%,Integer) -> %
--R hash : % -> SingleInteger            latex : % -> String
--R leadingCoefficient : % -> Coef       leadingMonomial : % -> %
--R map : ((Coef -> Coef),%) -> %        monomial : (Coef,Integer) -> %
--R monomial? : % -> Boolean             one? : % -> Boolean
--R order : (%,Integer) -> Integer       order : % -> Integer
--R pole? : % -> Boolean                 recip : % -> Union(%,"failed")
--R reductum : % -> %                    removeZeroes : (Integer,%) -> %
--R removeZeroes : % -> %                sample : () -> %
--R truncate : (%,Integer) -> %          variable : % -> Symbol
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (SparseUnivariateTaylorSeries(Coef,var,cen),%) -> % if Coef has FIELD
--R ?*? : (%,SparseUnivariateTaylorSeries(Coef,var,cen)) -> % if Coef has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (SparseUnivariateTaylorSeries(Coef,var,cen),SparseUnivariateTaylorSeries(Coef,var,cen)
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R ?<? : (%,%) -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef ha
--R ?<=? : (%,%) -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef h
--R ?>? : (%,%) -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef ha
--R ?>=? : (%,%) -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef h
--R D : (%,Symbol) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) and Coe
--R D : (%,List(Symbol)) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) a
--R D : (%,Symbol,NonNegativeInteger) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has PDR
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if SparseUnivariateTaylorSeries(Coef,var,
--R D : % -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has DIFRING and Coef has FIELD or C
--R D : (%,NonNegativeInteger) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has DIFRING an
--R D : (%,(SparseUnivariateTaylorSeries(Coef,var,cen) -> SparseUnivariateTaylorSeries(Coef,var,
--R D : (%,(SparseUnivariateTaylorSeries(Coef,var,cen) -> SparseUnivariateTaylorSeries(Coef,var,
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Integer) -> Coef if Coef has **: (Coef,Integer) -> Coef and Coef has coerce
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FI
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R ceiling : % -> SparseUnivariateTaylorSeries(Coef,var,cen) if SparseUnivariateTaylorSeries(Coef,var,cen)
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and SparseUnivariateTaylorSeries(Coef,var,cen) has
--R coerce : Fraction(Integer) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(INT) and Coef
--R coerce : % -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or SparseU
--R coerce : Symbol -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(SYMBOL) and Coef has FIE
--R coerce : SparseUnivariateTaylorSeries(Coef,var,cen) -> %
--R coerce : Coef -> % if Coef has COMRING
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and SparseUnivariateTaylorSeries(Co
--R convert : % -> Pattern(Integer) if SparseUnivariateTaylorSeries(Coef,var,cen) has KONVERT(PATTERN(INT))
--R convert : % -> Pattern(Float) if SparseUnivariateTaylorSeries(Coef,var,cen) has KONVERT(PATTERN(FLOAT))
--R convert : % -> DoubleFloat if SparseUnivariateTaylorSeries(Coef,var,cen) has REAL and Coef has FIELD
--R convert : % -> Float if SparseUnivariateTaylorSeries(Coef,var,cen) has REAL and Coef has FIELD
--R convert : % -> InputForm if SparseUnivariateTaylorSeries(Coef,var,cen) has KONVERT(INFORM) and Coef has
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R denom : % -> SparseUnivariateTaylorSeries(Coef,var,cen) if Coef has FIELD
--R denominator : % -> % if Coef has FIELD
--R differentiate : (%,Symbol) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) and Co
--R differentiate : (%,List(Symbol)) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has PD
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if SparseUnivariateTaylorSeries(Coef,var
--R differentiate : % -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has DIFRING and Coef has FIELD or
--R differentiate : (%,NonNegativeInteger) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has DIFRING a
--R differentiate : (%,Variable(var)) -> %
--R differentiate : (%,(SparseUnivariateTaylorSeries(Coef,var,cen) -> SparseUnivariateTaylorSeries(Coef,var
--R differentiate : (%,(SparseUnivariateTaylorSeries(Coef,var,cen) -> SparseUnivariateTaylorSeries(Coef,var
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,SparseUnivariateTaylorSeries(Coef,var,cen)) -> % if SparseUnivariateTaylorSeries(Coef,var,cen)
--R ?.? : (%,%) -> % if Integer has SGROUP
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,List(SparseUnivariateTaylorSeries(Coef,var,cen)),List(SparseUnivariateTaylorSeries(Coef,var,c
--R eval : (%,SparseUnivariateTaylorSeries(Coef,var,cen),SparseUnivariateTaylorSeries(Coef,var,cen)) -> % i
--R eval : (%,Equation(SparseUnivariateTaylorSeries(Coef,var,cen))) -> % if SparseUnivariateTaylorSeries(Co
--R eval : (%,List(Equation(SparseUnivariateTaylorSeries(Coef,var,cen)))) -> % if SparseUnivariateTaylorSeri
--R eval : (%,List(Symbol),List(SparseUnivariateTaylorSeries(Coef,var,cen))) -> % if SparseUnivariateTaylorS
--R eval : (%,Symbol,SparseUnivariateTaylorSeries(Coef,var,cen)) -> % if SparseUnivariateTaylorSeries(Coef,
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Integer) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef ha
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
```

```
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R floor : % -> SparseUnivariateTaylorSeries(Coef,var,cen) if SparseUnivariateTaylorSeries(Coef
--R fractionPart : % -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has EUCDOM and Coef has
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R init : () -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has STEP and Coef has FIELD
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variab
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R laurent : (Integer,SparseUnivariateTaylorSeries(Coef,var,cen)) -> %
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R map : ((SparseUnivariateTaylorSeries(Coef,var,cen) -> SparseUnivariateTaylorSeries(Coef,var,
--R max : (%,%) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIEL
--R min : (%,%) -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIEL
--R monomial : (%,List(SingletonAsOrderedSet),List(Integer)) -> %
--R monomial : (%,SingletonAsOrderedSet,Integer) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R negative? : % -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef
--R nextItem : % -> Union(%,"failed") if SparseUnivariateTaylorSeries(Coef,var,cen) has STEP and
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R numer : % -> SparseUnivariateTaylorSeries(Coef,var,cen) if Coef has FIELD
--R numerator : % -> % if Coef has FIELD
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R positive? : % -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R ?quo? : (%,%) -> % if Coef has FIELD
--R random : () -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has INS and Coef has FIELD
--R rationalFunction : (%,Integer,Integer) -> Fraction(Polynomial(Coef)) if Coef has INTDOM
--R rationalFunction : (%,Integer) -> Fraction(Polynomial(Coef)) if Coef has INTDOM
--R reducedSystem : Matrix(%) -> Matrix(Integer) if SparseUnivariateTaylorSeries(Coef,var,cen) h
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(SparseUnivariateTaylorSeries(Coe
--R reducedSystem : Matrix(%) -> Matrix(SparseUnivariateTaylorSeries(Coef,var,cen)) if Coef has
--R ?rem? : (%,%) -> % if Coef has FIELD
--R retract : % -> Integer if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(INT) and Co
--R retract : % -> Fraction(Integer) if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(I
--R retract : % -> Symbol if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(SYMBOL) and
--R retract : % -> SparseUnivariateTaylorSeries(Coef,var,cen)
```

```
--R retractIfCan : % -> Union(Integer,"failed") if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(I
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if SparseUnivariateTaylorSeries(Coef,var,cen) has
--R retractIfCan : % -> Union(Symbol,"failed") if SparseUnivariateTaylorSeries(Coef,var,cen) has RETRACT(SY
--R retractIfCan : % -> Union(SparseUnivariateTaylorSeries(Coef,var,cen),"failed")
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: Integer,c: Coef)) -> %
--R sign : % -> Integer if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if Coef has FIELD
--R squareFreePart : % -> % if Coef has FIELD
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if Spars
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R taylor : % -> SparseUnivariateTaylorSeries(Coef,var,cen)
--R taylorIfCan : % -> Union(SparseUnivariateTaylorSeries(Coef,var,cen),"failed")
--R taylorRep : % -> SparseUnivariateTaylorSeries(Coef,var,cen)
--R terms : % -> Stream(Record(k: Integer,c: Coef))
--R truncate : (%,Integer,Integer) -> %
--R unit? : % -> Boolean if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or Spa
--R unitCanonical : % -> % if SparseUnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or S
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if SparseUnivariateTaylorSeries(Coef,var,cen
--R variables : % -> List(SingletonAsOrderedSet)
--R wholePart : % -> SparseUnivariateTaylorSeries(Coef,var,cen) if SparseUnivariateTaylorSeries(Coef,var,cen
--R
--E 1

)spool
)lisp (bye)
```

———-


— SparseUnivariateLaurentSeries.help —

```
=====================================================================
SparseUnivariateLaurentSeries examples
=====================================================================

See Also:
o )show SparseUnivariateLaurentSeries
```

———-

20.17.1 SparseUnivariateLaurentSeries (SULS)



Exports:

0	1	abs
acos	acosh	acot
acoth	acsc	acsch
approximate	asec	asech
asin	asinh	associates?
atan	atanh	ceiling
characteristic	charthRoot	center
coefficient	coerce	complete
conditionP	convert	cos
cosh	cot	coth
csc	csch	D
degree	denom	denominator
differentiate	divide	euclideanSize
eval	exp	expressIdealMember
exquo	extend	extendedEuclidean
factor	factorPolynomial	factorSquareFreePolynomial
floor	fractionPart	gcd
gcdPolynomial	hash	init
integrate	inv	latex
laurent	lcm	leadingCoefficient
leadingMonomial	log	map
max	min	monomial
monomial?	multiEuclidean	multiplyCoefficients
multiplyExponents	negative?	nextItem
nthRoot	numer	numerator
one?	order	patternMatch
pi	pole?	positive?
prime?	principalIdeal	random
rationalFunction	recip	reducedSystem
reductum	removeZeroes	retract
retractIfCan	sample	sec
sech	series	sign
sin	sinh	sizeLess?
solveLinearPolynomialEquation	sqrt	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
tan	tanh	taylor
taylorIfCan	taylorRep	terms
truncate	unit?	unitCanonical
unitNormal	variable	variables
wholePart	zero?	?*?
?**?	?+?	?-?
-?	?=?	?^?
?.?	?~=?	?/?
?<?	?<=?	?>?
?>=?	?^?	?quo?
?rem?		

— domain SULS SparseUnivariateLaurentSeries —

```
)abbrev domain SULS SparseUnivariateLaurentSeries
++ Author: Clifton J. Williamson
++ Date Created: 11 November 1994
++ Date Last Updated: 10 March 1995
++ Basic Operations:
++ Related Domains: InnerSparseUnivariatePowerSeries,
++   SparseUnivariateTaylorSeries, SparseUnivariatePuiseuxSeries
++ Also See:
++ AMS Classifications:
++ Keywords: sparse, series
++ Examples:
++ References:
++ Description:
++ Sparse Laurent series in one variable
++ \spadtype{SparseUnivariateLaurentSeries} is a domain representing Laurent
++ series in one variable with coefficients in an arbitrary ring.  The
++ parameters of the type specify the coefficient ring, the power series
++ variable, and the center of the power series expansion.  For example,
++ \spad{SparseUnivariateLaurentSeries(Integer,x,3)} represents Laurent
++ series in \spad{(x - 3)} with integer coefficients.

SparseUnivariateLaurentSeries(Coef,var,cen): Exports == Implementation where
  Coef : Ring
  var  : Symbol
  cen  : Coef
  I     ==> Integer
  NNI   ==> NonNegativeInteger
  OUT   ==> OutputForm
  P     ==> Polynomial Coef
  RF    ==> Fraction Polynomial Coef
  RN    ==> Fraction Integer
  S     ==> String
  SUTS  ==> SparseUnivariateTaylorSeries(Coef,var,cen)
  EFULS ==> ElementaryFunctionsUnivariateLaurentSeries(Coef,SUTS,%)

  Exports ==> UnivariateLaurentSeriesConstructorCategory(Coef,SUTS) with
    coerce: Variable(var) -> %
      ++ \spad{coerce(var)} converts the series variable \spad{var} into a
      ++ Laurent series.
    differentiate: (%,Variable(var)) -> %
      ++ \spad{differentiate(f(x),x)} returns the derivative of
      ++ \spad{f(x)} with respect to \spad{x}.
    if Coef has Algebra Fraction Integer then
      integrate: (%,Variable(var)) -> %
        ++ \spad{integrate(f(x))} returns an anti-derivative of the power
        ++ series \spad{f(x)} with constant coefficient 0.
        ++ We may integrate a series when we can divide coefficients
```

```
        ++ by integers.

  Implementation ==> InnerSparseUnivariatePowerSeries(Coef) add

    Rep := InnerSparseUnivariatePowerSeries(Coef)

    variable x == var
    center   x == cen

    coerce(v: Variable(var)) ==
      zero? cen => monomial(1,1)
      monomial(1,1) + monomial(cen,0)

    pole? x == negative? order(x,0)

--% operations with Taylor series

    coerce(uts:SUTS) == uts pretend %

    taylorIfCan uls ==
      pole? uls => "failed"
      uls pretend SUTS

    taylor uls ==
      (uts := taylorIfCan uls) case "failed" =>
        error "taylor: Laurent series has a pole"
      uts :: SUTS

    retractIfCan(x:%):Union(SUTS,"failed") == taylorIfCan x

    laurent(n,uts) == monomial(1,n) * (uts :: %)

    removeZeroes uls    == uls
    removeZeroes(n,uls) == uls

    taylorRep uls == taylor(monomial(1,-order(uls,0)) * uls)
    degree uls    == order(uls,0)

    numer uls == taylorRep uls
    denom uls == monomial(1,(-order(uls,0)) :: NNI)$SUTS

    (uts:SUTS) * (uls:%) == (uts :: %) * uls
    (uls:%) * (uts:SUTS) == uls * (uts :: %)

    if Coef has Field then
      (uts1:SUTS) / (uts2:SUTS) == (uts1 :: %) / (uts2 :: %)

    recip(uls) == iExquo(1,uls,false)

    if Coef has IntegralDomain then
```

```
    uls1 exquo uls2 == iExquo(uls1,uls2,false)

  if Coef has Field then
    uls1:% / uls2:% ==
      (q := uls1 exquo uls2) case "failed" =>
        error "quotient cannot be computed"
      q :: %

  differentiate(uls:%,v:Variable(var)) == differentiate uls

  elt(uls1:%,uls2:%) ==
    order(uls2,1) < 1 =>
      error "elt: second argument must have positive order"
    negative?(ord := order(uls1,0)) =>
      (recipr := recip uls2) case "failed" =>
        error "elt: second argument not invertible"
      uls3 := uls1 * monomial(1,-ord)
      iCompose(uls3,uls2) * (recipr :: %) ** ((-ord) :: NNI)
    iCompose(uls1,uls2)

  if Coef has IntegralDomain then
    rationalFunction(uls,n) ==
      zero?(e := order(uls,0)) =>
        negative? n => 0
        polynomial(taylor uls,n :: NNI) :: RF
      negative?(m := n - e) => 0
      poly := polynomial(taylor(monomial(1,-e) * uls),m :: NNI) :: RF
      v := variable(uls) :: RF; c := center(uls) :: P :: RF
      poly / (v - c) ** ((-e) :: NNI)

    rationalFunction(uls,n1,n2) == rationalFunction(truncate(uls,n1,n2),n2)

  if Coef has Algebra Fraction Integer then

    integrate uls ==
      zero? coefficient(uls,-1) =>
        error "integrate: series has term of order -1"
      integrate(uls)$Rep

    integrate(uls:%,v:Variable(var)) == integrate uls

    (uls1:%) ** (uls2:%) == exp(log(uls1) * uls2)

    exp uls   == exp(uls)$EFULS
    log uls   == log(uls)$EFULS
    sin uls   == sin(uls)$EFULS
    cos uls   == cos(uls)$EFULS
    tan uls   == tan(uls)$EFULS
    cot uls   == cot(uls)$EFULS
    sec uls   == sec(uls)$EFULS
```

```
      csc uls   == csc(uls)$EFULS
      asin uls  == asin(uls)$EFULS
      acos uls  == acos(uls)$EFULS
      atan uls  == atan(uls)$EFULS
      acot uls  == acot(uls)$EFULS
      asec uls  == asec(uls)$EFULS
      acsc uls  == acsc(uls)$EFULS
      sinh uls  == sinh(uls)$EFULS
      cosh uls  == cosh(uls)$EFULS
      tanh uls  == tanh(uls)$EFULS
      coth uls  == coth(uls)$EFULS
      sech uls  == sech(uls)$EFULS
      csch uls  == csch(uls)$EFULS
      asinh uls == asinh(uls)$EFULS
      acosh uls == acosh(uls)$EFULS
      atanh uls == atanh(uls)$EFULS
      acoth uls == acoth(uls)$EFULS
      asech uls == asech(uls)$EFULS
      acsch uls == acsch(uls)$EFULS

      if Coef has CommutativeRing then

        (uls:%) ** (r:RN) == cRationalPower(uls,r)

      else

        (uls:%) ** (r:RN) ==
          negative?(ord0 := order(uls,0)) =>
            order := ord0 :: I
            (n := order exquo denom(r)) case "failed" =>
              error "**: rational power does not exist"
            uts := retract(uls * monomial(1,-order))@SUTS
            utsPow := (uts ** r) :: %
            monomial(1,(n :: I) * numer(r)) * utsPow
          uts := retract(uls)@SUTS
          (uts ** r) :: %

--% OutputForms

    coerce(uls:%): OUT ==
      st := getStream uls
      if not(explicitlyEmpty? st or explicitEntries? st) _
        and (nx := retractIfCan(elt getRef uls))@Union(I,"failed") case I then
        count : NNI := _$streamCount$Lisp
        degr := min(count,(nx :: I) + count + 1)
        extend(uls,degr)
      seriesToOutputForm(st,getRef uls,variable uls,center uls,1)
```

———-

— **SULS.dotabb** —

```
"SULS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SULS"]
"ULSCCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ULSCCAT"]
"SULS" -> "ULSCCAT"
```

———-

20.18 domain SUP SparseUnivariatePolynomial

— **SparseUnivariatePolynomial.input** —

```
)set break resume
)sys rm -f SparseUnivariatePolynomial.output
)spool SparseUnivariatePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseUnivariatePolynomial
--R SparseUnivariatePolynomial R: Ring  is a domain constructor
--R Abbreviation for SparseUnivariatePolynomial is SUP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SUP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> %
--R D : (%,NonNegativeInteger) -> %       1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coefficients : % -> List R            coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      differentiate : % -> %
--R ?.? : (%,%) -> %                      ?.? : (%,R) -> R
--R eval : (%,List %,List %) -> %         eval : (%,%,%) -> %
--R eval : (%,Equation %) -> %            eval : (%,List Equation %) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             init : () -> % if R has STEP
--R latex : % -> String                   leadingCoefficient : % -> R
--R leadingMonomial : % -> %              map : ((R -> R),%) -> %
```

```
--R monomial? : % -> Boolean              monomials : % -> List %
--R one? : % -> Boolean                   primitiveMonomials : % -> List %
--R pseudoRemainder : (%,%) -> %          recip : % -> Union(%,"failed")
--R reductum : % -> %                     retract : % -> R
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction Integer,%) -> % if R has ALGEBRA FRAC INT
--R ?*? : (%,Fraction Integer) -> % if R has ALGEBRA FRAC INT
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List Symbol,List NonNegativeInteger) -> % if R has PDRING SYMBOL
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING SYMBOL
--R D : (%,List Symbol) -> % if R has PDRING SYMBOL
--R D : (%,Symbol) -> % if R has PDRING SYMBOL
--R D : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R D : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R D : (%,List SingletonAsOrderedSet) -> %
--R D : (%,SingletonAsOrderedSet) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
--R coefficient : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R coefficient : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction Integer -> % if R has ALGEBRA FRAC INT or R has RETRACT FRAC INT
--R coerce : SingletonAsOrderedSet -> %
--R composite : (Fraction %,%) -> Union(Fraction %,"failed") if R has INTDOM
--R composite : (%,%) -> Union(%,"failed") if R has INTDOM
--R conditionP : Matrix % -> Union(Vector %,"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SingletonAsOrderedSet has KONVERT INFORM and R has KONVERT INFORM
--R convert : % -> Pattern Integer if SingletonAsOrderedSet has KONVERT PATTERN INT and R has KONVERT PATTE
--R convert : % -> Pattern Float if SingletonAsOrderedSet has KONVERT PATTERN FLOAT and R has KONVERT PATTE
--R degree : (%,List SingletonAsOrderedSet) -> List NonNegativeInteger
--R degree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R differentiate : (%,(R -> R),%) -> %
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List Symbol,List NonNegativeInteger) -> % if R has PDRING SYMBOL
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING SYMBOL
```

```
--R differentiate : (%,List Symbol) -> % if R has PDRING SYMBOL
--R differentiate : (%,Symbol) -> % if R has PDRING SYMBOL
--R differentiate : (%,NonNegativeInteger) -> %
--R differentiate : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R differentiate : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R differentiate : (%,List SingletonAsOrderedSet) -> %
--R differentiate : (%,SingletonAsOrderedSet) -> %
--R discriminant : % -> R if R has COMRING
--R discriminant : (%,SingletonAsOrderedSet) -> % if R has COMRING
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R divideExponents : (%,NonNegativeInteger) -> Union(%,"failed")
--R ?.? : (%,Fraction %) -> Fraction % if R has INTDOM
--R elt : (Fraction %,R) -> R if R has FIELD
--R elt : (Fraction %,Fraction %) -> Fraction % if R has INTDOM
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R eval : (%,List SingletonAsOrderedSet,List %) -> %
--R eval : (%,SingletonAsOrderedSet,%) -> %
--R eval : (%,List SingletonAsOrderedSet,List R) -> %
--R eval : (%,SingletonAsOrderedSet,R) -> %
--R expressIdealMember : (List %,%) -> Union(List %,"failed") if R has FIELD
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R factor : % -> Factored % if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial % if
--R factorSquareFreePolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolyno
--R fmecg : (%,NonNegativeInteger,R,%) -> %
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List % -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> SparseUnivari
--R integrate : % -> % if R has ALGEBRA FRAC INT
--R isExpt : % -> Union(Record(var: SingletonAsOrderedSet,exponent: NonNegativeInteger),"failed"
--R isPlus : % -> Union(List %,"failed")
--R isTimes : % -> Union(List %,"failed")
--R karatsubaDivide : (%,NonNegativeInteger) -> Record(quotient: %,remainder: %)
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List % -> % if R has GCDDOM
--R mainVariable : % -> Union(SingletonAsOrderedSet,"failed")
--R makeSUP : % -> SparseUnivariatePolynomial R
--R mapExponents : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List SingletonAsOrderedSet) -> List NonNegativeInteger
--R minimumDegree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R minimumDegree : % -> NonNegativeInteger
--R monicDivide : (%,%) -> Record(quotient: %,remainder: %)
--R monicDivide : (%,%,SingletonAsOrderedSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List SingletonAsOrderedSet,List NonNegativeInteger) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
```

```
--R monomial : (R,NonNegativeInteger) -> %
--R multiEuclidean : (List %,%) -> Union(List %,"failed") if R has FIELD
--R multiplyExponents : (%,NonNegativeInteger) -> %
--R multivariate : (SparseUnivariatePolynomial %,SingletonAsOrderedSet) -> %
--R multivariate : (SparseUnivariatePolynomial R,SingletonAsOrderedSet) -> %
--R nextItem : % -> Union(%,"failed") if R has STEP
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,%) -> NonNegativeInteger if R has INTDOM
--R outputForm : (%,OutputForm) -> OutputForm
--R patternMatch : (%,Pattern Integer,PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if Si
--R patternMatch : (%,Pattern Float,PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if Singleto
--R pomopo! : (%,R,NonNegativeInteger,%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitivePart : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R principalIdeal : List % -> Record(coef: List %,generator: %) if R has FIELD
--R pseudoDivide : (%,%) -> Record(coef: R,quotient: %,remainder: %) if R has INTDOM
--R pseudoQuotient : (%,%) -> % if R has INTDOM
--R ?quo? : (%,%) -> % if R has FIELD
--R reducedSystem : Matrix % -> Matrix R
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix R,vec: Vector R)
--R reducedSystem : (Matrix %,Vector %) -> Record(mat: Matrix Integer,vec: Vector Integer) if R has LINEXP
--R reducedSystem : Matrix % -> Matrix Integer if R has LINEXP INT
--R ?rem? : (%,%) -> % if R has FIELD
--R resultant : (%,%) -> R if R has COMRING
--R resultant : (%,%,SingletonAsOrderedSet) -> % if R has COMRING
--R retract : % -> SingletonAsOrderedSet
--R retract : % -> Integer if R has RETRACT INT
--R retract : % -> Fraction Integer if R has RETRACT FRAC INT
--R retractIfCan : % -> Union(SingletonAsOrderedSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT INT
--R retractIfCan : % -> Union(Fraction Integer,"failed") if R has RETRACT FRAC INT
--R retractIfCan : % -> Union(R,"failed")
--R separate : (%,%) -> Record(primePart: %,commonPart: %) if R has GCDDOM
--R shiftLeft : (%,NonNegativeInteger) -> %
--R shiftRight : (%,NonNegativeInteger) -> %
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R solveLinearPolynomialEquation : (List SparseUnivariatePolynomial %,SparseUnivariatePolynomial %) -> Uni
--R squareFree : % -> Factored % if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial % -> Factored SparseUnivariatePolynomial % if R has P
--R subResultantGcd : (%,%) -> % if R has INTDOM
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R totalDegree : (%,List SingletonAsOrderedSet) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial R
--R univariate : (%,SingletonAsOrderedSet) -> SparseUnivariatePolynomial %
```

```
--R unmakeSUP : SparseUnivariatePolynomial R -> %
--R variables : % -> List SingletonAsOrderedSet
--R vectorise : (%,NonNegativeInteger) -> Vector R
--R
--E 1

)spool
)lisp (bye)
```

———-


— **SparseUnivariatePolynomial.help** —

```
=====================================================================
SparseUnivariatePolynomial examples
=====================================================================

See Also:
o )show SparseUnivariatePolynomial
```

———-

20.18.1 SparseUnivariatePolynomial (SUP)



See

⇒ “FreeModule” (FM) 7.30.1 on page 983
⇒ “PolynomialRing” (PR) 17.27.1 on page 2058
⇒ “UnivariatePolynomial” (UP) 22.4.1 on page 2794

Exports:

0	1
associates?	binomThmExpt
characteristic	charthRoot
coefficient	coefficients
coerce	composite
conditionP	content
convert	D
degree	differentiate
discriminant	divide
divideExponents	elt
euclideanSize	eval
expressIdealMember	exquo
extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial
fmecg	gcd
gcdPolynomial	ground
ground?	hash
init	integrate
isExpt	isPlus
isTimes	karatsubaDivide
latex	lcm
leadingCoefficient	leadingMonomial
mainVariable	makeSUP
map	mapExponents
max	min
minimumDegree	monicDivide
monomial	monomial?
monomials	multiEuclidean
multiplyExponents	multivariate
nextItem	numberOfMonomials
one?	order
outputForm	patternMatch
pomopo!	prime?
primitiveMonomials	primitivePart
principalIdeal	pseudoDivide
pseudoQuotient	pseudoRemainder
recip	reducedSystem
reductum	resultant
retract	retractIfCan
sample	separate
shiftLeft	shiftRight
sizeLess?	solveLinearPolynomialEquation
squareFree	squareFreePart
squareFreePolynomial	subResultantGcd
subtractIfCan	totalDegree
totalDegree	unit?
unitCanonical	unitNormal
univariate	univariate
unmakeSUP	variables
vectorise	zero?
?*?	?**?
?+?	?-?
-?	?=?
?^?	?.?
?~=?	?/?

— domain SUP SparseUnivariatePolynomial —

```
)abbrev domain SUP SparseUnivariatePolynomial
++ Author: Dave Barton, Barry Trager
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, monomial, coefficient, reductum, differentiate,
++ elt, map, resultant, discriminant
++ Related Constructors: UnivariatePolynomial, Polynomial
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain represents univariate polynomials over arbitrary
++ (not necessarily commutative) coefficient rings. The variable is
++ unspecified  so that the variable displays as \spad{?} on output.
++ If it is necessary to specify the variable name, use type \spadtype{UnivariatePolynomial}.
++ The representation is sparse
++ in the sense that only non-zero terms are represented.
++ Note that if the coefficient ring is a field, this domain forms a euclidean domain.

SparseUnivariatePolynomial(R:Ring): UnivariatePolynomialCategory(R) with
     outputForm : (%,OutputForm) -> OutputForm
        ++ outputForm(p,var) converts the SparseUnivariatePolynomial p to
        ++ an output form (see \spadtype{OutputForm}) printed as a polynomial in the
        ++ output form variable.
     fmecg: (%,NonNegativeInteger,R,%) -> %
        ++ fmecg(p1,e,r,p2) finds x : p1 - r * x**e * p2
    == PolynomialRing(R,NonNegativeInteger)
  add
   --representations
   Term := Record(k:NonNegativeInteger,c:R)
   Rep  := List Term
   p:%
   n:NonNegativeInteger
   np: PositiveInteger
   FP ==> SparseUnivariatePolynomial %
   pp,qq: FP
   lpp:List FP

   -- for karatsuba
   kBound: NonNegativeInteger := 63
   upmp := UnivariatePolynomialMultiplicationPackage(R,%)


   if R has FieldOfPrimeCharacteristic  then
         p ** np == p ** (np pretend NonNegativeInteger)
         p ^ np  == p ** (np pretend NonNegativeInteger)
```

```
        p ^ n  == p ** n
        p ** n  ==
           null p => 0
           zero? n => 1
--           one? n => p
           (n = 1) => p
           empty? p.rest =>
             zero?(cc:=p.first.c ** n) => 0
             [[n * p.first.k, cc]]
           -- not worth doing special trick if characteristic is too small
           if characteristic()$R < 3 then return expt(p,n pretend PositiveInteger)$RepeatedSquaring(%)
           y:%:=1
           -- break up exponent in qn * characteristic + rn
           -- exponentiating by the characteristic is fast
           rec := divide(n, characteristic()$R)
           qn:= rec.quotient
           rn:= rec.remainder
           repeat
               if rn = 1 then y := y * p
               if rn > 1 then y:= y * binomThmExpt([p.first], p.rest, rn)
               zero? qn => return y
               -- raise to the characteristic power
               p:= [[t.k * characteristic()$R , primeFrobenius(t.c)$R ]$Term for t in p]
               rec := divide(qn, characteristic()$R)
               qn:= rec.quotient
               rn:= rec.remainder
           y



   zero?(p): Boolean == empty?(p)
--   one?(p):Boolean == not empty? p and (empty? rest p and zero? first(p).k and one? first(p).c)
   one?(p):Boolean == not empty? p and (empty? rest p and zero? first(p).k and (first(p).c = 1))
   ground?(p): Boolean == empty? p or (empty? rest p and zero? first(p).k)
   multiplyExponents(p,n) == [ [u.k*n,u.c] for u in p]
   divideExponents(p,n) ==
     null p => p
     m:= (p.first.k :: Integer exquo n::Integer)
     m case "failed" => "failed"
     u:= divideExponents(p.rest,n)
     u case "failed" => "failed"
     [[m::Integer::NonNegativeInteger,p.first.c],:u]
   karatsubaDivide(p, n)  ==
     zero? n => [p, 0]
     lowp: Rep := p
     highp: Rep := []
     repeat
       if empty? lowp then break
       t := first lowp
       if t.k < n then break
```

```
      lowp := rest lowp
      highp := cons([subtractIfCan(t.k,n)::NonNegativeInteger,t.c]$Term,highp)
    [ reverse highp,  lowp]
  shiftRight(p, n)  ==
     [[subtractIfCan(t.k,n)::NonNegativeInteger,t.c]$Term for t in p]
  shiftLeft(p, n)  ==
     [[t.k + n,t.c]$Term for t in p]
  pomopo!(p1,r,e,p2) ==
        rout:%:= []
        for tm in p2 repeat
           e2:= e + tm.k
           c2:= r * tm.c
           c2 = 0 => "next term"
           while not null p1 and p1.first.k > e2 repeat
             (rout:=[p1.first,:rout]; p1:=p1.rest)  --use PUSH and POP?
           null p1 or p1.first.k < e2 => rout:=[[e2,c2],:rout]
           if (u:=p1.first.c + c2) ^= 0 then rout:=[[e2, u],:rout]
           p1:=p1.rest
        NRECONC(rout,p1)$Lisp

-- implementation using karatsuba algorithm conditionally
--
--   p1 * p2 ==
--     xx := p1::Rep
--     empty? xx => p1
--     yy := p2::Rep
--     empty? yy => p2
--     zero? first(xx).k => first(xx).c * p2
--     zero? first(yy).k => p1 * first(yy).c
--     (first(xx).k > kBound) and (first(yy).k > kBound) and (#xx > kBound) and (#yy > kBound) =
--       karatsubaOnce(p1,p2)$upmp
--     xx := reverse xx
--     res : Rep := empty()
--     for tx in xx repeat res:= rep pomopo!( res,tx.c,tx.k,p2)
--     res


  univariate(p:%) == p pretend SparseUnivariatePolynomial(R)
  multivariate(sup:SparseUnivariatePolynomial(R),v:SingletonAsOrderedSet) ==
     sup pretend %
  univariate(p:%,v:SingletonAsOrderedSet) ==
    zero? p => 0
    monomial(leadingCoefficient(p)::%,degree p) +
        univariate(reductum p,v)
  multivariate(supp:SparseUnivariatePolynomial(%),v:SingletonAsOrderedSet) ==
    zero? supp => 0
    lc:=leadingCoefficient supp
    degree lc > 0 => error "bad form polynomial"
    monomial(leadingCoefficient lc,degree supp) +
        multivariate(reductum supp,v)
```

```
if R has FiniteFieldCategory and R has PolynomialFactorizationExplicit then
  RXY ==> SparseUnivariatePolynomial SparseUnivariatePolynomial R
  squareFreePolynomial pp ==
     squareFree(pp)$UnivariatePolynomialSquareFree(%,FP)
  factorPolynomial pp ==
       (generalTwoFactor(pp pretend RXY)$TwoFactorize(R))
                   pretend Factored SparseUnivariatePolynomial %
  factorSquareFreePolynomial pp ==
       (generalTwoFactor(pp pretend RXY)$TwoFactorize(R))
                   pretend Factored SparseUnivariatePolynomial %
  gcdPolynomial(pp,qq) == gcd(pp,qq)$FP
  factor p == factor(p)$DistinctDegreeFactorize(R,%)
  solveLinearPolynomialEquation(lpp,pp) ==
    solveLinearPolynomialEquation(lpp, pp)$FiniteFieldSolveLinearPolynomialEquation(R,%,FP)
else if R has PolynomialFactorizationExplicit then
  import PolynomialFactorizationByRecursionUnivariate(R,%)
  solveLinearPolynomialEquation(lpp,pp)==
    solveLinearPolynomialEquationByRecursion(lpp,pp)
  factorPolynomial(pp) ==
    factorByRecursion(pp)
  factorSquareFreePolynomial(pp) ==
    factorSquareFreeByRecursion(pp)

if R has IntegralDomain then
 if R has approximate then
  p1 exquo p2  ==
     null p2 => error "Division by 0"
     p2 = 1 => p1
     p1=p2 => 1
   --(p1.lastElt.c exquo p2.lastElt.c) case "failed" => "failed"
     rout:= []@List(Term)
     while not null p1 repeat
        (a:= p1.first.c exquo p2.first.c)
        a case "failed" => return "failed"
        ee:= subtractIfCan(p1.first.k, p2.first.k)
        ee case "failed" => return "failed"
        p1:= fmecg(p1.rest, ee, a, p2.rest)
        rout:= [[ee,a], :rout]
     null p1 => reverse(rout)::%    -- nreverse?
     "failed"
 else -- R not approximate
  p1 exquo p2  ==
     null p2 => error "Division by 0"
     p2 = 1 => p1
   --(p1.lastElt.c exquo p2.lastElt.c) case "failed" => "failed"
     rout:= []@List(Term)
     while not null p1 repeat
        (a:= p1.first.c exquo p2.first.c)
        a case "failed" => return "failed"
        ee:= subtractIfCan(p1.first.k, p2.first.k)
```

```
         ee case "failed" => return "failed"
         p1:= fmecg(p1.rest, ee, a, p2.rest)
         rout:= [[ee,a], :rout]
      null p1 => reverse(rout)::%    -- nreverse?
      "failed"
fmecg(p1,e,r,p2) ==       -- p1 - r * x**e * p2
       rout:%:= []
       r:= - r
       for tm in p2 repeat
          e2:= e + tm.k
          c2:= r * tm.c
          c2 = 0 => "next term"
          while not null p1 and p1.first.k > e2 repeat
            (rout:=[p1.first,:rout]; p1:=p1.rest)  --use PUSH and POP?
          null p1 or p1.first.k < e2 => rout:=[[e2,c2],:rout]
          if (u:=p1.first.c + c2) ^= 0 then rout:=[[e2, u],:rout]
          p1:=p1.rest
       NRECONC(rout,p1)$Lisp
pseudoRemainder(p1,p2) ==
  null p2 => error "PseudoDivision by Zero"
  null p1 => 0
  co:=p2.first.c;
  e:=p2.first.k;
  p2:=p2.rest;
  e1:=max(p1.first.k:Integer-e+1,0):NonNegativeInteger
  while not null p1 repeat
    if (u:=subtractIfCan(p1.first.k,e)) case "failed" then leave
    p1:=fmecg(co * p1.rest, u, p1.first.c, p2)
    e1:= (e1 - 1):NonNegativeInteger
  e1 = 0 => p1
  co ** e1 * p1
toutput(t1:Term,v:OutputForm):OutputForm ==
  t1.k = 0 => t1.c :: OutputForm
  if t1.k = 1
    then mon:= v
    else mon := v ** t1.k::OutputForm
  t1.c = 1 => mon
  t1.c = -1 and
       ((t1.c :: OutputForm) = (-1$Integer)::OutputForm)@Boolean => - mon
  t1.c::OutputForm * mon
outputForm(p:%,v:OutputForm) ==
  l: List(OutputForm)
  l:=[toutput(t,v) for t in p]
  null l => (0$Integer)::OutputForm -- else FreeModule 0 problems
  reduce("+",l)

coerce(p:%):OutputForm == outputForm(p, "?"::OutputForm)
elt(p:%,val:R) ==
   null p => 0$R
   co:=p.first.c
```

```
      n:=p.first.k
      for tm in p.rest repeat
       co:= co * val ** (n - (n:=tm.k)):NonNegativeInteger + tm.c
      n = 0 => co
      co * val ** n
   elt(p:%,val:%) ==
      null p => 0$%
      coef:% := p.first.c :: %
      n:=p.first.k
      for tm in p.rest repeat
       coef:= coef * val ** (n-(n:=tm.k)):NonNegativeInteger+(tm.c::%)
      n = 0 => coef
      coef * val ** n

   monicDivide(p1:%,p2:%) ==
      null p2 => error "monicDivide: division by 0"
      leadingCoefficient p2 ^= 1 => error "Divisor Not Monic"
      p2 = 1 => [p1,0]
      null p1 => [0,0]
      degree p1 < (n:=degree p2) => [0,p1]
      rout:Rep := []
      p2 := p2.rest
      while not null p1 repeat
         (u:=subtractIfCan(p1.first.k, n)) case "failed" => leave
         rout:=[[u, p1.first.c], :rout]
         p1:=fmecg(p1.rest, rout.first.k, rout.first.c, p2)
      [reverse_!(rout),p1]

   if R has IntegralDomain then
       discriminant(p) == discriminant(p)$PseudoRemainderSequence(R,%)
--     discriminant(p) ==
--       null p or zero?(p.first.k) => error "cannot take discriminant of constants"
--       dp:=differentiate p
--       corr:=  p.first.c ** ((degree p - 1 - degree dp)::NonNegativeInteger)
--       (-1)**((p.first.k*(p.first.k-1)) quo 2):NonNegativeInteger
--         * (corr * resultant(p,dp) exquo p.first.c)::R

       subResultantGcd(p1,p2) == subResultantGcd(p1,p2)$PseudoRemainderSequence(R,%)
--     subResultantGcd(p1,p2) ==    --args # 0, non-coef, prim, ans not prim
--       --see algorithm 1 (p. 4) of Brown's latest (unpublished) paper
--       if p1.first.k < p2.first.k then (p1,p2):=(p2,p1)
--       p:=pseudoRemainder(p1,p2)
--       co:=1$R;
--       e:= (p1.first.k - p2.first.k):NonNegativeInteger
--       while not null p and p.first.k ^= 0 repeat
--         p1:=p2; p2:=p; p:=pseudoRemainder(p1,p2)
--         null p or p.first.k = 0 => "enuf"
--         co:=(p1.first.c ** e exquo co ** max(0, (e-1))::NonNegativeInteger)::R
--         e:= (p1.first.k - p2.first.k):NonNegativeInteger;  c1:=co**e
--         p:=[[tm.k,((tm.c exquo p1.first.c)::R exquo c1)::R] for tm in p]
```

```
--       if null p then p2 else 1$%

       resultant(p1,p2) == resultant(p1,p2)$PseudoRemainderSequence(R,%)
--     resultant(p1,p2) ==      --SubResultant PRS Algorithm
--        null p1 or null p2 => 0$R
--        0 = degree(p1) => ((first p1).c)**degree(p2)
--        0 = degree(p2) => ((first p2).c)**degree(p1)
--        if p1.first.k < p2.first.k then
--          (if odd?(p1.first.k) then p1:=-p1;  (p1,p2):=(p2,p1))
--        p:=pseudoRemainder(p1,p2)
--        co:=1$R;  e:=(p1.first.k-p2.first.k):NonNegativeInteger
--        while not null p repeat
--           if not odd?(e) then p:=-p
--           p1:=p2;  p2:=p;  p:=pseudoRemainder(p1,p2)
--           co:=(p1.first.c ** e exquo co ** max(e:Integer-1,0):NonNegativeInteger)::R
--           e:= (p1.first.k - p2.first.k):NonNegativeInteger;  c1:=co**e
--           p:=(p exquo ((leadingCoefficient p1) * c1))::%
--        degree p2 > 0 => 0$R
--        (p2.first.c**e exquo co**((e-1)::NonNegativeInteger))::R
   if R has GcdDomain then
     content(p) == if null p then 0$R else "gcd"/[tm.c for tm in p]
        --make CONTENT more efficient?

     primitivePart(p) ==
        null p => p
        ct :=content(p)
        unitCanonical((p exquo ct)::%)
               -- exquo  present since % is now an IntegralDomain

     gcd(p1,p2) ==
          gcdPolynomial(p1 pretend SparseUnivariatePolynomial R,
                        p2 pretend SparseUnivariatePolynomial R) pretend %

   if R has Field then
     divide( p1, p2)  ==
       zero? p2 => error "Division by 0"
--       one? p2 => [p1,0]
       (p2 = 1) => [p1,0]
       ct:=inv(p2.first.c)
       n:=p2.first.k
       p2:=p2.rest
       rout:=empty()$List(Term)
       while p1 ^= 0 repeat
          (u:=subtractIfCan(p1.first.k, n)) case "failed" => leave
          rout:=[[u, ct * p1.first.c], :rout]
          p1:=fmecg(p1.rest, rout.first.k, rout.first.c, p2)
       [reverse_!(rout),p1]

     p / co == inv(co) * p
```

———-

— **SUP.dotabb** —

```
"SUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SUP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"SUP" -> "PFECAT"
```

———-

20.19 domain SUPEXPR SparseUnivariatePolynomialExpressions

This domain is a hack, in some sense. What I'd really like to do - automatically - is to provide all operations supported by the coefficient domain, as long as the polynomials can be retracted to that domain, i.e., as long as they are just constants. I don't see another way to do this, unfortunately.

— **SparseUnivariatePolynomialExpressions.input** —

```
)set break resume
)sys rm -f SparseUnivariatePolynomialExpressions.output
)spool SparseUnivariatePolynomialExpressions.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseUnivariatePolynomialExpressions
--R
--R SparseUnivariatePolynomialExpressions(R: Ring)  is a domain constructor
--R Abbreviation for SparseUnivariatePolynomialExpressions is SUPEXPR
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SUPEXPR
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R D : (%,(R -> R)) -> %                 D : % -> %
--R D : (%,NonNegativeInteger) -> %       1 : () -> %
--R 0 : () -> %                           ?^? : (%,PositiveInteger) -> %
--R coefficients : % -> List(R)           coerce : R -> %
```

```
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      differentiate : % -> %
--R ?.? : (%,%) -> %                      ?.? : (%,R) -> R
--R eval : (%,%,%) -> %                   eval : (%,Equation(%)) -> %
--R ground : % -> R                       ground? : % -> Boolean
--R hash : % -> SingleInteger             init : () -> % if R has STEP
--R latex : % -> String                   leadingCoefficient : % -> R
--R leadingMonomial : % -> %              map : ((R -> R),%) -> %
--R monomial? : % -> Boolean              monomials : % -> List(%)
--R one? : % -> Boolean                   pi : () -> % if R has TRANFUN
--R pseudoRemainder : (%,%) -> %          recip : % -> Union(%,"failed")
--R reductum : % -> %                     retract : % -> R
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,%) -> % if R has TRANFUN
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?<? : (%,%) -> Boolean if R has ORDSET
--R ?<=? : (%,%) -> Boolean if R has ORDSET
--R ?>? : (%,%) -> Boolean if R has ORDSET
--R ?>=? : (%,%) -> Boolean if R has ORDSET
--R D : (%,(R -> R),NonNegativeInteger) -> %
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R D : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R D : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R D : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R D : (%,List(SingletonAsOrderedSet)) -> %
--R D : (%,SingletonAsOrderedSet) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if R has TRANFUN
--R acosh : % -> % if R has TRANFUN
--R acot : % -> % if R has TRANFUN
--R acoth : % -> % if R has TRANFUN
--R acsc : % -> % if R has TRANFUN
--R acsch : % -> % if R has TRANFUN
--R asec : % -> % if R has TRANFUN
--R asech : % -> % if R has TRANFUN
--R asin : % -> % if R has TRANFUN
--R asinh : % -> % if R has TRANFUN
--R associates? : (%,%) -> Boolean if R has INTDOM
--R atan : % -> % if R has TRANFUN
--R atanh : % -> % if R has TRANFUN
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and R has PFECAT or R has CHARNZ
```

```
--R coefficient : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R coefficient : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : % -> % if R has INTDOM
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : SingletonAsOrderedSet -> %
--R composite : (Fraction(%),%) -> Union(Fraction(%),"failed") if R has INTDOM
--R composite : (%,%) -> Union(%,"failed") if R has INTDOM
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and R has PFECAT
--R content : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R content : % -> R if R has GCDDOM
--R convert : % -> InputForm if SingletonAsOrderedSet has KONVERT(INFORM) and R has KONVERT(INFORM)
--R convert : % -> Pattern(Integer) if SingletonAsOrderedSet has KONVERT(PATTERN(INT)) and R has KONVERT(PA
--R convert : % -> Pattern(Float) if SingletonAsOrderedSet has KONVERT(PATTERN(FLOAT)) and R has KONVERT(PA
--R cos : % -> % if R has TRANFUN
--R cosh : % -> % if R has TRANFUN
--R cot : % -> % if R has TRANFUN
--R coth : % -> % if R has TRANFUN
--R csc : % -> % if R has TRANFUN
--R csch : % -> % if R has TRANFUN
--R degree : (%,List(SingletonAsOrderedSet)) -> List(NonNegativeInteger)
--R degree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R differentiate : (%,(R -> R),%) -> %
--R differentiate : (%,(R -> R)) -> %
--R differentiate : (%,(R -> R),NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,List(Symbol)) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,Symbol) -> % if R has PDRING(SYMBOL)
--R differentiate : (%,NonNegativeInteger) -> %
--R differentiate : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R differentiate : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R differentiate : (%,List(SingletonAsOrderedSet)) -> %
--R differentiate : (%,SingletonAsOrderedSet) -> %
--R discriminant : % -> R if R has COMRING
--R discriminant : (%,SingletonAsOrderedSet) -> % if R has COMRING
--R divide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R divideExponents : (%,NonNegativeInteger) -> Union(%,"failed")
--R ?.? : (%,Fraction(%)) -> Fraction(%) if R has INTDOM
--R elt : (Fraction(%),R) -> R if R has FIELD
--R elt : (Fraction(%),Fraction(%)) -> Fraction(%) if R has INTDOM
--R euclideanSize : % -> NonNegativeInteger if R has FIELD
--R eval : (%,List(SingletonAsOrderedSet),List(%)) -> %
--R eval : (%,SingletonAsOrderedSet,%) -> %
--R eval : (%,List(SingletonAsOrderedSet),List(R)) -> %
--R eval : (%,SingletonAsOrderedSet,R) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R exp : % -> % if R has TRANFUN
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if R has FIELD
```

```
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if R has FIELD
--R factor : % -> Factored(%) if R has PFECAT
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R gcd : (%,%) -> % if R has GCDDOM
--R gcd : List(%) -> % if R has GCDDOM
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R integrate : % -> % if R has ALGEBRA(FRAC(INT))
--R isExpt : % -> Union(Record(var: SingletonAsOrderedSet,exponent: NonNegativeInteger),"failed"
--R isPlus : % -> Union(List(%),"failed")
--R isTimes : % -> Union(List(%),"failed")
--R karatsubaDivide : (%,NonNegativeInteger) -> Record(quotient: %,remainder: %)
--R lcm : (%,%) -> % if R has GCDDOM
--R lcm : List(%) -> % if R has GCDDOM
--R log : % -> % if R has TRANFUN
--R mainVariable : % -> Union(SingletonAsOrderedSet,"failed")
--R makeSUP : % -> SparseUnivariatePolynomial(R)
--R mapExponents : ((NonNegativeInteger -> NonNegativeInteger),%) -> %
--R max : (%,%) -> % if R has ORDSET
--R min : (%,%) -> % if R has ORDSET
--R minimumDegree : (%,List(SingletonAsOrderedSet)) -> List(NonNegativeInteger)
--R minimumDegree : (%,SingletonAsOrderedSet) -> NonNegativeInteger
--R minimumDegree : % -> NonNegativeInteger
--R monicDivide : (%,%) -> Record(quotient: %,remainder: %)
--R monicDivide : (%,%,SingletonAsOrderedSet) -> Record(quotient: %,remainder: %)
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (R,NonNegativeInteger) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if R has FIELD
--R multiplyExponents : (%,NonNegativeInteger) -> %
--R multivariate : (SparseUnivariatePolynomial(%),SingletonAsOrderedSet) -> %
--R multivariate : (SparseUnivariatePolynomial(R),SingletonAsOrderedSet) -> %
--R nextItem : % -> Union(%,"failed") if R has STEP
--R numberOfMonomials : % -> NonNegativeInteger
--R order : (%,%) -> NonNegativeInteger if R has INTDOM
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pomopo! : (%,R,NonNegativeInteger,%) -> %
--R prime? : % -> Boolean if R has PFECAT
--R primitiveMonomials : % -> List(%)
--R primitivePart : (%,SingletonAsOrderedSet) -> % if R has GCDDOM
--R primitivePart : % -> % if R has GCDDOM
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if R has FIELD
--R pseudoDivide : (%,%) -> Record(coef: R,quotient: %,remainder: %) if R has INTDOM
--R pseudoQuotient : (%,%) -> % if R has INTDOM
--R ?quo? : (%,%) -> % if R has FIELD
--R reducedSystem : Matrix(%) -> Matrix(R)
```

```
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(R),vec: Vector(R))
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if R has LINE
--R reducedSystem : Matrix(%) -> Matrix(Integer) if R has LINEXP(INT)
--R ?rem? : (%,%) -> % if R has FIELD
--R resultant : (%,%) -> R if R has COMRING
--R resultant : (%,%,SingletonAsOrderedSet) -> % if R has COMRING
--R retract : % -> SingletonAsOrderedSet
--R retract : % -> Integer if R has RETRACT(INT)
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(SingletonAsOrderedSet,"failed")
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(R,"failed")
--R sec : % -> % if R has TRANFUN
--R sech : % -> % if R has TRANFUN
--R separate : (%,%) -> Record(primePart: %,commonPart: %) if R has GCDDOM
--R shiftLeft : (%,NonNegativeInteger) -> %
--R shiftRight : (%,NonNegativeInteger) -> %
--R sin : % -> % if R has TRANFUN
--R sinh : % -> % if R has TRANFUN
--R sizeLess? : (%,%) -> Boolean if R has FIELD
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R squareFree : % -> Factored(%) if R has GCDDOM
--R squareFreePart : % -> % if R has GCDDOM
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if R has
--R subResultantGcd : (%,%) -> % if R has INTDOM
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if R has TRANFUN
--R tanh : % -> % if R has TRANFUN
--R totalDegree : (%,List(SingletonAsOrderedSet)) -> NonNegativeInteger
--R totalDegree : % -> NonNegativeInteger
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R univariate : % -> SparseUnivariatePolynomial(R)
--R univariate : (%,SingletonAsOrderedSet) -> SparseUnivariatePolynomial(%)
--R unmakeSUP : SparseUnivariatePolynomial(R) -> %
--R variables : % -> List(SingletonAsOrderedSet)
--R vectorise : (%,NonNegativeInteger) -> Vector(R)
--R
--E 1

)spool
)lisp (bye)
```


———-

— SparseUnivariatePolynomialExpressions.help —

```
=============================================================================
SparseUnivariatePolynomialExpressions examples
=============================================================================

See Also:
o )show SparseUnivariatePolynomialExpressions
```

20.19.1 SparseUnivariatePolynomialExpressions (SUPEXPR)



Exports:

0	1	acos
acosh	acot	acoth
acsc	acsch	asec
asech	asin	asinh
associates?	atan	atanh
binomThmExpt	characteristic	charthRoot
coefficient	coefficients	coerce
composite	conditionP	content
convert	cos	cosh
cot	coth	csc
csch	D	degree
differentiate	discriminant	divide
divideExponents	elt	euclideanSize
eval	exp	expressIdealMember
exquo	extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial	gcd
gcdPolynomial	ground	ground?
hash	init	integrate
isExpt	isPlus	isTimes
karatsubaDivide	latex	lcm
leadingCoefficient	leadingMonomial	log
mainVariable	makeSUP	map
mapExponents	max	min
minimumDegree	monicDivide	monomial
monomial?	monomials	multiEuclidean
multiplyExponents	multivariate	nextItem
numberOfMonomials	one?	order
patternMatch	pi	pomopo!
prime?	primitiveMonomials	primitivePart
principalIdeal	pseudoDivide	pseudoQuotient
pseudoRemainder	recip	reducedSystem
reductum	resultant	retract
retractIfCan	sample	sec
sech	separate	shiftLeft
shiftRight	sin	sinh
sizeLess?	solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial	subResultantGcd
subtractIfCan	tan	tanh
totalDegree	unit?	unitCanonical
unitNormal	univariate	unmakeSUP
variables	vectorise	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?.?	?~=?
?/?	?<?	?<=?
?>?	?>=?	?quo?
?rem?		

— domain SUPEXPR SparseUnivariatePolynomialExpressions —

```
)abbrev domain SUPEXPR SparseUnivariatePolynomialExpressions
++ Author: Mark Botch
++ Description:
++ This domain has no description

SparseUnivariatePolynomialExpressions(R: Ring): Exports == Implementation where

    Exports == UnivariatePolynomialCategory R with

        if R has TranscendentalFunctionCategory
        then TranscendentalFunctionCategory

    Implementation == SparseUnivariatePolynomial R add

        if R has TranscendentalFunctionCategory then
            log(p: %): % ==
                ground? p => coerce log ground p
                output(hconcat("log p for p= ", p::OutputForm))$OutputPackage
                error "SUPTRAFUN: log only defined for elements of the coefficient ring"

            exp(p: %): % ==
                ground? p => coerce exp ground p
                output(hconcat("exp p for p= ", p::OutputForm))$OutputPackage
                error "SUPTRAFUN: exp only defined for elements of the coefficient ring"
            sin(p: %): % ==
                ground? p => coerce sin ground p
                output(hconcat("sin p for p= ", p::OutputForm))$OutputPackage
                error "SUPTRAFUN: sin only defined for elements of the coefficient ring"
            asin(p: %): % ==
                ground? p => coerce asin ground p
                output(hconcat("asin p for p= ", p::OutputForm))$OutputPackage
                error "SUPTRAFUN: asin only defined for elements of the coefficient ring"
            cos(p: %): % ==
                ground? p => coerce cos ground p
                output(hconcat("cos p for p= ", p::OutputForm))$OutputPackage
                error "SUPTRAFUN: cos only defined for elements of the coefficient ring"
            acos(p: %): % ==
                ground? p => coerce acos ground p
                output(hconcat("acos p for p= ", p::OutputForm))$OutputPackage
                error "SUPTRAFUN: acos only defined for elements of the coefficient ring"

            ———————-
```

— SUPEXPR.dotabb —

```
"SUPEXPR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SUPEXPR"]
```

```
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"SUPEXPR" -> "PFECAT"
```

———-

20.20 domain SUPXS SparseUnivariatePuiseuxSeries

— SparseUnivariatePuiseuxSeries.input —

```
)set break resume
)sys rm -f SparseUnivariatePuiseuxSeries.output
)spool SparseUnivariatePuiseuxSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseUnivariatePuiseuxSeries
--R
--R SparseUnivariatePuiseuxSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for SparseUnivariatePuiseuxSeries is SUPXS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SUPXS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coerce : Variable(var) -> %          coerce : Integer -> %
--R coerce : % -> OutputForm             complete : % -> %
--R degree : % -> Fraction(Integer)      hash : % -> SingleInteger
--R latex : % -> String                  leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %             map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean             one? : % -> Boolean
--R order : % -> Fraction(Integer)       pole? : % -> Boolean
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R sample : () -> %                     variable : % -> Symbol
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRING(SYMB
--R D : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRIN
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and C
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Integer),Coef) -
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Fraction(Integer)) -> Coef if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,Fraction(Integer)) -> Coef
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R coerce : SparseUnivariateTaylorSeries(Coef,var,cen) -> %
--R coerce : SparseUnivariateLaurentSeries(Coef,var,cen) -> %
--R coerce : Coef -> % if Coef has COMRING
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(var)) -> %
--R differentiate : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Co
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Inte
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,%) -> % if Fraction(Integer) has SGROUP
```

```
--R ?.? : (%,Fraction(Integer)) -> Coef
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,Fraction(Integer)) -> %
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef ->
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R laurent : % -> SparseUnivariateLaurentSeries(Coef,var,cen)
--R laurentIfCan : % -> Union(SparseUnivariateLaurentSeries(Coef,var,cen),"failed")
--R laurentRep : % -> SparseUnivariateLaurentSeries(Coef,var,cen)
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(Fraction(Integer))) -> %
--R monomial : (%,SingletonAsOrderedSet,Fraction(Integer)) -> %
--R monomial : (Coef,Fraction(Integer)) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyExponents : (%,Fraction(Integer)) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,Fraction(Integer)) -> Fraction(Integer)
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R puiseux : (Fraction(Integer),SparseUnivariateLaurentSeries(Coef,var,cen)) -> %
--R ?quo? : (%,%) -> % if Coef has FIELD
--R rationalPower : % -> Fraction(Integer)
--R ?rem? : (%,%) -> % if Coef has FIELD
--R retract : % -> SparseUnivariateTaylorSeries(Coef,var,cen)
--R retract : % -> SparseUnivariateLaurentSeries(Coef,var,cen)
--R retractIfCan : % -> Union(SparseUnivariateTaylorSeries(Coef,var,cen),"failed")
--R retractIfCan : % -> Union(SparseUnivariateLaurentSeries(Coef,var,cen),"failed")
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : (NonNegativeInteger,Stream(Record(k: Fraction(Integer),c: Coef))) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if Coef has FIELD
```

```
--R squareFreePart : % -> % if Coef has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: Fraction(Integer),c: Coef))
--R truncate : (%,Fraction(Integer),Fraction(Integer)) -> %
--R truncate : (%,Fraction(Integer)) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— SparseUnivariatePuiseuxSeries.help —

```
=====================================================================
SparseUnivariatePuiseuxSeries examples
=====================================================================

See Also:
o )show SparseUnivariatePuiseuxSeries
```

———-

20.20.1 SparseUnivariatePuiseuxSeries (SUPXS)



Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
characteristic	charthRoot	center	coefficient
coerce	complete	cos	cosh
cot	coth	csc	csch
D	degree	differentiate	divide
euclideanSize	eval	exp	expressIdealMember
exquo	extend	extendedEuclidean	factor
gcd	gcdPolynomial	hash	integrate
inv	latex	laurent	laurentIfCan
laurentRep	lcm	leadingCoefficient	leadingMonomial
log	map	monomial	monomial?
multiEuclidean	multiplyExponents	nthRoot	one?
order	pi	pole?	prime?
principalIdeal	puiseux	rationalPower	recip
reductum	retract	retractIfCan	sample
sec	sech	series	sin
sinh	sizeLess?	sqrt	squareFree
squareFreePart	subtractIfCan	tan	tanh
terms	truncate	unit?	unitCanonical
unitNormal	variable	variables	zero?
?.?	?*?	?**?	?+?
?-?	-?	?=?	?^?
?~=?	?/?	?quo?	?rem?

— domain SUPXS SparseUnivariatePuiseuxSeries —

```
)abbrev domain SUPXS SparseUnivariatePuiseuxSeries
++ Author: Clifton J. Williamson
++ Date Created: 11 November 1994
++ Date Last Updated: 28 February 1995
++ Basic Operations:
++ Related Domains: InnerSparseUnivariatePowerSeries,
++   SparseUnivariateTaylorSeries, SparseUnivariateLaurentSeries
++ Also See:
++ AMS Classifications:
++ Keywords: sparse, series
++ Examples:
++ References:
++ Description:
++ Sparse Puiseux series in one variable
++ \spadtype{SparseUnivariatePuiseuxSeries} is a domain representing Puiseux
++ series in one variable with coefficients in an arbitrary ring.  The
++ parameters of the type specify the coefficient ring, the power series
++ variable, and the center of the power series expansion.  For example,
```

```
++ \spad{SparseUnivariatePuiseuxSeries(Integer,x,3)} represents Puiseux
++ series in \spad{(x - 3)} with \spadtype{Integer} coefficients.

SparseUnivariatePuiseuxSeries(Coef,var,cen): Exports == Implementation where
  Coef : Ring
  var  : Symbol
  cen  : Coef
  I    ==> Integer
  NNI  ==> NonNegativeInteger
  OUT  ==> OutputForm
  RN   ==> Fraction Integer
  SUTS ==> SparseUnivariateTaylorSeries(Coef,var,cen)
  SULS ==> SparseUnivariateLaurentSeries(Coef,var,cen)
  SUPS ==> InnerSparseUnivariatePowerSeries(Coef)

  Exports ==> Join(UnivariatePuiseuxSeriesConstructorCategory(Coef,SULS),_
                   RetractableTo SUTS) with
    coerce: Variable(var) -> %
      ++ coerce(var) converts the series variable \spad{var} into a
      ++ Puiseux series.
    differentiate: (%,Variable(var)) -> %
      ++ \spad{differentiate(f(x),x)} returns the derivative of
      ++ \spad{f(x)} with respect to \spad{x}.
    if Coef has Algebra Fraction Integer then
      integrate: (%,Variable(var)) -> %
        ++ \spad{integrate(f(x))} returns an anti-derivative of the power
        ++ series \spad{f(x)} with constant coefficient 0.
        ++ We may integrate a series when we can divide coefficients
        ++ by integers.

  Implementation ==> UnivariatePuiseuxSeriesConstructor(Coef,SULS) add

    Rep := Record(expon:RN,lSeries:SULS)

    getExpon: % -> RN
    getExpon pxs == pxs.expon

    variable x == var
    center   x == cen

    coerce(v: Variable(var)) ==
      zero? cen => monomial(1,1)
      monomial(1,1) + monomial(cen,0)

    coerce(uts:SUTS) == uts :: SULS :: %

    retractIfCan(upxs:%):Union(SUTS,"failed") ==
      (uls := retractIfCan(upxs)@Union(SULS,"failed")) case "failed" =>
        "failed"
      retractIfCan(uls :: SULS)@Union(SUTS,"failed")
```

```
    if Coef has "*": (Fraction Integer, Coef) -> Coef then
      differentiate(upxs:%,v:Variable(var)) == differentiate upxs

    if Coef has Algebra Fraction Integer then
      integrate(upxs:%,v:Variable(var)) == integrate upxs

--% OutputForms

    coerce(x:%): OUT ==
      sups : SUPS := laurentRep(x) pretend SUPS
      st := getStream sups; refer := getRef sups
      if not(explicitlyEmpty? st or explicitEntries? st) _
        and (nx := retractIfCan(elt refer)@Union(I,"failed")) case I then
        count : NNI := _$streamCount$Lisp
        degr := min(count,(nx :: I) + count + 1)
        extend(sups,degr)
      seriesToOutputForm(st,refer,variable x,center x,rationalPower x)
```

———-

— SUPXS.dotabb —

```
"SUPXS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SUPXS"]
"ULSCCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ULSCCAT"]
"SUPXS" -> "ULSCCAT"
```

———-

20.21 domain ORESUP SparseUnivariateSkewPolynomial

— SparseUnivariateSkewPolynomial.input —

```
)set break resume
)sys rm -f SparseUnivariateSkewPolynomial.output
)spool SparseUnivariateSkewPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseUnivariateSkewPolynomial
```

```
--R
--R SparseUnivariateSkewPolynomial(R: Ring,sigma: Automorphism(R),delta: (R -> R))  is a domain
--R Abbreviation for SparseUnivariateSkewPolynomial is ORESUP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ORESUP
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        apply : (%,R,R) -> R
--R coefficients : % -> List(R)           coerce : R -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R degree : % -> NonNegativeInteger      hash : % -> SingleInteger
--R latex : % -> String                   leadingCoefficient : % -> R
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R reductum : % -> %                     retract : % -> R
--R sample : () -> %                      zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT))
--R content : % -> R if R has GCDDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R leftDivide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R leftExactQuotient : (%,%) -> Union(%,"failed") if R has FIELD
--R leftExtendedGcd : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R leftGcd : (%,%) -> % if R has FIELD
--R leftLcm : (%,%) -> % if R has FIELD
--R leftQuotient : (%,%) -> % if R has FIELD
--R leftRemainder : (%,%) -> % if R has FIELD
--R minimumDegree : % -> NonNegativeInteger
--R monicLeftDivide : (%,%) -> Record(quotient: %,remainder: %) if R has INTDOM
--R monicRightDivide : (%,%) -> Record(quotient: %,remainder: %) if R has INTDOM
--R monomial : (R,NonNegativeInteger) -> %
--R outputForm : (%,OutputForm) -> OutputForm
--R primitivePart : % -> % if R has GCDDOM
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R rightDivide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R rightExactQuotient : (%,%) -> Union(%,"failed") if R has FIELD
```

```
--R rightExtendedGcd : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R rightGcd : (%,%) -> % if R has FIELD
--R rightLcm : (%,%) -> % if R has FIELD
--R rightQuotient : (%,%) -> % if R has FIELD
--R rightRemainder : (%,%) -> % if R has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— **SparseUnivariateSkewPolynomial.help** —

```
=====================================================================
SparseUnivariateSkewPolynomial examples
=====================================================================

See Also:
o )show SparseUnivariateSkewPolynomial
```

———-

20.21.1 SparseUnivariateSkewPolynomial (ORESUP)



See

⇒ “Automorphism” (AUTOMOR) 2.44.1 on page 230
⇒ “UnivariateSkewPolynomial” (OREUP) 22.8.1 on page 2839

Exports:

0	1	apply	characteristic	coefficient
coefficients	coerce	content	degree	exquo
hash	latex	leadingCoefficient	leftDivide	leftExactQuotient
leftExtendedGcd	leftGcd	leftLcm	leftQuotient	leftRemainder
minimumDegree	monicLeftDivide	monicRightDivide	monomial	one?
outputForm	primitivePart	recip	reductum	retract
retractIfCan	rightDivide	rightExactQuotient	rightExtendedGcd	rightGcd
rightLcm	rightQuotient	rightRemainder	sample	subtractIfCan
zero?	?*?	?**?	?+?	?-?
-?	?=?	?^?	?~=?	

— domain ORESUP SparseUnivariateSkewPolynomial —

```
)abbrev domain ORESUP SparseUnivariateSkewPolynomial
++ Author: Manuel Bronstein
++ Date Created: 19 October 1993
++ Date Last Updated: 1 February 1994
++ Description:
++ This is the domain of sparse univariate skew polynomials over an Ore
++ coefficient field.
++ The multiplication is given by \spad{x a = \sigma(a) x + \delta a}.

SparseUnivariateSkewPolynomial(R:Ring, sigma:Automorphism R, delta: R -> R):
 UnivariateSkewPolynomialCategory R with
      outputForm: (%, OutputForm) -> OutputForm
        ++ outputForm(p, x) returns the output form of p using x for the
        ++ otherwise anonymous variable.
   == SparseUnivariatePolynomial R add
      import UnivariateSkewPolynomialCategoryOps(R, %)

      x:% * y:%      == times(x, y, sigma, delta)
      apply(p, c, r) == apply(p, c, r, sigma, delta)

      if R has IntegralDomain then
          monicLeftDivide(a, b)  == monicLeftDivide(a, b, sigma)
          monicRightDivide(a, b) == monicRightDivide(a, b, sigma)

      if R has Field then
          leftDivide(a, b)  == leftDivide(a, b, sigma)
          rightDivide(a, b) == rightDivide(a, b, sigma)
```

———-

— ORESUP.dotabb —

```
"ORESUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ORESUP"]
```

```
"OREPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OREPCAT"]
"ORESUP" -> "OREPCAT"
```

———-

20.22 domain SUTS SparseUnivariateTaylorSeries

— **SparseUnivariateTaylorSeries.input** —

```
)set break resume
)sys rm -f SparseUnivariateTaylorSeries.output
)spool SparseUnivariateTaylorSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SparseUnivariateTaylorSeries
--R
--R SparseUnivariateTaylorSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for SparseUnivariateTaylorSeries is SUTS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SUTS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coefficients : % -> Stream(Coef)     coerce : Variable(var) -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R complete : % -> %                    degree : % -> NonNegativeInteger
--R hash : % -> SingleInteger            latex : % -> String
--R leadingCoefficient : % -> Coef       leadingMonomial : % -> %
--R map : ((Coef -> Coef),%) -> %        monomial? : % -> Boolean
--R one? : % -> Boolean                  order : % -> NonNegativeInteger
--R pole? : % -> Boolean                 quoByVar : % -> %
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R sample : () -> %                     series : Stream(Coef) -> %
--R variable : % -> Symbol               zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Coef) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRING(SYM
--R D : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRI
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeInteger,Coef)
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,NonNegativeInteger) -> Coef if Coef has **: (Coef,NonNegativeInteger) -> Co
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,NonNegativeInteger) -> Coef
--R coerce : UnivariatePolynomial(var,Coef) -> %
--R coerce : Coef -> % if Coef has COMRING
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(var)) -> %
--R differentiate : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef ha
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and C
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeIn
--R ?.? : (%,%) -> % if NonNegativeInteger has SGROUP
--R ?.? : (%,NonNegativeInteger) -> Coef
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,NonNegativeInteger) -> Coef
```

```
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,NonNegativeInteger) -> %
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef -
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (Coef,NonNegativeInteger) -> %
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,NonNegativeInteger) -> NonNegativeInteger
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R polynomial : (%,NonNegativeInteger,NonNegativeInteger) -> Polynomial(Coef)
--R polynomial : (%,NonNegativeInteger) -> Polynomial(Coef)
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: NonNegativeInteger,c: Coef)) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: NonNegativeInteger,c: Coef))
--R truncate : (%,NonNegativeInteger,NonNegativeInteger) -> %
--R truncate : (%,NonNegativeInteger) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R univariatePolynomial : (%,NonNegativeInteger) -> UnivariatePolynomial(var,Coef)
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— SparseUnivariateTaylorSeries.help —

```
=====================================================================
SparseUnivariateTaylorSeries examples
=====================================================================

See Also:
```

```
o )show SparseUnivariateTaylorSeries
```

20.22.1 SparseUnivariateTaylorSeries (SUTS)



Exports:

0	1	acos	acosh	acot
acoth	acsc	acsch	approximate	asec
asech	asin	asinh	associates?	atan
atanh	center	characteristic	charthRoot	coefficient
coefficients	coerce	complete	cos	cosh
cot	coth	csc	csch	D
degree	differentiate	eval	exp	exquo
extend	hash	integrate	latex	leadingCoefficient
leadingMonomial	log	map	monomial	monomial?
multiplyCoefficients	multiplyExponents	nthRoot	one?	order
pole?	pi	polynomial	polynomial	quoByVar
recip	reductum	sample	sec	sech
series	sin	sinh	sqrt	subtractIfCan
tan	tanh	terms	truncate	truncate
unit?	unitCanonical	unitNormal	univariatePolynomial	variable
variables	zero?	?*?	?**?	?+?
?-?	-?	?=?	?^?	?~=?
?/?	?.?			

— domain SUTS SparseUnivariateTaylorSeries —

```
)abbrev domain SUTS SparseUnivariateTaylorSeries
++ Author: Clifton J. Williamson
++ Date Created: 16 February 1990
++ Date Last Updated: 10 March 1995
++ Basic Operations:
```

```
++ Related Domains: InnerSparseUnivariatePowerSeries,
++   SparseUnivariateLaurentSeries, SparseUnivariatePuiseuxSeries
++ Also See:
++ AMS Classifications:
++ Keywords: Taylor series, sparse power series
++ Examples:
++ References:
++ Description:
++ Sparse Taylor series in one variable
++ \spadtype{SparseUnivariateTaylorSeries} is a domain representing Taylor
++ series in one variable with coefficients in an arbitrary ring.  The
++ parameters of the type specify the coefficient ring, the power series
++ variable, and the center of the power series expansion.  For example,
++ \spadtype{SparseUnivariateTaylorSeries}(Integer,x,3) represents Taylor
++ series in \spad{(x - 3)} with \spadtype{Integer} coefficients.

SparseUnivariateTaylorSeries(Coef,var,cen): Exports == Implementation where
  Coef : Ring
  var  : Symbol
  cen  : Coef
  COM  ==> OrderedCompletion Integer
  I    ==> Integer
  L    ==> List
  NNI  ==> NonNegativeInteger
  OUT  ==> OutputForm
  P    ==> Polynomial Coef
  REF  ==> Reference OrderedCompletion Integer
  RN   ==> Fraction Integer
  Term ==> Record(k:Integer,c:Coef)
  SG   ==> String
  ST   ==> Stream Term
  UP   ==> UnivariatePolynomial(var,Coef)

  Exports ==> UnivariateTaylorSeriesCategory(Coef) with
    coerce: UP -> %
      ++\spad{coerce(p)} converts a univariate polynomial p in the variable
      ++\spad{var} to a univariate Taylor series in \spad{var}.
    univariatePolynomial: (%,NNI) -> UP
      ++\spad{univariatePolynomial(f,k)} returns a univariate polynomial
      ++ consisting of the sum of all terms of f of degree \spad{<= k}.
    coerce: Variable(var) -> %
      ++\spad{coerce(var)} converts the series variable \spad{var} into a
      ++ Taylor series.
    differentiate: (%,Variable(var)) -> %
      ++ \spad{differentiate(f(x),x)} computes the derivative of
      ++ \spad{f(x)} with respect to \spad{x}.
    if Coef has Algebra Fraction Integer then
      integrate: (%,Variable(var)) -> %
        ++ \spad{integrate(f(x),x)} returns an anti-derivative of the power
        ++ series \spad{f(x)} with constant coefficient 0.
```

```
        ++ We may integrate a series when we can divide coefficients
        ++ by integers.

  Implementation ==> InnerSparseUnivariatePowerSeries(Coef) add
    import REF

    Rep := InnerSparseUnivariatePowerSeries(Coef)

    makeTerm: (Integer,Coef) -> Term
    makeTerm(exp,coef) == [exp,coef]
    getCoef: Term -> Coef
    getCoef term == term.c
    getExpon: Term -> Integer
    getExpon term == term.k

    monomial(coef,expon) == monomial(coef,expon)$Rep
    extend(x,n) == extend(x,n)$Rep

    0 == monomial(0,0)$Rep
    1 == monomial(1,0)$Rep

    recip uts == iExquo(1,uts,true)

    if Coef has IntegralDomain then
      uts1 exquo uts2 == iExquo(uts1,uts2,true)

    quoByVar uts == taylorQuoByVar(uts)$Rep

    differentiate(x:%,v:Variable(var)) == differentiate x

--% Creation and destruction of series

    coerce(v: Variable(var)) ==
      zero? cen => monomial(1,1)
      monomial(1,1) + monomial(cen,0)

    coerce(p:UP) ==
      zero? p => 0
      if not zero? cen then p := p(monomial(1,1)$UP + monomial(cen,0)$UP)
      st : ST := empty()
      while not zero? p repeat
        st := concat(makeTerm(degree p,leadingCoefficient p),st)
        p := reductum p
      makeSeries(ref plusInfinity(),st)

    univariatePolynomial(x,n) ==
      extend(x,n); st := getStream x
      ans : UP := 0; oldDeg : I := 0;
      mon := monomial(1,1)$UP - monomial(center x,0)$UP; monPow : UP := 1
      while explicitEntries? st repeat
```

```
    (xExpon := getExpon(xTerm := frst st)) > n => return ans
    pow := (xExpon - oldDeg) :: NNI; oldDeg := xExpon
    monPow := monPow * mon ** pow
    ans := ans + getCoef(xTerm) * monPow
    st := rst st
  ans

polynomial(x,n) ==
  extend(x,n); st := getStream x
  ans : P := 0; oldDeg : I := 0;
  mon := (var :: P) - (center(x) :: P); monPow : P := 1
  while explicitEntries? st repeat
    (xExpon := getExpon(xTerm := frst st)) > n => return ans
    pow := (xExpon - oldDeg) :: NNI; oldDeg := xExpon
    monPow := monPow * mon ** pow
    ans := ans + getCoef(xTerm) * monPow
    st := rst st
  ans

polynomial(x,n1,n2) == polynomial(truncate(x,n1,n2),n2)

truncate(x,n)     == truncate(x,n)$Rep
truncate(x,n1,n2) == truncate(x,n1,n2)$Rep

iCoefficients: (ST,REF,I) -> Stream Coef
iCoefficients(x,refer,n) == delay
  -- when this function is called, we are computing the nth order
  -- coefficient of the series
  explicitlyEmpty? x => empty()
  -- if terms up to order n have not been computed,
  -- apply lazy evaluation
  nn := n :: COM
  while (nx := elt refer) < nn repeat lazyEvaluate x
  -- must have nx >= n
  explicitEntries? x =>
    xCoef := getCoef(xTerm := frst x); xExpon := getExpon xTerm
    xExpon = n => concat(xCoef,iCoefficients(rst x,refer,n + 1))
    -- must have nx > n
    concat(0,iCoefficients(x,refer,n + 1))
  concat(0,iCoefficients(x,refer,n + 1))

coefficients uts ==
  refer := getRef uts; x := getStream uts
  iCoefficients(x,refer,0)

terms uts == terms(uts)$Rep pretend Stream Record(k:NNI,c:Coef)

iSeries: (Stream Coef,I,REF) -> ST
iSeries(st,n,refer) == delay
  -- when this function is called, we are creating the nth order
```

```
      -- term of a series
      empty? st => (setelt(refer,plusInfinity()); empty())
      setelt(refer,n :: COM)
      zero? (coef := frst st) => iSeries(rst st,n + 1,refer)
      concat(makeTerm(n,coef),iSeries(rst st,n + 1,refer))

    series(st:Stream Coef) ==
      refer := ref(-1)
      makeSeries(refer,iSeries(st,0,refer))

    nniToI: Stream Record(k:NNI,c:Coef) -> ST
    nniToI st ==
      empty? st => empty()
      term : Term := [(frst st).k,(frst st).c]
      concat(term,nniToI rst st)

    series(st:Stream Record(k:NNI,c:Coef)) == series(nniToI st)$Rep

--% Values

    variable x == var
    center   x == cen

    coefficient(x,n) == coefficient(x,n)$Rep
    elt(x:%,n:NonNegativeInteger) == coefficient(x,n)

    pole? x == false

    order x    == (order(x)$Rep) :: NNI
    order(x,n) == (order(x,n)$Rep) :: NNI

--% Composition

    elt(uts1:%,uts2:%) ==
      zero? uts2 => coefficient(uts1,0) :: %
      not zero? coefficient(uts2,0) =>
        error "elt: second argument must have positive order"
      iCompose(uts1,uts2)

--% Integration

    if Coef has Algebra Fraction Integer then

      integrate(x:%,v:Variable(var)) == integrate x

--% Transcendental functions

      (uts1:%) ** (uts2:%) == exp(log(uts1) * uts2)

      if Coef has CommutativeRing then
```

```
        (uts:%) ** (r:RN) == cRationalPower(uts,r)

        exp uts == cExp uts
        log uts == cLog uts

        sin uts == cSin uts
        cos uts == cCos uts
        tan uts == cTan uts
        cot uts == cCot uts
        sec uts == cSec uts
        csc uts == cCsc uts

        asin uts == cAsin uts
        acos uts == cAcos uts
        atan uts == cAtan uts
        acot uts == cAcot uts
        asec uts == cAsec uts
        acsc uts == cAcsc uts

        sinh uts == cSinh uts
        cosh uts == cCosh uts
        tanh uts == cTanh uts
        coth uts == cCoth uts
        sech uts == cSech uts
        csch uts == cCsch uts

        asinh uts == cAsinh uts
        acosh uts == cAcosh uts
        atanh uts == cAtanh uts
        acoth uts == cAcoth uts
        asech uts == cAsech uts
        acsch uts == cAcsch uts

      else

        ZERO    : SG := "series must have constant coefficient zero"
        ONE     : SG := "series must have constant coefficient one"
        NPOWERS : SG := "series expansion has terms of negative degree"

        (uts:%) ** (r:RN) ==
--          not one? coefficient(uts,0) =>
          not (coefficient(uts,0) = 1) =>
            error "**: constant coefficient must be one"
          onePlusX : % := monomial(1,0) + monomial(1,1)
          ratPow := cPower(uts,r :: Coef)
          iCompose(ratPow,uts - 1)

        exp uts ==
          zero? coefficient(uts,0) =>
```

```
            expx := cExp monomial(1,1)
            iCompose(expx,uts)
          error concat("exp: ",ZERO)

        log uts ==
--          one? coefficient(uts,0) =>
          (coefficient(uts,0) = 1) =>
            log1PlusX := cLog(monomial(1,0) + monomial(1,1))
            iCompose(log1PlusX,uts - 1)
          error concat("log: ",ONE)

        sin uts ==
          zero? coefficient(uts,0) =>
            sinx := cSin monomial(1,1)
            iCompose(sinx,uts)
          error concat("sin: ",ZERO)

        cos uts ==
          zero? coefficient(uts,0) =>
            cosx := cCos monomial(1,1)
            iCompose(cosx,uts)
          error concat("cos: ",ZERO)

        tan uts ==
          zero? coefficient(uts,0) =>
            tanx := cTan monomial(1,1)
            iCompose(tanx,uts)
          error concat("tan: ",ZERO)

        cot uts ==
          zero? uts => error "cot: cot(0) is undefined"
          zero? coefficient(uts,0) => error concat("cot: ",NPOWERS)
          error concat("cot: ",ZERO)

        sec uts ==
          zero? coefficient(uts,0) =>
            secx := cSec monomial(1,1)
            iCompose(secx,uts)
          error concat("sec: ",ZERO)

        csc uts ==
          zero? uts => error "csc: csc(0) is undefined"
          zero? coefficient(uts,0) => error concat("csc: ",NPOWERS)
          error concat("csc: ",ZERO)

        asin uts ==
          zero? coefficient(uts,0) =>
            asinx := cAsin monomial(1,1)
            iCompose(asinx,uts)
          error concat("asin: ",ZERO)
```

```
atan uts ==
  zero? coefficient(uts,0) =>
    atanx := cAtan monomial(1,1)
    iCompose(atanx,uts)
  error concat("atan: ",ZERO)

acos z == error "acos: acos undefined on this coefficient domain"
acot z == error "acot: acot undefined on this coefficient domain"
asec z == error "asec: asec undefined on this coefficient domain"
acsc z == error "acsc: acsc undefined on this coefficient domain"

sinh uts ==
  zero? coefficient(uts,0) =>
    sinhx := cSinh monomial(1,1)
    iCompose(sinhx,uts)
  error concat("sinh: ",ZERO)

cosh uts ==
  zero? coefficient(uts,0) =>
    coshx := cCosh monomial(1,1)
    iCompose(coshx,uts)
  error concat("cosh: ",ZERO)

tanh uts ==
  zero? coefficient(uts,0) =>
    tanhx := cTanh monomial(1,1)
    iCompose(tanhx,uts)
  error concat("tanh: ",ZERO)

coth uts ==
  zero? uts => error "coth: coth(0) is undefined"
  zero? coefficient(uts,0) => error concat("coth: ",NPOWERS)
  error concat("coth: ",ZERO)

sech uts ==
  zero? coefficient(uts,0) =>
    sechx := cSech monomial(1,1)
    iCompose(sechx,uts)
  error concat("sech: ",ZERO)

csch uts ==
  zero? uts => error "csch: csch(0) is undefined"
  zero? coefficient(uts,0) => error concat("csch: ",NPOWERS)
  error concat("csch: ",ZERO)

asinh uts ==
  zero? coefficient(uts,0) =>
    asinhx := cAsinh monomial(1,1)
    iCompose(asinhx,uts)
```

```
          error concat("asinh: ",ZERO)

        atanh uts ==
          zero? coefficient(uts,0) =>
            atanhx := cAtanh monomial(1,1)
            iCompose(atanhx,uts)
          error concat("atanh: ",ZERO)

        acosh uts == error "acosh: acosh undefined on this coefficient domain"
        acoth uts == error "acoth: acoth undefined on this coefficient domain"
        asech uts == error "asech: asech undefined on this coefficient domain"
        acsch uts == error "acsch: acsch undefined on this coefficient domain"

    if Coef has Field then
      if Coef has Algebra Fraction Integer then

        (uts:%) ** (r:Coef) ==
--          not one? coefficient(uts,1) =>
          not (coefficient(uts,1) = 1) =>
            error "**: constant coefficient should be 1"
          cPower(uts,r)

--% OutputForms

    coerce(x:%): OUT ==
      count : NNI := _$streamCount$Lisp
      extend(x,count)
      seriesToOutputForm(getStream x,getRef x,variable x,center x,1)
```

———-

— SUTS.dotabb —

```
"SUTS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SUTS"]
"UTSCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=UTSCAT"]
"SUTS" -> "UTSCAT"
```

———-

20.23 domain SHDP SplitHomogeneousDirectProduct

— SplitHomogeneousDirectProduct.input —

```
)set break resume
```

```
)sys rm -f SplitHomogeneousDirectProduct.output
)spool SplitHomogeneousDirectProduct.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SplitHomogeneousDirectProduct
--R
--R SplitHomogeneousDirectProduct(dimtot: NonNegativeInteger,dim1: NonNegativeInteger,S: OrderedAbelianMono
--R Abbreviation for SplitHomogeneousDirectProduct is SHDP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SHDP
--R
--R------------------------------ Operations --------------------------------
--R -? : % -> % if S has RING             1 : () -> % if S has MONOID
--R 0 : () -> % if S has CABMON           coerce : % -> Vector(S)
--R copy : % -> %                         directProduct : Vector(S) -> %
--R ?.? : (%,Integer) -> S                elt : (%,Integer,S) -> S
--R empty : () -> %                       empty? : % -> Boolean
--R entries : % -> List(S)                eq? : (%,%) -> Boolean
--R index? : (Integer,%) -> Boolean       indices : % -> List(Integer)
--R map : ((S -> S),%) -> %               qelt : (%,Integer) -> S
--R sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?*? : (PositiveInteger,%) -> % if S has ABELSG
--R ?*? : (NonNegativeInteger,%) -> % if S has CABMON
--R ?*? : (S,%) -> % if S has RING
--R ?*? : (%,S) -> % if S has RING
--R ?*? : (%,%) -> % if S has MONOID
--R ?*? : (Integer,%) -> % if S has RING
--R ?**? : (%,PositiveInteger) -> % if S has MONOID
--R ?**? : (%,NonNegativeInteger) -> % if S has MONOID
--R ?+? : (%,%) -> % if S has ABELSG
--R ?-? : (%,%) -> % if S has RING
--R ?/? : (%,S) -> % if S has FIELD
--R ?<? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?<=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R ?>? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R ?>=? : (%,%) -> Boolean if S has OAMONS or S has ORDRING
--R D : (%,(S -> S)) -> % if S has RING
--R D : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R D : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R D : % -> % if S has DIFRING and S has RING
--R ?^? : (%,PositiveInteger) -> % if S has MONOID
```

```
--R ?^? : (%,NonNegativeInteger) -> % if S has MONOID
--R abs : % -> % if S has ORDRING
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R characteristic : () -> NonNegativeInteger if S has RING
--R coerce : S -> % if S has SETCAT
--R coerce : Fraction(Integer) -> % if S has RETRACT(FRAC(INT)) and S has SETCAT
--R coerce : Integer -> % if S has RETRACT(INT) and S has SETCAT or S has RING
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R differentiate : (%,(S -> S)) -> % if S has RING
--R differentiate : (%,(S -> S),NonNegativeInteger) -> % if S has RING
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if S has PDRING(SYMBOL) and S
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,List(Symbol)) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,Symbol) -> % if S has PDRING(SYMBOL) and S has RING
--R differentiate : (%,NonNegativeInteger) -> % if S has DIFRING and S has RING
--R differentiate : % -> % if S has DIFRING and S has RING
--R dimension : () -> CardinalNumber if S has FIELD
--R dot : (%,%) -> S if S has RING
--R entry? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,S) -> % if $ has shallowlyMutable
--R first : % -> S if Integer has ORDSET
--R hash : % -> SingleInteger if S has SETCAT
--R index : PositiveInteger -> % if S has FINITE
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R lookup : % -> PositiveInteger if S has FINITE
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if S has OAMONS or S has ORDRING
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R min : (%,%) -> % if S has OAMONS or S has ORDRING
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R negative? : % -> Boolean if S has ORDRING
--R one? : % -> Boolean if S has MONOID
--R parts : % -> List(S) if $ has finiteAggregate
--R positive? : % -> Boolean if S has ORDRING
--R qsetelt! : (%,Integer,S) -> S if $ has shallowlyMutable
--R random : () -> % if S has FINITE
--R recip : % -> Union(%,"failed") if S has MONOID
--R reducedSystem : Matrix(%) -> Matrix(S) if S has RING
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(S),vec: Vector(S)) if S has RING
```

```
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if S has LINE
--R reducedSystem : Matrix(%) -> Matrix(Integer) if S has LINEXP(INT) and S has RING
--R retract : % -> S if S has SETCAT
--R retract : % -> Fraction(Integer) if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retract : % -> Integer if S has RETRACT(INT) and S has SETCAT
--R retractIfCan : % -> Union(S,"failed") if S has SETCAT
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if S has RETRACT(FRAC(INT)) and S has SETCAT
--R retractIfCan : % -> Union(Integer,"failed") if S has RETRACT(INT) and S has SETCAT
--R setelt : (%,Integer,S) -> S if $ has shallowlyMutable
--R sign : % -> Integer if S has ORDRING
--R size : () -> NonNegativeInteger if S has FINITE
--R size? : (%,NonNegativeInteger) -> Boolean
--R subtractIfCan : (%,%) -> Union(%,"failed") if S has CABMON
--R sup : (%,%) -> % if S has OAMONS
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R unitVector : PositiveInteger -> % if S has RING
--R zero? : % -> Boolean if S has CABMON
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— SplitHomogeneousDirectProduct.help —

```
=====================================================================
SplitHomogeneousDirectProduct examples
=====================================================================

See Also:
o )show SplitHomogeneousDirectProduct
```

———-

20.23.1 SplitHomogeneousDirectProduct (SHDP)



See

⇒ "OrderedDirectProduct" (ODP) 16.13.1 on page 1783
⇒ "HomogeneousDirectProduct" (HDP) 9.9.1 on page 1142

Exports:

0	1	abs	any?	characteristic
coerce	copy	count	D	differentiate
dimension	directProduct	dot	elt	empty
empty?	entries	entry?	eq?	eval
every?	fill!	first	hash	index
index?	indices	latex	less?	lookup
map	map!	max	maxIndex	member?
members	min	minIndex	more?	negative?
one?	parts	positive?	qelt	qsetelt!
random	recip	reducedSystem	retract	retractIfCan
sample	setelt	sign	size	size?
subtractIfCan	sup	swap!	unitVector	zero?
#?	?*?	?**?	?+?	?-?
?/?	?<?	?<=?	?=?	?>?
?>=?	?^?	?~=?	-?	?.?

— domain SHDP SplitHomogeneousDirectProduct —

```
)abbrev domain SHDP SplitHomogeneousDirectProduct
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors: Vector, DirectProduct
++ Also See: OrderedDirectProduct, HomogeneousDirectProduct
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type represents the finite direct or cartesian product of an
```

```
++ underlying ordered component type. The vectors are ordered as if
++ they were split into two blocks. The dim1 parameter specifies the
++ length of the first block. The ordering is lexicographic between
++ the blocks but acts like \spadtype{HomogeneousDirectProduct}
++ within each block. This type is a suitable third argument for
++ \spadtype{GeneralDistributedMultivariatePolynomial}.

SplitHomogeneousDirectProduct(dimtot,dim1,S) : T == C where
   NNI ==> NonNegativeInteger
   dim1,dimtot : NNI
   S         : OrderedAbelianMonoidSup

   T == DirectProductCategory(dimtot,S)
   C == DirectProduct(dimtot,S) add
        Rep:=Vector(S)
        lessThanRlex(v1:%,v2:%,low:NNI,high:NNI):Boolean ==
 -- reverse lexicographical ordering
          n1:S:=0
          n2:S:=0
          for i in low..high repeat
            n1:= n1+qelt(v1,i)
            n2:=n2+qelt(v2,i)
          n1<n2 => true
          n2<n1 => false
          for i in reverse(low..high) repeat
            if qelt(v2,i) < qelt(v1,i) then return true
            if qelt(v1,i) < qelt(v2,i) then return false
          false

        (v1:% < v2:%):Boolean ==
          lessThanRlex(v1,v2,1,dim1) => true
          for i in 1..dim1 repeat
                if qelt(v1,i) ^= qelt(v2,i) then return false
          lessThanRlex(v1,v2,dim1+1,dimtot)
```

———-

— **SHDP.dotabb** —

```
"SHDP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SHDP"]
"DIRPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=DIRPCAT"]
"SHDP" -> "DIRPCAT"
```

———-

20.24 domain SPLNODE SplittingNode

— SplittingNode.input —

```
)set break resume
)sys rm -f SplittingNode.output
)spool SplittingNode.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SplittingNode
--R
--R SplittingNode(V: Join(SetCategory,Aggregate),C: Join(SetCategory,Aggregate))  is a domain co
--R Abbreviation for SplittingNode is SPLNODE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SPLNODE
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                coerce : % -> OutputForm
--R condition : % -> C                    construct : (V,C) -> %
--R construct : (V,C,Boolean) -> %        copy : % -> %
--R empty : () -> %                       empty? : % -> Boolean
--R hash : % -> SingleInteger             latex : % -> String
--R setCondition! : (%,C) -> %            setEmpty! : % -> %
--R setStatus! : (%,Boolean) -> %         setValue! : (%,V) -> %
--R status : % -> Boolean                 value : % -> V
--R ?~=? : (%,%) -> Boolean
--R construct : (V,List(C)) -> List(%)
--R construct : List(Record(val: V,tower: C)) -> List(%)
--R construct : Record(val: V,tower: C) -> %
--R infLex? : (%,%,((V,V) -> Boolean),((C,C) -> Boolean)) -> Boolean
--R subNode? : (%,%,((C,C) -> Boolean)) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— SplittingNode.help —

```
=====================================================================
SplittingNode examples
=====================================================================
```

```
See Also:
o )show SplittingNode
```

———-

20.24.1 SplittingNode (SPLNODE)



See

⇒ “SplittingNode” (SPLNODE) 20.24.1 on page 2479

Exports:

coerce	condition	construct	copy	empty
empty?	hash	infLex?	latex	setCondition!
setEmpty!	setStatus!	setValue!	status	subNode?
value	?=?	?~=?		

— domain SPLNODE SplittingNode —

```
)abbrev domain SPLNODE SplittingNode
++ Author: Marc Moereno Maza
++ Date Created: 07/05/1996
++ Date Last Updated:  07/19/1996
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ References:
++ Description:
++ This domain exports a modest implementation for the
++ vertices of splitting trees. These vertices are called
++ here splitting nodes. Every of these nodes store 3 informations.
++ The first one is its value, that is the current expression
++ to evaluate. The second one is its condition, that is the
++ hypothesis under which the value has to be evaluated.
```

```
++ The last one is its status, that is a boolean flag
++ which is true iff the value is the result of its
++ evaluation under its condition. Two splitting vertices
++ are equal iff they have the sane values and the same
++ conditions (so their status do not matter).

SplittingNode(V,C) : Exports == Implementation where

  V:Join(SetCategory,Aggregate)
  C:Join(SetCategory,Aggregate)
  Z ==> Integer
  B ==> Boolean
  O ==> OutputForm
  VT ==> Record(val:V, tower:C)
  VTB ==> Record(val:V, tower:C, flag:B)

  Exports ==  SetCategory with

     empty : () -> %
       ++ \axiom{empty()} returns the same as
       ++ \axiom{[empty()$V,empty()$C,false]$%}
     empty? : % -> B
       ++ \axiom{empty?(n)} returns true iff the node n is \axiom{empty()$%}.
     value : % -> V
       ++ \axiom{value(n)} returns the value of the node n.
     condition : % -> C
       ++ \axiom{condition(n)} returns the condition of the node n.
     status : % -> B
       ++ \axiom{status(n)} returns the status of the node n.
     construct : (V,C,B) -> %
       ++ \axiom{construct(v,t,b)} returns the non-empty node with
       ++ value v, condition t and flag b
     construct : (V,C) -> %
       ++ \axiom{construct(v,t)} returns the same as
       ++ \axiom{construct(v,t,false)}
     construct : VT ->  %
       ++ \axiom{construct(vt)} returns the same as
       ++ \axiom{construct(vt.val,vt.tower)}
     construct : List VT ->  List %
       ++ \axiom{construct(lvt)} returns the same as
       ++ \axiom{[construct(vt.val,vt.tower) for vt in lvt]}
     construct : (V, List C) -> List %
       ++ \axiom{construct(v,lt)} returns the same as
       ++ \axiom{[construct(v,t) for t in lt]}
     copy : % -> %
       ++ \axiom{copy(n)} returns a copy of n.
     setValue! : (%,V) -> %
       ++ \axiom{setValue!(n,v)} returns n whose value
       ++ has been replaced by v if it is not
       ++ empty, else an error is produced.
```

```
    setCondition! : (%,C) -> %
      ++ \axiom{setCondition!(n,t)} returns n whose condition
      ++ has been replaced by t if it is not
      ++ empty, else an error is produced.
    setStatus!: (%,B) -> %
      ++ \axiom{setStatus!(n,b)} returns n whose status
      ++ has been replaced by b if it is not
      ++ empty, else an error is produced.
    setEmpty! : % -> %
      ++ \axiom{setEmpty!(n)} replaces n by \axiom{empty()$%}.
    infLex? : (%,%,(V,V) -> B,(C,C) -> B) -> B
      ++ \axiom{infLex?(n1,n2,o1,o2)} returns true iff
      ++ \axiom{o1(value(n1),value(n2))} or
      ++ \axiom{value(n1) = value(n2)} and
      ++ \axiom{o2(condition(n1),condition(n2))}.
    subNode? : (%,%,(C,C) -> B) -> B
      ++ \axiom{subNode?(n1,n2,o2)} returns true iff
      ++ \axiom{value(n1) = value(n2)} and
      ++ \axiom{o2(condition(n1),condition(n2))}

  Implementation == add

    Rep ==> VTB

    rep(n:%):Rep == n pretend Rep
    per(r:Rep):% == r pretend %

    empty() == per [empty()$V,empty()$C,false]$Rep
    empty?(n:%) == empty?((rep n).val)$V and  empty?((rep n).tower)$C
    value(n:%) == (rep n).val
    condition(n:%) == (rep n).tower
    status(n:%) == (rep n).flag
    construct(v:V,t:C,b:B) ==  per [v,t,b]$Rep
    construct(v:V,t:C) == [v,t,false]$%
    construct(vt:VT) == [vt.val,vt.tower]$%
    construct(lvt:List VT) == [[vt]$% for vt in lvt]
    construct(v:V,lt: List C) == [[v,t]$% for t in lt]
    copy(n:%) == per copy rep n
    setValue!(n:%,v:V) ==
       (rep n).val := v
       n
    setCondition!(n:%,t:C) ==
       (rep n).tower := t
       n
    setStatus!(n:%,b:B) ==
       (rep n).flag := b
       n
    setEmpty!(n:%) ==
       (rep n).val := empty()$V
       (rep n).tower := empty()$C
```

```
      n
   infLex?(n1,n2,o1,o2) ==
      o1((rep n1).val,(rep n2).val) => true
      (rep n1).val = (rep n2).val =>
         o2((rep n1).tower,(rep n2).tower)
      false
   subNode?(n1,n2,o2) ==
      (rep n1).val = (rep n2).val =>
         o2((rep n1).tower,(rep n2).tower)
      false
   -- sample() == empty()
   n1:% = n2:% ==
      (rep n1).val ~= (rep n2).val => false
      (rep n1).tower = (rep n2).tower
   n1:% ~= n2:% ==
      (rep n1).val = (rep n2).val => false
      (rep n1).tower ~= (rep n2).tower
   coerce(n:%):O ==
      l1,l2,l3,l : List O
      l1 := [message("value == "), ((rep n).val)::O]
      o1 : O := blankSeparate l1
      l2 := [message(" tower == "), ((rep n).tower)::O]
      o2 : O := blankSeparate l2
      if ((rep n).flag)
        then
          o3 := message(" closed == true")
        else
          o3 := message(" closed == false")
      l := [o1,o2,o3]
      bracket commaSeparate l
```

———-

— SPLNODE.dotabb —

```
"SPLNODE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SPLNODE"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"TYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TYPE"]
"SPLNODE" -> "BASTYPE"
"SPLNODE" -> "KOERCE"
"SPLNODE" -> "TYPE"
```

———-

20.25 domain SPLTREE SplittingTree

— SplittingTree.input —

```
)set break resume
)sys rm -f SplittingTree.output
)spool SplittingTree.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SplittingTree
--R
--R SplittingTree(V: Join(SetCategory,Aggregate),C: Join(SetCategory,Aggregate))  is a domain constructor
--R Abbreviation for SplittingTree is SPLTREE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SPLTREE
--R
--R------------------------------ Operations --------------------------------
--R children : % -> List(%)               conditions : % -> List(C)
--R construct : (V,C,V,List(C)) -> %      construct : (V,C,List(%)) -> %
--R copy : % -> %                         cyclic? : % -> Boolean
--R distance : (%,%) -> Integer           empty : () -> %
--R empty? : % -> Boolean                 eq? : (%,%) -> Boolean
--R leaf? : % -> Boolean                  nodes : % -> List(%)
--R sample : () -> %                     updateStatus! : % -> %
--R value : % -> SplittingNode(V,C)
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if SplittingNode(V,C) has SETCAT
--R any? : ((SplittingNode(V,C) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if SplittingNode(V,C) has SETCAT
--R coerce : % -> OutputForm if SplittingNode(V,C) has SETCAT
--R construct : (V,C,List(SplittingNode(V,C))) -> %
--R construct : SplittingNode(V,C) -> %
--R count : (SplittingNode(V,C),%) -> NonNegativeInteger if $ has finiteAggregate and SplittingNode(V,C) has
--R count : ((SplittingNode(V,C) -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R ?.value : (%,value) -> SplittingNode(V,C)
--R eval : (%,List(SplittingNode(V,C)),List(SplittingNode(V,C))) -> % if SplittingNode(V,C) has EVALAB(SPLNO
--R eval : (%,SplittingNode(V,C),SplittingNode(V,C)) -> % if SplittingNode(V,C) has EVALAB(SPLNODE(V,C)) and
--R eval : (%,Equation(SplittingNode(V,C))) -> % if SplittingNode(V,C) has EVALAB(SPLNODE(V,C)) and Splittin
--R eval : (%,List(Equation(SplittingNode(V,C)))) -> % if SplittingNode(V,C) has EVALAB(SPLNODE(V,C)) and Sp
--R every? : ((SplittingNode(V,C) -> Boolean),%) -> Boolean if $ has finiteAggregate
--R extractSplittingLeaf : % -> Union(%,"failed")
--R hash : % -> SingleInteger if SplittingNode(V,C) has SETCAT
--R latex : % -> String if SplittingNode(V,C) has SETCAT
--R leaves : % -> List(SplittingNode(V,C))
--R less? : (%,NonNegativeInteger) -> Boolean
```

```
--R map : ((SplittingNode(V,C) -> SplittingNode(V,C)),%) -> %
--R map! : ((SplittingNode(V,C) -> SplittingNode(V,C)),%) -> % if $ has shallowlyMutable
--R member? : (SplittingNode(V,C),%) -> Boolean if $ has finiteAggregate and SplittingNode(V,C)
--R members : % -> List(SplittingNode(V,C)) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if SplittingNode(V,C) has SETCAT
--R nodeOf? : (SplittingNode(V,C),%) -> Boolean
--R parts : % -> List(SplittingNode(V,C)) if $ has finiteAggregate
--R remove : (SplittingNode(V,C),%) -> %
--R remove! : (SplittingNode(V,C),%) -> %
--R result : % -> List(Record(val: V,tower: C))
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,value,SplittingNode(V,C)) -> SplittingNode(V,C) if $ has shallowlyMutable
--R setvalue! : (%,SplittingNode(V,C)) -> SplittingNode(V,C) if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R splitNodeOf! : (%,%,List(SplittingNode(V,C)),((C,C) -> Boolean)) -> %
--R splitNodeOf! : (%,%,List(SplittingNode(V,C))) -> %
--R subNodeOf? : (SplittingNode(V,C),%,((C,C) -> Boolean)) -> Boolean
--R ?~=? : (%,%) -> Boolean if SplittingNode(V,C) has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— SplittingTree.help —

```
=====================================================================
SplittingTree examples
=====================================================================

See Also:
o )show SplittingTree
```

———-

20.25.1 SplittingTree (SPLTREE)



See

⇒ "SplittingTree" (SPLTREE) 20.25.1 on page 2485

Exports:

any?	child?	children	coerce
conditions	construct	copy	count
cyclic?	distance	empty	empty?
eq?	eval	every?	extractSplittingLeaf
hash	latex	leaf?	leaves
less?	map	map!	member?
members	more?	node?	nodeOf?
nodes	parts	remove	remove!
result	sample	setchildren!	setelt
setvalue!	size?	splitNodeOf!	splitNodeOf!
subNodeOf?	updateStatus!	value	# ?
?=?	?.value	?~=?	

— domain SPLTREE SplittingTree —

```
)abbrev domain SPLTREE SplittingTree
++ Author: Marc Moereno Maza
++ Date Created: 07/05/1996
++ Date Last Updated:  07/19/1996
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++      M. MORENO MAZA "Calculs de pgcd au-dessus des tours
++      d'extensions simples et resolution des systemes d'equations
++      algebriques" These, Universite P.etM. Curie, Paris, 1997.
++ Description:
++ This domain exports a modest implementation of splitting
++ trees. Spliiting trees are needed when the
```

```
++ evaluation of some quantity under some hypothesis
++ requires to split the hypothesis into sub-cases.
++ For instance by adding some new hypothesis on one
++ hand and its negation on another hand. The computations
++ are terminated is a splitting tree \axiom{a} when
++ \axiom{status(value(a))} is \axiom{true}. Thus,
++ if for the splitting tree \axiom{a} the flag
++ \axiom{status(value(a))} is \axiom{true}, then
++ \axiom{status(value(d))} is \axiom{true} for any
++ subtree \axiom{d} of \axiom{a}. This property
++ of splitting trees is called the termination
++ condition. If no vertex in a splitting tree \axiom{a}
++ is equal to another, \axiom{a} is said to satisfy
++ the no-duplicates condition. The splitting
++ tree \axiom{a} will satisfy this condition
++ if nodes are added to \axiom{a} by mean of
++ \axiom{splitNodeOf!} and if \axiom{construct}
++ is only used to create the root of \axiom{a}
++ with no children.

SplittingTree(V,C) : Exports == Implementation where

  V:Join(SetCategory,Aggregate)
  C:Join(SetCategory,Aggregate)
  B ==> Boolean
  O ==> OutputForm
  NNI ==> NonNegativeInteger
  VT ==> Record(val:V, tower:C)
  VTB ==> Record(val:V, tower:C, flag:B)
  S ==> SplittingNode(V,C)
  A ==> Record(root:S,subTrees:List(%))

  Exports ==  RecursiveAggregate(S) with
     shallowlyMutable
     finiteAggregate
     extractSplittingLeaf : % -> Union(%,"failed")
       ++ \axiom{extractSplittingLeaf(a)} returns the left
       ++ most leaf (as a tree) whose status is false
       ++ if any, else "failed" is returned.
     updateStatus! : % -> %
       ++ \axiom{updateStatus!(a)} returns a where the status
       ++ of the vertices are updated to satisfy
       ++ the "termination condition".
     construct : S -> %
       ++ \axiom{construct(s)} creates a splitting tree
       ++ with value (i.e. root vertex) given by
       ++ \axiom{s} and no children. Thus, if the
       ++ status of \axiom{s} is false, \axiom{[s]}
       ++ represents the starting point of the
       ++ evaluation \axiom{value(s)} under the
```

```
    ++ hypothesis \axiom{condition(s)}.
  construct : (V,C, List %) -> %
    ++ \axiom{construct(v,t,la)} creates a splitting tree
    ++ with value (i.e. root vertex) given by
    ++ \axiom{[v,t]$S} and with \axiom{la} as
    ++ children list.
  construct : (V,C,List S) -> %
    ++ \axiom{construct(v,t,ls)} creates a splitting tree
    ++ with value (i.e. root vertex) given by
    ++ \axiom{[v,t]$S} and with children list given by
    ++ \axiom{[[s]$% for s in ls]}.
  construct : (V,C,V,List C) -> %
    ++ \axiom{construct(v1,t,v2,lt)} creates a splitting tree
    ++ with value (i.e. root vertex) given by
    ++ \axiom{[v,t]$S} and with children list given by
    ++ \axiom{[[[v,t]$S]$% for s in ls]}.
  conditions : % -> List C
    ++ \axiom{conditions(a)} returns the list of the conditions
    ++ of the leaves of a
  result : % -> List VT
    ++ \axiom{result(a)} where \axiom{ls} is the leaves list of \axiom{a}
    ++ returns \axiom{[[value(s),condition(s)]$VT for s in ls]}
    ++ if the computations are terminated in \axiom{a} else
    ++ an error is produced.
  nodeOf? : (S,%) -> B
    ++ \axiom{nodeOf?(s,a)} returns true iff some node of \axiom{a}
    ++ is equal to \axiom{s}
  subNodeOf? : (S,%,(C,C) -> B) -> B
    ++ \axiom{subNodeOf?(s,a,sub?)} returns true iff for some node
    ++ \axiom{n} in \axiom{a} we have \axiom{s = n} or
    ++ \axiom{status(n)} and \axiom{subNode?(s,n,sub?)}.
  remove : (S,%) -> %
    ++ \axiom{remove(s,a)} returns the splitting tree obtained
    ++ from a by removing every sub-tree \axiom{b} such
    ++ that \axiom{value(b)} and \axiom{s} have the same
    ++ value, condition and status.
  remove! : (S,%) -> %
    ++ \axiom{remove!(s,a)} replaces a by remove(s,a)
  splitNodeOf! : (%,%,List(S)) -> %
    ++ \axiom{splitNodeOf!(l,a,ls)} returns \axiom{a} where the children
    ++ list of \axiom{l} has been set to
    ++ \axiom{[[s]$% for s in ls | not nodeOf?(s,a)]}.
    ++ Thus, if \axiom{l} is not a node of \axiom{a}, this
    ++ latter splitting tree is unchanged.
  splitNodeOf! : (%,%,List(S),(C,C) -> B) -> %
    ++ \axiom{splitNodeOf!(l,a,ls,sub?)} returns \axiom{a} where the children
    ++ list of \axiom{l} has been set to
    ++ \axiom{[[s]$% for s in ls | not subNodeOf?(s,a,sub?)]}.
    ++ Thus, if \axiom{l} is not a node of \axiom{a}, this
    ++ latter splitting tree is unchanged.
```

```
Implementation == add

   Rep ==> A

   rep(n:%):Rep == n pretend Rep
   per(r:Rep):% == r pretend %

   construct(s:S) ==
      per [s,[]]$A
   construct(v:V,t:C,la:List(%)) ==
      per [[v,t]$S,la]$A
   construct(v:V,t:C,ls:List(S)) ==
      per [[v,t]$S,[[s]$% for s in ls]]$A
   construct(v1:V,t:C,v2:V,lt:List(C)) ==
      [v1,t,([v2,lt]$S)@(List S)]$%

   empty?(a:%) == empty?((rep a).root) and empty?((rep a).subTrees)
   empty() == [empty()$S]$%

   remove(s:S,a:%) ==
     empty? a => a
     (s = value(a)) and (status(s) = status(value(a))) => empty()$%
     la := children(a)
     lb : List % := []
     while (not empty? la) repeat
        lb := cons(remove(s,first la), lb)
        la := rest la
     lb := reverse remove(empty?,lb)
     [value(value(a)),condition(value(a)),lb]$%

   remove!(s:S,a:%) ==
     empty? a => a
     (s = value(a)) and (status(s) = status(value(a))) =>
       (rep a).root := empty()$S
       (rep a).subTrees := []
       a
     la := children(a)
     lb : List % := []
     while (not empty? la) repeat
        lb := cons(remove!(s,first la), lb)
        la := rest la
     lb := reverse remove(empty()$%,lb)
     setchildren!(a,lb)

   value(a:%) ==
      (rep a).root
   children(a:%) ==
      (rep a).subTrees
```

```
leaf?(a:%) ==
   empty? a => false
   empty? (rep a).subTrees
setchildren!(a:%,la:List(%)) ==
   (rep a).subTrees := la
   a
setvalue!(a:%,s:S) ==
   (rep a).root := s
   s
cyclic?(a:%) == false
map(foo:(S -> S),a:%) ==
  empty? a => a
  b : % := [foo(value(a))]$%
  leaf? a => b
  setchildren!(b,[map(foo,c) for c in children(a)])
map!(foo:(S -> S),a:%) ==
  empty? a => a
  setvalue!(a,foo(value(a)))
  leaf? a => a
  setchildren!(a,[map!(foo,c) for c in children(a)])
copy(a:%) ==
  map(copy,a)
eq?(a1:%,a2:%) ==
  error"in eq? from SPLTREE : la vache qui rit est-elle folle?"
nodes(a:%) ==
  empty? a => []
  leaf? a => [a]
  cons(a,concat([nodes(c) for c in children(a)]))
leaves(a:%) ==
  empty? a => []
  leaf? a => [value(a)]
  concat([leaves(c) for c in children(a)])
members(a:%) ==
  empty? a => []
  leaf? a => [value(a)]
  cons(value(a),concat([members(c) for c in children(a)]))
#(a:%) ==
  empty? a => 0$NNI
  leaf? a => 1$NNI
  reduce("+",[#c for c in children(a)],1$NNI)$(List NNI)
a1:% = a2:% ==
  empty? a1 => empty? a2
  empty? a2 => false
  leaf? a1 =>
    not leaf? a2 => false
    value(a1) =$S value(a2)
  leaf? a2 => false
  value(a1) ~=$S value(a2) => false
  children(a1) = children(a2)
-- sample() == [sample()$S]$%
```

```
localCoerce(a:%,k:NNI):O ==
  s : String
  if k = 1 then  s := "* " else s := "-> "
  for i in 2..k repeat s := concat("-+",s)$String
  ro : O := left(hconcat(message(s)$O,value(a)::O)$O)$O
  leaf? a => ro
  lo : List O := [localCoerce(c,k+1) for c in children(a)]
  lo := cons(ro,lo)
  vconcat(lo)$O
coerce(a:%):O ==
  empty? a => vconcat(message(" ")$O,message("* []")$O)
  vconcat(message(" ")$O,localCoerce(a,1))

extractSplittingLeaf(a:%) ==
  empty? a => "failed"::Union(%,"failed")
  status(value(a))$S => "failed"::Union(%,"failed")
  la := children(a)
  empty? la => a
  while (not empty? la) repeat
     esl := extractSplittingLeaf(first la)
     (esl case %) => return(esl)
     la := rest la
  "failed"::Union(%,"failed")

updateStatus!(a:%) ==
  la := children(a)
  (empty? la) or (status(value(a))$S) => a
  done := true
  while (not empty? la) and done repeat
     done := done and status(value(updateStatus! first la))
     la := rest la
  setStatus!(value(a),done)$S
  a

result(a:%) ==
  empty? a => []
  not status(value(a))$S =>
     error"in result from SLPTREE : mad cow!"
  ls : List S := leaves(a)
  [[value(s),condition(s)]$VT for s in ls]

conditions(a:%) ==
  empty? a => []
  ls : List S := leaves(a)
  [condition(s) for s in ls]

nodeOf?(s:S,a:%) ==
  empty? a => false
  s =$S value(a) => true
  la := children(a)
```

```
      while (not empty? la) and (not nodeOf?(s,first la)) repeat
         la := rest la
      not empty? la

    subNodeOf?(s:S,a:%,sub?:((C,C) -> B)) ==
      empty? a => false
      -- s =$S value(a) => true
      status(value(a)$%)$S and subNode?(s,value(a),sub?)$S => true
      la := children(a)
      while (not empty? la) and (not subNodeOf?(s,first la,sub?)) repeat
         la := rest la
      not empty? la

    splitNodeOf!(l:%,a:%,ls:List(S)) ==
      ln := removeDuplicates ls
      la : List % := []
      while not empty? ln repeat
         if not nodeOf?(first ln,a)
           then
             la := cons([first ln]$%, la)
         ln := rest ln
      la := reverse la
      setchildren!(l,la)$%
      if empty? la then (rep l).root := [empty()$V,empty()$C,true]$S
      updateStatus!(a)

    splitNodeOf!(l:%,a:%,ls:List(S),sub?:((C,C) -> B)) ==
      ln := removeDuplicates ls
      la : List % := []
      while not empty? ln repeat
         if not subNodeOf?(first ln,a,sub?)
           then
             la := cons([first ln]$%, la)
         ln := rest ln
      la := reverse la
      setchildren!(l,la)$%
      if empty? la then (rep l).root := [empty()$V,empty()$C,true]$S
      updateStatus!(a)
```

———-

— SPLTREE.dotabb —

```
"SPLTREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SPLTREE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"SPLTREE" -> "STRING"
```

———-

20.26 domain SREGSET SquareFreeRegularTriangularSet

— SquareFreeRegularTriangularSet.input —

```
)set break resume
)sys rm -f SquareFreeRegularTriangularSet.output
)spool SquareFreeRegularTriangularSet.output
)set message test on
)set message auto off
)clear all
--S 1 of 23
R := Integer
--R
--R
--R   (1)  Integer
--R                                                          Type: Domain
--E 1

--S 2 of 23
ls : List Symbol := [x,y,z,t]
--R
--R
--R   (2)  [x,y,z,t]
--R                                                    Type: List(Symbol)
--E 2

--S 3 of 23
V := OVAR(ls)
--R
--R
--R   (3)  OrderedVariableList([x,y,z,t])
--R                                                          Type: Domain
--E 3

--S 4 of 23
E := IndexedExponents V
--R
--R
--R   (4)  IndexedExponents(OrderedVariableList([x,y,z,t]))
--R                                                          Type: Domain
--E 4

--S 5 of 23
P := NSMP(R, V)
--R
--R
--R   (5)
--R   NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
```

```
--R                                                                    Type: Domain
--E 5

--S 6 of 23
x: P := 'x
--R
--R
--R   (6)  x
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 6

--S 7 of 23
y: P := 'y
--R
--R
--R   (7)  y
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 7

--S 8 of 23
z: P := 'z
--R
--R
--R   (8)  z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 8

--S 9 of 23
t: P := 't
--R
--R
--R   (9)  t
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 9

--S 10 of 23
ST := SREGSET(R,E,V,P)
--R
--R
--R   (10)
--R  SquareFreeRegularTriangularSet(Integer,IndexedExponents(OrderedVariableList([
--R  x,y,z,t])),OrderedVariableList([x,y,z,t]),NewSparseMultivariatePolynomial(Int
--R  eger,OrderedVariableList([x,y,z,t])))
--R                                                                    Type: Domain
--E 10

--S 11 of 23
p1 := x ** 31 - x ** 6 - x - y
--R
--R
```

```
--R          31    6
--R   (11)  x   - x  - x - y
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 11

--S 12 of 23
p2 := x ** 8  - z
--R
--R
--R          8
--R   (12)  x  - z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 12

--S 13 of 23
p3 := x ** 10 - t
--R
--R
--R          10
--R   (13)  x   - t
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 13

--S 14 of 23
lp := [p1, p2, p3]
--R
--R
--R           31    6          8      10
--R   (14)  [x   - x  - x - y,x  - z,x   - t]
--IType: List(NewSparseMultivariatePolynomial(Integer,...
--E 14

--S 15 of 23
zeroSetSplit(lp)$ST
--R
--R
--R            5    4      2     3     8     5    3    2   4                2
--R   (15)  [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z }]
--IType: List(SquareFreeRegularTriangularSet(Integer,...
--E 15

--S 16 of 23
zeroSetSplit(lp,false)$ST
--R
--R
--R   (16)
--R      5    4      2     3     8     5    3    2   4                2
--R   [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z },
--R      3      5            2    2
--R    {t  - 1,z  - t,t y + z ,z x  - t}, {t,z,y,x}]
```

```
--IType: List(SquareFreeRegularTriangularSet(Integer,...
--E 16

--S 17 of 23
T := REGSET(R,E,V,P)
--R
--R
--R   (17)
--R  RegularTriangularSet(Integer,IndexedExponents(OrderedVariableList([x,y,z,t]))
--R  ,OrderedVariableList([x,y,z,t]),NewSparseMultivariatePolynomial(Integer,Order
--R  edVariableList([x,y,z,t])))
--R                                                                  Type: Domain
--E 17

--S 18 of 23
lts := zeroSetSplit(lp,false)$T
--R
--R
--R   (18)
--R      5    4      2     3     8     5    3    2   4                2
--R   [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z },
--R      3      5          2     3         2
--R    {t  - 1,z  - t,t z y  + 2z y + 1,z x  - t}, {t,z,y,x}]
--IType: List(RegularTriangularSet(Integer,IndexedExponents(...
--E 18

--S 19 of 23
ts := lts.2
--R
--R
--R           3      5          2     3         2
--R   (19)  {t  - 1,z  - t,t z y  + 2z y + 1,z x  - t}
--IType: RegularTriangularSet(Integer,IndexedExponents(...
--E 19

--S 20 of 23
pol := select(ts,'y)$T
--R
--R
--R              2     3
--R   (20)  t z y  + 2z y + 1
--IType: Union(NewSparseMultivariatePolynomial(Integer,...
--E 20

--S 21 of 23
tower := collectUnder(ts,'y)$T
--R
--R
--R           3      5
--R   (21)  {t  - 1,z  - t}
```

```
--IType: RegularTriangularSet(Integer,IndexedExponents(...
--E 21

--S 22 of 23
pack := RegularTriangularSetGcdPackage(R,E,V,P,T)
--R
--R
--R   (22)
--R  RegularTriangularSetGcdPackage(Integer,IndexedExponents(OrderedVariableList([
--R  x,y,z,t])),OrderedVariableList([x,y,z,t]),NewSparseMultivariatePolynomial(Int
--R  eger,OrderedVariableList([x,y,z,t])),RegularTriangularSet(Integer,IndexedExpo
--R  nents(OrderedVariableList([x,y,z,t])),OrderedVariableList([x,y,z,t]),NewSpars
--R  eMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t])))))
--R                                                                  Type: Domain
--E 22

--S 23 of 23
toseSquareFreePart(pol,tower)$pack
--R
--R
--R                        2          3      5
--R   (23)  [[val= t y + z ,tower= {t  - 1,z  - t}]]
--IType: List(Record(val: NewSparseMultivariatePolynomial(...
--E 23
)spool
)lisp (bye)
```

———-

— SquareFreeRegularTriangularSet.help —

```
====================================================================
SquareFreeRegularTriangularSet examples
====================================================================

The SquareFreeRegularTriangularSet domain constructor implements
square-free regular triangular sets.  See the RegularTriangularSet
domain constructor for general regular triangular sets.  Let T be a
regular triangular set consisting of polynomials t1, ..., tm ordered
by increasing main variables.  The regular triangular set T is
square-free if T is empty or if t1, ..., tm-1 is square-free and if the
polynomial tm is square-free as a univariate polynomial with coefficients
in the tower of simple extensions associated with t1,...,tm-1.

The main interest of square-free regular triangular sets is that their
associated towers of simple extensions are product of fields.
Consequently, the saturated ideal of a square-free regular triangular
set is radical.  This property simplifies some of the operations
related to regular triangular sets.  However, building square-free
```

```
regular triangular sets is generally more expensive than building
general regular triangular sets.

As the RegularTriangularSet domain constructor, the
SquareFreeRegularTriangularSet domain constructor also implements a
method for solving polynomial systems by means of regular triangular
sets.  This is in fact the same method with some adaptations to take
into account the fact that the computed regular chains are
square-free.  Note that it is also possible to pass from a
decomposition into general regular triangular sets to a decomposition
into square-free regular triangular sets.  This conversion is used
internally by the LazardSetSolvingPackage package constructor.

N.B. When solving polynomial systems with the
SquareFreeRegularTriangularSet domain constructor or the
LazardSetSolvingPackage package constructor, decompositions have no
redundant components.  See also LexTriangularPackage and
ZeroDimensionalSolvePackage for the case of algebraic systems with a
finite number of (complex) solutions.

We shall explain now how to use the constructor SquareFreeRegularTriangularSet.

This constructor takes four arguments.  The first one, R, is the
coefficient ring of the polynomials; it must belong to the category
GcdDomain.  The second one, E, is the exponent monoid of the
polynomials; it must belong to the category OrderedAbelianMonoidSup.
the third one, V, is the ordered set of variables; it must belong to
the category OrderedSet.  The last one is the polynomial ring; it must
belong to the category RecursivePolynomialCategory(R,E,V).  The
abbreviation for SquareFreeRegularTriangularSet} is SREGSET.

Note that the way of understanding triangular decompositions
is detailed in the example of the RegularTriangularSet constructor.

Let us illustrate the use of this constructor with one example
(Donati-Traverso).  Define the coefficient ring.

  R := Integer
    Integer
                                  Type: Domain

Define the list of variables,

  ls : List Symbol := [x,y,z,t]
    [x,y,z,t]
                                  Type: List Symbol

and make it an ordered set;

  V := OVAR(ls)
```

```
    OrderedVariableList [x,y,z,t]
                                Type: Domain
```

then define the exponent monoid.

```
  E := IndexedExponents V
    IndexedExponents OrderedVariableList [x,y,z,t]
                                Type: Domain
```

Define the polynomial ring.

```
  P := NSMP(R, V)
    NewSparseMultivariatePolynomial(Integer,OrderedVariableList [x,y,z,t])
                                Type: Domain
```

Let the variables be polynomial.

```
  x: P := 'x
    x
           Type: NewSparseMultivariatePolynomial(Integer,
                                 OrderedVariableList [x,y,z,t])

  y: P := 'y
    y
           Type: NewSparseMultivariatePolynomial(Integer,
                                 OrderedVariableList [x,y,z,t])

  z: P := 'z
    z
           Type: NewSparseMultivariatePolynomial(Integer,
                                 OrderedVariableList [x,y,z,t])

  t: P := 't
    t
           Type: NewSparseMultivariatePolynomial(Integer,
                                 OrderedVariableList [x,y,z,t])
```

Now call the SquareFreeRegularTriangularSet domain constructor.

```
  ST := SREGSET(R,E,V,P)
  SquareFreeRegularTriangularSet(Integer,IndexedExponents OrderedVariableList [
  x,y,z,t],OrderedVariableList [x,y,z,t],NewSparseMultivariatePolynomial(Intege
  r,OrderedVariableList [x,y,z,t]))
                                 Type: Domain
```

Define a polynomial system.

```
  p1 := x ** 31 - x ** 6 - x - y
      31    6
     x   - x  - x - y
```

```
          Type: NewSparseMultivariatePolynomial(Integer,
                                OrderedVariableList [x,y,z,t])

  p2 := x ** 8  - z
      8
     x  - z
          Type: NewSparseMultivariatePolynomial(Integer,
                                OrderedVariableList [x,y,z,t])

  p3 := x ** 10 - t
      10
     x   - t
          Type: NewSparseMultivariatePolynomial(Integer,
                                OrderedVariableList [x,y,z,t])

  lp := [p1, p2, p3]
       31    6          8      10
     [x   - x  - x - y,x  - z,x   - t]
          Type: List NewSparseMultivariatePolynomial(Integer,
                                     OrderedVariableList [x,y,z,t])
```

First of all, let us solve this system in the sense of Kalkbrener.

```
  zeroSetSplit(lp)$ST
        5    4      2     3     8     5    3    2   4                2
     [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z }]
        Type: List SquareFreeRegularTriangularSet(Integer,
                     IndexedExponents OrderedVariableList [x,y,z,t],
                     OrderedVariableList [x,y,z,t],
                     NewSparseMultivariatePolynomial(Integer,
                        OrderedVariableList [x,y,z,t]))
```

And now in the sense of Lazard (or Wu and other authors).

```
  zeroSetSplit(lp,false)$ST
      5    4      2     3     8     5    3    2   4                2
   [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z },
      3      5           2    2
    {t  - 1,z  - t,t y + z ,z x  - t}, {t,z,y,x}]
        Type: List SquareFreeRegularTriangularSet(Integer,
                     IndexedExponents OrderedVariableList [x,y,z,t],
                     OrderedVariableList [x,y,z,t],
                     NewSparseMultivariatePolynomial(Integer,
                        OrderedVariableList [x,y,z,t]))
```

Now to see the difference with the RegularTriangularSet domain
constructor, we define:

```
  T := REGSET(R,E,V,P)
  RegularTriangularSet(Integer,IndexedExponents OrderedVariableList [x,y,z,t],O
```

```
  rderedVariableList [x,y,z,t],NewSparseMultivariatePolynomial(Integer,OrderedV
  ariableList [x,y,z,t]))
                                  Type: Domain
```

and compute:

```
  lts := zeroSetSplit(lp,false)$T
      5    4      2     3     8     5    3    2   4                2
   [{z  - t ,t z y  + 2z y - t  + 2t  + t  - t ,(t  - t)x - t y - z },
     3      5          2     3         2
    {t  - 1,z  - t,t z y  + 2z y + 1,z x  - t}, {t,z,y,x}]
          Type: List RegularTriangularSet(Integer,
                      IndexedExponents OrderedVariableList [x,y,z,t],
                      OrderedVariableList [x,y,z,t],
                      NewSparseMultivariatePolynomial(Integer,
                         OrderedVariableList [x,y,z,t]))
```

If you look at the second set in both decompositions in the sense of Lazard, you will see that the polynomial with main variable y is not the same.

Let us understand what has happened.

We define:

```
  ts := lts.2
          3      5          2     3         2
   (19)  {t  - 1,z  - t,t z y  + 2z y + 1,z x  - t}
        Type: RegularTriangularSet(Integer,
                IndexedExponents OrderedVariableList [x,y,z,t],
                OrderedVariableList [x,y,z,t],
                NewSparseMultivariatePolynomial(Integer,
                   OrderedVariableList [x,y,z,t]))

  pol := select(ts,'y)$T
         2     3
     t z y  + 2z y + 1
      Type: Union(NewSparseMultivariatePolynomial(Integer,
                             OrderedVariableList [x,y,z,t]),...)

  tower := collectUnder(ts,'y)$T
       3      5
     {t  - 1,z  - t}
      Type: RegularTriangularSet(Integer,
              IndexedExponents OrderedVariableList [x,y,z,t],
              OrderedVariableList [x,y,z,t],
              NewSparseMultivariatePolynomial(Integer,
                 OrderedVariableList [x,y,z,t]))

  pack := RegularTriangularSetGcdPackage(R,E,V,P,T)
  RegularTriangularSetGcdPackage(Integer,IndexedExponents OrderedVariableList [
```

```
  x,y,z,t],OrderedVariableList [x,y,z,t],NewSparseMultivariatePolynomial(Intege
  r,OrderedVariableList [x,y,z,t]),RegularTriangularSet(Integer,IndexedExponent
  s OrderedVariableList [x,y,z,t],OrderedVariableList [x,y,z,t],NewSparseMultiv
  ariatePolynomial(Integer,OrderedVariableList [x,y,z,t]))
                                      Type: Domain
```


Then we compute:

```
  toseSquareFreePart(pol,tower)$pack
                  2          3      5
    [[val= t y + z ,tower= {t  - 1,z  - t}]]
       Type: List Record(val: NewSparseMultivariatePolynomial(Integer,
                                  OrderedVariableList [x,y,z,t]),
                          tower: RegularTriangularSet(Integer,
                            IndexedExponents OrderedVariableList [x,y,z,t],
                            OrderedVariableList [x,y,z,t],
                            NewSparseMultivariatePolynomial(Integer,
                                OrderedVariableList [x,y,z,t])))
```

See Also:
-)help GcdDomain
-)help OrderedAbelianMonoidSup
-)help OrderedSet
-)help RecursivePolynomialCategory
-)help ZeroDimensionalSolvePackage
-)help LexTriangularPackage
-)help LazardSetSolvingPackage
-)help RegularTriangularSet
-)show SquareFreeRegularTriangularSet

———-

20.26.1 SquareFreeRegularTriangularSet (SREGSET)



Exports:

algebraic?	algebraicCoefficients?
algebraicVariables	any?
augment	autoReduced?
basicSet	coerce
coHeight	collect
collectQuasiMonic	collectUnder
collectUpper	convert
construct	copy
count	degree
empty	empty?
eq?	eval
every?	extend
extendIfCan	find
first	hash
headReduce	headReduced?
headRemainder	infRittWu?
initiallyReduce	initiallyReduced?
initials	internalAugment
internalZeroSetSplit	intersect
invertible?	invertibleSet
invertibleElseSplit?	last
lastSubResultant	lastSubResultantElseSplit
less?	latex
mainVariable?	mainVariables
map	map!
member?	members
more?	mvar
normalized?	parts
preprocess	purelyAlgebraic?
purelyAlgebraicLeadingMonomial?	purelyTranscendental?
quasiComponent	reduce
reduceByQuasiMonic	reduced?
remainder	remove
removeDuplicates	removeZero
rest	retract
retractIfCan	rewriteIdealWithHeadRemainder
rewriteIdealWithRemainder	rewriteSetWithReduction
roughBase?	roughEqualIdeals?
roughSubIdeal?	roughUnitIdeal?
sample	select
size?	sort
squareFreePart	stronglyReduce
stronglyReduced?	triangular?
trivialIdeal?	variables
zeroSetSplit	zeroSetSplitIntoTriangularSystems
#?	?=?
?~=?	

— domain SREGSET SquareFreeRegularTriangularSet —

```
)abbrev domain SREGSET SquareFreeRegularTriangularSet
++ Author: Marc Moreno Maza
++ Date Created: 08/25/1998
++ Date Last Updated: 16/12/1998
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References :
++  [1] M. MORENO MAZA "A new algorithm for computing triangular
++      decomposition of algebraic varieties" NAG Tech. Rep. 4/98.
++ Description:
++ This domain provides an implementation of square-free regular chains.
++ Moreover, the operation zeroSetSplit
++ is an implementation of a new algorithm for solving polynomial systems by
++ means of regular chains.

SquareFreeRegularTriangularSet(R,E,V,P) : Exports == Implementation where

  R : GcdDomain
  E : OrderedAbelianMonoidSup
  V : OrderedSet
  P : RecursivePolynomialCategory(R,E,V)
  N ==> NonNegativeInteger
  Z ==> Integer
  B ==> Boolean
  LP ==> List P
  PtoP ==> P -> P
  PS ==> GeneralPolynomialSet(R,E,V,P)
  PWT ==> Record(val : P, tower : $)
  BWT ==> Record(val : Boolean, tower : $)
  LpWT ==> Record(val : (List P), tower : $)
  Split ==> List $
  iprintpack ==> InternalPrintPackage()
  polsetpack ==> PolynomialSetUtilitiesPackage(R,E,V,P)
  quasicomppack ==> SquareFreeQuasiComponentPackage(R,E,V,P,$)
  regsetgcdpack ==> SquareFreeRegularTriangularSetGcdPackage(R,E,V,P,$)
  regsetdecomppack ==> SquareFreeRegularSetDecompositionPackage(R,E,V,P,$)

  Exports ==  SquareFreeRegularTriangularSetCategory(R,E,V,P) with

     internalAugment: (P,$,B,B,B,B,B) -> List $
       ++ \axiom{internalAugment(p,ts,b1,b2,b3,b4,b5)}
       ++ is an internal subroutine, exported only for developement.
     zeroSetSplit: (LP, B, B) -> Split
       ++ \axiom{zeroSetSplit(lp,clos?,info?)} has the same specifications as
```

```
      ++ zeroSetSplit from RegularTriangularSetCategory
      ++ from \spadtype{RegularTriangularSetCategory}
      ++ Moreover, if clos? then solves in the sense of the Zariski closure
      ++ else solves in the sense of the regular zeros. If \axiom{info?} then
      ++ do print messages during the computations.
    zeroSetSplit: (LP, B, B, B, B) -> Split
      ++ \axiom{zeroSetSplit(lp,b1,b2.b3,b4)}
      ++ is an internal subroutine, exported only for developement.
    internalZeroSetSplit: (LP, B, B, B) -> Split
      ++ \axiom{internalZeroSetSplit(lp,b1,b2,b3)}
      ++ is an internal subroutine, exported only for developement.
    pre_process: (LP, B, B) -> Record(val: LP, towers: Split)
      ++ \axiom{pre_process(lp,b1,b2)}
      ++ is an internal subroutine, exported only for developement.

  Implementation == add

    Rep ==> LP

    rep(s:$):Rep == s pretend Rep
    per(l:Rep):$ == l pretend $

    copy ts ==
      per(copy(rep(ts))$LP)
    empty() ==
      per([])
    empty?(ts:$) ==
      empty?(rep(ts))
    parts ts ==
      rep(ts)
    members ts ==
      rep(ts)
    map (f : PtoP, ts : $) : $ ==
      construct(map(f,rep(ts))$LP)$$
    map! (f : PtoP, ts : $) : $  ==
      construct(map!(f,rep(ts))$LP)$$
    member? (p,ts) ==
      member?(p,rep(ts))$LP
    unitIdealIfCan() ==
      "failed"::Union($,"failed")
    roughUnitIdeal? ts ==
      false
    coerce(ts:$) : OutputForm ==
      lp : List(P) := reverse(rep(ts))
      brace([p::OutputForm for p in lp]$List(OutputForm))$OutputForm
    mvar ts ==
      empty? ts => error "mvar$SREGSET: #1 is empty"
      mvar(first(rep(ts)))$P
    first ts ==
      empty? ts => "failed"::Union(P,"failed")
```

```
  first(rep(ts))::Union(P,"failed")
last ts ==
  empty? ts => "failed"::Union(P,"failed")
  last(rep(ts))::Union(P,"failed")
rest ts ==
  empty? ts => "failed"::Union($,"failed")
  per(rest(rep(ts)))::Union($,"failed")
coerce(ts:$) : (List P) ==
  rep(ts)

collectUpper (ts,v) ==
  empty? ts => ts
  lp := rep(ts)
  newlp : Rep := []
  while (not empty? lp) and (mvar(first(lp)) > v) repeat
    newlp := cons(first(lp),newlp)
    lp := rest lp
  per(reverse(newlp))

collectUnder (ts,v) ==
  empty? ts => ts
  lp := rep(ts)
  while (not empty? lp) and (mvar(first(lp)) >= v) repeat
    lp := rest lp
  per(lp)

construct(lp:List(P)) ==
  ts : $ := per([])
  empty? lp => ts
  lp := sort(infRittWu?,lp)
  while not empty? lp repeat
    eif := extendIfCan(ts,first(lp))
    not (eif case $) =>
      error"in construct : List P -> $  from SREGSET : bad #1"
    ts := eif::$
    lp := rest lp
  ts

extendIfCan(ts:$,p:P) ==
  ground? p => "failed"::Union($,"failed")
  empty? ts =>
    p := squareFreePart primitivePart p
    (per([p]))::Union($,"failed")
  not (mvar(ts) < mvar(p)) => "failed"::Union($,"failed")
  invertible?(init(p),ts)@Boolean =>
    lts: Split := augment(p,ts)
    #lts ~= 1 => "failed"::Union($,"failed")
    (first lts)::Union($,"failed")
  "failed"::Union($,"failed")
```

```
removeZero(p:P, ts:$): P ==
  (ground? p) or (empty? ts) => p
  v := mvar(p)
  ts_v_- := collectUnder(ts,v)
  if algebraic?(v,ts)
    then
      q := lazyPrem(p,select(ts,v)::P)
      zero? q => return q
      zero? removeZero(q,ts_v_-) => return 0
  empty? ts_v_- => p
  q: P := 0
  while positive? degree(p,v) repeat
     q := removeZero(init(p),ts_v_-) * mainMonomial(p) + q
     p := tail(p)
  q + removeZero(p,ts_v_-)

internalAugment(p:P,ts:$): $ ==
  -- ASSUME that adding p to ts DOES NOT require any split
  ground? p => error "in internalAugment$SREGSET: ground? #1"
  first(internalAugment(p,ts,false,false,false,false,false))

internalAugment(lp:List(P),ts:$): $ ==
  -- ASSUME that adding p to ts DOES NOT require any split
  empty? lp => ts
  internalAugment(rest lp, internalAugment(first lp, ts))

internalAugment(p:P,ts:$,rem?:B,red?:B,prim?:B,sqfr?:B,extend?:B): Split ==
  -- ASSUME p is not a constant
  -- ASSUME mvar(p) is not algebraic w.r.t. ts
  -- ASSUME init(p) invertible modulo ts
  -- if rem? then REDUCE p by remainder
  -- if prim? then REPLACE p by its main primitive part
  -- if sqfr? then FACTORIZE SQUARE FREE p over R
  -- if extend? DO NOT ASSUME every pol in ts_v_+ is invertible modulo ts
  v := mvar(p)
  ts_v_- := collectUnder(ts,v)
  ts_v_+ := collectUpper(ts,v)
  if rem? then p := remainder(p,ts_v_-).polnum
  -- if rem? then p := reduceByQuasiMonic(p,ts_v_-)
  if red? then p := removeZero(p,ts_v_-)
  if prim? then p := mainPrimitivePart p
  lts: Split
  if sqfr?
    then
      lts: Split := []
      lsfp := squareFreeFactors(p)$polsetpack
      for f in lsfp repeat
        (ground? f) or (mvar(f) < v) => "leave"
        lpwt := squareFreePart(f,ts_v_-)
        for pwt in lpwt repeat
```

```
            sfp := pwt.val; us := pwt.tower
            lts := cons( per(cons(pwt.val, rep(pwt.tower))), lts)
        else
          lts: Split := [per(cons(p,rep(ts_v_-)))]
      extend? => extend(members(ts_v_+),lts)
      [per(concat(rep(ts_v_+),rep(us))) for us in lts]

    augment(p:P,ts:$): List $ ==
      ground? p => error "in augment$SREGSET: ground? #1"
      algebraic?(mvar(p),ts) => error "in augment$SREGSET: bad #1"
      -- ASSUME init(p) invertible modulo ts
      -- DOES NOT ASSUME anything else.
      -- THUS reduction, mainPrimitivePart and squareFree are NEEDED
      internalAugment(p,ts,true,true,true,true,true)

    extend(p:P,ts:$): List $ ==
      ground? p => error "in extend$SREGSET: ground? #1"
      v := mvar(p)
      not (mvar(ts) < mvar(p)) => error "in extend$SREGSET: bad #1"
      split: List($) := invertibleSet(init(p),ts)
      lts: List($) := []
      for us in split repeat
        lts := concat(augment(p,us),lts)
      lts

    invertible?(p:P,ts:$): Boolean ==
      stoseInvertible?(p,ts)$regsetgcdpack

    invertible?(p:P,ts:$): List BWT ==
      stoseInvertible?_sqfreg(p,ts)$regsetgcdpack

    invertibleSet(p:P,ts:$): Split ==
      stoseInvertibleSet_sqfreg(p,ts)$regsetgcdpack

    lastSubResultant(p1:P,p2:P,ts:$): List PWT ==
      stoseLastSubResultant(p1,p2,ts)$regsetgcdpack

    squareFreePart(p:P, ts: $): List PWT ==
      stoseSquareFreePart(p,ts)$regsetgcdpack

    intersect(p:P, ts: $): List($) == decompose([p], [ts], false, false)$regsetdecomppack

    intersect(lp: LP, lts: List($)): List($) == decompose(lp, lts, false, false)$regsetdecomppack
       -- SOLVE in the regular zero sense
       -- and DO NOT PRINT info

    decompose(p:P, ts: $): List($) == decompose([p], [ts], true, false)$regsetdecomppack

    decompose(lp: LP, lts: List($)): List($) == decompose(lp, lts, true, false)$regsetdecomppack
       -- SOLVE in the closure sense
```

```
   -- and DO NOT PRINT info

zeroSetSplit(lp:List(P)) == zeroSetSplit(lp,true,false)
   -- by default SOLVE in the closure sense
   -- and DO NOT PRINT info

zeroSetSplit(lp:List(P), clos?: B) == zeroSetSplit(lp,clos?, false)

zeroSetSplit(lp:List(P), clos?: B, info?: B) ==
  -- if clos? then SOLVE in the closure sense
  -- if info? then PRINT info
  -- by default USE hash-tables
  -- and PREPROCESS the input system
  zeroSetSplit(lp,true,clos?,info?,true)

zeroSetSplit(lp:List(P),hash?:B,clos?:B,info?:B,prep?:B) ==
  -- if hash? then USE hash-tables
  -- if info? then PRINT information
  -- if clos? then SOLVE in the closure sense
  -- if prep? then PREPROCESS the input system
  if hash?
    then
      s1, s2, s3, dom1, dom2, dom3: String
      e: String := empty()$String
      if info? then (s1,s2,s3) := ("w","g","i") else (s1,s2,s3) := (e,e,e)
      if info?
        then
          (dom1, dom2, dom3) := ("QCMPACK", "REGSETGCD: Gcd", "REGSETGCD: Inv Set")
        else
          (dom1, dom2, dom3) := (e,e,e)
      startTable!(s1,"W",dom1)$quasicomppack
      startTableGcd!(s2,"G",dom2)$regsetgcdpack
      startTableInvSet!(s3,"I",dom3)$regsetgcdpack
  lts := internalZeroSetSplit(lp,clos?,info?,prep?)
  if hash?
    then
      stopTable!()$quasicomppack
      stopTableGcd!()$regsetgcdpack
      stopTableInvSet!()$regsetgcdpack
  lts

internalZeroSetSplit(lp:LP,clos?:B,info?:B,prep?:B) ==
  -- if info? then PRINT information
  -- if clos? then SOLVE in the closure sense
  -- if prep? then PREPROCESS the input system
  if prep?
    then
      pp := pre_process(lp,clos?,info?)
      lp := pp.val
      lts := pp.towers
```

```
        else
          ts: $ := [[]]
          lts := [ts]
      lp := remove(zero?, lp)
      any?(ground?, lp) => []
      empty? lp => lts
      empty? lts => lts
      lp := sort(infRittWu?,lp)
      clos? => decompose(lp,lts, clos?, info?)$regsetdecomppack
      -- IN DIM > 0 with clos? the following is not false ...
      for p in lp repeat
        lts := decompose([p],lts, clos?, info?)$regsetdecomppack
      lts

    largeSystem?(lp:LP): Boolean ==
      -- Gonnet and Gerdt and not Wu-Wang.2
      #lp > 16 => true
      #lp < 13 => false
      lts: List($) := []
      (#lp :: Z - numberOfVariables(lp,lts)$regsetdecomppack :: Z) > 3

    smallSystem?(lp:LP): Boolean ==
      -- neural, Vermeer, Liu, and not f-633 and not Hairer-2
      #lp < 5

    mediumSystem?(lp:LP): Boolean ==
      -- f-633 and not Hairer-2
      lts: List($) := []
      (numberOfVariables(lp,lts)$regsetdecomppack :: Z - #lp :: Z) < 2

--    lin?(p:P):Boolean == ground?(init(p)) and one?(mdeg(p))
    lin?(p:P):Boolean == ground?(init(p)) and (mdeg(p) = 1)

    pre_process(lp:LP,clos?:B,info?:B): Record(val: LP, towers: Split) ==
      -- if info? then PRINT information
      -- if clos? then SOLVE in the closure sense
      ts: $ := [[]];
      lts: Split := [ts]
      empty? lp => [lp,lts]
      lp1: List P := []
      lp2: List P := []
      for p in lp repeat
         ground? (tail p) => lp1 := cons(p, lp1)
         lp2 := cons(p, lp2)
      lts: Split := decompose(lp1,[ts],clos?,info?)$regsetdecomppack
      probablyZeroDim?(lp)$polsetpack =>
         largeSystem?(lp) => return [lp2,lts]
         if #lp > 7
           then
             -- Butcher (8,8) + Wu-Wang.2 (13,16)
```

```
        lp2 := crushedSet(lp2)$polsetpack
        lp2 := remove(zero?,lp2)
        any?(ground?,lp2) => return [lp2, lts]
        lp3 := [p for p in lp2 | lin?(p)]
        lp4 := [p for p in lp2 | not lin?(p)]
        if clos?
          then
            lts := decompose(lp4,lts, clos?, info?)$regsetdecomppack
          else
            lp4 := sort(infRittWu?,lp4)
            for p in lp4 repeat
              lts := decompose([p],lts, clos?, info?)$regsetdecomppack
        lp2 := lp3
      else
        lp2 := crushedSet(lp2)$polsetpack
        lp2 := remove(zero?,lp2)
        any?(ground?,lp2) => return [lp2, lts]
    if clos?
      then
        lts := decompose(lp2,lts, clos?, info?)$regsetdecomppack
      else
        lp2 := sort(infRittWu?,lp2)
        for p in lp2 repeat
          lts := decompose([p],lts, clos?, info?)$regsetdecomppack
    lp2 := []
    return [lp2,lts]
smallSystem?(lp) => [lp2,lts]
mediumSystem?(lp) => [crushedSet(lp2)$polsetpack,lts]
lp3 := [p for p in lp2 | lin?(p)]
lp4 := [p for p in lp2 | not lin?(p)]
if clos?
  then
    lts := decompose(lp4,lts, clos?, info?)$regsetdecomppack
  else
    lp4 := sort(infRittWu?,lp4)
    for p in lp4 repeat
      lts := decompose([p],lts, clos?, info?)$regsetdecomppack
if clos?
  then
    lts := decompose(lp3,lts, clos?, info?)$regsetdecomppack
  else
    lp3 := sort(infRittWu?,lp3)
    for p in lp3 repeat
      lts := decompose([p],lts, clos?, info?)$regsetdecomppack
lp2 := []
return [lp2,lts]
```

———-

— **SREGSET.dotabb** —

```
"SREGSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SREGSET"]
"SFRTCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=SFRTCAT"]
"SREGSET" -> "SFRTCAT"
```

———-

20.27 domain SQMATRIX SquareMatrix

— **SquareMatrix.input** —

```
)set break resume
)sys rm -f SquareMatrix.output
)spool SquareMatrix.output
)set message test on
)set message auto off
)clear all
--S 1 of 6
)set expose add constructor SquareMatrix
--R
--I   SquareMatrix is now explicitly exposed in frame frame0
--E 1

--S 2 of 6
m := squareMatrix [ [1,-%i],[%i,4] ]
--R
--R
--R        +1   - %i+
--R   (1)  |        |
--R        +%i   4  +
--R                                        Type: SquareMatrix(2,Complex(Integer))
--E 2

--S 3 of 6
m*m - m
--R
--R
--R        + 1   - 4%i+
--R   (2)  |          |
--R        +4%i   13  +
--R                                        Type: SquareMatrix(2,Complex(Integer))
--E 3

--S 4 of 6
```

```
mm := squareMatrix [ [m, 1], [1-m, m**2] ]
--R
--R
--R        ++1   - %i+      +1  0+   +
--R        ||        |      |    |   |
--R        |+%i   4  +      +0  1+   |
--R   (3)  |                         |
--R        |+ 0    %i +  + 2   - 5%i+|
--R        ||         |  |           ||
--R        ++- %i  - 3+  +5%i   17  ++
--R                       Type: SquareMatrix(2,SquareMatrix(2,Complex(Integer)))
--E 4

--S 5 of 6
p := (x + m)**2
--R
--R
--R         2   + 2   - 2%i+    + 2   - 5%i+
--R   (4)  x  + |          |x + |          |
--R             +2%i    8  +    +5%i   17  +
--R                            Type: Polynomial(SquareMatrix(2,Complex(Integer)))
--E 5

--S 6 of 6
p::SquareMatrix(2, ?)
--R
--R
--R        + 2                         +
--R        |x  + 2x + 2  - 2%i x - 5%i|
--R   (5)  |                           |
--R        |              2            |
--R        +2%i x + 5%i  x  + 8x + 17 +
--R                            Type: SquareMatrix(2,Polynomial(Complex(Integer)))
--E 6
)spool
)lisp (bye)
```

———-

— SquareMatrix.help —

```
====================================================================
SquareMatrix examples
====================================================================

The top level matrix type in Axiom is Matrix, which provides basic
arithmetic and linear algebra functions.  However, since the matrices
can be of any size it is not true that any pair can be added or
multiplied.  Thus Matrix has little algebraic structure.
```

Sometimes you want to use matrices as coefficients for polynomials or in other algebraic contexts. In this case, SquareMatrix should be used. The domain SquareMatrix(n,R) gives the ring of n by n square matrices over R.

Since SquareMatrix is not normally exposed at the top level, you must expose it before it can be used.

```
)set expose add constructor SquareMatrix
```

Once SQMATRIX has been exposed, values can be created using the squareMatrix function.

```
m := squareMatrix [ [1,-%i],[%i,4] ]
  +1   - %i+
  |        |
  +%i   4  +
                      Type: SquareMatrix(2,Complex Integer)
```

The usual arithmetic operations are available.

```
m*m - m
  + 1   - 4%i+
  |          |
  +4%i   13  +
                      Type: SquareMatrix(2,Complex Integer)
```

Square matrices can be used where ring elements are required.
For example, here is a matrix with matrix entries.

```
mm := squareMatrix [ [m, 1], [1-m, m**2] ]
  ++1   - %i+      +1  0+   +
  ||        |      |    |   |
  |+%i   4  +      +0  1+   |
  |                         |
  |+ 0    %i +  + 2   - 5%i+|
  ||         |  |          ||
  ++- %i  - 3+  +5%i   17  ++
                      Type: SquareMatrix(2,SquareMatrix(2,Complex Integer))
```

Or you can construct a polynomial with square matrix coefficients.


```
p := (x + m)**2
   2   + 2   - 2%i+    + 2   - 5%i+
  x  + |          |x + |          |
       +2%i    8  +    +5%i   17  +
                      Type: Polynomial SquareMatrix(2,Complex Integer)
```

This value can be converted to a square matrix with polynomial coefficients.

```
  p::SquareMatrix(2, ?)
    + 2                          +
    |x  + 2x + 2  - 2%i x - 5%i|
    |                           |
    |              2            |
    +2%i x + 5%i   x  + 8x + 17 +
                        Type: SquareMatrix(2,Polynomial Complex Integer)

See Also:
o )help Matrix
o )show SquareMatrix
```

20.27.1 SquareMatrix (SQMATRIX)



See

⇒ “IndexedMatrix” (IMATRIX) 10.12.1 on page 1208
⇒ “Matrix” (MATRIX) 14.7.1 on page 1590
⇒ “RectangularMatrix” (RMATRIX) 19.4.1 on page 2211

Exports:

0	1	antisymmetric?	any?	characteristic
coerce	column	convert	copy	count
D	determinant	diagonal	diagonal?	diagonalMatrix
diagonalProduct	differentiate	elt	empty	empty?
eq?	eval	every?	exquo	hash
inverse	latex	less?	listOfLists	map
map!	matrix	maxColIndex	maxRowIndex	member?
members	minColIndex	minordet	minRowIndex	more?
ncols	nrows	nullSpace	nullity	one?
parts	qelt	rank	recip	reducedSystem
retract	retractIfCan	row	rowEchelon	sample
scalarMatrix	size?	square?	squareMatrix	subtractIfCan
symmetric?	trace	transpose	zero?	#?
?*?	?**?	?+?	?-?	-?
?=?	?^?	?~=?	?/?	

— domain SQMATRIX SquareMatrix —

```
)abbrev domain SQMATRIX SquareMatrix
++ Author: Grabmeier, Gschnitzer, Williamson
++ Date Created: 1987
++ Date Last Updated: July 1990
++ Basic Operations:
++ Related Domains: IndexedMatrix, Matrix, RectangularMatrix
++ Also See:
++ AMS Classifications:
++ Keywords: matrix, linear algebra
++ Examples:
++ References:
++ Description:
++ \spadtype{SquareMatrix} is a matrix domain of square matrices, where the
++ number of rows (= number of columns) is a parameter of the type.

SquareMatrix(ndim,R): Exports == Implementation where
  ndim : NonNegativeInteger
  R    : Ring
  Row ==> DirectProduct(ndim,R)
  Col ==> DirectProduct(ndim,R)
  MATLIN ==> MatrixLinearAlgebraFunctions(R,Row,Col,$)

  Exports ==> Join(SquareMatrixCategory(ndim,R,Row,Col),_
                   CoercibleTo Matrix R) with

    transpose: $ -> $
      ++ \spad{transpose(m)} returns the transpose of the matrix m.
    squareMatrix: Matrix R -> $
      ++ \spad{squareMatrix(m)} converts a matrix of type \spadtype{Matrix}
      ++ to a matrix of type \spadtype{SquareMatrix}.
```

```
    coerce: $ -> Matrix R
      ++ \spad{coerce(m)} converts a matrix of type \spadtype{SquareMatrix}
      ++ to a matrix of type \spadtype{Matrix}.
--  symdecomp : $ -> Record(sym:$,antisym:$)
--    ++ \spad{symdecomp(m)} decomposes the matrix m as a sum of a symmetric
--    ++ matrix \spad{m1} and an antisymmetric matrix \spad{m2}. The object
--    ++ returned is the Record \spad{[m1,m2]}
--  if R has commutative("*") then
--    minorsVect: -> Vector(Union(R,"uncomputed")) --range: 1..2**n-1
--      ++ \spad{minorsVect(m)} returns a vector of the minors of the matrix m
    if R has commutative("*") then central
      ++ the elements of the Ring R, viewed as diagonal matrices, commute
      ++ with all matrices and, indeed, are the only matrices which commute
      ++ with all matrices.
    if R has commutative("*") and R has unitsKnown then unitsKnown
      ++ the invertible matrices are simply the matrices whose determinants
      ++ are units in the Ring R.
    if R has ConvertibleTo InputForm then ConvertibleTo InputForm

  Implementation ==> Matrix R add
    minr ==> minRowIndex
    maxr ==> maxRowIndex
    minc ==> minColIndex
    maxc ==> maxColIndex
    mini ==> minIndex
    maxi ==> maxIndex

    ZERO := scalarMatrix 0
    0    == ZERO
    ONE  := scalarMatrix 1
    1    == ONE

    characteristic() == characteristic()$R

    matrix(l: List List R) ==
      -- error check: this is a top level function
      #l ^= ndim => error "matrix: wrong number of rows"
      for ll in l repeat
        #ll ^= ndim => error "matrix: wrong number of columns"
      ans : Matrix R := new(ndim,ndim,0)
      for i in minr(ans)..maxr(ans) for ll in l repeat
        for j in minc(ans)..maxc(ans) for r in ll repeat
          qsetelt_!(ans,i,j,r)
      ans pretend $

    row(x,i)    == directProduct row(x pretend Matrix(R),i)
    column(x,j) == directProduct column(x pretend Matrix(R),j)
    coerce(x:$):OutputForm == coerce(x pretend Matrix R)$Matrix(R)

    scalarMatrix r == scalarMatrix(ndim,r)$Matrix(R) pretend $
```

```
diagonalMatrix l ==
  #l ^= ndim =>
    error "diagonalMatrix: wrong number of entries in list"
  diagonalMatrix(l)$Matrix(R) pretend $

coerce(x:$):Matrix(R) == copy(x pretend Matrix(R))

squareMatrix x ==
  (nrows(x) ^= ndim) or (ncols(x) ^= ndim) =>
    error "squareMatrix: matrix of bad dimensions"
  copy(x) pretend $

x:$ * v:Col ==
  directProduct((x pretend Matrix(R)) * (v :: Vector(R)))

v:Row * x:$ ==
  directProduct((v :: Vector(R)) * (x pretend Matrix(R)))

x:$ ** n:NonNegativeInteger ==
  ((x pretend Matrix(R)) ** n) pretend $

if R has commutative("*") then

  determinant x == determinant(x pretend Matrix(R))
  minordet x    == minordet(x pretend Matrix(R))

if R has EuclideanDomain then

  rowEchelon x == rowEchelon(x pretend Matrix(R)) pretend $

if R has IntegralDomain then

  rank x    == rank(x pretend Matrix(R))
  nullity x == nullity(x pretend Matrix(R))
  nullSpace x ==
    [directProduct c for c in nullSpace(x pretend Matrix(R))]

if R has Field then

  dimension() == (m * n) :: CardinalNumber

  inverse x ==
    (u := inverse(x pretend Matrix(R))) case "failed" => "failed"
    (u :: Matrix(R)) pretend $

  x:$ ** n:Integer ==
    ((x pretend Matrix(R)) ** n) pretend $

  recip x == inverse x
```

```
    if R has ConvertibleTo InputForm then
      convert(x:$):InputForm ==
         convert [convert("squareMatrix"::Symbol)@InputForm,
                  convert(x::Matrix(R))]$List(InputForm)
```

———-

— SQMATRIX.dotabb —

```
"SQMATRIX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SQMATRIX"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SQMATRIX" -> "ALIST"
```

———-

20.28 domain STACK Stack

— Stack.input —

```
)set break resume
)sys rm -f Stack.output
)spool Stack.output
)set message test on
)set message auto off
)clear all

--S 1 of 44
a:Stack INT:= stack [1,2,3,4,5]
--R
--R   (1)  [1,2,3,4,5]
--R                                                    Type: Stack(Integer)
--E 1

--S 2 of 44
pop! a
--R
--R   (2)  1
--R                                                 Type: PositiveInteger
--E 2

--S 3 of 44
a
```

```
--R
--R   (3)  [2,3,4,5]
--R                                                    Type: Stack(Integer)
--E 3

--S 4 of 44
extract! a
--R
--R   (4)  2
--R                                                 Type: PositiveInteger
--E 4

--S 5 of 44
a
--R
--R   (5)  [3,4,5]
--R                                                    Type: Stack(Integer)
--E 5

--S 6 of 44
push!(9,a)
--R
--R   (6)  9
--R                                                 Type: PositiveInteger
--E 6

--S 7 of 44
a
--R
--R   (7)  [9,3,4,5]
--R                                                    Type: Stack(Integer)
--E 7

--S 8 of 44
insert!(8,a)
--R
--R   (8)  [8,9,3,4,5]
--R                                                    Type: Stack(Integer)
--E 8

--S 9 of 44
a
--R
--R   (9)  [8,9,3,4,5]
--R                                                    Type: Stack(Integer)
--E 9

--S 10 of 44
inspect a
--R
```

```
--R   (10)  8
--R                                                  Type: PositiveInteger
--E 10

--S 11 of 44
empty? a
--R
--R   (11)  false
--R                                                          Type: Boolean
--E 11

--S 12 of 44
top a
--R
--R   (12)  8
--R                                                  Type: PositiveInteger
--E 12

--S 13 of 44
depth a
--R
--R   (13)  5
--R                                                  Type: PositiveInteger
--E 13

--S 14 of 44
#a
--R
--R   (14)  5
--R                                                  Type: PositiveInteger
--E 14

--S 15 of 44
less?(a,9)
--R
--R   (15)  true
--R                                                          Type: Boolean
--E 15

--S 16 of 44
more?(a,9)
--R
--R   (16)  false
--R                                                          Type: Boolean
--E 16

--S 17 of 44
size?(a,#a)
--R
--R   (17)  true
```

```
--R                                                        Type: Boolean
--E 17

--S 18 of 44
size?(a,9)
--R
--R   (18)  false
--R                                                        Type: Boolean
--E 18

--S 19 of 44
parts a
--R
--R   (19)  [8,9,3,4,5]
--R                                                    Type: List(Integer)
--E 19

--S 20 of 44
bag([1,2,3,4,5])$Stack(INT)
--R
--R   (20)  [5,4,3,2,1]
--R                                                   Type: Stack(Integer)
--E 20

--S 21 of 44
b:=empty()$(Stack INT)
--R
--R   (21)  []
--R                                                   Type: Stack(Integer)
--E 21

--S 22 of 44
empty? b
--R
--R   (22)  true
--R                                                        Type: Boolean
--E 22

--S 23 of 44
sample()$Stack(INT)
--R
--R   (23)  []
--R                                                   Type: Stack(Integer)
--E 23

--S 24 of 44
c:=copy a
--R
--R   (24)  [8,9,3,4,5]
--R                                                   Type: Stack(Integer)
```

```
--E 24

--S 25 of 44
eq?(a,c)
--R
--R   (25)  false
--R                                                    Type: Boolean
--E 25

--S 26 of 44
eq?(a,a)
--R
--R   (26)  true
--R                                                    Type: Boolean
--E 26

--S 27 of 44
(a=c)@Boolean
--R
--R   (27)  true
--R                                                    Type: Boolean
--E 27

--S 28 of 44
(a=a)@Boolean
--R
--R   (28)  true
--R                                                    Type: Boolean
--E 28

--S 29 of 44
a~=c
--R
--R   (29)  false
--R                                                    Type: Boolean
--E 29

--S 30 of 44
any?(x+->(x=4),a)
--R
--R   (30)  true
--R                                                    Type: Boolean
--E 30

--S 31 of 44
any?(x+->(x=11),a)
--R
--R   (31)  false
--R                                                    Type: Boolean
--E 31
```

```
--S 32 of 44
every?(x+->(x=11),a)
--R
--R   (32)  false
--R                                                        Type: Boolean
--E 32

--S 33 of 44
count(4,a)
--R
--R   (33)  1
--R                                                  Type: PositiveInteger
--E 33

--S 34 of 44
count(x+->(x>2),a)
--R
--R   (34)  5
--R                                                  Type: PositiveInteger
--E 34

--S 35 of 44
map(x+->x+10,a)
--R
--R   (35)  [18,19,13,14,15]
--R                                                   Type: Stack(Integer)
--E 35

--S 36 of 44
a
--R
--R   (36)  [8,9,3,4,5]
--R                                                   Type: Stack(Integer)
--E 36

--S 37 of 44
map!(x+->x+10,a)
--R
--R   (37)  [18,19,13,14,15]
--R                                                   Type: Stack(Integer)
--E 37

--S 38 of 44
a
--R
--R   (38)  [18,19,13,14,15]
--R                                                   Type: Stack(Integer)
--E 38
```

```
--S 39 of 44
members a
--R
--R   (39)  [18,19,13,14,15]
--R                                                        Type: List(Integer)
--E 39

--S 40 of 44
member?(14,a)
--R
--R   (40)  true
--R                                                           Type: Boolean
--E 40

--S 41 of 44
coerce a
--R
--R
--R   (41)  [18,19,13,14,15]
--R                                                      Type: OutputForm
--E 41

--S 42 of 44
hash a
--R
--R
--I   (42)  4999539
--R                                                      Type: SingleInteger
--E 42

--S 43 of 44
latex a
--R
--R
--R   (43)  "\mbox{\bf Unimplemented}"
--R                                                           Type: String
--E 43

--S 44 of 44
)show Stack
--R
--R Stack(S: SetCategory)  is a domain constructor
--R Abbreviation for Stack is STACK
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for STACK
--R
--R------------------------------ Operations ------------------------------
--R bag : List(S) -> %                    copy : % -> %
--R depth : % -> NonNegativeInteger       empty : () -> %
--R empty? : % -> Boolean                 eq? : (%,%) -> Boolean
```

```
--R extract! : % -> S                    insert! : (S,%) -> %
--R inspect : % -> S                     map : ((S -> S),%) -> %
--R pop! : % -> S                        push! : (S,%) -> S
--R sample : () -> %                     stack : List(S) -> %
--R top : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(S) if $ has finiteAggregate
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 44
)spool
)lisp (bye)
```

———-

— Stack.help —

```
=====================================================================
Stack examples
=====================================================================

A Stack object is represented as a list ordered by last-in, first-out.
It operates like a pile of books, where the "next" book is the one
on the top of the pile.

Here we create a stack of integers from a list. Notice that the
order in the list is the order in the stack.

   a:Stack INT:= stack [1,2,3,4,5]
      [1,2,3,4,5]
```

We can remove the top of the stack using pop!:

```
   pop! a
      1
```

Notice that the use of pop! is destructive (destructive operations
in Axiom usually end with ! to indicate that the underylying data
structure is changed).

```
   a
      [2,3,4,5]
```

The extract! operation is another name for the pop! operation and
has the same effect. This operation treats the stack as a BagAggregate:

```
   extract! a
      2
```

and you can see that it also has destructively modified the stack:

```
   a
      [3,4,5]
```

Next we push a new element on top of the stack:

```
   push!(9,a)
      9
```

Again, the push! operation is destructive so the stack is changed:

```
   a
      [9,2,3,4,5]
```

Another name for push! is insert!, which treats the stack as a BagAggregate:

```
   insert!(8,a)
      [8,9,3,4,5]
```

and it modifies the stack:

```
   a
      [8,9,3,4,5]
```

The inspect function returns the top of the stack without modification,
viewed as a BagAggregate:

```
   inspect a
      8
```

The empty? operation returns true only if there are no element on the stack, otherwise it returns false:

```
   empty? a
      false
```

The top operation returns the top of stack without modification, viewed as a Stack:

```
   top a
      8
```

The depth operation returns the number of elements on the stack:

```
   depth a
      5
```

which is the same as the # (length) operation:

```
   #a
       5
```

The less? predicate will compare the stack length to an integer:

```
   less?(a,9)
        true
```

The more? predicate will compare the stack length to an integer:

```
   more?(a,9)
        false
```

The size? operation will compare the stack length to an integer:

```
   size?(a,#a)
        true
```

and since the last computation must alwasy be true we try:

```
   size?(a,9)
        false
```

The parts function will return the stack as a list of its elements:

```
   parts a
        [8,9,3,4,5]
```

If we have a BagAggregate of elements we can use it to construct a stack. Notice that the elements are pushed in reverse order:

```
   bag([1,2,3,4,5])$Stack(INT)
        [5,4,3,2,1]
```

The empty function will construct an empty stack of a given type:

```
   b:=empty()$(Stack INT)
        []
```

and the empty? predicate allows us to find out if a stack is empty:

```
   empty? b
        true
```

The sample function returns a sample, empty stack:

```
   sample()$Stack(INT)
        []
```

We can copy a stack and it does not share storage so subsequent
modifications of the original stack will not affect the copy:

```
   c:=copy a
        [8,9,3,4,5]
```

The eq? function is only true if the lists are the same reference,
so even though c is a copy of a, they are not the same:

```
   eq?(a,c)
        false
```

However, a clearly shares a reference with itself:

```
   eq?(a,a)
        true
```

But we can compare a and c for equality:

```
   (a=c)@Boolean
        true
```

and clearly a is equal to itself:

```
   (a=a)@Boolean
        true
```

and since a and c are equal, they are clearly NOT not-equal:

```
   a~=c
        false
```

```
We can use the any? function to see if a predicate is true for any element:

   any?(x+->(x=4),a)
        true

or false for every element:

   any?(x+->(x=11),a)
        false

We can use the every? function to check every element satisfies a predicate:

   every?(x+->(x=11),a)
        false

We can count the elements that are equal to an argument of this type:

   count(4,a)
        1

or we can count against a boolean function:

   count(x+->(x>2),a)
        5

You can also map a function over every element, returning a new stack:

   map(x+->x+10,a)
        [18,19,13,14,15]

Notice that the orignal stack is unchanged:

   a
        [8,9,3,4,5]

You can use map! to map a function over every element and change
the original stack since map! is destructive:

   map!(x+->x+10,a)
       [18,19,13,14,15]

Notice that the orignal stack has been changed:

   a
       [18,19,13,14,15]

The member function can also get the element of the stack as a list:


   members a
       [18,19,13,14,15]
```

```
and using member? we can test if the stack holds a given element:

   member?(14,a)
       true

See Also:
o )show Stack
o )show ArrayStack
o )show Queue
o )show Dequeue
o )show Heap
o )show BagAggregate
```

20.28.1 Stack (STACK)



See

⇒ “ArrayStack” (ASTACK) 2.10.1 on page 65
⇒ “Queue” (QUEUE) 18.5.1 on page 2150
⇒ “Dequeue” (DEQUEUE) 5.5.1 on page 499
⇒ “Heap” (HEAP) 9.2.1 on page 1104

Exports:

any?	bag	coerce	copy	count
depth	empty	empty?	eq?	eval
every?	extract!	hash	insert!	inspect
latex	less?	map	map!	member?
members	more?	parts	pop!	push!
sample	size?	stack	top	#?
?=?	?~=?			

— domain STACK Stack —

```
)abbrev domain STACK Stack
++ Author: Michael Monagan, Stephen Watt, Timothy Daly
++ Date Created:June 86 and July 87
++ Date Last Updated:Feb 09
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Linked List implementation of a Stack
--% Dequeue and Heap data types

Stack(S:SetCategory): StackAggregate S with
    stack: List S -> %
      ++ stack([x,y,...,z]) creates a stack with first (top)
      ++ element x, second element y,...,and last element z.
      ++
      ++X a:Stack INT:= stack [1,2,3,4,5]

 -- Inherited Signatures repeated for examples documentation

    pop_! : % -> S
      ++
      ++X a:Stack INT:= stack [1,2,3,4,5]
      ++X pop! a
      ++X a
    extract_! : % -> S
      ++
      ++X a:Stack INT:= stack [1,2,3,4,5]
      ++X extract! a
      ++X a
    push_! : (S,%) -> S
      ++
      ++X a:Stack INT:= stack [1,2,3,4,5]
      ++X push!(9,a)
      ++X a
    insert_! : (S,%) -> %
      ++
      ++X a:Stack INT:= stack [1,2,3,4,5]
      ++X insert!(8,a)
      ++X a
    inspect : % -> S
      ++
      ++X a:Stack INT:= stack [1,2,3,4,5]
      ++X inspect a
    top : % -> S
      ++
```

```
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X top a
depth : % -> NonNegativeInteger
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X depth a
less? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X less?(a,9)
more? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X more?(a,9)
size? : (%,NonNegativeInteger) -> Boolean
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X size?(a,5)
bag : List S -> %
  ++
  ++X bag([1,2,3,4,5])$Stack(INT)
empty? : % -> Boolean
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X empty? a
empty : () -> %
  ++
  ++X b:=empty()$(Stack INT)
sample : () -> %
  ++
  ++X sample()$Stack(INT)
copy : % -> %
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X copy a
eq? : (%,%) -> Boolean
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X b:=copy a
  ++X eq?(a,b)
map :  ((S -> S),%) -> %
  ++
  ++X a:Stack INT:= stack [1,2,3,4,5]
  ++X map(x+->x+10,a)
  ++X a
if $ has shallowlyMutable then
  map! :  ((S -> S),%) -> %
    ++
    ++X a:Stack INT:= stack [1,2,3,4,5]
    ++X map!(x+->x+10,a)
```

```
      ++X a
    if S has SetCategory then
      latex : % -> String
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X latex a
      hash : % -> SingleInteger
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X hash a
      coerce : % -> OutputForm
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X coerce a
      "=": (%,%) -> Boolean
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X b:Stack INT:= stack [1,2,3,4,5]
        ++X (a=b)@Boolean
      "~=" : (%,%) -> Boolean
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X b:=copy a
        ++X (a~=b)
    if % has finiteAggregate then
      every? : ((S -> Boolean),%) -> Boolean
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X every?(x+->(x=4),a)
      any? : ((S -> Boolean),%) -> Boolean
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X any?(x+->(x=4),a)
      count :  ((S -> Boolean),%) -> NonNegativeInteger
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X count(x+->(x>2),a)
      _# : % -> NonNegativeInteger
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X #a
      parts : % -> List S
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X parts a
      members : % -> List S
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X members a
    if % has finiteAggregate and S has SetCategory then
```

```
      member? : (S,%) -> Boolean
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X member?(3,a)
      count : (S,%) -> NonNegativeInteger
        ++
        ++X a:Stack INT:= stack [1,2,3,4,5]
        ++X count(4,a)

  == add
    Rep := Reference List S
    s = t == deref s = deref t
    coerce(d:%): OutputForm == bracket [e::OutputForm for e in deref d]
    copy s == ref copy deref s
    depth s == # deref s
    # s == depth s
    pop_! (s:%):S ==
        empty? s => error "empty stack"
        e := first deref s
        setref(s,rest deref s)
        e
    extract_! (s:%):S == pop_! s
    top (s:%):S ==
        empty? s => error "empty stack"
        first deref s
    inspect s == top s
    push_!(e,s) == (setref(s,cons(e,deref s));e)
    insert_!(e:S,s:%):% == (push_!(e,s);s)
    empty() == ref nil()$List(S)
    empty? s == null deref s
    stack s == ref copy s
    parts s == copy deref s
    map(f,s) == ref map(f,deref s)
    map!(f,s) == ref map!(f,deref s)
```

———-

— STACK.dotabb —

```
"STACK" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STACK"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"STACK" -> "FLAGG"
```

———-

20.29 domain SD StochasticDifferential

— StochasticDifferential.input —

```
)set break resume
)sys rm -f StochasticDifferential.output
)spool StochasticDifferential.output
)set message test on
)set message auto off
)clear all

--S 1 of 12
dt := introduce!(t,dt)
--R
--R
--R   (1)  dt
--R                                  Type: Union(BasicStochasticDifferential,...)
--E 1

--S 2 of 12
dX := introduce!(X,dX)
--R
--R
--R   (2)  dX
--R                                  Type: Union(BasicStochasticDifferential,...)
--E 2

--S 3 of 12
dY := introduce!(Y,dY)
--R
--R
--R   (3)  dY
--R                                  Type: Union(BasicStochasticDifferential,...)
--E 3

--S 4 of 12
copyBSD()
--R
--R
--R   (4)  [dX,dY,dt]
--R                                       Type: List(BasicStochasticDifferential)
--E 4

--S 5 of 12
copyIto()
--R
--R
--R   (5)  table(t= dt,Y= dY,X= dX)
```

```
--R                                Type: Table(Symbol,BasicStochasticDifferential)
--E 5

--S 6 of 12
copyQuadVar()             -- display of multiplication table
--R
--R
--R   (6)  table()
--R Type: Table(StochasticDifferential(Integer),StochasticDifferential(Integer))
--E 6

--S 7 of 12
statusIto()
--R
--R
--R        +B S D   :  dX  dY  dt+
--R        |                     |
--R        |drift   :  ?   ?   ? |
--R        |                     |
--R        |  *                  |
--R   (7)  |                     |
--R        |  dX    :  ?   ?   ? |
--R        |                     |
--R        |  dY    :  ?   ?   ? |
--R        |                     |
--R        +  dt    :  ?   ?   ? +
--R                                                          Type: OutputForm
--E 7

--S 8 of 12
copyDrift()       -- display of drift list
--R
--R
--R   (8)  table()
--R Type: Table(StochasticDifferential(Integer),StochasticDifferential(Integer))
--E 8

--S 9 of 12
nbsd := #copyBSD()
--R
--R
--R   (9)  3
--R                                                       Type: PositiveInteger
--E 9

--S 10 of 12
ItoMultArray:ARRAY2(SD INT) :=new(nbsd,nbsd,0$SD(INT))
--R
--R
--R         +0  0  0+
```

```
--R         |       |
--R   (10)  |0  0  0|
--R         |       |
--R         +0  0  0+
--R                   Type: TwoDimensionalArray(StochasticDifferential(Integer))
--E 10

--S 11 of 12
ItoMultArray
--R
--R
--R         +0  0  0+
--R         |       |
--R   (11)  |0  0  0|
--R         |       |
--R         +0  0  0+
--R                   Type: TwoDimensionalArray(StochasticDifferential(Integer))
--E 11

--S 12 of 12
statusIto()
--R
--R
--R         +B S D   :  dX  dY  dt+
--R         |                     |
--R         |drift   :  ?   ?   ? |
--R         |                     |
--R         |  *                  |
--R   (12)  |                     |
--R         |  dX    :  ?   ?   ? |
--R         |                     |
--R         |  dY    :  ?   ?   ? |
--R         |                     |
--R         +  dt    :  ?   ?   ? +
--R                                                        Type: OutputForm
--E 12

)spool
)lisp (bye)
```

———-

— StochasticDifferential.help —

```
=====================================================================
StochasticDifferential examples
=====================================================================
A basic implementation of StochasticDifferential(R) using the
associated domain BasicStochasticDifferential in the underlying
```

```
representation as sparse multivariate polynomials. The domain is
a module over Expression(R), and is a ring without identity
(AXIOM term is "Rng"). Note that separate instances, for example
using R=Integer and R=Float, have different hidden structure
(multiplication and drift tables).

dt := introduce!(t,dt)
   dt

dX := introduce!(X,dX)
   dX

dY := introduce!(Y,dY)
   dY

copyBSD()
   [dX,dY,dt]

copyIto()
   table(t= dt,Y= dY,X= dX)

copyQuadVar()             -- display of multiplication table
   table()

statusIto()
   +B S D   :  dX  dY  dt+
   |                     |
   |drift   :  ?   ?   ? |
   |                     |
   |  *                  |
   |                     |
   |  dX    :  ?   ?   ? |
   |                     |
   |  dY    :  ?   ?   ? |
   |                     |
   +  dt    :  ?   ?   ? +

copyDrift()       -- display of drift list
   table()

nbsd := #copyBSD()
   3


ItoMultArray:ARRAY2(SD INT) :=new(nbsd,nbsd,0$SD(INT))
   +0  0  0+
   |       |
   |0  0  0|
   |       |
   +0  0  0+
```

```
ItoMultArray
   +0  0  0+
   |       |
   |0  0  0|
   |       |
   +0  0  0+

statusIto()
   +B S D   :  dX  dY  dt+
   |                     |
   |drift   :  ?   ?   ? |
   |                     |
   |  *                  |
   |                     |
   |  dX    :  ?   ?   ? |
   |                     |
   |  dY    :  ?   ?   ? |
   |                     |
   +  dt    :  ?   ?   ? +


See Also:
o )help BasicStochasticDifferential
o )show StochasticDifferential
```

20.29.1 StochasticDifferential (SD)



See

⇐ “BasicStochasticDifferential” (BSD) 3.6.1 on page 270

Exports:

0	coerce	copyDrift	copyQuadVar
drift	hash	latex	sample
statusIto	uncorrelated?	zero?	alterDrift!
alterQuadVar!	coefficient	coerce	equation
freeOf?	listSD	retract	retractIfCan
subtractIfCan	?*?	?**?	?+?
?-?	-?	?/?	?=?
?^?	?~=?		

— domain SD StochasticDifferential —

```
)abbrev domain SD StochasticDifferential
++ Author: Wilfrid S. Kendall
++ Last Last Updated: July 26, 1999
++ Related Domains: BasicStochasticDifferential
++ AMS Classifications:
++ Keywords: stochastic differential, semimartingale.
++ References: Ito (1975), Kendall (1991a,b; 1993a,b).
++ Description:
++ A basic implementation of StochasticDifferential(R) using the
++ associated domain BasicStochasticDifferential in the underlying
++ representation as sparse multivariate polynomials. The domain is
++ a module over Expression(R), and is a ring without identity
++ (AXIOM term is "Rng"). Note that separate instances, for example
++ using R=Integer and R=Float, have different hidden structure
++ (multiplication and drift tables).

StochasticDifferential(R:Join(OrderedSet, IntegralDomain)):
 Category == Implementation where
  ER ==> Expression(R)
  PR ==> Polynomial(R)
  FR ==> Fraction(PR)
  BSD ==> BasicStochasticDifferential
  PI ==> PositiveInteger
  NNI ==> NonNegativeInteger
  OF  ==> OutputForm
  Category ==> Join(Rng, Module(ER)) with

   RetractableTo(BSD)

   alterQuadVar!:(BSD,BSD,%) -> Union(%,"failed")
    ++ alterQuadVar! adds multiplication formula for a
    ++ pair of stochastic differentials to a private table.
    ++ Failure occurs if
    ++  (a) either of first or second arguments is not basic
    ++  (b) third argument is not exactly of first degree

   alterDrift!:(BSD,%) -> Union(%,"failed")
```

```
 ++ alterDrift! adds drift formula for a
 ++ stochastic differential to a private table.
 ++ Failure occurs if
 ++  (a) first arguments is not basic
 ++  (b) second argument is not exactly of first degree

drift:% -> %
 ++ drift(dx) returns the drift of \axiom{dx}

freeOf?:(%,BSD) -> Boolean
 ++ freeOf?(sd,dX) checks whether \axiom{dX} occurs in
 ++ \axiom{sd} as a module element

coefficient:(%,BSD) -> ER
 ++ coefficient(sd,dX) returns the coefficient of \axiom{dX}
 ++ in the stochastic differential \axiom{sd}

listSD:(%) -> List BSD
 ++ listSD(dx) returns a list of all \axiom{BSD} involved
 ++ in the generation of \axiom{dx} as a module element

equation:(%,R) -> Union(Equation %,"failed")
 ++ equation(dx,0) allows RHS of Equation % to be zero
equation:(R,%) -> Union(Equation %,"failed")
 ++ equation(0,dx) allows LHS of Equation % to be zero

copyDrift:() -> Table(%,%)
 ++ copyDrift returns private table of drifts
 ++ of basic stochastic differentials for inspection

copyQuadVar:() -> Table(%,%)
 ++ copyQuadVar returns private multiplication table
 ++ of basic stochastic differentials for inspection

"/"      : (%, ER) -> %
   ++ dx/y divides the stochastic differential dx
   ++ by the previsible function y.

"**"     : (%, PI) -> %
   ++ dx**n is dx multiplied by itself n times.

"^"      : (%, PI) -> %
   ++ dx^n is dx multiplied by itself n times.

statusIto:()  -> OF
 ++ statusIto() displays the current state of \axiom{setBSD},
 ++ \axiom{tableDrift}, and \axiom{tableQuadVar}. Question
 ++ marks are printed instead of undefined entries
 ++
 ++X dt:=introduce!(t,dt)
```

```
   ++X dX:=introduce!(X,dX)
   ++X dY:=introduce!(Y,dY)
   ++X copyBSD()
   ++X copyIto()
   ++X copyhQuadVar()
   ++X statusIto()

  uncorrelated?: (%,%) -> Boolean
   ++ uncorrelated?(dx,dy) checks whether its two arguments
   ++ have zero quadratic co-variation.
  uncorrelated?: (List %,List %) -> Boolean
   ++ uncorrelated?(l1,l2) checks whether its two arguments
   ++ are lists of stochastic differentials of zero inter-list
   ++ quadratic co-variation.
  uncorrelated?: (List List %) -> Boolean
   ++ uncorrelated?(ll) checks whether its argument is a list
   ++ of lists of stochastic differentials of zero inter-list
   ++ quadratic co-variation.

 Implementation ==> SparseMultivariatePolynomial(ER,BSD) add
  Rep:=SparseMultivariatePolynomial(ER,BSD)

  (v:% / s:ER):% == inv(s) * v

  tableQuadVar:Table(%,%)  := table()
  tableDrift:Table(%,%) := table()

  alterQuadVar!(da:BSD,db:BSD,dXdY:%):Union(%,"failed") ==
   -- next two lines for security only!
   1 < totalDegree(dXdY)                => "failed"
   0 ~= coefficient(dXdY,degree(1)$Rep) => "failed"
   not(0::% = (dXdY*dXdY)::%) => "failed"
   setelt(tableQuadVar,((da::Rep)*(db::Rep))$Rep,dXdY)$Table(%,%)
   -- We have to take care here to avoid a bad
   -- recursion on \axiom{*:(%,%)->%}

  alterDrift!(da:BSD,dx:%):Union(%,"failed") ==
   1 < totalDegree(dx)                => "failed"
   0 ~= coefficient(dx,degree(1)$Rep) => "failed"
   not(0::% = (dx*dx)::%) => "failed"
   setelt(tableDrift,da::Rep,dx)$Table(%,%)

  multSDOrError(dm:%):% ==
   c := leadingCoefficient dm
   (dmm := search(dm/c,tableQuadVar))
     case "failed" =>
      print hconcat(message("ERROR IN ")$OF,(dm/c)::OF)
      error "Above product of sd's is not defined"
   c*dmm
```

```
(dx:% * dy:%) : % ==
 1 < totalDegree(dx) =>
  print hconcat(message("ERROR IN ")$OF,dx::OF)
  error "bad sd in lhs of sd product"
 1 < totalDegree(dy) =>
  print hconcat(message("ERROR IN ")$OF,dy::OF)
  error "bad sd in rhs of sd product"
 reduce("+",map(multSDOrError,monomials((dx*dy)$Rep)),0)
 -- We have to take care here to avoid a bad
 -- recursion on \axiom{*:(%,%)->%}

(dx:% ** n:PI) : % ==
 n = 1 => dx
 n = 2 => dx*dx
 n > 2 => 0::%

(dx:% ^ n:PI) : % == dx**n

driftSDOrError(dm:%):% ==
 c := leadingCoefficient dm
 (dmm := search(dm/c,tableDrift))
   case "failed" =>
    print hconcat(message("ERROR IN ")$OF,(dm/c)::OF)
    error "drift of sd is not defined"
 c*dmm

drift(dx:%):% ==
 reduce("+",map(driftSDOrError,monomials(dx)),0)

freeOf?(sd,dX) == (0 = coefficient(sd,dX,1))

coefficient(sd:%,dX:BSD):ER ==
 retract(coefficient(sd,dX,1))@ER

listSD(sd) ==
 [retract(dX)@BSD for dX in primitiveMonomials(sd)]

equation(dx:%,zero:R):Union(Equation %,"failed") ==
 not(0 = zero) => "failed"
 equation(dx,0::%)
equation(zero:R,dx:%):Union(Equation %,"failed") ==
 not(0 = zero) => "failed"
 equation(0::%,dx)

copyDrift() == tableDrift
copyQuadVar() == tableQuadVar

xDrift(dx:BSD):OF ==
 (xdx := search(dx::Rep,tableDrift)) case "failed" => "?"::OF
 xdx::OF
```

```
   xQV(dx:BSD,dy:BSD):OF ==
    (xdxdy := search((dx::% * dy::%)$Rep,tableQuadVar))
      case "failed" => "?"::Symbol::OF
    xdxdy::OF

   statusIto():OF ==
    bsd  := copyBSD()$BSD
    bsdo := [dx::OF for dx in bsd]
    blank:= ""::Symbol::OF
    colon:= ":"::Symbol::OF
    bsdh := "B S D "::Symbol::OF
    dfth := "drift "::Symbol::OF
    qvh  := "*"::Symbol::OF
    head := append([bsdh,colon],bsdo)
    drift:= append([dfth,colon],[xDrift dx for dx in bsd])
    space:= append([qvh ,blank],[blank for dx in bsd])
    qv   := [append([dy::OF,colon],[xQV(dx,dy) for dx in bsd])
                                               for dy in bsd]
    matrix(append([head,drift,space],qv))$OF

   uncorrelated?(dx:%,dy:%): Boolean == (0::% = dx*dy)

   uncorrelated?(l1:List %,l2:List %): Boolean ==
    reduce("and", [
     reduce("and",[uncorrelated?(dx,dy) for dy in l2],true)
      for dx in l1 ],true)

   uncorrelated1?(l1:List %,ll:List List %): Boolean ==
    reduce("and",[uncorrelated?(l1,l2) for l2 in ll],true)

   uncorrelated?(ll:List List %): Boolean ==
    (0$Integer = # ll) => true
    (1 = # ll) => true
    uncorrelated1?(first ll,rest ll) and uncorrelated?(rest ll)
```

———-

— SD.dotabb —

```
"SD" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SD"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"SD" -> "FS"
```

———-

20.30 domain STREAM Stream

— Stream.input —

```
)set break resume
)sys rm -f Stream.output
)spool Stream.output
)set message test on
)set message auto off
)clear all
--S 1 of 12
ints := [i for i in 0..]
--R
--R
--R   (1)  [0,1,2,3,4,5,6,7,8,9,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 1

--S 2 of 12
f : List INT -> List INT
--R
--R                                                                   Type: Void
--E 2

--S 3 of 12
f x == [x.1 + x.2, x.1]
--R
--R                                                                   Type: Void
--E 3

--S 4 of 12
fibs := [i.2 for i in [generate(f,[1,1])]]
--R
--R   Compiling function f with type List(Integer) -> List(Integer)
--R
--R   (4)  [1,1,2,3,5,8,13,21,34,55,...]
--R                                                        Type: Stream(Integer)
--E 4

--S 5 of 12
[i for i in ints | odd? i]
--R
--R
--R   (5)  [1,3,5,7,9,11,13,15,17,19,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 5

--S 6 of 12
```

```
odds := [2*i+1 for i in ints]
--R
--R
--R   (6)  [1,3,5,7,9,11,13,15,17,19,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 6

--S 7 of 12
scan(0,+,odds)
--R
--R
--R   (7)  [1,4,9,16,25,36,49,64,81,100,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 7

--S 8 of 12
[i*j for i in ints for j in odds]
--R
--R
--R   (8)  [0,3,10,21,36,55,78,105,136,171,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 8

--S 9 of 12
map(*,ints,odds)
--R
--R
--R   (9)  [0,3,10,21,36,55,78,105,136,171,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 9

--S 10 of 12
first ints
--R
--R
--R   (10)  0
--R                                                     Type: NonNegativeInteger
--E 10

--S 11 of 12
rest ints
--R
--R
--R   (11)  [1,2,3,4,5,6,7,8,9,10,...]
--R                                              Type: Stream(NonNegativeInteger)
--E 11

--S 12 of 12
fibs 20
--R
```

```
--R
--R   (12)  6765
--R                                                    Type: PositiveInteger
--E 12
)spool
)lisp (bye)
```

———-

— Stream.help —

```
=====================================================================
Stream examples
=====================================================================

A Stream object is represented as a list whose last element contains
the wherewithal to create the next element, should it ever be required.

Let ints be the infinite stream of non-negative integers.

  ints := [i for i in 0..]
    [0,1,2,3,4,5,6,7,8,9,...]
                                  Type: Stream NonNegativeInteger

By default, ten stream elements are calculated.  This number may be
changed to something else by the system command
  )set streams calculate

More generally, you can construct a stream by specifying its initial
value and a function which, when given an element, creates the next element.

  f : List INT -> List INT
                                  Type: Void

  f x == [x.1 + x.2, x.1]
                                  Type: Void

  fibs := [i.2 for i in [generate(f,[1,1])]]
    [1,1,2,3,5,8,13,21,34,55,...]
                                  Type: Stream Integer

You can create the stream of odd non-negative integers by either filtering
them from the integers, or by evaluating an expression for each integer.

  [i for i in ints | odd? i]
    [1,3,5,7,9,11,13,15,17,19,...]
                                  Type: Stream NonNegativeInteger

  odds := [2*i+1 for i in ints]
```

```
    [1,3,5,7,9,11,13,15,17,19,...]
                                Type: Stream NonNegativeInteger
```

You can accumulate the initial segments of a stream using the scan operation.

```
  scan(0,+,odds)
    [1,4,9,16,25,36,49,64,81,100,...]
                                Type: Stream NonNegativeInteger
```

The corresponding elements of two or more streams can be combined in this way.

```
  [i*j for i in ints for j in odds]
    [0,3,10,21,36,55,78,105,136,171,...]
                                Type: Stream NonNegativeInteger

  map(*,ints,odds)
    [0,3,10,21,36,55,78,105,136,171,...]
                                Type: Stream NonNegativeInteger
```

Many operations similar to those applicable to lists are available for streams.


```
  first ints
    0
                                Type: NonNegativeInteger

  rest ints
    [1,2,3,4,5,6,7,8,9,10,...]
                                Type: Stream NonNegativeInteger

  fibs 20
    6765
                                Type: PositiveInteger
```

See Also:
o)help StreamFunctions1
o)help StreamFunctions2
o)help StreamFunctions3
o)show Stream

20.30.1 Stream (STREAM)



Exports:

any?	child?	children
coerce	complete	concat
concat!	cons	construct
convert	copy	count
cycleEntry	cycleLength	cycleSplit!
cycleTail	cyclic?	delay
delete	distance	elt
empty	empty?	entries
entry?	eq?	eval
eval	eval	eval
every?	explicitEntries?	explicitlyEmpty?
explicitlyFinite?	extend	fill!
filterUntil	filterWhile	find
findCycle	first	frst
generate	hash	index?
indices	insert	insert
last	latex	lazy?
lazyEvaluate	leaf?	leaves
less?	map	map!
maxIndex	member?	members
minIndex	more?	new
nodes	node?	numberOfComputedEntries
output	parts	possiblyInfinite?
qelt	qsetelt!	reduce
remove	removeDuplicates	repeating
repeating?	rest	rst
sample	second	select
setchildren!	setelt	setfirst!
setlast!	setrest!	setvalue!
showAll?	showAllElements	size?
split!	swap!	tail
third	value	#?
?=?	?~=?	?.?
?.last	?.rest	?.first
?.value		

— domain STREAM Stream —

```
)abbrev domain STREAM Stream
++ Implementation of streams via lazy evaluation
++ Authors: Burge, Watt; updated by Clifton J. Williamson
++ Date Created: July 1986
++ Date Last Updated: 30 March 1990
++ Keywords: stream, infinite list, infinite sequence
++ Examples:
++ References:
```

```
++ Description:
++ A stream is an implementation of an infinite sequence using
++ a list of terms that have been computed and a function closure
++ to compute additional terms when needed.

Stream(S): Exports == Implementation where
--  problems:
--  1) dealing with functions which basically want a finite structure
--  2) 'map' doesn't deal with cycles very well

  S : Type
  B   ==> Boolean
  OUT ==> OutputForm
  I   ==> Integer
  L   ==> List
  NNI ==> NonNegativeInteger
  U   ==> UniversalSegment I

  Exports ==> LazyStreamAggregate(S) with
    shallowlyMutable
      ++ one may destructively alter a stream by assigning new
      ++ values to its entries.

    coerce: L S -> %
      ++ coerce(l) converts a list l to a stream.
      ++
      ++X m:=[1,2,3,4,5,6,7,8,9,10,11,12]
      ++X coerce(m)@Stream(Integer)
      ++X m::Stream(Integer)

    repeating: L S -> %
      ++ repeating(l) is a repeating stream whose period is the list l.
      ++
      ++X m:=repeating([-1,0,1,2,3])

    if S has SetCategory then
      repeating?: (L S,%) -> B
        ++ repeating?(l,s) returns true if a stream s is periodic
        ++ with period l, and false otherwise.
        ++
        ++X m:=[1,2,3]
        ++X n:=repeating(m)
        ++X repeating?(m,n)

    findCycle: (NNI,%) -> Record(cycle?: B, prefix: NNI, period: NNI)
      ++ findCycle(n,st) determines if st is periodic within n.
      ++
      ++X m:=[1,2,3]
      ++X n:=repeating(m)
      ++X findCycle(3,n)
```

```
    ++X findCycle(2,n)

  delay: (() -> %) -> %
    ++ delay(f) creates a stream with a lazy evaluation defined by
    ++ function f.
    ++ Caution: This function can only be called in compiled code.
  cons: (S,%) -> %
    ++ cons(a,s) returns a stream whose \spad{first} is \spad{a}
    ++ and whose \spad{rest} is s.
    ++ Note: \spad{cons(a,s) = concat(a,s)}.
    ++
    ++X m:=[1,2,3]
    ++X n:=repeating(m)
    ++X cons(4,n)

  if S has SetCategory then
    output: (I, %) -> Void
      ++ output(n,st) computes and displays the first n entries
      ++ of st.
      ++
      ++X m:=[1,2,3]
      ++X n:=repeating(m)
      ++X output(5,n)

    showAllElements: % -> OUT
      ++ showAllElements(s) creates an output form which displays all
      ++ computed elements.
      ++
      ++X m:=[1,2,3,4,5,6,7,8,9,10,11,12]
      ++X n:=m::Stream(PositiveInteger)
      ++X showAllElements n

    showAll?: () -> B
      ++ showAll?() returns true if all computed entries of streams
      ++ will be displayed.
      --!! this should be a function of one argument
  setrest_!: (%,I,%) -> %
    ++ setrest!(x,n,y) sets rest(x,n) to y. The function will expand
    ++ cycles if necessary.
    ++
    ++X p:=[i for i in 1..]
    ++X q:=[i for i in 9..]
    ++X setrest!(p,4,q)
    ++X p

  generate: (() -> S) -> %
    ++ generate(f) creates an infinite stream all of whose elements are
    ++ equal to \spad{f()}.
    ++ Note: \spad{generate(f) = [f(),f(),f(),...]}.
    ++
```

```
      ++X f():Integer == 1
      ++X generate(f)

    generate: (S -> S,S) -> %
      ++ generate(f,x) creates an infinite stream whose first element is
      ++ x and whose nth element (\spad{n > 1}) is f applied to the previous
      ++ element. Note: \spad{generate(f,x) = [x,f(x),f(f(x)),...]}.
      ++
      ++X f(x:Integer):Integer == x+10
      ++X generate(f,10)

    filterWhile: (S -> Boolean,%) -> %
      ++ filterWhile(p,s) returns \spad{[x0,x1,...,x(n-1)]} where
      ++ \spad{s = [x0,x1,x2,..]} and
      ++ n is the smallest index such that \spad{p(xn) = false}.
      ++
      ++X m:=[i for i in 1..]
      ++X f(x:PositiveInteger):Boolean ==  x < 5
      ++X filterWhile(f,m)

    filterUntil: (S -> Boolean,%) -> %
      ++ filterUntil(p,s) returns \spad{[x0,x1,...,x(n)]} where
      ++ \spad{s = [x0,x1,x2,..]} and
      ++ n is the smallest index such that \spad{p(xn) = true}.
      ++
      ++X m:=[i for i in 1..]
      ++X f(x:PositiveInteger):Boolean ==  x < 5
      ++X filterUntil(f,m)

--    if S has SetCategory then
--      map: ((S,S) -> S,%,%,S) -> %
--       ++ map(f,x,y,a) is equivalent to map(f,x,y)
--       ++ If z = map(f,x,y,a), then z = map(f,x,y) except if
--       ++ x.n = a and rest(rest(x,n)) = rest(x,n) in which case
--       ++ rest(z,n) = rest(y,n) or if y.m = a and rest(rest(y,m)) =
--       ++ rest(y,m) in which case rest(z,n) = rest(x,n).
--       ++ Think of the case where f(xi,yi) = xi + yi and a = 0.

  Implementation ==> add
    MIN ==> 1  -- minimal stream index; see also the defaults in LZSTAGG
    x:%

    import CyclicStreamTools(S,%)

--% representation

    -- This description of the rep is not quite true.
    -- The Rep is a pair of one of three forms:
    --    [value: S,             rest: %]
    --    [nullstream:    Magic, NIL    ]
```

```
    --    [nonnullstream: Magic, fun: () -> %]
    -- Could use a record of unions if we could guarantee no tags.

    NullStream:    S := _$NullStream$Lisp    pretend S
    NonNullStream: S := _$NonNullStream$Lisp pretend S

    Rep := Record(firstElt: S, restOfStream: %)

    explicitlyEmpty? x == EQ(frst x,NullStream)$Lisp
    lazy? x            == EQ(frst x,NonNullStream)$Lisp

--% signatures of local functions

    setfrst_!     : (%,S) -> S
    setrst_!      : (%,%) -> %
    setToNil_!    : % -> %
    setrestt_!    : (%,I,%) -> %
    lazyEval      : % -> %
    expand_!      : (%,I) -> %

--% functions to access or change record fields without lazy evaluation

    frst x == x.firstElt
    rst  x == x.restOfStream

    setfrst_!(x,s) == x.firstElt := s
    setrst_!(x,y)  == x.restOfStream := y

    setToNil_! x ==
    -- destructively changes x to a null stream
      setfrst_!(x,NullStream); setrst_!(x,NIL$Lisp)
      x

--% SETCAT functions

    if S has SetCategory then

      getm              : (%,L OUT,I) -> L OUT
      streamCountCoerce : % -> OUT
      listm             : (%,L OUT,I) -> L OUT

      getm(x,le,n) ==
        explicitlyEmpty? x => le
        lazy? x =>
          n > 0 =>
            empty? x => le
            getm(rst x,concat(frst(x) :: OUT,le),n - 1)
          concat(message("..."),le)
        eq?(x,rst x) => concat(overbar(frst(x) :: OUT),le)
        n > 0 => getm(rst x,concat(frst(x) :: OUT,le),n - 1)
```

```
    concat(message("..."),le)

  streamCountCoerce x ==
  -- this will not necessarily display all stream elements
  -- which have been computed
    count := _$streamCount$Lisp
    -- compute count elements
    y := x
    for i in 1..count while not empty? y repeat y := rst y
    fc := findCycle(count,x)
    not fc.cycle? => bracket reverse_! getm(x,empty(),count)
    le : L OUT := empty()
    for i in 1..fc.prefix repeat
      le := concat(first(x) :: OUT,le)
      x := rest x
    pp : OUT :=
      fc.period = 1 => overbar(frst(x) :: OUT)
      pl : L OUT := empty()
      for i in 1..fc.period repeat
        pl := concat(frst(x) :: OUT,pl)
        x  := rest x
      overbar commaSeparate reverse_! pl
    bracket reverse_! concat(pp,le)

  listm(x,le,n) ==
    explicitlyEmpty? x => le
    lazy? x =>
      n > 0 =>
        empty? x => le
        listm(rst x, concat(frst(x) :: OUT,le),n-1)
      concat(message("..."),le)
    listm(rst x,concat(frst(x) :: OUT,le),n-1)

  showAllElements x ==
  -- this will display all stream elements which have been computed
  -- and will display at least n elements with n = streamCount$Lisp
    extend(x,_$streamCount$Lisp)
    cycElt := cycleElt x
    cycElt case "failed" =>
      le := listm(x,empty(),_$streamCount$Lisp)
      bracket reverse_! le
    cycEnt := computeCycleEntry(x,cycElt :: %)
    le : L OUT := empty()
    while not eq?(x,cycEnt) repeat
      le := concat(frst(x) :: OUT,le)
      x := rst x
    len := computeCycleLength(cycElt :: %)
    pp : OUT :=
      len = 1 => overbar(frst(x) :: OUT)
      pl : L OUT := []
```

```
          for i in 1..len repeat
            pl := concat(frst(x) :: OUT,pl)
            x := rst x
          overbar commaSeparate reverse_! pl
        bracket reverse_! concat(pp,le)

      showAll?() ==
        NULL(_$streamsShowAll$Lisp)$Lisp => false
        true

      coerce(x):OUT ==
        showAll?() => showAllElements x
        streamCountCoerce x

--% AGG functions

    lazyCopy:% -> %
    lazyCopy x == delay
      empty? x => empty()
      concat(frst x, copy rst x)

    copy x ==
      cycElt := cycleElt x
      cycElt case "failed" => lazyCopy x
      ce := cycElt :: %
      len := computeCycleLength(ce)
      e := computeCycleEntry(x,ce)
      d := distance(x,e)
      cycle := complete first(e,len)
      setrst_!(tail cycle,cycle)
      d = 0 => cycle
      head := complete first(x,d::NNI)
      setrst_!(tail head,cycle)
      head

--% CNAGG functions

    construct l ==
      -- copied from defaults to avoid loading defaults
      empty? l => empty()
      concat(first l, construct rest l)

--% ELTAGG functions

    elt(x:%,n:I) ==
      -- copied from defaults to avoid loading defaults
      n < MIN or empty? x => error "elt: no such element"
      n = MIN => frst x
      elt(rst x,n - 1)
```

```
    seteltt:(%,I,S) -> S
    seteltt(x,n,s) ==
      n = MIN => setfrst_!(x,s)
      seteltt(rst x,n - 1,s)

    setelt(x,n:I,s:S) ==
      n < MIN or empty? x => error "setelt: no such element"
      x := expand_!(x,n - MIN + 1)
      seteltt(x,n,s)

--% IXAGG functions

    removee: ((S -> Boolean),%) -> %
    removee(p,x) == delay
      empty? x => empty()
      p(frst x) => remove(p,rst x)
      concat(frst x,remove(p,rst x))

    remove(p,x) ==
      explicitlyEmpty? x => empty()
      eq?(x,rst x) =>
        p(frst x) => empty()
        x
      removee(p,x)

    selectt: ((S -> Boolean),%) -> %
    selectt(p,x) == delay
      empty? x => empty()
      not p(frst x) => select(p, rst x)
      concat(frst x,select(p,rst x))

    select(p,x) ==
      explicitlyEmpty? x => empty()
      eq?(x,rst x) =>
        p(frst x) => x
        empty()
      selectt(p,x)

    map(f,x) ==
      map(f,x pretend Stream(S))$StreamFunctions2(S,S) pretend %

    map(g,x,y) ==
      xs := x pretend Stream(S); ys := y pretend Stream(S)
      map(g,xs,ys)$StreamFunctions3(S,S,S) pretend %

    fill_!(x,s) ==
      setfrst_!(x,s)
      setrst_!(x,x)

    map_!(f,x) ==
```

```
    -- too many problems with map_! on a lazy stream, so
    -- in this case, an error message is returned
      cyclic? x =>
        tail := cycleTail x ; y := x
        until y = tail repeat
          setfrst_!(y,f frst y)
          y := rst y
        x
      explicitlyFinite? x =>
        y := x
        while not empty? y repeat
          setfrst_!(y,f frst y)
          y := rst y
        x
      error "map!: stream with lazy evaluation"

    swap_!(x,m,n) ==
      (not index?(m,x)) or (not index?(n,x)) =>
        error "swap!: no such elements"
      x := expand_!(x,max(m,n) - MIN + 1)
      xm := elt(x,m); xn := elt(x,n)
      setelt(x,m,xn); setelt(x,n,xm)
      x

--% LNAGG functions

    concat(x:%,s:S) == delay
      empty? x => concat(s,empty())
      concat(frst x,concat(rst x,s))

    concat(x:%,y:%) == delay
      empty? x => copy y
      concat(frst x,concat(rst x, y))

    concat l == delay
      empty? l => empty()
      empty?(x := first l) => concat rest l
      concat(frst x,concat(rst x,concat rest l))

    setelt(x,seg:U,s:S) ==
      low := lo seg
      hasHi seg =>
        high := hi seg
        high < low => s
        (not index?(low,x)) or (not index?(high,x)) =>
          error "setelt: index out of range"
        x := expand_!(x,high - MIN + 1)
        y := rest(x,(low - MIN) :: NNI)
        for i in 0..(high-low) repeat
          setfrst_!(y,s)
```

```
          y := rst y
        s
      not index?(low,x) => error "setelt: index out of range"
      x := rest(x,(low - MIN) :: NNI)
      setrst_!(x,x)
      setfrst_!(x,s)

--% RCAGG functions

    empty() == [NullStream, NIL$Lisp]

    lazyEval x == (rst(x):(()-> %)) ()

    lazyEvaluate x ==
      st := lazyEval x
      setfrst_!(x, frst st)
      setrst_!(x,if EQ(rst st,st)$Lisp then x else rst st)
      x

    -- empty? is the only function that explicitly causes evaluation
    -- of a stream element
    empty? x ==
      while lazy? x repeat
        st := lazyEval x
        setfrst_!(x, frst st)
        setrst_!(x,if EQ(rst st,st)$Lisp then x else rst st)
      explicitlyEmpty? x

    --setvalue(x,s) == setfirst_!(x,s)

    --setchildren(x,l) ==
      --empty? l => error "setchildren: empty list of children"
      --not(empty? rest l) => error "setchildren: wrong number of children"
      --setrest_!(x,first l)

--% URAGG functions

    first(x,n) == delay
    -- former name: take
      n = 0 or empty? x => empty()
      (concat(frst x, first(rst x,(n-1) :: NNI)))

    concat(s:S,x:%) == [s,x]
    cons(s,x) == concat(s,x)

    cycleSplit_! x ==
      cycElt := cycleElt x
      cycElt case "failed" =>
        error "cycleSplit_!: non-cyclic stream"
      y := computeCycleEntry(x,cycElt :: %)
```

```
    eq?(x,y) => (setToNil_! x; return y)
    z := rst x
    repeat
      eq?(y,z) => (setrest_!(x,empty()); return y)
      x := z ; z := rst z

  expand_!(x,n) ==
  -- expands cycles (if necessary) so that the first n
  -- elements of x will not be part of a cycle
    n < 1 => x
    y := x
    for i in 1..n while not empty? y repeat y := rst y
    cycElt := cycleElt x
    cycElt case "failed" => x
    e := computeCycleEntry(x,cycElt :: %)
    d : I := distance(x,e)
    d >= n => x
    if d = 0 then
      -- roll the cycle 1 entry
      d := 1
      t := cycleTail e
      if eq?(t,e) then
        t := concat(frst t,empty())
        e := setrst_!(t,t)
        setrst_!(x,e)
      else
        setrst_!(t,concat(frst e,rst e))
        e := rst e
    nLessD := (n-d) :: NNI
    y := complete first(e,nLessD)
    e := rest(e,nLessD)
    setrst_!(tail y,e)
    setrst_!(rest(x,(d-1) :: NNI),y)
    x

  first x ==
    empty? x => error "Can't take the first of an empty stream."
    frst x

  concat_!(x:%,y:%) ==
    empty? x => y
    setrst_!(tail x,y)

  concat_!(x:%,s:S) ==
    concat_!(x,concat(s,empty()))

  setfirst_!(x,s) == setelt(x,0,s)
  setelt(x,"first",s) == setfirst_!(x,s)
  setrest_!(x,y) ==
    empty? x => error "setrest!: empty stream"
```

```
      setrst_!(x,y)
    setelt(x,"rest",y) == setrest_!(x,y)

    setlast_!(x,s) ==
      empty? x => error "setlast!: empty stream"
      setfrst_!(tail x, s)
    setelt(x,"last",s) == setlast_!(x,s)

    split_!(x,n) ==
      n < MIN => error "split!: index out of range"
      n = MIN =>
        y : % := empty()
        setfrst_!(y,frst x)
        setrst_!(y,rst x)
        setToNil_! x
        y
      x := expand_!(x,n - MIN)
      x := rest(x,(n - MIN - 1) :: NNI)
      y := rest x
      setrst_!(x,empty())
      y

--% STREAM functions

    coerce(l: L S) == construct l

    repeating l ==
      empty? l =>
        error "Need a non-null list to make a repeating stream."
      x0 : % := x := construct l
      while not empty? rst x repeat x := rst x
      setrst_!(x,x0)

    if S has SetCategory then

      repeating?(l, x) ==
        empty? l =>
          error "Need a non-empty? list to make a repeating stream."
        empty? rest l =>
          not empty? x and frst x = first l and x = rst x
        x0 := x
        for s in l repeat
          empty? x or s ^= frst x => return false
          x := rst x
        eq?(x,x0)

    findCycle(n, x) ==
      hd := x
      -- Determine whether periodic within n.
      tl := rest(x, n)
```

```
      explicitlyEmpty? tl => [false, 0, 0]
      i := 0; while not eq?(x,tl) repeat (x := rst x; i := i + 1)
      i = n => [false, 0, 0]
      -- Find period. Now x=tl, so step over and find it again.
      x := rst x; per := 1
      while not eq?(x,tl) repeat (x := rst x; per := per + 1)
      -- Find non-periodic part.
      x := hd; xp := rest(hd, per); npp := 0
      while not eq?(x,xp) repeat (x := rst x; xp := rst xp; npp := npp+1)
      [true, npp, per]

    delay(fs:()->%) == [NonNullStream, fs pretend %]

--     explicitlyEmpty? x == markedNull? x

    explicitEntries? x ==
      not explicitlyEmpty? x and not lazy? x

    numberOfComputedEntries x ==
      explicitEntries? x => numberOfComputedEntries(rst x) + 1
      0

    if S has SetCategory then

      output(n,x) ==
        (not(n>0))or empty? x => void()
        mathPrint(frst(x)::OUT)$Lisp
        output(n-1, rst x)

    setrestt_!(x,n,y) ==
      n = 0 => setrst_!(x,y)
      setrestt_!(rst x,n-1,y)

    setrest_!(x,n,y) ==
      n < 0 or empty? x => error "setrest!: no such rest"
      x := expand_!(x,n+1)
      setrestt_!(x,n,y)

    generate f    == delay concat(f(), generate f)
    gen:(S -> S,S) -> %
    gen(f,s) == delay(ss:=f s; concat(ss, gen(f,ss)))
    generate(f,s)==concat(s,gen(f,s))

    concat(x:%,y:%) ==delay
      empty? x => y
      concat(frst x,concat(rst x,y))

    swhilee:(S -> Boolean,%) -> %
    swhilee(p,x) == delay
      empty? x      => empty()
```

```
      not p(frst x) => empty()
      concat(frst x,filterWhile(p,rst x))
    filterWhile(p,x)==
      explicitlyEmpty? x => empty()
      eq?(x,rst x) =>
        p(frst x) => x
        empty()
      swhilee(p,x)

    suntill: (S -> Boolean,%) -> %
    suntill(p,x) == delay
      empty? x  => empty()
      p(frst x) => concat(frst x,empty())
      concat(frst x, filterUntil(p, rst x))

    filterUntil(p,x)==
      explicitlyEmpty? x => empty()
      eq?(x,rst x) =>
        p(frst x) => concat(frst x,empty())
        x
      suntill(p,x)

--  if S has SetCategory then
--    mapp: ((S,S) -> S,%,%,S) -> %
--    mapp(f,x,y,a) == delay
--      empty? x or empty? y => empty()
--      concat(f(frst x,frst y), map(f,rst x,rst y,a))
--      map(f,x,y,a) ==
--      explicitlyEmpty? x => empty()
--      eq?(x,rst x) =>
--        frst x=a => y
--        map(f(frst x,#1),y)
--      explicitlyEmpty? y => empty()
--      eq?(y,rst y) =>
--        frst y=a => x
--        p(f(#1,frst y),x)
--      mapp(f,x,y,a)
```

———-

— STREAM.dotabb —

```
"STREAM" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STREAM"]
"LZSTAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=LZSTAGG"]
"STREAM" -> "LZSTAGG"
```

———-

20.31 domain STRING String

— String.input —

```
)set break resume
)sys rm -f String.output
)spool String.output
)set message test on
)set message auto off
)clear all
--S 1 of 35
hello := "Hello, I'm AXIOM!"
--R
--R
--R   (1)  "Hello, I'm AXIOM!"
--R                                                          Type: String
--E 1

--S 2 of 35
said := "Jane said, \_"Look!\_""
--R
--R
--R   (2)  "Jane said, \"Look!\""
--R                                                          Type: String
--E 2

--S 3 of 35
saw := "She saw exactly one underscore: \_\_."
--R
--R
--R   (3)  "She saw exactly one underscore: \\."
--R                                                          Type: String
--E 3

--S 4 of 35
gasp: String := new(32, char "x")
--R
--R
--R   (4)  "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx"
--R                                                          Type: String
--E 4

--S 5 of 35
#gasp
--R
--R
--R   (5)  32
--R                                                  Type: PositiveInteger
```

```
--E 5

--S 6 of 35
hello.2
--R
--R
--R   (6)  e
--R                                                    Type: Character
--E 6

--S 7 of 35
hello 2
--R
--R
--R   (7)  e
--R                                                    Type: Character
--E 7

--S 8 of 35
hello(2)
--R
--R
--R   (8)  e
--R                                                    Type: Character
--E 8

--S 9 of 35
hullo := copy hello
--R
--R
--R   (9)  "Hello, I'm AXIOM!"
--R                                                       Type: String
--E 9

--S 10 of 35
hullo.2 := char "u"; [hello, hullo]
--R
--R
--R   (10)  ["Hello, I'm AXIOM!","Hullo, I'm AXIOM!"]
--R                                                 Type: List(String)
--E 10

--S 11 of 35
saidsaw := concat ["alpha","---","omega"]
--R
--R
--R   (11)  "alpha---omega"
--R                                                       Type: String
--E 11
```

```
--S 12 of 35
concat("hello ","goodbye")
--R
--R
--R   (12)  "hello goodbye"
--R                                                          Type: String
--E 12

--S 13 of 35
"This " "is " "several " "strings " "concatenated."
--R
--R
--R   (13)  "This is several strings concatenated."
--R                                                          Type: String
--E 13

--S 14 of 35
hello(1..5)
--R
--R
--R   (14)  "Hello"
--R                                                          Type: String
--E 14

--S 15 of 35
hello(8..)
--R
--R
--R   (15)  "I'm AXIOM!"
--R                                                          Type: String
--E 15

--S 16 of 35
split(hello, char " ")
--R
--R
--R   (16)  ["Hello,","I'm","AXIOM!"]
--R                                                  Type: List(String)
--E 16

--S 17 of 35
other := complement alphanumeric();
--R
--R                                                Type: CharacterClass
--E 17

--S 18 of 35
split(saidsaw, other)
--R
--R
```

```
--R   (18)  ["alpha","omega"]
--R                                                    Type: List(String)
--E 18

--S 19 of 35
trim("## ++ relax ++ ##", char "#")
--R
--R
--R   (19)  " ++ relax ++ "
--R                                                          Type: String
--E 19

--S 20 of 35
trim("## ++ relax ++ ##", other)
--R
--R
--R   (20)  "relax"
--R                                                          Type: String
--E 20

--S 21 of 35
leftTrim("## ++ relax ++ ##", other)
--R
--R
--R   (21)  "relax ++ ##"
--R                                                          Type: String
--E 21

--S 22 of 35
rightTrim("## ++ relax ++ ##", other)
--R
--R
--R   (22)  "## ++ relax"
--R                                                          Type: String
--E 22

--S 23 of 35
upperCase hello
--R
--R
--R   (23)  "HELLO, I'M AXIOM!"
--R                                                          Type: String
--E 23

--S 24 of 35
lowerCase hello
--R
--R
--R   (24)  "hello, i'm axiom!"
--R                                                          Type: String
```

```
--E 24

--S 25 of 35
prefix?("He", "Hello")
--R
--R
--R   (25)  true
--R                                                    Type: Boolean
--E 25

--S 26 of 35
prefix?("Her", "Hello")
--R
--R
--R   (26)  false
--R                                                    Type: Boolean
--E 26

--S 27 of 35
suffix?("", "Hello")
--R
--R
--R   (27)  true
--R                                                    Type: Boolean
--E 27

--S 28 of 35
suffix?("LO", "Hello")
--R
--R
--R   (28)  false
--R                                                    Type: Boolean
--E 28

--S 29 of 35
substring?("ll", "Hello", 3)
--R
--R
--R   (29)  true
--R                                                    Type: Boolean
--E 29

--S 30 of 35
substring?("ll", "Hello", 4)
--R
--R
--R   (30)  false
--R                                                    Type: Boolean
--E 30
```

```
--S 31 of 35
n := position("nd", "underground", 1)
--R
--R
--R   (31)  2
--R                                                    Type: PositiveInteger
--E 31

--S 32 of 35
n := position("nd", "underground", n+1)
--R
--R
--R   (32)  10
--R                                                    Type: PositiveInteger
--E 32

--S 33 of 35
n := position("nd", "underground", n+1)
--R
--R
--R   (33)  0
--R                                                 Type: NonNegativeInteger
--E 33

--S 34 of 35
position(char "d", "underground", 1)
--R
--R
--R   (34)  3
--R                                                    Type: PositiveInteger
--E 34

--S 35 of 35
position(hexDigit(), "underground", 1)
--R
--R
--R   (35)  3
--R                                                    Type: PositiveInteger
--E 35
)spool
)lisp (bye)
```

———-

— String.help —

```
=====================================================================
String examples
=====================================================================
```

```
The type String provides character strings.  Character strings
provide all the operations for a one-dimensional array of characters,
plus additional operations for manipulating text.

String values can be created using double quotes.

  hello := "Hello, I'm AXIOM!"
    "Hello, I'm AXIOM!"
                                Type: String

Note, however, that double quotes and underscores must be preceded by
an extra underscore.

  said := "Jane said, \_"Look!\_""
    "Jane said, \"Look!\""
                                Type: String

  saw := "She saw exactly one underscore: \_\_."
    "She saw exactly one underscore: \\."
                                Type: String

It is also possible to use new to create a string of any size filled
with a given character.  Since there are many new functions it is
necessary to indicate the desired type.

  gasp: String := new(32, char "x")
    "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx"
                                Type: String

The length of a string is given by #.

  #gasp
    32
                                Type: PositiveInteger

Indexing operations allow characters to be extracted or replaced in strings.
For any string s, indices lie in the range 1..#s.

  hello.2
    e
                                Type: Character

Indexing is really just the application of a string to a subscript, so
any application syntax works.

  hello 2
    e
                                Type: Character
```

```
  hello(2)
    e
                                Type: Character
```

If it is important not to modify a given string, it should be copied before any updating operations are used.

```
  hullo := copy hello
    "Hello, I'm AXIOM!"
                                Type: String

  hullo.2 := char "u"; [hello, hullo]
    ["Hello, I'm AXIOM!","Hullo, I'm AXIOM!"]
                                Type: List String
```

Operations are provided to split and join strings. The concat operation allows several strings to be joined together.

```
  saidsaw := concat ["alpha","---","omega"]
    "alpha---omega"
                                Type: String
```

There is a version of concat that works with two strings.

```
  concat("hello ","goodbye")
    "hello goodbye"
                                Type: String
```

Juxtaposition can also be used to concatenate strings.

```
  "This " "is " "several " "strings " "concatenated."
    "This is several strings concatenated."
                                Type: String
```

Substrings are obtained by giving an index range.

```
  hello(1..5)
    "Hello"
                                Type: String

  hello(8..)
    "I'm AXIOM!"
                                Type: String
```

A string can be split into several substrings by giving a separation character or character class.

```
  split(hello, char " ")
    ["Hello,","I'm","AXIOM!"]
                                Type: List String
```

```
  other := complement alphanumeric();
                                Type: CharacterClass

  split(saidsaw, other)
    ["alpha","omega"]
                                Type: List String
```

Unwanted characters can be trimmed from the beginning or end of a string using the operations trim, leftTrim and rightTrim.

```
  trim("## ++ relax ++ ##", char "#")
    " ++ relax ++ "
                                Type: String
```

Each of these functions takes a string and a second argument to specify the characters to be discarded.

```
  trim("## ++ relax ++ ##", other)
    "relax"
                                Type: String
```

The second argument can be given either as a single character or as a character class.

```
  leftTrim("## ++ relax ++ ##", other)
    "relax ++ ##"
                                Type: String

  rightTrim("## ++ relax ++ ##", other)
    "## ++ relax"
                                Type: String
```

Strings can be changed to upper case or lower case using the operations upperCase and lowerCase.

```
  upperCase hello
    "HELLO, I'M AXIOM!"
                                Type: String
```

The versions with the exclamation mark change the original string, while the others produce a copy.

```
  lowerCase hello
    "hello, i'm axiom!"
                                Type: String
```

Some basic string matching is provided. The function prefix? tests whether one string is an initial prefix of another.

```
  prefix?("He", "Hello")
    true
                                Type: Boolean

  prefix?("Her", "Hello")
    false
                                Type: Boolean
```

A similar function, suffix?, tests for suffixes.

```
  suffix?("", "Hello")
    true
                                Type: Boolean

  suffix?("LO", "Hello")
    false
                                Type: Boolean
```

The function substring? tests for a substring given a starting position.

```
  substring?("ll", "Hello", 3)
    true
                                Type: Boolean

  substring?("ll", "Hello", 4)
    false
                                Type: Boolean
```

A number of position functions locate things in strings. If the first argument to position is a string, then position(s,t,i) finds the location of s as a substring of t starting the search at position i.

```
  n := position("nd", "underground", 1)
    2
                                Type: PositiveInteger

  n := position("nd", "underground", n+1)
    10
                                Type: PositiveInteger
```

If s is not found, then 0 is returned (minIndex(s)-1 in IndexedString).

```
  n := position("nd", "underground", n+1)
    0
                                Type: NonNegativeInteger
```

To search for a specific character or a member of a character class, a different first argument is used.


```
  position(char "d", "underground", 1)
```

```
    3
                                Type: PositiveInteger

  position(hexDigit(), "underground", 1)
    3
                                Type: PositiveInteger

See Also:
o )help Character
o )help CharacterClass
o )show String
```

20.31.1 String (STRING)



See

⇒ “Character” (CHAR) 4.3.1 on page 359
⇒ “CharacterClass” (CCLASS) 4.4.1 on page 367
⇒ “IndexedString” (ISTRING) 10.14.1 on page 1218

Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	delete	elt
empty	empty?	entries	entry?	eq?
eval	every?	fill!	find	first
hash	index?	indices	insert	latex
leftTrim	less?	lowerCase	lowerCase!	map
map!	match	match?	max	maxIndex
member?	members	merge	min	minIndex
more?	new	OMwrite	parts	position
prefix?	qelt	qsetelt!	reduce	removeDuplicates
replace	reverse	reverse!	rightTrim	sample
select	setelt	size?	sort	sort!
sorted?	split	string	substring?	suffix?
swap!	trim	upperCase	upperCase!	#?
?=?	?.?	?~=?	?<?	?<=?
?>?	?>=?			

— domain STRING String —

```
)abbrev domain STRING String
++ Author: Mark Botch
++ Description:
++ This is the domain of character strings. Strings are 1 based.

String(): StringCategory == IndexedString(1) add
    string n == STRINGIMAGE(n)$Lisp

    OMwrite(x: %): String ==
      s: String := ""
      sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
      dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
      OMputObject(dev)
      OMputString(dev, x pretend String)
      OMputEndObject(dev)
      OMclose(dev)
      s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
      s

    OMwrite(x: %, wholeObj: Boolean): String ==
      s: String := ""
      sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
      dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
      if wholeObj then
        OMputObject(dev)
      OMputString(dev, x pretend String)
      if wholeObj then
        OMputEndObject(dev)
      OMclose(dev)
```

```
      s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
      s

    OMwrite(dev: OpenMathDevice, x: %): Void ==
      OMputObject(dev)
      OMputString(dev, x pretend String)
      OMputEndObject(dev)

    OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
      if wholeObj then
        OMputObject(dev)
      OMputString(dev, x pretend String)
      if wholeObj then
        OMputEndObject(dev)
```

———-

— STRING.dotabb —

```
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"STRICAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=STRICAT"]
"STRING" -> "STRICAT"
```

———-

20.32 domain STRTBL StringTable

— StringTable.input —

```
)set break resume
)sys rm -f StringTable.output
)spool StringTable.output
)set message test on
)set message auto off
)clear all
--S 1 of 3
t: StringTable(Integer) := table()
--R
--R
--R   (1)  table()
--R                                                    Type: StringTable(Integer)
--E 1

--S 2 of 3
```

```
for s in split("My name is Ian Watt.",char " ")
  repeat
    t.s := #s
--R
--R                                                                   Type: Void
--E 2

--S 3 of 3
for key in keys t repeat output [key, t.key]
--R
--R   ["Watt.",5]
--R   ["Ian",3]
--R   ["is",2]
--R   ["name",4]
--R   ["My",2]
--R                                                                   Type: Void
--E 3
)spool
)lisp (bye)
```

———-

— **StringTable.help** —

```
====================================================================
StringTable examples
====================================================================

This domain provides a table type in which the keys are known to be strings
so special techniques can be used.  Other than performance, the type
StringTable(S) should behave exactly the same way as Table(String,S).

This creates a new table whose keys are strings.

  t: StringTable(Integer) := table()
    table()
                              Type: StringTable Integer

The value associated with each string key is the number of characters
in the string.


for s in split("My name is Ian Watt.",char " ")
  repeat
    t.s := #s
                              Type: Void

  for key in keys t repeat output [key, t.key]
   ["Watt.",5]
   ["Ian",3]
```

```
   ["is",2]
   ["name",4]
   ["My",2]
                                   Type: Void

See Also:
o )help Table
o )show StringTable
```

20.32.1 StringTable (STRTBL)



See

⇒ “HashTable” (HASHTBL) 9.1.1 on page 1089
⇒ “InnerTable” (INTABL) 10.27.1 on page 1303
⇒ “Table” (TABLE) 21.1.1 on page 2631
⇒ “EqTable” (EQTBL) 6.2.1 on page 669
⇒ “GeneralSparseTable” (GSTBL) 8.5.1 on page 1048
⇒ “SparseTable” (STBL) 20.16.1 on page 2418

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	elt	empty
empty?	entries	entry?	eq?	eval
every?	extract!	fill!	find	first
hash	index?	indices	insert!	inspect
key?	keys	latex	less?	map
map!	maxIndex	member?	members	minIndex
more?	parts	qelt	qsetelt!	reduce
remove	remove!	removeDuplicates	sample	search
select	select!	setelt	size?	swap!
table	#?	?=?	?~=?	?.?

— **domain STRTBL StringTable** —

```
)abbrev domain STRTBL StringTable
++ Author: Stephen M. Watt
++ Date Created:
++ Date Last Updated: June 21, 1991
++ Basic Operations:
++ Related Domains: Table
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
++ This domain provides tables where the keys are strings.
++ A specialized hash function for strings is used.

StringTable(Entry: SetCategory) ==
    HashTable(String, Entry, "CVEC")
```

———-

— **STRTBL.dotabb** —

```
"STRTBL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRTBL"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"STRTBL" -> "TBAGG"
```

———-

20.33 domain SUBSPACE SubSpace

The first argument n is the dimension of the subSpace

The SubSpace domain is implemented as a tree. The root of the tree is the only node in which the field dataList - which points to a list of points over the ring, R - is defined. The children of the root are the top level components of the SubSpace (in 2D, these would be separate curves; in 3D, these would be separate surfaces).

The pt field is only defined in the leaves.

By way of example, consider a three dimensional subspace with two components - a three by three grid and a sphere. The internal representation of this subspace is a tree with a depth of three.

The root holds a list of all the points used in the subspace (so, if the grid and the sphere share points, the shared points would not be represented redundantly but would be referenced by index).

The root, in this case, has two children - the first points to the grid component and the second to the sphere component. The grid child has four children of its own - a 3x3 grid has 4 endpoints - and each of these point to a list of four points. To see it another way, the grid (child of the root) holds a list of line components which, when placed one above the next, forms a grid. Each of these line components is a list of points.

Points could be explicitly added to subspaces at any level. A path could be given as an argument to the addPoint() function. It is a list of NonNegativeIntegers and refers, in order, to the n-th child of the current node. For example,

```
addPoint(s,[2,3],p)
```

would add the point p to the subspace s by going to the second child of the root and then the third child of that node. If the path does extend to the full depth of the tree, nodes are automatically added so that the tree is of constant depth down any path. By not specifying the full path, new components could be added - e.g. for s from SubSpace(3,Float)

```
addPoint(s,[],p)
```

would create a new child to the root (a new component in N-space) and extend a path to a leaf of depth 3 that points to the data held in p. The subspace s would now have a new component which has one child which, in turn, has one child (the leaf). The new component is then a point.

— SubSpace.input —

```
)set break resume
)sys rm -f SubSpace.output
)spool SubSpace.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SubSpace
--R
--R SubSpace(n: PositiveInteger,R: Ring)  is a domain constructor
--R Abbreviation for SubSpace is SUBSPACE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SUBSPACE
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean                addPoint2 : (%,Point(R)) -> %
--R birth : % -> %                        children : % -> List(%)
--R coerce : % -> OutputForm              deepCopy : % -> %
```

```
--R extractClosed : % -> Boolean          extractPoint : % -> Point(R)
--R hash : % -> SingleInteger             internal? : % -> Boolean
--R latex : % -> String                   leaf? : % -> Boolean
--R level : % -> NonNegativeInteger       merge : List(%) -> %
--R merge : (%,%) -> %                    new : () -> %
--R parent : % -> %                       pointData : % -> List(Point(R))
--R root? : % -> Boolean                  separate : % -> List(%)
--R shallowCopy : % -> %                  subspace : () -> %
--R ?~=? : (%,%) -> Boolean
--R addPoint : (%,Point(R)) -> NonNegativeInteger
--R addPoint : (%,List(NonNegativeInteger),NonNegativeInteger) -> %
--R addPoint : (%,List(NonNegativeInteger),Point(R)) -> %
--R addPointLast : (%,%,Point(R),NonNegativeInteger) -> %
--R child : (%,NonNegativeInteger) -> %
--R closeComponent : (%,List(NonNegativeInteger),Boolean) -> %
--R defineProperty : (%,List(NonNegativeInteger),SubSpaceComponentProperty) -> %
--R extractIndex : % -> NonNegativeInteger
--R extractProperty : % -> SubSpaceComponentProperty
--R modifyPoint : (%,NonNegativeInteger,Point(R)) -> %
--R modifyPoint : (%,List(NonNegativeInteger),NonNegativeInteger) -> %
--R modifyPoint : (%,List(NonNegativeInteger),Point(R)) -> %
--R numberOfChildren : % -> NonNegativeInteger
--R traverse : (%,List(NonNegativeInteger)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— SubSpace.help —

```
=====================================================================
SubSpace examples
=====================================================================

See Also:
o )show SubSpace
```

———-

20.33.1 SubSpace (SUBSPACE)



See

⇒ "Point" (POINT) 17.24.1 on page 2025
⇒ "SubSpaceComponentProperty" (COMPPROP) 20.34.1 on page 2592

Exports:

addPoint	addPointLast	addPoint2	birth	child
children	closeComponent	coerce	deepCopy	defineProperty
extractClosed	extractIndex	extractPoint	extractProperty	hash
internal?	latex	leaf?	level	merge
merge	modifyPoint	new	numberOfChildren	parent
pointData	root?	separate	shallowCopy	subspace
traverse	? =?	?=?		

— domain SUBSPACE SubSpace —

```
)abbrev domain SUBSPACE SubSpace
++ Author: Mark Botch
++ Description:
++ This domain is not documented

SubSpace(n:PI,R:Ring) : Exports == Implementation where
  I    ==> Integer
  PI   ==> PositiveInteger
  NNI  ==> NonNegativeInteger
  L    ==> List
  B    ==> Boolean
  POINT ==> Point(R)
  PROP ==> SubSpaceComponentProperty()
  S ==> String
  O ==> OutputForm
  empty ==> nil  -- macro to ease conversion to new aggcat.spad

  Exports ==> SetCategory with
    leaf?          : % -> B
        ++ leaf?(x) is not documented
    root?          : % -> B
```

```
    ++ root?(x) is not documented
internal?      : % -> B
    ++ internal?(x) is not documented
new            : () -> %
    ++ new() is not documented
subspace       : () -> %
    ++ subspace() is not documented
birth          : % -> %       -- returns a pointer to the baby
    ++ birth(x) is not documented
child          : (%,NNI) -> %
    ++ child(x,n) is not documented
children       : % -> List %
    ++ children(x) is not documented
numberOfChildren: % -> NNI
    ++ numberOfChildren(x) is not documented
shallowCopy    : % -> %
    ++ shallowCopy(x) is not documented
deepCopy       : % -> %
    ++ deepCopy(x) is not documented
merge          : (%,%) -> %
  ++ merge(s1,s2) the subspaces s1 and s2 into a single subspace.
merge          : List % -> %
  ++ merge(ls) a list of subspaces, ls, into one subspace.
separate       : % -> List %
  ++ separate(s) makes each of the components of the \spadtype{SubSpace},
  ++ s, into a list of separate and distinct subspaces and returns
  ++ the list.
addPoint       : (%,List NNI,POINT) -> %
  ++ addPoint(s,li,p) adds the 4 dimensional point, p, to the 3
  ++ dimensional subspace, s. The list of non negative integers, li,
  ++ dictates the path to follow, or, to look at it another way,
  ++ points to the component in which the point is to be added.  It's
  ++ length should range from 0 to \spad{n - 1} where n is the dimension
  ++ of the subspace. If the length is \spad{n - 1}, then a specific
  ++ lowest level component is being referenced.  If it is less than
  ++ \spad{n - 1}, then some higher level component (0 indicates top
  ++ level component) is being referenced and a component of that level
  ++ with the desired point is created.  The subspace s is returned
  ++ with the additional point.
addPoint2      : (%,POINT) -> %
  ++ addPoint2(s,p) adds the 4 dimensional point, p, to the 3
  ++ dimensional subspace, s.
  ++ The subspace s is returned with the additional point.
addPointLast   : (%,%,POINT, NNI) -> %
  ++ addPointLast(s,s2,li,p) adds the 4 dimensional point, p, to the 3
  ++ dimensional subspace, s. s2 point to the end of the subspace
  ++ s. n is the path in the s2 component.
  ++ The subspace s is returned with the additional point.
modifyPoint    : (%,List NNI,POINT) -> %
  ++ modifyPoint(s,li,p) replaces an existing point in the 3 dimensional
```

```
    ++ subspace, s, with the 4 dimensional point, p.  The list of non
    ++ negative integers, li, dictates the path to follow, or, to look at
    ++ it another way, points to the component in which the existing point
    ++ is to be modified.  An error message occurs if s is empty, otherwise
    ++ the subspace s is returned with the point modification.
  addPoint       : (%,List NNI,NNI) -> %
    ++ addPoint(s,li,i) adds the 4 dimensional point indicated by the
    ++ index location, i, to the 3 dimensional subspace, s. The list of
    ++ non negative integers, li, dictates the path to follow, or, to
    ++ look at it another way, points to the component in which the point
    ++ is to be added.  It's length should range from 0 to \spad{n - 1}
    ++ where n is the dimension of the subspace. If the length is
    ++ \spad{n - 1}, then a specific lowest level component is being
    ++ referenced.  If it is less than \spad{n - 1}, then some higher
    ++ level component (0 indicates top level component) is being
    ++ referenced and a component of that level with the desired point
    ++ is created.  The subspace s is returned with the additional point.
  modifyPoint    : (%,List NNI,NNI) -> %
    ++ modifyPoint(s,li,i) replaces an existing point in the 3 dimensional
    ++ subspace, s, with the 4 dimensional point indicated by the index
    ++ location, i.  The list of non negative integers, li, dictates
    ++ the path to follow, or, to look at it another way, points to the
    ++ component in which the existing point is to be modified.  An error
    ++ message occurs if s is empty, otherwise the subspace s is returned
    ++ with the point modification.
  addPoint       : (%,POINT) -> NNI
    ++ addPoint(s,p) adds the point, p, to the 3 dimensional subspace, s,
    ++ and returns the new total number of points in s.
  modifyPoint    : (%,NNI,POINT) -> %
    ++ modifyPoint(s,ind,p) modifies the point referenced by the index
    ++ location, ind, by replacing it with the point, p in the 3 dimensional
    ++ subspace, s.  An error message occurs if s is empty, otherwise the
    ++ subspace s is returned with the point modification.

  closeComponent : (%,List NNI,B)     -> %
    ++ closeComponent(s,li,b) sets the property of the component in the
    ++ 3 dimensional subspace, s, to be closed if b is true, or open if
    ++ b is false.  The list of non negative integers, li, dictates the
    ++ path to follow, or, to look at it another way, points to the
    ++ component whose closed property is to be set.  The subspace, s,
    ++ is returned with the component property modification.
  defineProperty : (%,List NNI,PROP)  -> %
    ++ defineProperty(s,li,p) defines the component property in the
    ++ 3 dimensional subspace, s, to be that of p, where p is of the
    ++ domain \spadtype{SubSpaceComponentProperty}.  The list of non
    ++ negative integers, li, dictates the path to follow, or, to look
    ++ at it another way, points to the component whose property is
    ++ being defined.  The subspace, s, is returned with the component
    ++ property definition.
  traverse       : (%,List NNI) -> %
```

```
    ++ traverse(s,li) follows the branch list of the 3 dimensional
    ++ subspace, s, along the path dictated by the list of non negative
    ++ integers, li, which points to the component which has been
    ++ traversed to.  The subspace, s, is returned, where s is now
    ++ the subspace pointed to by li.
  extractPoint    : %  -> POINT
    ++ extractPoint(s) returns the point which is given by the current
    ++ index location into the point data field of the 3 dimensional
    ++ subspace s.
  extractIndex    : % -> NNI
    ++ extractIndex(s) returns a non negative integer which is the current
    ++ index of the 3 dimensional subspace s.
  extractClosed   : %  -> B
    ++ extractClosed(s) returns the \spadtype{Boolean} value of the closed
    ++ property for the indicated 3 dimensional subspace s.  If the
    ++ property is closed, \spad{True} is returned, otherwise \spad{False}
    ++ is returned.
  extractProperty : %  -> PROP
    ++ extractProperty(s) returns the property of domain
    ++ \spadtype{SubSpaceComponentProperty} of the indicated 3 dimensional
    ++ subspace s.
  level           : % -> NNI
    ++ level(s) returns a non negative integer which is the current
    ++ level field of the indicated 3 dimensional subspace s.
  parent          : % -> %
    ++ parent(s) returns the subspace which is the parent of the indicated
    ++ 3 dimensional subspace s.  If s is the top level subspace an error
    ++ message is returned.
  pointData       : % -> L POINT
    ++ pointData(s) returns the list of points from the point data field
    ++ of the 3 dimensional subspace s.

Implementation ==> add
  import String()

  Rep := Record(pt:POINT, index:NNI, property:PROP, _
                childrenField:List %, _
                lastChild: List %, _
                levelField:NNI, _
                pointDataField:L POINT, _
                lastPoint: L POINT, _
                noPoints: NNI, _
                noChildren: NNI, _
                parentField:List %) -- needn't be list but...base case?

  TELLWATT : String := "Non-null list: Please inform Stephen Watt"

  leaf? space ==  empty? children space
  root? space == (space.levelField = 0$NNI)
  internal? space == ^(root? space and leaf? space)
```

```
new() ==
  [point(empty())$POINT,0,new()$PROP,empty(),empty(),0,_
                                  empty(),empty(),0,0,empty()]
subspace() == new()

birth momma ==
  baby := new()
  baby.levelField := momma.levelField+1
  baby.parentField := [momma]
  if not empty?(lastKid := momma.lastChild) then
    not empty? rest lastKid => error TELLWATT
  if empty? lastKid
    then
      momma.childrenField := [baby]
      momma.lastChild := momma.childrenField
      momma.noChildren := 1
    else
      setrest_!(lastKid,[baby])
      momma.lastChild := rest lastKid
      momma.noChildren := momma.noChildren + 1
  baby

child(space,num) ==
  space.childrenField.num

children space == space.childrenField
numberOfChildren space == space.noChildren

shallowCopy space ==
  node := new()
  node.pt         := space.pt
  node.index      := space.index
  node.property   := copy(space.property)
  node.levelField := space.levelField
  node.parentField := nil()
  if root? space then
    node.pointDataField := copy(space.pointDataField)
    node.lastPoint := tail(node.pointDataField)
    node.noPoints := space.noPoints
  node

deepCopy space ==
  node := shallowCopy(space)
  leaf? space => node
  for c in children space repeat
    cc := deepCopy c
    cc.parentField := [node]
    node.childrenField := cons(cc,node.childrenField)
  node.childrenField := reverse_!(node.childrenField)
```

```
    node.lastChild := tail node.childrenField
    node

  merge(s1,s2) ==
     ------------------ need to worry about reindexing s2 & parentField
    n1 : Rep := deepCopy s1
    n2 : Rep := deepCopy s2
    n1.childrenField := append(children n1,children n2)
    n1

  merge listOfSpaces ==
     ------------------ need to worry about reindexing & parentField
    empty? listOfSpaces => error "empty list passed as argument to merge"
         -- notice that the properties of the first subspace on the
         -- list are the ones that are inherited...hmmmm...
    space := deepCopy first listOfSpaces
    for s in rest listOfSpaces repeat
         -- because of the initial deepCopy, above, everything is
         -- deepCopied to be consistent...more hmmm...
      space.childrenField := append(space.childrenField,[deepCopy c for c in s.childrenField])
    space

  separate space ==
     ------------------ need to worry about reindexing & parentField
    spaceList := empty()
    for s in space.childrenField repeat
      spc:=shallowCopy space
      spc.childrenField:=[deepCopy s]
      spaceList := cons(spc,spaceList)
    spaceList

  addPoint(space:%,path:List NNI,point:POINT) ==
    if not empty?(lastPt := space.lastPoint) then
      not empty? rest lastPt => error TELLWATT
    if empty? lastPt
      then
        space.pointDataField := [point]
        space.lastPoint := space.pointDataField
      else
        setrest_!(lastPt,[point])
        space.lastPoint := rest lastPt
    space.noPoints := space.noPoints + 1
    which := space.noPoints
    node := space
    depth : NNI := 0
    for i in path repeat
      node := child(node,i)
      depth := depth + 1
    for more in depth..(n-1) repeat
      node := birth node
```

```
    node.pt := point      -- will be obsolete field
    node.index := which
    space

  addPoint2(space:%,point:POINT) ==
    if not empty?(lastPt := space.lastPoint) then
      not empty? rest lastPt => error TELLWATT
    if empty? lastPt
      then
        space.pointDataField := [point]
        space.lastPoint := space.pointDataField
      else
        setrest_!(lastPt,[point])
        space.lastPoint := rest lastPt
    space.noPoints := space.noPoints + 1
    which := space.noPoints
    node := space
    depth : NNI := 0
    node := birth node
    first := node
    for more in 1..n-1 repeat
      node := birth node
    node.pt := point      -- will be obsolete field
    node.index := which
    first

  addPointLast(space:%,node:%, point:POINT, depth:NNI) ==
    if not empty?(lastPt := space.lastPoint) then
      not empty? rest lastPt => error TELLWATT
    if empty? lastPt
      then
        space.pointDataField := [point]
        space.lastPoint := space.pointDataField
      else
        setrest_!(lastPt,[point])
        space.lastPoint := rest lastPt
    space.noPoints := space.noPoints + 1
    which := space.noPoints
    if depth = 2 then node := child(node, 2)
    for more in depth..(n-1) repeat
      node := birth node
    node.pt := point      -- will be obsolete field
    node.index := which
    node -- space

  addPoint(space:%,path:List NNI,which:NNI) ==
    node := space
    depth : NNI := 0
    for i in path repeat
      node := child(node,i)
```

```
      depth := depth + 1
    for more in depth..(n-1) repeat
      node := birth node
    node.pt := space.pointDataField.which   -- will be obsolete field
    node.index := which
    space

  addPoint(space:%,point:POINT) ==
    root? space =>
      if not empty?(lastPt := space.lastPoint) then
        not empty? rest lastPt => error TELLWATT
      if empty? lastPt
        then
          space.pointDataField := [point]
          space.lastPoint := space.pointDataField
        else
          setrest_!(lastPt,[point])
          space.lastPoint := rest lastPt
      space.noPoints := space.noPoints + 1
    error "You need to pass a top level SubSpace (level should be zero)"

  modifyPoint(space:%,path:List NNI,point:POINT) ==
    if not empty?(lastPt := space.lastPoint) then
      not empty? rest lastPt => error TELLWATT
    if empty? lastPt
      then
        space.pointDataField := [point]
        space.lastPoint := space.pointDataField
      else
        setrest_!(lastPt,[point])
        space.lastPoint := rest lastPt
    space.noPoints := space.noPoints + 1
    which := space.noPoints
    node := space
    for i in path repeat
      node := child(node,i)
    node.pt := point       ---------- will be obsolete field
    node.index := which
    space

  modifyPoint(space:%,path:List NNI,which:NNI) ==
    node := space
    for i in path repeat
      node := child(node,i)
    node.pt := space.pointDataField.which ---------- will be obsolete field
    node.index := which
    space

  modifyPoint(space:%,which:NNI,point:POINT) ==
    root? space =>
```

```
    space.pointDataField.which := point
    space
  error "You need to pass a top level SubSpace (level should be zero)"

closeComponent(space,path,val) ==
  node := space
  for i in path repeat
    node := child(node,i)
  close(node.property,val)
  space

defineProperty(space,path,prop) ==
  node := space
  for i in path repeat
    node := child(node,i)
  node.property := prop
  space

traverse(space,path) ==
  for i in path repeat space := child(space,i)
  space

extractPoint space ==
  node := space
  while ^root? node repeat node := parent node
  (node.pointDataField).(space.index)
extractIndex space == space.index
extractClosed space == closed? space.property
extractProperty space == space.property

parent space ==
  empty? space.parentField => error "This is a top level SubSpace - it does not have a paren
  first space.parentField
pointData space == space.pointDataField
level space == space.levelField
s1 = s2 ==
    ------------ extra checks for list of point data
  (leaf? s1 and leaf? s2) =>
    (s1.pt = s2.pt) and (s1.property = s2.property) and (s1.levelField = s2.levelField)
  -- note that the ordering of children is important
  #s1.childrenField ^= #s2.childrenField => false
  and/[c1 = c2 for c1 in s1.childrenField for c2 in s2.childrenField]
   and (s1.property = s2.property) and (s1.levelField = s2.levelField)
coerce(space:%):O ==
  hconcat([n::O,"-Space with depth of "::O,                    _
          (n - space.levelField)::O," and "::O,(s:=(#space.childrenField))::O,  _
          (s=1 => " component"::O;" components"::O)])
```

— **SUBSPACE.dotabb** —

```
"SUBSPACE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SUBSPACE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"SUBSPACE" -> "STRING"
```

———-

20.34 domain COMPPROP SubSpaceComponentProperty

— **SubSpaceComponentProperty.input** —

```
)set break resume
)sys rm -f SubSpaceComponentProperty.output
)spool SubSpaceComponentProperty.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SubSpaceComponentProperty
--R SubSpaceComponentProperty  is a domain constructor
--R Abbreviation for SubSpaceComponentProperty is COMPPROP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for COMPPROP
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               close : (%,Boolean) -> Boolean
--R closed? : % -> Boolean               coerce : % -> OutputForm
--R copy : % -> %                        hash : % -> SingleInteger
--R latex : % -> String                  new : () -> %
--R solid : (%,Boolean) -> Boolean       solid? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```


———-

— **SubSpaceComponentProperty.help** —

```
=======================================================================
SubSpaceComponentProperty examples
=======================================================================

See Also:
o )show SubSpaceComponentProperty
```

20.34.1 SubSpaceComponentProperty (COMPPROP)



See

⇒ “Point” (POINT) 17.24.1 on page 2025
⇒ “SubSpace” (SUBSPACE) 20.33.1 on page 2582

Exports:

close	closed?	coerce	copy	hash
latex	new	solid	solid?	?~=?
?=?				

— domain COMPPROP SubSpaceComponentProperty —

```
)abbrev domain COMPPROP SubSpaceComponentProperty
++ Author: Mark Botch
++ Description:
++ This domain implements some global properties of subspaces.

SubSpaceComponentProperty() : Exports == Implementation where

  O ==> OutputForm
  I    ==> Integer
  PI   ==> PositiveInteger
  NNI  ==> NonNegativeInteger
  L    ==> List
  B    ==> Boolean
```

```
  Exports ==> SetCategory with
    new     : () -> %
        ++ new() is not documented
    closed? : % -> B
        ++ closed?(x) is not documented
    solid?  : % -> B
        ++ solid?(x) is not documented
    close   : (%,B) -> B
        ++ close(x,b) is not documented
    solid   : (%,B) -> B
        ++ solid(x,b) is not documented
    copy    : % -> %
        ++ copy(x) is not documented

  Implementation ==> add
    Rep := Record(closed:B, solid:B)
    closed? p == p.closed
    solid? p == p.solid
    close(p,b) == p.closed := b
    solid(p,b) == p.solid := b
    new() == [false,false]
    copy p ==
      annuderOne := new()
      close(annuderOne,closed? p)
      solid(annuderOne,solid? p)
      annuderOne
    coerce p ==
      hconcat(["Component is "::O,
              (closed? p => ""::O; "not "::O),"closed, "::O, _
              (solid? p => ""::O; "not "::O),"solid"::O ])
```

———-

— COMPPROP.dotabb —

```
"COMPPROP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=COMPPROP"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"COMPPROP" -> "BASTYPE"
"COMPPROP" -> "KOERCE"
```

———-

20.35 domain SUCH SuchThat

— SuchThat.input —

```
)set break resume
)sys rm -f SuchThat.output
)spool SuchThat.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SuchThat
--R SuchThat(S1: SetCategory,S2: SetCategory)  is a domain constructor
--R Abbreviation for SuchThat is SUCH
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SUCH
--R
--R------------------------------ Operations ------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> OutputForm
--R construct : (S1,S2) -> %             hash : % -> SingleInteger
--R latex : % -> String                  lhs : % -> S1
--R rhs : % -> S2                        ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```

———-


— SuchThat.help —

```
=====================================================================
SuchThat examples
=====================================================================

See Also:
o )show SuchThat
```

———-

20.35.1 SuchThat (SUCH)



Exports:

coerce	construct	hash	latex	lhs
rhs	?=?	?~=?		

— **domain SUCH SuchThat** —

```
)abbrev domain SUCH SuchThat
++ Author: Mark Botch
++ Description:
++ This domain implements "such that" forms

SuchThat(S1, S2): Cat == Capsule where
    E ==> OutputForm
    S1, S2: SetCategory

    Cat == SetCategory with
        construct: (S1, S2) -> %
                ++ construct(s,t) makes a form s:t
        lhs: % -> S1
                ++ lhs(f) returns the left side of f
        rhs: % -> S2
                ++ rhs(f) returns the right side of f

    Capsule == add
        Rep := Record(obj: S1, cond: S2)
        construct(o, c) == [o, c]$Record(obj: S1, cond: S2)
        lhs st == st.obj
        rhs st == st.cond
        coerce(w):E == infix("|"::E, w.obj::E, w.cond::E)
```

————-

— **SUCH.dotabb** —

```
"SUCH" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SUCH"]
"BASTYPE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=BASTYPE"]
"KOERCE" [color="#4488FF",href="bookvol10.2.pdf#nameddest=KOERCE"]
"SUCH" -> "BASTYPE"
"SUCH" -> "KOERCE"
```

———-

20.36 domain SWITCH Switch

— Switch.input —

```
)set break resume
)sys rm -f Switch.output
)spool Switch.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Switch
--R
--R Switch  is a domain constructor
--R Abbreviation for Switch is SWITCH
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SWITCH
--R
--R------------------------------ Operations ------------------------------
--R NOT : % -> %                          coerce : Symbol -> %
--R coerce : % -> OutputForm
--R AND : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),swit
--R EQ : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R GE : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R GT : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R LE : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R LT : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R NOT : Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R OR : (Union(I: Expression(Integer),F: Expression(Float),CF: Expression(Complex(Float)),switc
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Switch.help** —

```
====================================================================
Switch examples
====================================================================

See Also:
o )show Switch
```

———-

20.36.1 Switch (SWITCH)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266
⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “FortranProgram” (FORTRAN) 7.18.1 on page 926
⇒ “ThreeDimensionalMatrix” (M3D) 21.7.1 on page 2671
⇒ “SimpleFortranProgram” (SFORT) 20.11.1 on page 2373
⇒ “FortranTemplate” (FTEM) 7.20.1 on page 937
⇒ “FortranExpression” (FEXPR) 7.17.1 on page 917

Exports:
coerce AND EQ GE GT LE LT NOT OR

— **domain SWITCH Switch** —

```
)abbrev domain SWITCH Switch
-- Because of a bug in the compiler:
)bo $noSubsumption:=false

++ Author: Mike Dewar
++ Date Created: April 1991
```

```
++ Date Last Updated: March 1994 30.6.94 Added coercion from Symbol MCD
++ Basic Operations:
++ Related Constructors: FortranProgram, FortranCode, FortranTypes
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain builds representations of boolean expressions for use with
++ the \axiomType{FortranCode} domain.

Switch():public == private where
  EXPR ==> Union(I:Expression Integer,F:Expression Float,
                 CF:Expression Complex Float,switch:%)

  public ==  CoercibleTo OutputForm with
    coerce : Symbol -> $
        ++ coerce(s) is not documented
    LT : (EXPR,EXPR) -> $
      ++ LT(x,y) returns the \axiomType{Switch} expression representing \spad{x<y}.
    GT : (EXPR,EXPR) -> $
      ++ GT(x,y) returns the \axiomType{Switch} expression representing \spad{x>y}.
    LE : (EXPR,EXPR) -> $
      ++ LE(x,y) returns the \axiomType{Switch} expression representing \spad{x<=y}.
    GE : (EXPR,EXPR) -> $
      ++ GE(x,y) returns the \axiomType{Switch} expression representing \spad{x>=y}.
    OR : (EXPR,EXPR) -> $
      ++ OR(x,y) returns the \axiomType{Switch} expression representing \spad{x or y}.
    EQ : (EXPR,EXPR) -> $
      ++ EQ(x,y) returns the \axiomType{Switch} expression representing \spad{x = y}.
    AND : (EXPR,EXPR) -> $
      ++ AND(x,y) returns the \axiomType{Switch} expression representing \spad{x and y}.
    NOT : EXPR -> $
      ++ NOT(x) returns the \axiomType{Switch} expression representing \spad{\~~x}.
    NOT : $ -> $
      ++ NOT(x) returns the \axiomType{Switch} expression representing \spad{\~~x}.

  private == add
    Rep := Record(op:BasicOperator,rands:List EXPR)

    -- Public function definitions

    nullOp : BasicOperator := operator NULL

    coerce(s:%):OutputForm ==
      rat := (s . op)::OutputForm
      ran := [u::OutputForm for u in s.rands]
      (s . op) = nullOp => first ran
      #ran = 1 =>
        prefix(rat,ran)
```

```
      infix(rat,ran)

    coerce(s:Symbol):$ == [nullOp,[[s::Expression(Integer)]$EXPR]$List(EXPR)]$Rep

    NOT(r:EXPR):% ==
      [operator("~"::Symbol),[r]$List(EXPR)]$Rep

    NOT(r:%):% ==
      [operator("~"::Symbol),[[r]$EXPR]$List(EXPR)]$Rep

    LT(r1:EXPR,r2:EXPR):% ==
      [operator("<"::Symbol),[r1,r2]$List(EXPR)]$Rep

    GT(r1:EXPR,r2:EXPR):% ==
      [operator(">"::Symbol),[r1,r2]$List(EXPR)]$Rep

    LE(r1:EXPR,r2:EXPR):% ==
      [operator("<="::Symbol),[r1,r2]$List(EXPR)]$Rep

    GE(r1:EXPR,r2:EXPR):% ==
      [operator(">="::Symbol),[r1,r2]$List(EXPR)]$Rep

    AND(r1:EXPR,r2:EXPR):% ==
      [operator("and"::Symbol),[r1,r2]$List(EXPR)]$Rep

    OR(r1:EXPR,r2:EXPR):% ==
      [operator("or"::Symbol),[r1,r2]$List(EXPR)]$Rep

    EQ(r1:EXPR,r2:EXPR):% ==
      [operator("EQ"::Symbol),[r1,r2]$List(EXPR)]$Rep
```

———-

— SWITCH.dotabb —

```
"SWITCH" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SWITCH"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SWITCH" -> "ALIST"
```

———-

20.37 domain SYMBOL Symbol

— Symbol.input —

```
)set break resume
)sys rm -f Symbol.output
)spool Symbol.output
)set message test on
)set message auto off
)clear all
--S 1 of 24
X: Symbol := 'x
--R
--R
--R   (1)  x
--R                                                    Type: Symbol
--E 1

--S 2 of 24
XX: Symbol := x
--R
--R
--R   (2)  x
--R                                                    Type: Symbol
--E 2

--S 3 of 24
A := 'a
--R
--R
--R   (3)  a
--R                                                 Type: Variable(a)
--E 3

--S 4 of 24
B := b
--R
--R
--R   (4)  b
--R                                                 Type: Variable(b)
--E 4

--S 5 of 24
x**2 + 1
--R
--R
--R         2
--R   (5)  x  + 1
--R                                           Type: Polynomial(Integer)
--E 5

--S 6 of 24
"Hello"::Symbol
--R
```

```
--R
--R   (6)  Hello
--R                                                    Type: Symbol
--E 6

--S 7 of 24
new()$Symbol
--R
--R
--R   (7)  %A
--R                                                    Type: Symbol
--E 7

--S 8 of 24
new()$Symbol
--R
--R
--R   (8)  %B
--R                                                    Type: Symbol
--E 8

--S 9 of 24
new("xyz")$Symbol
--R
--R
--R   (9)  %xyz0
--R                                                    Type: Symbol
--E 9

--S 10 of 24
X[i,j]
--R
--R
--R   (10)  x
--R          i,j
--R                                                    Type: Symbol
--E 10

--S 11 of 24
U := subscript(u, [1,2,1,2])
--R
--R
--R   (11)  u
--R          1,2,1,2
--R                                                    Type: Symbol
--E 11

--S 12 of 24
V := superscript(v, [n])
--R
```

```
--R
--R          n
--R   (12)  v
--R                                                    Type: Symbol
--E 12

--S 13 of 24
P := argscript(p, [t])
--R
--R
--R   (13)  p(t)
--R                                                    Type: Symbol
--E 13

--S 14 of 24
scripted? U
--R
--R
--R   (14)  true
--R                                                    Type: Boolean
--E 14

--S 15 of 24
scripted? X
--R
--R
--R   (15)  false
--R                                                    Type: Boolean
--E 15

--S 16 of 24
string X
--R
--R
--R   (16)  "x"
--R                                                    Type: String
--E 16

--S 17 of 24
name U
--R
--R
--R   (17)  u
--R                                                    Type: Symbol
--E 17

--S 18 of 24
scripts U
--R
--R
```

```
--R   (18)  [sub= [1,2,1,2],sup= [],presup= [],presub= [],args= []]
--IType: Record(sub: List(OutputForm),sup: List(OutputForm),...
--E 18

--S 19 of 24
name X
--R
--R
--R   (19)  x
--R                                                              Type: Symbol
--E 19

--S 20 of 24
scripts X
--R
--R
--R   (20)  [sub= [],sup= [],presup= [],presub= [],args= []]
--IType: Record(sub: List(OutputForm),sup: List(OutputForm),...
--E 20

--S 21 of 24
M := script(Mammoth, [ [i,j],[k,l],[0,1],[2],[u,v,w] ])
--R
--R
--R         0,1       k,l
--R   (21)     Mammoth   (u,v,w)
--R           2       i,j
--R                                                              Type: Symbol
--E 21

--S 22 of 24
scripts M
--R
--R
--R   (22)  [sub= [i,j],sup= [k,l],presup= [0,1],presub= [2],args= [u,v,w]]
--IType: Record(sub: List(OutputForm),sup: List(OutputForm),...
--E 22

--S 23 of 24
N := script(Nut, [ [i,j],[k,l],[0,1] ])
--R
--R
--R         0,1   k,l
--R   (23)     Nut
--R               i,j
--R                                                              Type: Symbol
--E 23

--S 24 of 24
scripts N
```

```
--R
--R
--R   (24)  [sub= [i,j],sup= [k,l],presup= [0,1],presub= [],args= []]
--IType: Record(sub: List(OutputForm),sup: List(OutputForm),...
--E 24
)spool
)lisp (bye)
```

———-

— Symbol.help —

```
=====================================================================
Symbol examples
=====================================================================

Symbols are one of the basic types manipulated by Axiom.  The
Symbol domain provides ways to create symbols of many varieties.

The simplest way to create a symbol is to "single quote" an identifier.

  X: Symbol := 'x
    x
                                    Type: Symbol

This gives the symbol even if x has been assigned a value.  If x has
not been assigned a value, then it is possible to omit the quote.

  XX: Symbol := x
    x
                                    Type: Symbol

Declarations must be used when working with symbols, because otherwise
the interpreter tries to place values in a more specialized type Variable.

  A := 'a
    a
                                    Type: Variable a

  B := b
    b
                                    Type: Variable b

The normal way of entering polynomials uses this fact.

  x**2 + 1
     2
    x  + 1
                                    Type: Polynomial Integer
```

```
Another convenient way to create symbols is to convert a string.
This is useful when the name is to be constructed by a program.

  "Hello"::Symbol
    Hello
                                    Type: Symbol

Sometimes it is necessary to generate new unique symbols, for example,
to name constants of integration.  The expression new() generates a
symbol starting with %.

  new()$Symbol
    %A
                                    Type: Symbol

Successive calls to new produce different symbols.

  new()$Symbol
    %B
                                    Type: Symbol

The expression new("s") produces a symbol starting with %s.

  new("xyz")$Symbol
    %xyz0
                                    Type: Symbol

A symbol can be adorned in various ways.  The most basic thing is
applying a symbol to a list of subscripts.

  X[i,j]
     x
      i,j
                                    Type: Symbol

Somewhat less pretty is to attach subscripts, superscripts or arguments.

  U := subscript(u, [1,2,1,2])
     u
      1,2,1,2
                                    Type: Symbol

  V := superscript(v, [n])
      n
     v
                                    Type: Symbol

  P := argscript(p, [t])
    p(t)
```

```
                                    Type: Symbol
```

It is possible to test whether a symbol has scripts using the scripted? test.

```
  scripted? U
    true
                                    Type: Boolean

  scripted? X
    false
                                    Type: Boolean
```

If a symbol is not scripted, then it may be converted to a string.

```
  string X
    "x"
                                    Type: String
```

The basic parts can always be extracted using the name and scripts operations.

```
  name U
    u
                                    Type: Symbol

  scripts U
    [sub= [1,2,1,2],sup= [],presup= [],presub= [],args= []]
                 Type: Record(sub: List OutputForm,
                              sup: List OutputForm,
                              presup: List OutputForm,
                              presub: List OutputForm,
                              args: List OutputForm)

  name X
    x
                                    Type: Symbol

  scripts X
    [sub= [],sup= [],presup= [],presub= [],args= []]
                 Type: Record(sub: List OutputForm,
                              sup: List OutputForm,
                              presup: List OutputForm,
                              presub: List OutputForm,
                              args: List OutputForm)
```

The most general form is obtained using the script operation. This operation takes an argument which is a list containing, in this order, lists of subscripts, superscripts, presuperscripts, presubscripts and arguments to a symbol.

```
  M := script(Mammoth, [ [i,j],[k,l],[0,1],[2],[u,v,w] ])
```

```
     0,1       k,l
        Mammoth   (u,v,w)
       2       i,j
                                    Type: Symbol

  scripts M
    [sub= [i,j],sup= [k,l],presup= [0,1],presub= [2],args= [u,v,w]]
                  Type: Record(sub: List OutputForm,
                               sup: List OutputForm,
                               presup: List OutputForm,
                               presub: List OutputForm,
                               args: List OutputForm)


If trailing lists of scripts are omitted, they are assumed to be empty.

  N := script(Nut, [ [i,j],[k,l],[0,1] ])
     0,1   k,l
        Nut
           i,j
                                    Type: Symbol

  scripts N
    [sub= [i,j],sup= [k,l],presup= [0,1],presub= [],args= []]
                  Type: Record(sub: List OutputForm,
                               sup: List OutputForm,
                               presup: List OutputForm,
                               presub: List OutputForm,
                               args: List OutputForm)


See Also:
o )show Symbol
```

20.37.1 Symbol (SYMBOL)



Exports:

argscript	coerce	convert	hash	latex
list	max	min	name	new
OMwrite	patternMatch	resetNew	sample	script
scripts	scripted?	string	subscript	superscript
?~=?	?.?	?<?	?<=?	?=?
?>?	?>=?			

— domain SYMBOL Symbol —

```
)abbrev domain SYMBOL Symbol
++ Author: Stephen Watt
++ Date Created: 1986
++ Date Last Updated: 7 Mar 1991, 29 Apr. 1994 (FDLL)
++ Keywords: symbol.
++ Description:
++ Basic and scripted symbols.

Symbol(): Exports == Implementation where
  L ==> List OutputForm
  Scripts ==> Record(sub:L,sup:L,presup:L,presub:L,args:L)

  Exports ==> Join(OrderedSet, ConvertibleTo InputForm, OpenMath,
        ConvertibleTo Symbol,
         ConvertibleTo Pattern Integer, ConvertibleTo Pattern Float,
          PatternMatchable Integer, PatternMatchable Float) with
     new: () -> %
       ++ new() returns a new symbol whose name starts with %.
     new: % -> %
       ++ new(s) returns a new symbol whose name starts with %s.
     resetNew: () -> Void
       ++ resetNew() resets the internals counters that new() and
       ++ new(s) use to return distinct symbols every time.
     coerce: String -> %
       ++ coerce(s) converts the string s to a symbol.
```

```
    name: % -> %
      ++ name(s) returns s without its scripts.
    scripted?: % -> Boolean
      ++ scripted?(s) is true if s has been given any scripts.
    scripts: % -> Scripts
      ++ scripts(s) returns all the scripts of s.
    script: (%, List L) -> %
      ++ script(s, [a,b,c,d,e]) returns s with subscripts a,
      ++ superscripts b, pre-superscripts c, pre-subscripts d,
      ++ and argument-scripts e.  Omitted components are taken to be empty.
      ++ For example, \spad{script(s, [a,b,c])} is equivalent to
      ++ \spad{script(s,[a,b,c,[],[]])}.
    script: (%, Scripts) -> %
      ++ script(s, [a,b,c,d,e]) returns s with subscripts a,
      ++ superscripts b, pre-superscripts c, pre-subscripts d,
      ++ and argument-scripts e.
    subscript: (%, L) -> %
      ++ subscript(s, [a1,...,an]) returns s
      ++ subscripted by \spad{[a1,...,an]}.
    superscript: (%, L) -> %
      ++ superscript(s, [a1,...,an]) returns s
      ++ superscripted by \spad{[a1,...,an]}.
    argscript: (%, L) -> %
      ++ argscript(s, [a1,...,an]) returns s
      ++ arg-scripted by \spad{[a1,...,an]}.
    elt: (%, L) -> %
      ++ elt(s,[a1,...,an]) or s([a1,...,an]) returns s subscripted by \spad{[a1,...,an]}.
    string: % -> String
      ++ string(s) converts the symbol s to a string.
      ++ Error: if the symbol is subscripted.
    list: % -> List %
      ++ list(sy) takes a scripted symbol and produces a list
      ++ of the name followed by the scripts.
    sample: constant -> %
      ++ sample() returns a sample of %

  Implementation ==> add
    count: Reference(Integer) := ref 0
    xcount: AssociationList(%, Integer) := empty()
    istrings:PrimitiveArray(String) :=
                    construct ["0","1","2","3","4","5","6","7","8","9"]
    -- the following 3 strings shall be of empty intersection
    nums:String:="0123456789"
    ALPHAS:String:="ABCDEFGHIJKLMNOPQRSTUVWXYZ"
    alphas:String:="abcdefghijklmnopqrstuvwxyz"

    writeOMSym(dev: OpenMathDevice, x: %): Void ==
      scripted? x =>
        error "Cannot convert a scripted symbol to OpenMath"
      OMputVariable(dev, x pretend Symbol)
```

```
OMwrite(x: %): String ==
  s: String := ""
  sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
  dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
  OMputObject(dev)
  writeOMSym(dev, x)
  OMputEndObject(dev)
  OMclose(dev)
  s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
  s

OMwrite(x: %, wholeObj: Boolean): String ==
  s: String := ""
  sp := OM_-STRINGTOSTRINGPTR(s)$Lisp
  dev: OpenMathDevice := OMopenString(sp pretend String, OMencodingXML)
  if wholeObj then
    OMputObject(dev)
  writeOMSym(dev, x)
  if wholeObj then
    OMputEndObject(dev)
  OMclose(dev)
  s := OM_-STRINGPTRTOSTRING(sp)$Lisp pretend String
  s

OMwrite(dev: OpenMathDevice, x: %): Void ==
  OMputObject(dev)
  writeOMSym(dev, x)
  OMputEndObject(dev)

OMwrite(dev: OpenMathDevice, x: %, wholeObj: Boolean): Void ==
  if wholeObj then
    OMputObject(dev)
  writeOMSym(dev, x)
  if wholeObj then
    OMputEndObject(dev)

hd:String    := "*"
lhd          := #hd
ord0         := ord char("0")$Character

istring  : Integer -> String
syprefix : Scripts -> String
syscripts: Scripts -> L

convert(s:%):InputForm == convert(s pretend Symbol)$InputForm
convert(s:%):Symbol    == s pretend Symbol
coerce(s:String):%     == VALUES(INTERN(s)$Lisp)$Lisp
x = y                  == EQUAL(x,y)$Lisp
x < y                  == GGREATERP(y, x)$Lisp
```

```
coerce(x:%):OutputForm == outputForm(x pretend Symbol)
subscript(sy, lx)      == script(sy, [lx, nil, nil(), nil(), nil()])
elt(sy,lx)             == subscript(sy,lx)
superscript(sy, lx)    == script(sy,[nil(),lx, nil(), nil(), nil()])
argscript(sy, lx)      == script(sy,[nil(),nil(), nil(), nil(), lx])

patternMatch(x:%,p:Pattern Integer,l:PatternMatchResult(Integer,%))==
  (patternMatch(x pretend Symbol, p, l pretend
   PatternMatchResult(Integer, Symbol))$PatternMatchSymbol(Integer))
     pretend PatternMatchResult(Integer, %)

patternMatch(x:%, p:Pattern Float, l:PatternMatchResult(Float, %)) ==
  (patternMatch(x pretend Symbol, p, l pretend
   PatternMatchResult(Float, Symbol))$PatternMatchSymbol(Float))
     pretend PatternMatchResult(Float, %)

convert(x:%):Pattern(Float) ==
  coerce(x pretend Symbol)$Pattern(Float)

convert(x:%):Pattern(Integer) ==
  coerce(x pretend Symbol)$Pattern(Integer)

syprefix sc ==
  ns: List Integer := [#sc.presub, #sc.presup, #sc.sup, #sc.sub]
  while #ns >= 2 and zero? first ns repeat ns := rest ns
  concat concat(concat(hd, istring(#sc.args)),
                            [istring n for n in reverse_! ns])

syscripts sc ==
  all := sc.presub
  all := concat(sc.presup, all)
  all := concat(sc.sup, all)
  all := concat(sc.sub, all)
  concat(all, sc.args)

script(sy: %, ls: List L) ==
  sc: Scripts := [nil(), nil(), nil(), nil(), nil()]
  if not null ls then (sc.sub    := first ls; ls := rest ls)
  if not null ls then (sc.sup    := first ls; ls := rest ls)
  if not null ls then (sc.presup := first ls; ls := rest ls)
  if not null ls then (sc.presub := first ls; ls := rest ls)
  if not null ls then (sc.args   := first ls; ls := rest ls)
  script(sy, sc)

script(sy: %, sc: Scripts) ==
  scripted? sy => error "Cannot add scripts to a scripted symbol"
  (concat(concat(syprefix sc, string name sy)::%::OutputForm,
                                          syscripts sc)) pretend %

string e ==
```

```
      not scripted? e => PNAME(e)$Lisp
      error "Cannot form string from non-atomic symbols."

-- Scripts ==> Record(sub:L,sup:L,presup:L,presub:L,args:L)
    latex e ==
      s : String := (PNAME(name e)$Lisp) pretend String
      if #s > 1 and s.1 ^= char "\" then
        s := concat("\mbox{\it ", concat(s, "}")$String)$String
      not scripted? e => s
      ss : Scripts := scripts e
      lo : List OutputForm := ss.sub
      sc : String
      if not empty? lo then
        sc := "__{"
        while not empty? lo repeat
            sc := concat(sc, latex first lo)$String
            lo := rest lo
            if not empty? lo then sc := concat(sc, ", ")$String
        sc := concat(sc, "}")$String
        s := concat(s, sc)$String
      lo := ss.sup
      if not empty? lo then
        sc := "^{"
        while not empty? lo repeat
            sc := concat(sc, latex first lo)$String
            lo := rest lo
            if not empty? lo then sc := concat(sc, ", ")$String
        sc := concat(sc, "}")$String
        s := concat(s, sc)$String
      lo := ss.presup
      if not empty? lo then
        sc := "{}^{"
        while not empty? lo repeat
            sc := concat(sc, latex first lo)$String
            lo := rest lo
            if not empty? lo then sc := concat(sc, ", ")$String
        sc := concat(sc, "}")$String
        s := concat(sc, s)$String
      lo := ss.presub
      if not empty? lo then
        sc := "{}__{"
        while not empty? lo repeat
            sc := concat(sc, latex first lo)$String
            lo := rest lo
            if not empty? lo then sc := concat(sc, ", ")$String
        sc := concat(sc, "}")$String
        s := concat(sc, s)$String
      lo := ss.args
      if not empty? lo then
        sc := "\left( {"
```

```
      while not empty? lo repeat
          sc := concat(sc, latex first lo)$String
          lo := rest lo
          if not empty? lo then sc := concat(sc, ", ")$String
      sc := concat(sc, "} \right)")$String
      s := concat(s, sc)$String
    s

  anyRadix(n:Integer,s:String):String ==
    ns:String:=""
    repeat
      qr := divide(n,#s)
      n  := qr.quotient
      ns := concat(s.(qr.remainder+minIndex s),ns)
      if zero?(n) then return ns

  new() ==
    sym := anyRadix(count()::Integer,ALPHAS)
    count() := count() + 1
    concat("%",sym)::%

  new x ==
    n:Integer :=
      (u := search(x, xcount)) case "failed" => 0
      inc(u::Integer)
    xcount(x) := n
    xx :=
      not scripted? x => string x
      string name x
    xx := concat("%",xx)
    xx :=
      (position(xx.maxIndex(xx),nums)>=minIndex(nums)) =>
        concat(xx, anyRadix(n,alphas))
      concat(xx, anyRadix(n,nums))
    not scripted? x => xx::%
    script(xx::%,scripts x)

  resetNew() ==
    count() := 0
    for k in keys xcount repeat remove_!(k, xcount)
    void

  scripted? sy ==
    not ATOM(sy)$Lisp

  name sy ==
    not scripted? sy => sy
    str := string first list sy
    for i in lhd+1..#str repeat
      not digit?(str.i) => return((str.(i..#str))::%)
```

```
      error "Improper scripted symbol"

    scripts sy ==
      not scripted? sy => [nil(), nil(), nil(), nil(), nil()]
      nscripts: List NonNegativeInteger := [0, 0, 0, 0, 0]
      lscripts: List L := [nil(), nil(), nil(), nil(), nil()]
      str  := string first list sy
      nstr := #str
      m := minIndex nscripts
      for i in m.. for j in lhd+1..nstr while digit?(str.j) repeat
          nscripts.i := (ord(str.j) - ord0)::NonNegativeInteger
      -- Put the number of function scripts at the end.
      nscripts := concat(rest nscripts, first nscripts)
      allscripts := rest list sy
      m := minIndex lscripts
      for i in m.. for n in nscripts repeat
        #allscripts < n => error "Improper script count in symbol"
        lscripts.i := [a::OutputForm for a in first(allscripts, n)]
        allscripts := rest(allscripts, n)
      [lscripts.m, lscripts.(m+1), lscripts.(m+2),
                                       lscripts.(m+3), lscripts.(m+4)]

    istring n ==
      n > 9 => error "Can have at most 9 scripts of each kind"
      istrings.(n + minIndex istrings)

    list sy ==
      not scripted? sy =>
         error "Cannot convert a symbol to a list if it is not subscripted"
      sy pretend List(%)

    sample() == "aSymbol"::%
```

———-

— SYMBOL.dotabb —

```
"SYMBOL" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SYMBOL",
          shape=ellipse]
"STRICAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=STRICAT"]
"SYMBOL" -> "STRICAT"
```

———-

20.38 domain SYMTAB SymbolTable

— SymbolTable.input —

```
)set break resume
)sys rm -f SymbolTable.output
)spool SymbolTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SymbolTable
--R
--R SymbolTable  is a domain constructor
--R Abbreviation for SymbolTable is SYMTAB
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SYMTAB
--R
--R------------------------------ Operations --------------------------------
--R coerce : % -> OutputForm              empty : () -> %
--R externalList : % -> List(Symbol)      newTypeLists : % -> SExpression
--R parametersOf : % -> List(Symbol)      printTypes : % -> Void
--R coerce : % -> Table(Symbol,FortranType)
--R declare! : (Symbol,FortranType,%) -> FortranType
--R declare! : (List(Symbol),FortranType,%) -> FortranType
--R fortranTypeOf : (Symbol,%) -> FortranType
--R symbolTable : List(Record(key: Symbol,entry: FortranType)) -> %
--R typeList : (FortranScalarType,%) -> List(Union(name: Symbol,bounds: List(Union(S: Symbol,P: Polynomial(
--R typeLists : % -> List(List(Union(name: Symbol,bounds: List(Union(S: Symbol,P: Polynomial(Integer))))))
--R
--E 1

)spool
)lisp (bye)
```


— SymbolTable.help —

```
=====================================================================
SymbolTable examples
=====================================================================

See Also:
o )show SymbolTable
```

———-

20.38.1 SymbolTable (SYMTAB)



See

⇒ “FortranScalarType” (FST) 7.19.1 on page 932
⇒ “FortranType” (FT) 7.21.1 on page 941
⇒ “TheSymbolTable” (SYMS) 21.6.1 on page 2665

Exports:

coerce	declare!	empty	externalList	fortranTypeOf
newTypeLists	parametersOf	printTypes	symbolTable	typeList
typeLists				

— domain SYMTAB SymbolTable —

```
)abbrev domain SYMTAB SymbolTable
++ Author: Mike Dewar
++ Date Created:  October 1992
++ Date Last Updated: 12 July 1994
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Create and manipulate a symbol table for generated FORTRAN code

SymbolTable() : exports == implementation where

  T   ==> Union(S:Symbol,P:Polynomial Integer)
  TL1 ==> List T
  TU  ==> Union(name:Symbol,bounds:TL1)
  TL  ==> List TU
  SEX ==> SExpression
```

```
OFORM ==> OutputForm
L   ==> List
FSTU ==> Union(fst:FortranScalarType,void:"void")

exports ==> CoercibleTo OutputForm with
  coerce : $ -> Table(Symbol,FortranType)
    ++ coerce(x) returns a table view of x
  empty  : () -> $
    ++ empty() returns a new, empty symbol table
  declare! : (L Symbol,FortranType,$) -> FortranType
    ++ declare!(l,t,tab) creates new entrys in tab, declaring each of l
    ++ to be of type t
  declare! : (Symbol,FortranType,$) -> FortranType
    ++ declare!(u,t,tab) creates a new entry in tab, declaring u to be of
    ++ type t
  fortranTypeOf : (Symbol,$) -> FortranType
    ++ fortranTypeOf(u,tab) returns the type of u in tab
  parametersOf: $ -> L Symbol
    ++ parametersOf(tab) returns a list of all the symbols declared in tab
  typeList : (FortranScalarType,$) -> TL
    ++ typeList(t,tab) returns a list of all the objects of type t in tab
  externalList : $ -> L Symbol
    ++ externalList(tab) returns a list of all the external symbols in tab
  typeLists : $ -> L TL
    ++ typeLists(tab) returns a list of lists of types of objects in tab
  newTypeLists : $ -> SEX
    ++ newTypeLists(x) is not documented
  printTypes: $ -> Void
    ++ printTypes(tab) produces FORTRAN type declarations from tab, on the
    ++ current FORTRAN output stream
  symbolTable: L Record(key:Symbol,entry:FortranType) -> $
    ++ symbolTable(l) creates a symbol table from the elements of l.

implementation ==> add

  Rep := Table(Symbol,FortranType)

  coerce(t:$):OFORM ==
    coerce(t)$Rep

  coerce(t:$):Table(Symbol,FortranType) ==
    t pretend Table(Symbol,FortranType)

  symbolTable(l:L Record(key:Symbol,entry:FortranType)):$ ==
    table(l)$Rep

  empty():$ ==
    empty()$Rep

  parametersOf(tab:$):L(Symbol) ==
```

```
  keys(tab)

declare!(name:Symbol,type:FortranType,tab:$):FortranType ==
  setelt(tab,name,type)$Rep
  type

declare!(names:L Symbol,type:FortranType,tab:$):FortranType ==
  for name in names repeat setelt(tab,name,type)$Rep
  type

fortranTypeOf(u:Symbol,tab:$):FortranType ==
  elt(tab,u)$Rep

externalList(tab:$):L(Symbol) ==
 [u for u in keys(tab) | external? fortranTypeOf(u,tab)]

typeList(type:FortranScalarType,tab:$):TL ==
  scalarList := []@TL
  arrayList  := []@TL
  for u in keys(tab)$Rep repeat
    uType : FortranType := fortranTypeOf(u,tab)
    sType : FSTU := scalarTypeOf(uType)
    if (sType case fst and (sType.fst)=type) then
      uDim : TL1 := [[v]$T for v in dimensionsOf(uType)]
      if empty? uDim then
        scalarList := cons([u]$TU,scalarList)
      else
        arrayList := cons([cons([u],uDim)$TL1]$TU,arrayList)
  -- Scalars come first in case they are integers which are later
  -- used as an array dimension.
  append(scalarList,arrayList)

typeList2(type:FortranScalarType,tab:$):TL ==
  tl := []@TL
  symbolType : Symbol := coerce(type)$FortranScalarType
  for u in keys(tab)$Rep repeat
    uType : FortranType := fortranTypeOf(u,tab)
    sType : FSTU := scalarTypeOf(uType)
    if (sType case fst and (sType.fst)=type) then
      uDim : TL1 := [[v]$T for v in dimensionsOf(uType)]
      tl := if empty? uDim then cons([u]$TU,tl)
            else cons([cons([u],uDim)$TL1]$TU,tl)
  empty? tl => tl
  cons([symbolType]$TU,tl)

updateList(sType:SEX,name:SEX,lDims:SEX,tl:SEX):SEX ==
  l : SEX := ASSOC(sType,tl)$Lisp
  entry : SEX := if null?(lDims) then name else CONS(name,lDims)$Lisp
  null?(l) => CONS([sType,entry]$Lisp,tl)$Lisp
  RPLACD(l,CONS(entry,cdr l)$Lisp)$Lisp
```

```
    tl

  newTypeLists(tab:$):SEX ==
    tl := []$Lisp
    for u in keys(tab)$Rep repeat
      uType : FortranType := fortranTypeOf(u,tab)
      sType : FSTU := scalarTypeOf(uType)
      dims  : L Polynomial Integer := dimensionsOf uType
      lDims : L SEX := [convert(convert(v)@InputForm)@SEX for v in dims]
      lType : SEX := if sType case void
        then convert(void::Symbol)@SEX
        else coerce(sType.fst)$FortranScalarType
      tl := updateList(lType,convert(u)@SEX,convert(lDims)@SEX,tl)
    tl

  typeLists(tab:$):L(TL) ==
    fortranTypes := ["real"::FortranScalarType, _
           "double precision"::FortranScalarType, _
           "integer"::FortranScalarType, _
           "complex"::FortranScalarType, _
           "logical"::FortranScalarType, _
           "character"::FortranScalarType]@L(FortranScalarType)
    tl := []@L TL
    for u in fortranTypes repeat
      types : TL := typeList2(u,tab)
      if (not null types) then
        tl := cons(types,tl)$(L TL)
    tl

  oForm2(w:T):OFORM ==
    w case S => w.S::OFORM
    w case P => w.P::OFORM

  oForm(v:TU):OFORM ==
    v case name => v.name::OFORM
    v case bounds =>
      ll : L OFORM := [oForm2(uu) for uu in v.bounds]
      ll :: OFORM

  outForm(t:TL):L OFORM ==
   [oForm(u) for u in t]

  printTypes(tab:$):Void ==
    -- It is important that INTEGER is the first element of this
    -- list since INTEGER symbols used in type declarations must
    -- be declared in advance.
    ft := ["integer"::FortranScalarType, _
           "real"::FortranScalarType, _
           "double precision"::FortranScalarType, _
           "complex"::FortranScalarType, _
```

```
            "logical"::FortranScalarType, _
            "character"::FortranScalarType]@L(FortranScalarType)
      for ty in ft repeat
        tl : TL := typeList(ty,tab)
        otl : L OFORM := outForm(tl)
        fortFormatTypes(ty::OFORM,otl)$Lisp
      el : L OFORM := [u::OFORM for u in externalList(tab)]
      fortFormatTypes("EXTERNAL"::OFORM,el)$Lisp
      void()$Void
```

———-

— SYMTAB.dotabb —

```
"SYMTAB" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SYMTAB"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SYMTAB" -> "ALIST"
```

———-

20.39 domain SYMPOLY SymmetricPolynomial

— SymmetricPolynomial.input —

```
)set break resume
)sys rm -f SymmetricPolynomial.output
)spool SymmetricPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show SymmetricPolynomial
--R
--R SymmetricPolynomial(R: Ring)  is a domain constructor
--R Abbreviation for SymmetricPolynomial is SYMPOLY
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SYMPOLY
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                    ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                    ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %      ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                    ?-? : (%,%) -> %
```

```
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       coefficient : (%,Partition) -> R
--R coefficients : % -> List(R)          coerce : R -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R degree : % -> Partition              ground : % -> R
--R ground? : % -> Boolean               hash : % -> SingleInteger
--R latex : % -> String                  leadingCoefficient : % -> R
--R leadingMonomial : % -> %             map : ((R -> R),%) -> %
--R minimumDegree : % -> Partition       monomial : (R,Partition) -> %
--R monomial? : % -> Boolean             one? : % -> Boolean
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R retract : % -> R                     sample : () -> %
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if R has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,R) -> % if R has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R associates? : (%,%) -> Boolean if R has INTDOM
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if R has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if R has CHARNZ
--R coerce : Fraction(Integer) -> % if R has ALGEBRA(FRAC(INT)) or R has RETRACT(FRAC(INT))
--R coerce : % -> % if R has INTDOM
--R content : % -> R if R has GCDDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R exquo : (%,%) -> Union(%,"failed") if R has INTDOM
--R fmecg : (%,Partition,R,%) -> % if Partition has CABMON and R has INTDOM
--R mapExponents : ((Partition -> Partition),%) -> %
--R numberOfMonomials : % -> NonNegativeInteger
--R pomopo! : (%,R,Partition,%) -> %
--R primitivePart : % -> % if R has GCDDOM
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unit? : % -> Boolean if R has INTDOM
--R unitCanonical : % -> % if R has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if R has INTDOM
--R
--E 1

)spool
)lisp (bye)
```


— SymmetricPolynomial.help —

```
==========================================================================
SymmetricPolynomial examples
==========================================================================

See Also:
o )show SymmetricPolynomial
```

———-

20.39.1 SymmetricPolynomial (SYMPOLY)



See

⇒ “Partition” (PRTITION) 17.9.1 on page 1889

Exports:

0	1	associates?	binomThmExpt
characteristic	charthRoot	coefficient	
coefficients	coerce	content	degree
exquo	exquo	fmecg	ground
ground?	hash	latex	leadingCoefficient
leadingMonomial	map	mapExponents	minimumDegree
monomial	monomial?	numberOfMonomials	one?
pomopo!	primitivePart	recip	reductum
retract	retractIfCan	sample	subtractIfCan
unit?	unitCanonical	unitNormal	zero?
?~=?	?**?	?/?	?^?
?*?	?+?	?-?	-?
?=?			

— domain SYMPOLY SymmetricPolynomial —

```
)abbrev domain SYMPOLY SymmetricPolynomial
```

```
++ Author: Mark Botch
++ Description:
++ This domain implements symmetric polynomial

SymmetricPolynomial(R:Ring) == PolynomialRing(R,Partition) add
       Term:=  Record(k:Partition,c:R)
       Rep:=  List Term

-- override PR implementation because coeff. arithmetic too expensive (??)

       if R has EntireRing then
         (p1:%) * (p2:%)  ==
            null p1 => 0
            null p2 => 0
            zero?(p1.first.k) => p1.first.c * p2
--            one? p2 => p1
            (p2 = 1) => p1
            +/[[[t1.k+t2.k,t1.c*t2.c]$Term for t2 in p2]
                   for t1 in reverse(p1)]
                   -- This 'reverse' is an efficiency improvement:
                   -- reduces both time and space [Abbott/Bradford/Davenport]
        else
         (p1:%) * (p2:%)  ==
            null p1 => 0
            null p2 => 0
            zero?(p1.first.k) => p1.first.c * p2
--            one? p2 => p1
            (p2 = 1) => p1
            +/[[[t1.k+t2.k,r]$Term for t2 in p2 | (r:=t1.c*t2.c) ^= 0]
                 for t1 in reverse(p1)]
                  -- This 'reverse' is an efficiency improvement:
                  -- reduces both time and space [Abbott/Bradford/Davenport]
```

———-

— SYMPOLY.dotabb —

```
"SYMPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SYMPOLY"]
"FAMR" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FAMR"]
"SYMPOLY" -> "FAMR"
```

———-

Chapter 21

Chapter T

21.1 domain TABLE Table

— Table.input —

```
)set break resume
)sys rm -f Table.output
)spool Table.output
)set message test on
)set message auto off
)clear all
--S 1 of 18
t: Table(Polynomial Integer, String) := table()
--R
--R
--R   (1)  table()
--R                                      Type: Table(Polynomial(Integer),String)
--E 1

--S 2 of 18
setelt(t, x**2 - 1, "Easy to factor")
--R
--R
--R   (2)  "Easy to factor"
--R                                                              Type: String
--E 2

--S 3 of 18
t(x**3 + 1) := "Harder to factor"
--R
--R
--R   (3)  "Harder to factor"
```

```
--R                                                                Type: String
--E 3

--S 4 of 18
t(x) := "The easiest to factor"
--R
--R
--R   (4)  "The easiest to factor"
--R                                                                Type: String
--E 4

--S 5 of 18
elt(t, x)
--R
--R
--R   (5)  "The easiest to factor"
--R                                                                Type: String
--E 5

--S 6 of 18
t.x
--R
--R
--R   (6)  "The easiest to factor"
--R                                                                Type: String
--E 6

--S 7 of 18
t x
--R
--R
--R   (7)  "The easiest to factor"
--R                                                                Type: String
--E 7

--S 8 of 18
t.(x**2 - 1)
--R
--R
--R   (8)  "Easy to factor"
--R                                                                Type: String
--E 8

--S 9 of 18
t (x**3 + 1)
--R
--R
--R   (9)  "Harder to factor"
--R                                                                Type: String
--E 9
```

```
--S 10 of 18
keys t
--R
--R
--R             3      2
--R   (10)  [x,x  + 1,x  - 1]
--R                                                Type: List(Polynomial(Integer))
--E 10

--S 11 of 18
search(x, t)
--R
--R
--R   (11)  "The easiest to factor"
--R                                                  Type: Union(String,...)
--E 11

--S 12 of 18
search(x**2, t)
--R
--R
--R   (12)  "failed"
--R                                                Type: Union("failed",...)
--E 12

--S 13 of 18
search(x**2, t) case "failed"
--R
--R
--R   (13)  true
--R                                                             Type: Boolean
--E 13

--S 14 of 18
remove!(x**2-1, t)
--R
--R
--R   (14)  "Easy to factor"
--R                                                  Type: Union(String,...)
--E 14

--S 15 of 18
remove!(x-1, t)
--R
--R
--R   (15)  "failed"
--R                                                Type: Union("failed",...)
--E 15
```

```
--S 16 of 18
#t
--R
--R
--R   (16)  2
--R                                                    Type: PositiveInteger
--E 16

--S 17 of 18
members t
--R
--R
--R   (17)  ["The easiest to factor","Harder to factor"]
--R                                                       Type: List(String)
--E 17

--S 18 of 18
count(s: String +-> prefix?("Hard", s), t)
--R
--R
--R   (18)  1
--R                                                    Type: PositiveInteger
--E 18
)spool
)lisp (bye)
```

———-

— Table.help —

```
=====================================================================
Table examples
=====================================================================

The Table constructor provides a general structure for associative
storage.  This type provides hash tables in which data objects can be
saved according to keys of any type.  For a given table, specific
types must be chosen for the keys and entries.

In this example the keys to the table are polynomials with integer
coefficients.  The entries in the table are strings.

  t: Table(Polynomial Integer, String) := table()
    table()
                               Type: Table(Polynomial Integer,String)

To save an entry in the table, the setelt operation is used.  This can
be called directly, giving the table a key and an entry.
```

```
  setelt(t, x**2 - 1, "Easy to factor")
    "Easy to factor"
                                Type: String
```

Alternatively, you can use assignment syntax.

```
  t(x**3 + 1) := "Harder to factor"
    "Harder to factor"
                                Type: String

  t(x) := "The easiest to factor"
    "The easiest to factor"
                                Type: String
```

Entries are retrieved from the table by calling the elt operation.

```
  elt(t, x)
    "The easiest to factor"
                                Type: String
```

This operation is called when a table is "applied" to a key using this
or the following syntax.

```
  t.x
    "The easiest to factor"
                                Type: String

  t x
    "The easiest to factor"
                                Type: String
```

Parentheses are used only for grouping. They are needed if the key is
an infixed expression.

```
  t.(x**2 - 1)
    "Easy to factor"
                                Type: String
```

Note that the elt operation is used only when the key is known to be
in the table, otherwise an error is generated.

```
  t (x**3 + 1)
    "Harder to factor"
                                Type: String
```

You can get a list of all the keys to a table using the keys operation.

```
  keys t
        3      2
    [x,x  + 1,x  - 1]
```

```
                                Type: List Polynomial Integer
```

If you wish to test whether a key is in a table, the search operation is used. This operation returns either an entry or "failed".

```
  search(x, t)
    "The easiest to factor"
                                Type: Union(String,...)

  search(x**2, t)
    "failed"
                                Type: Union("failed",...)
```

The return type is a union so the success of the search can be tested using case.

```
  search(x**2, t) case "failed"
    true
                                Type: Boolean
```

The remove operation is used to delete values from a table.

```
  remove!(x**2-1, t)
    "Easy to factor"
                                Type: Union(String,...)
```

If an entry exists under the key, then it is returned. Otherwise remove returns "failed".

```
  remove!(x-1, t)
    "failed"
                                Type: Union("failed",...)
```

The number of key-entry pairs can be found using the # operation.

```
  #t
    2
                                Type: PositiveInteger
```

Just as keys returns a list of keys to the table, a list of all the entries can be obtained using the members operation.

```
  members t
   (17)  ["The easiest to factor","Harder to factor"]
                                Type: List String
```

A number of useful operations take functions and map them on to the table to compute the result. Here we count the entries which have "Hard" as a prefix.


```
  count(s: String +-> prefix?("Hard", s), t)
    1
                                Type: PositiveInteger

Other table types are provided to support various needs.
  o AssociationList gives a list with a table view. This allows new
    entries to be appended onto the front of the list to cover up old
    entries. This is useful when table entries need to be stacked or when
    frequent list traversals are required.
  o EqTable gives tables in which keys are considered equal only when
    they are in fact the same instance of a structure.
  o StringTable should be used when the keys are known to be strings.
  o SparseTable provides tables with default entries, so lookup never fails.
    The GeneralSparseTable constructor can be used to make any table type
    behave this way.
  o KeyedAccessFile allows values to be saved in a file, accessed as a table.

See Also:
o )help AssociationList
o )help EqTable
o )help StringTable
o )help SparseTable
o )help GeneralSparseTable
o )help KeyedAccessFile
o )show Table
```

———-

21.1.1 Table (TABLE)



See

⇒ “HashTable” (HASHTBL) 9.1.1 on page 1089
⇒ “InnerTable” (INTABL) 10.27.1 on page 1303
⇒ “EqTable” (EQTBL) 6.2.1 on page 669

⇒ "StringTable" (STRTBL) 20.32.1 on page 2578
⇒ "GeneralSparseTable" (GSTBL) 8.5.1 on page 1048
⇒ "SparseTable" (STBL) 20.16.1 on page 2418

Exports:

any?	bag	coerce	construct	convert
copy	count	dictionary	elt	empty
empty?	entries	entry?	eq?	eval
eval	every?	extract!	fill!	find
first	hash	index?	indices	insert!
inspect	key?	keys	latex	less?
map	map	map!	maxIndex	member?
members	minIndex	more?	parts	qelt
qsetelt!	reduce	remove	remove!	removeDuplicates
sample	search	select	select!	setelt
size?	swap!	table	#?	?=?
?~=?	?.?			

— domain TABLE Table —

```
)abbrev domain TABLE Table
++ Author: Stephen M. Watt, Barry Trager
++ Date Created: 1985
++ Date Last Updated: Sept 15, 1992
++ Basic Operations:
++ Related Domains: HashTable, EqTable, StringTable, AssociationList
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ This is the general purpose table type.
++ The keys are hashed to look up the entries.
++ This creates a \spadtype{HashTable} if equal for the Key
++ domain is consistent with Lisp EQUAL otherwise an
++ \spadtype{AssociationList}

Table(Key: SetCategory, Entry: SetCategory):Exports == Implementation where
    Exports ==> TableAggregate(Key, Entry) with
                    finiteAggregate

    Implementation ==> InnerTable(Key, Entry,
        if hashable(Key)$Lisp then HashTable(Key, Entry, "UEQUAL")
          else AssociationList(Key, Entry))
```

— **TABLE.dotabb** —

```
"TABLE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TABLE"]
"TBAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TBAGG"]
"TABLE" -> "TBAGG"
```

———-

21.2 domain TABLEAU Tableau

— **Tableau.input** —

```
)set break resume
)sys rm -f Tableau.output
)spool Tableau.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Tableau
--R
--R Tableau(S: SetCategory)  is a domain constructor
--R Abbreviation for Tableau is TABLEAU
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for TABLEAU
--R
--R------------------------------ Operations --------------------------------
--R coerce : % -> OutputForm              listOfLists : % -> List(List(S))
--R tableau : List(List(S)) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Tableau.help** —

```
=======================================================================
Tableau examples
=======================================================================

See Also:
```

```
o )show Tableau
```

21.2.1 Tableau (TABLEAU)



Exports:
coerce listOfLists tableau

— domain TABLEAU Tableau —

```
)abbrev domain TABLEAU Tableau
++ Author: William H. Burge
++ Date Created: 1987
++ Date Last Updated: 23 Sept 1991
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords: Young tableau
++ References:
++ Description:
++ The tableau domain is for printing Young tableaux, and
++ coercions to and from List List S where S is a set.

Tableau(S:SetCategory):Exports == Implementation where
  L   ==> List
  I   ==> Integer
  NNI ==> NonNegativeInteger
  OUT ==> OutputForm
  V   ==> Vector
  fm==>formMatrix$PrintableForm()
  Exports ==>  with
    tableau : L L S -> %
```

```
      ++ tableau(ll) converts a list of lists ll to a tableau.
    listOfLists : % -> L L S
      ++ listOfLists t converts a tableau t to a list of lists.
    coerce : % -> OUT
      ++ coerce(t) converts a tableau t to an output form.
  Implementation ==> add

    Rep := L L S

    tableau(lls:(L L S)) == lls pretend %
    listOfLists(x:%):(L L S) == x pretend (L L S)
    makeupv : (NNI,L S) -> L OUT
    makeupv(n,ls)==
        v:=new(n,message " ")$(List OUT)
        for i in 1..#ls for s in  ls repeat v.i:=box(s::OUT)
        v
    maketab : L L S -> OUT
    maketab lls ==
      ll :  L OUT :=
        empty? lls => [[empty()]]
        sz:NNI:=# first lls
        [blankSeparate makeupv(sz,i) for i in lls]
      pile ll

    coerce(x:%):OUT == maketab listOfLists x
```

———-

— TABLEAU.dotabb —

```
"TABLEAU" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TABLEAU"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"TABLEAU" -> "FLAGG"
```

———-

21.3 domain TS TaylorSeries

— TaylorSeries.input —

```
)set break resume
)sys rm -f TaylorSeries.output
)spool TaylorSeries.output
)set message test on
```

```
)set message auto off
)clear all

--S 1 of 1
)show TaylorSeries
--R
--R TaylorSeries(Coef: Ring)  is a domain constructor
--R Abbreviation for TaylorSeries is TS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for TS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,Coef) -> %                  ?*? : (Coef,%) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R D : (%,List(Symbol)) -> %            D : (%,Symbol) -> %
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       coerce : Polynomial(Coef) -> %
--R coerce : Symbol -> %                 coerce : Integer -> %
--R coerce : % -> OutputForm             complete : % -> %
--R differentiate : (%,Symbol) -> %      eval : (%,%,%) -> %
--R eval : (%,Equation(%)) -> %          eval : (%,Symbol,%) -> %
--R hash : % -> SingleInteger            latex : % -> String
--R leadingCoefficient : % -> Coef       leadingMonomial : % -> %
--R map : ((Coef -> Coef),%) -> %        monomial? : % -> Boolean
--R one? : % -> Boolean                  pole? : % -> Boolean
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R sample : () -> %                     variables : % -> List(Symbol)
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> %
--R D : (%,Symbol,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,NonNegativeInteger) -> Polynomial(Coef)
--R coefficient : (%,List(Symbol),List(NonNegativeInteger)) -> %
--R coefficient : (%,Symbol,NonNegativeInteger) -> %
--R coefficient : (%,IndexedExponents(Symbol)) -> Coef
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R coerce : % -> % if Coef has INTDOM
--R coerce : Coef -> % if Coef has COMRING
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R degree : % -> IndexedExponents(Symbol)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> %
--R differentiate : (%,Symbol,NonNegativeInteger) -> %
--R differentiate : (%,List(Symbol)) -> %
--R eval : (%,List(%),List(%)) -> %
--R eval : (%,List(Equation(%))) -> %
--R eval : (%,List(Symbol),List(%)) -> %
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,NonNegativeInteger) -> %
--R fintegrate : ((() -> %),Symbol,Coef) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol,Coef) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has ALGEBRA(FRAC(INT))
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(Symbol),List(NonNegativeInteger)) -> %
--R monomial : (%,Symbol,NonNegativeInteger) -> %
--R monomial : (Coef,IndexedExponents(Symbol)) -> %
--R monomial : (%,Symbol,IndexedExponents(Symbol)) -> %
--R monomial : (%,List(Symbol),List(IndexedExponents(Symbol))) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,Symbol,NonNegativeInteger) -> NonNegativeInteger
--R order : (%,Symbol) -> NonNegativeInteger
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R polynomial : (%,NonNegativeInteger,NonNegativeInteger) -> Polynomial(Coef)
--R polynomial : (%,NonNegativeInteger) -> Polynomial(Coef)
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R subtractIfCan : (%,%) -> Union(%,"failed")
```

```
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R
--E 1

)spool
)lisp (bye)
```

———-


— **TaylorSeries.help** —

```
=====================================================================
TaylorSeries examples
=====================================================================

See Also:
o )show TaylorSeries
```

———-

21.3.1 TaylorSeries (TS)



See

⇒ “SparseMultivariateTaylorSeries” (SMTS) 20.15.1 on page 2408

Exports:

0	1	acos	acosh	acot
acoth	acsc	acsch	asec	asech
asin	asinh	associates?	atan	atanh
characteristic	charthRoot	coefficient	coerce	complete
cos	cosh	cot	coth	csc
csch	D	degree	differentiate	eval
exp	exquo	extend	fintegrate	hash
integrate	latex	leadingCoefficient	leadingMonomial	log
map	monomial	monomial?	nthRoot	one?
order	pi	pole?	polynomial	recip
reductum	sample	sec	sech	sin
sinh	sqrt	subtractIfCan	tan	tanh
unit?	unitCanonical	unitNormal	variables	zero?
?*?	?**?	?+?	?-?	-?
?=?	?^?	?~=?	?/?	

— domain TS TaylorSeries —

```
)abbrev domain TS TaylorSeries
++ Authors: Burge, Watt, Williamson
++ Date Created: 15 August 1988
++ Date Last Updated: 18 May 1991
++ Basic Operations:
++ Related Domains: SparseMultivariateTaylorSeries
++ Also See: UnivariateTaylorSeries
++ AMS Classifications:
++ Keywords: multivariate, Taylor, series
++ Examples:
++ References:
++ Description:
++ \spadtype{TaylorSeries} is a general multivariate Taylor series domain
++ over the ring Coef and with variables of type Symbol.

TaylorSeries(Coef): Exports == Implementation where
  Coef  : Ring
  L   ==> List
  NNI ==> NonNegativeInteger
  SMP ==> Polynomial Coef
  StS ==> Stream SMP

  Exports ==> MultivariateTaylorSeriesCategory(Coef,Symbol) with
    coefficient: (%,NNI) -> SMP
      ++\spad{coefficient(s, n)} gives the terms of total degree n.
    coerce: Symbol -> %
      ++\spad{coerce(s)} converts a variable to a Taylor series
    coerce: SMP -> %
      ++\spad{coerce(s)} regroups terms of s by total degree
      ++ and forms a series.
```

```
    if Coef has Algebra Fraction Integer then
      integrate: (%,Symbol,Coef) -> %
        ++\spad{integrate(s,v,c)} is the integral of s with respect
        ++ to v and having c as the constant of integration.
      fintegrate: (() -> %,Symbol,Coef) -> %
        ++\spad{fintegrate(f,v,c)} is the integral of \spad{f()} with respect
        ++ to v and having c as the constant of integration.
        ++ The evaluation of \spad{f()} is delayed.

  Implementation ==> SparseMultivariateTaylorSeries(Coef,Symbol,SMP) add
    Rep := StS -- Below we use the fact that Rep of PS is Stream SMP.

    polynomial(s,n) ==
      sum : SMP := 0
      for i in 0..n while not empty? s repeat
        sum := sum + frst s
        s:= rst s
      sum
```

———-

— **TS.dotabb** —

```
"TS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TS"]
"TRANFUN" [color="#4488FF",href="bookvol10.2.pdf#nameddest=TRANFUN"]
"PSCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PSCAT"]
"TS" -> "PSCAT"
"TS" -> "TRANFUN"
```

———-

21.4 domain TEX TexFormat

21.4.1 product(product(i*j,i=a..b),j=c..d) fix

The expression prints properly in ascii text but the tex output is incorrect. Originally the input

```
product(product(i*j,i=a..b),j=c..d)
```

prints as

$$PI2\,(j = c,\ d,\ PI2\,(i = a,\ b,\ i\ j)) \tag{1}$$

but now says: The problem is in [[src/algebra/tex.spad.pamphlet]] in the list of constants. The code used to read

```
    plexOps       : L S := ["SIGMA","SIGMA2","PI","INTSIGN","INDEFINTEGRAL"]$(L S)
    plexPrecs     : L I := [    700, 800,      700,           700]$(L I)
```

it now reads:

— **product(product(i*j,i=a..b),j=c..d) fix** —

```
    plexOps       : L S := ["SIGMA","SIGMA2","PI","PI2","INTSIGN","INDEFINTEGRAL"]$(L S)
    plexPrecs     : L I := [    700, 800,     700, 800 , 700,      700]$(L I)
```

————-

in addition we need to add a line defining [[PI2]] in [[formatPlex]]:

— **define PI2** —

```
        op = "PI2"     => "\prod"
```

————-

— **TexFormat.input** —

```
)set break resume
)sys rm -f TexFormat.output
)spool TexFormat.output
)set message test on
)set message auto off
)clear all

--S 1 of 11
(1/2)::TEX
--R
--R
--R   (1)  ["$$","\frac{1}{2} ","$$"]
--R                                                    Type: TexFormat
--E 1

--S 2 of 11
(1/(x+5))::TEX
--R
--R
--R   (2)  ["$$","\frac{1}{{x+5}} ","$$"]
--R                                                    Type: TexFormat
--E 2

--S 3 of 11
((x+3)/(y-5))::TEX
--R
--R
--R   (3)  ["$$","\frac{{x+3}}{{y -5}} ","$$"]
--R                                                    Type: TexFormat
```

```
--E 3

--S 4 of 11
)set output fraction horizontal
--R
--E 4

--S 5 of 11
(1/2)::TEX
--R
--R
--R   (4)  ["$$","SLASH ","\left(","{1, \: 2} ","\right)","$$"]
--R                                                        Type: TexFormat
--E 5

--S 6 of 11
(1/(x+5))::TEX
--R
--R
--R   (5)
--R   ["$$","SLASH ","\left(","{1, \: {\left( x+5 ","\right)}}","\right)","$$"]
--R                                                        Type: TexFormat
--E 6

--S 7 of 11
)set output mathml on
--R
--E 7

--S 8 of 11
1/2
--R
--R
--R   (6)  1/2
--R<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big" display="block">
--R<mrow><mn>1</mn><mo>/</mo><mn>2</mn></mrow>
--R</math>
--R
--R                                                  Type: Fraction(Integer)
--E 8

--S 9 of 11
1/(x+5)
--R
--R
--R   (7)  1/(x + 5)
--R<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big" display="block">
--R<mrow><mn>1</mn><mo>/</mo><mrow><mo>(</mo><mi>x</mi><mo>+</mo><mn>5</mn><mo>)</mo></mrow></mr
--R</math>
--R
```

```
--R                                          Type: Fraction(Polynomial(Integer))
--E 9

--S 10 of 11
(x+3)/(y-5)
--R
--R
--R   (8)  (x + 3)/(y - 5)
--R<math xmlns="http://www.w3.org/1998/Math/MathML" mathsize="big" display="block">
--R<mrow><mrow><mo>(</mo><mi>x</mi><mo>+</mo><mn>3</mn><mo>)</mo></mrow><mo>/</mo><mrow><mo>(</mo><mi>y</mi>
--R</math>
--R
--R                                          Type: Fraction(Polynomial(Integer))
--E 10

--S 11 of 11
)show TexFormat
--R
--R TexFormat  is a domain constructor
--R Abbreviation for TexFormat is TEX
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for TEX
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : OutputForm -> %
--R coerce : % -> OutputForm             display : % -> Void
--R display : (%,Integer) -> Void        epilogue : % -> List(String)
--R hash : % -> SingleInteger            latex : % -> String
--R new : () -> %                        prologue : % -> List(String)
--R tex : % -> List(String)              ?~=? : (%,%) -> Boolean
--R convert : (OutputForm,Integer,OutputForm) -> %
--R convert : (OutputForm,Integer) -> %
--R setEpilogue! : (%,List(String)) -> List(String)
--R setPrologue! : (%,List(String)) -> List(String)
--R setTex! : (%,List(String)) -> List(String)
--R
--E 11

)spool
)lisp (bye)
```

———-

— TexFormat.help —

```
=====================================================================
TexFormat examples
=====================================================================
```

```
You can ask Axiom to show latex output. In particular, this can be
used for complex output.

(1/2)::TEX

     ["$$","\frac{1}{2} ","$$"]

(1/(x+5))::TEX

     ["$$","\frac{1}{{x+5}} ","$$"]

((x+3)/(y-5))::TEX

     ["$$","\frac{{x+3}}{{y -5}} ","$$"]


We can change the fraction display so it is horizontal:

)set output fraction horizontal

(1/2)::TEX

     ["$$","SLASH ","\left(","{1, \: 2} ","\right)","$$"]

(1/(x+5))::TEX

     ["$$","SLASH ","\left(","{1, \: {x+5}} ","\right)","$$"]


((x+3)/(y-5))::TEX

     ["$$","SLASH ","\left(","{{x+3}, \: {y -5}} ","\right)","$$"]


See Also:
o )show TexFormat
```

———-

21.4.2 TexFormat (TEX)



Exports:

coerce	convert	display	epilogue	hash
latex	new	prologue	setEpilogue!	setPrologue!
setTex!	tex	convert	?=?	?~=?

— domain TEX TexFormat —

```
)abbrev domain TEX TexFormat
++ Author: Robert S. Sutor
++ Date Created: 1987 through 1992
++ Change History:
++   05/15/91 RSS Changed matrix formatting to use array environment.
++   06/27/91 RSS Fixed segments
++   08/12/91 RSS Removed some grouping for things, added newWithNum and
++                ungroup, improved line splitting
++   08/15/91 RSS Added mbox support for strings
++   10/15/91 RSS Handle \%\% at beginning of string
++   01/22/92 RSS Use \[ and \] instead of $$ and $$. Use
++                %AXIOM STEP NUMBER: instead of \leqno
++   02/27/92 RSS Escape dollar signs appearing in the input.
++   03/09/92 RSS Handle explicit blank appearing in the input.
++   11/28/93 JHD Added code for the VCONCAT and TAG operations.
++   06/27/95 RSS Change back to $$ and \leqno for Saturn
++ Basic Operations: coerce, convert, display, epilogue,
++   tex, new, prologue, setEpilogue!, setTex!, setPrologue!
++ Related Constructors: TexFormat1
++ Also See: ScriptFormulaFormat
++ AMS Classifications:
++ Keywords: TeX, LaTeX, output, format
++ References: \TeX{} is a trademark of the American Mathematical Society.
++ Description:
++ \spadtype{TexFormat} provides a coercion from \spadtype{OutputForm} to
++ \TeX{} format.  The particular dialect of \TeX{} used is \LaTeX{}.
++ The basic object consists of three parts: a prologue, a
++ tex part and an epilogue. The functions \spadfun{prologue},
```

```
++ \spadfun{tex} and \spadfun{epilogue} extract these parts,
++ respectively.  The main guts of the expression go into the tex part.
++ The other parts can be set (\spadfun{setPrologue!},
++ \spadfun{setEpilogue!}) so that contain the appropriate tags for
++ printing. For example, the prologue and epilogue might simply
++ contain ``\verb+\[+'' and ``\verb+\]+'', respectively, so that
++ the TeX section will be printed in LaTeX display math mode.

TexFormat(): public == private where
  E      ==> OutputForm
  I      ==> Integer
  L      ==> List
  S      ==> String
  US     ==> UniversalSegment(Integer)

  public == SetCategory with
    coerce:   E -> $
      ++ coerce(o) changes o in the standard output format to TeX
      ++ format.
    convert:  (E,I) -> $
      ++ convert(o,step) changes o in standard output format to
      ++ TeX format and also adds the given step number. This is useful
      ++ if you want to create equations with given numbers or have the
      ++ equation numbers correspond to the interpreter step numbers.
    convert:  (E,I,E) -> $
      ++ convert(o,step,type) changes o in standard output format to
      ++ TeX format and also adds the given step number and type. This
      ++ is useful if you want to create equations with given numbers
      ++ or have the equation numbers correspond to the interpreter step
      ++ numbers.
    display:  ($, I) -> Void
      ++ display(t,width) outputs the TeX formatted code t so that each
      ++ line has length less than or equal to \spadvar{width}.
    display:  $ -> Void
      ++ display(t) outputs the TeX formatted code t so that each
      ++ line has length less than or equal to the value set by
      ++ the system command \spadsyscom{set output length}.
    epilogue: $ -> L S
      ++ epilogue(t) extracts the epilogue section of a TeX form t.
    tex:      $ -> L S
      ++ tex(t) extracts the TeX section of a TeX form t.
    new:      () -> $
      ++ new() create a new, empty object. Use \spadfun{setPrologue!},
      ++ \spadfun{setTex!} and \spadfun{setEpilogue!} to set the various
      ++ components of this object.
    prologue: $ -> L S
      ++ prologue(t) extracts the prologue section of a TeX form t.
    setEpilogue!: ($, L S) -> L S
      ++ setEpilogue!(t,strings) sets the epilogue section of a TeX form t
      ++ to strings.
```

```
    setTex!:  ($, L S) -> L S
      ++ setTex!(t,strings) sets the TeX section of a TeX form t to strings.
    setPrologue!: ($, L S) -> L S
      ++ setPrologue!(t,strings) sets the prologue section of a TeX form t
      ++ to strings.

  private == add
    import OutputForm
    import Character
    import Integer
    import List OutputForm
    import List String

    Rep := Record(prolog : L S, TeX : L S, epilog : L S)

    -- local variables declarations and definitions

    expr: E
    prec,opPrec: I
    str:  S
    blank         : S := " \  "

    maxPrec       : I   := 1000000
    minPrec       : I   := 0

    unaryOps      : L S := ["-","^"]$(L S)
    unaryPrecs    : L I := [700,260]$(L I)

    -- the precedence of / in the following is relatively low because
    -- the bar obviates the need for parentheses.
    binaryOps     : L S := ["+->","|","**","/","<",">","=","OVER"]$(L S)
    binaryPrecs   : L I := [0,0,900, 700,400,400,400,   700]$(L I)

    naryOps       : L S := ["-","+","*",blank,",",";"," ","ROW","",
       " \cr ","&"," \\ "]$(L S)
    naryPrecs     : L I := [700,700,800,  800,110,110,  0,    0, 0,
             0,  0,   0]$(L I)
    naryNGOps     : L S := ["ROW","&"]$(L S)

\getchunk{product(product(i*j,i=a..b),j=c..d) fix}

    specialOps    : L S := ["MATRIX","BRACKET","BRACE","CONCATB","VCONCAT",  _
                            "AGGLST","CONCAT","OVERBAR","ROOT","SUB","TAG", _
                            "SUPERSUB","ZAG","AGGSET","SC","PAREN", _
                            "SEGMENT","QUOTE","theMap" ]

    -- the next two lists provide translations for some strings for
    -- which TeX provides special macros.

    specialStrings : L S :=
```

```
      ["cos", "cot", "csc", "log", "sec", "sin", "tan",
        "cosh", "coth", "csch", "sech", "sinh", "tanh",
          "acos","asin","atan","erf","...","$","infinity"]
    specialStringsInTeX : L S :=
      ["\cos","\cot","\csc","\log","\sec","\sin","\tan",
        "\cosh","\coth","\csch","\sech","\sinh","\tanh",
          "\arccos","\arcsin","\arctan","\erf","\ldots","\$","\infty"]

    -- local function signatures

    addBraces:      S -> S
    addBrackets:    S -> S
    group:          S -> S
    formatBinary:   (S,L E, I) -> S
    formatFunction: (S,L E, I) -> S
    formatMatrix:   L E -> S
    formatNary:     (S,L E, I) -> S
    formatNaryNoGroup: (S,L E, I) -> S
    formatNullary:  S -> S
    formatPlex:     (S,L E, I) -> S
    formatSpecial:  (S,L E, I) -> S
    formatUnary:    (S,  E, I) -> S
    formatTex:      (E,I) -> S
    newWithNum:     I -> $
    parenthesize:   S -> S
    precondition:   E -> E
    postcondition:  S -> S
    splitLong:      (S,I) -> L S
    splitLong1:     (S,I) -> L S
    stringify:      E -> S
    ungroup:        S -> S

    -- public function definitions

    new() : $ ==
--    [["\["]$(L S), [""]$(L S), ["\]"]$(L S)]$Rep
      [["$$"]$(L S), [""]$(L S), ["$$"]$(L S)]$Rep

    newWithNum(stepNum: I) : $ ==
--    num : S := concat("%AXIOM STEP NUMBER: ",string(stepNum)$S)
--    [["\["]$(L S), [""]$(L S), ["\]",num]$(L S)]$Rep
      num : S := concat(concat("\leqno(",string(stepNum)$S),")")$S
      [["$$"]$(L S), [""]$(L S), [num,"$$"]$(L S)]$Rep

    coerce(expr : E): $ ==
      f : $ := new()$$
      f.TeX := [postcondition
        formatTex(precondition expr, minPrec)]$(L S)
      f
```

```
convert(expr : E, stepNum : I): $ ==
  f : $ := newWithNum(stepNum)
  f.TeX := [postcondition
    formatTex(precondition expr, minPrec)]$(L S)
  f

display(f : $, len : I) ==
  s,t : S
  for s in f.prolog repeat sayTeX$Lisp s
  for s in f.TeX repeat
    for t in splitLong(s, len) repeat sayTeX$Lisp t
  for s in f.epilog repeat sayTeX$Lisp s
  void()$Void

display(f : $) ==
  display(f, _$LINELENGTH$Lisp pretend I)

prologue(f : $) == f.prolog
tex(f : $)  == f.TeX
epilogue(f : $) == f.epilog

setPrologue!(f : $, l : L S) == f.prolog := l
setTex!(f : $, l : L S)  == f.TeX := l
setEpilogue!(f : $, l : L S) == f.epilog := l

coerce(f : $): E ==
  s,t : S
  l : L S := nil
  for s in f.prolog repeat l := concat(s,l)
  for s in f.TeX repeat
    for t in splitLong(s, (_$LINELENGTH$Lisp pretend Integer) - 4) repeat
      l := concat(t,l)
  for s in f.epilog repeat l := concat(s,l)
  (reverse l) :: E

-- local function definitions

ungroup(str: S): S ==
  len : I := #str
  len < 2 => str
  lbrace : Character := char "{"
  rbrace : Character := char "}"
  -- drop leading and trailing braces
  if (str.1 =$Character lbrace) and (str.len =$Character rbrace) then
    u : US := segment(2,len-1)$US
    str := str.u
  str

postcondition(str: S): S ==
  str := ungroup str
```

```
    len : I := #str
    plus : Character := char "+"
    minus: Character := char "-"
    len < 4 => str
    for i in 1..(len-1) repeat
      if (str.i =$Character plus) and (str.(i+1) =$Character minus)
        then setelt(str,i,char " ")$S
    str

  stringify expr == (object2String$Lisp expr) pretend S

  lineConcat( line : S, lines: L S ) : L S ==
    length := #line

    if ( length > 0 ) then
      -- If the last character is a backslash then split at "\ ".
      -- Reinstate the blank.

      if (line.length = char "\" ) then line := concat(line, " ")

      -- Remark: for some reason, "\%" at the beginning
      -- of a line has the "\" erased when printed

      if ( line.1 = char "%" ) then line := concat(" \", line)
      else if ( line.1 = char "\" ) and length > 1 and ( line.2 = char "%" ) then
        line := concat(" ", line)

      lines := concat(line,lines)$List(S)
    lines

  splitLong(str : S, len : I): L S ==
    -- this blocks into lines
    if len < 20 then len := _$LINELENGTH$Lisp
    splitLong1(str, len)

  splitLong1(str : S, len : I) ==
    -- We first build the list of lines backwards and then we
    -- reverse it.

    l : List S := nil
    s : S := ""
    ls : I := 0
    ss : S
    lss : I
    for ss in split(str,char " ") repeat
      -- have the newline macro end a line (even if it means the line
      -- is slightly too long)

      ss = "\\" =>
        l := lineConcat( concat(s,ss), l )
```

```
        s := ""
        ls := 0

      lss := #ss

      -- place certain tokens on their own lines for clarity

      ownLine : Boolean :=
        u : US := segment(1,4)$US
        (lss > 3) and ("\end" = ss.u) => true
        u      := segment(1,5)$US
        (lss > 4) and ("\left" = ss.u) => true
        u      := segment(1,6)$US
        (lss > 5) and (("\right" = ss.u) or ("\begin" = ss.u)) => true
        false

      if ownLine or (ls + lss > len) then
        if not empty? s then l := lineConcat( s, l )
        s := ""
        ls := 0

      ownLine or lss > len => l := lineConcat( ss, l )

      (lss = 1) and (ss.1 = char "\") =>
        ls := ls + lss + 2
        s := concat(s,concat(ss,"  ")$S)$S

      ls := ls + lss + 1
      s := concat(s,concat(ss," ")$S)$S

    if ls > 0 then l := lineConcat( s, l )

    reverse l

  group str ==
    concat ["{",str,"}"]

  addBraces str ==
    concat ["\left\{ ",str," \right\}"]

  addBrackets str ==
    concat ["\left[ ",str," \right]"]

  parenthesize str ==
    concat ["\left( ",str," \right)"]

  precondition expr ==
    outputTran$Lisp expr

  formatSpecial(op : S, args : L E, prec : I) : S ==
```

```
arg : E
prescript : Boolean := false
op = "theMap" => "\mbox{theMap(...)}"
op = "AGGLST" =>
  formatNary(",",args,prec)
op = "AGGSET" =>
  formatNary(";",args,prec)
op = "TAG" =>
  group concat [formatTex(first args,prec),
                "\rightarrow",
                 formatTex(second args,prec)]
op = "VCONCAT" =>
  group concat("\begin{array}{c}",
               concat(concat([concat(formatTex(u, minPrec),"\\")
                             for u in args]::L S),
                      "\end{array}"))
op = "CONCATB" =>
  formatNary(" ",args,prec)
op = "CONCAT" =>
  formatNary("",args,minPrec)
op = "QUOTE" =>
  group concat("{\tt '}",formatTex(first args, minPrec))
op = "BRACKET" =>
  group addBrackets ungroup formatTex(first args, minPrec)
op = "BRACE" =>
  group addBraces ungroup formatTex(first args, minPrec)
op = "PAREN" =>
  group parenthesize ungroup formatTex(first args, minPrec)
op = "OVERBAR" =>
  null args => ""
  group concat ["\overline ",formatTex(first args, minPrec)]
op = "ROOT" =>
  null args => ""
  tmp : S := group formatTex(first args, minPrec)
  null rest args => group concat ["\sqrt ",tmp]
  group concat
    ["\root ",group formatTex(first rest args, minPrec)," \of ",tmp]
op = "SEGMENT" =>
  tmp : S := concat [formatTex(first args, minPrec),".."]
  group
    null rest args =>  tmp
    concat [tmp,formatTex(first rest args, minPrec)]
op = "SUB" =>
  group concat [formatTex(first args, minPrec)," \sb ",
    formatSpecial("AGGLST",rest args,minPrec)]
op = "SUPERSUB" =>
  -- variable name
  form : List S := [formatTex(first args, minPrec)]
  -- subscripts
  args := rest args
```

```
      null args => concat(form)$S
      tmp : S := formatTex(first args, minPrec)
      if (tmp ^= "") and (tmp ^= "{}") and (tmp ^= " ") then
        form := append(form,[" \sb ",group tmp])$(List S)
      -- superscripts
      args := rest args
      null args => group concat(form)$S
      tmp : S := formatTex(first args, minPrec)
      if (tmp ^= "") and (tmp ^= "{}") and (tmp ^= " ") then
        form := append(form,[" \sp ",group tmp])$(List S)
      -- presuperscripts
      args := rest args
      null args => group concat(form)$S
      tmp : S := formatTex(first args, minPrec)
      if (tmp ^= "") and (tmp ^= "{}") and (tmp ^= " ") then
        form := append([" \sp ",group tmp],form)$(List S)
        prescript := true
      -- presubscripts
      args := rest args
      null args =>
        group concat
          prescript => cons("{}",form)
          form
      tmp : S := formatTex(first args, minPrec)
      if (tmp ^= "") and (tmp ^= "{}") and (tmp ^= " ") then
        form := append([" \sb ",group tmp],form)$(List S)
        prescript := true
      group concat
        prescript => cons("{}",form)
        form
    op = "SC" =>
      -- need to handle indentation someday
      null args => ""
      tmp := formatNaryNoGroup(" \\ ", args, minPrec)
      group concat ["\begin{array}{l} ",tmp," \end{array} "]
    op = "MATRIX" => formatMatrix rest args
    op = "ZAG" =>
      concat [" \zag{",formatTex(first args, minPrec),"}{",
        formatTex(first rest args,minPrec),"}"]
    concat ["not done yet for ",op]

  formatPlex(op : S, args : L E, prec : I) : S ==
    hold : S
    p : I := position(op,plexOps)
    p < 1 => error "unknown Tex unary op"
    opPrec := plexPrecs.p
    n : I := #args
    (n ^= 2) and (n ^= 3) => error "wrong number of arguments for plex"
    s : S :=
      op = "SIGMA"   => "\sum"
```

```
        op = "SIGMA2"   => "\sum"
        op = "PI"      => "\prod"
\getchunk{define PI2}
        op = "INTSIGN" => "\int"
        op = "INDEFINTEGRAL" => "\int"
        "????"
      hold := formatTex(first args,minPrec)
      args := rest args
      if op ^= "INDEFINTEGRAL" then
        if hold ^= "" then
          s := concat [s," \sb",group concat ["\displaystyle ",hold]]
        if not null rest args then
          hold := formatTex(first args,minPrec)
          if hold ^= "" then
            s := concat [s," \sp",group concat ["\displaystyle ",hold]]
          args := rest args
        s := concat [s," ",formatTex(first args,minPrec)]
      else
        hold := group concat [hold," ",formatTex(first args,minPrec)]
        s := concat [s," ",hold]
      if opPrec < prec then s := parenthesize s
      group s

    formatMatrix(args : L E) : S ==
      -- format for args is [[ROW ...],[ROW ...],[ROW ...]]
      -- generate string for formatting columns (centered)
      cols : S := "{"
      for i in 2..#(first(args) pretend L E) repeat
        cols := concat(cols,"c")
      cols := concat(cols,"} ")
      group addBrackets concat
        ["\begin{array}",cols,formatNaryNoGroup(" \\ ",args,minPrec),
          " \end{array} "]

    formatFunction(op : S, args : L E, prec : I) : S ==
      group concat [op, " ", parenthesize formatNary(",",args,minPrec)]

    formatNullary(op : S) ==
      op = "NOTHING" => ""
      group concat [op,"()"]

    formatUnary(op : S, arg : E, prec : I) ==
      p : I := position(op,unaryOps)
      p < 1 => error "unknown Tex unary op"
      opPrec := unaryPrecs.p
      s : S := concat [op,formatTex(arg,opPrec)]
      opPrec < prec => group parenthesize s
      op = "-" => s
      group s
```

```
formatBinary(op : S, args : L E, prec : I) : S ==
  p : I := position(op,binaryOps)
  p < 1 => error "unknown Tex binary op"
  op :=
    op = "|"     => " \mid "
    op = "**"    => " \sp "
    op = "/"     => " \over "
    op = "OVER"  => " \over "
    op = "+->"   => " \mapsto "
    op
  opPrec := binaryPrecs.p
  s : S := formatTex(first args, opPrec)
  if op = " \over " then
    s := concat [" \frac{",s,"}{",formatTex(first rest args, opPrec),"}"]
  else if op = " \sp " then
    s := concat [s,"^",formatTex(first rest args, opPrec)]
  else
    s := concat [s,op,formatTex(first rest args, opPrec)]
  group
    op = " \over " => s
    opPrec < prec => parenthesize s
    s

formatNary(op : S, args : L E, prec : I) : S ==
  group formatNaryNoGroup(op, args, prec)

formatNaryNoGroup(op : S, args : L E, prec : I) : S ==
  null args => ""
  p : I := position(op,naryOps)
  p < 1 => error "unknown Tex nary op"
  op :=
    op = ","     => ", \: "
    op = ";"     => "; \: "
    op = "*"     => blank
    op = " "     => " \ "
    op = "ROW"   => " & "
    op
  l : L S := nil
  opPrec := naryPrecs.p
  for a in args repeat
    l := concat(op,concat(formatTex(a,opPrec),l)$L(S))$L(S)
  s : S := concat reverse rest l
  opPrec < prec => parenthesize s
  s

formatTex(expr,prec) ==
  i,len : Integer
  intSplitLen : Integer := 20
  ATOM(expr)$Lisp pretend Boolean =>
    str := stringify expr
```

```
  len := #str
  INTEGERP$Lisp expr =>
    i := expr pretend Integer
    if (i < 0) or (i > 9)
      then
        group
           nstr : String := ""
           -- insert some blanks into the string, if too long
           while ((len := #str) > intSplitLen) repeat
             nstr := concat [nstr," ",
               elt(str,segment(1,intSplitLen)$US)]
             str := elt(str,segment(intSplitLen+1)$US)
           empty? nstr => str
           nstr :=
             empty? str => nstr
             concat [nstr," ",str]
           elt(nstr,segment(2)$US)
      else str
  str = "%pi" => "\pi"
  str = "%e"  => "e"
  str = "%i"  => "i"
  len > 1 and str.1 = char "%" and str.2 = char "%" =>
    u : US := segment(3,len)$US
    concat(" \%\%",str.u)
  len > 0 and str.1 = char "%" => concat(" \",str)
  len > 1 and digit? str.1 => group str -- should handle floats
  len > 0 and str.1 = char "_"" =>
    concat(concat(" \mbox{\tt ",str),"} ")
  len = 1 and str.1 = char " " => "{\ }"
  (i := position(str,specialStrings)) > 0 =>
    specialStringsInTeX.i
  (i := position(char " ",str)) > 0 =>
    -- We want to preserve spacing, so use a roman font.
    concat(concat(" \mbox{\rm ",str),"} ")
  str
l : L E := (expr pretend L E)
null l => blank
op : S := stringify first l
args : L E := rest l
nargs : I := #args

-- special cases
member?(op, specialOps) => formatSpecial(op,args,prec)
member?(op, plexOps)    => formatPlex(op,args,prec)

-- nullary case
0 = nargs => formatNullary op

-- unary case
(1 = nargs) and member?(op, unaryOps) =>
```

```
        formatUnary(op, first args, prec)

      -- binary case
      (2 = nargs) and member?(op, binaryOps) =>
        formatBinary(op, args, prec)

      -- nary case
      member?(op,naryNGOps) => formatNaryNoGroup(op,args, prec)
      member?(op,naryOps) => formatNary(op,args, prec)
      op := formatTex(first l,minPrec)
      formatFunction(op,args,prec)
```

———-

— **TEX.dotabb** —

```
"TEX" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TEX"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"TEX" -> "STRING"
```

———-

21.5 domain TEXTFILE TextFile

— **TextFile.input** —

```
)set break resume
)sys rm -f TextFile.output
)spool TextFile.output
)set message test on
)set message auto off
)clear all
--S 1 of 10
f1: TextFile := open("/etc/group", "input")
--R
--R
--R   (1)  "/etc/group"
--R                                                    Type: TextFile
--E 1

--S 2 of 10
f2: TextFile := open("MOTD", "output")
--R
--R
```

```
--R   (2)  "MOTD"
--R                                                    Type: TextFile
--E 2

--S 3 of 10
l := readLine! f1
--R
--R
--I   (3)  "ROOT:x:0:"
--R                                                      Type: String
--E 3

--S 4 of 10
writeLine!(f2, upperCase l)
--R
--R
--I   (4)  "ROOT:X:0:"
--R                                                      Type: String
--E 4

--S 5 of 10
while not endOfFile? f1 repeat
  s := readLine! f1
  writeLine!(f2, upperCase s)
--R
--R                                                        Type: Void
--E 5

--S 6 of 10
close! f1
--R
--R
--R   (6)  "/etc/group"
--R                                                    Type: TextFile
--E 6

--S 7 of 10
write!(f2, "-The-")
--R
--R
--R   (7)  "-The-"
--R                                                      Type: String
--E 7

--S 8 of 10
write!(f2, "-End-")
--R
--R
--R   (8)  "-End-"
--R                                                      Type: String
```

```
--E 8

--S 9 of 10
writeLine! f2
--R
--R
--R   (9)  ""
--R                                                          Type: String
--E 9

--S 10 of 10
close! f2
--R
--R
--R   (10)  "MOTD"
--R                                                        Type: TextFile
--E 10
)system rm -f MOTD
)spool
)lisp (bye)
```

———-

— TextFile.help —

```
========================================================================
TextFile examples
========================================================================

The domain TextFile allows Axiom to read and write character data and
exchange text with other programs.  This type behaves in Axiom much
like a File of strings, with additional operations to cause new lines.
We give an example of how to produce an upper case copy of a file.

This is the file from which we read the text.

  f1: TextFile := open("/etc/group", "input")
    "/etc/group"
                                Type: TextFile

This is the file to which we write the text.

  f2: TextFile := open("/tmp/MOTD", "output")
    "MOTD"
                                Type: TextFile

Entire lines are handled using the readLine and writeLine operations.

  l := readLine! f1
```

```
    "root:x:0:root"
                                Type: String

  writeLine!(f2, upperCase l)
    "ROOT:X:0:ROOT"
                                Type: String
```

Use the endOfFile? operation to check if you have reached the end of the file.

```
  while not endOfFile? f1 repeat
    s := readLine! f1
    writeLine!(f2, upperCase s)
                                Type: Void
```

The file f1 is exhausted and should be closed.

```
  close! f1
    "/etc/group"
                                Type: TextFile
```

It is sometimes useful to write lines a bit at a time. The write operation allows this.

```
  write!(f2, "-The-")
    "-The-"
                                Type: String

  write!(f2, "-End-")
    "-End-"
                                Type: String
```

This ends the line. This is done in a machine-dependent manner.

```
  writeLine! f2
    ""
                                Type: String

  close! f2
    "MOTD"
                                Type: TextFile
```


Finally, clean up.

```
  )system rm /tmp/MOTD
```

See Also:
o)help File
o)help KeyedAccessFile
o)help Library
o)show TextFile

———-

21.5.1 TextFile (TEXTFILE)



See

⇒ “File” (FILE) 7.2.1 on page 772
⇒ “BinaryFile” (BINFILE) 3.8.1 on page 279
⇒ “KeyedAccessFile” (KAFILE) 12.2.1 on page 1381
⇒ “Library” (LIB) 13.2.1 on page 1396

Exports:

close!	coerce	endOfFile?	hash	iomode
latex	name	open	read!	readIfCan!
readLine!	readLineIfCan!	reopen!	write!	writeLine!
?=?	?~=?			

— domain TEXTFILE TextFile —

```
)abbrev domain TEXTFILE TextFile
++ Author: Stephen M. Watt
++ Date Created: 1985
++ Date Last Updated: June 4, 1991
++ Basic Operations: writeLine! readLine! readLineIfCan! readIfCan! endOfFile?
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain provides an implementation of text files.  Text is stored
++ in these files using the native character set of the computer.

TextFile: Cat == Def where
```

```
    StreamName ==> Union(FileName, "console")

    Cat == FileCategory(FileName, String) with
        writeLine_!: (%, String) -> String
          ++ writeLine!(f,s) writes the contents of the string s
          ++ and finishes the current line in the file f.
          ++ The value of s is returned.

        writeLine_!: % -> String
          ++ writeLine!(f) finishes the current line in the file f.
          ++ An empty string is returned.  The call \spad{writeLine!(f)} is
          ++ equivalent to \spad{writeLine!(f,"")}.

        readLine_!: % -> String
          ++ readLine!(f) returns a string of the contents of a line from
          ++ the file f.

        readLineIfCan_!: % -> Union(String, "failed")
          ++ readLineIfCan!(f) returns a string of the contents of a line from
          ++ file f, if possible.  If f is not readable or if it is
          ++ positioned at the end of file, then \spad{"failed"} is returned.

        readIfCan_!: % -> Union(String, "failed")
          ++ readIfCan!(f) returns a string of the contents of a line from
          ++ file f, if possible.  If f is not readable or if it is
          ++ positioned at the end of file, then \spad{"failed"} is returned.

        endOfFile?: % -> Boolean
          ++ endOfFile?(f) tests whether the file f is positioned after the
          ++ end of all text.  If the file is open for output, then
          ++ this test is always true.

    Def == File(String) add
        FileState ==> SExpression

        Rep := Record(fileName:   FileName,    _
                      fileState:  FileState,   _
                      fileIOmode: String)

        read_! f      == readLine_! f
        readIfCan_! f == readLineIfCan_! f

        readLine_! f ==
            f.fileIOmode ^= "input"  => error "File not in read state"
            s: String := read_-line(f.fileState)$Lisp
            PLACEP(s)$Lisp => error "End of file"
            s
        readLineIfCan_! f ==
            f.fileIOmode ^= "input"  => error "File not in read state"
            s: String := read_-line(f.fileState)$Lisp
```

```
            PLACEP(s)$Lisp => "failed"
            s
        write_!(f, x) ==
            f.fileIOmode ^= "output" => error "File not in write state"
            PRINTEXP(x, f.fileState)$Lisp
            x
        writeLine_! f ==
            f.fileIOmode ^= "output" => error "File not in write state"
            TERPRI(f.fileState)$Lisp
            ""
        writeLine_!(f, x) ==
            f.fileIOmode ^= "output" => error "File not in write state"
            PRINTEXP(x, f.fileState)$Lisp
            TERPRI(f.fileState)$Lisp
            x
        endOfFile? f ==
          f.fileIOmode = "output" => false
          (EOFP(f.fileState)$Lisp pretend Boolean) => true
          false
```

———-

— **TEXTFILE.dotabb** —

```
"TEXTFILE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TEXTFILE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"TEXTFILE" -> "STRING"
```

———-

21.6 domain SYMS TheSymbolTable

— **TheSymbolTable.input** —

```
)set break resume
)sys rm -f TheSymbolTable.output
)spool TheSymbolTable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show TheSymbolTable
--R
```

```
--R TheSymbolTable  is a domain constructor
--R Abbreviation for TheSymbolTable is SYMS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SYMS
--R
--R------------------------------ Operations --------------------------------
--R clearTheSymbolTable : () -> Void      coerce : % -> OutputForm
--R currentSubProgram : () -> Symbol      empty : () -> %
--R endSubProgram : () -> Symbol          newSubProgram : Symbol -> Void
--R printHeader : () -> Void              printHeader : Symbol -> Void
--R printHeader : (Symbol,%) -> Void      printTypes : Symbol -> Void
--R showTheSymbolTable : () -> %
--R argumentList! : List(Symbol) -> Void
--R argumentList! : (Symbol,List(Symbol)) -> Void
--R argumentList! : (Symbol,List(Symbol),%) -> Void
--R argumentListOf : (Symbol,%) -> List(Symbol)
--R clearTheSymbolTable : Symbol -> Void
--R declare! : (Symbol,FortranType,Symbol) -> FortranType
--R declare! : (Symbol,FortranType) -> FortranType
--R declare! : (List(Symbol),FortranType,Symbol,%) -> FortranType
--R declare! : (Symbol,FortranType,Symbol,%) -> FortranType
--R returnType! : Union(fst: FortranScalarType,void: void) -> Void
--R returnType! : (Symbol,Union(fst: FortranScalarType,void: void)) -> Void
--R returnType! : (Symbol,Union(fst: FortranScalarType,void: void),%) -> Void
--R returnTypeOf : (Symbol,%) -> Union(fst: FortranScalarType,void: void)
--R symbolTableOf : (Symbol,%) -> SymbolTable
--R
--E 1

)spool
)lisp (bye)
```

———-


— TheSymbolTable.help —

```
=====================================================================
TheSymbolTable examples
=====================================================================

See Also:
o )show TheSymbolTable
```

———-

21.6.1 TheSymbolTable (SYMS)



See

⇒ "FortranScalarType" (FST) 7.19.1 on page 932
⇒ "FortranType" (FT) 7.21.1 on page 941
⇒ "SymbolTable" (SYMTAB) 20.38.1 on page 2616

Exports:

argumentList!	argumentListOf	clearTheSymbolTable	coerce	currentSubProgram
declare!	empty	endSubProgram	newSubProgram	printHeader
printTypes	returnType!	returnTypeOf	showTheSymbolTable	symbolTableOf

— domain SYMS TheSymbolTable —

```
)abbrev domain SYMS TheSymbolTable
++ Author: Mike Dewar
++ Date Created:  October 1992
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ Creates and manipulates one global symbol table for FORTRAN
++ code generation, containing details of types, dimensions, and argument
++ lists.

TheSymbolTable() : Exports == Implementation where

  S    ==> Symbol
  FST  ==> FortranScalarType
  FSTU ==> Union(fst:FST,void:"void")

  Exports == CoercibleTo OutputForm with
    showTheSymbolTable : () -> $
```

```
  ++ showTheSymbolTable() returns the current symbol table.
clearTheSymbolTable : () -> Void
  ++ clearTheSymbolTable() clears the current symbol table.
clearTheSymbolTable : Symbol -> Void
  ++ clearTheSymbolTable(x) removes the symbol x from the table
declare! : (Symbol,FortranType,Symbol,$) -> FortranType
  ++ declare!(u,t,asp,tab) declares the parameter u of subprogram asp
  ++ to have type t in symbol table tab.
declare! : (List Symbol,FortranType,Symbol,$) -> FortranType
  ++ declare!(u,t,asp,tab) declares the parameters u of subprogram asp
  ++ to have type t in symbol table tab.
declare! : (Symbol,FortranType) -> FortranType
  ++ declare!(u,t) declares the parameter u to have type t in the
  ++ current level of the symbol table.
declare! : (Symbol,FortranType,Symbol) -> FortranType
  ++ declare!(u,t,asp) declares the parameter u to have type t in asp.
newSubProgram : Symbol -> Void
  ++ newSubProgram(f) asserts that from now on type declarations are part
  ++ of subprogram f.
currentSubProgram : () -> Symbol
  ++ currentSubProgram() returns the name of the current subprogram being
  ++ processed
endSubProgram : () -> Symbol
  ++ endSubProgram() asserts that we are no longer processing the current
  ++ subprogram.
argumentList! : (Symbol,List Symbol,$) -> Void
  ++ argumentList!(f,l,tab) declares that the argument list for subprogram f
  ++ in symbol table tab is l.
argumentList! : (Symbol,List Symbol) -> Void
  ++ argumentList!(f,l) declares that the argument list for subprogram f in
  ++ the global symbol table is l.
argumentList! : List Symbol -> Void
  ++ argumentList!(l) declares that the argument list for the current
  ++ subprogram in the global symbol table is l.
returnType! : (Symbol,FSTU,$) -> Void
  ++ returnType!(f,t,tab) declares that the return type of subprogram f in
  ++ symbol table tab is t.
returnType! : (Symbol,FSTU) -> Void
  ++ returnType!(f,t) declares that the return type of subprogram f in
  ++ the global symbol table is t.
returnType! : FSTU -> Void
  ++ returnType!(t) declares that the return type of he current subprogram
  ++ in the global symbol table is t.
printHeader : (Symbol,$) -> Void
  ++ printHeader(f,tab) produces the FORTRAN header for subprogram f in
  ++ symbol table tab on the current FORTRAN output stream.
printHeader : Symbol -> Void
  ++ printHeader(f) produces the FORTRAN header for subprogram f in
  ++ the global symbol table on the current FORTRAN output stream.
printHeader : () -> Void
```

```
    ++ printHeader() produces the FORTRAN header for the current subprogram in
    ++ the global symbol table on the current FORTRAN output stream.
  printTypes:  Symbol -> Void
    ++ printTypes(tab) produces FORTRAN type declarations from tab, on the
    ++ current FORTRAN output stream
  empty : () -> $
    ++ empty() creates a new, empty symbol table.
  returnTypeOf : (Symbol,$) -> FSTU
    ++ returnTypeOf(f,tab) returns the type of the object returned by f
  argumentListOf : (Symbol,$) -> List(Symbol)
    ++ argumentListOf(f,tab) returns the argument list of f
  symbolTableOf : (Symbol,$) -> SymbolTable
    ++ symbolTableOf(f,tab) returns the symbol table of f

Implementation == add

  Entry : Domain  := Record(symtab:SymbolTable, _
                            returnType:FSTU, _
                            argList:List Symbol)

  Rep := Table(Symbol,Entry)

  -- These are the global variables we want to update:
  theSymbolTable : $ := empty()$Rep
  currentSubProgramName : Symbol := MAIN

  newEntry():Entry ==
    construct(empty()$SymbolTable,["void"]$FSTU,[]::List(Symbol))$Entry

  checkIfEntryExists(name:Symbol,tab:$) : Void ==
    key?(name,tab) => void()$Void
    setelt(tab,name,newEntry())$Rep
    void()$Void

  returnTypeOf(name:Symbol,tab:$):FSTU ==
    elt(elt(tab,name)$Rep,returnType)$Entry

  argumentListOf(name:Symbol,tab:$):List(Symbol) ==
    elt(elt(tab,name)$Rep,argList)$Entry

  symbolTableOf(name:Symbol,tab:$):SymbolTable ==
    elt(elt(tab,name)$Rep,symtab)$Entry

  coerce(u:$):OutputForm ==
    coerce(u)$Rep

  showTheSymbolTable():$ ==
    theSymbolTable

  clearTheSymbolTable():Void ==
```

```
    theSymbolTable := empty()$Rep
    void()$Void

  clearTheSymbolTable(u:Symbol):Void ==
    remove!(u,theSymbolTable)$Rep
    void()$Void

  empty():$ ==
    empty()$Rep

  currentSubProgram():Symbol ==
    currentSubProgramName

  endSubProgram():Symbol ==
  -- If we want to support more complex languages then we should keep
  -- a list of subprograms / blocks - but for the moment lets stick with
  -- Fortran.
    currentSubProgramName := MAIN

  newSubProgram(u:Symbol):Void ==
    setelt(theSymbolTable,u,newEntry())$Rep
    currentSubProgramName := u
    void()$Void

  argumentList!(u:Symbol,args:List Symbol,symbols:$):Void ==
    checkIfEntryExists(u,symbols)
    setelt(elt(symbols,u)$Rep,argList,args)$Entry

  argumentList!(u:Symbol,args:List Symbol):Void ==
    argumentList!(u,args,theSymbolTable)

  argumentList!(args:List Symbol):Void ==
    checkIfEntryExists(currentSubProgramName,theSymbolTable)
    setelt(elt(theSymbolTable,currentSubProgramName)$Rep, _
           argList,args)$Entry

  returnType!(u:Symbol,type:FSTU,symbols:$):Void ==
    checkIfEntryExists(u,symbols)
    setelt(elt(symbols,u)$Rep,returnType,type)$Entry

  returnType!(u:Symbol,type:FSTU):Void ==
    returnType!(u,type,theSymbolTable)

  returnType!(type:FSTU ):Void ==
    checkIfEntryExists(currentSubProgramName,theSymbolTable)
    setelt(elt(theSymbolTable,currentSubProgramName)$Rep, _
           returnType,type)$Entry

  declare!(u:Symbol,type:FortranType):FortranType ==
    declare!(u,type,currentSubProgramName,theSymbolTable)
```

```
    declare!(u:Symbol,type:FortranType,asp:Symbol,symbols:$):FortranType ==
      checkIfEntryExists(asp,symbols)
      declare!(u,type, elt(elt(symbols,asp)$Rep,symtab)$Entry)$SymbolTable

    declare!(u:List Symbol,type:FortranType,asp:Symbol,syms:$):FortranType ==
      checkIfEntryExists(asp,syms)
      declare!(u,type, elt(elt(syms,asp)$Rep,symtab)$Entry)$SymbolTable

    declare!(u:Symbol,type:FortranType,asp:Symbol):FortranType ==
      checkIfEntryExists(asp,theSymbolTable)
      declare!(u,type,elt(elt(theSymbolTable,asp)$Rep,symtab)$Entry)$SymbolTable

    printHeader(u:Symbol,symbols:$):Void ==
      entry := elt(symbols,u)$Rep
      fortFormatHead(elt(entry,returnType)$Entry::OutputForm,u::OutputForm, _
                     elt(entry,argList)$Entry::OutputForm)$Lisp
      printTypes(elt(entry,symtab)$Entry)$SymbolTable

    printHeader(u:Symbol):Void ==
      printHeader(u,theSymbolTable)

    printHeader():Void ==
      printHeader(currentSubProgramName,theSymbolTable)

    printTypes(u:Symbol):Void ==
      printTypes(elt(elt(theSymbolTable,u)$Rep,symtab)$Entry)$SymbolTable
```

———-

— SYMS.dotabb —

```
"SYMS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SYMS"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"SYMS" -> "ALIST"
```

———-

21.7 domain M3D ThreeDimensionalMatrix

— ThreeDimensionalMatrix.input —

```
)set break resume
)sys rm -f ThreeDimensionalMatrix.output
```

```
)spool ThreeDimensionalMatrix.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ThreeDimensionalMatrix
--R
--R ThreeDimensionalMatrix(R: SetCategory)  is a domain constructor
--R Abbreviation for ThreeDimensionalMatrix is M3D
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for M3D
--R
--R------------------------------ Operations --------------------------------
--R copy : % -> %                          empty : () -> %
--R empty? : % -> Boolean                  eq? : (%,%) -> Boolean
--R map : ((R -> R),%) -> %                sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if R has SETCAT
--R any? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> PrimitiveArray(PrimitiveArray(PrimitiveArray(R)))
--R coerce : PrimitiveArray(PrimitiveArray(PrimitiveArray(R))) -> %
--R coerce : % -> OutputForm if R has SETCAT
--R construct : List(List(List(R))) -> %
--R count : (R,%) -> NonNegativeInteger if $ has finiteAggregate and R has SETCAT
--R count : ((R -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R elt : (%,NonNegativeInteger,NonNegativeInteger,NonNegativeInteger) -> R
--R eval : (%,List(R),List(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,R,R) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,Equation(R)) -> % if R has EVALAB(R) and R has SETCAT
--R eval : (%,List(Equation(R))) -> % if R has EVALAB(R) and R has SETCAT
--R every? : ((R -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if R has SETCAT
--R identityMatrix : NonNegativeInteger -> % if R has RING
--R latex : % -> String if R has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((R -> R),%) -> % if $ has shallowlyMutable
--R matrixConcat3D : (Symbol,%,%) -> %
--R matrixDimensions : % -> Vector(NonNegativeInteger)
--R member? : (R,%) -> Boolean if $ has finiteAggregate and R has SETCAT
--R members : % -> List(R) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R parts : % -> List(R) if $ has finiteAggregate
--R plus : (%,%) -> % if R has RING
--R setelt! : (%,NonNegativeInteger,NonNegativeInteger,NonNegativeInteger,R) -> R
--R size? : (%,NonNegativeInteger) -> Boolean
--R zeroMatrix : (NonNegativeInteger,NonNegativeInteger,NonNegativeInteger) -> % if R has RING
--R ?~=? : (%,%) -> Boolean if R has SETCAT
--R
--E 1
```

```
)spool
)lisp (bye)
```

———-


— **ThreeDimensionalMatrix.help** —

```
==========================================================================
ThreeDimensionalMatrix examples
==========================================================================

See Also:
o )show ThreeDimensionalMatrix
```

———-

21.7.1 ThreeDimensionalMatrix (M3D)



See

⇒ “Result” (RESULT) 19.9.1 on page 2266
⇒ “FortranCode” (FC) 7.16.1 on page 901
⇒ “FortranProgram” (FORTRAN) 7.18.1 on page 926
⇒ “SimpleFortranProgram” (SFORT) 20.11.1 on page 2373
⇒ “Switch” (SWITCH) 20.36.1 on page 2597
⇒ “FortranTemplate” (FTEM) 7.20.1 on page 937
⇒ “FortranExpression” (FEXPR) 7.17.1 on page 917

Exports:

any?	coerce	construct	copy	count
elt	empty	empty?	eq?	eval
every?	hash	identityMatrix	latex	less?
map	map!	matrixConcat3D	matrixDimensions	member?
members	more?	parts	plus	sample
setelt!	size?	zeroMatrix	#?	?=?
?~=?				

— domain M3D ThreeDimensionalMatrix —

```
)abbrev domain M3D ThreeDimensionalMatrix
++ Author: William Naylor
++ Date Created: 20 October 1993
++ Date Last Updated: 20 May 1994
++ BasicFunctions:
++ Related Constructors: Matrix
++ Also See: PrimitiveArray
++ AMS Classification:
++ Keywords:
++ References:
++ Description:
++ This domain represents three dimensional matrices over a general object type

ThreeDimensionalMatrix(R) : Exports == Implementation where

  R : SetCategory
  L ==> List
  NNI ==> NonNegativeInteger
  A1AGG ==> OneDimensionalArrayAggregate
  ARRAY1 ==> OneDimensionalArray
  PA ==> PrimitiveArray
  INT ==> Integer
  PI ==> PositiveInteger

  Exports ==> HomogeneousAggregate(R) with

    if R has Ring then
      zeroMatrix : (NNI,NNI,NNI) -> $
         ++ zeroMatrix(i,j,k) create a matrix with all zero terms
      identityMatrix : (NNI) -> $
         ++ identityMatrix(n) create an identity matrix
         ++ we note that this must be square
      plus : ($,$) -> $
         ++ plus(x,y) adds two matrices, term by term
         ++ we note that they must be the same size
    construct : (L L L R) -> $
       ++ construct(lll) creates a 3-D matrix from a List List List R lll
    elt : ($,NNI,NNI,NNI) -> R
```

```
      ++ elt(x,i,j,k) extract an element from the matrix x
   setelt! :($,NNI,NNI,NNI,R) -> R
      ++ setelt!(x,i,j,k,s) (or x.i.j.k:=s) sets a specific element of the array to some value of type R
   coerce : (PA PA PA R) -> $
      ++ coerce(p) moves from the representation type
      ++ (PrimitiveArray  PrimitiveArray  PrimitiveArray R)
      ++ to the domain
   coerce : $ -> (PA PA PA R)
          ++ coerce(x) moves from the domain to the representation type
   matrixConcat3D : (Symbol,$,$) -> $
        ++ matrixConcat3D(s,x,y) concatenates two 3-D matrices along a specified axis
   matrixDimensions : $ -> Vector NNI
        ++ matrixDimensions(x) returns the dimensions of a matrix

 Implementation ==>  (PA PA PA R) add

   import (PA PA PA R)
   import (PA PA R)
   import (PA R)
   import R

   matrix1,matrix2,resultMatrix : $

   -- function to concatenate two matrices
   -- the first argument must be a symbol, which is either i,j or k
   -- to specify the direction in which the concatenation is to take place
   matrixConcat3D(dir : Symbol,mat1 : $,mat2 : $) : $ ==
     ^((dir = (i::Symbol)) or (dir = (j::Symbol)) or (dir = (k::Symbol)))_
      => error "the axis of concatenation must be i,j or k"
     mat1Dim := matrixDimensions(mat1)
     mat2Dim := matrixDimensions(mat2)
     iDim1 := mat1Dim.1
     jDim1 := mat1Dim.2
     kDim1 := mat1Dim.3
     iDim2 := mat2Dim.1
     jDim2 := mat2Dim.2
     kDim2 := mat2Dim.3
     matRep1 : (PA PA PA R) := copy(mat1 :: (PA PA PA R))$(PA PA PA R)
     matRep2 : (PA PA PA R) := copy(mat2 :: (PA PA PA R))$(PA PA PA R)
     retVal : $

     if (dir = (i::Symbol)) then
       -- j,k dimensions must agree
       if (^((jDim1 = jDim2) and (kDim1=kDim2)))
       then
         error "jxk do not agree"
       else
         retVal := (coerce(concat(matRep1,matRep2)$(PA PA PA R))$$)@$

     if (dir = (j::Symbol)) then
```

```
      -- i,k dimensions must agree
      if (^((iDim1 = iDim2) and (kDim1=kDim2)))
      then
        error "ixk do not agree"
      else
        for i in 0..(iDim1-1) repeat
          setelt(matRep1,i,(concat(elt(matRep1,i)$(PA PA PA R)_
           ,elt(matRep2,i)$(PA PA PA R))$(PA PA R))@(PA PA R))$(PA PA PA R)
        retVal := (coerce(matRep1)$$)@$

    if (dir = (k::Symbol)) then
      temp : (PA PA R)
      -- i,j dimensions must agree
      if (^((iDim1 = iDim2) and (jDim1=jDim2)))
      then
        error "ixj do not agree"
      else
        for i in 0..(iDim1-1) repeat
          temp := copy(elt(matRep1,i)$(PA PA PA R))$(PA PA R)
          for j in 0..(jDim1-1) repeat
            setelt(temp,j,concat(elt(elt(matRep1,i)$(PA PA PA R)_
            ,j)$(PA PA R),elt(elt(matRep2,i)$(PA PA PA R),j)$(PA PA R)_
            )$(PA R))$(PA PA R)
          setelt(matRep1,i,temp)$(PA PA PA R)
        retVal := (coerce(matRep1)$$)@$

    retVal

  matrixDimensions(mat : $) : Vector NNI ==
    matRep : (PA PA PA R) := mat :: (PA PA PA R)
    iDim : NNI := (#matRep)$(PA PA PA R)
    matRep2 : PA PA R := elt(matRep,0)$(PA PA PA R)
    jDim : NNI := (#matRep2)$(PA PA R)
    matRep3 : (PA R) := elt(matRep2,0)$(PA PA R)
    kDim : NNI := (#matRep3)$(PA R)
    retVal : Vector NNI := new(3,0)$(Vector NNI)
    retVal.1 := iDim
    retVal.2 := jDim
    retVal.3 := kDim
    retVal

  coerce(matrixRep : (PA PA PA R)) : $ == matrixRep pretend $

  coerce(mat : $) : (PA PA PA R) == mat pretend (PA PA PA R)

  -- i,j,k must be with in the bounds of the matrix
  elt(mat : $,i : NNI,j : NNI,k : NNI) : R ==
    matDims := matrixDimensions(mat)
    iLength := matDims.1
    jLength := matDims.2
```

```
      kLength := matDims.3
      ((i > iLength) or (j > jLength) or (k > kLength) or (i=0) or (j=0) or_
(k=0)) => error "coordinates must be within the bounds of the matrix"
      matrixRep : PA PA PA R := mat :: (PA PA PA R)
      elt(elt(elt(matrixRep,i-1)$(PA PA PA R),j-1)$(PA PA R),k-1)$(PA R)

    setelt!(mat : $,i : NNI,j : NNI,k : NNI,val : R)_
       : R ==
      matDims := matrixDimensions(mat)
      iLength := matDims.1
      jLength := matDims.2
      kLength := matDims.3
      ((i > iLength) or (j > jLength) or (k > kLength) or (i=0) or (j=0) or_
(k=0)) => error "coordinates must be within the bounds of the matrix"
      matrixRep : PA PA PA R := mat :: (PA PA PA R)
      row2 : PA PA R := copy(elt(matrixRep,i-1)$(PA PA PA R))$(PA PA R)
      row1 : PA R := copy(elt(row2,j-1)$(PA PA R))$(PA R)
      setelt(row1,k-1,val)$(PA R)
      setelt(row2,j-1,row1)$(PA PA R)
      setelt(matrixRep,i-1,row2)$(PA PA PA R)
      val

    if R has Ring then
      zeroMatrix(iLength:NNI,jLength:NNI,kLength:NNI) : $ ==
        (new(iLength,new(jLength,new(kLength,(0$R))$(PA R))$(PA PA R))$(PA PA PA R)) :: $

      identityMatrix(iLength:NNI) : $ ==
        retValueRep : PA PA PA R := zeroMatrix(iLength,iLength,iLength)$$ :: (PA PA PA R)
        row1 : PA R
        row2 : PA PA R
        row1empty : PA R := new(iLength,0$R)$(PA R)
        row2empty : PA PA R := new(iLength,copy(row1empty)$(PA R))$(PA PA R)
        for count in 0..(iLength-1) repeat
          row1 := copy(row1empty)$(PA R)
          setelt(row1,count,1$R)$(PA R)
          row2 := copy(row2empty)$(PA PA R)
          setelt(row2,count,copy(row1)$(PA R))$(PA PA R)
          setelt(retValueRep,count,copy(row2)$(PA PA R))$(PA PA PA R)
        retValueRep :: $


      plus(mat1 : $,mat2 :$) : $ ==

        mat1Dims := matrixDimensions(mat1)
        iLength1 := mat1Dims.1
        jLength1 := mat1Dims.2
        kLength1 := mat1Dims.3

        mat2Dims := matrixDimensions(mat2)
        iLength2 := mat2Dims.1
```

```
        jLength2 := mat2Dims.2
        kLength2 := mat2Dims.3

        -- check that the dimensions are the same
        (^(iLength1 = iLength2) or ^(jLength1 = jLength2) or ^(kLength1 = kLength2))_
         => error "error the matrices are different sizes"

        sum : R
        row1 : (PA R) := new(kLength1,0$R)$(PA R)
        row2 : (PA PA R) := new(jLength1,copy(row1)$(PA R))$(PA PA R)
        row3 : (PA PA PA R) := new(iLength1,copy(row2)$(PA PA R))$(PA PA PA R)

        for i in 1..iLength1 repeat
          for j in 1..jLength1 repeat
            for k in 1..kLength1 repeat
              sum := (elt(mat1,i,j,k)::R +$R_
                      elt(mat2,i,j,k)::R)
              setelt(row1,k-1,sum)$(PA R)
            setelt(row2,j-1,copy(row1)$(PA R))$(PA PA R)
          setelt(row3,i-1,copy(row2)$(PA PA R))$(PA PA PA R)

        resultMatrix := (row3 pretend $)

        resultMatrix

    construct(listRep : L L L R) : $ ==

      (#listRep)$(L L L R) = 0 => error "empty list"
      (#(listRep.1))$(L L R) = 0 => error "empty list"
      (#((listRep.1).1))$(L R) = 0 => error "empty list"
      iLength := (#listRep)$(L L L R)
      jLength := (#(listRep.1))$(L L R)
      kLength := (#((listRep.1).1))$(L R)

      --first check that the matrix is in the correct form
      for subList in listRep repeat
        ^((#subList)$(L L R) = jLength) => error_
 "can not have an irregular shaped matrix"
        for subSubList in subList repeat
          ^((#(subSubList))$(L R) = kLength) => error_
 "can not have an irregular shaped matrix"

      row1 : (PA R) := new(kLength,((listRep.1).1).1)$(PA R)
      row2 : (PA PA R) := new(jLength,copy(row1)$(PA R))$(PA PA R)
      row3 : (PA PA PA R) := new(iLength,copy(row2)$(PA PA R))$(PA PA PA R)

      for i in 1..iLength repeat
        for j in 1..jLength repeat
          for k in 1..kLength repeat
```

```
            element := elt(elt(elt(listRep,i)$(L L L R),j)$(L L R),k)$(L R)
            setelt(row1,k-1,element)$(PA R)
          setelt(row2,j-1,copy(row1)$(PA R))$(PA PA R)
        setelt(row3,i-1,copy(row2)$(PA PA R))$(PA PA PA R)

      resultMatrix := (row3 pretend $)

      resultMatrix
```

———-

— **M3D.dotabb** —

```
"M3D" [color="#88FF44",href="bookvol10.3.pdf#nameddest=M3D"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"M3D" -> "ALIST"
```

———-

21.8 domain VIEW3D ThreeDimensionalViewport

— **ThreeDimensionalViewport.input** —

```
)set break resume
)sys rm -f ThreeDimensionalViewport.output
)spool ThreeDimensionalViewport.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ThreeDimensionalViewport
--R
--R ThreeDimensionalViewport  is a domain constructor
--R Abbreviation for ThreeDimensionalViewport is VIEW3D
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for VIEW3D
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               axes : (%,String) -> Void
--R clipSurface : (%,String) -> Void     close : % -> Void
--R coerce : % -> OutputForm             controlPanel : (%,String) -> Void
--R diagonals : (%,String) -> Void       drawStyle : (%,String) -> Void
--R eyeDistance : (%,Float) -> Void      hash : % -> SingleInteger
```

```
--R hitherPlane : (%,Float) -> Void       intensity : (%,Float) -> Void
--R key : % -> Integer                    latex : % -> String
--R makeViewport3D : % -> %               options : % -> List(DrawOption)
--R perspective : (%,String) -> Void      reset : % -> Void
--R rotate : (%,Float,Float) -> Void      showRegion : (%,String) -> Void
--R title : (%,String) -> Void            viewDeltaXDefault : Float -> Float
--R viewDeltaXDefault : () -> Float       viewDeltaYDefault : Float -> Float
--R viewDeltaYDefault : () -> Float       viewPhiDefault : Float -> Float
--R viewPhiDefault : () -> Float          viewThetaDefault : Float -> Float
--R viewThetaDefault : () -> Float        viewZoomDefault : Float -> Float
--R viewZoomDefault : () -> Float         viewport3D : () -> %
--R write : (%,String) -> String          zoom : (%,Float) -> Void
--R ?~=? : (%,%) -> Boolean
--R colorDef : (%,Color,Color) -> Void
--R dimensions : (%,NonNegativeInteger,NonNegativeInteger,PositiveInteger,PositiveInteger) -> Vo
--R lighting : (%,Float,Float,Float) -> Void
--R makeViewport3D : (ThreeSpace(DoubleFloat),List(DrawOption)) -> %
--R makeViewport3D : (ThreeSpace(DoubleFloat),String) -> %
--R modifyPointData : (%,NonNegativeInteger,Point(DoubleFloat)) -> Void
--R move : (%,NonNegativeInteger,NonNegativeInteger) -> Void
--R options : (%,List(DrawOption)) -> %
--R outlineRender : (%,String) -> Void
--R resize : (%,PositiveInteger,PositiveInteger) -> Void
--R rotate : (%,Integer,Integer) -> Void
--R showClipRegion : (%,String) -> Void
--R subspace : (%,ThreeSpace(DoubleFloat)) -> %
--R subspace : % -> ThreeSpace(DoubleFloat)
--R translate : (%,Float,Float) -> Void
--R viewpoint : (%,Float,Float,Float) -> Void
--R viewpoint : (%,Float,Float) -> Void
--R viewpoint : (%,Integer,Integer,Float,Float,Float) -> Void
--R viewpoint : (%,Record(theta: DoubleFloat,phi: DoubleFloat,scale: DoubleFloat,scaleX: DoubleF
--R viewpoint : % -> Record(theta: DoubleFloat,phi: DoubleFloat,scale: DoubleFloat,scaleX: Doubl
--R viewpoint : (%,Float,Float,Float,Float,Float) -> Void
--R write : (%,String,List(String)) -> String
--R write : (%,String,String) -> String
--R zoom : (%,Float,Float,Float) -> Void
--R
--E 1

)spool
)lisp (bye)
```

———-


— ThreeDimensionalViewport.help —

```
=====================================================================
ThreeDimensionalViewport examples
```

```
================================================================================

See Also:
o )show ThreeDimensionalViewport
```

21.8.1 ThreeDimensionalViewport (VIEW3D)



Exports:

axes	clipSurface	colorDef	close	coerce
controlPanel	diagonals	dimensions	drawStyle	eyeDistance
hash	hitherPlane	intensity	key	latex
lighting	makeViewport3D	modifyPointData	move	options
outlineRender	perspective	reset	resize	rotate
showClipRegion	showRegion	subspace	title	translate
viewDeltaXDefault	viewDeltaYDefault	viewPhiDefault	viewpoint	viewThetaDefault
viewZoomDefault	viewport3D	write	zoom	?=?
?~=?				

— domain VIEW3D ThreeDimensionalViewport —

```
)abbrev domain VIEW3D ThreeDimensionalViewport
++ Author: Jim Wen
++ Date Created: 28 April 1989
++ Date Last Updated: 2 November 1991, Jim Wen
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ ThreeDimensionalViewport creates viewports to display graphs
```

```
ThreeDimensionalViewport(): Exports == Implementation where
  VIEW    ==> VIEWPORTSERVER$Lisp
  sendI   ==> SOCK_-SEND_-INT
  sendSF  ==> SOCK_-SEND_-FLOAT
  sendSTR ==> SOCK_-SEND_-STRING
  getI    ==> SOCK_-GET_-INT
  getSF   ==> SOCK_-GET_-FLOAT

  typeVIEW3D   ==> 1$I
  typeVIEWTube ==> 4

  makeVIEW3D ==> (-1)$SingleInteger

  I   ==> Integer
  PI  ==> PositiveInteger
  NNI ==> NonNegativeInteger
  XY  ==> Record( X:I, Y:I )
  XYP ==> Record( X:PI, Y:PI )
  XYNN ==> Record( X:NNI, Y:NNI )
  SF  ==> DoubleFloat
  F   ==> Float
  L   ==> List
  Pt ==> ColoredThreeDimensionalPoint
  SEG ==> Segment
  S   ==> String
  E   ==> OutputForm
  PLOT3D ==> Plot3D
  TUBE   ==> TubePlot
  V   ==> Record( theta:SF, phi:SF, scale:SF, scaleX:SF, scaleY:SF, scaleZ:SF, deltaX:SF, deltaY
  H   ==> Record( hueOffset:I, hueNumber:I)
  FLAG   ==> Record( showCP:I, style:I, axesOn:I, diagonalsOn:I, outlineRenderOn:I, showRegionFi
  FR  ==> Record( fn:Fn2, fc: FnU, xmin:SF, xmax:SF, ymin:SF, ymax:SF, xnum:I, ynum:I )
  FParamR ==> Record( theTube:TUBE )
  LR  ==> Record( lightX:SF, lightY:SF, lightZ:SF, lightTheta:SF, lightPhi:SF , translucence:SF)
  UFR ==> Union(FR,FParamR,"undefined")
  PR  ==> Record( perspectiveField:I, eyeDistance:SF, hitherPlane:SF)
  VR  ==> Record( clipXMin:SF, clipXMax:SF, clipYMin:SF, clipYMax:SF, clipZMin:SF, clipZMax:SF,
  C   ==> Color()
  B   ==> Boolean
  POINT ==> Point(SF)
  SUBSPACE ==> SubSpace(3,SF)
  SPACE3 ==> ThreeSpace(SF)
  DROP ==> DrawOption
  COORDSYS ==> CoordinateSystems(SF)

    -- the below macros correspond to the ones in include/actions.h
  ROTATE       ==> 0$I  -- rotate      in actions.h
  ZOOM         ==> 1$I  -- zoom        in actions.h
  TRANSLATE    ==> 2    -- translate   in actions.h
```

```
  rendered     ==> 3    -- render      in actions.h
  hideControl  ==> 4
  closeAll     ==> 5
  axesOnOff    ==> 6
  opaque       ==> 7    -- opaqueMesh  in action.h
  contour      ==> 24
  RESET        ==> 8
  wireMesh     ==> 9    -- transparent in actions.h
  region3D     ==> 12
  smooth       ==> 22
  diagOnOff    ==> 26
  outlineOnOff ==> 13
  zoomx        ==> 14
  zoomy        ==> 15
  zoomz        ==> 16
  perspectiveOnOff ==> 27
  clipRegionOnOff ==> 66
  clipSurfaceOnOff ==> 67

  SPADBUTTONPRESS ==> 100
  COLORDEF        ==> 101
  MOVE            ==> 102
  RESIZE          ==> 103
  TITLE           ==> 104
  lightDef        ==> 108
  translucenceDef ==> 109
  writeView       ==> 110
  eyeDistanceData ==> 111
  modifyPOINT     ==> 114
--  printViewport   ==> 115
  hitherPlaneData ==> 116
  queryVIEWPOINT  ==> 117
  changeVIEWPOINT ==> 118

  noControl ==> 0$I

  yes       ==> 1$I
  no        ==> 0$I

  EYED      ==> 500::SF  -- see draw.h, should be the same(?) as clipOffset
  HITHER    ==> (-250)::SF   -- see process.h in view3D/ (not yet passed to viewman)

  openTube  ==> 1$I
  closedTube ==> 0$I

  fun2Var3D  ==> "   Three Dimensional Viewport: Function of Two Variables"
  para1Var3D ==> "   Three Dimensional Viewport: Parametric Curve of One Variable"
  undef3D    ==> "   Three Dimensional Viewport: No function defined for this viewport yet"

  Exports ==> SetCategory with
```

```
viewThetaDefault      : ()                                        -> F
  ++ viewThetaDefault() returns the current default longitudinal
  ++ view angle in radians.
viewThetaDefault      : F                                         -> F
  ++ viewThetaDefault(t) sets the current default longitudinal
  ++ view angle in radians to the value t and returns t.
viewPhiDefault        : ()                                        -> F
  ++ viewPhiDefault() returns the current default latitudinal
  ++ view angle in radians.
viewPhiDefault        : F                                         -> F
  ++ viewPhiDefault(p) sets the current default latitudinal
  ++ view angle in radians to the value p and returns p.
viewZoomDefault       : ()                                        -> F
  ++ viewZoomDefault() returns the current default graph scaling
  ++ value.
viewZoomDefault       : F                                         -> F
  ++ viewZoomDefault(s) sets the current default graph scaling
  ++ value to s and returns s.
viewDeltaXDefault     : ()                                        -> F
  ++ viewDeltaXDefault() returns the current default horizontal
  ++ offset from the center of the viewport window.
viewDeltaXDefault     : F                                         -> F
  ++ viewDeltaXDefault(dx) sets the current default horizontal
  ++ offset from the center of the viewport window to be \spad{dx}
  ++ and returns \spad{dx}.
viewDeltaYDefault     : ()                                        -> F
  ++ viewDeltaYDefault() returns the current default vertical
  ++ offset from the center of the viewport window.
viewDeltaYDefault     : F                                         -> F
  ++ viewDeltaYDefault(dy) sets the current default vertical
  ++ offset from the center of the viewport window to be \spad{dy}
  ++ and returns \spad{dy}.
viewport3D            : ()                                        -> %
  ++ viewport3D() returns an undefined three-dimensional viewport
  ++ of the domain \spadtype{ThreeDimensionalViewport} whose
  ++ contents are empty.
makeViewport3D        : %                                         -> %
  ++ makeViewport3D(v) takes the given three-dimensional viewport,
  ++ v, of the domain \spadtype{ThreeDimensionalViewport} and
  ++ displays a viewport window on the screen which contains
  ++ the contents of v.
makeViewport3D        : (SPACE3,S)                                -> %
  ++ makeViewport3D(sp,s) takes the given space, \spad{sp} which is
  ++ of the domain \spadtype{ThreeSpace} and displays a viewport
  ++ window on the screen which contains the contents of \spad{sp},
  ++ and whose title is given by s.
makeViewport3D        : (SPACE3,L DROP)                           -> %
  ++ makeViewport3D(sp,lopt) takes the given space, \spad{sp} which is
  ++ of the domain \spadtype{ThreeSpace} and displays a viewport
  ++ window on the screen which contains the contents of \spad{sp},
```

```
  ++ and whose draw options are indicated by the list \spad{lopt}, which
  ++ is a list of options from the domain \spad{DrawOption}.
subspace              : %                                    -> SPACE3
  ++ subspace(v) returns the contents of the viewport v, which is
  ++ of the domain \spadtype{ThreeDimensionalViewport}, as a subspace
  ++ of the domain \spad{ThreeSpace}.
subspace              : (%,SPACE3)                           -> %
  ++ subspace(v,sp) places the contents of the viewport v, which is
  ++ of the domain \spadtype{ThreeDimensionalViewport}, in the subspace
  ++ \spad{sp}, which is of the domain \spad{ThreeSpace}.
modifyPointData       : (%,NNI,POINT)                        -> Void
  ++ modifyPointData(v,ind,pt) takes the viewport, v, which is of the
  ++ domain \spadtype{ThreeDimensionalViewport}, and places the data
  ++ point, \spad{pt} into the list of points database of v at the index
  ++ location given by \spad{ind}.
options               : %                                    -> L DROP
  ++ options(v) takes the viewport, v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport} and returns a list of all
  ++ the draw options from the domain \spad{DrawOption} which are
  ++ being used by v.
options               : (%,L DROP)                           -> %
  ++ options(v,lopt) takes the viewport, v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport} and sets the draw options
  ++ being used by v to those indicated in the list, \spad{lopt},
  ++ which is a list of options from the domain \spad{DrawOption}.
move                  : (%,NNI,NNI)                          -> Void
  ++ move(v,x,y) displays the three-dimensional viewport, v, which
  ++ is of domain \spadtype{ThreeDimensionalViewport}, with the upper
  ++ left-hand corner of the viewport window at the screen
  ++ coordinate position x, y.
resize                : (%,PI,PI)                            -> Void
  ++ resize(v,w,h) displays the three-dimensional viewport, v, which
  ++ is of domain \spadtype{ThreeDimensionalViewport}, with a width
  ++ of w and a height of h, keeping the upper left-hand corner
  ++ position unchanged.
title                 : (%,S)                                -> Void
  ++ title(v,s) changes the title which is shown in the three-dimensional
  ++ viewport window, v of domain \spadtype{ThreeDimensionalViewport}.
dimensions            : (%,NNI,NNI,PI,PI)                    -> Void
  ++ dimensions(v,x,y,width,height) sets the position of the
  ++ upper left-hand corner of the three-dimensional viewport, v,
  ++ which is of domain \spadtype{ThreeDimensionalViewport}, to
  ++ the window coordinate x, y, and sets the dimensions of the
  ++ window to that of \spad{width}, \spad{height}.  The new
  ++ dimensions are not displayed until the function
  ++ \spadfun{makeViewport3D} is executed again for v.
viewpoint             : (%,F,F,F,F,F)                        -> Void
  ++ viewpoint(v,th,phi,s,dx,dy) sets the longitudinal view angle
  ++ to \spad{th} radians, the latitudinal view angle to \spad{phi}
  ++ radians, the scale factor to \spad{s}, the horizontal viewport
```

```
  ++ offset to \spad{dx}, and the vertical viewport offset to \spad{dy}
  ++ for the viewport v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport}.  The new viewpoint position
  ++ is not displayed until the function \spadfun{makeViewport3D} is
  ++ executed again for v.
viewpoint             : (%) -> V
  ++ viewpoint(v) returns the current viewpoint setting of the given
  ++ viewport, v.  This function is useful in the situation where the
  ++ user has created a viewport, proceeded to interact with it via
  ++ the control panel and desires to save the values of the viewpoint
  ++ as the default settings for another viewport to be created using
  ++ the system.
viewpoint : (%,V) -> Void
  ++ viewpoint(v,viewpt) sets the viewpoint for the viewport.  The
  ++ viewport record consists of the latitudal and longitudal angles,
  ++ the zoom factor, the x,y and z scales, and the x and y displacements.
viewpoint             : (%,I,I,F,F,F)                          -> Void
  ++ viewpoint(v,th,phi,s,dx,dy) sets the longitudinal view angle
  ++ to \spad{th} degrees, the latitudinal view angle to \spad{phi}
  ++ degrees, the scale factor to \spad{s}, the horizontal viewport
  ++ offset to \spad{dx}, and the vertical viewport offset to \spad{dy}
  ++ for the viewport v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport}.  The new viewpoint position
  ++ is not displayed until the function \spadfun{makeViewport3D} is
  ++ executed again for v.
viewpoint             : (%,F,F)                                -> Void
  ++ viewpoint(v,th,phi) sets the longitudinal view angle to \spad{th}
  ++ radians and the latitudinal view angle to \spad{phi} radians
  ++ for the viewport v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport}.  The new viewpoint position
  ++ is not displayed until the function \spadfun{makeViewport3D} is
  ++ executed again for v.
viewpoint             : (%,F,F,F)                              -> Void
  ++ viewpoint(v,rotx,roty,rotz) sets the rotation about the x-axis
  ++ to be \spad{rotx} radians, sets the rotation about the y-axis
  ++ to be \spad{roty} radians, and sets the rotation about the z-axis
  ++ to be \spad{rotz} radians, for the viewport v, which is of the
  ++ domain \spadtype{ThreeDimensionalViewport} and displays v with
  ++ the new view position.
controlPanel          : (%,S)                                  -> Void
  ++ controlPanel(v,s) displays the control panel of the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}, if s is "on", or hides
  ++ the control panel if s is "off".
axes                  : (%,S)                                  -> Void
  ++ axes(v,s) displays the axes of the given three-dimensional
  ++ viewport, v, which is of domain \spadtype{ThreeDimensionalViewport},
  ++ if s is "on", or does not display the axes if s is "off".
diagonals             : (%,S)                                  -> Void
  ++ diagonals(v,s) displays the diagonals of the polygon outline
```

```
  ++ showing a triangularized surface instead of a quadrilateral
  ++ surface outline, for the given three-dimensional viewport v
  ++ which is of domain \spadtype{ThreeDimensionalViewport}, if s is
  ++ "on", or does not display the diagonals if s is "off".
outlineRender         : (%,S)                                  -> Void
  ++ outlineRender(v,s) displays the polygon outline showing either
  ++ triangularized surface or a quadrilateral surface outline depending
  ++ on the whether the \spadfun{diagonals} function has been set, for
  ++ the given three-dimensional viewport v which is of domain
  ++ \spadtype{ThreeDimensionalViewport}, if s is "on", or does not
  ++ display the polygon outline if s is "off".
drawStyle             : (%,S)                                  -> Void
  ++ drawStyle(v,s) displays the surface for the given three-dimensional
  ++ viewport v which is of domain \spadtype{ThreeDimensionalViewport}
  ++ in the style of drawing indicated by s.  If s is not a valid
  ++ drawing style the style is wireframe by default.  Possible
  ++ styles are \spad{"shade"}, \spad{"solid"} or \spad{"opaque"},
  ++ \spad{"smooth"}, and \spad{"wireMesh"}.
rotate                : (%,F,F)                                -> Void
  ++ rotate(v,th,phi) rotates the graph to the longitudinal view angle
  ++ \spad{th} radians and the latitudinal view angle \spad{phi} radians
  ++ for the viewport v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport}.
rotate                : (%,I,I)                                -> Void
  ++ rotate(v,th,phi) rotates the graph to the longitudinal view angle
  ++ \spad{th} degrees and the latitudinal view angle \spad{phi} degrees
  ++ for the viewport v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport}.  The new rotation position
  ++ is not displayed until the function \spadfun{makeViewport3D} is
  ++ executed again for v.
zoom                  : (%,F)                                  -> Void
  ++ zoom(v,s) sets the graph scaling factor to s, for the viewport v,
  ++ which is of the domain \spadtype{ThreeDimensionalViewport}.
zoom                  : (%,F,F,F)                              -> Void
  ++ zoom(v,sx,sy,sz) sets the graph scaling factors for the x-coordinate
  ++ axis to \spad{sx}, the y-coordinate axis to \spad{sy} and the
  ++ z-coordinate axis to \spad{sz} for the viewport v, which is of
  ++ the domain \spadtype{ThreeDimensionalViewport}.
translate             : (%,F,F)                                -> Void
  ++ translate(v,dx,dy) sets the horizontal viewport offset to \spad{dx}
  ++ and the vertical viewport offset to \spad{dy}, for the viewport v,
  ++ which is of the domain \spadtype{ThreeDimensionalViewport}.
perspective           : (%,S)                                  -> Void
  ++ perspective(v,s) displays the graph in perspective if s is "on",
  ++ or does not display perspective if s is "off" for the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}.
eyeDistance           : (%,F)                                  -> Void
  ++ eyeDistance(v,d) sets the distance of the observer from the center
  ++ of the graph to d, for the viewport v, which is of the domain
```

```
  ++ \spadtype{ThreeDimensionalViewport}.
hitherPlane           : (%,F)                                    -> Void
  ++ hitherPlane(v,h) sets the hither clipping plane of the graph to h,
  ++ for the viewport v, which is of the domain
  ++ \spadtype{ThreeDimensionalViewport}.
showRegion            : (%,S)                                    -> Void
  ++ showRegion(v,s) displays the bounding box of the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}, if s is "on", or does not
  ++ display the box if s is "off".
showClipRegion        : (%,S)                                    -> Void
  ++ showClipRegion(v,s) displays the clipping region of the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}, if s is "on", or does not
  ++ display the region if s is "off".
clipSurface           : (%,S)                                    -> Void
  ++ clipSurface(v,s) displays the graph with the specified
  ++ clipping region removed if s is "on", or displays the graph
  ++ without clipping implemented if s is "off", for the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}.
lighting              : (%,F,F,F)                                -> Void
  ++ lighting(v,x,y,z) sets the position of the light source to
  ++ the coordinates x, y, and z and displays the graph for the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}.
intensity             : (%,F)                                    -> Void
  ++ intensity(v,i) sets the intensity of the light source to i, for
  ++ the given three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}.
reset                 :  %                                       -> Void
  ++ reset(v) sets the current state of the graph characteristics
  ++ of the given three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}, back to their initial settings.
colorDef              : (%,C,C)                                  -> Void
  ++ colorDef(v,c1,c2) sets the range of colors along the colormap so
  ++ that the lower end of the colormap is defined by \spad{c1} and the
  ++ top end of the colormap is defined by \spad{c2}, for the given
  ++ three-dimensional viewport, v, which is of domain
  ++ \spadtype{ThreeDimensionalViewport}.
write                 : (%,S)                                    -> S
  ++ write(v,s) takes the given three-dimensional viewport, v, which
  ++ is of domain \spadtype{ThreeDimensionalViewport}, and creates
  ++ a directory indicated by s, which contains the graph data
  ++ file for v.
write                 : (%,S,S)                                  -> S
  ++ write(v,s,f) takes the given three-dimensional viewport, v, which
  ++ is of domain \spadtype{ThreeDimensionalViewport}, and creates
  ++ a directory indicated by s, which contains the graph data
  ++ file for v and an optional file type f.
```

```
    write                : (%,S,L S)                                -> S
      ++ write(v,s,lf) takes the given three-dimensional viewport, v, which
      ++ is of domain \spadtype{ThreeDimensionalViewport}, and creates
      ++ a directory indicated by s, which contains the graph data
      ++ file for v and the optional file types indicated by the list lf.
    close                :  %                                       -> Void
      ++ close(v) closes the viewport window of the given
      ++ three-dimensional viewport, v, which is of domain
      ++ \spadtype{ThreeDimensionalViewport}, and terminates the
      ++ corresponding process ID.
    key                  :  %                                       -> I
      ++ key(v) returns the process ID number of the given three-dimensional
      ++ viewport, v, which is of domain \spadtype{ThreeDimensionalViewport}.
--    print                :  %                                        -> Void

  Implementation ==> add
    import Color()
    import ViewDefaultsPackage()
    import Plot3D()
    import TubePlot()
    import POINT
    import PointPackage(SF)
    import SubSpaceComponentProperty()
    import SPACE3
    import MeshCreationRoutinesForThreeDimensions()
    import DrawOptionFunctions0
    import COORDSYS
    import Set(PositiveInteger)

    Rep := Record (key:I, fun:I, _
                   title:S, moveTo:XYNN, size:XYP, viewpoint:V, colors:H, flags:FLAG, _
                   lighting:LR, perspective:PR, volume:VR, _
                   space3D:SPACE3, _
                   optionsField:L DROP)

    degrees := pi()$F / 180.0
    degreesSF := pi()$SF / 180
    defaultTheta  : Reference(SF) := ref(convert(pi()$F/4.0)@SF)
    defaultPhi    : Reference(SF) := ref(convert(-pi()$F/4.0)@SF)
    defaultZoom   : Reference(SF) := ref(convert(1.2)@SF)
    defaultDeltaX : Reference(SF) := ref 0
    defaultDeltaY : Reference(SF) := ref 0


--%Local Functions
    checkViewport (viewport:%):B ==
        -- checks to see if this viewport still exists
        -- by sending the key to the viewport manager and
        -- waiting for its reply after it checks it against
        -- the viewports in its list. a -1 means it doesn't
```

```
      -- exist.
    sendI(VIEW,viewport.key)$Lisp
    i := getI(VIEW)$Lisp
    (i < 0$I) =>
      viewport.key := 0$I
      error "This viewport has already been closed!"
    true

  arcsinTemp(x:SF):SF ==
    -- the asin function doesn't exist in the SF domain currently
    x >= 1  => (pi()$SF / 2)  -- to avoid floating point error from SF (ie 1.0 -> 1.00001)
    x <= -1 => 3 * pi()$SF / 2
    convert(asin(convert(x)@Float)$Float)@SF

  arctanTemp(x:SF):SF == convert(atan(convert(x)@Float)$Float)@SF

  doOptions(v:Rep):Void ==
    v.title := title(v.optionsField,"AXIOM3D")
    st:S := style(v.optionsField,"wireMesh")
    if (st = "shade" or st = "render") then
      v.flags.style := rendered
    else if (st = "solid" or st = "opaque") then
      v.flags.style := opaque
    else if (st = "contour") then
      v.flags.style := contour
    else if (st = "smooth") then
      v.flags.style := smooth
    else v.flags.style := wireMesh
    v.viewpoint := viewpoint(v.optionsField,
      [deref defaultTheta,deref defaultPhi,deref defaultZoom, _
        1$SF,1$SF,1$SF,deref defaultDeltaX, deref defaultDeltaY])
      -- etc - 3D specific stuff...

--%Exported Functions : Default Settings
  viewport3D() ==
    [0,typeVIEW3D,"AXIOM3D",[viewPosDefault().1,viewPosDefault().2], _
     [viewSizeDefault().1,viewSizeDefault().2], _
      [deref defaultTheta,deref defaultPhi,deref defaultZoom, _
        1$SF,1$SF,1$SF,deref defaultDeltaX, deref defaultDeltaY], [0,27], _
          [noControl,wireMesh,yes,no,no,no], [0$SF,0$SF,1$SF,0$SF,0$SF,1$SF], _
            [yes, EYED, HITHER], [0$SF,1$SF,0$SF,1$SF,0$SF,1$SF,no,yes], _
              create3Space()$SPACE3, [] ]

  subspace viewport ==
    viewport.space3D

  subspace(viewport,space) ==
    viewport.space3D := space
    viewport
```

```
options viewport ==
  viewport.optionsField

options(viewport,opts) ==
  viewport.optionsField := opts
  viewport

makeViewport3D(space:SPACE3,Title:S):% ==
  v := viewport3D()
  v.space3D := space
  v.optionsField := [title(Title)]
  makeViewport3D v

makeViewport3D(space:SPACE3,opts:L DROP):% ==
  v := viewport3D()
  v.space3D := space
  v.optionsField := opts
  makeViewport3D v

makeViewport3D viewport ==
  doOptions viewport --local function to extract and assign optional arguments for 3D viewports
  sayBrightly(["   Transmitting data..."::E]$List(E))$Lisp
  transform := coord(viewport.optionsField,cartesian$COORDSYS)$DrawOptionFunctions0
  check(viewport.space3D)
  lpts := lp(viewport.space3D)
  lllipts  := lllip(viewport.space3D)
  llprops := llprop(viewport.space3D)
  lprops  := lprop(viewport.space3D)
    -- check for dimensionality of points
    -- if they are all 4D points, then everything is okay
    -- if they are all 3D points, then pad an extra constant
    -- coordinate for color
    -- if they have varying dimensionalities, give an error
  s := brace()$Set(PI)
  for pt in lpts repeat
    insert_!(dimension pt,s)
  #s > 1 => error "All points should have the same dimension"
  (n := first parts s) < 3 => error "Dimension of points should be greater than 2"
  sendI(VIEW,viewport.fun)$Lisp
  sendI(VIEW,makeVIEW3D)$Lisp
  sendSTR(VIEW,viewport.title)$Lisp
  sendSF(VIEW,viewport.viewpoint.deltaX)$Lisp
  sendSF(VIEW,viewport.viewpoint.deltaY)$Lisp
  sendSF(VIEW,viewport.viewpoint.scale)$Lisp
  sendSF(VIEW,viewport.viewpoint.scaleX)$Lisp
  sendSF(VIEW,viewport.viewpoint.scaleY)$Lisp
  sendSF(VIEW,viewport.viewpoint.scaleZ)$Lisp
  sendSF(VIEW,viewport.viewpoint.theta)$Lisp
  sendSF(VIEW,viewport.viewpoint.phi)$Lisp
  sendI(VIEW,viewport.moveTo.X)$Lisp
```

```
      sendI(VIEW,viewport.moveTo.Y)$Lisp
      sendI(VIEW,viewport.size.X)$Lisp
      sendI(VIEW,viewport.size.Y)$Lisp
      sendI(VIEW,viewport.flags.showCP)$Lisp
      sendI(VIEW,viewport.flags.style)$Lisp
      sendI(VIEW,viewport.flags.axesOn)$Lisp
      sendI(VIEW,viewport.flags.diagonalsOn)$Lisp
      sendI(VIEW,viewport.flags.outlineRenderOn)$Lisp
      sendI(VIEW,viewport.flags.showRegionField)$Lisp  -- add to make3D.c
      sendI(VIEW,viewport.volume.clipRegionField)$Lisp  -- add to make3D.c
      sendI(VIEW,viewport.volume.clipSurfaceField)$Lisp  -- add to make3D.c
      sendI(VIEW,viewport.colors.hueOffset)$Lisp
      sendI(VIEW,viewport.colors.hueNumber)$Lisp
      sendSF(VIEW,viewport.lighting.lightX)$Lisp
      sendSF(VIEW,viewport.lighting.lightY)$Lisp
      sendSF(VIEW,viewport.lighting.lightZ)$Lisp
      sendSF(VIEW,viewport.lighting.translucence)$Lisp
      sendI(VIEW,viewport.perspective.perspectiveField)$Lisp
      sendSF(VIEW,viewport.perspective.eyeDistance)$Lisp
        -- new, crazy points domain stuff
          -- first, send the point data list
      sendI(VIEW,#lpts)$Lisp
      for pt in lpts repeat
        aPoint := transform pt
        sendSF(VIEW,xCoord aPoint)$Lisp
        sendSF(VIEW,yCoord aPoint)$Lisp
        sendSF(VIEW,zCoord aPoint)$Lisp
        n = 3 => sendSF(VIEW,zCoord aPoint)$Lisp
        sendSF(VIEW,color aPoint)$Lisp  -- change to c
          -- now, send the 3d subspace structure
      sendI(VIEW,#lllipts)$Lisp
      for allipts in lllipts for oneprop in lprops for onelprops in llprops repeat
           -- the following is false for f(x,y) and user-defined for [x(t),y(t),z(t)]
           -- this is temporary - until the generalized points stuff gets put in
        sendI(VIEW,(closed? oneprop => yes; no))$Lisp
        sendI(VIEW,(solid? oneprop => yes; no))$Lisp
        sendI(VIEW,#allipts)$Lisp
        for alipts in allipts for tinyprop in onelprops repeat
           -- the following is false for f(x,y) and true for [x(t),y(t),z(t)]
           -- this is temporary -- until the generalized points stuff gets put in
          sendI(VIEW,(closed? tinyprop => yes;no))$Lisp
          sendI(VIEW,(solid? tinyprop => yes;no))$Lisp
          sendI(VIEW,#alipts)$Lisp
          for oneIndexedPoint in alipts repeat
            sendI(VIEW,oneIndexedPoint)$Lisp
      viewport.key := getI(VIEW)$Lisp
      viewport
         -- the key (now set to 0) should be what the viewport returns

    viewThetaDefault    == convert(defaultTheta())@F
```

```
    viewThetaDefault  t ==
      defaultTheta() := convert(t)@SF
      t
    viewPhiDefault      == convert(defaultPhi())@F
    viewPhiDefault    t ==
      defaultPhi() := convert(t)@SF
      t
    viewZoomDefault     == convert(defaultZoom())@F
    viewZoomDefault   t ==
      defaultZoom() := convert(t)@SF
      t
    viewDeltaXDefault   == convert(defaultDeltaX())@F
    viewDeltaXDefault t ==
      defaultDeltaX() := convert(t)@SF
      t
    viewDeltaYDefault   == convert(defaultDeltaY())@F
    viewDeltaYDefault t ==
      defaultDeltaY() := convert(t)@SF
      t

--Exported Functions: Available features for 3D viewports
    lighting(viewport,Xlight,Ylight,Zlight) ==
      viewport.lighting.lightX := convert(Xlight)@SF
      viewport.lighting.lightY := convert(Ylight)@SF
      viewport.lighting.lightZ := convert(Zlight)@SF
      (key(viewport) ^= 0$I) =>
        sendI(VIEW,typeVIEW3D)$Lisp
        sendI(VIEW,lightDef)$Lisp
        checkViewport viewport =>
          sendSF(VIEW,viewport.lighting.lightX)$Lisp
          sendSF(VIEW,viewport.lighting.lightY)$Lisp
          sendSF(VIEW,viewport.lighting.lightZ)$Lisp
          getI(VIEW)$Lisp          -- acknowledge

    axes (viewport,onOff) ==
      if onOff = "on" then viewport.flags.axesOn := yes
      else viewport.flags.axesOn := no
      (key(viewport) ^= 0$I) =>
        sendI(VIEW,typeVIEW3D)$Lisp
        sendI(VIEW,axesOnOff)$Lisp
        checkViewport viewport =>
          sendI(VIEW,viewport.flags.axesOn)$Lisp
          getI(VIEW)$Lisp          -- acknowledge

    diagonals (viewport,onOff) ==
      if onOff = "on" then viewport.flags.diagonalsOn := yes
      else viewport.flags.diagonalsOn := no
      (key(viewport) ^= 0$I) =>
        sendI(VIEW,typeVIEW3D)$Lisp
        sendI(VIEW,diagOnOff)$Lisp
```

```
    checkViewport viewport =>
      sendI(VIEW,viewport.flags.diagonalsOn)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

outlineRender (viewport,onOff) ==
  if onOff = "on" then viewport.flags.outlineRenderOn := yes
  else viewport.flags.outlineRenderOn := no
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,outlineOnOff)$Lisp
    checkViewport viewport =>
      sendI(VIEW,viewport.flags.outlineRenderOn)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

controlPanel (viewport,onOff) ==
  if onOff = "on" then viewport.flags.showCP := yes
  else viewport.flags.showCP := no
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,hideControl)$Lisp
    checkViewport viewport =>
      sendI(VIEW,viewport.flags.showCP)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

drawStyle (viewport,how) ==
  if (how = "shade") then                    -- render
    viewport.flags.style := rendered
  else if (how = "solid") then               -- opaque
    viewport.flags.style := opaque
  else if (how = "contour") then             -- contour
    viewport.flags.style := contour
  else if (how = "smooth") then              -- smooth
    viewport.flags.style := smooth
  else viewport.flags.style := wireMesh
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,viewport.flags.style)$Lisp
    checkViewport viewport =>
      getI(VIEW)$Lisp          -- acknowledge

reset viewport ==
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,SPADBUTTONPRESS)$Lisp
    checkViewport viewport =>
      sendI(VIEW,RESET)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

close viewport ==
  (key(viewport) ^= 0$I) =>
```

```
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,closeAll)$Lisp
      checkViewport viewport =>
        getI(VIEW)$Lisp          -- acknowledge
        viewport.key := 0$I

  viewpoint (viewport:%):V ==
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,queryVIEWPOINT)$Lisp
      checkViewport viewport =>
        deltaX_sf : SF := getSF(VIEW)$Lisp
        deltaY_sf : SF := getSF(VIEW)$Lisp
        scale_sf  : SF := getSF(VIEW)$Lisp
        scaleX_sf : SF := getSF(VIEW)$Lisp
        scaleY_sf : SF := getSF(VIEW)$Lisp
        scaleZ_sf : SF := getSF(VIEW)$Lisp
        theta_sf  : SF := getSF(VIEW)$Lisp
        phi_sf    : SF := getSF(VIEW)$Lisp
        getI(VIEW)$Lisp          -- acknowledge
        viewport.viewpoint :=
          [ theta_sf, phi_sf, scale_sf, scaleX_sf, scaleY_sf, scaleZ_sf,
            deltaX_sf, deltaY_sf ]
      viewport.viewpoint

  viewpoint (viewport:%, viewpt:V):Void ==
    viewport.viewpoint := viewpt
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,changeVIEWPOINT)$Lisp
      checkViewport viewport =>
        sendSF(VIEW,viewport.viewpoint.deltaX)$Lisp
        sendSF(VIEW,viewport.viewpoint.deltaY)$Lisp
        sendSF(VIEW,viewport.viewpoint.scale)$Lisp
        sendSF(VIEW,viewport.viewpoint.scaleX)$Lisp
        sendSF(VIEW,viewport.viewpoint.scaleY)$Lisp
        sendSF(VIEW,viewport.viewpoint.scaleZ)$Lisp
        sendSF(VIEW,viewport.viewpoint.theta)$Lisp
        sendSF(VIEW,viewport.viewpoint.phi)$Lisp
        getI(VIEW)$Lisp          -- acknowledge


  viewpoint (viewport:%,Theta:F,Phi:F,Scale:F,DeltaX:F,DeltaY:F):Void ==
    viewport.viewpoint :=
      [convert(Theta)@SF,convert(Phi)@SF,convert(Scale)@SF,1$SF,1$SF,1$SF,convert(DeltaX)@SF,convert(Delta

  viewpoint (viewport:%,Theta:I,Phi:I,Scale:F,DeltaX:F,DeltaY:F):Void ==
    viewport.viewpoint := [convert(Theta)@SF * degreesSF,convert(Phi)@SF * degreesSF,
      convert(Scale)@SF,1$SF,1$SF,1$SF,convert(DeltaX)@SF,convert(DeltaY)@SF]
```

```
viewpoint (viewport:%,Theta:F,Phi:F):Void ==
  viewport.viewpoint.theta := convert(Theta)@SF * degreesSF
  viewport.viewpoint.phi   := convert(Phi)@SF * degreesSF

viewpoint (viewport:%,X:F,Y:F,Z:F):Void ==
  Theta : F
  Phi : F
  if (X=0$F) and (Y=0$F) then
    Theta := 0$F
    if (Z>=0$F) then
      Phi := 0$F
    else
      Phi := 180.0
  else
    Theta := asin(Y/(R := sqrt(X*X+Y*Y)))
    if (Z=0$F) then
      Phi := 90.0
    else
      Phi := atan(Z/R)
  rotate(viewport, Theta * degrees, Phi * degrees)

title (viewport,Title) ==
  viewport.title := Title
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,TITLE)$Lisp
    checkViewport viewport =>
      sendSTR(VIEW,Title)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

colorDef (viewport,HueOffset,HueNumber) ==
  viewport.colors := [h := (hue HueOffset),(hue HueNumber) - h]
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,COLORDEF)$Lisp
    checkViewport viewport =>
      sendI(VIEW,hue HueOffset)$Lisp
      sendI(VIEW,hue HueNumber)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

dimensions (viewport,ViewX,ViewY,ViewWidth,ViewHeight) ==
  viewport.moveTo := [ViewX,ViewY]
  viewport.size   := [ViewWidth,ViewHeight]

move(viewport,xLoc,yLoc) ==
  viewport.moveTo := [xLoc,yLoc]
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,MOVE)$Lisp
    checkViewport viewport =>
```

```
      sendI(VIEW,xLoc)$Lisp
      sendI(VIEW,yLoc)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

resize(viewport,xSize,ySize) ==
  viewport.size := [xSize,ySize]
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,RESIZE)$Lisp
    checkViewport viewport =>
      sendI(VIEW,xSize)$Lisp
      sendI(VIEW,ySize)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

coerce viewport ==
  (key(viewport) = 0$I) =>
    hconcat
      ["Closed or Undefined ThreeDimensionalViewport: "::E,
       (viewport.title)::E]
  hconcat ["ThreeDimensionalViewport: "::E, (viewport.title)::E]

key viewport == viewport.key

rotate(viewport:%,Theta:I,Phi:I) ==
  rotate(viewport,Theta::F * degrees,Phi::F * degrees)

rotate(viewport:%,Theta:F,Phi:F) ==
  viewport.viewpoint.theta := convert(Theta)@SF
  viewport.viewpoint.phi   := convert(Phi)@SF
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,ROTATE)$Lisp
    checkViewport viewport =>
      sendSF(VIEW,viewport.viewpoint.theta)$Lisp
      sendSF(VIEW,viewport.viewpoint.phi)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

zoom(viewport:%,Scale:F) ==
  viewport.viewpoint.scale := convert(Scale)@SF
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW3D)$Lisp
    sendI(VIEW,ZOOM)$Lisp
    checkViewport viewport =>
      sendSF(VIEW,viewport.viewpoint.scale)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

zoom(viewport:%,ScaleX:F,ScaleY:F,ScaleZ:F) ==
  viewport.viewpoint.scaleX := convert(ScaleX)@SF
  viewport.viewpoint.scaleY := convert(ScaleY)@SF
  viewport.viewpoint.scaleZ := convert(ScaleZ)@SF
```

```
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,zoomx)$Lisp
      checkViewport viewport =>
        sendSF(VIEW,viewport.viewpoint.scaleX)$Lisp
        sendSF(VIEW,viewport.viewpoint.scaleY)$Lisp
        sendSF(VIEW,viewport.viewpoint.scaleZ)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  translate(viewport,DeltaX,DeltaY) ==
    viewport.viewpoint.deltaX := convert(DeltaX)@SF
    viewport.viewpoint.deltaY := convert(DeltaY)@SF
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,TRANSLATE)$Lisp
      checkViewport viewport =>
        sendSF(VIEW,viewport.viewpoint.deltaX)$Lisp
        sendSF(VIEW,viewport.viewpoint.deltaY)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  intensity(viewport,Amount) ==
    if (Amount < 0$F) or (Amount > 1$F) then
      error "The intensity must be a value between 0 and 1, inclusively."
    viewport.lighting.translucence := convert(Amount)@SF
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,translucenceDef)$Lisp
      checkViewport viewport =>
        sendSF(VIEW,viewport.lighting.translucence)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  write(viewport:%,Filename:S,aThingToWrite:S) ==
    write(viewport,Filename,[aThingToWrite])

  write(viewport,Filename) ==
    write(viewport,Filename,viewWriteDefault())

  write(viewport:%,Filename:S,thingsToWrite:L S) ==
    stringToSend : S := ""
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,writeView)$Lisp
      checkViewport viewport =>
        sendSTR(VIEW,Filename)$Lisp
        m := minIndex(avail := viewWriteAvailable())
        for aTypeOfFile in thingsToWrite repeat
          if (writeTypeInt:= position(upperCase aTypeOfFile,avail)-m) < 0 then
            sayBrightly(["  > "::E,(concat(aTypeOfFile, _
              " is not a valid file type for writing a 3D viewport"))::E]$List(E))$Lisp
          else
```

```
            sendI(VIEW,writeTypeInt+(1$I))$Lisp
        sendI(VIEW,0$I)$Lisp     -- no more types of things to write
        getI(VIEW)$Lisp          -- acknowledge
        Filename

  perspective (viewport,onOff) ==
    if onOff = "on" then viewport.perspective.perspectiveField := yes
    else viewport.perspective.perspectiveField := no
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,perspectiveOnOff)$Lisp
      checkViewport viewport =>
        sendI(VIEW,viewport.perspective.perspectiveField)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  showRegion (viewport,onOff) ==
    if onOff = "on" then viewport.flags.showRegionField := yes
    else viewport.flags.showRegionField := no
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,region3D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,viewport.flags.showRegionField)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  showClipRegion (viewport,onOff) ==
    if onOff = "on" then viewport.volume.clipRegionField := yes
    else viewport.volume.clipRegionField := no
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,clipRegionOnOff)$Lisp
      checkViewport viewport =>
        sendI(VIEW,viewport.volume.clipRegionField)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  clipSurface (viewport,onOff) ==
    if onOff = "on" then viewport.volume.clipSurfaceField := yes
    else viewport.volume.clipSurfaceField := no
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,clipSurfaceOnOff)$Lisp
      checkViewport viewport =>
        sendI(VIEW,viewport.volume.clipSurfaceField)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  eyeDistance(viewport:%,EyeDistance:F) ==
    viewport.perspective.eyeDistance := convert(EyeDistance)@SF
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW3D)$Lisp
      sendI(VIEW,eyeDistanceData)$Lisp
```

```
        checkViewport viewport =>
          sendSF(VIEW,viewport.perspective.eyeDistance)$Lisp
          getI(VIEW)$Lisp          -- acknowledge

    hitherPlane(viewport:%,HitherPlane:F) ==
      viewport.perspective.hitherPlane := convert(HitherPlane)@SF
      (key(viewport) ^= 0$I) =>
        sendI(VIEW,typeVIEW3D)$Lisp
        sendI(VIEW,hitherPlaneData)$Lisp
        checkViewport viewport =>
          sendSF(VIEW,viewport.perspective.hitherPlane)$Lisp
          getI(VIEW)$Lisp          -- acknowledge

    modifyPointData(viewport,anIndex,aPoint) ==
      (n := dimension aPoint) < 3 => error "The point should have dimension of at least 3"
      viewport.space3D := modifyPointData(viewport.space3D,anIndex,aPoint)
      (key(viewport) ^= 0$I) =>
        sendI(VIEW,typeVIEW3D)$Lisp
        sendI(VIEW,modifyPOINT)$Lisp
        checkViewport viewport =>
          sendI(VIEW,anIndex)$Lisp
          sendSF(VIEW,xCoord aPoint)$Lisp
          sendSF(VIEW,yCoord aPoint)$Lisp
          sendSF(VIEW,zCoord aPoint)$Lisp
          if (n = 3) then sendSF(VIEW,convert(0.5)@SF)$Lisp
          else sendSF(VIEW,color aPoint)$Lisp
          getI(VIEW)$Lisp          -- acknowledge

--    print viewport ==
--      (key(viewport) ^= 0$I) =>
--        sendI(VIEW,typeVIEW3D)$Lisp
--        sendI(VIEW,printViewport)$Lisp
--        checkViewport viewport =>
--          getI(VIEW)$Lisp          -- acknowledge
```

———-

— VIEW3D.dotabb —

```
"VIEW3D" [color="#88FF44",href="bookvol10.3.pdf#nameddest=VIEW3D"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"VIEW3D" -> "FSAGG"
```

———-

21.9 domain SPACE3 ThreeSpace

— ThreeSpace.input —

```
)set break resume
)sys rm -f ThreeSpace.output
)spool ThreeSpace.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show ThreeSpace
--R
--R ThreeSpace(R: Ring)  is a domain constructor
--R Abbreviation for ThreeSpace is SPACE3
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for SPACE3
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean                check : % -> %
--R closedCurve : % -> List(Point(R))     closedCurve : List(Point(R)) -> %
--R closedCurve? : % -> Boolean           coerce : % -> OutputForm
--R components : % -> List(%)             composite : List(%) -> %
--R composites : % -> List(%)             copy : % -> %
--R create3Space : SubSpace(3,R) -> %     create3Space : () -> %
--R curve : % -> List(Point(R))           curve : List(Point(R)) -> %
--R curve : (%,List(List(R))) -> %        curve : (%,List(Point(R))) -> %
--R curve? : % -> Boolean                 hash : % -> SingleInteger
--R latex : % -> String                   lp : % -> List(Point(R))
--R merge : (%,%) -> %                    merge : List(%) -> %
--R mesh : % -> List(List(Point(R)))      mesh : List(List(Point(R))) -> %
--R mesh? : % -> Boolean                  point : % -> Point(R)
--R point : Point(R) -> %                 point : (%,List(R)) -> %
--R point : (%,Point(R)) -> %             point? : % -> Boolean
--R polygon : % -> List(Point(R))         polygon : List(Point(R)) -> %
--R polygon : (%,List(List(R))) -> %      polygon? : % -> Boolean
--R subspace : % -> SubSpace(3,R)         ?~=? : (%,%) -> Boolean
--R closedCurve : (%,List(List(R))) -> %
--R closedCurve : (%,List(Point(R))) -> %
--R enterPointData : (%,List(Point(R))) -> NonNegativeInteger
--R lllip : % -> List(List(List(NonNegativeInteger)))
--R lllp : % -> List(List(List(Point(R))))
--R llprop : % -> List(List(SubSpaceComponentProperty))
--R lprop : % -> List(SubSpaceComponentProperty)
--R mesh : (List(List(Point(R))),Boolean,Boolean) -> %
--R mesh : (%,List(List(List(R))),Boolean,Boolean) -> %
--R mesh : (%,List(List(Point(R))),Boolean,Boolean) -> %
```

```
--R mesh : (%,List(List(List(R))),List(SubSpaceComponentProperty),SubSpaceComponentProperty) ->
--R mesh : (%,List(List(Point(R))),List(SubSpaceComponentProperty),SubSpaceComponentProperty) ->
--R modifyPointData : (%,NonNegativeInteger,Point(R)) -> %
--R numberOfComponents : % -> NonNegativeInteger
--R numberOfComposites : % -> NonNegativeInteger
--R objects : % -> Record(points: NonNegativeInteger,curves: NonNegativeInteger,polygons: NonNeg
--R point : (%,NonNegativeInteger) -> %
--R polygon : (%,List(Point(R))) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **ThreeSpace.help** —

```
=====================================================================
ThreeSpace examples
=====================================================================

See Also:
o )show ThreeSpace
```

———-

21.9.1 ThreeSpace (SPACE3)



Exports:

check	closedCurve	closedCurve?	coerce	components
composite	composites	copy	create3Space	curve
curve?	enterPointData	hash	latex	lllip
lllp	llprop	lprop	lp	merge
mesh	mesh?	modifyPointData	numberOfComponents	objects
point	point?	polygon	polygon?	subspace
?=?	?~=?			

— domain SPACE3 ThreeSpace —

```
)abbrev domain SPACE3 ThreeSpace
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ The domain ThreeSpace is used for creating three dimensional
++ objects using functions for defining points, curves, polygons, constructs
++ and the subspaces containing them.

ThreeSpace(R:Ring):Exports == Implementation where
  -- m is the dimension of the point

  I    ==> Integer
  PI   ==> PositiveInteger
  NNI  ==> NonNegativeInteger
  L    ==> List
  B    ==> Boolean
  O    ==> OutputForm
  SUBSPACE ==> SubSpace(3,R)
  POINT  ==> Point(R)
  PROP   ==> SubSpaceComponentProperty()
  REP3D  ==> Record(lp:L POINT,llliPt:L L L NNI, llProp:L L PROP, lProp:L PROP)
  OBJ3D  ==> Record(points:NNI, curves:NNI, polygons:NNI, constructs:NNI)

  Exports ==> ThreeSpaceCategory(R)
  Implementation ==> add
    import COMPPROP
    import POINT
    import SUBSPACE
    import ListFunctions2(List(R),POINT)
    import Set(NNI)

    Rep := Record( subspaceField:SUBSPACE, compositesField:L SUBSPACE, _
```

```
                  rep3DField:REP3D, objectsField:OBJ3D, _
                  converted:B)

--% Local Functions
    convertSpace : % -> %
    convertSpace space ==
      space.converted => space
      space.converted := true
      lllipt : L L L NNI := []
      llprop : L L PROP := []
      lprop : L PROP := []
      for component in children space.subspaceField repeat
        lprop := cons(extractProperty component,lprop)
        tmpllipt : L L NNI := []
        tmplprop : L PROP := []
        for curve in children component repeat
          tmplprop := cons(extractProperty curve,tmplprop)
          tmplipt : L NNI := []
          for point in children curve repeat
            tmplipt := cons(extractIndex point,tmplipt)
          tmpllipt := cons(reverse_! tmplipt,tmpllipt)
        llprop := cons(reverse_! tmplprop, llprop)
        lllipt := cons(reverse_! tmpllipt, lllipt)
      space.rep3DField := [pointData space.subspaceField,
                           reverse_! lllipt,reverse_! llprop,reverse_! lprop]
      space


--% Exported Functions
    polygon(space:%,points:L POINT) ==
      #points < 3 =>
        error "You need at least 3 points to define a polygon"
      pt := addPoint2(space.subspaceField,first points)
      points := rest points
      addPointLast(space.subspaceField, pt, first points, 1)
      for p in rest points repeat
        addPointLast(space.subspaceField, pt, p, 2)
      space.converted := false
      space
    create3Space() == [ new()$SUBSPACE, [], [ [], [], [], [] ], [0,0,0,0], false ]
    create3Space(s) == [ s, [], [ [], [], [], [] ], [0,0,0,0], false ]
    numberOfComponents(space) == #(children((space::Rep).subspaceField))
    numberOfComposites(space) == #((space::Rep).compositesField)
    merge(listOfThreeSpaces) ==
          -- * -- we may want to remove duplicate components when that functionality exists in L
      newspace := create3Space(merge([ts.subspaceField for ts in listOfThreeSpaces]))
--      newspace.compositesField := [for cs in ts.compositesField for ts in listOfThreeSpaces]
      for ts in listOfThreeSpaces repeat
        newspace.compositesField := append(ts.compositesField,newspace.compositesField)
      newspace
```

```
    merge(s1,s2) == merge([s1,s2])
    composite(listOfThreeSpaces) ==
      space := create3Space()
      space.subspaceField := merge [s.subspaceField for s in listOfThreeSpaces]
      space.compositesField := [deepCopy space.subspaceField]
--      for aSpace in listOfThreeSpaces repeat
          -- create a composite (which are supercomponents that group
          -- separate components together) out of all possible components
--        space.compositesField := append(children aSpace.subspaceField,space.compositesField)
      space
    components(space) == [create3Space(s) for s in separate space.subspaceField]
    composites(space) == [create3Space(s) for s in space.compositesField]
    copy(space) ==
      spc := create3Space(deepCopy(space.subspaceField))
      spc.compositesField := [deepCopy s for s in space.compositesField]
      spc

    enterPointData(space,listOfPoints) ==
      for p in listOfPoints repeat
        addPoint(space.subspaceField,p)
      #(pointData space.subspaceField)
    modifyPointData(space,i,p) ==
      modifyPoint(space.subspaceField,i,p)
      space

      -- 3D primitives, each grouped in the following order
      --     xxx?(s)  : query whether the threespace, s, holds an xxx
      --     xxx(s)   : extract xxx from threespace, s
      --     xxx(p)   : create a new three space with xxx, p
      --     xxx(s,p) : add xxx, p, to a three space, s
      --     xxx(s,q) : add an xxx, convertable from q, to a three space, s
      --     xxx(s,i) : add an xxx, the data for xxx being indexed by reference  *** complete this
    point?(space:%) ==
      #(c:=children space.subspaceField) > 1$NNI =>
        error "This ThreeSpace has more than one component"
        -- our 3-space has one component, a list of list of points
      #(kid:=children first c) = 1$NNI => -- the component has one subcomponent (a list of points)
        #(children first kid) = 1$NNI  -- this list of points only has one entry, so it's a point
      false
    point(space:%) ==
      point? space => extractPoint(traverse(space.subspaceField,[1,1,1]::L NNI))
      error "This ThreeSpace holds something other than a single point - try the objects() command"
    point(aPoint:POINT) == point(create3Space(),aPoint)
    point(space:%,aPoint:POINT) ==
      addPoint(space.subspaceField,[],aPoint)
      space.converted := false
      space
    point(space:%,l:L R) ==
      pt := point(l)
      point(space,pt)
```

```
point(space:%,i:NNI) ==
  addPoint(space.subspaceField,[],i)
  space.converted := false
  space

curve?(space:%) ==
  #(c:=children space.subspaceField) > 1$NNI =>
    error "This ThreeSpace has more than one component"
    -- our 3-space has one component, a list of list of points
  #(children first c) = 1$NNI -- there is only one subcomponent, so it's a list of points
curve(space:%) ==
  curve? space =>
    spc := first children first children space.subspaceField
    [extractPoint(s) for s in children spc]
  error "This ThreeSpace holds something other than a curve - try the objects() command"
curve(points:L POINT) == curve(create3Space(),points)
curve(space:%,points:L POINT) ==
  addPoint(space.subspaceField,[],first points)
  path : L NNI := [#(children space.subspaceField),1]
  for p in rest points repeat
    addPoint(space.subspaceField,path,p)
  space.converted := false
  space
curve(space:%,points:L L R) ==
  pts := map(point,points)
  curve(space,pts)

closedCurve?(space:%) ==
  #(c:=children space.subspaceField) > 1$NNI =>
    error "This ThreeSpace has more than one component"
    -- our 3-space has one component, a list of list of points
  #(kid := children first c) = 1$NNI => -- there is one subcomponent => it's a list of point
    extractClosed first kid   -- is it a closed curve?
  false
closedCurve(space:%) ==
  closedCurve? space =>
    spc := first children first children space.subspaceField
      -- get the list of points
    [extractPoint(s) for s in children spc]
      -- for now, we are not repeating points...
  error "This ThreeSpace holds something other than a curve - try the objects() command"
closedCurve(points:L POINT) == closedCurve(create3Space(),points)
closedCurve(space:%,points:L POINT) ==
  addPoint(space.subspaceField,[],first points)
  path : L NNI := [#(children space.subspaceField),1]
  closeComponent(space.subspaceField,path,true)
  for p in rest points repeat
    addPoint(space.subspaceField,path,p)
  space.converted := false
  space
```

```
closedCurve(space:%,points:L L R) ==
  pts := map(point,points)
  closedCurve(space,pts)

polygon?(space:%) ==
  #(c:=children space.subspaceField) > 1$NNI =>
    error "This ThreeSpace has more than one component"
    -- our 3-space has one component, a list of list of points
  #(kid:=children first c) = 2::NNI =>
      -- there are two subcomponents
      -- the convention is to have one point in the first child and to put
      -- the remaining points (2 or more) in the second, and last, child
    #(children first kid) = 1$NNI and #(children second kid) > 2::NNI
  false  -- => returns Void...?
polygon(space:%) ==
  polygon? space =>
    listOfPoints : L POINT :=
      [extractPoint(first children first (cs := children first children space.subspaceField))]
    [extractPoint(s) for s in children second cs]
  error "This ThreeSpace holds something other than a polygon - try the objects() command"
polygon(points:L POINT) == polygon(create3Space(),points)
polygon(space:%,points:L L R) ==
  pts := map(point,points)
  polygon(space,pts)

mesh?(space:%) ==
  #(c:=children space.subspaceField) > 1$NNI =>
    error "This ThreeSpace has more than one component"
    -- our 3-space has one component, a list of list of points
  #(kid:=children first c) > 1$NNI =>
      -- there are two or more subcomponents (list of points)
      -- so this may be a definition of a mesh; if the size
      -- of each list of points is the same and they are all
      -- greater than 1(?) then we have an acceptable mesh
      -- use a set to hold the curve size info: if heterogenous
      -- curve sizes exist, then the set would hold all the sizes;
      -- otherwise it would just have the one element indicating
      -- the sizes for all the curves
      whatSizes := brace()$Set(NNI)
      for eachCurve in kid repeat
        insert_!(#children eachCurve,whatSizes)
      #whatSizes > 1 => error "Mesh defined with curves of different sizes"
      first parts whatSizes < 2 =>
        error "Mesh defined with single point curves (use curve())"
      true
  false
mesh(space:%) ==
  mesh? space =>
    llp : L L POINT := []
    for lpSpace in children first children space.subspaceField repeat
```

```
          llp := cons([extractPoint(s) for s in children lpSpace],llp)
        llp
      error "This ThreeSpace holds something other than a mesh - try the objects() command"
    mesh(points:L L POINT) == mesh(create3Space(),points,false,false)
    mesh(points:L L POINT,prop1:B,prop2:B) == mesh(create3Space(),points,prop1,prop2)
--+ old ones \/
    mesh(space:%,llpoints:L L L R,lprops:L PROP,prop:PROP) ==
      pts := [map(point,points) for points in llpoints]
      mesh(space,pts,lprops,prop)
    mesh(space:%,llp:L L POINT,lprops:L PROP,prop:PROP) ==
      addPoint(space.subspaceField,[],first first llp)
      defineProperty(space.subspaceField,path:L NNI:=[#children space.subspaceField],prop)
      path := append(path,[1])
      defineProperty(space.subspaceField,path,first lprops)
      for p in rest (first llp) repeat
        addPoint(space.subspaceField,path,p)
      for lp in rest llp for aProp in rest lprops for count in 2.. repeat
        addPoint(space.subspaceField,path := [first path],first lp)
        path := append(path,[count])
        defineProperty(space.subspaceField,path,aProp)
        for p in rest lp repeat
          addPoint(space.subspaceField,path,p)
      space.converted := false
      space
--+ old ones /\
    mesh(space:%,llpoints:L L L R,prop1:B,prop2:B) ==
      pts := [map(point,points) for points in llpoints]
      mesh(space,pts,prop1,prop2)
    mesh(space:%,llp:L L POINT,prop1:B,prop2:B) ==
        -- prop2 refers to property of the ends of a surface (list of lists of points)
        -- while prop1 refers to the individual curves (list of points)
        -- ** note we currently use Booleans for closed (rather than a pair
        -- ** of booleans for closed and solid)
      propA : PROP := new()
      close(propA,prop1)
      propB : PROP := new()
      close(propB,prop2)
      addPoint(space.subspaceField,[],first first llp)
      defineProperty(space.subspaceField,path:L NNI:=[#children space.subspaceField],propB)
      path := append(path,[1])
      defineProperty(space.subspaceField,path,propA)
      for p in rest (first llp) repeat
        addPoint(space.subspaceField,path,p)
      for lp in rest llp for count in 2.. repeat
        addPoint(space.subspaceField,path := [first path],first lp)
        path := append(path,[count])
        defineProperty(space.subspaceField,path,propA)
        for p in rest lp repeat
          addPoint(space.subspaceField,path,p)
      space.converted := false
```

```
      space

    lp space ==
      if ^space.converted then space := convertSpace space
      space.rep3DField.lp
    lllip space   ==
      if ^space.converted then space := convertSpace space
      space.rep3DField.llliPt
--    lllp space   ==
--      if ^space.converted then space := convertSpace space
--      space.rep3DField.lllPt
    llprop space ==
      if ^space.converted then space := convertSpace space
      space.rep3DField.llProp
    lprop space  ==
      if ^space.converted then space := convertSpace space
      space.rep3DField.lProp

      -- this function is just to see how this representation really
      -- does work
    objects space ==
      if ^space.converted then space := convertSpace space
      numPts        := 0$NNI
      numCurves     := 0$NNI
      numPolys      := 0$NNI
      numConstructs := 0$NNI
      for component in children space.subspaceField repeat
        #(kid:=children component) = 1 =>
          #(children first kid) = 1 => numPts := numPts + 1
          numCurves := numCurves + 1
        (#kid = 2) and _
          (#children first kid = 1) and _
          (#children first rest kid ^= 1) =>
             numPolys := numPolys + 1
        numConstructs := numConstructs + 1
        -- otherwise, a mathematical surface is assumed
        -- there could also be garbage representation
        -- since there are always more permutations that
        -- we could ever want, so the user should not
        -- fumble around too much with the structure
        -- as other applications need to interpret it
      [numPts,numCurves,numPolys,numConstructs]

    check(s) ==
      ^s.converted => convertSpace s
      s

    subspace(s) == s.subspaceField

    coerce(s) ==
```

```
      if ^s.converted then s := convertSpace s
      hconcat(["3-Space with "::O, _
               (sizo:=#(s.rep3DField.llliPt))::O, _
               (sizo=1=>" component"::O;" components"::O)])
```

———-

— SPACE3.dotabb —

```
"SPACE3" [color="#88FF44",href="bookvol10.3.pdf#nameddest=SPACE3"]
"FSAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FSAGG"]
"SPACE3" -> "FSAGG"
```

———-

21.10 domain TREE Tree

— Tree.input —

```
)set break resume
)sys rm -f Tree.output
)spool Tree.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Tree
--R
--R Tree(S: SetCategory)  is a domain constructor
--R Abbreviation for Tree is TREE
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for TREE
--R
--R------------------------------ Operations --------------------------------
--R children : % -> List(%)               copy : % -> %
--R cyclic? : % -> Boolean                cyclicCopy : % -> %
--R cyclicEntries : % -> List(%)          cyclicEqual? : (%,%) -> Boolean
--R cyclicParents : % -> List(%)          distance : (%,%) -> Integer
--R ?.value : (%,value) -> S              empty : () -> %
--R empty? : % -> Boolean                 eq? : (%,%) -> Boolean
--R leaf? : % -> Boolean                  leaves : % -> List(S)
--R map : ((S -> S),%) -> %               nodes : % -> List(%)
--R sample : () -> %                      tree : S -> %
```

```
--R tree : List(S) -> %                  tree : (S,List(%)) -> %
--R value : % -> S
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R any? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R child? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R count : (S,%) -> NonNegativeInteger if $ has finiteAggregate and S has SETCAT
--R count : ((S -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R eval : (%,List(S),List(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,S,S) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,Equation(S)) -> % if S has EVALAB(S) and S has SETCAT
--R eval : (%,List(Equation(S))) -> % if S has EVALAB(S) and S has SETCAT
--R every? : ((S -> Boolean),%) -> Boolean if $ has finiteAggregate
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map! : ((S -> S),%) -> % if $ has shallowlyMutable
--R member? : (S,%) -> Boolean if $ has finiteAggregate and S has SETCAT
--R members : % -> List(S) if $ has finiteAggregate
--R more? : (%,NonNegativeInteger) -> Boolean
--R node? : (%,%) -> Boolean if S has SETCAT
--R parts : % -> List(S) if $ has finiteAggregate
--R setchildren! : (%,List(%)) -> % if $ has shallowlyMutable
--R setelt : (%,value,S) -> S if $ has shallowlyMutable
--R setvalue! : (%,S) -> S if $ has shallowlyMutable
--R size? : (%,NonNegativeInteger) -> Boolean
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— Tree.help —

```
=====================================================================
Tree examples
=====================================================================

See Also:
o )show Tree
```

———-

21.10.1 Tree (TREE)



See

⇒ "BinaryTree" (BTREE) 3.11.1 on page 294
⇒ "BinarySearchTree" (BSTREE) 3.9.1 on page 287
⇒ "BinaryTournament" (BTOURN) 3.10.1 on page 291
⇒ "BalancedBinaryTree" (BBTREE) 3.1.1 on page 236
⇒ "PendantTree" (PENDTREE) 17.13.1 on page 1911

Exports:

any?	child?	children	coerce	copy
count	cyclic?	cyclicCopy	cyclicEntries	cyclicEqual?
cyclicParents	distance	empty	empty?	eq?
eval	every?	hash	latex	leaf?
leaves	less?	map	map!	member?
members	more?	node?	nodes	parts
sample	setchildren!	setelt	setvalue!	size?
tree	value	#?	?=?	?~=?
?.value				

— domain TREE Tree —

```
)abbrev domain TREE Tree
++ Author:W. H. Burge
++ Date Created:17 Feb 1992
++ Date Last Updated:
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ Examples:
++ References:
++ Description:
++ \spadtype{Tree(S)} is a basic domains of tree structures.
++ Each tree is either empty or else is a node consisting of a value and
++ a list of (sub)trees.
```

```
Tree(S: SetCategory): T==C where
 T== RecursiveAggregate(S) with
     finiteAggregate
     shallowlyMutable
     tree: (S,List %) -> %
       ++ tree(nd,ls) creates a tree with value nd, and children ls.
       ++
       ++X t1:=tree [1,2,3,4]
       ++X tree(5,[t1])

     tree: List S -> %
       ++ tree(ls) creates a tree from a list of elements of s.
       ++
       ++X tree [1,2,3,4]

     tree: S -> %
       ++ tree(nd) creates a tree with value nd, and no children
       ++
       ++X tree 6

     cyclic?: % -> Boolean
       ++ cyclic?(t) tests if t is a cyclic tree.
       ++
       ++X t1:=tree [1,2,3,4]
       ++X cyclic? t1

     cyclicCopy: % -> %
       ++ cyclicCopy(l) makes a copy of a (possibly) cyclic tree l.
       ++
       ++X t1:=tree [1,2,3,4]
       ++X cyclicCopy t1

     cyclicEntries:    % -> List %
       ++ cyclicEntries(t) returns a list of top-level cycles in tree t.
       ++
       ++X t1:=tree [1,2,3,4]
       ++X cyclicEntries t1

     cyclicEqual?: (%, %) -> Boolean
       ++ cyclicEqual?(t1, t2) tests of two cyclic trees have
       ++ the same structure.
       ++
       ++X t1:=tree [1,2,3,4]
       ++X t2:=tree [1,2,3,4]
       ++X cyclicEqual?(t1,t2)

     cyclicParents: % -> List %
       ++ cyclicParents(t) returns a list of cycles that are parents of t.
       ++
```

```
       ++X t1:=tree [1,2,3,4]
       ++X cyclicParents t1

C== add
   cycleTreeMax ==> 5

   Rep := Union(node:Record(value: S, args: List %),empty:"empty")
   t:%
   br:%
   s: S
   ls: List S
   empty? t == t case empty
   empty()  == ["empty"]
   children t ==
     t case empty => error "cannot take the children of an empty tree"
     (t.node.args)@List(%)
   setchildren_!(t,lt) ==
     t case empty => error "cannot set children of an empty tree"
     (t.node.args:=lt;t pretend %)
   setvalue_!(t,s) ==
     t case empty => error "cannot set value of an empty tree"
     (t.node.value:=s;s)
   count(n, t) ==
     t case empty => 0
     i := +/[count(n, c) for c in children t]
     value t = n => i + 1
     i
   count(fn: S -> Boolean, t: %): NonNegativeInteger ==
     t case empty => 0
     i := +/[count(fn, c) for c in children t]
     fn value t => i + 1
     i
   map(fn, t) ==
     t case empty => t
     tree(fn value t,[map(fn, c) for c in children t])
   map_!(fn, t) ==
     t case empty => t
     setvalue_!(t, fn value t)
     for c in children t repeat map_!(fn, c)
   tree(s,lt) == [[s,lt]]
   tree(s) == [[s,[]]]
   tree(ls) ==
     empty? ls => empty()
     tree(first ls, [tree s for s in rest ls])
   value t ==
     t case empty => error "cannot take the value of an empty tree"
     t.node.value
   child?(t1,t2) ==
     empty? t2 => false
     "or"/[t1 = t for t in children t2]
```

```
distance1(t1: %, t2: %): Integer ==
  t1 = t2 => 0
  t2 case empty => -1
  u := [n for t in children t2 | (n := distance1(t1,t)) >= 0]
  #u > 0 => 1 + "min"/u
  -1
distance(t1,t2) ==
  n := distance1(t1, t2)
  n >= 0 => n
  distance1(t2, t1)
node?(t1, t2) ==
  t1 = t2 => true
  t case empty => false
  "or"/[node?(t1, t) for t in children t2]
leaf? t ==
  t case empty => false
  empty? children t
leaves t ==
  t case empty => empty()
  leaf? t => [value t]
  "append"/[leaves c for c in children t]
less? (t, n) == # t < n
more?(t, n) == # t > n
nodes t ==       ---buggy
  t case empty => empty()
  nl := [nodes c for c in children t]
  nl = empty() => [t]
  cons(t,"append"/nl)
size? (t, n) == # t = n
any?(fn, t) ==  ---bug fixed
  t case empty => false
  fn value t or "or"/[any?(fn, c) for c in children t]
every?(fn, t) ==
  t case empty => true
  fn value t and "and"/[every?(fn, c) for c in children t]
member?(n, t) ==
  t case empty => false
  n = value t or "or"/[member?(n, c) for c in children t]
members t == parts t
parts t == --buggy?
  t case empty => empty()
  u := [parts c for c in children t]
  u = empty() => [value t]
  cons(value t,"append"/u)

---Functions that guard against cycles: =, #, copy-------------

-----> =
equal?: (%, %, %, %, Integer) -> Boolean
```

```
t1 = t2 == equal?(t1, t2, t1, t2, 0)

equal?(t1, t2, ot1, ot2, k) ==
  k = cycleTreeMax and (cyclic? ot1 or cyclic? ot2) =>
    error "use cyclicEqual? to test equality on cyclic trees"
  t1 case empty => t2 case empty
  t2 case empty => false
  value t1 = value t2 and (c1 := children t1) = (c2 := children t2) and
    "and"/[equal?(x,y,ot1, ot2,k + 1) for x in c1 for y in c2]

-----> #
treeCount: (%, %, NonNegativeInteger) -> NonNegativeInteger
# t == treeCount(t, t, 0)
treeCount(t, origTree, k) ==
  k = cycleTreeMax and cyclic? origTree =>
    error "# is not defined on cyclic trees"
  t case empty => 0
  1 + +/[treeCount(c, origTree, k + 1) for c in children t]

-----> copy
copy1: (%, %, Integer) -> %
copy t == copy1(t, t, 0)
copy1(t, origTree, k) ==
  k = cycleTreeMax and cyclic? origTree =>
    error "use cyclicCopy to copy a cyclic tree"
  t case empty  => t
  empty? children t => tree value t
  tree(value t, [copy1(x, origTree, k + 1) for x in children t])

-----------Functions that allow cycles---------------
--local utility functions:
eqUnion: (List %, List %) -> List %
eqMember?: (%, List %) -> Boolean
eqMemberIndex: (%, List %, Integer) -> Integer
lastNode: List % -> List %
insert: (%, List %) -> List %

-----> coerce to OutputForm
if S has SetCategory then
  multipleOverbar: (OutputForm, Integer, List %) -> OutputForm
  coerce1: (%, List %, List %) -> OutputForm

  coerce(t:%): OutputForm == coerce1(t, empty()$(List %), cyclicParents t)

  coerce1(t,parents, pl) ==
    t case empty => empty()@List(S)::OutputForm
    eqMember?(t, parents) =>
      multipleOverbar((".")::OutputForm,eqMemberIndex(t, pl,0),pl)
    empty? children t => value t::OutputForm
    nodeForm := (value t)::OutputForm
```

```
      if (k := eqMemberIndex(t, pl, 0)) > 0 then
         nodeForm := multipleOverbar(nodeForm, k, pl)
      prefix(nodeForm,
        [coerce1(br,cons(t,parents),pl) for br in children t])

    multipleOverbar(x, k, pl) ==
      k < 1 => x
      #pl = 1 => overbar x
      s : String := "abcdefghijklmnopqrstuvwxyz"
      c := s.(1 + ((k - 1) rem 26))
      overlabel(c::OutputForm, x)

-----> cyclic?
cyclic2?: (%, List %) -> Boolean

cyclic? t == cyclic2?(t, empty()$(List %))

cyclic2?(x,parents) ==
  empty? x => false
  eqMember?(x, parents) => true
  for y in children x repeat
    cyclic2?(y,cons(x, parents)) => return true
  false

-----> cyclicCopy
cyclicCopy2: (%, List %) -> %
copyCycle2: (%, List %) -> %
copyCycle4: (%, %, %, List %) -> %

cyclicCopy(t) == cyclicCopy2(t, cyclicEntries t)

cyclicCopy2(t, cycles) ==
  eqMember?(t, cycles) => return copyCycle2(t, cycles)
  tree(value t, [cyclicCopy2(c, cycles) for c in children t])

copyCycle2(cycle, cycleList) ==
  newCycle := tree(value cycle, nil)
  setchildren!(newCycle,
    [copyCycle4(c,cycle,newCycle, cycleList) for c in children cycle])
  newCycle

copyCycle4(t, cycle, newCycle, cycleList) ==
  empty? cycle => empty()
  eq?(t, cycle) => newCycle
  eqMember?(t, cycleList) => copyCycle2(t, cycleList)
  tree(value t,
       [copyCycle4(c, cycle, newCycle, cycleList) for c in children t])

-----> cyclicEntries
cyclicEntries3: (%, List %, List %) -> List %
```

```
cyclicEntries(t) == cyclicEntries3(t, empty()$(List %), empty()$(List %))

cyclicEntries3(t, parents, cl) ==
  empty? t => cl
  eqMember?(t, parents) => insert(t, cl)
  parents := cons(t, parents)
  for y in children t repeat
    cl := cyclicEntries3(t, parents, cl)
  cl

-----> cyclicEqual?
cyclicEqual4?: (%, %, List %, List %) -> Boolean

cyclicEqual?(t1, t2) ==
  cp1 := cyclicParents t1
  cp2 := cyclicParents t2
  #cp1 ^= #cp2 or null cp1 => t1 = t2
  cyclicEqual4?(t1, t2, cp1, cp2)

cyclicEqual4?(t1, t2, cp1, cp2) ==
  t1 case empty => t2 case empty
  t2 case empty => false
  0 ^= (k := eqMemberIndex(t1, cp1, 0)) => eq?(t2, cp2 . k)
  value t1 = value t2 and
    "and"/[cyclicEqual4?(x,y,cp1,cp2)
             for x in children t1 for y in children t2]

-----> cyclicParents t
cyclicParents3: (%, List %, List %) -> List %

cyclicParents t == cyclicParents3(t, empty()$(List %), empty()$(List %))

cyclicParents3(x, parents, pl) ==
  empty? x => pl
  eqMember?(x, parents) =>
    cycleMembers := [y for y in parents while not eq?(x,y)]
    eqUnion(cons(x, cycleMembers), pl)
  parents := cons(x, parents)
  for y in children x repeat
    pl := cyclicParents3(y, parents, pl)
  pl

insert(x, l) ==
  eqMember?(x, l) => l
  cons(x, l)

lastNode l ==
  empty? l => error "empty tree has no last node"
  while not empty? rest l repeat l := rest l
```

```
      l

    eqMember?(y,l) ==
      for x in l repeat eq?(x,y) => return true
      false

    eqMemberIndex(x, l, k) ==
      null l => k
      k := k + 1
      eq?(x, first l) => k
      eqMemberIndex(x, rest l, k)

    eqUnion(u, v) ==
      null u => v
      x := first u
      newV :=
        eqMember?(x, v) => v
        cons(x, v)
      eqUnion(rest u, newV)
```

———-

— **TREE.dotabb** —

```
"TREE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TREE"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"TREE" -> "STRING"
```

———-

21.11 domain TUBE TubePlot

— **TubePlot.input** —

```
)set break resume
)sys rm -f TubePlot.output
)spool TubePlot.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show TubePlot
--R
```

```
--R TubePlot(Curve: PlottableSpaceCurveCategory)  is a domain constructor
--R Abbreviation for TubePlot is TUBE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for TUBE
--R
--R------------------------------ Operations ------------------------------
--R closed? : % -> Boolean               getCurve : % -> Curve
--R open? : % -> Boolean
--R listLoops : % -> List(List(Point(DoubleFloat)))
--R setClosed : (%,Boolean) -> Boolean
--R tube : (Curve,List(List(Point(DoubleFloat))),Boolean) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— **TubePlot.help** —

```
========================================================================
TubePlot examples
========================================================================

See Also:
o )show TubePlot
```

———-

21.11.1 TubePlot (TUBE)



Exports:
closed? getCurve listLoops open? setClosed tube

— domain TUBE TubePlot —

```
)abbrev domain TUBE TubePlot
++ Author: Clifton J. Williamson
++ Date Created: Bastille Day 1989
++ Date Last Updated: 5 June 1990
++ Keywords:
++ Examples:
++ Description:
++ Package for constructing tubes around 3-dimensional parametric curves.
++ Domain of tubes around 3-dimensional parametric curves.

TubePlot(Curve): Exports == Implementation where
  Curve : PlottableSpaceCurveCategory
  B   ==> Boolean
  L   ==> List
  Pt  ==> Point DoubleFloat

  Exports ==> with
    getCurve: % -> Curve
      ++ getCurve(t) returns the \spadtype{PlottableSpaceCurveCategory}
      ++ representing the parametric curve of the given tube plot t.
    listLoops: % -> L L Pt
      ++ listLoops(t) returns the list of lists of points, or the 'loops',
      ++ of the given tube plot t.
    closed?: % -> B
      ++ closed?(t) tests whether the given tube plot t is closed.
    open?: % -> B
      ++ open?(t) tests whether the given tube plot t is open.
    setClosed: (%,B) -> B
      ++ setClosed(t,b) declares the given tube plot t to be closed if
      ++ b is true, or if b is false, t is set to be open.
    tube: (Curve,L L Pt,B) -> %
      ++ tube(c,ll,b) creates a tube of the domain \spadtype{TubePlot} from a
      ++ space curve c of the category \spadtype{PlottableSpaceCurveCategory},
      ++ a list of lists of points (loops) ll and a boolean b which if
      ++ true indicates a closed tube, or if false an open tube.

  Implementation ==> add

--% representation

    Rep := Record(parCurve:Curve,loops:L L Pt,closedTube?:B)

    getCurve plot == plot.parCurve

    listLoops plot == plot.loops

    closed? plot == plot.closedTube?
```

```
    open? plot   == not plot.closedTube?

    setClosed(plot,flag) == plot.closedTube? := flag

    tube(curve,ll,b) == [curve,ll,b]
```

———-

— TUBE.dotabb —

```
"TUBE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TUBE"]
"RADCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RADCAT"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"TUBE" -> "FIELD"
"TUBE" -> "RADCAT"
```

———-

21.12 domain TUPLE Tuple

— Tuple.input —

```
)set break resume
)sys rm -f Tuple.output
)spool Tuple.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Tuple
--R
--R Tuple(S: Type)  is a domain constructor
--R Abbreviation for Tuple is TUPLE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for TUPLE
--R
--R------------------------------ Operations ------------------------------
--R coerce : PrimitiveArray(S) -> %       coerce : % -> PrimitiveArray(S)
--R length : % -> NonNegativeInteger
--R ?=? : (%,%) -> Boolean if S has SETCAT
--R coerce : % -> OutputForm if S has SETCAT
--R hash : % -> SingleInteger if S has SETCAT
--R latex : % -> String if S has SETCAT
```

```
--R select : (%,NonNegativeInteger) -> S
--R ?~=? : (%,%) -> Boolean if S has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— **Tuple.help** —

```
====================================================================
Tuple examples
====================================================================

See Also:
o )show Tuple
```

———-

21.12.1 Tuple (TUPLE)



See

⇒ “PrimitiveArray” (PRIMARR) 17.30.1 on page 2075
⇒ “IndexedFlexibleArray” (IFARRAY) 10.10.1 on page 1191
⇒ “FlexibleArray” (FARRAY) 7.14.1 on page 856
⇒ “IndexedOneDimensionalArray” (IARRAY1) 10.13.1 on page 1212
⇒ “OneDimensionalArray” (ARRAY1) 16.3.1 on page 1740

Exports:
coerce hash latex length select ?=? ?~=?

— **domain TUPLE Tuple** —

```
)abbrev domain TUPLE Tuple
++ Author: Mark Botch
++ Description:
++ This domain is used to interface with the interpreter's notion
++ of comma-delimited sequences of values.

Tuple(S:Type): CoercibleTo(PrimitiveArray S) with
  coerce: PrimitiveArray S -> %
   ++ coerce(a) makes a tuple from primitive array a
   ++
   ++X t1:PrimitiveArray(Integer):= [i for i in 1..10]
   ++X t2:=coerce(t1)$Tuple(Integer)

  select: (%, NonNegativeInteger) -> S
   ++ select(x,n) returns the n-th element of tuple x.
   ++ tuples are 0-based
   ++
   ++X t1:PrimitiveArray(Integer):= [i for i in 1..10]
   ++X t2:=coerce(t1)$Tuple(Integer)
   ++X select(t2,3)

  length: % -> NonNegativeInteger
   ++ length(x) returns the number of elements in tuple x
   ++
   ++X t1:PrimitiveArray(Integer):= [i for i in 1..10]
   ++X t2:=coerce(t1)$Tuple(Integer)
   ++X length(t2)

  if S has SetCategory then SetCategory
 == add
  Rep := Record(len : NonNegativeInteger, elts : PrimitiveArray S)

  coerce(x: PrimitiveArray S): %  == [#x, x]
  coerce(x:%): PrimitiveArray(S) == x.elts
  length x == x.len

  select(x, n) ==
    n >= x.len => error "Index out of bounds"
    x.elts.n

  if S has SetCategory then
    x = y == (x.len = y.len) and (x.elts =$PrimitiveArray(S) y.elts)
    coerce(x : %): OutputForm ==
      paren [(x.elts.i)::OutputForm
             for i in minIndex x.elts .. maxIndex x.elts]$List(OutputForm)
```

— **TUPLE.dotabb** —

```
"TUPLE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=TUPLE"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"A1AGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=A1AGG"]
"TUPLE" -> "A1AGG"
"TUPLE" -> "A1AGG-"
```

———-

21.13 domain ARRAY2 TwoDimensionalArray

— **TwoDimensionalArray.input** —

```
)set break resume
)sys rm -f TwoDimensionalArray.output
)spool TwoDimensionalArray.output
)set message test on
)set message auto off
)clear all
--S 1 of 20
arr : ARRAY2 INT := new(5,4,0)
--R
--R
--R        +0  0  0  0+
--R        |          |
--R        |0  0  0  0|
--R        |          |
--R   (1)  |0  0  0  0|
--R        |          |
--R        |0  0  0  0|
--R        |          |
--R        +0  0  0  0+
--R                                          Type: TwoDimensionalArray(Integer)
--E 1

--S 2 of 20
setelt(arr,1,1,17)
--R
--R
--R   (2)  17
--R                                                     Type: PositiveInteger
--E 2

--S 3 of 20
```

```
arr
--R
--R
--R        +17  0  0  0+
--R        |           |
--R        |0   0  0  0|
--R        |           |
--R   (3)  |0   0  0  0|
--R        |           |
--R        |0   0  0  0|
--R        |           |
--R        +0   0  0  0+
--R                                        Type: TwoDimensionalArray(Integer)
--E 3

--S 4 of 20
elt(arr,1,1)
--R
--R
--R   (4)  17
--R                                                   Type: PositiveInteger
--E 4

--S 5 of 20
arr(3,2) := 15
--R
--R
--R   (5)  15
--R                                                   Type: PositiveInteger
--E 5

--S 6 of 20
arr(3,2)
--R
--R
--R   (6)  15
--R                                                   Type: PositiveInteger
--E 6

--S 7 of 20
row(arr,1)
--R
--R
--R   (7)  [17,0,0,0]
--R                                        Type: OneDimensionalArray(Integer)
--E 7

--S 8 of 20
column(arr,1)
--R
```

```
--R
--R   (8)  [17,0,0,0,0]
--R                                                Type: OneDimensionalArray(Integer)
--E 8

--S 9 of 20
nrows(arr)
--R
--R
--R   (9)  5
--R                                                            Type: PositiveInteger
--E 9

--S 10 of 20
ncols(arr)
--R
--R
--R   (10)  4
--R                                                            Type: PositiveInteger
--E 10

--S 11 of 20
map(-,arr)
--R
--R
--R         +- 17   0    0  0+
--R         |                 |
--R         | 0     0    0  0|
--R         |                 |
--R   (11)  | 0    - 15  0  0|
--R         |                 |
--R         | 0     0    0  0|
--R         |                 |
--R         + 0     0    0  0+
--R                                                Type: TwoDimensionalArray(Integer)
--E 11

--S 12 of 20
map((x +-> x + x),arr)
--R
--R
--R         +34  0   0  0+
--R         |             |
--R         |0   0   0  0|
--R         |             |
--R   (12)  |0   30  0  0|
--R         |             |
--R         |0   0   0  0|
--R         |             |
--R         +0   0   0  0+
```

```
--R                                                  Type: TwoDimensionalArray(Integer)
--E 12

--S 13 of 20
arrc := copy(arr)
--R
--R
--R         +17  0   0  0+
--R         |            |
--R         |0   0   0  0|
--R         |            |
--R   (13)  |0   15  0  0|
--R         |            |
--R         |0   0   0  0|
--R         |            |
--R         +0   0   0  0+
--R                                                  Type: TwoDimensionalArray(Integer)
--E 13

--S 14 of 20
map!(-,arrc)
--R
--R
--R         +- 17   0    0  0+
--R         |                |
--R         | 0     0    0  0|
--R         |                |
--R   (14)  | 0    - 15  0  0|
--R         |                |
--R         | 0     0    0  0|
--R         |                |
--R         + 0     0    0  0+
--R                                                  Type: TwoDimensionalArray(Integer)
--E 14

--S 15 of 20
arrc
--R
--R
--R         +- 17   0    0  0+
--R         |                |
--R         | 0     0    0  0|
--R         |                |
--R   (15)  | 0    - 15  0  0|
--R         |                |
--R         | 0     0    0  0|
--R         |                |
--R         + 0     0    0  0+
--R                                                  Type: TwoDimensionalArray(Integer)
--E 15
```

```
--S 16 of 20
arr
--R
--R
--R         +17  0   0  0+
--R         |             |
--R         |0   0   0  0|
--R         |             |
--R   (16)  |0   15  0  0|
--R         |             |
--R         |0   0   0  0|
--R         |             |
--R         +0   0   0  0+
--R                                        Type: TwoDimensionalArray(Integer)
--E 16

--S 17 of 20
member?(17,arr)
--R
--R
--R   (17)  true
--R                                                              Type: Boolean
--E 17

--S 18 of 20
member?(10317,arr)
--R
--R
--R   (18)  false
--R                                                              Type: Boolean
--E 18

--S 19 of 20
count(17,arr)
--R
--R
--R   (19)  1
--R                                                     Type: PositiveInteger
--E 19

--S 20 of 20
count(0,arr)
--R
--R
--R   (20)  18
--R                                                     Type: PositiveInteger
--E 20
)spool
)lisp (bye)
```

———-

— TwoDimensionalArray.help —

```
=====================================================================
TwoDimensionalArray examples
=====================================================================

The TwoDimensionalArray domain is used for storing data in a two
dimensional data structure indexed by row and by column.  Such an
array is a homogeneous data structure in that all the entries of the
array must belong to the same Axiom domain..  Each array has a fixed
number of rows and columns specified by the user and arrays are not
extensible.  In Axiom, the indexing of two-dimensional arrays is
one-based.  This means that both the "first" row of an array and the
"first" column of an array are given the index 1.  Thus, the entry
in the upper left corner of an array is in position (1,1).

The operation new creates an array with a specified number of rows and
columns and fills the components of that array with a specified entry.
The arguments of this operation specify the number of rows, the number
of columns, and the entry.

This creates a five-by-four array of integers, all of whose entries are
zero.

  arr : ARRAY2 INT := new(5,4,0)
        +0  0  0  0+
        |          |
        |0  0  0  0|
        |          |
        |0  0  0  0|
        |          |
        |0  0  0  0|
        |          |
        +0  0  0  0+
                         Type: TwoDimensionalArray Integer

The entries of this array can be set to other integers using setelt.

Issue this to set the element in the upper left corner of this array to 17.

  setelt(arr,1,1,17)
    17
                         Type: PositiveInteger

Now the first element of the array is 17.

  arr
```

```
       +17  0  0  0+
       |           |
       |0   0  0  0|
       |           |
       |0   0  0  0|
       |           |
       |0   0  0  0|
       |           |
       +0   0  0  0+
                        Type: TwoDimensionalArray Integer
```

Likewise, elements of an array are extracted using the operation elt.

```
  elt(arr,1,1)
    17
                        Type: PositiveInteger
```

Another way to use these two operations is as follows. This sets the element in position (3,2) of the array to 15.

```
  arr(3,2) := 15
    15
                        Type: PositiveInteger
```

This extracts the element in position (3,2) of the array.

```
  arr(3,2)
    15
                        Type: PositiveInteger
```

The operations elt and setelt come equipped with an error check which verifies that the indices are in the proper ranges. For example, the above array has five rows and four columns, so if you ask for the entry in position (6,2) with arr(6,2) Axiom displays an error message. If there is no need for an error check, you can call the operations qelt and qsetelt which provide the same functionality but without the error check. Typically, these operations are called in well-tested programs.

The operations row and column extract rows and columns, respectively, and return objects of OneDimensionalArray with the same underlying element type.

```
  row(arr,1)
    [17,0,0,0]
                        Type: OneDimensionalArray Integer

  column(arr,1)
    [17,0,0,0,0]
                        Type: OneDimensionalArray Integer
```

```
You can determine the dimensions of an array by calling the operations
nrows and ncols, which return the number of rows and columns, respectively.

  nrows(arr)
    5
                          Type: PositiveInteger

  ncols(arr)
    4
                          Type: PositiveInteger

To apply an operation to every element of an array, use map.  This
creates a new array.  This expression negates every element.

  map(-,arr)
         +- 17   0    0  0+
         |                 |
         | 0     0    0  0|
         |                 |
         | 0    - 15  0  0|
         |                 |
         | 0     0    0  0|
         |                 |
         + 0     0    0  0+
                          Type: TwoDimensionalArray Integer

This creates an array where all the elements are doubled.

  map((x +-> x + x),arr)
         +34  0   0  0+
         |             |
         |0   0   0  0|
         |             |
         |0   30  0  0|
         |             |
         |0   0   0  0|
         |             |
         +0   0   0  0+
                          Type: TwoDimensionalArray Integer

To change the array destructively, use map instead of map.  If you
need to make a copy of any array, use copy.

  arrc := copy(arr)
         +17  0   0  0+
         |             |
         |0   0   0  0|
         |             |
         |0   15  0  0|
         |             |
```

```
        |0   0   0  0|
        |            |
        +0   0   0  0+
                        Type: TwoDimensionalArray Integer

  map!(-,arrc)
        +- 17   0    0  0+
        |                 |
        | 0     0    0  0|
        |                 |
        | 0    - 15  0  0|
        |                 |
        | 0     0    0  0|
        |                 |
        + 0     0    0  0+
                        Type: TwoDimensionalArray Integer

  arrc
        +- 17   0    0  0+
        |                 |
        | 0     0    0  0|
        |                 |
        | 0    - 15  0  0|
        |                 |
        | 0     0    0  0|
        |                 |
        + 0     0    0  0+
                        Type: TwoDimensionalArray Integer

  arr
        +17  0   0  0+
        |            |
        |0   0   0  0|
        |            |
        |0   15  0  0|
        |            |
        |0   0   0  0|
        |            |
        +0   0   0  0+
                        Type: TwoDimensionalArray Integer

Use member? to see if a given element is in an array.

  member?(17,arr)
    true
                        Type: Boolean

  member?(10317,arr)
    false
                        Type: Boolean
```


```
To see how many times an element appears in an array, use count.

  count(17,arr)
    1
                          Type: PositiveInteger

  count(0,arr)
    18
                          Type: PositiveInteger

See Also:
o )help Matrix
o )help OneDimensionalArray
o )show TwoDimensionalArray
```

21.13.1 TwoDimensionalArray (ARRAY2)



See

⇒ "InnerIndexedTwoDimensionalArray" (IIARRAY2) 10.23.1 on page 1258
⇒ "IndexedTwoDimensionalArray" (IARRAY2) 10.15.1 on page 1225

Exports:

any?	coerce	column	copy	count
elt	empty	empty?	eq?	eval
every?	fill!	hash	latex	less?
map	map!	maxColIndex	maxRowIndex	member?
members	more?	minColIndex	minRowIndex	ncols
new	nrows	parts	qelt	qsetelt!
row	sample	setColumn!	setRow!	setelt
size?	# ?	?=?	?~=?	

— domain ARRAY2 TwoDimensionalArray —

```
)abbrev domain ARRAY2 TwoDimensionalArray
++ Author: Mark Botch
++ Description:
++ A TwoDimensionalArray is a two dimensional array with
++ 1-based indexing for both rows and columns.

TwoDimensionalArray(R):Exports == Implementation where
  R : Type
  Row ==> OneDimensionalArray R
  Col ==> OneDimensionalArray R

  Exports ==> TwoDimensionalArrayCategory(R,Row,Col) with
    shallowlyMutable
      ++ One may destructively alter TwoDimensionalArray's.

  Implementation ==> InnerIndexedTwoDimensionalArray(R,1,1,Row,Col)
```

———-

— ARRAY2.dotabb —

```
"ARRAY2" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ARRAY2"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"ARR2CAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ARR2CAT"]
"ARRAY2" -> "ARR2CAT"
"ARRAY2" -> "A1AGG"
```

———-

21.14 domain VIEW2D TwoDimensionalViewport

— TwoDimensionalViewport.help —

```
==========================================================================
TwoDimensionalViewport examples
==========================================================================

We want to graph x^3 * (a+b*x) on the interval x=-1..1
so we clear out the workspace

We assign values to the constants
```

```
  a:=0.5
    0.5
                                Type: Float
  b:=0.5
    0.5
                                Type: Float
```

We draw the first case of the graph

```
  y1:=draw(x^3*(a+b*x),x=-1..1,title=="2.2.10 explicit")
    TwoDimensionalViewport: "2.2.10 explicit"
                                Type: TwoDimensionalViewport
```

We fetch the graph of the first object

```
  g1:=getGraph(y1,1)
    Graph with 1 point list
                                Type: GraphImage
```

We extract its points

```
  pointLists g1
   [
     [[-1.,0.,1.,3.], [-0.95833333333333337,-1.8336166570216028E-2,1.,3.],
      [-0.91666666666666674,-3.2093942901234518E-2,1.,3.],
      [-0.87500000000000011,-4.18701171875E-2,1.,3.],
      [-0.83333333333333348,-4.8225308641975301E-2,1.,3.],
      [-0.79166666666666685,-5.1683967496141986E-2,1.,3.],
      [-0.75000000000000022,-5.2734375E-2,1.,3.],
      [-0.70833333333333359,-5.1828643422067916E-2,1.,3.],
      [-0.66666666666666696,-4.9382716049382741E-2,1.,3.],
      [-0.62500000000000033,-4.5776367187500042E-2,1.,3.],
      [-0.5833333333333337,-4.1353202160493867E-2,1.,3.],
      [-0.54166666666666707,-3.6420657310956832E-2,1.,3.],
      [-0.50000000000000044,-3.1250000000000056E-2,1.,3.],
      [-0.45833333333333376,-2.6076328607253136E-2,1.,3.],
      [-0.41666666666666707,-2.1098572530864244E-2,1.,3.],
      [-0.37500000000000039,-1.6479492187500042E-2,1.,3.],
      [-0.3333333333333337,-1.2345679012345713E-2,1.,3.],
      [-0.29166666666666702,-8.7875554591049648E-3,1.,3.],
      [-0.25000000000000033,-5.8593750000000208E-3,1.,3.],
      [-0.20833333333333368,-3.5792221257716214E-3,1.,3.],
      [-0.16666666666666702,-1.9290123456790237E-3,1.,3.],
      [-0.12500000000000036,-8.5449218750000705E-4,1.,3.],
      [-8.3333333333333703E-2,-2.6523919753086765E-4,1.,3.],
      [-4.1666666666667039E-2,-3.4661940586420673E-5,1.,3.],
      [-3.7470027081099033E-16,-2.6304013894372334E-47,1.,3.],
      [4.166666666666629E-2,3.7676022376542178E-5,1.,3.],
      [8.3333333333332954E-2,3.1346450617283515E-4,1.,3.],
      [0.12499999999999961,1.0986328124999894E-3,1.,3.],
```

```
      [0.16666666666666627,2.7006172839505972E-3,1.,3.],
      [0.20833333333333293,5.463023244598731E-3,1.,3.],
      [0.24999999999999958,9.765624999999948E-3,1.,3.],
      [0.29166666666666624,1.6024365837191284E-2,1.,3.],
      [0.33333333333333293,2.469135802469126E-2,1.,3.],
      [0.37499999999999961,3.6254882812499882E-2,1.,3.],
      [0.4166666666666663,5.1239390432098617E-2,1.,3.],
      [0.45833333333333298,7.0205500096450435E-2,1.,3.],
      [0.49999999999999967,9.3749999999999792E-2,1.,3.],
      [0.5416666666666663,0.12250584731867258,1.,3.],
      [0.58333333333333293,0.15714216820987617,1.,3.],
      [0.62499999999999956,0.1983642578124995,1.,3.],
      [0.6666666666666619,0.24691358024691298,1.,3.],
      [0.70833333333333282,0.30356776861496837,1.,3.],
      [0.74999999999999944,0.369140624999999,1.,3.],
      [0.79166666666666607,0.44448212046681984,1.,3.],
      [0.8333333333333327,0.530478395061727,1.,3.],
      [0.87499999999999933,0.62805175781249845,1.,3.],
      [0.91666666666666596,0.73816068672839308,1.,3.],
      [0.95833333333333259,0.86179982880015205,1.,3.], [1.,1.,1.,3.]]
    ]
                        Type: List List Point DoubleFloat
```

Now we create a second graph with a changed parameter

```
  b:=1.0
    1.0
                        Type: Float
```

We draw it

```
  y2:=draw(x^3*(a+b*x),x=-1..1)
    TwoDimensionalViewport: "AXIOM2D"
                        Type: TwoDimensionalViewport
```

We fetch this new graph

```
  g2:=getGraph(y2,1)
    Graph with 1 point list
                       Type: GraphImage
```

We get the points from this graph

```
  pointLists g2
   [
     [[-1.,0.5,1.,3.], [-0.95833333333333337,0.40339566454475323,1.,3.],
      [-0.91666666666666674,0.32093942901234584,1.,3.],
      [-0.87500000000000011,0.25122070312500017,1.,3.],
      [-0.83333333333333348,0.19290123456790137,1.,3.],
      [-0.79166666666666685,0.14471510898919768,1.,3.],
```

```
      [-0.75000000000000022,0.10546875000000019,1.,3.],
      [-0.70833333333333359,7.404091917438288E-2,1.,3.],
      [-0.66666666666666696,4.938271604938288E-2,1.,3.],
      [-0.62500000000000033,3.0517578125000125E-2,1.,3.],
      [-0.5833333333333337,1.6541280864197649E-2,1.,3.],
      [-0.54166666666666707,6.6219376929013279E-3,1.,3.],
      [-0.50000000000000044,5.5511151231257827E-17,1.,3.],
      [-0.45833333333333376,-4.011742862654287E-3,1.,3.],
      [-0.41666666666666707,-6.0281635802469057E-3,1.,3.],
      [-0.37500000000000039,-6.5917968750000035E-3,1.,3.],
      [-0.3333333333333337,-6.1728395061728461E-3,1.,3.],
      [-0.29166666666666702,-5.1691502700617377E-3,1.,3.],
      [-0.25000000000000033,-3.9062500000000104E-3,1.,3.],
      [-0.20833333333333368,-2.6373215663580349E-3,1.,3.],
      [-0.16666666666666702,-1.543209876543218E-3,1.,3.],
      [-0.12500000000000036,-7.3242187500000564E-4,1.,3.],
      [-8.3333333333333703E-2,-2.4112654320987957E-4,1.,3.],
      [-4.1666666666667039E-2,-3.315489969135889E-5,1.,3.],
      [-3.7470027081099033E-16,-2.6304013894372324E-47,1.,3.],
      [4.166666666666629E-2,3.9183063271603852E-5,1.,3.],
      [8.3333333333332954E-2,3.3757716049382237E-4,1.,3.],
      [0.12499999999999961,1.2207031249999879E-3,1.,3.],
      [0.16666666666666627,3.0864197530863957E-3,1.,3.],
      [0.20833333333333293,6.4049238040123045E-3,1.,3.],
      [0.24999999999999958,1.1718749999999934E-2,1.,3.],
      [0.29166666666666624,1.9642771026234473E-2,1.,3.],
      [0.33333333333333293,3.0864197530864071E-2,1.,3.],
      [0.37499999999999961,4.6142578124999847E-2,1.,3.],
      [0.4166666666666663,6.6309799382715848E-2,1.,3.],
      [0.45833333333333298,9.2270085841049135E-2,1.,3.],
      [0.49999999999999967,0.12499999999999971,1.,3.],
      [0.5416666666666663,0.16554844232253049,1.,3.],
      [0.58333333333333293,0.21503665123456736,1.,3.],
      [0.62499999999999956,0.27465820312499928,1.,3.],
      [0.66666666666666619,0.3456790123456781,1.,3.],
      [0.70833333333333282,0.42943733121141858,1.,3.],
      [0.74999999999999944,0.52734374999999845,1.,3.],
      [0.79166666666666607,0.64088119695215873,1.,3.],
      [0.8333333333333327,0.77160493827160281,1.,3.],
      [0.87499999999999933,0.92114257812499756,1.,3.],
      [0.91666666666666596,1.0911940586419722,1.,3.],
      [0.95833333333333259,1.2835316599151199,1.,3.], [1.,1.5,1.,3.]]
    ]
                          Type: List List Point DoubleFloat
```

and we put these points, g2 onto the first graph y1 as graph 2

```
  putGraph(y1,g2,2)
                          Type: Void
```

```
And now we do the whole sequence again

  b:=2.0
    2.0
                            Type: Float

  y3:=draw(x^3*(a+b*x),x=-1..1)
    TwoDimensionalViewport: "AXIOM2D"
                           Type: TwoDimensionalViewport

  g3:=getGraph(y3,1)
    Graph with 1 point list
                           Type: GraphImage

  pointLists g3
   [
     [[-1.,1.5,1.,3.], [-0.95833333333333337,1.2468593267746917,1.,3.],
      [-0.91666666666666674,1.0270061728395066,1.,3.],
      [-0.87500000000000011,0.83740234375000044,1.,3.],
      [-0.83333333333333348,0.67515432098765471,1.,3.],
      [-0.79166666666666685,0.53751326195987703,1.,3.],
      [-0.75000000000000022,0.42187500000000056,1.,3.],
      [-0.70833333333333359,0.32578004436728447,1.,3.],
      [-0.66666666666666696,0.24691358024691412,1.,3.],
      [-0.62500000000000033,0.18310546875000044,1.,3.],
      [-0.5833333333333337,0.1323302469135807,1.,3.],
      [-0.54166666666666707,9.2707127700617648E-2,1.,3.],
      [-0.50000000000000044,6.2500000000000278E-2,1.,3.],
      [-0.45833333333333376,4.0117428626543411E-2,1.,3.],
      [-0.41666666666666707,2.4112654320987775E-2,1.,3.],
      [-0.37500000000000039,1.3183593750000073E-2,1.,3.],
      [-0.3333333333333337,6.1728395061728877E-3,1.,3.],
      [-0.29166666666666702,2.0676601080247183E-3,1.,3.],
      [-0.25000000000000033,1.0408340855860843E-17,1.,3.],
      [-0.20833333333333368,-7.5352044753086191E-4,1.,3.],
      [-0.16666666666666702,-7.7160493827160663E-4,1.,3.],
      [-0.12500000000000036,-4.8828125000000282E-4,1.,3.],
      [-8.3333333333333703E-2,-1.9290123456790339E-4,1.,3.],
      [-4.1666666666667039E-2,-3.0140817901235325E-5,1.,3.],
      [-3.7470027081099033E-16,-2.6304013894372305E-47,1.,3.],
      [4.166666666666629E-2,4.21971450617272E-5,1.,3.],
      [8.3333333333332954E-2,3.8580246913579681E-4,1.,3.],
      [0.12499999999999961,1.4648437499999848E-3,1.,3.],
      [0.16666666666666627,3.8580246913579933E-3,1.,3.],
      [0.20833333333333293,8.2887249228394497E-3,1.,3.],
      [0.24999999999999958,1.562499999999991E-2,1.,3.],
      [0.29166666666666624,2.6879581404320851E-2,1.,3.],
      [0.33333333333333293,4.3209876543209694E-2,1.,3.],
      [0.37499999999999961,6.5917968749999764E-2,1.,3.],
      [0.4166666666666663,9.6450617283950296E-2,1.,3.],
```

```
      [0.45833333333333298,0.13639925733024652,1.,3.],
      [0.49999999999999967,0.18749999999999956,1.,3.],
      [0.5416666666666663,0.25163363233024633,1.,3.],
      [0.58333333333333293,0.33082561728394977,1.,3.],
      [0.62499999999999956,0.42724609374999883,1.,3.],
      [0.66666666666666619,0.5432098765432084,1.,3.],
      [0.70833333333333282,0.68117645640431912,1.,3.],
      [0.74999999999999944,0.84374999999999756,1.,3.],
      [0.79166666666666607,1.0336793499228365,1.,3.],
      [0.8333333333333327,1.2538580246913544,1.,3.],
      [0.87499999999999933,1.507324218749996,1.,3.],
      [0.91666666666666596,1.7972608024691306,1.,3.],
      [0.95833333333333259,2.1269953221450555,1.,3.], [1.,2.5,1.,3.]]
    ]
                        Type: List List Point DoubleFloat

and put the third graphs points g3 onto the first graph y1 as graph 3


  putGraph(y1,g3,3)
                        Type: Void

Finally we show the combined result

  vp:=makeViewport2D(y1)
    TwoDimensionalViewport: "2.2.10 explicit"
                        Type: TwoDimensionalViewport

See Also:
o )show TwoDimensionalViewport
```

21.14.1 TwoDimensionalViewport (VIEW2D)



Exports:

axes	close	coerce	connect	controlPanel
dimensions	getGraph	getPickedPoints	graphState	graphStates
graphs	hash	key	latex	makeViewport2D
move	options	points	putGraph	region
reset	resize	scale	show	title
translate	units	update	viewport2D	write
?=?	?~=?			

— domain VIEW2D TwoDimensionalViewport —

```
)abbrev domain VIEW2D TwoDimensionalViewport
++ Author: Jim Wen
++ Date Created: 28 April 1989
++ Date Last Updated: 29 October 1991, Jon Steinbach
++ Basic Operations:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ TwoDimensionalViewport creates viewports to display graphs.

TwoDimensionalViewport ():Exports == Implementation where

  VIEW    ==> VIEWPORTSERVER$Lisp
  sendI   ==> SOCK_-SEND_-INT
  sendSF  ==> SOCK_-SEND_-FLOAT
  sendSTR ==> SOCK_-SEND_-STRING
  getI    ==> SOCK_-GET_-INT
  getSF   ==> SOCK_-GET_-FLOAT

  typeGRAPH  ==> 2
  typeVIEW2D ==> 3

  makeGRAPH  ==> (-1)$SingleInteger
  makeVIEW2D ==> (-1)$SingleInteger

  I    ==> Integer
  PI   ==> PositiveInteger
  NNI  ==> NonNegativeInteger
  XY   ==> Record( X:I, Y:I )
  XYP  ==> Record( X:PI, Y:PI )
  XYNN ==> Record( X:NNI, Y:NNI )
  F    ==> Float
  SF   ==> DoubleFloat
  STR  ==> String
  L    ==> List
```

```
V    ==> Vector
E    ==> OutputForm
FLAG ==> Record( showCP:I )
PAL  ==> Palette()
B    ==> Boolean
G    ==> GraphImage
GS   ==> Record( scaleX:SF, scaleY:SF, deltaX:SF, deltaY:SF, _
                 points:I, connect:I, spline:I, _
                 axes:I, axesColor:PAL, units:I, unitsColor:PAL, _
                 showing:I)
GU   ==> Union(G,"undefined")
DROP ==> DrawOption
POINT ==> Point(SF)

TRANSLATE2D     ==> 0$I
SCALE2D         ==> 1$I
pointsOnOff     ==> 2
connectOnOff    ==> 3
spline2D        ==> 4   -- used for controlling regions, now
reset2D         ==> 5
hideControl2D   ==> 6
closeAll2D      ==> 7
axesOnOff2D     ==> 8
unitsOnOff2D    ==> 9

SPADBUTTONPRESS ==> 100
MOVE            ==> 102
RESIZE          ==> 103
TITLE           ==> 104
showing2D       ==> 105  -- as defined in include/actions.h
putGraph2D      ==> 106
writeView       ==> 110
axesColor2D     ==> 112
unitsColor2D    ==> 113
getPickedPTS    ==> 119

graphStart      ==> 13   -- as defined in include/actions.h

noControl ==> 0$I

yes       ==> 1$I
no        ==> 0$I

maxGRAPHS ==> 9::I   -- should be the same as maxGraphs in include/view2d.h

fileTypeDefs ==> ["PIXMAP"]    -- see include/write.h for things to include

Exports ==> SetCategory with
  getPickedPoints : $ -> L POINT
    ++ getPickedPoints(x)
```

```
    ++ returns a list of small floats for the points the
    ++ user interactively picked on the viewport
    ++ for full integration into the system, some design
    ++ issues need to be addressed: e.g. how to go through
    ++ the GraphImage interface, how to default to graphs, etc.
  viewport2D     : ()                                    -> $
    ++ viewport2D() returns an undefined two-dimensional viewport
    ++ of the domain \spadtype{TwoDimensionalViewport} whose
    ++ contents are empty.
  makeViewport2D : $                                     -> $
    ++ makeViewport2D(v) takes the given two-dimensional viewport,
    ++ v, of the domain \spadtype{TwoDimensionalViewport} and
    ++ displays a viewport window on the screen which contains
    ++ the contents of v.
  options        : $                                     -> L DROP
    ++ options(v) takes the given two-dimensional viewport, v, of the
    ++ domain \spadtype{TwoDimensionalViewport} and returns a list
    ++ containing the draw options from the domain \spadtype{DrawOption}
    ++ for v.
  options        : ($,L DROP)                            -> $
    ++ options(v,lopt) takes the given two-dimensional viewport, v,
    ++ of the domain \spadtype{TwoDimensionalViewport} and returns
    ++ v with it's draw options modified to be those which are indicated
    ++ in the given list, \spad{lopt} of domain \spadtype{DrawOption}.
  makeViewport2D : (G,L DROP)                            -> $
    ++ makeViewport2D(gi,lopt) creates and displays a viewport window
    ++ of the domain \spadtype{TwoDimensionalViewport} whose graph
    ++ field is assigned to be the given graph, \spad{gi}, of domain
    ++ \spadtype{GraphImage}, and whose options field is set to be
    ++ the list of options, \spad{lopt} of domain \spadtype{DrawOption}.
  graphState     : ($,PI,SF,SF,SF,SF,I,I,I,I,PAL,I,PAL,I) -> Void
    ++ graphState(v,num,sX,sY,dX,dY,pts,lns,box,axes,axesC,un,unC,cP)
    ++ sets the state of the characteristics for the graph indicated
    ++ by \spad{num} in the given two-dimensional viewport v, of domain
    ++ \spadtype{TwoDimensionalViewport}, to the values given as
    ++ parameters.  The scaling of the graph in the x and y component
    ++ directions is set to be \spad{sX} and \spad{sY}; the window
    ++ translation in the x and y component directions is set to be
    ++ \spad{dX} and \spad{dY}; The graph points, lines, bounding box,
    ++ axes, or units will be shown in the viewport if their given
    ++ parameters \spad{pts}, \spad{lns}, \spad{box}, \spad{axes} or
    ++ \spad{un} are set to be \spad{1}, but will not be shown if they
    ++ are set to \spad{0}.  The color of the axes and the color of the
    ++ units are indicated by the palette colors \spad{axesC} and
    ++ \spad{unC} respectively.  To display the control panel when
    ++ the viewport window is displayed, set \spad{cP} to \spad{1},
    ++ otherwise set it to \spad{0}.
  graphStates    : $                                     -> V GS
    ++ graphStates(v) returns and shows a listing of a record containing
    ++ the current state of the characteristics of each of the ten graph
```

```
  ++ records in the given two-dimensional viewport, v, which is of
  ++ domain \spadtype{TwoDimensionalViewport}.
graphs         : $                                  -> V GU
  ++ graphs(v) returns a vector, or list, which is a union of all
  ++ the graphs, of the domain \spadtype{GraphImage}, which are
  ++ allocated for the two-dimensional viewport, v, of domain
  ++ \spadtype{TwoDimensionalViewport}.  Those graphs which have
  ++ no data are labeled "undefined", otherwise their contents
  ++ are shown.
title          : ($,STR)                            -> Void
  ++ title(v,s) changes the title which is shown in the two-dimensional
  ++ viewport window, v of domain \spadtype{TwoDimensionalViewport}.
putGraph       : ($,G,PI)                           -> Void
  ++ putGraph(v,gi,n) sets the graph field indicated by n, of the
  ++ indicated two-dimensional viewport, v, which is of domain
  ++ \spadtype{TwoDimensionalViewport}, to be the graph, \spad{gi}
  ++ of domain \spadtype{GraphImage}.  The contents of viewport, v,
  ++ will contain \spad{gi} when the function \spadfun{makeViewport2D}
  ++ is called to create the an updated viewport v.
getGraph       : ($,PI)                             -> G
  ++ getGraph(v,n) returns the graph which is of the domain
  ++ \spadtype{GraphImage} which is located in graph field n
  ++ of the given two-dimensional viewport, v, which is of the
  ++ domain \spadtype{TwoDimensionalViewport}.
axes           : ($,PI,STR)                         -> Void
  ++ axes(v,n,s) displays the axes of the graph in field n of
  ++ the given two-dimensional viewport, v, which is of domain
  ++ \spadtype{TwoDimensionalViewport}, if s is "on", or does
  ++ not display the axes if s is "off".
axes           : ($,PI,PAL)                         -> Void
  ++ axes(v,n,c) displays the axes of the graph in field n of
  ++ the given two-dimensional viewport, v, which is of domain
  ++ \spadtype{TwoDimensionalViewport}, with the axes color set to
  ++ the given palette color c.
units          : ($,PI,STR)                         -> Void
  ++ units(v,n,s) displays the units of the graph in field n of
  ++ the given two-dimensional viewport, v, which is of domain
  ++ \spadtype{TwoDimensionalViewport}, if s is "on", or does
  ++ not display the units if s is "off".
units          : ($,PI,PAL)                         -> Void
  ++ units(v,n,c) displays the units of the graph in field n of
  ++ the given two-dimensional viewport, v, which is of domain
  ++ \spadtype{TwoDimensionalViewport}, with the units color set to
  ++ the given palette color c.
points         : ($,PI,STR)                         -> Void
  ++ points(v,n,s) displays the points of the graph in field n of
  ++ the given two-dimensional viewport, v, which is of domain
  ++ \spadtype{TwoDimensionalViewport}, if s is "on", or does
  ++ not display the points if s is "off".
region         : ($,PI,STR)                         -> Void
```

```
    ++ region(v,n,s) displays the bounding box of the graph in
    ++ field n of the given two-dimensional viewport, v, which is
    ++ of domain \spadtype{TwoDimensionalViewport}, if s is "on",
    ++ or does not display the bounding box if s is "off".
  connect        : ($,PI,STR)                          -> Void
    ++ connect(v,n,s) displays the lines connecting the graph
    ++ points in field n of the given two-dimensional viewport, v,
    ++ which is of domain \spadtype{TwoDimensionalViewport}, if s
    ++ is "on", or does not display the lines if s is "off".
  controlPanel   : ($,STR)                             -> Void
    ++ controlPanel(v,s) displays the control panel of the given
    ++ two-dimensional viewport, v, which is of domain
    ++ \spadtype{TwoDimensionalViewport}, if s is "on", or hides
    ++ the control panel if s is "off".
  close          : $                                   -> Void
    ++ close(v) closes the viewport window of the given
    ++ two-dimensional viewport, v, which is of domain
    ++ \spadtype{TwoDimensionalViewport}, and terminates the
    ++ corresponding process ID.
  dimensions     : ($,NNI,NNI,PI,PI)                   -> Void
    ++ dimensions(v,x,y,width,height) sets the position of the
    ++ upper left-hand corner of the two-dimensional viewport, v,
    ++ which is of domain \spadtype{TwoDimensionalViewport}, to
    ++ the window coordinate x, y, and sets the dimensions of the
    ++ window to that of \spad{width}, \spad{height}.  The new
    ++ dimensions are not displayed until the function
    ++ \spadfun{makeViewport2D} is executed again for v.
  scale          : ($,PI,F,F)                          -> Void
    ++ scale(v,n,sx,sy) displays the graph in field n of the given
    ++ two-dimensional viewport, v, which is of domain
    ++ \spadtype{TwoDimensionalViewport}, scaled by the factor \spad{sx}
    ++ in the x-coordinate direction and by the factor \spad{sy} in
    ++ the y-coordinate direction.
  translate      : ($,PI,F,F)                          -> Void
    ++ translate(v,n,dx,dy) displays the graph in field n of the given
    ++ two-dimensional viewport, v, which is of domain
    ++ \spadtype{TwoDimensionalViewport}, translated by \spad{dx} in
    ++ the x-coordinate direction from the center of the viewport, and
    ++ by \spad{dy} in the y-coordinate direction from the center.
    ++ Setting \spad{dx} and \spad{dy} to \spad{0} places the center
    ++ of the graph at the center of the viewport.
  show           : ($,PI,STR)                          -> Void
    ++ show(v,n,s) displays the graph in field n of the given
    ++ two-dimensional viewport, v, which is of domain
    ++ \spadtype{TwoDimensionalViewport}, if s is "on", or does not
    ++ display the graph if s is "off".
  move           : ($,NNI,NNI)                         -> Void
    ++ move(v,x,y) displays the two-dimensional viewport, v, which
    ++ is of domain \spadtype{TwoDimensionalViewport}, with the upper
    ++ left-hand corner of the viewport window at the screen
```

```
    ++ coordinate position x, y.
  update         :($,G,PI)                                -> Void
    ++ update(v,gr,n) drops the graph \spad{gr} in slot \spad{n}
    ++ of viewport \spad{v}. The graph gr must have been
    ++ transmitted already and acquired an integer key.
  resize         : ($,PI,PI)                              -> Void
    ++ resize(v,w,h) displays the two-dimensional viewport, v, which
    ++ is of domain \spadtype{TwoDimensionalViewport}, with a width
    ++ of w and a height of h, keeping the upper left-hand corner
    ++ position unchanged.
  write          : ($,STR)                                -> STR
    ++ write(v,s) takes the given two-dimensional viewport, v, which
    ++ is of domain \spadtype{TwoDimensionalViewport}, and creates
    ++ a directory indicated by s, which contains the graph data
    ++ files for v.
  write          : ($,STR,STR)                            -> STR
    ++ write(v,s,f) takes the given two-dimensional viewport, v, which
    ++ is of domain \spadtype{TwoDimensionalViewport}, and creates
    ++ a directory indicated by s, which contains the graph data
    ++ files for v and an optional file type f.
  write          : ($,STR,L STR)                          -> STR
    ++ write(v,s,lf) takes the given two-dimensional viewport, v, which
    ++ is of domain \spadtype{TwoDimensionalViewport}, and creates
    ++ a directory indicated by s, which contains the graph data
    ++ files for v and the optional file types indicated by the list lf.
  reset          :  $                                     -> Void
    ++ reset(v) sets the current state of the graph characteristics
    ++ of the given two-dimensional viewport, v, which is of domain
    ++ \spadtype{TwoDimensionalViewport}, back to their initial settings.
  key            :  $                                     -> I
    ++ key(v) returns the process ID number of the given two-dimensional
    ++ viewport, v, which is of domain \spadtype{TwoDimensionalViewport}.
  coerce         :  $                                     -> E
    ++ coerce(v) returns the given two-dimensional viewport, v, which
    ++ is of domain \spadtype{TwoDimensionalViewport} as output of
    ++ the domain \spadtype{OutputForm}.

Implementation ==> add

  import GraphImage()
  import Color()
  import Palette()
  import ViewDefaultsPackage()
  import DrawOptionFunctions0
  import POINT

  Rep := Record (key:I, graphsField:V GU, graphStatesField:V GS, _
                 title:STR, moveTo:XYNN, size:XYP, flags:FLAG, optionsField:L DROP)

  defaultGS : GS := [convert(0.9)@SF, convert(0.9)@SF, 0$SF, 0$SF, _
```

```
                yes, yes, no, _
                yes, axesColorDefault(), no, unitsColorDefault(), _
                yes]


 --% Local Functions
checkViewport (viewport:$):B ==
    -- checks to see if this viewport still exists
    -- by sending the key to the viewport manager and
    -- waiting for its reply after it checks it against
    -- the viewports in its list. a -1 means it doesn't
    -- exist.
  sendI(VIEW,viewport.key)$Lisp
  i := getI(VIEW)$Lisp
  (i < 0$I) =>
    viewport.key := 0$I
    error "This viewport has already been closed!"
  true

doOptions(v:Rep):Void ==
  v.title := title(v.optionsField,"AXIOM2D")
  -- etc - 2D specific stuff...

 --% Exported Functions

options viewport ==
  viewport.optionsField

options(viewport,opts) ==
  viewport.optionsField := opts
  viewport

putGraph (viewport,aGraph,which) ==
  if ((which > maxGRAPHS) or (which < 1)) then
    error "Trying to put a graph with a negative index or too big an index"
  viewport.graphsField.which := aGraph

getGraph (viewport,which) ==
  if ((which > maxGRAPHS) or (which < 1)) then
    error "Trying to get a graph with a negative index or too big an index"
  viewport.graphsField.which case "undefined" =>
    error "Graph is undefined!"
  viewport.graphsField.which::GraphImage


graphStates viewport  == viewport.graphStatesField
graphs viewport       == viewport.graphsField
key viewport          == viewport.key

dimensions(viewport,ViewX,ViewY,ViewWidth,ViewHeight) ==
```

```
    viewport.moveTo := [ViewX,ViewY]
    viewport.size   := [ViewWidth,ViewHeight]

  move(viewport,xLoc,yLoc) ==
    viewport.moveTo := [xLoc,yLoc]
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,MOVE)$Lisp
      checkViewport viewport =>
        sendI(VIEW,xLoc)$Lisp
        sendI(VIEW,yLoc)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  update(viewport,graph,slot) ==
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,putGraph2D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,key graph)$Lisp
        sendI(VIEW,slot)$Lisp
        getI(VIEW)$Lisp -- acknowledge

  resize(viewport,xSize,ySize) ==
    viewport.size := [xSize,ySize]
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,RESIZE)$Lisp
      checkViewport viewport =>
        sendI(VIEW,xSize)$Lisp
        sendI(VIEW,ySize)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  translate(viewport,graphIndex,xTranslateF,yTranslateF) ==
    xTranslate := convert(xTranslateF)@SF
    yTranslate := convert(yTranslateF)@SF
    if (graphIndex > maxGRAPHS) then
      error "Referring to a graph with too big an index"
    viewport.graphStatesField.graphIndex.deltaX := xTranslate
    viewport.graphStatesField.graphIndex.deltaY := yTranslate
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,TRANSLATE2D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,graphIndex)$Lisp
        sendSF(VIEW,xTranslate)$Lisp
        sendSF(VIEW,yTranslate)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  scale(viewport,graphIndex,xScaleF,yScaleF) ==
    xScale := convert(xScaleF)@SF
```

```
    yScale := convert(yScaleF)@SF
    if (graphIndex > maxGRAPHS) then
      error "Referring to a graph with too big an index"
    viewport.graphStatesField.graphIndex.scaleX := xScale  -- check union (undefined?)
    viewport.graphStatesField.graphIndex.scaleY := yScale  -- check union (undefined?)
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,SCALE2D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,graphIndex)$Lisp
        sendSF(VIEW,xScale)$Lisp
        sendSF(VIEW,yScale)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  viewport2D ==
    [0,new(maxGRAPHS,"undefined"), _
     new(maxGRAPHS,copy defaultGS),"AXIOM2D", _
      [viewPosDefault().1,viewPosDefault().2],[viewSizeDefault().1,viewSizeDefault().2], _
       [noControl], [] ]

  makeViewport2D(g:G,opts:L DROP) ==
    viewport               := viewport2D()
    viewport.graphsField.1 := g
    viewport.optionsField := opts
    makeViewport2D viewport

  makeViewport2D viewportDollar ==
    viewport := viewportDollar::Rep
    doOptions viewport --local function to extract and assign optional arguments for 2D viewports
    sayBrightly(["   AXIOM2D data being transmitted to the viewport manager..."::E]$List(E))$Lisp
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,makeVIEW2D)$Lisp
    sendSTR(VIEW,viewport.title)$Lisp
    sendI(VIEW,viewport.moveTo.X)$Lisp
    sendI(VIEW,viewport.moveTo.Y)$Lisp
    sendI(VIEW,viewport.size.X)$Lisp
    sendI(VIEW,viewport.size.Y)$Lisp
    sendI(VIEW,viewport.flags.showCP)$Lisp
    for i in 1..maxGRAPHS repeat
      g := (graphs viewport).i
      if g case "undefined" then
        sendI(VIEW,0$I)$Lisp
      else
        sendI(VIEW,key(g::G))$Lisp
        gs := (graphStates viewport).i
        sendSF(VIEW,gs.scaleX)$Lisp
        sendSF(VIEW,gs.scaleY)$Lisp
        sendSF(VIEW,gs.deltaX)$Lisp
        sendSF(VIEW,gs.deltaY)$Lisp
        sendI(VIEW,gs.points)$Lisp
```

```
      sendI(VIEW,gs.connect)$Lisp
      sendI(VIEW,gs.spline)$Lisp
      sendI(VIEW,gs.axes)$Lisp
      hueShade := hue hue gs.axesColor + shade gs.axesColor * numberOfHues()
      sendI(VIEW,hueShade)$Lisp
      sendI(VIEW,gs.units)$Lisp
      hueShade := hue hue gs.unitsColor + shade gs.unitsColor * numberOfHues()
      sendI(VIEW,hueShade)$Lisp
      sendI(VIEW,gs.showing)$Lisp
  viewport.key := getI(VIEW)$Lisp
  viewport

graphState(viewport,num,sX,sY,dX,dY,Points,Lines,Spline, _
           Axes,AxesColor,Units,UnitsColor,Showing) ==
  viewport.graphStatesField.num := [sX,sY,dX,dY,Points,Lines,Spline, _
                                    Axes,AxesColor,Units,UnitsColor,Showing]

title(viewport,Title) ==
  viewport.title := Title
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,TITLE)$Lisp
    checkViewport viewport =>
      sendSTR(VIEW,Title)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

reset viewport ==
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,SPADBUTTONPRESS)$Lisp
    checkViewport viewport =>
      sendI(VIEW,reset2D)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

axes (viewport:$,graphIndex:PI,onOff:STR) : Void ==
  if (graphIndex > maxGRAPHS) then
    error "Referring to a graph with too big an index"
  if onOff = "on" then
    status := yes
  else
    status := no
  viewport.graphStatesField.graphIndex.axes := status  -- check union (undefined?)
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,axesOnOff2D)$Lisp
    checkViewport viewport =>
      sendI(VIEW,graphIndex)$Lisp
      sendI(VIEW,status)$Lisp
      getI(VIEW)$Lisp          -- acknowledge
```

```
axes (viewport:$,graphIndex:PI,color:PAL) : Void ==
  if (graphIndex > maxGRAPHS) then
    error "Referring to a graph with too big an index"
  viewport.graphStatesField.graphIndex.axesColor := color
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,axesColor2D)$Lisp
    checkViewport viewport =>
      sendI(VIEW,graphIndex)$Lisp
      hueShade := hue hue color + shade color * numberOfHues()
      sendI(VIEW,hueShade)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

units (viewport:$,graphIndex:PI,onOff:STR) : Void ==
  if (graphIndex > maxGRAPHS) then
    error "Referring to a graph with too big an index"
  if onOff = "on" then
    status := yes
  else
    status := no
  viewport.graphStatesField.graphIndex.units := status  -- check union (undefined?)
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,unitsOnOff2D)$Lisp
    checkViewport viewport =>
      sendI(VIEW,graphIndex)$Lisp
      sendI(VIEW,status)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

units (viewport:$,graphIndex:PI,color:PAL) : Void ==
  if (graphIndex > maxGRAPHS) then
    error "Referring to a graph with too big an index"
  viewport.graphStatesField.graphIndex.unitsColor := color
  (key(viewport) ^= 0$I) =>
    sendI(VIEW,typeVIEW2D)$Lisp
    sendI(VIEW,unitsColor2D)$Lisp
    checkViewport viewport =>
      sendI(VIEW,graphIndex)$Lisp
      hueShade := hue hue color + shade color * numberOfHues()
      sendI(VIEW,hueShade)$Lisp
      getI(VIEW)$Lisp          -- acknowledge

connect (viewport:$,graphIndex:PI,onOff:STR) : Void ==
  if (graphIndex > maxGRAPHS) then
    error "Referring to a graph with too big an index"
  if onOff = "on" then
    status := 1$I
  else
    status := 0$I
  viewport.graphStatesField.graphIndex.connect := status  -- check union (undefined?)
```

```
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,connectOnOff)$Lisp
      checkViewport viewport =>
        sendI(VIEW,graphIndex)$Lisp
        sendI(VIEW,status)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  points (viewport:$,graphIndex:PI,onOff:STR) : Void ==
    if (graphIndex > maxGRAPHS) then
      error "Referring to a graph with too big an index"
    if onOff = "on" then
      status := 1$I
    else
      status := 0$I
    viewport.graphStatesField.graphIndex.points := status  -- check union (undefined?)
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,pointsOnOff)$Lisp
      checkViewport viewport =>
        sendI(VIEW,graphIndex)$Lisp
        sendI(VIEW,status)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  region (viewport:$,graphIndex:PI,onOff:STR) : Void ==
    if (graphIndex > maxGRAPHS) then
      error "Referring to a graph with too big an index"
    if onOff = "on" then
      status := 1$I
    else
      status := 0$I
    viewport.graphStatesField.graphIndex.spline := status  -- check union (undefined?)
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,spline2D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,graphIndex)$Lisp
        sendI(VIEW,status)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  show (viewport,graphIndex,onOff) ==
    if (graphIndex > maxGRAPHS) then
      error "Referring to a graph with too big an index"
    if onOff = "on" then
      status := 1$I
    else
      status := 0$I
    viewport.graphStatesField.graphIndex.showing := status  -- check union (undefined?)
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
```

```
      sendI(VIEW,showing2D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,graphIndex)$Lisp
        sendI(VIEW,status)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  controlPanel (viewport,onOff) ==
    if onOff = "on" then viewport.flags.showCP := yes
    else viewport.flags.showCP := no
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,hideControl2D)$Lisp
      checkViewport viewport =>
        sendI(VIEW,viewport.flags.showCP)$Lisp
        getI(VIEW)$Lisp          -- acknowledge

  close viewport ==
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,closeAll2D)$Lisp
      checkViewport viewport =>
        getI(VIEW)$Lisp          -- acknowledge
        viewport.key := 0$I

  coerce viewport ==
    (key(viewport) = 0$I) =>
      hconcat ["Closed or Undefined TwoDimensionalViewport: "::E,
               (viewport.title)::E]
    hconcat ["TwoDimensionalViewport: "::E, (viewport.title)::E]

  write(viewport:$,Filename:STR,aThingToWrite:STR) ==
    write(viewport,Filename,[aThingToWrite])

  write(viewport,Filename) ==
    write(viewport,Filename,viewWriteDefault())

  write(viewport:$,Filename:STR,thingsToWrite:L STR) ==
    stringToSend : STR := ""
    (key(viewport) ^= 0$I) =>
      sendI(VIEW,typeVIEW2D)$Lisp
      sendI(VIEW,writeView)$Lisp
      checkViewport viewport =>
        sendSTR(VIEW,Filename)$Lisp
        m := minIndex(avail := viewWriteAvailable())
        for aTypeOfFile in thingsToWrite repeat
          if (writeTypeInt:= position(upperCase aTypeOfFile,avail)-m) < 0 then
            sayBrightly(["  > "::E,(concat(aTypeOfFile, _
              " is not a valid file type for writing a 2D viewport"))::E]$List(E))$Lisp
          else
            sendI(VIEW,writeTypeInt+(1$I))$Lisp
```

```
                --              stringToSend := concat [stringToSend,"%",aTypeOfFile]
                --              sendSTR(VIEW,stringToSend)$Lisp
          sendI(VIEW,0$I)$Lisp   -- no more types of things to write
          getI(VIEW)$Lisp        -- acknowledge
          Filename
```

———-

— VIEW2D.dotabb —

```
"VIEW2D" [color="#88FF44",href="bookvol10.3.pdf#nameddest=VIEW2D"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"VIEW2D" -> "STRING"
```

———-

Chapter 22

Chapter U

22.1 domain UFPS UnivariateFormalPowerSeries

— UnivariateFormalPowerSeries.input —

```
)set break resume
)sys rm -f UnivariateFormalPowerSeries.output
)spool UnivariateFormalPowerSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariateFormalPowerSeries
--R
--R UnivariateFormalPowerSeries(Coef: Ring)  is a domain constructor
--R Abbreviation for UnivariateFormalPowerSeries is UFPS
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for UFPS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coefficients : % -> Stream(Coef)     coerce : Variable(QUOTE(x)) -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R complete : % -> %                    degree : % -> NonNegativeInteger
--R evenlambert : % -> %                 hash : % -> SingleInteger
```

```
--R lagrange : % -> %                    lambert : % -> %
--R latex : % -> String                  leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %             map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean             oddlambert : % -> %
--R one? : % -> Boolean                  order : % -> NonNegativeInteger
--R pole? : % -> Boolean                 quoByVar : % -> %
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R revert : % -> %                      sample : () -> %
--R series : Stream(Coef) -> %           variable : % -> Symbol
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Coef) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRING(SYM
--R D : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRI
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeInteger,Coef)
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,NonNegativeInteger) -> Coef if Coef has **: (Coef,NonNegativeInteger) -> Co
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,NonNegativeInteger) -> Coef
--R coerce : UnivariatePolynomial(QUOTE(x),Coef) -> %
--R coerce : Coef -> % if Coef has COMRING
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(QUOTE(x))) -> %
--R differentiate : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRING(SYM
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRI
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeInteger,Coef)
--R ?.? : (%,%) -> % if NonNegativeInteger has SGROUP
--R ?.? : (%,NonNegativeInteger) -> Coef
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,NonNegativeInteger) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,NonNegativeInteger) -> %
--R generalLambert : (%,Integer,Integer) -> %
--R integrate : (%,Variable(QUOTE(x))) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef ->
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R invmultisect : (Integer,Integer,%) -> %
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (Coef,NonNegativeInteger) -> %
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R multisect : (Integer,Integer,%) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,NonNegativeInteger) -> NonNegativeInteger
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R polynomial : (%,NonNegativeInteger,NonNegativeInteger) -> Polynomial(Coef)
--R polynomial : (%,NonNegativeInteger) -> Polynomial(Coef)
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: NonNegativeInteger,c: Coef)) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: NonNegativeInteger,c: Coef))
--R truncate : (%,NonNegativeInteger,NonNegativeInteger) -> %
--R truncate : (%,NonNegativeInteger) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R univariatePolynomial : (%,NonNegativeInteger) -> UnivariatePolynomial(QUOTE(x),Coef)
--R variables : % -> List(SingletonAsOrderedSet)
--R
```

```
--E 1

)spool
)lisp (bye)
```

———-


— **UnivariateFormalPowerSeries.help** —

```
=====================================================================
UnivariateFormalPowerSeries examples
=====================================================================

See Also:
o )show UnivariateFormalPowerSeries
```

———-

22.1.1 UnivariateFormalPowerSeries (UFPS)



Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coefficients	coerce	complete	cos
cosh	cot	coth	csc
csch	D	degree	differentiate
eval	evenlambert	exp	exquo
extend	generalLambert	hash	integrate
invmultisect	lagrange	lambert	latex
leadingCoefficient	leadingMonomial	log	map
monomial	monomial?	multiplyCoefficients	multiplyExponents
multisect	nthRoot	oddlambert	one?
order	pi	pole?	polynomial
quoByVar	recip	reductum	revert
sample	sec	sech	series
sin	sinh	sqrt	subtractIfCan
tan	tanh	terms	truncate
unit?	unitCanonical	unitNormal	univariatePolynomial
variable	variables	zero?	?*?
?**?	?+?	?-?	-?
?=?	?^?	?~=?	?/?
?.?			

— domain UFPS UnivariateFormalPowerSeries —

```
)abbrev domain UFPS UnivariateFormalPowerSeries
++ Author: Mark Botch
++ Description:
++ This domain has no description

UnivariateFormalPowerSeries(Coef: Ring) ==
    UnivariateTaylorSeries(Coef, 'x, 0$Coef)
```

———-

— UFPS.dotabb —

```
"UFPS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UFPS"]
"UTSCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=UTSCAT"]
"UFPS" -> "UTSCAT"
```

———-

22.2 domain ULS UnivariateLaurentSeries

— UnivariateLaurentSeries.input —

```
)set break resume
)sys rm -f UnivariateLaurentSeries.output
)spool UnivariateLaurentSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariateLaurentSeries
--R
--R UnivariateLaurentSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for UnivariateLaurentSeries is ULS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ULS
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Coef,%) -> %                   ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        center : % -> Coef
--R coefficient : (%,Integer) -> Coef     coerce : Variable(var) -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R complete : % -> %                     degree : % -> Integer
--R ?.? : (%,Integer) -> Coef             extend : (%,Integer) -> %
--R hash : % -> SingleInteger             latex : % -> String
--R leadingCoefficient : % -> Coef        leadingMonomial : % -> %
--R map : ((Coef -> Coef),%) -> %         monomial : (Coef,Integer) -> %
--R monomial? : % -> Boolean              one? : % -> Boolean
--R order : (%,Integer) -> Integer        order : % -> Integer
--R pole? : % -> Boolean                  recip : % -> Union(%,"failed")
--R reductum : % -> %                     removeZeroes : (Integer,%) -> %
--R removeZeroes : % -> %                 sample : () -> %
--R truncate : (%,Integer) -> %           variable : % -> Symbol
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (UnivariateTaylorSeries(Coef,var,cen),%) -> % if Coef has FIELD
--R ?*? : (%,UnivariateTaylorSeries(Coef,var,cen)) -> % if Coef has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (UnivariateTaylorSeries(Coef,var,cen),UnivariateTaylorSeries(Coef,var,cen)) -> % if Coef has FIELL
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R ?<? : (%,%) -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or Univari
--R ?<=? : (%,%) -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or Univa
--R ?>? : (%,%) -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or Univari
--R ?>=? : (%,%) -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or Univa
--R D : (%,Symbol) -> % if UnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) and Coef has FIELD or Coe
--R D : (%,List(Symbol)) -> % if UnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) and Coef has FIELD
--R D : (%,Symbol,NonNegativeInteger) -> % if UnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) and Co
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if UnivariateTaylorSeries(Coef,var,cen) has PDRING(SY
--R D : % -> % if UnivariateTaylorSeries(Coef,var,cen) has DIFRING and Coef has FIELD or Coef has *: (Integ
--R D : (%,NonNegativeInteger) -> % if UnivariateTaylorSeries(Coef,var,cen) has DIFRING and Coef has FIELD o
--R D : (%,(UnivariateTaylorSeries(Coef,var,cen) -> UnivariateTaylorSeries(Coef,var,cen)),NonNegativeIntege
--R D : (%,(UnivariateTaylorSeries(Coef,var,cen) -> UnivariateTaylorSeries(Coef,var,cen))) -> % if Coef has
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Integer) -> Coef if Coef has **: (Coef,Integer) -> Coef and Coef has coerce: Symbol ->
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD o
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R ceiling : % -> UnivariateTaylorSeries(Coef,var,cen) if UnivariateTaylorSeries(Coef,var,cen) has INS and
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and UnivariateTaylorSeries(Coef,var,cen) has PFECAT
--R coerce : Fraction(Integer) -> % if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(INT) and Coef has FI
--R coerce : % -> % if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or UnivariateTayl
--R coerce : Symbol -> % if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(SYMBOL) and Coef has FIELD
--R coerce : UnivariateTaylorSeries(Coef,var,cen) -> %
--R coerce : Coef -> % if Coef has COMRING
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and UnivariateTaylorSeries(Coef,var
--R convert : % -> Pattern(Integer) if UnivariateTaylorSeries(Coef,var,cen) has KONVERT(PATTERN(INT)) and Co
--R convert : % -> Pattern(Float) if UnivariateTaylorSeries(Coef,var,cen) has KONVERT(PATTERN(FLOAT)) and Co
--R convert : % -> DoubleFloat if UnivariateTaylorSeries(Coef,var,cen) has REAL and Coef has FIELD
--R convert : % -> Float if UnivariateTaylorSeries(Coef,var,cen) has REAL and Coef has FIELD
--R convert : % -> InputForm if UnivariateTaylorSeries(Coef,var,cen) has KONVERT(INFORM) and Coef has FIELD
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R denom : % -> UnivariateTaylorSeries(Coef,var,cen) if Coef has FIELD
--R denominator : % -> % if Coef has FIELD
--R differentiate : (%,Symbol) -> % if UnivariateTaylorSeries(Coef,var,cen) has PDRING(SYMBOL) a
--R differentiate : (%,List(Symbol)) -> % if UnivariateTaylorSeries(Coef,var,cen) has PDRING(SYM
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if UnivariateTaylorSeries(Coef,var,cen) h
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if UnivariateTaylorSeries(Coe
--R differentiate : % -> % if UnivariateTaylorSeries(Coef,var,cen) has DIFRING and Coef has FIEL
--R differentiate : (%,NonNegativeInteger) -> % if UnivariateTaylorSeries(Coef,var,cen) has DIFR
--R differentiate : (%,Variable(var)) -> %
--R differentiate : (%,(UnivariateTaylorSeries(Coef,var,cen) -> UnivariateTaylorSeries(Coef,var,
--R differentiate : (%,(UnivariateTaylorSeries(Coef,var,cen) -> UnivariateTaylorSeries(Coef,var,
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,UnivariateTaylorSeries(Coef,var,cen)) -> % if UnivariateTaylorSeries(Coef,var,cen)
--R ?.? : (%,%) -> % if Integer has SGROUP
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,List(UnivariateTaylorSeries(Coef,var,cen)),List(UnivariateTaylorSeries(Coef,var,ce
--R eval : (%,UnivariateTaylorSeries(Coef,var,cen),UnivariateTaylorSeries(Coef,var,cen)) -> % if
--R eval : (%,Equation(UnivariateTaylorSeries(Coef,var,cen))) -> % if UnivariateTaylorSeries(Coe
--R eval : (%,List(Equation(UnivariateTaylorSeries(Coef,var,cen)))) -> % if UnivariateTaylorSeri
--R eval : (%,List(Symbol),List(UnivariateTaylorSeries(Coef,var,cen))) -> % if UnivariateTaylorS
--R eval : (%,Symbol,UnivariateTaylorSeries(Coef,var,cen)) -> % if UnivariateTaylorSeries(Coef,v
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Integer) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and C
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R floor : % -> UnivariateTaylorSeries(Coef,var,cen) if UnivariateTaylorSeries(Coef,var,cen) ha
--R fractionPart : % -> % if UnivariateTaylorSeries(Coef,var,cen) has EUCDOM and Coef has FIELD
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R init : () -> % if UnivariateTaylorSeries(Coef,var,cen) has STEP and Coef has FIELD
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variab
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R laurent : (Integer,UnivariateTaylorSeries(Coef,var,cen)) -> %
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R map : ((UnivariateTaylorSeries(Coef,var,cen) -> UnivariateTaylorSeries(Coef,var,cen)),%) ->
--R max : (%,%) -> % if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or U
```

```
--R min : (%,%) -> % if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD or UnivariateTay
--R monomial : (%,List(SingletonAsOrderedSet),List(Integer)) -> %
--R monomial : (%,SingletonAsOrderedSet,Integer) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R negative? : % -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R nextItem : % -> Union(%,"failed") if UnivariateTaylorSeries(Coef,var,cen) has STEP and Coef has FIELD
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R numer : % -> UnivariateTaylorSeries(Coef,var,cen) if Coef has FIELD
--R numerator : % -> % if Coef has FIELD
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%) if Univaria
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Integer,%) if Un
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R positive? : % -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R ?quo? : (%,%) -> % if Coef has FIELD
--R random : () -> % if UnivariateTaylorSeries(Coef,var,cen) has INS and Coef has FIELD
--R rationalFunction : (%,Integer,Integer) -> Fraction(Polynomial(Coef)) if Coef has INTDOM
--R rationalFunction : (%,Integer) -> Fraction(Polynomial(Coef)) if Coef has INTDOM
--R reducedSystem : Matrix(%) -> Matrix(Integer) if UnivariateTaylorSeries(Coef,var,cen) has LINEXP(INT) and
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) if Univariate
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(UnivariateTaylorSeries(Coef,var,cen)),vec: V
--R reducedSystem : Matrix(%) -> Matrix(UnivariateTaylorSeries(Coef,var,cen)) if Coef has FIELD
--R ?rem? : (%,%) -> % if Coef has FIELD
--R retract : % -> Integer if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(INT) and Coef has FIELD
--R retract : % -> Fraction(Integer) if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(INT) and Coef has I
--R retract : % -> Symbol if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(SYMBOL) and Coef has FIELD
--R retract : % -> UnivariateTaylorSeries(Coef,var,cen)
--R retractIfCan : % -> Union(Integer,"failed") if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(INT) and
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if UnivariateTaylorSeries(Coef,var,cen) has RETRAC
--R retractIfCan : % -> Union(Symbol,"failed") if UnivariateTaylorSeries(Coef,var,cen) has RETRACT(SYMBOL) a
--R retractIfCan : % -> Union(UnivariateTaylorSeries(Coef,var,cen),"failed")
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: Integer,c: Coef)) -> %
--R sign : % -> Integer if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if Coef has FIELD
--R squareFreePart : % -> % if Coef has FIELD
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if Univa
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R taylor : % -> UnivariateTaylorSeries(Coef,var,cen)
```

```
--R taylorIfCan : % -> Union(UnivariateTaylorSeries(Coef,var,cen),"failed")
--R taylorRep : % -> UnivariateTaylorSeries(Coef,var,cen)
--R terms : % -> Stream(Record(k: Integer,c: Coef))
--R truncate : (%,Integer,Integer) -> %
--R unit? : % -> Boolean if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIELD
--R unitCanonical : % -> % if UnivariateTaylorSeries(Coef,var,cen) has OINTDOM and Coef has FIEL
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if UnivariateTaylorSeries(Coef,v
--R variables : % -> List(SingletonAsOrderedSet)
--R wholePart : % -> UnivariateTaylorSeries(Coef,var,cen) if UnivariateTaylorSeries(Coef,var,cen
--R
--E 1

)spool
)lisp (bye)
```

———-


— **UnivariateLaurentSeries.help** —

```
=====================================================================
UnivariateLaurentSeries examples
=====================================================================

See Also:
o )show UnivariateLaurentSeries
```

———-

22.2.1 UnivariateLaurentSeries (ULS)



See

⇒ “UnivariateLaurentSeriesConstructor” (ULSCONS) 22.3.1 on page 2770

Exports:

0	1	abs
acos	acosh	acot
acoth	acsc	acsch
approximate	asec	asech
asin	asinh	associates?
atan	atanh	ceiling
center	characteristic	charthRoot
coerce	coefficient	coerce
complete	conditionP	convert
cos	cosh	cot
coth	csc	csch
D	degree	denom
denominator	differentiate	divide
euclideanSize	eval	exp
expressIdealMember	exquo	extend
extendedEuclidean	factor	factorPolynomial
factorSquareFreePolynomial	floor	fractionPart
gcd	gcdPolynomial	hash
init	integrate	inv
latex	laurent	leadingCoefficient
leadingMonomial	lcm	log
map	max	min
monomial	monomial?	multiEuclidean
multiplyCoefficients	multiplyExponents	negative?
nextItem	nthRoot	numer
numerator	one?	order
patternMatch	pi	pole?
positive?	prime?	principalIdeal
random	rationalFunction	recip
reducedSystem	reductum	removeZeroes
retract	retractIfCan	sample
sec	sech	series
sign	sin	sinh
sizeLess?	solveLinearPolynomialEquation	sqrt
squareFree	squareFreePart	squareFreePolynomial
subtractIfCan	tan	tanh
taylor	taylorIfCan	taylorRep
terms	truncate	unit?
unitCanonical	unitNormal	variable
variables	wholePart	zero?
?*?	?**?	?+?
?-?	-?	?=?
?^?	?.?	?~=?
?/?	?<?	?<=?
?>?	?>=?	?^?
?.?	?quo?	?rem?

— domain ULS UnivariateLaurentSeries —

```
)abbrev domain ULS UnivariateLaurentSeries
++ Author: Clifton J. Williamson
++ Date Created: 18 January 1990
++ Date Last Updated: 21 September 1993
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: series, Laurent
++ Examples:
++ References:
++ Description:
++ Dense Laurent series in one variable
++ \spadtype{UnivariateLaurentSeries} is a domain representing Laurent
++ series in one variable with coefficients in an arbitrary ring.  The
++ parameters of the type specify the coefficient ring, the power series
++ variable, and the center of the power series expansion.  For example,
++ \spad{UnivariateLaurentSeries(Integer,x,3)} represents Laurent series in
++ \spad{(x - 3)} with integer coefficients.

UnivariateLaurentSeries(Coef,var,cen): Exports == Implementation where
  Coef : Ring
  var  : Symbol
  cen  : Coef
  I   ==> Integer
  UTS ==> UnivariateTaylorSeries(Coef,var,cen)

  Exports ==> UnivariateLaurentSeriesConstructorCategory(Coef,UTS) with
    coerce: Variable(var) -> %
      ++ \spad{coerce(var)} converts the series variable \spad{var} into a
      ++ Laurent series.
    differentiate: (%,Variable(var)) -> %
      ++ \spad{differentiate(f(x),x)} returns the derivative of
      ++ \spad{f(x)} with respect to \spad{x}.
    if Coef has Algebra Fraction Integer then
      integrate: (%,Variable(var)) -> %
        ++ \spad{integrate(f(x))} returns an anti-derivative of the power
        ++ series \spad{f(x)} with constant coefficient 0.
        ++ We may integrate a series when we can divide coefficients
        ++ by integers.

  Implementation ==> UnivariateLaurentSeriesConstructor(Coef,UTS) add

    variable x == var
    center   x == cen

    coerce(v:Variable(var)) ==
```

```
      zero? cen => monomial(1,1)
      monomial(1,1) + monomial(cen,0)

    differentiate(x:%,v:Variable(var)) == differentiate x

    if Coef has Algebra Fraction Integer then
      integrate(x:%,v:Variable(var)) == integrate x
```

———-

— **ULS.dotabb** —

```
"ULS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ULS"]
"ULSCCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ULSCCAT"]
"ULS" -> "ULSCCAT"
```

———-

22.3 domain ULSCONS UnivariateLaurentSeriesConstructor

— **UnivariateLaurentSeriesConstructor.input** —

```
)set break resume
)sys rm -f UnivariateLaurentSeriesConstructor.output
)spool UnivariateLaurentSeriesConstructor.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariateLaurentSeriesConstructor
--R
--R UnivariateLaurentSeriesConstructor(Coef: Ring,UTS: UnivariateTaylorSeriesCategory(Coef))  is a domain co
--R Abbreviation for UnivariateLaurentSeriesConstructor is ULSCONS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for ULSCONS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
```

```
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coefficient : (%,Integer) -> Coef    coerce : UTS -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R complete : % -> %                    degree : % -> Integer
--R ?.? : (%,Integer) -> Coef            extend : (%,Integer) -> %
--R hash : % -> SingleInteger            latex : % -> String
--R laurent : (Integer,UTS) -> %         leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %             map : ((Coef -> Coef),%) -> %
--R monomial : (Coef,Integer) -> %       monomial? : % -> Boolean
--R one? : % -> Boolean                  order : (%,Integer) -> Integer
--R order : % -> Integer                 pole? : % -> Boolean
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R removeZeroes : (Integer,%) -> %      removeZeroes : % -> %
--R retract : % -> UTS                   sample : () -> %
--R taylor : % -> UTS                    taylorRep : % -> UTS
--R truncate : (%,Integer) -> %          variable : % -> Symbol
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (UTS,%) -> % if Coef has FIELD
--R ?*? : (%,UTS) -> % if Coef has FIELD
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (UTS,UTS) -> % if Coef has FIELD
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R ?<? : (%,%) -> Boolean if UTS has ORDSET and Coef has FIELD
--R ?<=? : (%,%) -> Boolean if UTS has ORDSET and Coef has FIELD
--R ?>? : (%,%) -> Boolean if UTS has ORDSET and Coef has FIELD
--R ?>=? : (%,%) -> Boolean if UTS has ORDSET and Coef has FIELD
--R D : (%,Symbol) -> % if UTS has PDRING(SYMBOL) and Coef has FIELD or Coef has *: (Integer,Coe
--R D : (%,List(Symbol)) -> % if UTS has PDRING(SYMBOL) and Coef has FIELD or Coef has *: (Integ
--R D : (%,Symbol,NonNegativeInteger) -> % if UTS has PDRING(SYMBOL) and Coef has FIELD or Coef
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if UTS has PDRING(SYMBOL) and Coef has FI
--R D : % -> % if UTS has DIFRING and Coef has FIELD or Coef has *: (Integer,Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if UTS has DIFRING and Coef has FIELD or Coef has *: (Intege
--R D : (%,(UTS -> UTS),NonNegativeInteger) -> % if Coef has FIELD
--R D : (%,(UTS -> UTS)) -> % if Coef has FIELD
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R abs : % -> % if UTS has OINTDOM and Coef has FIELD
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Integer) -> Coef if Coef has **: (Coef,Integer) -> Coef and Coef has coerce: Symbol ->
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R ceiling : % -> UTS if UTS has INS and Coef has FIELD
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if $ has CHARNZ and UTS has PFECAT and Coef has FIELD or UTS has CHA
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R coerce : Symbol -> % if UTS has RETRACT(SYMBOL) and Coef has FIELD
--R coerce : Coef -> % if Coef has COMRING
--R conditionP : Matrix(%) -> Union(Vector(%),"failed") if $ has CHARNZ and UTS has PFECAT and Coef has FIEL
--R convert : % -> Pattern(Integer) if UTS has KONVERT(PATTERN(INT)) and Coef has FIELD
--R convert : % -> Pattern(Float) if UTS has KONVERT(PATTERN(FLOAT)) and Coef has FIELD
--R convert : % -> InputForm if UTS has KONVERT(INFORM) and Coef has FIELD
--R convert : % -> Float if UTS has REAL and Coef has FIELD
--R convert : % -> DoubleFloat if UTS has REAL and Coef has FIELD
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R denom : % -> UTS if Coef has FIELD
--R denominator : % -> % if Coef has FIELD
--R differentiate : (%,Symbol) -> % if UTS has PDRING(SYMBOL) and Coef has FIELD or Coef has *: (Integer,Coe
--R differentiate : (%,List(Symbol)) -> % if UTS has PDRING(SYMBOL) and Coef has FIELD or Coef has *: (Integ
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if UTS has PDRING(SYMBOL) and Coef has FIELD or Coef
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if UTS has PDRING(SYMBOL) and Coef has FI
--R differentiate : % -> % if UTS has DIFRING and Coef has FIELD or Coef has *: (Integer,Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if UTS has DIFRING and Coef has FIELD or Coef has *: (Intege
--R differentiate : (%,(UTS -> UTS),NonNegativeInteger) -> % if Coef has FIELD
--R differentiate : (%,(UTS -> UTS)) -> % if Coef has FIELD
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,UTS) -> % if UTS has ELTAB(UTS,UTS) and Coef has FIELD
--R ?.? : (%,%) -> % if Integer has SGROUP
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,List(UTS),List(UTS)) -> % if UTS has EVALAB(UTS) and Coef has FIELD
--R eval : (%,UTS,UTS) -> % if UTS has EVALAB(UTS) and Coef has FIELD
--R eval : (%,Equation(UTS)) -> % if UTS has EVALAB(UTS) and Coef has FIELD
--R eval : (%,List(Equation(UTS))) -> % if UTS has EVALAB(UTS) and Coef has FIELD
--R eval : (%,List(Symbol),List(UTS)) -> % if UTS has IEVALAB(SYMBOL,UTS) and Coef has FIELD
--R eval : (%,Symbol,UTS) -> % if UTS has IEVALAB(SYMBOL,UTS) and Coef has FIELD
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Integer) -> Coef
```

```
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R factorPolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%))
--R factorSquareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolyn
--R floor : % -> UTS if UTS has INS and Coef has FIELD
--R fractionPart : % -> % if UTS has EUCDOM and Coef has FIELD
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUniva
--R init : () -> % if UTS has STEP and Coef has FIELD
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variab
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R map : ((UTS -> UTS),%) -> % if Coef has FIELD
--R max : (%,%) -> % if UTS has ORDSET and Coef has FIELD
--R min : (%,%) -> % if UTS has ORDSET and Coef has FIELD
--R monomial : (%,List(SingletonAsOrderedSet),List(Integer)) -> %
--R monomial : (%,SingletonAsOrderedSet,Integer) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R negative? : % -> Boolean if UTS has OINTDOM and Coef has FIELD
--R nextItem : % -> Union(%,"failed") if UTS has STEP and Coef has FIELD
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R numer : % -> UTS if Coef has FIELD
--R numerator : % -> % if Coef has FIELD
--R patternMatch : (%,Pattern(Integer),PatternMatchResult(Integer,%)) -> PatternMatchResult(Inte
--R patternMatch : (%,Pattern(Float),PatternMatchResult(Float,%)) -> PatternMatchResult(Float,%)
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R positive? : % -> Boolean if UTS has OINTDOM and Coef has FIELD
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R ?quo? : (%,%) -> % if Coef has FIELD
--R random : () -> % if UTS has INS and Coef has FIELD
--R rationalFunction : (%,Integer,Integer) -> Fraction(Polynomial(Coef)) if Coef has INTDOM
--R rationalFunction : (%,Integer) -> Fraction(Polynomial(Coef)) if Coef has INTDOM
--R reducedSystem : Matrix(%) -> Matrix(Integer) if UTS has LINEXP(INT) and Coef has FIELD
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(Integer),vec: Vector(Integer)) i
--R reducedSystem : (Matrix(%),Vector(%)) -> Record(mat: Matrix(UTS),vec: Vector(UTS)) if Coef h
--R reducedSystem : Matrix(%) -> Matrix(UTS) if Coef has FIELD
--R ?rem? : (%,%) -> % if Coef has FIELD
--R retract : % -> Symbol if UTS has RETRACT(SYMBOL) and Coef has FIELD
--R retract : % -> Fraction(Integer) if UTS has RETRACT(INT) and Coef has FIELD
```

```
--R retract : % -> Integer if UTS has RETRACT(INT) and Coef has FIELD
--R retractIfCan : % -> Union(Symbol,"failed") if UTS has RETRACT(SYMBOL) and Coef has FIELD
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if UTS has RETRACT(INT) and Coef has FIELD
--R retractIfCan : % -> Union(Integer,"failed") if UTS has RETRACT(INT) and Coef has FIELD
--R retractIfCan : % -> Union(UTS,"failed")
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: Integer,c: Coef)) -> %
--R sign : % -> Integer if UTS has OINTDOM and Coef has FIELD
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R solveLinearPolynomialEquation : (List(SparseUnivariatePolynomial(%)),SparseUnivariatePolynomial(%)) -> U
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if Coef has FIELD
--R squareFreePart : % -> % if Coef has FIELD
--R squareFreePolynomial : SparseUnivariatePolynomial(%) -> Factored(SparseUnivariatePolynomial(%)) if UTS h
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R taylorIfCan : % -> Union(UTS,"failed")
--R terms : % -> Stream(Record(k: Integer,c: Coef))
--R truncate : (%,Integer,Integer) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R wholePart : % -> UTS if UTS has EUCDOM and Coef has FIELD
--R
--E 1

)spool
)lisp (bye)
```

———-


— UnivariateLaurentSeriesConstructor.help —

```
=====================================================================
UnivariateLaurentSeriesConstructor examples
=====================================================================

See Also:
o )show UnivariateLaurentSeriesConstructor
```

———-

22.3.1 UnivariateLaurentSeriesConstructor (ULSCONS)



See

⇒ “UnivariateLaurentSeries” (ULS) 22.2.1 on page 2762

Exports:

0	1	abs
acos	acosh	acot
acoth	acsc	acsch
approximate	asec	asech
asin	asinh	associates?
atan	atanh	ceiling
center	characteristic	charthRoot
coefficient	coerce	complete
conditionP	convert	cos
cosh	cot	coth
csc	csch	D
degree	denom	denominator
differentiate	divide	extend
euclideanSize	eval	exp
expressIdealMember	exquo	extendedEuclidean
factor	factorPolynomial	factorSquareFreePolynomial
floor	fractionPart	gcd
gcdPolynomial	hash	init
integrate	inv	latex
laurent	lcm	leadingCoefficient
leadingMonomial	log	map
max	min	monomial
monomial?	multiEuclidean	multiplyCoefficients
multiplyExponents	negative?	nextItem
nthRoot	numer	numerator
one?	order	patternMatch
pi	pole?	positive?
prime?	principalIdeal	random
rationalFunction	recip	reducedSystem
reductum	removeZeroes	retract
retractIfCan	sample	sec
sech	series	sign
sin	sinh	sizeLess?
solveLinearPolynomialEquation	sqrt	squareFree
squareFreePart	squareFreePolynomial	subtractIfCan
tan	tanh	taylor
taylorIfCan	taylorRep	terms
truncate	unit?	unitCanonical
unitNormal	variable	variables
wholePart	zero?	?*?
?**?	?+?	?-?
-?	?=?	?^?
?.?	?~=?	?/?
?<?	?<=?	?>?
?>=?	?quo?	?rem?

— domain ULSCONS UnivariateLaurentSeriesConstructor —

```
)abbrev domain ULSCONS UnivariateLaurentSeriesConstructor
++ Authors: Bill Burge, Clifton J. Williamson
++ Date Created: August 1988
++ Date Last Updated: 17 June 1996
++ Fix History:
++ 14 June 1996: provided missing exquo: (%,%) -> % (Frederic Lehobey)
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: series, Laurent, Taylor
++ Examples:
++ References:
++ Description:
++ This package enables one to construct a univariate Laurent series
++ domain from a univariate Taylor series domain. Univariate
++ Laurent series are represented by a pair \spad{[n,f(x)]}, where n is
++ an arbitrary integer and \spad{f(x)} is a Taylor series.  This pair
++ represents the Laurent series \spad{x**n * f(x)}.

UnivariateLaurentSeriesConstructor(Coef,UTS):_
 Exports == Implementation where
  Coef    : Ring
  UTS     : UnivariateTaylorSeriesCategory Coef
  I     ==> Integer
  L     ==> List
  NNI   ==> NonNegativeInteger
  OUT   ==> OutputForm
  P     ==> Polynomial Coef
  RF    ==> Fraction Polynomial Coef
  RN    ==> Fraction Integer
  ST    ==> Stream Coef
  TERM  ==> Record(k:I,c:Coef)
  monom ==> monomial$UTS
  EFULS ==> ElementaryFunctionsUnivariateLaurentSeries(Coef,UTS,%)
  STTAYLOR ==> StreamTaylorSeriesOperations Coef

  Exports ==> UnivariateLaurentSeriesConstructorCategory(Coef,UTS)

  Implementation ==> add

--% representation

    Rep := Record(expon:I,ps:UTS)

    getExpon : % -> I
    getUTS   : % -> UTS
```

```
    getExpon x == x.expon
    getUTS   x == x.ps

--% creation and destruction

    laurent(n,psr) == [n,psr]
    taylorRep x    == getUTS x
    degree x       == getExpon x

    0 == laurent(0,0)
    1 == laurent(0,1)

    monomial(s,e) == laurent(e,s::UTS)

    coerce(uts:UTS):% == laurent(0,uts)
    coerce(r:Coef):%  == r :: UTS  :: %
    coerce(i:I):%     == i :: Coef :: %

    taylorIfCan uls ==
      n := getExpon uls
      n < 0 =>
        uls := removeZeroes(-n,uls)
        getExpon(uls) < 0 => "failed"
        getUTS uls
      n = 0 => getUTS uls
      getUTS(uls) * monom(1,n :: NNI)

    taylor uls ==
      (uts := taylorIfCan uls) case "failed" =>
        error "taylor: Laurent series has a pole"
      uts :: UTS

    termExpon: TERM -> I
    termExpon term == term.k
    termCoef: TERM -> Coef
    termCoef term == term.c
    rec: (I,Coef) -> TERM
    rec(exponent,coef) == [exponent,coef]

    recs: (ST,I) -> Stream TERM
    recs(st,n) == delay
      empty? st => empty()
      zero? (coef := frst st) => recs(rst st,n + 1)
      concat(rec(n,coef),recs(rst st,n + 1))

    terms x == recs(coefficients getUTS x,getExpon x)

    recsToCoefs: (Stream TERM,I) -> ST
    recsToCoefs(st,n) == delay
```

```
      empty? st => empty()
      term := frst st; ex := termExpon term
      n = ex => concat(termCoef term,recsToCoefs(rst st,n + 1))
      concat(0,recsToCoefs(rst st,n + 1))

    series st ==
      empty? st => 0
      ex := termExpon frst st
      laurent(ex,series recsToCoefs(st,ex))

--% normalizations

    removeZeroes x ==
      empty? coefficients(xUTS := getUTS x) => 0
      coefficient(xUTS,0) = 0 =>
        removeZeroes laurent(getExpon(x) + 1,quoByVar xUTS)
      x

    removeZeroes(n,x) ==
      n <= 0 => x
      empty? coefficients(xUTS := getUTS x) => 0
      coefficient(xUTS,0) = 0 =>
        removeZeroes(n - 1,laurent(getExpon(x) + 1,quoByVar xUTS))
      x

--% predicates

    x = y ==
      EQ(x,y)$Lisp => true
      (expDiff := getExpon(x) - getExpon(y)) = 0 =>
        getUTS(x) = getUTS(y)
      abs(expDiff) > _$streamCount$Lisp => false
      expDiff > 0 =>
        getUTS(x) * monom(1,expDiff :: NNI) = getUTS(y)
      getUTS(y) * monom(1,(- expDiff) :: NNI) = getUTS(x)

    pole? x ==
      (n := degree x) >= 0 => false
      x := removeZeroes(-n,x)
      degree x < 0

--% arithmetic

    x + y  ==
      n := getExpon(x) - getExpon(y)
      n >= 0 =>
        laurent(getExpon y,getUTS(y) + getUTS(x) * monom(1,n::NNI))
      laurent(getExpon x,getUTS(x) + getUTS(y) * monom(1,(-n)::NNI))

    x - y  ==
```

```
      n := getExpon(x) - getExpon(y)
      n >= 0 =>
        laurent(getExpon y,getUTS(x) * monom(1,n::NNI) - getUTS(y))
      laurent(getExpon x,getUTS(x) - getUTS(y) * monom(1,(-n)::NNI))

    x:% * y:% == laurent(getExpon x + getExpon y,getUTS x * getUTS y)

    x:% ** n:NNI ==
      zero? n =>
        zero? x => error "0 ** 0 is undefined"
        1
      laurent(n * getExpon(x),getUTS(x) ** n)

    recip x ==
      x := removeZeroes(1000,x)
      zero? coefficient(x,d := degree x) => "failed"
      (uts := recip getUTS x) case "failed" => "failed"
      laurent(-d,uts :: UTS)

    elt(uls1:%,uls2:%) ==
      (uts := taylorIfCan uls2) case "failed" =>
        error "elt: second argument must have positive order"
      uts2 := uts :: UTS
      not zero? coefficient(uts2,0) =>
        error "elt: second argument must have positive order"
      if (deg := getExpon uls1) < 0 then uls1 := removeZeroes(-deg,uls1)
      (deg := getExpon uls1) < 0 =>
        (recipr := recip(uts2 :: %)) case "failed" =>
          error "elt: second argument not invertible"
        uts1 := taylor(uls1 * monomial(1,-deg))
        (elt(uts1,uts2) :: %) * (recipr :: %) ** ((-deg) :: NNI)
      elt(taylor uls1,uts2) :: %

    eval(uls:%,r:Coef) ==
      if (n := getExpon uls) < 0 then uls := removeZeroes(-n,uls)
      uts := getUTS uls
      (n := getExpon uls) < 0 =>
        zero? r => error "eval: 0 raised to negative power"
        (recipr := recip r) case "failed" =>
          error "eval: non-unit raised to negative power"
        (recipr :: Coef) ** ((-n) :: NNI) *$STTAYLOR eval(uts,r)
      zero? n => eval(uts,r)
      r ** (n :: NNI) *$STTAYLOR eval(uts,r)

--% values

    variable x == variable getUTS x
    center   x == center   getUTS x

    coefficient(x,n) ==
```

```
      a := n - getExpon(x)
      a >= 0 => coefficient(getUTS x,a :: NNI)
      0

    elt(x:%,n:I) == coefficient(x,n)

--% other functions

    order x == getExpon x + order getUTS x
    order(x,n) ==
      (m := n - (e := getExpon x)) < 0 => n
      e + order(getUTS x,m :: NNI)

    truncate(x,n) ==
      (m := n - (e := getExpon x)) < 0 => 0
      laurent(e,truncate(getUTS x,m :: NNI))

    truncate(x,n1,n2) ==
      if n2 < n1 then (n1,n2) := (n2,n1)
      (m1 := n1 - (e := getExpon x)) < 0 => truncate(x,n2)
      laurent(e,truncate(getUTS x,m1 :: NNI,(n2 - e) :: NNI))

    if Coef has IntegralDomain then
      rationalFunction(x,n) ==
        (m := n - (e := getExpon x)) < 0 => 0
        poly := polynomial(getUTS x,m :: NNI) :: RF
        zero? e => poly
        v := variable(x) :: RF; c := center(x) :: P :: RF
        positive? e => poly * (v - c) ** (e :: NNI)
        poly / (v - c) ** ((-e) :: NNI)

      rationalFunction(x,n1,n2) ==
        if n2 < n1 then (n1,n2) := (n2,n1)
        (m1 := n1 - (e := getExpon x)) < 0 => rationalFunction(x,n2)
        poly := polynomial(getUTS x,m1 :: NNI,(n2 - e) :: NNI) :: RF
        zero? e => poly
        v := variable(x) :: RF; c := center(x) :: P :: RF
        positive? e => poly * (v - c) ** (e :: NNI)
        poly / (v - c) ** ((-e) :: NNI)

      --  La fonction < exquo > manque dans laurent.spad,
      --les lignes suivantes le mettent en evidence :
      --
      --ls := laurent(0,series [i for i in 1..])$ULS(INT,x,0)
      ---- missing function in laurent.spad of Axiom 2.0a version of
      ---- Friday March 10, 1995 at 04:15:22 on 615:
      --exquo(ls,ls)
      --
      --  Je l'ai ajoutee a laurent.spad.
      --
```

```
    --Frederic Lehobey
    x exquo y ==
      x := removeZeroes(1000,x)
      y := removeZeroes(1000,y)
      zero? coefficient(y, d := degree y) => "failed"
      (uts := (getUTS x) exquo (getUTS y)) case "failed" => "failed"
      laurent(degree x-d,uts :: UTS)

  if Coef has coerce: Symbol -> Coef then
    if Coef has "**": (Coef,I) -> Coef then

      approximate(x,n) ==
        (m := n - (e := getExpon x)) < 0 => 0
        app := approximate(getUTS x,m :: NNI)
        zero? e => app
        app * ((variable(x) :: Coef) - center(x)) ** e

  complete x == laurent(getExpon x,complete getUTS x)
  extend(x,n) ==
    e := getExpon x
    (m := n - e) < 0 => x
    laurent(e,extend(getUTS x,m :: NNI))

  map(f:Coef -> Coef,x:%) == laurent(getExpon x,map(f,getUTS x))

  multiplyCoefficients(f,x) ==
    e := getExpon x
    laurent(e,multiplyCoefficients((z1:I):Coef +-> f(e + z1),getUTS x))

  multiplyExponents(x,n) ==
    laurent(n * getExpon x,multiplyExponents(getUTS x,n))

  differentiate x ==
    e := getExpon x
    laurent(e - 1,
            multiplyCoefficients((z1:I):Coef +-> (e + z1)::Coef,getUTS x))

  if Coef has PartialDifferentialRing(Symbol) then
    differentiate(x:%,s:Symbol) ==
      (s = variable(x)) => differentiate x
      map((z1:Coef):Coef +-> differentiate(z1,s),x)
                              - differentiate(center x,s)*differentiate(x)

  characteristic() == characteristic()$Coef

  if Coef has Field then

    retract(x:%):UTS                       == taylor x
    retractIfCan(x:%):Union(UTS,"failed") == taylorIfCan x
```

```
      (x:%) ** (n:I) ==
        zero? n =>
          zero? x => error "0 ** 0 is undefined"
          1
        n > 0 => laurent(n * getExpon(x),getUTS(x) ** (n :: NNI))
        xInv := inv x; minusN := (-n) :: NNI
        laurent(minusN * getExpon(xInv),getUTS(xInv) ** minusN)

      (x:UTS) * (y:%) == (x :: %) * y
      (x:%) * (y:UTS) == x * (y :: %)

      inv x ==
        (xInv := recip x) case "failed" =>
          error "multiplicative inverse does not exist"
        xInv :: %

      (x:%) / (y:%) ==
        (yInv := recip y) case "failed" =>
          error "inv: multiplicative inverse does not exist"
        x * (yInv :: %)

      (x:UTS) / (y:UTS) == (x :: %) / (y :: %)

      numer x ==
        (n := degree x) >= 0 => taylor x
        x := removeZeroes(-n,x)
        (n := degree x) = 0 => taylor x
        getUTS x

      denom x ==
        (n := degree x) >= 0 => 1
        x := removeZeroes(-n,x)
        (n := degree x) = 0 => 1
        monom(1,(-n) :: NNI)

--% algebraic and transcendental functions

    if Coef has Algebra Fraction Integer then

      coerce(r:RN) == r :: Coef :: %

      if Coef has Field then
         (x:%) ** (r:RN) == x **$EFULS r

      exp x   == exp(x)$EFULS
      log x   == log(x)$EFULS
      sin x   == sin(x)$EFULS
      cos x   == cos(x)$EFULS
      tan x   == tan(x)$EFULS
      cot x   == cot(x)$EFULS
```

```
sec x   == sec(x)$EFULS
csc x   == csc(x)$EFULS
asin x  == asin(x)$EFULS
acos x  == acos(x)$EFULS
atan x  == atan(x)$EFULS
acot x  == acot(x)$EFULS
asec x  == asec(x)$EFULS
acsc x  == acsc(x)$EFULS
sinh x  == sinh(x)$EFULS
cosh x  == cosh(x)$EFULS
tanh x  == tanh(x)$EFULS
coth x  == coth(x)$EFULS
sech x  == sech(x)$EFULS
csch x  == csch(x)$EFULS
asinh x == asinh(x)$EFULS
acosh x == acosh(x)$EFULS
atanh x == atanh(x)$EFULS
acoth x == acoth(x)$EFULS
asech x == asech(x)$EFULS
acsch x == acsch(x)$EFULS

ratInv: I -> Coef
ratInv n ==
  zero? n => 1
  inv(n :: RN) :: Coef

integrate x ==
  not zero? coefficient(x,-1) =>
    error "integrate: series has term of order -1"
  e := getExpon x
  laurent(e+1,multiplyCoefficients((z:I):Coef+->ratInv(e+1+z),getUTS x))

if Coef has integrate: (Coef,Symbol) -> Coef and _
   Coef has variables: Coef -> List Symbol then
  integrate(x:%,s:Symbol) ==
    (s = variable(x)) => integrate x
    not entry?(s,variables center x)
       => map((z1:Coef):Coef+->integrate(z1,s),x)
    error "integrate: center is a function of variable of integration"

if Coef has TranscendentalFunctionCategory and _
   Coef has PrimitiveFunctionCategory and _
   Coef has AlgebraicallyClosedFunctionSpace Integer then

  integrateWithOneAnswer: (Coef,Symbol) -> Coef
  integrateWithOneAnswer(f,s) ==
    res := integrate(f,s)$FunctionSpaceIntegration(I,Coef)
    res case Coef => res :: Coef
    first(res :: List Coef)
```

```
    integrate(x:%,s:Symbol) ==
      (s = variable(x)) => integrate x
      not entry?(s,variables center x) =>
        map((z1:Coef):Coef +-> integrateWithOneAnswer(z1,s),x)
      error "integrate: center is a function of variable of integration"

termOutput:(I,Coef,OUT) -> OUT
termOutput(k,c,vv) ==
-- creates a term c * vv ** k
  k = 0 => c :: OUT
  mon :=
    k = 1 => vv
    vv ** (k :: OUT)
  c = 1 => mon
  c = -1 => -mon
  (c :: OUT) * mon

showAll?:() -> Boolean
-- check a global Lisp variable
showAll?() == true

termsToOutputForm:(I,ST,OUT) -> OUT
termsToOutputForm(m,uu,xxx) ==
  l : L OUT := empty()
  empty? uu => (0$Coef) :: OUT
  n : NNI ; count : NNI := _$streamCount$Lisp
  for n in 0..count while not empty? uu repeat
    if frst(uu) ^= 0 then
      l := concat(termOutput((n :: I) + m,frst(uu),xxx),l)
    uu := rst uu
  if showAll?() then
    for n in (count + 1).. while explicitEntries? uu and _
           not eq?(uu,rst uu) repeat
      if frst(uu) ^= 0 then
        l := concat(termOutput((n::I) + m,frst(uu),xxx),l)
      uu := rst uu
  l :=
    explicitlyEmpty? uu => l
    eq?(uu,rst uu) and frst uu = 0 => l
    concat(prefix("O" :: OUT,[xxx ** ((n :: I) + m) :: OUT]),l)
  empty? l => (0$Coef) :: OUT
  reduce("+",reverse_! l)

coerce(x:%):OUT ==
  x := removeZeroes(_$streamCount$Lisp,x)
  m := degree x
  uts := getUTS x
  p := coefficients uts
  var := variable uts; cen := center uts
  xxx :=
```

```
        zero? cen => var :: OUT
        paren(var :: OUT - cen :: OUT)
      termsToOutputForm(m,p,xxx)
```

———-

— **ULSCONS.dotabb** —

```
"ULSCONS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ULSCONS"]
"ACFS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACFS"]
"ULSCCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ULSCCAT"]
"ULSCONS" -> "ULSCCAT"
"ULSCONS" -> "ACFS"
```

———-

22.4 domain UP UnivariatePolynomial

— **UnivariatePolynomial.input** —

```
)set break resume
)sys rm -f UnivariatePolynomial.output
)spool UnivariatePolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 35
(p,q) : UP(x,INT)
--R
--R                                                                Type: Void
--E 1

--S 2 of 35
p := (3*x-1)**2 * (2*x + 8)
--R
--R
--R           3      2
--R   (2)  18x  + 60x  - 46x + 8
--R                                      Type: UnivariatePolynomial(x,Integer)
--E 2

--S 3 of 35
q := (1 - 6*x + 9*x**2)**2
--R
```

```
--R
--R           4       3      2
--R   (3)  81x  - 108x  + 54x  - 12x + 1
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 3

--S 4 of 35
p**2 + p*q
--R
--R
--R             7        6        5         4        3        2
--R   (4)  1458x  + 3240x  - 7074x  + 10584x  - 9282x  + 4120x  - 878x + 72
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 4

--S 5 of 35
leadingCoefficient p
--R
--R
--R   (5)  18
--R                                                        Type: PositiveInteger
--E 5

--S 6 of 35
degree p
--R
--R
--R   (6)  3
--R                                                        Type: PositiveInteger
--E 6

--S 7 of 35
reductum p
--R
--R
--R           2
--R   (7)  60x  - 46x + 8
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 7

--S 8 of 35
gcd(p,q)
--R
--R
--R          2
--R   (8)  9x  - 6x + 1
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 8

--S 9 of 35
```

```
lcm(p,q)
--R
--R
--R            5       4       3       2
--R   (9)  162x  + 432x  - 756x  + 408x  - 94x + 8
--R                                       Type: UnivariatePolynomial(x,Integer)
--E 9

--S 10 of 35
resultant(p,q)
--R
--R
--R   (10)  0
--R                                                  Type: NonNegativeInteger
--E 10

--S 11 of 35
D p
--R
--R
--R            2
--R   (11)  54x  + 120x - 46
--R                                       Type: UnivariatePolynomial(x,Integer)
--E 11

--S 12 of 35
p(2)
--R
--R
--R   (12)  300
--R                                                    Type: PositiveInteger
--E 12

--S 13 of 35
p(q)
--R
--R
--R   (13)
--R             12            11            10            9            8
--R     9565938x   - 38263752x   + 70150212x   - 77944680x  + 58852170x
--R   +
--R               7           6           5           4          3         2
--R     - 32227632x  + 13349448x  - 4280688x  + 1058184x  - 192672x  + 23328x
--R   +
--R     - 1536x + 40
--R                                       Type: UnivariatePolynomial(x,Integer)
--E 13

--S 14 of 35
q(p)
```

```
--R
--R
--R   (14)
--R             12             11             10             9              8
--R     8503056x   + 113374080x   + 479950272x   + 404997408x  - 1369516896x
--R   +
--R                7              6              5              4             3
--R     - 626146848x  + 2939858712x  - 2780728704x  + 1364312160x  - 396838872x
--R   +
--R              2
--R     69205896x  - 6716184x + 279841
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 14

--S 15 of 35
l := coefficients p
--R
--R
--R   (15)  [18,60,- 46,8]
--R                                                          Type: List(Integer)
--E 15

--S 16 of 35
reduce(gcd,l)
--R
--R
--R   (16)  2
--R                                                       Type: PositiveInteger
--E 16

--S 17 of 35
content p
--R
--R
--R   (17)  2
--R                                                       Type: PositiveInteger
--E 17

--S 18 of 35
ux := (x**4+2*x+3)::UP(x,INT)
--R
--R
--R          4
--R   (18)  x  + 2x + 3
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 18

--S 19 of 35
vectorise(ux,5)
--R
```

```
--R
--R   (19)  [3,2,0,0,1]
--R                                                        Type: Vector(Integer)
--E 19

--S 20 of 35
squareTerms(p) ==   reduce(+,[t**2 for t in monomials p])
--R
--R                                                                   Type: Void
--E 20

--S 21 of 35
p
--R
--R
--R            3      2
--R   (21)  18x  + 60x  - 46x + 8
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 21

--S 22 of 35
squareTerms p
--R
--R   Compiling function squareTerms with type UnivariatePolynomial(x,
--R      Integer) -> UnivariatePolynomial(x,Integer)
--R
--R             6        4        2
--R   (22)  324x  + 3600x  + 2116x  + 64
--R                                        Type: UnivariatePolynomial(x,Integer)
--E 22

--S 23 of 35
(r,s) : UP(a1,FRAC INT)
--R
--R                                                                   Type: Void
--E 23

--S 24 of 35
r := a1**2 - 2/3
--R
--R
--R           2   2
--R   (24)  a1  - -
--R               3
--R                              Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 24

--S 25 of 35
s := a1 + 4
--R
```

```
--R
--R   (25)  a1 + 4
--R                                Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 25

--S 26 of 35
r quo s
--R
--R
--R   (26)  a1 - 4
--R                                Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 26

--S 27 of 35
r rem s
--R
--R
--R         46
--R   (27)  --
--R          3
--R                                Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 27

--S 28 of 35
d := divide(r, s)
--R
--R
--R                                        46
--R   (28)  [quotient= a1 - 4,remainder= --]
--R                                         3
--IType: Record(quotient: UnivariatePolynomial(a1,Fraction(Integer)),...
--E 28

--S 29 of 35
r - (d.quotient * s + d.remainder)
--R
--R
--R   (29)  0
--R                                Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 29

--S 30 of 35
integrate r
--R
--R
--R         1   3   2
--R   (30)  - a1  - - a1
--R         3       3
--R                                Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 30
```

```
--S 31 of 35
integrate s
--R
--R
--R         1   2
--R   (31)  - a1  + 4a1
--R         2
--R                              Type: UnivariatePolynomial(a1,Fraction(Integer))
--E 31

--S 32 of 35
t : UP(a1,FRAC POLY INT)
--R
--R                                                                    Type: Void
--E 32

--S 33 of 35
t := a1**2 - a1/b2 + (b1**2-b1)/(b2+3)
--R
--R
--R                           2
--R           2    1      b1  - b1
--R   (33)  a1  - -- a1 + --------
--R               b2       b2 + 3
--R                 Type: UnivariatePolynomial(a1,Fraction(Polynomial(Integer)))
--E 33

--S 34 of 35
u : FRAC POLY INT := t
--R
--R
--R           2  2      2           2
--R         a1 b2  + (b1  - b1 + 3a1  - a1)b2 - 3a1
--R   (34)  ---------------------------------------
--R                          2
--R                        b2  + 3b2
--R                                          Type: Fraction(Polynomial(Integer))
--E 34

--S 35 of 35
u :: UP(b1,?)
--R
--R
--R                                    2
--R            1     2      1        a1 b2 - a1
--R   (35)  ------ b1  - ------ b1 + ----------
--R         b2 + 3       b2 + 3          b2
--R                 Type: UnivariatePolynomial(b1,Fraction(Polynomial(Integer)))
--E 35
```

```
)spool
)lisp (bye)
```

———-

— UnivariatePolynomial.help —

```
=====================================================================
UnivariatePolynomial examples
=====================================================================

The domain constructor UnivariatePolynomial (abbreviated UP) creates
domains of univariate polynomials in a specified variable.  For
example, the domain UP(a1,POLY FRAC INT) provides polynomials in the
single variable a1 whose coefficients are general polynomials with
rational number coefficients.

Restriction: Axiom does not allow you to create types where
UnivariatePolynomial is contained in the coefficient type of
Polynomial. Therefore, UP(x,POLY INT) is legal but POLY UP(x,INT)
is not.

UP(x,INT) is the domain of polynomials in the single variable x with
integer coefficients.

  (p,q) : UP(x,INT)
                          Type: Void

  p := (3*x-1)**2 * (2*x + 8)
       3      2
    18x  + 60x  - 46x + 8
                          Type: UnivariatePolynomial(x,Integer)

  q := (1 - 6*x + 9*x**2)**2
       4       3      2
    81x  - 108x  + 54x  - 12x + 1
                          Type: UnivariatePolynomial(x,Integer)

The usual arithmetic operations are available for univariate polynomials.

  p**2 + p*q
         7        6        5         4        3        2
    1458x  + 3240x  - 7074x  + 10584x  - 9282x  + 4120x  - 878x + 72
                          Type: UnivariatePolynomial(x,Integer)

The operation leadingCoefficient extracts the coefficient of the term
of highest degree.

  leadingCoefficient p
```

```
   18
                        Type: PositiveInteger
```

The operation degree returns the degree of the polynomial. Since the polynomial has only one variable, the variable is not supplied to operations like degree.

```
  degree p
    3
                        Type: PositiveInteger
```

The reductum of the polynomial, the polynomial obtained by subtracting the term of highest order, is returned by reductum.

```
  reductum p
       2
    60x  - 46x + 8
                        Type: UnivariatePolynomial(x,Integer)
```

The operation gcd computes the greatest common divisor of two polynomials.

```
  gcd(p,q)
      2
    9x  - 6x + 1
                        Type: UnivariatePolynomial(x,Integer)
```

The operation lcm computes the least common multiple.

```
  lcm(p,q)
        5       4       3       2
    162x  + 432x  - 756x  + 408x  - 94x + 8
                        Type: UnivariatePolynomial(x,Integer)
```

The operation resultant computes the resultant of two univariate polynomials. In the case of p and q, the resultant is 0 because they share a common root.

```
  resultant(p,q)
    0
                        Type: NonNegativeInteger
```

To compute the derivative of a univariate polynomial with respect to its variable, use the function D.

```
  D p
       2
    54x  + 120x - 46
                        Type: UnivariatePolynomial(x,Integer)
```

Univariate polynomials can also be used as if they were functions. To

```
evaluate a univariate polynomial at some point, apply the polynomial
to the point.

  p(2)
    300
                          Type: PositiveInteger

The same syntax is used for composing two univariate polynomials, i.e.
substituting one polynomial for the variable in another.  This substitutes
q for the variable in p.

  p(q)
             12            11            10            9            8
    9565938x   - 38263752x   + 70150212x   - 77944680x  + 58852170x
   +
                7            6           5           4          3         2
    - 32227632x  + 13349448x  - 4280688x  + 1058184x  - 192672x  + 23328x
   +
    - 1536x + 40
                          Type: UnivariatePolynomial(x,Integer)

This substitutes p for the variable in q.

  q(p)
             12             11             10             9              8
    8503056x   + 113374080x   + 479950272x   + 404997408x  - 1369516896x
   +
                 7              6              5              4             3
    - 626146848x  + 2939858712x  - 2780728704x  + 1364312160x  - 396838872x
   +
              2
    69205896x  - 6716184x + 279841
                          Type: UnivariatePolynomial(x,Integer)

To obtain a list of coefficients of the polynomial, use coefficients.

  l := coefficients p
    [18,60,- 46,8]
                          Type: List Integer

From this you can use gcd and reduce to compute the content of the polynomial.

  reduce(gcd,l)
    2
                          Type: PositiveInteger

Alternatively (and more easily), you can just call content.

  content p
    2
```

```
                          Type: PositiveInteger
```

Note that the operation coefficients omits the zero coefficients from the list. Sometimes it is useful to convert a univariate polynomial to a vector whose i-th position contains the degree i-1 coefficient of the polynomial.

```
  ux := (x**4+2*x+3)::UP(x,INT)
     4
    x  + 2x + 3
                          Type: UnivariatePolynomial(x,Integer)
```

To get a complete vector of coefficients, use the operation vectorise, which takes a univariate polynomial and an integer denoting the length of the desired vector.

```
  vectorise(ux,5)
    [3,2,0,0,1]
                          Type: Vector Integer
```

It is common to want to do something to every term of a polynomial, creating a new polynomial in the process.

This is a function for iterating across the terms of a polynomial, squaring each term.

```
  squareTerms(p) ==   reduce(+,[t**2 for t in monomials p])
                          Type: Void
```

Recall what p looked like.

```
  p
       3      2
    18x  + 60x  - 46x + 8
                          Type: UnivariatePolynomial(x,Integer)
```

We can demonstrate squareTerms on p.

```
  squareTerms p
        6        4        2
    324x  + 3600x  + 2116x  + 64
                          Type: UnivariatePolynomial(x,Integer)
```

When the coefficients of the univariate polynomial belong to a field, it is possible to compute quotients and remainders. For example, when the coefficients are rational numbers, as opposed to integers. The important property of a field is that non-zero elements can be divided and produce another element. The quotient of the integers 2 and 3 is not another integer.

```
  (r,s) : UP(a1,FRAC INT)
                          Type: Void

  r := a1**2 - 2/3
      2   2
    a1  - -
          3
                          Type: UnivariatePolynomial(a1,Fraction Integer)

  s := a1 + 4
    a1 + 4
                          Type: UnivariatePolynomial(a1,Fraction Integer)
```

When the coefficients are rational numbers or rational expressions, the operation quo computes the quotient of two polynomials.

```
  r quo s
    a1 - 4
                          Type: UnivariatePolynomial(a1,Fraction Integer)
```

The operation rem computes the remainder.

```
  r rem s
    46
    --
     3
                          Type: UnivariatePolynomial(a1,Fraction Integer)
```

The operation divide can be used to return a record of both components.

```
  d := divide(r, s)
                                  46
    [quotient= a1 - 4,remainder= --]
                                   3
       Type: Record(quotient: UnivariatePolynomial(a1,Fraction Integer),
                    remainder: UnivariatePolynomial(a1,Fraction Integer))
```

Now we check the arithmetic!

```
  r - (d.quotient * s + d.remainder)
    0
                          Type: UnivariatePolynomial(a1,Fraction Integer)
```

It is also possible to integrate univariate polynomials when the coefficients belong to a field.

```
  integrate r
    1   3   2
    - a1  - - a1
    3       3
```

```
                          Type: UnivariatePolynomial(a1,Fraction Integer)
```

```
integrate s
  1   2
  - a1  + 4a1
  2
                          Type: UnivariatePolynomial(a1,Fraction Integer)
```

One application of univariate polynomials is to see expressions in terms of a specific variable.

We start with a polynomial in a1 whose coefficients are quotients of polynomials in b1 and b2.

```
t : UP(a1,FRAC POLY INT)
                          Type: Void
```

Since in this case we are not talking about using multivariate polynomials in only two variables, we use Polynomial. We also use Fraction because we want fractions.

```
t := a1**2 - a1/b2 + (b1**2-b1)/(b2+3)
                    2
     2    1      b1  - b1
   a1  - -- a1 + --------
         b2       b2 + 3
                  Type: UnivariatePolynomial(a1,Fraction Polynomial Integer)
```

We push all the variables into a single quotient of polynomials.


```
u : FRAC POLY INT := t
     2  2      2           2
    a1 b2  + (b1  - b1 + 3a1  - a1)b2 - 3a1
    ---------------------------------------
                    2
                   b2  + 3b2
                         Type: Fraction Polynomial Integer
```

Alternatively, we can view this as a polynomial in the variable This is a mode-directed conversion: you indicate as much of the structure as you care about and let Axiom decide on the full type and how to do the transformation.

```
u :: UP(b1,?)
                              2
       1     2      1        a1 b2 - a1
    ------ b1  - ------ b1 + ----------
    b2 + 3       b2 + 3          b2
                  Type: UnivariatePolynomial(b1,Fraction Polynomial Integer)
```

```
See Also:
o )help MultivariatePolynomial
o )help DistributedMultivariatePolynomial
o )show UnivariatePolynomial
```

22.4.1 UnivariatePolynomial (UP)



See

⇒ “FreeModule” (FM) 7.30.1 on page 983
⇒ “PolynomialRing” (PR) 17.27.1 on page 2058
⇒ “SparseUnivariatePolynomial” (SUP) 20.18.1 on page 2434

Exports:

0	1
associates?	binomThmExpt
characteristic	charthRoot
coefficient	coefficients
coerce	composite
conditionP	content
convert	D
degree	differentiate
discriminant	divide
divideExponents	elt
euclideanSize	eval
expressIdealMember	exquo
extendedEuclidean	factor
factorPolynomial	factorSquareFreePolynomial
fmecg	gcd
gcdPolynomial	ground
ground?	hash
init	integrate
isExpt	isPlus
isTimes	karatsubaDivide
latex	lcm
leadingCoefficient	leadingMonomial
mainVariable	makeSUP
mapExponents	map
max	min
minimumDegree	monicDivide
monomial	monomial?
monomials	multiEuclidean
multiplyExponents	multivariate
nextItem	numberOfMonomials
one?	order
patternMatch	pomopo!
prime?	primitivePart
primitiveMonomials	principalIdeal
pseudoDivide	pseudoQuotient
pseudoRemainder	recip
reducedSystem	reductum
resultant	retract
retractIfCan	sample
separate	shiftLeft
shiftRight	sizeLess?
solveLinearPolynomialEquation	squareFree
squareFreePart	squareFreePolynomial
subResultantGcd	subtractIfCan
totalDegree	totalDegree
unit?	unitCanonical
unitNormal	univariate
unmakeSUP	variables
vectorise	zero?
?*?	?**?
?+?	?-?
-?	?=?
?^?	?.?
?~=?	?/?
?<?	?<=?

— domain UP UnivariatePolynomial —

```
)abbrev domain UP UnivariatePolynomial
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions: Ring, monomial, coefficient, reductum, differentiate,
++ elt, map, resultant, discriminant
++ Related Constructors: SparseUnivariatePolynomial, MultivariatePolynomial
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain represents univariate polynomials in some symbol
++ over arbitrary (not necessarily commutative) coefficient rings.
++ The representation is sparse
++ in the sense that only non-zero terms are represented.
++ Note that if the coefficient ring is a field, then this domain
++ forms a euclidean domain.

UnivariatePolynomial(x:Symbol, R:Ring):
  UnivariatePolynomialCategory(R) with
    coerce: Variable(x) -> %
      ++ coerce(x) converts the variable x to a univariate polynomial.
    fmecg: (%,NonNegativeInteger,R,%) -> %
        ++ fmecg(p1,e,r,p2) finds x : p1 - r * x**e * p2
   == SparseUnivariatePolynomial(R)   add
    Rep:=SparseUnivariatePolynomial(R)
    coerce(p:%):OutputForm  == outputForm(p, outputForm x)
    coerce(v:Variable(x)):% == monomial(1, 1)
```

———-

— UP.dotabb —

```
"UP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"UP" -> "PFECAT"
```

———-

22.5 domain UPXS UnivariatePuiseuxSeries

— UnivariatePuiseuxSeries.input —

```
)set break resume
)sys rm -f UnivariatePuiseuxSeries.output
)spool UnivariatePuiseuxSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariatePuiseuxSeries
--R
--R UnivariatePuiseuxSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for UnivariatePuiseuxSeries is UPXS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for UPXS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coerce : Variable(var) -> %          coerce : Integer -> %
--R coerce : % -> OutputForm             complete : % -> %
--R degree : % -> Fraction(Integer)      hash : % -> SingleInteger
--R latex : % -> String                  leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %             map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean             one? : % -> Boolean
--R order : % -> Fraction(Integer)       pole? : % -> Boolean
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R sample : () -> %                     variable : % -> Symbol
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
```

```
--R D : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRING(SYMB
--R D : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRIN
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and C
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Integer),Coef) -
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Fraction(Integer)) -> Coef if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,Fraction(Integer)) -> Coef
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R coerce : UnivariateTaylorSeries(Coef,var,cen) -> %
--R coerce : UnivariateLaurentSeries(Coef,var,cen) -> %
--R coerce : Coef -> % if Coef has COMRING
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(var)) -> %
--R differentiate : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Co
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Inte
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,%) -> % if Fraction(Integer) has SGROUP
--R ?.? : (%,Fraction(Integer)) -> Coef
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,Fraction(Integer)) -> %
```

```
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef ->
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R laurent : % -> UnivariateLaurentSeries(Coef,var,cen)
--R laurentIfCan : % -> Union(UnivariateLaurentSeries(Coef,var,cen),"failed")
--R laurentRep : % -> UnivariateLaurentSeries(Coef,var,cen)
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(Fraction(Integer))) -> %
--R monomial : (%,SingletonAsOrderedSet,Fraction(Integer)) -> %
--R monomial : (Coef,Fraction(Integer)) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyExponents : (%,Fraction(Integer)) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,Fraction(Integer)) -> Fraction(Integer)
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R puiseux : (Fraction(Integer),UnivariateLaurentSeries(Coef,var,cen)) -> %
--R ?quo? : (%,%) -> % if Coef has FIELD
--R rationalPower : % -> Fraction(Integer)
--R ?rem? : (%,%) -> % if Coef has FIELD
--R retract : % -> UnivariateTaylorSeries(Coef,var,cen)
--R retract : % -> UnivariateLaurentSeries(Coef,var,cen)
--R retractIfCan : % -> Union(UnivariateTaylorSeries(Coef,var,cen),"failed")
--R retractIfCan : % -> Union(UnivariateLaurentSeries(Coef,var,cen),"failed")
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : (NonNegativeInteger,Stream(Record(k: Fraction(Integer),c: Coef))) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if Coef has FIELD
--R squareFreePart : % -> % if Coef has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: Fraction(Integer),c: Coef))
--R truncate : (%,Fraction(Integer),Fraction(Integer)) -> %
--R truncate : (%,Fraction(Integer)) -> %
```

```
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **UnivariatePuiseuxSeries.help** —

```
=====================================================================
UnivariatePuiseuxSeries examples
=====================================================================

See Also:
o )show UnivariatePuiseuxSeries
```

———-

22.5.1 UnivariatePuiseuxSeries (UPXS)



See

⇒ “UnivariatePuiseuxSeriesConstructor” (UPXSCONS) 22.6.1 on page 2808

Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coerce	complete	cos	cosh
cot	coth	csc	csch
D	degree	differentiate	divide
euclideanSize	eval	exp	expressIdealMember
exquo	extend	extendedEuclidean	factor
gcd	gcdPolynomial	hash	integrate
inv	latex	laurent	laurentIfCan
laurentRep	lcm	leadingCoefficient	leadingMonomial
log	map	monomial	monomial?
multiEuclidean	multiplyExponents	nthRoot	one?
order	pi	pole?	prime?
principalIdeal	puiseux	rationalPower	recip
reductum	retract	retractIfCan	sample
sec	sech	series	sin
sinh	sizeLess?	sqrt	squareFree
squareFreePart	subtractIfCan	tan	tanh
terms	truncate	unit?	unitCanonical
unitNormal	variable	variables	zero?
?*?	?**?	?+?	?-?
-?	?=?	?^?	?~=?
?/?	?.?	?quo?	?rem?

— domain UPXS UnivariatePuiseuxSeries —

```
)abbrev domain UPXS UnivariatePuiseuxSeries
++ Author: Clifton J. Williamson
++ Date Created: 28 January 1990
++ Date Last Updated: 21 September 1993
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: series, Puiseux
++ Examples:
++ References:
++ Description:
++ Dense Puiseux series in one variable
++ \spadtype{UnivariatePuiseuxSeries} is a domain representing Puiseux
++ series in one variable with coefficients in an arbitrary ring.  The
++ parameters of the type specify the coefficient ring, the power series
++ variable, and the center of the power series expansion.  For example,
++ \spad{UnivariatePuiseuxSeries(Integer,x,3)} represents Puiseux series in
```

```
++ \spad{(x - 3)} with \spadtype{Integer} coefficients.

UnivariatePuiseuxSeries(Coef,var,cen): Exports == Implementation where
  Coef : Ring
  var  : Symbol
  cen  : Coef
  I   ==> Integer
  L   ==> List
  NNI ==> NonNegativeInteger
  OUT ==> OutputForm
  RN  ==> Fraction Integer
  ST  ==> Stream Coef
  UTS ==> UnivariateTaylorSeries(Coef,var,cen)
  ULS ==> UnivariateLaurentSeries(Coef,var,cen)

  Exports ==> Join(UnivariatePuiseuxSeriesConstructorCategory(Coef,ULS),_
                   RetractableTo UTS) with
    coerce: Variable(var) -> %
      ++ coerce(var) converts the series variable \spad{var} into a
      ++ Puiseux series.
    differentiate: (%,Variable(var)) -> %
      ++ \spad{differentiate(f(x),x)} returns the derivative of
      ++ \spad{f(x)} with respect to \spad{x}.
    if Coef has Algebra Fraction Integer then
      integrate: (%,Variable(var)) -> %
        ++ \spad{integrate(f(x))} returns an anti-derivative of the power
        ++ series \spad{f(x)} with constant coefficient 0.
        ++ We may integrate a series when we can divide coefficients
        ++ by integers.

  Implementation ==> UnivariatePuiseuxSeriesConstructor(Coef,ULS) add

    Rep := Record(expon:RN,lSeries:ULS)

    getExpon: % -> RN
    getExpon pxs == pxs.expon

    variable upxs == var
    center   upxs == cen

    coerce(uts:UTS) == uts :: ULS :: %

    retractIfCan(upxs:%):Union(UTS,"failed") ==
      (ulsIfCan := retractIfCan(upxs)@Union(ULS,"failed")) case "failed" =>
        "failed"
      retractIfCan(ulsIfCan :: ULS)

    --retract(upxs:%):UTS ==
      --(ulsIfCan := retractIfCan(upxs)@Union(ULS,"failed")) case "failed" =>
        --error "retractIfCan: series has fractional exponents"
```

```
    --utsIfCan := retractIfCan(ulsIfCan :: ULS)@Union(UTS,"failed")
    --utsIfCan case "failed" =>
      --error "retractIfCan: series has negative exponents"
    --utsIfCan :: UTS

  coerce(v:Variable(var)) ==
    zero? cen => monomial(1,1)
    monomial(1,1) + monomial(cen,0)

  if Coef has "*": (Fraction Integer, Coef) -> Coef then
    differentiate(upxs:%,v:Variable(var)) == differentiate upxs

  if Coef has Algebra Fraction Integer then
    integrate(upxs:%,v:Variable(var)) == integrate upxs

  if Coef has coerce: Symbol -> Coef then
    if Coef has "**": (Coef,RN) -> Coef then

      roundDown: RN -> I
      roundDown rn ==
        -- returns the largest integer <= rn
        (den := denom rn) = 1 => numer rn
        n := (num := numer rn) quo den
        positive?(num) => n
        n - 1

      stToCoef: (ST,Coef,NNI,NNI) -> Coef
      stToCoef(st,term,n,n0) ==
        (n > n0) or (empty? st) => 0
        frst(st) * term ** n + stToCoef(rst st,term,n + 1,n0)

      approximateLaurent: (ULS,Coef,I) -> Coef
      approximateLaurent(x,term,n) ==
        (m := n - (e := degree x)) < 0 => 0
        app := stToCoef(coefficients taylorRep x,term,0,m :: NNI)
        zero? e => app
        app * term ** (e :: RN)

      approximate(x,r) ==
        e := rationalPower(x)
        term := ((variable(x) :: Coef) - center(x)) ** e
        approximateLaurent(laurentRep x,term,roundDown(r / e))

  termOutput:(RN,Coef,OUT) -> OUT
  termOutput(k,c,vv) ==
  -- creates a term c * vv ** k
    k = 0 => c :: OUT
    mon :=
      k = 1 => vv
      vv ** (k :: OUT)
```

```
      c = 1 => mon
      c = -1 => -mon
      (c :: OUT) * mon

    showAll?:() -> Boolean
    -- check a global Lisp variable
    showAll?() == true

    termsToOutputForm:(RN,RN,ST,OUT) -> OUT
    termsToOutputForm(m,rat,uu,xxx) ==
      l : L OUT := empty()
      empty? uu => 0 :: OUT
      n : NNI; count : NNI := _$streamCount$Lisp
      for n in 0..count while not empty? uu repeat
        if frst(uu) ^= 0 then
          l := concat(termOutput((n :: I) * rat + m,frst uu,xxx),l)
        uu := rst uu
      if showAll?() then
        for n in (count + 1).. while explicitEntries? uu and _
               not eq?(uu,rst uu) repeat
          if frst(uu) ^= 0 then
            l := concat(termOutput((n :: I) * rat + m,frst uu,xxx),l)
          uu := rst uu
      l :=
        explicitlyEmpty? uu => l
        eq?(uu,rst uu) and frst uu = 0 => l
        concat(prefix("O" :: OUT,[xxx ** (((n::I) * rat + m) :: OUT)]),l)
      empty? l => 0 :: OUT
      reduce("+",reverse_! l)

    coerce(upxs:%):OUT ==
      rat := getExpon upxs; uls := laurentRep upxs
      count : I := _$streamCount$Lisp
      uls := removeZeroes(_$streamCount$Lisp,uls)
      m : RN := (degree uls) * rat
      p := coefficients taylorRep uls
      xxx :=
        zero? cen => var :: OUT
        paren(var :: OUT - cen :: OUT)
      termsToOutputForm(m,rat,p,xxx)
```

———-

— UPXS.dotabb —

```
"UPXS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UPXS"]
"ULSCCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ULSCCAT"]
"UPXS" -> "ULSCCAT"
```

———-

22.6 domain UPXSCONS UnivariatePuiseuxSeriesConstructor

— UnivariatePuiseuxSeriesConstructor.input —

```
)set break resume
)sys rm -f UnivariatePuiseuxSeriesConstructor.output
)spool UnivariatePuiseuxSeriesConstructor.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariatePuiseuxSeriesConstructor
--R
--R UnivariatePuiseuxSeriesConstructor(Coef: Ring,ULS: UnivariateLaurentSeriesCategory(Coef))  is a domain c
--R Abbreviation for UnivariatePuiseuxSeriesConstructor is UPXSCONS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for UPXSCONS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                   ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        center : % -> Coef
--R coerce : ULS -> %                     coerce : Integer -> %
--R coerce : % -> OutputForm              complete : % -> %
--R degree : % -> Fraction(Integer)       hash : % -> SingleInteger
--R latex : % -> String                   laurent : % -> ULS
--R laurentRep : % -> ULS                 leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %              map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean              one? : % -> Boolean
--R order : % -> Fraction(Integer)        pole? : % -> Boolean
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R retract : % -> ULS                    sample : () -> %
--R variable : % -> Symbol                zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Integer) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> % if Coef has FIELD
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRING(SYMB
--R D : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has PDRIN
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and C
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Integer),Coef) -
--R ?^? : (%,Integer) -> % if Coef has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,Fraction(Integer)) -> Coef if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,Fraction(Integer)) -> Coef
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R coerce : Coef -> % if Coef has COMRING
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : % -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Coef has
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (Fraction(Integer),Coef) -> Coef and Co
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (Fraction(Integer),Coef) -
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (Fraction(Inte
--R divide : (%,%) -> Record(quotient: %,remainder: %) if Coef has FIELD
--R ?.? : (%,%) -> % if Fraction(Integer) has SGROUP
--R ?.? : (%,Fraction(Integer)) -> Coef
```

```
--R euclideanSize : % -> NonNegativeInteger if Coef has FIELD
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,Fraction(Integer)) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R expressIdealMember : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,Fraction(Integer)) -> %
--R extendedEuclidean : (%,%) -> Record(coef1: %,coef2: %,generator: %) if Coef has FIELD
--R extendedEuclidean : (%,%,%) -> Union(Record(coef1: %,coef2: %),"failed") if Coef has FIELD
--R factor : % -> Factored(%) if Coef has FIELD
--R gcd : (%,%) -> % if Coef has FIELD
--R gcd : List(%) -> % if Coef has FIELD
--R gcdPolynomial : (SparseUnivariatePolynomial(%),SparseUnivariatePolynomial(%)) -> SparseUnivariatePolynor
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef ->
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R inv : % -> % if Coef has FIELD
--R laurentIfCan : % -> Union(ULS,"failed")
--R lcm : (%,%) -> % if Coef has FIELD
--R lcm : List(%) -> % if Coef has FIELD
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(Fraction(Integer))) -> %
--R monomial : (%,SingletonAsOrderedSet,Fraction(Integer)) -> %
--R monomial : (Coef,Fraction(Integer)) -> %
--R multiEuclidean : (List(%),%) -> Union(List(%),"failed") if Coef has FIELD
--R multiplyExponents : (%,Fraction(Integer)) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,Fraction(Integer)) -> Fraction(Integer)
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R prime? : % -> Boolean if Coef has FIELD
--R principalIdeal : List(%) -> Record(coef: List(%),generator: %) if Coef has FIELD
--R puiseux : (Fraction(Integer),ULS) -> %
--R ?quo? : (%,%) -> % if Coef has FIELD
--R rationalPower : % -> Fraction(Integer)
--R ?rem? : (%,%) -> % if Coef has FIELD
--R retractIfCan : % -> Union(ULS,"failed")
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : (NonNegativeInteger,Stream(Record(k: Fraction(Integer),c: Coef))) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sizeLess? : (%,%) -> Boolean if Coef has FIELD
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R squareFree : % -> Factored(%) if Coef has FIELD
--R squareFreePart : % -> % if Coef has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: Fraction(Integer),c: Coef))
--R truncate : (%,Fraction(Integer),Fraction(Integer)) -> %
--R truncate : (%,Fraction(Integer)) -> %
```

```
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **UnivariatePuiseuxSeriesConstructor.help** —

```
=====================================================================
UnivariatePuiseuxSeriesConstructor examples
=====================================================================

See Also:
o )show UnivariatePuiseuxSeriesConstructor
```

———-

22.6.1 UnivariatePuiseuxSeriesConstructor (UPXSCONS)



See

⇒ “UnivariatePuiseuxSeries” (UPXS) 22.5.1 on page 2800

Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coerce	complete	cos	cosh
cot	coth	csc	csch
D	degree	differentiate	divide
euclideanSize	eval	exp	expressIdealMember
exquo	extend	extendedEuclidean	factor
gcd	gcdPolynomial	hash	integrate
inv	latex	laurent	laurentIfCan
laurentRep	lcm	leadingCoefficient	leadingMonomial
log	map	monomial	monomial?
multiEuclidean	multiplyExponents	nthRoot	one?
order	pi	pole?	prime?
principalIdeal	puiseux	rationalPower	recip
reductum	retract	retractIfCan	sample
sec	sech	series	sin
sinh	sizeLess?	sqrt	squareFree
squareFreePart	subtractIfCan	tan	tanh
terms	truncate	unit?	unitCanonical
unitNormal	variable	variables	zero?
?*?	?**?	?+?	?-?
-?	?=?	?^?	?~=?
?/?	?.?	?quo?	?rem?

— domain UPXSCONS UnivariatePuiseuxSeriesConstructor —

```
)abbrev domain UPXSCONS UnivariatePuiseuxSeriesConstructor
++ Author: Clifton J. Williamson
++ Date Created: 9 May 1989
++ Date Last Updated: 30 November 1994
++ Basic Operations:
++ Related Domains:
++ Also See:
++ AMS Classifications:
++ Keywords: series, Puiseux, Laurent
++ Examples:
++ References:
++ Description:
++ This package enables one to construct a univariate Puiseux series
++ domain from a univariate Laurent series domain. Univariate
++ Puiseux series are represented by a pair \spad{[r,f(x)]}, where r is
++ a positive rational number and \spad{f(x)} is a Laurent series.
++ This pair represents the Puiseux series \spad{f(x^r)}.
```

```
UnivariatePuiseuxSeriesConstructor(Coef,ULS):_
 Exports == Implementation where
  Coef  : Ring
  ULS   : UnivariateLaurentSeriesCategory Coef
  I     ==> Integer
  L     ==> List
  NNI   ==> NonNegativeInteger
  OUT   ==> OutputForm
  PI    ==> PositiveInteger
  RN    ==> Fraction Integer
  ST    ==> Stream Coef
  LTerm ==> Record(k:I,c:Coef)
  PTerm ==> Record(k:RN,c:Coef)
  ST2LP ==> StreamFunctions2(LTerm,PTerm)
  ST2PL ==> StreamFunctions2(PTerm,LTerm)

  Exports ==> UnivariatePuiseuxSeriesConstructorCategory(Coef,ULS)

  Implementation ==> add

--% representation

    Rep := Record(expon:RN,lSeries:ULS)

    getExpon: % -> RN
    getULS  : % -> ULS

    getExpon pxs == pxs.expon
    getULS   pxs == pxs.lSeries

--% creation and destruction

    puiseux(n,ls)   == [n,ls]
    laurentRep x    == getULS x
    rationalPower x == getExpon x
    degree x        == getExpon(x) * degree(getULS(x))

    0 == puiseux(1,0)
    1 == puiseux(1,1)

    monomial(c,k) ==
      k = 0 => c :: %
      k < 0 => puiseux(-k,monomial(c,-1))
      puiseux(k,monomial(c,1))

    coerce(ls:ULS) == puiseux(1,ls)
    coerce(r:Coef) == r :: ULS  :: %
    coerce(i:I)    == i :: Coef :: %

    laurentIfCan upxs ==
```

```
      r := getExpon upxs
--      one? denom r =>
      (denom r) = 1 =>
        multiplyExponents(getULS upxs,numer(r) :: PI)
      "failed"

    laurent upxs ==
      (uls := laurentIfCan upxs) case "failed" =>
        error "laurent: Puiseux series has fractional powers"
      uls :: ULS

    multExp: (RN,LTerm) -> PTerm
    multExp(r,lTerm) == [r * lTerm.k,lTerm.c]

    terms upxs ==
      map((t1:LTerm):PTerm+->multExp(getExpon upxs,t1),terms getULS upxs)$ST2LP

    clearDen: (I,PTerm) -> LTerm
    clearDen(n,lTerm) ==
      (int := retractIfCan(n * lTerm.k)@Union(I,"failed")) case "failed" =>
        error "series: inappropriate denominator"
      [int :: I,lTerm.c]

    series(n,stream) ==
      str := map((t1:PTerm):LTerm +-> clearDen(n,t1),stream)$ST2PL
      puiseux(1/n,series str)

--% normalizations

    rewrite:(%,PI) -> %
    rewrite(upxs,m) ==
      -- rewrites a series in x**r as a series in x**(r/m)
      puiseux((getExpon upxs)*(1/m),multiplyExponents(getULS upxs,m))

    ratGcd: (RN,RN) -> RN
    ratGcd(r1,r2) ==
      -- if r1 = prod(p prime,p ** ep(r1)) and
      -- if r2 = prod(p prime,p ** ep(r2)), then
      -- ratGcd(r1,r2) = prod(p prime,p ** min(ep(r1),ep(r2)))
      gcd(numer r1,numer r2) / lcm(denom r1,denom r2)

    withNewExpon:(%,RN) -> %
    withNewExpon(upxs,r) ==
      rewrite(upxs,numer(getExpon(upxs)/r) pretend PI)

--% predicates

    upxs1 = upxs2 ==
      r1 := getExpon upxs1; r2 := getExpon upxs2
      ls1 := getULS upxs1; ls2 := getULS upxs2
```

```
      (r1 = r2) => (ls1 = ls2)
      r := ratGcd(r1,r2)
      m1 := numer(getExpon(upxs1)/r) pretend PI
      m2 := numer(getExpon(upxs2)/r) pretend PI
      multiplyExponents(ls1,m1) = multiplyExponents(ls2,m2)

    pole? upxs == pole? getULS upxs

--% arithmetic

    applyFcn:((ULS,ULS) -> ULS,%,%) -> %
    applyFcn(op,pxs1,pxs2) ==
      r1 := getExpon pxs1; r2 := getExpon pxs2
      ls1 := getULS pxs1; ls2 := getULS pxs2
      (r1 = r2) => puiseux(r1,op(ls1,ls2))
      r := ratGcd(r1,r2)
      m1 := numer(getExpon(pxs1)/r) pretend PI
      m2 := numer(getExpon(pxs2)/r) pretend PI
      puiseux(r,op(multiplyExponents(ls1,m1),multiplyExponents(ls2,m2)))

    pxs1 + pxs2     == applyFcn((z1:ULS,z2:ULS):ULS+->z1 +$ULS z2,pxs1,pxs2)
    pxs1 - pxs2     == applyFcn((z1:ULS,z2:ULS):ULS+->z1 -$ULS z2,pxs1,pxs2)
    pxs1:% * pxs2:% == applyFcn((z1:ULS,z2:ULS):ULS+->z1 *$ULS z2,pxs1,pxs2)

    pxs:% ** n:NNI == puiseux(getExpon pxs,getULS(pxs)**n)

    recip pxs ==
      rec := recip getULS pxs
      rec case "failed" => "failed"
      puiseux(getExpon pxs,rec :: ULS)

    RATALG : Boolean := Coef has Algebra(Fraction Integer)

    elt(upxs1:%,upxs2:%) ==
      uls1 := laurentRep upxs1; uls2 := laurentRep upxs2
      r1 := rationalPower upxs1; r2 := rationalPower upxs2
      (n := retractIfCan(r1)@Union(Integer,"failed")) case Integer =>
        puiseux(r2,uls1(uls2 ** r1))
      RATALG =>
        if zero? (coef := coefficient(uls2,deg := degree uls2)) then
          deg := order(uls2,deg + 1000)
          zero? (coef := coefficient(uls2,deg)) =>
            error "elt: series with many leading zero coefficients"
        -- a fractional power of a Laurent series may not be defined:
        -- if f(x) = c * x**n + ..., then f(x) ** (p/q) will be defined
        -- only if q divides n
        b := lcm(denom r1,deg); c := b quo deg
        mon : ULS := monomial(1,c)
        uls2 := elt(uls2,mon) ** r1
        puiseux(r2*(1/c),elt(uls1,uls2))
```

```
      error "elt: rational powers not available for this coefficient domain"

    if Coef has "**": (Coef,Integer) -> Coef and
       Coef has "**": (Coef, RN) -> Coef then
         eval(upxs:%,a:Coef) == eval(getULS upxs,a ** getExpon(upxs))

    if Coef has Field then

      pxs1:% / pxs2:% == applyFcn((z1:ULS,z2:ULS):ULS+->z1 /$ULS z2,pxs1,pxs2)

      inv upxs ==
        (invUpxs := recip upxs) case "failed" =>
          error "inv: multiplicative inverse does not exist"
        invUpxs :: %

--% values

    variable upxs == variable getULS upxs
    center   upxs == center   getULS upxs

    coefficient(upxs,rn) ==
--      one? denom(n := rn / getExpon upxs) =>
      (denom(n := rn / getExpon upxs)) = 1 =>
        coefficient(getULS upxs,numer n)
      0

    elt(upxs:%,rn:RN) == coefficient(upxs,rn)

--% other functions

    roundDown: RN -> I
    roundDown rn ==
      -- returns the largest integer <= rn
      (den := denom rn) = 1 => numer rn
      n := (num := numer rn) quo den
      positive?(num) => n
      n - 1

    roundUp: RN -> I
    roundUp rn ==
      -- returns the smallest integer >= rn
      (den := denom rn) = 1 => numer rn
      n := (num := numer rn) quo den
      positive?(num) => n + 1
      n

    order upxs == getExpon upxs * order getULS upxs
    order(upxs,r) ==
      e := getExpon upxs
      ord := order(getULS upxs, n := roundDown(r / e))
```

```
    ord = n => r
    ord * e

  truncate(upxs,r) ==
    e := getExpon upxs
    puiseux(e,truncate(getULS upxs,roundDown(r / e)))

  truncate(upxs,r1,r2) ==
    e := getExpon upxs
    puiseux(e,truncate(getULS upxs,roundUp(r1 / e),roundDown(r2 / e)))

  complete upxs == puiseux(getExpon upxs,complete getULS upxs)
  extend(upxs,r) ==
    e := getExpon upxs
    puiseux(e,extend(getULS upxs,roundDown(r / e)))

  map(fcn,upxs) == puiseux(getExpon upxs,map(fcn,getULS upxs))

  characteristic() == characteristic()$Coef

  -- multiplyCoefficients(f,upxs) ==
    -- r := getExpon upxs
    -- puiseux(r,multiplyCoefficients(f(#1 * r),getULS upxs))

  multiplyExponents(upxs:%,n:RN) ==
    puiseux(n * getExpon(upxs),getULS upxs)
  multiplyExponents(upxs:%,n:PI) ==
    puiseux(n * getExpon(upxs),getULS upxs)

  if Coef has "*": (Fraction Integer, Coef) -> Coef then

    differentiate upxs ==
      r := getExpon upxs
      puiseux(r,differentiate getULS upxs) * monomial(r :: Coef,r-1)

    if Coef has PartialDifferentialRing(Symbol) then

      differentiate(upxs:%,s:Symbol) ==
        (s = variable(upxs)) => differentiate upxs
        dcds := differentiate(center upxs,s)
        map((z1:Coef):Coef+->differentiate(z1,s),upxs)
                                              - dcds*differentiate(upxs)

  if Coef has Algebra Fraction Integer then

    coerce(r:RN) == r :: Coef :: %

    ratInv: RN -> Coef
    ratInv r ==
      zero? r => 1
```

```
        inv(r) :: Coef

      integrate upxs ==
        not zero? coefficient(upxs,-1) =>
          error "integrate: series has term of order -1"
        r := getExpon upxs
        uls := getULS upxs
        uls := multiplyCoefficients((z1:Integer):Coef+->ratInv(z1*r+1),uls)
        monomial(1,1) * puiseux(r,uls)

      if Coef has integrate: (Coef,Symbol) -> Coef and _
         Coef has variables: Coef -> List Symbol then

        integrate(upxs:%,s:Symbol) ==
          (s = variable(upxs)) => integrate upxs
          not entry?(s,variables center upxs)
            => map((z1:Coef):Coef +-> integrate(z1,s),upxs)
          error "integrate: center is a function of variable of integration"

      if Coef has TranscendentalFunctionCategory and _
         Coef has PrimitiveFunctionCategory and _
         Coef has AlgebraicallyClosedFunctionSpace Integer then

        integrateWithOneAnswer: (Coef,Symbol) -> Coef
        integrateWithOneAnswer(f,s) ==
          res := integrate(f,s)$FunctionSpaceIntegration(I,Coef)
          res case Coef => res :: Coef
          first(res :: List Coef)

        integrate(upxs:%,s:Symbol) ==
          (s = variable(upxs)) => integrate upxs
          not entry?(s,variables center upxs) =>
            map((z1:Coef):Coef +-> integrateWithOneAnswer(z1,s),upxs)
          error "integrate: center is a function of variable of integration"

      if Coef has Field then
         (upxs:%) ** (q:RN) ==
           num := numer q; den := denom q
--           one? den => upxs ** num
           den = 1 => upxs ** num
           r := rationalPower upxs; uls := laurentRep upxs
           deg := degree uls
           if zero?(coef := coefficient(uls,deg)) then
             deg := order(uls,deg + 1000)
             zero?(coef := coefficient(uls,deg)) =>
               error "power of series with many leading zero coefficients"
           ulsPow := (uls * monomial(1,-deg)$ULS) ** q
           puiseux(r,ulsPow) * monomial(1,deg*q*r)

      applyUnary: (ULS -> ULS,%) -> %
```

```
applyUnary(fcn,upxs) ==
  puiseux(rationalPower upxs,fcn laurentRep upxs)

exp upxs   == applyUnary(exp,upxs)
log upxs   == applyUnary(log,upxs)
sin upxs   == applyUnary(sin,upxs)
cos upxs   == applyUnary(cos,upxs)
tan upxs   == applyUnary(tan,upxs)
cot upxs   == applyUnary(cot,upxs)
sec upxs   == applyUnary(sec,upxs)
csc upxs   == applyUnary(csc,upxs)
asin upxs  == applyUnary(asin,upxs)
acos upxs  == applyUnary(acos,upxs)
atan upxs  == applyUnary(atan,upxs)
acot upxs  == applyUnary(acot,upxs)
asec upxs  == applyUnary(asec,upxs)
acsc upxs  == applyUnary(acsc,upxs)
sinh upxs  == applyUnary(sinh,upxs)
cosh upxs  == applyUnary(cosh,upxs)
tanh upxs  == applyUnary(tanh,upxs)
coth upxs  == applyUnary(coth,upxs)
sech upxs  == applyUnary(sech,upxs)
csch upxs  == applyUnary(csch,upxs)
asinh upxs == applyUnary(asinh,upxs)
acosh upxs == applyUnary(acosh,upxs)
atanh upxs == applyUnary(atanh,upxs)
acoth upxs == applyUnary(acoth,upxs)
asech upxs == applyUnary(asech,upxs)
acsch upxs == applyUnary(acsch,upxs)
```

———-

— UPXSCONS.dotabb —

```
"UPXSCONS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UPXSCONS"]
"ACFS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACFS"]
"UPXSCONS" -> "ACFS"
```

———-

22.7 domain UPXSSING UnivariatePuiseuxSeriesWithExponentialSingularity

— UnivariatePuiseuxSeriesWithExponentialSingularity.input —

```
)set break resume
)sys rm -f UnivariatePuiseuxSeriesWithExponentialSingularity.output
)spool UnivariatePuiseuxSeriesWithExponentialSingularity.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariatePuiseuxSeriesWithExponentialSingularity
--R
--R UnivariatePuiseuxSeriesWithExponentialSingularity(R: Join(OrderedSet,RetractableTo(Integer),LinearlyExpl
--R Abbreviation for UnivariatePuiseuxSeriesWithExponentialSingularity is UPXSSING
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for UPXSSING
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        associates? : (%,%) -> Boolean
--R coerce : % -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              ground? : % -> Boolean
--R hash : % -> SingleInteger             latex : % -> String
--R leadingMonomial : % -> %              monomial? : % -> Boolean
--R one? : % -> Boolean                   recip : % -> Union(%,"failed")
--R reductum : % -> %                     sample : () -> %
--R unit? : % -> Boolean                  unitCanonical : % -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if UnivariatePuiseuxSeries(FE,var,cen) has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if UnivariatePuiseuxSeries(FE,var,cen) has ALGEBRA(FRAC(INT))
--R ?*? : (UnivariatePuiseuxSeries(FE,var,cen),%) -> %
--R ?*? : (%,UnivariatePuiseuxSeries(FE,var,cen)) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,UnivariatePuiseuxSeries(FE,var,cen)) -> % if UnivariatePuiseuxSeries(FE,var,cen) has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R binomThmExpt : (%,%,NonNegativeInteger) -> % if UnivariatePuiseuxSeries(FE,var,cen) has COMRING
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if UnivariatePuiseuxSeries(FE,var,cen) has CHARNZ
--R coefficient : (%,ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)) -> UnivariatePuiseuxSeries(FE,var,cen
--R coefficients : % -> List(UnivariatePuiseuxSeries(FE,var,cen))
--R coerce : Fraction(Integer) -> % if UnivariatePuiseuxSeries(FE,var,cen) has ALGEBRA(FRAC(INT)) or Univari
--R coerce : UnivariatePuiseuxSeries(FE,var,cen) -> %
--R content : % -> UnivariatePuiseuxSeries(FE,var,cen) if UnivariatePuiseuxSeries(FE,var,cen) has GCDDOM
--R degree : % -> ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)
--R dominantTerm : % -> Union(Record(%term: Record(%coef: UnivariatePuiseuxSeries(FE,var,cen),%expon: Expone
--R exquo : (%,%) -> Union(%,"failed")
--R exquo : (%,UnivariatePuiseuxSeries(FE,var,cen)) -> Union(%,"failed") if UnivariatePuiseuxSeries(FE,var,c
```

```
--R ground : % -> UnivariatePuiseuxSeries(FE,var,cen)
--R leadingCoefficient : % -> UnivariatePuiseuxSeries(FE,var,cen)
--R limitPlus : % -> Union(OrderedCompletion(FE),"failed")
--R map : ((UnivariatePuiseuxSeries(FE,var,cen) -> UnivariatePuiseuxSeries(FE,var,cen)),%) -> %
--R mapExponents : ((ExponentialOfUnivariatePuiseuxSeries(FE,var,cen) -> ExponentialOfUnivariate
--R minimumDegree : % -> ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)
--R monomial : (UnivariatePuiseuxSeries(FE,var,cen),ExponentialOfUnivariatePuiseuxSeries(FE,var,
--R numberOfMonomials : % -> NonNegativeInteger
--R pomopo! : (%,UnivariatePuiseuxSeries(FE,var,cen),ExponentialOfUnivariatePuiseuxSeries(FE,var
--R primitivePart : % -> % if UnivariatePuiseuxSeries(FE,var,cen) has GCDDOM
--R retract : % -> UnivariatePuiseuxSeries(FE,var,cen)
--R retract : % -> Fraction(Integer) if UnivariatePuiseuxSeries(FE,var,cen) has RETRACT(FRAC(INT
--R retract : % -> Integer if UnivariatePuiseuxSeries(FE,var,cen) has RETRACT(INT)
--R retractIfCan : % -> Union(UnivariatePuiseuxSeries(FE,var,cen),"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if UnivariatePuiseuxSeries(FE,var,cen)
--R retractIfCan : % -> Union(Integer,"failed") if UnivariatePuiseuxSeries(FE,var,cen) has RETRA
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %)
--R
--E 1

)spool
)lisp (bye)
```

———-


— UnivariatePuiseuxSeriesWithExponentialSingularity.help —

```
=====================================================================
UnivariatePuiseuxSeriesWithExponentialSingularity examples
=====================================================================

See Also:
o )show UnivariatePuiseuxSeriesWithExponentialSingularity
```

———-

22.7.1 UnivariatePuiseuxSeriesWithExponentialSingularity (UPXSSING)



See

⇒ "ExponentialOfUnivariatePuiseuxSeries" (EXPUPXS) 6.7.1 on page 709
⇒ "ExponentialExpansion" (EXPEXPAN) 6.5.1 on page 681

Exports:

0	1	associates?	binomThmExpt	characteristic
charthRoot	coefficient	coefficients	coerce	content
degree	dominantTerm	exquo	ground	ground?
hash	latex	leadingCoefficient	leadingMonomial	limitPlus
map	mapExponents	minimumDegree	monomial	monomial?
numberOfMonomials	one?	pomopo!	primitivePart	recip
reductum	retract	retractIfCan	sample	subtractIfCan
unit?	unitCanonical	unitNormal	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?	?/?		

— **domain UPXSSING UnivariatePuiseuxSeriesWithExponentialSingularity** —

```
)abbrev domain UPXSSING UnivariatePuiseuxSeriesWithExponentialSingularity
++ Author: Clifton J. Williamson
++ Date Created: 4 August 1992
++ Date Last Updated: 27 August 1992
++ Basic Operations:
++ Related Domains: UnivariatePuiseuxSeries(FE,var,cen),
++                  ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)
++                  ExponentialExpansion(R,FE,var,cen)
++ Also See:
++ AMS Classifications:
++ Keywords: limit, functional expression, power series
++ Examples:
++ References:
++ Description:
++ UnivariatePuiseuxSeriesWithExponentialSingularity is a domain used to
```

```
++ represent functions with essential singularities.  Objects in this
++ domain are sums, where each term in the sum is a univariate Puiseux
++ series times the exponential of a univariate Puiseux series.  Thus,
++ the elements of this domain are sums of expressions of the form
++ \spad{g(x) * exp(f(x))}, where g(x) is a univariate Puiseux series
++ and f(x) is a univariate Puiseux series with no terms of non-negative
++ degree.

UnivariatePuiseuxSeriesWithExponentialSingularity(R,FE,var,cen):_
  Exports == Implementation where
  R   : Join(OrderedSet,RetractableTo Integer,_
             LinearlyExplicitRingOver Integer,GcdDomain)
  FE  : Join(AlgebraicallyClosedField,TranscendentalFunctionCategory,_
             FunctionSpace R)
  var : Symbol
  cen : FE
  B       ==> Boolean
  I       ==> Integer
  L       ==> List
  RN      ==> Fraction Integer
  UPXS    ==> UnivariatePuiseuxSeries(FE,var,cen)
  EXPUPXS ==> ExponentialOfUnivariatePuiseuxSeries(FE,var,cen)
  OFE     ==> OrderedCompletion FE
  Result  ==> Union(OFE,"failed")
  PxRec   ==> Record(k: Fraction Integer,c:FE)
  Term    ==> Record(%coef:UPXS,%expon:EXPUPXS,%expTerms:List PxRec)
    -- the %expTerms field is used to record the list of the terms (a 'term'
    -- records an exponent and a coefficient) in the exponent %expon
  TypedTerm ==> Record(%term:Term,%type:String)
    -- a term together with a String which tells whether it has an infinite,
    -- zero, or unknown limit as var -> cen+
  TRec    ==> Record(%zeroTerms: List Term,_
                     %infiniteTerms: List Term,_
                     %failedTerms: List Term,_
                     %puiseuxSeries: UPXS)
  SIGNEF  ==> ElementaryFunctionSign(R,FE)

  Exports ==> Join(FiniteAbelianMonoidRing(UPXS,EXPUPXS),IntegralDomain) with
    limitPlus : % -> Union(OFE,"failed")
      ++ limitPlus(f(var)) returns \spad{limit(var -> cen+,f(var))}.
    dominantTerm : % -> Union(TypedTerm,"failed")
      ++ dominantTerm(f(var)) returns the term that dominates the limiting
      ++ behavior of \spad{f(var)} as \spad{var -> cen+} together with a
      ++ \spadtype{String} which briefly describes that behavior.  The
      ++ value of the \spadtype{String} will be \spad{"zero"} (resp.
      ++ \spad{"infinity"}) if the term tends to zero (resp. infinity)
      ++ exponentially and will \spad{"series"} if the term is a
      ++ Puiseux series.

  Implementation ==> PolynomialRing(UPXS,EXPUPXS) add
```

```
makeTerm : (UPXS,EXPUPXS) -> Term
coeff : Term -> UPXS
exponent : Term -> EXPUPXS
exponentTerms : Term -> List PxRec
setExponentTerms_! : (Term,List PxRec) -> List PxRec
computeExponentTerms_! : Term -> List PxRec
terms : % -> List Term
sortAndDiscardTerms: List Term -> TRec
termsWithExtremeLeadingCoef : (L Term,RN,I) -> Union(L Term,"failed")
filterByOrder: (L Term,(RN,RN) -> B) -> Record(%list:L Term,%order:RN)
dominantTermOnList : (L Term,RN,I) -> Union(Term,"failed")
iDominantTerm : L Term -> Union(Record(%term:Term,%type:String),"failed")

retractIfCan f ==
  (numberOfMonomials f = 1) and (zero? degree f) => leadingCoefficient f
  "failed"

recip f ==
  numberOfMonomials f = 1 =>
    monomial(inv leadingCoefficient f,- degree f)
  "failed"

makeTerm(coef,expon) == [coef,expon,empty()]
coeff term == term.%coef
exponent term == term.%expon
exponentTerms term == term.%expTerms
setExponentTerms_!(term,list) == term.%expTerms := list
computeExponentTerms_! term ==
  setExponentTerms_!(term,entries complete terms exponent term)

terms f ==
  -- terms with a higher order singularity will appear closer to the
  -- beginning of the list because of the ordering in EXPPUPXS;
  -- no "expnonent terms" are computed by this function
  zero? f => empty()
  concat(makeTerm(leadingCoefficient f,degree f),terms reductum f)

sortAndDiscardTerms termList ==
  -- 'termList' is the list of terms of some function f(var), ordered
  -- so that terms with a higher order singularity occur at the
  -- beginning of the list.
  -- This function returns lists of candidates for the "dominant
  -- term" in 'termList', i.e. the term which describes the
  -- asymptotic behavior of f(var) as var -> cen+.
  -- 'zeroTerms' will contain terms which tend to zero exponentially
  -- and contains only those terms with the lowest order singularity.
  -- 'zeroTerms' will be non-empty only when there are no terms of
  -- infinite or series type.
  -- 'infiniteTerms' will contain terms which tend to infinity
  -- exponentially and contains only those terms with the highest
```

```
-- order singularity.
-- 'failedTerms' will contain terms which have an exponential
-- singularity, where we cannot say whether the limiting value
-- is zero or infinity. Only terms with a higher order sigularity
-- than the terms on 'infiniteList' are included.
-- 'pSeries' will be a Puiseux series representing a term without an
-- exponential singularity.  'pSeries' will be non-zero only when no
-- other terms are known to tend to infinity exponentially
zeroTerms : List Term := empty()
infiniteTerms : List Term := empty()
failedTerms : List Term := empty()
-- we keep track of whether or not we've found an infinite term
-- if so, 'infTermOrd' will be set to a negative value
infTermOrd : RN := 0
-- we keep track of whether or not we've found a zero term
-- if so, 'zeroTermOrd' will be set to a negative value
zeroTermOrd : RN := 0
ord : RN := 0; pSeries : UPXS := 0  -- dummy values
while not empty? termList repeat
  -- 'expon' is a Puiseux series
  expon := exponent(term := first termList)
  -- quit if there is an infinite term with a higher order singularity
  (ord := order(expon,0)) > infTermOrd => leave "infinite term dominates"
  -- if ord = 0, we've hit the end of the list
  (ord = 0) =>
    -- since we have a series term, don't bother with zero terms
    leave(pSeries := coeff(term); zeroTerms := empty())
  coef := coefficient(expon,ord)
  -- if we can't tell if the lowest order coefficient is positive or
  -- negative, we have a "failed term"
  (signum := sign(coef)$SIGNEF) case "failed" =>
    failedTerms := concat(term,failedTerms)
    termList := rest termList
  -- if the lowest order coefficient is positive, we have an
  -- "infinite term"
  (sig := signum :: Integer) = 1 =>
    infTermOrd := ord
    infiniteTerms := concat(term,infiniteTerms)
    -- since we have an infinite term, don't bother with zero terms
    zeroTerms := empty()
    termList := rest termList
  -- if the lowest order coefficient is negative, we have a
  -- "zero term" if there are no infinite terms and no failed
  -- terms, add the term to 'zeroTerms'
  if empty? infiniteTerms then
    zeroTerms :=
      ord = zeroTermOrd => concat(term,zeroTerms)
      zeroTermOrd := ord
      list term
  termList := rest termList
```

```
    -- reverse "failed terms" so that higher order singularities
    -- appear at the beginning of the list
    [zeroTerms,infiniteTerms,reverse_! failedTerms,pSeries]

  termsWithExtremeLeadingCoef(termList,ord,signum) ==
    -- 'termList' consists of terms of the form [g(x),exp(f(x)),...];
    -- when 'signum' is +1 (resp. -1), this function filters 'termList'
    -- leaving only those terms such that coefficient(f(x),ord) is
    -- maximal (resp. minimal)
    while (coefficient(exponent first termList,ord) = 0) repeat
      termList := rest termList
    empty? termList => error "UPXSSING: can't happen"
    coefExtreme := coefficient(exponent first termList,ord)
    outList := list first termList; termList := rest termList
    for term in termList repeat
      (coefDiff := coefficient(exponent term,ord) - coefExtreme) = 0 =>
        outList := concat(term,outList)
      (sig := sign(coefDiff)$SIGNEF) case "failed" => return "failed"
      (sig :: Integer) = signum => outList := list term
    outList

  filterByOrder(termList,predicate) ==
    -- 'termList' consists of terms of the form [g(x),exp(f(x)),expTerms],
    -- where 'expTerms' is a list containing some of the terms in the
    -- series f(x).
    -- The function filters 'termList' and, when 'predicate' is < (resp. >),
    -- leaves only those terms with the lowest (resp. highest) order term
    -- in 'expTerms'
    while empty? exponentTerms first termList repeat
      termList := rest termList
      empty? termList => error "UPXSING: can't happen"
    ordExtreme := (first exponentTerms first termList).k
    outList := list first termList
    for term in rest termList repeat
      not empty? exponentTerms term =>
        (ord := (first exponentTerms term).k) = ordExtreme =>
          outList := concat(term,outList)
        predicate(ord,ordExtreme) =>
          ordExtreme := ord
          outList := list term
    -- advance pointers on "exponent terms" on terms on 'outList'
    for term in outList repeat
      setExponentTerms_!(term,rest exponentTerms term)
    [outList,ordExtreme]

  dominantTermOnList(termList,ord0,signum) ==
    -- finds dominant term on 'termList'
    -- it is known that "exponent terms" of order < 'ord0' are
    -- the same for all terms on 'termList'
    newList := termsWithExtremeLeadingCoef(termList,ord0,signum)
```

```
    newList case "failed" => "failed"
    termList := newList :: List Term
    empty? rest termList => first termList
    filtered :=
      signum = 1 => filterByOrder(termList,(x,y) +-> x < y)
      filterByOrder(termList,(x,y) +-> x > y)
    termList := filtered.%list
    empty? rest termList => first termList
    dominantTermOnList(termList,filtered.%order,signum)

  iDominantTerm termList ==
    termRecord := sortAndDiscardTerms termList
    zeroTerms := termRecord.%zeroTerms
    infiniteTerms := termRecord.%infiniteTerms
    failedTerms := termRecord.%failedTerms
    pSeries := termRecord.%puiseuxSeries
    -- in future versions, we will deal with "failed terms"
    -- at present, if any occur, we cannot determine the limit
    not empty? failedTerms => "failed"
    not zero? pSeries => [makeTerm(pSeries,0),"series"]
    not empty? infiniteTerms =>
      empty? rest infiniteTerms => [first infiniteTerms,"infinity"]
      for term in infiniteTerms repeat computeExponentTerms_! term
      ord0 := order exponent first infiniteTerms
      (dTerm := dominantTermOnList(infiniteTerms,ord0,1)) case "failed" =>
        return "failed"
      [dTerm :: Term,"infinity"]
    empty? rest zeroTerms => [first zeroTerms,"zero"]
    for term in zeroTerms repeat computeExponentTerms_! term
    ord0 := order exponent first zeroTerms
    (dTerm := dominantTermOnList(zeroTerms,ord0,-1)) case "failed" =>
      return "failed"
    [dTerm :: Term,"zero"]

  dominantTerm f == iDominantTerm terms f

  limitPlus f ==
    -- list the terms occurring in 'f'; if there are none, then f = 0
    empty?(termList := terms f) => 0
    -- compute dominant term
    (tInfo := iDominantTerm termList) case "failed" => "failed"
    termInfo := tInfo :: Record(%term:Term,%type:String)
    domTerm := termInfo.%term
    (type := termInfo.%type) = "series" =>
      -- find limit of series term
      (ord := order(pSeries := coeff domTerm,1)) > 0 => 0
      coef := coefficient(pSeries,ord)
      member?(var,variables coef) => "failed"
      ord = 0 => coef :: OFE
      -- in the case of an infinite limit, we need to know the sign
```

```
        -- of the first non-zero coefficient
        (signum := sign(coef)$SIGNEF) case "failed" => "failed"
        (signum :: Integer) = 1 => plusInfinity()
        minusInfinity()
      type = "zero" => 0
      -- examine lowest order coefficient in series part of 'domTerm'
      ord := order(pSeries := coeff domTerm)
      coef := coefficient(pSeries,ord)
      member?(var,variables coef) => "failed"
      (signum := sign(coef)$SIGNEF) case "failed" => "failed"
      (signum :: Integer) = 1 => plusInfinity()
      minusInfinity()
```

———-

— UPXSSING.dotabb —

```
"UPXSSING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UPXSSING"]
"FS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FS"]
"ACF" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACF"]
"UPXSSING" -> "ACF"
"UPXSSING" -> "FS"
```

———-

22.8 domain OREUP UnivariateSkewPolynomial

— UnivariateSkewPolynomial.input —

```
)set break resume
)sys rm -f UnivariateSkewPolynomial.output
)spool UnivariateSkewPolynomial.output
)set message test on
)set message auto off
)set message type off
)clear all

--S 1 of 33
F:=EXPR(FRAC(INT))
--R
--R
--R   (1)  Expression(Fraction(Integer))
--E 1
```

```
--S 2 of 33
Dx:F->F:=f+->D(f,['x])
--R
--R
--R   (2)  theMap(Closure)
--E 2

--S 3 of 33
D0:=OREUP('d,F,1,Dx)
--R
--R
--R   (3)
--I  UnivariateSkewPolynomial(d,Expression(Fraction(Integer)),R -> R,theMap(LAMBDA
--I  -CLOSURE(NIL,NIL,NIL,G1393(envArg),SPADCALL(G1393,coerceOrCroak(CONS(QUOTE(Li
--I  st(Variable(x))),wrap(LIST(QUOTE(x)))),QUOTE(List(Symbol)),QUOTE(*1;anonymous
--I  Function;0;initial;internal)),ELT(*1;anonymousFunction;0;initial;internal;MV,
  0)))))
--E 3

--S 4 of 33
u:D0:=(operator 'u)(x)
--R
--R
--R   (4)  u(x)
--E 4

--S 5 of 33
d:D0:='d
--R
--R
--R   (5)  d
--E 5

--S 6 of 33
a:D0:=u^3*d^3+u^2*d^2+u*d+1
--R
--R
--R            3 3       2 2
--R   (6)  u(x) d  + u(x) d  + u(x)d + 1
--E 6

--S 7 of 33
b:D0:=(u+1)*d^2+2*d
--R
--R
--R                    2
--R   (7)  (u(x) + 1)d  + 2d
--E 7

--S 8 of 33
```

```
r:=rightDivide(a,b)
--R
--R
--R   (8)
--R                                  3 ,          3       2
--R                    3      - u(x) u (x) - u(x)  + u(x)
--R                 u(x)
--R   [quotient= -------- d + ----------------------------,
--R              u(x) + 1               2
--R                                   u(x)  + 2u(x) + 1
--R                    3 ,           3
--R                2u(x) u (x) + 3u(x)  + u(x)
--R
--R    remainder= -------------------------- d + 1]
--R                        2
--R                    u(x)  + 2u(x) + 1
--E 8

--S 9 of 33
r.quotient
--R
--R
--R                             3 ,          3       2
--R              3      - u(x) u (x) - u(x)  + u(x)
--R          u(x)
--R   (9)  -------- d + ----------------------------
--R        u(x) + 1               2
--R                              u(x)  + 2u(x) + 1
--E 9

--S 10 of 33
r.remainder
--R
--R
--R              3 ,           3
--R         2u(x) u (x) + 3u(x)  + u(x)
--R
--R   (10)  -------------------------- d + 1
--R                  2
--R              u(x)  + 2u(x) + 1
--E 10

)clear all

--S 11 of 33
R:=UP('t,INT)
--R
--R
--R   (1)  UnivariatePolynomial(t,Integer)
--E 11
```

```
--S 12 of 33
W:=OREUP('x,R,1,D)
--R
--R
--R   (2)
--R  UnivariateSkewPolynomial(x,UnivariatePolynomial(t,Integer),R -> R,theMap(DIFR
--I  ING-;D;2S;1,0))
--E 12

--S 13 of 33
t:W:='t
--R
--R
--R   (3)  t
--E 13

--S 14 of 33
x:W:='x
--R
--R
--R   (4)  x
--E 14

--S 15 of 33
a:W:=(t-1)*x^4+(t^3+3*t+1)*x^2+2*t*x+t^3
--R
--R
--R                4     3           2           3
--R   (5)  (t - 1)x  + (t  + 3t + 1)x  + 2t x + t
--E 15

--S 16 of 33
b:W:=(6*t^4+2*t^2)*x^3+3*t^2*x^2
--R
--R
--R           4     2  3     2 2
--R   (6)  (6t  + 2t )x  + 3t x
--E 16

--S 17 of 33
a*b
--R
--R
--R   (7)
--R        5     4     3     2  7       4      3      2        6
--R     (6t  - 6t  + 2t  - 2t )x  + (96t  - 93t  + 13t  - 16t)x
--R   +
--R        7      5     4       3       2       5
--R     (6t  + 20t  + 6t  + 438t  - 406t  - 24)x
```

```
--R   +
--R         6      5       4      3       2              4
--R     (48t  + 15t  + 152t  + 61t  + 603t  - 532t - 36)x
--R   +
--R        7      5      4       3       2              3
--R     (6t  + 74t  + 60t  + 226t  + 116t  + 168t - 140)x
--R   +
--R        5     3      2            2
--R     (3t  + 6t  + 12t  + 18t + 6)x
--E 17

--S 18 of 33
a^3
--R
--R
--R   (8)
--R       3     2           12      5     4      3      2           10
--R     (t  - 3t  + 3t - 1)x   + (3t  - 6t  + 12t  - 15t  + 3t + 3)x
--R   +
--R        3      2       9      7     6      5      4      3     2            8
--R     (6t  - 12t  + 6t)x  + (3t  - 3t  + 21t  - 18t  + 24t  - 9t  - 15t - 3)x
--R   +
--R         5      4      3      2        7
--R     (12t  - 12t  + 36t  - 24t  - 12t)x
--R   +
--R       9      7     6      5     4      3      2           6
--R     (t  + 15t  - 3t  + 45t  + 6t  + 36t  + 15t  + 9t + 1)x
--R   +
--R        7      5      3      2       5
--R     (6t  + 48t  + 54t  + 36t  + 6t)x
--R   +
--R        9      7     6      5      4      3      2  4
--R     (3t  + 21t  + 3t  + 39t  + 18t  + 39t  + 12t )x
--R   +
--R         7      5      4     3  3      9     7     6      5  2     7     9
--R     (12t  + 36t  + 12t  + 8t )x  + (3t  + 9t  + 3t  + 12t )x  + 6t x + t
--E 18

)clear all

--S 19 of 33
S:EXPR(INT)->EXPR(INT):=e+->eval(e,[n],[n+1])
--R
--R
--R   (1)  theMap(Closure)
--E 19

--S 20 of 33
DF:EXPR(INT)->EXPR(INT):=e+->eval(e,[n],[n+1])-e
--R
```

```
--R
--R   (2)  theMap(Closure)
--E 20

--S 21 of 33
D0:=OREUP('D,EXPR(INT),morphism S,DF)
--R
--R
--R   (3)
--I  UnivariateSkewPolynomial(D,Expression Integer,R -> R,theMap LAMBDA-CLOSURE(NI
--I  L,NIL,NIL,G9384 envArg,SPADCALL(SPADCALL(G9384,coerceOrCroak(CONS(QUOTE List
--I  Variable n,wrap LIST QUOTE n),QUOTE List Expression Integer,QUOTE *1;anonymou
--I  sFunction;9;frame0;internal),coerceOrCroak(CONS(QUOTE List Polynomial Integer
--I  ,wrap LIST SPADCALL(QUOTE 1(n,1 0),QUOTE 0,ELT(*1;anonymousFunction;9;frame0;
--I  internal;MV,0))),QUOTE List Expression Integer,QUOTE *1;anonymousFunction;9;f
--I  rame0;internal),ELT(*1;anonymousFunction;9;frame0;internal;MV,1)),G9384,ELT(*
--I  1;anonymousFunction;9;frame0;internal;MV,2))))
--E 21

--S 22 of 33
u:=(operator 'u)[n]
--R
--R
--R   (4)  u(n)
--E 22

--S 23 of 33
L:D0:='D+u
--R
--R
--R   (5)  D + u(n)
--E 23

--S 24 of 33
L^2
--R
--R
--R         2                2
--R   (6)  D  + 2u(n)D + u(n)
--E 24

)clear all

--S 25 of 33
)set expose add constructor SquareMatrix
--R
--I   SquareMatrix is now explicitly exposed in frame frame0
--E 25

--S 26 of 33
```

```
R:=SQMATRIX(2,INT)
--R
--R
--R   (1)  SquareMatrix(2,Integer)
--E 26

--S 27 of 33
y:R:=matrix [[1,1],[0,1]]
--R
--R
--R        +1  1+
--R   (2)  |    |
--R        +0  1+
--E 27

--S 28 of 33
delta:R->R:=r+->y*r-r*y
--R
--R
--R   (3)  theMap(Closure)
--E 28

--S 29 of 33
S:=OREUP('x,R,1,delta)
--R
--R
--R   (4)
--I  UnivariateSkewPolynomial(x,SquareMatrix(2,Integer),R -> R,theMap(LAMBDA-CLOSU
--I  RE(NIL,NIL,NIL,G1461(envArg),SPADCALL(SPADCALL(getValueFromEnvironment(QUOTE(
--I  y),QUOTE(SquareMatrix(2,Integer))),G1461,ELT(*1;anonymousFunction;3;initial;i
--I  nternal;MV,0)),SPADCALL(G1461,getValueFromEnvironment(QUOTE(y),QUOTE(SquareMa
--I  trix(2,Integer))),ELT(*1;anonymousFunction;3;initial;internal;MV,0)),ELT(*1;a
--I  nonymousFunction;3;initial;internal;MV,1)))))
--E 29

--S 30 of 33
x:S:='x
--R
--R
--R   (5)  x
--E 30

--S 31 of 33
a:S:=matrix [[2,3],[1,1]]
--R
--R
--R        +2  3+
--R   (6)  |    |
--R        +1  1+
--E 31
```

```
--S 32 of 33
x^2*a
--R
--R
--R        +2  3+ 2   +2  - 2+    +0  - 2+
--R   (7)  |    |x  + |      |x + |      |
--R        +1  1+     +0  - 2+    +0   0 +
--E 32

--S 33 of 33
)show UnivariateSkewPolynomial
--R
--R UnivariateSkewPolynomial(x: Symbol,R: Ring,sigma: Automorphism(R),delta: (R -> R))  is a dom
--R Abbreviation for UnivariateSkewPolynomial is OREUP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for OREUP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (R,%) -> %                      ?*? : (%,R) -> %
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        apply : (%,R,R) -> R
--R coefficients : % -> List(R)           coerce : Variable(x) -> %
--R coerce : R -> %                       coerce : Integer -> %
--R coerce : % -> OutputForm              degree : % -> NonNegativeInteger
--R hash : % -> SingleInteger             latex : % -> String
--R leadingCoefficient : % -> R           one? : % -> Boolean
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R retract : % -> R                      sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coefficient : (%,NonNegativeInteger) -> R
--R coerce : Fraction(Integer) -> % if R has RETRACT(FRAC(INT))
--R content : % -> R if R has GCDDOM
--R exquo : (%,R) -> Union(%,"failed") if R has INTDOM
--R leftDivide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R leftExactQuotient : (%,%) -> Union(%,"failed") if R has FIELD
--R leftExtendedGcd : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R leftGcd : (%,%) -> % if R has FIELD
--R leftLcm : (%,%) -> % if R has FIELD
--R leftQuotient : (%,%) -> % if R has FIELD
--R leftRemainder : (%,%) -> % if R has FIELD
--R minimumDegree : % -> NonNegativeInteger
```

```
--R monicLeftDivide : (%,%) -> Record(quotient: %,remainder: %) if R has INTDOM
--R monicRightDivide : (%,%) -> Record(quotient: %,remainder: %) if R has INTDOM
--R monomial : (R,NonNegativeInteger) -> %
--R primitivePart : % -> % if R has GCDDOM
--R retract : % -> Fraction(Integer) if R has RETRACT(FRAC(INT))
--R retract : % -> Integer if R has RETRACT(INT)
--R retractIfCan : % -> Union(R,"failed")
--R retractIfCan : % -> Union(Fraction(Integer),"failed") if R has RETRACT(FRAC(INT))
--R retractIfCan : % -> Union(Integer,"failed") if R has RETRACT(INT)
--R rightDivide : (%,%) -> Record(quotient: %,remainder: %) if R has FIELD
--R rightExactQuotient : (%,%) -> Union(%,"failed") if R has FIELD
--R rightExtendedGcd : (%,%) -> Record(coef1: %,coef2: %,generator: %) if R has FIELD
--R rightGcd : (%,%) -> % if R has FIELD
--R rightLcm : (%,%) -> % if R has FIELD
--R rightQuotient : (%,%) -> % if R has FIELD
--R rightRemainder : (%,%) -> % if R has FIELD
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 33
)set expose drop constructor SquareMatrix

)spool
)lisp (bye)
```

———-

— UnivariateSkewPolynomial.help —

```
=====================================================================
UnivariateSkewPolynomial examples
=====================================================================

Skew or Ore polynomial rings provide a unified framework to
compute with differential and difference equations.

In the following, let A be an integral domain, equipped with two
endomorphisms \sigma and \delta where:

 \sigma: A -> A is an injective ring endomorphism
 \delta: A -> A, the pseudo-derivation with respect to \sigma,
         is an additive endomorphism with

     \delta(ab) = \sigma(a)\delta(b) + \delta(a)b

         for all a,b in A

Note that in the domains and categories below, these properties are
not checked.
```

```
The skew polynomial ring [\Delta;\sigma,\delta] is the ring of
polynomials in \Delta with coefficients in A, with the usual addition,
while the product is given by

 \Delta a = \sigma(a)\Delta + \delta(a) for a in A

The two most important examples of skew polynomial rings are:

  K(x)[D,1,\delta], where 1 is the identity on K and \delta is
                    the usual derviative, is the ring of differential
                    polynomials

  K [E,n,\mapsto n+1,0] is the ring of linear recurrence operators
   n                    with polynomial coefficients


------------------------------------------------------------------------

For example,

The UnivariateSkewPolynomialCategory (OREPCAT) provides a unified
framework for polynomial rings in a non-central indeterminate over
some coefficient ring R. The commutation relations between the
indeterminate x and the coefficient t is given by

   x r = \sigma(r) x + \delta(r)

where \sigma is a ring endomorphism of R
and   \delta is a \sigma-derivation of R
which is an additive map from R to R such that

   \delta(rs) = \sigma(r) \delta(s) + \delta(r) s

In case \sigma is the identity map on R, a \sigma-derivation of R
is just called a derivation. Here are some examples

We start with a linear ordinary differential operator. First, we
define the coefficient ring to be expressions in one variable x
with fractional coefficients:

   F:=EXPR(FRAC(INT))

Define Dx to be a derivative d/dx:

   Dx:F->F:=f+->D(f,['x])

Define a skew polynomial ring over F with identity endomorphism as
\sigma and derivation d/dx as \delta:
```

```
D0:=OREUP('d,F,1,Dx)

u:D0:=(operator 'u)(x)

d:D0:='d

a:D0:=u^3*d^3+u^2*d^2+u*d+1

         3 3       2 2
     u(x) d  + u(x) d  + u(x)d + 1

b:D0:=(u+1)*d^2+2*d

                2
     (u(x) + 1)d  + 2d

r:=rightDivide(a,b)

                                  3 ,          3       2
                    3      - u(x) u (x) - u(x)  + u(x)
                 u(x)
[quotient= -------- d + ----------------------------,
           u(x) + 1                2
                                 u(x)  + 2u(x) + 1
                     3 ,           3
            2u(x) u (x) + 3u(x)  + u(x)

 remainder= --------------------------- d + 1]
                        2
                    u(x)  + 2u(x) + 1


r.quotient

                           3 ,          3       2
           3      - u(x) u (x) - u(x)  + u(x)
       u(x)
     -------- d + ----------------------------
     u(x) + 1                2
                           u(x)  + 2u(x) + 1


r.remainder

           3 ,           3
      2u(x) u (x) + 3u(x)  + u(x)

      --------------------------- d + 1
                2
           u(x)  + 2u(x) + 1
```

```
------------------------------------------------------------------------

   )clear all

As a second example, we consider the so-called Weyl algebra.

Define the coefficient ring to be an ordinary polynomial over integers
in one variable t

   R:=UP('t,INT)

Define a skew polynomial ring over R with identity map as \sigma
and derivation d/dt as \delta. The resulting algebra is then called
a Weyl algebra. This is a simple ring over a division ring that is
non-commutative, similar to the ring of matrices.

   W:=OREUP('x,R,1,D)

   t:W:='t

   x:W:='x

Let

   a:W:=(t-1)*x^4+(t^3+3*t+1)*x^2+2*t*x+t^3

                4     3           2           3
        (t - 1)x  + (t  + 3t + 1)x  + 2t x + t

   b:W:=(6*t^4+2*t^2)*x^3+3*t^2*x^2

           4     2  3     2 2
        (6t  + 2t )x  + 3t x

Then

   a*b
           5     4     3     2  7       4      3      2        6
        (6t  - 6t  + 2t  - 2t )x  + (96t  - 93t  + 13t  - 16t)x
      +
           7      5     4       3       2       5
        (6t  + 20t  + 6t  + 438t  - 406t  - 24)x
      +
            6      5       4      3       2              4
        (48t  + 15t  + 152t  + 61t  + 603t  - 532t - 36)x
      +
           7      5      4       3       2               3
        (6t  + 74t  + 60t  + 226t  + 116t  + 168t - 140)x
```

```
     +
          5     3      2            2
       (3t  + 6t  + 12t  + 18t + 6)x

  a^3
        3     2           12      5     4      3      2           10
      (t  - 3t  + 3t - 1)x   + (3t  - 6t  + 12t  - 15t  + 3t + 3)x
    +
         3      2       9      7     6      5      4      3     2            8
      (6t  - 12t  + 6t)x  + (3t  - 3t  + 21t  - 18t  + 24t  - 9t  - 15t - 3)x
    +
          5      4      3      2        7
      (12t  - 12t  + 36t  - 24t  - 12t)x
    +
        9      7     6      5     4      3      2           6
      (t  + 15t  - 3t  + 45t  + 6t  + 36t  + 15t  + 9t + 1)x
    +
         7      5      3      2       5
      (6t  + 48t  + 54t  + 36t  + 6t)x
    +
         9      7     6      5      4      3      2  4
      (3t  + 21t  + 3t  + 39t  + 18t  + 39t  + 12t )x
    +
          7      5      4     3  3      9     7     6      5  2     7     9
      (12t  + 36t  + 12t  + 8t )x  + (3t  + 9t  + 3t  + 12t )x  + 6t x + t
```

```
   )clear all
```

As a third example, we construct a difference operator algebra over the ring of EXPR(INT) by using an automorphism S defined by a "shift" operation S:EXPR(INT) -> EXPR(INT)

```
   s(e)(n) = e(n+1)
```

and an S-derivation defined by DF:EXPR(INT) -> EXPR(INT) as

```
   DF(e)(n) = e(n+1)-e(n)
```

Define S to be a "shift" operator, which acts on expressions with the discrete variable n:

```
   S:EXPR(INT)->EXPR(INT):=e+->eval(e,[n],[n+1])
```

Define DF to be a "difference" operator, which acts on expressions with a discrete variable n:

```
   DF:EXPR(INT)->EXPR(INT):=e+->eval(e,[n],[n+1])-e
```

```
Then define the difference operator algebra D0:

   D0:=OREUP('D,EXPR(INT),morphism S,DF)

   u:=(operator 'u)[n]

   L:D0:='D+u

        D + u(n)

   L^2

         2                2
        D  + 2u(n)D + u(n)

------------------------------------------------------------------------

   )clear all

As a fourth example, we construct a skew polynomial ring by using an
inner derivation \delta induced by a fixed y in R:

   \delta(r) = yr - ry

First we should expose the constructor SquareMatrix so it is visible
in the interpreter:

   )set expose add constructor SquareMatrix

Define R to be the square matrix with integer entries:

   R:=SQMATRIX(2,INT)

   y:R:=matrix [[1,1],[0,1]]
        +1  1+
        |    |
        +0  1+

Define the inner derivative \delta:

   delta:R->R:=r+->y*r-r*y

Define S to be a skew polynomial determined by \sigma = 1
and \delta as an inner derivative:

   S:=OREUP('x,R,1,delta)

   x:S:='x
```


```
a:S:=matrix [[2,3],[1,1]]
     +2  3+
     |    |
     +1  1+

x^2*a
     +2  3+ 2   +2  - 2+    +0  - 2+
     |    |x  + |      |x + |      |
     +1  1+     +0  - 2+    +0   0 +
```

See Also:
o)show UnivariateSkewPolynomial
o)show UnivariateSkewPolynomialCategory
o)show SquareMatrix

———————-

22.8.1 UnivariateSkewPolynomial (OREUP)



See

⇒ “Automorphism” (AUTOMOR) 2.44.1 on page 230
⇒ “SparseUnivariateSkewPolynomial” (ORESUP) 20.21.1 on page 2459

Exports:

0	1	apply
characteristic	coefficient	coefficients
coerce	content	degree
exquo	hash	latex
leadingCoefficient	leftDivide	leftExactQuotient
leftExtendedGcd	leftGcd	leftLcm
leftQuotient	leftRemainder	minimumDegree
monicLeftDivide	monicRightDivide	monomial
one?	primitivePart	recip
reductum	retract	retractIfCan
rightDivide	rightExactQuotient	rightExtendedGcd
rightGcd	rightLcm	rightQuotient
rightRemainder	sample	subtractIfCan
zero?	?*?	?**?
?+?	?-?	-?
?=?	?^?	?~=?

— domain OREUP UnivariateSkewPolynomial —

```
)abbrev domain OREUP UnivariateSkewPolynomial
++ Author: Manuel Bronstein
++ Date Created: 19 October 1993
++ Date Last Updated: 1 February 1994
++ Description:
++ This is the domain of univariate skew polynomials over an Ore
++ coefficient field in a named variable.
++ The multiplication is given by \spad{x a = \sigma(a) x + \delta a}.

UnivariateSkewPolynomial(x:Symbol,R:Ring,sigma:Automorphism R,delta: R -> R):
 UnivariateSkewPolynomialCategory R with
   coerce: Variable x -> %
     ++ coerce(x) returns x as a skew-polynomial.
  == SparseUnivariateSkewPolynomial(R, sigma, delta) add
     Rep := SparseUnivariateSkewPolynomial(R, sigma, delta)
     coerce(v:Variable(x)):% == monomial(1, 1)
     coerce(p:%):OutputForm  == outputForm(p, outputForm x)$Rep
```

———-

— OREUP.dotabb —

```
"OREUP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=OREUP"]
"OREPCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=OREPCAT"]
"OREUP" -> "OREPCAT"
```

———-

22.9 domain UTS UnivariateTaylorSeries

— UnivariateTaylorSeries.input —

```
)set break resume
)sys rm -f UnivariateTaylorSeries.output
)spool UnivariateTaylorSeries.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariateTaylorSeries
--R
--R UnivariateTaylorSeries(Coef: Ring,var: Symbol,cen: Coef)  is a domain constructor
--R Abbreviation for UnivariateTaylorSeries is UTS
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for UTS
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
--R ?*? : (%,%) -> %                     ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %       ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                     ?-? : (%,%) -> %
--R -? : % -> %                          ?=? : (%,%) -> Boolean
--R 1 : () -> %                          0 : () -> %
--R ?^? : (%,PositiveInteger) -> %       center : % -> Coef
--R coefficients : % -> Stream(Coef)     coerce : Variable(var) -> %
--R coerce : Integer -> %                coerce : % -> OutputForm
--R complete : % -> %                    degree : % -> NonNegativeInteger
--R evenlambert : % -> %                 hash : % -> SingleInteger
--R lagrange : % -> %                    lambert : % -> %
--R latex : % -> String                  leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %             map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean             oddlambert : % -> %
--R one? : % -> Boolean                  order : % -> NonNegativeInteger
--R pole? : % -> Boolean                 quoByVar : % -> %
--R recip : % -> Union(%,"failed")       reductum : % -> %
--R revert : % -> %                      sample : () -> %
--R series : Stream(Coef) -> %           variable : % -> Symbol
--R zero? : % -> Boolean                 ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Coef) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
```

```
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRING(SYM
--R D : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRI
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeInteger,Coef)
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,NonNegativeInteger) -> Coef if Coef has **: (Coef,NonNegativeInteger) -> Co
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,NonNegativeInteger) -> Coef
--R coerce : UnivariatePolynomial(var,Coef) -> %
--R coerce : Coef -> % if Coef has COMRING
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(var)) -> %
--R differentiate : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef ha
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and C
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeIn
--R ?.? : (%,%) -> % if NonNegativeInteger has SGROUP
--R ?.? : (%,NonNegativeInteger) -> Coef
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,NonNegativeInteger) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,NonNegativeInteger) -> %
--R generalLambert : (%,Integer,Integer) -> %
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variables: Coef ->
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R invmultisect : (Integer,Integer,%) -> %
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (Coef,NonNegativeInteger) -> %
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R multisect : (Integer,Integer,%) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,NonNegativeInteger) -> NonNegativeInteger
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R polynomial : (%,NonNegativeInteger,NonNegativeInteger) -> Polynomial(Coef)
--R polynomial : (%,NonNegativeInteger) -> Polynomial(Coef)
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: NonNegativeInteger,c: Coef)) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: NonNegativeInteger,c: Coef))
--R truncate : (%,NonNegativeInteger,NonNegativeInteger) -> %
--R truncate : (%,NonNegativeInteger) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R univariatePolynomial : (%,NonNegativeInteger) -> UnivariatePolynomial(var,Coef)
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— UnivariateTaylorSeries.help —

```
=====================================================================
UnivariateTaylorSeries examples
=====================================================================

See Also:
o )show UnivariateTaylorSeries
```

———-

22.9.1 UnivariateTaylorSeries (UTS)



See

⇒ "InnerTaylorSeries" (ITAYLOR) 10.28.1 on page 1306

Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coefficients	coerce	complete	cos
cosh	cot	coth	csc
csch	D	degree	differentiate
eval	evenlambert	exp	exquo
extend	generalLambert	hash	integrate
invmultisect	lagrange	lambert	latex
leadingCoefficient	leadingMonomial	log	map
monomial	monomial?	multiplyCoefficients	multiplyExponents
multisect	nthRoot	oddlambert	one?
order	pi	pole?	polynomial
quoByVar	recip	reductum	revert
sample	sec	sech	series
sin	sinh	sqrt	subtractIfCan
tan	tanh	terms	truncate
unit?	unitCanonical	unitNormal	univariatePolynomial
variable	variables	zero?	?*?
?**?	?+?	?-?	-?
?=?	?^?	?~=?	?.?

— domain UTS UnivariateTaylorSeries —

```
)abbrev domain UTS UnivariateTaylorSeries
```

```
++ Author: Clifton J. Williamson
++ Date Created: 21 December 1989
++ Date Last Updated: 21 September 1993
++ Basic Operations:
++ Related Domains: UnivariateLaurentSeries(Coef,var,cen),
++ UnivariatePuiseuxSeries(Coef,var,cen)
++ Also See:
++ AMS Classifications:
++ Keywords: dense, Taylor series
++ Examples:
++ References:
++ Description:
++ Dense Taylor series in one variable
++ \spadtype{UnivariateTaylorSeries} is a domain representing Taylor
++ series in
++ one variable with coefficients in an arbitrary ring.  The parameters
++ of the type specify the coefficient ring, the power series variable,
++ and the center of the power series expansion.  For example,
++ \spadtype{UnivariateTaylorSeries}(Integer,x,3) represents
++ Taylor series in
++ \spad{(x - 3)} with \spadtype{Integer} coefficients.

UnivariateTaylorSeries(Coef,var,cen): Exports == Implementation where
  Coef :  Ring
  var  :  Symbol
  cen  :  Coef
  I    ==> Integer
  NNI  ==> NonNegativeInteger
  P    ==> Polynomial Coef
  RN   ==> Fraction Integer
  ST   ==> Stream
  STT  ==> StreamTaylorSeriesOperations Coef
  TERM ==> Record(k:NNI,c:Coef)
  UP   ==> UnivariatePolynomial(var,Coef)
  Exports ==> UnivariateTaylorSeriesCategory(Coef) with
    coerce: UP -> %
      ++\spad{coerce(p)} converts a univariate polynomial p in the variable
      ++\spad{var} to a univariate Taylor series in \spad{var}.
    univariatePolynomial: (%,NNI) -> UP
      ++\spad{univariatePolynomial(f,k)} returns a univariate polynomial
      ++ consisting of the sum of all terms of f of degree \spad{<= k}.
    coerce: Variable(var) -> %
      ++\spad{coerce(var)} converts the series variable \spad{var} into a
      ++ Taylor series.
    differentiate: (%,Variable(var)) -> %
      ++ \spad{differentiate(f(x),x)} computes the derivative of
      ++ \spad{f(x)} with respect to \spad{x}.
    lagrange: % -> %
      ++\spad{lagrange(g(x))} produces the Taylor series for \spad{f(x)}
      ++ where \spad{f(x)} is implicitly defined as \spad{f(x) = x*g(f(x))}.
```

```
    lambert: % -> %
      ++\spad{lambert(f(x))} returns \spad{f(x) + f(x^2) + f(x^3) + ...}.
      ++ This function is used for computing infinite products.
      ++ \spad{f(x)} should have zero constant coefficient.
      ++ If \spad{f(x)} is a Taylor series with constant term 1, then
      ++ \spad{product(n = 1..infinity,f(x^n)) = exp(log(lambert(f(x))))}.
    oddlambert: % -> %
      ++\spad{oddlambert(f(x))} returns \spad{f(x) + f(x^3) + f(x^5) + ...}.
      ++ \spad{f(x)} should have a zero constant coefficient.
      ++ This function is used for computing infinite products.
      ++ If \spad{f(x)} is a Taylor series with constant term 1, then
      ++ \spad{product(n=1..infinity,f(x^(2*n-1)))=exp(log(oddlambert(f(x))))}.
    evenlambert: % -> %
      ++\spad{evenlambert(f(x))} returns \spad{f(x^2) + f(x^4) + f(x^6) + ...}.
      ++ \spad{f(x)} should have a zero constant coefficient.
      ++ This function is used for computing infinite products.
      ++ If \spad{f(x)} is a Taylor series with constant term 1, then
      ++ \spad{product(n=1..infinity,f(x^(2*n))) = exp(log(evenlambert(f(x))))}.
    generalLambert: (%,I,I) -> %
      ++\spad{generalLambert(f(x),a,d)} returns \spad{f(x^a) + f(x^(a + d)) +
      ++ f(x^(a + 2 d)) + ... }. \spad{f(x)} should have zero constant
      ++ coefficient and \spad{a} and d should be positive.
    revert: % -> %
      ++ \spad{revert(f(x))} returns a Taylor series \spad{g(x)} such that
      ++ \spad{f(g(x)) = g(f(x)) = x}. Series \spad{f(x)} should have constant
      ++ coefficient 0 and 1st order coefficient 1.
    multisect: (I,I,%) -> %
      ++\spad{multisect(a,b,f(x))} selects the coefficients of
      ++ \spad{x^((a+b)*n+a)}, and changes this monomial to \spad{x^n}.
    invmultisect: (I,I,%) -> %
      ++\spad{invmultisect(a,b,f(x))} substitutes \spad{x^((a+b)*n)}
      ++ for \spad{x^n} and multiples by \spad{x^b}.
    if Coef has Algebra Fraction Integer then
      integrate: (%,Variable(var)) -> %
        ++ \spad{integrate(f(x),x)} returns an anti-derivative of the power
        ++ series \spad{f(x)} with constant coefficient 0.
        ++ We may integrate a series when we can divide coefficients
        ++ by integers.

  Implementation ==> InnerTaylorSeries(Coef) add

    Rep := Stream Coef

--% creation and destruction of series

    stream: % -> Stream Coef
    stream x  == x pretend Stream(Coef)

    coerce(v:Variable(var)) ==
      zero? cen => monomial(1,1)
```

```
    monomial(1,1) + monomial(cen,0)

  coerce(n:I)    == n :: Coef :: %
  coerce(r:Coef) == coerce(r)$STT
  monomial(c,n)  == monom(c,n)$STT

  getExpon: TERM -> NNI
  getExpon term == term.k
  getCoef: TERM -> Coef
  getCoef term == term.c
  rec: (NNI,Coef) -> TERM
  rec(expon,coef) == [expon,coef]

  recs: (ST Coef,NNI) -> ST TERM
  recs(st,n) == delay$ST(TERM)
    empty? st => empty()
    zero? (coef := frst st) => recs(rst st,n + 1)
    concat(rec(n,coef),recs(rst st,n + 1))

  terms x == recs(stream x,0)

  recsToCoefs: (ST TERM,NNI) -> ST Coef
  recsToCoefs(st,n) == delay
    empty? st => empty()
    term := frst st; expon := getExpon term
    n = expon => concat(getCoef term,recsToCoefs(rst st,n + 1))
    concat(0,recsToCoefs(st,n + 1))

  series(st: ST TERM) == recsToCoefs(st,0)

  stToPoly: (ST Coef,P,NNI,NNI) -> P
  stToPoly(st,term,n,n0) ==
    (n > n0) or (empty? st) => 0
    frst(st) * term ** n + stToPoly(rst st,term,n + 1,n0)

  polynomial(x,n) == stToPoly(stream x,(var :: P) - (cen :: P),0,n)

  polynomial(x,n1,n2) ==
    if n1 > n2 then (n1,n2) := (n2,n1)
    stToPoly(rest(stream x,n1),(var :: P) - (cen :: P),n1,n2)

  stToUPoly: (ST Coef,UP,NNI,NNI) -> UP
  stToUPoly(st,term,n,n0) ==
    (n > n0) or (empty? st) => 0
    frst(st) * term ** n + stToUPoly(rst st,term,n + 1,n0)

  univariatePolynomial(x,n) ==
    stToUPoly(stream x,monomial(1,1)$UP - monomial(cen,0)$UP,0,n)

  coerce(p:UP) ==
```

```
      zero? p => 0
      if not zero? cen then
        p := p(monomial(1,1)$UP + monomial(cen,0)$UP)
      st : ST Coef := empty()
      oldDeg : NNI := degree(p) + 1
      while not zero? p repeat
        deg := degree p
        delta := (oldDeg - deg - 1) :: NNI
        for i in 1..delta repeat st := concat(0$Coef,st)
        st := concat(leadingCoefficient p,st)
        oldDeg := deg; p := reductum p
      for i in 1..oldDeg repeat st := concat(0$Coef,st)
      st

    if Coef has coerce: Symbol -> Coef then
      if Coef has "**": (Coef,NNI) -> Coef then

        stToCoef: (ST Coef,Coef,NNI,NNI) -> Coef
        stToCoef(st,term,n,n0) ==
          (n > n0) or (empty? st) => 0
          frst(st) * term ** n + stToCoef(rst st,term,n + 1,n0)

        approximate(x,n) ==
          stToCoef(stream x,(var :: Coef) - cen,0,n)

--% values

    variable x == var
    center   s == cen

    coefficient(x,n) ==
       -- Cannot use elt!  Should return 0 if stream doesn't have it.
       u := stream x
       while not empty? u and n > 0 repeat
         u := rst u
         n := (n - 1) :: NNI
       empty? u or n ^= 0 => 0
       frst u

    elt(x:%,n:NNI) == coefficient(x,n)

--% functions

    map(f,x) == map(f,x)$Rep
    eval(x:%,r:Coef) == eval(stream x,r-cen)$STT
    differentiate x == deriv(stream x)$STT
    differentiate(x:%,v:Variable(var)) == differentiate x
    if Coef has PartialDifferentialRing(Symbol) then
      differentiate(x:%,s:Symbol) ==
        (s = variable(x)) => differentiate x
```

```
      map(y +-> differentiate(y,s),x)
            - differentiate(center x,s)*differentiate(x)
  multiplyCoefficients(f,x) == gderiv(f,stream x)$STT
  lagrange x == lagrange(stream x)$STT
  lambert x == lambert(stream x)$STT
  oddlambert x == oddlambert(stream x)$STT
  evenlambert x == evenlambert(stream x)$STT
  generalLambert(x:%,a:I,d:I) == generalLambert(stream x,a,d)$STT
  extend(x,n) == extend(x,n+1)$Rep
  complete x == complete(x)$Rep
  truncate(x,n) == first(stream x,n + 1)$Rep
  truncate(x,n1,n2) ==
    if n2 < n1 then (n1,n2) := (n2,n1)
    m := (n2 - n1) :: NNI
    st := first(rest(stream x,n1)$Rep,m + 1)$Rep
    for i in 1..n1 repeat st := concat(0$Coef,st)
    st
  elt(x:%,y:%) == compose(stream x,stream y)$STT
  revert x == revert(stream x)$STT
  multisect(a,b,x) == multisect(a,b,stream x)$STT
  invmultisect(a,b,x) == invmultisect(a,b,stream x)$STT
  multiplyExponents(x,n) == invmultisect(n,0,x)
  quoByVar x == (empty? x => 0; rst x)
  if Coef has IntegralDomain then
    unit? x == unit? coefficient(x,0)
  if Coef has Field then
    if Coef is RN then
      (x:%) ** (s:Coef) == powern(s,stream x)$STT
    else
      (x:%) ** (s:Coef) == power(s,stream x)$STT

  if Coef has Algebra Fraction Integer then
    coerce(r:RN) == r :: Coef :: %

    integrate x == integrate(0,stream x)$STT
    integrate(x:%,v:Variable(var)) == integrate x

    if Coef has integrate: (Coef,Symbol) -> Coef and _
       Coef has variables: Coef -> List Symbol then
      integrate(x:%,s:Symbol) ==
        (s = variable(x)) => integrate x
        not entry?(s,variables center x) => map(y +-> integrate(y,s),x)
        error "integrate: center is a function of variable of integration"

    if Coef has TranscendentalFunctionCategory and _
       Coef has PrimitiveFunctionCategory and _
       Coef has AlgebraicallyClosedFunctionSpace Integer then

      integrateWithOneAnswer: (Coef,Symbol) -> Coef
      integrateWithOneAnswer(f,s) ==
```

```
          res := integrate(f,s)$FunctionSpaceIntegration(I,Coef)
          res case Coef => res :: Coef
          first(res :: List Coef)

        integrate(x:%,s:Symbol) ==
          (s = variable(x)) => integrate x
          not entry?(s,variables center x) =>
            map(y +-> integrateWithOneAnswer(y,s),x)
          error "integrate: center is a function of variable of integration"

--% OutputForms
--  We use the default coerce: % -> OutputForm in UTSCAT&
```

———-

— UTS.dotabb —

```
"UTS" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UTS"]
"ACFS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACFS"]
"UTS" -> "ACFS"
```

———-

22.10 domain UTSZ UnivariateTaylorSeriesCZero

— UnivariateTaylorSeriesCZero.input —

```
)set break resume
)sys rm -f UnivariateTaylorSeriesCZero.output
)spool UnivariateTaylorSeriesCZero.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show UnivariateTaylorSeriesCZero
--R
--R UnivariateTaylorSeriesCZero(Coef: Ring,var: Symbol)  is a domain constructor
--R Abbreviation for UnivariateTaylorSeriesCZero is UTSZ
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for UTSZ
--R
--R------------------------------ Operations ------------------------------
--R ?*? : (Coef,%) -> %                  ?*? : (%,Coef) -> %
```

```
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        center : % -> Coef
--R coefficients : % -> Stream(Coef)      coerce : Variable(var) -> %
--R coerce : Integer -> %                 coerce : % -> OutputForm
--R complete : % -> %                     degree : % -> NonNegativeInteger
--R evenlambert : % -> %                  hash : % -> SingleInteger
--R lagrange : % -> %                     lambert : % -> %
--R latex : % -> String                   leadingCoefficient : % -> Coef
--R leadingMonomial : % -> %              map : ((Coef -> Coef),%) -> %
--R monomial? : % -> Boolean              oddlambert : % -> %
--R one? : % -> Boolean                   order : % -> NonNegativeInteger
--R pole? : % -> Boolean                  quoByVar : % -> %
--R recip : % -> Union(%,"failed")        reductum : % -> %
--R revert : % -> %                       sample : () -> %
--R series : Stream(Coef) -> %            variable : % -> Symbol
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
--R ?*? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (Fraction(Integer),%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,Fraction(Integer)) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,%) -> % if Coef has ALGEBRA(FRAC(INT))
--R ?**? : (%,Coef) -> % if Coef has FIELD
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,Coef) -> % if Coef has FIELD
--R D : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R D : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRING(SYMBOL)
--R D : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDRING(SYMBOL)
--R D : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef has PDI
--R D : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and
--R ?^? : (%,NonNegativeInteger) -> %
--R acos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acoth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R acsch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R approximate : (%,NonNegativeInteger) -> Coef if Coef has **: (Coef,NonNegativeInteger) -> Coef and Coef
--R asec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R asinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R associates? : (%,%) -> Boolean if Coef has INTDOM
--R atan : % -> % if Coef has ALGEBRA(FRAC(INT))
--R atanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R characteristic : () -> NonNegativeInteger
```

```
--R charthRoot : % -> Union(%,"failed") if Coef has CHARNZ
--R coefficient : (%,NonNegativeInteger) -> Coef
--R coerce : UnivariatePolynomial(var,Coef) -> %
--R coerce : Coef -> % if Coef has COMRING
--R coerce : % -> % if Coef has INTDOM
--R coerce : Fraction(Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R cos : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cosh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R cot : % -> % if Coef has ALGEBRA(FRAC(INT))
--R coth : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csc : % -> % if Coef has ALGEBRA(FRAC(INT))
--R csch : % -> % if Coef has ALGEBRA(FRAC(INT))
--R differentiate : (%,Variable(var)) -> %
--R differentiate : % -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef
--R differentiate : (%,Symbol) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and Coef ha
--R differentiate : (%,List(Symbol)) -> % if Coef has *: (NonNegativeInteger,Coef) -> Coef and C
--R differentiate : (%,Symbol,NonNegativeInteger) -> % if Coef has *: (NonNegativeInteger,Coef)
--R differentiate : (%,List(Symbol),List(NonNegativeInteger)) -> % if Coef has *: (NonNegativeIn
--R ?.? : (%,%) -> % if NonNegativeInteger has SGROUP
--R ?.? : (%,NonNegativeInteger) -> Coef
--R eval : (%,Coef) -> Stream(Coef) if Coef has **: (Coef,NonNegativeInteger) -> Coef
--R exp : % -> % if Coef has ALGEBRA(FRAC(INT))
--R exquo : (%,%) -> Union(%,"failed") if Coef has INTDOM
--R extend : (%,NonNegativeInteger) -> %
--R generalLambert : (%,Integer,Integer) -> %
--R integrate : (%,Variable(var)) -> % if Coef has ALGEBRA(FRAC(INT))
--R integrate : (%,Symbol) -> % if Coef has integrate: (Coef,Symbol) -> Coef and Coef has variab
--R integrate : % -> % if Coef has ALGEBRA(FRAC(INT))
--R invmultisect : (Integer,Integer,%) -> %
--R log : % -> % if Coef has ALGEBRA(FRAC(INT))
--R monomial : (%,List(SingletonAsOrderedSet),List(NonNegativeInteger)) -> %
--R monomial : (%,SingletonAsOrderedSet,NonNegativeInteger) -> %
--R monomial : (Coef,NonNegativeInteger) -> %
--R multiplyCoefficients : ((Integer -> Coef),%) -> %
--R multiplyExponents : (%,PositiveInteger) -> %
--R multisect : (Integer,Integer,%) -> %
--R nthRoot : (%,Integer) -> % if Coef has ALGEBRA(FRAC(INT))
--R order : (%,NonNegativeInteger) -> NonNegativeInteger
--R pi : () -> % if Coef has ALGEBRA(FRAC(INT))
--R polynomial : (%,NonNegativeInteger,NonNegativeInteger) -> Polynomial(Coef)
--R polynomial : (%,NonNegativeInteger) -> Polynomial(Coef)
--R sec : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sech : % -> % if Coef has ALGEBRA(FRAC(INT))
--R series : Stream(Record(k: NonNegativeInteger,c: Coef)) -> %
--R sin : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sinh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R sqrt : % -> % if Coef has ALGEBRA(FRAC(INT))
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R tan : % -> % if Coef has ALGEBRA(FRAC(INT))
```

```
--R tanh : % -> % if Coef has ALGEBRA(FRAC(INT))
--R terms : % -> Stream(Record(k: NonNegativeInteger,c: Coef))
--R truncate : (%,NonNegativeInteger,NonNegativeInteger) -> %
--R truncate : (%,NonNegativeInteger) -> %
--R unit? : % -> Boolean if Coef has INTDOM
--R unitCanonical : % -> % if Coef has INTDOM
--R unitNormal : % -> Record(unit: %,canonical: %,associate: %) if Coef has INTDOM
--R univariatePolynomial : (%,NonNegativeInteger) -> UnivariatePolynomial(var,Coef)
--R variables : % -> List(SingletonAsOrderedSet)
--R
--E 1

)spool
)lisp (bye)
```

———-


— **UnivariateTaylorSeriesCZero.help** —

```
=====================================================================
UnivariateTaylorSeriesCZero examples
=====================================================================

See Also:
o )show UnivariateTaylorSeriesCZero
```

———-

22.10.1 UnivariateTaylorSeriesCZero (UTSZ)



See

⇒ “InnerTaylorSeries” (ITAYLOR) 10.28.1 on page 1306

Exports:

0	1	acos	acosh
acot	acoth	acsc	acsch
approximate	asec	asech	asin
asinh	associates?	atan	atanh
center	characteristic	charthRoot	coefficient
coefficients	coerce	complete	cos
cosh	cot	coth	csc
csch	D	degree	differentiate
eval	evenlambert	exp	exquo
extend	generalLambert	hash	integrate
invmultisect	lagrange	lambert	latex
leadingCoefficient	leadingMonomial	log	map
monomial	monomial?	multiplyCoefficients	multiplyExponents
multisect	nthRoot	oddlambert	one?
order	pi	pole?	polynomial
quoByVar	recip	reductum	revert
sample	sec	sech	series
sin	sinh	sqrt	subtractIfCan
tan	tanh	terms	truncate
unit?	unitCanonical	unitNormal	univariatePolynomial
variable	variables	zero?	?.?
?~=?	?/?	?*?	?**?
?+?	?-?	-?	?=?
?^?			

— domain UTSZ UnivariateTaylorSeriesCZero —

```
)abbrev domain UTSZ UnivariateTaylorSeriesCZero
++ Author: Gaetan Hache
++ Date Created: September 1996
++ Date Last Updated: April, 2010, by Tim Daly
++ Description:
++ Part of the Package for Algebraic Function Fields in one variable PAFF

UnivariateTaylorSeriesCZero(Coef,var): Exports == Implementation where
  Coef :  Ring
  var  :  Symbol
  I    ==> Integer
  NNI  ==> NonNegativeInteger
  P    ==> Polynomial Coef
  RN   ==> Fraction Integer
  ST   ==> Stream
  STT  ==> StreamTaylorSeriesOperations Coef
  TERM ==> Record(k:NNI,c:Coef)
  UP   ==> UnivariatePolynomial(var,Coef)
  Exports ==> UnivariateTaylorSeriesCategory(Coef) with
    coerce: UP -> %
```

```
    ++\spad{coerce(p)} converts a univariate polynomial p in the variable
    ++\spad{var} to a univariate Taylor series in \spad{var}.
  univariatePolynomial: (%,NNI) -> UP
    ++\spad{univariatePolynomial(f,k)} returns a univariate polynomial
    ++ consisting of the sum of all terms of f of degree \spad{<= k}.
  coerce: Variable(var) -> %
    ++\spad{coerce(var)} converts the series variable \spad{var} into a
    ++ Taylor series.
  differentiate: (%,Variable(var)) -> %
    ++ \spad{differentiate(f(x),x)} computes the derivative of
    ++ \spad{f(x)} with respect to \spad{x}.
  lagrange: % -> %
    ++\spad{lagrange(g(x))} produces the Taylor series for \spad{f(x)}
    ++ where \spad{f(x)} is implicitly defined as \spad{f(x) = x*g(f(x))}.
  lambert: % -> %
    ++\spad{lambert(f(x))} returns \spad{f(x) + f(x^2) + f(x^3) + ...}.
    ++ This function is used for computing infinite products.
    ++ \spad{f(x)} should have zero constant coefficient.
    ++ If \spad{f(x)} is a Taylor series with constant term 1, then
    ++ \spad{product(n = 1..infinity,f(x^n)) = exp(log(lambert(f(x))))}.
  oddlambert: % -> %
    ++\spad{oddlambert(f(x))} returns \spad{f(x) + f(x^3) + f(x^5) + ...}.
    ++ \spad{f(x)} should have a zero constant coefficient.
    ++ This function is used for computing infinite products.
    ++ If \spad{f(x)} is a Taylor series with constant term 1, then
    ++ \spad{product(n=1..infinity,f(x^(2*n-1)))=exp(log(oddlambert(f(x))))}.
  evenlambert: % -> %
    ++\spad{evenlambert(f(x))} returns \spad{f(x^2) + f(x^4) + f(x^6) + ...}.
    ++ \spad{f(x)} should have a zero constant coefficient.
    ++ This function is used for computing infinite products.
    ++ If \spad{f(x)} is a Taylor series with constant term 1, then
    ++ \spad{product(n=1..infinity,f(x^(2*n)))=exp(log(evenlambert(f(x))))}.
  generalLambert: (%,I,I) -> %
    ++\spad{generalLambert(f(x),a,d)} returns \spad{f(x^a) + f(x^(a + d)) +
    ++ f(x^(a + 2 d)) + ... }. \spad{f(x)} should have zero constant
    ++ coefficient and \spad{a} and d should be positive.
  revert: % -> %
    ++ \spad{revert(f(x))} returns a Taylor series \spad{g(x)} such that
    ++ \spad{f(g(x)) = g(f(x)) = x}. Series \spad{f(x)} should have constant
    ++ coefficient 0 and 1st order coefficient 1.
  multisect: (I,I,%) -> %
    ++\spad{multisect(a,b,f(x))} selects the coefficients of
    ++ \spad{x^((a+b)*n+a)}, and changes this monomial to \spad{x^n}.
  invmultisect: (I,I,%) -> %
    ++\spad{invmultisect(a,b,f(x))} substitutes \spad{x^((a+b)*n)}
    ++ for \spad{x^n} and multiples by \spad{x^b}.
  if Coef has Algebra Fraction Integer then
    integrate: (%,Variable(var)) -> %
      ++ \spad{integrate(f(x),x)} returns an anti-derivative of the power
      ++ series \spad{f(x)} with constant coefficient 0.
```

```
      ++ We may integrate a series when we can divide coefficients
      ++ by integers.

 Implementation ==> InnerTaylorSeries(Coef) add

  Rep := Stream Coef

  --% creation and destruction of series

  stream: % -> Stream Coef
  stream x  == x pretend Stream(Coef)

  coerce(v:Variable(var)) ==
    monomial(1,1)

  coerce(n:I)    == n :: Coef :: %
  coerce(r:Coef) == coerce(r)$STT
  monomial(c,n)  == monom(c,n)$STT

  getExpon: TERM -> NNI
  getExpon term == term.k
  getCoef: TERM -> Coef
  getCoef term == term.c
  rec: (NNI,Coef) -> TERM
  rec(expon,coef) == [expon,coef]

  recs: (ST Coef,NNI) -> ST TERM
  recs(st,n) == delay$ST(TERM)
    empty? st => empty()
    zero? (coef := frst st) => recs(rst st,n + 1)
    concat(rec(n,coef),recs(rst st,n + 1))

  terms x == recs(stream x,0)

  recsToCoefs: (ST TERM,NNI) -> ST Coef
  recsToCoefs(st,n) == delay
    empty? st => empty()
    term := frst st; expon := getExpon term
    n = expon => concat(getCoef term,recsToCoefs(rst st,n + 1))
    concat(0,recsToCoefs(st,n + 1))

  series(st: ST TERM) == recsToCoefs(st,0)

  stToPoly: (ST Coef,P,NNI,NNI) -> P
  stToPoly(st,term,n,n0) ==
    (n > n0) or (empty? st) => 0
    frst(st) * term ** n + stToPoly(rst st,term,n + 1,n0)

  polynomial(x,n) == stToPoly(stream x,(var :: P),0,n)
```

```
    polynomial(x,n1,n2) ==
      if n1 > n2 then (n1,n2) := (n2,n1)
      stToPoly(rest(stream x,n1),(var :: P),n1,n2)

    stToUPoly: (ST Coef,UP,NNI,NNI) -> UP
    stToUPoly(st,term,n,n0) ==
      (n > n0) or (empty? st) => 0
      frst(st) * term ** n + stToUPoly(rst st,term,n + 1,n0)

    univariatePolynomial(x,n) ==
      stToUPoly(stream x,monomial(1,1)$UP,0,n)

    coerce(p:UP) ==
      zero? p => 0
      st : ST Coef := empty()
      oldDeg : NNI := degree(p) + 1
      while not zero? p repeat
        deg := degree p
        delta := (oldDeg - deg - 1) :: NNI
        for i in 1..delta repeat st := concat(0$Coef,st)
        st := concat(leadingCoefficient p,st)
        oldDeg := deg; p := reductum p
      for i in 1..oldDeg repeat st := concat(0$Coef,st)
      st

    if Coef has coerce: Symbol -> Coef then
      if Coef has "**": (Coef,NNI) -> Coef then

        stToCoef: (ST Coef,Coef,NNI,NNI) -> Coef
        stToCoef(st,term,n,n0) ==
          (n > n0) or (empty? st) => 0
          frst(st) * term ** n + stToCoef(rst st,term,n + 1,n0)

        approximate(x,n) ==
          stToCoef(stream x,(var :: Coef),0,n)

--% values

    variable x == var
    center   x == 0$Coef

    coefficient(x,n) ==
       -- Cannot use elt!  Should return 0 if stream doesn't have it.
       u := stream x
       while not empty? u and n > 0 repeat
         u := rst u
         n := (n - 1) :: NNI
       empty? u or n ^= 0 => 0
       frst u
```

```
    elt(x:%,n:NNI) == coefficient(x,n)

--% functions

    map(f,x) == map(f,x)$Rep
    eval(x:%,r:Coef) == eval(stream x,r)$STT
    differentiate x == deriv(stream x)$STT
    differentiate(x:%,v:Variable(var)) == differentiate x
    if Coef has PartialDifferentialRing(Symbol) then
      differentiate(x:%,s:Symbol) ==
        (s = variable(x)) => differentiate x
       map(differentiate(#1,s),x) - differentiate(0,s)*differentiate(x)
    multiplyCoefficients(f,x) == gderiv(f,stream x)$STT
    lagrange x == lagrange(stream x)$STT
    lambert x == lambert(stream x)$STT
    oddlambert x == oddlambert(stream x)$STT
    evenlambert x == evenlambert(stream x)$STT
    generalLambert(x:%,a:I,d:I) == generalLambert(stream x,a,d)$STT
    extend(x,n) == extend(x,n+1)$Rep
    complete x == complete(x)$Rep
    truncate(x,n) == first(stream x,n + 1)$Rep
    truncate(x,n1,n2) ==
      if n2 < n1 then (n1,n2) := (n2,n1)
      m := (n2 - n1) :: NNI
      st := first(rest(stream x,n1)$Rep,m + 1)$Rep
      for i in 1..n1 repeat st := concat(0$Coef,st)
      st
    elt(x:%,y:%) == compose(stream x,stream y)$STT
    revert x == revert(stream x)$STT
    multisect(a,b,x) == multisect(a,b,stream x)$STT
    invmultisect(a,b,x) == invmultisect(a,b,stream x)$STT
    multiplyExponents(x,n) == invmultisect(n,0,x)
    quoByVar x == (empty? x => 0; rst x)
    if Coef has IntegralDomain then
      unit? x == unit? coefficient(x,0)
    if Coef has Field then
      if Coef is RN then
        (x:%) ** (s:Coef) == powern(s,stream x)$STT
      else
        (x:%) ** (s:Coef) == power(s,stream x)$STT

    if Coef has Algebra Fraction Integer then
      coerce(r:RN) == r :: Coef :: %

      integrate x == integrate(0,stream x)$STT
      integrate(x:%,v:Variable(var)) == integrate x

      if Coef has integrate: (Coef,Symbol) -> Coef and _
         Coef has variables: Coef -> List Symbol then
        integrate(x:%,s:Symbol) ==
```

```
          (s = variable(x)) => integrate x
          map(integrate(#1,s),x)

      if Coef has TranscendentalFunctionCategory and _
         Coef has PrimitiveFunctionCategory and _
         Coef has AlgebraicallyClosedFunctionSpace Integer then

        integrateWithOneAnswer: (Coef,Symbol) -> Coef
        integrateWithOneAnswer(f,s) ==
          res := integrate(f,s)$FunctionSpaceIntegration(I,Coef)
          res case Coef => res :: Coef
          first(res :: List Coef)

        integrate(x:%,s:Symbol) ==
          (s = variable(x)) => integrate x
          map(integrateWithOneAnswer(#1,s),x)
```

———-

— UTSZ.dotabb —

```
"UTSZ" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UTSZ"]
"ACFS" [color="#4488FF",href="bookvol10.2.pdf#nameddest=ACFS"]
"UTSZ" -> "ACFS"
```

———-

22.11 domain UNISEG UniversalSegment

— UniversalSegment.input —

```
)set break resume
)sys rm -f UniversalSegment.output
)spool UniversalSegment.output
)set message test on
)set message auto off
)clear all
--S 1 of 9
pints := 1..
--R
--R
--R   (1)  1..
--R                                    Type: UniversalSegment(PositiveInteger)
--E 1
```

```
--S 2 of 9
nevens := (0..) by -2
--R
--R
--R   (2)  0.. by - 2
--R                                    Type: UniversalSegment(NonNegativeInteger)
--E 2

--S 3 of 9
useg: UniversalSegment(Integer) := 3..10
--R
--R
--R   (3)  3..10
--R                                                Type: UniversalSegment(Integer)
--E 3

--S 4 of 9
hasHi pints
--R
--R
--R   (4)  false
--R                                                                    Type: Boolean
--E 4

--S 5 of 9
hasHi nevens
--R
--R
--R   (5)  false
--R                                                                    Type: Boolean
--E 5

--S 6 of 9
hasHi useg
--R
--R
--R   (6)  true
--R                                                                    Type: Boolean
--E 6

--S 7 of 9
expand pints
--R
--R
--R   (7)  [1,2,3,4,5,6,7,8,9,10,...]
--R                                                          Type: Stream(Integer)
--E 7

--S 8 of 9
```

```
expand nevens
--R
--R
--R   (8)  [0,- 2,- 4,- 6,- 8,- 10,- 12,- 14,- 16,- 18,...]
--R                                                    Type: Stream(Integer)
--E 8

--S 9 of 9
expand [1, 3, 10..15, 100..]
--R
--R
--R   (9)  [1,3,10,11,12,13,14,15,100,101,...]
--R                                                    Type: Stream(Integer)
--E 9
)spool
)lisp (bye)
```

———-

— UniversalSegment.help —

```
=====================================================================
UniversalSegment examples
=====================================================================

The UniversalSegment domain generalizes Segment by allowing segments
without a "hi" end point.

  pints := 1..
    1..
                                Type: UniversalSegment PositiveInteger

  nevens := (0..) by -2
    0.. by - 2
                                Type: UniversalSegment NonNegativeInteger

Values of type Segment are automatically converted to type
UniversalSegment when appropriate.

  useg: UniversalSegment(Integer) := 3..10
    3..10
                                Type: UniversalSegment Integer

The operation hasHi is used to test whether a segment has a hi end point.

  hasHi pints
    false
                                Type: Boolean
```

```
  hasHi nevens
    false
                                Type: Boolean

  hasHi useg
    true
                                Type: Boolean

All operations available on type Segment apply to UniversalSegment, with
the proviso that expansions produce streams rather than lists.  This is
to accommodate infinite expansions.


  expand pints
    [1,2,3,4,5,6,7,8,9,10,...]
                                Type: Stream Integer

  expand nevens
    [0,- 2,- 4,- 6,- 8,- 10,- 12,- 14,- 16,- 18,...]
                                Type: Stream Integer

  expand [1, 3, 10..15, 100..]
    [1,3,10,11,12,13,14,15,100,101,...]
                                Type: Stream Integer

See Also:
o )help Segment
o )help SegmentBinding
o )help List
o )help Stream
o )show UniversalSegment
```

22.11.1 UniversalSegment (UNISEG)



See

⇒ "Segment" (SEG) 20.2.1 on page 2325
⇒ "SegmentBinding" (SEGBIND) 20.3.1 on page 2330

Exports:

BY	coerce	convert	expand	hasHi
hash	hi	high	incr	latex
lo	low	map	segment	segment
?=?	?SEGMENT	?..?	?~=?	

— domain UNISEG UniversalSegment —

```
)abbrev domain UNISEG UniversalSegment
++ Author:  Robert S. Sutor
++ Date Created: 1987
++ Date Last Updated: June 4, 1991
++ Basic Operations:
++ Related Domains: Segment
++ Also See:
++ AMS Classifications:
++ Keywords: equation
++ Examples:
++ References:
++ Description:
++ This domain provides segments which may be half open.
++ That is, ranges of the form \spad{a..} or \spad{a..b}.

UniversalSegment(S: Type): SegmentCategory(S) with
    SEGMENT: S -> %
        ++ \spad{l..} produces a half open segment,
        ++ that is, one with no upper bound.
    segment: S -> %
        ++ segment(l) is an alternate way to construct the segment \spad{l..}.
    coerce : Segment S -> %
        ++ coerce(x) allows \spadtype{Segment} values to be used as %.
    hasHi: % -> Boolean
```

```
        ++ hasHi(s) tests whether the segment s has an upper bound.

    if S has SetCategory then SetCategory

    if S has OrderedRing then
      SegmentExpansionCategory(S, Stream S)
--    expand : (List %, S) -> Stream S
--    expand : (%, S) -> Stream S

  == add
    Rec  ==> Record(low: S, high: S, incr: Integer)
    Rec2 ==> Record(low: S, incr: Integer)
    SEG ==> Segment S

    Rep := Union(Rec2, Rec)
    a,b : S
    s : %
    i: Integer
    ls : List %

    segment a == [a, 1]$Rec2 :: Rep
    segment(a,b) == [a,b,1]$Rec :: Rep
    BY(s,i) ==
      s case Rec => [lo s, hi s, i]$Rec ::Rep
      [lo s, i]$Rec2 :: Rep

    lo s ==
      s case Rec2 => (s :: Rec2).low
      (s :: Rec).low

    low s ==
      s case Rec2 => (s :: Rec2).low
      (s :: Rec).low

    hasHi s == s case Rec

    hi s ==
      not hasHi(s) => error "hi: segment has no upper bound"
      (s :: Rec).high

    high s ==
      not hasHi(s) => error "high: segment has no upper bound"
      (s :: Rec).high

    incr s ==
      s case Rec2 => (s :: Rec2).incr
      (s :: Rec).incr

    SEGMENT(a) == segment a
    SEGMENT(a,b) == segment(a,b)
```

```
    coerce(sg : SEG): % == segment(lo sg, hi sg)

    convert a == [a,a,1]

    if S has SetCategory then

       (s1:%) = (s2:%) ==
          s1 case Rec2 =>
             s2 case Rec2 =>
                 s1.low = s2.low and s1.incr = s2.incr
             false
          s1 case Rec =>
             s2 case Rec =>
                 s2.low = s2.low and s1.high=s2.high and s1.incr=s2.incr
             false
          false

       coerce(s: %): OutputForm ==
         seg :=
           e := (lo s)::OutputForm
           hasHi s => SEGMENT(e, (hi s)::OutputForm)
           SEGMENT e
         inc := incr s
         inc = 1 => seg
         infix(" by "::OutputForm, seg, inc::OutputForm)

    if S has OrderedRing then
      expand(s:%)       == expand([s])
      map(f:S->S, s:%)  == map(f, expand s)

      plusInc(t: S, a: S): S == t + a

      expand(ls: List %):Stream S ==
        st:Stream S := empty()
        null ls => st

        lb:List(Segment S) := nil()
        while not null ls and hasHi first ls repeat
            s  := first ls
            ls := rest ls
            ns := BY(SEGMENT(lo s, hi s), incr s)$Segment(S)
            lb := concat_!(lb,ns)
        if not null ls then
            s := first ls
            st: Stream S := generate(x +-> x+incr(s)::S, lo s)
        else
            st: Stream S := empty()
        concat(construct expand(lb),  st)
```

———-

— **UNISEG.dotabb** —

```
"UNISEG" [color="#88FF44",href="bookvol10.3.pdf#nameddest=UNISEG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"UNISEG" -> "FLAGG-"
```

———-

22.12 domain U32VEC U32Vector

— **U32Vector.input** —

```
)set break resume
)sys rm -f U32Vector.output
)spool U32Vector.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show U32Vector
--R
--R U32Vector  is a domain constructor
--R Abbreviation for U32Vector is U32VEC
--R This constructor is exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for U32VEC
--R
--R------------------------------ Operations --------------------------------
--R concat : List(%) -> %                concat : (%,%) -> %
--R concat : (Integer,%) -> %            concat : (%,Integer) -> %
--R construct : List(Integer) -> %       copy : % -> %
--R delete : (%,Integer) -> %            ?.? : (%,Integer) -> Integer
--R empty : () -> %                      empty? : % -> Boolean
--R entries : % -> List(Integer)         eq? : (%,%) -> Boolean
--R index? : (Integer,%) -> Boolean      indices : % -> List(Integer)
--R insert : (%,%,Integer) -> %          qelt : (%,Integer) -> Integer
--R reverse : % -> %                     sample : () -> %
--R #? : % -> NonNegativeInteger if $ has finiteAggregate
--R ?<? : (%,%) -> Boolean if Integer has ORDSET
--R ?<=? : (%,%) -> Boolean if Integer has ORDSET
--R ?=? : (%,%) -> Boolean if Integer has SETCAT
--R ?>? : (%,%) -> Boolean if Integer has ORDSET
--R ?>=? : (%,%) -> Boolean if Integer has ORDSET
```

```
--R any? : ((Integer -> Boolean),%) -> Boolean if $ has finiteAggregate
--R coerce : % -> OutputForm if Integer has SETCAT
--R convert : % -> InputForm if Integer has KONVERT(INFORM)
--R copyInto! : (%,%,Integer) -> % if $ has shallowlyMutable
--R count : (Integer,%) -> NonNegativeInteger if $ has finiteAggregate and Integer has SETCAT
--R count : ((Integer -> Boolean),%) -> NonNegativeInteger if $ has finiteAggregate
--R delete : (%,UniversalSegment(Integer)) -> %
--R ?.? : (%,UniversalSegment(Integer)) -> %
--R elt : (%,Integer,Integer) -> Integer
--R entry? : (Integer,%) -> Boolean if $ has finiteAggregate and Integer has SETCAT
--R eval : (%,List(Integer),List(Integer)) -> % if Integer has EVALAB(INT) and Integer has SETCAT
--R eval : (%,Integer,Integer) -> % if Integer has EVALAB(INT) and Integer has SETCAT
--R eval : (%,Equation(Integer)) -> % if Integer has EVALAB(INT) and Integer has SETCAT
--R eval : (%,List(Equation(Integer))) -> % if Integer has EVALAB(INT) and Integer has SETCAT
--R every? : ((Integer -> Boolean),%) -> Boolean if $ has finiteAggregate
--R fill! : (%,Integer) -> % if $ has shallowlyMutable
--R find : ((Integer -> Boolean),%) -> Union(Integer,"failed")
--R first : % -> Integer if Integer has ORDSET
--R hash : % -> SingleInteger if Integer has SETCAT
--R insert : (Integer,%,Integer) -> %
--R latex : % -> String if Integer has SETCAT
--R less? : (%,NonNegativeInteger) -> Boolean
--R map : (((Integer,Integer) -> Integer),%,%) -> %
--R map : ((Integer -> Integer),%) -> %
--R map! : ((Integer -> Integer),%) -> % if $ has shallowlyMutable
--R max : (%,%) -> % if Integer has ORDSET
--R maxIndex : % -> Integer if Integer has ORDSET
--R member? : (Integer,%) -> Boolean if $ has finiteAggregate and Integer has SETCAT
--R members : % -> List(Integer) if $ has finiteAggregate
--R merge : (%,%) -> % if Integer has ORDSET
--R merge : (((Integer,Integer) -> Boolean),%,%) -> %
--R min : (%,%) -> % if Integer has ORDSET
--R minIndex : % -> Integer if Integer has ORDSET
--R more? : (%,NonNegativeInteger) -> Boolean
--R new : (NonNegativeInteger,Integer) -> %
--R parts : % -> List(Integer) if $ has finiteAggregate
--R position : (Integer,%,Integer) -> Integer if Integer has SETCAT
--R position : (Integer,%) -> Integer if Integer has SETCAT
--R position : ((Integer -> Boolean),%) -> Integer
--R qsetelt! : (%,Integer,Integer) -> Integer if $ has shallowlyMutable
--R reduce : (((Integer,Integer) -> Integer),%) -> Integer if $ has finiteAggregate
--R reduce : (((Integer,Integer) -> Integer),%,Integer) -> Integer if $ has finiteAggregate
--R reduce : (((Integer,Integer) -> Integer),%,Integer,Integer) -> Integer if $ has finiteAggregate and Inte
--R remove : ((Integer -> Boolean),%) -> % if $ has finiteAggregate
--R remove : (Integer,%) -> % if $ has finiteAggregate and Integer has SETCAT
--R removeDuplicates : % -> % if $ has finiteAggregate and Integer has SETCAT
--R reverse! : % -> % if $ has shallowlyMutable
--R select : ((Integer -> Boolean),%) -> % if $ has finiteAggregate
--R setelt : (%,UniversalSegment(Integer),Integer) -> Integer if $ has shallowlyMutable
--R setelt : (%,Integer,Integer) -> Integer if $ has shallowlyMutable
```

```
--R size? : (%,NonNegativeInteger) -> Boolean
--R sort : % -> % if Integer has ORDSET
--R sort : (((Integer,Integer) -> Boolean),%) -> %
--R sort! : % -> % if $ has shallowlyMutable and Integer has ORDSET
--R sort! : (((Integer,Integer) -> Boolean),%) -> % if $ has shallowlyMutable
--R sorted? : % -> Boolean if Integer has ORDSET
--R sorted? : (((Integer,Integer) -> Boolean),%) -> Boolean
--R swap! : (%,Integer,Integer) -> Void if $ has shallowlyMutable
--R ?~=? : (%,%) -> Boolean if Integer has SETCAT
--R
--E 1

)spool
)lisp (bye)
```

———-


— U32Vector.help —

```
=====================================================================
U32Vector examples
=====================================================================

See Also:
o )show U32Vector
```

———-

22.12.1 U32Vector (U32VEC)



See

⇒ “Segment” (SEG) 20.2.1 on page 2325
⇒ “SegmentBinding” (SEGBIND) 20.3.1 on page 2330

Exports:

#?	?.?	?.?	?<=?	?<?
?=?	?>=?	?>?	?~=?	any?
coerce	concat	construct	convert	copy
copyInto!	count	delete	elt	empty
empty?	entries	entry?	eq?	eval
every?	fill!	find	first	hash
index?	indices	insert	latex	less?
map	map!	max	maxIndex	member?
members	merge	min	minIndex	more?
new	parts	position	qelt	qsetelt!
reduce	remove	removeDuplicates	reverse	reverse!
sample	select	setelt	size?	sort
sort!	sorted?	swap!		

— **domain U32VEC U32Vector** —

```
)abbrev domain U32VEC U32Vector
++ Author: Waldek Hebisch
++ Description: This is a low-level domain which implements vectors
++ (one dimensional arrays) of unsigned 32-bit numbers.  Indexing
++ is 0 based, there is no bound checking (unless provided by
++ lower level).
U32Vector() : OneDimensionalArrayAggregate Integer == add
   Qsize ==> QV32LEN$Lisp
   Qelt ==> ELT32$Lisp
   Qsetelt ==> SETELT32$Lisp
   Qnew ==> MAKE_-ARRAY32$Lisp

   #x                          == Qsize x
   minIndex x                  == 0
   empty()                     == Qnew(0$Lisp, 0$Lisp)
   new(n, x)                   == Qnew (n, x)
   qelt(x, i)                  == Qelt(x, i)
   elt(x:%, i:Integer)         == Qelt(x, i)
   qsetelt_!(x, i, s)          == Qsetelt(x, i, s)
   setelt(x:%, i:Integer, s:Integer) == Qsetelt(x, i, s)
   fill_!(x, s)       == (for i in 0..((Qsize x) - 1) repeat Qsetelt(x, i, s); x)
```

———-

— **U32VEC.dotabb** —

```
"U32VEC" [color="#88FF44",href="bookvol10.3.pdf#nameddest=U32VEC"]
"A1AGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=A1AGG"]
"U32VEC" -> "A1AGG"
```

Chapter 23

Chapter V

23.1 domain VARIABLE Variable

— Variable.input —

```
)set break resume
)sys rm -f Variable.output
)spool Variable.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show Variable
--R
--R Variable(sym: Symbol)  is a domain constructor
--R Abbreviation for Variable is VARIABLE
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for VARIABLE
--R
--R------------------------------ Operations --------------------------------
--R ?=? : (%,%) -> Boolean               coerce : % -> Symbol
--R coerce : % -> OutputForm             hash : % -> SingleInteger
--R latex : % -> String                  variable : () -> Symbol
--R ?~=? : (%,%) -> Boolean
--R
--E 1

)spool
)lisp (bye)
```


———-

— Variable.help —

```
========================================================================
Variable examples
========================================================================

See Also:
o )show Variable
```

23.1.1 Variable (VARIABLE)



Exports:
coerce hash latex variable ?=? ?~=?

— domain VARIABLE Variable —

```
)abbrev domain VARIABLE Variable
++ Author: Mark Botch
++ Description:
++ This domain implements variables

Variable(sym:Symbol): Join(SetCategory, CoercibleTo Symbol) with
        coerce  : % -> Symbol
                ++ coerce(x) returns the symbol
        variable: () -> Symbol
                ++ variable() returns the symbol
    == add
        coerce(x:%):Symbol     == sym
        coerce(x:%):OutputForm == sym::OutputForm
        variable()             == sym
        x = y                  == true
```

```
        latex(x:%):String      == latex sym
```

———-

— **VARIABLE.dotabb** —

```
"VARIABLE" [color="#88FF44",href="bookvol10.3.pdf#nameddest=VARIABLE"]
"ALIST" [color="#88FF44",href="bookvol10.3.pdf#nameddest=ALIST"]
"VARIABLE" -> "ALIST"
```

———-

23.2 domain VECTOR Vector

— **Vector.input** —

```
)set break resume
)sys rm -f Vector.output
)spool Vector.output
)set message test on
)set message auto off
)clear all
--S 1 of 11
u : VECTOR INT := new(5,12)
--R
--R
--R   (1)  [12,12,12,12,12]
--R                                                    Type: Vector(Integer)
--E 1

--S 2 of 11
v : VECTOR INT := vector([1,2,3,4,5])
--R
--R
--R   (2)  [1,2,3,4,5]
--R                                                    Type: Vector(Integer)
--E 2

--S 3 of 11
#(v)
--R
--R
--R   (3)  5
--R                                                    Type: PositiveInteger
```

```
--E 3

--S 4 of 11
v.2
--R
--R
--R   (4)  2
--R                                                    Type: PositiveInteger
--E 4

--S 5 of 11
v.3 := 99
--R
--R
--R   (5)  99
--R                                                    Type: PositiveInteger
--E 5

--S 6 of 11
v
--R
--R
--R   (6)  [1,2,99,4,5]
--R                                                    Type: Vector(Integer)
--E 6

--S 7 of 11
5 * v
--R
--R
--R   (7)  [5,10,495,20,25]
--R                                                    Type: Vector(Integer)
--E 7

--S 8 of 11
v * 7
--R
--R
--R   (8)  [7,14,693,28,35]
--R                                                    Type: Vector(Integer)
--E 8

--S 9 of 11
w : VECTOR INT := vector([2,3,4,5,6])
--R
--R
--R   (9)  [2,3,4,5,6]
--R                                                    Type: Vector(Integer)
--E 9
```

```
--S 10 of 11
v + w
--R
--R
--R   (10)  [3,5,103,9,11]
--R                                                    Type: Vector(Integer)
--E 10

--S 11 of 11
v - w
--R
--R
--R   (11)  [- 1,- 1,95,- 1,- 1]
--R                                                    Type: Vector(Integer)
--E 11
)spool
)lisp (bye)
```

———-

— Vector.help —

```
========================================================================
Vector examples
========================================================================

The Vector domain is used for storing data in a one-dimensional
indexed data structure.  A vector is a homogeneous data structure in
that all the components of the vector must belong to the same Axiom
domain.  Each vector has a fixed length specified by the user; vectors
are not extensible.  This domain is similar to the OneDimensionalArray
domain, except that when the components of a Vector belong to a Ring,
arithmetic operations are provided.

As with the OneDimensionalArray domain, a Vector can be created by
calling the operation new, its components can be accessed by calling
the operations elt and qelt, and its components can be reset by
calling the operations setelt and qsetelt.

This creates a vector of integers of length 5 all of whose components are 12.

  u : VECTOR INT := new(5,12)
    [12,12,12,12,12]
                                Type: Vector Integer

This is how you create a vector from a list of its components.

  v : VECTOR INT := vector([1,2,3,4,5])
    [1,2,3,4,5]
```

```
                                Type: Vector Integer
```

Indexing for vectors begins at 1. The last element has index equal to the length of the vector, which is computed by #.

```
 #(v)
    5
                                Type: PositiveInteger
```

This is the standard way to use elt to extract an element. Functionally, it is the same as if you had typed elt(v,2).

```
  v.2
    2
                                Type: PositiveInteger
```

This is the standard way to use setelt to change an element. It is the same as if you had typed setelt(v,3,99).

```
  v.3 := 99
    99
                                Type: PositiveInteger
```

Now look at v to see the change. You can use qelt and qsetelt (instead of elt and setelt, respectively) but only when you know that the index is within the valid range.

```
  v
    [1,2,99,4,5]
                                Type: Vector Integer
```

When the components belong to a Ring, Axiom provides arithmetic operations for Vector. These include left and right scalar multiplication.

```
  5 * v
    [5,10,495,20,25]
                                Type: Vector Integer

  v * 7
    [7,14,693,28,35]
                                Type: Vector Integer

  w : VECTOR INT := vector([2,3,4,5,6])
    [2,3,4,5,6]
                                Type: Vector Integer
```

Addition and subtraction are also available.

```
  v + w
    [3,5,103,9,11]
```

```
                                Type: Vector Integer
```


Of course, when adding or subtracting, the two vectors must have the same length or an error message is displayed.

```
  v - w
    [- 1,- 1,95,- 1,- 1]
                                Type: Vector Integer
```

See Also:
o)help List
o)help Matrix
o)help OneDimensionalArray
o)help Set
o)help Table
o)help TwoDimensionalArray
o)show Vector

———-

23.2.1 Vector (VECTOR)



Exports:

any?	coerce	concat	construct	convert
copy	copyInto!	count	cross	delete
dot	elt	empty	empty?	entries
entry?	eq?	eval	every?	fill!
find	first	hash	index?	indices
insert	latex	length	less?	magnitude
map	map!	max	maxIndex	member?
members	merge	min	minIndex	more?
new	outerProduct	parts	position	qelt
qsetelt!	reduce	remove	removeDuplicates	reverse
reverse!	sample	select	setelt	size?
sort	sort!	sorted?	swap!	vector
zero	#?	?*?	?+?	?-?
?<?	?<=?	?=?	?>?	?>=?
?.?	?~=?	-?	?.?	

— domain VECTOR Vector —

```
)abbrev domain VECTOR Vector
++ Author: Mark Botch
++ Date Created:
++ Date Last Updated:
++ Basic Functions:
++ Related Constructors: IndexedVector, DirectProduct
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type represents vector like objects with varying lengths
++ and indexed by a finite segment of integers starting at 1.

Vector(R:Type): Exports == Implementation where
 VECTORMININDEX ==> 1       -- if you want to change this, be my guest

 Exports ==> VectorCategory R with
   vector: List R -> %
     ++ vector(l) converts the list l to a vector.
 Implementation ==>
  IndexedVector(R, VECTORMININDEX) add
     vector l == construct l
     if R has ConvertibleTo InputForm then
       convert(x:%):InputForm ==
          convert [convert("vector"::Symbol)@InputForm,
                          convert(parts x)@InputForm]
```

———-

— **VECTOR.dotabb** —

```
"VECTOR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=VECTOR",
          shape=ellipse]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"VECTOR" -> "STRING"
```

———-

23.3 domain VOID Void

— **Void.input** —

```
)set break resume
)sys rm -f Void.output
)spool Void.output
)set message test on
)set message auto off
)clear all
--S 1 of 5
r := (a; b; if c then d else e; f)
--R
--R
--RDaly Bug
--R   An expression following if/when must evaluate to a Boolean and you
--R      have written one that does not.
--E 1

--S 2 of 5
a : Integer
--R
--R                                                              Type: Void
--E 2

)set message void on

--S 3 of 5
b : Fraction Integer
--R
--R
--R   (2)  "()"
--R                                                              Type: Void
--E 3

)set message void off
```

```
--S 4 of 5
3::Void
--R
--R                                                                Type: Void
--E 4

--S 5 of 5
% :: PositiveInteger
--R
--R
--RDaly Bug
--R   Cannot convert from type Void to PositiveInteger for value
--R   "()"
--R
--E 5
)spool
)lisp (bye)
```

———-

— Void.help —

```
====================================================================
Void examples
====================================================================

When an expression is not in a value context, it is given type Void.
For example, in the expression

  r := (a; b; if c then d else e; f)

values are used only from the subexpressions c and f: all others are thrown
away.  The subexpressions a, b, d and e are evaluated for side-effects only
and have type Void.  There is a unique value of type Void.

You will most often see results of type Void when you declare a variable.

  a : Integer
                                Type: Void

Usually no output is displayed for Void results.  You can force the
display of a rather ugly object by issuing

  )set message void on

  b : Fraction Integer
                                Type: Void
```

```
  )set message void off

All values can be converted to type Void.


  3::Void
                                  Type: Void

Once a value has been converted to Void, it cannot be recovered.

  % :: PositiveInteger
   Cannot convert from type Void to PositiveInteger for value "()"

See Also:
o )show Void
```

23.3.1 Void (VOID)



Exports:
coerce void

— domain VOID Void —

```
)abbrev domain VOID Void
-- These types act as the top and bottom of the type lattice
-- and are known to the compiler and interpreter for type resolution.
++ Author: Stephen M. Watt
++ Date Created: 1986
++ Date Last Updated: May 30, 1991
++ Basic Operations:
++ Related Domains: ErrorFunctions, ResolveLatticeCompletion, Exit
++ Also See:
```

```
++ AMS Classifications:
++ Keywords: type, mode, coerce, no value
++ Examples:
++ References:
++ Description:
++ This type is used when no value is needed, e.g., in the \spad{then}
++ part of a one armed \spad{if}.
++ All values can be coerced to type Void.  Once a value has been coerced
++ to Void, it cannot be recovered.

Void: with
        void: () -> %
          ++ void() produces a void object.
        coerce: % -> OutputForm
          ++ coerce(v) coerces void object to outputForm.
    == add
        Rep := String
        void()      == voidValue()$Lisp
        coerce(v:%) == coerce(v)$Rep
```

———-

— VOID.dotabb —

```
"VOID" [color="#88FF44",href="bookvol10.3.pdf#nameddest=VOID"]
"STRING" [color="#88FF44",href="bookvol10.3.pdf#nameddest=STRING"]
"VOID" -> "STRING"
```

———-

Chapter 24

Chapter W

24.1 domain WP WeightedPolynomials

— WeightedPolynomials.input —

```
)set break resume
)sys rm -f WeightedPolynomials.output
)spool WeightedPolynomials.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show WeightedPolynomials
--R
--R WeightedPolynomials(R: Ring,VarSet: OrderedSet,E: OrderedAbelianMonoidSup,P: PolynomialCategory(R,E,VarS
--R Abbreviation for WeightedPolynomials is WP
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for WP
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (Integer,%) -> %
--R ?*? : (PositiveInteger,%) -> %        ?**? : (%,PositiveInteger) -> %
--R ?+? : (%,%) -> %                      ?-? : (%,%) -> %
--R -? : % -> %                           ?=? : (%,%) -> Boolean
--R 1 : () -> %                           0 : () -> %
--R ?^? : (%,PositiveInteger) -> %        coerce : P -> %
--R coerce : % -> P                       coerce : Integer -> %
--R coerce : % -> OutputForm              hash : % -> SingleInteger
--R latex : % -> String                   one? : % -> Boolean
--R recip : % -> Union(%,"failed")        sample : () -> %
--R zero? : % -> Boolean                  ?~=? : (%,%) -> Boolean
```

```
--R ?*? : (%,R) -> % if R has COMRING
--R ?*? : (R,%) -> % if R has COMRING
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?/? : (%,%) -> Union(%,"failed") if R has FIELD
--R ?^? : (%,NonNegativeInteger) -> %
--R changeWeightLevel : NonNegativeInteger -> Void
--R characteristic : () -> NonNegativeInteger
--R coerce : R -> % if R has COMRING
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R
--E 1

)spool
)lisp (bye)
```

———-


— WeightedPolynomials.help —

```
=====================================================================
WeightedPolynomials examples
=====================================================================

See Also:
o )show WeightedPolynomials
```

———-

24.1.1 WeightedPolynomials (WP)



Exports:

0	1	changeWeightLevel	characteristic
coerce	hash	latex	one?
recip	sample	subtractIfCan	zero?
?~=?	?*?	?**?	?/?
?^?	?*?	?**?	?+?
?-?	-?	?=?	

— domain WP WeightedPolynomials —

```
)abbrev domain WP WeightedPolynomials
++ Author: James Davenport
++ Date Created:  17 April 1992
++ Date Last Updated: 12 July 1992
++ Basic Functions: Ring, changeWeightLevel
++ Related Constructors: PolynomialRing
++ Also See: OrdinaryWeightedPolynomials
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain represents truncated weighted polynomials over a general
++ (not necessarily commutative) polynomial type. The variables must be
++ specified, as must the weights.
++ The representation is sparse
++ in the sense that only non-zero terms are represented.

WeightedPolynomials(R:Ring,VarSet: OrderedSet, E:OrderedAbelianMonoidSup,
                          P:PolynomialCategory(R,E,VarSet),
                            vl:List VarSet, wl:List NonNegativeInteger,
                             wtlevel:NonNegativeInteger):
       Ring with
         if R has CommutativeRing then Algebra(R)
         coerce: $ -> P
                 ++ convert back into a "P", ignoring weights
         if R has Field then "/": ($,$) -> Union($,"failed")
                 ++ x/y division (only works if minimum weight
                 ++ of divisor is zero, and if R is a Field)
         coerce: P -> $
                 ++ coerce(p) coerces p into Weighted form,
                 ++ applying weights and ignoring terms
         changeWeightLevel: NonNegativeInteger -> Void
                 ++ changeWeightLevel(n) changes the weight level to
                 ++ the new value given:
                 ++ NB: previously calculated terms are not affected
    ==
  add
   --representations
   Rep  := PolynomialRing(P,NonNegativeInteger)
```

```
p:P
w,x1,x2:$
n:NonNegativeInteger
z:Integer
changeWeightLevel(n) ==
     wtlevel:=n
lookupList:List Record(var:VarSet, weight:NonNegativeInteger)
if #vl ^= #wl then error "incompatible length lists in WeightedPolynomial"
lookupList:=[[v,n] for v in vl for n in wl]
-- local operation
innercoerce:(p,z) -> $
lookup:Varset -> NonNegativeInteger
lookup v ==
   l:=lookupList
   while l ^= [] repeat
     v = l.first.var => return l.first.weight
     l:=l.rest
   0
innercoerce(p,z) ==
   z<0 => 0
   zero? p => 0
   mv:= mainVariable p
   mv case "failed" => monomial(p,0)
   n:=lookup(mv)
   up:=univariate(p,mv)
   ans:$
   ans:=0
   while not zero? up  repeat
     d:=degree up
     f:=n*d
     lcup:=leadingCoefficient up
     up:=up-leadingMonomial up
     mon:=monomial(1,mv,d)
     f<=z =>
         tmp:= innercoerce(lcup,z-f)
         while not zero? tmp repeat
           ans:=ans+ monomial(mon*leadingCoefficient(tmp),degree(tmp)+f)
           tmp:=reductum tmp
   ans
coerce(p):$ == innercoerce(p,wtlevel)
coerce(w):P ==  "+"/[c for c in coefficients w]
coerce(p:$):OutputForm ==
  zero? p => (0$Integer)::OutputForm
  degree p = 0 => leadingCoefficient(p):: OutputForm
  reduce("+",(reverse [paren(c::OutputForm) for c in coefficients p])
              ::List OutputForm)
0 == 0$Rep
1 == 1$Rep
x1 = x2 ==
   -- Note that we must strip out any terms greater than wtlevel
```

```
      while degree x1 > wtlevel repeat
            x1 := reductum x1
      while degree x2 > wtlevel repeat
            x2 := reductum x2
      x1 =$Rep x2
   x1 + x2 == x1 +$Rep x2
   -x1 == -(x1::Rep)
   x1 * x2 ==
     -- Note that this is probably an extremely inefficient definition
     w:=x1 *$Rep x2
     while degree(w) > wtlevel repeat
           w:=reductum w
     w
```

———-

— WP.dotabb —

```
"WP" [color="#88FF44",href="bookvol10.3.pdf#nameddest=WP"]
"PFECAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=PFECAT"]
"WP" -> "PFECAT"
```

———-

24.2 domain WUTSET WuWenTsunTriangularSet

— WuWenTsunTriangularSet.input —

```
)set break resume
)sys rm -f WuWenTsunTriangularSet.output
)spool WuWenTsunTriangularSet.output
)set message test on
)set message auto off
)clear all
--S 1 of 16
R := Integer
--R
--R
--R   (1)  Integer
--R                                                          Type: Domain
--E 1

--S 2 of 16
ls : List Symbol := [x,y,z,t]
```

```
--R
--R
--R   (2)  [x,y,z,t]
--R                                                        Type: List(Symbol)
--E 2

--S 3 of 16
V := OVAR(ls)
--R
--R
--R   (3)  OrderedVariableList([x,y,z,t])
--R                                                              Type: Domain
--E 3

--S 4 of 16
E := IndexedExponents V
--R
--R
--R   (4)  IndexedExponents(OrderedVariableList([x,y,z,t]))
--R                                                              Type: Domain
--E 4

--S 5 of 16
P := NSMP(R, V)
--R
--R
--R   (5)
--R   NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--R                                                              Type: Domain
--E 5

--S 6 of 16
x: P := 'x
--R
--R
--R   (6)  x
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 6

--S 7 of 16
y: P := 'y
--R
--R
--R   (7)  y
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 7

--S 8 of 16
z: P := 'z
--R
```

```
--R
--R   (8)  z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 8

--S 9 of 16
t: P := 't
--R
--R
--R   (9)  t
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 9

--S 10 of 16
T := WUTSET(R,E,V,P)
--R
--R
--R   (10)
--R  WuWenTsunTriangularSet(Integer,IndexedExponents(OrderedVariableList([x,y,z,t]
--R  )),OrderedVariableList([x,y,z,t]),NewSparseMultivariatePolynomial(Integer,Ord
--R  eredVariableList([x,y,z,t])))
--R                                                                  Type: Domain
--E 10

--S 11 of 16
p1 := x ** 31 - x ** 6 - x - y
--R
--R
--R          31    6
--R   (11)  x   - x  - x - y
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 11

--S 12 of 16
p2 := x ** 8  - z
--R
--R
--R          8
--R   (12)  x  - z
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 12

--S 13 of 16
p3 := x ** 10 - t
--R
--R
--R          10
--R   (13)  x   - t
--RType: NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t]))
--E 13
```

```
--S 14 of 16
lp := [p1, p2, p3]
--R
--R
--R           31    6          8      10
--R   (14)  [x   - x  - x - y,x  - z,x   - t]
--RType: List(NewSparseMultivariatePolynomial(Integer,OrderedVariableList([x,y,z,t])))
--E 14

--S 15 of 16
characteristicSet(lp)$T
--R
--R
--R   (15)
--R     5    4  4 2 2     3 4        7     4      6    6    3      3     3     3
--R   {z  - t ,t z y  + 2t z y + (- t  + 2t  - t)z  + t z,(t  - 1)z x - z y - t }
--IType: Union(WuWenTsunTriangularSet(Integer,IndexedExponents(...
--E 15

--S 16 of 16
zeroSetSplit(lp)$T
--R
--R
--R   (16)
--R                 3      5    4  3     3    2
--R   [{t,z,y,x}, {t  - 1,z  - t ,z y + t ,z x  - t},
--R      5    4  4 2 2     3 4        7     4      6    6    3      3     3     3
--R    {z  - t ,t z y  + 2t z y + (- t  + 2t  - t)z  + t z,(t  - 1)z x - z y - t }]
--IType: List(WuWenTsunTriangularSet(Integer,IndexedExponents(...
--E 16
)spool
)lisp (bye)
```

———-

— WuWenTsunTriangularSet.help —

```
====================================================================
WuWenTsunTriangularSet examples
====================================================================

The WuWenTsunTriangularSet domain constructor implements the
characteristic set method of Wu Wen Tsun.  This algorithm computes a
list of triangular sets from a list of polynomials such that the
algebraic variety defined by the given list of polynomials decomposes
into the union of the regular-zero sets of the computed triangular
sets.  The constructor takes four arguments.  The first one, R, is the
coefficient ring of the polynomials; it must belong to the category
```

```
IntegralDomain. The second one, E, is the exponent monoid of the
polynomials; it must belong to the category OrderedAbelianMonoidSup.
The third one, V, is the ordered set of variables; it must belong to
the category OrderedSet.  The last one is the polynomial ring; it must
belong to the category RecursivePolynomialCategory(R,E,V).  The
abbreviation for WuWenTsunTriangularSet is WUTSET.

Let us illustrate the facilities by an example.

Define the coefficient ring.

  R := Integer
    Integer
                                Type: Domain

Define the list of variables,

  ls : List Symbol := [x,y,z,t]
    [x,y,z,t]
                                Type: List Symbol

and make it an ordered set;

  V := OVAR(ls)
    OrderedVariableList [x,y,z,t]
                                Type: Domain

then define the exponent monoid.

  E := IndexedExponents V
    IndexedExponents OrderedVariableList [x,y,z,t]
                                Type: Domain

Define the polynomial ring.

  P := NSMP(R, V)
    NewSparseMultivariatePolynomial(Integer,OrderedVariableList [x,y,z,t])
                                Type: Domain

Let the variables be polynomial.

  x: P := 'x
    x
       Type: NewSparseMultivariatePolynomial(Integer,
               OrderedVariableList [x,y,z,t])

  y: P := 'y
    y
       Type: NewSparseMultivariatePolynomial(Integer,
               OrderedVariableList [x,y,z,t])
```

```
  z: P := 'z
    z
       Type: NewSparseMultivariatePolynomial(Integer,
              OrderedVariableList [x,y,z,t])

  t: P := 't
    t
       Type: NewSparseMultivariatePolynomial(Integer,
              OrderedVariableList [x,y,z,t])
```

Now call the WuWenTsunTriangularSet domain constructor.

```
  T := WUTSET(R,E,V,P)
  WuWenTsunTriangularSet(Integer,IndexedExponents OrderedVariableList [x,y,z,t]
  ,OrderedVariableList [x,y,z,t],NewSparseMultivariatePolynomial(Integer,Ordere
  dVariableList [x,y,z,t]))
                               Type: Domain
```

Define a polynomial system.

```
  p1 := x ** 31 - x ** 6 - x - y
      31    6
     x   - x  - x - y
              Type: NewSparseMultivariatePolynomial(Integer,
                     OrderedVariableList [x,y,z,t])

  p2 := x ** 8  - z
      8
     x  - z
              Type: NewSparseMultivariatePolynomial(Integer,
                     OrderedVariableList [x,y,z,t])

  p3 := x ** 10 - t
      10
     x   - t
              Type: NewSparseMultivariatePolynomial(Integer,
                     OrderedVariableList [x,y,z,t])

  lp := [p1, p2, p3]
      31    6          8      10
    [x   - x  - x - y,x  - z,x   - t]
         Type: List NewSparseMultivariatePolynomial(Integer,
                     OrderedVariableList [x,y,z,t])
```

Compute a characteristic set of the system.

```
  characteristicSet(lp)$T
     5    4  4 2 2     3 4        7     4      6    6    3      3     3     3
   {z  - t ,t z y  + 2t z y + (- t  + 2t  - t)z  + t z,(t  - 1)z x - z y - t }
```

```
           Type: Union(WuWenTsunTriangularSet(Integer,
                         IndexedExponents OrderedVariableList [x,y,z,t],
                         OrderedVariableList [x,y,z,t],
                         NewSparseMultivariatePolynomial(Integer,
                           OrderedVariableList [x,y,z,t])),...)
```

Solve the system.

```
  zeroSetSplit(lp)$T
              3      5    4  3     3    2
  [{t,z,y,x}, {t  - 1,z  - t ,z y + t ,z x  - t},
     5    4  4 2 2     3 4        7     4      6    6    3      3     3     3
   {z  - t ,t z y  + 2t z y + (- t  + 2t  - t)z  + t z,(t  - 1)z x - z y - t }]
        Type: List WuWenTsunTriangularSet(Integer,
                     IndexedExponents OrderedVariableList [x,y,z,t],
                     OrderedVariableList [x,y,z,t],
                     NewSparseMultivariatePolynomial(Integer,
                        OrderedVariableList [x,y,z,t]))
```


The RegularTriangularSet and SquareFreeRegularTriangularSet domain constructors, the LazardSetSolvingPackage package constructors as well as, SquareFreeRegularTriangularSet and ZeroDimensionalSolvePackage package constructors also provide operations to compute triangular decompositions of algebraic varieties. These five constructor use a special kind of characteristic sets, called regular triangular sets. These special characteristic sets have better properties than the general ones. Regular triangular sets and their related concepts are presented in the paper "On the Theories of Triangular sets" By P. Aubry, D. Lazard and M. Moreno Maza (to appear in the Journal of Symbolic Computation). The decomposition algorithm (due to the third author) available in the four above constructors provide generally better timings than the characteristic set method. In fact, the WUTSET constructor remains interesting for the purpose of manipulating characteristic sets whereas the other constructors are more convenient for solving polynomial systems.

Note that the way of understanding triangular decompositions is detailed in the example of the RegularTriangularSet constructor.

See Also:
o)help RecursivePolynomialCategory
o)help RegularTriangularSet
o)help SquareFreeRegularTriangularSet
o)help LazardSetSolvingPackage
o)help ZeroDimensionalSolvePackage
o)show WuWenTsunTriangularSet

———————-

24.2.1 WuWenTsunTriangularSet (WUTSET)



See

⇒ “GeneralTriangularSet” (GTSET) 8.6.1 on page 1053

Exports:

algebraic?	algebraicVariables
any?	autoReduced?
basicSet	characteristicSerie
characteristicSet	coerce
coHeight	collect
collectQuasiMonic	collectUnder
collectUpper	construct
convert	copy
count	degree
empty	empty?
eq?	eval
every?	extend
extendIfCan	find
first	hash
headReduce	headReduced?
headRemainder	infRittWu?
initiallyReduce	initiallyReduced?
initials	last
latex	less?
mainVariable?	mainVariables
map	map!
medialSet	member?
members	more?
mvar	normalized?
normalized?	parts
quasiComponent	reduce
reduceByQuasiMonic	reduced?
remainder	remove
removeDuplicates	removeZero
rest	retract
retractIfCan	rewriteIdealWithHeadRemainder
rewriteIdealWithRemainder	rewriteSetWithReduction
roughBase?	roughEqualIdeals?
roughSubIdeal?	roughUnitIdeal?
sample	select
size?	sort
stronglyReduce	stronglyReduced?
triangular?	trivialIdeal?
variables	zeroSetSplit
zeroSetSplitIntoTriangularSystems	#?
?=?	?~=?

— domain WUTSET WuWenTsunTriangularSet —

```
)abbrev domain WUTSET WuWenTsunTriangularSet
```

```
++ Author: Marc Moreno Maza (marc@nag.co.uk)
++ Date Created: 11/18/1995
++ Date Last Updated: 12/15/1998
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References :
++ [1] W. T. WU "A Zero Structure Theorem for polynomial equations solving"
++      MM Research Preprints, 1987.
++ [2] D. M. WANG "An implementation of the characteristic set method in Maple"
++      Proc. DISCO'92. Bath, England.
++ Description:
++ A domain constructor of the category \axiomType{GeneralTriangularSet}.
++ The only requirement for a list of polynomials to be a member of such
++ a domain is the following: no polynomial is constant and two distinct
++ polynomials have distinct main variables. Such a triangular set may
++ not be auto-reduced or consistent. The construct operation
++ does not check the previous requirement. Triangular sets are stored
++ as sorted lists w.r.t. the main variables of their members.
++ Furthermore, this domain exports operations dealing with the
++ characteristic set method of Wu Wen Tsun and some optimizations
++ mainly proposed by Dong Ming Wang.

WuWenTsunTriangularSet(R,E,V,P) : Exports == Implementation where

  R : IntegralDomain
  E : OrderedAbelianMonoidSup
  V : OrderedSet
  P : RecursivePolynomialCategory(R,E,V)
  N ==> NonNegativeInteger
  Z ==> Integer
  B ==> Boolean
  LP ==> List P
  A ==> FiniteEdge P
  H ==> FiniteSimpleHypergraph P
  GPS ==> GeneralPolynomialSet(R,E,V,P)
  RBT ==> Record(bas:$,top:LP)
  RUL ==> Record(chs:Union($,"failed"),rfs:LP)
  pa ==> PolynomialSetUtilitiesPackage(R,E,V,P)
  NLpT ==> SplittingNode(LP,$)
  ALpT ==> SplittingTree(LP,$)
  O ==> OutputForm
  OP ==> OutputPackage

  Exports ==  TriangularSetCategory(R,E,V,P) with

     medialSet : (LP,((P,P)->B),((P,P)->P)) -> Union($,"failed")
        ++ \axiom{medialSet(ps,redOp?,redOp)} returns \axiom{bs} a basic set
```

```
      ++ (in Wu Wen Tsun sense w.r.t the reduction-test \axiom{redOp?})
      ++ of some set generating the same ideal as \axiom{ps} (with
      ++ rank not higher than  any basic set of \axiom{ps}), if no non-zero
      ++ constant polynomials appear during the computations, else
      ++ \axiom{"failed"} is returned. In the former case, \axiom{bs} has to be
      ++ understood as a candidate for being a characteristic set of \axiom{ps}.
      ++ In the original algorithm, \axiom{bs} is simply a basic set of \axiom{ps}.
    medialSet: LP -> Union($,"failed")
      ++ \axiom{medial(ps)} returns the same as
      ++ \axiom{medialSet(ps,initiallyReduced?,initiallyReduce)}.
    characteristicSet : (LP,((P,P)->B),((P,P)->P)) -> Union($,"failed")
      ++ \axiom{characteristicSet(ps,redOp?,redOp)} returns a non-contradictory
      ++ characteristic set of \axiom{ps} in Wu Wen Tsun sense w.r.t the
      ++ reduction-test \axiom{redOp?} (using \axiom{redOp} to reduce
      ++ polynomials w.r.t a \axiom{redOp?} basic set), if no
      ++ non-zero constant polynomial appear during those reductions,
      ++ else \axiom{"failed"} is returned.
      ++ The operations \axiom{redOp} and \axiom{redOp?} must satisfy
      ++ the following conditions: \axiom{redOp?(redOp(p,q),q)} holds
      ++ for every polynomials \axiom{p,q} and there exists an integer
      ++ \axiom{e} and a polynomial \axiom{f} such that we have
      ++ \axiom{init(q)^e*p = f*q + redOp(p,q)}.
    characteristicSet: LP -> Union($,"failed")
      ++ \axiom{characteristicSet(ps)} returns the same as
      ++ \axiom{characteristicSet(ps,initiallyReduced?,initiallyReduce)}.
    characteristicSerie  : (LP,((P,P)->B),((P,P)->P)) -> List $
      ++ \axiom{characteristicSerie(ps,redOp?,redOp)} returns a list \axiom{lts}
      ++ of triangular sets such that the zero set of \axiom{ps} is the
      ++ union of the regular zero sets of the members of \axiom{lts}.
      ++ This is made by the Ritt and Wu Wen Tsun process applying
      ++ the operation \axiom{characteristicSet(ps,redOp?,redOp)}
      ++ to compute characteristic sets in Wu Wen Tsun sense.
    characteristicSerie: LP ->  List $
      ++ \axiom{characteristicSerie(ps)} returns the same as
      ++ \axiom{characteristicSerie(ps,initiallyReduced?,initiallyReduce)}.

  Implementation == GeneralTriangularSet(R,E,V,P) add

    removeSquares: $ -> Union($,"failed")

    Rep ==> LP

    rep(s:$):Rep == s pretend Rep
    per(l:Rep):$ == l pretend $

    removeAssociates (lp:LP):LP ==
      removeDuplicates [primPartElseUnitCanonical(p) for p in lp]

    medialSetWithTrace (ps:LP,redOp?:((P,P)->B),redOp:((P,P)->P)):Union(RBT,"failed") ==
      qs := rewriteIdealWithQuasiMonicGenerators(ps,redOp?,redOp)$pa
```

```
      contradiction : B := any?(ground?,ps)
      contradiction => "failed"::Union(RBT,"failed")
      rs : LP := qs
      bs : $
      while (not empty? rs) and (not contradiction) repeat
        rec := basicSet(rs,redOp?)
        contradiction := (rec case "failed")@B
        if not contradiction
          then
            bs := (rec::RBT).bas
            rs := (rec::RBT).top
            rs :=  rewriteIdealWithRemainder(rs,bs)
--            contradiction := ((not empty? rs) and (one? first(rs)))
            contradiction := ((not empty? rs) and (first(rs) = 1))
            if (not empty? rs) and (not contradiction)
              then
                rs := rewriteSetWithReduction(rs,bs,redOp,redOp?)
--                contradiction := ((not empty? rs) and (one? first(rs)))
                contradiction := ((not empty? rs) and (first(rs) = 1))
        if (not empty? rs) and (not contradiction)
          then
            rs := removeDuplicates concat(rs,members(bs))
            rs := rewriteIdealWithQuasiMonicGenerators(rs,redOp?,redOp)$pa
--            contradiction := ((not empty? rs) and (one? first(rs)))
            contradiction := ((not empty? rs) and (first(rs) = 1))
      contradiction => "failed"::Union(RBT,"failed")
      ([bs,qs]$RBT)::Union(RBT,"failed")

    medialSet(ps:LP,redOp?:((P,P)->B),redOp:((P,P)->P)) ==
      foo: Union(RBT,"failed") := medialSetWithTrace(ps,redOp?,redOp)
      (foo case "failed") => "failed" :: Union($,"failed")
      ((foo::RBT).bas) :: Union($,"failed")

    medialSet(ps:LP) == medialSet(ps,initiallyReduced?,initiallyReduce)

    characteristicSetUsingTrace(ps:LP,redOp?:((P,P)->B),redOp:((P,P)->P)):Union($,"failed") ==
      ps := removeAssociates ps
      ps := remove(zero?,ps)
      contradiction : B := any?(ground?,ps)
      contradiction => "failed"::Union($,"failed")
      rs : LP := ps
      qs : LP := ps
      ms : $
      while (not empty? rs) and (not contradiction) repeat
        rec := medialSetWithTrace (qs,redOp?,redOp)
        contradiction := (rec case "failed")@B
        if not contradiction
          then
            ms := (rec::RBT).bas
            qs := (rec::RBT).top
```

```
            qs := rewriteIdealWithRemainder(qs,ms)
--            contradiction := ((not empty? qs) and (one? first(qs)))
            contradiction := ((not empty? qs) and (first(qs) = 1))
            if not contradiction
              then
                rs :=  rewriteSetWithReduction(qs,ms,lazyPrem,reduced?)
--                contradiction := ((not empty? rs) and (one? first(rs)))
                contradiction := ((not empty? rs) and (first(rs) = 1))
            if  (not contradiction) and (not empty? rs)
              then
                qs := removeDuplicates(concat(rs,concat(members(ms),qs)))
      contradiction => "failed"::Union($,"failed")
      ms::Union($,"failed")

    characteristicSet(ps:LP,redOp?:((P,P)->B),redOp:((P,P)->P)) ==
      characteristicSetUsingTrace(ps,redOp?,redOp)

    characteristicSet(ps:LP) == characteristicSet(ps,initiallyReduced?,initiallyReduce)

    characteristicSerie(ps:LP,redOp?:((P,P)->B),redOp:((P,P)->P)) ==
      a := [[ps,empty()$$]$NLpT]$ALpT
      while ((esl := extractSplittingLeaf(a)) case ALpT) repeat
         ps := value(value(esl::ALpT)$ALpT)$NLpT
         charSet? := characteristicSetUsingTrace(ps,redOp?,redOp)
         if not (charSet? case $)
            then
               setvalue!(esl::ALpT,[nil()$LP,empty()$$,true]$NLpT)
               updateStatus!(a)
            else
               cs := (charSet?)::$
               lics := initials(cs)
               lics := removeRedundantFactors(lics)$pa
               lics := sort(infRittWu?,lics)
               if empty? lics
                  then
                     setvalue!(esl::ALpT,[ps,cs,true]$NLpT)
                     updateStatus!(a)
                  else
                     ln : List NLpT := [[nil()$LP,cs,true]$NLpT]
                     while not empty? lics repeat
                        newps := cons(first(lics),concat(cs::LP,ps))
                        lics := rest lics
                        newps := removeDuplicates newps
                        newps := sort(infRittWu?,newps)
                        ln := cons([newps,empty()$$,false]$NLpT,ln)
                     splitNodeOf!(esl::ALpT,a,ln)
      remove(empty()$$,conditions(a))

    characteristicSerie(ps:LP) ==  characteristicSerie (ps,initiallyReduced?,initiallyReduce)
```

```
    if R has GcdDomain
    then

      removeSquares (ts:$):Union($,"failed") ==
        empty?(ts)$$ => ts::Union($,"failed")
        p := (first ts)::P
        rsts : Union($,"failed")
        rsts := removeSquares((rest ts)::$)
        not(rsts case $) => "failed"::Union($,"failed")
        newts := rsts::$
        empty? newts =>
          p := squareFreePart(p)
          (per([primitivePart(p)]$LP))::Union($,"failed")
        zero? initiallyReduce(init(p),newts) => "failed"::Union($,"failed")
        p := primitivePart(removeZero(p,newts))
        ground? p => "failed"::Union($,"failed")
        not (mvar(newts) < mvar(p)) => "failed"::Union($,"failed")
        p := squareFreePart(p)
        (per(cons(unitCanonical(p),rep(newts))))::Union($,"failed")

      zeroSetSplit lp ==
        lts : List $ := characteristicSerie(lp,initiallyReduced?,initiallyReduce)
        lts := removeDuplicates(lts)$(List $)
        newlts : List $ := []
        while not empty? lts repeat
          ts := first lts
          lts := rest lts
          iic := removeSquares(ts)
          if iic case $
            then
              newlts := cons(iic::$,newlts)
        newlts := removeDuplicates(newlts)$(List $)
        sort(infRittWu?, newlts)

    else

      zeroSetSplit lp ==
        lts : List $ := characteristicSerie(lp,initiallyReduced?,initiallyReduce)
        sort(infRittWu?, removeDuplicates lts)
```

———-

— WUTSET.dotabb —

```
"WUTSET" [color="#88FF44",href="bookvol10.3.pdf#nameddest=WUTSET"]
"RPOLCAT" [color="#4488FF",href="bookvol10.2.pdf#nameddest=RPOLCAT"]
"WUTSET" -> "RPOLCAT"
```

———-

Chapter 25

Chapter X

25.1 domain XDPOLY XDistributedPolynomial

Polynomial arithmetic with non-commutative variables has been improved by a contribution of Michel Petitot (University of Lille I, France). The domain constructor **XDistributedPolynomial** provide a distributed representation for these polynomials. It is the non-commutative equivalent for the **DistributedMultivariatePolynomial** constructor.

— XDistributedPolynomial.input —

```
)set break resume
)sys rm -f XDistributedPolynomial.output
)spool XDistributedPolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show XDistributedPolynomial
--R
--R XDistributedPolynomial(vl: OrderedSet,R: Ring)  is a domain constructor
--R Abbreviation for XDistributedPolynomial is XDPOLY
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for XDPOLY
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (%,%) -> %                      ?*? : (vl,%) -> %
--R ?*? : (%,R) -> %                      ?*? : (R,%) -> %
--R ?*? : (Integer,%) -> %                ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %       ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                      -? : % -> %
--R ?=? : (%,%) -> Boolean                1 : () -> %
```

```
--R 0 : () -> %                          ?^? : (%,PositiveInteger) -> %
--R coef : (%,%) -> R                    coefficients : % -> List(R)
--R coerce : Integer -> %                coerce : R -> %
--R coerce : vl -> %                     coerce : % -> OutputForm
--R constant : % -> R                    constant? : % -> Boolean
--R degree : % -> NonNegativeInteger     hash : % -> SingleInteger
--R latex : % -> String                  leadingCoefficient : % -> R
--R lquo : (%,vl) -> %                   lquo : (%,%) -> %
--R map : ((R -> R),%) -> %              mirror : % -> %
--R monomial? : % -> Boolean             monomials : % -> List(%)
--R one? : % -> Boolean                  quasiRegular : % -> %
--R quasiRegular? : % -> Boolean         recip : % -> Union(%,"failed")
--R reductum : % -> %                    rquo : (%,vl) -> %
--R rquo : (%,%) -> %                    sample : () -> %
--R varList : % -> List(vl)              zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (R,OrderedFreeMonoid(vl)) -> %
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coef : (%,OrderedFreeMonoid(vl)) -> R
--R coefficient : (%,OrderedFreeMonoid(vl)) -> R
--R coerce : OrderedFreeMonoid(vl) -> %
--R leadingMonomial : % -> OrderedFreeMonoid(vl)
--R leadingTerm : % -> Record(k: OrderedFreeMonoid(vl),c: R)
--R listOfTerms : % -> List(Record(k: OrderedFreeMonoid(vl),c: R))
--R lquo : (%,OrderedFreeMonoid(vl)) -> %
--R maxdeg : % -> OrderedFreeMonoid(vl)
--R mindeg : % -> OrderedFreeMonoid(vl)
--R mindegTerm : % -> Record(k: OrderedFreeMonoid(vl),c: R)
--R monom : (OrderedFreeMonoid(vl),R) -> %
--R numberOfMonomials : % -> NonNegativeInteger
--R retract : % -> OrderedFreeMonoid(vl)
--R retractIfCan : % -> Union(OrderedFreeMonoid(vl),"failed")
--R rquo : (%,OrderedFreeMonoid(vl)) -> %
--R sh : (%,%) -> % if R has COMRING
--R sh : (%,NonNegativeInteger) -> % if R has COMRING
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R trunc : (%,NonNegativeInteger) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-


— XDistributedPolynomial.help —

```
=======================================================================
XDistributedPolynomial examples
=======================================================================

See Also:
o )show XDistributedPolynomial
```

———-

25.1.1 XDistributedPolynomial (XDPOLY)



Exports:

0	1	characteristic	coef
coefficient	coefficients	coerce	constant
constant?	degree	hash	latex
leadingCoefficient	listOfTerms	leadingMonomial	leadingTerm
lquo	map	mirror	monomial?
monomials	maxdeg	mindeg	mindegTerm
monom	numberOfMonomials	one?	quasiRegular
quasiRegular?	recip	reductum	retract
retractIfCan	rquo	sample	sh
subtractIfCan	trunc	varList	zero?
?*?	?**?	?+?	?-?
-?	?=?	?^?	?~=?

— domain XDPOLY XDistributedPolynomial —

```
)abbrev domain XDPOLY XDistributedPolynomial
++ Author: Michel Petitot petitot@lifl.fr
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
++ Related Constructors:
```

```
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type supports distributed multivariate polynomials
++ whose variables do not commute.
++ The coefficient ring may be non-commutative too.
++ However, coefficients and variables commute.

XDistributedPolynomial(vl:OrderedSet,R:Ring): XDPcat == XDPdef where

  WORD ==> OrderedFreeMonoid(vl)
  I    ==> Integer
  NNI  ==> NonNegativeInteger
  TERM ==> Record(k:WORD, c:R)

  XDPcat == Join(FreeModuleCat(R, WORD), XPolynomialsCat(vl,R))

  XDPdef == XPolynomialRing(R,WORD) add

       import( WORD, TERM)

    -- Representation
       Rep  :=  List TERM

    -- local functions
       shw: (WORD , WORD) -> %    -- shuffle de 2 mots

    -- definitions

       mindegTerm p == last(p)$Rep

       if R has CommutativeRing then
         sh(p:%, n:NNI):% ==
            n=0 => 1
            n=1 => p
            n1: NNI := (n-$I 1)::NNI
            sh(p, sh(p,n1))


         sh(p1:%, p2:%) ==
           p:% := 0
           for t1 in p1 repeat
             for t2 in p2 repeat
                p := p + (t1.c * t2.c) * shw(t1.k,t2.k)
           p

       coerce(v: vl):% == coerce(v::WORD)
       v:vl * p:% ==
```

```
    [[v * t.k , t.c]$TERM for t in p]

  mirror p ==
    null p => p
    monom(mirror$WORD leadingMonomial p, leadingCoefficient p) + _
          mirror reductum p

  degree(p) == length(maxdeg(p))$WORD

  trunc(p, n) ==
    p = 0 => p
    degree(p) > n => trunc( reductum p , n)
    p

  varList p ==
    constant? p => []
    le : List vl := "setUnion"/[varList(t.k) for t in p]
    sort_!(le)

  rquo(p:% , w: WORD) ==
    [[r::WORD,t.c]$TERM for t in p | not (r:= rquo(t.k,w)) case "failed" ]
  lquo(p:% , w: WORD) ==
    [[r::WORD,t.c]$TERM for t in p | not (r:= lquo(t.k,w)) case "failed" ]
  rquo(p:% , v: vl) ==
    [[r::WORD,t.c]$TERM for t in p | not (r:= rquo(t.k,v)) case "failed" ]
  lquo(p:% , v: vl) ==
    [[r::WORD,t.c]$TERM for t in p | not (r:= lquo(t.k,v)) case "failed" ]

  shw(w1,w2) ==
    w1 = 1$WORD => w2::%
    w2 = 1$WORD => w1::%
    x: vl := first w1 ; y: vl := first w2
    x * shw(rest w1,w2) + y * shw(w1,rest w2)

  lquo(p:%,q:%):% ==
    +/  [r * t.c for t in q | (r := lquo(p,t.k)) ^= 0]

  rquo(p:%,q:%):% ==
    +/  [r * t.c for t in q | (r := rquo(p,t.k)) ^= 0]

  coef(p:%,q:%):R ==
    p = 0 => 0$R
    q = 0 => 0$R
    p.first.k > q.first.k => coef(p.rest,q)
    p.first.k < q.first.k => coef(p,q.rest)
    return p.first.c * q.first.c + coef(p.rest,q.rest)
```

———-

— XDPOLY.dotabb —

```
"XDPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=XDPOLY"]
"XPOLYC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=XPOLYC"]
"XDPOLY" -> "XPOLYC"
```

———-

25.2 domain XPBWPOLY XPBWPolynomial

— XPBWPolynomial.input —

```
)set break resume
)sys rm -f XPBWPolynomial.output
)spool XPBWPolynomial.output
)set message test on
)set message auto off
)clear all
--S 1 of 39
a:Symbol := 'a
--R
--R
--R   (1)  a
--R                                                          Type: Symbol
--E 1

--S 2 of 39
b:Symbol := 'b
--R
--R
--R   (2)  b
--R                                                          Type: Symbol
--E 2

--S 3 of 39
RN := Fraction(Integer)
--R
--R
--R   (3)  Fraction(Integer)
--R                                                          Type: Domain
--E 3

--S 4 of 39
word := OrderedFreeMonoid Symbol
--R
```

```
--R
--R   (4)  OrderedFreeMonoid(Symbol)
--R                                                                Type: Domain
--E 4

--S 5 of 39
lword := LyndonWord(Symbol)
--R
--R
--R   (5)  LyndonWord(Symbol)
--R                                                                Type: Domain
--E 5

--S 6 of 39
base := PoincareBirkhoffWittLyndonBasis Symbol
--R
--R
--R   (6)  PoincareBirkhoffWittLyndonBasis(Symbol)
--R                                                                Type: Domain
--E 6

--S 7 of 39
dpoly := XDistributedPolynomial(Symbol, RN)
--R
--R
--R   (7)  XDistributedPolynomial(Symbol,Fraction(Integer))
--R                                                                Type: Domain
--E 7

--S 8 of 39
rpoly := XRecursivePolynomial(Symbol, RN)
--R
--R
--R   (8)  XRecursivePolynomial(Symbol,Fraction(Integer))
--R                                                                Type: Domain
--E 8

--S 9 of 39
lpoly := LiePolynomial(Symbol, RN)
--R
--R
--R   (9)  LiePolynomial(Symbol,Fraction(Integer))
--R                                                                Type: Domain
--E 9

--S 10 of 39
poly  := XPBWPolynomial(Symbol, RN)
--R
--R
--R   (10)  XPBWPolynomial(Symbol,Fraction(Integer))
```

```
--R                                                                Type: Domain
--E 10

--S 11 of 39
liste : List lword := LyndonWordsList([a,b], 6)
--R
--R
--R   (11)
--R                      2        2     3      2 2       3     4      3 2
--R   [[a], [b], [a b], [a b], [a b ], [a b], [a b ], [a b ], [a b], [a b ],
--R      2          2 3           2       4     5      4 2     3          3 3
--R    [a b a b], [a b ], [a b a b ], [a b ], [a b], [a b ], [a b a b], [a b ],
--R      2     2     2 2        2 4           3       5
--R    [a b a b ], [a b a b], [a b ], [a b a b ], [a b ]]
--R                                              Type: List(LyndonWord(Symbol))
--E 11

--S 12 of 39
0$poly
--R
--R
--R   (12)  0
--R                              Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 12

--S 13 of 39
1$poly
--R
--R
--R   (13)  1
--R                              Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 13

--S 14 of 39
p : poly := a
--R
--R
--R   (14)  [a]
--R                              Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 14

--S 15 of 39
q : poly := b
--R
--R
--R   (15)  [b]
--R                              Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 15

--S 16 of 39
```

```
pq: poly := p*q
--R
--R
--R   (16)  [a b] + [b][a]
--R                                Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 16

--S 17 of 39
pq :: dpoly
--R
--R
--R   (17)  a b
--R                       Type: XDistributedPolynomial(Symbol,Fraction(Integer))
--E 17

--S 18 of 39
mirror pq
--R
--R
--R   (18)  [b][a]
--R                                Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 18

--S 19 of 39
listOfTerms pq
--R
--R
--R   (19)  [[k= [b][a],c= 1],[k= [a b],c= 1]]
--RType: List(Record(k: PoincareBirkhoffWittLyndonBasis(Symbol),c: Fraction(Integer)))
--E 19

--S 20 of 39
reductum pq
--R
--R
--R   (20)  [a b]
--R                                Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 20

--S 21 of 39
leadingMonomial pq
--R
--R
--R   (21)  [b][a]
--R                                 Type: PoincareBirkhoffWittLyndonBasis(Symbol)
--E 21

--S 22 of 39
coefficients pq
--R
```

```
--R
--R   (22)  [1,1]
--R                                                  Type: List(Fraction(Integer))
--E 22

--S 23 of 39
leadingTerm pq
--R
--R
--R   (23)  [k= [b][a],c= 1]
--RType: Record(k: PoincareBirkhoffWittLyndonBasis(Symbol),c: Fraction(Integer))
--E 23

--S 24 of 39
degree pq
--R
--R
--R   (24)  2
--R                                                     Type: PositiveInteger
--E 24

--S 25 of 39
pq4:=exp(pq,4)
--R
--R
--R   (25)
--R                           1              1     2       1      2
--R     1 + [a b] + [b][a] + - [a b][a b] + - [a b ][a] + - [b][a b]
--R                           2              2             2
--R   +
--R     3               1
--R     - [b][a b][a] + - [b][b][a][a]
--R     2               2
--R                               Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 25

--S 26 of 39
log(pq4,4) - pq
--R
--R
--R   (26)  0
--R                               Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 26

--S 27 of 39
lp1 :lpoly := LiePoly liste.10
--R
--R
--R           3 2
--R   (27)  [a b ]
```

```
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 27

--S 28 of 39
lp2 :lpoly := LiePoly liste.11
--R
--R
--R           2
--R   (28)  [a b a b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 28

--S 29 of 39
lp :lpoly := [lp1, lp2]
--R
--R
--R           3 2 2
--R   (29)  [a b a b a b]
--R                                Type: LiePolynomial(Symbol,Fraction(Integer))
--E 29

--S 30 of 39
lpd1: dpoly := lp1
--R
--R
--R          3 2     2         2 2                    2 2           2    2 3
--R   (30)  a b  - 2a b a b - a b a + 4a b a b a - a b a  - 2b a b a  + b a
--R                      Type: XDistributedPolynomial(Symbol,Fraction(Integer))
--E 30

--S 31 of 39
lpd2: dpoly := lp2
--R
--R
--R   (31)
--R      2         2 2          2                    2 2       3        2
--R     a b a b - a b a - 3a b a b + 4a b a b a - a b a  + 2b a b - 3b a b a
--R   +
--R            2
--R     b a b a
--R                      Type: XDistributedPolynomial(Symbol,Fraction(Integer))
--E 31

--S 32 of 39
lpd : dpoly := lpd1 * lpd2 - lpd2 * lpd1
--R
--R
--R   (32)
--R      3 2 2         3 2 2 2      3 2     2      3 2            3 2   2 2
--R     a b a b a b - a b a b a - 3a b a b a b + 4a b a b a b a - a b a b a
```

```
--R   +
--R       3 3 3      3 3 2       3 3     2    2       3 2     2       2 2
--R     2a b a b - 3a b a b a + a b a b a  - a b a b a b  + 3a b a b a b a
--R   +
--R       2          2       2                   2         2 2     2     2 3
--R     6a b a b a b a b - 12a b a b a b a b a + 3a b a b a b a  - 4a b a b a b
--R   +
--R       2     2 2       2     3 3    2 2 4 2     2 2 3          2 2 2   2
--R     6a b a b a b a - a b a b a  + a b a b  - 3a b a b a b + 3a b a b a b
--R   +
--R         2 2     3      2 2     2        2 2         2    2 2   2 3
--R     - 2a b a b a b + 3a b a b a b a - 3a b a b a b a  + a b a b a
--R   +
--R           2   3 2         2   2             2   2 2           2
--R     3a b a b a b  - 6a b a b a b a b - 3a b a b a b a + 12a b a b a b a b a
--R   +
--R            2     2 2         2 2     2         2 3 3            4 2
--R     - 3a b a b a b a  - 6a b a b a b a  + 3a b a b a  - 4a b a b a b
--R   +
--R               3                  2   2                 3
--R     12a b a b a b a b - 12a b a b a b a b + 8a b a b a b a b
--R   +
--R                    2                         2              2 3      2 5 2
--R     - 12a b a b a b a b a + 12a b a b a b a b a  - 4a b a b a b a  + a b a b
--R   +
--R           2 4           2 3   2        2 2   3        2 2   2
--R     - 3a b a b a b + 3a b a b a b - 2a b a b a b + 3a b a b a b a
--R   +
--R           2 2       2      2 2 2 3       3   3 2       3   2
--R     - 3a b a b a b a  + a b a b a  - 2b a b a b  + 4b a b a b a b
--R   +
--R         3   2 2        3                 3     2 2       3 2     2       3 3 3
--R     2b a b a b a - 8b a b a b a b a + 2b a b a b a  + 4b a b a b a  - 2b a b a
--R   +
--R         2   4 2       2   3           2   3 2         2   2
--R     3b a b a b  - 6b a b a b a b - 3b a b a b a + 12b a b a b a b a
--R   +
--R           2   2 2 2       2           2       2     2 3          5 2
--R     - 3b a b a b a  - 6b a b a b a b a  + 3b a b a b a  - b a b a b
--R   +
--R             4 2           3   2            3                 3 2 2
--R     3b a b a b a + 6b a b a b a b - 12b a b a b a b a + 3b a b a b a
--R   +
--R               2   3           2   2            2 2 3    2 5         2 5 2
--R     - 4b a b a b a b + 6b a b a b a b a - b a b a b a  + b a b a b - b a b a
--R   +
--R         2 4   2      2 4           2 4 2 2     2 3   3      2 3   2
--R     - 3b a b a b + 4b a b a b a - b a b a  + 2b a b a b - 3b a b a b a
--R   +
--R      2 3       2
```

```
--R     b a b a b a
--R                        Type: XDistributedPolynomial(Symbol,Fraction(Integer))
--E 32

--S 33 of 39
lp :: dpoly - lpd
--R
--R
--R   (33)  0
--R                        Type: XDistributedPolynomial(Symbol,Fraction(Integer))
--E 33

--S 34 of 39
p := 3 * lp
--R
--R
--R            3 2 2
--R   (34)  3[a b a b a b]
--R                                Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 34

--S 35 of 39
q := lp1
--R
--R
--R           3 2
--R   (35)  [a b ]
--R                                Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 35

--S 36 of 39
pq:= p * q
--R
--R
--R            3 2 2        3 2
--R   (36)  3[a b a b a b][a b ]
--R                                Type: XPBWPolynomial(Symbol,Fraction(Integer))
--E 36

--S 37 of 39
pr:rpoly := p :: rpoly
--R
--R
--R   (37)
--R       a
--R    *
--R           a
--R        *
--R               a b b
--R            *
```

```
--R                a(a b(a b 3 + b a(- 3)) + b(a(a b(- 9) + b a 12) + b a a(- 3)))
--R              +
--R                b a(a(a b 6 + b a(- 9)) + b a a 3)
--R          +
--R              b
--R           *
--R                  a b
--R               *
--R                     a
--R                  *
--R                       a(a b b(- 3) + b b a 9)
--R                     +
--R                       b(a(a b 18 + b a(- 36)) + b a a 9)
--R                  +
--R                    b(a a(a b(- 12) + b a 18) + b a a a(- 3))
--R              +
--R                  b a
--R               *
--R                    a(a(a b b 3 + b a b(- 9)) + b a a b 9)
--R                  +
--R                    b(a(a(a b(- 6) + b a 9) + b a a(- 9)) + b a a a 3)
--R       +
--R           b
--R        *
--R               a
--R            *
--R                  a b
--R               *
--R                     a
--R                  *
--R                       a(a b b 9 + b(a b(- 18) + b a(- 9)))
--R                     +
--R                       b(a b a 36 + b a a(- 9))
--R                  +
--R                    b(a b a a(- 18) + b a a a 9)
--R              +
--R                  b a
--R               *
--R                    a(a(a b b(- 12) + b a b 36) + b a a b(- 36))
--R                  +
--R                    b(a(a(a b 24 + b a(- 36)) + b a a 36) + b a a a(- 12))
--R          +
--R              b a a
--R           *
--R                a(a(a b b 3 + b a b(- 9)) + b a a b 9)
--R              +
--R                b(a(a(a b(- 6) + b a 9) + b a a(- 9)) + b a a a 3)
--R   +
--R       b
--R    *
```

```
--R           a
--R        *
--R               a
--R            *
--R                   a b
--R                *
--R                       a
--R                    *
--R                         a(a b b(- 6) + b(a b 12 + b a 6))
--R                       +
--R                         b(a b a(- 24) + b a a 6)
--R                    +
--R                      b(a b a a 12 + b a a a(- 6))
--R               +
--R                   b a
--R                *
--R                       a
--R                    *
--R                         a(a b b 9 + b(a b(- 18) + b a(- 9)))
--R                       +
--R                         b(a b a 36 + b a a(- 9))
--R                    +
--R                      b(a b a a(- 18) + b a a a 9)
--R           +
--R               b a a
--R            *
--R                 a(a(a b b(- 3) + b b a 9) + b(a(a b 18 + b a(- 36)) + b a a 9))
--R               +
--R                 b(a a(a b(- 12) + b a 18) + b a a a(- 3))
--R       +
--R           b a a a
--R        *
--R             a(a b(a b 3 + b a(- 3)) + b(a(a b(- 9) + b a 12) + b a a(- 3)))
--R           +
--R             b a(a(a b 6 + b a(- 9)) + b a a 3)
--R                                Type: XRecursivePolynomial(Symbol,Fraction(Integer))
--E 37

--S 38 of 39
qr:rpoly := q :: rpoly
--R
--R
--R   (38)
--R     a(a(a b b 1 + b(a b(- 2) + b a(- 1))) + b(a b a 4 + b a a(- 1)))
--R   +
--R     b(a b a a(- 2) + b a a a 1)
--R                                Type: XRecursivePolynomial(Symbol,Fraction(Integer))
--E 38

--S 39 of 39
```

```
pq :: rpoly - pr*qr
--R
--R
--R   (39)  0
--R                          Type: XRecursivePolynomial(Symbol,Fraction(Integer))
--E 39
)spool
)lisp (bye)
```

———-

— XPBWPolynomial.help —

```
=====================================================================
XPBWPolynomial examples
=====================================================================

Initialisations

  a:Symbol := 'a
    a
                                    Type: Symbol

  b:Symbol := 'b
    b
                                    Type: Symbol

  RN := Fraction(Integer)
    Fraction Integer
                                    Type: Domain

  word := OrderedFreeMonoid Symbol
    OrderedFreeMonoid Symbol
                                    Type: Domain

  lword := LyndonWord(Symbol)
    LyndonWord Symbol
                                    Type: Domain

  base := PoincareBirkhoffWittLyndonBasis Symbol
    PoincareBirkhoffWittLyndonBasis Symbol
                                    Type: Domain

  dpoly := XDistributedPolynomial(Symbol, RN)
    XDistributedPolynomial(Symbol,Fraction Integer)
                                    Type: Domain

  rpoly := XRecursivePolynomial(Symbol, RN)
    XRecursivePolynomial(Symbol,Fraction Integer)
```

```
                                Type: Domain

  lpoly := LiePolynomial(Symbol, RN)
    LiePolynomial(Symbol,Fraction Integer)
                                Type: Domain

  poly  := XPBWPolynomial(Symbol, RN)
    XPBWPolynomial(Symbol,Fraction Integer)
                                Type: Domain

  liste : List lword := LyndonWordsList([a,b], 6)
                      2       2     3      2 2       3     4      3 2
   [[a], [b], [a b], [a b], [a b ], [a b], [a b ], [a b ], [a b], [a b ],
     2         2 3          2       4     5      4 2     3          3 3
    [a b a b], [a b ], [a b a b ], [a b ], [a b], [a b ], [a b a b], [a b ],
     2     2     2 2       2 4          3       5
    [a b a b ], [a b a b], [a b ], [a b a b ], [a b ]]
                                Type: List LyndonWord Symbol
```

Let's make some polynomials

```
  0$poly
    0
                          Type: XPBWPolynomial(Symbol,Fraction Integer)

  1$poly
    1
                          Type: XPBWPolynomial(Symbol,Fraction Integer)

  p : poly := a
    [a]
                          Type: XPBWPolynomial(Symbol,Fraction Integer)

  q : poly := b
    [b]
                          Type: XPBWPolynomial(Symbol,Fraction Integer)

  pq: poly := p*q
    [a b] + [b][a]
                          Type: XPBWPolynomial(Symbol,Fraction Integer)
```

Coerce to distributed polynomial

```
  pq :: dpoly
    a b
                     Type: XDistributedPolynomial(Symbol,Fraction Integer)
```

Check some polynomial operations

```
  mirror pq
```

```
   [b][a]
                    Type: XPBWPolynomial(Symbol,Fraction Integer)

  listOfTerms pq
    [[k= [b][a],c= 1],[k= [a b],c= 1]]
     Type: List Record(k: PoincareBirkhoffWittLyndonBasis Symbol,
                       c: Fraction Integer)

  reductum pq
    [a b]
                    Type: XPBWPolynomial(Symbol,Fraction Integer)

  leadingMonomial pq
    [b][a]
                    Type: PoincareBirkhoffWittLyndonBasis Symbol

  coefficients pq
    [1,1]
                    Type: List Fraction Integer

  leadingTerm pq
    [k= [b][a],c= 1]
              Type: Record(k: PoincareBirkhoffWittLyndonBasis Symbol,
                           c: Fraction Integer)

  degree pq
    2
                    Type: PositiveInteger

  pq4:=exp(pq,4)
                          1              1     2       1      2
     1 + [a b] + [b][a] + - [a b][a b] + - [a b ][a] + - [b][a b]
                          2              2             2
   +
     3               1
     - [b][a b][a] + - [b][b][a][a]
     2               2
                    Type: XPBWPolynomial(Symbol,Fraction Integer)

  log(pq4,4) - pq
   (26)  0
                    Type: XPBWPolynomial(Symbol,Fraction Integer)

Calculations with verification in XDistributedPolynomial.

  lp1 :lpoly := LiePoly liste.10
       3 2
     [a b ]
                    Type: LiePolynomial(Symbol,Fraction Integer)
```

```
lp2 :lpoly := LiePoly liste.11
    2
  [a b a b]
                  Type: LiePolynomial(Symbol,Fraction Integer)

lp :lpoly := [lp1, lp2]
    3 2 2
  [a b a b a b]
                  Type: LiePolynomial(Symbol,Fraction Integer)

lpd1: dpoly := lp1
   3 2     2         2 2                    2 2           2    2 3
  a b  - 2a b a b - a b a + 4a b a b a - a b a  - 2b a b a  + b a
                  Type: XDistributedPolynomial(Symbol,Fraction Integer)

lpd2: dpoly := lp2
    2         2 2          2                    2 2       3       2
   a b a b - a b a - 3a b a b + 4a b a b a - a b a  + 2b a b - 3b a b a
 +
         2
   b a b a
                  Type: XDistributedPolynomial(Symbol,Fraction Integer)

lpd : dpoly := lpd1 * lpd2 - lpd2 * lpd1
    3 2 2         3 2 2 2      3 2     2      3 2            3 2   2 2
   a b a b a b - a b a b a - 3a b a b a b + 4a b a b a b a - a b a b a
 +
     3 3 3      3 3 2       3 3     2    2       3 2     2       2 2
   2a b a b - 3a b a b a + a b a b a  - a b a b a b  + 3a b a b a b a
 +
     2           2       2                    2         2 2     2     2 3
   6a b a b a b a b - 12a b a b a b a b a + 3a b a b a b a  - 4a b a b a b
 +
     2     2 2       2     3 3    2 2 4 2     2 2 3          2 2 2   2
   6a b a b a b a - a b a b a  + a b a b  - 3a b a b a b + 3a b a b a b
 +
       2 2     3      2 2     2        2 2         2    2 2   2 3
   - 2a b a b a b + 3a b a b a b a - 3a b a b a b a  + a b a b a
 +
         2   3 2         2   2             2   2 2           2
   3a b a b a b  - 6a b a b a b a b - 3a b a b a b a + 12a b a b a b a b a
 +
          2     2 2         2 2     2         2 3 3            4 2
   - 3a b a b a b a  - 6a b a b a b a  + 3a b a b a  - 4a b a b a b
 +
             3                  2   2                 3
   12a b a b a b a b - 12a b a b a b a b + 8a b a b a b a b
 +
                   2                        2             2 3      2 5 2
   - 12a b a b a b a b a + 12a b a b a b a b a  - 4a b a b a b a  + a b a b
```

```
  +
        2 4           2 3   2       2 2   3       2 2   2
    - 3a b a b a b + 3a b a b a b - 2a b a b a b + 3a b a b a b a
  +
        2 2       2     2 2 2 3       3   3 2       3   2
    - 3a b a b a b a  + a b a b a  - 2b a b a b  + 4b a b a b a b
  +
       3   2 2       3                 3    2 2      3 2    2      3 3 3
    2b a b a b a - 8b a b a b a b a + 2b a b a b a  + 4b a b a b a  - 2b a b a
  +
       2   4 2      2   3           2   3 2        2   2
    3b a b a b  - 6b a b a b a b - 3b a b a b a + 12b a b a b a b a
  +
        2   2 2 2      2          2      2    2 3         5 2
    - 3b a b a b a  - 6b a b a b a b a  + 3b a b a b a  - b a b a b
  +
          4 2           3   2           3                3 2 2
    3b a b a b a + 6b a b a b a b - 12b a b a b a b a + 3b a b a b a
  +
             2   3           2   2           2 2 3    2 5        2 5 2
    - 4b a b a b a b + 6b a b a b a b a - b a b a b a  + b a b a b - b a b a
  +
       2 4   2     2 4          2 4 2 2    2 3   3     2 3   2
    - 3b a b a b + 4b a b a b a - b a b a  + 2b a b a b - 3b a b a b a
  +
     2 3      2
    b a b a b a
                    Type: XDistributedPolynomial(Symbol,Fraction Integer)

  lp :: dpoly - lpd
    0
                    Type: XDistributedPolynomial(Symbol,Fraction Integer)

Calculations with verification in XRecursivePolynomial.

  p := 3 * lp
       3 2 2
    3[a b a b a b]
                    Type: XPBWPolynomial(Symbol,Fraction Integer)

  q := lp1
      3 2
    [a b ]
                    Type: XPBWPolynomial(Symbol,Fraction Integer)

  pq:= p * q
       3 2 2       3 2
    3[a b a b a b][a b ]
                    Type: XPBWPolynomial(Symbol,Fraction Integer)
```

```
pr:rpoly := p :: rpoly
     a
  *
        a
     *
           a b b
         *
           a(a b(a b 3 + b a(- 3)) + b(a(a b(- 9) + b a 12) + b a a(- 3)))
           +
             b a(a(a b 6 + b a(- 9)) + b a a 3)
        +
           b
         *
              a b
           *
                 a
              *
                    a(a b b(- 3) + b b a 9)
                 +
                    b(a(a b 18 + b a(- 36)) + b a a 9)
              +
                b(a a(a b(- 12) + b a 18) + b a a a(- 3))
           +
              b a
           *
                a(a(a b b 3 + b a b(- 9)) + b a a b 9)
              +
                b(a(a(a b(- 6) + b a 9) + b a a(- 9)) + b a a a 3)
     +
        b
     *
           a
        *
              a b
           *
                 a
              *
                    a(a b b 9 + b(a b(- 18) + b a(- 9)))
                 +
                    b(a b a 36 + b a a(- 9))
              +
                b(a b a a(- 18) + b a a a 9)
           +
              b a
           *
                a(a(a b b(- 12) + b a b 36) + b a a b(- 36))
              +
                b(a(a(a b 24 + b a(- 36)) + b a a 36) + b a a a(- 12))
        +
           b a a
```

```
          *
               a(a(a b b 3 + b a b(- 9)) + b a a b 9)
             +
               b(a(a(a b(- 6) + b a 9) + b a a(- 9)) + b a a a 3)
  +
     b
   *
          a
       *
             a
          *
                a b
             *
                   a
                *
                     a(a b b(- 6) + b(a b 12 + b a 6))
                   +
                     b(a b a(- 24) + b a a 6)
                +
                  b(a b a a 12 + b a a a(- 6))
             +
                b a
             *
                   a
                *
                     a(a b b 9 + b(a b(- 18) + b a(- 9)))
                   +
                     b(a b a 36 + b a a(- 9))
                +
                  b(a b a a(- 18) + b a a a 9)
          +
             b a a
          *
              a(a(a b b(- 3) + b b a 9) + b(a(a b 18 + b a(- 36)) + b a a 9))
             +
               b(a a(a b(- 12) + b a 18) + b a a a(- 3))
       +
          b a a a
        *
            a(a b(a b 3 + b a(- 3)) + b(a(a b(- 9) + b a 12) + b a a(- 3)))
          +
            b a(a(a b 6 + b a(- 9)) + b a a 3)
                    Type: XRecursivePolynomial(Symbol,Fraction Integer)


qr:rpoly := q :: rpoly
   a(a(a b b 1 + b(a b(- 2) + b a(- 1))) + b(a b a 4 + b a a(- 1)))
 +
   b(a b a a(- 2) + b a a a 1)
                    Type: XRecursivePolynomial(Symbol,Fraction Integer)
```

```
  pq :: rpoly - pr*qr
    0
                        Type: XRecursivePolynomial(Symbol,Fraction Integer)

See Also:
o )show XPBWPolynomial
```

———-

25.2.1 XPBWPolynomial (XPBWPOLY)



Exports:

0	1	characteristic	coef
coefficient	coefficients	coerce	constant
constant?	degree	exp	hash
latex	leadingCoefficient	leadingMonomial	leadingTerm
LiePolyIfCan	listOfTerms	log	lquo
map	maxdeg	mindeg	mindegTerm
mirror	monom	monomial?	monomials
numberOfMonomials	one?	product	quasiRegular
quasiRegular?	recip	reductum	retract
retractIfCan	rquo	sample	sh
subtractIfCan	trunc	varList	zero?
?*?	?**?	?+?	?-?
-?	?=?	?^?	?~=?

— domain XPBWPOLY XPBWPolynomial —

```
)abbrev domain XPBWPOLY XPBWPolynomial
++ Author: Michel Petitot (petitot@lifl.fr).
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
```

```
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain constructor implements polynomials in non-commutative
++ variables written in the Poincare-Birkhoff-Witt basis from the
++ Lyndon basis.
++ These polynomials can be used to compute Baker-Campbell-Hausdorff
++ relations.

XPBWPolynomial(VarSet:OrderedSet,R:CommutativeRing): XDPcat == XDPdef where

  WORD   ==> OrderedFreeMonoid(VarSet)
  LWORD  ==> LyndonWord(VarSet)
  LWORDS ==> List LWORD
  BASIS  ==> PoincareBirkhoffWittLyndonBasis(VarSet)
  TERM   ==> Record(k:BASIS, c:R)
  LTERMS ==> List(TERM)
  LPOLY  ==> LiePolynomial(VarSet,R)
  EX     ==> OutputForm
  XDPOLY ==> XDistributedPolynomial(VarSet,R)
  XRPOLY ==> XRecursivePolynomial(VarSet,R)
  TERM1  ==> Record(k:LWORD, c:R)
  NNI    ==> NonNegativeInteger
  I      ==> Integer
  RN     ==> Fraction(Integer)

  XDPcat == Join(XPolynomialsCat(VarSet,R), FreeModuleCat(R, BASIS)) with
    coerce      : LPOLY -> $
      ++ \axiom{coerce(p)} returns \axiom{p}.
    coerce      : $ -> XDPOLY
      ++ \axiom{coerce(p)} returns \axiom{p} as a distributed polynomial.
    coerce      : $ -> XRPOLY
      ++ \axiom{coerce(p)} returns \axiom{p} as a recursive polynomial.
    LiePolyIfCan: $ -> Union(LPOLY,"failed")
      ++ \axiom{LiePolyIfCan(p)} return  \axiom{p} if \axiom{p} is a Lie polynomial.
    product     : ($,$,NNI) -> $           -- produit tronque a l'ordre n
      ++ \axiom{product(a,b,n)} returns \axiom{a*b} (truncated up to order \axiom{n}).

    if R has Module(RN) then
       exp      : ($,NNI) -> $
          ++ \axiom{exp(p,n)} returns the exponential of \axiom{p}
          ++ (truncated up to order \axiom{n}).
       log      : ($,NNI) -> $
          ++ \axiom{log(p,n)} returns the logarithm of \axiom{p}
          ++ (truncated up to order \axiom{n}).
```

```
XDPdef == FreeModule1(R,BASIS) add
     import(TERM)

  -- Representation
     Rep:= LTERMS

  -- local functions
     prod1: (BASIS, $) -> $
     prod2: ($, BASIS) -> $
     prod : (BASIS, BASIS) -> $

     prod11: (BASIS, $, NNI) -> $
     prod22: ($, BASIS, NNI) -> $

     outForm : TERM -> EX
     Dexpand : BASIS -> XDPOLY
     Rexpand : BASIS -> XRPOLY
     process : (List LWORD, LWORD, List LWORD) -> $
     mirror1 : BASIS -> $

  -- functions locales
     outForm t ==
         t.c =$R 1 => t.k :: EX
         t.k =$BASIS 1 => t.c :: EX
         t.c::EX * t.k ::EX

     prod1(b:BASIS, p:$):$ ==
       +/ [t.c * prod(b, t.k) for t in p]

     prod2(p:$, b:BASIS):$ ==
       +/ [t.c * prod(t.k, b) for t in p]

     prod11(b,p,n) ==
         limit: I := n -$I length b
         +/ [t.c * prod(b, t.k) for t in p| length(t.k) :: I <= limit]

     prod22(p,b,n) ==
         limit: I := n -$I length b
         +/ [t.c * prod(t.k, b) for t in p| length(t.k) :: I <= limit]

     prod(g,d) ==
       d = 1 => monom(g,1)
       g = 1 => monom(d,1)
       process(reverse listOfTerms g, first d, rest listOfTerms d)

     Dexpand b ==
       b = 1 => 1$XDPOLY
       */ [LiePoly(l)$LPOLY :: XDPOLY for l in listOfTerms b]

     Rexpand b ==
```

```
      b = 1 => 1$XRPOLY
      */ [LiePoly(l)$LPOLY :: XRPOLY for l in listOfTerms b]

    mirror1(b:BASIS):$ ==
      b = 1 => 1
      lp: LPOLY := LiePoly first b
      lp := mirror lp
      mirror1(rest b) * lp :: $

    process(gauche, x, droite) ==    -- algo du "collect process"
      null gauche => monom( cons(x, droite) pretend BASIS, 1$R)
      r1, r2 : $
      not lexico(first gauche, x) =>     -- cas facile !!!
        monom(append(reverse gauche, cons(x, droite)) pretend BASIS , 1$R)

      p: LPOLY := [first gauche , x]      -- on crochete !!!
      null droite =>
        r1 :=  +/ [t.c * process(rest gauche, t.k, droite) for t in _
                   listOfTerms p]
        r2 :=  process( rest gauche, x, list first gauche)
        r1 + r2
      rd: List LWORD := rest droite; fd: LWORD := first droite
      r1 := +/ [t.c * process(list t.k, fd, rd) for t in  listOfTerms p]
      r1 := +/ [t.c * process(rest gauche, first t.k, rest listOfTerms(t.k))_
               for t in  r1]
      r2 := process([first gauche, x], fd, rd)
      r2 := +/ [t.c * process(rest gauche, first t.k, rest listOfTerms(t.k))_
               for t in  r2]
      r1 + r2

  -- definitions
    1 == monom(1$BASIS, 1$R)

    coerce(r:R):$ == [[1$BASIS , r]$TERM ]

    coerce(p:$):EX ==
      null p => (0$R) :: EX
      le : List EX := nil
      for rec in p repeat le := cons(outForm rec, le)
      reduce(_+, le)$List(EX)

    coerce(v: VarSet):$ == monom(v::BASIS , 1$R)
    coerce(p: LPOLY):$ ==
       [[t.k :: BASIS , t.c ]$TERM for t in listOfTerms p]

    coerce(p:$):XDPOLY ==
      +/ [t.c * Dexpand t.k for t in p]

    coerce(p:$):XRPOLY ==
      p = 0 => 0$XRPOLY
```

```
        +/ [t.c * Rexpand t.k for t in p]

      constant? p == (null p) or (leadingMonomial(p) =$BASIS 1)
      constant p ==
        null p => 0$R
        p.last.k = 1$BASIS => p.last.c
        0$R

      quasiRegular? p == (p=0) or (p.last.k ^= 1$BASIS)
      quasiRegular p ==
        p = 0 => p
        p.last.k = 1$BASIS => delete(p, maxIndex p)
        p

      x:$ * y:$ ==
        y = 0$$ => 0
        +/ [t.c * prod1(t.k, y) for t in x]

--      listOfTerms p == p pretend LTERMS

      varList p ==
         lv: List VarSet := "setUnion"/ [varList(b.k)$BASIS for b in p]
         sort(lv)

      degree(p) ==
         p=0 => error "null polynomial"
         length(leadingMonomial p)

      trunc(p, n) ==
        p = 0 => p
        degree(p) > n => trunc( reductum p , n)
        p

      product(x,y,n) ==
        x = 0 => 0
        y = 0 => 0
        +/ [t.c * prod11(t.k, y, n) for t in x]

      if R has Module(RN) then
        exp (p,n) ==
            p = 0 => 1
            not quasiRegular? p =>
              error "a proper polynomial is required"
            s : $ := 1 ; r: $ := 1                  -- resultat
            for i in 1..n repeat
               k1 :RN := 1/i
               k2 : R := k1 * 1$R
               s := k2 * product(p, s, n)
               r := r + s
            r
```

```
        log (p,n) ==
            p = 1 => 0
            p1: $ := 1 - p
            not quasiRegular? p1 =>
              error "constant term <> 1, impossible log "
            s : $ := - 1 ; r: $ := 0                -- resultat
            for i in 1..n repeat
              k1 :RN := 1/i
              k2 : R := k1 * 1$R
              s := product(p1, s, n)
              r := k2 * s + r
            r

      LiePolyIfCan p ==
        p = 0 => 0$LPOLY
        "and"/ [retractable?(t.k)$BASIS for t in p] =>
           lt : List TERM1 := _
                [[retract(t.k)$BASIS, t.c]$TERM1 for t in p]
           lt pretend LPOLY
        "failed"

      mirror p ==
        +/ [t.c * mirror1(t.k) for t in p]
```

———-

— **XPBWPOLY.dotabb** —

```
"XPBWPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=XPBWPOLY"]
"XPOLYC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=XPOLYC"]
"XPBWPOLY" -> "XPOLYC"
```

———-

25.3 domain XPOLY XPolynomial

— **XPolynomial.input** —

```
)set break resume
)sys rm -f XPolynomial.output
)spool XPolynomial.output
)set message test on
)set message auto off
```

```
)clear all
--S 1 of 14
poly := XPolynomial(Integer)
--R
--R
--R   (1)  XPolynomial(Integer)
--R                                                                Type: Domain
--E 1

--S 2 of 14
pr: poly := 2*x + 3*y-5
--R
--R
--R   (2)  - 5 + x 2 + y 3
--R                                                 Type: XPolynomial(Integer)
--E 2

--S 3 of 14
pr2: poly := pr*pr
--R
--R
--R   (3)  25 + x(- 20 + x 4 + y 6) + y(- 30 + x 6 + y 9)
--R                                                 Type: XPolynomial(Integer)
--E 3

--S 4 of 14
pd  := expand pr
--R
--R
--R   (4)  - 5 + 2x + 3y
--R                                Type: XDistributedPolynomial(Symbol,Integer)
--E 4

--S 5 of 14
pd2 := pd*pd
--R
--R
--R                            2                   2
--R   (5)  25 - 20x - 30y + 4x  + 6x y + 6y x + 9y
--R                                Type: XDistributedPolynomial(Symbol,Integer)
--E 5

--S 6 of 14
expand(pr2) - pd2
--R
--R
--R   (6)  0
--R                                Type: XDistributedPolynomial(Symbol,Integer)
--E 6
```

```
--S 7 of 14
qr :=  pr**3
--R
--R
--R   (7)
--R     - 125 + x(150 + x(- 60 + x 8 + y 12) + y(- 90 + x 12 + y 18))
--R   +
--R     y(225 + x(- 90 + x 12 + y 18) + y(- 135 + x 18 + y 27))
--R                                                  Type: XPolynomial(Integer)
--E 7

--S 8 of 14
qd :=  pd**3
--R
--R
--R   (8)
--R                               2                        2     3      2
--R     - 125 + 150x + 225y - 60x  - 90x y - 90y x - 135y  + 8x  + 12x y + 12x y x
--R   +
--R          2        2                2       3
--R     18x y  + 12y x  + 18y x y + 18y x + 27y
--R                                  Type: XDistributedPolynomial(Symbol,Integer)
--E 8

--S 9 of 14
trunc(qd,2)
--R
--R
--R                                  2                       2
--R   (9)  - 125 + 150x + 225y - 60x  - 90x y - 90y x - 135y
--R                                  Type: XDistributedPolynomial(Symbol,Integer)
--E 9

--S 10 of 14
trunc(qr,2)
--R
--R
--R   (10)  - 125 + x(150 + x(- 60) + y(- 90)) + y(225 + x(- 90) + y(- 135))
--R                                                  Type: XPolynomial(Integer)
--E 10

--S 11 of 14
Word := OrderedFreeMonoid Symbol
--R
--R
--R   (11)  OrderedFreeMonoid(Symbol)
--R                                                                Type: Domain
--E 11

--S 12 of 14
```

```
w: Word := x*y**2
--R
--R
--R            2
--R   (12)  x y
--R                                              Type: OrderedFreeMonoid(Symbol)
--E 12

--S 13 of 14
rquo(qr,w)
--R
--R
--R   (13)  18
--R                                                   Type: XPolynomial(Integer)
--E 13

--S 14 of 14
sh(pr,w::poly)
--R
--R
--R   (14)  x(x y y 4 + y(x y 2 + y(- 5 + x 2 + y 9))) + y x y y 3
--R                                                   Type: XPolynomial(Integer)
--E 14
)spool
)lisp (bye)
```

———-

— XPolynomial.help —

```
=====================================================================
XPolynomial examples
=====================================================================

The XPolynomial domain constructor implements multivariate polynomials
whose set of variables is Symbol.  These variables do not commute.
The only parameter of this construtor is the coefficient ring which
may be non-commutative.  However, coefficients and variables commute.
The representation of the polynomials is recursive.  The abbreviation
for XPolynomial is XPOLY.

Other constructors like XPolynomialRing, XRecursivePolynomial as well
as XDistributedPolynomial, LiePolynomial and XPBWPolynomial implement
multivariate polynomials in non-commutative variables.

We illustrate now some of the facilities of the XPOLY domain constructor.

Define a polynomial ring over the integers.
```

```
  poly := XPolynomial(Integer)
    XPolynomial Integer
                                  Type: Domain
```

Define a first polynomial,

```
  pr: poly := 2*x + 3*y-5
    - 5 + x 2 + y 3
                                  Type: XPolynomial Integer
```

and a second one.

```
  pr2: poly := pr*pr
    25 + x(- 20 + x 4 + y 6) + y(- 30 + x 6 + y 9)
                                  Type: XPolynomial Integer
```

Rewrite pr in a distributive way,

```
  pd  := expand pr
    - 5 + 2x + 3y
                                  Type: XDistributedPolynomial(Symbol,Integer)
```

compute its square,

```
  pd2 := pd*pd
                         2                   2
    25 - 20x - 30y + 4x  + 6x y + 6y x + 9y
                                  Type: XDistributedPolynomial(Symbol,Integer)
```

and checks that:

```
  expand(pr2) - pd2
    0
                                  Type: XDistributedPolynomial(Symbol,Integer)
```

We define:

```
  qr :=  pr**3
     - 125 + x(150 + x(- 60 + x 8 + y 12) + y(- 90 + x 12 + y 18))
   +
     y(225 + x(- 90 + x 12 + y 18) + y(- 135 + x 18 + y 27))
                                  Type: XPolynomial Integer
```

and:

```
  qd :=  pd**3
                              2                         2     3      2
     - 125 + 150x + 225y - 60x  - 90x y - 90y x - 135y  + 8x  + 12x y + 12x y x
   +
          2        2                2       3
```

```
     18x y  + 12y x  + 18y x y + 18y x + 27y
                                Type: XDistributedPolynomial(Symbol,Integer)
```

We truncate qd at degree 3.

```
  trunc(qd,2)
                              2                       2
    - 125 + 150x + 225y - 60x  - 90x y - 90y x - 135y
                                Type: XDistributedPolynomial(Symbol,Integer)
```

The same for qr:

```
  trunc(qr,2)
    - 125 + x(150 + x(- 60) + y(- 90)) + y(225 + x(- 90) + y(- 135))
                                Type: XPolynomial Integer
```

We define:

```
  Word := OrderedFreeMonoid Symbol
    OrderedFreeMonoid Symbol
                                Type: Domain
```

and:

```
  w: Word := x*y**2
       2
    x y
                                Type: OrderedFreeMonoid Symbol
```

We can compute the right-quotient of qr by r:

```
  rquo(qr,w)
    18
                                Type: XPolynomial Integer
```


and the shuffle-product of pr by r:

```
  sh(pr,w::poly)
    x(x y y 4 + y(x y 2 + y(- 5 + x 2 + y 9))) + y x y y 3
                                Type: XPolynomial Integer
```

See Also:
o)help XPBWPolynomial
o)help LiePolynomial
o)help XDistributedPolynomial
o)help XRecursivePolynomial
o)help XPolynomialRing
o)show XPolynomial

———-

25.3.1 XPolynomial (XPOLY)



Exports:

0	1	characteristic	coef	coerce
constant	constant?	degree	expand	hash
latex	lquo	map	maxdeg	mindeg
mindegTerm	mirror	monom	monomial?	RemainderList
one?	quasiRegular	quasiRegular?	recip	retract
retractIfCan	rquo	sample	sh	subtractIfCan
trunc	unexpand	varList	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?			

— domain XPOLY XPolynomial —

```
)abbrev domain XPOLY XPolynomial
++ Author: Michel Petitot petitot@lifl.fr
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++   extend renomme en expand
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type supports multivariate polynomials whose set of variables
++ is \spadtype{Symbol}. The representation is recursive.
++ The coefficient ring may be non-commutative and the variables
++ do not commute. However, coefficients and variables commute.
```

```
XPolynomial(R:Ring) == XRecursivePolynomial(Symbol, R)
```

———-

— **XPOLY.dotabb** —

```
"XPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=XPOLY"]
"XPOLYC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=XPOLYC"]
"XPOLY" -> "XPOLYC"
```

———-

25.4 domain XPR XPolynomialRing

— **XPolynomialRing.input** —

```
)set break resume
)sys rm -f XPolynomialRing.output
)spool XPolynomialRing.output
)set message test on
)set message auto off
)clear all
--S 1 of 15
Word := OrderedFreeMonoid(Symbol)
--R
--R
--R   (1)  OrderedFreeMonoid(Symbol)
--R                                                          Type: Domain
--E 1

--S 2 of 15
poly:= XPR(Integer,Word)
--R
--R
--R   (2)  XPolynomialRing(Integer,OrderedFreeMonoid(Symbol))
--R                                                          Type: Domain
--E 2

--S 3 of 15
p:poly := 2 * x - 3 * y + 1
--R
--R
--R   (3)  1 + 2x - 3y
```

```
--R                    Type: XPolynomialRing(Integer,OrderedFreeMonoid(Symbol))
--E 3

--S 4 of 15
q:poly := 2 * x + 1
--R
--R
--R   (4)  1 + 2x
--R                    Type: XPolynomialRing(Integer,OrderedFreeMonoid(Symbol))
--E 4

--S 5 of 15
p + q
--R
--R
--R   (5)  2 + 4x - 3y
--R                    Type: XPolynomialRing(Integer,OrderedFreeMonoid(Symbol))
--E 5

--S 6 of 15
p * q
--R
--R
--R                       2
--R   (6)  1 + 4x - 3y + 4x  - 6y x
--R                    Type: XPolynomialRing(Integer,OrderedFreeMonoid(Symbol))
--E 6

--S 7 of 15
(p+q)**2-p**2-q**2-2*p*q
--R
--R
--R   (7)  - 6x y + 6y x
--R                    Type: XPolynomialRing(Integer,OrderedFreeMonoid(Symbol))
--E 7

--S 8 of 15
M := SquareMatrix(2,Fraction Integer)
--R
--R
--R   (8)  SquareMatrix(2,Fraction(Integer))
--R                                                              Type: Domain
--E 8

--S 9 of 15
poly1:= XPR(M,Word)
--R
--R
--R   (9)
--R   XPolynomialRing(SquareMatrix(2,Fraction(Integer)),OrderedFreeMonoid(Symbol))
```

```
--R                                                                  Type: Domain
--E 9

--S 10 of 15
m1:M := matrix [ [i*j**2 for i in 1..2] for j in 1..2]
--R
--R
--R         +1  2+
--R   (10)  |    |
--R         +4  8+
--R                                      Type: SquareMatrix(2,Fraction(Integer))
--E 10

--S 11 of 15
m2:M := m1 - 5/4
--R
--R
--R         +  1    +
--R         |- -  2 |
--R         |  4    |
--R   (11)  |       |
--R         |     27|
--R         | 4   --|
--R         +      4+
--R                                      Type: SquareMatrix(2,Fraction(Integer))
--E 11

--S 12 of 15
m3: M := m2**2
--R
--R
--R         +129     +
--R         |---  13 |
--R         | 16     |
--R   (12)  |        |
--R         |     857|
--R         |26   ---|
--R         +      16+
--R                                      Type: SquareMatrix(2,Fraction(Integer))
--E 12

--S 13 of 15
pm:poly1   := m1*x + m2*y + m3*z - 2/3
--R
--R
--R         +  2     +             +  1    +    +129     +
--R         |- -   0 |             |- -  2 |    |---  13 |
--R         |  3     |   +1  2+    |  4    |    | 16     |
--R   (13)  |        | + |    |x + |       |y + |        |z
--R         |       2|   +4  8+    |     27|    |     857|
```

```
--R         | 0   - -|             | 4   --|    |26   ---|
--R         +       3+             +      4+    +      16+
--RType: XPolynomialRing(SquareMatrix(2,Fraction(Integer)),OrderedFreeMonoid(Symbol))
--E 13

--S 14 of 15
qm:poly1 := pm - m1*x
--R
--R
--R         +  2     +   +  1    +    +129     +
--R         |- -   0 |   |- -  2 |    |---  13 |
--R         |  3     |   |  4    |    | 16     |
--R   (14)  |        | + |       |y + |        |z
--R         |       2|   |     27|    |     857|
--R         | 0   - -|   | 4   --|    |26   ---|
--R         +       3+   +      4+    +      16+
--RType: XPolynomialRing(SquareMatrix(2,Fraction(Integer)),OrderedFreeMonoid(Symbol))
--E 14

--S 15 of 15
qm**3
--R
--R
--R   (15)
--R     +   8      +   +  1  8+    +43   52 +    +  129       +
--R     |- --   0  |   |- -  -|    |--   -- |    |- ---  - 26 |
--R     |  27      |   |  3  3|    | 4    3 |    |   8        | 2
--R     |          | + |      |y + |        |z + |            |y
--R     |         8|   |16    |    |104  857|    |         857|
--R     | 0    - --|   |--   9|    |---  ---|    |- 52   - ---|
--R     +        27+   + 3    +    + 3    12+    +          8 +
--R   +
--R     +  3199     831 +      +  3199     831 +      +  103169     6409 +
--R     |- ----   - --- |      |- ----   - --- |      |- ------   - ---- |
--R     |   32       4  |      |   32       4  |      |    128        4  | 2
--R     |               |y z + |               |z y + |                 |z
--R     |  831     26467|      |  831     26467|      |   6409     820977|
--R     |- ---   - -----|      |- ---   - -----|      | - ----   - ------|
--R     +   2        32 +      +   2        32 +      +     2        128 +
--R   +
--R     +3199   831 +     +103169   6409 +      +103169   6409 +
--R     |----   --- |     |------   ---- |      |------   ---- |
--R     | 64     8  | 3   |  256      8  | 2    |  256      8  |
--R     |           |y  + |              |y z + |              |y z y
--R     |831   26467|     | 6409   820977|      | 6409   820977|
--R     |---   -----|     | ----   ------|      | ----   ------|
--R     + 4      64 +     +   4      256 +      +   4      256 +
--R   +
--R     +3178239   795341 +       +103169   6409 +       +3178239   795341 +
--R     |-------   ------ |       |------   ---- |       |-------   ------ |
```

```
--R     |  1024      128  |   2   |  256      8  |   2   |  1024      128  |
--R     |                 |y z  + |             |z y  + |                 |z y z
--R     |795341   25447787|       | 6409   820977|       |795341   25447787|
--R     |------   --------|       | ----   ------|       |------   --------|
--R     +  64       1024  +       +   4      256 +       +  64       1024  +
--R   +
--R     +3178239   795341 +      +98625409  12326223 +
--R     |-------   ------ |      |--------  -------- |
--R     |  1024      128  | 2    |  4096       256   | 3
--R     |                 |z y + |                   |z
--R     |795341   25447787|      |12326223  788893897|
--R     |------   --------|      |--------  ---------|
--R     +  64       1024  +      +   128       4096  +
--RType: XPolynomialRing(SquareMatrix(2,Fraction(Integer)),OrderedFreeMonoid(Symbol))
--E 15
)spool
)lisp (bye)
```

———-

— XPolynomialRing.help —

```
=====================================================================
XPolynomialRing examples
=====================================================================

The XPolynomialRing domain constructor implements generalized
polynomials with coefficients from an arbitrary Ring (not necessarily
commutative) and whose exponents are words from an arbitrary
OrderedMonoid (not necessarily commutative too).  Thus these
polynomials are (finite) linear combinations of words.

This constructor takes two arguments.  The first one is a Ring and the
second is an OrderedMonoid.  The abbreviation for XPolynomialRing is XPR.

Other constructors like XPolynomial, XRecursivePolynomial,
XDistributedPolynomial, LiePolynomial and XPBWPolynomial implement
multivariate polynomials in non-commutative variables.

We illustrate now some of the facilities of the XPR domain constructor.

Define the free ordered monoid generated by the symbols.

  Word := OrderedFreeMonoid(Symbol)
    OrderedFreeMonoid Symbol
                                  Type: Domain

Define the linear combinations of these words with integer coefficients.
```

```
  poly:= XPR(Integer,Word)
    XPolynomialRing(Integer,OrderedFreeMonoid Symbol)
                                  Type: Domain
```

Then we define a first element from poly.

```
  p:poly := 2 * x - 3 * y + 1
    1 + 2x - 3y
                      Type: XPolynomialRing(Integer,OrderedFreeMonoid Symbol)
```

And a second one.

```
  q:poly := 2 * x + 1
    1 + 2x
                      Type: XPolynomialRing(Integer,OrderedFreeMonoid Symbol)
```

We compute their sum,

```
  p + q
    2 + 4x - 3y
                      Type: XPolynomialRing(Integer,OrderedFreeMonoid Symbol)
```

their product,

```
  p * q
                     2
    1 + 4x - 3y + 4x  - 6y x
                      Type: XPolynomialRing(Integer,OrderedFreeMonoid Symbol)
```

and see that variables do not commute.

```
  (p+q)**2-p**2-q**2-2*p*q
    - 6x y + 6y x
                      Type: XPolynomialRing(Integer,OrderedFreeMonoid Symbol)
```

Now we define a ring of square matrices,

```
  M := SquareMatrix(2,Fraction Integer)
    SquareMatrix(2,Fraction Integer)
                                  Type: Domain
```

and the linear combinations of words with these matrices as coefficients.

```
  poly1:= XPR(M,Word)
   XPolynomialRing(SquareMatrix(2,Fraction Integer),OrderedFreeMonoid Symbol)
                                  Type: Domain
```

Define a first matrix,

```
  m1:M := matrix [ [i*j**2 for i in 1..2] for j in 1..2]
```

```
        +1  2+
        |    |
        +4  8+
                                Type: SquareMatrix(2,Fraction Integer)
```

a second one,

```
  m2:M := m1 - 5/4
        +  1    +
        |- -  2 |
        |  4    |
        |       |
        |     27|
        | 4   --|
        +      4+
                                Type: SquareMatrix(2,Fraction Integer)
```

and a third one.

```
  m3: M := m2**2
        +129     +
        |---  13 |
        | 16     |
        |        |
        |     857|
        |26   ---|
        +      16+
                                Type: SquareMatrix(2,Fraction Integer)
```

Define a polynomial,

```
  pm:poly1   := m1*x + m2*y + m3*z - 2/3
        +  2     +             +  1    +    +129     +
        |- -   0 |             |- -  2 |    |---  13 |
        |  3     |   +1  2+    |  4    |    | 16     |
        |        | + |    |x + |       |y + |        |z
        |       2|   +4  8+    |     27|    |     857|
        | 0   - -|             | 4   --|    |26   ---|
        +       3+             +      4+    +      16+
    Type: XPolynomialRing(SquareMatrix(2,Fraction Integer),
                          OrderedFreeMonoid Symbol)
```

a second one,

```
  qm:poly1 := pm - m1*x
        +  2     +   +  1    +    +129     +
        |- -   0 |   |- -  2 |    |---  13 |
        |  3     |   |  4    |    | 16     |
        |        | + |       |y + |        |z
        |       2|   |     27|    |     857|
```

```
        | 0   - -|   | 4   --|    |26   ---|
        +       3+   +      4+    +      16+
     Type: XPolynomialRing(SquareMatrix(2,Fraction Integer),
                           OrderedFreeMonoid Symbol)
```


and the following power.

```
  qm**3
    +   8      +   +  1  8+    +43   52 +    +  129       +
    |- --   0  |   |- -  -|    |--   -- |    |- ---  - 26 |
    |  27      |   |  3  3|    | 4    3 |    |   8        | 2
    |          | + |      |y + |        |z + |            |y
    |         8|   |16    |    |104  857|    |         857|
    | 0    - --|   |--   9|    |---  ---|    |- 52   - ---|
    +        27+   + 3    +    + 3    12+    +          8 +
  +
    +  3199     831 +      +  3199     831 +      +  103169     6409 +
    |- ----   - --- |      |- ----   - --- |      |- ------   - ---- |
    |   32       4  |      |   32       4  |      |    128        4  | 2
    |               |y z + |               |z y + |                  |z
    |  831     26467|      |  831     26467|      |   6409     820977|
    |- ---   - -----|      |- ---   - -----|      | - ----   - ------|
    +   2        32 +      +   2        32 +      +     2        128 +
  +
    +3199   831 +     +103169   6409 +      +103169   6409 +
    |----   --- |     |------   ---- |      |------   ---- |
    | 64     8  | 3   |  256      8  | 2    |  256      8  |
    |           |y  + |              |y z + |              |y z y
    |831   26467|     | 6409   820977|      | 6409   820977|
    |---   -----|     | ----   ------|      | ----   ------|
    + 4      64 +     +   4      256 +      +   4      256 +
  +
    +3178239   795341 +       +103169   6409 +       +3178239   795341 +
    |-------   ------ |       |------   ---- |       |-------   ------ |
    |  1024      128  |   2   |  256      8  |   2   |  1024      128  |
    |                 |y z  + |              |z y  + |                 |z y z
    |795341   25447787|       | 6409   820977|       |795341   25447787|
    |------   --------|       | ----   ------|       |------   --------|
    +  64       1024  +       +   4      256 +       +  64       1024  +
  +
    +3178239   795341 +      +98625409  12326223 +
    |-------   ------ |      |--------  -------- |
    |  1024      128  | 2    |  4096       256   | 3
    |                 |z y + |                   |z
    |795341   25447787|      |12326223  788893897|
    |------   --------|      |--------  ---------|
    +  64       1024  +      +   128       4096  +
       Type: XPolynomialRing(SquareMatrix(2,Fraction Integer),
                             OrderedFreeMonoid Symbol)
```

```
See Also:
o )help XPBWPolynomial
o )help LiePolynomial
o )help XDistributedPolynomial
o )help XRecursivePolynomial
o )help XPolynomial
o )show XPolynomialRing
```

———-

25.4.1 XPolynomialRing (XPR)



Exports:

0	1	characteristic	coef
coefficient	coefficients	coerce	constant
constant?	hash	latex	leadingCoefficient
leadingMonomial	leadingTerm	listOfTerms	map
maxdeg	mindeg	monom	monomial?
monomials	numberOfMonomials	one?	quasiRegular
quasiRegular?	recip	reductum	retract
retractIfCan	sample	subtractIfCan	zero?
#?	?*?	?**?	?+?
?-?	-?	?=?	?^?
?~=?			

— domain XPR XPolynomialRing —

```
)abbrev domain XPR XPolynomialRing
++ Author: Michel Petitot petitot@lifl.fr
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++ Basic Functions:
```

```
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This domain represents generalized polynomials with coefficients
++ (from a not necessarily commutative ring), and words
++ belonging to an arbitrary \spadtype{OrderedMonoid}.
++ This type is used, for instance, by the \spadtype{XDistributedPolynomial}
++ domain constructor where the Monoid is free.

XPolynomialRing(R:Ring,E:OrderedMonoid): T == C where
  TERM   ==> Record(k: E, c: R)
  EX     ==> OutputForm
  NNI    ==> NonNegativeInteger

  T == Join(Ring, XAlgebra(R), FreeModuleCat(R,E)) with
    --operations
      "*": (%,R) -> %
        ++ \spad{p*r} returns the product of \spad{p} by \spad{r}.
      "#": % -> NonNegativeInteger
        ++ \spad{# p} returns the number of terms in \spad{p}.
      coerce: E -> %
        ++ \spad{coerce(e)} returns \spad{1*e}
      maxdeg: % -> E
        ++ \spad{maxdeg(p)} returns the greatest word occurring in the polynomial \spad{p}
        ++ with a non-zero coefficient. An error is produced if  \spad{p} is zero.
      mindeg: % -> E
        ++ \spad{mindeg(p)} returns the smallest word occurring in the polynomial \spad{p}
        ++ with a non-zero coefficient. An error is produced if  \spad{p} is zero.
      reductum : % -> %
        ++ \spad{reductum(p)} returns \spad{p} minus its leading term.
        ++ An error is produced if  \spad{p} is zero.
      coef  : (%,E) -> R
        ++ \spad{coef(p,e)} extracts the coefficient of the monomial \spad{e}.
        ++ Returns zero if \spad{e} is not present.
      constant?:% -> Boolean
        ++ \spad{constant?(p)} tests whether the polynomial \spad{p} belongs to the
        ++ coefficient ring.
      constant: % -> R
        ++ \spad{constant(p)} return the constant term of \spad{p}.
      quasiRegular? : % -> Boolean
        ++ \spad{quasiRegular?(x)} return true if \spad{constant(p)} is zero.
      quasiRegular : % -> %
        ++ \spad{quasiRegular(x)} return \spad{x} minus its constant term.
      map   : (R -> R, %) -> %
        ++ \spad{map(fn,x)} returns \spad{Sum(fn(r_i) w_i)} if \spad{x} writes \spad{Sum(r_i w_i
      if R has Field then "/" : (%,R) -> %
        ++ \spad{p/r} returns \spad{p*(1/r)}.
```

```
  --assertions
    if R has noZeroDivisors then noZeroDivisors
    if R has unitsKnown then unitsKnown
    if R has canonicalUnitNormal then canonicalUnitNormal
        ++ canonicalUnitNormal guarantees that the function
        ++ unitCanonical returns the same representative for all
        ++ associates of any particular element.


C == FreeModule1(R,E) add
  --representations
     Rep:=  List TERM
  --uses
     repeatMultExpt: (%,NonNegativeInteger) -> %
  --define
     1  == [[1$E,1$R]]

     characteristic  == characteristic$R
     #x == #$Rep x
     maxdeg p == if null p then  error " polynome nul !!"
                           else p.first.k
     mindeg p == if null p then  error " polynome nul !!"
                           else (last p).k

     coef(p,e)  ==
        for tm in p repeat
          tm.k=e => return tm.c
          tm.k < e => return 0$R
        0$R

     constant? p == (p = 0) or (maxdeg(p) = 1$E)
     constant  p == coef(p,1$E)

     quasiRegular? p == (p=0) or (last p).k ^= 1$E
     quasiRegular  p ==
        quasiRegular?(p) => p
        [t for t in p | not(t.k = 1$E)]

     recip(p) ==
         p=0 => "failed"
         p.first.k > 1$E => "failed"
         (u:=recip(p.first.c)) case "failed" => "failed"
         (u::R)::%

     coerce(r:R) == if r=0$R then 0$% else [[1$E,r]]
     coerce(n:Integer) == (n::R)::%

     if R has noZeroDivisors then
       p1:% * p2:%  ==
```

```
           null p1 => 0
           null p2 => 0
           p1.first.k = 1$E => p1.first.c * p2
           p2 = 1 => p1
--           +/[[[t1.k*t2.k,t1.c*t2.c]$TERM for t2 in p2]
--                   for t1 in reverse(p1)]
           +/[[[t1.k*t2.k,t1.c*t2.c]$TERM for t2 in p2]
                 for t1 in p1]
        else
         p1:% * p2:%  ==
           null p1 => 0
           null p2 => 0
           p1.first.k = 1$E => p1.first.c * p2
           p2 = 1 => p1
--           +/[[[t1.k*t2.k,r]$TERM for t2 in p2 | not (r:=t1.c*t2.c) =$R 0]
--                 for t1 in reverse(p1)]
           +/[[[t1.k*t2.k,r]$TERM for t2 in p2 | not (r:=t1.c*t2.c) =$R 0]
                 for t1 in p1]
      p:% ** nn:NNI  == repeatMultExpt(p,nn)
      repeatMultExpt(x,nn) ==
           nn = 0 => 1
           y:% := x
           for i in 2..nn repeat y:= x * y
           y

      outTerm(r:R, m:E):EX ==
           r=1 => m::EX
           m=1 => r::EX
           r::EX * m::EX

--      coerce(x:%) : EX ==
--        null x => (0$R) :: EX
--        le : List EX := nil
--        for rec in x repeat
--          rec.c = 1$R => le := cons(rec.k :: EX, le)
--          rec.k = 1$E => le := cons(rec.c :: EX, le)
--          le := cons(mkBinary("*"::EX,rec.c :: EX,
--            rec.k :: EX), le)
--        1 = #le => first le
--        mkNary("+" :: EX,le)

      coerce(a:%):EX ==
           empty? a => (0$R)::EX
           reduce(_+, reverse_! [outTerm(t.c, t.k) for t in a])$List(EX)


      if R has Field then
         x/r == inv(r)*x
```

———-

— **XPR.dotabb** —

```
"XPR" [color="#88FF44",href="bookvol10.3.pdf#nameddest=XPR"]
"FLAGG" [color="#4488FF",href="bookvol10.2.pdf#nameddest=FLAGG"]
"FLAGG-" [color="#88FF44",href="bookvol10.3.pdf#nameddest=FLAGG"]
"FIELD"  [color="#4488FF",href="bookvol10.2.pdf#nameddest=FIELD"]
"XPR" -> "FLAGG"
"XPR" -> "FLAGG-"
"XPR" -> "FIELD"
```

———-

25.5 domain XRPOLY XRecursivePolynomial

— **XRecursivePolynomial.input** —

```
)set break resume
)sys rm -f XRecursivePolynomial.output
)spool XRecursivePolynomial.output
)set message test on
)set message auto off
)clear all

--S 1 of 1
)show XRecursivePolynomial
--R
--R XRecursivePolynomial(VarSet: OrderedSet,R: Ring)  is a domain constructor
--R Abbreviation for XRecursivePolynomial is XRPOLY
--R This constructor is not exposed in this frame.
--R Issue )edit bookvol10.3.pamphlet to see algebra source code for XRPOLY
--R
--R------------------------------ Operations --------------------------------
--R ?*? : (VarSet,%) -> %                ?*? : (%,R) -> %
--R ?*? : (R,%) -> %                     ?*? : (%,%) -> %
--R ?*? : (Integer,%) -> %               ?*? : (PositiveInteger,%) -> %
--R ?**? : (%,PositiveInteger) -> %      ?+? : (%,%) -> %
--R ?-? : (%,%) -> %                     -? : % -> %
--R ?=? : (%,%) -> Boolean               1 : () -> %
--R 0 : () -> %                          ?^? : (%,PositiveInteger) -> %
--R coef : (%,%) -> R                    coerce : VarSet -> %
--R coerce : R -> %                      coerce : Integer -> %
--R coerce : % -> OutputForm             constant : % -> R
--R constant? : % -> Boolean             degree : % -> NonNegativeInteger
```

```
--R hash : % -> SingleInteger             latex : % -> String
--R lquo : (%,%) -> %                     lquo : (%,VarSet) -> %
--R map : ((R -> R),%) -> %               mirror : % -> %
--R monomial? : % -> Boolean              one? : % -> Boolean
--R quasiRegular : % -> %                 quasiRegular? : % -> Boolean
--R recip : % -> Union(%,"failed")        rquo : (%,%) -> %
--R rquo : (%,VarSet) -> %                sample : () -> %
--R varList : % -> List(VarSet)           zero? : % -> Boolean
--R ?~=? : (%,%) -> Boolean
--R ?*? : (NonNegativeInteger,%) -> %
--R ?**? : (%,NonNegativeInteger) -> %
--R RemainderList : % -> List(Record(k: VarSet,c: %))
--R ?^? : (%,NonNegativeInteger) -> %
--R characteristic : () -> NonNegativeInteger
--R coef : (%,OrderedFreeMonoid(VarSet)) -> R
--R coerce : OrderedFreeMonoid(VarSet) -> %
--R expand : % -> XDistributedPolynomial(VarSet,R)
--R lquo : (%,OrderedFreeMonoid(VarSet)) -> %
--R maxdeg : % -> OrderedFreeMonoid(VarSet)
--R mindeg : % -> OrderedFreeMonoid(VarSet)
--R mindegTerm : % -> Record(k: OrderedFreeMonoid(VarSet),c: R)
--R monom : (OrderedFreeMonoid(VarSet),R) -> %
--R retract : % -> OrderedFreeMonoid(VarSet)
--R retractIfCan : % -> Union(OrderedFreeMonoid(VarSet),"failed")
--R rquo : (%,OrderedFreeMonoid(VarSet)) -> %
--R sh : (%,NonNegativeInteger) -> % if R has COMRING
--R sh : (%,%) -> % if R has COMRING
--R subtractIfCan : (%,%) -> Union(%,"failed")
--R trunc : (%,NonNegativeInteger) -> %
--R unexpand : XDistributedPolynomial(VarSet,R) -> %
--R
--E 1

)spool
)lisp (bye)
```

———-

— XRecursivePolynomial.help —


```
=====================================================================
XRecursivePolynomial examples
=====================================================================

See Also:
o )show XRecursivePolynomial
```

———-

Polynomial arithmetic with non-commutative variables has been improved by a contribution of Michel Petitot (University of Lille I, France). The domain constructors **XRecursivePolynomial** provides a recursive for these polynomials. It is the non-commutative equivalents for the **SparseMultivariatePolynomial** constructor.

25.5.1 XRecursivePolynomial (XRPOLY)



Exports:

0	1	characteristic	coef	coerce
constant	constant?	degree	expand	hash
latex	lquo	map	maxdeg	mindeg
mindegTerm	mirror	monom	monomial?	one?
quasiRegular	quasiRegular?	recip	RemainderList	retract
retractIfCan	rquo	sample	sh	subtractIfCan
trunc	unexpand	varList	zero?	?*?
?**?	?+?	?-?	-?	?=?
?^?	?~=?			

— domain XRPOLY XRecursivePolynomial —

```
)abbrev domain XRPOLY XRecursivePolynomial
++ Author: Michel Petitot petitot@lifl.fr
++ Date Created: 91
++ Date Last Updated: 7 Juillet 92
++ Fix History: compilation v 2.1 le 13 dec 98
++   extend renomme en expand
++ Basic Functions:
++ Related Constructors:
++ Also See:
++ AMS Classifications:
++ Keywords:
++ References:
++ Description:
++ This type supports multivariate polynomials whose variables do not commute.
++ The representation is recursive. The coefficient ring may be
++ non-commutative. Coefficients and variables commute.
```

```
XRecursivePolynomial(VarSet:OrderedSet,R:Ring):  Xcat == Xdef where
  I      ==> Integer
  NNI    ==> NonNegativeInteger
  XDPOLY ==> XDistributedPolynomial(VarSet, R)
  EX     ==> OutputForm
  WORD   ==> OrderedFreeMonoid(VarSet)
  TERM   ==> Record(k:VarSet , c:%)
  LTERMS ==> List(TERM)
  REGPOLY==> FreeModule1(%, VarSet)
  VPOLY  ==> Record(c0:R, reg:REGPOLY)

  Xcat == XPolynomialsCat(VarSet,R) with
       expand: % -> XDPOLY
         ++ \spad{expand(p)} returns \spad{p} in distributed form.
       unexpand : XDPOLY -> %
         ++ \spad{unexpand(p)} returns \spad{p} in recursive form.
       RemainderList: % -> LTERMS
         ++ \spad{RemainderList(p)} returns the regular part of \spad{p}
         ++ as a list of terms.

  Xdef == add
       import(VPOLY)

    -- representation
       Rep     := Union(R,VPOLY)

    -- local functions
       construct: LTERMS -> REGPOLY
       simplifie: VPOLY -> %
       lquo1: (LTERMS,LTERMS) -> %        -- a ajouter
       coef1: (LTERMS,LTERMS) -> R        -- a ajouter
       outForm: REGPOLY -> EX

    --define
       construct(lt) == lt pretend REGPOLY
       p1:%  =  p2:%  ==
         p1 case R =>
             p2 case R => p1 =$R p2
             false
         p2 case R => false
         p1.c0 =$R p2.c0 and p1.reg =$REGPOLY p2.reg

       monom(w, r) ==
         r =0 => 0
         r * w::%

--       if R has Field then                  -- Bug non resolu !!!!!!!!
--         p:% / r: R == inv(r) * p
```

```
rquo(p1:%, p2:%):% ==
  p2 case R => p1 * p2::R
  p1 case R => p1  * p2.c0
  x:REGPOLY := construct [[t.k, a]$TERM for t in listOfTerms(p1.reg) _
                 | (a:= rquo(t.c,p2)) ^= 0$% ]$LTERMS
  simplifie [coef(p1,p2) , x]$VPOLY

trunc(p,n) ==
  n = 0 or (p case R) => (constant p)::%
  n1: NNI := (n-1)::NNI
  lt: LTERMS := [[t.k, r]$TERM for t in listOfTerms p.reg _
                | (r := trunc(t.c, n1)) ^= 0]$LTERMS
  x: REGPOLY := construct lt
  simplifie [constant p, x]$VPOLY

unexpand p ==
  constant? p => (constant p)::%
  vl: List VarSet := sort((y,z) +-> y > z, varList p)
  x : REGPOLY := _
    construct [[v, unexpand r]$TERM for v in vl| (r:=lquo(p,v)) ^= 0]
  [constant p, x]$VPOLY

if R has CommutativeRing then
  sh(p:%, n:NNI):% ==
     n = 0 => 1
     p case R => (p::R)** n
     n1: NNI := (n-1)::NNI
     p1: % := n * sh(p, n1)
     lt: LTERMS := [[t.k, sh(t.c, p1)]$TERM for t in listOfTerms p.reg]
     [p.c0 ** n, construct lt]$VPOLY

  sh(p1:%, p2:%) ==
     p1 case R => p1::R * p2
     p2 case R => p1 * p2::R
     lt1:LTERMS := listOfTerms p1.reg ; lt2:LTERMS := listOfTerms p2.reg
     x: REGPOLY := construct [[t.k,sh(t.c,p2)]$TERM for t in lt1]
     y: REGPOLY := construct [[t.k,sh(p1,t.c)]$TERM for t in lt2]
     [p1.c0*p2.c0,x + y]$VPOLY

RemainderList p ==
    p case R => []
    listOfTerms( p.reg)$REGPOLY

lquo(p1:%,p2:%):% ==
  p2 case R => p1 * p2
  p1 case R => p1  *$R p2.c0
  p1 * p2.c0 +$% lquo1(listOfTerms p1.reg, listOfTerms p2.reg)

lquo1(x:LTERMS,y:LTERMS):% ==
  null x => 0$%
```

```
  null y => 0$%
  x.first.k < y.first.k => lquo1(x,y.rest)
  x.first.k = y.first.k =>
      lquo(x.first.c,y.first.c) + lquo1(x.rest,y.rest)
  return lquo1(x.rest,y)

coef(p1:%, p2:%):R ==
  p1 case R => p1::R * constant p2
  p2 case R => p1.c0 * p2::R
  p1.c0 * p2.c0 +$R coef1(listOfTerms p1.reg, listOfTerms p2.reg)

coef1(x:LTERMS,y:LTERMS):R ==
  null x => 0$R
  null y => 0$R
  x.first.k < y.first.k => coef1(x,y.rest)
  x.first.k = y.first.k =>
      coef(x.first.c,y.first.c) + coef1(x.rest,y.rest)
  return coef1(x.rest,y)

------------------------------------------------------------
outForm(p:REGPOLY): EX ==
   le : List EX :=  [t.k::EX * t.c::EX for t in listOfTerms p]
   reduce(_+, reverse_! le)$List(EX)

coerce(p:$): EX ==
   p case R => (p::R)::EX
   p.c0 = 0 => outForm p.reg
   p.c0::EX + outForm p.reg

0 == 0$R::%
1 == 1$R::%
constant? p ==  p case R
constant p ==
   p case R => p
   p.c0

simplifie p ==
  p.reg = 0$REGPOLY => (p.c0)::%
  p

coerce (v:VarSet):% ==
  [0$R,coerce(v)$REGPOLY]$VPOLY

coerce (r:R):% == r::%
coerce (n:Integer) == n::R::%
coerce (w:WORD) ==
  w = 1 => 1$R
  (first w) * coerce(rest w)

expand p ==
```

```
    p case R => p::R::XDPOLY
    lt:LTERMS := listOfTerms(p.reg)
    ep:XDPOLY := (p.c0)::XDPOLY
    for t in lt repeat
      ep:= ep + t.k * expand(t.c)
    ep

  - p:% ==
    p case R => -$R p
    [- p.c0, - p.reg]$VPOLY

  p1 + p2 ==
    p1 case R and p2 case R => p1 +$R p2
    p1 case R => [p1 + p2.c0 , p2.reg]$VPOLY
    p2 case R => [p2 + p1.c0 , p1.reg]$VPOLY
    simplifie [p1.c0 + p2.c0 , p1.reg +$REGPOLY p2.reg]$VPOLY

  p1 - p2 ==
    p1 case R and p2 case R => p1 -$R p2
    p1 case R => [p1 - p2.c0 , -p2.reg]$VPOLY
    p2 case R => [p1.c0 - p2 , p1.reg]$VPOLY
    simplifie [p1.c0 - p2.c0 , p1.reg -$REGPOLY p2.reg]$VPOLY

  n:Integer * p:% ==
    n=0 => 0$%
    p case R => n *$R p
    -- [ n*p.c0,n*p.reg]$VPOLY
    simplifie [ n*p.c0,n*p.reg]$VPOLY

  r:R * p:% ==
    r=0 => 0$%
    p case R => r *$R p
    -- [ r*p.c0,r*p.reg]$VPOLY
    simplifie [ r*p.c0,r*p.reg]$VPOLY

  p:% * r:R ==
    r=0 => 0$%
    p case R => p *$R r
    -- [ p.c0 * r,p.reg * r]$VPOLY
    simplifie [ r*p.c0,r*p.reg]$VPOLY

  v:VarSet * p:% ==
     p = 0 => 0$%
     [0$R, v *$REGPOLY p]$VPOLY

  p1:% * p2:% ==
    p1 case R => p1::R * p2
    p2 case R => p1 * p2::R
    x:REGPOLY := p1.reg *$REGPOLY p2
    y:REGPOLY := (p1.c0)::% *$REGPOLY p2.reg  -- maladroit:(p1.c0)::% !!
```

```
  -- [ p1.c0 * p2.c0 , x+y ]$VPOLY
  simplifie [ p1.c0 * p2.c0 , x+y ]$VPOLY

lquo(p:%, v:VarSet):% ==
  p case R => 0
  coefficient(p.reg,v)$REGPOLY

lquo(p:%, w:WORD):% ==
  w = 1$WORD => p
  lquo(lquo(p,first w),rest w)

rquo(p:%, v:VarSet):% ==
  p case R => 0
  x:REGPOLY := construct [[t.k, a]$TERM for t in listOfTerms(p.reg)
                  | (a:= rquo(t.c,v)) ^= 0 ]
  simplifie [constant(coefficient(p.reg,v)) , x]$VPOLY

rquo(p:%, w:WORD):% ==
  w = 1$WORD => p
  rquo(rquo(p,rest w),first w)

coef(p:%, w:WORD):R ==
  constant lquo(p,w)

quasiRegular? p ==
  p case R => p = 0$R
  p.c0 = 0$R

quasiRegular p ==
  p case R => 0$%
  [0$R,p.reg]$VPOLY

characteristic == characteristic()$R
recip p ==
  p case R => recip(p::R)
  "failed"

mindeg p ==
  p case R =>
    p = 0 => error "XRPOLY.mindeg: polynome nul !!"
    1$WORD
  p.c0 ^= 0 => 1$WORD
  "min"/[(t.k) *$WORD mindeg(t.c) for t in listOfTerms p.reg]

maxdeg p ==
  p case R =>
     p = 0 => error "XRPOLY.maxdeg: polynome nul !!"
     1$WORD
  "max"/[(t.k) *$WORD maxdeg(t.c) for t in listOfTerms p.reg]
```

```
        degree p ==
           p = 0 => error "XRPOLY.degree: polynome nul !!"
           length(maxdeg p)

        map(fn,p) ==
          p case R => fn(p::R)
          x:REGPOLY := construct [[t.k,a]$TERM for t in listOfTerms p.reg
                         |(a := map(fn,t.c)) ^= 0$R]
          simplifie [fn(p.c0),x]$VPOLY

        varList p ==
          p case R => []
          lv: List VarSet := "setUnion"/[varList(t.c) for t in listOfTerms p.reg]
          lv:= setUnion(lv,[t.k for t in listOfTerms p.reg])
          sort_!(lv)
```

———-

— **XRPOLY.dotabb** —

```
"XRPOLY" [color="#88FF44",href="bookvol10.3.pdf#nameddest=XRPOLY"]
"XPOLYC" [color="#4488FF",href="bookvol10.2.pdf#nameddest=XPOLYC"]
"XRPOLY" -> "XPOLYC"
```

———-

Chapter 26

Chapter Y

Chapter 27

Chapter Z

Chapter 28

The bootstrap code

28.1 BOOLEAN.lsp

BOOLEAN depends on **ORDSET** which depends on **SETCAT** which depends on **BASTYPE** which depends on **BOOLEAN**. We need to break this cycle to build the algebra. So we keep a cached copy of the translated BOOLEAN domain which we can write into the **MID** directory. We compile the lisp code and copy the **BOOLEAN.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

— **BOOLEAN.lsp BOOTSTRAP** —

```
(|/VERSIONCHECK| 2)

(PUT
  (QUOTE |BOOLEAN;test;2$;1|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM (|a|) |a|)))

(DEFUN |BOOLEAN;test;2$;1| (|a| |$|) |a|)

(DEFUN |BOOLEAN;nt| (|b| |$|)
  (COND (|b| (QUOTE NIL))
  ((QUOTE T) (QUOTE T))))

(PUT
  (QUOTE |BOOLEAN;true;$;3|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL (QUOTE T))))

(DEFUN |BOOLEAN;true;$;3| (|$|)
  (QUOTE T))

(PUT
```

```
  (QUOTE |BOOLEAN;false;$;4|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL NIL)))

(DEFUN |BOOLEAN;false;$;4| (|$|) NIL)

(DEFUN |BOOLEAN;not;2$;5| (|b| |$|)
  (COND
    (|b| (QUOTE NIL))
    ((QUOTE T) (QUOTE T))))

(DEFUN |BOOLEAN;^;2$;6| (|b| |$|)
  (COND
    (|b| (QUOTE NIL))
    ((QUOTE T) (QUOTE T))))

(DEFUN |BOOLEAN;~;2$;7| (|b| |$|)
  (COND
    (|b| (QUOTE NIL))
    ((QUOTE T) (QUOTE T))))

(DEFUN |BOOLEAN;and;3$;8| (|a| |b| |$|)
  (COND
    (|a| |b|)
    ((QUOTE T) (QUOTE NIL))))

(DEFUN |BOOLEAN;/\;3$;9| (|a| |b| |$|)
  (COND
    (|a| |b|)
    ((QUOTE T) (QUOTE NIL))))

(DEFUN |BOOLEAN;or;3$;10| (|a| |b| |$|)
  (COND
    (|a| (QUOTE T))
    ((QUOTE T) |b|)))

(DEFUN |BOOLEAN;\/;3$;11| (|a| |b| |$|)
  (COND
    (|a| (QUOTE T))
    ((QUOTE T) |b|)))

(DEFUN |BOOLEAN;xor;3$;12| (|a| |b| |$|)
  (COND
    (|a| (|BOOLEAN;nt| |b| |$|))
    ((QUOTE T) |b|)))

(DEFUN |BOOLEAN;nor;3$;13| (|a| |b| |$|)
  (COND
    (|a| (QUOTE NIL))
    ((QUOTE T) (|BOOLEAN;nt| |b| |$|))))
```

```
(DEFUN |BOOLEAN;nand;3$;14| (|a| |b| |$|)
  (COND
    (|a| (|BOOLEAN;nt| |b| |$|))
    ((QUOTE T) (QUOTE T))))

(PUT
  (QUOTE |BOOLEAN;=;3$;15|)
  (QUOTE |SPADreplace|)
  (QUOTE |BooleanEquality|))

(DEFUN |BOOLEAN;=;3$;15| (|a| |b| |$|)
  (|BooleanEquality| |a| |b|))

(DEFUN |BOOLEAN;implies;3$;16| (|a| |b| |$|)
  (COND
    (|a| |b|)
    ((QUOTE T) (QUOTE T))))

(DEFUN |BOOLEAN;<;3$;17| (|a| |b| |$|)
  (COND
    (|b|
      (COND
        (|a| (QUOTE NIL))
        ((QUOTE T) (QUOTE T))))
    ((QUOTE T) (QUOTE NIL))))

(PUT
  (QUOTE |BOOLEAN;size;Nni;18|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL 2)))

(DEFUN |BOOLEAN;size;Nni;18| (|$|) 2)

(DEFUN |BOOLEAN;index;Pi$;19| (|i| |$|)
  (COND
    ((SPADCALL |i| (QREFELT |$| 26)) (QUOTE NIL))
    ((QUOTE T) (QUOTE T))))

(DEFUN |BOOLEAN;lookup;$Pi;20| (|a| |$|)
  (COND
    (|a| 1)
    ((QUOTE T) 2)))

(DEFUN |BOOLEAN;random;$;21| (|$|)
  (COND
    ((SPADCALL (|random|) (QREFELT |$| 26)) (QUOTE NIL))
    ((QUOTE T) (QUOTE T))))

(DEFUN |BOOLEAN;convert;$If;22| (|x| |$|)
```

```
  (COND
    (|x| (SPADCALL (SPADCALL "true" (QREFELT |$| 33)) (QREFELT |$| 35)))
    ((QUOTE T)
      (SPADCALL (SPADCALL "false" (QREFELT |$| 33)) (QREFELT |$| 35)))))

(DEFUN |BOOLEAN;coerce;$Of;23| (|x| |$|)
  (COND
    (|x| (SPADCALL "true" (QREFELT |$| 38)))
    ((QUOTE T) (SPADCALL "false" (QREFELT |$| 38)))))

(DEFUN |Boolean| ()
  (PROG ()
    (RETURN
      (PROG (G82461)
        (RETURN
          (COND
            ((LETT G82461 (HGET |$ConstructorCache| '|Boolean|)
                   |Boolean|)
             (|CDRwithIncrement| (CDAR G82461)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|Boolean|
                                   (LIST
                                    (CONS NIL (CONS 1 (|Boolean;|)))))))
                 (LETT G82461 T |Boolean|))
               (COND
                 ((NOT G82461) (HREM |$ConstructorCache| '|Boolean|)))))))))))

(DEFUN |Boolean;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|Boolean|) |Boolean|)
        (LETT $ (make-array 41) |Boolean|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL) |Boolean|))
        (|haddProp| |$ConstructorCache| '|Boolean| NIL (CONS 1 $))
        (|stuffDomainSlots| $)
        $))))

(setf (get
  (QUOTE |Boolean|)
  (QUOTE |infovec|))
    (LIST
      (QUOTE
        #(NIL NIL NIL NIL NIL NIL
          (|Boolean|)
          |BOOLEAN;test;2$;1|
          (CONS IDENTITY
```

```
      (FUNCALL (|dispatchFunction| |BOOLEAN;true;$;3|) |$|))
    (CONS IDENTITY
      (FUNCALL (|dispatchFunction| |BOOLEAN;false;$;4|) |$|))
    |BOOLEAN;not;2$;5|
    |BOOLEAN;^;2$;6|
    |BOOLEAN;~;2$;7|
    |BOOLEAN;and;3$;8|
    |BOOLEAN;/\\;3$;9|
    |BOOLEAN;or;3$;10|
    |BOOLEAN;\\/;3$;11|
    |BOOLEAN;xor;3$;12|
    |BOOLEAN;nor;3$;13|
    |BOOLEAN;nand;3$;14|
    |BOOLEAN;=;3$;15|
    |BOOLEAN;implies;3$;16|
    |BOOLEAN;<;3$;17|
    (|NonNegativeInteger|)
    |BOOLEAN;size;Nni;18|
    (|Integer|)
    (0 . |even?|)
    (|PositiveInteger|)
    |BOOLEAN;index;Pi$;19|
    |BOOLEAN;lookup;$Pi;20|
    |BOOLEAN;random;$;21|
    (|String|)
    (|Symbol|)
    (5 . |coerce|)
    (|InputForm|)
    (10 . |convert|)
    |BOOLEAN;convert;$If;22|
    (|OutputForm|)
    (15 . |message|)
    |BOOLEAN;coerce;$Of;23|
    (|SingleInteger|)))
(QUOTE
   #(|~=| 20 |~| 26 |xor| 31 |true| 37 |test| 41 |size| 46 |random| 50
     |or| 54 |not| 60 |nor| 65 |nand| 71 |min| 77 |max| 83 |lookup| 89
     |latex| 94 |index| 99 |implies| 104 |hash| 110 |false| 115
     |convert| 119 |coerce| 124 |and| 129 |^| 135 |\\/| 140 |>=| 146
     |>| 152 |=| 158 |<=| 164 |<| 170 |/\\| 176))
(QUOTE NIL)
(CONS
  (|makeByteWordVec2| 1 (QUOTE (0 0 0 0 0 0 0)))
  (CONS
    (QUOTE
      #(|OrderedSet&| NIL |Logic&| |SetCategory&| NIL |BasicType&| NIL))
    (CONS
      (QUOTE
        #((|OrderedSet|)
          (|Finite|)
```

```
              (|Logic|)
              (|SetCategory|)
              (|ConvertibleTo| 34)
              (|BasicType|)
              (|CoercibleTo| 37)))
           (|makeByteWordVec2|
             40
             (QUOTE
               (1 25 6 0 26 1 32 0 31 33 1 34 0 32 35 1 37 0 31 38 2 0 6 0 0
                1 1 0 0 0 12 2 0 0 0 0 17 0 0 0 8 1 0 6 0 7 0 0 23 24 0 0 0
                30 2 0 0 0 0 15 1 0 0 0 10 2 0 0 0 0 18 2 0 0 0 0 19 2 0 0 0
                0 1 2 0 0 0 0 1 1 0 27 0 29 1 0 31 0 1 1 0 0 27 28 2 0 0 0 0
                21 1 0 40 0 1 0 0 0 9 1 0 34 0 36 1 0 37 0 39 2 0 0 0 0 13 1
                0 0 0 11 2 0 0 0 0 16 2 0 6 0 0 1 2 0 6 0 0 1 2 0 6 0 0 20 2
                0 6 0 0 1 2 0 6 0 0 22 2 0 0 0 0 14))))))
      (QUOTE |lookupComplete|)))

(setf (get (QUOTE |Boolean|) (QUOTE NILADIC)) T)
```

———-

28.2 CHAR.lsp BOOTSTRAP

CHAR depends on a chain of files. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **CHAR** category which we can write into the **MID** directory. We compile the lisp code and copy the **CHAR.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— CHAR.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT (QUOTE |CHAR;=;2$B;1|) (QUOTE |SPADreplace|) (QUOTE EQL))

(DEFUN |CHAR;=;2$B;1| (|a| |b| |$|) (EQL |a| |b|))

(PUT (QUOTE |CHAR;<;2$B;2|) (QUOTE |SPADreplace|) (QUOTE QSLESSP))

(DEFUN |CHAR;<;2$B;2| (|a| |b| |$|) (QSLESSP |a| |b|))

(PUT (QUOTE |CHAR;size;Nni;3|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL 256)))

(DEFUN |CHAR;size;Nni;3| (|$|) 256)
```

```
(DEFUN |CHAR;index;Pi$;4| (|n| |$|) (SPADCALL (|-| |n| 1) (QREFELT |$| 18)))

(DEFUN |CHAR;lookup;$Pi;5| (|c| $)
  (PROG (G90919)
    (RETURN
      (PROG1 (LETT G90919 (+ 1 (SPADCALL |c| (QREFELT $ 21)))
                   |CHAR;lookup;$Pi;5|)
        (|check-subtype| (> G90919 0) '(|PositiveInteger|) G90919)))))

(DEFUN |CHAR;char;I$;6| (|n| |$|) (SPADCALL |n| (QREFELT |$| 23)))

(PUT (QUOTE |CHAR;ord;$I;7|) (QUOTE |SPADreplace|) (QUOTE (XLAM (|c|) |c|)))

(DEFUN |CHAR;ord;$I;7| (|c| |$|) |c|)

(DEFUN |CHAR;random;$;8| (|$|)
 (SPADCALL (REMAINDER2 (|random|) (SPADCALL (QREFELT |$| 16)))
           (QREFELT |$| 18)))

(PUT (QUOTE |CHAR;space;$;9|)
 (QUOTE |SPADreplace|) (QUOTE (XLAM NIL (QENUM "   " 0))))

(DEFUN |CHAR;space;$;9| (|$|) (QENUM "   " 0))

(PUT (QUOTE |CHAR;quote;$;10|)
 (QUOTE |SPADreplace|) (QUOTE (XLAM NIL (QENUM "\" " 0))))

(DEFUN |CHAR;quote;$;10| (|$|) (QENUM "\" " 0))

(PUT (QUOTE |CHAR;escape;$;11|)
 (QUOTE |SPADreplace|) (QUOTE (XLAM NIL (QENUM "_ " 0))))

(DEFUN |CHAR;escape;$;11| (|$|) (QENUM "_ " 0))

(DEFUN |CHAR;coerce;$Of;12| (|c| |$|)
 (ELT (QREFELT |$| 10)
      (|+| (QREFELT |$| 11) (SPADCALL |c| (QREFELT |$| 21)))))

(DEFUN |CHAR;digit?;$B;13| (|c| |$|)
 (SPADCALL |c| (|spadConstant| |$| 31) (QREFELT |$| 33)))

(DEFUN |CHAR;hexDigit?;$B;14| (|c| |$|)
 (SPADCALL |c| (|spadConstant| |$| 35) (QREFELT |$| 33)))

(DEFUN |CHAR;upperCase?;$B;15| (|c| |$|)
 (SPADCALL |c| (|spadConstant| |$| 37) (QREFELT |$| 33)))

(DEFUN |CHAR;lowerCase?;$B;16| (|c| |$|)
 (SPADCALL |c| (|spadConstant| |$| 39) (QREFELT |$| 33)))
```

```
(DEFUN |CHAR;alphabetic?;$B;17| (|c| |$|)
 (SPADCALL |c| (|spadConstant| |$| 41) (QREFELT |$| 33)))

(DEFUN |CHAR;alphanumeric?;$B;18| (|c| |$|)
 (SPADCALL |c| (|spadConstant| |$| 43) (QREFELT |$| 33)))

(DEFUN |CHAR;latex;$S;19| (|c| |$|)
 (STRCONC "\\mbox{`" (STRCONC (|MAKE-FULL-CVEC| 1 |c|) "'}")))

(DEFUN |CHAR;char;S$;20| (|s| |$|)
 (COND
  ((EQL (QCSIZE |s|) 1)
    (SPADCALL |s| (SPADCALL |s| (QREFELT |$| 47)) (QREFELT |$| 48)))
  ((QUOTE T) (|error| "String is not a single character"))))

(DEFUN |CHAR;upperCase;2$;21| (|c| |$|)
 (QENUM (PNAME (UPCASE (code-char (SPADCALL |c| (QREFELT |$| 21))))) 0))

(DEFUN |CHAR;lowerCase;2$;22| (|c| |$|)
 (QENUM (PNAME (DOWNCASE (code-char (SPADCALL |c| (QREFELT |$| 21))))) 0))

(DEFUN |Character| ()
  (PROG ()
    (RETURN
      (PROG (G90941)
        (RETURN
          (COND
            ((LETT G90941 (HGET |$ConstructorCache| '|Character|)
                  |Character|)
             (|CDRwithIncrement| (CDAR G90941)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|Character|
                                   (LIST
                                    (CONS NIL (CONS 1 (|Character;|))))))
                 (LETT G90941 T |Character|))
               (COND
                ((NOT G90941) (HREM |$ConstructorCache| '|Character|)))))))))))

(DEFUN |Character;| ()
  (PROG (|dv$| $ |pv$| G90939 |i|)
    (RETURN
      (SEQ (PROGN
            (LETT |dv$| '(|Character|) |Character|)
            (LETT $ (make-array 53) |Character|)
            (QSETREFV $ 0 |dv$|)
            (QSETREFV $ 3
                (LETT |pv$| (|buildPredVector| 0 0 NIL) |Character|))
            (|haddProp| |$ConstructorCache| '|Character| NIL
                (CONS 1 $))
```

```
            (|stuffDomainSlots| $)
            (QSETREFV $ 6 (|SingleInteger|))
            (QSETREFV $ 10
                (SPADCALL
                    (PROGN
                      (LETT G90939 NIL |Character|)
                      (SEQ (LETT |i| 0 |Character|) G190
                           (COND ((QSGREATERP |i| 255) (GO G191)))
                           (SEQ (EXIT (LETT G90939
                                       (CONS (code-char |i|) G90939)
                                       |Character|)))
                           (LETT |i| (QSADD1 |i|) |Character|)
                           (GO G190) G191 (EXIT (NREVERSE0 G90939))))
                    (QREFELT $ 9)))
            (QSETREFV $ 11 0)
            $)))))

(setf (get (QUOTE |Character|) (QUOTE |infovec|))
 (LIST (QUOTE
  #(NIL NIL NIL NIL NIL NIL (QUOTE |Rep|) (|List| 28) (|PrimitiveArray| 28)
   (0 . |construct|) (QUOTE |OutChars|) (QUOTE |minChar|) (|Boolean|)
   |CHAR;=;2$B;1| |CHAR;<;2$B;2| (|NonNegativeInteger|) |CHAR;size;Nni;3|
   (|Integer|) |CHAR;char;I$;6| (|PositiveInteger|) |CHAR;index;Pi$;4|
   |CHAR;ord;$I;7| |CHAR;lookup;$Pi;5| (5 . |coerce|) |CHAR;random;$;8|
   |CHAR;space;$;9| |CHAR;quote;$;10| |CHAR;escape;$;11| (|OutputForm|)
   |CHAR;coerce;$Of;12| (|CharacterClass|) (10 . |digit|) (|Character|)
   (14 . |member?|) |CHAR;digit?;$B;13| (20 . |hexDigit|)
   |CHAR;hexDigit?;$B;14| (24 . |upperCase|) |CHAR;upperCase?;$B;15|
   (28 . |lowerCase|) |CHAR;lowerCase?;$B;16| (32 . |alphabetic|)
   |CHAR;alphabetic?;$B;17| (36 . |alphanumeric|) |CHAR;alphanumeric?;$B;18|
   (|String|) |CHAR;latex;$S;19| (40 . |minIndex|) (45 . |elt|)
   |CHAR;char;S$;20| |CHAR;upperCase;2$;21| |CHAR;lowerCase;2$;22|
   (|SingleInteger|))) (QUOTE #(|~=| 51 |upperCase?| 57 |upperCase| 62
   |space| 67 |size| 71 |random| 75 |quote| 79 |ord| 83 |min| 88 |max| 94
   |lowerCase?| 100 |lowerCase| 105 |lookup| 110 |latex| 115 |index| 120
   |hexDigit?| 125 |hash| 130 |escape| 135 |digit?| 139 |coerce| 144 |char|
   149 |alphanumeric?| 159 |alphabetic?| 164 |>=| 169 |>| 175 |=| 181 |<=|
   187 |<| 193)) (QUOTE NIL)
   (CONS
    (|makeByteWordVec2| 1 (QUOTE (0 0 0 0 0 0)))
    (CONS
     (QUOTE #(NIL |OrderedSet&| NIL |SetCategory&| |BasicType&| NIL))
     (CONS
      (QUOTE #((|OrderedFinite|) (|OrderedSet|) (|Finite|) (|SetCategory|)
               (|BasicType|) (|CoercibleTo| 28)))
       (|makeByteWordVec2| 52
        (QUOTE (1 8 0 7 9 1 6 0 17 23 0 30 0 31 2 30 12 32 0 33 0 30 0 35
                0 30 0 37 0 30 0 39 0 30 0 41 0 30 0 43 1 45 17 0 47 2 45
                32 0 17 48 2 0 12 0 0 1 1 0 12 0 38 1 0 0 0 50 0 0 0 25 0
                0 15 16 0 0 0 24 0 0 0 26 1 0 17 0 21 2 0 0 0 0 1 2 0 0 0
```

```
              0 1 1 0 12 0 40 1 0 0 0 51 1 0 19 0 22 1 0 45 0 46 1 0 0 19
              20 1 0 12 0 36 1 0 52 0 1 0 0 0 27 1 0 12 0 34 1 0 28 0 29
              1 0 0 45 49 1 0 0 17 18 1 0 12 0 44 1 0 12 0 42 2 0 12 0 0
              1 2 0 12 0 0 1 2 0 12 0 0 13 2 0 12 0 0 1 2 0 12 0 0 14))))))
  (QUOTE |lookupComplete|)))

(setf (get (QUOTE |Character|) (QUOTE NILADIC)) T)
```

———-

28.3 DFLOAT.lsp BOOTSTRAP

DFLOAT depends on itself. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **DFLOAT** category which we can write into the **MID** directory. We compile the lisp code and copy the **DFLOAT.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— DFLOAT.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(DEFUN |DFLOAT;OMwrite;$S;1| (|x| |$|)
 (PROG (|sp| |dev| |s|)
  (RETURN
   (SEQ
    (LETT |s| "" |DFLOAT;OMwrite;$S;1|)
    (LETT |sp| (|OM-STRINGTOSTRINGPTR| |s|) |DFLOAT;OMwrite;$S;1|)
    (LETT |dev|
     (SPADCALL |sp| (SPADCALL (QREFELT |$| 7)) (QREFELT |$| 10))
     |DFLOAT;OMwrite;$S;1|)
    (SPADCALL |dev| (QREFELT |$| 12))
    (SPADCALL |dev| |x| (QREFELT |$| 14))
    (SPADCALL |dev| (QREFELT |$| 15))
    (SPADCALL |dev| (QREFELT |$| 16))
    (LETT |s| (|OM-STRINGPTRTOSTRING| |sp|) |DFLOAT;OMwrite;$S;1|)
    (EXIT |s|)))))

(DEFUN |DFLOAT;OMwrite;$BS;2| (|x| |wholeObj| |$|)
 (PROG (|sp| |dev| |s|)
  (RETURN
   (SEQ
    (LETT |s| "" |DFLOAT;OMwrite;$BS;2|)
    (LETT |sp| (|OM-STRINGTOSTRINGPTR| |s|) |DFLOAT;OMwrite;$BS;2|)
    (LETT |dev|
     (SPADCALL |sp| (SPADCALL (QREFELT |$| 7)) (QREFELT |$| 10))
     |DFLOAT;OMwrite;$BS;2|)
```

```
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 12))))
    (SPADCALL |dev| |x| (QREFELT |$| 14))
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 15))))
    (SPADCALL |dev| (QREFELT |$| 16))
    (LETT |s| (|OM-STRINGPTRTOSTRING| |sp|) |DFLOAT;OMwrite;$BS;2|)
    (EXIT |s|)))))

(DEFUN |DFLOAT;OMwrite;Omd$V;3| (|dev| |x| |$|)
 (SEQ
  (SPADCALL |dev| (QREFELT |$| 12))
  (SPADCALL |dev| |x| (QREFELT |$| 14))
  (EXIT (SPADCALL |dev| (QREFELT |$| 15)))))

(DEFUN |DFLOAT;OMwrite;Omd$BV;4| (|dev| |x| |wholeObj| |$|)
 (SEQ
  (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 12))))
  (SPADCALL |dev| |x| (QREFELT |$| 14))
  (EXIT (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 15)))))))

(PUT (QUOTE |DFLOAT;checkComplex|) (QUOTE |SPADreplace|) (QUOTE |C-TO-R|))

(DEFUN |DFLOAT;checkComplex| (|x| |$|) (|C-TO-R| |x|))

(PUT
 (QUOTE |DFLOAT;base;Pi;6|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL (|FLOAT-RADIX| 0.0))))

(DEFUN |DFLOAT;base;Pi;6| (|$|) (|FLOAT-RADIX| 0.0))

(DEFUN |DFLOAT;mantissa;$I;7| (|x| |$|) (QCAR (|DFLOAT;manexp| |x| |$|)))

(DEFUN |DFLOAT;exponent;$I;8| (|x| |$|) (QCDR (|DFLOAT;manexp| |x| |$|)))

(PUT
 (QUOTE |DFLOAT;precision;Pi;9|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL (|FLOAT-DIGITS| 0.0))))

(DEFUN |DFLOAT;precision;Pi;9| (|$|) (|FLOAT-DIGITS| 0.0))

(DEFUN |DFLOAT;bits;Pi;10| ($)
  (PROG (G105705)
    (RETURN
      (COND
        ((EQL (FLOAT-RADIX 0.0) 2) (FLOAT-DIGITS 0.0))
        ((EQL (FLOAT-RADIX 0.0) 16) (* 4 (FLOAT-DIGITS 0.0)))
        ('T
         (PROG1 (LETT G105705
                      (truncate (SPADCALL (FLOAT-DIGITS 0.0)
```

```
                                (SPADCALL
                                    (FLOAT (FLOAT-RADIX 0.0)
                                     MOST-POSITIVE-LONG-FLOAT)
                                    (QREFELT $ 28))
                                (QREFELT $ 29)))
                        |DFLOAT;bits;Pi;10|)
          (|check-subtype| (> G105705 0) '(|PositiveInteger|) G105705)))))))

(PUT
 (QUOTE |DFLOAT;max;$;11|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL |MOST-POSITIVE-LONG-FLOAT|)))

(DEFUN |DFLOAT;max;$;11| (|$|) |MOST-POSITIVE-LONG-FLOAT|)

(PUT
 (QUOTE |DFLOAT;min;$;12|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL |MOST-NEGATIVE-LONG-FLOAT|)))

(DEFUN |DFLOAT;min;$;12| (|$|) |MOST-NEGATIVE-LONG-FLOAT|)

(DEFUN |DFLOAT;order;$I;13| (|a| |$|)
 (|-| (|+| (|FLOAT-DIGITS| 0.0) (SPADCALL |a| (QREFELT |$| 26))) 1))

(PUT
 (QUOTE |DFLOAT;Zero;$;14|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL (FLOAT 0 |MOST-POSITIVE-LONG-FLOAT|))))

(DEFUN |DFLOAT;Zero;$;14| (|$|) (FLOAT 0 |MOST-POSITIVE-LONG-FLOAT|))

(PUT
 (QUOTE |DFLOAT;One;$;15|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL (FLOAT 1 |MOST-POSITIVE-LONG-FLOAT|))))

(DEFUN |DFLOAT;One;$;15| (|$|) (FLOAT 1 |MOST-POSITIVE-LONG-FLOAT|))

(DEFUN |DFLOAT;exp1;$;16| (|$|)
 (|/|
  (FLOAT 534625820200 |MOST-POSITIVE-LONG-FLOAT|)
  (FLOAT 196677847971 |MOST-POSITIVE-LONG-FLOAT|)))

(PUT (QUOTE |DFLOAT;pi;$;17|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL PI)))

(DEFUN |DFLOAT;pi;$;17| (|$|) PI)

(DEFUN |DFLOAT;coerce;$Of;18| (|x| |$|) (SPADCALL |x| (QREFELT |$| 39)))
```

```
(DEFUN |DFLOAT;convert;$If;19| (|x| |$|) (SPADCALL |x| (QREFELT |$| 42)))

(PUT (QUOTE |DFLOAT;<;2$B;20|) (QUOTE |SPADreplace|) (QUOTE |<|))

(DEFUN |DFLOAT;<;2$B;20| (|x| |y| |$|) (|<| |x| |y|))

(PUT (QUOTE |DFLOAT;-;2$;21|) (QUOTE |SPADreplace|) (QUOTE |-|))

(DEFUN |DFLOAT;-;2$;21| (|x| |$|) (|-| |x|))

(PUT (QUOTE |DFLOAT;+;3$;22|) (QUOTE |SPADreplace|) (QUOTE |+|))

(DEFUN |DFLOAT;+;3$;22| (|x| |y| |$|) (|+| |x| |y|))

(PUT (QUOTE |DFLOAT;-;3$;23|) (QUOTE |SPADreplace|) (QUOTE |-|))

(DEFUN |DFLOAT;-;3$;23| (|x| |y| |$|) (|-| |x| |y|))

(PUT (QUOTE |DFLOAT;*;3$;24|) (QUOTE |SPADreplace|) (QUOTE |*|))

(DEFUN |DFLOAT;*;3$;24| (|x| |y| |$|) (|*| |x| |y|))

(PUT (QUOTE |DFLOAT;*;I2$;25|) (QUOTE |SPADreplace|) (QUOTE |*|))

(DEFUN |DFLOAT;*;I2$;25| (|i| |x| |$|) (|*| |i| |x|))

(PUT (QUOTE |DFLOAT;max;3$;26|) (QUOTE |SPADreplace|) (QUOTE MAX))

(DEFUN |DFLOAT;max;3$;26| (|x| |y| |$|) (MAX |x| |y|))

(PUT (QUOTE |DFLOAT;min;3$;27|) (QUOTE |SPADreplace|) (QUOTE MIN))

(DEFUN |DFLOAT;min;3$;27| (|x| |y| |$|) (MIN |x| |y|))

(PUT (QUOTE |DFLOAT;=;2$B;28|) (QUOTE |SPADreplace|) (QUOTE |=|))

(DEFUN |DFLOAT;=;2$B;28| (|x| |y| |$|) (|=| |x| |y|))

(PUT (QUOTE |DFLOAT;/;$I$;29|) (QUOTE |SPADreplace|) (QUOTE |/|))

(DEFUN |DFLOAT;/;$I$;29| (|x| |i| |$|) (|/| |x| |i|))

(DEFUN |DFLOAT;sqrt;2$;30| (|x| |$|) (|DFLOAT;checkComplex| (SQRT |x|) |$|))

(DEFUN |DFLOAT;log10;2$;31| (|x| |$|) (|DFLOAT;checkComplex| (|log| |x|) |$|))

(PUT (QUOTE |DFLOAT;**;$I$;32|) (QUOTE |SPADreplace|) (QUOTE EXPT))

(DEFUN |DFLOAT;**;$I$;32| (|x| |i| |$|) (EXPT |x| |i|))
```

```
(DEFUN |DFLOAT;**;3$;33| (|x| |y| |$|)
 (|DFLOAT;checkComplex| (EXPT |x| |y|) |$|))

(PUT
 (QUOTE |DFLOAT;coerce;I$;34|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|i|) (FLOAT |i| |MOST-POSITIVE-LONG-FLOAT|))))

(DEFUN |DFLOAT;coerce;I$;34| (|i| |$|) (FLOAT |i| |MOST-POSITIVE-LONG-FLOAT|))

(PUT (QUOTE |DFLOAT;exp;2$;35|) (QUOTE |SPADreplace|) (QUOTE EXP))

(DEFUN |DFLOAT;exp;2$;35| (|x| |$|) (EXP |x|))

(DEFUN |DFLOAT;log;2$;36| (|x| |$|) (|DFLOAT;checkComplex| (LN |x|) |$|))

(DEFUN |DFLOAT;log2;2$;37| (|x| |$|) (|DFLOAT;checkComplex| (LOG2 |x|) |$|))

(PUT (QUOTE |DFLOAT;sin;2$;38|) (QUOTE |SPADreplace|) (QUOTE SIN))

(DEFUN |DFLOAT;sin;2$;38| (|x| |$|) (SIN |x|))

(PUT (QUOTE |DFLOAT;cos;2$;39|) (QUOTE |SPADreplace|) (QUOTE COS))

(DEFUN |DFLOAT;cos;2$;39| (|x| |$|) (COS |x|))

(PUT (QUOTE |DFLOAT;tan;2$;40|) (QUOTE |SPADreplace|) (QUOTE TAN))

(DEFUN |DFLOAT;tan;2$;40| (|x| |$|) (TAN |x|))

(PUT (QUOTE |DFLOAT;cot;2$;41|) (QUOTE |SPADreplace|) (QUOTE COT))

(DEFUN |DFLOAT;cot;2$;41| (|x| |$|) (COT |x|))

(PUT (QUOTE |DFLOAT;sec;2$;42|) (QUOTE |SPADreplace|) (QUOTE SEC))

(DEFUN |DFLOAT;sec;2$;42| (|x| |$|) (SEC |x|))

(PUT (QUOTE |DFLOAT;csc;2$;43|) (QUOTE |SPADreplace|) (QUOTE CSC))

(DEFUN |DFLOAT;csc;2$;43| (|x| |$|) (CSC |x|))

(DEFUN |DFLOAT;asin;2$;44| (|x| |$|) (|DFLOAT;checkComplex| (ASIN |x|) |$|))

(DEFUN |DFLOAT;acos;2$;45| (|x| |$|) (|DFLOAT;checkComplex| (ACOS |x|) |$|))

(PUT (QUOTE |DFLOAT;atan;2$;46|) (QUOTE |SPADreplace|) (QUOTE ATAN))

(DEFUN |DFLOAT;atan;2$;46| (|x| |$|) (ATAN |x|))
```

```
(DEFUN |DFLOAT;acsc;2$;47| (|x| |$|) (|DFLOAT;checkComplex| (ACSC |x|) |$|))

(PUT (QUOTE |DFLOAT;acot;2$;48|) (QUOTE |SPADreplace|) (QUOTE ACOT))

(DEFUN |DFLOAT;acot;2$;48| (|x| |$|) (ACOT |x|))

(DEFUN |DFLOAT;asec;2$;49| (|x| |$|) (|DFLOAT;checkComplex| (ASEC |x|) |$|))

(PUT (QUOTE |DFLOAT;sinh;2$;50|) (QUOTE |SPADreplace|) (QUOTE SINH))

(DEFUN |DFLOAT;sinh;2$;50| (|x| |$|) (SINH |x|))

(PUT (QUOTE |DFLOAT;cosh;2$;51|) (QUOTE |SPADreplace|) (QUOTE COSH))

(DEFUN |DFLOAT;cosh;2$;51| (|x| |$|) (COSH |x|))

(PUT (QUOTE |DFLOAT;tanh;2$;52|) (QUOTE |SPADreplace|) (QUOTE TANH))

(DEFUN |DFLOAT;tanh;2$;52| (|x| |$|) (TANH |x|))

(PUT (QUOTE |DFLOAT;csch;2$;53|) (QUOTE |SPADreplace|) (QUOTE CSCH))

(DEFUN |DFLOAT;csch;2$;53| (|x| |$|) (CSCH |x|))

(PUT (QUOTE |DFLOAT;coth;2$;54|) (QUOTE |SPADreplace|) (QUOTE COTH))

(DEFUN |DFLOAT;coth;2$;54| (|x| |$|) (COTH |x|))

(PUT (QUOTE |DFLOAT;sech;2$;55|) (QUOTE |SPADreplace|) (QUOTE SECH))

(DEFUN |DFLOAT;sech;2$;55| (|x| |$|) (SECH |x|))

(PUT (QUOTE |DFLOAT;asinh;2$;56|) (QUOTE |SPADreplace|) (QUOTE ASINH))

(DEFUN |DFLOAT;asinh;2$;56| (|x| |$|) (ASINH |x|))

(DEFUN |DFLOAT;acosh;2$;57| (|x| |$|) (|DFLOAT;checkComplex| (ACOSH |x|) |$|))

(DEFUN |DFLOAT;atanh;2$;58| (|x| |$|) (|DFLOAT;checkComplex| (ATANH |x|) |$|))

(PUT (QUOTE |DFLOAT;acsch;2$;59|) (QUOTE |SPADreplace|) (QUOTE ACSCH))

(DEFUN |DFLOAT;acsch;2$;59| (|x| |$|) (ACSCH |x|))

(DEFUN |DFLOAT;acoth;2$;60| (|x| |$|) (|DFLOAT;checkComplex| (ACOTH |x|) |$|))

(DEFUN |DFLOAT;asech;2$;61| (|x| |$|) (|DFLOAT;checkComplex| (ASECH |x|) |$|))

(PUT (QUOTE |DFLOAT;/;3$;62|) (QUOTE |SPADreplace|) (QUOTE |/|))
```

```
(DEFUN |DFLOAT;/;3$;62| (|x| |y| |$|) (|/| |x| |y|))

(PUT (QUOTE |DFLOAT;negative?;$B;63|) (QUOTE |SPADreplace|) (QUOTE MINUSP))

(DEFUN |DFLOAT;negative?;$B;63| (|x| |$|) (MINUSP |x|))

(PUT (QUOTE |DFLOAT;zero?;$B;64|) (QUOTE |SPADreplace|) (QUOTE ZEROP))

(DEFUN |DFLOAT;zero?;$B;64| (|x| |$|) (ZEROP |x|))

(PUT (QUOTE |DFLOAT;hash;$I;65|) (QUOTE |SPADreplace|) (QUOTE SXHASH))

(DEFUN |DFLOAT;hash;$I;65| (|x| |$|) (SXHASH |x|))

(DEFUN |DFLOAT;recip;$U;66| (|x| |$|)
 (COND
  ((ZEROP |x|) (CONS 1 "failed"))
  ((QUOTE T) (CONS 0 (|/| 1.0 |x|)))))

(PUT
 (QUOTE |DFLOAT;differentiate;2$;67|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) 0.0)))

(DEFUN |DFLOAT;differentiate;2$;67| (|x| |$|) 0.0)

(DEFUN |DFLOAT;Gamma;2$;68| (|x| |$|) (SPADCALL |x| (QREFELT |$| 93)))

(DEFUN |DFLOAT;Beta;3$;69| (|x| |y| |$|) (SPADCALL |x| |y| (QREFELT |$| 95)))

(PUT (QUOTE |DFLOAT;wholePart;$I;70|) (QUOTE |SPADreplace|) (QUOTE truncate))

(DEFUN |DFLOAT;wholePart;$I;70| (|x| |$|) (truncate |x|))

(DEFUN |DFLOAT;float;2IPi$;71| (|ma| |ex| |b| |$|)
 (|*| |ma| (EXPT (FLOAT |b| |MOST-POSITIVE-LONG-FLOAT|) |ex|)))

(PUT
 (QUOTE |DFLOAT;convert;2$;72|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) |x|)))

(DEFUN |DFLOAT;convert;2$;72| (|x| |$|) |x|)

(DEFUN |DFLOAT;convert;$F;73| (|x| |$|) (SPADCALL |x| (QREFELT |$| 101)))

(DEFUN |DFLOAT;rationalApproximation;$NniF;74| (|x| |d| |$|)
 (SPADCALL |x| |d| 10 (QREFELT |$| 105)))

(DEFUN |DFLOAT;atan;3$;75| (|x| |y| |$|)
```

```
 (PROG (|theta|)
  (RETURN
   (SEQ
    (COND
     ((|=| |x| 0.0)
      (COND
       ((|<| 0.0 |y|) (|/| PI 2))
       ((|<| |y| 0.0) (|-| (|/| PI 2)))
       ((QUOTE T) 0.0)))
     ((QUOTE T)
      (SEQ
       (LETT |theta|
        (ATAN (|FLOAT-SIGN| 1.0 (|/| |y| |x|)))
        |DFLOAT;atan;3$;75|)
       (COND
        ((|<| |x| 0.0) (LETT |theta| (|-| PI |theta|) |DFLOAT;atan;3$;75|)))
       (COND ((|<| |y| 0.0) (LETT |theta| (|-| |theta|) |DFLOAT;atan;3$;75|)))
       (EXIT |theta|)))))))

(DEFUN |DFLOAT;retract;$F;76| (|x| $)
  (PROG (G105780)
    (RETURN
      (SPADCALL |x|
          (PROG1 (LETT G105780 (- (FLOAT-DIGITS 0.0) 1)
                       |DFLOAT;retract;$F;76|)
            (|check-subtype| (>= G105780 0) '(|NonNegativeInteger|)
                G105780))
          (FLOAT-RADIX 0.0) (QREFELT $ 105)))))

(DEFUN |DFLOAT;retractIfCan;$U;77| (|x| $)
  (PROG (G105785)
    (RETURN
      (CONS 0
            (SPADCALL |x|
                (PROG1 (LETT G105785 (- (FLOAT-DIGITS 0.0) 1)
                             |DFLOAT;retractIfCan;$U;77|)
                  (|check-subtype| (>= G105785 0)
                      '(|NonNegativeInteger|) G105785))
                (FLOAT-RADIX 0.0) (QREFELT $ 105))))))

(DEFUN |DFLOAT;retract;$I;78| (|x| |$|)
 (PROG (|n|)
  (RETURN
   (SEQ
    (LETT |n| (truncate |x|) |DFLOAT;retract;$I;78|)
    (EXIT
     (COND
      ((|=| |x| (FLOAT |n| |MOST-POSITIVE-LONG-FLOAT|)) |n|)
      ((QUOTE T) (|error| "Not an integer")))))))
```

```
(DEFUN |DFLOAT;retractIfCan;$U;79| (|x| |$|)
 (PROG (|n|)
  (RETURN
   (SEQ
    (LETT |n| (truncate |x|) |DFLOAT;retractIfCan;$U;79|)
    (EXIT
     (COND
      ((|=| |x| (FLOAT |n| |MOST-POSITIVE-LONG-FLOAT|)) (CONS 0 |n|))
      ((QUOTE T) (CONS 1 "failed")))))))))

(DEFUN |DFLOAT;sign;$I;80| (|x| |$|)
 (SPADCALL (|FLOAT-SIGN| |x| 1.0) (QREFELT |$| 111)))

(PUT
 (QUOTE |DFLOAT;abs;2$;81|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) (|FLOAT-SIGN| 1.0 |x|))))

(DEFUN |DFLOAT;abs;2$;81| (|x| |$|) (|FLOAT-SIGN| 1.0 |x|))

(DEFUN |DFLOAT;manexp| (|x| $)
  (PROG (|s| G105806 |me| |two53|)
    (RETURN
      (SEQ (EXIT (COND
                  ((ZEROP |x|) (CONS 0 0))
                  ('T
                   (SEQ (LETT |s| (SPADCALL |x| (QREFELT $ 114))
                              |DFLOAT;manexp|)
                        (LETT |x| (FLOAT-SIGN 1.0 |x|)
                              |DFLOAT;manexp|)
                        (COND
                          ((< MOST-POSITIVE-LONG-FLOAT |x|)
                           (PROGN
                             (LETT G105806
                                   (CONS
                                    (+
                                     (* |s|
                                      (SPADCALL
                                       MOST-POSITIVE-LONG-FLOAT
                                       (QREFELT $ 25)))
                                     1)
                                    (SPADCALL MOST-POSITIVE-LONG-FLOAT
                                     (QREFELT $ 26)))
                                   |DFLOAT;manexp|)
                             (GO G105806))))
                        (LETT |me| (MANEXP |x|) |DFLOAT;manexp|)
                        (LETT |two53|
                              (EXPT (FLOAT-RADIX 0.0)
                                    (FLOAT-DIGITS 0.0))
                              |DFLOAT;manexp|)
```

```
                        (EXIT (CONS (* |s|
                                       (truncate (* |two53| (QCAR |me|))))
                                    (- (QCDR |me|) (FLOAT-DIGITS 0.0))))))))
          G105806 (EXIT G105806)))))

(DEFUN |DFLOAT;rationalApproximation;$2NniF;83| (|f| |d| |b| $)
  (PROG (|#G102| |nu| |ex| BASE G105809 |de| |tol| |#G103| |q| |r| |p2|
                 |q2| G105827 |#G104| |#G105| |p0| |p1| |#G106| |#G107|
                 |q0| |q1| |#G108| |#G109| |s| |t| G105825)
    (RETURN
      (SEQ (EXIT (SEQ
       (PROGN
        (LETT |#G102| (|DFLOAT;manexp| |f| $)
                              |DFLOAT;rationalApproximation;$2NniF;83|)
        (LETT |nu| (QCAR |#G102|)
                              |DFLOAT;rationalApproximation;$2NniF;83|)
        (LETT |ex| (QCDR |#G102|)
                              |DFLOAT;rationalApproximation;$2NniF;83|)
        |#G102|)
       (LETT BASE (FLOAT-RADIX 0.0)
                             |DFLOAT;rationalApproximation;$2NniF;83|)
       (EXIT
        (COND
         ((< |ex| 0)
          (SEQ
           (LETT |de|
            (EXPT BASE
             (PROG1
              (LETT G105809 (- |ex|) |DFLOAT;rationalApproximation;$2NniF;83|)
              (|check-subtype| (>= G105809 0) '(|NonNegativeInteger|)
                G105809)))
            |DFLOAT;rationalApproximation;$2NniF;83|)
           (EXIT
            (COND
             ((< |b| 2) (|error| "base must be > 1"))
             (t
              (SEQ
               (LETT |tol| (EXPT |b| |d|)
                  |DFLOAT;rationalApproximation;$2NniF;83|)
               (LETT |s| |nu|
                  |DFLOAT;rationalApproximation;$2NniF;83|)
               (LETT |t| |de|
                  |DFLOAT;rationalApproximation;$2NniF;83|)
               (LETT |p0| 0
                  |DFLOAT;rationalApproximation;$2NniF;83|)
               (LETT |p1| 1
                  |DFLOAT;rationalApproximation;$2NniF;83|)
               (LETT |q0| 1
                  |DFLOAT;rationalApproximation;$2NniF;83|)
               (LETT |q1| 0
```

```
   |DFLOAT;rationalApproximation;$2NniF;83|)
(EXIT
 (SEQ G190 NIL
  (SEQ
   (PROGN
    (LETT |#G103| (DIVIDE2 |s| |t|)
     |DFLOAT;rationalApproximation;$2NniF;83|)
    (LETT |q| (QCAR |#G103|)
     |DFLOAT;rationalApproximation;$2NniF;83|)
    (LETT |r| (QCDR |#G103|)
     |DFLOAT;rationalApproximation;$2NniF;83|)
    |#G103|)
   (LETT |p2| (+ (* |q| |p1|) |p0|)
    |DFLOAT;rationalApproximation;$2NniF;83|)
   (LETT |q2| (+ (* |q| |q1|) |q0|)
    |DFLOAT;rationalApproximation;$2NniF;83|)
   (COND
    ((OR (EQL |r| 0)
      (< (SPADCALL |tol| (ABS (- (* |nu| |q2|) (* |de| |p2|)))
                   (QREFELT $ 118))
                   (* |de| (ABS |p2|))))
     (EXIT
      (PROGN
       (LETT G105827
        (SPADCALL |p2| |q2| (QREFELT $ 117))
        |DFLOAT;rationalApproximation;$2NniF;83|)
       (GO G105827)))))
     (PROGN
      (LETT |#G104| |p1|
       |DFLOAT;rationalApproximation;$2NniF;83|)
      (LETT |#G105| |p2|
       |DFLOAT;rationalApproximation;$2NniF;83|)
      (LETT |p0| |#G104|
       |DFLOAT;rationalApproximation;$2NniF;83|)
      (LETT |p1| |#G105|
       |DFLOAT;rationalApproximation;$2NniF;83|))
      (PROGN
       (LETT |#G106| |q1|
        |DFLOAT;rationalApproximation;$2NniF;83|)
       (LETT |#G107| |q2|
        |DFLOAT;rationalApproximation;$2NniF;83|)
       (LETT |q0| |#G106|
        |DFLOAT;rationalApproximation;$2NniF;83|)
       (LETT |q1| |#G107|
        |DFLOAT;rationalApproximation;$2NniF;83|))
       (EXIT
        (PROGN
         (LETT |#G108| |t|
          |DFLOAT;rationalApproximation;$2NniF;83|)
         (LETT |#G109| |r|
```

```
                        |DFLOAT;rationalApproximation;$2NniF;83|)
                       (LETT |s| |#G108|
                        |DFLOAT;rationalApproximation;$2NniF;83|)
                       (LETT |t| |#G109|
                        |DFLOAT;rationalApproximation;$2NniF;83|))))
                       NIL (GO G190) G191
                       (EXIT NIL)))))))))
        ('T
         (SPADCALL
          (* |nu|
           (EXPT BASE
            (PROG1
             (LETT G105825 |ex| |DFLOAT;rationalApproximation;$2NniF;83|)
             (|check-subtype| (>= G105825 0) '(|NonNegativeInteger|)
                G105825))))
          (QREFELT $ 119)))))))
    G105827
      (EXIT G105827)))))

(DEFUN |DFLOAT;**;$F$;84| (|x| |r| $)
  (PROG (|n| |d| G105837)
    (RETURN
      (SEQ (EXIT (COND
                   ((ZEROP |x|)
                    (COND
                      ((SPADCALL |r| (QREFELT $ 120))
                       (|error| "0**0 is undefined"))
                      ((SPADCALL |r| (QREFELT $ 121))
                       (|error| "division by 0"))
                      ('T 0.0)))
                   ((OR (SPADCALL |r| (QREFELT $ 120))
                        (SPADCALL |x| (QREFELT $ 122)))
                    1.0)
                   ('T
                    (COND
                      ((SPADCALL |r| (QREFELT $ 123)) |x|)
                      ('T
                       (SEQ (LETT |n| (SPADCALL |r| (QREFELT $ 124))
                                  |DFLOAT;**;$F$;84|)
                            (LETT |d| (SPADCALL |r| (QREFELT $ 125))
                                  |DFLOAT;**;$F$;84|)
                            (EXIT (COND
                                    ((MINUSP |x|)
                                     (COND
                                       ((ODDP |d|)
                                        (COND
                                          ((ODDP |n|)
                                           (PROGN
                                             (LETT G105837
                                              (-
```

```
                                                  (SPADCALL (- |x|) |r|
                                                   (QREFELT $ 126)))
                                                  |DFLOAT;**;$F$;84|)
                                                 (GO G105837)))
                                               ('T
                                                (PROGN
                                                 (LETT G105837
                                                  (SPADCALL (- |x|) |r|
                                                   (QREFELT $ 126))
                                                  |DFLOAT;**;$F$;84|)
                                                 (GO G105837)))))
                                            ('T (|error| "negative root"))))
                                          ((EQL |d| 2)
                                           (EXPT
                                            (SPADCALL |x| (QREFELT $ 54))
                                            |n|))
                                          ('T
                                           (SPADCALL |x|
                                            (/
                                             (FLOAT |n|
                                              MOST-POSITIVE-LONG-FLOAT)
                                             (FLOAT |d|
                                              MOST-POSITIVE-LONG-FLOAT))
                                            (QREFELT $ 57)))))))))))
                 G105837 (EXIT G105837)))))

(DEFUN |DoubleFloat| ()
  (PROG ()
    (RETURN
      (PROG (G105850)
        (RETURN
          (COND
            ((LETT G105850 (HGET |$ConstructorCache| '|DoubleFloat|)
                   |DoubleFloat|)
             (|CDRwithIncrement| (CDAR G105850)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|DoubleFloat|
                                   (LIST
                                    (CONS NIL
                                     (CONS 1 (|DoubleFloat;|))))))
                 (LETT G105850 T |DoubleFloat|))
               (COND
                 ((NOT G105850)
                  (HREM |$ConstructorCache| '|DoubleFloat|)))))))))))

(DEFUN |DoubleFloat;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
```

```
        (LETT |dv$| '(|DoubleFloat|) |DoubleFloat|)
        (LETT $ (make-array 140) |DoubleFloat|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL) |DoubleFloat|))
        (|haddProp| |$ConstructorCache| '|DoubleFloat| NIL (CONS 1 $))
        (|stuffDomainSlots| $)
        $))))

(setf (get
 (QUOTE |DoubleFloat|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE #(NIL NIL NIL NIL NIL NIL (|OpenMathEncoding|) (0 . |OMencodingXML|)
  (|String|) (|OpenMathDevice|) (4 . |OMopenString|) (|Void|)
  (10 . |OMputObject|) (|DoubleFloat|) (15 . |OMputFloat|)
  (21 . |OMputEndObject|) (26 . |OMclose|) |DFLOAT;OMwrite;$S;1|
  (|Boolean|) |DFLOAT;OMwrite;$BS;2| |DFLOAT;OMwrite;Omd$V;3|
  |DFLOAT;OMwrite;Omd$BV;4| (|PositiveInteger|) |DFLOAT;base;Pi;6|
  (|Integer|) |DFLOAT;mantissa;$I;7| |DFLOAT;exponent;$I;8|
  |DFLOAT;precision;Pi;9| |DFLOAT;log2;2$;37| (31 . |*|)
  |DFLOAT;bits;Pi;10| |DFLOAT;max;$;11| |DFLOAT;min;$;12|
  |DFLOAT;order;$I;13|
  (CONS IDENTITY (FUNCALL (|dispatchFunction| |DFLOAT;Zero;$;14|) |$|))
  (CONS IDENTITY (FUNCALL (|dispatchFunction| |DFLOAT;One;$;15|) |$|))
  |DFLOAT;exp1;$;16| |DFLOAT;pi;$;17| (|OutputForm|) (37 . |outputForm|)
  |DFLOAT;coerce;$Of;18| (|InputForm|) (42 . |convert|)
  |DFLOAT;convert;$If;19| |DFLOAT;<;2$B;20| |DFLOAT;-;2$;21|
  |DFLOAT;+;3$;22| |DFLOAT;-;3$;23| |DFLOAT;*;3$;24| |DFLOAT;*;I2$;25|
  |DFLOAT;max;3$;26| |DFLOAT;min;3$;27| |DFLOAT;=;2$B;28|
  |DFLOAT;/;$I$;29| |DFLOAT;sqrt;2$;30| |DFLOAT;log10;2$;31|
  |DFLOAT;**;$I$;32| |DFLOAT;**;3$;33| |DFLOAT;coerce;I$;34|
  |DFLOAT;exp;2$;35| |DFLOAT;log;2$;36| |DFLOAT;sin;2$;38|
  |DFLOAT;cos;2$;39| |DFLOAT;tan;2$;40| |DFLOAT;cot;2$;41|
  |DFLOAT;sec;2$;42| |DFLOAT;csc;2$;43| |DFLOAT;asin;2$;44|
  |DFLOAT;acos;2$;45| |DFLOAT;atan;2$;46| |DFLOAT;acsc;2$;47|
  |DFLOAT;acot;2$;48| |DFLOAT;asec;2$;49| |DFLOAT;sinh;2$;50|
  |DFLOAT;cosh;2$;51| |DFLOAT;tanh;2$;52| |DFLOAT;csch;2$;53|
  |DFLOAT;coth;2$;54| |DFLOAT;sech;2$;55| |DFLOAT;asinh;2$;56|
  |DFLOAT;acosh;2$;57| |DFLOAT;atanh;2$;58| |DFLOAT;acsch;2$;59|
  |DFLOAT;acoth;2$;60| |DFLOAT;asech;2$;61| |DFLOAT;/;3$;62|
  |DFLOAT;negative?;$B;63| |DFLOAT;zero?;$B;64| |DFLOAT;hash;$I;65|
  (|Union| |$| (QUOTE "failed")) |DFLOAT;recip;$U;66|
  |DFLOAT;differentiate;2$;67| (|DoubleFloatSpecialFunctions|)
  (47 . |Gamma|) |DFLOAT;Gamma;2$;68| (52 . |Beta|) |DFLOAT;Beta;3$;69|
  |DFLOAT;wholePart;$I;70| |DFLOAT;float;2IPi$;71| |DFLOAT;convert;2$;72|
  (|Float|) (58 . |convert|) |DFLOAT;convert;$F;73| (|Fraction| 24)
  (|NonNegativeInteger|) |DFLOAT;rationalApproximation;$2NniF;83|
  |DFLOAT;rationalApproximation;$NniF;74| |DFLOAT;atan;3$;75|
  |DFLOAT;retract;$F;76| (|Union| 103 (QUOTE "failed"))
```

```
|DFLOAT;retractIfCan;$U;77| |DFLOAT;retract;$I;78|
(|Union| 24 (QUOTE "failed")) |DFLOAT;retractIfCan;$U;79|
|DFLOAT;sign;$I;80| |DFLOAT;abs;2$;81| (63 . |Zero|) (67 . |/|)
(73 . |*|) (79 . |coerce|) (84 . |zero?|) (89 . |negative?|)
(94 . |one?|) (99 . |one?|) (104 . |numer|) (109 . |denom|)
|DFLOAT;**;$F$;84| (|Pattern| 100) (|PatternMatchResult| 100 |$|)
(|Factored| |$|) (|Union| 131 (QUOTE "failed")) (|List| |$|)
(|Record| (|:| |coef1| |$|) (|:| |coef2| |$|) (|:| |generator| |$|))
(|Record| (|:| |coef1| |$|) (|:| |coef2| |$|))
(|Union| 133 (QUOTE "failed"))
(|Record| (|:| |quotient| |$|) (|:| |remainder| |$|))
(|Record| (|:| |coef| 131) (|:| |generator| |$|))
(|SparseUnivariatePolynomial| |$|) (|Record| (|:| |unit| |$|)
(|:| |canonical| |$|) (|:| |associate| |$|)) (|SingleInteger|)))
(QUOTE #(|~=| 114 |zero?| 120 |wholePart| 125 |unitNormal| 130
 |unitCanonical| 135 |unit?| 140 |truncate| 145 |tanh| 150 |tan|
 155 |subtractIfCan| 160 |squareFreePart| 166 |squareFree| 171
 |sqrt| 176 |sizeLess?| 181 |sinh| 187 |sin| 192 |sign| 197 |sech|
 202 |sec| 207 |sample| 212 |round| 216 |retractIfCan| 221 |retract|
 231 |rem| 241 |recip| 247 |rationalApproximation| 252 |quo| 265
 |principalIdeal| 271 |prime?| 276 |precision| 281 |positive?| 285
 |pi| 290 |patternMatch| 294 |order| 301 |one?| 306 |nthRoot| 311
 |norm| 317 |negative?| 322 |multiEuclidean| 327 |min| 333 |max| 343
 |mantissa| 353 |log2| 358 |log10| 363 |log| 368 |lcm| 373 |latex|
 384 |inv| 389 |hash| 394 |gcdPolynomial| 404 |gcd| 410 |fractionPart|
 421 |floor| 426 |float| 431 |factor| 444 |extendedEuclidean| 449
 |exquo| 462 |expressIdealMember| 468 |exponent| 474 |exp1| 479 |exp|
 483 |euclideanSize| 488 |divide| 493 |digits| 499 |differentiate|
 503 |csch| 514 |csc| 519 |coth| 524 |cot| 529 |cosh| 534 |cos| 539
 |convert| 544 |coerce| 564 |characteristic| 594 |ceiling| 598 |bits|
 603 |base| 607 |atanh| 611 |atan| 616 |associates?| 627 |asinh| 633
 |asin| 638 |asech| 643 |asec| 648 |acsch| 653 |acsc| 658 |acoth| 663
 |acot| 668 |acosh| 673 |acos| 678 |abs| 683 |^| 688 |Zero| 706 |One|
 710 |OMwrite| 714 |Gamma| 738 D 743 |Beta| 754 |>=| 760 |>| 766 |=|
 772 |<=| 778 |<| 784 |/| 790 |-| 802 |+| 813 |**| 819 |*| 849))
(QUOTE ((|approximate| . 0) (|canonicalsClosed| . 0)
 (|canonicalUnitNormal| . 0) (|noZeroDivisors| . 0)
 ((|commutative| "*") . 0) (|rightUnitary| . 0) (|leftUnitary| . 0)
 (|unitsKnown| . 0)))
(CONS
 (|makeByteWordVec2| 1 (QUOTE (0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 
```

```
    |ElementaryFunctionCategory&| NIL |HyperbolicFunctionCategory&|
    |ArcTrigonometricFunctionCategory&| |TrigonometricFunctionCategory&|
    NIL NIL |RadicalCategory&| |RetractableTo&| |RetractableTo&| NIL
    NIL |BasicType&| NIL)) (CONS (QUOTE #((|FloatingPointSystem|)
    (|RealNumberSystem|) (|Field|) (|EuclideanDomain|)
    (|PrincipalIdealDomain|) (|UniqueFactorizationDomain|)
    (|GcdDomain|) (|DivisionRing|) (|IntegralDomain|) (|Algebra| 103)
    (|Algebra| |$$|) (|DifferentialRing|) (|CharacteristicZero|)
    (|OrderedRing|) (|Module| 103) (|EntireRing|) (|CommutativeRing|)
    (|Module| |$$|) (|OrderedAbelianGroup|) (|BiModule| 103 103)
    (|BiModule| |$$| |$$|) (|Ring|) (|OrderedCancellationAbelianMonoid|)
    (|RightModule| 103) (|LeftModule| 103) (|LeftModule| |$$|) (|Rng|)
    (|RightModule| |$$|) (|OrderedAbelianMonoid|) (|AbelianGroup|)
    (|OrderedAbelianSemiGroup|) (|CancellationAbelianMonoid|)
    (|AbelianMonoid|) (|Monoid|) (|PatternMatchable| 100) (|OrderedSet|)
    (|AbelianSemiGroup|) (|SemiGroup|) (|TranscendentalFunctionCategory|)
    (|RealConstant|) (|SetCategory|) (|ConvertibleTo| 41)
    (|ElementaryFunctionCategory|) (|ArcHyperbolicFunctionCategory|)
    (|HyperbolicFunctionCategory|) (|ArcTrigonometricFunctionCategory|)
    (|TrigonometricFunctionCategory|) (|OpenMath|) (|ConvertibleTo| 127)
    (|RadicalCategory|) (|RetractableTo| 103) (|RetractableTo| 24)
    (|ConvertibleTo| 100) (|ConvertibleTo| 13) (|BasicType|)
    (|CoercibleTo| 38)))
(|makeByteWordVec2| 139
 (QUOTE (0 6 0 7 2 9 0 8 6 10 1 9 11 0 12 2 9 11 0 13 14 1 9 11 0 15
  1 9 11 0 16 2 0 0 22 0 29 1 38 0 13 39 1 41 0 13 42 1 92 13 13 93 2 92
  13 13 13 95 1 100 0 13 101 0 103 0 116 2 103 0 24 24 117 2 24 0 104 0
  118 1 103 0 24 119 1 103 18 0 120 1 103 18 0 121 1 0 18 0 122 1 103 18
  0 123 1 103 24 0 124 1 103 24 0 125 2 0 18 0 0 1 1 0 18 0 87 1 0 24 0
  97 1 0 138 0 1 1 0 0 0 1 1 0 18 0 1 1 0 0 0 1 1 0 0 0 75 1 0 0 0 63 2
  0 89 0 0 1 1 0 0 0 1 1 0 129 0 1 1 0 0 0 54 2 0 18 0 0 1 1 0 0 0 73 1
  0 0 0 61 1 0 24 0 114 1 0 0 0 78 1 0 0 0 65 0 0 0 1 1 0 0 0 1 1 0 109
  0 110 1 0 112 0 113 1 0 103 0 108 1 0 24 0 111 2 0 0 0 0 1 1 0 89 0
  90 2 0 103 0 104 106 3 0 103 0 104 104 105 2 0 0 0 0 1 1 0 136 131 1
  1 0 18 0 1 0 0 22 27 1 0 18 0 1 0 0 0 37 3 0 128 0 127 128 1 1 0 24
  0 33 1 0 18 0 122 2 0 0 0 24 1 1 0 0 0 1 1 0 18 0 86 2 0 130 131 0 1
  0 0 0 32 2 0 0 0 0 51 0 0 0 31 2 0 0 0 0 50 1 0 24 0 25 1 0 0 0 28 1
  0 0 0 55 1 0 0 0 60 1 0 0 131 1 2 0 0 0 0 1 1 0 8 0 1 1 0 0 0 1 1 0
  24 0 88 1 0 139 0 1 2 0 137 137 137 1 1 0 0 131 1 2 0 0 0 0 1 1 0 0
  0 1 1 0 0 0 1 3 0 0 24 24 22 98 2 0 0 24 24 1 1 0 129 0 1 2 0 132 0
  0 1 3 0 134 0 0 0 1 2 0 89 0 0 1 2 0 130 131 0 1 1 0 24 0 26 0 0 0
  36 1 0 0 0 59 1 0 104 0 1 2 0 135 0 0 1 0 0 22 1 1 0 0 0 91 2 0 0 0
  104 1 1 0 0 0 76 1 0 0 0 66 1 0 0 0 77 1 0 0 0 64 1 0 0 0 74 1 0 0 0
  62 1 0 41 0 43 1 0 127 0 1 1 0 13 0 99 1 0 100 0 102 1 0 0 103 1 1 0
  0 24 58 1 0 0 103 1 1 0 0 24 58 1 0 0 0 1 1 0 38 0 40 0 0 104 1 1 0
  0 0 1 0 0 22 30 0 0 22 23 1 0 0 0 81 2 0 0 0 0 107 1 0 0 0 69 2 0 18
  0 0 1 1 0 0 0 79 1 0 0 0 67 1 0 0 0 84 1 0 0 0 72 1 0 0 0 82 1 0 0 0
  70 1 0 0 0 83 1 0 0 0 71 1 0 0 0 80 1 0 0 0 68 1 0 0 0 115 2 0 0 0
  24 1 2 0 0 0 104 1 2 0 0 0 22 1 0 0 0 34 0 0 0 35 2 0 11 9 0 20 3 0
  11 9 0 18 21 1 0 8 0 17 2 0 8 0 18 19 1 0 0 0 94 1 0 0 0 1 2 0 0 0
```

```
   104 1 2 0 0 0 0 96 2 0 18 0 0 1 2 0 18 0 0 1 2 0 18 0 0 52 2 0 18 0
   0 1 2 0 18 0 0 44 2 0 0 0 24 53 2 0 0 0 0 85 2 0 0 0 0 47 1 0 0 0
   45 2 0 0 0 0 46 2 0 0 0 0 57 2 0 0 0 103 126 2 0 0 0 24 56 2 0 0 0
   104 1 2 0 0 0 22 1 2 0 0 0 103 1 2 0 0 103 0 1 2 0 0 0 0 48 2 0 0
   24 0 49 2 0 0 104 0 1 2 0 0 22 0 29))))))
  (QUOTE |lookupComplete|)))

(setf (get (QUOTE |DoubleFloat|) (QUOTE NILADIC)) T)
```

———-

28.4 ILIST.lsp BOOTSTRAP

ILIST depends on a chain of files. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **ILIST** category which we can write into the **MID** directory. We compile the lisp code and copy the **ILIST.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— ILIST.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT (QUOTE |ILIST;#;$Nni;1|) (QUOTE |SPADreplace|) (QUOTE LENGTH))

(DEFUN |ILIST;#;$Nni;1| (|x| |$|) (LENGTH |x|))

(PUT (QUOTE |ILIST;concat;S2$;2|) (QUOTE |SPADreplace|) (QUOTE CONS))

(DEFUN |ILIST;concat;S2$;2| (|s| |x| |$|) (CONS |s| |x|))

(PUT (QUOTE |ILIST;eq?;2$B;3|) (QUOTE |SPADreplace|) (QUOTE EQ))

(DEFUN |ILIST;eq?;2$B;3| (|x| |y| |$|) (EQ |x| |y|))

(PUT (QUOTE |ILIST;first;$S;4|) (QUOTE |SPADreplace|) (QUOTE |SPADfirst|))

(DEFUN |ILIST;first;$S;4| (|x| |$|) (|SPADfirst| |x|))

(PUT
 (QUOTE |ILIST;elt;$firstS;5|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x| "first") (|SPADfirst| |x|))))

(DEFUN |ILIST;elt;$firstS;5| (|x| G101995 |$|) (|SPADfirst| |x|))

(PUT (QUOTE |ILIST;empty;$;6|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL NIL)))
```

```
(DEFUN |ILIST;empty;$;6| (|$|) NIL)

(PUT (QUOTE |ILIST;empty?;$B;7|) (QUOTE |SPADreplace|) (QUOTE NULL))

(DEFUN |ILIST;empty?;$B;7| (|x| |$|) (NULL |x|))

(PUT (QUOTE |ILIST;rest;2$;8|) (QUOTE |SPADreplace|) (QUOTE CDR))

(DEFUN |ILIST;rest;2$;8| (|x| |$|) (CDR |x|))

(PUT
 (QUOTE |ILIST;elt;$rest$;9|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x| "rest") (CDR |x|))))

(DEFUN |ILIST;elt;$rest$;9| (|x| G102000 |$|) (CDR |x|))

(DEFUN |ILIST;setfirst!;$2S;10| (|x| |s| |$|)
 (COND
  ((SPADCALL |x| (QREFELT |$| 17)) (|error| "Cannot update an empty list"))
  ((QUOTE T) (QCAR (RPLACA |x| |s|)))))

(DEFUN |ILIST;setelt;$first2S;11| (|x| G102005 |s| |$|)
 (COND
   ((SPADCALL |x| (QREFELT |$| 17)) (|error| "Cannot update an empty list"))
   ((QUOTE T) (QCAR (RPLACA |x| |s|)))))

(DEFUN |ILIST;setrest!;3$;12| (|x| |y| |$|)
 (COND
  ((SPADCALL |x| (QREFELT |$| 17)) (|error| "Cannot update an empty list"))
  ((QUOTE T) (QCDR (RPLACD |x| |y|)))))

(DEFUN |ILIST;setelt;$rest2$;13| (|x| G102010 |y| |$|)
 (COND
  ((SPADCALL |x| (QREFELT |$| 17)) (|error| "Cannot update an empty list"))
  ((QUOTE T) (QCDR (RPLACD |x| |y|)))))

(PUT
 (QUOTE |ILIST;construct;L$;14|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|l|) |l|)))

(DEFUN |ILIST;construct;L$;14| (|l| |$|) |l|)

(PUT
 (QUOTE |ILIST;parts;$L;15|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|s|) |s|)))
```

```
(DEFUN |ILIST;parts;$L;15| (|s| |$|) |s|)

(PUT (QUOTE |ILIST;reverse!;2$;16|) (QUOTE |SPADreplace|) (QUOTE NREVERSE))

(DEFUN |ILIST;reverse!;2$;16| (|x| |$|) (NREVERSE |x|))

(PUT (QUOTE |ILIST;reverse;2$;17|) (QUOTE |SPADreplace|) (QUOTE REVERSE))

(DEFUN |ILIST;reverse;2$;17| (|x| |$|) (REVERSE |x|))

(DEFUN |ILIST;minIndex;$I;18| (|x| |$|) (QREFELT |$| 7))

(DEFUN |ILIST;rest;$Nni$;19| (|x| |n| |$|)
 (PROG (|i|)
  (RETURN
   (SEQ
    (SEQ
     (LETT |i| 1 |ILIST;rest;$Nni$;19|)
     G190
     (COND ((QSGREATERP |i| |n|) (GO G191)))
     (SEQ
      (COND ((NULL |x|) (|error| "index out of range")))
      (EXIT (LETT |x| (QCDR |x|) |ILIST;rest;$Nni$;19|)))
     (LETT |i| (QSADD1 |i|) |ILIST;rest;$Nni$;19|)
     (GO G190)
     G191
     (EXIT NIL))
    (EXIT |x|)))))

(DEFUN |ILIST;copy;2$;20| (|x| |$|)
 (PROG (|i| |y|)
  (RETURN
   (SEQ
    (LETT |y| (SPADCALL (QREFELT |$| 16)) |ILIST;copy;2$;20|)
    (SEQ
     (LETT |i| 0 |ILIST;copy;2$;20|)
     G190
     (COND
      ((NULL (COND ((NULL |x|) (QUOTE NIL)) ((QUOTE T) (QUOTE T)))) (GO G191)))
     (SEQ
      (COND
       ((EQ |i| 1000)
        (COND ((SPADCALL |x| (QREFELT |$| 33)) (|error| "cyclic list")))))
      (LETT |y| (CONS (QCAR |x|) |y|) |ILIST;copy;2$;20|)
      (EXIT (LETT |x| (QCDR |x|) |ILIST;copy;2$;20|)))
     (LETT |i| (QSADD1 |i|) |ILIST;copy;2$;20|)
     (GO G190)
     G191
     (EXIT NIL))
    (EXIT (NREVERSE |y|))))))
```

```
(DEFUN |ILIST;coerce;$Of;21| (|x| |$|)
 (PROG (|s| |y| |z|)
  (RETURN
   (SEQ
    (LETT |y| NIL |ILIST;coerce;$Of;21|)
    (LETT |s| (SPADCALL |x| (QREFELT |$| 35)) |ILIST;coerce;$Of;21|)
    (SEQ
     G190
     (COND ((NULL (NEQ |x| |s|)) (GO G191)))
     (SEQ
      (LETT |y|
       (CONS (SPADCALL (SPADCALL |x| (QREFELT |$| 13)) (QREFELT |$| 37)) |y|)
       |ILIST;coerce;$Of;21|)
      (EXIT (LETT |x| (SPADCALL |x| (QREFELT |$| 18)) |ILIST;coerce;$Of;21|)))
     NIL
     (GO G190)
     G191
     (EXIT NIL))
    (LETT |y| (NREVERSE |y|) |ILIST;coerce;$Of;21|)
    (EXIT
     (COND
      ((SPADCALL |s| (QREFELT |$| 17)) (SPADCALL |y| (QREFELT |$| 39)))
      ((QUOTE T)
       (SEQ
        (LETT |z|
         (SPADCALL
          (SPADCALL (SPADCALL |x| (QREFELT |$| 13)) (QREFELT |$| 37))
          (QREFELT |$| 41))
         |ILIST;coerce;$Of;21|)
        (SEQ
         G190
         (COND ((NULL (NEQ |s| (SPADCALL |x| (QREFELT |$| 18)))) (GO G191)))
         (SEQ
          (LETT |x| (SPADCALL |x| (QREFELT |$| 18)) |ILIST;coerce;$Of;21|)
          (EXIT
           (LETT |z|
            (CONS
             (SPADCALL (SPADCALL |x| (QREFELT |$| 13)) (QREFELT |$| 37))
             |z|)
            |ILIST;coerce;$Of;21|)))
         NIL
         (GO G190)
         G191
         (EXIT NIL))
        (EXIT
         (SPADCALL
          (SPADCALL |y|
           (SPADCALL
            (SPADCALL
```

```
            (NREVERSE |z|)
            (QREFELT |$| 42))
           (QREFELT |$| 43))
          (QREFELT |$| 44))
         (QREFELT |$| 39)))))))))))

(DEFUN |ILIST;=;2$B;22| (|x| |y| $)
  (PROG (G102042)
    (RETURN
      (SEQ (EXIT (COND
                   ((EQ |x| |y|) 'T)
                   ('T
                    (SEQ (SEQ G190
                              (COND
                                ((NULL (COND
                                         ((OR (NULL |x|) (NULL |y|))
                                          'NIL)
                                         ('T 'T)))
                                 (GO G191)))
                              (SEQ (EXIT
                                     (COND
                                       ((NULL
                                         (SPADCALL (QCAR |x|) (QCAR |y|)
                                          (QREFELT $ 46)))
                                        (PROGN
                                          (LETT G102042 'NIL
                                           |ILIST;=;2$B;22|)
                                          (GO G102042)))
                                       ('T
                                        (SEQ
                                         (LETT |x| (QCDR |x|)
                                          |ILIST;=;2$B;22|)
                                         (EXIT
                                          (LETT |y| (QCDR |y|)
                                           |ILIST;=;2$B;22|)))))))
                                   NIL (GO G190) G191 (EXIT NIL))
                         (EXIT (COND
                                 ((NULL |x|) (NULL |y|))
                                 ('T 'NIL)))))))
           G102042 (EXIT G102042)))))

(DEFUN |ILIST;latex;$S;23| (|x| |$|)
 (PROG (|s|)
  (RETURN
   (SEQ
    (LETT |s| "\\left[" |ILIST;latex;$S;23|)
    (SEQ
     G190
     (COND
      ((NULL (COND ((NULL |x|) (QUOTE NIL)) ((QUOTE T) (QUOTE T))))
```

```
       (GO G191)))
     (SEQ
      (LETT |s|
        (STRCONC |s| (SPADCALL (QCAR |x|) (QREFELT |$| 49)))
        |ILIST;latex;$S;23|)
      (LETT |x| (QCDR |x|) |ILIST;latex;$S;23|)
      (EXIT
       (COND
        ((NULL (NULL |x|))
          (LETT |s| (STRCONC |s| ", ") |ILIST;latex;$S;23|)))))
     NIL
     (GO G190)
     G191
     (EXIT NIL))
    (EXIT (STRCONC |s| " \\right]")))))))

(DEFUN |ILIST;member?;S$B;24| (|s| |x| $)
  (PROG (G102052)
    (RETURN
      (SEQ (EXIT (SEQ (SEQ G190
                           (COND
                             ((NULL (COND ((NULL |x|) 'NIL) ('T 'T)))
                              (GO G191)))
                           (SEQ (EXIT (COND
                                        ((SPADCALL |s| (QCAR |x|)
                                          (QREFELT $ 46))
                                         (PROGN
                                           (LETT G102052 'T
                                            |ILIST;member?;S$B;24|)
                                           (GO G102052)))
                                        ('T
                                         (LETT |x| (QCDR |x|)
                                          |ILIST;member?;S$B;24|)))))
                           NIL (GO G190) G191 (EXIT NIL))
                      (EXIT 'NIL)))
           G102052 (EXIT G102052)))))

(DEFUN |ILIST;concat!;3$;25| (|x| |y| |$|)
 (PROG (|z|)
  (RETURN
   (SEQ
    (COND
     ((NULL |x|)
      (COND
       ((NULL |y|) |x|)
       ((QUOTE T)
        (SEQ
         (PUSH (SPADCALL |y| (QREFELT |$| 13)) |x|)
         (QRPLACD |x| (SPADCALL |y| (QREFELT |$| 18))) (EXIT |x|)))))
     ((QUOTE T)
```

```
      (SEQ
       (LETT |z| |x| |ILIST;concat!;3$;25|)
       (SEQ
        G190
        (COND
         ((NULL (COND ((NULL (QCDR |z|)) (QUOTE NIL)) ((QUOTE T) (QUOTE T))))
           (GO G191)))
        (SEQ (EXIT (LETT |z| (QCDR |z|) |ILIST;concat!;3$;25|)))
        NIL
        (GO G190)
        G191
        (EXIT NIL))
       (QRPLACD |z| |y|)
       (EXIT |x|)))))))

(DEFUN |ILIST;removeDuplicates!;2$;26| (|l| |$|)
 (PROG (|f| |p| |pr| |pp|)
  (RETURN
   (SEQ
    (LETT |p| |l| |ILIST;removeDuplicates!;2$;26|)
    (SEQ
     G190
     (COND
      ((NULL (COND ((NULL |p|) (QUOTE NIL)) ((QUOTE T) (QUOTE T)))) (GO G191)))
     (SEQ
      (LETT |pp| |p| |ILIST;removeDuplicates!;2$;26|)
      (LETT |f| (QCAR |p|) |ILIST;removeDuplicates!;2$;26|)
      (LETT |p| (QCDR |p|) |ILIST;removeDuplicates!;2$;26|)
      (EXIT
       (SEQ
        G190
        (COND
         ((NULL
           (COND
            ((NULL (LETT |pr| (QCDR |pp|) |ILIST;removeDuplicates!;2$;26|))
              (QUOTE NIL))
            ((QUOTE T) (QUOTE T))))
          (GO G191)))
        (SEQ
         (EXIT
          (COND
           ((SPADCALL (QCAR |pr|) |f| (QREFELT |$| 46))
             (QRPLACD |pp| (QCDR |pr|)))
           ((QUOTE T) (LETT |pp| |pr| |ILIST;removeDuplicates!;2$;26|)))))
        NIL
        (GO G190)
        G191
        (EXIT NIL))))
     NIL
     (GO G190)
```

```
     G191
     (EXIT NIL))
    (EXIT |l|)))))

(DEFUN |ILIST;sort!;M2$;27| (|f| |l| |$|)
 (|ILIST;mergeSort| |f| |l| (SPADCALL |l| (QREFELT |$| 9)) |$|))

(DEFUN |ILIST;merge!;M3$;28| (|f| |p| |q| |$|)
 (PROG (|r| |t|)
  (RETURN
   (SEQ
    (COND
     ((NULL |p|) |q|)
     ((NULL |q|) |p|)
     ((EQ |p| |q|) (|error| "cannot merge a list into itself"))
     ((QUOTE T)
      (SEQ
       (COND
        ((SPADCALL (QCAR |p|) (QCAR |q|) |f|)
         (SEQ
          (LETT |r| (LETT |t| |p| |ILIST;merge!;M3$;28|) |ILIST;merge!;M3$;28|)
          (EXIT (LETT |p| (QCDR |p|) |ILIST;merge!;M3$;28|))))
        ((QUOTE T)
         (SEQ
          (LETT |r| (LETT |t| |q| |ILIST;merge!;M3$;28|) |ILIST;merge!;M3$;28|)
          (EXIT (LETT |q| (QCDR |q|) |ILIST;merge!;M3$;28|)))))
       (SEQ
        G190
        (COND
         ((NULL
           (COND
            ((OR (NULL |p|) (NULL |q|)) (QUOTE NIL))
            ((QUOTE T) (QUOTE T))))
          (GO G191)))
        (SEQ
         (EXIT
          (COND
           ((SPADCALL (QCAR |p|) (QCAR |q|) |f|)
            (SEQ
             (QRPLACD |t| |p|)
             (LETT |t| |p| |ILIST;merge!;M3$;28|)
             (EXIT (LETT |p| (QCDR |p|) |ILIST;merge!;M3$;28|))))
           ((QUOTE T)
            (SEQ
             (QRPLACD |t| |q|)
             (LETT |t| |q| |ILIST;merge!;M3$;28|)
             (EXIT (LETT |q| (QCDR |q|) |ILIST;merge!;M3$;28|)))))))
        NIL
        (GO G190)
        G191
```

```
        (EXIT NIL))
       (QRPLACD |t| (COND ((NULL |p|) |q|) ((QUOTE T) |p|)))
       (EXIT |r|)))))))))

(DEFUN |ILIST;split!;$I$;29| (|p| |n| $)
  (PROG (G102085 |q|)
    (RETURN
      (SEQ (COND
             ((< |n| 1) (|error| "index out of range"))
             ('T
              (SEQ (LETT |p|
                         (SPADCALL |p|
                             (PROG1 (LETT G102085 (- |n| 1)
                                     |ILIST;split!;$I$;29|)
                               (|check-subtype| (>= G102085 0)
                                   '(|NonNegativeInteger|) G102085))
                             (QREFELT $ 32))
                         |ILIST;split!;$I$;29|)
                   (LETT |q| (QCDR |p|) |ILIST;split!;$I$;29|)
                   (QRPLACD |p| NIL) (EXIT |q|)))))))))

(DEFUN |ILIST;mergeSort| (|f| |p| |n| $)
  (PROG (G102089 |l| |q|)
    (RETURN
      (SEQ (COND
             ((EQL |n| 2)
              (COND
                ((SPADCALL
                     (SPADCALL (SPADCALL |p| (QREFELT $ 18))
                         (QREFELT $ 13))
                     (SPADCALL |p| (QREFELT $ 13)) |f|)
                  (LETT |p| (SPADCALL |p| (QREFELT $ 28))
                        |ILIST;mergeSort|)))))
           (EXIT (COND
                   ((< |n| 3) |p|)
                   ('T
                    (SEQ (LETT |l|
                               (PROG1 (LETT G102089 (QUOTIENT2 |n| 2)
                                       |ILIST;mergeSort|)
                                 (|check-subtype| (>= G102089 0)
                                     '(|NonNegativeInteger|) G102089))
                               |ILIST;mergeSort|)
                         (LETT |q| (SPADCALL |p| |l| (QREFELT $ 57))
                               |ILIST;mergeSort|)
                         (LETT |p| (|ILIST;mergeSort| |f| |p| |l| $)
                               |ILIST;mergeSort|)
                         (LETT |q|
                               (|ILIST;mergeSort| |f| |q| (- |n| |l|)
                                   $)
                               |ILIST;mergeSort|)
```

```
                        (EXIT (SPADCALL |f| |p| |q| (QREFELT $ 56)))))))))))

(DEFUN |IndexedList| (&REST G102103 &AUX G102101)
  (DSETQ G102101 G102103)
  (PROG ()
    (RETURN
      (PROG (G102102)
        (RETURN
          (COND
            ((LETT G102102
                   (|lassocShiftWithFunction| (|devaluateList| G102101)
                       (HGET |$ConstructorCache| '|IndexedList|)
                       '|domainEqualList|)
                   |IndexedList|)
             (|CDRwithIncrement| G102102))
            ('T
             (UNWIND-PROTECT
               (PROG1 (APPLY (|function| |IndexedList;|) G102101)
                 (LETT G102102 T |IndexedList|))
               (COND
                 ((NOT G102102)
                  (HREM |$ConstructorCache| '|IndexedList|)))))))))))

(DEFUN |IndexedList;| (|#1| |#2|)
  (PROG (DV$1 DV$2 |dv$| $ G102100 |pv$|)
    (RETURN
      (PROGN
        (LETT DV$1 (|devaluate| |#1|) |IndexedList|)
        (LETT DV$2 (|devaluate| |#2|) |IndexedList|)
        (LETT |dv$| (LIST '|IndexedList| DV$1 DV$2) |IndexedList|)
        (LETT $ (make-array 71) |IndexedList|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$|
                  (|buildPredVector| 0 0
                      (LIST (|HasCategory| |#1| '(|SetCategory|))
                            (|HasCategory| |#1|
                                '(|ConvertibleTo| (|InputForm|)))
                            (LETT G102100
                                  (|HasCategory| |#1| '(|OrderedSet|))
                                  |IndexedList|)
                            (OR G102100
                                (|HasCategory| |#1| '(|SetCategory|)))
                            (|HasCategory| (|Integer|) '(|OrderedSet|))
                            (AND (|HasCategory| |#1|
                                     (LIST '|Evalable|
                                           (|devaluate| |#1|)))
                                 (|HasCategory| |#1| '(|SetCategory|)))
                            (OR (AND (|HasCategory| |#1|
                                     (LIST '|Evalable|
```

```
                                        (|devaluate| |#1|)))
                                    G102100)
                                (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     (|HasCategory| |#1|
                                      '(|SetCategory|))))))
                  |IndexedList|))
        (|haddProp| |$ConstructorCache| '|IndexedList| (LIST DV$1 DV$2)
            (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 6 |#1|)
        (QSETREFV $ 7 |#2|)
        (COND
          ((|testBitVector| |pv$| 1)
           (PROGN
             (QSETREFV $ 45
                 (CONS (|dispatchFunction| |ILIST;coerce;$Of;21|) $))
             (QSETREFV $ 47
                 (CONS (|dispatchFunction| |ILIST;=;2$B;22|) $))
             (QSETREFV $ 50
                 (CONS (|dispatchFunction| |ILIST;latex;$S;23|) $))
             (QSETREFV $ 51
                 (CONS (|dispatchFunction| |ILIST;member?;S$B;24|) $)))))
        (COND
          ((|testBitVector| |pv$| 1)
           (QSETREFV $ 53
               (CONS (|dispatchFunction|
                         |ILIST;removeDuplicates!;2$;26|)
                     $))))
        $))))

(setf (get
 (QUOTE |IndexedList|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE #(
   NIL NIL NIL NIL NIL NIL (|local| |#1|) (|local| |#2|)
   (|NonNegativeInteger|) |ILIST;#;$Nni;1| |ILIST;concat;S2$;2| (|Boolean|)
   |ILIST;eq?;2$B;3| |ILIST;first;$S;4| (QUOTE "first") |ILIST;elt;$firstS;5|
   |ILIST;empty;$;6| |ILIST;empty?;$B;7| |ILIST;rest;2$;8| (QUOTE "rest")
   |ILIST;elt;$rest$;9| |ILIST;setfirst!;$2S;10| |ILIST;setelt;$first2S;11|
   |ILIST;setrest!;3$;12| |ILIST;setelt;$rest2$;13| (|List| 6)
   |ILIST;construct;L$;14| |ILIST;parts;$L;15| |ILIST;reverse!;2$;16|
   |ILIST;reverse;2$;17| (|Integer|) |ILIST;minIndex;$I;18|
   |ILIST;rest;$Nni$;19| (0 . |cyclic?|) |ILIST;copy;2$;20|
   (5 . |cycleEntry|) (|OutputForm|) (10 . |coerce|) (|List| |$|)
   (15 . |bracket|) (|List| 36) (20 . |list|) (25 . |commaSeparate|)
   (30 . |overbar|) (35 . |concat!|) (41 . |coerce|) (46 . |=|) (52 . |=|)
   (|String|) (58 . |latex|) (63 . |latex|) (68 . |member?|)
```

```
 |ILIST;concat!;3$;25| (74 . |removeDuplicates!|) (|Mapping| 11 6 6)
 |ILIST;sort!;M2$;27| |ILIST;merge!;M3$;28| |ILIST;split!;$I$;29|
 (|Mapping| 6 6 6) (|Equation| 6) (|List| 59) (|Mapping| 11 6) (|Void|)
 (|UniversalSegment| 30) (QUOTE "last") (QUOTE "value") (|Mapping| 6 6)
 (|InputForm|) (|SingleInteger|) (|List| 30) (|Union| 6 (QUOTE "failed"))))
(QUOTE #(
 |~=| 79 |value| 85 |third| 90 |tail| 95 |swap!| 100 |split!| 107
 |sorted?| 113 |sort!| 124 |sort| 135 |size?| 146 |setvalue!| 152
 |setrest!| 158 |setlast!| 164 |setfirst!| 170 |setelt| 176
 |setchildren!| 218 |select!| 224 |select| 230 |second| 236 |sample|
 241 |reverse!| 245 |reverse| 250 |rest| 255 |removeDuplicates!|
 266 |removeDuplicates| 271 |remove!| 276 |remove| 288 |reduce|
 300 |qsetelt!| 321 |qelt| 328 |possiblyInfinite?| 334 |position|
 339 |parts| 358 |nodes| 363 |node?| 368 |new| 374 |more?| 380
 |minIndex| 386 |min| 391 |merge!| 397 |merge| 410 |members| 423
 |member?| 428 |maxIndex| 434 |max| 439 |map!| 445 |map| 451 |list|
 464 |less?| 469 |leaves| 475 |leaf?| 480 |latex| 485 |last| 490
 |insert!| 501 |insert| 515 |indices| 529 |index?| 534 |hash| 540
 |first| 545 |find| 556 |fill!| 562 |explicitlyFinite?| 568 |every?|
 573 |eval| 579 |eq?| 605 |entry?| 611 |entries| 617 |empty?| 622
 |empty| 627 |elt| 631 |distance| 674 |delete!| 680 |delete| 692
 |cyclic?| 704 |cycleTail| 709 |cycleSplit!| 714 |cycleLength| 719
 |cycleEntry| 724 |count| 729 |copyInto!| 741 |copy| 748 |convert|
 753 |construct| 758 |concat!| 763 |concat| 775 |coerce| 798
 |children| 803 |child?| 808 |any?| 814 |>=| 820 |>| 826 |=| 832
 |<=| 838 |<| 844 |#| 850))
(QUOTE ((|shallowlyMutable| . 0) (|finiteAggregate| . 0)))
(CONS
 (|makeByteWordVec2| 7 (QUOTE (0 0 0 0 0 0 0 0 0 0 3 0 0 7 4 0 0 7 1 2 4)))
 (CONS
  (QUOTE #(|ListAggregate&| |StreamAggregate&| |ExtensibleLinearAggregate&|
    |FiniteLinearAggregate&| |UnaryRecursiveAggregate&| |LinearAggregate&|
    |RecursiveAggregate&| |IndexedAggregate&| |Collection&|
    |HomogeneousAggregate&| |OrderedSet&| |Aggregate&| |EltableAggregate&|
    |Evalable&| |SetCategory&| NIL NIL |InnerEvalable&| NIL NIL
    |BasicType&|))
  (CONS
   (QUOTE #(
    (|ListAggregate| 6) (|StreamAggregate| 6)
    (|ExtensibleLinearAggregate| 6) (|FiniteLinearAggregate| 6)
    (|UnaryRecursiveAggregate| 6) (|LinearAggregate| 6)
    (|RecursiveAggregate| 6) (|IndexedAggregate| 30 6)
    (|Collection| 6) (|HomogeneousAggregate| 6) (|OrderedSet|)
    (|Aggregate|) (|EltableAggregate| 30 6) (|Evalable| 6) (|SetCategory|)
    (|Type|) (|Eltable| 30 6) (|InnerEvalable| 6 6) (|CoercibleTo| 36)
    (|ConvertibleTo| 67) (|BasicType|)))
   (|makeByteWordVec2| 70
    (QUOTE (1 0 11 0 33 1 0 0 0 35 1 6 36 0 37 1 36 0 38 39 1 40 0 36
     41 1 36 0 38 42 1 36 0 0 43 2 40 0 0 36 44 1 0 36 0 45 2 6 11 0 0
     46 2 0 11 0 0 47 1 6 48 0 49 1 0 48 0 50 2 0 11 6 0 51 1 0 0 0 53
```

```
      2 1 11 0 0 1 1 0 6 0 1 1 0 6 0 1 1 0 0 0 1 3 0 62 0 30 30 1 2 0 0
      0 30 57 1 3 11 0 1 2 0 11 54 0 1 1 3 0 0 1 2 0 0 54 0 55 1 3 0 0 1
      2 0 0 54 0 1 2 0 11 0 8 1 2 0 6 0 6 1 2 0 0 0 0 23 2 0 6 0 6 1 2 0
      6 0 6 21 3 0 6 0 30 6 1 3 0 6 0 63 6 1 3 0 6 0 64 6 1 3 0 0 0 19 0
      24 3 0 6 0 14 6 22 3 0 6 0 65 6 1 2 0 0 0 38 1 2 0 0 61 0 1 2 0 0
      61 0 1 1 0 6 0 1 0 0 0 1 1 0 0 0 28 1 0 0 0 29 2 0 0 0 8 32 1 0 0
      0 18 1 1 0 0 53 1 1 0 0 1 2 1 0 6 0 1 2 0 0 61 0 1 2 1 0 6 0 1 2 0
      0 61 0 1 4 1 6 58 0 6 6 1 2 0 6 58 0 1 3 0 6 58 0 6 1 3 0 6 0 30 6
      1 2 0 6 0 30 1 1 0 11 0 1 2 1 30 6 0 1 3 1 30 6 0 30 1 2 0 30 61 0
      1 1 0 25 0 27 1 0 38 0 1 2 1 11 0 0 1 2 0 0 8 6 1 2 0 11 0 8 1 1 5
      30 0 31 2 3 0 0 0 1 2 3 0 0 0 1 3 0 0 54 0 0 56 2 3 0 0 0 1 3 0 0
      54 0 0 1 1 0 25 0 1 2 1 11 6 0 51 1 5 30 0 1 2 3 0 0 0 1 2 0 0 66
      0 1 3 0 0 58 0 0 1 2 0 0 66 0 1 1 0 0 6 1 2 0 11 0 8 1 1 0 25 0 1
      1 0 11 0 1 1 1 48 0 50 2 0 0 0 8 1 1 0 6 0 1 3 0 0 6 0 30 1 3 0 0
      0 0 30 1 3 0 0 0 0 30 1 3 0 0 6 0 30 1 1 0 69 0 1 2 0 11 30 0 1 1
      1 68 0 1 2 0 0 0 8 1 1 0 6 0 13 2 0 70 61 0 1 2 0 0 0 6 1 1 0 11
      0 1 2 0 11 61 0 1 3 6 0 0 6 6 1 3 6 0 0 25 25 1 2 6 0 0 59 1 2 6
      0 0 60 1 2 0 11 0 0 12 2 1 11 6 0 1 1 0 25 0 1 1 0 11 0 17 0 0 0
      16 2 0 6 0 30 1 3 0 6 0 30 6 1 2 0 0 0 63 1 2 0 6 0 64 1 2 0 0 0
      19 20 2 0 6 0 14 15 2 0 6 0 65 1 2 0 30 0 0 1 2 0 0 0 63 1 2 0 0 0
      30 1 2 0 0 0 63 1 2 0 0 0 30 1 1 0 11 0 33 1 0 0 0 1 1 0 0 0 1 1 0
      8 0 1 1 0 0 0 35 2 1 8 6 0 1 2 0 8 61 0 1 3 0 0 0 0 30 1 1 0 0 0
      34 1 2 67 0 1 1 0 0 25 26 2 0 0 0 0 52 2 0 0 0 6 1 1 0 0 38 1 2 0
      0 0 6 1 2 0 0 6 0 10 2 0 0 0 0 1 1 1 36 0 45 1 0 38 0 1 2 1 11 0
      0 1 2 0 11 61 0 1 2 3 11 0 0 1 2 3 11 0 0 1 2 1 11 0 0 47 2 3 11
      0 0 1 2 3 11 0 0 1 1 0 8 0 9))))))
  (QUOTE |lookupComplete|)))
```

———-

28.5 INT.lsp BOOTSTRAP

INT depends on **OINTDOM** which depends on **ORDRING** which depends on **INT**. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **INT** category which we can write into the **MID** directory. We compile the lisp code and copy the **INT.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— INT.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(DEFUN |INT;writeOMInt| (|dev| |x| |$|)
 (SEQ
  (COND
```

```
   ((|<| |x| 0)
    (SEQ
     (SPADCALL |dev| (QREFELT |$| 8))
     (SPADCALL |dev| "arith1" "unary_minus" (QREFELT |$| 10))
     (SPADCALL |dev| (|-| |x|) (QREFELT |$| 12))
     (EXIT (SPADCALL |dev| (QREFELT |$| 13)))))
   ((QUOTE T) (SPADCALL |dev| |x| (QREFELT |$| 12))))))

(DEFUN |INT;OMwrite;$S;2| (|x| |$|)
 (PROG (|sp| |dev| |s|)
  (RETURN
   (SEQ
    (LETT |s| "" |INT;OMwrite;$S;2|)
    (LETT |sp| (|OM-STRINGTOSTRINGPTR| |s|) |INT;OMwrite;$S;2|)
    (LETT |dev|
     (SPADCALL |sp| (SPADCALL (QREFELT |$| 15)) (QREFELT |$| 16))
     |INT;OMwrite;$S;2|)
    (SPADCALL |dev| (QREFELT |$| 17))
    (|INT;writeOMInt| |dev| |x| |$|)
    (SPADCALL |dev| (QREFELT |$| 18))
    (SPADCALL |dev| (QREFELT |$| 19))
    (LETT |s| (|OM-STRINGPTRTOSTRING| |sp|) |INT;OMwrite;$S;2|)
    (EXIT |s|)))))

(DEFUN |INT;OMwrite;$BS;3| (|x| |wholeObj| |$|)
 (PROG (|sp| |dev| |s|)
  (RETURN
   (SEQ
    (LETT |s| "" |INT;OMwrite;$BS;3|)
    (LETT |sp| (|OM-STRINGTOSTRINGPTR| |s|) |INT;OMwrite;$BS;3|)
    (LETT |dev|
     (SPADCALL |sp| (SPADCALL (QREFELT |$| 15)) (QREFELT |$| 16))
     |INT;OMwrite;$BS;3|)
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 17))))
    (|INT;writeOMInt| |dev| |x| |$|)
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 18))))
    (SPADCALL |dev| (QREFELT |$| 19))
    (LETT |s| (|OM-STRINGPTRTOSTRING| |sp|) |INT;OMwrite;$BS;3|)
    (EXIT |s|)))))

(DEFUN |INT;OMwrite;Omd$V;4| (|dev| |x| |$|)
 (SEQ
  (SPADCALL |dev| (QREFELT |$| 17))
  (|INT;writeOMInt| |dev| |x| |$|)
  (EXIT (SPADCALL |dev| (QREFELT |$| 18)))))

(DEFUN |INT;OMwrite;Omd$BV;5| (|dev| |x| |wholeObj| |$|)
 (SEQ
  (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 17))))
  (|INT;writeOMInt| |dev| |x| |$|)
```

```
  (EXIT (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 18)))))))

(PUT (QUOTE |INT;zero?;$B;6|) (QUOTE |SPADreplace|) (QUOTE ZEROP))

(DEFUN |INT;zero?;$B;6| (|x| |$|) (ZEROP |x|))

(PUT (QUOTE |INT;Zero;$;7|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL 0)))

(DEFUN |INT;Zero;$;7| (|$|) 0)

(PUT (QUOTE |INT;One;$;8|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL 1)))

(DEFUN |INT;One;$;8| (|$|) 1)

(PUT (QUOTE |INT;base;$;9|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL 2)))

(DEFUN |INT;base;$;9| (|$|) 2)

(PUT (QUOTE |INT;copy;2$;10|) (QUOTE |SPADreplace|) (QUOTE (XLAM (|x|) |x|)))

(DEFUN |INT;copy;2$;10| (|x| |$|) |x|)

(PUT
 (QUOTE |INT;inc;2$;11|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) (|+| |x| 1))))

(DEFUN |INT;inc;2$;11| (|x| |$|) (|+| |x| 1))

(PUT
 (QUOTE |INT;dec;2$;12|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) (|-| |x| 1))))

(DEFUN |INT;dec;2$;12| (|x| |$|) (|-| |x| 1))

(PUT (QUOTE |INT;hash;2$;13|) (QUOTE |SPADreplace|) (QUOTE SXHASH))

(DEFUN |INT;hash;2$;13| (|x| |$|) (SXHASH |x|))

(PUT (QUOTE |INT;negative?;$B;14|) (QUOTE |SPADreplace|) (QUOTE MINUSP))

(DEFUN |INT;negative?;$B;14| (|x| |$|) (MINUSP |x|))

(DEFUN |INT;coerce;$Of;15| (|x| |$|) (SPADCALL |x| (QREFELT |$| 35)))

(PUT
 (QUOTE |INT;coerce;2$;16|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|m|) |m|)))
```

```
(DEFUN |INT;coerce;2$;16| (|m| |$|) |m|)

(PUT
 (QUOTE |INT;convert;2$;17|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) |x|)))

(DEFUN |INT;convert;2$;17| (|x| |$|) |x|)

(PUT
 (QUOTE |INT;length;2$;18|)
 (QUOTE |SPADreplace|)
 (QUOTE |INTEGER-LENGTH|))

(DEFUN |INT;length;2$;18| (|a| |$|) (|INTEGER-LENGTH| |a|))

(DEFUN |INT;addmod;4$;19| (|a| |b| |p| $)
  (PROG (|c| G86338)
    (RETURN
      (SEQ (EXIT (SEQ (SEQ (LETT |c| (+ |a| |b|) |INT;addmod;4$;19|)
                           (EXIT (COND
                                   ((NULL (< |c| |p|))
                                    (PROGN
                                      (LETT G86338 (- |c| |p|)
                                       |INT;addmod;4$;19|)
                                      (GO G86338))))))
                      (EXIT |c|)))
           G86338 (EXIT G86338)))))

(DEFUN |INT;submod;4$;20| (|a| |b| |p| |$|)
 (PROG (|c|)
  (RETURN
   (SEQ
    (LETT |c| (|-| |a| |b|) |INT;submod;4$;20|)
    (EXIT (COND ((|<| |c| 0) (|+| |c| |p|)) ((QUOTE T) |c|)))))))

(DEFUN |INT;mulmod;4$;21| (|a| |b| |p| |$|) (REMAINDER2 (|*| |a| |b|) |p|))

(DEFUN |INT;convert;$F;22| (|x| |$|) (SPADCALL |x| (QREFELT |$| 44)))

(PUT
 (QUOTE |INT;convert;$Df;23|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|x|) (FLOAT |x| |MOST-POSITIVE-LONG-FLOAT|))))

(DEFUN |INT;convert;$Df;23| (|x| |$|) (FLOAT |x| |MOST-POSITIVE-LONG-FLOAT|))

(DEFUN |INT;convert;$If;24| (|x| |$|) (SPADCALL |x| (QREFELT |$| 49)))
```

```
(PUT (QUOTE |INT;convert;$S;25|) (QUOTE |SPADreplace|) (QUOTE STRINGIMAGE))

(DEFUN |INT;convert;$S;25| (|x| |$|) (STRINGIMAGE |x|))

(DEFUN |INT;latex;$S;26| (|x| |$|)
 (PROG (|s|)
  (RETURN
   (SEQ
    (LETT |s| (STRINGIMAGE |x|) |INT;latex;$S;26|)
    (COND ((|<| -1 |x|) (COND ((|<| |x| 10) (EXIT |s|)))))
    (EXIT (STRCONC "{" (STRCONC |s| "}")))))))

(DEFUN |INT;positiveRemainder;3$;27| (|a| |b| |$|)
 (PROG (|r|)
  (RETURN
   (COND
    ((MINUSP (LETT |r| (REMAINDER2 |a| |b|) |INT;positiveRemainder;3$;27|))
      (COND
       ((MINUSP |b|) (|-| |r| |b|))
       ((QUOTE T) (|+| |r| |b|))))
    ((QUOTE T) |r|)))))

(PUT
 (QUOTE |INT;reducedSystem;2M;28|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|m|) |m|)))

(DEFUN |INT;reducedSystem;2M;28| (|m| |$|) |m|)

(DEFUN |INT;reducedSystem;MVR;29| (|m| |v| |$|) (CONS |m| (QUOTE |vec|)))

(PUT (QUOTE |INT;abs;2$;30|) (QUOTE |SPADreplace|) (QUOTE ABS))

(DEFUN |INT;abs;2$;30| (|x| |$|) (ABS |x|))

(PUT (QUOTE |INT;random;$;31|) (QUOTE |SPADreplace|) (QUOTE |random|))

(DEFUN |INT;random;$;31| (|$|) (|random|))

(PUT (QUOTE |INT;random;2$;32|) (QUOTE |SPADreplace|) (QUOTE RANDOM))

(DEFUN |INT;random;2$;32| (|x| |$|) (RANDOM |x|))

(PUT (QUOTE |INT;=;2$B;33|) (QUOTE |SPADreplace|) (QUOTE EQL))

(DEFUN |INT;=;2$B;33| (|x| |y| |$|) (EQL |x| |y|))

(PUT (QUOTE |INT;<;2$B;34|) (QUOTE |SPADreplace|) (QUOTE |<|))

(DEFUN |INT;<;2$B;34| (|x| |y| |$|) (|<| |x| |y|))
```

```
(PUT (QUOTE |INT;-;2$;35|) (QUOTE |SPADreplace|) (QUOTE |-|))

(DEFUN |INT;-;2$;35| (|x| |$|) (|-| |x|))

(PUT (QUOTE |INT;+;3$;36|) (QUOTE |SPADreplace|) (QUOTE |+|))

(DEFUN |INT;+;3$;36| (|x| |y| |$|) (|+| |x| |y|))

(PUT (QUOTE |INT;-;3$;37|) (QUOTE |SPADreplace|) (QUOTE |-|))

(DEFUN |INT;-;3$;37| (|x| |y| |$|) (|-| |x| |y|))

(PUT (QUOTE |INT;*;3$;38|) (QUOTE |SPADreplace|) (QUOTE |*|))

(DEFUN |INT;*;3$;38| (|x| |y| |$|) (|*| |x| |y|))

(PUT (QUOTE |INT;*;3$;39|) (QUOTE |SPADreplace|) (QUOTE |*|))

(DEFUN |INT;*;3$;39| (|m| |y| |$|) (|*| |m| |y|))

(PUT (QUOTE |INT;**;$Nni$;40|) (QUOTE |SPADreplace|) (QUOTE EXPT))

(DEFUN |INT;**;$Nni$;40| (|x| |n| |$|) (EXPT |x| |n|))

(PUT (QUOTE |INT;odd?;$B;41|) (QUOTE |SPADreplace|) (QUOTE ODDP))

(DEFUN |INT;odd?;$B;41| (|x| |$|) (ODDP |x|))

(PUT (QUOTE |INT;max;3$;42|) (QUOTE |SPADreplace|) (QUOTE MAX))

(DEFUN |INT;max;3$;42| (|x| |y| |$|) (MAX |x| |y|))

(PUT (QUOTE |INT;min;3$;43|) (QUOTE |SPADreplace|) (QUOTE MIN))

(DEFUN |INT;min;3$;43| (|x| |y| |$|) (MIN |x| |y|))

(PUT (QUOTE |INT;divide;2$R;44|) (QUOTE |SPADreplace|) (QUOTE DIVIDE2))

(DEFUN |INT;divide;2$R;44| (|x| |y| |$|) (DIVIDE2 |x| |y|))

(PUT (QUOTE |INT;quo;3$;45|) (QUOTE |SPADreplace|) (QUOTE QUOTIENT2))

(DEFUN |INT;quo;3$;45| (|x| |y| |$|) (QUOTIENT2 |x| |y|))

(PUT (QUOTE |INT;rem;3$;46|) (QUOTE |SPADreplace|) (QUOTE REMAINDER2))

(DEFUN |INT;rem;3$;46| (|x| |y| |$|) (REMAINDER2 |x| |y|))

(PUT (QUOTE |INT;shift;3$;47|) (QUOTE |SPADreplace|) (QUOTE ASH))
```

```
(DEFUN |INT;shift;3$;47| (|x| |y| |$|) (ASH |x| |y|))

(DEFUN |INT;exquo;2$U;48| (|x| |y| |$|)
 (COND
  ((OR (ZEROP |y|) (NULL (ZEROP (REMAINDER2 |x| |y|)))) (CONS 1 "failed"))
  ((QUOTE T) (CONS 0 (QUOTIENT2 |x| |y|)))))

(DEFUN |INT;recip;$U;49| (|x| |$|)
 (COND
  ((OR (EQL |x| 1) (EQL |x| -1)) (CONS 0 |x|))
  ((QUOTE T) (CONS 1 "failed"))))

(PUT (QUOTE |INT;gcd;3$;50|) (QUOTE |SPADreplace|) (QUOTE GCD))

(DEFUN |INT;gcd;3$;50| (|x| |y| |$|) (GCD |x| |y|))

(DEFUN |INT;unitNormal;$R;51| (|x| |$|)
 (COND
  ((|<| |x| 0) (VECTOR -1 (|-| |x|) -1))
  ((QUOTE T) (VECTOR 1 |x| 1))))

(PUT (QUOTE |INT;unitCanonical;2$;52|) (QUOTE |SPADreplace|) (QUOTE ABS))

(DEFUN |INT;unitCanonical;2$;52| (|x| |$|) (ABS |x|))

(DEFUN |INT;solveLinearPolynomialEquation| (|lp| |p| |$|)
 (SPADCALL |lp| |p| (QREFELT |$| 91)))

(DEFUN |INT;squareFreePolynomial| (|p| |$|) (SPADCALL |p| (QREFELT |$| 95)))

(DEFUN |INT;factorPolynomial| (|p| $)
  (PROG (|pp| G86409)
    (RETURN
      (SEQ (LETT |pp| (SPADCALL |p| (QREFELT $ 96))
                 |INT;factorPolynomial|)
           (EXIT (COND
                   ((EQL (SPADCALL |pp| (QREFELT $ 97))
                         (SPADCALL |p| (QREFELT $ 97)))
                    (SPADCALL |p| (QREFELT $ 99)))
                   ('T
                    (SPADCALL (SPADCALL |pp| (QREFELT $ 99))
                        (SPADCALL (CONS #'|INT;factorPolynomial!0| $)
                            (SPADCALL
                                (PROG2 (LETT G86409
                                        (SPADCALL
                                         (SPADCALL |p| (QREFELT $ 97))
                                         (SPADCALL |pp| (QREFELT $ 97))
                                         (QREFELT $ 81))
                                        |INT;factorPolynomial|)
```

```
                                        (QCDR G86409)
                                    (|check-union| (QEQCAR G86409 0) $
                                        G86409))
                                (QREFELT $ 102))
                            (QREFELT $ 106))
                        (QREFELT $ 108)))))))))

(DEFUN |INT;factorPolynomial!0| (|#1| |$|) (SPADCALL |#1| (QREFELT |$| 100)))

(DEFUN |INT;factorSquareFreePolynomial| (|p| |$|)
 (SPADCALL |p| (QREFELT |$| 109)))

(DEFUN |INT;gcdPolynomial;3Sup;57| (|p| |q| |$|)
 (COND
  ((SPADCALL |p| (QREFELT |$| 110)) (SPADCALL |q| (QREFELT |$| 111)))
  ((SPADCALL |q| (QREFELT |$| 110)) (SPADCALL |p| (QREFELT |$| 111)))
  ((QUOTE T) (SPADCALL (LIST |p| |q|) (QREFELT |$| 114)))))

(DEFUN |Integer| ()
  (PROG ()
    (RETURN
      (PROG (G86434)
        (RETURN
          (COND
            ((LETT G86434 (HGET |$ConstructorCache| '|Integer|)
                   |Integer|)
             (|CDRwithIncrement| (CDAR G86434)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|Integer|
                                   (LIST
                                    (CONS NIL (CONS 1 (|Integer;|))))))
                 (LETT G86434 T |Integer|))
               (COND
                 ((NOT G86434) (HREM |$ConstructorCache| '|Integer|)))))))))))

(DEFUN |Integer;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|Integer|) |Integer|)
        (LETT $ (make-array 130) |Integer|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL) |Integer|))
        (|haddProp| |$ConstructorCache| '|Integer| NIL (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 69
            (QSETREFV $ 68 (CONS (|dispatchFunction| |INT;*;3$;39|) $)))
        $))))
```

```
(setf (get
 (QUOTE |Integer|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE
   #(NIL NIL NIL NIL NIL NIL (|Void|) (|OpenMathDevice|) (0 . |OMputApp|)
    (|String|) (5 . |OMputSymbol|) (|Integer|) (12 . |OMputInteger|)
    (18 . |OMputEndApp|) (|OpenMathEncoding|) (23 . |OMencodingXML|)
    (27 . |OMopenString|) (33 . |OMputObject|) (38 . |OMputEndObject|)
    (43 . |OMclose|) |INT;OMwrite;$S;2| (|Boolean|) |INT;OMwrite;$BS;3|
    |INT;OMwrite;Omd$V;4| |INT;OMwrite;Omd$BV;5| |INT;zero?;$B;6|
    (CONS IDENTITY (FUNCALL (|dispatchFunction| |INT;Zero;$;7|) |$|))
    (CONS IDENTITY (FUNCALL (|dispatchFunction| |INT;One;$;8|) |$|))
    |INT;base;$;9| |INT;copy;2$;10| |INT;inc;2$;11| |INT;dec;2$;12|
    |INT;hash;2$;13| |INT;negative?;$B;14| (|OutputForm|)
    (48 . |outputForm|) |INT;coerce;$Of;15| |INT;coerce;2$;16|
    |INT;convert;2$;17| |INT;length;2$;18| |INT;addmod;4$;19|
    |INT;submod;4$;20| |INT;mulmod;4$;21| (|Float|) (53 . |coerce|)
    |INT;convert;$F;22| (|DoubleFloat|) |INT;convert;$Df;23| (|InputForm|)
    (58 . |convert|) |INT;convert;$If;24| |INT;convert;$S;25|
    |INT;latex;$S;26| |INT;positiveRemainder;3$;27| (|Matrix| 11)
    (|Matrix| |$|) |INT;reducedSystem;2M;28|
    (|Record| (|:| |mat| 54) (|:| |vec| (|Vector| 11)))
    (|Vector| |$|) |INT;reducedSystem;MVR;29| |INT;abs;2$;30|
    |INT;random;$;31| |INT;random;2$;32| |INT;=;2$B;33|
    |INT;<;2$B;34| |INT;-;2$;35| |INT;+;3$;36| |INT;-;3$;37| NIL NIL
    (|NonNegativeInteger|) |INT;**;$Nni$;40| |INT;odd?;$B;41|
    |INT;max;3$;42| |INT;min;3$;43|
    (|Record| (|:| |quotient| |$|) (|:| |remainder| |$|))
    |INT;divide;2$R;44| |INT;quo;3$;45| |INT;rem;3$;46| |INT;shift;3$;47|
    (|Union| |$| (QUOTE "failed")) |INT;exquo;2$U;48| |INT;recip;$U;49|
    |INT;gcd;3$;50|
    (|Record| (|:| |unit| |$|) (|:| |canonical| |$|) (|:| |associate| |$|))
    |INT;unitNormal;$R;51| |INT;unitCanonical;2$;52|
    (|Union| 88 (QUOTE "failed")) (|List| 89)
    (|SparseUnivariatePolynomial| 11)
    (|IntegerSolveLinearPolynomialEquation|)
    (63 . |solveLinearPolynomialEquation|) (|Factored| 93)
    (|SparseUnivariatePolynomial| |$$|)
    (|UnivariatePolynomialSquareFree| |$$| 93) (69 . |squareFree|)
    (74 . |primitivePart|) (79 . |leadingCoefficient|)
    (|GaloisGroupFactorizer| 93) (84 . |factor|) (89 . |coerce|)
    (|Factored| |$|) (94 . |factor|) (|Mapping| 93 |$$|)
    (|Factored| |$$|) (|FactoredFunctions2| |$$| 93) (99 . |map|)
    (|FactoredFunctionUtilities| 93) (105 . |mergeFactors|)
    (111 . |factorSquareFree|) (116 . |zero?|) (121 . |unitCanonical|)
    (|List| 93) (|HeuGcd| 93) (126 . |gcd|)
    (|SparseUnivariatePolynomial| |$|) |INT;gcdPolynomial;3Sup;57|
    (|Union| 118 (QUOTE "failed")) (|Fraction| 11)
```

```
   (|PatternMatchResult| 11 |$|) (|Pattern| 11)
   (|Union| 11 (QUOTE "failed")) (|Union| 123 (QUOTE "failed"))
   (|List| |$|)
   (|Record| (|:| |coef| 123) (|:| |generator| |$|))
   (|Record| (|:| |coef1| |$|) (|:| |coef2| |$|))
   (|Union| 125 (QUOTE "failed"))
   (|Record| (|:| |coef1| |$|) (|:| |coef2| |$|) (|:| |generator| |$|))
   (|PositiveInteger|) (|SingleInteger|)))
 (QUOTE #(|~=| 131 |zero?| 137 |unitNormal| 142 |unitCanonical| 147
      |unit?| 152 |symmetricRemainder| 157 |subtractIfCan| 163 |submod| 169
      |squareFreePart| 176 |squareFree| 181 |sizeLess?| 186 |sign| 192
      |shift| 197 |sample| 203 |retractIfCan| 207 |retract| 212 |rem| 217
      |reducedSystem| 223 |recip| 234 |rationalIfCan| 239 |rational?| 244
      |rational| 249 |random| 254 |quo| 263 |principalIdeal| 269
      |prime?| 274 |powmod| 279 |positiveRemainder| 286 |positive?| 292
      |permutation| 297 |patternMatch| 303 |one?| 310 |odd?| 315
      |nextItem| 320 |negative?| 325 |multiEuclidean| 330 |mulmod| 336
      |min| 343 |max| 349 |mask| 355 |length| 360 |lcm| 365 |latex| 376
      |invmod| 381 |init| 387 |inc| 391 |hash| 396 |gcdPolynomial| 406
      |gcd| 412 |factorial| 423 |factor| 428 |extendedEuclidean| 433
      |exquo| 446 |expressIdealMember| 452 |even?| 458
      |euclideanSize| 463 |divide| 468 |differentiate| 474 |dec| 485
      |copy| 490 |convert| 495 |coerce| 525 |characteristic| 545
      |bit?| 549 |binomial| 555 |base| 561 |associates?| 565
      |addmod| 571 |abs| 578 |^| 583 |Zero| 595 |One| 599
      |OMwrite| 603 D 627 |>=| 638 |>| 644 |=| 650 |<=| 656 |<| 662
      |-| 668 |+| 679 |**| 685 |*| 697))
 (QUOTE (
  (|infinite| . 0) (|noetherian| . 0) (|canonicalsClosed| . 0)
  (|canonical| . 0) (|canonicalUnitNormal| . 0)
  (|multiplicativeValuation| . 0) (|noZeroDivisors| . 0)
  ((|commutative| "*") . 0) (|rightUnitary| . 0) (|leftUnitary| . 0)
  (|unitsKnown| . 0)))
 (CONS
   (|makeByteWordVec2| 1
    (QUOTE (0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
            0 0 0 0 0 0 0 0 0 0 0 0 0 0 0)))
   (CONS
    (QUOTE #(
     |IntegerNumberSystem&| |EuclideanDomain&| |UniqueFactorizationDomain&|
     NIL NIL |GcdDomain&| |IntegralDomain&| |Algebra&| NIL NIL
     |DifferentialRing&| |OrderedRing&| NIL NIL |Module&| NIL NIL
     |Ring&| NIL NIL NIL NIL NIL |AbelianGroup&| NIL NIL
     |AbelianMonoid&| |Monoid&| NIL NIL |OrderedSet&|
     |AbelianSemiGroup&| |SemiGroup&| NIL |SetCategory&|
     NIL NIL NIL NIL NIL NIL NIL |RetractableTo&| NIL |BasicType&| NIL))
    (CONS
     (QUOTE #(
      (|IntegerNumberSystem|) (|EuclideanDomain|)
      (|UniqueFactorizationDomain|) (|PrincipalIdealDomain|)
```

```
       (|OrderedIntegralDomain|) (|GcdDomain|) (|IntegralDomain|)
       (|Algebra| |$$|) (|CharacteristicZero|) (|LinearlyExplicitRingOver| 11)
       (|DifferentialRing|) (|OrderedRing|) (|CommutativeRing|) (|EntireRing|)
       (|Module| |$$|) (|OrderedAbelianGroup|) (|BiModule| |$$| |$$|)
       (|Ring|) (|OrderedCancellationAbelianMonoid|) (|LeftModule| |$$|)
       (|Rng|) (|RightModule| |$$|) (|OrderedAbelianMonoid|) (|AbelianGroup|)
       (|OrderedAbelianSemiGroup|) (|CancellationAbelianMonoid|)
       (|AbelianMonoid|) (|Monoid|) (|StepThrough|) (|PatternMatchable| 11)
       (|OrderedSet|) (|AbelianSemiGroup|) (|SemiGroup|) (|RealConstant|)
       (|SetCategory|) (|OpenMath|) (|ConvertibleTo| 9)
       (|ConvertibleTo| 43) (|ConvertibleTo| 46)
       (|CombinatorialFunctionCategory|) (|ConvertibleTo| 120)
       (|ConvertibleTo| 48) (|RetractableTo| 11) (|ConvertibleTo| 11)
       (|BasicType|) (|CoercibleTo| 34)))
      (|makeByteWordVec2| 129 (QUOTE (1 7 6 0 8 3 7 6 0 9 9 10 2 7 6 0 11
       12 1 7 6 0 13 0 14 0 15 2 7 0 9 14 16 1 7 6 0 17 1 7 6 0 18 1 7 6 0
       19 1 34 0 11 35 1 43 0 11 44 1 48 0 11 49 2 90 87 88 89 91 1 94 92
       93 95 1 93 0 0 96 1 93 2 0 97 1 98 92 93 99 1 93 0 2 100 1 0 101 0
       102 2 105 92 103 104 106 2 107 92 92 92 108 1 98 92 93 109 1 93 21
       0 110 1 93 0 0 111 1 113 93 112 114 2 0 21 0 0 1 1 0 21 0 25 1 0 84
       0 85 1 0 0 0 86 1 0 21 0 1 2 0 0 0 0 1 2 0 80 0 0 1 3 0 0 0 0 0 41
       1 0 0 0 1 1 0 101 0 1 2 0 21 0 0 1 1 0 11 0 1 2 0 0 0 0 79 0 0 0 1
       1 0 121 0 1 1 0 11 0 1 2 0 0 0 0 78 2 0 57 55 58 59 1 0 54 55 56 1
       0 80 0 82 1 0 117 0 1 1 0 21 0 1 1 0 118 0 1 1 0 0 0 62 0 0 0 61 2
       0 0 0 0 77 1 0 124 123 1 1 0 21 0 1 3 0 0 0 0 0 1 2 0 0 0 0 53 1 0
       21 0 1 2 0 0 0 0 1 3 0 119 0 120 119 1 1 0 21 0 1 1 0 21 0 72 1 0
       80 0 1 1 0 21 0 33 2 0 122 123 0 1 3 0 0 0 0 0 42 2 0 0 0 0 74 2 0
       0 0 0 73 1 0 0 0 1 1 0 0 0 39 1 0 0 123 1 2 0 0 0 0 1 1 0 9 0 52 2
       0 0 0 0 1 0 0 0 1 1 0 0 0 30 1 0 0 0 32 1 0 129 0 1 2 0 115 115 115
       116 2 0 0 0 0 83 1 0 0 123 1 1 0 0 0 1 1 0 101 0 102 3 0 126 0 0 0
       1 2 0 127 0 0 1 2 0 80 0 0 81 2 0 122 123 0 1 1 0 21 0 1 1 0 70 0
       1 2 0 75 0 0 76 1 0 0 0 1 2 0 0 0 70 1 1 0 0 0 31 1 0 0 0 29 1 0 9
       0 51 1 0 46 0 47 1 0 43 0 45 1 0 48 0 50 1 0 120 0 1 1 0 11 0 38 1
       0 0 11 37 1 0 0 11 37 1 0 0 0 1 1 0 34 0 36 0 0 70 1 2 0 21 0 0 1
       2 0 0 0 0 1 0 0 0 28 2 0 21 0 0 1 3 0 0 0 0 0 40 1 0 0 0 60 2 0 0
       0 70 1 2 0 0 0 128 1 0 0 0 26 0 0 0 27 3 0 6 7 0 21 24 2 0 9 0 21
       22 2 0 6 7 0 23 1 0 9 0 20 1 0 0 0 1 2 0 0 0 70 1 2 0 21 0 0 1 2
       0 21 0 0 1 2 0 21 0 0 63 2 0 21 0 0 1 2 0 21 0 0 64 2 0 0 0 0 67
       1 0 0 0 65 2 0 0 0 0 66 2 0 0 0 70 71 2 0 0 0 128 1 2 0 0 0 0 68
       2 0 0 11 0 69 2 0 0 70 0 1 2 0 0 128 0 1))))))
  (QUOTE |lookupComplete|)))

(setf (get (QUOTE |Integer|) (QUOTE NILADIC)) T)
```

———-

28.6 ISTRING.lsp BOOTSTRAP

ISTRING depends on a chain of files. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **ISTRING** category which we can write into the **MID** directory. We compile the lisp code and copy the **ISTRING.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— ISTRING.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT '|ISTRING;new;NniC$;1| '|SPADreplace| 'MAKE-FULL-CVEC)

(DEFUN |ISTRING;new;NniC$;1| (|n| |c| |$|) (|MAKE-FULL-CVEC| |n| |c|))

(PUT '|ISTRING;empty;$;2| '|SPADreplace|
     '(XLAM NIL (MAKE-FULL-CVEC 0)))

(DEFUN |ISTRING;empty;$;2| (|$|) (|MAKE-FULL-CVEC| 0))

(DEFUN |ISTRING;empty?;$B;3| (|s| |$|) (EQL (QCSIZE |s|) 0))

(PUT '|ISTRING;#;$Nni;4| '|SPADreplace| 'QCSIZE)

(DEFUN |ISTRING;#;$Nni;4| (|s| |$|) (QCSIZE |s|))

(PUT '|ISTRING;=;2$B;5| '|SPADreplace| 'EQUAL)

(DEFUN |ISTRING;=;2$B;5| (|s| |t| |$|) (EQUAL |s| |t|))

(PUT '|ISTRING;<;2$B;6| '|SPADreplace|
     '(XLAM (|s| |t|) (CGREATERP |t| |s|)))

(DEFUN |ISTRING;<;2$B;6| (|s| |t| |$|) (CGREATERP |t| |s|))

(PUT '|ISTRING;concat;3$;7| '|SPADreplace| 'STRCONC)

(DEFUN |ISTRING;concat;3$;7| (|s| |t| |$|) (STRCONC |s| |t|))

(PUT '|ISTRING;copy;2$;8| '|SPADreplace| 'COPY-SEQ)

(DEFUN |ISTRING;copy;2$;8| (|s| |$|) (|COPY-SEQ| |s|))

(DEFUN |ISTRING;insert;2$I$;9| (|s| |t| |i| $)
  (SPADCALL
      (SPADCALL
          (SPADCALL |s|
```

```
              (SPADCALL (QREFELT $ 6) (- |i| 1) (QREFELT $ 20))
              (QREFELT $ 21))
          |t| (QREFELT $ 16))
      (SPADCALL |s| (SPADCALL |i| (QREFELT $ 22)) (QREFELT $ 21))
      (QREFELT $ 16)))

(DEFUN |ISTRING;coerce;$Of;10| (|s| |$|) (SPADCALL |s| (QREFELT |$| 26)))

(DEFUN |ISTRING;minIndex;$I;11| (|s| |$|) (QREFELT |$| 6))

(DEFUN |ISTRING;upperCase!;2$;12| (|s| $)
  (SPADCALL (ELT $ 31) |s| (QREFELT $ 33)))

(DEFUN |ISTRING;lowerCase!;2$;13| (|s| $)
  (SPADCALL (ELT $ 36) |s| (QREFELT $ 33)))

(DEFUN |ISTRING;latex;$S;14| (|s| $)
  (STRCONC "\\mbox{``" (STRCONC |s| "''}")))

(DEFUN |ISTRING;replace;$Us2$;15| (|s| |sg| |t| $)
  (PROG (|l| |m| |n| |h| G91425 |r| G91433 G91432 |i| G91431
             |k|)
    (RETURN
      (SEQ (LETT |l| (- (SPADCALL |sg| (QREFELT $ 39)) (QREFELT $ 6))
                 |ISTRING;replace;$Us2$;15|)
           (LETT |m| (SPADCALL |s| (QREFELT $ 13))
                 |ISTRING;replace;$Us2$;15|)
           (LETT |n| (SPADCALL |t| (QREFELT $ 13))
                 |ISTRING;replace;$Us2$;15|)
           (LETT |h|
                 (COND
                   ((SPADCALL |sg| (QREFELT $ 40))
                    (- (SPADCALL |sg| (QREFELT $ 41)) (QREFELT $ 6)))
                   ('T (- (SPADCALL |s| (QREFELT $ 42)) (QREFELT $ 6))))
                 |ISTRING;replace;$Us2$;15|)
           (COND
             ((OR (OR (< |l| 0) (NULL (< |h| |m|))) (< |h| (- |l| 1)))
              (EXIT (|error| "index out of range"))))
           (LETT |r|
                 (SPADCALL
                     (PROG1 (LETT G91425
                                  (+ (- |m| (+ (- |h| |l|) 1)) |n|)
                                  |ISTRING;replace;$Us2$;15|)
                       (|check-subtype| (>= G91425 0)
                           '(|NonNegativeInteger|) G91425))
                     (SPADCALL (QREFELT $ 43)) (QREFELT $ 9))
                 |ISTRING;replace;$Us2$;15|)
           (SEQ (LETT |i| 0 |ISTRING;replace;$Us2$;15|)
                (LETT G91433 (- |l| 1) |ISTRING;replace;$Us2$;15|)
                (LETT |k| 0 |ISTRING;replace;$Us2$;15|) G190
```

```
                (COND ((QSGREATERP |i| G91433) (GO G191)))
                (SEQ (EXIT (QESET |r| |k| (QENUM |s| |i|))))
                (LETT |k|
                      (PROG1 (QSADD1 |k|)
                        (LETT |i| (QSADD1 |i|)
                              |ISTRING;replace;$Us2$;15|))
                      |ISTRING;replace;$Us2$;15|)
                (GO G190) G191 (EXIT NIL))
           (SEQ (LETT |i| 0 |ISTRING;replace;$Us2$;15|)
                (LETT G91432 (- |n| 1) |ISTRING;replace;$Us2$;15|)
                (LETT |k| |k| |ISTRING;replace;$Us2$;15|) G190
                (COND ((QSGREATERP |i| G91432) (GO G191)))
                (SEQ (EXIT (QESET |r| |k| (QENUM |t| |i|))))
                (LETT |k|
                      (PROG1 (+ |k| 1)
                        (LETT |i| (QSADD1 |i|)
                              |ISTRING;replace;$Us2$;15|))
                      |ISTRING;replace;$Us2$;15|)
                (GO G190) G191 (EXIT NIL))
           (SEQ (LETT |i| (+ |h| 1) |ISTRING;replace;$Us2$;15|)
                (LETT G91431 (- |m| 1) |ISTRING;replace;$Us2$;15|)
                (LETT |k| |k| |ISTRING;replace;$Us2$;15|) G190
                (COND ((> |i| G91431) (GO G191)))
                (SEQ (EXIT (QESET |r| |k| (QENUM |s| |i|))))
                (LETT |k|
                      (PROG1 (+ |k| 1)
                        (LETT |i| (+ |i| 1) |ISTRING;replace;$Us2$;15|))
                      |ISTRING;replace;$Us2$;15|)
                (GO G190) G191 (EXIT NIL))
           (EXIT |r|)))))

(DEFUN |ISTRING;setelt;$I2C;16| (|s| |i| |c| $)
  (SEQ (COND
         ((OR (< |i| (QREFELT $ 6))
              (< (SPADCALL |s| (QREFELT $ 42)) |i|))
          (|error| "index out of range"))
         ('T (SEQ (QESET |s| (- |i| (QREFELT $ 6)) |c|) (EXIT |c|))))))

(DEFUN |ISTRING;substring?;2$IB;17| (|part| |whole| |startpos| $)
  (PROG (|np| |nw| |iw| |ip| G91443 G91442 G91438)
    (RETURN
      (SEQ (EXIT (SEQ (LETT |np| (QCSIZE |part|)
                            |ISTRING;substring?;2$IB;17|)
                      (LETT |nw| (QCSIZE |whole|)
                            |ISTRING;substring?;2$IB;17|)
                      (LETT |startpos| (- |startpos| (QREFELT $ 6))
                            |ISTRING;substring?;2$IB;17|)
                      (EXIT (COND
                              ((< |startpos| 0)
                               (|error| "index out of bounds"))
```

```
                                ((< (- |nw| |startpos|) |np|) 'NIL)
                                ('T
                                 (SEQ (SEQ
                                       (EXIT
                                        (SEQ
                                         (LETT |iw| |startpos|
                                          |ISTRING;substring?;2$IB;17|)
                                         (LETT |ip| 0
                                          |ISTRING;substring?;2$IB;17|)
                                         (LETT G91443 (- |np| 1)
                                          |ISTRING;substring?;2$IB;17|)
                                         G190
                                         (COND
                                           ((QSGREATERP |ip| G91443)
                                            (GO G191)))
                                         (SEQ
                                          (EXIT
                                           (COND
                                             ((NULL
                                               (EQL (QENUM |part| |ip|)
                                                (QENUM |whole| |iw|)))
                                              (PROGN
                                                (LETT G91438
                                                 (PROGN
                                                   (LETT G91442 'NIL
                                                    |ISTRING;substring?;2$IB;17|)
                                                   (GO G91442))
                                                  |ISTRING;substring?;2$IB;17|)
                                                 (GO G91438))))))
                                         (LETT |ip|
                                          (PROG1 (QSADD1 |ip|)
                                            (LETT |iw| (+ |iw| 1)
                                             |ISTRING;substring?;2$IB;17|))
                                          |ISTRING;substring?;2$IB;17|)
                                         (GO G190) G191 (EXIT NIL)))
                                       G91438 (EXIT G91438))
                                      (EXIT 'T)))))))
          G91442 (EXIT G91442)))))

(DEFUN |ISTRING;position;2$2I;18| (|s| |t| |startpos| $)
  (PROG (|r|)
    (RETURN
      (SEQ (LETT |startpos| (- |startpos| (QREFELT $ 6))
                 |ISTRING;position;2$2I;18|)
           (EXIT (COND
                   ((< |startpos| 0) (|error| "index out of bounds"))
                   ((NULL (< |startpos| (QCSIZE |t|)))
                    (- (QREFELT $ 6) 1))
                   ('T
                    (SEQ (LETT |r| (STRPOS |s| |t| |startpos| NIL)
```

```
                              |ISTRING;position;2$2I;18|)
                         (EXIT (COND
                                 ((EQ |r| NIL) (- (QREFELT $ 6) 1))
                                 ('T (+ |r| (QREFELT $ 6))))))))))))

(DEFUN |ISTRING;position;C$2I;19| (|c| |t| |startpos| $)
  (PROG (|r| G91454 G91453)
    (RETURN
      (SEQ (EXIT (SEQ (LETT |startpos| (- |startpos| (QREFELT $ 6))
                            |ISTRING;position;C$2I;19|)
                      (EXIT (COND
                              ((< |startpos| 0)
                               (|error| "index out of bounds"))
                              ((NULL (< |startpos| (QCSIZE |t|)))
                               (- (QREFELT $ 6) 1))
                              ('T
                               (SEQ (SEQ
                                     (LETT |r| |startpos|
                                      |ISTRING;position;C$2I;19|)
                                     (LETT G91454
                                      (QSDIFFERENCE (QCSIZE |t|) 1)
                                      |ISTRING;position;C$2I;19|)
                                     G190
                                     (COND
                                       ((> |r| G91454) (GO G191)))
                                     (SEQ
                                      (EXIT
                                       (COND
                                         ((EQL (QENUM |t| |r|) |c|)
                                          (PROGN
                                            (LETT G91453
                                             (+ |r| (QREFELT $ 6))
                                             |ISTRING;position;C$2I;19|)
                                            (GO G91453))))))
                                     (LETT |r| (+ |r| 1)
                                      |ISTRING;position;C$2I;19|)
                                     (GO G190) G191 (EXIT NIL))
                                    (EXIT (- (QREFELT $ 6) 1)))))))))
           G91453 (EXIT G91453)))))

(DEFUN |ISTRING;position;Cc$2I;20| (|cc| |t| |startpos| $)
  (PROG (|r| G91461 G91460)
    (RETURN
      (SEQ (EXIT (SEQ (LETT |startpos| (- |startpos| (QREFELT $ 6))
                            |ISTRING;position;Cc$2I;20|)
                      (EXIT (COND
                              ((< |startpos| 0)
                               (|error| "index out of bounds"))
                              ((NULL (< |startpos| (QCSIZE |t|)))
                               (- (QREFELT $ 6) 1))
```

```
                              ('T
                               (SEQ (SEQ
                                     (LETT |r| |startpos|
                                      |ISTRING;position;Cc$2I;20|)
                                     (LETT G91461
                                      (QSDIFFERENCE (QCSIZE |t|) 1)
                                      |ISTRING;position;Cc$2I;20|)
                                     G190
                                     (COND
                                       ((> |r| G91461) (GO G191)))
                                     (SEQ
                                      (EXIT
                                       (COND
                                         ((SPADCALL (QENUM |t| |r|)
                                           |cc| (QREFELT $ 49))
                                          (PROGN
                                            (LETT G91460
                                             (+ |r| (QREFELT $ 6))
                                             |ISTRING;position;Cc$2I;20|)
                                            (GO G91460))))))
                                     (LETT |r| (+ |r| 1)
                                      |ISTRING;position;Cc$2I;20|)
                                     (GO G190) G191 (EXIT NIL))
                                    (EXIT (- (QREFELT $ 6) 1))))))))
          G91460 (EXIT G91460)))))

(DEFUN |ISTRING;suffix?;2$B;21| (|s| |t| $)
  (PROG (|n| |m|)
    (RETURN
      (SEQ (LETT |n| (SPADCALL |t| (QREFELT $ 42))
                 |ISTRING;suffix?;2$B;21|)
           (LETT |m| (SPADCALL |s| (QREFELT $ 42))
                 |ISTRING;suffix?;2$B;21|)
           (EXIT (COND
                   ((< |n| |m|) 'NIL)
                   ('T
                    (SPADCALL |s| |t| (- (+ (QREFELT $ 6) |n|) |m|)
                        (QREFELT $ 46)))))))))

(DEFUN |ISTRING;split;$CL;22| (|s| |c| $)
  (PROG (|n| |j| |i| |l|)
    (RETURN
      (SEQ (LETT |n| (SPADCALL |s| (QREFELT $ 42))
                 |ISTRING;split;$CL;22|)
           (SEQ (LETT |i| (QREFELT $ 6) |ISTRING;split;$CL;22|) G190
                (COND
                  ((OR (> |i| |n|)
                       (NULL (SPADCALL
                                 (SPADCALL |s| |i| (QREFELT $ 52)) |c|
                                 (QREFELT $ 53))))
```

```
        (GO G191)))
     (SEQ (EXIT 0))
     (LETT |i| (+ |i| 1) |ISTRING;split;$CL;22|) (GO G190)
     G191 (EXIT NIL))
(LETT |l| (SPADCALL (QREFELT $ 55)) |ISTRING;split;$CL;22|)
(SEQ G190
     (COND
       ((NULL (COND
                ((< |n| |i|) 'NIL)
                ('T
                 (SEQ (LETT |j|
                            (SPADCALL |c| |s| |i|
                             (QREFELT $ 48))
                            |ISTRING;split;$CL;22|)
                      (EXIT (COND
                              ((< |j| (QREFELT $ 6)) 'NIL)
                              ('T 'T)))))))
        (GO G191)))
     (SEQ (LETT |l|
                (SPADCALL
                    (SPADCALL |s|
                        (SPADCALL |i| (- |j| 1)
                         (QREFELT $ 20))
                        (QREFELT $ 21))
                    |l| (QREFELT $ 56))
                |ISTRING;split;$CL;22|)
          (EXIT (SEQ (LETT |i| |j| |ISTRING;split;$CL;22|)
                     G190
                     (COND
                       ((OR (> |i| |n|)
                            (NULL
                             (SPADCALL
                              (SPADCALL |s| |i| (QREFELT $ 52))
                              |c| (QREFELT $ 53))))
                        (GO G191)))
                     (SEQ (EXIT 0))
                     (LETT |i| (+ |i| 1)
                           |ISTRING;split;$CL;22|)
                     (GO G190) G191 (EXIT NIL))))
     NIL (GO G190) G191 (EXIT NIL))
(COND
  ((NULL (< |n| |i|))
   (LETT |l|
         (SPADCALL
             (SPADCALL |s| (SPADCALL |i| |n| (QREFELT $ 20))
                 (QREFELT $ 21))
             |l| (QREFELT $ 56))
         |ISTRING;split;$CL;22|)))
(EXIT (SPADCALL |l| (QREFELT $ 57)))))))
```

```
(DEFUN |ISTRING;split;$CcL;23| (|s| |cc| $)
  (PROG (|n| |j| |i| |l|)
    (RETURN
      (SEQ (LETT |n| (SPADCALL |s| (QREFELT $ 42))
                 |ISTRING;split;$CcL;23|)
           (SEQ (LETT |i| (QREFELT $ 6) |ISTRING;split;$CcL;23|) G190
                (COND
                  ((OR (> |i| |n|)
                       (NULL (SPADCALL
                                 (SPADCALL |s| |i| (QREFELT $ 52)) |cc|
                                 (QREFELT $ 49))))
                   (GO G191)))
                (SEQ (EXIT 0))
                (LETT |i| (+ |i| 1) |ISTRING;split;$CcL;23|) (GO G190)
                G191 (EXIT NIL))
           (LETT |l| (SPADCALL (QREFELT $ 55)) |ISTRING;split;$CcL;23|)
           (SEQ G190
                (COND
                  ((NULL (COND
                           ((< |n| |i|) 'NIL)
                           ('T
                            (SEQ (LETT |j|
                                       (SPADCALL |cc| |s| |i|
                                        (QREFELT $ 50))
                                       |ISTRING;split;$CcL;23|)
                                 (EXIT (COND
                                         ((< |j| (QREFELT $ 6)) 'NIL)
                                         ('T 'T)))))))
                   (GO G191)))
                (SEQ (LETT |l|
                           (SPADCALL
                               (SPADCALL |s|
                                   (SPADCALL |i| (- |j| 1)
                                    (QREFELT $ 20))
                                   (QREFELT $ 21))
                               |l| (QREFELT $ 56))
                           |ISTRING;split;$CcL;23|)
                     (EXIT (SEQ (LETT |i| |j| |ISTRING;split;$CcL;23|)
                                G190
                                (COND
                                  ((OR (> |i| |n|)
                                    (NULL
                                     (SPADCALL
                                      (SPADCALL |s| |i| (QREFELT $ 52))
                                      |cc| (QREFELT $ 49))))
                                   (GO G191)))
                                (SEQ (EXIT 0))
                                (LETT |i| (+ |i| 1)
                                      |ISTRING;split;$CcL;23|)
                                (GO G190) G191 (EXIT NIL))))
```

```
              NIL (GO G190) G191 (EXIT NIL))
          (COND
            ((NULL (< |n| |i|))
             (LETT |l|
                   (SPADCALL
                       (SPADCALL |s| (SPADCALL |i| |n| (QREFELT $ 20))
                           (QREFELT $ 21))
                       |l| (QREFELT $ 56))
                   |ISTRING;split;$CcL;23|)))
          (EXIT (SPADCALL |l| (QREFELT $ 57)))))))

(DEFUN |ISTRING;leftTrim;$C$;24| (|s| |c| $)
  (PROG (|n| |i|)
    (RETURN
      (SEQ (LETT |n| (SPADCALL |s| (QREFELT $ 42))
                 |ISTRING;leftTrim;$C$;24|)
           (SEQ (LETT |i| (QREFELT $ 6) |ISTRING;leftTrim;$C$;24|) G190
                (COND
                  ((OR (> |i| |n|)
                       (NULL (SPADCALL
                                 (SPADCALL |s| |i| (QREFELT $ 52)) |c|
                                 (QREFELT $ 53))))
                    (GO G191)))
                (SEQ (EXIT 0))
                (LETT |i| (+ |i| 1) |ISTRING;leftTrim;$C$;24|)
                (GO G190) G191 (EXIT NIL))
           (EXIT (SPADCALL |s| (SPADCALL |i| |n| (QREFELT $ 20))
                     (QREFELT $ 21)))))))

(DEFUN |ISTRING;leftTrim;$Cc$;25| (|s| |cc| $)
  (PROG (|n| |i|)
    (RETURN
      (SEQ (LETT |n| (SPADCALL |s| (QREFELT $ 42))
                 |ISTRING;leftTrim;$Cc$;25|)
           (SEQ (LETT |i| (QREFELT $ 6) |ISTRING;leftTrim;$Cc$;25|)
                G190
                (COND
                  ((OR (> |i| |n|)
                       (NULL (SPADCALL
                                 (SPADCALL |s| |i| (QREFELT $ 52)) |cc|
                                 (QREFELT $ 49))))
                    (GO G191)))
                (SEQ (EXIT 0))
                (LETT |i| (+ |i| 1) |ISTRING;leftTrim;$Cc$;25|)
                (GO G190) G191 (EXIT NIL))
           (EXIT (SPADCALL |s| (SPADCALL |i| |n| (QREFELT $ 20))
                     (QREFELT $ 21)))))))

(DEFUN |ISTRING;rightTrim;$C$;26| (|s| |c| $)
  (PROG (|j| G91487)
```

```
    (RETURN
      (SEQ (SEQ (LETT |j| (SPADCALL |s| (QREFELT $ 42))
                      |ISTRING;rightTrim;$C$;26|)
                (LETT G91487 (QREFELT $ 6)
                      |ISTRING;rightTrim;$C$;26|)
                G190
                (COND
                  ((OR (< |j| G91487)
                       (NULL (SPADCALL
                                 (SPADCALL |s| |j| (QREFELT $ 52)) |c|
                                 (QREFELT $ 53))))
                   (GO G191)))
                (SEQ (EXIT 0))
                (LETT |j| (+ |j| -1) |ISTRING;rightTrim;$C$;26|)
                (GO G190) G191 (EXIT NIL))
           (EXIT (SPADCALL |s|
                     (SPADCALL (SPADCALL |s| (QREFELT $ 28)) |j|
                         (QREFELT $ 20))
                     (QREFELT $ 21)))))))

(DEFUN |ISTRING;rightTrim;$Cc$;27| (|s| |cc| $)
  (PROG (|j| G91491)
    (RETURN
      (SEQ (SEQ (LETT |j| (SPADCALL |s| (QREFELT $ 42))
                      |ISTRING;rightTrim;$Cc$;27|)
                (LETT G91491 (QREFELT $ 6)
                      |ISTRING;rightTrim;$Cc$;27|)
                G190
                (COND
                  ((OR (< |j| G91491)
                       (NULL (SPADCALL
                                 (SPADCALL |s| |j| (QREFELT $ 52)) |cc|
                                 (QREFELT $ 49))))
                   (GO G191)))
                (SEQ (EXIT 0))
                (LETT |j| (+ |j| -1) |ISTRING;rightTrim;$Cc$;27|)
                (GO G190) G191 (EXIT NIL))
           (EXIT (SPADCALL |s|
                     (SPADCALL (SPADCALL |s| (QREFELT $ 28)) |j|
                         (QREFELT $ 20))
                     (QREFELT $ 21)))))))


(DEFUN |ISTRING;concat;L$;28| (|l| $)
  (PROG (G91500 G91494 G91492 G91493 |t| |s| G91499 |i|)
    (RETURN
      (SEQ (LETT |t|
                 (SPADCALL
                     (PROGN
                       (LETT G91493 NIL |ISTRING;concat;L$;28|)
```

```
                    (SEQ (LETT |s| NIL |ISTRING;concat;L$;28|)
                         (LETT G91500 |l| |ISTRING;concat;L$;28|)
                         G190
                         (COND
                           ((OR (ATOM G91500)
                                (PROGN
                                  (LETT |s| (CAR G91500)
                                   |ISTRING;concat;L$;28|)
                                  NIL))
                            (GO G191)))
                         (SEQ (EXIT (PROGN
                                     (LETT G91494
                                      (SPADCALL |s| (QREFELT $ 13))
                                      |ISTRING;concat;L$;28|)
                                     (COND
                                       (G91493
                                        (LETT G91492
                                         (+ G91492 G91494)
                                         |ISTRING;concat;L$;28|))
                                       ('T
                                        (PROGN
                                          (LETT G91492 G91494
                                           |ISTRING;concat;L$;28|)
                                          (LETT G91493 'T
                                           |ISTRING;concat;L$;28|)))))))
                         (LETT G91500 (CDR G91500)
                               |ISTRING;concat;L$;28|)
                         (GO G190) G191 (EXIT NIL))
                    (COND (G91493 G91492) ('T 0)))
                  (SPADCALL (QREFELT $ 43)) (QREFELT $ 9))
                |ISTRING;concat;L$;28|)
          (LETT |i| (QREFELT $ 6) |ISTRING;concat;L$;28|)
          (SEQ (LETT |s| NIL |ISTRING;concat;L$;28|)
               (LETT G91499 |l| |ISTRING;concat;L$;28|) G190
               (COND
                 ((OR (ATOM G91499)
                      (PROGN
                        (LETT |s| (CAR G91499)
                              |ISTRING;concat;L$;28|)
                        NIL))
                  (GO G191)))
               (SEQ (SPADCALL |t| |s| |i| (QREFELT $ 65))
                    (EXIT (LETT |i|
                                (+ |i| (SPADCALL |s| (QREFELT $ 13)))
                                |ISTRING;concat;L$;28|)))
               (LETT G91499 (CDR G91499) |ISTRING;concat;L$;28|)
               (GO G190) G191 (EXIT NIL))
          (EXIT |t|)))))

(DEFUN |ISTRING;copyInto!;2$I$;29| (|y| |x| |s| $)
```

```
  (PROG (|m| |n|)
    (RETURN
      (SEQ (LETT |m| (SPADCALL |x| (QREFELT $ 13))
                 |ISTRING;copyInto!;2$I$;29|)
           (LETT |n| (SPADCALL |y| (QREFELT $ 13))
                 |ISTRING;copyInto!;2$I$;29|)
           (LETT |s| (- |s| (QREFELT $ 6)) |ISTRING;copyInto!;2$I$;29|)
           (COND
             ((OR (< |s| 0) (< |n| (+ |s| |m|)))
              (EXIT (|error| "index out of range"))))
           (RPLACSTR |y| |s| |m| |x| 0 |m|) (EXIT |y|)))))


(DEFUN |ISTRING;elt;$IC;30| (|s| |i| $)
  (COND
    ((OR (< |i| (QREFELT $ 6)) (< (SPADCALL |s| (QREFELT $ 42)) |i|))
     (|error| "index out of range"))
    ('T (QENUM |s| (- |i| (QREFELT $ 6))))))

(DEFUN |ISTRING;elt;$Us$;31| (|s| |sg| $)
  (PROG (|l| |h|)
    (RETURN
      (SEQ (LETT |l| (- (SPADCALL |sg| (QREFELT $ 39)) (QREFELT $ 6))
                 |ISTRING;elt;$Us$;31|)
           (LETT |h|
                 (COND
                   ((SPADCALL |sg| (QREFELT $ 40))
                    (- (SPADCALL |sg| (QREFELT $ 41)) (QREFELT $ 6)))
                   ('T (- (SPADCALL |s| (QREFELT $ 42)) (QREFELT $ 6))))
                 |ISTRING;elt;$Us$;31|)
           (COND
             ((OR (< |l| 0)
                  (NULL (< |h| (SPADCALL |s| (QREFELT $ 13)))))
              (EXIT (|error| "index out of bound"))))
           (EXIT (SUBSTRING |s| |l| (MAX 0 (+ (- |h| |l|) 1))))))))


(DEFUN |ISTRING;hash;$I;32| (|s| $)
  (PROG (|n|)
    (RETURN
      (SEQ (LETT |n| (QCSIZE |s|) |ISTRING;hash;$I;32|)
           (EXIT (COND
                   ((ZEROP |n|) 0)
                   ((EQL |n| 1)
                    (SPADCALL
                        (SPADCALL |s| (QREFELT $ 6) (QREFELT $ 52))
                        (QREFELT $ 67)))
                   ('T
                    (* (* (SPADCALL
                              (SPADCALL |s| (QREFELT $ 6)
```

```
                                (QREFELT $ 52))
                            (QREFELT $ 67))
                        (SPADCALL
                            (SPADCALL |s| (- (+ (QREFELT $ 6) |n|) 1)
                                (QREFELT $ 52))
                            (QREFELT $ 67)))
                    (SPADCALL
                        (SPADCALL |s|
                            (+ (QREFELT $ 6) (QUOTIENT2 |n| 2))
                            (QREFELT $ 52))
                        (QREFELT $ 67))))))))))

(PUT '|ISTRING;match;2$CNni;33| '|SPADreplace| '|stringMatch|)

(DEFUN |ISTRING;match;2$CNni;33| (|pattern| |target| |wildcard| $)
  (|stringMatch| |pattern| |target| |wildcard|))

(DEFUN |ISTRING;match?;2$CB;34| (|pattern| |target| |dontcare| $)
  (PROG (|n| |m| G91514 G91516 |s| G91518 G91526 |i| |p|
           G91519 |q|)
    (RETURN
      (SEQ (EXIT (SEQ (LETT |n| (SPADCALL |pattern| (QREFELT $ 42))
                            |ISTRING;match?;2$CB;34|)
                      (LETT |p|
                            (PROG1 (LETT G91514
                                    (SPADCALL |dontcare| |pattern|
                                     (LETT |m|
                                      (SPADCALL |pattern|
                                       (QREFELT $ 28))
                                      |ISTRING;match?;2$CB;34|)
                                     (QREFELT $ 48))
                                    |ISTRING;match?;2$CB;34|)
                              (|check-subtype| (>= G91514 0)
                                  '(|NonNegativeInteger|) G91514))
                            |ISTRING;match?;2$CB;34|)
                      (EXIT (COND
                              ((EQL |p| (- |m| 1))
                               (SPADCALL |pattern| |target|
                                   (QREFELT $ 14)))
                              ('T
                               (SEQ (COND
                                      ((NULL (EQL |p| |m|))
                                       (COND
                                         ((NULL
                                           (SPADCALL
                                            (SPADCALL |pattern|
                                             (SPADCALL |m| (- |p| 1)
                                              (QREFELT $ 20))
                                             (QREFELT $ 21))
                                            |target| (QREFELT $ 70)))
```

```
      (EXIT 'NIL)))))
(LETT |i| |p|
 |ISTRING;match?;2$CB;34|)
(LETT |q|
 (PROG1
  (LETT G91516
   (SPADCALL |dontcare| |pattern|
    (+ |p| 1) (QREFELT $ 48))
   |ISTRING;match?;2$CB;34|)
   (|check-subtype| (>= G91516 0)
    '(|NonNegativeInteger|)
    G91516))
 |ISTRING;match?;2$CB;34|)
(SEQ G190
 (COND
  ((NULL
    (COND
     ((EQL |q| (- |m| 1)) 'NIL)
     ('T 'T)))
   (GO G191)))
 (SEQ
  (LETT |s|
   (SPADCALL |pattern|
    (SPADCALL (+ |p| 1) (- |q| 1)
     (QREFELT $ 20))
    (QREFELT $ 21))
   |ISTRING;match?;2$CB;34|)
  (LETT |i|
   (PROG1
    (LETT G91518
     (SPADCALL |s| |target| |i|
      (QREFELT $ 47))
     |ISTRING;match?;2$CB;34|)
     (|check-subtype|
      (>= G91518 0)
      '(|NonNegativeInteger|)
      G91518))
   |ISTRING;match?;2$CB;34|)
  (EXIT
   (COND
     ((EQL |i| (- |m| 1))
      (PROGN
        (LETT G91526 'NIL
         |ISTRING;match?;2$CB;34|)
        (GO G91526)))
     ('T
      (SEQ
       (LETT |i|
        (+ |i|
         (SPADCALL |s|
```

```
                                          (QREFELT $ 13)))
                                        |ISTRING;match?;2$CB;34|)
                                       (LETT |p| |q|
                                        |ISTRING;match?;2$CB;34|)
                                       (EXIT
                                        (LETT |q|
                                         (PROG1
                                          (LETT G91519
                                           (SPADCALL |dontcare|
                                            |pattern| (+ |q| 1)
                                            (QREFELT $ 48))
                                           |ISTRING;match?;2$CB;34|)
                                           (|check-subtype|
                                            (>= G91519 0)
                                            '(|NonNegativeInteger|)
                                            G91519))
                                          |ISTRING;match?;2$CB;34|)))))))
                                  NIL (GO G190) G191 (EXIT NIL))
                                 (COND
                                   ((NULL (EQL |p| |n|))
                                    (COND
                                      ((NULL
                                        (SPADCALL
                                         (SPADCALL |pattern|
                                          (SPADCALL (+ |p| 1) |n|
                                           (QREFELT $ 20))
                                          (QREFELT $ 21))
                                         |target| (QREFELT $ 51)))
                                       (EXIT 'NIL)))))
                                 (EXIT 'T)))))))
           G91526 (EXIT G91526)))))

(DEFUN |IndexedString| (G91535)
  (PROG ()
    (RETURN
      (PROG (G91536)
        (RETURN
          (COND
            ((LETT G91536
                   (|lassocShiftWithFunction|
                       (LIST (|devaluate| G91535))
                       (HGET |$ConstructorCache| '|IndexedString|)
                       '|domainEqualList|)
                   |IndexedString|)
             (|CDRwithIncrement| G91536))
            ('T
             (UNWIND-PROTECT
               (PROG1 (|IndexedString;| G91535)
                 (LETT G91536 T |IndexedString|))
               (COND
```

```
                ((NOT G91536)
                 (HREM |$ConstructorCache| '|IndexedString|))))))))))))

(DEFUN |IndexedString;| (|#1|)
  (PROG (DV$1 |dv$| $ G91534 G91533 |pv$|)
    (RETURN
      (PROGN
        (LETT DV$1 (|devaluate| |#1|) |IndexedString|)
        (LETT |dv$| (LIST '|IndexedString| DV$1) |IndexedString|)
        (LETT $ (make-array 83) |IndexedString|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$|
                  (|buildPredVector| 0 0
                      (LIST (|HasCategory| (|Character|)
                                '(|SetCategory|))
                            (|HasCategory| (|Character|)
                                '(|ConvertibleTo| (|InputForm|)))
                            (LETT G91534
                                  (|HasCategory| (|Character|)
                                      '(|OrderedSet|))
                                  |IndexedString|)
                            (OR G91534
                                (|HasCategory| (|Character|)
                                    '(|SetCategory|)))
                            (|HasCategory| (|Integer|) '(|OrderedSet|))
                            (LETT G91533
                                  (AND (|HasCategory| (|Character|)
                                        '(|Evalable| (|Character|)))
                                       (|HasCategory| (|Character|)
                                        '(|SetCategory|)))
                                  |IndexedString|)
                            (OR (AND (|HasCategory| (|Character|)
                                      '(|Evalable| (|Character|)))
                                     G91534)
                                G91533)))
                  |IndexedString|))
        (|haddProp| |$ConstructorCache| '|IndexedString| (LIST DV$1)
            (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 6 |#1|)
        $))))

(setf (get '|IndexedString| '|infovec|)
    (LIST '#(NIL NIL NIL NIL NIL NIL (|local| |#1|)
             (|NonNegativeInteger|) (|Character|) |ISTRING;new;NniC$;1|
             |ISTRING;empty;$;2| (|Boolean|) |ISTRING;empty?;$B;3|
             |ISTRING;#;$Nni;4| |ISTRING;=;2$B;5| |ISTRING;<;2$B;6|
             |ISTRING;concat;3$;7| |ISTRING;copy;2$;8| (|Integer|)
             (|UniversalSegment| 18) (0 . SEGMENT)
```

```
   |ISTRING;elt;$Us$;31| (6 . SEGMENT)
   |ISTRING;insert;2$I$;9| (|String|) (|OutputForm|)
   (11 . |outputForm|) |ISTRING;coerce;$Of;10|
   |ISTRING;minIndex;$I;11| (|CharacterClass|)
   (16 . |upperCase|) (20 . |upperCase|) (|Mapping| 8 8)
   (25 . |map!|) |ISTRING;upperCase!;2$;12|
   (31 . |lowerCase|) (35 . |lowerCase|)
   |ISTRING;lowerCase!;2$;13| |ISTRING;latex;$S;14|
   (40 . |lo|) (45 . |hasHi|) (50 . |hi|) (55 . |maxIndex|)
   (60 . |space|) |ISTRING;replace;$Us2$;15|
   |ISTRING;setelt;$I2C;16| |ISTRING;substring?;2$IB;17|
   |ISTRING;position;2$2I;18| |ISTRING;position;C$2I;19|
   (64 . |member?|) |ISTRING;position;Cc$2I;20|
   |ISTRING;suffix?;2$B;21| |ISTRING;elt;$IC;30| (70 . =)
   (|List| $$) (76 . |empty|) (80 . |concat|)
   (86 . |reverse!|) (|List| $) |ISTRING;split;$CL;22|
   |ISTRING;split;$CcL;23| |ISTRING;leftTrim;$C$;24|
   |ISTRING;leftTrim;$Cc$;25| |ISTRING;rightTrim;$C$;26|
   |ISTRING;rightTrim;$Cc$;27| |ISTRING;copyInto!;2$I$;29|
   |ISTRING;concat;L$;28| (91 . |ord|) |ISTRING;hash;$I;32|
   |ISTRING;match;2$CNni;33| (96 . |prefix?|)
   |ISTRING;match?;2$CB;34| (|List| 8) (|List| 74)
   (|Equation| 8) (|Mapping| 8 8 8) (|InputForm|)
   (|SingleInteger|) (|Mapping| 11 8) (|Mapping| 11 8 8)
   (|Void|) (|Union| 8 '"failed") (|List| 18))
'#(~= 102 |upperCase!| 108 |upperCase| 113 |trim| 118 |swap!|
   130 |suffix?| 137 |substring?| 143 |split| 150 |sorted?|
   162 |sort!| 173 |sort| 184 |size?| 195 |setelt| 201
   |select| 215 |sample| 221 |rightTrim| 225 |reverse!| 237
   |reverse| 242 |replace| 247 |removeDuplicates| 254
   |remove| 259 |reduce| 271 |qsetelt!| 292 |qelt| 299
   |prefix?| 305 |position| 311 |parts| 344 |new| 349 |more?|
   355 |minIndex| 361 |min| 366 |merge| 372 |members| 385
   |member?| 390 |maxIndex| 396 |max| 401 |match?| 407
   |match| 414 |map!| 421 |map| 427 |lowerCase!| 440
   |lowerCase| 445 |less?| 450 |leftTrim| 456 |latex| 468
   |insert| 473 |indices| 487 |index?| 492 |hash| 498 |first|
   508 |find| 513 |fill!| 519 |every?| 525 |eval| 531 |eq?|
   557 |entry?| 563 |entries| 569 |empty?| 574 |empty| 579
   |elt| 583 |delete| 608 |count| 620 |copyInto!| 632 |copy|
   639 |convert| 644 |construct| 649 |concat| 654 |coerce|
   677 |any?| 687 >= 693 > 699 = 705 <= 711 < 717 |#| 723)
'((|shallowlyMutable| . 0) (|finiteAggregate| . 0))
(CONS (|makeByteWordVec2| 7
         '(0 0 0 0 0 0 0 3 0 0 7 4 0 0 7 1 2 4))
      (CONS '#(|StringAggregate&|
               |OneDimensionalArrayAggregate&|
               |FiniteLinearAggregate&| |LinearAggregate&|
               |IndexedAggregate&| |Collection&|
               |HomogeneousAggregate&| |OrderedSet&|
```

```
   |Aggregate&| |EltableAggregate&| |Evalable&|
   |SetCategory&| NIL NIL |InnerEvalable&| NIL
   NIL |BasicType&|)
(CONS '#((|StringAggregate|)
         (|OneDimensionalArrayAggregate| 8)
         (|FiniteLinearAggregate| 8)
         (|LinearAggregate| 8)
         (|IndexedAggregate| 18 8)
         (|Collection| 8)
         (|HomogeneousAggregate| 8)
         (|OrderedSet|) (|Aggregate|)
         (|EltableAggregate| 18 8) (|Evalable| 8)
         (|SetCategory|) (|Type|)
         (|Eltable| 18 8) (|InnerEvalable| 8 8)
         (|CoercibleTo| 25) (|ConvertibleTo| 76)
         (|BasicType|))
      (|makeByteWordVec2| 82
          '(2 19 0 18 18 20 1 19 0 18 22 1 25 0
            24 26 0 29 0 30 1 8 0 0 31 2 0 0 32 0
            33 0 29 0 35 1 8 0 0 36 1 19 18 0 39
            1 19 11 0 40 1 19 18 0 41 1 0 18 0 42
            0 8 0 43 2 29 11 8 0 49 2 8 11 0 0 53
            0 54 0 55 2 54 0 2 0 56 1 54 0 0 57 1
            8 18 0 67 2 0 11 0 0 70 2 1 11 0 0 1
            1 0 0 0 34 1 0 0 0 1 2 0 0 0 8 1 2 0
            0 0 29 1 3 0 80 0 18 18 1 2 0 11 0 0
            51 3 0 11 0 0 18 46 2 0 58 0 29 60 2
            0 58 0 8 59 1 3 11 0 1 2 0 11 79 0 1
            1 3 0 0 1 2 0 0 79 0 1 1 3 0 0 1 2 0
            0 79 0 1 2 0 11 0 7 1 3 0 8 0 19 8 1
            3 0 8 0 18 8 45 2 0 0 78 0 1 0 0 0 1
            2 0 0 0 8 63 2 0 0 0 29 64 1 0 0 0 1
            1 0 0 0 1 3 0 0 0 19 0 44 1 1 0 0 1 2
            1 0 8 0 1 2 0 0 78 0 1 4 1 8 75 0 8 8
            1 3 0 8 75 0 8 1 2 0 8 75 0 1 3 0 8 0
            18 8 1 2 0 8 0 18 1 2 0 11 0 0 70 3 1
            18 8 0 18 48 2 1 18 8 0 1 3 0 18 29 0
            18 50 3 0 18 0 0 18 47 2 0 18 78 0 1
            1 0 72 0 1 2 0 0 7 8 9 2 0 11 0 7 1 1
            5 18 0 28 2 3 0 0 0 1 2 3 0 0 0 1 3 0
            0 79 0 0 1 1 0 72 0 1 2 1 11 8 0 1 1
            5 18 0 42 2 3 0 0 0 1 3 0 11 0 0 8 71
            3 0 7 0 0 8 69 2 0 0 32 0 33 3 0 0 75
            0 0 1 2 0 0 32 0 1 1 0 0 0 37 1 0 0 0
            1 2 0 11 0 7 1 2 0 0 0 8 61 2 0 0 0
            29 62 1 1 24 0 38 3 0 0 8 0 18 1 3 0
            0 0 0 18 23 1 0 82 0 1 2 0 11 18 0 1
            1 1 77 0 1 1 0 18 0 68 1 5 8 0 1 2 0
            81 78 0 1 2 0 0 0 8 1 2 0 11 78 0 1 3
            6 0 0 72 72 1 3 6 0 0 8 8 1 2 6 0 0
```

```
                              73 1 2 6 0 0 74 1 2 0 11 0 0 1 2 1 11
                              8 0 1 1 0 72 0 1 1 0 11 0 12 0 0 0 10
                              2 0 0 0 0 1 2 0 0 0 19 21 2 0 8 0 18
                              52 3 0 8 0 18 8 1 2 0 0 0 18 1 2 0 0
                              0 19 1 2 1 7 8 0 1 2 0 7 78 0 1 3 0 0
                              0 0 18 65 1 0 0 0 17 1 2 76 0 1 1 0 0
                              72 1 1 0 0 58 66 2 0 0 0 0 16 2 0 0 0
                              8 1 2 0 0 8 0 1 1 1 25 0 27 1 0 0 8 1
                              2 0 11 78 0 1 2 3 11 0 0 1 2 3 11 0 0
                              1 2 1 11 0 0 14 2 3 11 0 0 1 2 3 11 0
                              0 15 1 0 7 0 13)))))
        '|lookupComplete|))
```

———-

28.7 LIST.lsp BOOTSTRAP

LIST depends on a chain of files. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **LIST** category which we can write into the **MID** directory. We compile the lisp code and copy the **LIST.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— LIST.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT (QUOTE |LIST;nil;$;1|) (QUOTE |SPADreplace|) (QUOTE (XLAM NIL NIL)))

(DEFUN |LIST;nil;$;1| (|$|) NIL)

(PUT (QUOTE |LIST;null;$B;2|) (QUOTE |SPADreplace|) (QUOTE NULL))

(DEFUN |LIST;null;$B;2| (|l| |$|) (NULL |l|))

(PUT (QUOTE |LIST;cons;S2$;3|) (QUOTE |SPADreplace|) (QUOTE CONS))

(DEFUN |LIST;cons;S2$;3| (|s| |l| |$|) (CONS |s| |l|))

(PUT (QUOTE |LIST;append;3$;4|) (QUOTE |SPADreplace|) (QUOTE APPEND))

(DEFUN |LIST;append;3$;4| (|l| |t| |$|) (APPEND |l| |t|))

(DEFUN |LIST;writeOMList| (|dev| |x| |$|)
 (SEQ
  (SPADCALL |dev| (QREFELT |$| 14))
```

```
  (SPADCALL |dev| "list1" "list" (QREFELT |$| 16))
  (SEQ
   G190
   (COND
    ((NULL (COND ((NULL |x|) (QUOTE NIL)) ((QUOTE T) (QUOTE T)))) (GO G191)))
   (SEQ
    (SPADCALL |dev| (|SPADfirst| |x|) (QUOTE NIL) (QREFELT |$| 17))
    (EXIT (LETT |x| (CDR |x|) |LIST;writeOMList|)))
   NIL
   (GO G190)
   G191
   (EXIT NIL))
  (EXIT (SPADCALL |dev| (QREFELT |$| 18)))))

(DEFUN |LIST;OMwrite;$S;6| (|x| |$|)
 (PROG (|sp| |dev| |s|)
  (RETURN
   (SEQ
    (LETT |s| "" |LIST;OMwrite;$S;6|)
    (LETT |sp| (|OM-STRINGTOSTRINGPTR| |s|) |LIST;OMwrite;$S;6|)
    (LETT |dev|
     (SPADCALL |sp| (SPADCALL (QREFELT |$| 20)) (QREFELT |$| 21))
     |LIST;OMwrite;$S;6|)
    (SPADCALL |dev| (QREFELT |$| 22))
    (|LIST;writeOMList| |dev| |x| |$|)
    (SPADCALL |dev| (QREFELT |$| 23))
    (SPADCALL |dev| (QREFELT |$| 24))
    (LETT |s| (|OM-STRINGPTRTOSTRING| |sp|) |LIST;OMwrite;$S;6|)
    (EXIT |s|)))))

(DEFUN |LIST;OMwrite;$BS;7| (|x| |wholeObj| |$|)
 (PROG (|sp| |dev| |s|)
  (RETURN
   (SEQ
    (LETT |s| "" |LIST;OMwrite;$BS;7|)
    (LETT |sp| (|OM-STRINGTOSTRINGPTR| |s|) |LIST;OMwrite;$BS;7|)
    (LETT |dev|
     (SPADCALL |sp| (SPADCALL (QREFELT |$| 20)) (QREFELT |$| 21))
     |LIST;OMwrite;$BS;7|)
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 22))))
    (|LIST;writeOMList| |dev| |x| |$|)
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 23))))
    (SPADCALL |dev| (QREFELT |$| 24))
    (LETT |s| (|OM-STRINGPTRTOSTRING| |sp|) |LIST;OMwrite;$BS;7|)
    (EXIT |s|)))))

(DEFUN |LIST;OMwrite;Omd$V;8| (|dev| |x| |$|)
 (SEQ
  (SPADCALL |dev| (QREFELT |$| 22))
  (|LIST;writeOMList| |dev| |x| |$|)
```

```
  (EXIT (SPADCALL |dev| (QREFELT |$| 23)))))

(DEFUN |LIST;OMwrite;Omd$BV;9| (|dev| |x| |wholeObj| |$|)
 (SEQ
  (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 22))))
  (|LIST;writeOMList| |dev| |x| |$|)
  (EXIT (COND (|wholeObj| (SPADCALL |dev| (QREFELT |$| 23)))))))

(DEFUN |LIST;setUnion;3$;10| (|l1| |l2| |$|)
 (SPADCALL (SPADCALL |l1| |l2| (QREFELT |$| 29)) (QREFELT |$| 30)))

(DEFUN |LIST;setIntersection;3$;11| (|l1| |l2| |$|)
 (PROG (|u|)
  (RETURN
   (SEQ
    (LETT |u| NIL |LIST;setIntersection;3$;11|)
    (LETT |l1| (SPADCALL |l1| (QREFELT |$| 30)) |LIST;setIntersection;3$;11|)
    (SEQ
     G190
     (COND
      ((NULL (COND ((NULL |l1|) (QUOTE NIL)) ((QUOTE T) (QUOTE T))))
       (GO G191)))
     (SEQ
      (COND
       ((SPADCALL (|SPADfirst| |l1|) |l2| (QREFELT |$| 32))
        (LETT |u| (CONS (|SPADfirst| |l1|) |u|) |LIST;setIntersection;3$;11|)))
      (EXIT (LETT |l1| (CDR |l1|) |LIST;setIntersection;3$;11|)))
     NIL
     (GO G190)
     G191
     (EXIT NIL))
    (EXIT |u|)))))

(DEFUN |LIST;setDifference;3$;12| (|l1| |l2| |$|)
 (PROG (|l11| |lu|)
  (RETURN
   (SEQ
    (LETT |l1| (SPADCALL |l1| (QREFELT |$| 30)) |LIST;setDifference;3$;12|)
    (LETT |lu| NIL |LIST;setDifference;3$;12|)
    (SEQ
     G190
     (COND
      ((NULL (COND ((NULL |l1|) (QUOTE NIL)) ((QUOTE T) (QUOTE T))))
       (GO G191)))
     (SEQ
      (LETT |l11|
       (SPADCALL |l1| 1 (QREFELT |$| 35))
       |LIST;setDifference;3$;12|)
      (COND
       ((NULL (SPADCALL |l11| |l2| (QREFELT |$| 32)))
```

```
        (LETT |lu| (CONS |l11| |lu|) |LIST;setDifference;3$;12|)))
       (EXIT (LETT |l1| (CDR |l1|) |LIST;setDifference;3$;12|)))
      NIL
      (GO G190)
      G191
      (EXIT NIL))
     (EXIT |lu|)))))

(DEFUN |LIST;convert;$If;13| (|x| $)
  (PROG (G102544 |a| G102545)
    (RETURN
      (SEQ (SPADCALL
             (CONS (SPADCALL (SPADCALL "construct" (QREFELT $ 38))
                     (QREFELT $ 40))
                   (PROGN
                     (LETT G102544 NIL |LIST;convert;$If;13|)
                     (SEQ (LETT |a| NIL |LIST;convert;$If;13|)
                          (LETT G102545 |x| |LIST;convert;$If;13|)
                          G190
                          (COND
                            ((OR (ATOM G102545)
                                 (PROGN
                                   (LETT |a| (CAR G102545)
                                    |LIST;convert;$If;13|)
                                   NIL))
                             (GO G191)))
                          (SEQ (EXIT (LETT G102544
                                      (CONS
                                       (SPADCALL |a| (QREFELT $ 41))
                                       G102544)
                                      |LIST;convert;$If;13|)))
                          (LETT G102545 (CDR G102545)
                                |LIST;convert;$If;13|)
                          (GO G190) G191 (EXIT (NREVERSE0 G102544)))))
             (QREFELT $ 43))))))

(DEFUN |List| (G102555)
  (PROG ()
    (RETURN
      (PROG (G102556)
        (RETURN
          (COND
            ((LETT G102556
                   (|lassocShiftWithFunction|
                       (LIST (|devaluate| G102555))
                       (HGET |$ConstructorCache| '|List|)
                       '|domainEqualList|)
                   |List|)
             (|CDRwithIncrement| G102556))
            ('T
```

```
            (UNWIND-PROTECT
              (PROG1 (|List;| G102555) (LETT G102556 T |List|))
              (COND
                ((NOT G102556) (HREM |$ConstructorCache| '|List|))))))))))))

(DEFUN |List;| (|#1|)
  (PROG (DV$1 |dv$| $ G102554 |pv$|)
    (RETURN
      (PROGN
        (LETT DV$1 (|devaluate| |#1|) |List|)
        (LETT |dv$| (LIST '|List| DV$1) |List|)
        (LETT $ (make-array 62) |List|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$|
                  (|buildPredVector| 0 0
                      (LIST (|HasCategory| |#1| '(|SetCategory|))
                            (|HasCategory| |#1|
                                '(|ConvertibleTo| (|InputForm|)))
                            (LETT G102554
                                  (|HasCategory| |#1| '(|OrderedSet|))
                                  |List|)
                            (OR G102554
                                (|HasCategory| |#1| '(|SetCategory|)))
                            (|HasCategory| |#1| '(|OpenMath|))
                            (|HasCategory| (|Integer|) '(|OrderedSet|))
                            (AND (|HasCategory| |#1|
                                     (LIST '|Evalable|
                                      (|devaluate| |#1|)))
                                 (|HasCategory| |#1| '(|SetCategory|)))
                            (OR (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     G102554)
                                (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     (|HasCategory| |#1|
                                      '(|SetCategory|))))))
                   |List|))
        (|haddProp| |$ConstructorCache| '|List| (LIST DV$1) (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 6 |#1|)
        (COND
          ((|testBitVector| |pv$| 5)
           (PROGN
             (QSETREFV $ 25
                 (CONS (|dispatchFunction| |LIST;OMwrite;$S;6|) $))
             (QSETREFV $ 26
                 (CONS (|dispatchFunction| |LIST;OMwrite;$BS;7|) $))
```

```
            (QSETREFV $ 27
                (CONS (|dispatchFunction| |LIST;OMwrite;Omd$V;8|) $))
            (QSETREFV $ 28
                (CONS (|dispatchFunction| |LIST;OMwrite;Omd$BV;9|) $)))))
        (COND
          ((|testBitVector| |pv$| 1)
           (PROGN
            (QSETREFV $ 31
                (CONS (|dispatchFunction| |LIST;setUnion;3$;10|) $))
            (QSETREFV $ 33
                (CONS (|dispatchFunction|
                          |LIST;setIntersection;3$;11|)
                      $))
            (QSETREFV $ 36
                (CONS (|dispatchFunction| |LIST;setDifference;3$;12|)
                      $)))))
        (COND
          ((|testBitVector| |pv$| 2)
           (QSETREFV $ 44
               (CONS (|dispatchFunction| |LIST;convert;$If;13|) $))))
        $))))

(setf (get
 (QUOTE |List|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE #(
   NIL NIL NIL NIL NIL (|IndexedList| 6 (NRTEVAL 1)) (|local| |#1|)
   |LIST;nil;$;1| (|Boolean|) |LIST;null;$B;2| |LIST;cons;S2$;3|
   |LIST;append;3$;4| (|Void|) (|OpenMathDevice|) (0 . |OMputApp|)
   (|String|) (5 . |OMputSymbol|) (12 . |OMwrite|) (19 . |OMputEndApp|)
   (|OpenMathEncoding|) (24 . |OMencodingXML|) (28 . |OMopenString|)
   (34 . |OMputObject|) (39 . |OMputEndObject|) (44 . |OMclose|)
   (49 . |OMwrite|) (54 . |OMwrite|) (60 . |OMwrite|) (66 . |OMwrite|)
   (73 . |concat|) (79 . |removeDuplicates|) (84 . |setUnion|)
   (90 . |member?|) (96 . |setIntersection|) (|Integer|) (102 . |elt|)
   (108 . |setDifference|) (|Symbol|) (114 . |coerce|) (|InputForm|)
   (119 . |convert|) (124 . |convert|) (|List| |$|) (129 . |convert|)
   (134 . |convert|) (|Mapping| 6 6 6) (|NonNegativeInteger|)
   (|List| 6) (|List| 49) (|Equation| 6) (|Mapping| 8 6)
   (|Mapping| 8 6 6) (|UniversalSegment| 34) (QUOTE "last")
   (QUOTE "rest") (QUOTE "first") (QUOTE "value") (|Mapping| 6 6)
   (|SingleInteger|) (|OutputForm|) (|List| 34) (|Union| 6 (QUOTE "failed"))))
  (QUOTE #(|setUnion| 139 |setIntersection| 145 |setDifference| 151
   |removeDuplicates| 157 |null| 162 |nil| 167 |member?| 171 |elt| 177
   |convert| 183 |cons| 188 |concat| 194 |append| 200 |OMwrite| 206))
  (QUOTE ((|shallowlyMutable| . 0) (|finiteAggregate| . 0)))
  (CONS
   (|makeByteWordVec2| 8 (QUOTE (0 0 0 0 0 0 0 0 0 0 3 0 0 8 4 0 0 8 1 2 4 5)))
   (CONS (QUOTE #(
```

```
    |ListAggregate&| |StreamAggregate&| |ExtensibleLinearAggregate&|
    |FiniteLinearAggregate&| |UnaryRecursiveAggregate&| |LinearAggregate&|
    |RecursiveAggregate&| |IndexedAggregate&| |Collection&|
    |HomogeneousAggregate&| |OrderedSet&| |Aggregate&| |EltableAggregate&|
    |Evalable&| |SetCategory&| NIL NIL |InnerEvalable&| NIL NIL
    |BasicType&| NIL))
   (CONS
     (QUOTE #((|ListAggregate| 6) (|StreamAggregate| 6)
      (|ExtensibleLinearAggregate| 6) (|FiniteLinearAggregate| 6)
      (|UnaryRecursiveAggregate| 6) (|LinearAggregate| 6)
      (|RecursiveAggregate| 6) (|IndexedAggregate| 34 6) (|Collection| 6)
      (|HomogeneousAggregate| 6) (|OrderedSet|) (|Aggregate|)
      (|EltableAggregate| 34 6) (|Evalable| 6) (|SetCategory|)
      (|Type|) (|Eltable| 34 6) (|InnerEvalable| 6 6) (|CoercibleTo| 59)
      (|ConvertibleTo| 39) (|BasicType|) (|OpenMath|)))
    (|makeByteWordVec2| 44
     (QUOTE (
      1 13 12 0 14 3 13 12 0 15 15 16 3 6 12 13 0 8 17 1 13 12 0 18 0
      19 0 20 2 13 0 15 19 21 1 13 12 0 22 1 13 12 0 23 1 13 12 0 24 1 0 15
      0 25 2 0 15 0 8 26 2 0 12 13 0 27 3 0 12 13 0 8 28 2 0 0 0 0 29 1 0 0
      0 30 2 0 0 0 0 31 2 0 8 6 0 32 2 0 0 0 0 33 2 0 6 0 34 35 2 0 0 0 0 36
      1 37 0 15 38 1 39 0 37 40 1 6 39 0 41 1 39 0 42 43 1 0 39 0 44 2 1 0 0
      0 31 2 1 0 0 0 33 2 1 0 0 0 36 1 1 0 0 30 1 0 8 0 9 0 0 0 7 2 1 8 6 0
      32 2 0 6 0 34 35 1 2 39 0 44 2 0 0 6 0 10 2 0 0 0 0 29 2 0 0 0 0 11 3
      5 12 13 0 8 28 2 5 12 13 0 27 1 5 15 0 25 2 5 15 0 8 26))))))
  (QUOTE |lookupIncomplete|)))
```

———-

28.8 NNI.lsp BOOTSTRAP

NNI depends on itself. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **NNI** category which we can write into the **MID** directory. We compile the lisp code and copy the **NNI.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— NNI.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(SETQ |$CategoryFrame|
      (|put| '|NonNegativeInteger| '|SuperDomain| '(|Integer|)
             (|put| '(|Integer|) '|SubDomain|
                    (CONS '(|NonNegativeInteger| COND ((< |#1| 0) 'NIL)
                                ('T 'T))
                          (DELASC '|NonNegativeInteger|
```

```
                                (|get| '(|Integer|) '|SubDomain|
                                       |$CategoryFrame|)))
                    |$CategoryFrame|)))

(PUT '|NNI;sup;3$;1| '|SPADreplace| 'MAX)

(DEFUN |NNI;sup;3$;1| (|x| |y| |$|) (MAX |x| |y|))

(PUT '|NNI;shift;$I$;2| '|SPADreplace| 'ASH)

(DEFUN |NNI;shift;$I$;2| (|x| |n| |$|) (ASH |x| |n|))

(DEFUN |NNI;subtractIfCan;2$U;3| (|x| |y| |$|)
  (PROG (|c|)
    (RETURN
      (SEQ
        (LETT |c| (|-| |x| |y|) |NNI;subtractIfCan;2$U;3|)
        (EXIT
          (COND
            ((|<| |c| 0) (CONS 1 "failed"))
            ((QUOTE T) (CONS 0 |c|)))))))))

(DEFUN |NonNegativeInteger| ()
  (PROG ()
    (RETURN
      (PROG (G96708)
        (RETURN
          (COND
            ((LETT G96708
                   (HGET |$ConstructorCache| '|NonNegativeInteger|)
                   |NonNegativeInteger|)
             (|CDRwithIncrement| (CDAR G96708)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache|
                                   '|NonNegativeInteger|
                                   (LIST
                                    (CONS NIL
                                     (CONS 1 (|NonNegativeInteger;|))))))
                 (LETT G96708 T |NonNegativeInteger|))
               (COND
                 ((NOT G96708)
                  (HREM |$ConstructorCache| '|NonNegativeInteger|)))))))))))

(DEFUN |NonNegativeInteger;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|NonNegativeInteger|) |NonNegativeInteger|)
        (LETT $ (make-array 17) |NonNegativeInteger|)
```

```
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL)
                  |NonNegativeInteger|))
        (|haddProp| |$ConstructorCache| '|NonNegativeInteger| NIL
            (CONS 1 $))
        (|stuffDomainSlots| $)
        $))))

(setf (get
  (QUOTE |NonNegativeInteger|)
  (QUOTE |infovec|))
  (LIST
    (QUOTE
      #(NIL NIL NIL NIL NIL
        (|Integer|)
        |NNI;sup;3$;1|
        |NNI;shift;$I$;2|
        (|Union| |$| (QUOTE "failed"))
        |NNI;subtractIfCan;2$U;3|
        (|Record| (|:| |quotient| |$|) (|:| |remainder| |$|))
        (|PositiveInteger|)
        (|Boolean|)
        (|NonNegativeInteger|)
        (|SingleInteger|)
        (|String|)
        (|OutputForm|)))
    (QUOTE
      #(|~=| 0 |zero?| 6 |sup| 11 |subtractIfCan| 17 |shift| 23 |sample| 29
        |rem| 33 |recip| 39 |random| 44 |quo| 49 |one?| 55 |min| 60 |max| 66
        |latex| 72 |hash| 77 |gcd| 82 |exquo| 88 |divide| 94 |coerce| 100
        |^| 105 |Zero| 117 |One| 121 |>=| 125 |>| 131 |=| 137 |<=| 143
        |<| 149 |+| 155 |**| 161 |*| 173))
    (QUOTE ((((|commutative| "*") . 0)))
    (CONS
      (|makeByteWordVec2| 1 (QUOTE (0 0 0 0 0 0 0 0 0 0 0 0 0)))
      (CONS
        (QUOTE
          #(NIL NIL NIL NIL NIL
            |Monoid&|
            |AbelianMonoid&|
            |OrderedSet&|
            |SemiGroup&|
            |AbelianSemiGroup&|
            |SetCategory&|
            |BasicType&|
            NIL))
        (CONS
          (QUOTE
            #((|OrderedAbelianMonoidSup|)
```

```
            (|OrderedCancellationAbelianMonoid|)
            (|OrderedAbelianMonoid|)
            (|OrderedAbelianSemiGroup|)
            (|CancellationAbelianMonoid|)
            (|Monoid|)
            (|AbelianMonoid|)
            (|OrderedSet|)
            (|SemiGroup|)
            (|AbelianSemiGroup|)
            (|SetCategory|)
            (|BasicType|)
            (|CoercibleTo| 16)))
        (|makeByteWordVec2| 16
          (QUOTE
            (2 0 12 0 0 1 1 0 12 0 1 2 0 0 0 0 6 2 0 8 0 0 9 2 0 0 0 5 7 0 0
             0 1 2 0 0 0 0 1 1 0 8 0 1 1 0 0 0 1 2 0 0 0 0 1 1 0 12 0 1 2 0
             0 0 0 1 2 0 0 0 0 1 1 0 15 0 1 1 0 14 0 1 2 0 0 0 0 1 2 0 8 0 0
             1 2 0 10 0 0 1 1 0 16 0 1 2 0 0 0 11 1 2 0 0 0 13 1 0 0 0 1 0 0
             0 1 2 0 12 0 0 1 2 0 12 0 0 1 2 0 12 0 0 1 2 0 12 0 0 1 2 0 12
             0 0 1 2 0 0 0 0 1 2 0 0 0 11 1 2 0 0 0 13 1 2 0 0 0 0 0 1 2 0 0
             11 0 1 2 0 0 13 0 1))))))
    (QUOTE |lookupComplete|)))

(setf (get (QUOTE |NonNegativeInteger|) (QUOTE NILADIC)) T)
```

———-

28.9 OUTFORM.lsp BOOTSTRAP

OUTFORM depends on itself. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **OUTFORM** category which we can write into the **MID** directory. We compile the lisp code and copy the **OUTFORM.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— OUTFORM.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT (QUOTE |OUTFORM;print;$V;1|) (QUOTE |SPADreplace|) (QUOTE |mathprint|))

(DEFUN |OUTFORM;print;$V;1| (|x| |$|) (|mathprint| |x|))

(DEFUN |OUTFORM;message;S$;2| (|s| |$|)
 (COND
  ((SPADCALL |s| (QREFELT |$| 11)) (SPADCALL (QREFELT |$| 12)))
```

```
  ((QUOTE T) |s|)))

(DEFUN |OUTFORM;messagePrint;SV;3| (|s| |$|)
 (SPADCALL (SPADCALL |s| (QREFELT |$| 13)) (QREFELT |$| 8)))

(PUT (QUOTE |OUTFORM;=;2$B;4|) (QUOTE |SPADreplace|) (QUOTE EQUAL))

(DEFUN |OUTFORM;=;2$B;4| (|a| |b| |$|) (EQUAL |a| |b|))

(DEFUN |OUTFORM;=;3$;5| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "=" |$|) |a| |b|))

(PUT
 (QUOTE |OUTFORM;coerce;2$;6|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|a|) |a|)))

(DEFUN |OUTFORM;coerce;2$;6| (|a| |$|) |a|)

(PUT
 (QUOTE |OUTFORM;outputForm;I$;7|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|n|) |n|)))

(DEFUN |OUTFORM;outputForm;I$;7| (|n| |$|) |n|)

(PUT
 (QUOTE |OUTFORM;outputForm;S$;8|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|e|) |e|)))

(DEFUN |OUTFORM;outputForm;S$;8| (|e| |$|) |e|)

(PUT
 (QUOTE |OUTFORM;outputForm;Df$;9|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM (|f|) |f|)))

(DEFUN |OUTFORM;outputForm;Df$;9| (|f| |$|) |f|)

(PUT (QUOTE |OUTFORM;sform|) (QUOTE |SPADreplace|) (QUOTE (XLAM (|s|) |s|)))

(DEFUN |OUTFORM;sform| (|s| |$|) |s|)

(PUT (QUOTE |OUTFORM;eform|) (QUOTE |SPADreplace|) (QUOTE (XLAM (|e|) |e|)))

(DEFUN |OUTFORM;eform| (|e| |$|) |e|)

(PUT (QUOTE |OUTFORM;iform|) (QUOTE |SPADreplace|) (QUOTE (XLAM (|n|) |n|)))
```

```
(DEFUN |OUTFORM;iform| (|n| |$|) |n|)

(DEFUN |OUTFORM;outputForm;S$;13| (|s| |$|)
 (|OUTFORM;sform|
   (SPADCALL
    (SPADCALL (QREFELT |$| 26))
    (SPADCALL |s| (SPADCALL (QREFELT |$| 26)) (QREFELT |$| 27))
    (QREFELT |$| 28))
   |$|))

(PUT
 (QUOTE |OUTFORM;width;$I;14|)
 (QUOTE |SPADreplace|)
 (QUOTE |outformWidth|))

(DEFUN |OUTFORM;width;$I;14| (|a| |$|) (|outformWidth| |a|))

(PUT (QUOTE |OUTFORM;height;$I;15|) (QUOTE |SPADreplace|) (QUOTE |height|))

(DEFUN |OUTFORM;height;$I;15| (|a| |$|) (|height| |a|))

(PUT
 (QUOTE |OUTFORM;subHeight;$I;16|)
 (QUOTE |SPADreplace|)
 (QUOTE |subspan|))

(DEFUN |OUTFORM;subHeight;$I;16| (|a| |$|) (|subspan| |a|))

(PUT
 (QUOTE |OUTFORM;superHeight;$I;17|)
 (QUOTE |SPADreplace|)
 (QUOTE |superspan|))

(DEFUN |OUTFORM;superHeight;$I;17| (|a| |$|) (|superspan| |a|))

(PUT
 (QUOTE |OUTFORM;height;I;18|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL 20)))

(DEFUN |OUTFORM;height;I;18| (|$|) 20)

(PUT
 (QUOTE |OUTFORM;width;I;19|)
 (QUOTE |SPADreplace|)
 (QUOTE (XLAM NIL 66)))

(DEFUN |OUTFORM;width;I;19| (|$|) 66)

(DEFUN |OUTFORM;center;$I$;20| (|a| |w| |$|)
```

```
 (SPADCALL
  (SPADCALL
   (QUOTIENT2 (|-| |w| (SPADCALL |a| (QREFELT |$| 30))) 2)
   (QREFELT |$| 36))
  |a|
  (QREFELT |$| 37)))

(DEFUN |OUTFORM;left;$I$;21| (|a| |w| |$|)
 (SPADCALL
  |a|
  (SPADCALL (|-| |w| (SPADCALL |a| (QREFELT |$| 30))) (QREFELT |$| 36))
  (QREFELT |$| 37)))

(DEFUN |OUTFORM;right;$I$;22| (|a| |w| |$|)
 (SPADCALL
  (SPADCALL (|-| |w| (SPADCALL |a| (QREFELT |$| 30))) (QREFELT |$| 36))
  |a|
  (QREFELT |$| 37)))

(DEFUN |OUTFORM;center;2$;23| (|a| |$|)
 (SPADCALL |a| (SPADCALL (QREFELT |$| 35)) (QREFELT |$| 38)))

(DEFUN |OUTFORM;left;2$;24| (|a| |$|)
 (SPADCALL |a| (SPADCALL (QREFELT |$| 35)) (QREFELT |$| 39)))

(DEFUN |OUTFORM;right;2$;25| (|a| |$|)
 (SPADCALL |a| (SPADCALL (QREFELT |$| 35)) (QREFELT |$| 40)))

(DEFUN |OUTFORM;vspace;I$;26| (|n| |$|)
 (COND
  ((EQL |n| 0) (SPADCALL (QREFELT |$| 12)))
  ((QUOTE T)
   (SPADCALL
    (|OUTFORM;sform| " " |$|)
    (SPADCALL (|-| |n| 1) (QREFELT |$| 44))
    (QREFELT |$| 45)))))

(DEFUN |OUTFORM;hspace;I$;27| (|n| |$|)
 (COND
  ((EQL |n| 0) (SPADCALL (QREFELT |$| 12)))
  ((QUOTE T) (|OUTFORM;sform| (|fillerSpaces| |n|) |$|))))

(DEFUN |OUTFORM;rspace;2I$;28| (|n| |m| |$|)
 (COND
  ((OR (EQL |n| 0) (EQL |m| 0)) (SPADCALL (QREFELT |$| 12)))
  ((QUOTE T)
   (SPADCALL
    (SPADCALL |n| (QREFELT |$| 36))
    (SPADCALL |n| (|-| |m| 1) (QREFELT |$| 46))
    (QREFELT |$| 45)))))
```

```
(DEFUN |OUTFORM;matrix;L$;29| (|ll| $)
  (PROG (G82748 |l| G82749 |lv|)
    (RETURN
      (SEQ (LETT |lv|
                 (PROGN
                   (LETT G82748 NIL |OUTFORM;matrix;L$;29|)
                   (SEQ (LETT |l| NIL |OUTFORM;matrix;L$;29|)
                        (LETT G82749 |ll| |OUTFORM;matrix;L$;29|) G190
                        (COND
                          ((OR (ATOM G82749)
                               (PROGN
                                 (LETT |l| (CAR G82749)
                                       |OUTFORM;matrix;L$;29|)
                                 NIL))
                           (GO G191)))
                        (SEQ (EXIT (LETT G82748
                                         (CONS (LIST2VEC |l|) G82748)
                                         |OUTFORM;matrix;L$;29|)))
                        (LETT G82749 (CDR G82749)
                              |OUTFORM;matrix;L$;29|)
                        (GO G190) G191 (EXIT (NREVERSE0 G82748))))
                 |OUTFORM;matrix;L$;29|)
           (EXIT (CONS (|OUTFORM;eform| 'MATRIX $) (LIST2VEC |lv|)))))))

(DEFUN |OUTFORM;pile;L$;30| (|l| |$|)
 (CONS (|OUTFORM;eform| (QUOTE SC) |$|) |l|))

(DEFUN |OUTFORM;commaSeparate;L$;31| (|l| |$|)
 (CONS (|OUTFORM;eform| (QUOTE AGGLST) |$|) |l|))

(DEFUN |OUTFORM;semicolonSeparate;L$;32| (|l| |$|)
 (CONS (|OUTFORM;eform| (QUOTE AGGSET) |$|) |l|))

(DEFUN |OUTFORM;blankSeparate;L$;33| (|l| $)
  (PROG (|c| |u| G82757 |l1|)
    (RETURN
      (SEQ (LETT |c| (|OUTFORM;eform| 'CONCATB $)
                 |OUTFORM;blankSeparate;L$;33|)
           (LETT |l1| NIL |OUTFORM;blankSeparate;L$;33|)
           (SEQ (LETT |u| NIL |OUTFORM;blankSeparate;L$;33|)
                (LETT G82757 (SPADCALL |l| (QREFELT $ 53))
                      |OUTFORM;blankSeparate;L$;33|)
                G190
                (COND
                  ((OR (ATOM G82757)
                       (PROGN
                         (LETT |u| (CAR G82757)
                               |OUTFORM;blankSeparate;L$;33|)
                         NIL))
```

```
                  (GO G191)))
               (SEQ (EXIT (COND
                           ((EQCAR |u| |c|)
                            (LETT |l1|
                                  (SPADCALL (CDR |u|) |l1|
                                   (QREFELT $ 54))
                                  |OUTFORM;blankSeparate;L$;33|))
                           ('T
                            (LETT |l1| (CONS |u| |l1|)
                                  |OUTFORM;blankSeparate;L$;33|)))))
               (LETT G82757 (CDR G82757)
                     |OUTFORM;blankSeparate;L$;33|)
               (GO G190) G191 (EXIT NIL))
          (EXIT (CONS |c| |l1|))))))

(DEFUN |OUTFORM;brace;2$;34| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE BRACE) |$|) |a|))

(DEFUN |OUTFORM;brace;L$;35| (|l| |$|)
 (SPADCALL (SPADCALL |l| (QREFELT |$| 51)) (QREFELT |$| 56)))

(DEFUN |OUTFORM;bracket;2$;36| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE BRACKET) |$|) |a|))

(DEFUN |OUTFORM;bracket;L$;37| (|l| |$|)
 (SPADCALL (SPADCALL |l| (QREFELT |$| 51)) (QREFELT |$| 58)))

(DEFUN |OUTFORM;paren;2$;38| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE PAREN) |$|) |a|))

(DEFUN |OUTFORM;paren;L$;39| (|l| |$|)
 (SPADCALL (SPADCALL |l| (QREFELT |$| 51)) (QREFELT |$| 60)))

(DEFUN |OUTFORM;sub;3$;40| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SUB) |$|) |a| |b|))

(DEFUN |OUTFORM;super;3$;41| (|a| |b| |$|)
 (LIST
  (|OUTFORM;eform| (QUOTE SUPERSUB) |$|)
  |a|
  (|OUTFORM;sform| " " |$|) |b|))

(DEFUN |OUTFORM;presub;3$;42| (|a| |b| |$|)
 (LIST
  (|OUTFORM;eform| (QUOTE SUPERSUB) |$|)
  |a|
  (|OUTFORM;sform| " " |$|)
  (|OUTFORM;sform| " " |$|)
  (|OUTFORM;sform| " " |$|)
  |b|))
```

```
(DEFUN |OUTFORM;presuper;3$;43| (|a| |b| |$|)
 (LIST
  (|OUTFORM;eform| (QUOTE SUPERSUB) |$|)
  |a|
  (|OUTFORM;sform| " " |$|)
  (|OUTFORM;sform| " " |$|)
  |b|))

(DEFUN |OUTFORM;scripts;$L$;44| (|a| |l| |$|)
 (COND
  ((SPADCALL |l| (QREFELT |$| 66)) |a|)
  ((SPADCALL (SPADCALL |l| (QREFELT |$| 67)) (QREFELT |$| 66))
    (SPADCALL |a| (SPADCALL |l| (QREFELT |$| 68)) (QREFELT |$| 62)))
  ((QUOTE T) (CONS (|OUTFORM;eform| (QUOTE SUPERSUB) |$|) (CONS |a| |l|)))))

(DEFUN |OUTFORM;supersub;$L$;45| (|a| |l| |$|)
 (SEQ
  (COND
   ((ODDP (SPADCALL |l| (QREFELT |$| 71)))
    (LETT |l|
     (SPADCALL |l| (LIST (SPADCALL (QREFELT |$| 12))) (QREFELT |$| 73))
     |OUTFORM;supersub;$L$;45|)))
  (EXIT (CONS (|OUTFORM;eform| (QUOTE ALTSUPERSUB) |$|) (CONS |a| |l|)))))

(DEFUN |OUTFORM;hconcat;3$;46| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE CONCAT) |$|) |a| |b|))

(DEFUN |OUTFORM;hconcat;L$;47| (|l| |$|)
 (CONS (|OUTFORM;eform| (QUOTE CONCAT) |$|) |l|))

(DEFUN |OUTFORM;vconcat;3$;48| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE VCONCAT) |$|) |a| |b|))

(DEFUN |OUTFORM;vconcat;L$;49| (|l| |$|)
 (CONS (|OUTFORM;eform| (QUOTE VCONCAT) |$|) |l|))

(DEFUN |OUTFORM;^=;3$;50| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "^=" |$|) |a| |b|))

(DEFUN |OUTFORM;<;3$;51| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "<" |$|) |a| |b|))

(DEFUN |OUTFORM;>;3$;52| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| ">" |$|) |a| |b|))

(DEFUN |OUTFORM;<=;3$;53| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "<=" |$|) |a| |b|))

(DEFUN |OUTFORM;>=;3$;54| (|a| |b| |$|)
```

```
 (LIST (|OUTFORM;sform| ">=" |$|) |a| |b|))

(DEFUN |OUTFORM;+;3$;55| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "+" |$|) |a| |b|))

(DEFUN |OUTFORM;-;3$;56| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "-" |$|) |a| |b|))

(DEFUN |OUTFORM;-;2$;57| (|a| |$|)
 (LIST (|OUTFORM;sform| "-" |$|) |a|))

(DEFUN |OUTFORM;*;3$;58| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "*" |$|) |a| |b|))

(DEFUN |OUTFORM;/;3$;59| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "/" |$|) |a| |b|))

(DEFUN |OUTFORM;**;3$;60| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "**" |$|) |a| |b|))

(DEFUN |OUTFORM;div;3$;61| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "div" |$|) |a| |b|))

(DEFUN |OUTFORM;rem;3$;62| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "rem" |$|) |a| |b|))

(DEFUN |OUTFORM;quo;3$;63| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "quo" |$|) |a| |b|))

(DEFUN |OUTFORM;exquo;3$;64| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "exquo" |$|) |a| |b|))

(DEFUN |OUTFORM;and;3$;65| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "and" |$|) |a| |b|))

(DEFUN |OUTFORM;or;3$;66| (|a| |b| |$|)
 (LIST (|OUTFORM;sform| "or" |$|) |a| |b|))

(DEFUN |OUTFORM;not;2$;67| (|a| |$|)
 (LIST (|OUTFORM;sform| "not" |$|) |a|))

(DEFUN |OUTFORM;SEGMENT;3$;68| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SEGMENT) |$|) |a| |b|))

(DEFUN |OUTFORM;SEGMENT;2$;69| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SEGMENT) |$|) |a|))

(DEFUN |OUTFORM;binomial;3$;70| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE BINOMIAL) |$|) |a| |b|))
```

```
(DEFUN |OUTFORM;empty;$;71| (|$|)
 (LIST (|OUTFORM;eform| (QUOTE NOTHING) |$|)))

(DEFUN |OUTFORM;infix?;$B;72| (|a| $)
  (PROG (G82802 |e|)
    (RETURN
      (SEQ (EXIT (SEQ (LETT |e|
                            (COND
                              ((IDENTP |a|) |a|)
                              ((STRINGP |a|) (INTERN |a|))
                              ('T
                               (PROGN
                                 (LETT G82802 'NIL
                                       |OUTFORM;infix?;$B;72|)
                                 (GO G82802))))
                            |OUTFORM;infix?;$B;72|)
                      (EXIT (COND ((GET |e| 'INFIXOP) 'T) ('T 'NIL)))))
           G82802 (EXIT G82802)))))

(PUT (QUOTE |OUTFORM;elt;$L$;73|) (QUOTE |SPADreplace|) (QUOTE CONS))

(DEFUN |OUTFORM;elt;$L$;73| (|a| |l| |$|) (CONS |a| |l|))

(DEFUN |OUTFORM;prefix;$L$;74| (|a| |l| |$|)
 (COND
  ((NULL (SPADCALL |a| (QREFELT |$| 98))) (CONS |a| |l|))
  ((QUOTE T)
   (SPADCALL |a|
    (SPADCALL (SPADCALL |l| (QREFELT |$| 51)) (QREFELT |$| 60))
    (QREFELT |$| 37)))))

(DEFUN |OUTFORM;infix;$L$;75| (|a| |l| |$|)
 (COND
  ((SPADCALL |l| (QREFELT |$| 66)) (SPADCALL (QREFELT |$| 12)))
  ((SPADCALL (SPADCALL |l| (QREFELT |$| 67)) (QREFELT |$| 66))
    (SPADCALL |l| (QREFELT |$| 68)))
  ((SPADCALL |a| (QREFELT |$| 98)) (CONS |a| |l|))
  ((QUOTE T)
   (SPADCALL
    (LIST
     (SPADCALL |l| (QREFELT |$| 68))
     |a|
     (SPADCALL |a| (SPADCALL |l| (QREFELT |$| 101)) (QREFELT |$| 102)))
    (QREFELT |$| 75)))))

(DEFUN |OUTFORM;infix;4$;76| (|a| |b| |c| |$|)
 (COND
  ((SPADCALL |a| (QREFELT |$| 98)) (LIST |a| |b| |c|))
  ((QUOTE T) (SPADCALL (LIST |b| |a| |c|) (QREFELT |$| 75)))))
```

```
(DEFUN |OUTFORM;postfix;3$;77| (|a| |b| |$|)
 (SPADCALL |b| |a| (QREFELT |$| 37)))

(DEFUN |OUTFORM;string;2$;78| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE STRING) |$|) |a|))

(DEFUN |OUTFORM;quote;2$;79| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE QUOTE) |$|) |a|))

(DEFUN |OUTFORM;overbar;2$;80| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE OVERBAR) |$|) |a|))

(DEFUN |OUTFORM;dot;2$;81| (|a| |$|)
 (SPADCALL |a| (|OUTFORM;sform| "." |$|) (QREFELT |$| 63)))

(DEFUN |OUTFORM;prime;2$;82| (|a| |$|)
 (SPADCALL |a| (|OUTFORM;sform| "," |$|) (QREFELT |$| 63)))

(DEFUN |OUTFORM;dot;$Nni$;83| (|a| |nn| |$|)
 (PROG (|s|)
  (RETURN
   (SEQ
    (LETT |s|
     (|MAKE-FULL-CVEC| |nn| (SPADCALL "." (QREFELT |$| 110)))
     |OUTFORM;dot;$Nni$;83|)
    (EXIT (SPADCALL |a| (|OUTFORM;sform| |s| |$|) (QREFELT |$| 63)))))))

(DEFUN |OUTFORM;prime;$Nni$;84| (|a| |nn| |$|)
 (PROG (|s|)
  (RETURN
   (SEQ
    (LETT |s|
     (|MAKE-FULL-CVEC| |nn| (SPADCALL "," (QREFELT |$| 110)))
     |OUTFORM;prime;$Nni$;84|)
    (EXIT (SPADCALL |a| (|OUTFORM;sform| |s| |$|) (QREFELT |$| 63)))))))

(DEFUN |OUTFORM;overlabel;3$;85| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE OVERLABEL) |$|) |a| |b|))

(DEFUN |OUTFORM;box;2$;86| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE BOX) |$|) |a|))

(DEFUN |OUTFORM;zag;3$;87| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE ZAG) |$|) |a| |b|))

(DEFUN |OUTFORM;root;2$;88| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE ROOT) |$|) |a|))

(DEFUN |OUTFORM;root;3$;89| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE ROOT) |$|) |a| |b|))
```

```
(DEFUN |OUTFORM;over;3$;90| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE OVER) |$|) |a| |b|))

(DEFUN |OUTFORM;slash;3$;91| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SLASH) |$|) |a| |b|))

(DEFUN |OUTFORM;assign;3$;92| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE LET) |$|) |a| |b|))

(DEFUN |OUTFORM;label;3$;93| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE EQUATNUM) |$|) |a| |b|))

(DEFUN |OUTFORM;rarrow;3$;94| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE TAG) |$|) |a| |b|))

(DEFUN |OUTFORM;differentiate;$Nni$;95| (|a| |nn| $)
  (PROG (G82832 |r| |s|)
    (RETURN
      (SEQ (COND
             ((ZEROP |nn|) |a|)
             ((< |nn| 4) (SPADCALL |a| |nn| (QREFELT $ 112)))
             ('T
              (SEQ (LETT |r|
                         (SPADCALL
                             (PROG1 (LETT G82832 |nn|
                                     |OUTFORM;differentiate;$Nni$;95|)
                               (|check-subtype| (> G82832 0)
                                   '(|PositiveInteger|) G82832))
                             (QREFELT $ 125))
                         |OUTFORM;differentiate;$Nni$;95|)
                   (LETT |s| (SPADCALL |r| (QREFELT $ 126))
                         |OUTFORM;differentiate;$Nni$;95|)
                   (EXIT (SPADCALL |a|
                             (SPADCALL (|OUTFORM;sform| |s| $)
                                 (QREFELT $ 60))
                             (QREFELT $ 63)))))))))))

(DEFUN |OUTFORM;sum;2$;96| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SIGMA) |$|) (SPADCALL (QREFELT |$| 12)) |a|))

(DEFUN |OUTFORM;sum;3$;97| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SIGMA) |$|) |b| |a|))

(DEFUN |OUTFORM;sum;4$;98| (|a| |b| |c| |$|)
 (LIST (|OUTFORM;eform| (QUOTE SIGMA2) |$|) |b| |c| |a|))

(DEFUN |OUTFORM;prod;2$;99| (|a| |$|)
 (LIST (|OUTFORM;eform| (QUOTE PI) |$|) (SPADCALL (QREFELT |$| 12)) |a|))
```

```
(DEFUN |OUTFORM;prod;3$;100| (|a| |b| |$|)
 (LIST (|OUTFORM;eform| (QUOTE PI) |$|) |b| |a|))

(DEFUN |OUTFORM;prod;4$;101| (|a| |b| |c| |$|)
 (LIST (|OUTFORM;eform| (QUOTE PI2) |$|) |b| |c| |a|))

(DEFUN |OUTFORM;int;2$;102| (|a| |$|)
 (LIST
  (|OUTFORM;eform| (QUOTE INTSIGN) |$|)
  (SPADCALL (QREFELT |$| 12))
  (SPADCALL (QREFELT |$| 12))
  |a|))

(DEFUN |OUTFORM;int;3$;103| (|a| |b| |$|)
 (LIST
  (|OUTFORM;eform| (QUOTE INTSIGN) |$|)
  |b|
  (SPADCALL (QREFELT |$| 12))
  |a|))

(DEFUN |OUTFORM;int;4$;104| (|a| |b| |c| |$|)
 (LIST (|OUTFORM;eform| (QUOTE INTSIGN) |$|) |b| |c| |a|))

(DEFUN |OutputForm| ()
  (PROG ()
    (RETURN
      (PROG (G82846)
        (RETURN
          (COND
            ((LETT G82846 (HGET |$ConstructorCache| '|OutputForm|)
                   |OutputForm|)
             (|CDRwithIncrement| (CDAR G82846)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|OutputForm|
                                   (LIST
                                    (CONS NIL (CONS 1 (|OutputForm;|))))))
                 (LETT G82846 T |OutputForm|))
               (COND
                 ((NOT G82846)
                  (HREM |$ConstructorCache| '|OutputForm|)))))))))))

(DEFUN |OutputForm;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|OutputForm|) |OutputForm|)
        (LETT $ (make-array 138) |OutputForm|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
```

```
          (LETT |pv$| (|buildPredVector| 0 0 NIL) |OutputForm|))
       (|haddProp| |$ConstructorCache| '|OutputForm| NIL (CONS 1 $))
       (|stuffDomainSlots| $)
       (QSETREFV $ 6 (|List| $))
       $))))

(setf (get
 (QUOTE |OutputForm|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE #(
   NIL NIL NIL NIL NIL NIL (QUOTE |Rep|) (|Void|) |OUTFORM;print;$V;1|
   (|Boolean|) (|String|) (0 . |empty?|) |OUTFORM;empty;$;71|
   |OUTFORM;message;S$;2| |OUTFORM;messagePrint;SV;3|
   |OUTFORM;=;2$B;4| |OUTFORM;=;3$;5| (|OutputForm|)
   |OUTFORM;coerce;2$;6| (|Integer|) |OUTFORM;outputForm;I$;7|
   (|Symbol|) |OUTFORM;outputForm;S$;8| (|DoubleFloat|)
   |OUTFORM;outputForm;Df$;9| (|Character|) (5 . |quote|)
   (9 . |concat|) (15 . |concat|) |OUTFORM;outputForm;S$;13|
   |OUTFORM;width;$I;14| |OUTFORM;height;$I;15|
   |OUTFORM;subHeight;$I;16| |OUTFORM;superHeight;$I;17|
   |OUTFORM;height;I;18| |OUTFORM;width;I;19| |OUTFORM;hspace;I$;27|
   |OUTFORM;hconcat;3$;46| |OUTFORM;center;$I$;20|
   |OUTFORM;left;$I$;21| |OUTFORM;right;$I$;22| |OUTFORM;center;2$;23|
   |OUTFORM;left;2$;24| |OUTFORM;right;2$;25| |OUTFORM;vspace;I$;26|
   |OUTFORM;vconcat;3$;48| |OUTFORM;rspace;2I$;28| (|List| 49)
   |OUTFORM;matrix;L$;29| (|List| |$|) |OUTFORM;pile;L$;30|
   |OUTFORM;commaSeparate;L$;31| |OUTFORM;semicolonSeparate;L$;32|
   (21 . |reverse|) (26 . |append|) |OUTFORM;blankSeparate;L$;33|
   |OUTFORM;brace;2$;34| |OUTFORM;brace;L$;35| |OUTFORM;bracket;2$;36|
   |OUTFORM;bracket;L$;37| |OUTFORM;paren;2$;38| |OUTFORM;paren;L$;39|
   |OUTFORM;sub;3$;40| |OUTFORM;super;3$;41| |OUTFORM;presub;3$;42|
   |OUTFORM;presuper;3$;43| (32 . |null|) (37 . |rest|) (42 . |first|)
   |OUTFORM;scripts;$L$;44| (|NonNegativeInteger|) (47 . |#|)
   (|List| |$$|) (52 . |append|) |OUTFORM;supersub;$L$;45|
   |OUTFORM;hconcat;L$;47| |OUTFORM;vconcat;L$;49| |OUTFORM;^=;3$;50|
   |OUTFORM;<;3$;51| |OUTFORM;>;3$;52| |OUTFORM;<=;3$;53|
   |OUTFORM;>=;3$;54| |OUTFORM;+;3$;55| |OUTFORM;-;3$;56|
   |OUTFORM;-;2$;57| |OUTFORM;*;3$;58| |OUTFORM;/;3$;59|
   |OUTFORM;**;3$;60| |OUTFORM;div;3$;61| |OUTFORM;rem;3$;62|
   |OUTFORM;quo;3$;63| |OUTFORM;exquo;3$;64| |OUTFORM;and;3$;65|
   |OUTFORM;or;3$;66| |OUTFORM;not;2$;67| |OUTFORM;SEGMENT;3$;68|
   |OUTFORM;SEGMENT;2$;69| |OUTFORM;binomial;3$;70|
   |OUTFORM;infix?;$B;72| |OUTFORM;elt;$L$;73| |OUTFORM;prefix;$L$;74|
   (58 . |rest|) |OUTFORM;infix;$L$;75| |OUTFORM;infix;4$;76|
   |OUTFORM;postfix;3$;77| |OUTFORM;string;2$;78| |OUTFORM;quote;2$;79|
   |OUTFORM;overbar;2$;80| |OUTFORM;dot;2$;81| |OUTFORM;prime;2$;82|
   (63 . |char|) |OUTFORM;dot;$Nni$;83| |OUTFORM;prime;$Nni$;84|
   |OUTFORM;overlabel;3$;85| |OUTFORM;box;2$;86| |OUTFORM;zag;3$;87|
   |OUTFORM;root;2$;88| |OUTFORM;root;3$;89| |OUTFORM;over;3$;90|
```

```
 |OUTFORM;slash;3$;91| |OUTFORM;assign;3$;92|
 |OUTFORM;label;3$;93| |OUTFORM;rarrow;3$;94| (|PositiveInteger|)
 (|NumberFormats|) (68 . |FormatRoman|) (73 . |lowerCase|)
 |OUTFORM;differentiate;$Nni$;95| |OUTFORM;sum;2$;96|
 |OUTFORM;sum;3$;97| |OUTFORM;sum;4$;98| |OUTFORM;prod;2$;99|
 |OUTFORM;prod;3$;100| |OUTFORM;prod;4$;101| |OUTFORM;int;2$;102|
 |OUTFORM;int;3$;103| |OUTFORM;int;4$;104| (|SingleInteger|)))
(QUOTE #(|~=| 78 |zag| 84 |width| 90 |vspace| 99 |vconcat| 104
 |supersub| 115 |superHeight| 121 |super| 126 |sum| 132 |subHeight|
 150 |sub| 155 |string| 161 |slash| 166 |semicolonSeparate| 172
 |scripts| 177 |rspace| 183 |root| 189 |right| 200 |rem| 211
 |rarrow| 217 |quote| 223 |quo| 228 |prod| 234 |print| 252
 |prime| 257 |presuper| 268 |presub| 274 |prefix| 280 |postfix|
 286 |pile| 292 |paren| 297 |overlabel| 307 |overbar| 313 |over|
 318 |outputForm| 324 |or| 344 |not| 350 |messagePrint| 355
 |message| 360 |matrix| 365 |left| 370 |latex| 381 |label| 386
 |int| 392 |infix?| 410 |infix| 415 |hspace| 428 |height| 433
 |hconcat| 442 |hash| 453 |exquo| 458 |empty| 464 |elt| 468 |dot|
 474 |div| 485 |differentiate| 491 |commaSeparate| 497 |coerce|
 502 |center| 507 |bracket| 518 |brace| 528 |box| 538 |blankSeparate|
 543 |binomial| 548 |assign| 554 |and| 560 |^=| 566 SEGMENT 572
 |>=| 583 |>| 589 |=| 595 |<=| 607 |<| 613 |/| 619 |-| 625 |+|
 636 |**| 642 |*| 648))
(QUOTE NIL)
(CONS
 (|makeByteWordVec2| 1 (QUOTE (0 0 0)))
 (CONS
  (QUOTE #(|SetCategory&| |BasicType&| NIL))
  (CONS
   (QUOTE #((|SetCategory|) (|BasicType|) (|CoercibleTo| 17)))
   (|makeByteWordVec2| 137 (QUOTE (1 10 9 0 11 0 25 0 26 2 10 0 0 25
     27 2 10 0 25 0 28 1 6 0 0 53 2 6 0 0 0 54 1 6 9 0 66 1 6 0 0 67 1
     6 2 0 68 1 6 70 0 71 2 72 0 0 0 73 1 72 0 0 101 1 25 0 10 110 1 124
     10 123 125 1 10 0 0 126 2 0 9 0 0 1 2 0 0 0 0 115 0 0 19 35 1 0 19
     0 30 1 0 0 19 44 1 0 0 49 76 2 0 0 0 0 45 2 0 0 0 49 74 1 0 19 0
     33 2 0 0 0 0 63 2 0 0 0 0 129 3 0 0 0 0 0 130 1 0 0 0 128 1 0 19
     0 32 2 0 0 0 0 62 1 0 0 0 105 2 0 0 0 0 119 1 0 0 49 52 2 0 0 0
     49 69 2 0 0 19 19 46 1 0 0 0 116 2 0 0 0 0 117 1 0 0 0 43 2 0 0
     0 19 40 2 0 0 0 0 89 2 0 0 0 0 122 1 0 0 0 106 2 0 0 0 0 90 3 0
     0 0 0 0 133 1 0 0 0 131 2 0 0 0 0 132 1 0 7 0 8 2 0 0 0 70 112 1
     0 0 0 109 2 0 0 0 0 65 2 0 0 0 0 64 2 0 0 0 49 100 2 0 0 0 0 104
     1 0 0 49 50 1 0 0 49 61 1 0 0 0 60 2 0 0 0 0 113 1 0 0 0 107 2 0
     0 0 0 118 1 0 0 10 29 1 0 0 23 24 1 0 0 21 22 1 0 0 19 20 2 0 0
     0 0 93 1 0 0 0 94 1 0 7 10 14 1 0 0 10 13 1 0 0 47 48 1 0 0 0 42
     2 0 0 0 19 39 1 0 10 0 1 2 0 0 0 0 121 3 0 0 0 0 0 136 2 0 0 0 0
     135 1 0 0 0 134 1 0 9 0 98 2 0 0 0 49 102 3 0 0 0 0 0 103 1 0 0
     19 36 0 0 19 34 1 0 19 0 31 1 0 0 49 75 2 0 0 0 0 37 1 0 137 0 1
     2 0 0 0 0 91 0 0 0 12 2 0 0 0 49 99 2 0 0 0 70 111 1 0 0 0 108 2
     0 0 0 0 88 2 0 0 0 70 127 1 0 0 49 51 1 0 17 0 18 1 0 0 0 41 2 0
     0 0 19 38 1 0 0 0 58 1 0 0 49 59 1 0 0 49 57 1 0 0 0 56 1 0 0 0
```

```
      114 1 0 0 49 55 2 0 0 0 0 97 2 0 0 0 0 120 2 0 0 0 0 92 2 0 0 0
      0 77 1 0 0 0 96 2 0 0 0 0 95 2 0 0 0 0 81 2 0 0 0 0 79 2 0 0 0 0
      16 2 0 9 0 0 15 2 0 0 0 0 80 2 0 0 0 0 78 2 0 0 0 0 86 1 0 0 0 84
      2 0 0 0 0 83 2 0 0 0 0 82 2 0 0 0 0 87 2 0 0 0 0 85))))))
  (QUOTE |lookupComplete|)))

(setf (get (QUOTE |OutputForm|) (QUOTE NILADIC)) T)
```

———-

28.10 PI.lsp BOOTSTRAP

PI depends on itself. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **PI** category which we can write into the **MID** directory. We compile the lisp code and copy the **PI.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— PI.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(SETQ |$CategoryFrame|
      (|put| '|PositiveInteger| '|SuperDomain| '(|NonNegativeInteger|)
             (|put| '(|NonNegativeInteger|) '|SubDomain|
                    (CONS '(|PositiveInteger| < 0 |#1|)
                          (DELASC '|PositiveInteger|
                                  (|get| '(|NonNegativeInteger|)
                                         '|SubDomain| |$CategoryFrame|)))
                    |$CategoryFrame|)))

(DEFUN |PositiveInteger| ()
  (PROG ()
    (RETURN
      (PROG (G96739)
        (RETURN
          (COND
            ((LETT G96739 (HGET |$ConstructorCache| '|PositiveInteger|)
                   |PositiveInteger|)
             (|CDRwithIncrement| (CDAR G96739)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache|
                                   '|PositiveInteger|
                                   (LIST
                                    (CONS NIL
                                     (CONS 1 (|PositiveInteger;|)))))))
```

```
                (LETT G96739 T |PositiveInteger|))
               (COND
                 ((NOT G96739)
                  (HREM |$ConstructorCache| '|PositiveInteger|))))))))))))

(DEFUN |PositiveInteger;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|PositiveInteger|) |PositiveInteger|)
        (LETT $ (make-array 12) |PositiveInteger|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL) |PositiveInteger|))
        (|haddProp| |$ConstructorCache| '|PositiveInteger| NIL
            (CONS 1 $))
        (|stuffDomainSlots| $)
        $))))

(setf (get
  (QUOTE |PositiveInteger|)
  (QUOTE |infovec|))
  (LIST
    (QUOTE
      #(NIL NIL NIL NIL NIL
        (|NonNegativeInteger|)
        (|PositiveInteger|)
        (|Boolean|)
        (|Union| |$| (QUOTE "failed"))
        (|SingleInteger|)
        (|String|)
        (|OutputForm|)))
    (QUOTE #(|~=| 0 |sample| 6 |recip| 10 |one?| 15 |min| 20 |max| 26
             |latex| 32 |hash| 37 |gcd| 42 |coerce| 48 |^| 53 |One| 65
             |>=| 69 |>| 75 |=| 81 |<=| 87 |<| 93 |+| 99 |**| 105 |*| 117))
    (QUOTE ((((|commutative| "*") . 0)))
    (CONS
      (|makeByteWordVec2| 1 (QUOTE (0 0 0 0 0 0 0)))
      (CONS
        (QUOTE #(|Monoid&| |AbelianSemiGroup&| |SemiGroup&| |OrderedSet&|
                 |SetCategory&| |BasicType&| NIL))
        (CONS
          (QUOTE #(
            (|Monoid|)
            (|AbelianSemiGroup|)
            (|SemiGroup|)
            (|OrderedSet|)
            (|SetCategory|)
            (|BasicType|)
            (|CoercibleTo| 11)))
```

```
         (|makeByteWordVec2| 11
          (QUOTE (2 0 7 0 0 1 0 0 0 1 1 0 8 0 1 1 0 7 0 1 2 0 0 0 0 1 2 0 0 0
                  0 1 1 0 10 0 1 1 0 9 0 1 2 0 0 0 0 1 1 0 11 0 1 2 0 0 0 6 1
                  2 0 0 0 5 1 0 0 0 1 2 0 7 0 0 1 2 0 7 0 0 1 2 0 7 0 0 1 2 0
                  7 0 0 1 2 0 7 0 0 1 2 0 0 0 0 1 2 0 0 0 6 1 2 0 0 0 5 1 2 0
                  0 0 0 1 2 0 0 6 0 1))))))
     (QUOTE |lookupComplete|)))

(setf (get (QUOTE |PositiveInteger|) (QUOTE NILADIC)) T)
```

———-

28.11 PRIMARR.lsp BOOTSTRAP

PRIMARR depends on itself. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **PRIMARR** category which we can write into the **MID** directory. We compile the lisp code and copy the **PRIMARR.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— PRIMARR.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT (QUOTE |PRIMARR;#;$Nni;1|) (QUOTE |SPADreplace|) (QUOTE QVSIZE))

(DEFUN |PRIMARR;#;$Nni;1| (|x| |$|) (QVSIZE |x|))

(PUT (QUOTE |PRIMARR;minIndex;$I;2|)
 (QUOTE |SPADreplace|) (QUOTE (XLAM (|x|) 0)))

(DEFUN |PRIMARR;minIndex;$I;2| (|x| |$|) 0)

(PUT (QUOTE |PRIMARR;empty;$;3|)
 (QUOTE |SPADreplace|) (QUOTE (XLAM NIL (make-array 0))))

(DEFUN |PRIMARR;empty;$;3| (|$|) (make-array 0))

(DEFUN |PRIMARR;new;NniS$;4| (|n| |x| |$|)
 (SPADCALL (make-array |n|) |x| (QREFELT |$| 12)))

(PUT (QUOTE |PRIMARR;qelt;$IS;5|) (QUOTE |SPADreplace|) (QUOTE ELT))

(DEFUN |PRIMARR;qelt;$IS;5| (|x| |i| |$|) (ELT |x| |i|))

(PUT (QUOTE |PRIMARR;elt;$IS;6|) (QUOTE |SPADreplace|) (QUOTE ELT))
```

```
(DEFUN |PRIMARR;elt;$IS;6| (|x| |i| |$|) (ELT |x| |i|))

(PUT (QUOTE |PRIMARR;qsetelt!;$I2S;7|) (QUOTE |SPADreplace|) (QUOTE SETELT))

(DEFUN |PRIMARR;qsetelt!;$I2S;7| (|x| |i| |s| |$|) (SETELT |x| |i| |s|))

(PUT (QUOTE |PRIMARR;setelt;$I2S;8|) (QUOTE |SPADreplace|) (QUOTE SETELT))

(DEFUN |PRIMARR;setelt;$I2S;8| (|x| |i| |s| |$|) (SETELT |x| |i| |s|))

(DEFUN |PRIMARR;fill!;$S$;9| (|x| |s| $)
  (PROG (|i| G82338)
    (RETURN
      (SEQ (SEQ (LETT |i| 0 |PRIMARR;fill!;$S$;9|)
                (LETT G82338 (QVMAXINDEX |x|) |PRIMARR;fill!;$S$;9|)
                G190 (COND ((QSGREATERP |i| G82338) (GO G191)))
                (SEQ (EXIT (SETELT |x| |i| |s|)))
                (LETT |i| (QSADD1 |i|) |PRIMARR;fill!;$S$;9|) (GO G190)
                G191 (EXIT NIL))
           (EXIT |x|)))))

(DEFUN |PrimitiveArray| (G82348)
  (PROG ()
    (RETURN
      (PROG (G82349)
        (RETURN
          (COND
            ((LETT G82349
                   (|lassocShiftWithFunction|
                       (LIST (|devaluate| G82348))
                       (HGET |$ConstructorCache| '|PrimitiveArray|)
                       '|domainEqualList|)
                   |PrimitiveArray|)
             (|CDRwithIncrement| G82349))
            ('T
             (UNWIND-PROTECT
               (PROG1 (|PrimitiveArray;| G82348)
                 (LETT G82349 T |PrimitiveArray|))
               (COND
                 ((NOT G82349)
                  (HREM |$ConstructorCache| '|PrimitiveArray|)))))))))))

(DEFUN |PrimitiveArray;| (|#1|)
  (PROG (DV$1 |dv$| $ G82347 |pv$|)
    (RETURN
      (PROGN
        (LETT DV$1 (|devaluate| |#1|) |PrimitiveArray|)
        (LETT |dv$| (LIST '|PrimitiveArray| DV$1) |PrimitiveArray|)
        (LETT $ (make-array 35) |PrimitiveArray|)
```

```
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$|
                  (|buildPredVector| 0 0
                      (LIST (|HasCategory| |#1| '(|SetCategory|))
                            (|HasCategory| |#1|
                                '(|ConvertibleTo| (|InputForm|)))
                            (LETT G82347
                                  (|HasCategory| |#1| '(|OrderedSet|))
                                  |PrimitiveArray|)
                            (OR G82347
                                (|HasCategory| |#1| '(|SetCategory|)))
                            (|HasCategory| (|Integer|) '(|OrderedSet|))
                            (AND (|HasCategory| |#1|
                                     (LIST '|Evalable|
                                      (|devaluate| |#1|)))
                                 (|HasCategory| |#1| '(|SetCategory|)))
                            (OR (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     G82347)
                                (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     (|HasCategory| |#1|
                                      '(|SetCategory|))))))
                  |PrimitiveArray|))
        (|haddProp| |$ConstructorCache| '|PrimitiveArray| (LIST DV$1)
            (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 6 |#1|)
        $))))

(setf (get (QUOTE |PrimitiveArray|) (QUOTE |infovec|))
 (LIST
  (QUOTE
   #(NIL NIL NIL NIL NIL NIL (|local| |#1|) (|NonNegativeInteger|)
     |PRIMARR;#;$Nni;1| (|Integer|) |PRIMARR;minIndex;$I;2|
     |PRIMARR;empty;$;3| |PRIMARR;fill!;$S$;9| |PRIMARR;new;NniS$;4|
     |PRIMARR;qelt;$IS;5| |PRIMARR;elt;$IS;6| |PRIMARR;qsetelt!;$I2S;7|
     |PRIMARR;setelt;$I2S;8| (|Mapping| 6 6 6) (|Boolean|) (|List| 6)
     (|Equation| 6) (|List| 21) (|Mapping| 19 6) (|Mapping| 19 6 6)
     (|UniversalSegment| 9) (|Void|) (|Mapping| 6 6) (|InputForm|)
     (|OutputForm|) (|String|) (|SingleInteger|) (|List| |$|)
     (|Union| 6 (QUOTE "failed")) (|List| 9)))
  (QUOTE
   #(|~=| 0 |swap!| 6 |sorted?| 13 |sort!| 24 |sort| 35 |size?| 46 |setelt|
     52 |select| 66 |sample| 72 |reverse!| 76 |reverse| 81 |removeDuplicates|
     86 |remove| 91 |reduce| 103 |qsetelt!| 124 |qelt| 131 |position| 137
     |parts| 156 |new| 161 |more?| 167 |minIndex| 173 |min| 178 |merge| 184
```

```
    |members| 197 |member?| 202 |maxIndex| 208 |max| 213 |map!| 219 |map|
    225 |less?| 238 |latex| 244 |insert| 249 |indices| 263 |index?| 268
    |hash| 274 |first| 279 |find| 284 |fill!| 290 |every?| 296 |eval| 302
    |eq?| 328 |entry?| 334 |entries| 340 |empty?| 345 |empty| 350 |elt| 354
    |delete| 373 |count| 385 |copyInto!| 397 |copy| 404 |convert| 409
    |construct| 414 |concat| 419 |coerce| 442 |any?| 447 |>=| 453 |>| 459
    |=| 465 |<=| 471 |<| 477 |#| 483))
(QUOTE ((|shallowlyMutable| . 0) (|finiteAggregate| . 0)))
(CONS
  (|makeByteWordVec2| 7 (QUOTE (0 0 0 0 0 0 3 0 0 7 4 0 0 7 1 2 4)))
  (CONS
   (QUOTE #(|OneDimensionalArrayAggregate&| |FiniteLinearAggregate&|
    |LinearAggregate&| |IndexedAggregate&| |Collection&|
    |HomogeneousAggregate&| |OrderedSet&| |Aggregate&| |EltableAggregate&|
    |Evalable&| |SetCategory&| NIL NIL |InnerEvalable&| NIL NIL |BasicType&|))
   (CONS
    (QUOTE
     #((|OneDimensionalArrayAggregate| 6) (|FiniteLinearAggregate| 6)
       (|LinearAggregate| 6) (|IndexedAggregate| 9 6) (|Collection| 6)
       (|HomogeneousAggregate| 6) (|OrderedSet|) (|Aggregate|)
       (|EltableAggregate| 9 6) (|Evalable| 6) (|SetCategory|) (|Type|)
       (|Eltable| 9 6) (|InnerEvalable| 6 6) (|CoercibleTo| 29)
       (|ConvertibleTo| 28) (|BasicType|)))
    (|makeByteWordVec2| 34
     (QUOTE
      (2 1 19 0 0 1 3 0 26 0 9 9 1 1 3 19 0 1 2 0 19 24 0 1 1 3 0 0 1 2 0 0
       24 0 1 1 3 0 0 1 2 0 0 24 0 1 2 0 19 0 7 1 3 0 6 0 25 6 1 3 0 6 0 9
       6 17 2 0 0 23 0 1 0 0 0 1 1 0 0 0 1 1 0 0 0 1 1 1 0 0 1 2 1 0 6 0 1
       2 0 0 23 0 1 4 1 6 18 0 6 6 1 3 0 6 18 0 6 1 2 0 6 18 0 1 3 0 6 0 9
       6 16 2 0 6 0 9 14 2 1 9 6 0 1 3 1 9 6 0 9 1 2 0 9 23 0 1 1 0 20 0 1
       2 0 0 7 6 13 2 0 19 0 7 1 1 5 9 0 10 2 3 0 0 0 1 2 3 0 0 0 1 3 0 0
       24 0 0 1 1 0 20 0 1 2 1 19 6 0 1 1 5 9 0 1 2 3 0 0 0 1 2 0 0 27 0 1
       3 0 0 18 0 0 1 2 0 0 27 0 1 2 0 19 0 7 1 1 1 30 0 1 3 0 0 0 0 9 1 3
       0 0 6 0 9 1 1 0 34 0 1 2 0 19 9 0 1 1 1 31 0 1 1 5 6 0 1 2 0 33 23
       0 1 2 0 0 0 6 12 2 0 19 23 0 1 3 6 0 0 20 20 1 2 6 0 0 21 1 3 6 0 0
       6 6 1 2 6 0 0 22 1 2 0 19 0 0 1 2 1 19 6 0 1 1 0 20 0 1 1 0 19 0 1
       0 0 0 11 2 0 0 0 25 1 2 0 6 0 9 15 3 0 6 0 9 6 1 2 0 0 0 9 1 2 0 0
       0 25 1 2 1 7 6 0 1 2 0 7 23 0 1 3 0 0 0 0 9 1 1 0 0 0 1 1 2 28 0 1
       1 0 0 20 1 1 0 0 32 1 2 0 0 6 0 1 2 0 0 0 0 1 2 0 0 0 6 1 1 1 29 0
       1 2 0 19 23 0 1 2 3 19 0 0 1 2 3 19 0 0 1 2 1 19 0 0 1 2 3 19 0 0 1
       2 3 19 0 0 1 1 0 7 0 8))))))
(QUOTE |lookupComplete|)))
```

28.12 REF.lsp BOOTSTRAP

REF depends on a chain of files. We need to break this cycle to build the algebra. So

we keep a cached copy of the translated **REF** category which we can write into the **MID** directory. We compile the lisp code and copy the **REF.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— REF.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(PUT (QUOTE |REF;=;2$B;1|) (QUOTE |SPADreplace|) (QUOTE EQ))

(DEFUN |REF;=;2$B;1| (|p| |q| |$|) (EQ |p| |q|))

(PUT (QUOTE |REF;ref;S$;2|) (QUOTE |SPADreplace|) (QUOTE LIST))

(DEFUN |REF;ref;S$;2| (|v| |$|) (LIST |v|))

(PUT (QUOTE |REF;elt;$S;3|) (QUOTE |SPADreplace|) (QUOTE QCAR))

(DEFUN |REF;elt;$S;3| (|p| |$|) (QCAR |p|))

(DEFUN |REF;setelt;$2S;4| (|p| |v| |$|) (PROGN (RPLACA |p| |v|) (QCAR |p|)))

(PUT (QUOTE |REF;deref;$S;5|) (QUOTE |SPADreplace|) (QUOTE QCAR))

(DEFUN |REF;deref;$S;5| (|p| |$|) (QCAR |p|))

(DEFUN |REF;setref;$2S;6| (|p| |v| |$|) (PROGN (RPLACA |p| |v|) (QCAR |p|)))

(DEFUN |REF;coerce;$Of;7| (|p| |$|)
 (SPADCALL
  (SPADCALL "ref" (QREFELT |$| 17))
  (LIST (SPADCALL (QCAR |p|) (QREFELT |$| 18)))
  (QREFELT |$| 20)))

(DEFUN |Reference| (G82336)
  (PROG ()
    (RETURN
      (PROG (G82337)
        (RETURN
          (COND
            ((LETT G82337
                   (|lassocShiftWithFunction|
                       (LIST (|devaluate| G82336))
                       (HGET |$ConstructorCache| '|Reference|)
                       '|domainEqualList|)
                   |Reference|)
             (|CDRwithIncrement| G82337))
            ('T
```

```
             (UNWIND-PROTECT
               (PROG1 (|Reference;| G82336)
                 (LETT G82337 T |Reference|))
               (COND
                ((NOT G82337) (HREM |$ConstructorCache| '|Reference|)))))))))))

(DEFUN |Reference;| (|#1|)
  (PROG (DV$1 |dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT DV$1 (|devaluate| |#1|) |Reference|)
        (LETT |dv$| (LIST '|Reference| DV$1) |Reference|)
        (LETT $ (make-array 23) |Reference|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$|
                  (|buildPredVector| 0 0
                      (LIST (|HasCategory| |#1| '(|SetCategory|))))
                  |Reference|))
        (|haddProp| |$ConstructorCache| '|Reference| (LIST DV$1)
            (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 6 |#1|)
        (QSETREFV $ 7 (|Record| (|:| |value| |#1|)))
        (COND
          ((|testBitVector| |pv$| 1)
           (QSETREFV $ 21
               (CONS (|dispatchFunction| |REF;coerce;$Of;7|) $))))
        $))))

(setf (get
 (QUOTE |Reference|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE
  #(NIL NIL NIL NIL NIL NIL (|local| |#1|) (QUOTE |Rep|) (|Boolean|)
    |REF;=;2$B;1| |REF;ref;S$;2| |REF;elt;$S;3| |REF;setelt;$2S;4|
    |REF;deref;$S;5| |REF;setref;$2S;6| (|String|) (|OutputForm|)
    (0 . |message|) (5 . |coerce|) (|List| |$|) (10 . |prefix|)
    (16 . |coerce|) (|SingleInteger|)))
  (QUOTE #(|~=| 21 |setref| 27 |setelt| 33 |ref| 39 |latex| 44 |hash| 49
           |elt| 54 |deref| 59 |coerce| 64 |=| 69))
   (QUOTE NIL)
   (CONS
    (|makeByteWordVec2| 1 (QUOTE (1 0 1 1)))
    (CONS
     (QUOTE #(|SetCategory&| NIL |BasicType&| NIL))
     (CONS
      (QUOTE #((|SetCategory|) (|Type|) (|BasicType|) (|CoercibleTo| 16)))
      (|makeByteWordVec2| 22
```

```
      (QUOTE (1 16 0 15 17 1 6 16 0 18 2 16 0 0 19 20 1 0 16 0 21 2 1 8 0
              0 1 2 0 6 0 6 14 2 0 6 0 6 12 1 0 0 6 10 1 1 15 0 1 1 1 22
              0 1 1 0 6 0 11 1 0 6 0 13 1 1 16 0 21 2 0 8 0 0 9))))))
  (QUOTE |lookupComplete|)))
```

———-

28.13 SINT.lsp BOOTSTRAP

— SINT.lsp BOOTSTRAP —

```
(/VERSIONCHECK 2)

(DEFUN |SINT;writeOMSingleInt| (|dev| |x| $)
  (SEQ
    (COND
      ((QSLESSP |x| 0)
        (SEQ
          (SPADCALL |dev| (QREFELT $ 9))
          (SPADCALL |dev| "arith1" "unaryminus" (QREFELT $ 11))
          (SPADCALL |dev| (QSMINUS |x|) (QREFELT $ 13))
          (EXIT (SPADCALL |dev| (QREFELT $ 14)))))
      ((QUOTE T) (SPADCALL |dev| |x| (QREFELT $ 13))))))

(DEFUN |SINT;OMwrite;$S;2| (|x| $)
  (PROG (|sp| |dev| |s|)
    (RETURN
      (SEQ
        (LETT |s| "" |SINT;OMwrite;$S;2|)
        (LETT |sp| (OM-STRINGTOSTRINGPTR |s|) |SINT;OMwrite;$S;2|)
        (LETT |dev|
          (SPADCALL |sp| (SPADCALL (QREFELT $ 16)) (QREFELT $ 17))
          |SINT;OMwrite;$S;2|)
        (SPADCALL |dev| (QREFELT $ 18))
        (|SINT;writeOMSingleInt| |dev| |x| $)
        (SPADCALL |dev| (QREFELT $ 19))
        (SPADCALL |dev| (QREFELT $ 20))
        (LETT |s| (OM-STRINGPTRTOSTRING |sp|) |SINT;OMwrite;$S;2|)
        (EXIT |s|)))))

(DEFUN |SINT;OMwrite;$BS;3| (|x| |wholeObj| $)
  (PROG (|sp| |dev| |s|)
    (RETURN
      (SEQ
        (LETT |s| "" |SINT;OMwrite;$BS;3|)
        (LETT |sp| (OM-STRINGTOSTRINGPTR |s|) |SINT;OMwrite;$BS;3|)
```

```
        (LETT |dev|
          (SPADCALL |sp| (SPADCALL (QREFELT $ 16)) (QREFELT $ 17))
          |SINT;OMwrite;$BS;3|)
        (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 18))))
        (|SINT;writeOMSingleInt| |dev| |x| $)
        (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 19))))
        (SPADCALL |dev| (QREFELT $ 20))
        (LETT |s| (OM-STRINGPTRTOSTRING |sp|) |SINT;OMwrite;$BS;3|)
        (EXIT |s|)))))

(DEFUN |SINT;OMwrite;Omd$V;4| (|dev| |x| $)
  (SEQ
    (SPADCALL |dev| (QREFELT $ 18))
    (|SINT;writeOMSingleInt| |dev| |x| $)
    (EXIT (SPADCALL |dev| (QREFELT $ 19)))))

(DEFUN |SINT;OMwrite;Omd$BV;5| (|dev| |x| |wholeObj| $)
  (SEQ
    (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 18))))
    (|SINT;writeOMSingleInt| |dev| |x| $)
    (EXIT (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 19)))))))

(PUT
  (QUOTE |SINT;reducedSystem;MM;6|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM (|m|) |m|)))

(DEFUN |SINT;reducedSystem;MM;6| (|m| $) |m|)

(DEFUN |SINT;coerce;$Of;7| (|x| $)
  (SPADCALL |x| (QREFELT $ 30)))

(PUT
  (QUOTE |SINT;convert;$I;8|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM (|x|) |x|)))

(DEFUN |SINT;convert;$I;8| (|x| $) |x|)

(DEFUN |SINT;*;I2$;9| (|i| |y| $)
  (QSTIMES (SPADCALL |i| (QREFELT $ 33)) |y|))

(PUT
  (QUOTE |SINT;Zero;$;10|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL 0)))

(DEFUN |SINT;Zero;$;10| ($) 0)

(PUT
```

```
  (QUOTE |SINT;One;$;11|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL 1)))

(DEFUN |SINT;One;$;11| ($) 1)

(PUT
  (QUOTE |SINT;base;$;12|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL 2)))

(DEFUN |SINT;base;$;12| ($) 2)

(PUT
  (QUOTE |SINT;max;$;13|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL MOST-POSITIVE-FIXNUM)))

(DEFUN |SINT;max;$;13| ($) MOST-POSITIVE-FIXNUM)

(PUT
  (QUOTE |SINT;min;$;14|)
  (QUOTE |SPADreplace|)
  (QUOTE (XLAM NIL MOST-NEGATIVE-FIXNUM)))

(DEFUN |SINT;min;$;14| ($) MOST-NEGATIVE-FIXNUM)

(PUT
  (QUOTE |SINT;=;2$B;15|)
  (QUOTE |SPADreplace|)
  (QUOTE EQL))

(DEFUN |SINT;=;2$B;15| (|x| |y| $)
  (EQL |x| |y|))

(PUT
  (QUOTE |SINT;~;2$;16|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGNOT))

(DEFUN |SINT;~;2$;16| (|x| $)
  (LOGNOT |x|))

(PUT
  (QUOTE |SINT;not;2$;17|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGNOT))

(DEFUN |SINT;not;2$;17| (|x| $)
  (LOGNOT |x|))
```

```
(PUT
  (QUOTE |SINT;/\\;3$;18|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGAND))

(DEFUN |SINT;/\\;3$;18| (|x| |y| $)
  (LOGAND |x| |y|))

(PUT
  (QUOTE |SINT;\\/;3$;19|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGIOR))

(DEFUN |SINT;\\/;3$;19| (|x| |y| $)
  (LOGIOR |x| |y|))

(PUT
  (QUOTE |SINT;Not;2$;20|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGNOT))

(DEFUN |SINT;Not;2$;20| (|x| $)
  (LOGNOT |x|))

(PUT
  (QUOTE |SINT;And;3$;21|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGAND))

(DEFUN |SINT;And;3$;21| (|x| |y| $)
  (LOGAND |x| |y|))

(PUT
  (QUOTE |SINT;Or;3$;22|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGIOR))

(DEFUN |SINT;Or;3$;22| (|x| |y| $)
  (LOGIOR |x| |y|))

(PUT
  (QUOTE |SINT;xor;3$;23|)
  (QUOTE |SPADreplace|)
  (QUOTE LOGXOR))

(DEFUN |SINT;xor;3$;23| (|x| |y| $)
  (LOGXOR |x| |y|))

(PUT
```

```
  (QUOTE |SINT;<;2$B;24|)
  (QUOTE |SPADreplace|)
  (QUOTE QSLESSP))

(DEFUN |SINT;<;2$B;24| (|x| |y| $)
  (QSLESSP |x| |y|))

(PUT
  (QUOTE |SINT;inc;2$;25|)
  (QUOTE |SPADreplace|)
  (QUOTE QSADD1))

(DEFUN |SINT;inc;2$;25| (|x| $)
  (QSADD1 |x|))

(PUT
  (QUOTE |SINT;dec;2$;26|)
  (QUOTE |SPADreplace|)
  (QUOTE QSSUB1))

(DEFUN |SINT;dec;2$;26| (|x| $)
  (QSSUB1 |x|))

(PUT
  (QUOTE |SINT;-;2$;27|)
  (QUOTE |SPADreplace|)
  (QUOTE QSMINUS))

(DEFUN |SINT;-;2$;27| (|x| $)
  (QSMINUS |x|))

(PUT
  (QUOTE |SINT;+;3$;28|)
  (QUOTE |SPADreplace|)
  (QUOTE QSPLUS))

(DEFUN |SINT;+;3$;28| (|x| |y| $)
  (QSPLUS |x| |y|))

(PUT
  (QUOTE |SINT;-;3$;29|)
  (QUOTE |SPADreplace|)
  (QUOTE QSDIFFERENCE))

(DEFUN |SINT;-;3$;29| (|x| |y| $)
  (QSDIFFERENCE |x| |y|))

(PUT
  (QUOTE |SINT;*;3$;30|)
  (QUOTE |SPADreplace|)
```

```
  (QUOTE QSTIMES))

(DEFUN |SINT;*;3$;30| (|x| |y| $)
  (QSTIMES |x| |y|))

(DEFUN |SINT;**;$Nni$;31| (|x| |n| $)
  (SPADCALL (EXPT |x| |n|) (QREFELT $ 33)))

(PUT
  (QUOTE |SINT;quo;3$;32|)
  (QUOTE |SPADreplace|)
  (QUOTE QSQUOTIENT))

(DEFUN |SINT;quo;3$;32| (|x| |y| $)
  (QSQUOTIENT |x| |y|))

(PUT
  (QUOTE |SINT;rem;3$;33|)
  (QUOTE |SPADreplace|)
  (QUOTE QSREMAINDER))

(DEFUN |SINT;rem;3$;33| (|x| |y| $)
  (QSREMAINDER |x| |y|))

(DEFUN |SINT;divide;2$R;34| (|x| |y| $)
  (CONS (QSQUOTIENT |x| |y|) (QSREMAINDER |x| |y|)))

(PUT (QUOTE |SINT;gcd;3$;35|)
  (QUOTE |SPADreplace|) (QUOTE GCD))

(DEFUN |SINT;gcd;3$;35| (|x| |y| $)
  (GCD |x| |y|))

(PUT
  (QUOTE |SINT;abs;2$;36|)
  (QUOTE |SPADreplace|)
  (QUOTE QSABSVAL))

(DEFUN |SINT;abs;2$;36| (|x| $)
  (QSABSVAL |x|))

(PUT
  (QUOTE |SINT;odd?;$B;37|)
  (QUOTE |SPADreplace|)
  (QUOTE QSODDP))

(DEFUN |SINT;odd?;$B;37| (|x| $)
  (QSODDP |x|))

(PUT
```

```
  (QUOTE |SINT;zero?;$B;38|)
  (QUOTE |SPADreplace|)
  (QUOTE QSZEROP))

(DEFUN |SINT;zero?;$B;38| (|x| $)
  (QSZEROP |x|))

(PUT
  (QUOTE |SINT;max;3$;39|)
  (QUOTE |SPADreplace|)
  (QUOTE QSMAX))

(DEFUN |SINT;max;3$;39| (|x| |y| $)
  (QSMAX |x| |y|))

(PUT
  (QUOTE |SINT;min;3$;40|)
  (QUOTE |SPADreplace|)
  (QUOTE QSMIN))

(DEFUN |SINT;min;3$;40| (|x| |y| $)
  (QSMIN |x| |y|))

(PUT
  (QUOTE |SINT;hash;2$;41|)
  (QUOTE |SPADreplace|)
  (QUOTE SXHASH))

(DEFUN |SINT;hash;2$;41| (|x| $)
  (SXHASH |x|))

(PUT
  (QUOTE |SINT;length;2$;42|)
  (QUOTE |SPADreplace|)
  (QUOTE INTEGER-LENGTH))

(DEFUN |SINT;length;2$;42| (|x| $)
  (INTEGER-LENGTH |x|))

(PUT
  (QUOTE |SINT;shift;3$;43|)
  (QUOTE |SPADreplace|)
  (QUOTE QSLEFTSHIFT))

(DEFUN |SINT;shift;3$;43| (|x| |n| $)
  (QSLEFTSHIFT |x| |n|))

(PUT
  (QUOTE |SINT;mulmod;4$;44|)
  (QUOTE |SPADreplace|)
```

```
  (QUOTE QSMULTMOD))

(DEFUN |SINT;mulmod;4$;44| (|a| |b| |p| $)
  (QSMULTMOD |a| |b| |p|))

(PUT
  (QUOTE |SINT;addmod;4$;45|)
  (QUOTE |SPADreplace|)
  (QUOTE QSADDMOD))

(DEFUN |SINT;addmod;4$;45| (|a| |b| |p| $)
  (QSADDMOD |a| |b| |p|))

(PUT
  (QUOTE |SINT;submod;4$;46|)
  (QUOTE |SPADreplace|)
  (QUOTE QSDIFMOD))

(DEFUN |SINT;submod;4$;46| (|a| |b| |p| $)
  (QSDIFMOD |a| |b| |p|))

(PUT
  (QUOTE |SINT;negative?;$B;47|)
  (QUOTE |SPADreplace|)
  (QUOTE QSMINUSP))

(DEFUN |SINT;negative?;$B;47| (|x| $)
  (QSMINUSP |x|))

(PUT
  (QUOTE |SINT;reducedSystem;MVR;48|)
  (QUOTE |SPADreplace|)
  (QUOTE CONS))

(DEFUN |SINT;reducedSystem;MVR;48| (|m| |v| $)
  (CONS |m| |v|))

(DEFUN |SINT;positiveRemainder;3$;49| (|x| |n| $)
  (PROG (|r|)
    (RETURN
      (SEQ
        (LETT |r| (QSREMAINDER |x| |n|) |SINT;positiveRemainder;3$;49|)
        (EXIT
          (COND
            ((QSMINUSP |r|)
              (COND
                ((QSMINUSP |n|) (QSDIFFERENCE |x| |n|))
                ((QUOTE T) (QSPLUS |r| |n|))))
            ((QUOTE T) |r|)))))))
```

```
(DEFUN |SINT;coerce;I$;50| (|x| $)
  (SEQ
    (COND
      ((NULL (< MOST-POSITIVE-FIXNUM |x|))
        (COND ((NULL (< |x| MOST-NEGATIVE-FIXNUM)) (EXIT |x|)))))
     (EXIT (|error| "integer too large to represent in a machine word"))))

(DEFUN |SINT;random;$;51| ($)
  (SEQ
    (SETELT $ 6 (REMAINDER (TIMES 314159269 (QREFELT $ 6)) 2147483647))
    (EXIT (REMAINDER (QREFELT $ 6) 67108864))))

(PUT
  (QUOTE |SINT;random;2$;52|)
  (QUOTE |SPADreplace|)
  (QUOTE RANDOM))

(DEFUN |SINT;random;2$;52| (|n| $)
  (RANDOM |n|))

(DEFUN |SINT;unitNormal;$R;53| (|x| $)
  (COND
    ((QSLESSP |x| 0) (VECTOR -1 (QSMINUS |x|) -1))
    ((QUOTE T) (VECTOR 1 |x| 1))))

(DEFUN |SingleInteger| ()
  (PROG ()
    (RETURN
      (PROG (G1358)
        (RETURN
          (COND
            ((LETT G1358 (HGET |$ConstructorCache| '|SingleInteger|)
                   |SingleInteger|)
             (|CDRwithIncrement| (CDAR G1358)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|SingleInteger|
                                   (LIST
                                    (CONS NIL
                                     (CONS 1 (|SingleInteger;|))))))
                 (LETT G1358 T |SingleInteger|))
               (COND
                 ((NOT G1358)
                  (HREM |$ConstructorCache| '|SingleInteger|)))))))))))

(DEFUN |SingleInteger;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|SingleInteger|) |SingleInteger|)
```

```
        (LETT $ (make-array 103) |SingleInteger|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL) |SingleInteger|))
        (|haddProp| |$ConstructorCache| '|SingleInteger| NIL
            (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 6 1)
        $))))

(setf (get '|SingleInteger| '|infovec|)
    (LIST '#(NIL NIL NIL NIL NIL NIL '|seed| (|Void|)
             (|OpenMathDevice|) (0 . |OMputApp|) (|String|)
             (5 . |OMputSymbol|) (|Integer|) (12 . |OMputInteger|)
             (18 . |OMputEndApp|) (|OpenMathEncoding|)
             (23 . |OMencodingXML|) (27 . |OMopenString|)
             (33 . |OMputObject|) (38 . |OMputEndObject|)
             (43 . |OMclose|) |SINT;OMwrite;$S;2| (|Boolean|)
             |SINT;OMwrite;$BS;3| |SINT;OMwrite;Omd$V;4|
             |SINT;OMwrite;Omd$BV;5| (|Matrix| 12) (|Matrix| $)
             |SINT;reducedSystem;MM;6| (|OutputForm|) (48 . |coerce|)
             |SINT;coerce;$Of;7| |SINT;convert;$I;8| (53 . |coerce|)
             |SINT;*;I2$;9|
             (CONS IDENTITY
                   (FUNCALL (|dispatchFunction| |SINT;Zero;$;10|) $))
             (CONS IDENTITY
                   (FUNCALL (|dispatchFunction| |SINT;One;$;11|) $))
             |SINT;base;$;12| |SINT;max;$;13| |SINT;min;$;14|
             |SINT;=;2$B;15| |SINT;~;2$;16| |SINT;not;2$;17|
             |SINT;/\\;3$;18| |SINT;\\/;3$;19| |SINT;Not;2$;20|
             |SINT;And;3$;21| |SINT;Or;3$;22| |SINT;xor;3$;23|
             |SINT;<;2$B;24| |SINT;inc;2$;25| |SINT;dec;2$;26|
             |SINT;-;2$;27| |SINT;+;3$;28| |SINT;-;3$;29|
             |SINT;*;3$;30| (|NonNegativeInteger|) |SINT;**;$Nni$;31|
             |SINT;quo;3$;32| |SINT;rem;3$;33|
             (|Record| (|:| |quotient| $) (|:| |remainder| $))
             |SINT;divide;2$R;34| |SINT;gcd;3$;35| |SINT;abs;2$;36|
             |SINT;odd?;$B;37| |SINT;zero?;$B;38| |SINT;max;3$;39|
             |SINT;min;3$;40| |SINT;hash;2$;41| |SINT;length;2$;42|
             |SINT;shift;3$;43| |SINT;mulmod;4$;44| |SINT;addmod;4$;45|
             |SINT;submod;4$;46| |SINT;negative?;$B;47|
             (|Record| (|:| |mat| 26) (|:| |vec| (|Vector| 12)))
             (|Vector| $) |SINT;reducedSystem;MVR;48|
             |SINT;positiveRemainder;3$;49| |SINT;coerce;I$;50|
             |SINT;random;$;51| |SINT;random;2$;52|
             (|Record| (|:| |unit| $) (|:| |canonical| $)
                 (|:| |associate| $))
             |SINT;unitNormal;$R;53| (|Union| 85 '"failed")
             (|Fraction| 12) (|Union| $ '"failed") (|Float|)
             (|DoubleFloat|) (|Pattern| 12) (|PatternMatchResult| 12 $)
```

```
   (|InputForm|) (|Union| 12 '"failed")
   (|Record| (|:| |coef| 94) (|:| |generator| $)) (|List| $)
   (|Union| 94 '"failed")
   (|Record| (|:| |coef1| $) (|:| |coef2| $)
       (|:| |generator| $))
   (|Record| (|:| |coef1| $) (|:| |coef2| $))
   (|Union| 97 '"failed") (|Factored| $)
   (|SparseUnivariatePolynomial| $) (|PositiveInteger|)
   (|SingleInteger|))
'#(~= 58 ~ 64 |zero?| 69 |xor| 74 |unitNormal| 80
   |unitCanonical| 85 |unit?| 90 |symmetricRemainder| 95
   |subtractIfCan| 101 |submod| 107 |squareFreePart| 114
   |squareFree| 119 |sizeLess?| 124 |sign| 130 |shift| 135
   |sample| 141 |retractIfCan| 145 |retract| 150 |rem| 155
   |reducedSystem| 161 |recip| 172 |rationalIfCan| 177
   |rational?| 182 |rational| 187 |random| 192 |quo| 201
   |principalIdeal| 207 |prime?| 212 |powmod| 217
   |positiveRemainder| 224 |positive?| 230 |permutation| 235
   |patternMatch| 241 |one?| 248 |odd?| 253 |not| 258
   |nextItem| 263 |negative?| 268 |multiEuclidean| 273
   |mulmod| 279 |min| 286 |max| 296 |mask| 306 |length| 311
   |lcm| 316 |latex| 327 |invmod| 332 |init| 338 |inc| 342
   |hash| 347 |gcdPolynomial| 357 |gcd| 363 |factorial| 374
   |factor| 379 |extendedEuclidean| 384 |exquo| 397
   |expressIdealMember| 403 |even?| 409 |euclideanSize| 414
   |divide| 419 |differentiate| 425 |dec| 436 |copy| 441
   |convert| 446 |coerce| 471 |characteristic| 491 |bit?| 495
   |binomial| 501 |base| 507 |associates?| 511 |addmod| 517
   |abs| 524 ^ 529 |\\/| 541 |Zero| 547 |Or| 551 |One| 557
   |OMwrite| 561 |Not| 585 D 590 |And| 601 >= 607 > 613 = 619
   <= 625 < 631 |/\\| 637 - 643 + 654 ** 660 * 672)
'((|noetherian| . 0) (|canonicalsClosed| . 0)
  (|canonical| . 0) (|canonicalUnitNormal| . 0)
  (|multiplicativeValuation| . 0) (|noZeroDivisors| . 0)
  ((|commutative| "*") . 0) (|rightUnitary| . 0)
  (|leftUnitary| . 0) (|unitsKnown| . 0))
(CONS (|makeByteWordVec2| 1
         '(0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
           0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
           0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
           0))
      (CONS '#(|IntegerNumberSystem&| |EuclideanDomain&|
               |UniqueFactorizationDomain&| NIL NIL
               |GcdDomain&| |IntegralDomain&| |Algebra&|
               |Module&| NIL |Module&| NIL NIL |Module&| NIL
               |DifferentialRing&| |OrderedRing&| NIL
               |Module&| NIL |Module&| NIL NIL NIL NIL NIL
               NIL |Ring&| NIL NIL NIL NIL NIL NIL NIL NIL
               NIL NIL NIL NIL NIL |AbelianGroup&| NIL NIL
               |AbelianMonoid&| |Monoid&| NIL NIL NIL NIL
```

```
   |OrderedSet&| |AbelianSemiGroup&| |SemiGroup&|
   |Logic&| NIL |SetCategory&| NIL NIL NIL NIL
   |RetractableTo&| NIL NIL NIL |RetractableTo&|
   NIL NIL NIL NIL NIL NIL |RetractableTo&| NIL
   |BasicType&| NIL)
(CONS '#((|IntegerNumberSystem|)
         (|EuclideanDomain|)
         (|UniqueFactorizationDomain|)
         (|PrincipalIdealDomain|)
         (|OrderedIntegralDomain|) (|GcdDomain|)
         (|IntegralDomain|) (|Algebra| $$)
         (|Module| 12)
         (|LinearlyExplicitRingOver| 12)
         (|Module| G1062)
         (|LinearlyExplicitRingOver| G1062)
         (|CharacteristicZero|)
         (|Module| G106217)
         (|LinearlyExplicitRingOver| G106217)
         (|DifferentialRing|) (|OrderedRing|)
         (|CommutativeRing|) (|Module| |t#1|)
         (|EntireRing|) (|Module| $$)
         (|BiModule| 12 12)
         (|BiModule| G1062 G1062)
         (|BiModule| G106217 G106217)
         (|OrderedAbelianGroup|)
         (|BiModule| |t#1| |t#1|)
         (|BiModule| $$ $$) (|Ring|)
         (|RightModule| 12) (|LeftModule| 12)
         (|RightModule| G1062)
         (|LeftModule| G1062)
         (|RightModule| G106217)
         (|LeftModule| G106217)
         (|OrderedCancellationAbelianMonoid|)
         (|RightModule| |t#1|)
         (|LeftModule| |t#1|) (|LeftModule| $$)
         (|Rng|) (|RightModule| $$)
         (|OrderedAbelianMonoid|)
         (|AbelianGroup|)
         (|OrderedAbelianSemiGroup|)
         (|CancellationAbelianMonoid|)
         (|AbelianMonoid|) (|Monoid|)
         (|PatternMatchable| 12)
         (|PatternMatchable| G1065)
         (|StepThrough|)
         (|PatternMatchable| G106220)
         (|OrderedSet|) (|AbelianSemiGroup|)
         (|SemiGroup|) (|Logic|) (|RealConstant|)
         (|SetCategory|) (|OpenMath|)
         (|CoercibleTo| G82356)
         (|ConvertibleTo| 89)
```

```
   (|ConvertibleTo| 91)
   (|RetractableTo| 12)
   (|ConvertibleTo| 12)
   (|ConvertibleTo| G1064)
   (|ConvertibleTo| G1063)
   (|RetractableTo| G1061)
   (|ConvertibleTo| G1060)
   (|ConvertibleTo| 87)
   (|ConvertibleTo| 88)
   (|CombinatorialFunctionCategory|)
   (|ConvertibleTo| G106219)
   (|ConvertibleTo| G106218)
   (|RetractableTo| G106216)
   (|ConvertibleTo| G106215) (|BasicType|)
   (|CoercibleTo| 29))
(|makeByteWordVec2| 102
    '(1 8 7 0 9 3 8 7 0 10 10 11 2 8 7 0 12
      13 1 8 7 0 14 0 15 0 16 2 8 0 10 15
      17 1 8 7 0 18 1 8 7 0 19 1 8 7 0 20 1
      12 29 0 30 1 0 0 12 33 2 0 22 0 0 1 1
      0 0 0 41 1 0 22 0 65 2 0 0 0 0 48 1 0
      82 0 83 1 0 0 0 1 1 0 22 0 1 2 0 0 0
      0 1 2 0 86 0 0 1 3 0 0 0 0 0 73 1 0 0
      0 1 1 0 99 0 1 2 0 22 0 0 1 1 0 12 0
      1 2 0 0 0 0 70 0 0 0 1 1 0 92 0 1 1 0
      12 0 1 2 0 0 0 0 59 1 0 26 27 28 2 0
      75 27 76 77 1 0 86 0 1 1 0 84 0 1 1 0
      22 0 1 1 0 85 0 1 1 0 0 0 81 0 0 0 80
      2 0 0 0 0 58 1 0 93 94 1 1 0 22 0 1 3
      0 0 0 0 0 1 2 0 0 0 0 78 1 0 22 0 1 2
      0 0 0 0 1 3 0 90 0 89 90 1 1 0 22 0 1
      1 0 22 0 64 1 0 0 0 42 1 0 86 0 1 1 0
      22 0 74 2 0 95 94 0 1 3 0 0 0 0 0 71
      0 0 0 39 2 0 0 0 0 67 0 0 0 38 2 0 0
      0 0 66 1 0 0 0 1 1 0 0 0 69 1 0 0 94
      1 2 0 0 0 0 1 1 0 10 0 1 2 0 0 0 0 1
      0 0 0 1 1 0 0 0 50 1 0 0 0 68 1 0 102
      0 1 2 0 100 100 100 1 1 0 0 94 1 2 0
      0 0 0 62 1 0 0 0 1 1 0 99 0 1 2 0 96
      0 0 1 3 0 98 0 0 0 1 2 0 86 0 0 1 2 0
      95 94 0 1 1 0 22 0 1 1 0 56 0 1 2 0
      60 0 0 61 1 0 0 0 1 2 0 0 0 56 1 1 0
      0 0 51 1 0 0 0 1 1 0 87 0 1 1 0 88 0
      1 1 0 89 0 1 1 0 91 0 1 1 0 12 0 32 1
      0 0 12 79 1 0 0 0 1 1 0 0 12 79 1 0
      29 0 31 0 0 56 1 2 0 22 0 0 1 2 0 0 0
      0 1 0 0 0 37 2 0 22 0 0 1 3 0 0 0 0 0
      72 1 0 0 0 63 2 0 0 0 56 1 2 0 0 0
      101 1 2 0 0 0 0 44 0 0 0 35 2 0 0 0 0
      47 0 0 0 36 3 0 7 8 0 22 25 2 0 10 0
```

```
                                22 23 2 0 7 8 0 24 1 0 10 0 21 1 0 0
                                0 45 1 0 0 0 1 2 0 0 0 56 1 2 0 0 0 0
                                46 2 0 22 0 0 1 2 0 22 0 0 1 2 0 22 0
                                0 40 2 0 22 0 0 1 2 0 22 0 0 49 2 0 0
                                0 0 43 1 0 0 0 52 2 0 0 0 0 54 2 0 0
                                0 0 53 2 0 0 0 56 57 2 0 0 0 101 1 2
                                0 0 0 0 55 2 0 0 12 0 34 2 0 0 56 0 1
                                2 0 0 101 0 1)))))
          '|lookupComplete|))

(setf (get (QUOTE |SingleInteger|) (QUOTE NILADIC)) T)
```

———-

28.14 SYMBOL.lsp BOOTSTRAP

SYMBOL depends on a chain of files. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **SYMBOL** category which we can write into the **MID** directory. We compile the lisp code and copy the **SYMBOL.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— SYMBOL.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(DEFUN |SYMBOL;writeOMSym| (|dev| |x| $)
  (COND
    ((SPADCALL |x| (QREFELT $ 21))
     (|error| "Cannot convert a scripted symbol to OpenMath"))
    ('T (SPADCALL |dev| |x| (QREFELT $ 25)))))

(DEFUN |SYMBOL;OMwrite;$S;2| (|x| $)
  (PROG (|sp| |dev| |s|)
    (RETURN
      (SEQ (LETT |s| "" |SYMBOL;OMwrite;$S;2|)
           (LETT |sp| (OM-STRINGTOSTRINGPTR |s|) |SYMBOL;OMwrite;$S;2|)
           (LETT |dev|
                 (SPADCALL |sp| (SPADCALL (QREFELT $ 27))
                     (QREFELT $ 29))
                 |SYMBOL;OMwrite;$S;2|)
           (SPADCALL |dev| (QREFELT $ 30))
           (|SYMBOL;writeOMSym| |dev| |x| $)
           (SPADCALL |dev| (QREFELT $ 31))
           (SPADCALL |dev| (QREFELT $ 32))
           (LETT |s| (OM-STRINGPTRTOSTRING |sp|) |SYMBOL;OMwrite;$S;2|)
```

```
          (EXIT |s|)))))

(DEFUN |SYMBOL;OMwrite;$BS;3| (|x| |wholeObj| $)
  (PROG (|sp| |dev| |s|)
    (RETURN
      (SEQ (LETT |s| "" |SYMBOL;OMwrite;$BS;3|)
           (LETT |sp| (OM-STRINGTOSTRINGPTR |s|)
                 |SYMBOL;OMwrite;$BS;3|)
           (LETT |dev|
                 (SPADCALL |sp| (SPADCALL (QREFELT $ 27))
                     (QREFELT $ 29))
                 |SYMBOL;OMwrite;$BS;3|)
           (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 30))))
           (|SYMBOL;writeOMSym| |dev| |x| $)
           (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 31))))
           (SPADCALL |dev| (QREFELT $ 32))
           (LETT |s| (OM-STRINGPTRTOSTRING |sp|)
                 |SYMBOL;OMwrite;$BS;3|)
           (EXIT |s|)))))

(DEFUN |SYMBOL;OMwrite;Omd$V;4| (|dev| |x| $)
  (SEQ (SPADCALL |dev| (QREFELT $ 30))
       (|SYMBOL;writeOMSym| |dev| |x| $)
       (EXIT (SPADCALL |dev| (QREFELT $ 31)))))

(DEFUN |SYMBOL;OMwrite;Omd$BV;5| (|dev| |x| |wholeObj| $)
  (SEQ (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 30))))
       (|SYMBOL;writeOMSym| |dev| |x| $)
       (EXIT (COND (|wholeObj| (SPADCALL |dev| (QREFELT $ 31)))))))

(DEFUN |SYMBOL;convert;$If;6| (|s| |$|) (SPADCALL |s| (QREFELT |$| 44)))

(PUT '|SYMBOL;convert;2$;7| '|SPADreplace| '(XLAM (|s|) |s|))

(DEFUN |SYMBOL;convert;2$;7| (|s| |$|) |s|)

(DEFUN |SYMBOL;coerce;S$;8| (|s| |$|) (VALUES (INTERN |s|)))

(PUT '|SYMBOL;=;2$B;9| '|SPADreplace| 'EQUAL)

(DEFUN |SYMBOL;=;2$B;9| (|x| |y| |$|) (EQUAL |x| |y|))

(PUT '|SYMBOL;<;2$B;10| '|SPADreplace|
     '(XLAM (|x| |y|) (GGREATERP |y| |x|)))

(DEFUN |SYMBOL;<;2$B;10| (|x| |y| |$|) (GGREATERP |y| |x|))

(DEFUN |SYMBOL;coerce;$Of;11| (|x| |$|) (SPADCALL |x| (QREFELT |$| 51)))

(DEFUN |SYMBOL;subscript;$L$;12| (|sy| |lx| $)
```

```
  (SPADCALL |sy| (LIST |lx| NIL NIL NIL NIL) (QREFELT $ 54)))

(DEFUN |SYMBOL;elt;$L$;13| (|sy| |lx| $)
  (SPADCALL |sy| |lx| (QREFELT $ 56)))

(DEFUN |SYMBOL;superscript;$L$;14| (|sy| |lx| $)
  (SPADCALL |sy| (LIST NIL |lx| NIL NIL NIL) (QREFELT $ 54)))

(DEFUN |SYMBOL;argscript;$L$;15| (|sy| |lx| $)
  (SPADCALL |sy| (LIST NIL NIL NIL NIL |lx|) (QREFELT $ 54)))

(DEFUN |SYMBOL;patternMatch;$P2Pmr;16| (|x| |p| |l| $)
  (SPADCALL |x| |p| |l| (QREFELT $ 63)))

(DEFUN |SYMBOL;patternMatch;$P2Pmr;17| (|x| |p| |l| $)
  (SPADCALL |x| |p| |l| (QREFELT $ 69)))

(DEFUN |SYMBOL;convert;$P;18| (|x| |$|) (SPADCALL |x| (QREFELT |$| 72)))

(DEFUN |SYMBOL;convert;$P;19| (|x| |$|) (SPADCALL |x| (QREFELT |$| 74)))

(DEFUN |SYMBOL;syprefix| (|sc| $)
  (PROG (|ns| G108218 |n| G108219)
    (RETURN
      (SEQ (LETT |ns|
                 (LIST (LENGTH (QVELT |sc| 3)) (LENGTH (QVELT |sc| 2))
                       (LENGTH (QVELT |sc| 1)) (LENGTH (QVELT |sc| 0)))
                 |SYMBOL;syprefix|)
           (SEQ G190
                (COND
                  ((NULL (COND
                           ((< (LENGTH |ns|) 2) 'NIL)
                           ('T (ZEROP (|SPADfirst| |ns|)))))
                    (GO G191)))
                (SEQ (EXIT (LETT |ns| (CDR |ns|) |SYMBOL;syprefix|)))
                NIL (GO G190) G191 (EXIT NIL))
           (EXIT (SPADCALL
                   (CONS (STRCONC (QREFELT $ 37)
                                  (|SYMBOL;istring|
                                   (LENGTH (QVELT |sc| 4)) $))
                         (PROGN
                           (LETT G108218 NIL |SYMBOL;syprefix|)
                           (SEQ (LETT |n| NIL |SYMBOL;syprefix|)
                                (LETT G108219 (NREVERSE |ns|)
                                      |SYMBOL;syprefix|)
                                G190
                                (COND
                                  ((OR (ATOM G108219)
                                    (PROGN
                                      (LETT |n| (CAR G108219)
```

```
                                        |SYMBOL;syprefix|)
                                       NIL))
                                   (GO G191)))
                                (SEQ (EXIT
                                      (LETT G108218
                                       (CONS (|SYMBOL;istring| |n| $)
                                        G108218)
                                       |SYMBOL;syprefix|)))
                                (LETT G108219 (CDR G108219)
                                      |SYMBOL;syprefix|)
                                (GO G190) G191
                                (EXIT (NREVERSE0 G108218)))))
                     (QREFELT $ 77)))))))

(DEFUN |SYMBOL;syscripts| (|sc| $)
  (PROG (|all|)
    (RETURN
      (SEQ (LETT |all| (QVELT |sc| 3) |SYMBOL;syscripts|)
           (LETT |all| (SPADCALL (QVELT |sc| 2) |all| (QREFELT $ 78))
                 |SYMBOL;syscripts|)
           (LETT |all| (SPADCALL (QVELT |sc| 1) |all| (QREFELT $ 78))
                 |SYMBOL;syscripts|)
           (LETT |all| (SPADCALL (QVELT |sc| 0) |all| (QREFELT $ 78))
                 |SYMBOL;syscripts|)
           (EXIT (SPADCALL |all| (QVELT |sc| 4) (QREFELT $ 78)))))))

(DEFUN |SYMBOL;script;$L$;22| (|sy| |ls| $)
  (PROG (|sc|)
    (RETURN
      (SEQ (LETT |sc| (VECTOR NIL NIL NIL NIL NIL)
                 |SYMBOL;script;$L$;22|)
           (COND
             ((NULL (NULL |ls|))
              (SEQ (QSETVELT |sc| 0 (|SPADfirst| |ls|))
                   (EXIT (LETT |ls| (CDR |ls|) |SYMBOL;script;$L$;22|)))))
           (COND
             ((NULL (NULL |ls|))
              (SEQ (QSETVELT |sc| 1 (|SPADfirst| |ls|))
                   (EXIT (LETT |ls| (CDR |ls|) |SYMBOL;script;$L$;22|)))))
           (COND
             ((NULL (NULL |ls|))
              (SEQ (QSETVELT |sc| 2 (|SPADfirst| |ls|))
                   (EXIT (LETT |ls| (CDR |ls|) |SYMBOL;script;$L$;22|)))))
           (COND
             ((NULL (NULL |ls|))
              (SEQ (QSETVELT |sc| 3 (|SPADfirst| |ls|))
                   (EXIT (LETT |ls| (CDR |ls|) |SYMBOL;script;$L$;22|)))))
           (COND
             ((NULL (NULL |ls|))
              (SEQ (QSETVELT |sc| 4 (|SPADfirst| |ls|))
```

```
                (EXIT (LETT |ls| (CDR |ls|) |SYMBOL;script;$L$;22|)))))
          (EXIT (SPADCALL |sy| |sc| (QREFELT $ 80)))))))

(DEFUN |SYMBOL;script;$R$;23| (|sy| |sc| $)
  (COND
    ((SPADCALL |sy| (QREFELT $ 21))
     (|error| "Cannot add scripts to a scripted symbol"))
    ('T
     (CONS (SPADCALL
               (SPADCALL
                   (STRCONC (|SYMBOL;syprefix| |sc| $)
                            (SPADCALL (SPADCALL |sy| (QREFELT $ 81))
                                (QREFELT $ 82)))
                   (QREFELT $ 47))
               (QREFELT $ 52))
           (|SYMBOL;syscripts| |sc| $)))))

(DEFUN |SYMBOL;string;$S;24| (|e| $)
  (COND
    ((NULL (SPADCALL |e| (QREFELT $ 21))) (PNAME |e|))
    ('T (|error| "Cannot form string from non-atomic symbols."))))

(DEFUN |SYMBOL;latex;$S;25| (|e| $)
  (PROG (|ss| |lo| |sc| |s|)
    (RETURN
      (SEQ (LETT |s| (PNAME (SPADCALL |e| (QREFELT $ 81)))
                 |SYMBOL;latex;$S;25|)
           (COND
             ((< 1 (QCSIZE |s|))
              (COND
                ((NULL (SPADCALL (SPADCALL |s| 1 (QREFELT $ 83))
                           (SPADCALL "\\" (QREFELT $ 40))
                           (QREFELT $ 84)))
                 (LETT |s| (STRCONC "\\mbox{\\it " (STRCONC |s| "}"))
                       |SYMBOL;latex;$S;25|))))))
           (COND ((NULL (SPADCALL |e| (QREFELT $ 21))) (EXIT |s|)))
           (LETT |ss| (SPADCALL |e| (QREFELT $ 85))
                 |SYMBOL;latex;$S;25|)
           (LETT |lo| (QVELT |ss| 0) |SYMBOL;latex;$S;25|)
           (COND
             ((NULL (NULL |lo|))
              (SEQ (LETT |sc| "_{" |SYMBOL;latex;$S;25|)
                   (SEQ G190
                        (COND
                          ((NULL (COND ((NULL |lo|) 'NIL) ('T 'T)))
                           (GO G191)))
                        (SEQ (LETT |sc|
                                   (STRCONC |sc|
                                    (SPADCALL (|SPADfirst| |lo|)
                                     (QREFELT $ 86)))
```

```
                        |SYMBOL;latex;$S;25|)
                   (LETT |lo| (CDR |lo|)
                        |SYMBOL;latex;$S;25|)
                   (EXIT (COND
                           ((NULL (NULL |lo|))
                            (LETT |sc| (STRCONC |sc| ", ")
                             |SYMBOL;latex;$S;25|)))))
              NIL (GO G190) G191 (EXIT NIL))
         (LETT |sc| (STRCONC |sc| "}") |SYMBOL;latex;$S;25|)
         (EXIT (LETT |s| (STRCONC |s| |sc|)
                     |SYMBOL;latex;$S;25|)))))
(LETT |lo| (QVELT |ss| 1) |SYMBOL;latex;$S;25|)
(COND
  ((NULL (NULL |lo|))
   (SEQ (LETT |sc| "^{" |SYMBOL;latex;$S;25|)
        (SEQ G190
             (COND
               ((NULL (COND ((NULL |lo|) 'NIL) ('T 'T)))
                (GO G191)))
             (SEQ (LETT |sc|
                        (STRCONC |sc|
                         (SPADCALL (|SPADfirst| |lo|)
                          (QREFELT $ 86)))
                        |SYMBOL;latex;$S;25|)
                  (LETT |lo| (CDR |lo|)
                        |SYMBOL;latex;$S;25|)
                  (EXIT (COND
                          ((NULL (NULL |lo|))
                           (LETT |sc| (STRCONC |sc| ", ")
                            |SYMBOL;latex;$S;25|)))))
             NIL (GO G190) G191 (EXIT NIL))
        (LETT |sc| (STRCONC |sc| "}") |SYMBOL;latex;$S;25|)
        (EXIT (LETT |s| (STRCONC |s| |sc|)
                    |SYMBOL;latex;$S;25|)))))
(LETT |lo| (QVELT |ss| 2) |SYMBOL;latex;$S;25|)
(COND
  ((NULL (NULL |lo|))
   (SEQ (LETT |sc| "{}^{" |SYMBOL;latex;$S;25|)
        (SEQ G190
             (COND
               ((NULL (COND ((NULL |lo|) 'NIL) ('T 'T)))
                (GO G191)))
             (SEQ (LETT |sc|
                        (STRCONC |sc|
                         (SPADCALL (|SPADfirst| |lo|)
                          (QREFELT $ 86)))
                        |SYMBOL;latex;$S;25|)
                  (LETT |lo| (CDR |lo|)
                        |SYMBOL;latex;$S;25|)
                  (EXIT (COND
```

```
                              ((NULL (NULL |lo|))
                               (LETT |sc| (STRCONC |sc| ", ")
                                |SYMBOL;latex;$S;25|)))))
                    NIL (GO G190) G191 (EXIT NIL))
              (LETT |sc| (STRCONC |sc| "}") |SYMBOL;latex;$S;25|)
              (EXIT (LETT |s| (STRCONC |sc| |s|)
                          |SYMBOL;latex;$S;25|)))))
        (LETT |lo| (QVELT |ss| 3) |SYMBOL;latex;$S;25|)
        (COND
          ((NULL (NULL |lo|))
           (SEQ (LETT |sc| "{}_{" |SYMBOL;latex;$S;25|)
                (SEQ G190
                     (COND
                       ((NULL (COND ((NULL |lo|) 'NIL) ('T 'T)))
                        (GO G191)))
                     (SEQ (LETT |sc|
                                (STRCONC |sc|
                                 (SPADCALL (|SPADfirst| |lo|)
                                  (QREFELT $ 86)))
                                |SYMBOL;latex;$S;25|)
                          (LETT |lo| (CDR |lo|)
                                |SYMBOL;latex;$S;25|)
                          (EXIT (COND
                                  ((NULL (NULL |lo|))
                                   (LETT |sc| (STRCONC |sc| ", ")
                                    |SYMBOL;latex;$S;25|)))))
                     NIL (GO G190) G191 (EXIT NIL))
              (LETT |sc| (STRCONC |sc| "}") |SYMBOL;latex;$S;25|)
              (EXIT (LETT |s| (STRCONC |sc| |s|)
                          |SYMBOL;latex;$S;25|)))))
        (LETT |lo| (QVELT |ss| 4) |SYMBOL;latex;$S;25|)
        (COND
          ((NULL (NULL |lo|))
           (SEQ (LETT |sc| "\\left( {" |SYMBOL;latex;$S;25|)
                (SEQ G190
                     (COND
                       ((NULL (COND ((NULL |lo|) 'NIL) ('T 'T)))
                        (GO G191)))
                     (SEQ (LETT |sc|
                                (STRCONC |sc|
                                 (SPADCALL (|SPADfirst| |lo|)
                                  (QREFELT $ 86)))
                                |SYMBOL;latex;$S;25|)
                          (LETT |lo| (CDR |lo|)
                                |SYMBOL;latex;$S;25|)
                          (EXIT (COND
                                  ((NULL (NULL |lo|))
                                   (LETT |sc| (STRCONC |sc| ", ")
                                    |SYMBOL;latex;$S;25|)))))
                     NIL (GO G190) G191 (EXIT NIL))
```

```
                (LETT |sc| (STRCONC |sc| "} \\right)")
                      |SYMBOL;latex;$S;25|)
                (EXIT (LETT |s| (STRCONC |s| |sc|)
                            |SYMBOL;latex;$S;25|)))))
          (EXIT |s|)))))

(DEFUN |SYMBOL;anyRadix| (|n| |s| $)
  (PROG (|qr| |ns| G108274)
    (RETURN
      (SEQ (EXIT (SEQ (LETT |ns| "" |SYMBOL;anyRadix|)
                      (EXIT (SEQ G190 NIL
                                 (SEQ (LETT |qr|
                                       (DIVIDE2 |n| (QCSIZE |s|))
                                       |SYMBOL;anyRadix|)
                                      (LETT |n| (QCAR |qr|)
                                       |SYMBOL;anyRadix|)
                                      (LETT |ns|
                                       (SPADCALL
                                        (SPADCALL |s|
                                         (+ (QCDR |qr|)
                                          (SPADCALL |s| (QREFELT $ 88)))
                                         (QREFELT $ 83))
                                        |ns| (QREFELT $ 89))
                                       |SYMBOL;anyRadix|)
                                      (EXIT
                                       (COND
                                         ((ZEROP |n|)
                                          (PROGN
                                            (LETT G108274 |ns|
                                             |SYMBOL;anyRadix|)
                                            (GO G108274))))))
                                 NIL (GO G190) G191 (EXIT NIL)))))
          G108274 (EXIT G108274)))))

(DEFUN |SYMBOL;new;$;27| ($)
  (PROG (|sym|)
    (RETURN
      (SEQ (LETT |sym|
                 (|SYMBOL;anyRadix|
                     (SPADCALL (QREFELT $ 9) (QREFELT $ 90))
                     (QREFELT $ 18) $)
                 |SYMBOL;new;$;27|)
           (SPADCALL (QREFELT $ 9)
               (+ (SPADCALL (QREFELT $ 9) (QREFELT $ 90)) 1)
               (QREFELT $ 91))
           (EXIT (SPADCALL (STRCONC "%" |sym|) (QREFELT $ 47)))))))

(DEFUN |SYMBOL;new;2$;28| (|x| $)
  (PROG (|u| |n| |xx|)
    (RETURN
```

```
      (SEQ (LETT |n|
                 (SEQ (LETT |u|
                            (SPADCALL |x| (QREFELT $ 12)
                                (QREFELT $ 94))
                            |SYMBOL;new;2$;28|)
                      (EXIT (COND
                              ((QEQCAR |u| 1) 0)
                              ('T (+ (QCDR |u|) 1)))))
                 |SYMBOL;new;2$;28|)
           (SPADCALL (QREFELT $ 12) |x| |n| (QREFELT $ 95))
           (LETT |xx|
                 (COND
                   ((NULL (SPADCALL |x| (QREFELT $ 21)))
                    (SPADCALL |x| (QREFELT $ 82)))
                   ('T
                    (SPADCALL (SPADCALL |x| (QREFELT $ 81))
                        (QREFELT $ 82))))
                 |SYMBOL;new;2$;28|)
           (LETT |xx| (STRCONC "%" |xx|) |SYMBOL;new;2$;28|)
           (LETT |xx|
                 (COND
                   ((NULL (< (SPADCALL
                                 (SPADCALL |xx|
                                     (SPADCALL |xx| (QREFELT $ 96))
                                     (QREFELT $ 83))
                                 (QREFELT $ 17) (QREFELT $ 97))
                             (SPADCALL (QREFELT $ 17) (QREFELT $ 88))))
                    (STRCONC |xx|
                             (|SYMBOL;anyRadix| |n| (QREFELT $ 19) $)))
                   ('T
                    (STRCONC |xx|
                             (|SYMBOL;anyRadix| |n| (QREFELT $ 17) $))))
                 |SYMBOL;new;2$;28|)
           (COND
             ((NULL (SPADCALL |x| (QREFELT $ 21)))
              (EXIT (SPADCALL |xx| (QREFELT $ 47)))))
           (EXIT (SPADCALL (SPADCALL |xx| (QREFELT $ 47))
                     (SPADCALL |x| (QREFELT $ 85)) (QREFELT $ 80)))))))

(DEFUN |SYMBOL;resetNew;V;29| ($)
  (PROG (|k| G108297)
    (RETURN
      (SEQ (SPADCALL (QREFELT $ 9) 0 (QREFELT $ 91))
           (SEQ (LETT |k| NIL |SYMBOL;resetNew;V;29|)
                (LETT G108297 (SPADCALL (QREFELT $ 12) (QREFELT $ 100))
                      |SYMBOL;resetNew;V;29|)
               G190
                (COND
                  ((OR (ATOM G108297)
                       (PROGN
```

```
                    (LETT |k| (CAR G108297)
                          |SYMBOL;resetNew;V;29|)
                    NIL))
                (GO G191)))
            (SEQ (EXIT (SPADCALL |k| (QREFELT $ 12)
                          (QREFELT $ 101))))
            (LETT G108297 (CDR G108297) |SYMBOL;resetNew;V;29|)
            (GO G190) G191 (EXIT NIL))
        (EXIT (SPADCALL (QREFELT $ 102)))))))

(DEFUN |SYMBOL;scripted?;$B;30| (|sy| $)
  (COND ((ATOM |sy|) 'NIL) ('T 'T)))

(DEFUN |SYMBOL;name;2$;31| (|sy| $)
  (PROG (|str| |i| G108304 G108303 G108301)
    (RETURN
      (SEQ (EXIT (COND
                   ((NULL (SPADCALL |sy| (QREFELT $ 21))) |sy|)
                   ('T
                    (SEQ (LETT |str|
                               (SPADCALL
                                   (SPADCALL
                                    (SPADCALL |sy| (QREFELT $ 104))
                                    (QREFELT $ 105))
                                   (QREFELT $ 82))
                               |SYMBOL;name;2$;31|)
                         (SEQ (EXIT (SEQ
                                     (LETT |i| (+ (QREFELT $ 38) 1)
                                      |SYMBOL;name;2$;31|)
                                     (LETT G108304 (QCSIZE |str|)
                                      |SYMBOL;name;2$;31|)
                                     G190
                                     (COND
                                       ((> |i| G108304) (GO G191)))
                                     (SEQ
                                      (EXIT
                                       (COND
                                         ((NULL
                                           (SPADCALL
                                            (SPADCALL |str| |i|
                                             (QREFELT $ 83))
                                            (QREFELT $ 106)))
                                          (PROGN
                                            (LETT G108301
                                             (PROGN
                                               (LETT G108303
                                                (SPADCALL
                                                 (SPADCALL |str|
                                                  (SPADCALL |i|
                                                   (QCSIZE |str|)
```

```
                                                  (QREFELT $ 108))
                                                 (QREFELT $ 109))
                                                (QREFELT $ 47))
                                               |SYMBOL;name;2$;31|)
                                              (GO G108303))
                                             |SYMBOL;name;2$;31|)
                                            (GO G108301))))))
                                     (LETT |i| (+ |i| 1)
                                      |SYMBOL;name;2$;31|)
                                     (GO G190) G191 (EXIT NIL)))
                               G108301 (EXIT G108301))
                          (EXIT (|error| "Improper scripted symbol"))))))
                G108303 (EXIT G108303)))))

(DEFUN |SYMBOL;scripts;$R;32| (|sy| $)
  (PROG (|lscripts| |str| |nstr| |j| G108307 |nscripts| |m| |n| G108316
           |i| G108317 |a| G108318 |allscripts|)
    (RETURN
      (SEQ (COND
             ((NULL (SPADCALL |sy| (QREFELT $ 21)))
              (VECTOR NIL NIL NIL NIL NIL))
             ('T
              (SEQ (LETT |nscripts| (LIST 0 0 0 0 0)
                         |SYMBOL;scripts;$R;32|)
                   (LETT |lscripts| (LIST NIL NIL NIL NIL NIL)
                         |SYMBOL;scripts;$R;32|)
                   (LETT |str|
                         (SPADCALL
                             (SPADCALL (SPADCALL |sy| (QREFELT $ 104))
                                 (QREFELT $ 105))
                             (QREFELT $ 82))
                         |SYMBOL;scripts;$R;32|)
                   (LETT |nstr| (QCSIZE |str|) |SYMBOL;scripts;$R;32|)
                   (LETT |m| (SPADCALL |nscripts| (QREFELT $ 111))
                         |SYMBOL;scripts;$R;32|)
                   (SEQ (LETT |j| (+ (QREFELT $ 38) 1)
                              |SYMBOL;scripts;$R;32|)
                        (LETT |i| |m| |SYMBOL;scripts;$R;32|) G190
                        (COND
                          ((OR (> |j| |nstr|)
                               (NULL (SPADCALL
                                       (SPADCALL |str| |j|
                                        (QREFELT $ 83))
                                       (QREFELT $ 106))))
                            (GO G191)))
                        (SEQ (EXIT (SPADCALL |nscripts| |i|
                                   (PROG1
                                    (LETT G108307
                                     (-
                                      (SPADCALL
```

```
                        (SPADCALL |str| |j|
                         (QREFELT $ 83))
                        (QREFELT $ 41))
                       (QREFELT $ 42))
                      |SYMBOL;scripts;$R;32|)
                      (|check-subtype| (>= G108307 0)
                       '(|NonNegativeInteger|) G108307))
                     (QREFELT $ 113))))
     (LETT |i|
           (PROG1 (+ |i| 1)
             (LETT |j| (+ |j| 1)
                   |SYMBOL;scripts;$R;32|))
           |SYMBOL;scripts;$R;32|)
     (GO G190) G191 (EXIT NIL))
(LETT |nscripts|
      (SPADCALL (CDR |nscripts|)
          (|SPADfirst| |nscripts|) (QREFELT $ 114))
      |SYMBOL;scripts;$R;32|)
(LETT |allscripts|
      (SPADCALL (SPADCALL |sy| (QREFELT $ 104))
          (QREFELT $ 115))
      |SYMBOL;scripts;$R;32|)
(LETT |m| (SPADCALL |lscripts| (QREFELT $ 116))
      |SYMBOL;scripts;$R;32|)
(SEQ (LETT |n| NIL |SYMBOL;scripts;$R;32|)
     (LETT G108316 |nscripts|
           |SYMBOL;scripts;$R;32|)
     (LETT |i| |m| |SYMBOL;scripts;$R;32|) G190
     (COND
       ((OR (ATOM G108316)
            (PROGN
              (LETT |n| (CAR G108316)
                    |SYMBOL;scripts;$R;32|)
              NIL))
         (GO G191)))
     (SEQ (EXIT (COND
                  ((<
                    (SPADCALL |allscripts|
                     (QREFELT $ 117))
                    |n|)
                   (|error|
                    "Improper script count in symbol"))
                  ('T
                   (SEQ
                    (SPADCALL |lscripts| |i|
                     (PROGN
                       (LETT G108317 NIL
                        |SYMBOL;scripts;$R;32|)
                       (SEQ
                        (LETT |a| NIL
```

```
                                        |SYMBOL;scripts;$R;32|)
                                       (LETT G108318
                                        (SPADCALL |allscripts| |n|
                                         (QREFELT $ 118))
                                        |SYMBOL;scripts;$R;32|)
                                       G190
                                       (COND
                                         ((OR (ATOM G108318)
                                            (PROGN
                                              (LETT |a|
                                               (CAR G108318)
                                               |SYMBOL;scripts;$R;32|)
                                              NIL))
                                           (GO G191)))
                                       (SEQ
                                        (EXIT
                                         (LETT G108317
                                          (CONS
                                           (SPADCALL |a|
                                            (QREFELT $ 52))
                                           G108317)
                                          |SYMBOL;scripts;$R;32|)))
                                       (LETT G108318 (CDR G108318)
                                        |SYMBOL;scripts;$R;32|)
                                       (GO G190) G191
                                       (EXIT (NREVERSE0 G108317))))
                                    (QREFELT $ 119))
                                   (EXIT
                                    (LETT |allscripts|
                                     (SPADCALL |allscripts| |n|
                                      (QREFELT $ 120))
                                     |SYMBOL;scripts;$R;32|)))))))
                         (LETT |i|
                               (PROG1 (+ |i| 1)
                                 (LETT G108316 (CDR G108316)
                                       |SYMBOL;scripts;$R;32|))
                               |SYMBOL;scripts;$R;32|)
                         (GO G190) G191 (EXIT NIL))
                   (EXIT (VECTOR (SPADCALL |lscripts| |m|
                                           (QREFELT $ 121))
                                 (SPADCALL |lscripts| (+ |m| 1)
                                           (QREFELT $ 121))
                                 (SPADCALL |lscripts| (+ |m| 2)
                                           (QREFELT $ 121))
                                 (SPADCALL |lscripts| (+ |m| 3)
                                           (QREFELT $ 121))
                                 (SPADCALL |lscripts| (+ |m| 4)
                                           (QREFELT $ 121))))))))))))

(DEFUN |SYMBOL;istring| (|n| $)
```

```
  (COND
    ((< 9 |n|) (|error| "Can have at most 9 scripts of each kind"))
    ('T (ELT (QREFELT $ 16) (+ |n| 0)))))

(DEFUN |SYMBOL;list;$L;34| (|sy| $)
  (COND
    ((NULL (SPADCALL |sy| (QREFELT $ 21)))
     (|error| "Cannot convert a symbol to a list if it is not subscripted"))
    ('T |sy|)))

(DEFUN |SYMBOL;sample;$;35| (|$|) (SPADCALL "aSymbol" (QREFELT |$| 47)))

(DEFUN |Symbol| ()
  (PROG ()
    (RETURN
      (PROG (G108325)
        (RETURN
          (COND
            ((LETT G108325 (HGET |$ConstructorCache| '|Symbol|)
                   |Symbol|)
             (|CDRwithIncrement| (CDAR G108325)))
            ('T
             (UNWIND-PROTECT
               (PROG1 (CDDAR (HPUT |$ConstructorCache| '|Symbol|
                                   (LIST
                                    (CONS NIL (CONS 1 (|Symbol;|))))))
                 (LETT G108325 T |Symbol|))
               (COND
                 ((NOT G108325) (HREM |$ConstructorCache| '|Symbol|)))))))))))

(DEFUN |Symbol;| ()
  (PROG (|dv$| $ |pv$|)
    (RETURN
      (PROGN
        (LETT |dv$| '(|Symbol|) |Symbol|)
        (LETT $ (make-array 124) |Symbol|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$| (|buildPredVector| 0 0 NIL) |Symbol|))
        (|haddProp| |$ConstructorCache| '|Symbol| NIL (CONS 1 $))
        (|stuffDomainSlots| $)
        (QSETREFV $ 9 (SPADCALL 0 (QREFELT $ 8)))
        (QSETREFV $ 12 (SPADCALL (QREFELT $ 11)))
        (QSETREFV $ 16
            (SPADCALL (LIST "0" "1" "2" "3" "4" "5" "6" "7" "8" "9")
                (QREFELT $ 15)))
        (QSETREFV $ 17 "0123456789")
        (QSETREFV $ 18 "ABCDEFGHIJKLMNOPQRSTUVWXYZ")
        (QSETREFV $ 19 "abcdefghijklmnopqrstuvwxyz")
        (QSETREFV $ 37 "*")
```

```
        (QSETREFV $ 38 (QCSIZE (QREFELT $ 37)))
        (QSETREFV $ 42
            (SPADCALL (SPADCALL "0" (QREFELT $ 40)) (QREFELT $ 41)))
        $))))

(setf (get '|Symbol| '|infovec|)
    (LIST '#(NIL NIL NIL NIL NIL NIL (|Integer|) (|Reference| 6)
             (0 . |ref|) '|count| (|AssociationList| $$ 6)
             (5 . |empty|) '|xcount| (|List| 28) (|PrimitiveArray| 28)
             (9 . |construct|) '|istrings| '|nums| 'ALPHAS '|alphas|
             (|Boolean|) |SYMBOL;scripted?;$B;30| (|Void|) (|Symbol|)
             (|OpenMathDevice|) (14 . |OMputVariable|)
             (|OpenMathEncoding|) (20 . |OMencodingXML|) (|String|)
             (24 . |OMopenString|) (30 . |OMputObject|)
             (35 . |OMputEndObject|) (40 . |OMclose|)
             |SYMBOL;OMwrite;$S;2| |SYMBOL;OMwrite;$BS;3|
             |SYMBOL;OMwrite;Omd$V;4| |SYMBOL;OMwrite;Omd$BV;5| '|hd|
             '|lhd| (|Character|) (45 . |char|) (50 . |ord|) '|ord0|
             (|InputForm|) (55 . |convert|) |SYMBOL;convert;$If;6|
             |SYMBOL;convert;2$;7| |SYMBOL;coerce;S$;8|
             |SYMBOL;=;2$B;9| |SYMBOL;<;2$B;10| (|OutputForm|)
             (60 . |outputForm|) |SYMBOL;coerce;$Of;11| (|List| 55)
             |SYMBOL;script;$L$;22| (|List| 50)
             |SYMBOL;subscript;$L$;12| |SYMBOL;elt;$L$;13|
             |SYMBOL;superscript;$L$;14| |SYMBOL;argscript;$L$;15|
             (|PatternMatchResult| 6 23) (|Pattern| 6)
             (|PatternMatchSymbol| 6) (65 . |patternMatch|)
             (|PatternMatchResult| 6 $) |SYMBOL;patternMatch;$P2Pmr;16|
             (|PatternMatchResult| (|Float|) 23) (|Pattern| (|Float|))
             (|PatternMatchSymbol| (|Float|)) (72 . |patternMatch|)
             (|PatternMatchResult| (|Float|) $)
             |SYMBOL;patternMatch;$P2Pmr;17| (79 . |coerce|)
             |SYMBOL;convert;$P;18| (84 . |coerce|)
             |SYMBOL;convert;$P;19| (|List| $) (89 . |concat|)
             (94 . |concat|)
             (|Record| (|:| |sub| 55) (|:| |sup| 55) (|:| |presup| 55)
                 (|:| |presub| 55) (|:| |args| 55))
             |SYMBOL;script;$R$;23| |SYMBOL;name;2$;31|
             |SYMBOL;string;$S;24| (100 . |elt|) (106 . =)
             |SYMBOL;scripts;$R;32| (112 . |latex|)
             |SYMBOL;latex;$S;25| (117 . |minIndex|) (122 . |concat|)
             (128 . |elt|) (133 . |setelt|) |SYMBOL;new;$;27|
             (|Union| 6 '"failed") (139 . |search|) (145 . |setelt|)
             (152 . |maxIndex|) (157 . |position|) |SYMBOL;new;2$;28|
             (|List| $$) (163 . |keys|) (168 . |remove!|)
             (174 . |void|) |SYMBOL;resetNew;V;29| |SYMBOL;list;$L;34|
             (178 . |first|) (183 . |digit?|) (|UniversalSegment| 6)
             (188 . SEGMENT) (194 . |elt|) (|List| 112)
             (200 . |minIndex|) (|NonNegativeInteger|) (205 . |setelt|)
             (212 . |concat|) (218 . |rest|) (223 . |minIndex|)
```

```
   (228 . |#|) (233 . |first|) (239 . |setelt|)
   (246 . |rest|) (252 . |elt|)
   (CONS IDENTITY
         (FUNCALL (|dispatchFunction| |SYMBOL;sample;$;35|)
                  $))
   (|SingleInteger|))
'#(~= 258 |superscript| 264 |subscript| 270 |string| 276
   |scripts| 281 |scripted?| 286 |script| 291 |sample| 303
   |resetNew| 307 |patternMatch| 311 |new| 325 |name| 334
   |min| 339 |max| 345 |list| 351 |latex| 356 |hash| 361
   |elt| 366 |convert| 372 |coerce| 392 |argscript| 402
   |OMwrite| 408 >= 432 > 438 = 444 <= 450 < 456)
'NIL
(CONS (|makeByteWordVec2| 1 '(0 0 0 0 0 0 0 0 0 0))
      (CONS '#(|OrderedSet&| NIL NIL |SetCategory&|
               |BasicType&| NIL NIL NIL NIL NIL NIL)
            (CONS '#((|OrderedSet|)
                     (|PatternMatchable| (|Float|))
                     (|PatternMatchable| 6) (|SetCategory|)
                     (|BasicType|) (|ConvertibleTo| 67)
                     (|ConvertibleTo| 61)
                     (|ConvertibleTo| 23) (|OpenMath|)
                     (|ConvertibleTo| 43) (|CoercibleTo| 50))
                  (|makeByteWordVec2| 123
                      '(1 7 0 6 8 0 10 0 11 1 14 0 13 15 2 24
                        22 0 23 25 0 26 0 27 2 24 0 28 26 29
                        1 24 22 0 30 1 24 22 0 31 1 24 22 0
                        32 1 39 0 28 40 1 39 6 0 41 1 43 0 23
                        44 1 50 0 23 51 3 62 60 23 61 60 63 3
                        68 66 23 67 66 69 1 67 0 23 72 1 61 0
                        23 74 1 28 0 76 77 2 55 0 0 0 78 2 28
                        39 0 6 83 2 39 20 0 0 84 1 50 28 0 86
                        1 28 6 0 88 2 28 0 39 0 89 1 7 6 0 90
                        2 7 6 0 6 91 2 10 93 2 0 94 3 10 6 0
                        2 6 95 1 28 6 0 96 2 28 6 39 0 97 1
                        10 99 0 100 2 10 93 2 0 101 0 22 0
                        102 1 99 2 0 105 1 39 20 0 106 2 107
                        0 6 6 108 2 28 0 0 107 109 1 110 6 0
                        111 3 110 112 0 6 112 113 2 110 0 0
                        112 114 1 99 0 0 115 1 53 6 0 116 1
                        99 112 0 117 2 99 0 0 112 118 3 53 55
                        0 6 55 119 2 99 0 0 112 120 2 53 55 0
                        6 121 2 0 20 0 0 1 2 0 0 0 55 58 2 0
                        0 0 55 56 1 0 28 0 82 1 0 79 0 85 1 0
                        20 0 21 2 0 0 0 53 54 2 0 0 0 79 80 0
                        0 0 122 0 0 22 103 3 0 64 0 61 64 65
                        3 0 70 0 67 70 71 1 0 0 0 98 0 0 0 92
                        1 0 0 0 81 2 0 0 0 0 1 2 0 0 0 0 1 1
                        0 76 0 104 1 0 28 0 87 1 0 123 0 1 2
                        0 0 0 55 57 1 0 61 0 75 1 0 67 0 73 1
```

```
                                0 23 0 46 1 0 43 0 45 1 0 0 28 47 1 0
                                50 0 52 2 0 0 0 55 59 3 0 22 24 0 20
                                36 2 0 28 0 20 34 2 0 22 24 0 35 1 0
                                28 0 33 2 0 20 0 0 1 2 0 20 0 0 1 2 0
                                20 0 0 48 2 0 20 0 0 1 2 0 20 0 0 49)))))
          '|lookupComplete|))

(setf (get '|Symbol| 'NILADIC) T)
```

———-

28.15 VECTOR.lsp BOOTSTRAP

VECTOR depends on itself. We need to break this cycle to build the algebra. So we keep a cached copy of the translated **VECTOR** category which we can write into the **MID** directory. We compile the lisp code and copy the **VECTOR.o** file to the **OUT** directory. This is eventually forcibly replaced by a recompiled version.

Note that this code is not included in the generated catdef.spad file.

— VECTOR.lsp BOOTSTRAP —

```
(|/VERSIONCHECK| 2)

(DEFUN |VECTOR;vector;L$;1| (|l| |$|) (SPADCALL |l| (QREFELT |$| 8)))

(DEFUN |VECTOR;convert;$If;2| (|x| |$|)
 (SPADCALL
  (LIST
   (SPADCALL (SPADCALL "vector" (QREFELT |$| 12)) (QREFELT |$| 14))
   (SPADCALL (SPADCALL |x| (QREFELT |$| 15)) (QREFELT |$| 16)))
  (QREFELT |$| 18)))

(DEFUN |Vector| (G84134)
  (PROG ()
    (RETURN
      (PROG (G84135)
        (RETURN
          (COND
            ((LETT G84135
                   (|lassocShiftWithFunction|
                       (LIST (|devaluate| G84134))
                       (HGET |$ConstructorCache| '|Vector|)
                       '|domainEqualList|)
                   |Vector|)
             (|CDRwithIncrement| G84135))
            ('T
```

```
            (UNWIND-PROTECT
              (PROG1 (|Vector;| G84134) (LETT G84135 T |Vector|))
              (COND
                ((NOT G84135) (HREM |$ConstructorCache| '|Vector|)))))))))))

(DEFUN |Vector;| (|#1|)
  (PROG (DV$1 |dv$| $ G84133 |pv$|)
    (RETURN
      (PROGN
        (LETT DV$1 (|devaluate| |#1|) |Vector|)
        (LETT |dv$| (LIST '|Vector| DV$1) |Vector|)
        (LETT $ (make-array 36) |Vector|)
        (QSETREFV $ 0 |dv$|)
        (QSETREFV $ 3
            (LETT |pv$|
                  (|buildPredVector| 0 0
                      (LIST (|HasCategory| |#1| '(|SetCategory|))
                            (|HasCategory| |#1|
                                '(|ConvertibleTo| (|InputForm|)))
                            (LETT G84133
                                  (|HasCategory| |#1| '(|OrderedSet|))
                                  |Vector|)
                            (OR G84133
                                (|HasCategory| |#1| '(|SetCategory|)))
                            (|HasCategory| (|Integer|) '(|OrderedSet|))
                            (|HasCategory| |#1| '(|AbelianSemiGroup|))
                            (|HasCategory| |#1| '(|AbelianMonoid|))
                            (|HasCategory| |#1| '(|AbelianGroup|))
                            (|HasCategory| |#1| '(|Monoid|))
                            (|HasCategory| |#1| '(|Ring|))
                            (AND (|HasCategory| |#1|
                                     '(|RadicalCategory|))
                                 (|HasCategory| |#1| '(|Ring|)))
                            (AND (|HasCategory| |#1|
                                     (LIST '|Evalable|
                                      (|devaluate| |#1|)))
                                 (|HasCategory| |#1| '(|SetCategory|)))
                            (OR (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     G84133)
                                (AND (|HasCategory| |#1|
                                      (LIST '|Evalable|
                                       (|devaluate| |#1|)))
                                     (|HasCategory| |#1|
                                      '(|SetCategory|))))))
                  |Vector|))
        (|haddProp| |$ConstructorCache| '|Vector| (LIST DV$1)
            (CONS 1 $))
        (|stuffDomainSlots| $)
```

```
        (QSETREFV $ 6 |#1|)
        (COND
          ((|testBitVector| |pv$| 2)
           (QSETREFV $ 19
               (CONS (|dispatchFunction| |VECTOR;convert;$If;2|) $))))
        $))))

(setf (get
 (QUOTE |Vector|)
 (QUOTE |infovec|))
 (LIST
  (QUOTE #(NIL NIL NIL NIL NIL (|IndexedVector| 6 (NRTEVAL 1)) (|local| |#1|)
    (|List| 6) (0 . |construct|) |VECTOR;vector;L$;1| (|String|) (|Symbol|)
    (5 . |coerce|) (|InputForm|) (10 . |convert|) (15 . |parts|)
    (20 . |convert|) (|List| |$|) (25 . |convert|) (30 . |convert|)
    (|Mapping| 6 6 6) (|Boolean|) (|NonNegativeInteger|) (|List| 24)
    (|Equation| 6) (|Integer|) (|Mapping| 21 6) (|Mapping| 21 6 6)
    (|UniversalSegment| 25) (|Void|) (|Mapping| 6 6) (|Matrix| 6)
    (|OutputForm|) (|SingleInteger|) (|Union| 6 (QUOTE "failed"))
    (|List| 25)))
  (QUOTE #(|vector| 35 |parts| 40 |convert| 45 |construct| 50))
  (QUOTE ((|shallowlyMutable| . 0) (|finiteAggregate| . 0)))
  (CONS
   (|makeByteWordVec2| 13 (QUOTE (0 0 0 0 0 0 0 3 0 0 13 4 0 0 13 1 2 4)))
   (CONS
    (QUOTE #(|VectorCategory&| |OneDimensionalArrayAggregate&|
      |FiniteLinearAggregate&| |LinearAggregate&| |IndexedAggregate&|
      |Collection&| |HomogeneousAggregate&| |OrderedSet&| |Aggregate&|
      |EltableAggregate&| |Evalable&| |SetCategory&| NIL NIL
      |InnerEvalable&| NIL NIL |BasicType&|))
    (CONS
     (QUOTE #((|VectorCategory| 6) (|OneDimensionalArrayAggregate| 6)
      (|FiniteLinearAggregate| 6) (|LinearAggregate| 6)
      (|IndexedAggregate| 25 6) (|Collection| 6)
      (|HomogeneousAggregate| 6) (|OrderedSet|) (|Aggregate|)
      (|EltableAggregate| 25 6) (|Evalable| 6) (|SetCategory|)
      (|Type|) (|Eltable| 25 6) (|InnerEvalable| 6 6)
      (|CoercibleTo| 32) (|ConvertibleTo| 13) (|BasicType|)))
     (|makeByteWordVec2| 19
      (QUOTE (1 0 0 7 8 1 11 0 10 12 1 13 0 11 14 1 0 7 0 15 1 7 13 0 16 1 13
          0 17 18 1 0 13 0 19 1 0 0 7 9 1 0 7 0 15 1 2 13 0 19 1 0 0 7 8))))))
  (QUOTE |lookupIncomplete|)))
```

Chapter 29

Chunk collections

— algebra —

```
\getchunk{domain AFFPL AffinePlane}
\getchunk{domain AFFPLPS AffinePlaneOverPseudoAlgebraicClosureOfFiniteField}
\getchunk{domain AFFSP AffineSpace}
\getchunk{domain ALGSC AlgebraGivenByStructuralConstants}
\getchunk{domain ALGFF AlgebraicFunctionField}
\getchunk{domain AN AlgebraicNumber}
\getchunk{domain ANON AnonymousFunction}
\getchunk{domain ANTISYM AntiSymm}
\getchunk{domain ANY Any}
\getchunk{domain ASTACK ArrayStack}
\getchunk{domain ASP1 Asp1}
\getchunk{domain ASP10 Asp10}
\getchunk{domain ASP12 Asp12}
\getchunk{domain ASP19 Asp19}
\getchunk{domain ASP20 Asp20}
\getchunk{domain ASP24 Asp24}
\getchunk{domain ASP27 Asp27}
\getchunk{domain ASP28 Asp28}
\getchunk{domain ASP29 Asp29}
\getchunk{domain ASP30 Asp30}
\getchunk{domain ASP31 Asp31}
\getchunk{domain ASP33 Asp33}
\getchunk{domain ASP34 Asp34}
\getchunk{domain ASP35 Asp35}
\getchunk{domain ASP4 Asp4}
\getchunk{domain ASP41 Asp41}
\getchunk{domain ASP42 Asp42}
\getchunk{domain ASP49 Asp49}
\getchunk{domain ASP50 Asp50}
```

```
\getchunk{domain ASP55 Asp55}
\getchunk{domain ASP6 Asp6}
\getchunk{domain ASP7 Asp7}
\getchunk{domain ASP73 Asp73}
\getchunk{domain ASP74 Asp74}
\getchunk{domain ASP77 Asp77}
\getchunk{domain ASP78 Asp78}
\getchunk{domain ASP8 Asp8}
\getchunk{domain ASP80 Asp80}
\getchunk{domain ASP9 Asp9}
\getchunk{domain JORDAN AssociatedJordanAlgebra}
\getchunk{domain LIE AssociatedLieAlgebra}
\getchunk{domain ALIST AssociationList}
\getchunk{domain ATTRBUT AttributeButtons}
\getchunk{domain AUTOMOR Automorphism}

\getchunk{domain BBTREE BalancedBinaryTree}
\getchunk{domain BPADIC BalancedPAdicInteger}
\getchunk{domain BPADICRT BalancedPAdicRational}
\getchunk{domain BFUNCT BasicFunctions}
\getchunk{domain BOP BasicOperator}
\getchunk{domain BINARY BinaryExpansion}
\getchunk{domain BINFILE BinaryFile}
\getchunk{domain BSTREE BinarySearchTree}
\getchunk{domain BTOURN BinaryTournament}
\getchunk{domain BTREE BinaryTree}
\getchunk{domain BITS Bits}
\getchunk{domain BLHN BlowUpWithHamburgerNoether}
\getchunk{domain BLQT BlowUpWithQuadTrans}
\getchunk{domain BOOLEAN Boolean}

\getchunk{domain CARD CardinalNumber}
\getchunk{domain CARTEN CartesianTensor}
\getchunk{domain CHAR Character}
\getchunk{domain CCLASS CharacterClass}
\getchunk{domain CLIF CliffordAlgebra}
\getchunk{domain COLOR Color}
\getchunk{domain COMM Commutator}
\getchunk{domain COMPLEX Complex}
\getchunk{domain CDFMAT ComplexDoubleFloatMatrix}
\getchunk{domain CDFVEC ComplexDoubleFloatVector}
\getchunk{domain CONTFRAC ContinuedFraction}

\getchunk{domain DHMATRIX DenavitHartenbergMatrix}
\getchunk{domain DBASE Database}
\getchunk{domain DLIST DataList}
\getchunk{domain DECIMAL DecimalExpansion}
\getchunk{domain DEQUEUE Dequeue}
\getchunk{domain DERHAM DeRhamComplex}
\getchunk{domain DSMP DifferentialSparseMultivariatePolynomial}
```

```
\getchunk{domain DIRPROD DirectProduct}
\getchunk{domain DPMM DirectProductMatrixModule}
\getchunk{domain DPMO DirectProductModule}
\getchunk{domain DIRRING DirichletRing}
\getchunk{domain DMP DistributedMultivariatePolynomial}
\getchunk{domain DIV Divisor}
\getchunk{domain DFLOAT DoubleFloat}
\getchunk{domain DFMAT DoubleFloatMatrix}
\getchunk{domain DFVEC DoubleFloatVector}
\getchunk{domain DROPT DrawOption}
\getchunk{domain D01AJFA d01ajfAnnaType}
\getchunk{domain D01AKFA d01akfAnnaType}
\getchunk{domain D01ALFA d01alfAnnaType}
\getchunk{domain D01AMFA d01amfAnnaType}
\getchunk{domain D01ANFA d01anfAnnaType}
\getchunk{domain D01APFA d01apfAnnaType}
\getchunk{domain D01AQFA d01aqfAnnaType}
\getchunk{domain D01ASFA d01asfAnnaType}
\getchunk{domain D01FCFA d01fcfAnnaType}
\getchunk{domain D01GBFA d01gbfAnnaType}
\getchunk{domain D01TRNS d01TransformFunctionType}
\getchunk{domain D02BBFA d02bbfAnnaType}
\getchunk{domain D02BHFA d02bhfAnnaType}
\getchunk{domain D02CJFA d02cjfAnnaType}
\getchunk{domain D02EJFA d02ejfAnnaType}
\getchunk{domain D03EEFA d03eefAnnaType}
\getchunk{domain D03FAFA d03fafAnnaType}

\getchunk{domain EQTBL EqTable}
\getchunk{domain EQ Equation}
\getchunk{domain EXPEXPAN ExponentialExpansion}
\getchunk{domain EXPUPXS ExponentialOfUnivariatePuiseuxSeries}
\getchunk{domain EMR EuclideanModularRing}
\getchunk{domain EXIT Exit}
\getchunk{domain EXPR Expression}
\getchunk{domain EAB ExtAlgBasis}
\getchunk{domain E04DGFA e04dgfAnnaType}
\getchunk{domain E04FDFA e04fdfAnnaType}
\getchunk{domain E04GCFA e04gcfAnnaType}
\getchunk{domain E04JAFA e04jafAnnaType}
\getchunk{domain E04MBFA e04mbfAnnaType}
\getchunk{domain E04NAFA e04nafAnnaType}
\getchunk{domain E04UCFA e04ucfAnnaType}

\getchunk{domain FR Factored}
\getchunk{domain FILE File}
\getchunk{domain FNAME FileName}
\getchunk{domain FARRAY FlexibleArray}
\getchunk{domain FDIV FiniteDivisor}
\getchunk{domain FF FiniteField}
```

```
\getchunk{domain FFCG FiniteFieldCyclicGroup}
\getchunk{domain FFCGX FiniteFieldCyclicGroupExtension}
\getchunk{domain FFCGP FiniteFieldCyclicGroupExtensionByPolynomial}
\getchunk{domain FFX FiniteFieldExtension}
\getchunk{domain FFP FiniteFieldExtensionByPolynomial}
\getchunk{domain FFNB FiniteFieldNormalBasis}
\getchunk{domain FFNBX FiniteFieldNormalBasisExtension}
\getchunk{domain FFNBP FiniteFieldNormalBasisExtensionByPolynomial}
\getchunk{domain FLOAT Float}
\getchunk{domain FC FortranCode}
\getchunk{domain FEXPR FortranExpression}
\getchunk{domain FORTRAN FortranProgram}
\getchunk{domain FST FortranScalarType}
\getchunk{domain FTEM FortranTemplate}
\getchunk{domain FT FortranType}
\getchunk{domain FCOMP FourierComponent}
\getchunk{domain FSERIES FourierSeries}
\getchunk{domain FRAC Fraction}
\getchunk{domain FRIDEAL FractionalIdeal}
\getchunk{domain FRMOD FramedModule}
\getchunk{domain FAGROUP FreeAbelianGroup}
\getchunk{domain FAMONOID FreeAbelianMonoid}
\getchunk{domain FGROUP FreeGroup}
\getchunk{domain FM FreeModule}
\getchunk{domain FM1 FreeModule1}
\getchunk{domain FMONOID FreeMonoid}
\getchunk{domain FNLA FreeNilpotentLie}
\getchunk{domain FPARFRAC FullPartialFractionExpansion}
\getchunk{domain FUNCTION FunctionCalled}

\getchunk{domain GDMP GeneralDistributedMultivariatePolynomial}
\getchunk{domain GMODPOL GeneralModulePolynomial}
\getchunk{domain GCNAALG GenericNonAssociativeAlgebra}
\getchunk{domain GPOLSET GeneralPolynomialSet}
\getchunk{domain GSTBL GeneralSparseTable}
\getchunk{domain GTSET GeneralTriangularSet}
\getchunk{domain GSERIES GeneralUnivariatePowerSeries}
\getchunk{domain GRIMAGE GraphImage}
\getchunk{domain GOPT GuessOption}
\getchunk{domain GOPT0 GuessOptionFunctions0}

\getchunk{domain HASHTBL HashTable}
\getchunk{domain HEAP Heap}
\getchunk{domain HEXADEC HexadecimalExpansion}
\getchunk{domain HTMLFORM HTMLFormat}
\getchunk{domain HDP HomogeneousDirectProduct}
\getchunk{domain HDMP HomogeneousDistributedMultivariatePolynomial}
\getchunk{domain HELLFDIV HyperellipticFiniteDivisor}

\getchunk{domain ICP InfClsPt}
```

```
\getchunk{domain ICARD IndexCard}
\getchunk{domain IBITS IndexedBits}
\getchunk{domain IDPAG IndexedDirectProductAbelianGroup}
\getchunk{domain IDPAM IndexedDirectProductAbelianMonoid}
\getchunk{domain IDPO IndexedDirectProductObject}
\getchunk{domain IDPOAM IndexedDirectProductOrderedAbelianMonoid}
\getchunk{domain IDPOAMS IndexedDirectProductOrderedAbelianMonoidSup}
\getchunk{domain INDE IndexedExponents}
\getchunk{domain IFARRAY IndexedFlexibleArray}
\getchunk{domain ILIST IndexedList}
\getchunk{domain IMATRIX IndexedMatrix}
\getchunk{domain IARRAY1 IndexedOneDimensionalArray}
\getchunk{domain ISTRING IndexedString}
\getchunk{domain IARRAY2 IndexedTwoDimensionalArray}
\getchunk{domain IVECTOR IndexedVector}
\getchunk{domain ITUPLE InfiniteTuple}
\getchunk{domain INFCLSPT InfinitlyClosePoint}
\getchunk{domain INFCLSPS InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField}
\getchunk{domain IAN InnerAlgebraicNumber}
\getchunk{domain IFF InnerFiniteField}
\getchunk{domain IFAMON InnerFreeAbelianMonoid}
\getchunk{domain IIARRAY2 InnerIndexedTwoDimensionalArray}
\getchunk{domain IPADIC InnerPAdicInteger}
\getchunk{domain IPF InnerPrimeField}
\getchunk{domain ISUPS InnerSparseUnivariatePowerSeries}
\getchunk{domain INTABL InnerTable}
\getchunk{domain ITAYLOR InnerTaylorSeries}
\getchunk{domain INFORM InputForm}
\getchunk{domain INT Integer}
\getchunk{domain ZMOD IntegerMod}
\getchunk{domain INTFTBL IntegrationFunctionsTable}
\getchunk{domain IR IntegrationResult}
\getchunk{domain INTRVL Interval}

\getchunk{domain KERNEL Kernel}
\getchunk{domain KAFILE KeyedAccessFile}

\getchunk{domain LAUPOL LaurentPolynomial}
\getchunk{domain LIB Library}
\getchunk{domain LEXP LieExponentials}
\getchunk{domain LPOLY LiePolynomial}
\getchunk{domain LSQM LieSquareMatrix}
\getchunk{domain LODO LinearOrdinaryDifferentialOperator}
\getchunk{domain LODO1 LinearOrdinaryDifferentialOperator1}
\getchunk{domain LODO2 LinearOrdinaryDifferentialOperator2}
\getchunk{domain LIST List}
\getchunk{domain LMOPS ListMonoidOps}
\getchunk{domain LMDICT ListMultiDictionary}
\getchunk{domain LA LocalAlgebra}
\getchunk{domain LO Localize}
```

```
\getchunk{domain LWORD LyndonWord}

\getchunk{domain MCMPLX MachineComplex}
\getchunk{domain MFLOAT MachineFloat}
\getchunk{domain MINT MachineInteger}
\getchunk{domain MAGMA Magma}
\getchunk{domain MKCHSET MakeCachableSet}
\getchunk{domain MMLFORM MathMLFormat}
\getchunk{domain MATRIX Matrix}
\getchunk{domain MODMON ModMonic}
\getchunk{domain MODMONOM ModuleMonomial}
\getchunk{domain MODFIELD ModularField}
\getchunk{domain MODRING ModularRing}
\getchunk{domain MODOP ModuleOperator}
\getchunk{domain MOEBIUS MoebiusTransform}
\getchunk{domain MRING MonoidRing}
\getchunk{domain MSET Multiset}
\getchunk{domain MPOLY MultivariatePolynomial}
\getchunk{domain MYEXPR MyExpression}
\getchunk{domain MYUP MyUnivariatePolynomial}

\getchunk{domain NSDPS NeitherSparseOrDensePowerSeries}
\getchunk{domain NSMP NewSparseMultivariatePolynomial}
\getchunk{domain NSUP NewSparseUnivariatePolynomial}
\getchunk{domain NONE None}
\getchunk{domain NNI NonNegativeInteger}
\getchunk{domain NOTTING NottinghamGroup}
\getchunk{domain NIPROB NumericalIntegrationProblem}
\getchunk{domain ODEPROB NumericalODEProblem}
\getchunk{domain OPTPROB NumericalOptimizationProblem}
\getchunk{domain PDEPROB NumericalPDEProblem}

\getchunk{domain OCT Octonion}
\getchunk{domain ODEIFTBL ODEIntensityFunctionsTable}
\getchunk{domain ARRAY1 OneDimensionalArray}
\getchunk{domain ONECOMP OnePointCompletion}
\getchunk{domain OMCONN OpenMathConnection}
\getchunk{domain OMDEV OpenMathDevice}
\getchunk{domain OMENC OpenMathEncoding}
\getchunk{domain OMERR OpenMathError}
\getchunk{domain OMERRK OpenMathErrorKind}
\getchunk{domain OP Operator}
\getchunk{domain OMLO OppositeMonogenicLinearOperator}
\getchunk{domain ORDCOMP OrderedCompletion}
\getchunk{domain ODP OrderedDirectProduct}
\getchunk{domain OFMONOID OrderedFreeMonoid}
\getchunk{domain OVAR OrderedVariableList}
\getchunk{domain ODPOL OrderlyDifferentialPolynomial}
\getchunk{domain ODVAR OrderlyDifferentialVariable}
\getchunk{domain ODR OrdinaryDifferentialRing}
```

```
\getchunk{domain OWP OrdinaryWeightedPolynomials}
\getchunk{domain OSI OrdSetInts}
\getchunk{domain OUTFORM OutputForm}

\getchunk{domain PADIC PAdicInteger}
\getchunk{domain PADICRC PAdicRationalConstructor}
\getchunk{domain PADICRAT PAdicRational}
\getchunk{domain PALETTE Palette}
\getchunk{domain PARPCURV ParametricPlaneCurve}
\getchunk{domain PARSCURV ParametricSpaceCurve}
\getchunk{domain PARSURF ParametricSurface}
\getchunk{domain PFR PartialFraction}
\getchunk{domain PLACES Places}
\getchunk{domain PLACESPS PlacesOverPseudoAlgebraicClosureOfFiniteField}
\getchunk{domain PRTITION Partition}
\getchunk{domain PATTERN Pattern}
\getchunk{domain PATLRES PatternMatchListResult}
\getchunk{domain PATRES PatternMatchResult}
\getchunk{domain PENDTREE PendantTree}
\getchunk{domain PERM Permutation}
\getchunk{domain PERMGRP PermutationGroup}
\getchunk{domain HACKPI Pi}
\getchunk{domain ACPLOT PlaneAlgebraicCurvePlot}
\getchunk{domain PLCS Plcs}
\getchunk{domain PLOT Plot}
\getchunk{domain PLOT3D Plot3D}
\getchunk{domain PBWLB PoincareBirkhoffWittLyndonBasis}
\getchunk{domain POINT Point}
\getchunk{domain POLY Polynomial}
\getchunk{domain IDEAL PolynomialIdeals}
\getchunk{domain PR PolynomialRing}
\getchunk{domain PI PositiveInteger}
\getchunk{domain PF PrimeField}
\getchunk{domain PRIMARR PrimitiveArray}
\getchunk{domain PRODUCT Product}
\getchunk{domain PROJPL ProjectivePlane}
\getchunk{domain PROJSP ProjectiveSpace}
\getchunk{domain PACEXT PseudoAlgebraicClosureOfAlgExtOfRationalNumber}
\getchunk{domain PACOFF PseudoAlgebraicClosureOfFiniteField}
\getchunk{domain PACRAT PseudoAlgebraicClosureOfRationalNumber}

\getchunk{domain QFORM QuadraticForm}
\getchunk{domain QALGSET QuasiAlgebraicSet}
\getchunk{domain QUAT Quaternion}
\getchunk{domain QEQUAT QueryEquation}
\getchunk{domain QUEUE Queue}

\getchunk{domain RADFF RadicalFunctionField}
\getchunk{domain RADIX RadixExpansion}
\getchunk{domain RECLOS RealClosure}
```

```
\getchunk{domain RMATRIX RectangularMatrix}
\getchunk{domain REF Reference}
\getchunk{domain RGCHAIN RegularChain}
\getchunk{domain REGSET RegularTriangularSet}
\getchunk{domain RESRING ResidueRing}
\getchunk{domain RESULT Result}
\getchunk{domain RULE RewriteRule}
\getchunk{domain ROIRC RightOpenIntervalRootCharacterization}
\getchunk{domain ROMAN RomanNumeral}
\getchunk{domain ROUTINE RoutinesTable}
\getchunk{domain RULECOLD RuleCalled}
\getchunk{domain RULESET Ruleset}

\getchunk{domain FORMULA ScriptFormulaFormat}
\getchunk{domain SEG Segment}
\getchunk{domain SEGBIND SegmentBinding}
\getchunk{domain SET Set}
\getchunk{domain SEX SExpression}
\getchunk{domain SEXOF SExpressionOf}
\getchunk{domain SAE SimpleAlgebraicExtension}
\getchunk{domain SFORT SimpleFortranProgram}
\getchunk{domain SINT SingleInteger}
\getchunk{domain SAOS SingletonAsOrderedSet}
\getchunk{domain SDPOL SequentialDifferentialPolynomial}
\getchunk{domain SDVAR SequentialDifferentialVariable}
\getchunk{domain SETMN SetOfMIntegersInOneToN}
\getchunk{domain SMP SparseMultivariatePolynomial}
\getchunk{domain SMTS SparseMultivariateTaylorSeries}
\getchunk{domain STBL SparseTable}
\getchunk{domain SULS SparseUnivariateLaurentSeries}
\getchunk{domain SUP SparseUnivariatePolynomial}
\getchunk{domain SUPEXPR SparseUnivariatePolynomialExpressions}
\getchunk{domain SUPXS SparseUnivariatePuiseuxSeries}
\getchunk{domain ORESUP SparseUnivariateSkewPolynomial}
\getchunk{domain SUTS SparseUnivariateTaylorSeries}
\getchunk{domain SHDP SplitHomogeneousDirectProduct}
\getchunk{domain SPLNODE SplittingNode}
\getchunk{domain SPLTREE SplittingTree}
\getchunk{domain SREGSET SquareFreeRegularTriangularSet}
\getchunk{domain SQMATRIX SquareMatrix}
\getchunk{domain STACK Stack}
\getchunk{domain STREAM Stream}
\getchunk{domain STRING String}
\getchunk{domain STRTBL StringTable}
\getchunk{domain SUBSPACE SubSpace}
\getchunk{domain COMPPROP SubSpaceComponentProperty}
\getchunk{domain SUCH SuchThat}
\getchunk{domain SWITCH Switch}
\getchunk{domain SYMBOL Symbol}
\getchunk{domain SYMTAB SymbolTable}
```

```
\getchunk{domain SYMPOLY SymmetricPolynomial}

\getchunk{domain TABLE Table}
\getchunk{domain TABLEAU Tableau}
\getchunk{domain TS TaylorSeries}
\getchunk{domain TEX TexFormat}
\getchunk{domain TEXTFILE TextFile}
\getchunk{domain SYMS TheSymbolTable}
\getchunk{domain M3D ThreeDimensionalMatrix}
\getchunk{domain VIEW3D ThreeDimensionalViewport}
\getchunk{domain SPACE3 ThreeSpace}
\getchunk{domain TREE Tree}
\getchunk{domain TUBE TubePlot}
\getchunk{domain TUPLE Tuple}
\getchunk{domain ARRAY2 TwoDimensionalArray}
\getchunk{domain VIEW2D TwoDimensionalViewport}

\getchunk{domain UFPS UnivariateFormalPowerSeries}
\getchunk{domain ULS UnivariateLaurentSeries}
\getchunk{domain ULSCONS UnivariateLaurentSeriesConstructor}
\getchunk{domain UP UnivariatePolynomial}
\getchunk{domain UPXS UnivariatePuiseuxSeries}
\getchunk{domain UPXSCONS UnivariatePuiseuxSeriesConstructor}
\getchunk{domain UPXSSING UnivariatePuiseuxSeriesWithExponentialSingularity}
\getchunk{domain OREUP UnivariateSkewPolynomial}
\getchunk{domain UTS UnivariateTaylorSeries}
\getchunk{domain UTSZ UnivariateTaylorSeriesCZero}
\getchunk{domain UNISEG UniversalSegment}

\getchunk{domain VARIABLE Variable}
\getchunk{domain VECTOR Vector}
\getchunk{domain VOID Void}

\getchunk{domain WP WeightedPolynomials}
\getchunk{domain WUTSET WuWenTsunTriangularSet}

\getchunk{domain XDPOLY XDistributedPolynomial}
\getchunk{domain XPBWPOLY XPBWPolynomial}
\getchunk{domain XPOLY XPolynomial}
\getchunk{domain XPR XPolynomialRing}
\getchunk{domain XRPOLY XRecursivePolynomial}
```

Chapter 30

Index

Index

*
    NOTTING, 1711
**
    NOTTING, 1711
-?
    ALGFF, 28
    ALGSC, 15
    AN, 35
    ANTISYM, 40
    BINARY, 277
    BPADIC, 242
    BPADICRT, 247
    CARTEN, 342
    CDFMAT, 413
    CDFVEC, 419
    CLIF, 388
    COMPLEX, 406
    CONTFRAC, 432
    DECIMAL, 453
    DERHAM, 517
    DFLOAT, 575
    DFMAT, 587
    DFVEC, 593
    DHMATRIX, 479
    DIRPROD, 534
    DIRRING, 551
    DIV, 563
    DMP, 560
    DPMM, 540
    DPMO, 545
    DSMP, 529
    EMR, 672
    EQ, 661
    EXPEXPAN, 682
    EXPR, 694
    EXPUPXS, 710
    FAGROUP, 975
    FDIV, 783
    FEXPR, 917
    FF, 790
    FFCG, 795
    FFCGP, 805
    FFCGX, 800
    FFNB, 830
    FFNBP, 842
    FFNBX, 836
    FFP, 821
    FFX, 816
    FLOAT, 879
    FM, 983
    FM1, 987
    FNLA, 997
    FR, 756
    FRAC, 956
    FSERIES, 948
    GCNAALG, 1035
    GDMP, 1022
    GMODPOL, 1029
    GSERIES, 1061
    HACKPI, 1944
    HDMP, 1150
    HDP, 1143
    HELLFDIV, 1153
    HEXADEC, 1113
    IAN, 1245
    IDPAG, 1172
    IFF, 1252
    IMATRIX, 1208
    INT, 1330
    INTRVL, 1352
    IPADIC, 1262
    IPF, 1271
    IR, 1343
    ISUPS, 1279

ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
LA, 1488
LAUPOL, 1390
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OUTFORM, 1834
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRODUCT, 2079
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VECTOR, 2878
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336

/

NOTTING, 1711
=
NOTTING, 1711
?/ΓE30F?
BITS, 299
BOOLEAN, 307
?<?
ALIST, 221
AN, 35
ARRAY1, 1740
BINARY, 277
BITS, 299
BOOLEAN, 307
BOP, 258
BPADICRT, 247
BSD, 270
CARD, 318
CCLASS, 368
CDFVEC, 419
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EAB, 713
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FARRAY, 856
FCOMP, 945
FEXPR, 917
FLOAT, 879
FMONOID, 991
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IDPOAM, 1182
IDPOAMS, 1185
IFARRAY, 1192
ILIST, 1201
INDE, 1187
INT, 1330
INTRVL, 1352
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LA, 1488
LIST, 1472
LO, 1491
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MODMON, 1600
MODMONOM, 1612
MPOLY, 1650
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
ORDCOMP, 1777
OSI, 1830
OUTFORM, 1834
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PBWLB, 2020
PERM, 1916
PERMGRP, 1926

PI, 2066
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAOS, 2386
SDPOL, 2352
SDVAR, 2358
SET, 2338
SHDP, 2476
SINT, 2380
SMP, 2391
STRING, 2575
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UP, 2795
VECTOR, 2878
?<=?
ALIST, 221
AN, 35
ARRAY1, 1740
BINARY, 277
BITS, 299
BOOLEAN, 307
BOP, 258
BPADICRT, 247
BSD, 270
CARD, 318
CDFVEC, 419
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DIRPROD, 534
DIV, 563
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EAB, 713
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FARRAY, 856
FCOMP, 945
FEXPR, 917
FLOAT, 879
FMONOID, 991
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IDPOAM, 1182
IDPOAMS, 1185
IFARRAY, 1192
ILIST, 1201
INDE, 1187
INT, 1330
INTRVL, 1352
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LA, 1488
LIST, 1472
LO, 1491
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MODMON, 1600
MODMONOM, 1612
MPOLY, 1650

MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
ORDCOMP, 1777
OSI, 1830
OUTFORM, 1834
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PBWLB, 2020
PERM, 1916
PERMGRP, 1926
PI, 2066
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAOS, 2386
SDPOL, 2352
SDVAR, 2358
SHDP, 2476
SINT, 2380
SMP, 2391
STRING, 2575
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UP, 2795
VECTOR, 2878

?=?
BSD, 270
?>?
ALIST, 221
AN, 35
ARRAY1, 1740
BINARY, 277
BITS, 299
BOOLEAN, 307
BOP, 258
BPADICRT, 247
BSD, 270
CARD, 318
CDFVEC, 419
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EAB, 713
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FARRAY, 856
FCOMP, 945
FEXPR, 917
FLOAT, 879
FMONOID, 991
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IDPOAM, 1182
IDPOAMS, 1185

IFARRAY, 1192
ILIST, 1201
INDE, 1187
INT, 1330
INTRVL, 1352
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LA, 1488
LIST, 1472
LO, 1491
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MODMON, 1600
MODMONOM, 1612
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
ORDCOMP, 1777
OSI, 1830
OUTFORM, 1834
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PBWLB, 2020
PERM, 1916
PI, 2066
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAOS, 2386
SDPOL, 2352
SDVAR, 2358
SHDP, 2476
SINT, 2380
SMP, 2391
STRING, 2575
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UP, 2795
VECTOR, 2878
?>=?
ALIST, 221
AN, 35
ARRAY1, 1740
BINARY, 277
BITS, 299
BOOLEAN, 307
BOP, 258
BPADICRT, 247
BSD, 270
CARD, 318
CDFVEC, 419
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EAB, 713
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710

FAGROUP, 975
FARRAY, 856
FCOMP, 945
FEXPR, 917
FLOAT, 879
FMONOID, 991
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IDPOAM, 1182
IDPOAMS, 1185
IFARRAY, 1192
ILIST, 1201
INDE, 1187
INT, 1330
INTRVL, 1352
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LA, 1488
LIST, 1472
LO, 1491
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MODMON, 1600
MODMONOM, 1612
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
ORDCOMP, 1777
OSI, 1830
OUTFORM, 1834
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PBWLB, 2020
PERM, 1916
PI, 2066
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAOS, 2386
SDPOL, 2352
SDVAR, 2358
SHDP, 2476
SINT, 2380
SMP, 2391
STRING, 2575
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UP, 2795
VECTOR, 2878
?ΓE30F/?
IBITS, 1169
SINT, 2380
?ΓE30F/?
BITS, 299
BOOLEAN, 307
? =?
DIRRING, 551
?**?
ALGFF, 28

ALGSC, 15
AN, 35
ANTISYM, 40
AUTOMOR, 231
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CDFMAT, 413
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FMONOID, 991
FNLA, 997
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IDEAL, 2047
IFF, 1252
IMATRIX, 1208
INFORM, 1311
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
JORDAN, 209
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIE, 214
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731

ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OUTFORM, 1834
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
POLY, 2044
PR, 2058
PRODUCT, 2079
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
?*?
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
AUTOMOR, 231
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CARTEN, 342
CDFMAT, 413
CDFVEC, 419
CLIF, 388
COLOR, 394
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672

EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNLA, 997
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFF, 1252
IMATRIX, 1208
INDE, 1187
INFORM, 1311
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
MAGMA, 1533
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744

ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OUTFORM, 1834
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRODUCT, 2079
PRTITION, 1889
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VECTOR, 2878
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
?+?
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CARTEN, 342
CDFMAT, 413
CDFVEC, 419
CLIF, 388
COLOR, 394
COMPLEX, 406
CONTFRAC, 432
DBASE, 442
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DMP, 560
DPMO, 545
DSMP, 529
EMR, 672

EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FM, 983
FM1, 987
FNLA, 997
FPARFRAC, 1010
FR, 756
FRAC, 956
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFF, 1252
IMATRIX, 1208
INDE, 1187
INFORM, 1311
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
LA, 1488
LAUPOL, 1390
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OUTFORM, 1834
OWP, 1828
PACOFF, 2102
PACRAT, 2112

PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRODUCT, 2079
PRTITION, 1889
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VECTOR, 2878
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
?-?
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CARTEN, 342
CDFMAT, 413
CDFVEC, 419
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DBASE, 442
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FDIV, 783
FEXPR, 917
FF, 790

FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FM, 983
FM1, 987
FNLA, 997
FR, 756
FRAC, 956
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IDPAG, 1172
IFF, 1252
IMATRIX, 1208
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
LA, 1488
LAUPOL, 1390
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OUTFORM, 1834
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRODUCT, 2079
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212

ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VECTOR, 2878
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
?..?
OUTFORM, 1834
SEG, 2325
UNISEG, 2863
?.?
AFFPLPS, 7
AFFSP, 9
ALGSC, 15
ALIST, 221
ARRAY1, 1740
AUTOMOR, 231
BINARY, 277
BITS, 299
BPADICRT, 247
CARTEN, 342
CDFVEC, 419
COMPLEX, 406
DBASE, 442
DECIMAL, 453
DFVEC, 593
DIRPROD, 534
DIRRING, 551
DLIST, 448
DPMM, 540
DPMO, 545
EMR, 672
EQTBL, 669
EXPEXPAN, 682
EXPUPXS, 710
FARRAY, 856
FR, 756
FRAC, 956
GCNAALG, 1035
GSERIES, 1061
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
HEXADEC, 1113
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IFARRAY, 1192
ILIST, 1201
INFORM, 1311
INTABL, 1304
ISTRING, 1218
ISUPS, 1279
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
LIB, 1397
LIE, 214
LIST, 1472
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MODMON, 1600

MODOP, 1615, 1771
MYUP, 1663
NSDPS, 1670
NSUP, 1696
OCT, 1731
ODP, 1783
OUTFORM, 1834
PADICRAT, 1852
PADICRC, 1857
PERM, 1916
PERMGRP, 1926
PLACES, 1985
PLACESPS, 1987
POINT, 2026
PRIMARR, 2075
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
QFORM, 2120
QUAT, 2133
RADIX, 2172
RESULT, 2267
ROUTINE, 2298
RULE, 2271
RULESET, 2309
SEX, 2360
SEXOF, 2363
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMBOL, 2608
TABLE, 2632
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
VECTOR, 2878
?.count
DLIST, 448
?.first
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
?.last
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
?.left
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
PENDTREE, 1911
?.rest
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
?.right
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
PENDTREE, 1911
?.sort
DLIST, 448
?.unique
DLIST, 448
?.value
ALIST, 221
BBTREE, 237
BSTREE, 287

BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
?/ΓE30F?
IBITS, 1169
SINT, 2380
?/?
ALGFF, 28
AN, 35
AUTOMOR, 231
BINARY, 277
BPADICRT, 247
CDFMAT, 413
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DFMAT, 587
DHMATRIX, 479
DIRPROD, 534
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FRAC, 956
FRIDEAL, 965
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
IMATRIX, 1208
INFORM, 1311
IPF, 1271
ISUPS, 1279
LA, 1488
LEXP, 1403
LO, 1491
LPOLY, 1415
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MODFIELD, 1606
MODMON, 1600
MOEBIUS, 1622
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODP, 1783
ODPOL, 1818
ODR, 1825
OUTFORM, 1834
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PERM, 1916
PF, 2071
PFR, 1880
POLY, 2044

PR, 2058
PRODUCT, 2079
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RMATRIX, 2212
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SMP, 2391
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTSZ, 2854
WP, 2885
?=?
AFFPLPS, 7
AFFSP, 9
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ANON, 38
ANTISYM, 40
ANY, 50
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
ATTRBUT, 224
AUTOMOR, 231
BBTREE, 237
BFUNCT, 249
BINARY, 277
BINFILE, 280
BITS, 299
BLHN, 301
BLQT, 304
BOOLEAN, 307
BOP, 258
BPADIC, 242
BPADICRT, 247
BSTREE, 287
BTOURN, 291
BTREE, 295
CARD, 318
CARTEN, 342
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
CHAR, 359
CLIF, 388
COLOR, 394
COMM, 397
COMPLEX, 406
COMPPROP, 2592
CONTFRAC, 432
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617, 620
D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
D10ANFA, 614
DBASE, 442
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593

DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DROPT, 596
DSMP, 529
DSTREE, 522
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732
E04NAFA, 735
E04UCFA, 739
EAB, 713
EMR, 672
EQ, 661
EQTBL, 669
EXIT, 677
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FARRAY, 856
FC, 902
FCOMP, 945
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FILE, 772
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNAME, 780
FNLA, 997
FORMULA, 2312
FPARFRAC, 1010
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
FST, 933
FT, 941
FTEM, 938
FUNCTION, 1015
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GOPT, 1075
GOPT0, 1081
GPOLSET, 1044
GRIMAGE, 1065
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HELLFDIV, 1153
HEXADEC, 1113
HTMLFORM, 1122
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IC, 1161
ICARD, 1163
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255

IFARRAY, 1192
IFF, 1252
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INFCLSPS, 1240
INFCLSPT, 1234
INFORM, 1311
INT, 1330
INTABL, 1304
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
KERNEL, 1372
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LMOPS, 1477
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
M3D, 2672
MAGMA, 1533
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MMLFORM, 1571
MODFIELD, 1606
MODMON, 1600
MODMONOM, 1612
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NIPROB, 1713
NNI, 1706
NONE, 1704
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODEPROB, 1716
ODP, 1783
ODPOL, 1818
ODR, 1825
ODVAR, 1821
OFMONOID, 1795
OMENC, 1755
OMERR, 1758
OMERRK, 1761
OMLO, 1773
ONECOMP, 1744
OPTPROB, 1719
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OSI, 1830
OUTFORM, 1834
OVAR, 1803
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PALETTE, 1862
PATLRES, 1904
PATRES, 1906
PATTERN, 1894
PBWLB, 2020

PDEPROB, 1722
PENDTREE, 1911
PERM, 1916
PERMGRP, 1926
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
PRODUCT, 2079
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
PRTITION, 1889
QALGSET, 2123
QFORM, 2120
QUAT, 2133
QUEUE, 2150
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REF, 2215
REGSET, 2252
RESRING, 2262
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROIRC, 2276
ROMAN, 2293
ROUTINE, 2298
RULE, 2271
RULECOLD, 2307
RULESET, 2309
SAE, 2368
SAOS, 2386
SD, 2540
SDPOL, 2352
SDVAR, 2358
SEG, 2325
SEGBIND, 2330
SET, 2338
SETMN, 2344
SEX, 2360
SEXOF, 2363
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SPACE3, 2701
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUBSPACE, 2582
SUCH, 2595
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMBOL, 2608
SYMPOLY, 2622
TABLE, 2632
TEX, 2645
TEXTFILE, 2661
TREE, 2710
TS, 2639
TUPLE, 2721
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VARIABLE, 2872
VECTOR, 2878
VIEW2d, 2739
VIEW3D, 2679

WP, 2885
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
?SEGMENT
OUTFORM, 1834
UNISEG, 2863
?^=?
OUTFORM, 1834
?^?
ALGFF, 28
AN, 35
ANTISYM, 40
AUTOMOR, 231
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FMONOID, 991
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LA, 1488
LAUPOL, 1390
LEXP, 1403
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670

NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
POLY, 2044
PR, 2058
PRODUCT, 2079
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
? =?
FC, 902
HTMLFORM, 1122
OMERR, 1758
SUBSPACE, 2582
?~=?
AFFPLPS, 7
AFFSP, 9
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ANON, 38
ANTISYM, 40
ANY, 50
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
ATTRBUT, 224
AUTOMOR, 231
BBTREE, 237
BFUNCT, 249
BINARY, 277
BINFILE, 280
BITS, 299
BLHN, 301
BLQT, 304
BOOLEAN, 307
BOP, 258
BPADIC, 242

BPADICRT, 247
BSD, 270
BSTREE, 287
BTOURN, 291
BTREE, 295
CARD, 318
CARTEN, 342
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
CHAR, 359
CLIF, 388
COLOR, 394
COMM, 397
COMPLEX, 406
COMPPROP, 2592
CONTFRAC, 432
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617, 620
D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
D10ANFA, 614
DBASE, 442
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIV, 563
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DROPT, 596
DSMP, 529
DSTREE, 522
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732
E04NAFA, 735
E04UCFA, 739
EAB, 713
EMR, 672
EQ, 661
EQTBL, 669
EXIT, 677
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FARRAY, 856
FCOMP, 945
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FILE, 772
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNAME, 780
FNLA, 997
FORMULA, 2312
FPARFRAC, 1010
FR, 756
FRAC, 956

FRIDEAL, 965
FRMOD, 970
FSERIES, 948
FT, 941
FTEM, 938
FUNCTION, 1015
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GOPT, 1075
GOPT0, 1081
GPOLSET, 1044
GRIMAGE, 1065
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IC, 1161
ICARD, 1163
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFARRAY, 1192
IFF, 1252
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INFCLSPS, 1240
INFCLSPT, 1234
INFORM, 1311
INT, 1330
INTABL, 1304
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
KERNEL, 1372
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LMOPS, 1477
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
M3D, 2672
MAGMA, 1533
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MMLFORM, 1571
MODFIELD, 1606
MODMON, 1600
MODMONOM, 1612
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663

NIPROB, 1713
NNI, 1706
NONE, 1704
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODEPROB, 1716
ODP, 1783
ODPOL, 1818
ODR, 1825
ODVAR, 1821
OFMONOID, 1795
OMENC, 1755
OMERRK, 1761
OMLO, 1773
ONECOMP, 1744
OPTPROB, 1719
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OSI, 1830
OUTFORM, 1834
OVAR, 1803
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PALETTE, 1862
PATLRES, 1904
PATRES, 1906
PATTERN, 1894
PBWLB, 2020
PDEPROB, 1722
PENDTREE, 1911
PERM, 1916
PERMGRP, 1926
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
PRODUCT, 2079
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
PRTITION, 1889
QALGSET, 2123
QFORM, 2120
QUAT, 2133
QUEUE, 2150
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REF, 2215
REGSET, 2252
RESRING, 2262
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROIRC, 2276
ROMAN, 2293
ROUTINE, 2298
RULE, 2271
RULECOLD, 2307
RULESET, 2309
SAE, 2368
SAOS, 2386
SD, 2540
SDPOL, 2352
SDVAR, 2358
SEG, 2325
SEGBIND, 2330
SET, 2338
SETMN, 2344
SEX, 2360
SEXOF, 2363
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SPACE3, 2701
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502

STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUCH, 2595
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMBOL, 2608
SYMPOLY, 2622
TABLE, 2632
TEX, 2645
TEXTFILE, 2661
TREE, 2710
TS, 2639
TUPLE, 2721
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VARIABLE, 2872
VECTOR, 2878
VIEW2d, 2739
VIEW3D, 2679
WP, 2885
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
?and?
BITS, 299
BOOLEAN, 307
IBITS, 1169
OUTFORM, 1834
?div?
OFMONOID, 1795
OUTFORM, 1834
?or?
BITS, 299
BOOLEAN, 307
IBITS, 1169
OUTFORM, 1834
?quo?
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525

MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSUP, 1696
ODR, 1825
OUTFORM, 1834
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
?rem?
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSUP, 1696
ODR, 1825
OUTFORM, 1834
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435

SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
#?
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
STREAM, 2550
#?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INFORM, 1311
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SEX, 2360
SEXOF, 2363
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
XPR, 2945
^
NOTTING, 1711
^=
NOTTING, 1711
^?
BITS, 299

BOOLEAN, 307
IBITS, 1169

?
SINT, 2380

~?
BITS, 299
BOOLEAN, 307
IBITS, 1169

0
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CARTEN, 342
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DIV, 563
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FM, 983
FM1, 987
FNLA, 997
FR, 756
FRAC, 956
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IDPAG, 1172
IDPAM, 1176
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFF, 1252
INDE, 1187
INFORM, 1311
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISUPS, 1279
ITAYLOR, 1306
JORDAN, 209
LA, 1488
LAUPOL, 1390
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424

MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
PRODUCT, 2079
PRTITION, 1889
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336

1

ALGFF, 28
AN, 35
ANTISYM, 40
AUTOMOR, 231
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CARTEN, 342
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575

DIRPROD, 534
DIRRING, 551
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FMONOID, 991
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
INFORM, 1311
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LA, 1488
LAUPOL, 1390
LEXP, 1403
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NOTTING, 1711
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PBWLB, 2020
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
POLY, 2044
PR, 2058

PRODUCT, 2079
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336

any?
IFARRAY, 1192

abs
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DIRPROD, 534
DPMM, 540
DPMO, 545
EXPEXPAN, 682
EXPR, 694
FEXPR, 917
FLOAT, 879
FRAC, 956
HDP, 1143
HEXADEC, 1113
INT, 1330
LA, 1488
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
OCT, 1731
ODP, 1783
ONECOMP, 1744
ORDCOMP, 1777
PADICRAT, 1852
PADICRC, 1857
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SHDP, 2476
SINT, 2380
SULS, 2425
ULS, 2763
ULSCONS, 2771

absolutelyIrreducible?
ALGFF, 28
RADFF, 2160

acos
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425

SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
acosh
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
acot
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
acoth
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
ACPLOT, 1958
coerce, 1958
listBranches, 1958
makeSketch, 1958
refine, 1958
xRange, 1958
yRange, 1958
acsc
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352

MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
acsch
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
actualExtensionV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
adaptive
DROPT, 596
adaptive3D?
PLOT3D, 2008
adaptive?
PLOT, 1995
addBadValue
PATTERN, 1894
additive?
DIRRING, 551
addMatch
PATRES, 1906
addMatchRestricted
PATRES, 1906
addmod
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
addPoint
SUBSPACE, 2582
addPoint2
SUBSPACE, 2582
addPointLast
SUBSPACE, 2582
adjoint
LODO, 1437
LODO1, 1447
LODO2, 1459
MODOP, 1615, 1771
AffinePlane, 4
AffinePlaneOverPseudoAlgebraicClosureOfFiniteField, 7
affinePoint
AFFPLPS, 7
AFFSP, 9
AffineSpace, 9
AFFPL, 4
AFFPLPS, 7
?.?, 7
?=?, 7
?~=?, 7
affinePoint, 7
coerce, 7
conjugate, 7
definingField, 7
degree, 7
hash, 7
latex, 7
list, 7
orbit, 7
origin, 7

pointValue, 7
rational?, 7
removeConjugate, 7
setelt, 7
AFFSP, 9
?.?, 9
?=?, 9
?~=?, 9
affinePoint, 9
coerce, 9
conjugate, 9
definingField, 9
degree, 9
hash, 9
latex, 9
list, 9
orbit, 9
origin, 9
pointValue, 9
rational?, 9
removeConjugate, 9
setelt, 9
airyAi
DFLOAT, 575
EXPR, 694
airyBi
DFLOAT, 575
EXPR, 694
Aleph
CARD, 318
AlgebraGivenByStructuralConstants, 14
algebraic?
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
GTSET, 1054
IFF, 1252
IPF, 1271
PACOFF, 2102
PACRAT, 2112
PF, 2071
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
algebraicCoefficients?
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
AlgebraicFunctionField, 27
AlgebraicNumber, 35
algebraicOf
RECLOS, 2203
algebraicVariables
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
ALGFF, 27
-?, 28
?**?, 28
?*?, 28
?+?, 28
?-?, 28
?/?, 28
?=?, 28
?^?, 28
?~=?, 28
?quo?, 28
?rem?, 28
0, 28
1, 28
absolutelyIrreducible?, 28
algSplitSimple, 28
associates?, 28
basis, 28
branchPoint?, 28
branchPointAtInfinity?, 28
characteristic, 28
characteristicPolynomial, 28
charthRoot, 28
coerce, 28
complementaryBasis, 28
conditionP, 28
convert, 28

coordinates, 28
createPrimitiveElement, 28
D, 28
definingPolynomial, 28
derivationCoordinates, 28
differentiate, 28
discreteLog, 28
discriminant, 28
divide, 28
elliptic, 28
elt, 28
euclideanSize, 28
expressIdealMember, 28
exquo, 28
extendedEuclidean, 28
factor, 28
factorsOfCyclicGroupSize, 28
gcd, 28
gcdPolynomial, 28
generator, 28
genus, 28
hash, 28
hyperelliptic, 28
index, 28
init, 28
integral?, 28
integralAtInfinity?, 28
integralBasis, 28
integralBasisAtInfinity, 28
integralCoordinates, 28
integralDerivationMatrix, 28
integralMatrix, 28
integralMatrixAtInfinity, 28
integralRepresents, 28
inv, 28
inverseIntegralMatrix, 28
inverseIntegralMatrixAtInfinity, 28
knownInfBasis, 28
latex, 28
lcm, 28
lift, 28
lookup, 28
minimalPolynomial, 28
multiEuclidean, 28
nextItem, 28
nonSingularModel, 28
norm, 28
normalizeAtInfinity, 28
numberOfComponents, 28
one?, 28
order, 28
prime?, 28
primeFrobenius, 28
primitive?, 28
primitiveElement, 28
primitivePart, 28
principalIdeal, 28
ramified?, 28
ramifiedAtInfinity?, 28
random, 28
rank, 28
rationalPoint?, 28
rationalPoints, 28
recip, 28
reduce, 28
reduceBasisAtInfinity, 28
reducedSystem, 28
regularRepresentation, 28
representationType, 28
represents, 28
retract, 28
retractIfCan, 28
sample, 28
singular?, 28
singularAtInfinity?, 28
size, 28
sizeLess?, 28
squareFree, 28
squareFreePart, 28
subtractIfCan, 28
tableForDiscreteLogarithm, 28
trace, 28
traceMatrix, 28
unit?, 28
unitCanonical, 28
unitNormal, 28
yCoordinates, 28
zero?, 28
ALGSC, 14
-?, 15
?**?, 15
?*?, 15

?+?, 15
?-?, 15
?.?, 15
?=?, 15
?~=?, 15
0, 15
alternative?, 15
antiAssociative?, 15
antiCommutative?, 15
antiCommutator, 15
apply, 15
associative?, 15
associator, 15
associatorDependence, 15
basis, 15
coerce, 15
commutative?, 15
commutator, 15
conditionsForIdempotents, 15
convert, 15
coordinates, 15
flexible?, 15
hash, 15
jacobiIdentity?, 15
jordanAdmissible?, 15
jordanAlgebra?, 15
latex, 15
leftAlternative?, 15
leftCharacteristicPolynomial, 15
leftDiscriminant, 15
leftMinimalPolynomial, 15
leftNorm, 15
leftPower, 15
leftRankPolynomial, 15
leftRecip, 15
leftRegularRepresentation, 15
leftTrace, 15
leftTraceMatrix, 15
leftUnit, 15
leftUnits, 15
lieAdmissible?, 15
lieAlgebra?, 15
noncommutativeJordanAlgebra?, 15
plenaryPower, 15
powerAssociative?, 15
rank, 15
recip, 15
represents, 15
rightAlternative?, 15
rightCharacteristicPolynomial, 15
rightDiscriminant, 15
rightMinimalPolynomial, 15
rightNorm, 15
rightPower, 15
rightRankPolynomial, 15
rightRecip, 15
rightRegularRepresentation, 15
rightTrace, 15
rightTraceMatrix, 15
rightUnit, 15
rightUnits, 15
sample, 15
someBasis, 15
structuralConstants, 15
subtractIfCan, 15
unit, 15
zero?, 15
algSplitSimple
ALGFF, 28
RADFF, 2160
ALIST, 220
?<?, 221
?<=?, 221
?>?, 221
?>=?, 221
?.?, 221
?.first, 221
?.last, 221
?.rest, 221
?.value, 221
?=?, 221
?~=?, 221
#?, 221
any?, 221
assoc, 221
bag, 221
child?, 221
children, 221
coerce, 221
concat, 221
construct, 221
convert, 221

copy, 221
copyInto, 221
count, 221
cycleEntry, 221
cycleLength, 221
cycleSplit, 221
cycleTail, 221
cyclic?, 221
delete, 221
dictionary, 221
distance, 221
elt, 221
empty, 221
empty?, 221
entries, 221
entry?, 221
eq?, 221
eval, 221
every?, 221
explicitlyFinite?, 221
extract, 221
fill, 221
find, 221
first, 221
hash, 221
index?, 221
indices, 221
insert, 221
inspect, 221
key?, 221
keys, 221
last, 221
latex, 221
leaf?, 221
leaves, 221
less?, 221
list, 221
map, 221
max, 221
maxIndex, 221
member?, 221
members, 221
merge, 221
min, 221
minIndex, 221
more?, 221
new, 221
node?, 221
nodes, 221
parts, 221
position, 221
possiblyInfinite?, 221
qelt, 221
qsetelt, 221
reduce, 221
remove, 221
removeDuplicates, 221
rest, 221
reverse, 221
sample, 221
search, 221
second, 221
select, 221
setchildren, 221
setelt, 221
setfirst, 221
setlast, 221
setrest, 221
setvalue, 221
size?, 221
sort, 221
sorted?, 221
split, 221
swap, 221
table, 221
tail, 221
third, 221
value, 221
allDegrees
GOPT, 1075
GOPT0, 1081
allRootsOf
RECLOS, 2203
ROIRC, 2276
alphabetic
CCLASS, 368
alphabetic?
CHAR, 359
alphanumeric
CCLASS, 368
alphanumeric?
CHAR, 359

alternative?
    ALGSC, 15
    GCNAALG, 1035
    JORDAN, 209
    LIE, 214
    LSQM, 1424
AN, 35
    -?, 35
    ?<?, 35
    ?<=?, 35
    ?>?, 35
    ?>=?, 35
    ?**?, 35
    ?*?, 35
    ?+?, 35
    ?-?, 35
    ?/?, 35
    ?=?, 35
    ?^?, 35
    ?~=?, 35
    ?quo?, 35
    ?rem?, 35
    0, 35
    1, 35
    associates?, 35
    belong?, 35
    box, 35
    characteristic, 35
    coerce, 35
    convert, 35
    D, 35
    definingPolynomial, 35
    denom, 35
    differentiate, 35
    distribute, 35
    divide, 35
    elt, 35
    euclideanSize, 35
    eval, 35
    even?, 35
    expressIdealMember, 35
    exquo, 35
    extendedEuclidean, 35
    factor, 35
    freeOf?, 35
    gcd, 35
    gcdPolynomial, 35
    hash, 35
    height, 35
    inv, 35
    is?, 35
    kernel, 35
    kernels, 35
    latex, 35
    lcm, 35
    mainKernel, 35
    map, 35
    max, 35
    min, 35
    minPoly, 35
    multiEuclidean, 35
    norm, 35
    nthRoot, 35
    numer, 35
    odd?, 35
    one?, 35
    operator, 35
    operators, 35
    paren, 35
    prime?, 35
    principalIdeal, 35
    recip, 35
    reduce, 35
    reducedSystem, 35
    retract, 35
    retractIfCan, 35
    rootOf, 35
    rootsOf, 35
    sample, 35
    sizeLess?, 35
    sqrt, 35
    squareFree, 35
    squareFreePart, 35
    subst, 35
    subtractIfCan, 35
    tower, 35
    unit?, 35
    unitCanonical, 35
    unitNormal, 35
    zero?, 35
    zeroOf, 35
    zerosOf, 35

An
MODMON, 1600
AND
SWITCH, 2597
And
IBITS, 1169
SINT, 2380
ANON, 38
?=?, 38
?~=?, 38
coerce, 38
hash, 38
latex, 38
AnonymousFunction, 38
antiAssociative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
antiCommutative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
antiCommutator
ALGSC, 15
FNLA, 997
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
ANTISYM, 40
-?, 40
?**?, 40
?*?, 40
?+?, 40
?-?, 40
?=?, 40
?^?, 40
?~=?, 40
0, 40
1, 40
characteristic, 40
coefficient, 40
coerce, 40
degree, 40
exp, 40
generator, 40
hash, 40
homogeneous?, 40
latex, 40
leadingBasisTerm, 40
leadingCoefficient, 40
map, 40
one?, 40
recip, 40
reductum, 40
retract, 40
retractable?, 40
retractIfCan, 40
sample, 40
subtractIfCan, 40
zero?, 40
AntiSymm, 40
antisymmetric?
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
ANY, 50
?=?, 50
?~=?, 50
any, 50
coerce, 50
dom, 50
domainOf, 50
hash, 50
latex, 50
obj, 50
objectOf, 50
showTypeInOutput, 50
Any, 50
any
ANY, 50
any?
ALIST, 221
ARRAY1, 1740

ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895

append
LIST, 1472

appendPoint
GRIMAGE, 1065

apply
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
ORESUP, 2460
OREUP, 2840

applyQuote
EXPR, 694
MYEXPR, 1656

approximants
CONTFRAC, 432

approximate
BPADIC, 242

BPADICRT, 247
EXPUPXS, 710
GSERIES, 1061
IPADIC, 1262
ISUPS, 1279
NSDPS, 1670
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
RECLOS, 2203
ROIRC, 2276
SULS, 2425
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
argscript
SYMBOL, 2608
argument
COMPLEX, 406
FCOMP, 945
KERNEL, 1372
MCMPLX, 1511
argumentListOf
SYMS, 2665
arity
BOP, 258
ARRAY1, 1740
?<?, 1740
?<=?, 1740
?>?, 1740
?>=?, 1740
?.?, 1740
?=?, 1740
?~=?, 1740
#?, 1740
any?, 1740
coerce, 1740
concat, 1740
construct, 1740
convert, 1740
copy, 1740
copyInto, 1740
count, 1740
delete, 1740
elt, 1740
empty, 1740
empty?, 1740
entries, 1740
entry?, 1740
eq?, 1740
eval, 1740
every?, 1740
fill, 1740
find, 1740
first, 1740
hash, 1740
index?, 1740
indices, 1740
insert, 1740
latex, 1740
less?, 1740
map, 1740
max, 1740
maxIndex, 1740
member?, 1740
members, 1740
merge, 1740
min, 1740
minIndex, 1740
more?, 1740
new, 1740
oneDimensionalArray, 1740
parts, 1740
position, 1740
qelt, 1740
qsetelt, 1740
reduce, 1740
remove, 1740
removeDuplicates, 1740
reverse, 1740
sample, 1740
select, 1740
setelt, 1740
size?, 1740
sort, 1740
sorted?, 1740

swap, 1740
ARRAY2, 2732
?=?, 2732
?~=?, 2732
#?, 2732
any?, 2732
coerce, 2732
column, 2732
copy, 2732
count, 2732
elt, 2732
empty, 2732
empty?, 2732
eq?, 2732
eval, 2732
every?, 2732
fill, 2732
hash, 2732
latex, 2732
less?, 2732
map, 2732
maxColIndex, 2732
maxRowIndex, 2732
member?, 2732
members, 2732
minColIndex, 2732
minRowIndex, 2732
more?, 2732
ncols, 2732
new, 2732
nrows, 2732
parts, 2732
qelt, 2732
qsetelt, 2732
row, 2732
sample, 2732
setColumn, 2732
setelt, 2732
setRow, 2732
size?, 2732
ArrayStack, 65
arrayStack
ASTACK, 65
asec
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
asech
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
asin
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710

FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
asinh
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
ASP1, 71
coerce, 71
outputAsFortran, 71
retract, 71
retractIfCan, 71
Asp1, 71
ASP10, 75
coerce, 75
outputAsFortran, 75
retract, 75
retractIfCan, 75
Asp10, 75
ASP12, 79
coerce, 79
outputAsFortran, 79
Asp12, 79
ASP19, 82
coerce, 82
outputAsFortran, 82
retract, 82
retractIfCan, 82
Asp19, 82
ASP20, 89
coerce, 90, 95
outputAsFortran, 90, 95
retract, 90, 95
retractIfCan, 90, 95
Asp20, 89
ASP24, 95
Asp24, 95
ASP27, 99
coerce, 99
outputAsFortran, 99
Asp27, 99
ASP28, 102
coerce, 102
outputAsFortran, 102
Asp28, 102
ASP29, 108
coerce, 108
outputAsFortran, 108
Asp29, 108
ASP30, 111
coerce, 111
outputAsFortran, 111
Asp30, 111
ASP31, 115
coerce, 115
outputAsFortran, 115
retract, 115
retractIfCan, 115
Asp31, 115

ASP33, 120
    coerce, 120
    outputAsFortran, 120
Asp33, 120
ASP34, 123
    coerce, 123
    outputAsFortran, 123
Asp34, 123
ASP35, 127
    coerce, 127
    outputAsFortran, 127
    retract, 127
    retractIfCan, 127
Asp35, 127
ASP4, 132
    coerce, 132
    outputAsFortran, 132
    retract, 132
    retractIfCan, 132
Asp4, 132
ASP41, 136
    coerce, 136
    outputAsFortran, 136
    retract, 136
    retractIfCan, 136
Asp41, 136
ASP42, 142
    coerce, 142
    outputAsFortran, 142
    retract, 142
    retractIfCan, 142
Asp42, 142
ASP49, 149
    coerce, 149
    outputAsFortran, 149
    retract, 149
    retractIfCan, 149
Asp49, 149
ASP50, 153
    coerce, 154
    outputAsFortran, 154
    retract, 154
    retractIfCan, 154
Asp50, 153
ASP55, 158
    coerce, 159
    outputAsFortran, 159
    retract, 159
    retractIfCan, 159
Asp55, 158
ASP6, 164
    coerce, 164
    outputAsFortran, 164
    retract, 164
    retractIfCan, 164
Asp6, 164
ASP7, 169
    coerce, 169
    outputAsFortran, 169
    retract, 169
    retractIfCan, 169
Asp7, 169
ASP73, 174
    coerce, 174
    outputAsFortran, 174
    retract, 174
    retractIfCan, 174
Asp73, 174
ASP74, 178
    coerce, 178
    outputAsFortran, 178
    retract, 178
    retractIfCan, 178
Asp74, 178
ASP77, 184
    coerce, 184
    outputAsFortran, 184
    retract, 184
    retractIfCan, 184
Asp77, 184
ASP78, 189
    coerce, 189
    outputAsFortran, 189
    retract, 189
    retractIfCan, 189
Asp78, 189
ASP8, 193
    coerce, 193
    outputAsFortran, 193
Asp8, 193
ASP80, 197
    coerce, 197

outputAsFortran, 197
retract, 197
retractIfCan, 197
Asp80, 197
ASP9, 202
coerce, 202
outputAsFortran, 202
retract, 202
retractIfCan, 202
Asp9, 202
assert
BOP, 258
assign
FC, 902
OUTFORM, 1834
assoc
ALIST, 221
AssociatedJordanAlgebra, 208
AssociatedLieAlgebra, 213
associates?
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DIRRING, 551
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391

SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
AssociationList, 220
associative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
associator
ALGSC, 15
FNLA, 997
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
associatorDependence
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
ASTACK, 65
?=?, 65
?~=?, 65
#?, 65
any?, 65
arrayStack, 65
bag, 65
coerce, 65
copy, 65
count, 65
depth, 65
empty, 65
empty?, 65
eq?, 65
eval, 65
every?, 65
extract, 65
hash, 65
insert, 65
inspect, 65
latex, 65
less?, 65
map, 65
member?, 65
members, 65
more?, 65
parts, 65
pop, 65
push, 65
sample, 65
size?, 65
top, 65
atan
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854

atanh
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
atom?
INFORM, 1311
SEX, 2360
SEXOF, 2363
atoms
PATLRES, 1904
ATTRBUT, 224
?=?, 224
?~=?, 224
coerce, 224
decrease, 224
getButtonValue, 224
hash, 224
increase, 224
latex, 224
resetAttributeButtons, 224
setAttributeButtonStep, 224
setButtonValue, 224
AttributeButtons, 224
augment
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
AUTOMOR, 230
?**?, 231
?*?, 231
?.?, 231
?/?, 231
?=?, 231
?^?, 231
?~=?, 231
1, 231
coerce, 231
commutator, 231
conjugate, 231
hash, 231
inv, 231
latex, 231
morphism, 231
one?, 231
recip, 231
sample, 231
Automorphism, 230
autoReduced?
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
axes
VIEW2d, 2739
VIEW3D, 2679

back
DEQUEUE, 499
QUEUE, 2150
backOldPos
IDEAL, 2047
bag
ALIST, 221
ASTACK, 65
CCLASS, 368
DEQUEUE, 499
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
HEAP, 1104
INTABL, 1304
KAFILE, 1382
LIB, 1397

LMDICT, 1483
MSET, 1638
QUEUE, 2150
RESULT, 2267
ROUTINE, 2298
SET, 2338
STACK, 2530
STBL, 2418
STRTBL, 2578
TABLE, 2632
BalancedBinaryTree, 236
balancedBinaryTree
BBTREE, 237
BalancedPAdicInteger, 242
BalancedPAdicRational, 246
base
DFLOAT, 575
FLOAT, 879
INT, 1330
MFLOAT, 1516
MINT, 1525
PERMGRP, 1926
ROMAN, 2293
SINT, 2380
BasicFunctions, 249
BasicOperator, 258
basicSet
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
BasicStochasticDifferential, 270
basis
ALGFF, 28
ALGSC, 15
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FRIDEAL, 965
FRMOD, 970
GCNAALG, 1035
IFF, 1252
IPF, 1271
JORDAN, 209
LIE, 214
LSQM, 1424
MCMPLX, 1511
PF, 2071
RADFF, 2160
SAE, 2368
BBTREE, 236
?.left, 237
?.right, 237
?.value, 237
?=?, 237
?~=?, 237
#?, 237
any?, 237
balancedBinaryTree, 237
child?, 237
children, 237
coerce, 237
copy, 237
count, 237
cyclic?, 237
distance, 237
empty, 237
empty?, 237
eq?, 237
eval, 237
every?, 237
hash, 237
latex, 237
leaf?, 237
leaves, 237
left, 237
less?, 237
map, 237
mapDown, 237
mapUp, 237
member?, 237
members, 237
more?, 237
node, 237

node?, 237
nodes, 237
parts, 237
right, 237
sample, 237
setchildren, 237
setelt, 237
setleaves, 237
setleft, 237
setright, 237
setvalue, 237
size?, 237
value, 237
belong?
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
besselI
DFLOAT, 575
EXPR, 694
besselJ
DFLOAT, 575
EXPR, 694
besselK
DFLOAT, 575
EXPR, 694
besselY
DFLOAT, 575
EXPR, 694
Beta
DFLOAT, 575
EXPR, 694
bfEntry
BFUNCT, 249
bfKeys
BFUNCT, 249
BFUNCT, 249
?=?, 249
?~=?, 249
bfEntry, 249
bfKeys, 249
coerce, 249
hash, 249
latex, 249
BINARY, 276
-?, 277
?<?, 277
?<=?, 277
?>?, 277
?>=?, 277
?**?, 277
?*?, 277
?+?, 277
?-?, 277
?.?, 277
?/?, 277
?=?, 277
?^?, 277
?~=?, 277
?quo?, 277
?rem?, 277
0, 277
1, 277
abs, 277
associates?, 277
binary, 277
ceiling, 277
characteristic, 277
charthRoot, 277
coerce, 277
conditionP, 277
convert, 277
D, 277
denom, 277
denominator, 277
differentiate, 277
divide, 277
euclideanSize, 277
eval, 277
expressIdealMember, 277
exquo, 277
extendedEuclidean, 277
factor, 277
factorPolynomial, 277
factorSquareFreePolynomial, 277
floor, 277
fractionPart, 277
gcd, 277
gcdPolynomial, 277
hash, 277

init, 277
inv, 277
latex, 277
lcm, 277
map, 277
max, 277
min, 277
multiEuclidean, 277
negative?, 277
nextItem, 277
numer, 277
numerator, 277
one?, 277
patternMatch, 277
positive?, 277
prime?, 277
principalIdeal, 277
random, 277
recip, 277
reducedSystem, 277
retract, 277
retractIfCan, 277
sample, 277
sign, 277
sizeLess?, 277
solveLinearPolynomialEquation, 277
squareFree, 277
squareFreePart, 277
squareFreePolynomial, 277
subtractIfCan, 277
unit?, 277
unitCanonical, 277
unitNormal, 277
wholePart, 277
zero?, 277
binary
BINARY, 277
INFORM, 1311
BinaryExpansion, 276
BinaryFile, 279
BinarySearchTree, 287
binarySearchTree
BSTREE, 287
BinaryTournament, 291
binaryTournament
BTOURN, 291
BinaryTree, 294
binaryTree
BTREE, 295
BINFILE, 279
?=?, 280
?~=?, 280
close, 280
coerce, 280
hash, 280
iomode, 280
latex, 280
name, 280
open, 280
position, 280
read, 280
readIfCan, 280
reopen, 280
write, 280
binomial
EXPR, 694
INT, 1330
MINT, 1525
MYEXPR, 1656
OUTFORM, 1834
ROMAN, 2293
SINT, 2380
binomThmExpt
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819

birth
SUBSPACE, 2582
bit?
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
BITS, 299
?/ΓE30F?, 299
?<?, 299
?<=?, 299
?>?, 299
?>=?, 299
?ΓE30F/?, 299
?.?, 299
?=?, 299
?~=?, 299
?and?, 299
?or?, 299
#?, 299
^?, 299
~?, 299
any?, 299
bits, 299
coerce, 299
concat, 299
construct, 299
convert, 299
copy, 299
copyInto, 299
count, 299
delete, 299
elt, 299
empty, 299
empty?, 299
entries, 299
entry?, 299
eq?, 299
eval, 299
every?, 299
fill, 299
find, 299
first, 299
hash, 299
index?, 299
indices, 299
insert, 299
latex, 299
less?, 299
map, 299
max, 299
maxIndex, 299
member?, 299
members, 299
merge, 299
min, 299
minIndex, 299
more?, 299
nand, 299
new, 299
nor, 299
not?, 299
parts, 299
position, 299
qelt, 299
qsetelt, 299
reduce, 299
remove, 299
removeDuplicates, 299
reverse, 299
sample, 299
setelt, 299
size?, 299
sort, 299
sorted?, 299
swap, 299
xor, 299
Bits, 299
bits
BITS, 299
DFLOAT, 575
FLOAT, 879
MFLOAT, 1516
blankSeparate
OUTFORM, 1834
BLHN, 301
?=?, 301
?~=?, 301
chartCoord, 301
coerce, 301
createHN, 301
excepCoord, 301

hash, 301
infClsPt?, 301
latex, 301
quotValuation, 301
ramifMult, 301
transCoord, 301
type, 301
block
FC, 902
BlowUpWithHamburgerNoether, 301
BlowUpWithQuadTrans, 304
BLQT, 304
?=?, 304
?~=?, 304
chartCoord, 304
coerce, 304
createHN, 304
excepCoord, 304
hash, 304
infClsPt?, 304
latex, 304
quotValuation, 304
ramifMult, 304
transCoord, 304
type, 304
blue
COLOR, 394
BOOLEAN, 306
?/ΓE30F?, 307
?<?, 307
?<=?, 307
?>?, 307
?>=?, 307
?ΓE30F/?, 307
?=?, 307
?~=?, 307
?and?, 307
?or?, 307
^?, 307
~?, 307
coerce, 307
convert, 307
false, 307
hash, 307
implies, 307
index, 307
latex, 307
lookup, 307
max, 307
min, 307
nand, 307
nor, 307
not?, 307
random, 307
size, 307
test, 307
true, 307
xor, 307
Boolean, 306
BOP, 258
?<?, 258
?<=?, 258
?>?, 258
?>=?, 258
?=?, 258
?~=?, 258
arity, 258
assert, 258
coerce, 258
comparison, 258
copy, 258
deleteProperty, 258
display, 258
equality, 258
has?, 258
hash, 258
input, 258
is?, 258
latex, 258
max, 258
min, 258
name, 258
nary?, 258
nullary?, 258
operator, 258
properties, 258
property, 258
setProperties, 258
setProperty, 258
unary?, 258
weight, 258
box

AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
OUTFORM, 1834
BPADIC, 242
-?, 242
?**?, 242
?*?, 242
?+?, 242
?-?, 242
?=?, 242
?^?, 242
?~=?, 242
?quo?, 242
?rem?, 242
0, 242
1, 242
approximate, 242
associates?, 242
characteristic, 242
coerce, 242
complete, 242
digits, 242
divide, 242
euclideanSize, 242
expressIdealMember, 242
exquo, 242
extend, 242
extendedEuclidean, 242
gcd, 242
gcdPolynomial, 242
hash, 242
latex, 242
lcm, 242
moduloP, 242
modulus, 242
multiEuclidean, 242
one?, 242
order, 242
principalIdeal, 242
quotientByP, 242
recip, 242
root, 242
sample, 242
sizeLess?, 242
sqrt, 242
subtractIfCan, 242
unit?, 242
unitCanonical, 242
unitNormal, 242
zero?, 242
BPADICRT, 246
-?, 247
?<?, 247
?<=?, 247
?>?, 247
?>=?, 247
?**?, 247
?*?, 247
?+?, 247
?-?, 247
?.?, 247
?/?, 247
?=?, 247
?^?, 247
?~=?, 247
?quo?, 247
?rem?, 247
0, 247
1, 247
abs, 247
approximate, 247
associates?, 247
ceiling, 247
characteristic, 247
charthRoot, 247
coerce, 247
conditionP, 247
continuedFraction, 247
convert, 247
D, 247
denom, 247
denominator, 247
differentiate, 247
divide, 247
euclideanSize, 247
eval, 247
expressIdealMember, 247
exquo, 247
extendedEuclidean, 247

factor, 247
factorPolynomial, 247
factorSquareFreePolynomial, 247
floor, 247
fractionPart, 247
gcd, 247
gcdPolynomial, 247
hash, 247
init, 247
inv, 247
latex, 247
lcm, 247
map, 247
max, 247
min, 247
multiEuclidean, 247
negative?, 247
nextItem, 247
numer, 247
numerator, 247
one?, 247
patternMatch, 247
positive?, 247
prime?, 247
principalIdeal, 247
random, 247
recip, 247
reducedSystem, 247
removeZeroes, 247
retract, 247
retractIfCan, 247
sample, 247
sign, 247
sizeLess?, 247
solveLinearPolynomialEquation, 247
squareFree, 247
squareFreePart, 247
squareFreePolynomial, 247
subtractIfCan, 247
unit?, 247
unitCanonical, 247
unitNormal, 247
wholePart, 247
zero?, 247

brace
CCLASS, 368
MSET, 1638
OUTFORM, 1834
SET, 2338

bracket
OUTFORM, 1834

branchPoint?
ALGFF, 28
RADFF, 2160

branchPointAtInfinity?
ALGFF, 28
RADFF, 2160

bright
PALETTE, 1862

BSD, 270
?<?, 270
?<=?, 270
?=?, 270
?>?, 270
?>=?, 270
?~=?, 270
coerce, 270
convert, 270
convertIfCan, 270
copyBSD, 270
copyIto, 270
d, 270
getSmgl, 270
hash, 270
introduce, 270
latex, 270
max, 270
min, 270

BSTREE, 287
?.left, 287
?.right, 287
?.value, 287
?=?, 287
?~=?, 287
#?, 287
any?, 287
binarySearchTree, 287
child?, 287
children, 287
coerce, 287
copy, 287
count, 287

cyclic?, 287
distance, 287
empty, 287
empty?, 287
eq?, 287
eval, 287
every?, 287
hash, 287
insert, 287
insertRoot, 287
latex, 287
leaf?, 287
leaves, 287
left, 287
less?, 287
map, 287
member?, 287
members, 287
more?, 287
node, 287
node?, 287
nodes, 287
parts, 287
right, 287
sample, 287
setchildren, 287
setelt, 287
setleft, 287
setright, 287
setvalue, 287
size?, 287
split, 287
value, 287
BTOURN, 291
?.left, 291
?.right, 291
?.value, 291
?=?, 291
?~=?, 291
#?, 291
any?, 291
binaryTournament, 291
child?, 291
children, 291
coerce, 291
copy, 291
count, 291
cyclic?, 291
distance, 291
empty, 291
empty?, 291
eq?, 291
eval, 291
every?, 291
hash, 291
insert, 291
latex, 291
leaf?, 291
leaves, 291
left, 291
less?, 291
map, 291
member?, 291
members, 291
more?, 291
node, 291
node?, 291
nodes, 291
parts, 291
right, 291
sample, 291
setchildren, 291
setelt, 291
setleft, 291
setright, 291
setvalue, 291
size?, 291
value, 291
BTREE, 294
?.left, 295
?.right, 295
?.value, 295
?=?, 295
?~=?, 295
#?, 295
any?, 295
binaryTree, 295
child?, 295
children, 295
coerce, 295
copy, 295
count, 295

cyclic?, 295
distance, 295
empty, 295
empty?, 295
eq?, 295
eval, 295
every?, 295
hash, 295
latex, 295
leaf?, 295
leaves, 295
left, 295
less?, 295
map, 295
member?, 295
members, 295
more?, 295
node, 295
node?, 295
nodes, 295
parts, 295
right, 295
sample, 295
setchildren, 295
setelt, 295
setleft, 295
setright, 295
setvalue, 295
size?, 295
value, 295
build
GMODPOL, 1029
BY
SEG, 2325
UNISEG, 2863

cAcos
ISUPS, 1279
cAcosh
ISUPS, 1279
cAcot
ISUPS, 1279
cAcoth
ISUPS, 1279
cAcsc
ISUPS, 1279
cAcsch
ISUPS, 1279
call
FC, 902
car
INFORM, 1311
SEX, 2360
SEXOF, 2363
CARD, 318
?<?, 318
?<=?, 318
?>?, 318
?>=?, 318
?**?, 318
?*?, 318
?+?, 318
?-?, 318
?=?, 318
?^?, 318
?~=?, 318
0, 318
1, 318
Aleph, 318
coerce, 318
countable?, 318
finite?, 318
generalizedContinuumHypothesisAssumed, 318
generalizedContinuumHypothesisAssumed?, 318
hash, 318
latex, 318
max, 318
min, 318
one?, 318
recip, 318
retract, 318
retractIfCan, 318
sample, 318
zero?, 318
cardinality
CCLASS, 368
SET, 2338
CardinalNumber, 318
CARTEN, 342
-?, 342

?*?, 342
?+?, 342
?-?, 342
?.?, 342
?=?, 342
?~=?, 342
0, 342
1, 342
coerce, 342
contract, 342
degree, 342
elt, 342
hash, 342
kroneckerDelta, 342
latex, 342
leviCivitaSymbol, 342
product, 342
rank, 342
ravel, 342
reindex, 342
retract, 342
retractIfCan, 342
sample, 342
transpose, 342
unravel, 342
CartesianTensor, 342
cAsec
ISUPS, 1279
cAsech
ISUPS, 1279
cAsin
ISUPS, 1279
cAsinh
ISUPS, 1279
cAtan
ISUPS, 1279
cAtanh
ISUPS, 1279
CCLASS, 367
?<?, 368
?=?, 368
?~=?, 368
#?, 368
alphabetic, 368
alphanumeric, 368
any?, 368
bag, 368
brace, 368
cardinality, 368
charClass, 368
coerce, 368
complement, 368
construct, 368
convert, 368
copy, 368
count, 368
dictionary, 368
difference, 368
digit, 368
empty, 368
empty?, 368
eq?, 368
eval, 368
every?, 368
extract, 368
find, 368
hash, 368
hexDigit, 368
index, 368
insert, 368
inspect, 368
intersect, 368
latex, 368
less?, 368
lookup, 368
lowerCase, 368
map, 368
max, 368
member?, 368
members, 368
min, 368
more?, 368
parts, 368
random, 368
reduce, 368
remove, 368
removeDuplicates, 368
sample, 368
select, 368
set, 368
size, 368
size?, 368

subset?, 368
symmetricDifference, 368
union, 368
universe, 368
upperCase, 368
cCos
ISUPS, 1279
cCosh
ISUPS, 1279
cCot
ISUPS, 1279
cCoth
ISUPS, 1279
cCsc
ISUPS, 1279
cCsch
ISUPS, 1279
CDFMAT, 413
-?, 413
?**?, 413
?*?, 413
?+?, 413
?-?, 413
?/?, 413
?=?, 413
?~=?, 413
#?, 413
antisymmetric?, 413
any?, 413
coerce, 413
column, 413
columnSpace, 413
copy, 413
count, 413
determinant, 413
diagonal?, 413
diagonalMatrix, 413
elt, 413
empty, 413
empty?, 413
eq?, 413
eval, 413
every?, 413
exquo, 413
fill, 413
hash, 413
horizConcat, 413
inverse, 413
latex, 413
less?, 413
listOfLists, 413
map, 413
matrix, 413
maxColIndex, 413
maxRowIndex, 413
member?, 413
members, 413
minColIndex, 413
minordet, 413
minRowIndex, 413
more?, 413
ncols, 413
new, 413
nrows, 413
nullity, 413
nullSpace, 413
parts, 413
pfaffian, 413
qelt, 413
qnew, 413
qsetelt, 413
rank, 413
row, 413
rowEchelon, 413
sample, 413
scalarMatrix, 413
setColumn, 413
setelt, 413
setRow, 413
setsubMatrix, 413
size?, 413
square?, 413
squareTop, 413
subMatrix, 413
swapColumns, 413
swapRows, 413
symmetric?, 413
transpose, 413
vertConcat, 413
zero, 413
CDFVEC, 419
-?, 419

?<?, 419
?<=?, 419
?>?, 419
?>=?, 419
?*?, 419
?+?, 419
?-?, 419
?.?, 419
?=?, 419
?~=?, 419
#?, 419
any?, 419
coerce, 419
concat, 419
construct, 419
convert, 419
copy, 419
copyInto, 419
count, 419
cross, 419
delete, 419
dot, 419
elt, 419
empty, 419
empty?, 419
entries, 419
entry?, 419
eq?, 419
eval, 419
every?, 419
fill, 419
find, 419
first, 419
hash, 419
index?, 419
indices, 419
insert, 419
latex, 419
length, 419
less?, 419
magnitude, 419
map, 419
max, 419
maxIndex, 419
member?, 419
members, 419
merge, 419
min, 419
minIndex, 419
more?, 419
new, 419
outerProduct, 419
parts, 419
position, 419
qelt, 419
qnew, 419
qsetelt, 419
reduce, 419
remove, 419
removeDuplicates, 419
reverse, 419
sample, 419
select, 419
setelt, 419
size?, 419
sort, 419
sorted?, 419
swap, 419
vector, 419
zero, 419
cdr
INFORM, 1311
SEX, 2360
SEXOF, 2363
ceiling
BINARY, 277
BPADICRT, 247
DECIMAL, 453
DFLOAT, 575
EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HEXADEC, 1113
MFLOAT, 1516
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
center
EXPUPXS, 710

GSERIES, 1061
ISUPS, 1279
NSDPS, 1670
OUTFORM, 1834
SULS, 2425
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
cExp
ISUPS, 1279
changeBase
MFLOAT, 1516
changeMeasure
ROUTINE, 2298
changeThreshhold
ROUTINE, 2298
changeWeightLevel
OWP, 1828
WP, 2885
CHAR, 359
?<?, 359
?<=?, 359
?>?, 359
?>=?, 359
?=?, 359
?~=?, 359
alphabetic?, 359
alphanumeric?, 359
char, 359
coerce, 359
digit?, 359
escape, 359
hash, 359
hexDigit?, 359
index, 359
latex, 359
lookup, 359
lowerCase, 359
lowerCase?, 359
max, 359
min, 359
ord, 359
quote, 359
random, 359
size, 359
space, 359
upperCase, 359
upperCase?, 359
char
CHAR, 359
Character, 359
character?
FST, 933
CharacterClass, 367
characteristic
ALGFF, 28
AN, 35
ANTISYM, 40
BINARY, 277
BPADIC, 242
BPADICRT, 247
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836

FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
FSERIES, 948
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LA, 1488
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936

XPR, 2945
XRPOLY, 2951
ZMOD, 1336
characteristicPolynomial
ALGFF, 28
COMPLEX, 406
MCMPLX, 1511
RADFF, 2160
SAE, 2368
characteristicSerie
WUTSET, 2895
characteristicSet
WUTSET, 2895
charClass
CCLASS, 368
chartCoord
BLHN, 301
BLQT, 304
charthRoot
ALGFF, 28
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FRAC, 956
GDMP, 1022
GSERIES, 1061
HDMP, 1150
HEXADEC, 1113
IFF, 1252
IPF, 1271
ISUPS, 1279
LAUPOL, 1390
MCMPLX, 1511
MODMON, 1600
MODOP, 1615, 1771
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODPOL, 1818
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PF, 2071
POLY, 2044
PR, 2058
QUAT, 2133
RADFF, 2160
RADIX, 2172
SAE, 2368
SDPOL, 2352
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
chartV
IC, 1161
INFCLSPS, 1240

INFCLSPT, 1234
check
GOPT, 1075
GOPT0, 1081
SPACE3, 2701
checkExtraValues
GOPT, 1075
checkOptions
GOPT0, 1081
child
SUBSPACE, 2582
child?
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
children
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
SUBSPACE, 2582
TREE, 2710
Ci
EXPR, 694
clearTheFTable
INTFTBL, 1339
clearTheIFTable
ODEIFTBL, 1734
clearTheSymbolTable
SYMS, 2665
CLIF, 388
-?, 388
?**?, 388
?*?, 388
?+?, 388
?-?, 388
?/?, 388
?=?, 388
?^?, 388
?~=?, 388
0, 388
1, 388
characteristic, 388
coefficient, 388
coerce, 388
dimension, 388
e, 388
hash, 388
latex, 388
monomial, 388
one?, 388
recip, 388
sample, 388
subtractIfCan, 388
zero?, 388
CliffordAlgebra, 388
clip
DROPT, 596
clipSurface
VIEW3D, 2679
cLog
ISUPS, 1279
close
COMPPROP, 2592
VIEW2d, 2739
VIEW3D, 2679
closeComponent
SUBSPACE, 2582
closed?
COMPPROP, 2592
TUBE, 2718
closedCurve

SPACE3, 2701
closedCurve?
SPACE3, 2701
code
FC, 902
coef
LPOLY, 1415
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
coefficient
ANTISYM, 40
CLIF, 388
DERHAM, 517
DIV, 563
DMP, 560
DSMP, 529
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FM1, 987
GDMP, 1022
GSERIES, 1061
HDMP, 1150
IFAMON, 1255
ISUPS, 1279
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
OMLO, 1773
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SD, 2540
SDPOL, 2352
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
coefficients
DMP, 560
DSMP, 529
FM1, 987
GDMP, 1022
HDMP, 1150
ITAYLOR, 1306
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SDPOL, 2352

SMP, 2391
SUP, 2435
SUPEXPR, 2449
SUTS, 2464
SYMPOLY, 2622
UFPS, 2757
UP, 2795
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
coefOfFirstNonZeroTerm
NSDPS, 1670
coerce
ACPLOT, 1958
AFFPLPS, 7
AFFSP, 9
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ANON, 38
ANTISYM, 40
ANY, 50
ARRAY1, 1740
ARRAY2, 2732
ASP1, 71
ASP10, 75
ASP12, 79
ASP19, 82
ASP20, 90, 95
ASP27, 99
ASP28, 102
ASP29, 108
ASP30, 111
ASP31, 115
ASP33, 120
ASP34, 123
ASP35, 127
ASP4, 132
ASP41, 136
ASP42, 142
ASP49, 149
ASP50, 154
ASP55, 159
ASP6, 164
ASP7, 169
ASP73, 174
ASP74, 178
ASP77, 184
ASP78, 189
ASP8, 193
ASP80, 197
ASP9, 202
ASTACK, 65
ATTRBUT, 224
AUTOMOR, 231
BBTREE, 237
BFUNCT, 249
BINARY, 277
BINFILE, 280
BITS, 299
BLHN, 301
BLQT, 304
BOOLEAN, 307
BOP, 258
BPADIC, 242
BPADICRT, 247
BSD, 270
BSTREE, 287
BTOURN, 291
BTREE, 295
CARD, 318
CARTEN, 342
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
CHAR, 359
CLIF, 388
COLOR, 394
COMM, 397
COMPLEX, 406
COMPPROP, 2592
CONTFRAC, 432
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617
D01AQFA, 620

D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
D10ANFA, 614
DBASE, 442
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DROPT, 596
DSMP, 529
DSTREE, 522
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732
E04NAFA, 735
E04UCFA, 739
EAB, 713
EMR, 672
EQ, 661
EQTBL, 669
EXIT, 677
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FARRAY, 856
FC, 902
FCOMP, 945
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FILE, 772
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNAME, 780
FNLA, 997
FORMULA, 2312
FORTRAN, 926
FPARFRAC, 1010
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
FST, 933
FT, 941
FTEM, 938
FUNCTION, 1015
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GOPT, 1075
GOPT0, 1081
GPOLSET, 1044
GRIMAGE, 1065
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090

HDMP, 1150
HDP, 1143
HEAP, 1104
HELLFDIV, 1153
HEXADEC, 1113
HTMLFORM, 1122
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IC, 1161
ICARD, 1163
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFARRAY, 1192
IFF, 1252
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INFCLSPS, 1240
INFCLSPT, 1234
INFORM, 1311
INT, 1330
INTABL, 1304
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1279
ITAYLOR, 1306
ITUPLE, 1231
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
KERNEL, 1372
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LMOPS, 1477
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
M3D, 2672
MAGMA, 1533
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MMLFORM, 1571
MODFIELD, 1606
MODMON, 1600
MODMONOM, 1612
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NIPROB, 1713
NNI, 1706
NONE, 1704
NOTTING, 1711
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODEPROB, 1716
ODP, 1783
ODPOL, 1818
ODR, 1825
ODVAR, 1821
OFMONOID, 1795
OMENC, 1755
OMERR, 1758

OMERRK, 1761
OMLO, 1773
ONECOMP, 1744
OPTPROB, 1719
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OSI, 1830
OUTFORM, 1834
OVAR, 1803
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PALETTE, 1862
PATLRES, 1904
PATRES, 1906
PATTERN, 1894
PBWLB, 2020
PDEPROB, 1722
PENDTREE, 1911
PERM, 1916
PERMGRP, 1926
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
PLOT, 1995
PLOT3D, 2008
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
PRODUCT, 2079
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
PRTITION, 1889
QALGSET, 2123
QEQUAT, 2135
QFORM, 2120
QUAT, 2133
QUEUE, 2150
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REF, 2215
REGSET, 2252
RESRING, 2262
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROIRC, 2276
ROMAN, 2293
ROUTINE, 2298
RULE, 2271
RULECOLD, 2307
RULESET, 2309
SAE, 2368
SAOS, 2386
SD, 2540
SDPOL, 2352
SDVAR, 2358
SEG, 2325
SEGBIND, 2330
SET, 2338
SETMN, 2344
SEX, 2360
SEXOF, 2363
SFORT, 2374
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SPACE3, 2701
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUBSPACE, 2582
SUCH, 2595
SULS, 2425
SUP, 2435
SUPEXPR, 2449

SUPXS, 2455
SUTS, 2464
SWITCH, 2597
SYMBOL, 2608
SYMPOLY, 2622
SYMS, 2665
SYMTAB, 2616
TABLE, 2632
TABLEAU, 2634
TEX, 2645
TEXTFILE, 2661
TREE, 2710
TS, 2639
TUPLE, 2721
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VARIABLE, 2872
VECTOR, 2878
VIEW2d, 2739
VIEW3D, 2679
VOID, 2881
WP, 2885
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
coerceImages
PERM, 1916
coerceL
HTMLFORM, 1122
MMLFORM, 1571
coerceListOfPairs
PERM, 1916
coercePreimagesImages
PERM, 1916
coerceS
HTMLFORM, 1122
MMLFORM, 1571
coHeight
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
collect
DIV, 563
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
collectQuasiMonic
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
collectUnder
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
collectUpper
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
COLOR, 394
?*?, 394
?+?, 394
?=?, 394
?~=?, 394
blue, 394
coerce, 394
color, 394

green, 394
hash, 394
hue, 394
latex, 394
numberOfHues, 394
red, 394
yellow, 394
Color, 394
color
COLOR, 394
colorDef
VIEW3D, 2679
colorFunction
DROPT, 596
column
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
columnSpace
CDFMAT, 413
DFMAT, 587
COMM, 397
?=?, 397
?~=?, 397
coerce, 397
hash, 397
latex, 397
mkcomm, 397
commaSeparate
OUTFORM, 1834
comment
FC, 902
common
FC, 902
commutative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
commutativeEquality
LMOPS, 1477
Commutator, 397
commutator
ALGSC, 15
AUTOMOR, 231
EQ, 661
EXPR, 694
FGROUP, 980
FNLA, 997
FRIDEAL, 965
GCNAALG, 1035
JORDAN, 209
LEXP, 1403
LIE, 214
LSQM, 1424
MOEBIUS, 1622
MYEXPR, 1656
NOTTING, 1711
PERM, 1916
PRODUCT, 2079
compactFraction
PFR, 1880
comparison
BOP, 258
compile
INFORM, 1311
complement
CCLASS, 368
SET, 2338
complementaryBasis
ALGFF, 28
RADFF, 2160
complete
BPADIC, 242
CONTFRAC, 432
EXPUPXS, 710
GSERIES, 1061
IPADIC, 1262
ISUPS, 1279
NSDPS, 1670
PADIC, 1847
SMTS, 2409
STREAM, 2550

SULS, 2425
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
COMPLEX, 405
-?, 406
?<?, 406
?<=?, 406
?>?, 406
?>=?, 406
?**?, 406
?*?, 406
?+?, 406
?-?, 406
?.?, 406
?/?, 406
?=?, 406
?^?, 406
?~=?, 406
?quo?, 406
?rem?, 406
0, 406
1, 406
abs, 406
acos, 406
acosh, 406
acot, 406
acoth, 406
acsc, 406
acsch, 406
argument, 406
asec, 406
asech, 406
asin, 406
asinh, 406
associates?, 406
atan, 406
atanh, 406
basis, 406
characteristic, 406
characteristicPolynomial, 406
charthRoot, 406
coerce, 406
complex, 406
conditionP, 406
conjugate, 406
convert, 406
coordinates, 406
cos, 406
cosh, 406
cot, 406
coth, 406
createPrimitiveElement, 406
csc, 406
csch, 406
D, 406
definingPolynomial, 406
derivationCoordinates, 406
differentiate, 406
discreteLog, 406
discriminant, 406
divide, 406
euclideanSize, 406
eval, 406
exp, 406
expressIdealMember, 406
exquo, 406
extendedEuclidean, 406
factor, 406
factorPolynomial, 406
factorsOfCyclicGroupSize, 406
factorSquareFreePolynomial, 406
gcd, 406
gcdPolynomial, 406
generator, 406
hash, 406
imag, 406
imaginary, 406
index, 406
init, 406
inv, 406
latex, 406
lcm, 406
lift, 406
log, 406

lookup, 406
map, 406
max, 406
min, 406
minimalPolynomial, 406
multiEuclidean, 406
nextItem, 406
norm, 406
nthRoot, 406
OMwrite, 406
one?, 406
order, 406
patternMatch, 406
pi, 406
polarCoordinates, 406
prime?, 406
primeFrobenius, 406
primitive?, 406
primitiveElement, 406
principalIdeal, 406
random, 406
rank, 406
rational, 406
rational?, 406
rationalIfCan, 406
real, 406
recip, 406
reduce, 406
reducedSystem, 406
regularRepresentation, 406
representationType, 406
represents, 406
retract, 406
retractIfCan, 406
sample, 406
sec, 406
sech, 406
sin, 406
sinh, 406
size, 406
sizeLess?, 406
solveLinearPolynomialEquation, 406
sqrt, 406
squareFree, 406
squareFreePart, 406
squareFreePolynomial, 406
subtractIfCan, 406
tableForDiscreteLogarithm, 406
tan, 406
tanh, 406
trace, 406
traceMatrix, 406
unit?, 406
unitCanonical, 406
unitNormal, 406
zero?, 406
Complex, 405
complex
COMPLEX, 406
MCMPLX, 1511
complex?
FST, 933
ComplexDoubleFloatMatrix, 413
ComplexDoubleFloatVector, 419
component
GRIMAGE, 1065
components
SPACE3, 2701
composite
MODMON, 1600
MYUP, 1663
NSUP, 1696
SPACE3, 2701
SUP, 2435
SUPEXPR, 2449
UP, 2795
composites
SPACE3, 2701
COMPPROP, 2592
?=?, 2592
?~=?, 2592
close, 2592
closed?, 2592
coerce, 2592
copy, 2592
hash, 2592
latex, 2592
new, 2592
solid, 2592
solid?, 2592
computePowers
MODMON, 1600

concat
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIV, 563
DLIST, 448
FARRAY, 856
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
NSDPS, 1670
POINT, 2026
PRIMARR, 2075
ROUTINE, 2298
STREAM, 2550
STRING, 2575
U32VEC, 2869
VECTOR, 2878
cond
FC, 902
condition
SPLNODE, 2479
conditionP
ALGFF, 28
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DMP, 560
DSMP, 529
EXPEXPAN, 682
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FRAC, 956
GDMP, 1022
HDMP, 1150
HEXADEC, 1113
IFF, 1252
IPF, 1271
MCMPLX, 1511
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PACOFF, 2102
PADICRAT, 1852
PADICRC, 1857
PF, 2071
POLY, 2044
RADFF, 2160
RADIX, 2172
SAE, 2368
SDPOL, 2352
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
conditions
SPLTREE, 2485
conditionsForIdempotents
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
conjug
MODOP, 1615, 1771
conjugate
AFFPLPS, 7
AFFSP, 9
AUTOMOR, 231
COMPLEX, 406
EQ, 661
EXPR, 694

FGROUP, 980
FRIDEAL, 965
LEXP, 1403
MCMPLX, 1511
MOEBIUS, 1622
MYEXPR, 1656
NOTTING, 1711
OCT, 1731
PACOFF, 2102
PACRAT, 2112
PERM, 1916
PRODUCT, 2079
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
PRTITION, 1889
QUAT, 2133
connect
VIEW2d, 2739
cons
LIST, 1472
STREAM, 2550
constant
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
constant?
PATTERN, 1894
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
construct
ALIST, 221
ARRAY1, 1740
BITS, 299
CCLASS, 368
CDFVEC, 419
DFVEC, 593
DLIST, 448
EQTBL, 669
FARRAY, 856
FPARFRAC, 1010
FT, 941
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
ITUPLE, 1231
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LPOLY, 1415
M3D, 2672
MODMONOM, 1612
MSET, 1638
NSDPS, 1670
PATRES, 1906
POINT, 2026
PRIMARR, 2075
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
ROUTINE, 2298
SET, 2338
SPLNODE, 2479
SPLTREE, 2485
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUCH, 2595
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
contains?
INTRVL, 1352
content
DSMP, 529

GDMP, 1022
HDMP, 1150
LODO, 1437
LODO1, 1447
LODO2, 1459
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819
CONTFRAC, 432
-?, 432
?**?, 432
?*?, 432
?+?, 432
?-?, 432
?/?, 432
?=?, 432
?^?, 432
?~=?, 432
?quo?, 432
?rem?, 432
0, 432
1, 432
approximants, 432
associates?, 432
characteristic, 432
coerce, 432
complete, 432
continuedFraction, 432
convergents, 432
denominators, 432
divide, 432
euclideanSize, 432
expressIdealMember, 432
exquo, 432
extend, 432
extendedEuclidean, 432
factor, 432
gcd, 432
gcdPolynomial, 432
hash, 432
inv, 432
latex, 432
lcm, 432
multiEuclidean, 432
numerators, 432
one?, 432
partialDenominators, 432
partialNumerators, 432
partialQuotients, 432
prime?, 432
principalIdeal, 432
recip, 432
reducedContinuedFraction, 432
reducedForm, 432
sample, 432
sizeLess?, 432
squareFree, 432
squareFreePart, 432
subtractIfCan, 432
unit?, 432
unitCanonical, 432
unitNormal, 432
wholePart, 432
zero?, 432
continue
FC, 902
ContinuedFraction, 432
continuedFraction
BPADICRT, 247
CONTFRAC, 432
PADICRAT, 1852
PADICRC, 1857
contract
CARTEN, 342
controlPanel
VIEW2d, 2739
VIEW3D, 2679
convergents

CONTFRAC, 432
convert
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ARRAY1, 1740
BINARY, 277
BITS, 299
BOOLEAN, 307
BPADICRT, 247
BSD, 270
CCLASS, 368
CDFVEC, 419
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DLIST, 448
DMP, 560
DSMP, 529
EQTBL, 669
EXPEXPAN, 682
EXPR, 694
FARRAY, 856
FLOAT, 879
FORMULA, 2312
FPARFRAC, 1010
FR, 756
FRAC, 956
GCNAALG, 1035
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INFORM, 1311
INT, 1330
INTABL, 1304
IPF, 1271
ISTRING, 1218
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
KERNEL, 1372
LAUPOL, 1390
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODMON, 1600
MPOLY, 1650
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
OCT, 1731
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PF, 2071
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRTITION, 1889
QUAT, 2133
RADFF, 2160
RADIX, 2172
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROMAN, 2293
ROUTINE, 2298
SAE, 2368
SAOS, 2386
SDPOL, 2352
SEG, 2325

SET, 2338
SEX, 2360
SEXOF, 2363
SINT, 2380
SMP, 2391
SQMATRIX, 2515
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
TABLE, 2632
TEX, 2645
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
VECTOR, 2878
WUTSET, 2895
ZMOD, 1336
convertIfCan
BSD, 270
coord
DROPT, 596
coordinate
PARPCURV, 1865
PARSCURV, 1868
PARSURF, 1870
coordinates
ALGFF, 28
ALGSC, 15
COMPLEX, 406
DROPT, 596
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
GCNAALG, 1035
IFF, 1252
IPF, 1271
JORDAN, 209
LIE, 214
LSQM, 1424
MCMPLX, 1511
PF, 2071
RADFF, 2160
SAE, 2368
copy
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BOP, 258
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
COMPPROP, 2592
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169

IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INT, 1330
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MINT, 1525
MSET, 1638
NSDPS, 1670
ODP, 1783
PATTERN, 1894
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROMAN, 2293
ROUTINE, 2298
SET, 2338
SHDP, 2476
SINT, 2380
SPACE3, 2701
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
copyBSD
BSD, 270
copyDrift
SD, 2540
copyIto
BSD, 270
copyQuadVar
SD, 2540
cos
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FCOMP, 945
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
cosh
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425

SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
cot
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
coth
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
count
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208

INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895

countable?
CARD, 318

cPower
ISUPS, 1279

cRationalPower
ISUPS, 1279

create
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
PLACES, 1985
PLACESPS, 1987
SAOS, 2386

create3Space
SPACE3, 2701

createHN
BLHN, 301
BLQT, 304

createNormalElement
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PF, 2071

createPrimitiveElement
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PF, 2071
RADFF, 2160
SAE, 2368

cross
CDFVEC, 419
DFVEC, 593
IVECTOR, 1229
POINT, 2026

VECTOR, 2878
csc
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
csch
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
cSec
ISUPS, 1279
cSech
ISUPS, 1279
cSin
ISUPS, 1279
cSinh
ISUPS, 1279
csubst
SMTS, 2409
cTan
ISUPS, 1279
cTanh
ISUPS, 1279
currentSubProgram
SYMS, 2665
curve
PARPCURV, 1865
PARSCURV, 1868
SPACE3, 2701
curve?
SPACE3, 2701
curveColor
DROPT, 596
curveV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
cycle
PERM, 1916
cycleEntry
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
cycleLength
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
cyclePartition
PERM, 1916
cycleRagits

RADIX, 2172
cycles
PERM, 1916
cycleTail
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
cyclic?
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
cyclicCopy
TREE, 2710
cyclicEntries
TREE, 2710
cyclicEqual?
TREE, 2710
cyclicParents
TREE, 2710

D
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DIRPROD, 534
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FPARFRAC, 1010
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPF, 1271
ISUPS, 1279
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MINT, 1525
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODP, 1783
ODPOL, 1818
ODR, 1825

OMLO, 1773
PACOFF, 2102
PADICRAT, 1852
PADICRC, 1857
PF, 2071
POLY, 2044
QUAT, 2133
RADFF, 2160
RADIX, 2172
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
d
BSD, 270
D01AJFA, 602
?=?, 602
?~=?, 602
coerce, 602
hash, 602
latex, 602
measure, 602
numericalIntegration, 602
d01ajfAnnaType, 602
D01AKFA, 605
?=?, 605
?~=?, 605
coerce, 605
hash, 605
latex, 605
measure, 605
numericalIntegration, 605
d01akfAnnaType, 605
D01ALFA, 608
?=?, 608
?~=?, 608
coerce, 608
hash, 608
latex, 608
measure, 608
numericalIntegration, 608
d01alfAnnaType, 608
D01AMFA, 611
?=?, 611
?~=?, 611
coerce, 611
hash, 611
latex, 611
measure, 611
numericalIntegration, 611
d01amfAnnaType, 611
D01ANFA, 614
d01anfAnnaType, 614
D01APFA, 617
?=?, 617, 620
?~=?, 617, 620
coerce, 617
hash, 617, 620
latex, 617, 620
measure, 617, 620
numericalIntegration, 617, 620
d01apfAnnaType, 617
D01AQFA, 620
coerce, 620
d01aqfAnnaType, 620
D01ASFA, 624
?=?, 624
?~=?, 624
coerce, 624
hash, 624
latex, 624
measure, 624
numericalIntegration, 624
d01asfAnnaType, 624

D01FCFA, 627
?=?, 627
?~=?, 627
coerce, 627
hash, 627
latex, 627
measure, 627
numericalIntegration, 627
d01fcfAnnaType, 627
D01GBFA, 630
?=?, 630
?~=?, 630
coerce, 630
hash, 630
latex, 630
measure, 630
numericalIntegration, 630
d01gbfAnnaType, 630
d01TransformFunctionType, 633
D01TRNS, 633
?=?, 633
?~=?, 633
coerce, 633
hash, 633
latex, 633
measure, 633
numericalIntegration, 633
D02BBFA, 638
?=?, 638
?~=?, 638
coerce, 638
hash, 638
latex, 638
measure, 638
ODESolve, 638
d02bbfAnnaType, 638
D02BHFA, 641
?=?, 641
?~=?, 641
coerce, 641
hash, 641
latex, 641
measure, 641
ODESolve, 641
d02bhfAnnaType, 641
D02CJFA, 645
?=?, 645
?~=?, 645
coerce, 645
hash, 645
latex, 645
measure, 645
ODESolve, 645
d02cjfAnnaType, 645
D02EJFA, 648
?=?, 648
?~=?, 648
coerce, 648
hash, 648
latex, 648
measure, 648
ODESolve, 648
d02ejfAnnaType, 648
D03EEFA, 652
?=?, 652
?~=?, 652
coerce, 652
hash, 652
latex, 652
measure, 652
PDESolve, 652
d03eefAnnaType, 652
D03FAFA, 655
?=?, 655
?~=?, 655
coerce, 655
hash, 655
latex, 655
measure, 655
PDESolve, 655
d03fafAnnaType, 655
D10ANFA
?=?, 614
?~=?, 614
coerce, 614
hash, 614
latex, 614
measure, 614
numericalIntegration, 614
dark
PALETTE, 1862
Database, 442

DataList, 447
datalist
    DLIST, 448
DBASE, 442
    ?+?, 442
    ?-?, 442
    ?.?, 442
    ?=?, 442
    ?~=?, 442
    coerce, 442
    display, 442
    fullDisplay, 442
    hash, 442
    latex, 442
debug
    GOPT, 1075
    GOPT0, 1081
    PLOT, 1995
debug3D
    PLOT3D, 2008
dec
    INT, 1330
    MINT, 1525
    ROMAN, 2293
    SINT, 2380
DECIMAL, 453
    -?, 453
    ?<?, 453
    ?<=?, 453
    ?>?, 453
    ?>=?, 453
    ?**?, 453
    ?*?, 453
    ?+?, 453
    ?-?, 453
    ?.?, 453
    ?/?, 453
    ?=?, 453
    ?^?, 453
    ?~=?, 453
    ?quo?, 453
    ?rem?, 453
    0, 453
    1, 453
    abs, 453
    associates?, 453
    ceiling, 453
    characteristic, 453
    charthRoot, 453
    coerce, 453
    conditionP, 453
    convert, 453
    D, 453
    decimal, 453
    denom, 453
    denominator, 453
    differentiate, 453
    divide, 453
    euclideanSize, 453
    eval, 453
    expressIdealMember, 453
    exquo, 453
    extendedEuclidean, 453
    factor, 453
    factorPolynomial, 453
    factorSquareFreePolynomial, 453
    floor, 453
    fractionPart, 453
    gcd, 453
    gcdPolynomial, 453
    hash, 453
    init, 453
    inv, 453
    latex, 453
    lcm, 453
    map, 453
    max, 453
    min, 453
    multiEuclidean, 453
    negative?, 453
    nextItem, 453
    numer, 453
    numerator, 453
    one?, 453
    patternMatch, 453
    positive?, 453
    prime?, 453
    principalIdeal, 453
    random, 453
    recip, 453
    reducedSystem, 453
    retract, 453

retractIfCan, 453
sample, 453
sign, 453
sizeLess?, 453
solveLinearPolynomialEquation, 453
squareFree, 453
squareFreePart, 453
squareFreePolynomial, 453
subtractIfCan, 453
unit?, 453
unitCanonical, 453
unitNormal, 453
wholePart, 453
zero?, 453
decimal
DECIMAL, 453
DecimalExpansion, 453
declare
INFORM, 1311
decompose
FDIV, 783
HELLFDIV, 1153
decrease
ATTRBUT, 224
decreasePrecision
DFLOAT, 575
FLOAT, 879
MFLOAT, 1516
deepCopy
SUBSPACE, 2582
deepestInitial
NSMP, 1681
deepestTail
NSMP, 1681
deepExpand
FNLA, 997
defineProperty
SUBSPACE, 2582
definingEquations
QALGSET, 2123
definingField
AFFPLPS, 7
AFFSP, 9
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
definingInequation
QALGSET, 2123
definingPolynomial
ALGFF, 28
AN, 35
COMPLEX, 406
EXPR, 694
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IAN, 1245
IFF, 1252
IPF, 1271
MCMPLX, 1511
MYEXPR, 1656
PACOFF, 2102
PACRAT, 2112
PF, 2071
RADFF, 2160
ROIRC, 2276
SAE, 2368
degree
AFFPLPS, 7
AFFSP, 9
ANTISYM, 40
CARTEN, 342
DERHAM, 517
DIV, 563
DMP, 560
DSMP, 529
EAB, 713
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836

FFP, 821
FFX, 816
GDMP, 1022
GSERIES, 1061
GTSET, 1054
HDMP, 1150
IC, 1161
IFF, 1252
INFCLSPS, 1240
INFCLSPT, 1234
IPF, 1271
ISUPS, 1279
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
OMLO, 1773
ORESUP, 2460
OREUP, 2840
PACOFF, 2102
PACRAT, 2112
PERM, 1916
PERMGRP, 1926
PF, 2071
PLACES, 1985
PLACESPS, 1987
POLY, 2044
PR, 2058
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
REGSET, 2252
RGCHAIN, 2221
SDPOL, 2352
SMP, 2391
SMTS, 2409
SREGSET, 2502
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
delay
NSDPS, 1670
STREAM, 2550
delete
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
NSDPS, 1670
POINT, 2026
PRIMARR, 2075
STREAM, 2550
STRING, 2575
U32VEC, 2869
VECTOR, 2878
delta

SETMN, 2344
DenavitHartenbergMatrix, 478
denom
AN, 35
BINARY, 277
BPADICRT, 247
DECIMAL, 453
EXPEXPAN, 682
EXPR, 694
FRAC, 956
FRIDEAL, 965
HEXADEC, 1113
IAN, 1245
LA, 1488
LO, 1491
MYEXPR, 1656
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
denominator
BINARY, 277
BPADICRT, 247
DECIMAL, 453
EXPEXPAN, 682
EXPR, 694
FRAC, 956
HEXADEC, 1113
MYEXPR, 1656
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
denominators
CONTFRAC, 432
depth
ASTACK, 65
DEQUEUE, 499
PATTERN, 1894
STACK, 2530
DEQUEUE, 499
?=?, 499
?~=?, 499
#?, 499
any?, 499
back, 499
bag, 499
bottom, 499
coerce, 499
copy, 499
count, 499
depth, 499
dequeue, 499
empty, 499
empty?, 499
enqueue, 499
eq?, 499
eval, 499
every?, 499
extract, 499
extractBottom, 499
extractTop, 499
front, 499
hash, 499
height, 499
insert, 499
insertBottom, 499
insertTop, 499
inspect, 499
latex, 499
length, 499
less?, 499
map, 499
member?, 499
members, 499
more?, 499
parts, 499
pop, 499
push, 499
reverse, 499
rotate, 499
sample, 499
size?, 499
top, 499
Dequeue, 499
dequeue
DEQUEUE, 499
deref

REF, 2215
DERHAM, 517
-?, 517
?**?, 517
?*?, 517
?+?, 517
?-?, 517
?=?, 517
?^?, 517
?~=?, 517
0, 517
1, 517
characteristic, 517
coefficient, 517
coerce, 517
degree, 517
exteriorDifferential, 517
generator, 517
hash, 517
homogeneous?, 517
latex, 517
leadingBasisTerm, 517
leadingCoefficient, 517
map, 517
one?, 517
recip, 517
reductum, 517
retract, 517
retractable?, 517
retractIfCan, 517
sample, 517
subtractIfCan, 517
totalDifferential, 517
zero?, 517
DeRhamComplex, 517
derivationCoordinates
ALGFF, 28
COMPLEX, 406
MCMPLX, 1511
RADFF, 2160
SAE, 2368
DesingTree, 522
destruct
INFORM, 1311
PATRES, 1906
SEX, 2360
SEXOF, 2363
determinant
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
SQMATRIX, 2515
DFLOAT, 574
-?, 575
?<?, 575
?<=?, 575
?>?, 575
?>=?, 575
?**?, 575
?*?, 575
?+?, 575
?-?, 575
?/?, 575
?=?, 575
?^?, 575
?~=?, 575
?quo?, 575
?rem?, 575
0, 575
1, 575
abs, 575
acos, 575
acosh, 575
acot, 575
acoth, 575
acsc, 575
acsch, 575
airyAi, 575
airyBi, 575
asec, 575
asech, 575
asin, 575
asinh, 575
associates?, 575
atan, 575
atanh, 575
base, 575
besselI, 575
besselJ, 575

besselK, 575
besselY, 575
Beta, 575
bits, 575
ceiling, 575
characteristic, 575
coerce, 575
convert, 575
cos, 575
cosh, 575
cot, 575
coth, 575
csc, 575
csch, 575
D, 575
decreasePrecision, 575
differentiate, 575
digamma, 575
digits, 575
divide, 575
doubleFloatFormat, 575
euclideanSize, 575
exp, 575
exp1, 575
exponent, 575
expressIdealMember, 575
exquo, 575
extendedEuclidean, 575
factor, 575
float, 575
floor, 575
fractionPart, 575
Gamma, 575
gcd, 575
gcdPolynomial, 575
hash, 575
increasePrecision, 575
integerDecode, 575
inv, 575
latex, 575
lcm, 575
log, 575
log10, 575
log2, 575
machineFraction, 575
mantissa, 575
max, 575
min, 575
multiEuclidean, 575
negative?, 575
norm, 575
nthRoot, 575
OMwrite, 575
one?, 575
order, 575
patternMatch, 575
pi, 575
polygamma, 575
positive?, 575
precision, 575
prime?, 575
principalIdeal, 575
rationalApproximation, 575
recip, 575
retract, 575
retractIfCan, 575
round, 575
sample, 575
sec, 575
sech, 575
sign, 575
sin, 575
sinh, 575
sizeLess?, 575
sqrt, 575
squareFree, 575
squareFreePart, 575
subtractIfCan, 575
tan, 575
tanh, 575
truncate, 575
unit?, 575
unitCanonical, 575
unitNormal, 575
wholePart, 575
zero?, 575
DFMAT, 586
-?, 587
?**?, 587
?*?, 587
?+?, 587
?-?, 587

?/?, 587
?=?, 587
?~=?, 587
#?, 587
antisymmetric?, 587
any?, 587
coerce, 587
column, 587
columnSpace, 587
copy, 587
count, 587
determinant, 587
diagonal?, 587
diagonalMatrix, 587
elt, 587
empty, 587
empty?, 587
eq?, 587
eval, 587
every?, 587
exquo, 587
fill, 587
hash, 587
horizConcat, 587
inverse, 587
latex, 587
less?, 587
listOfLists, 587
map, 587
matrix, 587
maxColIndex, 587
maxRowIndex, 587
member?, 587
members, 587
minColIndex, 587
minordet, 587
minRowIndex, 587
more?, 587
ncols, 587
new, 587
nrows, 587
nullity, 587
nullSpace, 587
parts, 587
pfaffian, 587
qelt, 587
qnew, 587
qsetelt, 587
rank, 587
row, 587
rowEchelon, 587
sample, 587
scalarMatrix, 587
setColumn, 587
setelt, 587
setRow, 587
setsubMatrix, 587
size?, 587
square?, 587
squareTop, 587
subMatrix, 587
swapColumns, 587
swapRows, 587
symmetric?, 587
transpose, 587
vertConcat, 587
zero, 587
DFVEC, 592
-?, 593
?<?, 593
?<=?, 593
?>?, 593
?>=?, 593
?*?, 593
?+?, 593
?-?, 593
?.?, 593
?=?, 593
?~=?, 593
#?, 593
any?, 593
coerce, 593
concat, 593
construct, 593
convert, 593
copy, 593
copyInto, 593
count, 593
cross, 593
delete, 593
dot, 593
elt, 593

empty, 593
empty?, 593
entries, 593
entry?, 593
eq?, 593
eval, 593
every?, 593
fill, 593
find, 593
first, 593
hash, 593
index?, 593
indices, 593
insert, 593
latex, 593
length, 593
less?, 593
magnitude, 593
map, 593
max, 593
maxIndex, 593
member?, 593
members, 593
merge, 593
min, 593
minIndex, 593
more?, 593
new, 593
outerProduct, 593
parts, 593
position, 593
qelt, 593
qnew, 593
qsetelt, 593
reduce, 593
remove, 593
removeDuplicates, 593
reverse, 593
sample, 593
select, 593
setelt, 593
size?, 593
sort, 593
sorted?, 593
swap, 593
zero, 593

DHMATRIX, 478
-?, 479
?**?, 479
?*?, 479
?+?, 479
?-?, 479
?/?, 479
?=?, 479
?~=?, 479
#?, 479
antisymmetric?, 479
any?, 479
coerce, 479
column, 479
copy, 479
count, 479
determinant, 479
diagonal?, 479
diagonalMatrix, 479
elt, 479
empty, 479
empty?, 479
eq?, 479
eval, 479
every?, 479
exquo, 479
fill, 479
hash, 479
horizConcat, 479
identity, 479
inverse, 479
latex, 479
less?, 479
listOfLists, 479
map, 479
matrix, 479
maxColIndex, 479
maxRowIndex, 479
member?, 479
members, 479
minColIndex, 479
minordet, 479
minRowIndex, 479
more?, 479
ncols, 479
new, 479

nrows, 479
nullity, 479
nullSpace, 479
parts, 479
qelt, 479
qsetelt, 479
rank, 479
rotatex, 479
rotatey, 479
rotatez, 479
row, 479
rowEchelon, 479
sample, 479
scalarMatrix, 479
scale, 479
setColumn, 479
setelt, 479
setRow, 479
setsubMatrix, 479
size?, 479
square?, 479
squareTop, 479
subMatrix, 479
swapColumns, 479
swapRows, 479
symmetric?, 479
translate, 479
transpose, 479
vertConcat, 479
zero, 479
diagonal
LSQM, 1424
SQMATRIX, 2515
diagonal?
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
diagonalMatrix
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
SQMATRIX, 2515
diagonalProduct
LSQM, 1424
SQMATRIX, 2515
diagonals
VIEW3D, 2679
dictionary
ALIST, 221
CCLASS, 368
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
INTABL, 1304
KAFILE, 1382
LIB, 1397
LMDICT, 1483
MSET, 1638
RESULT, 2267
ROUTINE, 2298
SET, 2338
STBL, 2418
STRTBL, 2578
TABLE, 2632
difference
CCLASS, 368
MSET, 1638
SET, 2338
DifferentialSparseMultivariatePolynomial, 528
differentialVariables
DSMP, 529
ODPOL, 1818
SDPOL, 2352
differentiate
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DIRPROD, 534
DMP, 560
DPMM, 540

DPMO, 545
DSMP, 529
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FPARFRAC, 1010
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPF, 1271
IR, 1343
ISUPS, 1279
LAUPOL, 1390
LSQM, 1424
MCMPLX, 1511
MINT, 1525
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODP, 1783
ODPOL, 1818
ODR, 1825
ODVAR, 1821
OMLO, 1773
OUTFORM, 1834
PACOFF, 2102
PADICRAT, 1852
PADICRC, 1857
PF, 2071
POLY, 2044
QUAT, 2133
RADFF, 2160
RADIX, 2172
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SDVAR, 2358
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
digamma
DFLOAT, 575
EXPR, 694
digit
CCLASS, 368
digit?
CHAR, 359
digits
BPADIC, 242
DFLOAT, 575
FLOAT, 879
IPADIC, 1262
MFLOAT, 1516

PADIC, 1847
dilog
EXPR, 694
dim
PALETTE, 1862
dimension
CLIF, 388
DIRPROD, 534
DPMM, 540
DPMO, 545
EQ, 661
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FNLA, 997
HDP, 1143
IDEAL, 2047
IFF, 1252
IPF, 1271
ODP, 1783
PACOFF, 2102
PACRAT, 2112
PF, 2071
POINT, 2026
RMATRIX, 2212
SHDP, 2476
dimensions
VIEW2d, 2739
VIEW3D, 2679
dimensionsOf
FT, 941
directory
FNAME, 780
DirectProduct, 534
directProduct
DIRPROD, 534
DPMM, 540
DPMO, 545
HDP, 1143
ODP, 1783
SHDP, 2476
DirectProductMatrixModule, 540
DirectProductModule, 544
directSum
LODO, 1437
LODO1, 1447
LODO2, 1459
DirichletRing, 551
DIRPROD, 534
-?, 534
?<?, 534
?<=?, 534
?>?, 534
?>=?, 534
?**?, 534
?*?, 534
?+?, 534
?-?, 534
?.?, 534
?/?, 534
?=?, 534
?^?, 534
?~=?, 534
#?, 534
0, 534
1, 534
abs, 534
any?, 534
characteristic, 534
coerce, 534
copy, 534
count, 534
D, 534
differentiate, 534
dimension, 534
directProduct, 534
dot, 534
elt, 534
empty, 534
empty?, 534
entries, 534
entry?, 534
eq?, 534
eval, 534
every?, 534
fill, 534

first, 534
hash, 534
index, 534
index?, 534
indices, 534
latex, 534
less?, 534
lookup, 534
map, 534
max, 534
maxIndex, 534
member?, 534
members, 534
min, 534
minIndex, 534
more?, 534
negative?, 534
one?, 534
parts, 534
positive?, 534
qelt, 534
qsetelt, 534
random, 534
recip, 534
reducedSystem, 534
retract, 534
retractIfCan, 534
sample, 534
setelt, 534
sign, 534
size, 534
size?, 534
subtractIfCan, 534
sup, 534
swap, 534
unitVector, 534
zero?, 534
DIRRING, 551
-?, 551
? =?, 551
?**?, 551
?*?, 551
?+?, 551
?-?, 551
?.?, 551
?=?, 551
?^?, 551
0, 551
1, 551
additive?, 551
associates?, 551
characteristic, 551
coerce, 551
exquo, 551
hash, 551
latex, 551
multiplicative?, 551
one?, 551
recip, 551
sample, 551
subtractIfCan, 551
unit?, 551
unitCanonical, 551
unitNormal, 551
zero?, 551
zeta, 551
discreteLog
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PACRAT, 2112
PF, 2071
RADFF, 2160
SAE, 2368
discriminant
ALGFF, 28
COMPLEX, 406
DMP, 560
DSMP, 529
GDMP, 1022

HDMP, 1150
MCMPLX, 1511
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
RADFF, 2160
SAE, 2368
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
display
BOP, 258
DBASE, 442
FORMULA, 2312
HTMLFORM, 1122
ICARD, 1163
MMLFORM, 1571
TEX, 2645
displayAsGF
GOPT0, 1081
displayKind
GOPT, 1075
distance
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
distinguishedRootsOf
PACOFF, 2102
PACRAT, 2112
distribute
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
DistributedMultivariatePolynomial, 559
DIV, 563
-?, 563
?<=?, 563
?*?, 563
?+?, 563
?-?, 563
?=?, 563
?~=?, 563
0, 563
coefficient, 563
coerce, 563
collect, 563
concat, 563
degree, 563
divOfPole, 563
divOfZero, 563
effective?, 563
hash, 563
head, 563
highCommonTerms, 563
incr, 563
latex, 563
mapCoef, 563
mapGen, 563
nthCoef, 563
nthFactor, 563
reductum, 563
retract, 563
retractIfCan, 563
sample, 563
size, 563
split, 563
subtractIfCan, 563
supp, 563
suppOfPole, 563
suppOfZero, 563
terms, 563
zero?, 563
divide

ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FMONOID, 991
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
divideExponents
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
Divisor, 563
divisor
FDIV, 783
HELLFDIV, 1153
divOfPole
DIV, 563
divOfZero
DIV, 563
DLIST, 447
?<?, 448
?<=?, 448
?>?, 448
?>=?, 448
?.?, 448
?.count, 448
?.first, 448
?.last, 448
?.rest, 448

?.sort, 448
?.unique, 448
?.value, 448
?=?, 448
?~=?, 448
#?, 448
any?, 448
child?, 448
children, 448
coerce, 448
concat, 448
construct, 448
convert, 448
copy, 448
copyInto, 448
count, 448
cycleEntry, 448
cycleLength, 448
cycleSplit, 448
cycleTail, 448
cyclic?, 448
datalist, 448
delete, 448
distance, 448
elt, 448
empty, 448
empty?, 448
entries, 448
entry?, 448
eq?, 448
eval, 448
every?, 448
explicitlyFinite?, 448
fill, 448
find, 448
first, 448
hash, 448
index?, 448
indices, 448
insert, 448
last, 448
latex, 448
leaf?, 448
leaves, 448
less?, 448
list, 448
map, 448
max, 448
maxIndex, 448
member?, 448
members, 448
merge, 448
min, 448
minIndex, 448
more?, 448
new, 448
node?, 448
nodes, 448
parts, 448
position, 448
possiblyInfinite?, 448
qelt, 448
qsetelt, 448
reduce, 448
remove, 448
removeDuplicates, 448
rest, 448
reverse, 448
sample, 448
second, 448
select, 448
setchildren, 448
setelt, 448
setfirst, 448
setlast, 448
setrest, 448
setvalue, 448
size?, 448
sort, 448
sorted?, 448
split, 448
swap, 448
tail, 448
third, 448
value, 448
DMP, 559
-?, 560
?<?, 560
?<=?, 560
?>?, 560
?>=?, 560
?**?, 560

?*?, 560
?+?, 560
?-?, 560
?/?, 560
?=?, 560
?^?, 560
?~=?, 560
0, 560
1, 560
associates?, 560
binomThmExpt, 560
characteristic, 560
charthRoot, 560
coefficient, 560
coefficients, 560
coerce, 560
conditionP, 560
convert, 560
D, 560
degree, 560
differentiate, 560
discriminant, 560
eval, 560
exquo, 560
factor, 560
factorPolynomial, 560
factorSquareFreePolynomial, 560
gcd, 560
gcdPolynomial, 560
ground, 560
ground?, 560
hash, 560
isExpt, 560
isPlus, 560
isTimes, 560
latex, 560
lcm, 560
leadingCoefficient, 560
leadingMonomial, 560
mainVariable, 560
map, 560
mapExponents, 560
max, 560
min, 560
minimumDegree, 560
monicDivide, 560
monomial, 560
monomial?, 560
monomials, 560
multivariate, 560
numberOfMonomials, 560
one?, 560
patternMatch, 560
pomopo, 560
prime?, 560
primitiveMonomials, 560
primitivePart, 560
recip, 560
reducedSystem, 560
reductum, 560
reorder, 560
resultant, 560
retract, 560
retractIfCan, 560
sample, 560
solveLinearPolynomialEquation, 560
squareFree, 560
squareFreePart, 560
squareFreePolynomial, 560
subtractIfCan, 560
totalDegree, 560
unit?, 560
unitCanonical, 560
unitNormal, 560
univariate, 560
variables, 560
zero?, 560
dom
ANY, 50
domainOf
ANY, 50
dominantTerm
UPXSSING, 2819
dot
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DPMM, 540
DPMO, 545
HDP, 1143
IVECTOR, 1229
ODP, 1783

OUTFORM, 1834
POINT, 2026
SHDP, 2476
VECTOR, 2878
double?
FST, 933
doubleComplex?
FST, 933
DoubleFloat, 574
doubleFloatFormat
DFLOAT, 575
DoubleFloatMatrix, 586
DoubleFloatVector, 592
DPMM, 540
-?, 540
?<?, 540
?<=?, 540
?>?, 540
?>=?, 540
?**?, 540
?*?, 540
?-?, 540
?.?, 540
?/?, 540
?=?, 540
?^?, 540
?~=?, 540
#?, 540
0, 540
1, 540
abs, 540
any?, 540
characteristic, 540
coerce, 540
copy, 540
count, 540
D, 540
differentiate, 540
dimension, 540
directProduct, 540
dot, 540
elt, 540
empty, 540
empty?, 540
entries, 540
entry?, 540
eq?, 540
eval, 540
every?, 540
fill, 540
first, 540
hash, 540
index, 540
index?, 540
indices, 540
latex, 540
less?, 540
lookup, 540
map, 540
max, 540
maxIndex, 540
member?, 540
members, 540
min, 540
minIndex, 540
more?, 540
negative?, 540
one?, 540
parts, 540
positive?, 540
qelt, 540
qsetelt, 540
random, 540
recip, 540
reducedSystem, 540
retract, 540
retractIfCan, 540
sample, 540
setelt, 540
sign, 540
size, 540
size?, 540
subtractIfCan, 540
sup, 540
swap, 540
unitVector, 540
zero?, 540
DPMO, 544
-?, 545
?<?, 545
?<=?, 545
?>?, 545

?>=?, 545
?**?, 545
?*?, 545
?+?, 545
?-?, 545
?.?, 545
?/?, 545
?=?, 545
?^?, 545
?~=?, 545
#?, 545
0, 545
1, 545
abs, 545
any?, 545
characteristic, 545
coerce, 545
copy, 545
count, 545
D, 545
differentiate, 545
dimension, 545
directProduct, 545
dot, 545
elt, 545
empty, 545
empty?, 545
entries, 545
entry?, 545
eq?, 545
eval, 545
every?, 545
fill, 545
first, 545
hash, 545
index, 545
index?, 545
indices, 545
latex, 545
less?, 545
lookup, 545
map, 545
max, 545
maxIndex, 545
member?, 545
members, 545
min, 545
minIndex, 545
more?, 545
negative?, 545
one?, 545
parts, 545
positive?, 545
qelt, 545
qsetelt, 545
random, 545
recip, 545
reducedSystem, 545
retract, 545
retractIfCan, 545
sample, 545
setelt, 545
sign, 545
size, 545
size?, 545
subtractIfCan, 545
sup, 545
swap, 545
unitVector, 545
zero?, 545
DrawOption, 595
drawStyle
VIEW3D, 2679
drift
SD, 2540
DROPT, 595
?=?, 596
?~=?, 596
adaptive, 596
clip, 596
coerce, 596
colorFunction, 596
coord, 596
coordinates, 596
curveColor, 596
hash, 596
latex, 596
option, 596
option?, 596
pointColor, 596
range, 596
ranges, 596

space, 596
style, 596
title, 596
toScale, 596
tubePoints, 596
tubeRadius, 596
unit, 596
var1Steps, 596
var2Steps, 596
viewpoint, 596
DSMP, 528
-?, 529
?<?, 529
?<=?, 529
?>?, 529
?>=?, 529
?**?, 529
?*?, 529
?+?, 529
?-?, 529
?/?, 529
?=?, 529
?^?, 529
?~=?, 529
0, 529
1, 529
associates?, 529
binomThmExpt, 529
characteristic, 529
charthRoot, 529
coefficient, 529
coefficients, 529
coerce, 529
conditionP, 529
content, 529
convert, 529
D, 529
degree, 529
differentialVariables, 529
differentiate, 529
discriminant, 529
eval, 529
exquo, 529
factor, 529
factorPolynomial, 529
factorSquareFreePolynomial, 529
gcd, 529
gcdPolynomial, 529
ground, 529
ground?, 529
hash, 529
initial, 529
isExpt, 529
isobaric?, 529
isPlus, 529
isTimes, 529
latex, 529
lcm, 529
leader, 529
leadingCoefficient, 529
leadingMonomial, 529
makeVariable, 529
map, 529
mapExponents, 529
max, 529
min, 529
minimumDegree, 529
monicDivide, 529
monomial, 529
monomial?, 529
monomials, 529
multivariate, 529
numberOfMonomials, 529
one?, 529
order, 529
patternMatch, 529
pomopo, 529
prime?, 529
primitiveMonomials, 529
primitivePart, 529
recip, 529
reducedSystem, 529
reductum, 529
resultant, 529
retract, 529
retractIfCan, 529
sample, 529
separant, 529
solveLinearPolynomialEquation, 529
squareFree, 529
squareFreePart, 529
squareFreePolynomial, 529

subtractIfCan, 529
totalDegree, 529
unit?, 529
unitCanonical, 529
unitNormal, 529
univariate, 529
variables, 529
weight, 529
weights, 529
zero?, 529
DSTREE, 522
?.value, 522
?=?, 522
?~=?, 522
#?, 522
any?, 522
child?, 522
children, 522
coerce, 522
copy, 522
count, 522
cyclic?, 522
distance, 522
empty, 522
empty?, 522
encode, 522
eq?, 522
eval, 522
every?, 522
fullOut, 522
fullOutput, 522
hash, 522
latex, 522
leaf?, 522
leaves, 522
less?, 522
map, 522
member?, 522
members, 522
more?, 522
node?, 522
nodes, 522
parts, 522
sample, 522
setchildren, 522
setelt, 522
setvalue, 522
size?, 522
tree, 522
value, 522
duplicates
LMDICT, 1483
MSET, 1638
duplicates?
LMDICT, 1483

e
CLIF, 388
E04DGFA, 717
?=?, 717
?~=?, 717
coerce, 717
hash, 717
latex, 717
measure, 717
numericalOptimization, 717
e04dgfAnnaType, 717
E04FDFA, 720
?=?, 720
?~=?, 720
coerce, 720
hash, 720
latex, 720
measure, 720
numericalOptimization, 720
e04fdfAnnaType, 720
E04GCFA, 724
?=?, 724
?~=?, 724
coerce, 724
hash, 724
latex, 724
measure, 724
numericalOptimization, 724
e04gcfAnnaType, 724
E04JAFA, 728
?=?, 728
?~=?, 728
coerce, 728
hash, 728
latex, 728
measure, 728

numericalOptimization, 728
e04jafAnnaType, 728
E04MBFA, 731
?=?, 732
?~=?, 732
coerce, 732
hash, 732
latex, 732
measure, 732
numericalOptimization, 732
e04mbfAnnaType, 731
E04NAFA, 735
?=?, 735
?~=?, 735
coerce, 735
hash, 735
latex, 735
measure, 735
numericalOptimization, 735
e04nafAnnaType, 735
E04UCFA, 738
?=?, 739
?~=?, 739
coerce, 739
hash, 739
latex, 739
measure, 739
numericalOptimization, 739
e04ucfAnnaType, 738
EAB, 713
?<?, 713
?<=?, 713
?>?, 713
?>=?, 713
?=?, 713
?~=?, 713
coerce, 713
degree, 713
exponents, 713
hash, 713
latex, 713
max, 713
min, 713
Nul, 713
effective?
DIV, 563
Ei
EXPR, 694
elem?
IR, 1343
element?
IDEAL, 2047
elements
SETMN, 2344
elliptic
ALGFF, 28
RADFF, 2160
elt
ALGFF, 28
ALIST, 221
AN, 35
ARRAY1, 1740
ARRAY2, 2732
BITS, 299
CARTEN, 342
CDFMAT, 413
CDFVEC, 419
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
EXPR, 694
FARRAY, 856
FEXPR, 917
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229

KAFILE, 1382
LIB, 1397
LIST, 1472
LSQM, 1424
M3D, 2672
MATRIX, 1591
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODP, 1783
PATTERN, 1894
POINT, 2026
PRIMARR, 2075
RADFF, 2160
REF, 2215
RESULT, 2267
RMATRIX, 2212
ROUTINE, 2298
RULE, 2271
RULESET, 2309
SHDP, 2476
SQMATRIX, 2515
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUP, 2435
SUPEXPR, 2449
TABLE, 2632
U32VEC, 2869
UP, 2795
VECTOR, 2878
empty
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
OUTFORM, 1834
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QALGSET, 2123
QUEUE, 2150
REGSET, 2252
RESULT, 2267

RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SYMS, 2665
SYMTAB, 2616
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
empty?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QALGSET, 2123
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578

TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
EMR, 672
-?, 672
?**?, 672
?*?, 672
?+?, 672
?-?, 672
?.?, 672
?=?, 672
?^?, 672
?~=?, 672
?quo?, 672
?rem?, 672
0, 672
1, 672
associates?, 672
characteristic, 672
coerce, 672
divide, 672
euclideanSize, 672
expressIdealMember, 672
exQuo, 672
exquo, 672
extendedEuclidean, 672
gcd, 672
gcdPolynomial, 672
hash, 672
inv, 672
latex, 672
lcm, 672
modulus, 672
multiEuclidean, 672
one?, 672
principalIdeal, 672
recip, 672
reduce, 672
sample, 672
sizeLess?, 672
subtractIfCan, 672
unit?, 672
unitCanonical, 672
unitNormal, 672
zero?, 672
encode
DSTREE, 522
endOfFile?
TEXTFILE, 2661
endSubProgram
SYMS, 2665
enterPointData
SPACE3, 2701
entries
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
INTFTBL, 1339
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578

TABLE, 2632
U32VEC, 2869
VECTOR, 2878
entry
INTFTBL, 1339
entry?
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
enumerate
SETMN, 2344
epilogue
FORMULA, 2312
TEX, 2645
EQ, 661
-?, 661
?**?, 661
?*?, 661
?+?, 661
?-?, 661
?/?, 661
?=?, 661
?^?, 661
?~=?, 661
0, 661
1, 661
characteristic, 661
coerce, 661
commutator, 661
conjugate, 661
D, 661
differentiate, 661
dimension, 661
equation, 661
eval, 661
factorAndSplit, 661
hash, 661
inv, 661
latex, 661
leftOne, 661
leftZero, 661
lhs, 661
map, 661
one?, 661
recip, 661
rhs, 661
rightOne, 661
rightZero, 661
sample, 661
subst, 661
subtractIfCan, 661
swap, 661
SWITCH, 2597
zero?, 661
eq
INFORM, 1311
SEX, 2360

SEXOF, 2363
eq?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
EqTable, 669
EQTBL, 669
?.?, 669
?=?, 669
?~=?, 669
#?, 669
any?, 669
bag, 669
coerce, 669
construct, 669
convert, 669
copy, 669
count, 669
dictionary, 669
elt, 669
empty, 669
empty?, 669

entries, 669
entry?, 669
eq?, 669
eval, 669
every?, 669
extract, 669
fill, 669
find, 669
first, 669
hash, 669
index?, 669
indices, 669
insert, 669
inspect, 669
key?, 669
keys, 669
latex, 669
less?, 669
map, 669
maxIndex, 669
member?, 669
members, 669
minIndex, 669
more?, 669
parts, 669
qelt, 669
qsetelt, 669
reduce, 669
remove, 669
removeDuplicates, 669
sample, 669
search, 669
select, 669
setelt, 669
size?, 669
swap, 669
table, 669
equality
BOP, 258
Equation, 661
equation
EQ, 661
QEQUAT, 2135
SD, 2540
SEGBIND, 2330
erf
EXPR, 694
errorInfo
OMERR, 1758
errorKind
OMERR, 1758
escape
CHAR, 359
EuclideanModularRing, 672
euclideanSize
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606

MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
eval
ALIST, 221
AN, 35
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BINARY, 277
BITS, 299
BPADICRT, 247
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
COMPLEX, 406
DECIMAL, 453
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
DSTREE, 522
EQ, 661
EQTBL, 669
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FARRAY, 856
FEXPR, 917
FR, 756
FRAC, 956
GDMP, 1022
GPOLSET, 1044
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
ISUPS, 1279
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483

LPOLY, 1415
LSQM, 1424
M3D, 2672
MATRIX, 1591
MCMPLX, 1511
MODMON, 1600
MOEBIUS, 1622
MPOLY, 1650
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
PENDTREE, 1911
PERM, 1916
POINT, 2026
POLY, 2044
PRIMARR, 2075
QUAT, 2133
QUEUE, 2150
RADIX, 2172
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SDPOL, 2352
SET, 2338
SHDP, 2476
SMP, 2391
SMTS, 2409
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TABLE, 2632
TREE, 2710
TS, 2639
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
VECTOR, 2878
WUTSET, 2895
evaluate
MODOP, 1615, 1771
evaluateInverse
MODOP, 1615, 1771
even?
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
INT, 1330
MINT, 1525
MYEXPR, 1656
PERM, 1916
ROMAN, 2293
SINT, 2380
evenlambert
UFPS, 2757
UTS, 2844
UTSZ, 2854
every?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291

BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
exactQuotient
NSMP, 1681
excepCoord
BLHN, 301
BLQT, 304
excpDivV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
exists?
FNAME, 780
EXIT, 677
?=?, 677
?~=?, 677
coerce, 677
hash, 677
latex, 677
Exit, 677
exp
ANTISYM, 40
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061

INTRVL, 1352
LEXP, 1403
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
XPBWPOLYL, 2925
exp1
DFLOAT, 575
FLOAT, 879
expand
FR, 756
SEG, 2325
UNISEG, 2863
XPOLY, 2936
XRPOLY, 2951
EXPEXPAN, 681
-?, 682
?<?, 682
?<=?, 682
?>?, 682
?>=?, 682
?**?, 682
?*?, 682
?+?, 682
?-?, 682
?.?, 682
?/?, 682
?=?, 682
?^?, 682
?~=?, 682
?quo?, 682
?rem?, 682
0, 682
1, 682
abs, 682
associates?, 682
ceiling, 682
characteristic, 682
charthRoot, 682
coerce, 682
conditionP, 682
convert, 682
D, 682
denom, 682
denominator, 682
differentiate, 682
divide, 682
euclideanSize, 682
eval, 682
expressIdealMember, 682
exquo, 682
extendedEuclidean, 682
factor, 682
factorPolynomial, 682
factorSquareFreePolynomial, 682
floor, 682
fractionPart, 682
gcd, 682
gcdPolynomial, 682
hash, 682
init, 682
inv, 682
latex, 682
lcm, 682
limitPlus, 682
map, 682
max, 682
min, 682
multiEuclidean, 682
negative?, 682
nextItem, 682
numer, 682
numerator, 682
one?, 682
patternMatch, 682
positive?, 682
prime?, 682
principalIdeal, 682
random, 682
recip, 682
reducedSystem, 682

retract, 682
retractIfCan, 682
sample, 682
sign, 682
sizeLess?, 682
solveLinearPolynomialEquation, 682
squareFree, 682
squareFreePart, 682
squareFreePolynomial, 682
subtractIfCan, 682
unit?, 682
unitCanonical, 682
unitNormal, 682
wholePart, 682
zero?, 682
explicitEntries?
NSDPS, 1670
STREAM, 2550
explicitlyEmpty?
NSDPS, 1670
STREAM, 2550
explicitlyFinite?
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
exponent
DFLOAT, 575
EXPUPXS, 710
FLOAT, 879
FR, 756
MFLOAT, 1516
MODMONOM, 1612
exponential
EXPUPXS, 710
ExponentialExpansion, 681
ExponentialOfUnivariatePuiseuxSeries, 709
exponentialOrder
EXPUPXS, 710
exponents
EAB, 713
EXPR, 693
-?, 694
?<?, 694
?<=?, 694
?>?, 694
?>=?, 694
?**?, 694
?*?, 694
?+?, 694
?-?, 694
?/?, 694
?=?, 694
?^?, 694
?~=?, 694
?quo?, 694
?rem?, 694
0, 694
1, 694
abs, 694
acos, 694
acosh, 694
acot, 694
acoth, 694
acsc, 694
acsch, 694
airyAi, 694
airyBi, 694
applyQuote, 694
asec, 694
asech, 694
asin, 694
asinh, 694
associates?, 694
atan, 694
atanh, 694
belong?, 694
besselI, 694
besselJ, 694
besselK, 694
besselY, 694
Beta, 694
binomial, 694
box, 694
characteristic, 694
charthRoot, 694
Ci, 694
coerce, 694
commutator, 694
conjugate, 694

convert, 694
cos, 694
cosh, 694
cot, 694
coth, 694
csc, 694
csch, 694
D, 694
definingPolynomial, 694
denom, 694
denominator, 694
differentiate, 694
digamma, 694
dilog, 694
distribute, 694
divide, 694
Ei, 694
elt, 694
erf, 694
euclideanSize, 694
eval, 694
even?, 694
exp, 694
expressIdealMember, 694
exquo, 694
extendedEuclidean, 694
factor, 694
factorial, 694
factorials, 694
factorPolynomial, 694
freeOf?, 694
Gamma, 694
gcd, 694
gcdPolynomial, 694
ground, 694
ground?, 694
hash, 694
height, 694
integral, 694
inv, 694
is?, 694
isExpt, 694
isMult, 694
isPlus, 694
isPower, 694
isTimes, 694
kernel, 694
kernels, 694
latex, 694
lcm, 694
li, 694
log, 694
mainKernel, 694
map, 694
max, 694
min, 694
minPoly, 694
multiEuclidean, 694
nthRoot, 694
number?, 694
numer, 694
numerator, 694
odd?, 694
one?, 694
operator, 694
operators, 694
paren, 694
patternMatch, 694
permutation, 694
pi, 694
polygamma, 694
prime?, 694
principalIdeal, 694
product, 694
recip, 694
reduce, 694
reducedSystem, 694
retract, 694
retractIfCan, 694
rootOf, 694
rootsOf, 694
sample, 694
sec, 694
sech, 694
Si, 694
simplifyPower, 694
sin, 694
sinh, 694
sizeLess?, 694
sqrt, 694
squareFree, 694
squareFreePart, 694

squareFreePolynomial, 694
subst, 694
subtractIfCan, 694
summation, 694
tan, 694
tanh, 694
tower, 694
unit?, 694
unitCanonical, 694
unitNormal, 694
univariate, 694
variables, 694
zero?, 694
zeroOf, 694
zerosOf, 694
expr
INFORM, 1311
SEX, 2360
SEXOF, 2363
expressIdealMember
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
Expression, 693
exprex
HTMLFORM, 1122
MMLFORM, 1571
EXPUPXS, 709
-?, 710
?<?, 710

?<=?, 710
?>?, 710
?>=?, 710
?**?, 710
?*?, 710
?+?, 710
?-?, 710
?.?, 710
?/?, 710
?=?, 710
?^?, 710
?~=?, 710
?quo?, 710
?rem?, 710
0, 710
1, 710
acos, 710
acosh, 710
acot, 710
acoth, 710
acsc, 710
acsch, 710
approximate, 710
asec, 710
asech, 710
asin, 710
asinh, 710
associates?, 710
atan, 710
atanh, 710
center, 710
characteristic, 710
charthRoot, 710
coefficient, 710
coerce, 710
complete, 710
cos, 710
cosh, 710
cot, 710
coth, 710
csc, 710
csch, 710
D, 710
degree, 710
differentiate, 710
divide, 710
euclideanSize, 710
eval, 710
exp, 710
exponent, 710
exponential, 710
exponentialOrder, 710
expressIdealMember, 710
exquo, 710
extend, 710
extendedEuclidean, 710
factor, 710
gcd, 710
gcdPolynomial, 710
hash, 710
integrate, 710
inv, 710
latex, 710
lcm, 710
leadingCoefficient, 710
leadingMonomial, 710
log, 710
map, 710
max, 710
min, 710
monomial, 710
monomial?, 710
multiEuclidean, 710
multiplyExponents, 710
nthRoot, 710
one?, 710
order, 710
pi, 710
pole?, 710
prime?, 710
principalIdeal, 710
recip, 710
reductum, 710
sample, 710
sec, 710
sech, 710
series, 710
sin, 710
sinh, 710
sizeLess?, 710
sqrt, 710
squareFree, 710

squareFreePart, 710
subtractIfCan, 710
tan, 710
tanh, 710
terms, 710
truncate, 710
unit?, 710
unitCanonical, 710
unitNormal, 710
variable, 710
variables, 710
zero?, 710
exQuo
EMR, 672
MODFIELD, 1606
MODRING, 1609
exquo
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
CDFMAT, 413
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DFMAT, 587
DHMATRIX, 479
DIRRING, 551
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
IMATRIX, 1208
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
ORESUP, 2460
OREUP, 2840
OUTFORM, 1834
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880

POLY, 2044
PR, 2058
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RMATRIX, 2212
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
ExtAlgBasis, 713
extDegree
PACOFF, 2102
PACRAT, 2112
extend
BPADIC, 242
CONTFRAC, 432
EXPUPXS, 710
GSERIES, 1061
GTSET, 1054
IPADIC, 1262
ISUPS, 1279
NSDPS, 1670
PADIC, 1847
POINT, 2026
REGSET, 2252
RGCHAIN, 2221
SMTS, 2409
SREGSET, 2502
STREAM, 2550
SULS, 2425
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
WUTSET, 2895
extendedEuclidean
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330

IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
extendedResultant
NSUP, 1696
extendedSubResultantGcd
NSMP, 1681
NSUP, 1696
extendIfCan
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
extension
FNAME, 780
extensionDegree
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PACOFF, 2102
PACRAT, 2112
PF, 2071
exteriorDifferential
DERHAM, 517
external?
FT, 941
externalList
SYMTAB, 2616
extractClosed
SUBSPACE, 2582
extractIndex
SUBSPACE, 2582
extractPoint
SUBSPACE, 2582
extractProperty
SUBSPACE, 2582
extractSplittingLeaf
SPLTREE, 2485
eyeDistance
VIEW3D, 2679

factor
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560

DSMP, 529
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPF, 1271
LWORD, 1500
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
factorAndSplit
EQ, 661
Factored, 756
factorial
EXPR, 694
INT, 1330
MINT, 1525
MYEXPR, 1656
ROMAN, 2293
SINT, 2380
factorials
EXPR, 694
MYEXPR, 1656
factorList
FR, 756
factorPolynomial
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694
FRAC, 956
GDMP, 1022
HDMP, 1150
HEXADEC, 1113
MCMPLX, 1511

MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
POLY, 2044
RADIX, 2172
SDPOL, 2352
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
factors
FGROUP, 980
FMONOID, 991
FR, 756
OFMONOID, 1795
factorsOfCyclicGroupSize
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PF, 2071
RADFF, 2160
SAE, 2368
factorSquareFreePolynomial
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DMP, 560
DSMP, 529
EXPEXPAN, 682
FRAC, 956
GDMP, 1022
HDMP, 1150
HEXADEC, 1113
MCMPLX, 1511
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
POLY, 2044
RADIX, 2172
SDPOL, 2352
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
FAGROUP, 974
-?, 975
?<?, 975
?<=?, 975
?>?, 975
?>=?, 975
?*?, 975
?+?, 975
?-?, 975
?=?, 975
?~=?, 975
0, 975
coefficient, 975
coerce, 975
hash, 975
highCommonTerms, 975
latex, 975
mapCoef, 975
mapGen, 975

max, 975
min, 975
nthCoef, 975
nthFactor, 975
retract, 975
retractIfCan, 975
sample, 975
size, 975
subtractIfCan, 975
terms, 975
zero?, 975
failed
PATLRES, 1904
PATRES, 1906
failed?
PATLRES, 1904
PATRES, 1906
false
BOOLEAN, 307
FAMONOID, 977
?*?, 978
?+?, 978
?=?, 978
?~=?, 978
0, 978
coefficient, 978
coerce, 978
hash, 978
highCommonTerms, 978
latex, 978
mapCoef, 978
mapGen, 978
nthCoef, 978
nthFactor, 978
retract, 978
retractIfCan, 978
sample, 978
size, 978
subtractIfCan, 978
terms, 978
zero?, 978
FARRAY, 856
?<?, 856
?<=?, 856
?>?, 856
?>=?, 856
?.?, 856
?=?, 856
?~=?, 856
#?, 856
any?, 856
coerce, 856
concat, 856
construct, 856
convert, 856
copy, 856
copyInto, 856
count, 856
delete, 856
elt, 856
empty, 856
empty?, 856
entries, 856
entry?, 856
eq?, 856
eval, 856
every?, 856
fill, 856
find, 856
first, 856
flexibleArray, 856
hash, 856
index?, 856
indices, 856
insert, 856
latex, 856
less?, 856
map, 856
max, 856
maxIndex, 856
member?, 856
members, 856
merge, 856
min, 856
minIndex, 856
more?, 856
new, 856
parts, 856
physicalLength, 856
position, 856
qelt, 856
qsetelt, 856

reduce, 856
remove, 856
removeDuplicates, 856
reverse, 856
sample, 856
select, 856
setelt, 856
shrinkable, 856
size?, 856
sort, 856
sorted?, 856
swap, 856
FC, 901
?=?, 902
? =?, 902
assign, 902
block, 902
call, 902
code, 902
coerce, 902
comment, 902
common, 902
cond, 902
continue, 902
forLoop, 902
getCode, 902
goto, 902
hash, 902
latex, 902
operation, 902
printCode, 902
printStatement, 902
repeatUntilLoop, 902
returns, 902
save, 902
setLabelValue, 902
stop, 902
whileLoop, 902
FCOMP, 945
?<?, 945
?<=?, 945
?>?, 945
?>=?, 945
?=?, 945
?~=?, 945
argument, 945
coerce, 945
cos, 945
hash, 945
latex, 945
max, 945
min, 945
sin, 945
sin?, 945
FDIV, 783
-?, 783
?*?, 783
?+?, 783
?-?, 783
?=?, 783
?~=?, 783
0, 783
coerce, 783
decompose, 783
divisor, 783
finiteBasis, 783
generator, 783
hash, 783
ideal, 783
latex, 783
lSpaceBasis, 783
principal?, 783
reduce, 783
sample, 783
subtractIfCan, 783
zero?, 783
FEXPR, 917
-?, 917
?<?, 917
?<=?, 917
?>?, 917
?>=?, 917
?**?, 917
?*?, 917
?+?, 917
?-?, 917
?=?, 917
?^?, 917
?~=?, 917
0, 917
1, 917
abs, 917

acos, 917
asin, 917
atan, 917
belong?, 917
box, 917
characteristic, 917
coerce, 917
cos, 917
cosh, 917
D, 917
definingPolynomial, 917
differentiate, 917
distribute, 917
elt, 917
eval, 917
even?, 917
exp, 917
freeOf?, 917
hash, 917
height, 917
is?, 917
kernel, 917
kernels, 917
latex, 917
log, 917
log10, 917
mainKernel, 917
map, 917
max, 917
min, 917
minPoly, 917
odd?, 917
one?, 917
operator, 917
operators, 917
paren, 917
pi, 917
recip, 917
retract, 917
retractIfCan, 917
sample, 917
sin, 917
sinh, 917
sqrt, 917
subst, 917
subtractIfCan, 917
tan, 917
tanh, 917
tower, 917
useNagFunctions, 917
variables, 917
zero?, 917
FF, 789
-?, 790
?**?, 790
?*?, 790
?+?, 790
?-?, 790
?/?, 790
?=?, 790
?^?, 790
?~=?, 790
?quo?, 790
?rem?, 790
0, 790
1, 790
algebraic?, 790
associates?, 790
basis, 790
characteristic, 790
charthRoot, 790
coerce, 790
conditionP, 790
coordinates, 790
createNormalElement, 790
createPrimitiveElement, 790
D, 790
definingPolynomial, 790
degree, 790
differentiate, 790
dimension, 790
discreteLog, 790
divide, 790
euclideanSize, 790
expressIdealMember, 790
exquo, 790
extendedEuclidean, 790
extensionDegree, 790
factor, 790
factorsOfCyclicGroupSize, 790
Frobenius, 790
gcd, 790

gcdPolynomial, 790
generator, 790
hash, 790
index, 790
inGroundField?, 790
init, 790
inv, 790
latex, 790
lcm, 790
linearAssociatedExp, 790
linearAssociatedLog, 790
linearAssociatedOrder, 790
lookup, 790
minimalPolynomial, 790
multiEuclidean, 790
nextItem, 790
norm, 790
normal?, 790
normalElement, 790
one?, 790
order, 790
prime?, 790
primeFrobenius, 790
primitive?, 790
primitiveElement, 790
principalIdeal, 790
random, 790
recip, 790
representationType, 790
represents, 790
retract, 790
retractIfCan, 790
sample, 790
size, 790
sizeLess?, 790
squareFree, 790
squareFreePart, 790
subtractIfCan, 790
tableForDiscreteLogarithm, 790
trace, 790
transcendenceDegree, 790
transcendent?, 790
unit?, 790
unitCanonical, 790
unitNormal, 790
zero?, 790

FFCG, 794
-?, 795
?**?, 795
?*?, 795
?+?, 795
?-?, 795
?/?, 795
?=?, 795
?^?, 795
?~=?, 795
?quo?, 795
?rem?, 795
0, 795
1, 795
algebraic?, 795
associates?, 795
basis, 795
characteristic, 795
charthRoot, 795
coerce, 795
conditionP, 795
coordinates, 795
createNormalElement, 795
createPrimitiveElement, 795
D, 795
definingPolynomial, 795
degree, 795
differentiate, 795
dimension, 795
discreteLog, 795
divide, 795
euclideanSize, 795
expressIdealMember, 795
exquo, 795
extendedEuclidean, 795
extensionDegree, 795
factor, 795
factorsOfCyclicGroupSize, 795
Frobenius, 795
gcd, 795
gcdPolynomial, 795
generator, 795
getZechTable, 795
hash, 795
index, 795
inGroundField?, 795

init, 795
inv, 795
latex, 795
lcm, 795
linearAssociatedExp, 795
linearAssociatedLog, 795
linearAssociatedOrder, 795
lookup, 795
minimalPolynomial, 795
multiEuclidean, 795
nextItem, 795
norm, 795
normal?, 795
normalElement, 795
one?, 795
order, 795
prime?, 795
primeFrobenius, 795
primitive?, 795
primitiveElement, 795
principalIdeal, 795
random, 795
recip, 795
representationType, 795
represents, 795
retract, 795
retractIfCan, 795
sample, 795
size, 795
sizeLess?, 795
squareFree, 795
squareFreePart, 795
subtractIfCan, 795
tableForDiscreteLogarithm, 795
trace, 795
transcendenceDegree, 795
transcendent?, 795
unit?, 795
unitCanonical, 795
unitNormal, 795
zero?, 795
FFCGP, 804
-?, 805
?**?, 805
?*?, 805
?+?, 805
?-?, 805
?/?, 805
?=?, 805
?^?, 805
?~=?, 805
?quo?, 805
?rem?, 805
0, 805
1, 805
algebraic?, 805
associates?, 805
basis, 805
characteristic, 805
charthRoot, 805
coerce, 805
conditionP, 805
coordinates, 805
createNormalElement, 805
createPrimitiveElement, 805
D, 805
definingPolynomial, 805
degree, 805
differentiate, 805
dimension, 805
discreteLog, 805
divide, 805
euclideanSize, 805
expressIdealMember, 805
exquo, 805
extendedEuclidean, 805
extensionDegree, 805
factor, 805
factorsOfCyclicGroupSize, 805
Frobenius, 805
gcd, 805
gcdPolynomial, 805
generator, 805
getZechTable, 805
hash, 805
index, 805
inGroundField?, 805
init, 805
inv, 805
latex, 805
lcm, 805
linearAssociatedExp, 805

linearAssociatedLog, 805
linearAssociatedOrder, 805
lookup, 805
minimalPolynomial, 805
multiEuclidean, 805
nextItem, 805
norm, 805
normal?, 805
normalElement, 805
one?, 805
order, 805
prime?, 805
primeFrobenius, 805
primitive?, 805
primitiveElement, 805
principalIdeal, 805
random, 805
recip, 805
representationType, 805
represents, 805
retract, 805
retractIfCan, 805
sample, 805
size, 805
sizeLess?, 805
squareFree, 805
squareFreePart, 805
subtractIfCan, 805
tableForDiscreteLogarithm, 805
trace, 805
transcendenceDegree, 805
transcendent?, 805
unit?, 805
unitCanonical, 805
unitNormal, 805
zero?, 805
FFCGX, 799
-?, 800
?**?, 800
?*?, 800
?+?, 800
?-?, 800
?/?, 800
?=?, 800
?^?, 800
?~=?, 800
?quo?, 800
?rem?, 800
0, 800
1, 800
algebraic?, 800
associates?, 800
basis, 800
characteristic, 800
charthRoot, 800
coerce, 800
conditionP, 800
coordinates, 800
createNormalElement, 800
createPrimitiveElement, 800
D, 800
definingPolynomial, 800
degree, 800
differentiate, 800
dimension, 800
discreteLog, 800
divide, 800
euclideanSize, 800
expressIdealMember, 800
exquo, 800
extendedEuclidean, 800
extensionDegree, 800
factor, 800
factorsOfCyclicGroupSize, 800
Frobenius, 800
gcd, 800
gcdPolynomial, 800
generator, 800
getZechTable, 800
hash, 800
index, 800
inGroundField?, 800
init, 800
inv, 800
latex, 800
lcm, 800
linearAssociatedExp, 800
linearAssociatedLog, 800
linearAssociatedOrder, 800
lookup, 800
minimalPolynomial, 800
multiEuclidean, 800

nextItem, 800
norm, 800
normal?, 800
normalElement, 800
one?, 800
order, 800
prime?, 800
primeFrobenius, 800
primitive?, 800
primitiveElement, 800
principalIdeal, 800
random, 800
recip, 800
representationType, 800
represents, 800
retract, 800
retractIfCan, 800
sample, 800
size, 800
sizeLess?, 800
squareFree, 800
squareFreePart, 800
subtractIfCan, 800
tableForDiscreteLogarithm, 800
trace, 800
transcendenceDegree, 800
transcendent?, 800
unit?, 800
unitCanonical, 800
unitNormal, 800
zero?, 800
FFNB, 829
-?, 830
?**?, 830
?*?, 830
?+?, 830
?-?, 830
?/?, 830
?=?, 830
?^?, 830
?~=?, 830
?quo?, 830
?rem?, 830
0, 830
1, 830
algebraic?, 830
associates?, 830
basis, 830
characteristic, 830
charthRoot, 830
coerce, 830
conditionP, 830
coordinates, 830
createNormalElement, 830
createPrimitiveElement, 830
D, 830
definingPolynomial, 830
degree, 830
differentiate, 830
dimension, 830
discreteLog, 830
divide, 830
euclideanSize, 830
expressIdealMember, 830
exquo, 830
extendedEuclidean, 830
extensionDegree, 830
factor, 830
factorsOfCyclicGroupSize, 830
Frobenius, 830
gcd, 830
gcdPolynomial, 830
generator, 830
getMultiplicationMatrix, 830
getMultiplicationTable, 830
hash, 830
index, 830
inGroundField?, 830
init, 830
inv, 830
latex, 830
lcm, 830
linearAssociatedExp, 830
linearAssociatedLog, 830
linearAssociatedOrder, 830
lookup, 830
minimalPolynomial, 830
multiEuclidean, 830
nextItem, 830
norm, 830
normal?, 830
normalElement, 830

one?, 830
order, 830
prime?, 830
primeFrobenius, 830
primitive?, 830
primitiveElement, 830
principalIdeal, 830
random, 830
recip, 830
representationType, 830
represents, 830
retract, 830
retractIfCan, 830
sample, 830
size, 830
sizeLess?, 830
sizeMultiplication, 830
squareFree, 830
squareFreePart, 830
subtractIfCan, 830
tableForDiscreteLogarithm, 830
trace, 830
transcendenceDegree, 830
transcendent?, 830
unit?, 830
unitCanonical, 830
unitNormal, 830
zero?, 830
FFNBP, 841
-?, 842
?**?, 842
?*?, 842
?+?, 842
?-?, 842
?/?, 842
?=?, 842
?^?, 842
?~=?, 842
?quo?, 842
?rem?, 842
0, 842
1, 842
algebraic?, 842
associates?, 842
basis, 842
characteristic, 842
charthRoot, 842
coerce, 842
conditionP, 842
coordinates, 842
createNormalElement, 842
createPrimitiveElement, 842
D, 842
definingPolynomial, 842
degree, 842
differentiate, 842
dimension, 842
discreteLog, 842
divide, 842
euclideanSize, 842
expressIdealMember, 842
exquo, 842
extendedEuclidean, 842
extensionDegree, 842
factor, 842
factorsOfCyclicGroupSize, 842
Frobenius, 842
gcd, 842
gcdPolynomial, 842
generator, 842
getMultiplicationMatrix, 842
getMultiplicationTable, 842
hash, 842
index, 842
inGroundField?, 842
init, 842
inv, 842
latex, 842
lcm, 842
linearAssociatedExp, 842
linearAssociatedLog, 842
linearAssociatedOrder, 842
lookup, 842
minimalPolynomial, 842
multiEuclidean, 842
nextItem, 842
norm, 842
normal?, 842
normalElement, 842
one?, 842
order, 842
prime?, 842

primeFrobenius, 842
primitive?, 842
primitiveElement, 842
principalIdeal, 842
random, 842
recip, 842
representationType, 842
represents, 842
retract, 842
retractIfCan, 842
sample, 842
size, 842
sizeLess?, 842
sizeMultiplication, 842
squareFree, 842
squareFreePart, 842
subtractIfCan, 842
tableForDiscreteLogarithm, 842
trace, 842
transcendenceDegree, 842
transcendent?, 842
unit?, 842
unitCanonical, 842
unitNormal, 842
zero?, 842
FFNBX, 835
-?, 836
?**?, 836
?*?, 836
?+?, 836
?-?, 836
?/?, 836
?=?, 836
?^?, 836
?~=?, 836
?quo?, 836
?rem?, 836
0, 836
1, 836
algebraic?, 836
associates?, 836
basis, 836
characteristic, 836
charthRoot, 836
coerce, 836
conditionP, 836
coordinates, 836
createNormalElement, 836
createPrimitiveElement, 836
D, 836
definingPolynomial, 836
degree, 836
differentiate, 836
dimension, 836
discreteLog, 836
divide, 836
euclideanSize, 836
expressIdealMember, 836
exquo, 836
extendedEuclidean, 836
extensionDegree, 836
factor, 836
factorsOfCyclicGroupSize, 836
Frobenius, 836
gcd, 836
gcdPolynomial, 836
generator, 836
getMultiplicationMatrix, 836
getMultiplicationTable, 836
hash, 836
index, 836
inGroundField?, 836
init, 836
inv, 836
latex, 836
lcm, 836
linearAssociatedExp, 836
linearAssociatedLog, 836
linearAssociatedOrder, 836
lookup, 836
minimalPolynomial, 836
multiEuclidean, 836
nextItem, 836
norm, 836
normal?, 836
normalElement, 836
one?, 836
order, 836
prime?, 836
primeFrobenius, 836
primitive?, 836
primitiveElement, 836

principalIdeal, 836
random, 836
recip, 836
representationType, 836
represents, 836
retract, 836
retractIfCan, 836
sample, 836
size, 836
sizeLess?, 836
sizeMultiplication, 836
squareFree, 836
squareFreePart, 836
subtractIfCan, 836
tableForDiscreteLogarithm, 836
trace, 836
transcendenceDegree, 836
transcendent?, 836
unit?, 836
unitCanonical, 836
unitNormal, 836
zero?, 836
FFP, 820
-?, 821
?**?, 821
?*?, 821
?+?, 821
?-?, 821
?/?, 821
?=?, 821
?^?, 821
?~=?, 821
?quo?, 821
?rem?, 821
0, 821
1, 821
algebraic?, 821
associates?, 821
basis, 821
characteristic, 821
charthRoot, 821
coerce, 821
conditionP, 821
coordinates, 821
createNormalElement, 821
createPrimitiveElement, 821
D, 821
definingPolynomial, 821
degree, 821
differentiate, 821
dimension, 821
discreteLog, 821
divide, 821
euclideanSize, 821
expressIdealMember, 821
exquo, 821
extendedEuclidean, 821
extensionDegree, 821
factor, 821
factorsOfCyclicGroupSize, 821
Frobenius, 821
gcd, 821
gcdPolynomial, 821
generator, 821
hash, 821
index, 821
inGroundField?, 821
init, 821
inv, 821
latex, 821
lcm, 821
linearAssociatedExp, 821
linearAssociatedLog, 821
linearAssociatedOrder, 821
lookup, 821
minimalPolynomial, 821
multiEuclidean, 821
nextItem, 821
norm, 821
normal?, 821
normalElement, 821
one?, 821
order, 821
prime?, 821
primeFrobenius, 821
primitive?, 821
primitiveElement, 821
principalIdeal, 821
random, 821
recip, 821
representationType, 821
represents, 821

retract, 821
retractIfCan, 821
sample, 821
size, 821
sizeLess?, 821
squareFree, 821
squareFreePart, 821
subtractIfCan, 821
tableForDiscreteLogarithm, 821
trace, 821
transcendenceDegree, 821
transcendent?, 821
unit?, 821
unitCanonical, 821
unitNormal, 821
zero?, 821
FFX, 815
-?, 816
?**?, 816
?*?, 816
?+?, 816
?-?, 816
?/?, 816
?=?, 816
?^?, 816
?~=?, 816
?quo?, 816
?rem?, 816
0, 816
1, 816
algebraic?, 816
associates?, 816
basis, 816
characteristic, 816
charthRoot, 816
coerce, 816
conditionP, 816
coordinates, 816
createNormalElement, 816
createPrimitiveElement, 816
D, 816
definingPolynomial, 816
degree, 816
differentiate, 816
dimension, 816
discreteLog, 816
divide, 816
euclideanSize, 816
expressIdealMember, 816
exquo, 816
extendedEuclidean, 816
extensionDegree, 816
factor, 816
factorsOfCyclicGroupSize, 816
Frobenius, 816
gcd, 816
gcdPolynomial, 816
generator, 816
hash, 816
index, 816
inGroundField?, 816
init, 816
inv, 816
latex, 816
lcm, 816
linearAssociatedExp, 816
linearAssociatedLog, 816
linearAssociatedOrder, 816
lookup, 816
minimalPolynomial, 816
multiEuclidean, 816
nextItem, 816
norm, 816
normal?, 816
normalElement, 816
one?, 816
order, 816
prime?, 816
primeFrobenius, 816
primitive?, 816
primitiveElement, 816
principalIdeal, 816
random, 816
recip, 816
representationType, 816
represents, 816
retract, 816
retractIfCan, 816
sample, 816
size, 816
sizeLess?, 816
squareFree, 816

squareFreePart, 816
subtractIfCan, 816
tableForDiscreteLogarithm, 816
trace, 816
transcendenceDegree, 816
transcendent?, 816
unit?, 816
unitCanonical, 816
unitNormal, 816
zero?, 816
FGROUP, 980
?**?, 980
?*?, 980
?/?, 980
?=?, 980
?^?, 980
?~=?, 980
1, 980
coerce, 980
commutator, 980
conjugate, 980
factors, 980
hash, 980
inv, 980
latex, 980
mapExpon, 980
mapGen, 980
nthExpon, 980
nthFactor, 980
one?, 980
recip, 980
retract, 980
retractIfCan, 980
sample, 980
size, 980
figureUnits
GRIMAGE, 1065
FILE, 772
?=?, 772
?~=?, 772
close, 772
coerce, 772
flush, 772
hash, 772
iomode, 772
latex, 772
name, 772
open, 772
read, 772
readIfCan, 772
reopen, 772
write, 772
File, 772
FileName, 780
filename
FNAME, 780
filterUntil
ITUPLE, 1231
STREAM, 2550
filterUpTo
NSDPS, 1670
filterWhile
ITUPLE, 1231
STREAM, 2550
find
ALIST, 221
ARRAY1, 1740
BITS, 299
CCLASS, 368
CDFVEC, 419
DFVEC, 593
DLIST, 448
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
MSET, 1638
NSDPS, 1670
POINT, 2026

PRIMARR, 2075
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
ROUTINE, 2298
SET, 2338
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
findCoef
NSDPS, 1670
findCycle
STREAM, 2550
findTerm
NSDPS, 1670
finite?
CARD, 318
ONECOMP, 1744
ORDCOMP, 1777
finiteBasis
FDIV, 783
FiniteDivisor, 783
FiniteField, 789
FiniteFieldCyclicGroup, 794
FiniteFieldCyclicGroupExtension, 799
FiniteFieldCyclicGroupExtensionByPolynomial, 804
FiniteFieldExtension, 815
FiniteFieldExtensionByPolynomial, 820
FiniteFieldNormalBasis, 829
FiniteFieldNormalBasisExtension, 835
FiniteFieldNormalBasisExtensionByPolynomial, 841
fintegrate
SMTS, 2409
TS, 2639
first
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
MAGMA, 1533
NSDPS, 1670
ODP, 1783
OFMONOID, 1795
PBWLB, 2020
POINT, 2026
PRIMARR, 2075
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
ROUTINE, 2298
SHDP, 2476
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
firstDenom
PFR, 1880
firstNumer

PFR, 1880
fixedPoints
PERM, 1916
flagFactor
FR, 756
flatten
INFORM, 1311
flexible?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
FlexibleArray, 856
flexibleArray
FARRAY, 856
IFARRAY, 1192
FLOAT, 878
-?, 879
?<?, 879
?<=?, 879
?>?, 879
?>=?, 879
?**?, 879
?*?, 879
?+?, 879
?-?, 879
?/?, 879
?=?, 879
?^?, 879
?~=?, 879
?quo?, 879
?rem?, 879
0, 879
1, 879
abs, 879
acos, 879
acosh, 879
acot, 879
acoth, 879
acsc, 879
acsch, 879
asec, 879
asech, 879
asin, 879
asinh, 879
associates?, 879
atan, 879
atanh, 879
base, 879
bits, 879
ceiling, 879
characteristic, 879
coerce, 879
convert, 879
cos, 879
cosh, 879
cot, 879
coth, 879
csc, 879
csch, 879
D, 879
decreasePrecision, 879
differentiate, 879
digits, 879
divide, 879
euclideanSize, 879
exp, 879
exp1, 879
exponent, 879
expressIdealMember, 879
exquo, 879
extendedEuclidean, 879
factor, 879
float, 879
floor, 879
fractionPart, 879
gcd, 879
gcdPolynomial, 879
hash, 879
increasePrecision, 879
inv, 879
latex, 879
lcm, 879
log, 879
log10, 879
log2, 879
mantissa, 879
max, 879
min, 879
multiEuclidean, 879
negative?, 879

norm, 879
normalize, 879
nthRoot, 879
OMwrite, 879
one?, 879
order, 879
outputFixed, 879
outputFloating, 879
outputGeneral, 879
outputSpacing, 879
patternMatch, 879
pi, 879
positive?, 879
precision, 879
prime?, 879
principalIdeal, 879
rationalApproximation, 879
recip, 879
relerror, 879
retract, 879
retractIfCan, 879
round, 879
sample, 879
sec, 879
sech, 879
shift, 879
sign, 879
sin, 879
sinh, 879
sizeLess?, 879
sqrt, 879
squareFree, 879
squareFreePart, 879
subtractIfCan, 879
tan, 879
tanh, 879
truncate, 879
unit?, 879
unitCanonical, 879
unitNormal, 879
wholePart, 879
zero?, 879
Float, 878
float
DFLOAT, 575
FLOAT, 879
INFORM, 1311
MFLOAT, 1516
SEX, 2360
SEXOF, 2363
float?
INFORM, 1311
SEX, 2360
SEXOF, 2363
floor
BINARY, 277
BPADICRT, 247
DECIMAL, 453
DFLOAT, 575
EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HEXADEC, 1113
MFLOAT, 1516
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
flush
FILE, 772
FM, 983
-?, 983
?*?, 983
?+?, 983
?-?, 983
?=?, 983
?~=?, 983
0, 983
coerce, 983
hash, 983
latex, 983
leadingCoefficient, 983
leadingSupport, 983
map, 983
monomial, 983
reductum, 983
sample, 983
subtractIfCan, 983
zero?, 983
FM1, 987

-?, 987
?*?, 987
?+?, 987
?-?, 987
?=?, 987
?~=?, 987
0, 987
coefficient, 987
coefficients, 987
coerce, 987
hash, 987
latex, 987
leadingCoefficient, 987
leadingMonomial, 987
leadingTerm, 987
listOfTerms, 987
map, 987
monom, 987
monomial?, 987
monomials, 987
numberOfMonomials, 987
reductum, 987
retract, 987
retractIfCan, 987
sample, 987
subtractIfCan, 987
zero?, 987
fmecg
MYUP, 1663
NSUP, 1696
PR, 2058
SUP, 2435
SYMPOLY, 2622
UP, 2795
FMONOID, 991
?<?, 991
?<=?, 991
?>?, 991
?>=?, 991
?**?, 991
?*?, 991
?=?, 991
?^?, 991
?~=?, 991
1, 991
coerce, 991
divide, 991
factors, 991
hash, 991
hclf, 991
hcrf, 991
latex, 991
lquo, 991
mapExpon, 991
mapGen, 991
max, 991
min, 991
nthExpon, 991
nthFactor, 991
one?, 991
overlap, 991
recip, 991
retract, 991
retractIfCan, 991
rquo, 991
sample, 991
size, 991
FNAME, 780
?=?, 780
?~=?, 780
coerce, 780
directory, 780
exists?, 780
extension, 780
filename, 780
hash, 780
latex, 780
name, 780
new, 780
readable?, 780
writable?, 780
FNLA, 997
-?, 997
?**?, 997
?*?, 997
?+?, 997
?-?, 997
?=?, 997
?~=?, 997
0, 997
antiCommutator, 997
associator, 997

coerce, 997
commutator, 997
deepExpand, 997
dimension, 997
generator, 997
hash, 997
latex, 997
leftPower, 997
plenaryPower, 997
rightPower, 997
sample, 997
shallowExpand, 997
subtractIfCan, 997
zero?, 997
forLoop
FC, 902
FORMULA, 2312
?=?, 2312
?~=?, 2312
coerce, 2312
convert, 2312
display, 2312
epilogue, 2312
formula, 2312
hash, 2312
latex, 2312
new, 2312
prologue, 2312
setEpilogue, 2312
setFormula, 2312
setPrologue, 2312
formula
FORMULA, 2312
FORTRAN, 926
coerce, 926
outputAsFortran, 926
fortran
SFORT, 2374
fortranCarriageReturn
FTEM, 938
fortranCharacter
FT, 941
FortranCode, 901
fortranComplex
FT, 941
fortranDouble
FT, 941
fortranDoubleComplex
FT, 941
FortranExpression, 917
fortranInteger
FT, 941
fortranLiteral
FTEM, 938
fortranLiteralLine
FTEM, 938
fortranLogical
FT, 941
FortranProgram, 926
fortranReal
FT, 941
FortranScalarType, 932
FortranTemplate, 937
FortranType, 941
fortranTypeOf
SYMTAB, 2616
foundPlaces
PLACES, 1985
PLACESPS, 1987
FourierComponent, 945
FourierSeries, 948
FPARFRAC, 1010
?+?, 1010
?=?, 1010
?~=?, 1010
coerce, 1010
construct, 1010
convert, 1010
D, 1010
differentiate, 1010
fracPart, 1010
fullPartialFraction, 1010
hash, 1010
latex, 1010
polyPart, 1010
FR, 756
-?, 756
?**?, 756
?*?, 756
?+?, 756
?-?, 756
?.?, 756

?=?, 756
?^?, 756
?~=?, 756
0, 756
1, 756
associates?, 756
characteristic, 756
coerce, 756
convert, 756
D, 756
differentiate, 756
eval, 756
expand, 756
exponent, 756
exquo, 756
factor, 756
factorList, 756
factors, 756
flagFactor, 756
gcd, 756
gcdPolynomial, 756
hash, 756
irreducibleFactor, 756
latex, 756
lcm, 756
makeFR, 756
map, 756
nilFactor, 756
nthExponent, 756
nthFactor, 756
nthFlag, 756
numberOfFactors, 756
one?, 756
prime?, 756
primeFactor, 756
rational, 756
rational?, 756
rationalIfCan, 756
recip, 756
retract, 756
retractIfCan, 756
sample, 756
sqfrFactor, 756
squareFree, 756
squareFreePart, 756
subtractIfCan, 756
unit, 756
unit?, 756
unitCanonical, 756
unitNormal, 756
unitNormalize, 756
zero?, 756
FRAC, 956
-?, 956
?<?, 956
?<=?, 956
?>?, 956
?>=?, 956
?**?, 956
?*?, 956
?+?, 956
?-?, 956
?.?, 956
?/?, 956
?=?, 956
?^?, 956
?~=?, 956
?quo?, 956
?rem?, 956
0, 956
1, 956
abs, 956
associates?, 956
ceiling, 956
characteristic, 956
charthRoot, 956
coerce, 956
conditionP, 956
convert, 956
D, 956
denom, 956
denominator, 956
differentiate, 956
divide, 956
euclideanSize, 956
eval, 956
expressIdealMember, 956
exquo, 956
extendedEuclidean, 956
factor, 956
factorPolynomial, 956
factorSquareFreePolynomial, 956

floor, 956
fractionPart, 956
gcd, 956
gcdPolynomial, 956
hash, 956
init, 956
inv, 956
latex, 956
lcm, 956
map, 956
max, 956
min, 956
multiEuclidean, 956
negative?, 956
nextItem, 956
numer, 956
numerator, 956
OMwrite, 956
one?, 956
patternMatch, 956
positive?, 956
prime?, 956
principalIdeal, 956
random, 956
recip, 956
reducedSystem, 956
retract, 956
retractIfCan, 956
sample, 956
sign, 956
sizeLess?, 956
solveLinearPolynomialEquation, 956
squareFree, 956
squareFreePart, 956
squareFreePolynomial, 956
subtractIfCan, 956
unit?, 956
unitCanonical, 956
unitNormal, 956
wholePart, 956
zero?, 956
fracPart
FPARFRAC, 1010
Fraction, 956
FractionalIdeal, 965
fractionPart
BINARY, 277
BPADICRT, 247
DECIMAL, 453
DFLOAT, 575
EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HEXADEC, 1113
MFLOAT, 1516
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
fractRadix
RADIX, 2172
fractRagits
RADIX, 2172
FramedModule, 970
FreeAbelianGroup, 974
FreeAbelianMonoid, 977
FreeGroup, 980
FreeModule, 983
FreeModule1, 987
FreeMonoid, 991
FreeNilpotentLie, 997
freeOf?
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
SD, 2540
FRIDEAL, 965
?**?, 965
?*?, 965
?/?, 965
?=?, 965
?^?, 965
?~=?, 965
1, 965
basis, 965
coerce, 965
commutator, 965
conjugate, 965

denom, 965
hash, 965
ideal, 965
inv, 965
latex, 965
minimize, 965
norm, 965
numer, 965
one?, 965
randomLC, 965
recip, 965
sample, 965
FRMOD, 970
?**?, 970
?*?, 970
?=?, 970
?^?, 970
?~=?, 970
1, 970
basis, 970
coerce, 970
hash, 970
latex, 970
module, 970
norm, 970
one?, 970
recip, 970
sample, 970
Frobenius
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PACOFF, 2102
PACRAT, 2112
PF, 2071
frobenius
MODMON, 1600
front
DEQUEUE, 499
QUEUE, 2150
frst
NSDPS, 1670
STREAM, 2550
FSERIES, 948
-?, 948
?**?, 948
?*?, 948
?+?, 948
?-?, 948
?=?, 948
?^?, 948
?~=?, 948
0, 948
1, 948
characteristic, 948
coerce, 948
hash, 948
latex, 948
makeCos, 948
makeSin, 948
one?, 948
recip, 948
sample, 948
subtractIfCan, 948
zero?, 948
FST, 932
?=?, 933
character?, 933
coerce, 933
complex?, 933
double?, 933
doubleComplex?, 933
integer?, 933
logical?, 933
real?, 933
FT, 941
?=?, 941
?~=?, 941
coerce, 941
construct, 941
dimensionsOf, 941
external?, 941
fortranCharacter, 941
fortranComplex, 941

fortranDouble, 941
fortranDoubleComplex, 941
fortranInteger, 941
fortranLogical, 941
fortranReal, 941
hash, 941
latex, 941
scalarTypeOf, 941
fTable
INTFTBL, 1339
FTEM, 937
?=?, 938
?~=?, 938
close, 938
coerce, 938
fortranCarriageReturn, 938
fortranLiteral, 938
fortranLiteralLine, 938
hash, 938
iomode, 938
latex, 938
name, 938
open, 938
processTemplate, 938
read, 938
reopen, 938
write, 938
fullDisplay
DBASE, 442
ICARD, 1163
fullOut
DSTREE, 522
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
fullOutput
DSTREE, 522
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
PACOFF, 2102
PACRAT, 2112
fullPartialFraction
FPARFRAC, 1010
FullPartialFractionExpansion, 1010
FUNCTION, 1015
?=?, 1015
?~=?, 1015
coerce, 1015
hash, 1015
latex, 1015
name, 1015
function
INFORM, 1311
FunctionCalled, 1015
functionName
GOPT, 1075
GOPT0, 1081
functionNames
GOPT, 1075

Gamma
DFLOAT, 575
EXPR, 694
gcd
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956

GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
PI, 2066
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
gcdPolynomial
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
LAUPOL, 1390

MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
GCNAALG, 1034
-?, 1035
?**?, 1035
?*?, 1035
?+?, 1035
?-?, 1035
?.?, 1035
?=?, 1035
?~=?, 1035
0, 1035
alternative?, 1035
antiAssociative?, 1035
antiCommutative?, 1035
antiCommutator, 1035
apply, 1035
associative?, 1035
associator, 1035
associatorDependence, 1035
basis, 1035
coerce, 1035
commutative?, 1035
commutator, 1035
conditionsForIdempotents, 1035
convert, 1035
coordinates, 1035
flexible?, 1035
generic, 1035
genericLeftDiscriminant, 1035
genericLeftMinimalPolynomial, 1035
genericLeftNorm, 1035
genericLeftTrace, 1035
genericLeftTraceForm, 1035
genericRightDiscriminant, 1035
genericRightMinimalPolynomial, 1035
genericRightNorm, 1035
genericRightTrace, 1035
genericRightTraceForm, 1035
hash, 1035
jacobiIdentity?, 1035
jordanAdmissible?, 1035
jordanAlgebra?, 1035
latex, 1035
leftAlternative?, 1035
leftCharacteristicPolynomial, 1035
leftDiscriminant, 1035
leftMinimalPolynomial, 1035
leftNorm, 1035
leftPower, 1035
leftRankPolynomial, 1035
leftRecip, 1035
leftRegularRepresentation, 1035
leftTrace, 1035
leftTraceMatrix, 1035
leftUnit, 1035

leftUnits, 1035
lieAdmissible?, 1035
lieAlgebra?, 1035
noncommutativeJordanAlgebra?, 1035
plenaryPower, 1035
powerAssociative?, 1035
rank, 1035
recip, 1035
represents, 1035
rightAlternative?, 1035
rightCharacteristicPolynomial, 1035
rightDiscriminant, 1035
rightMinimalPolynomial, 1035
rightNorm, 1035
rightPower, 1035
rightRankPolynomial, 1035
rightRecip, 1035
rightRegularRepresentation, 1035
rightTrace, 1035
rightTraceMatrix, 1035
rightUnit, 1035
rightUnits, 1035
sample, 1035
someBasis, 1035
structuralConstants, 1035
subtractIfCan, 1035
unit, 1035
zero?, 1035
GDMP, 1022
-?, 1022
?<?, 1022
?<=?, 1022
?>?, 1022
?>=?, 1022
?**?, 1022
?*?, 1022
?+?, 1022
?-?, 1022
?=?, 1022
?^?, 1022
?~=?, 1022
0, 1022
1, 1022
associates?, 1022
binomThmExpt, 1022
characteristic, 1022
charthRoot, 1022
coefficient, 1022
coefficients, 1022
coerce, 1022
conditionP, 1022
content, 1022
D, 1022
degree, 1022
differentiate, 1022
discriminant, 1022
eval, 1022
exquo, 1022
factor, 1022
factorPolynomial, 1022
factorSquareFreePolynomial, 1022
gcd, 1022
gcdPolynomial, 1022
ground, 1022
ground?, 1022
hash, 1022
isExpt, 1022
isPlus, 1022
isTimes, 1022
latex, 1022
lcm, 1022
leadingCoefficient, 1022
leadingMonomial, 1022
mainVariable, 1022
map, 1022
mapExponents, 1022
max, 1022
min, 1022
minimumDegree, 1022
monicDivide, 1022
monomial, 1022
monomial?, 1022
monomials, 1022
multivariate, 1022
numberOfMonomials, 1022
one?, 1022
patternMatch, 1022
pomopo, 1022
prime?, 1022
primitiveMonomials, 1022
primitivePart, 1022
recip, 1022

reducedSystem, 1022
reductum, 1022
reorder, 1022
resultant, 1022
retract, 1022
retractIfCan, 1022
sample, 1022
solveLinearPolynomialEquation, 1022
squareFree, 1022
squareFreePart, 1022
squareFreePolynomial, 1022
subtractIfCan, 1022
totalDegree, 1022
unit?, 1022
unitCanonical, 1022
unitNormal, 1022
univariate, 1022
variables, 1022
zero?, 1022
GE
SWITCH, 2597
GeneralDistributedMultivariatePolynomial, 1022
generalizedContinuumHypothesisAssumed
CARD, 318
generalizedContinuumHypothesisAssumed?
CARD, 318
generalLambert
UFPS, 2757
UTS, 2844
UTSZ, 2854
GeneralModulePolynomial, 1029
GeneralPolynomialSet, 1044
generalPosition
IDEAL, 2047
GeneralSparseTable, 1048
GeneralTriangularSet, 1053
GeneralUnivariatePowerSeries, 1060
generate
ITUPLE, 1231
STREAM, 2550
generator
ALGFF, 28
ANTISYM, 40
COMPLEX, 406
DERHAM, 517
FDIV, 783
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FNLA, 997
HELLFDIV, 1153
IFF, 1252
IPF, 1271
MCMPLX, 1511
PF, 2071
RADFF, 2160
SAE, 2368
generators
IDEAL, 2047
PERMGRP, 1926
generic
GCNAALG, 1035
generic?
PATTERN, 1894
genericLeftDiscriminant
GCNAALG, 1035
genericLeftMinimalPolynomial
GCNAALG, 1035
genericLeftNorm
GCNAALG, 1035
genericLeftTrace
GCNAALG, 1035
genericLeftTraceForm
GCNAALG, 1035
GenericNonAssociativeAlgebra, 1034
genericRightDiscriminant
GCNAALG, 1035
genericRightMinimalPolynomial
GCNAALG, 1035
genericRightNorm
GCNAALG, 1035
genericRightTrace
GCNAALG, 1035
genericRightTraceForm
GCNAALG, 1035
genus

ALGFF, 28
RADFF, 2160
getBadValues
PATTERN, 1894
getButtonValue
ATTRBUT, 224
getCode
FC, 902
getCurve
TUBE, 2718
getExplanations
ROUTINE, 2298
getGraph
VIEW2d, 2739
getMatch
PATRES, 1906
getMeasure
ROUTINE, 2298
getMultiplicationMatrix
FFNB, 830
FFNBP, 842
FFNBX, 836
getMultiplicationTable
FFNB, 830
FFNBP, 842
FFNBX, 836
getPickedPoints
VIEW2d, 2739
getRef
ISUPS, 1279
getSmgl
BSD, 270
getStream
ISUPS, 1279
getZechTable
FFCG, 795
FFCGP, 805
FFCGX, 800
GMODPOL, 1029
-?, 1029
?*?, 1029
?+?, 1029
?-?, 1029
?=?, 1029
?~=?, 1029
0, 1029
build, 1029
coerce, 1029
hash, 1029
latex, 1029
leadingCoefficient, 1029
leadingExponent, 1029
leadingIndex, 1029
leadingMonomial, 1029
monomial, 1029
multMonom, 1029
reductum, 1029
sample, 1029
subtractIfCan, 1029
unitVector, 1029
zero?, 1029
GOPT, 1075
?=?, 1075
?~=?, 1075
allDegrees, 1075
check, 1075
checkExtraValues, 1075
coerce, 1075
debug, 1075
displayKind, 1075
functionName, 1075
functionNames, 1075
hash, 1075
homogeneous, 1075
indexName, 1075
latex, 1075
maxDegree, 1075
maxDerivative, 1075
maxLevel, 1075
maxMixedDegree, 1075
maxPower, 1075
maxShift, 1075
maxSubst, 1075
one, 1075
option, 1075
safety, 1075
Somos, 1075
variableName, 1075
GOPT0, 1081
?=?, 1081
?~=?, 1081
allDegrees, 1081

check, 1081
checkOptions, 1081
coerce, 1081
debug, 1081
displayAsGF, 1081
functionName, 1081
hash, 1081
homogeneous, 1081
indexName, 1081
latex, 1081
maxDegree, 1081
maxDerivative, 1081
maxLevel, 1081
maxMixedDegree, 1081
maxPower, 1081
maxShift, 1081
maxSubst, 1081
MonteCarlo, 1081
one, 1081
safety, 1081
Somos, 1081
variableName, 1081
goto
FC, 902
GPOLSET, 1044
?=?, 1044
?~=?, 1044
#?, 1044
any?, 1044
coerce, 1044
collect, 1044
collectUnder, 1044
collectUpper, 1044
construct, 1044
convert, 1044
copy, 1044
count, 1044
empty, 1044
empty?, 1044
eq?, 1044
eval, 1044
every?, 1044
find, 1044
hash, 1044
headRemainder, 1044
latex, 1044
less?, 1044
mainVariable?, 1044
mainVariables, 1044
map, 1044
member?, 1044
members, 1044
more?, 1044
mvar, 1044
parts, 1044
reduce, 1044
remainder, 1044
remove, 1044
removeDuplicates, 1044
retract, 1044
retractIfCan, 1044
rewriteIdealWithHeadRemainder, 1044
rewriteIdealWithRemainder, 1044
roughBase?, 1044
roughEqualIdeals?, 1044
roughSubIdeal?, 1044
roughUnitIdeal?, 1044
sample, 1044
select, 1044
size?, 1044
sort, 1044
triangular?, 1044
trivialIdeal?, 1044
variables, 1044
GraphImage, 1065
graphImage
GRIMAGE, 1065
graphs
VIEW2d, 2739
graphState
VIEW2d, 2739
graphStates
VIEW2d, 2739
green
COLOR, 394
GRIMAGE, 1065
?=?, 1065
?~=?, 1065
appendPoint, 1065
coerce, 1065
component, 1065
figureUnits, 1065

graphImage, 1065
hash, 1065
key, 1065
latex, 1065
makeGraphImage, 1065
point, 1065
pointLists, 1065
putColorInfo, 1065
ranges, 1065
units, 1065
groebner
IDEAL, 2047
groebner?
IDEAL, 2047
groebnerIdeal
IDEAL, 2047
ground
DMP, 560
DSMP, 529
EXPR, 694
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819
ground?
DMP, 560
DSMP, 529
EXPR, 694
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PACOFF, 2102
PACRAT, 2112
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819
GSERIES, 1060
-?, 1061
?**?, 1061
?*?, 1061
?+?, 1061
?-?, 1061
?.?, 1061
?/?, 1061
?=?, 1061
?^?, 1061
?~=?, 1061
?quo?, 1061
?rem?, 1061
0, 1061
1, 1061
acos, 1061
acosh, 1061
acot, 1061
acoth, 1061
acsc, 1061
acsch, 1061
approximate, 1061
asec, 1061
asech, 1061
asin, 1061
asinh, 1061
associates?, 1061
atan, 1061
atanh, 1061
center, 1061

characteristic, 1061
charthRoot, 1061
coefficient, 1061
coerce, 1061
complete, 1061
cos, 1061
cosh, 1061
cot, 1061
coth, 1061
csc, 1061
csch, 1061
D, 1061
degree, 1061
differentiate, 1061
divide, 1061
euclideanSize, 1061
eval, 1061
exp, 1061
expressIdealMember, 1061
exquo, 1061
extend, 1061
extendedEuclidean, 1061
factor, 1061
gcd, 1061
gcdPolynomial, 1061
hash, 1061
integrate, 1061
inv, 1061
latex, 1061
lcm, 1061
leadingCoefficient, 1061
leadingMonomial, 1061
log, 1061
map, 1061
monomial, 1061
monomial?, 1061
multiEuclidean, 1061
multiplyExponents, 1061
nthRoot, 1061
one?, 1061
order, 1061
pi, 1061
pole?, 1061
prime?, 1061
principalIdeal, 1061
recip, 1061
reductum, 1061
sample, 1061
sec, 1061
sech, 1061
series, 1061
sin, 1061
sinh, 1061
sizeLess?, 1061
sqrt, 1061
squareFree, 1061
squareFreePart, 1061
subtractIfCan, 1061
tan, 1061
tanh, 1061
terms, 1061
truncate, 1061
unit?, 1061
unitCanonical, 1061
unitNormal, 1061
variable, 1061
variables, 1061
zero?, 1061
GSTBL, 1048
?.?, 1049
?=?, 1049
?~=?, 1049
#?, 1049
any?, 1049
bag, 1049
coerce, 1049
construct, 1049
convert, 1049
copy, 1049
count, 1049
dictionary, 1049
elt, 1049
empty, 1049
empty?, 1049
entries, 1049
entry?, 1049
eq?, 1049
eval, 1049
every?, 1049
extract, 1049
fill, 1049
find, 1049

first, 1049
hash, 1049
index?, 1049
indices, 1049
insert, 1049
inspect, 1049
key?, 1049
keys, 1049
latex, 1049
less?, 1049
map, 1049
maxIndex, 1049
member?, 1049
members, 1049
minIndex, 1049
more?, 1049
parts, 1049
qelt, 1049
qsetelt, 1049
reduce, 1049
remove, 1049
removeDuplicates, 1049
sample, 1049
search, 1049
select, 1049
setelt, 1049
size?, 1049
swap, 1049
table, 1049
GT
SWITCH, 2597
GTSET, 1053
?=?, 1054
?~=?, 1054
#?, 1054
algebraic?, 1054
algebraicVariables, 1054
any?, 1054
autoReduced?, 1054
basicSet, 1054
coerce, 1054
coHeight, 1054
collect, 1054
collectQuasiMonic, 1054
collectUnder, 1054
collectUpper, 1054
construct, 1054
convert, 1054
copy, 1054
count, 1054
degree, 1054
empty, 1054
empty?, 1054
eq?, 1054
eval, 1054
every?, 1054
extend, 1054
extendIfCan, 1054
find, 1054
first, 1054
hash, 1054
headReduce, 1054
headReduced?, 1054
headRemainder, 1054
infRittWu?, 1054
initiallyReduce, 1054
initiallyReduced?, 1054
initials, 1054
last, 1054
latex, 1054
less?, 1054
mainVariable?, 1054
mainVariables, 1054
map, 1054
member?, 1054
members, 1054
more?, 1054
mvar, 1054
normalized?, 1054
parts, 1054
quasiComponent, 1054
reduce, 1054
reduceByQuasiMonic, 1054
reduced?, 1054
remainder, 1054
remove, 1054
removeDuplicates, 1054
removeZero, 1054
rest, 1054
retract, 1054
retractIfCan, 1054
rewriteIdealWithHeadRemainder, 1054

rewriteIdealWithRemainder, 1054
rewriteSetWithReduction, 1054
roughBase?, 1054
roughEqualIdeals?, 1054
roughSubIdeal?, 1054
roughUnitIdeal?, 1054
sample, 1054
select, 1054
size?, 1054
sort, 1054
stronglyReduce, 1054
stronglyReduced?, 1054
triangular?, 1054
trivialIdeal?, 1054
variables, 1054
zeroSetSplit, 1054
zeroSetSplitIntoTriangularSystems, 1054
GuessOption, 1075
GuessOptionFunctions0, 1081

HACKPI, 1943
-?, 1944
?**?, 1944
?*?, 1944
?+?, 1944
?-?, 1944
?/?, 1944
?=?, 1944
?^?, 1944
?~=?, 1944
?quo?, 1944
?rem?, 1944
0, 1944
1, 1944
associates?, 1944
characteristic, 1944
coerce, 1944
convert, 1944
divide, 1944
euclideanSize, 1944
expressIdealMember, 1944
exquo, 1944
extendedEuclidean, 1944
factor, 1944
gcd, 1944
gcdPolynomial, 1944
hash, 1944
inv, 1944
latex, 1944
lcm, 1944
multiEuclidean, 1944
one?, 1944
pi, 1944
prime?, 1944
principalIdeal, 1944
recip, 1944
retract, 1944
retractIfCan, 1944
sample, 1944
sizeLess?, 1944
squareFree, 1944
squareFreePart, 1944
subtractIfCan, 1944
unit?, 1944
unitCanonical, 1944
unitNormal, 1944
zero?, 1944
halfExtendedResultant1
NSUP, 1696
halfExtendedResultant2
NSUP, 1696
halfExtendedSubResultantGcd1
NSMP, 1681
NSUP, 1696
halfExtendedSubResultantGcd2
NSMP, 1681
NSUP, 1696
has?
BOP, 258
hash
AFFPLPS, 7
AFFSP, 9
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ANON, 38
ANTISYM, 40
ANY, 50
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65

ATTRBUT, 224
AUTOMOR, 231
BBTREE, 237
BFUNCT, 249
BINARY, 277
BINFILE, 280
BITS, 299
BLHN, 301
BLQT, 304
BOOLEAN, 307
BOP, 258
BPADIC, 242
BPADICRT, 247
BSD, 270
BSTREE, 287
BTOURN, 291
BTREE, 295
CARD, 318
CARTEN, 342
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
CHAR, 359
CLIF, 388
COLOR, 394
COMM, 397
COMPLEX, 406
COMPPROP, 2592
CONTFRAC, 432
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617, 620
D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
D10ANFA, 614
DBASE, 442
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DROPT, 596
DSMP, 529
DSTREE, 522
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732
E04NAFA, 735
E04UCFA, 739
EAB, 713
EMR, 672
EQ, 661
EQTBL, 669
EXIT, 677
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FARRAY, 856
FC, 902
FCOMP, 945
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836

FFP, 821
FFX, 816
FGROUP, 980
FILE, 772
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNAME, 780
FNLA, 997
FORMULA, 2312
FPARFRAC, 1010
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
FT, 941
FTEM, 938
FUNCTION, 1015
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GOPT, 1075
GOPT0, 1081
GPOLSET, 1044
GRIMAGE, 1065
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HELLFDIV, 1153
HEXADEC, 1113
HTMLFORM, 1122
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IC, 1161
ICARD, 1163
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFARRAY, 1192
IFF, 1252
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INFCLSPS, 1240
INFCLSPT, 1234
INFORM, 1311
INT, 1330
INTABL, 1304
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
KERNEL, 1372
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LMOPS, 1477
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
M3D, 2672
MAGMA, 1533
MATRIX, 1591
MCMPLX, 1511

MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MMLFORM, 1571
MODFIELD, 1606
MODMON, 1600
MODMONOM, 1612
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NIPROB, 1713
NNI, 1706
NONE, 1704
NOTTING, 1711
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODEPROB, 1716
ODP, 1783
ODPOL, 1818
ODR, 1825
ODVAR, 1821
OFMONOID, 1795
OMENC, 1755
OMERR, 1758
OMERRK, 1761
OMLO, 1773
ONECOMP, 1744
OPTPROB, 1719
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OSI, 1830
OUTFORM, 1834
OVAR, 1803
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PALETTE, 1862
PATLRES, 1904
PATRES, 1906
PATTERN, 1894
PBWLB, 2020
PDEPROB, 1722
PENDTREE, 1911
PERM, 1916
PERMGRP, 1926
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
PRODUCT, 2079
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
PRTITION, 1889
QALGSET, 2123
QFORM, 2120
QUAT, 2133
QUEUE, 2150
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REF, 2215
REGSET, 2252
RESRING, 2262
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROIRC, 2276
ROMAN, 2293
ROUTINE, 2298
RULE, 2271
RULECOLD, 2307
RULESET, 2309
SAE, 2368
SAOS, 2386
SD, 2540

SDPOL, 2352
SDVAR, 2358
SEG, 2325
SEGBIND, 2330
SET, 2338
SETMN, 2344
SEX, 2360
SEXOF, 2363
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SPACE3, 2701
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUBSPACE, 2582
SUCH, 2595
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMBOL, 2608
SYMPOLY, 2622
TABLE, 2632
TEX, 2645
TEXTFILE, 2661
TREE, 2710
TS, 2639
TUPLE, 2721
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VARIABLE, 2872
VECTOR, 2878
VIEW2d, 2739
VIEW3D, 2679
WP, 2885
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
hasHi
UNISEG, 2863
HashTable, 1089
HASHTBL, 1089
?.?, 1090
?=?, 1090
?~=?, 1090
#?, 1090
any?, 1090
bag, 1090
coerce, 1090
construct, 1090
convert, 1090
copy, 1090
count, 1090
dictionary, 1090
elt, 1090
empty, 1090
empty?, 1090
entries, 1090
entry?, 1090
eq?, 1090
eval, 1090
every?, 1090
extract, 1090
fill, 1090
find, 1090
first, 1090
hash, 1090
index?, 1090
indices, 1090
insert, 1090

inspect, 1090
key?, 1090
keys, 1090
latex, 1090
less?, 1090
map, 1090
maxIndex, 1090
member?, 1090
members, 1090
minIndex, 1090
more?, 1090
parts, 1090
qelt, 1090
qsetelt, 1090
reduce, 1090
remove, 1090
removeDuplicates, 1090
sample, 1090
search, 1090
select, 1090
setelt, 1090
size?, 1090
swap, 1090
table, 1090
hasPredicate?
PATTERN, 1894
hasTopPredicate?
PATTERN, 1894
hclf
FMONOID, 991
OFMONOID, 1795
hconcat
OUTFORM, 1834
hcrf
FMONOID, 991
OFMONOID, 1795
HDMP, 1149
-?, 1150
?<?, 1150
?<=?, 1150
?>?, 1150
?>=?, 1150
?**?, 1150
?*?, 1150
?+?, 1150
?-?, 1150
?/?, 1150
?=?, 1150
?^?, 1150
?~=?, 1150
0, 1150
1, 1150
associates?, 1150
binomThmExpt, 1150
characteristic, 1150
charthRoot, 1150
coefficient, 1150
coefficients, 1150
coerce, 1150
conditionP, 1150
content, 1150
convert, 1150
D, 1150
degree, 1150
differentiate, 1150
discriminant, 1150
eval, 1150
exquo, 1150
factor, 1150
factorPolynomial, 1150
factorSquareFreePolynomial, 1150
gcd, 1150
gcdPolynomial, 1150
ground, 1150
ground?, 1150
hash, 1150
isExpt, 1150
isPlus, 1150
isTimes, 1150
latex, 1150
lcm, 1150
leadingCoefficient, 1150
leadingMonomial, 1150
mainVariable, 1150
map, 1150
mapExponents, 1150
max, 1150
min, 1150
minimumDegree, 1150
monicDivide, 1150
monomial, 1150
monomial?, 1150

monomials, 1150
multivariate, 1150
numberOfMonomials, 1150
one?, 1150
patternMatch, 1150
pomopo, 1150
prime?, 1150
primitiveMonomials, 1150
primitivePart, 1150
recip, 1150
reducedSystem, 1150
reductum, 1150
reorder, 1150
resultant, 1150
retract, 1150
retractIfCan, 1150
sample, 1150
solveLinearPolynomialEquation, 1150
squareFree, 1150
squareFreePart, 1150
squareFreePolynomial, 1150
subtractIfCan, 1150
totalDegree, 1150
unit?, 1150
unitCanonical, 1150
unitNormal, 1150
univariate, 1150
variables, 1150
zero?, 1150
HDP, 1142
-?, 1143
?<?, 1143
?<=?, 1143
?>?, 1143
?>=?, 1143
?**?, 1143
?*?, 1143
?+?, 1143
?-?, 1143
?.?, 1143
?/?, 1143
?=?, 1143
?^?, 1143
?~=?, 1143
#?, 1143
0, 1143
1, 1143
abs, 1143
any?, 1143
characteristic, 1143
coerce, 1143
copy, 1143
count, 1143
D, 1143
differentiate, 1143
dimension, 1143
directProduct, 1143
dot, 1143
elt, 1143
empty, 1143
empty?, 1143
entries, 1143
entry?, 1143
eq?, 1143
eval, 1143
every?, 1143
fill, 1143
first, 1143
hash, 1143
index, 1143
index?, 1143
indices, 1143
latex, 1143
less?, 1143
lookup, 1143
map, 1143
max, 1143
maxIndex, 1143
member?, 1143
members, 1143
min, 1143
minIndex, 1143
more?, 1143
negative?, 1143
one?, 1143
parts, 1143
positive?, 1143
qelt, 1143
qsetelt, 1143
random, 1143
recip, 1143
reducedSystem, 1143

retract, 1143
retractIfCan, 1143
sample, 1143
setelt, 1143
sign, 1143
size, 1143
size?, 1143
subtractIfCan, 1143
sup, 1143
swap, 1143
unitVector, 1143
zero?, 1143
head
DIV, 563
NSMP, 1681
headReduce
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
headReduced?
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
headRemainder
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
HEAP, 1104
?=?, 1104
?~=?, 1104
#?, 1104
any?, 1104
bag, 1104
coerce, 1104
copy, 1104
count, 1104
empty, 1104
empty?, 1104
eq?, 1104
eval, 1104
every?, 1104
extract, 1104
hash, 1104
heap, 1104
insert, 1104
inspect, 1104
latex, 1104
less?, 1104
map, 1104
max, 1104
member?, 1104
members, 1104
merge, 1104
more?, 1104
parts, 1104
sample, 1104
size?, 1104
Heap, 1104
heap
HEAP, 1104
height
AN, 35
DEQUEUE, 499
EXPR, 694
FEXPR, 917
IAN, 1245
KERNEL, 1372
MYEXPR, 1656
OUTFORM, 1834
HELLFDIV, 1153
-?, 1153
?*?, 1153
?+?, 1153
?-?, 1153
?=?, 1153
?~=?, 1153
0, 1153
coerce, 1153
decompose, 1153
divisor, 1153
generator, 1153
hash, 1153
ideal, 1153

latex, 1153
principal?, 1153
reduce, 1153
sample, 1153
subtractIfCan, 1153
zero?, 1153
hex
HEXADEC, 1113
HEXADEC, 1112
-?, 1113
?<?, 1113
?<=?, 1113
?>?, 1113
?>=?, 1113
?**?, 1113
?*?, 1113
?+?, 1113
?-?, 1113
?.?, 1113
?/?, 1113
?=?, 1113
?^?, 1113
?~=?, 1113
?quo?, 1113
?rem?, 1113
0, 1113
1, 1113
abs, 1113
associates?, 1113
ceiling, 1113
characteristic, 1113
charthRoot, 1113
coerce, 1113
conditionP, 1113
convert, 1113
D, 1113
denom, 1113
denominator, 1113
differentiate, 1113
divide, 1113
euclideanSize, 1113
eval, 1113
expressIdealMember, 1113
exquo, 1113
extendedEuclidean, 1113
factor, 1113
factorPolynomial, 1113
factorSquareFreePolynomial, 1113
floor, 1113
fractionPart, 1113
gcd, 1113
gcdPolynomial, 1113
hash, 1113
hex, 1113
init, 1113
inv, 1113
latex, 1113
lcm, 1113
map, 1113
max, 1113
min, 1113
multiEuclidean, 1113
negative?, 1113
nextItem, 1113
numer, 1113
numerator, 1113
one?, 1113
patternMatch, 1113
positive?, 1113
prime?, 1113
principalIdeal, 1113
random, 1113
recip, 1113
reducedSystem, 1113
retract, 1113
retractIfCan, 1113
sample, 1113
sign, 1113
sizeLess?, 1113
solveLinearPolynomialEquation, 1113
squareFree, 1113
squareFreePart, 1113
squareFreePolynomial, 1113
subtractIfCan, 1113
unit?, 1113
unitCanonical, 1113
unitNormal, 1113
wholePart, 1113
zero?, 1113
HexadecimalExpansion, 1112
hexDigit
CCLASS, 368

hexDigit?
CHAR, 359
hi
SEG, 2325
UNISEG, 2863
high
SEG, 2325
UNISEG, 2863
highCommonTerms
DIV, 563
FAGROUP, 975
FAMONOID, 978
IFAMON, 1255
hitherPlane
VIEW3D, 2679
homogeneous
GOPT, 1075
GOPT0, 1081
homogeneous?
ANTISYM, 40
DERHAM, 517
HomogeneousDirectProduct, 1142
HomogeneousDistributedMultivariatePolynomial, 1149
homogenize
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
horizConcat
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
MATRIX, 1591
hspace
OUTFORM, 1834
HTMLFORM, 1122
?=?, 1122
? =?, 1122
coerce, 1122
coerceL, 1122
coerceS, 1122
display, 1122
exprex, 1122
hash, 1122
latex, 1122
HTMLFormat, 1122
hue
COLOR, 394
PALETTE, 1862
hyperelliptic
ALGFF, 28
RADFF, 2160
HyperellipticFiniteDivisor, 1153

IAN, 1244
-?, 1245
?<?, 1245
?<=?, 1245
?>?, 1245
?>=?, 1245
?**?, 1245
?*?, 1245
?+?, 1245
?-?, 1245
?/?, 1245
?=?, 1245
?^?, 1245
?~=?, 1245
?quo?, 1245
?rem?, 1245
0, 1245
1, 1245
associates?, 1245
belong?, 1245
box, 1245
characteristic, 1245
coerce, 1245
convert, 1245
D, 1245
definingPolynomial, 1245
denom, 1245
differentiate, 1245
distribute, 1245
divide, 1245
elt, 1245
euclideanSize, 1245
eval, 1245
even?, 1245
expressIdealMember, 1245
exquo, 1245
extendedEuclidean, 1245

factor, 1245
freeOf?, 1245
gcd, 1245
gcdPolynomial, 1245
hash, 1245
height, 1245
inv, 1245
is?, 1245
kernel, 1245
kernels, 1245
latex, 1245
lcm, 1245
mainKernel, 1245
map, 1245
max, 1245
min, 1245
minPoly, 1245
multiEuclidean, 1245
norm, 1245
nthRoot, 1245
numer, 1245
odd?, 1245
one?, 1245
operator, 1245
operators, 1245
paren, 1245
prime?, 1245
principalIdeal, 1245
recip, 1245
reduce, 1245
reducedSystem, 1245
retract, 1245
retractIfCan, 1245
rootOf, 1245
rootsOf, 1245
sample, 1245
sizeLess?, 1245
sqrt, 1245
squareFree, 1245
squareFreePart, 1245
subst, 1245
subtractIfCan, 1245
tower, 1245
trueEqual, 1245
unit?, 1245
unitCanonical, 1245
unitNormal, 1245
zero?, 1245
zeroOf, 1245
zerosOf, 1245
IARRAY1, 1212
?<?, 1213
?<=?, 1213
?>?, 1213
?>=?, 1213
?.?, 1213
?=?, 1213
?~=?, 1213
#?, 1213
any?, 1213
coerce, 1213
concat, 1213
construct, 1213
convert, 1213
copy, 1213
copyInto, 1213
count, 1213
delete, 1213
elt, 1213
empty, 1213
empty?, 1213
entries, 1213
entry?, 1213
eq?, 1213
eval, 1213
every?, 1213
fill, 1213
find, 1213
first, 1213
hash, 1213
index?, 1213
indices, 1213
insert, 1213
latex, 1213
less?, 1213
map, 1213
max, 1213
maxIndex, 1213
member?, 1213
members, 1213
merge, 1213
min, 1213

minIndex, 1213
more?, 1213
new, 1213
parts, 1213
position, 1213
qelt, 1213
qsetelt, 1213
reduce, 1213
remove, 1213
removeDuplicates, 1213
reverse, 1213
sample, 1213
select, 1213
setelt, 1213
size?, 1213
sort, 1213
sorted?, 1213
swap, 1213
IARRAY2, 1225
?=?, 1225
?~=?, 1225
#?, 1225
any?, 1225
coerce, 1225
column, 1225
copy, 1225
count, 1225
elt, 1225
empty, 1225
empty?, 1225
eq?, 1225
eval, 1225
every?, 1225
fill, 1225
hash, 1225
latex, 1225
less?, 1225
map, 1225
maxColIndex, 1225
maxRowIndex, 1225
member?, 1225
members, 1225
minColIndex, 1225
minRowIndex, 1225
more?, 1225
ncols, 1225
new, 1225
nrows, 1225
parts, 1225
qelt, 1225
qsetelt, 1225
row, 1225
sample, 1225
setColumn, 1225
setelt, 1225
setRow, 1225
size?, 1225
IBITS, 1169
?<?, 1169
?<=?, 1169
?>?, 1169
?>=?, 1169
?ΓE30F/?, 1169
?.?, 1169
?/ΓE30F?, 1169
?=?, 1169
?~=?, 1169
?and?, 1169
?or?, 1169
#?, 1169
^?, 1169
~?, 1169
And, 1169
any?, 1169
coerce, 1169
concat, 1169
construct, 1169
convert, 1169
copy, 1169
copyInto, 1169
count, 1169
delete, 1169
elt, 1169
empty, 1169
empty?, 1169
entries, 1169
entry?, 1169
eq?, 1169
eval, 1169
every?, 1169
fill, 1169
find, 1169

first, 1169
hash, 1169
index?, 1169
indices, 1169
insert, 1169
latex, 1169
less?, 1169
map, 1169
max, 1169
maxIndex, 1169
member?, 1169
members, 1169
merge, 1169
min, 1169
minIndex, 1169
more?, 1169
nand, 1169
new, 1169
nor, 1169
Not, 1169
not?, 1169
Or, 1169
parts, 1169
position, 1169
qelt, 1169
qsetelt, 1169
reduce, 1169
removeDuplicates, 1169
reverse, 1169
sample, 1169
select, 1169
size?, 1169
sort, 1169
sorted?, 1169
swap, 1169
xor, 1169
IC
?=?, 1161
?~=?, 1161
actualExtensionV, 1161
chartV, 1161
coerce, 1161
create, 1161
curveV, 1161
degree, 1161
excpDivV, 1161
fullOut, 1161
fullOutput, 1161
hash, 1161
latex, 1161
localParamV, 1161
localPointV, 1161
multV, 1161
pointV, 1161
setchart, 1161
setcurve, 1161
setexcpDiv, 1161
setlocalParam, 1161
setlocalPoint, 1161
setmult, 1161
setpoint, 1161
setsubmult, 1161
setsymbName, 1161
subMultV, 1161
symbNameV, 1161
ICARD, 1163
?<?, 1163
?<=?, 1163
?>?, 1163
?>=?, 1163
?.?, 1163
?=?, 1163
?~=?, 1163
coerce, 1163
display, 1163
fullDisplay, 1163
hash, 1163
latex, 1163
max, 1163
min, 1163
iCompose
ISUPS, 1279
ICP, 1160
IDEAL, 2047
?**?, 2047
?*?, 2047
?+?, 2047
?=?, 2047
?~=?, 2047
backOldPos, 2047
coerce, 2047
dimension, 2047

element?, 2047
generalPosition, 2047
generators, 2047
groebner, 2047
groebner?, 2047
groebnerIdeal, 2047
hash, 2047
ideal, 2047
in?, 2047
inRadical?, 2047
intersect, 2047
latex, 2047
leadingIdeal, 2047
one?, 2047
quotient, 2047
relationsIdeal, 2047
saturate, 2047
zero?, 2047
zeroDim?, 2047
ideal
FDIV, 783
FRIDEAL, 965
HELLFDIV, 1153
IDEAL, 2047
idealSimplify
QALGSET, 2123
identification
LEXP, 1403
identity
DHMATRIX, 479
identityMatrix
M3D, 2672
IDPAG, 1172
-?, 1172
?*?, 1172
?+?, 1172
?-?, 1172
?=?, 1172
?~=?, 1172
0, 1172
coerce, 1172
hash, 1172
latex, 1172
leadingCoefficient, 1172
leadingSupport, 1172
map, 1172
monomial, 1172
reductum, 1172
sample, 1172
subtractIfCan, 1172
zero?, 1172
IDPAM, 1175
?*?, 1176
?+?, 1176
?=?, 1176
?~=?, 1176
0, 1176
coerce, 1176
hash, 1176
latex, 1176
leadingCoefficient, 1176
leadingSupport, 1176
map, 1176
monomial, 1176
reductum, 1176
sample, 1176
zero?, 1176
IDPO, 1179
?=?, 1179
?~=?, 1179
coerce, 1179
hash, 1179
latex, 1179
leadingCoefficient, 1179
leadingSupport, 1179
map, 1179
monomial, 1179
reductum, 1179
IDPOAM, 1182
?<?, 1182
?<=?, 1182
?>?, 1182
?>=?, 1182
?*?, 1182
?+?, 1182
?=?, 1182
?~=?, 1182
0, 1182
coerce, 1182
hash, 1182
latex, 1182
leadingCoefficient, 1182

leadingSupport, 1182
map, 1182
max, 1182
min, 1182
monomial, 1182
reductum, 1182
sample, 1182
zero?, 1182
IDPOAMS, 1184
?<?, 1185
?<=?, 1185
?>?, 1185
?>=?, 1185
?*?, 1185
?+?, 1185
?=?, 1185
?~=?, 1185
0, 1185
coerce, 1185
hash, 1185
latex, 1185
leadingCoefficient, 1185
leadingSupport, 1185
map, 1185
max, 1185
min, 1185
monomial, 1185
reductum, 1185
sample, 1185
subtractIfCan, 1185
sup, 1185
zero?, 1185
iExquo
ISUPS, 1279
IFAMON, 1254
?*?, 1255
?+?, 1255
?=?, 1255
?~=?, 1255
0, 1255
coefficient, 1255
coerce, 1255
hash, 1255
highCommonTerms, 1255
latex, 1255
mapCoef, 1255
mapGen, 1255
nthCoef, 1255
nthFactor, 1255
retract, 1255
retractIfCan, 1255
sample, 1255
size, 1255
subtractIfCan, 1255
terms, 1255
zero?, 1255
IFARRAY, 1191
?<?, 1192
?<=?, 1192
?>?, 1192
?>=?, 1192
?.?, 1192
?=?, 1192
?~=?, 1192
#?, 1192
any?, 1192
coerce, 1192
concat, 1192
construct, 1192
convert, 1192
copy, 1192
copyInto, 1192
count, 1192
delete, 1192
elt, 1192
empty, 1192
empty?, 1192
entries, 1192
entry?, 1192
eq?, 1192
eval, 1192
every?, 1192
fill, 1192
find, 1192
first, 1192
flexibleArray, 1192
hash, 1192
index?, 1192
indices, 1192
insert, 1192
latex, 1192
less?, 1192

map, 1192
max, 1192
maxIndex, 1192
member?, 1192
members, 1192
merge, 1192
min, 1192
minIndex, 1192
more?, 1192
new, 1192
parts, 1192
physicalLength, 1192
position, 1192
qelt, 1192
qsetelt, 1192
reduce, 1192
remove, 1192
removeDuplicates, 1192
reverse, 1192
sample, 1192
select, 1192
setelt, 1192
shrinkable, 1192
size?, 1192
sort, 1192
sorted?, 1192
swap, 1192
IFF, 1251
-?, 1252
?**?, 1252
?*?, 1252
?+?, 1252
?-?, 1252
?/?, 1252
?=?, 1252
?^?, 1252
?~=?, 1252
?quo?, 1252
?rem?, 1252
0, 1252
1, 1252
algebraic?, 1252
associates?, 1252
basis, 1252
characteristic, 1252
charthRoot, 1252
coerce, 1252
conditionP, 1252
coordinates, 1252
createNormalElement, 1252
createPrimitiveElement, 1252
D, 1252
definingPolynomial, 1252
degree, 1252
differentiate, 1252
dimension, 1252
discreteLog, 1252
divide, 1252
euclideanSize, 1252
expressIdealMember, 1252
exquo, 1252
extendedEuclidean, 1252
extensionDegree, 1252
factor, 1252
factorsOfCyclicGroupSize, 1252
Frobenius, 1252
gcd, 1252
gcdPolynomial, 1252
generator, 1252
hash, 1252
index, 1252
inGroundField?, 1252
init, 1252
inv, 1252
latex, 1252
lcm, 1252
linearAssociatedExp, 1252
linearAssociatedLog, 1252
linearAssociatedOrder, 1252
lookup, 1252
minimalPolynomial, 1252
multiEuclidean, 1252
nextItem, 1252
norm, 1252
normal?, 1252
normalElement, 1252
one?, 1252
order, 1252
prime?, 1252
primeFrobenius, 1252
primitive?, 1252
primitiveElement, 1252

principalIdeal, 1252
random, 1252
recip, 1252
representationType, 1252
represents, 1252
retract, 1252
retractIfCan, 1252
sample, 1252
size, 1252
sizeLess?, 1252
squareFree, 1252
squareFreePart, 1252
subtractIfCan, 1252
tableForDiscreteLogarithm, 1252
trace, 1252
transcendenceDegree, 1252
transcendent?, 1252
unit?, 1252
unitCanonical, 1252
unitNormal, 1252
zero?, 1252
iFTable
ODEIFTBL, 1734
IIARRAY2, 1258
?=?, 1258
?~=?, 1258
#?, 1258
any?, 1258
coerce, 1258
column, 1258
copy, 1258
count, 1258
elt, 1258
empty, 1258
empty?, 1258
eq?, 1258
eval, 1258
every?, 1258
fill, 1258
hash, 1258
latex, 1258
less?, 1258
map, 1258
maxColIndex, 1258
maxRowIndex, 1258
member?, 1258
members, 1258
minColIndex, 1258
minRowIndex, 1258
more?, 1258
ncols, 1258
new, 1258
nrows, 1258
parts, 1258
qelt, 1258
qsetelt, 1258
row, 1258
sample, 1258
setColumn, 1258
setelt, 1258
setRow, 1258
size?, 1258
ILIST, 1200
?<?, 1201
?<=?, 1201
?>?, 1201
?>=?, 1201
?.?, 1201
?.first, 1201
?.last, 1201
?.rest, 1201
?.value, 1201
?=?, 1201
?~=?, 1201
#?, 1201
any?, 1201
child?, 1201
children, 1201
coerce, 1201
concat, 1201
construct, 1201
convert, 1201
copy, 1201
copyInto, 1201
count, 1201
cycleEntry, 1201
cycleLength, 1201
cycleSplit, 1201
cycleTail, 1201
cyclic?, 1201
delete, 1201
distance, 1201

elt, 1201
empty, 1201
empty?, 1201
entries, 1201
entry?, 1201
eq?, 1201
eval, 1201
every?, 1201
explicitlyFinite?, 1201
fill, 1201
find, 1201
first, 1201
hash, 1201
index?, 1201
indices, 1201
insert, 1201
last, 1201
latex, 1201
leaf?, 1201
leaves, 1201
less?, 1201
list, 1201
map, 1201
max, 1201
maxIndex, 1201
member?, 1201
members, 1201
merge, 1201
min, 1201
minIndex, 1201
more?, 1201
new, 1201
node?, 1201
nodes, 1201
parts, 1201
position, 1201
possiblyInfinite?, 1201
qelt, 1201
qsetelt, 1201
reduce, 1201
remove, 1201
removeDuplicates, 1201
rest, 1201
reverse, 1201
sample, 1201
second, 1201
select, 1201
setchildren, 1201
setelt, 1201
setfirst, 1201
setlast, 1201
setrest, 1201
setvalue, 1201
size?, 1201
sort, 1201
sorted?, 1201
split, 1201
swap, 1201
tail, 1201
third, 1201
value, 1201
imag
COMPLEX, 406
MCMPLX, 1511
imagE
OCT, 1731
images
ACPLOT, 1958
AFFPL, 4
AFFPLPS, 7
AFFSP, 9
ALGFF, 28
ALGSC, 14
ALIST, 220
AN, 35
ANON, 38
ANTISYM, 40
ANY, 50
ARRAY1, 1740
ARRAY2, 2732
ASP1, 71
ASP10, 75
ASP12, 79
ASP19, 82
ASP20, 89
ASP24, 95
ASP27, 99
ASP28, 102
ASP29, 108
ASP30, 111
ASP31, 115
ASP33, 120

ASP34, 123
ASP35, 127
ASP4, 132
ASP41, 136
ASP42, 142
ASP49, 149
ASP50, 153
ASP55, 159
ASP6, 164
ASP7, 169
ASP73, 174
ASP74, 178
ASP77, 184
ASP78, 189
ASP8, 193
ASP80, 197
ASP9, 202
ASTACK, 65
ATTRBUT, 224
AUTOMOR, 230
BBTREE, 236
BFUNCT, 249
BINARY, 276
BINFILE, 279
BITS, 299
BLHN, 301
BLQT, 304
BOOLEAN, 306
BOP, 258
BPADIC, 242
BPADICRT, 247
BSD, 270
BSTREE, 287
BTOURN, 291
BTREE, 294
CARD, 318
CARTEN, 342
CCLASS, 367
CDFMAT, 413
CDFVEC, 419
CHAR, 359
CLIF, 388
COLOR, 394
COMM, 397
COMPLEX, 405
COMPPROP, 2592
CONTFRAC, 432
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01ANFA, 614
D01APFA, 617
D01AQFA, 620
D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
DBASE, 442
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 574
DFMAT, 586
DFVEC, 592
DHMATRIX, 478
DIRPROD, 534
DIRRING, 551
DIV, 563
DLIST, 447
DMP, 559
DPMM, 540
DPMO, 544
DROPT, 595
DSMP, 528
DSTREE, 522
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 731
E04NAFA, 735
E04UCFA, 738
EAB, 713
EMR, 672
EQ, 661

EQTBL, 669
EXIT, 677
EXPEXPAN, 681
EXPR, 693
EXPUPXS, 709
FAGROUP, 974
FAMONOID, 977
FARRAY, 856
FC, 901
FCOMP, 945
FDIV, 783
FEXPR, 917
FF, 789
FFCG, 794
FFCGP, 804
FFCGX, 799
FFNB, 829
FFNBP, 841
FFNBX, 835
FFP, 820
FFX, 815
FGROUP, 980
FILE, 772
FLOAT, 878
FM, 983
FM1, 987
FMONOID, 991
FNAME, 780
FNLA, 997
FORMULA, 2312
FORTRAN, 926
FPARFRAC, 1010
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
FST, 932
FT, 941
FTEM, 937
FUNCTION, 1015
GCNAALG, 1034
GDMP, 1022
GMODPOL, 1029
GOPT, 1075
GOPT0, 1081
GPOLSET, 1044
GRIMAGE, 1065
GSERIES, 1060
GSTBL, 1048
GTSET, 1053
HACKPI, 1943
HASHTBL, 1089
HDMP, 1149
HDP, 1142
HEAP, 1104
HELLFDIV, 1153
HEXADEC, 1112
HTMLFORM, 1122
IAN, 1244
IARRAY1, 1212
IARRAY2, 1225
IBITS, 1169
ICARD, 1163
ICP, 1160
IDEAL, 2047
IDPAG, 1172
IDPAM, 1175
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1184
IFAMON, 1254
IFARRAY, 1191
IFF, 1251
IIARRAY2, 1258
ILIST, 1200
IMATRIX, 1208
INDE, 1187
INFCLSPS, 1239
INFCLSPT, 1234
INFORM, 1311
INT, 1329
INTABL, 1303
INTFTBL, 1339
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1278
ITAYLOR, 1306
ITUPLE, 1231

IVECTOR, 1229
JORDAN, 208
KAFILE, 1381
KERNEL, 1372
LA, 1488
LAUPOL, 1389
LEXP, 1403
LIB, 1396
LIE, 213
LIST, 1472
LMDICT, 1483
LMOPS, 1477
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1414
LSQM, 1423
LWORD, 1500
M3D, 2671
MAGMA, 1533
MATRIX, 1590
MCMPLX, 1510
MFLOAT, 1515
MINT, 1525
MKCHSET, 1538
MMLFORM, 1571
MODFIELD, 1606
MODMON, 1599
MODMONOM, 1612
MODOP, 1615
MODRING, 1608
MOEBIUS, 1622
MPOLY, 1649
MRING, 1626
MSET, 1638
MYEXPR, 1655
MYUP, 1662
NIPROB, 1713
NNI, 1706
NONE, 1704
NOTTING, 1711
NSDPS, 1669
NSMP, 1680
NSUP, 1695
OCT, 1731
ODEIFTBL, 1734
ODEPROB, 1716
ODP, 1783
ODPOL, 1817
ODR, 1824
ODVAR, 1821
OFMONOID, 1795
OMCONN, 1747
OMDEV, 1750
OMENC, 1755
OMERR, 1758
OMERRK, 1761
OMLO, 1773
ONECOMP, 1743
OP, 1770
OPTPROB, 1719
ORDCOMP, 1776
ORESUP, 2459
OREUP, 2839
OSI, 1830
OUTFORM, 1833
OVAR, 1803
OWP, 1827
PACEXT, 2092
PACOFF, 2101
PACRAT, 2112
PADIC, 1847
PADICRAT, 1851
PADICRC, 1856
PALETTE, 1862
PARPCURV, 1865
PARSCURV, 1868
PARSURF, 1870
PATLRES, 1903
PATRES, 1906
PATTERN, 1894
PBWLB, 2020
PDEPROB, 1722
PENDTREE, 1911
PERM, 1915
PERMGRP, 1926
PF, 2070
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987

PLCS, 1989
PLOT, 1995
PLOT3D, 2008
POINT, 2025
POLY, 2043
PR, 2058
PRIMARR, 2075
PRODUCT, 2078
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2087
PRTITION, 1889
QALGSET, 2123
QEQUAT, 2135
QFORM, 2120
QUAT, 2132
QUEUE, 2150
RADFF, 2159
RADIX, 2171
RECLOS, 2202
REF, 2215
REGSET, 2251
RESRING, 2262
RESULT, 2266
RGCHAIN, 2220
RMATRIX, 2211
ROIRC, 2276
ROMAN, 2292
ROUTINE, 2297
RULE, 2271
RULECOLD, 2307
RULESET, 2309
SAE, 2368
SAOS, 2386
SD, 2539
SDPOL, 2351
SDVAR, 2357
SEG, 2325
SEGBIND, 2330
SET, 2338
SETMN, 2344
SEX, 2360
SEXOF, 2362
SFORT, 2373
SHDP, 2476
SINT, 2380
SMP, 2390
SMTS, 2408
SPACE3, 2700
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2514
SREGSET, 2501
STACK, 2530
STBL, 2418
STREAM, 2549
STRING, 2574
STRTBL, 2578
SUBSPACE, 2582
SUCH, 2595
SULS, 2424
SUP, 2434
SUPEXPR, 2448
SUPXS, 2454
SUTS, 2464
SWITCH, 2597
SYMBOL, 2608
SYMPOLY, 2622
SYMS, 2665
SYMTAB, 2616
TABLE, 2631
TABLEAU, 2634
TEX, 2645
TEXTFILE, 2661
TREE, 2710
TS, 2638
TUBE, 2718
TUPLE, 2721
U32VEC, 2868
UFPS, 2756
ULS, 2762
ULSCONS, 2770
UNISEG, 2863
UP, 2794
UPXS, 2800
UPXSCONS, 2808
UPXSSING, 2819
UTS, 2844
UTSZ, 2853
VARIABLE, 2872
VECTOR, 2877
VIEW2D, 2738

VIEW3D, 2679
VOID, 2881
WP, 2884
WUTSET, 2894
XDPOLY, 2905
XPBWPOLY, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1335
imagI
OCT, 1731
QUAT, 2133
imagi
OCT, 1731
imaginary
COMPLEX, 406
MCMPLX, 1511
imagJ
OCT, 1731
QUAT, 2133
imagj
OCT, 1731
imagK
OCT, 1731
QUAT, 2133
imagk
OCT, 1731
IMATRIX, 1208
-?, 1208
?**?, 1208
?*?, 1208
?+?, 1208
?-?, 1208
?/?, 1208
?=?, 1208
?~=?, 1208
#?, 1208
antisymmetric?, 1208
any?, 1208
coerce, 1208
column, 1208
copy, 1208
count, 1208
determinant, 1208
diagonal?, 1208
diagonalMatrix, 1208
elt, 1208
empty, 1208
empty?, 1208
eq?, 1208
eval, 1208
every?, 1208
exquo, 1208
fill, 1208
hash, 1208
horizConcat, 1208
inverse, 1208
latex, 1208
less?, 1208
listOfLists, 1208
map, 1208
matrix, 1208
maxColIndex, 1208
maxRowIndex, 1208
member?, 1208
members, 1208
minColIndex, 1208
minordet, 1208
minRowIndex, 1208
more?, 1208
ncols, 1208
new, 1208
nrows, 1208
nullity, 1208
nullSpace, 1208
parts, 1208
qelt, 1208
qsetelt, 1208
rank, 1208
row, 1208
rowEchelon, 1208
sample, 1208
scalarMatrix, 1208
setColumn, 1208
setelt, 1208
setRow, 1208
setsubMatrix, 1208
size?, 1208
square?, 1208
squareTop, 1208
subMatrix, 1208

swapColumns, 1208
swapRows, 1208
symmetric?, 1208
transpose, 1208
vertConcat, 1208
zero, 1208
implies
BOOLEAN, 307
in?
IDEAL, 2047
inc
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
incr
DIV, 563
SEG, 2325
UNISEG, 2863
increase
ATTRBUT, 224
increasePrecision
DFLOAT, 575
FLOAT, 879
MFLOAT, 1516
incrementKthElement
SETMN, 2344
INDE, 1187
?<?, 1187
?<=?, 1187
?>?, 1187
?>=?, 1187
?*?, 1187
?+?, 1187
?=?, 1187
?~=?, 1187
0, 1187
coerce, 1187
hash, 1187
latex, 1187
leadingCoefficient, 1187
leadingSupport, 1187
map, 1187
max, 1187
min, 1187
monomial, 1187
reductum, 1187
sample, 1187
subtractIfCan, 1187
sup, 1187
zero?, 1187
index
ALGFF, 28
BOOLEAN, 307
CCLASS, 368
CHAR, 359
COMPLEX, 406
DIRPROD, 534
DPMM, 540
DPMO, 545
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
HDP, 1143
IFF, 1252
IPF, 1271
MCMPLX, 1511
MODMON, 1600
MODMONOM, 1612
MRING, 1626
OCT, 1731
ODP, 1783
OVAR, 1803
PACOFF, 2102
PF, 2071
PRODUCT, 2079
RADFF, 2160
SAE, 2368
SET, 2338
SETMN, 2344
SHDP, 2476
ZMOD, 1336
index?
ALIST, 221
ARRAY1, 1740
BITS, 299

CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
IndexCard, 1163
IndexedBits, 1169
IndexedDirectProductAbelianGroup, 1172
IndexedDirectProductAbelianMonoid, 1175
IndexedDirectProductObject, 1179
IndexedDirectProductOrderedAbelianMonoid, 1182
IndexedDirectProductOrderedAbelianMonoidSup, 1184
IndexedExponents, 1187
IndexedFlexibleArray, 1191
IndexedList, 1200
IndexedMatrix, 1208
IndexedOneDimensionalArray, 1212
IndexedString, 1218
IndexedTwoDimensionalArray, 1225
IndexedVector, 1229
indexName
GOPT, 1075
GOPT0, 1081
indices
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632

U32VEC, 2869
VECTOR, 2878
inf
INTRVL, 1352
INFCLSPS, 1239
?=?, 1240
?~=?, 1240
actualExtensionV, 1240
chartV, 1240
coerce, 1240
create, 1240
curveV, 1240
degree, 1240
excpDivV, 1240
fullOut, 1240
fullOutput, 1240
hash, 1240
latex, 1240
localParamV, 1240
localPointV, 1240
multV, 1240
pointV, 1240
setchart, 1240
setcurve, 1240
setexcpDiv, 1240
setlocalParam, 1240
setlocalPoint, 1240
setmult, 1240
setpoint, 1240
setsubmult, 1240
setsymbName, 1240
subMultV, 1240
symbNameV, 1240
INFCLSPT, 1234
?=?, 1234
?~=?, 1234
actualExtensionV, 1234
chartV, 1234
coerce, 1234
create, 1234
curveV, 1234
degree, 1234
excpDivV, 1234
fullOut, 1234
fullOutput, 1234
hash, 1234
latex, 1234
localParamV, 1234
localPointV, 1234
multV, 1234
pointV, 1234
setchart, 1234
setcurve, 1234
setexcpDiv, 1234
setlocalParam, 1234
setlocalPoint, 1234
setmult, 1234
setpoint, 1234
setsubmult, 1234
setsymbName, 1234
subMultV, 1234
symbNameV, 1234
InfClsPt, 1160
infClsPt?
BLHN, 301
BLQT, 304
infinite?
ONECOMP, 1744
ORDCOMP, 1777
InfiniteTuple, 1231
InfinitlyClosePoint, 1234
InfinitlyClosePointOverPseudoAlgebraicClosureOfFiniteField, 1239
infinity
ONECOMP, 1744
infix
OUTFORM, 1834
infix?
OUTFORM, 1834
infLex?
SPLNODE, 2479
INFORM, 1311
?**?, 1311
?*?, 1311
?+?, 1311
?.?, 1311
?/?, 1311
?=?, 1311
?~=?, 1311
#?, 1311
0, 1311
1, 1311

atom?, 1311
binary, 1311
car, 1311
cdr, 1311
coerce, 1311
compile, 1311
convert, 1311
declare, 1311
destruct, 1311
eq, 1311
expr, 1311
flatten, 1311
float, 1311
float?, 1311
function, 1311
hash, 1311
integer, 1311
integer?, 1311
interpret, 1311
lambda, 1311
latex, 1311
list?, 1311
null?, 1311
pair?, 1311
parse, 1311
string, 1311
string?, 1311
symbol, 1311
symbol?, 1311
unparse, 1311
infRittWu?
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
inGroundField?
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PACOFF, 2102
PACRAT, 2112
PF, 2071
init
ALGFF, 28
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
EXPEXPAN, 682
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FRAC, 956
HEXADEC, 1113
IFF, 1252
INT, 1330
IPF, 1271
MCMPLX, 1511
MINT, 1525
MODMON, 1600
MYUP, 1663
NSMP, 1681
NSUP, 1696
PACOFF, 2102
PADICRAT, 1852
PADICRC, 1857
PF, 2071
RADFF, 2160
RADIX, 2172
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763

ULSCONS, 2771
UP, 2795
ZMOD, 1336
initial
DSMP, 529
ODPOL, 1818
SDPOL, 2352
initializeGroupForWordProblem
PERMGRP, 1926
initiallyReduce
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
initiallyReduced?
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
initials
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
InnerAlgebraicNumber, 1244
InnerFiniteField, 1251
InnerFreeAbelianMonoid, 1254
InnerIndexedTwoDimensionalArray, 1258
InnerPAdicInteger, 1262
InnerPrimeField, 1271
InnerSparseUnivariatePowerSeries, 1278
InnerTable, 1303
InnerTaylorSeries, 1306
input
BOP, 258
InputForm, 1311
inR?
PATTERN, 1894
inRadical?
IDEAL, 2047
insert
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
NSDPS, 1670
POINT, 2026
PRIMARR, 2075
STREAM, 2550
STRING, 2575
U32VEC, 2869
VECTOR, 2878
insertMatch
PATRES, 1906
inspect
ALIST, 221
ASTACK, 65
CCLASS, 368
DEQUEUE, 499
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
HEAP, 1104
INTABL, 1304
KAFILE, 1382
LIB, 1397
LMDICT, 1483
MSET, 1638
QUEUE, 2150
RESULT, 2267
ROUTINE, 2298
SET, 2338
STACK, 2530
STBL, 2418
STRTBL, 2578
TABLE, 2632
INT, 1329

-?, 1330
?<?, 1330
?<=?, 1330
?>?, 1330
?>=?, 1330
?**?, 1330
?*?, 1330
?+?, 1330
?-?, 1330
?=?, 1330
?^?, 1330
?~=?, 1330
?quo?, 1330
?rem?, 1330
0, 1330
1, 1330
abs, 1330
addmod, 1330
associates?, 1330
base, 1330
binomial, 1330
bit?, 1330
characteristic, 1330
coerce, 1330
convert, 1330
copy, 1330
D, 1330
dec, 1330
differentiate, 1330
divide, 1330
euclideanSize, 1330
even?, 1330
expressIdealMember, 1330
exquo, 1330
extendedEuclidean, 1330
factor, 1330
factorial, 1330
gcd, 1330
gcdPolynomial, 1330
hash, 1330
inc, 1330
init, 1330
invmod, 1330
latex, 1330
lcm, 1330
length, 1330
mask, 1330
max, 1330
min, 1330
mulmod, 1330
multiEuclidean, 1330
negative?, 1330
nextItem, 1330
odd?, 1330
OMwrite, 1330
one?, 1330
patternMatch, 1330
permutation, 1330
positive?, 1330
positiveRemainder, 1330
powmod, 1330
prime?, 1330
principalIdeal, 1330
random, 1330
rational, 1330
rational?, 1330
rationalIfCan, 1330
recip, 1330
reducedSystem, 1330
retract, 1330
retractIfCan, 1330
sample, 1330
shift, 1330
sign, 1330
sizeLess?, 1330
squareFree, 1330
squareFreePart, 1330
submod, 1330
subtractIfCan, 1330
symmetricRemainder, 1330
unit?, 1330
unitCanonical, 1330
unitNormal, 1330
zero?, 1330
int
OUTFORM, 1834
INTABL, 1303
?.?, 1304
?=?, 1304
?~=?, 1304
#?, 1304
any?, 1304

bag, 1304
coerce, 1304
construct, 1304
convert, 1304
copy, 1304
count, 1304
dictionary, 1304
elt, 1304
empty, 1304
empty?, 1304
entries, 1304
entry?, 1304
eq?, 1304
eval, 1304
every?, 1304
extract, 1304
fill, 1304
find, 1304
first, 1304
hash, 1304
index?, 1304
indices, 1304
insert, 1304
inspect, 1304
key?, 1304
keys, 1304
latex, 1304
less?, 1304
map, 1304
maxIndex, 1304
member?, 1304
members, 1304
minIndex, 1304
more?, 1304
parts, 1304
qelt, 1304
qsetelt, 1304
reduce, 1304
remove, 1304
removeDuplicates, 1304
sample, 1304
search, 1304
select, 1304
setelt, 1304
size?, 1304
swap, 1304
table, 1304
Integer, 1329
integer
INFORM, 1311
SEX, 2360
SEXOF, 2363
integer?
FST, 933
INFORM, 1311
SEX, 2360
SEXOF, 2363
integerDecode
DFLOAT, 575
IntegerMod, 1335
integral
EXPR, 694
IR, 1343
integral?
ALGFF, 28
RADFF, 2160
integralAtInfinity?
ALGFF, 28
RADFF, 2160
integralBasis
ALGFF, 28
RADFF, 2160
integralBasisAtInfinity
ALGFF, 28
RADFF, 2160
integralCoordinates
ALGFF, 28
RADFF, 2160
integralDerivationMatrix
ALGFF, 28
RADFF, 2160
integralMatrix
ALGFF, 28
RADFF, 2160
integralMatrixAtInfinity
ALGFF, 28
RADFF, 2160
integralRepresents
ALGFF, 28
RADFF, 2160
integrate
EXPUPXS, 710

GSERIES, 1061
ISUPS, 1279
MODMON, 1600
MYUP, 1663
NSUP, 1696
POLY, 2044
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
IntegrationFunctionsTable, 1339
IntegrationResult, 1343
intensity
VIEW3D, 2679
internal?
SUBSPACE, 2582
internalAugment
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
internalZeroSetSplit
REGSET, 2252
SREGSET, 2502
interpret
INFORM, 1311
intersect
CCLASS, 368
IDEAL, 2047
MSET, 1638
REGSET, 2252
RGCHAIN, 2221
SET, 2338
SREGSET, 2502
Interval, 1352
interval
INTRVL, 1352
INTFTBL, 1339
clearTheFTable, 1339
entries, 1339
entry, 1339
fTable, 1339
insert, 1339
keys, 1339
showAttributes, 1339
showTheFTable, 1339
INTRVL, 1352
-?, 1352
?<?, 1352
?<=?, 1352
?>?, 1352
?>=?, 1352
?**?, 1352
?*?, 1352
?+?, 1352
?-?, 1352
?=?, 1352
?^?, 1352
?~=?, 1352
0, 1352
1, 1352
acos, 1352
acosh, 1352
acot, 1352
acoth, 1352
acsc, 1352
acsch, 1352
asec, 1352
asech, 1352
asin, 1352
asinh, 1352
associates?, 1352
atan, 1352
atanh, 1352
characteristic, 1352
coerce, 1352
contains?, 1352
cos, 1352
cosh, 1352
cot, 1352
coth, 1352
csc, 1352

csch, 1352
exp, 1352
exquo, 1352
gcd, 1352
gcdPolynomial, 1352
hash, 1352
inf, 1352
interval, 1352
latex, 1352
lcm, 1352
log, 1352
max, 1352
min, 1352
negative?, 1352
nthRoot, 1352
one?, 1352
pi, 1352
positive?, 1352
qinterval, 1352
recip, 1352
retract, 1352
retractIfCan, 1352
sample, 1352
sec, 1352
sech, 1352
sin, 1352
sinh, 1352
sqrt, 1352
subtractIfCan, 1352
sup, 1352
tan, 1352
tanh, 1352
unit?, 1352
unitCanonical, 1352
unitNormal, 1352
width, 1352
zero?, 1352
inv
ALGFF, 28
AN, 35
AUTOMOR, 231
BINARY, 277
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FRAC, 956
FRIDEAL, 965
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
IPF, 1271
LEXP, 1403
MCMPLX, 1511
MFLOAT, 1516
MODFIELD, 1606
MODRING, 1609
MOEBIUS, 1622
MYEXPR, 1656
NOTTING, 1711
NSDPS, 1670
OCT, 1731
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PERM, 1916
PF, 2071
PFR, 1880
PRODUCT, 2079
QUAT, 2133
RADFF, 2160

RADIX, 2172
RECLOS, 2203
SAE, 2368
SULS, 2425
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
inverse
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
SQMATRIX, 2515
inverseIntegralMatrix
ALGFF, 28
RADFF, 2160
inverseIntegralMatrixAtInfinity
ALGFF, 28
RADFF, 2160
invertible?
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
invertibleElseSplit?
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
invertibleSet
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
invmod
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
invmultisect
UFPS, 2757
UTS, 2844
UTSZ, 2854
iomode
BINFILE, 280
FILE, 772
FTEM, 938
KAFILE, 1382
TEXTFILE, 2661
IPADIC, 1262
-?, 1262
?**?, 1262
?*?, 1262
?+?, 1262
?-?, 1262
?=?, 1262
?^?, 1262
?~=?, 1262
?quo?, 1262
?rem?, 1262
0, 1262
1, 1262
approximate, 1262
associates?, 1262
characteristic, 1262
coerce, 1262
complete, 1262
digits, 1262
divide, 1262
euclideanSize, 1262
expressIdealMember, 1262
exquo, 1262
extend, 1262
extendedEuclidean, 1262
gcd, 1262
gcdPolynomial, 1262
hash, 1262
latex, 1262
lcm, 1262
moduloP, 1262
modulus, 1262
multiEuclidean, 1262
one?, 1262
order, 1262
principalIdeal, 1262
quotientByP, 1262
recip, 1262
root, 1262
sample, 1262
sizeLess?, 1262
sqrt, 1262

subtractIfCan, 1262
unit?, 1262
unitCanonical, 1262
unitNormal, 1262
zero?, 1262
IPF, 1271
-?, 1271
?**?, 1271
?*?, 1271
?+?, 1271
?-?, 1271
?/?, 1271
?=?, 1271
?^?, 1271
?~=?, 1271
?quo?, 1271
?rem?, 1271
0, 1271
1, 1271
algebraic?, 1271
associates?, 1271
basis, 1271
characteristic, 1271
charthRoot, 1271
coerce, 1271
conditionP, 1271
convert, 1271
coordinates, 1271
createNormalElement, 1271
createPrimitiveElement, 1271
D, 1271
definingPolynomial, 1271
degree, 1271
differentiate, 1271
dimension, 1271
discreteLog, 1271
divide, 1271
euclideanSize, 1271
expressIdealMember, 1271
exquo, 1271
extendedEuclidean, 1271
extensionDegree, 1271
factor, 1271
factorsOfCyclicGroupSize, 1271
Frobenius, 1271
gcd, 1271
gcdPolynomial, 1271
generator, 1271
hash, 1271
index, 1271
inGroundField?, 1271
init, 1271
inv, 1271
latex, 1271
lcm, 1271
linearAssociatedExp, 1271
linearAssociatedLog, 1271
linearAssociatedOrder, 1271
lookup, 1271
minimalPolynomial, 1271
multiEuclidean, 1271
nextItem, 1271
norm, 1271
normal?, 1271
normalElement, 1271
one?, 1271
order, 1271
prime?, 1271
primeFrobenius, 1271
primitive?, 1271
primitiveElement, 1271
principalIdeal, 1271
random, 1271
recip, 1271
representationType, 1271
represents, 1271
retract, 1271
retractIfCan, 1271
sample, 1271
size, 1271
sizeLess?, 1271
squareFree, 1271
squareFreePart, 1271
subtractIfCan, 1271
tableForDiscreteLogarithm, 1271
trace, 1271
transcendenceDegree, 1271
transcendent?, 1271
unit?, 1271
unitCanonical, 1271
unitNormal, 1271
zero?, 1271

IR, 1343
-?, 1343
?*?, 1343
?+?, 1343
?-?, 1343
?=?, 1343
?~=?, 1343
0, 1343
coerce, 1343
differentiate, 1343
elem?, 1343
hash, 1343
integral, 1343
latex, 1343
logpart, 1343
mkAnswer, 1343
notelem, 1343
ratpart, 1343
retract, 1343
retractIfCan, 1343
sample, 1343
subtractIfCan, 1343
zero?, 1343
irreducibleFactor
FR, 756
is?
AN, 35
BOP, 258
EXPR, 694
FEXPR, 917
IAN, 1245
KERNEL, 1372
MYEXPR, 1656
isExpt
DMP, 560
DSMP, 529
EXPR, 694
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PATTERN, 1894
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
isList
PATTERN, 1894
isMult
EXPR, 694
MYEXPR, 1656
isobaric?
DSMP, 529
ODPOL, 1818
SDPOL, 2352
isOp
PATTERN, 1894
isPlus
DMP, 560
DSMP, 529
EXPR, 694
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PATTERN, 1894
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
isPower
EXPR, 694
MYEXPR, 1656
PATTERN, 1894
isQuotient
PATTERN, 1894
isTimes
DMP, 560

DSMP, 529
EXPR, 694
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PATTERN, 1894
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
ISTRING, 1218
?<?, 1218
?<=?, 1218
?>?, 1218
?>=?, 1218
?.?, 1218
?=?, 1218
?~=?, 1218
#?, 1218
any?, 1218
coerce, 1218
concat, 1218
construct, 1218
convert, 1218
copy, 1218
copyInto, 1218
count, 1218
delete, 1218
elt, 1218
empty, 1218
empty?, 1218
entries, 1218
entry?, 1218
eq?, 1218
eval, 1218
every?, 1218
fill, 1218
find, 1218
first, 1218
hash, 1218
index?, 1218
indices, 1218
insert, 1218
latex, 1218
leftTrim, 1218
less?, 1218
lowerCase, 1218
map, 1218
match, 1218
match?, 1218
max, 1218
maxIndex, 1218
member?, 1218
members, 1218
merge, 1218
min, 1218
minIndex, 1218
more?, 1218
new, 1218
parts, 1218
position, 1218
prefix?, 1218
qelt, 1218
qsetelt, 1218
reduce, 1218
remove, 1218
removeDuplicates, 1218
replace, 1218
reverse, 1218
rightTrim, 1218
sample, 1218
select, 1218
setelt, 1218
size?, 1218
sort, 1218
sorted?, 1218
split, 1218
substring?, 1218
suffix?, 1218
swap, 1218
trim, 1218
upperCase, 1218
ISUPS, 1278
-?, 1279

?**?, 1279
?*?, 1279
?+?, 1279
?-?, 1279
?.?, 1279
?/?, 1279
?=?, 1279
?^?, 1279
?~=?, 1279
0, 1279
1, 1279
approximate, 1279
associates?, 1279
cAcos, 1279
cAcosh, 1279
cAcot, 1279
cAcoth, 1279
cAcsc, 1279
cAcsch, 1279
cAsec, 1279
cAsech, 1279
cAsin, 1279
cAsinh, 1279
cAtan, 1279
cAtanh, 1279
cCos, 1279
cCosh, 1279
cCot, 1279
cCoth, 1279
cCsc, 1279
cCsch, 1279
center, 1279
cExp, 1279
characteristic, 1279
charthRoot, 1279
cLog, 1279
coefficient, 1279
coerce, 1279
complete, 1279
cPower, 1279
cRationalPower, 1279
cSec, 1279
cSech, 1279
cSin, 1279
cSinh, 1279
cTan, 1279
cTanh, 1279
D, 1279
degree, 1279
differentiate, 1279
eval, 1279
exquo, 1279
extend, 1279
getRef, 1279
getStream, 1279
hash, 1279
iCompose, 1279
iExquo, 1279
integrate, 1279
latex, 1279
leadingCoefficient, 1279
leadingMonomial, 1279
makeSeries, 1279
map, 1279
monomial, 1279
monomial?, 1279
multiplyCoefficients, 1279
multiplyExponents, 1279
one?, 1279
order, 1279
pole?, 1279
recip, 1279
reductum, 1279
sample, 1279
series, 1279
seriesToOutputForm, 1279
subtractIfCan, 1279
taylorQuoByVar, 1279
terms, 1279
truncate, 1279
unit?, 1279
unitCanonical, 1279
unitNormal, 1279
variable, 1279
variables, 1279
zero?, 1279
ITAYLOR, 1306
-?, 1306
?**?, 1306
?*?, 1306
?+?, 1306
?-?, 1306

?=?, 1306
?^?, 1306
?~=?, 1306
0, 1306
1, 1306
associates?, 1306
characteristic, 1306
coefficients, 1306
coerce, 1306
exquo, 1306
hash, 1306
latex, 1306
one?, 1306
order, 1306
pole?, 1306
recip, 1306
sample, 1306
series, 1306
subtractIfCan, 1306
unit?, 1306
unitCanonical, 1306
unitNormal, 1306
zero?, 1306
iteratedInitials
NSMP, 1681
ITUPLE, 1231
coerce, 1231
construct, 1231
filterUntil, 1231
filterWhile, 1231
generate, 1231
map, 1231
select, 1231
IVECTOR, 1229
-?, 1229
?<?, 1229
?<=?, 1229
?>?, 1229
?>=?, 1229
?*?, 1229
?+?, 1229
?-?, 1229
?.?, 1229
?=?, 1229
?~=?, 1229
#?, 1229
any?, 1229
coerce, 1229
concat, 1229
construct, 1229
convert, 1229
copy, 1229
copyInto, 1229
count, 1229
cross, 1229
delete, 1229
dot, 1229
elt, 1229
empty, 1229
empty?, 1229
entries, 1229
entry?, 1229
eq?, 1229
eval, 1229
every?, 1229
fill, 1229
find, 1229
first, 1229
hash, 1229
index?, 1229
indices, 1229
insert, 1229
latex, 1229
length, 1229
less?, 1229
magnitude, 1229
map, 1229
max, 1229
maxIndex, 1229
member?, 1229
members, 1229
merge, 1229
min, 1229
minIndex, 1229
more?, 1229
new, 1229
outerProduct, 1229
parts, 1229
position, 1229
qelt, 1229
qsetelt, 1229
reduce, 1229

remove, 1229
removeDuplicates, 1229
reverse, 1229
sample, 1229
select, 1229
setelt, 1229
size?, 1229
sort, 1229
sorted?, 1229
swap, 1229
zero, 1229

jacobiIdentity?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
JORDAN, 208
-?, 209
?**?, 209
?*?, 209
?+?, 209
?-?, 209
?.?, 209
?=?, 209
?~=?, 209
0, 209
alternative?, 209
antiAssociative?, 209
antiCommutative?, 209
antiCommutator, 209
apply, 209
associative?, 209
associator, 209
associatorDependence, 209
basis, 209
coerce, 209
commutative?, 209
commutator, 209
conditionsForIdempotents, 209
convert, 209
coordinates, 209
flexible?, 209
hash, 209
jacobiIdentity?, 209
jordanAdmissible?, 209
jordanAlgebra?, 209
latex, 209
leftAlternative?, 209
leftCharacteristicPolynomial, 209
leftDiscriminant, 209
leftMinimalPolynomial, 209
leftNorm, 209
leftPower, 209
leftRankPolynomial, 209
leftRecip, 209
leftRegularRepresentation, 209
leftTrace, 209
leftTraceMatrix, 209
leftUnit, 209
leftUnits, 209
lieAdmissible?, 209
lieAlgebra?, 209
noncommutativeJordanAlgebra?, 209
plenaryPower, 209
powerAssociative?, 209
rank, 209
recip, 209
represents, 209
rightAlternative?, 209
rightCharacteristicPolynomial, 209
rightDiscriminant, 209
rightMinimalPolynomial, 209
rightNorm, 209
rightPower, 209
rightRankPolynomial, 209
rightRecip, 209
rightRegularRepresentation, 209
rightTrace, 209
rightTraceMatrix, 209
rightUnit, 209
rightUnits, 209
sample, 209
someBasis, 209
structuralConstants, 209
subtractIfCan, 209
unit, 209
zero?, 209
jordanAdmissible?
ALGSC, 15
GCNAALG, 1035

JORDAN, 209
LIE, 214
LSQM, 1424
jordanAlgebra?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424

KAFILE, 1381
?.?, 1382
?=?, 1382
?~=?, 1382
#?, 1382
any?, 1382
bag, 1382
close, 1382
coerce, 1382
construct, 1382
convert, 1382
copy, 1382
count, 1382
dictionary, 1382
elt, 1382
empty, 1382
empty?, 1382
entries, 1382
entry?, 1382
eq?, 1382
eval, 1382
every?, 1382
extract, 1382
fill, 1382
find, 1382
first, 1382
hash, 1382
index?, 1382
indices, 1382
insert, 1382
inspect, 1382
iomode, 1382
key?, 1382
keys, 1382
latex, 1382
less?, 1382
map, 1382
maxIndex, 1382
member?, 1382
members, 1382
minIndex, 1382
more?, 1382
name, 1382
open, 1382
pack, 1382
parts, 1382
qelt, 1382
qsetelt, 1382
read, 1382
reduce, 1382
remove, 1382
removeDuplicates, 1382
reopen, 1382
sample, 1382
search, 1382
select, 1382
setelt, 1382
size?, 1382
swap, 1382
table, 1382
write, 1382
karatsubaDivide
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
KERNEL, 1372
?<?, 1372
?<=?, 1372
?>?, 1372
?>=?, 1372
?=?, 1372
?~=?, 1372
argument, 1372
coerce, 1372
convert, 1372
hash, 1372
height, 1372
is?, 1372
kernel, 1372

latex, 1372
max, 1372
min, 1372
name, 1372
operator, 1372
position, 1372
setPosition, 1372
symbolIfCan, 1372
Kernel, 1372
kernel
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
KERNEL, 1372
MYEXPR, 1656
kernels
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
key
GRIMAGE, 1065
VIEW2d, 2739
VIEW3D, 2679
key?
ALIST, 221
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
INTABL, 1304
KAFILE, 1382
LIB, 1397
RESULT, 2267
ROUTINE, 2298
STBL, 2418
STRTBL, 2578
TABLE, 2632
KeyedAccessFile, 1381
keys
ALIST, 221
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
INTABL, 1304
INTFTBL, 1339
KAFILE, 1382
LIB, 1397
ODEIFTBL, 1734
RESULT, 2267
ROUTINE, 2298
STBL, 2418
STRTBL, 2578
TABLE, 2632
knownInfBasis
ALGFF, 28
kroneckerDelta
CARTEN, 342

LA, 1488
-?, 1488
?<?, 1488
?<=?, 1488
?>?, 1488
?>=?, 1488
?**?, 1488
?*?, 1488
?+?, 1488
?-?, 1488
?/?, 1488
?=?, 1488
?^?, 1488
?~=?, 1488
0, 1488
1, 1488
abs, 1488
characteristic, 1488
coerce, 1488
denom, 1488
hash, 1488
latex, 1488
max, 1488
min, 1488
negative?, 1488
numer, 1488
one?, 1488
positive?, 1488
recip, 1488
sample, 1488
sign, 1488
subtractIfCan, 1488

zero?, 1488
label
OUTFORM, 1834
lagrange
UFPS, 2757
UTS, 2844
UTSZ, 2854
lambda
INFORM, 1311
lambert
UFPS, 2757
UTS, 2844
UTSZ, 2854
last
ALIST, 221
DLIST, 448
GTSET, 1054
ILIST, 1201
LIST, 1472
NSDPS, 1670
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
STREAM, 2550
WUTSET, 2895
lastNonNul
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
lastNonNull
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
lastSubResultant
NSMP, 1681
NSUP, 1696
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
lastSubResultantElseSplit
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
latex
AFFPLPS, 7
AFFSP, 9
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ANON, 38
ANTISYM, 40
ANY, 50
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
ATTRBUT, 224
AUTOMOR, 231
BBTREE, 237
BFUNCT, 249
BINARY, 277
BINFILE, 280
BITS, 299
BLHN, 301
BLQT, 304
BOOLEAN, 307
BOP, 258
BPADIC, 242
BPADICRT, 247
BSD, 270
BSTREE, 287
BTOURN, 291
BTREE, 295
CARD, 318
CARTEN, 342
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
CHAR, 359
CLIF, 388
COLOR, 394
COMM, 397
COMPLEX, 406
COMPPROP, 2592
CONTFRAC, 432
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617, 620
D01ASFA, 624
D01FCFA, 627

D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
D10ANFA, 614
DBASE, 442
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DROPT, 596
DSMP, 529
DSTREE, 522
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732
E04NAFA, 735
E04UCFA, 739
EAB, 713
EMR, 672
EQ, 661
EQTBL, 669
EXIT, 677
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FARRAY, 856
FC, 902
FCOMP, 945
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FILE, 772
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNAME, 780
FNLA, 997
FORMULA, 2312
FPARFRAC, 1010
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
FT, 941
FTEM, 938
FUNCTION, 1015
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GOPT, 1075
GOPT0, 1081
GPOLSET, 1044
GRIMAGE, 1065
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HELLFDIV, 1153

HEXADEC, 1113
HTMLFORM, 1122
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IC, 1161
ICARD, 1163
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFARRAY, 1192
IFF, 1252
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INFCLSPS, 1240
INFCLSPT, 1234
INFORM, 1311
INT, 1330
INTABL, 1304
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
KERNEL, 1372
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LMOPS, 1477
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
M3D, 2672
MAGMA, 1533
MATRIX, 1591
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MMLFORM, 1571
MODFIELD, 1606
MODMON, 1600
MODMONOM, 1612
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NIPROB, 1713
NNI, 1706
NONE, 1704
NOTTING, 1711
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODEPROB, 1716
ODP, 1783
ODPOL, 1818
ODR, 1825
ODVAR, 1821
OFMONOID, 1795
OMENC, 1755
OMERR, 1758
OMERRK, 1761
OMLO, 1773
ONECOMP, 1744
OPTPROB, 1719
ORDCOMP, 1777

ORESUP, 2460
OREUP, 2840
OSI, 1830
OUTFORM, 1834
OVAR, 1803
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PALETTE, 1862
PATLRES, 1904
PATRES, 1906
PATTERN, 1894
PBWLB, 2020
PDEPROB, 1722
PENDTREE, 1911
PERM, 1916
PERMGRP, 1926
PF, 2071
PFR, 1880
PI, 2066
PLACES, 1985
PLACESPS, 1987
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
PRODUCT, 2079
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
PRTITION, 1889
QALGSET, 2123
QFORM, 2120
QUAT, 2133
QUEUE, 2150
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REF, 2215
REGSET, 2252
RESRING, 2262
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROIRC, 2276
ROMAN, 2293
ROUTINE, 2298
RULE, 2271
RULECOLD, 2307
RULESET, 2309
SAE, 2368
SAOS, 2386
SD, 2540
SDPOL, 2352
SDVAR, 2358
SEG, 2325
SEGBIND, 2330
SET, 2338
SETMN, 2344
SEX, 2360
SEXOF, 2363
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SPACE3, 2701
SPLNODE, 2479
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SUBSPACE, 2582
SUCH, 2595
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMBOL, 2608
SYMPOLY, 2622
TABLE, 2632
TEX, 2645
TEXTFILE, 2661
TREE, 2710
TS, 2639

TUPLE, 2721
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VARIABLE, 2872
VECTOR, 2878
VIEW2d, 2739
VIEW3D, 2679
WP, 2885
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
LAUPOL, 1389
-?, 1390
?**?, 1390
?*?, 1390
?+?, 1390
?-?, 1390
?=?, 1390
?^?, 1390
?~=?, 1390
?quo?, 1390
?rem?, 1390
0, 1390
1, 1390
associates?, 1390
characteristic, 1390
charthRoot, 1390
coefficient, 1390
coerce, 1390
convert, 1390
D, 1390
degree, 1390
differentiate, 1390
divide, 1390
euclideanSize, 1390
expressIdealMember, 1390
exquo, 1390
extendedEuclidean, 1390
gcd, 1390
gcdPolynomial, 1390
hash, 1390
latex, 1390
lcm, 1390
leadingCoefficient, 1390
monomial, 1390
monomial?, 1390
multiEuclidean, 1390
one?, 1390
order, 1390
principalIdeal, 1390
recip, 1390
reductum, 1390
retract, 1390
retractIfCan, 1390
sample, 1390
separate, 1390
sizeLess?, 1390
subtractIfCan, 1390
trailingCoefficient, 1390
unit?, 1390
unitCanonical, 1390
unitNormal, 1390
zero?, 1390
laurent
SULS, 2425
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
laurentIfCan
SUPXS, 2455
UPXS, 2801
UPXSCONS, 2809
LaurentPolynomial, 1389
laurentRep
SUPXS, 2455
UPXS, 2801
UPXSCONS, 2809

LazardQuotient
NSMP, 1681
LazardQuotient2
NSMP, 1681
lazy?
NSDPS, 1670
STREAM, 2550
lazyEvaluate
NSDPS, 1670
STREAM, 2550
lazyPquo
NSMP, 1681
lazyPrem
NSMP, 1681
lazyPremWithDefault
NSMP, 1681
lazyPseudoDivide
NSMP, 1681
NSUP, 1696
lazyPseudoQuotient
NSUP, 1696
lazyPseudoRemainder
NSUP, 1696
lazyResidueClass
NSMP, 1681
NSUP, 1696
lcm
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368

SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
LE
SWITCH, 2597
leader
DSMP, 529
ODPOL, 1818
SDPOL, 2352
leadingBasisTerm
ANTISYM, 40
DERHAM, 517
leadingCoefficient
ANTISYM, 40
DERHAM, 517
DMP, 560
DSMP, 529
EXPUPXS, 710
FM, 983
FM1, 987
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HDMP, 1150
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
INDE, 1187
ISUPS, 1279
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
OMLO, 1773
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
leadingExponent
GMODPOL, 1029
leadingIdeal
IDEAL, 2047
leadingIndex
GMODPOL, 1029
leadingMonomial
DMP, 560
DSMP, 529
EXPUPXS, 710
FM1, 987
GDMP, 1022

GMODPOL, 1029
GSERIES, 1061
HDMP, 1150
ISUPS, 1279
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
leadingSupport
FM, 983
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
INDE, 1187
leadingTerm
FM1, 987
LPOLY, 1415
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
leaf?
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
PLACES, 1985
PLACESPS, 1987
SPLTREE, 2485
STREAM, 2550
SUBSPACE, 2582
TREE, 2710
leastMonomial
NSMP, 1681
leaves
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
left
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
LWORD, 1500

MAGMA, 1533
OUTFORM, 1834
PENDTREE, 1911
ROIRC, 2276
leftAlternative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftCharacteristicPolynomial
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftDiscriminant
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftDivide
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftExactQuotient
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftExtendedGcd
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftGcd
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftLcm
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftMinimalPolynomial
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftMult
LMOPS, 1477
leftNorm
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftOne
EQ, 661
leftPower
ALGSC, 15
FNLA, 997
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftQuotient
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftRankPolynomial
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftRecip
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214

LSQM, 1424
leftRegularRepresentation
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftRemainder
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
leftTrace
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftTraceMatrix
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftTrim
ISTRING, 1218
STRING, 2575
leftUnit
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftUnits
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
leftZero
EQ, 661
length
CDFVEC, 419
DEQUEUE, 499
DFVEC, 593
INT, 1330
IVECTOR, 1229
LWORD, 1500
MAGMA, 1533
MINT, 1525
OFMONOID, 1795
PBWLB, 2020
POINT, 2026
QUEUE, 2150
ROMAN, 2293
SINT, 2380
TUPLE, 2721
VECTOR, 2878
less?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169

IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
level
SUBSPACE, 2582
leviCivitaSymbol
CARTEN, 342
lexico
LWORD, 1500
MAGMA, 1533
OFMONOID, 1795
LEXP, 1403
?**?, 1403
?*?, 1403
?/?, 1403
?=?, 1403
?^?, 1403
?~=?, 1403
1, 1403
coerce, 1403
commutator, 1403
conjugate, 1403
exp, 1403
hash, 1403
identification, 1403
inv, 1403
latex, 1403
listOfTerms, 1403
log, 1403
LyndonBasis, 1403
LyndonCoordinates, 1403
mirror, 1403
one?, 1403
recip, 1403
sample, 1403
varList, 1403
lhs
EQ, 661
RULE, 2271
SUCH, 2595
li
EXPR, 694
LIB, 1396
?.?, 1397
?=?, 1397
?~=?, 1397
#?, 1397
any?, 1397
bag, 1397
close, 1397
coerce, 1397
construct, 1397
convert, 1397
copy, 1397

count, 1397
dictionary, 1397
elt, 1397
empty, 1397
empty?, 1397
entries, 1397
entry?, 1397
eq?, 1397
eval, 1397
every?, 1397
extract, 1397
fill, 1397
find, 1397
first, 1397
hash, 1397
index?, 1397
indices, 1397
insert, 1397
inspect, 1397
key?, 1397
keys, 1397
latex, 1397
less?, 1397
library, 1397
map, 1397
maxIndex, 1397
member?, 1397
members, 1397
minIndex, 1397
more?, 1397
pack, 1397
parts, 1397
qelt, 1397
qsetelt, 1397
reduce, 1397
remove, 1397
removeDuplicates, 1397
sample, 1397
search, 1397
select, 1397
setelt, 1397
size?, 1397
swap, 1397
table, 1397
Library, 1396
library
LIB, 1397
LIE, 213
-?, 214
?**?, 214
?*?, 214
?+?, 214
?-?, 214
?.?, 214
?=?, 214
?~=?, 214
0, 214
alternative?, 214
antiAssociative?, 214
antiCommutative?, 214
antiCommutator, 214
apply, 214
associative?, 214
associator, 214
associatorDependence, 214
basis, 214
coerce, 214
commutative?, 214
commutator, 214
conditionsForIdempotents, 214
convert, 214
coordinates, 214
flexible?, 214
hash, 214
jacobiIdentity?, 214
jordanAdmissible?, 214
jordanAlgebra?, 214
latex, 214
leftAlternative?, 214
leftCharacteristicPolynomial, 214
leftDiscriminant, 214
leftMinimalPolynomial, 214
leftNorm, 214
leftPower, 214
leftRankPolynomial, 214
leftRecip, 214
leftRegularRepresentation, 214
leftTrace, 214
leftTraceMatrix, 214
leftUnit, 214
leftUnits, 214
lieAdmissible?, 214

lieAlgebra?, 214
noncommutativeJordanAlgebra?, 214
plenaryPower, 214
powerAssociative?, 214
rank, 214
recip, 214
represents, 214
rightAlternative?, 214
rightCharacteristicPolynomial, 214
rightDiscriminant, 214
rightMinimalPolynomial, 214
rightNorm, 214
rightPower, 214
rightRankPolynomial, 214
rightRecip, 214
rightRegularRepresentation, 214
rightTrace, 214
rightTraceMatrix, 214
rightUnit, 214
rightUnits, 214
sample, 214
someBasis, 214
structuralConstants, 214
subtractIfCan, 214
unit, 214
zero?, 214
lieAdmissible?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
lieAlgebra?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
LieExponentials, 1403
LiePoly
LPOLY, 1415
LiePolyIfCan
LPOLY, 1415
XPBWPOLYL, 2925
LiePolynomial, 1414
LieSquareMatrix, 1423
lift
ALGFF, 28
COMPLEX, 406
MCMPLX, 1511
MODMON, 1600
PACOFF, 2102
PACRAT, 2112
RADFF, 2160
RESRING, 2262
SAE, 2368
light
PALETTE, 1862
lighting
VIEW3D, 2679
limitPlus
EXPEXPAN, 682
UPXSSING, 2819
linearAssociatedExp
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PF, 2071
linearAssociatedLog
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PF, 2071
linearAssociatedOrder
FF, 790
FFCG, 795

FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PF, 2071
LinearOrdinaryDifferentialOperator, 1437
LinearOrdinaryDifferentialOperator1, 1447
LinearOrdinaryDifferentialOperator2, 1459
LIST, 1472
?<?, 1472
?<=?, 1472
?>?, 1472
?>=?, 1472
?.?, 1472
?.first, 1472
?.last, 1472
?.rest, 1472
?.value, 1472
?=?, 1472
?~=?, 1472
#?, 1472
any?, 1472
append, 1472
child?, 1472
children, 1472
coerce, 1472
concat, 1472
cons, 1472
construct, 1472
convert, 1472
copy, 1472
copyInto, 1472
count, 1472
cycleEntry, 1472
cycleLength, 1472
cycleSplit, 1472
cycleTail, 1472
cyclic?, 1472
delete, 1472
distance, 1472
elt, 1472
empty, 1472
empty?, 1472
entries, 1472
entry?, 1472
eq?, 1472
eval, 1472
every?, 1472
explicitlyFinite?, 1472
fill, 1472
find, 1472
first, 1472
hash, 1472
index?, 1472
indices, 1472
insert, 1472
last, 1472
latex, 1472
leaf?, 1472
leaves, 1472
less?, 1472
list, 1472
map, 1472
max, 1472
maxIndex, 1472
member?, 1472
members, 1472
merge, 1472
min, 1472
minIndex, 1472
more?, 1472
new, 1472
nil, 1472
node?, 1472
nodes, 1472
null, 1472
OMwrite, 1472
parts, 1472
position, 1472
possiblyInfinite?, 1472
qelt, 1472
qsetelt, 1472
reduce, 1472
remove, 1472
removeDuplicates, 1472
rest, 1472
reverse, 1472

sample, 1472
second, 1472
select, 1472
setchildren, 1472
setDifference, 1472
setelt, 1472
setfirst, 1472
setIntersection, 1472
setlast, 1472
setrest, 1472
setUnion, 1472
setvalue, 1472
size?, 1472
sort, 1472
sorted?, 1472
split, 1472
swap, 1472
tail, 1472
third, 1472
value, 1472
List, 1472
list
AFFPLPS, 7
AFFSP, 9
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
SYMBOL, 2608
list?
INFORM, 1311
SEX, 2360
SEXOF, 2363
listBranches
ACPLOT, 1958
PLOT, 1995
PLOT3D, 2008
listLoops
TUBE, 2718
ListMonoidOps, 1477
ListMultiDictionary, 1483
listOfLists
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
TABLEAU, 2634
listOfMonoms
LMOPS, 1477
listOfTerms
FM1, 987
LEXP, 1403
LPOLY, 1415
PBWLB, 2020
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
listRepresentation
PERM, 1916
lists
PATLRES, 1904
listSD
SD, 2540
lllip
SPACE3, 2701
lllp
SPACE3, 2701
llprop
SPACE3, 2701
LMDICT, 1483
?=?, 1483
?~=?, 1483
#?, 1483
any?, 1483
bag, 1483
coerce, 1483
construct, 1483
convert, 1483
copy, 1483
count, 1483
dictionary, 1483
duplicates, 1483
duplicates?, 1483
empty, 1483
empty?, 1483

eq?, 1483
eval, 1483
every?, 1483
extract, 1483
find, 1483
hash, 1483
insert, 1483
inspect, 1483
latex, 1483
less?, 1483
map, 1483
member?, 1483
members, 1483
more?, 1483
parts, 1483
reduce, 1483
remove, 1483
removeDuplicates, 1483
sample, 1483
select, 1483
size?, 1483
substitute, 1483
LMOPS, 1477
?=?, 1477
?~=?, 1477
coerce, 1477
commutativeEquality, 1477
hash, 1477
latex, 1477
leftMult, 1477
listOfMonoms, 1477
makeMulti, 1477
makeTerm, 1477
makeUnit, 1477
mapExpon, 1477
mapGen, 1477
nthExpon, 1477
nthFactor, 1477
outputForm, 1477
plus, 1477
retract, 1477
retractIfCan, 1477
reverse, 1477
rightMult, 1477
size, 1477
LO, 1491
-?, 1491
?<?, 1491
?<=?, 1491
?>?, 1491
?>=?, 1491
?*?, 1491
?+?, 1491
?-?, 1491
?/?, 1491
?=?, 1491
?~=?, 1491
0, 1491
coerce, 1491
denom, 1491
hash, 1491
latex, 1491
max, 1491
min, 1491
numer, 1491
sample, 1491
subtractIfCan, 1491
zero?, 1491
lo
SEG, 2325
UNISEG, 2863
LocalAlgebra, 1488
Localize, 1491
localParam
PLACES, 1985
PLACESPS, 1987
localParamV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
localPointV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
LODO, 1437
-?, 1437
?**?, 1437
?*?, 1437
?+?, 1437
?-?, 1437
?.?, 1437
?=?, 1437

?^?, 1437
?~=?, 1437
0, 1437
1, 1437
adjoint, 1437
apply, 1437
characteristic, 1437
coefficient, 1437
coefficients, 1437
coerce, 1437
content, 1437
D, 1437
degree, 1437
directSum, 1437
exquo, 1437
hash, 1437
latex, 1437
leadingCoefficient, 1437
leftDivide, 1437
leftExactQuotient, 1437
leftExtendedGcd, 1437
leftGcd, 1437
leftLcm, 1437
leftQuotient, 1437
leftRemainder, 1437
minimumDegree, 1437
monicLeftDivide, 1437
monicRightDivide, 1437
monomial, 1437
one?, 1437
primitivePart, 1437
recip, 1437
reductum, 1437
retract, 1437
retractIfCan, 1437
rightDivide, 1437
rightExactQuotient, 1437
rightExtendedGcd, 1437
rightGcd, 1437
rightLcm, 1437
rightQuotient, 1437
rightRemainder, 1437
sample, 1437
subtractIfCan, 1437
symmetricPower, 1437
symmetricProduct, 1437
symmetricSquare, 1437
zero?, 1437
LODO1, 1447
-?, 1447
?**?, 1447
?*?, 1447
?+?, 1447
?-?, 1447
?.?, 1447
?=?, 1447
?^?, 1447
?~=?, 1447
0, 1447
1, 1447
adjoint, 1447
apply, 1447
characteristic, 1447
coefficient, 1447
coefficients, 1447
coerce, 1447
content, 1447
D, 1447
degree, 1447
directSum, 1447
exquo, 1447
hash, 1447
latex, 1447
leadingCoefficient, 1447
leftDivide, 1447
leftExactQuotient, 1447
leftExtendedGcd, 1447
leftGcd, 1447
leftLcm, 1447
leftQuotient, 1447
leftRemainder, 1447
minimumDegree, 1447
monicLeftDivide, 1447
monicRightDivide, 1447
monomial, 1447
one?, 1447
primitivePart, 1447
recip, 1447
reductum, 1447
retract, 1447
retractIfCan, 1447
rightDivide, 1447

rightExactQuotient, 1447
rightExtendedGcd, 1447
rightGcd, 1447
rightLcm, 1447
rightQuotient, 1447
rightRemainder, 1447
sample, 1447
subtractIfCan, 1447
symmetricPower, 1447
symmetricProduct, 1447
symmetricSquare, 1447
zero?, 1447
LODO2, 1459
-?, 1459
?**?, 1459
?*?, 1459
?+?, 1459
?-?, 1459
?.?, 1459
?=?, 1459
?^?, 1459
?~=?, 1459
0, 1459
1, 1459
adjoint, 1459
apply, 1459
characteristic, 1459
coefficient, 1459
coefficients, 1459
coerce, 1459
content, 1459
D, 1459
degree, 1459
directSum, 1459
exquo, 1459
hash, 1459
latex, 1459
leadingCoefficient, 1459
leftDivide, 1459
leftExactQuotient, 1459
leftExtendedGcd, 1459
leftGcd, 1459
leftLcm, 1459
leftQuotient, 1459
leftRemainder, 1459
minimumDegree, 1459
monicLeftDivide, 1459
monicRightDivide, 1459
monomial, 1459
one?, 1459
primitivePart, 1459
recip, 1459
reductum, 1459
retract, 1459
retractIfCan, 1459
rightDivide, 1459
rightExactQuotient, 1459
rightExtendedGcd, 1459
rightGcd, 1459
rightLcm, 1459
rightQuotient, 1459
rightRemainder, 1459
sample, 1459
subtractIfCan, 1459
symmetricPower, 1459
symmetricProduct, 1459
symmetricSquare, 1459
zero?, 1459
log
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
LEXP, 1403
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854

XPBWPOLYL, 2925
log10
DFLOAT, 575
FEXPR, 917
FLOAT, 879
log2
DFLOAT, 575
FLOAT, 879
logical?
FST, 933
logpart
IR, 1343
lookup
ALGFF, 28
BOOLEAN, 307
CCLASS, 368
CHAR, 359
COMPLEX, 406
DIRPROD, 534
DPMM, 540
DPMO, 545
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
HDP, 1143
IFF, 1252
IPF, 1271
MCMPLX, 1511
MODMON, 1600
MRING, 1626
OCT, 1731
ODP, 1783
OVAR, 1803
PACOFF, 2102
PF, 2071
PRODUCT, 2079
RADFF, 2160
SAE, 2368
SET, 2338
SETMN, 2344
SHDP, 2476
ZMOD, 1336
low
SEG, 2325
UNISEG, 2863
lowerCase
CCLASS, 368
CHAR, 359
ISTRING, 1218
STRING, 2575
lowerCase?
CHAR, 359
lp
SPACE3, 2701
LPOLY, 1414
-?, 1415
?*?, 1415
?+?, 1415
?-?, 1415
?/?, 1415
?=?, 1415
?~=?, 1415
0, 1415
coef, 1415
coefficient, 1415
coefficients, 1415
coerce, 1415
construct, 1415
degree, 1415
eval, 1415
hash, 1415
latex, 1415
leadingCoefficient, 1415
leadingMonomial, 1415
leadingTerm, 1415
LiePoly, 1415
LiePolyIfCan, 1415
listOfTerms, 1415
lquo, 1415
map, 1415
mirror, 1415
monom, 1415
monomial?, 1415
monomials, 1415
numberOfMonomials, 1415
reductum, 1415

retract, 1415
retractIfCan, 1415
rquo, 1415
sample, 1415
subtractIfCan, 1415
trunc, 1415
varList, 1415
zero?, 1415
lprop
SPACE3, 2701
lquo
FMONOID, 991
LPOLY, 1415
OFMONOID, 1795
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
lSpaceBasis
FDIV, 783
LSQM, 1423
-?, 1424
?**?, 1424
?*?, 1424
?+?, 1424
?-?, 1424
?.?, 1424
?/?, 1424
?=?, 1424
?^?, 1424
?~=?, 1424
#?, 1424
0, 1424
1, 1424
alternative?, 1424
antiAssociative?, 1424
antiCommutator, 1424
antisymmetric?, 1424
any?, 1424
apply, 1424
associative?, 1424
associator, 1424
associatorDependence, 1424
basis, 1424
characteristic, 1424
coerce, 1424
column, 1424
commutative?, 1424
commutator, 1424
conditionsForIdempotents, 1424
convert, 1424
coordinates, 1424
copy, 1424
count, 1424
D, 1424
determinant, 1424
diagonal, 1424
diagonal?, 1424
diagonalMatrix, 1424
diagonalProduct, 1424
differentiate, 1424
elt, 1424
empty, 1424
empty?, 1424
eq?, 1424
eval, 1424
every?, 1424
exquo, 1424
flexible?, 1424
hash, 1424
inverse, 1424
jacobiIdentity?, 1424
jordanAdmissible?, 1424
jordanAlgebra?, 1424
latex, 1424
leftAlternative?, 1424
leftCharacteristicPolynomial, 1424
leftDiscriminant, 1424
leftMinimalPolynomial, 1424
leftNorm, 1424
leftPower, 1424
leftRankPolynomial, 1424
leftRecip, 1424
leftRegularRepresentation, 1424
leftTrace, 1424
leftTraceMatrix, 1424
leftUnit, 1424
leftUnits, 1424
less?, 1424
lieAdmissible?, 1424
lieAlgebra?, 1424
listOfLists, 1424

map, 1424
matrix, 1424
maxColIndex, 1424
maxRowIndex, 1424
member?, 1424
members, 1424
minColIndex, 1424
minordet, 1424
minRowIndex, 1424
more?, 1424
ncols, 1424
noncommutativeJordanAlgebra?, 1424
nrows, 1424
nullity, 1424
nullSpace, 1424
one?, 1424
parts, 1424
plenaryPower, 1424
powerAssociative?, 1424
qelt, 1424
rank, 1424
recip, 1424
reducedSystem, 1424
represents, 1424
retract, 1424
retractIfCan, 1424
rightAlternative?, 1424
rightCharacteristicPolynomial, 1424
rightDiscriminant, 1424
rightMinimalPolynomial, 1424
rightNorm, 1424
rightPower, 1424
rightRankPolynomial, 1424
rightRecip, 1424
rightRegularRepresentation, 1424
rightTrace, 1424
rightTraceMatrix, 1424
rightUnit, 1424
rightUnits, 1424
row, 1424
rowEchelon, 1424
sample, 1424
scalarMatrix, 1424
size?, 1424
someBasis, 1424
square?, 1424
structuralConstants, 1424
subtractIfCan, 1424
symmetric?, 1424
trace, 1424
unit, 1424
zero?, 1424
LT
SWITCH, 2597
LWORD, 1500
?<?, 1500
?<=?, 1500
?>?, 1500
?>=?, 1500
?=?, 1500
?~=?, 1500
coerce, 1500
factor, 1500
hash, 1500
latex, 1500
left, 1500
length, 1500
lexico, 1500
lyndon, 1500
lyndon?, 1500
lyndonIfCan, 1500
LyndonWordsList, 1500
LyndonWordsList1, 1500
max, 1500
min, 1500
retract, 1500
retractable?, 1500
retractIfCan, 1500
right, 1500
varList, 1500
lyndon
LWORD, 1500
lyndon?
LWORD, 1500
LyndonBasis
LEXP, 1403
LyndonCoordinates
LEXP, 1403
lyndonIfCan
LWORD, 1500
LyndonWord, 1500
LyndonWordsList

LWORD, 1500
LyndonWordsList1
LWORD, 1500

M3D, 2671
?=?, 2672
?~=?, 2672
#?, 2672
any?, 2672
coerce, 2672
construct, 2672
copy, 2672
count, 2672
elt, 2672
empty, 2672
empty?, 2672
eq?, 2672
eval, 2672
every?, 2672
hash, 2672
identityMatrix, 2672
latex, 2672
less?, 2672
map, 2672
matrixConcat3D, 2672
matrixDimensions, 2672
member?, 2672
members, 2672
more?, 2672
parts, 2672
plus, 2672
sample, 2672
setelt, 2672
size?, 2672
zeroMatrix, 2672
MachineComplex, 1510
MachineFloat, 1515
machineFraction
DFLOAT, 575
MachineInteger, 1525
MAGMA, 1533
?<?, 1533
?<=?, 1533
?>?, 1533
?>=?, 1533
?*?, 1533
?=?, 1533
?~=?, 1533
coerce, 1533
first, 1533
hash, 1533
latex, 1533
left, 1533
length, 1533
lexico, 1533
max, 1533
min, 1533
mirror, 1533
rest, 1533
retract, 1533
retractable?, 1533
retractIfCan, 1533
right, 1533
varList, 1533
Magma, 1533
magnitude
CDFVEC, 419
DFVEC, 593
IVECTOR, 1229
POINT, 2026
VECTOR, 2878
mainCharacterization
RECLOS, 2203
mainCoefficients
NSMP, 1681
mainContent
NSMP, 1681
mainDefiningPolynomial
RECLOS, 2203
mainForm
RECLOS, 2203
mainKernel
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
mainMonomial
NSMP, 1681
mainMonomials
NSMP, 1681
mainPrimitivePart

NSMP, 1681
mainSquareFreePart
NSMP, 1681
mainValue
RECLOS, 2203
mainVariable
DMP, 560
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
mainVariable?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
mainVariables
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
MakeCachableSet, 1538
makeCos
FSERIES, 948
makeFR
FR, 756
makeGraphImage
GRIMAGE, 1065
makeMulti
LMOPS, 1477
makeop
MODOP, 1615, 1771
makeprod
PRODUCT, 2079
makeResult
PATLRES, 1904
makeSeries
ISUPS, 1279
makeSin
FSERIES, 948
makeSketch
ACPLOT, 1958
makeSUP
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
makeTerm
LMOPS, 1477
makeUnit
LMOPS, 1477
makeVariable
DSMP, 529
ODVAR, 1821
SDPOL, 2352
SDVAR, 2358
makeViewport2D
VIEW2d, 2739
makeViewport3D
VIEW3D, 2679
mantissa
DFLOAT, 575
FLOAT, 879
MFLOAT, 1516
map
ALIST, 221
AN, 35
ANTISYM, 40
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BINARY, 277
BITS, 299
BPADICRT, 247
BSTREE, 287

BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
COMPLEX, 406
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
DSTREE, 522
EQ, 661
EQTBL, 669
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FARRAY, 856
FEXPR, 917
FM, 983
FM1, 987
FR, 756
FRAC, 956
GDMP, 1022
GPOLSET, 1044
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INTABL, 1304
ISTRING, 1218
ISUPS, 1279
ITUPLE, 1231
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LPOLY, 1415
LSQM, 1424
M3D, 2672
MATRIX, 1591
MCMPLX, 1511
MODMON, 1600
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
PENDTREE, 1911
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
QUAT, 2133
QUEUE, 2150
RADIX, 2172
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221

RMATRIX, 2212
ROUTINE, 2298
SDPOL, 2352
SEG, 2325
SET, 2338
SHDP, 2476
SMP, 2391
SMTS, 2409
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TABLE, 2632
TREE, 2710
TS, 2639
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UNISEG, 2863
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
VECTOR, 2878
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951

mapCoef
DIV, 563
FAGROUP, 975
FAMONOID, 978
IFAMON, 1255

mapExpon
FGROUP, 980
FMONOID, 991
LMOPS, 1477

mapExponents
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819

mapGen
DIV, 563
FAGROUP, 975
FAMONOID, 978
FGROUP, 980
FMONOID, 991
IFAMON, 1255
LMOPS, 1477

mask
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380

match
ISTRING, 1218
STRING, 2575

match?
ISTRING, 1218
STRING, 2575

MathMLForm, 1571

MathMLFormat , 1542, 1544
MATRIX, 1590
-?, 1591
?**?, 1591
?*?, 1591
?+?, 1591
?-?, 1591
?/?, 1591
?=?, 1591
?~=?, 1591
#?, 1591
antisymmetric?, 1591
any?, 1591
coerce, 1591
column, 1591
convert, 1591
copy, 1591
count, 1591
determinant, 1591
diagonal?, 1591
diagonalMatrix, 1591
elt, 1591
empty, 1591
empty?, 1591
eq?, 1591
eval, 1591
every?, 1591
exquo, 1591
fill, 1591
hash, 1591
horizConcat, 1591
inverse, 1591
latex, 1591
less?, 1591
listOfLists, 1591
map, 1591
matrix, 1591
maxColIndex, 1591
maxRowIndex, 1591
member?, 1591
members, 1591
minColIndex, 1591
minordet, 1591
minRowIndex, 1591
more?, 1591
ncols, 1591
new, 1591
nrows, 1591
nullity, 1591
nullSpace, 1591
parts, 1591
qelt, 1591
qsetelt, 1591
rank, 1591
row, 1591
rowEchelon, 1591
sample, 1591
scalarMatrix, 1591
setColumn, 1591
setelt, 1591
setRow, 1591
setsubMatrix, 1591
size?, 1591
square?, 1591
squareTop, 1591
subMatrix, 1591
swapColumns, 1591
swapRows, 1591
symmetric?, 1591
transpose, 1591
vertConcat, 1591
zero, 1591
Matrix, 1590
matrix
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
OUTFORM, 1834
QFORM, 2120
RMATRIX, 2212
SQMATRIX, 2515
matrixConcat3D
M3D, 2672
matrixDimensions
M3D, 2672
max
ALIST, 221
AN, 35
ARRAY1, 1740

BINARY, 277
BITS, 299
BOOLEAN, 307
BOP, 258
BPADICRT, 247
BSD, 270
CARD, 318
CCLASS, 368
CDFVEC, 419
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EAB, 713
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FARRAY, 856
FCOMP, 945
FEXPR, 917
FLOAT, 879
FMONOID, 991
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEAP, 1104
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IDPOAM, 1182
IDPOAMS, 1185
IFARRAY, 1192
ILIST, 1201
INDE, 1187
INT, 1330
INTRVL, 1352
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LA, 1488
LIST, 1472
LO, 1491
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MODMON, 1600
MODMONOM, 1612
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
ORDCOMP, 1777
OSI, 1830
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PBWLB, 2020
PERM, 1916
PI, 2066
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAOS, 2386
SDPOL, 2352

SDVAR, 2358
SET, 2338
SHDP, 2476
SINT, 2380
SMP, 2391
STRING, 2575
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UP, 2795
VECTOR, 2878
maxColIndex
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
maxdeg
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
maxDegree
GOPT, 1075
GOPT0, 1081
maxDerivative
GOPT, 1075
GOPT0, 1081
maximumExponent
MFLOAT, 1516
maxIndex
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
maxint
MINT, 1525
maxLevel
GOPT, 1075
GOPT0, 1081
maxMixedDegree
GOPT, 1075
GOPT0, 1081
maxPoints
PLOT, 1995
maxPoints3D
PLOT3D, 2008

maxPower
GOPT, 1075
GOPT0, 1081
maxRowIndex
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
maxShift
GOPT, 1075
GOPT0, 1081
maxSubst
GOPT, 1075
GOPT0, 1081
maxTower
PACOFF, 2102
PACRAT, 2112
MCMPLX, 1510
-?, 1511
?<?, 1511
?<=?, 1511
?>?, 1511
?>=?, 1511
?**?, 1511
?*?, 1511
?+?, 1511
?-?, 1511
?.?, 1511
?/?, 1511
?=?, 1511
?^?, 1511
?~=?, 1511
?quo?, 1511
?rem?, 1511
0, 1511
1, 1511
abs, 1511
acos, 1511
acosh, 1511
acot, 1511
acoth, 1511
acsc, 1511
acsch, 1511
argument, 1511
asec, 1511
asech, 1511
asin, 1511
asinh, 1511
associates?, 1511
atan, 1511
atanh, 1511
basis, 1511
characteristic, 1511
characteristicPolynomial, 1511
charthRoot, 1511
coerce, 1511
complex, 1511
conditionP, 1511
conjugate, 1511
convert, 1511
coordinates, 1511
cos, 1511
cosh, 1511
cot, 1511
coth, 1511
createPrimitiveElement, 1511
csc, 1511
csch, 1511
D, 1511
definingPolynomial, 1511
derivationCoordinates, 1511
differentiate, 1511
discreteLog, 1511
discriminant, 1511
divide, 1511
euclideanSize, 1511
eval, 1511
exp, 1511
expressIdealMember, 1511
exquo, 1511
extendedEuclidean, 1511
factor, 1511
factorPolynomial, 1511
factorsOfCyclicGroupSize, 1511
factorSquareFreePolynomial, 1511

gcd, 1511
gcdPolynomial, 1511
generator, 1511
hash, 1511
imag, 1511
imaginary, 1511
index, 1511
init, 1511
inv, 1511
latex, 1511
lcm, 1511
lift, 1511
log, 1511
lookup, 1511
map, 1511
max, 1511
min, 1511
minimalPolynomial, 1511
multiEuclidean, 1511
nextItem, 1511
norm, 1511
nthRoot, 1511
one?, 1511
order, 1511
patternMatch, 1511
pi, 1511
polarCoordinates, 1511
prime?, 1511
primeFrobenius, 1511
primitive?, 1511
primitiveElement, 1511
principalIdeal, 1511
random, 1511
rank, 1511
rational, 1511
rational?, 1511
rationalIfCan, 1511
real, 1511
recip, 1511
reduce, 1511
reducedSystem, 1511
regularRepresentation, 1511
representationType, 1511
represents, 1511
retract, 1511
retractIfCan, 1511
sample, 1511
sec, 1511
sech, 1511
sin, 1511
sinh, 1511
size, 1511
sizeLess?, 1511
solveLinearPolynomialEquation, 1511
sqrt, 1511
squareFree, 1511
squareFreePart, 1511
squareFreePolynomial, 1511
subtractIfCan, 1511
tableForDiscreteLogarithm, 1511
tan, 1511
tanh, 1511
trace, 1511
traceMatrix, 1511
unit?, 1511
unitCanonical, 1511
unitNormal, 1511
zero?, 1511
mdeg
NSMP, 1681
measure
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617, 620
D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
D03EEFA, 652
D03FAFA, 655
D10ANFA, 614
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732

E04NAFA, 735
E04UCFA, 739
medialSet
WUTSET, 2895
member?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
PERMGRP, 1926
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SETMN, 2344
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
members
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413

CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
merge
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
HEAP, 1104
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
POINT, 2026
PRIMARR, 2075
SPACE3, 2701
STRING, 2575
SUBSPACE, 2582
U32VEC, 2869
VECTOR, 2878
mesh
SPACE3, 2701
mesh?
SPACE3, 2701
message
OUTFORM, 1834
messagePrint

OUTFORM, 1834
MFLOAT, 1515
-?, 1516
?<?, 1516
?<=?, 1516
?>?, 1516
?>=?, 1516
?**?, 1516
?*?, 1516
?+?, 1516
?-?, 1516
?/?, 1516
?=?, 1516
?^?, 1516
?~=?, 1516
?quo?, 1516
?rem?, 1516
0, 1516
1, 1516
abs, 1516
associates?, 1516
base, 1516
bits, 1516
ceiling, 1516
changeBase, 1516
characteristic, 1516
coerce, 1516
convert, 1516
decreasePrecision, 1516
digits, 1516
divide, 1516
euclideanSize, 1516
exponent, 1516
expressIdealMember, 1516
exquo, 1516
extendedEuclidean, 1516
factor, 1516
float, 1516
floor, 1516
fractionPart, 1516
gcd, 1516
gcdPolynomial, 1516
hash, 1516
increasePrecision, 1516
inv, 1516
latex, 1516
lcm, 1516
mantissa, 1516
max, 1516
maximumExponent, 1516
min, 1516
minimumExponent, 1516
multiEuclidean, 1516
negative?, 1516
norm, 1516
nthRoot, 1516
one?, 1516
order, 1516
patternMatch, 1516
positive?, 1516
precision, 1516
prime?, 1516
principalIdeal, 1516
recip, 1516
retract, 1516
retractIfCan, 1516
round, 1516
sample, 1516
sign, 1516
sizeLess?, 1516
sqrt, 1516
squareFree, 1516
squareFreePart, 1516
subtractIfCan, 1516
truncate, 1516
unit?, 1516
unitCanonical, 1516
unitNormal, 1516
wholePart, 1516
zero?, 1516
middle
ROIRC, 2276
mightHaveRoots
ROIRC, 2276
min
ALIST, 221
AN, 35
ARRAY1, 1740
BINARY, 277
BITS, 299
BOOLEAN, 307
BOP, 258

BPADICRT, 247
BSD, 270
CARD, 318
CCLASS, 368
CDFVEC, 419
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DFVEC, 593
DIRPROD, 534
DLIST, 448
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EAB, 713
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FARRAY, 856
FCOMP, 945
FEXPR, 917
FLOAT, 879
FMONOID, 991
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IBITS, 1169
ICARD, 1163
IDPOAM, 1182
IDPOAMS, 1185
IFARRAY, 1192
ILIST, 1201
INDE, 1187
INT, 1330
INTRVL, 1352
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LA, 1488
LIST, 1472
LO, 1491
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MKCHSET, 1538
MODMON, 1600
MODMONOM, 1612
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
ORDCOMP, 1777
OSI, 1830
OVAR, 1803
PADICRAT, 1852
PADICRC, 1857
PBWLB, 2020
PERM, 1916
PI, 2066
POINT, 2026
POLY, 2044
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QUAT, 2133
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAOS, 2386
SDPOL, 2352
SDVAR, 2358
SET, 2338
SHDP, 2476
SINT, 2380
SMP, 2391

STRING, 2575
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
U32VEC, 2869
ULS, 2763
ULSCONS, 2771
UP, 2795
VECTOR, 2878
minColIndex
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
mindeg
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
mindegTerm
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
minimalPolynomial
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PF, 2071
RADFF, 2160
SAE, 2368
minimize
FRIDEAL, 965
minimumDegree
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
LODO, 1437
LODO1, 1447
LODO2, 1459
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
OMLO, 1773
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819
minimumExponent
MFLOAT, 1516
minIndex
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669

FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
minordet
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
SQMATRIX, 2515
minPoints
PLOT, 1995
minPoints3D
PLOT3D, 2008
minPoly
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
minRowIndex
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
MINT, 1525
-?, 1525
?<?, 1525
?<=?, 1525
?>?, 1525
?>=?, 1525
?**?, 1525
?*?, 1525
?+?, 1525
?-?, 1525
?=?, 1525
?^?, 1525
?~=?, 1525
?quo?, 1525
?rem?, 1525
0, 1525
1, 1525
abs, 1525
addmod, 1525
associates?, 1525
base, 1525
binomial, 1525
bit?, 1525
characteristic, 1525
coerce, 1525
convert, 1525
copy, 1525
D, 1525
dec, 1525
differentiate, 1525
divide, 1525
euclideanSize, 1525
even?, 1525
expressIdealMember, 1525

exquo, 1525
extendedEuclidean, 1525
factor, 1525
factorial, 1525
gcd, 1525
gcdPolynomial, 1525
hash, 1525
inc, 1525
init, 1525
invmod, 1525
latex, 1525
lcm, 1525
length, 1525
mask, 1525
max, 1525
maxint, 1525
min, 1525
mulmod, 1525
multiEuclidean, 1525
negative?, 1525
nextItem, 1525
odd?, 1525
one?, 1525
patternMatch, 1525
permutation, 1525
positive?, 1525
positiveRemainder, 1525
powmod, 1525
prime?, 1525
principalIdeal, 1525
random, 1525
rational, 1525
rational?, 1525
rationalIfCan, 1525
recip, 1525
reducedSystem, 1525
retract, 1525
retractIfCan, 1525
sample, 1525
shift, 1525
sign, 1525
sizeLess?, 1525
squareFree, 1525
squareFreePart, 1525
submod, 1525
subtractIfCan, 1525
symmetricRemainder, 1525
unit?, 1525
unitCanonical, 1525
unitNormal, 1525
zero?, 1525
minusInfinity
ORDCOMP, 1777
mirror
LEXP, 1403
LPOLY, 1415
MAGMA, 1533
OFMONOID, 1795
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
mkAnswer
IR, 1343
MKCHSET, 1538
?<?, 1538
?<=?, 1538
?>?, 1538
?>=?, 1538
?=?, 1538
?~=?, 1538
coerce, 1538
hash, 1538
latex, 1538
max, 1538
min, 1538
position, 1538
setPosition, 1538
mkcomm
COMM, 397
MMLFORM, 1571
?=?, 1571
?~=?, 1571
coerce, 1571
coerceL, 1571
coerceS, 1571
display, 1571
exprex, 1571
hash, 1571
latex, 1571
MODFIELD, 1606
-?, 1606

?**?, 1606
?*?, 1606
?+?, 1606
?-?, 1606
?/?, 1606
?=?, 1606
?^?, 1606
?~=?, 1606
?quo?, 1606
?rem?, 1606
0, 1606
1, 1606
associates?, 1606
characteristic, 1606
coerce, 1606
divide, 1606
euclideanSize, 1606
expressIdealMember, 1606
exQuo, 1606
exquo, 1606
extendedEuclidean, 1606
factor, 1606
gcd, 1606
gcdPolynomial, 1606
hash, 1606
inv, 1606
latex, 1606
lcm, 1606
modulus, 1606
multiEuclidean, 1606
one?, 1606
prime?, 1606
principalIdeal, 1606
recip, 1606
reduce, 1606
sample, 1606
sizeLess?, 1606
squareFree, 1606
squareFreePart, 1606
subtractIfCan, 1606
unit?, 1606
unitCanonical, 1606
unitNormal, 1606
zero?, 1606
modifyPoint
SUBSPACE, 2582
modifyPointData
SPACE3, 2701
VIEW3D, 2679
MODMON, 1599
-?, 1600
?<?, 1600
?<=?, 1600
?>?, 1600
?>=?, 1600
?**?, 1600
?*?, 1600
?+?, 1600
?-?, 1600
?.?, 1600
?/?, 1600
?=?, 1600
?^?, 1600
?~=?, 1600
?quo?, 1600
?rem?, 1600
0, 1600
1, 1600
An, 1600
associates?, 1600
binomThmExpt, 1600
characteristic, 1600
charthRoot, 1600
coefficient, 1600
coefficients, 1600
coerce, 1600
composite, 1600
computePowers, 1600
conditionP, 1600
content, 1600
convert, 1600
D, 1600
degree, 1600
differentiate, 1600
discriminant, 1600
divide, 1600
divideExponents, 1600
elt, 1600
euclideanSize, 1600
eval, 1600
expressIdealMember, 1600
exquo, 1600

extendedEuclidean, 1600
factor, 1600
factorPolynomial, 1600
factorSquareFreePolynomial, 1600
frobenius, 1600
gcd, 1600
gcdPolynomial, 1600
ground, 1600
ground?, 1600
hash, 1600
index, 1600
init, 1600
integrate, 1600
isExpt, 1600
isPlus, 1600
isTimes, 1600
karatsubaDivide, 1600
latex, 1600
lcm, 1600
leadingCoefficient, 1600
leadingMonomial, 1600
lift, 1600
lookup, 1600
mainVariable, 1600
makeSUP, 1600
map, 1600
mapExponents, 1600
max, 1600
min, 1600
minimumDegree, 1600
modulus, 1600
monicDivide, 1600
monomial, 1600
monomial?, 1600
monomials, 1600
multiEuclidean, 1600
multiplyExponents, 1600
multivariate, 1600
nextItem, 1600
numberOfMonomials, 1600
one?, 1600
order, 1600
patternMatch, 1600
pomopo, 1600
pow, 1600
prime?, 1600
primitiveMonomials, 1600
primitivePart, 1600
principalIdeal, 1600
pseudoDivide, 1600
pseudoQuotient, 1600
pseudoRemainder, 1600
random, 1600
recip, 1600
reduce, 1600
reducedSystem, 1600
reductum, 1600
resultant, 1600
retract, 1600
retractIfCan, 1600
sample, 1600
separate, 1600
setPoly, 1600
shiftLeft, 1600
shiftRight, 1600
size, 1600
sizeLess?, 1600
solveLinearPolynomialEquation, 1600
squareFree, 1600
squareFreePart, 1600
squareFreePolynomial, 1600
subResultantGcd, 1600
subtractIfCan, 1600
totalDegree, 1600
unit?, 1600
unitCanonical, 1600
unitNormal, 1600
univariate, 1600
unmakeSUP, 1600
UnVectorise, 1600
variables, 1600
Vectorise, 1600
vectorise, 1600
zero?, 1600
ModMonic, 1599
MODMONOM, 1612
?<?, 1612
?<=?, 1612
?>?, 1612
?>=?, 1612
?=?, 1612
?~=?, 1612

coerce, 1612
construct, 1612
exponent, 1612
hash, 1612
index, 1612
latex, 1612
max, 1612
min, 1612
MODOP, 1615
-?, 1615, 1771
?**?, 1615, 1771
?*?, 1615, 1771
?+?, 1615, 1771
?-?, 1615, 1771
?.?, 1615, 1771
?=?, 1615, 1771
?^?, 1615, 1771
?~=?, 1615, 1771
0, 1615, 1771
1, 1615, 1771
adjoint, 1615, 1771
characteristic, 1615, 1771
charthRoot, 1615, 1771
coerce, 1615, 1771
conjug, 1615, 1771
evaluate, 1615, 1771
evaluateInverse, 1615, 1771
hash, 1615, 1771
latex, 1615, 1771
makeop, 1615, 1771
one?, 1615, 1771
opeval, 1615, 1771
recip, 1615, 1771
retract, 1615, 1771
retractIfCan, 1615, 1771
sample, 1615, 1771
subtractIfCan, 1615, 1771
zero?, 1615, 1771
MODRING, 1608
-?, 1609
?**?, 1609
?*?, 1609
?+?, 1609
?-?, 1609
?=?, 1609
?^?, 1609
?~=?, 1609
0, 1609
1, 1609
characteristic, 1609
coerce, 1609
exQuo, 1609
hash, 1609
inv, 1609
latex, 1609
modulus, 1609
one?, 1609
recip, 1609
reduce, 1609
sample, 1609
subtractIfCan, 1609
zero?, 1609
ModularField, 1606
ModularRing, 1608
module
FRMOD, 970
ModuleMonomial, 1612
ModuleOperator, 1615
moduloP
BPADIC, 242
IPADIC, 1262
PADIC, 1847
modulus
BPADIC, 242
EMR, 672
IPADIC, 1262
MODFIELD, 1606
MODMON, 1600
MODRING, 1609
PADIC, 1847
MOEBIUS, 1622
?**?, 1622
?*?, 1622
?/?, 1622
?=?, 1622
?^?, 1622
?~=?, 1622
1, 1622
coerce, 1622
commutator, 1622
conjugate, 1622
eval, 1622

hash, 1622
inv, 1622
latex, 1622
moebius, 1622
one?, 1622
recip, 1622
sample, 1622
scale, 1622
shift, 1622
moebius
MOEBIUS, 1622
MoebiusTransform, 1622
monic?
NSMP, 1681
monicDivide
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
monicLeftDivide
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
monicModulo
NSMP, 1681
NSUP, 1696
monicRightDivide
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
MonoidRing, 1626
monom
FM1, 987
LPOLY, 1415
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
monomial
CLIF, 388
DMP, 560
DSMP, 529
EXPUPXS, 710
FM, 983
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HDMP, 1150
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
INDE, 1187
ISUPS, 1279
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
OMLO, 1773
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SMTS, 2409

SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
monomial2series
NSDPS, 1670
monomial?
DMP, 560
DSMP, 529
EXPUPXS, 710
FM1, 987
GDMP, 1022
GSERIES, 1061
HDMP, 1150
ISUPS, 1279
LAUPOL, 1390
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
monomials
DMP, 560
DSMP, 529
FM1, 987
GDMP, 1022
HDMP, 1150
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
MonteCarlo
GOPT0, 1081
more?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732

ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
morphism
AUTOMOR, 231
move
VIEW2d, 2739
VIEW3D, 2679
movedPoints
PERM, 1916
PERMGRP, 1926
MPOLY, 1649
-?, 1650
?<?, 1650
?<=?, 1650
?>?, 1650
?>=?, 1650
?**?, 1650
?*?, 1650
?+?, 1650
?-?, 1650
?/?, 1650
?=?, 1650
?^?, 1650
?~=?, 1650

0, 1650
1, 1650
associates?, 1650
binomThmExpt, 1650
characteristic, 1650
charthRoot, 1650
coefficient, 1650
coefficients, 1650
coerce, 1650
conditionP, 1650
content, 1650
convert, 1650
D, 1650
degree, 1650
differentiate, 1650
discriminant, 1650
eval, 1650
exquo, 1650
factor, 1650
factorPolynomial, 1650
factorSquareFreePolynomial, 1650
gcd, 1650
gcdPolynomial, 1650
ground, 1650
ground?, 1650
hash, 1650
isExpt, 1650
isPlus, 1650
isTimes, 1650
latex, 1650
lcm, 1650
leadingCoefficient, 1650
leadingMonomial, 1650
mainVariable, 1650
map, 1650
mapExponents, 1650
max, 1650
min, 1650
minimumDegree, 1650
monicDivide, 1650
monomial, 1650
monomial?, 1650
monomials, 1650
multivariate, 1650
numberOfMonomials, 1650
one?, 1650
patternMatch, 1650
pomopo, 1650
prime?, 1650
primitiveMonomials, 1650
primitivePart, 1650
recip, 1650
reducedSystem, 1650
reductum, 1650
resultant, 1650
retract, 1650
retractIfCan, 1650
sample, 1650
solveLinearPolynomialEquation, 1650
squareFree, 1650
squareFreePart, 1650
squareFreePolynomial, 1650
subtractIfCan, 1650
totalDegree, 1650
unit?, 1650
unitCanonical, 1650
unitNormal, 1650
univariate, 1650
variables, 1650
zero?, 1650
MRING, 1626
-?, 1626
?**?, 1626
?*?, 1626
?+?, 1626
?-?, 1626
?=?, 1626
?^?, 1626
?~=?, 1626
0, 1626
1, 1626
characteristic, 1626
charthRoot, 1626
coefficient, 1626
coefficients, 1626
coerce, 1626
hash, 1626
index, 1626
latex, 1626
leadingCoefficient, 1626
leadingMonomial, 1626
lookup, 1626

map, 1626
monomial, 1626
monomial?, 1626
monomials, 1626
numberOfMonomials, 1626
one?, 1626
random, 1626
recip, 1626
reductum, 1626
retract, 1626
retractIfCan, 1626
sample, 1626
size, 1626
subtractIfCan, 1626
terms, 1626
zero?, 1626
MSET, 1638
?<?, 1638
?=?, 1638
?~=?, 1638
#?, 1638
any?, 1638
bag, 1638
brace, 1638
coerce, 1638
construct, 1638
convert, 1638
copy, 1638
count, 1638
dictionary, 1638
difference, 1638
duplicates, 1638
empty, 1638
empty?, 1638
eq?, 1638
eval, 1638
every?, 1638
extract, 1638
find, 1638
hash, 1638
insert, 1638
inspect, 1638
intersect, 1638
latex, 1638
less?, 1638
map, 1638
member?, 1638
members, 1638
more?, 1638
multiset, 1638
parts, 1638
reduce, 1638
remove, 1638
removeDuplicates, 1638
sample, 1638
select, 1638
set, 1638
size?, 1638
subset?, 1638
symmetricDifference, 1638
union, 1638
mulmod
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
multiEuclidean
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061

HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
multiple?
PATTERN, 1894
multiplicative?
DIRRING, 551
multiplyCoefficients
ISUPS, 1279
SULS, 2425
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UTS, 2844
UTSZ, 2854
multiplyExponents
EXPUPXS, 710
GSERIES, 1061
ISUPS, 1279
MODMON, 1600
MYUP, 1663
NSDPS, 1670
NSUP, 1696
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
multisect
UFPS, 2757
UTS, 2844
UTSZ, 2854
Multiset, 1638
multiset
MSET, 1638
multivariate
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818

POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
MultivariatePolynomial, 1649
multMonom
GMODPOL, 1029
multV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
mvar
GPOLSET, 1044
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
MYEXPR, 1655
-?, 1656
?<?, 1656
?<=?, 1656
?>?, 1656
?>=?, 1656
?**?, 1656
?*?, 1656
?+?, 1656
?-?, 1656
?/?, 1656
?=?, 1656
?^?, 1656
?~=?, 1656
?quo?, 1656
?rem?, 1656
0, 1656
1, 1656
applyQuote, 1656
associates?, 1656
belong?, 1656
binomial, 1656
box, 1656
characteristic, 1656
charthRoot, 1656
coerce, 1656
commutator, 1656
conjugate, 1656
convert, 1656
D, 1656
definingPolynomial, 1656
denom, 1656
denominator, 1656
differentiate, 1656
distribute, 1656
divide, 1656
elt, 1656
euclideanSize, 1656
eval, 1656
even?, 1656
expressIdealMember, 1656
exquo, 1656
extendedEuclidean, 1656
factor, 1656
factorial, 1656
factorials, 1656
freeOf?, 1656
gcd, 1656
gcdPolynomial, 1656
ground, 1656
ground?, 1656
hash, 1656
height, 1656
inv, 1656
is?, 1656
isExpt, 1656
isMult, 1656
isPlus, 1656
isPower, 1656
isTimes, 1656
kernel, 1656
kernels, 1656
latex, 1656
lcm, 1656
mainKernel, 1656
map, 1656
max, 1656
min, 1656
minPoly, 1656
multiEuclidean, 1656
numer, 1656

numerator, 1656
odd?, 1656
one?, 1656
operator, 1656
operators, 1656
paren, 1656
patternMatch, 1656
permutation, 1656
prime?, 1656
principalIdeal, 1656
product, 1656
recip, 1656
reducedSystem, 1656
retract, 1656
retractIfCan, 1656
sample, 1656
sizeLess?, 1656
squareFree, 1656
squareFreePart, 1656
subst, 1656
subtractIfCan, 1656
summation, 1656
tower, 1656
unit?, 1656
unitCanonical, 1656
unitNormal, 1656
univariate, 1656
variables, 1656
zero?, 1656
MyExpression, 1655
MyUnivariatePolynomial, 1662
MYUP, 1662
-?, 1663
?<?, 1663
?<=?, 1663
?>?, 1663
?>=?, 1663
?**?, 1663
?*?, 1663
?+?, 1663
?-?, 1663
?.?, 1663
?/?, 1663
?=?, 1663
?^?, 1663
?~=?, 1663
?quo?, 1663
?rem?, 1663
0, 1663
1, 1663
associates?, 1663
binomThmExpt, 1663
characteristic, 1663
charthRoot, 1663
coefficient, 1663
coefficients, 1663
coerce, 1663
composite, 1663
conditionP, 1663
content, 1663
convert, 1663
D, 1663
degree, 1663
differentiate, 1663
discriminant, 1663
divide, 1663
divideExponents, 1663
elt, 1663
euclideanSize, 1663
eval, 1663
expressIdealMember, 1663
exquo, 1663
extendedEuclidean, 1663
factor, 1663
factorPolynomial, 1663
factorSquareFreePolynomial, 1663
fmecg, 1663
gcd, 1663
gcdPolynomial, 1663
ground, 1663
ground?, 1663
hash, 1663
init, 1663
integrate, 1663
isExpt, 1663
isPlus, 1663
isTimes, 1663
karatsubaDivide, 1663
latex, 1663
lcm, 1663
leadingCoefficient, 1663
leadingMonomial, 1663

mainVariable, 1663
makeSUP, 1663
map, 1663
mapExponents, 1663
max, 1663
min, 1663
minimumDegree, 1663
monicDivide, 1663
monomial, 1663
monomial?, 1663
monomials, 1663
multiEuclidean, 1663
multiplyExponents, 1663
multivariate, 1663
nextItem, 1663
numberOfMonomials, 1663
one?, 1663
order, 1663
patternMatch, 1663
pomopo, 1663
prime?, 1663
primitiveMonomials, 1663
primitivePart, 1663
principalIdeal, 1663
pseudoDivide, 1663
pseudoQuotient, 1663
pseudoRemainder, 1663
recip, 1663
reducedSystem, 1663
reductum, 1663
resultant, 1663
retract, 1663
retractIfCan, 1663
sample, 1663
separate, 1663
shiftLeft, 1663
shiftRight, 1663
sizeLess?, 1663
solveLinearPolynomialEquation, 1663
squareFree, 1663
squareFreePart, 1663
squareFreePolynomial, 1663
subResultantGcd, 1663
subtractIfCan, 1663
totalDegree, 1663
unit?, 1663
unitCanonical, 1663
unitNormal, 1663
univariate, 1663
unmakeSUP, 1663
variables, 1663
vectorise, 1663
zero?, 1663

name
BINFILE, 280
BOP, 258
FILE, 772
FNAME, 780
FTEM, 938
FUNCTION, 1015
KAFILE, 1382
KERNEL, 1372
RULECOLD, 2307
SYMBOL, 2608
TEXTFILE, 2661
nand
BITS, 299
BOOLEAN, 307
IBITS, 1169
nary?
BOP, 258
ncols
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
negative?
BINARY, 277
BPADICRT, 247
DECIMAL, 453
DFLOAT, 575
DIRPROD, 534
DPMM, 540
DPMO, 545

EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HDP, 1143
HEXADEC, 1113
INT, 1330
INTRVL, 1352
LA, 1488
MFLOAT, 1516
MINT, 1525
ODP, 1783
ONECOMP, 1744
ORDCOMP, 1777
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
RECLOS, 2203
ROIRC, 2276
ROMAN, 2293
SHDP, 2476
SINT, 2380
SULS, 2425
ULS, 2763
ULSCONS, 2771
NeitherSparseOrDensePowerSeries, 1669
new
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
BITS, 299
CDFMAT, 413
CDFVEC, 419
COMPPROP, 2592
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DLIST, 448
FARRAY, 856
FNAME, 780
FORMULA, 2312
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
MATRIX, 1591
NSDPS, 1670
PATLRES, 1904
PATRES, 1906
POINT, 2026
PRIMARR, 2075
STREAM, 2550
STRING, 2575
SUBSPACE, 2582
SYMBOL, 2608
TEX, 2645
U32VEC, 2869
VECTOR, 2878
newElement
PACOFF, 2102
PACRAT, 2112
NewSparseMultivariatePolynomial, 1680
NewSparseUnivariatePolynomial, 1695
newSubProgram
SYMS, 2665
newTypeLists
SYMTAB, 2616
nextItem
ALGFF, 28
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
EXPEXPAN, 682
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FRAC, 956
HEXADEC, 1113
IFF, 1252
INT, 1330

IPF, 1271
MCMPLX, 1511
MINT, 1525
MODMON, 1600
MYUP, 1663
NSUP, 1696
PACOFF, 2102
PADICRAT, 1852
PADICRC, 1857
PF, 2071
RADFF, 2160
RADIX, 2172
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
ZMOD, 1336
nextsubResultant2
NSMP, 1681
nil
LIST, 1472
nilFactor
FR, 756
NIPROB, 1713
?=?, 1713
?~=?, 1713
coerce, 1713
hash, 1713
latex, 1713
retract, 1713
NNI, 1706
?<?, 1706
?<=?, 1706
?>?, 1706
?>=?, 1706
?**?, 1706
?*?, 1706
?+?, 1706
?=?, 1706
?^?, 1706
?~=?, 1706
?quo?, 1706
?rem?, 1706
0, 1706
1, 1706
coerce, 1706
divide, 1706
exquo, 1706
gcd, 1706
hash, 1706
latex, 1706
max, 1706
min, 1706
one?, 1706
random, 1706
recip, 1706
sample, 1706
shift, 1706
subtractIfCan, 1706
sup, 1706
zero?, 1706
node
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
node?
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
nodeOf?
SPLTREE, 2485
nodes
ALIST, 221
BBTREE, 237
BSTREE, 287

BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
PENDTREE, 1911
SPLTREE, 2485
STREAM, 2550
TREE, 2710
noncommutativeJordanAlgebra?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
NONE, 1704
?=?, 1704
?~=?, 1704
coerce, 1704
hash, 1704
latex, 1704
None, 1704
NonNegativeInteger, 1706
nonSingularModel
ALGFF, 28
RADFF, 2160
nor
BITS, 299
BOOLEAN, 307
IBITS, 1169
norm
ALGFF, 28
AN, 35
COMPLEX, 406
DFLOAT, 575
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRIDEAL, 965
FRMOD, 970
IAN, 1245
IFF, 1252
IPF, 1271
MCMPLX, 1511
MFLOAT, 1516
OCT, 1731
PF, 2071
QUAT, 2133
RADFF, 2160
SAE, 2368
normal?
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PF, 2071
normalElement
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PF, 2071
normalize
FLOAT, 879
normalizeAtInfinity
ALGFF, 28
RADFF, 2160
normalized?
GTSET, 1054

NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
NOT
SWITCH, 2597
Not
IBITS, 1169
SINT, 2380
not?
BITS, 299
BOOLEAN, 307
IBITS, 1169
OUTFORM, 1834
SINT, 2380
notelem
IR, 1343
NOTTING, 1711
*, 1711
**, 1711
/, 1711
=, 1711
^, 1711
^=, 1711
1, 1711
coerce, 1711
commutator, 1711
conjugate, 1711
hash, 1711
inv, 1711
latex, 1711
one?, 1711
recip, 1711
retract, 1711
sample, 1711
NottinghamGroup, 1711
nrows
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
NSDPS, 1669
-?, 1670
?**?, 1670
?*?, 1670
?+?, 1670
?-?, 1670
?.?, 1670
?.first, 1670
?.last, 1670
?.rest, 1670
?.value, 1670
?/?, 1670
?=?, 1670
?^?, 1670
?~=?, 1670
?quo?, 1670
?rem?, 1670
#?, 1670
0, 1670
1, 1670
any?, 1670
approximate, 1670
associates?, 1670
center, 1670
characteristic, 1670
charthRoot, 1670
child?, 1670
children, 1670
coefficient, 1670
coefOfFirstNonZeroTerm, 1670
coerce, 1670
complete, 1670
concat, 1670
construct, 1670
convert, 1670
copy, 1670
count, 1670
cycleEntry, 1670
cycleLength, 1670
cycleSplit, 1670
cycleTail, 1670
cyclic?, 1670
D, 1670

degree, 1670
delay, 1670
delete, 1670
differentiate, 1670
distance, 1670
divide, 1670
elt, 1670
empty, 1670
empty?, 1670
entries, 1670
entry?, 1670
eq?, 1670
euclideanSize, 1670
eval, 1670
every?, 1670
explicitEntries?, 1670
explicitlyEmpty?, 1670
explicitlyFinite?, 1670
expressIdealMember, 1670
exquo, 1670
extend, 1670
extendedEuclidean, 1670
factor, 1670
fill, 1670
filterUpTo, 1670
find, 1670
findCoef, 1670
findTerm, 1670
first, 1670
frst, 1670
gcd, 1670
gcdPolynomial, 1670
hash, 1670
index?, 1670
indices, 1670
insert, 1670
inv, 1670
last, 1670
latex, 1670
lazy?, 1670
lazyEvaluate, 1670
lcm, 1670
leadingCoefficient, 1670
leadingMonomial, 1670
leaf?, 1670
leaves, 1670
less?, 1670
map, 1670
maxIndex, 1670
member?, 1670
members, 1670
minIndex, 1670
monomial, 1670
monomial2series, 1670
monomial?, 1670
more?, 1670
multiEuclidean, 1670
multiplyExponents, 1670
new, 1670
node?, 1670
nodes, 1670
numberOfComputedEntries, 1670
one?, 1670
order, 1670
orderIfNegative, 1670
parts, 1670
pole?, 1670
posExpnPart, 1670
possiblyInfinite?, 1670
prime?, 1670
principalIdeal, 1670
printInfo, 1670
qelt, 1670
qsetelt, 1670
recip, 1670
reduce, 1670
reductum, 1670
remove, 1670
removeDuplicates, 1670
removeFirstZeroes, 1670
removeZeroes, 1670
rest, 1670
rst, 1670
sample, 1670
sbt, 1670
second, 1670
select, 1670
series, 1670
setchildren, 1670
setelt, 1670
setfirst, 1670
setlast, 1670

setrest, 1670
setvalue, 1670
shift, 1670
size?, 1670
sizeLess?, 1670
split, 1670
squareFree, 1670
squareFreePart, 1670
subtractIfCan, 1670
swap, 1670
tail, 1670
terms, 1670
third, 1670
truncate, 1670
unit?, 1670
unitCanonical, 1670
unitNormal, 1670
value, 1670
variable, 1670
variables, 1670
zero?, 1670
NSMP, 1680
-?, 1681
?<?, 1681
?<=?, 1681
?>?, 1681
?>=?, 1681
?**?, 1681
?*?, 1681
?+?, 1681
?-?, 1681
?/?, 1681
?=?, 1681
?^?, 1681
?~=?, 1681
0, 1681
1, 1681
associates?, 1681
binomThmExpt, 1681
characteristic, 1681
charthRoot, 1681
coefficient, 1681
coefficients, 1681
coerce, 1681
conditionP, 1681
content, 1681
D, 1681
deepestInitial, 1681
deepestTail, 1681
degree, 1681
differentiate, 1681
discriminant, 1681
eval, 1681
exactQuotient, 1681
exquo, 1681
extendedSubResultantGcd, 1681
factor, 1681
factorPolynomial, 1681
factorSquareFreePolynomial, 1681
gcd, 1681
gcdPolynomial, 1681
ground, 1681
ground?, 1681
halfExtendedSubResultantGcd1, 1681
halfExtendedSubResultantGcd2, 1681
hash, 1681
head, 1681
headReduce, 1681
headReduced?, 1681
infRittWu?, 1681
init, 1681
initiallyReduce, 1681
initiallyReduced?, 1681
isExpt, 1681
isPlus, 1681
isTimes, 1681
iteratedInitials, 1681
lastSubResultant, 1681
latex, 1681
LazardQuotient, 1681
LazardQuotient2, 1681
lazyPquo, 1681
lazyPrem, 1681
lazyPremWithDefault, 1681
lazyPseudoDivide, 1681
lazyResidueClass, 1681
lcm, 1681
leadingCoefficient, 1681
leadingMonomial, 1681
leastMonomial, 1681
mainCoefficients, 1681
mainContent, 1681

mainMonomial, 1681
mainMonomials, 1681
mainPrimitivePart, 1681
mainSquareFreePart, 1681
mainVariable, 1681
map, 1681
mapExponents, 1681
max, 1681
mdeg, 1681
min, 1681
minimumDegree, 1681
monic?, 1681
monicDivide, 1681
monicModulo, 1681
monomial, 1681
monomial?, 1681
monomials, 1681
multivariate, 1681
mvar, 1681
nextsubResultant2, 1681
normalized?, 1681
numberOfMonomials, 1681
one?, 1681
patternMatch, 1681
pomopo, 1681
pquo, 1681
prem, 1681
prime?, 1681
primitiveMonomials, 1681
primitivePart, 1681
primPartElseUnitCanonical, 1681
pseudoDivide, 1681
quasiMonic?, 1681
recip, 1681
reduced?, 1681
reducedSystem, 1681
reductum, 1681
resultant, 1681
retract, 1681
retractIfCan, 1681
RittWuCompare, 1681
sample, 1681
solveLinearPolynomialEquation, 1681
squareFree, 1681
squareFreePart, 1681
squareFreePolynomial, 1681
subResultantChain, 1681
subResultantGcd, 1681
subtractIfCan, 1681
supRittWu?, 1681
tail, 1681
totalDegree, 1681
unit?, 1681
unitCanonical, 1681
unitNormal, 1681
univariate, 1681
variables, 1681
zero?, 1681
NSUP, 1695
-?, 1696
?<?, 1696
?<=?, 1696
?>?, 1696
?>=?, 1696
?**?, 1696
?*?, 1696
?+?, 1696
?-?, 1696
?.?, 1696
?/?, 1696
?=?, 1696
?^?, 1696
?~=?, 1696
?quo?, 1696
?rem?, 1696
0, 1696
1, 1696
associates?, 1696
binomThmExpt, 1696
characteristic, 1696
charthRoot, 1696
coefficient, 1696
coefficients, 1696
coerce, 1696
composite, 1696
conditionP, 1696
content, 1696
convert, 1696
D, 1696
degree, 1696
differentiate, 1696
discriminant, 1696

divide, 1696
divideExponents, 1696
elt, 1696
euclideanSize, 1696
eval, 1696
expressIdealMember, 1696
exquo, 1696
extendedEuclidean, 1696
extendedResultant, 1696
extendedSubResultantGcd, 1696
factor, 1696
factorPolynomial, 1696
factorSquareFreePolynomial, 1696
fmecg, 1696
gcd, 1696
gcdPolynomial, 1696
ground, 1696
ground?, 1696
halfExtendedResultant1, 1696
halfExtendedResultant2, 1696
halfExtendedSubResultantGcd1, 1696
halfExtendedSubResultantGcd2, 1696
hash, 1696
init, 1696
integrate, 1696
isExpt, 1696
isPlus, 1696
isTimes, 1696
karatsubaDivide, 1696
lastSubResultant, 1696
latex, 1696
lazyPseudoDivide, 1696
lazyPseudoQuotient, 1696
lazyPseudoRemainder, 1696
lazyResidueClass, 1696
lcm, 1696
leadingCoefficient, 1696
leadingMonomial, 1696
mainVariable, 1696
makeSUP, 1696
map, 1696
mapExponents, 1696
max, 1696
min, 1696
minimumDegree, 1696
monicDivide, 1696
monicModulo, 1696
monomial, 1696
monomial?, 1696
monomials, 1696
multiEuclidean, 1696
multiplyExponents, 1696
multivariate, 1696
nextItem, 1696
numberOfMonomials, 1696
one?, 1696
order, 1696
patternMatch, 1696
pomopo, 1696
prime?, 1696
primitiveMonomials, 1696
primitivePart, 1696
principalIdeal, 1696
pseudoDivide, 1696
pseudoQuotient, 1696
pseudoRemainder, 1696
recip, 1696
reducedSystem, 1696
reductum, 1696
resultant, 1696
retract, 1696
retractIfCan, 1696
sample, 1696
separate, 1696
shiftLeft, 1696
shiftRight, 1696
sizeLess?, 1696
solveLinearPolynomialEquation, 1696
squareFree, 1696
squareFreePart, 1696
squareFreePolynomial, 1696
subResultantGcd, 1696
subResultantsChain, 1696
subtractIfCan, 1696
totalDegree, 1696
unit?, 1696
unitCanonical, 1696
unitNormal, 1696
univariate, 1696
unmakeSUP, 1696
variables, 1696
vectorise, 1696

zero?, 1696
nthCoef
DIV, 563
FAGROUP, 975
FAMONOID, 978
IFAMON, 1255
nthExpon
FGROUP, 980
FMONOID, 991
LMOPS, 1477
OFMONOID, 1795
nthExponent
FR, 756
nthFactor
DIV, 563
FAGROUP, 975
FAMONOID, 978
FGROUP, 980
FMONOID, 991
FR, 756
IFAMON, 1255
LMOPS, 1477
OFMONOID, 1795
nthFlag
FR, 756
nthFractionalTerm
PFR, 1880
nthRoot
AN, 35
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
IAN, 1245
INTRVL, 1352
MCMPLX, 1511
MFLOAT, 1516
RECLOS, 2203
SMTS, 2409
SULS, 2425
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
Nul
EAB, 713
null
LIST, 1472
null?
INFORM, 1311
SEX, 2360
SEXOF, 2363
nullary?
BOP, 258
nullity
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
nullSpace
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
number?
EXPR, 694
numberOfChildren
SUBSPACE, 2582
numberOfComponents
ALGFF, 28
RADFF, 2160
SPACE3, 2701
numberOfComputedEntries
NSDPS, 1670
STREAM, 2550
numberOfCycles

PERM, 1916
numberOfFactors
FR, 756
numberOfFractionalTerms
PFR, 1880
numberOfHues
COLOR, 394
numberOfMonomials
DMP, 560
DSMP, 529
FM1, 987
GDMP, 1022
HDMP, 1150
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
numer
AN, 35
BINARY, 277
BPADICRT, 247
DECIMAL, 453
EXPEXPAN, 682
EXPR, 694
FRAC, 956
FRIDEAL, 965
HEXADEC, 1113
IAN, 1245
LA, 1488
LO, 1491
MYEXPR, 1656
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
numerator
BINARY, 277
BPADICRT, 247
DECIMAL, 453
EXPEXPAN, 682
EXPR, 694
FRAC, 956
HEXADEC, 1113
MYEXPR, 1656
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
numerators
CONTFRAC, 432
numericalIntegration
D01AJFA, 602
D01AKFA, 605
D01ALFA, 608
D01AMFA, 611
D01APFA, 617, 620
D01ASFA, 624
D01FCFA, 627
D01GBFA, 630
D01TRNS, 633
D10ANFA, 614
NumericalIntegrationProblem, 1713
NumericalODEProblem, 1716
numericalOptimization
E04DGFA, 717
E04FDFA, 720
E04GCFA, 724
E04JAFA, 728
E04MBFA, 732
E04NAFA, 735
E04UCFA, 739
NumericalOptimizationProblem, 1719

NumericalPDEProblem, 1722
numFunEvals
    PLOT, 1995
numFunEvals3D
    PLOT3D, 2008

obj
    ANY, 50
objectOf
    ANY, 50
objects
    SPACE3, 2701
OCT, 1731
    -?, 1731
    ?<?, 1731
    ?<=?, 1731
    ?>?, 1731
    ?>=?, 1731
    ?**?, 1731
    ?*?, 1731
    ?+?, 1731
    ?-?, 1731
    ?.?, 1731
    ?=?, 1731
    ?^?, 1731
    ?~=?, 1731
    0, 1731
    1, 1731
    abs, 1731
    characteristic, 1731
    charthRoot, 1731
    coerce, 1731
    conjugate, 1731
    convert, 1731
    eval, 1731
    hash, 1731
    imagE, 1731
    imagI, 1731
    imagi, 1731
    imagJ, 1731
    imagj, 1731
    imagK, 1731
    imagk, 1731
    index, 1731
    inv, 1731
    latex, 1731
    lookup, 1731
    map, 1731
    max, 1731
    min, 1731
    norm, 1731
    octon, 1731
    one?, 1731
    random, 1731
    rational, 1731
    rational?, 1731
    rationalIfCan, 1731
    real, 1731
    recip, 1731
    retract, 1731
    retractIfCan, 1731
    sample, 1731
    size, 1731
    subtractIfCan, 1731
    zero?, 1731
octon
    OCT, 1731
Octonion, 1731
odd?
    AN, 35
    EXPR, 694
    FEXPR, 917
    IAN, 1245
    INT, 1330
    MINT, 1525
    MYEXPR, 1656
    PERM, 1916
    ROMAN, 2293
    SINT, 2380
oddlambert
    UFPS, 2757
    UTS, 2844
    UTSZ, 2854
ODEIFTBL, 1734
    clearTheIFTable, 1734
    iFTable, 1734
    insert, 1734
    keys, 1734
    showIntensityFunctions, 1734
    showTheIFTable, 1734
ODEIntensityFunctionsTable, 1734
ODEPROB, 1716

?=?, 1716
?~=?, 1716
coerce, 1716
hash, 1716
latex, 1716
retract, 1716
ODESolve
D02BBFA, 638
D02BHFA, 641
D02CJFA, 645
D02EJFA, 648
ODP, 1783
-?, 1783
?<?, 1783
?<=?, 1783
?>?, 1783
?>=?, 1783
?**?, 1783
?*?, 1783
?+?, 1783
?-?, 1783
?.?, 1783
?/?, 1783
?=?, 1783
?^?, 1783
?~=?, 1783
#?, 1783
0, 1783
1, 1783
abs, 1783
any?, 1783
characteristic, 1783
coerce, 1783
copy, 1783
count, 1783
D, 1783
differentiate, 1783
dimension, 1783
directProduct, 1783
dot, 1783
elt, 1783
empty, 1783
empty?, 1783
entries, 1783
entry?, 1783
eq?, 1783
eval, 1783
every?, 1783
fill, 1783
first, 1783
hash, 1783
index, 1783
index?, 1783
indices, 1783
latex, 1783
less?, 1783
lookup, 1783
map, 1783
max, 1783
maxIndex, 1783
member?, 1783
members, 1783
min, 1783
minIndex, 1783
more?, 1783
negative?, 1783
one?, 1783
parts, 1783
positive?, 1783
qelt, 1783
qsetelt, 1783
random, 1783
recip, 1783
reducedSystem, 1783
retract, 1783
retractIfCan, 1783
sample, 1783
setelt, 1783
sign, 1783
size, 1783
size?, 1783
subtractIfCan, 1783
sup, 1783
swap, 1783
unitVector, 1783
zero?, 1783
ODPOL, 1817
-?, 1818
?<?, 1818
?<=?, 1818
?>?, 1818
?>=?, 1818

?**?, 1818
?*?, 1818
?+?, 1818
?-?, 1818
?/?, 1818
?=?, 1818
?^?, 1818
?~=?, 1818
0, 1818
1, 1818
associates?, 1818
binomThmExpt, 1818
characteristic, 1818
charthRoot, 1818
coefficient, 1818
coefficients, 1818
coerce, 1818
conditionP, 1818
content, 1818
D, 1818
degree, 1818
differentialVariables, 1818
differentiate, 1818
discriminant, 1818
eval, 1818
exquo, 1818
factor, 1818
factorPolynomial, 1818
factorSquareFreePolynomial, 1818
gcd, 1818
gcdPolynomial, 1818
ground, 1818
ground?, 1818
hash, 1818
initial, 1818
isExpt, 1818
isobaric?, 1818
isPlus, 1818
isTimes, 1818
latex, 1818
lcm, 1818
leader, 1818
leadingCoefficient, 1818
leadingMonomial, 1818
mainVariable, 1818
map, 1818
mapExponents, 1818
max, 1818
min, 1818
minimumDegree, 1818
monicDivide, 1818
monomial, 1818
monomial?, 1818
monomials, 1818
multivariate, 1818
numberOfMonomials, 1818
one?, 1818
order, 1818
patternMatch, 1818
pomopo, 1818
prime?, 1818
primitiveMonomials, 1818
primitivePart, 1818
recip, 1818
reducedSystem, 1818
reductum, 1818
resultant, 1818
retract, 1818
retractIfCan, 1818
sample, 1818
separant, 1818
solveLinearPolynomialEquation, 1818
squareFree, 1818
squareFreePart, 1818
squareFreePolynomial, 1818
subtractIfCan, 1818
totalDegree, 1818
unit?, 1818
unitCanonical, 1818
unitNormal, 1818
univariate, 1818
variables, 1818
weight, 1818
weights, 1818
zero?, 1818
ODR, 1824
-?, 1825
?**?, 1825
?*?, 1825
?+?, 1825
?-?, 1825
?/?, 1825

?=?, 1825
?^?, 1825
?~=?, 1825
?quo?, 1825
?rem?, 1825
0, 1825
1, 1825
associates?, 1825
characteristic, 1825
coerce, 1825
D, 1825
differentiate, 1825
divide, 1825
euclideanSize, 1825
expressIdealMember, 1825
exquo, 1825
extendedEuclidean, 1825
factor, 1825
gcd, 1825
gcdPolynomial, 1825
hash, 1825
inv, 1825
latex, 1825
lcm, 1825
multiEuclidean, 1825
one?, 1825
prime?, 1825
principalIdeal, 1825
recip, 1825
sample, 1825
sizeLess?, 1825
squareFree, 1825
squareFreePart, 1825
subtractIfCan, 1825
unit?, 1825
unitCanonical, 1825
unitNormal, 1825
zero?, 1825
ODVAR, 1821
?<?, 1821
?<=?, 1821
?>?, 1821
?>=?, 1821
?=?, 1821
?~=?, 1821
coerce, 1821
differentiate, 1821
hash, 1821
latex, 1821
makeVariable, 1821
max, 1821
min, 1821
order, 1821
retract, 1821
retractIfCan, 1821
variable, 1821
weight, 1821
OFMONOID, 1795
?<?, 1795
?<=?, 1795
?>?, 1795
?>=?, 1795
?**?, 1795
?*?, 1795
?=?, 1795
?^?, 1795
?~=?, 1795
?div?, 1795
1, 1795
coerce, 1795
factors, 1795
first, 1795
hash, 1795
hclf, 1795
hcrf, 1795
latex, 1795
length, 1795
lexico, 1795
lquo, 1795
max, 1795
min, 1795
mirror, 1795
nthExpon, 1795
nthFactor, 1795
one?, 1795
overlap, 1795
recip, 1795
rest, 1795
retract, 1795
retractIfCan, 1795
rquo, 1795
sample, 1795

size, 1795
varList, 1795
OMbindTCP
OMCONN, 1747
OMclose
OMDEV, 1750
OMcloseConn
OMCONN, 1747
OMCONN, 1747
OMbindTCP, 1747
OMcloseConn, 1747
OMconnectTCP, 1747
OMconnInDevice, 1747
OMconnOutDevice, 1747
OMmakeConn, 1747
OMconnectTCP
OMCONN, 1747
OMconnInDevice
OMCONN, 1747
OMconnOutDevice
OMCONN, 1747
OMDEV, 1750
OMclose, 1750
OMgetApp, 1750
OMgetAtp, 1750
OMgetAttr, 1750
OMgetBind, 1750
OMgetBVar, 1750
OMgetEndApp, 1750
OMgetEndAtp, 1750
OMgetEndAttr, 1750
OMgetEndBind, 1750
OMgetEndBVar, 1750
OMgetEndError, 1750
OMgetEndObject, 1750
OMgetError, 1750
OMgetFloat, 1750
OMgetInteger, 1750
OMgetObject, 1750
OMgetString, 1750
OMgetSymbol, 1750
OMgetType, 1750
OMgetVariable, 1750
OMopenFile, 1750
OMopenString, 1750
OMputApp, 1750
OMputAtp, 1750
OMputAttr, 1750
OMputBind, 1750
OMputBVar, 1750
OMputEndApp, 1750
OMputEndAtp, 1750
OMputEndAttr, 1750
OMputEndBind, 1750
OMputEndBVar, 1750
OMputEndError, 1750
OMputEndObject, 1750
OMputError, 1750
OMputFloat, 1750
OMputInteger, 1750
OMputObject, 1750
OMputString, 1750
OMputSymbol, 1750
OMputVariable, 1750
OMsetEncoding, 1750
OMENC, 1755
?=?, 1755
?~=?, 1755
coerce, 1755
hash, 1755
latex, 1755
OMencodingBinary, 1755
OMencodingSGML, 1755
OMencodingUnknown, 1755
OMencodingXML, 1755
OMencodingBinary
OMENC, 1755
OMencodingSGML
OMENC, 1755
OMencodingUnknown
OMENC, 1755
OMencodingXML
OMENC, 1755
OMERR, 1758
?=?, 1758
? =?, 1758
coerce, 1758
errorInfo, 1758
errorKind, 1758
hash, 1758
latex, 1758
omError, 1758

OMERRK, 1761
?=?, 1761
?~=?, 1761
coerce, 1761
hash, 1761
latex, 1761
OMParseError?, 1761
OMReadError?, 1761
OMUnknownCD?, 1761
OMUnknownSymbol?, 1761
omError
OMERR, 1758
OMgetApp
OMDEV, 1750
OMgetAtp
OMDEV, 1750
OMgetAttr
OMDEV, 1750
OMgetBind
OMDEV, 1750
OMgetBVar
OMDEV, 1750
OMgetEndApp
OMDEV, 1750
OMgetEndAtp
OMDEV, 1750
OMgetEndAttr
OMDEV, 1750
OMgetEndBind
OMDEV, 1750
OMgetEndBVar
OMDEV, 1750
OMgetEndError
OMDEV, 1750
OMgetEndObject
OMDEV, 1750
OMgetError
OMDEV, 1750
OMgetFloat
OMDEV, 1750
OMgetInteger
OMDEV, 1750
OMgetObject
OMDEV, 1750
OMgetString
OMDEV, 1750
OMgetSymbol
OMDEV, 1750
OMgetType
OMDEV, 1750
OMgetVariable
OMDEV, 1750
OMLO, 1773
-?, 1773
?**?, 1773
?*?, 1773
?+?, 1773
?-?, 1773
?=?, 1773
?^?, 1773
?~=?, 1773
0, 1773
1, 1773
characteristic, 1773
coefficient, 1773
coerce, 1773
D, 1773
degree, 1773
differentiate, 1773
hash, 1773
latex, 1773
leadingCoefficient, 1773
minimumDegree, 1773
monomial, 1773
one?, 1773
op, 1773
po, 1773
recip, 1773
reductum, 1773
sample, 1773
subtractIfCan, 1773
zero?, 1773
OMmakeConn
OMCONN, 1747
OMopenFile
OMDEV, 1750
OMopenString
OMDEV, 1750
OMParseError?
OMERRK, 1761
OMputApp
OMDEV, 1750

OMputAtp
OMDEV, 1750
OMputAttr
OMDEV, 1750
OMputBind
OMDEV, 1750
OMputBVar
OMDEV, 1750
OMputEndApp
OMDEV, 1750
OMputEndAtp
OMDEV, 1750
OMputEndAttr
OMDEV, 1750
OMputEndBind
OMDEV, 1750
OMputEndBVar
OMDEV, 1750
OMputEndError
OMDEV, 1750
OMputEndObject
OMDEV, 1750
OMputError
OMDEV, 1750
OMputFloat
OMDEV, 1750
OMputInteger
OMDEV, 1750
OMputObject
OMDEV, 1750
OMputString
OMDEV, 1750
OMputSymbol
OMDEV, 1750
OMputVariable
OMDEV, 1750
OMReadError?
OMERRK, 1761
OMsetEncoding
OMDEV, 1750
OMUnknownCD?
OMERRK, 1761
OMUnknownSymbol?
OMERRK, 1761
OMwrite
COMPLEX, 406
DFLOAT, 575
FLOAT, 879
FRAC, 956
INT, 1330
LIST, 1472
SINT, 2380
STRING, 2575
SYMBOL, 2608
one
GOPT, 1075
GOPT0, 1081
one?
ALGFF, 28
AN, 35
ANTISYM, 40
AUTOMOR, 231
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821

FFX, 816
FGROUP, 980
FLOAT, 879
FMONOID, 991
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IDEAL, 2047
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LA, 1488
LAUPOL, 1390
LEXP, 1403
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NOTTING, 1711
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
POLY, 2044
PR, 2058
PRODUCT, 2079
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757

ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
ONECOMP, 1743
-?, 1744
?<?, 1744
?<=?, 1744
?>?, 1744
?>=?, 1744
?**?, 1744
?*?, 1744
?+?, 1744
?-?, 1744
?=?, 1744
?^?, 1744
?~=?, 1744
0, 1744
1, 1744
abs, 1744
characteristic, 1744
coerce, 1744
finite?, 1744
hash, 1744
infinite?, 1744
infinity, 1744
latex, 1744
max, 1744
min, 1744
negative?, 1744
one?, 1744
positive?, 1744
rational, 1744
rational?, 1744
rationalIfCan, 1744
recip, 1744
retract, 1744
retractIfCan, 1744
sample, 1744
sign, 1744
subtractIfCan, 1744
zero?, 1744
OneDimensionalArray, 1740
oneDimensionalArray
ARRAY1, 1740
OnePointCompletion, 1743
OP, 1770
op
OMLO, 1773
open
BINFILE, 280
FILE, 772
FTEM, 938
KAFILE, 1382
TEXTFILE, 2661
open?
TUBE, 2718
OpenMathConnection, 1747
OpenMathDevice, 1750
OpenMathEncoding, 1755
OpenMathError, 1758
OpenMathErrorKind, 1761
operation
FC, 902
Operator, 1770
operator
AN, 35
BOP, 258
EXPR, 694
FEXPR, 917
IAN, 1245
KERNEL, 1372
MYEXPR, 1656
operators
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
opeval
MODOP, 1615, 1771

OppositeMonogenicLinearOperator, 1773
option
    DROPT, 596
    GOPT, 1075
option?
    DROPT, 596
optional?
    PATTERN, 1894
options
    VIEW2d, 2739
    VIEW3D, 2679
optpair
    PATTERN, 1894
OPTPROB, 1719
    ?=?, 1719
    ?~=?, 1719
    coerce, 1719
    hash, 1719
    latex, 1719
    retract, 1719
OR
    SWITCH, 2597
Or
    IBITS, 1169
    SINT, 2380
orbit
    AFFPLPS, 7
    AFFSP, 9
    PERM, 1916
    PERMGRP, 1926
    PROJPL, 2083
    PROJPLPS, 2085
    PROJSP, 2088
orbits
    PERMGRP, 1926
ord
    CHAR, 359
ORDCOMP, 1776
    -?, 1777
    ?<?, 1777
    ?<=?, 1777
    ?>?, 1777
    ?>=?, 1777
    ?**?, 1777
    ?*?, 1777
    ?+?, 1777
    ?-?, 1777
    ?=?, 1777
    ?^?, 1777
    ?~=?, 1777
    0, 1777
    1, 1777
    abs, 1777
    characteristic, 1777
    coerce, 1777
    finite?, 1777
    hash, 1777
    infinite?, 1777
    latex, 1777
    max, 1777
    min, 1777
    minusInfinity, 1777
    negative?, 1777
    one?, 1777
    plusInfinity, 1777
    positive?, 1777
    rational, 1777
    rational?, 1777
    rationalIfCan, 1777
    recip, 1777
    retract, 1777
    retractIfCan, 1777
    sample, 1777
    sign, 1777
    subtractIfCan, 1777
    whatInfinity, 1777
    zero?, 1777
order
    ALGFF, 28
    BPADIC, 242
    COMPLEX, 406
    DFLOAT, 575
    DSMP, 529
    EXPUPXS, 710
    FF, 790
    FFCG, 795
    FFCGP, 805
    FFCGX, 800
    FFNB, 830
    FFNBP, 842
    FFNBX, 836
    FFP, 821

FFX, 816
FLOAT, 879
GSERIES, 1061
IFF, 1252
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MODMON, 1600
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODPOL, 1818
ODVAR, 1821
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PERM, 1916
PERMGRP, 1926
PF, 2071
RADFF, 2160
SAE, 2368
SDPOL, 2352
SDVAR, 2358
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
OrderedCompletion, 1776
OrderedDirectProduct, 1783
OrderedFreeMonoid, 1795
OrderedVariableList, 1803
orderIfNegative
NSDPS, 1670
OrderlyDifferentialPolynomial, 1817
OrderlyDifferentialVariable, 1821
OrdinaryDifferentialRing, 1824
OrdinaryWeightedPolynomials, 1827
OrdSetInts, 1830
ORESUP, 2459
-?, 2460
?**?, 2460
?*?, 2460
?+?, 2460
?-?, 2460
?=?, 2460
?^?, 2460
?~=?, 2460
0, 2460
1, 2460
apply, 2460
characteristic, 2460
coefficient, 2460
coefficients, 2460
coerce, 2460
content, 2460
degree, 2460
exquo, 2460
hash, 2460
latex, 2460
leadingCoefficient, 2460
leftDivide, 2460
leftExactQuotient, 2460
leftExtendedGcd, 2460
leftGcd, 2460
leftLcm, 2460
leftQuotient, 2460
leftRemainder, 2460
minimumDegree, 2460
monicLeftDivide, 2460
monicRightDivide, 2460
monomial, 2460
one?, 2460
outputForm, 2460
primitivePart, 2460
recip, 2460
reductum, 2460
retract, 2460

retractIfCan, 2460
rightDivide, 2460
rightExactQuotient, 2460
rightExtendedGcd, 2460
rightGcd, 2460
rightLcm, 2460
rightQuotient, 2460
rightRemainder, 2460
sample, 2460
subtractIfCan, 2460
zero?, 2460
OREUP, 2839
-?, 2840
?**?, 2840
?*?, 2840
?+?, 2840
?-?, 2840
?=?, 2840
?^?, 2840
?~=?, 2840
0, 2840
1, 2840
apply, 2840
characteristic, 2840
coefficient, 2840
coefficients, 2840
coerce, 2840
content, 2840
degree, 2840
exquo, 2840
hash, 2840
latex, 2840
leadingCoefficient, 2840
leftDivide, 2840
leftExactQuotient, 2840
leftExtendedGcd, 2840
leftGcd, 2840
leftLcm, 2840
leftQuotient, 2840
leftRemainder, 2840
minimumDegree, 2840
monicLeftDivide, 2840
monicRightDivide, 2840
monomial, 2840
one?, 2840
primitivePart, 2840
recip, 2840
reductum, 2840
retract, 2840
retractIfCan, 2840
rightDivide, 2840
rightExactQuotient, 2840
rightExtendedGcd, 2840
rightGcd, 2840
rightLcm, 2840
rightQuotient, 2840
rightRemainder, 2840
sample, 2840
subtractIfCan, 2840
zero?, 2840
origin
AFFPLPS, 7
AFFSP, 9
OSI, 1830
?<?, 1830
?<=?, 1830
?>?, 1830
?>=?, 1830
?=?, 1830
?~=?, 1830
coerce, 1830
hash, 1830
latex, 1830
max, 1830
min, 1830
value, 1830
outerProduct
CDFVEC, 419
DFVEC, 593
IVECTOR, 1229
POINT, 2026
VECTOR, 2878
OUTFORM, 1833
-?, 1834
?<?, 1834
?<=?, 1834
?>?, 1834
?>=?, 1834
?**?, 1834
?*?, 1834
?+?, 1834
?-?, 1834

?..?, 1834
?.?, 1834
?/?, 1834
?=?, 1834
?SEGMENT, 1834
?^=?, 1834
?~=?, 1834
?and?, 1834
?div?, 1834
?or?, 1834
?quo?, 1834
?rem?, 1834
assign, 1834
binomial, 1834
blankSeparate, 1834
box, 1834
brace, 1834
bracket, 1834
center, 1834
coerce, 1834
commaSeparate, 1834
differentiate, 1834
dot, 1834
empty, 1834
exquo, 1834
hash, 1834
hconcat, 1834
height, 1834
hspace, 1834
infix, 1834
infix?, 1834
int, 1834
label, 1834
latex, 1834
left, 1834
matrix, 1834
message, 1834
messagePrint, 1834
not?, 1834
outputForm, 1834
over, 1834
overbar, 1834
overlabel, 1834
paren, 1834
pile, 1834
postfix, 1834
prefix, 1834
presub, 1834
presuper, 1834
prime, 1834
print, 1834
prod, 1834
quote, 1834
rarrow, 1834
right, 1834
root, 1834
rspace, 1834
scripts, 1834
semicolonSeparate, 1834
slash, 1834
string, 1834
sub, 1834
subHeight, 1834
sum, 1834
super, 1834
superHeight, 1834
supersub, 1834
vconcat, 1834
vspace, 1834
width, 1834
zag, 1834
outlineRender
VIEW3D, 2679
output
STREAM, 2550
outputAsFortran
ASP1, 71
ASP10, 75
ASP12, 79
ASP19, 82
ASP20, 90, 95
ASP27, 99
ASP28, 102
ASP29, 108
ASP30, 111
ASP31, 115
ASP33, 120
ASP34, 123
ASP35, 127
ASP4, 132
ASP41, 136
ASP42, 142

ASP49, 149
ASP50, 154
ASP55, 159
ASP6, 164
ASP7, 169
ASP73, 174
ASP74, 178
ASP77, 184
ASP78, 189
ASP8, 193
ASP80, 197
ASP9, 202
FORTRAN, 926
SFORT, 2374
outputFixed
FLOAT, 879
outputFloating
FLOAT, 879
OutputForm, 1833
outputForm
LMOPS, 1477
ORESUP, 2460
OUTFORM, 1834
SUP, 2435
OutputForm , 1540, 1543, 1545
outputGeneral
FLOAT, 879
outputSpacing
FLOAT, 879
OVAR, 1803
?<?, 1803
?<=?, 1803
?>?, 1803
?>=?, 1803
?=?, 1803
?~=?, 1803
coerce, 1803
convert, 1803
hash, 1803
index, 1803
latex, 1803
lookup, 1803
max, 1803
min, 1803
random, 1803
size, 1803
variable, 1803
over
OUTFORM, 1834
overbar
OUTFORM, 1834
overlabel
OUTFORM, 1834
overlap
FMONOID, 991
OFMONOID, 1795
OWP, 1827
-?, 1828
?**?, 1828
?*?, 1828
?+?, 1828
?-?, 1828
?/?, 1828
?=?, 1828
?^?, 1828
?~=?, 1828
0, 1828
1, 1828
changeWeightLevel, 1828
characteristic, 1828
coerce, 1828
hash, 1828
latex, 1828
one?, 1828
recip, 1828
sample, 1828
subtractIfCan, 1828
zero?, 1828

PACEXT, 2092
PACOFF, 2101
-?, 2102
?**?, 2102
?*?, 2102
?+?, 2102
?-?, 2102
?/?, 2102
?=?, 2102
?^?, 2102
?~=?, 2102
?quo?, 2102
?rem?, 2102

0, 2102
1, 2102
algebraic?, 2102
associates?, 2102
characteristic, 2102
charthRoot, 2102
coerce, 2102
conditionP, 2102
conjugate, 2102
createPrimitiveElement, 2102
D, 2102
definingPolynomial, 2102
degree, 2102
differentiate, 2102
dimension, 2102
discreteLog, 2102
distinguishedRootsOf, 2102
divide, 2102
euclideanSize, 2102
expressIdealMember, 2102
exquo, 2102
extDegree, 2102
extendedEuclidean, 2102
extensionDegree, 2102
factor, 2102
factorsOfCyclicGroupSize, 2102
Frobenius, 2102
fullOutput, 2102
gcd, 2102
gcdPolynomial, 2102
ground?, 2102
hash, 2102
index, 2102
inGroundField?, 2102
init, 2102
inv, 2102
latex, 2102
lcm, 2102
lift, 2102
lookup, 2102
maxTower, 2102
multiEuclidean, 2102
newElement, 2102
nextItem, 2102
one?, 2102
order, 2102
previousTower, 2102
prime?, 2102
primeFrobenius, 2102
primitive?, 2102
primitiveElement, 2102
principalIdeal, 2102
random, 2102
recip, 2102
reduce, 2102
representationType, 2102
retract, 2102
retractIfCan, 2102
sample, 2102
setTower, 2102
size, 2102
sizeLess?, 2102
squareFree, 2102
squareFreePart, 2102
subtractIfCan, 2102
tableForDiscreteLogarithm, 2102
transcendenceDegree, 2102
transcendent?, 2102
unit?, 2102
unitCanonical, 2102
unitNormal, 2102
vectorise, 2102
zero?, 2102
PACRAT, 2112
-?, 2112
?**?, 2112
?*?, 2112
?+?, 2112
?-?, 2112
?/?, 2112
?=?, 2112
?^?, 2112
?~=?, 2112
?quo?, 2112
?rem?, 2112
0, 2112
1, 2112
algebraic?, 2112
associates?, 2112
characteristic, 2112
charthRoot, 2112
coerce, 2112

conjugate, 2112
definingPolynomial, 2112
degree, 2112
dimension, 2112
discreteLog, 2112
distinguishedRootsOf, 2112
divide, 2112
euclideanSize, 2112
expressIdealMember, 2112
exquo, 2112
extDegree, 2112
extendedEuclidean, 2112
extensionDegree, 2112
factor, 2112
Frobenius, 2112
fullOutput, 2112
gcd, 2112
gcdPolynomial, 2112
ground?, 2112
hash, 2112
inGroundField?, 2112
inv, 2112
latex, 2112
lcm, 2112
lift, 2112
maxTower, 2112
multiEuclidean, 2112
newElement, 2112
one?, 2112
order, 2112
previousTower, 2112
prime?, 2112
primeFrobenius, 2112
principalIdeal, 2112
recip, 2112
reduce, 2112
retract, 2112
retractIfCan, 2112
sample, 2112
setTower, 2112
sizeLess?, 2112
squareFree, 2112
squareFreePart, 2112
subtractIfCan, 2112
transcendenceDegree, 2112
transcendent?, 2112
unit?, 2112
unitCanonical, 2112
unitNormal, 2112
vectorise, 2112
zero?, 2112
PADIC, 1847
-?, 1847
?**?, 1847
?*?, 1847
?+?, 1847
?-?, 1847
?=?, 1847
?^?, 1847
?~=?, 1847
?quo?, 1847
?rem?, 1847
0, 1847
1, 1847
approximate, 1847
associates?, 1847
characteristic, 1847
coerce, 1847
complete, 1847
digits, 1847
divide, 1847
euclideanSize, 1847
expressIdealMember, 1847
exquo, 1847
extend, 1847
extendedEuclidean, 1847
gcd, 1847
gcdPolynomial, 1847
hash, 1847
latex, 1847
lcm, 1847
moduloP, 1847
modulus, 1847
multiEuclidean, 1847
one?, 1847
order, 1847
principalIdeal, 1847
quotientByP, 1847
recip, 1847
root, 1847
sample, 1847
sizeLess?, 1847

sqrt, 1847
subtractIfCan, 1847
unit?, 1847
unitCanonical, 1847
unitNormal, 1847
zero?, 1847
padicallyExpand
PFR, 1880
padicFraction
PFR, 1880
PAdicInteger, 1847
PADICRAT, 1851
-?, 1852
?<?, 1852
?<=?, 1852
?>?, 1852
?>=?, 1852
?**?, 1852
?*?, 1852
?+?, 1852
?-?, 1852
?.?, 1852
?/?, 1852
?=?, 1852
?^?, 1852
?~=?, 1852
?quo?, 1852
?rem?, 1852
0, 1852
1, 1852
abs, 1852
approximate, 1852
associates?, 1852
ceiling, 1852
characteristic, 1852
charthRoot, 1852
coerce, 1852
conditionP, 1852
continuedFraction, 1852
convert, 1852
D, 1852
denom, 1852
denominator, 1852
differentiate, 1852
divide, 1852
euclideanSize, 1852
eval, 1852
expressIdealMember, 1852
exquo, 1852
extendedEuclidean, 1852
factor, 1852
factorPolynomial, 1852
factorSquareFreePolynomial, 1852
floor, 1852
fractionPart, 1852
gcd, 1852
gcdPolynomial, 1852
hash, 1852
init, 1852
inv, 1852
latex, 1852
lcm, 1852
map, 1852
max, 1852
min, 1852
multiEuclidean, 1852
negative?, 1852
nextItem, 1852
numer, 1852
numerator, 1852
one?, 1852
patternMatch, 1852
positive?, 1852
prime?, 1852
principalIdeal, 1852
random, 1852
recip, 1852
reducedSystem, 1852
removeZeroes, 1852
retract, 1852
retractIfCan, 1852
sample, 1852
sign, 1852
sizeLess?, 1852
solveLinearPolynomialEquation, 1852
squareFree, 1852
squareFreePart, 1852
squareFreePolynomial, 1852
subtractIfCan, 1852
unit?, 1852
unitCanonical, 1852
unitNormal, 1852

wholePart, 1852
zero?, 1852
PAdicRational, 1851
PAdicRationalConstructor, 1856
PADICRC, 1856
-?, 1857
?<?, 1857
?<=?, 1857
?>?, 1857
?>=?, 1857
?**?, 1857
?*?, 1857
?+?, 1857
?-?, 1857
?.?, 1857
?/?, 1857
?=?, 1857
?^?, 1857
?~=?, 1857
?quo?, 1857
?rem?, 1857
0, 1857
1, 1857
abs, 1857
approximate, 1857
associates?, 1857
ceiling, 1857
characteristic, 1857
charthRoot, 1857
coerce, 1857
conditionP, 1857
continuedFraction, 1857
convert, 1857
D, 1857
denom, 1857
denominator, 1857
differentiate, 1857
divide, 1857
euclideanSize, 1857
eval, 1857
expressIdealMember, 1857
exquo, 1857
extendedEuclidean, 1857
factor, 1857
factorPolynomial, 1857
factorSquareFreePolynomial, 1857
floor, 1857
fractionPart, 1857
gcd, 1857
gcdPolynomial, 1857
hash, 1857
init, 1857
inv, 1857
latex, 1857
lcm, 1857
map, 1857
max, 1857
min, 1857
multiEuclidean, 1857
negative?, 1857
nextItem, 1857
numer, 1857
numerator, 1857
one?, 1857
patternMatch, 1857
positive?, 1857
prime?, 1857
principalIdeal, 1857
random, 1857
recip, 1857
reducedSystem, 1857
removeZeroes, 1857
retract, 1857
retractIfCan, 1857
sample, 1857
sign, 1857
sizeLess?, 1857
solveLinearPolynomialEquation, 1857
squareFree, 1857
squareFreePart, 1857
squareFreePolynomial, 1857
subtractIfCan, 1857
unit?, 1857
unitCanonical, 1857
unitNormal, 1857
wholePart, 1857
zero?, 1857
pair?
INFORM, 1311
SEX, 2360
SEXOF, 2363
PALETTE, 1862

?=?, 1862
?~=?, 1862
bright, 1862
coerce, 1862
dark, 1862
dim, 1862
hash, 1862
hue, 1862
latex, 1862
light, 1862
pastel, 1862
shade, 1862
Palette, 1862
parametersOf
SYMTAB, 2616
parametric?
PLOT, 1995
ParametricPlaneCurve, 1865
ParametricSpaceCurve, 1867
ParametricSurface, 1870
paren
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
OUTFORM, 1834
parent
SUBSPACE, 2582
PARPCURV, 1865
coordinate, 1865
curve, 1865
PARSCURV, 1867
coordinate, 1868
curve, 1868
parse
INFORM, 1311
PARSURF, 1870
coordinate, 1870
surface, 1870
partialDenominators
CONTFRAC, 432
PartialFraction, 1880
partialFraction
PFR, 1880
partialNumerators
CONTFRAC, 432
partialQuotients
CONTFRAC, 432
Partition, 1889
partition
PRTITION, 1889
parts
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229

KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
pastel
PALETTE, 1862
PATLRES, 1903
?=?, 1904
?~=?, 1904
atoms, 1904
coerce, 1904
failed, 1904
failed?, 1904
hash, 1904
latex, 1904
lists, 1904
makeResult, 1904
new, 1904
PATRES, 1906
?=?, 1906
?~=?, 1906
addMatch, 1906
addMatchRestricted, 1906
coerce, 1906
construct, 1906
destruct, 1906
failed, 1906
failed?, 1906
getMatch, 1906
hash, 1906
insertMatch, 1906
latex, 1906
new, 1906
satisfy?, 1906
union, 1906
PATTERN, 1894
?**?, 1894
?*?, 1894
?+?, 1894
?/?, 1894
?=?, 1894
?~=?, 1894
0, 1894
1, 1894
addBadValue, 1894
coerce, 1894
constant?, 1894
convert, 1894
copy, 1894
depth, 1894
elt, 1894
generic?, 1894
getBadValues, 1894
hash, 1894
hasPredicate?, 1894
hasTopPredicate?, 1894
inR?, 1894
isExpt, 1894
isList, 1894
isOp, 1894
isPlus, 1894
isPower, 1894

isQuotient, 1894
isTimes, 1894
latex, 1894
multiple?, 1894
optional?, 1894
optpair, 1894
patternVariable, 1894
predicates, 1894
quoted?, 1894
resetBadValues, 1894
retract, 1894
retractIfCan, 1894
setPredicates, 1894
setTopPredicate, 1894
symbol?, 1894
topPredicate, 1894
variables, 1894
withPredicates, 1894
Pattern, 1894
pattern
RULE, 2271
patternMatch
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694
FLOAT, 879
FRAC, 956
GDMP, 1022
HDMP, 1150
HEXADEC, 1113
INT, 1330
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
POLY, 2044
RADIX, 2172
ROMAN, 2293
SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SYMBOL, 2608
ULS, 2763
ULSCONS, 2771
UP, 2795
PatternMatchListResult, 1903
PatternMatchResult, 1906
patternVariable
PATTERN, 1894
PBWLB, 2020
?<?, 2020
?<=?, 2020
?>?, 2020
?>=?, 2020
?=?, 2020
?~=?, 2020
1, 2020
coerce, 2020
first, 2020
hash, 2020
latex, 2020
length, 2020
listOfTerms, 2020
max, 2020
min, 2020
rest, 2020
retract, 2020
retractable?, 2020
retractIfCan, 2020
varList, 2020
pdct
PRTITION, 1889
PDEPROB, 1722
?=?, 1722
?~=?, 1722

coerce, 1722
hash, 1722
latex, 1722
retract, 1722
PDESolve
D03EEFA, 652
D03FAFA, 655
PendantTree, 1911
PENDTREE, 1911
?.left, 1911
?.right, 1911
?.value, 1911
?=?, 1911
?~=?, 1911
#?, 1911
any?, 1911
child?, 1911
children, 1911
coerce, 1911
copy, 1911
count, 1911
cyclic?, 1911
distance, 1911
empty, 1911
empty?, 1911
eq?, 1911
eval, 1911
every?, 1911
hash, 1911
latex, 1911
leaf?, 1911
leaves, 1911
left, 1911
less?, 1911
map, 1911
member?, 1911
members, 1911
more?, 1911
node?, 1911
nodes, 1911
parts, 1911
ptree, 1911
right, 1911
sample, 1911
setchildren, 1911
setelt, 1911
setleft, 1911
setright, 1911
setvalue, 1911
size?, 1911
value, 1911
PERM, 1915
?<?, 1916
?<=?, 1916
?>?, 1916
?>=?, 1916
?**?, 1916
?*?, 1916
?.?, 1916
?/?, 1916
?=?, 1916
?^?, 1916
?~=?, 1916
1, 1916
coerce, 1916
coerceImages, 1916
coerceListOfPairs, 1916
coercePreimagesImages, 1916
commutator, 1916
conjugate, 1916
cycle, 1916
cyclePartition, 1916
cycles, 1916
degree, 1916
eval, 1916
even?, 1916
fixedPoints, 1916
hash, 1916
inv, 1916
latex, 1916
listRepresentation, 1916
max, 1916
min, 1916
movedPoints, 1916
numberOfCycles, 1916
odd?, 1916
one?, 1916
orbit, 1916
order, 1916
recip, 1916
sample, 1916
sign, 1916

sort, 1916
PERMGRP, 1926
?<?, 1926
?<=?, 1926
?.?, 1926
?=?, 1926
?~=?, 1926
base, 1926
coerce, 1926
degree, 1926
generators, 1926
hash, 1926
initializeGroupForWordProblem, 1926
latex, 1926
member?, 1926
movedPoints, 1926
orbit, 1926
orbits, 1926
order, 1926
permutationGroup, 1926
random, 1926
strongGenerators, 1926
wordInGenerators, 1926
wordInStrongGenerators, 1926
wordsForStrongGenerators, 1926
Permutation, 1915
permutation
EXPR, 694
INT, 1330
MINT, 1525
MYEXPR, 1656
ROMAN, 2293
SINT, 2380
PermutationGroup, 1926
permutationGroup
PERMGRP, 1926
perspective
VIEW3D, 2679
PF, 2070
-?, 2071
?**?, 2071
?*?, 2071
?+?, 2071
?-?, 2071
?/?, 2071
?=?, 2071
?^?, 2071
?~=?, 2071
?quo?, 2071
?rem?, 2071
0, 2071
1, 2071
algebraic?, 2071
associates?, 2071
basis, 2071
characteristic, 2071
charthRoot, 2071
coerce, 2071
conditionP, 2071
convert, 2071
coordinates, 2071
createNormalElement, 2071
createPrimitiveElement, 2071
D, 2071
definingPolynomial, 2071
degree, 2071
differentiate, 2071
dimension, 2071
discreteLog, 2071
divide, 2071
euclideanSize, 2071
expressIdealMember, 2071
exquo, 2071
extendedEuclidean, 2071
extensionDegree, 2071
factor, 2071
factorsOfCyclicGroupSize, 2071
Frobenius, 2071
gcd, 2071
gcdPolynomial, 2071
generator, 2071
hash, 2071
index, 2071
inGroundField?, 2071
init, 2071
inv, 2071
latex, 2071
lcm, 2071
linearAssociatedExp, 2071
linearAssociatedLog, 2071
linearAssociatedOrder, 2071
lookup, 2071

minimalPolynomial, 2071
multiEuclidean, 2071
nextItem, 2071
norm, 2071
normal?, 2071
normalElement, 2071
one?, 2071
order, 2071
prime?, 2071
primeFrobenius, 2071
primitive?, 2071
primitiveElement, 2071
principalIdeal, 2071
random, 2071
recip, 2071
representationType, 2071
represents, 2071
retract, 2071
retractIfCan, 2071
sample, 2071
size, 2071
sizeLess?, 2071
squareFree, 2071
squareFreePart, 2071
subtractIfCan, 2071
tableForDiscreteLogarithm, 2071
trace, 2071
transcendenceDegree, 2071
transcendent?, 2071
unit?, 2071
unitCanonical, 2071
unitNormal, 2071
zero?, 2071
pfaffian
CDFMAT, 413
DFMAT, 587
PFR, 1880
-?, 1880
?**?, 1880
?*?, 1880
?+?, 1880
?-?, 1880
?/?, 1880
?=?, 1880
?^?, 1880
?~=?, 1880
?quo?, 1880
?rem?, 1880
0, 1880
1, 1880
associates?, 1880
characteristic, 1880
coerce, 1880
compactFraction, 1880
divide, 1880
euclideanSize, 1880
expressIdealMember, 1880
exquo, 1880
extendedEuclidean, 1880
factor, 1880
firstDenom, 1880
firstNumer, 1880
gcd, 1880
gcdPolynomial, 1880
hash, 1880
inv, 1880
latex, 1880
lcm, 1880
multiEuclidean, 1880
nthFractionalTerm, 1880
numberOfFractionalTerms, 1880
one?, 1880
padicallyExpand, 1880
padicFraction, 1880
partialFraction, 1880
prime?, 1880
principalIdeal, 1880
recip, 1880
sample, 1880
sizeLess?, 1880
squareFree, 1880
squareFreePart, 1880
subtractIfCan, 1880
unit?, 1880
unitCanonical, 1880
unitNormal, 1880
wholePart, 1880
zero?, 1880
physicalLength
FARRAY, 856
IFARRAY, 1192
PI, 2066

?<?, 2066
?<=?, 2066
?>?, 2066
?>=?, 2066
?**?, 2066
?*?, 2066
?+?, 2066
?=?, 2066
?^?, 2066
?~=?, 2066
1, 2066
coerce, 2066
gcd, 2066
hash, 2066
latex, 2066
max, 2066
min, 2066
one?, 2066
recip, 2066
sample, 2066
Pi, 1943
pi
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
HACKPI, 1944
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
pile
OUTFORM, 1834
PLACES, 1984
-?, 1985
?*?, 1985
?+?, 1985
?-?, 1985
?.?, 1985
?=?, 1985
?~=?, 1985
coerce, 1985
create, 1985
degree, 1985
foundPlaces, 1985
hash, 1985
itsALeaf, 1985
latex, 1985
leaf?, 1985
localParam, 1985
reduce, 1985
setDegree, 1985
setFoundPlacesToEmpty, 1985
setParam, 1985
Places, 1984
PlacesOverPseudoAlgebraicClosureOfFiniteField, 1987
PLACESPS, 1987
-?, 1987
?*?, 1987
?+?, 1987
?-?, 1987
?.?, 1987
?=?, 1987
?~=?, 1987
coerce, 1987
create, 1987
degree, 1987
foundPlaces, 1987
hash, 1987
itsALeaf, 1987
latex, 1987
leaf?, 1987
localParam, 1987
reduce, 1987
setDegree, 1987
setFoundPlacesToEmpty, 1987
setParam, 1987

PlaneAlgebraicCurvePlot, 1958
PLCS, 1989
Plcs, 1989
plenaryPower
    ALGSC, 15
    FNLA, 997
    GCNAALG, 1035
    JORDAN, 209
    LIE, 214
    LSQM, 1424
PLOT, 1995
    adaptive?, 1995
    coerce, 1995
    debug, 1995
    listBranches, 1995
    maxPoints, 1995
    minPoints, 1995
    numFunEvals, 1995
    parametric?, 1995
    plot, 1995
    plotPolar, 1995
    pointPlot, 1995
    refine, 1995
    screenResolution, 1995
    setAdaptive, 1995
    setMaxPoints, 1995
    setMinPoints, 1995
    setScreenResolution, 1995
    tRange, 1995
    xRange, 1995
    yRange, 1995
    zoom, 1995
Plot, 1995
plot
    PLOT, 1995
    PLOT3D, 2008
PLOT3D, 2008
    adaptive3D?, 2008
    coerce, 2008
    debug3D, 2008
    listBranches, 2008
    maxPoints3D, 2008
    minPoints3D, 2008
    numFunEvals3D, 2008
    plot, 2008
    pointPlot, 2008
    refine, 2008
    screenResolution3D, 2008
    setAdaptive3D, 2008
    setMaxPoints3D, 2008
    setMinPoints3D, 2008
    setScreenResolution3D, 2008
    tRange, 2008
    tValues, 2008
    xRange, 2008
    yRange, 2008
    zoom, 2008
    zRange, 2008
Plot3D, 2008
plotPolar
    PLOT, 1995
plus
    LMOPS, 1477
    M3D, 2672
plusInfinity
    ORDCOMP, 1777
po
    OMLO, 1773
PoincareBirkhoffWittLyndonBasis, 2020
POINT, 2025
    -?, 2026
    ?<?, 2026
    ?<=?, 2026
    ?>?, 2026
    ?>=?, 2026
    ?*?, 2026
    ?+?, 2026
    ?-?, 2026
    ?.?, 2026
    ?=?, 2026
    ?~=?, 2026
    #?, 2026
    any?, 2026
    coerce, 2026
    concat, 2026
    construct, 2026
    convert, 2026
    copy, 2026
    copyInto, 2026
    count, 2026
    cross, 2026
    delete, 2026

dimension, 2026
dot, 2026
elt, 2026
empty, 2026
empty?, 2026
entries, 2026
entry?, 2026
eq?, 2026
eval, 2026
every?, 2026
extend, 2026
fill, 2026
find, 2026
first, 2026
hash, 2026
index?, 2026
indices, 2026
insert, 2026
latex, 2026
length, 2026
less?, 2026
magnitude, 2026
map, 2026
max, 2026
maxIndex, 2026
member?, 2026
members, 2026
merge, 2026
min, 2026
minIndex, 2026
more?, 2026
new, 2026
outerProduct, 2026
parts, 2026
point, 2026
position, 2026
qelt, 2026
qsetelt, 2026
reduce, 2026
remove, 2026
removeDuplicates, 2026
reverse, 2026
sample, 2026
select, 2026
setelt, 2026
size?, 2026
sort, 2026
sorted?, 2026
swap, 2026
zero, 2026
Point, 2025
point
GRIMAGE, 1065
POINT, 2026
SPACE3, 2701
point?
SPACE3, 2701
pointColor
DROPT, 596
pointData
SUBSPACE, 2582
pointLists
GRIMAGE, 1065
pointPlot
PLOT, 1995
PLOT3D, 2008
points
VIEW2d, 2739
pointV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
pointValue
AFFPLPS, 7
AFFSP, 9
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
polarCoordinates
COMPLEX, 406
MCMPLX, 1511
pole?
EXPUPXS, 710
GSERIES, 1061
ISUPS, 1279
ITAYLOR, 1306
NSDPS, 1670
SMTS, 2409
SULS, 2425
SUPXS, 2455
SUTS, 2464
TS, 2639

UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
POLY, 2043
-?, 2044
?<?, 2044
?<=?, 2044
?>?, 2044
?>=?, 2044
?**?, 2044
?*?, 2044
?+?, 2044
?-?, 2044
?/?, 2044
?=?, 2044
?^?, 2044
?~=?, 2044
0, 2044
1, 2044
associates?, 2044
binomThmExpt, 2044
characteristic, 2044
charthRoot, 2044
coefficient, 2044
coefficients, 2044
coerce, 2044
conditionP, 2044
content, 2044
convert, 2044
D, 2044
degree, 2044
differentiate, 2044
discriminant, 2044
eval, 2044
exquo, 2044
factor, 2044
factorPolynomial, 2044
factorSquareFreePolynomial, 2044
gcd, 2044
gcdPolynomial, 2044
ground, 2044
ground?, 2044
hash, 2044
integrate, 2044
isExpt, 2044
isPlus, 2044
isTimes, 2044
latex, 2044
lcm, 2044
leadingCoefficient, 2044
leadingMonomial, 2044
mainVariable, 2044
map, 2044
mapExponents, 2044
max, 2044
min, 2044
minimumDegree, 2044
monicDivide, 2044
monomial, 2044
monomial?, 2044
monomials, 2044
multivariate, 2044
numberOfMonomials, 2044
one?, 2044
patternMatch, 2044
pomopo, 2044
prime?, 2044
primitiveMonomials, 2044
primitivePart, 2044
recip, 2044
reducedSystem, 2044
reductum, 2044
resultant, 2044
retract, 2044
retractIfCan, 2044
sample, 2044
solveLinearPolynomialEquation, 2044
squareFree, 2044
squareFreePart, 2044
squareFreePolynomial, 2044
subtractIfCan, 2044
totalDegree, 2044
unit?, 2044
unitCanonical, 2044
unitNormal, 2044
univariate, 2044
variables, 2044
zero?, 2044

polygamma
DFLOAT, 575
EXPR, 694
polygon
SPACE3, 2701
polygon?
SPACE3, 2701
Polynomial, 2043
polynomial
SMTS, 2409
SUTS, 2464
TS, 2639
UFPS, 2757
UTS, 2844
UTSZ, 2854
PolynomialIdeals, 2047
PolynomialRing, 2058
polyPart
FPARFRAC, 1010
posExpnPart
NSDPS, 1670
position
ALIST, 221
ARRAY1, 1740
BINFILE, 280
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
KERNEL, 1372
LIST, 1472
MKCHSET, 1538
POINT, 2026
PRIMARR, 2075
STRING, 2575
U32VEC, 2869
VECTOR, 2878
positive?
BINARY, 277
BPADICRT, 247
DECIMAL, 453
DFLOAT, 575
DIRPROD, 534
DPMM, 540
DPMO, 545
EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HDP, 1143
HEXADEC, 1113
INT, 1330
INTRVL, 1352
LA, 1488
MFLOAT, 1516
MINT, 1525
ODP, 1783
ONECOMP, 1744
ORDCOMP, 1777
PADICRAT, 1852
PADICRC, 1857
RADIX, 2172
RECLOS, 2203
ROIRC, 2276
ROMAN, 2293
SHDP, 2476
SINT, 2380
SULS, 2425
ULS, 2763
ULSCONS, 2771
PositiveInteger, 2066
positiveRemainder
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
possiblyInfinite?
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
postfix
OUTFORM, 1834
pow

MODMON, 1600
powerAssociative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
powers
PRTITION, 1889
powmod
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
pquo
NSMP, 1681
PR, 2058
-?, 2058
?**?, 2058
?*?, 2058
?+?, 2058
?-?, 2058
?/?, 2058
?=?, 2058
?^?, 2058
?~=?, 2058
0, 2058
1, 2058
associates?, 2058
binomThmExpt, 2058
characteristic, 2058
charthRoot, 2058
coefficient, 2058
coefficients, 2058
coerce, 2058
content, 2058
degree, 2058
exquo, 2058
fmecg, 2058
ground, 2058
ground?, 2058
hash, 2058
latex, 2058
leadingCoefficient, 2058
leadingMonomial, 2058
map, 2058
mapExponents, 2058
minimumDegree, 2058
monomial, 2058
monomial?, 2058
numberOfMonomials, 2058
one?, 2058
pomopo, 2058
primitivePart, 2058
recip, 2058
reductum, 2058
retract, 2058
retractIfCan, 2058
sample, 2058
subtractIfCan, 2058
unit?, 2058
unitCanonical, 2058
unitNormal, 2058
zero?, 2058
precision
DFLOAT, 575
FLOAT, 879
MFLOAT, 1516
predicates
PATTERN, 1894
prefix
OUTFORM, 1834
prefix?
ISTRING, 1218
STRING, 2575
prefixRagits
RADIX, 2172
prem
NSMP, 1681
preprocess
REGSET, 2252
SREGSET, 2502
presub
OUTFORM, 1834
presuper
OUTFORM, 1834
previousTower
PACOFF, 2102
PACRAT, 2112
PRIMARR, 2075
?<?, 2075
?<=?, 2075

?>?, 2075
?>=?, 2075
?.?, 2075
?=?, 2075
?~=?, 2075
#?, 2075
any?, 2075
coerce, 2075
concat, 2075
construct, 2075
convert, 2075
copy, 2075
copyInto, 2075
count, 2075
delete, 2075
elt, 2075
empty, 2075
empty?, 2075
entries, 2075
entry?, 2075
eq?, 2075
eval, 2075
every?, 2075
fill, 2075
find, 2075
first, 2075
hash, 2075
index?, 2075
indices, 2075
insert, 2075
latex, 2075
less?, 2075
map, 2075
max, 2075
maxIndex, 2075
member?, 2075
members, 2075
merge, 2075
min, 2075
minIndex, 2075
more?, 2075
new, 2075
parts, 2075
position, 2075
qelt, 2075
qsetelt, 2075
reduce, 2075
remove, 2075
removeDuplicates, 2075
reverse, 2075
sample, 2075
select, 2075
setelt, 2075
size?, 2075
sort, 2075
sorted?, 2075
swap, 2075
prime
OUTFORM, 1834
prime?
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252

INT, 1330
IPF, 1271
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
primeFactor
FR, 756
PrimeField, 2070
primeFrobenius
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PACRAT, 2112
PF, 2071
RADFF, 2160
SAE, 2368
primitive?
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PF, 2071
RADFF, 2160
SAE, 2368
PrimitiveArray, 2075
primitiveElement
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836

FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PF, 2071
RADFF, 2160
SAE, 2368
primitiveMonomials
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
primitivePart
ALGFF, 28
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
LODO, 1437
LODO1, 1447
LODO2, 1459
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
RADFF, 2160
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
SYMPOLY, 2622
UP, 2795
UPXSSING, 2819
primPartElseUnitCanonical
NSMP, 1681
principal?
FDIV, 783
HELLFDIV, 1153
principalIdeal
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390

MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
print
OUTFORM, 1834
printCode
FC, 902
printHeader
SYMS, 2665
printInfo
NSDPS, 1670
printStatement
FC, 902
printTypes
SYMS, 2665
SYMTAB, 2616
processTemplate
FTEM, 938
prod
OUTFORM, 1834
PRODUCT, 2078
-?, 2079
?<?, 2079
?<=?, 2079
?>?, 2079
?>=?, 2079
?**?, 2079
?*?, 2079
?+?, 2079
?-?, 2079
?/?, 2079
?=?, 2079
?^?, 2079
?~=?, 2079
0, 2079
1, 2079
coerce, 2079
commutator, 2079
conjugate, 2079
hash, 2079
index, 2079
inv, 2079
latex, 2079
lookup, 2079
makeprod, 2079
max, 2079
min, 2079
one?, 2079
random, 2079
recip, 2079
sample, 2079
selectfirst, 2079
selectsecond, 2079
size, 2079
subtractIfCan, 2079
sup, 2079
zero?, 2079
Product, 2078
product
CARTEN, 342
EXPR, 694
MYEXPR, 1656
XPBWPOLYL, 2925

ProjectivePlane, 2083
ProjectivePlaneOverPseudoAlgebraicClosureOfFiniteField, 2085
projectivePoint
  PROJPL, 2083
  PROJPLPS, 2085
  PROJSP, 2088
ProjectiveSpace, 2087
PROJPL, 2083
  ?.?, 2083
  ?=?, 2083
  ?~=?, 2083
  coerce, 2083
  conjugate, 2083
  definingField, 2083
  degree, 2083
  hash, 2083
  homogenize, 2083
  lastNonNul, 2083
  lastNonNull, 2083
  latex, 2083
  list, 2083
  orbit, 2083
  pointValue, 2083
  projectivePoint, 2083
  rational?, 2083
  removeConjugate, 2083
  setelt, 2083
PROJPLPS, 2085
  ?.?, 2085
  ?=?, 2085
  ?~=?, 2085
  coerce, 2085
  conjugate, 2085
  definingField, 2085
  degree, 2085
  hash, 2085
  homogenize, 2085
  lastNonNul, 2085
  lastNonNull, 2085
  latex, 2085
  list, 2085
  orbit, 2085
  pointValue, 2085
  projectivePoint, 2085
  rational?, 2085
  removeConjugate, 2085
  setelt, 2085
PROJSP, 2087
  ?.?, 2088
  ?=?, 2088
  ?~=?, 2088
  coerce, 2088
  conjugate, 2088
  definingField, 2088
  degree, 2088
  hash, 2088
  homogenize, 2088
  lastNonNul, 2088
  lastNonNull, 2088
  latex, 2088
  list, 2088
  orbit, 2088
  pointValue, 2088
  projectivePoint, 2088
  rational?, 2088
  removeConjugate, 2088
  setelt, 2088
prologue
  FORMULA, 2312
  TEX, 2645
properties
  BOP, 258
property
  BOP, 258
PRTITION, 1889
  ?<?, 1889
  ?<=?, 1889
  ?>?, 1889
  ?>=?, 1889
  ?*?, 1889
  ?+?, 1889
  ?=?, 1889
  ?~=?, 1889
  0, 1889
  coerce, 1889
  conjugate, 1889
  convert, 1889
  hash, 1889
  latex, 1889
  max, 1889
  min, 1889

partition, 1889
pdct, 1889
powers, 1889
sample, 1889
subtractIfCan, 1889
zero?, 1889
PseudoAlgebraicClosureOfAlgExtOfRationalNumber, 2092
PseudoAlgebraicClosureOfFiniteField, 2101
PseudoAlgebraicClosureOfRationalNumber, 2112
pseudoDivide
MODMON, 1600
MYUP, 1663
NSMP, 1681
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
pseudoQuotient
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
pseudoRemainder
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
ptree
PENDTREE, 1911
puiseux
SUPXS, 2455
UPXS, 2801
UPXSCONS, 2809
purelyAlgebraic?
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
purelyAlgebraicLeadingMonomial?
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
purelyTranscendental?
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
putColorInfo
GRIMAGE, 1065
putGraph
VIEW2d, 2739

QALGSET, 2123
?=?, 2123
?~=?, 2123
coerce, 2123
definingEquations, 2123
definingInequation, 2123
empty, 2123
empty?, 2123
hash, 2123
idealSimplify, 2123
latex, 2123
quasiAlgebraicSet, 2123
setStatus, 2123
simplify, 2123
status, 2123
qelt
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
BITS, 299
CDFMAT, 413
CDFVEC, 419
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169

IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LSQM, 1424
MATRIX, 1591
NSDPS, 1670
ODP, 1783
POINT, 2026
PRIMARR, 2075
RESULT, 2267
RMATRIX, 2212
ROUTINE, 2298
SHDP, 2476
SQMATRIX, 2515
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
QEQUAT, 2135
coerce, 2135
equation, 2135
value, 2135
variable, 2135
QFORM, 2120
-?, 2120
?*?, 2120
?+?, 2120
?-?, 2120
?.?, 2120
?=?, 2120
?~=?, 2120
0, 2120
coerce, 2120
hash, 2120
latex, 2120
matrix, 2120
quadraticForm, 2120
sample, 2120
subtractIfCan, 2120
zero?, 2120
qinterval
INTRVL, 1352
qnew
CDFMAT, 413
CDFVEC, 419
DFMAT, 587
DFVEC, 593
QuadraticForm, 2120
quadraticForm
QFORM, 2120
QuasiAlgebraicSet, 2123
quasiAlgebraicSet
QALGSET, 2123
quasiComponent
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
quasiMonic?
NSMP, 1681
quasiRegular
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
quasiRegular?
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
QUAT, 2132
-?, 2133
?<?, 2133
?<=?, 2133
?>?, 2133
?>=?, 2133
?**?, 2133
?*?, 2133
?+?, 2133

?-?, 2133
?.?, 2133
?=?, 2133
?^?, 2133
?~=?, 2133
0, 2133
1, 2133
abs, 2133
characteristic, 2133
charthRoot, 2133
coerce, 2133
conjugate, 2133
convert, 2133
D, 2133
differentiate, 2133
eval, 2133
hash, 2133
imagI, 2133
imagJ, 2133
imagK, 2133
inv, 2133
latex, 2133
map, 2133
max, 2133
min, 2133
norm, 2133
one?, 2133
quatern, 2133
rational, 2133
rational?, 2133
rationalIfCan, 2133
real, 2133
recip, 2133
reducedSystem, 2133
retract, 2133
retractIfCan, 2133
sample, 2133
subtractIfCan, 2133
zero?, 2133
quatern
QUAT, 2133
Quaternion, 2132
QueryEquation, 2135
QUEUE, 2150
?=?, 2150
?~=?, 2150
#?, 2150
any?, 2150
back, 2150
bag, 2150
coerce, 2150
copy, 2150
count, 2150
dequeue, 2150
empty, 2150
empty?, 2150
enqueue, 2150
eq?, 2150
eval, 2150
every?, 2150
extract, 2150
front, 2150
hash, 2150
insert, 2150
inspect, 2150
latex, 2150
length, 2150
less?, 2150
map, 2150
member?, 2150
members, 2150
more?, 2150
parts, 2150
queue, 2150
rotate, 2150
sample, 2150
size?, 2150
Queue, 2150
queue
QUEUE, 2150
quoByVar
SUTS, 2464
UFPS, 2757
UTS, 2844
UTSZ, 2854
quote
CHAR, 359
OUTFORM, 1834
quoted?
PATTERN, 1894
quotedOperators
RULE, 2271

quotient
IDEAL, 2047
quotientByP
BPADIC, 242
IPADIC, 1262
PADIC, 1847
quotValuation
BLHN, 301
BLQT, 304

RADFF, 2159
-?, 2160
?**?, 2160
?*?, 2160
?+?, 2160
?-?, 2160
?/?, 2160
?=?, 2160
?^?, 2160
?~=?, 2160
?quo?, 2160
?rem?, 2160
0, 2160
1, 2160
absolutelyIrreducible?, 2160
algSplitSimple, 2160
associates?, 2160
basis, 2160
branchPoint?, 2160
branchPointAtInfinity?, 2160
characteristic, 2160
characteristicPolynomial, 2160
charthRoot, 2160
coerce, 2160
complementaryBasis, 2160
conditionP, 2160
convert, 2160
coordinates, 2160
createPrimitiveElement, 2160
D, 2160
definingPolynomial, 2160
derivationCoordinates, 2160
differentiate, 2160
discreteLog, 2160
discriminant, 2160
divide, 2160
elliptic, 2160
elt, 2160
euclideanSize, 2160
expressIdealMember, 2160
exquo, 2160
extendedEuclidean, 2160
factor, 2160
factorsOfCyclicGroupSize, 2160
gcd, 2160
gcdPolynomial, 2160
generator, 2160
genus, 2160
hash, 2160
hyperelliptic, 2160
index, 2160
init, 2160
integral?, 2160
integralAtInfinity?, 2160
integralBasis, 2160
integralBasisAtInfinity, 2160
integralCoordinates, 2160
integralDerivationMatrix, 2160
integralMatrix, 2160
integralMatrixAtInfinity, 2160
integralRepresents, 2160
inv, 2160
inverseIntegralMatrix, 2160
inverseIntegralMatrixAtInfinity, 2160
latex, 2160
lcm, 2160
lift, 2160
lookup, 2160
minimalPolynomial, 2160
multiEuclidean, 2160
nextItem, 2160
nonSingularModel, 2160
norm, 2160
normalizeAtInfinity, 2160
numberOfComponents, 2160
one?, 2160
order, 2160
prime?, 2160
primeFrobenius, 2160
primitive?, 2160
primitiveElement, 2160
primitivePart, 2160

principalIdeal, 2160
ramified?, 2160
ramifiedAtInfinity?, 2160
random, 2160
rank, 2160
rationalPoint?, 2160
rationalPoints, 2160
recip, 2160
reduce, 2160
reduceBasisAtInfinity, 2160
reducedSystem, 2160
regularRepresentation, 2160
representationType, 2160
represents, 2160
retract, 2160
retractIfCan, 2160
sample, 2160
singular?, 2160
singularAtInfinity?, 2160
size, 2160
sizeLess?, 2160
squareFree, 2160
squareFreePart, 2160
subtractIfCan, 2160
tableForDiscreteLogarithm, 2160
trace, 2160
traceMatrix, 2160
unit?, 2160
unitCanonical, 2160
unitNormal, 2160
yCoordinates, 2160
zero?, 2160
RadicalFunctionField, 2159
RADIX, 2171
-?, 2172
?<?, 2172
?<=?, 2172
?>?, 2172
?>=?, 2172
?**?, 2172
?*?, 2172
?+?, 2172
?-?, 2172
?.?, 2172
?/?, 2172
?=?, 2172
?^?, 2172
?~=?, 2172
?quo?, 2172
?rem?, 2172
0, 2172
1, 2172
abs, 2172
associates?, 2172
ceiling, 2172
characteristic, 2172
charthRoot, 2172
coerce, 2172
conditionP, 2172
convert, 2172
cycleRagits, 2172
D, 2172
denom, 2172
denominator, 2172
differentiate, 2172
divide, 2172
euclideanSize, 2172
eval, 2172
expressIdealMember, 2172
exquo, 2172
extendedEuclidean, 2172
factor, 2172
factorPolynomial, 2172
factorSquareFreePolynomial, 2172
floor, 2172
fractionPart, 2172
fractRadix, 2172
fractRagits, 2172
gcd, 2172
gcdPolynomial, 2172
hash, 2172
init, 2172
inv, 2172
latex, 2172
lcm, 2172
map, 2172
max, 2172
min, 2172
multiEuclidean, 2172
negative?, 2172
nextItem, 2172
numer, 2172

numerator, 2172
one?, 2172
patternMatch, 2172
positive?, 2172
prefixRagits, 2172
prime?, 2172
principalIdeal, 2172
random, 2172
recip, 2172
reducedSystem, 2172
retract, 2172
retractIfCan, 2172
sample, 2172
sign, 2172
sizeLess?, 2172
solveLinearPolynomialEquation, 2172
squareFree, 2172
squareFreePart, 2172
squareFreePolynomial, 2172
subtractIfCan, 2172
unit?, 2172
unitCanonical, 2172
unitNormal, 2172
wholePart, 2172
wholeRadix, 2172
wholeRagits, 2172
zero?, 2172
RadixExpansion, 2171
ramified?
ALGFF, 28
RADFF, 2160
ramifiedAtInfinity?
ALGFF, 28
RADFF, 2160
ramifMult
BLHN, 301
BLQT, 304
random
ALGFF, 28
BINARY, 277
BOOLEAN, 307
BPADICRT, 247
CCLASS, 368
CHAR, 359
COMPLEX, 406
DECIMAL, 453
DIRPROD, 534
DPMM, 540
DPMO, 545
EXPEXPAN, 682
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FRAC, 956
HDP, 1143
HEXADEC, 1113
IFF, 1252
INT, 1330
IPF, 1271
MCMPLX, 1511
MINT, 1525
MODMON, 1600
MRING, 1626
NNI, 1706
OCT, 1731
ODP, 1783
OVAR, 1803
PACOFF, 2102
PADICRAT, 1852
PADICRC, 1857
PERMGRP, 1926
PF, 2071
PRODUCT, 2079
RADFF, 2160
RADIX, 2172
ROMAN, 2293
SAE, 2368
SET, 2338
SETMN, 2344
SHDP, 2476
SINT, 2380
SULS, 2425
ULS, 2763
ULSCONS, 2771
ZMOD, 1336
randomLC

FRIDEAL, 965
range
DROPT, 596
ranges
DROPT, 596
GRIMAGE, 1065
rank
ALGFF, 28
ALGSC, 15
CARTEN, 342
CDFMAT, 413
COMPLEX, 406
DFMAT, 587
DHMATRIX, 479
GCNAALG, 1035
IMATRIX, 1208
JORDAN, 209
LIE, 214
LSQM, 1424
MATRIX, 1591
MCMPLX, 1511
RADFF, 2160
RMATRIX, 2212
SAE, 2368
SQMATRIX, 2515
rarrow
OUTFORM, 1834
rational
COMPLEX, 406
FR, 756
INT, 1330
MCMPLX, 1511
MINT, 1525
OCT, 1731
ONECOMP, 1744
ORDCOMP, 1777
QUAT, 2133
ROMAN, 2293
SINT, 2380
rational?
AFFPLPS, 7
AFFSP, 9
COMPLEX, 406
FR, 756
INT, 1330
MCMPLX, 1511
MINT, 1525
OCT, 1731
ONECOMP, 1744
ORDCOMP, 1777
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
QUAT, 2133
ROMAN, 2293
SINT, 2380
rationalApproximation
DFLOAT, 575
FLOAT, 879
rationalFunction
SULS, 2425
ULS, 2763
ULSCONS, 2771
rationalIfCan
COMPLEX, 406
FR, 756
INT, 1330
MCMPLX, 1511
MINT, 1525
OCT, 1731
ONECOMP, 1744
ORDCOMP, 1777
QUAT, 2133
ROMAN, 2293
SINT, 2380
rationalPoint?
ALGFF, 28
RADFF, 2160
rationalPoints
ALGFF, 28
RADFF, 2160
rationalPower
SUPXS, 2455
UPXS, 2801
UPXSCONS, 2809
ratpart
IR, 1343
ravel
CARTEN, 342
readable?
FNAME, 780
real

COMPLEX, 406
MCMPLX, 1511
OCT, 1731
QUAT, 2133
real?
FST, 933
RealClosure, 2202
recip
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
AUTOMOR, 231
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FMONOID, 991
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
JORDAN, 209
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIE, 214
LODO, 1437
LODO1, 1447
LODO2, 1459
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NOTTING, 1711
NSDPS, 1670
NSMP, 1681

NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
POLY, 2044
PR, 2058
PRODUCT, 2079
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
ROIRC, 2276
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
RECLOS, 2202
-?, 2203
?<?, 2203
?<=?, 2203
?>?, 2203
?>=?, 2203
?**?, 2203
?*?, 2203
?+?, 2203
?-?, 2203
?/?, 2203
?=?, 2203
?^?, 2203
?~=?, 2203
?quo?, 2203
?rem?, 2203
0, 2203
1, 2203
abs, 2203
algebraicOf, 2203
allRootsOf, 2203
approximate, 2203
associates?, 2203
characteristic, 2203
coerce, 2203
divide, 2203
euclideanSize, 2203
expressIdealMember, 2203
exquo, 2203
extendedEuclidean, 2203
factor, 2203

gcd, 2203
gcdPolynomial, 2203
hash, 2203
inv, 2203
latex, 2203
lcm, 2203
mainCharacterization, 2203
mainDefiningPolynomial, 2203
mainForm, 2203
mainValue, 2203
max, 2203
min, 2203
multiEuclidean, 2203
negative?, 2203
nthRoot, 2203
one?, 2203
positive?, 2203
prime?, 2203
principalIdeal, 2203
recip, 2203
relativeApprox, 2203
rename, 2203
retract, 2203
retractIfCan, 2203
rootOf, 2203
sample, 2203
sign, 2203
sizeLess?, 2203
sqrt, 2203
squareFree, 2203
squareFreePart, 2203
subtractIfCan, 2203
unit?, 2203
unitCanonical, 2203
unitNormal, 2203
zero?, 2203
recoverAfterFail
ROUTINE, 2298
RectangularMatrix, 2211
rectangularMatrix
RMATRIX, 2212
red
COLOR, 394
reduce
ALGFF, 28
ALIST, 221
AN, 35
ARRAY1, 1740
BITS, 299
CCLASS, 368
CDFVEC, 419
COMPLEX, 406
DFVEC, 593
DLIST, 448
EMR, 672
EQTBL, 669
EXPR, 694
FARRAY, 856
FDIV, 783
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HELLFDIV, 1153
IAN, 1245
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
MCMPLX, 1511
MODFIELD, 1606
MODMON, 1600
MODRING, 1609
MSET, 1638
NSDPS, 1670
PACOFF, 2102
PACRAT, 2112
PLACES, 1985
PLACESPS, 1987
POINT, 2026
PRIMARR, 2075
RADFF, 2160
REGSET, 2252
RESRING, 2262
RESULT, 2267

RGCHAIN, 2221
ROUTINE, 2298
SAE, 2368
SET, 2338
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
reduceBasisAtInfinity
ALGFF, 28
RADFF, 2160
reduceByQuasiMonic
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
reduced?
GTSET, 1054
NSMP, 1681
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
reducedContinuedFraction
CONTFRAC, 432
reducedForm
CONTFRAC, 432
reducedSystem
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DIRPROD, 534
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EXPEXPAN, 682
EXPR, 694
FRAC, 956
GDMP, 1022
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
INT, 1330
LSQM, 1424
MCMPLX, 1511
MINT, 1525
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODP, 1783
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
POLY, 2044
QUAT, 2133
RADFF, 2160
RADIX, 2172
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
reductum
ANTISYM, 40
DERHAM, 517
DIV, 563
DMP, 560
DSMP, 529
EXPUPXS, 710
FM, 983

FM1, 987
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HDMP, 1150
IDPAG, 1172
IDPAM, 1176
IDPO, 1179
IDPOAM, 1182
IDPOAMS, 1185
INDE, 1187
ISUPS, 1279
LAUPOL, 1390
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
MODMON, 1600
MPOLY, 1650
MRING, 1626
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
OMLO, 1773
ORESUP, 2460
OREUP, 2840
POLY, 2044
PR, 2058
SDPOL, 2352
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
XDPOLY, 2905
XPBWPOLYL, 2925
XPR, 2945
REF, 2215
?=?, 2215
?~=?, 2215
coerce, 2215
deref, 2215
elt, 2215
hash, 2215
latex, 2215
ref, 2215
setelt, 2215
setref, 2215
ref
REF, 2215
Reference, 2215
refine
ACPLOT, 1958
PLOT, 1995
PLOT3D, 2008
ROIRC, 2276
region
VIEW2d, 2739
REGSET, 2251
?=?, 2252
?~=?, 2252
#?, 2252
algebraic?, 2252
algebraicCoefficients?, 2252
algebraicVariables, 2252
any?, 2252
augment, 2252
autoReduced?, 2252
basicSet, 2252
coerce, 2252
coHeight, 2252
collect, 2252
collectQuasiMonic, 2252
collectUnder, 2252
collectUpper, 2252
construct, 2252
convert, 2252

copy, 2252
count, 2252
degree, 2252
empty, 2252
empty?, 2252
eq?, 2252
eval, 2252
every?, 2252
extend, 2252
extendIfCan, 2252
find, 2252
first, 2252
hash, 2252
headReduce, 2252
headReduced?, 2252
headRemainder, 2252
infRittWu?, 2252
initiallyReduce, 2252
initiallyReduced?, 2252
initials, 2252
internalAugment, 2252
internalZeroSetSplit, 2252
intersect, 2252
invertible?, 2252
invertibleElseSplit?, 2252
invertibleSet, 2252
last, 2252
lastSubResultant, 2252
lastSubResultantElseSplit, 2252
latex, 2252
less?, 2252
mainVariable?, 2252
mainVariables, 2252
map, 2252
member?, 2252
members, 2252
more?, 2252
mvar, 2252
normalized?, 2252
parts, 2252
preprocess, 2252
purelyAlgebraic?, 2252
purelyAlgebraicLeadingMonomial?, 2252
purelyTranscendental?, 2252
quasiComponent, 2252
reduce, 2252
reduceByQuasiMonic, 2252
reduced?, 2252
remainder, 2252
remove, 2252
removeDuplicates, 2252
removeZero, 2252
rest, 2252
retract, 2252
retractIfCan, 2252
rewriteIdealWithHeadRemainder, 2252
rewriteIdealWithRemainder, 2252
rewriteSetWithReduction, 2252
roughBase?, 2252
roughEqualIdeals?, 2252
roughSubIdeal?, 2252
roughUnitIdeal?, 2252
sample, 2252
select, 2252
size?, 2252
sort, 2252
squareFreePart, 2252
stronglyReduce, 2252
stronglyReduced?, 2252
triangular?, 2252
trivialIdeal?, 2252
variables, 2252
zeroSetSplit, 2252
zeroSetSplitIntoTriangularSystems, 2252
RegularChain, 2220
regularRepresentation
ALGFF, 28
COMPLEX, 406
MCMPLX, 1511
RADFF, 2160
SAE, 2368
RegularTriangularSet, 2251
reindex
CARTEN, 342
relationsIdeal
IDEAL, 2047
relativeApprox
RECLOS, 2203
ROIRC, 2276
relerror
FLOAT, 879
remainder

GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
RemainderList
XPOLY, 2936
XRPOLY, 2951
remove
ALIST, 221
ARRAY1, 1740
BITS, 299
CCLASS, 368
CDFVEC, 419
DFVEC, 593
DLIST, 448
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
IARRAY1, 1213
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
MSET, 1638
NSDPS, 1670
POINT, 2026
PRIMARR, 2075
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
ROUTINE, 2298
SET, 2338
SPLTREE, 2485
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
removeConjugate
AFFPLPS, 7
AFFSP, 9
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
removeDuplicates
ALIST, 221
ARRAY1, 1740
BITS, 299
CCLASS, 368
CDFVEC, 419
DFVEC, 593
DLIST, 448
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
MSET, 1638
NSDPS, 1670
POINT, 2026
PRIMARR, 2075
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
ROUTINE, 2298
SET, 2338
SREGSET, 2502

STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
removeFirstZeroes
NSDPS, 1670
removeZero
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
removeZeroes
BPADICRT, 247
NSDPS, 1670
PADICRAT, 1852
PADICRC, 1857
SULS, 2425
ULS, 2763
ULSCONS, 2771
rename
RECLOS, 2203
reorder
DMP, 560
GDMP, 1022
HDMP, 1150
repeating
STREAM, 2550
repeating?
STREAM, 2550
repeatUntilLoop
FC, 902
replace
ISTRING, 1218
STRING, 2575
replaceKthElement
SETMN, 2344
representationType
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PF, 2071
RADFF, 2160
SAE, 2368
represents
ALGFF, 28
ALGSC, 15
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
GCNAALG, 1035
IFF, 1252
IPF, 1271
JORDAN, 209
LIE, 214
LSQM, 1424
MCMPLX, 1511
PF, 2071
RADFF, 2160
SAE, 2368
reset
VIEW2d, 2739
VIEW3D, 2679
resetAttributeButtons
ATTRBUT, 224
resetBadValues
PATTERN, 1894
resetNew
SYMBOL, 2608

ResidueRing, 2262
resize
  VIEW2d, 2739
  VIEW3D, 2679
RESRING, 2262
  -?, 2262
  ?**?, 2262
  ?*?, 2262
  ?+?, 2262
  ?-?, 2262
  ?=?, 2262
  ?^?, 2262
  ?~=?, 2262
  0, 2262
  1, 2262
  characteristic, 2262
  coerce, 2262
  hash, 2262
  latex, 2262
  lift, 2262
  one?, 2262
  recip, 2262
  reduce, 2262
  sample, 2262
  subtractIfCan, 2262
  zero?, 2262
rest
  ALIST, 221
  DLIST, 448
  GTSET, 1054
  ILIST, 1201
  LIST, 1472
  MAGMA, 1533
  NSDPS, 1670
  OFMONOID, 1795
  PBWLB, 2020
  REGSET, 2252
  RGCHAIN, 2221
  SREGSET, 2502
  STREAM, 2550
  WUTSET, 2895
RESULT, 2266
  ?.?, 2267
  ?=?, 2267
  ?~=?, 2267
  #?, 2267
any?, 2267
bag, 2267
coerce, 2267
construct, 2267
convert, 2267
copy, 2267
count, 2267
dictionary, 2267
elt, 2267
empty, 2267
empty?, 2267
entries, 2267
entry?, 2267
eq?, 2267
eval, 2267
every?, 2267
extract, 2267
fill, 2267
find, 2267
first, 2267
hash, 2267
index?, 2267
indices, 2267
insert, 2267
inspect, 2267
key?, 2267
keys, 2267
latex, 2267
less?, 2267
map, 2267
maxIndex, 2267
member?, 2267
members, 2267
minIndex, 2267
more?, 2267
parts, 2267
qelt, 2267
qsetelt, 2267
reduce, 2267
remove, 2267
removeDuplicates, 2267
sample, 2267
search, 2267
select, 2267
setelt, 2267
showArrayValues, 2267

showScalarValues, 2267
size?, 2267
swap, 2267
table, 2267
Result, 2266
result
SPLTREE, 2485
resultant
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
retract
ALGFF, 28
AN, 35
ANTISYM, 40
ASP1, 71
ASP10, 75
ASP19, 82
ASP20, 90, 95
ASP31, 115
ASP35, 127
ASP4, 132
ASP41, 136
ASP42, 142
ASP49, 149
ASP50, 154
ASP55, 159
ASP6, 164
ASP7, 169
ASP73, 174
ASP74, 178
ASP77, 184
ASP78, 189
ASP80, 197
ASP9, 202
BINARY, 277
BPADICRT, 247
CARD, 318
CARTEN, 342
COMPLEX, 406
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIV, 563
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EXPEXPAN, 682
EXPR, 694
FAGROUP, 975
FAMONOID, 978
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FM1, 987
FMONOID, 991
FR, 756
FRAC, 956
GDMP, 1022
GPOLSET, 1044
GTSET, 1054
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFAMON, 1255
IFF, 1252

INT, 1330
INTRVL, 1352
IPF, 1271
IR, 1343
LAUPOL, 1390
LMOPS, 1477
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODMON, 1600
MODOP, 1615, 1771
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NIPROB, 1713
NOTTING, 1711
NSMP, 1681
NSUP, 1696
OCT, 1731
ODEPROB, 1716
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795
ONECOMP, 1744
OPTPROB, 1719
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PBWLB, 2020
PDEPROB, 1722
PF, 2071
POLY, 2044
PR, 2058
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REGSET, 2252
RGCHAIN, 2221
ROMAN, 2293
RULE, 2271
SAE, 2368
SD, 2540
SDPOL, 2352
SDVAR, 2358
SHDP, 2476
SINT, 2380
SMP, 2391
SQMATRIX, 2515
SREGSET, 2502
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SYMPOLY, 2622
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
retractable?
ANTISYM, 40
DERHAM, 517
LWORD, 1500
MAGMA, 1533
PBWLB, 2020
retractIfCan
ALGFF, 28
AN, 35
ANTISYM, 40
ASP1, 71

ASP10, 75
ASP19, 82
ASP20, 90, 95
ASP31, 115
ASP35, 127
ASP4, 132
ASP41, 136
ASP42, 142
ASP49, 149
ASP50, 154
ASP55, 159
ASP6, 164
ASP7, 169
ASP73, 174
ASP74, 178
ASP77, 184
ASP78, 189
ASP80, 197
ASP9, 202
BINARY, 277
BPADICRT, 247
CARD, 318
CARTEN, 342
COMPLEX, 406
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIV, 563
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EXPEXPAN, 682
EXPR, 694
FAGROUP, 975
FAMONOID, 978
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FM1, 987
FMONOID, 991
FR, 756
FRAC, 956
GDMP, 1022
GPOLSET, 1044
GTSET, 1054
HACKPI, 1944
HDMP, 1150
HDP, 1143
HEXADEC, 1113
IAN, 1245
IFAMON, 1255
IFF, 1252
INT, 1330
INTRVL, 1352
IPF, 1271
IR, 1343
LAUPOL, 1390
LMOPS, 1477
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
LWORD, 1500
MAGMA, 1533
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODMON, 1600
MODOP, 1615, 1771
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODVAR, 1821
OFMONOID, 1795

ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PATTERN, 1894
PBWLB, 2020
PF, 2071
POLY, 2044
PR, 2058
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REGSET, 2252
RGCHAIN, 2221
ROMAN, 2293
RULE, 2271
SAE, 2368
SD, 2540
SDPOL, 2352
SDVAR, 2358
SHDP, 2476
SINT, 2380
SMP, 2391
SQMATRIX, 2515
SREGSET, 2502
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SYMPOLY, 2622
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
returns
FC, 902
returnTypeOf
SYMS, 2665
reverse
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
LMOPS, 1477
POINT, 2026
PRIMARR, 2075
STRING, 2575
U32VEC, 2869
VECTOR, 2878
revert
UFPS, 2757
UTS, 2844
UTSZ, 2854
rewriteIdealWithHeadRemainder
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
rewriteIdealWithRemainder
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
RewriteRule, 2271
rewriteSetWithReduction

GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
RGCHAIN, 2220
?=?, 2221
?~=?, 2221
#?, 2221
algebraic?, 2221
algebraicCoefficients?, 2221
algebraicVariables, 2221
any?, 2221
augment, 2221
autoReduced?, 2221
basicSet, 2221
coerce, 2221
coHeight, 2221
collect, 2221
collectQuasiMonic, 2221
collectUnder, 2221
collectUpper, 2221
construct, 2221
convert, 2221
copy, 2221
count, 2221
degree, 2221
empty, 2221
empty?, 2221
eq?, 2221
eval, 2221
every?, 2221
extend, 2221
extendIfCan, 2221
find, 2221
first, 2221
hash, 2221
headReduce, 2221
headReduced?, 2221
headRemainder, 2221
infRittWu?, 2221
initiallyReduce, 2221
initiallyReduced?, 2221
initials, 2221
internalAugment, 2221
intersect, 2221
invertible?, 2221
invertibleElseSplit?, 2221
invertibleSet, 2221
last, 2221
lastSubResultant, 2221
lastSubResultantElseSplit, 2221
latex, 2221
less?, 2221
mainVariable?, 2221
mainVariables, 2221
map, 2221
member?, 2221
members, 2221
more?, 2221
mvar, 2221
normalized?, 2221
parts, 2221
purelyAlgebraic?, 2221
purelyAlgebraicLeadingMonomial?, 2221
purelyTranscendental?, 2221
quasiComponent, 2221
reduce, 2221
reduceByQuasiMonic, 2221
reduced?, 2221
remainder, 2221
remove, 2221
removeDuplicates, 2221
removeZero, 2221
rest, 2221
retract, 2221
retractIfCan, 2221
rewriteIdealWithHeadRemainder, 2221
rewriteIdealWithRemainder, 2221
rewriteSetWithReduction, 2221
roughBase?, 2221
roughEqualIdeals?, 2221
roughSubIdeal?, 2221
roughUnitIdeal?, 2221
sample, 2221
select, 2221
size?, 2221
sort, 2221
squareFreePart, 2221
stronglyReduce, 2221
stronglyReduced?, 2221
triangular?, 2221

trivialIdeal?, 2221
variables, 2221
zeroSetSplit, 2221
zeroSetSplitIntoTriangularSystems, 2221
rhs
EQ, 661
RULE, 2271
SUCH, 2595
right
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
LWORD, 1500
MAGMA, 1533
OUTFORM, 1834
PENDTREE, 1911
ROIRC, 2276
rightAlternative?
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightCharacteristicPolynomial
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightDiscriminant
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightDivide
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightExactQuotient
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightExtendedGcd
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightGcd
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightLcm
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightMinimalPolynomial
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightMult
LMOPS, 1477
rightNorm
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightOne
EQ, 661
RightOpenIntervalRootCharacterization, 2276
rightPower
ALGSC, 15
FNLA, 997
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightQuotient
LODO, 1437

LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightRankPolynomial
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightRecip
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightRegularRepresentation
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightRemainder
LODO, 1437
LODO1, 1447
LODO2, 1459
ORESUP, 2460
OREUP, 2840
rightTrace
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightTraceMatrix
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightTrim
ISTRING, 1218
STRING, 2575
rightUnit
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightUnits
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
rightZero
EQ, 661
RittWuCompare
NSMP, 1681
RMATRIX, 2211
-?, 2212
?*?, 2212
?+?, 2212
?-?, 2212
?/?, 2212
?=?, 2212
?~=?, 2212
#?, 2212
0, 2212
antisymmetric?, 2212
any?, 2212
coerce, 2212
column, 2212
convert, 2212
copy, 2212
count, 2212
diagonal?, 2212
dimension, 2212
elt, 2212
empty, 2212
empty?, 2212
eq?, 2212
eval, 2212
every?, 2212
exquo, 2212
hash, 2212
latex, 2212
less?, 2212
listOfLists, 2212
map, 2212
matrix, 2212
maxColIndex, 2212

maxRowIndex, 2212
member?, 2212
members, 2212
minColIndex, 2212
minRowIndex, 2212
more?, 2212
ncols, 2212
nrows, 2212
nullity, 2212
nullSpace, 2212
parts, 2212
qelt, 2212
rank, 2212
rectangularMatrix, 2212
row, 2212
rowEchelon, 2212
sample, 2212
size?, 2212
square?, 2212
subtractIfCan, 2212
symmetric?, 2212
zero?, 2212
ROIRC, 2276
?=?, 2276
?~=?, 2276
allRootsOf, 2276
approximate, 2276
coerce, 2276
definingPolynomial, 2276
hash, 2276
latex, 2276
left, 2276
middle, 2276
mightHaveRoots, 2276
negative?, 2276
positive?, 2276
recip, 2276
refine, 2276
relativeApprox, 2276
right, 2276
rootOf, 2276
sign, 2276
size, 2276
zero?, 2276
ROMAN, 2292
-?, 2293
?<?, 2293
?<=?, 2293
?>?, 2293
?>=?, 2293
?**?, 2293
?*?, 2293
?+?, 2293
?-?, 2293
?=?, 2293
?^?, 2293
?~=?, 2293
?quo?, 2293
?rem?, 2293
0, 2293
1, 2293
abs, 2293
addmod, 2293
associates?, 2293
base, 2293
binomial, 2293
bit?, 2293
characteristic, 2293
coerce, 2293
convert, 2293
copy, 2293
D, 2293
dec, 2293
differentiate, 2293
divide, 2293
euclideanSize, 2293
even?, 2293
expressIdealMember, 2293
exquo, 2293
extendedEuclidean, 2293
factor, 2293
factorial, 2293
gcd, 2293
gcdPolynomial, 2293
hash, 2293
inc, 2293
init, 2293
invmod, 2293
latex, 2293
lcm, 2293
length, 2293
mask, 2293

max, 2293
min, 2293
mulmod, 2293
multiEuclidean, 2293
negative?, 2293
nextItem, 2293
odd?, 2293
one?, 2293
patternMatch, 2293
permutation, 2293
positive?, 2293
positiveRemainder, 2293
powmod, 2293
prime?, 2293
principalIdeal, 2293
random, 2293
rational, 2293
rational?, 2293
rationalIfCan, 2293
recip, 2293
reducedSystem, 2293
retract, 2293
retractIfCan, 2293
roman, 2293
sample, 2293
shift, 2293
sign, 2293
sizeLess?, 2293
squareFree, 2293
squareFreePart, 2293
submod, 2293
subtractIfCan, 2293
symmetricRemainder, 2293
unit?, 2293
unitCanonical, 2293
unitNormal, 2293
zero?, 2293
roman
ROMAN, 2293
RomanNumeral, 2292
root
BPADIC, 242
IPADIC, 1262
OUTFORM, 1834
PADIC, 1847
root?
SUBSPACE, 2582
rootOf
AN, 35
EXPR, 694
IAN, 1245
RECLOS, 2203
ROIRC, 2276
rootsOf
AN, 35
EXPR, 694
IAN, 1245
rotate
VIEW3D, 2679
rotatex
DHMATRIX, 479
rotatey
DHMATRIX, 479
rotatez
DHMATRIX, 479
roughBase?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
roughEqualIdeals?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
roughSubIdeal?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
roughUnitIdeal?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502

WUTSET, 2895
round
DFLOAT, 575
FLOAT, 879
MFLOAT, 1516
ROUTINE, 2297
?.?, 2298
?=?, 2298
?~=?, 2298
#?, 2298
any?, 2298
bag, 2298
changeMeasure, 2298
changeThreshhold, 2298
coerce, 2298
concat, 2298
construct, 2298
convert, 2298
copy, 2298
count, 2298
deleteRoutine, 2298
dictionary, 2298
elt, 2298
empty, 2298
empty?, 2298
entries, 2298
entry?, 2298
eq?, 2298
eval, 2298
every?, 2298
extract, 2298
fill, 2298
find, 2298
first, 2298
getExplanations, 2298
getMeasure, 2298
hash, 2298
index?, 2298
indices, 2298
insert, 2298
inspect, 2298
key?, 2298
keys, 2298
latex, 2298
less?, 2298
map, 2298
maxIndex, 2298
member?, 2298
members, 2298
minIndex, 2298
more?, 2298
parts, 2298
qelt, 2298
qsetelt, 2298
recoverAfterFail, 2298
reduce, 2298
remove, 2298
removeDuplicates, 2298
routines, 2298
sample, 2298
search, 2298
select, 2298
selectFiniteRoutines, 2298
selectIntegrationRoutines, 2298
selectMultiDimensionalRoutines, 2298
selectNonFiniteRoutines, 2298
selectODEIVPRoutines, 2298
selectOptimizationRoutines, 2298
selectPDERoutines, 2298
selectSumOfSquaresRoutines, 2298
setelt, 2298
showTheRoutinesTable, 2298
size?, 2298
swap, 2298
table, 2298
routines
ROUTINE, 2298
RoutinesTable, 2297
row
ARRAY2, 2732
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IARRAY2, 1225
IIARRAY2, 1258
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
rowEchelon
CDFMAT, 413

DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
rquo
FMONOID, 991
LPOLY, 1415
OFMONOID, 1795
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
rspace
OUTFORM, 1834
rst
NSDPS, 1670
STREAM, 2550
RULE, 2271
?.?, 2271
?=?, 2271
?~=?, 2271
coerce, 2271
elt, 2271
hash, 2271
latex, 2271
lhs, 2271
pattern, 2271
quotedOperators, 2271
retract, 2271
retractIfCan, 2271
rhs, 2271
rule, 2271
suchThat, 2271
rule
RULE, 2271
RuleCalled, 2307
RULECOLD, 2307
?=?, 2307
?~=?, 2307
coerce, 2307
hash, 2307
latex, 2307
name, 2307
rules
RULESET, 2309
RULESET, 2309
?.?, 2309
?=?, 2309
?~=?, 2309
coerce, 2309
elt, 2309
hash, 2309
latex, 2309
rules, 2309
ruleset, 2309
Ruleset, 2309
ruleset
RULESET, 2309

SAE, 2368
-?, 2368
?**?, 2368
?*?, 2368
?+?, 2368
?-?, 2368
?/?, 2368
?=?, 2368
?^?, 2368
?~=?, 2368
?quo?, 2368
?rem?, 2368
0, 2368
1, 2368
associates?, 2368
basis, 2368
characteristic, 2368
characteristicPolynomial, 2368
charthRoot, 2368
coerce, 2368
conditionP, 2368
convert, 2368
coordinates, 2368
createPrimitiveElement, 2368
D, 2368
definingPolynomial, 2368
derivationCoordinates, 2368
differentiate, 2368
discreteLog, 2368
discriminant, 2368

divide, 2368
euclideanSize, 2368
expressIdealMember, 2368
exquo, 2368
extendedEuclidean, 2368
factor, 2368
factorsOfCyclicGroupSize, 2368
gcd, 2368
gcdPolynomial, 2368
generator, 2368
hash, 2368
index, 2368
init, 2368
inv, 2368
latex, 2368
lcm, 2368
lift, 2368
lookup, 2368
minimalPolynomial, 2368
multiEuclidean, 2368
nextItem, 2368
norm, 2368
one?, 2368
order, 2368
prime?, 2368
primeFrobenius, 2368
primitive?, 2368
primitiveElement, 2368
principalIdeal, 2368
random, 2368
rank, 2368
recip, 2368
reduce, 2368
reducedSystem, 2368
regularRepresentation, 2368
representationType, 2368
represents, 2368
retract, 2368
retractIfCan, 2368
sample, 2368
size, 2368
sizeLess?, 2368
squareFree, 2368
squareFreePart, 2368
subtractIfCan, 2368
tableForDiscreteLogarithm, 2368
trace, 2368
traceMatrix, 2368
unit?, 2368
unitCanonical, 2368
unitNormal, 2368
zero?, 2368
safety
GOPT, 1075
GOPT0, 1081
sample
ALGFF, 28
ALGSC, 15
ALIST, 221
AN, 35
ANTISYM, 40
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
AUTOMOR, 231
BBTREE, 237
BINARY, 277
BITS, 299
BPADIC, 242
BPADICRT, 247
BSTREE, 287
BTOURN, 291
BTREE, 295
CARD, 318
CARTEN, 342
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DEQUEUE, 499
DERHAM, 517
DFLOAT, 575
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DIRRING, 551
DIV, 563
DLIST, 448

DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
DSTREE, 522
EMR, 672
EQ, 661
EQTBL, 669
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FARRAY, 856
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FLOAT, 879
FM, 983
FM1, 987
FMONOID, 991
FNLA, 997
FR, 756
FRAC, 956
FRIDEAL, 965
FRMOD, 970
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GPOLSET, 1044
GSERIES, 1061
GSTBL, 1049
GTSET, 1054
HACKPI, 1944
HASHTBL, 1090
HDMP, 1150
HDP, 1143
HEAP, 1104
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IDPAG, 1172
IDPAM, 1176
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFARRAY, 1192
IFF, 1252
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INDE, 1187
INT, 1330
INTABL, 1304
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISTRING, 1218
ISUPS, 1279
ITAYLOR, 1306
IVECTOR, 1229
JORDAN, 209
KAFILE, 1382
LA, 1488
LAUPOL, 1390
LEXP, 1403
LIB, 1397
LIE, 214
LIST, 1472
LMDICT, 1483
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
M3D, 2672
MATRIX, 1591

MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MOEBIUS, 1622
MPOLY, 1650
MRING, 1626
MSET, 1638
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NOTTING, 1711
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OFMONOID, 1795
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PENDTREE, 1911
PERM, 1916
PF, 2071
PFR, 1880
PI, 2066
POINT, 2026
POLY, 2044
PR, 2058
PRIMARR, 2075
PRODUCT, 2079
PRTITION, 1889
QFORM, 2120
QUAT, 2133
QUEUE, 2150
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REGSET, 2252
RESRING, 2262
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROMAN, 2293
ROUTINE, 2298
SAE, 2368
SD, 2540
SDPOL, 2352
SET, 2338
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMBOL, 2608
SYMPOLY, 2622
TABLE, 2632
TREE, 2710
TS, 2639
U32VEC, 2869
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819

UTS, 2844
UTSZ, 2854
VECTOR, 2878
WP, 2885
WUTSET, 2895
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
SAOS, 2386
?<?, 2386
?<=?, 2386
?>?, 2386
?>=?, 2386
?=?, 2386
?~=?, 2386
coerce, 2386
convert, 2386
create, 2386
hash, 2386
latex, 2386
max, 2386
min, 2386
satisfy?
PATRES, 1906
saturate
IDEAL, 2047
save
FC, 902
sbt
NSDPS, 1670
scalarMatrix
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
SQMATRIX, 2515
scalarTypeOf
FT, 941
scale
DHMATRIX, 479
MOEBIUS, 1622
VIEW2d, 2739
screenResolution
PLOT, 1995
screenResolution3D
PLOT3D, 2008
script
SYMBOL, 2608
scripted?
SYMBOL, 2608
ScriptFormulaFormat, 2312
scripts
OUTFORM, 1834
SYMBOL, 2608
SD, 2539
-?, 2540
?**?, 2540
?*?, 2540
?+?, 2540
?-?, 2540
?/?, 2540
?=?, 2540
?^?, 2540
?~=?, 2540
0, 2540
alterDrift, 2540
alterQuadVar, 2540
coefficient, 2540
coerce, 2540
copyDrift, 2540
copyQuadVar, 2540
drift, 2540
equation, 2540
freeOf?, 2540
hash, 2540
latex, 2540
listSD, 2540
retract, 2540
retractIfCan, 2540
sample, 2540
statusIto, 2540
subtractIfCan, 2540
uncorrelated?, 2540
zero?, 2540
SDPOL, 2351
-?, 2352
?<?, 2352

?<=?, 2352
?>?, 2352
?>=?, 2352
?**?, 2352
?*?, 2352
?+?, 2352
?-?, 2352
?/?, 2352
?=?, 2352
?^?, 2352
?~=?, 2352
0, 2352
1, 2352
associates?, 2352
binomThmExpt, 2352
characteristic, 2352
charthRoot, 2352
coefficient, 2352
coefficients, 2352
coerce, 2352
conditionP, 2352
content, 2352
convert, 2352
D, 2352
degree, 2352
differentialVariables, 2352
differentiate, 2352
discriminant, 2352
eval, 2352
exquo, 2352
factor, 2352
factorPolynomial, 2352
factorSquareFreePolynomial, 2352
gcd, 2352
gcdPolynomial, 2352
ground, 2352
ground?, 2352
hash, 2352
initial, 2352
isExpt, 2352
isobaric?, 2352
isPlus, 2352
isTimes, 2352
latex, 2352
lcm, 2352
leader, 2352
leadingCoefficient, 2352
leadingMonomial, 2352
mainVariable, 2352
makeVariable, 2352
map, 2352
mapExponents, 2352
max, 2352
min, 2352
minimumDegree, 2352
monicDivide, 2352
monomial, 2352
monomial?, 2352
monomials, 2352
multivariate, 2352
numberOfMonomials, 2352
one?, 2352
order, 2352
patternMatch, 2352
pomopo, 2352
prime?, 2352
primitiveMonomials, 2352
primitivePart, 2352
recip, 2352
reducedSystem, 2352
reductum, 2352
resultant, 2352
retract, 2352
retractIfCan, 2352
sample, 2352
separant, 2352
solveLinearPolynomialEquation, 2352
squareFree, 2352
squareFreePart, 2352
squareFreePolynomial, 2352
subtractIfCan, 2352
totalDegree, 2352
unit?, 2352
unitCanonical, 2352
unitNormal, 2352
univariate, 2352
variables, 2352
weight, 2352
weights, 2352
zero?, 2352
SDVAR, 2357
?<?, 2358

?<=?, 2358
?>?, 2358
?>=?, 2358
?=?, 2358
?~=?, 2358
coerce, 2358
differentiate, 2358
hash, 2358
latex, 2358
makeVariable, 2358
max, 2358
min, 2358
order, 2358
retract, 2358
retractIfCan, 2358
variable, 2358
weight, 2358
search
ALIST, 221
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
INTABL, 1304
KAFILE, 1382
LIB, 1397
RESULT, 2267
ROUTINE, 2298
STBL, 2418
STRTBL, 2578
TABLE, 2632
sec
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
sech
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
second
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
SEG, 2325
?..?, 2325
?=?, 2325
?~=?, 2325
BY, 2325
coerce, 2325
convert, 2325
expand, 2325
hash, 2325
hi, 2325
high, 2325

incr, 2325
latex, 2325
lo, 2325
low, 2325
map, 2325
segment, 2325
SEGBIND, 2330
?=?, 2330
?~=?, 2330
coerce, 2330
equation, 2330
hash, 2330
latex, 2330
segment, 2330
variable, 2330
Segment, 2325
segment
SEG, 2325
SEGBIND, 2330
UNISEG, 2863
SegmentBinding, 2330
select
ALIST, 221
ARRAY1, 1740
CCLASS, 368
CDFVEC, 419
DFVEC, 593
DLIST, 448
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
INTABL, 1304
ISTRING, 1218
ITUPLE, 1231
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
MSET, 1638
NSDPS, 1670
POINT, 2026
PRIMARR, 2075
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
ROUTINE, 2298
SET, 2338
SREGSET, 2502
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TUPLE, 2721
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
selectFiniteRoutines
ROUTINE, 2298
selectfirst
PRODUCT, 2079
selectIntegrationRoutines
ROUTINE, 2298
selectMultiDimensionalRoutines
ROUTINE, 2298
selectNonFiniteRoutines
ROUTINE, 2298
selectODEIVPRoutines
ROUTINE, 2298
selectOptimizationRoutines
ROUTINE, 2298
selectPDERoutines
ROUTINE, 2298
selectsecond
PRODUCT, 2079
selectSumOfSquaresRoutines
ROUTINE, 2298
semicolonSeparate
OUTFORM, 1834
separant
DSMP, 529
ODPOL, 1818
SDPOL, 2352
separate

LAUPOL, 1390
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUBSPACE, 2582
SUP, 2435
SUPEXPR, 2449
UP, 2795
SequentialDifferentialPolynomial, 2351
SequentialDifferentialVariable, 2357
series
EXPUPXS, 710
GSERIES, 1061
ISUPS, 1279
ITAYLOR, 1306
NSDPS, 1670
SULS, 2425
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
seriesToOutputForm
ISUPS, 1279
SET, 2338
?<?, 2338
?=?, 2338
?~=?, 2338
#?, 2338
any?, 2338
bag, 2338
brace, 2338
cardinality, 2338
coerce, 2338
complement, 2338
construct, 2338
convert, 2338
copy, 2338
count, 2338
dictionary, 2338
difference, 2338
empty, 2338
empty?, 2338
eq?, 2338
eval, 2338
every?, 2338
extract, 2338
find, 2338
hash, 2338
index, 2338
insert, 2338
inspect, 2338
intersect, 2338
latex, 2338
less?, 2338
lookup, 2338
map, 2338
max, 2338
member?, 2338
members, 2338
min, 2338
more?, 2338
parts, 2338
random, 2338
reduce, 2338
remove, 2338
removeDuplicates, 2338
sample, 2338
select, 2338
set, 2338
size, 2338
size?, 2338
subset?, 2338
symmetricDifference, 2338
union, 2338
universe, 2338
Set, 2338
set
CCLASS, 368
MSET, 1638
SET, 2338
setAdaptive
PLOT, 1995
setAdaptive3D
PLOT3D, 2008
setAttributeButtonStep
ATTRBUT, 224
setButtonValue

ATTRBUT, 224
setClosed
TUBE, 2718
setDifference
LIST, 1472
setelt
AFFPLPS, 7
AFFSP, 9
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CDFMAT, 413
CDFVEC, 419
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GSTBL, 1049
HASHTBL, 1090
HDP, 1143
IARRAY1, 1213
IARRAY2, 1225
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
MATRIX, 1591
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
PROJPL, 2083
PROJPLPS, 2085
PROJSP, 2088
REF, 2215
RESULT, 2267
ROUTINE, 2298
SHDP, 2476
SPLTREE, 2485
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
setFoundPlacesToEmpty
PLACES, 1985
PLACESPS, 1987
setIntersection
LIST, 1472
setLabelValue
FC, 902
setMaxPoints
PLOT, 1995
setMaxPoints3D
PLOT3D, 2008
setMinPoints
PLOT, 1995
setMinPoints3D
PLOT3D, 2008
SETMN, 2344
?=?, 2344
?~=?, 2344
coerce, 2344
delta, 2344
elements, 2344
enumerate, 2344
hash, 2344
incrementKthElement, 2344
index, 2344
latex, 2344
lookup, 2344

member?, 2344
random, 2344
replaceKthElement, 2344
setOfMinN, 2344
size, 2344
setOfMinN
SETMN, 2344
SetOfMIntegersInOneToN, 2344
setPoly
MODMON, 1600
setPosition
KERNEL, 1372
MKCHSET, 1538
setPredicates
PATTERN, 1894
setProperties
BOP, 258
setProperty
BOP, 258
setref
REF, 2215
setScreenResolution
PLOT, 1995
setScreenResolution3D
PLOT3D, 2008
setStatus
QALGSET, 2123
setTopPredicate
PATTERN, 1894
setUnion
LIST, 1472
SEX, 2360
?.?, 2360
?=?, 2360
?~=?, 2360
#?, 2360
atom?, 2360
car, 2360
cdr, 2360
coerce, 2360
convert, 2360
destruct, 2360
eq, 2360
expr, 2360
float, 2360
float?, 2360
hash, 2360
integer, 2360
integer?, 2360
latex, 2360
list?, 2360
null?, 2360
pair?, 2360
string, 2360
string?, 2360
symbol, 2360
symbol?, 2360
SEXOF, 2362
?.?, 2363
?=?, 2363
?~=?, 2363
#?, 2363
atom?, 2363
car, 2363
cdr, 2363
coerce, 2363
convert, 2363
destruct, 2363
eq, 2363
expr, 2363
float, 2363
float?, 2363
hash, 2363
integer, 2363
integer?, 2363
latex, 2363
list?, 2363
null?, 2363
pair?, 2363
string, 2363
string?, 2363
symbol, 2363
symbol?, 2363
SExpression, 2360
SExpressionOf, 2362
SFORT, 2373
coerce, 2374
fortran, 2374
outputAsFortran, 2374
sh
XDPOLY, 2905
XPBWPOLYL, 2925

XPOLY, 2936
XRPOLY, 2951
shade
PALETTE, 1862
shallowCopy
SUBSPACE, 2582
shallowExpand
FNLA, 997
SHDP, 2476
-?, 2476
?<?, 2476
?<=?, 2476
?>?, 2476
?>=?, 2476
?**?, 2476
?*?, 2476
?+?, 2476
?-?, 2476
?.?, 2476
?/?, 2476
?=?, 2476
?^?, 2476
?~=?, 2476
#?, 2476
0, 2476
1, 2476
abs, 2476
any?, 2476
characteristic, 2476
coerce, 2476
copy, 2476
count, 2476
D, 2476
differentiate, 2476
dimension, 2476
directProduct, 2476
dot, 2476
elt, 2476
empty, 2476
empty?, 2476
entries, 2476
entry?, 2476
eq?, 2476
eval, 2476
every?, 2476
fill, 2476
first, 2476
hash, 2476
index, 2476
index?, 2476
indices, 2476
latex, 2476
less?, 2476
lookup, 2476
map, 2476
max, 2476
maxIndex, 2476
member?, 2476
members, 2476
min, 2476
minIndex, 2476
more?, 2476
negative?, 2476
one?, 2476
parts, 2476
positive?, 2476
qelt, 2476
qsetelt, 2476
random, 2476
recip, 2476
reducedSystem, 2476
retract, 2476
retractIfCan, 2476
sample, 2476
setelt, 2476
sign, 2476
size, 2476
size?, 2476
subtractIfCan, 2476
sup, 2476
swap, 2476
unitVector, 2476
zero?, 2476
shift
FLOAT, 879
INT, 1330
MINT, 1525
MOEBIUS, 1622
NNI, 1706
NSDPS, 1670
ROMAN, 2293
SINT, 2380

shiftLeft
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
shiftRight
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
show
VIEW2d, 2739
showAll?
STREAM, 2550
showAllElements
STREAM, 2550
showArrayValues
RESULT, 2267
showAttributes
INTFTBL, 1339
showClipRegion
VIEW3D, 2679
showIntensityFunctions
ODEIFTBL, 1734
showRegion
VIEW3D, 2679
showScalarValues
RESULT, 2267
showTheFTable
INTFTBL, 1339
showTheIFTable
ODEIFTBL, 1734
showTheRoutinesTable
ROUTINE, 2298
showTheSymbolTable
SYMS, 2665
showTypeInOutput
ANY, 50
shrinkable
FARRAY, 856
IFARRAY, 1192
Si
EXPR, 694
sign
BINARY, 277
BPADICRT, 247
DECIMAL, 453
DFLOAT, 575
DIRPROD, 534
DPMM, 540
DPMO, 545
EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HDP, 1143
HEXADEC, 1113
INT, 1330
LA, 1488
MFLOAT, 1516
MINT, 1525
ODP, 1783
ONECOMP, 1744
ORDCOMP, 1777
PADICRAT, 1852
PADICRC, 1857
PERM, 1916
RADIX, 2172
RECLOS, 2203
ROIRC, 2276
ROMAN, 2293
SHDP, 2476
SINT, 2380
SULS, 2425
ULS, 2763
ULSCONS, 2771
SimpleAlgebraicExtension, 2368
SimpleFortranProgram, 2373
simplify
QALGSET, 2123
simplifyPower
EXPR, 694
sin
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FCOMP, 945
FEXPR, 917

FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
sin?
FCOMP, 945
SingleInteger, 2380
SingletonAsOrderedSet, 2386
singular?
ALGFF, 28
RADFF, 2160
singularAtInfinity?
ALGFF, 28
RADFF, 2160
sinh
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
SINT, 2380
-?, 2380
?<?, 2380
?<=?, 2380
?>?, 2380
?>=?, 2380
?ΓE30F/?, 2380
?**?, 2380
?*?, 2380
?+?, 2380
?-?, 2380
?/ΓE30F?, 2380
?=?, 2380
?^?, 2380
?~=?, 2380
?quo?, 2380
?rem?, 2380
?, 2380
0, 2380
1, 2380
abs, 2380
addmod, 2380
And, 2380
associates?, 2380
base, 2380
binomial, 2380
bit?, 2380
characteristic, 2380
coerce, 2380
convert, 2380
copy, 2380
D, 2380
dec, 2380
differentiate, 2380
divide, 2380
euclideanSize, 2380
even?, 2380
expressIdealMember, 2380
exquo, 2380
extendedEuclidean, 2380
factor, 2380
factorial, 2380

gcd, 2380
gcdPolynomial, 2380
hash, 2380
inc, 2380
init, 2380
invmod, 2380
latex, 2380
lcm, 2380
length, 2380
mask, 2380
max, 2380
min, 2380
mulmod, 2380
multiEuclidean, 2380
negative?, 2380
nextItem, 2380
Not, 2380
not?, 2380
odd?, 2380
OMwrite, 2380
one?, 2380
Or, 2380
patternMatch, 2380
permutation, 2380
positive?, 2380
positiveRemainder, 2380
powmod, 2380
prime?, 2380
principalIdeal, 2380
random, 2380
rational, 2380
rational?, 2380
rationalIfCan, 2380
recip, 2380
reducedSystem, 2380
retract, 2380
retractIfCan, 2380
sample, 2380
shift, 2380
sign, 2380
sizeLess?, 2380
squareFree, 2380
squareFreePart, 2380
submod, 2380
subtractIfCan, 2380
symmetricRemainder, 2380
unit?, 2380
unitCanonical, 2380
unitNormal, 2380
xor, 2380
zero?, 2380
size
ALGFF, 28
BOOLEAN, 307
CCLASS, 368
CHAR, 359
COMPLEX, 406
DIRPROD, 534
DIV, 563
DPMM, 540
DPMO, 545
FAGROUP, 975
FAMONOID, 978
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FGROUP, 980
FMONOID, 991
HDP, 1143
IFAMON, 1255
IFF, 1252
IPF, 1271
LMOPS, 1477
MCMPLX, 1511
MODMON, 1600
MRING, 1626
OCT, 1731
ODP, 1783
OFMONOID, 1795
OVAR, 1803
PACOFF, 2102
PF, 2071
PRODUCT, 2079
RADFF, 2160
ROIRC, 2276
SAE, 2368

SET, 2338
SETMN, 2344
SHDP, 2476
ZMOD, 1336
size?
ALIST, 221
ARRAY1, 1740
ARRAY2, 2732
ASTACK, 65
BBTREE, 237
BITS, 299
BSTREE, 287
BTOURN, 291
BTREE, 295
CCLASS, 368
CDFMAT, 413
CDFVEC, 419
DEQUEUE, 499
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
DIRPROD, 534
DLIST, 448
DPMM, 540
DPMO, 545
DSTREE, 522
EQTBL, 669
FARRAY, 856
GPOLSET, 1044
GSTBL, 1049
GTSET, 1054
HASHTBL, 1090
HDP, 1143
HEAP, 1104
IARRAY1, 1213
IARRAY2, 1225
IBITS, 1169
IFARRAY, 1192
IIARRAY2, 1258
ILIST, 1201
IMATRIX, 1208
INTABL, 1304
ISTRING, 1218
IVECTOR, 1229
KAFILE, 1382
LIB, 1397
LIST, 1472
LMDICT, 1483
LSQM, 1424
M3D, 2672
MATRIX, 1591
MSET, 1638
NSDPS, 1670
ODP, 1783
PENDTREE, 1911
POINT, 2026
PRIMARR, 2075
QUEUE, 2150
REGSET, 2252
RESULT, 2267
RGCHAIN, 2221
RMATRIX, 2212
ROUTINE, 2298
SET, 2338
SHDP, 2476
SPLTREE, 2485
SQMATRIX, 2515
SREGSET, 2502
STACK, 2530
STBL, 2418
STREAM, 2550
STRING, 2575
STRTBL, 2578
TABLE, 2632
TREE, 2710
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
sizeLess?
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710

FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FRAC, 956
GSERIES, 1061
HACKPI, 1944
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPADIC, 1262
IPF, 1271
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSUP, 1696
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SINT, 2380
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
sizeMultiplication
FFNB, 830
FFNBP, 842
FFNBX, 836
slash
OUTFORM, 1834
SMP, 2390
-?, 2391
?<?, 2391
?<=?, 2391
?>?, 2391
?>=?, 2391
?**?, 2391
?*?, 2391
?+?, 2391
?-?, 2391
?/?, 2391
?=?, 2391
?^?, 2391
?~=?, 2391
0, 2391
1, 2391
associates?, 2391
binomThmExpt, 2391
characteristic, 2391
charthRoot, 2391
coefficient, 2391
coefficients, 2391
coerce, 2391
conditionP, 2391
content, 2391
convert, 2391
D, 2391
degree, 2391
differentiate, 2391
discriminant, 2391
eval, 2391
exquo, 2391
factor, 2391
factorPolynomial, 2391

factorSquareFreePolynomial, 2391
gcd, 2391
gcdPolynomial, 2391
ground, 2391
ground?, 2391
hash, 2391
isExpt, 2391
isPlus, 2391
isTimes, 2391
latex, 2391
lcm, 2391
leadingCoefficient, 2391
leadingMonomial, 2391
mainVariable, 2391
map, 2391
mapExponents, 2391
max, 2391
min, 2391
minimumDegree, 2391
monicDivide, 2391
monomial, 2391
monomial?, 2391
monomials, 2391
multivariate, 2391
numberOfMonomials, 2391
one?, 2391
patternMatch, 2391
pomopo, 2391
prime?, 2391
primitiveMonomials, 2391
primitivePart, 2391
recip, 2391
reducedSystem, 2391
reductum, 2391
resultant, 2391
retract, 2391
retractIfCan, 2391
sample, 2391
solveLinearPolynomialEquation, 2391
squareFree, 2391
squareFreePart, 2391
squareFreePolynomial, 2391
subtractIfCan, 2391
totalDegree, 2391
unit?, 2391
unitCanonical, 2391
unitNormal, 2391
univariate, 2391
variables, 2391
zero?, 2391
SMTS, 2408
-?, 2409
?**?, 2409
?*?, 2409
?+?, 2409
?-?, 2409
?=?, 2409
?^?, 2409
?~=?, 2409
0, 2409
1, 2409
acos, 2409
acosh, 2409
acot, 2409
acoth, 2409
acsc, 2409
acsch, 2409
asec, 2409
asech, 2409
asin, 2409
asinh, 2409
associates?, 2409
atan, 2409
atanh, 2409
characteristic, 2409
charthRoot, 2409
coefficient, 2409
coerce, 2409
complete, 2409
cos, 2409
cosh, 2409
cot, 2409
coth, 2409
csc, 2409
csch, 2409
csubst, 2409
D, 2409
degree, 2409
differentiate, 2409
eval, 2409
exp, 2409
exquo, 2409

extend, 2409
fintegrate, 2409
hash, 2409
integrate, 2409
latex, 2409
leadingCoefficient, 2409
leadingMonomial, 2409
log, 2409
map, 2409
monomial, 2409
monomial?, 2409
nthRoot, 2409
one?, 2409
order, 2409
pi, 2409
pole?, 2409
polynomial, 2409
recip, 2409
reductum, 2409
sample, 2409
sec, 2409
sech, 2409
sin, 2409
sinh, 2409
sqrt, 2409
subtractIfCan, 2409
tan, 2409
tanh, 2409
unit?, 2409
unitCanonical, 2409
unitNormal, 2409
variables, 2409
zero?, 2409
solid
COMPPROP, 2592
solid?
COMPPROP, 2592
solveLinearPolynomialEquation
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DMP, 560
DSMP, 529
EXPEXPAN, 682
FRAC, 956
GDMP, 1022
HDMP, 1150
HEXADEC, 1113
MCMPLX, 1511
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
POLY, 2044
RADIX, 2172
SDPOL, 2352
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
someBasis
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
Somos
GOPT, 1075
GOPT0, 1081
sort
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
GPOLSET, 1044
GTSET, 1054
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218

IVECTOR, 1229
LIST, 1472
PERM, 1916
POINT, 2026
PRIMARR, 2075
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
STRING, 2575
U32VEC, 2869
VECTOR, 2878
WUTSET, 2895
sorted?
ALIST, 221
ARRAY1, 1740
BITS, 299
CDFVEC, 419
DFVEC, 593
DLIST, 448
FARRAY, 856
IARRAY1, 1213
IBITS, 1169
IFARRAY, 1192
ILIST, 1201
ISTRING, 1218
IVECTOR, 1229
LIST, 1472
POINT, 2026
PRIMARR, 2075
STRING, 2575
U32VEC, 2869
VECTOR, 2878
space
CHAR, 359
DROPT, 596
SPACE3, 2700
?=?, 2701
?~=?, 2701
check, 2701
closedCurve, 2701
closedCurve?, 2701
coerce, 2701
components, 2701
composite, 2701
composites, 2701
copy, 2701
create3Space, 2701
curve, 2701
curve?, 2701
enterPointData, 2701
hash, 2701
latex, 2701
lllip, 2701
lllp, 2701
llprop, 2701
lp, 2701
lprop, 2701
merge, 2701
mesh, 2701
mesh?, 2701
modifyPointData, 2701
numberOfComponents, 2701
objects, 2701
point, 2701
point?, 2701
polygon, 2701
polygon?, 2701
subspace, 2701
SparseMultivariatePolynomial, 2390
SparseMultivariateTaylorSeries, 2408
SparseTable, 2418
SparseUnivariateLaurentSeries, 2424
SparseUnivariatePolynomial, 2434
SparseUnivariatePolynomialExpressions, 2448
SparseUnivariatePuiseuxSeries, 2454
SparseUnivariateSkewPolynomial, 2459
SparseUnivariateTaylorSeries, 2464
split
BSTREE, 287
DIV, 563
ISTRING, 1218
STRING, 2575
SplitHomogeneousDirectProduct, 2476
SplittingNode, 2479
SplittingTree, 2485
SPLNODE, 2479
?=?, 2479
?~=?, 2479
coerce, 2479
condition, 2479
construct, 2479
copy, 2479

empty, 2479
empty?, 2479
hash, 2479
infLex?, 2479
latex, 2479
setCondition, 2479
setEmpty, 2479
setStatus, 2479
setValue, 2479
status, 2479
subNode?, 2479
value, 2479
SPLTREE, 2485
?.value, 2485
?=?, 2485
?~=?, 2485
#?, 2485
any?, 2485
child?, 2485
children, 2485
coerce, 2485
conditions, 2485
construct, 2485
copy, 2485
count, 2485
cyclic?, 2485
distance, 2485
empty, 2485
empty?, 2485
eq?, 2485
eval, 2485
every?, 2485
extractSplittingLeaf, 2485
hash, 2485
latex, 2485
leaf?, 2485
leaves, 2485
less?, 2485
map, 2485
member?, 2485
members, 2485
more?, 2485
node?, 2485
nodeOf?, 2485
nodes, 2485
parts, 2485
remove, 2485
result, 2485
sample, 2485
setchildren, 2485
setelt, 2485
setvalue, 2485
size?, 2485
splitNodeOf, 2485
subNodeOf?, 2485
updateStatus, 2485
value, 2485
sqfrFactor
FR, 756
SQMATRIX, 2514
-?, 2515
?**?, 2515
?*?, 2515
?+?, 2515
?-?, 2515
?/?, 2515
?=?, 2515
?^?, 2515
?~=?, 2515
#?, 2515
0, 2515
1, 2515
antisymmetric?, 2515
any?, 2515
characteristic, 2515
coerce, 2515
column, 2515
convert, 2515
copy, 2515
count, 2515
D, 2515
determinant, 2515
diagonal, 2515
diagonal?, 2515
diagonalMatrix, 2515
diagonalProduct, 2515
differentiate, 2515
elt, 2515
empty, 2515
empty?, 2515
eq?, 2515
eval, 2515

every?, 2515
exquo, 2515
hash, 2515
inverse, 2515
latex, 2515
less?, 2515
listOfLists, 2515
map, 2515
matrix, 2515
maxColIndex, 2515
maxRowIndex, 2515
member?, 2515
members, 2515
minColIndex, 2515
minordet, 2515
minRowIndex, 2515
more?, 2515
ncols, 2515
nrows, 2515
nullity, 2515
nullSpace, 2515
one?, 2515
parts, 2515
qelt, 2515
rank, 2515
recip, 2515
reducedSystem, 2515
retract, 2515
retractIfCan, 2515
row, 2515
rowEchelon, 2515
sample, 2515
scalarMatrix, 2515
size?, 2515
square?, 2515
squareMatrix, 2515
subtractIfCan, 2515
symmetric?, 2515
trace, 2515
transpose, 2515
zero?, 2515

sqrt
AN, 35
BPADIC, 242
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
IAN, 1245
INTRVL, 1352
IPADIC, 1262
MCMPLX, 1511
MFLOAT, 1516
PADIC, 1847
RECLOS, 2203
SMTS, 2409
SULS, 2425
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854

square?
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515

squareFree
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694

EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
IPF, 1271
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
squareFreePart
ALGFF, 28
AN, 35
BINARY, 277
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252

INT, 1330
IPF, 1271
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
RADFF, 2160
RADIX, 2172
RECLOS, 2203
REGSET, 2252
RGCHAIN, 2221
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SREGSET, 2502
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
squareFreePolynomial
BINARY, 277
BPADICRT, 247
COMPLEX, 406
DECIMAL, 453
DMP, 560
DSMP, 529
EXPEXPAN, 682
EXPR, 694
FRAC, 956
GDMP, 1022
HDMP, 1150
HEXADEC, 1113
MCMPLX, 1511
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PADICRAT, 1852
PADICRC, 1857
POLY, 2044
RADIX, 2172
SDPOL, 2352
SMP, 2391
SULS, 2425
SUP, 2435
SUPEXPR, 2449
ULS, 2763
ULSCONS, 2771
UP, 2795
SquareFreeRegularTriangularSet, 2501
SquareMatrix, 2514
squareMatrix
SQMATRIX, 2515
squareTop
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
MATRIX, 1591
SREGSET, 2501
?=?, 2502
?~=?, 2502
#?, 2502
algebraic?, 2502
algebraicCoefficients?, 2502
algebraicVariables, 2502
any?, 2502

augment, 2502
autoReduced?, 2502
basicSet, 2502
coerce, 2502
coHeight, 2502
collect, 2502
collectQuasiMonic, 2502
collectUnder, 2502
collectUpper, 2502
construct, 2502
convert, 2502
copy, 2502
count, 2502
degree, 2502
empty, 2502
empty?, 2502
eq?, 2502
eval, 2502
every?, 2502
extend, 2502
extendIfCan, 2502
find, 2502
first, 2502
hash, 2502
headReduce, 2502
headReduced?, 2502
headRemainder, 2502
infRittWu?, 2502
initiallyReduce, 2502
initiallyReduced?, 2502
initials, 2502
internalAugment, 2502
internalZeroSetSplit, 2502
intersect, 2502
invertible?, 2502
invertibleElseSplit?, 2502
invertibleSet, 2502
last, 2502
lastSubResultant, 2502
lastSubResultantElseSplit, 2502
latex, 2502
less?, 2502
mainVariable?, 2502
mainVariables, 2502
map, 2502
member?, 2502
members, 2502
more?, 2502
mvar, 2502
normalized?, 2502
parts, 2502
preprocess, 2502
purelyAlgebraic?, 2502
purelyAlgebraicLeadingMonomial?, 2502
purelyTranscendental?, 2502
quasiComponent, 2502
reduce, 2502
reduceByQuasiMonic, 2502
reduced?, 2502
remainder, 2502
remove, 2502
removeDuplicates, 2502
removeZero, 2502
rest, 2502
retract, 2502
retractIfCan, 2502
rewriteIdealWithHeadRemainder, 2502
rewriteIdealWithRemainder, 2502
rewriteSetWithReduction, 2502
roughBase?, 2502
roughEqualIdeals?, 2502
roughSubIdeal?, 2502
roughUnitIdeal?, 2502
sample, 2502
select, 2502
size?, 2502
sort, 2502
squareFreePart, 2502
stronglyReduce, 2502
stronglyReduced?, 2502
triangular?, 2502
trivialIdeal?, 2502
variables, 2502
zeroSetSplit, 2502
zeroSetSplitIntoTriangularSystems, 2502
STACK, 2530
?=?, 2530
?~=?, 2530
#?, 2530
any?, 2530
bag, 2530
coerce, 2530

copy, 2530
count, 2530
depth, 2530
empty, 2530
empty?, 2530
eq?, 2530
eval, 2530
every?, 2530
extract, 2530
hash, 2530
insert, 2530
inspect, 2530
latex, 2530
less?, 2530
map, 2530
member?, 2530
members, 2530
more?, 2530
parts, 2530
pop, 2530
push, 2530
sample, 2530
size?, 2530
stack, 2530
top, 2530
Stack, 2530
stack
STACK, 2530
status
QALGSET, 2123
SPLNODE, 2479
statusIto
SD, 2540
STBL, 2418
?.?, 2418
?=?, 2418
?~=?, 2418
#?, 2418
any?, 2418
bag, 2418
coerce, 2418
construct, 2418
convert, 2418
copy, 2418
count, 2418
dictionary, 2418
elt, 2418
empty, 2418
empty?, 2418
entries, 2418
entry?, 2418
eq?, 2418
eval, 2418
every?, 2418
extract, 2418
fill, 2418
find, 2418
first, 2418
hash, 2418
index?, 2418
indices, 2418
insert, 2418
inspect, 2418
key?, 2418
keys, 2418
latex, 2418
less?, 2418
map, 2418
maxIndex, 2418
member?, 2418
members, 2418
minIndex, 2418
more?, 2418
parts, 2418
qelt, 2418
qsetelt, 2418
reduce, 2418
remove, 2418
removeDuplicates, 2418
sample, 2418
search, 2418
select, 2418
setelt, 2418
size?, 2418
swap, 2418
table, 2418
StochasticDifferential, 2539
stop
FC, 902
STREAM, 2549
?.?, 2550
?.first, 2550

?.last, 2550
?.rest, 2550
?.value, 2550
?=?, 2550
?~=?, 2550
#?, 2550
any?, 2550
child?, 2550
children, 2550
coerce, 2550
complete, 2550
concat, 2550
cons, 2550
construct, 2550
convert, 2550
copy, 2550
count, 2550
cycleEntry, 2550
cycleLength, 2550
cycleSplit, 2550
cycleTail, 2550
cyclic?, 2550
delay, 2550
delete, 2550
distance, 2550
elt, 2550
empty, 2550
empty?, 2550
entries, 2550
entry?, 2550
eq?, 2550
eval, 2550
every?, 2550
explicitEntries?, 2550
explicitlyEmpty?, 2550
explicitlyFinite?, 2550
extend, 2550
fill, 2550
filterUntil, 2550
filterWhile, 2550
find, 2550
findCycle, 2550
first, 2550
frst, 2550
generate, 2550
hash, 2550
index?, 2550
indices, 2550
insert, 2550
last, 2550
latex, 2550
lazy?, 2550
lazyEvaluate, 2550
leaf?, 2550
leaves, 2550
less?, 2550
map, 2550
maxIndex, 2550
member?, 2550
members, 2550
minIndex, 2550
more?, 2550
new, 2550
node?, 2550
nodes, 2550
numberOfComputedEntries, 2550
output, 2550
parts, 2550
possiblyInfinite?, 2550
qelt, 2550
qsetelt, 2550
reduce, 2550
remove, 2550
removeDuplicates, 2550
repeating, 2550
repeating?, 2550
rest, 2550
rst, 2550
sample, 2550
second, 2550
select, 2550
setchildren, 2550
setelt, 2550
setfirst, 2550
setlast, 2550
setrest, 2550
setvalue, 2550
showAll?, 2550
showAllElements, 2550
size?, 2550
split, 2550
swap, 2550

tail, 2550
third, 2550
value, 2550
Stream, 2549
STRING, 2574
?<?, 2575
?<=?, 2575
?>?, 2575
?>=?, 2575
?.?, 2575
?=?, 2575
?~=?, 2575
#?, 2575
any?, 2575
coerce, 2575
concat, 2575
construct, 2575
convert, 2575
copy, 2575
copyInto, 2575
count, 2575
delete, 2575
elt, 2575
empty, 2575
empty?, 2575
entries, 2575
entry?, 2575
eq?, 2575
eval, 2575
every?, 2575
fill, 2575
find, 2575
first, 2575
hash, 2575
index?, 2575
indices, 2575
insert, 2575
latex, 2575
leftTrim, 2575
less?, 2575
lowerCase, 2575
map, 2575
match, 2575
match?, 2575
max, 2575
maxIndex, 2575
member?, 2575
members, 2575
merge, 2575
min, 2575
minIndex, 2575
more?, 2575
new, 2575
OMwrite, 2575
parts, 2575
position, 2575
prefix?, 2575
qelt, 2575
qsetelt, 2575
reduce, 2575
removeDuplicates, 2575
replace, 2575
reverse, 2575
rightTrim, 2575
sample, 2575
select, 2575
setelt, 2575
size?, 2575
sort, 2575
sorted?, 2575
split, 2575
string, 2575
substring?, 2575
suffix?, 2575
swap, 2575
trim, 2575
upperCase, 2575
String, 2574
string
INFORM, 1311
OUTFORM, 1834
SEX, 2360
SEXOF, 2363
STRING, 2575
SYMBOL, 2608
String , 1545
string?
INFORM, 1311
SEX, 2360
SEXOF, 2363
StringTable, 2578
strongGenerators

PERMGRP, 1926
stronglyReduce
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
stronglyReduced?
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
STRTBL, 2578
?.?, 2578
?=?, 2578
?~=?, 2578
#?, 2578
any?, 2578
bag, 2578
coerce, 2578
construct, 2578
convert, 2578
copy, 2578
count, 2578
dictionary, 2578
elt, 2578
empty, 2578
empty?, 2578
entries, 2578
entry?, 2578
eq?, 2578
eval, 2578
every?, 2578
extract, 2578
fill, 2578
find, 2578
first, 2578
hash, 2578
index?, 2578
indices, 2578
insert, 2578
inspect, 2578
key?, 2578
keys, 2578
latex, 2578
less?, 2578
map, 2578
maxIndex, 2578
member?, 2578
members, 2578
minIndex, 2578
more?, 2578
parts, 2578
qelt, 2578
qsetelt, 2578
reduce, 2578
remove, 2578
removeDuplicates, 2578
sample, 2578
search, 2578
select, 2578
setelt, 2578
size?, 2578
swap, 2578
table, 2578
structuralConstants
ALGSC, 15
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
style
DROPT, 596
sub
OUTFORM, 1834
subHeight
OUTFORM, 1834
subMatrix
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
MATRIX, 1591
submod
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
subMultV
IC, 1161
INFCLSPS, 1240

INFCLSPT, 1234
subNode?
SPLNODE, 2479
subNodeOf?
SPLTREE, 2485
subResultantChain
NSMP, 1681
subResultantGcd
MODMON, 1600
MYUP, 1663
NSMP, 1681
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
subResultantsChain
NSUP, 1696
subscript
SYMBOL, 2608
subset?
CCLASS, 368
MSET, 1638
SET, 2338
SUBSPACE, 2582
?=?, 2582
? =?, 2582
addPoint, 2582
addPoint2, 2582
addPointLast, 2582
birth, 2582
child, 2582
children, 2582
closeComponent, 2582
coerce, 2582
deepCopy, 2582
defineProperty, 2582
extractClosed, 2582
extractIndex, 2582
extractPoint, 2582
extractProperty, 2582
hash, 2582
internal?, 2582
latex, 2582
leaf?, 2582
level, 2582
merge, 2582
modifyPoint, 2582
new, 2582
numberOfChildren, 2582
parent, 2582
pointData, 2582
root?, 2582
separate, 2582
shallowCopy, 2582
subspace, 2582
traverse, 2582
SubSpace, 2582
subspace
SPACE3, 2701
SUBSPACE, 2582
VIEW3D, 2679
SubSpaceComponentProperty, 2592
subst
AN, 35
EQ, 661
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
substitute
LMDICT, 1483
substring?
ISTRING, 1218
STRING, 2575
subtractIfCan
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
BINARY, 277
BPADIC, 242
BPADICRT, 247
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DIV, 563
DMP, 560

DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FM, 983
FM1, 987
FNLA, 997
FR, 756
FRAC, 956
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IDPAG, 1172
IDPOAMS, 1185
IFAMON, 1255
IFF, 1252
INDE, 1187
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISUPS, 1279
ITAYLOR, 1306
JORDAN, 209
LA, 1488
LAUPOL, 1390
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609
MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880

POLY, 2044
PR, 2058
PRODUCT, 2079
PRTITION, 1889
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
SUCH, 2595
?=?, 2595
?~=?, 2595
coerce, 2595
construct, 2595
hash, 2595
latex, 2595
lhs, 2595
rhs, 2595
SuchThat, 2595
suchThat
RULE, 2271
suffix?
ISTRING, 1218
STRING, 2575
SULS, 2424
-?, 2425
?<?, 2425
?<=?, 2425
?>?, 2425
?>=?, 2425
?**?, 2425
?*?, 2425
?+?, 2425
?-?, 2425
?.?, 2425
?/?, 2425
?=?, 2425
?^?, 2425
?~=?, 2425
?quo?, 2425
?rem?, 2425
0, 2425
1, 2425
abs, 2425
acos, 2425
acosh, 2425
acot, 2425
acoth, 2425
acsc, 2425
acsch, 2425
approximate, 2425
asec, 2425
asech, 2425
asin, 2425
asinh, 2425
associates?, 2425
atan, 2425
atanh, 2425

ceiling, 2425
center, 2425
characteristic, 2425
charthRoot, 2425
coefficient, 2425
coerce, 2425
complete, 2425
conditionP, 2425
convert, 2425
cos, 2425
cosh, 2425
cot, 2425
coth, 2425
csc, 2425
csch, 2425
D, 2425
degree, 2425
denom, 2425
denominator, 2425
differentiate, 2425
divide, 2425
euclideanSize, 2425
eval, 2425
exp, 2425
expressIdealMember, 2425
exquo, 2425
extend, 2425
extendedEuclidean, 2425
factor, 2425
factorPolynomial, 2425
factorSquareFreePolynomial, 2425
floor, 2425
fractionPart, 2425
gcd, 2425
gcdPolynomial, 2425
hash, 2425
init, 2425
integrate, 2425
inv, 2425
latex, 2425
laurent, 2425
lcm, 2425
leadingCoefficient, 2425
leadingMonomial, 2425
log, 2425
map, 2425
max, 2425
min, 2425
monomial, 2425
monomial?, 2425
multiEuclidean, 2425
multiplyCoefficients, 2425
multiplyExponents, 2425
negative?, 2425
nextItem, 2425
nthRoot, 2425
numer, 2425
numerator, 2425
one?, 2425
order, 2425
patternMatch, 2425
pi, 2425
pole?, 2425
positive?, 2425
prime?, 2425
principalIdeal, 2425
random, 2425
rationalFunction, 2425
recip, 2425
reducedSystem, 2425
reductum, 2425
removeZeroes, 2425
retract, 2425
retractIfCan, 2425
sample, 2425
sec, 2425
sech, 2425
series, 2425
sign, 2425
sin, 2425
sinh, 2425
sizeLess?, 2425
solveLinearPolynomialEquation, 2425
sqrt, 2425
squareFree, 2425
squareFreePart, 2425
squareFreePolynomial, 2425
subtractIfCan, 2425
tan, 2425
tanh, 2425
taylor, 2425
taylorIfCan, 2425

taylorRep, 2425
terms, 2425
truncate, 2425
unit?, 2425
unitCanonical, 2425
unitNormal, 2425
variable, 2425
variables, 2425
wholePart, 2425
zero?, 2425
sum
OUTFORM, 1834
summation
EXPR, 694
MYEXPR, 1656
SUP, 2434
-?, 2435
?<?, 2435
?<=?, 2435
?>?, 2435
?>=?, 2435
?**?, 2435
?*?, 2435
?+?, 2435
?-?, 2435
?.?, 2435
?/?, 2435
?=?, 2435
?^?, 2435
?~=?, 2435
?quo?, 2435
?rem?, 2435
0, 2435
1, 2435
associates?, 2435
binomThmExpt, 2435
characteristic, 2435
charthRoot, 2435
coefficient, 2435
coefficients, 2435
coerce, 2435
composite, 2435
conditionP, 2435
content, 2435
convert, 2435
D, 2435
degree, 2435
differentiate, 2435
discriminant, 2435
divide, 2435
divideExponents, 2435
elt, 2435
euclideanSize, 2435
eval, 2435
expressIdealMember, 2435
exquo, 2435
extendedEuclidean, 2435
factor, 2435
factorPolynomial, 2435
factorSquareFreePolynomial, 2435
fmecg, 2435
gcd, 2435
gcdPolynomial, 2435
ground, 2435
ground?, 2435
hash, 2435
init, 2435
integrate, 2435
isExpt, 2435
isPlus, 2435
isTimes, 2435
karatsubaDivide, 2435
latex, 2435
lcm, 2435
leadingCoefficient, 2435
leadingMonomial, 2435
mainVariable, 2435
makeSUP, 2435
map, 2435
mapExponents, 2435
max, 2435
min, 2435
minimumDegree, 2435
monicDivide, 2435
monomial, 2435
monomial?, 2435
monomials, 2435
multiEuclidean, 2435
multiplyExponents, 2435
multivariate, 2435
nextItem, 2435
numberOfMonomials, 2435

one?, 2435
order, 2435
outputForm, 2435
patternMatch, 2435
pomopo, 2435
prime?, 2435
primitiveMonomials, 2435
primitivePart, 2435
principalIdeal, 2435
pseudoDivide, 2435
pseudoQuotient, 2435
pseudoRemainder, 2435
recip, 2435
reducedSystem, 2435
reductum, 2435
resultant, 2435
retract, 2435
retractIfCan, 2435
sample, 2435
separate, 2435
shiftLeft, 2435
shiftRight, 2435
sizeLess?, 2435
solveLinearPolynomialEquation, 2435
squareFree, 2435
squareFreePart, 2435
squareFreePolynomial, 2435
subResultantGcd, 2435
subtractIfCan, 2435
totalDegree, 2435
unit?, 2435
unitCanonical, 2435
unitNormal, 2435
univariate, 2435
unmakeSUP, 2435
variables, 2435
vectorise, 2435
zero?, 2435

sup
DIRPROD, 534
DPMM, 540
DPMO, 545
HDP, 1143
IDPOAMS, 1185
INDE, 1187
INTRVL, 1352
NNI, 1706
ODP, 1783
PRODUCT, 2079
SHDP, 2476

super
OUTFORM, 1834

superHeight
OUTFORM, 1834

superscript
SYMBOL, 2608

supersub
OUTFORM, 1834

SUPEXPR, 2448
-?, 2449
?<?, 2449
?<=?, 2449
?>?, 2449
?>=?, 2449
?**?, 2449
?*?, 2449
?+?, 2449
?-?, 2449
?.?, 2449
?/?, 2449
?=?, 2449
?^?, 2449
?~=?, 2449
?quo?, 2449
?rem?, 2449
0, 2449
1, 2449
acos, 2449
acosh, 2449
acot, 2449
acoth, 2449
acsc, 2449
acsch, 2449
asec, 2449
asech, 2449
asin, 2449
asinh, 2449
associates?, 2449
atan, 2449
atanh, 2449
binomThmExpt, 2449
characteristic, 2449

charthRoot, 2449
coefficient, 2449
coefficients, 2449
coerce, 2449
composite, 2449
conditionP, 2449
content, 2449
convert, 2449
cos, 2449
cosh, 2449
cot, 2449
coth, 2449
csc, 2449
csch, 2449
D, 2449
degree, 2449
differentiate, 2449
discriminant, 2449
divide, 2449
divideExponents, 2449
elt, 2449
euclideanSize, 2449
eval, 2449
exp, 2449
expressIdealMember, 2449
exquo, 2449
extendedEuclidean, 2449
factor, 2449
factorPolynomial, 2449
factorSquareFreePolynomial, 2449
gcd, 2449
gcdPolynomial, 2449
ground, 2449
ground?, 2449
hash, 2449
init, 2449
integrate, 2449
isExpt, 2449
isPlus, 2449
isTimes, 2449
karatsubaDivide, 2449
latex, 2449
lcm, 2449
leadingCoefficient, 2449
leadingMonomial, 2449
log, 2449
mainVariable, 2449
makeSUP, 2449
map, 2449
mapExponents, 2449
max, 2449
min, 2449
minimumDegree, 2449
monicDivide, 2449
monomial, 2449
monomial?, 2449
monomials, 2449
multiEuclidean, 2449
multiplyExponents, 2449
multivariate, 2449
nextItem, 2449
numberOfMonomials, 2449
one?, 2449
order, 2449
patternMatch, 2449
pi, 2449
pomopo, 2449
prime?, 2449
primitiveMonomials, 2449
primitivePart, 2449
principalIdeal, 2449
pseudoDivide, 2449
pseudoQuotient, 2449
pseudoRemainder, 2449
recip, 2449
reducedSystem, 2449
reductum, 2449
resultant, 2449
retract, 2449
retractIfCan, 2449
sample, 2449
sec, 2449
sech, 2449
separate, 2449
shiftLeft, 2449
shiftRight, 2449
sin, 2449
sinh, 2449
sizeLess?, 2449
solveLinearPolynomialEquation, 2449
squareFree, 2449
squareFreePart, 2449

squareFreePolynomial, 2449
subResultantGcd, 2449
subtractIfCan, 2449
tan, 2449
tanh, 2449
totalDegree, 2449
unit?, 2449
unitCanonical, 2449
unitNormal, 2449
univariate, 2449
unmakeSUP, 2449
variables, 2449
vectorise, 2449
zero?, 2449
supp
DIV, 563
suppOfPole
DIV, 563
suppOfZero
DIV, 563
supRittWu?
NSMP, 1681
SUPXS, 2454
-?, 2455
?**?, 2455
?*?, 2455
?+?, 2455
?-?, 2455
?.?, 2455
?/?, 2455
?=?, 2455
?^?, 2455
?~=?, 2455
?quo?, 2455
?rem?, 2455
0, 2455
1, 2455
acos, 2455
acosh, 2455
acot, 2455
acoth, 2455
acsc, 2455
acsch, 2455
approximate, 2455
asec, 2455
asech, 2455
asin, 2455
asinh, 2455
associates?, 2455
atan, 2455
atanh, 2455
center, 2455
characteristic, 2455
charthRoot, 2455
coefficient, 2455
coerce, 2455
complete, 2455
cos, 2455
cosh, 2455
cot, 2455
coth, 2455
csc, 2455
csch, 2455
D, 2455
degree, 2455
differentiate, 2455
divide, 2455
euclideanSize, 2455
eval, 2455
exp, 2455
expressIdealMember, 2455
exquo, 2455
extend, 2455
extendedEuclidean, 2455
factor, 2455
gcd, 2455
gcdPolynomial, 2455
hash, 2455
integrate, 2455
inv, 2455
latex, 2455
laurent, 2455
laurentIfCan, 2455
laurentRep, 2455
lcm, 2455
leadingCoefficient, 2455
leadingMonomial, 2455
log, 2455
map, 2455
monomial, 2455
monomial?, 2455
multiEuclidean, 2455

multiplyExponents, 2455
nthRoot, 2455
one?, 2455
order, 2455
pi, 2455
pole?, 2455
prime?, 2455
principalIdeal, 2455
puiseux, 2455
rationalPower, 2455
recip, 2455
reductum, 2455
retract, 2455
retractIfCan, 2455
sample, 2455
sec, 2455
sech, 2455
series, 2455
sin, 2455
sinh, 2455
sizeLess?, 2455
sqrt, 2455
squareFree, 2455
squareFreePart, 2455
subtractIfCan, 2455
tan, 2455
tanh, 2455
terms, 2455
truncate, 2455
unit?, 2455
unitCanonical, 2455
unitNormal, 2455
variable, 2455
variables, 2455
zero?, 2455
surface
PARSURF, 1870
SUTS, 2464
-?, 2464
?**?, 2464
?*?, 2464
?+?, 2464
?-?, 2464
?.?, 2464
?/?, 2464
?=?, 2464
?^?, 2464
?~=?, 2464
0, 2464
1, 2464
acos, 2464
acosh, 2464
acot, 2464
acoth, 2464
acsc, 2464
acsch, 2464
approximate, 2464
asec, 2464
asech, 2464
asin, 2464
asinh, 2464
associates?, 2464
atan, 2464
atanh, 2464
center, 2464
characteristic, 2464
charthRoot, 2464
coefficient, 2464
coefficients, 2464
coerce, 2464
complete, 2464
cos, 2464
cosh, 2464
cot, 2464
coth, 2464
csc, 2464
csch, 2464
D, 2464
degree, 2464
differentiate, 2464
eval, 2464
exp, 2464
exquo, 2464
extend, 2464
hash, 2464
integrate, 2464
latex, 2464
leadingCoefficient, 2464
leadingMonomial, 2464
log, 2464
map, 2464
monomial, 2464

monomial?, 2464
multiplyCoefficients, 2464
multiplyExponents, 2464
nthRoot, 2464
one?, 2464
order, 2464
pi, 2464
pole?, 2464
polynomial, 2464
quoByVar, 2464
recip, 2464
reductum, 2464
sample, 2464
sec, 2464
sech, 2464
series, 2464
sin, 2464
sinh, 2464
sqrt, 2464
subtractIfCan, 2464
tan, 2464
tanh, 2464
terms, 2464
truncate, 2464
unit?, 2464
unitCanonical, 2464
unitNormal, 2464
univariatePolynomial, 2464
variable, 2464
variables, 2464
zero?, 2464
swap
EQ, 661
SWITCH, 2597
AND, 2597
coerce, 2597
EQ, 2597
GE, 2597
GT, 2597
LE, 2597
LT, 2597
NOT, 2597
OR, 2597
Switch, 2597
symbNameV
IC, 1161
INFCLSPS, 1240
INFCLSPT, 1234
SYMBOL, 2608
?<?, 2608
?<=?, 2608
?>?, 2608
?>=?, 2608
?.?, 2608
?=?, 2608
?~=?, 2608
argscript, 2608
coerce, 2608
convert, 2608
hash, 2608
latex, 2608
list, 2608
max, 2608
min, 2608
name, 2608
new, 2608
OMwrite, 2608
patternMatch, 2608
resetNew, 2608
sample, 2608
script, 2608
scripted?, 2608
scripts, 2608
string, 2608
subscript, 2608
superscript, 2608
Symbol, 2608
symbol
INFORM, 1311
SEX, 2360
SEXOF, 2363
symbol?
INFORM, 1311
PATTERN, 1894
SEX, 2360
SEXOF, 2363
symbolIfCan
KERNEL, 1372
SymbolTable, 2616
symbolTable
SYMTAB, 2616
symbolTableOf

SYMS, 2665
symmetric?
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
LSQM, 1424
MATRIX, 1591
RMATRIX, 2212
SQMATRIX, 2515
symmetricDifference
CCLASS, 368
MSET, 1638
SET, 2338
SymmetricPolynomial, 2622
symmetricPower
LODO, 1437
LODO1, 1447
LODO2, 1459
symmetricProduct
LODO, 1437
LODO1, 1447
LODO2, 1459
symmetricRemainder
INT, 1330
MINT, 1525
ROMAN, 2293
SINT, 2380
symmetricSquare
LODO, 1437
LODO1, 1447
LODO2, 1459
SYMPOLY, 2622
-?, 2622
?**?, 2622
?*?, 2622
?+?, 2622
?-?, 2622
?/?, 2622
?=?, 2622
?^?, 2622
?~=?, 2622
0, 2622
1, 2622
associates?, 2622
binomThmExpt, 2622
characteristic, 2622
charthRoot, 2622
coefficient, 2622
coefficients, 2622
coerce, 2622
content, 2622
degree, 2622
exquo, 2622
fmecg, 2622
ground, 2622
ground?, 2622
hash, 2622
latex, 2622
leadingCoefficient, 2622
leadingMonomial, 2622
map, 2622
mapExponents, 2622
minimumDegree, 2622
monomial, 2622
monomial?, 2622
numberOfMonomials, 2622
one?, 2622
pomopo, 2622
primitivePart, 2622
recip, 2622
reductum, 2622
retract, 2622
retractIfCan, 2622
sample, 2622
subtractIfCan, 2622
unit?, 2622
unitCanonical, 2622
unitNormal, 2622
zero?, 2622
SYMS, 2665
argumentList, 2665
argumentListOf, 2665
clearTheSymbolTable, 2665
coerce, 2665
currentSubProgram, 2665
declare, 2665
empty, 2665
endSubProgram, 2665
newSubProgram, 2665
printHeader, 2665
printTypes, 2665

returnType, 2665
returnTypeOf, 2665
showTheSymbolTable, 2665
symbolTableOf, 2665
SYMTAB, 2616
coerce, 2616
declare, 2616
empty, 2616
externalList, 2616
fortranTypeOf, 2616
newTypeLists, 2616
parametersOf, 2616
printTypes, 2616
symbolTable, 2616
typeList, 2616
typeLists, 2616

TABLE, 2631
?.?, 2632
?=?, 2632
?~=?, 2632
#?, 2632
any?, 2632
bag, 2632
coerce, 2632
construct, 2632
convert, 2632
copy, 2632
count, 2632
dictionary, 2632
elt, 2632
empty, 2632
empty?, 2632
entries, 2632
entry?, 2632
eq?, 2632
eval, 2632
every?, 2632
extract, 2632
fill, 2632
find, 2632
first, 2632
hash, 2632
index?, 2632
indices, 2632
insert, 2632
inspect, 2632
key?, 2632
keys, 2632
latex, 2632
less?, 2632
map, 2632
maxIndex, 2632
member?, 2632
members, 2632
minIndex, 2632
more?, 2632
parts, 2632
qelt, 2632
qsetelt, 2632
reduce, 2632
remove, 2632
removeDuplicates, 2632
sample, 2632
search, 2632
select, 2632
setelt, 2632
size?, 2632
swap, 2632
table, 2632
Table, 2631
table
ALIST, 221
EQTBL, 669
GSTBL, 1049
HASHTBL, 1090
INTABL, 1304
KAFILE, 1382
LIB, 1397
RESULT, 2267
ROUTINE, 2298
STBL, 2418
STRTBL, 2578
TABLE, 2632
TABLEAU, 2634
coerce, 2634
listOfLists, 2634
tableau, 2634
Tableau, 2634
tableau
TABLEAU, 2634
tableForDiscreteLogarithm

ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
MCMPLX, 1511
PACOFF, 2102
PF, 2071
RADFF, 2160
SAE, 2368
tail
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
NSMP, 1681
STREAM, 2550
tan
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
tanh
COMPLEX, 406
DFLOAT, 575
EXPR, 694
EXPUPXS, 710
FEXPR, 917
FLOAT, 879
GSERIES, 1061
INTRVL, 1352
MCMPLX, 1511
SMTS, 2409
SULS, 2425
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
taylor
SULS, 2425
ULS, 2763
ULSCONS, 2771
taylorIfCan
SULS, 2425
ULS, 2763
ULSCONS, 2771
taylorQuoByVar
ISUPS, 1279
taylorRep
SULS, 2425
ULS, 2763
ULSCONS, 2771
TaylorSeries, 2638
terms
DIV, 563
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978

GSERIES, 1061
IFAMON, 1255
ISUPS, 1279
MRING, 1626
NSDPS, 1670
SULS, 2425
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
test
BOOLEAN, 307
TEX, 2645
?=?, 2645
?~=?, 2645
coerce, 2645
convert, 2645
display, 2645
epilogue, 2645
hash, 2645
latex, 2645
new, 2645
prologue, 2645
setEpilogue, 2645
setPrologue, 2645
setTex, 2645
tex, 2645
tex
TEX, 2645
TexFormat, 2645
TexFormat , 1541–1543
TexFormat1 , 1543
TEXTFILE, 2661
?=?, 2661
?~=?, 2661
close, 2661
coerce, 2661
endOfFile?, 2661
hash, 2661
iomode, 2661
latex, 2661
name, 2661
open, 2661
read, 2661
readIfCan, 2661
readLine, 2661
readLineIfCan, 2661
reopen, 2661
write, 2661
writeLine, 2661
TextFile, 2661
TheSymbolTable, 2665
third
ALIST, 221
DLIST, 448
ILIST, 1201
LIST, 1472
NSDPS, 1670
STREAM, 2550
ThreeDimensionalMatrix, 2671
ThreeDimensionalViewport, 2679
ThreeSpace, 2700
title
DROPT, 596
VIEW2d, 2739
VIEW3D, 2679
top
ASTACK, 65
DEQUEUE, 499
STACK, 2530
topPredicate
PATTERN, 1894
toScale
DROPT, 596
totalDegree
DMP, 560
DSMP, 529
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352

SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
totalDifferential
DERHAM, 517
tower
AN, 35
EXPR, 694
FEXPR, 917
IAN, 1245
MYEXPR, 1656
trace
ALGFF, 28
COMPLEX, 406
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
LSQM, 1424
MCMPLX, 1511
PF, 2071
RADFF, 2160
SAE, 2368
SQMATRIX, 2515
traceMatrix
ALGFF, 28
COMPLEX, 406
MCMPLX, 1511
RADFF, 2160
SAE, 2368
trailingCoefficient
LAUPOL, 1390
tRange
PLOT, 1995
PLOT3D, 2008
transcendenceDegree
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PACOFF, 2102
PACRAT, 2112
PF, 2071
transcendent?
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
IFF, 1252
IPF, 1271
PACOFF, 2102
PACRAT, 2112
PF, 2071
transCoord
BLHN, 301
BLQT, 304
translate
DHMATRIX, 479
VIEW2d, 2739
VIEW3D, 2679
transpose
CARTEN, 342
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
MATRIX, 1591
SQMATRIX, 2515
traverse
SUBSPACE, 2582
TREE, 2710
?.value, 2710

?=?, 2710
?~=?, 2710
#?, 2710
any?, 2710
child?, 2710
children, 2710
coerce, 2710
copy, 2710
count, 2710
cyclic?, 2710
cyclicCopy, 2710
cyclicEntries, 2710
cyclicEqual?, 2710
cyclicParents, 2710
distance, 2710
empty, 2710
empty?, 2710
eq?, 2710
eval, 2710
every?, 2710
hash, 2710
latex, 2710
leaf?, 2710
leaves, 2710
less?, 2710
map, 2710
member?, 2710
members, 2710
more?, 2710
node?, 2710
nodes, 2710
parts, 2710
sample, 2710
setchildren, 2710
setelt, 2710
setvalue, 2710
size?, 2710
tree, 2710
value, 2710
Tree, 2710
tree
DSTREE, 522
TREE, 2710
triangular?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
trim
ISTRING, 1218
STRING, 2575
trivialIdeal?
GPOLSET, 1044
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
true
BOOLEAN, 307
trueEqual
IAN, 1245
trunc
LPOLY, 1415
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
truncate
DFLOAT, 575
EXPUPXS, 710
FLOAT, 879
GSERIES, 1061
ISUPS, 1279
MFLOAT, 1516
NSDPS, 1670
SULS, 2425
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
TS, 2638
-?, 2639
?**?, 2639
?*?, 2639

?+?, 2639
?-?, 2639
?/?, 2639
?=?, 2639
?^?, 2639
?~=?, 2639
0, 2639
1, 2639
acos, 2639
acosh, 2639
acot, 2639
acoth, 2639
acsc, 2639
acsch, 2639
asec, 2639
asech, 2639
asin, 2639
asinh, 2639
associates?, 2639
atan, 2639
atanh, 2639
characteristic, 2639
charthRoot, 2639
coefficient, 2639
coerce, 2639
complete, 2639
cos, 2639
cosh, 2639
cot, 2639
coth, 2639
csc, 2639
csch, 2639
D, 2639
degree, 2639
differentiate, 2639
eval, 2639
exp, 2639
exquo, 2639
extend, 2639
fintegrate, 2639
hash, 2639
integrate, 2639
latex, 2639
leadingCoefficient, 2639
leadingMonomial, 2639
log, 2639
map, 2639
monomial, 2639
monomial?, 2639
nthRoot, 2639
one?, 2639
order, 2639
pi, 2639
pole?, 2639
polynomial, 2639
recip, 2639
reductum, 2639
sample, 2639
sec, 2639
sech, 2639
sin, 2639
sinh, 2639
sqrt, 2639
subtractIfCan, 2639
tan, 2639
tanh, 2639
unit?, 2639
unitCanonical, 2639
unitNormal, 2639
variables, 2639
zero?, 2639
TUBE, 2718
closed?, 2718
getCurve, 2718
listLoops, 2718
open?, 2718
setClosed, 2718
tube, 2718
tube
TUBE, 2718
TubePlot, 2718
tubePoints
DROPT, 596
tubeRadius
DROPT, 596
TUPLE, 2721
?=?, 2721
?~=?, 2721
coerce, 2721
hash, 2721
latex, 2721
length, 2721

select, 2721
Tuple, 2721
tValues
PLOT3D, 2008
TwoDimensionalArray, 2732
TwoDimensionalViewport, 2738
type
BLHN, 301
BLQT, 304
typeList
SYMTAB, 2616
typeLists
SYMTAB, 2616

U32VEC, 2868
?<?, 2869
?<=?, 2869
?>?, 2869
?>=?, 2869
?.?, 2869
?=?, 2869
?~=?, 2869
#?, 2869
any?, 2869
coerce, 2869
concat, 2869
construct, 2869
convert, 2869
copy, 2869
copyInto, 2869
count, 2869
delete, 2869
elt, 2869
empty, 2869
empty?, 2869
entries, 2869
entry?, 2869
eq?, 2869
eval, 2869
every?, 2869
fill, 2869
find, 2869
first, 2869
hash, 2869
index?, 2869
indices, 2869
insert, 2869
latex, 2869
less?, 2869
map, 2869
max, 2869
maxIndex, 2869
member?, 2869
members, 2869
merge, 2869
min, 2869
minIndex, 2869
more?, 2869
new, 2869
parts, 2869
position, 2869
qelt, 2869
qsetelt, 2869
reduce, 2869
remove, 2869
removeDuplicates, 2869
reverse, 2869
sample, 2869
select, 2869
setelt, 2869
size?, 2869
sort, 2869
sorted?, 2869
swap, 2869
U32Vector, 2868
UFPS, 2756
-?, 2757
?**?, 2757
?*?, 2757
?+?, 2757
?-?, 2757
?.?, 2757
?/?, 2757
?=?, 2757
?^?, 2757
?~=?, 2757
0, 2757
1, 2757
acos, 2757
acosh, 2757
acot, 2757
acoth, 2757

acsc, 2757
acsch, 2757
approximate, 2757
asec, 2757
asech, 2757
asin, 2757
asinh, 2757
associates?, 2757
atan, 2757
atanh, 2757
center, 2757
characteristic, 2757
charthRoot, 2757
coefficient, 2757
coefficients, 2757
coerce, 2757
complete, 2757
cos, 2757
cosh, 2757
cot, 2757
coth, 2757
csc, 2757
csch, 2757
D, 2757
degree, 2757
differentiate, 2757
eval, 2757
evenlambert, 2757
exp, 2757
exquo, 2757
extend, 2757
generalLambert, 2757
hash, 2757
integrate, 2757
invmultisect, 2757
lagrange, 2757
lambert, 2757
latex, 2757
leadingCoefficient, 2757
leadingMonomial, 2757
log, 2757
map, 2757
monomial, 2757
monomial?, 2757
multiplyCoefficients, 2757
multiplyExponents, 2757
multisect, 2757
nthRoot, 2757
oddlambert, 2757
one?, 2757
order, 2757
pi, 2757
pole?, 2757
polynomial, 2757
quoByVar, 2757
recip, 2757
reductum, 2757
revert, 2757
sample, 2757
sec, 2757
sech, 2757
series, 2757
sin, 2757
sinh, 2757
sqrt, 2757
subtractIfCan, 2757
tan, 2757
tanh, 2757
terms, 2757
truncate, 2757
unit?, 2757
unitCanonical, 2757
unitNormal, 2757
univariatePolynomial, 2757
variable, 2757
variables, 2757
zero?, 2757
ULS, 2762
-?, 2763
?<?, 2763
?<=?, 2763
?>?, 2763
?>=?, 2763
?**?, 2763
?*?, 2763
?+?, 2763
?-?, 2763
?.?, 2763
?/?, 2763
?=?, 2763
?^?, 2763
?~=?, 2763

?quo?, 2763
?rem?, 2763
0, 2763
1, 2763
abs, 2763
acos, 2763
acosh, 2763
acot, 2763
acoth, 2763
acsc, 2763
acsch, 2763
approximate, 2763
asec, 2763
asech, 2763
asin, 2763
asinh, 2763
associates?, 2763
atan, 2763
atanh, 2763
ceiling, 2763
center, 2763
characteristic, 2763
charthRoot, 2763
coefficient, 2763
coerce, 2763
complete, 2763
conditionP, 2763
convert, 2763
cos, 2763
cosh, 2763
cot, 2763
coth, 2763
csc, 2763
csch, 2763
D, 2763
degree, 2763
denom, 2763
denominator, 2763
differentiate, 2763
divide, 2763
euclideanSize, 2763
eval, 2763
exp, 2763
expressIdealMember, 2763
exquo, 2763
extend, 2763
extendedEuclidean, 2763
factor, 2763
factorPolynomial, 2763
factorSquareFreePolynomial, 2763
floor, 2763
fractionPart, 2763
gcd, 2763
gcdPolynomial, 2763
hash, 2763
init, 2763
integrate, 2763
inv, 2763
latex, 2763
laurent, 2763
lcm, 2763
leadingCoefficient, 2763
leadingMonomial, 2763
log, 2763
map, 2763
max, 2763
min, 2763
monomial, 2763
monomial?, 2763
multiEuclidean, 2763
multiplyCoefficients, 2763
multiplyExponents, 2763
negative?, 2763
nextItem, 2763
nthRoot, 2763
numer, 2763
numerator, 2763
one?, 2763
order, 2763
patternMatch, 2763
pi, 2763
pole?, 2763
positive?, 2763
prime?, 2763
principalIdeal, 2763
random, 2763
rationalFunction, 2763
recip, 2763
reducedSystem, 2763
reductum, 2763
removeZeroes, 2763
retract, 2763

retractIfCan, 2763
sample, 2763
sec, 2763
sech, 2763
series, 2763
sign, 2763
sin, 2763
sinh, 2763
sizeLess?, 2763
solveLinearPolynomialEquation, 2763
sqrt, 2763
squareFree, 2763
squareFreePart, 2763
squareFreePolynomial, 2763
subtractIfCan, 2763
tan, 2763
tanh, 2763
taylor, 2763
taylorIfCan, 2763
taylorRep, 2763
terms, 2763
truncate, 2763
unit?, 2763
unitCanonical, 2763
unitNormal, 2763
variable, 2763
variables, 2763
wholePart, 2763
zero?, 2763
ULSCONS, 2770
-?, 2771
?<?, 2771
?<=?, 2771
?>?, 2771
?>=?, 2771
?**?, 2771
?*?, 2771
?+?, 2771
?-?, 2771
?.?, 2771
?/?, 2771
?=?, 2771
?^?, 2771
?~=?, 2771
?quo?, 2771
?rem?, 2771
0, 2771
1, 2771
abs, 2771
acos, 2771
acosh, 2771
acot, 2771
acoth, 2771
acsc, 2771
acsch, 2771
approximate, 2771
asec, 2771
asech, 2771
asin, 2771
asinh, 2771
associates?, 2771
atan, 2771
atanh, 2771
ceiling, 2771
center, 2771
characteristic, 2771
charthRoot, 2771
coefficient, 2771
coerce, 2771
complete, 2771
conditionP, 2771
convert, 2771
cos, 2771
cosh, 2771
cot, 2771
coth, 2771
csc, 2771
csch, 2771
D, 2771
degree, 2771
denom, 2771
denominator, 2771
differentiate, 2771
divide, 2771
euclideanSize, 2771
eval, 2771
exp, 2771
expressIdealMember, 2771
exquo, 2771
extend, 2771
extendedEuclidean, 2771
factor, 2771

factorPolynomial, 2771
factorSquareFreePolynomial, 2771
floor, 2771
fractionPart, 2771
gcd, 2771
gcdPolynomial, 2771
hash, 2771
init, 2771
integrate, 2771
inv, 2771
latex, 2771
laurent, 2771
lcm, 2771
leadingCoefficient, 2771
leadingMonomial, 2771
log, 2771
map, 2771
max, 2771
min, 2771
monomial, 2771
monomial?, 2771
multiEuclidean, 2771
multiplyCoefficients, 2771
multiplyExponents, 2771
negative?, 2771
nextItem, 2771
nthRoot, 2771
numer, 2771
numerator, 2771
one?, 2771
order, 2771
patternMatch, 2771
pi, 2771
pole?, 2771
positive?, 2771
prime?, 2771
principalIdeal, 2771
random, 2771
rationalFunction, 2771
recip, 2771
reducedSystem, 2771
reductum, 2771
removeZeroes, 2771
retract, 2771
retractIfCan, 2771
sample, 2771
sec, 2771
sech, 2771
series, 2771
sign, 2771
sin, 2771
sinh, 2771
sizeLess?, 2771
solveLinearPolynomialEquation, 2771
sqrt, 2771
squareFree, 2771
squareFreePart, 2771
squareFreePolynomial, 2771
subtractIfCan, 2771
tan, 2771
tanh, 2771
taylor, 2771
taylorIfCan, 2771
taylorRep, 2771
terms, 2771
truncate, 2771
unit?, 2771
unitCanonical, 2771
unitNormal, 2771
variable, 2771
variables, 2771
wholePart, 2771
zero?, 2771
unary?
BOP, 258
uncorrelated?
SD, 2540
unexpand
XPOLY, 2936
XRPOLY, 2951
union
CCLASS, 368
MSET, 1638
PATRES, 1906
SET, 2338
UNISEG, 2863
?..?, 2863
?=?, 2863
?SEGMENT, 2863
?~=?, 2863
BY, 2863
coerce, 2863

convert, 2863
expand, 2863
hash, 2863
hasHi, 2863
hi, 2863
high, 2863
incr, 2863
latex, 2863
lo, 2863
low, 2863
map, 2863
segment, 2863
unit
ALGSC, 15
DROPT, 596
FR, 756
GCNAALG, 1035
JORDAN, 209
LIE, 214
LSQM, 1424
unit?
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DIRRING, 551
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380

SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
unitCanonical
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DIRRING, 551
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SMTS, 2409

SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
unitNormal
ALGFF, 28
AN, 35
BINARY, 277
BPADIC, 242
BPADICRT, 247
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
DIRRING, 551
DMP, 560
DSMP, 529
EMR, 672
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FR, 756
FRAC, 956
GDMP, 1022
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HEXADEC, 1113
IAN, 1245
IFF, 1252
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
ISUPS, 1279
ITAYLOR, 1306
LAUPOL, 1390
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
ODR, 1825
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
RADFF, 2160
RADIX, 2172
RECLOS, 2203
ROMAN, 2293
SAE, 2368
SDPOL, 2352
SINT, 2380
SMP, 2391
SMTS, 2409
SULS, 2425
SUP, 2435

SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
unitNormalize
FR, 756
units
GRIMAGE, 1065
VIEW2d, 2739
unitVector
DIRPROD, 534
DPMM, 540
DPMO, 545
GMODPOL, 1029
HDP, 1143
ODP, 1783
SHDP, 2476
univariate
DMP, 560
DSMP, 529
EXPR, 694
GDMP, 1022
HDMP, 1150
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSMP, 1681
NSUP, 1696
ODPOL, 1818
POLY, 2044
SDPOL, 2352
SMP, 2391
SUP, 2435
SUPEXPR, 2449
UP, 2795
UnivariateFormalPowerSeries, 2756
UnivariateLaurentSeries, 2762
UnivariateLaurentSeriesConstructor, 2770
UnivariatePolynomial, 2794
univariatePolynomial
SUTS, 2464
UFPS, 2757
UTS, 2844
UTSZ, 2854
UnivariatePuiseuxSeries, 2800
UnivariatePuiseuxSeriesConstructor, 2808
UnivariatePuiseuxSeriesWithExponentialSingularity, 2819
UnivariateSkewPolynomial, 2839
UnivariateTaylorSeries, 2844
UnivariateTaylorSeriesCZero, 2853
UniversalSegment, 2863
universe
CCLASS, 368
SET, 2338
unmakeSUP
MODMON, 1600
MYUP, 1663
NSUP, 1696
SUP, 2435
SUPEXPR, 2449
UP, 2795
unparse
INFORM, 1311
unravel
CARTEN, 342
UnVectorise
MODMON, 1600
UP, 2794
-?, 2795
?<?, 2795
?<=?, 2795
?>?, 2795
?>=?, 2795
?**?, 2795
?*?, 2795
?+?, 2795
?-?, 2795
?.?, 2795
?/?, 2795
?=?, 2795

?^?, 2795
?~=?, 2795
?quo?, 2795
?rem?, 2795
0, 2795
1, 2795
associates?, 2795
binomThmExpt, 2795
characteristic, 2795
charthRoot, 2795
coefficient, 2795
coefficients, 2795
coerce, 2795
composite, 2795
conditionP, 2795
content, 2795
convert, 2795
D, 2795
degree, 2795
differentiate, 2795
discriminant, 2795
divide, 2795
divideExponents, 2795
elt, 2795
euclideanSize, 2795
eval, 2795
expressIdealMember, 2795
exquo, 2795
extendedEuclidean, 2795
factor, 2795
factorPolynomial, 2795
factorSquareFreePolynomial, 2795
fmecg, 2795
gcd, 2795
gcdPolynomial, 2795
ground, 2795
ground?, 2795
hash, 2795
init, 2795
integrate, 2795
isExpt, 2795
isPlus, 2795
isTimes, 2795
karatsubaDivide, 2795
latex, 2795
lcm, 2795
leadingCoefficient, 2795
leadingMonomial, 2795
mainVariable, 2795
makeSUP, 2795
map, 2795
mapExponents, 2795
max, 2795
min, 2795
minimumDegree, 2795
monicDivide, 2795
monomial, 2795
monomial?, 2795
monomials, 2795
multiEuclidean, 2795
multiplyExponents, 2795
multivariate, 2795
nextItem, 2795
numberOfMonomials, 2795
one?, 2795
order, 2795
patternMatch, 2795
pomopo, 2795
prime?, 2795
primitiveMonomials, 2795
primitivePart, 2795
principalIdeal, 2795
pseudoDivide, 2795
pseudoQuotient, 2795
pseudoRemainder, 2795
recip, 2795
reducedSystem, 2795
reductum, 2795
resultant, 2795
retract, 2795
retractIfCan, 2795
sample, 2795
separate, 2795
shiftLeft, 2795
shiftRight, 2795
sizeLess?, 2795
solveLinearPolynomialEquation, 2795
squareFree, 2795
squareFreePart, 2795
squareFreePolynomial, 2795
subResultantGcd, 2795
subtractIfCan, 2795

totalDegree, 2795
unit?, 2795
unitCanonical, 2795
unitNormal, 2795
univariate, 2795
unmakeSUP, 2795
variables, 2795
vectorise, 2795
zero?, 2795
update
VIEW2d, 2739
upperCase
CCLASS, 368
CHAR, 359
ISTRING, 1218
STRING, 2575
upperCase?
CHAR, 359
UPXS, 2800
-?, 2801
?**?, 2801
?*?, 2801
?+?, 2801
?-?, 2801
?.?, 2801
?/?, 2801
?=?, 2801
?^?, 2801
?~=?, 2801
?quo?, 2801
?rem?, 2801
0, 2801
1, 2801
acos, 2801
acosh, 2801
acot, 2801
acoth, 2801
acsc, 2801
acsch, 2801
approximate, 2801
asec, 2801
asech, 2801
asin, 2801
asinh, 2801
associates?, 2801
atan, 2801
atanh, 2801
center, 2801
characteristic, 2801
charthRoot, 2801
coefficient, 2801
coerce, 2801
complete, 2801
cos, 2801
cosh, 2801
cot, 2801
coth, 2801
csc, 2801
csch, 2801
D, 2801
degree, 2801
differentiate, 2801
divide, 2801
euclideanSize, 2801
eval, 2801
exp, 2801
expressIdealMember, 2801
exquo, 2801
extend, 2801
extendedEuclidean, 2801
factor, 2801
gcd, 2801
gcdPolynomial, 2801
hash, 2801
integrate, 2801
inv, 2801
latex, 2801
laurent, 2801
laurentIfCan, 2801
laurentRep, 2801
lcm, 2801
leadingCoefficient, 2801
leadingMonomial, 2801
log, 2801
map, 2801
monomial, 2801
monomial?, 2801
multiEuclidean, 2801
multiplyExponents, 2801
nthRoot, 2801
one?, 2801
order, 2801

pi, 2801
pole?, 2801
prime?, 2801
principalIdeal, 2801
puiseux, 2801
rationalPower, 2801
recip, 2801
reductum, 2801
retract, 2801
retractIfCan, 2801
sample, 2801
sec, 2801
sech, 2801
series, 2801
sin, 2801
sinh, 2801
sizeLess?, 2801
sqrt, 2801
squareFree, 2801
squareFreePart, 2801
subtractIfCan, 2801
tan, 2801
tanh, 2801
terms, 2801
truncate, 2801
unit?, 2801
unitCanonical, 2801
unitNormal, 2801
variable, 2801
variables, 2801
zero?, 2801
UPXSCONS, 2808
-?, 2809
?**?, 2809
?*?, 2809
?+?, 2809
?-?, 2809
?.?, 2809
?/?, 2809
?=?, 2809
?^?, 2809
?~=?, 2809
?quo?, 2809
?rem?, 2809
0, 2809
1, 2809
acos, 2809
acosh, 2809
acot, 2809
acoth, 2809
acsc, 2809
acsch, 2809
approximate, 2809
asec, 2809
asech, 2809
asin, 2809
asinh, 2809
associates?, 2809
atan, 2809
atanh, 2809
center, 2809
characteristic, 2809
charthRoot, 2809
coefficient, 2809
coerce, 2809
complete, 2809
cos, 2809
cosh, 2809
cot, 2809
coth, 2809
csc, 2809
csch, 2809
D, 2809
degree, 2809
differentiate, 2809
divide, 2809
euclideanSize, 2809
eval, 2809
exp, 2809
expressIdealMember, 2809
exquo, 2809
extend, 2809
extendedEuclidean, 2809
factor, 2809
gcd, 2809
gcdPolynomial, 2809
hash, 2809
integrate, 2809
inv, 2809
latex, 2809
laurent, 2809
laurentIfCan, 2809

laurentRep, 2809
lcm, 2809
leadingCoefficient, 2809
leadingMonomial, 2809
log, 2809
map, 2809
monomial, 2809
monomial?, 2809
multiEuclidean, 2809
multiplyExponents, 2809
nthRoot, 2809
one?, 2809
order, 2809
pi, 2809
pole?, 2809
prime?, 2809
principalIdeal, 2809
puiseux, 2809
rationalPower, 2809
recip, 2809
reductum, 2809
retract, 2809
retractIfCan, 2809
sample, 2809
sec, 2809
sech, 2809
series, 2809
sin, 2809
sinh, 2809
sizeLess?, 2809
sqrt, 2809
squareFree, 2809
squareFreePart, 2809
subtractIfCan, 2809
tan, 2809
tanh, 2809
terms, 2809
truncate, 2809
unit?, 2809
unitCanonical, 2809
unitNormal, 2809
variable, 2809
variables, 2809
zero?, 2809
UPXSSING, 2819
-?, 2819
?**?, 2819
?*?, 2819
?+?, 2819
?-?, 2819
?/?, 2819
?=?, 2819
?^?, 2819
?~=?, 2819
0, 2819
1, 2819
associates?, 2819
binomThmExpt, 2819
characteristic, 2819
charthRoot, 2819
coefficient, 2819
coefficients, 2819
coerce, 2819
content, 2819
degree, 2819
dominantTerm, 2819
exquo, 2819
ground, 2819
ground?, 2819
hash, 2819
latex, 2819
leadingCoefficient, 2819
leadingMonomial, 2819
limitPlus, 2819
map, 2819
mapExponents, 2819
minimumDegree, 2819
monomial, 2819
monomial?, 2819
numberOfMonomials, 2819
one?, 2819
pomopo, 2819
primitivePart, 2819
recip, 2819
reductum, 2819
retract, 2819
retractIfCan, 2819
sample, 2819
subtractIfCan, 2819
unit?, 2819
unitCanonical, 2819
unitNormal, 2819

zero?, 2819
useNagFunctions
FEXPR, 917
UTS, 2844
-?, 2844
?**?, 2844
?*?, 2844
?+?, 2844
?-?, 2844
?.?, 2844
?=?, 2844
?^?, 2844
?~=?, 2844
0, 2844
1, 2844
acos, 2844
acosh, 2844
acot, 2844
acoth, 2844
acsc, 2844
acsch, 2844
approximate, 2844
asec, 2844
asech, 2844
asin, 2844
asinh, 2844
associates?, 2844
atan, 2844
atanh, 2844
center, 2844
characteristic, 2844
charthRoot, 2844
coefficient, 2844
coefficients, 2844
coerce, 2844
complete, 2844
cos, 2844
cosh, 2844
cot, 2844
coth, 2844
csc, 2844
csch, 2844
D, 2844
degree, 2844
differentiate, 2844
eval, 2844
evenlambert, 2844
exp, 2844
exquo, 2844
extend, 2844
generalLambert, 2844
hash, 2844
integrate, 2844
invmultisect, 2844
lagrange, 2844
lambert, 2844
latex, 2844
leadingCoefficient, 2844
leadingMonomial, 2844
log, 2844
map, 2844
monomial, 2844
monomial?, 2844
multiplyCoefficients, 2844
multiplyExponents, 2844
multisect, 2844
nthRoot, 2844
oddlambert, 2844
one?, 2844
order, 2844
pi, 2844
pole?, 2844
polynomial, 2844
quoByVar, 2844
recip, 2844
reductum, 2844
revert, 2844
sample, 2844
sec, 2844
sech, 2844
series, 2844
sin, 2844
sinh, 2844
sqrt, 2844
subtractIfCan, 2844
tan, 2844
tanh, 2844
terms, 2844
truncate, 2844
unit?, 2844
unitCanonical, 2844
unitNormal, 2844

univariatePolynomial, 2844
variable, 2844
variables, 2844
zero?, 2844
UTSZ, 2853
-?, 2854
?**?, 2854
?*?, 2854
?+?, 2854
?-?, 2854
?.?, 2854
?/?, 2854
?=?, 2854
?^?, 2854
?~=?, 2854
0, 2854
1, 2854
acos, 2854
acosh, 2854
acot, 2854
acoth, 2854
acsc, 2854
acsch, 2854
approximate, 2854
asec, 2854
asech, 2854
asin, 2854
asinh, 2854
associates?, 2854
atan, 2854
atanh, 2854
center, 2854
characteristic, 2854
charthRoot, 2854
coefficient, 2854
coefficients, 2854
coerce, 2854
complete, 2854
cos, 2854
cosh, 2854
cot, 2854
coth, 2854
csc, 2854
csch, 2854
D, 2854
degree, 2854
differentiate, 2854
eval, 2854
evenlambert, 2854
exp, 2854
exquo, 2854
extend, 2854
generalLambert, 2854
hash, 2854
integrate, 2854
invmultisect, 2854
lagrange, 2854
lambert, 2854
latex, 2854
leadingCoefficient, 2854
leadingMonomial, 2854
log, 2854
map, 2854
monomial, 2854
monomial?, 2854
multiplyCoefficients, 2854
multiplyExponents, 2854
multisect, 2854
nthRoot, 2854
oddlambert, 2854
one?, 2854
order, 2854
pi, 2854
pole?, 2854
polynomial, 2854
quoByVar, 2854
recip, 2854
reductum, 2854
revert, 2854
sample, 2854
sec, 2854
sech, 2854
series, 2854
sin, 2854
sinh, 2854
sqrt, 2854
subtractIfCan, 2854
tan, 2854
tanh, 2854
terms, 2854
truncate, 2854
unit?, 2854

unitCanonical, 2854
unitNormal, 2854
univariatePolynomial, 2854
variable, 2854
variables, 2854
zero?, 2854

value
ALIST, 221
BBTREE, 237
BSTREE, 287
BTOURN, 291
BTREE, 295
DLIST, 448
DSTREE, 522
ILIST, 1201
LIST, 1472
NSDPS, 1670
OSI, 1830
PENDTREE, 1911
QEQUAT, 2135
SPLNODE, 2479
SPLTREE, 2485
STREAM, 2550
TREE, 2710
var1Steps
DROPT, 596
var2Steps
DROPT, 596
VARIABLE, 2872
?=?, 2872
?~=?, 2872
coerce, 2872
hash, 2872
latex, 2872
variable, 2872
Variable, 2872
variable
EXPUPXS, 710
GSERIES, 1061
ISUPS, 1279
NSDPS, 1670
ODVAR, 1821
OVAR, 1803
QEQUAT, 2135
SDVAR, 2358
SEGBIND, 2330
SULS, 2425
SUPXS, 2455
SUTS, 2464
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
VARIABLE, 2872
variableName
GOPT, 1075
GOPT0, 1081
variables
DMP, 560
DSMP, 529
EXPR, 694
EXPUPXS, 710
FEXPR, 917
GDMP, 1022
GPOLSET, 1044
GSERIES, 1061
GTSET, 1054
HDMP, 1150
ISUPS, 1279
MODMON, 1600
MPOLY, 1650
MYEXPR, 1656
MYUP, 1663
NSDPS, 1670
NSMP, 1681
NSUP, 1696
ODPOL, 1818
PATTERN, 1894
POLY, 2044
REGSET, 2252
RGCHAIN, 2221
SDPOL, 2352
SMP, 2391
SMTS, 2409
SREGSET, 2502
SULS, 2425
SUP, 2435
SUPEXPR, 2449

SUPXS, 2455
SUTS, 2464
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UTS, 2844
UTSZ, 2854
WUTSET, 2895
varList
LEXP, 1403
LPOLY, 1415
LWORD, 1500
MAGMA, 1533
OFMONOID, 1795
PBWLB, 2020
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XRPOLY, 2951
vconcat
OUTFORM, 1834
VECTOR, 2877
-?, 2878
?<?, 2878
?<=?, 2878
?>?, 2878
?>=?, 2878
?*?, 2878
?+?, 2878
?-?, 2878
?.?, 2878
?=?, 2878
?~=?, 2878
#?, 2878
any?, 2878
coerce, 2878
concat, 2878
construct, 2878
convert, 2878
copy, 2878
copyInto, 2878
count, 2878
cross, 2878
delete, 2878
dot, 2878
elt, 2878
empty, 2878
empty?, 2878
entries, 2878
entry?, 2878
eq?, 2878
eval, 2878
every?, 2878
fill, 2878
find, 2878
first, 2878
hash, 2878
index?, 2878
indices, 2878
insert, 2878
latex, 2878
length, 2878
less?, 2878
magnitude, 2878
map, 2878
max, 2878
maxIndex, 2878
member?, 2878
members, 2878
merge, 2878
min, 2878
minIndex, 2878
more?, 2878
new, 2878
outerProduct, 2878
parts, 2878
position, 2878
qelt, 2878
qsetelt, 2878
reduce, 2878
remove, 2878
removeDuplicates, 2878
reverse, 2878
sample, 2878
select, 2878
setelt, 2878
size?, 2878
sort, 2878

sorted?, 2878
swap, 2878
vector, 2878
zero, 2878
Vector, 2877
vector
CDFVEC, 419
VECTOR, 2878
Vectorise
MODMON, 1600
vectorise
MODMON, 1600
MYUP, 1663
NSUP, 1696
PACOFF, 2102
PACRAT, 2112
SUP, 2435
SUPEXPR, 2449
UP, 2795
vertConcat
CDFMAT, 413
DFMAT, 587
DHMATRIX, 479
IMATRIX, 1208
MATRIX, 1591
VIEW2D, 2738
VIEW2d
?=?, 2739
?~=?, 2739
axes, 2739
close, 2739
coerce, 2739
connect, 2739
controlPanel, 2739
dimensions, 2739
getGraph, 2739
getPickedPoints, 2739
graphs, 2739
graphState, 2739
graphStates, 2739
hash, 2739
key, 2739
latex, 2739
makeViewport2D, 2739
move, 2739
options, 2739
points, 2739
putGraph, 2739
region, 2739
reset, 2739
resize, 2739
scale, 2739
show, 2739
title, 2739
translate, 2739
units, 2739
update, 2739
viewport2D, 2739
write, 2739
VIEW3D, 2679
?=?, 2679
?~=?, 2679
axes, 2679
clipSurface, 2679
close, 2679
coerce, 2679
colorDef, 2679
controlPanel, 2679
diagonals, 2679
dimensions, 2679
drawStyle, 2679
eyeDistance, 2679
hash, 2679
hitherPlane, 2679
intensity, 2679
key, 2679
latex, 2679
lighting, 2679
makeViewport3D, 2679
modifyPointData, 2679
move, 2679
options, 2679
outlineRender, 2679
perspective, 2679
reset, 2679
resize, 2679
rotate, 2679
showClipRegion, 2679
showRegion, 2679
subspace, 2679
title, 2679
translate, 2679

viewDeltaXDefault, 2679
viewDeltaYDefault, 2679
viewPhiDefault, 2679
viewpoint, 2679
viewport3D, 2679
viewThetaDefault, 2679
viewZoomDefault, 2679
write, 2679
zoom, 2679
viewDeltaXDefault
VIEW3D, 2679
viewDeltaYDefault
VIEW3D, 2679
viewPhiDefault
VIEW3D, 2679
viewpoint
DROPT, 596
VIEW3D, 2679
viewport2D
VIEW2d, 2739
viewport3D
VIEW3D, 2679
viewThetaDefault
VIEW3D, 2679
viewZoomDefault
VIEW3D, 2679
VOID, 2881
coerce, 2881
void, 2881
Void, 2881
void
VOID, 2881
vspace
OUTFORM, 1834

weight
BOP, 258
DSMP, 529
ODPOL, 1818
ODVAR, 1821
SDPOL, 2352
SDVAR, 2358
WeightedPolynomials, 2884
weights
DSMP, 529
ODPOL, 1818
SDPOL, 2352
whatInfinity
ORDCOMP, 1777
whileLoop
FC, 902
wholePart
BINARY, 277
BPADICRT, 247
CONTFRAC, 432
DECIMAL, 453
DFLOAT, 575
EXPEXPAN, 682
FLOAT, 879
FRAC, 956
HEXADEC, 1113
MFLOAT, 1516
PADICRAT, 1852
PADICRC, 1857
PFR, 1880
RADIX, 2172
SULS, 2425
ULS, 2763
ULSCONS, 2771
wholeRadix
RADIX, 2172
wholeRagits
RADIX, 2172
width
INTRVL, 1352
OUTFORM, 1834
withPredicates
PATTERN, 1894
wordInGenerators
PERMGRP, 1926
wordInStrongGenerators
PERMGRP, 1926
wordsForStrongGenerators
PERMGRP, 1926
WP, 2884
-?, 2885
?**?, 2885
?*?, 2885
?+?, 2885
?-?, 2885
?/?, 2885
?=?, 2885

?^?, 2885
?~=?, 2885
0, 2885
1, 2885
changeWeightLevel, 2885
characteristic, 2885
coerce, 2885
hash, 2885
latex, 2885
one?, 2885
recip, 2885
sample, 2885
subtractIfCan, 2885
zero?, 2885
writable?
FNAME, 780
write
VIEW2d, 2739
VIEW3D, 2679
WUTSET, 2894
?=?, 2895
?~=?, 2895
#?, 2895
algebraic?, 2895
algebraicVariables, 2895
any?, 2895
autoReduced?, 2895
basicSet, 2895
characteristicSerie, 2895
characteristicSet, 2895
coerce, 2895
coHeight, 2895
collect, 2895
collectQuasiMonic, 2895
collectUnder, 2895
collectUpper, 2895
construct, 2895
convert, 2895
copy, 2895
count, 2895
degree, 2895
empty, 2895
empty?, 2895
eq?, 2895
eval, 2895
every?, 2895
extend, 2895
extendIfCan, 2895
find, 2895
first, 2895
hash, 2895
headReduce, 2895
headReduced?, 2895
headRemainder, 2895
infRittWu?, 2895
initiallyReduce, 2895
initiallyReduced?, 2895
initials, 2895
last, 2895
latex, 2895
less?, 2895
mainVariable?, 2895
mainVariables, 2895
map, 2895
medialSet, 2895
member?, 2895
members, 2895
more?, 2895
mvar, 2895
normalized?, 2895
parts, 2895
quasiComponent, 2895
reduce, 2895
reduceByQuasiMonic, 2895
reduced?, 2895
remainder, 2895
remove, 2895
removeDuplicates, 2895
removeZero, 2895
rest, 2895
retract, 2895
retractIfCan, 2895
rewriteIdealWithHeadRemainder, 2895
rewriteIdealWithRemainder, 2895
rewriteSetWithReduction, 2895
roughBase?, 2895
roughEqualIdeals?, 2895
roughSubIdeal?, 2895
roughUnitIdeal?, 2895
sample, 2895
select, 2895
size?, 2895

sort, 2895
stronglyReduce, 2895
stronglyReduced?, 2895
triangular?, 2895
trivialIdeal?, 2895
variables, 2895
zeroSetSplit, 2895
zeroSetSplitIntoTriangularSystems, 2895
WuWenTsunTriangularSet, 2894

XDistributedPolynomial, 2905
XDPOLY, 2905
-?, 2905
?**?, 2905
?*?, 2905
?+?, 2905
?-?, 2905
?=?, 2905
?^?, 2905
?~=?, 2905
0, 2905
1, 2905
characteristic, 2905
coef, 2905
coefficient, 2905
coefficients, 2905
coerce, 2905
constant, 2905
constant?, 2905
degree, 2905
hash, 2905
latex, 2905
leadingCoefficient, 2905
leadingMonomial, 2905
leadingTerm, 2905
listOfTerms, 2905
lquo, 2905
map, 2905
maxdeg, 2905
mindeg, 2905
mindegTerm, 2905
mirror, 2905
monom, 2905
monomial?, 2905
monomials, 2905
numberOfMonomials, 2905
one?, 2905
quasiRegular, 2905
quasiRegular?, 2905
recip, 2905
reductum, 2905
retract, 2905
retractIfCan, 2905
rquo, 2905
sample, 2905
sh, 2905
subtractIfCan, 2905
trunc, 2905
varList, 2905
zero?, 2905
xor
BITS, 299
BOOLEAN, 307
IBITS, 1169
SINT, 2380
XPBWPOLY, 2925
XPBWPOLYL
-?, 2925
?**?, 2925
?*?, 2925
?+?, 2925
?-?, 2925
?=?, 2925
?^?, 2925
?~=?, 2925
0, 2925
1, 2925
characteristic, 2925
coef, 2925
coefficient, 2925
coefficients, 2925
coerce, 2925
constant, 2925
constant?, 2925
degree, 2925
exp, 2925
hash, 2925
latex, 2925
leadingCoefficient, 2925
leadingMonomial, 2925
leadingTerm, 2925
LiePolyIfCan, 2925

listOfTerms, 2925
log, 2925
lquo, 2925
map, 2925
maxdeg, 2925
mindeg, 2925
mindegTerm, 2925
mirror, 2925
monom, 2925
monomial?, 2925
monomials, 2925
numberOfMonomials, 2925
one?, 2925
product, 2925
quasiRegular, 2925
quasiRegular?, 2925
recip, 2925
reductum, 2925
retract, 2925
retractIfCan, 2925
rquo, 2925
sample, 2925
sh, 2925
subtractIfCan, 2925
trunc, 2925
varList, 2925
zero?, 2925
XPBWPolynomial, 2925
XPOLY, 2936
-?, 2936
?**?, 2936
?*?, 2936
?+?, 2936
?-?, 2936
?=?, 2936
?^?, 2936
?~=?, 2936
0, 2936
1, 2936
characteristic, 2936
coef, 2936
coerce, 2936
constant, 2936
constant?, 2936
degree, 2936
expand, 2936
hash, 2936
latex, 2936
lquo, 2936
map, 2936
maxdeg, 2936
mindeg, 2936
mindegTerm, 2936
mirror, 2936
monom, 2936
monomial?, 2936
one?, 2936
quasiRegular, 2936
quasiRegular?, 2936
recip, 2936
RemainderList, 2936
retract, 2936
retractIfCan, 2936
rquo, 2936
sample, 2936
sh, 2936
subtractIfCan, 2936
trunc, 2936
unexpand, 2936
varList, 2936
zero?, 2936
XPolynomial, 2936
XPolynomialRing, 2945
XPR, 2945
-?, 2945
?**?, 2945
?*?, 2945
?+?, 2945
?-?, 2945
?=?, 2945
?^?, 2945
?~=?, 2945
#?, 2945
0, 2945
1, 2945
characteristic, 2945
coef, 2945
coefficient, 2945
coefficients, 2945
coerce, 2945
constant, 2945
constant?, 2945

hash, 2945
latex, 2945
leadingCoefficient, 2945
leadingMonomial, 2945
leadingTerm, 2945
listOfTerms, 2945
map, 2945
maxdeg, 2945
mindeg, 2945
monom, 2945
monomial?, 2945
monomials, 2945
numberOfMonomials, 2945
one?, 2945
quasiRegular, 2945
quasiRegular?, 2945
recip, 2945
reductum, 2945
retract, 2945
retractIfCan, 2945
sample, 2945
subtractIfCan, 2945
zero?, 2945
xRange
ACPLOT, 1958
PLOT, 1995
PLOT3D, 2008
XRecursivePolynomial, 2951
XRPOLY, 2951
-?, 2951
?**?, 2951
?*?, 2951
?+?, 2951
?-?, 2951
?=?, 2951
?^?, 2951
?~=?, 2951
0, 2951
1, 2951
characteristic, 2951
coef, 2951
coerce, 2951
constant, 2951
constant?, 2951
degree, 2951
expand, 2951
hash, 2951
latex, 2951
lquo, 2951
map, 2951
maxdeg, 2951
mindeg, 2951
mindegTerm, 2951
mirror, 2951
monom, 2951
monomial?, 2951
one?, 2951
quasiRegular, 2951
quasiRegular?, 2951
recip, 2951
RemainderList, 2951
retract, 2951
retractIfCan, 2951
rquo, 2951
sample, 2951
sh, 2951
subtractIfCan, 2951
trunc, 2951
unexpand, 2951
varList, 2951
zero?, 2951

yCoordinates
ALGFF, 28
RADFF, 2160
yellow
COLOR, 394
yRange
ACPLOT, 1958
PLOT, 1995
PLOT3D, 2008

zag
OUTFORM, 1834
zero
CDFMAT, 413
CDFVEC, 419
DFMAT, 587
DFVEC, 593
DHMATRIX, 479
IMATRIX, 1208
IVECTOR, 1229

MATRIX, 1591
POINT, 2026
VECTOR, 2878
zero?
ALGFF, 28
ALGSC, 15
AN, 35
ANTISYM, 40
BINARY, 277
BPADIC, 242
BPADICRT, 247
CARD, 318
CLIF, 388
COMPLEX, 406
CONTFRAC, 432
DECIMAL, 453
DERHAM, 517
DFLOAT, 575
DIRPROD, 534
DIRRING, 551
DIV, 563
DMP, 560
DPMM, 540
DPMO, 545
DSMP, 529
EMR, 672
EQ, 661
EXPEXPAN, 682
EXPR, 694
EXPUPXS, 710
FAGROUP, 975
FAMONOID, 978
FDIV, 783
FEXPR, 917
FF, 790
FFCG, 795
FFCGP, 805
FFCGX, 800
FFNB, 830
FFNBP, 842
FFNBX, 836
FFP, 821
FFX, 816
FLOAT, 879
FM, 983
FM1, 987
FNLA, 997
FR, 756
FRAC, 956
FSERIES, 948
GCNAALG, 1035
GDMP, 1022
GMODPOL, 1029
GSERIES, 1061
HACKPI, 1944
HDMP, 1150
HDP, 1143
HELLFDIV, 1153
HEXADEC, 1113
IAN, 1245
IDEAL, 2047
IDPAG, 1172
IDPAM, 1176
IDPOAM, 1182
IDPOAMS, 1185
IFAMON, 1255
IFF, 1252
INDE, 1187
INT, 1330
INTRVL, 1352
IPADIC, 1262
IPF, 1271
IR, 1343
ISUPS, 1279
ITAYLOR, 1306
JORDAN, 209
LA, 1488
LAUPOL, 1390
LIE, 214
LO, 1491
LODO, 1437
LODO1, 1447
LODO2, 1459
LPOLY, 1415
LSQM, 1424
MCMPLX, 1511
MFLOAT, 1516
MINT, 1525
MODFIELD, 1606
MODMON, 1600
MODOP, 1615, 1771
MODRING, 1609

MPOLY, 1650
MRING, 1626
MYEXPR, 1656
MYUP, 1663
NNI, 1706
NSDPS, 1670
NSMP, 1681
NSUP, 1696
OCT, 1731
ODP, 1783
ODPOL, 1818
ODR, 1825
OMLO, 1773
ONECOMP, 1744
ORDCOMP, 1777
ORESUP, 2460
OREUP, 2840
OWP, 1828
PACOFF, 2102
PACRAT, 2112
PADIC, 1847
PADICRAT, 1852
PADICRC, 1857
PF, 2071
PFR, 1880
POLY, 2044
PR, 2058
PRODUCT, 2079
PRTITION, 1889
QFORM, 2120
QUAT, 2133
RADFF, 2160
RADIX, 2172
RECLOS, 2203
RESRING, 2262
RMATRIX, 2212
ROIRC, 2276
ROMAN, 2293
SAE, 2368
SD, 2540
SDPOL, 2352
SHDP, 2476
SINT, 2380
SMP, 2391
SMTS, 2409
SQMATRIX, 2515
SULS, 2425
SUP, 2435
SUPEXPR, 2449
SUPXS, 2455
SUTS, 2464
SYMPOLY, 2622
TS, 2639
UFPS, 2757
ULS, 2763
ULSCONS, 2771
UP, 2795
UPXS, 2801
UPXSCONS, 2809
UPXSSING, 2819
UTS, 2844
UTSZ, 2854
WP, 2885
XDPOLY, 2905
XPBWPOLYL, 2925
XPOLY, 2936
XPR, 2945
XRPOLY, 2951
ZMOD, 1336
zeroDim?
IDEAL, 2047
zeroMatrix
M3D, 2672
zeroOf
AN, 35
EXPR, 694
IAN, 1245
zeroSetSplit
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
zeroSetSplitIntoTriangularSystems
GTSET, 1054
REGSET, 2252
RGCHAIN, 2221
SREGSET, 2502
WUTSET, 2895
zerosOf
AN, 35
EXPR, 694

IAN, 1245
zeta
DIRRING, 551
ZMOD, 1335
-?, 1336
?**?, 1336
?*?, 1336
?+?, 1336
?-?, 1336
?=?, 1336
?^?, 1336
?~=?, 1336
0, 1336
1, 1336
characteristic, 1336
coerce, 1336
convert, 1336
hash, 1336
index, 1336
init, 1336
latex, 1336
lookup, 1336
nextItem, 1336
one?, 1336
random, 1336
recip, 1336
sample, 1336
size, 1336
subtractIfCan, 1336
zero?, 1336
zoom
PLOT, 1995
PLOT3D, 2008
VIEW3D, 2679
zRange
PLOT3D, 2008